

ETSI TS 100 531 V8.0.0 (2000-04)

Technical Specification

Digital cellular telecommunications system (Phase 2+); Discontinuous Reception (DRX) in the GSM system (GSM 03.13 version 8.0.0 Release 1999)

GSM®

GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS



Reference

RTS/SMG-020313Q8

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights.....	4
Foreword	4
1 Scope	5
2 References	5
3 Abbreviations	5
4 Overview of discontinuous reception	6
5 MSC functions	6
6 BSS functions.....	6
7 MS functions	7
8 Support via the air interface	7
9 Operational aspects	7
Annex A (informative): Change Request History	8
History	9

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the Special Mobile Group (SMG).

The present document provides a system wide view of the operation of discontinuous reception within the digital cellular telecommunications system (Phase 2/Phase 2+).

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 8.x.y

where:

- 8 indicates Release 1999 of GSM Phase 2+.
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

1 Scope

The present document provides a system wide view of the operation of discontinuous reception on the GSM system.

The support of DRX is mandatory in GSM PLMNs.

The detailed coding and procedural details are defined in the relevant Technical Specifications dealing with the specific interfaces that are involved, for instance GSM 08.08 and GSM 04.08. Reference is also made to the framing on the air interface which is defined in Technical Specification GSM 05.02.

The present document gives an overview of the implementation of discontinuous reception DRX within the GSM system, the actions required at MSC, BSS, and MS, the support of the facility via the air interface, and some operational aspects of the facility.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1999 document, references to GSM documents are for Release 1999 versions (version 8.x.y).

- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 04.08: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [3] GSM 05.02: "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [4] GSM 08.02: "Digital cellular telecommunications system (Phase 2+); Base Station System - Mobile-services Switching Centre (BSS - MSC) interface Interface principles".
- [5] GSM 08.08: "Digital cellular telecommunications system (Phase 2+); Mobile Switching Centre - Base Station System (MSC - BSS) interface Layer 3 specification".
- [6] GSM 03.68: "Digital cellular telecommunications system (Phase 2+); Voice Group Call Service (VGCS) Stage 2".
- [7] GSM 03.69: "Digital cellular telecommunications system (Phase 2+); Voice Broadcast Service (VBS) Stage 2".

3 Abbreviations

Abbreviations used in the present document are listed in GSM 01.04.

4 Overview of discontinuous reception

DRX is a technique that allows the mobile station to power down significant amounts of its internal circuitry for a high percentage of the time when it is in the idle mode.

It also ensures that the MS is aware of exactly when page requests for it may be transmitted and it can then therefore schedule other tasks such that it avoids the problem of not decoding valid page requests transmitted by the network in the idle mode periods.

The technique works by dividing the MSs within a cell into a set of groups. The group in which an MS resides is then known locally at both the MS and the BSS. All paging requests to each group are then scheduled and sent at a particular time which is derived from the TDMA frame number in conjunction with the IMSI of the MS and some BCCH transmitted data.

Thus both the BSS and the MS know when relevant page requests will be sent and the MS can power down for the period when it knows that page requests will not occur.

The page request can contain the IMSI and may contain the TMSI in order to identify the MS concerned. The IMSI is however always used to identify the paging population. Paging by means of the IMEI is for further study.

Mechanisms for the application of DRX for the voice group call and voice broadcast services are defined in stage 2 descriptions in GSM 03.68 [6] and GSM 03.69 [7], respectively.

5 MSC functions

The MSC is almost transparent to DRX, since it has no real time knowledge of the absolute frame numbers on the air interface (refer to Technical Specification GSM 08.02).

It should be noted, however, that the MSC does define which cells are to be paged in order to locate a particular MS. Normally this will be a location area.

The MSC therefore constructs page requests and sends them to a specific set of BSSs. Each page request always includes the IMSI. The timer to detect non receipt of a page response may require alteration depending upon the number of page groups that are involved. If this is the case, then the timer will be set by O and M command at the same time as the number of paging groups at the cell is altered.

6 BSS functions

At the BSS page requests are received. It is implicit (single cell BSSs) or explicit (multi cell BSSs) within the page requests from the MSC to which cell the page request is destined (Technical Specifications GSM 08.08 and GSM 08.02 refers).

The BSS analyses the IMSI in order to derive the page group of the MS involved. The air interface page request is then constructed and transmitted in the appropriate TDMA burst. If the page request includes a TMSI and IMSI then the IMSI is used to derive the page population and the TMSI is inserted into the actual page request message. The scheduling of the page requests is therefore completely controlled by the BSS.

The relationship between paging group and TDMA burst, and IMSI and paging group is given in Technical Specification GSM 05.02.

The exact scheduling mechanism used at the BSS is not defined in the present document.

However the BSS may set the "page mode" bits as described in Technical Specification GSM 04.08. This can be used to optimise paging load and reduce missed page requests during system reconfiguration.

7 MS functions

The MS shall derive its paging group as defined in Technical Specification GSM 05.02.

The MS shall interpret all paging requests in its paging group according to the paging mode bits as described in Technical Specification GSM 04.08.

8 Support via the air interface

The BCCH and paging channel messages are defined in Technical Specification GSM 04.08. Technical Specification GSM 05.02 defines the algorithms which enable an MS to know the exact frame and burst when page requests relevant to it might be transmitted.

9 Operational aspects

There will be occasions when it is necessary to alter the parameters of cell such that the paging group of the MS may alter.

If (referring to Technical Specification GSM 05.02) any of the parameters BS_AG_BLK_RES, BS_CC_CHANS_COMB, BS_CC_CHANS or BS_PA_MFRMS have to be altered, then the period when page requests may be lost can be minimised for example by:

Firstly setting the page mode to "page reorganisation" in all page requests on the affected cell for the exact duration of one paging period (i.e. BS_PA_MFRMS multiframes). At the completion of this announcement period, the BCCH parameters are set to the new values and the BSS starts scheduling the paging messages according to the new parameters. The page mode is reset to any of the values "normal mode" or "extended mode" as required.

Annex A (informative): Change Request History

Change history					
SMG No.	TDoc. No.	CR. No.	Section affected	New version	Subject/Comments
SMG#07				4.0.4	ETSI Publication
SMG#17				5.0.0	Release 1996 version
SMG#27				6.0.0	Release 1997 version
SMG#29				7.0.0	Release 1998 version
SMG#31				8.0.0	Release 1999 version

History

Document history		
V8.0.0	April 2000	Publication