

ETSI TS 100 587 V8.0.1 (2002-05)

Technical Specification

Digital cellular telecommunications system (Phase 2+); General Aspects on the BSS-MSC Interface (3GPP TS 08.01 version 8.0.1 Release 1999)



Reference

RTS/TSGG-020801v801

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
0 Introduction	5
0.1 Scope	5
0.2 References	5
0.3 Definitions and abbreviations.....	6
1 A-Interface capabilities	7
2 A-Interface specification objectives.....	7
3 A-Interface characteristics.....	7
4 Other specifications on the MSC-BSS interface	7
4.1 Technical Specification 3GPP TS 08.02 Interface Principles	7
4.2 Technical Specification 3GPP TS 08.04 Layer 1 - Specification.....	8
4.3 Technical Specification 3GPP TS 08.06 Signalling Transport Mechanism - Specification.....	8
4.4 Technical Specification 3GPP TS 08.08 Layer 3 Specification	8
4.5 Technical Specification 3GPP TS 08.20 Rate adaption on the BSS-MSC interface	9
Annex A (informative): Change History	10
History	11

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The present document specifies or references procedures used on the Base Station System (BSS) to Serving GPRS Support Node (SGSN) interface for control of GSM packet data services within the digital cellular telecommunications system (Phase 2+).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

x the first digit:

- 1 presented to TSG for information;
- 2 presented to TSG for approval;
- 3 or greater indicates TSG approved document under change control.

y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.

z the third digit is incremented when editorial only changes have been incorporated in the document.

0 Introduction

0.1 Scope

The present document is an introduction to the 3GPP TS 08.0x series of Technical Specifications and deals with the definition of the base station system (BSS) to mobile switching centre (MSC) (referred to as the A-interface) defined for the GSM system.

It also introduces Technical Specifications in the 3GPP TS 08.20 series, dealing with the support of data services on this interface.

The present document gives an overview of the content of the 3GPP TS 08.0x and 3GPP TS 08.20 series of Technical Specifications explaining how the detailed content of the Technical Specifications is partitioned and how the Technical Specifications can be used to support a full BSS-MSC interface.

0.2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 01.04: "Abbreviations and acronyms".
- [2] Void.
- [3] Void.
- [4] Void.
- [5] Void.
- [6] Void.
- [7] Void.
- [8] Void.
- [9] Void.
- [10] Void.
- [11] Void.
- [12] Void.
- [13] Void.
- [14] Void.
- [15] Void.
- [16] Void.
- [17] Void.

- [18] Void.
- [19] Void.
- [20] Void.
- [21] Void.
- [22] Void.
- [23] Void.
- [24] Void.
- [25] 3GPP TS 04.08: "Mobile radio interface layer 3 specification".
- [26] 3GPP TS 04.21: "Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [27] 3GPP TS 08.02: "Base Station System - Mobile-services Switching Centre (BSS - MSC) interface Interface principles".
- [28] 3GPP TS 08.04: "Base Station System - Mobile-services Switching Centre (BSS - MSC) interface Layer 1 specification".
- [29] 3GPP TS 08.06: "Signalling transport mechanism specification for the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [30] 3GPP TS 08.08: "Mobile Switching Centre - Base Station System (MSC - BSS) interface Layer 3 specification".
- [31] 3GPP TS 08.20: "Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [32] Void.
- [33] Void.
- [34] Void.
- [35] Void.
- [36] Void.
- [37] Void.
- [38] Void.
- [39] Void.
- [40] Void.
- [41] Void.
- [42] Void.
- [43] Void.
- [44] Void.
- [45] Void.
- [46] Void.

0.3 Definitions and abbreviations

Abbreviations used in this specification are listed in 3GPP TS 01.04.

1 A-Interface capabilities

The BSS-MSC interface shall be capable of supporting all the services offered to GSM users and subscribers. In addition it also allows for the allocation of suitable radio resources within the PLMN, and the operation and maintenance of those resources.

2 A-Interface specification objectives

The MSC to BSS interface specifications shall allow the following:

- i) Connection of various manufacturers BSSs to the same MSC;
- ii) The use of several manufacturers MSCs to the same type of BSS;
- iii) The use of the same BSS in any PLMN;
- iv) The use of the same MSC in any PLMN;
- v) The separate evolution of MSC and BSS technology, and;
- vi) The separate evolution of O&M facilities;
- vii) Evolution towards lower speech coding rates;
- viii) Support of all services defined in the 3GPP TS 02 series of Technical Specifications.

3 A-Interface characteristics

The interface is defined to be at the boundary of the MSC.

The MSC to BSS interface is specified by a set of characteristics, including:

- i) Physical and electromagnetic parameters;
- ii) Channel structures;
- iii) Network operating procedures;
- iv) Operation and Maintenance information support.

The definition of the MSC to BSS interface follows a layered approach similar to that in the ISDN. Layer 3 is for the most part based on Technical Specification 3GPP TS 04.08 with additional procedures added for the control of radio resources and the identification of transactions using the SCCP. Layer 2 is based on the signalling system No.7 (SS No.7) Message Transfer Part (MTP). Layer 1 is either digital (at 2 048 kbit/s, based on CCITT Rec. G703 clause 6) or analogue with the data being passed by the use of modems (this latter case is a national option).

4 Other specifications on the MSC-BSS interface

The full structure of the Technical Specifications specifying the MSC to BSS link are as follows.

4.1 Technical Specification 3GPP TS 08.02 Interface Principles

The present document deals with the functional split between the BSS and the MSC. This functional split is then supported by the other Technical Specifications in the 3GPP TS 08-series.

Technical Specification 3GPP TS 08.02 also contains some information on the placement of transcoders/rate adapters, these being functionally part of the BSS though a degree of freedom is allowed in their geographical location.

Lastly Technical Specification 3GPP TS 08.02 explains the use of transparent and non transparent signalling information across the interface. The key point is that the majority of call related signalling from the MS is passed in a fairly transparent way through the BSS.

4.2 Technical Specification 3GPP TS 08.04 Layer 1 - Specification

The present document defines the physical layer at the BSS-MSC interface point. The physical interface chosen is a 2Mbits/s (32*64kbits/s) interface according to the standard CCITT recommendations.

The speech coding called up in the present document is standard A-law, coding of the traffic bit streams for data calls is dealt with in Technical Specifications 3GPP TS 04.21 and 3GPP TS 08.20.

4.3 Technical Specification 3GPP TS 08.06 Signalling Transport Mechanism - Specification

In order to pass the signalling information between BSS and MSC some reliable transport mechanism has to be used. The basis of the transport mechanism is an internationally agreed protocol known as signalling system No.7.

Several services are required from this protocol but two key requirements are that messages can be transferred between the BSS and MSC without corruption, and secondly that a transaction with a particular mobile can be identified.

The correct transfer of messages without corruption is handled by the "Message Transfer Part" of SS No.7 and this is documented in Technical Specification 3GPP TS 08.06 which is an exceptions document to the CCITT specification. The subset so formed is designed so that it is compatible with a "full" MTP such as might be provided at an MSC.

The identification of the transaction involved implies some form of logical connection. This is achieved by using the signalling connection control part (SCCP) of SS No.7. Again a minimum subset is formed in order to ease implementation.

4.4 Technical Specification 3GPP TS 08.08 Layer 3 Specification

In the present document the application parts are described. There are two currently identified in the BSS to MSC interface protocol, these are the:

- BSSOMAP;
- BSSAP.

The BSSAP is further subdivided into two subprotocols, the BSSMAP and the DTAP.

The BSSMAP and DTAP are fully defined, the BSSOMAP is only supported in terms of a signalling transport ability.

The DTAP text is split between Technical Specifications 3GPP TS 08.06 and 3GPP TS 08.08 but the text in 3GPP TS 08.08 defines which layer 3 air interface messages are passed transparently through the BSS and which are analysed at the BSS.

The BSSMAP (base station system management application part) is that part of the protocol responsible for all aspects of the radio resource handling at the BSS. The text is structured as a set of procedures which are defined separately and can be employed as felt appropriate by the operator/manufacturer to meet the requirements of the application in which it is being used. The procedures themselves can be driven in different modes depending upon the input parameters received from the MSC or sent from the OMC.

The BSSOMAP (base station system operation and maintenance application part) supports all of the O and M communications for the BSS with either the MSC or the BSS. The actual detailed protocol at layer 3 is defined in the 3GPP TS 12-series of Technical Specifications.

4.5 Technical Specification 3GPP TS 08.20 Rate adaption on the BSS-MSC interface

The present document describes the means by which the radio interface data rates are adapted to the 64 kbits/s needed at the MSC and vice versa, down to the bit level.

Annex A (informative): Change History

Date / Meeting	Tdoc	CR	Subject	New ver
			Creation of R99 version	8.0.0
May 2002	-	-	Updated to 3GPP TS style format. Reference clause cleaned up	8.0.1

History

Document history		
V8.0.0	June 2000	Publication
V8.0.1	May 2002	Publication