

TS 100 594 V6.0.0 (1999-04)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Base Station Controller - Base Transceiver Station
(BSC - BTS) interface;
Layer 1 structure of physical circuits
(GSM 08.54 version 6.0.0 Release 1997)**



GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

ETSI 

Reference

DTS/SMG-030854Q6 (5i003003.PDF)

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights.....4

Foreword4

1 Scope.....5

2 References.....5

3 Abbreviations.....6

4 Layer 1 specification.....6

Annex A (informative): Change Request History7

History8

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the Special Mobile Group (SMG).

The present document defines the structure of the physical layer (layer 1) of the BSC - BTS/TRX interface for supporting traffic channels and control channels within the digital cellular telecommunications system (Phase 2/Phase 2+).

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 6.x.y

where:

- 6 indicates Release 1997 of GSM Phase 2+
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

1 Scope

The use and general aspects of the A-bis interface are given in Technical Specification GSM 08.51.

The present document defines the structure of the physical layer (layer 1) of the BSC - BTS/TRX interface for supporting traffic channels and control channels. Use of the physical layer for supporting link protocol is covered in Technical Specification GSM 08.56.

The physical layer is the lowest layer in the OSI Reference Model and it supports all functions required for transmission of bit streams on the physical medium.

For the present document only digital transmission will be considered, the use of analogue transmission is a national concern.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1997 document, references to GSM documents are for Release 1997 versions (version 6.x.y).

- [1] GSM 01.04: "European digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 08.20: "European digital cellular telecommunications system (Phase 2+); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [3] GSM 08.51: "European digital cellular telecommunications system (Phase 2+); Base Station Controller - Base Transceiver Station (BSC - BTS) interface General aspects".
- [4] GSM 08.56: "European digital cellular telecommunications system (Phase 2+); Base Station Controller - Base Transceiver Station (BSC - BTS) interface Layer 2 specification".
- [5] GSM 08.60 (ETS 300 597): "European digital cellular telecommunications system (Phase 2+); Inband control of remote transcoders and rate adaptors".
- [6] GSM 08.61: "European digital cellular telecommunications system (Phase 2+); Inband control of remote transcoders and rate adaptors (half rate)".
- [7] CCITT Recommendation G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
- [8] CCITT Recommendation G.705: "Characteristics required to terminate digital links on a digital exchange".
- [9] CCITT Recommendation G.711: "Pulse code modulation (PCM) of voice frequencies".
- [10] CCITT Recommendation G.732: "Characteristics of primary PCM multiplex equipment operating at 2048 kbit/s".
- [11] CCITT Recommendation I.460: "Multiplexing, rate adaption and support of existing interfaces".

3 Abbreviations

Abbreviations used in the present document are listed in GSM 01.04

4 Layer 1 specification

All the CCITT recommendations referred to are Blue Book.

Layer 1 shall utilize digital transmission at a rate of 2 048 kbit/sec with a frame structure of 32 * 64 kbit/sec time slots, as specified in CCITT Recommendation G.705 section 3 or at a rate of 64 kbit/sec.

The physical/electrical characteristics are defined in CCITT Recommendation G.703.

Synchronization at the BTS/TRX for the transmitted bit stream toward the BSC shall be derived from the received bit stream from the BSC.

For transmission rate at 64 kbit/sec it shall be an interface as defined in CCITT Recommendation G.703.

For transmission rate at 2048 kbit/sec the functional characteristics are defined in CCITT Recommendation G.732 section 2 and 3, and fault conditions should be treated in accordance with CCITT Recommendation G.732 section 4.

The idle pattern must be transmitted on every timeslot that is not assigned to a channel, and to every timeslot of a channel that is not allocated to a call. The idle pattern shall be 01010100 for a 64 kbit/sec channel and the 2-bit pattern 01 for 16 kbit/sec channels. For 8 kbit/s channels, the idle pattern shall be consecutive ones or zeros according to the corresponding idle pattern bit of a 16 kbit/s channel.

If transcoders are located in BTS speech encoding shall be the A-law as defined in CCITT Recommendation G.711.

If speech transcoders are located in the BSC the speech, data and signalling channels will utilize transmission rates of 8 kbit/sec, 16 kbit/sec or 64 kbit/sec according to Technical Specifications GSM 08.60 and GSM 08.61. They shall be rate adapted or multiplexed according to CCITT Recommendation I.460 with fixed format, to fit into the physical interface.

Data encoding is covered in Technical Specification GSM 08.20.

In the case of a 2 048 kbit/sec circuit, multidrop solutions should be possible. Dynamic sharing of terrestrial 64 kbit/sec channels between BTS:s on a per-call basis must not be used.

Annex A (informative): Change Request History

Change history					
SMG No.	TDoc. No.	CR. No.	Section affected	New version	Subject/Comments
SMG#07				4.0.4	ETSI Publication
SMG#13				4.1.0	ETSI Publication
SMG#16				5.0.0	Phase 2+ version
SMG#27				6.0.0	Release 1997 version

History

Document history		
V6.0.0	April 1999	Publication