

# TS 101 324 V1.2.5 (1999-06)

---

*Technical Specification*

**Telecommunications and Internet Protocol  
Harmonization Over Networks (TIPHON);  
Numbering;  
Scenario 1 + Scenario 2**

---



---

**Reference**

RTS/TIPHON-04001 (c9c00irf.PDF)

---

**Keywords**

addressing, internet, network, protocol

**ETSI**

---

**Postal address**

F-06921 Sophia Antipolis Cedex - FRANCE

---

**Office address**

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16  
Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Internet**

secretariat@etsi.fr  
Individual copies of this ETSI deliverable  
can be downloaded from  
<http://www.etsi.org>  
If you find errors in the present document, send your  
comment to: editor@etsi.fr

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.  
All rights reserved.

---

## Contents

Intellectual Property Rights .....	4
Foreword .....	4
1 Scope.....	5
2 References .....	5
3 Definitions and abbreviations.....	6
3.1 Definitions .....	6
3.2 Abbreviations.....	7
4 Naming scheme for identification of users and terminals within TIPHON compliant networks.....	7
4.1 General requirements .....	7
4.2 Specific requirements.....	7
4.2.1 Public TIPHON compliant networks.....	7
4.2.2 Private TIPHON compliant networks .....	7
5 Functionality required within the TIPHON compliant network.....	8
5.1 General requirements .....	8
5.2 Requirements for Scenario 1 (IP to SCN).....	8
5.3 Requirements for Scenario 2 (SCN to IP).....	8
Bibliography .....	9
History.....	10

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Project Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON).

---

# 1 Scope

The present document specifies the naming, numbering, and addressing scheme and related functionality required within TIPHON compliant networks for calls:

- from Internet Protocol (IP) based terminals to terminals in a Switched Circuit Network (SCN) (TIPHON scenario 1); and
- from terminals in an SCN to IP based terminals (TIPHON scenario 2).

The objective of the present document is to ensure satisfactory interworking between TIPHON compliant networks and SCNs. An SCN may be a public network or a private network.

These requirements affect terminal equipment and equipment that performs the roles of gatekeeper and gateway, and the calling procedure for the end user.

Where the text indicates the status of a requirement (i.e. as strict command or prohibition, as authorization leaving freedom, or as a capability or possibility), this may modify the nature of a requirement within a referenced standard used to provide the capability.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ITU-T Recommendation E.164 (1997): "The international public telecommunication numbering plan".
- [2] ITU-T Recommendation H.323 (version 2): "Packet based multimedia communications systems".
- [3] ETS 300 189: "Private Telecommunication Network (PTN); Addressing".
- [4] ISO/IEC 11571: "Information technology - Telecommunications and information exchange between systems - Numbering and sub-addressing in private integrated services networks".
- [5] TR 101 300: "Telecommunications and Internet Protocol Harmonization Over Networks (TIPHON); Description of technical issues".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**address:** string or combination of decimal digits, symbols, and additional information which identifies the specific termination point(s) of a connection in a public network(s) or, where applicable, in interconnected private network(s). (e.g. ITU-T Recommendation E.164 [1]).

**carrier:** provider of a transit network or services.

**country code for geographic areas:** combination of one, two or three digits identifying a specific country, countries in an integrated numbering plan, or a specific geographic area. (e.g. ITU-T Recommendation E.164 [1]).

**dialling plan:** string or combination of decimal digits, symbols, and additional information that defines the method by which the numbering plan is used. A dialling plan includes the use of prefixes, suffixes, and additional information, supplemental to the numbering plan, required to complete the call. (e.g. ITU-T Recommendation E.164 [1]).

**gatekeeper:** gatekeeper is an H.323 entity on the network that provides address translation and controls access to the network for H.323 terminals, gateways, and Multipoint Control Units (MCUs). The gatekeeper may also provide other services to the terminals, gateways, and MCUs such as bandwidth management and locating gateways (e.g. ITU-T Recommendation H.323 [2]).

**gateway:** H.323 gateway is an endpoint on a network which provides for real-time, two-way communications between H.323 terminals on an IP based network and other terminals on an SCN.

**global service:** service defined by the ITU-T, provisioned on the public switched network, to which the ITU-T has assigned a specific country code to enable the provision of that international service between two or more countries and/or integrated numbering plans (e.g. ITU-T Recommendation E.164 [1]).

**name:** alphanumeric label used for service reference by end users. A name may be portable.

**number:** string of decimal digits from a recognized number plan (e.g. ITU-T Recommendation E.164 [1]).

**numbering plan:** numbering plan specifies the format and structure of the numbers used within that plan. It typically consists of decimal digits segmented into groups in order to identify specific elements used for identification, routing and charging capabilities, e.g. within ITU-T Recommendation E.164 [1] to identify countries, national destinations, and subscribers. A numbering plan does not include prefixes, suffixes and additional information required to complete the call. The national numbering plan is the national implementation of the ITU-T Recommendation E.164 [1] numbering plan.

**prefix:** prefix is an indicator consisting of one or more digits, that allows the selection of different types of number formats, networks and/or services (e.g. ITU-T Recommendation E.164 [1]).

**Switched Circuit Network (SCN):** see TR 101 300 [5].

**TIPHON compliant network:** network that complies with the mandatory requirements in the TIPHON requirements documents:

- TR 101 306 (for compliance with TIPHON phase 1); and
- TR 101 307 (for compliance with TIPHON phase 2),

together with compliance to the parts of the TIPHON specifications in which these requirements are embodied.

**E.164 Number:** number conforming to the numbering plan and structure specified in ITU-T Recommendation E.164 [1].

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CLI	Calling Line Identity
IP	Internet Protocol
MCU	Multipoint Control Unit
SCN	Switched Circuit Network

---

## 4 Naming scheme for identification of users and terminals within TIPHON compliant networks

NOTE: It should be noted that an E.164 number (e.g. ITU-T Recommendation E.164 [1]) and numbers conforming to ETS 300 189 [3] or ISO/IEC 11571 [4] can act in the role of both a name and an address within their respective environment.

### 4.1 General requirements

At least one naming scheme used in TIPHON compliant networks shall meet the following objectives:

- 1) The names shall consist solely of the decimal digits.
- 2) The namespace shall be either a global system or consist of inter-operable local systems.
- 3) The names shall be globally unique *for public networks*.
- 4) The naming scheme shall enable the use of single-stage dialling.
- 5) The naming scheme shall not preclude the support of mobility and roaming according to TR 101 338.
- 6) The naming scheme *shall not preclude the support for portability*.

NOTE: applying to 1 – 6 (fix note according to ETSI policy; rs): Additional overlaid naming schemes may be used.

### 4.2 Specific requirements

#### 4.2.1 Public TIPHON compliant networks

In public TIPHON compliant networks, numbers passed to and from SCNs shall conform to ITU-T Recommendation E.164 [1].

NOTE: ITU-T Recommendation E.164 [1] provides various alternative forms of numbering. One or more forms may be used. There is not necessarily a one-to-one relationship between an E.164 number and each TIPHON compliant terminal. *There may be more than one "user" on a given terminal.*

#### 4.2.2 Private TIPHON compliant networks

In private TIPHON compliant networks, numbers passed to and from private SCNs shall conform to ETS 300 189 [3] or ISO/IEC 11571 [4].

In private TIPHON compliant networks, numbers passed directly to and from public SCNs shall conform to ITU-T Recommendation E.164 [1].

---

## 5 Functionality required within the TIPHON compliant network

### 5.1 General requirements

- 1) TIPHON compliant networks shall accept the international format of the E.164 number of the called party.
- 2) TIPHON compliant networks may accept any other form of E.164 numbers used within the country where they are located.
- 3) TIPHON compliant networks may also accept private network number forms (e.g. in the case of a private IP network connected to a private SCN).
- 4) TIPHON compliant networks shall convey unaltered any user initiated presentation restriction requests concerning the Calling Line Identity (CLI).
- 5) TIPHON compliant networks shall support the carrier selection mechanism as required by relevant bodies (e.g., a national regulatory authority).

NOTE: Carrier selection may be set by default, by pre-selection by the subscriber, by dialling a carrier access code and a carrier identification code, or by other methods available within that country.

### 5.2 Requirements for Scenario 1 (IP to SCN)

TIPHON compliant networks shall provide the following functionality:

- 1) The calling party in TIPHON compliant networks shall be able to identify the called party on the SCN by the E.164 number, or the number used within the SCN in the case of a private IP network connected to a private SCN.

NOTE 1: It is assumed that if another naming scheme is used in a TIPHON compliant network, the name will be mapped into an E.164 number, or mapped into the number used within the SCN in the case of a private IP network connected to a private SCN.

- 2) TIPHON compliant networks shall provide to the SCN a Calling Line Identity (CLI) for the calling user if required, irrespective of whether the calling user has invoked presentation restriction of the CLI. The CLI shall identify either the terminal, or the user, or both.

NOTE 2: The CLI is required by networks for management purposes even if it is not to be presented to the called user.

Where prefixes are used, TIPHON compliant networks shall support the prefixes used.

Where special numbers are associated with specific services, TIPHON compliant networks shall support the use of these numbers.

NOTE 3: Examples are emergency numbers (911, 112).

### 5.3 Requirements for Scenario 2 (SCN to IP)

TIPHON compliant networks shall provide the following functionality:

- 1) TIPHON compliant networks shall conform to any calling line identity restrictions received from the SCN.

NOTE: National regulations may make use of the "override capability", e.g. in the case of emergency services: even though the user's CLI restriction indication is carried by the network, the destination's CLI presentation supplementary service overrides it.

- 2) Where service provider portability is required, TIPHON compliant networks shall support it.



---

## Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

TR 101 338: "Telecommunications and Internet Protocol Harmonization Over Network (TIPHON); Analysis of existing roaming techniques applicable to TIPHON mobility services".

---

## History

<b>Document history</b>		
V1.1.6	June 1998	Publication
V1.2.5	June 1999	Publication