

ETSI TS 101 823-2-1 V1.2.1 (2001-12)

Technical Specification

**Broadband Radio Access Networks (BRAN);
HIPERLAN Type 2;
Conformance testing for the
Data Link Control (DLC) layer;
Part 2: Radio Link Control (RLC) sublayer;
Sub-part 1: Protocol Implementation Conformance
Statement (PICS) proforma**



Reference

RTS/BRAN-002T0A4-2-1

Keywords

access, HIPERLAN, PICS, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	7
4 Conformance to this PICS proforma specification.....	7
Annex A (normative): Protocol ICS proforma for TS 101 761-2.....	8
A.1 Guidance for completing the PICS proforma.....	8
A.1.1 Purposes and structure.....	8
A.1.2 Abbreviations and conventions	9
A.1.3 Instructions for completing the PICS proforma.....	10
A.2 Identification of the implementation	11
A.2.1 Date of the statement.....	11
A.2.2 Implementation Under Test (IUT) identification	11
A.2.3 System Under Test (SUT) identification	11
A.2.4 Product supplier.....	11
A.2.5 Client (if different from product supplier).....	12
A.2.6 PICS contact person	12
A.3 Identification of the protocol.....	13
A.4 Global statement of conformance.....	13
A.5 Roles.....	13
A.6 Mobile Terminal MT.....	13
A.6.1 Major MT capabilities and functionalities of RLC.....	14
A.6.1.1 Services supporting ACF: Association Control Function	14
A.6.1.1.1 Association functions	14
A.6.1.1.2 Security functions	15
A.6.1.1.3 Disassociation functions.....	16
A.6.1.1.4 Multicast functions.....	16
A.6.1.1.5 CL Broadcast functions.....	17
A.6.1.2 Services supporting RRC: Radio Resource Control	17
A.6.1.3 Services supporting DUC: DLC User Connection Control	18
A.6.2 RLC PDU descriptions, seen from MT	19
A.6.2.1 PDU descriptions for ACF support.....	19
A.6.2.2 PDU descriptions for RRC support.....	21
A.6.2.3 PDU descriptions for DUC support	23
A.6.2.4 PDU descriptions for unsupported messages	26
A.6.3 PDU parameters	26
A.7 Access Point AP.....	26
A.7.1 Major AP capabilities and functionalities of RLC	26
A.7.1.1 Services supporting ACF: Association Control Function	27
A.7.1.1.1 Association functions	27
A.7.1.1.2 Security functions	27
A.7.1.1.3 Disassociation functions.....	29
A.7.1.1.4 Multicast functions.....	29
A.7.1.1.5 CL Broadcast functions.....	29

A.7.1.2	Services supporting RRC: Radio Resource Control	30
A.7.1.3	Services supporting DUC: DLC User Connection Control	31
A.7.2	RLC PDU descriptions, seen from AP	32
A.7.2.1	PDU descriptions for ACF support.....	32
A.7.2.2	PDU descriptions for RRC support.....	34
A.7.2.3	PDU descriptions for DUC support	36
A.7.2.4	PDU descriptions for unsupported messages	39
A.7.3	PDU parameters	39
A.8	PDU parameters	40
A.8.1	Parameters of PDUs for ACF support	40
A.8.1.1	Association	40
A.8.1.2	Security	43
A.8.1.3	Authentication.....	46
A.8.1.4	Disassociation.....	48
A.8.1.5	Multicast	49
A.8.1.6	Broadcast	50
A.8.2	Parameters of PDUs for RRC support.....	52
A.8.2.1	Handover	52
A.8.2.2	Dynamic Frequency Selection (DFS)	56
A.8.2.3	Change frequency	59
A.8.2.4	Uplink power control.....	60
A.8.2.5	MT alive	60
A.8.2.6	MT absence.....	61
A.8.2.7	Power saving.....	61
A.8.3	Parameters of PDUs for DUC support	62
A.8.3.1	DUC setup	62
A.8.3.2	DUC release.....	63
A.8.3.3	DUC modify	63
A.8.3.4	Direct Mode DUC setup	65
A.8.3.5	Direct Mode DUC release.....	67
A.8.3.6	DUC relay release.....	68
A.8.3.7	Direct Mode DUC modify	68
A.8.4	Parameters of PDUs for non support.....	71
A.9	Values of PDUs Parameters	71
History	72

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Project Broadband Radio Access Networks (BRAN).

The present document is part 2, sub-part 1 of a multi-part deliverable covering Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Conformance testing for the Data Link Control (DLC) layer, as identified below:

Part 1: "Basic data transport function";

Part 2: "Radio Link Control (RLC) sublayer";

Sub-part 1: "Protocol Implementation Conformance Statement (PICS) proforma";

Sub-part 2: "Test Suite Structure and Test Purposes (TSS&TP) specification";

Sub-part 3: "Abstract Test Suite (ATS) specification".

Part 3: "Profile for Business Environment";

Part 4: "Extension for Home Environment";

Part 5: "Profile for Home Environment".

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the Radio Link Control (RLC) layer of HIPERLAN Type 2 as defined in TS 101 761-2 [1] in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [4] and ETS 300 406 [2].

The present document details in tabular form the implementation options, i.e. the optional functions additional to those which are mandatory to implement.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI TS 101 761-2 (V1.1.1): "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) Layer; Part 2: Radio Link Control (RLC) sublayer".
- [2] ETSI ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TS 101 761-2 [1], ISO/IEC 9646-1 [3], ISO/IEC 9646-7 [4] and the following apply:

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

NOTE: The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

Protocol ICS (PICS): ICS for an implementation or system claimed to conform to a given protocol specification

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACF	Association Control Function
AP	Access Point
APT	Access Point Transceiver
ARQ	Automatic Repeat reQUest
BCH	Broadcast CHannel
CL	Convergence Layer
DES	Data Encryption Standard
DFS	Dynamic Frequency Selection
DLC	Data Link Control
DM	Direct Mode
DUC	DLC User Connection
ICS	Implementation Conformance Statement
IUT	Implementation Under Test
MAC	Medium Access Control
MT	Mobile Terminal
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
RLC	Radio Link Control
RRC	Radio Resource Control
SCS	System Conformance Statement
SUT	System Under Test

4 Conformance to this PICS proforma specification

If it claims to conform to the present document, the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

A PICS, which conforms to the present document, shall be a conforming PICS proforma completed in accordance with the guidance for completion given in clause A.1.

Annex A (normative): Protocol ICS proforma for TS 101 761-2

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.
--

A.1 Guidance for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in TS 101 761-2 may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- guidance for completing the PICS proforma;
- identification of the implementation;
- identification of the TS 101 761-2;
- global statement of conformance;
- roles;
- Mobile Terminal MT:
 - major capabilities;
 - PDUs;
 - PDU parameters;
 - timers;
- Access Point AP:
 - major capabilities;
 - PDUs;
 - PDU parameters;
 - timers.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7.

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7, are used for the status column:

m	mandatory - the capability is required to be supported.
o	optional - the capability may be supported or not.
n/a	not applicable - in the given context, it is impossible to use the capability.
x	prohibited (excluded) - there is a requirement not to use this capability in the given context.
o.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table.
ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table.
i	irrelevant (out-of-scope) - capability outside the scope of the reference specification. No answer is requested from the supplier.

NOTE 1: This use of "i" status is not to be confused with the suffix "i" to the "o" and "c" statuses above.

Reference column

The reference column makes reference to TS 101 761-2, except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7, are used for the support column:

Y or y	supported by the implementation.
N or n	not supported by the implementation.
N/A, n/a or -	no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

If this PICS proforma is completed in order to describe a multiple-profile support in a system, it is necessary to be able to answer that a capability is supported for one profile and not supported for another. In that case, the supplier shall enter the unique reference to a conditional expression, preceded by "?" (e.g. ?3). This expression shall be given in the space for comments provided at the bottom of the table. It uses predicates defined in the SCS, each of which refers to a single profile and which takes the value TRUE if and only if that profile is to be used.

EXAMPLE 1: ?3: IF prof1 THEN Y ELSE N.

NOTE 2: As stated in ISO/IEC 9646-7, support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values: <min value> .. <max value>
 example: 5 .. 20
- list of values: <value1>, <value2>, ..., <valueN>
 example: 2, 4, 6, 8, 9
 example: '1101'B, '1011'B, '1111'B
 example: '0A'H, '34'H, '2F'H
- list of named values: <name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)
 example: reject(1), accept(2)
- length: size (<min size> .. <max size>)
 example: size (1 .. 8)

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 2: A.5/4 is the reference to the answer of item 4 in table A.5.

EXAMPLE 3: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table A.6.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause A.1.2.

However, the tables containing in "user role" or "Mobile Terminal MT" clause shall only be completed for MT implementations, and the tables containing in "network role" or "Access Point AP" clause shall only be completed for AP implementations.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

IUT version:

.....

A.2.3 System Under Test (SUT) identification

SUT name:

.....

Hardware configuration:

.....

Operating system:

.....

A.2.4 Product supplier

Name:

.....

Address:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.2.5 Client (if different from product supplier)

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

A.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS.)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.3 Identification of the protocol

This PICS proforma applies to the following standard:

TS 101 761-2 (V1.1.1): "Broadband Radio Access Networks (BRAN); HIPERLAN Type 2; Data Link Control (DLC) Layer; Part 2: Radio Link Control (RLC) sublayer".

A.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the TS 101 761-2 specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

A.5 Roles

Table A.1: Roles

Item	Role	Reference	Status	Support
1	Mobile Terminal MT	4	o.1	
2	Access Point AP	4	o.1	

o.1: It is mandatory to support at least one of these items.

Comments:

.....

.....

A.6 Mobile Terminal MT

This clause contains the PICS proforma tables related to the Mobile Terminal MT. They need to be completed for description of MT implementations only.

Prerequisite: A.1/1 -- Mobile Terminal MT

A.6.1 Major MT capabilities and functionalities of RLC

Table A.2: Major MT functionalities

Item	Services supporting:	Reference	Status	Support
1	Association Control Function ACF	5.1	m	
2	Radio Resource Control RRC	5.2	m	
3	DLC User Connection Control DUC	5.3	m	

A.6.1.1 Services supporting ACF: Association Control Function

The supplier of the implementation shall state the support of the implementation for the services required by each of the following ACF procedures and associated capabilities.

Table A.3: MT ACF procedures

Item	Services supporting:	Reference	Status	Support
1	Association functions	5.1.1	m	
2	Encryption	5.1.2	m	
3	Authentication	5.1.2	m	
4	Disassociation	5.1.3	m	
5	Multicast	5.1.4	o	
6	CL Broadcast	5.1.5	o	
7	Association Rejection	5.1.6	m	

Comments:

.....

.....

A.6.1.1.1 Association functions

Table A.4: MT Association functions

Item	Capabilities	Reference	Status	Support
1	MT receives Association message	5.1.1.1	m	
2	MT initiates Association request message	5.1.1.1	o	
3	MT initiates checking of Convergence Layer Ids	5.1.1.1	m	
4	MT supports multiple CL_Id	5.1.1.1	o	
5	MT sends request for Mac ID assignment	5.1.1.2	m	
6	MT initiates exchange of link capabilities	5.1.1.3	m	
7	MT initiates info transfer procedure with AP (or with MT for Direct Link purpose)	5.1.1.8	o	

Table A.5: MT Link capabilities

Item	Capabilities	Reference	Status	Support
1	MT supports centralized mode	5.1.1.3	m	
2	MT supports direct mode	5.3.7	o	
3	MT supports two frequency bands	5.1.1.3	o	

A.6.1.1.2 Security functions

Table A.6: MT Security functions

Item	Capabilities	Reference	Status	Support
1	MT supports user data encryption and initiates encryption start-up	5.1.1.4	m	
2	MT supports authentication	5.1.1.5, 5.1.1.6	m	
3	MT supports Direct Mode common key distribution	5.1.1.7	c601	

c601: IF A.5/2 -- If MT supports Direct mode
 THEN m -- then mandatory
 ELSE n/a

Table A.7: MT Encryption algorithm

Item	Capabilities	Reference	Status	Support
1	DES encryption	5.1.2.5	m	
2	Triple DES encryption	5.1.2.5	o	

Table A.8: MT Encryption keys

Item	Capabilities	Reference	Status	Support
1	DES encryption for unicast	5.1.2.5	m	
2	DES encryption for multicast	5.1.2.5	c801	
3	DES encryption for broadcast	5.1.2.5	c802	
4	Triple DES encryption for unicast	5.1.2.5	c803	
5	Triple DES encryption for multicast	5.1.2.5	c804	
6	Triple DES encryption for broadcast	5.1.2.5	c805	

c801: IF A.3/5 -- If MT supports multicast
 THEN m -- then mandatory
 ELSE n/a

c802: IF A.3/6 -- If MT supports broadcast
 THEN m -- then mandatory
 ELSE n/a

c803: IF A.7/2 -- If MT supports Triple DES
 THEN m -- then mandatory
 ELSE n/a

c804: IF A.3/5 AND A.7/2 -- If MT supports multicast AND Triple DES
 THEN m -- then mandatory
 ELSE n/a

c805: IF A.3/6 AND A.7/2 -- If MT supports broadcast AND Triple DES
 THEN m -- then mandatory
 ELSE n/a

Table A.9: MT Key management

Item	Capabilities	Reference	Status	Support
1	MT refreshes unicast encryption key	5.1.2.2	m	
2	MT refreshes common encryption keys for multicast	5.1.2.3	c901	
3	MT refreshes common encryption keys for broadcast	5.1.2.3	c902	

c901: IF A.3/5 -- If MT supports multicast
 THEN m -- then mandatory
 ELSE n/a

c902: IF A.3/6 -- If MT supports Broadcast
 THEN m -- then mandatory
 ELSE n/a

Table A.10: Authentication protocols and key identifiers assigned in MT

Item	Capabilities	Reference	Status	Support
1	IEEE address	5.1.1.5.3.2	o.2	
2	Extended IEEE address	5.1.1.5.3.3	o.2	
3	Network access identifier	5.1.1.5.3.4	o.2	
4	Distinguished name X509	5.1.1.5.3.5	o.2	
5	Compressed type	5.1.1.5.3.6	o.2	
6	Generic type	5.1.1.5.3.7	o.2	

o.2 Support of one of these items is mandatory, others are optional.

Table A.11: MT Authentication algorithms

Item	Capabilities	Reference	Status	Support
1	MD5 HMAC algorithm	5.1.1.6.1	m	
2	Public key based algorithm (RSA)	5.1.1.6.1	o	

Table A.12: RSA Authentication protocols in MT

Prerequisite: A.11 /2 -- MT supports public key based authentication				
Item	Capabilities	Reference	Status	Support
1	RSA512 bit signature	5.1.1.6.2	o.3	
2	RSA768 bit signature	5.1.1.6.3	o.3	
3	RSA1024 bit signature	5.1.1.6.4	o.3	

o.3: Support at least one of these items if A.11 /2 -- MT supports public key based authentication.

A.6.1.1.3 Disassociation functions

Table A.13: MT Disassociation

Item	Procedures	MT Initiating			MT Receiving		
		Reference	Status	Support	Reference	Status	Support
1	Explicit disassociation	5.1.3	m		5.1.3	m	
2	Implicit disassociation initiated by MT	5.1.3	m			n/a	

A.6.1.1.4 Multicast functions

Table A.14: MT Multicast

Prerequisite: A.3/5 -- MT supports multicast				
Item	Capabilities	Reference	Status	Support
1	MT initiates multicast (group join)	5.1.4	m	
2	MT leaves multicast group (group-leave message is used)	5.1.4	m	

A.6.1.1.5 CL Broadcast functions

Table A.15: MT CL broadcast

Prerequisite: A.3/6 -- MT supports CL Broadcast				
Item	Capabilities	Reference	Status	Support
1	MT initiates Broadcast (broadcast join)	5.1.5	m	
2	MT leaves Broadcast (broadcast - leave message is used)	5.1.5	o	

A.6.1.2 Services supporting RRC: Radio Resource Control

The supplier of the implementation shall state the support of the implementation for the services required by each of the following RRC procedures and associated capabilities.

Table A.16: MT RRC procedures

Item	Capabilities	Reference	Status	Support
1	Handover	5.2.1	o	
2	DFS Dynamic Frequency Selection	5.2.2	m	
3	Uplink/Downlink Power Control	5.2.3	m	
4	Direct link Power Control	5.2.3	o	
5	MT alive	5.2.4	m	
6	MT absence	5.2.5	o	
7	MT sleep / power saving	5.2.6	o	

Comments:

.....

.....

Table A.17: MT Handover capabilities

Prerequisite: A.16 /1 -- MT supports handover				
Item	Capabilities	Reference	Status	Support
1	MT supports Sector handover	5.2.1.1	o	
2	MT supports Radio handover	5.2.1.2	o	
3	MT supports Network handover	5.2.1.3	o	
4	Token distribution for Network handover	5.2.1.4	o	
6	Handover Rejection	5.2.1.5	m	
5	MT performs Handover when forced by AP	5.2.1.6	o	
6	MT notifies AP of Handover (message RLC Handover Notify is used)	5.2.1.2	o	

Table A.18: MT DFS Dynamic Frequency Selection measurements

Item	Capabilities	Reference	Status	Support
1	MT performs and reports measurements requested by AP	5.2.2.3	m	
2	MT performs and reports self initiated measurements	5.2.2.3	o	
3	MT performs change of operating frequency requested by AP	5.2.2.6	c1801	

c1801: IF A.5/2 -- If MT supports two frequency bands
 THEN m -- then mandatory
 ELSE n/a

A.6.1.3 Services supporting DUC: DLC User Connection Control

The supplier of the implementation shall state the support of the implementation for the services required by each of the following DUC procedures and associated capabilities.

Table A.19: MT DUC procedures

Item	Procedures	Reference	Status	Support
1	MT supports Centralized mode Unicast radio connection setup	5.3.1	m	
2	MT supports Centralized mode Unicast radio connection setup initiated by AP	5.3.1.1	o	
3	MT supports Centralized mode Unicast radio connection release	5.3.2	m	
4	MT supports Centralized mode Unicast radio connection modify	5.3.3	o	
5	MT supports Centralized mode Unicast radio connection reset	5.3.4	m	
6	MT supports Centralized mode Multicast radio connection	5.3.5	c1901	
7	MT supports Centralized mode Broadcast radio connection	5.3.6	c1902	
8	MT supports Direct Link Unicast radio connection setup	5.3.7	c1903	
9	MT supports Direct Link Unicast radio connection release	5.3.8	c1903	
10	MT supports Direct Link Unicast radio connection modify	5.3.9	c1903	
11	MT supports Direct Link Unicast radio connection reset	5.3.10	c1903	
12	MT supports Direct Link Unicast DUC relay (setup, release, modify)	5.3.7, 5.3.8, 5.3.9	c1906	
13	MT supports Direct Link Multicast radio connection	5.3.11	c1904	
14	MT supports Direct Link Broadcast radio connection	5.3.12	c1905	

c1901: IF A.3/5 -- If MT supports multicast
 THEN m -- then mandatory
 ELSE n/a

c1902: IF A.3/6 -- If MT supports broadcast
 THEN m -- then mandatory
 ELSE n/a

c1903: IF A.5/2 -- If MT supports Direct mode
 THEN m -- then mandatory
 ELSE n/a

c1904: IF A.3/5 AND A.5/2 -- If MT supports multicast AND Direct mode
 THEN m -- then mandatory
 ELSE n/a

c1905: IF A.3/6 AND A.5/2 -- If MT supports broadcast AND Direct mode
 THEN m -- then mandatory
 ELSE n/a

c1906: IF A.5/2 -- If MT supports Direct mode
 THEN o -- then optional
 ELSE n/a

A.6.2 RLC PDU descriptions, seen from MT

In the following PDU tables, statuses with M or O are the only valid cases, due to the direction of the PDU. When not applicable to a given direction, status n/a is defined. On many occasions, the conditional support is expressed by a prerequisite statement.

A.6.2.1 PDU descriptions for ACF support

Table A.20: Association PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RBCH_ASSOCIATION		n/a		5.1.1.1	m	
2	RLC_RBCH_ASSOCIATION_REQ	5.1.1.1	o			n/a	
3	RLC_MAC_ID_ASSIGN	5.1.1.2	m			n/a	
4	RLC_MAC_ID_ASSIGN_ACK		n/a		5.1.1.2	m	
5	RLC_MAC_ID_ASSIGN_NACK		n/a		5.1.1.2	m	
6	RLC_LINK_CAPABILITY	5.1.1.3	m			n/a	
7	RLC_LINK_CAPABILITY_ACK		n/a		5.1.1.3	m	
8	RLC_INFO	5.1.1.8	c2001			n/a	
9	RLC_INFO_ACK		n/a		5.1.1.8	c2001	

c2001: IF A.4/7 -- MT supports info transfer
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.21: Security PDUs

Prerequisite: none, encryption support is mandatory

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_KEY_EXCHANGE_MT1	5.1.1.4	m			n/a	
2	RLC_KEY_EXCHANGE_MT2	5.1.1.4	m			n/a	
3	RLC_KEY_EXCHANGE_AP1		n/a		5.1.1.4	m	
4	RLC_KEY_EXCHANGE_AP2		n/a		5.1.1.4	m	
5	RLC_DM_COMMON_KEY_DISTR	5.1.1.7	c2101			n/a	
6	RLC_DM_COMMON_KEY_DISTR_ACK		n/a		5.1.1.7	c2101	
7	RLC_UNICAST_KEY_REFRESH		n/a		5.1.1.2	m	
8	RLC_UNICAST_KEY_REFRESH_ACK	5.1.1.2	m			n/a	
9	RLC_COMMON_KEY_REFRESH		n/a		5.1.2.3.3	m	
10	RLC_COMMON_KEY_REFRESH_ACK	5.1.2.3.3	m			n/a	
11	RLC_COMMON_KEY_ACTIVATE		n/a		5.1.2.3.3	m	

c2101: IF A.5/2 MT supports Direct mode
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.22: Authentication PDUs

Prerequisite: none, authentication support is mandatory

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_AUTHENTICATION	5.1.1.5	m			n/a	
2	RLC_AUTHENTICATION_MT		n/a		5.1.1.5	m	
3	RLC_AUTHENTICATION_AP_1	5.1.1.6	m			n/a	
4	RLC_AUTHENTICATION_AP_2	5.1.1.6	c2201			n/a	
5	RLC_AUTHENTICATION_AP_3	5.1.1.6	c2202			n/a	
6	RLC_AUTHENTICATION_ACK_1		n/a		5.1.1.6	m	
7	RLC_AUTHENTICATION_ACK_2		n/a		5.1.1.6	c2201	
8	RLC_AUTHENTICATION_ACK_3		n/a		5.1.1.6	c2203	

c2201: IF A.11 /2-- MT supports public key based authentication
 THEN m -- then mandatory
 ELSE n/a

c2202: IF A.12/2 OR A.12/3 -- MT supports RSA768 bit signature OR RSA1024 bit signature
 THEN m -- then mandatory
 ELSE n/a

c2203: IF A.12/3 -- MT supports RSA1024 bit signature
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.23: Disassociation PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DISASSOCIATION	5.1.3	m		5.1.3	m	
2	RLC_DISASSOCIATION_ACK	5.1.3	m		5.1.3	m	

Comments:

.....

.....

Table A.24: MULTICAST PDUs

Prerequisite: A.3/5 MT supports Multicast

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_GROUP_JOIN	5.1.4	m			n/a	
2	RLC_GROUP_JOIN_ACK		n/a		5.1.4	m	
3	RLC_GROUP_JOIN_NACK		n/a		5.1.4	m	
4	RLC_GROUP_LEAVE	5.1.4	m			n/a	
5	RLC_GROUP_LEAVE_ACK		n/a		5.1.4	m	

Comments:

.....

.....

Table A.25: BROADCAST PDUs

Prerequisite: A.3/6 MT supports Broadcast

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_CL_BROADCAST_JOIN	5.1.5	m			n/a	
2	RLC_CL_BROADCAST_JOIN_ACK		n/a		5.1.5	m	
3	RLC_CL_BROADCAST_LEAVE	5.1.5	c2501			n/a	
4	RLC_CL_BROADCAST_LEAVE_ACK		n/a		5.1.5	c2501	

c2501: IF A.15/2 MT supports Broadcast leave message
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

A.6.2.2 PDU descriptions for RRC support

Table A.26: HANDOVER PDUs

Prerequisite: A.16/1 -- MT supports handover

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SECTOR_HANDOVER_REQUEST	5.2.1.1	m			n/a	
2	RLC_SECTOR_HANDOVER_ACK		n/a		5.2.1.1	m	
3	RLC_HANDOVER_NOTIFY	5.2.1.2	c2604			n/a	
4	RLC_HANDOVER_REQUEST	5.2.1.2	m			n/a	
5	RLC_RADIO_HANDOVER_COMPLETE		n/a		5.2.1.2	c2602	
6	RLC_HANDOVER_ASSOCIATION		n/a		5.2.1.3	m	
7	RLC_HANDOVER_LINK_CAPABILITY_ACK		n/a		5.2.1.3	m	
8	RLC_NW_SIGNALLING_HANDOVER	5.2.1.3	m			n/a	
9	RLC_NW_SIGNALLING_HANDOVER_ACK		n/a		5.2.1.3	m	
10	RLC_HO_INFO_DISTRIBUTION		n/a		5.2.1.4	m	
11	RLC_HO_INFO_DISTRIBUTION_ACK	5.2.1.4	m			n/a	
12	RLC_NETWORK_HANDOVER_COMPLETE		n/a		5.2.1.4	m	
13	RLC_FORCE_HANDOVER		n/a		5.2.1.6	c2603	
14	RLC_FORCE_HANDOVER_ACK	5.2.1.6	c2603			n/a	
15	RLC_HANDOVER_REQUEST_NACK	5.2.1.5	n/a		5.2.1.5	m	

c2602: IF A.17/2 - - MT supports Radio Handover
 THEN m -- then mandatory
 ELSE n/a

c2603: IF A.17/5 - - MT supports Forced Handover
 THEN m -- then mandatory
 ELSE n/a

c2604: IF A.17/7 - - MT notifies AP of Handover
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.27: DFS measurement PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_AP_ABSENCE		n/a		5.2.2.4	c2702	
2	RLC_DFS_MEASUREMENT_SHORT_REQUEST		n/a		5.2.2.4	m	
3	RLC_DFS_MEASUREMENT_PERCENTILES_REQUEST		n/a		5.2.2.4	m	
4	RLC_DFS_MEASUREMENT_COMPLETE_REQUEST		n/a		5.2.2.4	m	
5	RLC_DFS_MT_INIT_REPORT_REQUEST	5.2.2.4	c2701			n/a	
6	RLC_DFS_MT_INIT_REPORT_REQUEST_ACK		n/a		5.2.2.4	c2701	
7	RLC_DFS_REPORT_SHORT	5.2.2.4	m			n/a	
8	RLC_DFS_REPORT_PERCENTILES	5.2.2.4	m			n/a	
9	RLC_DFS_REPORT_COMPLETE	5.2.2.4	m			n/a	

c2701: IF A.18/2 - - MT performs and reports self initiated measurements
 THEN m -- then mandatory
 ELSE n/a

c2702: IF A.16/5 - - MT supports Absence
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.28: Change Frequency PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_CHANGE_FREQUENCY		n/a		5.2.2.6	m	

Table A.29: Transmission Power Control PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_UPLINK_PC_CALIBRATION		n/a		5.2.3	m	
2	RLC_MT_ALIVE_REQUEST		n/a		5.2.4	m	
3	RLC_MT_ALIVE_REQUEST_ACK	5.2.4	m			n/a	
4	RLC_MT_ALIVE	5.2.4	m			n/a	
5	RLC_MT_ALIVE_ACK		n/a		5.2.4	m	

Table A.30: MT Absence PDUs

Prerequisite: A.16 /5 -- MT supports Absence

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_MT_ABSENCE	5.2.5	m			n/a	
2	RLC_MT_ABSENCE_ACK		n/a		5.2.5	m	

Table A.31: Power saving / Power control PDUs

Prerequisite: A.16 /6 -- MT supports Power saving

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SLEEP	5.2.6	m			n/a	
2	RLC_SLEEP_ACK		n/a		5.2.6	m	

A.6.2.3 PDU descriptions for DUC support

Table A.32: DUC setup PDUs

Item	PDU	MT sending			MT receiving (AP initiate)		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SETUP	5.3.1.2	m		5.3.1.1	c3201	
2	RLC_CONNECT	5.3.1.1	c3201		5.3.1.2	m	
3	RLC_CONNECT_ACK	5.3.1.2	m		5.3.1.1	c3201	

c3201: IF A.19/2 -- MT supports Setup initiated by AP
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

Table A.33: DUC release PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELEASE	5.3.2.2	m		5.3.2.1	m	
2	RLC_RELEASE_ACK	5.3.2.1	m		5.3.2.2	m	

Comments:

.....

Table A.34: DUC modify PDUs

Prerequisite: A.19/4 MT supports Modify radio connection

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_MODIFY_REQ	5.3.3.2	m		5.3.3.1	m	
2	RLC_MODIFY	5.3.3.1	m		5.3.3.2	m	
3	RLC_MODIFY_ACK	5.3.3.2	m		5.3.3.1	m	

Comments:

.....

.....

Table A.35: DUC reset PDUs

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RESET	5.3.4.2	m		5.3.4.1	m	
2	RLC_RESET_ACK	5.3.4.1	m		5.3.4.2	m	

Comments:

.....

.....

Table A.36: Direct link DUC setup PDUs

Prerequisite: A.5/2 MT supports Direct mode

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_SETUP	5.3.7.2			5.3.7.1	m	
2	RLC_DM_CONNECT	5.3.7.1	m		5.3.7.2	m	
3	RLC_DM_CONNECT_ACK	5.3.7.2	m		5.3.7.1	m	
4	RLC_DM_CONNECT_COMPLETE		n/a		5.3.7.1	m	
5	RLC_DM_CONNECT_COMPLETE_ACK	5.3.7.1	m			n/a	

Comments:

.....

.....

Table A.37: RLC_RELAY PDUs

Prerequisite: A.5/2 AND A19/12 MT supports Direct mode AND relay functions

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_SETUP	5.3.7.3	m			n/a	
2	RLC_RELAY_SETUP_ACK		n/a		5.3.7.3	m	

Comments:

.....

.....

Table A.38: Direct link DUC release PDUs

Prerequisite: A.5/2 MT supports Direct mode

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_RELEASE	5.3.8.2	m		5.3.8.1	m	
2	RLC_DM_RELEASE_ACK	5.3.8.1	m		5.3.8.2	m	

Comments:

.....

.....

Table A.39: Direct link DUC relay release PDUs

Prerequisite: A.5/2 AND A19/12 MT supports Direct mode AND relay functions

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_RELEASE	5.3.8.3	m		5.3.8.3	m	
2	RLC_RELAY_RELEASE_ACK	5.3.8.3	m		5.3.8.3	m	

Comments:

.....

.....

Table A.40: Direct link DUC modify PDUs

Prerequisite: A.5/2 MT supports Direct mode

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_MODIFY_REQ	5.3.9.2	m		5.3.9.1	m	
2	RLC_DM_MODIFY	5.3.9.1	m		5.3.9.2	m	
3	RLC_DM_MODIFY_ACK	5.3.9.2	m		5.3.9.1	m	
4	RLC_DM_MODIFY_COMPLETE		n/a		5.3.9.1	m	
5	RLC_DM_MODIFY_COMPLETE_ACK	5.3.9.1	m		6.3.7.1	m	

Comments:

.....

.....

Table A.41: Direct link DUC relay modify PDUs

Prerequisite: A.5/2 AND A19/12 MT supports Direct mode AND relay functions

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_MODIFY	5.3.9.3	m			n/a	
2	RLC_RELAY_MODIFY_ACK		n/a		5.3.9.3	m	

Comments:

.....

.....

Table A.42: Direct link DUC reset PDUs

Prerequisite: A.5/2 MT supports Direct mode

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_RESET	5.3.10.2	m		5.3.10.1	m	
2	RLC_DM_RESET_ACK	5.3.10.1	m		5.3.10.2	m	

Comments:

.....

.....

A.6.2.4 PDU descriptions for unsupported messages

Table A.43

Item	PDU	MT sending			MT receiving		
		Reference	Status	Support	Reference	Status	Support
1	RLC_NO_SUPPORT	7	m		7	m	

A.6.3 PDU parameters

See clause A.8, common to MT and AP

A.7 Access Point AP

This clause contains the PICS proforma tables related to the Access Point AP. They need to be completed only to describe AP implementations:

Prerequisite: A.1/2 Access Point AP

A.7.1 Major AP capabilities and functionalities of RLC

Table A.44: Major AP functionalities

Item	Services supporting:	Reference	Status	Support
1	Association Control Function ACF	5.1	m	
2	Radio Resource Control RRC	5.2	m	
3	DLC User Connection Control DUC	5.3	m	

Comments:

.....

.....

A.7.1.1 Services supporting ACF: Association Control Function

The supplier of the implementation shall state the support of the implementation for the services required by each of the following ACF procedures and associated capabilities.

Table A.45: AP ACF procedures

Item	Services supporting:	Reference	Status	Support
1	Association functions	5.1.1	m	
2	Encryption	5.1.2	m	
3	Authentication	5.1.2	m	
4	Disassociation	5.1.3	m	
5	Multicast	5.1.4	o	
6	CL Broadcast	5.1.5	o	
7	Association Rejection	5.1.6	m	

A.7.1.1.1 Association functions

Table A.46: AP Association functions

Item	Capabilities	Reference	Status	Support
1	AP sends Association message	5.1.1.1	m	
2	AP receives Association request message	5.1.1.1	m	
3	AP assigns Mac ID	5.1.1.2	m	
4	AP defines link capabilities	5.1.1.3	m	
5	AP supports info transfer procedure	5.1.1.8	o	

Table A.47: AP Link capabilities

Item	Capabilities	Reference	Status	Support
1	AP supports centralized mode	5.1.1.3	m	
2	AP supports direct mode	5.1.1.3	o	
3	AP supports two frequency bands	5.1.1.3	o	

A.7.1.1.2 Security functions

Table A.48: AP Security functions

Item	Capabilities	Reference	Status	Support
1	AP supports user data encryption and initiates encryption start-up	5.1.1.4	m	
2	AP supports authentication	5.1.1.5, 5.1.1.6	m	
3	AP supports Direct Mode common key distribution	5.1.1.7	c4801	

c4801: IF A.47/2 -- If AP supports Direct mode
 THEN m -- then mandatory
 ELSE n/a

Table A.49: AP Encryption algorithm

Item	Capabilities	Reference	Status	Support
1	DES encryption	5.1.2.5	m	
2	Triple DES encryption	5.1.2.5	o	

Table A.50: AP Encryption keys

Item	Capabilities	Reference	Status	Support
1	DES encryption for unicast	5.1.2.5	m	
2	DES encryption for multicast	5.1.2.5	c5001	
3	DES encryption for broadcast	5.1.2.5	c5002	
4	Triple DES encryption for unicast	5.1.2.5	c5003	
5	Triple DES encryption for multicast	5.1.2.5	c5004	
6	Triple DES encryption for broadcast	5.1.2.5	c5005	

- c5001: IF A.45/5 -- If AP supports multicast
THEN m -- then mandatory
ELSE n/a
- c5002: IF A.45/6 -- If AP supports broadcast
THEN m -- then mandatory
ELSE n/a
- c5003: IF A.49/2 -- If AP supports Triple DES
THEN m -- then mandatory
ELSE n/a
- c5004: IF A.45/5 AND A.49/2 -- If AP supports multicast AND Triple DES
THEN m -- then mandatory
ELSE n/a
- c5005: IF A.45/6 AND A.49/2 -- If AP supports broadcast AND Triple DES
THEN m -- then mandatory
ELSE n/a

Table A.51: AP Key management

Item	Capabilities	Reference	Status	Support
1	AP refreshes unicast encryption key	5.1.2.2	o	
2	AP refreshes common encryption keys for multicast	5.1.2.3	c5101	
3	AP refreshes common encryption keys for broadcast	5.1.2.3	c5102	

- c5101: IF A.45/5 -- If AP supports multicast
THEN o -- then optional
ELSE n/a
- c5102: IF A.45/6 -- If AP supports Broadcast
THEN o -- then optional
ELSE n/a

Table A.52: Authentication key identifiers assigned in AP

Item	Capabilities	Reference	Status	Support
1	IEEE address	5.1.1.5.3	o.4	
2	Extended IEEE address	5.1.1.5.3	o.4	
3	Network access identifier	5.1.1.5.3	o.4	
4	Distinguished name X509	5.1.1.5.3	o.4	
5	Compressed type	5.1.1.5.3	o.4	
6	Generic type	5.1.1.5.3	o.4	

- o.4 Support of one of these items mandatory, others are optional.

Table A.53: AP Authentication algorithms

Item	Capabilities	Reference	Status	Support
1	MD5 HMAC algorithm	5.1.1.6.1	m	
2	Public key based algorithm (RSA)	5.1.1.6.1	o	

Table A.54: RSA Authentication protocols in AP

Prerequisite: A.53/2 -- AP supports public key based authentication

Item	Capabilities	Reference	Status	Support
1	RSA512 bit signature	5.1.1.6.2	o.5	
2	RSA768 bit signature	5.1.1.6.3	o.5	
3	RSA1024 bit signature	5.1.1.6.4	o.5	

o.5: Support at least one of these items.

A.7.1.1.3 Disassociation functions

Table A.55: AP Disassociation

Item	Procedures	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	Explicit disassociation	5.1.3	m		5.1.3	m	
2	Implicit disassociation initiated by MT	5.1.3	m			n/a	

A.7.1.1.4 Multicast functions

Table A.56: AP Multicast

Prerequisite: A.45/5 -- AP supports multicast

Item	Capabilities	Reference	Status	Support
1	AP receives multicast group join	5.1.4	m	
2	AP receives group-leave message from MT	5.1.4	m	

A.7.1.1.5 CL Broadcast functions

Table A.57: AP CL broadcast

Prerequisite: A.45/6 -- AP supports CL Broadcast

Item	Capabilities	Reference	Status	Support
1	AP receives broadcast join to initiate Broadcast	5.1.5	m	
2	AP receives broadcast leave to end Broadcast	5.1.5	o	

A.7.1.2 Services supporting RRC: Radio Resource Control

The supplier of the implementation shall state the support of the implementation for the services required by each of the following RRC procedures and associated capabilities.

Table A.58: AP RRC procedures

Item	Capabilities	Reference	Status	Support
1	Handover	5.2.1	o	
2	DFS Dynamic Frequency Selection	5.2.2	m	
3	Uplink/Downlink Power Control	5.2.3	m	
4	Direct link Power Control	5.2.3	o	
5	MT alive	5.2.4	m	
6	MT absence	5.2.5	o	
7	MT sleep / power saving	5.2.6	m	

Comments:

.....

.....

Table A.59: AP Handover capabilities

Prerequisite: A.58/1 -- AP supports handover

Item	Capabilities	Reference	Status	Support
1	AP supports Sector handover	5.2.1.1	o	
2	AP supports Radio handover	5.2.1.2	o	
3	AP supports Network handover	5.2.1.3	o	
4	Token distribution for Network handover	5.2.1.4	o	
5	Handover Rejection	5.2.1.5	m	
6	Handover is forced by AP	5.2.1.6	o	
7	AP is notified by MT of Handover (message RLC Handover Notify is used)	5.2.1.2	o	

Table A.60: AP DFS Dynamic Frequency Selection measurements

Item	Capabilities	Reference	Status	Support
1	AP requests MT for DFS measurements and reports	5.2.2.3	m	
2	AP accepts MT self initiated measurements reports	5.2.2.3	o	
3	AP requests change of operating frequency	5.2.2.6	c6001	

c6001: IF A.47/2 -- If AP supports two frequency bands
 THEN m -- then mandatory
 ELSE n/a

A.7.1.3 Services supporting DUC: DLC User Connection Control

The supplier of the implementation shall state the support of the implementation for the services required by each of the following DUC procedures and associated capabilities.

Table A.61: AP DUC procedures

Item	Procedures	Reference	Status	Support
1	AP supports Centralized mode Unicast radio connection setup	5.3.1	m	
2	AP initiates Centralized mode Unicast radio connection setup	5.3.1.1	o	
3	AP supports Centralized mode Unicast radio connection release	5.3.2	m	
4	AP supports Centralized mode Unicast radio connection modify	5.3.3	m	
5	AP supports Centralized mode Unicast radio connection reset	5.3.4	m	
6	AP supports Centralized mode Multicast radio connection	5.3.5	c6101	
7	AP supports Centralized mode Broadcast radio connection	5.3.6	c6102	
8	AP supports Direct Link Unicast radio connection setup	5.3.7	c6103	
9	AP supports Direct Link Unicast radio connection release	5.3.8	c6103	
10	AP supports Direct Link Unicast radio connection modify	5.3.9	c6103	
11	AP supports Direct Link Unicast radio connection reset	5.3.10	c6103	
12	AP supports Direct Link Unicast DUC relay setup, release, modify	5.3.7, 5.3.8, 5.3.9	c6103	
13	AP supports Direct Link Multicast radio connection	5.3.11	c6104	
14	AP supports Direct Link Broadcast radio connection	5.3.12	c6105	

c6101: IF A.45/5 -- If AP supports multicast
THEN m -- then mandatory
ELSE n/a

c6102: IF A.45/6 -- If AP supports broadcast
THEN m -- then mandatory
ELSE n/a

c6103: IF A.47/2 -- If AP supports Direct mode
THEN m -- then mandatory
ELSE n/a

c6104: IF A.45/5 AND A.47/2 -- If AP supports multicast AND Direct mode
THEN m -- then mandatory
ELSE n/a

c6105: IF A.45/6 AND A.47/2 -- If AP supports broadcast AND Direct mode
THEN m -- then mandatory
ELSE n/a

c6106: IF A.47/2 -- If AP supports Direct mode
THEN o -- then optional
ELSE n/a

A.7.2 RLC PDU descriptions, seen from AP

In the following PDU tables, statuses with M or O are the only valid cases, due to the direction of the PDU. When not applicable to a given direction, status n/a is defined. On many occasions, the conditional support is expressed by a prerequisite statement or an explicit condition.

A.7.2.1 PDU descriptions for ACF support

Table A.62: Association PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RBCH_ASSOCIATION		n/a		5.1.1.1	m	
2	RLC_RBCH_ASSOCIATION_REQ	5.1.1.1	m			n/a	
3	RLC_MAC_ID_ASSIGN	5.1.1.2	m			n/a	
4	RLC_MAC_ID_ASSIGN_ACK		n/a		5.1.1.2	m	
5	RLC_MAC_ID_ASSIGN_NACK		n/a		5.1.1.2	m	
6	RLC_LINK_CAPABILITY	5.1.1.3	m			n/a	
7	RLC_LINK_CAPABILITY_ACK		n/a		5.1.1.3	m	
8	RLC_INFO	5.1.1.8	c6201			n/a	
9	RLC_INFO_ACK		n/a		5.1.1.8	c6201	

c6201: IF A.46/7 -- AP supports info transfer
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.63: Security PDUs

Prerequisite: none, encryption support is mandatory

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_KEY_EXCHANGE_MT1	5.1.1.4	m			n/a	
2	RLC_KEY_EXCHANGE_MT2	5.1.1.4	m			n/a	
3	RLC_KEY_EXCHANGE_AP1		n/a		5.1.1.4	m	
4	RLC_KEY_EXCHANGE_AP2		n/a		5.1.1.4	m	
5	RLC_DM_COMMON_KEY_DISTR	5.1.1.7	c6301			n/a	
6	RLC_DM_COMMON_KEY_DISTR_ACK		n/a		5.1.1.7	c6301	
7	RLC_UNICAST_KEY_REFRESH		n/a		5.1.1.2	o	
8	RLC_UNICAST_KEY_REFRESH_ACK	5.1.1.2	o			n/a	
9	RLC_COMMON_KEY_REFRESH		n/a		5.1.2.3.3	o	
10	RLC_COMMON_KEY_REFRESH_ACK	5.1.2.3.3	o			n/a	
11	RLC_COMMON_KEY_ACTIVATE		n/a		5.1.2.3.3	o	

c6301: A.47/2 AP supports Direct mode
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.64: Authentication PDUs

Prerequisite: none, authentication support is mandatory

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_AUTHENTICATION	5.1.1.5	m			n/a	
2	RLC_AUTHENTICATION_MT		n/a		5.1.1.5	m	
3	RLC_AUTHENTICATION_AP_1	5.1.1.6	m			n/a	
4	RLC_AUTHENTICATION_AP_2	5.1.1.6	c6401			n/a	
5	RLC_AUTHENTICATION_AP_3	5.1.1.6	c6402			n/a	
6	RLC_AUTHENTICATION_ACK_1		n/a		5.1.1.6	m	
7	RLC_AUTHENTICATION_ACK_2		n/a		5.1.1.6	c6401	
8	RLC_AUTHENTICATION_ACK_3		n/a		5.1.1.6	c6403	

c6401: IF A.53/2 -- AP supports public key based authentication
 THEN m -- then mandatory
 ELSE n/a

c6402: IF A.54/2 OR A.54/3 -- AP supports RSA768 bit signature OR RSA1024 bit signature
 THEN m -- then mandatory
 ELSE n/a

c6403: IF A.54/3 -- AP supports RSA1024 bit signature
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

Table A.65: Disassociation PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DISASSOCIATION	5.1.3	m		5.1.3	m	
2	RLC_DISASSOCIATION_ACK	5.1.3	m		5.1.3	m	

Comments:

.....

Table A.66: MULTICAST PDUs

Prerequisite: A.45/5 AP supports Multicast

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_GROUP_JOIN	5.1.4	m			n/a	
2	RLC_GROUP_JOIN_ACK		n/a		5.1.4	m	
3	RLC_GROUP_JOIN_NACK		n/a		5.1.4	m	
4	RLC_GROUP_LEAVE	5.1.4	m			n/a	
5	RLC_GROUP_LEAVE_ACK		n/a		5.1.4	m	

Comments:

.....

Table A.67: BROADCAST PDUs

Prerequisite: A.45/6 AP supports Broadcast

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_CL_BROADCAST_JOIN	5.1.5	m			n/a	
2	RLC_CL_BROADCAST_JOIN_ACK		n/a		5.1.5	m	
3	RLC_GROUP_LEAVE	5.1.4	c6701			n/a	
4	RLC_GROUP_LEAVE_ACK		n/a		5.1.4	c6701	

c6701: IF A.57/2 AP supports broadcast leave message
 THEN m -- then mandatory
 ELSE n/a

Comments:

A.7.2.2 PDU descriptions for RRC support

Table A.68: HANDOVER PDUs

Prerequisite: A.58/1 -- AP supports handover

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SECTOR_HANDOVER_REQUEST	5.2.1.1	c6801			n/a	
2	RLC_SECTOR_HANDOVER_ACK		n/a		5.2.1.1	c6801	
3	RLC_HANDOVER_NOTIFY	5.2.1.2	c6804			n/a	
4	RLC_HANDOVER_REQUEST	5.2.1.2	m			n/a	
5	RLC_RADIO_HANDOVER_COMPLETE		n/a		5.2.1.2	c6802	
6	RLC_HANDOVER_ASSOCIATION		n/a		5.2.1.3	m	
7	RLC_HANDOVER_LINK_CAPABILITY_ACK		n/a		5.2.1.3	m	
8	RLC_NW_SIGNALLING_HANDOVER	5.2.1.3	m			n/a	
9	RLC_NW_SIGNALLING_HANDOVER_ACK		n/a		5.2.1.3	m	
10	RLC_HO_INFO_DISTRIBUTION		n/a		5.2.1.4	m	
11	RLC_HO_INFO_DISTRIBUTION_ACK	5.2.1.4	m			n/a	
12	RLC_NETWORK_HANDOVER_COMPLETE		n/a		5.2.1.4	m	
13	RLC_FORCE_HANDOVER		n/a		5.2.1.6	c6803	
14	RLC_FORCE_HANDOVER_ACK	5.2.1.6	c6803			n/a	
15	RLC_HANDOVER_REQUEST_NACK	5.2.1.5	n/a		5.2.1.5	m	

c6801: IF A.59/1 - - AP supports Sector Handover
 THEN m -- then mandatory
 ELSE n/a

c6802: IF A.59/2 - - AP supports Radio Handover
 THEN m -- then mandatory
 ELSE n/a

c6803: IF A.59/5 - - AP supports Forced Handover
 THEN m -- then mandatory
 ELSE n/a

c6804: IF A.59/7 - - AP is notified by MT of Handover
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.69: DFS measurement PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_AP_ABSENCE		n/a		5.2.2.4	c6902	
2	RLC_DFS_MEASUREMENT_SHORT_REQUEST		n/a		5.2.2.4	m	
3	RLC_DFS_MEASUREMENT_PERCENTILES_REQUEST		n/a		5.2.2.4	m	
4	RLC_DFS_MEASUREMENT_COMPLETE_REQUEST		n/a		5.2.2.4	m	
5	RLC_DFS_MT_INIT_REPORT_REQUEST	5.2.2.4	c6901			n/a	
6	RLC_DFS_MT_INIT_REPORT_REQUEST_ACK		n/a		5.2.2.4	c6901	
7	RLC_DFS_REPORT_SHORT	5.2.2.4	m			n/a	
8	RLC_DFS_REPORT_PERCENTILES	5.2.2.4	m			n/a	
9	RLC_DFS_REPORT_COMPLETE	5.2.2.4	m			n/a	

c6901: IF A.60/2 - - AP accepts MT self initiated measurement reports
 THEN m -- then mandatory
 ELSE n/a

c6902: IF A.58/5 - - AP supports MT Absence
 THEN m -- then mandatory
 ELSE n/a

Comments:

.....

.....

Table A.70: Change Frequency PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_CHANGE_FREQUENCY		n/a		5.2.2.6	m	

Table A.71: Transmission Power Control PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_UPLINK_PC_CALIBRATION		n/a		5.2.3	m	
2	RLC_MT_ALIVE_REQUEST		n/a		5.2.4	m	
3	RLC_MT_ALIVE_REQUEST_ACK	5.2.4	m			n/a	
4	RLC_MT_ALIVE	5.2.4	m			n/a	
5	RLC_MT_ALIVE_ACK		n/a		5.2.4	m	

Table A.72: Absence PDUs

Prerequisite: A.58/5 -- AP supports Absence

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_MT_ABSENCE_	5.2.5	m			n/a	
2	RLC_MT_ABSENCE_ACK		n/a		5.2.5	m	

Table A.73: Power saving / Power control PDUs

Prerequisite: none -- mandatory for AP to support Power saving

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SLEEP	5.2.6	m			n/a	
2	RLC_SLEEP_ACK		n/a		5.2.6	m	

A.7.2.3 PDU descriptions for DUC support

Table A.74: DUC setup PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_SETUP	5.3.1.2	m		5.3.1.1	c7401	
2	RLC_CONNECT	5.3.1.1	c7401		5.3.1.2	m	
3	RLC_CONNECT_ACK	5.3.1.2	m		5.3.1.1	c7401	

c7401: IF A.61/2 -- AP initiates DUC setup
 THEN m -- then mandatory
 ELSE n/a

Table A.75: DUC release PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELEASE	5.3.2.2	m		5.3.2.1	m	
2	RLC_RELEASE_ACK	5.3.2.1	m		5.3.2.2	m	

Comments:

.....

Table A.76: DUC modify PDUs

Prerequisite: A.61/4 AP supports DUC modify

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_MODIFY_REQ	5.3.3.2	m		5.3.3.1	m	
2	RLC_MODIFY	5.3.3.1	m		5.3.3.2	m	
3	RLC_MODIFY_ACK	5.3.3.2	m		5.3.3.1	m	

Comments:

.....

.....

Table A.77: DUC reset PDUs

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RESET	5.3.4.2	m		5.3.4.1	m	
2	RLC_RESET_ACK	5.3.4.1	m		5.3.4.2	m	

Comments:

.....

.....

Table A.78: Direct link DUC setup PDUs

Prerequisite: A.47/2 AP supports Direct mode

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_SETUP	5.3.7.2			5.3.7.1	m	
2	RLC_DM_CONNECT	5.3.7.1	m		5.3.7.2	m	
3	RLC_DM_CONNECT_ACK	5.3.7.2	m		5.3.7.1	m	
4	RLC_DM_CONNECT_COMPLETE		n/a		5.3.7.1	m	
5	RLC_DM_CONNECT_COMPLETE_ACK	5.3.7.1	m			n/a	

Comments:

.....

.....

Table A.79: RLC_RELAY PDUs

Prerequisite: A.47/2 AP supports Direct mode, in which case, relay is mandatory for AP

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_SETUP	5.3.7.3	m			n/a	
2	RLC_RELAY_SETUP_ACK		n/a		5.3.7.3	m	

Comments:

.....

.....

Table A.80: Direct link DUC release PDUs

Prerequisite: A.47/2 AP supports Direct mode

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_RELEASE	5.3.8.2	m		5.3.8.1	m	
2	RLC_DM_RELEASE_ACK	5.3.8.1	m		5.3.8.2	m	

Comments:

.....

.....

Table A.81: Direct link DUC relay release PDUs

Prerequisite: A.47/2 AP supports Direct mode, in which case, relay is mandatory for AP

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_RELEASE	5.3.8.3	m		5.3.8.3	m	
2	RLC_RELAY_RELEASE_ACK	5.3.8.3	m		5.3.8.3	m	

Comments:

.....

.....

Table A.82: Direct link DUC modify PDUs

Prerequisite: A.47/2 AP supports Direct mode

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_MODIFY_REQ	5.3.9.2	m		5.3.9.1	m	
2	RLC_DM_MODIFY	5.3.9.1	m		5.3.9.2	m	
3	RLC_DM_MODIFY_ACK	5.3.9.2	m		5.3.9.1	m	
4	RLC_DM_MODIFY_COMPLETE		n/a		5.3.9.1	m	
5	RLC_DM_MODIFY_COMPLETE_A CK	5.3.9.1	m		6.3.7.1	m	

Comments:

.....

.....

Table A.83: Direct link DUC relay modify PDUs

Prerequisite: A.47/2 AP supports Direct mode, in which case, relay is mandatory for AP

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_RELAY_MODIFY	5.3.9.3	m			n/a	
2	RLC_RELAY_MODIFY_ACK		n/a		5.3.9.3	m	

Comments:

.....

.....

Table A.84: Direct link DUC reset PDUs

Prerequisite: A.47/2 AP supports Direct mode

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_DM_RESET	5.3.10.2	m		5.3.10.1	m	
2	RLC_DM_RESET_ACK	5.3.10.1	m		5.3.10.2	m	

Comments:

.....

.....

A.7.2.4 PDU descriptions for unsupported messages

Table A.85

Item	PDU	AP receiving			AP sending		
		Reference	Status	Support	Reference	Status	Support
1	RLC_NO_SUPPORT	7	m		7	m	

Comments:

.....

.....

A.7.3 PDU parameters

See clause A.8, common to MT and AP.

A.8 PDU parameters

Prerequisites are specified, according to PDU status conditions. They differ whether it is an AP or an MT.

A.8.1 Parameters of PDUs for ACF support

A.8.1.1 Association

Table A.86: RLC_RBCH_ASSOCIATION parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.1, annex B	m	
2	network-operator-id	5.1.1.1, annex B	m See Note	
3	profile-vid-list	5.1.1.1, annex B	m	

NOTE: Should be defined as optional (o) as it is irrelevant for Home Environment profile

Comments:

.....

.....

Table A.87: RLC_RBCH_ASSOCIATION_REQ parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.1, annex B	m	
2	ap-id	5.1.1.1, annex B	m	
3	net-id	5.1.1.1, annex B	m	
4	mac-id	5.1.1.1, annex B	m	

Comments:

.....

.....

Table A.88: RLC_MAC_ID_ASSIGN parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.2, annex B	m	
2	magic	5.1.1.2, annex B	m	
3	rlc-version	5.1.1.2, annex B	m	
4	mac-id	5.1.1.2, annex B	m	

Comments:

.....

.....

Table A.89: RLC_MAC_ID_ASSIGN_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.2, annex B	m	
2	magic	5.1.1.2, annex B	m	
3	mac-id	5.1.1.2, annex B	m	
4	mac-id1	5.1.1.2, annex B	m	

Comments:

.....

.....

Table A.90: RLC_MAC_ID_ASSIGN_NACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.2, annex B	m	
2	magic	5.1.1.2, annex B	m	

Comments:

.....

.....

Table A.91: RLC_LINK_CAPABILITY parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.3, annex B	m	
2	dlc-version	5.1.1.3, annex B	m	
3	rlc-version	5.1.1.3, annex B	m	
4	cl-vid-list	5.1.1.3, annex B	m	
5	rss-value	5.1.1.3, annex B	m	
6	support64QAM	5.1.1.3, annex B	m	
7	freq-band	5.1.1.3, annex B	m	
8	direct-mode-cap	5.1.1.3, annex B	m	
9	cyclic-prefix	5.1.1.3, annex B	m	
10	support-fca	5.1.1.3, annex B	m	
11	support-fsa	5.1.1.3, annex B	m	
12	Ho-cap	5.1.1.3, annex B	m	
13	Cc-ho-cap	5.1.1.3, annex B	m	
14	time-gap-ach-uplink	5.1.1.3, annex B	m	
15	duty-cycle	5.1.1.3, annex B	m	
16	arq-delay-rx	5.1.1.3, annex B	m	
17	arq-delay-tx	5.1.1.3, annex B	m	
18	authentication-encryption-list	5.1.1.3, annex B	m	
19	dm-attributes	5.1.1.3, annex B	c9101	

c9101: IF A.5/2 MT supports Direct mode or A.47/2 AP supports Direct mode
 THEN mandatory
 ELSE n/a

Comments:

.....

.....

Table A.92: RLC_LINK_CAPABILITY_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.3, annex B	m	
2	profile-vid-list-selected	5.1.1.3, annex B	m	
3	freq-band	5.1.1.3, annex B	m	
4	rss-value	5.1.1.3, annex B	m	
5	apt-address-length	5.1.1.3, annex B	m	
6	support64QAM	5.1.1.3, annex B	m	
7	direct-mode-use-common-key	5.1.1.3, annex B	m	
8	direct-mode-cap	5.1.1.3, annex B	m	
9	cyclic-prefix	5.1.1.3, annex B	m	
10	support-fca	5.1.1.3, annex B	m	
11	support-fsa	5.1.1.3, annex B	m	
12	cc-ho-cap	5.1.1.3, annex B	m	
13	arq-delay-rx	5.1.1.3, annex B	m	
14	arq-delay-tx	5.1.1.3, annex B	m	
15	auth-encr-selected	5.1.1.3, annex B	m	
16	dm-attributes	5.1.1.3, annex B	c9201	

c9201: IF A.5/2 MT supports Direct mode or A.47/2 AP supports Direct mode
 THEN mandatory
 ELSE n/A

Comments:

.....

.....

Table A.93: RLC_INFO parameters

Prerequisite:

A.4/7 -- MT supports info transfer
 or
 A.46/7-- AP supports info transfer

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.8, annex B	m	
2	info-type	5.1.1.8, annex B	m	
3	info-count	5.1.1.8, annex B	m	
4	cl-data	5.1.1.8, annex B	o	
5	dlc-attributes	5.1.1.8, annex B	m	

Comments:

.....

.....

Table A.94: RLC_INFO_ACK parameters

Prerequisite:

A.4/7 -- MT supports info transfer

or

A.46/7-- AP supports info transfer

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.8, annex B	m	
2	info-count	5.1.1.8, annex B	m	
3	ci-data	5.1.1.8, annex B	o	
4	dlc-attributes	5.1.1.8, annex B	m	

Comments:

.....

.....

A.8.1.2 Security

Table A.95: RLC_KEY_EXCHANGE_MT_1 parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.4, annex B	m	
2	mt-dh-public-value-1	5.1.1.4, annex B	m	

Comments:

.....

.....

Table A.96: RLC_KEY_EXCHANGE_MT_2 parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.4, annex B	m	
2	mt-dh-public-value-2	5.1.1.4, annex B	m	

Comments:

.....

.....

Table A.97: RLC_KEY_EXCHANGE_AP_1 parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.4, annex B	m	
2	ap-dh-public-value-1	5.1.1.4, annex B	m	

Comments:

.....

.....

Table A.98: RLC_KEY_EXCHANGE_AP_2 parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.4, annex B	m	
2	ap-dh-public-value-2	5.1.1.4, annex B	m	

Comments:

.....

.....

Table A.99: RLC_DM_COMMON_KEY_DISTR parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.7, annex B	m	
2	dm-encr-alg	5.1.1.7, annex B	m	
3	key-id	5.1.1.7, annex B	m	
4	common-key	5.1.1.7, annex B	m	

Comments:

.....

.....

Table A.100: RLC_DM_COMMON_KEY_DISTR_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.7, annex B	m	
2	dm-encr-alg	5.1.1.7, annex B	m	
3	md5-on-key	5.1.1.7, annex B	m	

Comments:

.....

.....

Table A.101: RLC_UNICAST_KEY_REFRESH parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.2.2, annex B	m	
2	nonce	5.1.2.2, annex B	m	

Comments:

.....

.....

Table A.102: RLC_UNICAST_KEY_REFRESH_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.2.2, annex B	m	
2	md5-on-nonce	5.1.2.2, annex B	m	

Comments:

.....

.....

Table A.103: RLC_COMMON_KEY_REFRESH parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.2.3.3, annex B	m	
2	encr-info	5.1.2.3.3, annex B	m	
3	key-id	5.1.2.3.3, annex B	m	
4	common-key	5.1.2.3.3, annex B	m	

Comments:

.....

.....

Table A.104: RLC_COMMON_KEY_REFRESH_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.2.3.3, annex B	m	
2	encr-info	5.1.2.3.3, annex B	m	
3	md5-on-key	5.1.2.3.3, annex B	m	

Comments:

.....

.....

Table A.105: RLC_COMMON_KEY_ACTIVATE parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.2.3.3, annex B	m	
2	key-id	5.1.2.3.3, annex B	m	
3	last-mac-frame	5.1.2.3.3, annex B	m	

Comments:

.....

.....

A.8.1.3 Authentication

Table A.106: RLC_AUTHENTICATION parameters

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.5, annex B	m	
2	more	5.1.1.5, annex B	m	
3	mt-auth-id-type	5.1.1.5, annex B	m	
4	mt-auth-id-content	5.1.1.5, annex B	m	

Comments:

.....

.....

Table A.107: RLC_AUTHENTICATION_MT parameters

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.5, annex B	m	
2	challenge-to-mt	5.1.1.5, annex B	m	

Comments:

.....

.....

Table A.108: RLC_AUTHENTICATION_AP_1 parameters

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	challenge-to-ap	5.1.1.6, annex B	m	
3	mt-response-1	5.1.1.6, annex B	m	

Comments:

.....

.....

Table A.109: RLC_AUTHENTICATION_AP_2 parameters

Prerequisite:

A.11 /2 -- MT supports public key based authentication

or

A.53/2-- AP supports public key based authentication

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	mt-response-2	5.1.1.6, annex B	m	

Comments:

.....

.....

Table A.110: RLC_AUTHENTICATION_AP_3 parameters

Prerequisite:

A.12/2 OR A.12/3 -- MT supports RSA768 bit signature OR RSA1024 bit signature

or

A.54/2 OR A.54/3 -- AP supports RSA768 bit signature OR RSA1024 bit signature

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	mt-response-2	5.1.1.6, annex B	m	

Comments:

.....

.....

Table A.111: RLC_AUTHENTICATION_ACK-1 parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	ap-response-2	5.1.1.6, annex B	m	

Comments:

.....

.....

Table A.112: RLC_AUTHENTICATION_ACK-2 parameters

Prerequisite:

A.11 /2 -- MT supports public key based authentication

or

A.53/2-- AP supports public key based authentication

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	ap-response-2	5.1.1.6, annex B	m	

Comments:

.....

.....

Table A.113: RLC_AUTHENTICATION_ACK-3 parameters

Prerequisite:

A.54/3-- AP supports RSA1024 bit signature

or

A.12/3-- MT supports RSA1024 bit signature

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.1.6, annex B	m	
2	ap-response-2	5.1.1.6, annex B	m	

Comments:

.....

.....

A.8.1.4 Disassociation

Table A.114: RLC_DISASSOCIATION parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.3, annex B	m	
2	disassociation-cause	5.1.3, annex B	m	
3	mac-id	5.1.3, annex B	m	

Comments:

.....

.....

Table A.115: RLC_DISASSOCIATION_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.3, annex B	m	
2	mac-id	5.1.3, annex B	m	

Comments:

.....

.....

A.8.1.5 Multicast

Table A.116: RLC_GROUP_JOIN parameters

Prerequisite: A.3/5 MT supports Multicast

or

Prerequisite: A.45/5 AP supports Multicast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.4, annex B	m	
2	cl-data	5.1.4, annex B	m	
3	encryption-algorithm-proposal	5.1.4, annex B	m	

Comments:

.....

.....

Table A.117: RLC_GROUP_JOIN_ACK parameters

Prerequisite: A.3/5 MT supports Multicast

or

Prerequisite: A.45/5 AP supports Multicast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.4, annex B	m	
2	more-joins	5.1.4, annex B	m	
3	mac-id-and-cl-data-list	5.1.4, annex B	m	
4	encryption-algorithm-selected	5.1.4, annex B	m	
5	key-id	5.1.4, annex B	m	
6	common-key	5.1.4, annex B	m	

Comments:

.....

.....

Table A.118: RLC_GROUP_JOIN_NACK parameters

Prerequisite: A.3/5 MT supports Multicast

or

Prerequisite: A.45/5 AP supports Multicast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.4, annex B	m	
2	more-joins	5.1.4, annex B	m	
3	mac-id-and-cl-data-list	5.1.4, annex B	m	

Comments:

.....

.....

Table A.119: RLC_GROUP_LEAVE parameters

Prerequisite: A.3/5 MT supports Multicast

or

Prerequisite: A.45/5 AP supports Multicast

1	rlc-pdu-type	5.1.4, annex B	m	
2	cl-data	5.1.4, annex B	m	

Comments:

.....

.....

Table A.120: RLC_GROUP_LEAVE_ACK parameters

Prerequisite: A.3/5 MT supports Multicast

or

Prerequisite: A.45/5 AP supports Multicast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.4, annex B	m	
2	cl-data	5.1.4, annex B	m	

Comments:

.....

.....

A.8.1.6 Broadcast

Table A.121: RLC_CL_BROADCAST_JOIN parameters

Prerequisite: A.3/6 MT supports Broadcast

or

Prerequisite: A.45/6 AP supports Broadcast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.5, annex B	m	
2	cl-data	5.1.5, annex B	m	
3	encryption-algorithm-proposal	5.1.5, annex B	m	

Comments:

.....

.....

Table A.122: RLC_CL_BROADCAST_JOIN_ACK parameters

Prerequisite: A.3/6 MT supports Broadcast

or

Prerequisite: A.45/6 AP supports Broadcast

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.5, annex B	m	
2	more-joins	5.1.5, annex B	m	
3	window-size	5.1.5, annex B	m	
4	mac-id-and-cl-data-list	5.1.5, annex B	m	
5	encryption-algorithm-selected	5.1.5, annex B	m	
6	key-id	5.1.5, annex B	m	
7	common-key	5.1.5, annex B	m	
8	error-corr-mode	5.1.5, annex B	m	

Comments:

.....

.....

Table A.123: RLC_CL_BROADCAST_LEAVE parameters

Prerequisite: A.3/6 MT supports Broadcast AND A.15/2 MT supports Broadcast leave message

or

Prerequisite: A.45/6 AP supports Broadcast AND A.57/2 AP supports Broadcast leave message

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.5, annex B	m	
2	cl-data	5.1.5, annex B	m	

Comments:

.....

.....

Table A.124: RLC_CL_BROADCAST_LEAVE_ACK parameters

Prerequisite: A.3/6 MT supports Broadcast AND A.15/2 MT supports Broadcast leave message

or

Prerequisite: A.45/6 AP supports Broadcast AND A.57/2 AP supports Broadcast leave message

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.1.5, annex B	m	
2	cl-data	5.1.5, annex B	m	

Comments:

.....

.....

A.8.2 Parameters of PDUs for RRC support

A.8.2.1 Handover

Table A.125: RLC_SECTOR_HANOVER_REQUEST parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/1 - - AP supports Sector Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.1, annex B	m	
2	sector-id-new	5.2.1.1, annex B	m	
3	mac-id	5.2.1.1, annex B	m	

Comments:

.....

.....

Table A.126: RLC_SECTOR_HANOVER_ACK parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/1 - - AP supports Sector Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.1, annex B	m	

Comments:

.....

.....

Table A.127: RLC_HANOVER_NOTIFY parameters

Prerequisite: A.16 /1 -- MT supports handover AND A.17/7 - - MT notifies AP of Handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/7 - - AP is notified by MT of Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.2, annex B	m	
2	handover-cause	5.2.1.2, annex B	m	
3	ap-id	5.2.1.2, annex B	m	
4	net-id	5.2.1.2, annex B	m	
5	mac-id	5.2.1.2, annex B	m	

Comments:

.....

.....

Table A.128: RLC_HANDOVER_REQUEST parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.2, annex B	m	
2	mac-ld-old	5.2.1.2, annex B	m	
3	ap-ld-old	5.2.1.2, annex B	m	
4	net-ld-old	5.2.1.2, annex B	m	
5	duc-established	5.2.1.2, annex B	m	

Comments:

.....

.....

Table A.129: RLC_RADIO_HANDOVER_COMPLETE parameters

Prerequisite: A.16 /1 -- MT supports handover AND A.17/2 - - MT supports Radio Handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/2 - - AP supports Radio Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.2, annex B	m	
2	mac-id-old	5.2.1.2, annex B	m	
3	ap-id-old	5.2.1.2, annex B	m	
4	net-id-old	5.2.1.2, annex B	m	
5	mac-id-new	5.2.1.2, annex B	m	
6	cl-id	5.2.1.2, annex B	m	
7	duc-ext-ind	5.2.1.2, annex B	m	
8	cl-conn-attr-length	5.2.1.2, annex B	m	
9	duc-descr-list	5.2.1.2, annex B	m	

Comments:

.....

.....

Table A.130: RLC_HANDOVER_ASSOCIATION parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.3, annex B	m	
2	mac-id-old	5.2.1.3, annex B	m	
3	ap-id-old	5.2.1.3, annex B	m	
4	net-id-old	5.2.1.3, annex B	m	
5	mac-id-new	5.2.1.3, annex B	m	

Comments:

.....

.....

Table A.131: RLC_HANDOVER_LINK_CAPABILITY_ACK parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.3, annex B	m	
2	profile-vid-list	5.2.1.3, annex B	m	
3	freq-band	5.2.1.3, annex B	m	
4	rss-value	5.2.1.3, annex B	m	
5	apt-address-length	5.2.1.3, annex B	m	
6	support64QAM	5.2.1.3, annex B	m	
7	direct-mode-cap	5.2.1.3, annex B	m	
8	dm-use-common-key	5.2.1.3, annex B	m	
9	cyclic-prefix	5.2.1.3, annex B	m	
10	support-fca	5.2.1.3, annex B	m	
11	support-fsa	5.2.1.3, annex B	m	
12	arq-delay-rx	5.2.1.3, annex B	m	
13	arq-delay-tx	5.2.1.3, annex B	m	
14	auth-encr-selected	5.2.1.3, annex B	m	
15	start-encryption	5.2.1.3, annex B	m	
16	start-authentication	5.2.1.3, annex B	m	
17	Send-NW-Token	5.2.1.3, annex B	m	
18	Start-DUC-setup	5.2.1.3, annex B	m	
19	keep-connections	5.2.1.3, annex B	m	
20	Start-info-transfer	5.2.1.3, annex B	m	
21	dm-attributes	5.2.1.3, annex B	c13101	

c13101: IF A.5/2 MT supports Direct mode or A.47/2 AP supports Direct mode
 THEN mandatory
 ELSE n/a

Comments:

.....

Table A.132: RLC_NW_SIGNALLING_HANDOVER parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.3, annex B	m	
2	mt-token-auth-encr	5.2.1.3, annex B	c	

Comments:

.....

Table A.133: RLC_NW_SIGNALLING_HANDOVER_ACK parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.3, annex B	m	
2	ap-token-auth-encr	5.2.1.3, annex B	c	

Comments:

.....

.....

Table A.134: RLC_HO_INFO_DISTRIBUTION parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.4, annex B	m	
2	token	5.2.1.4, annex B	m	

Comments:

.....

.....

Table A.135: RLC_HO_INFO_DISTRIBUTION_ACK parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.4, annex B	m	
2	mac-id	5.2.1.4, annex B	m	

Comments:

.....

.....

Table A.136: RLC_NETWORK_HANDOVER_COMPLETE parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.4, annex B	m	
2	cl-id	5.2.1.4, annex B	m	
3	duc-ext-ind	5.2.1.4, annex B	m	
4	cl-conn-attr-length	5.2.1.4, annex B	m	
5	duc-descr-list	5.2.1.4, annex B	m	

Comments:

.....

.....

Table A.137: RLC_HANDOVER_REQUEST_NACK parameters

Prerequisite: A.16 /1 -- MT supports handover

or

Prerequisite: A.58/1 -- AP supports handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.5, annex B	m	
2	mac-id-old	5.2.1.5, annex B	m	
3	ap-id-old	5.2.1.5, annex B	m	
4	net-id-old	5.2.1.5, annex B	m	

Table A.138: RLC_FORCE_HANDOVER parameters

Prerequisite: A.16 /1 -- MT supports handover AND A.17/5 - - MT supports Forced Handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/5 - - AP supports Forced Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.6, annex B	m	
2	return-flag	5.2.1.6, annex B	m	
3	force-handover-cause	5.2.1.6, annex B	m	
4	frequency-index	5.2.1.6, annex B	m	
5	ap-id	5.2.1.6, annex B	m	
6	net-id	5.2.1.6, annex B	m	

Comments:

.....

.....

Table A.139: RLC_FORCE_HANDOVER_ACK parameters

Prerequisite: A.16 /1 -- MT supports handover AND A.17/5 - - MT supports Forced Handover

or

Prerequisite: A.58/1 -- AP supports handover AND A.59/5 - - AP supports Forced Handover

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.1.6, annex B	m	
2	mac-id	5.2.1.6, annex B	m	

A.8.2.2 Dynamic Frequency Selection (DFS)

Table A.140: RLC_AP_ABSENCE parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	first-mac-frame	5.2.2.4, annex B	m	
3	last-mac-frame	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.141: RLC_DFS_MEASUREMENT_SHORT_REQUEST parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	use-omni-antenna	5.2.2.4, annex B	m	
4	start-of-measurement	5.2.2.4, annex B	m	
5	length-of-measurement	5.2.2.4, annex B	m	
6	maximum-age-of-measurement	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.142: RLC_DFS_MEASUREMENT_PERCENTILES_REQUEST parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	use-omni-antenna	5.2.2.4, annex B	m	
4	start-of-measurement	5.2.2.4, annex B	m	
5	measurement-window	5.2.2.4, annex B	m	
6	rss-index-list	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.143: RLC_DFS_MEASUREMENT_COMPLETE_REQUEST parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	use-omni-antenna	5.2.2.4, annex B	m	
4	start-of-measurement	5.2.2.4, annex B	m	
5	measurement-window	5.2.2.4, annex B	m	
6	maximum-age-of-bch-measurement	5.2.2.4, annex B	m	
7	rss-index-list	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.144: RLC_DFS_MT_INIT_REPORT_REQUEST parameters

Prerequisite: A.18/2 - - MT performs and reports self initiated measurements

or

Prerequisite: A.60/2 - - AP accepts MT self initiated measurement reports

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	measurement-type	5.2.2.4, annex B	m	
3	frequency-index	5.2.2.4, annex B	m	
4	adjacent-ch-interference	5.2.2.4, annex B	m	
5	mac-id	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.145: RLC_DFS_MT_INIT_REPORT_REQUEST_ACK parameters

Prerequisite: A.18/2 - - MT performs and reports self initiated measurements

or

Prerequisite: A.60/2 - - AP accepts MT self initiated measurement reports

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	reporting-initialized	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.146: RLC_DFS_REPORT_SHORT parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	omni-antenna-used	5.2.2.4, annex B	m	
4	age-of-measurement	5.2.2.4, annex B	m	
5	last-own-bch-rx-level	5.2.2.4, annex B	m	
6	bch-found	5.2.2.4, annex B	m	
7	traffic-load	5.2.2.4, annex B	m	
8	ap-id	5.2.2.4, annex B	m	
9	tx-level	5.2.2.4, annex B	m	
10	net-ld	5.2.2.4, annex B	m	
11	bch-rx-Level	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.147: RLC_DFS_REPORT_PERCENTILES parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	omni-antenna-used	5.2.2.4, annex B	m	
4	last-own-bch-rx-level	5.2.2.4, annex B	m	
5	number-of-samples	5.2.2.4, annex B	m	
6	rss-index-list	5.2.2.4, annex B	m	
7	rss-statistics-list	5.2.2.4, annex B	m	

Comments:

.....

.....

Table A.148: RLC_DFS_REPORT_COMPLETE parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.4, annex B	m	
2	frequency-index	5.2.2.4, annex B	m	
3	omni-antenna-used	5.2.2.4, annex B	m	
4	age-of-measurement	5.2.2.4, annex B	m	
5	last-own-bch-rx-level	5.2.2.4, annex B	m	
6	number-of-samples	5.2.2.4, annex B	m	
7	bch-found	5.2.2.4, annex B	m	
8	traffic-load	5.2.2.4, annex B	m	
9	ap-id	5.2.2.4, annex B	m	
10	tx-level	5.2.2.4, annex B	m	
11	net-Id	5.2.2.4, annex B	m	
12	bch-rx-Level	5.2.2.4, annex B	m	
13	rss-index-list	5.2.2.4, annex B	m	
14	rss-statistics-list	5.2.2.4, annex B	m	

Comments:

.....

.....

A.8.2.3 Change frequency

Table A.149: RLC_CHANGE_FREQUENCY parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.2.6, annex B	m	
2	first-mac-frame	5.2.2.6, annex B	m	
3	last-mac-frame	5.2.2.6, annex B	m	
4	frequency-index	5.2.2.6, annex B	m	

Comments:

.....

.....

A.8.2.4 Uplink power control

Table A.150: RLC_UPLINK_PC_CALIBRATION parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.3.1, annex B	m	
2	pc-offset	5.2.3.1, annex B	m	

Comments:

.....

.....

A.8.2.5 MT alive

Table A.151: RLC_MT_ALIVE_REQUEST parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.4, annex B	m	
2	mt-alive-interval	5.2.4, annex B	m	

Comments:

.....

.....

Table A.152: RLC_MT_ALIVE_REQUEST_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.4, annex B	m	
2	mac-id	5.2.4, annex B	m	

Comments:

.....

.....

Table A.153: RLC_MT_ALIVE parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.4, annex B	m	
2	mac-id	5.2.4, annex B	m	

Comments:

.....

.....

Table A.154: RLC_MT_ALIVE_ACK parameters

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.4, annex B	m	

Comments:

.....

.....

A.8.2.6 MT absence

Table A.155: RLC_MT_ABSENCE parameters

Prerequisite: A.16/5 -- MT supports Absence

or

Prerequisite: A.58/5 -- AP supports Absence

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.5, annex B	m	
2	mt-absence-time	5.2.5, annex B	m	
3	mac-id	5.2.5, annex B	m	

Comments:

.....

.....

Table A.156: RLC_MT_ABSENCE_ACK parameters

Prerequisite: A.16 /5 -- MT supports Absence

or

Prerequisite: A.58/5 -- AP supports Absence

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.5, annex B	m	

Comments:

.....

.....

A.8.2.7 Power saving

Table A.157: RLC_SLEEP_REQUEST parameters

Prerequisite: A.16 /6 -- MT supports Power saving

or

Prerequisite: none -- mandatory for AP to support Power saving

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.6, annex B	m	
2	care-of-broadcast	5.2.6, annex B	m	
3	sleep-group	5.2.6, annex B	m	
4	mac-id	5.2.6, annex B	m	

Comments:

.....

.....

Table A.158: RLC_SLEEP_ACK parameters

Prerequisite: A.16 /6 -- MT supports Power saving

or

Prerequisite: none -- mandatory for AP to support Power saving

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.2.6, annex B	m	
2	care-of-broadcast	5.2.6, annex B	m	
3	sleep-group	5.2.6, annex B	m	
4	offset	5.2.6, annex B	m	

Comments:

.....

.....

A.8.3 Parameters of PDUs for DUC support

A.8.3.1 DUC setup

Table A.159: RLC_SETUP parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.1.1, annex B	m	
2	cl-id	5.3.1.1, annex B	m	
3	duc-ext-ind	5.3.1.1, annex B	m	
4	cl-conn-attr-length	5.3.1.1, annex B	m	
5	duc-descr-list	5.3.1.1, annex B	m	

Comments:

.....

.....

Table A.160: RLC_CONNECT parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.1.1, annex B	m	
2	cl-id	5.3.1.1, annex B	m	
3	cl-conn-attr-length	5.3.1.1, annex B	m	
4	duc-descr-list	5.3.1.1, annex B	m	

Comments:

.....

.....

Table A.161: RLC_CONNECT_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.1.1, annex B	m	
2	cl-id	5.3.1.1, annex B	m	
3	cl-conn-attr-length	5.3.1.1, annex B	m	
4	dlcc-descr-list	5.3.1.1, annex B	m	

Comments:

.....

.....

A.8.3.2 DUC release

Table A.162: RLC_RELEASE parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.2.1, annex B	m	
2	release-cause	5.3.2.1, annex B	m	
3	dlcc-id-list	5.3.2.1, annex B	m	

Comments:

.....

.....

Table A.163: RLC_RELEASE_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.2.1, annex B	m	
2	dlcc-id-list	5.3.2.1, annex B	m	

Comments:

.....

.....

A.8.3.3 DUC modify

Table A.164: RLC_MODIFY_REQ parameters

Prerequisite: A.21/4 MT supports Modify radio connection

or

A.61/4 AP supports DUC modify

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.3.1, annex B	m	
2	duc-ext-ind	5.3.3.1, annex B	m	
3	cl-conn-attr-length	5.3.3.1, annex B	m	
4	duc-descr-list	5.3.3.1, annex B	m	

Comments:

.....

.....

Table A.165: RLC_MODIFY parameters

Prerequisite: A.21/4 MT supports Modify radio connection
or
A.61/4 AP supports DUC modify

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.3.1, annex B	m	
2	cl-conn-attr-length	5.3.3.1, annex B	m	
3	duc-descr-list	5.3.3.1, annex B	m	

Comments:

.....

.....

Table A.166: RLC_MODIFY_ACK parameters

Prerequisite: A.21/4 MT supports Modify radio connection
or
A.61/4 AP supports DUC modify

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.3.1, annex B	m	
2	cl-conn-attr-length	5.3.3.1, annex B	m	
3	dlcc-descr-list	5.3.3.1, annex B	m	

Comments:

.....

.....

Table A.167: RLC_RESET parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.4.1, annex B	m	
2	dlcc-id-list	5.3.4.1, annex B	m	

Comments:

.....

.....

Table A.168: RLC_RESET_ACK parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.4.1, annex B	m	
2	dlcc-id-list	5.3.4.1, annex B	m	

Comments:

.....

.....

A.8.3.4 Direct Mode DUC setup

Table A.169: RLC_DM_SETUP parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.1, annex B	m	
2	peer-mac-id	5.3.7.1, annex B	m	
3	cl-id	5.3.7.1, annex B	m	
4	duc-ext-ind	5.3.7.1, annex B	m	
5	cl-conn-attr-length	5.3.7.1, annex B	m	
6	duc-descr-list	5.3.7.1, annex B	m	
7	cl-common-attr	5.3.7.1, annex B	m	

Comments:

.....

.....

Table A.170: RLC_DM_CONNECT parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.1, annex B	m	
2	peer-mac-id	5.3.7.1, annex B	m	
3	cl-id	5.3.7.1, annex B	m	
4	cl-conn-attr-length	5.3.7.1, annex B	m	
5	duc-descr-list	5.3.7.1, annex B	m	

Comments:

.....

.....

Table A.171: RLC_DM_CONNECT_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.1, annex B	m	
2	peer-mac-id	5.3.7.1, annex B	m	
3	cl-id	5.3.7.1, annex B	m	
4	cl-conn-attr-length	5.3.7.1, annex B	m	
5	dlcc-descr-list	5.3.7.1, annex B	m	

Comments:

.....

.....

Table A.172: RLC_DM_CONNECT_COMPLETE parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.1, annex B	m	
2	peer-mac-id	5.3.7.1, annex B	m	
3	dlcc-id-list	5.3.7.1, annex B	m	

Comments:

.....

.....

Table A.173: RLC_DM_COMPLETE_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.1, annex B	m	
2	peer-mac-id	5.3.7.1, annex B	m	
3	mac-id	5.3.7.1, annex B	m	

Comments:

.....

.....

Table A.174: RLC_RELAY_SETUP parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19/12 MT supports relay functions

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.3, annex B	m	
2	peer-mac-id	5.3.7.3, annex B	m	
3	cl-id	5.3.7.3, annex B	m	
4	duc-ext-ind	5.3.7.3, annex B	m	
5	cl-conn-attr-length	5.3.7.3, annex B	m	
6	duc-descr-list	5.3.7.3, annex B	m	
7	cl-common-attr	5.3.7.3, annex B	m	

Comments:

.....

.....

Table A.175: RLC_RELAY_SETUP_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19 /12 MT supports relay functions

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.7.3, annex B	m	
2	peer-mac-id	5.3.7.3, annex B	m	
3	cl-conn-attr-length	5.3.7.3, annex B	m	
4	dlcc-descr-list	5.3.7.3, annex B	m	

Comments:

.....

.....

A.8.3.5 Direct Mode DUC release

Table A.176: RLC_DM_RELEASE parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.8.1, annex B	m	
2	peer-mac-id	5.3.8.1, annex B	m	
3	release-cause	5.3.8.1, annex B	m	
4	dlcc-id-list	5.3.8.1, annex B	m	

Comments:

.....

.....

Table A.177: RLC_DM_RELEASE_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.8.1, annex B	m	
2	peer-mac-id	5.3.8.1, annex B	m	
3	dlcc-id-list	5.3.8.1, annex B	m	

Comments:

.....

.....

A.8.3.6 DUC relay release

Table A.178: RLC_RELAY_RELEASE parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19 /12 MT supports relay functions
or
Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.8.3, annex B	m	
2	peer-mac-id	5.3.8.3, annex B	m	
3	release-cause	5.3.8.3, annex B	m	
4	dlcc-id-list	5.3.8.3, annex B	m	

Comments:

.....

.....

Table A.179: RLC_RELAY_RELEASE_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19 /2 MT supports relay functions
or
Prerequisite: A.47/1 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.8.3, annex B	m	
2	peer-mac-id	5.3.8.3, annex B	m	
3	dlcc-id-list	5.3.8.3, annex B	m	

Comments:

.....

.....

A.8.3.7 Direct Mode DUC modify

Table A.180: RLC_DM_MODIFY_REQ parameters

Prerequisite: A.5/1 MT supports Direct mode
or
Prerequisite: A.47/1 AP supports Direct mode.

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.1, annex B	m	
2	peer-mac-id	5.3.9.1, annex B	m	
3	cl-conn-attr-length	5.3.9.1, annex B	m	
4	duc-descr-list	5.3.9.1, annex B	m	

Comments:

.....

.....

Table A.181: RLC_DM_MODIFY parameters

Prerequisite: A.5/1 MT supports Direct mode

or

Prerequisite: A.47/1 AP supports Direct mode.

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.1, annex B	m	
2	peer-mac-id	5.3.9.1, annex B	m	
3	cl-conn-attr-length	5.3.9.1, annex B	m	
4	duc-descr-list	5.3.9.1, annex B	m	

Comments:

.....

.....

Table A.182: RLC_DM_MODIFY_ACK parameters

Prerequisite: A.5/1 MT supports Direct mode

or

Prerequisite: A.47/1 AP supports Direct mode.

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.1, annex B	m	
2	peer-mac-id	5.3.9.1, annex B	m	
3	cl-conn-attr-length	5.3.9.1, annex B	m	
4	dlcc-descr-list	5.3.9.1, annex B	m	

Comments:

.....

.....

Table A.183: RLC_DM_MODIFY_COMPLETE parameters

Prerequisite: A.5/1 MT supports Direct mode

or

Prerequisite: A.47/1 AP supports Direct mode.

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.1, annex B	m	
2	peer-mac-id	5.3.9.1, annex B	m	
3	dlcc-descr-list	5.3.9.1, annex B	m	

Comments:

.....

.....

Table A.184: RLC_DM_MODIFY_COMPLETE_ACK parameters

Prerequisite: A.5/1 MT supports Direct mode

or

Prerequisite: A.47/1 AP supports Direct mode.

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.1, annex B	m	
2	peer-mac-id	5.3.9.1, annex B	m	
3	mac-id	5.3.9.1, annex B	m	

Comments:

.....

.....

Table A.185: RLC_RELAY_MODIFY parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19/12 MT supports relay functions

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.3, annex B	m	
2	peer-mac-id	5.3.9.3, annex B	m	
3	cl-conn-attr-length	5.3.9.3, annex B	m	
4	dlcc-descr-list	5.3.9.3, annex B	m	

Comments:

.....

.....

Table A.186: RLC_RELAY_MODIFY_ACK parameters

Prerequisite: A.5/2 MT supports Direct mode AND A.19/12 MT supports relay functions

or

Prerequisite: A.47/2 AP supports Direct mode

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	5.3.9.3, annex B	m	
2	peer-mac-id	5.3.9.3, annex B	m	
3	cl-conn-attr-length	5.3.9.3, annex B	m	
4	dlcc-descr-list	5.3.9.3, annex B	m	

Comments:

.....

.....

A.8.4 Parameters of PDUs for non support

Table A.187: RLC_NO_SUPPORT parameters

Prerequisite:

Item	Parameter	Reference	Status	Support
1	rlc-pdu-type	7, annex B	m	
2	sch-lch	7, annex B	m	
3	no-support-pdu-typei	7, annex B	m	
4	extension-type	7, annex B	m	
5	mac-id	7, annex B	m	

Comments:

.....

A.9 Values of PDUs Parameters

History

Document history		
V1.1.1	September 2000	Publication
V1.1.1	January 2001	Publication as EN 301 823-2-1
V1.2.1	December 2001	Publication