

ETSI TS 101 871-2 V1.2.1 (2003-04)

Technical Specification

**Digital Enhanced Cordless Telecommunications (DECT);
Application Specific Access Profile (ASAP);
DECT Multimedia Access Profile (DMAP);
Profile requirement list and profile specific
Implementation Conformance Statement (ICS) proforma;
Part 2: Fixed radio Termination (FT)**



Reference

RTS/DECT-040186-2

Keywords

access, data, DECT, ICS, interoperability,
multimedia, network, profile, radio, testing, voice

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

| | |
|--|-----------|
| Intellectual Property Rights | 5 |
| Foreword..... | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions and abbreviations..... | 7 |
| 3.1 Definitions | 7 |
| 3.2 Abbreviations | 7 |
| 4 Conformance requirement | 7 |
| 5 Introduction for completing the ICS proforma..... | 7 |
| 5.1 General | 7 |
| 5.2 Purposes and structure..... | 8 |
| 5.3 Abbreviations and conventions | 8 |
| Annex A (normative): DMAP Profile ICS Proforma for FT | 10 |
| A.1 Instruction for completing the ICS proforma | 10 |
| A.2 Identification of the implementation | 10 |
| A.2.1 Date of the statement..... | 10 |
| A.2.2 Implementation Under Test (IUT) identification | 10 |
| A.2.3 System Under Test (SUT) identification | 11 |
| A.2.4 Product supplier..... | 11 |
| A.2.5 Client | 11 |
| A.2.6 ICS contact person..... | 12 |
| A.3 Identification of the protocol..... | 12 |
| A.3.1 Defect report numbers and amendments implemented..... | 12 |
| A.3.2 Addenda implemented..... | 12 |
| A.4 ICS proforma tables..... | 13 |
| A.4.1 Global statement of conformance..... | 13 |
| A.4.2 General Application | 13 |
| A.4.3 Voice services | 13 |
| A.4.3.1 General..... | 13 |
| A.4.3.2 Network layer | 13 |
| A.4.3.3 Data link control layer | 13 |
| A.4.3.4 Medium access control layer | 13 |
| A.4.3.5 Physical layer..... | 13 |
| A.4.3.6 Management Entity (ME) | 14 |
| A.4.3.7 Application features | 14 |
| A.4.4 Data services | 14 |
| A.4.4.1 General..... | 14 |
| A.4.4.2 General requirements..... | 14 |
| A.4.4.3 Network layer | 15 |
| A.4.4.4 Data link control layer | 15 |
| A.4.4.5 Medium access control layer | 15 |
| A.4.4.6 Physical layer..... | 15 |
| A.4.4.7 Management Entity (ME) | 15 |
| A.4.4.8 Application features | 16 |
| A.4.4.9 Interworking functions..... | 16 |
| A.4.5 Distributed communication services | 16 |
| A.4.5.1 General..... | 16 |
| A.4.5.2 Distributed communication..... | 16 |
| A.4.6 Profile specific ICS Proforma | 16 |
| A.4.6.1 Profile specific procedures for Management Entity..... | 16 |

Annex B (informative): Bibliography.....18
History19

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

Foreword

This Technical Specification (TS) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 2 of a multi-part deliverable covering the DECT Multimedia Access Profile (DMAP); Profile Implementation Conformance Statement (ICS), as identified below:

Part 1: "Portable radio Termination (PT)";

Part 2: "Fixed radio Termination (FT)".

Annex A contains the requirement lists for the FT DECT Multimedia Access Profile, Application Specific Access Profile.

1 Scope

The present document provides the Profile requirement list and profile specific Implementation Conformance Statement proforma for the Digital Enhanced Cordless Telecommunications Multimedia Access Profile (DMAP), Application Specific Access Profile (ASAP) at the Fixed radio Termination as defined in EN 301 650 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI EN 301 650: "Digital Enhanced Cordless Telecommunications (DECT); DECT Multimedia Access Profile (DMAP); Application Specific Access Profile (ASAP)".
- [2] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [3] ETSI EN 300 444: "Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [4] ISO/IEC 9646-1: "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [5] ISO/IEC 9646-7: "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 7: Implementation Conformance Statements".
- [6] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".
- [7] ETSI TS 101 869-2: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Services (DPRS); Profile requirement list and profile specific Implementation Conformance Statement (ICS) proforma; Part 2: Fixed radio Termination (FT)".
- [8] ETSI EN 300 474-2: "Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP); Profile requirement list and profile specific Implementation Conformance Statement (ICS) proforma; Part 2: Fixed radio Termination (FT)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 175-1 [2], ISO/IEC 9646-1 [4], ISO/IEC 9646-7 [5] and the following apply:

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

NOTE: The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

Protocol ICS (PICS): PICS for an implementation or system claimed to conform to a given protocol specification

3.2 Abbreviations

For the purposes of the present document, the abbreviations defined in EN 301 650 [1] and ISO/IEC 9646-1 [4] apply.

4 Conformance requirement

The supplier of a protocol implementation, which is claimed to conform to the fixed termination specific requirements of EN 301 650 [1], shall verify that his protocol implementation meets the requirements described in the present document. All the requirements described in TS 101 869-2 [7] and EN 300 474-2 [8] apply with the changes indicated in annexA.

The clause A.4.2 and its subclauses indicate the general application support. The supplier of the implementation shall complete this part.

The clause A.4.3 and its subclauses indicate the profile requirements list and the mandatory clauses for voice services. The supplier of the implementation, which is claimed to support these services, shall complete this part.

The clause A.4.4 and its subclauses indicate the profile requirements list and the mandatory clauses for data services. The supplier of the implementation, which is claimed to support these services, shall complete this part

The clause A.4.5 and its subclauses indicate the profile specific ICS proforma. The supplier of the implementation shall complete this part.

An ICS, which conforms to the present document, shall be a conforming ICS proforma completed in accordance with the guidance for completion given in clause 5.

5 Introduction for completing the ICS proforma

5.1 General

The supplier of a protocol implementation that is claimed to conform to the fixed termination specific requirements of EN 301 650 [1] shall verify that his particular layer protocol implementation meets the profile RL for each layer. For this, he shall complete a copy of the corresponding layer ICS proforma contained in TS 101 869-2 [7] for data services and in EN 300 474-2 [8] for voice services and updated with the requirements from annex A.

The profile Requirement List (profile RL) as defined in annex A is based on TS 101 869-2 [7] for data services and on EN 300 474-2 [8] for voice services. The profile RL is produced by copying selected tables from TS 101 869-2 [7] or EN 300 474-2 [8], removing the column(s) to be completed by the supplier, and adding a new set of columns giving the new profile requirements, both in terms of the status and/or allowed values. The tables defined in the present document, reference the tables either in TS 101 869-2 [7] or in EN 300 474-2 [8], as relevant.

5.2 Purposes and structure

The purpose of this ICS proforma is to provide a mechanism whereby a supplier of an implementation of the Fixed radio termination of the EN 301 650 [1] may provide information about the implementation in a standardized manner.

The ICS proforma is subdivided into clauses for the following categories of information:

- Instruction for completing the ICS proforma;
- Identification of the implementation;
- Identification of the protocol;
- ICS proforma tables:
 - Global statement of conformance;
 - Other specific clauses.

5.3 Abbreviations and conventions

The ICS proforma contained in the annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [5].

Item column

The item column contains a number, which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Profile reference column

The reference column gives reference to EN 301 650 [1], except where explicitly stated otherwise.

Status column

The following notations, defined in ISO/IEC 9646-7 [5], are used for the status column:

| | |
|------------|---|
| M or m | mandatory - the capability is required to be supported. |
| O or o | optional - the capability may be supported or not (e.g. the capability is not allowed because the underlying DECT layers (service provider) cannot handle it or the requirement belongs to an application i.e. does not belong to the network layer). |
| X or x | prohibited (excluded) - there is a requirement not to use this capability in the given context. |
| O.i or o.i | qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table. |
| Ci or ci | conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table or which is defined in a general condition table. |

I or i out-of-scope - this capability is outside the scope of the given specification, and hence irrelevant and not subject to conformance testing. This status is in particular applicable for data fields, which are reserved for future use. The structure of such fields has to be supported, but the value is undefined and thus to be ignored.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [5], are used for the support column:

Y or y supported by the implementation

N or n not supported by the implementation

N/A, n/a or - no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status)

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line before a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

Annex A (normative): DMAP Profile ICS Proforma for FT

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the ICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed ICS.

A.1 Instruction for completing the ICS proforma

The supplier of the implementation shall complete the ICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause 5.

A.2 Identification of the implementation

A.2.1 Date of the statement

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

Table A.1: Date of statement

| Date of statement | | |
|-------------------|-------|------|
| Day | Month | Year |
| | | |

A.2.2 Implementation Under Test (IUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the IUT in table A.2.

Table A.2: IUT identification

| IUT identification | |
|--------------------|--|
| IUT name | |
| IUT version | |

A.2.3 System Under Test (SUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the SUT in table A.3.

Table A.3: SUT identification

| SUT identification | |
|------------------------|--|
| SUT name | |
| Hardware configuration | |
| Operating system | |

A.2.4 Product supplier

Table A.4: Product supplier

| Product supplier | |
|------------------------|--|
| Name | |
| Address | |
| Phone No. | |
| Fax No. | |
| E-mail address | |
| Additional information | |

A.2.5 Client

The product supplier information and client information should both be filled in if they are different.

Table A.5: Client

| Client | |
|------------------------|--|
| Name | |
| Address | |
| Phone No. | |
| Fax No. | |
| E-mail address | |
| Additional information | |

A.2.6 ICS contact person

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

Table A.6: Contact person

| Contact person | |
|------------------------|--|
| Name | |
| Address | |
| Phone No. | |
| Fax No. | |
| E-mail address | |
| Additional information | |

A.3 Identification of the protocol

The supplier of the implementation shall enter the title, reference number and date of the publication of the DMAP-Specification to which conformance is claimed, in table A.7.

Table A.7: Identification of protocol

| Identification of protocol | |
|----------------------------|--|
| Title of specification | Digital Enhanced Cordless Telecommunications (DECT); DECT Multimedia Access Profile (DMAP); Application Specific Access Profile (ASAP) |
| Reference no. | EN 301 650 |
| Date of Publication | |

A.3.1 Defect report numbers and amendments implemented

The supplier of the implementation shall enter the reference number of implementation defect reports or corresponding amendment documents which modify the specification to EN 301 650 in table A.8.

Table A.8: Defect report and amendments number

| Modification of specification | |
|-------------------------------|---------------|
| Defect report no. | Amendment no. |
| | |

A.3.2 Addenda implemented

The supplier of the implementation shall enter the titles and the reference number of implemented addenda to EN 301 650 in table A.9.

Table A.9: Addenda implemented

| Addenda implemented | |
|---------------------|---------------|
| Title | Reference no. |
| | |
| | |

A.4 ICS proforma tables

A.4.1 Global statement of conformance

Table A.10: Global statement of conformance

| Global statement of conformance | |
|---|--|
| Are all mandatory capabilities implemented? | |

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the ICS, with an explanation of why the implementation is non-conforming, on pages attached to the ICS proforma.

A.4.2 General Application

Table A.11: General Application supported

| Item | Feature name | Protocol | Profile reference | Status | Support |
|--|------------------------------------|------------|-------------------|---------|---------|
| 1 | Voice services | EN 300 444 | 6.2.1 | M | |
| 2 | Data services: Wireless V.24 | EN 301 649 | 6.2.1 | O.a1101 | |
| 3 | Data services: Wireless LAN | EN 301 649 | 6.2.1 | O.a1101 | |
| 4 | Distributed Communication services | EN 301 649 | 6.2.1 | O | |
| O.a1101: At least one of these options shall be supported. | | | | | |

A.4.3 Voice services

The supplier of the implementation, which is claimed to support the voice services by answering "Yes" into the support column of the item 1 of the table A.11 shall complete this clause.

A.4.3.1 General

To conform to the fixed termination requirements of EN 301 650 for voice services, the supplier shall complete a copy of the corresponding part of the ICS proforma contained in EN 300 474-2 and TS 101 869-2 updated with the requirements indicated in the part voice services (see clause A.4.3 and subclauses).

A.4.3.2 Network layer

In order to meet the requirements of EN 301 650, clause 6.2.2, the tables contained in EN 300 474-2, clauses A.2 and B.5.1.1 apply without modifications of the status column.

A.4.3.3 Data link control layer

In order to meet the requirements of EN 301 650, clause 6.2.3 the tables contained in EN 300 474-2, clauses A.3 and B.5.2 apply without modifications of the status column.

A.4.3.4 Medium access control layer

In order to meet the requirements of EN 301 650, clause 6.2.4, the tables contained in EN 300 474-2, clauses A.4 and B.5.3 apply without modifications of the status column.

A.4.3.5 Physical layer

The tables contained in EN 300 474-2, clauses A.5 and B.5.4 apply without modifications of the status column.

A.4.3.6 Management Entity (ME)

In order to meet the requirements of EN 301 650, clause 6.2.5, the tables contained in EN 300 474-2, clause B.5.1.4 apply without modifications of the status column.

A.4.3.7 Application features

In order to meet the requirements of EN 301 650, clause 6.2.6, the tables contained in EN 300 474-2, clauses B.5.1.2 and B.5.1.3 apply without modifications of the status column.

A.4.4 Data services

The supplier of the implementation, which is claimed to support the data services by answering "Yes" into the support column of either the item 2 or the item 3 of the table A.11 shall complete this clause.

A.4.4.1 General

To conform to the fixed termination requirements of EN 301 650 for data services, the supplier shall complete a copy of the corresponding part of the ICS proforma contained in TS 101 869-2 updated with the requirements indicated in the part data service (see clause A.4.4 and subclauses) of this annex.

A.4.4.2 General requirements

In order to meet the general requirements of EN 301 650 for data services, the tables contained in TS 101 869-2, annex A apply with the following modifications.

Table A.12: TS 101 869-2, table A.2: DPRS protocol service class supported

| Item | Feature name | Profile reference | Status |
|----------------------------------|--------------------|-------------------|--------|
| 1 | Class 1 | A.1 | I |
| 2 | Class 2 | A.1 | M |
| 3 | Frame Relay (FREL) | 6.2.1 | Ca001 |
| 4 | Character stream | 6.2.1 | Ca001 |
| Ca1201: IF A.11/2 THEN m ELSE i. | | | |
| Ca1202: IF A.11/3 THEN m ELSE i. | | | |

Table A.13: TS 101 869-2, table A.3: DPRS protocol functional entities supported

| Item | Feature name | Profile reference | Status |
|----------------------------------|----------------------------|-------------------|--------|
| 1 | NWK layer | 6.2.2 | M |
| 2 | DLC layer | 6.2.3 | M |
| 7 | Distributed Communications | 6.2.1 | Ca1301 |
| 8 | Ethernet IWF | B.1 | Ca1302 |
| 9 | Token Ring IWF | B.1 | I |
| 10 | IP IWF | B.1 | I |
| 11 | PPP IWF | B.1 | I |
| 12 | V.24 IWF | C.1 | Ca1303 |
| Ca1301: = A.11/4. | | | |
| Ca1302: IF A.12/3 THEN m ELSE i. | | | |
| Ca1303: IF A.12/4 THEN m ELSE i. | | | |

A.4.4.3 Network layer

In order to meet the requirements of EN 301 650, clause 6.2.2, the tables contained in TS 101 869-2, annex B apply with the following modifications.

Table A.14: TS 101 869-2, table B.2: NWK features supported

| Item | Feature name | Profile reference | Status WV.24 | Status WLAN |
|--|--------------------------------------|-------------------|--------------|-------------|
| 1 | Outgoing call | 6.2.2 | O.a1401 | O.a1402 |
| 2 | Off hook | 6.2.2 | M | M |
| 3 | On hook (full release) | 6.2.2 | O | O |
| 8 | Incoming call | 6.2.2 | O.a1401 | O.a1402 |
| 11 | Location registration | 6.2.2 | Ca1401 | Ca1402 |
| 12 | On air key allocation | 6.2.2 | M | M |
| 15 | Alerting | 6.2.2 | O | O |
| 20 | Terminate access rights FT initiated | 6.2.2 | M | M |
| 26 | Authentication of FT | 6.2.2 | M | M |
| O.a1401: At least one of these options shall be supported. | | | | |
| O.a1402: At least one of these options shall be supported. | | | | |
| Ca1401: IF fast setup supported THEN m ELSE o. | | | | |
| Ca1402: IF fast setup supported THEN m ELSE o. | | | | |

Table A.15: TS 101 869-2, table B.3: NWK procedures supported

| Item | Feature name | Profile reference | Status WV.24 | Status WLAN |
|--|--------------------------|-------------------|--------------|-------------|
| 1 | Outgoing call request | 6.2.2 | Ca1501 | Ca1502 |
| 7 | Incoming call connection | 6.2.2 | Ca1503 | Ca1504 |
| Ca1501: IF C.14/1 WV.24 THEN m ELSE i. | | | | |
| Ca1502: IF C.14/1 WLAN THEN m ELSE i. | | | | |
| Ca1503: IF C.14/8 WV.24 THEN m ELSE i. | | | | |
| Ca1504: IF C.14/8 WLAN THEN m ELSE i. | | | | |

A.4.4.4 Data link control layer

In order to meet the requirements of EN 301 650, clause 6.2.3, the tables contained in TS 101 869-2, annex C apply without modifications of the status column.

A.4.4.5 Medium access control layer

In order to meet the requirements of EN 301 650, clause 6.2.4, the tables contained in TS 101 869-2, annex D apply without modifications of the status column.

A.4.4.6 Physical layer

The tables contained in TS 101 869-2, annex E apply without modifications of the status column.

A.4.4.7 Management Entity (ME)

In order to meet the requirements of EN 301 650, clause 6.2.5, the tables contained in TS 101 869-2, annex F apply with the following modification.

Table A.16: TS 101 869-2, table F.2: Management Entity features supported

| Item | Feature name | Profile reference | Status WV.24 | Status WLAN |
|------|--------------------|-------------------|--------------|-------------|
| 1 | Class 1 management | 6.2.5 | I | I |

A.4.4.8 Application features

In order to meet the requirements of EN 301 650, clause 6.2.6, the tables contained in TS 101 869-2, annex G apply without modifications of the status column.

A.4.4.9 Interworking functions

In order to meet the requirements of EN 301 650, the tables contained in TS 101 869-2 annex I apply without modifications of the status column.

A.4.5 Distributed communication services

The supplier of the implementation, which is claimed to support the Distributed Communication services by answering "Yes" into the support column of the item 4 of table A.11 shall complete this clause.

A.4.5.1 General

To conform to the fixed termination requirements of EN 301 650 for voice services, the supplier shall complete a copy of the corresponding part of the ICS proforma contained in TS 101 869-2 updated with the requirements indicated in the part Distributed Communication services (see clause A.4.5 and subclauses).

A.4.5.2 Distributed communication

In order to meet the requirements of EN 301 650, clause 6.2.7, the tables contained in TS 101 869-2, annex H apply with the following modification.

Table A.17: TS 101 869-2, table H.2: Distributed communication features

| Prerequisite: A.11/4. | | | |
|-----------------------|-----------------------------|-------------------|--------|
| Item | Feature name | Profile reference | Status |
| 1 | Distributed Communications. | 6.2.7 | M |

A.4.6 Profile specific ICS Proforma

A.4.6.1 Profile specific procedures for Management Entity

Table A.18: Choice of Basic or Advanced connection

| Prerequisite: Connection without U-plane needed | | | |
|---|---|-------------------|--------|
| Item | Feature name | Profile reference | Status |
| 1 | FT initiating; FT supports voice only; PT supports voice only or both data and voice; Basic connection chosen. | 6.3.2 | M |
| 2 | FT initiating; FT supports both data and voice; PT supports voice only; Basic connection chosen. | 6.3.2 | M |
| 3 | FT initiating; FT supports both data and voice; PT supports data only; Advanced connection chosen. | 6.3.2 | M |
| 4 | FT initiating; FT supports data only; PT supports data only or both data and voice; Advanced connection chosen. | 6.3.2 | M |
| 5 | FT terminating; FT supports both data and voice; Basic or Advanced connection is chosen by PT; FT shall accept the request. | 6.3.2 | M |

Table A.19: Choice for establishing a new call with u-plane

| Prerequisite: A connection is established for a call without U-plane and one of the sides would like to initiate a call using U-plane | | | |
|---|---|-------------------|---------|
| Item | Feature name | Profile reference | Status |
| 1 | Service change procedure. | 6.3.2 | O.a1901 |
| 2 | Release of the old connection and setup the new connection. | 6.3.2 | O.a1901 |
| O.a1901: At least one of these options shall be supported. The option 2 is recommended. | | | |

Table A.20: Choice of paging for Voice or Data Incoming call

| Prerequisite: For terminals that support both services, and Incoming calls. Incoming call with U-plane needed. | | | |
|--|--|-------------------|--------|
| Item | Feature name | Profile reference | Status |
| 1 | Voice call; Collective ringing procedure using short paging message. | 6.3.2 | M |
| 2 | Data call; long paging format message. | 6.3.2 | M |

Annex B (informative): Bibliography

ETSI ETS 300 406 (1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".

ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) Layer".

ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) Layer".

ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) Layer".

ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and Addressing".

ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security Features".

ETSI EN 300 824: "Digital Enhanced Cordless Telecommunications (DECT); Cordless Terminal Mobility (CTM); CTM Access Profile (CAP)".

History

| Document history | | |
|-------------------------|---------------|-------------|
| V1.1.1 | November 2000 | Publication |
| V1.2.1 | April 2003 | Publication |
| | | |
| | | |
| | | |