



**Lawful Interception (LI);  
Handover Interface and  
Service-Specific Details (SSD) for IP delivery;  
Part 7: Service-specific details for Mobile Services**

---

**Reference**

RTS/LI-00212-7

---

**Keywords**

handover, IP, lawful interception, mobile, security

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction .....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.3 Abbreviations .....	7
4 General .....	8
4.1 Approach .....	8
4.2 Reference model.....	8
5 3GPP handover Headers, data exchange and networks.....	9
5.1 Approach .....	9
5.2 Structures.....	9
6 3GPP handover Intercept Related Information (IRI) and Content of Communication (CC).....	9
6.1 Definition of IRI events and CC.....	9
6.2 IRI format.....	9
6.3 CC format.....	9
7 Void.....	10
8 Void.....	10
9 EPS Headers, data exchange and networks.....	10
9.1 Approach .....	10
9.2 Structures.....	10
10 EPS Intercept Related Information (IRI) and Content of Communication (CC) .....	10
10.1 Definition of IRI events and CC.....	10
10.2 IRI format.....	10
10.3 CC format.....	11
11 IMS Conference Intercept Related Information (IRI) and Content of Communication (CC).....	11
11.1 Definition of IRI events and CC.....	11
11.2 IRI format.....	11
11.3 CC format.....	11
12 IMS-based VoIP Intercept Related Information (IRI) and Content of Communication (CC) .....	11
12.1 Definition of IRI events and CC.....	11
12.2 IRI format.....	11
12.3 CC format.....	12
13 Proximity Services Intercept Related Information (IRI) .....	12
13.1 Definition of IRI.....	12
13.2 IRI format.....	12
14 Group Communications System Enablers Intercept Related Information (IRI) and Content of Communication (CC) .....	12
14.1 Definition of IRI events and CC.....	12
14.2 IRI format.....	12
14.3 CC format.....	12

15	IRI and CC for services defined in 3GPP TS 33.128 .....	13
15.1	Definition of IRI events and CC.....	13
15.2	IRI and CC format.....	13
15.3	Network Function Identifier .....	13
15.4	Extended Interception Point Identifier .....	13
<b>Annex A (normative): ASN.1 for IRI and CC .....</b>		<b>14</b>
A.1	Note on integrating ASN.1 structures .....	14
A.1.1	Header field mappings.....	14
A.1.2	CIN allocation .....	16
<b>Annex B (informative): Change request history.....</b>		<b>17</b>
History .....		18

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

The present document is part 7 of a multi-part deliverable. Full details of the entire series can be found in part 1 [2].

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# Introduction

The ETSI TS 102 232 [i.1] series of standards aims to provide a common delivery interface for lawfully-intercepted material from a wide range of services. The aim of the present document is to increase the range of services to which the ETSI TS 102 232 [i.1] interface applies, by including services from 3GPP TS 33.108 [3] and 3GPP TS 33.128 [6] within the ETSI TS 102 232 [i.1] delivery framework.

---

# 1 Scope

## Introduction

The present document specifies an approach for the handover of the lawfully-intercepted information that is defined in the two standards: 3GPP TS 33.108 [3] and 3GPP TS 33.128 [6]. The present document uses the handover techniques defined in ETSI TS 102 232-1 [2]. In this way, the present document allows additional services to be delivered through a common interface.

## 3GPP TS 33.108

The scope of the present document includes the handover of lawfully-intercepted information from the following parts of 3GPP TS 33.108 [3]:

- Intercept Related Information (IRI) and the Content of Communication (CC) from the mobile circuit-switched domain (3GPP TS 33.108 [3], clause 5).
- IRI and CC from the mobile packet-switched domain (3GPP TS 33.108 [3], clause 6).
- IRI and CC from the multi-media domain (3GPP TS 33.108 [3], clause 7).
- IRI and CC from the EPS domain (3GPP TS 33.108 [3], clause 10).
- IRI and CC from the IMS Conference domain (3GPP TS 33.108 [3], clause 11).
- IRI and CC from the IMS-based VoIP domain (3GPP TS 33.108 [3], clause 12).
- IRI from the Proximity Services domain (3GPP TS 33.108 [3], clause 13).
- IRI and CC from the Group Communication System Enablers domain (3GPP TS 33.108 [3], clause 14).

The present document does not override or supersede any specifications or requirements in 3GPP TS 33.108 [3].

## 3GPP TS 33.128

The scope of the present document includes the handover of lawfully-intercepted information in accordance with 3GPP TS 33.128 [6].

---

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery".

- [3] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); LTE; Digital cellular telecommunications system (Phase 2+) (GSM); 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".
- [4] Void.
- [5] Void.
- [6] ETSI TS 133 128: "LTE; 5G; Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Security; Protocol and procedures for Lawful Interception (LI); Stage 3 (3GPP TS 33.128)".
- [7] ETSI TS 103 221-2: "Lawful Interception (LI); Internal Network Interfaces; Part 2: X2/X3".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TS 102 232 (all parts): "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery".
- [i.2] ETSI TS 101 671: "Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI TS 102 232-1 [2] and ETSI TS 101 671 [i.2] apply.

### 3.2 Symbols

Void.

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASN.1	Abstract Syntax Notation One
CC	Content of Communication
CC-PDU	Content of Communication Protocol Data Unit
CIN	Communications Identity Number
CONFLIC	Conference LI Correlation
CR	Change Request
CS	Circuit Switched
EPS	Evolved Packet System
GCSE	Group Communications System Enablers
GCSELIC	Group Communications System Enablers LI Correlation
IMS	IP Multimedia Subsystem
IP	Internet Protocol

IPID	Interception Point IDentifier
IRI	Intercept Related Information
LI	Lawful Interception
LI_X2	Lawful Interception Internal Interface 2
LI_X3	Lawful Interception Internal Interface 3
LTE	Long Term Evolution (of UMTS)
MF	Mediation Function (at CSP)
NFID	Network Function Identifier
PDU	Protocol Data Unit
ProSe	Proximity Services
PS	Packet Switched
TC	Technical Committee
TS	Technical Specification
uLIC	UMTS LI Correlation
UMTS	Universal Mobile Telecommunications System
VOIPLIC	Voice Over IP LI Correlation

---


## 4 General

### 4.1 Approach

The present document forms part 7 of the ETSI TS 102 232 [i.1] family of standards, in that it is a service-specific component of the ETSI TS 102 232-1 [2] framework.

3GPP TS 33.108 [3] and 3GPP TS 33.128 [6] define the interception behaviour that leads to IRI events on the handover interface, for both the packet data domain and circuit switched domain.

### 4.2 Reference model



**Figure 1: Reference model**



---

## 5 3GPP handover Headers, data exchange and networks

### 5.1 Approach

ETSI TS 102 232-1 [2] describes a technique for data exchange, and specifies the headers that shall be associated with the results of interception. The present document follows ETSI TS 102 232-1 [2] regarding headers, data exchange and networks demonstrates how the header fields in ETSI TS 102 232-1 [2] can be populated in a direct and straightforward manner using the interception information available in 3GPP TS 33.108 [3] and 3GPP TS 33.128 [6].

### 5.2 Structures

IRI events from 3GPP TS 33.108 [3], for both circuit and packet switched services, are sent using the uMTSIRI element of IRIContents.

CC from CS domain delivery in IP are sent using the CSvoice-CC-PDU element of CCContent, which is the CSvoice-CC-PDU from 3GPP TS 33.108 [3], containing cSvoiceLIC-header and payload.

CC from packet switched services are sent using the uMTSCC element CCContent, which is an OCTET STRING.

Alternatively, subject to national agreement, CC from packet switched services are sent using the uMTSCC-CC-PDU element of CCContent, which is the CC-PDU from 3GPP TS 33.108 [3], containing the uLIC-header and payload.

CC and IRI PDUs formatted according to 3GPP TS 33.128 [6] are sent using the threeGPP33128DefinedCC and threeGPP33128DefinedIRI elements of CCContent and IRIContents respectively.

---

## 6 3GPP handover Intercept Related Information (IRI) and Content of Communication (CC)

### 6.1 Definition of IRI events and CC

IRI events are defined as per 3GPP TS 33.108 [3].

### 6.2 IRI format

IRI events are defined as per 3GPP TS 33.108 [3] for both circuit and packet switched services. They are sent using the uMTSIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

### 6.3 CC format

CC from packet switched services are sent using the uMTSCC element CCContent, which is an OCTET STRING. The OCTET STRING will be as defined in the payload element of the CC-PDU structure in 3GPP TS 33.108 [3], clause B.4.

Alternatively, subject to national agreement, CC from packet switched services are sent using the uMTSCC-CC-PDU element of CCContent, which is the CC-PDU from 3GPP TS 33.108 [3], containing the uLIC-header and payload.

CC from CS domain delivery in IP are sent using the CSvoice-CC-PDU element of CCContent, which is the CSvoice-CC-PDU from 3GPP TS 33.108 [3], containing cSvoiceLIC-header and payload.

The information in the cVoiceLIC-header element of CSvoice-CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

The information in the uLIC-header element of CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

---

7 Void

8 Void

## 9 EPS Headers, data exchange and networks

### 9.1 Approach

ETSI TS 102 232-1 [2] describes a technique for data exchange, and specifies the headers that shall be associated with the results of interception. The present document follows ETSI TS 102 232-1 [2] regarding headers, data exchange and networks demonstrates how the header fields in ETSI TS 102 232-1 [2] can be populated in a direct and straightforward manner using the interception information available in 3GPP TS 33.108 [3].

### 9.2 Structures

IRI events from 3GPP TS 33.108 [3], for EPS services, are sent using the ePSIRI element of IRIContents.

CC from EPS services is sent using the ePSCC element of CCContent, which is an OCTET STRING.

Alternatively, subject to national agreement, CC from EPS services are sent using the ePSCC-CC-PDU element of CCContent, which is the CC-PDU from 3GPP TS 33.108 [3], containing the uLIC-header and payload.

---

## 10 EPS Intercept Related Information (IRI) and Content of Communication (CC)

### 10.1 Definition of IRI events and CC

IRI events are defined as per 3GPP TS 33.108 [3].

### 10.2 IRI format

IRI events for EPS services are defined as per clause 10 of 3GPP TS 33.108 [3]. They are sent using the ePSIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

## 10.3 CC format

CC from EPS is sent using the ePSCC element of CCContents, which is an OCTET STRING. The OCTET STRING will be as defined in the payload element of the CC-PDU structure in 3GPP TS 33.108 [3], clause B.10.

Alternatively, subject to national agreement, CC from EPS services are sent using the ePSCC-CC-PDU element of CCContents, which is the CC-PDU from 3GPP TS 33.108 [3], containing the uLIC-header and payload.

The information in the uLIC-header element of CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

---

# 11 IMS Conference Intercept Related Information (IRI) and Content of Communication (CC)

## 11.1 Definition of IRI events and CC

IRI events are defined as per 3GPP TS 33.108 [3].

## 11.2 IRI format

IRI events for IMS Conference services are defined as per clause 11 of 3GPP TS 33.108 [3]. They are sent using the confIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

## 11.3 CC format

CC from IMS Conference services are sent using the Conf-CC-PDU element of CCContents, which is the Conf-CC-PDU from 3GPP TS 33.108 [3], containing the confLIC-header and payload.

The information in the confLIC-header element of Conf-CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

NOTE: Octet string is not provided as it will break evidential use.

---

# 12 IMS-based VoIP Intercept Related Information (IRI) and Content of Communication (CC)

## 12.1 Definition of IRI events and CC

IRI events are defined as per 3GPP TS 33.108 [3].

## 12.2 IRI format

IRI events for IMS-based VoIP services are defined as per clause 12 of 3GPP TS 33.108 [3]. They are sent using the ePSIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

## 12.3 CC format

CC from IMS-based VoIP services are sent using the Voip-CC-PDU element of CCContents, which is the Voip-CC-PDU from 3GPP TS 33.108 [3], containing the voipLIC-header and payload.

The information in the voipLIC-header element of Voip-CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

NOTE: Octet string is not provided as it will break evidential use.

---

# 13 Proximity Services Intercept Related Information (IRI)

## 13.1 Definition of IRI

IRI events are defined as per 3GPP TS 33.108 [3].

## 13.2 IRI format

IRI events for Proximity Services (PROSE) are defined as per clause 13 of 3GPP TS 33.108 [3]. They are sent using the proseIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

---

# 14 Group Communications System Enablers Intercept Related Information (IRI) and Content of Communication (CC)

## 14.1 Definition of IRI events and CC

IRI events are defined as per 3GPP TS 33.108 [3].

## 14.2 IRI format

IRI events for Group Communications System Enablers (GCSE) services are defined as per clause 14 of 3GPP TS 33.108 [3]. They are sent using the gcseIRI element of IRIContents.

Fields which are duplicated in the 3GPP TS 33.108 [3] and ETSI TS 102 232-1 [2] structures should be populated consistently in both structures. Clause A.1 gives guidance on mapping between 3GPP TS 33.108 [3] elements and ETSI TS 102 232-1 [2] elements for IRI.

## 14.3 CC format

CC from Group Communications System Enablers (GCSE) services are sent using the Gcse-CC-PDU element of CCContents, which is the Gcse-CC-PDU from 3GPP TS 33.108 [3], containing the gcseLIC-header and payload.

The information in the gcseLIC-header element of Gcse-CC-PDU will be used to populate the header information in the LI-PS-PDU structure of ETSI TS 102 232-1 [2]. Clause A.1 gives guidance on the mapping between these elements.

NOTE: Octet string is not provided as it will break evidential use.

---

## 15 IRI and CC for services defined in 3GPP TS 33.128

### 15.1 Definition of IRI events and CC

IRI and CC events are defined as per 3GPP TS 33.128 [6].

### 15.2 IRI and CC format

3GPP TS 33.128 [6] defines the format for the contents of the `threeGPP33128DefinedIRI` and `threeGPP33128DefinedCC` elements for each IRI and CC event.

### 15.3 Network Function Identifier

If NFID (as defined in ETSI TS 103 221-2 [7], clause 5.3.7) is available on the `LI_X2` and `LI_X3` interfaces (as defined in 3GPP TS 33.128 [6]), in order to indicate the Network Function associated with the Point of Interception the `NetworkFunctionIdentifier` parameter (as defined in ETSI TS 102 232-1 [2]) shall be populated by the MF with the NFID value received over the `LI_X2` and `LI_X3` interfaces.

### 15.4 Extended Interception Point Identifier

If IPID (as defined in ETSI TS 103 221-2 [7], clause 5.3.8) is available on the `LI_X2` and `LI_X3` interfaces (as defined in 3GPP TS 33.128 [6]), in order to indicate the specific Point of Interception the `ExtendedInterceptionPointID` parameter (as defined in ETSI TS 102 232-1 [2]) shall be populated by the MF with the IPID value received over the `LI_X2` and `LI_X3` interfaces.

## Annex A (normative): ASN.1 for IRI and CC

### A.1 Note on integrating ASN.1 structures

#### A.1.1 Header field mappings

Table A.1 shows how elements of the ETSI TS 102 232-1 [2] PSHeader structure should be populated from information in the 3GPP TS 33.108 [3] IRI-Parameters structure.

**Table A.1: 3GPP TS 33.108 [3] to ETSI TS 102 232-1 [2] PSHeader mapping**

ETSI TS 102 232-1 [2] PSHeader element	Source from 3GPP TS 33.108 [3]
lawfulInterceptionIdentifier	Copied directly from IRI-Parameters.lawfulInterceptionIdentifier
authorizationCountryCode	Supplied directly by the MF
communicationIdentifier	See below for individual elements
networkIdentifier	See below for individual elements
operatorIdentifier	Copied directly from IRI-Parameters.networkIdentifier.operatorIdentifier
eTSI671NEID	Copied directly from IRI-Parameters.networkIdentifier Network-Element-Identifier
communicationIdentityNumber	See clause A.1.2
deliveryCountryCode	Supplied directly by the MF
sequenceNumber	Supplied directly by the MF
timeStamp	Copied from IRI-Parameters.timeStamp. This requires a conversion from HI2Operations.TimeStamp to GeneralizedTime

Table A.2 shows how elements of the ETSI TS 102 232-1 [2] IRIPayload structure should be populated from information in the 3GPP TS 33.108 [3] structures.

**Table A.2: 3GPP TS 33.108 [3] to ETSI TS 102 232-1 [2] IRIPayload mapping**

ETSI TS 102 232-1 [2] IRIPayload element	Source from 3GPP TS 33.108 [3]
iRIType	Inferred from UmtsIRIContent or EpsIRIContent or ConfIRIContent or ProSelIRIContent or GcseIRIContent or UmtsCS-IRIsContent
timeStamp	Copied from IRI-Parameters.timeStamp (assuming no aggregation of PDUs) This requires a conversion from HI2Operations.TimeStamp to GeneralizedTime
iRIContents	See below for individual elements
uMTSIRI	See below for individual elements
iRI-Parameters	Copied directly from IRI-Parameters, if handing over packet domain IRI
iRI-CS-Parameters	Copied directly from IRI-Parameters, if handing over circuit switched IRI
ePSIRI	See below for individual elements
iRI-EPS-Parameters	Copied directly from IRI-Parameters, if handing over EPS IRI See note
confIRI	See below for individual elements
iRI-Conf-Parameters	Copied directly from IRI-Parameters, if handing over CONF IRI
proselIRI	See below for individual elements
iRI-ProSe-Parameters	Copied directly from IRI-Parameters, if handing over PROSE IRI
gcseIRI	See below for individual elements
iRI-Gcse-Parameters	Copied directly from IRI-Parameters, if handing over GCSE IRI
NOTE:	EPS IRI is also used for IMS-based VoIP services.

Table A.3 shows how elements of the ETSI TS 102 232-1 [2] PSHeader structure should be populated from information in the 3GPP TS 33.108 [3] CC-PDU structure.

**Table A.3: 3GPP TS 33.108 [3] to ETSI TS 102 232-1 [2] PSHeader mapping**

ETSI TS 102 232-1 [2] PSHeader element	Source from 3GPP TS 33.108 [3]
lawfulInterceptionIdentifier	Copied from CC-PDU.uLIC-header.IIID or Conf-CC-PDU.confLIC-header.IIID or Voip-CC-PDU.voipLIC-header.IIID or Gcse-CC-PDU.gcseLIC-header.IIID or CSvoice-CC-PDU.cSvoiceLIC-header.IIID
authorizationCountryCode	Supplied directly by the MF
communicationIdentifier	See below for individual elements
networkIdentifier	See below for individual elements
operatorIdentifier	Supplied directly by the MF (see 3GPP TS 33.108 [3], clause 5.2.4)
eTSI671NEID	Supplied directly by the MF (see 3GPP TS 33.108 [3], clause 5.2.4)
communicationIdentityNumber	See clause A.1.2
deliveryCountryCode	Supplied directly by the MF
sequenceNumber	Supplied directly by the MF
timeStamp	Copied from CC-PDU.uLIC-header.timeStamp or Conf-CC-PDU.confLIC-header.timeStamp or Voip-CC-PDU.voipLIC-header.timeStamp or Gcse-CC-PDU.gcseLIC-header.timeStamp or CSvoice-CC-PDU.cSvoiceLIC-header.timeStamp This requires a conversion from HI2Operations.TimeStamp to GeneralizedTime

Table A.4 shows how elements of the ETSI TS 102 232-1 [2] CCPayload structure should be populated from information in the 3GPP TS 33.108 [3] structures.

**Table A.4: 3GPP TS 33.108 [3] to ETSI TS 102 232-1 [2] CCPayload mapping**

ETSI TS 102 232-1 [2] CCPayload element	Source from 3GPP TS 33.108 [3]
payloadDirection	Copied from CC-PDU.uLIC-header.t-PDU-direction or Conf-CC-PDU.confLIC-header.t-PDU-direction or Voip-CC-PDU.voipLIC-header.t-PDU-direction or Gcse-CC-PDU.gcseLIC-header.t-PDU-direction or CSvoice-CC-PDU.cSvoiceLIC-header.t-PDU-direction This requires a trivial translation between TPDU-direction and PayloadDirection enumerated types
timeStamp	Copied from CC-PDU.uLIC-header.timeStamp or Conf-CC-PDU.confLIC-header.timeStamp or Voip-CC-PDU.voipLIC-header.timeStamp or Gcse-CC-PDU.gcseLIC-header.timeStamp or CSvoice-CC-PDU.cSvoiceLIC-header.timeStamp This requires a conversion from HI2Operations.TimeStamp to GeneralizedTime
ccContents	See below for individual elements
uMTSCC	Bytes copied from CC-PDU.payload
uMTSCC-CC-PDU	Copied directly from UMTS CC-PDU (that is UMTS CC-PDU.uLIC-header plus UMTS CC-PDU.payload)
ePSCC	Bytes copied from CC-PDU.payload
ePSCC-CC-PDU	Copied directly from EPS CC-PDU (that is EPS CC-PDU.uLIC-header plus EPS CC-PDU.payload)
confCC-CC-PDU	Copied directly from Conf-CC-PDU (that is Conf-CC-PDU.confLICheader plus Conf-CC-PDU.payload)
voipCC-CC-PDU	Copied directly from Voip-CC-PDU (that is Voip-CC-PDU.voipLIC-header plus Voip-CC-PDU.payload)
gcseCC-CC-PDU	Copied directly from Gcse-CC-PDU (that is Gcse-CC-PDU.gcseLIC-header plus Gcse-CC-PDU.payload)
cSvoice-CC-PDU	Copied directly from CSvoice-CC-PDU (that is CSvoice-CC-PDU.cSvoiceLIC-header plus CSvoice-CC-PDU.payload)

## A.1.2 CIN allocation

CIN allocation follows ETSI TS 102 232-1 [2], clause 5.2.4. The CIN extension field may be used, if required, using the CorrelationValues field as described in 3GPP TS 33.108 [3].



## Annex B (informative): Change request history

Status of the present document: ETSI TS 102 232-7 Service-specific details for Mobile Services		
TC LI approval Date	Version	Remarks
January 2008	2.1.1	First publication of the TS after approval by ETSI/TC LI#17 (22-24 January 2008, Como)
February 2011	2.2.1	Included Change Request: ETSI TS 102 232-7 CR001 (Cat B) Addition of Service-Specific Details for CDMA2000 This CR was approved by TC LI#26 (15-17 February 2011, Sophia Antipolis)  Version 2.2.1 prepared by the Rapporteur
May 2012	3.1.1	Included Change Request: ETSI TS 102 232-7 CR002 (Cat B) Introduce changes to accommodate EPS This CR was approved by TC LI#30 (14-16 May 2012, Amsterdam)  Version 3.3.1 prepared by the Rapporteur
June 2013	3.2.1	Included Change Request: ETSI TS 102 232-7 CR003 (Cat B) to preserve the uLIC header This CR was approved by TC LI #33 (11-13 June 2013, Joensuu)  Version 3.2.1 prepared by the Rapporteur
February 2016	3.3.1	Included Change Request: ETSI TS 102 232-7 004r3 (Cat B) to accommodate the delivery of the 3GPP IMS-based VoIP and IMS Conference Services and Proximity Services (ProSe) and Group Communications System Enablers specified in 3GPP TS 33.108, clauses 11, 12, 13 and 14 This CR was approved by TC LI #41 (10-12 February 2016, Sophia Antipolis)  Version 3.3.1 prepared by the Rapporteur
February 2017	3.4.1	Included Change Request: ETSI 102 232 CR005r1 (Cat F). Table A.4 modified in order to be aligned with clause 12.3 C.C. format  This CR was approved by TC LI#44 (30 January - 1 February, Sophia Antipolis)
February 2018	3.5.1	Included Change Request: ETSI 102 232 CR006r3 (Cat B). modification to take account of changes from SA3LI#67 to have an IP-based CC handover interface  This CR was approved by TC LI#47 (5-7 February 2018, New Delhi), version prepared by the Rapporteur
February 2019	3.6.1	Included Change Request: ETSI TS 102 232 CR007 (Cat B): Inclusion of 33.128 services in part 7  This CR was approved by TC LI#50 (5-7 February 2019, Dubai), version prepared by the Rapporteur
October 2019	3.7.1	Included Change Request: ETSI TS 102 232-7 CR008 (Cat B): Adapt the introduction and scope  This CR was approved by TCLI#52 (15-17 October 2019, Turin), version prepared by the Rapporteur
July 2020	3.8.1	Included Change Request: ETSI TS 102 232-7 CR009 (Cat F): Correcting reference  This CR was approved by TCLI#54-e (June 2020, online), version prepared by the Rapporteur
July 2021	3.9.1	Withdrawn
September 2021	3.10.1	Included Change Requests: ETSI TS 102 232-7 CR010r3 (Cat C): Network Function ID ETSI TS 102 232-7 CR011r2 (Cat C): Extended Interception Point Identifier  These CR were approved by TCLI#57-e (June 2021, online)

---

## History

<b>Document history</b>		
V2.1.1	March 2008	Publication (Historical)
V2.2.1	March 2011	Publication (Historical)
V3.1.1	June 2012	Publication
V3.2.1	July 2013	Publication
V3.3.1	March 2016	Publication
V3.4.1	March 2017	Publication
V3.5.1	April 2018	Publication
V3.6.1	April 2019	Publication
V3.7.1	December 2019	Publication
V3.8.1	August 2020	Publication
V3.9.1	July 2021	Publication (Withdrawn)
V3.10.1	September 2021	Publication