

ETSI TS 102 708-2-1 V1.1.1 (2010-03)

Technical Specification

**Intelligent Transport Systems (ITS);
RTTT;
Test specifications for High Data Rate (HDR) data
transmission equipment operating in the 5,8 GHz ISM band;
Part 2: Application Layer Common Application
Service Elements;
Sub-Part 1: Protocol Implementation Conformance
Statement (PICS) proforma specification**



ReferenceDTS/ITS-0020005

KeywordsDSRC, application, layer 7, ITS, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions and abbreviations.....	7
3.1 Definitions.....	7
3.2 Abbreviations	7
4 Overview of the templates.....	7
5 Conformance requirement concerning PICS.....	7
Annex A (normative): PICS proforma for HDR DSRC application layer for OBU.....	8
A.1 Guidance for completing the PICS proforma.....	8
A.1.1 Purposes and structure.....	8
A.1.2 Abbreviations and conventions	8
A.1.3 Instructions for completing the PICS proforma.....	10
A.2 Identification of the implementation	10
A.2.1 Date of the statement.....	10
A.2.2 Implementation Under Test (IUT) identification	10
A.2.3 System Under Test (SUT) identification	11
A.2.4 Product supplier.....	11
A.2.5 Client (if different from product supplier).....	11
A.2.6 PICS contact person	12
A.3 Identification of the protocol.....	12
A.4 Global statement of conformance.....	13
A.5 Encoding rules.....	13
A.6 Protocol data units	13
A.7 Procedures	14
Annex B (normative): PICS proforma for HDR DSRC application layer for RSU	15
B.1 Guidance for completing the PICS proforma.....	15
B.1.1 Purposes and structure.....	15
B.1.2 Abbreviations and conventions	15
B.1.3 Instructions for completing the PICS proforma.....	17
B.2 Identification of the implementation	17
B.2.1 Date of the statement.....	17
B.2.2 Implementation Under Test (IUT) identification	17
B.2.3 System Under Test (SUT) identification	18
B.2.4 Product supplier.....	18
B.2.5 Client (if different from product supplier).....	18
B.2.6 PICS contact person	19
B.3 Identification of the protocol.....	19
B.4 Global statement of conformance.....	20
B.5 Encoding rules.....	20

B.6	Protocol data units	20
B.7	Procedures	21
History	22

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport System (ITS).

The present document is part 2, sub-part 1 of a multi-part deliverable covering the test specifications for High Data Rate (HDR) Dedicated Short Range Communication (DSRC), as identified below:

Part 1: "Data Link Layer";

Part 2: "Application Layer Common Application Service Elements":

Sub-part 1: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Sub-part 2: "Test Suite Structure and Test Purposes (TSS&TP)";

Sub-part 3: "Abstract Test Suite (ATS) and partial PIXIT proforma".

1 Scope

The present document specifies Protocol Implementation Conformance Statement (PICS) proformas for the OSI application layer of HDR DSRC as defined in ES 200 467-1 [1], in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3] and in ETS 300 406 [4].

This proforma is intended for use by suppliers of equipment which is claimed to conform to the HDR DSRC application layer, as specified in ES 200 674-1 [1].

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS). The present document provides proforma ICS templates, to be filled in by equipment suppliers.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI ES 200 674-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Road Transport and Traffic Telematics (RTTT); Part 1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band".
- [2] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concept".
- [3] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [4] ETSI ETS 300 406: "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ES 200 674-1 [1], ISO/IEC 9646-1 [2], ISO/IEC 9646-7 [3] and the following apply:

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ES 200 674-1 [1], ISO/IEC 9646-1 [2], ISO/IEC 9646-7 [3] and the following apply:

DSRC	Dedicated Short Range Communication
HDR	High Data Rate
ICS	Implementation Conformance Statement
IUT	Implementation Under Test
OBU	On Board Unit, an alternative descriptor to Mobile Equipment
PICS	Protocol Implementation Conformance Statement
RSU	Road Side Unit, an alternative descriptor to Fixed Equipment
RTTT	Road Transport and Traffic Telematics
SUT	System Under Test

4 Overview of the templates

The present document contains common PICS templates for On Board Unit (OBU) and Road Side Unit (RSU), for the OSI data link layer of HDR DSRC.

5 Conformance requirement concerning PICS

The actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

An ICS which conforms to the present document shall be a conforming PICS proforma completed in accordance with the instructions for completion given at the start of each annex.

Annex A (normative): PICS proforma for HDR DSRC application layer for OBU

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the proforma in this annex so that it can be used for its intended purposes and may further publish the completed proforma.

A.1 Guidance for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ES 200 674-1 [1] may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- guidance for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- global statement of conformance;
- PICS proforma tables.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

m	mandatory - the capability is required to be supported.
o	optional - the capability may be supported or not.
n/a	not applicable - in the given context, it is impossible to use the capability.
x	prohibited (excluded) - there is a requirement not to use this capability in the given context.
o.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table.

Reference column

The reference column makes reference to ES 200 674-1 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column:

Y or y	supported by the implementation.
N or n	not supported by the implementation.
N/A, n/a or -	no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

NOTE: As stated in ISO/IEC 9646-7 [3], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values:	<min value> .. <max value>
example:	5 .. 20
- list of values:	<value1>, <value2>, ..., <valueN>
example:	2 ,4 ,6 ,8, 9
example:	'1101'B, '1011'B, '1111'B
example:	'0A'H, '34'H, '2F'H
- list of named values:	<name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)
example:	reject(1), accept(2)
- length:	size (<min size> .. <max size>)
example:	size (1 .. 8)

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause A.1.2.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.2.3 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

Operating system:

.....

A.2.4 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.2.5 Client (if different from product supplier)

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....

A.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS.)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.3 Identification of the protocol

This PICS proforma applies to the following standard:

ES 200 674-1 [1]: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Road Transport and Traffic Telematics (RTTT); Part 1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band".

A.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

A.5 Encoding rules

Table A.1: Encoding rules

Item	Supported types	Reference	Status	Support (Y/N)
1	BITSTRING	11.4.1.1	m	
2	INTEGER	11.4.1.2	m	
3	SEQUENCE	11.4.2.1	m	
4	SEQUENCE OF	11.4.2.2	m	
5	CHOICE	11.4.2.3	m	
6	SET	11.4.2.4	m	

A.6 Protocol data units

Table A.2: APDU format

Item	Supported format	Reference	Status	Support (Y/N)
1	A-Association.request parameters	11.5.1	m	
2	A-Association.response parameters	11.6.1	m	

Table A.3: Directives

Item	Directive	Sending			Receiving		
		Reference	Status	Support (Y/N)	Reference	Status	Support (Y/N)
1	Open-Rq		n/a		11.5.2, 11.6.2	m	
2	Open-Rs	11.6.3	o			n/a	
3	Close-Rq		n/a		11.5.3, 11.6.2	m	
4	Close-Rs	11.6.4	o			n/a	
5	Set-TBA-Id-Rq		n/a		11.5.4, 11.6.2	m	
6	Set-TBA-Id-Rs	11.6.5	o			n/a	
7	Read-Display-Type-Rq		n/a		11.5.5, 11.6.2	o	
8	Read-Display-Type-Rs	11.6.6	o			n/a	
9	Read-Master-Core-Rq		n/a		11.5.6, 11.6.2	m	
10	Read-Master-Core-Rs	11.6.7	m			n/a	
11	Read-Appl-Core-Rq		n/a		11.5.7, 11.6.2	m	
12	Read-Appl-Core-Rs	11.6.8	m			n/a	
13	Write-Appl-Core-Rq		n/a		11.5.8, 11.6.2	m	
14	Write-Appl-Core-Rs	11.6.9	o			n/a	
15	Write-App-Core-Conf-Rq		n/a		11.5.9, 11.6.2	m	
16	Write-App-Core-Conf-Rs	11.6.10	m			n/a	
17	Read-Appl-Record-Rq		n/a		11.5.10, 11.6.2	m	
18	Read-Appl-Record-Rs	11.6.11	m			n/a	
19	Write-Appl-Record-Curr-Rq		n/a		11.5.11, 11.6.2	m	
20	Write-Appl-Record-Curr-Rs	11.6.12	m			n/a	
21	Write-Appl-Record-Curr-Conf-Rq		n/a		11.5.12, 11.6.2	m	
22	Write-Appl-Record-Curr-Conf-Rs	11.6.13	m			n/a	
23	Write-Appl-Record-Next-Rq		n/a		11.5.13, 11.6.2	m	
24	Write-Appl-Record-Next-Rs	11.6.14	m			n/a	
25	Write-Appl-Record-Next-Conf-Rq		n/a		11.5.14, 11.6.2	m	
26	Write-Appl-Record-Next-Conf-Rs	11.6.15	m			n/a	
27	Action-Rq		n/a		11.5.15, 11.6.2	o	
28	Action-Rs	11.6.16	o			n/a	

A.7 Procedures

Table A.4: Procedures

Item	Supported procedure	Reference	Status	Support (Y/N)
1	Session handling for directives with read access	11.2.3	m	
2	Session handling for directives with write access	11.2.3	m	
3	Session handling for Close-Rq	11.2.3	m	
4	Session handling for Action-Rq	11.2.3	o	
5	Session handling for Read-Display-Type-Rq	11.2.3	o	

Annex B (normative): PICS proforma for HDR DSRC application layer for RSU

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the proforma in this annex so that it can be used for its intended purposes and may further publish the completed proforma.

B.1 Guidance for completing the PICS proforma

B.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ES 200 674-1 [1] may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- guidance for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- global statement of conformance;
- PICS proforma tables.

B.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

m	mandatory - the capability is required to be supported.
o	optional - the capability may be supported or not.
n/a	not applicable - in the given context, it is impossible to use the capability.
x	prohibited (excluded) - there is a requirement not to use this capability in the given context.
o.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table.

Reference column

The reference column makes reference to ES 200 674-1 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column:

Y or y	supported by the implementation.
N or n	not supported by the implementation.
N/A, n/a or -	no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

NOTE: As stated in ISO/IEC 9646-7 [3], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a directive while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values:	<min value> .. <max value>
example:	5 .. 20
- list of values:	<value1>, <value2>, ..., <valueN>
example:	2 ,4 ,6 ,8, 9
example:	'1101'B, '1011'B, '1111'B
example:	'0A'H, '34'H, '2F'H
- list of named values:	<name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)
example:	reject(1), accept(2)
- length:	size (<min size> .. <max size>)
example:	size (1 .. 8)

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

B.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause A.1.2.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

B.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

B.2.1 Date of the statement

.....

B.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

B.2.3 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

Operating system:

.....

B.2.4 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

B.2.5 Client (if different from product supplier)

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....

B.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS.)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

B.3 Identification of the protocol

This PICS proforma applies to the following standard:

ES 200 674-1 [1]: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Road Transport and Traffic Telematics (RTTT); Part 1: Technical characteristics and test methods for High Data Rate (HDR) data transmission equipment operating in the 5,8 GHz Industrial, Scientific and Medical (ISM) band".

B.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

B.5 Encoding rules

Table B.1: Encoding rules

Item	Supported types	Reference	Status	Support (Y/N)
1	BITSTRING	11.4.1.1	m	
2	INTEGER	11.4.1.2	m	
3	SEQUENCE	11.4.2.1	m	
4	SEQUENCE OF	11.4.2.2	m	
5	CHOICE	11.4.2.3	m	
6	SET	11.4.2.4	m	

B.6 Protocol data units

Table B.2: APDU format

Item	Supported format	Reference	Status	Support (Y/N)
1	A-Association.request parameters	11.5.1	m	
2	A-Association.response parameters	11.6.1	m	

Table B.3: Directives

Item	Directive	Receiving			Sending		
		Reference	Status	Support (Y/N)	Reference	Status	Support (Y/N)
1	Open-Rq		n/a		11.5.2	m	
2	Open-Rs	11.6.3	m			n/a	
3	Close-Rq		n/a		11.5.3	m	
4	Close-Rs	11.6.4	m			n/a	
5	Set-TBA-Id-Rq		n/a		11.5.4	m	
6	Set-TBA-Id-Rs	11.6.5	m			n/a	
7	Read-Display-Type-Rq		n/a		11.5.5	o	
8	Read-Display-Type-Rs	11.6.6	o			n/a	
9	Read-Master-Core-Rq		n/a		11.5.6	m	
10	Read-Master-Core-Rs	11.6.7	m			n/a	
11	Read-Appl-Core-Rq		n/a		11.5.7	m	
12	Read-Appl-Core-Rs	11.6.8	m			n/a	
13	Write-Appl-Core-Rq		n/a		11.5.8	m	
14	Write-Appl-Core-Rs	11.6.9	m			n/a	
15	Write-Appl-Core-Conf-Rq		n/a		11.5.9	m	
16	Write-Appl-Core-Conf-Rs	11.6.10	m			n/a	
17	Read-Appl-Record-Rq		n/a		11.5.10	m	
18	Read-Appl-Record-Rs	11.6.11	m			n/a	
19	Write-Appl-Record-Curr-Rq		n/a		11.5.11	m	
20	Write-Appl-Record-Curr-Rs	11.6.12	m			n/a	
21	Write-Appl-Record-Curr-Conf-Rq		n/a		11.5.12	m	
22	Write-Appl-Record-Curr-Conf-Rs	11.6.13	m			n/a	
23	Write-Appl-Record-Next-Rq		n/a		11.5.13	m	
24	Write-Appl-Record-Next-Rs	11.6.14	m			n/a	
25	Write-Appl-Record-Next-Conf-Rq		n/a		11.5.14	m	
26	Write-Appl-Record-Next-Conf-Rs	11.6.15	m			n/a	
27	Action-Rq		n/a		11.5.15	o	
28	Action-Rs	11.6.16	o			n/a	

B.7 Procedures

Table B.4: Procedures

Item	Supported procedure	Reference	Status	Support (Y/N)
1	Session handling for directives with read access	11.2.3	m	
2	Session handling for directives with write access	11.2.3	m	
3	Session handling for Close-Rq	11.2.3	m	
4	Session handling for Action-Rq	11.2.3	o	
5	Session handling for Read-Display-Type-Rq	11.2.3	o	

History

Document history		
V1.1.1	March 2010	Publication