



**Intelligent Transport Systems (ITS);  
Testing;  
Conformance test specifications for  
Cooperative Awareness Basic Service (CA);  
Part 1: Test requirements and Protocol Implementation  
Conformance Statement (PICS) pro forma**

---

**Reference**

RTS/ITS-00188

---

**Keywords**

ITS, PICS, testing

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	5
3 Definition of terms, symbols and abbreviations.....	5
3.1 Terms.....	5
3.2 Symbols.....	5
3.3 Abbreviations .....	6
4 Conformance requirement concerning PICS.....	6
<b>Annex A (normative): CA PICS Pro forma.....</b>	<b>7</b>
A.1 Partial cancellation of copyright.....	7
A.2 Guidance for completing the PICS pro forma.....	7
A.2.1 Purposes and structure.....	7
A.2.2 Abbreviations and conventions .....	7
A.2.3 Instructions for completing the PICS pro forma.....	9
A.3 Identification of the implementation .....	9
A.3.1 Introduction .....	9
A.3.2 Date of the statement.....	9
A.3.3 Implementation Under Test (IUT) identification .....	9
A.3.4 System Under Test (SUT) identification .....	9
A.3.5 Product supplier.....	10
A.3.6 Client (if different from product supplier).....	10
A.3.7 PICS contact person .....	11
A.4 Identification of the protocol.....	11
A.5 Global statement of conformance.....	11
A.6 Tables .....	12
History .....	13

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 1 of a multi-part deliverable covering Conformance test specifications for Cooperative Awareness Basic Service (CA), as identified below:

- Part 1:** "**Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma**";
- Part 2: "Test Suite Structure and Test Purposes (TSS & TP)";
- Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) pro forma for Conformance test specification for Cooperative Awareness Basic Service (CA) as defined in ETSI EN 302 637-2 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [i.2].

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 637-2 (V1.4.1): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 9646-1 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".
- [i.2] ISO/IEC 9646-7 (1995): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 302 637-2 [1], ISO/IEC 9646-1 [i.1] and ISO/IEC 9646-7 [i.2] apply.

### 3.2 Symbols

Void.

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATS	Abstract Test Suite
CA	Cooperative Awareness
CAM	Cooperative Awareness Messages
CAN	Controller Area Network
ITS	Intelligent Transport Systems
ITS-S	ITS-Station
IUT	Implementation Under Test
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
SUT	System Under Test
TP	Test Purpose
TSS	Test Suite Structure

---

## 4 Conformance requirement concerning PICS

If it claims to conform to the present document, the actual PICS pro forma to be filled in by a supplier shall be technically equivalent to the text of the PICS pro forma given in annex A, and shall preserve the numbering, naming and ordering of the pro forma items.

A PICS which conforms to the present document shall be a conforming PICS pro forma completed in accordance with the instructions for completion given in clause A.2.

---

## Annex A (normative): CA PICS Pro forma

### A.1 Partial cancellation of copyright

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the Partial PICS pro forma in this annex so that it can be used for its intended purposes and may further publish the completed Partial PICS.

---

### A.2 Guidance for completing the PICS pro forma

#### A.2.1 Purposes and structure

The purpose of this PICS pro forma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ETSI EN 302 637-2 (V1.4.1) [1] may provide information about the implementation in a standardized manner.

The PICS pro forma is subdivided into clauses for the following categories of information:

- guidance for completing the PICS pro forma;
- identification of the implementation;
- identification of the ETSI EN 302 637-2 (V1.4.1) [1];
- global statement of conformance;
- PICS pro forma tables.

#### A.2.2 Abbreviations and conventions

The PICS pro forma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [i.2].

##### Item column

The item column contains a number which identifies the item in the table.

##### Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

##### Status column

The following notations, defined in ISO/IEC 9646-7 [i.2], are used for the status column:

- |     |   |
|-----|---|
| m   | mandatory - the capability is required to be supported;   |
| o   | optional - the capability may be supported or not;  |
| n/a | not applicable - in the given context, it is impossible to use the capability;                  |
| x   | prohibited (excluded) - there is a requirement not to use this capability in the given context; |

- o.i qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table;
- c.i conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table;
- i irrelevant (out-of-scope) - capability outside the scope of the reference specification. No answer is requested from the supplier.

NOTE 1: This use of "i" status is not to be confused with the suffix "i" to the "o" and "c" statuses above.

#### Reference column

The reference column makes reference to ETSI EN 302 637-2 (V1.4.1) [1], except where explicitly stated otherwise.

#### Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [i.2], are used for the support column:

- Y or y supported by the implementation;
- N or n not supported by the implementation;
- N/A, n/a or - no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

NOTE 2: As stated in ISO/IEC 9646-7 [i.2], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

#### Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values: <min value> .. <max value>  
EXAMPLE: 5 .. 20
- list of values: <value1>, <value2>, ..., <valueN>  
EXAMPLE: 2, 4 ,6 ,8, 9  
EXAMPLE: '1101'B, '1011'B, '1111'B  
EXAMPLE: '0A'H, '34'H, '2F'H
- list of named values: <name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)  
EXAMPLE: reject(1), accept(2)
- length: size (<min size> .. <max size>)  
EXAMPLE: size (1 .. 8)

#### Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

#### References to items

For each possible item answer (answer in the support column) within the PICS pro forma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a slash character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.



EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

### Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

## A.2.3 Instructions for completing the PICS pro forma

The supplier of the implementation shall complete the PICS pro forma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the PICS pro forma.

---

## A.3 Identification of the implementation

### A.3.1 Introduction

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) shall be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information shall both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS shall be named as the contact person.

### A.3.2 Date of the statement

.....

### A.3.3 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

### A.3.4 System Under Test (SUT) identification

SUT name:

.....

.....

Hardware configuration:

.....  
.....  
.....

Operating system:

.....

### A.3.5 Product supplier

Name:

.....

Address:

.....  
.....  
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....  
.....  
.....

### A.3.6 Client (if different from product supplier)

Name:

.....

Address:

.....  
.....  
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

### A.3.7 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

---

## A.4 Identification of the protocol

This PICS pro forma applies to the following standard: ETSI EN 302 637-2 (V1.4.1) [1]: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service".

---

## A.5 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No) .....

NOTE: Answering "No" to this question indicates non-conformance to the CA standard specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS pro forma.

## A.6 Tables

Unless stated otherwise, the column references of all tables below indicates the clause numbers of ETSI EN 302 637-2 [1].

**Table A.1: ITS Station type**

Item	Type	Reference	Status	Support
1	Road side ITS-S	6.1.2	o.101	
2	Vehicle ITS-S	6.1.2	o.101	
o.101: It is mandatory to support at least one of these types.				

**Table A.2: ITS Station type**

Item	Type	Reference	Status	Support
1	G5 Radio communication	6.1.3	o.201	
2	CV2X radio communication	6.1.3	o.201	
o.201: It is mandatory to support at least one of these types.				

**Table A.3: CA vehicle profiles**

Item	CA vehicle profile	Reference	Status	Support
1	PublicTransport	7.4	o	
2	SpecialTransport	7.4	o	
3	DangerousGoods	7.4	o	
4	RoadWork	7.4	o	
5	Rescue	7.4	o	
6	Emergency	7.4	o	
7	SafetyCar	7.4	o	

**Table A.4: CA Basic Functionality**

Item	Vehicle Type	Reference	Status	Support
1	Transmission of CA Messages	4.3	m	
2	Reception of CA Messages	4.4	m	

**Table A.5: ITS Security mode**

Item	Type	Reference	Status	Support
1	ITS-S security mode enabled	Table 2	m	

**Table A.6: Timing requirements**

Item	Name of field	Reference	Default value	Status	Support
1	Maximum time interval between CAM generation (T_GENCAMMAX)	6.1.3	1 000 ms	m	
2	Minimum time interval between CAM generation (T_GENCAMMIN)	6.1.3	100 ms	m	
3	T_GENCAMDCC	6.1.3	$T\_GENCAMMIN \leq T\_GENCAMDCC \leq T\_GENCAMMAX$	c.601	
c.601: This item is mandatory when the item A.2.2 is supported.					

---

## History

<b>Document history</b>		
V1.1.1	March 2011	Publication
V1.2.1	April 2014	Publication
V1.3.1	July 2015	Publication
V1.4.1	March 2017	Publication
V1.5.1	April 2020	Publication