

# ETSI TS 103 280 V2.1.1 (2017-08)



TECHNICAL SPECIFICATION

## **Lawful Interception (LI); Dictionary for common parameters**



---

Reference

RTS/LI-00146

---

Keywords

dictionary, Lawful Interception, security

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.  
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	6
3 Abbreviations .....	6
4 Release management .....	7
5 Parameter requirements.....	7
5.0 Introduction .....	7
5.1 Parameter attributes .....	7
5.2 Parameter naming conventions.....	8
5.3 Technology conventions.....	8
6 Parameter dictionary.....	8
7 Technical implementation .....	16
7.1 XSD.....	16
7.2 ASN.1 .....	16
<b>Annex A (normative): XSD definition.....</b>	<b>17</b>
<b>Annex B (normative): ASN.1 definition .....</b>	<b>20</b>
<b>Annex C (informative): Change Request history.....</b>	<b>21</b>
History .....	22

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

It contains also the XSD technical implementation as attachment to the original document available from the ETSI site.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document defines a dictionary of parameters that are commonly used in multiple TC LI specifications. Aside from defining a dictionary, the present document aims to provide technical means for other specifications to use. It is encouraged to use the present document in the development of new specifications.

It is foreseen that regular maintenance of the present document is be required. As such release management requirements will be defined.

Before accepting any new common parameter, the present document will provide a set of requirements the parameter has to comply to in order to become a common parameter.

---

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery".
- [2] W3C Recommendation 5 April 2012: "W3C XML Schema Definition Language (XSD)".
- [3] Recommendation ITU-T X.680: "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation".
- [4] Recommendation ITU-T E.164: "The international public telecommunication numbering plan".
- [5] Recommendation ITU-T E.212: "The international identification plan for public networks and subscriptions".
- [6] ETSI TS 123 003: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); Numbering, addressing and identification (3GPP TS 23.003)".
- [7] ETSI TS 102 657: "Lawful Interception (LI); Retained data handling; Handover interface for the request and delivery of retained data".
- [8] IETF RFC 791: "Internet Protocol".
- [9] IETF RFC 4632: "Classless Inter-domain Routing (CIDR): The Internet Address Assignment and Aggregation Plan".
- [10] IETF RFC 8200: "Internet Protocol, Version 6 (IPv6) Specification".
- [11] IETF RFC 4291: "IP Version 6 Addressing Architecture".
- [12] IETF RFC 793: "Transmission Control Protocol".
- [13] IETF RFC 768: "User Datagram Protocol".
- [14] IEEE 802.3<sup>TM</sup>: "IEEE Standard for Ethernet".

- [15] IETF RFC 5322: "Internet Message Format".
- [16] W3C Recommendation 28 October 2014: "HTML5 A vocabulary and associated APIs for HTML and XHTML".
- [17] IETF RFC 4122: "A Universally Unique Identifier (UUID) URN Namespace".
- [18] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions -- Part 1: Country codes".
- [19] IEEE Std 1003.1™-2008: "IEEE Standard for Information Technology - Portable Operating System Interface (POSIX(R))".
- [20] ISO/IEC 7812-1:2015: "Identification cards -- Identification of issuers -- Part 1: Numbering system".
- [21] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [22] IETF RFC 3966: "The tel URI for Telephone Numbers".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

---

## 3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASCII	American Standard Code for Information Interchange
ASN.1	Abstract Syntax Notation One
CC	Content of Communication
CIDR	Classless Inter-Domain Routing
CSP	Communications Service Provider
HEX	HEXadecimal
HI	Handover Interface
HI1	Handover Interface port 1 (for administrative information)
HI2	Handover Interface port 2 (for Intercept Related Information)
HI3	Handover Interface port 3 (for Content of Communication)
IMEI	International Mobile station Equipment Identity
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
IRI	Intercept Related Information
ISO	International Organisation for Standardisation
ITU-T	International Telecommunication Union - Telecommunication
LEA	Law Enforcement Agency
LIID	Lawful Interception Identifier
MAC	Media Access Control
POSIX	Portable Operating System Interface
RFC	Request For Comments

SIP	Session Initialization Protocol
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
URI	Uniform Resource Identifier
UTC	Coordinated Universal Time
UUID	Universally Unique IDentifier
XML	eXtended Markup Language
XSD	XML Schema Definition

---

## 4 Release management

This clause describes the release management requirements. The requirements are:

- The version of the present document is defined as <major>.<minor>.<patch>.
- The major version should be incremented when making a backwards incompatible change.
- The minor version should be incremented when adding backwards compatible functionality.
- The patch version should be incremented when fixing a backwards compatible bug.
- Once a major version has been incremented, the previous major version will be supported for 2 years after publication of the new version. Change requests issued to a version that is no longer supported will need to be issued for the latest supported major version.

---

## 5 Parameter requirements

### 5.0 Introduction

This clause describes the requirements a parameter should comply to in order to be specified as a common parameter.

### 5.1 Parameter attributes

#### Name

- The parameter should be assigned a unique name. The naming conventions used are described in clause 5.2.

#### Description

- A description of the parameter should be provided.

#### Usage guidance

- If there are circumstances in which additional usage guidance is applicable, use cases may be described in this attribute.

#### References to other specifications

- If the parameter is specified in another specification (such as an RFC), a reference to that specification shall be provided. If possible, the reference should point to the exact clause or clause in the specification.

EXAMPLE: Specify one or more sample values of the parameter.

#### Technical means to define and validate the parameter

- If possible, provide a regular expression to specify the value that is accepted by this parameter. Implementations may be required to perform additional validation on the value. The regular expressions follow the IEEE POSIX [19], section 9 regular expression format but shall be limited to the regular expression capabilities supported by XSD [2].

- Define the parameter in the XSD [2] in section 7.1.
- Define the parameter in the ASN.1 [3] in section 7.2.

## 5.2 Parameter naming conventions

### Allowed characters

- The following characters are allowed: A-Z, a-z and 0-9.

### Camel casing

- The name of the parameter is to be CamelCased, where the first character is uppercased. Any acronyms should be uppercased.

EXAMPLE:

- IPv4Address.
- SIPURI.
- EmailAddress.

## 5.3 Technology conventions

The used technologies defined in clause 7 may impose requirements that conflict with the requirements in clauses 5.1 and 5.2. In the case of a conflict and in exceptional cases, it is allowed to deviate from the requirements above.

---

# 6 Parameter dictionary

## LIID

Name	LIID
<b>Description</b>	<p>For each target identity related to an interception measure, the authorized CSP operator shall assign a special Lawful Interception IDentifier (LIID), which has been agreed between the LEA and the CSP. It is used within parameters of all HI interface ports.</p> <p>Using an indirect identification, pointing to a target identity makes it easier to keep the knowledge about a specific interception target limited within the authorized CSP operators and the handling agents at the LEA.</p> <p>The Lawful Interception IDentifier LIID is a component of the CC delivery procedure and of the IRI records. It shall be used within any information exchanged at the Handover Interfaces HI2 and HI3 for identification and correlation purposes.</p> <p>The LIID format shall consist of alphanumeric characters. It might for example, among other information, contain a lawful authorization reference number, and the date, when the lawful authorization was issued.</p> <p>The authorized CSP shall either enter a unique LIID for each target identity of the interception subject or as a national option a single LIID for multiple target identities all pertaining to the same interception subject.</p> <p>EXAMPLE: The interception subject has a telephony service with three telephone numbers. The CSP enters for each telephone number an own LIID, or optionally enters one LIID for all three telephone numbers.</p> <p>If more than one LEA intercepts the same target identity, there shall be unique LIIDs assigned, relating to each LEA.</p>
<b>Usage guidance</b>	<p>The LIID is defined as an OCTET STRING in ASN.1. This means it is possible to use binary octets or ASCII printable characters to express the LIID. To correctly handle this, the parameter accepts both variations.</p>



<b>References</b>	ETSI TS 102 232-1 [1], clause 5.2.2.
<b>Example</b>	ZZZ123 (ASCII printable LIID) 46565527098f6bcd4621d373cade4e832627b4f6ff00ff00ff (Binary LIID, represented in HEX)
<b>Regular expression</b>	^(?!~}{1,25}) ([0-9a-f]{26,50})\$
<b>XSD</b>	LIID, simpleType
<b>ASN.1</b>	LIID, OCTET STRING

### UTCDateTime

<b>Name</b>	UTCDateTime
<b>Description</b>	A UTC timestamp with second precision.
<b>Usage guidance</b>	-
<b>References</b>	W3C XML Schema Definition Language [2], section 3.3.7
<b>Example</b>	2015-12-27T13:37:00Z
<b>Regular expression</b>	^[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}z\$
<b>XSD</b>	UTCDateTime, simpleType
<b>ASN.1</b>	Not defined

### UTCMicrosecondDateTime

<b>Name</b>	UTCMicrosecondDateTime
<b>Description</b>	A UTC timestamp with microsecond precision.
<b>Usage guidance</b>	-
<b>References</b>	W3C XML Schema Definition Language [2], section 3.3.7
<b>Example</b>	2015-12-27T13:37:00.012345Z
<b>Regular expression</b>	^[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}z\$
<b>XSD</b>	UTCMicrosecondDateTime, simpleType
<b>ASN.1</b>	Not defined

### QualifiedDateTime

<b>Name</b>	QualifiedDateTime
<b>Description</b>	A timestamp with second precision and timezone qualifier.
<b>Usage guidance</b>	-
<b>References</b>	W3C XML Schema Definition Language [2], section 3.3.7
<b>Example</b>	2015-12-27T13:37:00+02:00
<b>Regular expression</b>	^[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(z [+-][0-9]{2}:[0-9]{2})\$
<b>XSD</b>	QualifiedDateTime, simpleType
<b>ASN.1</b>	Not defined

### QualifiedMicrosecondDateTime

<b>Name</b>	QualifiedMicrosecondDateTime
<b>Description</b>	A timestamp with microsecond precision and timezone qualifier.
<b>Usage guidance</b>	-
<b>References</b>	W3C XML Schema Definition Language [2], section 3.3.7
<b>Example</b>	2015-12-27T13:37:00.012345+02:00
<b>Regular expression</b>	^[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}(z [+-][0-9]{2}:[0-9]{2})\$
<b>XSD</b>	QualifiedMicrosecondDateTime, simpleType
<b>ASN.1</b>	Not defined

**InternationalE164**

<b>Name</b>	InternationalE164
<b>Description</b>	E.164 Number in fully international format, written as decimal digits.
<b>Usage guidance</b>	-
<b>References</b>	Recommendation ITU-T E.164 [4], clause 6
<b>Example</b>	31612345678
<b>Regular expression</b>	^[0-9]{1,15}\$
<b>XSD</b>	InternationalE164, simpleType
<b>ASN.1</b>	Not defined

**IMSI**

<b>Name</b>	IMSI
<b>Description</b>	International Mobile Subscriber Identity, written as decimal digits.
<b>Usage guidance</b>	-
<b>References</b>	Recommendation ITU-T E.212 [5], clause 6.1. 3GPP TS 23.003 [6], clause 2.2 and clause 2.3.
<b>Example</b>	204081234567890
<b>Regular expression</b>	^[0-9]{6,15}\$
<b>XSD</b>	IMSI, simpleType
<b>ASN.1</b>	Not defined

**IMEI**

<b>Name</b>	IMEI
<b>Description</b>	International Mobile station Equipment Identity, written as decimal digits without the Luhn check digit, annex B of ISO/IEC 7812-1 [20].
<b>Usage guidance</b>	To avoid implementation issues, the IMEI parameter explicitly excludes the Luhn check digit, annex B of ISO/IEC 7812-1 [20]. (See notes 1 and 2)
<b>References</b>	3GPP TS 23.003 [6], clause 6
<b>Example</b>	35395803121326
<b>Regular expression</b>	^[0-9]{14}\$
<b>XSD</b>	IMEI, simpleType
<b>ASN.1</b>	Not defined
NOTE 1: ETSI TS 102 657 [7] clause E.3 identifies potential issues with the inclusion/exclusion of the check digit. As such, the IMEI parameter is explicitly specified without the check digit.	
NOTE 2: The IMEICheckDigit parameter can be used when the check digit is explicitly required.	

**IMEICheckDigit**

<b>Name</b>	IMEICheckDigit
<b>Description</b>	International Mobile station Equipment Identity, written as decimal digits with the Luhn check digit, annex B of ISO/IEC 7812-1 [20].
<b>Usage guidance</b>	
<b>References</b>	3GPP TS 23.003 [6], clause 6
<b>Example</b>	35395803121326
<b>Regular expression</b>	^[0-9]{15}\$
<b>XSD</b>	IMEICheckDigit, simpleType
<b>ASN.1</b>	Not defined

**IPv4Address**

<b>Name</b>	IPv4Address
<b>Description</b>	IPv4 address, written in dotted decimal notation.
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 791 [8]
<b>Example</b>	192.0.2.1
<b>Regular expression</b>	^((25[0-5] 2[0-4][0-9] [01]?[0-9]?[0-9])\.){3}(25[0-5] 2[0-4][0-9] [01]?[0-9]?[0-9])\$
<b>XSD</b>	IPv4Address, simpleType
<b>ASN.1</b>	Not defined

**IPv4CIDR**

<b>Name</b>	IPv4CIDR
<b>Description</b>	IPv4 CIDR, written in dotted decimal notation followed by CIDR notation.
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 791 [8], IETF RFC 4632 [9]
<b>Example</b>	192.0.2.0/24
<b>Regular expression</b>	^((25[0-5] 2[0-4][0-9] [01]?[0-9]?[0-9])\.){3}(25[0-5] 2[0-4][0-9] [01]?[0-9]?[0-9])/([1-2]?[0-9] 3[0-2])\$
<b>XSD</b>	IPv4CIDR, simpleType
<b>ASN.1</b>	Not defined

**IPv6Address**

<b>Name</b>	IPv6Address
<b>Description</b>	IPv6 address, written as eight groups of four hexadecimal digits separated by a colon.
<b>Usage guidance</b>	It is recognized that IPv6 address formatting has various options. To reduce complexity in technical implementations, the IPv6Address parameter restricts the address to the fully uncompressed representation of the IPv6 address.
<b>References</b>	IETF RFC 8200 [10]
<b>Example</b>	2001:db8:0000:0000:0000:0000:0000:0001
<b>Regular expression</b>	^([0-9a-f]{4}:){7}([0-9a-f]{4})\$
<b>XSD</b>	IPv6Address, simpleType
<b>ASN.1</b>	Not defined

**IPv6CIDR**

<b>Name</b>	IPv6CIDR
<b>Description</b>	IPv6 CIDR, written as eight groups of four hexadecimal digits separated by a colon followed by CIDR notation.
<b>Usage guidance</b>	See IPv6Address parameter for usage guidance.
<b>References</b>	IETF RFC 8200 [10], IETF RFC 4632 [9] and IETF RFC 4291 [11]
<b>Example</b>	2001:db8:0000:0000:0000:0000:0000:0000/48
<b>Regular expression</b>	^([0-9a-f]{4}:){7}([0-9a-f]{4})/(((1-9)[0-9]?) (1[0-1][0-9]) (12[0-8]))\$
<b>XSD</b>	IPv6CIDR, simpleType
<b>ASN.1</b>	Not defined

**IPAddress**

<b>Name</b>	IPAddress
<b>Description</b>	Either a IPv4Address parameter or IPv6Address parameter.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	XSD <IPAddress> <IPv4Address>192.0.2.1</IPv4Address> </IPAddress>
<b>Regular expression</b>	-
<b>XSD</b>	IPAddress, complexType
<b>ASN.1</b>	Not defined

## IPCIDR

<b>Name</b>	IPCIDR
<b>Description</b>	Either a IPv4CIDR parameter or IPv6CIDR parameter.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	XSD <pre>&lt;IPCIDR&gt;   &lt;IPv4CIDR&gt;192.0.2.0/24&lt;/IPv4CIDR&gt; &lt;/IPCIDR&gt;</pre>
<b>Regular expression</b>	-
<b>XSD</b>	IPCIDR, complexType
<b>ASN.1</b>	Not defined

## TCPPort

<b>Name</b>	TCPPort
<b>Description</b>	TCP port, written in decimal notation.
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 793 [12]
<b>Example</b>	22
<b>Regular expression</b>	<code>^([1-9][0-9]{0,3} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])\$</code>
<b>XSD</b>	TCPPort, simpleType
<b>ASN.1</b>	TCPPort, INTEGER

## TCPPortRange

<b>Name</b>	TCPPortRange
<b>Description</b>	TCP port range, consists of a 'start' TCPPort parameter and an 'end' TCPPort parameter.
<b>Usage guidance</b>	The start and end values are inclusive.
<b>References</b>	-
<b>Example</b>	Regular expression 1024-2048  XSD <pre>&lt;TCPPortRange&gt;   &lt;start&gt;1024&lt;/start&gt;   &lt;end&gt;2048&lt;/end&gt; &lt;/TCPPortRange&gt;</pre>
<b>Regular expression</b>	<code>^([1-9][0-9]{0,3} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])-([1-9][0-9]{0,3} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])\$</code>
<b>XSD</b>	TCPPortRange, complexType
<b>ASN.1</b>	TCPPortRange, SEQUENCE

## UDPPort

<b>Name</b>	UDPPort
<b>Description</b>	UDP port, written in decimal notation.
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 768 [13]
<b>Example</b>	53
<b>Regular expression</b>	<code>^([0-9]{1,4} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])\$</code>
<b>XSD</b>	UDPPort, simpleType
<b>ASN.1</b>	UDPPort, INTEGER

## UDPPortRange

<b>Name</b>	UDPPortRange
<b>Description</b>	UDP port range, consists of a 'start' UDPPort parameter and an 'end' UDPPort parameter.
<b>Usage guidance</b>	The start and end values are inclusive.
<b>References</b>	-
<b>Example</b>	Regular expression 2048-4096 XSD <UDPPortRange> <start>2048</start> <end>4096</end> </UDPPortRange>
<b>Regular expression</b>	^([0-9]{1,4} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])-( [0-9]{1,4} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5] )\$
<b>XSD</b>	UDPPortRange, complexType
<b>ASN.1</b>	UDPPortRange, SEQUENCE

## Port

<b>Name</b>	Port
<b>Description</b>	Either a TCPPort parameter or a UDPPort parameter.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	XSD <Port> <TCPPort>22</TCPPort> </Port>
<b>Regular expression</b>	^([0-9]{1,4} [1-5][0-9]{4} 6[0-4][0-9]{3} 65[0-4][0-9]{2} 655[0-2][0-9] 6553[0-5])\$
<b>XSD</b>	Port, complexType
<b>ASN.1</b>	Port, CHOICE

## PortRange

<b>Name</b>	PortRange
<b>Description</b>	Either a TCPPortRange parameter or a UDPPortRange parameter.
<b>Usage guidance</b>	The start and end values are inclusive.
<b>References</b>	-
<b>Example</b>	XSD <PortRange> <TCPPortRange> <start>2048</start> <end>4096</end> </TCPPortRange> </PortRange>
<b>Regular expression</b>	-
<b>XSD</b>	PortRange, complexType
<b>ASN.1</b>	PortRange, CHOICE

### IPAddressPort

<b>Name</b>	IPAddressPort
<b>Description</b>	Combination of an IPAddress parameter and a Port parameter.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	XSD <pre>&lt;IPAddressPort&gt;   &lt;address&gt;     &lt;IPv4Address&gt;192.0.2.1&lt;/IPv4Address&gt;   &lt;/address&gt;   &lt;port&gt;     &lt;TCPPort&gt;22&lt;/TCPPort&gt;   &lt;/port&gt; &lt;/IPAddressPort&gt;</pre>
<b>Regular expression</b>	-
<b>XSD</b>	IPAddressPort, complexType
<b>ASN.1</b>	Not defined

### IPAddressPortRange

<b>Name</b>	IPAddressPortRange
<b>Description</b>	Combination of an IPAddress parameter and a PortRange parameter.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	XSD <pre>&lt;IPAddressPortRange&gt;   &lt;address&gt;     &lt;IPv4Address&gt;192.0.2.1&lt;/IPv4Address&gt;   &lt;/address&gt;   &lt;portRange&gt;     &lt;TCPPortRange&gt;       &lt;start&gt;2048&lt;/start&gt;       &lt;end&gt;4096&lt;/end&gt;     &lt;/TCPPortRange&gt;   &lt;/portRange&gt; &lt;/IPAddressPortRange&gt;</pre>
<b>Regular expression</b>	-
<b>XSD</b>	IPAddressPortRange, complexType
<b>ASN.1</b>	Not defined

### MACAddress

<b>Name</b>	MACAddress
<b>Description</b>	MAC address, written as six groups of two hexadecimal digits separated by a colon.
<b>Usage guidance</b>	-
<b>References</b>	IEEE 802.3 [14]
<b>Example</b>	c0:ff:ee:c0:ff:ee
<b>Regular expression</b>	^[a-f0-9]{2}:){5}[a-f0-9]{2}\$
<b>XSD</b>	MACAddress, simpleType
<b>ASN.1</b>	Not defined

### EmailAddress

<b>Name</b>	EmailAddress
<b>Description</b>	E-mail address
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 5322 [15]
<b>Example</b>	john.doe@example.com
<b>Regular expression</b>	^[a-zA-Z0-9.!#\$%&'*\+/=?^`{ }~-]+@[a-zA-Z0-9]([a-zA-Z0-9-]{0,61}[a-zA-Z0-9])?(\.[a-zA-Z0-9]([a-zA-Z0-9-]{0,61}[a-zA-Z0-9])?)*\$ See note.
<b>XSD</b>	EmailAddress, simpleType
<b>ASN.1</b>	Not defined
<b>NOTE:</b>	The regular expression above is sourced from the W3C HTML5 Recommendation [16].

**UUID**

<b>Name</b>	UUID
<b>Description</b>	UUID
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 4122 [17]
<b>Example</b>	de305d54-75b4-431b-adb2-eb6b9e546013
<b>Regular expression</b>	^[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}\$
<b>XSD</b>	UUID, simpleType
<b>ASN.1</b>	Not defined

**ISOCountryCode**

<b>Name</b>	ISOCountryCode
<b>Description</b>	An ISO 3166-1 alpha-2 [18] two-letter country code.
<b>Usage guidance</b>	-
<b>References</b>	ISO 3166-1 alpha-2 [18]
<b>Example</b>	"NL"
<b>Regular expression</b>	^[A-Z]{2}\$
<b>XSD</b>	ISOCountryCode, simpleType
<b>ASN.1</b>	Not defined

**ShortString**

<b>Name</b>	ShortString
<b>Description</b>	A string with a maximum length of 255 characters.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	string
<b>Regular expression</b>	-
<b>XSD</b>	ShortString, simpleType
<b>ASN.1</b>	Not defined

**LongString**

<b>Name</b>	LongString
<b>Description</b>	A string with a maximum length of 65 535 characters.
<b>Usage guidance</b>	-
<b>References</b>	-
<b>Example</b>	string
<b>Regular expression</b>	-
<b>XSD</b>	ShortString, simpleType
<b>ASN.1</b>	Not defined

**SIPURI**

<b>Name</b>	SIPURI
<b>Description</b>	SIP URI
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 3261 [21] section 19.1
<b>Example</b>	sip:user@example.com
<b>Regular expression</b>	^sips?:[a-zA-Z0-9!#\$%&-'=?-\\[\]_~%]+\$
<b>XSD</b>	SIPURI, simple type
<b>ASN.1</b>	Not defined

**TELURI**

<b>Name</b>	TELURI
<b>Description</b>	TEL URI
<b>Usage guidance</b>	-
<b>References</b>	IETF RFC 3966 [22]
<b>Example</b>	tel:+447700900000
<b>Regular expression</b>	^tel:[a-zA-Z0-9!#\$%&-i=?-[\ ]_~% ]+\$
<b>XSD</b>	TELURI, simple type
<b>ASN.1</b>	Not defined

---

## 7 Technical implementation

### 7.1 XSD

The XSD definition is defined in annex A. The XSD file named "TS\_103\_280\_v020101.xsd" is contained in archive "ts\_103280v020101p0.zip" which accompanies the present document.

The targetNamespace of the XSD is set to 'http://uri.etsi.org/03280/common/2017/07'. The XSD version is set to 2.1.1.

The targetNamespace shall be increased in the event of a major release as defined in clause 4 and the requirement to do so. The year in the targetNamespace shall be set to the year and month of publication of the major release.

The XSD version shall be increased according to the versioning scheme as defined in clause 4. A change to the present document shall not necessarily lead to a new XSD version. The XSD version shall only be increased when a change to the XSD is required, as such the version of the present document and the XSD version may differ.

As the XSD version is not part of the targetNamespace, an implementation should take into account that the appropriate version is used when importing the XSD.

### 7.2 ASN.1

The ASN.1 definition is defined in annex B. The ASN.1 file named "TS\_103\_280\_v020101.asn1" is contained in archive "ts\_103280v020101p0.zip" which accompanies the present document.

The ASN.1 object identifier is defined as itu-t(0) identified-organization(4) etsi(0) common-parameters(3280) version211(211).

The ASN.1 version shall be increased according to the versioning scheme as defined in clause 4. A change to the present document shall not necessarily lead to a new ASN.1 version. The ASN.1 version shall only be increased when a change to the ASN.1 is required, as such the version of the present document and the ASN.1 version may differ.



## Annex A (normative): XSD definition

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns="http://uri.etsi.org/03280/common/2017/07"
targetNamespace="http://uri.etsi.org/03280/common/2017/07" version="2.1.1"
elementFormDefault="qualified">
  <xs:simpleType name="ShortString">
    <xs:restriction base="xs:string">
      <xs:maxLength value="255"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="LongString">
    <xs:restriction base="xs:string">
      <xs:maxLength value="65535"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="LIID">
    <xs:restriction base="xs:normalizedString">
      <xs:pattern value="([!~]{1,25})|([0-9a-f]{26,50})"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="UTCDateTime">
    <xs:restriction base="xs:dateTime">
      <xs:pattern value="[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}Z"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="UTCMicrosecondDateTime">
    <xs:restriction base="xs:dateTime">
      <xs:pattern value="[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}Z"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="QualifiedDateTime">
    <xs:restriction base="xs:dateTime">
      <xs:pattern value="[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}(Z|[-+][0-9]{2}:[0-9]{2})"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="QualifiedMicrosecondDateTime">
    <xs:restriction base="xs:dateTime">
      <xs:pattern value="[0-9]{4}-[0-9]{2}-[0-9]{2}T[0-9]{2}:[0-9]{2}:[0-9]{2}\.[0-9]{6}(Z|[-+][0-9]{2}:[0-9]{2})"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="InternationalE164">
    <xs:restriction base="xs:token">
      <xs:pattern value="[0-9]{1,15}"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IMSI">
    <xs:restriction base="xs:token">
      <xs:pattern value="[0-9]{6,15}"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IMEI">
    <xs:restriction base="xs:token">
      <xs:pattern value="[0-9]{14}"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IMEICheckDigit">
    <xs:restriction base="xs:token">
      <xs:pattern value="[0-9]{15}"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IPv4Address">
    <xs:restriction base="xs:token">
      <xs:pattern value="((25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IPv4CIDR">
    <xs:restriction base="xs:token">
      <xs:pattern value="((25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])/([1-2]?[0-9]|3[0-2])"/>
    </xs:restriction>
  </xs:simpleType>

```

```

    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IPv6Address">
    <xs:restriction base="xs:token">
      <xs:pattern value="([0-9a-f]{4}:){7}([0-9a-f]{4})"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:simpleType name="IPv6CIDR">
    <xs:restriction base="xs:token">
      <xs:pattern value="([0-9a-f]{4}:){7}([0-9a-f]{4})/(((1-9)[0-9]?)|(1[0-1][0-9])|(12[0-
8]))"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="IPAddress">
    <xs:choice>
      <xs:element name="IPv4Address" type="IPv4Address"/>
      <xs:element name="IPv6Address" type="IPv6Address"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="IPCIDR">
    <xs:choice>
      <xs:element name="IPv4CIDR" type="IPv4CIDR"/>
      <xs:element name="IPv6CIDR" type="IPv6CIDR"/>
    </xs:choice>
  </xs:complexType>
  <xs:simpleType name="TCPPort">
    <xs:restriction base="xs:integer">
      <xs:minExclusive value="1"/>
      <xs:maxInclusive value="65535"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="TCPPortRange">
    <xs:sequence>
      <xs:element name="start" type="TCPPort"/>
      <xs:element name="end" type="TCPPort"/>
    </xs:sequence>
  </xs:complexType>
  <xs:simpleType name="UDPPort">
    <xs:restriction base="xs:integer">
      <xs:minInclusive value="0"/>
      <xs:maxInclusive value="65535"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="UDPPortRange">
    <xs:sequence>
      <xs:element name="start" type="UDPPort"/>
      <xs:element name="end" type="UDPPort"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Port">
    <xs:choice>
      <xs:element name="TCPPort" type="TCPPort"/>
      <xs:element name="UDPPort" type="UDPPort"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="PortRange">
    <xs:choice>
      <xs:element name="TCPPortRange" type="TCPPortRange"/>
      <xs:element name="UDPPortRange" type="UDPPortRange"/>
    </xs:choice>
  </xs:complexType>
  <xs:complexType name="IPAddressPort">
    <xs:sequence>
      <xs:element name="address" type="IPAddress"/>
      <xs:element name="port" type="Port"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="IPAddressPortRange">
    <xs:sequence>
      <xs:element name="address" type="IPAddress"/>
      <xs:element name="portRange" type="PortRange"/>
    </xs:sequence>
  </xs:complexType>
  <xs:simpleType name="MACAddress">
    <xs:restriction base="xs:token">
      <xs:pattern value="([a-f0-9]{2}:){5}[a-f0-9]{2}"/>
    </xs:restriction>
  </xs:simpleType>

```

```

<xs:simpleType name="EmailAddress">
  <xs:restriction base="ShortString">
    <xs:pattern value="[a-zA-Z0-9\.\!#\$\%&'\*\+\-\|\/=\?\^\_`\{\|\}\~\-\]+@[a-zA-Z0-9]([a-zA-Z0-9-]{0,61}[a-zA-Z0-9])?(\.[a-zA-Z0-9]([a-zA-Z0-9-]{0,61}[a-zA-Z0-9])?)*/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="UUID">
  <xs:restriction base="xs:token">
    <xs:pattern value="[a-f0-9]{8}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{4}-[a-f0-9]{12}"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ISOCountryCode">
  <xs:restriction base="xs:token">
    <xs:pattern value="[A-Z]{2}"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="SIPURI">
  <xs:restriction base="xs:anyURI">
    <xs:pattern value="sips?:[a-zA-Z0-9!#\$\%&'-;=?-\[\]\_~%]+"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="TELURI">
  <xs:restriction base="xs:anyURI">
    <xs:pattern value="tel:[a-zA-Z0-9!#\$\%&'-;=?-\[\]\_~%]+"/>
  </xs:restriction>
</xs:simpleType>
</xs:schema>

```

## Annex B (normative): ASN.1 definition

```
Common-Parameters
{itu-t(0) identified-organization(4) etsi(0) common-parameters(3280) version211(211)}

DEFINITIONS IMPLICIT TAGS EXTENSIBILITY IMPLIED ::= BEGIN

-- Object Identifier definitions

commonParameterDomainId OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0) common-
parameters(3280) version211(211)}

-- Common Parameter: LIID (as defined in clause 6)

LIID ::= OCTET STRING (SIZE (1..25))

-- Common Parameter: TCPPort (as defined in clause 6)

TCPPort ::= INTEGER (1..65535)

-- Common Parameter: TCPPortRange (as defined in clause 6)

TCPPortRange ::= SEQUENCE
{
    start [0] TCPPort,
    end   [1] TCPPort
}

-- Common Parameter: UDPPort (as defined in clause 6)

UDPPort ::= INTEGER (0..65535)

-- Common Parameter: UDPPortRange (as defined in clause 6)

UDPPortRange ::= SEQUENCE
{
    start [0] UDPPort,
    end   [1] UDPPort
}

-- Common Parameter: Port (as defined in clause 6)

Port ::= CHOICE
{
    tCPPort [0] TCPPort,
    uDPPort [1] UDPPort
}

-- Common Parameter: PortRange (as defined clause 6)

PortRange ::= CHOICE
{
    tCPPortRange [0] TCPPortRange,
    uDPPortRange [1] UDPPortRange
}

END
```

## Annex C (informative): Change Request history

Status of the present document Dictionary for common parameters		
TC LI approval date	Version	Remarks
June 2015	1.1.1	First publication of the TS after approval by ETSI TC LI#39 Document prepared by Steije van Schelt (rapporteur)
August 2016	1.1.2	Revision for a minor editorial correction.
January 2017	1.2.1	Included Change Requests agreed by LI#42: CR001r1, LI(16)P42024r1 (Cat D) Addition of XSD annex to ETSI TS 103 280 CR002r1, LI(16)P420r1 (Cat B) ASN.1 definitions in ETSI TS 103 280 Document prepared by Steije van Schelt (rapporteur)
June 2017	2.1.1	Included Change Requests: CR003r1 (agreed by LI#43), LI(16)P43009r1 (Cat F) Short IMSI CR005 (agreed by LI#45), LI(17)P45025 (Cat B) Addition of SIP URI and TEL URI to common definitions CR006r1 (agreed by LI#45), LI(17)P45026r1 (Cat B) Addition of ASN.1 definitions to ETSI TS 103 280 (Cat B) Addition of ASN.1 definitions Document prepared by Steije van Schelt (EVE compliancy solutions, rapporteur)

---

## History

<b>Document history</b>		
V1.1.1	August 2015	Publication
V1.1.2	August 2015	Publication
V1.2.1	August 2016	Publication
V2.1.1	August 2017	Publication