



**Publicly Available Specification (PAS);
Intelligent Transport Systems (ITS);
MirrorLink[®];
Part 19: Network Information Data Service**

CAUTION

The present document has been submitted to ETSI as a PAS produced by CCC and approved by the ETSI Technical Committee Intelligent Transport Systems (ITS).

CCC is owner of the copyright of the document CCC-TS-052 and/or had all relevant rights and had assigned said rights to ETSI on an "as is basis". Consequently, to the fullest extent permitted by law, ETSI disclaims all warranties whether express, implied, statutory or otherwise including but not limited to merchantability, non-infringement of any intellectual property rights of third parties. No warranty is given about the accuracy and the completeness of the content of the present document.

Reference

RTS/ITS-98-19

Keywords

interface, ITS, PAS, smartphone

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

©ETSI 2019.

© Car Connectivity Consortium 2011-2019.

All rights reserved.

ETSI logo is a Trade Mark of ETSI registered for the benefit of its Members.

MirrorLink® is a registered trademark of Car Connectivity Consortium LLC.

RFB® and VNC® are registered trademarks of RealVNC Ltd.

UPnP® is a registered trademark of Open Connectivity Foundation, Inc.

Other names or abbreviations used in the present document may be trademarks of their respective owners.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definition of terms, symbols and abbreviations.....	5
3.1 Terms.....	5
3.2 Symbols.....	5
3.3 Abbreviations	6
4 Data Service Definition.....	6
4.1 Network Info Data Server Version 1.0.....	6
5 SBP Binding.....	8
Annex A (informative): Authors and Contributors.....	9
History	10

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 19 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.1].

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document is part of the MirrorLink® specification which specifies an interface for enabling remote user interaction of a mobile device via another device. The present document is written having a vehicle head-unit to interact with the mobile device in mind, but it will similarly apply for other devices, which provide a color display, audio input/output and user input mechanisms.

The present document specifies Network Information Data Service based on SBP (Service Binary Protocol) framework [i.2]. The service is used to provide network capabilities and status information of Access Point to Client.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

Not applicable.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TS 103 544-1 (V1.3.1): "Publicly Available Specification (PAS); Intelligent Transport Systems (ITS); MirrorLink®; Part 1: Connectivity".
- [i.2] ETSI TS 103 544-6 (V1.3.1): "Publicly Available Specification (PAS); Intelligent Transport Systems (ITS); MirrorLink®; Part 6: Service Binary Protocol (SBP)".

3 Definition of terms, symbols and abbreviations

3.1 Terms

Void.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AP	Access Point
SBP	Service Binary Protocol

4 Data Service Definition

4.1 Network Info Data Server Version 1.0

```

/** The purpose of Network Information service is to provide network
 * capabilities and status of the Access Point to Client.
 * When MirrorLink Server and Client are connected through Wi-Fi
 * technology of Wi-Fi Alliance, both the ML Server and the Client
 * can be either an Access Point (AP) or Client. In-vehicle setting,
 * it is important for Client to know network status information of
 * the AP, as network delay on AP may cause poor response time of
 * applications requiring Internet connectivity on Client. MirrorLink
 * Client can select the "best" network interface to be used for the
 * Internet access with regard to network capabilities and the status
 * information of AP. The algorithm for a selection of the network
 * interface for the Internet access on Client is out of scope of
 * the present document. Wi-Fi connection established between the
 * MirrorLink Server and the Client shall be maintained while the
 * Client configures its network interfaces to access the Internet.
 * @version 1.0
 */
SERVICE com.mirrorlink.networkinfo {
ENUM<LONG> networkTypes {
/** GSM
 */
GSM = 0x0000000000000001;
/** GPRS
 */
GPRS = 0x0000000000000002;
/** EDGE
 */
EDGE = 0x0000000000000004;
/** UMTS
 */
UMTS = 0x0000000000000100;
/** HSDPA
 */
HSDPA = 0x0000000000000200;
/** HSUPA
 */
HSUPA = 0x0000000000000400;
/** HSPA+
 */
HSPA_plus = 0x0000000000000800;
/** EV-DO
 */
EV_DO = 0x0000000000010000;
/** 1xRTT
 */
OnexRTT = 0x0000000000020000;
/** LTE
 */
LTE = 0x0000000100000000;
/** WiMax
 */
WiMAX = 0x0000000200000000;
/** Others
 */
Others = 0x0001000000000000;
};
/** High-level status information of the active network.
 */
ENUM<BYTE> connectivityStatusValues {
/** Active and tethering enabled

```

```

    */
    ACTIVE_TETHER_ENABLED = 0x01;
    /** Active but tethering disabled
    */
    ACTIVE_TETHER_DISABLED = 0x02;
    /** Inactive
    */
    INACTIVE = 0x03;
    /** Disabled
    */
    DISABLED = 0x04;
};
/** Signal strength of the active network.
*/
ENUM<INT> signalStrengthValues {
    /** No signal
    */
    NO_SIGNAL = 0;
    /** Weakest signal
    */
    WEAKEST_SIGNAL = 1;
    /** Weak signal
    */
    WEAK_SIGNAL = 2;
    /** Medium signal
    */
    MEDIUM_SIGNAL = 3;
    /** Strong signal
    */
    STRONG_SIGNAL = 4;
    /** Strongest signal
    */
    STRONGTEST_SIGNAL = 5;
};
/** Network Support Object carrying network capabilities of Access
 * Point.
 * @mandatory, @readable, @version 1.0, @uid 0x157ec746
 */
OBJECT NetworkSupport {
    /** Bit wise OR of all supported Network Types.
    * A zero value indicates that there is no network support for
    * head-unit connectivity
    * @uid 0x4de85dff
    */
    LONG supportedNetworkType;
};
/** NetworkStatus Object returns the current network status
 * information directly. If the current network information is not
 * available, Server shall return "Not available" error code. This
 * applies to the case when the NetworkInfo Object is subscribed.
 * @mandatory, @readable, @version 1.0, @uid 0xa57409fb
 */
OBJECT NetworkStatus {
    /** Current network type being used.
    * Allowed values defined in ENUM<networkTypes>.
    * @uid 0x4de85dff
    */
    ENUM<networkTypes> supportedNetworkType;
    /** High-level status information of the active network.
    * Allowed values defined in ENUM<connectivityStatusValues>
    * @uid 0x7a16876e
    */
    ENUM<connectivityStatusValues> connectivityStatus;
    /** Signal strength of the active network.
    * Allowed values defined in ENUM<signalStrengthValues>
    * @uid 0xac3c518e
    */
    ENUM<signalStrengthValues> signalStrength;
};
/** DataBalanceStatus Object carrying current data balance status of
 * Access Point
 * @optional, @readable, @uid 0xae17bc3f
 */
OBJECT DataBalanceStatus {
    /** Roaming status of Access Point.
    * - True: Access Point is in roaming mode.
    * - False: Access Point is not in roaming mode
    * @uid 0x8b23237c

```

```

*/
BOOLEAN dataRoamingStatus;
/** Mobile data limit. The unit is Byte.
 * A zero value indicates mobile data is unlimited.
 * @uid 0xfcc18cca
 */
LONG mobileDataLimit;
/** Amount of mobile data used during the data usage cycle.
 * The unit is Byte.
 * @uid 0x2b6a50b0
 */
LONG mobileDataUsage;
};
};

```

5 SBP Binding

The Network Information Data Services uses the following objects and their access capabilities.

Table 1

Object Name	Access Type	Subscription Type
NetworkSupport	READABLE	
NetworkStatus	READABLE	ON_CHANGE, AUTO
DataBalanceStatus	READABLE	

The data sink should first Get *NetworkSupport* Object, and then it should subscribe *NetworkStatus* Object. The data source shall not provide *DataBalanceStatus* Object if required information is not available or not accurate. For instance, data balance or data usage information is valid only if a user inputs a billing cycle of the data plan on the Server device.

Annex A (informative): Authors and Contributors

The following people have contributed to the present document:

Rapporteur: Dr. Jörg Brakensiek, E-Qualus (for Car Connectivity Consortium LLC)

Other contributors: Mingoo Kim, LG Electronics

Jungwoo Kim, LG Electronics

History

Document history		
V1.3.0	October 2017	Publication
V1.3.1	October 2019	Publication