



EMTEL;
Testing - Conformance test specifications for
core elements for network independent access to
emergency services (NG112);
Part 2: Abstract Test Suite (ATS) and
Protocol Implementation eXtra Information for Testing (PIXIT)

Reference

RTS/EMTEL-00060-2

Keywordsconformance, emergency, emergency services,
interoperability, testing**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definition of terms, symbols and abbreviations.....	5
3.1 Terms.....	5
3.2 Symbols.....	6
3.3 Abbreviations	6
4 Abstract Test Method (ATM).....	6
4.1 Test Configuration.....	6
4.2 Test architecture	6
4.3 Ports and ASPs (Abstract Services Primitives)	7
4.3.1 Introduction.....	7
4.3.2 Primitives on httpPort	7
4.3.3 Primitives on SIP	7
5 Untestable Test Purposes.....	8
6 ATS conventions	8
6.1 Introduction	8
6.2 Testing conventions.....	8
6.2.1 Testing states	8
6.2.1.1 Initial state.....	8
6.2.1.2 Final state	8
6.3 Naming conventions.....	8
6.3.1 General guidelines	8
6.3.2 NG112 specific TTCN-3 naming conventions	9
6.3.3 Usage of Log statements.....	9
6.3.4 Test Case (TC) identifier	10
Annex A (normative): TTCN-3 modules.....	11
A.1 Online TTCN-3 modules.....	11
Annex B (normative): Parameters for Test Suite Configuration	12
B.1 IUT parameters.....	12
History	16

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Technical Specification (TS) has been produced by ETSI Special Committee Emergency Communications (EMTEL).

The present document is part 2 of a multi-part deliverable covering Conformance test specifications for core elements for network independent access to emergency services (NG112), as identified below:

Part 1: "Protocol Implementation Conformance Statement (PICS), Test Suite Structure and Test Purposes (TSS & TP)";

Part 2: "**Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)**".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document contains the Abstract Test Suite (ATS) for core elements for network independent access to emergency services (NG112) as defined in standards listed in clause 2.1 of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 103 650-1 (V1.2.1): "EMTEL; Testing - Conformance test specifications for core elements for network independent access to emergency services (NG112); Part 1: Protocol Implementation Conformance Statement (PICS), Test Suite Structure and Test Purposes (TSS & TP)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 9646-1 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [i.2] ISO/IEC 9646-2 (1994): "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 2: Abstract Test Suite specification".
- [i.3] ETSI ETS 300 406 (1995): "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [i.4] ETSI ES 201 873-1 (V4.5.1): "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 1: TTCN-3 Core Language".
-

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ISO/IEC 9646-1 [i.1], ISO/IEC 9646-2 [i.2] and ETSI ETS 300 406 [i.3] apply.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AML	Advanced Mobile Location
ASP	Abstract Services Primitives
ATM	Abstract Test Method
ATS	Abstract Test Suite
BCF	Border Control Function
ECRF	Emergency Call Routing Function
ESRP	Emergency Service Routing Proxy
IP	Internet Protocol
IUT	Implementation Under Test
LIS	Location Information Server
MTC	Main Test Component
NAPTR	Naming Authority Pointer
NG	Next Generation
PICS	Protocol Implementation Conformance Statement
PIXIT	Partial Protocol Implementation Extra Information for Testing
PSAP	Public Safety Answering Point
PTC	Parallel Test Component
SIP	Session Initiation Protocol
SIPP	Session Initiation Protocol packetize
SMS	Short Message Service
SRS	Spatial Reference System
SUT	System Under Test
TC	Test Case
TP	Test Purposes
TTCN	Testing and Test Control Notation
TTCN-3	Testing and Test Control Notation 3
UoM	Unit of Measure
URI	Uniform Resource Identifier
URN	Uniform Resource Name
XML	Extensible Markup Language
XSD	XML Schema Definition

4 Abstract Test Method (ATM)

4.1 Test Configuration

The test configurations as defined in ETSI TS 103 650-1 [1], clause 5, shall apply.

4.2 Test architecture

The present document implements the general TTCN-3 test architecture as shown in figure 1.

In single-component testcases, the MTC communicates with SUT over a port. In multi-component testcases, the MTC is used to synchronize the different PTCs. The PTCs communicate with the SUT over ports.

The Upper tester entity in the SUT enables triggering functionalities by simulating primitives from application.




Figure 1: Test system architecture

4.3 Ports and ASPs (Abstract Services Primitives)

4.3.1 Introduction

Two ports are used by the NG112 test suite:

- The httpPort, of type HttpPort
- The SIPP port of type SipPort

4.3.2 Primitives on httpPort

One type of primitives is used in the httpPort:

- HttpMessage type which can be either a Request message or a Response message

4.3.3 Primitives on SIP

Several types of primitives are used in the SIP:

- Request type, which is a generic SIP request message type
- REGISTER_Request type, which is a REGISTER SIP request message type
- INVITE_Request type, which is an INVITE SIP request message type
- OPTIONS_Request type, which is an OPTIONS SIP request message type
- INFO_Request type, which is an INFO SIP request message type
- BYE_Request type, which is a BYE SIP request message type
- CANCEL_Request type, which is a CANCEL SIP request message type
- NOTIFY_Request type, which is a NOTIFY SIP request message type
- SUBSCRIBE_Request type, which is a SUBSCRIBE SIP request message type
- Response type, which is a generic SIP response message type

5 Untestable Test Purposes

Not applicable.

6 ATS conventions

6.1 Introduction

The ATS conventions are intended to give a better understanding of the ATS but they also describe the conventions made for the development of the ATS. These conventions shall be considered during any later maintenance or further development of the ATS.

The ATS conventions contain two clauses, the testing conventions and the naming conventions. The testing conventions describe the functional structure of the ATS. The naming conventions describe the structure of the naming of all ATS elements.

To define the ATS, the guidelines of ETSI ETS 300 406 [i.3] were considered.

6.2 Testing conventions

6.2.1 Testing states

6.2.1.1 Initial state

All test cases start with the function `f_prInitialState`. This function brings the IUT in an "initialized" state by invoking the upper tester primitive `UtInitialize`.

6.2.1.2 Final state

All test cases end with the function `f_poDefault`. This function brings the IUT back in an "idle" state. As no specific actions are required for the idle state in the base standard, the function `f_poDefault` does not invoke any action.

As necessary, further actions may be included in the `f_poDefault` function.

6.3 Naming conventions

6.3.1 General guidelines

The naming convention is based on the following underlying principles:

- in most cases, identifiers should be prefixed with a short alphabetic string (specified in table 1) indicating the type of TTCN-3 element it represents;
- suffixes should not be used except in those specific cases identified in table 2;
- prefixes and suffixes should be separated from the body of the identifier with an underscore ("_");

EXAMPLE 1: `c_sixteen`, `t_wait`.

- only module names, data type names and module parameters should begin with an upper-case letter. All other names (i.e. the part of the identifier following the prefix) should begin with a lower-case letter;
- the start of second and subsequent words in an identifier should be indicated by capitalizing the first character. Underscores should not be used for this purpose.

EXAMPLE 2: `f_initialState`.

Table 1 specifies the naming guidelines for each element of the TTCN-3 language indicating the recommended prefix, suffixes (if any) and capitalization.

Table 1: ETSI TTCN-3 generic naming conventions

Language element	Naming convention	Prefix	Example identifier
Module	Use upper-case initial letter	none	NG112Templates
Group within a module	Use lower-case initial letter	none	messageGroup
Data type	Use upper-case initial letter	none	SetupContents
Message template	Use lower-case initial letter	m_	m_setupInit
Message template with wildcard or matching expression	Use lower-case initial letters	mw_	mw_anyUserReply
Signature template	Use lower-case initial letter	s_	s_callSignature
Port instance	Use lower-case initial letter	none	signallingPort
Test component instance	Use lower-case initial letter	none	userTerminal
Constant	Use lower-case initial letter	c_	c_maxRetransmission
Constant (defined within component type)	Use lower-case initial letter	cc_	cc_minDuration
External constant	Use lower-case initial letter	cx_	cx_macId
Function	Use lower-case initial letter	f_	f_authentication()
External function	Use lower-case initial letter	fx_	fx_calculateLength()
Altstep (incl. Default)	Use lower-case initial letter	a_	a_receiveSetup()
Test case	Use ETSI numbering	TC_	TC_COR_0009_47_ND
Variable (local)	Use lower-case initial letter	v_	v_macId
Variable (defined within a component type)	Use lower-case initial letters	vc_	vc_systemName
Timer (local)	Use lower-case initial letter	t_	t_wait
Timer (defined within a component)	Use lower-case initial letters	tc_	tc_authMin
Module parameters for PICS	Use all upper case letters	PICS_	PICS_DOOROPEN
Module parameters for other parameters	Use all upper case letters	PX_	PX_TESTER_STATION_ID
Formal Parameters	Use lower-case initial letter	p_	p_macId
Enumerated Values	Use lower-case initial letter	e_	e_syncOk

6.3.2 NG112 specific TTCN-3 naming conventions

Next to such general naming conventions, table 2 shows specific naming conventions that apply to the NG112 TTCN-3 test suite. The `<ng112_entity>` tag indicates the NG 112 entity: LIS, ESRP, ECRF, PSAP or BCF.

Table 2: NG112 specific TTCN-3 naming conventions

Language element	Naming convention	Identifier
Module containing the control part	Use upper-case initial letter	Ats<ng112_entity>_TestControl
Module containing test cases	Use upper-case initial letter	Ats<ng112_entity>_TestCases
Module containing types and values	Use upper-case initial letter	Ats<ng112_entity>_TypesAndValues
Module containing Templates	Use upper-case initial letter	Ats<ng112_entity>_Templates
Module containing functions	Use upper-case initial letter	Ats<ng112_entity>_Functions
Module containing external functions	Use upper-case initial letter	Ats<ng112_entity>_ExternalFunctions
Module containing components, ports and message definitions	Use upper-case initial letter	Ats<ng112_entity>_Interface
Module containing main component definitions	Use upper-case initial letter	Ats<ng112_entity>_TestSystem

6.3.3 Usage of Log statements

All TTCN-3 log statements use the following format using the same order:

- Three asterisks.
- The TTCN-3 test case or function identifier in which the log statement is defined.

- One of the categories of log: INFO, WARNING, ERROR, PASS, FAIL, INCONC, TIMEOUT.
- Free text.
- Three asterisks.

EXAMPLE 1:

```
log("*** TC_XX: INFO: Preamble: Received and answered Location Service Request ***");
```

Furthermore, the following rules are applied:

- Log statements are used in the body of the functions, so that invocation of functions are visible in the test logs.
- All TTCN-3 setverdict statement are combined (as defined in TTCN-3 as defined in ETSI ES 201 873-1 [i.4]) with a log statement following the same above rules (see example 2).

EXAMPLE 2:

```
setverdict(pass, "*** TC_XX: PASS: Header correctly formatted ***");
```

6.3.4 Test Case (TC) identifier

The test case naming convention shall follow the same naming convention as defined in ETSI TS 103 650-1 [1], clause 7.1.2.

EXAMPLE: TP identifier: TP_ESRP_FIND_SERVICE_BV_01
 TC identifier: TC_ESRP_FIND_SERVICE_BV_01

Annex A (normative): TTCN-3 modules

A.1 Online TTCN-3 modules

This test suite has been produced using the Testing and Test Control Notation (TTCN) according to ETSI ES 201 873-1 [i.4].

The TTCN-3 library modules, which form parts of the present document, are contained in the following repository:
<https://forge.etsi.org/rep/emtel/NG112/-/releases/V1.2.1>.

Annex B (normative): Parameters for Test Suite Configuration

B.1 IUT parameters

Table B.1: IUT parameters

Identifier	Description	
PX_DEVICE_URI_SIP	Comment	Devie SIP URI
	Type	Charstring
	Def. value	""
PX_DEVICE_NUMBER	Comment	Device <tel> number
	Type	DeviceURIs
	Def. value	{}
PX_DEVICE_NUMBER_POINT	Comment	Device <tel> number, Point configuration
	Type	Integer
	Def. value	0
PX_DEVICE_NUMBER_CIRCLE	Comment	Device <tel> number, Circle configuration
	Type	Integer
	Def. value	1
PX_DEVICE_NUMBER_CIVIC	Comment	Device <tel> number, Circle configuration
	Type	Integer
	Def. value	2
PX_UNKNOWN_DEVICE_NUMBER	Comment	Unknown device <tel> number
	Type	Integer
	Def. value	3
PX_UNKNOWN_DEVICE_URI	Comment	Unknown device URI
	Type	Charstring
	Def. value	""
PX_AML_MOBILE_NUMBER	Comment	Number of the mobile used for sending SMS
	Type	Charstring
	Def. value	"0043123456789"
PX_AML_LIS_ENDPOINT_NUMBER	Comment	Number of the IUT to receive SMS
	Type	Charstring
	Def. value	"0043987654321"
PX_AML_MESSAGE	Comment	The AML Message to be send
	Type	Charstring
	Def. value	"A\ML=1;lt=+54.76397;lg=-0.18305;rd=50;top=20130717141935;lc=90;pm=W;si=123456789012345;ei=1234567890123456;mcc=234;mnc=30;ml=128"
PX_DEVICE_NUMBER_POINT_POS	Comment	Device <tel> number, Circle configuration
	Type	XSD.DoubleList
	Def. value	{ 43.616891, 7.053179 }
PX_CIRCLE_POS	Comment	Circle position
	Type	XSD.DoubleList
	Def. value	{ 43.617174, 7.052750 }
PX_CIRCLE_UOM	Comment	Circle UOM
	Type	XSD.AnyURI
	Def. value	"urn:ogc:def:uom:EPSG::9001"
PX_CIRCLE_RADIUS	Comment	Circle radius
	Type	XSD.double
	Def. value	15.00
PX_SRS_NAME	Comment	Circle SRS
	Type	XSD.AnyURI
	Def. value	"urn:ogc:def:crs:EPSG::4326"

Identifier	Description	
PX_POINT_IN_E_POLICE_SERVICE_BOUNDARY	Comment	Point in Police service boundary
	Type	XSD.DoubleList
	Def. value	{ 43.62023, 7.071032 }
PX_CIRCLE_IN_V_POLICE_SERVICE_BOUNDARY_POS	Comment	Point in Police service boundary
	Type	XSD.DoubleList
	Def. value	{ 43.617174, 7.052750 }
PX_CIRCLE_IN_V_POLICE_SERVICE_BOUNDARY_RADIUS	Comment	Radius in Police service boundary
	Type	XSD.Double
	Def. value	2.00
PX_LOST_EXPIRES	Comment	Expiry time
	Type	XSD.DateTime
	Def. value	"2019-08-30T08:48:17+00:00"
PX_LOST_LAST_UPDATED	Comment	Last update time
	Type	XSD.DateTime
	Def. value	"2018-08-30T08:48:17+00:00"
PX_E_UNKNOWN_SERVICE_URN	Comment	Unknown URN
	Type	XSD.AnyURI
	Def. value	"urn:service:sos.unknown"
PX_ECRF_SOURCE	Comment	The ECRF Identifier
	Type	Charstring
	Def. value	"ecrf1.etsi.plugtests.net"
PX_ECRF_VIA	Comment	Should be the same as the Source
	Type	Charstring
	Def. value	"ecrf1.etsi.plugtests.net"
PX_ECRF_NAPTR	Comment	Should be the same as the Source
	Type	Charstring
	Def. value	"ecrf1.etsi.plugtests.net"
PX_CONFIGURED_SERVICE	Comment	Services configured for the ECRF
	Type	StringSet
	Def. value	{ "urn:service:sos", "urn:service:sos.ambulance", "urn:service:sos.fire", "urn:service:sos.police" }
PX_REDIRECT_TARGET	Comment	The target to redirect to
	Type	Charstring
	Def. value	"other.ecrf.plugtests.net"
PX_INVALID_REQUEST	Comment	An invalid request to be sent
	Type	Charstring
	Def. value	"<?xml version='1.0' encoding='UTF-8'?><invalid>xml"
PX_G1	Comment	Polygon Basis containing multiple geometries
	Type	DoubleList
	Def. value	{.....}
PX_G2	Comment	Polygon Basis containing multiple geometries
	Type	DoubleList
	Def. value	{.....}
PX_G3	Comment	Polygon Basis containing multiple geometries
	Type	DoubleList
	Def. value	{.....}
PX_POINT_IN_G1	Comment	Point in PX_G1
	Type	DoubleList
	Def. value	
PX_CIRCLE_IN_G1	Comment	Circle in PX_G1
	Type	Circle
	Def. value	
PX_CIRCLE_INTERSECT_ONLY_G1	Comment	Circle only intersecting PX_G1
	Type	Circle
	Def. value	

Identifier	Description	
PX_CIRCLE_INTERSECT_MAINLY_G1_AND_G2	Comment	Circle intersecting PX_G1 and PX_G2, but mainly PX_G1
	Type	Circle
	Def. value	
PX_ELLIPSE_IN_G1	Comment	Ellipse in PX_G1
	Type	Ellipse
	Def. value	
PX_ARCBAND_IN_G1	Comment	Arband in PX_G1
	Type	Arcband
	Def. value	
PX_POLYGON_IN_G1	Comment	Polygon in PX_G1
	Type	Polygon
	Def. value	
PX_POINT_IN_G3	Comment	Point in PX_G3
	Type	Point
	Def. value	
PX_ESRP_DEQUEUE_REGISTRATION_QUEUE	Comment	Queue for Dequeue Registration
	Type	Charstring
	Def. value	"sip:queue@esinet.io"
PX_ESRP_DEQUEUE_REGISTRATION_QUEUE_INVALID	Comment	Invalid Queue Name for Dequeue Registration
	Type	Charstring
	Def. value	"not-a-queue"
PX_ESRP_DEQUEUE_REGISTRATION_DEQUEUER	Comment	The endpoint of the Dequeuer
	Type	Charstring
	Def. value	"sip:127.0.0.1:5080@esinet.io"
PX_ESRP_DEQUEUE_REGISTRATION_EXPIRATION	Comment	The Dequeue Registration Expiration
	Type	Integer
	Def. value	3600
PX_ESRP_DEQUEUE_REGISTRATION_PREFERENCE	Comment	The Dequeue Registration Preference
	Type	Integer
	Def. value	5
PX_REDIRECT_TARGET	Comment	The NAPTR Record resolving to the ATS
	Type	XSD.String
	Def. value	"ecrf2.testcomponent.esinet.io"
PX_PSAP_SERVICE_URN	Comment	Police URN
	Type	XSD.AnyURI
	Def. value	"urn:service:sos.police"
PX_PSAP_GEOLOCATION	Comment	
	Type	
	Def. value	
PX_PSAP_CALL_INFO	Comment	SIP Call-Info header
	Type	
	Def. value	
PX_PSAP_DQ_SIP_URL	Comment	URI to ESRP Dequeue Registration web service
	Type	Charstring
	Def. value	
PX_PSAP_DQR_SIP_URL	Comment	SIP URI of dequeuer (where to send calls)
	Type	Charstring
	Def. value	
PX_PSAP_DQ_EXPIRY_TIME	Comment	Requested time in seconds this registration will expire
	Type	Integer
	Def. value	3600
PX_BCF_SERVICE_URN	Comment	Police URN
	Type	XSD.AnyURI
	Def. value	"urn:service:sos.police"

Identifier	Description	
PX_IMS_SUT_BCF_IPADDR	Comment	BCF IP address
	Type	Charstring
	Def. value	"127.0.0.1"
PX_IMS_SUT_BCF_HOME_DOMAIN	Comment	BCF domain address
	Type	Charstring
	Def. value	"bcf22.sut.net"
PX_IMS_SUT_BCF_PORT	Comment	BCF port number
	Type	Integer
	Def. value	5062
PX_BCF_CALL_INFO_INCIDENT_TRACKING_ID	Comment	Incident tracking id within Call-Info header
	Type	Charstring
	Def. value	"<urn:emergency:uid:incidentid:56..3f:bcf.at>"
PX_BCF_CALL_INFO_CALL_ID	Comment	Call id within Call-Info header
	Type	Charstring
	Def. value	"<urn:emergency:uid:callid:a56e556d871:bcf.at>"
PX_BCF_CALL_INFO_SOURCE_ID	Comment	Source id within Call-Info header
	Type	Charstring
	Def. value	"<urn:emergency:uid:sourceid:a7231gc42:bcf.com>"

History

Document history		
V1.1.1	January 2020	Publication
V1.2.1	August 2022	Publication