

ETSI TS 125 367 V9.5.0 (2011-01)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
Mobility procedures for Home Node B (HNB);
Overall description;
Stage 2
(3GPP TS 25.367 version 9.5.0 Release 9)**



Reference

RTS/TSGR-0225367v950

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM, **TIPHON**TM, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTETM is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM[®] and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	6
4 Overview	7
5 CSG Identification.....	8
6 CSG Selection	8
6.1 Manual CSG ID Selection.....	8
7 CSG Cell Reselection.....	8
7.1 Measurement Rules for CSG Cells.....	8
7.2 Reselection to CSG Cell.....	9
7.2.1 Criteria for Intra-frequency Cell Reselection.....	9
7.2.2 Criteria for Inter-frequency Cell Reselection.....	9
7.2.3 Criteria for Inter-RAT Cell Reselection.....	9
7.3 Reselection from CSG Cell	9
7.3.1 Criteria for Intra-frequency Cell Reselection.....	9
7.3.2 Criteria for Inter-frequency Cell Reselection.....	9
7.3.3 Criteria for Inter-RAT Cell Reselection.....	9
7.4 Reselection from CSG Cell to CSG Cell.....	9
7.5 Parameters for CSG Cell Reselection.....	9
8 CSG and Hybrid Cell Handover.....	10
8.1 Handover to CSG/Hybrid Cell	10
8.1.1 CSG/Hybrid Cell Intra-frequency Measurement Procedure	10
8.1.2 CSG/Hybrid Cell Inter-frequency/Inter-RAT Measurement Procedure	11
8.2 Handover from CSG Cell	12
8.3 Handover from CSG Cell to CSG Cell.....	12
9 Support of Hybrid Cells	12
9.1 Measurement Rules	12
9.2 Reselection	13
Annex B (informative): Void	14
Annex C (informative): Change history	15
History	16

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document provides a high level description of the mobility procedures applicable to Home NodeB support in the current Release. Where appropriate, the reasons behind the agreements are provided. Throughout this document, unless otherwise stated, the UE is assumed to be a current Release UE that supports the Closed Subscriber Group (CSG) feature, whether it is actually a member of a CSG or not. A UE that does not support the CSG feature is not required to support any of the procedures stated in this document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 25.304: "UE procedures in idle mode and procedures for cell reselection in connected mode".
- [3] 3GPP TS 25.331: "Radio Resource Control (RRC) protocol specification".
- [4] 3GPP TS 23.011: "Service accessibility".
- [5] 3GPP TS 22.220: "Service Requirements for Home NodeBs and Home eNodeBs".
- [6] 3GPP TS 25.467: "UTRAN architecture for 3G Home Node B (HNB)".
- [7] 3GPP TS 25.214: "Physical layer procedures (FDD)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

Acceptable Cell: A cell that satisfies certain conditions as specified [2]. A UE can always attempt emergency calls on an acceptable cell.

Allowed CSG Cell: A CSG cell on which a UE may normally camp if its CSG whitelist contains the cell's CSG Identity.

CSG whitelist: A list provided by NAS containing all the CSG Identities of the CSGs to which the subscriber belongs.

NOTE: This list is known as Allowed CSG List in Rel-8 Access Stratum specifications.

Available PLMN: A PLMN for which the UE has found at least one cell and read its PLMN identity.

Barred Cell: A cell a UE is not allowed to camp on.

Camped on a cell: UE has completed the cell selection/reselection process and has chosen a cell. The UE monitors system information and (in most cases) paging information.

Camped on any cell: UE is in idle mode and has completed the cell selection/reselection process and has chosen a cell irrespective of PLMN identity.

Closed Subscriber Group (CSG): A Closed Subscriber Group identifies subscribers of an operator who are permitted to access one or more cells of the PLMN but which have restricted access (CSG cells).

CSG Cell: A cell, part of the PLMN, broadcasting a CSG Indicator that is set to TRUE and a specific CSG identity. A CSG cell is accessible by the members of the closed subscriber group for that CSG identity.

CSG Identity (CSG ID): An identifier broadcast by a CSG/Hybrid cell or cells and used by the UE to facilitate access for authorised members of the associated Closed Subscriber Group.

DRX cycle: Individual time interval between monitoring Paging Occasion for a specific UE.

Equivalent PLMN list: List of PLMNs considered as equivalent by the UE for cell selection, cell reselection, MBSFN Cluster selection MBSFN Cluster reselection and handover according to the information provided by the NAS.

Home NodeB (HNB): A HNB is a customer-premises equipment that connects a 3GPP UE over UTRAN wireless air interface to a mobile operator's network using broadband IP backhaul.

HNB Name: The Home NodeB Name is a broadcast string in free text format that provides a human readable name for the Home NodeB CSG identity.

Home PLMN: A PLMN where the Mobile Country Code (MCC) and Mobile Network Code (MNC) of the PLMN identity are the same as the MCC and MNC of the IMSI.

Hybrid cell: A cell broadcasting a CSG identity which is accessible as a CSG cell by UEs which are members of the CSG and as a normal cell by all other UEs.

Non-CSG Cell: A cell that is not a CSG cell, e.g. a macro cell.

Process: A local action in the UE invoked by a RRC procedure or an Idle Mode procedure.

Radio Access Mode: Radio access mode of the cell, FDD or TDD.

Radio Access Technology: Type of technology used for radio access, for instance UTRA or GSM.

Registered PLMN: This is the PLMN on which certain Location Registration outcomes have occurred.

Registration Area: (NAS) registration area is an area in which the UE may roam without a need to perform location registration, which is a NAS procedure.

Reserved Cell: A cell on which camping is not allowed, except for particular UEs, if so indicated in the system information.

Restricted Cell: A cell on which camping is allowed, but access attempts are disallowed for UEs whose access classes are indicated as barred.

Selected PLMN: This is the PLMN that has been selected by the NAS, either manually or automatically.

Serving cell: The cell on which the UE is camped.

Strongest cell: The cell on a particular carrier that is considered strongest according to the layer 1 cell search procedure [7]. As the details of the layer 1 cell search are implementation dependent, the precise definition of 'strongest cell' is also implementation dependent.

Suitable Cell: This is a cell on which an UE may camp.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AS Access Stratum

BCCH	Broadcast Control Channel
CM	Connection Management
CN	Core Network
CSG	Closed Subscriber Group
DRX	Discontinuous Reception
E-UTRA	Evolved UMTS Terrestrial Radio Access
FDD	Frequency Division Duplex
GPRS	General Packet Radio Service
GSM	Global System for Mobile Communications
HCS	Hierarchical Cell Structure
HNB	Home NodeB
IMSI	International Mobile Subscriber Identity
MCC	Mobile Country Code
MM	Mobility Management
MNC	Mobile Network Code
NAS	Non-Access Stratum
PCH	Paging Channel
PI	Page Indicator
PICH	Page Indication Channel
PLMN	Public Land Mobile Network
RAT	Radio Access Technology
RRC	Radio Resource Control
SAP	Service Access Point
TDD	Time Division Duplex
TMGI	Temporary Mobile Group Identity
UE	User Equipment
UMTS	Universal Mobile Telecommunications System
UTRA	UMTS Terrestrial Radio Access
UTRAN	UMTS Terrestrial Radio Access Network

4 Overview

A Home NodeB may provide restricted access to only UEs belonging to a Closed Subscriber Group (CSG). One or more of such cells providing restricted access, known as CSG cells, are identified by a unique numeric identifier called CSG Identity. To facilitate access control, a UE with CSG subscription would have an CSG whitelist, which contains one or more CSG Identities associated with the CSG cells on which the UE is allowed access. The UE uses the CSG whitelist along with the CSG Identity broadcast by the CSG Cells in CSG cell selection and reselection.

A HNB can also be operated as a hybrid cell. A hybrid cell is accessed as a CSG cell by a UE whose CSG whitelist contains the cell's CSG ID and as a normal cell by all other UEs. Members of the CSG are expected to receive preferential access according to [5].

NOTE: Although pre-Rel-9 UEs are able to camp on hybrid cells (which would be regarded as normal cells for access) there is no possibility for these UEs to identify a hybrid cell as a CSG cell even though the cell's CSG identity is in the UE's CSG whitelist.

In addition, manual selection of CSG Identity is introduced, which enables the human user to manually select a CSG Identity for UE to camp on.

This document provides high level descriptions and procedures of the mobility features to support CSG deployment in the current Release. The following areas will be covered in the subsequent chapters:

- Identifiers associated with the CSG framework
- Manual selection of CSG Identity
- Measurement rules for CSG Cells
- Cell reselection to a CSG cell, from a CSG cell, and between CSG cells
- Handover to a CSG cell, from a CSG cell, and between CSG cells, where applicable

- Measurement rules, (re)selection and handover procedures for hybrid cells.

5 CSG Identification

One or more Closed Subscriber Group (CSG) cells are identified by a unique numeric identifier called CSG Identity or CSG ID. A UE belonging to a CSG has the corresponding CSG ID in its CSG whitelist. The CSG whitelist is maintained and provided by NAS. The CSG ID is broadcast in system information by the CSG cell or hybrid cell, and used by the UE for cell (re)selection and handover purposes.

A cell may optionally broadcast the CSG Indicator, whose presence and value of TRUE indicates the cell is a CSG cell. The absence of the CSG indicator in a cell which broadcasts a CSG identity indicates that it is a hybrid cell.

A CSG cell or hybrid cell may broadcast the HNB Name, a textual identifier, in system information. The HNB Name can be used to aid the human user in manual selection of a CSG ID.

At the physical layer, a CSG cell is identified by its carrier frequency (UARFCN) and Primary Scrambling Code (PSC). A set of PSCs could be reserved for CSG deployment and this reserved PSC range may be signalled in system information. The PSC of a CSG cell belongs to the reserved PSC range if broadcast.

On the mixed carrier frequency shared by both non-CSG cells (UMTS macro cells) and CSG cells, CSG cells broadcast in system information the PSC range reserved by the network for CSG cells. The non-CSG cells may also broadcast the reserved PSC range. The reserved PSC range is only applicable to the UARFCN within the PLMN where the UE received this information. The UE considers the last received reserved PSC range to be valid within the entire PLMN for the duration of 24 hours. The UE may use the reserved PSC information for CSG cell search and (re)selection purposes, according to UE's implementation.

Non-CSG cells and CSG cells may broadcast indications of one or more carrier frequencies used for dedicated CSG deployment. This information may be used by a UE to avoid unnecessary measurements on that frequency even when cell measurement rules would require measurements of this carrier frequency. Indications of which carrier frequencies are dedicated to CSG-only deployment may be signalled in system information and are applicable only in the cell where this information is broadcast.

6 CSG Selection

6.1 Manual CSG ID Selection

Manual CSG ID selection enables a human user to select a CSG ID. In manual CSG ID selection the UE may scan all frequencies in the supported frequency bands and display a list of found CSG IDs or the corresponding HNB Names if broadcast by the CSG cells or hybrid cells, and indications as to whether the found CSG IDs are contained in the UE's CSG whitelist. When the user selects an entry in the list, the UE selects any CSG cell or hybrid cell among the ones with same CSG ID. The UE may normally camp on the chosen cell if it is an allowed CSG cell or a hybrid cell.

During manual CSG ID selection a UE is allowed to perform Location Registration procedure on a CSG cell whose CSG ID is not in the CSG whitelist.

Based on the outcome of a Location Registration procedure initiated on a CSG cell, the UE's CSG whitelist is updated.

The UE is allowed to *not* support manual CSG ID selection in connected mode.

7 CSG Cell Reselection

7.1 Measurement Rules for CSG Cells

To measure allowed CSG cell(s), a UE applies an autonomous search function, per UE implementation, regardless of which RAT the UE is camping on. The autonomous search function determines when and where to search for the allowed CSG cells.

Autonomous search procedure is disabled by the search function if UE's CSG whitelist does not exist or is empty.

On a mixed carrier, a UE may avoid measurements of any CSG cells that are known by the UE to be not allowed.

A UE may avoid measurements of any CSG cells that are known by the UE to be not allowed on the carrier frequency dedicated to CSG deployment.

7.2 Reselection to CSG Cell

The cell reselection criteria described in this section is applicable when the UE is in the following call states: Idle Mode, Cell_PCH and URA_PCH states, but not Cell_FACH, unless otherwise stated.

7.2.1 Criteria for Intra-frequency Cell Reselection

For intra-frequency reselection from a non-CSG cell to an allowed CSG cell, the UE follows the same cell ranking rules as those defined for the UTRA case in [2]. The UE may ignore not allowed CSG cells in the ranking. The UE applies reselection parameters broadcast by the serving cell. A UE may normally camp on an allowed CSG cell.

7.2.2 Criteria for Inter-frequency Cell Reselection

For inter-frequency cell reselection, the UE considers the frequency where its allowed CSG cell is on to have the highest priority value, irrespective of network configured frequency priorities, as long as the allowed CSG cell remains best ranked on that frequency.

7.2.3 Criteria for Inter-RAT Cell Reselection

Inter-RAT reselection to an allowed CSG cell is supported when the UE is camped on another RAT. The UE requirements are defined in the specifications of the concerned RAT.

7.3 Reselection from CSG Cell

7.3.1 Criteria for Intra-frequency Cell Reselection

For intra-frequency reselection from an allowed CSG cell to a non-CSG cell, the UE follows the same cell ranking rules as those defined for the UTRA case defined in [2].

7.3.2 Criteria for Inter-frequency Cell Reselection

For inter-frequency reselection from an allowed CSG cell to a non-CSG cell, the UE follows the same cell ranking rules as those defined for the UTRA case defined in [2].

7.3.3 Criteria for Inter-RAT Cell Reselection

For reselection from a CSG cell to a GSM or E-UTRA cell, the UE follows the respective procedures defined in [2].

7.4 Reselection from CSG Cell to CSG Cell

For reselection between allowed CSG cells, the UE follows the same cell ranking rules as those defined for the UTRA case in [2].

7.5 Parameters for CSG Cell Reselection

No new parameters are defined for CSG cell ranking. The same cell reselection parameters defined for the UTRA case in [2] are used for CSG cell ranking purposes, if configured. The operator may configure the cell reselection parameters, such as Qoffset and Qhyst, to bias the reselection of CSG cells.

8 CSG and Hybrid Cell Handover

8.1 Handover to CSG/Hybrid Cell

Handover to a HNB/HeNB follows the framework as specified in [3], [6]. Handover to a HNB/HeNB is different from the normal handover procedure in three aspects:

1. **Proximity Estimation:** in case the UE is able to determine, based on UE implementation, that it is near a CSG or hybrid cell whose CSG ID is in the UE's CSG whitelist, the UE may provide to the SRNC an indication of proximity. The CSG proximity indication may be used as follows:
 - a. If a measurement configuration is not present for the concerned frequency/RAT, the SRNC may configure the UE to perform measurements and reporting for the concerned frequency/RAT.
 - b. The SRNC may determine whether to perform other actions related to handover to HNB/HeNBs based on having received a proximity indication (for example, the SRNC may not configure compressed mode gaps for the UE to detect the HNB/HeNB on a different frequency/RAT unless it has received a proximity indication).
2. **PSC/PCI Confusion:** due to the typical cell size of HNB/HeNBs being much smaller than macro cells, there can be multiple HNBs/HeNBs within the coverage of the SRNC that have the same PSC/PCI. This leads to a condition referred to as PSC/PCI confusion, wherein the SRNC is unable to determine the correct target cell for handover from the PSC/PCI included in the measurement reports from the UE. PSC/PCI confusion is solved by the UE reporting the cell identity of the target HNB/HeNB.
3. **Access Control:** If the target cell is a hybrid cell, prioritization of allocated resources may be performed based on the UE's membership status. Access control is done by a two step process, where first the UE reports the membership status based on the CSG ID received from the target cell and the UE's CSG whitelist, and then the network verifies the reported status.

Mobility from SRNC to a CSG/hybrid cell from network perspective is described in [6]. The following two sections describe the radio aspects. The SRNC in the call flows of these sections can be an RNC or a HNB.

8.1.1 CSG/Hybrid Cell Intra-frequency Measurement Procedure




Figure 8.1.1-1: Intra-frequency Measurement Procedure of CSG and Hybrid cells

- 1) The SRNC configures the UE with a measurement having "CSG Proximity detection" as measurement type.
- 2) The UE sends an "entering" CSG proximity indication when it determines it may be near a cell, (based on UE implementation) whose CSG ID is in the UE's CSG whitelist.
- 3) If a measurement configuration for CSG/hybrid cells is not present, the SRNC configures the UE with relevant measurement configuration which includes the PSCs that the UE must measure and the PSCs for which SI acquisition should be performed. The network may use the CSG proximity indication for intra-frequency case to minimize the time during which measurements for CSG/hybrid cells are configured.
- 4) The UE sends a measurement report including the measured PSC, Cell Identity, CSG ID and CSG membership indication of the target HNB to the SRNC (e.g., due to a triggered intra-frequency event 1d). The UE can acquire MIB and SIB3/SIB4 of intra-frequency target HNB cells in parallel with reception of the serving cell transmissions in CELL_DCH. No measurement gaps are required for reading MIB and SIB3/SIB4.
- 5) SRNC can then proceed with the handover processing as described in [6].

After sending an "entering" CSG proximity indication (step 2), if the UE determines that it is no longer near any cell (on the reported proximate RAT and frequency) whose CSG ID is in the UE's CSG whitelist, the UE sends a 'leaving' CSG proximity indication to the SRNC. Upon reception of this indication, the SRNC may reconfigure the UE to stop measurements configured.

The PSC confusion is resolved by steps 3 and 4. The SRNC can request SI acquisition and reporting for any PSC, not limited to PSCs of CSG or hybrid cells.

8.1.2 CSG/Hybrid Cell Inter-frequency/Inter-RAT Measurement Procedure




Figure 8.1.2-1: Inter-frequency Measurement Procedure of CSG and Hybrid cells.

- 1) The SRNC configures the UE with a measurement having "CSG Proximity detection" as measurement type.
- 2) The UE sends an "entering" CSG proximity indication when it determines it may be near a cell, (based on UE implementation) whose CSG ID is in the UE's CSG whitelist. The CSG proximity indication includes the RAT and frequency of the cell.
- 3) The SRNC configures a measurement on the concerned frequency/RAT to measure CSG/hybrid cells. Compressed mode gaps, if required by the UE, are also activated to allow UE to perform measurements on the reported RAT and frequency. The network may also use the proximity indication to minimize the requesting of handover preparation information of CSG/hybrid cells by avoiding requesting such information when the UE is not in the geographical area where cells whose CSG IDs are in the UEs CSG whitelist are located.
- 4) The UE sends a measurement report including the measured PSCs/PCIs.
- 5) The SRNC configures the UE to perform SI acquisition and reporting of a particular PSC/PCI.
- 6) The UE performs SI acquisition using autonomous gaps, i.e., the UE may suspend reception and transmission with the SRNC to acquire the relevant system information from the target HNB/HeNB.
- 7) The UE sends a measurement report including Cell Identity, CSG ID and CSG membership indication.
- 8) SRNC can then proceed with the handover processing. The handover processing for inter-frequency handover to a CSG/Hybrid cell is described in [6].

NOTE: The above steps also apply to inter-RAT mobility from UMTS cell to HeNB.

After sending an "entering" CSG proximity indication (step 2), if the UE determines that it is no longer near any cell (on the reported proximate RAT and frequency) whose CSG ID is in the UE's CSG whitelist, the UE sends a "leaving" CSG proximity indication to the SRNC. Upon reception of this indication, the SRNC may reconfigure the UE to stop measurements on the reported RAT and frequency.

In the above procedure, step 2 may not be performed in case the UE has not previously visited the HNB, e.g., when the UE first visits a CSG/hybrid cell.

The PSC/PCI confusion is resolved by steps 5, 6 and 7. The SRNC can request SI acquisition and reporting for any PSC/PCI, not limited to PSCs/PCIs of CSG or hybrid cells.

8.2 Handover from CSG Cell

In Cell_DCH state, the handover procedure from an allowed CSG cell to a non-CSG cell is expected to be the same as the procedure specified in [3].

8.3 Handover from CSG Cell to CSG Cell

In Cell_DCH state, handover between allowed CSG cells with the same CSG ID is expected to be the same as the procedure specified in Section 8.1.

In Cell_DCH state, handover between allowed CSG cells with different CSG IDs is expected to be the same as the procedure specified in Section 8.1.

9 Support of Hybrid Cells

9.1 Measurement Rules

To measure for hybrid cells with a CSG Identity belonging to an entry in the UE's CSG whitelist, measurement rules of Chapter 7.1 apply. Otherwise, normal measurement rules apply.

NOTE: The autonomous search for hybrid cells does not imply that UE need to constantly check the CSG ID of all cells it sees.

9.2 Reselection

In case the UE has CSG ID of the hybrid cell in its CSG whitelist, cell reselection procedures will be the same as for a CSG cell as described in Chapter 7.2.

For all other UEs, cell reselection procedures will utilise normal cell reselection rules.

Annex B (informative):
Void

Annex C (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Re v	Subject/Comment	Old	New
2008-11-17	RAN2#64				Proposal for 25.367 TS structure and Text Proposals	-	0.0.0
2008-11-20	RAN2#64				Revision based on discussion for email agreement.	-	0.0.1
2008-11-21	RAN2#64				Final text proposals for email agreement.	-	0.0.2
2008-11-25	RAN2#64				Revision based on email agreement.	-	1.0.0
2008-12	RP-42	RP-080873	-	-	v1.0.0 was approved at RAN #42 as v8.0.0 and put under CR control	1.0.0	8.0.0
2009-03	RP-43	RP-090135	0001	1	Corrections to manual CSG search	8.0.0	8.1.0
	RP-43	RP-090135	0002	1	Alignment to latest stage 3 agreements	8.0.0	8.1.0
2009-06	RP-44	RP-090524	0003	-	Idle mode requirements to support hybrid cells for HNB	8.1.0	9.0.0
2009-09	RP-45	RP-090930	0005	4	CR capturing HNB inbound mobility agreements	9.0.0	9.1.0
	RP-45	RP-090911	0008	-	Correction to manual CSG ID selection_25.367CR(R9)	9.0.0	9.1.0
2009-12	RP-46	RP-091343	0010	1	CR on Add Hybrid cell into the manual CSG ID selection in 25.367	9.1.0	9.2.0
	RP-46	RP-091343	0011	2	Draft CR capturing HNB inbound mobility agreements	9.1.0	9.2.0
	RP-46	RP-091343	0012	-	Removal of description related to small repetition of SIB3/4	9.1.0	9.2.0
	RP-46	RP-091343	0014	1	Renaming Allowed CSG List (25.367 Rel-9)	9.1.0	9.2.0
	RP-46	RP-091330	0015	-	Correction to definition of CSG cell.	9.1.0	9.2.0
2010-03	RP-47	RP-100306	0017	-	CR capturing HNB inbound mobility agreements	9.2.0	9.3.0
2010-06	RP-48	RP-100551	0018	-	Some corrections to 25.367	9.3.0	9.4.0
2010-12	RP-50	RP-101206	0019	-	Correction to the limitation of SI acquisition	9.4.0	9.5.0

History

Document history		
V9.2.0	February 2010	Publication
V9.3.0	April 2010	Publication
V9.4.0	June 2010	Publication
V9.5.0	January 2011	Publication