

ETSI TS 128 663 V11.3.0 (2016-01)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Generic Radio Access Network (RAN)
Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.663 version 11.3.0 Release 11)**



ReferenceRTS/TSGS-0528663vb30

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Solution Set Definition.....	7
Annex A (normative): CORBA Solution Set	8
A.0 Introduction	8
A.1 Architectural features	8
A.1.0 General	8
A.1.1 Syntax for Distinguished Names	8
A.1.2 Rules for NRM extensions	8
A.1.2.1 Allowed extensions.....	8
A.1.2.2 Extensions not allowed	8
A.2 Mapping	9
A.2.1 General mapping	9
A.2.2 Information Object Class (IOC) mapping	9
A.2.2.1 IOC SectorEquipmentFunction.....	9
A.2.2.2 IOC AntennaFunction.....	9
A.2.2.3 IOC TmaFunction	10
A.2.2.4 IOC CommonBSFunction.....	11
A.2.2.5 IOC GSMCellPart.....	11
A.2.2.6 IOC RepeaterFunction	11
A.3 Solution Set definitions	12
A.3.1 IDL definition structure	12
A.3.2 IDL specification "GenericRanNRMDefs.idl"	12
A.3.3 IDL specification (file name "RepeaterNetworkResourcesNRMDefs.idl")	13
Annex B (normative): XML Definitions	15
B.1 Architectural features	15
B.1.1 Syntax for Distinguished Names	15
B.2 Mapping	15
B.2.1 General mapping.....	15
B.2.2 Information Object Class (IOC) mapping.....	15
B.3 Solution Set definitions	15
B.3.1 XML definition structure.....	15
B.3.2 Graphical Representation	16
B.3.3 XML schema "genericRanNrm.xsd"	16
B.3.4 XML schema (file name "repeaterNrm.xsd").....	19
Annex C (informative): Change history	21
History	22

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 28.661 Generic Radio Access Network (RAN) Network Resource Model (NRM); Integration Reference Point (IRP); Requirements
- 28.662 Generic Radio Access Network (RAN) Network Resource Model (NRM); Integration Reference Point (IRP); Information Service (IS)
- 28.663 **Generic Radio Access Network (RAN) Network Resource Model (NRM); Integration Reference Point (IRP); Solution Set (SS) definitions**

1 Scope

The present document is part of an Integration Reference Point (IRP) named Generic Radio Access Network (RAN) Network Resource Model (NRM) IRP, through which an IRPAgent can communicate configuration management information to one or several IRPManagers concerning Generic RAN resources. The Generic RAN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the Solution Sets for the Generic RAN NRM IRP.

This Solution Set specification is related to 3GPP TS 28.662 V11. 1.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.153: "Telecommunication management; Integration Reference Point (IRP) technology specific templates, rules and guidelines".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 28.662: "Generic Radio Access Network (RAN) Network Resource Model (NRM); Integration Reference Point (IRP); Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] 3GPP TS 32.606: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [7] 3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [8] W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
- [9] Void.
- [10] W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures.
- [11] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
- [12] W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".
- [13] 3GPP TS 28.623: "Generic network resources Integration Reference Point (IRP); Solution Set (SS) definition".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 32.600 [3] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

XML file: See definition of [13].

XML document: See definition of [13].

XML declaration: See definition of [13].

XML element: See definition of [13].

empty XML element: See definition of [13].

XML content (of an XML element): See definition of [13].

XML start-tag: See definition of [13].

XML end-tag: See definition of [13].

XML empty-element tag: See definition of [13].

XML attribute specification: See definition of [13].

DTD: See definition of [13].

XML schema: See definition of [13].

XML namespace: See definition of [13].

XML complex type: See definition of [13].

XML element type: See definition of [13].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 32.600 [3], and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

BS	Base Station
CM	Configuration Management
CORBA	Common Object Request Broker Architecture
DTD	Document Type Definition
GSM	Global System for Mobile communication
IDL	Interface Definition Language (OMG)
IOC	Information Object Class
IRP	Integration Reference Point
IS	Information Service
MO	Managed Object
MOC	Managed Object Class
NRM	Network Resource Model
OMG	Object Management Group
RAN	Radio Access Network
SS	Solution Set
UMTS	Universal Mobile Telecommunications System
XML	eXtensible Markup Language

4 Solution Set Definition

This specification defines the following 3GPP Generic RAN NRM IRP Solution Set Definitions:

- 3GPP Generic RAN NRM IRP CORBA SS (Annex A).
- 3GPP Generic RAN NRM IRP XML Definitions (Annex B).

Annex A (normative): CORBA Solution Set

A.0 Introduction

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in Generic RAN NRM IRP: Information Service (TS 28.662 [4]).

A.1 Architectural features

A.1.0 General

The overall architectural feature of Generic RAN Network Resources IRP is specified in 3GPP TS 28.662 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

See clause A.1.1 of [13].

A.1.2 Rules for NRM extensions

See clause A.1.2 of [13].

A.1.2.1 Allowed extensions

See clause A.2.1 of [13].

A.1.2.2 Extensions not allowed

See clause A.2.1 of [13].

A.2 Mapping

A.2.1 General mapping

See clause A.2.1 of [13].

A.2.2 Information Object Class (IOC) mapping

A.2.2.1 IOC SectorEquipmentFunction

Mapping from NRM IOC SectorEquipmentFunction attributes and associations to SS equivalent MOC SectorEquipmentFunction attributes

IS Attribute	SS Attribute	SS Type
id	id	string
fqBand	fqBand	short
confOutputPower	confOutputPower	short
relatedTmaList	relatedTmaList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet
relatedAntennaList	relatedAntennaList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet
relatedCellList	relatedCellList	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReferenceSet

A.2.2.2 IOC AntennaFunction

Mapping from NRM IOC AntennaFunction attributes and associations to SS equivalent MOC AntennaFunction attributes

IS Attribute	SS Attribute	SS Type
id	id	string
retTiltValue	retTiltValue	short
bearing	bearing	short
retGroupName	retGroupName	string
height	height	short
maxAzimuthValue	maxAzimuthValue	short
minAzimuthValue	minAzimuthValue	short
horizBeamwidth	horizBeamwidth	short

IS Attribute	SS Attribute	SS Type
vertBeamwidth	vertBeamwidth	short
relatedCellList	relatedCellList	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet

NOTE: For all support qualifiers with the value "O", see attribute constraints in TS 28.622 [4].

A.2.2.3 IOC TmaFunction

Mapping from NRM IOC TmaFunction attributes and associations to SS equivalent MOC TmaFunction attributes

IS Attribute	SS Attribute	SS Type
id	id	string
tmaSubunitNumber	tmaSubunitNumber	unsigned short
tmaStateFlag	tmaStateFlag	unsigned short
tmaFunctionFlag	tmaFunctionFlag	unsigned short
tmaMinGain	tmaMinGain	unsigned short
tmaMaxGain	tmaMaxGain	unsigned short
tmaResolution	tmaResolution	unsigned short
tmaGainFigure	tmaGainFigure	unsigned short
tmaNumberOfSubunits	tmaNumber OfSubunits	unsigned short
tmaBaseStationId	tmaBaseStationId	string
tmaSectorId	tmaSectorId	string
tmaAntennaBearing	tmaAntennaBearing	unsigned short
tmaInstalledMechanicalTilt	tmaInstalledMechanicalTilt	short
tmaSubunitType	tmaSubunitType	unsigned short
tmaSubunitRxFrequencyBand	tmaSubunitRxFrequencyBand	sequence of unsigned short
tmaSubunitTxFrequencyBand	tmaSubunitTxFrequencyBand	sequence of unsigned short
tmaGainResolution	tmaGainResolution	unsigned short
relatedCellList	relatedCellList	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet

Editor's note: The attributes *tmaSubunitType*, *tmaSubunitRxFrequencyBand*, *tmaSubunitTxFrequencyBand*, *tmaGainResolution*, *tmaBaseStationId* and *tmaSectorId* are to be checked if they should be moved to inventory.

A.2.2.4 IOC CommonBSFunction

Mapping from NRM IOC CommonBSFunction attributes and associations to SS equivalent MOC CommonBSFunction attributes

IS Attribute	SS Attribute	SS Type
id	id	string
sharedTechnologies	sharedTechnologies	short

A.2.2.5 IOC GSMCellPart

Mapping from NRM IOC GSMCellPart attributes and associations to SS equivalent MOC GSMCellPart attributes

IS Attribute	SS Attribute	SS Type
id	id	string
aRFCN	aRFCN	string
tsc	tsc	long
aTA	aTA	short
relatedSectorEquipment	relatedSectorEquipment	GenericNetworkResourcesIRPSystem:: AttributeTypes::MOReference

A.2.2.6 IOC RepeaterFunction

Mapping from NRM IOC RepeaterFunction attributes to SS equivalent MOC RepeaterFunction attributes

IS Attribute	SS Attribute	SS Type
id	repeaterFunctionId	string
userLabel	userLabel	string
priority	priority	long
latitude	latitude	float
longitude	longitude	float
ctrlConnMode	ctrlConnMode	ctrlConnMode
environmentInfo	environmentInfo	string
powerSwitch	powerSwitch	powerSwitch
ulAttenuation	ulAttenuation	long
dlAttenuation	dlAttenuation	long
firmwareVer	firmwareVer	string

IS Attribute	SS Attribute	SS Type
repeaterType	repeaterType	repeaterType
externalUTRANCell	repeaterFunctionExternalUtranCell	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clauses A.3.2 and A.3.3 define the MO classes for the Generic RAN NRM IRP.

A.3.2 IDL specification "GenericRanNRMDefs.idl"

```
//File:GenericRanNRMDefs.idl
#ifndef _GENERICRANNRMDEFS_IDL_
#define _GENERICRANNRMDEFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module GenericRanNRMDefs
{
    /**
    * Definitions for MO class AntennaFunction
    */
    interface AntennaFunction: GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS= "AntennaFunction";
        // Attribute Names
        //
        const string id = "id";
        const string retTiltValue = "retTiltValue";
        const string bearing = "bearing";
        const string retGroupName = "retGroupName";
        const string height = "height";
        const string maxAzimuthValue = "maxAzimuthValue";
        const string minAzimuthValue = "minAzimuthValue";
        const string horizBeamwidth = "horizBeamwidth";
        const string vertBeamwidth = "vertBeamwidth";
        const string relatedCellList= "relatedCellList";
    };

    /**
    * Definitions for MO class TmaFunction
    */
    interface TmaFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "TmaFunction";
        // Attribute Names
        //
        const string id = "id";
        const string tmaSubunitNumber = "tmaSubunitNumber";
        const string tmaStateFlag = "tmaStateFlag";
        const string tmaFunctionFlag = "tmaFunctionFlag";
        const string tmaMinGain = "tmaMinGain";
        const string tmaMaxGain = "tmaMaxGain";
        const string tmaResolution = "tmaResolution";
        const string tmaGainFigure = "tmaGainFigure";
        const string tmaNumberOfSubunits = "tmaNumberOfSubunits";
        const string tmaBaseStationId = "tmaBaseStationId";
        const string tmaSectorId = "tmaSectorId";
        const string tmaAntennaBearing = "tmaAntennaBearing";
        const string tmaInstalledMechanicalTilt = "tmaInstalledMechanicalTilt";
        const string tmaSubunitType = "tmaSubunitType";
    };
};
```

```

    const string tmaSubunitRxFrequencyBand = "tmaSubunitRxFrequencyBand";
    const string tmaSubunitTxFrequencyBand = "tmaSubunitTxFrequencyBand";
    const string tmaGainResolution = "tmaGainResolution";
    const string relatedCellList= "relatedCellList";
};

/*
 * Definitions for MO class SectorEquipmentFunction
 */
interface SectorEquipmentFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "SectorEquipmentFunction";
    // Attribute Names
    //
    const string id = "id";
    const string fqBand = "fqBand";
    const string confOutputPower = "confOutputPower";
    const string relatedTmaList = "relatedTmaList";
    const string relatedAntennaList = "relatedAntennaList";
    const string relatedCellList= "relatedCellList";
};

/*
 * Definitions for MO class CommonBSFunction
 */
interface CommonBSFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "CommonBSFunction";
    // Attribute Names
    //
    const string id= "id";
    const string sharedTechnologies = "sharedTechnologies";
};

/*
 * Definitions for MO class GSMCellPart
 */
interface GSMCellPart : GenericNetworkResourcesNRMDefs::ManagedFunction
{
    const string CLASS = "GSMCellPart";
    // Attribute Names
    //
    const string id= "id";
    const string aRFCN = "aRFCN";
    const string tsc = "tsc";
    const string aTA = "aTA";
    const string relatedSectorEquipment = "relatedSectorEquipment";
};
}
#endif // _GENERICRANNRMDEFS_IDL_

```

A.3.3 IDL specification (file name "RepeaterNetworkResourcesNRMDefs.idl")

```

//File:RepeaterNetworkResourcesNRMDefs.idl
#ifndef _REPEATERNETWORKRESOURCESNRMDEFS_IDL_
#define _REPEATERNETWORKRESOURCESNRMDEFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module RepeaterNetworkResourcesNRMDefs
{
    /**
     * Definitions for MO class RepeaterFunction
     */
    interface RepeaterFunction : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "RepeaterFunction";
        // Attribute Names
        //
    }
}

```

```
    const string repeaterFunctionId    = "repeaterFunctionId";
    const string priority               = "priority";
    const string latitude               = "latitude";
    const string longitude              = "longitude";
    const string ctrlConnMode          = "ctrlConnMode";
    const string environmentInfo       = "environmentInfo";
    const string powerSwitch           = "powerSwitch";
    const string dLAttenuation         = "dLAttenuation";
    const string uLAttenuation         = "uLAttenuation";
    const string firmwareVer           = "firmwareVer";
    const string repeaterType          = "repeaterType";
    const string repeaterFunctionExternalUtranCell = "repeaterFunctionExternalUtranCell";
};

enum ctrlConnMode
{
    GSM_SMS,
    WCDMA_SMS,
    CIRCLE_SWITCH_DATA_CSD,
    PACKAGE_SWITCH_DATA_IP,
    SERIAL_PORT
};

enum powerSwitch {ON,OFF};

enum repeaterType
{
    WIDE_BAND_REPT_FUNCTION,
    FREQ_SEL_REPT_FUNCTION,
    FIBER_REPT_FUNCTION,
    INDOOR_REPT_FUNCTION,
    FREQ_SHIFT_REPT_FUNCTION
};
};
#endif // _REPEATER_NETWORK_RESOURCES_NRM_DEFS_IDL_
```

Annex B (normative): XML Definitions

This annex contains the XML Definitions for the Generic RAN NRM IRP as it applies to Itf-N, in accordance with Generic RAN NRM IRP IS definitions [4].

The XML file formats are based on XML [8], XML Schema [10] [11] and XML Namespace [12] standards.

B.1 Architectural features

The overall architectural feature of Generic RAN Network Resources IRP is specified in 3GPP TS 28.662 [4]. This clause specifies features that are specific to the Schema definitions.

The XML definitions of this document specify the schema for a configuration content.

When using the XML definitions for a configuration file transfer with the Bulk CM IRP, using either CORBA Solution Set of 3GPP TS 32.616 [7] or SOAP Solution Set of 3GPP TS 32.616 [7], the basic part of the XML file format definition is provided by 3GPP TS 32.616 [7]. The XML definitions of this document provide the schema for the configuration content to be included in such a configuration file.

When using the XML definitions with a SOAP Solution Set of any Interface IRP that perform operations on managed objects, for example the Basic CM IRP SOAP SS of 3GPP TS 32.606 [6], the XML definitions of this document provides the schema for the configuration content operated on by the interface IRP. Such configuration content can be name of managed object and, if applicable, IOC attributes.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

The mapping is not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema `genericRanNrm.xsd` for the Generic RAN Network Resources IRP NRM defined in 3GPP TS 28.662 [4] (except Repeater object).

XML schema `genericRanNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM (except Repeater object) Annex B.3.4 of the present document defines the NRM-specific XML schema `repeaterNrm.xsd` for the Repeater object of the Generic RAN Network Resources IRP NRM defined in 3GPP TS 28.662 [4].

XML schema `repeaterNrm.xsd` explicitly declares NRM-specific XML element types for Repeater object defined in the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [7].

B.3.2 Graphical Representation

The graphical representation is not present in the current version of this specification.

B.3.3 XML schema "genericRanNrm.xsd"

```

□ <?xml version="1.1" encoding="UTF-8"?>
□ <!--
□ 3GPP TS 28.663 Generic RAN Network Resources IRP
□ Bulk CM Configuration data file NRM-specific XML schema
genericRanNrm.xsd
-->
<schema xmlns="http://www.w3.org/2001/XMLSchema"
xmlns:xn="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
xmlns:gn="http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"
xmlns:gr="http://www.3gpp.org/ftp/specs/archive/28_series/28.663#genericRanNrm"
targetNamespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.663#genericRanNrm"
elementFormDefault="qualified">

  <import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"/>
  <import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.656#geranNrm"/>

  <!-- Generic RAN Network Resources IRP NRM attribute related XML types -->

  <simpleType name="angleValue">
    <restriction base="short">
      <minInclusive value="0"/>
      <maxInclusive value="3600"/>
    </restriction>
  </simpleType>

  <simpleType name="retGroupName">
    <restriction base="string">
      <maxLength value="80"/>
    </restriction>
  </simpleType>

  <simpleType name="bearing">
    <restriction base="short">
      <minInclusive value="0"/>
      <maxInclusive value="360"/>
    </restriction>
  </simpleType>

  <simpleType name="tmaFunctionFlag">
    <restriction base="unsignedShort">
      <minInclusive value="0"/>
      <maxInclusive value="1"/>
    </restriction>
  </simpleType>

  <simpleType name="tmaStateFlag">
    <restriction base="unsignedShort">
      <minInclusive value="0"/>
      <maxInclusive value="1"/>
    </restriction>
  </simpleType>

  <simpleType name="fourOctets">
    <restriction base="hexBinary">

```

```

    <length value="4"/>
  </restriction>
</simpleType>

<!-- Generic RAN Network Resources IRP NRM class associated XML elements -->

<element name="SectorEquipmentFunction"
  substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="fqBand" type="short" />
                <element name="confOutputPower" type="short" />
                <element name="relatedTmaList" type="xn:dnList" />
                <element name="relatedAntennaList" type="xn:dnList" />
                <element name="relatedCellList" type="xn:dnList" />
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="gr:SectorEquipmentFunctionOptionallyContainedNrmClass"/>

            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="AntennaFunction"
  substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="retTiltValue" type="gr:angleValue"
minOccurs="0"/>
                <element name="bearing" type="gr:bearing" minOccurs="0"/>
                <element name="retGroupName" type="gr:retGroupName"
minOccurs="0"/>
                <element name="height" type="short" minOccurs="0"/>
                <element name="maxAzimuthValue" type="gr:angleValue"
minOccurs="0"/>
                <element name="minAzimuthValue" type="gr:angleValue"
minOccurs="0"/>
                <element name="horizBeamwidth" type="gr:angleValue"
minOccurs="0"/>
                <element name="vertBeamwidth" type="gr:angleValue"
minOccurs="0"/>
                <element name="relatedCellList" type="xn:dnList" />
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="gr:AntennaFunctionOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="TmaFunction" substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>

```

```

    <element name="attributes" minOccurs="0">
      <complexType>
        <all>
          <element name="userLabel" type="string"/>
          <element name="tmaSubunitNumber" type="unsignedShort" />
          <element name="tmaStateFlag" type="gr:tmaStateFlag" />
          <element name="tmaFunctionFlag" type="gr:tmaFunctionFlag" />
          <element name="tmaMinGain" type="unsignedShort" />
          <element name="tmaMaxGain" type="unsignedShort" />
          <element name="tmaResolution" type="unsignedShort" />
          <element name="tmaGainFigure" type="unsignedShort" />
          <element name="tmaNumberOfSubunits" type="unsignedShort" />
          <element name="tmaBaseStationId" type="string" minOccurs="0"/>
          <element name="tmaSectorId" type="string" minOccurs="0"/>
          <element name="tmaAntennaBearing" type="unsignedShort"
minOccurs="0"/>
          <element name="tmaInstalledMechanicalTilt" type="short"
minOccurs="0"/>
          <element name="tmaSubunitType" type="unsignedShort"
minOccurs="0"/>
          <element name="tmaSubunitRxFrequencyBand" type="gr:fourOctets"
minOccurs="0"/>
          <element name="tmaSubunitTxFrequencyBand" type="gr:fourOctets"
minOccurs="0"/>
          <element name="tmaGainResolution" type="unsignedShort"
minOccurs="0"/>
          <element name="relatedCellList" type="xn:dnList"/>
        </all>
      </complexType>
    </element>
    <choice minOccurs="0" maxOccurs="unbounded">
      <element ref="gr:TmaFunctionOptionallyContainedNrmClass"/>
      <element ref="xn:VsDataContainer"/>
    </choice>
  </sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="GSMCellPart" substitutionGroup="gn:GsmCellOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="aRFCN" type="string"/>
                <element name="tsc" type="long"/>
                <element name="aTA" type="short"/>
                <element name="relatedSectorEquipment" type="xn:dn"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="gr:GSMCellPartOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="CommonBSFunction"
substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="sharedTechnologies" type="short"/>
              </all>
            </complexType>
          </element>

```

```

        </complexType>
      </element>
      <choice minOccurs="0" maxOccurs="unbounded">
        <element ref="gr:CommonBSFunctionOptionallyContainedNrmClass"/>
        <element ref="xn:VsDataContainer"/>
      </choice>
    </sequence>
  </extension>
</complexContent>
</complexType>
</element>

  <element name="SectorEquipmentFunctionOptionallyContainedNrmClass" type="xn:NrmClass"
abstract="true"/>
  <element name="AntennaFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
  <element name="TmaFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
  <element name="GSMCellPartOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
  <element name="CommonBSFunctionOptionallyContainedNrmClass" type="xn:NrmClass" abstract="true"/>
</schema>

```

B.3.4 XML schema (file name "repeaterNrm.xsd")

```

<?xml version="1.1" encoding="UTF-8"?>

<!--
3GPP TS 28.663 Generic RAN Network Resources IRP
Bulk CM Configuration data file NRM-specific XML schema
repeaterNrm.xsd
-->

<schema
  targetNamespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.663#repeaterNrm"
  elementFormDefault="qualified"
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:xn=
"http://www.3gpp.org/ftp/specs/archive/32_series/28.623#genericNrm"
  xmlns:rn=
"http://www.3gpp.org/ftp/specs/archive/32_series/28.663#repeaterNrm"
>

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
  />

  <!-- Repeater Network Resources IRP NRM attribute related XML types -->

  <simpleType name="priority">
    <restriction base="integer">
      <minInclusive value="0"/>
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>

  <simpleType name="dLAttenuation">
    <restriction base="integer">
      <minInclusive value="0"/>
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>

  <simpleType name="uLAttenuation">
    <restriction base="integer">
      <minInclusive value="0"/>
      <maxInclusive value="268435455"/>
    </restriction>
  </simpleType>

  <simpleType name="latitude">
    <restriction base="decimal">
      <fractionDigits value="4"/>
      <minInclusive value="-90.0000"/>
      <maxInclusive value="90.0000"/>
    </restriction>
  </simpleType>

```

```

<simpleType name="longitude">
  <restriction base="decimal">
    <fractionDigits value="4"/>
    <minInclusive value="-90.0000"/>
    <maxInclusive value="90.0000"/>
  </restriction>
</simpleType>

<simpleType name="ctrlConnMode">
  <restriction base="string">
    <enumeration value="GSM_SMS"/>
    <enumeration value="WCDMA_SMS"/>
    <enumeration value="CIRCLE_SWITCH_DATA_CSD"/>
    <enumeration value="PACKAGE_SWITCH_DAT_IP"/>
    <enumeration value="SERIAL_PORT"/>
  </restriction>
</simpleType>

<simpleType name="powerSwitch">
  <restriction base="string">
    <enumeration value="ON"/>
    <enumeration value="OFF"/>
  </restriction>
</simpleType>

<simpleType name="repeaterType">
  <restriction base="string">
    <enumeration value="WideBandReptFunction"/>
    <enumeration value="FreqSelReptFunction"/>
    <enumeration value="FiberReptFunction"/>
    <enumeration value="IndoorReptFunction"/>
    <enumeration value="FreqShiftReptFunction"/>
  </restriction>
</simpleType>

<!-- Repeater Network Resources IRP NRM class associated XML elements -->

<element
  name="RepeaterFunction "
  substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass "
>
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="priority" type="rn:priority"/>
                <element name="latitude" type="rn:latitude"/>
                <element name="longitude" type="rn:longitude"/>
                <element name="ctrlConnMode" type="rn:ctrlConnMode"/>
                <element name="environmentInfo" type="string"/>
                <element name="powerSwitch" type="rn:powerSwitch"/>
                <element name="dLAttenuation" type="rn:dLAttenuation"/>
                <element name="uLAttenuation" type="rn:uLAttenuation"/>
                <element name="firmwareVer" type="string"/>
                <element name="repeaterType" type="rn:repeaterType"/>
                <element name="repeaterFunctionExternalUtranCell" type="xn:dn"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
</schema>

```

Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
2013-09	SA#61	SP-130443	001	1	Add missing Repeater Object SS definitions	F	11.0.0	11.1.0
2014-06	SA#64	SP-140332	002	-	Upgrade W3C XML Schema version from 1.0 to 1.1	F	11.1.0	11.2.0
		SP-140359	003	-	remove the feature support statements	F		
2015-12	SA#70	SP-150691	006	-	Make the XML schema well formed	F	11.2.0	11.3.0

History

Document history		
V11.0.0	January 2013	Publication
V11.1.0	October 2013	Publication
V11.2.0	July 2014	Publication
V11.3.0	January 2016	Publication