



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Home Node B (HNB) Subsystem (HNS)
Network Resource Model (NRM)
Integration Reference Point (IRP);
Requirements
(3GPP TS 28.671 version 11.0.0 Release 11)**



Reference

DTS/TSGS-0528671vb00

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	6
4 Concepts and background	7
5 Requirements.....	7
Annex A (informative): Change history	8
History	9

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Ready for Converged Management

This specification is part of a set that has been developed for converged management solutions.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication Management; as identified below:

- 28.671: Telecommunication management; Home Node B Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP): Requirements**
- 28.672: Telecommunication management; Home Node B Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service (IS)
- 28.673: Telecommunication management; Home Node B (HNB) Subsystem (HNS) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions

1 Scope

The document describes the requirements for Home NodeB Subsystem (HNS), which includes Home NodeB (HNB) and Home NodeB gateway (HNB GW). The HNS NRM IRP requirements are targeted on both HNB and HNB GW NRM.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 25.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [3] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [4] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [5] 3GPP TS 32.150: "Telecommunication management; Integration Reference Point (IRP) Concept and definitions".
- [6] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".
- [7] 3GPP TS 25.467: "UTRAN architecture for 3G Home NodeB; Stage 2".
- [8] 3GPP TS 32.107: "Telecommunication management; Fixed Mobile Convergence (FMC) Federated Network Information Model (FNIM)".
- [9] 3GPP TS 28.620: "Telecommunication management; Fixed Mobile Convergence (FMC) Federated Network Information Model (FNIM) Umbrella Information Model (UIM)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

Integration Reference Point (IRP): See 3GPP TS 32.150 [5].

Information Service (IS): See 3GPP TS 32.150 [5].

Solution Set (SS): See 3GPP TS 32.150 [5].

IRP Solution Set: See 3GPP TS 32.101 [1].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CN	Core Network
GW	Gateway
HNB	Home Node B
HNS	Home Node B Subsystem
IRP	Integration Reference Point
IOC	Information Object Class
NRM	Network Resource Model
SCTP	Stream Control Transmission Protocol

4 Concepts and background

HNB Subsystem is defined in TS 23.060 [6]. According to the definition, a HNB subsystem consists of a HNB and a HNB GW. The HNB Subsystem appears as an RNS to the core network and is connected by means of the Iu-CS interface to the MSC and by means of the Iu-PS interface to the SGSN.

Detailed functions of HNB and HNB GW are described in TS 25.467 [7]. To be more specific, HNB is a Customer Premise Equipment that offers the Uu Interface to the UE. It provides RAN connectivity and supports RNC like functions as well as UE registration over Iuh. HNB Gateway (HNB-GW) terminates Iuh from HNB and appears as an RNC to the existing Core network using existing Iu interface. It supports HNB registration and UE registration over Iuh.

Based on the above characteristics, this specification defines respective HNS NRM IRP requirements.

5 Requirements

The following general and high-level requirements apply for the present IRP:

- A. IRP-related requirements in 3GPP TS 32.101 [2].
- B. IRP-related requirements in 3GPP TS 32.102 [3].
- C. IRP-related requirements in 3GPP TS 32.600 [4].

The NRM defined by this IRP:

- D. Shall support communications for telecommunication network management purposes, including management of converged networks.
- E. Is a member of the Federated Network Information Model (FNIM) [8] and its information is derived from FNIM Umbrella Information Model (UIM) [9]

In addition to the above, the following more specific requirements apply:

REQ-HNS_GW-CON-001 The Network Resource Model defined by this IRP shall contain HNB GW specific IOCs and related definitions.

REQ-HNS_GW-CON-002 The Network Resource Model defined by this IRP shall provide support for enabling consistency between HNB GW, HNB and related core network nodes.

REQ-HNS_GW-CON-003 The NRM specified by this IRP shall be able to view configuration information of the HNB GW entity. More detailed information is as follows:

- Shall allow for the viewing of basic configuration information including version, equipment type, equipment provider and unique identification, etc.
- Shall allow for the viewing of network configuration information including IP address, sub-network mask, default gateway and port configuration information, etc.
- Shall allow for the viewing of service related configuration information, for example the maximum number of HNB to be registered, the maximum number of packets to be forwarded, etc.

REQ-HNS_GW-CON-004 The NRM specified by this IRP shall capture Iuh interface information of HNB GW. More detailed information is as follows:

- Shall allow for the viewing of basic configuration information including Iuh identification etc.
- Shall allow for the viewing of network configuration information including SCTP management information, etc.

REQ-HNS_GW-CON-005 The NRM specified by this IRP shall capture the identity of registered HNB.

Annex A (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
2012-11					First draft			0.1.0
2012-12					Presented for information and approval		0.1.0	1.0.0
2012-12					New version after approval		1.0.0	11.0.0

History

Document history		
V11.0.0	January 2013	Publication