## ETSI TS 128 682 V13.1.0 (2016-04)



Universal Mobile Telecommunications System (UMTS); LTE;

Telecommunication management;
Wireless Local Area Network (WLAN)
Network Resource Model (NRM)
Integration Reference Point (IRP);
Information Service (IS)
(3GPP TS 28.682 version 13.1.0 Release 13)



# Reference RTS/TSGS-0528682vd10 Keywords LTE,UMTS

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a></a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

#### Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup> and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> and **LTE**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <a href="http://webapp.etsi.org/key/queryform.asp">http://webapp.etsi.org/key/queryform.asp</a>.

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## Contents

Intelle	ectual Property Rights	2
Forew	word	2
Moda	al verbs terminology	2
	word	
Introd	duction	4
1	Scope	5
2	References	5
3	Definitions abbreviations	5
3.1	Definitions	
3.2	Abbreviations	
4	Model	6
4.1	Imported information entities and local labels	6
4.2	Class diagram	6
4.2.1	Relationships	6
4.2.2	Inheritance	
4.3	Class definitions	
4.3.1	APFunction	
4.3.1.1		
4.3.1.2	2 Attributes	7
4.3.1.3	Notifications	8
Anne	ex A (informative): Change history	9
Histor	ry	10

#### **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

#### where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; as identified below:

- TS 28.680: Telecommunication management; Wireless Local Area Network (WLAN) management; Concepts and requirements
- TS 28.681: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Requirements
- TS 28.682: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)
- TS 28.683: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions

#### 1 Scope

The present document is part of an Integration Reference Point (IRP) named Wireless Local Area Networks (WLAN) Management Network Resource Model (NRM) IRP, through which an IRPAgent can communicate management information to one or several IRPManagers concerning WLAN management. The WLAN management NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the protocol neutral WLAN management NRM IRP: Information Service (IS).

The present document also contains stage 2 descriptions for those functionalities for the WLAN Management.

#### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 28.622: "Telecommunication management; Generic Network Resource Model (NRMs) Integration Reference Point (IRP): Information Service" (IS)".
- [3] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [4] IEEE 802.11<sup>TM</sup>-2012: "IEEE Standard for Information technology--Telecommunications and information exchange between systems Local and metropolitan area networks--Specific requirements Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [5] 3GPP TS 28.632: "Telecommunication management; Inventory Management (IM) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
- [6] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [7] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [8] 3GPP TS 32.150: "Telecommunication management; Integration Reference Point (IRP) Concept and definitions".

#### 3 Definitions abbreviations

#### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1], 3GPP TS 32.101 [6], 3GPP TS 32.102 [7], and 3GPP TS 32.150 [8] apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

#### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

AP	Access Point
IOC	Information Object Class
IRP	Integration Reference Point
NRM	Network Resource Model
PLMN	Public Land Mobile Network
UML	Unified Modelling Language
WLAN	Wireless Local Area Network

#### 4 Model

#### 4.1 Imported information entities and local labels

Label reference	Local label
3GPP TS 28.622 [2], IOC, ManagedElement	ManagedElement
3GPP TS 28.622 [2], IOC, ManagedFunction	ManagedFunction

#### 4.2 Class diagram

#### 4.2.1 Relationships

This clause depicts the set of classes (e.g. IOCs) that encapsulates the information relevant for this IRP. This clause provides an overview of the relationships between relevant classes in UML. Subsequent clauses provide more detailed specification of various aspects of these classes. Figure 4.2.1-1 shows the containment/naming hierarchy and the associations of the classes defined in the present document.




Figure 4.2.1-1 WLAN NRM Containment/Naming

NOTE: WLAN NRM may need to be updated, if the WLAN access point is to be part of PLMN.

#### 4.2.2 Inheritance

This clause depicts the inheritance relationships that exist between information object classes. Figure 4.2.2-1 shows the inheritance diagram of WLAN NRM.




Figure 4.2.2-1 WLAN NRM Inheritance Hierarchy

#### 4.3 Class definitions

#### 4.3.1 APFunction

#### 4.3.1.1 Definition

This class represents the functionality of wireless Access Point as defined in IEEE 802.11 [4].

The APFunction IOC instance is not visible to Basic CM IRPManager, Bulk CM IRPManager and Kernel CM IRPManager.

The ManagedElement IOC instance (TS 28.622 [2]) name-containing the APFunction IOC instance is not visible to Basic CM IRPManager, Bulk CM IRPManager and Kernel CM IRPManager in case all the instances directly name-contained by this ManagedElement IOC instance (TS 28.622 [2]) are of APFunction IOC.

The InventoryUnit IOC instance (TS 28.632 [5]), name-contained by the ManagedElement IOC instance (TS 28.622 [2]) that name-contains the APFunction IOC instance, is not visible to Basic CM IRPManager, Bulk CM IRPManager and Kernel CM IRPManager in case all the instances directly name-contained by this ManagedElement IOC instance (TS 28.622 [2]) are of APFunction IOC or InventoryUnit IOC.

The following are examples of cases describing the conditions where IOC instance(s) are not visible to Basic CM IRPManager, Bulk CM IRPManager and Kernel CM IRPManager:

- Case 1) if ManagedElement-1 name-contains only two instances: APFunction-A and APFunction-B, the three instances are not visible.
- Case 2) if ManagedElement-1 name-contains only two instances: APFunction-A and MMEFunction-76, the APFunction-A is not visible.
- Case 3) if ManagedElement-1 name-contains only two instances: APFunction-A and InventoryUnit-7883 (TS 28.632 [5]), the three instances are not visible.

#### 4.3.1.2 Attributes

None

#### 4.3.1.3 Notifications

The set of notifications defined in the following table is valid.

Name	Qualifier	Notes
notifyAckStateChanged	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyChangedAlarm	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyClearedAlarm	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyNewAlarm	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyComments	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyAlarmListRebuilt	See Alarm IRP (3GPP TS 32.111-2 [3])	
notifyPotentialFaultyAlarmList	See Alarm IRP (3GPP TS 32.111-2 [3])	

## Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2015-12	SA-70	SP- 150687			Presented for approval	1.2.0	2.0.0
					Upgrade to Release 13	2.0.0	13.0.0
2016-03	SA-71	SP- 160033	001	1	Clarification for APFunction visibility	13.0.0	13.1.0

## History

Document history				
V13.0.0 January 2016 Publication				
V13.1.0	April 2016	Publication		