

ETSI TS 129 199-12 V6.6.0 (2007-06)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
Open Service Access (OSA);
Parlay X web services;
Part 12: Multimedia conference
(3GPP TS 29.199-12 version 6.6.0 Release 6)**



Reference

RTS/TSGC-0529199-12v660

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2007.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the TIPHON logo are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	7
4 Detailed service description	7
5 Namespaces.....	8
6 Sequence diagrams	9
6.1 Setting up a conference	9
6.2 Adding and Removing Media	10
6.3 Conference owner disconnects	11
6.4 All participants disconnect	12
6.5 Conference ended by application	13
7 XML Schema data type definition	14
7.1 ConferenceStatus enumeration	14
7.2 ConferenceInfo structure	14
7.3 ParticipantInfo structure	14
7.4 ParticipantStatus enumeration	14
7.5 Media enumeration.....	14
7.6 MediaDirection enumeration.....	14
7.7 MediaInfo structure	15
8 Web Service interface definition.....	16
8.1 Interface: MultimediaConference.....	16
8.1.1 Operation: createConference	16
8.1.1.1 Input message: createConferenceRequest	16
8.1.1.2 Output message: createConferenceResponse	16
8.1.1.3 Referenced faults.....	17
8.1.2 Operation: getConferenceInfo	18
8.1.2.1 Input message: getConferenceInfoRequest	18
8.1.2.2 Output message: getConferenceInfoResponse	18
8.1.2.3 Referenced faults.....	18
8.1.3 Operation: endConference	18
8.1.3.1 Input message: endConferenceRequest.....	18
8.1.3.2 Output message: endConferenceResponse.....	18
8.1.3.3 Referenced faults.....	18
8.1.4 Operation: inviteParticipant	19
8.1.4.1 Input message: inviteParticipantRequest.....	19
8.1.4.2 Output message: inviteParticipantResponse	19
8.1.4.3 Referenced faults.....	19
8.1.5 Operation: disconnectParticipant	20
8.1.5.1 Input message: disconnectParticipantRequest.....	20
8.1.5.2 Output message: disconnectParticipantResponse.....	20
8.1.5.3 Referenced faults.....	20
8.1.6 Operation: getParticipantInfo.....	20
8.1.6.1 Input message: getParticipantInfoRequest	20
8.1.6.2 Output message: getParticipantInfoResponse	20

8.1.6.3	Referenced faults.....	20
8.1.7	Operation: getParticipants.....	21
8.1.7.1	Input message: getParticipantsRequest	21
8.1.7.2	Output message: getParticipantsResponse	21
8.1.7.3	Referenced faults.....	21
8.1.8	Operation: addMediaForParticipant.....	22
8.1.8.1	Input message: addMediaForParticipantRequest	22
8.1.8.2	Output message: addMediaForParticipantResponse	22
8.1.8.3	Referenced faults.....	22
8.1.9	Operation: deleteMediaForParticipant.....	23
8.1.9.1	Input message: deleteMediaForParticipantRequest	23
8.1.9.2	Output message: deleteMediaForParticipantResponse	23
8.1.9.3	Referenced faults.....	23
9	Fault definitions.....	24
9.1	PolicyException	24
9.1.1	POL0240: Too many participants.....	24
9.1.2	POL0241: Unavailable media.....	24
9.1.3	POL0242: Maximum duration exceeded	24
9.2	ServiceException.....	24
9.2.1	SVC0210: Duplicate media stream.....	24
9.2.2	SVC0211: Media stream does not match.....	24
10	Service policies	24
Annex A (normative):	WSDL for Multimedia conference	25
Annex B (informative):	Description of Parlay X Web Services Part 12: Multimedia conference for 3GPP2 cdma2000 networks.....	26
B.1	General Exceptions.....	26
B.2	Specific Exceptions	26
B.2.1	Clause 1: Scope	26
B.2.2	Clause 2: References	26
B.2.3	Clause 3: Definitions and abbreviations	26
B.2.4	Clause 4: Detailed service description.....	26
B.2.5	Clause 5: Namespaces	26
B.2.6	Clause 6: Sequence diagrams	27
B.2.7	Clause 7: XML Schema data type definition.....	27
B.2.8	Clause 8: Web Service interface definition	27
B.2.9	Clause 9: Fault definitions.....	27
B.2.10	Clause 10: Service policies.....	27
B.2.11	Annex A (normative): WSDL for Multimedia conference.....	27
Annex C (informative):	Change history	28
History		29

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

3GPP acknowledges the contribution of the Parlay X Web Services specifications from The Parlay Group. The Parlay Group is pleased to see 3GPP acknowledge and publish the present document, and the Parlay Group looks forward to working with the 3GPP community to improve future versions of the present document.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part 12 of a multi-part deliverable covering the 3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; Open Service Access (OSA); Parlay X Web Services, as identified below:

Part 1:	"Common"
Part 2:	"Third party call"
Part 3:	"Call Notification"
Part 4:	"Short Messaging"
Part 5:	"Multimedia Messaging"
Part 6:	"Payment"
Part 7:	"Account management"
Part 8:	"Terminal Status"
Part 9:	"Terminal location"
Part 10:	"Call handling"
Part 11:	"Audio call"
Part 12:	"Multimedia conference"
Part 13:	"Address list management"
Part 14:	"Presence"

1 Scope

The present document is Part 12 of the Stage 3 Parlay X Web Services specification for Open Service Access (OSA).

The OSA specifications define an architecture that enables application developers to make use of network functionality through an open standardized interface, i.e. the OSA APIs. The concepts and the functional architecture for the OSA are contained in 3GPP TS 23.198 [3]. The requirements for OSA are contained in 3GPP TS 22.127 [2].

The present document specifies the Multimedia Conference Web Service aspects of the interface. All aspects of the Multimedia Conference Web Service are defined here, these being:

- Name spaces.
- Sequence diagrams.
- Data definitions.
- Interface specification plus detailed method descriptions.
- Fault definitions.
- Service policies.
- WSDL Description of the interfaces.

The present document has been defined jointly between 3GPP TSG CT WG5, ETSI TISPAN and The Parlay Group.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 22.127: "Service Requirement for the Open Services Access (OSA); Stage 1".

[3] 3GPP TS 23.198: "Open Service Access (OSA); Stage 2".

[4] 3GPP TS 22.101: "Service aspects; Service principles".

[5] W3C Recommendation (2 May 2001): "XML Schema Part 2: Datatypes".

NOTE: Available at <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>.

[6] 3GPP TS 29.199-1: "Open Service Access (OSA); Parlay X Web Services; Part 1: Common".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 29.199-1 [6] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TS 29.199-1 [6] apply.

4 Detailed service description

The Multimedia Conferencing is a simple Web Service that allows the creation of a multimedia conference and the dynamic management of the participants and the media involved.

The underlying model of the service is based on the following entities:

- **Conference:** a "context" (uniquely identified) to which participants can be added/removed.
- **Participant:** each of the parties involved in the conference. Media can be added/removed for each participant. There may exist a participant that is also the "owner" of the conference, i.e. the user who can end the call and/or be the reference user for billing purposes.
- **Media:** the conference can utilize multiple media streams to support the participants' communication. In particular both audio and video streams are available, including the specific stream direction (i.e. in, out, bidirectional).

An application setting up a multimedia conference must initially invoke the **createConference** method. The result of such invocation is the creation of a "context" that represents a "virtual" room where users can "meet". A unique identifier is assigned to the just-created conference. At this stage no participant is connected yet.

Subsequently the application may wish to add participants to the conference. In order to do so the method **inviteParticipant** can be used. The result of such method is to alert the user of the incoming connection request (e.g. the user's terminal rings).

If the application wishes to check whether the user has accepted the invitation (i.e. is connected) it can invoke (at a later time) the **getParticipantInfo** method.

Note that:

- As soon as the first participant connects, the conference becomes "active". The duration of the conference is then measured starting from the moment the conference has become active.
- The initial media set utilized by the participant will depend on the conference type and the media actually supported by the participant's terminal.

During the conference session the application is able to:

- Add (or remove) a specific media stream to a single participant: e.g. adding a video bidirectional stream to a participant that has an audio connection to the conference. This can be obtained by invoking the **addMediaForParticipant** and the **DeleteMediaForParticipant** methods.
- Disconnect a participant from the conference, by invoking the **disconnectParticipant** method.
- Retrieve information related to the conference and its status, by invoking **getConferenceInfo** and **getParticipants**.

There are different conditions that can determine the end of the conference:

- 1) The application may invoke the method **endConference**, that "forces" the termination of the conference and the disconnection of all participants.
- 2) The owner of the conference (if defined) leaves the conference. If the owner is not defined this condition will apply when all the participants have left the conference (disconnected).
- 3) The conference duration exceeds a maximum value (specified during the conference creation step).

5 Namespaces

The Multimedia Conference interface uses the namespace:

http://www.csapi.org/wsd/parlayx/multimedia_conference/v2_3

The data types are defined in the namespace:

http://www.csapi.org/schema/parlayx/multimedia_conference/v2_2


The 'xsd' namespace is used in the present document to refer to the XML Schema data types defined in XML Schema [5]. The use of the name 'xsd' is not semantically significant.

6 Sequence diagrams

The following sequence diagrams illustrate typical scenarios of interaction between an application and the Multimedia Conferencing Web Service.


6.1 Setting up a conference

Set up a multimedia conference call.




6.2 Adding and Removing Media

On an existing conference call, add media to, or remove media from, a participant.



6.3 Conference owner disconnects

During a conference call, the conference owner disconnects.




6.4 All participants disconnect

End of conference call processing when all participants disconnect.



6.5 Conference ended by application

End of conference call processing when the conference is ended by the application.



7 XML Schema data type definition

7.1 ConferenceStatus enumeration

Element name	Description
Initial	The conference has been created but no participant is connected yet
Active	The conference is active, i.e. at least one user has connected
Terminated	The conference was terminated

7.2 ConferenceInfo structure

Name	Type	Optional	Description
Status	ConferenceStatus	No	Status of the conference
StartTime	xsd:dateTime	No	The time at which the conference was created
Duration	xsd:int	No	The duration of the conference so far (in seconds)
Owner	xsd:anyURI	No	Conference owner
NumberOfParticipants	xsd:int	No	Current number of connected participants
MaximumNumberOfParticipants	xsd:int	No	Maximum number of participants
ConferenceIdentifier	xsd:string	No	Conference identifier
ConferenceDescription	xsd:string	No	Conference description

7.3 ParticipantInfo structure

Name	Type	Optional	Description
Participant	xsd:anyURI	No	Participant identifier
MediaInfo	MediaInfo[1..unbounded]	No	Media information currently used
StartTime	xsd:dateTime	No	Time this participant joined the conference
Status	ParticipantStatus	No	Status of participant

7.4 ParticipantStatus enumeration

Element name	Description
Invited	Participant invited but not connected yet
Connected	Participant connected
Disconnected	Participant disconnected

7.5 Media enumeration

Element name	Description
Audio	Audio media type
Video	Video media type
Chat	Chat media type
Data	Other media type

7.6 MediaDirection enumeration

Element name	Description
In	Incoming
Out	Outgoing
InOut	Bidirectional

7.7 MediaInfo structure

Element name	Element Type	Optional	Description
mediaType	Media	No	type of media information
mediaDirection	MediaDirection	No	direction of media
value	xsd:string	No	specifies audio or video codec, or data or chat encoding, for example G.723. In case there is no specific encoding (e.g. binary data) this may be an empty string.

8 Web Service interface definition

8.1 Interface: MultimediaConference

The MultimediaConference interface can be used by an application for creating a multimedia conference call and for dynamically managing the participants and the media involved in the call.

8.1.1 Operation: createConference

The invocation of **createConference** requests to create a multi-media conference with initially no participants connected. The reference to the new multimedia conference is returned in the output parameter.

The conference termination can be driven either by a user action or by the expiring of a maximum duration. In particular, three possible situations are considered. In the first scenario, the concept of the "conference owner" is used. This user that has the control of the call and when the conference owner leaves the conference, all users are disconnected (such a user could be for instance the reference for the conference billing). In this scenario, the optional parameter **conferenceOwner** is present in the method call.

In the second scenario, the conference is terminated when the last participant abandons (in this case the parameter **conferenceOwner** is not present).

A third case is when the optional parameter **maximumDuration** is present: in this situation, when the maximum duration is reached, the conference is terminated.

The selection of the scenario depends on the presence of the optional parameters; if no optional parameter is present, the conference end condition is the disconnection of the last user in conference, if both are present, the conference is terminated when the duration expires (this case could happen if the information concerning the conference owner is needed for billing purposes).

The values **maximumDuration** and **maximumNumberOfParticipants** must not exceed the corresponding service policies otherwise a policy exception is raised.

8.1.1.1 Input message: createConferenceRequest

Part name	Part type	Optional	Description
ConferenceType	xsd:string	Yes	Conference type, i.e. one of a list of operator-specific identifiers that indicates how the conference is rendered on the terminals
ConferenceDescription	xsd:string	No	A text describing the conference
Charging	common:ChargingInformation	Yes	If present, defines the charge per unit of time consumed on the conference call. If the service does not support charging, a PolicyException (POL0008) will be returned.
MaximumDuration	xsd:int	Yes	If present it represents the maximum duration of the multimedia conference in seconds. If this parameter is present, it represents the end condition of the conference.
MaximumNumberOfParticipants	xsd:int	No	Maximum number of participants allowed
ConferenceOwner	xsd:anyURI	Yes	It is the address of the multimedia conference owner. If this parameter is present, and the maximumDuration is not present, the conference is terminated when this user disconnects, else this information can be used for billing or other purpose

8.1.1.2 Output message: createConferenceResponse

Part name	Part type	Optional	Description
result	xsd:string	No	Conference identifier

8.1.1.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.
- POL0008: Charging not supported.
- POL0240: Too many participants.
- POL0242: Maximum duration exceeded.

8.1.2 Operation: getConferenceInfo

The invocation of **getConferenceInfo** requests the information concerning the current status of the multi-media conference call identified by **conferenceIdentifier**.

8.1.2.1 Input message: getConferenceInfoRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier

8.1.2.2 Output message: getConferenceInfoResponse

Part name	Part type	Optional	Description
result	ConferenceInfo	No	Status of the conference

8.1.2.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

8.1.3 Operation: endConference

The invocation of **endConference** requests to terminate the multi-media conference call identified by **conferenceIdentifier**.

8.1.3.1 Input message: endConferenceRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier

8.1.3.2 Output message: endConferenceResponse

Part name	Part type	Optional	Description
None			

8.1.3.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

8.1.4 Operation: inviteParticipant

The invocation of **inviteParticipant** requests to add a new participant specified by **participant** to the multi-media conference call identified by **conferenceIdentifier**. The media used for the initial connection of the new participant depends on the conference type and the participant's supported media.

The operation will fail if the conference has already reached the maximum number of participants (as specified in the creation operation).

8.1.4.1 Input message: inviteParticipantRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier
Participant	xsd:anyURI	No	New participant invited

8.1.4.2 Output message: inviteParticipantResponse

Part name	Part type	Optional	Description
None			

8.1.4.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.
- POL0240: Too many participants.

8.1.5 Operation: disconnectParticipant

The invocation of **disconnectParticipant** requests to disconnect the participant specified by **participant** from the multi-media conference call identified by **conferenceIdentifier**.

8.1.5.1 Input message: disconnectParticipantRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier
Participant	xsd:anyURI	No	Participant

8.1.5.2 Output message: disconnectParticipantResponse

Part name	Part type	Optional	Description
None			

8.1.5.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

8.1.6 Operation: getParticipantInfo

The invocation of **getParticipantInfo** requests information concerning the current status of the participant specified by **participant**, in the multi-media conference call identified by **conferenceIdentifier**.

8.1.6.1 Input message: getParticipantInfoRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier
Participant	xsd:anyURI	No	Participant

8.1.6.2 Output message: getParticipantInfoResponse

Part name	Part type	Optional	Description
result	ParticipantInfo	No	Status of the participant

8.1.6.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

8.1.7 Operation: getParticipants

The invocation of **getParticipants** requests information concerning the current status of each participant of the multi-media conference call identified by **conferenceIdentifier**. The output includes participants already disconnected from the conference (if any).

8.1.7.1 Input message: getParticipantsRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier

8.1.7.2 Output message: getParticipantsResponse

Part name	Part type	Optional	Description
result	ParticipantInfo [0..unbounded]	Yes	Array containing status information for each participant

8.1.7.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

8.1.8 Operation: addMediaForParticipant

The invocation of **addMediaForParticipant** requests to add a **media** stream to the media set used by **participant**. The operation is executed on a single participant connected to the multi-media conference call identified by **conferenceIdentifier**. The new media has to be compatible with the type of multimedia conference and the set of media supported by the participant terminal, otherwise the operation will fail. If the participant has already the requested media stream, the operation will fail and throw *ServiceException* SVC0210.

8.1.8.1 Input message: addMediaForParticipantRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier
Participant	xsd:anyURI	No	Participant
Media	Media	No	It identifies the new media stream the participant will receive/send.
MediaDirection	MediaDirection	No	It indicates the direction of the media stream to add (in, out, etc.)

8.1.8.2 Output message: addMediaForParticipantResponse

Part name	Part type	Optional	Description
None			

8.1.8.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.
- SVC0210: Duplicate media stream

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.
- POL0241: Unavailable media.

8.1.9 Operation: deleteMediaForParticipant

The invocation of **deleteMediaForParticipant** requests to remove a **media** stream from the media set used by **participant**. The operation is executed on a single participant connected to the multi-media conference call identified by **conferenceIdentifier**. If the participant does not have the requested media stream, the operation will fail and throw **ServiceException SVC0211**.

8.1.9.1 Input message: deleteMediaForParticipantRequest

Part name	Part type	Optional	Description
ConferenceIdentifier	xsd:string	No	Conference identifier
Participant	xsd:anyURI	No	Participant
Media	Media	No	It identifies the media the user is not enabled to use any more.
MediaDirection	MediaDirection	No	It indicates the direction of the media stream to remove (in, out, etc.)

8.1.9.2 Output message: deleteMediaForParticipantResponse

Part name	Part type	Optional	Description
None			

8.1.9.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.
- SVC0211: Media stream does not match

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.

9 Fault definitions

9.1 PolicyException

9.1.1 POL0240: Too many participants

Too many participants.

Name	Description
Message Id	POL0240
Text	Too many participants
Variables	None

9.1.2 POL0241: Unavailable media

Name	Description
Message Id	POL0241
Text	Unavailable media
Variables	None

9.1.3 POL0242: Maximum duration exceeded

Name	Description
Message Id	POL0242
Text	Maximum duration exceeded. Maximum allowed is %1 seconds.
Variables	%1 – maximum duration set by service policy

9.2 ServiceException

9.2.1 SVC0210: Duplicate media stream

Name	Description
messageId	SVC0210
text	Duplicate media stream
variables	None

9.2.2 SVC0211: Media stream does not match

Name	Description
messageId	SVC0211
text	Media stream does not match
variables	None

10 Service policies

Name	Type	Description
MaximumDuration	xsd:int	Maximum duration (in seconds) a conference may be set up for
MaximumParticipants	xsd:int	Maximum number of participants a conference may be set up for
ChargingSupported	xsd:boolean	Is charging supported for the createConference operation

Annex A (normative): WSDL for Multimedia conference

The document/literal WSDL representation of this interface specification is compliant to 3GPP TS 29.199-1 [6] and is contained in text files (contained in archive 29199-12-660-doclit.zip) which accompanies the present document.

Annex B (informative): Description of Parlay X Web Services Part 12: Multimedia conference for 3GPP2 cdma2000 networks

This annex is intended to define the OSA Parlay X Web Services Stage 3 interface definitions and it provides the complete OSA specifications. It is an extension of OSA Parlay X Web Services specifications capabilities to enable operation in cdma2000 systems environment. They are in alignment with 3GPP2 Stage 1 requirements and Stage 2 architecture defined in:

- [1] 3GPP2 X.S0011-D: "cdma2000 Wireless IP Network Standard ", Version 1.1
- [2] 3GPP2 S.R0037-0: "IP Network Architecture Model for cdma2000 Spread Spectrum Systems", Version 3.0
- [3] 3GPP2 X.S0013-A: "All-IP Core Network Multimedia Domain"

These requirements are expressed as additions to and/or exclusions from the 3GPP Release 6 specification. The information given here is to be used by developers in 3GPP2 cdma2000 network architecture to interpret the 3GPP OSA specifications.

B.1 General Exceptions

The terms 3GPP and UMTS are not applicable for the cdma2000 family of standards. Nevertheless these terms are used (3GPP TR 21.905) mostly in the broader sense of "3G Wireless System". If not stated otherwise there are no additions or exclusions required.

CAMEL mappings are not applicable for cdma2000 systems.

B.2 Specific Exceptions

B.2.1 Clause 1: Scope

There are no additions or exclusions.

B.2.2 Clause 2: References

There are no additions or exclusions.

B.2.3 Clause 3: Definitions and abbreviations

There are no additions or exclusions.

B.2.4 Clause 4: Detailed service description

There are no additions or exclusions.

B.2.5 Clause 5: Namespaces

There are no additions or exclusions.

B.2.6 Clause 6: Sequence diagrams

There are no additions or exclusions.

B.2.7 Clause 7: XML Schema data type definition

There are no additions or exclusions.

B.2.8 Clause 8: Web Service interface definition

There are no additions or exclusions.

B.2.9 Clause 9: Fault definitions

There are no additions or exclusions.

B.2.10 Clause 10: Service policies

There are no additions or exclusions.

B.2.11 Annex A (normative): WSDL for Multimedia conference

There are no additions or exclusions.

Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Sep 2004	CN_25	NP-040360	--	--	Draft v100 submitted to TSG CN#25 for Approval.	--	1.0.0	6.0.0
Jun 2005	CT_28	CP-050221	0001	--	Optionals for Part 12	F	6.0.0	6.1.0
Dec 2005	CT_30	CP-050577	0002	--	Inconsistent part naming in PX response messages	F	6.1.0	6.2.0
Jun 2006	CT_32	CP-060195	0003	--	Change reference to OSA Stage 2 from 23.127 to 23.198	F	6.2.0	6.3.0
Dec 2006	CT_34	CP-060593	0004	--	Add missing ServiceExceptions to Multimedia Conference Web Service	F	6.3.0	6.4.0
Dec 2006	CT_34	CP-060593	0005	--	Correct the ParticipantInfo structure of Multimedia Conference Web Service	F	6.3.0	6.4.0
Mar 2007	CT_35	CP-070045	0006	--	Add OSA Parlay Web Services support for 3GPP2 networks	F	6.4.0	6.5.0
Mar 2007	CT_35	CP-070045	0007	--	Corrections to namespace version numbers	F	6.4.0	6.5.0
Jun 2007	CT_36	CP-070345	0009	--	Correction to Common Faults namespace version number	F	6.5.0	6.6.0

History

Document history		
V6.0.0	January 2005	Publication
V6.1.0	June 2005	Publication
V6.2.0	December 2005	Publication
V6.3.0	June 2006	Publication
V6.4.0	December 2006	Publication
V6.5.0	March 2007	Publication
V6.6.0	June 2007	Publication