

ETSI TS 129 222 V15.0.0 (2018-07)



**5G;**  
**Common API Framework for 3GPP Northbound APIs**  
**(3GPP TS 29.222 version 15.0.0 Release 15)**



---

Reference

DTS/TSGC-0329222vf00

---

Keywords

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

|  |    |
|--|----|
| Intellectual Property Rights .....   | 2  |
| Foreword.....  | 2  |
| Modal verbs terminology.....   | 2  |
| Foreword.....  | 10 |
| 1 Scope .....  | 11 |
| 2 References .....   | 11 |
| 3 Definitions and abbreviations.....   | 11 |
| 3.1 Definitions .....  | 11 |
| 3.2 Abbreviations .....  | 12 |
| 4 Overview .....   | 12 |
| 4.1 Introduction .....   | 12 |
| 4.2 Service Architecture .....   | 12 |
| 4.3 Functional Entities.....   | 13 |
| 4.3.1 API invoker.....   | 13 |
| 4.3.2 CAPIF core function.....   | 14 |
| 4.3.3 API exposing function .....  | 14 |
| 4.3.4 API publishing function.....   | 14 |
| 4.3.5 API management function .....  | 14 |
| 5 Services offered by the CAPIF Core Function.....   | 15 |
| 5.1 Introduction of Services .....   | 15 |
| 5.2 CAPIF_Discovery_Service_API.....   | 15 |
| 5.2.1 Service Description.....   | 15 |
| 5.2.1.1 Overview .....   | 15 |
| 5.2.2 Service Operations.....  | 16 |
| 5.2.2.1 Introduction .....   | 16 |
| 5.2.2.2 Discover_Service_API.....  | 16 |
| 5.2.2.2.1 General .....  | 16 |
| 5.2.2.2.2 API invoker discovering service API using Discover_Service_API service operation.....  | 16 |
| 5.3 CAPIF_Publish_Service_API .....  | 16 |
| 5.3.1 Service Description.....   | 16 |
| 5.3.1.1 Overview.....  | 16 |
| 5.3.2 Service Operations.....  | 17 |
| 5.3.2.1 Introduction.....  | 17 |
| 5.3.2.2 Publish_Service_API .....  | 17 |
| 5.3.2.2.1 General .....  | 17 |
| 5.3.2.2.2 API publishing function publishing service APIs on CAPIF core function using Publish_Service_API service operation .....       | 17 |
| 5.3.2.3 Unpublish_Service_API.....   | 17 |
| 5.3.2.3.1 General .....  | 17 |
| 5.3.2.3.2 API publishing function un-publishing service APIs from CAPIF core function using Unpublish_Service_API service operation..... | 17 |
| 5.3.2.4 Retrieve_Service_API.....  | 18 |
| 5.3.2.4.1 General .....  | 18 |
| 5.3.2.4.2 API publishing function retrieving service APIs from CAPIF core function using Retrieve_Service_API service operation.....     | 18 |
| 5.3.2.5 Update_Service_API.....  | 18 |
| 5.3.2.5.1 General .....  | 18 |
| 5.3.2.5.2 API publishing function updating published service APIs on CAPIF core function using Update_Service_API service operation..... | 18 |
| 5.4 CAPIF_Events_API .....   | 18 |
| 5.4.1 Service Description.....   | 18 |
| 5.4.1.1 Overview .....   | 18 |
| 5.4.2 Service Operations.....  | 19 |
| 5.4.2.1 Introduction.....  | 19 |

|            |   |    |
|------------|---|----|
| 5.4.2.2    | Event_Subscription_API.....   | 19 |
| 5.4.2.2.1  | General .....   | 19 |
| 5.4.2.2.2  | Subscribing to CAPIF events using Event_Subscription service operation .....  | 19 |
| 5.4.2.3    | Event_Unsubscription_API.....   | 19 |
| 5.4.2.3.1  | General .....   | 19 |
| 5.4.2.3.2  | Unsubscribing from CAPIF events using Event_Unsubscription service operation .....  | 19 |
| 5.4.2.4    | Event_Notification_API.....   | 19 |
| 5.4.2.4.1  | General .....   | 19 |
| 5.4.2.4.2  | Notifying CAPIF events using Event_Notification service operation.....  | 20 |
| 5.5        | CAPIF_API_Invoker_Management_API.....   | 20 |
| 5.5.1      | Service Description.....  | 20 |
| 5.5.1.1    | Overview.....   | 20 |
| 5.5.2      | Service Operations.....   | 20 |
| 5.5.2.1    | Introduction.....   | 20 |
| 5.5.2.2    | Onboard_API_Invoker_API.....  | 20 |
| 5.5.2.2.1  | General .....   | 20 |
| 5.5.2.2.2  | API invoker on-boarding itself as a recognized user of CAPIF using Onboard_API_Invoker service operation.....                                 | 20 |
| 5.5.2.3    | Offboard_API_Invoker_API.....   | 21 |
| 5.5.2.3.1  | General .....   | 21 |
| 5.5.2.3.2  | API invoker off-boarding itself as a recognized user of CAPIF using Offboard_API_Invoker service operation.....                               | 21 |
| 5.6        | CAPIF_Authentication_Authorization_API.....   | 21 |
| 5.6.1      | Service Description.....  | 21 |
| 5.6.1.1    | Overview.....   | 21 |
| 5.6.2      | Service Operations.....   | 22 |
| 5.6.2.1    | Introduction.....   | 22 |
| 5.6.2.2    | Service_Security_Method_Request_API.....  | 22 |
| 5.6.2.2.1  | General .....   | 22 |
| 5.6.2.2.2  | Request service API security method from CAPIF using Service_Security_Method_Request service operation.....                                   | 22 |
| 5.6.2.2.3  | Obtain authorization using Obtain_Authorization service operation.....  | 22 |
| 5.6.2.2.4  | Obtain API invoker's security information using Obtain_API_Invoker_Info service operation .....   | 23 |
| 5.6.2.2.5  | Invalidate authorization using Invalidate_Authorization service operation .....   | 23 |
| 5.7        | CAPIF_Monitoring_API.....   | 23 |
| 5.8        | CAPIF_Logging_API_Invocation_API .....  | 23 |
| 5.8.1      | Service Description.....  | 23 |
| 5.8.1.1    | Overview.....   | 23 |
| 5.8.2      | Service Operations.....   | 23 |
| 5.8.2.1    | Introduction.....   | 23 |
| 5.8.2.2    | Log_API_Invocation_API .....  | 23 |
| 5.8.2.2.1  | General .....   | 23 |
| 5.8.2.2.2  | Logging service API invocations using Log_API_Invocation service operation .....  | 23 |
| 5.9        | CAPIF_Auditing_API.....   | 24 |
| 5.9.1      | Service Description.....  | 24 |
| 5.9.1.1    | Overview.....   | 24 |
| 5.9.2      | Service Operations.....   | 24 |
| 5.9.2.1    | Introduction.....   | 24 |
| 5.9.2.2    | Query_Invocation_Logs_API .....   | 24 |
| 5.9.2.2.1  | General .....   | 24 |
| 5.9.2.2.2  | Query API invocation information logs using Query_Invocation_Logs service operation.....  | 24 |
| 5.10       | CAPIF_Access_Control_Policy_API.....  | 25 |
| 5.10.1     | Service Description.....  | 25 |
| 5.10.1.1   | Overview.....   | 25 |
| 5.10.2     | Service Operations.....   | 25 |
| 5.10.2.1   | Introduction.....   | 25 |
| 5.10.2.2   | Obtain_Access_Control_Policy .....  | 25 |
| 5.10.2.2.1 | General .....   | 25 |
| 5.10.2.2.2 | API exposing function obtaining access control policy from the CAPIF core function using Obtain_Access_Control_Policy service operation ..... | 25 |
| 5.10.3     | Related Events .....  | 25 |

|               |  |    |
|---------------|--|----|
| 6             | Services offered by the API exposing function.....   | 25 |
| 6.1           | Introduction of Services .....   | 25 |
| 6.2           | AEF_Authentication_API .....   | 26 |
| 6.2.1         | Service Description.....   | 26 |
| 6.2.1.1       | Overview .....   | 26 |
| 6.2.2         | Service Operations.....  | 26 |
| 6.2.2.1       | Introduction.....  | 26 |
| 6.2.2.2       | Authentication_Initiation_Request_API .....  | 26 |
| 6.2.2.2.1     | General .....  | 26 |
| 6.2.2.2.2     | API invoker initiating authentication using Authentication_Initiation_Request service operation..... | 26 |
| 7             | CAPIF Design Aspects Common for All APIs .....   | 26 |
| 7.1           | General .....  | 26 |
| 7.2           | Data Types.....  | 27 |
| 7.2.1         | General.....   | 27 |
| 7.2.2         | Referenced structured data types .....   | 27 |
| 7.2.3         | Referenced Simple data types and enumerations.....   | 27 |
| 7.3           | Usage of HTTP.....   | 27 |
| 7.4           | Content type .....   | 27 |
| 7.5           | URI structure .....  | 28 |
| 7.6           | Notifications.....   | 28 |
| 7.7           | Error handling .....   | 28 |
| 7.8           | Feature negotiation .....  | 28 |
| 7.9           | HTTP headers.....  | 28 |
| 8             | CAPIF API Definition.....  | 29 |
| 8.1           | CAPIF_Discovery_Service_API.....   | 29 |
| 8.1.1         | API URI .....  | 29 |
| 8.1.2         | Resources.....   | 29 |
| 8.1.2.1       | Overview .....   | 29 |
| 8.1.2.2       | Resource: All published service APIs .....   | 29 |
| 8.1.2.2.1     | Description .....  | 29 |
| 8.1.2.2.2     | Resource Definition.....   | 29 |
| 8.1.2.2.3     | Resource Standard Methods .....  | 30 |
| 8.1.2.2.4     | Resource Custom Operations .....   | 30 |
| 8.1.2.2.4.1   | Overview.....  | 30 |
| 8.1.2.2.4.2   | Operation: discover.....   | 30 |
| 8.1.2.2.4.2.1 | Description .....  | 30 |
| 8.1.2.2.4.2.2 | Operation Definition .....   | 30 |
| 8.1.3         | Notifications .....  | 30 |
| 8.1.4         | Data Model .....   | 30 |
| 8.1.4.1       | General .....  | 30 |
| 8.1.4.2       | Structured data types.....   | 31 |
| 8.1.4.2.1     | Introduction .....   | 31 |
| 8.1.4.2.2     | Type: APIQuery .....   | 31 |
| 8.1.4.2.3     | Type: DiscoveredAPIs.....  | 31 |
| 8.1.4.3       | Simple data types and enumerations .....   | 31 |
| 8.1.5         | Error Handling .....   | 31 |
| 8.1.6         | Feature negotiation .....  | 31 |
| 8.2           | CAPIF_Publish_Service_API .....  | 32 |
| 8.2.1         | API URI .....  | 32 |
| 8.2.2         | Resources.....   | 32 |
| 8.2.2.1       | Overview .....   | 32 |
| 8.2.2.2       | Resource: APF published APIs.....  | 33 |
| 8.2.2.2.1     | Description .....  | 33 |
| 8.2.2.2.2     | Resource Definition.....   | 33 |
| 8.2.2.2.3     | Resource Standard Methods .....  | 33 |
| 8.2.2.2.3.1   | POST.....  | 33 |
| 8.2.2.2.3.2   | GET.....   | 33 |
| 8.2.2.2.4     | Resource Custom Operations .....   | 34 |
| 8.2.2.3       | Resource: Individual APF published API .....   | 34 |

|             |  |    |
|-------------|--|----|
| 8.2.2.3.1   | Description .....                                    | 34 |
| 8.2.2.3.2   | Resource Definition .....                            | 34 |
| 8.2.2.3.3   | Resource Standard Methods .....                      | 34 |
| 8.2.2.3.3.1 | GET .....  | 34 |
| 8.2.2.3.3.2 | PUT .....  | 35 |
| 8.2.2.3.3.3 | DELETE .....   | 35 |
| 8.2.2.3.4   | Resource Custom Operations .....                     | 35 |
| 8.2.3       | Notifications .....                                  | 35 |
| 8.2.4       | Data Model .....                                     | 36 |
| 8.2.4.1     | General .....  | 36 |
| 8.2.4.2     | Structured data types .....                          | 36 |
| 8.2.4.2.1   | Introduction .....                                   | 36 |
| 8.2.4.2.2   | Type: ServiceAPIDescription .....                    | 36 |
| 8.2.4.2.3   | Type: InterfaceDescription .....                     | 37 |
| 8.2.4.3     | Simple data types and enumerations .....             | 37 |
| 8.2.4.3.1   | Introduction .....                                   | 37 |
| 8.2.4.3.2   | Simple data types .....                              | 37 |
| 8.2.4.3.3   | Enumeration: Protocol .....                          | 37 |
| 8.2.4.3.4   | Enumeration: DataFormat .....                        | 37 |
| 8.2.5       | Error Handling .....                                 | 37 |
| 8.2.6       | Feature negotiation .....                            | 37 |
| 8.3         | CAPIF_Events_API .....                               | 38 |
| 8.3.1       | API URI .....  | 38 |
| 8.3.2       | Resources .....                                      | 38 |
| 8.3.2.1     | Overview .....                                       | 38 |
| 8.3.2.2     | Resource: CAPIF Events Subscriptions .....           | 38 |
| 8.3.2.2.1   | Description .....                                    | 38 |
| 8.3.2.2.2   | Resource Definition .....                            | 39 |
| 8.3.2.2.3   | Resource Standard Methods .....                      | 39 |
| 8.3.2.2.3.1 | POST .....   | 39 |
| 8.3.2.2.4   | Resource Custom Operations .....                     | 39 |
| 8.3.2.3     | Resource: Individual CAPIF Events Subscription ..... | 39 |
| 8.3.2.3.1   | Description .....                                    | 39 |
| 8.3.2.3.2   | Resource Definition .....                            | 39 |
| 8.3.2.3.3   | Resource Standard Methods .....                      | 40 |
| 8.3.2.3.3.1 | DELETE .....   | 40 |
| 8.3.2.3.4   | Resource Custom Operations .....                     | 40 |
| 8.3.3       | Notifications .....                                  | 40 |
| 8.3.3.1     | General .....  | 40 |
| 8.3.3.2     | Event Notification .....                             | 40 |
| 8.3.3.2.1   | Description .....                                    | 40 |
| 8.3.3.2.2   | Notification definition .....                        | 41 |
| 8.3.4       | Data Model .....                                     | 41 |
| 8.3.4.1     | General .....  | 41 |
| 8.3.4.2     | Structured data types .....                          | 41 |
| 8.3.4.2.1   | Introduction .....                                   | 41 |
| 8.3.4.2.2   | Type: EventSubscription .....                        | 42 |
| 8.3.4.2.3   | Type: EventNotification .....                        | 42 |
| 8.3.4.3     | Simple data types and enumerations .....             | 42 |
| 8.3.4.3.1   | Introduction .....                                   | 42 |
| 8.3.4.3.2   | Simple data types .....                              | 42 |
| 8.3.4.3.3   | Enumeration: CAPIFEvent .....                        | 43 |
| 8.3.5       | Error Handling .....                                 | 43 |
| 8.3.6       | Feature negotiation .....                            | 43 |
| 8.4         | CAPIF_API_Invoker_Management_API .....               | 43 |
| 8.4.1       | API URI .....  | 43 |
| 8.4.2       | Resources .....                                      | 44 |
| 8.4.2.1     | Overview .....                                       | 44 |
| 8.4.2.2     | Resource: On-boarded API invokers .....              | 44 |
| 8.4.2.2.1   | Description .....                                    | 44 |
| 8.4.2.2.2   | Resource Definition .....                            | 44 |
| 8.4.2.2.3   | Resource Standard Methods .....                      | 44 |

|             |  |    |
|-------------|--|----|
| 8.4.2.2.3.1 | POST .....                                       | 44 |
| 8.4.2.2.4   | Resource Custom Operations .....                 | 45 |
| 8.4.2.3     | Resource: Individual On-boarded API Invoker..... | 45 |
| 8.4.2.3.1   | Description .....                                | 45 |
| 8.4.2.3.2   | Resource Definition.....                         | 45 |
| 8.4.2.3.3   | Resource Standard Methods .....                  | 45 |
| 8.4.2.3.3.1 | DELETE .....                                     | 45 |
| 8.3.2.3.4   | Resource Custom Operations .....                 | 46 |
| 8.4.3       | Notifications .....                              | 46 |
| 8.4.3.1     | General .....                                    | 46 |
| 8.4.3.2     | On-boarding Notification .....                   | 46 |
| 8.4.3.2.1   | Description .....                                | 46 |
| 8.4.3.2.2   | Notification definition .....                    | 46 |
| 8.4.4       | Data Model .....                                 | 47 |
| 8.4.4.1     | General .....                                    | 47 |
| 8.4.4.2     | Structured data types .....                      | 48 |
| 8.4.4.2.1   | Introduction .....                               | 48 |
| 8.4.4.2.2   | Type: APIInvokerEnrolmentDetails .....           | 48 |
| 8.4.4.2.3   | Type: OnboardingNotificationDestination .....    | 48 |
| 8.4.4.2.4   | Type: APIList .....                              | 48 |
| 8.4.4.2.5   | Type: OnboardingInformation .....                | 49 |
| 8.4.4.2.6   | Type: OnboardingRequestAck .....                 | 49 |
| 8.4.4.2.7   | Type: CAPIFOnboardingNotification .....          | 49 |
| 8.4.4.3     | Simple data types and enumerations .....         | 49 |
| 8.4.5       | Error Handling .....                             | 49 |
| 8.4.6       | Feature negotiation .....                        | 49 |
| 8.5         | CAPIF_Authentication_Authorization_API.....      | 50 |
| 8.5.1       | API URI .....                                    | 50 |
| 8.5.2       | Resources .....                                  | 50 |
| 8.5.2.1     | Overview .....                                   | 50 |
| 8.5.2.2     | Resource: Trusted API invokers .....             | 51 |
| 8.5.2.2.1   | Description .....                                | 51 |
| 8.5.2.2.2   | Resource Definition.....                         | 51 |
| 8.5.2.2.3   | Resource Standard Methods .....                  | 51 |
| 8.5.2.2.3.1 | POST.....  | 51 |
| 8.5.2.2.4   | Resource Custom Operations .....                 | 51 |
| 8.5.2.3     | Resource: Individual trusted API invokers .....  | 52 |
| 8.5.2.3.1   | Description .....                                | 52 |
| 8.5.2.3.2   | Resource Definition.....                         | 52 |
| 8.5.2.3.3   | Resource Standard Methods .....                  | 52 |
| 8.5.2.3.3.1 | GET.....   | 52 |
| 8.5.2.3.3.2 | DELETE .....                                     | 52 |
| 8.5.2.3.4   | Resource Custom Operations .....                 | 53 |
| 8.5.3       | Notifications .....                              | 53 |
| 8.5.3.1     | General .....                                    | 53 |
| 8.5.3.2     | Authorization revoked notification .....         | 53 |
| 8.5.3.2.1   | Description .....                                | 53 |
| 8.5.3.2.2   | Notification definition .....                    | 53 |
| 8.5.4       | Data Model .....                                 | 54 |
| 8.5.4.1     | General .....                                    | 54 |
| 8.5.4.2     | Structured data types .....                      | 55 |
| 8.5.4.2.1   | Introduction .....                               | 55 |
| 8.5.4.2.2   | Type: ServiceSecurity .....                      | 55 |
| 8.5.4.2.3   | Type: SecurityMethod .....                       | 55 |
| 8.5.4.2.4   | Type: securityNotificationDestination.....       | 56 |
| 8.5.4.3     | Simple data types and enumerations .....         | 56 |
| 8.5.5       | Error Handling .....                             | 56 |
| 8.5.6       | Feature negotiation .....                        | 56 |
| 8.6         | CAPIF_Access_Control_Policy_API.....             | 56 |
| 8.6.1       | API URI .....                                    | 56 |
| 8.6.2       | Resources.....                                   | 56 |
| 8.6.2.1     | Overview.....                                    | 56 |

|               |   |    |
|---------------|---|----|
| 8.6.2.2       | Resource: Access Control Policy List .....      | 57 |
| 8.6.2.2.1     | Description .....                               | 57 |
| 8.6.2.2.2     | Resource Definition .....                       | 57 |
| 8.6.2.2.3     | Resource Standard Methods .....                 | 57 |
| 8.6.2.2.3.1   | GET .....                                       | 57 |
| 8.6.2.2.4     | Resource Custom Operations .....                | 58 |
| 8.6.3         | Notifications .....                             | 58 |
| 8.6.4         | Data Model .....                                | 58 |
| 8.6.4.1       | General .....                                   | 58 |
| 8.6.4.2       | Structured data types .....                     | 58 |
| 8.6.4.2.1     | Introduction .....                              | 58 |
| 8.6.4.2.2     | Type: AccessControlPolicyList .....             | 58 |
| 8.6.4.2.3     | Type: APIInvokerPolicy .....                    | 59 |
| 8.6.4.2.4     | Type: TimeRangeList .....                       | 59 |
| 8.6.4.3       | Simple data types and enumerations .....        | 59 |
| 8.6.5         | Error Handling .....                            | 59 |
| 8.6.6         | Feature negotiation .....                       | 59 |
| 8.7           | CAPIF_Logging_API_Invocation_API .....          | 59 |
| 8.7.1         | API URI .....                                   | 59 |
| 8.7.2         | Resources .....                                 | 60 |
| 8.7.2.1       | Overview .....                                  | 60 |
| 8.7.2.2       | Resource: Logs .....                            | 60 |
| 8.7.2.2.1     | Description .....                               | 60 |
| 8.7.2.2.2     | Resource Definition .....                       | 60 |
| 8.7.2.2.3     | Resource Standard Methods .....                 | 61 |
| 8.7.2.2.3.1   | POST .....                                      | 61 |
| 8.7.2.2.4     | Resource Custom Operations .....                | 61 |
| 8.7.3         | Notifications .....                             | 61 |
| 8.7.4         | Data Model .....                                | 61 |
| 8.7.4.1       | General .....                                   | 61 |
| 8.7.4.2       | Structured data types .....                     | 62 |
| 8.7.4.2.1     | Introduction .....                              | 62 |
| 8.7.4.2.2     | Type: InvocationLogs .....                      | 62 |
| 8.7.4.2.3     | Type: Log .....                                 | 62 |
| 8.7.4.3       | Simple data types and enumerations .....        | 62 |
| 8.7.5         | Error Handling .....                            | 62 |
| 8.7.6         | Feature negotiation .....                       | 63 |
| 8.8           | CAPIF_Auditing_API .....                        | 63 |
| 8.8.1         | API URI .....                                   | 63 |
| 8.8.2         | Resources .....                                 | 63 |
| 8.8.2.1       | Overview .....                                  | 63 |
| 8.8.2.2       | Resource: All service API invocation logs ..... | 63 |
| 8.8.2.2.1     | Description .....                               | 63 |
| 8.8.2.2.2     | Resource Definition .....                       | 64 |
| 8.8.2.2.3     | Resource Standard Methods .....                 | 64 |
| 8.8.2.2.4     | Resource Custom Operations .....                | 64 |
| 8.8.2.2.4.1   | Overview .....                                  | 64 |
| 8.8.2.2.4.2   | Operation: query .....                          | 64 |
| 8.8.2.2.4.2.1 | Description .....                               | 64 |
| 8.8.2.2.4.2.2 | Operation Definition .....                      | 64 |
| 8.8.3         | Notifications .....                             | 64 |
| 8.8.4         | Data Model .....                                | 65 |
| 8.8.4.1       | General .....                                   | 65 |
| 8.8.4.2       | Structured data types .....                     | 66 |
| 8.8.4.2.1     | Introduction .....                              | 66 |
| 8.8.4.2.2     | Type: LogQuery .....                            | 66 |
| 8.8.4.2.3     | Type: LogData .....                             | 66 |
| 8.8.4.3       | Simple data types and enumerations .....        | 66 |
| 8.8.5         | Error Handling .....                            | 66 |
| 8.8.6         | Feature negotiation .....                       | 66 |
| 9             | AEF API Definition .....                        | 67 |

|   |  |           |
|---|--|-----------|
| 9.1   | AEF_Authentication_API .....                                 | 67        |
| 9.1.1   | API URI .....  | 67        |
| 9.1.2   | Resources .....  | 67        |
| 9.1.2.1   | Overview .....   | 67        |
| 9.1.2.2   | Resource: API invoker authentication profiles .....          | 68        |
| 9.1.2.2.1   | Description .....  | 68        |
| 9.1.2.2.2   | Resource Definition .....                                    | 68        |
| 9.1.2.2.3   | Resource Standard Methods .....                              | 68        |
| 9.1.2.2.3.1   | POST .....   | 68        |
| 9.1.2.2.4   | Resource Custom Operations .....                             | 68        |
| 9.1.3   | Notifications .....  | 68        |
| 9.1.4   | Data Model .....   | 69        |
| 9.1.4.1   | General .....  | 69        |
| 9.1.4.2   | Structured data types .....                                  | 69        |
| 9.1.4.2.1   | Introduction .....   | 69        |
| 9.1.4.2.2   | Type: APIInvokerDetails .....                                | 69        |
| 9.1.4.3   | Simple data types and enumerations .....                     | 69        |
| 9.1.5   | Error Handling .....   | 69        |
| 9.1.6   | Feature negotiation .....                                    | 69        |
| 10  | Security .....   | 69        |
| 10.1  | General .....  | 69        |
| 10.1  | CAPIF-1/1e security .....                                    | 70        |
| 10.2  | CAPIF-2/2e security and securely invoking service APIs ..... | 70        |
| <b>Annex A (normative): OpenAPI specification .....</b> |  | <b>71</b> |
| A.1   | General .....  | 71        |
| A.2   | CAPIF_Discover_Service_API .....                             | 71        |
| A.3   | CAPIF_Publish_Service_API .....                              | 71        |
| A.4   | CAPIF_Events_API .....                                       | 71        |
| A.5   | CAPIF_API_Invoker_Management_API .....                       | 71        |
| A.6   | CAPIF_Authentication_Authorization_API .....                 | 71        |
| A.7   | CAPIF_Access_Control_Policy_API .....                        | 71        |
| A.8   | CAPIF_Logging_API_Invocation_API .....                       | 71        |
| A.9   | CAPIF_Auditing_API .....                                     | 71        |
| A.10  | AEF_Authentication_API .....                                 | 71        |
| <b>Annex B (informative): Change history .....</b>      |  | <b>72</b> |
| History .....   |  | 73        |

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present specification describes the protocol for the Common API Framework (CAPIF) for 3GPP Northbound APIs. The CAPIF and the related stage 2 architecture and functional requirements are defined in 3GPP TS 23.222 [2].

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.222: "Functional architecture and information flows to support Common API Framework for 3GPP Northbound APIs; Stage 2".
- [3] Open API Initiative, "OpenAPI 3.0.0 Specification", <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>.
- [4] IETF RFC 7230: "Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing".
- [5] IETF RFC 7231: "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content".
- [6] IETF RFC 7232: "Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests".
- [7] IETF RFC 7233: "Hypertext Transfer Protocol (HTTP/1.1): Range Requests".
- [8] IETF RFC 7234: "Hypertext Transfer Protocol (HTTP/1.1): Caching".
- [9] IETF RFC 7235: "Hypertext Transfer Protocol (HTTP/1.1): Authentication".
- [10] IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
- [11] IETF RFC 5246, "The Transport Layer Security (TLS) Protocol Version 1.2".
- [12] IETF RFC 7159: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [13] IETF RFC 6455: "The WebSocket Protocol".
- [14] 3GPP TS 29.122: "T8 reference point for northbound Application Programming Interfaces (APIs)".
- [15] 3GPP TS 29.522: "5G System; Network Exposure Function Northbound APIs; Stage 3".
- [16] 3GPP TS 33.122: "Security Aspects of Common API Framework for 3GPP Northbound APIs"

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**API registry:** API registry is a registry maintained by the CAPIF core function to store information about the service APIs based on the data models defined in this specification. The structure of the API registry is out of scope of this specification.

**Subscribed functional entity:** A functional entity that delivers notifications to another functional entity upon subscription of such notifications.

**Subscribing functional entity:** A functional entity that subscribes to another functional entity for notifications.

## 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

|       |                         |
|-------|-------------------------|
| AEF   | API Exposing Function   |
| AMF   | API Management Function |
| APF   | API Publishing Function |
| CAPIF | Common API Framework    |
| CCF   | CAPIF Core Function     |

---

# 4 Overview


## 4.1 Introduction

In 3GPP, there are multiple northbound API-related specifications. To avoid duplication and inconsistency of approaches between different API specifications and to specify common services (e.g. authorization), 3GPP has considered in 3GPP TS 23.222 [2] the development of a common API framework (CAPIF) that includes common aspects applicable to any northbound service APIs.

The present document specifies the APIs needed to support CAPIF.

## 4.2 Service Architecture

3GPP TS 23.222, clause 6 [2] specifies the functional entities and domains of the functional model, which is depicted in Figure 4.2-1, in detail.



**Figure 4.2-1: CAPIF Functional Model**

CAPIF-1 and CAPIF-1e reference points connect an API invoker inside the PLMN Trust Domain and an API invoker outside the PLMN Trust Domain respectively, with the CAPIF core function.

CAPIF-2 and CAPIF-2e reference points connect an API invoker inside the PLMN Trust Domain and an API invoker outside the PLMN Trust Domain respectively, with the API exposing function.

CAPIF-3 reference point connects an API exposing function inside the PLMN Trust Domain with the CAPIF core function.

CAPIF-4 reference point connects an API publishing function inside the PLMN Trust Domain with the CAPIF core function.

CAPIF-5 reference point connects an API management function inside the PLMN Trust Domain with the CAPIF core function.

## 4.3 Functional Entities

### 4.3.1 API invoker

The API invoker is typically provided by a 3<sup>rd</sup> party application provider who has service agreement with PLMN operator. The API invoker may reside within the same trust domain as the PLMN operator network.

The API invoker supports several capabilities such as supporting

- the authentication and obtaining authorization and discovering using CAPIF-1/CAPIF-1e reference point as defined in 3GPP TS 23.222 [2]; and
- invoking the Service APIs using CAPIF-2/CAPIF-2e referenced point as defined in 3GPP TS 23.222 [2], e.g. the T8 interface as defined in 3GPP TS 29.122 [14] or the NEF Northbound interface as defined in 3GPP TS 29.522 [15].

### 4.3.2 CAPIF core function

The CAPIF core function (CCF) supports the following capabilities over CAPIF-1/CAPIF-1e reference point as defined in 3GPP TS 23.222 [2]:

- authenticating the API invoker;
- providing the authorization information; and
- discovery of service API information.

The CAPIF core function supports the following capabilities over CAPIF-3 reference point as defined in 3GPP TS 23.222 [2]:

- providing the service API access policy;
- providing the authentication and authorization information of API invoker for validation;
- logging of service API invocations and
- charging of service API invocations.

The CAPIF core function supports the following capabilities over CAPIF-4 reference point as defined in 3GPP TS 23.222 [2]:

- publishing and storing the service APIs information.

The CAPIF core function supports the following capabilities over CAPIF-5 reference point as defined in 3GPP TS 23.222 [2]:

- providing the service API invocation log for auditing;
- providing monitoring information the status of service APIs and
- storing configurations of the API provider policies.

### 4.3.3 API exposing function

The API exposing function (AEF) is the provider of the Service APIs and is also the service communication entry point of the Service API to the API invokers using CAPIF-2/CAPIF-2e reference point as defined in 3GPP TS 23.222 [2]. The API exposing function consists of capabilities such as authenticating the API invoker, validating the authorization provided by the CAPIF core function and logging the Service API invocations at the CAPIF core function using CAPIF-3 reference point as defined in 3GPP TS 23.222 [2].

According to the distributed deployment scenarios specified in 3GPP TS 23.222 [2], it is possible that the CAPIF can be deployed by splitting the functionality of the API exposing function among multiple API exposing function entities, of which one acts as the entry point. The source API exposing function takes the role of API invoker and communicates with the destination API exposing function over CAPIF-2.

### 4.3.4 API publishing function

The API publishing function (APF) enables the API provider to publish the Service APIs information using CAPIF-4 reference point as defined in 3GPP TS 23.222 [2] in order to enable the discovery of Service APIs by the API invoker.

### 4.3.5 API management function

The API management function (AMF) enables the API provider to perform administration of the Service APIs. The API management function supports several capabilities such as querying the Service API invocation log for auditing, monitoring the events, configuring the API provider policies and monitoring the status of the Service APIs using CAPIF-5 reference point as defined in 3GPP TS 23.222 [2].

## 5 Services offered by the CAPIF Core Function

### 5.1 Introduction of Services

The table 5.1-1 lists the CAPIF Core Function APIs below the service name. A service description subclause for each API gives a general description of the related API.

**Table 5.1-1: List of CAPIF Services**

| Service Name                           | Service Operations                  | Operation Semantics | Consumer(s)  |
|--|-------------------------------------|---------------------|--|
| CAPIF_Discover_Service_API             | Discover_Service_API                | Request/ Response   | AP Invoker   |
| CAPIF_Publish_Service_API              | Publish_Service_API                 | Request/ Response   | API Publishing Function  |
|  | Unpublish_Service_API               | Request/ Response   | API Publishing Function  |
|  | Update_Service_API                  | Request/ Response   | API Publishing Function  |
|  | Get_Service_API                     | Request/ Response   | API Publishing Function  |
| CAPIF_Events_API                       | Event_Subscription                  | Request/ Response   | API Invoker, API Publishing Function, API Management Function, API Exposing Function |
|  | Event_Notification                  | Notify              | API Invoker, API Publishing Function, API Management Function, API Exposing Function |
|  | Event_Unsubscription                | Request/ Response   | API Invoker, API Publishing Function, API Management Function, API Exposing Function |
| CAPIF_API_Invoker_Management_API       | Onboard_API_Invoker                 | Request/ Response   | API Invoker  |
|  | Offboard_API_Invoker                | Request/ Response   | API Invoker  |
| CAPIF_Authentication_Authorization_API | Service_Security_Method_Request     | Request/ Response   | API Invoker  |
|  | Obtain_Authorization                | Request/ Response   | API Invoker  |
|  | Obtain_API_Invoker_Info             | Request/ Response   | API exposing function  |
|  | Invalidate_Authorization            | Request/ Response   | API exposing function  |
| CAPIF_Monitoring_API                   | Event_Subscription                  | Request/ Response   | API Management Function  |
|  | Monitoring_Service_API_Notification | Notify              | API Management Function  |
|  | Event_Unsubscription                | Request/ Response   | API Management Function  |
| CAPIF_Logging_API_Invocation_API       | Log_API_Invocation                  | Request/ Response   | API exposing function  |
| CAPIF_Auditing_API                     | Query_API_Invocation_Log            | Request/ Response   | API management function  |
| CAPIF_Access_Control_Policy_API        | Obtain_Access_Control_Policy        | Request/Response    | API Exposing Function  |

NOTE: The CAPIF Event API can be reused in every API.

### 5.2 CAPIF\_Discovery\_Service\_API

#### 5.2.1 Service Description

##### 5.2.1.1 Overview

The CAPIF discovery service APIs, as defined in 3GPP TS 23.222 [2], allow API invokers via CAPIF-1 and CAPIF-1e reference point to discover service API available at the CAPIF core function.

## 5.2.2 Service Operations

### 5.2.2.1 Introduction

The service operation defined for Discovery\_Service\_API is shown in table 5.2.2.1-1.

**Table 5.2.2.1-1: Operations of the CAPIF\_Discovery\_Service\_API**

| Service operation name | Description  | Initiated by |
|------------------------|--|--------------|
| Discover_Service_API   | This service operation is used by an API invoker to discover service API available at the CAPIF core function. | API invoker  |

### 5.2.2.2 Discover\_Service\_API

#### 5.2.2.2.1 General

This service operation is a custom service operation used by an API invoker to discover service API available at the CAPIF core function.

#### 5.2.2.2.2 API invoker discovering service API using Discover\_Service\_API service operation

To discover service APIs available at the CAPIF core function, the API invoker shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include API invoker Identifier and the API Query.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. verify the identity of the API invoker and check if the API invoker is authorized to discover the service APIs;
2. if the API invoker is authorized to discover the service APIs, the CAPIF core function shall:
  - a. search the CAPIF core function (API registry) for APIs matching the API Query criteria;
  - b. apply the discovery policy, if any, on the search results and filter the search results;
  - c. return the filtered search results as a API List in the response message.

## 5.3 CAPIF\_Publish\_Service\_API

### 5.3.1 Service Description

#### 5.3.1.1 Overview

The CAPIF publish service APIs, as defined in 3GPP TS 23.222 [2], allow API publishing function via CAPIF-4 reference point to publish and manage published service APIs at the CAPIF core function.

## 5.3.2 Service Operations

### 5.3.2.1 Introduction

**Table 5.3.2.1-1: Operations of the CAPIF\_Publish\_Service\_API**

| Service operation name | Description   | Initiated by            |
|------------------------|---|-------------------------|
| Publish_Service_API    | This service operation is used by an API publishing function to publish service APIs on the CAPIF core function.          | API publishing function |
| Unpublish_Service_API  | This service operation is used by an API publishing function to un-publish service APIs from the CAPIF core function.     | API publishing function |
| Retrieve_Service_API   | This service operation is used by an API publishing function to retrieve service APIs from the CAPIF core function.       | API publishing function |
| Update_Service_API     | This service operation is used by an API publishing function to update published service APIs on the CAPIF core function. | API publishing function |

### 5.3.2.2 Publish\_Service\_API

#### 5.3.2.2.1 General

This service operation is used by an API publishing function to publish service APIs on the CAPIF core function.

#### 5.3.2.2.2 API publishing function publishing service APIs on CAPIF core function using Publish\_Service\_API service operation

To publish service APIs at the CAPIF core function, the API publishing function shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include API publishing function Identifier and API Information.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. verify the identity of the API publishing function and check if the API publishing function is authorized to publish service APIs;
2. if the API publishing function is authorized to publish service APIs, the CAPIF core function shall:
  - a. verify the API Information present in the HTTP POST message and add the service APIs in the CAPIF core function (API registry);
  - b. create a new resource as defined in subclause 8.2.3;
  - c. return the CAPIF Resource URI in the response message.

### 5.3.2.3 Unpublish\_Service\_API

#### 5.3.2.3.1 General

This service operation is used by an API publishing function to un-publish service APIs from the CAPIF core function.

#### 5.3.2.3.2 API publishing function un-publishing service APIs from CAPIF core function using Unpublish\_Service\_API service operation

To un-publish service APIs from the CAPIF core function, the API publishing function shall send an HTTP DELETE message using the CAPIF Resource URI received during the publish operation to the CAPIF core function.

Upon receiving the above described HTTP DELETE message, the CAPIF core function shall

1. verify the identity of the API publishing function and check if the API publishing function is authorized to un-publish service APIs;
2. if the API publishing function is authorized to un-publish service APIs, the CAPIF core function shall:

- a. delete the resource pointed by the CAPIF ResourceURI; and
- b. delete the relevant service APIs from the CAPIF core function (API registry).

### 5.3.2.4 Retrieve\_Service\_API

#### 5.3.2.4.1 General

This service operation is used by an API publishing function to retrieve service APIs from the CAPIF core function.

#### 5.3.2.4.2 API publishing function retrieving service APIs from CAPIF core function using Retrieve\_Service\_API service operation

To retrieve information about the published service APIs from the CAPIF core function, the API publishing function shall send an HTTP GET message with the API publishing function Identifier to the CAPIF core function.

Upon receiving the above described HTTP GET message, the CAPIF core function shall

1. verify the identity of the API publishing function and check if the API publishing function is authorized to retrieve information about the published service APIs;
2. if the API publishing function is authorized to retrieve information about the published service APIs, the CAPIF core function shall:
  - a. respond with the API Information associated with the CAPIF Resource Identifier mentioned in the HTTP GET message.

### 5.3.2.5 Update\_Service\_API

#### 5.3.2.5.1 General

This service operation is used by an API publishing function to update published service APIs on the CAPIF core function.

#### 5.3.2.5.2 API publishing function updating published service APIs on CAPIF core function using Update\_Service\_API service operation

To update information of published service APIs, the API publishing function shall send an HTTP PUT message with the relevant CAPIF Resource URI and API publishing function Identifier to the CAPIF core function. The body of the HTTP PUT message shall include updated API Information.

Upon receiving the above described HTTP PUT message, the CAPIF core function shall

1. verify the identity of the API publishing function and check if the API publishing function is authorized to update information of published service APIs;
2. if the API publishing function is authorized to update information of published service APIs, the CAPIF core function shall:
  - a. verify the API Information present in the HTTP PUT message and replace the service APIs in the CAPIF core function (API registry);
  - b. replace the existing resource accordingly.

## 5.4 CAPIF\_Events\_API

### 5.4.1 Service Description

#### 5.4.1.1 Overview

The CAPIF events APIs, as defined in 3GPP TS 23.222 [2], allow an API invoker via CAPIF-1 reference point, API exposure function via CAPIF-3 reference point, API publishing function via CAPIF-4 reference point and API management function via CAPIF-5 reference point to subscribe to and unsubscribe from CAPIF events and to receive notifications from CAPIF core function.

NOTE: The functional elements listed above are referred to as subscribing functional entity in the service operations described in the subclauses below.

## 5.4.2 Service Operations

### 5.4.2.1 Introduction

**Table 5.4.2.1-1: Operations of the CAPIF\_Events\_API**

| Service operation name | Description   | Initiated by                  |
|------------------------|---|-------------------------------|
| Event_Subscription     | This service operation is used by a Subscribing functional entity to subscribe to CAPIF events.                 | Subscribing functional entity |
| Event_Unsubscription   | This service operation is used by a Subscribing functional entity to unsubscribe from CAPIF events              | Subscribing functional entity |
| Event_Notification     | This service operation is used by CAPIF core function to send a notification to a Subscribing functional entity | CAPIF core function           |

### 5.4.2.2 Event\_Subscription\_API

#### 5.4.2.2.1 General

This service operation is used by a Subscribing functional entity to subscribe to CAPIF events.

#### 5.4.2.2.2 Subscribing to CAPIF events using Event\_Subscription service operation

To subscribe to CAPIF events, the Subscribing functional entity shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include Subscribing functional entity's Identifier, Event Type and a Notification Destination URI.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. verify the identity of the Subscribing functional entity and check if the Subscribing functional entity is authorized to subscribe to the CAPIF events mentioned in the HTTP POST message;
2. if the Subscribing functional entity is authorized to subscribe to the CAPIF events, the CAPIF core function shall:
  - a. create a new resource as defined in subclause 8.3.3.
  - b. return the CAPIF Resource URI in the response message.

### 5.4.2.3 Event\_Unsubscription\_API

#### 5.4.2.3.1 General

This service operation is used by a Subscribing functional entity to un-subscribe from CAPIF events.

#### 5.4.2.3.2 Unsubscribing from CAPIF events using Event\_Unsubscription service operation

To unsubscribe from CAPIF events, the Subscribing functional entity shall send an HTTP DELETE message using the CAPIF Resource Identifier to the CAPIF core function.

Upon receiving the HTTP DELETE message, the CAPIF core function shall delete the resource pointed by the CAPIF Resource URI.

### 5.4.2.4 Event\_Notification\_API

#### 5.4.2.4.1 General

This service operation is used by CAPIF core function to send a notification to a Subscribing functional entity

#### 5.4.2.4.2 Notifying CAPIF events using Event\_Notification service operation

To notify CAPIF events, the CAPIF core function shall send an HTTP POST message using the Notification Destination URI received in the subscription request. The body of the HTTP POST message shall include an Event Notification and CAPIF Resource URI.

Upon receiving the HTTP POST message, the Subscribing functional entity shall process the Event Notification.

## 5.5 CAPIF\_API\_Invoker\_Management\_API

### 5.5.1 Service Description

#### 5.5.1.1 Overview

The CAPIF API invoker management APIs, as defined in 3GPP TS 23.222 [2], allow API invokers via CAPIF-1 and CAPIF-1e reference point to on-board and off-board itself as a recognized user of the CAPIF.

### 5.5.2 Service Operations

#### 5.5.2.1 Introduction

**Table 5.5.2.1-1: Operations of the CAPIF\_API\_Invoker\_Management\_API**

| Service operation name | Description  | Initiated by        |
|------------------------|--|---------------------|
| Onboard_API_Invoker    | This service operation is used by an API invoker to on-board itself as a recognized user of CAPIF            | API invoker         |
| Offboard_API_Invoker   | This service operation is used by an API invoker to off-board itself as a recognized user of CAPIF           | API invoker         |
| Onboard_Notification   | This service operation is used by CAPIF core function to send a on-boarding notification to the API invoker. | CAPIF core function |

#### 5.5.2.2 Onboard\_API\_Invoker\_API

##### 5.5.2.2.1 General

This service operation is used by an API invoker to on-board itself as a recognized user of CAPIF

##### 5.5.2.2.2 API invoker on-boarding itself as a recognized user of CAPIF using Onboard\_API\_Invoker service operation

To on-board itself as a recognized user of the CAPIF, the API invoker shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include API invoker Enrolment Details, API List and a Notification Destination URI for on-boarding notification.

Upon receiving the above described HTTP POST message, the CAPIF core function shall check if the CAPIF core function can determine authorization of the request and on-board the API invoker automatically. If the CAPIF core function:

1. can determine authorization of the request and on-board the API invoker automatically, the CAPIF core function:
  - a. shall process the API invoker Enrolment Details and the API List received in the HTTP POST message and determine if the request sent by the API invoker is authorized or not;
  - b. if the API invoker's request is authorized, the CAPIF core function shall:
    - i. create the API invoker Profile consisting of an API invoker Identifier, Authentication Information, Authorization Information and CAPIF Identity Information;
    - ii. verify the API List present in the HTTP POST message and create a API List of APIs the API invoker is allowed to access;
    - iii. create a new resource as defined in subclause 8.4.3;

- iv. return the API invoker Profile, API List of APIs the API invoker is allowed to access and the CAPIF Resource URI in the response message.
2. cannot determine authorization of the request to on-board the API invoker automatically, the CAPIF core function:
    - a. shall acknowledge the receipt of the on-boarding request to the API invoker.
    - b. shall request the CAPIF administrator to validate the on-boarding request or the API management to validate the on-boarding request by sharing the API invoker Enrolment Details and the API List received in the HTTP POST message;
    - b. on receiving confirmation of successful validation of the on-boarding request from the CAPIF administrator or the API management, the CAPIF core function shall:
      - i. create the API invoker Profile consisting of an API invoker Identifier, Authentication Information, Authorization Information and CAPIF Identity Information;
      - ii. create a new resource as defined in subclause 8.4.3;
      - iii. deliver the API invoker Profile, API List of APIs the API invoker is allowed to access and the CAPIF Resource URI to the API invoker in a notification.

NOTE 1: How the CAPIF core function determines that the CAPIF core function can process the request and on-board the API invoker automatically is out-of-scope of this specification.

NOTE 2: How the CAPIF core function determines that the API invoker's request to on-board is authorized is specified in 3GPP TS 33.122 [16].

NOTE 3: Interactions between the CAPIF core function and the CAPIF administrator or the API management is out-of-scope of this specification.

## 5.5.2.3 Offboard\_API\_Invoker\_API

### 5.5.2.3.1 General

This service operation is used by an API invoker to off-board itself as a recognized user of CAPIF

### 5.5.2.3.2 API invoker off-boarding itself as a recognized user of CAPIF using Offboard\_API\_Invoker service operation

To off-board itself as a recognized user of the CAPIF, the API invoker shall send an HTTP DELETE message using the CAPIF Resource Identifier received during the on-boarding to the CAPIF core function.

Upon receiving the HTTP DELETE message, the CAPIF core function shall delete the resource representation pointed by the CAPIF Resource Identifier and shall delete the related API invoker profile.

## 5.6 CAPIF\_Authentication\_Authorization\_API

### 5.6.1 Service Description

#### 5.6.1.1 Overview

The CAPIF security APIs, as defined in 3GPP TS 23.222 [2], allow:

- API invokers via CAPIF-1/1e reference points to negotiate the service security method and obtain authorization for invoking service APIs; and
- API exposing function via CAPIF-3 reference point to obtain authentication information of the API invoker for authentication of the API invoker.

## 5.6.2 Service Operations

### 5.6.2.1 Introduction

**Table 5.6.2.1-1: Operations of the CAPIF\_Security\_API**

| Service operation name          | Description  | Initiated by          |
|---------------------------------|--|-----------------------|
| Service_Security_Method_Request | This service operation is used by an API invoker to negotiate and obtain information about service API security method for itself with CAPIF core function. This information is used by API invoker for service API invocations. | API invoker           |
| Obtain_Authorization            | This service operation is used by an API invoker to obtain authorization to access service APIs.   | API invoker           |
| Obtain_API_Invoker_Info         | This service operation is used by an API exposing function to obtain the authentication or authorization information related to an API invoker.  | API exposing function |
| Invalidate_Authorization        | This service operation is used by an API exposing function to invalidate the authorization of an API invoker.  | API exposing function |

### 5.6.2.2 Service\_Security\_Method\_Request\_API

#### 5.6.2.2.1 General

This service operation is used by an API invoker to negotiate and obtain service API security method from the CAPIF core function. The information received by API invoker shall be used for authentication with the API exposing function.

#### 5.6.2.2.2 Request service API security method from CAPIF using Service\_Security\_Method\_Request service operation

To negotiate and obtain service API security method information from the CAPIF core function, the API invoker shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include Security Method Request and a Notification Destination URI for security related notifications. The Security Method Request from the API invoker contains the unique interface details of the service APIs and a preferred method for each unique service API interface.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. determine the security method for each service API interface as specified in 3GPP TS 33.122 [16];
2. store the Notification Destination URI for security related notification.
3. create a new resource as defined in subclause 8.4.3;
4. return the security method information and the CAPIF Resource URI in the response message; and

#### 5.6.2.2.3 Obtain authorization using Obtain\_Authorization service operation

To obtain authorization information from the CAPIF core function to invoke service APIs, the API invoker shall send an HTTP GET message to the authorization endpoint of the CAPIF core function with the authorization parameters.

Upon receiving the above described HTTP GET message, the CAPIF core function shall:

1. determine the authorization rights of API invoker for the service API;
2. generate authorization information as specified in 3GPP TS 33.122 [16];
3. return the authorization information in the response message.

**Editor's Note: specification of authorization endpoint of the CAPIF core function and the token request is FFS.**

#### 5.6.2.2.4 Obtain API invoker's security information using Obtain\_API\_Invoker\_Info service operation

To obtain authentication or authorization information from the CAPIF core function to authenticate or authorize an API invoker, the API exposing function shall send an HTTP GET message to the CAPIF core function with the API invoker ID and an indication to request authentication and authorization information.

Upon receiving the above described HTTP GET message, the CAPIF core function shall:

1. determine the security information of API invoker for all the service API interfaces;
2. return the security information in the response message.

#### 5.6.2.2.5 Invalidate authorization using Invalidate\_Authorization service operation

To invalidate authorization of an API invoker, the API exposing function shall send an HTTP DELETE message to the CAPIF core function using the API invoker ID.

Upon receiving the above described HTTP DELETE message, the CAPIF core function shall delete the resource representation pointed by the API invoker ID and shall notify the API invoker of the authorization invalidation using the Notification Destination URI received in the Service\_Security\_Method\_Request message.

## 5.7 CAPIF\_Monitoring\_API

The CAPIF monitoring API as defined in 3GPP TS 23.222 [2], allow the API management function via CAPIF-5 reference point to monitor service API invocations and receive such monitoring events from the CAPIF core function.

The CAPIF\_Monitoring\_API shall use the CAPIF\_Events\_API as described in subclause 8.3 by setting the CAPIFEvent to "Monitoring service API" as described in subclause 8.3.6.3.3.

## 5.8 CAPIF\_Logging\_API\_Invocation\_API

### 5.8.1 Service Description

#### 5.8.1.1 Overview

The Logging API invocations APIs, as defined in 3GPP TS 23.222 [2], allow API exposing functions via CAPIF-3 reference point to log the information related to service API invocations on the CAPIF core function.

### 5.8.2 Service Operations

#### 5.8.2.1 Introduction

**Table 5.8.2.1-1: Operations of the CAPIF\_Logging\_API\_Invocation\_API**

| Service operation name | Description  | Initiated by          |
|------------------------|--|-----------------------|
| Log_API_Invocation     | This service operation is used by an API exposing function to log API invocation information on CAPIF core function. | API exposing function |

#### 5.8.2.2 Log\_API\_Invocation\_API

##### 5.8.2.2.1 General

This service operation is used by an API exposing function to log API invocation information on CAPIF core function.

##### 5.8.2.2.2 Logging service API invocations using Log\_API\_Invocation service operation

To log service API invocations at the CAPIF core function, the API exposing function shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include API exposing function identity information and API invocation log information.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. verify the identity of the API exposing function and check if the API exposing function is authorized to create service API invocation logs;
2. if the API exposing function is authorized to create service API invocation logs, the CAPIF core function shall:
  - a. process the API invocation log information received in the HTTP POST message and store the API invocation log information in the API repository;
  - b. create a new resource as defined in subclause 8.7.3; and
  - c. return the CAPIF Resource Identifier in the response message.

## 5.9 CAPIF\_Auditing\_API

### 5.9.1 Service Description

#### 5.9.1.1 Overview

The Auditing API, as defined in 3GPP TS 23.222 [2], allows API management functions via CAPIF-5 reference point to query the log information stored on the CAPIF core function.

### 5.9.2 Service Operations

#### 5.9.2.1 Introduction

**Table 5.9.2.1-1: Operations of the CAPIF\_Auditing\_API**

| Service operation name | Description  | Initiated by            |
|------------------------|--|-------------------------|
| Query_Invocation_Logs  | This service operation is used by an API management function to query API invocation information logs stored on CAPIF core function. | API management function |

#### 5.9.2.2 Query\_Invocation\_Logs\_API

##### 5.9.2.2.1 General

This service operation is a custom service operation used by an API management function to query API invocation information logs stored on CAPIF core function.

##### 5.9.2.2.2 Query API invocation information logs using Query\_Invocation\_Logs service operation

To query service API invocation logs at the CAPIF core function, the API management function shall send an HTTP POST message to the CAPIF core function. The body of the HTTP POST message shall include the API management function identity information and the log query.

Upon receiving the above described HTTP POST message, the CAPIF core function shall:

1. verify the identity of the API management function and check if the API management function is authorized to query the service API invocation logs;
2. if the API management function is authorized to query the service API invocation logs, the CAPIF core function shall:
  - a. search the API invocation logs for logs matching the Log Query criteria; and
  - b. return the search results in the response message.

## 5.10 CAPIF\_Access\_Control\_Policy\_API

### 5.10.1 Service Description

#### 5.10.1.1 Overview

The CAPIF access control policy APIs allow API exposing function via CAPIF-3 reference point to obtain the service API access policy from the CAPIF core function.

### 5.10.2 Service Operations

#### 5.10.2.1 Introduction

**Table 5.3.2.1-1: Operations of the CAPIF\_Access\_Control\_Policy\_API**

| Service operation name       | Description  | Initiated by          |
|------------------------------|--|-----------------------|
| Obtain_Access_Control_Policy | This service operation is used by an API exposing function to obtain the access control policy from the CAPIF core function. | API exposing function |

#### 5.10.2.2 Obtain\_Access\_Control\_Policy

##### 5.10.2.2.1 General

This service operation is used by an API exposing function to obtain the access control policy from the CAPIF core function.

##### 5.10.2.2.2 API exposing function obtaining access control policy from the CAPIF core function using Obtain\_Access\_Control\_Policy service operation

To obtain the access control policy from the CAPIF core function, the API exposing function shall send an HTTP GET message to the CAPIF core function with the API exposing function Identifier and API identification.

Upon receiving the above described HTTP GET message, the CAPIF core function shall

1. verify the identity of the API exposing function and check if the API exposing function is authorized to obtain the access control policy corresponding to the API identification;
2. if the API exposing function is authorized to obtain the access control policy, the CAPIF core function shall respond with the access control policy information corresponding to the API identification in the HTTP GET message.

### 5.10.3 Related Events

The CAPIF\_Access\_Control\_Policy\_API supports the subscription and notification of the status of access control information via the CAPIF\_Events\_API. The related events are specified in subclause 8.3.6.3.3.

---

## 6 Services offered by the API exposing function

### 6.1 Introduction of Services

The table 6.1-1 lists the API exposing function APIs below the service name. A service description subclause for each API gives a general description of the related API.

**Table 6.1-1: List of AEF Services**

| Service Name           | Service Operations                | Operation Semantics | Consumer(s) |
|------------------------|-----------------------------------|---------------------|-------------|
| AEF_Authentication_API | Authentication_Initiation_Request | Request/ Response   | API Invoker |

## 6.2 AEF\_Authentication\_API

### 6.2.1 Service Description

#### 6.2.1.1 Overview

The AEF authentication API, allows an API invokers via CAPIF-2/2e reference points to request API exposing function to ensure that authentication parameters necessary for authentication of the API invoker are available with the API exposing function. If the necessary authentication parameters are not available, the API exposing function fetches necessary authentication parameters from CAPIF core function to authenticate the API invoker.

### 6.2.2 Service Operations

#### 6.2.2.1 Introduction

The service operation defined for AEF\_Authentication\_Authorization\_API is shown in table 6.2.2.1-1.

**Table 6.2.2.1-1: Operations of the AEF\_Authentication\_API**

| Service operation name            | Description   | Initiated by |
|-----------------------------------|---|--------------|
| Authentication_Initiation_Request | This service operation is used by an API invoker to request API exposing function to fetch necessary authentication parameters from CAPIF core function to authenticate the API invoker | API invoker  |

#### 6.2.2.2 Authentication\_Initiation\_Request\_API

##### 6.2.2.2.1 General

This service operation is used by an API invoker to initiate authentication with the API exposing function. On receiving the Authentication\_Initiation\_Request the API exposing function fetches the authentication information of the API invoker from the CAPIF core function, if required.

##### 6.2.2.2.2 API invoker initiating authentication using Authentication\_Initiation\_Request service operation

To initiate authentication with the API exposing function, the API invoker shall send an HTTP POST message to the API exposing function. The body of the HTTP POST message shall contain the API invoker ID.

Upon receiving the above described HTTP POST message, the API exposing function shall:

1. check if the credentials of the API invoker for authentication are available with the API exposing function. if the credentials of the API invoker for authentication are not available, the API exposing function shall use the service defined in subclause 5.6.2.2.4 to fetch the credentials from the CAPIF core function.
2. once the credentials of the API invoker for authentication are available, the API exposing function shall:
  - a. create a resource with the information as described in 9.1.3;
  - b. return the resource URI in the response message.

## 7 CAPIF Design Aspects Common for All APIs

### 7.1 General

CAPIF APIs are RESTful APIs that allow secure access to the capabilities provided by CAPIF.

This document specifies the procedures triggered at different functional entities as a result of API invocation requests and event notifications. The stage-2 level requirements and signalling flows are defined in 3GPP TS 23.222 [2].

Several design aspects, as mentioned in the following subclauses, are specified in 3GPP TS 29.122 [14] and referenced by this specification.

## 7.2 Data Types

### 7.2.1 General

This clause defines structured data types, simple data types and enumerations that are applicable to several APIs defined in the present specification and can be referenced from data structures defined in the subsequent clauses.

In addition, data types that are defined in OpenAPI 3.0.0 Specification [3] can also be referenced from data structures defined in the subsequent clauses.

**NOTE:** As a convention, data types in the present specification are written with an upper-case letter in the beginning. Parameters are written with a lower-case letter in the beginning. As an exception, data types that are also defined in OpenAPI 3.0.0 Specification [3] can use a lower-case case letter in the beginning for consistency.

Table 7.2.1-1 specifies data types re-used by the CAPIF from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the CAPIF.

**Table 7.2.1-1: Re-used Data Types**

| Data type            | Reference           | Comments  |
|----------------------|---------------------|---|
| Uri                  | 3GPP TS 29.122 [14] |   |
| TestNotification     | 3GPP TS 29.122 [14] | Following clarifications apply:<br>- The SCEF is the CAPIF core function; and<br>- The SCS/AS is the Subscribing functional entity. |
| WebsocketNotifConfig | 3GPP TS 29.122 [14] | Following clarifications apply:<br>- The SCEF is the CAPIF core function; and<br>- The SCS/AS is the Subscribing functional entity. |

### 7.2.2 Referenced structured data types

**Editor's Note:** Structured data types applicable to several CAPIF APIs will be defined in this subclause.

### 7.2.3 Referenced Simple data types and enumerations

**Editor's Note:** Simple data types and enumerations applicable to several CAPIF APIs will be defined in this subclause.

Following simple data types defined in Table 7.2.3.1-1 are applicable to several APIs in this document:

**Table 7.2.3.1-1: Simple data types applicable to several APIs**

| Type name       | Description  |
|-----------------|--|
| CAPIFResourceId | string chosen by the CAPIF core function to serve as identifier in a resource URI. |

## 7.3 Usage of HTTP

For CAPIF APIs, support of HTTP/1.1 (IETF RFC 7230 [4], IETF RFC 7231 [5], IETF RFC 7232 [6], IETF RFC 7233 [7], IETF RFC 7234 [8] and IETF RFC 7235 [9]) over TLS (IETF RFC 5246 [11]) is mandatory and support of HTTP/2 (IETF RFC 7540 [10]) over TLS (IETF RFC 5246 [11]) is recommended.

A functional entity desiring to use HTTP/2 shall use the HTTP upgrade mechanism to negotiate applicable HTTP version as described in IETF RFC 7540 [10].

## 7.4 Content type

The bodies of HTTP request and successful HTTP responses shall be encoded in JSON format (see IETF RFC 7159 [12]).

The MIME media type that shall be used within the related Content-Type header field is "application/json", as defined in IETF RFC 7159 [12].

NOTE: This release only supports the content type JSON.

## 7.5 URI structure

All resource URIs of CAPIF APIs should have the following root structure:

**{apiRoot}/{apiName}/{apiVersion}/**

"apiRoot" is configured by means outside the scope of the present document. It includes the scheme ("https"), host and optional port, and an optional prefix string. "apiName" and "apiVersion" shall be set dependent on the API, as defined in the corresponding subclauses below.

All resource URIs in the subclauses below are defined relative to the above root URI.

NOTE 1: The "apiVersion" will only be increased if the new API version contains backward incompatible changes. Otherwise, the supported feature mechanism defined in subclause 7.8 can be used to negotiate extensions.

NOTE 2: A different root structure can be used when the resource URI is preconfigured in the API invoking entity.

The root structure may be followed by "apiSpecificSuffixes" that are dependent on the API and are defined separately for each API where they apply:

**{apiRoot}/{apiName}/{apiVersion}/{apiSpecificSuffixes}**

## 7.6 Notifications

The functional entities

- shall support the delivery of notifications using a separate HTTP connection towards an address;
- may support testing delivery of notifications; and
- may support the delivery of notification using WebSocket protocol (see IETF RFC 6455 [13]),

as described in 3GPP TS 29.122 [14], with the following clarifications:

- the SCEF is the CAPIF core function; and
- the SCS/AS is the Subscribing functional entity.

## 7.7 Error handling

Response bodies for error handling, as described in 3GPP TS 29.122 [14], are applicable to all APIs in the present specification unless specified otherwise, with the following clarifications:

- the SCEF is the CAPIF core function; and
- the SCS/AS is the functional entity invoking an API.

## 7.8 Feature negotiation

The functional entity invoking an API (i.e. the API invoker, the API exposing function, the API publishing function or the API management function) and the CAPIF core function use feature negotiation procedures defined in 3GPP TS 29.122 [14] to negotiate the supported features, with the following clarifications:

- The SCEF is the CAPIF core function; and
- The SCS/AS is the functional entity invoking an API.

## 7.9 HTTP headers

The HTTP headers described in 3GPP TS 29.122 [14] are applicable to all APIs in this document.

## 8 CAPIF API Definition

### 8.1 CAPIF\_Discovery\_Service\_API


#### 8.1.1 API URI

The request URI used in each HTTP request from the API invoker towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "service-apis".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.1.2.

#### 8.1.2 Resources

##### 8.1.2.1 Overview



**Figure 8.1.2.1-1: Resource URI structure of the CAPIF\_Discovery\_Service\_API**

Table 8.1.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.1.2.1-1: Resources and methods overview**

| Resource name              | Resource URI  | HTTP method or custom operation | Description                     |
|----------------------------|---|---------------------------------|---------------------------------|
| All published service APIs | {apiRoot}<br>/service-apis/v1<br>/allServiceApis/discover | discover<br>(POST)              | Discover published service APIs |

#### 8.1.2.2 Resource: All published service APIs

##### 8.1.2.2.1 Description

The All published service APIs resource represents all published service APIs on a CAPIF core function.

##### 8.1.2.2.2 Resource Definition

Resource URI: **{apiRoot}/service-apis/v1/allServiceApis**

This resource shall support the resource URI variables defined in table 8.1.2.2.2-1.

**Table 8.1.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition        |
|---------|-------------------|
| apiRoot | See subclause 7.5 |

### 8.1.2.2.3 Resource Standard Methods

None.

### 8.1.2.2.4 Resource Custom Operations

#### 8.1.2.2.4.1 Overview

**Table 8.1.2.2.4.1-1: Custom operations**

| Custom operation URI                              | Mapped HTTP method | Description                     |
|---|--------------------|---------------------------------|
| {apiRoot}/service-apis/v1/allServiceApis/discover | POST               | Discover published service APIs |

#### 8.1.2.2.4.2 Operation: discover

##### 8.1.2.2.4.2.1 Description

Discover custom operation is used by an API invoker to discover service API available at the CAPIF core function.

##### 8.1.2.2.4.2.2 Operation Definition

This operation shall support the URI query parameters specified in table 8.1.2.2.4.2.2-1.

**Table 8.1.2.2.4.2.2-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This operation shall support the request data structures specified in table 8.1.2.2.4.2.2-2 and the response data structure and response codes specified in table 8.1.2.2.4.2.2-3.

**Table 8.1.2.2.4.2.2-2: Data structures supported by the POST Request Body on this resource**

| Data type | P | Cardinality | Description   |
|-----------|---|-------------|---|
| APIQuery  | M | 1           | Query parameters to discover the published service APIs |

**Table 8.1.2.2.4.2.2-3: Data structures supported by the POST Response Body on this resource**

| Data type      | P | Cardinality | Response codes | Description                                       |
|----------------|---|-------------|----------------|---|
| DiscoveredAPIs | M | 1..N        | 200 OK         | Discovered APIs as result of the search operation |

## 8.1.3 Notifications

None.

## 8.1.4 Data Model

### 8.1.4.1 General

This subclause specifies the application data model supported by the API.

Table 8.1.4.1-1 specifies the data types defined for the CAPIF service based interface protocol.

**Table 8.1.4.1-1: Specific Data Types**

| Data type     | Section defined | Description  | Applicability |
|---------------|-----------------|--|---------------|
| APIQuery      | 8.1.4.2.2       | Query parameters for discovery of the service APIs |               |
| DiscoveredAPI | 8.1.4.2.3       | Definition of the service API                      |               |

Table 8.1.4.1-2 specifies data types re-used by the CAPIF\_Discovery\_Service\_API service:

**Table 8.1.4.1-2: Re-used Data Types**

| Data type             | Reference           | Comments                       | Applicability |
|-----------------------|---------------------|--------------------------------|---------------|
| ServiceAPIDescription | Subclause 8.2.4.2.2 | Description of the service API |               |
| InterfaceDescription  | Subclause 8.2.4.2.3 | Name of the protocol           |               |
| Protocol              | Subclause 8.2.4.3.3 | Protocol                       |               |
| DataFormat            | Subclause 8.2.4.3.4 | Data format                    |               |

## 8.1.4.2 Structured data types

### 8.1.4.2.1 Introduction

#### 8.1.4.2.2 Type: APIQuery

**Table 8.1.4.2.2-1: Definition of type APIQuery**

| Attribute name       | Data type            | P | Cardinality | Description  | Applicability |
|----------------------|----------------------|---|-------------|--|---------------|
| apiInvokerId         | string               | M | 1           | String identifying the API invoker assigned by the CAPIF core function |               |
| serviceName          | string               | O | 0..1        | Name of the service  |               |
| apiName              | string               | O | 0..1        | API name   |               |
| apiVersion           | string               | O | 0..1        | API version  |               |
| uri                  | Uri                  | O | 0..1        | Uri of the API   |               |
| protocol             | Protocol             | O | 0..1        | Protocol used by the API.  |               |
| interfaceDescription | InterfaceDescription | O | 0..N        | Interface details  |               |
| dataFormat           | DataFormat           | O | 0..1        | Data formats used by the API   |               |
| description          | string               | O | 0..1        | Text description of the API  |               |

#### 8.1.4.2.3 Type: DiscoveredAPIs

**Table 8.1.4.2.3-1: Definition of type DiscoveredAPIs**

| Attribute name        | Data type             | P | Cardinality | Description   | Applicability |
|-----------------------|-----------------------|---|-------------|---|---------------|
| apild                 | string                | M | 1           | Identifier of the service API                               |               |
| serviceAPIDescription | ServiceAPIDescription | O | 0..1        | Description of the service API as published by the service. |               |

### 8.1.4.3 Simple data types and enumerations

None.

## 8.1.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.1.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8.

**Table 8.1.6-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

## 8.2 CAPIF\_Publish\_Service\_API


### 8.2.1 API URI

The request URI used in each HTTP request from the API publishing function towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "published-apis".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.2.2.

### 8.2.2 Resources

#### 8.2.2.1 Overview



**Figure 8.2.2.1-1: Resource URI structure of the CAPIF\_Publish\_Service\_API**

Table 8.2.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.2.2.1-1: Resources and methods overview**

| Resource name                | Resource URI  | HTTP method or custom operation | Description                         |
|------------------------------|---|---------------------------------|-------------------------------------|
| APF published APIs           | {apiRoot}<br>/published-apis/v1<br>/{apfId}/serviceApis                         | POST                            | Publish a new API                   |
|                              |   | GET                             | Retrieve all published service APIs |
| Individual APF published API | {apiRoot}<br>/api-invocation-logs/v1<br>/{apfId}/serviceApis<br>/{serviceApiId} | GET                             | Retrieve a published service API    |
|                              |   | PUT                             | Update a published service API      |
|                              |   | DELETE                          | Unpublish a published service API   |

## 8.2.2.2 Resource: APF published APIs

### 8.2.2.2.1 Description

The APF published APIs resource represents all published service APIs of a API publishing function.

### 8.2.2.2.2 Resource Definition

Resource URI: `{apiRoot}/published-apis/v1/{apfId}/serviceApis`

This resource shall support the resource URI variables defined in table 8.2.2.2.2-1.

**Table 8.2.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition                              |
|---------|---|
| apiRoot | See subclause 7.5                       |
| apfId   | Identity of the API publishing function |

### 8.2.2.2.3 Resource Standard Methods

#### 8.2.2.2.3.1 POST

This method shall support the URI query parameters specified in table 8.2.2.2.3.1-1.

**Table 8.2.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.2.2.2.3.1-2 and the response data structures and response codes specified in table 8.2.2.2.3.1-3.

**Table 8.2.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type             | P | Cardinality | Description                                   |
|-----------------------|---|-------------|---|
| ServiceAPIDescription | M | 1           | Definition of the service API being published |

**Table 8.2.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type             | P | Cardinality | Response codes | Description  |
|-----------------------|---|-------------|----------------|--|
| ServiceAPIDescription | M | 1           | 201<br>Created | Service API published successfully.<br><br>The URI of the created resource shall be returned in the "Location" HTTP header |

#### 8.2.2.2.3.2 GET

This method shall support the URI query parameters specified in table 8.2.2.2.3.2-1.

**Table 8.2.2.2.3.2-1: URI query parameters supported by the GET method on this resource**

| Name  | Data type | P | Cardinality | Description                                    |
|-------|-----------|---|-------------|--|
| apfId | string    | M | 1           | String identifying the API publishing function |

This method shall support the request data structures specified in table 8.2.2.2.3.2-2 and the response data structures and response codes specified in table 8.2.2.2.3.2-3.

**Table 8.2.2.3.2-2: Data structures supported by the GET Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.2.2.3.1-3: Data structures supported by the GET Response Body on this resource**

| Data type             | P | Cardinality | Response codes | Description  |
|-----------------------|---|-------------|----------------|--|
| ServiceAPIDescription | O | 0..N        | 200 OK         | Definition of all service API(s) published by the API publishing function. |

#### 8.2.2.2.4 Resource Custom Operations

None.

### 8.2.2.3 Resource: Individual APF published API

#### 8.2.2.3.1 Description

The Individual APF published API resource represents an individual published service API.

#### 8.2.2.3.2 Resource Definition

Resource URI: **{apiRoot}/published-apis/v1/{apfld}/serviceApis/{serviceApiId}**

This resource shall support the resource URI variables defined in table 8.2.2.3.2-1.

**Table 8.2.2.3.2-1: Resource URI variables for this resource**

| Name         | Definition   |
|--------------|--|
| apiRoot      | See subclause 7.5                                      |
| apfld        | Identity of the API publishing function                |
| serviceApild | String identifying an individual published service API |

#### 8.2.2.3.3 Resource Standard Methods

##### 8.2.2.3.3.1 GET

This method shall support the URI query parameters specified in table 8.2.2.3.3.1-1.

**Table 8.2.2.3.3.1-1: URI query parameters supported by the GET method on this resource**

| Name  | Data type | P | Cardinality | Description                                    |
|-------|-----------|---|-------------|--|
| apfld | string    | M | 1           | String identifying the API publishing function |

This method shall support the request data structures specified in table 8.2.2.3.3.1-2 and the response data structures and response codes specified in table 8.2.2.3.3.1-3.

**Table 8.2.2.3.3.1-2: Data structures supported by the GET Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.2.2.3.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type             | P | Cardinality | Response codes | Description   |
|-----------------------|---|-------------|----------------|---|
| ServiceAPIDescription | O | 0..N        | 200 OK         | Definition of all service API published by the API publishing function. |

## 8.2.2.3.3.2 PUT

This method shall support the URI query parameters specified in table 8.2.2.3.3.2-1.

**Table 8.2.2.3.3.2-1: URI query parameters supported by the PUT method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.2.2.3.3.2-2 and the response data structures and response codes specified in table 8.2.2.3.3.2-3.

**Table 8.2.2.3.3.2-2: Data structures supported by the PUT Request Body on this resource**

| Data type             | P | Cardinality | Description                            |
|-----------------------|---|-------------|--|
| ServiceAPIDescription | M | 1           | Updated definition of the service API. |

**Table 8.2.2.3.3.2-3: Data structures supported by the PUT Response Body on this resource**

| Data type             | P | Cardinality | Response codes | Description  |
|-----------------------|---|-------------|----------------|--|
| ServiceAPIDescription | M | 1           | 200 OK         | Definition of the service API updated successfully.. |

## 8.2.2.3.3.3 DELETE

This method shall support the URI query parameters specified in table 8.2.2.3.3.3-1.

**Table 8.2.2.3.3.3-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.2.2.3.3.3-2 and the response data structures and response codes specified in table 8.2.2.3.3.3-3.

**Table 8.2.2.3.3.3-2: Data structures supported by the DELETE Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.2.2.3.3.3-3: Data structures supported by the DELETE Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description  |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The individual published service API matching the serviceApild is deleted. |

## 8.2.2.3.4 Resource Custom Operations

None.

## 8.2.3 Notifications

None.

## 8.2.4 Data Model

### 8.2.4.1 General

This subclause specifies the application data model supported by the API.

Table 8.2.4.1-1 specifies the data types defined for the CAPIF service based interface protocol.

**Table 8.2.4.1-1: Specific Data Types**

| Data type             | Section defined | Description                      | Applicability |
|-----------------------|-----------------|----------------------------------|---------------|
| ServiceAPIDescription | 8.2.4.2.2       | Definition of the service API    |               |
| InterfaceDescription  | 8.2.4.2.3       | Description of the API interface |               |

Table 8.2.4.1-2 specifies data types re-used by the CAPIF\_Publish\_Service\_API service:

**Table 8.2.4.1-2: Re-used Data Types**

| Data type | Reference           | Comments | Applicability |
|-----------|---------------------|----------|---------------|
| Ipv4Addr  | 3GPP TS 29.122 [14] |          |               |
| Ipv6Addr  | 3GPP TS 29.122 [14] |          |               |
| Uri       | 3GPP TS 29.122 [14] |          |               |
| Port      | 3GPP TS 29.122 [14] |          |               |

### 8.2.4.2 Structured data types

#### 8.2.4.2.1 Introduction

#### 8.2.4.2.2 Type: ServiceAPIDescription

**Table 8.2.4.2.2-1: Definition of type ServiceAPIDescription**

| Attribute name       | Data type            | P | Cardinality | Description   | Applicability |
|----------------------|----------------------|---|-------------|---|---------------|
| apiName              | string               | M | 1           | API name  |               |
| apiID                | string               | C | 0..1        | API identifier assigned by the CAPIF core function to the published service API. Shall not be present in the HTTP POST request from the API publishing function to the CAPIF core function. Shall be present in the HTTP POST response from the CAPIF core function to the API publishing function. |               |
| apiVersion           | string               | O | 0..1        | API version   |               |
| serviceName          | string               | O | 0..1        | Name of the service to which the API belongs  |               |
| interfaceDescription | InterfaceDescription | O | 0..N        | Interface details   |               |
| dataFormat           | DataFormat           | O | 0..1        | Data formats used by the API  |               |
| description          | string               | O | 0..1        | Text description of the API   |               |
| uri                  | Uri                  | O | 0..N        | Relative URI (s) of the API   |               |

## 8.2.4.2.3 Type: InterfaceDescription

**Table 8.2.4.2.3-1: Definition of type InterfaceDescription**

| Attribute name | Data type | P | Cardinality | Description                       | Applicability |
|----------------|-----------|---|-------------|-----------------------------------|---------------|
| domainName     | string    | O | 0..1        | Domain to which API belongs to    |               |
| ipv4Addr       | Ipv4Addr  | O | 0..1        | String identifying a IPv4 address |               |
| ipv6Addr       | Ipv6Addr  | O | 0..1        | String identifying a IPv6 address |               |
| port           | Port      | O | 0..1        | Port                              |               |
| protocol       | Protocol  | O | 0..1        | Protocol used by the API.         |               |

## 8.2.4.3 Simple data types and enumerations

## 8.2.4.3.1 Introduction

This subclause defines simple data types and enumerations that can be referenced from data structures defined in the previous subclauses.

## 8.2.4.3.2 Simple data types

The simple data types defined in table 8.2.4.3.2-1 shall be supported.

**Table 8.2.4.3.2-1: Simple data types**

| Type Name | Type Definition | Description | Applicability |
|-----------|-----------------|-------------|---------------|
| n/a       |                 |             |               |

## 8.2.4.3.3 Enumeration: Protocol

**Table 8.2.4.3.3-1: Enumeration Protocol**

| Enumeration value | Description             | Applicability |
|-------------------|-------------------------|---------------|
| HTTPS/1.1         | HTTP Secure version 1.1 |               |
| HTTPS/2           | HTTP Secure version 2.0 |               |

## 8.2.4.3.4 Enumeration: DataFormat

**Table 8.2.4.3.3-1: Enumeration DataFormat**

| Enumeration value | Description                | Applicability |
|-------------------|----------------------------|---------------|
| JSON              | JavaScript Object Notation |               |

## 8.2.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.2.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8.

**Table 8.2.6-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

## 8.3 CAPIF\_Events\_API


### 8.3.1 API URI

The request URI used in each HTTP request from the Subscribing functional entity towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "capif-events".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.3.2.

### 8.3.2 Resources

#### 8.3.2.1 Overview



**Figure 8.3.2.1-1: Resource URI structure of the CAPIF\_Events\_API**

Table 8.3.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.3.2.1-1: Resources and methods overview**

| Resource name                        | Resource URI  | HTTP method or custom operation | Description   |
|--------------------------------------|---|---------------------------------|---|
| CAPIF Events Subscriptions           | {apiRoot}/capif-events/v1/{subscriberId}/subscriptions                  | POST                            | Creates a new individual CAPIF Event Subscription                             |
| Individual CAPIF Events Subscription | {apiRoot}/capif-events/v1/{subscriberId}/subscriptions/{subscriptionId} | DELETE                          | Deletes an individual CAPIF Event Subscription identified by {subscriptionId} |

#### 8.3.2.2 Resource: CAPIF Events Subscriptions

##### 8.3.2.2.1 Description

The CAPIF Events Subscriptions resource represents all subscriptions of a Subscribing functional entity.

### 8.3.2.2.2 Resource Definition

Resource URI: {apiRoot}/capif-events/v1/{subscriberId}/subscriptions

This resource shall support the resource URI variables defined in table 8.3.2.2.2-1.

**Table 8.3.2.2.2-1: Resource URI variables for this resource**

| Name         | Definition                              |
|--------------|---|
| apiRoot      | See subclause 7.5                       |
| subscriberId | ID of the Subscribing functional entity |

### 8.3.2.2.3 Resource Standard Methods

#### 8.3.2.2.3.1 POST

This method shall support the URI query parameters specified in table 8.3.2.2.3.1-1.

**Table 8.3.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.3.2.2.3.1-2 and the response data structures and response codes specified in table 8.3.2.2.3.1-3.

**Table 8.3.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type         | P | Cardinality | Description   |
|-------------------|---|-------------|---|
| EventSubscription | M | 1           | Create a new individual CAPIF Events Subscription resource. |

**Table 8.3.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type         | P | Cardinality | Response codes | Description   |
|-------------------|---|-------------|----------------|---|
| EventSubscription | M | 1           | 201 Created    | CAPIF Events Subscription resource created successfully.<br>The URI of the created resource shall be returned in the "Location" HTTP header |

### 8.3.2.2.4 Resource Custom Operations

None.

## 8.3.2.3 Resource: Individual CAPIF Events Subscription

### 8.3.2.3.1 Description

The Individual CAPIF Events Subscription resource represents an individual event subscription of a Subscribing functional entity.

### 8.3.2.3.2 Resource Definition

Resource URI: {apiRoot}/capif-events/v1/{subscriberId}/subscriptions/{subscriptionId}

This resource shall support the resource URI variables defined in table 8.3.2.3.2-1.

**Table 8.3.2.3.2-1: Resource URI variables for this resource**

| Name           | Definition   |
|----------------|--|
| apiRoot        | See subclause 7.5                                    |
| subscriberId   | ID of the Subscribing functional entity              |
| subscriptionId | String identifying an individual Events Subscription |

### 8.3.2.3.3 Resource Standard Methods

#### 8.3.2.3.3.1 DELETE

This method shall support the URI query parameters specified in table 8.3.2.3.3.1-1.

**Table 8.3.2.3.3.1-1: URI query parameters supported by the DELETE method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.3.2.3.3.1-2 and the response data structures and response codes specified in table 8.3.2.3.3.1-3.

**Table 8.3.2.3.3.1-2: Data structures supported by the DELETE Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.3.2.3.3.1-3: Data structures supported by the DELETE Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description  |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The individual CAPIF Events Subscription matching the subscriptionId is deleted. |

### 8.3.2.3.4 Resource Custom Operations

None.

## 8.3.3 Notifications

### 8.3.3.1 General

The delivery of notifications shall conform to subclause 7.6.

**Table 8.3.3.1-1: Notifications overview**

| Notification       | Resource URI              | HTTP method or custom operation | Description (service operation)                         |
|--------------------|---------------------------|---------------------------------|---|
| Event notification | {notificationDestination} | POST                            | Notifies Subscribing functional entity of a CAPIF Event |

### 8.3.3.2 Event Notification

#### 8.3.3.2.1 Description

Event Notification is used by the CAPIF core function to notify a Subscribing functional entity of an Event. The Subscribing functional entity shall be subscribed to such Event Notification via the Individual CAPIF Events Subscription Resource.

### 8.3.3.2.2 Notification definition

The POST method shall be used for Event notification and the URI shall be the one provided by the API invoker during the on-boarding request.

Resource URI: {notificationDestination}

This method shall support the URI query parameters specified in table 8.3.3.2.2.1-1.

**Table 8.3.3.2.2-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.3.3.2.2-2 and the response data structures and response codes specified in table 8.3.3.2.2-3.

**Table 8.3.3.2.2-2: Data structures supported by the POST Request Body on this resource**

| Data type         | P | Cardinality | Description                               |
|-------------------|---|-------------|---|
| EventNotification | M | 1           | Notification information of a CAPIF Event |

**Table 8.3.3.2.2-3: Data structures supported by the POST Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description                                      |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The receipt of the Notification is acknowledged. |

## 8.3.4 Data Model

### 8.3.4.1 General

This subclause specifies the application data model supported by the API. Data types listed in subclause 7.2 apply to this API.

Table 8.3.4.1-1 specifies the data types defined specifically for the CAPIF\_Events\_API service.

**Table 8.3.4.1-1: CAPIF\_Events\_API specific Data Types**

| Data type         | Section defined | Description   | Applicability |
|-------------------|-----------------|---|---------------|
| EventSubscription | 8.3.4.2.2       | Represents an individual CAPIF Event Subscription resource              |               |
| EventNotification | 8.3.4.2.3       | Represents an individual CAPIF Event Subscription Notification resource |               |
| CAPIFEvent        | 8.3.4.3.2       | Describes CAPIF events  |               |

Table 8.3.4.1-2 specifies data types re-used by the CAPIF\_Events\_API service:

**Table 8.3.4.1-2: Re-used Data Types**

| Data type            | Reference           | Comments | Applicability |
|----------------------|---------------------|----------|---------------|
| Uri                  | 3GPP TS 29.122 [14] |          |               |
| TestNotification     | 3GPP TS 29.122 [14] |          |               |
| WebsocketNotifConfig | 3GPP TS 29.122 [14] |          |               |

### 8.3.4.2 Structured data types

#### 8.3.4.2.1 Introduction

This subclause defines the structures to be used in resource representations.

## 8.3.4.2.2 Type: EventSubscription

**Table 8.3.4.2.2-1: Definition of type EventSubscription**

| Attribute name              | Data type                   | P | Cardinality | Description  | Applicability           |
|-----------------------------|-----------------------------|---|-------------|--|-------------------------|
| events                      | CAPIFEvent                  | M | 1..N        | Subscribed events  |                         |
| notificationDestination     | Uri                         | M | 1           | URI where the notification should be delivered to.   |                         |
| requestTestNotification     | Boolean                     | O | 0..1        | Set to true by Subscribing functional entity to request the CAPIF core function to send a test notification as defined in in subclause 7.6. Set to false or omitted otherwise. | Notification_test_event |
| websocketNotificationConfig | WebsocketNotificationConfig | O | 0..1        | Configuration parameters to set up notification delivery over WebSocket protocol as defined in subclause 7.6.  | Notification_websocket  |

## 8.3.4.2.3 Type: EventNotification

**Table 8.3.4.2.4-1: Definition of type EventNotification**

| Attribute name | Data type  | P | Cardinality | Description  | Applicability |
|----------------|------------|---|-------------|--|---------------|
| subscriptionId | string     | M | 1           | Identifier of the subscription resource to which the notification is related – CAPIF resource identifier |               |
| events         | CAPIFEvent | M | 1..N        | Notifications of individual events   |               |

## 8.3.4.3 Simple data types and enumerations

## 8.3.4.3.1 Introduction

This subclause defines simple data types and enumerations that can be referenced from data structures defined in the previous subclauses.

## 8.3.4.3.2 Simple data types

None.

The simple data types defined in table 8.3.4.3.2-1 shall be supported.

**Table 8.3.4.3.2-1: Simple data types**

| Type Name | Type Definition | Description | Applicability |
|-----------|-----------------|-------------|---------------|
| n/a       |                 |             |               |

## 8.3.4.3.3 Enumeration: CAPIFEvent

Table 8.3.4.3.3-1: Enumeration CAPIFEvent

| Enumeration value                    | Description   | Applicability |
|--------------------------------------|---|---------------|
| Availability of service APIs         | Availability events of service APIs                                     |               |
| Service API update                   | Events related to change in service API information                     |               |
| Service API invocation               | Events corresponding to service API invocations                         |               |
| API invoker on-boarded               | Events related to API invoker status in CAPIF (on-boarded, off-boarded) |               |
| System related events                | Alarm events providing fault information                                |               |
| Performance related events           | Events related to system load conditions                                |               |
| Monitoring service API               | Events related to the status of the service APIs                        |               |
| Access control policy related events | Events related to status of the access control policy information       |               |

**Editor's Note:** The above table is not final and will be refined, for e.g. actual enumeration values need to be defined in capital letters.

## 8.3.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.3.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8. Table 8.3.6-1 lists the supported features for CAPIF\_Events\_API.

Table 8.3.6-1: Supported Features

| Feature number | Feature Name            | Description   |
|----------------|-------------------------|---|
| 1              | Notification_test_event | Testing of notification connection is supported according to subclause 7.6.   |
| 2              | Notification_websocket  | The delivery of notifications over Websocket is supported according to subclause 7.6. This feature requires that the Notification_test_event feature is also supported. |

**Editor's Note:** Supporting features specific to Subscribing functional entities is for further study.

## 8.4 CAPIF\_API\_Invoker\_Management\_API


## 8.4.1 API URI

The request URI used in each HTTP request from the API invoker towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "api-invoker-management".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.4.2.

## 8.4.2 Resources

### 8.4.2.1 Overview



**Figure 8.4.2.1-1: Resource URI structure of the CAPIF\_API\_Invoker\_Management\_API**

Table 8.4.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.4.2.1-1: Resources and methods overview**

| Resource name                     | Resource URI   | HTTP method or custom operation | Description   |
|-----------------------------------|--|---------------------------------|---|
| On-boarded API Invokers           | {apiRoot}<br>/api-invoker-management/v1<br>/onboardedInvokers                | POST                            | On-boards a new API invoker by creating a API invoker profile   |
| Individual On-boarded API Invoker | {apiRoot}<br>/api-invoker-management/v1<br>/onboardedInvokers/{onboardingId} | DELETE                          | Off-boards an individual API invoker by deleting the API invoker profile identified by {onboardingId} |

### 8.4.2.2 Resource: On-boarded API invokers

#### 8.4.2.2.1 Description

The On-boarded API Invokers resource represents all the API invokers that are on-boarded at a given CAPIF core function.

#### 8.4.2.2.2 Resource Definition

Resource URI: **{apiRoot}/api-invoker-management/v1/onboardedInvokers**

This resource shall support the resource URI variables defined in table 8.4.2.2.2-1.

**Table 8.4.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition        |
|---------|-------------------|
| apiRoot | See subclause 7.5 |

#### 8.4.2.2.3 Resource Standard Methods

##### 8.4.2.2.3.1 POST

This method shall support the URI query parameters specified in table 8.4.2.2.3.1-1.

**Table 8.4.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.4.2.2.3.1-2 and the response data structures and response codes specified in table 8.4.2.2.3.1-3.

**Table 8.4.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type                  | P | Cardinality | Description  |
|----------------------------|---|-------------|--|
| APIInvokerEnrolmentDetails | M | 1           | Enrolment details of the API invoker including notification destination URI for any on-boarding related notifications and an optional list of APIs the API invoker intends to invoke while on-board. |

**Table 8.4.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type                  | P | Cardinality | Response codes | Description  |
|----------------------------|---|-------------|----------------|--|
| APIInvokerEnrolmentDetails | M | 1           | 201 Created    | API invoker on-boarded successfully<br>The URI of the created resource shall be returned in the "Location" HTTP header. A list of APIs the API invoker is allowed to invoke while on-board may also be included. |
| OnboardingRequestAck       | M | 1           | 200 OK         | CAPIF core function acknowledging the received on-boarding request.  |

*Editor's Note: 202 Accepted response code as a POST response is for further study.*

#### 8.4.2.2.4 Resource Custom Operations

None.

#### 8.4.2.3 Resource: Individual On-boarded API Invoker

##### 8.4.2.3.1 Description

The Individual On-boarded API Invokers resource represents an individual API invoker that is on-boarded at a given CAPIF core function.

##### 8.4.2.3.2 Resource Definition

Resource URI: {apiRoot}/api-invoker-management/v1/onboardedInvokers/{onboardingId}

This resource shall support the resource URI variables defined in table 8.4.2.3.2-1.

**Table 8.4.2.3.2-1: Resource URI variables for this resource**

| Name         | Definition   |
|--------------|--|
| apiRoot      | See subclause 7.5  |
| onboardingId | String identifying an individual on-boarded API invoker resource |

##### 8.4.2.3.3 Resource Standard Methods

###### 8.4.2.3.3.1 DELETE

This method shall support the URI query parameters specified in table 8.4.2.3.3.1-1.

**Table 8.4.2.3.3.1-1: URI query parameters supported by the DELETE method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the response codes specified in table 8.4.2.3.3.1-2 and the response data structures and response codes specified in table 8.4.2.3.3.1-3.

**Table 8.4.2.3.3.1-2: Data structures supported by the DELETE Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.4.2.3.3.1-3: Data structures supported by the DELETE Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description  |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The individual on-boarded API invoker matching the onboardingId is deleted |

#### 8.3.2.3.4 Resource Custom Operations

None.

### 8.4.3 Notifications

#### 8.4.3.1 General

The delivery of notifications shall conform to subclause 7.6.

**Table 8.4.3.1-1: Notifications overview**

| Notification             | Resource URI              | HTTP method or custom operation | Description (service operation)          |
|--------------------------|---------------------------|---------------------------------|--|
| On-boarding notification | {notificationDestination} | POST                            | Notify API invoker of on-boarding result |

#### 8.4.3.2 On-boarding Notification

##### 8.4.3.2.1 Description

On-boarding Notification is used by the CAPIF core function to notify an API invoker of the on-boarding result.

##### 8.4.3.2.2 Notification definition

The POST method shall be used for On-boarding notification and the URI shall be the one provided by the API invoker during the on-boarding request.

Resource URI: {notificationDestination}

This method shall support the URI query parameters specified in table 8.4.3.2.2-1.

**Table 8.4.3.2.2-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.4.3.2.2-2 and the response data structures and response codes specified in table 8.4.3.2.2-3.

**Table 8.4.3.2.2-2: Data structures supported by the POST Request Body on this resource**

| Data type              | P | Cardinality | Description                          |
|------------------------|---|-------------|--------------------------------------|
| OnboardingNotification | M | 1           | Notification with on-boarding result |

**Table 8.4.3.2.2-3: Data structures supported by the POST Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description                                      |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The receipt of the Notification is acknowledged. |

## 8.4.4 Data Model

### 8.4.4.1 General

This subclause specifies the application data model supported by the API. Data types listed in subclause 7.2 apply to this API.

Table 8.4.4.1-1 specifies the data types defined specifically for the CAPIF\_API\_Invoker\_Management\_API service.

**Table 8.4.4.1-1: CAPIF\_API\_Invoker\_Management\_API specific Data Types**

| Data type                         | Section defined | Description                                | Applicability |
|-----------------------------------|-----------------|--|---------------|
| APIInvokerEnrolmentDetails        | 8.4.4.2.2       | API invoker's enrolment details            |               |
| OnboardingNotificationDestination | 8.4.4.2.3       | Notification destination details.          |               |
| APIList                           | 8.4.4.2.4       | List of APIs                               |               |
| OnboardingInformation             | 8.4.4.2.5       | On-boarding information of the API invoker |               |
| OnboardingRequestAck              | 8.4.4.2.6       | Acknowledgement to received request.       |               |
| CAPIFOnboardingNotification       | 8.4.4.2.7       | Notification with on-boarding result       |               |

Table 8.4.4.1-2 specifies data types re-used by the CAPIF\_API\_Invoker\_Management\_API service.

**Table 8.4.4.1-2: Re-used Data Types**

| Data type             | Reference           | Comments | Applicability |
|-----------------------|---------------------|----------|---------------|
| ServiceAPIDescription | Subclause 8.1.4.2.2 |          |               |
| Uri                   | 3GPP TS 29.122 [14] |          |               |
| TestNotification      | 3GPP TS 29.122 [14] |          |               |
| WebsocketNotifConfig  | 3GPP TS 29.122 [14] |          |               |

## 8.4.4.2 Structured data types

## 8.4.4.2.1 Introduction

## 8.4.4.2.2 Type: APIInvokerEnrolmentDetails

**Table 8.4.4.2.2-1: Definition of type APIInvokerEnrolmentDetails**

| Attribute name                    | Data type                         | P | Cardinality | Description   | Applicability |
|-----------------------------------|-----------------------------------|---|-------------|---|---------------|
| apiInvokerId                      | string                            | O | 0..1        | API invoker ID assigned by the CAPIF core function to the API invoker while on-boarding the API invoker. Shall not be present in the HTTP POST request from the API invoker to the CAPIF core function, to on-board itself. Shall be present in all other HTTP requests and responses.                  |               |
| onboardingInformation             | OnboardingInformation             | M | 1           | On-boarding information about the API invoker necessary for the CAPIF core function to on-board the API invoker.  |               |
| onboardingNotificationDestination | OnboardingNotificationDestination | O | 0..1        | Onboarding notification destination information provided by the API invoker. Shall be present in the HTTP POST request from the API invoker to the CAPIF core function, to on-board itself. Shall not be present in any other HTTP requests and responses.  |               |
| apiList                           | APIList                           | O | 0..1        | A list of APIs. When included by the API invoker in the HTTP request message, it lists the APIs that the API invoker intends to invoke while onboard. When included by the CAPIF core function in the HTTP response message, it lists the APIs that the API invoker is allowed to invoke while onboard. |               |

## 8.4.4.2.3 Type: OnboardingNotificationDestination

**Table 8.4.4.2.3-1: Definition of type OnboardingNotificationDestination**

| Attribute name              | Data type                   | P | Cardinality | Description   | Applicability           |
|-----------------------------|-----------------------------|---|-------------|---|-------------------------|
| notificationDestination     | Uri                         | M | 1           | URI where the notification should be delivered to.  |                         |
| requestTestNotification     | Boolean                     | O | 0..1        | Set to true by Subscribing functional entity to request the CAPIF core function to send a test notification as defined in subclause 7.6. Set to false or omitted otherwise. | Notification_test_event |
| websocketNotificationConfig | WebsocketNotificationConfig | O | 0..1        | Configuration parameters to set up notification delivery over Websocket protocol as defined in subclause 7.6.   | Notification_websocket  |

## 8.4.4.2.4 Type: APIList

**Table 8.4.4.2.4-1: Definition of type APIList**

| Attribute name        | Data type             | P | Cardinality | Description                   | Applicability |
|-----------------------|-----------------------|---|-------------|-------------------------------|---------------|
| serviceAPIDescription | ServiceAPIDescription | M | 1..N        | Definition of the service API |               |

## 8.4.4.2.5 Type: OnboardingInformation

**Table 8.4.4.2.5-1: Definition of type OnboardingInformation**

| Attribute name            | Data type | P | Cardinality | Description   | Applicability |
|---------------------------|-----------|---|-------------|---|---------------|
| apiInvokerOnboardingToken | string    | O | 0..1        | Base64 encoded OAuth Access Token received from the service provider. |               |
| apiInvokerPublicKey       | string    | O | 0..1        | Public Key of API Invoker   |               |
| apiInvokerCertificate     | string    | O | 0..1        | API invoker's generic client certificate                              |               |

## 8.4.4.2.6 Type: OnboardingRequestAck

**Table 8.4.4.2.6-1: Definition of type OnboardingRequestAck**

| Attribute name                    | Data type                         | P | Cardinality | Description  | Applicability |
|-----------------------------------|-----------------------------------|---|-------------|--|---------------|
| onboardingNotificationDestination | OnboardingNotificationDestination | M | 1           | On-boarding notification destination related details |               |

## 8.4.4.2.7 Type: CAPIFOnboardingNotification

**Table 8.4.4.2.7-1: Definition of type CAPIFOnboardingNotification**

| Attribute name             | Data type                 | P | Cardinality | Description   | Applicability |
|----------------------------|---------------------------|---|-------------|---|---------------|
| result                     | Boolean                   | M | 1           | Set to "true" indicate successful on-boarding. Otherwise set to "false"   |               |
| resourceLocation           | Uri                       | C | 1           | URI pointing to the new CAPIF resource created as a result of successful on-boarding.<br>This attribute shall be present if 'result' attribute is set to "true". Otherwise it shall not be present.                 |               |
| apiInvokerEnrolmentDetails | APIInvokeEnrolmentDetails | C | 1           | Enrolment details of the API invoker which are verified by the CAPIF administrator or API management.<br>This attribute shall be present if 'result' attribute is set to "true". Otherwise it shall not be present. |               |
| apiList                    | APIList                   | O | 0..1        | List of APIs API invoker is allowed to access.<br>This attribute may be present if 'result' attribute is set to "true". Otherwise it shall not be present.  |               |

## 8.4.4.3 Simple data types and enumerations

None.

## 8.4.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.4.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8. Table 8.4.6-1 lists the supported features for CAPIF\_API\_Invoker\_Management\_API.

**Table 8.4.6-1: Supported Features**

| Feature number | Feature Name            | Description   |
|----------------|-------------------------|---|
| 1              | Notification_test_event | Testing of notification connection is supported according to subclause 7.6.   |
| 2              | Notification_websocket  | The delivery of notifications over Websocket is supported according to subclause 7.6. This feature requires that the Notification_test_event feature is also supported. |

## 8.5 CAPIF\_Authentication\_Authorization\_API


### 8.5.1 API URI

The request URI used in each HTTP request from the API invoker or the API exposing function towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "capif-security".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.5.2.

### 8.5.2 Resources

#### 8.5.2.1 Overview



**Figure 8.5.2.1-1: Resource URI structure of the CAPIF\_Authentication\_Authorization\_API**

Table 8.5.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.5.2.1-1: Resources and methods overview**

| Resource name                   | Resource URI   | HTTP method or custom operation | Description   |
|---------------------------------|--|---------------------------------|---|
| Trusted API invokers            | { apiRoot }<br>/capif-security/v1<br>/trustedInvokers                  | POST                            | All trusted API invokers                              |
| Individual trusted API invokers | { apiRoot }<br>/capif-security/v1<br>/trustedInvokers/{ apiInvokerId } | GET                             | Retrieve authentication information of an API invoker |
|                                 |  | DELETE                          | Revoke the authorization of the API invoker           |

## 8.5.2.2 Resource: Trusted API invokers

### 8.5.2.2.1 Description

The Trusted API Invokers resource represents all the API invokers that are trusted by the CAPIF core function and have received authentication information from the CAPIF core function.

### 8.5.2.2.2 Resource Definition

Resource URI: {apiRoot}/capif-security/v1/trustedInvokers

This resource shall support the resource URI variables defined in table 8.5.2.2.2-1.

**Table 8.5.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition        |
|---------|-------------------|
| apiRoot | See subclause 7.5 |

### 8.5.2.2.3 Resource Standard Methods

#### 8.5.2.2.3.1 POST

This method shall support the URI query parameters specified in table 8.5.2.2.3.1-1.

**Table 8.5.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.5.2.2.3.1-2 and the response data structures and response codes specified in table 8.5.2.2.3.1-3.

**Table 8.5.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type       | P | Cardinality | Description  |
|-----------------|---|-------------|--|
| ServiceSecurity | M | 1           | Security method request from the API invoker to the CAPIF core function. The request indicates the a list of service APIs and a preferred method of security for the service APIs.<br><br>The request also includes a notification destination URI for security related notifications. |

**Table 8.5.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type       | P | Cardinality | Response codes | Description  |
|-----------------|---|-------------|----------------|--|
| ServiceSecurity | M | 1           | 201<br>Created | Security method from the CAPIF core function to the API invoker is based on the received request. The response indicates the security method to be used for the service APIs<br><br>The URI of the created resource shall be returned in the "Location" HTTP header. |

### 8.5.2.2.4 Resource Custom Operations

None.

### 8.5.2.3 Resource: Individual trusted API invokers

#### 8.5.2.3.1 Description

The Individual trusted API Invokers resource represents an individual API invokers that is trusted by the CAPIF core function and have received security related information from the CAPIF core function.

#### 8.5.2.3.2 Resource Definition

Resource URI: **{apiRoot}/capif-security/v1/trustedInvokers/{apiInvokerId}**

This resource shall support the resource URI variables defined in table 8.5.2.3.2-1.

**Table 8.5.2.3.2-1: Resource URI variables for this resource**

| Name         | Definition                                   |
|--------------|--|
| apiRoot      | See subclause 7.5                            |
| apiInvokerId | String identifying an individual API invoker |

#### 8.5.2.3.3 Resource Standard Methods

##### 8.5.2.3.3.1 GET

This method shall support the URI query parameters specified in table 8.5.2.3.3.1-1.

**Table 8.5.2.3.3.1-1: URI query parameters supported by the GET method on this resource**

| Name               | Data type | P | Cardinality | Description  |
|--------------------|-----------|---|-------------|--|
| apiInvokerId       | string    | M | 1           | String identifying the API invoker   |
| authenticationInfo | boolean   | O | 0..1        | When set to 'true', it indicates the CAPIF core function to send the authentication information of the API invoker. Set to false or omitted otherwise. |
| authorizationInfo  | boolean   | O | 0..1        | When set to 'true', it indicates the CAPIF core function to send the authorization information of the API invoker. Set to false or omitted otherwise.  |

This method shall support the request data structures specified in table 8.5.2.3.3.1-2 and the response data structures and response codes specified in table 8.5.2.3.3.1-3.

**Table 8.5.2.3.3.1-2: Data structures supported by the GET Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.5.2.3.3.1-3: Data structures supported by the GET Response Body on this resource**

| Data type       | P | Cardinality | Response codes | Description  |
|-----------------|---|-------------|----------------|--|
| ServiceSecurity | M | 1           | 200 OK         | The security related information of the API Invoker based on the request from the API exposing function. |

##### 8.5.2.3.3.2 DELETE

This method shall support the URI query parameters specified in table 8.5.2.3.3.2-1.

**Table 8.5.2.3.3.2-1: URI query parameters supported by the DELETE method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.5.2.3.3.2-2 and the response data structures and response codes specified in table 8.5.2.3.3.2-3.

**Table 8.5.2.3.3.2-2: Data structures supported by the DELETE Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.5.2.3.3.2-3: Data structures supported by the DELETE Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description   |
|-----------|---|-------------|----------------|---|
| n/a       |   |             | 204 No Content | Authorization of the API invoker revoked, and a notification is sent to the API invoker as specified in subclause 8.5.3.2 |

#### 8.5.2.3.4 Resource Custom Operations

None.

### 8.5.3 Notifications

#### 8.5.3.1 General

The delivery of notifications shall conform to subclause 7.6.

**Table 8.5.3.1-1: Notifications overview**

| Notification                       | Resource URI              | HTTP method or custom operation | Description (service operation)  |
|------------------------------------|---------------------------|---------------------------------|--|
| Authorization revoked notification | {notificationDestination} | POST                            | Notify API invoker that the authorization rights are revoked by the API exposing function. |

#### 8.5.3.2 Authorization revoked notification

##### 8.5.3.2.1 Description

Authorization revoked notification is used by the CAPIF core function to notify an API invoker that the authorization rights are revoked by the API exposing function.

##### 8.5.3.2.2 Notification definition

The POST method shall be used for Authorization revoked notification and the URI shall be the one provided by the API invoker during the Service\_Security\_Method\_Request service operation.

Resource URI: {notificationDestination}

This method shall support the URI query parameters specified in table 8.5.3.2.2-1.

**Table 8.5.3.2.2-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.5.3.2.2-2 and the response data structures and response codes specified in table 8.5.3.2.2-3.

**Table 8.5.3.2.2-2: Data structures supported by the POST Request Body on this resource**

| Data type            | P | Cardinality | Description   |
|----------------------|---|-------------|---|
| SecurityNotification | M | 1           | Notification with information related to revoked authorization. |

**Table 8.5.3.2.2-3: Data structures supported by the POST Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description                                      |
|-----------|---|-------------|----------------|--|
| n/a       |   |             | 204 No Content | The receipt of the Notification is acknowledged. |

## 8.5.4 Data Model

### 8.5.4.1 General

This subclause specifies the application data model supported by the API.

Table 8.5.4.1-1 specifies the data types defined for the CAPIF service based interface protocol.

**Table 8.5.4.1-1: Specific Data Types**

| Data type                       | Section defined | Description  | Applicability |
|---------------------------------|-----------------|--|---------------|
| ServiceSecurity                 | 8.5.4.2.2       | Details of the security method for each service API interface. When included by the API invoker, it shall indicate the preferred method of security. When included by the CAPIF core function, it shall indicate the security method to be used for the service API interface. |               |
| SecurityMethod                  | 8.5.4.2.3       | Interface details and the security method  |               |
| securityNotificationDestination | 8.5.4.2.4       | Notification destination details   |               |

Table 8.5.4.1-2 specifies data types re-used by the CAPIF\_Authentication\_Authorization\_API service based interface:

**Table 8.5.4.1-2: Re-used Data Types**

| Data type        | Reference           | Comments                 | Applicability |
|------------------|---------------------|--------------------------|---------------|
| InterfaceDetails | Subclause 8.2.4.2.3 | Details of the interface |               |

## 8.5.4.2 Structured data types

## 8.5.4.2.1 Introduction

## 8.5.4.2.2 Type: ServiceSecurity

**Table 8.5.4.2.2-1: Definition of type ServiceSecurity**

| Attribute name                  | Data type                       | P | Cardinality | Description  | Applicability |
|---------------------------------|---------------------------------|---|-------------|--|---------------|
| securityPreference              | SecurityMethod                  | C | 1..N        | API invoker's preference of the security method for a service API interface. Shall be present in the HTTP POST request from the API invoker to the CAPIF core function to negotiate the security mechanism. Shall not be present in any other HTTP request or HTTP response.     |               |
| selectedSecurity                | SecurityMethod                  | C | 1..N        | Security method for each service API interface selected by the CAPIF core function. Shall be present in the HTTP POST response from the CAPIF core function to the API invoker. Shall not be present in any other HTTP request or HTTP response.                                 |               |
| apiInvokerSecurity              | SecurityMethod                  | O | 0..N        | Security method for each service API interface selected for the API invoker by the CAPIF core function. May be present only in the HTTP GET response from the CAPIF core function to the API exposing function. Shall not be present in any other HTTP request or HTTP response. |               |
| securityNotificationDestination | SecurityNotificationDestination | C | 0..1        | Security notification destination information provided by the API invoker. Shall be present in the HTTP POST request from the API invoker to the CAPIF core function, to negotiate the security mechanism. Shall not be present in any other HTTP request or HTTP response.      |               |

## 8.5.4.2.3 Type: SecurityMethod

**Table 8.5.4.2.3-1: Definition of type SecurityMethod**

| Attribute name     | Data type        | P | Cardinality | Description                        | Applicability |
|--------------------|------------------|---|-------------|------------------------------------|---------------|
| interfaceDetails   | InterfaceDetails | M | 1           | Details of the interface           |               |
| securityMethod     | string           | M | 1           | Security method for the interface  |               |
| authenticationInfo | string           | O | 0..1        | Authentication related information |               |
| authorizationInfo  | string           | O | 0..1        | Authorization related information  |               |

Editor's Note: The data models should be improved to accommodate changes or improvements done in SA3.

## 8.5.4.2.4 Type: securityNotificationDestination

**Table 8.5.4.2.4-1: Definition of type securityNotificationDestination**

| Attribute name              | Data type                    | P | Cardinality | Description  | Applicability           |
|-----------------------------|------------------------------|---|-------------|--|-------------------------|
| notificationDestination     | Uri                          | M | 1           | URI where the notification should be delivered to.   |                         |
| requestTestNotification     | Boolean                      | O | 0..1        | Set to true by API invoker to request the CAPIF core function to send a test notification as defined in in subclause 7.6. Set to false or omitted otherwise. | Notification_test_event |
| websocketNotificationConfig | Websocket NotificationConfig | O | 0..1        | Configuration parameters to set up notification delivery over Websocket protocol as defined in subclause 7.6.  | Notification_websocket  |

## 8.5.4.3 Simple data types and enumerations

None.

## 8.5.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.5.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8. Table 8.5.6-1 lists the supported features for CAPIF\_Authentication\_Authorization\_API.

**Table 8.5.6-1: Supported Features**

| Feature number | Feature Name            | Description   |
|----------------|-------------------------|---|
| 1              | Notification_test_event | Testing of notification connection is supported according to subclause 7.6.   |
| 2              | Notification_websocket  | The delivery of notifications over Websocket is supported according to subclause 7.6. This feature requires that the Notification_test_event feature is also supported. |

## 8.6 CAPIF\_Access\_Control\_Policy\_API

## 8.6.1 API URI

The request URI used in each HTTP request from the API exposing function towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:


- The {apiName} shall be "access-control-policy".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.6.2.

## 8.6.2 Resources

## 8.6.2.1 Overview

This resource is created by the CAPIF administrator on the CAPIF core function.

**NOTE:** The details of the mechanisms used to create the Access Control Policy List resource on the CAPIF core function is out of the scope of the present document.



**Figure 8.6.2.1-1: Resource URI structure of the CAPIF\_Access\_Control\_Policy\_API**

Table 8.6.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.6.2.1-1: Resources and methods overview**

| Resource name              | Resource URI  | HTTP method or custom operation | Description                              |
|----------------------------|---|---------------------------------|--|
| Access Control Policy List | {apiRoot}/access-control-policy/v1/accessControlPolicyList/{serviceApiId} | GET                             | Retrieves the access control policy list |

## 8.6.2.2 Resource: Access Control Policy List

### 8.6.2.2.1 Description

The Access Control Policy List resource represents the access control information for all the service APIs.

### 8.6.2.2.2 Resource Definition

Resource URI: {apiRoot}/access-control-policy/v1/accessControlPolicyList

This resource shall support the resource URI variables defined in table 8.6.2.2.2-1.

**Table 8.6.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition        |
|---------|-------------------|
| apiRoot | See subclause 7.5 |

### 8.6.2.2.3 Resource Standard Methods

#### 8.6.2.2.3.1 GET

This method shall support the URI query parameters specified in table 8.6.2.2.3.1-1.

**Table 8.6.2.2.3.1-1: URI query parameters supported by the GET method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.6.2.2.3.1-2 and the response data structures and response codes specified in table 8.6.2.2.3.1-3.

**Table 8.6.2.2.3.1-2: Data structures supported by the GET Request Body on this resource**

| Data type | P | Cardinality | Description |
|-----------|---|-------------|-------------|
| n/a       |   |             |             |

**Table 8.6.2.2.3.1-3: Data structures supported by the GET Response Body on this resource**

| Data type               | P | Cardinality | Response codes | Description   |
|-------------------------|---|-------------|----------------|---|
| accessControlPolicyList | M | 1           | 200 OK         | List of the access control policy applicable for the service API requested. |

#### 8.6.2.2.4 Resource Custom Operations

None.

### 8.6.3 Notifications

None.

### 8.6.4 Data Model

#### 8.6.4.1 General

This subclause specifies the application data model supported by the API. Data types listed in subclause 7.2 apply to this API.

Table 8.6.4.1-1 specifies the data types defined specifically for the CAPIF\_Access\_Control\_Policy\_API service.

**Table 8.6.4.1-1: CAPIF\_Access\_Control\_Policy\_API specific Data Types**

| Data type               | Section defined | Description                | Applicability |
|-------------------------|-----------------|----------------------------|---------------|
| AccessControlPolicyList | 8.6.4.2.2       | Access control policy list |               |

Table 8.6.4.1-2 specifies data types re-used by the CAPIF\_Access\_Control\_Policy\_API service.

**Table 8.6.4.1-2: Re-used Data Types**

| Data type | Reference           | Comments | Applicability |
|-----------|---------------------|----------|---------------|
| Uri       | 3GPP TS 29.122 [14] |          |               |

#### 8.6.4.2 Structured data types

##### 8.6.4.2.1 Introduction

##### 8.6.4.2.2 Type: AccessControlPolicyList

**Table 8.6.4.2.2-1: Definition of type AccessControlPolicyList**

| Attribute name           | Data type     | P | Cardinality | Description   | Applicability |
|--------------------------|---------------|---|-------------|---|---------------|
| serviceAPIIdentification | string        | M | 1           | Service API ID assigned by the CAPIF core function to the service API while publishing the service API. |               |
| apiInvokerPolicy         | array(string) | M | 0..N        | Policy of each API invoker.   |               |

## 8.6.4.2.3 Type: APIInvokerPolicy

**Table 8.6.4.2.3-1: Definition of type APIInvokerPolicy**

| Attribute name                 | Data type            | P | Cardinality | Description   | Applicability |
|--------------------------------|----------------------|---|-------------|---|---------------|
| apiInvokerID                   | string               | M | 1           | API invoker ID assigned by the CAPIF core function  |               |
| allowedTotalInvocations        | integer              | O | 0..1        | Total number of invocations allowed on the service API by the API invoker.                      |               |
| allowedInvocationsPerSecond    | integer              | O | 0..1        | Invocations per second allowed on the service API by the API invoker.                           |               |
| allowedInvocationTimeRangeList | array(TimeRangeList) | O | 0..N        | The time ranges during which the invocations are allowed on the service API by the API invoker. |               |

## 8.6.4.2.4 Type: TimeRangeList

**Table 8.6.4.2.4-1: Definition of type TimeRangeList**

| Attribute name | Data type | P | Cardinality | Description   | Applicability |
|----------------|-----------|---|-------------|---|---------------|
| startTime      | DateTime  | M | 1           | The start time for the invocations to be allowed on the service API by the API invoker. |               |
| endTime        | DateTime  | M | 1           | The end time for the invocations to be allowed on the service API by the API invoker.   |               |

## 8.6.4.3 Simple data types and enumerations

None.

## 8.6.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.6.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8.

**Table 8.6.8-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

## 8.7 CAPIF\_Logging\_API\_Invocation\_API


## 8.7.1 API URI

The request URI used in each HTTP request from the API exposing function towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "api-invocation-logs".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.7.2

## 8.7.2 Resources

### 8.7.2.1 Overview



**Figure 8.7.2.1-1: Resource URI structure of the CAPIF\_Logging\_API\_Invocation\_API**

Table 8.7.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.7.2.1-1: Resources and methods overview**

| Resource name  | Resource URI  | HTTP method or custom operation | Description   |
|----------------|---|---------------------------------|---|
| Logs           | {apiRoot}<br>/api-invocation-logs/v1<br>/{{aeFld}}/logs           | POST                            | Creates a new log entry for service API invocations |
| Individual log | {apiRoot}<br>/api-invocation-logs/v1<br>/{{aeFld}}/logs/{{logId}} | n/a                             | Individual log entry                                |

### 8.7.2.2 Resource: Logs

#### 8.7.2.2.1 Description

The Logs resource represents all the log entries created by a API exposing function at CAPIF core function.

#### 8.7.2.2.2 Resource Definition

Resource URI: **{{apiRoot}}/api-invocation-logs/v1/{{aeFld}}/logs**

This resource shall support the resource URI variables defined in table 8.7.2.2.2-1.

**Table 8.7.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition                            |
|---------|---------------------------------------|
| apiRoot | See subclause 7.5                     |
| aeFld   | Identity of the API exposing function |

### 8.7.2.2.3 Resource Standard Methods

#### 8.7.2.2.3.1 POST

This method shall support the URI query parameters specified in table 8.7.2.2.3.1-1.

**Table 8.7.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 8.7.2.2.3.1-2 and the response data structures and response codes specified in table 8.7.2.2.3.1-3.

**Table 8.7.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type      | P | Cardinality | Description   |
|----------------|---|-------------|---|
| InvocationLogs | M | 201 Created | Log of service API invocations provided by API exposing function to store on the CAPIF core function. |

**Table 8.7.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type      | P | Cardinality | Response codes | Description  |
|----------------|---|-------------|----------------|--|
| InvocationLogs | M | 1           | 201 Created    | Log of service API invocations provided by API exposing function successfully stored on the CAPIF core function.<br><br>The URI of the created resource shall be returned in the "Location" HTTP header. |

#### 8.7.2.2.4 Resource Custom Operations

None.

### 8.7.3 Notifications

None.

### 8.7.4 Data Model

#### 8.7.4.1 General

This subclause specifies the application data model supported by the API.

Table 8.7.4.1-1 specifies the data types defined for the CAPIF service based interface protocol.

**Table 8.7.4.1-1: Specific Data Types**

| Data type      | Section defined | Description  | Applicability |
|----------------|-----------------|--|---------------|
| InvocationLogs | 8.7.4.2.2       | Set of Service API invocation logs to be stored on CAPIF core function |               |
| Log            | 8.7.4.2.3       | Individual log entries   |               |

Table 8.7.4.1-2 specifies data types re-used by the CAPIF\_Logging\_API\_Invocation\_API service:

**Table 8.7.4.1-2: Re-used Data Types**

| Data type | Reference           | Comments | Applicability |
|-----------|---------------------|----------|---------------|
| Ipv4Addr  | 3GPP TS 29.122 [14] |          |               |
| Ipv6Addr  | 3GPP TS 29.122 [14] |          |               |
| Port      | 3GPP TS 29.122 [14] |          |               |

## 8.7.4.2 Structured data types

### 8.7.4.2.1 Introduction

#### 8.7.4.2.2 Type: InvocationLogs

**Table 8.7.4.2.2-1: Definition of type InvocationLogs**

| Attribute name | Data type | P | Cardinality | Description   | Applicability |
|----------------|-----------|---|-------------|---|---------------|
| aefld          | string    | M | 1           | Identity information of the API exposing function requesting logging of service API invocations                             |               |
| apiInvokerId   | string    | M | 1           | Identity of the API invoker which invoked the service API   |               |
| ipv4Addr       | Ipv4Addr  | C | 0..1        | String identifying a IPv4 address of the API invoker. This attribute shall not be present if ipv6Addr attribute is present. |               |
| ipv6Addr       | Ipv6Addr  | C | 0..1        | String identifying a IPv6 address of the API invoker. This attribute shall not be present if ipv4Addr attribute is present. |               |
| port           | Port      | C | 0..1        | Port. This attribute shall be present if either ipv4Addr or the ipv6Addr attribute is present.                              |               |
| log            | Log       | M | 1..N        | Service API invocation log  |               |

#### 8.7.4.2.3 Type: Log

**Table 8.7.4.2.3-1: Definition of type Log**

| Attribute name       | Data type            | P | Cardinality | Description                               | Applicability |
|----------------------|----------------------|---|-------------|---|---------------|
| apiId                | string               | M | 1           | String identifying the API invoked.       |               |
| apiInvoked           | string               | M | 1           | Name of the API which was invoked         |               |
| version              | number               | M | 1           | Version of the API which was invoked      |               |
| resourceName         | string               | M | 1           | Name of the specific resource invoked     |               |
| operation            | string               | M | 1           | Operation that was invoked on the API     |               |
| result               | string               | M | 1           | Result or output of the invocation        |               |
| invocationTime       | DateTime             | O | 0..1        | Date on which it was invoked              |               |
| parameters           | string               | O | 0..1        | List of input parameters                  |               |
| interfaceDescription | InterfaceDescription | O | 0..1        | Interface description of the API invoked. |               |

### 8.7.4.3 Simple data types and enumerations

None.

## 8.7.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.7.6 Feature negotiation

**Table 8.7.8-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

## 8.8 CAPIF\_Auditing\_API


### 8.8.1 API URI

The request URI used in each HTTP request from the API management function towards the CAPIF core function shall have the structure as defined in subclause 7.5 with the following clarifications:

- The {apiName} shall be "logs".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 8.8.2.

### 8.8.2 Resources

#### 8.8.2.1 Overview



**Figure 8.8.2.1-1: Resource URI structure of the CAPIF\_Auditing\_API**

Table 8.8.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 8.8.2.1-1: Resources and methods overview**

| Resource name                   | Resource URI                                  | HTTP method or custom operation | Description  |
|---------------------------------|---|---------------------------------|--|
| All service API invocation logs | {apiRoot}<br>/logs/v1/apiInvocationLogs/query | query<br>(POST)                 | Query and retrieve service API invocation logs stored on the CAPIF core function |

**Editor's Note:** Check if the custom operation 'query' can be replaced with standard method HTTP GET.

#### 8.8.2.2 Resource: All service API invocation logs

##### 8.8.2.2.1 Description

The All service API invocation logs resource represents all service API invocation logs stored on the CAPIF core function.

### 8.8.2.2.2 Resource Definition

Resource URI: **{apiRoot}/logs/v1/apiInvocationLogs**

This resource shall support the resource URI variables defined in table 8.8.2.2.2-1.

**Table 8.8.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition        |
|---------|-------------------|
| apiRoot | See subclause 7.5 |

### 8.8.2.2.3 Resource Standard Methods

None.

### 8.8.2.2.4 Resource Custom Operations

#### 8.8.2.2.4.1 Overview

**Table 8.8.2.2.4.1-1: Custom operations**

| Custom operation URI                      | Mapped HTTP method | Description                       |
|---|--------------------|-----------------------------------|
| {apiRoot}/logs/v1/apiInvocationLogs/query | POST               | Query service API invocation logs |

#### 8.8.2.2.4.2 Operation: query

##### 8.8.2.2.4.2.1 Description

Query custom operation is used by an API management function to query service API invocation logs stored on the CAPIF core function.

##### 8.8.2.2.4.2.2 Operation Definition

This method shall support the URI query parameters specified in table 8.8.2.2.4.2.2-1.

**Table 8.8.2.2.4.2.2-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This operation shall support the request data structures specified in table 8.8.2.2.4.2.2-2 and the response data structure and response codes specified in table 8.8.2.2.4.2.2-3.

**Table 8.8.2.2.4.2.2-2: Data structures supported by the POST Request Body on this resource**

| Data type | P | Cardinality | Description  |
|-----------|---|-------------|--|
| LogQuery  | M | 1           | Query parameters to search and filter the service API invocation logs. |

**Table 8.8.2.2.4.2.2-3: Data structures supported by the POST Response Body on this resource**

| Data type | P | Cardinality | Response codes | Description   |
|-----------|---|-------------|----------------|---|
| LogData   | M | 1..N        | 200 OK         | Result of the query operation along with fetched service API invocation log data. |

## 8.8.3 Notifications

None.

## 8.8.4 Data Model

### 8.8.4.1 General

This subclause specifies the application data model supported by the API.

Table 8.8.4.1-1 specifies the data types defined for the CAPIF service based interface protocol.

**Table 8.8.4.1-1: Specific Data Types**

| Data type | Section defined | Description  | Applicability |
|-----------|-----------------|--------------|---------------|
| LogQuery  | 8.8.4.2.2       | Log Query    |               |
| LogData   | 8.8.4.2.3       | Query result |               |

Table 8.8.4.1-2 specifies data types re-used by the CAPIF\_Auditing\_API service:

**Table 8.8.4.1-2: Re-used Data Types**

| Data type | Reference           | Comments               | Applicability |
|-----------|---------------------|------------------------|---------------|
| Log       | Subclause 8.7.4.2.3 | Individual log entries |               |
| Ipv4Addr  | 3GPP TS 29.122 [14] |                        |               |
| Ipv6Addr  | 3GPP TS 29.122 [14] |                        |               |
| Uri       | 3GPP TS 29.122 [14] |                        |               |
| Port      | 3GPP TS 29.122 [14] |                        |               |

## 8.8.4.2 Structured data types

### 8.8.4.2.1 Introduction

#### 8.8.4.2.2 Type: LogQuery

**Table 8.8.4.2.2-1: Definition of type LogQuery**

| Attribute name       | Data type            | P | Cardinality | Description   | Applicability |
|----------------------|----------------------|---|-------------|---|---------------|
| aefld                | string               | O | 0..1        | String identifying the API exposing function  |               |
| apiInvokerId         | string               | O | 0..1        | String identifying the API invoker which invoked the service API  |               |
| ipv4Addr             | Ipv4Addr             | C | 0..1        | String identifying a IPv4 address of the API invoker. This attribute shall not be present if ipv6Addr attribute is present. |               |
| ipv6Addr             | Ipv6Addr             | C | 0..1        | String identifying a IPv6 address of the API invoker. This attribute shall not be present if ipv4Addr attribute is present. |               |
| port                 | Port                 | C | 0..1        | Port. This attribute shall be present if either ipv4Addr or the ipv6Addr attribute is present.                              |               |
| timeRangeStart       | DateTime             | O | 0..1        | Start time of the invocation time range   |               |
| timeRangeEnd         | DateTime             | O | 0..1        | End time of the invocation time range   |               |
| apild                | string               | O | 0..1        | String identifying the API invoked.   |               |
| apiName              | String               | O | 0..1        | Name of the API which was invoked   |               |
| version              | number               | O | 0..1        | Version of the API which was invoked  |               |
| operation            | string               | O | 0..1        | Operation that was invoked on the API   |               |
| result               | string               | O | 0..1        | Result or output of the invocation  |               |
| resourceName         | string               | O | 0..1        | Name of the specific resource invoked   |               |
| interfaceDescription | InterfaceDescription | O | 0..1        | Interface description of the API invoked.   |               |

#### 8.8.4.2.3 Type: LogData

**Table 8.8.4.2.3-1: Definition of type LogData**

| Attribute name | Data type | P | Cardinality | Description   | Applicability |
|----------------|-----------|---|-------------|---|---------------|
| aefld          | string    | O | 0..1        | Identity information of the API exposing function requesting logging of service API invocations |               |
| apiInvokerId   | string    | O | 0..1        | Identity of the API invoker which invoked the service API                                       |               |
| log            | Log       | O | 0..N        | APIs to be searched in the logs   |               |

### 8.8.4.3 Simple data types and enumerations

None.

## 8.8.5 Error Handling

General error responses are defined in subclause 7.7.

## 8.8.6 Feature negotiation

General feature negotiation procedures are defined in subclause 7.8.

**Table 8.8.6-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

## 9 AEF API Definition

### 9.1 AEF\_Authentication\_API

*Editor's Note: Check if the resource structure or the applicable HTTP methods can be improved.*


#### 9.1.1 API URI

The request URI used in each HTTP request from the API invoker towards the API exposing function shall have the following structure:

- The {apiRoot} shall be as defined in the service API specification using CAPIF.
- The {apiName} shall be "api-invoker-authentication".
- The {apiVersion} shall be "v1".
- The {apiSpecificSuffixes} shall be set as described in subclause 9.1.2.

#### 9.1.2 Resources

##### 9.1.2.1 Overview



**Figure 9.1.2.1-1: Resource URI structure of the API\_Invoker\_Authentication\_API**

Table 9.1.2.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 9.1.2.1-1: Resources and methods overview**

| Resource name                                 | Resource URI  | HTTP method or custom operation | Description  |
|---|---|---------------------------------|--|
| API invoker authentication profiles           | {apiRoot}/api-invoker-authentication/v1/authProfiles    | POST                            | Ensures API exposing function has credentials for API invoker authentication |
| Individual API invoker authentication profile | {apiRoot}/api-invoker-authentication/v1/{authProfileId} | n/a                             | Profile of an individual API invoker   |

|  |                               |  |  |
|--|-------------------------------|--|--|
|  | /authProfiles/{authProfileId} |  |  |
|--|-------------------------------|--|--|

## 9.1.2.2 Resource: API invoker authentication profiles

### 9.1.2.2.1 Description

The API invoker authentication profiles represent all the authentication profiles of different API invokers available at the API exposing function.

### 9.1.2.2.2 Resource Definition

Resource URI: {apiRoot}/api-invoker-authentication/v1/authProfiles

This resource shall support the resource URI variables defined in table 9.1.2.2.2-1.

**Table 9.1.2.2.2-1: Resource URI variables for this resource**

| Name    | Definition   |
|---------|--|
| apiRoot | Defined in the service API specification using CAPIF |

### 9.1.2.2.3 Resource Standard Methods

#### 9.1.2.2.3.1 POST

This method shall support the URI query parameters specified in table 9.1.2.2.3.1-1.

**Table 9.1.2.2.3.1-1: URI query parameters supported by the POST method on this resource**

| Name | Data type | P | Cardinality | Description |
|------|-----------|---|-------------|-------------|
| n/a  |           |   |             |             |

This method shall support the request data structures specified in table 9.1.2.2.3.1-2 and the response data structures and response codes specified in table 9.1.2.2.3.1-3.

**Table 9.1.2.2.3.1-2: Data structures supported by the POST Request Body on this resource**

| Data type         | P | Cardinality | Description                |
|-------------------|---|-------------|----------------------------|
| APIInvokerDetails | M | 1           | Details of the API invoker |

**Table 9.1.2.2.3.1-3: Data structures supported by the POST Response Body on this resource**

| Data type         | P | Cardinality | Response codes | Description   |
|-------------------|---|-------------|----------------|---|
| APIInvokerDetails | M | 1           | 201<br>Created | API exposing function has the authentication profile available and is ready for authentication of the API invoker |

### 9.1.2.2.4 Resource Custom Operations

None.

## 9.1.3 Notifications

None.

## 9.1.4 Data Model

### 9.1.4.1 General

This subclause specifies the application data model supported by the API. Data types listed in subclause 7.2 apply to this API.

Table 9.1.4.1-1 specifies the data types defined specifically for the AEF\_Authentication\_API service.

**Table 9.1.4.1-1: AEF\_Authentication\_API specific Data Types**

| Data type         | Section defined | Description           | Applicability |
|-------------------|-----------------|-----------------------|---------------|
| APIInvokerDetails | 9.1.4.2.2       | API invoker's details |               |

Table 9.1.4.1-2 specifies data types re-used by the CAPIF\_API\_Invoker\_Management\_API service.

**Table 9.1.4.1-2: Re-used Data Types**

| Data type | Reference | Comments | Applicability |
|-----------|-----------|----------|---------------|
| n/a       |           |          |               |

### 9.1.4.2 Structured data types

#### 9.1.4.2.1 Introduction

#### 9.1.4.2.2 Type: APIInvokerDetails

**Table 9.1.4.2.2-1: Definition of type APIInvokerDetails**

| Attribute name | Data type | P | Cardinality | Description  | Applicability |
|----------------|-----------|---|-------------|--|---------------|
| apiInvokerId   | string    | M | 1           | API invoker ID assigned by the CAPIF core function to the API invoker while on-boarding the API invoker. |               |

**Editor's Note:** The data models should be improved to accommodate changes or improvements done in SA3.

### 9.1.4.3 Simple data types and enumerations

None.

## 9.1.5 Error Handling

General error responses are defined in the service API specification using CAPIF.

## 9.1.6 Feature negotiation

General feature negotiation procedures are defined in the service API specification using CAPIF.

**Table 9.1.6-1: Supported Features**

| Feature number | Feature Name | Description |
|----------------|--------------|-------------|
| n/a            |              |             |

---

# 10 Security

## 10.1 General

Security methods for CAPIF are specified in 3GPP TS 33.122 [16].

## 10.1 CAPIF-1/1e security

Secure communication between API invoker and CAPIF core function over CAPIF-1 or CAPIF-1e reference point, using a TLS protocol based connection is defined in 3GPP TS 33.122 [16].

For Onboard\_API\_Invoker service operation of the CAPIF\_API\_Invoker\_Management\_API, the TLS protocol based connection shall be established using server certificate as defined in 3GPP TS 33.122 [16].

For rest of the CAPIF APIs, the TLS protocol based connection shall be established with certificate based mutual authentication as defined in 3GPP TS 33.122 [16].

## 10.2 CAPIF-2/2e security and securely invoking service APIs

For secure communication between API invoker and API exposing function and ensuring secure invocations of service APIs, the API invoker:

- shall negotiate the security method with the CAPIF core function using the Service\_Security\_Method\_Request service operation of the CAPIF\_Security\_API;
- shall initiate the authentication with the API exposing function using the Authentication\_Initiation\_Request service operation of the AEF\_Authentication\_API; and
- shall establish a secure connection with the API exposing function as defined in 3GPP TS 33.122 [16], using the method negotiated with the CAPIF core function.

---

## Annex A (normative): OpenAPI specification

### A.1 General

*This subclause will describe the purpose of the Annex.*

### A.2 CAPIF\_Discover\_Service\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.3 CAPIF\_Publish\_Service\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.4 CAPIF\_Events\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.5 CAPIF\_API\_Invoker\_Management\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.6 CAPIF\_Authentication\_Authorization\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.7 CAPIF\_Access\_Control\_Policy\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.8 CAPIF\_Logging\_API\_Invocation\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.9 CAPIF\_Auditing\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

### A.10 AEF\_Authentication\_API

*One subclause is introduced per Service, with the corresponding OpenAPI 3.0.0 Document.*

## Annex B (informative): Change history

| Change history |         |           |    |     |     |  |             |
|----------------|---------|-----------|----|-----|-----|--|-------------|
| Date           | Meeting | TDoc      | CR | Rev | Cat | Subject/Comment  | New version |
| 2018-03        | CT3#95  | C3-181278 |    |     |     | TS skeleton of Common API Framework for 3GPP Northbound APIs   | 0.0.0       |
| 2018-03        | CT3#95  | C3-181378 |    |     |     | Inclusion of documents agreed in CT3#95:<br>C3-181281, C3-181282, C3-181283, C3-181284, C3-181285, C3-181286, C3-181287, C3-181321, C3-181322, Rapporteur changes  | 0.1.0       |
| 2018-04        | CT3#96  | C3-182527 |    |     |     | Inclusion of documents agreed in CT3#96:<br>C3-182204, C3-182387, C3-182393, C3-182395, C3-182468, C3-182469, C3-182470, C3-182483, C3-182484, C3-182485   | 0.2.0       |
| 2018-05        | CT3#97  |           |    |     |     | Inclusion of documents agreed in CT3#97:<br>C3-183271, C3-183274, C3-183275, C3-183372, C3-183376, C3-183377, C3-183378, C3-183379, C3-183598, C3-183599, C3-183602, C3-183603, C3-183604, C3-183798, C3-183799, C3-183809, C3-183841, C3-183842 | 0.3.0       |
| 2018-06        | CT#80   | CP-181037 |    |     |     | TS sent to plenary for approval  | 1.0.0       |
| 2018-06        | CT#80   | CP-181037 |    |     |     | TS approved by plenary   | 15.0.0      |

---

# History

| <b>Document history</b> |           |             |
|-------------------------|-----------|-------------|
| V15.0.0                 | July 2018 | Publication |
|                         |           |             |
|                         |           |             |
|                         |           |             |
|                         |           |             |