ETSI TS 129 274 V14.7.0 (2018-04)



Universal Mobile Telecommunications System (UMTS); LTE; 3GPP Evolved Packet System (EPS); Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C); Stage 3 (3GPP TS 29.274 version 14.7.0 Release 14)



Reference RTS/TSGC-0429274ve70

> Keywords LTE,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: <u>http://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</u>

If you find errors in the present document, please send your comment to one of the following services: <u>https://portal.etsi.org/People/CommiteeSupportStaff.aspx</u>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI. The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

> © ETSI 2018. All rights reserved.

DECT[™], PLUGTESTS[™], UMTS[™] and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**[™] and LTE[™] are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M** logo is protected for the benefit of its Members.

GSM[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <u>http://webapp.etsi.org/key/queryform.asp</u>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

ETSI TS 129 274 V14.7.0 (2018-04)

Contents

Intelle	ectual Property Rights	2
Forew	vord	2
Moda	l verbs terminology	2
Forew	vord	11
1	Scope	12
2	References	12
3	Definitions, symbols and abbreviations	
3.1 3.2	Definitions Symbols	
3.2 3.3	Abbreviations	
4	General	18
4.1	GTP Tunnel	18
4.2	Protocol stack	18
4.2.0	General	
4.2.1	UDP header and port numbers	
4.2.1.0		
4.2.1.1		
4.2.1.2		
4.2.1.3	80, 0	
4.2.2	IP header and IP addresses	
4.2.2.1	e	
4.2.2.2		
4.2.2.3		
4.2.3	Layer 2 Layer 1	
4.2.4	Messages with GTPv2 defined replies: Classification of Initial and Triggered Messages	
4.2.5	Transmission Order and Bit Definitions	
5	GTP Header for Control Plane	
5.1	General format	
5.2	Control Plane GTP Extension Header	
5.3	GTP-C header for Echo and Version Not Supported Indication messages	
5.4	EPC specific GTP-C header	
5.5	Usage of the GTPv2-C Header	
5.5.1	General	
5.5.2	Conditions for sending TEID=0 in GTPv2-C header	
5.6	Format of the GTPv2-C Message	26
6	GTP-C Message Types and Message Formats	27
6.0	General	27
6.1	Message Format and Type values	
6.1.0	Message Type	
6.1.1	Presence requirements of Information Elements	
6.1.2	Grouped Information Elements	
6.1.3	Information Element instance	
6.2	Message Granularity	
7	GTP-C messages	
7.1	Path Management Messages	
7.1.0	General	
7.1.1	Echo Request	
7.1.2	Echo Response	
7.1.3	Version Not Supported Indication	
7.2	Tunnel Management Messages	35

7.2.0	General	
7.2.1	Create Session Request	
7.2.2	Create Session Response	
7.2.3	Create Bearer Request	
7.2.4	Create Bearer Response	
7.2.5	Bearer Resource Command	
7.2.6	Bearer Resource Failure Indication	
7.2.7	Modify Bearer Request	
7.2.8	Modify Bearer Response	
7.2.9	Delete Session Request and Delete Bearer Request	
7.2.9.1	Delete Session Request	
7.2.9.2	Delete Bearer Request	
7.2.10	Delete Session Response and Delete Bearer Response	
7.2.10.1	Delete Session Response	
7.2.10.2	Delete Bearer Response	
7.2.11	Downlink Data Notification messages	
7.2.11.1	Downlink Data Notification	
7.2.11.2	Downlink Data Notification Acknowledge	
7.2.11.3	Downlink Data Notification Failure Indication	
7.2.12	Delete Indirect Data Forwarding Tunnel Request	
7.2.13	Delete Indirect Data Forwarding Tunnel Response	
7.2.14	Modify Bearer Command and Failure Indication	
7.2.14.1	Modify Bearer Command	
7.2.14.2	Modify Bearer Failure Indication	
7.2.15	Update Bearer Request	
7.2.16	Update Bearer Response	
7.2.17	Delete Bearer Command and Failure Indication	
7.2.17.1	Delete Bearer Command	
7.2.17.2	Delete Bearer Failure Indication	
7.2.18	Create Indirect Data Forwarding Tunnel Request	
7.2.19	Create Indirect Data Forwarding Tunnel Response	
7.2.20	Void	
7.2.21 7.2.22	Release Access Bearers Request	
	Release Access Bearers Response	
7.2.23	Stop Paging Indication	
7.2.24 7.2.25	Modify Access Bearers Request Modify Access Bearers Response	
7.2.25	Remote UE Report Notification	
7.2.20	Remote UE Report Acknowledge	
7.3	Mobility Management Messages	
7.3.1	Forward Relocation Request.	
7.3.2	Forward Relocation Response	
7.3.3	Forward Relocation Complete Notification	
7.3.4	Forward Relocation Complete Acknowledge	
7.3.5	Context Request	
7.3.6	Context Response	
7.3.7	Context Acknowledge	
7.3.8	Identification Request	
7.3.9	Identification Response	
7.3.10	Forward Access Context Notification	
7.3.11	Forward Access Context Acknowledge	
7.3.12	Detach Notification	
7.3.13	Detach Acknowledge	
7.3.14	Change Notification Request	
7.3.15	Change Notification Response	
7.3.16	Relocation Cancel Request	
7.3.17	Relocation Cancel Response	
7.3.18	Configuration Transfer Tunnel	
7.3.19	RAN Information Relay	
7.3.20	ISR Status Indication	
7.3.21	UE Registration Query Request	
7.3.22	UE Registration Query Response	

7.4	CS Fallback and SRVCC related messages	243
7.4.1	Suspend Notification.	
7.4.2	Suspend Acknowledge	
7.4.3	Resume Notification	
7.4.4	Resume Acknowledge	
7.4.5	CS Paging Indication	
7.4.6	Alert MME Notification	
7.4.7	Alert MME Acknowledge	
7.4.8	UE Activity Notification	
7.4.9	UE Activity Acknowledge	
7.5	Non-3GPP access related messages	
7.5.1	Create Forwarding Tunnel Request	
7.5.2	Create Forwarding Tunnel Response	
7.6	Reliable Delivery of Signalling Messages	
7.7	Error Handling	
7.7.0	Handling Piggybacked Messages	
7.7.1	Protocol Errors	
7.7.2	Different GTP Versions	
7.7.3	GTP Message of Invalid Length	
7.7.4	Unknown GTP Message	
7.7.5	Unexpected GTP Message	
7.7.6	Missing Information Elements	
7.7.7	Invalid Length Information Element	
7.7.8	Semantically incorrect Information Element	
7.7.9	Unknown or unexpected Information Element	
7.7.10	Repeated Information Elements	
7.7.11	TFT Error Handling	
7.8	Path Failure	
7.9	Restoration and Recovery	
7.9.0	General	
7.9.1	Delete PDN Connection Set Request	
7.9.2	Delete PDN Connection Set Response	
7.9.3	Update PDN Connection Set Request	
7.9.3	Update PDN Connection Set Response	
7.9.4	PGW Restart Notification	
7.9.6	PGW Restart Notification Acknowledge	
7.9.7	PGW Downlink Triggering Notification	
7.9.8	PGW Downlink Triggering Acknowledge	
7.10	Fallback to GTPv1 mechanism	
7.11	Fallback to GTPv0	
7.12	Trace Management Messages	
7.12.1	Trace Session Activation	
7.12.2	Trace Session Deactivation	
7.13	MBMS Messages	
7.13.1	MBMS Session Start Request	
7.13.2	MBMS Session Start Response	
7.13.3	MBMS Session Update Request	
7.13.4	MBMS Session Update Response	
7.13.5	MBMS Session Stop Request	
7.13.6	MBMS Session Stop Response	
0		
	GTP-C Information Elements	
8.1	Information Element Types	
8.2	Information Element Format	
8.2.1	General	
8.2.1A	v 1	
8.2.2	Handling ASN.1/PER encoded parameters	
8.3	International Mobile Subscriber Identity (IMSI)	
8.4	Cause	
8.5	Recovery (Restart Counter)	
8.6	Access Point Name (APN)	
8.7	Aggregate Maximum Bit Rate (AMBR)	

8.8	EPS Bearer ID (EBI)	
8.9	IP Address	278
8.10	Mobile Equipment Identity (MEI)	278
8.11	MSISDN	278
8.12	Indication	
8.13	Protocol Configuration Options (PCO)	
8.14	PDN Address Allocation (PAA)	
8.15	Bearer Quality of Service (Bearer QoS)	
8.16	Flow Quality of Service (Flow QoS)	
8.17	RAT Type	
8.18	Serving Network	
8.19	EPS Bearer Level Traffic Flow Template (Bearer TFT)	
8.20	Traffic Aggregate Description (TAD)	
8.21	User Location Information (ULI)	
8.21.1	CGI field	
8.21.2	SAI field	
8.21.3	RAI field	
8.21.4	TAI field	
8.21.5	ECGI field	
8.21.6	LAI field	
8.21.7	– Macro eNodeB ID field	
8.21.8	Extended Macro eNodeB ID field	
8.22	Fully Qualified TEID (F-TEID)	
8.23	TMSI	
8.24	Global CN-Id	
8.25	S103 PDN Data Forwarding Info (S103PDF)	
8.26	S1-U Data Forwarding (S1UDF)	
8.27	Delay Value	
8.28	Bearer Context	
8.29	Charging ID	
8.30	Charging Characteristics	
8.31	Trace Information	
8.32	Bearer Flags	
8.32	Void	
8.34	PDN Type	
8.34 8.35	Procedure Transaction ID (PTI)	
8.35	Void	
8.30 8.37	Void	
	MM Context	
8.38	PDN Connection	
8.39		
8.40	PDU Numbers	
8.41	Packet TMSI (P-TMSI)	
8.42	P-TMSI Signature	
8.43	Hop Counter	
8.44	UE Time Zone	
8.45	Trace Reference	
8.46	Complete Request Message	
8.47	GUTI	
8.48	Fully Qualified Container (F-Container)	
8.49	Fully Qualified Cause (F-Cause)	
8.50	PLMN ID	
8.51	Target Identification	
8.52	Void	
8.53	Packet Flow ID	
8.54	RAB Context	
8.55	Source RNC PDCP context info	314
8.56	Port Number	
8.57	APN Restriction	314
8.58	Selection Mode	
8.59	Source Identification	
8.60	Void	
8.61	Change Reporting Action	316

8.62	Fully qualified PDN Connection Set Identifier (FQ-CSID)	
8.63	Channel needed	
8.64	eMLPP Priority	
8.65	Node Type	
8.66	Fully Qualified Domain Name (FQDN)	
8.67	Private Extension	
8.68	Transaction Identifier (TI)	
8.69	MBMS Session Duration.	
8.70	MBMS Service Area	
8.71	MBMS Session Identifier	
8.72	MBMS Flow Identifier	
8.73	MBMS IP Multicast Distribution	
8.74	MBMS Distribution Acknowledge	
8.75	User CSG Information (UCI)	
8.76	CSG Information Reporting Action	
8.77	RFSP Index	
8.78	CSG ID	
8.79	CSG Membership Indication (CMI)	
8.80	Service indicator	
8.81	Detach Type	
8.82	Local Distinguished Name (LDN)	
8.83	Node Features	
8.84	MBMS Time to Data Transfer	
8.85	Throttling	
8.86	Allocation/Retention Priority (ARP)	
8.87	EPC Timer	
8.88	Signalling Priority Indication	
8.89	Temporary Mobile Group Identity (TMGI)	
8.90	Additional MM context for SRVCC	
8.91	Additional flags for SRVCC	
8.92	Void	
8.93	MDT Configuration	
8.94	Additional Protocol Configuration Options (APCO)	
8.95	Absolute Time of MBMS Data Transfer	
8.96	H(e)NB Information Reporting	
8.97	IPv4 Configuration Parameters (IP4CP)	
8.98	Change to Report Flags	
8.99	Action Indication	
8.100	TWAN Identifier	
8.101	ULI Timestamp	
8.102	MBMS Flags	
8.103	RAN/NAS Cause	
8.104	CN Operator Selection Entity	
8.105	Trusted WLAN Mode Indication	
8.106	Node Number	
8.107	Node Identifier	
8.108	Presence Reporting Area Action	
8.109	Presence Reporting Area Information	
8.110	TWAN Identifier Timestamp	
8.111	Overload Control Information	
8.112	Load Control Information	
8.113	Metric	
8.114	Sequence Number	
8.115	APN and Relative Capacity	
8.116	WLAN Offloadability Indication	
8.117	Paging and Service Information	
8.117	Integer Number	
8.119	Millisecond Time Stamp	
8.120	Monitoring Event Information	
8.120 8.121	ECGI List	
8.121 8.122	Remote UE Context	
8.122 8.123	Remote User ID	
0.123		

8.124	Remote UE IP Information	
8.125	CIoT Optimizations Support Indication	
8.126	SCEF PDN Connection	
8.127	Header Compression Configuration	
8.128	Extended Protocol Configuration Options (ePCO)	
8.129	Serving PLMN Rate Control	351
8.130	Counter	
8.131	Mapped UE Usage Type	
9	Security	352
	-	
	IP - The Networking Technology used by GTP	
10.1	IP Version	
10.2	IP Fragmentation	
11	Notification of supported features between peer GTP-C entities	
11.1	General	
11.1.1	Introduction	
11.1.2	Defining a feature	
11.2	Dynamic discovery of supported features	
11.2.1	General	
11.2.2	Features supported by direct peer GTP-C entities	
12	GTP-C load & overload control mechanism	252
12.1		
12.1	General GTP-C overload problem	
12.1.1	Scenarios leading to overload	
12.1.2	Load & overload control concepts	
12.1.5	Load control solution	
12.2.1	Principles of load control	
12.2.2	Applicability to 3GPP and non-3GPP access based interfaces	
12.2.3	Node level load control	
12.2.4	APN level load control	
12.2.4.		
12.2.4.		
12.2.4.	3 Elements of APN load control	
12.2.5	Load Control Information	
12.2.5.	1 Definition	
12.2.5.	1.1 General description	358
12.2.5.		
12.2.5.	1	
12.2.5.		
12.2.5.		
12.2.5.		
12.2.5.		
12.2.5. 12.2.6		
12.2.0	Discovery of the support of the feature by the peer node Issues in the network with partial support of the feature	
12.2.7	Overload control solution	
12.3	Principles of overload control	
12.3.1	Applicability to 3GPP and non-3GPP access based interfaces	362
12.3.3	Node level overload control	
12.3.4	APN level overload control	
12.3.4.		
12.3.4.		
12.3.5	Overload Control Information	
12.3.5.		
12.3.5.		
12.3.5.		
12.3.5.	1.2.1 Overload Control Sequence Number	
12.3.5.		
12.3.5.		
12.3.5.	1.2.4 List of APNs	

12.3.5.1.3	Handling of p	parameters	
12.3.5.2		lusion	
12.3.5.3		Im number of instances	
12.3.6	Propagating the MM	E/S4-SGSN identity to the PGW	368
12.3.7	Updating the PGW v	vith overload control information of the target MME/S4-SGSN	368
12.3.8	The interaction with	APN congestion control using the PGW Back-Off Time	369
12.3.9	Message throttling		369
12.3.9.1			
12.3.9.2	Throttling algorit	hm – "Loss"	370
12.3.9.2.1	Description		370
12.3.9.3		zation	
12.3.9.3.1	-		
12.3.9.3.2	-	cedures	
12.3.9.3.3		sion parameters	
12.3.9.3.4		Message Priority signalled in the GTP-C message	
12.3.10		load control	
12.3.10.1			
12.3.10.2		o enforcement of the overload control	
12.3.10.2.1		nput of the network	
12.3.10.2.2		essing efficiency at the source GTP-C entity	
12.3.10.2.3		n by the overloaded GTP-C entity	
12.3.10.3		overload control between GTP-C entities in direct contact	
12.3.10.4		overload control between remote GTP-C entities	
12.3.10.4.1			
12.3.11		port of the feature by the peer node	
12.3.12		with partial support of the feature	
12.3.13	Implicit overload coi	ntrol mechanisms	
13 Dete	ction and handling o	f late arriving requests	375
		of requests which collide with an existing session context	
13.2.1			
13.2.2			
13.3 D		of requests which have timed out at the originating entity	
13.3.1			
13.3.2	Principles		376
14 Hand	lling of Bearer Cont	exts Mismatch	377
14 Haik 14.1 G	anaral		
		text Mismatch	
		text Mismatch	
14.3.1			
14.3.2		NS	
11.5.2	Exceptional sectority		
Annex A (Informative): E	Backward Compatibility Guidelines for Information Elements	379
Annov D ([nformativa]. 7	Frenchant conving of DANAD/S1AD IEs into CTD IEs	280
		Fransparent copying of RANAP/S1AP IEs into GTP IEs	
		lated generic transparent Containers over RANAP, S1-AP and GTP	
		AP IEs	
Б.3 О	ulei KANAF allu SI-F	AF 1ES	
Annex C (Normative): N	MME/S4-SGSN mapping table between S11/S4 and NAS Cause	
		alues	383
•	,	GTP-C load and overload control mechanism	
		pporting Load Control	
		pporting Overload Control	
		hm	
		plementation	
		d control between remote GTP-C entities	
D.4.1 E	xample of possible imp	plementation	

Annex E (Normative):	TWAN mapping table between GTPv2 S2a Cause and non-3GPP access Cause values	392
Annex F (Informative):	Change History	396
History		413

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the stage 3 of the control plane of the GPRS Tunnelling Protocol, Version 2 for Evolved Packet System interfaces (GTPv2-C).

In this document, unless otherwise specified, the S2a, S2b, S5 and S8 interfaces refer always to the GTP-based S2a, S2b, S5 and S8 interfaces respectively .

GTPv2-C shall be used across the following EPC signalling interfaces: S2a, S2b, S3, S4, S5, S8, S10, S11 and S16.

GTPv2-C shall be used across the Sm and Sn interfaces for MBMS in EPS.

GTPv2-C based protocols shall also be used across Sv (3GPP TS 29.280 [15]) and S101/S121 (3GPP TS 29.276 [14]) interfaces.

The procedures supported between the TWAN and the PGW on the S2a interface, and between the ePDG and the PGW on the S2b interface are specified in 3GPP TS 23.402 [45].

The present document specifies functions, procedures and information which apply to GERAN Iu mode. However, functionality related to GERAN Iu mode is neither maintained nor enhanced.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access".
- [4] 3GPP TS 29.060: "General Packet Radio Service (GPRS); GPRS Tunnelling Protocol (GTP) across the Gn and Gp interface".
- [5] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [6] IETF RFC 791 (STD 0005): "Internet Protocol", J. Postel.
- [7] IETF RFC 768 (STD 0006): "User Datagram Protocol", J. Postel.
- [8] 3GPP TS 32.251: "Telecommunication Management; Charging Management; Packet Switched (PS) domain charging.
- [9] 3GPP TS 32.298: "Telecommunication Management; Charging Management; Charging Data Record (CDR) parameter classification.
- [10] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
- [11] 3GPP TS 33.102: "3G security; Security architecture".
- [12] 3GPP TS 33.401: "3GPP System Architecture Evolution (SAE); Security architecture".

- [13] 3GPP TS 29.281: "General Packet Radio System (GPRS) Tunnelling Protocol User Plane (GTPv1-U)".
- [14] 3GPP TS 29.276: "3GPP Evolved Packet System (EPS); Optimized handover procedures and protocols between E-UTRAN Access and cdma2000 HRPD Access; Stage 3".
- [15] 3GPP TS 29.280: "Evolved Packet System (EPS); 3GPP Sv interface (MME to MSC, and SGSN to MSC) for SRVCC".
- [16] IETF RFC 2460: "Internet Protocol, Version 6 (IPv6) Specification".
- [17] 3GPP TS 23.007: "Restoration procedures".
- [18] 3GPP TS 32.422: "Telecommunication management; Subscriber and equipment trace; Trace control and configuration management ".
- [19] 3GPP TS 36.300: "Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2".
- [20] 3GPP TS 36.414: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 data transport".
- [21] 3GPP TS 23.272: "Circuit Switched (CS) fallback in Evolved Packet System (EPS); Stage 2".
- [22] 3GPP TS 29.118: "Mobility Management Entity (MME) Visitor Location Register (VLR) SGs interface specification".
- [23] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".
- [24] void
- [25] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [26] 3GPP TS 29.275: "Proxy Mobile IPv6 (PMIPv6) based Mobility and Tunnelling protocols; Stage 3".
- [27] 3GPP TS 44.018: "Mobile radio interface layer 3 specification; Radio Resource Control Protocol".
- [28] 3GPP TS 48.008: "Mobile Switching Centre Base Station System (MSC-BSS) interface; Layer 3 specification".
- [29] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [30] 3GPP TS 24.007: "Mobile radio interface signalling layer 3; General Aspects".
- [31] IETF RFC 1035: "Domain Names Implementation and Specification".
- [32] 3GPP TS 29.303: "Domain Name System Procedures; Stage 3".
- [33] 3GPP TS 25.413: "UTRAN Iu interface Radio Access Network Application Part (RANAP) signalling".
- [34] 3GPP TS 48.018: "General Packet Radio Service (GPRS); Base Station System (BSS) Serving GPRS Support Node (SGSN); BSS GPRS protocol (BSSGP)".
- [35] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2".

- [36] 3GPP TS 32.295: "Telecommunication management; Charging management; Charging Data Record (CDR) transfer".
- [37] 3GPP TS 23.246: "Multimedia Broadcast/Multicast Service (MBMS); Architecture and functional description".
- [38] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN) ".
- [39] IETF RFC 3588: "Diameter Base Protocol ".
- [40] IETF RFC 4607: "Source-Specific Multicast for IP".
- [41] 3GPP TS 29.002: "Mobile Application Part (MAP) specification".
- [42] 3GPP TS 29.010: "Information element mapping between Mobile Station Base Station System (MS - BSS) and Base Station System - Mobile-services Switching Centre (BSS - MSC); Signalling procedures and the Mobile Application Part (MAP)".
- [43] 3GPP TS 23.216: "Single Radio Voice Call Continuity (SRVCC); Stage 2".
- [44] 3GPP TS 32.423: "Telecommunication management; Subscriber and equipment trace: Trace data definition and management".
- [45] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses.
- [46] 3GPP TR 25.999: "HSPA Evolution (FDD)".
- [47] 3GPP TS 23.292: "IP Multimedia Subsystem (IMS) centralized services".
- [48] 3GPP TS 23.203: "Policy and charging control architecture; Stage 2".
- [49] ITU-T Recommendation X.691 (07/2002): "Information technology ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)".
- [50] 3GPP TS 33.402: "3GPP System Architecture Evolution (SAE); Security aspects of non-3GPP accesses".
- [51] 3GPP TS 23.139: "3GPP system fixed broadband access network interworking; Stage 2".
- [52] IEEE Std 802.11-2012: "IEEE Standard for Information technology Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [53] IETF RFC 5905: "Network Time Protocol Version 4: Protocol and Algorithms Specification".
- [54] 3GPP TS 32.299: "Telecommunication Management; Charging Management; Diameter charging applications.
- [55] 3GPP TS 23.251: " Network Sharing; Architecture and Functional Description".
- [56] 3GPP TS 23.271: "Location Services".
- [57] 3GPP TS 29.173: "Diameter-based SLh interface for Control Plane LCS".
- [58] IETF RFC 5453: "Reserved IPv6 Interface Identifiers".
- [59] IETF RFC 4776: "Dynamic Host Configuration Protocol (DHCPv4 and DHCPv6) Option for Civic Addresses Configuration Information".
- [60] IETF RFC 3046: "DHCP Relay Agent Information Option".
- [61] 3GPP TS 23.380: "IMS Restoration Procedures".
- [62] 3GPP TS 22.153: "Multimedia Priority Service".

- [63] 3GPP TS 24.302: "Access to the 3GPP Evolved Packet Core (EPC) via non-3GPP access networks; stage 3".
- [64] ITU-T Recommendation E.212: "The international identification plan for mobile terminals and mobile users".
- [65] IETF RFC 2474: "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers".
- [66] 3GPP TS 24.244: "Wireless LAN control plane protocol for trusted WLAN access to EPC".
- [67] IETF RFC 7296: "Internet Key Exchange Protocol Version 2 (IKEv2)".
- [68] 3GPP TS 29.273: "3GPP EPS AAA Interfaces".
- [69] 3GPP TS 29.336: "Home Subscriber Server (HSS) diameter interfaces for interworking with packet data networks and applications".
- [70] 3GPP TS 29.272: "Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol".
- [71] 3GPP TS 23.161: "Network-Based IP Flow Mobility (NBIFOM); Stage 2".
- [72] 3GPP TS 23.303: "Proximity-based services (ProSe); Stage 2".
- [73] 3GPP TS 24.161: "Network-Based IP Flow Mobility (NBIFOM); Stage 3".
- [74] 3GPP TS 23.682: "Architecture enhancements to facilitate communications with packet data networks and applications".
- [75] 3GPP TS 23.040: "Technical realization of the Short Message Service (SMS)".
- [76] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA); Packet Data Convergence Protocol (PDCP) specification".
- [77] IETF RFC 4995: "The RObust Header Compression (ROHC) Framework".
- [78] 3GPP TS 43.020: "Security related network functions".
- [79] 3GPP TS 36.444: "EUTRAN M3 Application Protocol (M3AP)".
- [80] 3GPP TS 29.244: "Interface between the Control Plane and the User Plane of EPC Nodes; stage 3".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

GTP-PDU: GTP Protocol Data Unit is either a GTP-C Message or a GTP-U Message. GTP-U Message may be either a signalling message across the user plane tunnel, or a G-PDU (see clause 6).

- Signalling Message: any GTP-PDU (GTP-C or GTP-U) except the G-PDU.
- **G-PDU:** GTP user plane message, which carries the original packet (payload). G-PDU consists of GTP-U header and a T-PDU.
- **T-PDU:** original packet, for example an IP datagram, from an UE or a network node in an external packet data network. A T-PDU is the payload that is tunnelled in the GTP-U tunnel.

- **GTP-C Message:** GTP control plane message type of a GTP-PDU. GTP-C message consists of GTP-C header, which is followed by zero or more information elements.
- **GTP-U Message:** GTP user plane message. The user plane messages are used to carry user data packets, and also signalling messages e.g. for path management and error indication. Therefore, GTP-U message consists of GTP-U header, which is followed by either a T-PDU, or zero or more information elements.

GTP Tunnel: A GTP tunnel is a communication tunnel between two GTP nodes (see subclause 4.1 "GTP Tunnel").

PDN Connection: "PDN Connection" in this specification only refers to the PDN connection through the SGW and PGW.

SCEF PDN Connection: The PDN connection to the SCEF. Unless otherwise indicated in a clause or subclause, "PDN Connections" do not refer to any SCEF PDN Connection.

Tunnel Endpoint: A tunnel endpoint is identified with a TEID, an IP address and a UDP port number (see subclause 4.1 "GTP Tunnel").

Tunnel Endpoint Identifier (TEID): unambiguously identifies a tunnel endpoint in scope of a path (see subclause 4.1 "GTP Tunnel").

3.2 Symbols

For the purposes of the present document, the following symbols apply:

S1-U	Interface between SGW and eNodeB
X2	Interface between eNodeBs

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AMBR	Aggregate Maximum Bit Rate
APN	Access Point Name
APN-NI	Access Point Name Network Identifier
APN-OI	Access Point Name Operator Identifier
C-MSISDN	Correlation MSISDN
EBI	EPS Bearer ID
eNodeB	Evolved Node B
EPC	Evolved Packet Core
ePDG	Evolved Packet Data Gateway
EPS	Evolved Packet System
F-TEID	Fully Qualified Tunnel Endpoint Identifier
G-PDU	GTP-U non-signalling PDU
GPRS	General Packet Radio Service
GTP	GPRS Tunnelling Protocol
GTP-PDU	GTP-C PDU or GTP-U PDU
GTPv2-C	GTP version 2, control plane
GTPv2-U	GTP version 2, user plane
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
LBI	Linked EPS Bearer ID
L1	Layer 1
L2	Layer 2
LGW	Local Gateway
LIPA	Local IP Access
MBMS	Multimedia Broadcast/Multicast Service
MEI	Mobile Equipment Identity
MSISDN	Mobile Subscriber ISDN Number
NBIFOM	Network-based IP Flow Mobility

NTP	Network Time Protocol
PAA	PDN Address Allocation
PCO	Protocol Configuration Options
PDU	Protocol Data Unit
PDN	Packet Data Network or Public Data Network
PGW	PDN Gateway
PTI	Procedure Transaction Id
QoS	Quality of Service
RAT	Radio Access Technology
RIM	RAN Information Management
SGW	Serving Gateway
SPID	Subscriber Profile ID for RAT/Frequency Priority
STN-SR	Session Transfer Number for SRVCC
TEID	Tunnel Endpoint Identifier
TEID-C	Tunnel Endpoint Identifier, control plane
TEID-U	Tunnel Endpoint Identifier, user plane
TFT	Traffic Flow Template
TLIV	Type Length Instance Value
TWAN	Trusted WLAN Access Network
UDP	User Datagram Protocol
ULI	User Location Information

4 General

4.1 GTP Tunnel

GTP tunnels are used between two nodes communicating over a GTP based interface, to separate traffic into different communication flows.

A GTP tunnel is identified in each node with a TEID, an IP address and a UDP port number. The receiving end side of a GTP tunnel locally assigns the TEID value the transmitting side has to use. The TEID values are exchanged between tunnel endpoints using GTP-C or S1-MME or Iu-PS messages. The GTPv2 entity communicates to the peer GTPv2 entity the TEID value at which it expects to receive all subsequent control plane messages related to that GTP tunnel via the:

- "Sender F-TEID for Control Plane" IE,
- "PGW S5/S8/S2a/S2b F-TEID for PMIP based interface or for GTP based Control Plane interface" IE,
- "MSC Server Sv TEID for Control Plane" IE,
- "S3/S16/S10 Address and TEID for Control Plane" IE, or
- "MME/SGSN Sv TEID for Control Plane" IE.

The criteria defining when the same or different GTP tunnels shall be used between the two nodes differs between the control and the user plane, and also between interfaces.

For the control plane, for each end-point of a GTP-C tunnel:

- The TEID-C shall be unique per PDN-Connection on GTP based S2a, S2b, S5 and S8 interfaces. The same tunnel shall be shared for the control messages related to all bearers associated to the PDN-Connection. A TEID-C on the S2a/S2b/S5/S8 interface shall be released after all its associated EPS bearers are deleted.
- There shall be only one pair of TEID-Cs per UE on each of the S3, S10 and the S16 interfaces. The same tunnel shall be shared for the control messages related to the same UE operation. A TEID-C on the S3/S10/S16 interface shall be released after its associated UE context is removed or the UE is detached. For the S3 interface, when ISR is active for the UE, during I-RAT handover between the ISR associated nodes, the existing S3 TEID-C may be re-used or new S3 TEID-C may be allocated. During this scenario, if the node decides to allocate new S3 TEID-C, it shall release its own old S3 TEID-C.
- There shall be only one pair of TEID-C per UE over the S11 and the S4 interfaces. The same tunnel shall be shared for the control messages related to the same UE operation. A TEID-C on the S11/S4 interface shall be released after all its associated EPS bearers are deleted.
- There shall be only one pair of TEID-C per MBMS Bearer Service (i.e. per TMGI and MBMS Flow Identifier, if the MBMS Flow Identifier is provided; or per TMGI, if the MBMS Flow Identifier is not provided) over the Sm and Sn interfaces respectively. The same tunnel shall be shared for the control messages related to the same MBMS Bearer Service. A TEID-C on the Sm/Sn interface shall be released after the MBMS Bearer Session is stopped.

For GTP-U, a TEID-U is used according to 3GPP TS 29.281 [13].

NOTE: GTP-U is based on GTP version 1 (GTPv1).

4.2 Protocol stack

4.2.0 General

The protocol stack for GTPv2 shall be as depicted in Figure 4.2.0-1.




Figure 4.2.0-1: GTPv2 stack

The GTPv2 headers are specified in the respective clauses of this specification.

The source and destination IP addresses and UDP ports used for each GTP-C message depend on the role that the message plays in a message exchange. A message can be an Initial message, or a Triggered message, or a Triggered message. An Initial message is sent to a peer GTP entity with a sequence number chosen by the sending entity (see subclause 7.6). A Triggered message is sent in response to an Initial message. Triggered Reply message may be sent in response to a Triggered message. See subclause 7.6 for the sequence number usage.

Typically, a Request message is an Initial message, but a Request message may be a Triggered messages in certain procedures where they are triggered by an Initial Command message. See subclause 4.2.5 for classification of the Initial messages and their possible Triggered messages, as well as cases where there are Triggered Reply messages to the Triggered messages.

Piggybacking is an optional feature, which is described in Annex F of 3GPP TS 23.401 [3]. If the feature is supported, then the piggybacking of the initial messages on triggered response messages for EUTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN (see sub-clauses 8.6 and 16.11 of 3GPP TS 23.402 [45]) and UE-requested PDN Connectivity procedures shall be implemented as per requirements in subclauses 4.2.0 and 5.5.1 of this specification .When piggybacking is used, a common IP header and a common UDP header shall be used for the triggered response message and the piggybacked initial message as depicted in Figure 4.2.0-2. Immediately following the triggered response message is the piggybacked initial message, following which no additional information shall be present. The subclause 5.5 specifies the usage of piggybacking-specific fields in the GTP-C header.

IP header	UDP header	Triggered response message (P=1)	Piggybacked initial message (P=0)
		(P=1)	(P=0)

Figure 4.2.0-2: Packet Format for the Piggybacking of messages

4.2.1 UDP header and port numbers

4.2.1.0 General

A User Datagram Protocol (UDP) compliant with IETF RFC 768 [7] shall be used.

4.2.1.1 Initial Messages

The UDP Destination Port number for GTPv2 Initial messages shall be 2123. It is the registered port number for GTP-C.

The UDP Source Port for a GTPv2 Initial message is a locally allocated port number at the sending GTP entity.

If GTPv2 and GTP' v2 modules are using the same IP address for sending messages, the implementation shall ensure that while some source port number is used by GTPv2 messages, the same source port number shall not be used by GTP' v2 messages. Otherwise, the IP interface may have difficulty to delivering a response message to the right protocol entity.

4.2.1.2 Triggered Messages

The UDP Destination Port value of a GTPv2 Triggered message and for a Triggered Reply message shall be the value of the UDP Source Port of the corresponding message to which this GTPv2 entity is replying, except in the case of the SGSN pool scenario.

The UDP Source Port of a GTPv2 Triggered message and for a Triggered Reply message shall be the value from the UDP Destination Port of the corresponding message to which this GTPv2 entity is replying, except in the case of the SGSN pool scenario.

In the SGSN pool scenario, if the Identification Request, the Context Request or the Suspend Notification messages have been forwarded by another SGSN in the pool, the UDP Destination Port for the Identification Response, the Context Response or the Suspend Acknowledge message shall be determined in the following way. The value from the information element "UDP Source Port Number", which was sent in the corresponding forwarded request, shall be copied into the UDP Destination Port field. The UDP Source Port for the Identification Response, the Context Response or the Suspend Acknowledge message may be a locally allocated port number at the sending GTP entity.

In the handover scenario when the CIoT feature is deployed, if the Forward Relocation Request message has been forwarded by the target MME, the UDP Destination Port for the Forward Relocation Response shall be set to the value of Source UDP Port Number IE included in the Forward Relocation Request message; the UDP Source Port for the Forward Relocation Response message may be a locally allocated port number at the sending GTP entity.

4.2.1.3 Piggybacked Messages

A piggybacked initial message is carried as a concatenation after a triggered response message and they share a common UDP header (see Figure 4.2.0-2).

The UDP Destination port for the IP packet containing both the triggered response message and the piggybacked initial message shall be the same as the port number used for the triggered response message.

The UDP Source port for the IP packet containing both the triggered response message and the piggybacked initial message shall be the same as the port number used for the triggered response message.

4.2.2 IP header and IP addresses

4.2.2.1 Initial Messages

The IP Destination Address of a GTPv2 Initial message shall be an IP address of the destination GTPv2 entity.

During the establishment of the GTP tunnel, the GTPv2 entity selects and communicates to the peer GTPv2 entity the IP Destination Address at which it expects to receive subsequent control plane Initial messages related to that GTP tunnel via the:

- "Sender F-TEID for Control Plane" IE,
- "PGW S5/S8/S2a/S2b F-TEID for PMIP based interface or for GTP based Control Plane interface" IE,
- "MSC Server Sv Address for Control Plane" IE,
- "S3/S16/S10 Address and TEID for Control Plane" IE, or

- "MME/SGSN Sv Address for Control Plane" IE.

During the network triggered service restoration procedure (see 3GPP TS 23.007 [17]), if an MME/S4-SGSN sends a Downlink Data Notification Failure Indication message to the SGW, then the destination address for this message shall be the SGW IP address signalled via the Sender F-TEID for Control Plane IE in the Downlink Data Notification message (if present in the message), otherwise the source IP address of the Downlink Data Notification message received earlier.

The IP Source Address of a GTPv2 Initial message shall be an IP address of the source GTPv2 entity from which the Initial message is originating.

4.2.2.2 Triggered Messages

The IP Destination Address of a GTPv2 Triggered message and for a Triggered Reply message shall be copied from the IP Source Address of the message to which this GTPv2 entity is replying, except in the case of the SGSN pool scenario.

The IP Source Address of a GTPv2 Triggered message and for a Triggered Reply message shall be copied from the IP destination address of the message to which this GTPv2 entity is replying, except in the case of SGSN pool scenario and handover scenario when the CIoT feature is deployed.

In the SGSN pool scenario, if the Identification Request, the Context Request or the Suspend Notification messages have been forwarded by another SGSN in the pool, the IP Source address for the Identification Response, the Context Response or the Suspend Acknowledge messages shall be locally allocated by the sending GTP entity. The IP Destination Address for the Identification Response, the Context Response or the Suspend Acknowledge messages shall be determined in the following way. The value from the information element "Address for Control Plane", which was sent in the corresponding Identification Request or the Suspend Notification message; or the value from the information element "S3/S16/S10 Address and TEID for Control Plane", which was sent in the corresponding Context Request message, shall be copied into the IP Destination Address field.

In the handover scenario when the CIoT feature is deployed, if the Forward Relocation Request message has been forwarded by the target MME, the IP Source address of the Forward Relocation Response shall be locally allocated by the sending GTP entity. The IP Destination Address field of the Forward Relocation Response shall be set to the value of the "Sender's F-TEID for Control Plane" IE received in the Forward Relocation Request message.

4.2.2.3 Piggybacked Messages

A piggybacked initial message is carried as a concatenation after a triggered response message and they share a common IP header (see Figure 4.2.0-2).

The IP Source Address for the IP packet containing both the triggered response message and the piggybacked initial message shall be the same as the IP Address used for the triggered response message.

The IP Destination Address for the IP packet containing both the triggered response message and the piggybacked initial message shall be the same as the IP Address used for the triggered response message.

4.2.3 Layer 2

Typically Ethernet should be used as a Layer 2 protocol, but operators may use any other technology.

4.2.4 Layer 1

Operators may use any appropriate Layer 1 technology.

4.2.5 Messages with GTPv2 defined replies: Classification of Initial and Triggered Messages

An Initial message is a GTPv2 message that is not triggered as a response to another GTPv2 message across the given interface.

The expected reply to a Request message is a Triggered message and the reply has the same message name as the Request but with "Response" replacing "Request".

3GPP TS 29.274 version 14.7.0 Release 14

NOTE 1: If the SGW receives a "Create Session Request" on S11/S4, this can trigger either of the following GTPv2 messages across S5/S8: "Create Session Request" or "Modify Bearer Request". However, neither of these messages across S5/S8 is considered to be a Triggered message.

If a Request message is a reply to a Command message, then the Request message is a Triggered message; otherwise the Request message is an Initial message. Responses do not have replies except when a "Context Acknowledge" is required as a reply to "Context Response" message as specified in relevant Stage 2 procedures. Context Acknowledge is always triggered message and does not have a reply.

NOTE 2: The "Context Acknowledge" message is sent only if the "Context Response" message is received with the acceptance cause.

A message whose name ends in "Command" is always an initial message. If a "Command" message fails, the name of the reply message is constructed by replacing "Command" with "Failure Indication". Apart from "Downlink Data Notification Failure Indication" message, a "Failure Indication" is a Triggered message. The "Failure Indication" message does not have a reply. If a "Command" message is successful, its reply will be a Request as specified in relevant Stage 2 procedures.

A message whose name ends in "Notification" is always an Initial message, The expected Triggered message in reply has the same message name but with "Acknowledge" replacing "Notification", except for the case of the message "Downlink Data Notification" which has the reply "Downlink Data Notification Acknowledge" and "PGW Resart Notification" which has the reply "PGW Restart Notification Acknowledge". An "Acknowledge" message does not have a reply.

CS Paging Indication, Stop Paging Indication, RAN Information Relay, Configuration Transfer Tunnel, Trace Session Activation, Trace Session Deactivation, ISR Status Indication and Downlink Data Notification Failure Indication messages are Initial messages that do not have a reply.

A Version Not Supported Indication message is a Triggered message.

4.3 Transmission Order and Bit Definitions

The messages in this document shall be transmitted in network octet order starting with octet 1 with the Most Significant Bit sent first.

The most significant bit of an octet in a GTP message is bit 8. If a value in a GTP message spans several octets and nothing else is stated, the most significant bit is bit 8 of the octet with the lowest number.

5 GTP Header for Control Plane

5.1 General format

Control Plane GTP uses a variable length header. Control Plane GTP header length shall be a multiple of 4 octets. Figure 5.1-1 illustrates the format of the GTPv2-C Header.

				Bi	ts				
Octets	8	7	6	5	4	3	2	1	
1		Version		Р	Т	Spare	Spare	Spare	
2		Message Type							
3		Message Length (1 st Octet)							
4		Message Length (2 nd Octet)							
m to	If T flag is set to 1, then TEID shall be placed into octets 5-								
k(m+3)	8. Otherwise, TEID field is not present at all.								
n to (n+2)		Sequence Number							
(n+3)	Spare								

Figure 5.1-1: General format of GTPv2 Header for Control Plane

Where:

- if T = 0, TEID field is not present, k = 0, m = 0 and n = 5;

- if T = 1, TEID field is present, k = 1, m = 5 and n = 9.

The usage of GTPv2-C header across the EPC specific interfaces is defined in the subclause 5.5 "Usage of the GTPv2-C Header". Octet 1 bits shall be coded as follows:

- Bits 6-8 represent the Version field.
- Bit 5 represents the Piggybacking flag (P).
- Bit 4 represents the TEID flag (T).
- Bits 3-1 are spare, the sender shall set them to "0" and the receiving entity shall ignore them.

5.2 Control Plane GTP Extension Header

The legacy Extension Header mechanism is not used for the GTP version 2 control plane (GTPv2-C). Future extensions will be implemented by adding Information Elements in the message body if new parameters are needed.

5.3 GTP-C header for Echo and Version Not Supported Indication messages

The GTPv2-C message header for the Echo Request, Echo Response and Version Not Supported Indication messages shall not contain the TEID field, but shall contain the Sequence Number fields, followed by one spare octet as depicted in figure 5.3-1. The spare bits shall be set to zero by the sender and ignored by the receiver. For the Version Not Supported Indication message header, the Sequence Number may be set to any number and shall be ignored by the receiver.




Figure 5.3-1: The format of Echo and Version Not Supported Indication messages Header

5.4 EPC specific GTP-C header

Apart from the Echo Request, Echo Response and Version Not Supported Indication messages, the GTP-C message header shall contain the TEID and Sequence Number fields followed by one spare octet. A typical GTP-C header is depicted in figure 5.4-1. The spare bits shall be set to zero by the sender and ignored by the receiver.

				Bi	ts			
Octets	8	7	6	5	4	3	2	1
1		Version		Р	T=1	MP	Spare	Spare
2				Messag	је Туре			
3					gth (1 st			
4			Messa	age Len	gth (2 nd	Octet)		
5		Tu	nnel En	dpoint le	dentifier	(1 st Oc	tet)	
6		Tunnel Endpoint Identifier (2 nd Octet)						
7		Tunnel Endpoint Identifier (3 rd Octet)						
8		Tunnel Endpoint Identifier (4 th Octet)						
9			Seque	nce Nur	nber (1 ^s	Octet)		
10			Sequer	nce Num	nber (2 nd	^d Octet)		
11			Sequer	nce Nun	nber (3 ^{rc}	Octet)		
12	Ν	/lessage	e Priorit	у		Sp	are	

Figure 5.4-1: The format of EPC specific GTPv2 Control Plane message Header

5.5 Usage of the GTPv2-C Header

5.5.1 General

The format of the GTPv2-C header is specified in subclause 5.1 "General format". The usage of the GTP-C header across e.g. S101/S121 (3GPP TS 29.276 [14]) and Sv (3GPP TS 29.280 [15]) interfaces are defined in their respective specifications.

The usage of the GTPv2-C header for EPC specific interfaces shall be as defined below.

The first octet of the header shall be used is the following way:

- Bits 8 to 6, which represent the GTP-C version, shall be set to decimal 2 ("010").
- Bit 5 represents a "P" flag. If the "P" flag is set to "0", no piggybacked message shall be present. If the "P" flag is set to "1", then another GTPv2-C message with its own header and body shall be present at the end of the current message.

When present, a piggybacked message shall have its "P" flag set to "0" in its own header. If a Create Session Response message (as part of EUTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN (see sub-clauses 8.6 and 16.11 of 3GPP TS 23.402 [45]) or UE-requested PDN connectivity procedure) has the "P" flag set to "1", then a single Create Bearer Request message shall be present as the piggybacked message. As a response to the Create Bearer Request message, if the Create Bearer Response has the "P" flag set to "1", then a single Modify Bearer Request (as part of EUTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN (see sub-clauses 8.6 and 16.11 of 3GPP TS 23.402 [45]) or UE-requested PDN connectivity procedure) shall be present as the piggybacked message. A Create Bearer Response with "P" flag set to "1" shall not be sent unless a Create Session Response and Create Bearer Response messages, all the EPC specific messages shall have the "P" flag set to "0".

- Bit 4 represents a "T" flag, which indicates if TEID field is present in the GTP-C header or not. If the "T" flag is set to 0, then the TEID field shall not be present in the GTP-C header. If the "T" flag is set to 1, then the TEID field shall immediately follow the Length field, in octets 5 to 8. Apart from the Echo Request, Echo Response and Version Not Supported Indication messages, in all EPC specific messages the value of the "T" flag shall be set to "1".
- Bit 3 represents a "MP" flag. If the "MP" flag is set to "1", then bits 8 to 5 of octet 12 shall indicate the message priority.
- Bit 2 is a spare bit. The sending entity shall set it to "0" and the receiving entity shall ignore it.
- Bit 1 is a spare bit. The sending entity shall set it to "0" and the receiving entity shall ignore it.

The usage of the fields in octets 2 - n of the header shall be as specified below.

- Octet 2 represents the Message type field, which shall be set to the unique value for each type of control plane message. Message type values are specified in Table 6.1-1 "Message types for GTPv2".
- Octets 3 to 4 represent the Message Length field. This field shall indicate the length of the message in octets excluding the mandatory part of the GTP-C header (the first 4 octets). The TEID (if present) and the Sequence Number shall be included in the length count. The format of the Length field of information elements is specified in subclause 8.2 "Information Element Format".
- A piggybacked initial message and the preceding triggered response message present in the common IP/UDP packet shall have their own length and sequence number in their respective GTP-C headers. The overall length of the IP/UDP packet shall indicate the total length of the two GTP-C messages.
- For EPC specific interfaces, T=1, and therefore octets 5 to 8 represent the Tunnel Endpoint Identifier (TEID) field. This field shall unambiguously identify a tunnel endpoint in the receiving GTP-C entity. The Tunnel Endpoint Identifier is set by the sending entity in the GTP header of all control plane messages to the TEID value provided by the corresponding receiving entity (see subclause 4.1). If a peer's TEID is not available the TEID field shall be present in a GTPv2-C header, but its value shall be set to "0", as specified in subclause 5.5.2 "Conditions for sending TEID=0 in GTPv2-C header".
- NOTE: The TEID in the GTP header of a Triggered (or Triggered Reply) message is set to the TEID value provided by the corresponding receiving entity regardless of whether the source IP address of the Initial (or Triggered) message and the IP Destination Address provided by the receiving entity for subsequent control plane Initial messages (see subclause 4.2.2.1) are the same or not.
- Octets 9 to 11 represent GTP Sequence Number field.
- Bits 8 to 5 of octet 12 shall indicate the relative priority of the GTP-C message, if the "MP" flag is set to 1 in Octet 1. It shall be encoded as the binary value of the Message Priority and it may take any value between 0 and 15, where 0 corresponds to the highest priority and 15 the lowest priority.

If the "MP" flag is set to "0" in Octet 1, bits 8 to 5 of octet 12 shall be set to "0" by the sending entity and ignored by the receiving entity.

- Bits 4 to 1 of octet 12 are spare bits. The sending entity shall set them to "0" and the receiving entity shall ignore them.

5.5.2 Conditions for sending TEID=0 in GTPv2-C header

If a peer's TEID is not available, the TEID field still shall be present in the header and its value shall be set to "0" in the following messages:

- Create Session Request message on S2a/S2b/S5/S8
- Create Session Request message on S4/S11, if for a given UE, the SGSN/MME has not yet obtained the Control TEID of the SGW.
- Create Indirect Data Forwarding Tunnel Request message on S4/S11, if the SGW selected by the MME/S4-SGSN for indirect data forwarding is different from the SGW used as anchor.
- Identification Request/Response messages.
- Forward Relocation Request message: over S10, S16 interfaces, over S3 interface during I-RAT handover when ISR is not active.
- Forward Relocation Request message over S3 interface during I-RAT handover between ISR associated nodes, when ISR is active for the UE, and if the node decides to allocate new S3 TEID-C.
- Context Request message.
- Relocation Cancel Request message except for the case where the old SGSN/MME has already been assigned the Tunnel Endpoint Identifier Control Plane of the new SGSN/MME.
- Relocation Cancel Response message if the new SGSN/MME does not have the Tunnel Endpoint Identifier Control Plane of the old SGSN/MME.

- Delete PDN Connection Set Request/Response messages.
- Configuration Transfer Tunnel message.
- RAN Information Relay message.
- If a node receives a message and the TEID-C in the GTPv2 header of the received message is not known, it shall respond with "Context not found" Cause in the corresponding response message to the sender, the TEID used in the GTPv2-C header in the response message shall be then set to zero.
- If a node receives a request message containing protocol error, e.g. Mandatory IE missing, which requires the receiver to reject the message as specified in clause 7.7, it shall reject the request message. For the response message, the node should look up the remote peer's TEID and accordingly set the GTPv2-C header TEID and the message cause code. As an implementation option, the node may not look up the remote peer's TEID and set the GTPv2-C header TEID to zero in the response message. However in this case, the cause code shall not be set to "Context not found".
- MBMS Session Start Request message.
- PGW Restart Notification / PGW Restart Notification Acknowledge messages.
- Downlink Data Notification message sent on S11/S4 as part of the Network Triggered Service Restoration procedure (see 3GPP TS 23.007 [17]), and corresponding Downlink Data Notification Acknowledge and Downlink Data Notification Failure Indication if the SGW did not include the Sender F-TEID for Control Plane IE in the Downlink Data Notification message.
- Stop Paging Indication message is sent to the the restarted CN node (or another node in the same pool) as part of the Network Triggered Service Restoration procedure with ISR (see 3GPP TS 23.007 [17]).
- Suspend Notification and Suspend Acknowledge messages: over S16 interface; over S3 interface when ISR is not active.
- PGW Downlink Triggering Notification message on S5 and S11/S4, PGW Downlink Triggering Acknowledge message on S11/S4, and PGW Downlink Triggering Acknowledge message on S5 if the PGW did not include the Sender F-TEID for Control Plane IE in the PGW Downlink Triggering Notification message.
- UE Registration Query Request and UE Registration Query Response messages over S3 interface.
- NOTE: Legacy implementation conforming to earlier versions of this specification can send the Change Notification Request/Response messages on the TEID zero in spite of the peer's node TEID being available.

5.6 Format of the GTPv2-C Message

The GTP-C header may be followed by subsequent information elements dependent on the type of control plane message.




Figure 5.6-1: GTP-C Header followed by subsequent Information Elements

6 GTP-C Message Types and Message Formats

6.0 General

A GTP-C message is sent across a GTP control plane tunnel. In a message, the GTP-C header is followed by zero or more information elements. The GTP-C messages are used for the control plane path management, for the control plane tunnel management and for mobility management.

A T-PDU is an original packet, for example an IP datagram, from an UE, or from a network node in an external packet data network.

6.1 Message Format and Type values

6.1.0 Message Type

GTP defines a set of messages between two associated EPC network elements. The messages to be used shall be as defined in Table 6.1-1.

Table 6.1-1: Message types for GTPv2

Message Type value (Decimal)	Message	Reference	Initial	Triggered
0	Reserved			
1	Echo Request		Х	
2	Echo Response			Х
3	Version Not Supported Indication			Х
4 to 16	Reserved for S101 interface	TS 29.276 [14]		
17 to 24	Reserved for S121 interface	TS 29.276 [14]		
25 to 31	Reserved for Sv interface	TS 29.280 [15]		
	SGSN/MME/ TWAN/ePDG to PGW (S4/S11, S5/S8, S2a, S2b)			
32	Create Session Request		Х	
33	Create Session Response			Х
36	Delete Session Request		Х	
37	Delete Session Response			Х
	SGSN/MME/ePDG to PGW (S4/S11, S5/S8, S2b)			
34	Modify Bearer Request		Х	
35	Modify Bearer Response			Х
	MME to PGW (S11, S5/S8)			
40	Remote UE Report Notification		Х	
41	Remote UE Report Acknowledge			Х
· ·	SGSN/MME to PGW (S4/S11, S5/S8)			
38	Change Notification Request		Х	
39	Change Notification Response			Х
42 to 63	For future use			
164	Resume Notification		Х	
165	Resume Acknowledge		~	Х
100	Messages without explicit response			Λ
64	Modify Bearer Command (MME/SGSN/ TWAN/ePDG to PGW – S11/S4, S5/S8, S2a,		Х	
65	S2b) Modify Bearer Failure Indication (PGW to MME/SGSN/ TWAN/ePDG – S5/S8, S11/S4, S2a,			Х
66	S2b) Delete Bearer Command		X	
67	(MME/SGSN to PGW – S11/S4, S5/S8) Delete Bearer Failure Indication			Х
68	(PGW to MME/SGSN – S5/S8, S11/S4)) Bearer Resource Command (MME/SGSN/TWAN/ePDG to PGW – S11/S4, S5/S8, S2a, S2b)		Х	
69	Bearer Resource Failure Indication (PGW to MME/SGSN/TWAN/ePDG – S5/S8, S11/S4, S2a, S2b)			Х
70	Downlink Data Notification Failure Indication (SGSN/MME to SGW – S4/S11)		Х	
71	Trace Session Activation (MME/SGSN/ TWAN/ePDG to PGW – S11/S4, S5/S8, S2a, S2b)		X	
72	Trace Session Deactivation (MME/SGSN/ TWAN/ePDG to PGW – S11/S4, S5/S8, S2a, S2b)		Х	
73	Stop Paging Indication (SGW to MME/SGSN – S11/S4)		Х	
74 to 94	For future use PGW to SGSN/MME/ TWAN/ePDG (S5/S8, S4/S11, S2a,			
	S2b)			
95	Create Bearer Request		Х	Х
96	Create Bearer Response			Х
97	Update Bearer Request		Х	Х
98	Update Bearer Response			Х
99	Delete Bearer Request		Х	Х
100	Delete Bearer Response PGW to MME, MME to PGW, SGW to PGW, SGW to MME, PGW to TWAN/ePDG, TWAN/ePDG to PGW (S5/S8, S11, S2a, S2b)			X

Message Type value (Decimal)	Message	Reference	Initial	Triggered
101	Delete PDN Connection Set Request		Х	
102	Delete PDN Connection Set Response			Х
	PGW to SGSN/MME(S5, S4/S11)			
103	PGW Downlink Triggering Notification		Х	
104	PGW Downlink Triggering Acknowledge			Х
105 to 127	For future use			
	MME to MME, SGSN to MME, MME to SGSN, SGSN to SGSN (S3/S10/S16)			
128	Identification Request		Х	
129	Identification Response			Х
130	Context Request		Х	
131	Context Response			<u>X</u>
132	Context Acknowledge		V	Х
133	Forward Relocation Request		Х	X
134	Forward Relocation Response		V	Х
135	Forward Relocation Complete Notification		Х	X
136	Forward Relocation Complete Acknowledge		V	Х
137	Forward Access Context Notification		Х	V
138	Forward Access Context Acknowledge			Х
139 140	Relocation Cancel Request		X	X
140	Relocation Cancel Response		v	X
141 142 to 148	Configuration Transfer Tunnel For future use		Х	
142 10 148	RAN Information Relay		X	
152	SGSN to MME, MME to SGSN (S3)		^	
140			X	
149 150	Detach Notification Detach Acknowledge		^	Х
150	CS Paging Indication		X	Λ
153	Alert MME Notification		X	
154	Alert MME Acknowledge		^	Х
155	UE Activity Notification		Х	Λ
156	UE Activity Acknowledge		~	Х
157	ISR Status Indication		Х	Λ
158	UE Registration Query Request		X	
159	UE Registration Query Response		~	Х
	SGSN/MME to SGW, SGSN to MME (S4/S11/S3) SGSN to SGSN (S16), SGW to PGW (S5/S8)			
162	Suspend Notification		X	
163	Suspend Acknowledge		~	Х
100	SGSN/MME to SGW (S4/S11)			Λ
160	Create Forwarding Tunnel Request		Х	
161	Create Forwarding Tunnel Response			Х
166	Create Indirect Data Forwarding Tunnel Request		Х	
167	Create Indirect Data Forwarding Tunnel Response			Х
168	Delete Indirect Data Forwarding Tunnel Request		Х	
169	Delete Indirect Data Forwarding Tunnel Response			Х
170	Release Access Bearers Request		Х	
171	Release Access Bearers Response			Х
172 to 175	For future use			
	SGW to SGSN/MME (S4/S11)			
176	Downlink Data Notification		Х	
177	Downlink Data Notification Acknowledge			Х
179	PGW Restart Notification		Х	
180	PGW Restart Notification Acknowledge			Х
	SGW to SGSN (S4)			
178	Reserved. Allocated in earlier version of the specification.			
181 to 199	For future use			
	SGW to PGW, PGW to SGW (S5/S8)			
200	Update PDN Connection Set Request		Х	
201	Update PDN Connection Set Response			Х
202 to 210	For future use			
	MME to SGW (S11)			
211	Modify Access Bearers Request		Х	

Message Type value (Decimal)	Message	Reference	Initial	Triggered
212	Modify Access Bearers Response			Х
213 to 230	For future use			
	MBMS GW to MME/SGSN (Sm/Sn)			
231	MBMS Session Start Request		Х	
232	MBMS Session Start Response			Х
233	MBMS Session Update Request		Х	
234	MBMS Session Update Response			Х
235	MBMS Session Stop Request		Х	
236	MBMS Session Stop Response			Х
237 to 239	For future use			
	Other			
240 to 247	Reserved for Sv interface (see also types 25 to 31)	TS 29.280 [15]		
248 to 255	For future use			

6.1.1 Presence requirements of Information Elements

There are four different presence requirements (Mandatory, Conditional, Optional, or Conditional-Optional) for an IE within a given GTP-PDU:

- Mandatory means that the IE shall be included by the sending side, and that the receiver diagnoses a "Mandatory IE missing" error, when detecting that the IE is not present. A response including a "Mandatory IE missing" cause, shall include the type of the missing IE.
- Conditional means:
 - that the IE shall be included by sending entity if the conditions specified in the relevant protocol specification are met;
 - the receiver shall check the conditions as specified in the corresponding message type description, based on the parameter combination in the message and/or on the state of the receiving node, to infer if a conditional IE shall be expected. Only if a receiver has sufficient information the following applies. A conditional IE, which is absolutely necessary for the receiving entity to complete the procedure, is missing, then the receiver shall abort the procedure.
- Conditional-Optional means:
 - that the IE shall be included by the up-to-date sending entity, if the conditions specified in the relevant protocol specification are met. An entity, which is at an earlier version of the protocol and therefore is not up-to-date, obviously cannot send such new IE.
 - the receiver need not check the presence of the IE in the message. If the receiver checks the presence of the Conditional-Optional IE, then the IE's absence shall not trigger any of the error handling procedures. The handling of an absence or erroneous such IEs shall be treated as Optional IEs as specified in subclause 7.7 "Error Handling".
- Optional means:
 - that the IE shall be included as a service option. Therefore, the IE may be included or not in a message. The handling of an absent optional IE, or an erroneous optional IE is specified in subclause 7.7 "Error Handling".

For conditional IEs, the clause describing the GTP-PDU explicitly defines the conditions under which the inclusion of each IE becomes mandatory or optional for that particular GTP-PDU. These conditions shall be defined so that the presence of a conditional IE only becomes mandatory if it is critical for the receiving entity. The definition might reference other protocol specifications for final terms used as part of the condition.

For grouped IEs, the presence requirement of the embedded IE shall follow the rules:

- The grouped IE is Mandatory within a given message: the presence requirements of individual embedded IEs are as stated within the Mandatory grouped IE for the given message.
- The grouped IE is Conditional within a given message: if the embedded IE in the grouped IE is Mandatory or Conditional, this embedded IE is viewed as Conditional IE by the receiver. If the embedded IE in the grouped IE

is Conditional-Optional, this embedded IE is viewed as Optional IE by the receiver. If the embedded IE in the grouped IE is Optional, this embedded IE is viewed as Optional IE by the receiver.

- The grouped IE is Conditional-Optional within a given message: if the embedded IE in the grouped IE is Mandatory or Conditional, this embedded IE is viewed as Conditional-Optional IE by the receiver. If the embedded IE in the grouped IE is Conditional-Optional, this embedded IE is viewed as Optional IE by the receiver. If the embedded IE in the grouped IE is Optional, this embedded IE is viewed as Optional IE by the receiver. If the embedded IE in the grouped IE is Optional, this embedded IE is viewed as Optional IE by the receiver.
- The grouped IE is Optional within a given message: all embedded IEs in the grouped IE are viewed as Optional IEs by the receiver.

In all of the above cases, appropriate error handling as described in subclause 7.7 shall be applied for protocol errors of the embedded IEs.

Only the Cause information element at message level shall be included in the response if the Cause contains a value that indicates that the request is not accepted regardless of whether there are other mandatory or conditional information elements defined for a given response message.

The following are exceptions:

- Optionally, the Protocol Configuration Options, Recovery, User Location Information (ULI), Load Control Information, Overload Control Information, Bearer Context and Local Distinguished Name (LDN) information elements may be included.
- For the rejection response of a Forward Relocation Request, the Forward Relocation Response message may also include an F-Cause IE as specified in clause 7.3.2.
- For the rejection response of a SRVCC PS to CS Request, the SRVCC PS to CS Response message may also include an SRVCC Cause IE as specified in clause 5.2.3 in 3GPP TS 29.280 [15].
- A Downlink Data Notification Acknowledge (with or) without an indication of success may also include a DL low priority traffic Throttling IE and the IMSI IE.
- The PGW Back-Off Time IE may also be returned when rejecting a Create Session Request with the cause "APN Congestion".
- Change Notification Response message may also include the IMSI and MEI information elements.
- Failure Indication type messages do not have "Accept" types of Cause values, i.e. all used values indicate the rejection, therefore for Failure Indication type of triggered messages, other information elements, other than the Cause IE, shall also be included according to the conditions of presence specified in the respective message, if they are available.
- The Context Response message (sent by an SGSN or MME) should also include the IMSI IE if the Cause IE contains the value "P-TMSI Signature mismatch", except if the UE is emergency attached and the UE is UICCless.
- The Create Bearer Response message, the Update Bearer Response message and the Delete Bearer Response message shall include the RAN/NAS Cause IE according to the conditions specified in subclauses 7.2.4, 7.2.16 and 7.2.10.2.
- The UE Registration Query Response message shall include IMSI to allow the SGSN to correlate the response message with the corresponding request.

If the Cause information element at Grouped IE level contains a value that indicates that the Grouped IE is not handled correctly, e.g. "Context Not Found" at Bearer Context IE level, the other information elements in this Grouped IE, other than the Cause IE, may not be included.

6.1.2 Grouped Information Elements

Information elements can contain other IEs. This type of IE is called "Grouped IEs".

Grouped IEs have a length value in the TLIV encoding, which includes the added length of all the embedded IEs. Overall coding of a grouped information element with 4 octets long IE header is defined in subclause 8.2 "Information Element Format". Each information element within a grouped IE also shall also contain 4 octets long IE header.

Grouped IEs are not marked by any flag or limited to a specific range of IE type values. The clause describing an IE in this specification shall explicitly state if it is grouped.

NOTE 1: Each entry into each Grouped IE creates a new scope level. Exit from the grouped IE closes the scope level. The GTPv2 message level is the top most scope. This is analogous to the local scope of a subroutine/function.

If more than one grouped information elements of the same type, but for a different purpose are sent with a message, these IEs shall have different Instance values.

If more than one grouped information elements of the same type and for the same purpose are sent with a message, these IEs shall have exactly the same Instance value to represent a list.

NOTE 2: For instance, all "Bearer Contexts Modified" IEs of the type "Bearer Context" in a "Modify Bearer Response" message shall have the Instance value of 0, while all "Bearer Contexts Marked for Removal" IEs of the type "Bearer Context" in the same message shall have the Instance value of 1.

6.1.3 Information Element instance

Every GTPv2 message and grouped IE within a message in this specification has a column documenting the instance value of each IE.

When a GTPv2 message is encoded for use the instance value of each included IE is encoded in the Instance field of the IE for the message scope. See clause 7 and subclause 8.2 for details of that encoding.

An Information Element in an encoded GTPv2 message or encoded grouped IE is identified by the pair of IE Type and Instance values and described by a specific row in the corresponding tables in subclauses of 7 in the present document.

If several Information Elements with the same Type and Instance values are included in an encoded GTPv2 message, they represent a list for the corresponding IE name and row identified in the message grammar in subclauses of clause 7.

If several Information Elements with the same Type and Instance values are included in an encoded grouped IE, they represent a list for the corresponding IE name and row identified in the grouped IE grammar in subclauses of clause 7.

In tables in this document the instance value for "Private Extension" is marked as VS (Vendor Specific). While an instance value must be encoded by the sender the value can be Vendor and even Private Extension specific.

The same IE name might be used in different messages (on the top level or within grouped IEs) in this specification. The instance value and name of an IE is only meaningful within the scope of the message definition. The combination of Type value and Instance value uniquely identifies a specific row in a message description table.

6.2 Message Granularity

The GTPv2-C messages shall be sent per UE on the S3, S10 and S16 interfaces.

The GTPv2-C messages shall be sent per PDN-Connection on the S2a, S2b, S4, S11, S5 and S8 interfaces apart from the following exclusion.

The following GTPv2-C messages are sent per UE on the S4 and S11 interfaces:

- Downlink Data Notification / Acknowledge / Failure Indication;
- Stop Paging Indication;
- Delete Indirect Data Forwarding Tunnel Request/Response;
- Delete Session Request/Response with Scope Indication set to 1 during following procedures with SGW change:
 - Tracking Area Update procedure;

- Routing Area Update procedure;
- Handover procedure;
- SRNS Relocation Cancel Using S4;
- Inter RAT handover Cancel procedure;
- S1 based handover cancel procedure;
- Delete Bearer Request/Response during a TAU/RAU/Handover procedure if the Cause value "ISR deactivation" is included in the Delete Session Request message, or when it is sent to delete the bearer resources on the other ISR associated CN node if the ISRAI flag is not set in the Modify Bearer Request/Modify Access Bearers Request message.
- Release Access Bearers Request/Response;
- Create Indirect Data Forwarding Tunnel Request/Response;
- Trace Session Activation;
- Trace Session Deactivation;
- Create Forwarding Tunnel Request/Response.

The following GTPv2-C messages are sent per UE on the S11 interface:

- Modify Access Bearers Request/Response.

The following GTPv2-C messages are sent per GTP-C entity on the S2a, S2b, S5, S8, and S11 interfaces:

- Delete PDN Connection Set Request/Response.

The following GTPv2-C messages are sent per GTP-C entity on the S5 and S8 interfaces:

- Update PDN Connection Set Request/Response.

The following GTPv2-C messages are sent per GTP-C entity on the S4 and S11 interfaces:

- PGW Restart Notification/Acknowledge.

The following GTPv2-C path management messages are sent per GTP-C entity on all GTPv2-C interfaces:

- Echo Request/Response;
- Version Not Supported Indication.

7 GTP-C messages

7.1 Path Management Messages

7.1.0 General

Three path management messages are specified for GTP-C: Echo Request, Echo Response and Version Not Supported Indication.

The usage of Echo Request / Response procedure is specified in 3GPP TS 23.007 [17].

7.1.1 Echo Request

Table 7.1.1-1 specifies the information elements included in the Echo Request message.

The Recovery information element contains the local Restart Counter, which is specified in 3GPP TS 23.007 [17])

The optional Private Extension contains vendor or operator specific information.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Recovery	Μ		Recovery	0
Sending Node Features		This IE shall be sent towards a peer node on any GTPv2 interface if the sending node supports at least one feature on this interface or if the sending node supports at least one feature and does not know the interface type towards the peer node. This IE may be present otherwise.	Node Features	0
Private Extension	0		Private Extension	VS

Table 7.1.1-1: Information Elements in Echo Request

7.1.2 Echo Response

Table 7.1.2-1 specifies the information elements included in the Echo Response message.

The Recovery information element contains the local Restart Counter, which is specified in 3GPP TS 23.007 [17])

The optional Private Extension contains vendor or operator specific information.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Recovery	Μ		Recovery	0
Sending Node Features		This IE shall be sent towards a peer node on any GTPv2 interface if the sending node supports at least one feature on this interface or if the sending node supports at least one feature and does not know the interface type towards the peer node. This IE may be present otherwise.	Node Features	0
Private Extension	0		Private Extension	VS

 Table 7.1.2-1: Information Elements in Echo Response

NOTE: Having no Cause IE in the Echo Response message is an exceptional case for a triggered message. Hence, a GTP entity that detects a GTP protocol error, e.g Mandatory IE missing, in the Echo Request message, ignores the IE(s) that are in error and sends Echo Response. In addition it can log the error.

7.1.3 Version Not Supported Indication

This message contains only the GTPv2 header and indicates the latest GTP version that the sending entity supports.

7.2 Tunnel Management Messages

7.2.0 General

A node shall include the Recovery information element if it is in contact with the node's peer for the first time, or if the node or the node's peer has restarted recently and the new Restart Counter value has not yet been indicated to the peer. The peer receiving the Recovery information element shall handle it as when an Echo Response message is received but shall consider the rest of the message in accordance with the message semantics and parameters.

7.2.1 Create Session Request

The direction of this message shall be from MME/S4-SGSN to SGW and from SGW to PGW, and from ePDG/TWAN to the PGW (see Table 6.1-1).

The Create Session Request message shall be sent on the S11 interface by the MME to the SGW, and on the S5/S8 interface by the SGW to the PGW as part of the procedures:

- E-UTRAN Initial Attach when a PDN connection needs to be established through the SGW and PGW
- Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN with GTP on S5/S8 interface (see subclauses 8.2, 8.6 and 16.11 of 3GPP TS 23.402 [45])
- UE requested PDN connectivity when a PDN connection needs to be established through the SGW and PGW
- Addition of a 3GPP access of NBIFOM procedure as specified by 3GPP TS 23.161 [71]

The message shall also be sent on S4 interface by the SGSN to the SGW, and on the S5/S8 interface by the SGW to the PGW as part of the procedures:

- PDP Context Activation
- Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN with GTP on S5/S8 interface (see sub-clauses 8.2, 8.6 and 16.11 of 3GPP TS 23.402 [45])
- Addition of a 3GPP access of the NBIFOM procedure as specified by 3GPP TS 23.161 [71]

The message shall also be sent on the S11 interface by the MME to the SGW as part of the procedures:

- Tracking Area Update procedure with Serving GW change
- S1/X2-based handover with SGW change
- UTRAN Iu mode to E-UTRAN Inter RAT handover with SGW change
- GERAN A/Gb mode to E-UTRAN Inter RAT handover with SGW change
- 3G Gn/Gp SGSN to MME combined hard handover and SRNS relocation procedure
- Gn/Gp SGSN to MME Tracking Area Update procedure
- Restoration of PDN connections after an SGW failure if the MME and PGW support these procedures as specified in 3GPP TS 23.007 [17]
- MME triggered Serving GW relocation
- Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN with PMIP on S5/S8 interface (see subclauses 8.2 and 16.11 of 3GPP TS 23.402 [45])

and on the S4 interface by the SGSN to the SGW as part of the procedures:

- Routing Area Update with MME interaction and with SGW change
- Gn/Gp SGSN to S4 SGSN Routing Area Update
- Inter SGSN Routeing Area Update Procedure and Combined Inter SGSN RA / LA Update using S4 with SGW change
- Iu mode RA Update Procedure using S4 with SGW change
- E-UTRAN to UTRAN Iu mode Inter RAT handover with SGW change
- E-UTRAN to GERAN A/Gb mode Inter RAT handover with SGW change
- Serving RNS relocation using S4 with SGW change
- Combined hard handover and SRNS relocation using S4 with SGW change
- Combined Cell / URA update and SRNS relocation using S4 with SGW change
- Enhanced serving RNS relocation with SGW relocation

- Restoration of PDN connections after an SGW failure if the SGSN and PGW support these procedures as specified in 3GPP TS 23.007 [17]
- S4-SGSN triggered Serving GW relocation
- Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN with PMIP on S5/S8 interface (see sub-clauses 8.2 and 16.11 of 3GPP TS 23.402 [45])

and on the S2b interface by the ePDG to the PGW as part of the procedures:

- Initial Attach with GTP on S2b
- UE initiated Connectivity to Additional PDN with GTP on S2b
- Handover to Untrusted Non-3GPP IP Access with GTP on S2b (See sub-clause 8.6 of 3GPP TS 23.402 [45])
- Initial Attach for emergency session (GTP on S2b)
- Addition of an access using S2b of NBIFOM procedure as specified by 3GPP TS 23.161 [71]

and on the S2a interface by the TWAN to the PGW as part of the procedure:

- Initial Attach in WLAN on GTP S2a
- Initial Attach in WLAN for Emergency Service on GTP S2a
- UE initiated Connectivity to Additional PDN with GTP on S2a
- Handover to TWAN with GTP on S2a (See sub-clause 16.10 of 3GPP TS 23.402 [45])
- Addition of an access using S2a of NBIFOM procedure as specified by 3GPP TS 23.161 [71].

If the new Create Session Request received by the SGW collides with an existing active PDN connection context (the existing PDN connection context is identified with the tuple [IMSI, EPS Bearer ID], where IMSI shall be replaced by TAC and SNR part of ME Identity for emergency attached UE without UICC or authenticated IMSI), this Create Session Request shall be treated as a request for a new session. Before creating the new session, the SGW should delete:

- the existing PDN connection context locally, if the Create Session Request is received with the TEID set to zero in the header, or if it is received with a TEID not set to zero in the header and it collides with the default bearer of an existing PDN connection context;
- the existing dedicated bearer context locally, if the Create Session Request collides with an existing dedicated bearer context and the message is received with a TEID not set to zero in the header.

In the former case, if the PGW S5/S8 IP address for control plane received in the new Create Session Request is different from the PGW S5/S8 IP address for control plane of the existing PDN connection, the SGW should also delete the existing PDN connection in the corresponding PGW by sending a Delete Session Request message.

NOTE 1: The SGW can send the Create Session Request and Delete Session Request over S5/S8 asynchronously, e.g. the SGW can send the Delete Session Request and then the Create Session Request without having to wait for the Delete Session Response. It does not matter if the PGW happens to receive the Delete Session Request after the Create Session Request since the PGW assigns a different S5/S8 F-TEID for control plane to the new PDN connection.

If the new Create Session Request received by the PGW collides with an existing PDN connection context (the existing PDN connection context is identified with the triplet [IMSI, EPS Bearer ID, Interface type], where applicable Interface type here is S2a TWAN GTP-C interface or S2b ePDG GTP-C interface or S5/S8 SGW GTP-C interface, and where IMSI shall be replaced by TAC and SNR part of ME Identity for emergency attached UE without UICC or authenticated IMSI), this Create Session Request shall be treated as a request for a new session. Before creating the new session, the PGW should delete:

- the existing PDN connection context, if the Create Session Request collides with the default bearer of an existing PDN connection context;
- the existing dedicated bearer context, if the Create Session Request collides with a dedicated bearer of an existing PDN connection context.

The PGW shall allocate a new PGW S5/S8 F-TEID for control plane to the new PDN connection, i.e. not the same F-TEID value as the one which was assigned to the existing PDN connection.

- NOTE 2: With GTP based S2a and S2b, the EPS Bearer IDs assigned for specific UE over S2a between the TWAN and PGW and over S2b between an ePDG and PGW are independent of the EPS Bearer IDs assigned for the same UE over S5/S8 and may overlap in value (see 3GPP TS 23.402 [45] subclause 4.6.2).
- NOTE 3: Only the TAC and SNR part of the ME Identity is used to identify an emergency attached UE without UICC or authenticated IMSI.

Table 7.2.1-1: Information Elements in a Create Session Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	C	 The IMSI shall be included in the message on the S4/S11 interface, and on S5/S8 interface if provided by the MME/SGSN, except for the case: If the UE is emergency attached and the UE is UICCless. The IMSI shall be included in the message on the S4/S11 interface, and on S5/S8 interface if provided by the MME/SGSN, but not used as an identifier if UE is emergency attached but IMSI is not authenticated. The IMSI shall be included in the message on the S2a/S2b interface, except for the case: if the UE is emergency attached and the UE is UICCless. 	IMSI	0
MSISDN	C	For an E-UTRAN Initial Attach and a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN the IE shall be included when used on the S11 interface, if provided in the subscription data from the HSS. For a PDP Context Activation procedure and a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN the IE shall be included when used on the S4 interface, if provided in the subscription data from the HSS. The IE shall be included for the case of a UE Requested PDN Connectivity, if the MME has it stored for that UE. It shall be included when used on the S5/S8 interfaces if provided by the MME/SGSN. The ePDG shall include this IE on the S2b interface during an Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b and a Handover to Untrusted Non-3GPP IP Access with GTP on S2b, if provided by the HSS/AAA. The TWAN shall include this IE on the S2a interface during an Initial Attach in WLAN on GTP S2a, Initial Attach in WLAN for Emergency Service on GTP S2a, UE initiated Connectivity to Additional PDN with GTP on S2a and a Handover to TWAN with GTP on S2a, if provided by the HSS/AAA.	MSISDN	0
ME Identity (MEI)	С	 The MME/SGSN shall include the ME Identity (MEI) IE on the S11/S4 interface: If the UE is emergency attached and the UE is UICCless; or If the UE is emergency attached and the IMSI is not authenticated For all other cases the MME/SGSN shall include the ME Identity (MEI) IE on the S11/S4 interface if it is available. If the SGW receives this IE, it shall forward it to the PGW on the S5/S8 interface. 	MEI	0

	CO The TWAN/ePDG shall include the ME Identity (MEI) IE on the S2a/S2b interface: - If the UE is emergency attached and the UE is UICCless; or		
	- If the UE is emergency attached and the IMSI is not authenticated.		
	For all other cases, the TWAN/ePDG shall include the ME Identity (MEI) IE on the S2a/S2b interface, if it is available.		
User Location Information (ULI)	 C This IE shall be included on the S11 interface for E-UTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN and UE-requested PDN Connectivity procedures. It shall include ECGI and TAI. The MME/SGSN shall also include it on the S11/S4 interface for TAU/RAU/X2-Handover/Enhanced SRNS Relocation procedure if the PGW/PCRF has requested location information change reporting and MME/SGSN support location information change reporting. CO This IE shall also be included on the S4 interface for PDP Context Activation procedure. It shall include CGI/SAI, together with RAI. CO This IE shall also be included on the S4/S11 interface for a TAU/RAU procedure if the level of support (User Location Change Reporting and/or CSG Information Change Reporting) changes; or the target MME/S4-SGSN cannot derive the level of support (User Location Change Reporting) for the source Gn/Gp SGSN. See NOTE 9. The MME shall include the ECGI and /or TAI in the ULI, the S4-SGSN shall include on the S4/S11 interface for: a TAU procedure with an S4-SGSN interaction, if the MME supports location information change reporting; a RAU procedure with an MME interaction, if the MME shall include the ECGI and TAI in the ULI, the S4-SGSN supports location information change reporting; a RAU procedure with an MME interaction, if the MME supports location information change reporting. The MME shall include the ECGI and TAI in the ULI, the S4-SGSN supports location information change reporting. The MME shall include the ECGI and TAI in the ULI, the S4-SGSN shall include the ECGI and TAI in the ULI, the S4-SGSN shall include the ECGI and TAI in the ULI, the S4-SGSN shall include the ECGI and TAI in the ULI, the S4-SGSN shall include the ECGI and TAI in the ULI, the S4-SGSN shall inclu	ULI (NOTE 10)	0
Serving Network	C This IE shall be included on the S4/S11, S5/S8 and S2b interfaces for an E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, a PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN, a UE requested PDN connectivity, an Attach with GTP on S2b, a UE initiated Connectivity to Additional PDN with GTP on S2b, a Handover to Untrusted Non-3GPP IP Access with GTP on S2b and an Initial Attach for emergency session (GTP on S2b). See NOTE 10.	Serving Network	0
	CO This IE shall be included on S4/S11 for RAU/TAU/Handover with SGW relocation procedures. See NOTE 10.		

	CO This IE shall be included on the S2a interface for an Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, a UE initiated Connectivity to Additional PDN with GTP on S2a and a Handover to TWAN with GTP on S2a. The TWAN shall set this IE to the PLMN identity of the selected PLMN used for 3GPP-based access authentication. The selected PLMN is the PLMN of the 3GPP AAA Proxy in roaming case and the PLMN of the 3GPP AAA Server in non-roaming case.		
RAT Type	 M This IE shall be set to the 3GPP access type or to the value matching the characteristics of the non-3GPP access the UE is using to attach to the EPS. The ePDG may use the access technology type of the untrusted non-3GPP access network if it is able to acquire it; otherwise it shall indicate Virtual as the RAT Type. The TWAN shall set the RAT Type value to "WLAN" on the S2a interface. See NOTE 3, NOTE 4. 	RAT Type	0

Г <u> </u> т		1	, 1
	C This IE shall be included if any one of the applicable flags is set to 1.		
	 Applicable flags are: S5/S8 Protocol Type: This flag shall be set to 1 on the S11/S4 interfaces if the chosen protocol type for the S5/S8 interface is PMIP. 		
	 Dual Address Bearer Flag: This flag shall be set to 1 on the S2b, S11/S4 and S5/S8 interfaces when the PDN Type, determined based on UE request and subscription record, is set to IPv4v6 and all SGSNs which the UE may be handed over to support dual addressing. This shall be determined based on node pre-configuration by the operator. (see also NOTE 5). The TWAN shall set this flag to 1 on the S2a interface if it supports IPv4 and IPv6 and the PDN Type determined from the UE request if single- connection mode or multi-connection mode is used (see 3GPP TS 23.402 [45]) and the user subscription data is set to IPv4v6. 		
Indication Flags	 Handover Indication: This flag shall be set to 1 on the S11/S4 and S5/S8 interface during a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, or a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN procedures, or an Addition of a 3GPP access of NBIFOM procedure. This flag shall be set to 1 on the S2b interface during a Handover from 3GPP access to Untrusted Non-3GPP IP Access with GTP on S2b and IP address preservation is requested by the UE, or an Addition of an access using S2b of NBIFOM procedure. This flag shall be set to 1 on the S2a interface during a Handover from 3GPP access to TWAN with GTP on S2a and IP address preservation is requested by the UE, or an Addition of an access using S2a of NBIFOM procedure. 		0
	- Operation Indication: This flag shall be set to 1 on the S4/S11 interface for a TAU/RAU procedure with SGW relocation, Enhanced SRNS Relocation with SGW relocation, X2-based handovers with SGW relocation and MME triggered Serving GW relocation.		
	 Direct Tunnel Flag: This flag shall be set to 1 on the S4 interface if Direct Tunnel is used. 		
	 Piggybacking Supported: This flag shall be set to 1 on the S11 interface only if the MME supports the piggybacking feature as described in Annex F of 3GPP TS 23.401 [3]. This flag shall be set to 1 on S5/S8 only if both the MME and the SGW support piggybacking. 		
	- Change Reporting support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interfaces if the SGSN/MME supports location Info Change Reporting and if the SGSN/MME's operator policy permits reporting of location change to the operator of the PGW with which the session is being established. See NOTE2.		
	 CSG Change Reporting Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interfaces if the SGSN/MME supports CSG 		

 Information Change Reporting and if the SGSN/MME's operator policy permits reporting of CSG Information change to the operator of the PGW with which the session is being established. See NOTE 2. Unauthenticated IMSI: This flag shall be set to 1 on the S4/S11, S5/S8 and S2a/S2b interfaces if the IMSI present in the message is not authenticated and is for an emergency attached UE. PDN Pause Support Indication: this flag shall be set to 1 on the S5/S8 interface if the SGW supports the PGW Pause of Charging procedure. NBIFOM Support Indication: This flag shall be set to 1 on S11/S4 if the MME/SGSN supports NBIFOM. This flag shall be set to 1 on S2a/S2b if the TWAN/ePDG supports NBIFOM. WLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S3/S8 interface if the S2a interface if the TWAN supports the VLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S2a interface if the TWAN supports the VLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S2a interface if the S0B supports the VLCP PDN Connection Modification procedure. UE Not Authorised Cause Code Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the S0B supports the S0B support the S0B supports the S0B support S0B supports th	
 on the S4/S11, S5/S8 and S2a/S2b interfaces if the IMSI present in the message is not authenticated and is for an emergency attached UE. PDN Pause Support Indication: this flag shall be set to 1 on the S5/S8 interface if the SGW supports the PGW Pause of Charging procedure. NBIFOM Support Indication: This flag shall be set to 1 on S11/S4 if the MME/SGSN supports NBIFOM. This flag shall be set to 1 on S5/S8 if both the SGW and the MME/SGSN support NBIFOM. This flag shall be set to 1 on S2a/S2b if the TWAN/ePDG supports NBIFOM. WLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S2a interface if the TWAN supports the WLCP PDN Connection Modification procedure. UE Not Authorised Cause Code Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the SGSN/MME supports 	
 set to 1 on the S5/S8 interface if the SGW supports the PGW Pause of Charging procedure. NBIFOM Support Indication: This flag shall be set to 1 on S11/S4 if the MME/SGSN supports NBIFOM. This flag shall be set to 1 on S5/S8 if both the SGW and the MME/SGSN support NBIFOM. This flag shall be set to 1 on S2a/S2b if the TWAN/ePDG supports NBIFOM. WLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S2a interface if the TWAN supports the WLCP PDN Connection Modification procedure. UE Not Authorised Cause Code Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the SGSN/MME supports 	
 to 1 on S11/S4 if the MME/SGSN supports NBIFOM. This flag shall be set to 1 on S5/S8 if both the SGW and the MME/SGSN support NBIFOM. This flag shall be set to 1 on S2a/S2b if the TWAN/ePDG supports NBIFOM. WLCP PDN Connection Modification Support Indication: This flag shall be set to 1 on the S2a interface if the TWAN supports the WLCP PDN Connection Modification procedure. UE Not Authorised Cause Code Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the SGSN/MME supports 	
Indication: This flag shall be set to 1 on the S2a interface if the TWAN supports the WLCP PDN Connection Modification procedure. - UE Not Authorised Cause Code Support Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the SGSN/MME supports	
Indication: This flag shall be set to 1 on S4/S11 and S5/S8 interface if the SGSN/MME supports	
the "UE not authorised by OCS or external AAA Server" Cause Code.	
- UE Available for Signalling Indication: this flag shall be set to 1 on S11/S4 during a TAU/RAU with SGW relocation procedure if there is pending network initiated PDN connection signalling for this PDN connection. The SGW shall include this IE on S5/S8 if it receives the flag from the MME/SGSN.	
- S11-U Tunnel Flag: this flag shall be set to 1 on the S11 interface if user data is transported in NAS signalling.	
- Extended PCO Support Indication: this flag shall be set to 1 on S11 interface by the MME if the UE and the MME support ePCO; and this flag shall be set to 1 on S5/S8 interface by the SGW if the SGW supports ePCO and MME has set the flag to 1.	
- Control Plane Only PDN Connection Indication: this flag shall be set to 1 over S11 and S5/S8 if the PDN Connection is set to Control Plane Only.	
- eNB Change Reporting Support Indication: This flag shall be set to 1 on S11 and S5/S8 interfaces if the MME supports location Info Change Reporting and if the MME's operator policy permits reporting of location change to the operator of the PGW with which the session is being established. See NOTE 19.	

Sender F-TEID for Control Plane	Μ		F-TEID	0
PGW S5/S8 Address for Control Plane or PMIP	С	This IE shall be sent on the S11 / S4 interfaces. The TEID or GRE Key is set to "0" in the E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, the PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN and the UE requested PDN connectivity procedures.	F-TEID	1
Access Point Name (APN)	Μ		APN	0
Selection Mode	С	This IE shall be included on the S4/S11 and S5/S8 interfaces for an E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, a PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN and a UE requested PDN connectivity. This IE shall be included on the S2b interface for an Initial Attach with GTP on S2b, a Handover to Untrusted Non- 3GPP IP Access with GTP on S2b, a UE initiated Connectivity to Additional PDN with GTP on S2b and an Initial Attach for emergency session (GTP on S2b). It shall indicate whether a subscribed APN or a non- subscribed APN chosen by the UE/MME/SGSN/ePDG/TWAN was selected, see NOTE 17. This IE shall be included on the S2a interface for an Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, a Handover to TWAN with GTP on S2a and a UE initiated Connectivity to Additional PDN with GTP on S2a. The value shall be set to "MS or network provided APN, subscription verified". When available, this IE shall be sent by the MME/SGSN on the S11/S4 interface during TAU/RAU/HO with SGW relocation.	Selection Mode	0
PDN Type	C	This IE shall be included on the S4/S11 and S5/S8 interfaces for an E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, a PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN and a UE requested PDN connectivity. This IE shall be set to IPv4, IPv6, IPv4v6 or Non-IP. This is based on the UE request and the subscription record retrieved from the HSS (for MME see 3GPP TS 23.401 [3], clause 5.3.1.1, and for SGSN see 3GPP TS 23.060 [35], clause 9.2.1). See NOTE 1. See NOTE 14.	PDN Type	0

· · · · · · · · · · · · · · · · · · ·			
	 C This IE shall be included the S4/S11, S5/S8 and S2a/S2b interfaces for an E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, a PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN, a UE requested PDN connectivity, an Attach with GTP on S2b, a UE initiated Connectivity to Additional PDN with GTP on S2b, a Handover to Untrusted Non-3GPP IP Access with GTP on S2b, an Initial Attach for emergency session (GTP on S2b, an Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, a UE initiated Connectivity to Additional PDN with GTP on S2a and a Handover to TWAN with GTP on S2a. For PMIP-based S5/S8, this IE shall also be included on the S4/S11 interfaces for TAU/RAU/Handover cases involving SGW relocation. The PDN type field in the PAA shall be set to IPv4, or IPv6 or IPv4v6, or Non-IP by MME/SGSN, based on the UE request and the subscription record retrieved from the HSS (see subclause 8.12 and also NOTE 5). The TWAN shall set the PDN type field in the PAA to IPv4, or IPv6 or IPv4v6 based on the UE request if single-connection mode or multi-connection mode is used (see 3GPP TS 23.402 [45]), the IP versions the TWAN supports 		
PDN Address Allocation (PAA)	and the PDN type received in the user subscription data from the HSS/3GPP AAA Server, or based on the UE request and the TWAN Emergency Configuration Data for an Initial Attach in WLAN for Emergency Service on GTP S2a. The ePDG shall set the PDN type field in the PAA to IPv4, or IPv6 or IPv4v6 based on the UE request and the subscription record retrieved from the HSS/3GPP AAA Server, or based on the UE request and the ePDG Emergency Configuration Data for an Initial Attach for emergency session (GTP on S2b).	ΡΑΑ	0
	For static IP address assignment (for MME see 3GPP TS 23.401 [3], clause 5.3.1.1, for SGSN see 3GPP TS 23.060 [35], clause 9.2.1, for ePDG see 3GPP TS 23.402 [45] subclause 4.7.3, and for TWAN see 3GPP TS 23.402 [45] subclause 16.1.5), the MME/SGSN/ePDG/TWAN shall set the IPv4 address and/or IPv6 prefix length and IPv6 prefix and Interface Identifier based on the subscribed values received from HSS, if available. For PDN Type IPv4v6, either one of the IP versions (i.e. IPv4 address or IPv6 prefix and Interface Identifier) or both the IP versions may be statically provisioned in the HSS. If only one of the IP versions is statically provisioned in the HSS, the MME/SGSN/ePDG/TWAN shall set the other IP version as all zeros. The value of PDN Type IE, if present in this message.		
	For a Handover to Untrusted Non-3GPP IP Access with GTP on S2b, the ePDG shall set the IPv4 address and/or IPv6 prefix length and IPv6 prefix and Interface Identifier based on the IP address(es) received from the UE. For IP PDN connections, if static IP address assignment is not used (e.g. static address is not received from the HSS)		
	not used (e.g. static address is not received from the HSS), and for scenarios other than a Handover to Untrusted Non- 3GPP IP Access with GTP on S2b, the IPv4 address shall be set to 0.0.0.0, and/or the IPv6 Prefix Length and IPv6 prefix and Interface Identifier shall all be set to zero.		

-	1			1
		For Non-IP PDN connections, the PDN Address and Prefix		
	~~	field shall not be present. See NOTE 14.		
	CO	This IE shall be sent by the MME/SGSN on S11/S4		
		interface during TAU/RAU/HO with SGW relocation.		
	С	This IE shall be included on the S4/S11 and S5/S8		
		interfaces in the E-UTRAN initial attach, a Handover from		
		Trusted or Untrusted Non-3GPP IP Access to E-UTRAN,		
		PDP Context Activation, a Handover from Trusted or		
Maximum APN		Untrusted Non-3GPP IP Access to UTRAN/GERAN and		•
Restriction		UE Requested PDN connectivity procedures.	APN Restriction	0
		This IE denotes the most stringent restriction as required		
		by any already active bearer context. If there are no		
		already active bearer contexts, this value is set to the least		
		•		
	0	restrictive type.		
	С	This IE represents the APN-AMBR. It shall be included on		
		the S4/S11, S5/S8 and S2a/S2b interfaces for an E-		
		UTRAN initial attach, a Handover from Trusted or		
		Untrusted Non-3GPP IP Access to E-UTRAN, UE		
		requested PDN connectivity, PDP Context Activation		
		procedure using S4, a Handover from Trusted or Untrusted		
		Non-3GPP IP Access to UTRAN/GERAN,		
Aggregate Maximum Bit Rate (APN-AMBR)		TAU/RAU/Handover from the Gn/Gp SGSN to the S4		~
		SGSN/MME procedures, Attach with GTP on S2b, a	AMBR	0
		Handover to Untrusted Non-3GPP IP Access with GTP on		
		S2b, UE initiated Connectivity to Additional PDN with GTP		
		on S2b, an Initial Attach for emergency session (GTP on		
		S2b), Initial Attach in WLAN on GTP S2a, an Initial Attach		
		in WLAN for Emergency Service on GTP S2a, a Handover		
		to TWAN with GTP on S2a and UE initiated Connectivity to		
	_	Additional PDN with GTP on S2a.		
	С	This IE shall be included on S4/S11 in RAU/TAU/HO		
Linked EPS Bearer ID		except in the Gn/Gp SGSN to MME/S4-SGSN	EBI	0
Linked Er o bearer ib		RAU/TAU/HO procedures with SGW change to identify the	LDI	0
		default bearer of the PDN Connection		
	CO	The TWAN shall include this IE on S2a interface (during		
		initial attach, handover to TWAN with GTP on S2a		
		procedure, UE-initiated additional PDN connectivity		
		procedures), if the single-connection mode or multiple-		
Trusted WLAN Mode		connection mode is used.	тумі	0
Indication		The TWAN shall not include this IE if transparent single-		Ŭ
		connection mode is used. The PGW shall assume that		
		transparent single-connection mode is used if it receives		
	_	this message without this IE from the TWAN.		
	С	If MME/SGSN receives PCO from the UE during the		
		Attach, PDN connectivity or Handover to 3GPP access	1	
		procedures, the MME/SGSN shall forward the PCO IE to	1	
Protocol	L	SGW. The SGW shall also forward it to PGW.		
	CO	If the TWAN receives a PCO from the UE during: an initial	DCO	0
Configuration Options		attach, handover to TWAN or UE-initiated additional PDN	PCO	0
(PCO)		connectivity with GTP on S2a procedures (in multi-		
		connection mode or single connection mode), the TWAN		
		shall forward the PCO IE to the PGW, see 3GPP TS		
	1	23.402 [45].	1	

Bearer Contexts to be created	Μ	Several IEs with the same type and instance value shall be included on the S4/S11 and S5/S8 interfaces as necessary to represent a list of Bearers. One single IE shall be included on the S2a/S2b interface. One bearer shall be included for E-UTRAN Initial Attach, PDP Context Activation, UE requested PDN Connectivity, Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b, Handovers between Untrusted Non-3GPP IP Access with GTP on S2b and 3GPP Access, Initial Attach for emergency session (GTP on S2b), Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, Handovers between TWAN with GTP on S2a and 3GPP Access and UE initiated Connectivity to Additional PDN with GTP on S2a. One or more bearers shall be included for a Handover/TAU/RAU with an SGW change. See NOTE 6 and NOTE 7.	Bearer Context	0
Bearer Contexts to be removed	С	This IE shall be included on the S4/S11 interfaces for the TAU/RAU/Handover cases where any of the bearers existing before the TAU/RAU/Handover procedure will be deactivated as consequence of the TAU/RAU/Handover procedure. For each of those bearers, an IE with the same type and instance value shall be included. See NOTE 6 and NOTE 7.	Bearer Context	1
Trace Information	С	This IE shall be included on the S4/S11 interface if an SGW trace is activated, and/or on the S5/S8 and S2a/2b interfaces if a PGW trace is activated. See 3GPP TS 32.422 [18].	Trace Information	0
Recovery	С	This IE shall be included on the S4/S11, S5/S8 and S S2a/2b interfaces if contacting the peer node for the first time.	Recovery	0
MME-FQ-CSID	С	This IE shall be included by the MME on the S11 interface and shall be forwarded by an SGW on the S5/S8 interfaces according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by the SGW on the S5/S8 interfaces according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
ePDG-FQ-CSID	С	This IE shall be included by the ePDG on the S2b interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	2
TWAN-FQ-CSID	С	This IE shall be included by the TWAN on the S2a interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	3
UE Time Zone		This IE shall be included by the MME over S11 during Initial Attach, a Handover from Trusted or Untrusted Non- 3GPP IP Access to E-UTRAN and UE Requested PDN Connectivity procedure. This IE shall be included by the SGSN over S4 during PDP Context Activation procedure and a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN. This IE shall be included by the MME/SGSN over S11/S4 TAU/RAU/Handover with SGW relocation. If SGW receives this IE, SGW shall forward it to PGW across S5/S8 interface. This IE shall be included by the TWAN on the S2a interface for Initial Attach in WLAN procedure, UE-initiated Connectivity to Additional PDN with GTP on S2a and handover to TWAN with GTP on S2a procedure as specified in 3GPP TS 23.402 [45].	UE Time Zone	0

User CSG Information (UCI)	co	This IE shall be included on the S4/S11 interface for E- UTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, UE- requested PDN Connectivity, PDP Context Activation and a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN using S4 procedures, if the UE is accessed via CSG cell or hybrid cell. The MME/SGSN shall also include it for TAU/RAU/Handover procedures with SGW relocation if the UE is accessed via a CSG cell or hybrid cell or leaves a CSG or hybrid cell and the PGW/PCRF has requested CSG info reporting and MME/SGSN support CSG info reporting. NOTE 11. The SGW shall include this IE on S5/S8 if it receives the User CSG information from MME/SGSN. See NOTE 10.	UCI	0
Charging Characteristics	С	This IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces according to 3GPP TS 32.251 [8]	Charging Characteristics	0
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME to the SGW on the S11 interface and by the S4-SGSN to the SGW on the S4 interface (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	0
SGW LDN	0	This IE is optionally sent by the SGW to the PGW on the S5/S8 interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	1
ePDG LDN	0	This IE is optionally sent by the ePDG to the PGW on the S2b interfaces (see 3GPP TS 32.423 [44]), when contacting the peer node for the first time.	Local Distinguished Name (LDN)	2
TWAN LDN	0	This IE may be sent by the TWAN to the PGW on the S2a interfaces (see 3GPP TS 32.423 [44]), when contacting the peer node for the first time.	Local Distinguished Name (LDN)	3
Signalling Priority Indication	со	The SGSN/MME shall include this IE on the S4/S11 interface if the UE indicates low access priority when requesting to establish the PDN connection. The SGW shall forward this IE in the Create Session Request message on the S5/S8 interfaces if received from the MME/SGSN.	Signalling Priority Indication	0
UE Local IP Address	СО	The ePDG shall include this IE on the S2b interface during an Initial Attach for emergency session (GTP on S2b). Otherwise the ePDG shall include this IE on the S2b interface based on local policy.	IP Address	0
UE UDP Port	со	The ePDG shall include this IE on the S2b interface if NAT is detected, the UDP encapsulation is used and the UE Local IP Address is present.	Port Number	0
Additional Protocol Configuration Options (APCO)	0	If multiple authentications are supported by the ePDG, the ePDG shall include this IE on the S2b interface and perform the corresponding procedures as specified for PAP and CHAP authentication of the UE with external networks in 3GPP TS 33.402 [50]. If the UE requests the DNS IPv4/IPv6 address in the Configuration Payload (CFG_REQ) during the IPsec tunnel establishment procedure (as specified in 3GPP TS 33.402 [50]), and if the ePDG supports the Additional Protocol Configuration Options IE, the ePDG may include this IE over S2b interface and correspondingly set the "DNS Server IPv4/v6 Address Request" parameter as defined in 3GPP TS 24.008 [5]. If the UE includes the P-CSCF_IP6_ADDRESS attribute, or the P-CSCF_IP4_ADDRESS attribute or both in the CFG_REQUEST configuration payload during the IPsec tunnel establishment procedure as specified in 3GPP TS 24.302 [63]), and if the ePDG supports these IKEv2 attributes and the Additional Protocol Configuration Options IE, the ePDG shall include this IE over the S2b interface and correspondingly set the P-CSCF IPv6 Address Request, or P-CSCF IPv4 Address Request, or both parameters as defined in 3GPP TS 24.008 [5].	Additional Protocol Configuration Options (APCO)	0

		1	
	 CO If the UE includes the P- CSCF_RESELECTION_SUPPORT Private Status Type in a Notify payload within the IKE_AUTH request message during the IPsec tunnel establishment procedure asspecified in 3GPP TS 24.302 [63], and if the ePDG supports the P-CSCF restoration extension procedure for the untrusted WLAN access (see 3GPP TS 23.380 [61]), the ePDG shall include this IE over the S2b interface and correspondingly set the P- CSCF_RESELECTION_SUPPORT, as defined in 3GPP TS 24.008 [5]. O The TWAN may include this IE on the S2a interface to retrieve additional IP configuration parameters from the PGW (e.g. DNS server) if the transparent single- 		
	connection mode is used as specified in 3GPP TS 23.402 [45].		
H(e)NB Local IP Address	 CO The MME/SGSN shall include this IE on S11/S4 interface if the MME/SGSN receives this information from H(e)NB in UE associated S1/lu signalling according (see 3GPP TS 23.139 [51]) during: E-UTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, UE-requested PDN Connectivity, PDP Context Activation and a a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN using S4; TAU/RAU/X2-based handover/Enhanced Serving RNS Relocation Procedure with SGW change, if the PGW/PCRF has requested H(e)NB information reporting for the PDN connection. The SGW shall forward this IE on S5/S8 interface if the SGW receives it from the MME/SGSN. 	IP Address	1
H(e)NB UDP Port	 CO The MME/SGSN shall include this IE on S11/S4 interface if the MME/SGSN receives this information from H(e)NB in UE associated S1/Iu signalling according (see 3GPP TS 23.139 [51]) during: E-UTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, UE-requested PDN Connectivity, PDP Context Activation and a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN using S4; TAU/RAU/X2-based handover/Enhanced Serving RNS Relocation Procedure with SGW relocation, if the PGW/PCRF has requested H(e)NB information reporting for the PDN connection. The SGW shall forward this IE on S5/S8 interface if the SGW receives it from the MME/SGSN. 	Port Number	1
MME/S4-SGSN Identifier	 CO If the PGW triggered SGW restoration procedure is supported, the MME/S4-SGSN shall include this IE on S11/S4 interface and the SGW shall forward this IE on S5 interface in the existing signalling as specified in 3GPP TS 23.007 [17]. If the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see subclause 12.3.11), the MME/S4-SGSN shall include this IE on the S11/S4 interface. In that case, the SGW shall forward this IE on the S5/S8 interface. 	IP Address	2
TWAN Identifier	CO This IE shall be included on the S2a interface for Initial Attach in WLAN procedure, UE-initiated Connectivity to Additional PDN with GTP on S2a and handover to TWAN with GTP on S2a procedure as specified in 3GPP TS 23.402 [45].	TWAN Identifier	0

ePDG IP Address	0	This IE may be included on the S2b interface based on local policy for Fixed Broadband access network interworking, see 3GPP TS 23.139 [51]. If present, it shall contain the ePDG IP address which is used as IKEv2 tunnel endpoint with the UE.	IP Address	3
CN Operator Selection Entity		In shared networks, the SGSN shall include this IE on the S4 interface for a PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN and RAU with SGW relocation procedures, if the information is available, to indicate whether the Serving Network has been selected by the UE or by the network. The SGW shall include this IE on S5/S8 if it receives it from the SGSN.	CN Operator Selection Entity	0
Presence Reporting Area Information		 The MME/SGSN shall include this IE in the following procedures, if the PGW/PCRF/OCS requested reporting changes of UE presence in the Presence Reporting Area(s) and the MME/SGSN supports such reporting: TAU/RAU/Handover procedures with SGW relocation and MME/SGSN change. The new MME/SGSN shall then indicate whether the UE is inside or outside the PRA for each of the active Presence Reporting Area(s), or indicate that the Presence Reporting Area(s) is inactive; TAU/RAU/Handover procedures with SGW relocation and without MME/SGSN change, if the UE enters or leaves the Presence Reporting Area(s). In this case, this IE shall only include the active PRA(s) that the UE has newly entered or left. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. See NOTE 20. 	Presence Reporting Area Information	0
MME/S4-SGSN's Overload Control Information	0	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8 interface.	Overload Control Information	0
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	1
TWAN/ePDG's Overload Control Information	0	During an overload condition, the TWAN/ePDG may include this IE over the S2a/S2b interface if the overload control feature is supported by the TWAN/ePDG and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the TWAN/ePDG shall provide only one instance of this IE, representing its overload information.	Overload Control Information	2
Origination Time Stamp	СО	The MME/SGSN and the TWAN/ePDG shall include this IE on the S11/S4 and S2a/S2b interface respectively, in the conditions specified in subclause 13.2. When present, the Origination Time Stamp shall contain the UTC time when the originating entity initiated the request.	Millisecond Time Stamp	0

	со	The SGW shall include this IE on the S5/S8 interface if it receives the Origination Time Stamp from the MME/SGSN and if it supports the procedure specified in subclause		
Maximum Wait Time		 13.2. The MME/SGSN and the TWAN/ePDG shall include this IE on the S11/S4 and S2a/S2b interface respectively, in the conditions specified in subclause 13.3. When present, the Maximum Wait Time shall contain the duration (number of milliseconds since the Origination Time Stamp) during which the originator of the request waits for a response. The SGW shall include this IE on the S5/S8 interface if it receives the Maximum Wait Time from the MME/SGSN and if it supports the procedure specified in subclause 	Integer Number	0
WLAN Location Information	со	13.3. This IE shall be included on the S2b interface if the WLAN Location Information is available.	TWAN Identifier	1
WLAN Location Timestamp	со	This IE shall be included on the S2b interface, if the WLAN Location Timestamp is available.	TWAN Identifier Timestamp	0
NBIFOM Container	со	This IE shall be included on the S11/S4 or S2a/S2b interfaces if the MME/S4-SGSN or the TWAN/ePDG receives an NBIFOM Container from the UE as specified in TS 24.161 73]. The Container Type shall be set to 4. If the SGW receives an NBIFOM Container from the MME/S4-SGSN, the SGW shall forward this IE to the PGW on the S5/S8 interface.	F-Container	0
Remote UE Context Connected	со	The MME shall include this IE on the S11 interface during a SGW relocation procedure if such information is available. Several IEs with the same type and instance value may be included as necessary to represent a list of remote UEs connected.	Remote UE Context	0
3GPP AAA Server Identifier		The ePDG/TWAN may include this IE on the S2a/S2b interface to provide the selected 3GPP AAA server identifier to the PGW. See NOTE 13.	Node Identifier	0
Extended Protocol Configuration Options (ePCO)	CO	If the MME receives ePCO from the UE during the Initial Attach, UE requested PDN Connectivity procedures, the MME shall forward the ePCO IE to the SGW if the MME supports ePCO. The SGW shall also forward it to the PGW if the SGW supports ePCO. See NOTE 15.	ePCO	0
Serving PLMN Rate Control	со	 The MME shall include this IE on the S11 interface if Serving PLMN Rate control is configured by the MME operator and the PDN Connection is set to Control Plane Only: during an Initial Attach, or a UE Requested PDN Connectivity procedure. during an inter MME TAU with SGW relocation procedure See NOTE 18. The SGW shall include this IE on S5/S8 if it receives this IE from MME. 	Serving PLMN Rate Control	0
MO Exception Data Counter	со	The MME shall include the counter if it has received the counter for RRC cause "MO Exception data" in the Context Response message during a TAU with an MME and SGW change.	Counter	0
UE TCP Port	СО	The ePDG shall include this IE on the S2b interface if NAT is detected, the TCP encapsulation is used and the UE Local IP Address is present.	Port Number	2

Mapped UE Usage Type	 CO The MME/SGSN shall include this IE on the S11/S4 interface, if available. When present, this IE shall contain the mapped UE usage type applicable to the PDN connection. See NOTE 21. CO The SGW shall include this IE on S5 if it receives it from the MME/SGSN. 	Mapped UE Usage Type	0
User Location Information for SGW	 CO The MME/SGSN shall include this IE on the S11/S4 interface, based on operator policy for the User Location Information to be sent to the SGW, if the user location information to be passed to the SGW is not already reported in the ULI IE in this message. When present, this IE shall include the ECGI, TAI, eNodel ID, RAI and/or RNC-ID, based on local policy. See NOTE 21. 	ULI	1
SGW-U node name	CO The SGW-C shall include this IE on the S5 interface, if available. See NOTE 21.	FQDN	0
Private Extension	O This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS

NOTE 1:	The conditional PDN Type IE is redundant on the S4/S11 and S5/S8 interfaces (as the PAA IE contains exactly the same field). The receiver may ignore it. This IE is never sent on the S2a/S2b interface.
NOTE 2:	
	Reporting Support Indication (whichever is applicable), even if stage 2 refers to MS Info Change Reporting Support Indication.
NOTE 3:	The methods that the ePDG may use to acquire the RAT type of the untrusted non-3GPP IP access network are not specified in this release.
NOTE 4:	The PDN-GW can be informed about the type of access network used by the UE over several reference points, see 3GPP TS 29.212 [30] for the mapping between the code values for the different access network types.
NOTE 5:	3GPP TS 23.401 [3] (see subclause 5.3.1.1) and 3GPP TS 23.060 [35] (see subclause 9.2.1) specify the handling of the cases when UE has requested IPv4v6 PDN Type, but MME does not set the Dual Address Bearer Flag due to the MME operator using single addressing per bearer to support interworking with nodes of earlier releases.
NOTE 6:	The Bearer Context to be created IE and Bearer Context to be removed IE, together, shall contain all the bearers belonging to the given PDN connection with each bearer appearing in only one of these IEs.
NOTE 7:	During S1 based handover/ Inter RAT handover/TAU/RAU with S4-SGSN/MME and SGW change, and handover/RAU/TAU from Gn/Gp SGSN to S4-SGSN/MME, if the target MME/S4-SGSN cannot accept one or more PDN connection(s) but can accept at least one or more remaining PDN Connection(s) of the UE, the target MME/SGSN shall indicate all the non GBR bearers of the unaccepted PDN Connection in the Bearer Contexts to be created IE. The (target) MME/SGSN shall indicate all the GBR bearers of the unaccepted PDN connection in the Bearer Contexts to be removed IE.
NOTE 8:	The conditions of presence of the IEs in the Create Session Request for the MME and S4-SGSN triggered Serving GW relocation (see subclause 5.10.4 of 3GPP TS 23.401 [3] and subclause 9.2.2.4 of 3GPP TS 23.060 [35]) are identical to those specified respectively for X2 handover with SGW relocation and for Enhanced Serving RNS Relocation with SGW relocation.
NOTE 9:	
NOTE 10:	In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID.
	In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in SAI/CGI to the PGW, for both supporting and non-supporting UEs. The Core Network Operator PLMN ID (selected by the UE for supporting UEs or allocated by the network for non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network. See subclause 4.4 of 3GPP TS 23.251 [55].
	If the UE initiates a TAU or RAU procedure back to the old MME/old S4 SGSN before completing the ongoing TAU or RAU procedure and the UE is not accessed via a CSG cell or hybrid cell, the old MME/old S4-SGSN shall treat this case as the UE leaves a CSG or hybrid cell.
NOTE 12:	
	If supported, the PGW shall contact the 3GPP AAA server (identified by this IE which carries the Origin-Host and Origin-Realm included in the DEA message received by the ePDG/TWAN over SWm or STa interface) for establishing the S6b session.
NOTE 14:	Before contacting an ÉPC entity, e.g. to send a Create Session Request message, the MME/SGSN shall ensure, during the selection procedure, that the receiving entities support Non-IP PDN type, as specified in subclause 5.9 of 3GPP TS 29.303 [32], e.g. using the Notification of Supported features procedure to learn if the candidate SGW supports the CIOT feature. See also the subclause 8.83.
NOTE 15:	An MME, SGW and PGW which supports NB-IoT and/or Non-IP PDN type shall support ePCO. A UE supporting NB-IoT access and/or Non-IP PDN type also support ePCO.
NOTE 16:	All the UE's SGi PDN Connections shall either have the Control Plane Only PDN Connection Indication set or not set.
NOTE 17:	If the APN was authorized based on the wildcard APN, the Selection Mode Value shall be set to indicate that the subscription is not verified, see Annex A of 3GPP TS 23.060 [35].
NOTE 18:	The MME can set the Control Plane Only Indication only during a PDN connection creation procedure, and the Serving PLMN Rate Control is only applicable to the PDN connection with Control Plane Only Indication set.
	During an inter MME with SGW relocation procedure, when the source MME has not set the Control Plane Only Indication, and the target MME supports only the Control Plane CloT Optimizations, then

the target MME shall not include the Serving PLMN Rate Control IE as the PDN connection cannot be changed to Control Plane Only.
 During an inter MME with SGW relocation procedure, when the source MME has set the Control Plane Only Indication and included Serving PLMN rate control IE in the Context Response message, and the target MME supports both the Control Plane CloT Optimisation and the establishment of the User Plane, the target MME cannot stop the Serving PLMN Rate Control, i.e. the PGW will continue to enforce Serving PLMN Rate Control as the Control Plane Only Indication for this PDN connection cannot be changed during this mobility procedure.
 NOTE 19: An MME which supports eNB Change Reporting shall also support Change reporting and therefore shall set both the Change Report Supporting indication and the eNB Changing Reporting Support Indication.

- NOTE 20: Upon inter MME/SGSN mobility, the target MME/SGSN shall report Presence Reporting Area Information for all the active and inactive PRAs requested by the PGW. Upon intra MME/SGSN mobility with SGW relocation, the MME/SGSN shall only report active PRAs whose Presence Reporting Area Information is changed, e.g. from inside to outside, or vice versa.
- NOTE 21: This information is used for the SGW-U or PGW-U selection (see Annex B.2 of 3GPP TS 29.244 [80]).

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Р	Condition / Comment	IE Type	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
TFT	0	This IE may be included on the S4/S11 interfaces.	Bearer TFT	0
S1-U eNodeB F-TEID	С	This IE shall be included on the S11 interface for X2-based handover with SGW relocation.	F-TEID	0
S4-U SGSN F-TEID	С	This IE shall be included on the S4 interface if the S4-U interface is used.	F-TEID	1
S5/S8-U SGW F- TEID	С	This IE shall be included on the S5/S8 interface for an "E- UTRAN Initial Attach", a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, a "PDP Context Activation", a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN or a "UE Requested PDN Connectivity".	F-TEID	2
S5/S8-U PGW F- TEID		This IE shall be included on the S4 and S11 interfaces for the TAU/RAU/Handover cases when the GTP-based S5/S8 is used. For PMIP-based S5/S8, this IE shall be included on the	F-TEID	3
		S11/S4 interface for the TAU/RAU/Handover cases if the PGW provided an alternate address for user plane, i.e. an IP address for user plane which is different from the IP address for control plane. When present, this IE shall contain the alternate IP address for user plane and the uplink GRE key. See NOTE 1.		
S12 RNC F-TEID	со	This IE shall be included on the S4 interface if the S12 interface is used in the Enhanced serving RNS relocation with SGW relocation procedure.	F-TEID	4
S2b-U ePDG F-TEID	С	This IE shall be included on the S2b interface for an Attach with GTP on S2b, a UE initiated Connectivity to Additional PDN with GTP on S2b, a Handover to Untrusted Non- 3GPP IP Access with GTP on S2b and an Initial Attach for emergency session (GTP on S2b).	F-TEID	5
S2a-U TWAN F-TEID	С	This IE shall be included on the S2a interface for an Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, a UE initiated Connectivity to Additional PDN with GTP on S2a and a Handover to TWAN with GTP on S2a.	F-TEID	6
Bearer Level QoS	Μ		Bearer QoS	0
S11-U MME F-TEID	CO	This IE shall be sent on the S11 interface, if S11-U is being used, during the E-UTRAN Initial Attach and UE requested PDN connectivity procedures. This IE may also be sent on the S11 interface, if S11-U is being used, during a Tracking Area Update procedure with Serving GW change, if the MME needs to establish the S11-U tunnel. See NOTE 2.	F-TEID	7
homogeneo NOTE 2: Establishing	usly the	o receive from the LMA an alternate LMA address for user pla across all the SGWs, when supported over PMIP-based S5/ S11-U tunnel at once during the Create Session Request/Re for a subsequent Modify Bearer Request/Response exchange	S8. sponse procedure	е

Table 7.2.1-2: Bearer Context to be created within Create Session Request

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
S4-U SGSN F-TEID	С	This IE shall be sent on the S4 interface if the S4-U	F-TEID	0
		interface is used. See NOTE 1.		
NOTE 1: The condition	onal	S4-U SGSN F-TEID IE is redundant.		

 Table 7.2.1-3: Bearer Context to be removed within Create Session Request

Table 7.2.1-4: Overload Control Information within Create Session Request

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Overload Reduction Metric	М	See clause 12.3.5.1.2.3 for the description and use of this parameter.	Metric	0
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0

Table 7.2.1-5: Remote UE Context Connected within Create Session Request

Octets 1		Remote UE Context IE Type = 191 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
Remote User ID		See subclause 8.123 for the description and use of this parameter	Remote User ID	0
Remote UE IP Information		See subclause 8.124 for the description and use of this parameter	Remote UE IP Information	0

7.2.2 Create Session Response

The Create Session Response message shall be sent on the S11/S4 interfaces by the SGW to the MME/S4-SGSN, on the S5/S8 interfaces by the PGW to the SGW, on the S2b interface by the PGW to the ePDG, and on the S2a interface by the PGW to the TWAN as part of the procedures listed for the Create Session Request (see subclause 7.2.1).

If handling of default bearer fails, then cause at the message level shall be a failure cause.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "New PDN type due to network preference".
- "New PDN type due to single address bearer only".
- "Missing or unknown APN".
- "GRE key not found".

- "Preferred PDN type not supported".
- "All dynamic addresses are occupied".
- "Remote peer not responding".
- "Semantic error in the TFT operation".
- "Syntactic error in the TFT operation".
- "Semantic errors in packet filter(s)".
- "Syntactic errors in packet filter(s)".
- "User authentication failed".
- "APN access denied no subscription".
- "APN Restriction type incompatibility with currently active PDN Connection".
- "Version not supported by next peer".
- "Denied in RAT".
- "Protocol type not supported".
- "APN congestion".
- "Multiple PDN connections for a given APN not allowed".
- "Multiple accesses to a PDN connection not allowed".
- "Context not found".
- "UE not authorised by OCS or external AAA Server".

Table 7.2.2-1: Information Elements in a Create Session Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ	See NOTE 2 and NOTE 4.	Cause	0
Change Reporting	С	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if the location Change Reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	Change Reporting Action	0
SG Information Reporting Action	CO	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if the CSG Info reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	CSG Information Reporting Action	0
I(e)NB Information Reporting	CO	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if H(e)NB information reporting is to be started or stopped (during a TAU/RAU with SGW change if started earlier) for the PDN connection in the SGSN/MME.	H(e)NB Information Reporting	0
Sender F-TEID for Control Plane	С	This IE shall be sent on the S11/S4 interfaces. For the S5/S8/ S2a/S2b interfaces it is not needed because its content would be identical to the IE PGW S5/S8/ S2a/S2b F-TEID for PMIP based interface or for GTP based Control Plane interface.	F-TEID	0
² GW S5/S8/ S2a/S2b ³ -TEID for PMIP vased interface or for 3TP based Control 21ane interface	C	The PGW shall include this IE on the S5/S8 interfaces during the Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, UE requested PDN connectivity, PDP Context Activation and a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN procedures. If the SGW receives this IE it shall forward the IE to MME/S4-SGSN on the S11/S4 interface. This IE shall include the TEID for GTP based S5/S8 case and the uplink GRE key in the PMIP based S5/S8 case. For PMIP based S5/S8, this IE shall be included on the S11/S4 interface and shall contain the PGW S5/S8 IP address for control plane; the same IP address shall be used for both control plane and the user plane communication if the Bearer Context IE does not contain a S5/S8-U PGW F-TEID IE. See NOTE 7. The PGW shall include this IE on the S2b interface during the Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b, Handover to Untrusted Non-3GPP IP Access with GTP on S2b procedures and Initial Attach for emergency session (GTP on S2b). The PGW shall include this IE on the S2a interface during the Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, UE initiated Connectivity to Additional PDN with GTP on S2a procedures See NOTE 6.	F-TEID	1

² DN Address \llocation (PAA)	C	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces for the E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN, UE requested PDN connectivity, Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b, Handover to Untrusted Non-3GPP IP Access with GTP on S2b, Initial Attach for emergency session (GTP on S2b), Initial Attach in WLAN on GTP S2a, Initial Attach in WLAN for Emergency Service on GTP S2a, UE initiated Connectivity to Additional PDN with GTP on S2a and Handover to TWAN with GTP on S2a. The PDN type field in the PAA shall be set to IPv4, or IPv6 or IPv4v6, or Non-IP by the PGW. See NOTE4. For the S4/S11 and S5/S8 interfaces, if the PGW uses DHCPv4 for IPv4 address allocation, the IPv4 address field shall be set to 0.0.0.0; otherwise, the IPv4 address field shall be set to non-zero value as specified in 3GPP TS 23.401 [3] and 3GPP TS 23.402 [45]. When assigning an IPv6 address the PGW shall send a non-zero Interface Identifier. See NOTE 8. For Non-IP PDN connections, the PDN Address and Prefix field shall not be present.	ΡΑΑ	0
VPN Restriction	С	This IE shall be included on the S5/S8 and S4/S11 interfaces in the E-UTRAN initial attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN and UE Requested PDN connectivity procedures. This IE shall also be included on S4/S11 during the Gn/Gp SGSN to S4 SGSN/MME RAU/TAU procedures. This IE denotes the restriction on the combination of types of APN for the APN associated with this EPS bearer Context.	APN Restriction	0
Aggregate Maximum Bit Rate (APN-AMBR)	С	This IE represents the APN-AMBR. It shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if the received APN-AMBR has been modified by the PCRF.	AMBR	0
inked EPS Bearer ID	С	This IE shall be sent on the S4/S11 interfaces during Gn/Gp SGSN to S4-SGSN/MME RAU/TAU procedure to identify the default bearer the PGW selects for the PDN Connection.	EBI	0
Protocol Configuration Options PCO)		If ePCO is not supported by the UE or the network, and if the PGW decides to return PCO to the UE during the Attach, PDN connectivity or Handover to 3GPP access procedures, PGW shall send PCO to SGW. If SGW receives the PCO IE, SGW shall forward it to MME/SGSN. For trusted WLAN access, if single-connection mode or multiple-connection mode is used, the PGW may include this IE over the S2a interface to send PCO to the UE.	PCO	0

}earer Contexts ⊧reated	M	EPS bearers corresponding to Bearer Contexts sent in request message. Several IEs with the same type and instance value may be included on the S5/S8 and S4/S11 as necessary to represent a list of Bearers. One single IE shall be included on the S2a/S2b interface. One bearer shall be included for E-UTRAN Initial Attach, a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN, PDP Context Activation, a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN, UE Requested PDN Connectivity , Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b, Handover to Untrusted Non-3GPP IP Access with GTP on S2b, Initial Attach for emergency session (GTP on S2b), Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, UE initiated Connectivity to Additional PDN with GTP on S2a and Handover to TWAN with GTP on S2a. One or more created bearers shall be included for a Handover/TAU/RAU with an SGW change. See NOTE 2.		0		
Bearer Contexts narked for removal	С	EPS bearers corresponding to Bearer Contexts to be removed that were sent in the Create Session Request message. For each of those bearers an IE with the same type and instance value shall be included on the S4/S11 interfaces.	Bearer Context	1		
Recovery	С	This IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0		
	•	Charging Gateway Name Charging Cateway Name Charging Cateway Configured, the PGW shall interface. See NOTE 1. Charging Cateway F	include this IE on th	ne S5 Iress is	FQDN	0
		Address configured, the PGW shall interface. See NOTE 1.	Include this IE on the	ne S5	IP Address	0
'GW-FQ-CSID	С	This IE shall be included by the PGW on the S5/S8 and S2a/S2b interfaces and, when received from S5/S8 be forwarded by the SGW on the S11 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0		
GW-FQ-CSID	С	This IE shall be included by the SGW on the S11 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1		
GW LDN	0	This IE is optionally sent by the SGW to the MME/SGSN on the S11/S4 interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	0		
'GW LDN	0	This IE is optionally included by the PGW on the S5/S8 and S2a/S2b interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	1		
'GW Back-Off Time	0	This IE may be included on the S5/S8 and S4/S11 interfaces when the PDN GW rejects the Create Session Request with the cause "APN congestion". It indicates the time during which the MME or S4-SGSN should refrain from sending subsequent PDN connection establishment requests to the PGW for the congested APN for services other than Service Users/emergency services. See NOTE 3.	EPC Timer	0		
Additional Protocol Configuration Options APCO)	CO	If multiple authentications are supported by the PGW and if PGW received the Additional Protocol Configuration Options IE in the Create Session Request, the PGW shall include this IE on the S2b interface and perform the corresponding procedures as specified for PAP and CHAP authentication of the UE with external networks in 3GPP TS 33.402 [50].	Additional Protocol Configuration Options (APCO)	0		

		If the PGW supports the Additional Protocol Configuration Options IE and if the PGW has received the Additional Protocol Configuration Options IE with the "DNS IPv4/IPv6 Server Address Request" parameter in the Create Session Request over S2b interface, the PGW may include this IE over the S2b interface with the "DNS IPv4/IPv6 Server Address" parameter as specified in 3GPP TS 24.008 [5]. If the PGW supports the Additional Protocol Configuration Options IE and if the PGW has received the Additional Protocol Configuration Options IE with the P-CSCF IPv4 Address Request, or P-CSCF IPv6 Address Request or both parameters in the Create Session Request over the S2b interface, the PGW may include this IE over the S2b interface, the PGW may include this IE over the S2b interface, the PGW may include this IE over the S2b interface, or both parameters respectively as specified in 3GPP TS 24.008 [5]. The PGW may include this IE on the S2a interface to provide the TWAN with additional IP configuration parameters (e.g. DNS server), if a corresponding request		
		was received in the Create Session Request message.		
rusted WLAN IPv4 Parameters	CO	 The PGW shall include this IE on the S2a interface to a Trusted WLAN Access if PDN Type in the PAA is set to IPv4 or IPv4v6 and the transparent single-connection mode is used as specified in 3GPP TS 23.402 [45]. This IE shall include: The Subnet Prefix Length of the subnet from which the PGW allocates the UE's IPv4 address. The IPv4 Default Router Address which belongs to the same subnet as the IPv4 address allocated to the UE. 	IPv4 Configuration Parameters (IP4CP)	0

ndication Flags	со	This IE shall be included if any one of the applicable flags is set to 1.	Indication	0
		Applicable flags are:		
		 PDN Pause Support Indication: this flag shall be set to 1 on the S5/S8 interface if the PGW supports the PGW Pause of Charging procedure. 		
		 PDN Pause Enable Indication: this flag shall be set to 1 on the S5/S8 interface if the PGW enables the SGW to use the PGW Pause of Charging procedure for this PDN connection. 		
		 Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. This flag shall be set to 1 by the PGW if the "PGW's Overload Control Information" is included and the Cause IE is set to a rejection cause code. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. 		
		 Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW. This flag shall be set to 1 by the SGW if the "SGW's Overload Control Information" is included and the Cause IE is set to a rejection cause code. 		
		 Delay Tolerant Connection Indication: the flag shall be set to 1 on the S5/S8 and S11/S4 interface if the PDN connection is "Delay Tolerant" (see subclause 8.12). 		
		- Triggering SGSN initiated PDP Context Creation/Modification Indication: this flag shall be set to 1 on the S5/S8 interfaces if the network- initiated NBIFOM mode is used for this PDN connection. The SGW shall set this flag on the S4 interface if it supports the NBIFOM feature and the flag is set on the S5/S8 interface.		
resence Reporting	СО	This IE shall be included on the S5/S8 and S11/S4 interfaces with the appropriate Action field if reporting changes of UE presence in a Presence Routing Area is to be started, stopped or modified for this subscriber in the MME/SGSN.	Presence Reporting Area	0
rea Action		Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. One IE shall be included per PRA to be started, stopped or modified.	Action	
GW's node level oad Control formation	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing its node level load information, if the load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access network, belongs (see clause 12.2.6).	Load Control Information	0

	СО	If the SGW receives this IE and if it supports the load		
		control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
PGW's APN level .oad Control nformation	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.2.6).	Load Control Information	1
		When present, the PGW shall provide one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 9, NOTE 11.		
	CO	If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4- SGSN on the S11/S4 interface.		
GW's node level .oad Control nformation	0	The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6).	Load Control Information	2
		When present, the SGW shall provide only one instance of this IE, representing its node level load information.		
PGW's Overload	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 10, NOTE 12.		
	со	If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
GW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
	со	This IE shall be included on the S5/S8 or S2a/S2b interfaces if the PGW needs to send NBIFOM informationas specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4.		
IBIFOM Container	со	If the SGW receives an NBIFOM Container from the PGW, the SGW shall forward this IE to the MME/S4-SGSN on the S11/S4 interface.	F-Container	0
PDN Connection Charging ID	СО	The PGW shall include this IE on the S5/S8 or S2a/S2b interfaces, during an Initial Attach, Initial PDN connection establishment, or Addition of an access procedures, when using NBIFOM, as specified in 3GPP TS 23.161 [71].	Charging ID	0

Extended Protocol Configuration Options ePCO)		СО	If the PGW decides to return ePCO to the UE during an Initial Attach, UE requested PDN Connectivity procedure, and if the PGW supports the ePCO and the EPCOSI flag is set to 1 in the Create Session Request message, the PGW shall send ePCO to the SGW. If the SGW receives the ePCO IE, the SGW shall forward it	ePCO	0	
_			to the MME. See NOTE 13.			
rivate Ex	tension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS	
JOTE1:			Gateway Name and Charging Gateway Address shall not be	included at the sam	ne	
JOTE2:	If the SGW	canr	are available, the operator configures a preferred value. Not accept any of the "Bearer Context Created" IEs within Cru CW about the Create Section Response with appropria			
IOTE 3:	The last rec	eive	GW shall send the Create Session Response with appropria d value of the PGW Back-Off Time IE shall supersede any p			
JOTE4:	3GPP TS 23	3.40 9 of t	and for this APN in the MME/SGSN. 1 [3] (see subclause 5.3.1.1) and 3GPP TS 23.060 [35] (see he cases when UE has requested IPv4v6 PDN Type, but PC			
IOTE 5: The conditions of presence of the IEs in the Create Session Response for the MME and S4-SGSN triggered Serving GW relocation (see subclause 5.10.4 of 3GPP TS 23.401 [3] and subclause 9.2.2.4 of 3GPP TS 23.060 [35]) are identical to those specified respectively for X2 handover with SGW relocation and for Enhanced Serving RNS Relocation with SGW relocation.						
JOTE 6:	GTP based	Con	and TEID/GRE key in "PGW S5/S8/ S2a/S2b F-TEID for PM trol Plane interface" IE are only provided for the subsequent DN connection and shall NOT be used for other PDN connect	GTP-C initial mess		
JOTE 7:						
JOTE 8:	E 8: The Interface Identifier value of zero is a reserved value (see IETF RFC 5453 [58]). Subclause 5.3.1.2.2 of 3GPP TS 23.401 [3] specifies the mechanism for preventing UE's link-local address collision with the PGW's link-local address.					
IOTE 9:						
JOTE 10:	The receive	r, su \PN	pporting the APN level overload information for the maximur level overload information for the first 10 APNs and ignore a			
IOTE 11: The APN level load information, provided within and across different instances of the "PGW's APN level Load Control Information" IE(s) shall be limited to 10 different APNs.						
IOTE 12: The APN level overload information, provided within and across different instances of the "PGW's Overload Control Information" IE(s) shall be limited to 10 different APNs.						
10TE 13:	The MME sl an indication	hall o h tha	consider the presence of the ePCO IE in the Create Session it the PGW and the SGW support the ePCO. The UE consid when it receives an ePCO from the PGW.		e as	

Table 7.2.2-2: Bearer Context Created within Create Session Response

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
EPS Bearer ID	Μ		EBI	0
Cause	Μ	This IE shall indicate if the bearer handling was successful,	Cause	0
		and if not, it gives information on the reason. (NOTE 1,		
		NOTE 2, NOTE 3)		
S1-U SGW F-TEID	С	This IE shall be included on the S11 interface if the S1-U	F-TEID	0
		interface is used, i.e. if the S11-U Tunnel flag was not set		
		in the Create Session Request. See NOTE 6		
S4-U SGW F-TEID	С	This IE shall be included on the S4 interface if the S4-U	F-TEID	1
		interface is used.		
S5/S8-U PGW F-	С	For GTP-based S5/S8, this User Plane IE shall be included	F-TEID	2
TEID		on S4/S11 and S5/S8 interfaces during the "E-UTRAN		
		Initial Attach", a Handover from Trusted or Untrusted Non-		
		3GPP IP Access to E-UTRAN, a "PDP Context Activation",		
		a Handover from Trusted or Untrusted Non-3GPP IP		
		Access to UTRAN/GERAN or a "UE Requested PDN		
		Connectivity".		
		For PMIP-based S5/S8, this IE shall be included on the		
		S4/S11 interface during the "E-UTRAN Initial Attach", a		
		Handover from Trusted or Untrusted Non-3GPP IP Access		
		to E-UTRAN, a "PDP Context Activation", a Handover from		
		Trusted or Untrusted Non-3GPP IP Access to		
		UTRAN/GERAN or a "UE Requested PDN Connectivity" if		
		the PGW provided an alternate address for user plane, i.e.		
		an IP address for user plane which is different from the IP address for control plane.		
		When present, this IE shall contain the alternate IP		
		address for user plane and the uplink GRE key.		
		See NOTE 4 and NOTE 5.		
S12 SGW F-TEID	С	This IE shall be included on the S4 interface if the S12	F-TEID	3
		interface is used.		
S2b-U PGW F-TEID	С	This IE (for user plane) shall be included on the S2b	F-TEID	4
		interface during the Attach with GTP on S2b, UE initiated		
		Connectivity to Additional PDN with GTP on S2b,		
		Handover to Untrusted Non-3GPP IP Access with GTP on		
		S2b, and Initial Attach for emergency session (GTP on		
		S2b).		
S2a-U PGW F-TEID	С	This IE (for user plane) shall be included on the S2a	F-TEID	5
		interface during the Initial Attach in WLAN on GTP S2a, an		
		Initial Attach in WLAN for Emergency Service on GTP S2a,		
		UE initiated Connectivity to Additional PDN with GTP on		
Deerer Level OeC	<u> </u>	S2a, and Handover to TWAN with GTP on S2a.	Deerer OeC	
Bearer Level QoS	С	This IE shall be included on the S5/S8, S4/S11 and	Bearer QoS	0
		S2a/S2b interfaces if the received QoS parameters have been modified.		
	С	This IE shall be included on the S5/S8 interface for an E-		
	C	UTRAN initial attach, a Handover from Trusted or		
		Untrusted Non-3GPP IP Access to E-UTRAN, a PDP		
		Context Activation, a Handover from Trusted or Untrusted		
		Non-3GPP IP Access to UTRAN/GERAN and a UE		
		requested PDN connectivity.	.	
Charging Id	0	If the S5/S8 interface is GTP, this IE may be included on	Charging Id	0
	Ĩ	the S4 interface, in order to support CAMEL charging at		
		the SGSN, for a PDP Context Activation, a Handover from		
		Trusted or Untrusted Non-3GPP IP Access to		
		UTRAN/GERAN, inter S4-SGSN RAU with SGW change		
		and Gn/Gp to S4-SGSN RAU.		
	1			

	CO	This IE shall be included on the S2a/S2b interface for an Initial Attach in WLAN on GTP S2a, an Initial Attach in WLAN for Emergency Service on GTP S2a, Attach with GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2b, Handover to Untrusted Non-3GPP IP Access with GTP on S2b, Initial Attach for emergency session (GTP on S2b, UE initiated Connectivity to Additional PDN with GTP on S2a, and Handover to TWAN with GTP on S2a.		
Bearer Flags	0	Applicable flags are: - PPC (Prohibit Payload Compression) : this flag may be set on the S5/S8 and S4 interfaces.	Bearer Flags	0
S11-U SGW F-TEID	С	This IE shall be included on the S11 interface if the S11-U interface is used, i.e. if the S11-U Tunnel flag was set in the Create Session Request. If the SGW supports both IP address types, the SGW shall send both IP addresses within the F-TEID IE. If only one IP address is included, then the MME shall assume that the SGW does not support the other IP address type.	F-TEID	6

NOTE 1: NOTE 2:	According to 3GPP TS 23.401 [3] e.g. subclause 5.5.1.2.2 "S1-based handover, normal" and 3GPP TS 23.060 [35], during the handover procedure with an SGW change, except in the case of X2-handover (NOTE2 addresses X2 based HO with SGW change case), the target MME/S4-SGSN initiates the Create Session Request/Response and Modify Bearer Request/Response procedures one after the other. After receiving the "Bearer Context to be Created" IEs within Create Session Request message, the SGW may not accept some of these bearers. The SGW however shall return all bearers with the "Bearer Context Created" IEs within Create Session Response message (this table), but with different Cause values. Bearers that were not accepted by the SGW shall have an appropriate rejection value in the Cause IE. The target MME/S4-SGSN shall send these non-accepted bearers to the target SGW within the "Bearer Context to be removed" IE in a subsequent Modify Bearer Request message. Therefore, the SGW shall allocate the DL S5/S8 SGW F-TEIDs also for the non-accepted bearers. MME/S4-SGSN should remove all of the non-accepted bearers by separate procedures (e.g. an MME/S4-SGSN initiated Dedicated Bearer Deactivation procedure). According to 3GPP TS 23.060 [35] subclause 5.5.1.1.3, "X2-based handover with Serving GW relocation", and 3GPP TS 23.060 [35] subclause 6.9.2.2.5A "Enhanced Serving RNS Relocation Procedure using S4", during the X2-handover procedure with an SGW change and Enhanced
	Serving RNS Relocation Procedure with an SGW change, the target MME/S4-SGSN shall initiate only the Create Session Request/Response procedure. The SGW shall return all bearers (including those not accepted by the SGW) with a "Bearer Context Created" IE within Create Session Response message (this table), but with different Cause values. Bearers that were not accepted by the SGW shall have an appropriate rejection value in the Cause IE, The MME/S4-SGSN should
	remove these non-accepted bearers by separate procedures as well.
	According to 3GPP TS 23.401 [3] e.g. subclause 5.3.3.1 "Tracking Area Update procedure with Serving GW change" and 3GPP TS 23.060 [35], during the RAU/TAU procedure with an SGW change, the target MME/S4-SGSN shall initiate only the Create Session Request/Response procedure. The SGW shall return all bearers (including those not accepted by the SGW) with a "Bearer Context Created" IE within Create Session Response message (this table), but with different Cause values. Bearers that were not accepted by the SGW shall have an appropriate rejection value in the Cause IE. When Active Flag or Follow-on request is set during TAU/RAU procedure, MME/S4- SGSN should not establish user plane tunnel over S1 or lu for those bearer contexts which were not accepted by the target SGW, while in the corresponding Modify Bearer Request message, the MME/S4-SGSN shall include all accepted bearer contexts in the "Bearer Context to be modified" IE and include all non-accepted bearer contexts in the "Bearer Context to be removed" IE. The MME/S4-SGSN should remove the bearers non-accepted by either SGW or eNB/RNC by separate procedures as well.
	The capability to receive from the LMA an alternate LMA address for user plane shall be supported homogeneously across all the SGWs, when supported over PMIP-based S5/S8.
NOTE 5:	For PMIP based S5/S8, the 'S5/S8-U PGW F-TEID' IE and the 'PGW S5/S8/ S2a/S2b F-TEID for PMIP based interface or for GTP based Control Plane interface' IE shall contain the same uplink GRE key; the Interface Type in these IEs shall be set to the value 9 (S5/S8 PGW PMIPv6 interface).
NOTE 6:	 When Control Plane CloT EPS Optimization is supported, the IP address spaces for S1-U and S11-U may be different, based on operator's deployment. If so, the following requirements shall apply: 1) if the CPOPCI (Control Plane Only PDN Connection Indication) flag is not set in the Create Session Request message, the SGW shall include both the S11-U SGW F-TEID and S1-U SGW F-TEID in the Create Session Response message, regardless of whether the S11-U Tunnel flag is set in the Create Request. 2) all the MMEs in the PLMN shall support receiving both the S11-U SGW F-TEID and S1-U SGW F-TEID in the Create Session Response response; the MME shall use them according to whether the CloT Control Plane Optimization is used.

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Р	Condition / Comment	IE Type	Ins.		
EPS Bearer ID	М		EBI	0		
Cause		This IE shall indicate if the bearer handling was successful, and if not, gives the information on the reason.	Cause	0		

Table 7.2.2-3: Bearer Context marked for removal within a Create Session Response

Octet 1		Load Control Information IE Type = 181 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Load Metric	Μ	See clauses 12.2.5.1.2.2 and 12.2.5.1.2.3 for the	Metric	0		
		description and use of this parameter.				
List of APN and	CO	The IE shall (only) be present in the "PGW's APN level	APN and Relative	0		
Relative Capacity		Load Control Information" IE.	Capacity			
		For indicating the APN level load, the PGW shall include				
		one or more instances of this IE, up to maximum of 10,				
		with the same type and instance value, representing a list				
		of APN(s) & its respective "Relative Capacity" (sharing the				
		same "Load Metric").				
		See clause 12.2.5.1.2.3 for the description and use of this				
		parameter.				
		See NOTE 1.				
		occurrences of "APN and Relative Capacity" IE are received				
the Load Control Information IE, the receiver shall treat it as a protocol error and ignore the entire						
Load Control Information IE instance.						

Table 7.2.2-4: Load Control Information within Create Session Response

Table 7.2.2-5: Overload Control Information within Create Session Response

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Р	Condition / Comment	ІЕ Туре	Ins.		
Overload Control Sequence Number	Μ	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0		
Overload Reduction Metric	Μ	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0		
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0		
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0		
NOTE 1: If more than 10 occurrences of APNs are received within one instance of the Overload Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control Information IE instance.						

7.2.3 Create Bearer Request

The direction of this message shall be from PGW to SGW and from SGW to MME/S4-SGSN, and from PGW to TWAN/ePDG (see Table 6.1-1).

The Create Bearer Request message shall be sent on the S5/S8 interface by the PGW to the SGW and on the S11 interface by the SGW to the MME as part of the Dedicated Bearer Activation procedure.

The message shall also be sent on the S5/S8 interface by the PGW to the SGW and on the S4 interface by the SGW to the SGSN as part of the Secondary PDP Context Activation procedure or the Network Requested Secondary PDP Context Activation procedure.

The message shall also be sent on the S2a interface by the PGW to the TWAN as part of the Dedicated bearer activation in WLAN on GTP S2a, and on the S2b interface by the PGW to the ePDG as part of the Dedicated S2b bearer activation with GTP on S2b.

The message shall also be sent on the S5/S8 or S2a/S2b interface by the PGW to the SGW or to the TWAN/ePDG and on the S11/S4 interface by the SGW to the MME/S4-SGSN as part of the Network-initiated IP flow mobility procedure or the UE-initiated IP flow mobility procedure, as specified by 3GPP TS 23.161 [71].

Table 7.2.3-1: Information Elements in a Create Bearer Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Procedure Transaction Id (PTI)	С	This IE shall be sent on the S5/S8 and S4/S11 interfaces when the procedure was initiated by a UE Requested Bearer Resource Modification Procedure or UE Requested Bearer Resource Allocation Procedure (see NOTE 1) or Secondary PDP Context Activation Procedure. The PTI shall be the same as the one used in the corresponding Bearer Resource Command.	PTI	0
Linked EPS Bearer ID (LBI)	М	This IE shall be included to indicate the default bearer associated with the PDN connection.	EBI	0
Protocol Configuration Options (PCO)	0	This IE may be sent on the S5/S8 and S4/S11 interfaces if ePCO is not supported by the UE or the network.	PCO	0
Bearer Contexts	М	Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers.	Bearer Context	0
PGW-FQ-CSID	С	This IE shall be included by the PGW on the S5/S8 and S2a/S2b interfaces and, when received from S5/S8 be forwarded by the SGW on the S11 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by the SGW on the S11 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
Change Reporting Action	С	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field If the location Change Reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	Change Reporting Action	0
CSG Information Reporting Action	СО	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if the CSG Info reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	CSG Information Reporting Action	0
H(e)NB Information Reporting	CO	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if H(e)NB information reporting is to be started or stopped for the PDN connection in the SGSN/MME.	H(e)NB Information Reporting	0
Presence Reporting Area Action	CO	This IE shall be included on the S5/S8 and S11/S4 interfaces with the appropriate Action field if reporting changes of UE presence in a Presence Routing Area is to be started, stopped or modified for this subscriber in the MME/SGSN. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. One IE shall be included per PRA	Presence Reporting Area Action	0
Indication Flags	СО	to be started, stopped or modified. This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: - Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node	Indication	0
		 identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW. 		

		The DOW may include this IE as the OF/OOL OOL/OC		~
PGW's node level Load Control Information		The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing its node level load information, if the load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access network, belongs (see clause 12.2.6).	Load Control Information	0
	CO	If the SGW receives this IE and if it supports the load control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
PGW's APN level Load Control Information	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.2.6).	Load Control Information	1
		When present, the PGW shall provide one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 2, NOTE 4.		
		If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
SGW's node level Load Control Information		The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6).	Load Control Information	2
		When present, the SGW shall provide only one instance of this IE, representing its node level load information.		
PGW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s).		
	CO	See NOTE 3, NOTE 5. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
SGW's Overload Control Information		During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
NBIFOM Container	СО	This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4.	F-Container	0
		If the SGW receives a NBIFOM Container IE from the PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS

NOTE 1:	This message refers to the UE requested bearer resource allocation procedure and UE requested bearer resource modification procedures defined in 3GPP TS 24.301 [23], both are specified in 3GPP TS 23.401 [3] in the clause "UE requested bearer resource modification".
NOTE 2:	The receiver, not supporting the APN level load control feature, shall ignore all the occurrence(s) of this IE, i.e. "Load Control Information" IE with instance number "1". The receiver, supporting the APN level load control feature and supporting the APN level load information for the maximum of 10 APNs, shall handle the APN level load information for the first 10 APNs and ignore any more APN level load information.
NOTE 3:	The receiver, supporting the APN level overload information for the maximum of 10 APNs, shall handle the APN level overload information for the first 10 APNs and ignore any more APN level overload information.
NOTE 4:	The APN level load information, provided within and across different instances of the "PGW's APN level Load Control Information" IE(s) shall be limited to 10 different APNs.
NOTE 5:	The APN level overload information, provided within and across different instances of the "PGW's Overload Control Information" IE(s) shall be limited to 10 different APNs.

NOTE: In the case that the procedure was initiated by a UE Requested Bearer Resource Modification Procedure or a UE Requested Bearer Resource Allocation Procedure or Secondary PDP Context Activation Procedure, then there will be only one instance of the Bearer Contexts IE in the Create Bearer Request.

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
EPS Bearer ID	Μ	This IE shall be set to 0.	EBI	0
TFT		This IE can contain both uplink and downlink packet filters to be sent to the UE or the TWAN/ePDG. The SGW shall forward the IE unmodified on the S4/S11 interface.	Bearer TFT	0
S1-U SGW F-TEID	С	This IE shall be sent on the S11 interface if the S1-U interface is used. If SGW supports both IPv4 and IPv6, it shall send both an IPv4 address and an IPv6 address within the S1-U SGW F-TEID IE. See NOTE 1.	F-TEID	0
S5/8-U PGW F-TEID		This IE shall be sent on the S4, S5/S8 and S11 interfaces for GTP-based S5/S8 interface. The MME/SGSN shall ignore the IE on S11/S4 for PMIP-based S5/S8 interface.	F-TEID	1
S12 SGW F-TEID	С	This IE shall be sent on the S4 interface if the S12 interface is used. See NOTE 1.	F-TEID	2
S4-U SGW F-TEID	С	This IE shall be sent on the S4 interface if the S4-U interface is used. See NOTE 1.	F-TEID	3
S2b-U PGW F-TEID	С	This IE (for user plane) shall be sent on the S2b interface.	F-TEID	4
S2a-U PGW F-TEID	С	This IE (for user plane) shall be sent on the S2a interface.	F-TEID	5
Bearer Level QoS	Μ		Bearer QoS	0
Charging Id		This IE shall be sent on the S5/S8 interface. If the S5/S8 interface is GTP, this IE may be sent on the S4 interface, in order to support CAMEL charging at the SGSN. This IE shall be sent on the S2a/S2b interface.	Charging Id	0
Bearer Flags		 Applicable flags are: PPC (Prohibit Payload Compression) : this flag may be set on the S5/S8 and S4 interfaces. vSRVCC indicator: This IE may be included by the PGW on the S5/S8 interface according to 3GPP TS 23.216 [43]. When received from S5/S8, SGW shall forward on the S11 interface. 	Bearer Flags	0
Protocol Configuration Options (PCO)	0	This IE may be sent on the S5/S8 and S4/S11 interfaces if ePCO is not supported by the UE or the network. This bearer level IE takes precedence over the PCO IE in the message body if they both exist.	PCO	0
Extended Protocol Configuration Options (ePCO)	0	This IE may be sent on the S5/S8 and S11 interfaces if the UE and the network support ePCO.	ePCO	0
NOTE 1: The SGW s interfaces.	hall	use the same F-TEID IP address and TEID values for S1-U,	S4-U and S12	

Table 7.2.3-2: Bearer Context within Create Bearer Request

Octet 1		Load Control Information IE Type = 181 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.			
elements							
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0			
Sequence Number		parameter.	Number				
Load Metric	Μ	See clauses 12.2.5.1.2.2 and 12.2.5.1.2.3 for the	Metric	0			
		description and use of this parameter.					
List of APN and	CO	The IE shall (only) be present in the "PGW's APN level	APN and Relative	0			
Relative Capacity		Load Control Information" IE.	Capacity				
		For indicating the APN level load, the PGW shall include					
		one or more instances of this IE, up to maximum of 10,					
		with the same type and instance value, representing a list					
		of APN(s) & its respective "Relative Capacity" (sharing the					
		same "Load Metric").					
		See clause 12.2.5.1.2.3 for the description and use of this					
		parameter.					
		See NOTE 1.					
		occurrences of "APN and Relative Capacity" IE are received					
the Load Control Information IE, the receiver shall treat it as a protocol error and ignore the entire							
Load Control Information IE instance.							

 Table 7.2.3-4: Overload Control Information within Create Bearer Request

Octet 1		Overload Control Information IE Type = 181 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.			
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0			
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0			
Period of Validity	M	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0			
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0			
Information	NOTE 1: If more than 10 occurrences of APNs are received within one instance of the Overload Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control Information IE instance.						

7.2.4 Create Bearer Response

The Create Bearer Response message shall be sent on the S5/S8 interface by the SGW to the PGW, and on the S11 interface by the MME to the SGW as part of the Dedicated Bearer Activation procedure.

The message shall also be sent on the S5/S8 interface by the SGW to the PGW and on the S4 interface by the SGSN to the SGW as part of Secondary PDP Context Activation procedure or the Network Requested Secondary PDP Context Activation procedure.

The message shall also be sent on the S2a interface by the TWAN to the PGW as part of the Dedicated bearer activation in WLAN on GTP S2a and on the S2b interface by the ePDG to the PGW as part of the Dedicated S2b bearer activation with GTP on S2b.

The message shall also be sent on the S5/S8 or S2a/S2b interface by the SGW or the TWAN/ePDG to the PGW and on the S11/S4 interface by the MME/S4-SGSN to the SGW as part of the Network-initiated IP flow mobility procedure or UE-initiated IP flow mobility procedure, as specified by 3GPP TS 23.161 [71].

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Context not found".
- "Semantic error in the TFT operation".
- "Syntactic error in the TFT operation".
- "Semantic errors in packet filter(s)".
- "Syntactic errors in packet filter(s)".
- "Unable to page UE".
- "UE not responding".
- "Unable to page UE due to Suspension".
- "UE refuses".
- "Denied in RAT".
- "Temporarily rejected due to handover/TAU/RAU procedure in progress".
- "MME/SGSN refuses due to VPLMN Policy".
- "UE is temporarily not reachable due to power saving".
- "Request rejected due to UE capability".

Table 7.2.4-1: Information Elements in a Create Bearer Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Bearer Contexts	М	All the bearer contexts included in the corresponding Create Bearer Request shall be included. Several IEs with this type and instance value shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces as necessary to represent a list of Bearers.	Bearer Context	0
Recovery	С	This IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0
MME-FQ-CSID	С	This IE shall be included by the MME on the S11 interfaceand shall be forwarded by the SGW on the S5/S8 interfaces according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by the SGW on the S5/S8 interfaces according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
ePDG-FQ-CSID	С	This IE shall be included by the ePDG on the S2b interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	2
TWAN-FQ-CSID	С	This IE shall be included by the TWAN on the S2a interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	3
Protocol Configuration Options (PCO)		If the UE includes the PCO IE, then the MME/SGSN shall copy the content of this IE transparently from the PCO IE included by the UE. If the SGW receives PCO from MME/SGSN, SGW shall forward it to the PGW.	PCO	0
UE Time Zone	со	This IE is optionally included by the MME on the S11 interface or by the SGSN on the S4 interface. The SGW shall forward this IE on the S5/S8 interface if the SGW receives it from the MME/SGSN. This IE shall be included by the TWAN on the S2a interface.	UE Time Zone	0
User Location Information (ULI)		This IE shall be included by the MME on the S11 interface or by the SGSN on the S4 interface. The CGI/SAI shall be included by SGSN and the ECGI shall be included by MME. See NOTE 1. The SGW shall forward this IE on the S5/S8 interface if it receives it from the MME/SGSN.	ULI	0
TWAN Identifier	со	This IE shall be included by the TWAN on the S2a interface as specified in 3GPP TS 23.402 [45].	TWAN Identifier	0
MME/S4-SGSN's Overload Control Information		During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8	Overload Control Information	0
SGW's Overload Control Information	0	interface. During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	1

Duran and Damartin a		The MME/000N shall include this JE are 044/04 if the	Desserves	~
Presence Reporting Area Information		The MME/SGSN shall include this IE on S11/S4 if the PGW/PCRF/OCS has requested to start or modify reporting changes of UE presence in Presence Reporting Area(s) in the corresponding Create Bearer Request message and the MME/SGSN supports such reporting. The MME/SGSN shall then indicate whether the UE is inside or outside the newly started or modified Presence Reporting Area(s), or indicate that the Presence Reporting Area(s) is inactive.	Presence Reporting Area Information	0
		Presence Reporting Area Information from the MME/SGSN.		
		Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Information. One IE shall be included for each PRA newly started or modified.		
MME/S4-SGSN Identifier		If the overload control feature is supported by the MME/S4- SGSN and is activated for the PLMN to which the PGW belongs (see subclause 12.3.11), the MME/S4-SGSN shall include this IE on the S11/S4 interface if the PGW has not been updated with the identity of the currently serving MME/S4-SGSN, i.e. if no other message carrying MME/S4-SGSN identity has been sent to the PGW during/after an inter-MME/S4-SGSN intra-SGW mobility procedure.		0
TWAN/ePDG's Overload Control Information	0	During an overload condition, the TWAN/ePDG may include this IE over the S2a/S2b interface if the overload control feature is supported by the TWAN/ePDG and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control Information	2
		When present, the TWAN/ePDG shall provide only one instance of this IE, representing its overload information.		
WLAN Location Information	СО	The ePDG shall include this IE on the S2b interface if the WLAN Location Information is available.	TWAN Identifier	1
WLAN Location Timestamp	со	The ePDG shall include this IE on the S2b interface, if the WLAN Location Timestamp is available.	TWAN Identifier Timestamp	1
UE Local IP Address	со	The ePDG shall include this IE on the S2b interface.	IP Address (See NOTE 2)	0
UE UDP Port	со	The ePDG shall include this IE on the S2b interface if NAT is detected and the UDP encapsulation is used.	Port Number	0
NBIFOM Container		This IE shall be included on the S11/S4 or S2a/S2b interfaces if the MME/S4-SGSN or the TWAN/ePDG receives a NBIFOM Container from the UE as specified in 3GPP TS 24.161 73]. The Container Type shall be set to 4.	F-Container	0
	СО	If the SGW receives a NBIFOM Container IE from the MME/S4-SGSN, the SGW shall forward it to the PGW on the S5/S8 interface.		
UE TCP Port	со	The ePDG shall include this IE on the S2b interface if NAT is detected and the TCP encapsulation is used.	Port Number	1
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS
	_			

NOTE 1: In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID.
 In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in SAI/CGI to the PGW, for both supporting UEs or allocated by the network for non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network. See subclause 4.4 of 3GPP TS 23.251 [55].

NOTE 2: It is not correct that the IP Address IE type with the same instance 0 appears twice in the message table, however, there is no problem because the MME/SGSN Identifier (received over S11/S4/S5/S8) and UE Local IP Address (received over S2b) can never appear in the same message. It was not possible to change the instance of IP Address IE type since it would have been a backward incompatible change.

Table 7.2.4-2: Bearer Context within Create Bearer Response

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Р	Condition / Comment	ІЕ Туре	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
Cause	М	This IE shall indicate if the bearer handling was successful, and if not, it gives information on the reason.	Cause	0
S1-U eNodeB F-TEID	С	This IE shall be sent on the S11 interface if the S1-U interface is used.	F-TEID	0
S1-U SGW F-TEID	С	This IE shall be sent on the S11 interface. It shall be used to correlate the bearers with those in the Create Bearer Request.	F-TEID	1
S5/8-U SGW F-TEID	С	This IE shall be sent on the S5/S8 interfaces.	F-TEID	2
S5/8-U PGW F-TEID	С	This IE shall be sent on the S5/S8 interfaces. It shall be used to correlate the bearers with those in the Create Bearer Request.	F-TEID	3
S12 RNC F-TEID	С	This IE shall be sent on the S4 interface if the S12 interface is used. See NOTE1.	F-TEID	4
S12 SGW F-TEID	С	This IE shall be sent on the S4 interface. It shall be used to correlate the bearers with those in the Create Bearer Request. See NOTE1.	F-TEID	5
S4-U SGSN F-TEID	С	This IE shall be sent on the S4 interface if the S4-U interface is used. See NOTE1.	F-TEID	6
S4-U SGW F-TEID	С	This IE shall be sent on the S4 interface. It shall be used to correlate the bearers with those in the Create Bearer Request. See NOTE1.	F-TEID	7
S2b-U ePDG F-TEID	С	This IE shall be sent on the S2b interface.	F-TEID	8
S2b-U PGW F-TEID	С	This IE shall be sent on the S2b interface. It shall be used to correlate the bearers with those in the Create Bearer Request.	F-TEID	9
S2a-U TWAN F-TEID	С	This IE shall be sent on the S2a interface.	F-TEID	10
S2a-U PGW F-TEID	С	This IE shall be sent on the S2a interface. It shall be used to correlate the bearers with those in the Create Bearer Request.	F-TEID	11
Protocol Configuration Options (PCO)	CO	If the UE includes the PCO IE in the corresponding message, then the MME/SGSN shall copy the content of this IE transparently from the PCO IE included by the UE. If the SGW receives PCO from MME/SGSN, SGW shall forward it to the PGW. This bearer level IE takes precedence over the PCO IE in the message body if they both exist.	PCO	0
RAN/NAS Cause	СО	If the bearer creation failed, the MME shall include this IE on the S11 interface to indicate the RAN cause and/or the NAS cause of the bearer creation failure, if available and if this information is permitted to be sent to the PGW operator according to MME operator's policy. If both a RAN cause and a NAS cause are generated, then several IEs with the same type and instance value shall be included to represent a list of causes. The SGW shall include this IE on the S5/S8 interface if it receives it from the MME. If the bearer creation failed, the TWAN shall include this IE on the S2a interface to indicate the cause of the bearer creation failure, if available and if this information is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 2. If the bearer creation failed, the ePDG shall include this IE on the S2b interface to indicate the cause of the bearer creation failure, if available and if this information is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 2. If the bearer creation failed, the ePDG shall include this IE on the S2b interface to indicate the cause of the bearer creation failure, if available and if this information is permitted to be sent to the PGW operator according to the ePDG operator's policy. When present, the IE shall be encoded as a Diameter or an IKEv2 cause. See NOTE 3.	RAN/NAS Cause	0

Extended P Configuratio (ePCO)			If the UE includes the ePCO IE, then the MME shall copy the content of this IE transparently from the ePCO IE included by the UE.	ePCO	0
			If the SGW receives ePCO from the MME, the SGW shall forward it to the PGW.		
ii ii S S S S S S S S S S S S S S S S S	nterfaces. H dle mode, th between the SGW F-TEII establish a d S4-U SGSN brovided F-T e.g. if the SC SGSN decid	lowe RN D IE lirec F-T EID GW i	use the same F-TEID IP address and TEID values for S1-U, ever, when sending a Create Bearer Request message to ar GW can not know whether the S4-SGSN will establish a dire C and the SGW. The SGW may include either the S4-U SG ¹ in the Create Bearer Request message. The S4-SGSN will t user plane tunnel or not and will provide accordingly either EID in the Create Bearer Response message, where the int may differ from the interface type of the SGW F-TEID used includes the S4-U SGW F-TEID in the Create Bearer Reque o use Direct Tunnelling, the S4-SGSN shall provide the S12 tesponse message, together with S4-U SGW F-TEID. The S	A S4-SGSN for a UE ect user plane tunner W F-TEID IE or the decide whether to a S12 RNC F-TEID erface type of the for bearer correlationst message, and if to RNC F-TEID in the	el S12 O or a on, the
NOTE 2: T	The TWAN oprocedure. T	he	s not exchange signalling with the 3GPP AAA Server nor wit TWAN may include an internal failure cause for the bearer c ed to encode the internal failure cause is implementation spe	reation failure. The	
NOTE 3: T	The ePDG d	loes an i	not exchange signalling with the 3GPP AAA Server in this p nternal failure cause for the bearer creation failure. The prot re cause is implementation specific.	procedure. The ePD	

 Table 7.2.4-3: Overload Control Information within Create Bearer Response

Octet 1		Overload Control Information IE Type = 180 (decimal)						
Octets 2 and 3		Length = n						
Octet 4		Spare and Instance fields	Spare and Instance fields					
Information elements	Р	Condition / Comment	IE Type	Ins.				
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0				
Overload Reduction Metric	М	See clause 12.3.5.1.2.3 for the description and use of this parameter.	Metric	0				
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0				

7.2.5 Bearer Resource Command

A Bearer Resource Command message shall be sent from a MME to a SGW and forwarded to PGW as a part of the UE requested bearer resource allocation procedure or UE requested bearer resource modification procedure (which is used also for a dedicated bearer deactivation), as specified by 3GPP TS 24.301 [23].

The message shall also be sent on the S4 interface by a SGSN to a SGW and on the S5/S8 interface by a SGW to a PGW as part of the MS initiated PDP Context modification procedure, or secondary PDP context activation procedure.

The message shall also be sent on the S11/S4 interface by an MME/S4-SGSN to a SGW and on the S5/S8 or S2a/S2b interface by a SGW or a TWAN/ePDG to a PGW as part of the UE-initiated IP flow mobility procedure and the UE requested IP flow mapping procedure, as specified by 3GPP TS 23.161 [71].

Table 7.2.5-1 specifies the presence of the IEs in the message.

Table 7.2.5-1: Information Elements in a Bearer Resource Command

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Linked EPS Bearer ID (LBI)	М		EBI	0
Procedure Transaction Id (PTI)	М		PTI	0
Flow Quality of Service (Flow QoS)	C	This IE shall be included on the S4/S11 interface if the "Requested New QoS"/"Required QoS" is included in the corresponding NAS message (see section 9.5.10 and section 9.5.4 in 3GPP TS 24.008 [5]) or the "Required traffic flow QoS" is included in the corresponding NAS message (see section 8.3.8 and section 8.3.10 in 3GPP TS 24.301 [23]). If SGW receives this IE, SGW shall forward it to PGW across S5/S8 interface.	Flow QoS	0
Traffic Aggregate		The TAD consists of the description of the packet filter(s) for a traffic flow aggregate. MME shall include this IE over S11 interface.		
Description (TAD)		If S4-SGSN receives this IE from the UE, it shall include it over S4 interface. If SGW receives this IE, the SGW shall forward it to PGW	TAD	0
RAT Type	С	over S5/S8 interface. See NOTE 2. This IE shall be included for MS initiated PDP Context modification procedure and Secondary PDP context activation procedure.	RAT Type	0
Serving Network	0	This IE may be included in the MS initiated PDP Context modification procedure. See NOTE 3.	Serving Network	0
User Location Information (ULI)	0	This IE may be included in the MS initiated PDP Context modification procedure. See NOTE 3.	ULI	0
EPS Bearer ID	С	This IE indicates the EPS Bearer that needs to be modified. It shall be included for MS initiated PDP Context modification procedure. For EUTRAN this IE shall be present if it is triggered by the NAS Bearer Resource Modification Request message and its value shall be set to the value of the "EPS bearer identity for packet filter" IE received in that NAS message.	EBI	1
Indication Flags	CO	 This IE shall be included if any one of the applicable flags is set to 1. Applicable flags: Change Reporting Support Indication: this flag may be set to 1 in the MS initiated PDP Context modification procedure if the SGSN/MME supports location Info Change Reporting and if the SGSN/MME's operator policy permits reporting of location change to the operator of the PGW with which the session is established. Direct Tunnel Flag: this flag shall be set to 1 on the S4 interface, if Direct Tunnel is used in the MS initiated PDP Context Modification procedure. 	Indication	0
S4-U SGSN F-TEID	С	This IE shall be included on the S4 interface when direct tunnel is not established in the MS initiated PDP Context modification procedure See NOTE 1	F-TEID	0
S12 RNC F-TEID		This IE shall be included on the S4 interface when direct tunnel flag is set to 1 in the MS initiated PDP Context modification procedure. See NOTE 1	F-TEID	1
Protocol Configuration Options (PCO)	0	If the UE includes the PCO IE, then the MME/SGSN shall copy the content of this IE transparently from the PCO IE included by the UE. If the SGW receives PCO from the MME/SGSN, the SGW shall forward it to the PGW.	PCO	0

Signalling Indication	Priority	СО	The SGSN/MME shall include this IE on the S4/S11 interface if the UE indicates low access priority during the	Signalling Priority Indication	0
			procedure. The SGW shall forward this IE on the S5/S8 interfaces if received from the MME/SGSN.		
MME/S4-S	Control	0	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control	0
Informatio	n	со	When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8	Information	
			interface.		
SGW's Ov Control Int		0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control Information	1
			When present, the SGW shall provide only one instance of this IE, representing its overload information.		
NBIFOM (Container	CO	This IE shall be included on the S11/S4 or S2a/S2b interfaces if the MME/S4-SGSN or the TWAN/ePDG receives an NBIFOM Container from the UE as specified in 3GPP TS 24.161 73]. The Container Type shall be set to 4.		0
			If the SGW receives an NBIFOM Container IE from the MME/S4-SGSN, the SGW shall forward it to the PGW on the S5/S8 interface.		
Extended Configurat (ePCO)	Protocol tion Options	0	If the UE includes the ePCO IE, then the MME shall copy the content of this IE transparently from the ePCO IE included by the UE. If the SGW receives ePCO from the MME, the SGW shall forward it to the PGW.	ePCO	0
Sender F- Control Pl		со	The SGW shall include this IE on the S5/S8 interfaces and set it to the last value sent to the PGW.	F-TEID	2
			If the Sender F-TEID for Control Plane is received, the PGW shall only handle the Bearer Resource Command message if the Sender F-TEID for Control Plane in this message is the same as the last Sender F-TEID for Control Plane received on the given interface.		
Private Ex	tension	0		Private Extension	VS
NOTE 1:	included in	Upda	S4-U SGSN F-TEID and S12 RNC F-TEID IE are redundant ate Bearer Response message in the MS initiated PDP Cont receiver may ignore it.		
NOTE 2:	In the secon	ndary DIE i	y PDP context activation procedure, if the Bearer Resource (is received, the PGW shall reject the message with cause "L		
NOTE 3:	In shared ne communication that of the a inter-operation non-support	etwo ted i lloca or ro ting l	rks, when the message is sent from the VPLMN to the HPLM n this IE shall be that of the selected Core Network Operator ated Core Network Operator for non-supporting UEs. As an e aming/sharing agreement, if the information on whether the UE is available, the PLMN ID that is communicated to the HI common PLMN ID.	for supporting UEs exception, based on UE is a supporting	, or or
	In shared ne PLMN ID sh communica Network Op non-support	etwo hall b ted in erate ting l	rks, when the MME/S4-SGSN and PGW pertain to the same be communicated in the ECGI to the PGW, and the Common n SAI/CGI to the PGW, for both supporting and non-support or PLMN ID (selected by the UE for supporting UEs or alloca UEs) shall be communicated in the TAI, RAI, UCI and the Se 4.4 of 3GPP TS 23.251 [55].	PLMN ID shall be ng UEs. The Core ated by the network	

NOTE: Depending on the protocol type on the S5/S8 interface, the SGW or the PGW will determine if the UE is requesting an Allocation/Modification operation of bearer resources for a traffic flow aggregate based on the TFT operation code and the packet filter ID value in the Traffic Aggregate (TAD) IE and/or the presence of the EPS Bearer ID IE.

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0		
Metric		parameter.				
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0		
		parameter.				
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				

Table 7.2.5-2: Overload Control Information within Bearer Resource Command

7.2.6 Bearer Resource Failure Indication

A Bearer Resource Failure Indication shall be sent by the PGW to an SGW and forwarded to the MME to indicate failure of the UE requested bearer resource allocation procedure or UE requested bearer resource modification procedure, as specified by 3GPP TS 24.301 [23].

The message shall also be sent by a PGW to an SGW and forwarded to an SGSN as part of the failure of an MS initiated PDP Context modification procedure or secondary PDP context activation procedure.

The message shall also be sent on the S5/S8 or S2a/S2b interface by a PGW to a SGW or to a TWAN/ePDG and the S11/S4 interface by a SGW to an MME/S4-SGSN as part of the UE-initiated IP flow mobility procedure and the UE requested IP flow mapping procedure, as specified by 3GPP TS 23.161 [71].

Table 7.2.6-1 specifies the presence of the IEs in the message.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Semantic error in the TAD operation".
- "Syntactic error in the TAD operation".
- "Semantic errors in packet filter(s)".
- "Syntactic errors in packet filter(s)".
- "Collision with network initiated request".
- "Service denied".
- "Bearer handling not supported".
- "UE context without TFT already activated".

Table 7.2.6-1: Information Elements in a Bearer Resource Failure Indication

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Linked EPS Bearer ID	Μ	See subclause 6.1.1 "Presence requirements of Information Elements".	EBI	0
Procedure Transaction ID (PTI)	М	See subclause 6.1.1 "Presence requirements of Information Elements".	PTI	0
Indication Flags	со	This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are:	Indication	0
		 Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW 		
PGW's Overload Control Information	0	selection) of the serving SGW. During an overload condition, the PGW may include this IE on the S5/S8, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 1, NOTE 2.		
	СО	If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
Recovery	0		Recovery	0
NBIFOM Container	CO	This IE shall be included on the S5/S8 or S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. If the SGW receives an NBIFOM Container IE from the	F-Container	0
		PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
Private Extension	0		Private Extension	VS
NOTE 1: The receive handle the A overload inf NOTE 2: The APN le	r, su APN orma vel c	pporting the APN level overload information for the maximur level overload information for the first 10 APNs and ignore a ation. overload information, provided within and across different ins of Information" IE(s) shall be limited to 10 different APNs.	n of 10 APNs, shall ny more APN level	

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0
Period of Validity	M	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0
	IE, t	occurrences of APNs are received within one instance of the he receiver shall treat it as a protocol error and ignore the en istance.		irol

Table 7.2.6-2: Overload Control Information within Bearer Resource Failure Indication

7.2.7 Modify Bearer Request

The direction of this message shall be from MME/S4-SGSN to SGW and/or from SGW to PGW (see Table 6.1-1).

The Modify Bearer Request message shall only be sent on the S11 interface by the MME to the SGW and on the S5/S8 interfaces by the SGW to the PGW as part of the procedures:

- E-UTRAN Tracking Area Update without SGW Change
- UE triggered Service Request
- S1-based Handover
- UTRAN Iu mode to E-UTRAN Inter RAT handover
- GERAN A/Gb mode to E-UTRAN Inter RAT handover
- E-UTRAN Initial Attach
- Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN with GTP on S5/S8 interface (see subclauses 8.2, 8.6 and 16.11 of 3GPP TS 23.402 [45])
- UE requested PDN connectivity
- 3G SGSN to MME combined hard handover and SRNS relocation procedure
- X2-based handover without SGW relocation
- UTRAN/GERAN to E-UTRAN SRVCC
- HSS-based P-CSCF restoration for 3GPP access (see 3GPP TS 23.380 [61])
- Connection Resume procedure (see subclause 5.3.5A of 3GPP TS 23.401 [3])
- reception of the RRC establishment cause "MO Exception data" in the NB-IoT RAT

It shall also only be sent on the S11 interface by the MME to the SGW as part of the procedure:

- E-UTRAN Initiated E-RAB modification procedure
- Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN with PMIP on S5/S8 interface (see subclauses 8.2 and 16.11 of 3GPP TS 23.402 [45])
- Tracking Area Update procedure with Serving GW change and data forwarding
- Mobile Originated Data transport in Control Plane CIoT EPS optimisation with P-GW connectivity
- Mobile Terminated Data Transport in Control Plane CIoT EPS optimisation with P-GW connectivity
- Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS optimisation procedure (see subclause 5.3.4B.4 of 3GPP TS 23.401 [3]).

It shall also only be sent on the S4 interface by the SGSN to the SGW and on the S5/S8 interfaces by the SGW to the PGW as part of the procedures:

- Routeing Area Update with MME interaction and without SGW change
- E-UTRAN to UTRAN Iu mode Inter RAT handover
- E-UTRAN to GERAN A/Gb mode Inter RAT handover
- Inter SGSN Routeing Area Update Procedure and Combined Inter SGSN RA / LA Update to S4 SGSNs without SGW change
- Iu mode RA Update Procedure without SGW change
- Serving RNS Relocation Procedure
- Combined Hard Handover and SRNS Relocation Procedure
- Combined Cell / URA Update and SRNS Relocation Procedure
- Enhanced Serving RNS Relocation without SGW relocation
- UE Initiated Service Request Procedure
- Iu mode to A/Gb mode Intra SGSN Change
- A/Gb mode to Iu mode Intra SGSN Change
- Iu mode to A/Gb mode Inter-SGSN Change
- A/Gb mode to Iu mode Inter-SGSN Change
- Paging Response with no established user plane on S4
- PDP Context Activation Procedure
- Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN with GTP on S5/S8 interface (see sub-clauses 8.2, 8.6 and 16.11 of 3GPP TS 23.402 [45])
- UTRAN/GERAN to UTRAN (HSPA) SRVCC
- HSS-based P-CSCF restoration for 3GPP access (see 3GPP TS 23.380 [61])

It shall also only be sent on the S4 interface by the SGSN to the SGW as part of the procedures:

- RAB Assignment Procedure
- SRVCC from E-UTRAN to UTRAN or GERAN with DTM HO support procedures and SRVCC from UTRAN (HSPA) to UTRAN or GERAN with DTM HO support.
- Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN with PMIP on S5/S8 interface (see sub-clauses 8.2 and 16.11 of 3GPP TS 23.402 [45])

- Routeing Area Update procedure with Serving GW change and data forwarding

and only on the S5/S8 interfaces by the SGW to the PGW as part of the procedures:

- Tracking Area Update procedure with SGW change
- Gn/Gp SGSN to S4 SGSN Routing Area Update
- X2 based handover with SGW relocation
- Gn/Gp SGSN to MME Tracking Area Update
- Enhanced Serving RNS Relocation with SGW relocation
- Routeing Area Update with MME interaction and with SGW change
- Inter SGSN Routeing Area Update Procedure and Combined Inter SGSN RA / LA Update using S4 with SGW change
- Iu mode RA Update Procedure using S4 with SGW change
- Restoration of PDN connections after an SGW failure if the MME/SGSN and PGW support these procedures as specified in 3GPP TS 23.007 [17]
- MME triggered Serving GW relocation
- S4-SGSN triggered Serving GW relocation
- PGW Pause of Charging procedure

and on the S2b interface by the ePDG to the PGW as part of the procedures:

- UE initiated IPsec tunnel update procedure

If the optional network triggered service restoration feature is supported by the MME, SGSN and SGW, then the Modify Bearer Request message shall also be sent as part of the network triggered service restoration procedure with ISR during an intra MME TAU and an intra S4-SGSN RAU procedure for UEs that had ISR active before either the MME or the S4-SGSN has restarted, as specified in 3GPP TS 23.007 [17]:

- on the S11 interface by the MME to the SGW, if the MME detected that the ISR associated S4-SGSN has restarted and UE performs a TAU procedure;
- on the S4 interface by the S4-SGSN to the SGW, if the S4-SGSN detected that the ISR associated MME has restarted and UE performs a RAU procedure.

This message can be used as an implicit resume of the suspended bearers in the SGW and in the PGW (see 3GPP TS 23.216 [43] sections 6.2.2.1 and 6.3.2.1, 3GPP TS 23.272 [21] sections 6.3, 6.5 and 7.4). A Modify Bearer Request used as an implicit resume can contain zero or more IE(s), depending on the conditions of presence of the IEs specified in table 7.2.7-1. The PGW should not consider a Modify Bearer Request with zero IE as an error.

The Modify Bearer Request message may also be sent in the following cases from the S4-SGSN to the SGW/PGW to report a change of Serving Network, User CSG Information or/and UE Time Zone which occured during a previous RAU procedure without SGSN change but which has not been reported yet to the SGW/PGW, or to indicate to the PGW that the UE is available for signalling if the PDN connection is delay tolerant and if there is pending network initiated PDN connection signalling:

- during a Service Request procedure to establish data radio bearers for the corresponding PDP context for a UE in UTRAN with an existing S4-U tunnel;
- when the SGSN receives an uplink LLC PDU for user data or any valid LLC frame serving as a paging response from a UE in GERAN with an existing S4-U tunnel.

The Modify Bearer Request message may also be sent in the following cases from the S4-SGSN to the SGW/PGW to report a change of User Location Information which occured during a previous RAU procedure without SGSN change but which has not been reported yet to the SGW/PGW, if the S4-SGSN is configured to defer the reporting of ULI change until a RAB/user plane is established:

- during a Service Request procedure to establish data radio bearers for the corresponding PDP context for a UE in UTRAN with an existing S4-U tunnel;
- when the SGSN receives an uplink LLC PDU for user data or any valid LLC frame serving as a paging response for a UE in GERAN with an existing S4-U tunnel.
- NOTE 1: the S4-SGSN can alternatively send a Change Notification Request message in the above cases, if no other information which requires the sending of a Modify Bearer Request, needs to be reported to the PGW.

The Modify Bearer Request message may also be sent by the MME to the SGW/PGW to report a change of Serving Network, User Location Information, User CSG Information, UE Time Zone or/and RAT Type, when user data is transported in NAS signalling, for a UE with an existing S11-U tunnel.

When requesting the PGW to pause or unpause charging for a PDN connection, the SGW shall wait for the PGW acknowledgement (i.e. Modify Bearer Response) before sending a new pause or unpause request.

NOTE 2: this ensures that the PGW always act per the most recent SGW request in particular in scenarios where the SGW would need to request the PGW to pause and unpause charging in a row (or vice-versa) and the Modify Bearer Request messages would arrive out of order at the PGW.

Upon receipt of a request from the PGW/PCRF/OCS in a message other than Create Bearer Request and Update Bearer Request to report changes of UE presence in new or modified Presence Reporting Area(s), the MME/S4-SGSN shall immediately send a Modify Bearer Request message or a Change Notification Request message to report to the PGW whether the UE is inside or outside the new or modified Presence Reporting Area(s) or whether the Presence Reporting Area(s) is inactive.

The MME/S4-SGSN shall also send a Modify Bearer Request message or a Change Notification Request message to report any subsequent change of UE presence in the Presence Reporting Area, as specified in 3GPP TS 23.401 [3] and 3GPP TS 23.060 [35].

If the Modify Bearer Request message is sent from the old MME/SGSN as part of Tracking/Routeing Area Update procedure with SGW change and data forwarding as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3], the old MME/SGSN shall only include the Bearer Contexts to be modified IE.

NOTE 3: Since the UE has left the old MME/SGSN, some information related to the UE, e.g. ULI, UE Time Zone, CSG, RAT Type in the old MME/SGSN are not valid any more.

Upon receipt of a Modify Bearer Request message that includes the Presence Reporting Area Information from the MME/S4-SGSN, the SGW shall send a Modify Bearer Request message on the S5/S8 interface if any of the following condition is met:

- ISR is not active;
- ISR is active, and the RAT Type has changed since last reported or the CPRAI flag has been set to 1.

The MME shall increment the "MO Exception data counter" by one each time the MME has received the RRC cause "MO Exception data". The MME may defer sending a Modify Bearer Request message to report a non-zero value for the MO Exception Data Counter based on local configuration.

Table 7.2.7-1: Information Elements in a Modify Bearer Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
ME Identity (MEI)		If an SGW receives this IE from an MME/SGSN during a TAU/RAU/Handover procedure, the SGW shall forward it across the S5/S8 interface to the PGW. The MME/SGSN may include this IE on the S11/S4	MEI	0
		interface if the IMSI is not available. The SGW shall forward it across the S5/S8 interface to the PGW if received. See NOTE 23.		
User Location Information (ULI)	C	The MME/SGSN shall include this IE for the TAU/RAU/Handover procedures if the PGW/PCRF has requested location information change reporting and MME/SGSN support location information change reporting. An MME/SGSN which supports location information change shall include this IE for UE-initiated Service Request and UE initiated Connection Resume procedures if the PGW/PCRF has requested location information change reporting and the UE's location info has changed. See NOTE 5, NOTE 17. The MME shall include the ECGI and/or TAI, or TAI and Macro eNB ID, or Macro eNB ID depending on the Change	ULI (NOTE 15)	0
		Reporting Action provided to the MME. The SGSN shall include either the CGI or SAI or RAI, or CGI/SAI together with RAI in the ULI depending on the Change Reporting Action provided to the SGSN.		
	со	When ISR is active, the MME/SGSN which supports location information change shall include this IE for UE- initiated Service Request procedure, if the PGW/PCRF has requested location information change reporting. This IE shall also be included on the S4/S11 interface for a		
		TAU/RAU/Handover with MME/SGSN change without SGW change procedure, if the level of support (User Location Change Reporting and/or CSG Information Change Reporting) changes. The MME shall include the ECGI and /or TAI in the ULI, the S4-SGSN shall include either the CGI or SAI or RAI, or CGI/SAI together with RAI in the ULI. See NOTE 10.		
	СО	 This IE shall also be included on the S4/S11 interface for a handover procedure with SGW change procedure if the level of support (User Location Change Reporting and/or CSG Information Change Reporting) changes; or 		
	 the target MME/S4-SGSN can not derive the level of support (User Location Change Reporting and/c CSG Information Change Reporting) for the source Gn/Gp SGSN. See NOTE 14. The MME shall include the ECGI and /or TAI in the ULI. 			
	со	the S4-SGSN shall include either the CGI or SAI or RAI, or CGI/SAI together with RAI in the ULI. See NOTE 10. This IE shall also be included on the S11/S4 interface during the following procedures if the MME/SGSN is configured to defer the reporting of ULI change until an E- RAB/RAB/ user plane is established, the ULI has changed during previous mobility procedures i.e. intra MME/S4-		
		SGSN TAU/RAU, and the change has not been reported to the PGW yet: - UE initiated Service Request, TAU or RAU with a request to establish data radio bearers;		
		 when the SGSN receives an uplink LLC PDU for user data or any valid LLC frame serving as a paging response for a UE in GERAN with an existing S4-U tunnel. 		

	his IE shall also be included on the S4/S11 interface for: - a TAU/Handover procedure with an S4-SGSN		
	interaction, if the MME supports location information change reporting;		
	 a RAU/Handover procedure with an MME interaction, if the SGSN supports location information change reporting. 		
S2 C0	he MME shall include the ECGI and TAI in the ULI. The 4-SGSN shall include the RAI and, if available, the GI/SAI information, in the ULI.		
	/hen ISR is not active, the SGW shall include this IE on 5/S8 if it receives the ULI from MME/SGSN.		
	/hen ISR is active, the SGW shall include this IE on 5/S8 if		
	 it receives the ULI from MME/S4-SGSN and the RAT Type has changed since last reported; or 		
	 it receives the ULI from MME/S4-SGSN and the CLII flag has been set to 1. 		
	his IE shall be included on S11/S4 interface during the ollowing procedures:		
	- TAU/RAU/handover if Serving Network is changed.		
	 TAU/RAU when the UE was ISR activated which is indicated by ISRAU flag. 		
	 UE triggered Service Request when UE is ISR activated. 		
Serving Network	 UE initiated Service Request if ISR is not active, but the Serving Network has changed during previous mobility procedures, i.e. intra MME/S4-SGSN TAU/RAU and the change has not been reported to the PGW yet. 	Serving Network	0
	- TAU/RAU procedure as part of the optional network triggered service restoration procedure with ISR, as specified by 3GPP TS 23.007 [17].	(NOTE 15)	0
du the Cł	his IE shall also be included on the S4/S11 interface uring a TAU/RAU/Handover with MME/SGSN change if he source MME/SGSN has set the SNCR bit in the hange to Report Flags IE in the Forward Relocation equest or Context Response message.		
IE Be	his IE shall be included on S5/S8 if the SGW receives this From MME/SGSN and if ISR is not active. his IE shall be included on S5/S8 if the SGW receives this from MME/SGSN and ISR is active and the Modify earer Request message needs to be sent to the PGW as becified in the 3GPP TS 23.401 [3].		
RAT Type C Tr an I-F	his IE shall be sent on the S11 interface for a TAU with n SGSN interaction, UE triggered Service Request or an RAT Handover.	RAT Type	0
MI Ini Tr ch	his IE shall be sent on the S4 interface for a RAU with IME interaction, a RAU with an SGSN change, a UE nitiated Service Request or an I-RAT Handover. his IE shall be sent on the S5/S8 interface if the RAT type hanges.		
TA SC	SGW receives this IE from MME/SGSN during a AU/RAU/Handover with SGW change procedure, the GW shall forward it across S5/S8 interface to PGW. See OTE 10.		

СО	 The IE shall be sent on the S11/S4 interface during the following procedures: an inter MME TAU or inter SGSN RAU when UE was ISR activated which is indicated by ISRAU flag. TAU/RAU procedure as part of optional network triggered service restoration procedure with ISR, as specified by 3GPP TS 23.007 [17]. 	
	If ISR is active, this IE shall also be included on the S11 interface in the S1-U GTP-U tunnel setup procedure during an intra-MME intra-SGW TAU procedure.	

Indication Flags	C This IE shall be included if any one of the applicable flags is set to 1.	Indication	0
	Applicable flags are: - Idle mode Signalling Reduction Activation Indication: This flag shall be set to 1 on S4/S11 interface, if the ISR is established between the MME and the S4 SGSN.		
	 Handover Indication: This flag shall be set to 1 on the S4/S11 and S5/S8 interfaces during a Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN or a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN procedures. 		
	 Direct Tunnel Flag: This flag shall be set to 1 on the S4 interface, if Direct Tunnel is used. 		
	 Change Reporting Support Indication: shall be set to 1 on S4/S11, S5/S8 interfaces, if the SGSN/MME supports location Info Change Reporting and if the SGSN/MME's operator policy permits reporting of location change to the operator of the PGW with which the session is established. This flag should be ignored by SGW if no message is sent on S5/S8. See NOTE 4. 		
	 CSG Change Reporting Support Indication: shall be set to 1 on S4/S11, S5/S8, if the SGSN/MME supports CSG Information Change Reporting and if the SGSN/MME's operator policy permits reporting of the CSG Information change to the operator of the PGW with which the session is established. This flag shall be ignored by SGW if no message is sent on S5/S8. See NOTE 4. 		
	 Change F-TEID support Indication: This flag shall be set to 1 on S4/S11 for an IDLE state UE initiated TAU/RAU procedure to allow the SGW changing the GTP-U F-TEID. 		
	 Propagate BBAI Information Change: The MME/SGSN shall set this flag to 1 on S11/S4 in procedures without MME/SGSN change if the PGW has requested H(e)NB information reporting and the H(e)NB local IP address or UDP port number information from H(e)NB in UE associated S1/lu signalling has changed. (NOTE 8) 		
	The MME/SGSN shall set this flag to 1 on S11/S4 during TAU/RAU/Handover with MME/SGSN change procedures if the PGW has requested H(e)NB information reporting. See 3GPP TS 23.139 [51].		
	 CS to PS SRVCC indication: This flag shall be set to 1 on S4/S11 and on S5/S8 during UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43]. 		
	 Change of Location Information Indication (CLII): This flag shall be set to 1 on S4/S11 interface only when the ISR is active for the UE. This flag shall be set to 1 by the MME/S4-SGSN if the ULI IE is included in the Modify Bearer Request message and the location information has changed since 		

last reported by the MME/S4-SGSN. See NOTE 9
 PDN Pause Support Indication: this flag shall be set to 1 on the S5/S8 interface during the TAU/RAU/handover with SGW relocation procedures if the new SGW supports the PGW Pause of Charging procedure.
 PDN Pause On Indication: this flag shall be set to 1 on the S5/S8 interface if the SGW requests the PGW to pause the charging for the PDN connection as specified in 3GPP TS 23.401 [3]. (NOTE 13).
 PDN Pause Off Indication: this flag shall be set to 1 on the S5/S8 interface if the SGW requests the PGW to unpause the charging for the PDN connection as specified in 3GPP TS 23.401 [3]. (NOTE 13).
- Change of Presence Reporting Area information Indication (CPRAI): this flag shall be set to 1 on the S4/S11 interface if ISR is active for the UE and if the Presence Reporting Area Information IE is included in the Modify Bearer Request message and the Presence Reporting Area information has changed since last reported by the MME/S4- SGSN. See NOTE 9.
 P-CSCF Restoration Indication: this flag shall be set to 1 on the S11/S4 and S5/S8 interfaces, for the IMS PDN connection, if the MME/S4-SGSN has received the indication from the HSS that a P- CSCF restoration is required for this user.
 UE Available for Signalling Indication: this flag shall be set to 1 on S11/S4 by the MME/SGSN during a TAU/RAU or a Service Request procedure for E-UTRAN/UTRAN, or UE initiated Connection Resume procedure for E-UTRAN, or at receipt of an uplink LLC PDU for user data or any valid LLC frame serving as a paging response for GERAN, if the PDN connection is delay tolerant and if there is pending network initiated PDN connection signalling. The SGW shall include this IE on S5/S8 if it receives the flag from the MME/SGSN.
 S11-U Tunnel Flag: this flag shall be set to 1 on the S11 interface if user data is transported in NAS signalling.
 Extended PCO Support Indication: this flag shall be set to 1 on S11 interface by the MME if the UE and the MME support ePCO. This flag shall be set to 1 on S5/S8 interface by the SGW if the SGW support ePCO and the MME has set the flag to 1 over the S11 interface. See NOTE 18.
 NBIFOM Support Indication: this flag shall be set to 1 on S11/S4 during an inter-PLMN mobility procedure for E-UTRAN/UTRAN if the MME/SGSN supports NBIFOM. This flag shall be set to 1 on S5/S8 during an inter- PLMN mobility procedure for E-UTRAN/UTRAN if both the SGW and the MME/SGSN support

103

NBIFOM. See NOTE 19.	
 eNB Change Reporting Support Indication: shall be set to 1 on S11, S5/S8 interfaces, if the MME supports location Info Change Reporting and if the MME's operator policy permits reporting of location change to the operator of the PGW with which the session is being established. See NOTE 21. 	

Sender F-TEID for	С	The new MME/SGSN shall include this IE on the S11 and	F-TEID	0
Control Plane	C	S4 interfaces for a TAU/RAU/ Handover with an		0
		MME/SGSN change and without any SGW change. See		
		NOTE 10.		
		If the SGW receives this IE and if it finds that its value is		
		the same as the earlier received value of this IE for this		
		UE, it should interpret this to mean that the MME/SGSN has not changed.		
		nas not changed.		
		The new SGW shall include this IE on the S5 and S8		
		interfaces for a TAU/RAU/Handover with a SGW change.		
		See NOTE 10.		
		If the PGW receives this IE and if it finds that its value is		
		the same as the earlier received value of this IE for this PDN connection, it should interpret this to mean that the		
		SGW has not changed.		
Aggregate Maximum	С	The APN-AMBR shall be sent for TAU/RAU/Handover from	AMBR	0
Bit Rate (APN-AMBR)	-	the Gn/Gp SGSN to the S4 SGSN/MME procedures.		_
Delay Downlink	С	his IE shall be sent on the S11 interface for a UE triggered	Delay Value	0
Packet Notification		Service Request and UE initiated Connection Resume		
Request		procedures. It shall contain the delay the SGW shall apply		
		between receiving downlink data and sending Downlink Data Notification for all UEs served by that MME (see		
		subclause 5.3.4.2 of 3GPP TS 23.401 [3]).		
	CO	This IE shall be sent on the S4 interface for a UE triggered		
		Service Request. It shall contain the delay the SGW shall		
		apply between receiving downlink data and sending		
		Downlink Data Notification for all UEs served by that		
		SGSN (see subclause 5.3.4.2 of 3GPP TS 23.401 [3]).		
Bearer Contexts to be	С	This IE shall be sent on the S4/S11 interface and S5/S8	Bearer Context	0
modified		interface, except - on the S5/S8 interface for a UE triggered Service		
		Request and UE initiated Connection Resume		
		procedures.		
		- on the S5/S8 interface for a TAU/RAU/HO without		
		SGW change procedure. See NOTE 10		
		- on the S5/S8 interface when requesting the PGW		
		to pause or unpause charging for the PDN connection.		
		 on the S5/S8 interface for any other procedure 		
		without SGW change which requires to send a		
		Modify Bearer Request to the PGW, e.g. HSS-		
		based P-CSCF restoration for 3GPP access,		
		reporting of UE presence in a Presence Reporting		
		Area, implicit resume of suspended bearers.		
		(see NOTE 6). When Handover Indication flag is set to 1 (i.e., for a		
		Handover from Trusted or Untrusted Non-3GPP IP Access		
		to E-UTRAN or a Handover from Trusted or Untrusted		
		Non-3GPP IP Access to UTRAN/GERAN procedures), the		
		PGW shall ignore this IE. See NOTE 1.		
		Several IEs with the same type and instance value may be		
		included as necessary to represent a list of Bearers to be		
		modified. During a TAU/RAU/Handover procedure with an SGW		
		change, the SGW includes all bearers it received from the		
		MME/SGSN (Bearer Contexts to be created, or Bearer		
		Contexts to be modified and also Bearer Contexts to be		
		removed) into the list of 'Bearer Contexts to be modified'		
		IEs, which are then sent on the S5/S8 interface to the		
		PGW (see NOTE 2, see NOTE 10).		
		During an E-LITRAN Initiated E PAR modification		
		During an E-UTRAN Initiated E-RAB modification procedure the MME shall send a Modify Bearer Request,		
		including all the bearers (those modified and those not		
		modified), per PDN connection for which at least one		
		bearer has changed. See NOTE 11.		

Bearer Contexts to be removed	С	This IE shall be included on the S4 and S11 interfaces for the TAU/RAU/Handover, UE initiated Connection Resume and Service Request procedures where any of the bearers existing before the TAU/RAU/Handover procedure, UE initiated Connection Resume and Service Request procedures will be deactivated as consequence of the TAU/RAU/Handover procedure, UE initiated Connection Resume and Service Request procedures. See NOTE 3 and NOTE 6. For each of those bearers, an IE with the same type and instance value, shall be included.	Bearer Context	1
Recovery	С	See NOTE 11. This IE shall be included if contacting the peer for the first time	Recovery	0
UE Time Zone	СО	This IE shall be included by the MME/SGSN on the S11/S4 interfaces if the UE Time Zone has changed in the case of TAU/RAU/Handover or UE initiated Service Request	UE Time Zone	0
		procedure. See NOTE 5. This IE shall also be included on the S4/S11 interface during a TAU/RAU/Handover with MME/SGSN change if the source MME/SGSN has set the TZCR bit in the Change to Report Flags IE in the Forward Relocation Request or Context Response message. If SGW receives this IE, SGW shall forward it to PGW across S5/S8 interface.		
MME-FQ-CSID	С	This IE shall be included by MME on S11 and shall be forwarded by SGW on S5/S8 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by SGW on S5/S8 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
User CSG Information (UCI)		The MME/SGSN shall include this IE for Handover procedures, UE initiated Connection Resume and UE- initiated Service Request procedure if the PGW/PCRF has requested CSG Info reporting and the MME/SGSN support the CSG information reporting and the User CSG information has changed (i.e. the UE is accessed via a new CSG cell or hybrid cell or leaves a CSG or hybrid cell). In TAU/RAU procedure without SGW change, this IE shall also be sent if the PGW/PCRF has requested CSG info reporting and MME/SGSN supports CSG info reporting and the User CSG information has changed (i.e. the UE is accessed via a new CSG cell or hybrid cell or leaves a CSG or hybrid cell) when UE requested to activate E-RAB for all the active EPS bearers in TAU procedure or to keep the lu connection after the completion of the RAU procedure. See NOTE 5. See NOTE 10. See NOTE 16. The SGW shall include this IE on S5/S8 if it receives the User CSG Information from MME/SGSN. See NOTE 15.	UCI	0
UE Local IP Address	СО	If the UE local IP Address has changed, the ePDG shall include this IE on S2b interface based on local policy for Fixed Broadband access network interworking (see 3GPP TS 23.139 [51]).	IP Address	1
UE UDP Port	CO	The ePDG shall include this IE on S2b interface if NAT is detected and UE Local IP Address is present for Fixed Broadband access network interworking (see 3GPP TS 23.139 [51]).	Port Number	1
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME to the SGW on the S11 interface and by the SGSN to the SGW on the S4 interface (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	0
SGW LDN	0	This IE is optionally sent by the SGW to the PGW on the S5/S8 interfaces (see 3GPP TS 32.423 [44]), for inter-SGW mobity, when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	1

H(e)NB Local IP Address	CO The MME/SGSN shall include this IE on S11/S4 interface if the PGW/PCRF has requested H(e)NB information reporting and the MME/SGSN has received this	IP Address	0
	information from H(e)NB in UE associated S1/lu signalling (see 3GPP TS 23.139 [51]).		
	The SGW shall forward this IE on S5/S8 interface if it is received from the MME/SGSN and - the Modify Bearer Request message needs to be		
	 sent to the PGW as specified in the 3GPP TS 23.401 [3]; or the Propagate BBAI information change flag is 		
	received from the MME/SGSN.		
H(e)NB UDP Port	(NOTE 7) CO The MME/SGSN shall include this IE on S11/S4 interface if the PGW/PCRF has requested H(e)NB information reporting and the MME/SGSN has received this information from H(e)NB in UE associated S1/Iu signalling (see 3GPP TS 23.139 [51]).	Port Number	0
	 The SGW shall forward this IE on S5/S8 interface if it is received from the MME/SGSN and the Modify Bearer Request message needs to be sent to the PGW as specified in the 3GPP TS 23.401 [3]; or the Propagate BBAI information change flag is received from the MME/SGSN. 		
	(NOTE 7)		
	CO If the PGW triggered SGW restoration procedure is supported, the MME/S4-SGSN shall include this IE on S11/S4 interface and the SGW shall forward this IE on S5 interface in the existing signalling as specified in 3GPP TS 23.007 [17].		
MME/S4-SGSN Identifier	If the overload control feature is supported by the MME/S4- SGSN and is activated for the PLMN to which the PGW belongs(see subclause 12.3.11), the MME/S4-SGSN shall include this IE on the S11/S4 interface during mobility procedures with MME/S4-SGSN change.	IP Address	2
	CO If the overload control feature is supported by the SGW and if the currently serving MME/S4-SGSN has provided this IE (in this message or in earlier message), the SGW shall include this IE on the S5/S8 interface and shall set it to the last received value of the serving MME/S4-SGSN identity.		
	CO In shared networks, the SGSN shall include this IE on the S4 interface for the RAU procedure, if the information is available, and if the Serving Network IE is present in the		
CN Operator Selection Entity	message or if the CN Operator Selection Entity has changed, to indicate whether the Serving Network has been selected by the UE or by the network.	CN Operator Selection Entity	0
	CO The SGW shall include this IE on S5/S8 if it receives it from the SGSN.		

Presence Reporting Area Information	CO The MME/SGSN shall include this IE:	Presence Reporting Area	0
	 if the PGW/PCRF/OCS has just requested to start or modify reporting changes of UE presence in a Presence Reporting Area and the MME/SGSN supports such reporting. The MME/SGSN shall then indicate whether the UE is inside or outside the newly started or modified Presence Reporting Area(s), or indicate the Presence Reporting Area(s) is inactive. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Information. One IE shall be included for each Presence Reporting Area newly started or modified. 	Reporting Area Information	
	The MME/SGSN shall also include this IE in the following procedures, if the PGW/PCRF requested to report changes of UE presence in a Presence Reporting Area and the MME/SGSN supports such reporting:		
	- TAU/RAU/Handover procedures without SGW change and with MME/SGSN change. The MME/SGSN shall then indicate whether the UE is inside or outside the Presence Reporting Area(s) for each of the active Presence Reporting Area(s), or indicate that the Presence Reporting Area(s) is inactive. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Information.		
	- TAU/RAU/Handover/Cell Update procedures without MME/SGSN change, UE initiated Connection Resume and UE-initiated Service Request procedure if the UE enters or leaves the Presence Reporting Area(s). Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Information. One IE shall be included for each active Presence Reporting Area that the UE has newly entered or left. See NOTE 5, NOTE 10.		
	- UE initiated Service Request, if ISR is active;		
	See NOTE 22. CO When ISR is not active, the SGW shall include this IE(s) on S5/S8 if it receives the Presence Reporting Area Information from MME/SGSN.		
	When ISR is active, the SGW shall include this IE(s) on S5/S8 if it receives the Presence Reporting Area Information from MME/S4-SGSN and - the RAT Type has changed since last reported; or		
	- the CPRAI flag has been set to 1.		
MME/S4-SGSN's Overload Control Information	O During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control	0
	 When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. CO If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8 interface. 	momation	

SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	1
	0	During an overload condition, the ePDG may include this		
ePDG's Overload Control Information		IE over the S2b interface if the overload control feature is supported by the ePDG and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control Information	2
		When present, the ePDG shall provide only one instance of this IE, representing its overload information.		
Serving PLMN Rate Control	со	The MME shall include this IE on the S11 interface if the Serving PLMN Rate is changed.	Serving PLMN Rate Control	0
		The target MME shall also include this IE on the S11 interface during an Inter-MME mobility procedure if the Serving PLMN Rate control is configured, and if the configured value is different from the one received from the old MME.		
		See NOTE 20.		
		The SGW shall include this IE on S5/S8 if it receives this IE from MME via the Create Session Request or the Modify Bearer Request message.		
MO Exception Data Counter	СО	The MME shall include this IE on the S11 interface when it needs to send a non-zero counter value for the MO Exception Data Counter. The timestamp in the counter shall be set with the time at which the counter value increased from 0 to 1.	Counter	0
		The SGW shall include this IE on S5/S8 if it has received the counter from the MME.		
IMSI		The MME/SGSN may include the IMSI if available. See NOTE 23.	IMSI	0
User Location Information for SGW	co	The MME/SGSN shall include this IE on the S11/S4 interface, based on operator policy for the User Location Information to be sent to the SGW, if the user location information to be passed to the SGW is not already reported in the ULI IE in this message. When present, this IE shall include the ECGI, TAI, eNodeB	ULI	1
		ID, RAI and/or RNC-ID, based on local policy. See NOTE 25.		
Private Extension	0		Private Extension	VS

- NOTE1: This requirement is introduced for backwards compatibility reasons. If Bearer Contexts to be modified IE(s) is received in the Modify Bearer Request message, the PGW shall include corresponding Bearer Contexts modified IE(s) in the Modify Bearer Response message.
- NOTE2: According to the description in 3GPP TS 23.401 [3] e.g. subclause 5.3.3.1 "Tracking Area Update procedure with Serving GW change" and 3GPP TS 23.060 [35], during a TAU/RAU/Handover procedure with an SGW change, if the SGW receives 'Bearer Context to be removed' IEs, the SGW shall allocate the S5/8-U SGW F-TEID for those bearers and include also these bearers in the 'Bearer contexts to be modified' IE, which is then sent within this message on the S5/S8 interface to the PGW.
- NOTE3: The 'Bearer Contexts to be removed' IE signals to the SGW that these bearers will be removed by the MME/SGSN later on by separate procedures (e.g. MME/S4-SGSN initiated Dedicated Bearer Deactivation procedure). Therefore, the SGW will not delete these bearers during the ongoing TAU/RAU/Handover procedure (without an SGW change), a Handover procedure (with an SGW change except for an X2-Handover), an UE initiated Connection Resume and a Service Request procedure.
- NOTE 4: 3GPP TS 23.401 [3] (e.g. subclause 5.3.2.1) and 3GPP TS 23.060 [35] (e.g. subclause 9.2.2.1) defines the MME/SGSN shall send the MS Info Change Reporting Support Indication to the PGW. In such case MME/SGSN shall use the Change Reporting Support Indication and/or CSG Change Reporting Support Indication (whichever is applicable), even if stage 2 refers to MS Info Change Reporting Support Indication.
- NOTE 5: In TAU/RAU procedure, if the UE requested to activate E-RAB for all the active EPS bearers in TAU procedure or to keep the lu connection after the completion of the RAU procedure, the User Location Info/User CSG Information/UE Time Zone/Presence Reporting Area Information shall not be sent in S1-U GTP-U tunnel setup procedure during the TAU procedure when the "active flag" is set (see 3GPP TS 24.301 [23] and 3GPP TS 23.401 [3]) or in the Service Request procedure after the completion of the RAU procedure.
- NOTE 6: 3GPP TS 23.401 [3] specifies that the target MME/SGSN (for a handover with MME/SGSN change and with or without SGW change) and the MME/SGSN (for a handover without MME/SGSN change and with SGW change) shall send the Modify Bearer Request message to the SGW in the S1 based handover/ Inter RAT handover for an unaccepted PDN Connection when at least one PDN Connection of the UE was accepted by the RAN. In this case, the (target) MME shall indicate the reserved IP address to the SGW in the S1 eNodeB F-TEID and the (target) SGSN shall indicate the reserved IP address to the SGW in the S12 RNC F-TEID for all the non GBR bearers of the unaccepted PDN Connection in the Bearer Contexts to be modified IE. An implementation may provide the mentioned reserved IP address e.g. from one of the reserved IP address ranges (see RFC5735 or http://www.iana.net/assignments/ipv4-address-space/ipv4-address-space.xml), or the IP address may be provisioned by a configuration. The (target) MME/SGSN shall indicate all the GBR bearers of the unaccepted PDN connection in the Bearer Contexts to be removed IE.
- NOTE 7: This IE is sent on S11/S4 in the specified conditions regardless of whether the H(e)NB local IP address and UDP port number information has changed or not to enable the SGW to propagate this IE in Modify Bearer Request over S5/S8 when required for reasons other than reporting a change in the H(e)NB local IP address and UDP port number information.
- NOTE 8: H(e)NB local IP address and UDP port number information changes when the UE moves from an (e)NB to an H(e)NB, or from one H(e)NB to another H(e)NB with a change in the fixed network backhaul, or from one H(e)NB to a (e)NB.
 The SGW shall send a Modify Bearer Request on S5/S8 if any of the following condition is met:

 a) the Propagate BBAI Information Change flag is received from the MME/SGSN;
 b) ISR is active and the RAT type has changed.
- NOTE 9: When ISR is active, the CLII and CPRAI flags allow the SGW to avoid sending Modify Bearer Request message over S5/S8 interface during UE-initiated Service Request procedure, when the ULI IE and/or the Presence Reporting Area Information IE is included over S11/S4 Modify Bearer Request message but the location information and/or the Presence Reporting Area information and the RAT Type has not changed since last reported by the SGW.
- NOTE 10: The RAU/TAU/Handover procedure which requires an SGW selection for the first time, e.g. a Gn/Gp SGSN to an S4 SGSN/MME RAU/TAU/Handover procedure, shall be handled in a similar manner to the RAU/TAU/Handover with an SGW change procedure.
- NOTE 11: The Bearer Context to be modified IE and Bearer Context to be removed IE, together, shall contain all the bearers belonging to the given PDN connection with each bearer appearing in only one of these IEs. See subclause 14 for the cases when a Bearer Context mismatch is detected.
- NOTE 12: The conditions of presence of the IEs in the Modify Bearer Request for the MME and S4-SGSN triggered Serving GW relocation (see subclause 5.10.4 of 3GPP TS 23.401 [3] and subclause 9.2.2.4 of 3GPP TS 23.060 [35]) are identical to those specified respectively for X2 handover with SGW relocation and for Enhanced Serving RNS Relocation with SGW relocation.
- NOTE 13: If this flag is set in the message, the PGW shall not interpret the absence of other IEs (e.g. MME-FQ-CSID, H(e)NB Local IP Address) as bearing any significance. The message may contain either the PDN Pause On Indication or the PDN Pause Off Indication, not both.

- NOTE 14: During the TAU/RAU/Handover from Gn/Gp SGSN, the target MME/S4-SGSN can not derive the level of support for User Location Change Reporting and/or CSG Information Change Reporting at the source Gn/Gp SGSN.
- NOTE 15: In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID.

In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in SAI/CGI to the PGW, for both supporting and non-supporting UEs. The Core Network Operator PLMN ID (selected by the UE for supporting UEs or allocated by the network for non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network. See subclause 4.4 of 3GPP TS 23.251 [55].

NOTE 16: If the UE initiates a TAU or RAU procedure back to the old MME/old S4 SGSN before completing the ongoing TAU or RAU procedure and the UE is not accessed via a CSG cell or hybrid cell, the old MME/old S4-SGSN shall treat this case as the UE leaves a CSG or hybrid cell.

NOTE 17: The MME/S4-SGSN may be configured to defer the reporting of ULI change until an E-RAB, RAB or user plane is established. In that case, the MME/S4-SGSN shall not send a Modify Bearer Request, unless this is required for other reasons, during TAU/RAU without MME/SGSN change or Service Request (for UTRAN) procedures not requesting to activate data radio bearer(s). For GERAN, the SGSN shall defer the reporting of ULI changes, if so configured in the SGSN, until receipt of an uplink LLC PDU for user data or any valid LLC frame serving as a paging response. The MME/S4-SGSN shall report ULI changes as soon as detected if it is not configured to defer the reporting of ULI changes until an E-RAB, RAB or user plane is established, or if an E-RAB, RAB or user plane is established.

- NOTE 18: During an Inter-MME/SGSN and Intra-SGW mobility procedure, if the SGW detects that the support of ePCO has changed, e.g. when the source MME supports ePCO while the target MME does not support it, the SGW shall trigger a Modify Bearer Request without setting the EPCOSI flag if the Modify Bearer Request message is not sent due to other reasons. The PGW shall interpret that ePCO is not supported for this PDN Connection.
- NOTE 19: The MME/SGSN or SGW reporting this indication to the PGW during an inter-PLMN procedure does not trigger any extra signalling.
- NOTE 20: The MME can set the Control Plane Only Indication only during a PDN connection creation procedure, and the Serving PLMN Rate Control is only applicable to the PDN connection with Control Plane Only Indication set.

During an inter MME without SGW relocation procedure, when the source MME has not set the Control Plane Only Indication, and the target MME supports only the Control Plane CloT Optimizations, then the target MME shall not include the Serving PLMN Rate Control IE as the PDN connection cannot be changed to Control Plane Only.

During an inter MME without SGW relocation procedure, when the source MME has set the Control Plane Only Indication and included Serving PLMN rate control IE in the Context Response message, and the target MME supports both the Control Plane CloT Optimisation and the establishment of the User Plane, the target MME cannot stop the Serving PLMN Rate Control, i.e. the PGW will continue to enforce Serving PLMN Rate Control as the Control Plane Only Indication for this PDN connection cannot be changed during this mobility procedure.

- NOTE 21: An MME which supports eNB Change Reporting shall also support Change reporting and therefore shall set both the Change Report Supporting indication and the eNB Changing Reporting Support Indication.
- NOTE 22: Upon inter MME/SGSN mobility, the target MME/SGSN shall report Presence Reporting Area Information for all the active and inactive PRAs requested by the PGW. Upon intra MME/SGSN mobility, the MME/SGSN shall only report active PRAs whose Presence Reporting Area Information is changed, e.g. from inside to outside, or vice versa.
- NOTE 23: The PGW may use the IMSI or the MEI to verify if the Modify Bearer Request message is received for the right UE context. In some error scenarios, e.g. when a delete bearer request (to delete a PDN connection) is lost over S5/S8, the PGW can receive the Modify Bearer Request message for the hanging PDN connection from the MME/SGSN and SGW, if the PGW has reassigned the F-TEID of the hanging PDN connection for another UE.
- NOTE 24: The eNB Change Reporting feature should be supported homogeneously across all MMEs in the network. Otherwise the PGW would not be notified about the change of support of eNB Change Reporting when the UE moves from an MME supporting eNB Change Reporting to an MME that does not support eNB Change Reporting.
- NOTE 25: This information is used for the SGW-U selection (see Annex B.2 of 3GPP TS 29.244 [x]).

Table 7.2.7-2: Bearer Context to be modified within Modify Bearer Request

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements	NA			0
EPS Bearer ID	M	See NOTE 1, NOTE 2.	EBI	0
S1 eNodeB F-TEID	С	This IE shall be sent on the S11 interface if the S1-U is	F-TEID	0
		being used: - for an E-UTRAN initial attach;		
		 for a Handover from Trusted or Untrusted Non- 3GPP IP Access to E-UTRAN; 		
		- for an UE triggered Service Request;		
		- for an UE initiated Connection Resume procedure;		
		 in all S1-U GTP-U tunnel setup procedure during a TAU procedure (see 3GPP TS 24.301 [23]) /handover cases; 		
		 in all procedures where the UE is already in ECM- CONNECTED state, e.g. E-UTRAN Initiated E- RAB modification procedure, possibly HSS-based P-CSCF restoration for 3GPP access. See NOTE 4; 		
		 in the Establishment of S1-U bearer during Data Transport in Control Plane CloT EPS optimisation procedure. See NOTE 7. 		
		If an MME is aware that the eNodeB supports both IP address types, the MME shall send both IP addresses within an F-TEID IE. If only one IP address is included, then the SGW shall assume that the eNodeB does not support the other IP address type. See NOTE 2, NOTE 5, NOTE 6.		
S5/8-U SGW F-TEID	С	This IE shall be sent on the S5/S8 interfaces for a Handover or a TAU/RAU with a SGW change.	F-TEID	1
S12 RNC F-TEID	С	If available, this IE shall be included if the message is sent on the S4 interface if S12 interface is being used. If an S4- SGSN is aware that the RNC supports both IP address types, the S4-SGSN shall send both IP addresses within an F-TEID IE. If only one IP address is included, then the SGW shall assume that the RNC does not support the other IP address type. See NOTE 2, NOTE 6.	F-TEID	2
S4-U SGSN F-TEID	С	If available, this IE shall be included if the message is sent on the S4 interface, if S4-U is being used. If an S4-SGSN supports both IP address types, the S4-SGSN shall send both IP addresses within an F-TEID IE. If only one IP address is included, then the SGW shall assume that the S4-SGSN does not support the other IP address type. See , NOTE 6.	F-TEID	3

			· · · ·
S11-U MME F-TEID	CO This IE shall be sent on the S11 interface if S11-U is being	F-TEID	4
	used, i.e. for the following procedures:		
	- Mobile Originated Data transport in Control Plane		
	CIoT EPS optimisation with P-GW connectivity		
	Mobile Terminated Data Transport in Control Plana		
	- Mobile Terminated Data Transport in Control Plane		
	CIoT EPS optimisation with P-GW connectivity		
	- in all procedures where the S11-U tunnel is		
	already established, e.g. when reporting a change		
	of User Location Information.		
	- TAU/RAU with SGW change procedure and data		
	forwarding of DL data buffered in the old SGW		
	(see subclause 5.3.3.1A of 3GPP TS 23.401 [3])		
	for a Control Plane Only PDN connection. See		
	NOTE 6.		
	NOTE 6.		
	This IE may also be sent on the S11 interface, if S11-U is		
	being used, during a E-UTRAN Tracking Area Update		
	without SGW Change, if the MME needs to establish the		
	S11-U tunnel.		
	See NOTE 8.		

NOTE 1: If only EPS Bearer ID IE is included in the Bearer Context to be modified IE during th without SGW change procedure, the SGW shall remove the stored SGSN/RNC/eNot	
userplane F-TEID locally. NOTE 2: When Direct Tunnel is used in 3G, e.g. during a Service Request procedure if the UE	
establish a partial set of radio access bearers and if the SGSN accepts it, or during a	
relocation procedure with some bearer contexts being preserved, the SGSN shall pro	
without S12 RNC F-TEID(s) for these bearer context(s) without corresponding radio a	
being established. The SGW shall be able to handle these bearer context(s). However	
releases this behaviour may not be supported by the SGW and hence for such SGW provide EBI together with S12 RNC F-TEID for each of the bearer context(s) in the B	
be modified IE.	
NOTE 3: It is not possible to establish or release a partial set of radio access bearers in E-UTF	RAN. The MME
shall provide in the Bearer Contexts to be modified IE, for a UE entering or being in C	
state, the EBI together with the S1 eNodeB F-TEID for all the bearers of the PDN cor	nnection affected
by the Modify Bearer Request other than those possibly indicated in the Bearer Cont	ext to be
removed IE.	
NOTE 4: When the PCO-based extension of the HSS based P-CSCF restoration for 3GPP acc	
supported as specified in subclause 5.4.3 of 3GPP TS 23.380 [61], the MME shall sto eNodeB F-TEID(s) of the IMS PDN connection for UEs with an IMS PDN connection	
CONNECTED state, so that the MME can include all the S1 eNodeB F-TEID(s) of the	
connection for such a UE in ECM-CONNECTED state in the Modify Bearer Request	
NOTE 5: When the PCO-based extension of the HSS based P-CSCF restoration for 3GPP acc	
supported as specified in subclause 5.4.3 of 3GPP TS 23.380 [61], the S4-SGSN sha	
RNC F-TEID(s) (if Direct Tunneling is used) for all the bearers of the IMS PDN conne	
corresponding radio access bearers established, for UEs with an IMS PDN connection	
CONNECTED state, so that the S4-SGSN can include all the S4-U SGSN F-TEID(s)	
Tunneling is not used) or S12 RNC F-TEID(s) (if Direct Tunneling is used) for all the IMS PDN connection with corresponding radio access bearers established, for such a	
CONNECTED state in the Modify Bearer Request message.	
NOTE 6: During a TAU/RAU with SGW change procedure and data forwarding of DL data buff	ered in the old
SGW (see subclause 5.3.3.1A of 3GPP TS 23.401 [3]), the old MME/SGSN shall pro	
SGW with the Forwarding F-TEID received in the Context Acknowledge message (or	
Context Acknowledge message when a Gn/Gp SGSN is involved) and encode it as e	
- eNB F-TEID for a PDN connection not established with the CPOPCI flag set to 1 (for	
- S11-U MME F-TEID for a PDN connection established with the CPOPCI flag set to MME), or	1 (for an old
- S12 RNC F-TEID or S4-U SGSN F-TEID (for an old SGSN),	
regardless of the interface type set in the F-TEID received from the new MME/SGSN	. This is to make
the downlink data forwarding appear as a regular downlink data transmission for the	
like a Service Request procedure.	
NOTE 7: In the Establishment of S1-U bearer during Data Transport in Control Plane CloT EP	
procedure (see subclause 5.3.4B.4 of 3GPP TS 23.401 [3]), the MME may send a M	
Request to the SGW, to request the establishment of the S1-U bearers, without send	
Release Access Bearers Request to tear down the S11-U bearers. In this case, the Mencode the bearers being switched from S11-U to S1-U in the Bearer Contexts to be	
the SGW shall release the S11-U bearers upon receipt of the Modify Bearer Request	
establishment of the S1-U bearers.	
NOTE 8: All the SGi PDN connections of a UE in E-UTRAN shall either use S11-U or S1-U be	
point in time. If S11-U is used, the MME shall establish the S11-U bearer of all the U	
connections.	

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
EPS Bearer ID	Μ		EBI	0

Table 7.2.7-3:	Bearer Context to	be removed w	vithin Modify	Bearer Request
----------------	--------------------------	--------------	---------------	----------------

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0
Sequence Number		parameter.	Number	
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0
Metric		parameter.		
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0
		parameter.		
		This IE should be set to "0" if the "Overload Reduction		
		Metric" is null. This IE shall be ignored by the receiver if the		
		"Overload Reduction Metric" is null.		

Table 7.2.7-4: Overload Control Information within Modify Bearer Request

7.2.8 Modify Bearer Response

The Modify Bearer Response message shall be sent on the S11/S4 interfaces by the SGW to the MME/S4-SGSN, on the S5/S8 interfaces by the PGW to the SGW and on the S2b interface by the PGW to the ePDG as part of the procedures listed for the Modify Bearer Request (see subclause 7.2.7).

If the MME has sent the counter for the RRC Cause "MO Exception data" in the Modify Bearer Resquest, the MME shall reset the counter value when receiving the Modify Bearer Response message.

If handling of default bearer fails, then Cause at the message level shall be a failure cause.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Context not found".
- "Service not supported".

Table 7.2.8-1: Information Elements in a Modify Bearer Response

0

Information elements	Ρ	Conditio	on / C	omment	ІЕ Туре	Ins.		
Cause	Μ				Cause	0		
ISISDN	С	This IE shall be included on if it is stored in its UE conte triggered due to TAU/RAU/	ext an	d if this message is	MSISDN	0		
inked EPS Bearer ID	С	This IE shall be sent on S5, Gn/Gp SGSN to the S4 SG default bearer the PGW sel This IE shall also be sent b Gn/Gp SGSN to S4-SGSN/ the default bearer the PGW Connection.	/S8 w SN c lects y SG /MME	when the UE moves from a or MME to identify the for the PDN Connection. W on S11, S4 during E HO procedures to identify	EBI	0		
VPN Restriction	С	This IE denotes the restriction of APN for the APN associated Context. This IE shall be indered and shall be forwarded ove Gn/Gp SGSN to MME/S4-String This IE shall also be included the Gn/Gp SGSN to S4 SG procedures. The target MME or SGSN to Restriction using the APN F	ated v clude r S11 SGSN ed or SN/N detern Restri	with this EPS bearer ad over S5/S8 interfaces, I/S4 interfaces during I handover procedures. a S5/S8 interfaces during IME RAU/TAU mines the Maximum APN iction.	APN Restriction	0		
Protocol Configuration Options PCO)	С	If SGW receives this IE fror S5/S8, the SGW shall forwa during Inter RAT handover GERAN to the E-UTRAN. S	ard P from	CO to MME/S4-SGSN the UTRAN or from the	PCO	0		
Bearer Contexts nodified	С	EPS bearers corresponding modified that were sent in N message. Several IEs with value may be included as n the Bearers which are modi	g to E Modif the s ieces	Bearer Contexts to be y Bearer Request ame type and instance	Bearer Context	0		
Bearer Contexts narked for removal	С	EPS bearers corresponding removed sent in the Modify Shall be included if request Contexts to be removed. For each of those bearers a instance value shall be inclu	Bea mes an IE	rer Request message. sage contained Bearer with the same type and	Bearer Context	1		
Change Reporting	С	This IE shall be included wi the location Change Report or stopped for this subscrib	ith the ting r	e appropriate Action field If nechanism is to be started	Change Reporting Action	0		
SG Information Reporting Action	со	This IE shall be included wi the location CSG Info chan started or stopped for this s	ith the ge re	e appropriate Action field if porting mechanism is to be		0		
I(e)NB Information Reporting	со	interfaces with the appropri information reporting is to b PDN connection in the SGS	ate A be sta SN/M	ction field if H(e)NB irted or stopped for the ME.	H(e)NB Information Reporting	0		
		Charging Gateway Name		When Charging Gateway F configured, the PGW shall interface during SGW reloc from Gn/Gp SGSN to S4-S	include this IE on the cation and when the GSN/MME. See NO	ie S5 UE m DTE 1.	noves	FQDN
		Charging Gateway Address		When Charging Gateway F configured, the PGW shall interface during SGW reloc from Gn/Gp SGSN to S4-S	include this IE on the action and when the	ne S5 UE m	noves	IP Address
'GW-FQ-CSID	С	This IE shall be included by forwarded by SGW on S11 in 3GPP TS 23.007 [17].	/ PG\	N on S5/S8and shall be	FQ-CSID	0		
GW-FQ-CSID	С	This IE shall be included by requirements in 3GPP TS 2	23.00	7 [17].	FQ-CSID	1		
lecovery	С	This IE shall be included if o time.	conta	acting the peer for the first	Recovery	0		
GW LDN	0	This IE is optionally sent by on the S11/S4 interfaces (s when communicating the LI time.	ee 3	GPP TS 32.423 [44]),	Local Distinguished Name (LDN)	0		

'GW LDN	0	This IE is optionally sent by the PGW to the SGW on the S5/S8 interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)Name	1
ndication Flags	CO	 This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: Static IPv4 Address Flag: This flag shall be set to 1 on the S5/S8 interface in the TAU/RAU/Handover with SGW change procedure if the PDP/PDN IPv4 address is static as specified in 3GPP TS 32.251 [8]. See NOTE 3. Static IPv6 Address Flag: This flag shall be set to 1 on the S5/S8 interface in the TAU/RAU/Handover with SGW change procedure if the PDP/PDN IPv6 address is static as specified in 3GPP TS 32.251 [8]. See NOTE 3. PDN Pause Support Indication: this flag shall be set to 1 on the S5/S8 interface during the TAU/RAU/handover with SGW relocation procedures if the PGW supports the PGW Pause of Charging procedure. PDN Pause Enable Indication: this flag shall be set to 1 on the S5/S8 interface during the TAU/RAU/handover with SGW relocation procedures if the PGW enables the new SGW to use the PGW Pause of Charging procedure. PDN Pause Enable Indication: this flag shall be set to 1 on the S5/S8 interface during the TAU/RAU/handover with SGW relocation procedures if the PGW enables the new SGW to use the PGW Pause of Charging procedure for this PDN connection. Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag to 1 on the S1/S4 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S1/S4 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set t	Indication	0
³ resence Reporting Area Action		This IE shall be included on the S5/S8 and S11/S4 interfaces with the appropriate Action field if reporting changes of UE presence in a Presence Routing Area is to be started, stopped or modified for this subscriber in the MME/SGSN. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions One IE shall be included for each Presence Reporting Area to be started, stopped or	Presence Reporting Area Action	0

'GW's node level .oad Control nformation	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing its node level load information, if the load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access network, belongs (see clause 12.2.6). If the SGW receives this IE and if it supports the load	Load Control Information	0
	0	control feature, it shall forward it to the MME/S4-SGSN on		
⁹ GW's APN level load Control nformation	0	the S11/S4 interface. The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.2.6).	Load Control Information	1
		When present, the PGW shall provide one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 5, NOTE 7.		
	СО	If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4- SGSN on the S11/S4 interface.		
GW's node level .oad Control nformation	0	The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6).	Load Control Information	2
		When present, the SGW shall provide only one instance of this IE, representing its node level load information.		
[•] GW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG for non- 3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to		
		maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 6, NOTE 8.		
	CO	If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
GW's Overload	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
PN Connection Charging ID	CO	The PGW shall include this IE on the S5/S8 interface during a TAU/RAU/HO with SGW relocation procedure, if a PDN connection Charging ID has been allocated during the initial Attach or Initial PDN connection establishment	Charging ID	0
Private Extension	0	procedure.	Private Extension	VS
Intate Enteneiten				

- IOTE 1: Both Charging Gateway Name and Charging Gateway Address shall not be included at the same time. When both are available, the operator configures a preferred value.
- JOTE 2: If MME receives the IE, but no NAS message is sent, MME discards the IE.
- IOTE 3: Static IPv4/IPv6 Address Flag is used by SGW to provide dynamic IPv4/v6 address flag information as specified in 3GPP TS 32.251 [8].
- JOTE 4: The conditions of presence of the IEs in the Modify Bearer Response for the MME and S4-SGSN triggered Serving GW relocation (see subclause 5.10.4 of 3GPP TS 23.401 [3] and subclause 9.2.2.4 of 3GPP TS 23.060 [35]) are identical to those specified respectively for X2 handover with SGW relocation and for Enhanced Serving RNS Relocation with SGW relocation.
- IOTE 5: The receiver, not supporting the APN level load control feature, shall ignore all the occurrence(s) of this IE, i.e. "Load Control Information" IE with instance number "1". The receiver, supporting the APN level load control feature and supporting the APN level load information for the maximum of 10 APNs, shall handle the APN level load information for the first 10 APNs and ignore any more APN level load information.
- JOTE 6: The receiver, supporting the APN level overload information for the maximum of 10 APNs, shall handle the APN level overload information for the first 10 APNs and ignore any more APN level overload information.
- JOTE 7: The APN level load information, provided within and across different instances of the "PGW's APN level Load Control Information" IE(s) shall be limited to 10 different APNs.
- JOTE 8: The APN level overload information, provided within and across different instances of the "PGW's Overload Control Information" IE(s) shall be limited to 10 different APNs.
- JOTE 9: The SGW may use the DTCI during a Network Triggered Service Restoration procedure as specified in the subclause 25.2.1 of 3GPP TS 23.007 [17].

Table 7.2.8-2: Bearer Context modified within Modify Bearer Response

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4 Information	Р	Spare and Instance fields Condition / Comment		Inc
elements	Г	Condition / Comment	ІЕ Туре	Ins.
EPS Bearer ID	Μ		EBI	0
Cause	Μ	This IE shall indicate if the bearer handling was successful,	Cause	0
		and if not, gives information on the reason.		_
S1-U SGW F-TEID	С	This IE shall be used on the S11 interface, if the S1 interface is used, i.e. if the S11-U Tunnel flag was not set in the Modify Bearer Request. If the 'Change F-TEID support Indication' flag was set to 1 in the Modify Bearer Request and the SGW needs to change the F-TEID, the SGW shall include the new GTP-U F-TEID value. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value. See NOTE 1	F-TEID	0
S12 SGW F-TEID	С	This IE shall be included on the S4 interface if the S12 interface is being used. If the 'Change F-TEID support Indication' flag was set to 1 in the Modify Bearer Request and the SGW needs to change the F-TEID, the SGW shall include the new GTP-U F-TEID value. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value. See NOTE 1	F-TEID	1
S4-U SGW F-TEID	C	This IE shall be present if used on the S4 interface if the S4-U interface is being used. If the 'Change F-TEID support Indication' flag was set to 1 in the Modify Bearer Request and the SGW needs to change the F-TEID, the SGW shall include the new GTP-U F-TEID value. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value. See NOTE 1	F-TEID	2
Charging ID	С	 This IE shall be present on the S5/S8 interface if this message is triggered due to one of the following procedures: TAU/RAU/HO with SGW relocation TAU/RAU/HO from Gn/Gp SGSN to MME/S4-SGSN 	Charging ID	0
	0	If S5/S8 interface is GTP, this IE may be sent on the S4 interface, in order to support CAMEL charging at the SGSN, for the following procedures: - inter-SGSN RAU/Handover/SRNS Relocation without SGW change. - inter-SGSN Handover/SRNS Relocation with SGW change.		
Bearer Flags	со	Applicable flags are: - PPC (Prohibit Payload Compression): This flag shall be sent on the S5/S8 and the S4 interfaces at S4-SGSN relocation.	Bearer Flags	0
S11-U SGW F-TEID		This IE shall be present on the S11 interface if S11-U is being used, i.e. if the S11-U Tunnel flag was set in the Modify Bearer Request. If the 'Change F-TEID support Indication' flag was set to 1 in the Modify Bearer Request and the SGW needs to change the F-TEID, the SGW shall include the new GTP-U F-TEID value. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value.	F-TEID	3
		use the same F-TEID IP address and TEID values for S1-U,		
Control Plan TEID.The S Request, E- UTRAN, UE Untrusted N procedures. During Han- than the one	ne C GW UTR E Rec Ion-3 Ion-3 dove	n exception, when separate IP address spaces are used for S IoT EPS Optimization, a different IP address and TEID may shall not change its F-TEID for a given interface during the H AN Initial Attach, Handover from Trusted or Untrusted Non-3 quested PDN connectivity, PDP Context Activation, Handover BGPP IP Access to UTRAN/GERAN and E-UTRAN Initiated er and Service Request the target eNodeB/RNC/SGSN may be by the source eNodeB/RNC/SGSN. In order to support su contain both an IPv4 address and an IPv6 address (see also	be used for the S1 ² Handover, Service 3GPP IP Access to er from Trusted or E-RAB modification use a different IP ty toch a scenario, the	1-U F- E- n pe SGW

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Р	Condition / Comment	IE Type	Ins.		
EPS Bearer ID	Μ		EBI	0		
Cause		This IE shall indicate if the bearer handling was successful, and if not, gives information on the reason.	Cause	0		

Table 7.2.8-3: Bearer Context marked for removal within Modify Bearer Response

Table 7.2.8-4: Load Control Information within Modify Bearer Response

Octet 1		Load Control Information IE Type = 181 (decimal)		
Octets 2 and 3	tets 2 and 3 Length = n			
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0
Sequence Number		parameter.	Number	
Load Metric	Μ	See clauses 12.2.5.1.2.2 and 12.2.5.1.2.3 for the description and use of this parameter.	Metric	0
List of APN and Relative Capacity	CO	The IE shall (only) be present in the "PGW's APN level Load Control Information" IE. For indicating the APN level load, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) & its respective "Relative Capacity" (sharing the same "Load Metric"). See clause 12.2.5.1.2.3 for the description and use of this parameter. See NOTE 1.	APN and Relative Capacity	0
the Load Co	ontro	occurrences of "APN and Relative Capacity" IE are received I Information IE, the receiver shall treat it as a protocol error formation IE instance.		

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0
NOTE 1: If more than 10 occurrences of APNs are received within one instance of the Overload Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control Information IE instance.				

 Table 7.2.8-5: Overload Control Information within Modify Bearer Response

7.2.9 Delete Session Request and Delete Bearer Request

7.2.9.1 Delete Session Request

The direction of this message shall be from MME/S4-SGSN to SGW, from SGW to PGW and from TWAN/ePDG to PGW (see Table 6.1-1).

A Delete Session Request message shall be sent on the S11 interface by the MME to the SGW and on the S5/S8 interface by the SGW to the PGW for a UE having at least one PDN connection through the SGW and PGW, as part of the procedures:

- EUTRAN Initial Attach
- UE, HSS or MME Initiated Detach
- UE or MME Requested PDN Disconnection

It shall also be sent on the S4 interface by the SGSN to the SGW, and on the S5/S8 interface by the SGW to the PGW as part of

- MS, HLR or SGSN initiated detach procedure
- Combined GPRS/IMSI Attach
- MS and SGSN Initiated PDN connection Deactivation Procedure using S4

On the S11 interface by the MME to the SGW as part of the procedures:

- Tracking Area Update with SGW Change
- S1 Based Handover with SGW Change
- X2 Based Handover with SGW Relocation
- E-UTRAN to UTRAN Iu mode Inter RAT handover with SGW change
- E-UTRAN to GERAN A/Gb mode Inter RAT handover with SGW change

- Inter RAT handover cancel with SGW change
- MME to 3G Gn/Gp SGSN combined hard handover and SRNS relocation procedure
- MME to SGSN Routing Area Update
- E-UTRAN to Gn/Gp SGSN Inter RAT handover
- S1 Based handover cancel with SGW change
- Optimised Active Handover: E-UTRAN Access to CDMA2000 HRPD Access
- MME triggered Serving GW relocation

And on the S4 interface by the SGSN to the SGW as part of

- Enhanced Serving RNS Relocation with SGW relocation using S4
- Routing Area Update with SGW change
- SGSN to MME Tracking Area Update with SGW change
- SRNS Relocation Cancel Procedure Using S4
- Inter RAT with SGW change handover cancel
- Serving RNS relocation with SGW change
- UTRAN Iu mode to E-UTRAN Inter RAT handover with SGW change
- GERAN A/Gb mode to E-UTRAN Inter RAT handover with SGW change
- S4 SGSN to Gn/Gp SGSN Routeing Area Update
- S4 SGSN to Gn/Gp SGSN Serving RNS Relocation Procedures
- S4 SGSN to Gn/Gp SGSN PS handover Procedures
- S4-SGSN triggered Serving GW relocation

The message shall also be sent on the S2b interface by the ePDG to the PGW as part of procedures:

- UE/ePDG Initiated Detach with GTP on S2b
- UE Requested PDN Disconnection with GTP on S2b
- HSS/AAA Initiated Detach with GTP on S2b

The message shall also be sent on the S2a interface by the TWAN to the PGW as part of procedures:

- UE/TWAN Initiated Detach and UE/TWAN Requested PDN Disconnection in WLAN on GTP S2a
- HSS/AAA Initiated Detach in WLAN on GTP S2a

This message may also be sent on S5/S8 interface by the SGW to the PGW:

- If Downlink Data Notification Acknowledge message with Context not found cause value is received.

During the detach procedure, if ISR is active and SGW receives a Delete Session Request, the SGW shall deactivate the ISR.

NOTE: The SGW can determine if it is a detach procedure based on e.g. it receives a Delete Session Request message for the last PDN Connection.

When ISR is active, during the Detach procedure the SGW shall forward the Delete Session Request message to the PGW on the S5/S8 interface after receiving both of the messages sent from the MME and the SGSN for the same PDN Connection.

If there are any procedure collisions, the Delete Session Request shall have precedence over any other Tunnel Management message.

During the handover procedure the Delete Session Request message shall not release the indirect data forwarding tunnels.

Possible Cause values are:

- "ISR deactivation ".
- "Network Failure".
- "QoS parameter mismatch".

Table 7.2.9.1-1 specifies the presence of the IEs in the message.

Table 7.2.9.1-1: Information Elements in a Delete Session Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause		If ISR is being de-activated, the Cause IE shall be included on the S4/S11 interface with the value "ISR deactivation", which indicates that the SGW shall delete the bearer resources by sending Delete Bearer Request to the MME/SGSN on which ISR was activated with the same Cause value "ISR deactivation". See NOTE 3	Cause	0
	co	The MME/SGSN shall include this IE if the message is sent due to a network failure as specified in subclause 15.7 of 3GPP TS 23.060 [35] and subclause 5.18 of 3GPP TS 23.401 [3]. It indicates to the PGW the reason of the failure. The SGW shall include this IE on S5/S8 if it receives the		
		Cause from the MME/SGSN.		
Linked EPS Bearer ID (LBI)	С	This IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces to indicate the default bearer associated with the PDN being disconnected unless in the handover/TAU/RAU with SGW relocation procedures.	EBI	0
User Location Information (ULI)	С	The MME/SGSN shall include this IE on the S4/S11 interface for the Detach procedure. The MME shall include ECGI, SGSN shall include CGI/SAI. The SGW shall include this IE on S5/S8 if it receives the ULI from MME/SGSN. See NOTE 4.	ULI (NOTE 7)	0
	CO	The MME/SGSN shall include this IE on the S4/S11 interface for the UE or MME Requested PDN Disconnection procedure/MS and SGSN Initiated PDN connection Deactivation Procedure using S4. The MME shall include ECGI, SGSN shall include CGI/SAI. The SGW shall include this IE on S5/S8 if it receives the ULI from the MME/SGSN.		

Indication Flage	C	This IE shall be included if any one of the applicable flags	Indication	0
Indication Flags	С	is set to 1.	indication	0
		Applicable flags:		
		- Operation Indication: This flag shall be set to 1		
		over S4/S11 interface, if the SGW needs to forward the Delete Session Request message to		
		the PGW. This flag shall not be set if the ISR		
		associated GTP entity sends this message to the		
		SGW in the Detach procedure. This flag shall also not be set to 1 in the SRNS Relocation Cancel		
		Using S4 (6.9.2.2.4a in 3GPP TS 23.060 [4]), Inter		
		RAT handover Cancel procedure with SGW		
		change TAU with Serving GW change, Gn/Gb based RAU (see 5.5.2.5, 5.3.3.1, D.3.5 in 3GPP		
		TS 23.401 [3], respectively), S1 Based handover		
		Cancel procedure with SGW change.		
		This flag shall also not be set to 1 for, e.g., X2		
		based handover procedure with SGW change(see		
		subclause 5.5.1.1.3 in 3GPP TS 23.401 [3]), or S1 based handover procedure with SGW change (see		
		subclause 5.5.1.2.2 in 3GPP TS 23.401 [3]). See		
		NOTE 1.		
		- Scope Indication: This flag shall be set to 1 on the		
		S4/S11 interface, if the request corresponds to		
		TAU/RAU/Handover with SGW change/SRNS Relocation Cancel Using S4 with SGW change,		
		Inter RAT handover Cancel procedure with SGW		
		change, S1 Based handover Cancel procedure		
		with SGW change. See NOTE 1.		
		- Release Over Any Access Indication (ROAAI):		
		This flag shall be set to 1 over the S4/S11 interface when an NB-IFOM capable MME/SGSN		
		wishes to request release of the PDN connection		
		over any applicable access, e.g.:		
		 during a basic P-CSCF restoration procedure; or 		
		- when the MME/SGSN wishes that the PDN		
		connection be reestablished via another PGW		
		for SIPTO.		
		See NOTE 9.		
Protocol		If the UE includes the PCO IE, then the MME/SGSN shall	PCO	0
Configuration Options (PCO)		copy the content of this IE transparently from the PCO IE included by the UE.		
(100)		If SGW receives the PCO IE, SGW shall forward it to		
		PGW.		
	со	For the multi-connection mode, if the TWAN receives the PCO from the UE, the TWAN shall forward the PCO IE to		
		the PGW.		
Originating Node	С	This IE shall be included on the S4/S11 interface if the ISR	Node Type	0
		is active in MME/SGSN to denote the type of the node		
		originating the message. The SGW shall release the corresponding Originating		
		Node related EPS Bearer contexts information in the PDN		
		Connection identified by the LBI.		

Sondor E TEID for		This IE may be included on the \$4/\$11 interfaces execut	F-TEID	0
Sender F-TEID for Control Plane	0	This IE may be included on the S4/S11 interfaces except when the source MME/SGSN initiates the deletion of PDN	F-TEID	0
		connections not supported by the target MME/SGSN		
		during a successful handover/TAU/RAU procedure with		
		MME/SGSN change and without SGW change (see		
		subclauses 5.3.3.2 and 5.5.1.2.1 of 3GPP TS 23.401 [3]),		
		in which case this IE shall not be included. See NOTE 10.		
		If the Sender F-TEID for Control Plane is received by the		
		SGW, the SGW shall only accept the Delete Session		
		Request message when the Sender F-TEID for Control		
		Plane in this message is the same as the Sender F-TEID for Control Plane that was last received in either the Create		
		Session Request message or the Modify Bearer Request		
		message on the given interface.		
		If the ISR is activated, two F-TEIDs exist: one for the MME		
		and the other for the SGSN. See NOTE 2.		
	0	This IE may be included on the S5/S8 and S2a/S2b		
		interfaces.		
		If the Sender F-TEID for Control Plane is received by the		
		PGW, the PGW shall only accept the Delete Session		
		Request message when the Sender F-TEID for Control		
		Plane in this message is the same as the Sender F-TEID		
		for Control Plane that was last received in either the Create Session Request message or the Modify Bearer Request		
		message on the given interface. See NOTE 6.		
	CO	The SGW shall include this IE on the S5/S8 interface if the		
	00	Delete Session Request is sent to clean up a hanging PDN		
		connection context in the PGW, i.e. as a result of receiving		
		a Create Session Request at the SGW colliding with an		
		existing PDN connection context (see subclause 7.2.1).		
UE Time Zone	CO	This IE shall be included by the MME on the S11 interface	UE Time Zone	0
		or by the SGSN on the S4 interface, for Detach and PDN		
		Disconnection procedures, if the UE Time Zone has		
		changed.		
	co	The SGW shall forward this IE on the S5/S8 interface if the		
		SGW receives it from the MME/SGSN, and if the Operation		
	<u> </u>	Indication bit received from the MME/SGSN is set to 1. This IE shall be included by the TWAN on the S2a		
	00	interface.		
ULI Timestamp	co	This IE shall be included on the S4/S11 interface if the ULI	ULI Timestamp	0
		IE is present. It indicates the time when the User Location		
		Information was acquired. The SGW shall include this IE on S5/S8 if the SGW		
		receives it from the MME/SGSN. See NOTE 4.		
RAN/NAS Release	0	The MME shall include this IE on the S11 interface to	RAN/NAS Cause	0
Cause	00	indicate the NAS release cause to release the PDN	INAN/INAO Oduse	U
Cuuco		connection, if available and this information is permitted to		
		be sent to the PGW operator according to MME operator's		
		policy.		
		The SGW shall include this IE on the S5/S8 interface if it		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1.		
	СО	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to		
	со	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN		
	СО	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted		
	СО	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN		
	СО	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8.		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to indicate the release cause to release the PDN connection,		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to		
		The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to indicate the release cause to release the PDN connection, if this information is available and is permitted to be sent to		
	CO	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to indicate the release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the S2b interface to indicate the release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the ePDG operator's policy. When present, the IE shall be encoded as a Diameter or an IKEv2 cause.		
TWAN Identifier	CO	The SGW shall include this IE on the S5/S8 interface if it receives it from the MME and if the Operation Indication bit received from the MME is set to 1. The TWAN shall include this IE on the S2a interface to indicate the TWAN release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the TWAN operator's policy. When present, the IE shall be encoded as a Diameter or an ESM cause. See NOTE 8. The ePDG shall include this IE on the S2b interface to indicate the release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the S2b interface to indicate the release cause to release the PDN connection, if this information is available and is permitted to be sent to the PGW operator according to the ePDG operator's policy. When present, the IE shall be encoded as a	TWAN Identifier	0

TWAN Identifier	0	This IE shall be included by the TWAN on the S2a if the	TWAN Identifier	0
Timestamp	00	TWAN Identifier IE is present. It shall indicate the time	Timestamp	0
Timestamp		when the TWAN acquired the TWAN Identifier information.	Timestamp	
	0	During an overload condition, the MME/S4-SGSN may		
	Ŭ	include this IE on the S11/S4 interface if the overload		
		control feature is supported by the MME/S4-SGSN and is		
		activated for the PLMN to which the PGW belongs (see		
MME/S4-SGSN's		clause 12.3.11).		
Overload Control			Overload Control	0
Information		When present, the MME/S4-SGSN shall provide only one	Information	Ũ
		instance of this IE, representing its overload information.		
	CO	If the SGW receives this IE and if it supports the overload		
		control feature, it shall forward it to the PGW on the S5/S8		
		interface.		
	0	During an overload condition, the SGW may include this IE		
		over the S5/S8 interface if the overload control feature is		
SGW's Overload		supported by the SGW and is activated for the PLMN to	Overload Control	
Control Information		which the PGW belongs (see clause 12.3.11).	Information	1
Control Information			mormation	
		When present, the SGW shall provide only one instance of		
		this IE, representing its overload information.		
	0	During an overload condition, the TWAN/ePDG may		
		include this IE over the S2a/S2b interface if the overload		
TWAN/ePDG's		control feature is supported by the TWAN/ePDG and is		
Overload Control		activated for the PLMN to which the PGW belongs (see	Overload Control	2
Information		clause 12.3.11).	Information	2
monnation				
		When present, the TWAN/ePDG shall provide only one		
		instance of this IE, representing its overload information.		
WLAN Location	co	The ePDG shall include this IE on the S2b interface if the	TWAN Identifier	1
Information	~ ~	WLAN Location Information is available.		-
WLAN Location	co	The ePDG shall include this IE on the S2b interface, if the	TWAN Identifier	1
Timestamp	~~	WLAN Location Timestamp is available.	Timestamp	
UE Local IP Address		The ePDG shall include this IE on the S2b interface.	IP Address	0
UE UDP Port	CO	The ePDG shall include this IE on the S2b interface if NAT	Port Number	0
	~~	is detected and UDP encapsulation is used.	500	
Extended Protocol	co	If the UE includes the ePCO IE, then the MME shall copy	ePCO	0
Configuration Options		the content of this IE transparently from the ePCO IE		
(ePCO)		included by the UE.		
		If the SGW receives the ePCO IE, the SGW shall forward it		
	00	to the PGW. The ePDG shall include this IE on the S2b interface if NAT	Dent Numerie au	4
UE TCP Port			Port Number	1
Drivete Extension		is detected and the TCP encapsulation is used.	Drivete Extension	VC
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b	Private Extension	VS
		interfaces.		

NOTE 1:	For the Indication Flags, the combination (Operation Indication, Scope Indication) = 1,1 shall be
	considered an error if received.
NOTE 2:	Following an inter RAT TAU/RAU failure, the target MME/SGSN may mistakenly initiate the implicit detach procedure while the UE is managed by the other MME/SGSN. In this case, the SGW will reject the Delete Session Request message with the cause "Invalid peer".
NOTE 3:	
NOTE 4:	If ISR is active, after receiving both the Delete Session Request messages from the MME and the SGSN, the SGW shall include the most recent ULI timestamp and the related User Location Information in the Delete Session Request message on S5/S8 interface.
NOTE 5:	The conditions of presence of the IEs in the Delete Session Request for the MME and S4-SGSN triggered Serving GW relocation (see subclause 5.10.4 of 3GPP TS 23.401 [3] and subclause 9.2.2.4 of 3GPP TS 23.060 [35]) are identical to those specified respectively for X2 handover with SGW relocation and for Enhanced Serving RNS Relocation with SGW relocation.
NOTE 6:	In some scenarios, e.g. during an S11/S4 path failure, the old SGW may send a Delete Session Request towards the PGW for a PDN connection which has already been relocated to a new SGW. In this case, the PGW shall reject the Delete Session Request message with the cause "Invalid peer".
NOTE 7:	In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID. In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in the ECGI to the Supporting UEs. The Core Network Operator PLMN ID (selected by the UE for supporting UEs or allocated by the network for non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network. See subclause 4.4 of 3GPP TS 23.251 [55].
NOTE 8:	This IE corresponds to the TWAN Release Cause IE specified in 3GPP TS 23.402 [45].
NOTE 9:	An NB-IFOM capable MME/SGSN remains unaware of whether the PDN connection to be released is associated with multiple accesses or not (i.e. whether this is a NB-IFOM PDN connection).
NOTE 10:	During an inter-MME/SGSN and intra SGW mobility procedure, if the Modify Bearer Request message from the target MME/SGSN arrives at the SGW before the Delete Session Request message from the source MME/SGSN, and if the Sender F-TEID for the Control Plane was included in the Delete Session Request, this would lead the SGW to reject the Delete Session Request message.

Octet 1		Overload Control Information IE Type = 180 (decimal)			
Octets 2 and 3		Length = n			
Octet 4		Spare and Instance fields			
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.	
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0	
Overload Reduction Metric	М	See clause 12.3.5.1.2.3 for the description and use of this parameter.	Metric	0	
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0	

Table 7.2.9.1-2: Overload Control Information within Delete Session Request

7.2.9.2 Delete Bearer Request

The direction of this message shall be from PGW to SGW, from SGW to MME/S4-SGSN and from PGW to TWAN/ePDG (see Table 6.1-1).

A Delete Bearer Request message shall be sent on the S5/S8 and S4/S11 interfaces as part of the following procedures:

- PGW or MME initiated bearer deactivation procedures,
- UE requested Bearer Resource Modification,
- MS and SGSN Initiated Bearer Deactivation procedure using S4 or
- PGW initiated bearer deactivation procedure using S4.

In the above cases, this Request is sent by the PGW to the SGW and shall be forwarded to the MME or S4-SGSN.

The message shall also be sent on the S4/S11 interface by the SGW to the SGSN/MME to delete the bearer resources on the other ISR associated CN node if the ISRAI flag is not set in the Modify Bearer Request/Modify Access Bearers Request message.

The message shall also be sent on the S4/S11 interface by the SGW to the SGSN/MME to delete the bearer resources on the other ISR associated CN node in the TAU/RAU/Handover procedures if the ISR related Cause IE is included in the Delete Session Request message.

The message shall also be sent on the S2b interface by the PGW to the ePDG as part of PGW Initiated Bearer Resource Allocation Deactivation procedure with GTP on S2b.

The message shall also be sent on the S2a interface by the PGW to the TWAN as part of the PGW Initiated Bearer Resource Allocation Deactivation in WLAN on GTP on S2a procedure.

The message may also be sent on the S11/S4 interface by the SGW to the MME/S4 SGSN when the SGW receives the Error Indication from PGW for the default bearer or the ICMP message from a PGW that indicates the UE specific error indication as specified in 3GPP TS 23.007 [17].

The message shall also be sent on the S5/S8 or S2a/S2b interface by the PGW to the SGW or to the TWAN/ePDG and on the S11/S4 interface by the SGW to the MME/S4-SGSN as part of the Network-initiated IP flow mobility procedure, as specified by 3GPP TS 23.161 [71].

If the UE uses NB-IoT, WB-EUTRAN or GERAN Extended Coverage with increased NAS transmission delay (see 3GPP TS 24.301 [23] and 3GPP TS 24.008 [5]), the MME/SGSN should proceed as specified for a UE in ECM-IDLE state with extended idle mode DRX enabled in subclause 5.4.4.1 of 3GPP TS 23.401 [3].

Possible Cause values are:

- "RAT changed from 3GPP to Non-3GPP",
- "ISR deactivation",
- "Access changed from Non-3GPP to 3GPP",
- "Reactivation requested",
- "PDN reconnection to this APN disallowed",
- "PDN connection inactivity timer expires",
- "Local release",
- "Multiple accesses to a PDN connection not allowed".

Table 7.2.9.2-1 specifies the presence of IEs in this message.

Table 7.2.9.2-1: Information Elements in a Delete Bearer Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Linked EPS Bearer ID (LBI)	С	If the request corresponds to the bearer deactivation procedure in case all bearers belonging to a PDN	EBI	0
		connection shall be released, then this IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces to indicate		
		the default bearer associated with the PDN being disconnected.		
		This IE shall be included only when the EPS Bearer ID is		
		not present in the message.		
	со	During a TAU/RAU/HO if the Cause value is set to "ISR deactivation" in the Delete Session Request message, or		
		when this message is used to delete the bearer resources		
		on the other ISR associated CN node if the ISRAI flag is		
		not set in the Modify Bearer Request/Modify Access		
		Bearers Request message, an SGW shall send all LBIs for a given UE with the message on S4/S11 interface. All LBI		
		IEs shall have the same type and instance value to		
	_	represent a list of IEs (see NOTE 1 and NOTE 2).		
EPS Bearer IDs	С	This IE shall be included on S5/S8, S4/S11 and S2a/S2b interfaces for deleting bearers different from the default	EBI	1
		one, i.e. for dedicated bearers. In this case at least one		
		dedicated bearer shall be included.		
		This IE shall be included only when the Linked EPS Bearer		
		ID is not present in the message. Several IEs with this type and instance values shall be		
		included as necessary to represent a list of Bearers.		
Failed Bearer	0	This IE may be included on the S5/S8 and S11 interfaces if	Bearer Context	0
Contexts		the request corresponds to MME initiated bearer deactivation procedure. This IE shall contain the list of		
		failed bearers if partial Bearer Contexts included in the		
		Delete Bearer Command message could not be deleted.		
Procedure	С	If the request corresponds to UE requested bearer	PTI	0
Transaction Id (PTI)		resource modification procedure for an E-UTRAN, this IE shall be included on the S5/S8 and S11 interfaces.		
Protocol	С	The PGW shall include Protocol Configuration Options	PCO	0
Configuration Options		(PCO) IE on the S5/S8 interface, if available and if ePCO		
(PCO)		is not supported by the UE or the network. If SGW receives this IE, SGW shall forward it to		
		SGSN/MME on the S4/S11 interface.		
	CO	For trusted WLAN access, if the default bearer of the PDN		
		connection is being deleted and if the multi-connection		
		mode is used, the PGW may include this IE over the S2a interface to send PCO to the UE.		
PGW-FQ-CSID	С	This IE shall be included by the PGW on the S5/S8 and	FQ-CSID	0
		S2a/S2b interfaces, and when received from S5/S8 be		
		forwarded by the SGW on the S11 interface according to the requirements in 3GPP TS 23.007 [17].		
SGW-FQ-CSID	С	This IE shall be included by the SGW on the S11 interface	FQ-CSID	1
		according to the requirements in 3GPP TS 23.007 [17].		
Cause	С	This IE shall be sent on S5/S8 and S11/S4 interfaces if the	Cause	0
		message is caused by a handover with or without optimization from 3GPP to non-3GPP (see subclause 9.3.2		
		in 3GPP TS 23.402 [45] and subclause 5.4.4.1 in 3GPP TS		
		23.401 [3], respectively). In this case the Cause value shall		
		be set to "RAT changed from 3GPP to Non-3GPP". This IE shall also be sent on S11/S4 interfaces when the		
		SGW requests to delete all bearer contexts for the given		
		UE in an MME or S4-SGSN due to ISR deactivation, and		
		the Cause value shall be set to "ISR deactivation".		
		This IE shall be sent on the S2a/S2b interface if the message is caused by handover from non-3GPP to 3GPP.		
		In this case the Cause value shall be set to "Access		
		changed from Non-3GPP to 3GPP".		

	0	This IE may be sent by a PGW on S5/S8 during PGW		
		initiated bearer deactivation procedures for the default		
		bearer with values of "Reactivation requested" or " PDN		
		reconnection to this APN disallowed" or "Multiple accesses		
		to a PDN connection not allowed" (see section 8.4 for		
		details).		
	0	This IE may be sent by a PGW on S5 during PGW initiated		
	Ŭ	bearer deactivation procedures for the default bearer with		
		values of "PDN connection inactivity timer expires" (see		
		section 8.4 for details).		
	<u> </u>	The IE shall be relayed by the SGW to the MME/S4-SGSN		
	00	if received from the PGW.		
	CO	This IE shall be sent by the PGW on S5/S8 or S2a/S2b		
		with the value "Reactivation requested", when the PGW		
		initiates the bearer deactivation procedure for the default		
		bearer as part of the P-CSCF restoration procedure over		
		3GPP access or WLAN access, as specified in 3GPP TS		
		23.380 [61].		
	0	This IE shall be sent by the PGW on S5/S8 or S2a/S2b		
	0			
		with the value "Local release", when the PGW initiates the		
	1	bearer deactivation procedure, for the default bearer of the		
	1	PDN connection, with local bearer release over one of the		
	1	accesses associated with the NB-IFOM connection. This		
		can be triggered, for example, as part of the P-CSCF		
		restoration procedure specified in 3GPP TS 23.380 [61], or		
		upon receipt by the PGW of a Delete Session Request		
		from an MME/SGSN with the ROAA Indication set to 1.		
		See NOTE 3.		
Indication Flags	CO	This IE shall be included if any one of the applicable flags	Indication	0
		is set to 1.		
		Applicable flags are:		
		 Associate OCI with PGW node's identity: The 		
		PGW shall set this flag to 1 on the S5/S8 interface		
		or S2a/S2b interface if it has included the "PGW's		
		Overload Control Information" and if this		
		information is to be associated with the node		
		identity (i.e. FQDN or the IP address received from		
		the HSS or DNS during the PGW selection) of the		
		serving PGW. The SGW shall set this flag on the		
		S11/S4 interface if it supports the overload control		
	1	feature and if the flag is set on the S5/S8 interface.		
		- Associate OCI with SGW node's identity: The		
	1	SGW shall set this flag to 1 on the S11/S4		
	1	interface if it has included the "SGW's Overload		
	1	Control Information" and if this information is to be		
	1			
	1	associated with the node identity (i.e. FQDN or the		
	1	IP address received from the DNS during the SGW		
	1	selection) of the serving SGW.		
PGW's node level		The PCW may include this IE on the SE/SS or SSe/SSE	Load Control	0
	0	The PGW may include this IE on the S5/S8 or S2a/S2b		0
Load Control	1	interface, providing its node level load information, if the	Information	
Information	1	load control feature is supported by the PGW and is		
	1	activated for the PLMN to which the access network node,		
	1	i.e. MME/S4-SGSN for 3GPP access network,		
	1	ePDG/TWAN for non-3GPP access network, belongs (see		
	L	clause 12.2.6).		
	CO	If the SGW receives this IE and if it supports the load		
	1	control feature, it shall forward it to the MME/S4-SGSN on		
1	1	the S11/S4 interface.	1	1

PGW's APN level Load Control Information 0 The PGW may include this IE on the SS/S8 or S2a/S2b Load Control Information Load Control Information Load Control Information 1 0 The PGW may include this IE on the SS/S8 or S2a/S2b Load Control Information Load Control Information 1 0 The PGW may include this IE on the SS/S8 or S2a/S2b Load Control Information for a list of APN(s). Load Control Information for a list of APN(s). Load Control Information for a list of APN(s). SGW's node level Load Control Information 0 The SGW may include this IE, over the S11/S4 interface. Load Control Information Load Control Information Load Control Information Load Control Information 2 PGW's Overload Control Information 0 The SGW may include this IE, over the SGW and is activated in the network (see clause 12.2.6). Load Control Information Verload Control Information 0 Deveload Control Information 0 PGW's Overload Control Information 0 Deveload Control Information 0 Deveload Control Information 0					
instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 3, NOTE 5. CO If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4- SGSN on the 511/S4 interface. Load Control Information 2 SGW's node level Load Control Information O The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6). Load Control Information 2 PGW's Overload Control Information O During an overload condition, the PGW may include this IE on the SS/S8 or S2a/S2b interface, if the overload control eature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, PDG/TWAN for non-3GPP access based network, PDG/TWAN for non-3GPP access based network, PDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11). Overload Control finite representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 4, NOTE 6. Overload Control Information Overload Control into S11/S4 interface. Overload Control Information Information SGW's Overload Control Information O During an overload condition, the SGW may include this IE Supported by the SGW and is activated on the MME/S4-SGSN on the S11/S4 interface. Overload Control Informatio	Load Control	0	interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network,		1
CO If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4- SGSN on the S11/S4 interface. 2 SGW's node level Load Control Information O The SGW may include this IE, over the S11/S4 interface if the load control leature is supported by the SGW and is activated in the network (see clause 12.2.6). Load Control Information 2 PGW's Overload Control Information O During an overload condition, the PGW may include this IE representing its node level load information. Overload Control Information 0 PGW's Overload Control Information O During an overload condition, the PGW may include this IE representing its overload information. Overload Control Information 0 PGW's Overload Control Information O During an overload condition, the PGW may include this IE representing its overload information. Overload Control Information 0 Vhen present, the PGW may include the same type and instance value, each representing its overload information for a list of APN(s). See NOTE 4, NOTE 6. Overload Control Information 0 SGW's Overload Control Information O During an overload contil information, the SGW may include this IE over the S11/S4 interface. Overload Control Information 1 SGW's Overload Control Information O During an overload contilion, the SGW may include this IE over the S11/S4 interface. Overload Control Information 1			instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s).		
Load Control Information the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6). Information PGW's Overload Control Information O During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control relature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, ePDG/TWAN to non-3GPP access based network, ePDG/TWAN to non-3GPP access based network, ePDG/TWAN to non-3GPP access based network and information. Information When present, the PGW shall provide at least one instance of this IE, representing its overload information. Men present, the SGW shall provide at least one instance of this IE, representing the overload information or a list of APN(s). See NOTE 4, NOTE 6. CO If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface. Overload Control Information SGW's Overload Control Information O During an overload condition, the SGW and is activated in the network (see clause 12.3.11). F-Container 1 NBIFOM Container CO This IE, representing its overload information. F-Container 0 NBIFOM Container CO This IE, shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. F-Containe		со	If the SGW receives this IE and if it supports APN level load control feature, it shall forward it to the MME/S4-		
Itel Tepresenting its node level load information. Overload Control PGW's Overload O During an overload condition, the PGW may include this IE Overload Control 0 Control Information O During an overload condition, the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access based network, belongs (see clause 12.3.11). When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control to providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 4, NOTE 6. Overload Control APN(s). See NOTE 4, NOTE 6. Overload Control APN(s). See NOTE 4, NOTE 6. Overload control of proverlong on overload control the SI1/S4 interface. 1 Information 1 SGW's Overload O During an overload condition, the SGW may include this IE overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11). Verload Control 1 1 NBIFOM Container CO This IE shall be included on the SS/S8 and S2a/S2b interface. F-Container 0 NBIFOM Container CO This IE shall be included on the SS/S8 interface. F-Container 0	Load Control	0	the load control feature is supported by the SGW and is		2
Control Information on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11). Information When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 4, NOTE 6. OVerload Control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface. SGW's Overload O During an overload condition, the SGW may include this IE overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface. Overload Control Information NBIFOM Container CO This IE shall be included on the SS/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPT TS 23.161 [71]. The Container Type shall be set to 4. F-Container 0 NBIFOM Container CO The SGW receives a NBIFOM Container IE from the PGW, the SGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. ePCO 0 Information If the SGW receives this IE, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. EVENthe SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface.			this IE, representing its node level load information.		
of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 4, NOTE 6. CO If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface. Overload Control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface. SGW's Overload O During an overload condition, the SGW may include this IE over the S11/S4 interface. Overload Control feature is supported by the SGW and is activated in the network (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information. F-Container 0 NBIFOM Container CO This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. F-Container 0 Co Tist B SW Shall forward it to the MME/S4-SGSN on the S11/S4 interface. Extended Protocol CO CO The SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. PCO 0 Extended Protocol CO CO The SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. PCO 0 Extended Protocol CO The SGW shall forward it to the S/S8 interface, i		0	on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause		0
COIf the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.Overload ControlSGW's Overload Control InformationODuring an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).Overload Control InformationOverload Control Information1NBIFOM ContainerCOThis IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4.F-Container0COIf the SGW receives a NBIFOM Container IE from the PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface.F-Container0Extended Protocol (ePCO)COThe PGW shall include Extended Protocol Configuration options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO.ePCO0			of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s).		
SGW's Overload Control Information O During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11). Overload Control Information 1 NBIFOM Container CO This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. F-Container 0 Extended Protocol Configuration Options (ePCO) CO The PGW shall include Extended Protocol Configuration of the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface. ePCO 0		со	If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on		
this IE, representing its overload information. NBIFOM Container CO NBIFOM Container CO This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. F-Container 0 CO If the SGW receives a NBIFOM Container IE from the PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. ePCO 0 Extended Protocol Configuration Options (ePCO) CO The PGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. ePCO 0 If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface. If the SGW shall forward it to the MME on the S11 interface.		0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).		1
NBIFOM Container CO This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4. F-Container 0 CO If the SGW receives a NBIFOM Container IE from the PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. F-Container 0 Extended Protocol Configuration Options (ePCO) CO The PGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. ePCO 0 If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface. If the SGW shall forward it to the MME on the S11 interface. ePCO 0					
PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. PGW, the SGW shall forward it to the MME/S4-SGSN on the S11/S4 interface. Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. 0 If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface. If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface.	NBIFOM Container		This IE shall be included on the S5/S8 and S2a/S2b interfaces if the PGW needs to send NBIFOM information as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4.	F-Container	0
Configuration Options (ePCO) Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface.		со	PGW, the SGW shall forward it to the MME/S4-SGSN on		
	Configuration Options		The PGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO.	ePCO	0
	Private Extension	0		Private Extension	VS

NOTE 1:	If the SGW has sent multiple LBIs to MME/SGSN, but have received only one LBI within the Delete
	Bearer Response message, this indicates that the MME/SGSN is pre Rel-10. In such case, the SGW
	shall send separate individual Delete Bearer Request message(s) for each of remaining LBIs.
NOTE 2:	If the SGW has received Delete Session Request with Cause value set to "ISR deactivation" and has
	subsequently sent a Delete Bearer Request to the MME/SGSN with Cause value set to "ISR
	deactivation", then the MME/SGSN shall delete all PDN connections corresponding to all of the LBIs
	received in the Delete Bearer Request message for this UE. The MME/SGSN shall ignore any LBIs
	for which there are no matching PDN connections corresponding to these LBIs.
NOTE 3:	Upon receiving a Delete Bearer Request message for the default bearer of the PDN connection with
	cause "Local release", the MME/SGSN or TWAN/ePDG shall behave as specified in subclause 5.7.3
	of the 3GPP TS 23.380 [61].

NOTE: In the case that the procedure was initiated by a UE Requested Bearer Resource Modification Procedure for an E-UTRAN as specified by 3GPP TS 24.301 [23], then there will be only one instance of the EPS Bearer IDs IE in the Delete Bearer Request.

Table 7.2.9.2-2: Bearer Context within	Delete Bearer Request
--	-----------------------

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
EPS Bearer ID	М		EBI	0
Cause	М	This IE shall indicate the reason of the unsuccessful handling of the bearer.	Cause	0

Table 7.2.9-3: Load Control Information within Delete Bearer Request

Octet 1		Load Control Information IE Type = 181 (decimal)		
Octets 2 and 3	Length = n			
Octet 4	Spare and Instance fields			
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Load Control Sequence Number	М	See clause 12.2.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Load Metric	М	See clauses 12.2.5.1.2.2 and 12.2.5.1.2.3 for the description and use of this parameter.	Metric	0
List of APN and Relative Capacity	CO	The IE shall (only) be present in the "PGW's APN level Load Control Information" IE. For indicating the APN level load, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) & its respective "Relative Capacity" (sharing the same "Load Metric"). See clause 12.2.5.1.2.3 for the description and use of this parameter. See NOTE 1.	APN and Relative Capacity	0
NOTE 1: If more than 10 occurrences of "APN and Relative Capacity" IE are received within one instance of the Load Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Load Control Information IE instance.				

Octet 1	Overload Control Information IE Type = 180 (decimal)			
Octets 2 and 3	Length = n			
Octet 4	Spare and Instance fields			
Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0
NOTE 1: If more than 10 occurrences of APNs are received within one instance of the Overload Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control Information IE instance.				

Table 7.2.9-4: Overload Control Information within Delete Bearer Request

7.2.10 Delete Session Response and Delete Bearer Response

7.2.10.1 Delete Session Response

A Delete Session Response message shall be sent on the S11 interface by the SGW to the MME and on the S5/S8 interface by the PGW to the SGW as part of the following procedures:

- EUTRAN Initial Attach
- UE, HSS or MME Initiated Detach
- UE or MME Requested PDN Disconnection

It shall also be sent on the S4 interface by the SGW to the SGSN and on the S5/S8 interface by the PGW to the SGW as part of the procedures:

- MS, HLR or SGSN initiated detach procedure
- Combined GPRS/IMSI Attach
- MS and SGSN Initiated Default Bearer Deactivation Procedure using S4

On the S11 interface by the SGW to the MME as part of the procedures:

- Tracking Area Update with SGW Change
- S1 Based Handover with SGW Change
- X2 Based Handover with SGW Relocation
- E-UTRAN to UTRAN Iu mode Inter RAT handover with SGW change
- E-UTRAN to GERAN A/Gb mode Inter RAT handover with SGW change
- Inter RAT handover cancel with SGW change
- MME to 3G Gn/Gp SGSN combined hard handover and SRNS relocation procedure

- MME to SGSN Routing Area Update
- E-UTRAN to Gn/Gp SGSN Inter RAT handover
- S1 Based handover cancel with SGW change
- Optimised Active Handover: E-UTRAN Access to CDMA2000 HRPD Access
- MME triggered Serving GW relocation

And on the S4 interface by the SGW to the SGSN as part of the procedures:

- Enhanced Serving RNS Relocation with SGW relocation using S4
- Routing Area Update with SGW change
- SGSN to MME Tracking Area Update with SGW change
- Serving RNS relocation with SGW change
- UTRAN Iu mode to E-UTRAN Inter RAT handover with SGW change
- GERAN A/Gb mode to E-UTRAN Inter RAT handover with SGW change
- S4 SGSN to Gn/Gp SGSN Routeing Area Update
- S4 SGSN to Gn/Gp SGSN Serving RNS Relocation Procedures
- S4 SGSN to Gn/Gp SGSN PS handover Procedures
- S4-SGSN triggered Serving GW relocation

The message shall also be sent on the S2b interface by the PGW to the ePDG as part of procedures:

- UE/ePDG Initiated Detach with GTP on S2b
- UE Requested PDN Disconnection with GTP on S2b
- HSS/AAA Initiated Detach with GTP on S2b

The message shall also be sent on the S2a interface by the PGW to the TWAN as part of procedures:

- UE/TWAN Initiated Detach and UE/TWAN Requested PDN Disconnection in WLAN on GTP S2a
- HSS/AAA Initiated Detach in WLAN on GTP S2a

This message may also be sent on S5/S8 interface by the PGW to the SGW:

- If Downlink Data Notification Acknowledge message with Context not found cause value is received.

The sending entity shall include Cause IE in the Delete Session Response message. The IE indicates if the peer has deleted the bearer, or not.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Context not found".
- "Invalid peer".

Table 7.2.10.1-1 specifies the presence of the IEs in the message.

Table 7.2.10.1-1: Information Elements in a Delete Session Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	С	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0
Protocol Configuration Options (PCO)	C CO	The PGW shall include Protocol Configuration Options (PCO) IE on the S5/S8 interface, if available and if the UE or the network does not support ePCO. If SGW receives this IE, SGW shall forward it to SGSN/MME on the S4/S11 interface. For trusted WLAN access, if the multi-connection mode is	PCO	0
		used, the PGW may include this IE over the S2a interface to send PCO to the UE.		
Indication Flags	co	 This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the SIN SOURD ADD SOURD A	Indication	0
PGW's node level Load Control Information	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing its node level load information, if the load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access network, belongs (see clause 12.2.6). If the SGW receives this IE and if it supports the load	Load Control Information	0
		control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
PGW's APN level Load Control Information	0	The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.2.6).	Load Control Information	1
	со	When present, the PGW shall provide one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 1, NOTE 3. If the SGW receives this IE and if it supports APN level		
		load control feature, it shall forward it to the MME/S4- SGSN on the S11/S4 interface.		
SGW's node level Load Control Information	0	The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6).	Load Control Information	2
		When present, the SGW shall provide only one instance of this IE, representing its node level load information.		

PGW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s).		
		See NOTE 2, NOTE 4. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
Extended Protocol Configuration Options (ePCO)		The PGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO.	ePCO	0
		If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface.		
Private Extension		This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	
NOTE 1: The receiver, not supporting the APN level load control feature, shall ignore all the occurrence(s) of this IE, i.e. "Load Control Information" IE with instance number "1". The receiver, supporting the APN level load control feature and supporting the APN level load information for the maximum of 10 APNs, shall handle the APN level load information for the first 10 APNs and ignore any more APN level load information.				
NOTE 2: The receiver, supporting the APN level overload information for the maximum of 10 APNs, shall handle the APN level overload information for the first 10 APNs and ignore any more APN level overload information.				
NOTE 3: The APN level load information, provided within and across different instances of the "PGW's APN level Load Control Information" IE(s) shall be limited to 10 different APNs.				
NOTE 4: The APN level overload information, provided within and across different instances of the "PGW's Overload Control Information" IE(s) shall be limited to 10 different APNs.				

Octet 1		Load Control Information IE Type = 181 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Load Metric	Μ	See clause 12.2.5.1.2.2 for the description and use of this	Metric	0		
		parameter.				
List of APN and	CO	The IE shall (only) be present in the "PGW's APN level	APN and Relative	0		
Relative Capacity		Load Control Information" IE.	Capacity			
		For indicating the APN level load, the PGW shall include				
		one or more instances of this IE, up to maximum of 10,				
		with the same type and instance value, representing a list				
		of APN(s) & its respective "Relative Capacity" (sharing the				
		same "Load Metric").				
		See clause 12.2.5.1.2.3 for the description and use of this				
		parameter.				
		See NOTE 1.				
		occurrences of "APN and Relative Capacity" IE are received				
the Load Control Information IE, the receiver shall treat it as a protocol error and ignore the entire						
Load Contr	Load Control Information IE instance.					

 Table 7.2.10.1-2: Load Control Information within Delete Session Response

Table 7.2.10.1-3: Overload Control Information within Delete Session Response

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields	Spare and Instance fields			
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the	Metric	0		
Metric		description and use of this parameter.				
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0		
		parameter.				
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				
List of Access Point	CO	The IE may (only) be present in the "PGW's Overload	APN	0		
Name (APN)		Control Information" IE.				
		For indicating the APN level overload, the PGW shall				
		include one or more instances of this IE, up to maximum of				
		10, with the same type and instance value, representing a				
		list of APN(s) (sharing the same "Overload Reduction				
		Metric" and "Period of Validity").				
		See NOTE 1.				
NOTE 1: If more than	10 ·	occurrences of APNs are received within one instance of the	Overload Control			
Information	Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control					
	Information IE instance.					

7.2.10.2 Delete Bearer Response

The Delete Bearer Response shall be sent as a response of Delete Bearer Request.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Context not found".

- "Temporarily rejected due to handover/TAU/RAU procedure in progress".

Table 7.2.10.2-1: Information Elements in Delete Bearer Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	М		Cause	0
Linked EPS Bearer ID (LBI)		If the response corresponds to the bearer deactivation procedure in case all the bearers associated with the default bearer of a PDN connection shall be released, this	EBI	0
		IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces to indicate the default bearer associated with the PDN being disconnected.		
	CO	During a TAU/RAU/HO, if an MME/SGSN has received a Delete Bearer Request message with Cause value "ISR deactivation" and multiple LBIs, the MME/SGSN shall include all these LBIs in the response message on S4/S11 interface. All LBI IEs shall have the same type and		
Bearer Contexts	С	instance value to represent a list of IEs. It shall be used on the S4/S11, S5/S8 and S2a/S2b interfaces for bearers different from default one. In this case at least one bearer shall be included. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers. Used for dedicated bearers. When used, at least one dedicated bearer shall be present. All the bearer contexts included in the EPS Bearer IDs IE of the corresponding Delete Bearer Request shall be included.	Bearer Context	0
Recovery	С	This IE shall be included on the S4/S11, S5/S8 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0
MME-FQ-CSID	С	This IE shall be included by MME the on S11 interface and shall be forwarded by the SGW on S5/S8 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by the SGW on the S5/S8 interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
ePDG-FQ-CSID	С	This IE shall be included by the ePDG on the S2b interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	2
TWAN-FQ-CSID	С	This IE shall be included by the TWAN on the S2a interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	3
Protocol Configuration Options (PCO)		An MME/SGSN shall include the PCO IE if such information was received from the UE. If the SGW receives this IE, the SGW shall forward it to PGW on the S5/S8 interface.	PCO	0
		For the multi-connection mode, if the default bearer of the PDN connection is being deleted and if the TWAN receives the PCO from the UE, the TWAN shall forward the PCO IE to the PGW.		
		This IE shall be included, if available, by the MME on the S11 interface or by the SGSN on the S4 interface. The SGW shall forward this IE on the S5/S8 interface if the		
UE Time Zone		SGW receives it from the MME/SGSN. This IE shall be included by the TWAN on the S2a	UE Time Zone	0
	со	interface. This IE shall be included by the MME on the S11 interface or by the SGSN on the S4 interface. The CGI/SAI shall be included by SGSN and the ECGI shall be included by		
User Location Information (ULI)	со	MME. See NOTE 2. The SGW shall forward this IE on the S5/S8 interface if it receives it from the MME/SGSN. See NOTE 1.	ULI	0
ULI Timestamp	CO	This IE shall be included on the S4/S11 interface if the ULI IE is present. It indicates the time when the User Location Information was acquired. The SGW shall include this IE on S5/S8 if the SGW receives it from the MME/SGSN. See NOTE 1.	ULI Timestamp	0
TWAN Identifier	со	This IE shall be included by the TWAN on the S2a interface as specified in 3GPP TS 23.402 [45].	TWAN Identifier	0

TWAN Identifier	CO	This IE shall be included by the TWAN on the S2a	TWAN Identifier	0
Timestamp		interface if the TWAN Identifier IE is present. It shall	Timestamp	
		indicate the time when the TWAN acquired the TWAN		
	_	Identifier information.		
	0	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload		
		control feature is supported by the MME/S4-SGSN and is		
		activated for the PLMN to which the PGW belongs (see		
MME/S4-SGSN's		clause 12.3.11).		
Overload Control			Overload Control Information	0
Information		When present, the MME/S4-SGSN shall provide only one	mormation	
		instance of this IE, representing its overload information.		
	co	If the SGW receives this IE and if it supports the overload		
		control feature, it shall forward it to the PGW on the S5/S8 interface.		
	0	During an overload condition, the SGW may include this IE		
	Ŭ	over the S5/S8 interface if the overload control feature is		
		supported by the SGW and is activated for the PLMN to		
SGW's Overload		which the PGW belongs (see clause 12.3.11).	Overload Control Information	1
			mormation	
		When present, the SGW shall provide only one instance of		
	00	this IE, representing its overload information.		
	CO	If the overload control feature is supported by the MME/S4- SGSN and is activated for the PLMN to which the PGW		
		belongs (see subclause 12.3.11), the MME/S4-SGSN shall		
		include this IE on the S11/S4 interface when there is at		
MME/S4-SGSN		least one bearer remaining for the given PDN connection		0
Identifier		after the bearer deletion, and the PGW has not been	IP Address	0
		updated with the identity of the currently serving MME/S4-		
		SGSN, i.e. if no other message carrying MME/S4-SGSN		
		identity has been sent to the PGW during/after an inter-		
	0	MME/S4-SGSN intra-SGW mobility procedure. During an overload condition, the TWAN/ePDG may		
	0	include this IE over the S2a/S2b interface if the overload		
		control feature is supported by the TWAN/ePDG and is		
TWAN/ePDG's Overload Control		activated for the PLMN to which the PGW belongs (see	Overload Control	2
Information		clause 12.3.11).	Information	2
Information				
		When present, the TWAN/ePDG shall provide only one		
WLAN Location	<u> </u>	instance of this IE, representing its overload information. The ePDG shall include this IE on the S2b interface if the		
Information	00	WLAN Location Information is available.	TWAN Identifier	1
WLAN Location	CO	The ePDG shall include this IE on the S2b interface, if the	TWAN Identifier	
Timestamp	00	WLAN Location Timestamp is available.	Timestamp	1
UE Local IP Address	CO	The ePDG shall include this IE on the S2b interface.	IP Address	0
UE UDP Port	CO	The ePDG shall include this IE on the S2b interface if NAT	Port Number	0
	_	is detected and UDP encapsulation is used.		
NBIFOM Container	co	This IE shall be included on the S11/S4 or S2a/S2b	F-Container	0
		interfaces if the MME/S4-SGSN or the TWAN/ePDG		
		receives a NBIFOM Container from the UE as specified in 3CPP TS 24 161 731 The Container Type shall be set to 4		
	CO	3GPP TS 24.161 73]. The Container Type shall be set to 4. If the SGW receives a NBIFOM Container IE from the	1	
		MME/S4-SGSN, the SGW shall forward it to the PGW on		
		the S5/S8 interface.		
UE TCP Port	CO	The ePDG shall include this IE on the S2b interface if NAT	Port Number	1
	1	is detected and TCP encapsulation is used.		
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b	Private Extension	VS
	1	interfaces.		

NOTE 1:	If ISR is active, after receiving both the Delete Bearer Response messages from the MME and the SGSN, the SGW shall include the most recent time and the related User Location Information in the
	Delete Bearer Response message on S5/S8 interface.
NOTE 2:	In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID.
	In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary
	PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be
	communicated in SAI/CGI to the PGW, for both supporting and non-supporting UEs. The Core
	Network Operator PLMN ID (selected by the UE for supporting UEs or allocated by the network for
	non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network.
	See subclause 4.4 of 3GPP TS 23.251 [55].

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.		
elements						
EPS Bearer ID	Μ		EBI	0		
Cause	М	This IE shall indicate if the bearer handling was successful,	Cause	0		
		and if not, gives information on the reason.				
Protocol	со	An MME/SGSN shall include the PCO IE if such	PCO	0		
Configuration Options		information was received from the UE.				
(PCO)		If the SGW receives this IE, the SGW shall forward it to				
		PGW on the S5/S8 interface.				
		This bearer level IE takes precedence over the PCO IE in				
244442	~ ~	the message body if they both exist.	5			
RAN/NAS Cause	CO	The MME shall include this IE on the S11 interface to	RAN/NAS Cause	0		
		indicate the RAN release cause and/or NAS release cause				
		to release the bearer, if this information is available and is				
		permitted to be sent to the PGW operator according to the				
		MME operator's policy.				
		If both a RAN release cause and a NAS release cause are				
		generated, then several IEs with the same type and				
		instance value shall be included to represent a list of causes.				
		The SGW shall include this IE on the S5/S8 interface if it				
		receives it from the MME.				
		See NOTE 1.				
		See NOTE 1.				
Extended Protocol	co	An MME shall include the ePCO IE if such information is	ePCO	0		
Configuration Options	00	received from the UE.	erco	0		
(ePCO)						
(01 00)		If the SGW receives this IE, the SGW shall forward it to the				
		PGW on the S5/S8 interface.				
NOTE 1: The MME m	l lav c	lefer the deactivation of GBR bearers for a short period (in th	e order of seconds	.)		
		an S1AP UE Context Release Request due to radio reasons,				
		corresponding radio and S1 bearers and thus avoid the dead				
		IME receives then a Delete Bearer Request while it is still de				
		ommand, the MME shall include in the Delete Bearer Respo				
	Cause IE it would have included in the Delete Bearer Command. See subclauses 5.3.5 and 5.4.4			.4.1		
of 3GPP TS						

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0		
Metric		parameter.				
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0		
		parameter.				
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				

Table 7.2.10.2-3: Overload Control Information within Delete Bearer Response

7.2.11 Downlink Data Notification messages

7.2.11.1 Downlink Data Notification

A Downlink Data Notification message shall be sent:

- on the S11 interface by the SGW to the MME as a part of the network triggered service request procedure;
- on the S4 interface by the SGW to the S4-SGSN as part of Paging with no established user plane on S4, SGW triggered paging with S4;
- on the S4 interface by the SGW to the S4-SGSN to re-establish all the previous released bearer(s) for a UE, upon receipt of downlink data for a UE in connected mode but without corresponding downlink bearer available;
- NOTE: This may occur e.g. if the S4-SGSN releases some but not all the bearers of the UE as specified in subclause 12.7.2.2 of 3GPP TS 23.060 [35].
- on S11/S4 interface by SGW to MME/S4-SGSN if the SGW has received an Error Indication (see 3GPP TS 29.281 [13]) from eNodeB/RNC/MME across S1-U/S12/S11-U interface. Respective SGW and MME/S4-SGSN functionality is specified in 3GPP TS 23.007 [17].
- on the S11/S4 interface by SGW to the MME/S4-SGSN as part of the network triggered service restoration procedure if both the SGW and the MME/S4-SGSN support this optional feature (see 3GPP TS 23.007 [17]).
- on the S11 interface by the SGW to the MME as a part of the Mobile Terminated Data Transport in Control Plane CIoT EPS optimisation with P-GW connectivity.

A Downlink Data Notification message may be sent:

- on the S4 by the SGW to the S4-SGSN if the SGW has received an Error Indication from S4-SGSN across S4-U interface.

Table 7.2.11.1-1 specifies the presence of the IEs in the message.

Table 7.2.11.1-1: Information Elements in a Downlink Data Notification

Information elements	Р	Condition / Comment	IE Type	Ins.
Cause EPS Bearer ID		If SGW receives an Error Indication from eNodeB/RNC/S4- SGSN/MME, the SGW shall send the Cause IE with value "Error Indication received from RNC/eNodeB/S4- SGSN/MME" to MME/S4-SGSN as specified in 3GPP TS 23.007 [17]. This IE shall be included on the S11 and S4 interfaces and shall be set as follows: - If the Downlink Data Notification is triggered by the arrival of downlink data packets at the SGW	Cause EBI	0
		 the arrival of downlink data packets at the SGW, the SGW shall include the EPS Bearer ID stored in the EPS bearer context of the bearer on which the downlink data packet was received; If the Downlink Data Notification is triggered by the receipt of an Error Indication from the eNodeB, RNC or S4-SGSN, the SGW shall include the EPS Bearer ID stored in the EPS bearer context of the bearer for which the Error Indication was received; If the ISR is active and the Downlink Data Notification is triggered by the arrival of control plane signalling, the SGW shall include the EPS Bearer ID present in the control plane signalling or derived from the control plane signalling (for PMIP based S5/S8), See NOTE 3). For a Downlink Data Notification triggered by a Create Bearer Request message, the SGW shall include the EPS Bearer ID of the corresponding PDN connection's default bearer. If both the SGW and the MME/S4-SGSN support the network triggered service restoration procedure (see 3GPP TS 23.007 [17]), and if the Downlink Data Notification is triggered by the arrival of control plane signalling, the SGW shall include the EPS Bearer ID present ID present in the control plane is triggered by the arrival of control plane signalling, the SGW shall include the EPS Bearer ID of the corresponding PDN connection's default bearer. 		
		plane signalling or derived from the control plane signaling (for PMIP based S5/S8). (See 3GPP TS 23.401[3], section 5.3.4.3). More than one IE with this type and instance values may be included to represent multiple bearers having received downlink data packets or being signalled in the received control plane message. See NOTE 1.		

Allocation/Datastics	000	This IE shall be included on the S11 and S1 interference and		0
Allocation/Retention Priority	CO	 This IE shall be included on the S11 and S4 interfaces and shall be set as follows: If the Downlink Data Notification is triggered by the arrival of downlink data packets at the SGW, the SGW shall include the ARP stored in the EPS bearer context of the bearer on which the downlink data packet was received; If the Downlink Data Notification is triggered by the receipt of an Error Indication from the eNodeB, RNC or S4-SGSN, the SGW shall include the ARP stored in the EPS bearer context of the bearer for which the Error Indication was received. If the ISR is active and the Downlink Data Notification is triggered by the arrival of control plane signalling, the SGW shall include the ARP if present in the control plane signalling. If the ARP is not present in the control plane signalling, the SGW shall include the ARP in the stored EPS bearer context. See NOTE 3. If both the SGW and the MME/S4-SGSN support the network triggered service restoration procedure (see 3GPP TS 23.007 [17]), and if the Downlink Data Notification is triggered by the arrival of control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the control plane signalling. If the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the control plane signalling, the SGW shall include the ARP is not present in the	ARP	0
IMSI		See NOTE 1. This IE shall be included on the S11/S4 interface as part of the network triggered service restoration procedure if both the SGW and the MME/S4-SGSN support this optional feature (see 3GPP TS 23.007 [17]).	IMSI	0
Sender F-TEID for Control Plane	0	This IE may be included on the S11/S4 interface towards the restarted CN node or an alternative CN node (same type of mobility node as the failed one) as part of the network triggered service restoration procedure with or without ISR if both the SGW and the MME/S4-SGSN support this optional feature (see 3GPP TS 23.007 [17]). This IE shall not be included otherwise. (NOTE 2)	F-TEID	0
Indication Flags	CO	 This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW. 	Indication	0
SGW's node level Load Control Information		The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6). When present, the SGW shall provide only one instance of this IE, representing its node level load information.	Load Control Information	0

	Overload nformation	0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control Information	0
			When present, the SGW shall provide only one instance of this IE, representing its overload information.		
Paging an Informatio		со	This IE, representing its overload information. This IE shall be included on the S11 and S4 interfaces, for an IP PDN connection, if the SGW supports the Paging Policy Differentiation feature (see subclause 4.9 of 3GPP TS 23.401 [3]) and if the Downlink Data Notification is triggered by the arrival of downlink data packets at the SGW. If the preceding conditions are fulfilled, then for each bearer and for each packet that triggers a Downlink Data Notification, the SGW shall copy, into the Paging Policy Indication value within this IE, the value of the DSCP in TOS (IPv4) or TC (IPv6) information received in the IP payload of the GTP-U packet from the PGW (see IETF RFC 2474 [65]). See NOTE 4. One IE with this type and instance value shall be included per EPS Bearers ID reported in the message,	Paging and Service Information	0
Private Ex	tension	0	See NOTE 1.	Private Extension	VS
		-	s parameter at the S4-SGSN is not specified in this release.		
					that s in
	For PMIP based S5/S8, if the SGW cannot derive the EPS bearer ID/ARP from the control plane signalling (received over Gxx interface) the SGW should use the corresponding PDN connection's (for which the control plane signalling is received) default EPS bearer's EPS bearer ID/ARP. Upon receiving a downlink data packet for a Non-IP PDN connection (see subclause 5.3.1 of 3GPP)			n's	
	TS 23.401 [Notification		he Paging and Service Information shall not be included in t sage.	he Downlink Data	

Octet 1		Load Control Information IE Type = 181 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Ρ	Condition / Comment	IE Type	Ins.		
Load Control Sequence Number	М	See clause 12.2.5.1.2.1 for the description and use of this parameter.	Sequence Number	0		
Load Metric	Μ	See clause 12.2.5.1.2.2 for the description and use of this parameter.	Metric	0		

Octet 1		Overload Control Information IE Type = 180 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information	Ρ	Condition / Comment	IE Type	Ins.			
elements							
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0			
Sequence Number		parameter.	Number				
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0			
Metric		parameter.					
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0			
		parameter.					
		This IE should be set to "0" if the "Overload Reduction					
		Metric" is null. This IE shall be ignored by the receiver if the					
		"Overload Reduction Metric" is null.					

 Table 7.2.11.1-3: Overload Control Information within Downlink Data Notification

7.2.11.2 Downlink Data Notification Acknowledge

A Downlink Data Notification Acknowledge shall be sent from a MME/SGSN to a SGW in response to Downlink Data Notification with an indication of success, or failure when MME/SGSN has reachability or abnormal conditions.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Unable to page UE".
- "Context not found".
- "Unable to page UE due to Suspension".
- "UE already re-attached".
- "Temporarily rejected due to handover/TAU/RAU procedure in progress".

Table 7.2.11.2-1 specifies the presence of the IEs in the message.

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements			Causa	_
Cause Data Notification Delay	C	he MME/SGSN shall include the delay the SGW shall apply between receiving downlink data and sending Downlink Data Notification for all UEs served by that MME/SGSN (see subclause 5.3.4.2 of 3GPP TS 23.401 [3]), if the rate of Downlink Data Notification event occurrence in the MME/SGSN becomes significant (as configured by the operator) and the MME/SGSN's load exceeds an operator configured value. See NOTE 4.	Cause Delay Value	0
Recovery	С	This IE shall be included if contacting the peer for the first time	Recovery	0
DL low priority traffic Throttling	0	The MME/SGSN may send this IE to the SGW to request the SGW to reduce the number of Downlink Data Notification requests it sends for downlink low priority traffic received for UEs in idle mode served by that MME/SGSN in proportion to the Throttling Factor and during the Throttling Delay.	Throttling	0
IMSI	~~	See NOTE 1, NOTE 2, NOTE 3. 3GPP TS 23.007 [17] specifies conditions for sending this	IMSI	0
IMSI	0	IE on the S11/S4 interface as part of the network triggered service restoration procedure, if both the SGW and the MME/S4-SGSN support this optional feature.	IMSI	0
DL Buffering Duration		 The MME/SGSN shall include this IE on the S11/S4 interface to indicate the duration during which the SGW shall buffer DL data for this UE without sending any further Downlink Data Notification message, if extended buffering in the SGW is required: for a UE in a power saving state (e.g. Power Saving Mode or extended idle mode DRX) that cannot be reached by paging at the moment, as specified in subclause 5.3.4.3 of 3GPP TS 23.401 [3], or. for a UE using NB-IoT, WB-EUTRAN or GERAN Extended Coverage with increased NAS transmission delay (see 3GPP TS 24.301 [23] and 3GPP TS 24.008 [5]). If this IE is included in the message, the Cause IE shall be set to "Request Accepted". 	EPC Timer	0
DL Buffering Suggested Packet	0	The MME/SGSN may include this IE on the S11/S4	Integer Number	0
Count		interface, if the DL Buffering Duration IE is included, to suggest the maximum number of downlink data packets to be buffered in the SGW for this UE.		
Private Extension	0		Private Extension	
values rec timer asso traffic or n configurati traffic). NOTE 2: For instan Throttling requests it MME/SGS NOTE 3: The DL low NOTE 4: The Data usage as t	eived ciated ot on in ce, if t Delay send SN, du w prio Notific he De	d value of the Throttling Factor and Throttling Delay shall sup from that MME/SGSN. The reception of a Throttling Delay s a with that MME/SGSN. The SGW shall determine whether a the basis of the bearer's ARP priority level and operator polic the SGW of the ARP priority levels to be considered as prior he DL low priority traffic Throttling IE indicates a Throttling F of 180 seconds, the SGW drops by 40% the number of Dow s for downlink low priority traffic received for UEs in idle mod ring a period of 180 seconds. rity traffic Throttling IE may be present whatever the value of cation Delay IE in the Data Notification Acknowledge has the elay Downlink Packet Notification Request IE in the Modify B Bearers Request.	hall restart the SGV bearer is for low pr cy (i.e. operator's itary or non-priorita actor of 40% and a mlink Data Notificat le served by that the Cause IE. same semantic and	V riority ry ion

Table 7.2.11.2-1: Information Elements in a Downlink Data Notification Acknowledge

7.2.11.3 Downlink Data Notification Failure Indication

A Downlink Data Notification Failure indication shall be sent from an MME/SGSN to a SGW indicating that the UE did not respond to paging. It shall also be sent in the case that the UE responded to the page with a Service Request but that the MME has rejected the request by sending a Service Reject to the UE. It may happen, for example, because the requested service is not supported or there is a bearer context mismatch.

This message should not be used after an MME/SGSN successfully receives the Service Request message from the UE in the Network Triggered Service Request procedure as defined in the 3GPP TS 23.401 [3].

NOTE: Either the Modify Bearer Request message or the Delete Bearer Command message is used by the MME/SGSN to indicate a possible failure case after an MME/SGSN successfully receives the Service Request message from the UE.

Possible Cause values are:

- "UE not responding".
- "Service denied".
- "UE already re-attached".

Table 7.2.11.3-1 specifies the presence of the IEs in the message.

Table 7.2.11.3-1: Information Elements in a Downlink Data Notification Failure Indication

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Originating Node		This IE shall be included on the S4/S11 interface if the ISR associated GTP entities i.e. MME, S4-SGSN, send this message to the SGW during the Network Triggered Service Request procedure to denote the type of the node originating the message.	Node Type	0
IMSI		3GPP TS 23.007 [17] specifies conditions for sending this IE on the S11/S4 interface as part of the network triggered service restoration procedure, if both the SGW and the MME/S4-SGSN support this optional feature.	IMSI	0
Private Extension	0		Private Extension	VS

7.2.12 Delete Indirect Data Forwarding Tunnel Request

The Delete Indirect Data Forwarding Tunnel Request message is sent on the S4/S11 interface by the SGSN/MME to the SGW to delete the Indirect Forwarding Tunnels in the Source SGW/Target SGW as part of the following procedures:

- S1-based handover
- UTRAN Iu mode to E-UTRAN Inter RAT handover
- GERAN A/Gb mode to E-UTRAN Inter RAT handover
- E-UTRAN to UTRAN Iu mode Inter RAT handover
- E-UTRAN to GERAN A/Gb mode Inter RAT handover
- MME to 3G SGSN combined hard handover and SRNS relocation procedure
- 3G SGSN to MME combined hard handover and SRNS relocation procedure
- Inter RAT handover Cancel
- S1-based handover Cancel
- Optimised Active Handover: E-UTRAN Access to CDMA2000 HRPD Access

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Private Extension	0	Vendor or operator specific information	Private Extension	VS

7.2.13 Delete Indirect Data Forwarding Tunnel Response

The Delete Indirect Data Forwarding Tunnel Response message is sent on the S4/S11 interface by the SGW to the SGSN/MME as part of the following procedures:

- S1-based handover
- UTRAN Iu mode to E-UTRAN Inter RAT handover
- GERAN A/Gb mode to E-UTRAN Inter RAT handover
- E-UTRAN to UTRAN Iu mode Inter RAT handover
- E-UTRAN to GERAN A/Gb mode Inter RAT handover
- MME to 3G SGSN combined hard handover and SRNS relocation procedure
- 3G SGSN to MME combined hard handover and SRNS relocation procedure
- Inter RAT handover Cancel
- S1-based handover Cancel
- Optimised Active Handover: E-UTRAN Access to CDMA2000 HRPD Access

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially"
- "Context not found".

Table 7.2.13-1: Information Element in Delete Indirect Data Forwarding Tunnel Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause		This IE shall indicate if the deletion of indirect tunnel is successful, and if not, gives information on the reason.	Cause	0
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	VS

7.2.14 Modify Bearer Command and Failure Indication

7.2.14.1 Modify Bearer Command

The Modify Bearer Command shall be sent on the S11 interface by the MME to the SGW and on the S5/S8 interface by the SGW to the PGW as part of the HSS Initiated Subscribed QoS Modification procedure, or when the SQCI flag or the PSCI flag is set to 1 in the Context Response message.

It shall also be sent on the S4 interface by the SGSN to the SGW and on the S5/S8 interface by the SGW to the PGW as part of the HSS Initiated subscribed QoS modification procedure, or when the SQCI flag or the PSCI flag is set to 1 in the Context Response message.

When deferred reporting of subscription change procedure is homogenously supported by MMEs and SGSNs in the serving network, the MME shall defer sending Modify Bearer Command if the related UE is not reachable by the

MME, e.g. when the UE is suspended, when the UE has entered into power saving mode or when the PPF is cleared in the MME, until the UE becomes reachable again as specified in 3GPP TS 23.401 [3].

NOTE: SGSNs do not defer the reporting of subscription change but need to support reporting the subscription change when receiving the PSCI flag in the Context Response message.

It shall also be sent on the S2a/S2b interface by the TWAN/ePDG to the PGW as part of the HSS Initiated Subscribed QoS Modification procedure.

Information elements	Р	Condition / Comment	IE Type	Ins.
APN-Aggregate Maximum Bit Rate (APN-AMBR)	М	This IE shall contain the APN-AMBR value received by the MME/SGSN/ TWAN/ePDG from the HSS.	AMBR	0
Bearer Context	М	Only one IE with this type and instance value shall be included and this shall represent the Default Bearer.	Bearer Context	0
MME/S4-SGSN's Overload Control Information	СО	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8 interface.	Overload Control Information	0
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	1
TWAN/ePDG's Overload Control Information	0	During an overload condition, the TWAN/ePDG may include this IE over the S2a/S2b interface if the overload control feature is supported by the TWAN/ePDG and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the TWAN/ePDG shall provide only one instance of this IE, representing its overload information.	Overload Control Information	2
Sender F-TEID for Control Plane		The SGW shall include this IE on the S5/S8 interfaces and set it to the last value sent to the PGW. If the Sender F-TEID for Control Plane is received, the PGW shall only handle the Modify Bearer Command message if the Sender F-TEID for Control Plane in this message is the same as the last Sender F-TEID for Control Plane received on the given interface.	F-TEID	0
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS

Octet 1	Bearer Context IE Type = 93 (decimal)					
Octets 2 and 3	Length = n	Length = n				
Octet 4	Spare and Instance fields					
Information	P Condition / Comment	IE Type	Ins.			
elements						
EPS Bearer ID	M This IE shall contain the default bearer ID.	EBI	0			
Bearer Level QoS	C Mandatory if other parameters than the APN-AMBR have been changed	Bearer QoS	0			
	CO This IE shall also be included if the SQCI flag or PSCI flag is set to 1 in the Context Response message.	g				

Table 7.2.14.1-2: Bearer Context within Modify Bearer Command

Table 7.2.14-3: Overload Control Information within Modify Bearer Command

Octet 1		Overload Control Information IE Type = 181 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.			
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0			
Overload Reduction Metric	М	See clause 12.3.5.1.2.3 for the description and use of this parameter.	Metric	0			
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0			

7.2.14.2 Modify Bearer Failure Indication

The Modify Bearer Failure Indication shall be sent on the S5/S8 interface by the PGW to the SGW and on the S11 interface by the SGW to the MME as part of failure of HSS Initiated Subscribed QoS Modification procedure, or when the SQCI flag or the PSCI flag is set to 1 in the Context Response message.

It shall also be sent on the S5/S8 interface by the PGW to the SGW and on the S4 interface by the SGW to the SGSN as part of failure of HSS Initiated subscribed QoS modification, or when the SQCI flag or the PSCI flag is set to 1 in the Context Response message.

It shall also be sent on the S2a/S2b interface by the PGW to the TWAN/ePDG as part of failure of HSS Initiated Subscribed QoS Modification procedure.

Cause IE indicates that an EPS bearer has not been updated in the PGW.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Context not found"
- "Service denied".

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	С	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0
Indication Flags	СО	This IE shall be included if any one of the applicable flags is set to 1.	Indication	0
		 Applicable flags are: Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW. 		
PGW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4- SGSN for 3GPP access based network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.3.11).	Overload Control Information	0
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 1, NOTE 2.		
		If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.		
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and and is activated in the network (see clause 12.3.11).	Overload Control Information	1
		When present, the SGW shall provide only one instance of this IE, representing its overload information.		
Private Extension		This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS
handle the overload in NOTE 2: The APN le	APN forma evel c	pporting the APN level overload information for the maximur level overload information for the first 10 APNs and ignore a ation. overload information, provided within and across different ins of Information" IE(s) shall be limited to 10 different APNs.	iny more APN level	

Table 7.2.14.2-1: Information Elements in a Modify Bearer Failure Indication

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0
Sequence Number		parameter.	Number	
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0
Metric		parameter.		
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0
		parameter.		
		This IE should be set to "0" if the "Overload Reduction		
		Metric" is null. This IE shall be ignored by the receiver if the		
		"Overload Reduction Metric" is null.		
List of Access Point	СО	The IE may (only) be present in the "PGW's Overload	APN	0
Name (APN)		Control Information" IE.		
		For indicating the APN level overload, the PGW shall		
		include one or more instances of this IE, up to maximum of		
		10, with the same type and instance value, representing a		
		list of APN(s) (sharing the same "Overload Reduction		
		Metric").		
		See NOTE 1.		
NOTE 1: If more than	n 10 (occurrences of APNs are received within one instance of the	Overload Control	
Information	IE, t	he receiver shall treat it as a protocol error and ignore the en	tire Overload Cont	rol
Information	IE ir	istance.		

Table 7.2.14-2: Overload Control Information within Modify Bearer Failure Indication

7.2.15 Update Bearer Request

The direction of this message shall be from PGW to SGW and/or from SGW to MME/S4-SGSN, and/or from PGW to TWAN/ePDG (see Table 6.1-1).

For GTP based S5/S8, the Update Bearer Request shall be sent by the PGW to the SGW and forwarded to the MME as part of the following procedures:

- PGW Initiated Bearer Modification with Bearer QoS Update
- HSS Initiated Subscribed QoS Modification
- PGW Initiated Bearer Modification without Bearer QoS Update
- UE Request Bearer Resource Modification procedure (see 3GPP TS 24.301 [23])
- UE requested bearer resource allocation procedure (see 3GPP TS 24.301 [23])
- P-CSCF restoration for 3GPP access (see 3GPP TS 23.380 [61])

The message shall also be sent on the S5/S8 interface by the PGW to the SGW and on the S4 interface by the SGW to the SGSN as part of the following procedures:

- PGW Initiated EPS Bearer Modification
- Execution part of MS-Initiated EPS Bearer Modification
- SGSN-Initiated EPS Bearer Modification Procedure using S4
- P-CSCF restoration for 3GPP access (see 3GPP TS 23.380 [61])

The message shall also be sent on the S2a/S2b interface by the PGW to the TWAN/ePDG as part of the following procedures:

- PGW Initiated Bearer Modification
- HSS Initiated Subscribed QoS Modification

- P-CSCF restoration for WLAN access (see 3GPP TS 23.380 [61])

For PMIP based S5/S8, the Update Bearer Request shall be sent on the S11 interface by the SGW to the MME and on the S4 interface by the SGW to the SGSN.

The message shall also be sent on the S5/S8 or S2a/S2b interface by the PGW to the SGW or to the TWAN/ePDG and on the S11/S4 interface by the SGW to the MME/S4-SGSN as part of the Network-initiated IP flow mobility procedure or the UE-initiated IP flow mobility procedure, as specified by 3GPP TS 23.161 [71].

Table 7.2.15-1 specifies the presence requirements and the conditions of the IEs in the message.

Table 7.2.15-1: Information Elements in an Update Bearer Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Bearer Contexts	М	This IE shall contain contexts related to bearers that need QoS/TFT modification. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers. If there is no QoS/TFT modification, only one IE with this type and instance value shall be included.	Bearer Context	0
Procedure Transaction Id (PTI)	С	If the request corresponds to UE requested bearer resource modification procedure or the UE requested bearer resource allocation procedure for an E-UTRAN (see NOTE 1) or MS initiated EPS bearer modification procedure, this IE shall be included. PTI shall be the same as the one used in the corresponding Bearer Resource Command	PTI	0
Protocol Configuration Options (PCO)	c co	The PGW shall include the Protocol Configuration Options (PCO) IE on the S5/S8 interface, if available and if ePCO is not supported by the UE or the network. The PCO IE shall carry a P-CSCF address list only when the UE is required to perform an IMS registration, e.g during the P- CSCF restoration procedure as defined in clause 5 of 3GPP TS 23.380 [61]. If SGW receives this IE, SGW shall forward it to SGSN/MME on the S4/S11 interface. The PGW shall include the Prococol Configuration Options (PCO) IE on the S2a interface, including the list of available P-CSCF addresses, as part of the P-CSCF restoration extension procedure for the TWAN access, as specified in 3GPP TS 23.380 [61].	PCO	0
Aggregate Maximum Bit Rate (APN-AMBR)	М	APN-AMBR	AMBR	0
Change Reporting Action	С	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field If the location Change Reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	Change Reporting Action	0
CSG Information Reporting Action		This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if the CSG Info reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	CSG Information Reporting Action	0
H(e)NB Information Reporting	CO	This IE shall be included on the S5/S8 and S4/S11 interfaces with the appropriate Action field if H(e)NB information reporting is to be started or stopped for the PDN connection in the SGSN/MME.	H(e)NB Information Reporting	0

Indication flags	CO This IE shall be included if any one of the applicable flags	Indication	0
	 is set to 1. Applicable flags are: Retrieve Location Indication: This flag shall be set to 1 on the S5/S8, S4/S11, S2a and S2b interfaces in the PGW Initiated Bearer Modification procedure if the location information is requested. 		
	 Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface. Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the set with the node identity		
	IP address received from the DNS during the SGW selection) of the serving SGW.		
PGW-FQ-CSID	C This IE shall be included by PGW on the S5/S8 and S2a/S2b interfaces, and when received from S5/S8 be forwarded by SGW on S11 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	C This IE shall be included by SGW on S11 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
Presence Reporting Area Action	CO This IE shall be included on the S5/S8 and S11/S4 interfaces with the appropriate Action field if reporting changes of UE presence in Presence Routing Area(s) is to be started, stopped or modified for this subscriber in the MME/SGSN.	Presence Reporting Area	0
	Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. One IE shall be included for each Presence Reporting Area to be started, stopped or modified.	Action	
PGW's node level Load Control Information	 O The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing its node level load information, if the load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access network, belongs (see clause 12.2.6). CO If the SGW receives this IE and if it supports the load control feature, it shall forward it to the MME/S4-SGSN on 	Load Control Information	0
PGW's APN level Load Control Information	 the S11/S4 interface. O The PGW may include this IE on the S5/S8 or S2a/S2b interface, providing APN level load information, if the APN level load control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access network, ePDG/TWAN for non-3GPP access based network, belongs (see clause 12.2.6). When present, the PGW shall provide one or more 	Load Control Information	1
	instances of this IE, up to maximum of 10, with the same type and instance value, each representing the load information for a list of APN(s). See NOTE 2, NOTE 4.		

	1		1	
	со	If the SGW receives this IE and if it supports APN level		
		load control feature, it shall forward it to the MME/S4- SGSN on the S11/S4 interface.		
SGW's node level	0	The SGW may include this IE, over the S11/S4 interface if	Load Control	2
Load Control		the load control feature is supported by the SGW and is	Information	2
Information		activated in the network (see clause 12.2.6).		
		When present, the SGW shall provide only one instance of		
		this IE, representing its node level load information.		
PGW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8 or S2a/S2b interface, if the overload control	Overload Control Information	0
Control Information		feature is supported by the PGW and is activated for the	mormation	
		PLMN to which the access network node, i.e. MME/S4-		
		SGSN for 3GPP access based network, ePDG/TWAN for		
		non-3GPP access based network, belongs (see clause		
		12.3.11).		
		When present, the PGW shall provide at least one instance		
		of this IE, representing its overload information.		
		Additionally, the PGW may indicate APN level overload		
		control by providing, one or more instances of this IE, up to		
		maximum of 10, with the same type and instance value,		
		each representing the overload information for a list of		
		APN(s). See NOTE 3, NOTE 5.		
	СО	If the SGW receives this IE and if it supports the overload		
		control feature, it shall forward it to the MME/S4-SGSN on		
		the S11/S4 interface.		
SGW's Overload	0	During an overload condition, the SGW may include this IE	Overload Control	1
Control Information		over the S11/S4 interface if the overload control feature is	Information	
		supported by the SGW and is activated in the network (see clause 12.3.11).		
		When present, the SGW shall provide only one instance of		
		this IE, representing its overload information.		
NBIFOM Container	со	This IE shall be included on the S5/S8 or S2a/S2b	F-Container	0
		interfaces if the PGW needs to send NBIFOM information		
		as specified in 3GPP TS 23.161 [71]. The Container Type shall be set to 4.		
	СО	If the SGW receives a NBIFOM Container IE from the		
		PGW, the SGW shall forward it to the MME/S4-SGSN on		
		the S11/S4 interface.		
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b	Private Extension	VS
NOTE 1: This massa		linterfaces. fers to the UE requested bearer resource allocation proced	ure and LIE request	od
		modification procedures defined in 3GPP TS 24.301 [23], b		cu
		1 [3] in the clause "UE requested bearer resource modification		
NOTE 2: The receive	er, no	t supporting the APN level load control feature, shall ignore	all the occurrence(s	
		d Control Information" IE with instance number "1". The rece		APN
		I feature and supporting the APN level load information for t		
level load in		dle the APN level load information for the first 10 APNs and ation	ignore any more AF	IN
		pporting the APN level overload information for the maximur	n of 10 APNs. shall	
		level overload information for the first 10 APNs and ignore a		
overload in	forma	ation.	-	
		bad information, provided within and across different instanc	es of the "PGW's Al	PN
		ol Information" IE(s) shall be limited to 10 different APNs.		
		verload information, provided within and across different ins	tances of the "PGW	S
Uverioad C	JUNIC	I Information" IE(s) shall be limited to 10 different APNs.		

NOTE: In the case that the procedure was initiated by a UE Requested Bearer Resource Modification Procedure or UE Requested Bearer Resource Allocation Procedure for an E-UTRAN or MS initiated EPS bearer modification procedure, then there will be only one instance of the Bearer Contexts IE in the Update Bearer Request.

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
TFT	С	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if message relates to Bearer Modification and TFT change. The SGW shall forward the IE unmodified on the S4/S11 interface.	Bearer TFT	0
Bearer Level QoS	С	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if QoS modification is requested	Bearer QoS	0
Bearer Flags	0	 Applicable flags: PPC (Prohibit Payload Compression): this flag may be set on the S5/S8 and S4 interfaces. vSRVCC indicator: This IE may be included by the PGW on the S5/S8 interface according to 3GPP TS 23.216 [43]. When received from S5/S8, SGW shall forward on the S11 interface. 	Bearer Flags	0
Protocol Configuration Options (PCO)	CO	PGW shall include Protocol Configuration Options (PCO) IE on the S5/S8 interface, if available and if ePCO is not supported by the UE or the network. The PCO IE shall carry a P-CSCF address list only when the UE is required to perform an IMS registration, e.g during the P-CSCF restoration procedure as defined in sub-clause 5.1 of 3GPP TS 23.380 [61]. This bearer level IE takes precedence over the PCO IE in the message body if they both exist. If the SGW receives this IE, the SGW shall forward it to the SGSN/MME on the S4/S11 interface. The PGW shall include the Prococol Configuration Options (PCO) IE on the S2a interface, including the list of available P-CSCF addresses, as part of the P-CSCF restoration extension procedure for the TWAN access, as specified in 3GPP TS 23.380 [61]. This bearer level IE takes precedence over the PCO IE in the message body if they both exist.	PCO	0
Additional Protocol Configuration Options (APCO)		The PGW shall include the Additional Prococol Configuration Options (APCO) IE on the S2b interface, including the list of available P-CSCF addresses, as part of the P-CSCF restoration extension procedure for the untrusted WLAN access, as specified in 3GPP TS 23.380 [61].	Additional Protocol Configuration Options (APCO)	0
Extended Protocol Configuration Options (ePCO)	CO	The PGW shall include Extended Protocol Configuration Options (ePCO) IE on the S5/S8 interface, if available and if the UE and the network support ePCO. The ePCO IE shall carry a P-CSCF address list only when the UE is required to perform an IMS registration, e.g during the P- CSCF restoration procedure as defined in sub-clause 5.1 of 3GPP TS 23.380 [61]. If the SGW receives this IE, the SGW shall forward it to the MME on the S11 interface.	ePCO	0

Table 7.2.15-2: Bearer C	ontext within Update	Bearer Request

Octet 1		Load Control Information IE Type = 181 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0
Sequence Number		parameter.	Number	
Load Metric	Μ	See clauses 12.2.5.1.2.2 and 12.2.5.1.2.3 for the	Metric	0
		description and use of this parameter.		
List of APN and	CO	The IE shall (only) be present in the "PGW's APN level	APN and Relative	0
Relative Capacity		Load Control Information" IE.	Capacity	
		For indicating the APN level load, the PGW shall include		
		one or more instances of this IE, up to maximum of 10,		
		with the same type and instance value, representing a list		
		of APN(s) & its respective "Relative Capacity" (sharing the		
		same "Load Metric").		
		See clause 12.2.5.1.2.3 for the description and use of this		
		parameter.		
		See NOTE 1.		
		occurrences of "APN and Relative Capacity" IE are received		
the Load C	ontro	I Information IE, the receiver shall treat it as a protocol error	and ignore the entir	e
Load Contr	ol Inf	ormation IE instance.		

Table 7.2.15-3: Load Control Information withi	n Update Bearer Request
--	-------------------------

Table 7.2.15-4: Overload Control Information within Update Bearer Request

Octet 1		Overload Control Information IE Type = 180 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0
Period of Validity	M	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0
	IE, t	occurrences of APNs are received within one instance of the he receiver shall treat it as a protocol error and ignore the en istance.		trol

7.2.16 Update Bearer Response

An Update Bearer Response shall be sent from a MME/SGSN to a SGW and forwarded to the PGW, and from TWAN/ePDG to the PGW as a response to an Update Bearer Request message.

Table 7.2.16-1 specifies the presence requirements and the conditions of the IEs in the message.

Cause IE indicates if an EPS bearer has been modified in the MME/SGSN/TWAN/ePDG or not. The EPS Bearer has not been modified in the MME/SGSN/TWAN/ePDG if the Cause IE value differs from "Request accepted" or "Request accepted partially". Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially"
- "Context not found"
- "Semantic error in the TFT operation".
- "Syntactic error in the TFT operation".
- "Semantic errors in packet filter(s)".
- "Syntactic errors in packet filter(s)".
- "Denied in RAT".
- "UE refuses".
- "Unable to page UE".
- "UE not responding".
- "Unable to page UE due to Suspension".
- "Temporarily rejected due to handover/TAU/RAU procedure in progress".
- "MME/SGSN refuses due to VPLMN Policy".
- "UE is temporarily not reachable due to power saving"

Table 7.2.16-1: Information Elements in an Update Bearer Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Bearer Contexts		This IE shall contain all the bearer contexts included in the corresponding Update Bearer Request. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers.	Bearer Context	0
Protocol Configuration Options (PCO)		An MME/SGSN shall include the PCO IE if such information was received from the UE. If the SGW receives this IE, the SGW shall forward it to PGW on the S5/S8 interface.	PCO	0
Recovery	С	This IE shall be included on the S5/S8, S4/S11 and S2a/S2b interfaces if contacting the peer for the first time	Recovery	0
MME-FQ-CSID	С	This IE shall be included by MME on S11and shall be forwarded by SGW on S5/S8 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID	С	This IE shall be included by SGW on S5/S8 according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
ePDG-FQ-CSID	С	This IE shall be included by the ePDG on the S2b interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	2
TWAN-FQ-CSID	С	This IE shall be included by the TWAN on the S2a interface according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	3
Indication Flags	СО	This IE shall be included if any one of the applicable flags is set to 1. Applicable flags: - Direct Tunnel Flag: This flag shall be set to 1 on the S4 interface, if Direct Tunnel is used.	Indication	0
UE Time Zone	со	This IE is optionally included by the MME on the S11 interface or by the SGSN on the S4 interface. The SGW shall forward this IE on the S5/S8 interface if the SGW receives it from the MME/SGSN. This IE shall be included by the TWAN on the S2a interface.	UE Time Zone	0
User Location Information (ULI)		This IE shall be included by the MME on the S11 interface or by the SGSN on the S4 interface. The CGI/SAI shall be included by SGSN and the ECGI shall be included by MME. See NOTE 1. The SGW shall forward this IE on the S5/S8 interface if it receives it from the MME/SGSN.	ULI	0
TWAN Identifier	со	This IE shall be included by the TWAN on the S2a interface as specified in 3GPP TS 23.402 [45].	TWAN Identifier	0
MME/S4-SGSN's Overload Control Information	со	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8 interface.	Overload Control Information	0
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	1

Presence Reporting Area Information	со	The MME/SGSN shall include this IE on S11/S4 if the PGW/PCRF/OCS has requested to start or modify	Presence Reporting Area	0
		reporting changes of UE presence in a Presence Reporting Area in the corresponding Update Bearer Request message and the MME/SGSN supports such reporting. The MME/SGSN shall then indicate whether the UE is	Information	
		inside or outside the newly started or modified Presence Reporting Area(s), or indicate that the Presence Reporting Area(s) is inactive.		
		The SGW shall include this IE on S5/S8 if it receives the Presence Reporting Area Information from the MME/SGSN.		
		Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Information. One IE shall be included for each Presence Reporting Area newly started or modified.		
MME/S4-SGSN	со	If the overload control feature is supported by the MME/S4- SGSN and is activated for the PLMN to which the PGW belongs (see subclause 12.3.11), the MME/S4-SGSN shall include this IE on the S11/S4 interface if the PGW has not been updated with the identity of the currently serving		
Identifier	CO	MME/S4-SGSN, i.e. if no other message carrying MME/S4-SGSN identity has been sent to the PGW during/after an inter-MME/S4-SGSN intra-SGW mobility procedure. If the overload control feature is supported by the SGW,	IP Address	0
		the SGW shall forward this IE on the S5/S8 interface.		
TWAN/ePDG's Overload Control	0	During an overload condition, the TWAN/ePDG may include this IE over the S2a/S2b interface if the overload control feature is supported by the TWAN/ePDG and is activated for the PLMN to which the PGW belongs (see clause 12.3.11).	Overload Control	2
Information		When present, the TWAN/ePDG shall provide only one instance of this IE, representing its overload information.	momaton	
WLAN Location Information	СО	The ePDG shall include this IE on the S2b interface if the WLAN Location Information is available.	TWAN Identifier	1
WLAN Location	со	The ePDG shall include this IE on the S2b interface, if the	TWAN Identifier	1
Timestamp UE Local IP Address	co	WLAN Location Timestamp is available. The ePDG shall include this IE on the S2b interface.	Timestamp IP Address	0
UE UDP Port		The ePDG shall include this IE on the S2b interface if NAT is detected and UDP encapsulation is used.	Port Number	0
NBIFOM Container	со	This IE shall be included on the S11/S4 or S2a/S2b interfaces if the MME/S4-SGSN or the TWAN/ePDG receives a NBIFOM Container from the UE as specified in 3GPP TS 24.161 73]. The Container Type shall be set to 4.	F-Container	0
	со	If the SGW receives a NBIFOM Container IE from the MME/S4-SGSN, the SGW shall forward it to the PGW on the S5/S8 interface.		
UE TCP Port	со	The ePDG shall include this IE on the S2b interface if NAT is detected and TCP encapsulation is used.	Port Number	1
Private Extension	0	This IE may be sent on the S5/S8, S4/S11 and S2a/S2b interfaces.	Private Extension	VS
		rks, when the message is sent from the VPLMN to the HPLN		
that of the a	alloca	n this IE shall be that of the selected Core Network Operator ated Core Network Operator for non-supporting UEs. As an e	exception, based on	1
non-suppor	ting l	aming/sharing agreement, if the information on whether the UE is available, the PLMN ID that is communicated to the HF		
UEs shall b	e the	e Common PLMN ID. rks, when the MME/S4-SGSN and PGW pertain to the same		-
PLMN ID sh	hall b	e communicated in the ECGI to the PGW, and the Common	PLMN ID shall be	,
Network Op	erate	n SAI/CGI to the PGW, for both supporting and non-supporti or PLMN ID (selected by the UE for supporting UEs or alloca	ted by the network	for
		UEs) shall be communicated in the TAI, RAI, UCI and the Se 1.4 of 3GPP TS 23.251 [55].		

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements	.			
EPS Bearer ID	M		EBI	0
Cause	М	This IE Indicates if the bearer handling was successful, and if not, gives information on the reason.	Cause	0
S4-U SGSN F-TEID	С	This IE shall be included on the S4 interface when direct	F-TEID	0
54-0 565NT-TEID		tunnel is not established. See NOTE 1.		0
S12 RNC F-TEID	С	This IE shall be included on the S4 interface when direct tunnel flag is set to 1. See NOTE 1.	F-TEID	1
Protocol	CO	An MME/SGSN shall include the PCO IE if such	PCO	0
Configuration Options		information was received from the UE.		-
(PCO)		If the SGW receives this IE, the SGW shall forward it to		
(/		PGW on the S5/S8 interface.		
		This bearer level IE takes precedence over the PCO IE in		
		the message body if they both exist.		
RAN/NAS Cause	CO	If the bearer modification failed, the MME shall include this	RAN/NAS Cause	0
	00	IE on the S11 interface to indicate the RAN cause and/or		0
		the NAS cause of the bearer modification failure, if		
		available and if this information is permitted to be sent to		
		the PGW operator according to MME operator's policy.		
		If both a RAN cause and a NAS cause are generated, then		
		several IEs with the same type and instance value shall be		
		included to represent a list of causes.		
		The SGW shall include this IE on the S5/S8 interface if it		
		receives it from the MME.		
	CO	If the bearer modification failed, the TWAN shall include		
		this IE on the S2a interface to indicate the cause of the		
		bearer modification failure, if available and if this		
		information is permitted to be sent to the PGW operator		
		according to the TWAN operator's policy. When present,		
		the IE shall be encoded as a Diameter or an ESM cause.		
	~~~	See NOTE 2.		
	00	If the bearer modification failed, the ePDG shall include		
		this IE on the S2b interface to indicate the cause of the		
		bearer modification failure, if available and if this		
		information is permitted to be sent to the PGW operator		
		according to the ePDG operator's policy. When present,		
		the IE shall be encoded as a Diameter or an IKEv2 cause.		
		See NOTE 3.		
Extended Protocol	CO	The MME shall include the ePCO IE if such information is	ePCO	0
<b>Configuration Options</b>		received from the UE.		
(ePCO)				
		If the SGW receives this IE, the SGW shall forward it to		
		PGW on the S5/S8 interface.		
NOTE 1: In some sc	enari	os, the SGSN is unable to provide neither the S12 RNC F-T	EID nor the S4-U S	GSN
		odate Bearer Response message, e.g. when Direct Tunnel is		
		, for a network requested user location retrieval procedure, the		
		C F-TEID. In those scenarios, the SGSN shall provide EBI(s)		
		U SGSN F-TEID. The SGW shall be able to handle these be		•
		lier releases this behaviour may not be supported by the SG		
		b be backward compatible, the SGSN shall provide EBI(s) to	gether with either th	ie
		EID or the S12 RNC F-TEID.		
S4-U SGSN			- Ale - 1100 1 - 41 1	
S4-U SGSN NOTE 2: The TWAN	does	s not exchange signalling with the 3GPP AAA Server nor with		<b>-</b> .
S4-U SGSN NOTE 2: The TWAN procedure.	does The	TWAN may include an internal failure cause for the bearer m	odification failure.	The
S4-U SGSN NOTE 2: The TWAN procedure. protocol typ	does The be us	TWAN may include an internal failure cause for the bearer me ed to encode the internal failure cause is implementation spe	odification failure.	
S4-U SGSN NOTE 2: The TWAN procedure. protocol typ	does The be us	TWAN may include an internal failure cause for the bearer m	odification failure.	
S4-U SGSN NOTE 2: The TWAN procedure. protocol typ NOTE 3: The ePDG	does The De us does	TWAN may include an internal failure cause for the bearer me ed to encode the internal failure cause is implementation spe	odification failure. ⁻ ecific. rocedure. The ePD	G

Table 7.2.16-2: Bearer Context within Update Bearer Response

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0		
Metric		parameter.				
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0		
		parameter.				
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				

Table 7.2.16-3: Overload Control Information within Update Bearer Response

# 7.2.17 Delete Bearer Command and Failure Indication

## 7.2.17.1 Delete Bearer Command

A Delete Bearer Command message shall be sent on the S11 interface by the MME to the SGW and on the S5/S8 interface by the SGW to the PGW as a part of the eNodeB requested bearer release or MME-Initiated Dedicated Bearer Deactivation procedure.

The message shall also be sent on the S4 interface by the SGSN to the SGW and on the S5/S8 interface by the SGW to the PGW as part of the MS and SGSN Initiated Bearer Deactivation procedure using S4.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Bearer Contexts	М	This IE shall be used to indicate dedicated bearers. When used, at least one dedicated bearer shall be present. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers	Bearer Context	0
User Location Information (ULI)	со	This IE shall be included by the MME on the S11 interface or by the SGSN on the S4 interface. The CGI/SAI shall be included by SGSN and the ECGI shall be included by MME. The SGW shall forward this IE on the S5/S8 interface if it receives it from the MME/SGSN. See NOTE 1.	ULI	0
ULI Timestamp	со	This IE shall be included on the S4/S11 interface if the ULI IE is present. It indicates the time when the User Location Information was acquired. The SGW shall include this IE on S5/S8 if the SGW receives it from the MME/SGSN.	ULI Timestamp	0
UE Time Zone		This IE shall be included, if available, by the MME on the S11 interface or by the SGSN on the S4 interface. The SGW shall forward this IE on the S5/S8 interface if the SGW receives it from the MME/SGSN.	UE Time Zone	0
MME/S4-SGSN's Overload Control Information	0	During an overload condition, the MME/S4-SGSN may include this IE on the S11/S4 interface if the overload control feature is supported by the MME/S4-SGSN and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the MME/S4-SGSN shall provide only one instance of this IE, representing its overload information. If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the PGW on the S5/S8	Overload Control Information	0
SGW's Overload Control Information	0	interface. During an overload condition, the SGW may include this IE over the S5/S8 interface if the overload control feature is supported by the SGW and is activated for the PLMN to which the PGW belongs (see clause 12.3.11). When present, the SGW shall provide only one instance of	Overload Control Information	1
Sender F-TEID for Control Plane	со	this IE, representing its overload information. The SGW shall include this IE on the S5/S8 interfaces and set it to the last value sent to the PGW. If the Sender F-TEID for Control Plane is received, the PGW shall only handle the Delete Bearer Command message if the Sender F-TEID for Control Plane in this message is the same as the last Sender F-TEID for Control Plane received on the given interface.	F-TEID	0
communica that of the a inter-operat non-suppor UEs shall b In shared n PLMN ID st communica Network Op non-suppor	ted in allocator ro ting l e the etwo hall b hall b ted in perate	rks, when the message is sent from the VPLMN to the HPLM n this IE shall be that of the selected Core Network Operator ated Core Network Operator for non-supporting UEs. As an e aming/sharing agreement, if the information on whether the JE is available, the PLMN ID that is communicated to the HF e Common PLMN ID. rks, when the MME/S4-SGSN and PGW pertain to the same e communicated in the ECGI to the PGW, and the Common in SAI/CGI to the PGW, for both supporting and non-supporti or PLMN ID (selected by the UE for supporting UEs or alloca JEs) shall be communicated in the TAI, RAI, UCI and the Se I.4 of 3GPP TS 23.251 [55].	for supporting UEs exception, based on UE is a supporting PLMN for non-support PLMN, the Primary PLMN ID shall be ng UEs. The Core ated by the network	at is , or or orting

Table 7.2.17.1-1: Information Elements in Delete Bearer Command

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.		
elements						
EPS Bearer ID	Μ		EBI	0		
Bearer Flags	co	<ul> <li>Applicable flags are:</li> <li>VB (Voice Bearer) indicator shall be set to indicate a voice bearer for PS-to-CS (v)SRVCC handover.</li> <li>Vind (vSRVCC indicator) indicator shall be set to indicate a video bearer for PS-to-CS vSRVCC handover.</li> </ul>	Bearer Flags	0		
RAN/NAS Release Cause	CO	The MME shall include this IE on the S11 interface to indicate the RAN release cause and/or NAS release cause to release the bearer, if available and this information is permitted to be sent to the PGW operator according to MME operator's policy. If both a RAN release cause and a NAS release cause are generated, then several IEs with the same type and instance value shall be included to represent a list of causes. The SGW shall include this IE on the S5/S8 interface if it receives it from the MME.	RAN/NAS Cause	0		

Table 7.2.17.1-2: Bearer Context within Delete Bearer Command

#### Table 7.2.17.1-3: Overload Control Information within Delete Bearer Command

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0		
Metric		parameter.				
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter.	EPC Timer	0		
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				

#### 7.2.17.2 Delete Bearer Failure Indication

A Delete Bearer Failure Indication shall be sent on the S5/S8 interface by the PGW to the SGW and on the S11 interface by the SGW to the MME as part of failure of eNodeB requested bearer release or MME Initiated Dedicated Bearer Deactivation procedure.

The message shall also be sent on the S5/S8 interface by the PGW to the SGW and on the S4 interface by the SGW to the SGSN as part of failure of MS and SGSN Initiated Bearer Deactivation procedure using S4.

This message shall be sent back if none of the bearers (not even a single one) included in the Delete Bearer Command message could be deleted.

The Cause IE indicates that the EPS bearer has not been deleted in the PGW.

When the SGW receives a Delete Bearer Failure Indication message from the PGW with the TEID set to zero in the GTPv2 header and the Cause IE is set to "Context Not Found", which implies that the PDN connection does not exist in the PGW, the SGW may send a Delete Bearer Request message to delete the PDN connection towards the MME/SGSN after sending the Delete Bearer Failure Indication message.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Context not found"

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.	
Cause	М		Cause	0	
Bearer Context	M	This IE shall contain the list of failed bearers. See subclause 6.1.1 "Presence requirements of Information Elements". Several IEs with the same type and instance value may be	Bearer Context	0	
Recovery	С	included as necessary to represent a list of failed bearers. This IE shall be included If contacting the peer for the first time.	Recovery	0	
Indication Flags	со	This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are:	Indication	0	
		<ul> <li>Associate OCI with PGW node's identity: The PGW shall set this flag to 1 on the S5/S8 interface or S2a/S2b interface if it has included the "PGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW. The SGW shall set this flag on the S11/S4 interface if it supports the overload control feature and if the flag is set on the S5/S8 interface.</li> </ul>			
		- Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW.			
PGW's Overload Control Information	0	During an overload condition, the PGW may include this IE on the S5/S8, if the overload control feature is supported by the PGW and is activated for the PLMN to which the access network node, i.e. MME/S4-SGSN for 3GPP access based network belongs (see clause 12.3.11).	Overload Control Information	0	
		When present, the PGW shall provide at least one instance of this IE, representing its overload information. Additionally, the PGW may indicate APN level overload control by providing, one or more instances of this IE, up to maximum of 10, with the same type and instance value, each representing the overload information for a list of APN(s). See NOTE 1, NOTE 2.			
	CO	If the SGW receives this IE and if it supports the overload control feature, it shall forward it to the MME/S4-SGSN on the S11/S4 interface.			
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11).	Overload Control Information	1	
Drivete For		When present, the SGW shall provide only one instance of this IE, representing its overload information.			
Private Extension	0		Private Extension		
handle the overload in	<ul> <li>NOTE 1: The receiver, supporting the APN level overload information for the maximum of 10 APNs, shall handle the APN level overload information for the first 10 APNs and ignore any more APN level overload information.</li> <li>NOTE 2: The APN level overload information, provided within and across different instances of the "PGW's</li> </ul>				
		Information" IE(s) shall be limited to 10 different APNs.		-	

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
EPS Bearer ID	Μ	See subclause 6.1.1 "Presence requirements of	EBI	0		
		Information Elements".				
Cause	Μ	This IE shall indicate the reason of the unsuccessful	Cause	0		
		handling of the bearer.				

 Table 7.2.17.2-2: Bearer Context within Delete Bearer Failure Indication

#### Table 7.2.17-3: Overload Control Information within Delete Bearer Failure Indication

Octet 1		Overload Control Information IE Type = 180 (decimal)			
Octets 2 and 3		Length = n			
Octet 4		Spare and Instance fields			
Information elements	Р	Condition / Comment	ІЕ Туре	Ins.	
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0	
Overload Reduction Metric	М	See clauses 12.3.5.1.2.3 and 12.3.5.1.2.4 for the description and use of this parameter.	Metric	0	
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0	
List of Access Point Name (APN)	CO	The IE may (only) be present in the "PGW's Overload Control Information" IE. For indicating the APN level overload, the PGW shall include one or more instances of this IE, up to maximum of 10, with the same type and instance value, representing a list of APN(s) (sharing the same "Overload Reduction Metric" and "Period of Validity"). See NOTE 1.	APN	0	
NOTE 1: If more than 10 occurrences of APNs are received within one instance of the Overload Control Information IE, the receiver shall treat it as a protocol error and ignore the entire Overload Control Information IE instance.					

# 7.2.18 Create Indirect Data Forwarding Tunnel Request

The Create Indirect Data Forwarding Tunnel Request message shall be sent on the S11/S4 interface by the MME/SGSN to the SGW as part of the Handover procedures or TAU/RAU procedure with Serving GW change and data forwarding as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3].

Table 7.2.18-1 specifies the presence requirements and the conditions of the IEs in the message.

Information elements	P	Condition / Comment	ІЕ Туре	Ins.
IMSI	C	<ul> <li>This IE shall be included by the MME/SGSN if the SGW that the MME/SGSN selects for indirect data forwarding is different from the SGW already in use for the UE as the anchor point except for the case: <ul> <li>If the UE is emergency attached and the UE is UICCless</li> </ul> </li> <li>When the IMSI is included in the message, it is not used as an identifier <ul> <li>if UE is emergency attached but IMSI is not authenticated.</li> </ul> </li> </ul>	IMSI	0
ME Identity (MEI)	С	See NOTE1. This IE shall be included by the MME/SGSN if the SGW	MEI	0
		<ul> <li>that the MME/SGSN selects for indirect data forwarding is different from the SGW already in use for the UE as the anchor point and if one of the following condition satisfies:</li> <li>If the UE is emergency attached and the UE is UICCless</li> </ul>		
		<ul> <li>If the UE is emergency attached and the IMSI is not authenticated</li> </ul>		
Indication Flags	CO	This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: - Unauthenticated IMSI: This flag shall be set to 1 if the IMSI present in the message is not authenticated and is for an emergency attached UE.	Indication	0
Sender F-TEID for Control Plane	С	This IE shall be included by the MME/SGSN if the SGW that the MME/SGSN selects for indirect data forwarding is different from the SGW already in use for the UE as the anchor point. See NOTE1.	F-TEID	0
Bearer Contexts	М	Several IEs with this type and instance value may be included as necessary to represent a list of Bearers	Bearer Context	0
Recovery	CO	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	
PGW, th supporte moved, t data forv	e SGW ed with S become varding	is hosting the UE's bearer(s) is considered as the (local) an may change due to mobility between eNodeBs, or E-UTRAN S4 based architecture. In these cases the new SGW where t s the new local anchor point. A source MME/SGSN may sel- which is different than the source (anchor) SGW. Similarly, a for indirect data forwarding which is different than the target	N and GERAN/UTR he UE's bearer(s) a ect an SGW for indi a target MME/SGSN	AN re rect

Table 7.2.18-1: Information Elements in a Create Indirect Data Forwarding Tunnel Request

Table 7.2.18-2: Bearer Context within Create Indirect Data Forwarding Tunnel Request

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	P	Condition / Comment	IE Type	Ins.
EPS Bearer ID	Μ		EBI	0
eNodeB F-TEID for	С	Target eNodeB F-TEID.	F-TEID	0
DL data forwarding		This IE shall be present in the message sent from the target MME to the SGW selected by the target MME for indirect data forwarding, or shall be included in the message sent from the source SGSN/MME to the SGW selected by the source MME for indirect data forwarding if the eNodeB F-TEID for DL data forwarding is included in the Forward Relocation Response message.		
	CO	Target eNodeB F-TEID. This IE shall be present in the message sent from the target MME to the SGW selected by the target MME for indirect data forwarding of the DL data buffered in the old SGW during a TAU with SGW change procedure and data forwarding, without Control Plane CIoT EPS optimisation, as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3].		
SGW F-TEID for DL data forwarding	С	Target SGW F-TEID This IE shall be present in the message sent from the source MME/SGSN to the SGW selected by the source MME for indirect data forwarding if SGW F-TEID for DL data forwarding is included in the Forward Relocation Response message. This F-TEID is assigned by the SGW that the target MME/SGSN selects for indirect data forwarding.	F-TEID	1
SGSN F-TEID for DL data forwarding	C	Target SGSN F-TEID This IE shall be present in the message sent from the target SGSN to the SGW selected by the target SGSN for indirect data forwarding in E-UTRAN to GERAN/UTRAN inter RAT handover with SGW relocation procedure, or shall be included in the message sent from the source MME to the SGW selected by the source MME for indirect data forwarding if the SGSN F-TEID for DL data forwarding is included in the Forwarding Relocation Response message.	F-TEID	2
	CO	This IE shall also be present in the message sent from the source MME to the SGW selected by the source MME for indirect data forwarding if the SGSN Address for User Traffic and the Tunnel Endpoint Identifier Data II are included in the GTPv1 Forward Relocation Response message as specified in D.3.7 of 3GPP TS 23.401 [3] This IE shall also be present, when Direct Tunnel is not used, in the message sent from the target SGSN to the SGW selected by the target SGSN for indirect data forwarding of the DL data buffered in the old SGW during a RAU with SGW change procedure and data forwarding, as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3].		
RNC F-TEID for DL data forwarding	С	Target RNC F-TEID This IE shall be present in the message sent from the target SGSN to the SGW selected by the target SGSN for indirect data forwarding in E-UTRAN to UTRAN inter RAT handover with SGW relocation procedure, or shall be included in the message sent from the source MME to the SGW selected by the source MME for indirect data forwarding if the RNC F-TEID for DL data forwarding is included in the Forwarding Relocation Response message.	F-TEID	3

	<ul> <li>CO This IE shall also be present in the message sent from the source MME to the SGW selected by the source MME for indirect data forwarding if the RNC IP address and TEID are included in the RAB Setup Information and/or the Additional RAB Setup Information in the GTPv1 Forwarding Relocation Response message as specified D.3.3 of 3GPP TS 23.401 [3].</li> <li>This IE shall be present, when Direct Tunnel is used, in the message sent from the target SGSN to the SGW selected by the target SGSN for indirect data forwarding of the DI data buffered in the old SGW during a RAU with SGW change procedure and data forwarding as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3].</li> </ul>	or in the ed	
eNodeB F-TEID for UL data forwarding	O Target eNodeB F-TEID. If available this IE may be present in the message, which sent during the intra-EUTRAN HO from the target MME the SGW selected by the target MME for indirect data forwarding, or may be included in the message sent from the source MME to the SGW selected by the source MM for indirect data forwarding if the eNodeB F-TEID for dat UL forwarding is included in the Forward Relocation Response message.	to n IE	4
SGW F-TEID for UL data forwarding	O Target SGW F-TEID If available this IE may be present in the message, which sent during the intra-EUTRAN HO from the source MME the SGW selected by the source MME for indirect data forwarding if SGW F-TEID for UL data forwarding is included in the Forward Relocation Response message. This F-TEID is assigned by the SGW that the target MM selects for indirect data forwarding.	to	5
MME F-TEID for DL data forwarding	CO Target MME S11-U F-TEID This IE shall be present in the message sent from the target MME to the SGW selected by the target MME for indirect data forwarding, during a TAU procedure with SGW change and data forwarding, with Control Plane C EPS optimisation, as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3].	F-TEID loT	6

# 7.2.19 Create Indirect Data Forwarding Tunnel Response

A Create Indirect Data Forwarding Tunnel Response message shall be sent by the SGW to the MME/SGSN as a response to a Create Indirect Data Forwarding Tunnel Request message.

Table 7.2.19-1 specifies the presence requirements and the conditions of the IEs in the message.

The Cause value indicates if the Indirect Data Forwarding Tunnels has been created in the SGW or not. No Indirect Data Forwarding Tunnels have been created in the SGW if the Cause differs from "Request accepted" or "Request accepted partially". Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Data forwarding not supported".
- "Context not found".

Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
Cause	Μ		Cause	0
Sender F-TEID for	С	This IE shall be included by an SGW if the SGW receives a	F-TEID	0
Control Plane		Sender F-TEID for Control Plane IE from an MME/SGSN in		
		a Create Indirect Data Forwarding Tunnel Request		
		message.		
		See also NOTE 1 in Table 7.2.18-1.		
Bearer Contexts	Μ	Several IEs with this type and instance value may be	Bearer Context	0
		included as necessary to represent a list of Bearers		
Recovery	CO	This IE shall be included if contacting the peer for the first	Recovery	0
		time		
Private Extension	0		Private Extension	VS

Table 7.2.19-1: Information Elements in a Create Indirect Data Forwarding Tunnel Response

## Table 7.2.19-2: Bearer Context within Create Indirect Data Forwarding Tunnel Response

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
Cause	Μ	This IE shall indicate if the tunnel setup was successful,	Cause	0
		and if not, gives information on the reason.		
S1-U SGW F-TEID	С	This IE shall be included in the response sent from the	F-TEID	0
for DL data		SGW selected by the source MME for indirect data		
forwarding		forwarding to the source MME. See NOTE 3.		
S12 SGW F-TEID for	С	S12 usage only.	F-TEID	1
DL data forwarding		This IE shall be included in the response sent from the		
		SGW selected by the source SGSN for indirect data		
		forwarding to the source SGSN. See NOTE 3.		
S4-U SGW F-TEID	С	S4-U usage only.	F-TEID	2
for DL data		This IE shall be included in the response sent from the		
forwarding		SGW selected by the source SGSN for indirect data		
		forwarding to the source SGSN. See NOTE 3.		
SGW F-TEID for DL	С	This IE shall be included in the response message sent	F-TEID	3
data forwarding		from the SGW selected by the target MME/SGSN for		
		indirect data forwarding to the target MME/SGSN. See		
		NOTE 3.		
S1-U SGW F-TEID	0	If available this IE may be included in the response sent	F-TEID	4
for UL data		during the intra-EUTRAN HO from the SGW selected by		
forwarding		the source MME for indirect data forwarding to the source		
		MME. See NOTE 4.		
SGW F-TEID for UL	0	If available this IE may be included in the response	F-TEID	5
data forwarding		message sent during the intra-EUTRAN HO from the SGW		
		selected by the target MME for indirect data forwarding to		
	Ĺ	the target MME. See NOTE 4.		
		varding if the SGW does not have enough information to dec		TEID
		1-U, S12, S4-U and SGW to include in the message, it may i		
		varding if the SGW does not have enough information to dec		TEID
		1-U and SGW to include in the message, it may include both		
		warding the SGW shall set the interface type in the F-TEID to	o 23, i.e "SGW GTF	P-U
		data forwarding" for S1-U/S4-U/S12/SGW.		
	5			
interface for	UL	data forwarding" for S1-U/SGW.		

# 7.2.20 Void

# 7.2.21 Release Access Bearers Request

The Release Access Bearers Request message shall be sent on the S11 interface by the MME to the SGW as part of the S1 release procedure and eNodeB initiated Connection Suspend procedure.

It may also be sent on the S11 interface by the MME to the SGW as part of the Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS optimisation procedure (see subclause 5.3.4B.4 of 3GPP TS 23.401 [3]).

NOTE: The S1 release procedure is also used to release the S11-U bearers for the Control Plane CIoT EPS optimisation, except in the case of data buffering in the MME.

The message shall also be sent on the S4 interface by the SGSN to the SGW as part of the procedures:

- RAB release using S4
- Iu Release using S4
- READY to STANDBY transition within the network

#### Table 7.2.21-1: Information Element in Release Access Bearers Request

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements List of RABs	0	Chall be present on C4 interface when this measure is	EBI	0
LIST OF RABS	С	Shall be present on S4 interface when this message is used to release a subset of all active RABs according to the RAB release procedure. Several IEs with this type and instance values shall be included as necessary to represent a list of RABs to be released.	ЕВІ	0
Originating Node	CO	This IE shall be sent on S11 interface, if ISR is active in the MME. This IE shall be sent on S4 interface, if ISR is active in the SGSN See NOTE 1.	Node Type	0
Indication Flags	CO	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags are: <ul> <li>Abnormal Release of Radio Link: This flag shall be set to 1 on the S11 interface</li> <li>if the S1 release is due to an abnormal release of the radio link, e.g. when the MME receives UE CONTEXT RELEASE REQUEST with the cause value set to Radio Connection With UE Lost, or</li> <li>if the MME performs DL data buffering and the operator specified policy/configuration conditions for triggering the PGW pause of charging are met (e.g. number/fraction of packets/bytes dropped at MME in downlink) as specified in subclause 5.3.6A of 3GPP TS23.401 [3].</li> </ul> </li> </ul>	Indication	0
Private Extension	0		Private Extension	VS
NOTE 1: If SGW has the S1-U F-TEIDs for the UE, but the Originating Node IE contains value "SGSN", then the SGW shall not release the user plane and shall send a positive response to the SGSN. If SGW has the S12 RNC TEIDs or S4-U SGSN TEIDs for the UE, but the Originating Node IE				
contains val response to		MME", then the SGW shall not release the user plane and sh MME.	nali send a positive	

# 7.2.22 Release Access Bearers Response

The Release Access Bearers Response message is sent on the S11 interface by the SGW to the MME as part of the S1 release procedure and eNodeB initiated Connection Suspend procedure.

It may also be sent on the S11 interface by the SGW to the MME as part of the Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS optimisation procedure (see subclause 5.3.4B.4 of 3GPP TS 23.401 [3]).

NOTE: The S1 release procedure is also used to release S11-U bearers for the Control Plane CIoT EPS optimisation, except in the case of data buffering in the MME.

The message shall also be sent on the S4 interface by the SGW to the SGSN as part of the procedures:

- RAB release using S4
- Iu Release using S4
- READY to STANDBY transition within the network

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Context not found".

## Table 7.2.22-1: Information Element in Release Access Bearers Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	0	This IE shall be included if contacting the peer for the first time	Recovery	0
Indication Flags	СО	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags are: <ul> <li>Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW.</li> </ul></li></ul>	Indication	0
SGW's node level Load Control Information	0	The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6). When present, the SGW shall provide only one instance of this IE, representing its node level load information.	Load Control Information	0
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	0
Private Extension	0		Private Extension	VS

Octet 1		Load Control Information IE Type = 181 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Load Metric	M	See clause 12.2.5.1.2.2 for the description and use of this	Metric	0		
		parameter.				

 Table 7.2.22-2: Load Control Information within Release Access Bearers Response

### Table 7.2.22-3: Overload Control Information within Release Access Bearers Response

Octet 1		Overload Control Information IE Type = 180 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.			
Overload Control Sequence Number	М	See clause 12.3.5.1.2.1 for the description and use of this parameter.	Sequence Number	0			
Overload Reduction Metric	М	See clause 12.3.5.1.2.3 for the description and use of this parameter.	Metric	0			
Period of Validity	М	See clause 12.3.5.1.2.2 for the description and use of this parameter. This IE should be set to "0" if the "Overload Reduction Metric" is null. This IE shall be ignored by the receiver if the "Overload Reduction Metric" is null.	EPC Timer	0			

# 7.2.23 Stop Paging Indication

A Stop Paging Indication message shall be sent on the S11/S4 interface by the SGW to the MME/SGSN as a part of the network triggered service request procedure.

Table 7.2.23-1 specifies the presence of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI		This IE shall be included on the S11/S4 interface when the Stop Paging Indication message is sent to the restarted CN node (or another node in the same pool) as part of the network triggered service restoration procedure with ISR (see 3GPP TS 23.007 [17]).	IMSI	0
Private Extension	0		Private Extension	VS

## 7.2.24 Modify Access Bearers Request

The direction of this message shall be from MME to SGW (see Table 6.1-1).

If both the SGW and the MME support the MABR feature (see subclause 8.83), an MME may send a Modify Access Bearer Request message on the S11 interface to an SGW as part of the following procedures:

- UE triggered Service Request if there is no suspended bearer for that UE,
- S1-based Handover without SGW relocation,
- X2-based handover without SGW relocation,
- Inter-MME E-UTRAN Tracking Area Update without SGW Change,

- Intra-MME E-UTRAN Tracking Area Update without SGW Change with Active Flag;
- E-UTRAN Initiated E-RAB modification procedure
- Mobile Originated Data transport in Control Plane CIoT EPS optimisation with P-GW connectivity
- Mobile Terminated Data Transport in Control Plane CIoT EPS optimisation with P-GW connectivity
- Connection Resume procedure (see subclause 5.3.5A of 3GPP TS 23.401 [3])
- Establishment of S1-U bearer during Data Transport in Control Plane CIoT EPS optimisation procedure (see subclause 5.3.4B.4 of 3GPP TS 23.401 [3]).

if all the following conditions are fulfilled:

- the RAT type has not changed;
- the Serving Network has not changed;
- the MME does not need to report a H(e)NB local IP address and UDP port number information change;
- the MME does not need to send UE's location and/or User CSG information or/and UE Time Zone and/or Presence Reporting Area information to the PDN GW;
- the MME does not need to send an MME-FQ-CSID as per the requirements specified in 3GPP TS 23.007 [17];
- ISR is not activated, if the Modify Access Bearers Request is sent as part of a UE triggered Service Request;
- ISR was not activated in the old MME which is indicated by the ISRAU flag in the Context Response, if the Modify Access Bearers Request is sent as part of an Inter-MME E-UTRAN Tracking Area Update without SGW change.
- the support of ePCO has not be changed during inter MME mobility.

The Modify Access Bearers Request message shall include all the bearer contexts of all the PDN connections of the UE.

Support of this message is optional for the MME and SGW.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Indication Flags	С	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags are: <ul> <li>ISRAI: This flag shall be set to 1 if ISR is established between the MME and the S4 SGSN for an S1-based Handover without SGW relocation and for an X2-based Handover without SGW relocation.</li> <li>Change F-TEID support Indication: This flag shall be set to 1 for an IDLE state UE initiated TAU procedure to allow the SGW changing the GTP-U F-TEID.</li> </ul> </li> </ul>	Indication	0
		<ul> <li>S11-U Tunnel Flag: this flag shall be set to 1 on the S11 interface if user data is transported in NAS signalling.</li> </ul>		
Sender F-TEID for Control Plane	С	The new MME shall include this IE on the S11 interface for a TAU/Handover with MME change and without any SGW change. If the SGW receives this IE and if it finds that its value is the same as the earlier received value of this IE for this UE, it should interpret this to mean that the MME has not changed.	F-TEID	0
Delay Downlink Packet Notification Request	С	This IE shall be sent for a UE triggered Service Request and UE initiated Connection Resume procedures. It shall contain the delay the SGW shall apply between receiving downlink data and sending Downlink Data Notification for all UEs served by that MME (see subclause 5.3.4.2 of 3GPP TS 23.401 [3]).	Delay Value	0
Bearer Contexts to be modified	С	Several IEs with the same type and instance value may be included as necessary to represent a list of Bearers to be modified. See NOTE 1.	Bearer Context	0
Bearer Contexts to be removed	C	This IE shall be included for the TAU/Handover, UE initiated Connection Resume and Service Request procedures where any of the bearers existing before the TAU/Handover procedure, UE initiated Connection Resume and Service Request procedures will be deactivated as consequence of the TAU/Handover procedure, UE initiated Connection Resume and Service Request procedures. For the Service Request and UE initiated Connection Resume procedures, all unaccepted bearers for this UE shall be included. For each of those bearers, an IE with the same type and instance value, shall be included. See NOTE 1.	Bearer Context	1
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	VS
all the beare	ers o	text to be modified IE and Bearer Context to be removed IE, f all the existing PDN connections of the UE, with each bear e subclause 14 for the cases when a Bearer Context misma	together, shall con er appearing in only	

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Туре	Ins.
elements				
EPS Bearer ID	Μ	See NOTE 1.	EBI	0
S1-U eNodeB F-TEID	С	<ul> <li>This IE shall be sent if S1-U is being used for:</li> <li>an UE triggered Service Request;</li> <li>S1-based Handover without SGW relocation;</li> </ul>	F-TEID	0
		- X2-based handover without SGW relocation;		
		<ul> <li>in S1-U GTP-U tunnel setup procedure during an Inter-MME E-UTRAN Tracking Area Update without SGW Change procedure or Intra-MME E- UTRAN Tracking Area Update without SGW Change procedure with Active Flag (see 3GPP TS 24.301 [23]);</li> </ul>		
		<ul> <li>an E-UTRAN Initiated E-RAB modification procedure;</li> </ul>		
		- an UE initiated Connection Resume;		
		<ul> <li>the Establishment of S1-U bearer during Data Transport in Control Plane CloT EPS optimisation procedure. See NOTE 2.</li> </ul>		
		If an MME is aware that the eNodeB supports both IP address types, the MME shall send both IP addresses within an F-TEID IE. If only one IP address is included, then the SGW shall assume that the eNodeB does not support the other IP address type.		
S11-U MME F-TEID	CO	<ul> <li>This IE shall be sent on the S11 interface if S11-U is being used, i.e. for the following procedures:         <ul> <li>Mobile Originated Data transport in Control Plane CloT EPS optimisation with P-GW connectivity</li> <li>Mobile Terminated Data Transport in Control Plane CloT EPS optimisation with P-GW connectivity</li> </ul> </li> </ul>	F-TEID	1
		rer ID IE is included in the Bearer Context to be modified IE of		
NOTE 2: In the Estab procedure ( Bearers Re prior Releas encode the the SGW sh	olishr see ques se Ao bear hall r	ocedure, the SGW shall remove the stored eNodeB/MME us ment of S1-U bearer during Data Transport in Control Plane of subclause 5.3.4B.4 of 3GPP TS 23.401 [3]), the MME may s at to the SGW, to request the establishment of the S1-U bear ccess Bearers Request to tear down the S11-U bearers. In the rers being switched from S11-U to S1-U in the Bearer Contex elease the S11-U bearers upon receipt of the Modify Access stablishment of the S1-U bearers.	CloT EPS optimisa end a Modify Acces ers, without sendin his case, the MME s kts to be modified II	tion ss g a shall

Table 7.2.24-2: Bearer Context to be modified within Modify Access Bearers Request

## Table 7.2.24-3: Bearer Context to be removed within Modify Access Bearers Request

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
EPS Bearer ID	Μ		EBI	0

# 7.2.25 Modify Access Bearers Response

If an SGW supports the MABR feature (see subclause 8.83), the SGW shall send a Modify Access Bearers Response message on the S11 interface to an MME as a response to a Modify Access Bearers Request message.

If handling of all default bearers to be modified fails, then Cause at the message level shall be a failure cause.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "Context not found".
- "Service not supported".
- "Modifications not limited to S1-U bearers"

The SGW shall send the cause value "Modifications not limited to S1-U bearers" if

- it can not serve the MME Request without corresponding S5/S8 signalling other than to unpause charging in the PGW, or without corresponding Gxc signalling when PMIP is used over the S5/S8 interface, or
- if there are suspended non-GBR bearers for that UE in the SGW (NOTE 3).

Upon receipt of that cause value, the MME shall repeat its request using Modify Bearer Request message per PDN connection.

- NOTE 1: This cause value is introduced for forward compatibility between an MME implementing this version of the specification and an SGW implementing a more recent version requiring the SGW to send S5/S8 signalling.
- NOTE 2: During an Inter-MME Intra-SGW handover/TAU, if the SGW, PGW and the old MME support the partial failure handling feature but the new MME doesn't, the SGW needs to inform the PGW about the change of FQ-CSID (see subclause 16.2.5 of 3GPP TS 23.007 [17]). If the SGW receives a Modify Access Bearers Request from the new MME, it can force the MME to send individual Modify Bearer Request message per PDN connection by returning the cause value "Modifications not limited to S1-U bearers".
- NOTE 3: There may be some suspended non-GBR bearers in the SGW during an Inter-MME Intra-SGW Tracking Area Update without SGW Change when the UE is coming back to E-UTRAN via a different MME than the MME serving the UE before the CSFB or SRVCC call.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Bearer Contexts modified	С	EPS bearers corresponding to Bearer Contexts to be modified that were sent in Modify Access Bearers Request message. Several IEs with the same type and instance value may be included as necessary to represent a list of the Bearers which are modified.	Bearer Context	0
Bearer Contexts marked for removal	С	EPS bearers corresponding to Bearer Contexts to be removed that were sent in the Modify Access Bearers Request message. Shall be included if request message contained Bearer Contexts to be removed. For each of those bearers an IE with the same type and instance value shall be included.	Bearer Context	1
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
Indication Flags	CO	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags are: <ul> <li>Associate OCI with SGW node's identity: The SGW shall set this flag to 1 on the S11/S4 interface if it has included the "SGW's Overload Control Information" and if this information is to be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW.</li> </ul></li></ul>	Indication	0
SGW's node level Load Control Information	0	The SGW may include this IE, over the S11/S4 interface if the load control feature is supported by the SGW and is activated in the network (see clause 12.2.6). When present, the SGW shall provide only one instance of this IE, representing its node level load information.	Load Control Information	0
SGW's Overload Control Information	0	During an overload condition, the SGW may include this IE over the S11/S4 interface if the overload control feature is supported by the SGW and is activated in the network (see clause 12.3.11). When present, the SGW shall provide only one instance of this IE, representing its overload information.	Overload Control Information	0
Private Extension	0		Private Extension	VS

Table 7.2.25-1: Information Elements in a Modify Access Bearers Response

Octets 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octets 4		Spare and Instance fields		
Information	Р	Condition / Comment	ІЕ Туре	Ins.
elements				
EPS Bearer ID	Μ		EBI	0
Cause	Μ	This IE shall indicate if the bearer handling was successful, and if not, gives information on the reason.	Cause	0
S1-U SGW F-TEID	С	This IE shall be present on the S11 interface if S1-U is being used, i.e. if the S11-U Tunnel flag was not set in the Modify Access Bearers Request. The SGW may change the GTP-U F-TEID value if the 'Change F-TEID support Indication' flag was set to 1 in the Modify Access Bearers Request. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value. See NOTE 1.	F-TEID	0
S11-U SGW F-TEID	С	This IE shall be present on the S11 interface if S11-U is being used, i.e. if the S11-U Tunnel flag was set in the Modify Access Bearers Request. If the 'Change F-TEID support Indication' flag was set to 1 in the Modify Bearer Request and the SGW needs to change the F-TEID, the SGW shall include the new GTP-U F-TEID value. Otherwise, the SGW shall return the currently allocated GTP-U F-TEID value.	F-TEID	1
and E-UTR During Han used by the	AN I dove sou	not change its F-TEID for a given interface during the Hando nitiated E-RAB modification procedures. er and Service Request the target eNodeB may use a differer rce eNodeB. In order to support such a scenario, the SGW F dress and an IPv6 address (see also subclause 8.22 "F-TEIE	nt IP type than the o -TEID should conta	one

## Table 7.2.25-2: Bearer Context modified within Modify Access Bearers Response

## Table 7.2.25-3: Bearer Context marked for removal within Modify Access Bearers Response

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.		
EPS Bearer ID	Μ		EBI	0		
Cause		This IE shall indicate if the bearer handling was successful, and if not, gives information on the reason.	Cause	0		

## Table 7.2.25-4: Load Control Information within Modify Access Bearers Response

Octet 1		Load Control Information IE Type = 181 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Load Control	Μ	See clause 12.2.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Load Metric	Μ	See clause 12.2.5.1.2.2 for the description and use of this	Metric	0		
		parameter.				

Octet 1		Overload Control Information IE Type = 180 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.		
elements						
Overload Control	Μ	See clause 12.3.5.1.2.1 for the description and use of this	Sequence	0		
Sequence Number		parameter.	Number			
Overload Reduction	Μ	See clause 12.3.5.1.2.3 for the description and use of this	Metric	0		
Metric		parameter.				
Period of Validity	Μ	See clause 12.3.5.1.2.2 for the description and use of this	EPC Timer	0		
		parameter.				
		This IE should be set to "0" if the "Overload Reduction				
		Metric" is null. This IE shall be ignored by the receiver if the				
		"Overload Reduction Metric" is null.				

Table 7.2.25-5: Overload Control Information within Modify Access Bearers Response

# 7.2.26 Remote UE Report Notification

The direction of this message shall be from MME to SGW and from SGW to the PGW (see Table 6.1-1).

This message is used by an MME to notify that at least one remote UE is newly connected to or disconnected from a ProSe UE-to-Network Relay when the MME receives such notification from the ProSe UE-to-Network Relay via the PDN connection established by the ProSe UE-to-Network Relay as specified in 3GPP TS 23.303 [72].

Table 7.2.26-1 specifies the presence of IEs in this message.

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
Remote UE Context	С	This IE shall be sent on the S11 interface and S5/S8	Remote UE	0
Connected		interface when the MME receives a report from the ProSe UE-to-Network Relay that a remote UE is newly connected.	Context	
		The SGW shall forward this IE to the PGW.		
		Several IEs with the same type and instance value may be included as necessary to represent a list of remote UEs newly connected.		
Remote UE Context Disconnected	С	This IE shall be sent on the S11 interface and S5/S8 interface when the MME receives a report from the ProSe UE-to-Network Relay that a remote UE is newly disconnected.	Remote UE Context	1
		The SGW shall forward this IE to the PGW.		
		Several IEs with the same type and instance value may be included as necessary to represent a list of remote UEs newly disconnected.		
Private Extension	0		Private Extension	VS

 Table 7.2.26-1: Information Elements in Remote UE Report Notification

Octets 1		Remote UE Context IE Type = 191 (decimal)				
Octets 2 and 3		Length = n				
Octets 4		Spare and Instance fields				
Information	Ρ	Condition / Comment	IE Type	Ins.		
elements						
Remote User ID	Μ	See subclause 8.123 for the description and use of this	Remote User ID	0		
		parameter				
Remote UE IP	Μ	See subclause 8.124 for the description and use of this	Remote UE IP	0		
Information		parameter	Information			

 Table 7.2.26-2: Remote UE Context Connected within Remote UE Report Notification

### Table 7.2.26-3: Remote UE Context Disconnected with Remote UE Report Notification

Octets 1		Remote UE Context IE Type = 191 (decimal)			
Octets 2 and 3		Length = n			
Octets 4		Spare and Instance fields			
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.	
Remote User ID		See subclause 8.123 for the description and use of this parameter	Remote User ID	0	

# 7.2.27 Remote UE Report Acknowledge

The Remote UE Report Acknowledge message shall be sent as the response to a Remote UE Report Notification, to acknowledge the information related to the remote UE(s) is received.

Possible Cause values are specified in Table 8.4-1.

Table 7.2.27-1 specifies the presence of IEs in this message.

Table 7.2.27-1: Information Elements in Remote UE Report A	Acknowledge
------------------------------------------------------------	-------------

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

# 7.3 Mobility Management Messages

## 7.3.1 Forward Relocation Request

A Forward Relocation Request message shall be sent from the source MME to the target MME over S10 interface as part of S1-based handover relocation procedure from the source MME to the target SGSN, or from the source SGSN to the target MME over S3 interface as part of Inter RAT handover and combined hard handover and SRNS relocation procedures, or from source SGSN to the target SGSN over S16 interface as part of SRNS Relocation and PS handover procedures.

A Forward Relocation Request message shall also be sent from the source MME to the target SGSN over S3 interface as part of SRVCC from E-UTRAN to UTRAN or GERAN with DTM HO support procedures and from source SGSN to the target SGSN over S16 interface as part of SRVCC from UTRAN (HSPA) to UTRAN or GERAN with DTM HO support.

A source MME/SGSN which supports CIoT knows whether the target MME/SGSN pool supports some CIoT optimisations either by using DNS procedures enhanced for DCNs or by local configuration, as specified in subclause 5.9 of 3GPP TS 29.303 [32]. The target MME/SGSN may forward the Forward Relocation Request to another MME/SGSN in the target MME/SGSN pool which is more suitable to serve the UE, based on the information received in the Forward Relocation Request message, e.g. required CIoT EPS optimisation(s) applicable to the given UE's attachment.

- NOTE 1: The source MME/SGSN does not need to know each individual CIoT feature the target MME/SGSN pool supports. The source MME/SGSN can behave as if the target MME/SGSN pool supports all CIoT features when the target MME/SGSN pool is known to support CIoT; the source MME/SGSN determines then which bearer contexts were successfully transferred as specified in sunclause 7.3.2.
- NOTE 2: Among the CIoT optimization features, only the support of SCEF Non-IP PDN connection and the support of SGi Non-IP PDN connection are applicable to a SGSN.

Forward Relocation procedure across S10 interface (when  $K_{ASME}$  is taken into use) shall be performed according to the Rules on Concurrent Running of Security Procedures, which are specified in 3GPP TS 33.401 [12].

When the source MME/SGSN supports one or more of the CIoT optimization features as specified in subclause 8.125, the source MME/SGSN shall transfer EPS bearer context(s) for SGi Non-IP PDN connections or for PDN connections to a SCEF only if the target serving node is known to support SGi Non-IP PDN connections or SCEF Non-IP PDN connections respectively, as specified in subclause 5.5.1.2.1 and 5.5.2 of 3GPP TS 23.401 [3]. The source MME/SGSN shall not proceed with the Forward Relocation Request procedure if the UE does not have any EPS bearer context(s) for SGi IP or Non-IP PDN connections that can be transferred to the target serving node, i.e. under the following conditions:

- If the UE is attached to the source MME/SGSN with only the PDN connection(s) of PDN type "non-IP" through the SGW and the PGW, with or without SCEF PDN connections, and the target serving node is known to not support SGi Non-IP PDN Connection (as specified in subclause 4.3.17.8.3.3 of 3GPP TS 23.401 [3] and in subclause 5.3.13.8 of 3GPP TS 23 060 [35]).

Table 7.3.1-1 specifies the presence requirements and conditions of the IEs in the message.

Table 7.3.1-1: Information Elements in a Forward Relocation Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	The IMSI shall be included in the message except for the case: - If the UE is emergency attached and the UE is UICCless.	IMSI	0
		The IMSI shall be included in the message but not used as an identifier - if UE is emergency attached but IMSI is not authenticated.		
Sender's F-TEID for Control Plane	М		F-TEID	0
MME/SGSN UE EPS PDN Connections	С	This IE shall be present, except over the S16 interface if there is no active PDP context and the source and target SGSNs supports SRNS relocation w/o PDN connection over GTPv2 (see NOTE 2). If the target MME/SGSN is known to not support SGi Non- IP PDN Connection (as specified in subclause 4.3.17.8.3.3 of 3GPP TS 23.401 [3] and in subclause 5.3.13.8 of 3GPP TS 23 060 [35]), then the source MME/SGSN shall only include PDN Connections of IP PDN type. Several IEs with this type and instance values shall be included as necessary to represent a list of PDN Connections	PDN Connection	0
SGW S11/S4 IP Address and TEID for Control Plane	С	This IE shall be present, except over the S16 interface if there is no active PDP context and the source and target SGSNs supports SRNS relocation w/o PDN connection over GTPv2 (see NOTE 2).	F-TEID	1
SGW node name	С	This IE identifies the SGW that was used by the old MME/S4-SGSN. It shall be included by the source MME/S4-SGSN, except over the S16 interface if there is no active PDP context and the source and target SGSNs supports SRNS relocation w/o PDN connection over GTPv2 (see NOTE 2).	FQDN	0
MME/SGSN UE MM Context	Μ		MM Context	0

Indication Flags	<u> </u>	This IE shall be included if any of the flags are set to 1	Indiantian	0
Indication Flags	С	<ul> <li>This IE shall be included if any of the flags are set to 1.</li> <li>Direct Forwarding Indication: This flag shall be set to 1 if direct forwarding is supported in the S1 based handover procedure. This flag shall not be set to 1 if the message is used for other handover procedures.</li> </ul>	Indication	0
		<ul> <li>Idle mode Signalling Reduction Supported Indication flag: This flag shall be set to 1 if the source MME/SGSN and associated SGW are capable to establish ISR for the UE.</li> </ul>		
		<ul> <li>Unauthenticated IMSI: This flag shall be set to 1 if the IMSI present in the message is not authenticated and is for an emergency attached UE.</li> </ul>		
		<ul> <li>Change Reporting support indication flag: This flag shall be set to 1 if the Source S4-SGSN/MME supports Location Change Reporting mechanism. See NOTE1. See NOTE 3.</li> </ul>		
		<ul> <li>CSG Change Reporting Support Indication flag: This flag shall be set to 1 if the Source S4- SGSN/MME supports CSG Information Change Reporting mechanism. See NOTE1. See NOTE 3.</li> </ul>		
		<ul> <li>Management Based MDT allowed flag: This flag shall be set to 1 for the S1 based inter-MME handover procedure over the S10 interface, if Management Based Minimization of Drive Tests (MDT) is allowed. See 3GPP TS 36.413 [10] and 3GPP TS 32.422 [18].</li> </ul>		
		<ul> <li>CSFB Indication: when configured to support the return to the last used PLMN after CSFB, the MME shall set this flag to 1 on the S3 interface if the PS handover procedure is due to CSFB (see subclause 4.3.2 of 3GPP TS 23.272 [21]). See NOTE 5.</li> </ul>		
		<ul> <li>Pending MT Short Message Indication: This flag shall be set to 1 if the source S4-SGSN/MME knows that there is one (or more) pending MT Short Message(s) in the SMS-GMSC for the UE as specified in subclause 10.1 of 3GPP TS 23.040 [75], Figure 17c). See NOTE 8.</li> </ul>		
E-UTRAN Transparent Container	С	This IE shall be included to contain the "Source to Target Transparent Container", if the message is used for UTRAN/GERAN to E-UTRAN inter RAT handover procedure, E-UTRAN intra RAT handover procedure and 3G SGSN to MME combined hard handover and SRNS relocation procedure. The Container Type shall be set to 3.	F-Container	0
UTRAN Transparent Container	С	This IE shall be included to contain the "Source to Target Transparent Container", if the message is used for PS handover to UTRAN Iu mode procedures, SRNS relocation procedure and E-TURAN to UTRAN inter RAT handover procedure. The Container Type shall be set to 1.	F-Container	1
BSS Container	С	This IE shall be included to contain the "Source BSS to Target BSS Transparent Container" if the message is used for PS handover to GERAN A/Gb mode and E-UTRAN to GERAN A/Gb mode inter RAT handover procedure. The Container Type shall be set to 2.	F-Container	2
Target Identification	С	This IE shall be included if the message is used for SRNS relocation procedure and handover to UTRAN/E-UTRAN procedures.	Target Identification	0

	co	This IE shall be included on the S3 interface if the		
		message is used for PS handover from E-UTRAN to		
	0	GERAN A/Gb mode.		0
HRPD access node	С	This IE shall be included only if the HRPD pre registration	IP-Address	0
S101 IP address	С	was performed at the source MME This IE shall be included only if the 1xRTT CS fallback pre	IP-Address	1
1xIWS S102 IP address	C		IP-Address	1
S1-AP Cause	С	registration was performed at the source MME This IE is the information received from the source	F-Cause	0
ST-AF Cause	C	eNodeB, and the source MME shall include this IE in the	r-Cause	0
		message. Refer to the 3GPP TS 29.010 [42] for the		
		mapping of cause values between S1AP, RANAP and		
		BSSGP.		
RANAP Cause	С	This IE is the information from the source RNC, the source	F-Cause	1
	Ū	SGSN shall include this IE in the message. Refer to the		
		3GPP TS 29.010 [42] for the mapping of cause values		
		between S1AP, RANAP and BSSGP.		
BSSGP Cause	С	This IE is the information received from source BSS, and	F-Cause	2
		the source SGSN shall include this IE in the message.		
		Refer to the 3GPP TS 29.010 [42] for the mapping of		
		cause values between S1AP, RANAP and BSSGP.		
Source Identification	С	This IE shall be included on the S16 interface if the	Source	0
		message is used for PS handover from GERAN/UTRAN to	Identification	
		GERAN A/Gb mode.		
Selected PLMN ID	С	The old MME/SGSN shall include this IE if the selected	PLMN ID	0
		PLMN identity is available. The Selected PLMN ID IE		
		indicates the target core network operator selected for the		
		UE in a shared network.		
Recovery	С	If contacting the peer for the first time	Recovery	0
Trace Information	С	This IE shall be included when session trace is active for	Trace Information	0
		this IMSI/IMEI.		
Subscribed RFSP	co	This IE shall be included during inter-MME/SGSN mobility	RFSP Index	0
Index		procedures, if the source MME/SGSN receives it from an		
	00	HSS.		4
RFSP Index in Use	CO	This IE shall be included only during inter-MME/SGSN	RFSP Index	1
		mobility procedures, if the source MME/SGSN supports the		
CSG ID	<u> </u>	feature. This IE shall be included on the S3/S10/S16 interfaces if	CSG ID	0
CSGID	00	the source MME/SGSN receives it from the source	CSGID	0
		eNodeB/RNC. It indicates the target CSG ID in case of a		
		handover to a CSG cell or hybrid cell.		
CSG Membership	CO	This IE shall be included on the S3/S10/S16 interfaces by	СМІ	0
Indication	00	the source MME/SGSN if the CSG access mode is	C.I.I.	Ŭ
indication		received from the source eNodeB/RNC and indicates the		
		target cell is a hybrid cell, or if the UE has emergency		
		bearer(s) and the target cell is a CSG cell.		
UE Time Zone	CO	When available, this IE shall be included by the source	UE Time Zone	0
		MME/S4-SGSN.		
Serving Network	CO	This IE shall be included to indicate the current Serving	Conving Notwork	0
		Network.	Serving Network	0
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME/S4-SGSN to the peer	Local	0
		MME/S4-SGSN on the S3/S10/S16 interfaces (see 3GPP	Distinguished	
		TS 32.423 [44]), when communicating the LDN to the peer	Name (LDN)	
	1	node for the first time.		
Additional MM	CO	This IE shall be sent by the source MME/S4-SGSN to the	Additional MM	0
context for SRVCC		target MME/S4-SGSN on the S3/S10/S16 interfaces if MS	context for	
		Classmark2, MS Classmark3 and the Supported Codec	SRVCC	
		are available in the source MME/S4-SGSN.		

Additional flags for SRVCC		This IE shall be included if any one of the applicable flags needs to be forwarded. Applicable flags:	Additional flags for SRVCC	0
		<ul> <li>ICS Indicator: This IE shall be sent by the source MME/S4-SGSN to the target MME/S4-SGSN on the S3/S10/S16 interfaces if ICS Indicator is available in the source MME/S4-SGSN.</li> </ul>		
		<ul> <li>vSRVCC flag: This IE shall be sent by the source MME to the target MME on the S10 interface if vSRVCC flag is available in the source MME.</li> </ul>		
STN-SR		This IE shall be sent by the source MME/S4-SGSN to the target MME/S4-SGSN on the S3/S10/S16 interfaces if STN-SR is available in the source MME/S4-SGSN.	STN-SR	0
C-MSISDN	СО	This IE shall be sent by the source MME/S4-SGSN to the target MME/S4-SGSN on the S3/S10/S16 interfaces if C-MSISDN is available in the source MME/S4-SGSN. The C-MSISDN is defined in 3GPP TS 23.003 [2].	MSISDN	0
MDT Configuration	СО	This IE shall be sent by the source MME to the target MME on the S10 interface for the S1-based handover relocation procedure, if the Job Type indicates Immediate MDT. See 3GPP TS 32.422 [18] subclause 4.2.6.	MDT Configuration	0
SGSN node name	СО	This IE shall be sent by the source SGSN on the S3 interface if both source SGSN and associated SGW support ISR. See NOTE 4.	FQDN	1
MME node name		This IE shall be sent by the source MME on the S3 interface if both source MME and associated SGW support ISR. See NOTE 4.	FQDN	2
User CSG Information (UCI)		This IE shall be sent by the source MME/S4-SGSN on the S3/S10/S16 interfaces if the source MME/SGSN has reported to the PGW that the UE is in a CSG or hybrid cell. It shall then contain the last User CSG information that the source MME/S4-SGSN has reported to the PGW. The absence of this IE indicates that the UE has not been reported to the PGW as being in a CSG or hybrid cell. See NOTE 6.	UCI	0
Monitoring Event Information		This IE shall be sent by the source MME/S4-SGSN on the S3/S10/S16 interfaces if monitoring events are to be continued in the target MME/S4-SGSN. More than one IE with this type and instance values may be included to represent multiple monitoring events.	Monitoring Event Information	0
UE Usage Type	CO	This IE shall be set to the subscribed UE Usage Type, if received from the HSS, and sent by the old MME/SGSN on the S3/S10/S16 interfaces if the old MME/SGSN supports the Dedicated Core Networks specified in TS 23.401 [3]. If the UE Usage Type is not available in the old MME/SGSN, the length field of this IE shall be set to 0. See NOTE 7.	Integer Number	0
MME/SGSN UE SCEF PDN Connections		This IE shall be present over the S10/S3/S16 interface if there is at least one SCEF PDN connection for this UE at the source MME/SGSN and if the target MME/SGSN is known to support SCEF Non-IP PDN Connections (as specified in subclause 5.13.1 of 3GPP TS 23.682 [74]). Several IEs with this type and instance values shall be included as necessary to represent a list of SCEF PDN Connections.	SCEF PDN Connection	0
MSISDN		This IE shall be present over the S10/S3/S16 interface if the UE's MSISDN is available and if there is at least one instance of the MME/SGSN UE SCEF PDN Connection IE included in the message.	MSISDN	1

Source LI		$\sim$	If the target MME/SCSN, extended by the source	Port Number	0
Source Ul Number	DP POIL		If the target MME/SGSN, selected by the source MME/SGSN, decides to forward the Forward Relocation	Port Number	0
Number			Request message to another more suitable MME/SGSN in		
			the same MME/SGSN pool, the MME/SGSN shall include		
			this IE, set to the Source UDP Port number of the received		
			message from the source MME/SGSN. The new target		
			MME/SGSN shall use this UDP port as the UDP		
			destination port in the Forward Relocation Response		
Serving D			message. This IC shall be included by the old MMC on \$10 interface.	Conving DLMN	0
	LMN Rate		This IE shall be included by the old MME on S10 interface	Serving PLMN	0
Control			if the Serving PLMN Rate control was enabled when there is at least one SCEF PDN connection. See NOTE 9.	Rate Control	
Drivete Ex	tanaian	0	is at least one SCEP PDN connection. See NOTE 9.	Drivete Extension	VC
Private Ex		-	[2] (a. a. autologica E 2 2 4) and 2CDD TS 22 060 [25] (a. a.	Private Extension	
NOTE 1:			[3] (e.g. subclause 5.3.2.1) and 3GPP TS 23.060 [35] (e.g.		
			/SGSN shall send the MS Info Change Reporting Support In		
			SGSN shall use the Change Reporting Support Indication a		
			ort Indication (whichever is applicable), even if stage 2 refers	s to MS Into Change	e
			ort Indication.	CONe (between w	hiah
NOTE 2.			used for SRNS relocation w/o PDN connection if all the S4-S can take place) support this optional GTPv2 procedure. Oth		
			cedure (see subclause 7.10). The S4-SGSN can know by lo		lii be
			S4-SGSNs support this procedure.	carconniguration	
NOTE 2			Il ignore the per UE Change Reporting Support Indication a	nd CSC Change	
NOTE 3.			ort Indication flags, as included within the Indication Flags IE		
			N connection i.e. within the Indication Flags IE of the MME/S		
	Connections			SON OL LI ST DI	N
			3GPP TS 23.401 [3], during an inter-RAT handover procedu	ure for a LIE with IS	P
NOTE 4.			urce MME/SGSN should select the ISR associated CN node		
			inter RAT HO when the ISR associated CN node can serve		
			hanged when ISR is being activated and used in the source		
			bsequent inter-RAT handover.		15
NOTE 5:			ds to include the last used LTE PLMN ID in the Equivalent F	21 MNI liet it conde to	tho
NOTE 5.			S 23.272 [21]), the SGSN shall derive the last used LTE PL		
	Network IE.				iving
NOTE 6:			ks, when the message is sent from the VPLMN to the HPLM	IN the PI MN ID th	at is
NOTE 0.			this IE shall be that of the selected Core Network Operator		
			ted Core Network Operator for non-supporting UEs. As an e		
			aming/sharing agreement, if the information on whether the		
			JE is available, the PLMN ID that is communicated to the HF		
			Common PLMN ID.		orung
			ks, when the MME/S4-SGSN and PGW pertain to the same	PI MN the Primar	v
			e communicated in the ECGI to the PGW, and the Common		y
			SAI/CGI to the PGW, for both supporting and non-supporti		
			or PLMN ID (selected by the UE for supporting UEs or alloca		for
			JEs) shall be communicated in the TAI, RAI, UCI and the Se		101
			.4 of 3GPP TS 23.251 [55].	in mighterwork.	
NOTE 7			e IE with the length field equal to 0 is used for the receiver t	o differentiate the c	ase
NOTE 7.			r does not support the Dedicated Core Network feature from		
			the Dedicated Core Network feature but no UE Usage type		
	subscription		and Dealeated Colo Notiven loadere but no OE Coage type		
NOTE 8.			pending MT Short Message at the SMS-GMSC during a har	ndover scenario wł	hen
			a Service Request towards the source MME/SGSN and a h		
			terward, before the SMS-GMSC is alerted to retransmit the		,
	Message.	uy al		pending wir Shoft	
NOTE 9:		лм⊨	may compare the value of the Serving PLMN Rate Control	received in the For	ward
			est message with the one configured locally, to determine if		
			rds the SCEF. The Serving PLMN Rate Control does not ap		
	Connection				•
L		arun	o mooodyo.		

The PDN Connection grouped IE shall be coded as depicted in Table 7.3.1-2.

Table 7.3.1-2: MME/SGSN UE EPS PDN Connections within Forward Relocation Request

204

Octet 1		PDN Connectio	n IE T	Гуре	= 109 (decimal)			1		
Octets 2 and 3										
Octet 4	_				ce fields		·	-		
Information elements	Ρ	Condi	tion /	Cor	nment	ІЕ Туре	Ins.			
<b>N</b> N	Μ					APN	0		APN Restriction	
		APN Restriction         C         This IE denotes the restriction on the combination of types of APN for the APN associated with this EPS bearer Context. The target MME or SGSN determines the Maximum APN Restriction using the APN Restriction. If available, the source MME/S4SGSN shall include this IE.								0
		Selection Mode	CC		/hen available, this IE sha IME/S4-SGSN	all be included by th	ne soui	rce	Selection Mode	0
Pv4 Address		This IE shall not be inclu assigned. See NOTE 1.				IP Address	0			
Pv6 Address		This IE shall not be inclu assigned.				IP Address	1			
inked EPS Bearer ID		This IE identifies the defactor of the connection.				EBI	0			
GW S5/S8 IP ddress for Control lane or PMIP	М	This IE shall include the case and the uplink GRE case. See NOTE 4.				F-TEID	0			
'GW node name	С	This IE shall be included the PGW FQDN.	if the	e sou	rce MME or SGSN has	FQDN	0			
Bearer Contexts		Several IEs with this type included as necessary to				Bearer Context	0			
Aggregate Maximum Bit Rate (APN-AMBR)	М					AMBR	0			
harging haracteristics	С	This IE shall be present supplied by the HSS to t subscription information.	he MN			Charging characteristics	0			
Change Reporting		This IE shall be included MME/SGSN. See NOTE	5.			Change Reporting Action				
SG Information		This IE shall be included MME/SGSN.				CSG Information Reporting Action	0			
l(e)NB Information रeporting	со	This IE shall be included MME/SGSN.	when	neve	r available at the source	H(e)NB Information Reporting	0			
ndication Flags	CO	flag shall be se supports Locati and if the S4-S support for the mechanism to t establishment a See NOTE 2.	ing su to 1 if on Ch GSN/N Locatio he PG and/or	uppo if the nang MME ion C GW, r moo	rt indication flag: This e Source S4-SGSN/MME e Reporting mechanism E has indicated the Change Reporting during the session dification procedures.	Indication	0			
		This flag shall b SGSN/MME su Reporting mech has indicated th Change Report session establis procedures. Se - Delay Tolerant flag shall be se by the source M	e set t pports nanism e sup ing to shmen e NOT Conne t to 1 c 1ME/S	to 1 s CS m an oport the nt an TE 2 ectio on th SGSI	Support Indication flag: if the Source S4- G Information Change d if the S4-SGSN/MME for the CSG Informatoin PGW, during the ad/or modification 2. on Indication flag: This he S3/S10/S16 interface N if the PGW indicated his delay tolerant.					
		shall be set to 1	on S ^r and th	610 ir	ndication flag: This flag nterface by the source ource MME support					

Signalling Priority	со	The source SGSN/MME shall include this IE if the UE indicated low access priority when establishing the PDN	Signalling Priority Indication	0
		connection.		
Change to Report	со	This IE shall be included by the SGSN if any one of the applicable flags is set to 1. See NOTE3. Applicable flags:	Change to Report Flags	0
		<ul> <li>Serving Network Change to Report: This flag shall be set to 1 if the source SGSN has detected a Serving Network change during a RAU procedure without SGSN change but has not yet reported this change to the PGW.</li> </ul>		
		<ul> <li>Time Zone Change to Report: This flag shall be set to 1 if the source SGSN has detected a UE Time Zone change during a RAU procedure without SGSN change but has not yet reported this change to the PGW.</li> </ul>		
.ocal Home Network D	со	This IE shall be sent over the S3/S10/S16 interface if SIPTO at the Local Network is active for the PDN connection in the SIPTO at the Local Network architecture with stand-alone GW.	FQDN	1
Presence Reporting Area Action	СО	This IE shall be included if the PGW requested the source MME/SGSN to report changes of UE presence in a Presence Reporting Area. The source MME/SGSN shall include the Presence Reporting Area Identifier and, if received from the PGW, the list of the Presence Reporting Area elements.	Presence Reporting Area Action	0
		Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. One IE shall be included for each Presence Reporting Area.		
VLAN Offloadability ndication	CO	If the MME/SGSN supports WLAN/3GPP Radio Interworking with RAN rules then this IE shall be included on S3/S10/S16 if the UE has been authorized to perform WLAN offload for at least one RAT.	WLAN Offloadability Indication	0
Remote UE Context	СО	The source MME shall include this IE on the S10 interface during an inter MME mobility procedure if such information is available. Several IEs with the same type and instance value may be included as necessary to represent a list of remote UEs connected.	Remote UE Context	0
'DN Type		The source MME/SGSN shall include this IE on the S10/S3/S16 interface, for a Non-IP PDN Connection, during an inter MME/SGSN mobility procedure, if the target MME/SGSN supports SGi Non-IP PDN connections.	PDN Type	0
leader Compression Configuration	CO	This IE shall be sent over the S10 interface if the use of IP Header Compression for Control Plane CloT EPS optimisations has been negotiated with the UE and the target MME is known to support CloT EPS optimisations.	Header Compression Configuration	0

10TE 1:	For deferred IPv4 address allocation, if the MME/S4-SGSN receives the PDN address "0.0.0.0" from
	PGW during "eUTRAN Initial Attach", "PDP Context Activation", "UE requested PDN Connectivity",
	then the MME/S4-SGSN shall include this IPv4 address "0.0.0.0".
JOTE 2:	3GPP TS 23.401 [3] (e.g. subclause 5.3.2.1) and 3GPP TS 23.060 [35] (e.g. subclause 9.2.2.1)
	defines the MME/SGSN shall send the MS Info Change Reporting Support Indication to the PGW. In
	such case MME/SGSN shall use the Change Reporting Support Indication and/or CSG Change
	Reporting Support Indication (whichever is applicable), even if stage 2 refers to MS Info Change
	Reporting Support Indication.
JOTE 3	When UE is camping on the 3G and performs a Service Request procedure, as specified in the
	subclause 6.12.1 of 3GPP TS 23.060 [35], if Service Type indicates Signalling, the signalling
	connection is established between the MS and the SGSN for sending upper-layer signalling
	messages, e.g. Activate PDP Context Request, but the resources for active PDP context(s) are not
	allocated, therefore the change of Serving Network or UE Time zone may not be reported to
	SGW/PGW for the existing PDP Contexts.
JOTE 4:	For PMIP based S5/S8, the 'PGW S5/S8 IP Address and TEID for user plane' IE and the 'PGW
	S5/S8 IP Address for Control Plane or PMIP' IE shall contain the same uplink GRE key; the Interface
	Type in these IEs shall be set to the value 9 (S5/S8 PGW PMIPv6 interface).
JOTE 5:	The target MME (respectively S4-SGSN) shall ignore this IE if it is received from an S4-SGSN
	(respectively an MME), i.e. over the S3 interface. In this case, the target serving node shall consider

(respectively an MME), i.e. over the S3 interface. In this case, the target serving node shall consider that no ULI change reporting is requested by the PGW for the target RAT, and the PGW shall request the target serving node to start ULI change reporting for the target RAT if so desired.

The Bearer Context grouped IE shall be coded as depicted in Table 7.3.1-3.

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
EPS Bearer ID	М		EBI	0
	C	This IE shall be present if a TFT is defined for this bearer.		-
TFT SGW S1/S4/S12 IP	-	See NOTE2.	Bearer TFT F-TEID	0
Address and TEID for user plane	IVI	See NOTE2.		0
PGW S5/S8 IP	С	This IE shall be present for GTP based S5/S8	F-TEID	1
Address and TEID for user plane				
Bearer Level QoS	Μ		Bearer QoS	0
BSS Container		The MME/S4 SGSN shall include the Packet Flow ID, Radio Priority, SAPI, PS Handover XID parameters in the TAU/RAU/Handover procedure, if available. See Figure 8.48-2. The Container Type shall be set to 2.	F-Container	0
Transaction Identifier		This IE shall be sent over S3/S10/S16 if the UE supports A/Gb and/or Iu mode.	TI	0
Bearer Flags	CO	<ul> <li>Applicable flags: <ul> <li>vSRVCC indicator: This IE shall be sent by the source MME to the target MME on the S10 interface if vSRVCC indicator is available in the source MME.</li> <li>ASI (Activity Status Indicator): the source S4-SGSN shall set this indicator to 1 on the S16 interface if the bearer context is preserved in the CN without an associated RAB.</li> </ul> </li> </ul>	Bearer Flags	0
S5/S8 IP Ad Type in the separate IP F-TEID in th in SGW S1 MME shall i	ddres se IE add ne S( 1 IP nclue	S5/S8, the 'PGW S5/S8 IP Address and TEID for user plan ss for Control Plane or PMIP' IE shall contain the same uplin ss shall be set to the value 9 (S5/S8 PGW PMIPv6 interface) ress spaces are used for S1-U and S11-U, the MMEs shall i GW S1/S4/S12/S11 IP Address and TEID for user plane IE a Address and TEID for user plane, when they are available; o de the SGW S1/S4/S12/S11 IP Address and TEID for user p FEID are the same.	k GRE key; the Inte . NOTE 2: When nclude both S1-U S and S11-U SGW F- therwise, the source	erface GW TEID ce

# Table 7.3.1-3: Bearer Context within MME/SGSN UE EPS PDN Connections within Forward Relocation Request

# Table 7.3.1-4: Remote UE Context Connected within MME/SGSN UE EPS PDN Connections within Forward Relocation Request

Octets 1		Remote UE Context IE Type = 191 (decimal)						
Octets 2 and 3		Length = n						
Octets 4		Spare and Instance fields						
Information elements	Ρ	Condition / Comment	IE Type	Ins.				
Remote User ID		See subclause 8.123 for the description and use of this parameter	Remote User ID	0				
Remote UE IP Information		See subclause 8.124 for the description and use of this parameter	Remote UE IP Information	0				

Octets 1		SCEF PDN Connection IE Type = 195 (decimal)						
Octets 2 and 3		Length = n						
Octets 4		Spare and Instance fields						
Information	Ρ	Condition / Comment	IE Type	Ins.				
elements								
APN	Μ		APN	0				
Default EPS Bearer	Μ	This IE shall identify the default bearer of the SCEF PDN	EBI	0				
ID		Connection.						
SCEF ID	Μ	This IE shall include the SCEF Identifier and the SCEF	Node Identifier	0				
		Realm for the APN.						

 Table 7.3.1-5: MME UE SCEF PDN Connections within Forward Relocation Request

# 7.3.2 Forward Relocation Response

A Forward Relocation Response message shall be sent as a response to Forward Relocation Request during S1-based handover procedure, Inter RAT handover procedures, SRNS Relocation procedure and PS handover procedures.

Based on the List of Set-up Bearers IE and the List of Set-up Bearers for SCEF PDN Connections IE in the Forward Relocation Response, the source MME shall determine whether the bearer contexts for SGi (IP or Non-IP) or SCEF PDN connections were successfully transferred to the target MME, and initiate procedures to release the SCEF PDN connections which were not successfully handed over.

Table 7.3.2-1 specifies the presence requirements and conditions of the IEs in the message.

Cause IE indicates if the relocation has been accepted, or not. The relocation has not been accepted by the target MME/SGSN if the Cause IE value differs from "Request accepted". Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Relocation failure".

Table 7.3.2-1: Information Elements in a Forward Relocation Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Sender's F-TEID for Control Plane	С	If the Cause IE contains the value "Request accepted", the target MME/SGSN shall include this IE in Forward Relocation Response message.	F-TEID	0
Indication Flags	С	This IE shall be included if any of the flags are set to 1. SGW Change Indication: - This flag shall be set to 1 if the target MME/SGSN has selected a new SGW.	Indication	0
List of Set-up Bearers		The list of set-up Bearers IE contains the EPS bearer Identifiers of the Bearers that were successfully allocated in the target system during a handover procedure. This IE shall be included if the source and target access type is EUTRAN and the Cause IE contains the value "Request accepted". See NOTE 1. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers.	Bearer Context	0
List of Set-up RABs	С	<ul> <li>The list of set-up RABs IE contains the RAB Identifiers of the RABs that were successfully allocated in the target system. This IE shall be included if the Cause IE contains the value "Request accepted" and <ul> <li>If the source access type is UTRAN and the target access type is E-UTRAN/UTRAN,</li> <li>If the source access type is E-UTRAN and the target access type is UTRAN,</li> <li>If the source access type is UTRAN,</li> <li>Request did not include the MME/SGSN UE EPS PDN Connections IE.</li> <li>See NOTE 1.</li> </ul> </li> <li>Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers.</li> </ul>	Bearer Context	1
List of Set-up PFCs	0	The list of set-up PFCs IE contains the Packet Flow Identifies of the PFCs that were successfully allocated in the target system during a PS handover to/from GERAN or inter RAT handover to/from GERAN. If the Cause IE contains the value "Request accepted", this IE may be included. See NOTE 1. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers.	Bearer Context	2
S1-AP Cause	С	This IE is included if cause value is contained in S1-AP message. Refer to the 3GPP TS 29.010 [42] for the mapping of cause values between S1AP, RANAP and BSSGP.	F-Cause	0
RANAP Cause		This IE is included if cause value is contained in RANAP message. Refer to the 3GPP TS 29.010 [42] for the mapping of cause values between S1AP, RANAP and BSSGP.	F-Cause	1
BSSGP Cause		For handover to GERAN, if a cause value is received from the Target BSC, the BSSGP Cause IE shall be included and shall be set to the cause value received from the target BSC. Refer to the 3GPP TS 29.010 [42] for the mapping of cause values between S1AP, RANAP and BSSGP.	F-Cause	2
E-UTRAN Transparent Container		This IE shall be included to contain the "Target to Source Transparent Container" during a handover to E-UTRAN. If the Cause IE contains the value "Request accepted". The Container Type shall be set to 3.	F-Container	0
UTRAN Transparent Container	С	This IE shall be included to contain the "Target to Source Transparent Container" during a handover to UTRAN. If the Cause IE contains the value "Request accepted". The Container Type shall be set to 1.	F-Container	1

BSS Container	С	This IE shall be included to contain the Target BSS to	F-Container	2
DSS Container	C	Source BSS Transparent Container during a handover to	F-Container	~
		GERAN. If the Cause IE contains the value "Request		
		accepted". The Container Type shall be set to 2		
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME/S4-SGSN to the peer	Local	0
IVIIVIE/34-303IN LDIN	0	MME/S4-SGSN on the S3/S10/S16 interfaces (see 3GPP	Distinguished	0
		TS 32.423 [44]), when communicating the LDN to the peer	Name (LDN)	
		node for the first time.	Name (LDN)	
SGSN node name	<u> </u>	This IE shall be sent by the target SGSN on the S3	FQDN	0
SGSN houe hame	00	interface if both target SGSN and associated SGW support		0
		ISR. See NOTE 2.		
MME node name	<u> </u>	This IE shall be sent by the target MME on the S3 interface	FQDN	1
MIME Hode hame	00	if both target MME and associated SGW support ISR. See	FQDN	1
		NOTE 2.		
SGSN Number	0	This IE may be sent by the target S4-SGSN to the source	Node Number	0
SGSIN NULLBEI	0	MME/S4-SGSN as specified in 3GPP TS 23.271 [56].	Node Number	0
	<u> </u>	This IE shall be included if the PMTSMI flag in the Forward		
	00	Relocation Request message is set to 1.		
SGSN Identifier	0	This IE may be sent by the target S4-SGSN to the source	Node Identifier	0
SGSN identilier	0	MME/S4-SGSN as specified in 3GPP TS 23.271 [56].	node identilier	0
MME Identifier	0	This IE may be sent by the target MME to the source	Node Identifier	1
	0	MME/S4-SGSN as specified in 3GPP TS 23.271 [56].	Node Identilier	
MME number for MT	0	This IE shall be included if the PMTSMI flag in the Forward	Node Number	1
SMS	00		Node Number	1
SGSN Identifier for	0	Relocation Request message is set to 1. This IE shall be included if the target S4-SGSN supports	Node Identifier	2
MT-SMS	00	the Gdd reference point and if the PMTSMI flag in the	Node Identilier	2
1011-31013		Forward Relocation Request message is set to 1.		
MME Identifier for MT	<u> </u>	This IE shall be included if the target MME supports the	Node Identifier	3
SMS	00	SGd reference point and if the PMTSMI flag in the Forward		3
31013		Relocation Request message is set to 1.		
List of Set-up Bearers	<u> </u>	This IE shall contain the EPS bearer Identifiers of the	Bearer Context	3
for SCEF PDN	00	Bearers of SCEF PDN connections that were successfully	Dealer Context	3
Connections		allocated in the target system during a handover		
Connections		procedure.		
		Several IEs with this type and instance values shall be		
		included as necessary to represent a list of Bearers.		
Private Extension	0		Private Extension	VS
	-	Relocation Request message, the inclusion of "RAN Cause"		
access type is E-UTRAN. In the Forward Relocation Request message, the inclusion of "RANAP Cause" indicates that the source access type is UTRAN. In the Forward Relocation Request				
message, the inclusion of "BSSGP Cause" indicates that the source access type is GERAN.				
NOTE 2: According to the 3GPP TS 23.401 [3], during an inter-RAT handover procedure for a UE with ISR				
activated, the source MME/SGSN should select the ISR associated CN node for this UE as the target				
		inter RAT HO when the ISR associated CN node can serve		
		changed when ISR is being activated and used in the source		
		ubsequent inter-RAT handover.		

Bearer Context IE in this message is specified in Table 7.3.2-2, the source system shall use this IE for data forwarding in handover.

Octet 1		Bearer Context IE Type = 93 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information	Ρ	Condition / Comment	ІЕ Туре	Ins.			
elements							
EPS Bearer ID	С	This IE shall be included if the message is used for S1-	EBI	0			
		Based handover procedure.					
		This IE shall be included if the message is used for SRNS					
		relocation procedure and Inter RAT handover to/from lu					
	~	mode procedures.					
Packet Flow ID	С	This IE shall be included if the message is used for PS	Packet Flow ID	0			
		handover and Inter RAT handover to/from A/Gb mode					
	С	procedures.	F-TEID	0			
eNodeB F-TEID for DL data forwarding	C	This IE shall be included for the message sent from the target MME, if the DL Transport Layer Address and DL	F-TEID	0			
DL uata ioi waruling		GTP TEID are included in the "SAE Bearers Admitted List"					
		of the S1AP: HANDOVER REQUEST ACKNOWLEDGE					
		and direct forwarding or indirect forwarding without SGW					
		change is applied.					
eNodeB F-TEID for	0	This IE may be included for the message sent from the	F-TEID	1			
UL data forwarding		target MME during the intra-EUTRAN HO, if the UL					
5		Transport Layer Address and UL GTP TEID are included in					
		the "SAE Bearers Admitted List" of the S1AP: HANDOVER					
		REQUEST ACKNOWLEDGE and direct forwarding or					
		indirect forwarding without SGW change is applied.					
SGW F-TEID for DL	С	This SGW F-TEID shall be included when indirect data	F-TEID	2			
data forwarding		forwarding with SGW change is applied.					
RNC F-TEID for DL	С	This RNC F-TEID shall be included in the message sent	F-TEID	3			
data forwarding		from SGSN, if the target system decides using RNC F-					
	_	TEID for data forwarding.		<u> </u>			
SGSN F-TEID for DL	С	This SGSN F-TEID shall be included in the message sent	F-TEID	4			
data forwarding		from SGSN, if the target system decides using SGSN F-					
	~	TEID for data forwarding.		_			
SGW F-TEID for UL	0	If available this SGW F-TEID may be included when	F-TEID	5			
data forwarding		indirect data forwarding with SGW change is applied, during the intra-EUTRAN HO.					
	l atoya		Boaror ID IE	L			
NOTE: The Bearer Context IE for an SCEF PDN connection shall only contain the EPS Bearer ID IE.							

#### Table 7.3.2-2: Bearer Context

# 7.3.3 Forward Relocation Complete Notification

A Forward Relocation Complete Notification message shall be sent to the source MME/SGSN to indicate the handover has been successfully finished.

Table 7.3.3-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Indication Flags		This IE shall be included if any of the flags are set to 1. Idle mode Signalling Reduction Activation Indication: This flag shall be set to 1 if the message is used for inter RAT handover and the UE has ISR capability. This flag is set to indicate to the source MME/SGSN whether it shall maintain the UE's context and whether it shall activate ISR.	Indication	0
Private Extension	0		Private Extension	VS

# 7.3.4 Forward Relocation Complete Acknowledge

A Forward Relocation Complete Acknowledge message shall be sent as a response to Forward Relocation Complete Notification during inter eNodeB handover with MME relocation procedure, SRNS Relocation with SGSN change procedures using S4 or Inter RAT Handover with MME/S4 SGSN interaction procedures.

Table 7.3.4-1 specifies the presence requirements and conditions of the IEs in the message.

Possible Cause values are specified in Table 8.4-1.

#### Table 7.3.4-1: Information Elements in a Forward Relocation Complete Acknowledge

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	0		Recovery	0
Private Extension	0		Private Extension	VS

## 7.3.5 Context Request

The new MME/SGSN shall send the Context Request message to the old MME/SGSN on S3/S16/S10 interface as a part of TAU/RAU procedure and UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure to get the MM and EPS bearer Contexts for the UE.

NOTE 1: During UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43], the GUTI, RAI IE, P-TMSI IE and P-TMSI Signature IE, are not received directly from the UE but from the MSC Server over Sv interface.

If the sending/new node is a MME, it shall include in the Context Request message:

- the GUTI IE and Complete TAU Request Message IE, if the GUTI or the indication of mapped or native GUTI received from UE indicates the old node is a MME, as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2].
- the RAI IE and the P-TMSI IE, which are derived from the GUTI received from UE, and the P-TMSI Signature that was received intact from the UE, if the GUTI or the indication of mapped or native GUTI indicates the old node is an SGSN as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2].

If the sending/new node is an SGSN, it shall include RAI IE, P-TMSI IE and P-TMSI Signature IE in the Context Request message. If the receiving/old node is an MME, it shall construct GUTI according to the RAI IE, P-TMSI IE and P-TMSI Signature IE (see the mapping relationship between RAI, P-TMSI, P-TMSI signature and GUTI defined in 3GPP TS23.003[2]), and find UE context via this GUTI.

The new MME differentiates the type of the old node as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2]. If the old node is an SGSN, the GUTI shall be mapped to RAI and P-TMSI by the new MME; if the old node is a MME, the new MME include GUTI IE and Complete TAU Request Message IE in the Context Request message. The Mapping between temporary and area identities is defined in 3GPP TS 23.003 [2].

The Target PLMN ID IE shall be used in old SGSN/MME in order to decide whether un-used authentication vectors to be distributed to new SGSN/MME or not. Distribution and use of authentication vectors between different serving network domains are specified in 3GPP TS 33.401 [12].

Table 7.3.5-1 specifies the presence requirements and conditions of the IEs in the message.

Table 7.3.5-1: Information Elements in a Context Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	IMSI shall be included if the UE has been successfully authenticated.	IMSI	0
GUTI	C CO	The New MME shall include this IE over S10 interface. This IE shall be included over S10 interface if available during UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43].	GUTI	0
Routeing Area Identity(RAI)	C CO	This IE shall be included over S3/S16 interface, if the GUTI or the indication of mapped or native GUTI indicates the old node is an SGSN, the new MME maps this IE from GUTI. This IE shall be included over S3/S16 interface if available during UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43].	ULI (NOTE 4)	0
Packet TMSI(P-TMSI)	C CO	This IE shall be included over S3/S16 interface. For the S3 interface, if sent by the MME, this IE is derived by the MME from the GUTI received from the UE. This IE shall be included over S3/S16 interface if available during UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43].	P-TMSI	0
P-TMSI Signature	C CO	This IE shall be included over S3/S16 interface if it is received from the UE. This IE shall be included over S3/S16 interface if available during UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43].	P-TMSI Signature	0
Complete TAU	С	The new MME shall include this IE if available, and the old	Complete	0
request message S3/S16/S10 Address and TEID for Control Plane	С	MME may use this IE for integrity check. See NOTE 3. This IE specifies the address and the TEID for control plane message which is chosen by the new MME/SGSN. In case of SGSN pool, the IPv4 or the IPv6 address field shall be set to the same value of the Source IP address of the IP packet carrying this message, and the relaying SGSN shall not change the content of this IE when sending it to the old SGSN. See NOTE 1.	Request Message F-TEID	0
UDP Source Port Number	С	If an SGSN within the same SGSN pool as the old SGSN receives this message, the SGSN shall include the UDP Source Port number of the received message in this parameter if this IE is not present and relay the message to the old SGSN. The old SGSN shall use this UDP port as the UDP destination port of the Context Response message.	Port Number	0
RAT Type	С	The RAT Type indicates the Radio Access Technology which is used in the new system.	RAT Type	0
Indication		<ul> <li>his IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable Flags are: <ul> <li>The MS Validated (MSV) flag, when set to 1, indicates that the new system has successfully authenticated the UE, or the new system has validated the integrity protection of the TAU request message. See NOTE 3.</li> </ul> </li> </ul>	Indication	0
Hop Counter		If an SGSN within the same SGSN pool with the old SGSN receives this message, the SGSN shall decrement the Hop Counter if this IE is present in the received message; otherwise, the SGSN may include a Hop Counter with a value of max-1, and may relay the message to the old SGSN.		0
Target PLMN ID	со	If available, this IE shall be included in order to allow old MME/SGSN to make a judgment whether un-used authentication vectors to be distributed or not.	Serving Network	0
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME/S4-SGSN to the peer MME/S4-SGSN on the S3/S10/S16 interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	0

SGSN node name       CO       This IE shall be sent by the new SGSN on the S3 interface if both new SGSN and associated SGW support ISR. See NOTE 2.       FQDN       (0)         MME node name       CO       This IE shall be sent by the new MME on the S3 interface if both new MME and associated SGW support ISR. See NOTE 2.       FQDN       (1)         SGSN Number       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Number       (1)         SGSN Identifier       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Identifier       (1)
NOTE 2.       MME node name       CO       This IE shall be sent by the new MME on the S3 interface if both new MME and associated SGW support ISR. See NOTE 2.       FQDN         SGSN Number       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Number       O         SGSN Identifier       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Identifier       O
MME node name       CO       This IE shall be sent by the new MME on the S3 interface if both new MME and associated SGW support ISR. See NOTE 2.       FQDN         SGSN Number       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Number       O         SGSN Identifier       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Identifier       O
both new MME and associated SGW support ISR. See NOTE 2.         NOTE 2.           SGSN Number         O         This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].         Node Number         O           SGSN Identifier         O         This IE may be sent by the target S4-SGSN to the source         Node Identifier         O
NOTE 2.         NOTE 2.           SGSN Number         O         This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].         Node Number         O           SGSN Identifier         O         This IE may be sent by the target S4-SGSN to the source         Node Identifier         O
SGSN Number       O       This IE may be sent by the target S4-SGSN to the source MME/S4-SGSN as specified in 3GPP TS 23.271 [56].       Node Number       O         SGSN Identifier       O       This IE may be sent by the target S4-SGSN to the source       Node Identifier       O
MME/S4-SGSN as specified in 3GPP TS 23.271 [56].           SGSN Identifier         O           This IE may be sent by the target S4-SGSN to the source         Node Identifier
SGSN Identifier O This IE may be sent by the target S4-SGSN to the source Node Identifier (
MME/S4 SGSN as specified in 2GDD TS 22 271 [56]
MME/S4-SGSN as specified in 3GPP TS 23.271 [56].
MME Identifier O This IE may be sent by the target MME to the source Node Identifier
MME/S4-SGSN as specified in 3GPP TS 23.271 [56].
CloT Optimizations CO This IE shall be sent by the new MME/SGSN on the CloT (
Support Indication S10/S3/S16 interface if it supports at least one CloT Optimizations
optimization. Support Indication
Private Extension O Private Extension V
NOTE 1: The relaying SGSN shall forward the Context Request message to the interface of the old SGSN,
where the interface type is matching what is indicated in the IE S3/S16/S10 Address and TEID for
Control Plane.
NOTE 2: According to the 3GPP TS 23.401 [3], during an inter-RAT handover procedure for a UE with ISR
activated, the source MME/SGSN should select the ISR associated CN node for this UE as the targ
CN node for the inter RAT HO when the ISR associated CN node can serve the target access. This
parameter is exchanged when ISR is being activated and used in the source MME/SGSN for this
decision upon subsequent inter-RAT handover.
NOTE 3: The Complete TAU request message IE is available except during UTRAN/GERAN to E-
UTRAN/UTRAN (HSPA) SRVCC procedure as specified in 3GPP TS 23.216 [43]. In these
procedures, the new MME shall set the Indication IE MSV (MS Validated) flag to 1.
NOTE 4: Only RAI field in the ULI IE type shall be present in the Routeing Area Identity (RAI) IE.

# 7.3.6 Context Response

A Context Response message shall be sent as a response to a previous Context Request message during TAU/RAU procedure and UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "IMSI/IMEI not known"
- "P-TMSI Signature mismatch"
- "User authentication failed"
- "Target access restricted for the subscriber"

Based on the subscription profile, when the access to the target RAT is prohibited for the subscriber, the old MME/SGSN may reject the Context Request message with the cause "Target access restricted for the subscriber".

When the source MME/SGSN supports one or more of the CIoT optimization features as indicated through the CIoT Optimizations Support Indication IE specified in subclause 8.125, and if the target node is a MME and the target MME has not set the AWOPDN bit of the CIoT Optimizations Support Indication IE set to 1 in the Context Request message as specified in subclause 8.125, the source MME/SGSN shall reject the Context Request with a cause value of "Request Rejected" under the following conditions (conditions are mutually exclusive):

- If the UE is attached to the source MME/SGSN without any PDN connection through the SGW and PGW and without any SCEF PDN connection.
- If the UE is attached to the source MME/SGSN with only the PDN connection(s) of PDN type "non-IP", through the SGW and the PGW but the UE has not activated any SCEF PDN connection and the target MME has not set the SGNIPDN bit of the CIoT Optimizations Support Indication IE set to 1 in the Context Request message as specified in subclause 8.125.
- If the UE is attached to the source MME/SGSN with only the SCEF PDN connection(s) but the UE has not activated any PDN connection through the SGW and PGW and the target MME has not set the SCNIPDN bit of the CIoT Optimizations Support Indication IE set to 1 in the Context Request message as specified in subclause 8.125.

- If the UE is attached to the source MME/SGSN with only PDN connection(s) of PDN type "non-IP", through the SGW and the PGW and at least one SCEF PDN connection and the target MME has neither set the SGNIPDN bit nor the SCNIPDN bit of the CIoT Optimizations Support Indication IE set to 1 in the Context Request message as specified in subclause 8.125.
- NOTE 2: Among the CIoT optimization features, only the support of SCEF Non-IP PDN connection and the support of SGi Non-IP PDN connection are applicable to a SGSN.

Table 7.3.6-1 specifies the presence requirements and conditions of the IEs in the message.

Table 7.3.6-1: Information Elements in a Context Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
IMSI	C	The IMSI shall be included in the message except for the case: - If the UE is emergency attached and the UE is	IMSI	0
		UICCless. The IMSI shall be included in the message but not used as		
		an identifier - if UE is emergency attached but IMSI is not authenticated.		
MME/SGSN UE MM Context	С	This IE shall be included if the Cause IE has the value " Request Accepted ".	MM Context	0
MME/SGSN UE EPS PDN Connections	С	This IE shall be included if there is at least a PDN connection for this UE through the SGW and PGW on the sending MME/SGSN. If the target MME/SGSN has not set the SGNIPDN bit of	PDN Connection	0
		the CloT Optimizations Support Indication IE to 1 in the Context Request, then the source MME/SGSN shall only include PDN Connections of IP PDN type (if any). Several IEs with this type and instance values shall be		
		included as necessary to represent a list of PDN Connections.		
Sender F-TEID for Control Plane	С	This IE shall be included if the Cause IE has the value "Request Accepted".	F-TEID	0
SGW S11/S4 IP	С	This IE shall be included if a SGW is being used by the old	F-TEID	1
Address and TEID for	•	MME/SGSN, except if:		
Control Plane		<ul> <li>the source and target MME/S4-SGSN support the MME/S4-SGSN triggered SGW restoration procedure, and the source MME/S4-SGSN has not</li> </ul>		
		<ul> <li>performed the SGW relocation procedure after the source SGW has failed as specified in 3GPP TS 23.007 [17].</li> <li>across the S16 interface if there is no active PDP</li> </ul>		
		context <ul> <li>across the S10 interface the UE does not have any PDN connection through the SGW and PGW</li> </ul>		
SGW node name	С	This IE identifies the SGW that was used by the old MME/SGSN and it shall be included by the source MME/S4-SGSN with the following exceptions:	FQDN	0
		<ul> <li>the source and target MME/S4-SGSN support the MME/S4-SGSN triggered SGW restoration procedure, and the source MME/S4-SGSN has not</li> </ul>		
		performed the SGW relocation procedure after the source SGW has failed as specified in 3GPP TS 23.007 [17]. - across the S16 interface if there is no active PDP		
		<ul> <li>across the S16 interface in there is no active PDP context</li> <li>across the S10 interface the UE does not have any PDN connection through the SGW and PGW</li> </ul>		

Indication Flags	С	This IE shall be included if any of the flags are set to 1.	Indication	0
		Idle mode Signalling Reduction Supported Indication: - This flag shall be set to 1 if the Cause IE value indicates "Request accepted" and the old system (including old MME/SGSN and the associated SGW) has the ISR capability.		
		Unauthenticated IMSI: - This flag shall be set to 1 if the IMSI present in the message is not authenticated and is for an emergency attached UE.		
		Change Reporting support indication flag: - This flag shall be set to 1 if the Source S4- SGSN/MME supports Location Change Reporting mechanism. See NOTE 1. See NOTE 2.		
		CSG Change Reporting support indication flag: - This flag shall be set to 1 if the Source S4- SGSN/MME supports CSG Information Change Reporting mechanism. See NOTE 1. See NOTE 2.		
		ISRAU: - This flag shall be set to 1 on S10/S16 interface if the ISR is activated for the UE before the UE moving to the new SGSN/MME.		
		Management Based MDT allowed flag: - This flag shall be set to 1 for the inter-MME TAU procedure over the S10 interface, if Management Based Minimization of Drive Tests (MDT) is allowed. See 3GPP TS 36.413 [10] and 3GPP TS 32.422 [18].		
		SGW Restoration Needed Indication (SRNI): - This flag shall be set to 1 if both source and target MME/S4-SGSN support the MME/S4-SGSN triggered SGW restoration procedure and the source MME/S4-SGSN has not performed the SGW relocation procedure after the source SGW has failed as specified in 3GPP TS 23.007 [17].		
		<ul> <li>CSFB Indication (CSFBI):</li> <li>when configured to support the return to the last used PLMN after CSFB, the MME shall set this flag to 1 on the S3 interface if the UE has been subject to CSFB recently (see subclause 4.3.2 of 3GPP TS 23.272 [21]). See NOTE 4.</li> </ul>		
		Buffered DL Data Waiting Indication (BDWI): - This flag shall be set to 1 on the S3/S10/S16 interface, during TAU/RAU with or without SGW change procedures, when it is required to forward to the UE DL data buffered in the (old) SGW, i.e. when the DL Data Buffer Expiration Time has not expired yet in the old MME/SGSN, as specified in subclause 4.3.17.7 of 3GPP TS 23.401 [3].		
		<ul> <li>Pending MT Short Message Indication (PMTSMI):</li> <li>This flag shall be set to 1 if the source S4- SGSN/MME knows that there is one (or more) pending MT Short Message(s) in the SMS-GMSC for the UE as specified in subclause 10.1 of 3GPP TS 23.040 [75], Figure 17c).</li> </ul>		
Trace Information HRPD access node	C C	This IE shall be included when session trace is active for this IMSI/IMEI. This IE shall be included only if the HRPD pre registration	Trace Information IP-Address	0
S101 IP address		was performed at the old MME		0

1xIWS S102 IP address	С	This IE shall be included only if the 1xRTT CS fallback pre registration was performed at the old MME	IP-Address	1
Subscribed RFSP Index	со	This IE shall be included only during inter-MME/SGSN mobility procedures, if the source MME/SGSN receives it from an HSS.	RFSP Index	0
RFSP Index in Use	со	This IE shall be included only during inter-MME/SGSN mobility procedures, if the source MME/SGSN supports the feature.	RFSP Index	1
UE Time Zone	CO	When available, this IE shall be included by the source MME/S4-SGSN.	UE Time Zone	0
MME/S4-SGSN LDN	0	This IE is optionally sent by the MME/S4-SGSN to the peer MME/S4-SGSN on the S3/S10/S16 interfaces (see 3GPP TS 32.423 [44]), when communicating the LDN to the peer node for the first time.	Local Distinguished Name (LDN)	0
MDT Configuration	со	This IE shall be sent by the source MME to the target MME on the S10 interface for inter-MME TAU procedure, if the Job Type indicates Immediate MDT. See 3GPP TS 32.422 [18] subclause 4.2.6.	MDT Configuration	0
SGSN node name	CO	This IE shall be sent by the old SGSN on the S3 interface if both old SGSN and associated SGW support ISR. See NOTE 3.	FQDN	1
MME node name	СО	This IE shall be sent by the old MME on the S3 interface if both old MME and associated SGW support ISR. See NOTE 3.	FQDN	2
User CSG Information (UCI)	CO	This IE shall be sent by the source MME/S4-SGSN on the S3/S10/S16 interfaces if the source MME/SGSN has reported to the PGW that the UE is in a CSG or hybrid cell. It shall then contain the last User CSG information that the source MME/S4-SGSN has reported to the PGW. The absence of this IE indicates that the UE has not been reported to the PGW as being in a CSG or hybrid cell. See NOTE 5.	UCI	0
Monitoring Event Information	CO	This IE shall be sent by the source MME/S4-SGSN on the S3/S10/S16 interfaces if monitoring events are to be continued in the target MME/S4-SGSN. More than one IE with this type and instance values may be included to represent multiple monitoring events.	Monitoring Event Information	0
UE Usage Type	СО	This IE shall be set to the subscribed UE Usage Type, if received from the HSS, and sent by the old MME/SGSN on the S3/S10/S16 interfaces if the old MME/SGSN supports the Dedicated Core Networks feature specified in TS 23.401 [3]. If the UE Usage Type is not available in the old MME/SGSN, the length field of this IE shall be set to 0. See NOTE 6.	Integer Number	0
MME/SGSN UE SCEF PDN Connections	С	This IE shall be included if there is at least one SCEF PDN connection for this UE at the source MME/SGSN and if the target MME/SGSN has set the SCNIPDN bit of the CloT Optimizations Support Indication IE to 1 in the Context Request as specified in subclause 8.125. Several IEs with this type and instance values shall be included as necessary to represent a list of SCEF PDN Connections.	SCEF PDN Connection	0
RAT Type	СО	This IE shall be included by the source MME or SGSN on the S10, S16 and S3 interface to indicate the old RAT type where the UE was camping. See NOTE 7.	RAT Type	0
Serving PLMN Rate Control	CO	This IE shall be included by the old MME on the S10 interface if such Serving PLMN Rate control was enabled when there is at least one SGi or SCEF PDN connection with the Control Plane Only Indication set. See NOTE 8.	Serving PLMN Rate Control	0
MO Exception Data Counter	CO	This IE shall be included on the S10 interfaces if the source MME has not yet reported a non-zero MO Exception Data Counter to the PGW. The timestamp in the counter shall be set with the time at which the counter value increased from 0 to 1.	Counter	0
Private Extension	0		Private Extension	VS

- NOTE 1: 3GPP TS 23.401 [3] (e.g. subclause 5.3.2.1) and 3GPP TS 23.060 [35] (e.g. subclause 9.2.2.1) defines the MME/SGSN shall send the MS Info Change Reporting Support Indication to the PGW. In such case MME/SGSN shall use the Change Reporting Support Indication and/or CSG Change Reporting Support Indication (whichever is applicable), even if stage 2 refers to MS Info Change Reporting Support Indication.
- NOTE 2: The receiver shall ignore the per UE Change Reporting Support Indication and CSG Change Reporting Support Indication flags, as included within the Indication Flags IE above, if these flags are included per PDN connection i.e. within the Indication Flags IE of the MME/SGSN UE EPS PDN Connections IE.
- NOTE 3: According to the 3GPP TS 23.401 [3], during an inter-RAT handover procedure for a UE with ISR activated, the source MME/SGSN should select the ISR associated CN node for this UE as the target CN node for the inter RAT HO when the ISR associated CN node can serve the target access. This parameter is exchanged when ISR is being activated and used in the source MME/SGSN for this decision upon subsequent inter-RAT handover.
- NOTE 4: If the SGSN needs to include the last used LTE PLMN ID in the Equivalent PLMN list it sends to the UE (see 3GPP TS 23.272 [21]), the SGSN shall derive the last used LTE PLMN ID from the Old RAI IE received in the RAU request message.
- NOTE 5: In shared networks, when the message is sent from the VPLMN to the HPLMN, the PLMN ID that is communicated in this IE shall be that of the selected Core Network Operator for supporting UEs, or that of the allocated Core Network Operator for non-supporting UEs. As an exception, based on inter-operator roaming/sharing agreement, if the information on whether the UE is a supporting or non-supporting UE is available, the PLMN ID that is communicated to the HPLMN for non-supporting UEs shall be the Common PLMN ID.

In shared networks, when the MME/S4-SGSN and PGW pertain to the same PLMN, the Primary PLMN ID shall be communicated in the ECGI to the PGW, and the Common PLMN ID shall be communicated in SAI/CGI to the PGW, for both supporting and non-supporting UEs. The Core Network Operator PLMN ID (selected by the UE for supporting UEs or allocated by the network for non-supporting UEs) shall be communicated in the TAI, RAI, UCI and the Serving Network. See subclause 4.4 of 3GPP TS 23.251 [55].

- NOTE 6: A UE Usage Type IE with the length field equal to 0 is used for the receiver to differentiate the case where the sender does not support the Dedicated Core Network feature from the case where the sender supports the Dedicated Core Network feature but no UE Usage type was received in UE's subscription.
- NOTE 7: The old RAT shall be used by the target MME/SGSN to determine if the RAT type has changed and, if so, to decide whether to maintain or deactivate the PDN connections of the UE based on the PDN-Connection-Continuity subscription parameter and operator policy, as specified in 3GPP TS 23.401 [3] and 3GPP TS 23.060 [35]. A target MME shall consider that the RAT type has changed if the target RAT is NB-IoT and a source MME (complying with an earlier version of the specification) does not include the RAT Type IE in the Context Response.
- NOTE 8: The target MME may compare the value of the Serving PLMN Rate Control received in the Context Response message with the one configured locally, to determine if such parameter needs to be updated towards the SCEF and/or PGW.

Table 7.3.6-2: MME/SGSN UE EPS PDN Connections within Context Response

Octet 1		PDN Connection IE Type = 109 (decimal)						
Octets 2 and 3		Length = n						
Octet 4		Spare and Instance fields						
Information elements	Ρ	Condition / Comment		ІЕ Туре	Ins.			
\PN	Μ			APN	0			
		APN Restriction C This IE denotes the re of APN for the APN as Context. The target MI Maximum APN Restrict If available, the source IE.	n. this	APN Restriction	0			
		Selection Mode CO When available, this IE MME/S4-SGSN	E sha	Il be included by the	e sour	ce	Selection Mode	0
Pv4 Address		This IE shall not be included if no IPv4 Address is assigned. See NOTE 1. See NOTE 5.		IP Address	0			
Pv6 Address	С	This IE shall not be included if no IPv6 Address is assigned. See NOTE 5.		IP Address	1			
inked EPS Bearer ID	М	M This IE identifies the default bearer of the PDN EBI 0 Connection.						
GW S5/S8 IP ddress for Control lane or PMIP	М	This IE shall include the TEID in the GTP based S5/S8 case and the uplink GRE key in the PMIP based S5/S8 case. See NOTE 3.		F-TEID	0			
'GW node name	С	This IE shall be included if the source MME or SGSN h the PGW FQDN.	nas	FQDN	0			
Bearer Contexts	М	Several IEs with this type and instance values may be included as necessary to represent a list of Bearers.		Bearer Context	0			
Aggregate Maximum Bit Rate (APN-AMBR)	Μ			AMBR	0			
Charging haracteristics		This IE shall be present if charging characteristics was supplied by the HSS to the MME/SGSN as a part of subscription information.		Charging characteristics	0			
Change Reporting	С	This IE shall be included whenever available at the sou MME/SGSN. See NOTE 4.	urce	Change Reporting Action	0			
SG Information	со	This IE shall be included whenever available at the sou MME/SGSN.	urce	CSG Information Reporting Action	0			
I(e)NB Information Reporting	СО	This IE shall be included whenever available at the sou MME/SGSN.	urce	H(e)NB Information Reporting	0			

ndication flags	co	This IE shall be included if any one of the applicable flags is set to 1.	Indication	0
		<ul> <li>Applicable flags:</li> <li>Subscribed QoS Change Indication: This flag shall be set to 1 if the subscribed QoS profile of the related PDN connection has changed in the old MME/SGSN when the UE is in ECM-IDLE state and ISR is activated.</li> </ul>		
		- Change Reporting support indication flag: This flag shall be set to 1 if the Source S4-SGSN/MME supports Location Change Reporting mechanism and if the S4-SGSN/MME has indicated the support for the Location Change Reporting mechanism to the PGW, during the session establishment and/or modification procedures. See NOTE 2.		
		<ul> <li>CSG Change Reporting Support Indication flag: This flag shall be set to 1 if the Source S4- SGSN/MME supports CSG Information Change Reporting mechanism and if the S4-SGSN/MME has indicated the support for the CSG Information Change Reporting to the PGW, during the session establishment and/or modification procedures. See NOTE 2.</li> </ul>		
		- Pending Subscription Change Indication flag: This flag shall be set to 1 on the S3/S10 interface if the source MME has received Subscribed QoS profile updates for QCI/ARP/APN-AMBR from the HSS but has deferred the reporting of these updates to the PGW/PCRF because the UE was not reachable.		
		<ul> <li>Pending Network Initiated PDN Connection Signalling Indication flag: This flag shall be set to 1 on the S3/S10/S16 interface by the source MME/SGSN if there is pending network initiated signalling for the PDN connection.</li> </ul>		
		<ul> <li>Delay Tolerant Connection Indication flag: This flag shall be set to 1 on the S3/S10/S16 interface by the source MME/SGSN if the PGW indicated that this PDN Connection is delay tolerant.</li> </ul>		
		<ul> <li>Extended PCO Support Indication flag: This flag shall be set to 1 on S10 interface by the source MME if the UE and the source MME support Extended PCO.</li> </ul>		
		<ul> <li>Control Plane Only PDN Connection Indication: This flag shall be set to 1 if the PDN Connection is set to Control Plane Only.</li> </ul>		
ignalling Priority	со	The source SGSN/MME shall include this IE if the UE indicated low access priority when establishing the PDN connection.	Signalling Priority Indication	0

hange to Report	CO	This IE shall be included by the MME/SGSN if any one of	Change To	0
lags		the applicable flags is set to 1.	Report Flags	
		Applicable flags: - Serving Network Change to Report: This flag shall		
		be set to 1 if the source MME/SGSN has detected		
		a Serving Network change during a TAU/RAU		
		procedure without MME/SGSN change but has not yet reported this change to the PGW.		
		yet reported this change to the PGW.		
		- Time Zone Change to Report: This flag shall be set		
		to 1 if the source MME/SGSN has detected a UE Time Zone change during a TAU/RAU procedure		
		without MME/SGSN change but has not yet		
		reported this change to the PGW.		
.ocal Home Network	со	This IE shall be sent over the S3/S10/S16 interface if	FQDN	1
D		SIPTO at the Local Network is active for the PDN		
		connection in the SIPTO at the Local Network architecture		
vresence Reporting	co	with stand-alone GW. This IE shall be included if the PGW requested the source	Presence	0
vrea Action		MME/SGSN to report changes of UE presence in a	Reporting Area	Ũ
		Presence Reporting Area. The source MME/SGSN shall	Action	
		include the Presence Reporting Area Identifier and, if received from the PGW, the list of the Presence Reporting		
		Area elements.		
		Several IEs with the same type and instance value may be		
		included as necessary to represent a list of Presence		
		Reporting Area Actions. One IE shall be included for each		
VLAN Offloadability	CO	Presence Reporting Area. If the MME/SGSN supports WLAN/3GPP Radio	WLAN	0
ndication	00	Interworking with RAN rules then this IE shall be included	Offloadability	Ŭ
		on S3/S10/S16 if the UE has been authorized to perform	Indication	
Remote UE Context	CO	WLAN offload for at least one RAT. The source MME shall include this IE on the S10 interface	Remote UE	0
Connected		during an inter MME mobility procedure if such information	Context	Ũ
		is available.		
		Several IEs with the same type and instance value may be included as necessary to represent a list of remote UEs		
		connected.		
'DN Type	со	The source MME/SGSN shall include this IE on the	PDN Type	0
		S10/S3/S16 interface, for a Non-IP PDN Connection, during an inter MME/SGSN mobility procedure if new		
		MME/SGSN supports non-IP PDN connection using SGi		
	00	as indicated in the Context Request message.	l la sala a	
leader Compression Configuration	00	This IE shall be sent over the S10 interface if the use of IP Header Compression for Control Plane CloT EPS	Header Compression	0
, en ligeren en liger		optimisations has been negotiated with the UE and the	Configuration	
		target MME has set the IHCSI bit of the CloT Optimizations		
		Support Indication IE to 1 in the Context Request as specified in subclause 8.125.		
JOTE 1: For deferre	d IPv	4 address allocation, if the MME/S4-SGSN receives the PDI	N address "0.0.0.0"	from
		JTRAN Initial Attach", "PDP Context Activation", "UE request	ed PDN Connectiv	ity",
		4-SGSN shall include this IPv4 address "0.0.0.0". 1 [3] (e.g. subclause 5.3.2.1) and 3GPP TS 23.060 [35] (e.g.	subclause 9.2.2 1	
defines the	MME	E/SGSN shall send the MS Info Change Reporting Support In	ndication to the PG	W. In
		/SGSN shall use the Change Reporting Support Indication a		
		ort Indication (whichever is applicable), even if stage 2 refers ort Indication.	s to IVIS INTO Change	e
JOTE 3: For PMIP b	ased	S5/S8, the 'PGW S5/S8 IP Address and TEID for user plane		
		ss for Control Plane or PMIP' IE shall contain the same uplin		erface
		is shall be set to the value 9 (S5/S8 PGW PMIPv6 interface). (respectively S4-SGSN) shall ignore this IE if it is received f		
(respectivel	y an	MME), i.e. over the S3 interface. In this case, the target service	ving node shall con	sider
		nge reporting is requested by the PGW for the target RAT, ar		
		et serving node to start ULI change reporting for the target R I connections, neither an IPv4 address nor an IPv6 address s		

The Bearer Context shall be coded as depicted in Table 7.3.6-3.

Table 7.3.6-3: Bearer Context within MME/SGSN UE EPS PDN Connections within Context Response
----------------------------------------------------------------------------------------------

Octet 1		Bearer Context IE Type = 93					
Octets 2 and 3		Length = n					
Octet 4		Sparae and Instance fields					
Information elements	n P	Condition / Comment	ІЕ Туре	Ins.			
EPS Bearer ID	М		EBI	0			
TFT	C	This IE shall be present if a TFT is defined for this bearer.	Bearer TFT	0			
SGW S1/S4/S12	-	The IE shall be present except if:	F-TEID	0			
IP Address and T		- the source and target MME/S4-SGSN support the	I ILID	Ŭ			
for user plane		MME/S4-SGSN triggered SGW restoration procedure, and the source MME/S4-SGSN has not performed the SGW relocation procedure after the					
		SGW has failed as specified in 3GPP TS 23.007 [17].					
		See NOTE 2 and NOTE3.					
PGW S5/S8 IP	C		F-TEID	1			
Address and TEI	D for CC	For PMIP-based S5/S8, this IE shall be included if the					
user plane		PGW provided an alternate address for user plane, i.e. an IP address for user plane which is different from the IP					
		address for control plane.					
		When present, this IE shall contain the alternate IP					
		address for user plane and the uplink GRE key.					
		See NOTE 1.					
Bearer Level Qo	S M		Bearer QoS	0			
BSS Container	CC	The MME/S4 SGSN shall include the Packet Flow ID,	F-Container	0			
		Radio Priority, SAPI, PS Handover XID parameters in the					
		TAU/RAU/Handover procedure, if available. The Container Type shall be set to 2.					
Transaction Iden	tifier C	This IE shall be sent over S3/S10/S16 if the UE supports A/Gb and/or Iu mode.	ΤI	0			
SGW S11 IP Add	dress CC	This IE shall be present if available. See NOTE 3.	F-TEID	2			
and TEID for use	er						
plane							
		d S5/S8, the 'PGW S5/S8 IP Address and TEID for user plane ss for Control Plane or PMIP' IE shall contain the same uplin					
		Es shall be set to the value 9 (S5/S8 PGW PMIPv6 interface).		mace			
		set the interface type in this IE to 1, i.e "S1-U SGW GTP-U in		and			
		This is done for backwards compatibility reasons, when the t					
		T optimizations.	0 0 0				
NOTE 3: When	separate	IP address spaces are used for S1-U and S11-U, the MME s					
		the SGW S1/S4/S12/S11 IP Address and TEID for user plan					
TEID i	n SGW S	11 IP Address and TEID for user plane, when they are availa	ble; otherwise, the				
		all include the SGW S1/S4/S12/S11 IP Address and TEID fo	r user plane IE, sin	се			
S1-U a	and S11-	J SGW F-TEID are the same.					

#### Table 7.3.6-4: Remote UE Context Connected within MME/SGSN UE EPS PDN Connections within Context Response

Octets 1		Remote UE Context IE Type = 191 (decimal)					
Octets 2 and 3		Length = n					
Octets 4		Spare and Instance fields					
Information elements	Ρ	Condition / Comment	IE Type	Ins.			
Remote User ID	М	See subclause 8.123 for the description and use of this parameter	Remote User ID	0			
Remote UE IP Information	М	See subclause 8.124 for the description and use of this parameter	Remote UE IP Information	0			

Octets 1		SCEF PDN Connection IE Type = x (decimal)						
Octets 2 and 3		Length = n						
Octets 4		Spare and Instance fields						
Information	Ρ	Condition / Comment	IE Type	Ins.				
elements								
APN	Μ		APN	0				
Default EPS Bearer	Μ	This IE identifies the default bearer of the SCEF PDN	EBI	0				
ID		Connection.						
SCEF ID	Μ	This IE shall include the SCEF Identifier and the SCEF	Node Identifier	0				
		Realm for the APN.						

Table 7.3.6-5: MME/SGSN UE SCEF PDN Connections within Context Response

# 7.3.7 Context Acknowledge

A Context Acknowledge message shall be sent as a response to a previous Context Response message, only if the previous Context Response message is received with the acceptance cause.

Possible cause values are specified in Table 8.4-1. Message specific cause values are:

- "User authentication failed".
- "Relocation failure due to NAS message redirection".
- "Denied in RAT".

Upon receiving cause value other than the request was accepted, the old MME/S4-SGSN shall continue as if the Context Request was never received.

Table 7.3.7-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	М		Cause	0
Indication flags	C	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable Flags are: <ul> <li>SGW Change Indication: This flag shall be set to 1 on the S3/S10/S16 interfaces if a new SGW has been selected. The old MME/old SGSN marks in its context that the information in the GWs and the HSS are invalid.</li> <li>Idle mode Signalling Reduction Activation Indication: If set to 1, this flag indicates to the old system that it shall maintain the UE's contexts. This flag shall be set to 1 on the S3 interface if the Cause IE value indicates "Request accepted" and ISR is activated as specified in 3GPP TS 23.401 [3].</li> </ul> </li> <li>See NOTE1.</li> </ul>	Indication	0
Forwarding F-TEID	CO	<ul> <li>This IE shall be included if only one bearer context was transferred in the Context Response message and data forwarding of DL data buffered in the old SGW is required, i.e. when the BDWI flag is set in the Context Response message and the SGW is changed, during TAU/RAU procedure with SGW change and data forwarding as specified in the subclause 5.3.3.1A of 3GPP TS 23.401 [3]. The interface type of the Forwarding F-TEID should be set to either: <ul> <li>23 ("SGW GTP-U interface for DL data forwarding") for indirect forwarding,</li> <li>0 (" S1-U eNodeB GTP-U interface") or 3 ("S12 RNC GTP-U interface"), if the eNB or RNC supports such forwarding, or</li> <li>15 ("S4 SGSN GTP-U interface").</li> </ul> </li> </ul>	F-TEID	0
Bearer Contexts	со	This IE shall be included if multiple bearer contexts were transferred in the Context Response message and data forwarding of DL data buffered in the old SGW is required, i.e. when the BDWI flag is set in the Context Response message and the SGW is changed, during TAU/RAU procedure with SGW change and data forwarding as specified in the subclause 5.3.3.1A of 3GPP TS 23.401 [3]. Several IEs with this type and instance value may be included as necessary to represent a list of Bearers.	Bearer Context	0
SGSN Number	CO	This IE shall be included if the PMTSMI flag in the Context Response message is set to 1.	Node Number	0
MME number for MT SMS	СО	This IE shall be included if the PMTSMI flag in the Context Response message is set to 1.	Node Number	1
SGSN Identifier for MT SMS		This IE shall be included if the target S4-SGSN supports the Gdd reference point and if the PMTSMI flag in the Context Response message is set to 1.	Node Identifier	0
MME Identifier for MT SMS		This IE shall be included if the target MME supports the SGd reference point and if the PMTSMI flag in the Context Response message is set to 1.	Node Identifier	1
		In Flags, the combination (SGW Change Indication, Idle modes shall be considered as an error if received.	Private Extension le signalling Activati	VS ion

Table 7.3.7-1: Information Elements in a Context Acknowledge

Octet 1		Bearer Context IE Type = 93 (decimal)				
Octets 2 and 3		Length = n				
Octet 4		Spare and Instance fields				
Information elements	Ρ	Condition / Comment	IE Type	Ins.		
EPS Bearer ID	Μ		EBI	0		
Forwarding F-TEID	М	<ul> <li>The interface type of the Forwarding F-TEID should be set to either:</li> <li>23 ("SGW GTP-U interface for DL data forwarding") for indirect forwarding,</li> <li>0 (" S1-U eNodeB GTP-U interface") or 3 ("S12 RNC GTP-U interface"), if the eNB or RNC supports such forwarding, or</li> <li>15 ("S4 SGSN GTP-U interface").</li> </ul>	F-TEID	0		

Table 7.3.7-2: Bearer Context within Context Acknowledge

## 7.3.8 Identification Request

If the UE identifies itself with temporary identity and it has changed SGSN/MME since detach in Attach procedure, the new MME/SGSN shall send an Identification Request message to the old SGSN/MME over S3, S16 or S10 interface to request IMSI.

Table 7.3.8-1 specifies the presence requirements and conditions of the IEs in the message.

If the sending/new node is a MME, it shall include in the Identification Request message:

- the GUTI IE and Complete Attach Request Message IE, if the GUTI or the indication of mapped or native GUTI received from UE indicates the old node is a MME, as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2].
- the RAI P-TMSI, which was derived from the GUTI received from UE, and the P-TMSI Signature that was received intact from the UE, if the GUTI or the indication of mapped or native GUTI indicates the old node is an SGSN as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2].

If the sending/new node is an SGSN, it shall include RAI IE, P-TMSI IE and P-TMSI Signature IE in the Identification Request message. If the receiving/old node is an MME, it shall construct GUTI according to the RAI IE, P-TMSI IE and P-TMSI Signature IE (see the mapping relationship between RAI, P-TMSI, P-TMSI signature and GUTI defined in 3GPP TS23.003[2]), and find UE context via this GUTI.

The new MME differentiates the type of the old node as specified in subclause 2.8.2.2.2 of 3GPP TS 23.003 [2]. If the old node is an SGSN, the GUTI shall be mapped to RAI and P-TMSI by the new MME; if the old node is a MME, the new MME include GUTI IE and Complete Attach Request Message IE in the Identification Request message. The Mapping between temporary and area identities is defined in 3GPP TS 23.003 [2].

The GUTI IE shall not coexist with any of the RAI IE, P-TMSI IE and P-TMSI Signature IE in an Identification Request message. If this occurs, the receiving node shall return a corresponding cause value in the response message.

The Target PLMN ID IE shall be used in old SGSN/MME in order to decide whether un-used authentication vectors to be distributed to new SGSN/MME or not. Distribution and use of authentication vectors between different serving network domains are specified in 3GPP TS 33.401 [12].

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
GUTI	С	The new MME shall include this IE over S10 interface.	GUTI	0
Routeing Area	С	This IE shall be included over S3/S16 interface, if the GUTI	ULI (NOTE 1)	0
Identity(RAI)		or the indication of mapped or native GUTI received from		
		the UE indicates the old node is an SGSN, the new MME		
		maps this IE from GUTI.		
Packet TMSI(P-TMSI)	С	This IE shall be included over S3/S16 interface. For the S3	P-TMSI	0
		interface, if sent by the MME, this IE is derived by the MME		
		from the GUTI received from the UE.		
P-TMSI Signature	С	This IE shall be included over S3/S16 interface, if it is	P-TMSI Signature	0
		received from the UE.		
Complete Attach	С	The new MME shall include this IE over S10 interface, and	Complete	0
Request Message		the old MME may use this IE for integrity check.	Request Message	
Address for Control	0	If an SGSN within the same SGSN pool with the old SGSN	IP Address	0
Plane		receives this message, the SGSN shall include the old IP		
		address of the received message in this optional		
		parameter if this IE is not present and relay the message to		
		the old SGSN.		
UDP Source Port	С	If an SGSN within the same SGSN pool as the old SGSN	Port Number	0
Number		receives this message, the SGSN shall include the UDP		
		Source Port number of the received message in this		
		parameter if this IE is not present and relay the message to		
		the old SGSN. The old SGSN shall use this UDP port as		
		the UDP destination port of the Identification Response		
		message.		
Hop Counter	0	If an SGSN within the same SGSN pool with the old SGSN	Hop Counter	0
		receives this message, the SGSN shall decrement the Hop		
		Counter if this IE is present in the received message;		
		otherwise, the SGSN may include a Hop Counter with a		
		value of max-1, and may relay the message to the old		
	-	SGSN.		
Target PLMN ID	со	If available, this IE shall be included in order to allow old	Serving Network	0
		MME/SGSN to make a judgment whether un-used		
		authentication vectors to be distributed or not.		
Private Extension	-	None	Private Extension	VS
NOTE 1: Only RAI fie	ld in	the ULI IE type shall be present in the Routeing Area Identit	ty (RAI) IE.	

Table 7.3.8-1: Information Elements in an Identification Request

# 7.3.9 Identification Response

The old SGSN/MME shall send an Identification Response message to the new MME/SGSN as a response to a previous Identification Request message over S3/S10/S16 interface.

Table 7.3.9-1 specifies the presence requirements and conditions of the IEs in the message.

For Intra Domain Connection of RAN Nodes to Multiple CN Nodes, if an old SGSN within an SGSN pool receives an Identification Request message that contains the optional parameter Address for Control Plane, the old SGSN shall use this address as destination IP address of the Identification Response message.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "P-TMSI Signature mismatch"
- "User authentication failed"

Only the Cause information element shall be included in the response if the Cause contains another value than "Request accepted".

Information	Р	Condition / Comment	ІЕ Туре	Ins.
elements	N.4		Causa	0
Cause	M		Cause	0
IMSI	С	This IE shall be included over the S10/S3/S16 interface if	IMSI	0
		the Cause contains the value "Request accepted".		
MME/SGSN UE MM	С	This IE shall be included over the S10/S3/S16 interface if	MM Context	0
Context		the integrity check or the P-TMSI signature check for the		
		Attach Request succeeds.		
Trace Information	CO	This IE shall be included over the S10/S3/S16 interface	Trace Information	0
		when session trace is active for this IMSI/IMEI.		
UE Usage Type	CO	This IE shall be set to the subscribed UE Usage Type, if	Integer Number	0
5 ,1		received from the HSS, and sent by the old MME/SGSN on		
		the S3/S10/S16 interfaces if the old MME/SGSN supports		
		the Dedicated Core Networks specified in TS 23.401 [3].		
		If the UE Usage Type is not available in the old		
		MME/SGSN, the length field of this IE shall be set to 0.		
		See NOTE 1.		
Monitoring Event	co	This IE shall be sent by the source MME/S4-SGSN on the	Monitoring Event	0
Information	00	S3/S10/S16 interfaces if monitoring events are to be	Information	U
Information		continued in the target MME/S4-SGSN.	mormation	
		More than one IE with this type and instance values may		
Drivets Extension	~	be included to represent multiple monitoring events.	Drivets Estancian	1/0
Private Extension	0		Private Extension	VS
NOTE 1: A UE Usage Type IE with the length field equal to 0 is used for the receiver to differentiate the case				
		er does not support the Dedicated Core Network feature from		
sender supports the Dedicated Core Network feature but no UE Usage type was received in UE's				
subscription	۱.			

Table 7.3.9-1: Information Elements in an Identification Response

# 7.3.10 Forward Access Context Notification

A Forward Access Context Notification message shall be sent from the Old SGSN to the New SGSN over the S16 interface to forward the RNC contexts to the target system, or sent from the Old MME to the New MME over the S10 interface to forward the RNC/eNodeB contexts to the target system.

When the old SGSN receives the RANAP message Forward SRNS Context, the old SGSN shall send a Forward Access Context Notification message to the new SGSN. The new SGSN shall forward the message to the target RNC using the corresponding RANAP message.

When the old SGSN receives a BSSGP message PS handover Required and the acknowledged peer-to-peer LLC operation is used for the Bearer Context or when "delivery order" is set in the Bearer Context QoS profile, the old SGSN shall send a Forward Access Context Notification message with the PDU Number IE to the new SGSN. The new SGSN shall forward the message to the target RNC/ target BSS using the corresponding RANAP message only for PS handover to Iu mode.

When the old SGSN receives a BSSGP message PS handover Required from source BSS/RNC for PS handover to A/Gb mode, the value part of RAB Context IE shall be empty according to its defined minimum length.

Table 7.3.10-1 specifics the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
RAB Contexts	С	This IE shall be included for S16 only. Several IEs with this type and instance values shall be included as necessary to represent a list of Bearers. For each RAB context in the received RANAP message, the old SGSN shall include this IE in the message.	RAB Context	0
Source RNC PDCP context Info	С	If available, the old SGSN shall include an Source RNC PDCP context info in the message.	Source RNC PDCP context Info	0
PDU Numbers	С	This IE only applies to S16. The old SGSN shall include this IE in the message if the acknowledged peer-to-peer LLC operation is used for the Bearer Context or when "delivery order" is set in the Bearer Context QoS profile in A/Gb mode to lu/A/Gb mode PS handover.	PDU Numbers	0
E-UTRAN Transparent Container	С	This IE shall be included over S10 to contain the "eNB Status Transfer Transparent Container" as specified in3GPP TS 36.413 [10]. Container Type shall be set to 3.	F-Container	0
Private Extension	0		Private Extension	VS

 Table 7.3.10-1: Information Elements in a Forward Access Context Notification

# 7.3.11 Forward Access Context Acknowledge

A Forward Access Context Acknowledge message shall be sent to the old MME/SGSN as a response to Forward Access Context Notification.

Possible Cause values are specified in Table 8.4-1.

Table 7.3.11-1 specifics the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

# 7.3.12 Detach Notification

A Detach Notification message shall be sent from an MME to the associated SGSN, or from an SGSN to the associated MME as a part of Detach procedure if the ISR is activated between the MME and SGSN for the UE.

Possible Cause values are:

- "Local Detach".
- "Complete Detach".

A Detach Notification message shall also be sent from an SGSN to the associated MME as a part of Detach procedure if the ISR is activated between the MME and SGSN for the UE.

Possible Cause values are:

- "IMSI Detach only".

"Local Detach" indicates that this detach is local to the MME/SGSN and so the associated SGSN/MME registration where the ISR is activated shall not be detached. The MME/SGSN that receives this message including this Cause value of "Local Detach" only deactivates the ISR. This Cause value shall be included in the procedures:

- MME/SGSN-initiated Detach Procedure in case of implicit detach.

"Complete Detach" indicates both the MME registration and the SGSN registration that the ISR is activated for, shall be detached. This "Complete Detach" Cause value shall be included in the procedures:

- UE-initiated Detach Procedure.
- MME/SGSN-initiated Detach Procedure in case of explicit detach.

For the purpose of SGs handling, the SGSN shall include Detach Type in the Detach Notification message for "Complete Detach" when the UE is combined IMSI/EPS attached and the ISR is activated.

Possible Detach Type values are:

- "PS Detach".
- "Combined PS/CS Detach".

"PS Detach" indicates that the MME shall perform explicit IMSI detach from EPS service as specified in section 5.4, 3GPP TS 29.118 [22]. "Combined PS/CS detach" indicates that the MME shall perform explicit IMSI detach from non-EPS service as specified in section 5.5, 3GPP TS 29.118 [22].

"IMSI Detach only" indicates that combined IMSI/EPS attached UE initiates IMSI only GPRS detach from non-GPRS service as specified in section 4.7.4.1, 3GPP TS 24.008 [5], and both the SGSN/MME registration shall be remained. The MME shall perform explicit IMSI detach from non-EPS service for the SGs handling purpose, which is specified in section 5.5, 3GPP TS 29.118 [22]. This "IMSI Detach only" Cause value shall be included in the procedures:

- UE-initiated Detach Procedure for GERAN/UTRAN for "IMSI Detach only".

Table 7.3.12-1 specifics the presence of the IEs in the message.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Detach Type		This IE shall be included by SGSN when the Cause indicates "Complete Detach" for the combined IMSI/EPS attached UE.	Detach Type	0
Private Extension	0		Private Extension	VS

# 7.3.13 Detach Acknowledge

A Detach Acknowledge message shall be sent as a response to a Detach Notification message during Detach procedure.

Possible Cause values are specified in Table 8.4-1.

Table 7.3.13-1 specifics the presence of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	0		Recovery	0
Private Extension	0		Private Extension	VS

### 7.3.14 Change Notification Request

3GPP TS 23.401 [3] and 3GPP TS 23.060 [4] specify that if PGW has requested ECGI/eNodeB ID/TAI/CGI/SAI/RAI Change Reporting or reporting of change of UE presence in Presence Reporting Area(s) or User CSG information Change Reporting and if MME/S4-SGSN supports the feature, then MME/S4-SGSN shall send the Change Notification Request message on the S11/S4 interface to the SGW. If SGW supports the feature, the SGW forwards the message on the GTP based S5/S8 interface to the PGW as part of location dependent charging related procedures.

In this version of the specification, the sender shall set the header TEID value to that of the peer node's Control Plane TEID on S11/S4 interface or to the peer node's Control Plane TEID on S5/S8 interface. However a receiver shall be prepared to receive messages in which the header TEID value is set to zero from implementation conforming to earlier versions of this specification. When that is the case, the receiver identifies the subscriber context based on the included LBI, IMSI, and/or MEI IEs.

The MME shall increment the "MO Exception Data Counter" by one each time the MME has received the RRC cause "MO Exception data". The MME may defer sending a Change Notification Request message to report a non-zero value for the "MO Exception Data Counter" based on local configuration.

Table 7.3.14-1: Information Element in Change Notification Request

Information elements	Ρ	Condition / Comment	IE Type	Ins.
IMSI	С	The MME/SGSN shall include IMSI in the message except for the case: - If the UE is emergency attached and the UE is UICCless.	IMSI	0
		The IMSI shall be included in the message but not used as an identifier - if UE is emergency attached but IMSI is not authenticated.		
ME Identity (MEI)	С	If the SGW receives this IE, it shall forward it to the PGW on S5/S8. The MME/SGSN shall include the ME Identity (MEI) IE:	MEI	0
		<ul> <li>If the UE is emergency attached and the UE is UICCless</li> </ul>	MET	U
		<ul> <li>If the UE is emergency attached and the IMSI is not authenticated</li> <li>If the SGW receives this IE, it shall forward it to the PGW on S5/S8.</li> </ul>		
Indication Flags	СО	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags are: <ul> <li>Unauthenticated IMSI: This flag shall be set to 1 if the IMSI present in the message is not authenticated and is for an emergency attached UE.</li> </ul> </li> </ul>	Indication	0
RAT Type	Μ	See NOTE 2.	RAT Type	0
User Location Information (ULI)	C CO	The SGSN shall include the User Location Information IE if the MS is located in a RAT Type of GERAN, UTRAN or GAN and shall include the CGI, SAI and/or RAI. The MME shall include the User Location Information IE if	ULI (NOTE 1)	0
	<u> </u>	the UE is located in a RAT Type of E-UTRAN and shall include the ECGI and/or TAI, or TAI and Macro eNB ID, or Macro eNB ID depending on the Change Reporting Action provided to the MME. If the SGW receives this IE it shall forward it to the PGW, if		
	00	it supports this feature.		
User CSG Information (UCI)	СО	The SGSN/MME shall include the User CSG Information IE if the MS is located in the CSG cell or the hybrid cell and the P-GW/PCRF decides to receive the CSG Information. If the SGW receives this IE it shall forward it to the PGW, if it supports this feature.	UCI	0
PGW S5/S8 GTP-C IP Address	C	This IE shall be sent on S4. This IE shall be sent on S11.	IP Address	0
LBI		This IE shall be sent on STT. This IE, identifying the PDN connection, shall be sent by the MME/SGSN on S11/S4. If the SGW receives this IE, it shall forward it to the PGW on S5/S8.	EBI	0

Presence Reporting	CO The MME/SGSN shall include this IE on the S11/S4	Presence	0
Area Information	interface if:	Reporting Area	0
		Information	
	- the PGW/PCRF/OCS has just requested to start		
	or modify reporting of change of UE presence in a		
	Presence Reporting Area and the MME/SGSN		
	supports such reporting. The MME/SGSN shall		
	then indicate whether the UE is inside or outside		
	the newly started or modified Presence Reporting		
	Area(s), or indicate the Presence Reporting Area(s) is inactive. Several IEs with the same type		
	and instance value may be included as necessary		
	to represent a list of Presence Reporting Area		
	Actions. One IE shall be included for each		
	Presence Reporting Area newly started or		
	modified.		
	- if the PGW/PCRF/OCS requested to report		
	changes of UE presence in a Presence Reporting		
	Area, the MME/SGSN supports such reporting and		
	the UE enters or leaves the Presence Reporting Area(s). Several IEs with the same type and		
	instance value may be included as necessary to		
	represent a list of Presence Reporting Area		
	Information. One IE shall be included for each		
	active Presence Reporting Area that the UE has		
	newly entered or left.		
	CO The SGW shall include this IE on S5/S8 if it receives the		
	Presence Reporting Area Information from MME/SGSN.		
MO Exception Data	CO The MME shall include this IE on the S11 interface when it	Counter	0
Counter	needs to send a non-zero counter value for the MO		
	Exception Data Counter. The timestamp in the counter shall be set with the time at which the counter value		
	increased from 0 to 1.		
	CO The SGW shall include this IE on S5/S8 if it receives the		
	MO Exception Data Counter from MME.		
Private Extension	O Vendor or operator specific information	Private Extension	VS
	etworks, when the message is sent from the VPLMN to the HPLM		
	ted in this IE shall be that of the selected Core Network Operator		
	Illocated Core Network Operator for non-supporting UEs. As an e		
	or roaming/sharing agreement, if the information on whether the l		
	ting UE is available, the PLMN ID that is communicated to the HF e the Common PLMN ID.	LIVIN IOF NON-SUPP	orung
	e the Common PLINN ID. etworks, when the MME/S4-SGSN and PGW pertain to the same	PLMN, the Primar	v
	hall be communicated in the ECGI to the PGW, and the Common		,
	ted in SAI/CGI to the PGW, for both supporting and non-supportin		
Network Op	erator PLMN ID (selected by the UE for supporting UEs or alloca	ted by the network	for
	ting UEs) shall be communicated in the TAI, RAI, UCI and the Se	rving Network.	
	use 4.4 of 3GPP TS 23.251 [55].		
	nay ignore RAT Type as the MME/SGSN always informs the PGV n the Modify Bearer Request message.	v about RAT Type	
	i the moulty beater nequest thessaye.		

# 7.3.15 Change Notification Response

The Change Notification Response message may be sent on the S11/S4 interface by the SGW to the MME/SGSN and is sent on the S5/S8 interface by the PGW to the SGW as part of location dependent charging related procedures to acknowledge the receipt of a Change Notification Request.

If SGW does not support the feature (see subclause 7.3.14 "Change Notification Request"), SGW may silently discard Change Notification Request message from MME/SGSN. If the MME/SGSN does not receive Change Notification Response, the MME/SGSN may either send Change Notification Request to the same SGW next time UE location changes, or not (marking SGW as not supporting the feature).

The Cause value indicates whether or not the Change Notification Request was received correctly. Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Request accepted partially".
- "IMSI/IMEI not known".

In this version of the specification, the sender shall set the header TEID value to that of the peer node's Control Plane TEID on S11/S4 interface or to the peer node's Control Plane TEID on S5/S8 interface. However a receiver shall be prepared to receive messages in which the header TEID value is set to zero from implementation conforming to earlier versions of this specification. When that is the case, the receiver identifies the subscriber context based on the included LBI, IMSI, and/or MEI IEs.

If the IMSI is unknown, or the IMEI is unknown when the UE is emergency attached and UICCless or the UE is emergency attached but the IMSI is not authenticated for the receiving GTP-C entity, then the message shall be silently discarded and no further processing of the IEs shall continue.

If the MME/SGSN receives Change Notification Response containing a Cause value of "IMSI/IMEI not known" and CS bit set to 1, this indicates that the associated PDN connection does not exist within the PGW. The Change Reporting mechanism shall be stopped in the receiving SGSN/MME for all Bearers of the associated PDN connection. The SGSN/MME shall then initiate PDN disconnection for all of these PDN Connections.

If the PDN Connection associated of the Change Notification Request message received by the SGW does not exist within the SGW, the SGW shall return Change Notification Response with the CS bit set to 0 to the MME/SGSN. The Change Reporting mechanism shall be stopped in the receiving SGSN/MME for all Bearers of the associated PDN connection, and the MME/SGSN shall then locally delete the PDN connection and release all associated resources.

If the location Change Reporting mechanism is to be stopped or modified for this subscriber in the SGSN/MME, then the PGW shall include the Change Reporting Action IE in the message and shall set the value of the Action field appropriately.

If the MME has sent the "MO Exception Data Counter" for the RRC Cause "MO Exception data" in the Change Notification Resquest, the MME shall reset the counter value when receiving the Change Notification Response message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	The IMSI shall be included in the message if it is received in the Change Notification Request message.	IMSI	0
ME Identity (MEI)	С	The ME Identity (MEI) shall be included in the message if it is received in the Change Notification Request message.	MEI	0
Cause	Μ		Cause	0
Change Reporting Action	С	This IE shall be included with the appropriate Action field If the location Change Reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	Change Reporting Action	0
CSG Information Reporting Action	СО	This IE shall be included with the appropriate Action field if the location CSG Info reporting mechanism is to be started or stopped for this subscriber in the SGSN/MME.	CSG Information Reporting Action	0
Presence Reporting Area Action	CO	This IE shall be included on the S5/S8 and S11/S4 interfaces with the appropriate Action field if reporting changes of UE presence in a Presence Routing Area is to be started, stopped or modified for this subscriber in the MME/SGSN. Several IEs with the same type and instance value may be included as necessary to represent a list of Presence Reporting Area Actions. One IE shall be included per Presence Reporting Area to be started, stopped or modified.	Presence Reporting Area Action	0
Private Extension	0		Private Extension	VS

#### Table 7.3.15-1: Information Element in Change Notification Response

# 7.3.16 Relocation Cancel Request

A Relocation Cancel Request message shall be sent from the source MME/SGSN to the target MME/SGSN on S3/S10/S16 interface as part of the Inter RAT handover Cancel procedure/S1 Based handover Cancel procedure and on the S16 interface as part of the SRNS Relocation Cancel Procedure.Table 7.3.16-1 specifics the presence of the IEs in the message.

Table 7.3.16-1: Information	Elements in	Relocation	Cancel Request
-----------------------------	-------------	------------	----------------

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	The IMSI shall be included in the message except for the case: - If the UE is emergency attached and the UE is UICCless.	IMSI	0
		The IMSI shall be included in the message but not used as an identifier - if UE is emergency attached but IMSI is not authenticated.		
ME Identity (MEI)	С	The MME/SGSN shall include the ME Identity (MEI) IE: - If the UE is emergency attached and the UE is UICCless	MEI	0
		- If the UE is emergency attached and the IMSI is not authenticated		
Indication Flags	CO	This IE shall be included if any one of the applicable flags is set to 1. Applicable flags are: - Unauthenticated IMSI: This flag shall be set to 1 if the IMSI present in the message is not authenticated and is for an emergency attached UE.	Indication	0
RANAP Cause	С	This IE shall be present in the case of SRNS relocation cancel procedure. It shall contain the cause value received from the source RNC in the Relocation Cancel message received over the lu interface.	F-Cause	0
Private Extension	0		Private Extension	VS

# 7.3.17 Relocation Cancel Response

A Relocation Cancel Response message shall be sent as a response to a previous Relocation Cancel Request message during the Inter RAT handover Cancel procedure/S1 Based handover Cancel procedure/SRNS Relocation Cancel Procedure.

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "IMSI/IMEI not known".

Table 7.3.17-1 specifics the presence of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

# 7.3.18 Configuration Transfer Tunnel

A Configuration Transfer Tunnel message shall be used to tunnel eNodeB Configuration Transfer messages from a source MME to a target MME over the S10 interface. The purpose of the eNodeB Direct Configuration Transfer is to transfer information from an eNodeB to another eNodeB in unacknowledged mode (see 3GPP TS 36.413 [10]).

Table 7.3.18-1 specifies the presence requirements and conditions of the IEs in the message.

Table 7.3.18-1: Information Elements in a Configuration Transfer Tunnel Message

Information elements	Ρ	Condition / Comment	IE Туре	Ins.
E-UTRAN Transparent Container		This IE shall contain the "SON Configuration Transfer" as specified in 3GPP TS 36.413 [10]. Container Type shall be set to 3.	F-Container	0
Target eNodeB ID	М	This IE shall contain the ID of the target eNodeB	Target Identification	0

# 7.3.19 RAN Information Relay

The RAN Information Relay message shall be sent on S3 interface between SGSN and MME to transfer the RAN information received by an SGSN from BSS or RNS (or GERAN Iu mode) or by an MME from eNodeB. The procedures are specified in 3GPP TS 23.401 [3].

This message shall also be sent on S16 interface to transfer the RAN information between GERAN or GERAN Iu mode or UTRAN.

For handling of protocol errors the RAN Information Relay message is treated as a Response message.

Table 7.3.19-1 specifies the presence requirements and conditions of the IEs in the message.

Table 7.3.19-1: Information	Elements in a RAN Information Relay
-----------------------------	-------------------------------------

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
BSS Container	М	All information elements from the BSSGP RIM PDU, starting from and including the BSSGP "PDU type", shall be contained within the BSS Container and forwarded to the destination MME/SGSN in the RAN Information Relay message. The Container Type shall be set to 2.	F-Container	0
RIM Routing Address	С	<ul> <li>This IE shall be included if the RIM Routing Address information is included in the message sent from the source RAN node.</li> <li>This IE identifies the destination RAN node where the RAN Information needs to be relayed to. It contains: <ul> <li>the destination RNC Identity when the target is GERAN Iu mode or UTRAN; or</li> <li>the destination Cell Identity when the target is GERAN; or</li> <li>the Target eNodeB ID when the target is E-UTRAN.</li> </ul> </li> </ul>	Target Identification	0
Private Extension	0	None	Private Extension	VS

# 7.3.20 ISR Status Indication

A ISR Status Indication message shall be sent on the S3 interface by the MME/SGSN to the ISR associated SGSN/MME as part of the following procedures:

the Restoration of PDN connections after an SGW failure for UEs with ISR as specified in 3GPP TS 23.007 [17];

- the HSS Based P-CSCF restoration procedure for 3GPP access (for both basic and PCO extension) as specified in 3GPP TS 23.380 [61].

Table 7.3.20-1 specifies the presence of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Action Indication	М	<ul> <li>This IE shall include one of the applicable Values:</li> <li>Deactivation Indication: If the value is set to 1, this indicates a request to the ISR associated MME/SGSN to deactivate ISR and remove the UE resource locally. See 3GPP TS 23.007 [17].</li> <li>Paging Indication: If the value is set to 2, this indicates a request to the ISR associated MME/SGSN to page the UE in IDLE state. See 3GPP TS 23.007 [17].</li> <li>Paging Stop Indication: If the value is set to 3, this indicates to the ISR associated MME/SGSN to stop paging the UE. See 3GPP TS 23.380 [61].</li> </ul>	Action Indication	0
Private Extension	0		Private Extension	VS

Table 7.3.20-1: Information E	Elements in an ISR	Status Indication
-------------------------------	--------------------	-------------------

# 7.3.21 UE Registration Query Request

The direction of this message shall be from S4-SGSN to MME (see Table 6.1-1).

This message shall be used to support CS/PS coordination for shared UTRAN and GERAN access. When an S4-SGSN receives a UE Registration Query from a RAN node, including an indication to also query MMEs, and if the UE (identified by IMSI) is not registered in the S4-SGSN, the S4-SGSN shall send a UE Registration Query Request message to all MMEs that may hold the UE's context, as specified in the subclause 7.1.6 of 3GPP TS 23.251 [55].

NOTE: How the S4-SGSN determines which MMEs it will query, is based on local configuration.

Table 7.3.21-1 specifies the presence of IEs in this message.

#### Table 7.3.21-1: Information Elements in UE Registration Query Request

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	Μ		IMSI	0
Private Extension	0		Private Extension	VS

### 7.3.22 UE Registration Query Response

The UE Registration Query Response message shall be sent as a response to a UE Registration Query Request, to report whether the inquired UE is registered in the MME and if so, with which Core Network Operator, as specified in the subclause 7.1.6 of 3GPP TS 23.251 [55].

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted", to be used when the UE is registered in the MME
- "IMSI/IMEI not known", to be used when the UE is not registered in the MME.

The IMSI received in the UE Registration Query Request message shall be included in the response, to allow correlation in the SGSN.

The Selected Core Network Operator Identifier identifies the core network operator currently serving the UE, and shall be included if the inquired UE is registered in the MME.

Table 7.3.22-1 specifies the presence of IEs in this message.

Information elements	Р	Condition / Comment IE Type	Ins.
Cause	М	Cause	0
IMSI	М	IMSI	0
Selected Core Network Operator Identifier	М	PLMN ID	0
Private Extension	0	Private Extension	VS

 Table 7.3.22-1: Information Elements in UE Registration Query Response

# 7.4 CS Fallback and SRVCC related messages

#### 7.4.1 Suspend Notification

The Suspend Notification message shall be sent on the S11 interface by the MME to the SGW and on the S5/S8 interface by the SGW to the PGW as part of the 1xRTT CS fallback procedures in 3GPP TS 23.272 [21].

The Suspend Notification message shall be sent on the S3 interface by the SGSN to the MME, on the S11 interface by the MME to the SGW, and on the S5/S8 interface by the SGW to the PGW as part of the SRVCC procedures in 3GPP TS 23.216 [43] or the CS fallback from E-UTRAN access to UTRAN/GERAN CS domain access related procedures in 3GPP TS 23.272 [21].

The Suspend Notification message shall be sent on the S16 interface as per the inter-SGSN suspend procedures in 3GPP TS 23.060 [35].

The Suspend Notification message shall be sent on the S16, the S4 and the S5/S8 interfaces as part of the SRVCC from UTRAN (HSPA) to GERAN without DTM support procedure in 3GPP TS 23.216 [43].

The Suspend Notification message shall be sent on the S4 and the S5/S8 interfaces as part of the CS fallback from E-UTRAN to GERAN CS domain related procedures in 3GPP TS 23.272 [21].

After receiving a Suspend Notification message, the SGW/PGW marks all the non-GBR bearers as suspended status. The PGW should discard packets it receives for the suspended UE.

Table 7.4.1-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	This IE shall be included only on the S11 interface. See NOTE 2.	IMSI	0
Routeing Area Identity(RAI)	С	This IE shall be included only on the S3 interface. See NOTE 1.	ULI (NOTE 3)	0
	CO	This IE shall be included on the S16 interface.		
Linked EPS Bearer ID	CO	This IE shall be included on the S11/S4 interface to	EBI	0
(LBI)		indicate the default bearer associated with the PDN connection.		
Packet TMSI(P-TMSI)	С	This IE shall be included only on the S3 interface. See NOTE 1.	P-TMSI	0
	CO	This IE shall be included on the S16 interface.		
Originating Node		This IE shall be sent on S11 interface, if before MME initiates a Detach procedure (a) ISR was active in the MME and (b) the MME was in EMM-Connected state (see also 8.65). This IE shall be sent on S4 interface, if before S4-SGSN	Node Type	0
		initiates a Detach procedure (a) ISR was active in the SGSN and (b) the SGSN was in PMM-Connected state (see also 8.65).		
Address for Control Plane	CO	If an SGSN within the same SGSN pool with the old SGSN receives this message, the SGSN shall include the source IP address of the received message in this optional parameter if this IE is not present and relay the message to the old SGSN.	IP Address	0
UDP Source Port Number	CO	If an SGSN within the same SGSN pool as the old SGSN receives this message, the SGSN shall include the UDP Source Port number of the received message in this parameter if this IE is not present and relay the message to the old SGSN. The old SGSN shall use this UDP port as the UDP destination port of the Suspend Acknowledge message.	Port Number	0
Hop Counter	0	If an SGSN within the same SGSN pool with the old SGSN receives this message, the SGSN shall decrement the Hop Counter if this IE is present in the received message; otherwise, the SGSN may include a Hop Counter with a value of max-1, and may relay the message to the old SGSN.	Hop Counter	0
Sender F-TEID for Control Plane	CO	The MME/SGSN and SGW shall include this IE on the S11/S4 and S5/S8 interfaces respectively and set it to the last value sent to the peer. If the Sender F-TEID for Control Plane is received, the receiver shall only handle the message if the Sender F-TEID for Control Plane in this message is the same as the last Sender F-TEID for Control Plane received on the given	F-TEID	0

Table 7.4.1-1: Information Element in Suspend Notification

Private Extension 0 Private Extension VS NOTE 1: If the ISR is not active, the MME can not suspend the bearers after receving the Suspend Notification message from the SGSN, the GUTI can not be derived from the P-TMSI and RAI pair as the P-TMSI Signature is not included in the message. The MME shall still reply the Suspend Acknowledge to the SGSN. Suspend procedure on MME, SGW and PGW are triggered by the S1 UE Context Release message sent from the eNodeB to the MME. Refer to section 6.3 and section 7.4 in 3GPP TS 23.272 [21] for detail. NOTE 2: The IMSI is present only for backward compatibility reasons since the SGW can derive the context

from the TEID in the header. In scenarios where IMSI is not present (e.g. UICCless UE during an Emergency call) a dummy IMSI shall be provided.

NOTE 3: Only RAI field in the ULI IE type shall be present in the Routeing Area Identity (RAI) IE.

#### 7.4.2 Suspend Acknowledge

interface

The Suspend Acknowledge message shall be sent on the S11 interface by the SGW to the MME and on the S5/S8 interface by the PGW to the SGW as part of the 1xRTT CS fallback procedures in 3GPP TS 23.272 [21].

The Suspend Acknowledge message shall be sent on the S3 interface by the MME to the SGSN, on the S11 interface by the SGW to the MME and on the S5/S8 interface by the PGW to SGW as part of the SRVCC procedures in 3GPP TS 23.216 [43] or the CS fallback from E-UTRAN access to UTRAN/GERAN CS domain access related procedures in 3GPP TS 23.272 [21].

The Suspend Acknowledge message shall be sent on the S16 interface as per the inter-SGSN suspend procedures in 3GPP TS 23.060 [35].

The Suspend Acknowledge message shall be sent on the S16, the S4 and the S5/S8 interfaces as part of the SRVCC from UTRAN (HSPA) to GERAN without DTM support procedure in 3GPP TS 23.216 [43].

The Suspend Acknowledge message shall be sent on the S4 and the S5/S8 interfaces as part of the CS fallback from E-UTRAN to GERAN CS domain related procedures in 3GPP TS 23.272 [21].

Possible Cause values are specified in Table 8.4-1.

For backward compatibility, if the IMSI IE is missing in the Suspend Notification message that is received on the S11 interface, the cause value "Mandatory IE missing" shall be used.

Table 7.4.2-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

### 7.4.3 Resume Notification

The Resume Notification message should be sent on the S11 interface by the MME to the SGW and forwarded on the S5/S8 interface by the SGW to the PGW as part of the resume procedure returning back to E-UTRAN in the case of CS fallback or SRVCC.

The Resume Notification message should also be sent on the S4 interface by the SGSN to the SGW and forwarded on the S5/S8 interface by the SGW to the PGW as part of the resume procedure returning from SRVCC to HSPA if there is no Modify Bearer Request message sent to the SGW and PGW as specified in 3GPP TS 23.216 [43].

The SGW may also send a Resume Notification message to the PGW on the S5/S8 interface upon receipt from the MME/S4-SGSN of a (non-empty) Modify Bearer Request used as an implicit resume of the suspended bearers in the SGW and in the PGW (see 3GPP TS 23.216 [43] sections 6.2.2.1 and 6.3.2.1, 3GPP TS 23.272 [21] sections 6.3, 6.5 and 7.4) if the conditions of presence of the IEs in the Modify Bearer Request specified in table 7.2.7-1 do not require any IE to be sent over S5/S8 to the PGW.

NOTE: This is an alternative to sending over S5/S8 a Modify Bearer Request used as an implicit resume with zero IE(s), see subclause 7.2.7.

After receiving a Resume Notification message or a Modify Bearer Request used as an implicit resume of the suspended bearers, the SGW/PGW clears suspended status for all the non-GBR bearers. The PGW shall forward packets it receives for the UE. If the suspended bearers are of the type S4-U GTP-U, the SGW shall forward over the S4-U interface, packets it receives for the UE, upon receipt of Resume Notification.

Table 7.4.3-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
IMSI	М	See NOTE1.	IMSI	0
Linked EPS Bearer ID (LBI)	СО	This IE shall be included on the S11/S4 interface to indicate the default bearer associated with the PDN connection.	EBI	0
Originating Node	CO	This IE shall be sent on S11 interface, if before MME initiates a Detach procedure (a) ISR was active in the MME and (b) the MME was in EMM-Connected state (see also 8.65). This IE shall be sent on S4 interface, if before S4-SGSN initiates a Detach procedure (a) ISR was active in the SGSN and (b) the SGSN was in PMM-Connected state (see also 8.65).	Node Type	0
Sender F-TEID for Control Plane	CO	The MME/SGŚN and SGW shall include this IE on the S11/S4 and S5/S8 interfaces respectively and set it to the last value sent to the peer If the Sender F-TEID for Control Plane is received, the receiver shall only handle the message if the Sender F- TEID for Control Plane in this message is the same as the last Sender F-TEID for Control Plane received on the given interface.	F-TEID	0
Private Extension	0		Private Extension	VS
NOTE 1: The IMSI is present only for backward compatibility reasons since the receiver can derive the context from the TEID in the header. In scenarios where IMSI is not present (e.g. UICCless UE during an Emergency call) a dummy IMSI shall be provided.				

Table 7.4.3-1: Information Element in Resume Notification

### 7.4.4 Resume Acknowledge

The Resume Acknowledge message should be sent on the S11 interface by the SGW to the MME and on the S5/S8 by the PGW to the SGW as part of the resume procedure returning back to E-UTRAN in the case of CS fallback or SRVCC.

The Resume Acknowledge message should also be sent on the S4 interface by the SGW to the SGSN and on the S5/S8 interface by the PGW to the SGW as part of the resume procedure returning from SRVCC to HSPA if there is no Modify Bearer Request message sent to the SGW and PGW as specified in 3GPP TS 23.216 [43].

The PGW shall also send a Resume Acknowledge message to the SGW on the S5/S8 interface as a response to a Resume Notification message sent by the SGW upon receipt from the MME/S4-SGSN of a (non-empty) Modify Bearer Request used as an implicit resume of the suspended bearers in the SGW and in the PGW (see 3GPP TS 23.216 [43] sections 6.2.2.1 and 6.3.2.1, 3GPP TS 23.272 [21] sections 6.3, 6.5 and 7.4) if the conditions of presence of the IEs in the Modify Bearer Request specified in table 7.2.7-1 do not require any IE to be sent to the PGW.

Possible Cause values are specified in Table 8.4-1.

Table 7.4.4-1 specifies the presence requirements and conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

# 7.4.5 CS Paging Indication

The CS Paging Indication shall be sent on the S3 interface by the MME to the associated SGSN when ISR is activated as part of mobile terminated CS services. The MME gets the related information from SGsAP-PAGING-REQUEST

#### 3GPP TS 29.274 version 14.7.0 Release 14

247

message as specified in 3GPP TS29.118 [21]. Table 7.4.5-1 specifies the presence requirements and the conditions of the IEs in the message.

NOTE: The SS code received on the SGs interface is not transferred to the SGSN because it is not used by the SGSN.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
IMSI	Μ		IMSI	0
VLR Name	Μ		FQDN	0
TMSI	0		TMSI	0
Location area identifier	0		ULI	0
Global CN-Id	0		Global CN-Id	0
Channel needed	0		Channel needed	0
eMLPP Priority	0		eMLPP Priority	0
Service Indicator	CO	This IE shall be sent if the service type for the paging is available.	Service Indicator	0
Private Extension	0		Private Extension	VS

#### Table 7.4.5-1: Information Element in CS Paging Indication

## 7.4.6 Alert MME Notification

An Alert MME Notification message shall be sent on the S3 interface by the MME to the associated SGSN as part of an SGs Non-EPS alert procedure (see 3GPP TS 29.118 [22]) when ISR is activated, except under the conditions specified in 3GPP TS 23.272 [21], to request to receive a notification when any activity from the UE is detected.

Table 7.4.6-1 specifies the presence requirements and the conditions of the IEs in the message.

Table 7.4.6-1: Information Element	t in Alert MME Notification
------------------------------------	-----------------------------

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Private Extension	0		Private Extension	VS

### 7.4.7 Alert MME Acknowledge

An Alert MME Acknowledge message shall be sent as a response to an Alert MME Notification message.

Possible Cause values are specified in Table 8.4-1.

NOTE: An SGSN implemented according to an earlier version of the specification will silently discard the Alert MME Notification message. An MME which does not receive an Alert MME Acknowledge message may not send further Alert MME Notification message to this SGSN.

Table 7.4.7-1 specifies the presence requirements and the conditions of the IEs in the message.

#### Table 7.4.7-1: Information Elements in Alert MME Acknowledge

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

## 7.4.8 UE Activity Notification

A UE Activity Notification message shall be sent on the S3 interface by the SGSN to the associated MME as part of an SGs Non-EPS alert procedure (see 3GPP TS 29.118 [22]) when ISR is activated, except under the conditions specified

in 3GPP TS 23.272 [21], to indicate that activity from a UE has been detected. Table 7.4.8-1 specifies the presence requirements and the conditions of the IEs in the message.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Private Extension	0		Private Extension	VS

# 7.4.9 UE Activity Acknowledge

A UE Activity Acknowledge message shall be sent as a response to a UE Activity Notification message.

Possible Cause values are specified in Table 8.4-1.

Table 7.4.9-1 specifics the presence requirements and the conditions of the IEs in the message.

#### Table 7.4.z-1: Information Elements in UE Activity Acknowledge

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

# 7.5 Non-3GPP access related messages

# 7.5.1 Create Forwarding Tunnel Request

A Create Forwarding Tunnel Request message shall be sent by a MME to a Serving GW as a part of the MME configures resources for indirect data forwarding during active handover procedure from E-UTRAN to CDMA 2000 HRPD access.

Table 7.5.1-1 specifies the presence requirements and the conditions of the IEs in the message.

Information	Ρ	Condition / Comment	IE Type	Ins.
elements				
S103 PDN Data Forwarding Info	М	The MME shall include the forwarding Infomation for all PDN connections of the UE requesting data forwarding towards the HSGW in the message as S103 PDN Data Forwarding Info information elements. For each of those PDN Connections, an IE with the same type and instance value shall be included. The Serving GW shall forward downlink data to the HSGW via the GRE tunnel identified by the HSGW Address and HSGW GRE Key included in this information element when it receives downlink data forwarded from the eNodeB belonging to the corresponding EPS bearers of the PDN connection.	S103PDF	0
Private Extension	0		Private Extension	VS

Table 7.5.1-1: Information Elements in a Create Forwarding Tunnel Request

# 7.5.2 Create Forwarding Tunnel Response

A Create Forwarding Tunnel Response message shall be sent by a Serving GW to a MME as a response to a Create Forwarding Tunnel Request message.

Table 7.5.2-1 specifies the presence requirements and the conditions of the IEs in the message.

The Cause value indicates if Data Forwarding Resources has been created in the Serving GW or not. Data Forwarding Resources have not been created in the Serving GW if the Cause differs from "Request accepted". Possible Cause values are specified in Table 8.4-1.

Only the Cause IE shall be included in the response if the Cause IE contains another value than "Request accepted".

Table 7.5.2-1: Information Elements in a Create Forwarding Tunnel Response

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
Cause	Μ		Cause	0
S1-U Data Forwarding Info	C	S1-U Data Forwarding Info shall be included in the message if the Cause contains the value "Request accepted". For each EPS bearer requesting data forwarding which is included in the S103 PDN Data Forwarding Info fields of corresponding Create Forwarding Tunnel Request message, the Serving GW shall assign a Serving GW S1-U Address and Serving GW S1-U TEID pair and included it in the response message as S1-U Data Forwarding Info information element. For each of those EPS bearers, an IE with the same type and instance value shall be included. The eNodeB shall forward downlink data of the EPS bearer to the Serving GW via the GTP-U tunnel identified by the Serving GW S1-U Address and Serving GW S1-U TEID.		0
Private Extension	0		Private Extension	VS

# 7.6 Reliable Delivery of Signalling Messages

Retransmission requirements in the current subclause do not apply to the Initial messages that do not have Triggered messages.

Reliable delivery in GTPv2 messages is accomplished by retransmission of these messages. A message shall be retransmitted if and only if a reply is expected for that message and the reply has not yet been received. There may be limits placed on the total number of retransmissions to avoid network overload.

Initial messages and their Triggered messages, as well as Triggered messages and their Triggered Reply messages are matched based on the Sequence Number and the IP address and port rules in subclause 4.2 "Protocol stack". Therefore, an Initial message and its Triggered message, as well as a Triggered message and its Triggered Reply message shall have exactly the same Sequence Number value. A retransmitted GTPv2 message (an Initial or a Triggered) has the exact same GTPv2 message content, including the GTP header, UDP ports, source and destination IP addresses as the originally transmitted GTPv2 message.

For each triplet of local IP address, local UDP port and remote peer's IP address a GTP entity maintains a sending queue with signalling messages to be sent to that peer. The message at the front of the queue shall be sent with a Sequence Number, and if the message has an expected reply, it shall be held in a list until a reply is received or until the GTP entity has ceased retransmission of that message. The Sequence Number shall be unique for each outstanding Initial message sourced from the same IP/UDP endpoint. A node running GTP may have several outstanding messages waiting for replies. Not counting retransmissions, a single GTP message with an expected reply shall be answered with a single GTP reply, regardless whether it is per UE, per APN, or per bearer

A piggybacked initial message (such as a Create Bearer Request message or Modify Bearer Request message) shall contain a Sequence Number that is assigned by sending GTP entity and the message shall be held in a list until a response is received. The response message to a piggybacked initial message may arrive without piggybacking (e.g., Create Bearer Response at PGW).

The Sequence Number in the GTP header of the triggered response message shall be copied from the respective request message.

If a request message (e.g., Create Session Request) triggers piggybacking (i.e., Create Bearer Request piggybacked on Create Session Response), re-transmission of the request message shall also trigger piggybacking. A Sequence Number used for a Command message shall have the most significant bit set to 1. A Sequence Number in a message, which was triggered by a Command message, as well as respective Triggered Reply message shall have the same Sequence

Number as the Command message (i.e. shall also have the most significant bit set to 1). This setting of the most significant bit of the Sequence Number is done to avoid potential clashes between the Sequence Number selected for a Command message, and the Sequence Number selected by a GTPv2 peer for a Request message, which was not triggered by a Command message.

A Sequence Number used for a Request message, which was not triggered by a Command message shall have the most significant bit set to 0.

A timer, denoted T3-RESPONSE, shall be started when a signalling message (for which a reply is expected) is sent. A signalling message or the triggered message has probably been lost if a reply has not been received before the T3-RESPONSE timer expires.

Once the T3-RESPONSE timer expires, the message corresponding to the T3-RESPONSE timer is then retransmitted if the total number of retry attempts is less than N3-REQUESTS times. The expiry of the timer for piggybacked request messages shall result in re-transmission of the original IP/UDP packet containing both the triggered response message and the piggybacked initial message. T3-RESPONSE timer and N3-REQUESTS counter setting is implementation dependent. That is, the timers and counters may be configurable per procedure. Multileg communications (e.g. Create Session Requests and Responses) however require longer timer values and possibly a higher number of retransmission attempts compared to single leg communication.

All received GTPv2 messages with an expected reply shall be replied to and all reply messages associated with a certain message shall always include the same information. Duplicated reply messages shall be discarded by the receiver unless the reply needs a reply. A received reply message without a matching outstanding message that is waiting for a reply should be discarded.

If a GTPv2 node is not successful with the transfer of a non-Echo signalling message, e.g. a Create Bearer Request message, it shall inform the upper layer of the unsuccessful transfer so that the controlling upper entity may take the necessary measures.

# 7.7 Error Handling

### 7.7.0 Handling Piggybacked Messages

For piggybacked initial messages, the following general rule shall apply: the triggered response message carrying the piggybacked message shall be processed first, according to the following sections. Subsequently, the piggybacked initial message shall be processed independently. If the processing of dedicated bearer activation message results in an error, this shall not affect the default bearer establishment. If the default bearer establishment fails, the dedicated bearer activation related message shall be discarded.

# 7.7.1 Protocol Errors

A protocol error is defined as a message or an Information Element received from a peer entity with unknown type, or if it is unexpected, or if it has an erroneous content.

The term silently discarded is used in the following subclauses to mean that the receiving GTP entity's implementation shall discard such a message without further processing, or that the receiving GTP entity discards such an IE and continues processing the message. The conditions for the receiving GTP entity to silently discard an IE are specified in the subsequent subclauses.

The handling of unknown, unexpected or erroneous GTP messages and IEs shall provide for the forward compatibility of GTP. Therefore, the sending GTP entity shall be able to safely include in a message a new conditional-optional or an optional IE. Such an IE may also have a new type value. Any legacy receiving GTP entity shall, however, silently discard such an IE and continue processing the message.

If a protocol error is detected by the receiving GTP entity, it should log the event including the erroneous message and may include the error in a statistical counter.

For Request messages and Response messages without a rejection Cause value, the following applies:

- An information element with "Mandatory" in the "Presence requirement" column of a message definition shall always be present in that message.

- An information element with "Conditional" in the "Presence requirement" column of a message definition shall be sent when the conditions detailed in the "Condition / Comment" column are met.

For Response messages containing a rejection Cause value, see subclause 6.1.1.

The Version Not Supported Indication message shall be considered as a Triggered message as specified in subclause 4.2.5 "Messages with GTPv2 defined replies: Classification of Initial and Triggered Messages".

The receiving GTP entity shall apply the error handling specified in the subsequent subclauses in decreasing priority.

If the received erroneous message is a reply to an outstanding GTP message, the GTP transaction layer shall stop retransmissions and notify the GTP application layer of the error even if the reply is silently discarded.

### 7.7.2 Different GTP Versions

If a GTPv2 entity receives a message of an unsupported GTP version, higher than GTPv2, it shall return a Version Not Supported Indication message and silently discard the received message.

If a GTPv2 entity listens to the GTPv0 port, the entity shall silently discard any received GTPv0 message.

If a GTPv2 entity does not support GTPv1 and receives a GTPv1 message, it shall silently discard the received message.

# 7.7.3 GTP Message of Invalid Length

If a GTP entity receives a message, which is too short to contain the respective GTPv2 header, the GTP-PDU shall be silently discarded.

Apart from a piggybacked GTP message or an Echo Request message, if a GTP entity receives a Request message within an IP/UDP packet of a length that is inconsistent with the value specified in the Length field of the GTP header, then the receiving GTP entity should log the error and shall send the Response message with Cause IE value set to "Invalid Length".

Apart from a piggybacked GTP message, if a GTP entity receives a Response message within an IP/UDP packet of a length that is inconsistent with the value specified in the Length field of the GTP header, then the receiving GTP entity should log the error and shall silently discard the message.

If a GTP entity receives two GTP messages (triggered response message and a piggybacked initial message) within an IP/UDP packet of a length that is inconsistent with the total length of the two concatenated messages as indicated by Length fields of the GTP headers, then the receiving GTP entity should log the error and return an appropriate Response message with Cause IE value set to "Invalid overall length of the triggered response message and a piggybacked initial message". That is:

- for a Create Session Response message together with a piggybacked Create Bearer Request message, a Create Bearer Response message should be returned with the above Cause value.
- for a Create Bearer Response message together with a piggybacked Modify Bearer Request message, a Modify Bearer Response message should be returned with the above Cause value.

# 7.7.4 Unknown GTP Message

If a GTP entity receives a message with an unknown Message Type value, it shall silently discard the message.

# 7.7.5 Unexpected GTP Message

If a GTP entity receives an unexpected initial message (see subclause 4.2 "Protocol stack"), for example a known message that is sent over an interface for which the message is not defined, or a message that is sent over an interface for which the message is defined, but the direction is incorrect, then the GTP entity shall silently discard the message and shall log an error.

If a GTP entity receives an unexpected triggered message which is not a request message (see subclause 4.2 "Protocol stack"), for example a message for which there is no corresponding outstanding request, it shall discard the message and may log an error.

When a GTP entity receives an unexpected triggered message, which is a request message, triggered by a command message, i.e. the MSB of the sequence number is set "1", e.g. in Create/Update/Delete Bearer Request messages, the GTP entity may continue to handle the request, e.g. to accept the Delete Bearer Request message.

NOTE: Whether to accept or reject such a message is implementation specific.

#### 7.7.6 Missing Information Elements

A GTP entity shall check if all mandatory IEs are present in the received Request message. Apart from Echo Request message, if one or more mandatory information elements are missing in the received Request message, the GTP entity should log the error and shall send a Response message with Cause IE value set to "Mandatory IE missing" together with the type and instance of the missing mandatory IE.

If a GTP entity receives a Response message with Cause IE value set to "Mandatory IE missing", it shall notify its upper layer.

A GTP entity shall check if all mandatory IEs are present in the received Response message without a rejection Cause value. If one or more mandatory information elements are missing, the GTP entity shall notify the upper layer and should log the error.

A GTP entity shall check if conditional information elements are present in the received Request message, if possible (i.e. if the receiving entity has sufficient information available to check if the respective conditions were met). If one or more conditional information elements are missing, a GTP entity should log the error and shall send a Response message with Cause IE value set to "Conditional IE missing" together with the type and instance of the missing conditional IE.

A GTP entity shall check if conditional information elements are present in the received Response message without a rejection Cause value, if possible (i.e. if the receiving entity has sufficient information available to check if the respective conditions were met). If one or more conditional information elements are missing, a GTP entity shall notify the upper layer and should log the error.

For Response messages containing a rejection Cause value, see subclause 6.1.1.

If the Indication IE is applicable for the message as a conditional IE and if it is not present, the GTP entity shall not reject the message unless there are other reasons to reject the message.

If the Indication IE is applicable for the message as conditional IE and if it is present with the value of all the applicable flags set to "0", the GTP entity shall not reject the message unless there are other reasons to reject the message.

Absence of an optional information element shall not trigger any of the error handling processes.

#### 7.7.7 Invalid Length Information Element

An information element has invalid length when the actual length of the IE is different from the value of the Length field in the IE header. Here, the actual length of the IE means the length of the content field of the received IE.

If a GTP message contains more than one information elements and one or more of them have invalid length, the receiving GTP entity can detect which of the IEs have invalid length only in the following cases:

- If the Length value in the IE header is greater than the overall length of the message;
- If the invalid length IE is the last one in the message.

Apart from Echo Request message, if a receiving GTP entity detects information element with invalid length in a Request message, it shall send an appropriate error response with Cause IE value set to "Invalid length" together with the type and instance of the offending IE.

Other Length field handling cases are specified below:

- If the received value of the Length field and the actual length of the fixed length IE are consistent, but the length is greater than that expected by the fixed number of octets, then the extra octets shall be discarded.
- If the received value of the Length field and the actual length of the fixed length IE are consistent, but the length is less than that expected by the fixed number of octets, this shall be considered an error, IE shall be discarded and if the IE was received as a Mandatory IE or a verifiable Conditional IE in a Request message, an appropriate error response with Cause IE value set to "Invalid length" together with the type and instance of the offending IE shall be returned to the sender.
- If the received value of the Length field and the actual length of the extendable length IE are consistent, but the length is greater than that expected by the fixed number of octets preceding the extended field(s), then the extra unknown octets shall be discarded.
- If the received value of the Length field and the actual length of the extendable length IE are consistent, but the length is less than the number of fixed octets defined for that IE, preceding the extended field(s), this shall be considered an error, IE shall be discarded and if the IE was received as a Mandatory IE or a verifiable Conditional IE in a Request message, an appropriate error response with Cause IE value set to "Invalid length" together with the type and instance of the offending IE shall be returned to the sender. Please refer to Table 8.1-1 for determining the number of fixed octets of an IE.

#### 7.7.8 Semantically incorrect Information Element

Apart from Echo Request message, the receiver of a GTP signalling message Request including a mandatory or a verifiable conditional information element with a semantically invalid Value shall discard the request, should log the error, and shall send a response with Cause set to "Mandatory IE incorrect" together with a type and instance of the offending IE.

The receiver of a GTP signalling message Response including a mandatory or a verifiable conditional information element with a semantically invalid Value shall notify the upper layer that a message with this sequence number has been received and should log the error.

If a GTP entity receives an information element with a value which is shown as reserved, it shall treat that information element as invalid and should log the error. If the invalid IE is received in a Request, and it is a mandatory IE or a verifiable conditional IE, the GTP entity shall send a response with Cause set to "Mandatory IE incorrect" together with a type and instance of the offending IE.

The principle is: the use of reserved values invokes error handling; the use of spare values can be silently discarded and so in the case of IEs with spare values used, processing shall be continued ignoring the spare values.

The receiver of a GTP signalling message including an optional information element with a Value that is not in the range defined for this information element value shall discard this IE, but shall treat the rest of the message as if this IE was absent and continue processing. The receiver shall not check the content of an information element field that is defined as 'spare''.

All semantically incorrect optional information elements in a GTP signalling message shall be treated as not present in the message.

#### 7.7.9 Unknown or unexpected Information Element

The receiver of a GTP message including an unexpected information element with known Type value, but with the instance value that is not defined for this message shall discard the IE and log an error. The receiver shall process the message.

An information element with a Type value which is defined in section 8.1 of the present specification but whose Instance Value is not expected in the received GTP signalling message according to the grammar defined in section 7 of the present specification shall be silently discarded (skipped) and the rest of the message processed as if this information element was not present.

NOTE: An Information Element in an encoded GTPv2 message or grouped IE is identified by the pair of IE Type and Instance value.

### 7.7.10 Repeated Information Elements

An Information Element is repeated if there is more than one IE with the same IE Type and Instance in the scope of the GTP message (scope of the grouped IE). Such an IE is a member in a list.

If an information element is repeated in a GTP signalling message in which repetition of the information element is not specified, only the contents of the information element appearing first shall be handled and all subsequent repetitions of the information element shall be ignored. When repetition of information elements is specified, only the contents of specified repeated information elements shall be handled and all subsequent repetitions of the information element shall be ignored.

#### 7.7.11 TFT Error Handling

TFT related error handling for EUTRAN is specified in 3GPP TS 24.301 [23] and for UTRAN/GERAN in 3GPP TS 24.008 [5].

## 7.8 Path Failure

Path failure handling procedures are specified in 3GPP TS 23.007 [17].

# 7.9 Restoration and Recovery

#### 7.9.0 General

Restoration and Recovery procedures are specified in 3GPP TS 23.007 [17].

#### 7.9.1 Delete PDN Connection Set Request

This message may be sent on the S2a, S2b, S5, S8, or S11 interfaces as specified in 3GPP TS 23.007 [17].

Table 7.9.1-1: Information Elements in a Delete PDN Connection Set Reque	est
--------------------------------------------------------------------------	-----

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
MME-FQ-CSID		This IE shall be included when a MME reports a partial fault according to the requirements in 3GPP TS 23.007 [17]. More than one FQ-CSID may appear.	FQ-CSID	0
SGW-FQ-CSID		This IE shall be included when a SGW reports a partial fault according to the requirements in 3GPP TS 23.007 [17]. More than one FQ-CSID may appear.	FQ-CSID	1
PGW-FQ-CSID		Shall be included when a PGW reports a partial fault. More than one FQ-CSID may appear	FQ-CSID	2
ePDG-FQ-CSID		This IE shall be included when an ePDG reports a partial fault according to the requirements in 3GPP TS 23.007 [17]. More than one FQ-CSID may appear.	FQ-CSID	3
TWAN-FQ-CSID		This IE shall be included when a TWAN reports a partial fault according to the requirements in 3GPP TS 23.007 [17]. More than one FQ-CSID may appear.	FQ-CSID	4
Private Extension	0	This IE may be sent on the S2a, S2b, S5, S8 and S11 interfaces.	Private Extension	VS

TEID of 0 shall be used for the Delete PDN Connection Set Request.

Only one type of FQ-CSID shall be included in each Delete PDN Connection Set Request, A mix of different types, such as SGW-FQ-CSID and PGW-FQ-CSID shall not be used. A combined node, such as a collocated PGW/SGW, shall send separate Delete PDN Connection Set Request for the PGW role and one for the SGW role if a partial fault impacts more than one role.

## 7.9.2 Delete PDN Connection Set Response

This message is sent as a response to the Delete PDN Connection Set Request.

#### Table 7.9.2: Information Elements in a Delete PDN Connection Set Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	СО	This IE shall be included if contacting the peer for the first time	Recovery	0
Private Extension		This IE may be sent on the S2a, S2b, S5, S8 and S11 interfaces.	Private Extension	VS

TEID of 0 shall be used for the Delete PDN Connection Set Response.

The following Cause values are defined:

- "Request Accepted"
- "Request rejected"
- "System failure".
- "Mandatory IE incorrect".
- "Conditional IE missing".
- "Invalid message format".

"Request Accepted" indicates the receiving node was capable of storing a CSID value for each PDN connection for the type of node (MME, SGW, PGW, TWAN or ePDG) in the Delete PDN Connection Set Request and has marked, or will mark immediately, the PDN connections for deletion as specified in 3GPP TS 23.007 [17]. "Request Accepted" shall be returned even if there are no PDN connections that match.

"Request rejected" shall be used when the receiver of the Delete PDN Connection Set Request is not capable of storing at least one CSID value per PDN connection for the type of node (MME, SGW, PGW, TWAN or ePDG) received in the Delete PDN Connection Set Request.

The SGW shall respond to the Delete PDN Connection Set Request independently, i.e. without waiting for replies.

### 7.9.3 Update PDN Connection Set Request

The SGW shall send this message to the PGW on S5/S8 according to the requirements in TS 23.007 [17].

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
MME-FQ-CSID		This IE shall be included for MME relocation without SGW relocation according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
SGW-FQ-CSID		This IE shall be included for MME relocation without SGW relocation according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	1
Private Extension	0		Private Extension	VS

Table 7.9.3-1: Information Elements in a Update PDN Connection Set Request

### 7.9.4 Update PDN Connection Set Response

This message is sent by the PGW to the SGW on S5/S8 in response to the Update PDN Connection Set Request message.

Information elements	Ρ	Condition / Comment	IE Type	Ins.
Cause	Μ		Cause	0
PGW-FQ-CSID		This IE shall be included for MME relocation without SGW relocation according to the requirements in 3GPP TS 23.007 [17].	FQ-CSID	0
Recovery		This IE shall be included if contacting the peer for the first time	Recovery	0
Private Extension	0		Private Extension	VS

 Table 7.9.4-1: Information Elements in a Update PDN Connection Set Response

The following Cause values are defined:

- "Request accepted"
- "Request rejected"
- "System failure".
- "Mandatory IE incorrect".
- "Conditional IE missing".
- "Invalid message format".

#### 7.9.5 PGW Restart Notification

The direction of this message shall be from SGW to MME/S4-SGSN (see Table 6.1-1).

If both the SGW and the MME/S4-SGSN support the PRN feature (see subclause 8.83), a PGW Restart Notification shall be sent when the SGW detects that the peer PGW has restarted, and a PGW Restart Notification may be sent when the SGW detects that the peer PGW has failed and not restarted, as specified in 3GPP TS 23.007 [17].

Table 7.9.5-1 specifies the presence of IEs in this message.

#### Table 7.9.5-1: Information Elements in PGW Restart Notification

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
PGW S5/S8 IP Address for Control Plane or PMIP	М		IP Address	0
SGW S11/S4 IP Address for Control Plane	М		IP Address	1
Cause		The SGW shall send the Cause IE with the value "PGW not responding" if it sends the PGW Restart Notification to notify that the peer PGW has failed and not restarted.	Cause	0
Private Extension	0		Private Extension	VS

### 7.9.6 PGW Restart Notification Acknowledge

The PGW Restart Notification Acknowledge shall be sent as a response of PGW Restart Notification to indicate that the MME/S4-SGSN deletes all the relevant PDN connections as specified in 3GPP TS 23.007 [17] if the Cause IE includes an acceptance cause.

Possible Cause values are specified in Table 8.4-1.

257

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Private Extension	0		Private Extension	VS

#### Table 7.9.6-1: Information Elements in PGW Restart Notification Acknowledge

### 7.9.7 PGW Downlink Triggering Notification

The direction of this message shall be from PGW to SGW and from SGW to MME(s)/S4-SGSN(s).

The PGW Downlink Triggering Notification shall be sent as part of the PGW triggered SGW restoration procedure if the MME/S4-SGSN, SGW and PGW support this optional feature as specified in 3GPP TS 23.007 [17].

Table 7.9.7-1: Information Elements in PGW Downlink Triggering Notification

Information	Ρ	Condition / Comment	ІЕ Туре	Ins.
elements				
IMSI	Μ		IMSI	0
MME/S4-SGSN identifier	С	This IE shall be included over S5 /S11/S4 interface as specified in 3GPP TS 23.007 [17].	IP Address	0
PGW S5 F-TEID for GTP or PMIP Control Plane (NOTE 2)		This IE may be included over the S5 interface. If present, it shall contain the PGW S5 F-TEID value assigned during the PDN connection establishment. (NOTE 1) The PGW shall include this IE over the S5 interface according to the conditions specified in subclauses 20.2.7.1 of 3GPP TS 23.007 [17]. If the SGW receives this IE it shall forward the IE to the MME/S4-SGSN over the S11/S4 interface. This IE shall include the PGW S5 IP address for control plane and TEID for GTP based S5 case or the uplink GRE key for control plane in the PMIP based S5 case.	F-TEID	0
Private Extension	0		Private Extension	VS
PGW's Con the PGW D	trol l ownl	set the header TEID value in the PGW Downlink Triggering A Plane TEID if the 'PGW S5 F-TEID for GTP or PMIP Control ink Triggering Notification message.	Plane' IE is present	t in
		ns of this specification, the name of this IE was 'Sender F-TE changed when extending the applicability of the IE to S4/S11		θ'.

### 7.9.8 PGW Downlink Triggering Acknowledge

The PGW Downlink Triggering Acknowledge message shall be sent as a response to a PGW Downlink Triggering Notification message if the MME/S4-SGSN, SGW and PGW support the PGW triggered SGW restoration feature as specified in 3GPP TS 23.007 [17].

Possible Cause values are specified in Table 8.4-1. Message specific cause values are:

- "Request accepted".
- "Context not found".

Information elements	Ρ	Condition / Comment	IE Type	Ins.
Cause	Μ		Cause	0
IMSI	С	This IE shall be included on S11/S4 interface if the Cause is indicating the rejection value "Context Not Found" and if the MME/S4-SGSN identifier is included in the corresponding PGW Downlink Triggering Notification message.	IMSI	0
MME/S4-SGSN identifier	С	This IE shall be included on S11/S4 interface if the Cause is indicating the rejection value "Context Not Found" and if the MME/S4-SGSN identifier is included in the corresponding PGW Downlink Triggering Notification message.	IP Address	0
Private Extension	0		Private Extension	VS

Table 7.9.8-1: Information Elements in PGW Downlink Triggering Acknowledge

### 7.10 Fallback to GTPv1 mechanism

An EPC entity shall assume that each GTP processing node that it is about to communicate with is GTPv2 capable. Before the first GTP tunnel is setup for a given UE/node, the EPC node shall always send a version 2 (GTPv2) message to a peer node. As an exception, during an inter-SGSN handover, even if the target SGSN is GTPv2 capable, the source SGSN shall send a GTPv1 message "Forward Relocation Request" to the target SGSN if the PDP Context(s) for this UE were established to GGSN(s), or if there is no active PDP context and the source or target SGSN does not support SRNS relocation w/o PDN connection over GTPv2 (see subclause 7.3.1).

A GTPv2 entity shall fallback to GTPv1 only if either a "Version Not Supported" message in GTPv1 format as specified in 3GPP TS 29.060 [4] is received from the peer node (this indicates that the peer GTP entity does not support GTPv2), or if a GTPv2 message is received with Cause value "Fallback to GTPv1".

If a GTPv1 "Version Not Supported" message in received, a GTPv2 entity may fallback to GTPv1. 3GPP TS 23.401 [3] (see annex D) and 3GPP TS 23.060 [35] specify GTP version usage during the mobility between a UTRAN/GERAN and an E-UTRAN.

A GTPv2 entity may receive a GTPv2 message with a Cause value "Fallback to GTPv1" in the following cases:

- an S4 SGSN receives the Cause code "Fallback to GTPv1" in a GTPv2 Context Response message over S16 interface. When an UE has activated a PDP context via S4 SGSN to GGSN and inter-SGSN RAU is underway, the old S4 SGSN shall include the Cause value "Fallback to GTPv1" in a GTPv2 Context Response message over S16 interface. In this case, the new S4 SGSN shall abort the ongoing GTPv2 procedure and send a GTPv1 "SGSN Context Request" message to the old S4 SGSN. The fallback to GTPv1 is performed only for this UE in the current procedure.
- an MME receives the Cause code "Fallback to GTPv1" in a GTPv2 Context Response message over the S3 interface. When an UE has active PDP context(s) via an S4 SGSN and a TAU is underway, the old S4 SGSN may include the Cause value "Fallback to GTPv1" in a GTPv2 Context Response message over the S3 interface. In this case, the MME shall abort the ongoing GTPv2 procedure and should send a GTPv1 "SGSN Context Request" message to the old S4 SGSN. The fallback to GTPv1 is performed only for this UE.

Fallback to GTPv1 shall not occur on already established GTP tunnels without change of the peer nodes of the communication bearer.

### 7.11 Fallback to GTPv0

Fallback from GTPv2 to GTPv0 shall not be supported. Therefore, GTPv2 entity should not listen to the well-known GTPv0 port 3386.

# 7.12 Trace Management Messages

### 7.12.1 Trace Session Activation

The Trace Session Activation message shall be sent on S11/S4 by the MME/SGSN to the SGW, on S2a/S2b by the TWAN/ePDG to the PGW, and on S5/S8 by the SGW to the PGW when session trace is activated for a particular IMSI or IMEI for a UE that is attached and active or attached and idle.

Table 7.12.1-1 specifies the presence of the IEs in the message.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
IMSI	С	<ul> <li>The MME/SGSN shall include the IMSI in the message on the S11/S4 interface except for the case:</li> <li>If the UE is emergency attached and the UE is UICCless.</li> </ul>	IMSI	0
		The IMSI shall be included in the message on the S11/S4 interface but not used as an identifier - if UE is emergency attached but IMSI is not authenticated.		
		The SGW shall forward this IE to the PGW on S5/S8 if received on S11/S4.		
		The TWAN/ePDG shall include this IE on the S2a/S2b interface except for the case: - If the UE is emergency attached and the UE is UICCless.		
		<ul> <li>The IMSI shall be included in the message on the S2a/S2b interface if available, but not used as an identifier</li> <li>if UE is emergency attached but IMSI is not authenticated.</li> </ul>		
Trace Information	М		Trace Information	0
ME Identity (MEI)		The MME/SGSN shall include the ME Identity (MEI) IE on the S11/S4 interface: - If the UE is emergency attached and the UE is UICCless	MEI	0
		<ul> <li>If the UE is emergency attached and the IMSI is not authenticated</li> </ul>		
		In other cases, the MME shall include the ME Identity (MEI) IE on the S11 interface, if available.		
	00	The SGW shall forward this IE to the PGW on S5/S8 if received on S11/S4.		
	CO	The TWAN/ePDG shall include the ME Identity (MEI) IE on the S2a/S2b interface: - If the UE is emergency attached and the UE is UICCless		
		- If the UE is emergency attached and the IMSI is not authenticated		
		In other cases, the TWAN/ePDG shall include the ME Identity (MEI) IE on the S2a/S2b interface, if available.		

### 7.12.2 Trace Session Deactivation

The Trace Session Deactivation message shall be sent on S11/S4 by the MME/SGSN to the SGW, on S2a/S2b by the TWAN/ePDG to the PGW, and on S5/S8 by the SGW to the PGW when session trace is deactivated for a particular IMSI or IMEI for a UE that is attached and active or attached and idle.

Table 7.12.2-1 specifies the presence of the IEs in the message.

#### Table 7.12.2-1: Information Elements in a Trace Session Deactivation

Information elements	Ρ	Condition / Comment IE Type		Ins.
Trace Reference	Μ	Trace Refere	nce	0

# 7.13 MBMS Messages

#### 7.13.1 MBMS Session Start Request

The MBMS Session Start Request message shall be sent on the Sm/Sn interface by the MBMS GW to the MME/SGSN as specified in 3GPP TS 23.246 [37] and 3GPP TS 23.007 [13].

Table 7.13.1-1 specifies the presence of the IEs in the message.

Information	Р	Condition / Comment	IE Type	Ins.
elements				
Sender F-TEID for	Μ		F-TEID	0
Control Plane				
Temporary Mobile	М	See NOTE 4.	TMGI	0
Group Identity (TMGI)	N.4		MDMC Casalan	0
MBMS Session	М		MBMS Session Duration	0
MBMS Service Area	М		MBMS Service Area	0
MBMS Session	С	This IE shall be forwarded to MME/SGSN if it is provided by the BM-SC.	MBMS Session Identifier	0
MBMS Flow Identifier	С	This IE shall be forwarded to MME/SGSN if it is provided by the BM-SC.	MBMS Flow Identifier	0
QoS profile	М	See NOTE 1.	Bearer QoS	0
MBMS IP Multicast Distribution	M	See NOTE 2.	MBMS IP Multicast Distribution	0
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
MBMS Time to Data Transfer	со	This IE shall be forwarded to MME/SGSN if it is received from the BM-SC.	MBMS Time to Data Transfer	0
MBMS Data Transfer Start	со	This IE shall be forwarded to the MME if it is received from the BM-SC.	Absolute Time of MBMS Data Transfer	0
MBMS Flags		<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags: <ul> <li>MBMS Session Re-establishment Indication: this flag shall be set to 1 on the Sm/Sn interfaces if the MBMS Session Start Request message is used to re-establish an MBMS session (see 3GPP TS 23.007 [13]).</li> </ul> </li> </ul>	MBMS Flags	
MBMS Alternative IP Multicast Distribution		If the MBMS GW supports both IPv4 and IPv6 M1 multicast address types, the MBMS GW may include this IE on the Sm interface to provide an alternative MBMS IP Multicast Distribution Address with a different address type (i.e. IPv4 or IPv6) than the one provided in the MBMS IP Multicast Distribution IE. See NOTE 2.	MBMS IP Multicast Distribution	1
MBMS Cell List	со	The MBMS GW shall include this IE on the Sm interface if a MBMS Cell List was received from the BM-SC. See NOTE 3.	ECGI-List	0
Private Extension	0		Private Extension	VS
NOTE 1: The uplink (	GBR	and uplink MBR shall be ignored by MME/SGSN as specifie		
<ul> <li>3GPP TS 29.061 [38].</li> <li>NOTE 2: If the MBMS GW supports both IPv4 and IPv6 M1 multicast address types, the MBMS GW may provide both IPv4 and IPv6 MBMS IP Multicast Distribution addresses on the Sm interface by including the MBMS IP Multicast Distribution IE and the MBMS Alternative IP Multicast Distribution IE in the MBMS Session Start Request. In this case, one of these IEs shall carry an IP Multicast Distribution Addresses. Both IEs shall contain the same C-TEID value.</li> <li>NOTE 3: The MBMS Cell List can contain from 1 up to 4096 cells (see 3GPP TS 29.061 [38]).</li> <li>NOTE 4: The PLMN ID in the TMGI IE received in the MBMS Session Start Request message may be different from the PLMN ID(s) either reported by the MCE(s) previously at the M3 Setup procedure or configured as supported PLMN(s), e.g. when shared MBMS network is deployed; the MME need not check it.</li> </ul>				

# 7.13.2 MBMS Session Start Response

The MBMS Session Start Response message shall be sent as a response to the MBMS Session Start Request message on the Sm/Sn interface by the MME/SGSN to the MBMS GW.

Table 7.13.2-1 specifies the presence of the IEs in the message.

Possible Cause values are specified in Table 8.4-1.

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Sender F-TEID for Control Plane	М		F-TEID	0
MBMS Distribution Acknowledge	С	This IE shall be included on the Sn interface.	MBMS Distribution Acknowledge	0
Sn-U SGSN F-TEID	С	This IE shall be included on the Sn interface if some RNCs have not accepted IP multicast distribution.	F-TEID	1
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	VS

Table 7.13.2-1: Information Elements in a MBMS Session Start Response

### 7.13.3 MBMS Session Update Request

The MBMS Session Update Request message shall be sent on the Sm/Sn interface by the MBMS GW to the MME/SGSN as specified in 3GPP TS 23.246 [37] and 3GPP TS 23.007 [13].

Table 7.13.3-1 specifies the presence of the IEs in the message.

Information	Ρ	Condition / Comment	IE Type	Ins.	
elements			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
MBMS Service Area	С	This IE shall be forwarded to MME/SGSN if it is provided	MBMS Service	0	
		by the BM-SC.	Area		
Temporary Mobile	Μ		TMGI	0	
Group Identity (TMGI)					
Sender F-TEID for	0		F-TEID	0	
Control Plane					
MBMS Session	Μ		MBMS Session	0	
Duration			Duration		
QoS profile		See NOTE 1.	Bearer QoS	0	
MBMS Session	С	This IE shall be forwarded to MME/SGSN if it is provided	MBMS Session	0	
Identifier		by the BM-SC.	Identifier		
MBMS Flow Identifier	С	This IE shall be forwarded to MME/SGSN if it is provided	MBMS Flow	0	
		by the BM-SC.	Identifier		
MBMS Time to Data	СО	This IE shall be forwarded to MME/SGSN if it is provided	MBMS Time to	0	
Transfer		by the BM-SC.	Data Transfer		
MBMS Data Transfer	со	This IE shall be forwarded to the MME if it is received from	Absolute Time of	0	
Start / Update / Stop		the BM-SC.	MBMS Data		
		See NOTE 3.	Transfer	_	
MBMS Cell List	co	The MBMS GW shall include this IE on the Sm interface if	ECGI List	0	
		a MBMS Cell List was received from the BM-SC.			
	0	See NOTE 2.		1/0	
Private Extension	0		Private Extension	VS	
		and uplink MBR shall be ignored by MME/SGSN as specifie	ed in Section 20.5 of	t	
3GPP TS 2	9.06	1 [38].			
NOTE OF THE MOME	Call	List concentrin from 1 up to 4006 collo (con 2000 TS 20.0	64 [20])		
NOTE 2: The MBMS Cell List can contain from 1 up to 4096 cells (see 3GPP TS 29.061 [38]). NOTE 3: The MME copies the absolute time received in this IE into the Time of MBMS Data Transfer IE in the					
M3AP MBMS SESSION START REQUESTor MBMS SESSION UPDATE REQUEST, or into the					
		Data Stop IE in the M3AP MBMS SESSION STOP REQUES			
		6 [37] and 3GPP TS 36.444 [79].	, as appropriate.	266	
3011132	J.24	o [o/] and ool F 10 00.444 [/3].			

# 7.13.4 MBMS Session Update Response

The MBMS Session Update Response message shall be sent as a response to the MBMS Session Update Request message on the Sm/Sn interface by the MME/SGSN to the MBMS GW.

Table 7.13.4-1 specifies the presence of the IEs in the message.

Possible Cause values are specified in Table 8.4-1.

 Table 7.13.4-1: Information Elements in a MBMS Session Update Response

Information elements	Ρ	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
MBMS Distribution Acknowledge	С	This IE shall be included on the Sn interface if service area is changed.	MBMS Distribution Acknowledge	0
Sn-U SGSN F-TEID	С	This IE shall be included on the Sn interface if any of the newly added RNCs have not accepted IP multicast distribution.	F-TEID	0
Recovery	С	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	VS

### 7.13.5 MBMS Session Stop Request

The MBMS Session Stop Request message shall be sent on the Sm/Sn interface by the MBMS GW to the MME/SGSN as specified in 3GPP TS 23.246 [37] and 3GPP TS 23.007 [13].

Table 7.13.5-1 specifies the presence of the IEs in the message.

Info specified in	Ρ	Condition / Comment	IE Type	Ins.
Table 8.4-1.rmation elements			21	
MBMS Flow Identifier	С	This IE shall be forwarded to MME/SGSN if it is provided by the BM-SC. See NOTE 1.	MBMS Flow Identifier	0
MBMS Data Transfer Stop	со	This IE shall be forwarded to the MME if it is received from the BM-SC.	Absolute Time of MBMS Data Transfer	0
MBMS Flags	CO	<ul> <li>This IE shall be included if any one of the applicable flags is set to 1.</li> <li>Applicable flags: <ul> <li>Local MBMS Bearer Context Release Indication:</li> <li>this flag shall be set to 1 on the Sm/Sn interfaces if the MBMS Session Stop Request message is used to release the MBMS bearer context locally in the MME/SGSN (see 3GPP TS 23.007 [13]).</li> </ul> </li> </ul>		0
Private Extension	0		Private Extension	VS
NOTE 1: The conditional MBMS Flow Identifier IE is redundant as MBMS Session Stop Request message is sent over non-zero TEID header. The receiver may ignore the MBMS Flow Identifier IE.				

### 7.13.6 MBMS Session Stop Response

The MBMS Session Stop Response message shall be sent as a response to the MBMS Session Stop Request message on the Sm/Sn interface by the MME/SGSN to the MBMS GW.

Table 7.13.6-1 specifies the presence of the IEs in the message.

Possible Cause values are are specified in Table 8.4-1.

Information elements	Р	Condition / Comment	ІЕ Туре	Ins.
Cause	Μ		Cause	0
Recovery	со	This IE shall be included if contacting the peer for the first time.	Recovery	0
Private Extension	0		Private Extension	VS

Table 7.13.6-1: Information Elements in a MBMS Session Stop Response

# 8 GTP-C Information Elements

# 8.1 Information Element Types

A GTP control plane (signalling) message may contain several information elements. In order to have forward compatible type definitions for the GTPv2 information elements, all of them shall be TLIV (Type, Length, Instance, Value) coded. GTPv2 information element type values are specified in the Table 8.1-1. The last column of this table indicates whether the information element is:

- Fixed Length: the IE has a fixed set of fields, and a fixed number of octets.
- Variable Length: the IE has a fixed set of fields, and has a variable number of octets. For example, the last octets may be numbered similar to "5 to (n+4)". In this example, if the value of the length field, n, is 0, then the last field is not present.
- Extendable: the IE has a variable number of fields, and has a variable number of octets. The last fields are typically specified with the statement: "These octet(s) is/are present only if explicitly specified". The legacy receiving entity shall ignore the unknown octets.

In order to improve the efficiency of troubleshooting, it is recommended that the information elements should be arranged in the signalling messages as well as in the grouped IEs, according to the order the information elements are listed in the message definition table or grouped IE definition table in section 7. However the receiving entity shall be prepared to handle the messages with information elements in any order.

Within information elements, certain fields may be described as spare. These bits shall be transmitted with the value set to 0. To allow for future features, the receiver shall not evaluate these bits. GTPv2-C information elements that have similar semantics in GTPv1-C shall be converted into GTPv1-C format, as specified in TS 29.060 [4], before sending them to a pre-R8 GSN.

Table 8.1-1: Information Element types for GTPv2

#### 266

	Reserved		
	International Mobile Subscriber Identity (IMSI)	Variable Length / 8.3	Not Applicable
	Cause	Variable Length / 8.4	Not Applicable
3	Recovery (Restart Counter)	Variable Length / 8.5	Not Applicable
	Reserved for S101 interface	See 3GPP TS 29.276 [14]	See 3GPP TS 29.276 [14]
	Reserved for S121 interface	See 3GPP TS 29.276 [14]	See 3GPP TS 29.276 [14]
	STN-SR	See 3GPP TS 29.280 [15]	See 3GPP TS 29.280 [15]
	Reserved for Sv interface	See 3GPP TS 29.280 [15]	See 3GPP TS 29.280 [15]
	Access Point Name (APN)	Variable Length / 8.6	Not Applicable
	Aggregate Maximum Bit Rate (AMBR)	Fixed Length / 8.7	8
	EPS Bearer ID (EBI)	Extendable / 8.8	1
	IP Address	Variable Length / 8.9	Not Applicable
	Mobile Equipment Identity (MEI)	Variable Length / 8.10	Not Applicable
	MSISDN	Variable Length / 8.11	Not Applicable
	Indication	Extendable / 8.12	2 Not Appliaghla
	Protocol Configuration Options (PCO) PDN Address Allocation (PAA)	Variable Length / 8.13 Variable Length / 8.14	Not Applicable Not Applicable
	Bearer Level Quality of Service (Bearer QoS)	Extendable / 8.15	22
	Flow Quality of Service (Flow QoS)	Extendable / 8.16	21
	RAT Type	Extendable / 8.17	1
	Serving Network	Extendable / 8.18	3
		Variable Length / 8.19	Not Applicable
	Traffic Aggregation Description (TAD)	Variable Length / 8.20	Not Applicable
	User Location Information (ULI)	Extendable / 8.21	"f+4-4" (See Figure 8.21-1)
	Fully Qualified Tunnel Endpoint Identifier (F-TEID)	Extendable / 8.22	9/21/25
	TMSI	Variable Length / 8.23	Not Applicable
	Global CN-Id	Variable Length / 8.24	Not Applicable
	S103 PDN Data Forwarding Info (S103PDF)	Variable Length / 8.25	Not Applicable
	S1-U Data Forwarding Info (S1UDF)	Variable Length/ 8.26	Not Applicable
	Delay Value	Extendable / 8.27	1
	Bearer Context	Extendable / 8.28	Not Applicable
	Charging ID	Extendable / 8.29	4
	Charging Characteristics	Extendable / 8.30	2
	Trace Information	Variable Length / 8.31	Not Applicable
	Bearer Flags	Extendable / 8.32	1
	Reserved		
99	PDN Type	Extendable / 8.34	1
100	Procedure Transaction ID	Extendable / 8.35	1
101	Reserved		
	Reserved		
103	MM Context (GSM Key and Triplets)	Extendable / 8.38	"r+1-4" (See Figure 8.38-1)
104	MM Context (UMTS Key, Used Cipher and	Extendable / 8.38	"r+1-4" (See Figure 8.38-2)
	Quintuplets)		
	MM Context (GSM Key, Used Cipher and Quintuplets)	Extendable / 8.38	"r+1-4" (See Figure 8.38-3)
106	MM Context (UMTS Key and Quintuplets)	Extendable / 8.38	"r+1-4" (See Figure 8.38-4)
		Extendable / 8.38	"s+64-4" (See Figure 8.38-5)
	Quintuplets)		
	MM Context (UMTS Key, Quadruplets and	Extendable / 8.38	"r+1-4" (See Figure 8.38-6)
	Quintuplets)	Estas dable / 0.00	Not Any Post In
	PDN Connection	Extendable / 8.39	Not Applicable
	PDU Numbers P-TMSI	Extendable / 8.40	9 Not Appliaghla
		Variable Length / 8.41	Not Applicable
	P-TMSI Signature	Variable Length / 8.42	Not Applicable
	Hop Counter UE Time Zone	Extendable / 8.43	1
		Extendable / 8.44	2
	Trace Reference	Fixed Length / 8.45	6 Not Applicable
	Complete Request Message GUTI	Variable Length / 8.46 Variable Length / 8.47	Not Applicable Not Applicable
	F-Container	Variable Length / 8.48	Not Applicable
	F-Container	Variable Length / 8.49	Not Applicable
	PLMN ID	Variable Length / 8.50	Not Applicable
	Target Identification	Variable Length / 8.51	Not Applicable
	Reserved		
	Packet Flow ID	Variable Length / 8.53	Not Applicable
	RAB Context	Fixed Length / 8.54	9
		Variable Length / 8.55	Not Applicable
125	Source RNC PDCP Context Info Port Number		
125 126	Port Number	Extendable / 8.56	2
125 126 127			

IE Type value (Decimal)	Information elements	Comment / Reference	Number of Fixed Octets	
130	Reserved			
131	Change Reporting Action	Variable Length / 8.61	Not Applicable	
132	Fully Qualified PDN Connection Set Identifier (FQ- CSID)	Extendable / 8.62	"q+1-4" (See Figure 8.62-1)	
133	Channel needed	Variable Length / 8.63	Not Applicable	
134	eMLPP Priority	Variable Length / 8.64	Not Applicable	
135	Node Type	Extendable / 8.65	1	
136	Fully Qualified Domain Name (FQDN)	Variable Length / 8.66	Not Applicable	
137	Transaction Identifier (TI)	Variable Length / 8.68	Not Applicable	
138	MBMS Session Duration	Extendable / 8.69	3	
139	MBMS Service Area MBMS Session Identifier	Variable Length / 8.70 Extendable / 8.71	Not Applicable	
<u>140</u> 141	MBMS Flow Identifier	Extendable / 8.72	1 2	
142	MBMS IP Multicast Distribution	Extendable / 8.73	"m+1-4" (See Figure 8.73-1)	
143	MBMS Distribution Acknowledge	Extendable / 8.74	1	
144	RFSP Index	Fixed Length / 8.77	2	
145	User CSG Information (UCI)	Extendable / 8.75	8	
146	CSG Information Reporting Action	Extendable / 8.76	1	
147	CSG ID	Extendable / 8.78	4	
148	CSG Membership Indication (CMI)	Extendable / 8.79	1	
149	Service indicator	Fixed Length / 8.80	1	
<u>150</u> 151	Detach Type Local Distiguished Name (LDN)	Fixed Length / 8.81 Variable Length / 8.82	1 Not Applicable	
152	Node Features	Extendable / 8.83		
153	MBMS Time to Data Transfer	Extendable / 8.84	1	
154	Throttling	Extendable / 8.85	2	
155	Allocation/Retention Priority (ARP)	Extendable / 8.86	1	
156	EPC Timer	Extendable / 8.87	1	
157	Signalling Priority Indication	Extendable / 8.88	1	
158	Temporary Mobile Group Identity (TMGI)	Extendable / 8.89	6	
159	Additional MM context for SRVCC	Extendable / 8.90	"e-4" (See Figure 8.90-1)	
160	Additional flags for SRVCC	Extendable / 8.91	1	
<u>161</u> 162	Reserved MDT Configuration	Extendable / 8.93	"q-4" (See Figure 8.93-1)	
163	Additional Protocol Configuration Options (APCO)	Extendable / 8.94	"m-4" (See Figure 8.93-1)	
164	Absolute Time of MBMS Data Transfer	Extendable / 8.95	8	
165	H(e)NB Information Reporting	Extendable / 8.96	1	
166	IPv4 Configuration Parameters (IP4CP)	Extendable / 8.97	5	
167	Change to Report Flags	Extendable / 8.98	1	
168	Action Indication	Extendable / 8.99	1	
169	TWAN Identifier	Extendable / 8.100	"k+6-4" (See Figure 8.100-1)	
170	ULI Timestamp	Extendable / 8.101	4	
171 172	MBMS Flags RAN/NAS Cause	Extendable / 8.102 Extendable / 8.103	1 "m-4" (See Figure 8.103-1)	
172	CN Operator Selection Entity	Extendable / 8.103	111-4 (See Figure 8.103-1)	
174	Trusted WLAN Mode Indication	Extendable / 8.104	1	
175	Node Number	Extendable / 8.106	"p-4" (See Figure 8.106-1)	
176	Node Identifier	Extendable / 8.107	"q-4" (See Figure 8.107-1)	
177	Presence Reporting Area Action	Extendable / 8.108	"t-4" (See Figure 8.108-1)	
178	Presence Reporting Area Information	Extendable / 8.109	4	
179	TWAN Identifier Timestamp	Extendable / 8.110	4	
180	Overload Control Information	Extendable / 8.111	Not Applicable	
181	Load Control Information	Extendable / 8.112	Not Applicable	
182	Metric Seguence Number	Fixed Length / 8.113 Fixed Length / 8.114	1 4	
<u>183</u> 184	Sequence Number APN and Relative Capacity	Extendable / 8.114	4 "m-4" (See Figure 8.115	
185	WLAN Offloadability Indication	Extendable / 8.116	1	
186	Paging and Service Information	Extendable / 8.117	m-4 (See Figure 8.117-1)	
187	Integer Number	Variable / 8.118	Not Applicable	
188	Millisecond Time Stamp	Extendable / 8.119	6	
189	Monitoring Event Information	Extendable / 8.120	"k+2-4" (See Figure 8.120-1)	
190	ECGI List	Extendable / 8.121	"m*7+2" (See Figure 8.121-1)	
191	Remote UE Context	Extendable / 8.122	Not Applicable	
192	Remote User ID	Extendable / 8.123	"c-4" (see Figure 8.123-1)	
<u>193</u> 194	Remote UE IP information CloT Optimizations Support Indication	Variable Length / 8.124 Extendable / 8.125	Not Applicable	
194	SCEF PDN Connection	Extendable / 8.125	Not Applicable	
195	Header Compression Configuration	Extendable / 8.120	4	
190	Extended Protocol Configuration Options (ePCO)	Variable Length / 8.128	Not Applicable	
	Serving PLMN Rate Control	Extendable / 8.129		

IE Type	Information elements	Comment / Reference	Number of Fixed Octets					
value								
(Decimal								
199	Counter	Extendable / 8.130	5					
200	Mapped UE Usage Type	Extendable / 8.131	2					
201 to 253	Spare. For future use.							
254	Special IE type for IE Type Extension	See NOTE 2	Not Applicable					
255	Private Extension	Variable Length / 8.67	Not Applicable					
256 to 6553	5 Spare. For future use.							
NOTE 1:	The size of the TLI (Type, Length and Instance) fie	elds, i.e "4" octets, has been su	ubtracted from the number of					
	the fixed octets of the "Fixed Length" and "Extendation	able" IEs. Hence for some of the	ne "Extendable" IEs, for					
	which the length is defined in terms of variable nur	nber of octets, "4" is explicitly	subtracted while defining the					
	fixed number of octets. E.g. Length of User Location Information is defined as "f+4" and fixed number of							
	octets for the same is defined as "f+4-4".							
NOTE 2:	TE 2: The IE Type value 254 indicates that the IE Type shall be further identified by an IE Type Extension field; see							
	subclause 8.2.1A. A GTP-C entity which does not							
	field shall ignore an IE received with the IE Type va							

### 8.2 Information Element Format

#### 8.2.1 General

Figure 8.2-1 depicts the format of an information element.

	Bits									
Octets	8	7	6	5	4	3	2	1		
1	Type = xxx (decimal)									
2 to3				Leng	th = n					
4		Spare Instance								
5 to (n+4)		IE spe	ecific da	ta or co	ntent of	f a grou	ped IE			

Figure 8.2-1: Information Element Format

An IE has the following mandatory fields:

- Type field: This field indicates the type of Information Element. The valid values of the IE type are defined in clause 8.1.
- Length: This field contains the length of the information element excluding the first four octets, which are common for all information elements (Type, Length and the contents of octet 4) and is denoted "n" in Figure 8.2-1. For all the length fields, bit 8 of the lowest numbered octet is the most significant bit and bit 1 of the highest numbered octet is the least significant bit.
- Instance: This field shall be used to differentiate amongst different parameters in one specific message which use the same information element type (see also subclause 6.1.3 "Information Element Instance").

An IE is said to be TLIV (Type, Length, Instance, Value) encoded.

#### 8.2.1A Information Element with an IE Type Extension field

Figure 8.2.1A-1 depicts the format of an information element with an IE Type Extension field.

	Bits										
Octets	8	7	6	5	4	3	2	1			
1	Type = 254 (decimal)										
2 to 3	Length = n										
4		Sp	are			Inst	ance				
5 to 6	IE Type Extension										
7 to n+4		IE sp	ecific d	ata or c	ontent	of a gro	up IE				

Figure 8.2.1A-1: Information Element with an IE Type Extension field

The IE Type in octet 1 of an information element with an IE Type Extension field shall be set to 254. Such IE shall be further identified by the value encoded in the IE Type Extension field in octets 5 and 6.

The value of the IE Type Extension shall be encoded in full hexadecimal representation (binary, not ASCII encoding) from 256 up to 65535. This field indicates the type of the Information Element and the valid values of the IE type Extension field are defined in subclause 8.1.

The semantics of the Length and Instance field remain the same as specified in subclause 8.2.1.

### 8.2.2 Handling ASN.1/PER encoded parameters

During the TAU/RAU/HO procedures MME/S4-SGSN GTPv2 entities send some of the RANAP/S1AP/BSSGP parameters to a GTPv2 peer. Copying of the BSSGP parameters into GTPv2 IEs is straightforward. RANAP and S1AP, however, use ASN.1/PER encoding, which is different from GTPv2 specific TLV encoding.

Transparent copying of RANAP/S1AP parameters across GTPv2 interfaces:

- a GTPv2 entity shall transparently copy the respective information into one or more octets of the GTPv2 IE as specified in Annex B and clause 8.48. With this approach, GTPv2 will not be impacted if the contents of such RANAP/S1AP parameter changes over the time.

Non-transparent copying of RANAP/S1AP parameters across GTPv2 interfaces:

- GTPv2 entity decodes ASN.1/PER parameter and shall encode the value(s) into one or more octets of the GTPv2 IE according to what is specified in the present document.

# 8.3 International Mobile Subscriber Identity (IMSI)

International Mobile Subscriber Identity (IMSI) is transferred via GTP tunnels. The sending entity copies the value part of the IMSI into the Value field of the IMSI IE. IMSI is defined in 3GPP TS 23.003 [2].

	Bits										
Octets	8	7	6	5	4	3	2	1			
1	Type = 1 (decimal)										
2 to 3		Length = n									
4		Sp	are		Instance						
5		Numbe	r digit 2		Number digit 1						
6		Numbe	r digit 4		Number digit 3						
n+4	Number digit m Number digit m-1										

Figure 8.3-1: IMSI

Octets 5 to (n+4) represent the IMSI value in international number format as described in ITU-T Rec E.212 [64], encoded as TBCD digits, i.e. digits from 0 through 9 are encoded "0000" to "1001". When there is an odd number of digits, bits 8 to 5 of the last octet are encoded with the filler "1111". The maximum number of digits is 15.

#### 8.4 Cause

Cause IE is coded as depicted in Figure 8.4-1.

Bits										
8	7	6	5	4	3	2	1			
	Type = 2 (decimal)									
	Length = n									
	Sp	are		Instance						
			Cause	e value						
		Spare			PCE	BCE	CS			
		Туре	e of the	offendi	ng IE					
		Length	of the o	offendin	g IE = 0	)				
	Sp	are			Inst	ance				
	8	Sp	T Spare Spare Type	8         7         6         5           Type = 2           Leng           Spare           Spare           Type of the           Length of the colspan=	8         7         6         5         4           Type = 2 (decim           Length = n           Spare           Cause value           Spare           Type of the offendin           Length of the offendin	8         7         6         5         4         3           Type = 2 (decimal)           Length = n           Spare         Instance           Cause value           Spare         PCE           Type of the offending IE           Length of the offending IE	8         7         6         5         4         3         2           Type = 2 (decimal)           Length = n           Spare         Instance           Cause value           Spare         PCE         BCE           Type of the offending IE           Length of the offending IE           Length of the offending IE			

Figure 8.4-1: Cause

270

Cause is a variable length IE, which may have either of the following two lengths values:

- If n = 2, a = 0 and the Cause IE shall be 6 octets long. Therefore, octets "a(n+1) to a(n+4)" will not be present.
- If n = 6, a = 1 and the Cause IE will be 10 octets long.

For PMIP based S5/S8, the SGW/MAG shall do the mapping between GTPv2 Cause IE and respective PMIPv6 IE as specified in 3GPP TS 29.275 [26].

The following bits within Octet 6 indicate:

- Bits 8 to 4: Spare, for future use and set to zero
- Bit 1 CS (Cause Source): If this bit is set to 1, it indicates that the corresponding error cause is originated by the remote node (i.e., the MME/SGSN to a PGW, or the PGW to an MME/SGSN). This bit is set to 0 to denote that the corresponding error cause is originated by the node sending the message.

The CS should be set to 1 by the SGW when the SGW relay a response message with cause value from the MME/SGSN to the PGW or from the PGW to the MME/SGSN. For PMIP based S5/S8, the SGW shall set the CS bit to 1 when the SGW/MAG relay a response message with the cause value from the PGW/LMA to the MME/SGSN.

- Bit 2 BCE (Bearer Context IE Error): If this bit is set to 1, it indicates that the corresponding rejection cause is due to the error in the Bearer Context IE. This bit shall be discarded if the cause value is one of Acceptance cause value as given in table 8.4-1.
- Bit 3 PCE (PDN Connection IE Error): If this bit is set to 1, it indicates that the corresponding rejection cause is due to the error in the PDN Connection IE. This bit shall be discarded if the cause value is one of Acceptance cause value as given in table 8.4-1.

The Cause value shall be included in a response message. In a response message, the Cause value indicates the acceptance or the rejection of the corresponding request message. The Cause value indicates the explicit reason for the rejection.

If the rejection is due to a mandatory IE or a verifiable conditional IE is faulty or missing, the offending IE shall be included within an additional field "a(n+1) to a(n+4)". Only Type and Instance fields of the offending IE that caused the rejection have a meaning. The length in the Octet 8-9 and spare bits in the Octet 10 shall be set to "0". In this case, the value of "n" shall be "6". Otherwise, the value of "n" is equal to "2".

The Cause may also be included in the request message. In a request message, the Cause value indicates the reason for the request.

"Request accepted" is returned when the GTPv2 entity has accepted a control plane request.

"Context Not Found" is used in the response message by a GTP entity when it receives a message for which it does not have context, e.g. TEID-C or EBI is not known. When "Context Not Found" is received at Bearer Context IE level, it means the bearer context is unknown in the peer. When "Context Not Found" is received at message level together with a known TEID-C in the GTPv2-C header in the response message, this indicates some bearer contexts are not known in the peer; the sender of the request message should further determine, based on the bearer context(s) included in the request message, that:

- if the default bearer is unknown, this means the PDN connection is not known in the peer;
- if one or more dedicated bearers are unknown, this means only those dedicated bearer contexts are not known in the peer.

"Context Not Found" may be used by the PGW in the Create Session Response message during the non-3GPP to 3GPP access handover procedures, if the request corresponds to the handover of a PDN connection which does not exist in the PGW.

"Context Not Found" may be used by the PGW in the Create Session Response message during the 3GPP to non-3GPP access handover procedures, if the request corresponds to the handover of a PDN connection which does not exist in the PGW.

"Service not supported" is used by the GTP entity when it receives a message, which corresponds to a feature or a service which is not supported by the node.

"Service denied" is used when the requested service cannot be granted.

"System failure" is used by the GTP entity to indicate a generic error condition.

"No resources available" is used by the GTP entity to indicate the temporary unavailability of the resource(s) to process the received request.

"Semantic error in the TFT operation", "Syntactic error in the TFT operation", "Semantic errors in packet filter(s)", "Syntactic errors in packet filters(s)", "UE context without TFT already activated", "Semantic error in the TAD operation" and "Syntactic error in the TAD operation" are indications of error cases involving TFT(s)/TAD(s) as specified in subclause 7.7.11 in this specification.

"Missing or unknown APN" is used by the PGW when it does not support the Access Point Name, received in Create Session Request message.

"Relocation failure" is used by the target MME/S4-SGSN to indicate the source MME/S4-SGSN that the relocation has failed.

"Relocation failure due to NAS message redirection" is used by the new MME/S4-SGSN to indicate to the old MME/S4-SGSN that the TAU/RAU procedure is not successful due to NAS message redirection as described in 3GPP TS 23.401 [3].

"Denied in RAT" is used by the GTP entity to indicate that the requested service is not accepted in the RAT.

"Preferred PDN type not supported" is used by the PGW to indicate that the PDN type received in the Create Session Request message is not supported by the PGW for the PDN corresponding to the received Access Point Name.

"Protocol type not supported" is used by the SGW to indicate that the S5/S8 protocol type requested by the MME/S4-SGSN is not supported by it.

"UE not responding" is used by the MME/S4-SGSN to indicate that the UE is not responding to the request initiated by the network, e.g. Paging.

"UE refuses" is used by the GTP entity to indicate that the UE, without specifying further detail, rejected the request from the network.

"Unable to page UE" is used by the MME/S4-SGSN to indicate its inability to page the UE, temporarily.

"User authentication failed" is used by the GTP entity to indicate that the request is rejected due to failure in authentication/security procedure.

"APN access denied – no subscription" is used to indicate that the PGW has denied the user access to an APN because a subscription is required, but the subscriber does not have the necessary subscription.

"Remote peer not responding" is used by the SGW for the messages spanning through two interfaces. This cause value is returned by the SGW to the MME/S4-SGSN or PGW in a response message where no response message is received from the PGW or MME/S4-SGSN.

"Collision with network initiated request" is used by the PGW to indicate that the UE-initiated bearer resource allocation/modification request is rejected since the PGW has requested a bearer resource allocation/modification for the same service using a network-initiated procedure.

"Unable to page UE due to Suspension" is used by the MME/S4-SGSN to indicate that the UE has not been paged because the bearers of the UE are in a suspended state.

"APN Restriction type Incompatible with currently active PDN connection" is used by the PGW to indicate that the newly requested PDN connection has APN restriction value that is not compatible with the currently active PDN connection(s)'s APN restriction value(s).

"Invalid peer" is used by the SGW to indicate that currently the UE is being managed by the different node (e.g. MME/S4-SGSN) than the node (e.g. S4-SGSN/MME) which has sent the Delete Session Request message.

"Invalid Reply from remote peer" is used by the SGW for the messages spanning through two interfaces. This cause value is returned by the SGW to the MME/SGSN or PGW in a reply message where the corresponding reply message on S5/S8 or S11/S4 from the PGW or MME/SGSN is not decoded as valid.

"Temporarily rejected due to handover/TAU/RAU procedure in progress" is used by the MME/S4-SGSN for the bearer related procedure initiated by the PGW. When the handover/TAU/RAU with/without SGW change and/or MME/S4-SGSN change is in progress, the MME/S4-SGSN may receive Create / Update / Delete Bearer request message for the bearer creation, modification or deletion initiated by the PGW. If the handover/TAU/RAU procedure results in the SGW and/or MME/S4-SGSN change, then the bearer related procedure cannot be handled temporarily by the MME/S4-SGSN till the handover/TAU/RAU procedure is completed. In that case the MME/S4-SGSN shall reject the bearer related procedure with this rejection cause. This cause is also used to indicate that the Downlink Data Notification message is rejected temporarily due to the mobility procedures with MME or SGSN change in progress as specified in sub-clause 5.3.4.3 in 3GPP TS 23.401 [3].

The usage of "Fallback to GTPv1" is specified in subclause 7.10 "Fallback to GTPv1 mechanism".

In the PGW initiated bearer deactivation procedure for the default bearer, the PGW may include the Cause IE in the Delete Bearer Request with values "RAT changed from 3GPP to Non-3GPP", "Reactivation requested" or "Reactivation disallowed to APN".

"APN Congestion" is used by the PGW and it indicates that the PGW has detected congestion for the requested APN and performs overload control for that APN which does not allow the PDN connection to be established.

"GTP-C Entity Congestion" is used to indicate that the GTP-C entity has detected node level congestion and performs overload control at the node level, which does not allow the request to be processed.

"UE already re-attached" is used by MME/S4-SGSN for the network triggered service restoration procedure as specified in 3GPP TS 23.007 [17]. The MME/S4-SGSN may send the Downlink Data Notification Acknowledge or Downlink Data Notification Failure Indication with this cause as part of the network triggered service restoration procedure.

"PDP connection inactivity timer expires" is used by the PGW in Delete Bearer Request(s) to indicate that all the bearer(s) for the emergency PDN connection are deleted upon the inactivity timer expiry as specified in 3GPP TS 23.203 [48].

"Network failure" is used by the SGSN or MME in the Delete Session Request to indicate that the message is sent due to a network problem.

"QoS parameter mismatch" is used by the SGSN or MME in the Delete Session Request to indicate that the PDN connection can not be established due to a QoS parameter mismatch.

"MME/SGSN refuses due to VPLMN policy" is used by the MME/SGSN in the VPLMN to indicate to the PGW in the Create Bearer Response or Update Bearer Response that it does not allow the establishment or modification of the bearer due to VPLMN operator's policy.

The listed cause values for rejection response message descriptions in clause 7 are not meant to be exhaustive lists. Therefore a GTPv2 node shall use the most appropriate matching rejection response cause value that is listed in Table 8.4-1.

If a Bearer Resource Command message is related to an established PDN connection for LIPA or for SIPTO at the local network, the LGW shall reject the Bearer Resource Command with the cause value of "Bearer handling not supported".

"Multiple PDN connections for a given APN not allowed" is used by SGW for reply message to the MME/S4-SGSN when PMIP-based S5/S8 is used. If either SGW or PGW does not support the multiple PDN connections to the same APN function, the SGW shall reject the PDN connectivity request procedure with this rejection cause when receiving Create Session Request for additional PDN connectivity to the given APN from the same UE.

As specified in sub-clause 5.3.1.1 in 3GPP TS 23.401 [3] and sub-clause 9.2.1 in 3GPP TS 23.060 [35], the cause value "New PDN type due to network preference" indicates that the UE has requested PDN type IPv4v6 and only IPv4 or IPv6 address is allowed for the PDN based on PGW operator policy.

As specified in sub-clause 5.3.1.1 in 3GPP TS 23.401 [3] and sub-clause 9.2.1 in 3GPP TS 23.060 [35], the cause value "New PDN type due to single address bearer only" indicates that the MS has requested PDN type IPv4v6 and both IPv4 and IPv6 addressing is possible in the PDN but the Dual Address Bearer Flag of the Indication IE is set to 0 or the Indication IE is absent, or only single IP version addressing is possible in the PDN.

"PGW not responding" is used by the SGW in PGW Restart Notification to indicate that the peer PGW has failed and not restarted as specified in subclause 7.9.5.

"UE context without TFT already activated" is used by the PGW in the Bearer Resource Failure Indication message to indicate that the PGW has received the Bearer Resource Command message without TAD IE in the secondary PDP Context Activation procedure.

"Target access restricted for the subscriber" is used by the MME/SGSN in the Context Response message to indicate that the target access is prohibited for the subscriber, based on the subscription profile.

"P-TMSI Signature mismatch" is used by the SGSN or MME in the Identification Response and Context Response message if the P-TMSI Signature stored in the old SGSN or MME does not match the value sent by the UE via the new SGSN or MME.

"Late Overlapping Request" is used by the PGW in the Create Session Response to indicate that the incoming request collides with an existing session which has a more recent time stamp than the time stamp of the new request, as specified in subclause 13.2.

"Timed Out Request" is used by the SGW and PGW in the Create Session Response to indicate that the incoming request is known to have already timed out at the originating entity, as specified in subclause 13.3.

"UE is temporarily not reachable due to power saving" is used by the MME/SGSN in the Create/Update Bearer Response message to reject the corresponding network initiated procedures for a Delay Tolerant PDN connection and also request the PGW to hold the network initiated procedure until it receives the subsequent Modify Bearer Request message with the UASI flag indicating that the UE is available for end to end signalling.

"UE not authorised by OCS or external AAA Server" is used by the PGW in the Create Session Response to reject the corresponding UE initiated procedures when the OCS or an external AAA Server on SGi did not authorise it and the support of the Cause Code was indicated by the SGSN/MME within the Create Session Request.

If a Create Session Request message requests the addition of an access to a PDN connection, and NBIFOM is not supported by the MME/SGSN, SGW or TWAN, the PGW should reject the request with the cause value of "Multiple accesses to a PDN connection not allowed". This cause is also used by the PGW in the Delete Bearer Request message to initiate the removal of 3GPP access from the PDN connection due to detection of the MME/SGSN or SGW not supporting NBIFOM at the inter-PLMN mobility procedure.

"Request rejected due to UE capability" is used by the MME in the Create Bearer Response to reject the request to add an EPS bearer that would exceed the UE capability (e.g. a NB-IoT UE can only support up to 2 EPS bearers). This cause value does not prevent the PGW from sending Create Bearer Request later.

#### Table 8.4-1: Cause values

Message Type	Cause value (decimal)	Meaning
	0	Reserved. Shall not be sent and if received the Cause shall be treated as an invalid IE
Request / Initial	1	Reserved
message	2	Local Detach
	3	Complete Detach
Ĺ	4	RAT changed from 3GPP to Non-3GPP
Ĺ	5	ISR deactivation
Ļ	6	Error Indication received from RNC/eNodeB/S4-SGSN/MME
Ļ	7	IMSI Detach Only
Ļ	8	Reactivation Requested
	9	PDN reconnection to this APN disallowed
	<u>10</u> 11	Access changed from Non-3GPP to 3GPP PDN connection inactivity timer expires
	12	PGW not responding
	13	Network Failure
ŀ	14	QoS parameter mismatch
-	15	Spare. This value range shall be used by Cause values in an initial/request message. See NOTE 5.
	16	Request accepted
Acceptance in a	17	Request accepted partially
Response /	18	New PDN type due to network preference.
triggered message. See	19	New PDN type due to single address bearer only.
NOTE 1.	20 to 63	Spare. This value range shall be used by Cause values in an acceptance
		response/triggered message
Rejection in a	64	Context Not Found
Response /	65	Invalid Message Format
triggered	66	Version not supported by next peer
message. See NOTE 1.	67	Invalid length
	68	Service not supported
	<u>69</u> 70	Mandatory IE incorrect Mandatory IE missing
F	70	Shall not be used. See NOTE 2 and NOTE 3.
ŀ	72	System failure
ŀ	73	No resources available
F	74	Semantic error in the TFT operation
ľ	75	Syntactic error in the TFT operation
Γ	76	Semantic errors in packet filter(s)
[	77	Syntactic errors in packet filter(s)
	78	Missing or unknown APN
ļ	79	Shall not be used. See NOTE 2 and NOTE 3.
Ļ	80	GRE key not found
Ļ	81	Relocation failure
	82	Denied in RAT
	83	Preferred PDN type not supported
	<u>84</u> 85	All dynamic addresses are occupied UE context without TFT already activated. See NOTE 6.
	86	Protocol type not supported
ŀ	87	UE not responding. See NOTE 7.
F	88	UE refuses
F	89	Service denied. See NOTE 7.
ľ	90	Unable to page UE
ľ	91	No memory available
ſ	92	User authentication failed
[	93	APN access denied – no subscription
[	94	Request rejected (reason not specified)
ļ	95	P-TMSI Signature mismatch
Ļ	96	IMSI/IMEI not known
Ļ	97	Semantic error in the TAD operation
	<u>98</u> 99	Syntactic error in the TAD operation
F	uu	Shall not be used. See NOTE 2 and NOTE 3.
F		
- - -	<u> </u>	Remote peer not responding Collision with network initiated request

		103	Conditional IE missing
		103	APN Restriction type Incompatible with currently active PDN connection
		104	Invalid overall length of the triggered response message and a piggybacked
		105	initial message
		106	Data forwarding not supported
		100	Invalid reply from remote peer
		107	Fallback to GTPv1
		109	Invalid peer
		110	Temporarily rejected due to handover/TAU/RAU procedure in progress
		110	Modifications not limited to S1-U bearers
		112	Request rejected for a PMIPv6 reason (see 3GPP TS 29.275 [26]).
		113	APN Congestion
		114	Bearer handling not supported
		115	UE already re-attached. See NOTE 7.
		116	Multiple PDN connections for a given APN not allowed
		117	Target access restricted for the subscriber
		118	Shall not be used. See NOTE 2 and NOTE 3.
		119	MME/SGSN refuses due to VPLMN Policy
		120	GTP-C Entity Congestion
		121	Late Overlapping Request
		122	Timed out Request
		123	UE is temporarily not reachable due to power saving
		124	Relocation failure due to NAS message redirection
		125	UE not authorised by OCS or external AAA Server
		126	Multiple accesses to a PDN connection not allowed
		127	Request rejected due to UE capability
		128 to 239	Spare. For future use in a triggered/response message See NOTE 4.
Request	/ Initial	240 to 255	Spare. For future use in an initial/request message. See NOTE 5.
messa		2.010200	
		ed cause values	for rejection in a response/triggered message can be also used for request
			t message is triggered by a command message.
NOTE 2:			ntically incorrect Information Element" specifies quite strict handling of the
-			erefore this table shall not contain any reserved values.
NOTE 3:			earlier versions of the spec. If received, it shall be interpreted as unspecified
			ified/unrecognized rejection cause shall be treated in the same ways as the cause
			ted (reason not specified)".
NOTE 4:			used in the newer versions of the spec. If the receiver cannot comprehend the
-			eted as unspecified rejection cause. Unspecified/unrecognized rejection cause
			ame ways as the cause value 94 "Request rejected (reason not specified)".
NOTE 5:			used in the newer versions of the spec. If the receiver cannot comprehend the
			eted as an unspecified request/initial message cause. Unspecified/unrecognized
			uest/initial message shall be implementation dependent (e.g. may be ignored).
NOTE 6:			y used over the S4, S5 and S8 interface in the secondary PDP Context Activation
			1A in 3GPP TS 23.060 [4]).
NOTE 7:			lso be used by a Downlink Data Notification Failure Indication, which is an initial
	messa	•	

The mapping at the MME/S4-SGSN between GTP cause values received over the S11/S4 interface and the NAS cause values sent to the UE is specified in Annex C.

# 8.5 Recovery (Restart Counter)

Recovery IE is coded as depicted in Figure 8.5-1.

The Recovery (Restart Counter) is encoded as 1 octet.




Figure 8.5-1: Recovery (Restart Counter)

# 8.6 Access Point Name (APN)

Access Point Name (APN) is transferred via GTP tunnels. The sending entity copies the value part of the APN into the Value field of the APN IE.




Figure 8.6-1: Access Point Name (APN)

The encoding the APN field follows 3GPP TS 23.003 [2] subclause 9.1. The content of the APN field shall be the full APN with both the APN Network Identifier and APN Operator Identifier being present as specified in 3GPP TS 23.003 [2] subclauses 9.1.1 and 9.1.2, 3GPP TS 23.060 [35] Annex A and 3GPP TS 23.401 [3] subclauses 4.3.8.1.

NOTE: The APN field is not encoded as a dotted string as commonly used in documentation.

# 8.7 Aggregate Maximum Bit Rate (AMBR)

Aggregate Maximum Bit Rate (AMBR) is transferred via GTP tunnels. The sending entity copies the value part of the AMBR into the Value field of the AMBR (APN-AMBR) IE.

AMBR is defined in clause 9.9.4.2 of 3GPP TS 24.301 [23], but shall be formatted as shown in Figure 8.7-1 as Unsigned32 binary integer values in kbps (1000 bits per second).

	Bits									
Octets	8	7	6	5	4	3	2	1		
1	Type = 72 (decimal)									
2 to 3				Leng	th = 8					
4		Sp	are			Inst	ance			
5 to 8	APN-AMBR for uplink									
9 to 12			APN	-AMBR	for dov	vnlink				

Figure 8.7-1: Aggregate Maximum Bit Rate (AMBR)

The APN-AMBR for uplink and the APN-AMBR for downlink may require converting values in bits per second to kilo bits per second when the APN-AMBR for uplink and the APN-AMBR for downlink are received from an interface other than GTPv2 interface. If such conversions result in fractions, then the value of APN-AMBR for uplink and the APN-AMBR for downlink shall be rounded upwards.

# 8.8 EPS Bearer ID (EBI)

EPS Bearer ID (EBI) is coded as depicted in Figure 8.8-1.

The overall length of the IE is 5 octets. In future releases of the spec additional octets may be specified and new semantic for the spare bits may be defined.

		Bits										
Octets	8	7	6	5	4	3	2	1				
1		Type = 73 (decimal)										
2 to 3				Leng	th = n							
4		Sp	are		Instance							
5	Spa	Spare (all bits set to 0) EPS Bearer ID (EBI)										
6 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified				

Figure 8.8-1: EPS Bearer ID (EBI)

The coding of EBI field and its value range is specified in 3GPP TS 24.007 [30], subclause 11.2.3.1.5, bits 5 to 8.

278

# 8.9 IP Address

IP Address is coded as depicted in Figure 8.9-1. The Length field may have only two values (4 or 16) that determine if the Value field contains IPv4 or IPv6 address.




Figure 8.9-1: IP address

# 8.10 Mobile Equipment Identity (MEI)

Mobile Equipment Identity (MEI) is coded as depicted in Figure 8.10-1. MEI is defined in subclause 6.2 of 3GPP TS 23.003 [2].




Figure 8.10-1: Mobile Equipment (ME) Identity (MEI)


The ME Identity field contains either the IMEI or the IMEISV as defined in subclause 6.2 of 3GPP TS 23.003 [2]. It is encoded as specified in subclause 7.7.53 of 3GPP TS 29.060 [4], beginning with octet 4 of Figure 7.7.53.1.

The IMEI(SV) digits are encoded using BCD coding where IMEI is 15 BCD digits and IMEISV is 16 BCD digits. For IMEI, bits 5 to 8 of the last octet shall be filled with an end mark coded as '1111'.

# 8.11 MSISDN

MSISDN is transferred via GTP tunnels. The sending entity copies the value part of the MSISDN into the Value field of the MSISDN IE. MSISDN is defined in 3GPP TS 23.003 [2].

	Bits											
Octets	8	7	6	5	4	3	2	1				
1		Type = 76 (decimal)										
2 to 3		Length = n										
4		Sp	are		Instance							
5		Numbe	r digit 2		Number digit 1							
6		Numbe	r digit 4		Number digit 3							
n+4	Number digit m Number digit m-1											



Octets 5 to (n+4) represent the MSISDN value is in international number format as described in ITU-T Rec E.164 [25] and 3GPP TS 29.002 [41]. MSISDN value contains only the actual MSISDN number (does not contain the "nature of address indicator" octet, which indicates "international number" as in 3GPP TS 29.002 [41]) and is encoded as TBCD digits, i.e. digits from 0 through 9 are encoded "0000" to "1001". When there is an odd number of digits, bits 8 to 5 of the last octet are encoded with the filler "1111".

# 8.12 Indication

Indication is coded as depicted in Figure 8.12-1.

	Bits									
Octets	8	7	6	5	4	3	2	1		
1			Ту	pe = 77	(decim	ial)				
2 to 3				Leng	th = n					
4		Spare Instance								
5	DAF	DTF	HI	DFI	OI	ISRSI	ISRAI	SGW		
								CI		
6	SQCI	UIMSI	CFSI	CRSI	Р	PT	SI	MSV		
7	RetLo	PBIC	SRNI	S6AF	S4AF	MBM	ISRA	CCRS		
	с					DT	U	I		
8	CPRA		PPOF	PPON	PPSI	CSFBI	CLII	CPSR		
	I	ARRL		/PPEI						
9	NSI	UASI	DTCI	BDWI	PSCI	PCRI	AOSI	AOPI		
10	ROAA	EPCO	CPOP	PMTS	S11T	PNSI	UNAC	WPM		
	I	SI	CI	MI	F		CSI	SI		
11	Spare	Spare	Spare	Spare	Spare	Spare	ENBC	TSPC		
							RSI	MI		
12 to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified		

Figure 8.12-1: Indication

For each message the applicable flags of the Indication IE shall be clearly specified in the individual message sub clause. The remaining flags of the Indication IE not so indicated shall be discarded by the receiver.

The receiver shall consider the value of the applicable flags as "0", if the Indication IE is applicable for the message but not included in the message by the sender.

The following bits within Octet 5 shall indicate:

- Bit 8 DAF (Dual Address Bearer Flag): This bit shall be set when the PDN Type, determined based on UE request and subscription record, is set to IPv4v6 and all SGSNs which the UE may be handed over to are Release 8 or above supporting dual addressing, which is determined based on node pre-configuration by the operator..
- Bit 7 DTF (Direct Tunnel Flag): This bit shall be set when the UE is in UTRAN and Direct Tunnel is selected
- Bit 6 HI (Handover Indication): If this bit is set to 1 over S11/S4 and S5/S8 interfaces, it shall indicate a UE handover from Trusted or Untrusted non-3GPP access to 3GPP access. This bit is applicable during the Handover from Trusted or Untrusted Non-3GPP IP Access to E-UTRAN or a Handover from Trusted or Untrusted Non-3GPP IP Access to UTRAN/GERAN procedures (see sub-clauses 8.2, 8.6 and 16.11 of 3GPP TS 23.402 [45]). . If this bit is set to 1 over GTP based S2a interface, it shall indicate a UE handover from 3GPP access and UE requested IP address preservation. If this bit is set to 1 over GTP based S2b interface, it shall indicate a UE handover from 3GPP access and UE requested IP address preservation.
- Bit 5 DFI (Direct Forwarding Indication): If this bit is set to 1, it shall indicate that the direct forwarding between the source eNodeB and the target eNodeB during the S1 based handover procedure is applied.
- Bit 4 OI (Operation Indication):
  - If this bit is set to 1, it shall denote that the receiving SGW of a "Create Session Request" shall send a Modify Bearer Request immediately to the PGW. This allows the SGW to differentiate if the "Create Session Request" received on S4/S11 interface belongs to a TAU/RAU with an SGW relocation (OI = 1), or X2-based handover with SGW relocation (OI = 1) or Enhanced SRNS Relocation with SGW relocation (OI=1) or MME triggered Serving GW relocation (OI = 1) or S1-based handover with SGW relocation (OI = 0).
  - It shall be set to 1 on S4/S11 interface if the SGW needs to forward the Delete Session Request message to PGW.
- Bit 3 ISRSI (Idle mode Signalling Reduction Supported Indication): If this is set to 1, it shall indicate that the old/source SGSN/MME and the associated SGW are capable to activate ISR.
- Bit 2 ISRAI (Idle mode Signalling Reduction Activation Indication): If this bit is set to 1, it shall indicate that the ISR is established between the MME and the S4 SGSN during a TAU/RAU without an SGW change

procedure or during an Inter RAT handover without an SGW change procedure. The SGW shall retain the resources for the other CN node that has its bearer resources on the SGW reserved. The old/source SGSN/MME shall maintain the UE's contexts and activate ISR.

- Bit 1 – SGWCI (SGW Change Indication): If this bit is set to 1, it shall indicate that the target MME/SGSN has selected a new SGW during a TAU/RAU or handover with an SGW change procedure.

The following bits within Octet 6 shall indicate:

- Bit 8 SQCI (Subscribed QoS Change Indication): If this bit is set to 1, it indicates that the subscribed QoS profile of the related PDN connection has changed in the old MME/SGSN when the UE is in ECM-IDLE state and ISR is activated. The new MME/SGSN shall trigger the Subscribed QoS Modification procedure. See 3GPP TS 23.401 [3], clause 5.3.9.2.
- Bit 7 UIMSI (Unauthenticated IMSI): If this bit is set to 1, it indicates that the IMSI present in the message is not authenticated and is for emergency attached UE.
- Bit 6 CFSI (Change F-TEID support indication): if this bit is set to 1, it indicates that the SGW can change the
  assigned GTP-U F-TEID in the current procedure. If the SGW needs to modify the GTP-U F-TEID and the CFSI
  flag is set to 1 in the corresponding request message, the SGW shall include the new F-TEID in the Modify
  Bearer Response/Modify Access Bearers Response message.
- Bit 5 CRSI (Change Reporting support indication): if this bit is set to 1, it indicates that the MME/S4 SGSN supports Location Change Reporting mechanism for the corresponding session.
- Bit 4 PS (Piggybacking Supported). This bit denotes whether the MME/SGW support piggybacking feature as described in Annex F of 3GPP TS 23.401 [3]. If set to 1, it indicates that the node is capable of processing two different GTP-C messages appearing back to back in a single UDP payload.
- Bit 3 PT (S5/S8 Protocol Type) If this bit set to 1, it shall indicate that the protocol type for the S5/S8 interface is PMIP; this bit is set to 0 to indicate that the protocol type for the S5/S8 interface is GTP.
- Bit 2 SI (Scope Indication): If this bit is set to 1, it indicates that all bearer resources of the UE shall be
  released by the SGW. This flag is set in messages during TAU/RAU/Handover with SGW change /SRNS
  Relocation Cancel Using S4 with SGW change/Inter RAT handover Cancel procedure with SGW change/S1
  Based handover Cancel procedure with SGW change.
- Bit 1 MSV (MS Validated): If this bit is set to 1, it shall indicate that the new MME/SGSN has successfully authenticated the UE.

The following bits within Octet 7shall indicate:

- Bit 8 – RetLoc (Retrieve Location Indication Flag): if this bit is set to 1, it indicates that the PGW requests the MME/SGSN or TWAN/ePDG to provide the User Location Information.

Bit 7 – PBIC (Propagate BBAI Information Change): if this bit is set to 1, it indicates a change in the H(e)NB local IP address and/or UDP port number, i.e. the UE moves from an (e)NB to a H(e)NB, or from one H(e)NB to another H(e)NB with the fixed network backhaul changed, or the UE moves from a H(e)NB to a (e)NB.

- Bit 6 SRNI (SGW Restoration Needed Indication): if this bit is set to 1, it indicates that the source MME/S4-SGSN has not performed the SGW relocation procedure after the source SGW has failed with or without restart, when the source and target MME/S4-SGSN support the MME/S4-SGSN triggered SGW restoration procedure as specified in 3GPP TS 23.007 [17].
- Bit 5 S6AF (Static IPv6 Address Flag): if this bit is set to 1, it indicates that PDP/PDN IPv6 address is static.
- Bit 4 S4AF (Static IPv4 Address Flag): if this bit is set to 1, it indicates that PDP/PDN IPv4 address is static.
- Bit 3 MBMDT (Management Based MDT allowed flag): if this bit is set to 1, it indicates that management based MDT is allowed.
- Bit 2 ISRAU (ISR is activated for the UE): if this bit is set to 1, it indicates that ISR is activated for the UE before the UE moving to the new SGSN/MME.
- Bit 1 CCRSI (CSG Change Reporting support indication): if this bit is set to 1, it indicates that the MME/S4 SGSN supports CSG Information Change Reporting mechanism for the corresponding session.

The following bits within Octet 8 shall indicate:

- Bit 8 CPRAI (Change of Presence Reporting Area information Indication): when ISR is active if this bit is set to 1, it indicates that the Presence Reporting Area information, which is provided as a part of the Presence Reporting Area Information IE, has changed since last reported by the MME/S4-SGSN. The SGW shall ignore this flag when ISR is not active.
- Bit 7 ARRL (Abnormal Release of Radio Link): if this bit is set to 1 by the MME, it indicates to the SGW that the access bearers are released due to an abnormal release of the radio link. Based on operator policy, this indication may be used by the SGW in subsequent decisions to trigger PDN charging pause if the PGW Pause of Charging feature has been enabled on that PDN connection.
- Bit 6 PPOFF (PDN Pause Off Indication): if this bit is set to 1 by the SGW, it indicates to the PGW that the charging for the PDN connection shall be unpaused.
- Bit 5 PPON (PDN Pause On Indication) / PPEI (PDN Pause Enabled Indication): if this bit is set to 1 by the SGW, it indicates to the PGW that the charging for the PDN connection shall be paused; if it is set to 1 by the PGW, it indicates that PGW enables the SGW to use the PGW Pause of Charging procedure for the PDN connection.
- Bit 4 PPSI (PDN Pause Support Indication): if this bit is set to 1 by the SGW, it indicates that the SGW supports the PGW Pause of Charging procedure; if it is set to 1 by the PGW, it indicates that the PGW supports the PGW Pause of Charging procedure.
- Bit 3 CSFBI (CSFB Indication): if this bit is set to 1, it indicates that the UE has been subject to CSFB.
- Bit 2 CLII (Change of Location Information Indication): when ISR is active if this bit is set to 1, it indicates that the location information, which is provided as a part of ULI IE, has changed since last reported by the MME/S4-SGSN. The SGW shall ignore this flag when ISR is not active.
- Bit 1 CPSR (CS to PS SRVCC indication): if this bit is set to 1, it indicates that a UTRAN/GERAN to E-UTRAN/UTRAN (HSPA) SRVCC procedure is underway and the associated message, i.e. Modify Bearer Request shall be forwarded to the PGW from the SGW as specified in 3GPP TS 23.216 [43].

The following bits within Octet 9 shall indicate:

- Bit 8 NSI (NBIFOM Support Indication): if this bit is set to 1, it indicates to the PGW that the NBIFOM is supported (see subclause 5.10 of 3GPP TS 23.161 [71]).
- Bit 7 UASI (UE Available for Signaling Indication): if this bit is set to 1, it indicates that the UE is available for end to end signalling and that the PGW should re-attempt the pending network initiated procedure.
- Bit 6 DTCI (Delay Tolerant Connection Indication): if this bit is set to 1, it indicates that the PDN connection
  is delay tolerant according to the local policies in the PGW, e.g. per APN.For this PDN connection the PGW
  supports receiving the rejection cause "UE is temporarily not reachable due to power saving" from the
  MME/SGSN via the SGW during a network initiated procedure and holding the network initiated procedure,
  until the PGW receives the subsequent Modify Bearer Request message with the UASI flag indicating that the
  UE is available for end to end signalling.
- Bit 5 BDWI (Buffered DL Data Waiting Indication): if this bit is set to 1, it indicates that there is DL data buffered in the (old) SGW, i.e. that the new MME/SGSN shall invoke data forwarding if there is an SGW change as specified in subclause 5.3.3.1A of 3GPP TS 23.401 [3], and that it shall setup the user plane in conjunction with the TAU/RAU procedure for delivery of the buffered DL data to the UE.
- Bit 4 PSCI (Pending Subscription Change Indication): If this bit is set to 1, it indicates that there is a pending report of the changed subscribed QoS profile of the related PDN connection in the old MME, so that the new MME/SGSN shall trigger the HSS Initiated Subscribed QoS Modification procedure towards the PGW. See subclause 5.3.9.2 of 3GPP TS 23.401 [3].
- Bit 3 PCRI (P-CSCF Restoration Indication): if this bit is set to 1, it indicates a request to trigger a P-CSCF restoration for the corresponding user (see 3GPP TS 23.380 [61]).
- Bit 2 AOSI (Associate OCI with SGW node's Identity): if this bit is set to 1, it indicates that the SGW provided "SGW's Overload Control Information" which shall be associated with the node identity (i.e. FQDN or the IP address received from the DNS during the SGW selection) of the serving SGW.

- Bit 1 – AOPI (Associate OCI with PGW node's Identity): if this bit is set to 1, it indicates that the PGW provided "PGW's Overload Control Information" which shall be associated with the node identity (i.e. FQDN or the IP address received from the HSS or DNS during the PGW selection) of the serving PGW.

The following bits within Octet 10 shall indicate:

- Bit 8 ROAAI (Release Over Any Access Indication): If this bit is set to 1, it indicates to the PGW that, if this is an NB-IFOM PDN connection, the PGW shall initiate the release of the corresponding PDN connection over the non-3GPP access over the S2a/S2b interface with the cause "Local release".
- Bit 7 EPCOSI (Extended PCO Support Indication): If this bit is set to 1, it indicates to the receiver that the Extended PCO is supported, e.g. when the PGW is the receiver, it indicates that the UE, the MME and the SGW support Extended PCO; when the target MME is the receiver, during an inter-MME mobility, it indicates that UE and the source MME support Extended PCO.
- Bit 6 CPOPCI (Control Plane Only PDN Connection Indication): If this bit is set to 1, it indicates that the PDN Connection is set to Control Plane Only, i.e. the user data pertaining to this PDN connection can only be transferred in NAS PDUs via the control plane.
- Bit 5 PMTSMI (Pending MT Short Message Indication): If this bit is set to 1, it indicates to the target MME/S4-SGSN that there is one (or more) pending MT Short Message(s) in the SMS-GMSC, i.e. that the target MME/S4-SGSN shall provide its E.164 address and Diameter Identity if available to receive the MT Short message and maintain the signalling connection with the UE for a longer time to enable the retransmission of the Short Message.
- Bit 4 S11-U Tunnel Flag (S11TF): This flag shall be set to 1 on the S11 interface if user data is transported in NAS signalling.
- Bit 3 PNSI (Pending Network Initiated PDN Connection Signalling Indication): if this bit is set to 1, it
  indicates to the target MME/SGSN that there is pending network initiated PDN connection signalling for the
  PDN connection, i.e. the target MME/SGSN shall set UASI flag in the Create Session Request or Modify Bearer
  Request message to indicate to the PGW that the UE is available for end to end signalling.
- Bit 2 UNACCSI (UE Not Authorised Cause Code Support Indication): If this bit is set to 1, it indicates that the Cause Code for "UE not authorized by OCS or external AAA Server" is supported by the S4-SGSN/MME.
- Bit 1 WLCP PDN Connection Modification Support Indication (WPMSI): if this bit is set to 1, it indicates that the TWAN supports the WLCP PDN Connection Modification procedure. This indication is used by the P-CSCF restoration extension procedure for TWAN access (see 3GPP TS 23.380 [61]).

The following bits within Octet 11 shall indicate:

- Bit 3 to 8 Spare, for future use and set to zero.
- Bit 2 ENBCRSI (eNB Change Reporting Support Indication): if this bit is set to 1, it indicates that the MME supports Macro eNodeB Change Reporting mechanism for the corresponding session.
- Bit 1–TSPCMI (Triggering SGSN initiated PDP Context Creation/Modification Indication): if this bit is set to 1, it indicates to the S4-SGSN that in the UE_initiated PDP Context Modification procedure, when the NBIFOM container is included, the S4-SGSN accepts the UE initiated PDP Context Modification procedure and initiates SGSN initiated PDP Context Creation/modification procedures respectively towards UE to transfer the NBIFOM container received from the PGW either in Create Bearer Request or Update Bearer Request message as specified in 3GPP TS 23.161 [71].

# 8.13 Protocol Configuration Options (PCO)

Protocol Configuration Options (PCO) is transferred via GTP tunnels. The sending entity copies the value part of the PCO into the Value field of the PCO IE. The detailed coding and maximum length of the PCO field from octets 5 to (n+4) shall be specified as per clause 10.5.6.3 of 3GPP TS 24.008 [5], starting with octet 3.

283




Figure 8.13-1: Protocol Configuration Options (PCO)

# 8.14 PDN Address Allocation (PAA)

The PDN Address Allocation is coded as depicted in Figure 8.14-1.



	Bits									
Octets	8	7	6	5	4	3	2	1		
1	Type = 79 (decimal)									
2 to 3	Length = n									
4		Sp	are			Inst	ance			
5	Spare PDN Type									
6 to (n+4)			PDN	Addre	ss and F	Prefix				

Figure 8.14-1: PDN Address Allocation (PAA)

PD	N ty	/pe val	ue (octet 5)
Bit	s		
3	2	1	
-	0	-	IPv4
	1		IPv6
-	1	-	IPv4v6
1	0	0	Non-IP
All	oth	er valu	es are reserved.
Bit	s 8-	4 of oc	tet 5 are spare and shall be coded as zero.
PD	N A	ddress	s and Prefix (octet 6 to n+4)
Pre	əfix	from o	alue indicates IPv4, an IPv4 address is present in the PDN Address and ctet 6 to octet 9. Bit 8 of octet 6 represents the most significant bit of the and bit 1 of octet 9 the least significant bit.
thro the	oug e mo	h 22 co ost sign	alue indicates IPv6, octet 6 contains the IPv6 Prefix Length. Octets 7 ontain an IPv6 Prefix and Interface Identifier. Bit 8 of octet 7 represents ificant bit of the IPv6 Prefix and Interface Identifier and bit 1 of octet 22 ificant bit.
thre the the rep	oug mo lea ores	h 22 co ost sign ist sign	alue indicates IPv4v6, octet 6 contains the IPv6 Prefix Length. Octets 7 ontain an IPv6 Prefix and Interface Identifier. Bit 8 of octet 7 represents ificant bit of the IPv6 Prefix and Interface Identifier and bit 1 of octet 22 ificant bit. Octets 23 through 26 contain an IPv4 address. Bit 8 of octet 23 e most significant bit of the IPv4 address and bit 1 of octet 26 the least
lf F	DN	l type v	alue indicates Non-IP, octets from 6 to 'n+4' shall not be present.

# 8.15 Bearer Quality of Service (Bearer QoS)

Bearer Quality of Service (Bearer QoS) is transferred via GTP tunnels. The sending entity copies the value part of the Bearer l QoS into the Value field of the Bearer QoS IE.

				В	its						
Octets	8	7	6	5	4	3	2	1			
1	Type = 80 (decimal)										
2-3		Length = n									
4		Sp	are			Inst	ance				
5	Spare	PCI		F	۲L		Spare	PVI			
6				Label	(QCI)						
7 to 11			Maxim	num bit	rate for	uplink					
12 to 16			Maximu	um bit ra	ate for c	lownlin	k				
17 to 21		Guaranteed bit rate for uplink									
22 to 26		Guaranteed bit rate for downlink									
27 to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	citly spec	ified			

Figure 8.15-1: Bearer Quality of Service (Bearer QoS)

Octet 5 represents the Allocation/Retention Priority (ARP) parameter. The meaning and value range of the parameters within the ARP are defined in 3GPP TS 29.212 [29]. The bits within the ARP octet are:

- Bit 1 PVI (Pre-emption Vulnerability): See 3GPP TS 29.212[29], clause 5.3.47 Pre-emption-Vulnerability AVP.
- Bit 2 spare
- Bits 3 to 6 PL (Priority Level): See 3GPP TS 29.212[29], clause 5.3.45 Priority-Level AVP. PL encodes each priority level defined for the Priority-Level AVP as the binary value of the priority level.
- Bit 7 PCI (Pre-emption Capability): See 3GPP TS 29.212[29], clause 5.3.46 Pre-emption-Capability AVP.
- Bit 8 spare.

Octet 6 contains the "QCI" value, as specified in 3GPP TS 23.203 [48].

The UL/DL MBR and GBR fields are encoded as kilobits per second (1 kbps = 1000 bps) in binary value. The UL/DL MBR and GBR fields may require converting values in bits per second to kilobits per second when the UL/DL MBR and GBR values are received from an interface other than GTPv2 interface. If such conversions result in fractions, then the value of UL/DL MBR and GBR fields shall be rounded upwards. For non-GBR bearers, both the UL/DL MBR and GBR should be set to zero. The range of QCI, Maximum bit rate for uplink, Maximum bit rate for downlink, Guaranteed bit rate for uplink and Guaranteed bit rate for downlink are specified in 3GPP TS 36.413 [10].

NOTE: The encoding in 3GPP TS 24.301 [23] and 3GPP TS 36.413 [10] is different from the encoding within this specification.

#### 8.16 Flow Quality of Service (Flow QoS)

Flow Quality of Service (Flow QoS) is transferred via GTP tunnels. The sending entity copies the value part of the Flow QoS into the Value field of the Flow QoS IE.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1			Ту	/pe = 81	decin	nal)						
2 to 3				Leng	th = n							
4		Sp	are			Inst	ance					
5				Label	(QCI)							
6 to 10			Maxin	num bit	rate for	uplink						
11 to 15			Maximu	um bit ra	ate for c	lownlinl	<b>(</b>					
16 to 20		Guaranteed bit rate for uplink										
21 to 25		Ģ	Guarant	eed bit	rate for	downlir	nk					
26 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified				

Figure 8.16-1: Flow Quality of Service (Flow QoS)

Octet 5 contains the "QCI" value, as specified in 3GPP TS 23.203 [48].

The UL/DL MBR and GBR fields are encoded as kilobits per second (1 kbps = 1000 bps) in binary value. For non-GBR bearers, both the UL/DL MBR and GBR should be set to zero. The range of QCI, Maximum bit rate for uplink,

#### 3GPP TS 29.274 version 14.7.0 Release 14

285

Maximum bit rate for downlink, Guaranteed bit rate for uplink and Guaranteed bit rate for downlink are specified in 3GPP TS 36.413 [10].

NOTE: The encoding in 3GPP TS 24.301 [23] and 3GPP TS 36.413 [10] is different from the encoding within this specification.

# 8.17 RAT Type

RAT Type is coded as depicted in Figure 8.17-1.

		Bits									
Octets	8	7	6	5	4	3	2	1			
1		Type = 82 (decimal)									
2 to 3				Leng	th = n						
4		Sp	are			Inst	ance				
5		RAT Type									
6 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified			

Figure 8.17-1: RAT Type

Table 8.17-1: R	AT Type values
TTypes	Values (Dec

RAT Types	Values (Decimal)
<reserved></reserved>	0
UTRAN	1
GERAN	2
WLAN	3
GAN	4
HSPA Evolution	5
EUTRAN (WB-E-UTRAN)	6
Virtual	7
EUTRAN-NB-IoT	8
<spare></spare>	9-255

- NOTE 1: For S4-SGSN, currently it is only possible to detect the difference between GERAN and UTRAN when GERAN Gb mode is used. If GERAN Iu mode is used, then an S4-SGSN may not be able to detect the difference between GERAN and UTRAN. Across the Gb interface, the SGSN may also not be able to detect the difference between GERAN and GAN. If S4-SGSN cannot detect that the HSPA Evolution 3GPP TR 25.999 [46] network is behind the Iu interface, the S4-SGSN will send the "UTRAN" RAT Type.
- NOTE 2: For the Iu interface case, if the SGSN detects UTRAN or HSPA, it sets the RAT-Type to "UTRAN". If the SGSN detects HSPA+, it sets the RAT-Type to "HSPA Evolution", otherwise the SGSN will send the "UTRAN" RAT Type.

# 8.18 Serving Network

Serving Network is coded as depicted in Figure 8.18-1.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1	Type = 83 (decimal)											
2 to 3	Length = n											
4		Sp	are		Instance							
5		MCC	digit 2		MCC digit 1							
6		MNC	digit 3		MCC digit 3							
7	MNC digit 2 MNC digit 1											
8 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified				

Figure 8.18-1: Serving Network

If an Administration decides to include only two digits in the MNC, then bits 5 to 8 of octet 6 are coded as "1111".

Unless specified otherwise in the specification, this IE contains the serving core network operator ID provided by the MME, S4-SGSN or ePDG, or the PLMN identity of the selected PLMN used for 3GPP-based access authentication provided by the TWAN.

NOTE: The serving core network operator ID is the PLMN ID of the MME, S4-SGSN or ePDG which is currently serving the UE. An S4-SGSN/MME which supports multiple PLMN IDs is considered as logically different S4-SGSNs/MMEs.

# 8.19 EPS Bearer Level Traffic Flow Template (Bearer TFT)

EPS Bearer Level Traffic Flow Template (Bearer TFT) is transferred via GTP tunnels. The sending entity copies the value part of the EPS Bearer Level TFT into the Value field of the EPS Bearer Level TFT IE. The detailed coding and maximum length of the EPS Bearer Level TFT IE is specified in 3GPP TS 24.008 [5], clause 10.5.6.12, beginning with octet 3.

		Bits									
Octets	8	7	6	5	4	3	2	1			
1	1 Type = 84 (decimal)										
2 to 3				Leng	th = n						
4		Spare Instance									
5 to (n+4)	E	EPS Bearer Level Traffic Flow Template (TFT)									

Figure 8.19-1: EPS Bearer Level Traffic Flow Template (Bearer TFT)

# 8.20 Traffic Aggregate Description (TAD)

The Traffic Aggregate Description IE is coded as depicted in Figure 8.20-1. The detailed coding and maximum length of Traffic Aggregate Description is specified in 3GPP TS 24.008 [5], clause 10.5.6.12, beginning with octet 3..

		Bits									
Octets	8	7	6	5	4	3	2	1			
1	Type = 85 (Decimal)										
2 to 3				Leng	:h = n						
4	Spare Instance										
5 to (n+4)		Traffic Aggregate Description									

Figure 8.20-1 Traffic Aggregate Description

# 8.21 User Location Information (ULI)

User Location Information (ULI) is a extendable IE that is coded as depicted in Figure 8.21-1. The CGI, SAI, RAI, TAI, ECGI and LAI identity types are defined in 3GPP TS 23.003 [2].

				Bi	ts			
Octets	8	7	6	5	4	3	2	1
1			Ту	pe = 86	(decim	ial)		
2 to 3				Lengt	th = n			
4		Spare Instance						
5	Exten	Macro	LAI	ECGI	TAI	RAI	SAI	CGI
	ded	eNode						
	Macro	B ID						
	eNode							
	B ID							
a to a+6				C	GI			
b to b+6				S	AI			
c to c+6				R	AI			
d to d+4				T/	41			
e to e+6				EC	GI			
f to f+4				L	41			
g to g+5			Ν	lacro el	lodeB I	D		
g to g+5	Extended Macro eNodeB ID							
h to (n+4)	Thes	e octet(	s) is/ar	e prese	nt only	if explic	itly spe	cified

Figure 8.21-1: User Location Information

The ULI IE shall contain only one identity of the same type (e.g. more than one CGI cannot be included), but ULI IE may contain more than one identity of a different type (e.g. ECGI and TAI). The flags LAI, ECGI, TAI, RAI, SAI, CGI, Macro eNodeB ID, and Extended Macro eNodeB ID in octet 5 indicate if the corresponding type shall be present in a respective field or not. If one of these flags is set to "0", the corresponding field shall not be present at all. If more than one identity of different type is present, then they shall be sorted in the following order: CGI, SAI, RAI, TAI, ECGI, LAI, Macro eNodeB ID, Extended Macro eNodeB ID. Only one of the Macro eNodeB ID or Extended Macro eNodeB ID shall be present in the ULI IE.

The following subclauses specify the coding of the fields representing different identities.

For each identity, if an Administration decides to include only two digits in the MNC, then "MNC digit 3" field of corresponding location shall be coded as "1111".

#### 8.21.1 CGI field

The coding of CGI (Cell Global Identifier) is depicted in Figure 8.21.1-1. Only zero or one CGI field shall be present in ULI IE.

		Bits										
Octets	8	7	6	5	4	3	2	1				
а		MCC	digit 2		MCC digit 1							
a+1		MNC	digit 3		MCC digit 3							
a+2		MNC	digit 2		MNC digit 1							
a+3 to a+4			Locati	on Area	a Code (LAC)							
a+5 to a+6			(	Cell Ide	ntity (C	1)						

Figure 8.21.1-1: CGI field

The Location Area Code (LAC) consists of 2 octets. Bit 8 of Octet a+3 is the most significant bit and bit 1 of Octet a+4 the least significant bit. The coding of the location area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The Cell Identity (CI) consists of 2 octets. Bit 8 of Octet a+5 is the most significant bit and bit 1 of Octet a+6 the least significant bit. The coding of the cell identity is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

#### 8.21.2 SAI field

The coding of SAI (Service Area Identifier) is depicted in Figure 8.21.2-1. Only zero or one SAI field shall be present in ULI IE.

				Bi	its			
Octets	8	7	6	5	4	3	2	1
b		MCC	digit 2			MCC	digit 1	
b+1		MNC	digit 3			MCC	digit 3	
b+2		MNC	digit 2			MNC	digit 1	
b+3 to b+4			Locati	ion Area	a Code	(LAC)		
b+5 to b+6			Servi	ce Area	Code	(SAC)		

Figure	8.21	.2-1:	SAI	field
--------	------	-------	-----	-------

The Location Area Code (LAC) consists of 2 octets. Bit 8 of Octet b+3 is the most significant bit and bit 1 of Octet b+4 the least significant bit. The coding of the location area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The Service Area Code (SAC) consists of 2 octets. Bit 8 of Octet b+5 is the most significant bit and bit 1 of Octet b+6 the least significant bit. The SAC is defined by the operator. See 3GPP TS 23.003 [2] section 12.5 for more information.

#### 8.21.3 RAI field

The coding of RAI (Routing Area Identity) is depicted in Figure 8.21.3-1. Only zero or one RAI field shall be present in ULI IE.

		Bits									
Octets	8	7	6	5	4	3	2	1			
С		MCC	digit 2			MCC	digit 1				
c+1		MNC	digit 3		MCC digit 3						
c+2		MNC	digit 2		MNC digit 1						
c+3 to c+4			Locati	on Area	a Code	(LAC)					
c+5 to c+6			Routir	ng Area	Code	(RAC)					

Figure 8.21.3-1: RAI field

The Location Area Code (LAC) consists of 2 octets. Bit 8 of Octet c+3 is the most significant bit and bit 1 of Octet c+4 the least significant bit. The coding of the location area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used (see 3GPP TS 23.003 [2]).

The Routing Area Code (RAC) consists of 2 octets. Only Octet c+5 contains the RAC. Octet c+6 is coded as all 1's (1111111). The RAC is defined by the operator. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used (see 3GPP TS 23.003 [2]).

#### 8.21.4 TAI field

The coding of TAI (Tracking Area Identity) is depicted in Figure 8.21.4-1. Only zero or one TAI field shall be present in ULI IE.

	Bits								
Octets	8	7	6	5	4	3	2	1	
d		MCC	digit 2		MCC digit 1				
d+1		MNC	digit 3		MCC digit 3				
d+2		MNC	digit 2		MNC digit 1				
d+3 to d+4			Track	ing Are	a Code	(TAC)			



The Tracking Area Code (TAC) consists of 2 octets. Bit 8 of Octet d+3 is the most significant bit and bit 1 of Octet d+4 the least significant bit. The coding of the tracking area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

#### 8.21.5 ECGI field

The coding of ECGI (E-UTRAN Cell Global Identifier) is depicted in Figure 8.21.5-1. Only zero or one ECGI field shall be present in ULI IE.

	Bits									
Octets	8	7	6	5	4	3	2	1		
е		MCC	digit 2			MCC	digit 1			
e+1		MNC	digit 3			MCC	digit 3			
e+2		MNC	digit 2			MNC	digit 1			
e+3		Sp	are		ECI					
e+4 to e+6			ECI (E-	UTRAN	V Cell Id	dentifier	)			


Figure 8.21.5-1: ECGI field

The E-UTRAN Cell Identifier (ECI) consists of 28 bits. The ECI field shall start with Bit 4 of octet e+3, which is the most significant bit. Bit 1 of Octet e+6 is the least significant bit. The coding of the E-UTRAN cell identifier is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

#### 8.21.6 LAI field

The coding of LAI (Location Area Identifier) is depicted in Figure 8.21.6-1.

	Bits									
Octets	8	7	6	5	4	3	2	1		
f		MCC	digit 2		MCC digit 1					
f+1		MNC	digit 3		MCC digit 3					
f+2		MNC	digit 2		MNC digit 1					
f+3 to f+4			Locati	ion Are	a Code	(LAC)				



The Location Area Code (LAC) consists of 2 octets. Bit 8 of Octet f+3 is the most significant bit and bit 1 of Octet f+4 the least significant bit. The coding of the location area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

#### 8.21.7 Macro eNodeB ID field

The coding of Macro eNodeB ID is depicted in Figure 8.21.7-1. Only zero or one Macro eNodeB ID or Extended Macro eNodeB ID field shall be present in ULI IE.

	Bits										
Octets	8	7	6	5	4	3	2	1			
g		MCC	digit 2			MCC	digit 1				
g+1		MNC	digit 3		MCC digit 3						
g+2		MNC	digit 2		MNC digit 1						
g+3		Sp	are		Macro eNodeB ID						
g+4 to g+5			Μ	acro el	NodeB	ID					

Figure 8.21.7-1: Macro eNodeB ID field

The Macro eNodeB ID consists of 20 bits. Bit 4 of Octet g+3 is the most significant bit and bit 1 of g+5 is the least significant bit. The coding of the Macro eNodeB ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

#### 8.21.8 Extended Macro eNodeB ID field

The coding of Extended Macro eNodeB ID is depicted in Figure 8.21.x-1. Only zero or one Extended Macro eNodeB ID or Macro eNodeB ID field shall be present in ULI IE.

	Bits									
Octets	8	7	6	5	4	3	2	1		
g		MCC	digit 2			MCC	digit 1			
g+1		MNC	digit 3		MCC digit 3					
g+2		MNC	digit 2		MNC digit 1					
g+3	SMeN	Sp	are	Ex	tended	Macro	eNodeB	B ID		
C C	В									
g+4 to g+5			Extend	ded Mad	ro eNo	deB ID				

Figure 8.21.8-1: Extended Macro eNodeB ID field

The Extended Macro eNodeB ID consists of 21 bits. The coding of the Extended Macro eNodeB ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

If the SMeNB flag is not set the Extended Macro eNodeB ID field contains a Long Macro eNodeB ID with a length of 21 Bits. Bit 5 of Octet g+3 is the most significant bit and bit 1 of g+5 is the least significant bit.

If the SMeNB flag is set the Extended Macro eNodeB ID field contains a Short Macro eNodeB ID with a length of 18 Bits. Bits 3 to 5 of Octet g+3 shall be set to 0 by the sender and shall be ignored by the receiver. Bit 2 of Octet g+3 is the most significant bit and bit 1 of Octet g+5 is the least significant bit.

NOTE: Homogenous support of the Extended Macro eNodeB ID IE is expected in a PLMN.

## 8.22 Fully Qualified TEID (F-TEID)

Fully Qualified Tunnel Endpoint Identifier (F-TEID) is coded as depicted in Figure 8.22-1.

		Bits										
Octets	8	7	6	5	4	3	2	1				
1		Type = 87 (decimal)										
2to 3				Leng	th = n							
4		Spare Instance										
5	V4	V6			Interfac	се Туре						
6 to 9			-	TEID / C	GRE Ke	у						
m to (m+3)				IPv4 a	ddress							
p to (p+15)				IPv6 a	ddress							
k to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified				

Figure 8.22-1: Fully Qualified Tunnel Endpoint Identifier (F-TEID)

The following flags are coded within Octet 5:

- Bit 8 V4: If this bit is set to "1", then IPv4 address field exists in the F-TEID, otherwise the IPv4 address field is not present at all.
- Bit 7 V6: If this bit is set to "1", then IPv6 address field exists in the F-TEID, otherwise the IPv6 address field is not present at all.

At least one of V4 and V6 shall be set to "1", and both may be set to "1".

- Bit 6 to Bit 1 Interface Type: This 6 bit wide integer can take the following values representing interface type and endpoint:
  - 0: S1-U eNodeB GTP-U interface
  - 1: S1-U SGW GTP-U interface
  - 2: S12 RNC GTP-U interface
  - 3: S12 SGW GTP-U interface

- 4: S5/S8 SGW GTP-U interface
- 5: S5/S8 PGW GTP-U interface
- 6: S5/S8 SGW GTP-C interface
- 7: S5/S8 PGW GTP-C interface
- 8: S5/S8 SGW PMIPv6 interface (the 32 bit GRE key is encoded in 32 bit TEID field)
- 9: S5/S8 PGW PMIPv6 interface (the 32 bit GRE key is encoded in the 32 bit TEID field, see subclause 6.3 in 3GPP TS 29.275 [26])
- 10: S11 MME GTP-C interface
- 11: S11/S4 SGW GTP-C interface
- 12: S10 MME GTP-C interface
- 13: S3 MME GTP-C interface
- 14: S3 SGSN GTP-C interface
- 15: S4 SGSN GTP-U interface
- 16: S4 SGW GTP-U interface
- 17: S4 SGSN GTP-C interface
- 18: S16 SGSN GTP-C interface
- 19: eNodeB GTP-U interface for DL data forwarding
- 20: eNodeB GTP-U interface for UL data forwarding
- 21: RNC GTP-U interface for data forwarding
- 22: SGSN GTP-U interface for data forwarding
- 23: SGW GTP-U interface for DL data forwarding
- 24: Sm MBMS GW GTP-C interface
- 25: Sn MBMS GW GTP-C interface
- 26: Sm MME GTP-C interface
- 27: Sn SGSN GTP-C interface
- 28: SGW GTP-U interface for UL data forwarding
- 29: Sn SGSN GTP-U interface
- 30: S2b ePDG GTP-C interface
- 31: S2b-U ePDG GTP-U interface
- 32: S2b PGW GTP-C interface
- 33: S2b-U PGW GTP-U interface
- 34: S2a TWAN GTP-U interface
- 35: S2a TWAN GTP-C interface
- 36: S2a PGW GTP-C interface
- 37: S2a PGW GTP-U interface

38: S11 MME GTP-U interface

39: S11 SGW GTP-U interface

Other values of "Interface Type" are spare and reserved for future use.

"Interface type" values with bit "6" set to 1 shall only be used between Rel-10 onwards GTPv2-C nodes.

NOTE 1: "Interface type" IE is defined with 5 bits only in the earlier releases of this specification, thus pre-Rel-10 GTPv2-C nodes can ignore bit "6" which is marked as "Spare" in earlier releases, allowing backward compatibility.

NOTE 2: Interface Type 8 is not used in this Release and in earlier Releases.

Octet 6 to 9 (TEID/GRE field) represent either a TEID or a GRE key. If both IPv4 and IPv6 addresses are present in F-TEID IE, then the TEID value shall be shared by both addresses.

Octets "m to (m+3)" and/or "p to (p+15)" (IPv4 address / IPv6 address fields), if present, contain respective address values.

## 8.23 TMSI

The TMSI, unambiguously associated with a given UE and Location area, is given by:

	Bits									
Octets	8	7	6	5	4	3	2	1		
1			Ту	/pe = 88	3 (decin	nal)				
2 to 3				Leng	th = n					
4		Sp	are			Inst	ance			
5 to (n+4)				TN	/ISI					
. ,		The TM	/ISI is d	efined i	n 3GPF	TS 23.	003 [2]			

Figure 8.23-1: TMSI

## 8.24 Global CN-Id

The Global CN-Id is coded as depicted in Figure 8.24-1.

				В	its							
Octets	8	7	6	5	4	3	2	1				
1		Type = 89 (decimal)										
2 to 3				Leng	th = n							
4		Sp	are			Inst	ance					
5		MCC	digit 2			MCC	digit 1					
6		MNC	digit 3			MCC	digit 3					
7		MNC	digit 2			MNC	digit 1					
8 to (n+4)				C	l-Id							
		The CN	I-Id is d	efined i	n 3GPF	P TS 23	.003 [2]					

Figure 8.24-1: Global CN-Id

If an Administration decides to include only two digits in the MNC, then bits 5 to 8 of octet 6 are coded as "1111".

# 8.25 S103 PDN Data Forwarding Info (S103PDF)

The HSGW Address and GRE Key identify a GRE Tunnel towards a HSGW over S103 interface for a specific PDN connection of the UE. The EPS Bearer IDs specify the EPS Bearers which require data forwarding that belonging to this PDN connection. The number of EPS bearer Ids included is specified by the value of EPS Bearer ID Number.

The spare bits indicate unused bits, which shall be set to 0 by the sending side and which shall not be evaluated by the receiving side.




Figure 8.25-1: S103 PDN Data Forwarding Info

# 8.26 S1-U Data Forwarding (S1UDF)

The Serving GW Address and Serving GW S1-U TEID consists of the S1-U Tunnel information allocated by the Serving GW for an EPS Bearer identified by the EPS Bearer ID which requires data forwarding during active handover from E-UTRAN Access to cdma2000 HRPD Access.

The spare bits indicate unused bits, which shall be set to 0 by the sending side and which shall not be evaluated by the receiving side.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1		Type = 91 (decimal)										
2 to 3				Leng	th = n							
4		Spare Instance										
5		Sp	are			EPS B	earer ID	)				
6		S	erving	GW Ad	dress Le	ength =	m					
7 to (m+6)			Servin	ig GW A	Address	[416]						
(m+7) to			Serv	ving GV	/ S1-U [·]	TEID						
(m+10)												

Figure 8.26-1: S1-U Data Forwarding Info

### 8.27 Delay Value

Delay Value is coded as depicted in Figure 8.27-1.

		Bits											
Octets	8	7	6	5	4	3	2	1					
1		Type = 92 (decimal)											
2 to 3				Leng	th = n								
4		Sp	are			Inst	ance						
5	Delay	Delay Value in integer multiples of 50 millisecs, or zero											
6 to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified					

Figure 8.27-1: Delay Value

Delay Value is set to zero in order to clear a previously set delay condition.

# 8.28 Bearer Context

Bearer Context is a grouped IE containing a number of other IEs. Which of those IEs are mandatory, optional or conditional and the conditions that apply are GTP message specific, and described in the corresponding subclause under clause 7.

Bearer Context may be repeated within a message with exactly the same Type and Instance values to represent a list of Bearer Contexts.

Bearer Context is coded as depicted in Table 8.28-1.

Table 8.28-1: Bearer Context Grouped Type

Octet 1		Bearer Context IE Type = 93 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	IE Type	Ins.
		a 5-column format in order to match the format used in subclate IE is further detailed for each specific GTP message includi		7, where

## 8.29 Charging ID

The Charging ID is coded as depicted in Figure 8.29-1. It is defined in 3GPP TS 32.251[8].

				В	its						
Octets	8	7	6	5	4	3	2	1			
1			Ту	/pe = 94	l (decin	nal)					
2 to 3				Leng	th = n						
4		Sp	are			Inst	ance				
5-8		Charging ID value									
9-(n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified			

Figure 8.29-1: Charging ID

# 8.30 Charging Characteristics

The charging characteristics information element is defined in 3GPP TS 32.251 [8] and is a way of informing both the SGW and PGW of the rules for producing charging information or informing the PGW to inhibit the establishment of the Gx session based on operator configured triggers. For the encoding of this information element see 3GPP TS 32.298 [9].




Figure 8.30-1: Charging Characteristics

## 8.31 Trace Information

Trace Information is coded as depicted in Figure 8.31-1. See 3GPP TS 32.422 [18] for details on trace related information.

				В	its								
Octets	8	7	6	5	4	3	2	1					
1		Type = 96(decimal)											
2 to 3				Leng	th = n								
4		Sp	are			Inst	ance						
5		MCC	digit 2			MCC	digit 1						
6		MNC	digit 3		MCC digit 3								
7		MNC	digit 2			MNC	digit 1						
8 to10				Trac	e ID								
11 to 19			Т	riggerir	ig Even	ts							
20 to 21		List of NE Types											
22		Session Trace Depth											
23 to 34		List of Interfaces											
35 to (n+4)		IP A	Address	s of Trac	ce Colle	ction E	ntity						

Figure 8.31-1: Trace Information

Octets 5 to 10 represent the Trace Reference parameter as defined in 3GPP TS 32.422 [18], clause 5.6.

Triggering Events, List of NE Types, Session Trace Depth are specified in 3GPP TS 32.422 [18].

List of Interfaces shall be encoded as the first 12 octets in the subclause 5.5 of 3GPP TS 32.422 [18].

See 3GPP TS 24.008 [5], clause 10.5.1.4, Mobile Identity, for the coding of MCC and MNC, whose values are obtained from the serving PLMN that the EM/NM is managing. If MNC is 2 digits long, bits 5 to 8 of octet 6 are coded as "1111".

### 8.32 Bearer Flags

Bearer Flags is coded as depicted in Figure 8.32-1.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1		Type = 97 (decimal)										
2 to 3		Length = n										
4		Sp	are			Insta	ance					
5		Spa	are		ASI	Vind	VB	PPC				
6-(n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified				

Figure 8.32-1: Bearer Flags

The following bits within Octet 5 indicate:

- Bit 1 PPC (Prohibit Payload Compression): This flag is used to determine whether an SGSN should attempt to compress the payload of user data when the users asks for it to be compressed (PPC = 0), or not (PPC = 1).
- Bit 2 VB (Voice Bearer): This flag is used to indicate a voice bearer when doing PS-to-CS (v)SRVCC handover.
- Bit 3 Vind (vSRVCC indicator): This flag is used to indicate that this bearer is an IMS video bearer and is candidate for PS-to-CS vSRVCC handover.
- Bit 4 ASI (Activity Status Indicator): When set to 1, this flag indicates that the bearer context is preserved in the CN without corresponding Radio Access Bearer established. The target S4-SGSN shall keep the bearer context associated with this indicator preserved. When the target S4-SGSN sends Relocation Request message towards the target RNC, the target S4-SGSN may not request to setup the RABs for those bearer contexts associated with this indicator.

#### 8.33 Void

# 8.34 PDN Type

The PDN Type is coded as depicted in Figure 8.34-1.

				В	ts							
Octets	8	7	6	5	4	3	2	1				
1		Type = 99 (decimal)										
2 to 3				Leng	th = n							
4		Sp	are			Inst	ance					
5		Spare PDN Type										
6 to n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified				

Figure 8.34-1: PDN Type

Table	8.34-1:	PDN	Type

F	PD	N t	ype val	ue (octet 5)
E	Bits	5		
3	3	2	1	
(	)	0	1	IPv4
0	)	1	0	IPv6
0	)	1	1	IPv4v6
1	1	0	0	Non-IP
A	٩I	oth	er valu	es are reserved.
E	Bits	s 8-	4 of oc	tet 5 are spare and shall be coded as zero.

# 8.35 Procedure Transaction ID (PTI)

Procedure Transaction Id is coded as depicted in Figure 8.35-1. It is defined in 3GPP TS 24.301 [23], clause 9.4 and is coded as specified in 3GPP TS 24.007 [30], clause 11.2.3.1a Procedure transaction identity.

		Bits										
Octets	8	7	6	5	4	3	2	1				
1		Type = 100 (decimal)										
2 to 3				Leng	th = n							
4		Sp	are			Insta	ance					
5		Procedure Transaction ID										
6 to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified				

Figure 8.35-1: Procedure Transaction ID

- 8.36 Void
- 8.37 Void

#### 8.38 MM Context

The MM Context information element contains the Mobility Management, UE security parameters that are necessary to transfer over S3/S16/S10 interface.

All Spare bits are set to zeros by the sender and ignored by the receiver. Spare bits in MM Context IE shall be set to 1's before sending MM Context IE to Gn/Gp SGSN.

#### 3GPP TS 29.274 version 14.7.0 Release 14

NOTE 1: The encoding of Spare bits in MM Context IE is different between GTPv1 and GTPv2. Spare bits in GTPv1 in MM Context IE there are set to 1s.

Security Mode indicates the type of security keys (GSM/UMTS/EPS) and Authentication Vectors (quadruplets /quintuplets/triplets) that are passed to the new MME/SGSN.

The DRX parameter coding is specified in clause 10.5.5.6 of 3GPP TS 24.008 [5]. If DRXI (DRX Indicator), bit 4 of octet 5, is set to "1", then the DRX parameter field is present, otherwise its octets are not present.

Uplink/downlink Subscribed UE AMBR (Aggregate Maximum Bit Rate) is coded as Unsigned32 integer values in kbps (1000 bps) for all non-GBR bearers according to the subscription of the user. The uplink/downlink Subscribed UE AMBR requires converting values in bits per second to kilobits per second when it is received from the HSS. If such conversions result in fractions, then the uplink/downlink Subscribed UE AMBR values shall be rounded upwards. If SAMBRI (Subscribed UE AMBR Indicator), bit 1 of octet 6, is set to "1", then the Uplink/downlink Subscribed UE AMBR parameter field is present, otherwise these parameters are not present. If no Subscribed UE AMBR is received from the HSS, the SAMBRI shall be set to "0".Uplink/downlink Used UE AMBR (Aggregate Maximum Bit Rate) is coded as Unsigned32 integer values in kbps (1000 bps) for all non-GBR bearers currently being used by the UE. If UAMBRI (Used UE AMBR Indicator), bit 2 of octet 6, is set to "1", then the Uplink/downlink Used UE AMBR parameter field is present, otherwise these parameters are not present.

The encoding of Mobile Equipment Identity (MEI) field shall be same as specified in clause 8.10 of this specification. If Length of Mobile Equipment Identity is zero, then the Mobile Equipment Identity parameter shall not be present. If the UE is emergency attached and the UE is UICCless or the IMSI is unauthenticated, Mobile Equipment Identity (MEI) shall be used as the UE identity.

The UE Network Capability coding is specified in clause 9.9.3.34 of 3GPP TS 24.301 [23]. If Length of UE Network Capability is zero, then the UE Network Capability parameter shall not be present.

The MS Network Capability coding is specified in clause 10.5.5.12 of 3GPP TS 24.008 [5]. If Length of MS Network Capability is zero, then the MS Network Capability parameter shall not be present.

The Voice Domain Preference and UE's Usage Setting coding is specified in clause 10.5.5.28 of 3GPP TS 24.008 [5]. If Length of Voice Domain Preference and UE's Usage Setting is zero, then the Voice Domain Preference and UE's Usage Setting parameter shall not be present.

Used Cipher indicates the GSM ciphering algorithm that is in use.

Used NAS Cipher indicates the EPS ciphering algorithm that is in use.

The Access restriction data is composed of UNA(UTRAN Not Allowed), GENA(GERAN Not Allowed), GANA(GAN Not Allowed), INA(I-HSPA-Evolution Not Allowed), ENA(WB-E-UTRAN Not Allowed), NBNA( NB-IoT Not Allowed), ECNA (Enhanced Coverage Not Allowed) and HNNA(HO-To-Non-3GPP-Access Not Allowed).

If the SGSN support the Higher bitrates than 16 Mbps flag, the Higher bitrates than 16 Mbps flag shall be included in the MM Context if:

- the source S4-SGSN has received "Higher bitrates than 16 Mbps flag" in the RANAP Initial UE Message or in RANAP Relocation Complete as defined in TS 25.413 [33] from the RNC, or
- the source S4-SGSN has stored the "Higher bitrates than 16 Mbps flag" (received from an SGSN via the Identification Response, Context Response or Forward Relocation Request during earlier procedures).

The S4-SGSN shall set the "Higher bitrates than 16 Mbps flag" to "1" if "Higher bitrates than 16 Mbps flag" is "allowed" and to "0" if it is "not allowed". The Length of Higher bitrates than 16 Mbps flag shall be set to zero if the S4-SGSN has not received the "Higher bitrates than 16 Mbps flag".

As depicted in Figure 8.38-1, the GSM Key, Used Cipher and Authentication Triplets that are unused in the old SGSN shall be transmitted to the new SGSN for the GSM subscribers. An array of at most 5 Authentication Triplets may be included. The field 'Number of Triplet' shall be set to the value '0' if no Authentication Triplet is included (i.e. octets '16 to h' are absent).

The Authentication Triplet coding is specified in Figure 8.38-7.

				Bi	ts									
Octets	8	7	6	5	4	3	2	1						
1	Type = 103 (decimal)													
2 to 3		Length = n												
4		Spare Instance												
5		curity M		Spare			CKSN							
6	Num	ber of T	riplet		Spare		<u> </u>	SAMB						
_							RI	RI						
7			Spare			U	Ised Cip	her						
8 to 15				K										
16 to h				nticatio										
(h+1) to				DRX pa	ramete	r								
(h+2)							_							
j to (j+3)				Subscri										
(j+4) to (j+7)				k Subsc			BR							
i to (i+3)				nk Useo										
(i+4) to (i+7)				nlink Use										
q		L	<u> </u>	f UE Ne			lity							
(q+1) to k				Networ										
k+1		L		f MS Ne			ility							
(k+2) to m				Networ										
m+1				bile Equ										
(m+2) to r				quipme										
r+1	ECNA	NBNA	HNNA	ENA	INA	GAN/	GENA	UNA						
r+2	Length of Voice Domain Preference and UE's Usage													
		-		Set	ting			-						
(r+3) to s	Voi	ice Don	nain Pre	eference	e and U	E's Us	age Set	ting						
(s+1) to	Thes	e octet	(s) is/ar	e prese	nt only	if expli	citly spe	cified						
(n+4)				-		•								

Figure 8.38-1: GSM Key and Triplets

As depicted in Figure 8.38-2, the UMTS Key, Used Cipher and Authentication Quintuplets that are unused in the old SGSN shall be transmitted to the new SGSN when the UMTS subscriber is attached to a GSM BSS in the old system, in case the user has a ME capable of UMTS AKA. An array of at most 5 Authentication Quintuplets may be included. The field 'Number of Quintuplets' shall be set to the value '0' if no Authentication Quintuplet is included (i.e. octets '40 to h' are absent).

If the UGIPAI (Used GPRS integrity protection algorithm Indicator), bit 3 of octet 6, is set to 1, then bits 4 to 6 of octet 7 shall contain the Used GPRS integrity protection algorithm field, otherwise these bits shall be set to 0 and ignored by the receiver.

The GUPII (GPRS User Plane Integrity Indicator), bit 4 of octet 6, shall be set to 1 if the subscriber profile indicated that user plane integrity protection is required and set to 0 otherwise.

NOTE 2: The encoding of the bits is not identical with GTPv1 as the spare bits are encoded differently.

The source S4-SGSN shall include the IOV_updates counter if it is supported and available. The IOV_updates counter is encoded as an integer with a length of 1 octet. The use of the IOV_updates counter is specified in 3GPP TS 43.020 [78]. If IOVI (IOV_updates Indicator), bit 5 of octet 6, is set to "1", then the IOV_updates counter parameter field shall be present, otherwise it shall not be present.

The Authentication Quintuplet coding is specified in Figure 8.38-8.

				Bi	ts							
Octets	8	7	6	5	4	3	2	1				
1			Тур	be = 104	4 (decin	nal)						
2 to 3	Length = n											
4			are				ance					
5		curity N		Spare			KSN/KS					
6		lumber	÷.	IOVI	GUPII		UAMB	-				
		uintuple				AI	RI	RI				
7	Sp	are		GPRS in		Us	ed Ciph	ner				
			protec	tion alg								
8 to 23					K							
24 to 39					K							
40 to h			Authent				5]					
(h+1) to			I	DRX pa	rametei	r						
(h+2)												
j to (j+3)			_		bed UE							
(j+4) to (j+7)			Downlinł				R					
i to (i+3)					I UE AN							
(j+12) to			Down	link Us	ed UE A	MBR						
(i+4)												
q		L	ength o				ty					
(q+1) to k					k Capat							
k+1		L	ength o				ty					
(k+2) to m					k Capat							
m+1			h of Mol									
(m+2) to r			Nobile E									
r+1			HNNA				GENA					
r+2	Len	gth of ∖	/oice Do			ce and	UE's Us	sage				
				Set								
(r+3) to s	Vo		nain Pre					ing				
s+1	Length of Higher bitrates than 16 Mbps flag											
s+2	Higher bitrates than 16 Mbps flag											
s+3					es cour							
(s+4) to	Thes	e octet	(s) is/ar	e prese	nt only i	f explic	itly spec	cified				
(n+4)												

Figure 8.38-2: UMTS Key, Used Cipher and Quintuplets

As depicted in Figure 8.38-3, the GSM Key, Used Cipher and Authentication Quintuplets that are unused in the old SGSN shall be transmitted to the new SGSN when the UMTS subscriber is attached to a GSM BSS in the old system, in case the user has a ME no capable of UMTS AKA. An array of at most 5 Authentication Quintuplets may be included. The field 'Number of Quintuplets' shall be set to the value '0' if no Authentication Quintuplet is included (i.e. octets '16 to h' are absent).

The Authentication Quintuplet coding is specified in Figure 8.38-8.

				Bi	ts								
Octets	8	7	6	5	4	3	2	1					
1			Ту	be = 10	5 (decin	nal)							
2 to 3		Length = n											
4		Spare Instance											
5		curity M		Spare		C	KSN/K	ī					
6		umber			Spare		-	SAMB					
_	Q	uintuple					RI	RI					
7			Spare			Us	sed Cip	her					
8 to 15							-1						
16 to h		A		cation C		-	5]						
(h+1) to (h+2)				DRX pa	rametei	ſ							
j to (j+3)			Uplink	Subscri	bed UE	AMBR							
(j+4) to (j+7)		D		k Subsc									
i to (i+3)			Upli	nk Used	JUE AN	/IBR							
(i+4) to (i+7)			Dowr	link Use	ed UE A	MBR							
q		L	ength o	f UE Ne	etwork C	Capabili	ty						
(q+1) to k			UE	Networl	k Capat	oility							
k+1		L	ength o	f MS Ne	etwork C	Capabil	ity						
(k+2) to m				Networ									
m+1		Length	n of Mo	bile Equ	ipment	Identity	/ (MEI)						
(m+2) to r				quipme	nt Ident	ity (ME	1)						
r+1	ECNA	NBNA	HNNA	ENA	INA	GANA	GENA	UNA					
r+2	Leng	gth of V	oice Do	omain P		ce and	UE's U	sage					
				Set									
(r+3) to s	Voi	Voice Domain Preference and UE's Usage Setting											
s+1		Length of Higher bitrates than 16 Mbps flag											
s+2		Higher bitrates than 16 Mbps flag											
(s+3) to	Thes	e octet	(s) is/ar	e prese	nt only i	f explic	itly spe	cified					
(n+4)													

Figure 8.38-3: GSM Key, Used Cipher and Quintuplets

As depicted in Figure 8.38-4, the UMTS Key, KSI and unused Authentication Quintuplets in the old SGSN may be transmitted to the new SGSN/MME when the UMTS subscriber is attached to UTRAN/GERAN in the old system, but it is not allowed to send quintuplets to an MME in a different serving network domain (see 3GPP TS 33.401 [12] clause 6.1.6). The MME may forward the UMTS Key, KSI and unused Authentication Quintuplets which were previously stored back to the same SGSN, for further details, refer to 3GPP TS 33.401 [12]. An array of at most 5 Authentication Quintuplets may be included. The field 'Number of Quintuplets' shall be set to the value '0' if no Authentication Quintuplet is included (i.e. octets '40 to h' are absent).

If the UGIPAI (Used GPRS integrity protection algorithm Indicator), bit 3 of octet 6, is set to 1, then bits 1 to 3 of octet 7 shall contain the Used GPRS integrity protection algorithm field, otherwise these bits shall be set to 0 and ignored by the receiver.

The GUPII (GPRS User Plane Integrity Indicator), bit 4 of octet 6, shall be set to 1 if the subscriber profile indicated that user plane integrity protection is required and set to 0 otherwise.

NOTE 3: The encoding of the bits is not identical with GTPv1 as the spare bits are encoded differently.

The source S4-SGSN shall include the IOV_updates counter if it is supported and available. The IOV_updates counter is encoded as an integer with a length of 1 octet. The use of the IOV_updates counter is specified in 3GPP TS 43.020 [78]. If IOVI (IOV_updates Indicator), bit 5 of octet 6, is set to "1", then the IOV_updates counter parameter field shall be present, otherwise it shall not be present.

The Authentication Quintuplet coding is specified in Figure 8.38-8.

				В	its					
Octets	8	7	6	5	4	3	2	1		
1		Type = 106 (decimal)								
2 to 3				Leng	th = n					
4		Spa		T		Inst	ance			
5		urity Mo		Spare			KSI			
6		umber o		IOVI	GUPII	UGIP	-	SAMB		
_	Qu	uintuple				AI	RI	RI		
7			Spare				GPRS i			
0.4- 00						protec	tion alg	orithm		
8 to 23					K K					
24 to 39 40 to h		۸	uthort				:1			
		Α			Quintup		2			
(h+1) to (h+2)		DRX parameter								
j to (j+3)	Uplink Subscribed UE AMBR									
(j+4) to (j+7)		Downlink Subscribed UE AMBR								
i to (i+3)	Uplink Used UE AMBR									
(i+4) to (i+7)	Downlink Used UE AMBR									
q	Length of UE Network Capability									
(q+1) to k	UE Network Capability									
k+1	Length of MS Network Capability									
(k+2) to m	MS Network Capability									
m+1	Length of Mobile Equipment Identity (MEI)									
(m+2) to r	Mobile Equipment Identity (MEI)									
r+1	ECNA NBNA HNNA ENA INA GANA GENA UNA									
r+2	Length of Voice Domain Preference and UE's Usage									
	Setting									
(r+3) to s	Voice Domain Preference and UE's Usage Setting									
s+1	Length of Higher bitrates than 16 Mbps flag									
s+2		Higher bitrates than 16 Mbps flag								
s+3					es cour					
(s+4) to	These	e octet(	s) is/ar	e prese	nt only i	f explic	itly spe	cified		
(n+4)										

Figure 8.38-4: UMTS Key a	and Quintuplets
---------------------------	-----------------

As depicted in Figure 8.38-5, the current EPS Security Context, a non-current EPS Security Context (if available), and unused Authentication Quadruplets in the old MME may be transmitted to the new MME. If the new MME is not in the same serving network domain then only the current EPS Security Context may be transmitted. An array of at most 5 Authentication Quadruplets may be included. The field 'Number of Quadruplets' shall be set to the value '0' if no Authentication Quadruplet is included (i.e. octets '46 to g' are absent). Authentication Quintuplets shall not be transmitted to the new MME (i.e. octets 'g+1 to h' shall be absent) even if the old MME has the Authentication Quintuplets for this UE. The field 'Number of Quintuplets' shall be set to the value '0'. The reasons for not sending Quintuplets are specified in3GPP TS 33.401 [12] clause 6.1.6.

The Authentication Quintuplet and Authentication Quadruplet codings are specified in Figure 8.38-8 and Figure 8.38-9 respectively.

The value of the NAS Downlink Count shall be set to the value that shall be used to send the next NAS message.

The value of the NAS Uplink Count shall be set to the largest NAS Uplink Count that was in a successfully integrity verified NAS message.

In Figure 8.38-5, the fields for the Old EPS Security Context (i.e. octets from s to s+64) may be present only in S10 Forward Relocation Request message according to the Rules on Concurrent Running of Security Procedures, which are specified in 3GPP TS 33.401 [12]. The octets for Old EPS Security Context shall be present if the OSCI (Old Security Context Indicator), bit 1 of octet 6) is set to "1"; otherwise they shall not be present.

If NHI_old (Next Hop Indicator for old EPS Security Context), bit 1 of octet s, is set to "1", then the parameters old NH (Next Hop) and old NCC (Next Hop Chaining Count) shall be present; otherwise the octets for old NH parameter shall not be present and the value of old NCC parameter shall be ignored by the receiver.




Figure 8.38-5: EPS Security Context and Quadruplets

If NHI (Next Hop Indicator), bit 5 of octet 5, is set to "1", then the optional parameters NH (Next Hop) and NCC (Next Hop Chaining Count) are both present, otherwise their octets are not present.

The UE Radio Capability for Paging information is specified in the subclause 9.2.1.98 of 3GPP TS 36.413 [10]. If Length of UE Radio Capability for Paging information is zero, then the UE Radio Capability for Paging information shall not be present. The old MME shall, when available, include UE Radio Capability for Paging information to the new MME as specified in the subclause 5.11.4 of 3GPP TS 23.401 [4].

As depicted in Figure 8.38-6, the old MME will derive CK' and IK' from  $K_{ASME}$  and transmit the CK' and IK' to the new SGSN. Authentication Quintuplets, if available, shall be transmitted to the SGSN if, and only if the MME received them from this SGSN earlier, according to 3GPP TS 33.401 [12] clause 6.1.5. An array of at most 5 Authentication Quintuplets may be included. The field 'Number of Quintuplets' shall be set to the value '0' if no Authentication Quadruplets may be included (i.e. octets 'g+1 to h' are absent). An array of at most 5 Authentication Quadruplets may be included. The field 'Number of Quadruplets' shall be set to the value '0' if no Authentication Quadruplets may be included. The field 'Number of Quadruplets' shall be set to the value '0' if no Authentication Quadruplets is included (i.e. octets 'g+1 to h' are absent). An array of at most 5 Authentication Quadruplets may be included. The field 'Number of Quadruplets' shall be set to the value '0' if no Authentication Quadruplets is included (i.e. octets '40 to g' are absent). A key K_{ASME} shall never be transmitted to an SGSN according to 3GPP TS 33.401 [12] clause 6.4.

The Authentication Quintuplet and Authentication Quadruplet codings are specified in Figure 8.38-8 and Figure 8.38-9 respectively.

#### 3GPP TS 29.274 version 14.7.0 Release 14

The old SGSN/MME may deliver both Authentication Quadruplets and Authentication Quintuplets it holds to the peer combo node to optimize the procedure.

NOTE: 3GPP TS 33.401 [12] states that "EPS authentication data shall not be forwarded from an MME towards an SGSN". The statement above assumes that the old MME can determine by local configuration that the peer node is a combo SGSN/MME (as opposed to a single SGSN).

	Bits							
Octets	8	7	6	5	4	3	2	1
1			Ту	be = 108	3 (decim	nal)		
2 to 3				Leng	th = n			
4			are			Inst	tance	
5	-	curity M		Spare			KSIASM	
6		umber			umber o		-	SAMB
	Q	uintuple	ets		uadrupl	et	RI	RI
7					are			
8 to 23				-	K			
24 to 39					<u>&lt;</u>			
40 to g				ication (				
(g+1) to h				ication (		-	5]	
(h+1) to		DRX parameter						
(h+2)								
j to (j+3)		Uplink Subscribed UE AMBR						
(j+4) to (j+7)	Downlink Subscribed UE AMBR							
i to (i+3)	Uplink Used UE AMBR							
(i+4) to (i+7)	Downlink Used UE AMBR							
q (m. 4) ta h	Length of UE Network Capability							
(q+1) to k	UE Network Capability							
k+1	Length of MS Network Capability							
(k+2) to m m+1	MS Network Capability							
	Length of Mobile Equipment Identity (MEI)							
(m+2) to r r+1								
r+2	ECNA NBNA HNNA ENA INA GANA GENA UNA							
r+2	Leng	Length of Voice Domain Preference and UE's Usage Setting						
(r+3) to s	Vai	co Don	agin Pr			='e Lle	age Set	tina
(s+1) to s							citly spe	-
(s+1) to (n+4)	mes	e ociel	(5) 15/81	e piese		i expli	citiy spe	cilleu
(1174)								

Figure 8.38-6: UMTS Key, Quadruplets and Quintuplets

				В	its			
Octets	8	7	6	5	4	3	2	1
1 to 16	RAND							
17 to 20	SRES							
21 to 28		Kc						

Figure	8.38-7:	Authentication	Triplet
--------	---------	----------------	---------

		Bits						
Octets	8	7	6	5	4	3	2	1
1 to 16				RA	ND			
17		XRES Length						
18 to m		XRES						
(m+1) to		СК						
(m+16)								
(m+17) to	IK							
(m+32)								
m+33	AUTN Length							
(m+34) to n				AL	ITN			

Figure 8.38-8: Authentication Quintuplet

	Bits							
Octets	8	7	6	5	4	3	2	1
1 to 16	RAND							
17	XRES Length							
18 to k	XRES							
k+1	AUTN Length							
(k+2) to m	AUTN							
(m+1) to	Kasme							
(m+32)								

#### Table 8.38-1: Security Mode Values

Security Type	Value (Decimal)
GSM Key and Triplets	0
UMTS Key, Used Cipher and Quintuplets	1
GSM Key, Used Cipher and Quintuplets	2
UMTS Key and Quintuplets	3
EPS Security Context and Quadruplets	4
UMTS Key, Quadruplets and Quintuplets	5
<spare></spare>	6-7

#### Table 8.38-2: Used NAS Cipher Values

Cipher Algorithm	Value (Decimal)
No ciphering	0
128-EEA1	1
128-EEA2	2
128-EEA3	3
EEA4	4
EEA5	5
EEA6	6
EEA7	7
<spare></spare>	8-15

#### Table 8.38-3: Used Cipher Values

Cipher Algorithm	Value (Decimal)
No ciphering	0
GEA/1	1
GEA/2	2
GEA/3	3
GEA/4	4
GEA/5	5
GEA/6	6
GEA/7	7

#### Table 8.38-4: Used NAS integrity protection algorithm Values

Integrity protection Algorithm	Value (Decimal)
No integrity protection	0
128-EIA1	1
128-EIA2	2
128-EIA3	3
EIA4	4
EIA5	5
EIA6	6
EIA7	7

Integrity protection Algorithm	Value (Decimal)
No integrity protection	0
spare	1
spare	2
spare	3
GIA4	4
GIA5	5
spare	6
spare	7

 Table 8.38-5: Used GPRS integrity protection algorithm Values

### 8.39 PDN Connection

The PDN connection is a grouped IE containing a number of other IEs and shall be coded as depicted in Table 8.39-1.

The PDN Connection IE may be repeated within a message when more than one PDN Connection is required to be sent. If so, the repeated IEs shall have exactly the same Instance values to represent a list of grouped IEs.

Table 8.39-1: PDN Connection Grouped Type

Octet 1		PDN Connection IE Type = 109 (decimal)		
Octets 2 and 3		Length = n		
Octet 4		Spare and Instance fields		
Information elements	Ρ	Condition / Comment	IE Type	Ins.
		a 5-column format in order to match the format used in subcles IE is further detailed for each specific GTP message includ	,	where

## 8.40 PDU Numbers

The PDU Numbers information element contains the sequence number status corresponding to a Bearer context in the old SGSN. This information element shall be sent only when acknowledged peer-to-peer LLC operation is used for the Bearer context or when the "delivery order" QoS attribute is set in the Bearer context QoS profile.

NSAPI identifies the Bearer context for which the PDU Number IE is intended.

DL GTP-U Sequence Number is the number for the next downlink GTP-U T-PDU to be sent to the UE when "delivery order" is set.

UL GTP-U Sequence Number is the number for the next uplink GTP-U T-PDU to be tunnelled to the S-GW when "delivery order" is set.

The Send N-PDU Number is used only when acknowledged peer-to-peer LLC operation is used for the Bearer context. Send N-PDU Number is the N-PDU number to be assigned by SNDCP to the next down link N-PDU received from the S-GW.

The Receive N-PDU Number is used only when acknowledged peer-to-peer LLC operation is used for the Bearer context. The Receive N-PDU Number is the N-PDU number expected by SNDCP from the next up link N-PDU to be received from the UE.

The PDU Number IE will be repeated for each Bearer Context for which this IE is required.

PDU Numbers IE is coded as depicted in Figure 8.40-1.

				В	its			
Octets	8	7	6	5	4	3	2	1
1			Ту	be = 11	0 (decir	nal)		
2 to 3				Leng	th = n			
4		Sp	are			Inst	ance	
5		Spare(	0000)			NS	API	
6-7			DL GTF	P-U See	quence	Numbe	r	
8-9			UL GTR	P-U See	quence	Numbe	r	
10-11			Sei	nd N-PI	DU Nun	nber		
12-13			Rece	eive N-I	PDU Nu	Imber		
14 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified

Figure 8.40-1: PDU Numbers

# 8.41 Packet TMSI (P-TMSI)

The P-TMSI, unambiguously associated with a given UE and routeing area, is given by:

	Bits											
Octets	8	8 7 6 5 4 3 2 1										
1		Type = 111 (decimal)										
2 to 3		Length = n										
4		Sp	are			Inst	ance					
5 to (n+4)		Packet TMSI (P-TMSI)										
	Г	he P-T	MSI is (	defined	in 3GP	P TS 23	3.003 [2	2].				

Figure 8.41-1: Packet TMSI (P-TMSI)

## 8.42 P-TMSI Signature

The content and the coding of the P-TMSI Signature information element are defined in 3GPP TS 24.008 [5].




Figure 8.42-1: P-TMSI Signature

# 8.43 Hop Counter

Where Intra Domain Connection of RAN Nodes to Multiple CN Node is applied, the Hop Counter may be used to prevent endless loops when relaying Identification Request messages and Context Request messages. The maximum value is operator specific and shall not be lower than 1.




Figure 8.43-1: Hop Counter

# 8.44 UE Time Zone

UE Time Zone is used to indicate the offset between universal time and local time in steps of 15 minutes of where the UE currently resides. The "Time Zone" field uses the same format as the "Time Zone" IE in 3GPP TS 24.008 [5].

UE Time Zone is coded as this is depicted in Figure 8.44-1. The value of the Time Zone field represents the time zone adjusted for daylight saving time. The value of the Daylight Saving Time field specifies the adjustment that has been made.

The spare bits indicate unused bits, which shall be set to 0 by the sending side and which shall not be evaluated by the receiving side.




Figure 8.44-1: UE Time Zone

Table 8.44-2 Possible values for the "Daylight Saving Time" field and their meanings.

Daylight Saving Time	Value (	binary)
	Bit 2	Bit 1
No adjustment for Daylight Saving Time	0	0
+1 hour adjustment for Daylight Saving Time	0	1
+2 hours adjustment for Daylight Saving Time	1	0
Spare	1	1

## 8.45 Trace Reference

Trace Reference shall be coded as depicted in Figure 8.45-1. See 3GPP TS 32.422 [18], clause 5.6, for the definition of Trace Reference.

See 3GPP TS 24.008 [5], clause 10.5.1.4, Mobile Identity, for the coding of MCC and MNC, whose values are obtained from the serving PLMN that the EM/NM is managing. If MNC is 2 digits long, bits 5 to 8 of octet 6 are coded as "1111".

				В	its							
Octets	8	7	6	5	4	3	2	1				
1		Type = 115 (decimal)										
2 to 3				Leng	th = 6							
4		Sp	are			Inst	ance					
5		MCC	digit 2			MCC	digit 1					
6		MNC	digit 3			MCC	digit 3					
7		MNC digit 2 MNC digit 1										
8 to10				Trac	ce ID							

Figure 8.45-1: Trace Reference

# 8.46 Complete Request Message

The Complete Request Message is coded as depicted in Figure 8.46-1.

	Bits										
Octets	8	7	6	5	4	3	2	1			
1		Type = 116 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5		C	omplete	Reque	st Mes	sage Ty	pe				
6 to (n+4)			Compl	ete Re	quest M	essage					

Figure 8.46-1: Complete Request Message

Complete Request Message type values are specified in Table 8.46-1.

Table 8.46-1: Complete Request Message type values and their meanings

Location Types	Values (Decimal)
Complete Attach Request Message	0
Complete TAU Request Message	1
<spare></spare>	2-255

## 8.47 GUTI

The GUTI is coded as depicted in Figure 8.47-1.

				В	its					
Octets	8	7	6	5	4	3	2	1		
1			Тур	be = 11	7 (decir	nal)				
2 to 3				Leng	th = n					
4		Spa	are			Inst	ance			
5		MCC	digit 2		MCC digit 1					
6		MNC	digit 3		MCC digit 3					
7		MNC	digit 2		MNC digit 1					
8 to 9		MME Group ID								
10				MME	Code					
11 to (n+4)				M-T	MSI					

Figure 8.47-1: GUTI

If an Administration decides to include only two digits in the MNC, then bits 5 to 8 of octet 6 are coded as "1111".

The "MME Group ID", "MME Code" and "M-TMSI" are specified in 3GPP TS 23.003 [2].

## 8.48 Fully Qualified Container (F-Container)

Fully Qualified Container (F-Container) is coded as depicted in Figure 8.48-1.

All Spare bits are set to zeros by the sender and ignored by the receiver.




Figure 8.48-1: Full Qualified Container (F-Container)

The F-Container field shall contain one of the following information, depending of the contents of the container transported by the specific GTP Information Element:

- *transparent copy* of the corresponding IEs (see subclause 8.2.2):
  - the "Source to Target Transparent Container" or the "Target to Source Transparent Container" as specified in 3GPP TS 25.413 [33]; or
  - the "SON Configuration Transfer" as specified in 3GPP TS 36.413 [10]; or
  - the "eNB Status Transfer Transparent Container" as specified in 3GPP TS 36.413 [10]; or
  - "Source BSS to Target BSS Transparent Container" or "Target BSS to Source BSS Transparent Container" as specified in 3GPP TS 48.018 [34] or 3GPP TS 25.413 [33], which contains the value part of the "Source BSS to Target BSS Transparent Container" IE or the value part of the "Target BSS to Source BSS Transparent

Container" IE defined in 3GPP TS 48.018 [34], i.e. octets 3 to n, excluding octet 1 (Element ID) and octet 2, 2a (Length) ; or

- transparent copy of the value part of the "NBIFOM Container" as specified in 3GPP TS 24.161 73].
- *transparent copy* of the octets of the encoded OCTET STRING of the "Source to Target Transparent Container" or the "Target to Source Transparent Container" specified in 3GPP TS 36.413 [10]; or
- transparent copy of the BSSGP RIM PDU as specified in 3GPP TS 48.018 [34]; or
- the Packet Flow ID, Radio Priority, SAPI, PS Handover XID parameters as specified in figure 8.42-2.
- NOTE 1: Annex B.2 provides further details on the encoding of Generic Transparent Containers over RANAP, S1-AP and GTP. See also Annex C of 3GPP TS 36.413 [10] for further details on how the MME constructs the F-Container field from the Source to Target Transparent Container or Target to Source Transparent Container IEs received from S1-AP.

Container Type values are specified in Table 8.48-2.

Container Types	Values (Decimal)
Reserved	0
UTRAN Transparent Container	1
BSS Container	2
E-UTRAN Transparent Container	3
NBIFOM Container	4
<spare></spare>	5-255

Table 8. 48-2: Container Type values

NOTE 2: For any other new future F-Container content types, new Container Type values may be needed, although use of RAT agnostic containers should be used whenever possible.

The BSS Container IE in the Bearer Context IE in Forward Relocation Request and Context Response messages is coded as depicted in Figure 8.48-3.

	Bits									
Octets	8	7	6	5	4	3	2	1		
6		Sp	are		PHX	SAPI	RP	PFI		
а		Packet Flow ID								
b		SA	١٩		Spare	Rad	dio Pric	ority		
С		XiD parameters length								
d to n				XiD par	ameters	3				



The flags PFI, RP, SAPI and PHX in octet 6 indicate the corresponding type of parameter (Packet FlowID, Radio Priority, SAPI and PS handover XID parameters) shall be present in a respective field or not. If one of these flags is set to "0", the corresponding field shall not be present at all. The Spare bit shall be set to zero by the sender and ignored by the receiver.

If PFI flag is set, Packet Flow ID shall be present in Octet a.

If RP flag is set, Radio Priority shall be present in Octet b.

If SAPI flag is set, SAPI shall be present in Octet b.

If PHX flag is set:

- XiD parameters length is present in Octet c.
- XiD parameters are present in Octet d to n.

# 8.49 Fully Qualified Cause (F-Cause)

Fully Qualified Cause (F- Cause) is coded as depicted in Figure 8.49-1.

Bits											
Octets	8	7	6	5	4	3	2	1			
1		Type = 119 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5		Spare Cause Type									
6 to (n+4)				F-Cau	se field						

Figure 8.49-1: Full Qualified Cause (F-Cause)

The value of Instance field of the F-Cause IE in a GTPv2 message shall indicate whether the F-Cause field contains RANAP Cause, BSSGP Cause or S1-AP Cause.

All spare bits shall be set to zeros by the sender and ignored by the receiver.

F-Cause field is coded as follows:

- For RANAP Cause, the F-Cause field shall contain a non-transparent copy of the cause value of the corresponding IE (see subclause 8.2.2), "Cause", as defined in clause 9.2.1.4 in 3GPP TS 25.413 [33]. Cause Type field shall be ignored by the receiver. The value of F-Cause field (which has a range of 1..512) is transferred over the Iu interface and encoded into two octet as binary integer.
- For BSSGP Cause, the F-Cause field shall contain a non-transparent copy of the cause value of the corresponding IE (see subclause 8.2.2), "Cause", as defined in clause 11.3.8 in 3GPP TS 48.018 [34]. Cause Type field shall be ignored by the receiver. The value of F-Cause field (which has a range of 0..255) is transferred over the Gb interface and encoded into one octet as binary integer.
- For S1-AP Cause, the F-Cause field shall contain a non-transparent copy of the cause value of the corresponding IE (see subclause 8.2.2), "Cause", as defined in clause 9.2.1.3 in 3GPP TS 36.413 [10].
   Cause Type field shall contain the RAN Cause subcategory as specified in 3GPP TS 36.413 [10] and it shall be encoded as in Table 8.49-1. The value of F-Cause field (and the associated RAN cause subcategory) is transferred over the S1-AP interface and encoded into one octet as binary integer.

Cause Type	Values (Decimal)
Radio Network Layer	0
Transport Layer	1
NAS	2
Protocol	3
Miscellaneous	4
<spare></spare>	5 to15

#### Table 8.49-1: Cause Type values and their meanings

# 8.50 PLMN ID

Octets 5-7 shall contain a non-transparent copy of the "PLMN Identity" parameter in 3GPP TS 36.413 [10].

				В	its			
Octets	8	7	6	5	4	3	2	1
1			Тур	be = 12	0 (decir	nal)		
2 to 3				Leng	th = n			
4		Spa	are			Inst	ance	
5 to (n+4)				PLN	IN ID			

Figure 8.50-1: PLMN ID

The encoding of the PLMN ID field is shown in Figures 8.50-2 and 8.50-3.

If three digits are included in the MNC, octets 5 to 7 shall be encoded as shown in Figure 8.50-2.

				Bits				
Octets	8	7	6	5	4	3	2	1
5		М	CC dig	it 2		MCO	C digit 1	
6		М	NC dig	it 1		MCO	C digit 3	
7		Μ	NC dig	it 3		MN	C digit 2	

Figure 8.50-2: PLMN ID Parameter with 3-digit MNC

If only two digits are included in the MNC, octets 5 to 7 shall be encoded as shown in Figure 8.50-3 with bits 5 to 8 of octet 6 (MNC digit 3) coded as "1111".

				Bits				
Octets	8	7	6	5	4	3	2	1
5		Μ	CC dig	it 2		MCC	C digit 1	
6			1111			MCC	C digit 3	
7		М	NC dig	it 2		MNG	C digit 1	

Figure 8.50-3: PLMN ID Parameter with 2-digit MNC

NOTE: The encoding is different from elsewhere in this document and is specified according to 3GPP TS 36.413 [10].

## 8.51 Target Identification

The Target Identification information element is coded as depicted in Figure 8.51-1.




Figure 8.51-1: Target Identification

Target Type values are specified in Table 8.51-1.

The Target Type is RNC ID for SRNS relocation procedure, handover to UTRAN and RAN Information Relay towards UTRAN or GERAN operating in GERAN Iu mode. In this case the "Target ID" field shall contain a non-transparent copy of the corresponding IEs (see subclause 8.2.2) and be encoded as specified in Figure 8.51-1a below. The "Target RNC-ID" part of the "Target ID" parameter is specified in 3GPP TS 25.413 [33].

- NOTE 1: The ASN.1 parameter "Target ID" is forwarded non-transparently in order to maintain backward compatibility.
- NOTE 2: The preamble of the "Target RNC-ID" (numerical value of e.g. 0x20) shall not be included into octets 6 to (n+4). Also, the optional "iE-Extensions" parameter shall not be included into the GTP IE.

				Bi	ts						
Octets	8	7	6	5	4	3	2	1			
6		MCC	digit 2			MCC	digit 1				
7		MNC digit 3 MCC digit 3									
8		MNC	digit 2			MNC	digit 1				
9 to 10		LAC									
11		RAC (see NOTE 3)									
12 to 13		RNC-ID									
a to (a+1)			Extend	led RN	C-ID (o	ptional)					

Figure 8.51-1a: Target ID for Type RNC ID

If only two digits are included in the MNC, then bits 5 to 8 of octet 7 (MNC digit 3) shall be coded as "1111".

The location area code (LAC) consists of 2 octets. Bit 8 of octet 9 is the most significant bit and bit 1 of octet 10 is the least significant bit. The coding of the location area code is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The RNC-ID consists of 2 octets and contains 12 bits long value (see 3GPP TS 25.413 [7]). Bit 4 of octet 12 is the most significant bit and bit 1 of octet 13 is the least significant bit (bits 8 to 5 of octet 12 are set to 0). The coding of the RNC-ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The Extended RNC-ID consists of 2 octets and contains 16 bits long value within the range 4096 to 65535. Bit 8 of octet a is the most significant bit and bit 1 of octet (a+1) is the least significant bit. The coding of the Extended RNC-ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used. If the optional Extended RNC-ID is included, then the receiver shall ignore the RNC-ID.

If the optional Extended RNC-ID is not included, then the length variable 'n' = 8 and the overall length of the IE is 13 octets. Otherwise, 'n' = 10 and the overall length of the IE is 15 octets.

NOTE 3: In the "TargetRNC-ID" ASN.1 type definition in 3GPP TS 25.413 [7] the "RAC" parameter is marked as optional. RAC is however always available at an SGSN/MME when it sends the RAC in e.g. a GTPv2 Forward Relocation Request message.

The Target Type is Macro eNodeB ID for handover to E-UTRAN Macro eNodeB and RAN Information Relay towards E-UTRAN. In this case the coding of the Target ID field shall be coded as depicted in Figure 8.51-2.

				В	its				
Octets	8	7	6	5	4	3	2	1	
6		MCC	digit 2			MCC	digit 1		
7		MNC	digit 3	MCC digit 3					
8		MNC	digit 2		MNC digit 1				
9		Sp	are		Ν	/lacro el	NodeB I	ID	
10 to 11			Μ	acro el	NodeB ID				
12 to 13			Tracki	ng Are	a Code	(TAC)			

Figure 8.51-2: Target ID for Type Macro eNodeB

The Macro eNodeB ID consists of 20 bits. Bit 4 of Octet 9 is the most significant bit and bit 1 of Octet 11 is the least significant bit. The coding of the Macro eNodeB ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The Target Type is Home eNodeB ID for handover to E-UTRAN Home eNodeB. In this case the coding of the Target ID field shall be coded as depicted in Figure 8.51-3.

		Bits									
Octets	8	7	6	5	4	3	2	1			
6		MCC	digit 2		MCC	digit 1					
7	MNC digit 3 MCC digit 3										
8		MNC	digit 2		MNC digit 1						
9		Sp	are		Home eNodeB ID						
10 to 12		Home eNodeB ID									
13 to 14			Tracki	ng Area	a Code	(TAC)					

Figure 8.51-3: Target ID for Type Home eNodeB

The Home eNodeB ID consists of 28 bits. See 3GPP TS 36.413 [10]. Bit 4 of Octet 9 is the most significant bit and bit 1 of Octet 12 is the least significant bit. The coding of the Home eNodeB ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

The Target Type is Extended Macro eNodeB ID for handover to E-UTRAN Macro eNodeB and RAN Information Relay towards E-UTRAN. In this case the coding of the Target ID field shall be coded as depicted in Figure 8.51-x.

		Bits										
Octets	8	7	6	5	4	3	2	1				
6		MCC digit 2 MCC digit 1										
7		MNC digit 3 MCC digit 3										
8		MNC digit 2 MNC digit 1										
9	SMeN	Sp	are	Ex	Extended Macro eNodeB ID							
	В	-										
10 to 11		Extended Macro eNodeB ID										
12 to 13			Tracki	ing Area	a Code	(TAC)						

Figure 8.51-4: Target ID for Type Extended Macro eNodeB

The Extended Macro eNodeB ID consists of 21 bits. The coding of the Macro eNodeB ID is the responsibility of each administration. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

If the SMeNB flag is not set the Extended Macro eNodeB ID contains a Long Macro eNodeB ID with a length of 21 Bits. Bit 5 of Octet 9 is the most significant bit and bit 1 of Octet 11 is the least significant bit.

If the SMeNB flag is set the Extended Macro eNodeB ID contains a Short Macro eNodeB ID with a length of 18 Bits. Bits 5 to 3 of Octet 9 shall be set to 0 by the sender and shall be ignored by the receiver. Bit 2 of Octet 9 is the most significant bit and bit 1 of Octet 11 is the least significant bit.

The Target Type is Cell Identifier for E-UTRAN handover to GERAN and RAN Information Relay towards GERAN. In this case the coding of the Target ID field shall be same as the Octets 3 to 10 of the Cell Identifier IEI in 3GPP TS 48.018 [34].

Table 8.51-1: Target Type values and their meanings

Target Types	Values (Decimal)
RNC ID	0
Macro eNodeB ID	1
Cell Identifier	2
Home eNodeB ID	3
Extended Macro eNodeB ID	4
<spare></spare>	5 to 255

### 8.52 Void

### 8.53 Packet Flow ID

The Packet Flow Id information element contains the packet flow identifier assigned to an EPS Bearer context as identified by EPS Bearer ID.

The spare bits 8 to 5 in octet 5 indicate unused bits, which shall be set to 0 by the sending side and which shall not be evaluated by the receiving side.

				В	its						
Octets	8	7	6	5	4	3	2	1			
1		Type = 123 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5		Sp	are			E	BI				
6 to (n+4)				Packet	Flow ID	)					

Figure 8.53-1: Packet Flow ID

#### 8.54 RAB Context

The RAB Context shall be coded as is depicted in Figure 8.54-1.

				Bi	ts				
Octets	8	7	6	5	4	3	2	1	_
1			Тур	be = 124	4 (decir	nal)			
2 to 3				Leng	th = 9				
4		Sp	are			Inst	ance		
5		Sp	are			NS	API		
6 to 7			DL GTF	P-U Sec	uence	Numbe	r		
8 to 9			UL GTF	P-U Sec	uence	Numbe	r		
10 to 11			DL PD	CP Seq	uence l	Number			
12 to 13			UL PD	CP Seq	uence l	Number			

Figure 8.54-1: RAB Context

The RAB Context IE may be repeated within a message with exactly the same Type and Instance to represent a list.

The RAB context information element contains sequence number status for one RAB in RNC, which corresponds to one PDP context. The RAB contexts are transferred between the RNCs via the SGSNs at inter SGSN hard handover.

NSAPI identifies the PDP context and the associated RAB for which the RAB context IE is intended.

DL GTP-U Sequence Number is the number for the next downlink GTP-U T-PDU to be sent to the UE.

UL GTP-U Sequence Number is the number for the next uplink GTP-U T-PDU to be tunnelled to the SGW.

DL PDCP Sequence Number is the number for the next downlink PDCP-PDU to be sent to the UE.

UL PDCP Sequence Number is the number for the next uplink PDCP-PDU to be received from the UE.

## 8.55 Source RNC PDCP context info

The purpose of the Source RNC PDCP context info IE is to transfer RNC PDCP context information from a source RNC to a target RNC during an SRNS relocation.




Figure 8.55-1: Source RNC PDCP context info

#### 8.56 Port Number

Port Number is coded as depicted in Figure 8.56-1.

	Bits										
Octets	8	7	6	5	4	3	2	1			
1		Type = 126 (decimal)									
2 to 3		Length = 2									
4		Sp	are			Inst	ance				
5 to 6		Port Number									
7 to (n+4)	Thes	e octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified			

Figure 8.56-1: Port Number

### 8.57 APN Restriction

The APN Restriction information element contains an unsigned integer value indicating the level of restriction imposed on EPS Bearer Contexts created to the associated APN.

The APN Restriction IE is coded as depicted in Figure 8.57-1:




Figure 8.57-1: APN Restriction Type Information Element

An APN Restriction value may be configured for each APN in the PGW. It is used to determine, on a per UE basis, whether it is allowed to establish EPS bearers to other APNs.

Table 8.57-1: Valid Combinations of APN Restriction

Maximum APN Restriction Value	Type of APN	Application Example	APN Restriction Value allowed to be established
0	No Existing Con	texts or Restriction	All
1	Public-1	MMS	1, 2, 3
2	Public-2	Internet	1, 2
3	Private-1	Corporate (e.g. who use MMS)	1
4	Private-2	Corporate (e.g. who do not use MMS)	None

## 8.58 Selection Mode

The Selection mode information element indicates the origin of the APN in the message.




Figure 8.58-1: Selection Mode Information Element

Table 8.58-1:	Selection	Mode	Values

Selection mode value	Value (Decimal)
MS or network provided APN, subscription verified	0
MS provided APN, subscription not verified	1
Network provided APN, subscription not verified	2
For future use. Shall not be sent. If received, shall be interpreted as the value "2".	3

## 8.59 Source Identification

The Source Identification information element is coded as depicted in Figure 8.59-1.

	Bits									
Octets	8	7	6	5	4	3	2	1		
1	Type = 129 (decimal)									
2 to 3	Length = n									
4		Sp	are		Instance					
5 to 12	Target Cell ID									
13	Source Type									
14 to (n+4)				Sour	ce ID					

Figure 8.59-1: Source Identification

The Target Cell ID shall be same as the Octets 3 to 10 of the Cell Identifier IEI in 3GPP TS 48.018 [34].

Source Type values are specified in Table 8.59-1.

If the Source Type is Cell ID, this indicates PS handover from GERAN A/Gb mode. In this case the coding of the Source ID field shall be same as the Octets 3 to 10 of the Cell Identifier IEI in 3GPP TS 48.018 [34].

If the Source Type is RNC ID, this indicates PS handover from GERAN Iu mode or for inter-RAT handover from UTRAN. In this case the Source ID field shall include a transparent copy of the corresponding parameter (see subclause 8.2.2), the Source RNC-ID as specified within the "Source ID" parameter in 3GPP TS 25.413 [33].

NOTE: In fact, the ASN.1/PER encoded binary value of the "Source RNC ID" shall be copied into octets 14 to (n+4).

Source Types	Values (Decimal)
Cell ID	0
RNC ID	1
reserved (NOTE)	2
<spare></spare>	3-255
NOTE: This value was allocated in a shall not be used.	an earlier version of the protocol and

Table 8.59-1: Source Type values and their meanings

### 8.60 Void

## 8.61 Change Reporting Action

Change Reporting Action IE is coded as depicted in Figure 8.61-1.

	Bits								
Octets	8	7	6	5	4	3	2	1	
1		Type = 131 (decimal)							
2 to 3	Length = n								
4		Spare Instance							
5 to (n+4)				Act	ion				

Figure 8.61-1: Change Reporting Action

Action	Value (Decimal)
Stop Reporting	0
Start Reporting CGI/SAI	1
Start Reporting RAI	2
Start Reporting TAI	3
Start Reporting ECGI	4
Start Reporting CGI/SAI and RAI	5
Start Reporting TAI and ECGI	6
Start Reporting Macro eNodeB ID	7
and Extended Macro eNodeB ID	
Start Reporting TAI, Macro	8
eNodeB ID and Extended Macro	
eNodeB ID	
<spare></spare>	9-255

Stop Reporting stops all reporting action types.

# 8.62 Fully qualified PDN Connection Set Identifier (FQ-CSID)

A fully qualified PDN Connection Set Identifier (FQ-CSID) identifies a set of PDN connections belonging to an arbitrary number of UEs on a MME, SGW, TWAN, ePDG or PGW. The FQ-CSID is used on S5, S8, S2a, S2b and S11 interfaces.

				В	its					
Octets	8	7	6	5	4	3	2	1		
1		Type = 132 (decimal)								
2 to 3				Leng	th = n					
4		Sp	are			Insta	ance			
5		Node-I	D Type		Number of CSIDs= m					
6 to p	Node-ID									
(p+1) to		First PDN Connection Set Identifier (CSID)								
(p+2)										
(p+3) to		Second PDN Connection Set Identifier (CSID)								
(p+4)										
q to q+1		m-th PDN Connection Set Identifier (CSID)								
(q+2) to	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified		
(n+4)										

The size of CSID is two octets. The FQ-CSID is coded as follows:

Figure 8.62-1: FQ-CSID

Where Node-ID Type values are:

- 0 indicates that Node-ID is a global unicast IPv4 address and p = 9.
- 1 indicates that Node-ID is a global unicast IPv6 address and p = 21.
- 2 indicates that Node-ID is a 4 octets long field with a 32 bit value stored in network order, and p= 9. The coding of the field is specified below:
- Most significant 20 bits are the binary encoded value of (MCC * 1000 + MNC).
- Least significant 12 bits is a 12 bit integer assigned by an operator to an MME, SGW, TWAN, ePDG or PGW. Other values of Node-ID Type are reserved.

Values of Number of CSID other than 1 are only employed in the Delete PDN Connection Set Request.

The node that creates the FQ-CSID, (i.e. MME for MME FQ-CSID, SGW for SGW FQ-CSID, TWAN for TWAN FQ-CSID, ePDG for ePDG FQ-CSID and PGW for PGW FQ-CSID), is responsible for making sure the Node-ID is globally unique and the CSID value is unique within that node.

When a FQ-CSID is stored by a receiving node, it is stored on a PDN basis even for messages impacting only one bearer (i.e. Create Bearer Request). See 3GPP TS 23.007 [17] for further details on the CSID and what specific requirements are placed on the PGW, TWAN, ePDG, SGW and MME.

## 8.63 Channel needed

The Channel needed shall be coded as depicted in Figure 8.63-1. Channel needed is coded as the IEI part and the value part of the Channel Needed IE defined in 3GPP TS 44.018[28]




Figure 8.63-1: Channel needed

## 8.64 eMLPP Priority

The eMLPP-Priority shall be coded as depicted in Figure 8.64-1. The eMLPP Priority is coded as the value part of the eMLPP-Priority IE defined in 3GPP TS 48.008 [29] (not including 3GPP TS 48.008 IEI and 3GPP TS 48.008 [29] length indicator).




Figure 8.64-1: eMLPP Priority

## 8.65 Node Type

Node Type is coded as this is depicted in Figure 8.65-1.

				В	its				
Octets	8	7	6	5	4	3	2	1	_
1			Ту	be = 13	5 (decir	nal)			
2-3			Le	ngth = I	n (decin	nal)			
4		Sp	are			Inst	ance		
5				Node	Туре				
6-(n+4)	Thes	se octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified	

Figure 8.65-1: Node Type

Node type values are specified in Table 8.65-1.

Table 8. 65-1: Node Type values

Node Types	Values (Decimal)
MME	0
SGSN	1
<spare></spare>	2-255

If with a Release Access Bearers Request, or Suspend Notification, or Resume an SGW receives a semantically erroneus/unexpected Originating Node, then the following applies:

- If SGW has an active connection to an MME, but the Originating Node IE contains value "SGSN", then the SGW shall not release the user plane and shall send a response to the SGSN with some appropriate cause value.

- If SGW has an active connection to an S4-SGSN, but the Originating Node IE contains value "MME", then the SGW shall not release the user plane and shall send a response to the MME with some appropriate cause value.

## 8.66 Fully Qualified Domain Name (FQDN)

Fully Qualified Domain Name (FQDN) is coded as depicted in Figure 8.66-1.




Figure 8.66-1: Fully Qualified Domain Name (FQDN)

The FQDN field encoding shall be identical to the encoding of a FQDN within a DNS message of section 3.1 of IETF RFC 1035 [31] but excluding the trailing zero byte.

NOTE 1: The FQDN field in the IE is not encoded as a dotted string as commonly used in DNS master zone files.

A "PGW node name" IE in S3/S10/S16 GTP messages shall be a PGW host name as per subclause 4.3.2 of 3GPP TS 29.303 [32] when the PGW FQDN IE is populated from 3GPP TS 29.303 [32] procedures. Specifically, the first DNS label is either "topon" or "topoff", and the canonical node name of the PGW starts at the third label. The same rules apply to "SGW node name" IE on S3/S10/S16 and "SGW-U node name" IE on S5.

NOTE 2: The constraint of subclause 4.3.2 of 3GPP TS 29.303 format is on populating the IE by 3GPP nodes for 3GPP nodes, the receiver shall not reject an IE that is otherwise correctly formatted since the IE might be populated for a non-3GPP node.

An "MME node name" IE and an "SGSN node name" IE in S3 GTP messages indicate the associated ISR node when the ISR becomes active.

### 8.67 Private Extension

Private Extension is coded as depicted in Figure 8.Figure 8.67-1.

Enterprise ID can be found at IANA web site (http://www.iana.org/assignments/enterprise-numbers).

	Bits								
Octets	8	7	6	5	4	3	2	1	
1	Type = 255 (decimal)								
2 to 3	Length = n								
4		Sp	are			Inst	ance		
5 to 6	Enterprise ID								
7 to (n+4)			F	Propriet	ary valu	ie			

Figure 8.67-1. Private Extension

# 8.68 Transaction Identifier (TI)

Transaction Identifier is coded as depicted in Figure 8.68-1. It is defined in 3GPP TS 24.301 [23], clause 9.9.4.17 and is coded as specified in 3GPP TS 24.007 [30], clause 11.2.3.1.3 Transaction identifier.

	Bits							
Octets	8	7	6	5	4	3	2	1
1	Type = 137 (decimal)							
2 to 3	Length = n							
4	Spare Instance							
5 to (n+4)	Transaction Identifier							

Figure 8.68-1: Transaction Identifier

## 8.69 MBMS Session Duration

The MBMS Session Duration is defined in 3GPP TS 23.246 [37]. The MBMS Session Duration information element indicates the estimated session duration of the MBMS service data transmission if available. The payload shall be encoded as per the MBMS-Session-Duration AVP defined in 3GPP TS 29.061 [38], excluding the AVP Header fields (as defined in IETF RFC 3588 [39], section 4.1).




Figure 8.69-1: MBMS Session Duration

# 8.70 MBMS Service Area

The MBMS Service Area is defined in 3GPP TS 23.246 [37]. The MBMS Service Area information element indicates the area over which the Multimedia Broadcast Multicast Service is to be distributed. The payload shall be encoded as per the MBMS-Service-Area AVP defined in 3GPP TS 29.061 [38], excluding the AVP Header fields (as defined in IETF RFC 3588 [39], section 4.1).




Figure 8.70-1: MBMS Service Area

## 8.71 MBMS Session Identifier

The MBMS Session Identifier information element contains a Session Identifier allocated by the BM-SC. The MBMS Session Identifier value part consists of 1 octet. The content and the coding are defined in 3GPP TS 29.061 [38].

-				D	40			
	Bits							
Octets	8	7	6	5	4	3	2	1
1	Type = 140 (decimal)							
2 to 3	Length = n							
4	Spare Instance							
5	MBMS Session Identifier							
6 to (n+4)	Thes	se octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified

Figure 8.71-1: MBMS Session Identifier

# 8.72 MBMS Flow Identifier

The MBMS Flow Identifier is defined in 3GPP TS 23.246 [37]. In broadcast mode, the MBMS Flow Identifier information element is included in MBMS Session Management messages to differentiate the different sub-sessions of an MBMS user service (identified by the TMGI) providing location-dependent content. The payload shall be encoded as per the MBMS-Flow-Identifier AVP defined in 3GPP TS 29.061 [38], excluding the AVP Header fields (as defined in IETF RFC 3588 [39], section 4.1).




Figure 8.72-1: MBMS Flow Identifier

## 8.73 MBMS IP Multicast Distribution

The MBMS IP Multicast Distribution IE is sent by the MBMS GW to the MME/SGSN in the MBMS Session Start Request. Source Specific Multicasting is used according to IETF RFC 4607 [40].

The IP Multicast Distribution Address and the IP Multicast Source Address fields contain the IPv4 or IPv6 address. The Address Type and Address Length fields shall be included in each field:

- The Address Type, which is a fixed length code (of 2 bits) identifying the type of address that is used in the Address field.
- The Address Length, which is a fixed length code (of 6 bits) identifying the length of the Address field.
- The Address, which is a variable length field shall contain either an IPv4 address or an IPv6 address.

Address Type 0 and Address Length 4 shall be used when Address is an IPv4 address.

Address Type 1 and Address Length 16 shall be used when Address is an IPv6 address.

Other combinations of values are not valid.

MBMS HC Indicator represents an indication if header compression should be used for MBMS user plane data, as specified in 3GPP TS 25.413 [33]. MBMS HC Indicator field is encoded as a one octet long enumeration.

NOTE: Currently, 3GPP TS 25.413 [33] specifies two enumeration values: 0 (indicates "uncompressed-header") and 1 (indicates "compressed-header").

Common Tunnel Endpoint Identifier is allocated at the source Tunnel Endpoint and signalled to the destination Tunnel Endpoint. There is one Common Tunnel Endpoint Identifier allocated per MBMS bearer service. The recommendations on how to set the value of C-TEID are provided in 3GPP TS 23.246 [37].

		Bits						
Octets	8	7	6	5	4	3	2	1
1		Type = 142 (decimal)						
2 to 3				Leng	gth=n			
4		Spare Instance						
5 to 8	Common Tunnel Endpoint Identifier							
9	Address Type Address Length							
10 to K	IF	IP Multicast Distribution Address (IPv4 or IPv6)					6)	
K+1	Address Type Address Length							
(k+2) to m	IP Multicast Source Address (IPv4 or IPv6)							
m+1		MBMS HC Indicator						
(m+2) to n	Thes	e octet	These octet(s) is/are present only if explicitly specified					

Figure 8.73-1: MBMS IP Multicast Distribution

## 8.74 MBMS Distribution Acknowledge

The MBMS Distribution Acknowledge IE is sent by the SGSN to the MBMS GW in the MBMS Session Start Response and MBMS Session Update Response. It is used by the MBMS GW to decide if an IP Multicast Distribution user plane shall be established, or a normal point-to-point user plane, or both.




Figure 8.74-1: MBMS Distribution Acknowledge

Table 8.74-1: Distribution Ind	lication values
--------------------------------	-----------------

Distribution Indication	Value (Decimal)
No RNCs have accepted IP multicast distribution	0
All RNCs have accepted IP multicast distribution	1
Some RNCs have accepted IP multicast distribution	2
Spare. For future use.	3

# 8.75 User CSG Information (UCI)

User CSG Information (UCI) is coded as depicted in Figure 8.75-1. The CSG ID is defined in 3GPP TS 23.003 [2].

				В	its			
Octets	8	7	6	5	4	3	2	1
1				Туре	= 145			
2 to 3				Leng	th = n			
4		Sp	are			Ins	tance	
5		MCC	digit 2		MCC digit 1			
6		MNC	digit 3		MCC digit 3			
7		MNC	digit 2			MNC	digit 1	
8		spare					CSG ID	
9 to11	CSG ID							
12	Access mode sp			are		LCSG	CMI	
13 to (n+4)	Thes	These octet(s) is/are present only if explicitly specified						

Figure 8.75-1: User CSG Information

For two digits in the MNC, bits 5 to 8 of octet 6 are coded as "1111".

The CSG ID consists of 4 octets. Bit 3 of Octet 8 is the most significant bit and bit 1 of Octet 11 is the least significant bit. The coding of the CSG ID is the responsibility of the operator that allocates the CSG ID by administrative means. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

Access mode values are specified in Table 8.75-1.

Access Mode	Values (Decimal)
Closed Mode	0
Hybrid Mode	1
Reserved	2-3

Leave CSG flag (LCSG) shall be set to "1" if UE leaves CSG cell/Hybrid cell, and in this case, the receiving node shall ignore the rest information in the IE.

CSG Membership Indication (CMI) values are specified in Table 8.75-2. CMI shall be included in the User CSG Information if the Access mode is Hybrid Mode. For the other values of Access Mode, the CMI shall be set to 0 by the sender and ignored by the receiver.

Table 8.75-2:	CSG Mem	bership i	indication	(CMI)	

СМІ	Values (Decimal)
Non CSG membership	0
CSG membership	1

NOTE: Due to a specification oversight, the CMI values in the above table are reversed from the values of the CMI IE (see subclause 8.79). Furthermore, the encoding is different between GTPv1 and GTPv2.

## 8.76 CSG Information Reporting Action

CSG Information Reporting Action is coded as depicted in Figure 8.76-1.




Figure 8.76-1: CSG Reporting Action


The following bits within Octet 5 shall indicate:

- Bit 1 UCICSG: When set to "1", shall indicate to start reporting User CSG Info when the UE enters/leaves/access through the CSG Cell.
- Bit 2 UCISHC: When set to "1", shall indicate to start reporting User CSG Info when the UE enters/leaves/access through Subscribed Hybrid Cell.
- Bit 3 UCIUHC: When set to "1", shall indicate to start Reporting User CSG Info when the UE enters/leaves/access through Unsubscribed Hybrid Cell.

All the bits 1 to 3 shall be set to 0 to stop reporting User CSG Info.

## 8.77 RFSP Index

Index to RAT/Frequency Selection Priority (RFSP Index) is coded as depicted in Figure 8.77-1, and contains a nontransparent copy of the corresponding IE (see subclause 8.2.2), "Subscriber Profile ID for RAT/Frequency Priority (SPID)" as specified in 3GPP TS 36.413 [10]. The SPID is an integer between 1 and 256 and is encoded as an unsigned integer, which requires the two octets specified for the RFSP Index parameter.



#### Figure 8.77-1. RFSP Index

## 8.78 CSG ID

CSG ID is coded as depicted in Figure 8.78-1. The CSG ID is defined in 3GPP TS 23.003 [2].




Figure 8.78-1: CSG ID

The CSG ID consists of 4 octets. Bit 3 of Octet 5 is the most significant bit and bit 1 of Octet 8 is the least significant bit. The coding of the CSG ID is the responsibility of the operator that allocates the CSG ID by administrative means. Coding using full hexadecimal representation (binary, not ASCII encoding) shall be used.

## 8.79 CSG Membership Indication (CMI)

CSG Membership Indication is coded as depicted in Figure 8.79-1.

				В	its				
Octets	8	7	6	5	4	3	2	1	
1		Type = 148							
2 to 3		Length = n							
4		Spare Instance							
5		Spare CMI							
6 to (n+4)	These octet(s) is/are present only if explicitly specified								

Figure 8.79-1: CSG Membership Indication



CSG Membership Indication (CMI) values are specified in Table 8.79-2.

Table 8.79-2: CS0	G Membership	indication	(CMI)
-------------------	--------------	------------	-------

СМІ	Values (Decimal)
CSG membership	0
Non CSG membership	1

NOTE: Due to a specification oversight, the CMI values in the above table are reversed from the values of the CSG-Membership-Indication AVP in 3GPP TS 32.299 [54], as well as from the values of the CMI in the UCI IE (see subclause 8.75). Therefore, when the above CMI values are sent over the charging interface, the values are encoded as specified in 3GPP TS 32.299 [54].

## 8.80 Service indicator

Service indicator is coded as depicted in Figure 8.80-1.




Figure 8.80-1. Service indicator

Service indicator values are specified in Table 8.80-1.

Service indicator	Values (Decimal)
<spare></spare>	0
CS call indicator	1
SMS indicator	2
<spare></spare>	3-255

Table 8.80-1: Service indicator values

## 8.81 Detach Type

Detach Type is coded as depicted in Figure 8.81-1.

				В	its			
Octets	8	7	6	5	4	3	2	1
1			Ту	oe = 15	0 (decir	nal)		
2 to 3	Length = 1							
4	Spare Instance							
5	Detach Type							

Figure 8.81-1: Detach Type

Table 8.81-1: Detach Type values

Detach Types	Values (Decimal)
<reserved></reserved>	0
PS Detach	1
Combined PS/CS Detach	2
<spare></spare>	3-255

## 8.82 Local Distinguished Name (LDN)

Represents the Local Distinguished Name (LDN) of the network element (see 3GPP TS 32.423 [44]).




Figure 8.82-1: Local Distinguished Name (LDN)

The LDN field consists of 1 up to a maximum of 400 ASCII characters, i.e., from 1 up to a maximum of 400 octets.

### 8.83 Node Features

Node Features IE is coded as depicted in Figure 8. 83-1.

				В	its				
Octets	8	7	6	5	4	3	2	1	
1		Type = 152 (decimal)							
2 to 3		Length = n							
4		Spare Instance							
5		Supported-Features							
6 to (n+4)	Thes	These octet(s) is/are present only if explicitly specified							

Figure 8.83-1: Node Features IE

The Node Features IE takes the form of a bitmask where each bit set indicates that the corresponding feature is supported. Spare bits shall be ignored by the receiver. The same bitmask is defined for all GTPv2 interfaces.

The following table specifies the features defined on GTPv2 interfaces and the interfaces on which they apply.

Feature Octet / Bit	Feature	Interface	Description
5/1	PRN	S11, S4	PGW Restart Notification. If both the SGW and the MME/S4-SGSN support this feature, the SGW shall send PGW Restart Notification message to the MME/S4-SGSN when the SGW detects that the peer PGW has restarted, and the SGW may send PGW Restart Notification message when the SGW detects that the peer PGW has failed and not restarted, as specified in subclause 7.9.5.
5/2	MABR	S11	Modify Access Bearers Request. If both the SGW and the MME support this feature, the MME may modify the S1-U bearers of all the PDN connections of the UE by sending a Modify Access Bearers Request message as specified in subclause 7.2.24.
5/3	NTSR	S11/S4	Network Triggered Service Restoration procedure. If both the SGW and the MME/S4-SGSN support this feature (see 3GPP TS 23.007 [17]), the SGW shall send a Downlink Data Notification message including the IMSI to the MME/S4-SGSN on the TEID 0 as part of a network triggered service restoration procedure.
5/4	CIOT	S11/S4	Cellular Internet Of Things. Support of this feature may be indicated over the S11/S4 interface, from the SGW to the MME/SGSN. See NOTE 1. If the SGW notifies the support of this feature over S11, it indicates to the MME that the SGW supports all the following CIoT features: - EUTRAN-NB-IoT RAT type, - Non-IP PDN type, - S11-U tunneling, - Serving PLMN Rate Control, - MO Exception Data indication, - Extended PCO If the SGW notifies the support of this feature over S4, it indicates to the SGSN that the SGW supports the Non-IP PDN type.
		eed to know whether the MME/S nd bit number within the Suppor	GSN support the CIoT feature.
		be used to refer to the octet / b	
Interface: A list of a	oplicable in	terfaces to the feature.	
Description: A clear	textual des	cription of the feature.	

#### Table 8.83-1: Node Features on GTPv2 interfaces

No features have been defined on the following GTPv2 interfaces in this version of the specification: S2a, S2b, S5, S8, S10, S3, S16, Sv, S101, S121, Sm, Sn.

## 8.84 MBMS Time to Data Transfer

The MBMS Time to Data Transfer indicates the minimum time occurring between the transmission of the MBMS SESSION START REQUEST message and the actual start of the data transfer. It is coded as shown in figure 8.84-1. Octet 5 is coded as the value part of the Time to MBMS Data Transfer IE defined in 3GPP TS 48.018 [34] (not including the IEI and length indicator octets specified in 3GPP TS 48.018 [34]).




Figure 8.84-1: MBMS Time to Data Transfer

## 8.85 Throttling

Throttling is coded as depicted in Figure 8.85-1.

				В	ts				
Octets	8	7	6	5	4	3	2	1	
1	Type = 154 (decimal)								
2 to 3	Length = n								
4	Spare Instance								
5	Throttling Delay Unit Throttling Delay Value								
6	Throttling Factor								
7 to (n+4)	These octet(s) is/are present only if explicitly specified								

Figure 8.85-1: Throttling

#### Table 8.85.1: Throttling information element

```
Throttling Delay (octet 5)
Bits 5 to 1 represent the binary coded timer value.
Bits 6 to 8 defines the timer unit for the timer as follows:
Bits
876
0 0 0 value is incremented in multiples of 2 seconds
0 0 1 value is incremented in multiples of 1 minute
0 1 0 value is incremented in multiples of 10 minutes
0 1 1 value is incremented in multiples of 1 hour
1 0 0 value is incremented in multiples of 10 hours
1 1 1 value indicates that the timer is deactivated.
Other values shall be interpreted as multiples of 1 minute.
Throttling Factor (octet 6)
The Throttling Factor indicates a percentage and may take binary coded integer
values from and including 0 up to and including 100. Other values shall be
considered as 0.
```

## 8.86 Allocation/Retention Priority (ARP)

Allocation/Retention Priority (ARP) is coded as depicted in Figure 8.86-1.

				В	its				
Octets	8	7	6	5	4	3	2	1	
1		Type = 155 (decimal)							
2 to 3		Length = n							
4		Spa	are			Inst	ance		
5	Spare	PCI	PL Spare PVI					PVI	
6 to (n+4)	These octet(s) is/are present only if explicitly specified								

Figure 8.86-1: Allocation/Retention Priority (ARP)

The meaning and value range of the parameters within the ARP are defined in 3GPP TS 29.212 [29]. The bits within the octet 5 are:

- Bit 1 PVI (Pre-emption Vulnerability): See 3GPP TS 29.212[29], clause 5.3.47 Pre-emption-Vulnerability AVP.
- Bit 2 spare
- Bits 3 to 6 PL (Priority Level): See 3GPP TS 29.212[29], clause 5.3.45 Priority-Level AVP. PL encodes each priority level defined for the Priority-Level AVP as the binary value of the priority level.
- Bit 7 PCI (Pre-emption Capability): See 3GPP TS 29.212[29], clause 5.3.46 Pre-emption-Capability AVP.
- Bit 8 spare.

### 8.87 EPC Timer

The purpose of the EPC Timer information element is to specify EPC specific timer values.

The EPC Timer information element is coded as shown in figure 8.87-1 and table 8.87.1

				В	its				
Octets	8	7	6	5	4	3	2	1	
1		Type = 156 (decimal)							
2 to 3		Length = n							
4		Spare Instance							
5	Timer unit Timer value								
6 to (n+4)	These octet(s) is/are present only if explicitly specified								

Figure 8.87-1: EPC Timer



Timer value
Bits 5 to 1 represent the binary coded timer value.
Timer unit
Bits 6 to 8 defines the timer value unit for the EPC timer as follows:
Bits
876
0 0 0 value is incremented in multiples of 2 seconds
0 0 1 value is incremented in multiples of 1 minute
0 1 0 value is incremented in multiples of 10 minutes
0 1 1 value is incremented in multiples of 1 hour
1 0 0 value is incremented in multiples of 10 hours
1 1 1 value indicates that the timer is infinite
Other values shall be interpreted as multiples of 1 minute in this version of the
protocol.
Timer unit and Timer value both set to all "zeros" shall be interpreted as an
indication that the timer is stopped.

### 8.88 Signalling Priority Indication

The Signalling Priority Indication information element contains signalling priority indications received from the UE for a specific PDN connection.

The Signalling Priority Indication information element is coded as shown in figure 8.88-1.




Figure 8.88-1: Signalling Priority Indication

The following bits within Octet 5 shall indicate:

- Bit 8 to 2 Spare, for future use and set to zero.
- Bit 1 LAPI (Low Access Priority Indication): This bit defines if the UE indicated low access priority when establishing the PDN connection. It shall be encoded as the Low Priority parameter of the Device Properties IE in 3GPP TS 24.008 [5]. The receiver shall assume the value "0" if the Signalling Priority Indication IE is applicable for a message but not included in that message by the sender. The low access priority indication may be included in charging records.

## 8.89 Temporary Mobile Group Identity (TMGI)

The TMGI contains the Temporary Mobile Group Identity allocated to the MBMS Bearer Service. The BM-SC always includes the MCC and MNC when allocating the TMGI, see 3GPP TS 29.061 [38].

It is coded as specified in Figure 8.89-1.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1		Type = 158 (decimal)										
2 to 3		Length = n										
4		Sp	are			Inst	ance					
5-10		TMGI										
11-(n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	citly spe	cified				

Figure 8.89-1: TMGI

Octets 5 to 10 shall be encoded as octets 3 to octet 8 in the figure 10.5.154 of 3GPP TS 24.008 [5].

## 8.90 Additional MM context for SRVCC

The additional MM Context for SRVCC information element contains mobile station classmarks, supported codec list that are necessary for the MME/S4-SGSN to perform SRVCC as defined in 3GPP TS 23.216 [43]. The coding of Mobile Station Classmarks and Supported Codec List fields include the IE value part as it is specified in 3GPP TS 24.008 [5].

				Bi	ts							
Octets	8	7	6	5	4	3	2	1				
1		Type = 159 (decimal)										
2 to 3		Length = n										
4		Spare Instance										
5		Length of the Mobile Station Classmark 2										
6 to a		Mobile Station Classmark 2										
b		Lengt	h of the	Mobile	Station	l Classr	nark 3					
(b+1) to c			Mobile	e Statior	n Classi	mark 3						
d		Length of the Supported Codec List										
(d+1) to e		Supported Codec List										
(e+1) to	Thes	These octet(s) is/are present only if explicitly specified										
(n+4)												

Figure 8.90-1: Additional MM context for SRVCC

For each of the Mobile Station Classmark 2, Mobile Station Classmark 3 and Supported Codec List parameters, if they are not available, then the associated length field shall be set to zero, and the particular parameter field shall not be present.

# 8.91 Additional flags for SRVCC

Additional flags for SRVCC is coded as depicted in Figure 8.91-1.

	Bits										
Octets	8	7	6	5	4	3	2	1			
1		Type = 160 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5	Spare VF ICS										
6-(n+4)	Thes	These octet(s) is/are present only if explicitly specified									

#### Figure 8.91-1: Additional flags for SRVCC

The following bits within Octet 5 indicate:

- Bit 1 ICS (IMS Centralized Service): This flag indicates that UE supports ICS specific service as specified in 3GPP TS 23.292 [47].
- Bit 2 VF (vSRVCC Flag): This flag indicates that the user is subscribed to the vSRVCC.

## 8.92 Void

## 8.93 MDT Configuration

MDT Configuration is coded as depicted in Figure 8.93-1.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1			Тур	oe = 16	2 (decin	nal)						
2 to 3				Leng	th = n							
4		Sp	are			Inst	ance					
5					Туре							
6 to 9		List of Measurements										
10		Reporting Trigger										
11		Report Interval										
12		Report Amount										
13		Event Threshold for RSRP										
14	Event Threshold for RSRQ											
15		Length of Area Scope										
a	Spa				lumber							
b			of LAI(				of RAI(	S)				
d	Spa			N	umber o							
e		Sp	are	001()		lumber	of TAI(	S)				
f to g					(1-32)							
h to i				· ·	) [1-8]							
k to l												
m to o				,	<u>) [1-32]</u>							
p to q		Spa	aro	TAI(S	) [1-8] PLI	PMI	MPI	CRR				
S		Spa	ale		FLI			MI				
u	(	Collectio	on peric	d for R	RM mea	asurem	ents LT	E				
v			Meas	suremer	nt Perio	d LTE						
w			Po	ositionir	ng Meth	od						
х				ber of I								
y to z				MDT PL	MN Lis	t						
r to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if explic	citly spe	cified				

#### Figure 8.93-1: MDT Configuration

Parameters in octets 5 to 14, p to q, u, v, w and y to z shall be encoded as specified in 3GPP TS 32.422 [18]. If Length of Area Scope equals zero, then Area Scope octets p to q shall not be present.

Octet 'a' to 'e' specifies which area scope information is present:

- Number of CGI (Cell Global Identifier), bit 1 to 6 of octet 'a' shall contain the number of CGI present in the CGI field. If Number of CGI is set to "0" octet 'f' to 'g' shall not be present.
- Bit 7 to 8 of octet 'a' are spare and reserved for future use.
- Number of RAI (Routing Area Identifier), bit 1 to 4 of octet 'b' shall contain the number of RAI present in the RAI field. If Number of RAI is set to "0" octet 'h' to 'i' shall not be present.
- Number of LAI (Location Area Identifier), bit 5 to 8 of octet 'b' shall contain the number of LAI present in the LAI field. If Number of LAI is set to "0" octet 'k' to 'l' shall not be present.
- Number of ECGI (E-UTRAN Cell Global Identifier), bit 1 to 6 of octet 'd' it shall contain the number of ECGI, present in the ECGI field. If Number of ECGI is set to "0" octet 'm' to 'o' shall not be present.
- Bit 7 to 8 of octet 'd' are spare and reserved for future use.
- Number of TAI (Tracking Area Identifier), bit 1 to 4 of octet 'e' it shall contain the number of TAI present in the TAI field. If Number of TAI is set to "0" octet 'p' to 'q' shall not be present.
- Bit 5 to 8 of octet 'e' are spare and reserved for future use.

The encoding of CGI field is specified in subclause 8.21.1.

The encoding of RAI field is specified in subclause 8.21.3.

The encoding of TAI field is specified in subclause 8.21.4.

The encoding of ECGI field is specified in subclause 8.21.5.

The encoding of LAI field is specified in subclause 8.21.6.

If CRRMI (Collection period for RRM measurements LTE Indicator), bit 1 of octet 's', is set to "1", then the Collection period for RRM measurements LTE parameter field shall be present, otherwise octet 'u' shall not be present.

If MPI (Measurement period LTE Indicator), bit 2 of octet 's', is set to "1", then the Measurement period LTE parameter field shall be present, otherwise octet 'v' shall not be present.

If PMI (Positioning Method Indicator), bit 3 of octet 's', is set to "1", then the Positioning Method parameter field shall be present, otherwise octet 'w' shall not be present.

If PLI (PLMN List Indicator), bit 4 of octet 's', is set to "1", then the Number of MDT PLMNs and MDT PLMN List parameters shall be present, otherwise octet 'x' and octets 'y to z' shall not be present.

The value of the Number of MDT PLMNs represents the number of 3-octet PLMNs contained within the MDT PLMN List parameter and shall be a number from 1 to 16. Each PLMN ID in the list shall be encoded as defined for octets 5 to 7 in subclause 8.18.

## 8.94 Additional Protocol Configuration Options (APCO)

The Additional Protocol Configuration Options (APCO) information element is used to exchange additional protocol configuration options between the TWAN/ePDG and the PGW.

The Additional Protocol Configuration Options information element is specified in 3GPP TS 29.275 [26] and its GTPv2 coding is shown in figure 8.94-1.

	Bits											
Octets	8	7	6	5	4	3	2	1				
1	Type = 163 (decimal)											
2 to 3	Length = n											
4		Sp	are		Instance							
5 to m	Additional Protocol Configuration Options (APCO)											
(m+1) to	These octet(s) is/are present only if explicitly specified											
(n+4)				-	-							

Figure 8.94-1: Additional Protocol Configuration Options

Octets (5 to m) of the Additional Protocol Configuration Options IE are encoded as specified in 3GPP TS 29.275 [26].

## 8.95 Absolute Time of MBMS Data Transfer

The Absolute Time of MBMS Data Transfer indicates the absolute time of the actual start, update or stop of the MBMS data transfer to ensure a synchronized session control and facilitate a graceful reallocation of resources for the MBSFN (MBMS Single Frequency Network) when needed for E-UTRAN access.

It is coded as shown in figure 8.95-1.




Figure 8.95-1: Absolute Time of MBMS Data Transfer

Octets 5 to 12 are coded as the time in seconds relative to 00:00:00 on 1 January 1900 (calculated as continuous time without leap seconds and traceable to a common time reference) where binary encoding of the integer part is in the 32 most significant bits and binary encoding of the fraction part in the 32 least significant bits. The fraction part is expressed with a granularity of  $1/2^{**}32$  second.

# 8.96 H(e)NB Information Reporting

H(e)NB number Information Reporting is coded as depicted in Figure 8.96-1.




Figure 8.96-1: H(e)NB Information Reporting

The following bits within Octet 5 shall indicate:

• Bit 1 – FTI: When set to "1", shall indicate to start reporting H(e)NB local IP address and UDP port number information change when the UE moves from (e)NB to H(e)NB, from H(e)NB to another H(e)NB with a fixed network backhaul change, or from H(e)NB to (e)NB.

The bit 1 shall be set to 0 to stop reporting H(e)NB local IP address and UDP port number information change.

# 8.97 IPv4 Configuration Parameters (IP4CP)

The IPv4 Configuration Parameters (IP4CP) is coded as depicted in Figure 8.97-1.




Figure 8. 97-1: IPv4 Configuration Parameters (IP4CP)

## 8.98 Change to Report Flags

Change to Report Flags IE is coded as depicted in Figure 8.98-1.

				В	its						
Octets	8	7	6	5	4	3	2	1			
1		Type = 167 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5		Spare TZCR SNCR									
6 to (n+4)	Thes	These octet(s) is/are present only if explicitly specified									

Figure 8.98-1: Change to Report Flags

For each message the applicable flags of the Change to Report Flags IE shall be clearly specified in the individual message sub clause. The remaining flags of the Change to Report Flags IE not so indicated shall be discarded by the receiver.

The receiver shall consider the value of the applicable flags as "0", if the Change to Report Flags IE is applicable for the message but not included in the message by the sender.

The following bits within Octet 5 shall indicate:

- Bit 8 to 3 Spare, for future use and set to zero.
- Bit 2 TZCR (Time Zone Change to Report): When set to 1, this bit indicates that a UE Time Zone change still needs to be reported to the SGW/PGW.

#### 3GPP TS 29.274 version 14.7.0 Release 14

334

- Bit 1 – SNCR (Serving Network Change to Report): When set to 1, this bit indicates that a Serving Network change still need to be reported to the SGW/PGW.

## 8.99 Action Indication

Action Indication is coded as depicted in Figure 8.99-1.




Figure 8.99-1: Action Indication

#### Table 8.99-1: Indication

Indication	Values (Decimal)
No Action	0
Deactivation Indication	1
Paging Indication	2
Paging Stop Indication	3
<spare></spare>	4 to7

If "deactivation indication" is set, it indicates that the receiving entity shall deactivate ISR and remove the UE resource locally as specified in 3GPP TS 23.007 [17] subclause 27.3.1.2.

If "paging indication" is set, it indicates that the receiving entity shall page the IDLE state UE as specified in 3GPP TS 23.007 [17] subclause 27.3.2.2.

If "paging stop indication" is set, it indicates that the receiving entity shall stop paging the UE as specified in 3GPP TS 23.380 [61] subclause 5.4.2.1 and subclause 5.4.3.2.

## 8.100 TWAN Identifier

The TWAN Identifier is used for reporting UE location in a Trusted WLAN Access Network (TWAN). See 3GPP TS 23.402 [45].

TWAN Identifier shall be coded as depicted in Figure 8.100-1.

					Bits							
Octets	8	7	6	5	4	3	2	1				
1			T	ype = 1	69 (deo	cimal)						
2 to 3				Ler	ngth = n	l						
4		Spa	are			ıl	nstance					
5		Spare		LAII	OPN	PLM	CIVAI	BSSIDI				
					AI	NI						
6				SSI	D Lengt	h						
7 to k		SSID										
(k+1) to		BSSID										
(k+6)												
q	Civic Address Length											
(q+1) to			Civi	c Addre	ess Info	rmatio	n					
(q+r)												
s to (s+3)				TWAN	I PLMN	-ID						
t			rwan	I Opera	tor Nar	ne Ler	ngth					
(t+1) to (t+u)			TV	VAN O	perator	Name						
v			F	Relay Io	dentity	Гуре						
(v+1)			R	elay Id	entity L	ength						
(v+2) to				Rela	y Identi	ty						
(v+w)												
Х		Circuit-ID Length										
(x+1) to				Cir	cuit-ID							
(x+y)												
p to (n+4)	Thes	se octet(	s) is/a	are pres	sent on	ly if ex	olicitly s	pecified				

Figure 8.100-1: TWAN Identifier

The BSSID and SSID shall be encoded as described in IEEE Std 802.11-2012 [52].

The TWAN identifier shall contain the SSID and, unless otherwise determined by the TWAN operator's policies, it shall contain at least the BSSID, the civic address of the access point to which the UE is attached or the Circuit-ID with the identity of the Relay (e.g. TWAG) which has allocated it (see subclause 16.1.7 of 3GPP TS 23.402 [45]). It may also contain the identifier of the TWAN operator, i.e. either the TWAN PLMN-ID if the TWAN is operated by a mobile operator or the TWAN Operator Name otherwise.

The SSID Length in octet '6' indicates the length of the SSID field. The SSID is an Octet String which shall have a maximum length of 32 octets (see IEEE Std 802.11-2012 [52]).

The BSSIDI flag in octet 5 indicates whether the BSSID in octets k+1 to k+6 shall be present. If BSSIDI is set to '1', then the BSSID shall be present. If BSSIDI is set to '0', then the BSSID shall not be present. The BSSID is an Octet String which shall be 6 octets long (see IEEE Std 802.11-2012 [52]).

The CIVAI flag in octet 5 indicates whether the Civic Address Length and Civic Address Information in octets 'q' and 'q+1' to 'q+r' shall be present. The Civic Address Length and Information shall be present if and only if the CIVAI flag is set to 1. When present, the Civic Address Information shall contain the civic address of the Access Point to which the UE is attached and it shall be encoded as defined in subclause 3.1 of IETF RFC 4776 [59] excluding the first 3 octets.

The PLMNI flag in octet 5 indicates whether the TWAN PLMN-ID in octets 's' to 's+3' shall be present. The TWAN PLMN-ID shall be present if and only if the PLMNI flag is set to 1. The TWAN PLMN-ID shall be encoded as octets 5 to 7 of the Serving Network IE in subclause 8.18. When present, the TWAN PLMN-ID shall indicate the PLMN-ID of the TWAN operator.

NOTE: the PLMN ID contained in the TWAN PLMN-ID can differ from the PLMN ID in the Serving Network IE.

The OPNAI flag in octet 5 indicates whether the TWAN Operator Name Length and TWAN Operator Name in octets 't' and 't+1' to 't+u' shall be present. The TWAN Operator Name Length and TWAN Operator Name shall be present if and only if the OPNAI flag is set to 1. The TWAN Operator Name shall be encoded as specified in subclause 19. 8 of 3GPP TS 23.003 [2]. When present, the TWAN Operator Name shall indicate the identifier of the TWAN operator.

The LAII flag in octet 5 indicates whether the Logical Access ID information is present in the TWAN Identifier IE. The Logical Access ID is encoded by the Relay Identity information in octets 'v' to 'v+w' and the Circuit-ID information in octets 'x' to 'x+y'. The Relay Identity information and the Circuit-ID information shall be present if the LAII flag is set to '1'. The Relay indicates a DHCP relay agent as defined in IETF RFC 3046 [60]. The Relay Identity Type indicates

the type of the Relay Identity as described in Table 8.100-1. The Relay Identity Length indicates the length of the Relay Identity. In case the Relay Identity Type indicates an IP address, the length indicates if it is IPv4 or IPv6 address of the Relay. The length is 4 octets for IPv4 and 16 octets for IPv6. If the Relay Identity type is set to 1 (i.e. an FQDN), it is encoded as described in section 3.1 of IETF RFC 1035 [31] but excluding the trailing zero byte. The Circuit-ID length indicates the length of the Circuit-ID. The Circuit-ID is as defined in IETF RFC 3046 [60], it is encoded as an Octetstring and provided by the Relay.

#### Table 8.100-1: Relay Identity Type

Relay Identity Type	Values (Decimal)
IPv4 or IPv6 Address	0
FQDN	1

## 8.101 ULI Timestamp

The ULI Timestamp IE is coded as shown in Figure 8.101-1. It indicates the UTC time when the user location information was acquired. Octets 5 to 8 are encoded in the same format as the first four octets of the 64-bit timestamp format as defined in section 6 of IETF RFC 5905 [53].

NOTE: The encoding is defined as the time in seconds relative to 00:00:00 on 1 January 1900.

				В	ts								
Octets	8	7	6	5	4	3	2	1					
1		Type = 170 (decimal)											
2 to 3		Length = n											
4		Sp	are			Inst	ance						
5-8		ULI Timestamp value											
9 to (n+4)	Thes	se octet	(s) is/ar	e prese	nt only	if explic	itly spe	cified					

Figure 8.101-1: ULI Timestamp

## 8.102 MBMS Flags

MBMS Flags is coded as depicted in Figure 8.102-1.

	Bits										
Octets	8	7	6	5	4	3	2	1			
1		Type = 171 (decimal)									
2 to 3		Length = n									
4		Sp	are			Inst	ance				
5	Spare LMRI MSRI							MSRI			
6 to (n+4)	Thes	These octet(s) is/are present only if explicitly specified									

Figure 8.102-1: MBMS Flags

The following bits within Octet 5 indicate:

- Bit 1 MSRI (MBMS Session Re-establishment Indication): if set to 1, this flag indicates that the MBMS Session Start Request message is used to re-establish an MBMS session (see 3GPP TS 23.007 [13])
- Bit 2 LMRI (Local MBMS Bearer Context Release Indication): if set to 1, this flag indicates that the MBMS Session Stop Request message is used to release the MBMS Bearer Context locally in the MME/SGSN (see 3GPP TS 23.007 [13]);
- Bit 3 to 8 Spare, for future use and set to zero.

## 8.103 RAN/NAS Cause

RAN/NAS Cause is coded as depicted in Figure 8.103-1.

				В	its									
Octets	8	7	6	5	4	3	2	1						
1		Type = 172 (decimal)												
2 to 3		Length = n												
4		Spare Instance												
5		Protoc	ol Type			Cause	э Туре							
6 to m	Cause Value													
(m+1) to (n+4)	Thes	These octet(s) is/are present only if explicitly specified												

Figure 8.103-1: RAN/NAS Cause

The Protocol Type field shall be encoded as per Table 8.103 -0:

Table 8.103-0: Protocol Type values

Protocol Type	Values (Decimal)
S1AP Cause	1
EMM Cause	2
ESM Cause	3
Diameter Cause	4
IKEv2 Cause	5
<spare></spare>	6-15

All spare bits shall be set to zeros by the sender and ignored by the receiver.

The Cause Value field shall be coded as follows:

For S1-AP Cause, the Cause Value field shall contain a non-transparent copy of the cause value of the corresponding IE (see subclause 8.2.2), "Cause", as defined in clause 9.2.1.3 in 3GPP TS 36.413 [10]. The Cause Type field shall contain the RAN Cause subcategory as specified in 3GPP TS 36.413 [10] and it shall be encoded as in Table 8.103-1. The value of the Cause Value field (and the associated RAN cause subcategory) is transferred over the S1-AP interface and encoded into one octet as binary integer.

Cause Type	Values (Decimal)
Radio Network Layer	0
Transport Layer	1
NAS	2
Protocol	3
Miscellaneous	4
<spare></spare>	5 to15

Table 8.103-1: Cause Type values and their meanings

- For EMM and ESM Causes, the Cause Value field shall contain the cause value as specified respectively for the "EMM Cause" IE and "ESM Cause" IE in subclauses 9.9.3.9 and 9.9.4.4 of 3GPP TS 24.301 [23], or for the "Cause" IE in subclause 8.11 of 3GPP TS 24.244 [66].

The value of the Cause Value field (which has a range of 0..255) shall be transferred encoded into one octet as binary integer.

The Cause Type field shall be ignored by the receiver.

- For Diameter Cause, the Cause Value field shall contain the cause value as specified for the Diameter Termination-Cause AVP in IETF RFC 3588 [39]. The Cause Value field shall be encoded into 2 octets as binary integer of the Termination-Cause AVP value. The currently assigned values for the Termination-Cause AVP can be found in the IANA registry for Termination-Cause AVP Values, IANA, "Termination-Cause AVP Values (code 295)", http://www.iana.org/assignments/aaa-parameters/aaa-parameters.xhtml#aaa-parameters-16. The Cause Type field shall be ignored by the receiver.
- For IKEv2 Cause, the Cause Value field shall contain the cause value as specified for the Internet Key Exchange Version 2 (IKEv2) Parameters, Notify message error type, in IETF RFC 7296 [67]. The Cause Value field shall be encoded into 2 octets as binary integer of the IKEv2 notify message error type value.

The currently assigned values for the IKEv2 notify message error type can be found in the IANA registry for "Internet Key Exchange Version 2 (IKEv2) Parameters", <u>http://www.iana.org/assignments/ikev2-parameters/ikev2-parameters.xhtml#ikev2-parameters-14</u> The Cause Type field shall be ignored by the receiver.

## 8.104 CN Operator Selection Entity

CN Operator Selection Entity is coded as depicted in Figure 8.104-1.




Figure 8.104-1: CN Operator Selection Entity

Selection mode value	Value (Decimal)
The Serving Network has been selected by the UE	0
The Serving Network has been selected by the network	1
For future use. Shall not be sent. If received, shall be interpreted as the value "1".	2, 3

#### Table 8.104-1: Selection Entity values

## 8.105 Trusted WLAN Mode Indication

The purpose of the Trusted WLAN Mode Indication information element is to convey the selected trusted WLAN Mode.

The content and encoding of the Trusted WLAN Mode Indication is depicted on Figure 8.105-1.




Figure 8.105-1: Trusted WLAN Mode Indication

The following bits within Octet 5 shall indicate:

- Bit 8 to 3 Spare, for future use and set to zero.
- Bit 2 MCM (Multiple-connection mode Indication): if this bit is set to 1, it indicates that the Multiple-connection mode is used.
- Bit 1 SCM (Single-connection mode Indication): if this bit is set to 1, it indicates that the Single-connection mode is used.

## 8.106 Node Number

Node Number shall be coded as depicted in Figure 8.106-1.




Figure 8.106-1: Node Number

The Node number shall carry an ISDN number.

If the Node Number carries the SGSN Number, then the SGSN number shall be coded according to the contents of ISDN-AddressString data type defined in 3GPP TS 29.002 [41]. The SGSN Number shall be in international format and the "nature of address indicator" shall indicate "international number". The SGSN Number is defined in 3GPP TS 23.003 [2]. The Length of Node Number shall not be zero.

If the Node Number carries the MME number for MT SMS, then it shall be coded according to the contents of ISDN-AddressString data type defined in 3GPP TS 29.002 [41]. The MME number for MT SMS shall be in international format and the "nature of address indicator" shall indicate "international number". The MME number for MT SMS is defined in 3GPP TS 23.003 [2]. The Length of Node Number shall not be zero.

## 8.107 Node Identifier

Node Identifier shall be coded as depicted in Figure 8.107-1.

				В	its			
Octets	8	7	6	5	4	3	2	1
1			Ту	oe = 17	6 (decin	nal)		
2 to 3				Leng	th = n			
4		Sp	are			Inst	ance	
5		Length of Node Name						
6 to p		Node Name						
(p+1)			Len	igth of N	lode Re	ealm		
(p+2) to q		Node Realm						
(q+1) to	Thes	se octet	(s) is/ar	e prese	nt only	if explic	citly spe	cified
(n+4)								

Figure 8.107-1: Node Identifier

The Node Identifier shall contain the Diameter Identity of the node.

If the Node Identifier contains a SGSN Identifier then:

- the Node Name shall be coded as the Diameter identity of the SGSN as defined in subclause 6.4.13 of 3GPP TS 29.173 [57] and;
- the Node Realm shall be coded as the Diameter realm identity of the SGSN and as defined in subclause 6.4.14 of 3GPP TS 29.173 [57] and;
- Both the Node Name and the Node Realm shall be present and neither the Length of Node Name nor the Length of Node Realm shall be zero.

If the Node Identifier contains a MME Identifier then:

- the Node Name shall be coded as the Diameter identity of the MME as defined in subclause 6.4.4 of 3GPP TS 29.173 [57] and;
- the Node Realm shall be coded as the Diameter realm identity of the MME as defined in subclause 6.4.12 of 3GPP TS 29.173 [57] and;
- Both the Node Name and the Node Realm shall be present and neither the Length of Node Name nor the Length of Node Realm shall be zero.

If the Node Identifer contains a 3GPP AAA Server Identifier then:

- the Node Name shall be coded as the 3GPP-AAA-Server-Name as defined in subclause 8.2.3.24 of 3GPP TS 29.273 [68] and;
- the Node Realm shall be coded as the Diameter realm of the 3GPP AAA server in the format of a Diameter identity as defined in IETF RFC 3588 [39].

If the Node Identifier contains an SCEF information, then:

- the Node Name shall be coded as the SCEF-ID as defined in subclause 8.4.5 of 3GPP TS 29.336 [69] and;
- the Node Realm shall be coded as the Diameter realm of the SCEF as defined in subclause 8.4.y of TS 29.272 [70].

## 8.108 Presence Reporting Area Action

Presence Reporting Area Action is coded as depicted in Figure 8.108-1.

				Bi	ts			
Octets	8	7	6	5	4	3	2	1
1				Туре	= 177			
2 to 3		Length = n						
4		Sp	are			Insta	ance	
5	Spare			INAP		Action		
				RA				
6 to 8					ing Area			
9		Numbe	r of TA		1	Numbe	r of RA	
10	Spa	are		Numb	per of Ma	acro eN	lodeB	
11	Spa	are		Numb	per of Ho	ome eN	lodeB	
12	Spa	are		Number of ECGI				
13	Spa	are		Number of SAI				
14	Spa	are		Number of CGI				
15 to k				TAIs [115]				
(k+1) to m		Macro eNB IDs [163]						
(m+1) to p		Home eNB IDs [163]						
(p+1) to q		ECGIs [163]						
(q+1) to r		RAIs [115]						
(r+1) to s	SAIs [163]							
(s+1) to t		CGIs [163]						
t+1	Spa	are	Number of Extended Macro eNodeB					
(t+2) to v		E	xtende	d Macro	eNB ID	s [16	3]	
u to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only i	f explic	itly spe	cified

Figure 8.108-1: Pre	esence Report	ing Area	Action
---------------------	---------------	----------	--------

Table 0 100 1. Action values

Table 8.108-1: Action values						
Action	Value (Decimal)					
Start Reporting changes of UE presence in the PRA	1					
Stop Reporting changes of UE presence in the PRA	2					
Modify Presence Reporting Area elements composing the PRA	3					
<spare></spare>	0, 4-7					

The Action value 1 (Start Reporting change) shall be used to request to start reporting changes of UE presence in the Presence Reporting Area identified by the Presence Reporting Area Identifier and, if present, the Presence Reporting Area elements composing the Presence Reporting Area.

The Action value 2 (Stop Reporting change) shall be used to request to stop reporting changes of UE presence in a Presence Reporting Area.

The Action value 3 (Modify Presence Reporting Area elements composing the PRA) shall be used to request to modify the Presence Reporting Area elements composing the PRA and to continue reporting changes of UE presence in that Presence Report Area.

The Inactive PRA (INAPRA) flag in the Octet 5 shall be set to 1 on the S10/S16/S3 interface if the PRA is inactive in the source MME/SGSN during an inter MME/SGSN mobility procedure, i.e. the reporting change of UE presence in this Presence Reporting Area was requested by the PGW/PCRF/OCS but it was deactivated by the source MME/SGSN, e.g. due to an overload situation.

The Presence Reporting Area Identifier shall be present if the Action value requests to start, stop or modify reporting changes of UE presence in a Presence Reporting Area. If so, the Presence Reporting Area Identifier shall contain an identifier of the Presence Reporting Area and be encoded using full hexadecimal representation(binary, not ASCII encoding). The Presence Reporting Area Identifier is defined in subclause 19.10 of 3GPP TS 23.003 [2].

Octets 9 to 14 shall be present if the Action value requests to start reporting change of UE presence in a Presence Reporting Area and the Presence Reporting Area is not pre-configured in the MME/SGSN, or the Action value requests to modify the Presence Reporting Area elements composing a Presence Reporting Area not pre-configured in the MME/SGSN. If so, these octets shall indicate the number of TAI (15 at most), Macro eNodeB ID (63 at most), Home eNodeB ID (63 at most), ECGI (63 at most), RAI (15 at most), SAI (63 at most) and CGI (63 at most) which compose the PRA.

TAIs in octets 15 to 'k', if any, shall be encoded as per the TAI field in subclause 8.21.4. Octets 15 to 'k' shall be absent if the field 'Number of TAI' is set to the value '0'.

Macro eNB IDs in octets 'k+1' to 'm', if any, shall be encoded as per octets 6 to 11 of the Target ID for type Macro eNodeB in figure 8.51-2. Octets 'k+1' to 'm' shall be absent if the field 'Number of Macro eNodeB' is set to the value '0'.

Home eNB IDs in octets 'm+1' to 'p', if any, shall be encoded as per octets 6 to 12 of the Target ID for type Home eNodeB in figure 8.51-3. Octets 'm+1' to 'p' shall be absent if the field 'Number of Home eNodeB' is set to the value '0'.

ECGIs in octets 'p+1' to 'q', if any, shall be encoded as per the ECGI field in subclause 8.21.5. Octets 'p+1' to 'q' shall be absent if the field 'Number of ECGI' is set to the value '0'.

RAIs in octets 'q+1' to 'r', if any, shall be encoded as per the RAI field in subclause 8.21.3. Octets 'q+1' to 'r' shall be absent if the field 'Number of RAI' is set to the value '0'.

SAIs in octets r+1' to s', if any, shall be encoded as per the SAI field in subclause 8.21.2. Octets r+1' to s' shall be absent if the field 'Number of SAI' is set to the value '0'.

CGIs in octets 's+1' to 't', if any, shall be encoded as per the CGI field in subclause 8.21.1. Octets 's+1' to 't' shall be absent if the field 'Number of CGI' is set to the value '0'.

Extended Macro eNB IDs in octets 't+2' to 'v', if any, shall be encoded as per octets 6 to 11 of the Target ID for type Extended Macro eNodeB in figure 8.51-x. Octets 't+2' to 'v' shall be absent if the field 'Number of Extended Macro eNodeB' is set to the value '0'.

## 8.109 Presence Reporting Area Information

Presence Reporting Area Information is coded as depicted in Figure 8.109-1.




Figure 8.109-1: Presence Reporting Area Information

The PRA Identifier in octets 5 to 7 shall be present and shall contain the identifier of the PRA the UE is entering or leaving. It shall be encoded using full hexadecimal representation (binary, not ASCII encoding). The PRA Identifier is defined in subclause 19.10 of 3GPP TS 23.003 [2].

The PRA Identifier in the Octets 5 to 7 shall be set to the PRA Set ID if the MME/SGSN is requested to report the change of UE presence in a PRA Set. In this case:

- the Additional PRA (APRA) flag in octet 8 shall be set to 1 if the reporting of change of UE presence for the PRA Set is active and the UE presence has changed for at least one PRA within the PRA Set (i.e. if the UE enters or leaves the PRA Set, or the UE moves between the PRAs within the PRA Set). The subsequent 4 octets shall then be present and shall contain the identifier of the individual PRA within the PRA Set which the UE has newly entered or left, with the information of whether the UE is inside or outside this PRA.
- the Additional PRA (APRA) flag in octet a+3 shall be set to 1 if the UE presence status has changed for more than one individual PRA within the PRA Set. In that case, the subsequent 4 Octets shall be included and encoded as specified above for the octets a to a+3. The MME/SGSN shall report each individual PRA(s) within the PRA Set that the UE has newly entered or left.
- if the reporting of change of UE presence for the PRA Set is inactive, i.e. the INAPRA flag in octet 8 is set to 1, then the Additional PRA (APRA) flag in octet 8 shall not be set to 1 and no Additional PRA Identifier shall be included.

The Inside PRA flag (IPRA) shall be set to 1 if the UE is inside or enters the Presence Reporting Area identified by the PRA Identifier.

The Outside PRA flag (OPRA) shall be set to 1 if the UE is outside or leaves the Presence Reporting Area identified by the PRA Identifier.

The Inactive PRA (INAPRA) flag in octet 8 shall be set to 1 if the PRA is inactive in the MME/SGSN, i.e. the reporting of change of UE presence in this PRA is currently deactivated in the MME/SGSN, e.g. due to an overload situation.

Either the IPRA or the OPRA flag or the INAPRA shall be set to 1, not several ones, for a given Presence Reporting Area Identifier.

## 8.110 TWAN Identifier Timestamp

The TWAN Identifier Timestamp IE is coded as shown in Figure 8.110-1. It indicates the UTC time when the TWAN Identifier information was acquired. Octets 5 to 8 shall be encoded in the same format as the first four octets of the 64bit timestamp format as defined in section 6 of IETF RFC 5905 [53].

NOTE: The encoding is defined as the time in seconds relative to 00:00:00 on 1 January 1900.




Figure 8.1 ⁴	10-1: TWAN	Identifier	Timestamp
-------------------------	------------	------------	-----------

## 8.111 Overload Control Information

Overload Control Information is a grouped IE containing a number of other IEs. Which of those IEs are mandatory, optional or conditional and the conditions that apply are GTP message specific, and described in the corresponding subclause under clause 7.

Overload Control Information may be repeated within a message with exactly the same Type and Instance values to represent a list of Overload Control Information.

Overload Control Information is coded as depicted in Table 8.111-1.

Octet 1		Overload Control Information IE Type = 180 (decimal)					
Octets 2 and 3		Length = n					
Octet 4		Spare and Instance fields					
Information elements P Condition / Comment		ІЕ Туре	Ins.				
NOTE: This table uses a 5-column format in order to match the format used in subclauses of clause 7, where the usage of this IE is further detailed for each specific GTP message including it.							

## 8.112 Load Control Information

Load Control Information is a grouped IE containing a number of other IEs. Which of those IEs are mandatory, optional or conditional and the conditions that apply are GTP message specific, and described in the corresponding subclause under clause 7.

Load Control Information may be repeated within a message with exactly the same Type and Instance values to represent a list of Load Control Information.

Load Control Information is coded as depicted in Table 8.112-1.

Octet 1			Load Control Information IE Type = 181 (decimal)				
Octets 2 a	nd 3		Length = n				
Octet 4			Spare and Instance fields				
Informatio	on elements	Ρ	Condition / Comment	IE Type	Ins.		
NOTE: This table uses a 5-column format in order to match the format used in subclauses of clause 7, where							
the usage of this IE is further detailed for each specific GTP message including it.							

### 8.113 Metric

The Metric IE is coded as shown in Figure 8.113-1. It indicates a percentage and may take binary coded integer values from and including 0 up to and including 100. Other values shall be considered as 0.




Figure 8.113-1: Metric

## 8.114 Sequence Number

The Sequence Number IE is coded as shown in Figure 8.114-1 and it contains Unsigned32 binary integer value.

				В	its			
Octets	8	7	6	5	4	3	2	1
1	Type = 183 (decimal)							
2 to 3	Length = 4							
4		Sp	are			Inst	ance	
5 to 8	Sequence Number							

Figure 8.114-1: Sequence Number

## 8.115 APN and Relative Capacity

The APN and Relative Capacity IE is coded as shown in Figure 8.115-1.

	Bits							
Octets	8	7	6	5	4	3	2	1
1	Type = 184 (decimal)							
2 to 3	Length = n							
4	Spare Instance							
5	Relative Capacity							
6	APN Length							
7 to m	Access Point Name (APN)							
(m+1) to	These octet(s) is/are present only if explicitly specified							
(n+4)					-		-	

Figure 8.115-1: APN and Relative Capacity

The Relative Capacity represents the resources configured for the given APN as compared to the total resources of the target PGW, in percentage. It shall take binary coded integer values from 1 up to 100. Other values shall be considered as 0.

The APN Length in octet '6' indicates the length of the APN field.

The APN field, from octet 7 to 'm' shall be encoded as octet 5 to (n+4)' defined in clause 8.6.

## 8.116 WLAN Offloadability Indication

WLAN Offloadability Indication IE is coded as depicted in Figure 8.116-1.




Figure 8.116-1: WLAN Offloadability Indication

Octet 5 indicates if WLAN Offload has been authorized for the UE:

- Bit 8 to 3 Spare, for future use and set to zero.
- Bit 2 reflects the information available at the UE regarding E-UTRAN Offloadability. When set to '1', this indicates that the UE has been authorized to perform WLAN offload from E-UTRAN. When set to '0', this indicates that the UE has not been authorized to perform WLAN offload from E-UTRAN.
- Bit 1 reflects the information available at the UE regarding UTRAN Offloadability. When set to '1', this indicates that the UE has been authorized to perform WLAN offload from UTRAN. When set to '0', this indicates that the UE has not been authorized to perform WLAN offload from UTRAN.

## 8.117 Paging and Service Information

The Paging and Service Information IE is used to carry per bearer paging and service information. It is coded as shown in Figure 8.117-1.




Figure 8.117-1: Paging and Service Information

The EBI value, in octet 5, indicates the EPS Bearer ID for which the Paging and Service Information is provided. The EBI field shall be encoded as the EBI field in the EPS Bearer ID (EBI) IE type (see subclause 8.8).

The PPI flag in octet 6 indicates whether the Paging Policy Indication value in octet 'm' shall be present. If PPI is set to '1', then the Paging Policy Indication value shall be present. If PPI is set to '0', then octet 'm' shall not be present.

The Paging Policy Indication value, in octet 'm', shall be encoded as the DSCP in TOS (IPv4) or TC (IPv6) information received in the IP payload of the GTP-U packet from the PGW (see IETF RFC 2474 [65]).

### 8.118 Integer Number

Integer Number is coded as depicted in Figure 8.118-1.




Figure 8.118-1: Integer Number

The Integer Number value is encoded with the number of octets defined in the Length field, e.g. when n=2, the range of the integer number value is from 0 to 65535.

The Integer Number value shall be encoded as further described below for the following information elements:

- Maximum Wait Time IE: the length shall be set to 2, i.e. the integer number value shall be encoded as a 16 bit unsigned integer.
- DL Buffering Suggested Packet Count IE: the length shall be set to 1 or 2;
- UE Usage Type IE: the length shall be set to 1, i.e. the integer number value shall be encoded as a 8 bit unsigned integer as specified in subclause 7.3.202 of 3GPP TS 29.272 [70].

### 8.119 Millisecond Time Stamp

The Millisecond Time Stamp IE is coded as shown in Figure 8.119-1. Octets 5 to 10 represent a 48 bit unsigned integer in network order format and are encoded as the number of milliseconds since 00:00:00 January 1, 1900 00:00 UTC, i.e. as the rounded value of 1000 x the value of the 64-bit timestamp (Seconds + (Fraction / (1<<32))) defined in section 6 of IETF RFC 5905 [53].




Figure 8.119-1: Millisecond Time Stamp

### 8.120 Monitoring Event Information

The Monitoring Event Information contains the monitoring event parameters that are necessary to transfer over the S3/S16/S10 interface.

The Monitoring Event Information is coded as depicted in Figure 8.120-1.

	Bits								
Octets	8	7	6	5	4	3	2	1	
1			Ту	oe = 189	9 (decin	nal)			
2 to 3				Leng	th = n				
4	Spare Instance								
5 to 8	SCEF Reference ID								
9			ç	SCEF II	D Lengt	h			
10 to k				SCE	FID				
(k+1) to	Remaining Number of Reports								
(k+2)									
(k+3) to	These octet(s) is/are present only if explicitly specified								
(n+4)									

Figure 8.120-1: Monitoring Event Information

The SCEF Reference ID, the SCEF ID shall be encoded as specified in subclause 8.4.4 and 8.4.5 of 3GPP TS 29.336 [69].


The SCEF ID Length indicates the length of the SCEF ID in octets.

The Remaining Number of Reports indicates the number of reports which are outstanding to be sent to the SCEF. It shall be encoded as specified in subclause 8.4.8 of 3GPP TS 29.336 [69],

## 8.121 ECGI List

MBMS Cell List is an extendable IE that is coded as depicted in Figure 8.120-1. The ECGI identity types are defined in 3GPP TS 23.003 [2].

		Bits							
Octets	8	7	6	5	4	3	2	1	
1	Type = 190 (decimal)								
2 to 3	Length = n								
4	Spare Instance								
5 to 6	Number of ECGI Fields = m								
7 to (m*7+6)	ECGI List of m ECGI Fields								
(m*7+7) to (n+4)	Thes	e octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified	



The Number of ECGI Fields shall indicate the number of ECGI fields in the ECGI List.

In the present version of this specification, the Length n shall be set to m times 7 plus 2.

The ECGI List shall consist of m ECGI fields. Each ECGI field shall be encoded as specified in subclause 8.21.5 and thus is 7 octets long.

# 8.122 Remote UE Context

Remote UE Context is a grouped IE containing a number of other IEs. Which of those IEs are mandatory, optional or conditional and the conditions that apply are GTP message specific, and described in the corresponding subclause under clause 7.

Remote UE Context may be repeated within a message with exactly the same Type and Instance values to represent a list of Remote UE Context.

Remote UE Context is coded as depicted in Table 8.122-1.

Octet 1			Bearer Context IE Type = 191 (decimal)							
Octets 2 a	nd 3		Length = n							
Octet 4			Spare and Instance fields							
Information elements		Ρ	Condition / Comment	IE Type	Ins.					
NOTE: This table uses a 5-column format in order to match the format used in subclauses of clause 7, where										
the usage of this IF is further detailed for each specific GTP message including it										

Table 8.122-1: Remote UE	Context	Grouped	Туре
--------------------------	---------	---------	------

## 8.123 Remote User ID

Remote User ID is transferred via GTP tunnels and is coded as depicted in Figure 8.123-1. The Remote User ID IE shall contain one IMSI identity and, if available, one IMEI identity and/or one MSISDN identity. The flag MSISDNF in octet 5 indicates if the MSISDN shall be present in the respective field. The flag IMEIF in octet 5 indicates if the IMEI shall be present in the respective field. The IMSI field including the Length of IMSI shall be always present.

	Bits									
Octets	8	7	6	5	4	3	2	1		
1			Ту	pe = 19	2 (decin	nal)				
2 to 3				Leng	th = n					
4		Sp	are			Inst	tance			
5			Sp	are			IMEIF	MSIS		
	DNF							DNF		
6		Length of IMSI								
7 to a				IN	ISI					
b			Le	ength of	f MSISE	N				
b+1 to c				MSI	SDN					
d	Length of IMEI									
d+1 to e	IMEI									
(e+1) to (n+4)	Thes	e octet	(s) is/ar	e prese	nt only	if expli	citly spe	cified		

Figure 8.123-1: Remote User ID

The coding of IMSI field, from octets 7 to 'a' shall be encoded as the octets 5 to n+4 of the IMSI IE type specified in subclause 8.3.

The coding of MSISDN field, octets 'b+1' to 'c' shall be encoded as the octets 5 to n+4 of the MSISDN IE type specified in subclause 8.11.

The coding of IMEI field, octets 'd+1' to 'e' shall be encoded as the octets 5 to n+4 of the MEI IE type specified in subclause 8.10.

## 8.124 Remote UE IP Information

Remote UE IP Information is transferred via GTP tunnels and is coded as depicted in Figure 8.124-1. Remote UE IP information field, octets 5 to n+4 shall be encoded as the octets from 'j' to 'j+k' of the Remote UE Context IE specified in subclause 9.9.4.20 of 3GPP TS 24.301 [23].




Figure 8.124-1: Remote UE IP Information

# 8.125 CIoT Optimizations Support Indication

CIoT Optimizations Support Indication is coded as depicted in Figure 8.125-1 below.

	Bits									
Octets	8	7	6	5	4	3	2	1		
1	Type = 194 (decimal)									
2 to 3	Length = n									
4		Sp	are		Instance					
5	Spare	Spare	Spare	Spare	IHCSI	AWO	SCNI	SGNI		
	•	•	•	•		PDN	PDN			
6 to (n+4)	These octet(s) is/are present only if explicitly specified									

Figure 8.125-1: CloT Optimizations Support Indication

Octet 5 carries the feature support bits for each of the CIoT optimization as follows:

- Bit 8 to Bit 5: Spare, for future use and set to 0.

- Bit 4 IHCSI (IP Header Compression Support Indication): Indicates the support of IP header compression based on ROHC framework (see IETF RFC 4995 [77]) for Control Plane CIoT EPS optimisations, when set to '1'.
- Bit 3 AWOPDN (Attach without PDN Support Indication): Indicates the support of Attach without PDN connection as specified in section 4.3.5.10 of 3GPP TS 23.401 [3], when set to '1'. Here the word "PDN connection" implies both the PDN connection through SGW and PGW and the PDN connection through SCEF.
- Bit 2 SCNIPDN (SCEF Non IP PDN Support Indication): Indicates the support of SCEF Non IP PDN Connection as specified in section 5.13.1 of 3GPP TS 23.682 [74], when set to '1'.
- Bit 1 SGNIPDN (SGi Non IP PDN Support Indication): Indicates the support of SGi Non IP PDN Connection as specified in section 4.3.17.8.3.3 of 3GPP TS 23.401 [3] and 3GPP TS 23.060 [35], when set to '1'.

## 8.126 SCEF PDN Connection

The SCEF PDN connection is a grouped IE containing a number of other IEs and shall be coded as depicted in Table 8.126-1.

The SCEF PDN Connection IE may be repeated within a message when more than one SCEF PDN Connection is required to be sent. If so, the repeated IEs shall have exactly the same Instance values to represent a list of grouped IEs.

Octet 1			PDN Connection IE Type = 195 (decimal)									
Octets 2 and	d 3		Length = n									
Octet 4		Spare and Instance fields										
Information elements		Ρ	Condition / Comment	ІЕ Туре	Ins.							
NOTE: This table uses a 5-column format in order to match the format used in subclauses of clause 7, where the usage of this IE is further detailed for each specific GTP message including it.												

#### Table 8.126-1: PDN Connection Grouped Type

## 8.127 Header Compression Configuration

The Header Compression Configuration includes the information necessary for the ROHC channel setup.

The Header Compression Configuration shall be encoded as specified in Figure 8.127-1.

		Bits								
Octets	8	7	6	5	4	3	2	1		
1	Type = 196 (decimal)									
2 to 3	Length = n									
4	Spare Instance									
5 to 6	ROHC Profiles									
7 to 8	MAX_CID									
9 to (n+4)	Thes	se octet	(s) is/ar	e prese	ent only	if explic	itly spe	cified		


Figure 8.127-1: Header Compression Configuration

					,			1.0)		
	ROHC Profiles (octets 5 and 6) Bits									
36 pa us on Co	The ROHC Profiles shall indicate which of the ROHC profiles specified in 3GPP TS 36.323 [76] are allowed to be used (i.e. have been negotiated) with the UE. When a particular bit is set to 1, this indicates that the corresponding profile is allowed to be used. The No Compression profile 0x000 shall also be considered as allowed if at least one bit is set to 1. When all the bits are set to 0, this indicates that only the No Compression profile 0x000 is allowed to be used. Octet 5									
8	7	6	5	4	3	2	1	Profile Identifier	Usage	
0 0 0 0 0 0 0 1	0 0 0 0 0 1 0	0 0 0 0 1 0	0 1 0	0 0 1 0 0 0	0 0	0 1 0 0 0 0 0	0 0	0x0002 0x0003 0x0004 0x0006 0x0102 0x0103 0x0104	UDP/IP ESP/IP IP TCP/IP UDP/IP ESP/IP IP Spare	
00	ctet	6								
8	7	6	5	4	3	2	1	Profile Identifier	Usage	
0 0 0 0 0 0 1	0 0 0 0 0 1 0	0	0 0 1	0 0 1 0 0 0	1 0 0	0 0 0			Spare Spare Spare Spare Spare Spare Spare Spare	
M	MAX_CID (octet 7 to 8)									
(i.e	This is the maximum CID value specified in 3GPP TS 36.323 [76] allowed to be used (i.e. which has been negotiated) with the UE. This shall be encoded as a 2 byte integer with a value in the range from 1 to 16383.									

Table 8.127-1: Header	Compression	Configuration
-----------------------	-------------	---------------

# 8.128 Extended Protocol Configuration Options (ePCO)

Protocol Configuration Options (PCO) is transferred via GTP tunnels. The sending entity copies the value part of the ePCO into the value field of the Extended Protocol Configuration Options IE. The detailed coding and maximum length of the Extended Protocol Configuration Options field from octets 5 to (n+4) shall be specified as per clause 9.9.4.x of 3GPP TS 24.008 [5], starting with octet 4.



# 8.129 Serving PLMN Rate Control

Serving PLMN Rate Control may be configured in the Serving PLMN network, to protect serving network, e.g. the MME and the Signalling Radio Bearers in the E-UTRAN, from the load generated by NAS Data PDUs. It defines the maximum number of the NAS Data PDUs which can be transferred by the Serving Network per 6 minute interval.

The maximum number of the NAS Data PDUs which can be transferred for both downlink and uplink shall be configured to a value greater than 10. When the value is set to 0, it shall indicate Serving PLMN Rate Control is not applicable to the PDN Connection for the given direction.

The Serving PLMN Rate Control shall only apply to the PDN Connection(s) which is set to Control Plane Only.

Serving PLMN Rate Control Information is coded as depicted in Figure 8.129-1.

	Bits							
Octets	8	7	6	5	4	3	2	1
1	Type = 198 (decimal)							
2 to 3	Length = n							
4	Spare			Instance				
5 to 6	Uplink Rate Limit							
7 to 8	Downlink Rate Limit							
9 to (n-4)	These octet(s) is/are present only if explicitly specified							
	Figuro	8 1 20.	1. 50	wina P		2 ato C	ontrol	

Figure 8.129-1: Serving PLMN Rate Control

## 8.130 Counter

Counter IE is coded as depicted in Figure 8.130-1.




Figure 8.130-1: Counter

Octets 5 to 8 shall be encoded in the same format as the first four octets of the 64-bit timestamp format as defined in section 6 of IETF RFC 5905 [53].

NOTE: The encoding is defined as the time in seconds relative to 00:00:00 on 1 January 1900.

Octet 9 represents an integer with a length of 1 octet.

# 8.131 Mapped UE Usage Type

Mapped UE Usage Type shall be coded as depicted in Figure 8.131-1. Mapped UE Usage Type is defined in subclause 5.8.1 of 3GPP TS 29.003 [32].

	Bits							
Octets	8	7	6	5	4	3	2	1
1	Type = 200 (decimal)							
2 to 3	Length = n							
4	Spare			Instance				
5 to 6	Mapped UE Usage Type							
7 to (n+4)	These octet(s) is/are present only if explicitly specified							

Figure 8.131-1: Mapped UE Usage Type

The Mapped UE Usage Type shall be encoded as a two octets binary integer.

# 9 Security

GTPv2-C communications shall be protected according to security mechanisms defined in 3GPP TS 33.401 [12].

# 10 IP - The Networking Technology used by GTP

# 10.1 IP Version

GTPv2 entities shall support both versions of the Internet Protocol, version 4 (IPv4) as defined by IETF RFC 791 [6], and version 6 (IPv6) as defined by IETF RFC 2460 [16].

# 10.2 IP Fragmentation

It is specified here how the fragmentation mechanism shall work with GTP-C.

Fragmentation should be avoided if possible. Examples of fragmentation drawbacks are:

- Fragmentation is inefficient, since the complete IP header is duplicated in each fragment.
- If one fragment is lost, the complete packet has to be discarded. The reason is that no selective retransmission of fragments is possible.

Path MTU discovery should be used, especially if GTPv2-C message is encapsulated with IPv6 header. The application should find out the path MTU, and thereby utilise more efficient fragmentation mechanisms.

# 11 Notification of supported features between peer GTP-C entities

## 11.1 General

### 11.1.1 Introduction

New functionality, i.e. functionality beyond the Rel-9 standard, which can not be specified without backward incompatible changes (e.g. requiring support of a new message or a specific receiver node's behaviour) should be introduced as a feature, see subclause 11.1.2.

A GTP-C entity should verify that a backward incompatible feature is supported by its peer GTP entities before starting to use it.

NOTE: GTPv2 does not support a Comprehension Required mechanism allowing a sender to force the receiver to support comprehension of some specific IEs as a precondition to process a backward incompatible message.

Features may be generic node capabilities supported homogeneously for all GTP tunnels, UEs and PDN connections. Such features are referred in this specification as "Node Features". They are signalled with the granularity of a node on all GTPv2 interfaces (i.e. S11, S4, S5, S8, S10, S3, S16, Sv, S101, S121, Sm, Sn, S2a, S2b). A GTP-C entity may discover the features supported by a peer GTP-C entity with which it is in direct contact as specified in subclause 11.2.1.

### 11.1.2 Defining a feature

A feature is a function extending the base GTPv2 functionality that has a significant meaning to the operation of GTPv2, i.e. a single new parameter without a substantial meaning to the functionality of the GTPv2 endpoints should not be defined to be a new feature.

A functionality requiring the definition of a new GTPv2 message or extending the use of an existing message over a new interface should be defined as a feature.

NOTE: Features are ultimately defined on a case-by-case basis on the merits of defining an extension as a feature.

Features should be defined so that they are independent from each other. A GTP-C entity may support the same feature over different interfaces, e.g. an SGW may support a feature over both S11 and S4 interface, however support of a feature on a given interface shall not depend on the support of the same or another feature on another interface.

## 11.2 Dynamic discovery of supported features

#### 11.2.1 General

A node supporting at least one feature defined in the Node Features IE shall support dynamic discovery of supported features as specified in the following subclauses.

#### 11.2.2 Features supported by direct peer GTP-C entities

A node shall signal to a direct peer node the list of features it supports by sending the Sending Node Features IE in every Echo Request and Echo Response messages to that node.

An exception to this is where the sending node does not support or use any features towards the peer node and is not prepared to accept a message which is constructed by making use of any features.

The peer receiving the Sending Node Features IE shall store the list of features supported by the sending node per IP address and only update this list based on the Sending Node Features IE in the Echo Request and Echo Response messages, and it shall only use common supported features to initiate subsequent GTPv2 messages towards this IP address. Receipt of an Echo Request or an Echo Response message without the Sending Node Features IE shall indicate that the sending node does not support any feature specified in Table 8.83-1 on the corresponding interface.

# 12 GTP-C load & overload control mechanism

### 12.1 General

#### 12.1.1 GTP-C overload problem

GTP-C entities can communicate with other GTP-C peers in direct contact (e.g. MME and SGW) or remote GTP-C peers through intermediate GTP-C entities (e.g. MME and PGW via the SGW). In normal conditions, requests sent by a GTP-C entity can be processed by the receiving GTP-C entity which can send back a message indicating the result of the request (success/failure).

Overload situations in a GTP-C entity occur when the number of incoming requests exceeds the maximum request throughput supported by the receiving GTP-C entity, e.g. when the internal available resources of the GTP-C entity, such as processing power or memory, are not sufficient to serve the number of incoming requests. As a consequence of the overload situation, the receiving GTP-C entity cannot successfully process the exceeding proportion of requests. These requests can be either simply dropped or extremely delayed in the processing. At best, the GTP-C entity may have enough internal resources to send back to the request initiator a message indicating that the requests cannot be successfully processed. Whatever the behaviour of the overloaded GTP-C entities, the rate of successfully processed requests and consequently the overall performances of the network decrease.

NOTE: GTP-C overload control does not target to address transport network congestion. It assumes a transport network that is still capable to exchange signalling traffic.

Given the nature of GTP-C protocol in how it relies on retransmissions of unacknowledged requests (GTP-C is carried over UDP transport), when a GTP-C entity experiences overload (or severe overload) the number of unacknowledged GTP-C messages compounds exponentially and can lead to a node congestion or even collapse. An overload or failure of a node can lead to an increase of the load on the other nodes in the network and, in the worst case, turn into a complete network issue via a snowball effect.

The impact of GTP-C overload to services can be such as:

- loss of PDN connectivity (IMS, Internet ...) and associated services;
- loss of ability to setup and release radio and core network bearers necessary to support services e.g. GBR bearers for VoLTE or dedicated bearers for Voice over WLAN;
- loss of ability to report to the PGW/PCRF user's information changes, e.g. location information for emergency services and lawful intercept, changes in RAT or QoS;
- and billing errors and a loss of revenue.

#### 12.1.2 Scenarios leading to overload

Reasons for these temporary overload cases can be many and various in an operational network, such as insufficient internal resource capacity of a GTP-C entity faced with a sudden burst of requests, e.g. after network failure/restart procedures affecting a large number of users, deficiency of a GTP-C entity component leading to a drastic reduction of the overall performances of the GTP-C entity.

Examples of GTP-C signalling based scenarios which can cause GTP-C overload are:

- a traffic flood resulting from the failure of a network element, inducing a signalling spike, e.g. when the network needs to re-establish the PDN connections affected by the failure of an EPC node;
- a traffic flood resulting from a large number of users performing TAU/RAU or from frequent transitions between idle and connected mode;
- an exceptional event locally generating a traffic spike, e.g. a large amount of calls (and dedicated bearers) being setup almost simultaneously upon a catastrophic event or an exceptional but predictable event (e.g. Christmas, New year) via a 3GPP access or a WLAN access;
- Frequent RAT-reselection due to scattered non-3GPP (e.g. WiFi) coverage or massive mobility between 3GPP and non-3GPP coverage may potentially cause frequent or massive intersystem change activities, i.e. UEs trying to either create PDN connections over the new access or moving PDN connections between 3GPP and non-3GPP coverage.

Besides, GTP-C load balancing based only on semi-static DNS weights can lead to a load imbalance and thus GTP-C signalling scenarios, such as those mentioned above, may result in an overload of the SGWs or PGWs with the highest load while there is still remaining capacity on other SGWs or PGWs.

#### 12.1.3 Load & overload control concepts

Load control refers to "GTP-C signalling based Load Control" as defined in subclause 4.3.7.1a.1 of 3GPP TS 23.401 [3] and subclause 5.3.6.1a of 3GPP TS 23.060 [35].

Overload control refers to "GTP-C signaling based Overload Control" as defined in subclause 4.3.7.1a.2 of 3GPP TS 23.401 [3] and subclause 5.3.6.1a of 3GPP TS 23.060 [35].

Load control and overload control are two distinct but complementary concepts:

load control enables a GTP-C entity (e.g. an SGW/PGW) to send its load information to a GTP-C peer (e.g. an MME/SGSN, ePDG, TWAN) to adaptively balance the session load across entities supporting the same function (e.g. an SGW cluster) according to their effective load. The load information reflects the operating status of the resources of the GTP-C entity.

- overload control enables a GTP-C entity becoming or being overloaded to gracefully reduce its incoming signalling load by instructing its GTP-C peers to reduce sending traffic according to its available signalling capacity to successfully process the traffic. A GTP-C entity is in overload when it operates over its signalling capacity which results in diminished performance (including impacts to handling of incoming and outgoing traffic).

Load control allows for better balancing of the session load, so as to attempt to prevent overload in the first place (preventive action). Overload control aims at shedding the incoming traffic as close to the traffic source as possible generally when an overload has occurred (reactive action), so to avoid spreading the problem inside the network and to avoid using resources of intermediate nodes in the network for signalling that would anyhow be discarded by the overloaded node.

Load control does not trigger overload mitigation actions even if the GTP-C entity reports a high load.

Load control and overload control may be supported and activated independently in the network.

### 12.2 Load control solution

#### 12.2.1 Principles of load control

The stage 2 requirements on GTP-C load control solution are defined in clause 4.3.7.1a.1 of 3GPP TS 23.401 [3] and clause 5.3.6.1a of 3GPP TS 23.060 [35]. The high level principles are summarized below:

- a) Load Control is an optional feature;
- b) a GTP-C node may signal its Load Control Information to reflect the operating status of its resources, allowing the receiving GTP-C peer node to use this information to augment the existing GW selection procedures;
- c) the calculation of the Load Control Information is implementation dependent and its calculation and transfer shall not add significant additional load to the node itself and to its corresponding peer nodes;
- d) the Load Control Information may provide load information of a GTP-C node (e.g. a PGW) or, if the APN level load control feature is supported, may provide the load information about specific APN(s);
- e) the SGW may send its Load Control Information to the MME/S4-SGSN. The PGW may send its Load Control Information to the MME/S4-SGSN via the SGW. For non-3GPP access based interfaces, the PGW may send its Load Control Information to the ePDG and TWAN;
- f) the Load Control Information shall be piggybacked in GTP-C request or response messages such that the exchange of Load Control Information does not trigger extra signalling;
- NOTE: The inclusion of Load Control Information in existing messages means that the frequency of transmission of load control information increases as the session load increases, allowing for faster feedback and thus better regulation of the load.
- g) a node supporting Load Control sends Load Control Information to a peer GTP-C node based on local configuration (see clause 12.2.6);
- h) the format of the Load Control Information shall be specified with enough precision to guarantee a common interpretation of this information allowing interoperability between nodes of different vendors;
- i) for the inter-PLMN case, local configuration may restrict the exchange and use of Load Control Information across PLMNs;
- j) the GTP-C node may decide to send different values of Load Control Information on inter-network (roaming) and on intra-network (non-roaming) interfaces based on local configuration, i.e. the values sent on intra-network interfaces may differ from the values sent on inter-network interfaces. However, on intra-network interfaces, the node should send the same values between the 3GPP and non-3GPP access based interfaces.
- k) the Load Control Information received via GTP-C signalling shall be used in conjunction with the information received from the DNS, during the node selection procedure. Refer to 3GPP TS 29.303 [32] for further details.

### 12.2.2 Applicability to 3GPP and non-3GPP access based interfaces

Load Control may be supported on the 3GPP & non-3GPP access based interfaces and nodes as summarized by the Table 12.2.2-1.

Originator	Consumer	Applicable Interfaces				
PGW	MME	S5/S8, S11				
		SGW relays Load Control Information from S5/S8 to S11 interface.				
PGW	S4-SGSN	S5/S8, S4				
		SGW relays Load Control Information from S5/S8 to S4 interface.				
SGW	MME	S11				
SGW	S4-SGSN	S4				
PGW	ePDG	S2b				
PGW	TWAN	S2a				

Table 12.2.2-1: Applicability of Load Control to GTP-C interfaces and nodes

NOTE: Refer to Annex D.1 for information on the GTP-C interfaces for which Load Control is not supported.

#### 12.2.3 Node level load control

Node level load control refers to advertising of the load information at node level -i.e. load information at node level granularity - and selection of the target node based on this information. It helps to achieve an evenly load balanced network by the use of the dynamic load information provided within the Load Control Information.

### 12.2.4 APN level load control

#### 12.2.4.1 General

APN level load control refers to advertising of the load information at APN level granularity and selection of the target node based on this information. It helps to achieve an evenly load balanced network at APN granularity by the use of the dynamic load information provided within the Load Control Information with the APN scope. Only a PGW may advertise APN level load information.

APN level load control is an optional feature that may be supported when the following pre-condition is applicable.

#### **Pre-Condition:**

In the given network, when the ratio of the configured APN resource to the overall capacity of the PGW is not the same across all the PGWs in the network.

NOTE: In other cases, e.g. when all the resources of the PGW are available for all the APNs served by that PGW, the node level load information is exactly the same as APN level load information, for each of its APNs, and hence performing node load control is sufficient.

If APN load control is supported and activated at the PGW, the PGW should advertise the APN load information. If the APN level load control feature is supported at the node performing the PGW selection, i.e. an MME, S4-SGSN, ePDG, TWAN, the node shall utilize this information when selecting the PGW.

#### 12.2.4.2 Justifications for APN load control support

Following are the justifications to support the APN level load control in the network when the pre-condition specified in 12.2.3.1 is applicable:

1) To achieve load balancing at the APN level granularity: The PGW may be configured to handle more than one APN in the network. In such a case, the PGW may be additionally configured to allocate different resources for each of the configured APNs, e.g. the PGW may be configured to handle "X" number of sessions for the "consumer" APN and to handle "Y" number of session for the "corporate" APN. The ratio of this limit, i.e. "X" and "Y", to the PGW's capacity may not be the same across all the PGWs in the network. In this case, the load information with node level granularity is not sufficient and could result in a network where one PGW has more

sessions for the "consumer" APN while another PGW has more sessions for the "corporate" APN. Thus, an evenly load balanced network at APN level load granularity cannot be realized.

- 2) To ensure effective overload control in the network: If the distribution of sessions at APN level is uneven, then there is a higher risk of overload of some PGWs, as compared to other PGWs, e.g. the PGW handling more sessions for "consumer" APN may have to handle more messages, (e.g. generated due to mobility events resulting from a change of ULI, RAT type, Serving GW, etc.) as compared to the PGW handling more sessions for the "stationary-machine" APN. Hence, the PGW handling "consumer" APN sessions may be at higher risk of overload, as compared to the other PGWs in the network, and hence, this situation may result in poor overload control of the network.
- **3)** To ensure an efficient node selection algorithm: Based on the node level load information, the source node, (e.g. the MME) may end-up selecting the PGW for a new session for the given APN. However, the selected PGW may reject the new session request, if it is running at 100% load capacity for the given APN, or the new session request may be throttled by the source node based on the overload information of the APN for the given PGW. Thus the new session request may be denied, (i.e. rejected by the selected PGW or throttled by the source node based on PGW's APN level overload information) while the other PGW may have the capacity to handle the same. Thus, the lack of APN level load information may result in inefficient node selection algorithm by the source node.

#### 12.2.4.3 Elements of APN load control

To allow for an effective APN load control, at least the following information (in addition to the other applicable information for load control as defined in clause 12.2.5.1.2) is required to be advertised by the PGW, as part of the APN level load information:

APN: The APN for which the PGW wants to advertise the load information.

**APN-Load-Metric**: It indicates the current resource utilization for a particular APN, as a percentage, compared to the total resources reserved for that APN at the target PGW. Its computation is implementation dependent and it has same characteristics as "Load-Metric", as described in clause 12.2.5.1.2.2, when applied at the APN level.

**APN-relative-capacity**: It indicates the total resources configured for a given APN, compared to the total resources of the target PGW, as a percentage. It is a static parameter and does not change unless the resources configured for the APN change. Using APN-relative-capacity and the DNS weight-factor of the given PGW, the source node can judge the PGW's APN related resources as compared other PGWs in the network, i.e. the PGW's APN-weight-factor can be calculated by multiplying the APN-relative-capacity and DNS-weight-factor of the PGW (PGW's-APN-weight-factor = PGW's-APN-relative-capacity X DNS-weight-factor).

For the following example configuration:

PGW1-APN1-relative-capacity = 50%; PGW2-APN1- relative-capacity = 20%; PGW3-APN1- relative-capacity = 10%

PGW1-weight-factor = 20; PGW2-weight-factor = 20; PGW3-weight-factor = 60;

The APN level weight-factor for each of the PGWs can be calculated as below:

PGW1-APN1-weight-factor = 50% X 20 = 10.

PGW2-APN1-weight-factor = 20% X 20 = 4.

PGW3-APN1-weight-factor =  $10\% \times 60 = 6$ .

Thus, based on the APN-weight-factor it can be concluded that the PGW1 has highest APN1 related resources reserved, as compared to the other PGWs in the network. Hence the source node should use this information to favour PGW1 over other PGWs for APN1 related new session requests.

## 12.2.5 Load Control Information

#### 12.2.5.1 Definition

#### 12.2.5.1.1 General description

Within a message, one or multiple instances of the Load Control Information (LCI) IE may be included by the same GTP-C entity.

When providing load control information in a message for the first time or subsequently, the GTP-C entity shall always include the full set of load control information, i.e. all the node level and APN Level applicable instances of the Load Control Information, even if only a subset of the load control information has changed. All the instances of the LCI IE provided by a given GTP-C entity in a message shall contain the same Load-Control-Sequence-Number. The Load Control Sequence Number shall be incremented whenever the load control information is changed (see subclause 12.2.5.1.2.1).

The receiver shall overwrite any stored load control information of a peer with the newly received load control information (via one or multiple instances) from the same peer node if the new load control information is more recent than the old information as indicated by the Load Control Sequence Number, e.g. if the receiver has stored 'X' instances of the load control information for a peer node, it overwrites those 'X' instances with the new set of 'Y' instances received in a message from the same peer node, where X, Y are any integer number.

The receiver shall consider all the parameters received in the same instance of the LCI IE in conjunction while using this information for node selection. When more than one instance of the LCI IE is received, the receiver shall consider the parameters included in each instance independently, when using this information for node selection.

The parameters are further defined in subclauses 12.2.5.1.2 and 12.2.5.1.3.

Load control information may be extended with new parameters in future versions of the specification. Any new parameter will have to be categorized as:

- Non-critical optional parameters: the support of these parameters is *not critical* for the receiver. The receiver can successfully and correctly comprehend the load control information instance, containing one or more of these parameters, by using the other parameters and ignoring the non-critical optional parameter.
- Critical optional parameters: the support of these parameters is *critical* for the receiver to correctly comprehend the instance of the load control information containing one or more of these parameters.

The sender may include one or more non-critical optional parameters within any instance of the LCI IE without having the knowledge of the receiver's capability to support the same. However, the sender shall only include one or more critical optional parameter in any instance of the LCI IE towards a receiver if the corresponding receiver is known to support those parameters. The sender may be aware of this either via signalling methods or by configuration; (this will have to be defined when introducing any such new parameter in future).

Each instance of the LCI IE shall be associated to the node identity (FQDN or IP address of the GW node received from the HSS or the DNS) of the serving SGW or PGW, i.e. the identity determined during the SGW or PGW selection.

NOTE: The Node type is derived based on the instance number of the LCI IE.

#### 12.2.5.1.2 Parameters

#### 12.2.5.1.2.1 Load Control Sequence Number

The Load Control Sequence number contains a value that indicates the sequence number associated with the LCI IE. This sequence number shall be used to differentiate any two LCI IEs generated at two different instances by the same GTP-C entity. The Load Control Sequence Number shall be supported (if load control is supported) and shall always be present in the LCI IE.

The GTP-C entity generating this information shall increment the Load Control Sequence Number whenever modifying some information in the Load Control Information IE. The Load Control Sequence Number shall not be incremented otherwise. The node may use the time, represented in an unsigned integer format, of the generation of the Load Control Information to populate the Load Control Sequence Number.

When multiple instances of the LCI IE are provided in a message by a given GTP-C node, each of them shall contain the same Load Control Sequence Number value.

This parameter shall be used by the receiver of the Load Control Information IE to properly collate out-of-order load control information, e.g. due to GTP-C retransmissions. This parameter shall also be used by the receiver of the LCI IE to determine whether the newly received load control information has changed compared to load control information previously received from the same node earlier.

NOTE: The GTP-C sequence number cannot be used for collating out-of-order load control information as e.g. load control information may be sent in both GTP-C requests and responses, using independent GTP-C sequence numbering.

If the receiving entity has already received and stored load control information from the peer GTP-C entity, the receiving entity shall update its load control information only if the Load Control Sequence Number received in the new load control information is higher than the stored value of the Load Control Sequence Number associated with the peer GTP-C entity. However due to roll-over of the Load Control Sequence Number or restart of the node, the Load Control Sequence Number may be reset to an appropriate base value by the peer GTP-C entity, hence the receiving entity shall be prepared to receive (and process) a Load Control Sequence Number parameter whose value is less than the previous value.

#### 12.2.5.1.2.2 Load Metric

The Load Metric parameter shall indicate the current load level of the originating node. The computation of the Load Metric is left to implementation. The node may consider various aspects, such as: the used capacity of the node based on activated bearers in relationship to maximum number of bearers the node can handle, the load that these active bearers produce in the node (e.g. memory/CPU usage in relationship to the total memory/CPU available, etc.).

The Load Metric represents the current load level of the sending node as a percentage within the range of 0 to100, where 0 means no or 0% load and 100 means maximum or 100% load reached (i.e. no further load is desirable).

The Load Metric shall be supported (if load control is supported). The Load Metric shall always be included in the Load Control Information.

Considering the processing requirement of the receiver of the Load Control Information (e.g. handling of the new information, tuning the node selection algorithm to take the new information into account), the sender should refrain from advertising every small variation (e.g. with the granularity of 1 or 2), in the Load Metric which does not result in useful improvement in node selection logic at the receiver. During the typical operating condition of the sender, a larger variation in the Load Metric, e.g. 5 or more units, should be considered as reasonable enough for advertising the new Load Control Information and thus justifying the processing requirement (to handle the new information) of the receiver.

NOTE: The range of the Load Metric, i.e. 0 to 100, does not mandate the sender to collect its own load information at every increment/decrement and hence to advertise the change of Load Metric with a granularity of 1%. Based on various implementation specific criteria, such as: the architecture, session and signalling capacity, the current load and so on, the sender is free to define its own logic and periodicity with which its own load information is collected.

#### 12.2.5.1.2.3 List-of-APN_and_Relative Capacity

The List-of-APN_and_Relative Capacity parameter contains a list of the tuple (APN, Relative Capacity) and this indicates one or more APNs for which the Load Control Information is applicable. The "APN" contains the name of the APN and the Relative Capacity indicates the resources configured for a given APN, compared to the total resources configured at the target PGW, as a percentage.

When present in the LCI IE, the scope of the load information shall be the list of indicated APNs for the PGW that sends the load control information. In that case, the "Load Metric" shall be interpreted as an "APN-Load-Metric" and shall indicate the current resource utilization for the indicated APNs, as a percentage, as compared to the total resources configured for the indicated APNs at the target PGW.

Its computation is implementation dependent and it has the same characteristics as "Load Metric". Only one instance of the List-Of-APN_and_Relative Capacity IE may be included within one Load Control Information instance.

NOTE 1: The maximum number of tuples (APN, Relative Capacity) in the List-of-APN_and_Relative Capacity IE is set to 10. More than 10 occurrences of (APN, Relative Capacity), within one single instance of the List-of-APN_and_Relative Capacity IE is treated as protocol error by the receiver.

If the List-of-APN_and_Relative Capacity IE has not been included, the scope of the Load Control Information shall be the entire PGW node (unless restricted by other parameters in the LCI IE).

This parameter may be supported (if load control is supported) and shall be supported when APN level load control is supported.

The receiver shall handle this parameter, when it is received, if it supports APN level load control. The receiver shall ignore a Load Control Information instance applicable for an APN, if it does not support APN level load control.

NOTE 2: The PGW encodes the APN level load information and node level load information using different instance numbers in the message, so that the receiver will ignore the APN level load information, if it does not support the APN level load control feature.

The maximum number of APNs, for which the PGW may advertise the Load Control Information, shall be limited to 10, i.e. the maximum number of occurrences of the tuple (APN, Relative Capacity) within and across various instances of the LCI IE shall be limited to 10, for a given PGW. Hence, if the PGW supports more than 10 APNs, it shall advertise the load control information for at most 10 of the most important APNs. In future, if needed, this limit may be increased to allow the PGW to advertise the load information for more APNs. In that case, the receiver not supporting the higher limit shall handle the first 10 APNs and shall ignore the load information for the remaining APNs.

NOTE 3: The limit of the number of APN's takes into account various aspects such as: the processing and storage requirements at the overloaded node and the receiver, the number of important APNs for which load control advertisement will be necessary and interoperability between the nodes.

When including load control information for some APN(s), the PGW shall also provide node level load control information by providing one instance of the Load Control Information without the List-of-APN_and_Relative Capacity parameter.

A node selecting a PGW for a given APN shall apply the APN level load information, if available for that APN. If this parameter is not received for a given APN but it has been received for other APN(s) from the same PGW, then for this given APN, the node performing PGW selection shall calculate the load metric, as described in 3GPP TS 29.303 [32], for the target PGW.

### 12.2.5.1.3 Handling of parameters

If the PLMN supports the Load Control feature (see subclause 12.2.6), the support, inclusion and handling of the parameters, within Load Control Information, is summarized in table 12.2.5.1.3-1.

Parameter	Support by the sender	Support by the receiver	Inclusion by the sender	Handling by the receiver
Load Control sequence number (as defined in clause 12.2.5.1.2.1)	Mandatory	Mandatory	Mandatory	Mandatory
Load Metric (as defined in clause 12.2.5.1.2.2)	Mandatory	Mandatory	Mandatory	Mandatory
List-of- APN_and_Relative Capacity (as defined in clause 12.2.5.1.2.3)	Optional (NOTE 1)	Optional (NOTE 1)	Optional (NOTE 2)	Conditional (NOTE 3)
NOTE 1: This is an option NOTE 2: The PGW shall	I send this parameter whature is supported and e er is received, the received	nilst providing APN leve nabled.	l load control information	n, if the APN level

Table 12.2.5.1.3-1: Parameters of the Load Control Information

## 12.2.5.2 Frequency of inclusion

How often the sender includes the load control information is implementation specific. The sender shall ensure that new/updated load control information is propagated to the target receivers within an acceptable delay, such that the purpose of the information (i.e. effective load balancing) is achieved. The sender may include the LCI IE e.g. as follows:

- the sender may include Load Control Information towards a peer only when the new/changed value has not already been provided to that peer;
- the sender may include the Load Control Information in each and every message (extended with LCI IE) towards the peer;
- the sender may include Load Control Information periodically, i.e. include the information during a first period then cease to do so during a second period.

The sender may also implement a combination of one or more of the above approaches. Besides, the sender may also decide to include the Load Control Information only in a subset of the applicable GTP-C messages.

The receiver shall be prepared to receive the load control information in any of the GTP-C messages extended with an LCI IE and upon such reception, shall be able act upon the received load control information.

### 12.2.5.3 Limit on maximum number of instances

A GTP-C entity may signal one or multiple instances of the LCI IE, with each providing load control information for a different scope. In order to limit the processing of the message on the receiver side and the size of the message on transport level, the number of load control information instances shall be limited:

- at message level: there shall be at most one instance of node level LCI IE per node (i.e. per SGW or PGW) and at most 10 APN level instances.
- at node level: the maximum number of instances of LCI IE which may be provided across multiple messages by a given node shall be the same as the maximum number of instances of LCI IE at message level.

## 12.2.6 Discovery of the support of the feature by the peer node

A GTP-C entity shall determine whether to use the load control feature (i.e. provide or handle load control information)

- within the PLMN, based on the operator's policy (local PLMN-wide configuration);
- across the PLMN boundaries, based on the operator's policy (local configuration per PLMN).
- NOTE: The feature may be activated when all or some of the nodes in the PLMN support the feature. The GTP-C entity assumes that all of the peer nodes support this feature when the feature is activated, i.e. it does not need to determine which peers support the feature.

The above operator policy/local configuration may allow the use of load control at node level, load control at node level and APN level, or none.

## 12.2.7 Issues in the network with partial support of the feature

The Load Control feature should be supported homogenously across all the SGWs and PGWs in the network. Not supporting this feature homogeneously across the SGWs and PGWs may result in poor load balancing in the network such that the SGWs or PGWs not supporting the feature may operate near their maximum capacity (thus being more vulnerable to overload conditions) while SGWs or PGWs supporting the feature have free capacity.

The Load Control feature should be supported homogenously across all the MMEs, S4-SGSNs, ePDGs and TWANs. However, use of the feature when not all of these nodes support the feature may not necessarily create a problem since the load may remain fairly balanced across the SGWs and PGWs assuming that the network imbalance caused by the non-supporting node may get rectified by the supporting nodes making use of dynamic load information while selecting the SGWs and PGWs.

## 12.3 Overload control solution

## 12.3.1 Principles of overload control

The stage 2 requirements on GTP-C overload control are defined in clause 4.3.7.1a.2 of 3GPP TS 23.401 [3] and clause 5.3.6.1a of 3GPP TS 23.060 [35]. The high level principles are summarized below:

- a) Overload control is an optional feature;
- b) a GTP-C entity may signal its overload to its GTP-C peers by including Overload Control Information in GTP-C signalling which provides guidance to the receiving GTP-C entity to decide actions which lead to signalling traffic mitigation towards the sender of the information;
- c) the Overload Control Information may provide the overload information of a GTP-C entity, e.g. a PGW, or a specific APN(s) associated with the GTP-C entity;
- d) an MME/S4-SGSN may signal an overload to the PGW, via the SGW. An SGW may signal an overload to the MME/S4-SGSN and to the PGW. A PGW may signal an overload to the MME/S4-SGSN, via the SGW. For non-3GPP access based interfaces, a PGW may signal an overload to the ePDG and the TWAN; the ePDG and the TWAN may signal an overload to the PGW.
- NOTE 1: An MME/S4-SGSN will not signal an overload to the SGW (i.e. the SGW will not perform overload control towards the MME/S4-SGSN), as this is redundant with DDN throttling (see subclause 12.3.3).
- e) the overload control feature should continue to allow for preferential treatment of priority users (eMPS) and emergency services;
- f) the Overload Control Information is piggybacked in GTP control plane request or response messages such that the exchange of the Overload Control Information does not trigger extra signalling;
- NOTE 2: The inclusion of Overload Control Information in existing messages means that the frequency increases as the signalling load increases, thus allowing faster feedback and better regulation.
- g) the computation and transfer of the Overload Control Information shall not add significant additional load to the GTP-C entity itself and to its corresponding peer GTP-C entities. The calculation of Overload Control Information should not severely impact the resource utilization of the GTP-C entity, especially considering the overload situation;
- h) clause 4.3.7.1a.2 of 3GPP TS 23.401 [3] and clause 4.5 of 3GPP TS 23.402 [45] provides examples of various potential overload mitigation actions based on the reception of the overload related information exchanged between GTP-C entities, for 3GPP access based interfaces and non-3GPP access based interfaces, respectively. However, the exact internal processing logics of a GTP-C entity will not be standardized;
- i) for the inter-PLMN case, local configuration may restrict the exchange and use of Overload Control Information across PLMNs;
- j) the GTP-C entity may decide to send different values of Overload Control Information on inter-network (roaming) and on intra-network (non-roaming) interfaces based on local configuration, i.e. the values sent on intra-network interfaces may differ from the values sent on inter-network interfaces. However, on intra-network interfaces, the GTP-C entity should send the same values between the 3GPP and non-3GPP access based interfaces;

## 12.3.2 Applicability to 3GPP and non-3GPP access based interfaces

The Overload Control feature may be supported on the 3GPP & non-3GPP access based interfaces and nodes as summarized by the Table 12.3.2-1.

Originator	Consumer	Applicable Interfaces	
MME	PGW	S11, S5/S8	
		SGW relays Overload Control Information from S11 to S5/S8	
		interface.	
S4-SGSN	PGW	S4, S5/S8	
		SGW relays Overload Control Information from S4 to S5/S8	
		interface.	
SGW	MME	S11	
SGW	S4-SGSN	S4	
SGW	PGW	S5/S8	
		(in MME/S4-SGSN originated signalling towards the PGW)	
PGW	MME	S5/S8, S11	
		SGW relays Overload Control Information from S5/S8 to S11	
		interface.	
PGW	S4-SGSN	S5/S8, S4	
		SGW relays Overload Control Information from S5/S8 to S4	
		interface.	
PGW	TWAN	S2a (Trusted WLAN access)	
PGW	ePDG	S2b (Untrusted WLAN access)	
TWAN	PGW	S2a (Trusted WLAN access)	
ePDG	PGW	S2b (Untrusted WLAN access)	

# Table 12.3.2-1: Applicability of overload control to 3GPP & non-3GPP access based GTP-C interfaces and nodes

NOTE: Refer to Annex D.2 for information on the GTP-C interfaces for which Overload Control is not supported.

## 12.3.3 Node level overload control

Node level overload control refers to advertising of the overload information at node level, i.e. overload information at node level granularity, and applying the mitigation policies towards the target node based on this information. This helps in preventing severe overload and hence potential breakdown of the GTP-C node.

When a GTP-C entity determines that the offered incoming signalling traffic is growing (or is about to grow) beyond its nominal capacity, it may signal an Overload Control Information IE to instruct its GTP-C peers to reduce the offered load accordingly.

Overload Control is performed independently for each direction between two GTP-C entities. Overload Control may run concurrently, but independently, for each direction between the two GTP-C entities.

Overload control of SGW originated traffic towards the MME/S4-SGSN shall rely on Downlink Data Notification throttling, as specified in subclause 4.3.7.4.1a of 3GPP TS 23.401 [3] and 5.3.6.5 of 3GPP TS 23.060 [35], with the addition that the SGWs should be allowed, by configuration, to throttle DDN requests for low priority, as well as normal priority traffic (the SGW shall then throttle by priority DDN requests for low priority traffic).

## 12.3.4 APN level overload control

## 12.3.4.1 General

APN level overload control refers to advertising of the overload information at APN level granularity and hence applying the mitigation policies based on this information to the signalling traffic related to this APN only. Only a PGW may advertise APN level overload information when it detects overload for certain APNs, e.g. based on shortage of internal or external resources for an APN (e.g. IP address pool).

NOTE: When all the internal and external resources, applicable to the APNs, are available for all the APNs served by a PGW, the node level overload information is exactly the same as APN level overload information of that PGW, for each of its APNs, and hence, performing node overload control can be sufficient.

## 12.3.4.2 Elements of APN overload control

For allowing the effective APN overload control, at least the following information (in addition to the other applicable information for overload control as defined in clause 12.3.5.1.2) are required to be advertised by the source node, as part of the APN level overload information:

APN: The APN for which the source node wants to advertise the overload information;

**APN-Overload-Reduction-Metric**: It indicates the requested overload reduction for the signalling traffic corresponding to a particular APN, as a percentage. Its computation is implementation dependent and it has the same characteristics as the "Overload-Reduction-Metric", described in clause12.3.5.1.2.1, when applied at APN level.

## 12.3.5 Overload Control Information

## 12.3.5.1 Definition

## 12.3.5.1.1 General description

Within a message, one or multiple instances of the Overload Control Information (OCI) IE may be included by the same GTP-C entity. Each instance shall provide information about the overload condition to allow the receiver to apply mitigation actions which will result in an efficient alleviation of the overload condition at the sender.

The GTP-C entity shall always include the full set of overload control information, i.e. all the node level and APN level applicable instances of the OCI IE, when signalling overload control information in a message for the first time or subsequently towards the receiver, even when only a subset of the overload control information has changed. All the instances of the OCI IE provided by a given GTP-C entity in a message shall contain the same Overload Control Sequence Number. The Overload Control Sequence Number shall be incremented whenever the overload control information is modified (see subclause 12.3.5.1.2.1).

When including overload control information for some APN(s), the PGW should not provide any node level Overload Control Information unless the node level information is also applicable.

The receiver shall overwrite any stored overload control information of a peer with the newly received overload control information (received via one or multiple instances of OCI IE) from the same GTP-C peer entity, if the new information is more recent than the old information as indicated by the Overload Control Sequence Number, e.g. if the receiver has stored 'X' instances of the OCI IE for a peer GTP-C entity, it shall overwrite those 'X' instances with the new set of 'Y' instances received in a message from the same GTP-C peer entity, where X, Y are any integer numbers.

The receiver shall consider all the parameters received in the same instance of the OCI IE in conjunction while applying the overload mitigation action. When more than one instance of the OCI IE is included, the receiver shall consider the parameters included in each instance independently, while applying the overload mitigation action.

The parameters are further described in subclauses 12.3.5.1.2 and 12.3.5.1.3.

Overload control information may be extended with new parameters in future versions of the specification. Any new parameter will have to be categorized as:

- Non-critical optional parameters: the support of these parameters is not critical for the receiver. The receiver can successfully and correctly comprehend the Overload Control Information instance, containing one or more of these parameters, by using the other parameters and ignoring the non-critical optional parameters.
- Critical optional parameters: the support of these parameters is critical for the receiver to correctly comprehend the instance of the Overload Control Information containing one or more of these parameters.

The sender may include one or more non-critical optional parameter(s) within any instance of Overload Control Information, without having the knowledge of the receiver's capability to support the same. However, the sender shall only include one or more critical optional parameter(s) in any instance of Overload Control Information towards a receiver, if the corresponding receiver is known to support these parameter(s). The sender may be aware of this either via signalling methods or by configuration; this will have to be defined when introducing any such new parameter in the future.

Each instance of the OCI shall be associated by default to the GTP-C entity corresponding to the peer node's IP address of the PDN connection, over which the OCI IE is received, i.e. to the IP address received within the "Sender F-TEID for

control plane" IE, the "PGW S5/S8/ S2a/S2b F-TEID for PMIP based interface or for GTP based Control Plane interface" IE or within the "MME/S4-SGSN Identifier" IE.

Alternatively, the GW (i.e. SGW and PGW) nodes may send Overload Control Information which is associated with the GW node's identity, i.e. the FQDN or IP address of the GW node received from the HSS (for a PGW) or the DNS (for an SGW or PGW), the identity determined during the GW selection. In that case, the GW node shall provide an explicit indication that the OCI IE included in the message belongs to the GW node's identity.

#### 12.3.5.1.2 Parameters

#### 12.3.5.1.2.1 Overload Control Sequence Number

The GTP-C protocol requires retransmitted messages to have the same contents as the original message (see clause 7.6). Due to GTP-C retransmissions, the overload control information received by a GTP-C entity at a given time may be less recent than the overload control information already received from the same GTP-C entity. The Overload Control Sequence Number aids in sequencing the overload control information received from an overloaded GTP-C entity. The Overload Control Sequence Number contains a value that indicates the sequence number associated with the Overload Control Information IE. This sequence number shall be used to differentiate between two OCI IEs generated at two different instants, by the same GTP-C entity.

The Overload Control Sequence Number parameter shall be supported (when supporting the overload control feature) and shall always be present in the Overload Control Information IE.

The GTP-C entity generating this information shall increment the Overload Control Sequence Number whenever modifying some information in the OCI IE. The Overload Control Sequence Number shall not be incremented otherwise. The GTP-C entity may use the time, represented in an unsigned integer format, of the generation of the overload control information, to populate the Overload Control Sequence Number.

When multiple instances of the OCI IE are provided in the same message by a given GTP-C entity, each of the Overload Control Sequence Numbers shall have the same value.

This parameter shall be used by the receiver of the OCI IE to properly collate out-of-order OCI IEs, e.g. due to GTP-C retransmissions. This parameter shall also be used by the receiver of the OCI IE to determine whether the newly received overload control information has changed compared to the overload control information previously received from the same GTP-C entity. If the newly received overload control information has the same Overload Control Sequence Number as the previously received overload control information from the same GTP-C peer, then the receiver may simply discard the newly received overload control information whilst continuing to apply the overload abatement procedures, as per the previous value.

- NOTE 1: The timer corresponding to the Period of Validity (see 12.3.5.1.2.2) is not restarted if the newly received overload control information has the same Overload Control Sequence Number as the previously received overload control information. If the overload condition persists and the overloaded GTP-C entity needs to extend the duration during which the overload information applies, the sender needs to provide a new overload control information with an incremented Overload Control Sequence Number (even if the parameters within the overload control information have not changed).
- NOTE 2: The GTP-C Sequence Number cannot be used for collating out-of-order overload information as e.g. overload control information may be sent in both GTP-C requests and responses, using independent GTP-C sequence numbering.

If the receiving GTP-C entity already received and stored overload control information, which is still valid, from the overloaded GTP-C entity, the receiving entity shall update its overload control information, only if the Overload-Sequence-Number received in the new overload control information is larger than the value of the Overload Control Sequence Number associated with the stored information. However due to roll-over of the Overload Control Sequence Number or restart of the GTP-C entity, the Overload Control Sequence Number may be reset to an appropriate base value by the peer GTP-C entity, hence the receiving entity shall be prepared to receive (and process) an Overload Control Sequence Number parameter whose value is less than the previous value.

#### 12.3.5.1.2.2 Period of Validity

The Period of Validity indicates the length of time during which the overload condition specified by the OCI IE is to be considered as valid (unless overridden by subsequent new overload control information).

An overload condition shall be considered as valid from the time the OCI IE is received until the period of validity expires or until another OCI IE with a new set of information (identified using the Overload Control Sequence Number) is received from the same GTP-C entity (at which point the newly received overload control information shall prevail). The timer corresponding to the period of validity shall be restarted each time an OCI IE with a new set of information (identified using the Overload Control Sequence Number) is received. When this timer expires, the last received overload control information shall be considered outdated and obsolete, i.e. any associated overload condition shall be considered to have ceased.

The Period of Validity parameter shall be supported (when supporting overload control).

The Period of Validity parameter achieves the following:

- it avoids the need for the overloaded GTP-C entity to include the Overload Control Information IE in every GTP-C messages it signals to its GTP-C peers when the overload state does not change; thus it minimizes the processing required at the overloaded GTP-C entity and its GTP-C peers upon sending/receiving GTP-C signalling;
- it allows to reset the overload condition after some time in the GTP-C peers having received an overload
  indication from the overloaded GTP-C entity, e.g. if no signalling traffic takes place between these GTP-C
  entities for some time due to overload mitigation actions. This also removes the need for the overloaded GTP-C
  entity to remember the list of GTP-C entities to which it has sent a non-null overload reduction metric and to
  which it would subsequently need to signal when the overload condition ceases, if the Period of Validity
  parameter was not defined.

#### 12.3.5.1.2.3 Overload Reduction Metric

The Overload Reduction Metric shall have a value in the range of 0 to 100 (inclusive) which indicates the percentage of traffic reduction the sender of the overload control information requests the receiver to apply. An Overload Reduction Metric of "0" always indicates that the GTP-C entity is not in overload (that is, no overload abatement procedures need to be applied) for the indicated scope.

Considering the processing requirement of the receiver of the Overload Control Information, e.g. to perform overload control based on the updated Overload Reduction Metric, the sender should refrain from advertising every small variation, e.g. with the granularity of 1 or 2, in the Overload Reduction Metric which does not result in useful improvement for mitigating the overload situation. During the typical operating condition of the sender, a larger variation in the Overload Reduction Metric, e.g. 5 or more units, should be considered as reasonable enough for advertising a new Overload Reduction Metric Information and thus justifying the processing requirement (to handle the new information) of the receiver.

NOTE: The range of Overload Reduction Metric, i.e. 0 to 100, does not mandate the sender to collect its own overload information at every increment/decrement and hence to advertise the change of Overload Reduction Metric with a granularity of 1%. Based on various implementation specific criteria, such as the architecture, session and signalling capacity, the current load/overload situation and so on, the sender is free to define its own logic and periodicity with which its own overload control information is collected.

The computation of the exact value for this parameter is left as an implementation choice at the sending GTP-C entity.

The Overload Reduction Metric shall be supported (when supporting overload control) and shall always be present in the OCI IE.

The inclusion of the OCI IE signals an overload situation is occuring, unless the Overload Reduction Metric is set to 0, which signals that the overload condition has ceased. Conversely, the absence of the OCI IE in a message does not mean that the overload has abated.

#### 12.3.5.1.2.4 List of APNs

The List of APNs IE indicates one or more APNs for which the Overload Control Information is applicable. When present in the OCI IE, the scope of the overload control information shall be the list of the indicated APNs for the PGW that sends the overload control information. At most one instance of the List of APNs IE shall be included within one Overload Control Information instance.

NOTE 1: The maximum number of APNs in the List of APNs is set to 10. More than 10 occurrences of APN within one single instance of the List of APNs IE is treated as a protocol error by the receiver.

If the List of APNs IE has not been included, the scope of the Overload Control Information shall be the entire GTP-C entity (unless restricted by other parameters in the Overload Control Information IE).

The List of APNs parameter shall be supported (when supporting overload control). The List of APNs may be present or absent in the Overload Control Information IE (depending on the scope of the reported overload control information).

NOTE 2: The instance number of both the node-level and APN-level overload control information is "0" and the instance number is therefore not used to indicate if the scope of the overload control information is on PGW node level or APN level.

This parameter may be provided by the PGW only and it shall be used by the MME/S4-SGSN and the TWAN/ePDG only.

The maximum number of APNs, for which the PGW may advertise the Overload Control Information, shall be limited to 10, i.e. the maximum number of occurrences of APNs within and across various instances of the Overload Control Information IE shall be limited to 10 for a given PGW. Hence, if the PGW supports more than 10 APNs, it shall advertise the overload control for at most 10 of the most important APNs. In future, if needed, this limit may be increased to allow the PGW to advertise the overload information for more APNs. In that case, the receiver that does not support the higher limit shall only handle the first 10 APNs and ignore the overload information for the remaining APNs to enable future compatibility.

NOTE 3: Considering various aspects such as: the processing and storage requirements at the overloaded GTP-C entity and the receiver, the number of important APNs for which overload control advertisement could be necessary, interoperability between the nodes of various vendors, etc. it was decided to define a limit on maximum number of APNs for advertising the overload control information. It was decided to fix this limit to 10 whilst also ensuring that the mechanism exists to extend this limit in future releases, if required.

#### 12.3.5.1.3 Handling of parameters

If the PLMN supports the Overload Control feature (see subclause 12.3.11), the support, inclusion and handling of the parameters, within overload control information, is summarized in table 12.3.5.1.3-1.

Parameter	Support by the sender	Support by the receiver	Inclusion by the sender	Handling by the receiver
Overload Control Sequence Number (as defined in clause 12.3.5.1.2.1)	Mandatory	Mandatory	Mandatory	Mandatory
Period of Validity (as defined in clause 12.3.5.1.2.2)	Mandatory	Mandatory	Mandatory	Mandatory
Overload Reduction Metric (as defined in clause 12.3.5.1.2.3)	Mandatory	Mandatory	Mandatory	Mandatory
List of APNs (as defined in clause 12.3.5.1.2.4)	Mandatory	Mandatory	Optional (NOTE 1)	Conditional (NOTE 2)

#### Table 12.3.5.1.3-1: Parameters of the Overload Control Information

1: The PGW shall send this parameter whilst providing APN level overload control information.

2: If this parameter is received, the receiver shall handle and process APN level overload control information.

## 12.3.5.2 Frequency of inclusion

How often or when the sender includes the overload control information is implementation specific. The sender shall ensure that new/updated overload control information is propagated to the target receivers with an acceptable delay, such that the purpose of the information, (i.e. the effective overload control protection) is achieved. The following are some of the potential approaches the sender may implement for including the OCI IE:

- the sender may include OCI IE towards a receiver only when the new/changed value has not already been provided to the given receiver;

- the sender may include the OCI IE in a subset of the messages towards the receiver;
- the sender may include the OCI IE periodically, i.e. include the information during a first period then cease to do so during a second period.

The sender may also implement a combination of one or more of the above approaches. Besides, the sender may also include the OCI IE only in a subset of the applicable GTP-C messages.

The receiver shall be prepared to receive the overload control information received in any of the GTP-C messages extended with an OCI IE and upon such reception, shall be able act upon the received information.

### 12.3.5.3 Limit on maximum number of instances

A GTP-C entity may signal one or multiple instances of the OCI IE, each instance providing overload control information for a different scope. The receiver shall handle all these instances, from each of the peer GTP-C entities, by processing, storing and acting upon the same foroverload control. In order to limit the processing of the message on the receiver side and the size of the message, the number of overload control information instances shall be limited:

- at message level: there shall be at most one instance of node-level Overload Control Information IE per node and at most 10 APN-level instances.
- at node level: the maximum number of instances of the OCI IE which may be provided across multiple messages by a given node shall be the same as the maximum number of instances of the OCI IE at message level.

## 12.3.6 Propagating the MME/S4-SGSN identity to the PGW

When the Overload Control feature is supported by the MME/S4-SGSN and the SGW, and it is also activated for the PLMN to which the PGW belongs (see subclause 12.3.11), the following shall apply:

- The MME/S4-SGSN shall include the MME/S4-SGSN identity towards the SGW during:
  - the PDN connection establishment, any mobility with an MME/S4-SGSN change or any SGW change procedures;
  - the dedicated bearer activation procedure, PGW initiated bearer modification procedure and PGW initiated bearer deactivation procedure as per the conditions specified in the corresponding messages.
- The SGW shall forward the MME/S4-SGSN identifier to the PGW if it is received in the Create/Update/Delete Bearer Response messages. When it is received in other GTP-C messages, the SGW shall store the received MME/S4-SGSN identity and shall include the currently serving MME/S4-SGSN's identity in subsequent Modify Bearer Request messages which are sent over the S5/S8 interface, whenever there is signalling over the S5/S8 interface.
- NOTE: This allows updating of the PGW with the identity of the new MME/S4-SGSN during inter-MME/SGSN mobility scenarios as early as possible and without generating extra signalling over the S5/S8 interface. Inter-MME/inter-SGSN intra SGW mobility scenarios not requiring to send any S5/S8 signalling could result in the PGW not being updated with the currently serving MME/S4-SGSN's identity, for a given subscriber, until subsequent S5/S8 signalling takes place for the same PDN connection. However, considering these scenarios are not so frequent and considering that several features anyway require S5/S8 signalling during these scenarios (e.g. for user location reporting), the PGW will most often get the identity of the currently serving MME/S4-SGSN. Hence the risk that the PGW wrongly throttles PGW initiated signalling for that PDN connection, if the old MME/S4-SGSN is in overload, is low.
- The PGW shall store the currently serving MME/S4-SGSN identity, received from the SGW, to be able to reduce the PGW initiated signalling messages for the PDN connections during an overload situation at the serving MME/S4-SGSN.

# 12.3.7 Updating the PGW with overload control information of the target MME/S4-SGSN

During inter-MME/S4-SGSN mobility without SGW change scenarios, the SGW shall forward the MME/S4-SGSN's overload control information over the S5/S8 interface only if the Modify Bearer Request message needs to be sent over

the S5/S8 for another reason, e.g. if the ULI, CGI, Serving Network, needs to be reported to the PGW, i.e. the SGW shall not generate a Modify Bearer Request message over the S5/S8 interface for the sole purpose of reporting the MME/S4-SGSN's overload control information. This avoids generating extra signalling over the S5/S8 interface.

NOTE: If the MME/S4-SGSN provides overload control information during the scenarios which do not result in S5/S8 signaling, e.g. during an inter MME/S4-SGSN and intra SGW mobility, when no other information such as: the ULI, CGI or Serving Network, needs to be reported to the PGW, the overload information will not be relayed on to the PGW. Hence, the MME/S4-SGSN needs consider this when including overload control information.

## 12.3.8 The interaction with APN congestion control using the PGW Back-Off Time

When detecting that a given APN is congested, the PGW shall either use the PGW Back-Off Time mechanism (see subclause 4.3.7.5 of 3GPP TS 23.401 [3]) or the APN level overload control mechanism (i.e. providing an Overload Control Information IE with an APN-List included) for that APN, but not both together for the same APN, e.g. if the PGW provides an Overload Control Information IE with an APN-List set to "APN1", it shall not reject Create Session Request messages for "APN1" with a PGW Back-Off Time until the Period-Of-Validity of the overload information previously sent has expired.

The PGW may however use both mechanisms concurrently for different APNs, e.g. the PGW may reject Create Session Request messages for the "APN2" with a PGW Back-Off Time IE, if the APN2 is also congested and if there is no on-going APN-level overload control mechanism for that APN.

When rejecting a Create Session Request due to APN congestion, the PGW shall set the "APN Congestion" cause, regardless of the aforementioned mechanisms.

If the MME/S4-SGSN or ePDG/TWAN has one mechanism active for a given APN and PGW, (e.g. an MME has received a PGW Back-Off Time) and if subsequently it receives information for the same APN and PGW for another mechanism, (e.g. the MME receives an Overload Control Info IE with APN-List included for the same APN), then it shall deactivate/stop the earlier mechanism and consider only the information received for the latter mechanism.

Different PGWs may use concurrently different mechanisms for the same APN.

## 12.3.9 Message throttling

## 12.3.9.1 General

As part of the overload mitigation, a GTP-C entity shall reduce the total number of messages, which would have been sent otherwise, towards the overloaded peer based on the information received within the Overload Control Information. This shall be achieved by discarding a fraction of the messages in proportion to the overload level of the target peer. This is called message throttling.

Message throttling shall only apply to initial messages. Triggered request or response messages should not be throttled since that would result in the retransmission of the corresponding request message by the sender.

Before piggybacking the initial message over a response message, the initial message should be subject to the message throttling in the similar manner as any other non-piggybacked initial message. If the node decides to throttle this initial message then the response message should be sent without any piggyback message.

370

A GTP-C entity supporting GTP-C overload control shall support and use the "Loss" algorithm as specified in this clause, for message throttling.

## 12.3.9.2 Throttling algorithm – "Loss"

#### 12.3.9.2.1 Description

An overloaded GTP-C entity shall ask its peers to reduce the number of requests they would ordinarily send by signalling Overload Control Information including the requested traffic reduction, as a percentage, within the "Overload-Reduction-Metric", as specified in clause 12.3.5.1.2.1.

The recipients of the "Overload-Reduction-Metric" shall reduce the number of requests sent by that percentage, either by redirecting them to an alternate destination if possible (e.g. the Create Session Request message may be redirected to an alternate SGW/PGW), or by failing the request and treating it as if it was rejected by the destination GTP-C entity.

For example, if a sender requests another peer to reduce the traffic it is sending by 10%, then that peer shall throttle 10% of the traffic that would have otherwise been sent to this GTP-C entity.

The overloaded GTP-C entity should periodically adjust the requested traffic reduction based e.g. on the traffic reduction factor that is currently in use, the current system utilization (i.e. the overload level) and the desired system utilization (i.e. the target load level), and/or the rate of the current overall received traffic.

Annex D.3.1 provides an (informative) example of a possible implementation of the "Loss" algorithm, amongst other possible methods.

- NOTE 1: This algorithm does not guarantee that the future traffic towards the overloaded GTP-C entity will be less than the past traffic but it ensures that the total traffic sent towards the overloaded GTP-C entity is less than what would have been sent without any throttling in place. If after requesting a certain reduction in traffic, the overloaded GTP-C entity receives more traffic than in the past, whilst still in overload, leading to the worsening rather than an improvement in the overload level, then the overloaded GTP-C entity can request for more reduction in traffic. Thus, by periodically adjusting the requested traffic reduction, the overloaded node can ensure that it receives, approximately, the amount of traffic which it can handle.
- NOTE 2: Since the reduction is requested as a percentage, and not as an absolute amount, this algorithm achieves a good useful throughput towards the overloaded node when the traffic conditions vary at the source nodes (depending upon the events generated towards these source nodes by other entities in the network), as a potential increase of traffic from some source nodes can possibly be compensated by a potential decrease of traffic from other source nodes.

### 12.3.9.3 Message prioritization

### 12.3.9.3.1 Description

When performing message throttling:

- GTP requests related to priority traffic (i.e. eMPS as described in 3GPP TS 22.153 [62]) and emergency have the highest priority. Depending on regional/national requirements and network operator policy, these GTP requests shall be the last to be throttled, when applying traffic reduction, and the priority traffic shall be exempted from throttling due to GTP overload control up to the point where the requested traffic reduction cannot be achieved without throttling the priority traffic;
- for other types of sessions, messages throttling should consider the relative priority of the messages so that the messages which are considered as low priority are considered for throttling before the other messages. The relative priority of the messages may be derived from the relative priority of the procedure for which the message is being sent (as specified in subclause 12.3.9.3.2) or may be derived from the session parameters (as specified in subclause 12.3.9.3.3).
- NOTE: A random throttling mechanism, i.e. discarding the messages without any special consideration, could result in an overall poor congestion mitigation mechanism and bad user experience.

An overloaded node may also apply these message prioritization schemes when handling incoming initial messages during an overloaded condition, as part of the self-protection mechanism (see subclause 12.3.10.2.3).

#### 12.3.9.3.2 Based on procedures

Message prioritization may be performed based on the relative priority of the procedure for which the message is being sent. Procedures are grouped into various categories and each of these categories is assigned a priority. Additionally, within a given category of procedures, messages may be further prioritized based on session parameters such as: APN, QCI, ARP and/or LAPI (as described in subclause 12.3.9.3.3).

Subsequently, messages with a high priority shall be given lower preference to throttle and messages with low priority shall be given higher preference to throttle.

The grouping of the procedures is not performed based on an individual GTP-C entity but whilst considering all the procedures in general. A GTP-C entity should consider the procedures applicable to it and apply prioritized message throttling based on the category of the procedure, as described below. The categories are listed in decreasing order of priority with category 1 having the highest priority. For each category a non-exhaustive list of messages is provided. Any existing or newly defined message in future should be considered based on the category (as specified below) of the procedure for which the message is sent.

- 1. UE session mobility within and across 3GPP or non-3GPP access: Procedures involving active or idle mode UE mobility, such that GTP-C signalling is involved, shall be classified under this category. Some examples are X2/S1 based handover with/without an SGW change, TAU/RAU with a change of MME/SGSN with/without an SGW change, 3GPP access to trusted non-3GPP access handover, etc. Throttling of these messages, during the procedures related to UE session mobility, would result in the failure of the corresponding procedures. This could result potentially in the loss of the PDN connection and/or the interruption of the services. Hence, the messages, as identified below, when sent during the procedures belonging to this category, shall be considered with the highest priority and hence, shall be given the lowest preference to throttle.
  - Create Session Request,
  - Create Session Request with "handover" indication bit set,
  - Modify Bearer Request,
  - Modify Bearer Request with "handover" indication bit set,
  - Modify Access Bearer Request.
- 2. **Release of PDN connection or bearer resources:** Procedures resulting in the deactivation of an existing PDN connection, the deactivation of bearer(s) or of data forwarding tunnel of an UE leads to freeing up of the resources at the overloaded node and hence, can potentially ease the overload situation, since the freed up resources can be used for serving the remaining of the UEs. Thus, the messages belonging to this category resulting in the deactivation of PDN connection or bearer(s) or data forwarding tunnel(s), as identified below, shall be treated with the next lower level of priority and hence shall be given the corresponding preference whilst throttling:
  - Delete Session Request,
  - Delete Bearer Request,
  - Delete Bearer Command,
  - Delete Indirect Data Forwarding Tunnel Request.
- 3. **Miscellaneous session management procedures:** This category shall consist of the session management procedures, except PDN connection creation and bearer creation/modification procedures. Some examples are location reporting, when it is not combined with other mobility procedures, Service request and S1 release procedure. These procedures do not severely impact the on-going service of the UE. Hence, the messages, as identified below, when sent during the procedures identified under this category, shall be treated with the next lower level of priority and hence, shall be given the corresponding preference whilst throttling:
  - Release Access Bearer Request,
  - Modify Bearer Request,
  - Change Notification,
  - Suspend Notification,

- Resume Notification.
- 4. **Request for new PDN Connection or bearer resources:** Procedures requesting the creation of PDN connection, creation or modification of bearer(s) or creation of data forwarding tunnel shall be classified in this category. Throttling of the messages belonging to this category would result in denial of new services while continuing with the existing services. However, this is the natural outcome of an overload condition, i.e. the overloaded node, due to lack of resources, is not able to provision new services while the trying to maintain the existing services and hence, the messages, as identified below, when sent during the procedures belonging to this category, shall be considered with the lowest level of priority and hence shall be given highest preference to throttle:
  - Create Session Request during PDN connection request,
  - Create Bearer Request,
  - Update Bearer Request,
  - Bearer Resource Command,
  - Modify Bearer Command,
  - Create Indirect Data Forwarding Tunnel Request.

#### 12.3.9.3.3 Based on session parameters

Message prioritization may be performed based on the session parameters, such as: APN, QCI, ARP and/or Low Access Priority Indicator (LAPI). The procedures and messages associated with the higher priority sessions shall be given lesser preference whilst throttling, as compared to the procedures and messages associated with the lower priority sessions. Within each group of sessions, the messages may be further prioritized based on the category of the procedure for which the message is being sent (as described in subclause 12.3.9.3.2).

NOTE: This type of prioritization scheme ensures a good handling of all the messages and procedures related to higher priority sessions but can lead to throttle messages related to a critical procedure, e.g. UE mobility, for lower priority sessions over messages related to less critical procedures, e.g. location reporting, for a higher priority session.

#### 12.3.9.3.4 Based on the Message Priority signalled in the GTP-C message

Message prioritization may be performed by an overloaded node, when handling incoming messages during an overloaded condition, based on the relative GTP-C message priority signalled in the GTP-C header (see subclauses 5.4 and 5.5).

A GTP-C entity shall determine whether to set and use the message priority in GTP-C signalling within the PLMN and/or across the PLMN boundaries, based on operator policy and roaming agreements. The following requirements shall apply if being used.

A sending GTP-C entity shall determine the relative message priority to signal in the message according to the principles specified in subclause 12.3.9.3.1. If the message affects multiple bearers (e.g. Modify Bearer Request), the relative message priority should be determined considering the highest priority ARP among all the bearers.

A GTP-C entity should set the same message priority in a Triggered message or Triggered Reply message as received in the corresponding Initial message or Triggered message respectively.

The message priority values sent on intra-network interfaces may differ from the values sent on inter-network interfaces. When messages cross PLMN boundaries, the Message Priority in the GTP-C header may be stripped or modified in these messages.

NOTE : This is to take into account that the priority definitions can vary between PLMNs and avoid messages from a foreign PLMN to gain unwarranted preferential treatment.

For incoming GTP-C messages that do not have a message priority in the GTP-C header, the receiving GTP-C entity:

- shall apply a default priority, if the incoming message is an Initial message;

- should apply the message priority sent in the Initial message or Triggered message, if the incoming message is a Triggered or Triggered Reply message (respectively).

This feature should be supported homogenously across the nodes in the network, otherwise an overloaded node will process initial messages received from the non-supporting nodes according to the default priority while initial messages received from supporting nodes will be processed according to the message priority signalled in the GTP-C message.

## 12.3.10 Enforcement of overload control

## 12.3.10.1 General

When a GTP-C entity receives Overload Control Information from its peer, it shall apply the overload abatement algorithm, based on the received information, for the messages sent towards the peer GTP-C entity. This is called "enforcement of overload control" and it involves throttling of the messages targeted for the overloaded peer.

#### 12.3.10.2 Aspects related to enforcement of the overload control

#### 12.3.10.2.1 Good throughput of the network

A source GTP-C entity should avoid any mechanism resulting in over throttling of the messages. Enforcement of the overload control whilst ensuring that good throughput (i.e. measured in terms of the rate of total number of messages the overloaded GTP-C entity can successfully process) of the network remains consistent to that when no overload control is applied, should be one of the prime objective of the source GTP-C entity.

NOTE: Over throttling of messages would negatively affect end user services and cause potential additional signalling in the network e.g. if the corresponding procedure is retried at a later time.

#### 12.3.10.2.2 Message processing efficiency at the source GTP-C entity

Enforcement of overload control requires extra logic and extra processing at the source GTP-C entity. This is an overhead since the source GTP-C entity has to spend its resources in an activity other than processing of the messages. Hence, the implementation as well as the processing complexity of the enforcement of the overload control, should not result in a significantly poorer efficiency of the source GTP-C entity.

#### 12.3.10.2.3 Self-protection by the overloaded GTP-C entity

A source GTP-C entity enforcing the overload control cannot ensure that the overloaded peer will not receive more messages than what it can handle during the overload condition, e.g. the "loss" algorithm does not guarantee that the future traffic reaches perfectly that requested by the overloaded GTP-C entity. Hence, the overloaded target GTP-C entity shall protect itself from the risk of meltdown even in a network where all the sending GTP-C entities support the overload control mechanism. As a part of this self-protection, the overloaded target GTP-C entity may reject the messages which it cannot handle during an overloaded state. A GTP-C entity which decides to not process an incoming request message due to overload should still send a reject response message, if possible, indicating the temporary unavailability of the resources; otherwise the request message may be dropped.

NOTE: Without a response message, the source GTP-C entity cannot determine whether the request did not reach the target GTP-C entity due to a network error or whether the target GTP-C entity was in overload and not able to process the request and send a response message. This will cause the source GTP-C entity to retransmit the request message and hence will increase further the overload at the target node.

The GTP-C entity may apply message prioritization as described in subclause 12.3.9.3 when selecting the incoming request messages to be throttled.

While rejecting the message due to overload, the GTP-C entity shall set the cause to "GTP-C Entity Congestion" or "APN congestion" (for node level or APN level overload respectively) and may include the Overload Control Information in the rejection response as specified in subclauses 12.3.5.1.1 and 12.3.11.

## 12.3.10.3 Enforcement of overload control between GTP-C entities in direct contact

A source GTP-C entity shall enforce overload control for traffic destined to a GTP-C entity in direct contact based on the overload reduction metric received from that peer, e.g. the MME applies the overload control for the messages targeted for the SGW based on the overload information of the SGW.

## 12.3.10.4 Enforcement of overload control between remote GTP-C entities

#### 12.3.10.4.1 Description

For messages destined to a remote GTP-C entity (i.e. a GTP-C entity not in direct contact but reached via an intermediate GTP-C entity), the source GTP-C entity shall enforce the overload control based on the overload information of the target of the message, as well as the overload information of the intermediate GTP-C entity, e.g. the MME applies the overload control for messages targeted for the PGW based on the overload information of the SGW and PGW.

For the received messages, the intermediate GTP-C entity shall not further enforce any overload control and hence, shall not reject any message towards the source GTP-C entity.

Annex D.4.1 provides an (informative) example of a possible implementation.

- NOTE 1: This approach ensures the overload protection of the Target as well as Intermediate GTP-C entities.
- NOTE 2: The source GTP-C entity may be connected to the same Target GTP-C entity via multiple different Intermediate GTP-C entities. The exact algorithm used at the source GTP-C entity to enforce the overload control, as per the aforementioned requirements, is implementation specific.

## 12.3.11 Discovery of the support of the feature by the peer node

A GTP-C entity shall determine whether to use the overload control feature:

- within the PLMN, based on operator's policy (local PLMN-wide configuration);
- across the PLMN boundaries, based on operator's policy (local configuration per PLMN).
- NOTE: The feature can be activated when all or some of the nodes in the PLMN support the feature. The GTP-C entity assumes that all the peer nodes support this feature when the feature is activated, i.e. it does not need to determine which peers support the feature.

The above operator policy/local configuration may allow the use of overload control at node level and APN level, or none.

## 12.3.12 Issues in the network with partial support of the feature

The Overload Control feature should be supported homogenously across the nodes in the network, otherwise:

- an overloaded node will get messages beyond its acceptable processing capacity, even after announcing its overload status. This may result in severe overload and possibly a breakdown of the node;
- a non-supporting node will get an unfair advantage in sending all the messages to an overloaded node, whereas a supporting node, would be requested to throttle more messages.

## 12.3.13 Implicit overload control mechanisms

Implicit overload control mechanisms are mechanisms used between GTP-C entities when GTP-C overload control is not supported or not enabled between them, e.g. across PLMN boundary based on operator's policy, to help reducing the overload at the overloaded node:

- a GTP-C entity which decides to not process an incoming request message due to overload should still send a reject response message, if possible, indicating the temporary unavailability of the resources, e.g. No resources available; otherwise the GTP-C entity may drop the incoming request message.

- NOTE: Without a response message, the source GTP-C entity cannot determine whether the request did not reach the target GTP-C entity due to a network error or whether the target GTP-C entity was in overload and not able to process the request and send a response message. This will cause the source GTP-C entity to retransmit the request message and hence will increase further the overload at the target node.
- a GTP-C entity in overload may support messages throttling as a self protection mechanism and may apply message prioritization as described in subclause 12.3.9.3 when selecting the incoming request messages to be throttled;
- based on the number and rate of reject responses indicating temporary unavailability of resources, e.g. No resources available, a source GTP-C entity should try to assess the overload level of the target GTP-C entity and apply correspondingly message throttling as described in subclause 12.3.9 to reduce the amount of traffic sent towards the overloaded GTP-C entity.

# 13 Detection and handling of late arriving requests

## 13.1 General

The procedures specified in this clause aim at handling more efficiently requests which may arrive late at upstreams entities, e.g. in networks experiencing processing or transport delays.

These procedures are optional to support. When supported, the use of these procedures is dependent on operator policy.

The procedure specified in subclause 13.2 may be used with or without the procedure specified in subclause 13.3. The procedure specified in subclause 13.3 shall only be used in conjunction with the procedure specified in subclause 13.2.

# 13.2 Detection and handling of requests which collide with an existing session context

## 13.2.1 General

This procedure enables an entity, which receives a request colliding with an existing session context, to know the time at which the new request and the existing session were originated, and to accept the new request only if it is more recent than the existing session.

The originating entities within the PLMN (i.e. MME, SGSN, TWAN and ePDG) shall be NTP synchronized.

## 13.2.2 Principles

The following principles shall apply if this procedure is supported and enabled by operator policy.

A GTP-C entity originating a Create Session Request (i.e. MME, SGSN, TWAN or ePDG) shall include in the message the Origination Time Stamp indicating the absolute time at which the request is initiated.

The SGW shall forward this parameter over the S5/S8 interface, if it is received from the MME/SGSN.

Upon receipt of a session establishment request which collides with an existing session context, the PGW shall accept the new session establishment request only if it contains a more recent time stamp than the time stamp stored for the existing session. An incoming session request shall be considered as more recent than an existing session and be accepted if no Origination Time Stamp information was provided for at least one of the two sessions. The PGW shall reject an incoming request whose time stamp is less recent than the time stamp of the existing session with the cause 'Late Overlapping Request'.

3GPP TS 29.212 [29] and 3GPP TS 29.273 [68] further specify:

- the PGW requirements regarding the forwarding of the Origination Time Stamp parameter over the Gx and/or S6b interfaces, when received from the SGW or TWAN/ePDG;

- the handling of the Origination Time Stamp parameter by the PCRF and 3GPP AAA Server for an incoming request colliding with an existing session context.

An originating entity which detects a NTP failure shall not include the Origination Time Stamp towards other entities.

# 13.3 Detection and handling of requests which have timed out at the originating entity

## 13.3.1 General

This procedure enables an entity which receives a request to know when the request times out at the originating entity, and to stop further processing, at the receiver and further upstream entities, a request which has timed out at the originating entity.

The originating entities (i.e. MME, SGSN, TWAN and ePDG) and the receiving entities (i.e. SGW, PGW, PCRF, 3GPP AAA Server) shall be NTP synchronized. This procedure may be used between entities pertaining to the same PLMN, and if allowed by operator policy, between entities pertaining to different PLMNs.

This procedure shall not affect the setting of the retransmission timers by intermediate entities. E.g. the SGW shall set its T3 and N3 retransmission parameters as specified in this specification, irrespective of the time at which the request times out at the originating entity.

## 13.3.2 Principles

The following principles shall apply if this procedure is supported, enabled by operator policy and if the PGW pertains to the same PLMN as the originating entity or if the PGW pertains to a different PLMN and operator policy in the originating entity allows to use this procedure towards this PLMN.

A GTP-C entity originating a Create Session Request (i.e. MME, SGSN, TWAN or ePDG) shall include in the message the Origination Time Stamp indicating the absolute time at which the request is initiated, as specified in subclause 13.2.2, and the Maximum Wait Time indicating the maximum time period to complete the processing of the request. The Maximum Wait Time, together with the Origination Time Stamp, indicates the absolute time at which the request times out at the originating entity.

The MME/SGSN shall set the Maximum Wait Time to a value smaller or equal to  $(N3+1) \times T3$  set in the SGW, to avoid upstream entities continuing to process requests which would have ceased to be processed by the SGW, which could result in hanging contexts in upstream entities.

NOTE 1: If the Maximum Wait Time is set to a value smaller than N3 x T3 set in the SGW, the SGW actually stops retransmitting a given GTP-C Create Session Request as soon as it receives a rejection response from the PGW due to the expiry of the Maximum Wait Time. I.e. the Maximum Wait Time actually leads to shorten the duration during which the SGW retransmits the GTP-C request.

The SGW shall forward the Origination Time Stamp over the S5/S8 interface as specified in subclause 13.2.2. The SGW shall also forward the Maximum Wait Time over the S5/S8 interface, if received from the MME/SGSN.

Upon receipt of a request which contains the Origination Time Stamp and the Maximum Wait Time parameters, the receiving entity should check that the request has not already timed out at the originating entity. The receiving entity may perform additional similar checks during the processing of the request, e.g. upon receipt of a response from the next upstream entity.

The receiving entity should reject a request that is known to have timed out with the cause 'Timed Out Request'; it may alternatively drop the request. Besides, the receiving entity should initiate the release of any session it may have successfully created towards an upstream entity, to avoid hanging sessions in the network.

NOTE 2: Sending a rejection response over the last hop towards the originating node, i.e. over S11/S4 or S2a/S2b, is not useful as the request has timed out at the originated entity.

In the context of this specification, the receiving entity refers to an SGW or PGW.

3GPP TS 29.212 [29] and 3GPP TS 29.273 [68] further specify:

- the PGW requirements regarding the forwarding of the Maximum Wait Time parameter over the Gx and/or S6b interfaces, when received from the SGW or TWAN/ePDG;
- the handling of the Maximum Wait Time parameter by the PCRF and 3GPP AAA Server.

An originating entity which detects a NTP failure shall not insert the Origination Time Stamp and the Maximum Wait Time parameters towards other entities. A receiving entity which detects a NTP failure shall ignore the the Maximum Wait Time parameter.

# 14 Handling of Bearer Contexts Mismatch

## 14.1 General

Bearer Contexts mismatch among different EPC entities, e.g. MME/SGW/PGW, can happen due to various reasons, e.g. transport network delay, signalling overload.

## 14.2 Detection of Bearer Context Mismatch

Bearer Context mismatch can be detected by a receiving GTP-C entity in the following cases:

- when at least one dedicated bearer context in the request message is unknown; or
- when at least one dedicated bearer context is missing in the request message in comparison to the bearer contexts stored; or
- when receiving a response message indicating that one of the dedicated bearer context(s) was unknown, by using the cause code "Context not found" at the Bearer Context level. See also subclause 8.4.

The Modify Bearer Request/Response and the Modify Access Bearer Request/Response in particular enables an easy detection of bearer contexts mismatch since all the bearer contexts, either of the PDN connection for a Modify Bearer Request/Response or of all the UE's PDN connections for a Modify Access Bearer Request/Response, need to be included in the messages.

## 14.3 Handling of Bearer Context Mismatch

## 14.3.1 General

The following requirements should apply:

- When an EPC entity receives a response message, where one or more dedicated bearer context(s) is associated with the Cause code "Context Not Found" while the PDN connection is known by the peer, the EPC entity shall delete the corresponding bearer context(s);
- 2) When an SGW receives a Modify Bearer Request, where one or more dedicated bearer context(s) is missing in the request message in comparison to the Bearer Context(s) stored for the UE's PDN connection, the SGW shall accept the Modify Bearer Request message and delete the corresponding bearer context(s) locally. The PGW shall apply the same behavior if the Modify Bearer Request received at the PGW includes the Bearer Contexts to be modified IE;
- 3) When a SGW receives a Modify Bearer Request, where only one or more dedicated bearer context(s) is unknown, the SGW shall accept the Modify Bearer Request message partially and set the cause code "Context Not Found" for those unknown bearer context(s) at Bearer Context level. The PGW shall apply the same behavior if the Modify Bearer Request received at the PGW includes the Bearer Contexts to be modified IE;
- 4) When a SGW receives a Modify Access Bearer Request, where one or more dedicated bearer context(s) is missing in the request message in comparison to the Bearer Context(s) stored for all the UE's PDN connections, the SGW shall delete the corresponding bearer context(s) locally;

- 5) When a SGW receives a Modify Access Bearer Request, where only one or more dedicated bearer context(s) is unknown, the SGW shall accept the Modify Access Bearer Request message partially and set the cause code "Context Not Found" for those unknown bearer context(s) at Bearer Context level.
- NOTE: It is assumed the PGW can at least use a subsequent Modify Bearer Request to resolve Bearer Context mismatch, so that the SGW need not send explicit message to delete unknown Bearer Context.

## 14.3.2 Exceptional scenarios

During a dedicated bearer creation procedure, temporary Bearer Context mismatch may occur at the SGW, e.g. due to the collision between Create Bearer Request and Modify (Access) Bearer Request messages. Applying the general requirements of subclause 14.3.1 may in such case lead to unnecessary signalling and cause extra latency. The SGW should handle such Bearer Context mismatch in an implementation specific way, but in such a way to accept the Modify (Access) Bearer Request message and to not locally delete the missing Bearer Context.

During a Network Triggered Service Request procedure, which is triggered by a dedicated bearer creation procedure towards a UE in Idle mode, the MME shall include only the existing Bearer Contexts (not the new Bearer Contexts just created) in the corresponding Modify (Access) Bearer Request message. The same principle shall apply when piggybacking is used, i.e. when the Modify Bearer Request is piggybacked in the Create Bearer Response message, the MME shall include only the existing Bearer Contexts just created) in the corresponding Modify (Access) Bearer Request is piggybacked in the Create Bearer Response message, the MME shall include only the existing Bearer Contexts (not the new Bearer Contexts just created) in the corresponding Modify (Access) Bearer Request message.

NOTE: During a Network Triggered Service Request procedure, which is triggered by a dedicated bearer creation procedure towards a UE in Idle mode, bearer mismatches can be avoided by the MME sending the Create Bearer Response only after it receives the Modify Bearer Response message, however in some rare cases, the signalling can be delayed for the UE, e.g. if the Modify Bearer Response is lost.

# Annex A (Informative): Backward Compatibility Guidelines for Information Elements

In order to preserve backward compatibility, the following rules should apply when adding or modifying information elements for existing messages.

- No new mandatory (M) information elements should be added.
- No new conditional (C) information elements should be added.
- Any new IEs should be either:

optional (O), having no conditions on their presence, or

conditional-optional (CO), having conditions that should apply only to the sender and not to the receiver.

Such conditions should be worded generally as follows: "This IE shall be sent over the xxx interface <condition>. The receiving entity need not check the IE's presence."

- If any new conditions are added to a previously specified conditional (C) information element, these new conditions should apply only to the sender and not to the receiver.

Such additional conditions should be worded generally as follows: "This IE shall be sent over the xxx interface <condition>. For this optional condition, the receiving entity need not check the IE's presence."

Existing conditions for such conditional (C) IEs should be treated as before, and the presence of the IEs should remain conditional (C).

# Annex B (Informative): Transparent copying of RANAP/S1AP IEs into GTP IEs

# B.1 General

This annex provides details on how a GTPv2 entity transparently copies information received from RANAP or S1AP into GTPv2 IE or IE field.

RANAP and S1AP ASN.1 encoding details in this annex are informative. The reference specifications are 3GPP TS 25.413 [33] and 3GPP TS 36.413 [10] respectively.

The respective RANAP/S1AP Information Elements are transported on the Iu/S1 interface within a "protocol-IE container" which is composed of:

- an Information Element Identity (referred to below as "IE-ID"),
- an indication how the receiver shall react if the Information Element is not comprehended (referred to below as "criticality"),
- and an "open type field" which consists of a length indication ("OT-LI") and the Information Element itself (referred to below as "IE").

RANAP/S1AP PDUs and the contained IEs are defined by means of ASN.1, the specified encoding is PER (packed encoding rule), Octet aligned variant:

- PER minimises the information sent on the respective interface to the absolute minimum;
- Hence, type definitions of fixed length are encoded without any type or length indication, only type definitions of variable length contain a length indication, e.g.
  - an OCTET STRING with indefinite length would need to contain a length indication (referred to below as "OCT-LI") followed by the actual octets (referred to below as "octets");
  - a SEQUENCE neither contains a type, nor a length-indication. Only in case of optional elements it contains a kind of bit string with each position of this bitstring indicating the presence of an OPTIONAL element (an encoded SEQUENCE type is referred to below as "sequence").

## B.2 Handover/Relocation related generic transparent Containers over RANAP, S1-AP and GTP

Handover/Relocation related generic transparent containers are defined in 3GPP TS 25.413 [33] and 3GPP TS 36.413 [10] ("Source to Target Transparent Container" IE and "Target to Source Transparent Container" IE) to carry UTRAN, E-UTRAN or GERAN specific information via CN interfaces in a RAT-agnostic way.

The encoding of these handover/relocation related generic transparent containers is different in RANAP and S1-AP. See 3GPP TS 36.413 [10] Annex C. The difference is that the "Source to Target Transparent Container" IE and "Target to Source Transparent Container" IE are ASN.1 encoded over RANAP as "IE-ID||criticality||OT-LI||octets" (i.e. one length field only for the open type field) and over S1AP as "IE-ID||criticality||OT-LI||octets" (i.e. with 2 length fields, one for the open type field ("OT-LI"), one for the octet string encoding ("OCT-LI")), while "octets" contain the actual RAT specific handover/relocation information.

This gives the following chain of encodings (represented in the notation introduced in the Notes above) end-to-end.

### LTE to LTE

#### ETSI TS 129 274 V14.7.0 (2018-04)





Figure B.2-1: LTE to LTE - Encoding of Generic Transparent Containers

In the case of LTE-LTE handover, the "octets" contain the "Source eNB to Target eNB Transparent Container" (defined as an ASN.1 SEQUENCE in 3GPP TS 36.413[10]).

The source MME, after decoding the HO REQUIRED message of S1AP, passes transparently the "sequence" to the target MME.

The target MME encodes similarly at target side with the same definitions: it feeds the received "sequence" into the S1AP ASN.1 encoder in order to encode the HO REQUEST message towards the target eNB. The "sequence" is then extracted from the S1AP ASN.1 of eNB and given to application part of eNB.

#### LTE to 3G



#### Figure B.2-2: LTE to 3G - Encoding of Generic Transparent Containers

At source side, the same encoding is done but for LTE to 3G handover, this time the "octets" on the line is the "Source RNC to Target RNC Transparent Container" (encoded according to the target system RANAP i.e. as an ASN.1 SEQUENCE in 3GPP TS 25.413 [33]).

Again the source MME passes transparently the "sequence" to the target MME i.e. the "Source RNC to Target RNC Transparent Container".

At the target side, the RANAP RELOCATION REQUEST message was not upgraded: the "sequence" received from the Gn or S3 interface ("Source RNC to Target RNC Transparent Container") is not encoded as an OCTET STRING as on S1, but directly represent the "Source To Target Transparent Container" within the RANAP:RELOCATION REQUEST message, which in case of inter-RAT handover to 3G represent the "Source RNC to Target RNC Transparent Container", transported on the Iu interface as the "IE" part of the "IE container". There is no additional length field added as on the S1 interface ("OCT-LI").

The target side remains therefore fully backwards compatible with UMTS release 7.

#### 3G to LTE




Figure B.2-3: 3G to LTE - Encoding of Generic Transparent Containers

The RELOCATION REQUIRED message was upgraded from release 8 onwards renaming the previously contained "Source RNC to Target RNC Transparent Container" to "Source to Target Transparent Container", being able to transport also a "Source eNB to Target eNB Transparent Container".

Despite being defined as an octet string, in order to not impact the R7 SGSN, the octet string was specified as "to be replaced" by either the UTRAN or E-UTRAN specific container. This fact is explained e.g. within the NOTE in the ASN.1 of 3GPP TS 25.413 [33], as shown in this excerpt:

Source-ToTarget-TransparentContainer ::= OCTET STRING -- This IE is a transparent container, the IE shall be encoded not as an OCTET STRING but according to the type specifications of the target system. -- Note: In the current version of this specification, this IE may either carry the Source RNC to -- Target RNC Transparent Container or the Source eNB to Target eNB Transparent Container IE as -- defined in [49]

By so doing, the Release 7 source SGSN receives only one length field (the "OT-LI") instead of two (the "OT-LI and the "OCT-LI") as if it would receive an "Source RNC to Target RNC Transparent Container" from a Release 7 RNC, ensuring fully Release 7 backwards compatibility as requested by 3GPP TS 23.401 [3] Annex D. This is illustrated in Figure B.1-3 above.

As explained above, this Release 7 backwards compatibility constraint only applies to RANAP to cope with Release 7 SGSN nodes and does NOT apply to LTE. This is why the note is NOT present in the ASN.1 of 3GPP TS 36.413 [10] for LTE i.e. the S1AP octet string does not need "to be replaced".

Then "sequence" is passed transparently to the target MME. The target MME encodes the "sequence" within an OCTET STRING resulting in two length fields as expected by target eNB ASN.1 S1AP decoder.

# B.3 Other RANAP and S1-AP IEs

When transparently copying a RANAP/S1AP IE, other than the handover/relocation related generic transparent containers (see Annex B.1) into GTP IE, or GTP IE field the following applies:

- a transparent copy of a RANAP/S1AP IE, which is transported on the Iu/S1 interface within a "protocol-IE container", neither includes the Information Element Identity ("IE-ID") nor the "criticality" nor the open type field related length indication ("OT-LI"), but only the Information Element itself ("IE").
- "IE" refers to all parts of the encoded type of the Information Element, i.e. including also any related length indication (in case of types with variable length) and preamble (see ITU-T X.691 [49] for the definition of the term "preamble").

# Annex C (Normative): MME/S4-SGSN mapping table between S11/S4 and NAS Cause values

The MME/S4-SGSN initiates session management requests towards the SGW and PGW or mobility management requests towards the source/target MME/S4-SGSN. If this operation is not successful, there are several possible cause codes, which need to be mapped to the appropriate cause codes over NAS to the UE.

Additionally, the MME/S4-SGSN initiates session management requests towards the UE. If this operation is not successful, there are several possible NAS cause codes which need to be mapped to the appropriate GTP cause codes over S11/S4 interface towards the SGW.

The MME/S4-SGSN should map these cause codes as defined in tables C.1 to C.5 unless specified otherwise in the tables.

Table C.1: Mapping from S11/S4 to NAS Cause values – Rejection indication from SGW

Reject indication from SGW to	NAS ESM Cause to UE	SM Cause to UE
MME/S4-SGSN over S11/S4	(NOTE 1, NOTE 2, NOTE 3)	(NOTE 1, NOTE 2, NOTE 3)
#64 "Context not found" (during UE initiated PDN connectivity request for non-3GPP to 3GPP handover procedure)	#54 "PDN connection does not exist"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #31 "Activation rejected, unspecified"
#64 "Context not found" (during all other procedures)	#30 "Request rejected by Serving GW or PDN GW"#38 "Network failure" #43 "Invalid EPS bearer identity"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure" #43 "Unknown PDP Context"
#65 Invalid Message Format	#30 "Request rejected by Serving GW or PDN GW" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#66 "Version not supported by next peer"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#67 "Invalid length"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#68 "Service not supported"	#32 "Service option not supported"	#32 "Service option not supported"
#69 "Mandatory IE incorrect"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#70 "Mandatory IE missing"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#72 "System Failure"	<ul> <li>#34 "Service option temporarily out of order"</li> <li>#38 "Network Failure"</li> <li>#30 "Request rejected by Serving GW or PDN GW"</li> </ul>	<ul> <li>#34 "Service option temporarily out of order"</li> <li>#38 "Network failure"</li> <li>#30 "Activation rejected by GGSN, Serving GW or PDN GW"</li> </ul>
#73 "No Resources available"	#34 "Service option temporarily out of order" #26 "Insufficient resources"	#34 "Service option temporarily out of order" #26 "Insufficient resources"
#76 "Semantic errors in packet filter(s)"	#44 "Semantic errors in packet filter(s)"	#44 "Semantic errors in packet filter(s)"
#77 "Syntactic errors in packet filter(s)"	#45 "Syntactical error in packet filter(s)"	#45 "Syntactical error in packet filter(s)"
#78 "Missing or unknown APN"	# 27 "Missing or unknown APN"	# 27 "Missing or unknown APN"
#80 "GRE key not found"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network Failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#83 "Preferred PDN type not supported"	#32 "Service option not supported" #50 "PDN type IPv4 only allowed" #51 "PDN type IPv6 only allowed"	#32 "Service option not supported" #50 "PDP type IPv4 only allowed" #51 "PDP type IPv6 only allowed"
#84 "All dynamic addresses are occupied"	#26 "Insufficient resources"	#26 "Insufficient resources"
#85 "UE context without TFT already activated"	NA	#46 "PDP context without TFT already activated"
#86 "Protocol type not supported"	#30 "Request rejected by Serving GW or PDN GW" #38 "Network Failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #38 "Network failure"
#89 "Service denied"	#30 "Request rejected by Serving GW or PDN GW" #31 "Request rejected, unspecified" #38 "Network failure"	#30 "Activation rejected by GGSN, Serving GW or PDN GW" #31 "Activation rejected, unspecified" #38 "Network failure"
#91 "No memory available"	#34 "Service option temporarily out of order"	#34 "Service option temporarily out of order"
#92 "User authentication failed"	#26 "Insufficient resources" #29 "User authentication failed" NOTE	#26 "Insufficient resources" #29 "User authentication failed"
#93 "APN access denied – no subscription"	#33 "Requested service option not subscribed" # 27 "Missing or unknown APN"	#33 "Requested service option not subscribed" # 27 "Missing or unknown APN"

#30 "Request rejected by Serving GW	#30 "Activation rejected by GGSN,
or PDN GW"	Serving GW or PDN GW"
#38 "Network Failure"	#38 "Network failure"
#41 "Semantic error in the TFT	#41 "Semantic error in the TFT
operation"	operation"
#42 "Syntactical error in the TFT	#42 "Syntactical error in the TFT
operation"	operation"
#34 "Service option temporarily out of	#34 "Service option temporarily out of
order"	order"
#38 "Network Failure"	#38 "Network failure"
#56 "Collision with network initiated	#56 "Collision with network initiated
request"	request"
	#30 "Activation rejected by GGSN,
or PDN GW"	Serving GW or PDN GW"
#38 "Network Failure"	#38 "Network failure"
#112 "APN restriction value	#112 "APN restriction value
incompatible with active EPS bearer	incompatible with active PDP context"
context"	
	#30 "Activation rejected by GGSN,
	Serving GW or PDN GW"
	#31 "Activation rejected, unspecified"
	#30 "Activation rejected by GGSN,
or PDN GW"	Serving GW or PDN GW"
#38 "Network Failure"	#38 "Network failure"
#26 "Insufficient resources"	#26 "Insufficient resources"
#60 "Bearer handling not supported"	#60 "Bearer handling not supported"
#55 "Multiple PDN connections for a	#30 "Activation rejected by GGSN,
given APN not allowed"	Serving GW or PDN GW"
	#31 "Activation rejected, unspecified"
#113 "Multiple accesses to a PDN	#113 "Multiple accesses to a PDN
connection not allowed"	connection not allowed"
	or PDN GW" #38 "Network Failure" #41 "Semantic error in the TFT operation" #42 "Syntactical error in the TFT operation" #34 "Service option temporarily out of order" #38 "Network Failure" #56 "Collision with network initiated request" #30 "Request rejected by Serving GW or PDN GW" #38 "Network Failure" #112 "APN restriction value incompatible with active EPS bearer context" #30 "Request rejected by Serving GW or PDN GW" #31 "Request rejected by Serving GW or PDN GW" #31 "Request rejected by Serving GW or PDN GW" #33 "Network Failure" #60 "Bearer handling not supported" #55 "Multiple PDN connections for a given APN not allowed"

NOTE 1: See 3GPP TS 24.301 [23] and 3GPP TS 24.008 [5] for NAS ESM and SM causes respectively.
 NOTE 2: The MME/S4-SGSN may for certain GTP cause codes trigger a new GTP procedure instead of rejecting the NAS request.

NOTE 3: When multiple NAS Cause values are defined for a given GTP cause value, any of those NAS Cause values may be sent to the UE based on implementation choice.

NOTE: The MME can send the EMM cause set to #15 "No suitable cells in tracking area" to the UE, if the PDN connectivity request is rejected due to the ESM cause #29, which is mapped from the GTPv2 cause code #92 or XXX, based on operator policies. See 3GPP TS 24.301 [23]. This enables a roamer to get service in a VPLMN even when being rejected via LTE access due to e.g. no credit authorisation from the OCS.

Table C.2: Mapping from S11/S4 to NAS Cause values – Acceptance indicati	on from SGW

Acceptance indication from SGW to MME/S4-SGN over S11/S4	NAS ESM Cause to UE	SM Cause to UE	
#18 "New PDN type due to network preference"	#50 "PDN type IPv4 only allowed" #51 "PDN type IPv6 only allowed" (NOTE 1)	#50 "PDP type IPv4 only allowed" #51 "PDP type IPv6 only allowed" (NOTE 1)	
#19 "New PDN type due to single address bearer only"#52 "single address bearers only allowed"#52 "single address bearers only allowed"NOTE 1: The actual NAS cause sent to the UE depends on the allocated IP address type.			

## Table C.3: Mapping from S11/S4 to NAS Cause values – Indication in request from SGW

Indication in a request / initial message from SGW to MME/S4- SGSN over S11/S4	NAS ESM Cause to UE	SM Cause to UE
#8 "Reactivation Requested" (NOTE 1)	Shall be mapped to: #39 "Reactivation requested" in the NAS bearer context deactivation procedure. For the last PDN connection in E- UTRAN, "Reactivation requested" shall be mapped to "re-attach required" in the NAS detach type IE.	Shall be mapped to: #39 "Reactivation requested" in the NAS bearer context deactivation procedure.
#9 "PDN reconnection to this APN disallowed" (NOTE 1)	Implementation specific NAS cause value indicating to the UE that the APN is not currently available. For the last PDN connection, NAS detach type IE should be set to "re- attach not required".	Implementation specific NAS cause value indicating to the UE that the APN is not currently available.

### Table C.4: Mapping from NAS to S11/S4 Cause values – Rejection indication from MME/S4-SGSN

NAS ESM Cause from UE (NOTE 1)	SM Cause from UE (NOTE 1)	Reject indication from MME/S4- SGSN to SGW over S11/S4 (NOTE 2)
#26 "Insufficient Resources"	#26 "Insufficient Resources"	#73 "No Resources available" #88 "UE refuses"
#31 "Request rejected, unspecified"	#31 "Activation rejected, unspecified"	#94 "Request rejected" #88 "UE refuses"
#41 "Semantic error in the TFT operation"	#41 "Semantic error in the TFT operation"	#74 "Semantic error in the TFT operation"
#42 "Syntactical error in the TFT operation"	#42 "Syntactical error in the TFT operation"	#75 "Syntactical error in the TFT operation"
#43 "Invalid EPS bearer identity"	#43 "Unknown PDP Context"	#64 "Context not found" #88 "UE refuses"
#44 "Semantic errors in packet filter(s)"	#44 "Semantic errors in packet filter(s)"	#76 "Semantic errors in packet filter(s)"
#45 "Syntactical error in packet filter(s)"	#45 "Syntactical error in packet filter(s)"	#77 "Syntactical error in packet filter(s)"
#47 "PTI mismatch"	NA	#94 "Request rejected" #88 "UE refuses"
NA	#48 "Request rejected, Bearer Control Mode violation"	#94 "Request rejected" #88 "UE refuses"
#81 "Invalid PTI value"	NA	#94 "Request rejected" #88 "UE refuses"
NOTE 2: When multiple GTPv2 Caus	and 3GPP TS 24.008 [5] for NAS ESM ar se values are defined for a given NAS Ca SGW based on implementation choice.	

Table C.5: Mapping from S3/S16 to NAS Cause values – Reje	ection indication from MME/S4-SGSN

Reject indication from MME/S4- SGSN to MME/S4-SGSN over S3/S16	NAS ESM Cause to UE (NOTE 1, NOTE 2)	SM Cause to UE (NOTE 1, NOTE 2)	
#117 "Target access restricted for the subscriber"	<ul> <li>#15 "No suitable cells in tracking area", or</li> <li>#13 "Roaming not allowed in this tracking area", or</li> <li>#12 "Tracking area not allowed"</li> </ul>	<ul><li>#15 "No suitable cells in tracking area", or</li><li>#13 "Roaming not allowed in this tracking area", or</li><li>#12 "Tracking area not allowed"</li></ul>	
<ul> <li>NOTE 1: See 3GPP TS 24.301 [23] and 3GPP TS 24.008 [5] for NAS ESM and SM causes respectively.</li> <li>NOTE 2: When multiple NAS Cause values are defined for a given GTP cause value, any of those NAS Cause values may be sent to the UE based on implementation choice.</li> </ul>			

# Annex D (Informative): GTP-C load and overload control mechanism

# D.1 GTP-C interfaces not supporting Load Control

Load Control has been designed as a generic mechanism possibly applicable to any GTP-C node. However, for the reasons clarified below, in the current release, Load Control is not supported for the following GTP-C based interfaces:

- S3, S10, S16 (limited GTP-C signalling traffic, to minimize impact to the MME/S4-SGSN);
- Sm, Sn (limited GTP-C signalling traffic, to avoid impact to the MBMS GW);
- Sv (limited GTP-C signalling traffic, to avoid impact to the legacy CS products);
- S101, S121 (to avoid impacts to the legacy HRPD products);
- Gn/Gp (to avoid impact to the legacy Gn-SGSN/GGSN products and GTPv1-C protocol).

# D.2 GTP-C interfaces not supporting Overload Control

Overload Control has been designed as a generic mechanism possibly applicable to any GTP-C based interface and any direction. However for the reasons clarified below, in the current release, Overload Control is not supported for the following GTP-C based interfaces:

- S3, S10, S16 (see considerations below, to minimize impact to MME and S4-SGSN);
  - most of the S3 traffic would remain internal to the combo-node with the deployment of combo-MME/S4-SGSN nodes. The traffic over S10/S16 is also reduced with the deployment of MME and SGSN pools. It is therefore not essential to throttle the traffic on these interfaces when an MME or S4-SGSN experiences overload;
  - throttling signalling on these interfaces resulting from a user's mobility (inter-MME/S4-SGSN TAU, RAU and Handover) would result in bad end user's perception (handover failure, loss of PDN connections) and so needs to be avoided as far as possible;
  - an MME or S4-SGSN in overload may drop locally incoming RIM messages without causing GTP-C retransmissions (although this may cause the RAN to retransmit the message).
- S11/S4 (from an MME/S4-SGSN to an SGW, with SGW as consumer; see consideration below);
  - by allowing the SGW to throttle DDN requests for normal priority traffic, the overload control of the messages originated by the SGW towards the MME/S4-SGSN is covered and hence, an SGW performing overload control towards the MME/S4-SGSN using Overload Control Information would be redundant.
- S5/S8 (from a PGW to an SGW, with the SGW as a consumer; no signalling message, originated by the SGW towards the PGW, that is identified as requiring overload control);
- Sm, Sn (no overload scenario identified, limited GTP-C traffic, to avoid impact to the MBMS GW);
- Sv (no overload scenario identified, to avoid impact to the legacy CS products);
- S101, S121 (no overload scenario identified, to avoid impact to the legacy HRPD products);
- Gn/Gp (to avoid impact to the legacy Gn-SGSN/GGSN products and GTPv1-C protocol);

# D.3 "Loss" throttling algorithm

## D.3.1 Example of possible implementation

This subclause provides an example of a possible implementation of the "Loss" algorithm, amongst other possible methods.

It is possible to make use of a statistical loss function (e.g., random selection of messages to throttle based on the indicated percentage) to decide if the given message can be sent or need to be throttled. For example, the source node generates a random number between (0, 100) for each message which is a potential candidate for throttling. To realize 10% throttling, messages with a random number 10 or less are throttled and hence this achieves approximately a 10% reduction in the overall traffic. The actual traffic reduction might vary slightly from the requested percentage, albeit by an insignificant amount.

The algorithm can select certain messages to throttle in priority. For example, implementations can distinguish between higher-priority and lower-priority messages, and drop the lower-priority messages in favour of dropping the higher priority messages, as long as the total reduction in traffic conforms to the requested reduction in effect at the time. For example, in the 50-50 distribution of high priority and low priority messages, 20% reduction to low priority messages and 0% reduction to high priority messages need to be applied in order to achieve the effective reduction in traffic by 10% towards the overloaded node.

# D.4 Enforcement of overload control between remote GTP-C entities

## D.4.1 Example of possible implementation

This subclause provides an example of a possible implementation of the enforcement of overload control between remote GTP-C entities, amongst other possible methods, considering the example network topology described in Figure D.4.1-1.




Figure D.4.1-1: Example network topology

The source GTP-C entity can apply message throttling according to the maximum of the overload reduction metric reported by the intermediate and target GTP-C entities, i.e. max (Intermediate_Overload-Metric, Target_Overload-Metric), for each of the path between the source and the target GTP-C entities. Each path is considered independently whilst performing the message throttling.

Considering the following example overload condition for the topology above:

Target_Overload-Metric = 30%

IntermediateA_Overload-Metric = 10%

391

## $IntermediateB_Overload-Metric = 20\%$

IntermediateC_Overload-Metric = 40%

Target_Terminated-Messages = 100

IntermediateA-Target_Messages = 20

IntermediateB-Target_Messages = 50

IntermediateC-Target_Messages = 30

the source GTP-C entity applies message throttling as follows:

Source-IntermediateA_Messages = 14 (message throttling of 30% applied)

Source-IntermediateB_Messages = 35 (message throttling of 30% applied)

Source-IntermediateC_Messages = 18 (message throttling of 40% applied)

Source-Target_Messages = 67 (the Target GTP-C entity receives 67 messages although it could have handled 70 messages in the overloaded condition).

# Annex E (Normative): TWAN mapping table between GTPv2 S2a Cause and non-3GPP access Cause values

The TWAN initiates session establishment requests or mobility management requests towards the PGW. If this operation is not successful, there are several possible cause codes, which need to be mapped to the appropriate cause codes over non-3GPP access to the UE.

The TWAN should map these cause codes as defined in Table E.1, Table E.2, Table E.3 and Table E.4.

Table E.1: Mapping from GTPv2 S2a to non-3GPP access Cause values – Rejection indication from PGW

Reject indication from PGW to TWAN over S2a	WLCP Cause to UE for MCM	Diameter Cause to 3GPP AAA Server for SCM
#64 "Context not found" (during UE initiated PDN connectivity request for 3GPP to non-3GPP handover procedure)	#54 "PDN connection does not exist"	#54 "PDN connection does not exist"
#65 Invalid Message Format	#30 "Request rejected by PDN GW" #38 "Network failure"	#30 "Request rejected by PDN GW" #38 "Network failure"
#67 "Invalid length"	#30 "Request rejected by PDN GW" #38 "Network failure"	#30 "Request rejected by PDN GW" #38 "Network failure"
#68 "Service not supported"	#32 "Service option not supported"	#32 "Service option not supported"
#69 "Mandatory IE incorrect"	#30 "Request rejected by PDN GW" #38 "Network failure"	#30 "Request rejected by PDN GW" #38 "Network failure"
#70 "Mandatory IE missing"	#30 "Request rejected by PDN GW" #38 "Network failure"	#30 "Request rejected by PDN GW" #38 "Network failure"
#72 "System Failure"	#34 "Service option temporarily out of order" #38 "Network Failure" #30 "Request rejected by PDN GW"	#34 "Service option temporarily out of order" #38 "Network Failure" #30 "Request rejected by PDN GW"
#73 "No Resources available"	#34 "Service option temporarily out of order" #26 "Insufficient resources"	#34 "Service option temporarily out of order" #26 "Insufficient resources"
#78 "Missing or unknown APN"	# 27 "Missing or unknown APN"	# 27 "unknown APN"
#83 "Preferred PDN type not supported"	#32 "Service option not supported" #50 "PDN type IPv4 only allowed" #51 "PDN type IPv6 only allowed"	#32 "Service option not supported" #50 "PDN type IPv4 only allowed" #51 "PDN type IPv6 only allowed"
#84 "All dynamic addresses are occupied"	#26 "Insufficient resources"	#26 "Insufficient resources"
#89 "Service denied"	#30 "Request rejected by PDN GW" #31 "Request rejected, unspecified" #38 "Network failure"	#30 "Request rejected by PDN GW" #31 "Request rejected, unspecified" #38 "Network failure"
#91 "No memory available"	#34 "Service option temporarily out of order" #26 "Insufficient resources"	#34 "Service option temporarily out of order" #26 "Insufficient resources"
#92 "User authentication failed" #93 "APN access denied –	#92 "User authentication failed"	#92 "User authentication failed"
no subscription"	#33 "Requested service option not subscribed" # 27 "Missing or unknown APN"	#33 "Requested service option not subscribed" # 27 "unknown APN"
#94 "Request rejected (reason not specified)"	#30 "Request rejected by PDN GW" #38 "Network Failure"	#30 "Request rejected by PDN GW" #38 "Network Failure"
#100 "Remote peer not responding"	#34 "Service option temporarily out of order" #38 "Network Failure"	#34 "Service option temporarily out of order" #38 "Network Failure"
#101 "Collision with network initiated request"	#31 "Request rejected, unspecified"	NA
#103 "Conditional IE missing"	#30 "Request rejected by PDN GW" #38 "Network Failure"	#30 "Request rejected by PDN GW" #38 "Network Failure"

#113 "APN Congestion" #120 "GTP-C Entity Congestion"	#26 "Insufficient resources"	#26 "Insufficient resources"	
#116 "Multiple PDN connections for a given APN not allowed"	#55 "Multiple PDN connections for a given APN not allowed"	NA	
#126 "Multiple accesses to a PDN connection not allowed"	#113 "Multiple accesses to a PDN connection not allowed"	#113 "Multiple accesses to a PDN connection not allowed"	
<ul> <li>NOTE 1: See 3GPP TS 24.244 [66] for WLCP causes.</li> <li>NOTE 2: When multiple non-3GPP access cause values are defined for a given GTP cause value, any of those cause values may be sent to the UE based on implementation choice.</li> </ul>			

# Table E.2: Mapping from GTPv2 S2a to non-3GPP access Cause values – Acceptance indication from PGW

Acceptance indication from PGW to TWAN over S2a	WLCP Cause to UE for MCM	Diameter Cause to 3GPP AAA Server for SCM
#18 "New PDN type due to network preference"	#50 "PDN type IPv4 only allowed" #51 "PDN type IPv6 only allowed"	NA
#19 "New PDN type due to single address bearer only"	#52 "single address bearers only allowed"	NA
NOTE 1: The actual WLCP cause sent to the UE depends on the allocated IP address type.		

## Table E.3: Mapping from GTPv2 S2a to WLCP Cause values – Indication in request from PGW

Indication in disconnection message from PGW to TWAN over S2a	WLCP Cause to UE for MCM	
#8 "Reactivation Requested"	#39 "Reactivation requested"	
#9 "PDN reconnection to this APN	Implementation specific WLCP cause	
disallowed"	value indicating to the UE that the	
(NOTE 1)	APN is not currently available.	
NOTE 1: In Delete Bearer Request during the PGW initiated bearer		
deactivation procedure for the default bearer		

## Table E.4: Mapping from WLCP to GTP Cause values – Rejection indication from TWAN

WLCP Cause from UE	Reject indication from TWAN to PGW	
#31 "request rejected, unspecified"	#94 "Request rejected"	
	#88 "UE refuses"	
NOTE 1: See 3GPP TS 24.244 [66] for WLCP causes.		
NOTE 2: When multiple GTPv2 Cause values are defined for a given WLCP		
Cause value, any of those GTPv2 Cause values may be sent to the		
PGW based on implementation choice.		

396

Annex F (Informative): Change History

2009-03         CT#43         CP-09005         0001         1         Relocation Cancel ReqRes         8.0.0         8.1.0           2009-03         CT#43         CP-09005         0005         4         Sections 1 through E ditorial Clean-up         8.0.0         8.1.0           2009-03         CT#43         CP-09005         0006         2         Detete Session and Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-09005         0007         2         Cleanup in path management and bearer ormmand messages         8.0.0         8.1.0           2009-03         CT#43         CP-09005         0018         1         Contact Session/Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0012         1         Contact Session/Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0025         1         Deomrink Data Notification         8.0.0	Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2029-03         CT443         CP-80050         0.003         1         Relocation Cancel Reg/Res         8.0.0         8.1.0           2029-03         CT443         CP-80050         0.006         2         Delter Baire         8.0.0         8.1.0           2029-03         CT443         CP-80050         0.006         2         Delter Session and Delter Bearer messages         8.0.0         8.1.0           2029-03         CT443         CP-80050         0.006         2         Update User Message         8.0.0         8.1.0           2029-04         CT443         CP-80050         0.011         1         Creation Session Session         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0<	2008-12	CT#42	CP-080717			V2.0.0 approved in CT#42	2.0.0	8.0.0
2009-33         CT#43         CP-90050         0004         2         Path Failure         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0006         4         Bectors Intrough E Editorial Clean-up         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0006         2         Update User Plane messages         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0118         1         Create Session/Bearer Messages         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0118         1         Coreta Session/Bearer Messages         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0212         1         Cormmand Messages         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0221         1         Cormmand Messages         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0261         Downin Potentian         8.0.0         8.1.0           2009-33         CT#43         CP-90050         0272         Scondary PDP Activation         8.0.0         8.1.0           2009-33         CT#43         CP-900500					2			
2009-03         CT#43         CP-000050         00065         2         Betornal Through E Editorial Clean-up         8.0.0         8.1.0           2009-03         CT#43         CP-000050         00068         2         Update Laser Plane messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0118         1         Create Session and Decarre messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         01019         1         Control Network         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         1         Control Network         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         1         Control Network         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         1         Doutinin Data Maifaction         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         1         Doutinin Data Maifaction         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0024         1         Doutinin Data Maifaction         8.0.0         8.1.0           2009-03								
2009-03         CT#43         CP-09005         006         2         Deterts Session and Deterts Bearer messages         8.00         8.1.0           2009-03         CT#43         CP-09005         0018         1         Creates Session/Bearer Messages         8.00         8.1.0           2009-03         CT#43         CP-090050         0018         1         Creates Session/Bearer Messages         8.00         8.1.0           2009-03         CT#43         CP-090050         0022         1         Is OSF related messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Detete Bearer ID         8.0.0         8.1.0           2009-0							8.0.0	
2009-03         CT#43         CP-000050         0071         2         Lickarup in path management and baarer command messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0071         2         Cienarup in path management and baarer command messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0071         2         Tierater Session/Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0021         1         Command Messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         3         Data Forwarding Info         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         1         Deteles Session messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         2         Socordary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0022         2         Socordary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0032         1         LP-Keuteintin         Rocon         8.1.0								
2009-03         CT#43         CP-000050         0018         1         Create Session/Bearr Messages         8.0.0         6.1.0           2009-03         CT#43         CP-000050         0018         1         Constance Messages         8.0.0         6.1.0           2009-03         CT#43         CP-000050         0022         1         Ext or CSF Prelated messages         8.0.0         6.1.0           2009-03         CT#43         CP-000050         0022         1         Command Messages         8.0.0         6.1.0           2009-03         CT#43         CP-000050         0022         3         Delete Bearr messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0026         2         Delete Bearr messages         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0026         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0026         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-000050         0026         2         Secondary PDP Activation         8.0.0         8.1.0          2         Secondary PDP Act								
2009-03         CT#43         CP-090056         0019         2         Modif Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090056         0021         1         Command Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090056         00221         3         Data Forwarding Info         8.0.0         8.1.0           2009-03         CT#43         CP-090056         00223         3         Data Forwarding Info         8.0.0         8.1.0           2009-03         CT#43         CP-090056         0024         2         Deteles Seasion messages         8.0.0         8.1.0           2009-03         CT#43         CP-090056         0025         1         Ownink Data Notfication         8.0.0         8.1.0           2009-03         CT#43         CP-090056         00267         2         Stop Paging         8.0.0         8.1.0           2009-03         CT#43         CP-090056         0023         1         EPE Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090056         0034         1         AdtR IE encoding         8.0.0         8.1.0           2009-03         CT#43								
2009-03         CT#43         CP-090050         0021         2         Modriy Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00221         1         Command Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00223         3         Delete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00242         2         Delete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00252         1         Downink Data Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00262         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00272         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00242         1         FETEE IE I								
2009-03         CT#43         CP-090050         0021         1         Command Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Data Forwarding Info         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         3         Data Forwarding Info         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0024         2         Delete Season messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0025         1         Downink Data Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00262         2         Scondary PDP Advation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00263         2         Linked EPS Bearer ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Advatis Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Forward SNNS Convent Notification         8.0.0         8.1.0           2009-03         CT#43								
2009-03         CT#43         CP-930056         0021         1         Command Messages         6.0.0         8.1.0           2009-03         CT#43         CP-930056         0022         3         Delete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0024         2         Delete Session messages         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0026         1         Downink Data Notification         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0026         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0032         2         Inced EPS Bearer ID         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0032         1         Inced EPS Bearer ID         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0035         -         Attentication         8.0.0         8.1.0           2009-03         CT#43         CP-930056         0044         1         Forward SRNS Context Notification         8.0.0         8.1.0           2009-03         CT#43								
2009-03         CT#43         CP-900050         0023         3         Delete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0024         2         Delete Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0026         1         Downink Dtata Notification         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0026         2         Update Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0027         2         Scondary CPA Activation         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0034         1         AMBR IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-900050         0041         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#44         CP-900050         0041         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#44         CP-900050         0044         1         IF-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#44<								
2009-03         CT#43         CP-000050         0024         Delete Session messages         6.00         6.10           2009-03         CT#43         CP-000050         0026         1         Downlink Data Nutlification         8.00         8.10           2009-03         CT#43         CP-000050         0026         2         Decembersage         8.00         8.10           2009-03         CT#43         CP-000050         0028         2         Econdary PDP Activation         8.00         8.10           2009-03         CT#43         CP-000050         0032         1         EPS Baarer Contexts Printization         8.00         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10         8.10								
2009-03         CT#43         CP-900050         0025         1         0029103         CT#43         CP-900050         0025         1         0029103         CT#43         CP-900050         0026         2         Update Bearer messages         8.0.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.								
2009-03         CT#43         CP-090050         0026         1         Downlink Data Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0027         2         Skondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0028         2         Skondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0033         1         Linked EPS Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         AMtentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Foreid SNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Foreid SNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         EType ordening         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         MM context enhancements         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0027         2         Vpdate Bearer messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0022         2         Stoondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0033         1         EPS Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Authentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0035         -         Authentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Forward SRNS Context Natification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         ET syntamin         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         ET syntamin         8.0.0         8.1.0         8.0.0         8.1.0         8.0.0         8.1.0           2009-03         CT#43 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>								
2009-03         CT#43         CP-090050         0022         2         Secondary PDP Activation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0023         1         EPS Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0033         1         Linked EPS Bearer ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Authentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Freidication         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Forward SRN Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         ET type ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Remove unseel Padres IEs         8.0.0         8.1.0           2009-03								
2009-03         CT#43         CP-090050         0002         I EPS Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0003         1         EPS Bearer Contexts Prioritization         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Authentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0036         -         Authentication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         Forward SRNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Removal or Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0								
2009-03         CT#43         CP-090050         0032         1         EPS Bearer ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         AMBR IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         Anternitication Failure Cause Code         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0040         1         Forward SRNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Forward SRNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         ET type ordening         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0054         1         Remove nuseed IP Address IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Sesion Activation/Deactivation when UE is attacheed         8.0.0         8.1.0 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
2009-03         CT#43         CP-090050         0034         1         AMBR IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0034         1         AMBR IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Remove unsed IP Address IES         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Remove unsed IP Address IES         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Corrections to Trace Information IE         8.0.0         8.1.0         8.0.0								
2079-03         CT#43         CP-090050         0034         1         AMBR IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0040         1         Forward SRNS Context Notification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         ETTED IE clarification recitions         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Imvoration recitions         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Trace Information IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Information IE         8.0.0         8.1.0           2009-03								
2009-03         CT#43         CP-090050         0040         1         F-090050         0040         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0041         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0043         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Indentification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Indentification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Remova in Gearr ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Remova in dwd bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Crarecloses Bearers Requestration Her to be included in S11 and SS/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
2009-03         CT#43         CP-090050         0040         1         Forward SRNS Context Nutification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0043         1         Internification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0054         2         Trace Information IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00561         1         Release Acce								
2009-03         CT#43         CP-090050         0041         1         F-TEID IE clarification         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0043         1         Identification Response algorithm information         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         IE Type ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         IE Type ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Remova IG Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Corrections to Trace Information IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         1         Release Coresp Bearer Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Release Pand 10 clease         8.1.0         8.1.0	2009-03							
2009-03         CT#43         CP-090214         0043         4         SGW Selection during TAU and corrections to Grouped IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         IEType ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         Microatist enhancements         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection dures IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Seison Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0056         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Release Accees Bearers Request/Response         8.0.0								
2009-03         CT#43         CP-090050         0044         2         IE Type ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0044         2         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0046         1         NMC Context enhancements         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Remova IG Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0054         2         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0056         3         Frace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00661         4         Finalizing GTPA2 Ero								
2009-03         CT#43         CP-090050         0044         2         IE Type ordering         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0045         1         MM Context enhancements         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Removal of Medress IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         1         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00664         1         GTP-2/clause 9 and 10 clearup         8.					-			
2009-03         CT#43         CP-090050         0045         2         Indication IE corrections         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Remove unused IP Address IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0054         2         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         1         Reve UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00661         Relazer Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00661         1         GP142 Caror Handing clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00664         1         GP142 Caror Handing clause         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0048         1         MM Context enhancements         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Corrections to Trace Information IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0056         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0								
2009-03         CT#43         CP-090050         0050         1         Removal of Bearer ID List IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Remove unused IP Address IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Sclection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Information IE         to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0051         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         1         GTPv2 clause 9 and 10 cleanup         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         1         GTPv2 clause 9 and 10 cleanup         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer R								
2009-03         CT#43         CP-090050         0051         1         Remove unused IP Address IEs         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0053         1         Corrections to Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Ission Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0059         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0063         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00664         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         3         Location Change Reporting         8								
2009-03         CT#43         CP-090050         0052         1         Selection Mode bits         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0054         1         Corrections to Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0056         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0061         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer AcoS necoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Chan								
2009-03         CT#43         CP-090050         0054         1         Corrections to Trace Information IE         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         3         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0055         1         Trace Session Activation/Deactivation/Deactivation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         00664         1         Finalizing GTP/2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Modify Bearer Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0081         1         Non-3GPP Requests i								
2009-03         CT#43         CP-090050         0054         2         Trace Information IE to be included in S11 and S5/S8 messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0059         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0060         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0063         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         1         Modify Bearer Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup or Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF					1			
2009-03         CT#43         CP-090050         0055         3         Trace Session Activation/Deactivation when UE is attached         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0060         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0061         3         Piggybacking of Dedicated Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0081         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         1         Support for error response for conflictin								
2009-03         CT#43         CP-090050         0059         1         New UE Time Zone IE Type         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0060         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0063         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         1         GTPv2 clause 9 and 10 cleanup         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0080         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support of IP address retrieval for ANRF         8.0.0         8.1.0 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
2009-03         CT#43         CP-090050         0060         1         Release Access Bearers Request/Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         4         Finalizing GTPV2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         4         GTPV2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0								
2009-03         CT#43         CP-090256         0061         3         Piggybacking of Dedicated Bearer Messages         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0064         1         GTPV2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
2009-03         CT#43         CP-090050         0063         4         Finalizing GTPv2 Error Handling clause         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of reror response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTPv2-C message <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
2009-03         CT#43         CP-090050         0064         1         GTPv2 clause 9 and 10 cleanup         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0080         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0084         3         Finalization of Partial fault handling in GTPv2         8.0					-			
2009-03         CT#43         CP-090050         0066         4         RAN Information Relay message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of arget ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Header for the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Header for the GTPv2-C message         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0067         2         Bearer QoS encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0080         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0084         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MISISDN encoding         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0068         1         Modify Bearer Response         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encod								
2009-03         CT#43         CP-090050         0075         3         Location Change Reporting         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0077         2         Cleanup on Cause Values         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0080         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTPv2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.								
2009-03         CT#43         CP-090050         0080         1         Non-3GPP Requests in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         FileD Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1								
2009-03         CT#43         CP-090050         0082         3         Support of IP address retrieval for ANRF         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0083         1         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTP/2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0083         1         Support for error response for conflicting resource request         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0								
2009-03         CT#43         CP-090050         0085         1         Clarification of Target ID vs Cell ID         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTPv2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Tarfic Aggregate Description IE encoding         8.0.0         8.1.0 </td <td>2009-03</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	2009-03							
2009-03         CT#43         CP-090050         0089         2         TEID Value of the GTP header         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTPv2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0109         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0 <tr< td=""><td>2009-03</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr<>	2009-03							
2009-03         CT#43         CP-090050         0093         3         Header for the Format of the GTPv2-C message         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0								
2009-03         CT#43         CP-090050         0094         3         Finalization of Partial fault handling in GTPv2         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03 <td>2009-03</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	2009-03							
2009-03         CT#43         CP-090050         0095         1         MSISDN encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03<								
2009-03         CT#43         CP-090050         0096         1         IMSI encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reinable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>								
2009-03         CT#43         CP-090050         0097         1         PMIP error code reservation         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reinoval of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1								
2009-03         CT#43         CP-090050         0098         -         Removal of Comprehension Required from messages 7.3.1 to 7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-03         -         -         -         Support for new cause code of "Unable to page UE due to CSFB"         <								
2009-03         CT#43         CP-090050         0098         -         7.3.13         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-03         -         -         -         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0	2009-03	CT#43	CP-090050	0097	1		8.0.0	8.1.0
2009-03         CT#43         CP-090050         0099         -         Cause value for PGW not responding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-03         -         -         -         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0107         -         Support for new cause code of "Unable to page UE due to CSFB" <td< td=""><td>0000 55</td><td>oT</td><td>00.000</td><td>0.00</td><td></td><td></td><td></td><td>o · -</td></td<>	0000 55	oT	00.000	0.00				o · -
2009-03         CT#43         CP-090050         0100         -         Traffic Aggregate Description IE encoding         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-04         CT#44         CP-090288         0107         -         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         1         in Downlink Data Notification Acknowledgement.         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address					-			
2009-03         CT#43         CP-090050         0101         3         Protocol Stack         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-06         CT#44         CP-090288         0107         -         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         1         in Downlink Data Notification Acknowledgement.         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0								
2009-03         CT#43         CP-090050         0102         1         Reliable delivery for EPC         8.0.0         8.1.0           2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-06         CT#44         CP-090288         0107         -         Suspend and Resume are also used for 1xRTT CS Fallback         8.1.1         8.2.0           2009-06         CT#44         O108         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         1         in Downlink Data Notification Acknowledgement.         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0								
2009-03         CT#43         CP-090050         0104         -         Removal of reservation for message types of GTP-U         8.0.0         8.1.0           2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0           2009-03         -         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-06         CT#44         CP-090288         0107         -         Suspend and Resume are also used for 1xRTT CS Fallback         8.1.1         8.2.0           2009-06         CT#44         O108         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0								
2009-03         CT#43         CP-090239         0105         1         Essential correction to grouped IE type coding         8.0.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.0         8.1.1         8.1.0         8.1.1         8.1.1         8.1.1         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2.0         8.1.1         8.2								
2009-03         -         -         -         Some of the table formats corrected         8.1.0         8.1.1           2009-06         CT#44         CP-090288         0107         -         Suspend and Resume are also used for 1xRTT CS Fallback         8.1.1         8.2.0           2009-06         CT#44         0108         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         1         In Downlink Data Notification Acknowledgement.         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0								
2009-06         CT#44         CP-090288         0107         -         Suspend and Resume are also used for 1xRTT CS Fallback         8.1.1         8.2.0           2009-06         CT#44         0108         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         0108         Support for new cause code of "Unable to page UE due to CSFB"         8.1.1         8.2.0           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0	2009-03	CT#43	CP-090239	0105				
2009-06       CT#44       0108       Support for new cause code of "Unable to page UE due to CSFB"       8.1.1       8.2.0         2009-06       CT#44       CP-090288       0109       1       Corrections on GTPv2 for 1x IWS IP address       8.1.1       8.2.0		-	-	-	-			
CP-090288         1         in Downlink Data Notification Acknowledgement.         1           2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0	2009-06		CP-090288		-			
2009-06         CT#44         CP-090288         0109         1         Corrections on GTPv2 for 1x IWS IP address         8.1.1         8.2.0	2009-06	CT#44		0108			8.1.1	8.2.0
		07/11						
2009-06   C1#44   CP-090288   0110   1   Clarification of Operation Indication (OI) 8.1.1 8.2.0								
	2009-06	CT#44	CP-090288	0110	1	Clarification of Operation Indication (OI)	8.1.1	8.2.0

2009-06         C1           2009-06         C1 </th <th>T#44       T#44       T#44</th> <th>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</th> <th>0111 0112 0114 0115 0117 0118 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</th> <th>1 1 2 1 1 1 1 1 2 1 1 2 2 2 1 1 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 2 2 1 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 1 2 1 2 2 1 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2</th> <th>Usage of User Location Information (ULI) IE PGW S5/S8 IP Address in Context Response message Delete Indirect Data Forwarding Tunnel Response Error_Handling. Withdrawn PCO Extensions added to messages Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</th> <th>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</th> <th>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.00 8</th>	T#44       T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0111 0112 0114 0115 0117 0118 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	1 1 2 1 1 1 1 1 2 1 1 2 2 2 1 1 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 2 2 1 2 2 2 2 1 1 2 2 2 2 2 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 2 1 1 1 2 2 1 2 1 2 2 1 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Usage of User Location Information (ULI) IE PGW S5/S8 IP Address in Context Response message Delete Indirect Data Forwarding Tunnel Response Error_Handling. Withdrawn PCO Extensions added to messages Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.00 8
2009-06         CT           2009-06         CT </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0114 0115 0117 0118 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</td> <td>1 2 1 1 2 1 1 2 1 2 2 2 1 1 1 2 2 2 1 1 1 2</td> <td>Delete Indirect Data Forwarding Tunnel Response         Error_Handling. Withdrawn         PCO Extensions added to messages         Clarifications to message directions         Removal of specification drafting hints         ISR related alignments         Clarifications to grouped IE usage         Clarification to Recovery IE type         Missing conditions         Clarification of ARP encoding         Units for APN-AMBR         Clarification of Mobile Equipment Identity IE encoding         EPS Bearer Level TFT encoding         UE-initiated procedures with one bearer only         Combine UL and DL TFT IEs         PGW S5/S8 IP Address and TEID for user plane         Transaction Identifier information element         Delete Bearer Request         Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.00 8</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0114 0115 0117 0118 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	1 2 1 1 2 1 1 2 1 2 2 2 1 1 1 2 2 2 1 1 1 2	Delete Indirect Data Forwarding Tunnel Response         Error_Handling. Withdrawn         PCO Extensions added to messages         Clarifications to message directions         Removal of specification drafting hints         ISR related alignments         Clarifications to grouped IE usage         Clarification to Recovery IE type         Missing conditions         Clarification of ARP encoding         Units for APN-AMBR         Clarification of Mobile Equipment Identity IE encoding         EPS Bearer Level TFT encoding         UE-initiated procedures with one bearer only         Combine UL and DL TFT IEs         PGW S5/S8 IP Address and TEID for user plane         Transaction Identifier information element         Delete Bearer Request         Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.00 8
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0115 0117 0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</td> <td>2 1 1 2 1 1 2 - - 2 2 2 1 1 1 2</td> <td>Error_Handling. Withdrawn PCO Extensions added to messages Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.0000000000</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0115 0117 0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	2 1 1 2 1 1 2 - - 2 2 2 1 1 1 2	Error_Handling. Withdrawn PCO Extensions added to messages Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.00 8.2.0000000000
2009-06         C1           2009-06         C1 </td <td>T#44       CT#44       CT#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0117 0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</td> <td>1 - - - - - - - - - - - - -</td> <td>PCO Extensions added to messages         Clarifications to message directions         Removal of specification drafting hints         ISR related alignments         Clarifications to grouped IE usage         Clarification to Recovery IE type         Missing conditions         Clarification of ARP encoding         Units for APN-AMBR         Clarification of Mobile Equipment Identity IE encoding         EPS Bearer Level TFT encoding         UE-initiated procedures with one bearer only         Combine UL and DL TFT IEs         PGW S5/S8 IP Address and TEID for user plane         Transaction Identifier information element         Delete Bearer Request         Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44       CT#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0117 0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	1 - - - - - - - - - - - - -	PCO Extensions added to messages         Clarifications to message directions         Removal of specification drafting hints         ISR related alignments         Clarifications to grouped IE usage         Clarification to Recovery IE type         Missing conditions         Clarification of ARP encoding         Units for APN-AMBR         Clarification of Mobile Equipment Identity IE encoding         EPS Bearer Level TFT encoding         UE-initiated procedures with one bearer only         Combine UL and DL TFT IEs         PGW S5/S8 IP Address and TEID for user plane         Transaction Identifier information element         Delete Bearer Request         Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</td> <td>1 - 1 2 1 - - 2 2 2 1 1 1 2</td> <td>Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0118 0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	1 - 1 2 1 - - 2 2 2 1 1 1 2	Clarifications to message directions Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150</td> <td>- 1 1 2 1 - 2 2 2 1 1 1 2</td> <td>Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0119 0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150	- 1 1 2 1 - 2 2 2 1 1 1 2	Removal of specification drafting hints ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151</td> <td>1 1 2 1 - - 2 2 2 1 1 1 1 2</td> <td>ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0120 0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	1 1 2 1 - - 2 2 2 1 1 1 1 2	ISR related alignments Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1         8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151</td> <td>1 2 1 - 2 2 2 1 1 1 2</td> <td>Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0122 0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	1 2 1 - 2 2 2 1 1 1 2	Clarifications to grouped IE usage Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151</td> <td>2 1 - 2 2 2 1 1 1 2</td> <td>Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0125 0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	2 1 - 2 2 2 1 1 1 2	Clarification to Recovery IE type Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IES PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1           2009-06         C1 </td <td>T#44       T#44       T#44</td> <td>CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288</td> <td>0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151</td> <td>1 - - 2 2 1 1 1 2</td> <td>Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change</td> <td>8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1</td> <td>8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0</td>	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0127 0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	1 - - 2 2 1 1 1 2	Missing conditions Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0128 0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	1 - 2 - 2 2 1 1 1 2	Clarification of ARP encoding Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0129 0131 0134 0136 0137 0142 0143 0147 0149 0150 0151	2 - 2 1 1 1 2	Units for APN-AMBR Clarification of Mobile Equipment Identity IE encoding EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0134 0136 0137 0142 0143 0147 0149 0150 0151	- 2 1 1 1 2	EPS Bearer Level TFT encoding UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0136 0137 0142 0143 0147 0149 0150 0151	2 2 1 1 1 2	UE-initiated procedures with one bearer only Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44 2T#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0137 0142 0143 0147 0149 0150 0151	2 1 1 2	Combine UL and DL TFT IEs PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0 8.2.0
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0142 0143 0147 0149 0150 0151	1 1 1 2	PGW S5/S8 IP Address and TEID for user plane Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1 8.1.1	8.2.0 8.2.0 8.2.0
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0143 0147 0149 0150 0151	1 1 2	Transaction Identifier information element Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1 8.1.1	8.2.0 8.2.0
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0147 0149 0150 0151	1 2	Delete Bearer Request Modify Bearer Request for TAU without MME or SGW change	8.1.1	8.2.0
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288 CP-090288 CP-090288	0149 0150 0151	2	Modify Bearer Request for TAU without MME or SGW change		
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288 CP-090288	0150 0151			ŏ.1.1	メンロ
2009-06         C1	CT#44 CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288 CP-090288	0151	2	Illos of ADNI DAA in Croote Secolar Deguast and SE/SC LL DOM		
2009-06         C1	CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288			Use of APN, PAA in Create Session Request, and S5/S8-U PGW F-TEID in Create Session Response	8.1.1	8.2.0
2009-06         C1	CT#44 CT#44 CT#44 CT#44	CP-090288 CP-090288		1	Message table corrections	8.1.1	8.2.0
2009-06         C1	CT#44 CT#44 CT#44	CP-090288	0153	-	Presence requirement for IEs in response	8.1.1	8.2.0
2009-06         C1	CT#44 CT#44		0154	2	Offending IE in the Cause IE	8.1.1	8.2.0
2009-06         C1	T#44	CP-090288	0156	1	Minor corrections	8.1.1	8.2.0
2009-06         C1           2009-06         C1           2009-06         C1           2009-06         C1           2009-06         C1		CP-090288	0157	1	FQ-CSID corrections	8.1.1	8.2.0
2009-06 C1 2009-06 C1		CP-090288	0158	-	APN and FQDN encoding clarifications	8.1.1	8.2.0
2009-06 CT	T#44	CP-090288	0159	-	Removal of Trace Information IE from Update Bearer Request	8.1.1	8.2.0
	T#44	CP-090288	0160	1	Corrections in PDN Connection group IE	8.1.1	8.2.0
		CP-090288	0161	1	Missing IEs in "Update Bearer Response"	8.1.1	8.2.0
	T#44	CP-090288	0164	2	PDN Type	8.1.1	8.2.0
	T#44	CP-090288	0168	1	IE corrections in Modify Bearer signalling	8.1.1	8.2.0
		CP-090288	0169	2	Create Session Request Clarification	8.1.1	8.2.0
		CP-090288	0175	-	TEID in Detach Notification/ACK	8.1.1	8.2.0
	T#44	CP-090288	0176	-	Condition of bearer context in Modify Bearer messages	8.1.1	8.2.0
		CP-090288	0177	1	Delete Session Request granularity	8.1.1	8.2.0
		CP-090288	0178	-	Deletion of IMSI in the Update Bearer Request	8.1.1	8.2.0
	T#44 T#44	CP-090288 CP-090288	0180 0181	1	Delete Session Request/Response and Delete Bearer Request Detach Notification	8.1.1 8.1.1	8.2.0 8.2.0
		CP-090288	0183	-	SGSN Info for Data Forwarding	8.1.1	8.2.0
		CP-090288	0183	1	Delete Session Request	8.1.1	8.2.0
		CP-090288	0185	1	APN AMBR clarification	8.1.1	8.2.0
		CP-090288	0186	1	Delete Bearer Request when ISR activated	8.1.1	8.2.0
		CP-090288	0187	1	Clarify the usage of the MS validated IE	8.1.1	8.2.0
		CP-090288	0189	1	UDP Source port and IP Source Address	8.1.1	8.2.0
		CP-090288	0190	-	Recovery IE	8.1.1	8.2.0
		CP-090288	0192	1	APN Information	8.1.1	8.2.0
		CP-090500	0193	3	Cause value	8.1.1	8.2.0
		CP-090288	0195	1	Cleanup indication	8.1.1	8.2.0
2009-06 CT	T#44	CP-090288	0196	1	Cleanup the usage of some messages	8.1.1	8.2.0
		CP-090288	0198	1	Linked EPS Bearer ID	8.1.1	8.2.0
		CP-090288	0199	1	PCO parameter	8.1.1	8.2.0
		CP-090288	0200	1	PDP Context Activation	8.1.1	8.2.0
		CP-090288	0201	1	User Location Info	8.1.1	8.2.0
		CP-090288	0202	2	F-Cause IE correction	8.1.1	8.2.0
		CP-090288	0206	1	Message granularity	8.1.1	8.2.0
		CP-090321	0209	-	Bearer Context in the Modify Bearer Command	8.1.1	8.2.0
		CP-090493	0210	1	Sequence Number Extension	8.1.1	8.2.0
		CP-090355	0212	-	Bearer Resource Command clarification	8.1.1	8.2.0
	T#44	CP-090485	0213	1	Piggybacked message clarifications	8.1.1	8.2.0
2009-06 CT	T#44	CP-090472	0214	1	Corrections on handling Charging ID IE and Charging Characteristics IE	8.1.1	8.2.0
2009-09 C1		CP-090533	0214	-	Usage of GTPv2-C Header	8.2.0	8.3.0
		CP-090533 CP-090533	0215	-	Create Session Request and Response	8.2.0	8.3.0
		CP-090533 CP-090533	0216	1	Cleanup Editors Note	8.2.0	8.3.0
		CP-090533 CP-090533	0217	1	Message format and Type values	8.2.0	8.3.0
		CP-090533	0210	-	S16 Influence	8.2.0	8.3.0
	T#45	CP-090533	0220	1	MM Context	8.2.0	8.3.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2009-09	CT#45	CP-090533	0223	-	F-Container	8.2.0	8.3.0
2009-09	CT#45	CP-090533	0225	-	Change Reporting Action	8.2.0	8.3.0
2009-09	CT#45	CP-090533	0226	1	Procedure names	8.2.0	8.3.0
2009-09	CT#45			_	Changes to Create-Session-Request and Create-Session-	8.2.0	8.3.0
	OT 11 45	CP-090533	0228	3	Response messages		
2009-09	CT#45	CP-090533	0229	1	Changes to Modify-Bearer-Response	8.2.0	8.3.0
2009-09 2009-09	CT#45 CT#45	CP-090533	0232	2	Piggybacking Clarifications	8.2.0 8.2.0	8.3.0
2009-09	CT#45 CT#45	CP-090533 CP-090533	0236	1 2	Delete Bearer Request Cause value for ISR deactivation Modify Bearer Request Bearer Level QoS	8.2.0	8.3.0 8.3.0
2009-09	CT#45	CF-090333	0237	2	Possible reject response Cause values in GTPv2 message	8.2.0	8.3.0
2003 03	01#43	CP-090533	0239	1	descriptions	0.2.0	0.0.0
2009-09	CT#45	CP-090533	0241	1	SGW F-TEID for S1-U, S12 and S4 for User Plane	8.2.0	8.3.0
2009-09	CT#45	CP-090533	0243	2	Clarification on the usage of Version Not Supported Indication	8.2.0	8.3.0
2009-09	CT#45				Clarifications on Sender-F-TEID for CP and S3/S10/S16 CP IP	8.2.0	8.3.0
		CP-090533	0244	1	Addr and TEID IEs		
2009-09	CT#45	CP-090533	0245	1	Cause Value in Echo Response	8.2.0	8.3.0
2009-09	CT#45	CP-090533	0246	-	Corrections in ULI IE and PDN Connection IE definitions	8.2.0	8.3.0
2009-09	CT#45				GTPv2 Initial and Triggered Message definition and Sequence	8.2.0	8.3.0
		CP-090533	0247	3	Number handling		
2009-09	CT#45	CP-090533	0249	1	Missing Cause values in some message descriptions	8.2.0	8.3.0
2009-09	CT#45	CP-090533	0250	4	Add TAC to Target Identification IE	8.2.0	8.3.0
2009-09	CT#45		0050		IMSI and Sender F-TEID in Create Indirect Data Forwarding	8.2.0	8.3.0
2000.00	CT#45	CP-090533	0256	1	Tunnel Messages	0.0.0	000
2009-09		CP-090534	0258	1	Indication in Forward Relocation messages	8.2.0	8.3.0
2009-09 2009-09	CT#45	CP-090534	0259 0260	1	Paging cause Correlate the bearers in the Create Bearer Response	8.2.0	8.3.0
	CT#45 CT#45	CP-090534		-		8.2.0	8.3.0
2009-09 2009-09	CT#45 CT#45	CP-090534 CP-090534	0261	3	Cleanup cause values Delete Bearer Failure Indication	8.2.0	8.3.0
2009-09	CT#45 CT#45	CP-090534 CP-090534	0262	 1	Cleanup Modify Bearer Request	8.2.0 8.2.0	8.3.0 8.3.0
2009-09	CT#45 CT#45	CP-090534 CP-090534	0263	2	IEs in Response	8.2.0	8.3.0
2009-09	CT#45	CP-090534 CP-090534	0264	-	CS Paging Indication	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0200	2	Serving Network	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0268	3	Service Handover support	8.2.0	8.3.0
2009-09	CT#45	01-000004	0200	5	Fix incorrect interface name, incorrect reference and other	8.2.0	8.3.0
2000 00	01//40	CP-090534	0269	3	misreading texts	0.2.0	0.0.0
2009-09	CT#45				Clarification on cause value for Downlink Data Notification Failure	8.2.0	8.3.0
		CP-090534	0270	1	Indication		
2009-09	CT#45	CP-090534	0271	2	Clarification on the Authentication Vector handling	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0276	1	Clarification on Authentication Vector encoding	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0278	5	Clarification on Error indication for EPC and DT	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0279	3	Aligning MBR units to kbps	8.2.0	8.3.0
2009-09	CT#45				Clarification to the PGW's UP address in Create Session	8.2.0	8.3.0
		CP-090534	0281	1	Response		
2009-09	CT#45	CP-090534		4	Modify Bearer procedure for X2 and S1 based handovers	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0290	1	Add necessary cause value to the Update Bearer Response	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0292	-	Update on Concurrent Running of Security Procedures	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0295	2	APN Restriction IE	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0296	1	Change Reporting IE	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0297	1	ULI Clarification	8.2.0	8.3.0
2009-09	CT#45	CP-090534	0301	-	Charging ID Delate Indirect Data Forwarding Tunnel Request/Response	8.2.0	8.3.0
2009-09 2009-09	CT#45 CT#45	CP-090534 CP-090535	0302 0303	1 1	Delete Indirect Data Forwarding Tunnel Request/Response SGW F-TEID	8.2.0 8.2.0	8.3.0 8.3.0
2009-09	CT#45 CT#45	CP-090535 CP-090535	0303	1	BCM	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0304	3	Charging Gateway Address	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0308	1	LBI Clarifications for Gn/Gp Handovers	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0309	1	Trace management messages and IE related clarifications	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0310	1	Indirect Data Forwarding Tunnel clarifications	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0311	2	Concurrent Running of Security Procedures	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0315	1	Cause value corrections	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0316	1	Identification Response	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0317	1	NSAPI and EBI in Forward Relocation Response	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0318	1	Cause in the CSFB related messages	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0320	1	Update Bearer Complete	8.2.0	8.3.0
				1	PCO IE	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0321				
		CP-090535 CP-090535	0321	-	Cleanup Trace Management messages	8.2.0	8.3.0
2009-09 2009-09 2009-09	CT#45 CT#45 CT#45	CP-090535 CP-090535	0322 0323	-	Cleanup section 5.3 and 8.12		8.3.0
2009-09 2009-09	CT#45 CT#45	CP-090535	0322	- - 1	Cleanup section 5.3 and 8.12 APN AMBR in the Create Bearer Request	8.2.0	
2009-09 2009-09 2009-09 2009-09 2009-09	CT#45 CT#45 CT#45 CT#45 CT#45	CP-090535 CP-090535 CP-090535 CP-090535	0322 0323		Cleanup section 5.3 and 8.12 APN AMBR in the Create Bearer Request UDP Source Port Number	8.2.0 8.2.0	8.3.0
2009-09 2009-09 2009-09 2009-09 2009-09 2009-09	CT#45 CT#45 CT#45 CT#45 CT#45 CT#45	CP-090535 CP-090535 CP-090535 CP-090535 CP-090535	0322 0323 0324 0325 0326	- - 1 1 -	Cleanup section 5.3 and 8.12 APN AMBR in the Create Bearer Request UDP Source Port Number Presence Requirments for grouped IE	8.2.0 8.2.0 8.2.0 8.2.0 8.2.0	8.3.0 8.3.0 8.3.0 8.3.0
2009-09 2009-09 2009-09 2009-09 2009-09	CT#45 CT#45 CT#45 CT#45 CT#45	CP-090535 CP-090535 CP-090535 CP-090535	0322 0323 0324 0325	- - 1	Cleanup section 5.3 and 8.12 APN AMBR in the Create Bearer Request UDP Source Port Number	8.2.0 8.2.0 8.2.0 8.2.0	8.3.0 8.3.0 8.3.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2009-09	CT#45	CP-090535	0334	-	Trace Depth per session	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0335	4	Backward compatibility requirements for presence	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0338	1	ECGI encoding correction	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0339	1	Consistant PDN type setting	8.2.0	8.3.0
2009-09 2009-09	CT#45 CT#45	CP-090535 CP-090729	0340 0341	1 1	GTP Cause value usage Partial failure handling alignment with stage 2	8.2.0 8.2.0	8.3.0 8.3.0
2009-09	CT#45 CT#45	CP-090729 CP-090729	0341	2	Partial failure handling for MME relocation w/o SGW relocation	8.2.0	8.3.0
2009-09	CT#45	CP-090729 CP-090535	0342	1	Security Specification for GTPV2-C	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0349	1	Avoiding Source Port Overlap between GTPv2-C and GTPv2-C'	8.2.0	8.3.0
2009-09	CT#45	CP-090535	0350	-	Delete Bearer Command PCO removal	8.2.0	8.3.0
2009-09	CT#45	CP-090559	0253	2	Scope of GTP-C protocol	8.2.0	9.0.0
2009-09	CT#45	CP-090559	0254	4	MBMS session management messages	8.2.0	9.0.0
2009-09	CT#45	CP-090562	0285	1	IMEI based GTP Changes	8.2.0	9.0.0
2009-09	CT#45	CP-090745	0286	4	Unauthenticated IMSI for emergency in GTP	8.2.0	9.0.0
2009-09	CT#45	CP-090562	0343	1	IMEI based Id in GTP messages	8.2.0	9.0.0
2009-09	CT#45	CP-090562	0344	1	Unauthenticated IMSI in GTP messages	8.2.0	9.0.0
					Editorial correction. Wrong style was used in Paragraph character	9.0.0	9.0.1
2009-10	CT#46	00.000700	0050		7.1.3.	0.0.4	0.4.0
2009-12	CT#46	CP-090769	0356	1	Selection Mode IE	9.0.1	9.1.0
2009-12	CT#46	CP-090798	0357	2	PTP bearer fallback	9.0.1	9.1.0
2009-12 2009-12	CT#46 CT#46	CP-090770 CP-090769	0359 0361	- 1	Bearer QoS in Modify Bearer Request Release Access Bearer Request	9.0.1 9.0.1	9.1.0 9.1.0
2009-12	CT#46 CT#46	CP-090769 CP-090770	0361	-	Bearer context in Create Session messages	9.0.1	9.1.0
2009-12	CT#46 CT#46	CP-090770 CP-090770	0365	-	ISRAI flag in the Forward Relocation Complete Notification	9.0.1	9.1.0
2009-12	CT#46 CT#46	CP-090770 CP-090770	0365	-	Mapping between RAI, P-TMSI, P-TMSI signature and GUTI	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0309	-	APN IE encoding	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0373	1	Correction on the condition for resource release of other CN node	9.0.1	9.1.0
2009-12	CT#46	CP-090970	0375	2	APN Restriction	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0377	1	Cause value "Invalid reply from remote peer"	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0380	1	Indication Flags in Delete Session Request	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0382	1	Suspend	9.0.1	9.1.0
					Removal of forwarding Charging Gateway Address/Name to S4-	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0386		SGSN		
2009-12	CT#46	CP-090770	0388	2	Charging ID in S4-SGSN	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0390	-	Correction of Message Direction for Create Session Response	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0392	1	PPC (Prohibit Payload Compression) alignment with Stage-2	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0393	3	UE TimeZone and ULI included in Bearer Response messages	9.0.1	9.1.0
2009-12	CT#46	CP-090804	0395	4	Support for CSG based charging	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0397	3	User Location Information	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0399	2	PDN type	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0403	-	Removal of ULI from Release Access Bearer Req	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0405	-	Removal of NSAPI IE	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0407	2	Indication IE clarification Addition of uplink, downlink F-TEIDs in Create Indirect Data	9.0.1 9.0.1	9.1.0 9.1.0
2009-12	CT#46	CP-090770	0409	3	Forwarding Tunnel Request and Response messages	9.0.1	9.1.0
2000 12	CT#46	01 000110	0.100	0	Clarifications on use of the Sender-F-TEID for CP in HO	9.0.1	9.1.0
2009-12	2	CP-090770	0411	2	procedure	0.0.1	0.110
2009-12	CT#46	CP-090770	0417	-	Clarifications to MSISDN coding	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0419	2	Enhanced handling of RFSP index at the SGSN/MME	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0423	2	TFT related error handling	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0425	4	Essential correction to the Indirect Data Forwarding procedure	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0434	-	Correcting misaligned IE presence type statements	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0438	1	Correcting PCO conditions in Modify Bearer Response	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0442	2	Delete Indirect Data Forwarding Tunnel messages	9.0.1	9.1.0
2009-12	CT#46	CP-090777	0448	1	SRVCC - voice bearer handling in PS HO / DTM scenarios	9.0.1	9.1.0
2009-12	CT#46	CP-090975	0450	2	NAS Count value	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0452	1	Charging Characteristics value for active PDN connections	9.0.1	9.1.0
2009-12	CT#46	CP-090786	0453	1	eNodeB Cause and RANAP Cause corrections	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0455	-	Change the NSAPI to EBI in the PFI IE	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0457	-	Enhanced SRNS Relocation Procedure	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0459	-	Forward Access Context Acknowledge	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0461	-	Correct the message Modify Bearer Request	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0471	1	Cleanup Suspend Notification message	9.0.1	9.1.0
2009-12	CT#46	CP-090769	0475	1	Forward Relocation Request: Selected PLMN ID	9.0.1	9.1.0
2009-12	CT#46	CP-090770	0484	1	Change Reporting Action	9.0.1	9.1.0
2009-12	CT#47	CP-090770 CP-100021	0484	1	Essential clarification to MME executed TAU procedure	9.1.0	9.2.0
2010-03	CT#47	CP-100022	0495	5	Essential correction to the MM context IE type	9.1.0	9.2.0
2010-03	CT#47 CT#47	CP-100022 CP-100021	0495	1	Resolving ambiguity for Target Identification IE coding	9.1.0	9.2.0
	CT#47	CP-100021	0504		PCO	9.1.0	9.2.0
2010-03							

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2010-03	CT#47	CP-100021	0506	1	RFSP Index	9.1.0	9.2.0
2010-03	CT#47	CP-100049	0508	1	Include CSG ID and CSG Membership Indication in S3 and S10	9.1.0	9.2.0
2010-03	CT#47	CP-100035	0510	2	Location change reporting in EPS	9.1.0	9.2.0
2010-03	CT#47	CP-100019	0512		The encoding of APN IE	9.1.0	9.2.0
2010-03	CT#47	CP-100021	0514	1	Indirect Data Forwarding	9.1.0	9.2.0
2010-03	CT#47	CP-100021	0516	2	HSS/PGW initiated Bearer QoS Modification procedure	9.1.0	9.2.0
2010-03 2010-03	CT#47 CT#47	CP-100022 CP-100022	0518 0520	1 2	APN IE description correction P-TMSI Signature	9.1.0 9.1.0	9.2.0 9.2.0
2010-03	CT#47 CT#47	CP-100022 CP-100035	0520	1	Corrections to the RAN Information Management procedures	9.1.0	9.2.0
2010-03	CT#47	CP-100033	0523		Source Identification for E-UTRAN to GERAN handover	9.1.0	9.2.0
2010-03	CT#47	CP-100049	0524	1	Handovers to HeNB cells	9.1.0	9.2.0
2010-03	CT#47	CP-100022	0530	1	Granularity	9.1.0	9.2.0
2010-03	CT#47	CP-100021	0533	2	Change Reporting Support Indicator	9.1.0	9.2.0
2010	CT#47	CP-100021	0535		MM Context IE type correction	9.1.0	9.2.0
2010-03	CT#47				Removal of TEIDs for PS voice bearer UP in Bearer Context for	9.1.0	9.2.0
		CP-100027	0537	2	SRVCC		
2010-03	CT#47	CP-100021	0539		Correction on the presence condition of Charging ID IE on S4	9.1.0	9.2.0
2010-03	CT#47	CP-100035	0541	3	Suspend	9.1.0	9.2.0
2010-03	CT#47	CP-100022	0548	1	Modify Octets Sequence Number of RAB Context IE	9.1.0	9.2.0
2010-03	CT#47	CB 400000	0550	4	Revive the cause value "User Authentication Failed" in the Create	9.1.0	9.2.0
2010.02	CT#47	CP-100022	0550	1	Session Response	010	0.2.0
2010-03	_	CP-100035	0554	1	Fix PCO handling by defining it per bearer	9.1.0	9.2.0
2010 2010-03	CT#47 CT#47	CP-100022 CP-100022	0556 0558	2	Fix PDN Connection Grouped Type Correction on the down link notification failure procedure	9.1.0 9.1.0	9.2.0 9.2.0
2010-03			0565		Correction of the presence condition of IEs		9.2.0
2010-03	CT#47 CT#47	CP-100022 CP-100021	0565	2	Figure number, Information element and message usage	9.1.0 9.1.0	9.2.0
2010-03	CT#47 CT#47	CF-100021	0507	1	2G related parameters in the Forward Relocation Request and	9.1.0	9.2.0
2010-03	01#47	CP-100022	0569	2	Context Response	9.1.0	9.2.0
2010-03	CT#47	CP-100022	0505	2	Essential correction to the Create Bearer Request message	9.1.0	9.2.0
2010-03	CT#47	CP-100022	0581	1	Essential correction to FTEID IE	9.1.0	9.2.0
2010-03	CT#47	01 100022	0001	1	Essential correction to Modify Bearer Request for non-3GPP to	9.1.0	9.2.0
2010 00	01// 11	CP-100022	0583	2	3GPP handover	0.1.0	0.2.0
2010-03	CT#47	CP-100021	0585		Removal of unncessary cause "Unexpected repeated IE"	9.1.0	9.2.0
2010-03	CT#47				Removal of indirect uplink data forwarding from Inter RAT	9.1.0	9.2.0
	_	CP-100022	0587	1	handovers		
2010-03	CT#47	CP-100021	0591	1	Trace alignment with TS 32.422	9.1.0	9.2.0
2010-06	CT#48	CP-100266	0599	1	Essential corrections to M-TMSI mapping	9.2.0	9.3.0
2010-06	CT#48	CP-100266	0603	3	Change Notification	9.2.0	9.3.0
2010-06	CT#48				Fix missing conditional description for IEs in the context response	9.2.0	9.3.0
		CP-100266	0605	1	message		
2010-06	CT#48	CP-100266	0614	1	Change Reporting Support Indication	9.2.0	9.3.0
2010-06	CT#48	CP-100266	0618	1	Handover/Relocation cancel procedure	9.2.0	9.3.0
2010-06	CT#48	CP-100266	0624	1	ULI in the Modify Bearer Request message	9.2.0	9.3.0
2010-06	CT#48	CP-100266			MM context IE encoding	9.2.0	
2010-06	CT#48	CP-100266	0635	2	MBR in handover from non-3GPP to 3GPP	9.2.0	9.3.0
2010-06	CT#48	CP-100266	0637	1	Suspend over S16	9.2.0	9.3.0
2010-06	CT#48	CP-100266	0642	1	Adding Service indicator to CS Paging Indication Fallback to GTPv1	9.2.0	9.3.0
2010-06 2010-06	CT#48 CT#48	CP-100266	0647	3	Essential correction to ULI IE condition in Modify Bearer Request	9.2.0 9.2.0	9.3.0 9.3.0
2010-00	01#40	CP-100266	0650	2	essential correction to OLI TE condition in Modify Bearer Request	5.2.0	9.3.0
2010-06	CT#48	CP-100266	0657	1	TEID in Change Notification	9.2.0	9.3.0
2010-00	CT#48	CP-100266	0659	1	Charging ID	9.2.0	9.3.0
2010-06	CT#48	200200		- ·	Alert MME Notification / UE Activity Notification procedure on S3	9.2.0	9.3.0
		CP-100266	0664		interface		2.0.0
2010-06	CT#48	CP-100281	0540	4	Leave CSG Cell indication	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0609	1	Use of Rejection Cause values	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0616	2	Flow QoS in the Bearer Resource Command message	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0633	1	Correction to the reference in Create indirect DF Tunnel Request	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0638	1	Removal of FFS	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0673	1	Message type table	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0639	3	Implicit resume	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0670	1	Cause IE type	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0667	2	Clarifications to redundant IEs	9.2.0	9.3.0
2010-06	CT#48	CP-100281	0669	1	EBI value range and coding	9.2.0	9.3.0
	CT#48				Cause IE enhacements to distinguish errors in the message level	9.2.0	9.3.0
2010-06	01#40			1	IE versus errors in the grouped IE within the message	1	
2010-06		CP-100281	0651				
2010-06 2010-06	CT#48	CP-100281	0672	1	Bearer Resource Command usage	9.2.0	9.3.0
2010-06 2010-06 2010-06	CT#48 CT#48	CP-100281 CP-100287	0672 0654	1	Bearer Resource Command usage Sn-U SGSN F-TEID	9.2.0	9.3.0
2010-06 2010-06 2010-06 2010-06	CT#48 CT#48 CT#48	CP-100281	0672		Bearer Resource Command usage Sn-U SGSN F-TEID Allocation and Retention Priority for MBMS E-RAB	9.2.0 9.2.0	9.3.0 9.3.0
2010-06 2010-06 2010-06	CT#48 CT#48	CP-100281 CP-100287	0672 0654	1	Bearer Resource Command usage Sn-U SGSN F-TEID	9.2.0	9.3.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2010-06	CT#48	CP-100298	0680		Essential correction for the Initial Attach procedure	9.2.0	9.3.0
2010-06	CT#48	00 4000-0			Transferring of UE's usage setting and voice capability between	9.2.0	9.3.0
0040.00	OT#40	CP-100276	0612		CN nodes	0.0.0	0.0.0
2010-06 2010-09	CT#48 CT#49	CP-100408 CP-100452	0544 0607	6 5	Clarifying the bearers to be deactivated on the S5/S8 interface Fix Sudden disconnection after the inter RAT MM attempt	9.2.0 9.3.0	9.3.0
2010-09	CT#49 CT#49	CP-100452 CP-100445	0607	э 4	IP Address IE clarification	9.3.0	9.4.0 9.4.0
2010-09	CT#49 CT#49	CP-100445 CP-100451	0681	2	Serving Network semantics	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0685	2	Originating Node	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0687	1	Condition of ISRAI Flag	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0689	1	PDN Connection for Subscription Data Change	9.3.0	9.4.0
2010-09	CT#49	CP-100580	0690	4	Clarification for Create Session Response	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0693	2	An exception to use GTPv2	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0694		IEs to be included in rejection response messages	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0695	2	Ambiguity for encoding MBR/GBR	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0696		Wrong reference to DRX parameter	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0697		Selection Mode	9.3.0	9.4.0
2010-09	CT#49	CP-100452	0701	2	Stop CSG Information Reporting	9.3.0	9.4.0
2010-09	CT#49	00 400 450	0700		Create Session Request/Response and Modify Bearer	9.3.0	9.4.0
0010.00	OT#40	CP-100452	0702		Request/Response for RAU procedure	0.0.0	0.4.0
2010-09	CT#49	CP-100452	0703	4	Suspend message on S3 interface	9.3.0	9.4.0
2010-09	CT#49	CP-100445	0705	1	Cause value in Detach Notification	9.3.0	9.4.0
2010-09 2010-09	CT#49 CT#49	CP-100445	0707	1	S1 based handover cancel	9.3.0 9.3.0	9.4.0
2010-09	CT#49 CT#49	CP-100445 CP-100452	0709 0711	1 2	Used NAS integrity protection algorithm values TAU with Active Flag	9.3.0	9.4.0 9.4.0
2010-09	CT#49 CT#49	CP-100452 CP-100452	0711	 1	Trace Report File LDNs	9.3.0	9.4.0
2010-09	CT#49 CT#49	CP-100452 CP-100445	0718	1	Change Notification Response	9.3.0	9.4.0
2010-09	CT#49 CT#49	CP-100445 CP-100451	0718	1	Presence rules and error handling for embedded IEs	9.3.0	9.4.0
2010-09	CT#49 CT#49	CP-100451	0723	1	Dual Address Bearer Flag	9.3.0	9.4.0
2010-09	CT#49 CT#49	01-100431	0724	-	Rejecting the dedicated bearer related procedure from MME to	9.3.0	9.4.0
2010-03	01#43	CP-100451	0726	1	SGW and PGW	3.3.0	3.4.0
2010-09	CT#49	CP-100636	0727	2	Correction to condition of sending Context Acknowledge message	9.3.0	9.4.0
2010-09	CT#49	CP-100451	0729	2	Clarification to the OI flag usage in Delete Session Request	9.3.0	9.4.0
2010-09	CT#49	CP-100451	0732	1	Correcting non-existent Cause value	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0736	1	Resume messages	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0738	1	LAI field	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0740	1	P-TMSI Signature	9.3.0	9.4.0
2010-09	CT#49	CP-100453	0744	2	Change Reporting Support Indication	9.3.0	9.4.0
2010-09	CT#49	CP-100451	0745	1	Error handling	9.3.0	9.4.0
2010-09	CT#49	CP-100451	0746	1	Flow QoS IE	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0748	1	PDN Connection for Subscription Data Change	9.3.0	9.4.0
2010-09	CT#49	CP-100444	0750	1	E-UTRAN to HRPD handover	9.3.0	9.4.0
2010-09	CT#49				Correcting type value of the MBMS Session Start Response	9.3.0	9.4.0
	07.40	CP-100451	0751		message		
	CT#49	CP-100451	0754	_	GTP protocol errors		9.4.0
2010-09	CT#49	CP-100451	0755	1	Essential Clarification in Forward Relocation Response message	9.3.0	9.4.0
2010-09 2010-09	CT#49	CP-100469	0662	4	New Modify Access Bearers procedure Notification of supported features between peer GTP-C entities	9.4.0	10.0.0
2010-09	CT#49 CT#49	CP-100469 CP-100469	0698 0734	6 1	Length of IPv6 Prefix	9.4.0 9.4.0	10.0.0
2010-09		CP-100469 CP-100695	0758	1	OI flag in Delete Session Request alignment with stage		10.0.0
	CT#50 CT#50	CP-100695 CP-100695	0758	3	ISR in Delete Bearer Request		10.1.0
2010-12	CT#50 CT#50	CP-100695 CP-100695	0787	4	PGW Restart Notification		10.1.0
2010-12	CT#50	CP-100695	0798	2	Feature definition for the Modify Access Bearers procedure		10.1.0
2010-12	CT#50	3	0.00	-	Modify Access Bearers procedure during Inter-MME Intra-SGW		10.1.0
		CP-100695	0799	1	TAU		
2010-12	CT#50	CP-100695	0812	1	Clarifications to Failure Indication type of messages	10.0.0	10.1.0
2010-12	CT#50	CP-100695	0817	2	EPS Bearer ID in Downlink Data Notification message		10.1.0
2010-12	CT#50	CP-100695	0818	1	Clarifying possible cause value sets		10.1.0
2010-12	CT#50	CP-100695	0823	2	SGSN Failure handling	10.0.0	10.1.0
2010-12	CT#50	CP-100695	0835	1	Handover Indication	10.0.0	10.1.0
2010-12	CT#50	CP-100695	0842	1	Cause values for Delete Bearer Request		10.1.0
2010-12	CT#50	CP-100688	0848	2	MME/SGSN overload control by throttling of DL low priority traffic		10.1.0
2010-12	CT#50	CP-100675	0773	1	Suspend and Resume procedure		10.1.0
2010-12	CT#50	CP-100675	0775	1	Range for BSSGP Cause		10.1.0
2010-12	CT#50	CP-100675	0777	1	RAT Type in the Modify Bearer Request message		10.1.0
2010-12	CT#50	CP-100675	0781	-	ISR for SGW		10.1.0
2010-12	CT#50	CP-100675	0783	1	ISR in the Detach procedure		10.1.0
2010-12	CT#50	00	0=6-		Missing Cause Code mapping for IRAT Handover between	10.0.0	10.1.0
0040.40	OT//50	CP-100675	0789	1	GERAN and EUTRAN	10.0.0	40.4.6
	CT#50	CP-100675	0794	-	Voice bearer flag	10.0.0	10.1.0
2010-12		00 400075	0004		MDMC some stigned	4000	4040
2010-12 2010-12 2010-12	CT#50 CT#50	CP-100675 CP-100675	0801 0821	1	MBMS corrections CSG Reporting	10.0.0	10.1.0 10.1.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2010-12	CT#50	CP-100675	0825	-	Target Identification	10.0.0	
2010-12	CT#50	CP-100675	0830	2	Reporting UE Time Zone changes		10.1.0
2010-12	CT#50	CP-100675	0838	1	Essential correction for UE Timezone reporting	10.0.0	10.1.0
2010-12	CT#50	CP-100675	0846	2	ISR activated flag	10.0.0	10.1.0
2010-12	CT#50	CP-100672	0851	1	Determination of type of source node during TAU/RAU		10.1.0
2010-12	CT#50				Essential correction to Create Indirect Data Forwarding Tunnel	10.0.0	10.1.0
	07/0	CP-100674	0765	1	Response		
2010-12	CT#50	CP-100686	0767	1	GTP-C Information Elements for GTP based S2b interface		10.1.0
2010-12	CT#50	CP-100686	0786	-	Delete PDN Connection Set		10.1.0
2010-12 2010-12	CT#50 CT#50	CP-100686	0796	-	Addition of GTP over S2b to clauses 1 to 6 Create Session Request/Response & Create Bearer		10.1.0
2010-12	01#30	CP-100686	0797	3	Request/Response	10.0.0	10.1.0
2010-12	CT#50	CP-100686	0802	-	Delete Session and Bearer messages	10 0 0	10.1.0
2010-12	CT#50	0	0002		Modify Bearer Command/Failure Indication and Update Bearer	10.0.0	10.1.0
		CP-100686	0804	-	Req/Rsp		
2010-12	CT#50	CP-100686	0807	-	Trace Session Activation/Deactivation for GTP-S2b	10.0.0	10.1.0
2010-12	CT#50				Handling of Create Session Request message on header TEID =	10.0.0	10.1.0
		CP-100686	0839	1	0		
2010-12	CT#50	CP-100687	0769	2	Downlink data notification information for MPS services	10.0.0	10.1.0
2010-12	CT#50	CP-100667	0828	-	UE Time Zone adjustments	10.0.0	10.1.0
2010-12	CT#50	CP-100669	0816	2	Essential alignment with PMIP spec		10.1.0
2011-03	CT#51	CP-110064	0921	1	Data Delay Notification		10.2.0
2011-03	CT#51	CP-110064	0916	-	Clean up with GTP-C Information Elements		10.2.0
2011-03	CT#51				Inclusion of Node Type in DDN Failure Indication when the ISR is	10.1.0	10.2.0
		CP-110064	0911	1	active		
2011-03	CT#51	CP-110064	0897	1	Create Session Response		10.2.0
2011-03	CT#51	CP-110064	0896	-	UE Network Capability IE		10.2.0
2011-03	CT#51			-	Adding "Initial", "Triggered" and "Initial or triggered by a	10.1.0	10.2.0
0011.00	07/54	CP-110064	0895	2	Command" attributes to the messages in table 6.1	40.4.0	40.0.0
2011-03	CT#51	CP-110064	0894	1	Adding a separate subclause for TEID=0		10.2.0
2011-03	CT#51	CP-110064	0893	1	Removing optional Cause IE from Echo Response		10.2.0
2011-03	CT#51	CP-110064	0875	2	RAT type clarification for S4-SGSN		10.2.0
2011-03	CT#51	CP-110064	0874	1	Essential correction to the table NOTE for the Create Session Response message	10.1.0	10.2.0
2011-03	CT#51	CP-110064	0872	1	Error Indication for SGW	10.1.0	10 2 0
2011-03	CT#51	CP-110064	0872	1	Cleanup for GTPv2	10.1.0	
2011-03	CT#51	CP-110064	0870	2	RAT Type in Modify Access Bearers Request	10.1.0	
2011-03	CT#51	CP-110064	0869	-	Bearer context in Modify Bearer Request	10.1.0	
2011-03	CT#51	CP-110064	0860	-	S1-U eNodeB F-TEID IE in the Modify Access Bearers Request	10.1.0	
2011-03	CT#51	CP-110064	0855	1	Correction for VNSI	10.1.0	
2011-03	CT#51	CP-110064	0844	6	Serving Network IE	10.1.0	
2011-03	CT#51	CP-110061	0856	2	APN based congestion control	10.1.0	
2011-03	CT#51	CP-110061	0858	1	Low access priority indicator	10.1.0	
2011-03	CT#51		0859	1	EBI and ARP IEs in Downlink Data Notification	10.1.0	
2011-03		CP-110049	0918	2		10.1.0	
2011-03	CT#51	CP-110049	0901	1	UE Time Zone condition Delete Session Request	10.1.0	
2011-03	CT#51	CP-110049	0889	3	Subscribed UE-AMBR in mobility procedure	10.1.0	
2011-03	CT#51	CP-110049	0884	5	Essential correction to the fallback to GTPv1 feature	10.1.0	10.2.0
2011-03	CT#51	CP-110049	0881	1	RAT Type in the Modify bearer request message	10.1.0	
2011-03	CT#51				Missed procedures for the Delete Session Request and Response		10.2.0
		CP-110049	0879	-	messages		
2011-03	CT#51	CP-110049	0866	1	Correction to passing of LDN	10.1.0	
2011-03	CT#51	CP-110049	0862	-	S103 resource release	10.1.0	
2011-03	CT#51	CP-110049	0886	-	Essential correction to the to GTPv2 cause table	10.1.0	
2011-03	CT#51	CP-110042	0914	1	Essential correction to the encoding of Target RNC-ID	10.1.0	
2011-03	CT#51	CP-110056	0887	5	Unsupported Bearer Handling for LIPA	10.1.0	
2011-03	CT#51	CP-110083	0892	3	Adding IMSI to DDN	10.1.0	
2011-03	CT#51	CP-110053	0899	1	Temporary Mobile Group Identity	10.1.0	
2011-03	CT#51	CP-110042	0867	1	Correcting IE Type for Bearer QoS IE from Variable to Extendable	10.1.0	
2011-03	CT#51	CP-110266	0903	2	UE Time Zone condition in Modify Bearer Request	10.1.0	
2011-03	CT#51	CP-110059	0915	-	Serving network in the Create Session Request message	10.1.0	
2011-03	CT#51	CP-110072	0923	-	CS BIT to be available for initial message	10.1.0	
2011-05					Editorial correction in section 7.10 because of misimplentation of	10.2.0	10.2.1
2011.00	CT#EO	CD 110355	0007	0	CT#51 agreed CR C4-110990	10.2.4	10.2.0
2011-06	CT#52	CP-110355	0927	2	Mapping of ASN.1/PER parameters to GTPv2 IEs	10.2.1	
2011-06	CT#52	CP-110355	0940	3	Downlink Data Notification for S4		10.3.0
2011-06	CT#52	CP-110355	0964	1	IE Type Extendable Corrections		10.3.0
2011-06	CT#52	CP-110366	0930	2	Fix SRVCC related data transfer between MMEs/SGSNs	10.2.1	
2011-06	CT#52	CP-110366	0932	1	UE Time Zone IE in Delete Session Request message		10.3.0
2011-06	CT#52	CP-110366	0943	1	Higher bitrates than 16 Mbps flag	10.2.1	
2011-06	CT#52	CP-110366	0953	1	Temporary Rejection Cause	10.2.1	10.3.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2011-06	CT#52	CP-110366	0958	1	Cause IE in DDN message	10.2.1	10.3.0
2011-06	CT#52	CP-110378	0928	2	Alignment with stage 2 for EPC node restart with active ISR	10.2.1	10.3.0
2011-06	CT#52	CP-110374	0924	1	Setting a sequence number in a Command	10.2.1	10.3.0
2011-06	CT#52	CP-110374		1	Clarification for Create Session Response	10.2.1	
2011-06	CT#52	CP-110374	0944 0947	2	Max MBR/APN-AMBR	10.2.1	10.3.0
2011-06 2011-06	CT#52 CT#52	CP-110374 CP-110374	0947	3	Inactive Emergency PDN Handling ARP supporting on M3 interface for MBMS	10.2.1	10.3.0 10.3.0
2011-06	CT#52	CP-110374	0948		Downlink Data Notification message	10.2.1	10.3.0
2011-00	CT#52	CP-110374		1	Serving Network	10.2.1	10.3.0
2011-06	CT#52	CP-110374	0956	2	Serving Network IE in Modify Bearer Request	10.2.1	10.3.0
2011-06	CT#52	01 110074	0000		LAPI during UE initiated bearer resource allocation / modification		10.3.0
2011 00	001	CP-110369	0945		procedures		
2011-08					Editorial correction in section 7.10 because of misimplentation of CT#51 agreed CR C4-110990	10.3.0	10.3.1
2011-09	CT#53	CP-110721	0969	1	Additional MM context for SRVCC	10.3.1	10.4.0
2011-09	CT#53	01 110721	0000		Condition for sending Cause IE with DBReq during a HO from	10.3.1	
2011 00	01//00	CP-110557	0977	1	3GPP to non-3GPP	10.0.1	10.1.0
2011-09	CT#53	CP-110557	0986	1	Essential Clarification for SGSN pool	10.3.1	10.4.0
2011-09	CT#53	CP-110557	0994	1	Essential correction to handling of EPDN session for UICCless UE	10.3.1	10.4.0
2011-09	CT#53				Correction to ULI and UCI IE inclusion condition in Change	10.3.1	10.4.0
	07/	CP-110557	0996	1	Notification Req	10	10.10
2011-09	CT#53	CP-110557	1000	1	Correction to header TEID of Suspend Notification over S3/S16	10.3.1	10.4.0
2011-09	CT#53	CP-110557	1002	1	Extended IE handling when received fields are less than expected fields	10.3.1	10.4.0
2011-09	CT#53	CP-110557 CP-110557	1002	1	Cause Code for DDN	10.3.1	10.4.0
2011-09	CT#53	CP-110557 CP-110574	0975	3	MDT configuration information		
2011-09	CT#53	CP-110567	0980		Correction to Create Session Response LDN IEs		10.4.0
2011-09	CT#53	CP-110567	0982	2	IP address parameter	10.3.1	10.4.0
2011-09	CT#53	CP-110567	0967	1	Signalling path failure handling	10.3.1	10.4.0
2011-09	CT#53	CP-110567	0983	1	Node Type		10.4.0
2011-09	CT#53	CP-110567	0987	1	Clarification for Context Not Found	10.3.1	10.4.0
2011-09	CT#53	CP-110567	0988	1	Recovery IE in MBMS Session Stop Response message	10.3.1	10.4.0
2011-09	CT#53	0			Removal of PCO from Failed Bearer Context of Delete Bearer	10.3.1	10.4.0
		CP-110567	1001		Request		
2011-09	CT#53	CP-110567	1006		Downlink Data Notification for S4	10.3.1	10.4.0
2011-09	CT#53	CP-110557	1010	1	MEI in Modify Bearer Request	10.3.1	10.4.0
2011-09	CT#53	CP-110577	0972	1	OI flag in Delete Session Request	10.4.0	
2011-09	CT#53	CP-110577	0973	1	Clarification to DAF PAA usage		11.0.0
2011-09	CT#53	CP-110577	0974		Correcting Port Number IE type definition	10.4.0	
2011-09	CT#53	CP-110584	0989	3	Add vSRVCC updates to the GTP based interfaces	10.4.0	
2011-09	CT#53	00 440577	0000		Clarification on the Bearer Contexts to be removed IE in Modify	10.4.0	11.0.0
2011.00		CP-110577	0990	1	Access Bearers Request message	11.0.0	11.0.1
2011-09	CT#54	CP-110810	1000		CR 0914r1 title in history table corrected as in CR database.	11.0.0	
2011-12 2011-12	CT#54	CP-110810 CP-110810	1026	1	Delete Session Response Bearer Resource Command	11.0.1	11.1.0
2011-12	CT#54	CP-110810		1			11.1.0
2011-12	CT#54	CP-110810 CP-110810	1049 1035	1	Clarification on the length restriction of PCO, TFT IE Correction on SGW-FQ-CSID		11.1.0
2011-12	CT#54	51-110010	1030		Correction to Downlink Data Notification message due to control	11.0.1	11.1.0
2011-12	01#34	CP-110790	1051	3	plane signalling	11.0.1	11.1.0
2011-12	CT#54	CP-110790	1048	2	MBMS IP Multicast Distribution IE	11.0.1	11.1.0
2011-12	CT#54	CP-110784	1054	2	Defining the fixed number of octets for extendable IEs	11.0.1	
2011-12	CT#54	CP-110790	1063		Delete Session Request granularity	11.0.1	
2011-12	CT#54	00.00000			Essential correction to the TAD IE inclusion in Bearer Resource	11.0.1	11.1.0
		$CD_{-}110782$	1058	2	Command over S4		
	0 <b></b>	CP-110782					
2011-12	CT#54	CP-110810	1059	2	Fix inconsistency within the specification for GTP version handling	11.0.1	
2011-12	CT#54	CP-110810 CP-110810	1059 1036	2	Fix inconsistency within the specification for GTP version handling IE conditions in some message	11.0.1	11.1.0
2011-12 2011-12	CT#54 CT#54	CP-110810 CP-110810 CP-110790	1059 1036 1065	2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages	11.0.1 11.0.1	11.1.0 11.1.0
2011-12 2011-12 2011-12	CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790	1059 1036 1065 1019	2 1 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP	11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810	1059 1036 1065 1019 1033	2 1 2 1	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request	11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810 CP-110810	1059 1036 1065 1019 1033 1061	2 1 2 1 1	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810 CP-110810 CP-110810	1059 1036 1065 1019 1033 1061 1038	2 1 2 1 1 1	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810 CP-110810 CP-110810 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022	2 1 2 1 1 1 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810 CP-110810 CP-110810 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030	2 1 2 1 1 1 2 3	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110790 CP-110790 CP-110790 CP-110810 CP-110810 CP-110784 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030 1080	2 1 2 1 1 1 2 3 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110810 CP-110790 CP-110790 CP-110810 CP-110810 CP-110810 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030	2 1 2 1 1 1 2 3	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures Missing Originating Node IE when ISR is active	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110790 CP-110790 CP-110790 CP-110810 CP-110810 CP-110784 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030 1080 1083	2 1 2 1 1 1 2 3 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110790 CP-110790 CP-110790 CP-110810 CP-110810 CP-110784 CP-110784 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030 1080 1083	2 1 2 1 1 1 2 3 2 2 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures Missing Originating Node IE when ISR is active Correction to the Sender F-TEID IE description of the Forward Relocation Request	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110790 CP-110790 CP-110790 CP-110810 CP-110810 CP-110784 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030 1080 1083 1088	2 1 2 1 1 2 3 2 2 2 1	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures Missing Originating Node IE when ISR is active Correction to the Sender F-TEID IE description of the Forward	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0         11.1.0
2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12 2011-12	CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54 CT#54	CP-110810 CP-110790 CP-110790 CP-110790 CP-110810 CP-110810 CP-110784 CP-110784 CP-110784 CP-110784 CP-110784	1059 1036 1065 1019 1033 1061 1038 1022 1030 1080 1083 1088 1103	2 1 2 1 1 2 3 2 2 2 1 2	Fix inconsistency within the specification for GTP version handling IE conditions in some message Indirect Data Forwarding messages Referencing Information Elements defined outside GTP Scope Indication IE in Delete Session Request ULI in the Create Session Request Update PDN Connection Set Request Essential clarification on F-TEID in Create Bearer Response Modify Bearer Request as implicit resume User CSG Information in TAU/RAU procedures Missing Originating Node IE when ISR is active Correction to the Sender F-TEID IE description of the Forward Relocation Request Missing Cause Value for MUPSAP	11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1 11.0.1	11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0 11.1.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2011-12	CT#54	CP-110810	1072	1	TFT in the SGW for PMIP based S5/S8 interface	11.0.1	11.1.0
2011-12	CT#54	CP-110810	1073	1	MBMS Flow ID in the MBMS Session Stop message	11.0.1	11.1.0
2011-12	CT#54	CP-110810	1085	2	Change Notification Reporting with Non-Zero TEID	11.0.1	
2011-12	CT#54	CP-110810	1090	1	LBI in the Delete Bearer Request	11.0.1	11.1.0
2011-12	CT#54	CP-110810	1091	-	DRX parameter ZUC based EEA3 and EIA3 security algorithm	11.0.1	
2011-12	CT#54	CP-110810	1092 1098	- 2	Suspend Notification	11.0.1 11.0.1	
2011-12	CT#54 CT#54	CP-110810 CP-110790	1098	 1	PCO IE in the Modify Bearer Request message		11.1.0
2011-12	CT#54	CP-110790	1073	1	IMEI not known cause	11.0.1	
2011-12	CT#54	CP-110790	1094	2	Correction on the bearer context for modification procedure		11.1.0
2011-12	CT#54	CP-110790	1108	-	UE Time Zone condition in Modify Bearer Request		
2011-12	CT#54	CP-110815	1067	1	PGW restoration upon PGW failure w/o restart	11.0.1	
2011-12	CT#54	CP-110792	1070	3	Authentication with external networks over GTP S2b	-	11.1.0
2011-12	CT#54	CP-110816	1086	-	Add vSRVCC indicator to Delete Bearer Command	11.0.1	11.1.0
2012-03	CT#55	CP-120017	1117	-	Handover to CSG cell with emergency bearer	11.1.0	11.2.0
2012-03	CT#55	CP-120017	1120	-	Pre-Rel-7 QoS description correction	11.1.0	11.2.0
2012-03	CT#55	CP-120017	1126	2	Reserved Bearer Context at SRNS Relocation		11.2.0
2012-03	CT#55	CP-120017	1146	2	Higher bitrates than 16 Mbps flag		11.2.0
2012-03	CT#55	CP-120017	1180	1	ULI reporting for S4		11.2.0
2012-03	CT#55	CP-120026	1133	6	UE Requested Bearer Resource Modification Procedure		11.2.0
2012-03	CT#55	CP-120026	1135	-	Presence requirements of Information Elements		11.2.0
2012-03	CT#55	CP-120026	1141	2	Max MBR/APN-AMBR in enhanced SRNS relocation procedure		11.2.0
2012-03	CT#55	CP-120026 CP-120026	1147 1152	1	Clarification of Echo Response Location change reporting support indication related correction		11.2.0
2012-03 2012-03	CT#55 CT#55	CP-120026 CP-120026	1152 1154	1	Location change reporting support indication related correction Fix Inter RAT HO issue when ISR active		11.2.0 11.2.0
2012-03	CT#55	GE-120020	1134	I	Bearer Context to be modified in the Modify Bearer Request		11.2.0
2012-03	01#35	CP-120036	1077	4	message	11.1.0	11.2.0
2012-03	CT#55	CP-120036	1113	2	Mapping between S11/S4 and NAS Cause values	11.1.0	11.2.0
2012-03	CT#55	CP-120036	1114	1	Absolute time for MBMS data transfer start and stop		11.2.0
2012-03	CT#55	CP-120036	1155	1	Cause code description		11.2.0
2012-03	CT#55	CP-120036	1158	-	SRVCC PS to CS Response	11.1.0	11.2.0
2012-03	CT#55	CP-120036	1170	1	Charging ID for Non-3GPP IP Access	11.1.0	11.2.0
2012-03	CT#55	CP-120036	1171	1	Sender's F-TEID for Control Plane		
2012-03	CT#55				Clean up of the irrelevant cause codes from the GTPv2 triggered	11.1.0	11.2.0
		CP-120036	1173	1	messages		
2012-03	CT#55	OD 400000	4475	~	PGW based provisioning of the DNS server address for the S2b	11.1.0	11.2.0
2012-03	CT#55	CP-120036 CP-120036	1175 1177	2	interface GTPv2 header	11 1 0	11 2 0
2012-03	CT#55	CP-120030 CP-120042	1159	2	New IEs for ePDG scenario		11.2.0 11.2.0
2012-03	CT#55	CP-120042	1161	-	Voice/Video bearer for vSRVCC		11.2.0
2012-03	CT#55	CP-120045	1163	-	Addition of GTP based S2a in clauses 1 to 6		11.2.0
2012-03	CT#55	CP-120045	1164	1	Create Session Request on GTP based S2a	-	11.2.0
2012-03	CT#55	CP-120045	1165	1	Create Bearer Request on GTP based S2a		11.2.0
2012-03	CT#55				Delete Session Request & Delete Bearer Request on GTP based		11.2.0
		CP-120045	1166	1	S2a		
2012-03	CT#55				Modify Bearer Command & Update Bearer Request on GTP	11.1.0	11.2.0
0040.00	OT#55	CP-120045	1167	1	based S2a	44.4.0	44.0.0
2012-03	CT#55	CP-120045	1168	1	Trace Session Activation & Deactivation on GTP based S2a		11.2.0
2012-03	CT#55	CP-120045	1169	-	Delete PDN Connection Set on GTP based S2a		11.2.0
2012-06 2012-06	CT#56 CT#56	CP-120230 CP-120230	1156 1157	1 3	CSR and MBR message for SGW restoration procedure Context Response message		11.3.0 11.3.0
2012-06	CT#56 CT#56	CP-120230 CP-120233	1157	3	Reporting of H(e)NB local IP address and port	11.2.0	
2012-06	CT#56	CP-120233 CP-120228	1182	5	reporting or rite/rite locar in address and port	11.2.0	11.3.0
2012-00	CT#56	51 120220	1102		Adding Originating Node IE to the Delete Session Request for ISR	11.2.0	11.3.0
	2		4400	5	cases		
		CP-120228	1183				44.0.0
2012-06	CT#56	CP-120228 CP-120233	1183 1186	1		11.2.0	11.3.0
2012-06 2012-06	CT#56 CT#56	CP-120228 CP-120233 CP-120240			Updated UE local IP in S2b procedure Network provided Location Information	11.2.0 11.2.0	11.3.0
		CP-120233	1186	1	Updated UE local IP in S2b procedure	11.2.0	
2012-06	CT#56	CP-120233 CP-120240	1186 1187	1 2	Updated UE local IP in S2b procedure Network provided Location Information	11.2.0 11.2.0	11.3.0
2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230	1186 1187 1191 1194 1195	1 2	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier	11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230	1186 1187 1191 1194 1195 1196	1 2 1 - 1	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230 CP-120234	1186 1187 1191 1194 1195 1196 1197	1 2 1 - 1 2	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230 CP-120234 CP-120228	1186 1187 1191 1194 1195 1196 1197 1198	1 2 - - 1 2 1	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230 CP-120234	1186 1187 1191 1194 1195 1196 1197	1 2 1 - 1 2	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230 CP-120234 CP-120228 CP-120228	1186 1187 1191 1194 1195 1196 1197 1198 1199	1 2 1 - 1 2 1 3	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active ULI inclusion condition during Service Request procedure when	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120228 CP-120230 CP-120230 CP-120234 CP-120228	1186 1187 1191 1194 1195 1196 1197 1198	1 2 - - 1 2 1	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active ULI inclusion condition during Service Request procedure when ISR is active	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120230 CP-120230 CP-120234 CP-120228 CP-120228 CP-120228	1186 1187 1191 1194 1195 1196 1197 1198 1199 1200	1 2 1 - 1 2 1 3 2	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active ULI inclusion condition during Service Request procedure when ISR is active Addition of Subnet Mask and Default Router Address in Create	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120228 CP-120230 CP-120230 CP-120234 CP-120228 CP-120228 CP-120228 CP-120228	1186           1187           1191           1194           1195           1196           1197           1198           1199           1200           1201	1 2 1 - 1 2 1 3 2 1	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active ULI inclusion condition during Service Request procedure when ISR is active Addition of Subnet Mask and Default Router Address in Create Session Response for Trusted WLAN Access over S2a	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0
2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06 2012-06	CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56 CT#56	CP-120233 CP-120240 CP-120224 CP-120230 CP-120230 CP-120234 CP-120228 CP-120228 CP-120228	1186 1187 1191 1194 1195 1196 1197 1198 1199 1200	1 2 1 - 1 2 1 3 2	Updated UE local IP in S2b procedure Network provided Location Information CFSI in the modify access bearers request The usage of TEID0 Inclusion of MME/S4-SGSN Identifier PGW Downlink Triggering Notification/Acknowledge Additions for CS to PS SRVCC Mapping of NAS ESM/SM Cause codes to S11/S4 Cause codes Release of old S3 GTP-C TEIDs during I-RAT HO with ISR active ULI inclusion condition during Service Request procedure when ISR is active Addition of Subnet Mask and Default Router Address in Create	11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0 11.2.0	11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0 11.3.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2012-06	CT#56	CP-120228	1211	-	More choices of mapping between GTPv2 cause code to the NAS ESM/SM Cause codes	11.2.0	11.3.0
2012-06	CT#56	CP-120228	1213	1	Extended RNC ID in Target Identification IE	11.2.0	11.3.0
2012-06	CT#56	01 120220	1210		Clarification to "SGW node name" & "SGW S11/S4 IP Address	11.2.0	
	0	CP-120228	1214	1	and TEID for Control Plane" IE presence conditions		
2012-09	CT#57				SGW DL/UL F-TEID for data forwarding in Forward Relocation	11.3.0	11.4.0
		CP-120448	1230	-	Response message		
2012-09	CT#57	CP-120477	1216	1	RAT Type for EPC access via TWAN	11.3.0	
2012-09	CT#57	CP-120457	1217	-	Encoding of Absolute Time of MBMS Data Transfer	11.3.0	
2012-09	CT#57	CP-120457	1219	2	Sender's F-TEID in the Forward Relocation Response	11.3.0	
2012-09	CT#57				Presence condition of APN-AMBR in the Modify Bearer Response	11.3.0	11.4.0
0040.00	07/157	CP-120457	1221	-	message	44.0.0	
2012-09	CT#57	CP-120457	1222	2	GTP Tunnel	11.3.0	
2012-09	CT#57	CP-120457	1224 1226	1	Delete Session Request usage in SGW with active ISR	11.3.0 11.3.0	
2012-09 2012-09	CT#57 CT#57	CP-120457 CP-120457	1226	-	Context Request note error PAA clarification for PDN type IPv4v6	11.3.0	
2012-09	CT#57	CP-120457 CP-120457	1220	2	F-TEID interface types for Indirect Forwarding	11.3.0	
2012-09	CT#57	CP-120457 CP-120457	1232	2		11.3.0	
2012-09	CT#57	CP-120457 CP-120457	1235	2	Zero TEID Usage In Relocation Cancel Response PDP connection inactivity timer expires	11.3.0	
2012-09	CT#57	CP-120437 CP-120475	1235	1	MSV flag in rSRVCC procedure	11.3.0	
2012-09	CT#57	CP-120475 CP-120475	1220	-	Selected PLMN ID	11.3.0	
2012-09	CT#57 CT#57	CP-120475 CP-120656	1230	-	Reference list correction to align with the corrected TS 29.212 title	11.3.0	
2012-09	CT#57	CP-120656 CP-120718	1237	1	Removal of Maximum MBR/APN-AMBR	11.3.0	
2012-12	CT#58	01-120/10	1240		Change to Report Flags for delayed reporting of change of SN/TZ	11.4.0	
2012-12	01#30	CP-120718	1243	3	during inter-CN node mobility	11.4.0	11.5.0
2012-12	CT#58	CP-120718	1270	1	Additional MBR for delayed reporting of change of SN/TZ/UCI	11.4.0	1150
2012-12	CT#58	CP-120718	1291	3	Delete Bearer Request with ISR deactivation	11.4.0	
2012-12	CT#58	CP-120744	1231	4	Adding a Cause Value in Delete Session Request message	11.4.0	
2012-12	CT#58	CP-120744	1238	-	Forward Relocation Request over the S3 interface		11.5.0
2012-12	CT#58	01 120744	1230		Corrections to reference titles and octet numbering of IE		11.5.0
2012 12	01//00	CP-120744	1244	-	definitions		11.0.0
2012-12	CT#58				Clarifications on sending/new node and receiving/old node about	11.4.0	11.5.0
		CP-120744	1245	-	Identification Request message		
2012-12	CT#58	CP-120744	1246	-	Multiple CSID	11.4.0	11.5.0
2012-12	CT#58				TEID of the Change Notification Request and Response	11.4.0	11.5.0
		CP-120744	1247	-	messages		
2012-12	CT#58	CP-120744	1253	3	Suspend Notification/Acknowledge message in SGSN pool	11.4.0	11.5.0
2012-12	CT#58	CP-120744	1254	-	Sender F-TEID IE in Modify Bearer Request message	11.4.0	11.5.0
2012-12	CT#58	CP-120744	1262	1	Clarification of Delete Bearer Failure Indication	11.4.0	11.5.0
2012-12	CT#58	CP-120744	1263	2	Cause value "ISR deactivation"	11.4.0	
2012-12	CT#58	CP-120744	1264	1	IPv4 address allocation	11.4.0	11.5.0
2012-12	CT#58				Sender F-TEID in DDN msg (network triggered service restoration	11.4.0	11.5.0
		CP-120744	1265	1	procedure)		
2012-12	CT#58	CP-120744	1268	-	Correction to IP Address Instance values in CSReq & MBReq		11.5.0
2012-12	CT#58				Clarifications on value definitions of PDN Type, Security Mode and	11.4.0	11.5.0
0040.40	07/150	CP-120744	1273	-	Used NAS Cipher IE		44 5 0
2012-12	CT#58	00 400744	4070	4	Clarification on UCI in Create Session Request message during	11.4.0	11.5.0
0040.40	07//50	CP-120744	1276	1	SGW relocation	44.4.0	44.5.0
2012-12	CT#58	CP-120744	1283	1	Change reporting requested by PCRF		11.5.0
2012-12	CT#58	CP-120744	1294	1	Selected PLMN ID		11.5.0
2012-12	CT#58	CP-120739 CP-120739	1271 1278	1	Sender F-TEID in PGW Downlink Triggering Notification	11.4.0	
2012-12 2012-12	CT#58	0-120/39	1 1 Z / Ŏ	2	SGW failure when ISR is active enhancement	11.4.0	
12012-12	CT#FO			2		4	11.5.0
	CT#58	CP-120733	1272	2	TWAN operator identification for EPC access charging		11 5 0
2012-12	CT#58	CP-120733 CP-120733	1272 1286	3	Trusted WLAN AP identity over GTP S2a	11.4.0	
2012-12 2012-12	CT#58 CT#58	CP-120733 CP-120733 CP-120726	1272 1286 1279	3 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request	11.4.0 11.4.0	11.5.0
2012-12 2012-12 2012-12	CT#58 CT#58 CT#58	CP-120733 CP-120733 CP-120726 CP-120710	1272 1286 1279 1257	3 1 2	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message	11.4.0 11.4.0 11.4.0	11.5.0 11.5.0
2012-12 2012-12 2012-12 2012-12	CT#58 CT#58 CT#58 CT#58	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744	1272 1286 1279 1257 1258	3 1 2 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution"	11.4.0 11.4.0 11.4.0 11.4.0	11.5.0 11.5.0 11.5.0
2012-12 2012-12 2012-12 2012-12 2013-03	CT#58 CT#58 CT#58 CT#58 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021	1272 1286 1279 1257 1258 1306	3 1 2 1 2	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network	11.4.0 11.4.0 11.4.0 11.4.0 11.5.0	11.5.0 11.5.0 11.5.0 11.6.0
2012-12 2012-12 2012-12 2012-12 2013-03 2013-03	CT#58 CT#58 CT#58 CT#58 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021	1272 1286 1279 1257 1258 1306 1307	3 1 2 1 2 2	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call	11.4.0 11.4.0 11.4.0 11.4.0 11.5.0 11.5.0	11.5.0 11.5.0 11.5.0 11.6.0 11.6.0
2012-12 2012-12 2012-12 2012-12 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#58 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130018	1272 1286 1279 1257 1258 1306 1307 1310	3 1 2 1 2	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0	11.5.0 11.5.0 11.6.0 11.6.0 11.6.0
2012-12 2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130018 CP-130027	1272 1286 1279 1257 1258 1306 1307 1310 1320	3 1 2 1 2 2 2 -	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0	11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 11.6.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130018 CP-130027 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296	3 1 2 1 2 2 2 - 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0	11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 11.6.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130018 CP-130027	1272 1286 1279 1257 1258 1306 1307 1310 1320	3 1 2 1 2 2 2 -	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility"	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0 11.6.0	11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130027 CP-130029 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296 1297	3 1 2 1 2 2 2 - 1 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility" Corrections to abbreviation of Radio Access Technology and	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0	11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130027 CP-130029 CP-130029 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296 1297 1302	3 1 2 1 2 2 2 - 1 1 1 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility" Corrections to abbreviation of Radio Access Technology and definition of cause value	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0 11.6.0	11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130027 CP-130029 CP-130029 CP-130029 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296 1297 1302 1303	3 1 2 1 2 2 2 - 1 1 1 1 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility" Corrections to abbreviation of Radio Access Technology and definition of cause value Corrections to descriptions of RFSP Index	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0	11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0 12.0.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130027 CP-130029 CP-130029 CP-130029 CP-130029 CP-130029 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296 1297 1302 1303 1311	3 1 2 1 2 2 - 1 1 1 1 1 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility" Corrections to abbreviation of Radio Access Technology and definition of cause value Corrections to descriptions of RFSP Index Correct the NOTE for Cause value	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0	11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0 12.0.0 12.0.0 12.0.0
2012-12 2012-12 2012-12 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03 2013-03	CT#58 CT#58 CT#58 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59 CT#59	CP-120733 CP-120733 CP-120726 CP-120710 CP-120744 CP-130021 CP-130021 CP-130027 CP-130029 CP-130029 CP-130029 CP-130029	1272 1286 1279 1257 1258 1306 1307 1310 1320 1296 1297 1302 1303	3 1 2 1 2 2 2 - 1 1 1 1 1	Trusted WLAN AP identity over GTP S2a H(e)NB local IP address/port in create session request Removal of TFT IE from Create Session Response message Clarifications on RAT Type Values "UTRAN" and "HSPA evolution" Populating Serving Network IMSI in Suspend Notification for UICCless Emergency Call User CSG Information reporting during inter-MME/SGSN mobility Sending SSID for SaMOG in GTP Bearer QoS Clarificatyion of term "PS mobility" Corrections to abbreviation of Radio Access Technology and definition of cause value Corrections to descriptions of RFSP Index	11.4.0 11.4.0 11.4.0 11.5.0 11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 11.6.0 11.6.0	11.5.0 11.5.0 11.5.0 11.6.0 11.6.0 11.6.0 12.0.0 12.0.0 12.0.0 12.0.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2013-03	CT#59			_	Correcting the Flow QoS IE reference for Bearer Resource	11.6.0	12.0.0
	07/170	CP-130029	1319	1	Command		10.0.0
2013-03	CT#59	CP-130031	1308	1	Clarification of Resume when S4-U is enabled		12.0.0
2013-03	CT#59 CT#60	CP-130031	1313 1324	1	Stop Paging Indication in service restoration procedure		12.0.0 12.1.0
2013-06 2013-06	CT#60	CP-130304 CP-130304	1324		Direct Tunnel Flag Handling ASN.1/PER encoded parameters		12.1.0
2013-00	CT#60	CP-130304	1321	2	Presence requirements clarification		12.1.0
2013-06	CT#60	CP-130304	1330	3	CR on Unaccepted PDN connection during TAU and Handover		12.1.0
2013-06	CT#60	CP-130304	1343	1	TWAN Identifier		12.1.0
2013-06	CT#60	CP-130304	1339	1	Missing Recovery IE		12.1.0
2013-06	CT#60	CP-130304	1337	2	The setting EPS bearer ID/ARP for MME paging strategy	12.0.0	12.1.0
2013-06	CT#60				Delete Bearer Request triggered by PMIP error indication	12.0.0	12.1.0
		CP-130304	1336	2	message		
2013-06	CT#60	CP-130304	1332	1	Prohibit Payload Compression Indication Corrections		12.1.0
2013-06	CT#60	CP-130296	1341	2	ULI Timestamp		12.1.0
2013-06	CT#60	CP-130378	1323	1	SIPTO at the local network		12.1.0
2013-06	CT#60	CP-130282	1346	-	Removal of TFT IE from Create Session Response message	-	12.1.0
2013-06	CT#60	CP-130290	1329	2	Bearer Context to be modified in Modify Bearer Request		12.1.0
2013-09	CT#61	00 400 440	4050		Reporting ULI and TimeZone at MME-initiated bearer related	12.1.0	12.2.0
0040.00	07/04	CP-130449	1350	1	procedures	40.4.0	40.0.0
2013-09	CT#61	CP-130454	1347	1	New MBMS flags for eMBMS restoration		12.2.0
2013-09	CT#61	CP-130467	1348	1	Serving Network IE definition		12.2.0
2013-09	CT#61	CP-130467	1354	3	Indication Flags		12.2.0
2013-09	CT#61	CP-130467	1355	2	Sending Recovery IE in GTPv2-C messages	-	12.2.0
2013-09	CT#61	CP-130467	1361	2	Enforcing access restriction during I-RAT RAU/TAU procedures		12.2.0
2013-09	CT#61	CP-130467	1371	1	Modify Access Bearer for Intra TAU w/o SGW change		12.2.0
2013-09	CT#61	CP-130467	1372	1	GTP-C message types for rSRVCC		12.2.0
2013-09	CT#61	CP-130446	1352	1	Returning to former LTE PLMN after CSFB		12.2.0
2013-09	CT#61	CD 120112	1000	4	Inclusion of ePDG IP address of IKEv2 tunnel endpoint on S2b-	12.1.0	12.2.0
0040.00	07/04	CP-130443	1363	1	GTP	40.4.0	40.0.0
2013-09	CT#61	CP-130453	1364	1	SIPTO at the Local Network		12.2.0
2013-09	CT#61	CP-130462	1365	1	GERAN lu Mode		12.2.0
2013-09	CT#61	CP-130470	1366	-	Update to cover the S121		12.2.0
2013-09	CT#61	CP-130583	1368	4	ULI Timestamp IE format		12.2.0
2013-12	CT#62	CP-130626	1374	3	Reporting the RAN/NAS release cause during bearer release procedures	12.2.0	12.3.0
2013-12	CT#62	CP-130626	1374	-	MM Context IE in Identification Response	1220	12.3.0
2013-12	CT#62	CP-130626	1376	4	Core Network Operator selection origin		12.3.0
2013-12	CT#62	CP-130626	1378	1	Correct Presence requirement for Conditional IE		12.3.0
2013-12	CT#62	CP-130626	1382	1	Delete Session Request/Response		12.3.0
2013-12	CT#62	CP-130626	1383	1	Correction the ULI for RAI IE		12.3.0
2013-12	CT#62	CP-130626	1384	1	Correct the Message Type value reserved for S101		12.3.0
2013-12	CT#62	CP-130626	1385	1	Harmonisation of the abbreviation LBI		12.3.0
2013-12	CT#62	CP-130626			Variable length parameters in GTPv2 IEs		12.3.0
2013-12	CT#62	CP-130626		1	Removing APN-AMBR from Modify Bearer Response		12.3.0
2013-12	CT#62	01-100020	1002	1	Clarification on encoding of bit rates when converting bits per		12.3.0
2010 12	01//02				second received over Diameter interfaces to kilo bits per second	12.2.0	12.0.0
		CP-130626	1393	1	over GTPv2.		
2013-12	CT#62	CP-130626	1396	2	Correct the value of the Selection Mode IE	12.2.0	12.3.0
2013-12	CT#62	CP-130626	1397	1	Cause IE condition in the Delete Session Request		12.3.0
2013-12	CT#62	CP-130626	1398	2	S1-U eNodeB F-TEID in Create Bearer Response		12.3.0
2013-12	CT#62	CP-130626	1400	2	SS code used in the Paging message		12.3.0
2013-12	CT#62	CP-130626	1405	1	PGW IP Addresses in Initial Messages		12.3.0
2013-12	CT#62	CP-130626	1406	2	PGW and SGW Charging alignment in downlink	12.2.0	12.3.0
2013-12	CT#62				ULI reporting in the Create Session Request and Modify Bearer		12.3.0
		CP-130613	1387	2	Request message		
2013-12	CT#62	CP-130604	1390	1	Correction on Trace information		12.3.0
2013-12	CT#62				Support HO indication and additional PDN request on the S2a	12.2.0	12.3.0
		CP-130633	1394	2	GTP interface		
2014-03	CT#63	CP-140029	1409	1	F-TEID Interface Type 8	12.3.0	12.4.0
2014-03	CT#63	CP-140029	1410	2	S12, S4-U, S1-U F-TEID values	12.3.0	12.4.0
2014-03	CT#63	CP-140029	1411	2	Triggered messages		12.4.0
2014-03	CT#63	CP-140029	1413	2	F-Container Definition Correction		12.4.0
2014-03	CT#63	CP-140029	1417	2	CSG Membership Indication values		12.4.0
	CT#63	CP-140029	1418	1	Dummy IMSI in Resume Notification	12.3.0	12.4.0
2014-03			1 1 1 0	2	Sender F-TEID in the Delete Session Request message	1230	12.4.0
2014-03	CT#63	CP-140029	1419				
2014-03 2014-03		CP-140029	1419	1	PLMN ID communicated to the HPLMN in network sharing		12.4.0
2014-03 2014-03 2014-03	CT#63 CT#63 CT#63	CP-140029 CP-140030			PLMN ID communicated to the HPLMN in network sharing TWAN-ID reporting extensions for NPLI for TWAN access	12.3.0 12.3.0	12.4.0 12.4.0
2014-03 2014-03 2014-03 2014-03	CT#63 CT#63 CT#63 CT#63	CP-140029 CP-140030 CP-140030	1423 1421 1422	1	PLMN ID communicated to the HPLMN in network sharing TWAN-ID reporting extensions for NPLI for TWAN access TWAN-ID contents extensions for NPLI for TWAN access	12.3.0 12.3.0 12.3.0	12.4.0 12.4.0 12.4.0
2014-03 2014-03 2014-03	CT#63 CT#63 CT#63	CP-140029 CP-140030	1423 1421	1 1	PLMN ID communicated to the HPLMN in network sharing TWAN-ID reporting extensions for NPLI for TWAN access	12.3.0 12.3.0 12.3.0 12.3.0	12.4.0 12.4.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2014-03	CT#63	CP-140022	1431	1	Update the ULI Timestamp IE format	12.3.0	12.4.0
2014-03	CT#63	CP-140022	1435	2	Bearer context in Update Bearer Response when DTF is set		12.4.0
2014-03	CT#63	CP-140021	1433	1	Temporarily rejected due to mobility procedure in progress		12.4.0
2014-03	CT#64	00.440004	4.400	~	Introduction of Node Number and Node Identifier (to carry SGSN	12.4.0	12.5.0
2014.00	CT#64	CP-140261	1438	3	Lgd Identifier and MME SLg identifier)	12.4.0	10 5 0
2014-06	CT#64	CP-140261	1443	1	Number of authentication vectors in the MM Context IE	-	
2014-06	CT#64	CP-140261	1444	2	Context Response with P-TMSI Signature mismatch		12.5.0
2014-06	CT#64	CP-140261	1448	1	Including CSG change reporting for Change Notification procedure Spare bits in MM Context	12.4.0	12.5.0
2014-06 2014-06	CT#64 CT#64	CP-140261 CP-140261	1452 1455	1	User CSG Information reporting in rollback case		12.5.0
2014-06	CT#64	CP-140261 CP-140261	1455	1	Corrections to Node Type	_	12.5.0
2014-00	CT#64	CP-140201 CP-140261	1450	1	Update the condition of the UE Time Zone IE	-	12.5.0
2014-00	CT#64	01-140201	1457	1	A new Cause Value for the case where an MME in the VPLMN	_	12.5.0
2014 00	01#04	CP-140261	1460	1	refuses to setup/modify a Bearer	12.4.0	12.0.0
2014-06	CT#64	CP-140261	1478	2	Alternate LMA address for user plane	12.4.0	12.5.0
2014-06	CT#64	CP-140261	1479	1	PLMN ID communicated in the VPLMN in network sharing		12.5.0
2014-06	CT#64	CP-140261	1482	1	Version Not Supported Indication		12.5.0
2014-06	CT#64	CP-140261	1489	3	IPv6 address allocation		12.5.0
2014-06	CT#64	CP-140261	1490	3	Context Request Indication flags		12.5.0
2014-06	CT#64	01 110201	1100	Ŭ	Update cause to indicate downlink message delivery failure due to		12.5.0
201100	•••••	CP-140235	1445	5	crash with mobility event		
2014-06	CT#64	CP-140235	1447	2	MDT configuration during inter-MME handover	12.4.0	12.5.0
2014-06	CT#64	CP-140242	1441	3	Reporting changes of UE presence in Presence Reporting Area		12.5.0
2014-06	CT#64	CP-140247	1451	-	PCO in the HO to TWAN procedures		12.5.0
2014-06	CT#64	CP-140247	1487	2	PCO in handover to 3GPP access	12.4.0	
2014-06	CT#64	CP-140252	1439	1	TWAN Identifier Timestamp		12.5.0
2014-06	CT#64	CP-140252	1440	-	Civic address encoding	12.4.0	12.5.0
2014-06	CT#64				Extension to the TWAN Identifier contents: new Line Identifier	12.4.0	12.5.0
		CP-140252	1459	4	(Logical Access ID)		
2014-06	CT#64	CP-140252	1481	2	SSID not sufficient for TWAN location	12.4.0	12.5.0
2014-06	CT#64	CP-140241	1461	1	Propagation of MME/S4-SGSN identity to PGW	12.4.0	12.5.0
2014-06	CT#64				Updating PGW with overload control information of target	12.4.0	12.5.0
		CP-140241	1462	1	MME/S4-SGSN		
2014-06	CT#64	CP-140241	1463	1	Interaction with congestion control using APN back-off timer	12.4.0	12.5.0
2014-06	CT#64				Discovery of the support of the GTP signalling based Load Control	12.4.0	12.5.0
		CP-140241	1464	1	feature by the peer node		
2014-06	CT#64				Discovery of the support of the GTP signalling based Overload	12.4.0	12.5.0
0044.00	07/04	CP-140241	1465	1	Control feature by the peer node	10.1.0	10 5 0
2014-06	CT#64	00 4400 44	4.400		Issues in the network with partial support of the GTP Load Control	12.4.0	12.5.0
2011.00	OT#04	CP-140241	1466	1	feature	10.1.0	12.5.0
2014-06	CT#64	CP-140241	1467	1	Issues in the network with partial support of the GTP Overload Control feature	12.4.0	12.5.0
2014-06	CT#64	CP-140241 CP-140241	1467	1	Implicit overload control mechanisms	1240	12.5.0
	CT#64	CP-140241	1469	2	Load control solution: General aspects		12.5.0
2014-00	CT#64	CP-140241	1470	3	Overload control solution: General aspects		12.5.0
2014-00	CT#64	GF-140241	1470	5	Addition of Load & Overload Control Info IEs in session mgmt.		12.5.0
2014-00	01#04	CP-140241	1471	1	messages	12.4.0	12.5.0
2014-06	CT#64	CP-140241	1472	2	Definition of new IEs for Load & Overload Control feature	1240	12.5.0
2014-06	CT#64	CP-140241	1475	1	Overload problem, scenarios, load and overload control concepts		12.5.0
2014-06	CT#64	CP-140241	1476	1	Overload control: message throttling		12.5.0
2014-06	CT#64	CP-140241	1477	2	Enforcement of overload control		12.5.0
2014-06	CT#64	CP-140241	1480	2	Load control information		12.5.0
2014-06	CT#64	CP-140241	1488	2	Overload Control Information		12.5.0
2014-09	CT#65	CP-140512	1492	-	Handovers between non-3GPP and 3GPP access		12.6.0
2014-09	CT#65	CP-140512	1493	2	Setting Handover Indication flag		12.6.0
2014-09	CT#65				Reporting the RAN/NAS cause during bearer		12.6.0
		CP-140512	1507	2	creation/modification failure scenarios		
2014-09	CT#65	CP-140512	1510	1	Correct procedure name for PDN connection deactivation	12.5.0	12.6.0
2014-09	CT#65	CP-140512	1512	1	Repeated procedure description	12.5.0	12.6.0
2014-09	CT#65	CP-140512	1514	-	Create Session Request received for an existing PDN connection	12.5.0	12.6.0
2014-09	CT#65	CP-140512	1515	2	Deferred SN/CSG/Time zone change reporting in GERAN	12.5.0	12.6.0
2014-09	CT#65	CP-140502	1495	2	MDT PLMN List configuration parameter		12.6.0
2014-09	CT#65	CP-140502	1509	1	Bearer contexts in Modify Access Bearers Request		12.6.0
2014-09	CT#65				Inclusion of MME/S4-SGSN Identifier in the Create/Update/Delete	12.5.0	12.6.0
		CP-140505	1496	3	Bearer Response message		
2014-09	CT#65	CP-140505	1498	1	Addition of missing changes		12.6.0
2014-09	CT#65				Inclusion PRA information in the Create/Update Bearer Response	12.5.0	12.6.0
		CP-140522	1497	1	message		
		CD 110500	1500	-	Reporting changes of UE presence in a Presence Reporting Area	1250	12.6.0
2014-09	CT#65	CP-140522					
2014-09 2014-09 2014-09	CT#65 CT#65 CT#65	CP-140522 CP-140522 CP-140506	1500 1501 1499	2	ULI change reporting when E-RAB/RAB/user plane is established P-CSCF Restoration Indication	12.5.0	12.6.0 12.6.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2014-09	CT#65	CP-140521	1511	3	Introduction of Dual Connectivity Function	12.5.0	12.6.0
2014-09	CT#65	CP-140518	1513	2	PGW F-TEID in the PGW Downlink Triggering Notification		12.6.0
2014-09	CT#65	CP-140501	1518	-	BSS container in Forward Relocation Request / Response		12.6.0
2014-12	CT#66	CP-140758	1505	3	Target Cell Identification in E-UTRAN to GERAN PS Handover		12.7.0
2014-12	CT#66	CP-140761	1540	2	P-CSCF Address Inclusion in PCO IE of Update Bearer Request		12.7.0
2014-12	CT#66	CP-140795	1519	2	Handling of load control and overload control parameters		12.7.0
2014-12 2014-12	CT#66	CP-140795 CP-140795	1520	3	Overload control message prioritization		12.7.0 12.7.0
	CT#66 CT#66		1521	2	Propagating the MME/S4-SGSN identity to the PGW Overload/Load Control Information IE on S2a/S2b/S4/S11		12.7.0
2014-12 2014-12	CT#66	CP-140795	1542	1	EBI value to use in Downlink Data Notification Triggered by a		12.7.0
2014-12	C1#00	CP-140972	1523	1	Dedicated Bearer Activation procedure when ISR is active	12.0.0	12.7.0
2014-12	CT#66	01 140072	1020		Essential clarification on the usage of cause code "Context Not	12.6.0	12.7.0
2014 12	01//00	CP-140972	1526	3	Found"	12.0.0	12.7.0
2014-12	CT#66	CP-140972	1528	2	Pending subscription change	12.6.0	12.7.0
2014-12	CT#66	CP-140972	1532	3	Handovers from non-3GPP IP access to 3GPP IP access		12.7.0
2014-12	CT#66	CP-140972	1534	1	Removal of Optimized HO procedure from HRPD to EUTRAN		12.7.0
2014-12	CT#66	CP-140972	1535	-	Type value of the BSS Container IE in Context Response	12.6.0	12.7.0
2014-12	CT#66	CP-140972	1536	1	Length of Recovery IE	12.6.0	12.7.0
2014-12	CT#66				Additional cause code mapping for non-availability of Services due	12.6.0	12.7.0
		CP-140972	1541	3	to LTE-Roaming		
2014-12	CT#66	CP-140972	1544	-	Missing Value definition of GUTI	12.6.0	
2014-12	CT#66	CP-140972	1545	3	Message piggybacking clarification		12.7.0
2014-12	CT#66	00 4 4070 4	4505		Paging stop indication for ISR during P-CSCF restoration	12.6.0	12.7.0
004440	OT#00	CP-140794	1525	1	procedure	40.0.0	40 7 0
2014-12	CT#66	CP-140972	1527	2	MEI in Create Session Request	12.6.0	
2014-12	CT#66	CP-140794	1529	1	Bearer Contexts to be modified IE in 'Modify Bearer Request		12.7.0
2014-12	CT#66	CP-140779	1530	1 5	TWAN PLMN ID		12.7.0 12.7.0
2014-12 2014-12	CT#66 CT#66	CP-140780	1533	Э	WLAN Offloadability transfer during mobility procedures No change S1 SGW F-TEID in E-UTRAN Initiated E-RAB	12.6.0	
2014-12	C1#00	CP-140789	1543	1	modification procedure	12.0.0	12.7.0
2014-12	CT#66	01 140705	1040		Inclusion of PCO in Delete Session/Bearer Request for TWAN	12.6.0	12.7.0
2014-12	01#00	CP-140784	1548	1	access	12.0.0	12.7.0
2014-12	CT#66	CP-140796	1524	2	Provisioning of P-CSCF address via APCO for S2b	12.7.0	13.0.0
2014-12	CT#66	CP-140760	1546	1	GTP-C overload control from TWAN/ePDG to PGW		13.0.0
2015-03	CT#67	CP-150037	1547	3	MBMS Alternative IP Multicast Distribution Address		13.1.0
2015-03	CT#67	CP-150037	1550	1	Clarification of RAC encoding	13.0.0	13.1.0
2015-03	CT#67	CP-150037	1551	1	MBMS Flow Identifier clarification	13.0.0	13.1.0
2015-03	CT#67	CP-150037	1554	1	Unexpected GTP message clarification		13.1.0
2015-03	CT#67	CP-150037	1556	1	UE Registration Query	13.0.0	13.1.0
2015-03	CT#67	CP-150037	1557	3	Correction on definition of IMSI		13.1.0
2015-03	CT#67				Bearer Contexts in Create Bearer Response, Update Bearer	13.0.0	13.1.0
		00 450007	4550		Response and Delete Bearer Response for partial failure and		
2015 02	CT#67	CP-150037 CP-150037	1559 1561	1	success cases. Cause IMSI not known	10.0.0	13.1.0
2015-03 2015-03		0		-		13.0.0	
2015-03	CT#67 CT#67	CP-150037 CP-150025	1566 1553	1 2	TWAN Release Cause ULI IE condition in Create session Request message		13.1.0
2015-03	CT#67	CP-150025	1563	1	PDN Type in PAA IE for S2b case		13.1.0
2015-03	CT#67	CP-150025	1568	1	ULI change reporting upon inter-RAT mobility	13.0.0	
2015-03	CT#67	CP-150041	1565	1	Paging Policy Indication in Downlink Data Notification message		13.1.0
2015-06	CT#68	CP-150254	1589	-	ARP Value in Downlink Data Notification message		13.2.0
2015-06	CT#68				Contents of ULI IE in the Modify Bearer Request during		13.2.0
		CP-150254	1594	1	Handovers to UTRAN		
2015-06	CT#68				TEID-C header value not known / Failure Indication message	13.1.0	13.2.0
		CP-150270	1570	3	Cause value rules		
2015-06	CT#68	CP-150270	1573	-	RAT Type in Change Notification Request		13.2.0
2015-06	CT#68	CP-150270	1575	2	PCO in CSReq for handover to TWAN with GTP over S2a		13.2.0
2015-06	CT#68	CP-150270	1576	2	Correction to ULI inclusion for PDP activation procedure		13.2.0
2015-06	CT#68	CP-150270	1577	3	IE inclusion for non-3GPP to 3GPP handover case		13.2.0
2015-06	CT#68	CP-150270	1578	-	Inclusion of EBI in Delete Bearer Request message		13.2.0
2015-06	CT#68	CP-150270	1581	2	User CSG Information in TAU/RAU with SGW change procedure		13.2.0
2015-06	CT#68	CP-150270	1582	2	Session/bearer release cause over S2a	13.1.0	
2015-06	CT#68	CP-150270	1583	2	Session/bearer release cause over S2b		13.2.0
2015-06	CT#68	CP-150270	1599	1	At receiving Delete Bearer Failure Indication sent on zero-TEID		13.2.0
2015-06	CT#68	CP-150270	1600	1	UCI condition in Modify Bearer Request message		13.2.0
2015-06	CT#68	CP-150270	1601	2	Upon receiving unexpected triggered messages		13.2.0
2015-06 2015-06	CT#68 CT#68	CP-150270 CP-150270	1603 1604	1 1	Correction to ULI for the S5/S8 interface Presence condition of embedded IEs in a Grouped IE		13.2.0 13.2.0
2015-06	CT#68	CP-150270 CP-150270	1604	1	EBI and ARP in DDN message sent to S4-SGSN		13.2.0
2015-06	CT#68	51-150270	1000		Message Granularity of Restoration/Recovery and Path		13.2.0
2010-00	511700	CP-150270	1606	1	Management messages	10.1.0	10.2.0
2015-06	CT#68	CP-150274	1595	1	IMEI(SV) signalling over GTP based S2a and S2b	13.1.0	13.2.0
				•			

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2015-09	CT#69				Modify Access Bearers Request leading to unpause charging in	13.2.0	13.3.0
2015-09	CT#69	CP-150433	1615	-	the PGW Receipt of a Create Session Request at SGW colliding with an	12.2.0	13.3.0
2015-09	01#09	CP-150442	1608	1	existing PDN connection context	13.2.0	13.3.0
2015-09	CT#69	CP-150442	1609	2	Detection and handling of late arriving requests	13.2.0	13.3.0
2015-09	CT#69				eDRX impact on GTPv2 for network originated control plane	13.2.0	13.3.0
	07/00	CP-150439	1610	1	procedure	10.0.0	(0.0.0
2015-09	CT#69	CD 150454	1611	2	Enhancement in Downlink Data Notification Acknowledgement for	13.2.0	13.3.0
2015-09	CT#69	CP-150454	1011	2	extended buffering in the SGW Data forwarding for buffered DL data during TAU/RAU with SGW	13.2.0	13.3.0
2010 00	01//00	CP-150454	1612	2	change	10.2.0	10.0.0
2015-09	CT#69	CP-150448	1613	1	Usage of Charging Characteristics for activating PCC function	13.2.0	13.3.0
2015-09	CT#69	CP-150448	1616	-	SSID and BSSID encoding clarification		13.3.0
2015-09	CT#69	CP-150448	1619	2	Monitoring Event Information		13.3.0
2015-09 2015-09	CT#69 CT#69	CP-150440	1620	3	UE Usage Type for Dedicated Core Network Feature Reject Cause in Context Acknowledge for Dedicated Core	13.2.0	13.3.0 13.3.0
2015-09	C1#09	CP-150440	1621	2	Network Feature	13.2.0	13.3.0
2015-09	CT#69	CP-150451	1625	2	MME/SGSN/SGW/TWAN/ePDG NBIFOM support indication	13.2.0	13.3.0
2015-12	CT#70	CP-150761	1626	1	Cell List in MBMS Session Requests		13.4.0
2015-12	CT#70				Extensions for P-CSCF restoration for trusted and untrusted	13.3.0	13.4.0
0045.40	07/70	CP-150780	1627	-	WLAN access	40.0.0	40.4.0
2015-12	CT#70	CP-150770	1628	1	Emergency PDN connection over untrusted WLAN access		13.4.0 13.4.0
2015-12 2015-12	CT#70 CT#70	CP-150770 CP-150760	1660 1631	1	User Location Information reporting extensions over S2b Load and overload metrics on APN level		13.4.0
2015-12	CT#70	CP-150760	1633	2	Load and overload IE Instances		13.4.0
2015-12	CT#70	CP-150760	1635	2	Load and overload sequence numbers per node		13.4.0
2015-12	CT#70	CP-150760	1636	2	Load and overload Sequence Number check		13.4.0
2015-12	CT#70	CP-150752	1637	3	Modify Bearer Request when "Active flag" is set		13.4.0
2015-12	CT#70	CP-150752	1639	2	PCO in Create Session Request and Response		13.4.0
2015-12	CT#70	CP-150752	1641	2	Context not found in handovers	13.3.0	
2015-12 2015-12	CT#70 CT#70	CP-150752 CP-150752	1645 1646	-	Correct the wrong IE name Coding of CSG ID		13.4.0 13.4.0
2015-12	CT#70	CP-150752	1651	1	Extension of GTPv2 IE type		13.4.0
2015-12	CT#70	CP-150752	1653	3	Addition of new GTPv2 Cause Code for Credit Check		13.4.0
2015-12	CT#70	CP-150752	1663	1	Inclusion of RAN/NAS Cause in Delete Bearer Response		13.4.0
2015-12	CT#70	CP-150752	1665	2	F-Container Type Value	13.3.0	
2015-12	CT#70	CP-150773	1642	2	Network-initiated IP flow mobility		13.4.0
2015-12	CT#70	CP-150773	1643	2	UE-initiated IP Flow Mobility and IP Flow Mapping		13.4.0
2015-12 2015-12	CT#70 CT#70	CP-150773	1644	2	Addition of one access to a PDN connection in NBIFOM Define a cause value for the rejection of additional access to a		13.4.0 13.4.0
2013-12	01#70	CP-150773	1650	1	PDN connection	13.3.0	13.4.0
2015-12	CT#70	CP-150773	1669	1	NBIFOM support indication	13.3.0	13.4.0
2015-12	CT#70	CP-150751	1648	1	UE Radio Capability for Paging Information		13.4.0
2015-12	CT#70	CP-150751	1658	3	Mapping table between GTPv2 S2a and WLCP/Diameter		13.4.0
2015-12	CT#70	00 450754	4007		Operation Indication in MME triggered Serving GW relocation	13.3.0	13.4.0
2015-12	CT#70	CP-150751	1667	1	procedure Transferring DTCI and PNSI during inter MME/SGSN mobility	1330	13.4.0
2013-12	01#70	CP-150776	1649	2	procedure	15.5.0	13.4.0
2015-12	CT#70	CP-150776	1652	1	Delay Tolerant Connection Indication	13.3.0	13.4.0
2015-12	CT#70	CP-150776	1655	1	DTCI in SGW		13.4.0
2015-12	CT#70	CP-150772	1656	2	Remote UE Report Notification		13.4.0
2015-12	CT#70	CP-150756	1662	1	Presence Reporting Area Identifier		13.4.0
2015-12	CT#70	CP-150782	1659	1	Handling of Create Session Request without Origination Timestamp	13.3.0	13.4.0
2015-12	CT#70	CP-150782 CP-150781	1668	1	UE Usage Type Coding	13.3.0	13.4.0
2015-12	CT#70	CP-150778	1670	-	Monitoring Events in Identification Response		13.4.0
2015-12	CT#70	CP-150778	1671	3	Remove Editor's Note on the Monitoring Event Information		13.4.0
2015-12	CT#70	CP-150765	1680	1	Instance numbers for overload control information		13.4.0
2016-03	CT#71	CP-160016	1684	1	Add cause values to TWAN mapping table		13.5.0
2016-03	CT#71	CP-160035	1682	-	Update the reference for NBIFOM container		13.5.0
2016-03 2016-03	CT#71 CT#71	CP-160035 CP-160038	1692 1685	-	PDN Connection Charging ID Octet number in MM context IE		13.5.0 13.5.0
2016-03	CT#71	CP-160038 CP-160038	1686	-	Protocol Type in Create Session Request		13.5.0
2016-03	CT#71	0. 100000	1000		Incorrect use of the term "full hexadecimal representation" to		13.5.0
		CP-160038	1688	1	mean binary encoding		
2016-03	CT#71				Use case for inclusion of the RAN/NAS Cause in Delete Bearer	13.4.0	13.5.0
0046.00	07/7	CP-160038	1691	-	Response	40.15	40 - 6
2016-03	CT#71 CT#71	CP-160038	1693	3	Transferring AAA identifier from the ePDG to the PGW		13.5.0
2016-03	01#/1	CP-160033	1689	3	S11-U tunneling for MO/MT data transport in control plane (SGi based) – with new S11-U F-TEIDs	13.4.0	13.5.0
2016-03	CT#71	CP-160033	1690	1	RAT-Type extension for NB-IoT	13.4.0	13.5.0

Date	TSG #	TSG Doc	CR	Rev		Old	New
2016-03	CT#71	CP-160033	1697	6	Transfer of non IP PDN to peer MME during mobility	13.4.0	
2016-03	CT#71				Addition of NB-IoT radio access type to the Access-Restriction-	13.4.0	13.5.0
		CP-160033	1698	1	Data feature		
2016-03	CT#71	CP-160033	1699	1	No Delete Session Request for non-existing PDN connection	13.4.0	
2016-03	CT#71	CP-160033	1700	1	No Create Session Request for Attach without PDN connection		13.5.0
2016-03	CT#71	0.5.400000	1704		No Paging and Service Information in DDN for non-IP PDN	13.4.0	13.5.0
	0	CP-160033	1701	2	connections		
2016-03	CT#71	CP-160033	1704	1	Protocol change for Connection Suspend and Resume Procedure	13.4.0	
2016-03	CT#71	CP-160033	1705	2	Protocol change for introducing new non-IP PDN type		13.5.0
2016-03	CT#71	CP160025	1687	-	P-CSCF_RESELECTION_SUPPORT Private Status Type		13.5.0
2016-03	CT#71	CP-160036	1694	2	Cleanup of the editor's notes for reporting remote UE		13.5.0
2016-03	CT#71	CP-160030	1695	1	Triggering MT SM retransmission by the SMS GMSC to a UE in eDRX during inter MME/SGSN mobility procedure		13.5.0
2016-06	CT#72	CP-160214	1713	1	Correction to the inclusion of PRA IE in Create Session Request on S5/S8 interface	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1706	4	Handover for non-NB-IoT devices using CIoT optimisations	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1707	1	S11-U bearers handling during the TAU procedure	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1708	3	Transfer of Header Compression Configuration during inter-MME mobility	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1714	2	Rejecting Context Request with RAT type change from/to NB-IoT	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1715	2	Addressing Editor's Note on SCEF PDN Connections IE in Context Response	13.5.0	13.6.0
2016-06	CT#72	CP-160228	1719	1	MME triggered PGW pause of charging	13.5.0	13.6.0
2016-06	CT#72	01-100220	1715		Transfer of Header Compresson Configuration during inter-MME	13.5.0	13.6.0
2010 00	0112	CP-160228	1726	1	Handover	10.0.0	10.0.0
2016-06	CT#72	CP-160228	1734	3	Simultaneous support for CP and UP optimisation	13.5.0	13.6.0
2016-06	CT#72			-	Extended Protocol Configuration Option and Support ePCO	13.5.0	13.6.0
		CP-160228	1737	2	indication		
2016-06	CT#72	CP-160228	1738	1	Selection of an EPC entity supporting CIoT	13.5.0	13.6.0
2016-06	CT#72				Clarification on inclusion of the Sending Node Features IE in Echo	13.5.0	13.6.0
		CP-160234	1709	1	Request & Response messages		
2016-06	CT#72	CP-160234	1710	4	Bearer mismatching handling		13.6.0
2016-06	CT#72				Add both IP addresses within S1-U SGW F-TEID in Create Bearer	13.5.0	13.6.0
		CP-160234	1718	1	Request		
2016-06	CT#72				Incorrect conditions for ULI IE in CSReq for X2 Handover and	13.5.0	13.6.0
		CP-160234	1722	1	Enhanced SRNS Relocation		
2016-06	CT#72	CP-160234	1723	-	Selection Mode value for Wildcard authorized APN		13.6.0
2016-06	CT#72	CP-160234	1727	1	Data Notification Delay in DDN Acknowledge		13.6.0
2016-06	CT#72	CP-160234	1728	-	Associate OCI with SGW node's identity		13.6.0
2016-06	CT#72	CP-160234	1733	1	A correction on the reference index of UE usage type in TS29.274	13.5.0	
2016-06	CT#72	CP-160234	1740	1	Essential clarification for Modify Access Bearer Request when only EBI is present	13.5.0	13.6.0
2016-06	CT#72	CP-160234	1740	1	Extensions for EGPRS access security enhancements	1350	13.6.0
2016-06	CT#72	01-100234	1742		Handling of NW-initiated session/bearer release for NB-IFOM		13.6.0
2010-00	01#12	CP-160231	1716	3	connections	15.5.0	15.0.0
2016-06	CT#72	CP-160231	1725	2	Clarification of the Relay Identity included in TWAN Identifier	1350	13.6.0
2016-06	CT#72	CP-160231	1729	2	NBIFOM support indication during inter-PLMN mobility		13.6.0
2016-06	CT#72	01 100201	1720	2	Cause value "Multiple accesses to a PDN connection not allowed"		13.6.0
2010 00	01///2	CP-160231	1741	1	in NW-initiated PDN disconnection procedure	10.0.0	10.0.0
2016-06	CT#72	CP-160232	1735	1	Addition of IMEI in Remote User ID	13.5.0	13.6.0
2016-06	CT#72	CP-160218	1681	6	Adding eNB change reporting in Location Change Reporting		14.0.0
2016-06	CT#72	CP-160217	1736	1	GTPv2 impact for NonIP-GPRS		14.0.0
2016-09	CT#73	CP-160423	1747		Dedicated bearer deletion signalling for a UE using Extended Coverage		14.1.0
2016-09	CT#73	CP-160424	1745		Extended DL Data Buffering for Extended Coverage	14.0.0	1/10
2016-09		CP-160423	1749	-	Data switching from CP to UP without sending a Release Access	14.0.0	
2016-09	CT#73	CP-160423	1751	-	Bearers Request S11-U bearers of multiple SGi PDN connections using Data over	14.0.0	14.1.0
					the Control Plane		
2016-09	CT#73	CP-160423	1765		Clarification on the inclusion of the Serving PLMN Rate Control during Inter MME procedure	14.0.0	14.1.0
	CT#73	CP-160421	1753	2	Unaccepted PDN connection during an Intra-MME/SGSN handover		
2016-09		CD 160424	1766	-	Inclusion of Sender' F-TEID in the Command message	14.0.0	14.1.0
2016-09 2016-09	CT#73	CP-160421			A new Flag from PGW to SGSN	14 0 0	14.1.0
	CT#73	CP-160421 CP-160422	1760	1	A new hag nonin ow to soon	14.0.0	
2016-09	CT#73				Correction on ePCO	14.0.0	
2016-09 2016-09	CT#73 CT#73 CT#73	CP-160422	1760	3 2	Correction on ePCO Clarification on the release of unsuccessful EPC bearer context at	14.0.0	
2016-09 2016-09 2016-09 2016-09	CT#73 CT#73 CT#73 CT#73	CP-160422 CP-160424 CP-160424	1760 1763 1764	3 2	Correction on ePCO Clarification on the release of unsuccessful EPC bearer context at mobility procedures when interworking with CloT	14.0.0 14.0.0	14.1.0 14.1.0
2016-09 2016-09 2016-09 2016-09 2016-09	CT#73 CT#73 CT#73 CT#73 CT#73	CP-160422 CP-160424 CP-160424 CP-160424	1760 1763 1764 1771	3 2 2	Correction on ePCO Clarification on the release of unsuccessful EPC bearer context at mobility procedures when interworking with CloT Handling of Exception Reports in the Core Network	14.0.0 14.0.0 14.0.0	14.1.0 14.1.0 14.1.0
2016-09 2016-09 2016-09 2016-09 2016-09 2016-09	CT#73 CT#73 CT#73 CT#73 CT#73 CT#73	CP-160422 CP-160424 CP-160424 CP-160424 CP-160424	1760 1763 1764 1771 1773	3 2 2 1	Correction on ePCO Clarification on the release of unsuccessful EPC bearer context at mobility procedures when interworking with CloT Handling of Exception Reports in the Core Network Keep the S11-U SGW F-TEID the same as the S1-U SGW F-TEID	14.0.0 14.0.0 14.0.0 14.0.0	14.1.0 14.1.0 14.1.0 14.1.0
2016-09 2016-09 2016-09 2016-09 2016-09	CT#73 CT#73 CT#73 CT#73 CT#73 CT#73 CT#73	CP-160422 CP-160424 CP-160424 CP-160424	1760 1763 1764 1771	3 2 2 1 2	Correction on ePCO Clarification on the release of unsuccessful EPC bearer context at mobility procedures when interworking with CloT Handling of Exception Reports in the Core Network	14.0.0 14.0.0 14.0.0 14.0.0	14.1.0 14.1.0 14.1.0 14.1.0 14.1.0

Date	TSG #	TSG Doc	CR	Rev	Subject/Comment	Old	New
2016-12	CT#74	CP-160676	1797	2	Support of PRA Set Reporting	14.1.0	14.2.0
2016-12	CT#74	CP-160679	1777	1	User identification for the emergency service	14.1.0	14.2.0
2016-12	CT#74	CP-160679	1781	1	Emergency services over WLAN for unauthenticated UEs	14.1.0	14.2.0
2016-12	CT#74	CP-160675	1778	3	Inclusion of IMSI in the Modify Bearer Request message	14.1.0	14.2.0
2016-12	CT#74	CP-160675	1782	1	Message Priority Indication over GTP	14.1.0	14.2.0
2016-12	CT#74	CP-160675	1784	1	Mobility support for NonIP in GPRS	14.1.0	14.2.0
2016-12	CT#74	CP-160675	1796	2	IP address instance in the Create Bearer Response	14.1.0	14.2.0
2016-12	CT#74	CP-160675	1800	2	eNB change reporting for inter MME handover	14.1.0	14.2.0
2016-12	CT#74	CP-160652	1780	1	IOV_updates counter	14.1.0	14.2.0
2016-12	CT#74	CP-160652	1802	1	Absolute Time in MBMS Session Update Request	14.1.0	14.2.0
2016-12	CT#74				Remove SGSN applicability for ePCO in the Create Session	14.1.0	14.2.0
		CP-160685	1783	-	Request message		
2016-12	CT#74				New GTP Cause to Restrict the Number of EPS Bearers for NB-IoT	14.1.0	14.2.0
		CP-160657	1787	3	UE		
2016-12	CT#74				Add Bearer Context to Context Acknowledge message for Data	14.1.0	14.2.0
		CP-160667	1789	2	forwarding		
2016-12	CT#74	CP-160656	1793	1	Remove an editor's note	14.1.0	14.2.0
2016-12	CT#74	CP-160655	1795	-	Remote UE Context IE type in Create Session Request	14.1.0	14.2.0
2016-12	CT#74	CP-160680	1803	1	GW selection by S4-SGSN for Non-IP PDN type	14.1.0	14.2.0
2016-12	CT#74				Transferring subscribed UE usage type during inter MME/SGSN	14.1.0	14.2.0
		CP-160665	1805	1	mobility		
2017-03	CT#75				Bearer context mismatch during dedicated bearer creation	14.2.0	14.3.0
		CP-170026	1817	-	procedure		
2017-03		CP-170041	1806	2	PLMN ID Check and Enhanced TV Services	14.2.0	14.3.0
2017-03	CT#75	CP-170039	1807	1	Enhanced Coverage	14.2.0	
2017-03	CT#75	CP-170039	1813	1	PDN Continuity at Inter-RAT mobility	14.2.0	14.3.0
2017-03		CP-170040	1808	1	Bearer Contexts in Delete Bearer Failure Indication	14.2.0	14.3.0
2017-03	CT#75				Including Sender's F-TEID in Delete Session Request message for	14.2.0	14.3.0
		CP-170040	1809	1	S2a/S2b		
2017-03	CT#75	CP-170040	1814	3	Support of long and short Macro eNodeB IDs	14.2.0	14.3.0
2017-03	CT#75	CP-170040	1815	1	Maximum Wait Time over the S8	14.2.0	14.3.0
2017-06	CT#76	CP-171019	1821	1	CN Operator Selection Entity		14.4.0
2017-06	CT#76	CP-171021	1823	1	Mo Exception Data Counter	14.3.0	14.4.0
2017-09	CT#77				TAU with SGW change and Data forwarding for CP only PDN	14.4.0	14.5.0
		CP-172014	1827	1	connection		
2017-09	CT#77	CP-172014	1831	1	Use of MABR when support of ePCO is changed	14.4.0	14.5.0
2017-09	CT#77	CP-172020	1824	1	GTP-C Extensions for SGW-U and PGW-U selection with CUPS	14.4.0	14.5.0
2017-09	CT#77	CP-172017	1838	4	Coding of area scope in MDT Configuration parameter	14.4.0	14.5.0
2017-12	CT#78	CP-173013	1867	1	SGW handling of TFT	14.5.0	14.6.0
2017-12	CT#78	CP-173021	1857	2	S11-U interface separation from S1-U interface	14.5.0	14.6.0
2018-03	CT#79	CP-180015	1891	-	Support of long and short Macro eNodeB IDs	14.6.0	14.7.0

## 413

## History

Document history						
V14.3.0	May 2017	Publication				
V14.4.0	July 2017	Publication				
V14.5.0	October 2017	Publication				
V14.6.0	January 2018	Publication				
V14.7.0	April 2018	Publication				