

# ETSI TS 129 504 V17.10.0 (2023-04)



**5G;  
5G System;  
Unified Data Repository Services;  
Stage 3  
(3GPP TS 29.504 version 17.10.0 Release 17)**



---

**Reference**

RTS/TSGC-0429503vgf0

---

**Keywords**

5G

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope .....	8
2 References .....	8
3 Definitions and abbreviations.....	9
3.1 Definitions .....	9
3.2 Abbreviations .....	9
4 Overview .....	9
5 Services offered by the UDR.....	10
5.1 Introduction .....	10
5.2 Nudr_DataRepository Service.....	11
5.2.1 Service Description.....	11
5.2.1.1 Service and operation description .....	11
5.2.1.2 Service operation and data access authorization .....	11
5.2.2 Service Operations.....	12
5.2.2.1 Introduction.....	12
5.2.2.2 Query.....	12
5.2.2.2.1 General .....	12
5.2.2.2.2 Data retrieval .....	12
5.2.2.2.3 Retrieval of subset of a resource.....	13
5.2.2.3 Create .....	14
5.2.2.3.1 General .....	14
5.2.2.3.2 Data Creation using PUT.....	15
5.2.2.3.3 Data Creation using POST .....	15
5.2.2.4 Delete .....	16
5.2.2.4.1 General .....	16
5.2.2.4.2 Deleting Data.....	16
5.2.2.5 Update .....	16
5.2.2.5.1 General .....	16
5.2.2.5.2 Data Update using PATCH .....	16
5.2.2.5.3 Data Update using PUT.....	17
5.2.2.6 Subscribe .....	17
5.2.2.6.1 General .....	17
5.2.2.6.2 NF service consumer subscribes to notifications to UDR .....	18
5.2.2.6.3 Stateless UDM subscribes to notifications to UDR .....	18
5.2.2.7 Unsubscribe.....	19
5.2.2.7.1 General .....	19
5.2.2.7.2 Unsubscribe service operation.....	19
5.2.2.8 Notify .....	20
5.2.2.8.1 General .....	20
5.2.2.8.2 Notification to NF service consumer on data change .....	20
5.2.2.8.3 Notification to stateless UDM on data change .....	20
5.2.2.9 DataRestorationNotification.....	21
5.2.2.9.1 General .....	21
5.2.2.9.2 Notification on Data Restoration.....	21
5.3 Nudr_GroupIDmap Service.....	22
5.3.1 Service Description.....	22
5.3.1.1 Service and operation description .....	22
5.3.2 Service Operations.....	22
5.3.2.1 Introduction.....	22
5.3.2.2 Query.....	22

5.3.2.2.1	General .....	22
5.3.2.2.2	NF-Group ID retrieval .....	22
6	API Definitions .....	23
6.1	Nudr_DataRepository Service API .....	23
6.1.1	API URI .....	23
6.1.2	Usage of HTTP .....	23
6.1.2.1	General .....	23
6.1.2.2	HTTP standard headers .....	24
6.1.2.2.1	General .....	24
6.1.2.2.2	Content type .....	24
6.1.2.2.3	Cache-Control .....	24
6.1.2.2.4	ETag .....	24
6.1.2.2.5	If-None-Match .....	24
6.1.2.2.5a	If-Match .....	24
6.1.2.2.6	Last-Modified .....	24
6.1.2.2.7	If-Modified-Since .....	25
6.1.2.2.8	When to Use Entity-Tags and Last-Modified Dates .....	25
6.1.2.3	HTTP custom headers .....	25
6.1.2.3.1	General .....	25
6.1.2.3.2	3gpp-Sbi-Message-Priority .....	25
6.1.2.3.3	3gpp-Sbi-Notification-Correlation .....	25
6.1.3	Resources .....	26
6.1.3.1	Overview .....	26
6.1.3.2	SubscriptionData .....	27
6.1.3.3	PolicyData .....	27
6.1.3.4	StructuredDataForExposure .....	27
6.1.3.5	ApplicationData .....	27
6.1.3.6	Resource: DataRestorationEvents .....	27
6.1.3.6.1	Description .....	27
6.1.3.6.2	Resource Definition .....	27
6.1.3.6.3	Resource Standard Methods .....	27
6.1.4	Custom Operations without associated resources .....	28
6.1.5	Notifications .....	28
6.1.5.1	General .....	28
6.1.5.2	Data Change Notification .....	28
6.1.5.3	Data Restoration Notification .....	28
6.1.5a	Data Model .....	30
6.1.5a.1	General .....	30
6.1.5a.2	Structured data types .....	30
6.1.5a.2.1	Introduction .....	30
6.1.5a.2.2	Type: DataRestorationNotification .....	31
6.1.6	Error Handling .....	31
6.1.7	Security .....	32
6.1.8	Feature negotiation .....	35
6.2	Nudr_GroupIDmap Service API .....	38
6.2.1	API URI .....	38
6.2.2	Usage of HTTP .....	38
6.2.2.1	General .....	38
6.2.2.2	HTTP standard headers .....	39
6.2.2.2.1	General .....	39
6.2.2.2.2	Content type .....	39
6.2.2.2.3	Cache-Control .....	39
6.2.2.2.4	ETag .....	39
6.2.2.2.5	If-None-Match .....	39
6.2.2.2.6	Last-Modified .....	39
6.2.2.2.7	If-Modified-Since .....	39
6.2.2.2.8	When to Use Entity-Tags and Last-Modified Dates .....	39
6.2.2.3	HTTP custom headers .....	40
6.2.2.3.1	General .....	40
6.2.3	Resources .....	40
6.2.3.1	Overview .....	40

6.2.3.2	Resource NfGroupIds.....	40
6.2.3.2.1	Description .....	40
6.2.3.2.2	Resource Definition .....	40
6.2.3.2.3	Resource Standard Methods .....	40
6.2.4	Custom Operations without associated resources .....	41
6.2.5	Notifications .....	41
6.2.6	Data Model .....	41
6.2.6.1	General .....	41
6.2.6.2	Structured data types .....	42
6.2.6.2.1	Introduction .....	42
6.2.6.2.2	Type: NfGroupIdMapResult.....	42
6.2.6.3	Simple data types and enumerations .....	42
6.2.6.3.1	Introduction .....	42
6.2.6.3.2	Simple data types.....	42
6.2.7	Error Handling .....	42
6.2.7.1	General .....	42
6.2.7.2	Protocol Errors .....	42
6.2.7.3	Application Errors .....	42
6.2.8	Security .....	43
6.2.9	Feature Negotiation.....	43
<b>Annex A (normative):    OpenAPI specification.....</b>		<b>44</b>
A.1	General .....	44
A.2	Nudr_DataRepository API .....	44
A.3	Nudr_GroupIDmap API.....	50
<b>Annex B (informative):    Change history .....</b>		<b>53</b>
History .....		57

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.



---

# 1 Scope

The present document specifies the stage 3 protocol and high level data model for the Nudr Service Based Interface. It provides stage 3 protocol definitions and message flows, and specifies the API for each service offered by the Unified Data Repository (UDR). The data model and usage of the subscription data is specified in 3GPP TS 29.505 [2], and the data model and usage of the policy data, structured data for exposure and application data are specified in 3GPP TS 29.519 [3].

The 5G System architecture is specified in 3GPP TS 23.501 [4]. The stage 2 definition and related procedures for Nudr SBI service are specified in 3GPP TS 23.502 [5] and 3GPP TS 23.503 [6].

The Technical Realization of the Service Based Architecture is specified in 3GPP TS 29.500 [7] and the Principles and Guidelines for Services Definition is specified in 3GPP TS 29.501 [8].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 29.505: "5G System; Usage of the Unified Data Repository Services for Subscription Data; Stage 3".
- [3] 3GPP TS 29.519: "5G System; Usage of the Unified Data Repository Service for Policy Data, Structured Data for Exposure and Application Data; Stage 3".
- [4] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [5] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [6] 3GPP TS 23.503: "Policy and Charging Control Framework for the 5G System; Stage 2".
- [7] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [8] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [9] IETF RFC 6901(April 2013): "JavaScript Object Notation (JSON) Pointer".
- [10] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces Stage 3".
- [11] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [12] 3GPP TS 33.501: "Security architecture and procedures for 5G system".
- [13] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
- [14] 3GPP TS 29.510: "Network Function Repository Services; Stage 3".
- [15] IETF RFC 7232: "Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests".
- [16] IETF RFC 7234: "Hypertext Transfer Protocol (HTTP/1.1): Caching".
- [17] IETF RFC 7807: "Problem Details for HTTP APIs".

- [18] IETF RFC 7396: "JSON Merge Patch".
- [19] IETF RFC 6902: "JavaScript Object Notation (JSON) Patch".
- [20] 3GPP TR 21.900: "Technical Specification Group working methods".
- [21] OpenAPI Initiative, "OpenAPI Specification Version 3.0.0", <https://spec.openapis.org/oas/v3.0.0>
- 

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

GPSI	Generic Public Subscription Identifier
NEF	Network Exposure Function
PCF	Policy Control Function
SUPI	Subscription Permanent Identifier
UDM	Unified Data Management
UDR	Unified Data Repository


---

## 4 Overview

The Unified Data Repository (UDR) is the network entity in the 5G Core Network (5GC) supporting the following functionalities:

- Storage and retrieval of subscription data as specified in 3GPP TS 29.505 [2];
- Storage and retrieval of policy data as specified in 3GPP TS 29.519 [3];
- Storage and retrieval of structured data for exposure as specified in 3GPP TS 29.519 [3];
- Storage and retrieval of application data (including Packet Flow Descriptions (PFDs) for application detection, application request information for multiple UEs) as specified in 3GPP TS 29.519 [3];
- Subscription to notification and the notification of subscribed data changes.
- Storage and retrieval of NF-Group Id mapping data.

Figures 4-1 shows the data storage architecture for the 5GC:



**Figure 4-1: Data storage architecture**

The Nudr interface is used by the network functions (i.e. UDM, PCF, NEF and NRF) to access a particular set of the data stored in the UDR.

**NOTE:** Services offered by the UDR via the Nudr service based interface can also be consumed by the HSS as specified in 3GPP TS 23.632 clause 5.2.4.

## 5 Services offered by the UDR

### 5.1 Introduction

The UDR offers the following services via the Nudr interface:

- Nudr\_DataRepository Service

**NOTE:** This service corresponds to the Nudr\_DataManagement service in 3GPP TS 23.501 [4], 3GPP TS 23.502 [5] and 3GPP TS 23.503 [6].

- Nudr\_GroupIDmap Service

Table 5.1-1 summarizes the corresponding APIs defined for this specification.

Table 5.1-1: API Descriptions

Service Name	Clause	Description	OpenAPI Specification File	apiName	Annex
Nudr_DataRepository	6.1	Unified Data Repository Service	TS29504_Nudr_DR.yaml	nudr-dr	A.2
Nudr_GroupIDmap	6.2	Unified Data Repository Service for NF-Group ID retrieval	TS29504_Nudr_GroupIDmap.yaml	nudr-group-id-map	A.3

## 5.2 Nudr\_DataRepository Service

### 5.2.1 Service Description

#### 5.2.1.1 Service and operation description

The UDR is acting as NF Service Producer. It provides Unified Data Repository service to the NF service consumer. The known NF Service Consumers are the UDM, PCF and NEF.

For the Nudr\_DataRepository service, the following service operations are defined:

- Query
- Create
- Delete
- Update
- Subscribe
- Unsubscribe
- Notify
- DataRestorationNotification

This service allows NF service consumers to retrieve, create, update, modify and delete data stored in the UDR.

This service allows the NF service consumers to subscribe/unsubscribe the data change notification and to be notified of the data change.

This service allows the NF service consumers to be notified upon the UDR restoration.

#### 5.2.1.2 Service operation and data access authorization

UDR provides one Nudr\_DataRepository service to all of the NF consumers, while different types of data may have different data access authorizations, the UDR shall be able to have the authorization management mechanism to guarantee the safety of data access.

And the information in the Nudr\_DataRepository service operation should be able to identify the NF type of the consumer and the service operation type or name, and to indicate the requested data information including the data set and data subset, and the resource/data identifier. All HTTP methods for the service operation shall include the information in the appropriate place of the HTTP message.

If there is an illegal service operation or data access request initiated by a NF consumer, the service failure response should be returned through the Nudr interface with an explicit cause value.

**NOTE:** For allowed service operations or data access requests initiated by an NF consumer it is not expected (unless explicitly specified otherwise) that the UDR performs any consumer-specific application logic to check whether a requested service operation should be rejected.

## 5.2.2 Service Operations

### 5.2.2.1 Introduction

This clause specifies the generic Nudr\_DataRepository service operations towards the different data sets as shown in Figure 4-1.

The HTTP request of the service operations contains a resource URI where the {apiSpecificResourceUriPart} (see clause 4.4.2 in 3GPP TS 29.501 [8]) consists of a top-level segment and sub-level segment(s), followed by query parameters (optional or required).

If multiple query parameters are defined for a method on the resource, the default logical relationship between the different query parameters shall be the logical "AND", unless explicitly indicated on each specific resource and operation on the Nudr\_DataRepository API.

NOTE: Not all query parameters imply necessarily a logical relationship with other parameters (e.g. "supported-features"); whether or not such logical relationship exists, is determined by the semantics of the different query parameters in each resource and operation.

For Create, Query, Update and Delete operations, the top-level segment indicates one top level resource representing one of the data sets, which are defined as "/subscription-data", "/policy-data", "/exposure-data" and "/application-data" in Figure 6.1.3.1-1. And a certain child resource is indicated by the end URI of the sub-level segments, which are defined in 3GPP TS 29.505 [2] for use when the top-level segment is "/subscription-data" and in 3GPP TS 29.519 [3] for use when the top-level segment is "/policy-data", "/exposure-data" or "/application-data".

For Subscribe/Unsubscribe to data change notification operations, the resource of the subscription to the notification should be as the child resource of each of the data sets (i.e. "/subscription-data", "/policy-data", "/exposure-data" and "/application-data"), which are indicated by the top-level segment in the URI. And the resource representation of the subscription to the notification should be indicated by the sub-level segment of each data set.

The following procedures for each operation should be taken as the common procedures and applicable to corresponding detail procedures with the same service operation in 3GPP TS 29.505 [2] and 3GPP TS 29.519 [3].

### 5.2.2.2 Query

#### 5.2.2.2.1 General


The Query service operation is used to retrieve the data stored in the UDR. HTTP GET method shall be used for the service operation to request the certain data record(s). One piece of data records should be a data set, a data subset, a group of data in one data subset, or a specific data. If the data record(s) are the attribute(s), query parameter or the combination of query parameters should be used as the filters to control the content of result.

#### 5.2.2.2.2 Data retrieval

Figure 5.2.2.2.2-1 shows a scenario where the NF service consumer (e.g. UDM, PCF or NEF) sends a request to the UDR to retrieve data.

Query parameters may be used for data retrieval:

- i) Clause 5.2.2.2.3 specifies the query parameter used for retrieving subset of a resource;
- ii) Other query parameters are defined in 3GPP TS 29.505 [2] and 3GPP TS 29.519 [3].



**Figure 5.2.2.2-1: Retrieving Data**

1. The NF service consumer shall send a GET request to the resource representing the data. Query parameters may be used to restrict the response to the requested data record(s) of the resource's representation. Query parameters may also indicate the features that the NF service consumer supports as described in clause 6.6.2 of 3GPP TS 29.500 [7].
2. On success, the UDR shall respond with "200 OK" with the message body containing the requested data record(s) restricted to the query parameters. (and thus also to the indicated features supported by the NF service consumer).

On failure, the UDR shall return an appropriated error code with the error cause information.

The error codes of corresponding service operations in 3GPP TS 29.505 [2] and 3GPP TS 29.519 [3] shall align and comply with the failure response mechanism which is defined in 3GPP TS 29.500 [7].

### 5.2.2.2.3 Retrieval of subset of a resource

When a resource has multiple attributes, it is allowed for the NFs to retrieve a subset of the attributes. When the attribute is of type map, it is allowed for the NFs to retrieve individual member(s) of that map. For retrieval of subset of a resource, a new query parameter "fields" is defined to carry the identities of the attributes to be retrieved. The definition of "fields" query parameter is:

- 1) "fields" query parameter is of type array; and
- 2) each element of the array is of type string encoded as a JSON pointer as defined IETF RFC 6901 [9].

NOTE: identifying an individual element in the array is supported by JSON pointer, however it is not recommended to use this feature if the client is not exactly aware of the order of the members in the array.

If retrieval of subset of a particular resource is supported, then all the attributes of the corresponding data type of that resource shall be optional or conditional.

#### EXAMPLE 1:

Given the following representation of ExResource:

```

{
  "lv1Attr1": "value1"
  "lv1Attr2": "value2"
  "lv1Attr3": {
    "lv2Attr1": "value3"
    "lv2Attr2": "value4"
  }
}

```

To retrieve "lv1Attr1" and "lv2Attr2", the NF sends the following request:

```
GET /ExResource?fields=/lv1Attr1, /lv1Attr3/lv2Attr2
```

Upon success, the UDR then returns the following representation:

```
{
  "lv1Attr1": "value1"
  "lv1Attr3": {
    "lv2Attr2": "value4"
  }
}
```

#### EXAMPLE 2:

Given the following representation of ExResource:

```
{
  "Attr1": "value1"
  "Attr2": "value2"
  "AttrMap": {
    "Key1": {ExObject1}
    "Key2": {ExObject2}
  }
}
```

To retrieve "Attr1" and the second member of "AttrMap ", the NF sends the following request:

```
GET /ExResource?fields=/Attr1, /AttrMap/Key2
```

Upon success, the UDR then returns the following representation:

```
{
  "Attr1": "value1"
  "AttrMap": {
    "Key2": {ExObject2}
  }
}
```

### 5.2.2.3 Create

#### 5.2.2.3.1 General


The Create service operation is used by the NF service consumer (e.g. NEF) to create the data into the UDR.

The following procedures using the Create service operation are supported:

- Data creation using PUT
- Data creation using POST

### 5.2.2.3.2 Data Creation using PUT

Figure 5.2.2.3.2-1 shows a scenario where the NF service consumer (e.g. NEF) sends a request to the UDR to create data. The parent resource of the resource identified by the resource URI shall be of archetype Store (see clause C.3 in 3GPP TS 29.501 [8]).




**Figure 5.2.2.3.2-1: Creating Data using PUT**

1. The NF service consumer shall send a PUT request to the resource representing the data. The payload body of the PUT request shall contain the representation of the new data.
2. On success, the UDR shall respond with "201 Created" with the payload containing the representation of the created data, and the "Location" header shall be present and contains the URI of the created data.

On failure, the UDR shall return an appropriated error code with the error cause information.

### 5.2.2.3.3 Data Creation using POST

Figure 5.2.2.3.3-1 shows a scenario where the NF service consumer (e.g. NEF) sends a request to the UDR to create data. The resource identified by the resource URI shall be of archetype Collection (see clause C.2 in 3GPP TS 29.501 [8]).



**Figure 5.2.2.3.3-1: Creating Data using POST**

1. The NF service consumer shall send a POST request to create the new data record as the child resource of the parent resource in the UDR. The payload body of the POST request shall contain the representation of the new data.
2. The UDR generates the data identifier and constructs the URI for the created data record by appending the data identifier to the parent resource URI received as request URI of the POST request.

On success, the UDR shall respond with "201 Created" with the payload containing the representation of the created data, and the "Location" header shall be present and contains the URI of the created data.



On failure, the UDR shall return an appropriated error code with the error cause information.

## 5.2.2.4 Delete

### 5.2.2.4.1 General

The Delete service operation is used by the NF service consumer (e.g. NEF) to remove the data from the UDR.


The following procedures using the Delete service operation are supported:

- Data Deletion

HTTP DELETE method shall be used.

### 5.2.2.4.2 Deleting Data

Figure 5.2.2.4.2-1 shows a scenario where the NF service consumer (e.g. NEF) sends a request to the UDR to delete a data record.



**Figure 5.2.2.4.2-1: Deleting Data**

1. The NF service consumer shall send a DELETE request to the resource representing the data. The payload body of the request shall be empty.
2. On success, the UDR shall respond with "204 No Content", the payload body of the DELETE response shall be empty.

On failure, the UDR shall return an appropriated error code with the error cause information.

## 5.2.2.5 Update

### 5.2.2.5.1 General

The Update service operation is used by the NF service consumer (e.g. UDM, PCF or NEF) to update the data stored in the UDR.


The following procedures using the Update service operation are supported:

- Data Update using PATCH
- Data Update using PUT

HTTP PATCH method shall be used to add/create, delete or modify part of the value(s) in the data record (e.g. a specific data or a group of data in one data subset). HTTP PUT method shall be used to replace a complete data record.

### 5.2.2.5.2 Data Update using PATCH

Figure 5.2.2.5.2-1 shows a scenario where the NF service consumer (e.g. UDM, PCF or NEF) sends a request to the UDR to update some parts of the data record.




**Figure 5.2.2.5.2-1: Data Updating using PATCH**

1. The NF service consumer shall send a PATCH request to the resource representing the data record. The payload body contains the modification instruction towards the data record.
2. On success, the UDR shall respond with "204 No Content".

On failure, the UDR shall return an appropriated error code with the error cause information.

### 5.2.2.5.3 Data Update using PUT

Figure 5.2.2.5.3-1 shows a scenario where the NF service consumer (e.g. UDM, PCF or NEF) sends a request to the UDR to update the whole data record.



**Figure 5.2.2.5.3-1: Data Updating using PUT**

1. The NF service consumer shall send a PUT request to the resource representing the data record. The payload body contains the new data for the resource.
2. On success, the UDR shall respond with "204 No Content" or "200 OK".

On failure, the UDR shall return an appropriated error code with the error cause information.

## 5.2.2.6 Subscribe


### 5.2.2.6.1 General

The Subscribe service operation is used for the NF service consumer to explicitly subscribe to the data change notification from the UDR.

Permanent Subscription Data i.e. sub-resources of the ProvisionedData resource (see 3GPP TS 29.505 [2]) can be modified only by means of provisioning at the UDR and may be (as a deployment option) implicitly subscribed by the UDM as described in 3GPP TS 29.501 [8] clause 4.6.2.2.1. If so and when a data modification of permanent subscription data occurs by means of provisioning and there is the need to notify at least one serving node (e.g. AMF, SMF, SMSF), the UDR shall select one of the suitable and available UDMs (as discovered via the NRF) and send a notification using the callback URI provided by the NRF during UDM discovery.

### 5.2.2.6.2 NF service consumer subscribes to notifications to UDR

Figure 5.2.2.6.2-1 shows a scenario where the NF service consumer (e.g. UDM, PCF or NEF) sends a request to the UDR to subscribe to data change notifications.



**Figure 5.2.2.6.2-1: subscribing to data change notifications**

1. The NF service consumer sends a POST request to the parent resource (...<top-level segment>/subs-to-notif). The NF service consumer describes the notifications it wants to receive, and it also indicates the features it supports (see clause 6.6.2 of 3GPP TS 29.500 [7]). The request may contain an expiry time, suggested by the NF Service Consumer as a hint, representing the time upto which the subscription is desired to be kept active.
2. On success, the UDR responds with "201 Created" with the message body containing a representation of the created subscription and indicating the supported features (see clause 6.6.2 of 3GPP TS 29.500 [7]). The Location HTTP header shall contain the URI of the created subscription. In subsequent notifications according to clause 5.2.2.8.2, the UDR only uses the indicated supported features.


The response based on operator policies and taking into account the expiry time included in the request, may contain an expiry time (i.e a future timestamp), as determined by the UDR, after which the subscription becomes invalid. If an expiry time was included in the request, then the expiry time returned in the response should be less than or equal to that value. Once the subscription expires, if the NF Service Consumer wants to keep receiving notifications, it shall create a new subscription in the UDR. The UDR shall not provide the same expiry time (i.e a future timestamp) for many subscriptions in order to avoid all of them expiring and recreating the subscription at the same time. If the expiry time is not included in the response, the NF Service Consumer shall consider the subscription to be valid without an expiry time.

On failure, the UDR returns an appropriated error code with the error cause information.

Once the subscription has been created, an NF Service Consumer may request the update of the subscription in UDR (e.g., to request an extension of the subscription lifetime before the subscription expires) by issuing a PUT or PATCH request, as described in 3GPP TS 29.501 [8], clause 4.6.2.2.3.

### 5.2.2.6.3 Stateless UDM subscribes to notifications to UDR

Figure 5.2.2.6.3-1 shows a scenario where the stateless UDM subscribes to notification to the UDR.



**Figure 5.2.2.6.3-1: subscribing to data change notifications via stateless UDM**

1. The stateless UDM sends a POST request to the UDR to subscribe to the notifications.

The SubData in the POST request body shall indicate the same data for which a change will trigger a notification.

The SubData in the POST request body shall contain a callbackReference URI to which the notifications will be sent to. The host part of the callbackReference URI shall be set to the FQDN of the UDM set to which the stateless UDM belongs.

The SubData in the POST request body shall contain an original callbackReference URI of the NF which initially triggers the subscription.

The request may contain an expiry time, suggested by the NF Service Consumer as a hint, representing the time upto which the subscription is desired to be kept active.

2. On success, the UDR responds with "201 Created" with the message body containing a representation of the created subscription. The Location HTTP header shall contain the URI of the created subscription and that URI shall contain the subscription ID allocated by the UDR.

The response based on operator policies and taking into account the expiry time included in the request, may contain an expiry time (i.e a future timestamp), as determined by the UDR, after which the subscription becomes invalid. If an expiry time was included in the request, then the expiry time returned in the response should be less than or equal to that value. Once the subscription expires, if the NF Service Consumer wants to keep receiving notifications, it shall create a new subscription in the UDR. The UDR shall not provide the same expiry time (i.e a future timestamp) for many subscriptions in order to avoid all of them expiring and recreating the subscription at the same time. If the expiry time is not included in the response, the NF Service Consumer shall consider the subscription to be valid without an expiry time.

On failure, the UDR returns an appropriated error code with the error cause information.

Once the subscription has been created, the stateless UDM may request the update of the subscription in UDR (e.g., to request an extension of the subscription lifetime before the subscription expires) by issuing a PUT or PATCH request, as described in 3GPP TS 29.501 [8], clause 4.6.2.2.3.


## 5.2.2.7 Unsubscribe

### 5.2.2.7.1 General

The Unsubscribe service operation is used for the NF service consumer to unsubscribe to the data change notification from the UDR.

### 5.2.2.7.2 Unsubscribe service operation

Figure 5.2.2.7.2-1 shows a scenario where the NF service consumer (e.g. UDM, PCF or NEF) sends a request to the UDR to unsubscribe to data change notifications.



**Figure 5.2.2.7.2-1: Unsubscribing to the data change notifications**

1. The NF service consumer sends a DELETE request to the resource identified by the URI previously received during subscription creation, i.e. in the Location header field of the HTTP 201 Created response.
2. On success, the UDR responds with "204 No Content".

On failure, the UDR returns an appropriated error code with the error cause information.


## 5.2.2.8 Notify

### 5.2.2.8.1 General

The Notify service operation is used for the UDR to notify the data change notification to the previous subscribe operation requestor.

### 5.2.2.8.2 Notification to NF service consumer on data change

Figure 5.2.2.8.2-1 shows a scenario where the UDR notifies the NF service consumer about the subscribed data change. The request contains the CallbackReference URI as previously received in the subscribe operation (see clause 5.2.2.6).




**Figure 5.2.2.8.2-1: Data Change Notification**

1. The UDR sends a POST request to the callbackReference URI as provided by the NF service consumer in the subscribe operation.
2. On success, the NF service consumer responds with "204 No Content".

On failure, the NF service consumer responds an appropriated error code with the error cause information.

### 5.2.2.8.3 Notification to stateless UDM on data change

Figure 5.2.2.8.3-1 shows a scenario where the UDR notifies the NF service consumer about the subscribed data change.



**Figure 5.2.2.8.3-1: Data Change Notification to stateless UDM**

1. The UDR sends a POST request to the callbackReference URI as provided by the stateless UDM in the subscribe operation.

The notification in the POST request body shall contain the original callbackReference URI which is received in step 1 of Figure 5.2.2.6.3-1.

When the notification in the POST request body includes one or more arrays, the UDR shall use the complete replacement representation of the arrays, see 3GPP TS29.501 [4], Annex E.

When the notification in the POST request body includes one or more arrays where all the array elements have been removed, the UDR shall include the original array representation, i.e. in the origValue attribute of the ChangeItem.

2. On success, the stateless UDM responds with "204 No Content".

On failure, the stateless UDM responds an appropriated error code with the error cause information.

## 5.2.2.9 DataRestorationNotification


### 5.2.2.9.1 General

The DataRestorationNotification service operation is used for the UDR to send notifications on UDR restoration event to one or a set of NFs which are subject to the data restoration procedure.

### 5.2.2.9.2 Notification on Data Restoration

The notification on data restoration may be based on implicit subscription to data restoration event. When the NF service consumer (e.g. UDM) access UDR (i.e. to access the data stored in the UDR) for the first time, the UDR shall identify the identity of the NF service consumer via the NF instance ID contained in the 3gpp-Sbi-NF-Peer-Info header field of the request, then the UDR may create a default subscription on data restoration for that NF service consumer accordingly.

Figure 5.2.2.9.2-1 shows a scenario where the UDR notifies the NF service consumer about the need to restore data due to a potential data-loss event occurred at the UDR. The dataRestorationCallbackUri contained in the request is the default callback URI as discovered from NRF.



**Figure 5.2.2.9.2-1: Data Restoration Notification**

1. The UDR sends a POST request to the dataRestorationCallbackUri as discovered from NRF.
2. On success, the NF service consumer responds with "204 No Content".

On failure, the NF service consumer responds an appropriated error code with the error cause information.

## 5.3 Nudr\_GroupIDmap Service

### 5.3.1 Service Description

#### 5.3.1.1 Service and operation description

The Nudr\_GroupIDmap service may be used by NF service consumers (e.g. NRF or SCP) to retrieve the NF-GroupId for a given NF type and subscriber identifier; see G3GPP TS 23.501 [4] and 3GPP TS 23.502 [5].

For the Nudr\_GroupIDmap service, the following service operations are defined:

- Query

This service allows NF service consumers to retrieve, NfGroupId data stored in the UDR.

### 5.3.2 Service Operations

#### 5.2.2.1 Introduction

The service operations defined for the Nudr\_GroupIDmap service are as follows:

- Query: It allows an NF consumer (e.g. NRF) to retrieve the NF group ID for a given NF type and subscriber.

#### 5.3.2.2 Query


##### 5.3.2.2.1 General

The following procedure using the Query service operation is supported:

- NF-Group ID Retrieval

##### 5.3.2.2.2 NF-Group ID retrieval

Figure 5.3.2.2.2-1 shows a scenario where the NF service consumer (e.g. NRF) sends a request to the UDR to retrieve the UDM-group ID.



**Figure 5.3.2.2-1: Retrieving NF-Group Id**

1. The NF service consumer shall send a GET request to the resource representing the data. Query parameters shall be used to identify the NF type (e.g. UDM) of the requested NF-Group ID (e.g. UDM-Group ID) and the subscriber-id.
2. On success, the UDR shall respond with "200 OK" with the message body containing the requested data  
On failure, the UDR shall return an appropriated error code with the error cause information.

## 6 API Definitions

### 6.1 Nudr\_DataRepository Service API

#### 6.1.1 API URI

The Nudr-dr shall use the Nudr-dr API.

The request URI used in HTTP request from the NF service consumer towards the NF service producer shall have the structure defined in clause 4.4.1 of 3GPP TS 29.501 [8], i.e.:

**{apiRoot}/{apiName}/{apiVersion}/{apiSpecificResourceUriPart}**

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [8].
- The <apiName> shall be "nudr-dr".
- The <apiVersion> shall be "v2".
- The <apiSpecificResourceUriPart> shall be set as described in clause 6.1.3.

#### 6.1.2 Usage of HTTP

##### 6.1.2.1 General

Nudr service shall comply with the usage of HTTP/2.0 protocol over Service Based Interfaces. (See Clause 5, 3GPP TS 29.500[7]).



## 6.1.2.2 HTTP standard headers

### 6.1.2.2.1 General

The usage of HTTP standard headers shall be supported on Nudr interface as defined in clause 5.2.2 of 3GPP TS 29.500 [7].

### 6.1.2.2.2 Content type

The following content types shall be supported:

- JSON, as defined in IETF RFC 8259 [11], shall be used as content type of the HTTP bodies specified in the present specification as indicated in clause 5.4 of 3GPP TS 29.500 [7].
- The Problem Details JSON Object (IETF RFC 7807 [17]). The use of the Problem Details JSON object in a HTTP response body shall be signalled by the content type "application/problem+json".
- JSON Merge Patch (IETF RFC 7396 [18]). The use of the JSON Merge Patch format in a HTTP request body shall be signalled by the content type "application/merge-patch+json".
- JSON Patch (IETF RFC 6902 [19]). The use of the JSON Patch format in a HTTP request body shall be signalled by the content type "application/json-patch+json".

### 6.1.2.2.3 Cache-Control

As described in IETF RFC 7234 [16] clause 5.2, a "Cache-Control" header should be included in HTTP responses carrying a representation of cacheable resources (e.g. SessionManagementSubscriptionData). If it is included, it shall contain a "max-age" value, indicating the amount of time in seconds after which the received response is considered stale.

The "max-age" value shall be configurable by operator policy.

### 6.1.2.2.4 ETag

As described in IETF RFC 7232 [15] clause 2.3, an "ETag" (entity-tag) header should be included in HTTP responses carrying a representation of cacheable resources (e.g. AccessAndMobilitySubscriptionData) or modifyable resources (e.g. Amf3GppAccessRegistration) to allow an NF Service Consumer performing a conditional GET request with "If-None-Match" header or a conditional POST / PUT / PATCH / DELETE request with "If-Match" header. If it is included, it shall contain a server-generated strong validator, that allows further matching of this value (included in subsequent client requests) with a given resource representation stored in the server or in a cache.

### 6.1.2.2.5 If-None-Match

As described in IETF RFC 7232 [15] clause 3.2, an NF Service Consumer may issue conditional GET request towards UDR by including an "If-None-Match" header in HTTP requests containing one or several entity tags received in previous responses for the same resource.

### 6.1.2.2.5a If-Match

As described in IETF RFC 7232 [15] clause 3.1, an NF Service Consumer may issue conditional POST / PUT / PATCH / DELETE request towards UDR by including an "If-Match" header in HTTP requests containing an entity tag received in previous responses for the same resource.

### 6.1.2.2.6 Last-Modified

As described in IETF RFC 7232 [15] clause 2.2, a "Last-Modified" header should be included in HTTP responses carrying a representation of cacheable resources (e.g. SmfSelectionSubscriptionData) to allow an NF Service Consumer performing a conditional request with "If-Modified-Since" header.

#### 6.1.2.2.7 If-Modified-Since

As described in IETF RFC 7232 [15] clause 3.3, an NF Service Consumer may issue conditional GET request towards UDR, by including an "If-Modified-Since" header in HTTP requests.

#### 6.1.2.2.8 When to Use Entity-Tags and Last-Modified Dates

Both "ETag" and "Last-Modified" headers should be sent in the same HTTP response as stated in IETF RFC 7232 [15] clause 2.4.

NOTE: "ETag" is a stronger validator than "Last-Modified" and is preferred.

If the UDR included an "ETag" header with the resource then a conditional GET request for this resource shall be performed with the "If-None-Match" header, and a POST / PUT / PATCH / DELETE request for this resource shall be performed with the "If-Match" header.

### 6.1.2.3 HTTP custom headers

#### 6.1.2.3.1 General

The custom HTTP headers applicable to Nudr service are specified in the following clauses.

#### 6.1.2.3.2 3gpp-Sbi-Message-Priority

Nudr interface shall support 3gpp-Sbi-Message-Priority custom header. The header contains the HTTP/2 message priority value. See details in Clause 5.2.3.2.2 of 3GPP TS 29.500 [7].

#### 6.1.2.3.3 3gpp-Sbi-Notification-Correlation

The 3gpp-Sbi-Notification-Correlation header field is used by a NF in a UDR resource create/update/delete request to indicate the subscription context(s) whose notification needs to be disabled when triggered as consequence of a request including this header. Subsequent create/update/delete requests that do not include the 3gpp-Sbi-Notification-Correlation header trigger the corresponding notifications as per currently defined procedures.

This header contains subscription identifier(s), as provided by the UDR during the subscribe operation.

The encoding of the header follows the ABNF as defined in IETF RFC 7230 [12].

3gpp-Sbi-Notification-Correlation = "3gpp-Sbi-Notification-Correlation" ":" 1\*(OWS subscriptionId ",")


subscriptionId = token

See clause 3.2.6 of IETF RFC 7230 [12] for the "token" definition.

EXAMPLE: 3gpp-Sbi-Notification-Correlation: subsid123, subsid345.

## 6.1.3 Resources

### 6.1.3.1 Overview



**Figure 6.1.3.1-1: Resource URI structure of the Nudr\_DataRepository API**

Table 6.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 6.1.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
SubscriptionData	/subscription-data	none	For sub-level resource names, resource URIs and HTTP methods see 3GPP TS 29.505 [2]
PolicyData	/policy-data	none	For sub-level resource names, resource URIs and HTTP methods see 3GPP TS 29.519 [3]
StructuredDataForExposure	/exposure-data	none	For sub-level resource names, resource URIs and HTTP methods see 3GPP TS 29.519 [3]
ApplicationData	/application-data	none	For sub-level resource names, resource URIs and HTTP methods see 3GPP TS 29.519 [3]
DataRestorationEvents	/data-restoration-events	POST	This is a pseudo operation.

### 6.1.3.2 SubscriptionData

See 3GPP TS 29.505 [2].

### 6.1.3.3 PolicyData

See 3GPP TS 29.519 [3].

### 6.1.3.4 StructuredDataForExposure

See 3GPP TS 29.519 [3].

### 6.1.3.5 ApplicationData

See 3GPP TS 29.519 [3].

### 6.1.3.6 Resource: DataRestorationEvents

#### 6.1.3.6.1 Description

#### 6.1.3.6.2 Resource Definition

Resource URI: **{apiRoot}/nudr-dr/<apiVersion>/data-restoration-events**

This resource shall support the resource URI variables defined in table 6.1.3.6.2-1.

Table 6.1.3.6.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	string	See clause 6.1.1
apiVersion	string	See clause 6.1.1

#### 6.1.3.6.3 Resource Standard Methods

##### 6.1.3.6.3.1 POST

This method will not be actually invoked.

This method shall support the URI query parameters specified in table 6.1.3.6.3.1-1.

**Table 6.1.3.6.3.1-1: URI query parameters supported by the POST method on this resource**

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 6.1.3.6.3.1-2 and the response data structures and response codes specified in table 6.1.3.6.3.1-3.

**Table 6.1.3.6.3.1-2: Data structures supported by the POST Request Body on this resource**

Data type	P	Cardinality	Description
Any			

**Table 6.1.3.6.3.1-3: Data structures supported by the POST Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
n/a				

## 6.1.4 Custom Operations without associated resources

In this release of this specification, no custom operations without associated resources are defined for the Nudr\_DataRepository Service.

## 6.1.5 Notifications

### 6.1.5.1 General

This clause specifies the general mechanism of notifications in the following scenarios:

- notification of changed data which are stored in the UDR;
- notification of data restoration.

The mechanism shall be applicable to the data specified in 3GPP TS 29.505[2] and 3GPP TS 29.519[3].

### 6.1.5.2 Data Change Notification

The POST method shall be used for Data Change Notifications and the URI shall be as provided during the subscription procedure.

Resource URI: {callbackReference}

Support of POST request data structures should contain the object of changed data and conditionally the URI of original Callback reference, which is received from the original subscribed NF.

### 6.1.5.3 Data Restoration Notification

The POST method shall be used to inform the NF Service Consumer about a potential data-loss event occurred at the UDR, and the callback URI shall be dynamically discovered by UDR by querying NRF for a default notification URI.

Resource URI: {dataRestorationCallbackUri}

Support of URI query parameters is specified in table 6.1.5.3-1.

**Table 6.1.5.3-1: URI query parameters supported by the POST method**

Name	Data type	P	Cardinality	Description
n/a				

Support of request data structures is specified in table 6.1.5.3-2 and of response data structures and response codes is specified in table 6.1.5.3-3.

**Table 6.1.5.3-2: Data structures supported by the POST Request Body**

Data type	P	Cardinality	Description
DataRestorationNotification	M	1	Contains identifiers representing those UEs potentially affected by a data-loss event at the UDR.

**Table 6.1.5.3-3: Data structures supported by the POST Response Body**

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	Upon success, an empty response body shall be returned.
RedirectResponse	O	0..1	307 Temporary Redirect	Temporary redirection. The response shall include a Location header field containing a different URI. The URI shall be an alternative URI of the resource located on an alternative service instance within the same NF or NF (service) set. If an SCP redirects the message to another SCP then the location header field shall contain the same URI or a different URI pointing to the endpoint of the NF service consumer to which the notification should be sent.
RedirectResponse	O	0..1	308 Permanent Redirect	Permanent redirection. The response shall include a Location header field containing a different URI. The URI shall be an alternative URI of the resource located on an alternative service instance within the same NF or NF (service) set. If an SCP redirects the message to another SCP then the location header field shall contain the same URI or a different URI pointing to the endpoint of the NF service consumer to which the notification should be sent.
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute may be used to indicate one of the following application errors: - CONTEXT_NOT_FOUND

NOTE: In addition, common data structures as listed in table 5.2.7.1-1 of 3GPP TS 29.500 [7] are supported.

**Table 6.1.5.3-4: Headers supported by the 307 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the Callback URI of the target NF Service Consumer (e.g. UDM) to which the request is redirected
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target NF (service) instance ID towards which the request is redirected

**Table 6.1.5.3-5: Headers supported by the 308 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	Contains the Callback URI of the target NF Service Consumer (e.g. AMF) to which the request is redirected
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target NF (service) instance ID towards which the request is redirected

## 6.1.5a Data Model

### 6.1.5a.1 General

This clause specifies the application data model supported by the API.

Table 6.1.5a.1-1 specifies the data types defined for the Nudr\_DataRepository API.

**Table 6.1.5a.1-1: Nudr\_DataRepository specific Data Types**

Data type	Clause defined	Description
DataRestorationNotification	6.2.5a.2.2	Contains identities representing those UEs potentially affected by a data-loss event at the UDR

Table 6.1.5a.1-2 specifies data types re-used by the Nudr\_DataRepository service-based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nudr\_DataRepository service-based interface.

**Table 6.1.5a.1-2: Nudr\_DataRepository re-used Data Types**

Data type	Reference	Comments
Dnn	3GPP TS 29.571 [10]	Data Network Name with Network Identifier only.
Snssai	3GPP TS 29.571 [10]	Single NSSAI
NfGroupId	3GPP TS 29.571 [10]	NF Group ID
IdentityRange	3GPP TS 29.510 [14]	Identity Range
SupiRange	3GPP TS 29.510 [14]	SUPI Range

### 6.1.5a.2 Structured data types

#### 6.1.5a.2.1 Introduction

This clause defines the structures to be used in resource representations.

## 6.1.5a.2.2 Type: DataRestorationNotification

**Table 6.2.5a.2.2-1: Definition of type DataRestorationNotification**

Attribute name	Data type	P	Cardinality	Description
supiRanges	array(SupiRange)	O	1..N	If present, it contains the list of SUPIs potentially subject to a data-loss event at the UDR.
gpsiRanges	array(IdentityRange)	O	1..N	If present, it contains the list of GPSIs potentially subject to a data-loss event at the UDR.
resetIds	array(string)	O	1..N	If present, it contains the list of Reset-IDs of those UEs potentially subject to a data-loss event at the UDR.
sNssaiList	array(Snssai)	O	1..N	If present, it contains the list of slices (S-NSSAIs) potentially subject to a data-loss event at the UDR.
dnnList	array(Dnn)	O	1..N	If present, it contains the list of DNNs potentially subject to a data-loss event at the UDR.
lastReplicationTime	DateTime	O	0..1	If present, it contains the timestamp of the most recent instant when the data was assumed to be consistent at UDR (i.e. the potential data loss event at UDR did not occur before this instant).
recoveryTime	DateTime	O	0..1	If present, it contains the timestamp of the instant when the potential data loss event was recovered at UDR (i.e. all data records stored by UDR after this time are assumed to be consistent).
udrGroupId	NfGroupId	O	0..1	If present, it contains the ID of the UDR Group whose UEs have been potentially subject to a data loss event at the UDR.

## 6.1.6 Error Handling

Table 6.1.6-1 lists common response body data structures used within the nudr-dr (Nudr\_DataRepository) API

**Table 6.1.6-1: Common Response Body Data Structures**

Data type	P	Cardinality	Response codes	Description
ProblemDetails	O	0..1	4xx, 5xx responses	For error status codes, the UDR may provide detailed information.
NOTE: In addition common data structures as defined in 3GPP TS 29.500 [7] are supported.				

The "ProblemDetails" data structure may contain a "cause" attribute to indicate the application error, see 3GPP TS 29.571 [10]. The values for "cause" attribute are defined in table 6.1.6-2.



Table 6.1.6-2: Application Errors

Application Error	HTTP status code	Description
NF_TYPE_NOT_ALLOWED	403 Forbidden	The target data set is not permitted to access for the NF type of the NF consumer.
UNSUPPORTED_MONITORED_URI	501 Not Implemented	The subscribe service operation is not able to be implemented due to invalid resource URI to be monitored).
USER_NOT_FOUND	404 Not Found	The user indicated in the HTTP/2 request does not exist in the UDR.
DATA_NOT_FOUND	404 Not Found	The data indicated in the HTTP/2 request is unavailable in the UDR.
INCORRECT_CONDITIONAL_GET_REQUEST	412 Precondition Failed	One or more conditions given in the request header fields evaluated to false when tested in the UDR.
UNPROCESSABLE_REQUEST	422 Unprocessable Entity	The request cannot be processed due to semantic errors when trying to process a patch method.
DATABASE_INCONSISTENCY	500 Internal Server Error	Requested data cannot be returned due to database inconsistency
RESOURCE_TEMP_MOVED	307 Temporary Redirect	The resource is unavailable in the current target URI but can be temporarily found in an alternative URI.
RESOURCE_MOVED	308 Permanent Redirect	The resource is unavailable in the current target URI but can be permanently found in an alternative URI.
GROUP_IDENTIFIER_NOT_FOUND	404 Not Found	The group identifier does not exist.
MODIFICATION_NOT_ALLOWED	403 Forbidden	Modification of the target resource representation is not permitted.
PLMN_NOT_FOUND	404 Not Found	The 'servingPlmnId' indicated in the HTTP/2 query is unavailable in the UDR. This status code is also used when 'servingPlmnId' path variable contains SNPN ID, see Table 5.2.3.2-1 in 3GPP TS 29.505 [2].
NOTE:	The error codes shall apply to both 3GPP TS 29.505 [2] and 3GPP TS 29.519 [3]. In addition error codes shall comply with the definition in clause 5.2.7.2 of 3GPP TS 29.500 [7].	

## 6.1.7 Security

As indicated in 3GPP TS 33.501 [12], the access to the Nudr\_DataRepository API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [13]), using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [14]) plays the role of the authorization server.

If OAuth2 authorization is used, an NF Service Consumer, prior to consuming services offered by the Nudr\_DataRepository API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [14], clause 5.4.2.2.

NOTE: When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Nudr\_DataRepository service.

The Nudr\_DataRepository API defines the following scopes for OAuth2 authorization:

**Table 6.1.7-1: Oauth2 scopes defined in Nudr\_DataRepository API**

Scope	Description
"nudr-dr"	Access to the Nudr DataRepository API
"nudr-dr:subscription-data"	Access to the SubscriptionData data set.
"nudr-dr:subscription-data:authentication-subscription:read"	Access to read the AuthenticationSubscription resource of the SubscriptionData data set.
"nudr-dr:subscription-data:authentication-subscription:modify"	Access to update the AuthenticationSubscription resource of the SubscriptionData data set.
"nudr-dr:subscription-data:registrations:write"	Write access to NF registration resources of the SubscriptionData data set.
"nudr-dr:policy-data"	Access to the PolicyData data set.
"nudr-dr:policy-data:ues:read"	Access to read the UEs resource.
"nudr-dr:policy-data:ues:am-data:read"	Access to read the UEs Access and Mobility Policy data.
"nudr-dr:policy-data:ues:ue-policy-set:read"	Access to read the UEs Policy Set data.
"nudr-dr:policy-data:ues:ue-policy-set:create"	Access to create the UEs Policy Set data.
"nudr-dr:policy-data:ues:ue-policy-set:modify"	Access to update the UEs Policy Set data.
"nudr-dr:policy-data:ues:sm-data:read"	Access to read the UEs Session Management policy data.
"nudr-dr:policy-data:ues:sm-data:modify"	Access to update the UEs Session Management policy data.
"nudr-dr:policy-data:ues:sm-data:create"	Access to create the UEs Session Management policy data.
"nudr-dr:policy-data:sponsor-connectivity-data:read"	Access to read the sponsored connectivity data.
"nudr-dr:policy-data:bdt-data:read"	Access to read the BDT data resource.
"nudr-dr:policy-data:bdt-data:create"	Access to create the BDT data resource.
"nudr-dr:policy-data:bdt-data:modify"	Access to update the BDT data resource.
"nudr-dr:policy-data:subs-to-notify:create"	Access to create Subscriptions resources.
"nudr-dr:policy-data:subs-to-notify:modify"	Access to update Subscriptions resources.
"nudr-dr:policy-data:ues:operator-specific-data:read"	Access to read the UEs operator specific policy data.
"nudr-dr:policy-data:ues:operator-specific-data:modify"	Access to update the UEs operator specific policy data.
"nudr-dr:policy-data:ues:operator-specific-data:create"	Access to create the UEs operator specific policy data.
"nudr-dr:policy-data:slice-control-data:read"	Access to read Slice specific Policy Control Data.
"nudr-dr:policy-data:slice-control-data:modify"	Access to update Slice specific Policy Control Data.
"nudr-dr:exposure-data"	Access to the ExposureData data set.
"nudr-dr:exposure-data:access-and-mobility-data:create"	Access to create Access and Mobility data.
"nudr-dr:exposure-data:access-and-mobility-data:read"	Access to read Access and Mobility data.
"nudr-dr:exposure-data:access-and-mobility-data:modify"	Access to update Access and Mobility data.
"nudr-dr:exposure-data:session-management-data:create"	Access to create Session Management data.
"nudr-dr:exposure-data:session-management-data:read"	Access to read Session Management data.
"nudr-dr:exposure-data:session-management-data:modify"	Access to update Session Management data.
"nudr-dr:exposure-data:subs-to-notify:create"	Access to create Subscriptions resources.
"nudr-dr:exposure-data:subs-to-notify:modify"	Access to update Subscriptions resources.
"nudr-dr:application-data"	Access to the ApplicationData data set.
"nudr-dr:application-data:pfds:read"	Access to read PFDData.
"nudr-dr:application-data:pfds:modify"	Access to update PFDData.
"nudr-dr:application-data:pfds:create"	Access to create PFDData.
"nudr-dr:application-data:influence-data:read"	Access to read Traffic Influence Data.

"nudr-dr:application-data:influence-data:create"	Access to create Traffic Influence Data.
"nudr-dr:application-data:influence-data:modify"	Access to update Traffic Influence Data.
"nudr-dr:application-data:influence-data:subscriptions:create"	Access to create Traffic Influence Data Subscriptions.
"nudr-dr:application-data:influence-data:subscriptions:read"	Access to read Traffic Influence Data Subscriptions.
"nudr-dr:application-data:influence-data:subscriptions:modify"	Access to update Traffic Influence Data Subscriptions.
"nudr-dr:application-data:bdt-policy-data:read"	Access to read BDT Policy Data.
"nudr-dr:application-data:bdt-policy-data:create"	Access to create BDT Policy Data.
"nudr-dr:application-data:bdt-policy-data:modify"	Access to update BDT Policy Data.
"nudr-dr:application-data:iptv-config-data:read"	Access to read IPTV Configuration Data.
"nudr-dr:application-data:iptv-config-data:create"	Access to create IPTV Configuration Data.
"nudr-dr:application-data:iptv-config-data:modify"	Access to update IPTV Configuration Data.
"nudr-dr:application-data:service-param-data:read"	Access to read Service Parameter Data.
"nudr-dr:application-data:service-param-data:create"	Access to create Service Parameter Data.
"nudr-dr:application-data:service-param-data:modify"	Access to update Service Parameter Data.
"nudr-dr:application-data:am-influence-data:read"	Access to read AM Influence Data.
"nudr-dr:application-data:am-influence-data:create"	Access to create AM Influence Data.
"nudr-dr:application-data:am-influence-data:modify"	Access to update AM Influence Data.
"nudr-dr:application-data:subs-to-notify:create"	Access to create Subscriptions resources.
"nudr-dr:application-data:subs-to-notify:read"	Access to read Subscriptions resources.
"nudr-dr:application-data:subs-to-notify:modify"	Access to update Subscriptions resources.
"nudr-dr:application-data:eas-deploy-data:read"	Access to read EAS Deployment Information Data.
"nudr-dr:application-data:eas-deploy-data:create"	Access to create EAS Deployment Information Data.
"nudr-dr:application-data:eas-deploy-data:modify"	Access to update EAS Deployment Information Data.

## 6.1.8 Feature negotiation

The optional features in table 6.1.8-1 are defined for the Nudr\_DataRepository API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [7].

**Table 6.1.8-1: Supported Features**

Feature number	Feature Name	Description
1	ResourceRemovalNotificationPolicyData	This feature indicates the support of the complete removal of a Policy Data resource.
2	ResourceNotificationExposureDataFix	This feature indicates the support of corrections to Notifications of data changes in the Exposure Data resource.
3	DomainNameProtocol	This feature supports the additional protocol matching condition for the domain name in PFD data.
4	EnhancedBackgroundDataTransfer	This feature indicates the support of applying the Background Data Transfer Policy to a future PDU session requested by the AF for Policy Data resource and Application Data resource as defined in 3GPP TS 29.519 [3]. This feature requires the support of SessionManagementPolicyDataPatch feature to update Background Data Transfer data within the Session Management Policy Data.
5	MacAddressRange	This feature indicates the support of a set of MAC addresses with a specific range for the traffic filter in the application data resource as specified in 3GPP TS 29.519 [3].
6	MultiTemporalCondition	This feature indicates the support of multiple temporal validity conditions in the Traffic Influence Data resource as specified in 3GPP TS 29.519 [3].
7	PatchReport	If some of the modifications included in the PATCH request are not successfully implemented, the UDM reports the result of PATCH request execution to the consumer. See clause 5.2.7.2 of 3GPP TS 29.500 [7].
8	URLLC	This feature indicates support of Ultra Reliable Low Latency Communication (URLLC) requirements, i.e. AF application relocation and UE address(es) preservation in the Application Data resource as specified in 3GPP TS 29.519 [3].
9	SessionManagementPolicyDataPatch	This feature indicates the support of the HTTP PATCH method to update the session management policy data defined in a Policy Data resource as specified in 3GPP TS 29.519 [3].
10	ConditionalSubscriptionwithPartialNotification	This feature indicates the support of subscription to notification of resource data changes conditioned to the change occurs in a fragment of the resource. It applies for Policy Data resources as specified in 3GPP TS 29.519 [3].
11	EnhancedInfluDataNotification	This feature indicates the support of enhancement of data change Notifications in the Influence Data resource as specified in 3GPP TS 29.519 [3].
12	PerUePerSnAuthStatus	This feature indicates the support of the Individual authentication status per UE per serving network as specified in 3GPP TS 29.505 [2].
13	OpSpecDataMapNotification	This feature indicates the support of the notification of data changes in the OperatorSpecificData resource by including the complete map of Operator Specific Data Containers. It applies to Policy Data resources as specified in 3GPP TS 29.519 [3].
14		Reserved
15	OSDResource_Create_Delete	This feature indicates the support of the creation and the removal of the OperatorSpecificData resource by a Policy Data NF service consumer. It applies to Policy Data resources as specified in 3GPP TS 29.519 [3].
16	AF_latency	This feature indicates the support for Edge relocation considering user plane latency. It applies for Influence Data resource as specified in 3GPP TS 29.519 [3].
17	CHFsetSupport	This feature indicates the support of CHF redundancy and failover mechanisms based on CHF instance availability within a CHF Set, (i.e. secondary CHF address may be omitted). It applies to Policy Data resources as specified in 3GPP TS 29.519 [3].
18	ConditionalSubscriptionWithExcludeNotification	This feature indicates the support in the subscription to notification of data changes of the indication of the properties whose changes do not trigger a notification. It applies to Policy Data resources as specified in 3GPP TS 29.519 [3]. It requires the support of OpSpecDataMapNotification feature
19	ProSe	This feature indicates the support of UE 5G ProSe policies and subscription information. It applies for Policy Data resources as specified in 3GPP TS 29.519 [3].

20	NSAC	This feature indicates the support of NSAC (Network Slice Admission Control) related policy subscription information. It applies to Policy Data resources as specified in 3GPP TS 29.519 [3].
21	UESubDataSetRetrieve	This feature indicates the support of the UE Subscription Data Sets Retrieve as specified in clause 5.2.47 of 3GPP TS 29.505 [2].
22	SharedSmSubsData	This feature indicates the support of shared Session Management Subscription Data. If the NF consumer (UDM) does not support this feature, the UDR shall not take the alternative to include extendedSmSubsData in SmSubsData. It applies to Subscription Data resources as specified in 3GPP TS 29.505 [2].
23	DeliveryOutcome	This feature indicates the support of functionality to allow PCF notifications about the outcome of the UE Policy delivery related to the invocation of AF provisioned service parameters as specified in 3GPP TS 29.519 [3].
24	AfGuideURSP	This feature indicates the support of Application guidance for URSP determination related application data as specified in 3GPP TS 29.519 [3].
25	EasDeployment	This feature indicates the support of EAS Deployment Information Data and Subscription related application data as specified in 3GPP TS 29.519 [3].
26	DCAMP	This feature indicates the support of DCAMP related application data. It applies to Application Data resources as specified in 3GPP TS 29.519 [3].
27	FilterAnyUE	This feature indicates the support of queries and subscriptions to service parameter data resource filtered by the any UE indication as specified in 3GPP TS 29.519 [3].
28	SimultConnectivity	This feature indicates the support of temporary simultaneously connectivity at edge relocation. It applies for Influence Data resource as specified in 3GPP TS 29.519 [3].
29	EeSubscriptionExt	This feature indicates the support of handling EE subscription data along with associated subscription resources as specified in 3GPP TS 29.505 [2].
30	PeiResource	This feature indicates the support of storing PEI in the PeiInfo resource as specified in 3GPP TS 29.505 [2].

## 6.2 Nudr\_GroupIDmap Service API

### 6.2.1 API URI

URIs of this API shall have the following root:

```
{apiRoot}/<apiName>/<apiVersion>
```

where "apiRoot" is defined in clause 4.4.1 of 3GPP TS 29.501 [8], the "apiName" shall be set to "nudr-group-id-map" and the "apiVersion" shall be set to "v1" for the current version of this specification.

### 6.2.2 Usage of HTTP

#### 6.2.2.1 General

HTTP/2, as defined in IETF RFC 7540 [13], shall be used as specified in clause 5 of 3GPP TS 29.500 [7].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [7].

HTTP messages and bodies for the Nudr\_GroupIDmap service shall comply with the OpenAPI [21] specification contained in Annex A3.

## 6.2.2.2 HTTP standard headers

### 6.2.2.2.1 General

The usage of HTTP standard headers shall be supported on Nudr interface as defined in clause 5.2.2 of 3GPP TS 29.500 [7].

#### 6.2.2.2.2 Content type

The following content types shall be supported:

- JSON, as defined in IETF RFC 8259 [11], shall be used as content type of the HTTP bodies specified in the present specification as indicated in clause 5.4 of 3GPP TS 29.500 [7].
- The Problem Details JSON Object (IETF RFC 7807 [17]). The use of the Problem Details JSON object in a HTTP response body shall be signalled by the content type "application/problem+json".

#### 6.2.2.2.3 Cache-Control

As described in IETF RFC 7234 [16] clause 5.2, a "Cache-Control" header should be included in HTTP responses carrying a representation of cacheable resources. If it is included, it shall contain a "max-age" value, indicating the amount of time in seconds after which the received response is considered stale.

The "max-age" value shall be configurable by operator policy.

#### 6.2.2.2.4 ETag

As described in IETF RFC 7232 [15] clause 2.3, an "ETag" (entity-tag) header should be included in HTTP responses carrying a representation of cacheable resources to allow an NF Service Consumer performing a conditional GET request with "If-None-Match" header. If it is included, it shall contain a server-generated strong validator, that allows further matching of this value (included in subsequent client requests) with a given resource representation stored in the server or in a cache.

#### 6.2.2.2.5 If-None-Match

As described in IETF RFC 7232 [15] clause 3.2, an NF Service Consumer may issue conditional GET request towards UDR by including an "If-None-Match" header in HTTP requests containing one or several entity tags received in previous responses for the same resource.

#### 6.2.2.2.6 Last-Modified

As described in IETF RFC 7232 [15] clause 2.2, a "Last-Modified" header should be included in HTTP responses carrying a representation of cacheable resources (e.g. SmfSelectionSubscriptionData) to allow an NF Service Consumer performing a conditional request with "If-Modified-Since" header.

#### 6.2.2.2.7 If-Modified-Since

As described in IETF RFC 7232 [15] clause 3.3, an NF Service Consumer may issue conditional GET request towards UDR, by including an "If-Modified-Since" header in HTTP requests.

#### 6.2.2.2.8 When to Use Entity-Tags and Last-Modified Dates

Both "ETag" and "Last-Modified" headers should be sent in the same HTTP response as stated in IETF RFC 7232 [15] clause 2.4.

NOTE: "ETag" is a stronger validator than "Last-Modified" and is preferred.

If the UDR included an "ETag" header with the resource then a conditional GET request for this resource shall be performed with the "If-None-Match" header.



### 6.2.2.3 HTTP custom headers

#### 6.2.2.3.1 General

In this release of this specification, no custom headers specific to the Nudr\_GroupIDmap service are defined. For 3GPP specific HTTP custom headers used across all service-based interfaces, see clause 5.2.3 of 3GPP TS 29.500 [7].

## 6.2.3 Resources

### 6.2.3.1 Overview

//{apiRoot}/nudr-group-id-map/<apiVersion>



**Figure 6.2.3.1-1: Resource URI structure of the nudr-group-id-map API**

Table 6.2.3.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 6.2.3.1-1: Resources and methods overview**

Resource name	Resource URI	HTTP method	Description
NfGroupIds	/nf-group-ids	GET	

### 6.2.3.2 Resource NfGroupIds

#### 6.2.3.2.1 Description

This resource represents the NF-Group IDs for a subscriber.

#### 6.2.3.2.2 Resource Definition

Resource URI: {apiRoot}/nudr-group-id-map/<apiVersion>/nf-group-ids

This resource shall support the resource URI variables defined in table 6.2.3.2.2-1.

**Table 6.2.3.2.2-1: Resource URI variables for this resource**

Name	Definition
apiRoot	See clause 6.2.1

#### 6.2.3.2.3 Resource Standard Methods

##### 6.2.3.2.3.1 GET

This method shall support the URI query parameters specified in table 6.2.3.2.3.1-1.

**Table 6.2.3.2.3.1-1: URI query parameters supported by the GET method on this resource**

Name	Data type	P	Cardinality	Description
nf-type	array(NFType)	M	1..N	see 3GPP TS 29.510 [14]
subscriberId	SubscriberId	M	1	Represents the Subscription Identifier SUPI or GPSI or IMPI or IMPU (see 3GPP TS 23.501 [4] clause 5.9.2 and clause 5.9.8) pattern: ^(imsi-[0-9]{5,15} nai-.+ msisdn-[0-9]{5,15} extid-[^\@]+\@[^\@]+ impi-.+ impu-.+ .+)\$.

NOTE: The format of the query parameter subscriberId is in line with the yaml and thus does not follow the lower-with-hyphen format specified in 3GPP TS 29.501 [8].

This method shall support the request data structures specified in table 6.2.3.2.3.1-2 and the response data structures and response codes specified in table 6.2.3.2.3.1-3.

**Table 6.2.3.2.3.1-2: Data structures supported by the GET Request Body on this resource**

Data type	P	Cardinality	Description
n/a			

**Table 6.2.3.2.3.1-3: Data structures supported by the GET Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
NfGroupIdMapResult	M	1	200 OK	Upon success, a response body containing the NF-Group IDs for the requested NF types shall be returned.
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute may be set to one of the following application errors: - USER_NOT_FOUND

NOTE: In addition common data structures as listed in table 5.2.7.1-1 of 3GPP TS 29.500 are supported.

## 6.2.4 Custom Operations without associated resources

In this release of this specification, no custom operations without associated resources are defined for the Nudr\_GroupIDmap Service.

## 6.2.5 Notifications

In this release of this specification, no notifications are defined for the Nudr\_GroupIDmap Service.

## 6.2.6 Data Model

### 6.2.6.1 General

This clause specifies the application data model supported by the API.

Table 6.2.6.1-1 specifies the structured data types defined for the Nudr\_GroupIDmap service API. For simple data types defined for the Nudr\_GroupIDmap service API see table 6.2.6.3.2-1.

**Table 6.2.6.1-1: Nudr\_GroupIDmap specific Data Types**

Data type	Clause defined	Description
NfGroupIdMapResult	6.2.6.2.2	NF-Group IDs for the requested NF types
SubscriberId	6.2.6.3.2	Represents the Subscription Identifier SUPI or GPSI or IMPI or IMPU

Table 6.2.6.1-2 specifies data types re-used by the Nudr\_GroupIDmap service API from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nudr\_GroupIDmap service API.

**Table 6.2.6.1-2: Nudr\_GroupIDmap re-used Data Types**

Data type	Reference	Comments
ProblemDetails	3GPP TS 29.571 [10]	Common data type used in response bodies
NFType	3GPP TS 29.510 [14]	
NfGroupId	3GPP TS 29.571 [10]	

## 6.2.6.2 Structured data types

### 6.2.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

#### 6.2.6.2.2 Type: NfGroupIdMapResult

**Table 6.2.6.2.2-1: Definition of type NfGroupIdMapResult**

Attribute name	Data type	P	Cardinality	Description
nfGroupIDs	map(NfGroupId)	M	1..N	A map (list of key-value pairs where NFType serves as key) of NfGroupIDs

## 6.2.6.3 Simple data types and enumerations

### 6.2.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

#### 6.2.6.3.2 Simple data types

The simple data types defined in table 6.2.6.3.2-1 shall be supported.

**Table 6.2.6.3.2-1: Simple data types**

Type Name	Type Definition	Description
SubscriberId	string	Pattern: $\wedge(\text{imsi-[0-9]\{5,15\} nai-.\+ msisdn-[0-9]\{5,15\} extid-[\wedge\@]+\@[\wedge\@]+\text{impi-}.\+ \text{impu-}.\+ .+)\$$

## 6.2.7 Error Handling

### 6.2.7.1 General

HTTP error handling shall be supported as specified in clause 5.2.4 of 3GPP TS 29.500 [7].

#### 6.2.7.2 Protocol Errors

Protocol errors handling shall be supported as specified in clause 5.2.7 of 3GPP TS 29.500 [7].

#### 6.2.7.3 Application Errors

The common application errors defined in the Table 5.2.7.2-1 in 3GPP TS 29.500 [7] may also be used for the Nudr\_GroupIDmap service. The following application errors listed in Table 6.2.7.3-1 are specific for the Nudr\_GroupIDmap service.

**Table 6.2.7.3-1: Application errors**

Application Error	HTTP status code	Description
USER_NOT_FOUND	404 Not Found	The user does not exist in the HPLMN

## 6.2.8 Security

As indicated in 3GPP TS 33.501 [12], the access to the Nudr\_GroupIDmap API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [13]), using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [14]) plays the role of the authorization server.

If OAuth2 authorization is used, an NF Service Consumer, prior to consuming services offered by the Nudr\_GroupIDmap API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [14], clause 5.4.2.2.

**NOTE:** When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Nudr\_GroupIDmap service.

The Nudr\_GroupIDmap API defines scopes for OAuth2 authorization as specified in 3GPP TS 33.501 [12]; it defines a single scope consisting on the name of the service (i.e., "nudr-group-id-map"), and it does not define any additional scopes at resource or operation level.

## 6.2.9 Feature Negotiation

The optional features in table 6.2.9-1 are defined for the Nudr\_GroupIDmap API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [7].

**Table 6.2.9-1: Supported Features**

Feature number	Feature Name	Description

---

# Annex A (normative): OpenAPI specification

## A.1 General

This document specifies the common service operations and the top level data model for Nudr\_DataRepository Service Based Interface. There are no specific HTTP methods or custom operations on the four top level resources in Table 6.1.3.1-1. Hence, the top level OpenAPI specification is not needed.

This Annex takes precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

**NOTE:** The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on a Git-based repository, that uses the GitLab software version control system (see 3GPP TS 29.501 [8] clause 5.3.1 and 3GPP TR 21.900 [20] clause 5B).

---

## A.2 Nudr\_DataRepository API

This Annex specifies the formal definition of the Nudr\_DataRepository service. It consists of OpenAPI 3.0.0 specifications, in YAML format.

The OpenAPI 3.0.0 definition related to SubscriptionData shall comply with the definition in 3GPP TS 29.505 [2].

The OpenAPI 3.0.0 definition related to PolicyData, StructuredDataForExposure and ApplicationData shall comply with the definition in 3GPP TS 29.519 [3].

The OpenAPI file for the Nudr\_DataRepository API is defined as follows:

```
openapi: 3.0.0

info:
  version: 2.2.2
  title: 'Nudr_DataRepository API OpenAPI file'
  description: |
    Unified Data Repository Service.
    © 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.

externalDocs:
  description: 3GPP TS 29.504 V17.9.0; 5G System; Unified Data Repository Services; Stage 3
  url: 'https://www.3gpp.org/ftp/Specs/archive/29_series/29.504/'

servers:
  - description: API root
    url: '{apiRoot}/nudr-dr/v2'
    variables:
      apiRoot:
        default: https://example.com

security:
  - {}
  - oAuth2ClientCredentials:
    - nudr-dr

paths:
  /subscription-data/{ueId}/authentication-data/authentication-subscription:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1authentication-
    data~1authentication-subscription'
  /subscription-data/{ueId}/authentication-data/authentication-status:
```

```

    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1lauthentication-
data~1lauthentication-status'
    /subscription-data/{ueId}/authentication-data/authentication-status/{servingNetworkName}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1lauthentication-
data~1lauthentication-status~1%7B-servingNetworkName%7D'
    /subscription-data/{ueId}/ue-update-confirmation-data/sor-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1ue-update-
confirmation-data~1sor-data'
    /subscription-data/{ueId}/ue-update-confirmation-data/upu-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1ue-update-
confirmation-data~1upu-data'
    /subscription-data/{ueId}/ue-update-confirmation-data/subscribed-cag:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1ue-update-
confirmation-data~1subscribed-cag'
    /subscription-data/{ueId}/ue-update-confirmation-data/subscribed-snssais:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1ue-update-
confirmation-data~1subscribed-snssais'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/am-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1am-data'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/smf-selection-subscription-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1smf-selection-subscription-data'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/smf-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1sm-data'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/lcs-bca-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1lcs-bca-data'
    /subscription-data/{ueId}/context-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data'
    /subscription-data/{ueId}/context-data/amf-3gpp-access:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1amf-
3gpp-access'
    /subscription-data/{ueId}/context-data/amf-non-3gpp-access:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1amf-
non-3gpp-access'
    /subscription-data/{ueId}/context-data/smf-registrations:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1smf-
registrations'
    /subscription-data/{ueId}/context-data/smf-registrations/{pduSessionId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1smf-
registrations~1%7BpduSessionId%7D'
    /subscription-data/{ueId}/operator-specific-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1operator-specific-
data'
    /subscription-data/{ueId}/context-data/smsf-3gpp-access:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1smsf-3gpp-access'
    /subscription-data/{ueId}/context-data/smsf-non-3gpp-access:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1smsf-non-3gpp-access'
    /subscription-data/{ueId}/context-data/location:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1location'
    /subscription-data/{ueId}/context-data/ip-sm-gw:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ip-
sm-gw'
    /subscription-data/{ueId}/context-data/mwd:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1mwd'
    /subscription-data/{ueId}/context-data/roaming-information:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1roaming-information'
    /subscription-data/{ueId}/context-data/pei-info:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1pei-
info'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/sms-mng-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1sms-mng-data'
    /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/sms-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7B-servingPlmnId%7D~1lprovisioned-data~1sms-data'
    /subscription-data/{ueId}/lcs-privacy-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1lcs-privacy-data'
    /subscription-data/{ueId}/lcs-mo-data:

```

```

    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1lcs-mo-data'
  /subscription-data/{ueId}/pp-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1pp-data'
  /subscription-data/{ueId}/context-data/ee-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ee-
subscriptions'
  /subscription-data/{ueId}/context-data/ee-subscriptions/{subsId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ee-
subscriptions~1%7BsubsId%7D'
  /subscription-data/{ueId}/context-data/ee-subscriptions/{subsId}/amf-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ee-
subscriptions~1%7BsubsId%7D~1amf-subscriptions'
  /subscription-data/{ueId}/context-data/ee-subscriptions/{subsId}/smf-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ee-
subscriptions~1%7BsubsId%7D~1smf-subscriptions'
  /subscription-data/{ueId}/context-data/ee-subscriptions/{subsId}/hss-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1ee-
subscriptions~1%7BsubsId%7D~1hss-subscriptions'
  /subscription-data/group-data/{ueGroupId}/ee-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-subscriptions'
  /subscription-data/group-data/{ueGroupId}/ee-subscriptions/{subsId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-subscriptions~1%7BsubsId%7D'
  /subscription-data/group-data/{ueGroupId}/ee-subscriptions/{subsId}/amf-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-subscriptions~1%7BsubsId%7D~1amf-subscriptions'
  /subscription-data/group-data/{ueGroupId}/ee-subscriptions/{subsId}/smf-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-subscriptions~1%7BsubsId%7D~1smf-subscriptions'
  /subscription-data/group-data/{ueGroupId}/ee-subscriptions/{subsId}/hss-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-subscriptions~1%7BsubsId%7D~1hss-subscriptions'
  /subscription-data/group-data/{ueGroupId}/ee-profile-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-
data~1%7BueGroupId%7D~1ee-profile-data'
  /subscription-data/group-data/5g-vn-groups:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-data~15g-vn-groups'
  /subscription-data/group-data/5g-vn-groups/{externalGroupId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-data~15g-vn-
groups~1%7BexternalGroupId%7D'
  /subscription-data/group-data/5g-vn-groups/internal:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-data~15g-vn-
groups~1internal'
  /subscription-data/group-data/5g-vn-groups/pp-profile-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-data~15g-vn-groups~1pp-
profile-data'
  /subscription-data/{ueId}/ee-profile-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1ee-profile-data'
  /subscription-data/{ueId}/context-data/sdm-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1sdm-
subscriptions'
  /subscription-data/{ueId}/context-data/sdm-subscriptions/{subsId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1sdm-
subscriptions~1%7BsubsId%7D'
  /subscription-data/{ueId}/context-data/nidd-authorizations:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1nidd-authorizations'
  /subscription-data/{ueId}/context-data/sdm-subscriptions/{subsId}/hss-sdm-subscriptions:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-data~1sdm-
subscriptions~1%7BsubsId%7D~1hss-sdm-subscriptions'
  /subscription-data/shared-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1shared-data'
  /subscription-data/shared-data/{sharedDataId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1shared-
data~1%7BsharedDataId%7D'
  /subscription-data/subs-to-notify:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1subs-to-notify'
  /subscription-data/subs-to-notify/{subsId}:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1subs-to-notify~1%7BsubsId%7D'
  /subscription-data/{ueId}/{servingPlmnId}/provisioned-data/trace-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-
data~1%7BueId%7D~1%7BservingPlmnId%7D~1provisioned-data~1trace-data'
  /subscription-data/{ueId}/identity-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1identity-data'
  /subscription-data/{ueId}/operator-determined-barring-data:
    $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1operator-
determined-barring-data'

```

```

/subscription-data/{ueId}/nidd-authorization-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1nidd-
authorization-data'
/subscription-data/{ueId}/service-specific-authorization-data/{serviceType}:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1service-specific-
authorization-data~1%7BserviceType%7D'
/subscription-data/{ueId}/v2x-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1v2x-data'
/subscription-data/{ueId}/pp-profile-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1pp-profile-data'
/subscription-data/{ueId}/coverage-restriction-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1coverage-
restriction-data'
/subscription-data/group-data/group-identifiers:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1group-data~1group-identifiers'
/subscription-data/{ueId}/prose-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1prose-data'
/subscription-data/{ueId}/pp-data-store:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1pp-data-store'
/subscription-data/{ueId}/context-data/service-specific-authorizations/{serviceType}:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1context-
data~1service-specific-authorizations~1%7BserviceType%7D'
/subscription-data/{ueId}/5mbs-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~15mbs-data'
/subscription-data/{ueId}/uc-data:
  $ref: 'TS29505_Subscription_Data.yaml#/paths/~1subscription-data~1%7BueId%7D~1uc-data'
/policy-data/ues/{ueId}:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D'
/policy-data/ues/{ueId}/am-data:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D~1am-data'
/policy-data/ues/{ueId}/ue-policy-set:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D~1ue-policy-set'
/policy-data/ues/{ueId}/sm-data:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D~1sm-data'
/policy-data/ues/{ueId}/sm-data/{usageMonId}:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D~1sm-
data~1%7BusageMonId%7D'
/policy-data/sponsor-connectivity-data/{sponsorId}:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1sponsor-connectivity-
data~1%7BsponsorId%7D'
/policy-data/bdt-data:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1bdt-data'
/policy-data/bdt-data/{bdtReferenceId}:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1bdt-data~1%7BbdtReferenceId%7D'
/policy-data/subs-to-notify:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1subs-to-notify'
/policy-data/subs-to-notify/{subsId}:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1subs-to-notify~1%7BsubsId%7D'
/policy-data/ues/{ueId}/operator-specific-data:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1ues~1%7BueId%7D~1operator-specific-data'
/application-data/pfds:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-data~1pfds'
/application-data/pfds/{appId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-data~1pfds~1%7BappId%7D'
/application-data/influenceData:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-data~1influenceData'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/influenceData/{influenceId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-
data~1influenceData~1%7BinfluenceId%7D'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/policy-data/plmns/{plmnId}/ue-policy-set:
  $ref: 'TS29519_Policy_Data.yaml#/paths/~1policy-data~1plmns~1%7BplmnId%7D~1ue-policy-set'
/application-data/bdtPolicyData:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-data~1bdtPolicyData'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/bdtPolicyData/{bdtPolicyId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-
data~1bdtPolicyData~1%7BbdtPolicyId%7D'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/iptvConfigData:
  $ref: 'TS29519_Application_Data.yaml#/paths/~1application-data~1iptvConfigData'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.

```



```

/application-data/iptvConfigData/{configurationId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-
data~liptvConfigData~1%7BconfigurationId%7D'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/serviceParamData:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-data~lserviceParamData'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/serviceParamData/{serviceParamId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-
data~lserviceParamData~1%7BserviceParamId%7D'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/influenceData/subs-to-notify:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-data~linfluenceData~lsubs-to-notify'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/influenceData/subs-to-notify/{subscriptionId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-data~linfluenceData~lsubs-to-
notify~1%7BsubscriptionId%7D'
# The path segment is left not following the naming convention as defined in 3GPP TS 29.501 due to
backward compatibility consideration.
/application-data/subs-to-notify:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-data~lsubs-to-notify'
/application-data/subs-to-notify/{subsId}:
  $ref: 'TS29519_Application_Data.yaml#/paths/~lapplication-data~lsubs-to-notify~1%7BsubsId%7D'
/exposure-data/{ueId}/access-and-mobility-data:
  $ref: 'TS29519_Exposure_Data.yaml#/paths/~lexposure-data~1%7BueId%7D~laccess-and-mobility-data'
/exposure-data/{ueId}/session-management-data/{pduSessionId}:
  $ref: 'TS29519_Exposure_Data.yaml#/paths/~lexposure-data~1%7BueId%7D~lsession-management-
data~1%7BpduSessionId%7D'
/exposure-data/subs-to-notify:
  $ref: 'TS29519_Exposure_Data.yaml#/paths/~lexposure-data~lsubs-to-notify'
/exposure-data/subs-to-notify/{subId}:
  $ref: 'TS29519_Exposure_Data.yaml#/paths/~lexposure-data~lsubs-to-notify~1%7BsubId%7D'
/data-restoration-events:
  post:
    # This is a pseudo operation, clients shall NOT invoke this method!
    summary: subscribe to data restoration notifications
    operationId: CreateIndividualSubscription
    tags:
      - Subscriptions (Collection)
    requestBody:
      required: true
      content:
        application/json:
          schema: {}
    responses:
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'
    callbacks:
      restorationNotification:
        '{dataRestorationCallbackUri}':
          # The URI in {dataRestorationCallbackUri} is the default endpoint discovered from NRF.
          post:
            requestBody:
              required: true
              content:
                application/json:
                  schema:
                    $ref: '#/components/schemas/DataRestorationNotification'
            responses:
              '204':
                description: No Content, Notification was succesfull
              '307':
                description: Temporary Redirect
                content:
                  application/json:
                    schema:
                      $ref: 'TS29571_CommonData.yaml#/components/schemas/RedirectResponse'
            headers:
              Location:
                description: 'The URI pointing to the resource located on the redirect target
NF service consumer'
              required: true
              schema:
                type: string

```

```

    '308':
      description: Permanent Redirect
      content:
        application/json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/RedirectResponse'
      headers:
        Location:
          description: 'The URI pointing to the resource located on the redirect target
NF service consumer'
          required: true
          schema:
            type: string
    '404':
      $ref: 'TS29571_CommonData.yaml#/components/responses/404'
  default:
    $ref: 'TS29571_CommonData.yaml#/components/responses/default'

components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            nudr-dr: Access to the Nudr_DataRepository API
            nudr-dr:subscription-data: Access to the SubscriptionData data set
AuthenticationSubscription resource of the SubscriptionData data set
            nudr-dr:subscription-data:authentication-subscription:read: Access to read the
AuthenticationSubscription resource of the SubscriptionData data set
            nudr-dr:subscription-data:authentication-subscription:modify: Access to update the
AuthenticationSubscription resource of the SubscriptionData data set
            nudr-dr:subscription-data:registrations:write: Write access to NF registration resources
of the SubscriptionData data set
            nudr-dr:policy-data: Access to the PolicyData data set
            nudr-dr:policy-data:ues:read: Access to read the UEs resource
            nudr-dr:policy-data:ues:am-data:read: Access to read the UEs Access and Mobility policy
data
            nudr-dr:policy-data:ues:ue-policy-set:read: Access to read the UEs Policy Set data
            nudr-dr:policy-data:ues:ue-policy-set:create: Access to create the UEs Policy Set data
            nudr-dr:policy-data:ues:ue-policy-set:modify: Access to update the UEs Policy Set data
            nudr-dr:policy-data:ues:sm-data:read: Access to read the UEs Session Management Policy
data
            nudr-dr:policy-data:ues:sm-data:modify: Access to update the UEs Session Management
Policy data
            nudr-dr:policy-data:ues:sm-data:create: Access to create the UEs Session Management
Policy data
            nudr-dr:policy-data:sponsor-connectivity-data:read: Access to read the sponsored
Connectivity Data
            nudr-dr:policy-data:bdt-data:read: Access to read the BDT data resource
            nudr-dr:policy-data:bdt-data:create: Access to create the BDT data resource
            nudr-dr:policy-data:bdt-data:modify: Access to update the BDT data resource
            nudr-dr:policy-data:subs-to-notify:create: Access to create Subscriptions resources
            nudr-dr:policy-data:subs-to-notify:modify: Access to update Subscriptions resources
            nudr-dr:policy-data:ues:operator-specific-data:read: Access to read the UEs operator
specific policy data
            nudr-dr:policy-data:ues:operator-specific-data:modify: Access to update the UEs operator
specific policy data
            nudr-dr:policy-data:ues:operator-specific-data:create: Access to create the UEs operator
specific policy data
            nudr-dr:policy-data:slice-control-data:read: Access to read Slice specific Policy
Control Data
            nudr-dr:policy-data:slice-control-data:modify: Access to update Slice specific Policy
Control Data
            nudr-dr:exposure-data: Access to the ExposureData data set
            nudr-dr:exposure-data:access-and-mobility-data:create: Access to create ExposureData
            nudr-dr:exposure-data:access-and-mobility-data:read: Access to read ExposureData
            nudr-dr:exposure-data:access-and-mobility-data:modify: Access to update ExposureData
            nudr-dr:exposure-data:session-management-data:create: Access to create ExposureData
            nudr-dr:exposure-data:session-management-data:read: Access to read ExposureData
            nudr-dr:exposure-data:session-management-data:modify: Access to update ExposureData
            nudr-dr:exposure-data:subs-to-notify:create: Access to create Subscriptions resources
            nudr-dr:exposure-data:subs-to-notify:modify: Access to update Subscriptions resources
            nudr-dr:application-data: Access to the ApplicationData data set
            nudr-dr:application-data:pfds:read: Access to read PFDData
            nudr-dr:application-data:pfds:modify: Access to update PFDData
            nudr-dr:application-data:pfds:create: Access to create PFDData
            nudr-dr:application-data:influence-data:read: Access to read Traffic Influence Data

```

```

    nudr-dr:application-data:influence-data:create: Access to create Traffic Influence Data.
    nudr-dr:application-data:influence-data:modify: Access to update Traffic Influence Data
    nudr-dr:application-data:influence-data:subscriptions:read: Access to read Traffic
Influence Data Subscriptions
    nudr-dr:application-data:influence-data:subscriptions:create: Access to create Traffic
Influence Data Subscriptions
    nudr-dr:application-data:influence-data:subscriptions:modify: Access to update Traffic
Influence Data Subscriptions
    nudr-dr:application-data:bdt-policy-data:read: Access to read BDT Policy Data
    nudr-dr:application-data:bdt-policy-data:create: Access to create BDT Policy Data
    nudr-dr:application-data:bdt-policy-data:modify: Access to update BDT Policy Data
    nudr-dr:application-data:iptv-config-data:read: Access to read IPTV Configuration Data
    nudr-dr:application-data:iptv-config-data:create: Access to create IPTV Configuration
Data
    nudr-dr:application-data:iptv-config-data:modify: Access to update IPTV Configuration
Data
    nudr-dr:application-data:service-param-data:read: Access to read Service Parameter Data
    nudr-dr:application-data:service-param-data:create: Access to create Service Parameter
Data
    nudr-dr:application-data:service-param-data:modify: Access to update Service Parameter
Data
    nudr-dr:application-data:am-influence-data:read: Access to read AM Influence Data
    nudr-dr:application-data:am-influence-data:create: Access to create AM Influence Data
    nudr-dr:application-data:am-influence-data:modify: Access to update AM Influence Data
    nudr-dr:application-data:subs-to-notify:create: Access to create Subscriptions resources
    nudr-dr:application-data:subs-to-notify:read: Access to read Subscriptions resources
    nudr-dr:application-data:subs-to-notify:modify: Access to update Subscriptions resources
    nudr-dr:application-data:eas-deploy-data:read: Access to read EAS Deployment Information
Data
    nudr-dr:application-data:eas-deploy-data:create: Access to create EAS Deployment
Information Data
    nudr-dr:application-data:eas-deploy-data:modify: Access to update EAS Deployment
Information Data

schemas:
  DataRestorationNotification:
    description: Contains identities representing those UEs potentially affected by a data-loss
event at the UDR
    type: object
    properties:
      supiRanges:
        type: array
        items:
          $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/SupiRange'
        minItems: 1
      gpsiRanges:
        type: array
        items:
          $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/IdentityRange'
        minItems: 1
      resetIds:
        type: array
        items:
          type: string
        minItems: 1
      sNssaiList:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
        minItems: 1
      dnnList:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Dnn'
        minItems: 1
      udrGroupId:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'

```

---

## A.3 Nudr\_GroupIDmap API

```
openapi: 3.0.0
```

```
info:
  version: 1.1.0
```

```

title: 'Nudr_GroupIDmap'
description: |
  Unified Data Repository Service for NF-Group ID retrieval.
  © 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
  All rights reserved.

externalDocs:
  description: 3GPP TS 29.504 V17.7.0; 5G System; Unified Data Repository Services; Stage 3
  url: 'https://www.3gpp.org/ftp/Specs/archive/29_series/29.504/'

servers:
  - description: API root
    url: '{apiRoot}/nudr-group-id-map/v1'
    variables:
      apiRoot:
        default: https://example.com

security:
  - {}
  - oAuth2ClientCredentials:
      - nudr-group-id-map

paths:
  /nf-group-ids:
    get:
      summary: Retrieves NF-Group IDs for provided Subscriber and NF types
      operationId: GetNfGroupIDs
      tags:
        - NF Group IDs (Document)
      parameters:
        - name: nf-type
          in: query
          description: Type of NF
          required: true
          style: form
          explode: false
          schema:
            type: array
            items:
              $ref: 'TS29510_Nnrf_NFManagement.yaml#/components/schemas/NFType'
            minItems: 1
        - name: subscriberId
          # The name of this query parameter is left not following the naming convention as defined in 3GPP TS
          # 29.501 due to backward compatibility consideration.
          in: query
          description: Identifier of the subscriber
          required: true
          schema:
            $ref: '#/components/schemas/SubscriberId'
      responses:
        '200':
          description: Expected response to a valid request
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/NfGroupIdMapResult'
        '404':
          $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      default:
        description: Unexpected error

components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            nudr-group-id-map: Access to the Nudr_GroupIDmap API

schemas:

# COMPLEX TYPES:

```

```
NfGroupIdMapResult:
  description: Contains the NfGroupIds for the requested NF types. The NFType is the key of the
map.
  type: object
  additionalProperties:
    $ref: 'TS29571_CommonData.yaml#/components/schemas/NfGroupId'
  minProperties: 1

# SIMPLE TYPES:

SubscriberId:
  description: Represents the Subscription Identifier SUPI or GPSI or IMPI or IMPU.
  type: string
  pattern: '^(imsi-[0-9]{5,15}|nai-\.+|msisdn-[0-9]{5,15}|extid-[^\@]+\@[^\@]+|impi-\.+|impu-\.+|\.+)\$'

# ENUMS:
```

## Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2018-01	CT4#82	C4-181365				TS skeleton	0.0.0
2018-01	CT4#82	C4-181396				Inclusion of pCRs agreed at CT4#82, including C4-181366, C4-181367, C4-181323 and C4-181385.	0.1.0
2018-03	CT4#83	C4-182441				Inclusion of pCRs agreed at CT4#83, including C4-182337, C4-182429.	0.2.0
2018-04	CT4#84	C4-183522				Inclusion of pCRs agreed at CT4#84, including C4-183497, C4-183295, C4-183296, C4-183297, C4-183102, C4-183420, C4-183498.	0.3.0
2018-05	CT4#85	C4-184636				Inclusion of pCRs agreed at CT4#85, including C4-184482, C4-184484, C4-184167, C4-184168, C4-184489, C4-184564, C4-184637.	0.4.0
2018-06	CT#80	CP-181102				Presented for information and approval	1.0.0
2018-06	CT#80					Approved in CT#80.	15.0.0
2018-09	CT#81	CP-182057	0002	1	F	Service Name	15.1.0
2018-09	CT#81	CP-182057	0006	2	F	Supported Features Negotiation	15.1.0
2018-09	CT#81	CP-182057	0004	2	F	Error handling in UDR	15.1.0
2018-09	CT#81	CP-182211	0003	4		OpenAPI file for Nudr_DataRepository API	15.1.0
2018-10	CT#82	CP-183015	0008	-	F	Update the Reference point name	15.2.0
2018-10	CT#82	CP-183015	0009	-	F	Introduction of Barring of Roaming in 5GC	15.2.0
2018-10	CT#82	CP-183015	0010	1	F	Shared Data	15.2.0
2018-10	CT#82	CP-183015	0011	-		Get multiple datasets for ProvsionedData	15.2.0
2018-10	CT#82	CP-183015	0012	1	F	Definition of Authentication Data	15.2.0
2018-12	CT#82	CP-183015	0013	1	F	Adding headers for cache control and conditional request to the Nudr Services API	15.2.0
2018-12	CT#82	CP-183015	0014	-		APIRoot Clarification	15.2.0
2018-12	CT#82	CP-183015	0015	2	F	lifetime of subscription	15.2.0
2018-12	CT#82	CP-183015	0016	1	F	Authorized Event Types	15.2.0
2018-12	CT#82	CP-183015	0017	-		Group Subscription Path	15.2.0
2018-12	CT#82	CP-183177	0018	2	F	PLMN ID as key for UE data sets	15.2.0
2018-12	CT#82	CP-183241	0020	1	F	Correction to Nudr_DataRepository service OpenAPI	15.2.0
2019-03	CT#83	CP-190020	0021	1		CR 0018r2 was not implemented	15.3.0
2019-03	CT#83	CP-190020	0022	2		Corrections on openAPI	15.3.0
2019-03	CT#83	CP-190020	0023			UDR Application Errors	15.3.0
2019-03	CT#83	CP-190020	0025	1		Missing URLs in UDR API	15.3.0
2019-03	CT#83	CP-190172	0026	1		3GPP TS 29.504 API version update	15.3.0
2019-06	CT#84	CP-191031	0027	-	F	Content Type	15.4.0
2019-06	CT#84	CP-191031	0028	-	F	UE Parameter Update (UPU)	15.4.0
2019-06	CT#84	CP-191031	0030	1	F	Group Identifier Translation	15.4.0
2019-06	CT#84	CP-191031	0032	2	F	Storage of OpenAPI specification files	15.4.0
2019-06	CT#84	CP-191031	0034	1	F	Missing Context Path	15.4.0
2019-06	CT#84	CP-191031	0035	-	F	Copyright Note in YAML file	15.4.0
2019-06	CT#84	CP-191031	0038	-	F	3GPP TS 29.504 API version update	15.4.0
2019-06	CT#84	CP-191031	0036	1	F	Resource notification featurres for Policy and Exposure Data	15.4.0
2019-06	CT#84	CP-191048	0037	-	F	3GPP TS 29.504 API version update	16.0.0
2019-06	CT#84	CP-191051	0029	1	B	PFD extension for domain name	16.0.0
2019-09	CT#85	CP-192133	0040	-	B	Closed Access Group	16.1.0
2019-09	CT#85	CP-192133	0041	-	B	VN-Group parameter provisioning	16.1.0
2019-09	CT#85	CP-192123	0042	-	B	Conditional POST / PUT / PATCH / DELETE requests	16.1.0
2019-09	CT#85	CP-192190	0048	1	B	New supported features for xBDT	16.1.0
2019-09	CT#85	CP-192123	0049	1	B	Support a set of MAC addresses in traffic filter	16.1.0
2019-09	CT#85	CP-192123	0050	1	B	Multiple temporal validity conditions for AF traffic influence	16.1.0
2019-09	CT#85	CP-192123	0039	1	B	Network Slicing Subscription Change	16.1.0
2019-09	CT#85	CP-192123	0044	1	F	UDR Application Errors	16.1.0
2019-09	CT#85	CP-192104	0054	1	A	Correction on Feature numbers	16.1.0
2019-09	CT#85	CP-192120	0056	-	F	3GPP TS 29.504 API version update	16.1.0
2019-10	-	-	-	-	-	TS outlook fixed	16.1.1
2019-12	CT#86	CP-193028	0066		A	Wrong YAML Structure of OpenAPI 'info' Clause	16.2.0
2019-12	CT#86	CP-193028	0068		A	CR 0026r1 was not correctly implemented	16.2.0
2019-12	CT#86	CP-193039	0070	1	B	Update Application Data Resources	16.2.0
2019-12	CT#86	CP-193044	0073		F	3GPP TS 29.504 API version update	16.2.0
2019-12	CT#86	CP-193049	0069	1	B	NIDD Authorization Data	16.2.0
2019-12	CT#86	CP-193055	0060	1	B	LCS Private	16.2.0
2019-12	CT#86	CP-193055	0061	1	B	Mobile Originated Data	16.2.0
2019-12	CT#86	CP-193060	0058	1	B	Missed URLLC feature from Application Data	16.2.0
2019-12	CT#86	CP-193063	0059		B	Patch Report Feature	16.2.0
2019-12	CT#86	CP-193063	0057	2	F	Clarification on Implicit Subscriptions to Notifications	16.2.0
2019-12	CT#86	CP-193130	0064	2	B	Nudr_GroupIDmap Service	16.2.0
2019-12	CT#86	CP-193064	0063	1	B	Definition of SessionManagementPolicyDataPatch feature	16.2.0
2020-03	CT#87	CP-200020	0079		B	Mute Notifications	16.3.0

2020-03	CT#87	CP-200039	0074	2	F	Add Corresponding API descriptions in clause 5.1	16.3.0
2020-03	CT#87	CP-200020	0080	1	B	Definition of ConditionalSubscription and NotificationResourceFragment features	16.3.0
2020-03	CT#87	CP-200052	0082		F	3GPP TS 29.504 Rel16 API version and External doc update	16.3.0
2020-03	CT#87	CP-200098	0083		B	Definition of EnhancedInfluDataNotification feature	16.3.0
2020-06	CT#88-e	CP-201046	0084		B	Coverage restriction data resource	16.4.0
2020-06	CT#88-e	CP-201032	0086		B	Location information retrieval for GMLC	16.4.0
2020-06	CT#88-e	CP-201032	0087		B	Resource LcsPrivacySubscriptionData	16.4.0
2020-06	CT#88-e	CP-201071	0088		F	Storage of YAML files in ETSI Forge	16.4.0
2020-06	CT#88-e	CP-201020	0090		A	Definition of OpSpecDataMapNotification feature	16.4.0
2020-06	CT#88-e	CP-201049	0091		B	Correction on V2X Subscription data	16.4.0
2020-06	CT#88-e	CP-201034	0093		F	Cardinality of ProblemDetails	16.4.0
2020-06	CT#88-e	CP-201034	0094		B	Resource Level Authorization	16.4.0
2020-06	CT#88-e	CP-201033	0095		B	Support of SMSolP	16.4.0
2020-06	CT#88-e	CP-201032	0096		F	Mobile Originated Data retrieval	16.4.0
2020-06	CT#88-e	CP-201034	0097		F	New feature of per UE per serving network authEvent	16.4.0
2020-06	CT#88-e	CP-201073	0098		F	29.504 Rel16 API version and External doc update	16.4.0
2020-09	CT#89-e	CP-202110	100		F	Scopes for Resource Level Authorization	16.5.0
2020-09	CT#89-e	CP-202112	104		F	Store Broadcast Location Assistance Data	16.5.0
2020-09	CT#89-e	CP-202110	105	1	F	Corrections with regard to references	16.5.0
2020-09	CT#89-e	CP-202096	107		F	API version and External doc update	16.5.0
2020-09	CT#89-e	CP-202123	101		B	Resource Level Authorization for Data Sets	17.0.0
2020-09	CT#89-e	CP-202123	102		B	Resource Level Authorization for registrations	17.0.0
2020-09	CT#89-e	CP-202120	106		B	API version and External doc update	17.0.0
2020-12	CT#90-e	CP-203049	0111	1	A	HSS can consume UDR services	17.1.0
2020-12	CT#90-e	CP-203042	0113		A	5G VN Groups	17.1.0
2020-12	CT#90-e	CP-203035	0115		A	Storage of YAML files in 3GPP Forge	17.1.0
2020-12	CT#90-e	CP-203061	0117		B	Data retrieval of multiple policy data sets	17.1.0
2020-12	CT#90-e	CP-203055	0119		F	Rel17 API version and External doc update	17.1.0
2021-03	CT#91-e	CP-210021	0120		F	SCP may consume Nudr service	17.2.0
2021-03	CT#91-e	CP-210043	0122	1	A	Incorrect NfGroupIds definition and missing UDR access paths	17.2.0
2021-03	CT#91-e	CP-210021	0123	1	B	Add Feature for Session Management Policy Data per PLMN	17.2.0
2021-03	CT#91-e	CP-210034	0124	1	F	OpenAPI Reference and description field for map data types	17.2.0
2021-03	CT#91-e	CP-210048	0126		A	SMF Events Storage Resource Path	17.2.0
2021-03	CT#91-e	CP-210029	0127		F	29.504 Rel-17 API version and External doc update	17.2.0
2021-06	CT#92-e	CP-211028	0130	1	F	Change Notification of Array to Stateless UDM	17.3.0
2021-06	CT#92-e	CP-211028	0142		F	Data Types Descriptions	17.3.0
2021-06	CT#92-e	CP-211031	0131	1	B	Support of User Plane Latency requirements	17.3.0
2021-06	CT#92-e	CP-211039	0132		B	Store ProSe Subscription Data	17.3.0
2021-06	CT#92-e	CP-211039	0144		B	Add new ProSe feature	17.3.0
2021-06	CT#92-e	CP-211045	0141		B	Correction to OSD Handling	17.3.0
2021-06	CT#92-e	CP-211045	0143		B	New feature ConditionalSubscriptionWithExcludeNotification	17.3.0
2021-06	CT#92-e	CP-211050	0145		F	29.504 Rel-17 API version and External doc update	17.3.0
2021-06	CT#92-e	CP-211059	0140	1	F	Correction to Charing Information	17.3.0
2021-06	CT#92-e	CP-211079	0134		A	Subscribed EE profile data for a group	17.3.0
2021-06	CT#92-e	CP-211079	0136		A	Subscribed PP profile data for 5g-VN-group	17.3.0
2021-06	CT#92-e	CP-211079	0138		A	Subscribed PP profile data	17.3.0
2021-09	CT#93-e	CP-212030	0148	1	B	New feature for NSAC	17.4.0
2021-09	CT#93-e	CP-212049	0150	1	B	Get the PP data of multiple Afs	17.4.0
2021-09	CT#93-e	CP-212059	0151		F	29.504 Rel-17 API version and External doc update	17.4.0
2021-09	CT#93-e	CP-212064	0154		A	SharedDataId Resource	17.4.0
2021-12	CT#94-e	CP-213085	0156		B	UE Subscription Data Sets Retrieve	17.5.0
2021-12	CT#94-e	CP-213085	0157		F	Corrections to the API URI	17.5.0
2021-12	CT#94-e	CP-213085	0159		B	Share Session Management Subscription Data	17.5.0
2021-12	CT#94-e	CP-213086	0163		F	NIDD Authorization data storage	17.5.0
2021-12	CT#94-e	CP-213086	0167		F	Subscription update	17.5.0
2021-12	CT#94-e	CP-213087	0168		B	Update Roaming Status in EPC	17.5.0
2021-12	CT#94-e	CP-213087	0162	1	F	Consumer service logic	17.5.0
2021-12	CT#94-e	CP-213088	0166	1	A	Naming Convention	17.5.0
2021-12	CT#94-e	CP-213093	0155	1	B	Support for Service Specific Authorization	17.5.0
2021-12	CT#94-e	CP-213093	0164		B	Supported Features needed for the Enhanced Edge Computing functionality	17.5.0
2021-12	CT#94-e	CP-213097	0158		B	Store 5MBS Subscription Data	17.5.0
2021-12	CT#94-e	CP-213121	0169		F	29.504 Rel-17 API version and External doc update	17.5.0
2021-12	CT#94-e	CP-213136	0161		A	Path definitions	17.5.0
2022-03	CT#95-e	CP-220023	0176		F	Resource paths in Group Subscription Storage	17.6.0
2022-03	CT#95-e	CP-220031	0179	1	B	Handling of supported features for Edge Computing	17.6.0
2022-03	CT#95-e	CP-220036	0174	1	B	UDR restoration notification	17.6.0
2022-03	CT#95-e	CP-220041	0173		B	SOR-AF as NF consumer of UDR	17.6.0
2022-03	CT#95-e	CP-220042	0178	1	B	UDR features for TSC and DCAMP	17.6.0
2022-03	CT#95-e	CP-220047	0172	1	B	New value for 404 status code	17.6.0



2022-03	CT#95-e	CP-220049	0175	1	B	User Consent subscription	17.6.0
2022-03	CT#95-e	CP-220066	0181		F	29.504 Rel-17 API version and External doc update	17.6.0
2022-03	CT#95-e	CP-220090	0180		F	Update incorrect NOTE format	17.6.0
2022-06	CT#96-e	CP-221025	0191	1	F	UDR Restoration	17.7.0
2022-06	CT#96-e	CP-221028	0185	1	F	Logical Relationship of Query Parameters	17.7.0
2022-06	CT#96-e	CP-221028	0186	1	F	OAuth2 scopes for policy data	17.7.0
2022-06	CT#96-e	CP-221028	0189		F	OAuth2 scopes for exposure data	17.7.0
2022-06	CT#96-e	CP-221029	0188	1	F	OAuth2 scopes for application data	17.7.0
2022-06	CT#96-e	CP-221029	0190	1	F	UDM to support Optimized EventExposure Subscriptions Data access over Nudr	17.7.0
2022-06	CT#96-e	CP-221034	0184	1	F	Missing supported features in Nudr service	17.7.0
2022-06	CT#96-e	CP-221051	0193		F	29.504 Rel-17 API version and External doc update	17.7.0
2022-06	CT#96-e	CP-221052	0192		F	Update of description of feature ConditionalSubscriptionWithExcludeNotification	17.7.0
2022-06	CT#96-e	CP-221057	0183		F	FilterAnyUE feature	17.7.0
2022-09	CT#97-e	CP-222057	0194		F	PEI Information	17.8.0
2022-09	CT#97-e	CP-222058	0195		F	29.504 Rel-17 API version and External doc update	17.8.0
2022-12	CT#98-e	CP-223066	0200		F	29.504 Rel-17 API version and External doc update	17.9.0
2023-03	CT#99	CP-230072	0202	1	F	Removing of unnecessary feature	17.10.0

---

# History

<b>Document history</b>		
V17.6.0	May 2022	Publication
V17.7.0	July 2022	Publication
V17.8.0	October 2022	Publication
V17.9.0	January 2023	Publication
V17.10.0	April 2023	Publication