

# ETSI TS 129 559 V17.3.0 (2023-07)



**5G;  
5G System;  
5G ProSe Key Management Services;  
Stage 3  
(3GPP TS 29.559 version 17.3.0 Release 17)**



---

**Reference**

RTS/TSGC-0429559vh30

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope .....	7
2 References .....	7
3 Definitions of terms, symbols and abbreviations .....	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 Overview .....	8
5 Services offered by the 5G PKMF .....	9
5.1 Introduction .....	9
5.2 Npkmf_PKMFKeyRequest Service .....	9
5.2.1 Service Description.....	9
5.2.2 Service Operations.....	9
5.2.2.1 Introduction.....	9
5.2.2.2 ProseKey .....	9
5.2.2.2.1 General .....	9
5.3 Npkmf_ResolveRemoteUserId Service.....	10
5.3.1 Service Description.....	10
5.3.2 Service Operations .....	11
5.3.2.1 Introduction.....	11
5.3.2.2 Retrieve .....	11
5.3.2.2.1 General .....	11
6 API Definitions .....	11
6.1 Npkmf_PKMFKeyRequest Service API.....	11
6.1.1 Introduction.....	11
6.1.2 Usage of HTTP .....	12
6.1.2.1 General .....	12
6.1.2.2 HTTP standard headers .....	12
6.1.2.2.1 General .....	12
6.1.2.2.2 Content type .....	12
6.1.2.3 HTTP custom headers .....	12
6.1.3 Resources .....	12
6.1.3.1 Overview .....	12
6.1.3.2 Resource: ProSe Keys Collection .....	13
6.1.3.2.1 Description .....	13
6.1.3.2.2 Resource Definition.....	13
6.1.3.2.3 Resource Standard Methods .....	13
6.1.3.2.4 Resource Custom Operations .....	14
6.1.3.2.4.1 Overview.....	14
6.1.3.2.4.2 Operation: request.....	14
6.1.3.2.4.2.1 Description .....	14
6.1.3.2.4.2.2 Operation Definition .....	14
6.1.4 Custom Operations without associated resources .....	15
6.1.5 Notifications .....	15
6.1.6 Data Model .....	15
6.1.6.1 General .....	15
6.1.6.2 Structured data types .....	16
6.1.6.2.1 Introduction .....	16
6.1.6.2.2 Type: ProseKeyReqData .....	16

6.1.6.2.3	Type: ProseKeyRspData.....	17
6.1.6.3	Simple data types and enumerations .....	17
6.1.6.3.1	Introduction .....	17
6.1.6.3.2	Simple data types.....	17
6.1.6.4	Data types describing alternative data types or combinations of data types .....	18
6.1.6.5	Binary data .....	18
6.1.7	Error Handling .....	18
6.1.7.1	General .....	18
6.1.7.2	Protocol Errors .....	19
6.1.7.3	Application Errors.....	19
6.1.8	Feature negotiation .....	19
6.1.9	Security .....	19
6.1.10	HTTP redirection .....	19
6.2	Npkmf_ResolveRemoteUserId Service API .....	20
6.2.1	Introduction.....	20
6.2.2	Usage of HTTP .....	20
6.2.2.1	General .....	20
6.2.2.2	HTTP standard headers .....	20
6.2.2.2.1	General .....	20
6.2.2.2.2	Content type .....	20
6.2.2.3	HTTP custom headers .....	20
6.2.3	Resources .....	21
6.2.3.1	Overview .....	21
6.2.4	Custom Operations without associated resources .....	21
6.2.4.1	Overview .....	21
6.2.4.2	Operation: resolve-id.....	21
6.2.4.2.1	Description .....	21
6.2.4.2.2	Operation Definition.....	21
6.2.5	Notifications .....	22
6.2.6	Data Model .....	22
6.2.6.1	General .....	22
6.2.6.2	Structured data types .....	23
6.2.6.2.1	Introduction .....	23
6.2.6.2.2	Type: ResolveRequest.....	23
6.2.6.2.3	Type: ResolveResponse.....	23
6.2.6.3	Simple data types and enumerations .....	23
6.2.6.4	Data types describing alternative data types or combinations of data types .....	23
6.2.6.5	Binary data .....	23
6.2.7	Error Handling .....	24
6.2.7.1	General .....	24
6.2.7.2	Protocol Errors .....	24
6.2.7.3	Application Errors.....	24
6.2.8	Feature negotiation .....	24
6.2.9	Security .....	24
6.2.10	HTTP redirection.....	24
<b>Annex A (normative):</b>	<b>OpenAPI specification.....</b>	<b>26</b>
A.1	General .....	26
A.2	Npkmf_PKMFKeyRequest API.....	26
A.3	Npkmf_ResolveRemoteUserId API .....	28
<b>Annex B (informative):</b>	<b>Change history .....</b>	<b>30</b>
History .....		31

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

---

# 1 Scope

The present document specifies the stage 3 protocol and data model for the Npkmf Service Based Interface. It provides stage 3 protocol definitions and message flows, and specifies the API for each service offered by the 5G PKMF as specified in 3GPP TS 33.503 [4].

The 5G System stage 2 architecture and procedures are specified in 3GPP TS 23.501 [2] and 3GPP TS 23.502 [3].

The Technical Realization of the Service Based Architecture and the Principles and Guidelines for Services Definition are specified in 3GPP TS 29.500 [5] and 3GPP TS 29.501 [6].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 33.503: "Security Aspects of Proximity based Services (ProSe) in the 5G System (5GS)".
- [5] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [6] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [7] OpenAPI : "OpenAPI Specification Version 3.0.0", <https://spec.openapis.org/oas/v3.0.0>.
- [8] IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
- [9] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [10] IETF RFC 7807: "Problem Details for HTTP APIs".
- [11] 3GPP TS 33.501: "Security architecture and procedures for 5G system".
- [12] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
- [13] 3GPP TS 29.510: "Network Function Repository Services; Stage 3".
- [14] 3GPP TR 21.900: "Technical Specification Group working methods".
- [15] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces; Stage 3".
- [16] 3GPP TS 24.554: "Proximity-services (ProSe) in 5G System (5GS) protocol aspects; Stage 3".
- [17] 3GPP TS 29.503: "5G System; Unified Data Management Services; Stage 3".
- [18] 3GPP TS 29.509: "5G System; Authentication Server Services; Stage 3".



## 3 Definitions of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**5G PKMF:** 5G ProSe Key Management Function (5G PKMF) is the logical function handling network related actions required for the key management and the security material for discovery of a 5G ProSe UE-to-Network Relay by a 5G ProSe Remote UE; and for establishing a secure PC5 communication link between a 5G ProSe Remote UE and 5G ProSe UE-to-Network Relay.

**PKMF Key Request:** A procedure employed by the 5G PKMF of the 5G ProSe Remote UE to request the discovery security materials to the 5G PKMFs of the potential 5G ProSe UE-to-Network Relays from which the 5G ProSe Remote UE gets the relay services; or employed by the 5G PKMF of the 5G ProSe UE-to-Network Relay to request the security materials (e.g. PRUK key) for PC5 communication with the 5G ProSe Remote UE from the 5G PKMF of the 5G ProSe Remote UE.

### 3.2 Symbols

Void

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5G PKMF	5G ProSe Key Management Function
5G ProSe	5G Proximity based Services
RPAUID	Restricted ProSe Application User ID
PDUID	ProSe Discovery UE ID
UP-PRUK	User Plane ProSe Remote User Key

## 4 Overview

The 5G ProSe Key Management Function (5G PKMF) is the logical function handling network related actions required for the key management and the security material for discovery of a 5G ProSe UE-to-Network Relay by a 5G ProSe Remote UE; and for establishing a secure PC5 communication link between a 5G ProSe Remote UE and 5G ProSe UE-to-Network Relay (see 3GPP TS 33.503 [4]).

Figure 4-1 provides the reference model (in service based interface representation and in reference point representation), with focus on the 5G PKMF:




Figure 4-1: Reference model – 5G PKMF

**Editor's note:** The reference point between PKMF and SMF will be aligned with Stage 2.

The functionalities supported by the 5G PKMF are listed in clause 4.2.1.2 of 3GPP TS 33.503 [4].

## 5 Services offered by the 5G PKMF

### 5.1 Introduction

The table 5.1-1 shows the PKMF Services and PKMF Service Operations:

**Table 5.1-1: List of 5G PKMF Services**

Service Name	Service Operations	Operation Semantics	Example Consumer(s)
Npkmf_PKMFKeyRequest	ProseKey	Request/Response	PKMF
Npkmf_ResolveRemoteUserId	Retrieve	Request/Response	SMF, 5G PKMF

Table 5.1-2 summarizes the corresponding APIs defined for this specification.

**Table 5.1-2: API Descriptions**

Service Name	Clause	Description	OpenAPI Specification File	apiName	Annex
Npkmf_PKMFKeyRequest	6.1	PKMF Key Request Service	TS29559_Npkmf_PKMFKeyRequest.yaml	npkmf-keyrequest	A.2
Npkmf_ResolveRemoteUserId	6.2	PKMF Resolve Remote User ID Service	TS29559_Npkmf_UserId.yaml	npkmf-userid	A.3

## 5.2 Npkmf\_PKMFKeyRequest Service

### 5.2.1 Service Description

This service enables an NF (i.e. another PKMF in another PLMN) to request information related to 5G ProSe keying. The following are the key functionalities of this NF service.

- Provide 5G ProSe related keying material

### 5.2.2 Service Operations

#### 5.2.2.1 Introduction

#### 5.2.2.2 ProseKey


##### 5.2.2.2.1 General

The ProseKey service operation is invoked by a NF Service Consumer, i.e. another PKMF in another PLMN, towards the PKMF to retrieve the keying material related to 5G ProSe.

The ProseKey service operation is used during the following procedure:

- PC5 security establishment for 5G ProSe UE-to-Network relay communication over User Plane (see 3GPP TS 33.503 [4], clause 6.3.3.2.2)

The NF Service Consumer (i.e. another PKMF in another PLMN) shall retrieve the 5G ProSe related keying material by invoking the "request" custom method on the resource URI of "Prose Keys Collection" resource, see clause 6.1.3.2.4. See also Figure 5.2.2.2.1-1.



**Figure 5.2.2.2.1-1 ProseKey service operation**

1. The NF Service Consumer shall send a HTTP POST request to invoke "request" custom method. The payload of the request shall be an object of "ProseKeyReqData" data type. The payload shall include the Relay Service Code, the KNRP freshness parameter 1, and either the SUCI of the 5G ProSe Remote UE or the UP-PRUK ID.
- 2a. On success, the PKMF shall respond with the status code "200 OK". The payload of the response shall be an object of "ProseKeyRspData" data type. The payload shall include the KNRP, the KNRP freshness parameter 2 and optionally the GPI.
- 2b. On failure or redirection, one of the HTTP status codes listed in table 6.1.3.2.4.2.2-2 shall be returned. For a 4xx/5xx response, the message body shall contain a ProblemDetails structure with the "cause" attribute set to one of the application errors listed in table 6.1.3.2.4.2.2-2.
3. [conditional] If synchronization failed when UE processes the authentication challenge in the GPI and a subsequent Key Request is sent for resynchronization, the NF Service Consumer shall send a HTTP POST request to invoke "request" custom method. The payload of the request shall be an object of "ProseKeyReqData" data type. The payload shall include the Relay Service Code, the KNRP freshness parameter 1, the information for resynchronization (RAND and AUTS).
- 4a. On success, the PKMF shall respond with the status code "200 OK". The payload of the response shall be an object of "ProseKeyRspData" data type. The payload shall include the KNRP, the KNRP freshness parameter 2 and the GPI.
- 4b. On failure or redirection, one of the HTTP status codes listed in table 6.1.3.2.4.2.2-2 shall be returned. For a 4xx/5xx response, the message body shall contain a ProblemDetails structure with the "cause" attribute set to one of the application errors listed in table 6.1.3.2.4.2.2-2.

## 5.3 Npkmf\_ResolveRemoteUserId Service

### 5.3.1 Service Description

The Npkmf\_ResolveRemoteUserId service enables a NF to request the PKMF to resolve Remote User ID (i.e., UP-PRUK ID) to SUPI.

## 5.3.2 Service Operations

### 5.3.2.1 Introduction

The service operation defined for the Npkmf\_ResolveRemoteUserId service is as follows:

- Retrieve: It allows a consumer NF to get an user's SUPI from Remote User ID.


### 5.3.2.2 Retrieve

#### 5.3.2.2.1 General

The Retrieve service operation is used during the following procedure:

- PC5 security establishment for 5G ProSe UE-to-Network relay communication over User Plane (see 3GPP TS 33.503 [4], clause 6.3.3.2.2)

The NF Service Consumer (e.g., SMF, PKMF) shall request the PKMF to get the SUPI of a 5G ProSe Remote UE as shown in Figure 5.3.2.2.1-1



**Figure 5.3.2.2.1-1: Requesting the SUPI of a ProSe Remote UE**

1. The NF service consumer (e.g., SMF, PKMF) sends a POST request to the resource representing the resolve-id custom operation. The request body shall contain the UP-PRUK ID.
- 2a. On success, the PKMF responds with "200 OK" with the message body containing the corresponding SUPI.
- 2b. If there is no valid data, HTTP status code "404 Not Found" shall be returned including additional error information in the response body (in the "ProblemDetails" element).

On failure, the appropriate HTTP status code indicating the error shall be returned and appropriate additional error information should be returned in the POST response body.

---

## 6 API Definitions

### 6.1 Npkmf\_PKMFKeyRequest Service API

#### 6.1.1 Introduction

The Npkmf\_PKMFKeyRequest shall use the Npkmf\_PKMFKeyRequest API.

The API URI of the Npkmf\_PKMFKeyRequest API shall be:

**{apiRoot}/<apiName>/<apiVersion>**

The request URIs used in HTTP requests from the NF service consumer towards the NF service producer shall have the Resource URI structure defined in clause 4.4.1 of 3GPP TS 29.501 [6], i.e.:

**{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>**

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [6].
- The <apiName> shall be "npkmf-keyrequest".
- The <apiVersion> shall be "v1".
- The <apiSpecificResourceUriPart> shall be set as described in clause 6.1.3.

## 6.1.2 Usage of HTTP

### 6.1.2.1 General

HTTP/2, IETF RFC 7540 [8], shall be used as specified in clause 5 of 3GPP TS 29.500 [5].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [5].

The OpenAPI [7] specification of HTTP messages and content bodies for the Npkmf\_PKMFKeyRequest API is contained in Annex A.

### 6.1.2.2 HTTP standard headers

#### 6.1.2.2.1 General

See clause 5.2.2 of 3GPP TS 29.500 [5] for the usage of HTTP standard headers.

#### 6.1.2.2.2 Content type

JSON, IETF RFC 8259 [9], shall be used as content type of the HTTP bodies specified in the present specification as specified in clause 5.4 of 3GPP TS 29.500 [5]. The use of the JSON format shall be signalled by the content type "application/json".

"Problem Details" JSON object shall be used to indicate additional details of the error in a HTTP response body and shall be signalled by the content type "application/problem+json", as defined in IETF RFC 7807 [10].

### 6.1.2.3 HTTP custom headers


The mandatory HTTP custom header fields specified in clause 5.2.3.2 of 3GPP TS 29.500 [5] shall be applicable, and the optional HTTP custom header fields specified in clause 5.2.3.3 of 3GPP TS 29.500 [5] may be supported.

## 6.1.3 Resources

### 6.1.3.1 Overview

This clause describes the structure for the Resource URIs and the resources and methods used for the service.

Figure 6.1.3.1-1 describes the resource URI structure of the Npkmf\_PKMFKeyRequest API.



**Figure 6.1.3.1-1: Resource URI structure of the Npkmf\_PKMFKeyRequest API**

Table 6.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 6.1.3.1-1: Resources and methods overview**

Resource name	Resource URI	HTTP method or custom operation	Description
ProSe Keys Collection	/prose-keys	request (POST)	ProseKey service operation

## 6.1.3.2 Resource: ProSe Keys Collection

### 6.1.3.2.1 Description

This resource represents the collection of the ProSe Keys managed by the PKMF.

This resource is modelled with the Collection resource archetype (see clause C.2 of 3GPP TS 29.501 [5]).

### 6.1.3.2.2 Resource Definition

Resource URI: {apiRoot}/<apiName>/<apiVersion>/prose-keys

This resource shall support the resource URI variables defined in table 6.1.3.2.2-1.

**Table 6.1.3.2.2-1: Resource URI variables for this resource**

Name	Data type	Definition
apiRoot	string	See clause 6.1.1

### 6.1.3.2.3 Resource Standard Methods

There is no standard method supported by the resource.

## 6.1.3.2.4 Resource Custom Operations

## 6.1.3.2.4.1 Overview

**Table 6.1.3.2.4.1-1: Custom operations**

Operation name	Custom operation URI	Mapped HTTP method	Description
request	{resourceUri}/request	POST	ProseKey service operation

## 6.1.3.2.4.2 Operation: request

## 6.1.3.2.4.2.1 Description

This custom operation requests the keying material related to 5G ProSe in the PKMF.

## 6.1.3.2.4.2.2 Operation Definition

This operation shall support the request data structures specified in table 6.1.3.2.4.2.2-1 and the response data structure and response codes specified in table 6.1.3.2.4.2.2-2.

**Table 6.1.3.2.4.2.2-1: Data structures supported by the POST Request Body on this resource**

Data type	P	Cardinality	Description
ProseKeyReqData	M	1	Representation of the input to request the keying material.

**Table 6.1.3.2.4.2.2-2: Data structures supported by the POST Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
ProseKeyRespData	M	1	200 OK	Representation of the successfully requested keying material.
RedirectResponse	O	0..1	307 Temporary Redirect	Temporary redirection. The response shall include a Location header field containing a different URI, or the same URI if a request is redirected to the same target resource via a different SCP. In the former case, the URI shall be an alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. (NOTE 2)
RedirectResponse	O	0..1	308 Permanent Redirect	Permanent redirection. The response shall include a Location header field containing a different URI, or the same URI if a request is redirected to the same target resource via a different SCP. In the former case, the URI shall be an alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. (NOTE 2)
ProblemDetails	O	0..1	403 Not Found	The "cause" attribute shall be set to one of the following application error: - UE_NOT_AUTHORIZED See table 6.1.7.3-1 for the description of these errors.
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute shall be set to one of the following application error: - UE_NOT_FOUND See table 6.1.7.3-1 for the description of these errors.
NOTE1: The mandatory HTTP error status code for the POST method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [5] also apply.				
NOTE 2: RedirectResponse may be inserted by an SCP, see clause 6.10.9.1 of 3GPP TS 29.500 [4].				

**Table 6.1.3.2.4.2.2-3: Headers supported by the 307 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	An alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. Or the same URI, if a request is redirected to the same target resource via a different SCP.
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target PKMF (service) instance ID towards which the request is redirected

**Table 6.1.3.2.4.2.2-4: Headers supported by the 308 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	An alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. Or the same URI, if a request is redirected to the same target resource via a different SCP.
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target PKMF (service) instance ID towards which the request is redirected

## 6.1.4 Custom Operations without associated resources

There is no custom operation without associated resources supported in Npkmf\_PKMFKeyRequest Service.

## 6.1.5 Notifications

There is no notification defined for Npkmf\_PKMFKeyRequest service.

## 6.1.6 Data Model

### 6.1.6.1 General

This clause specifies the application data model supported by the API.

Table 6.1.6.1-1 specifies the data types defined for the Npkmf\_PKMFKeyRequest service based interface protocol.

**Table 6.1.6.1-1: Npkmf\_PKMFKeyRequest specific Data Types**

Data type	Clause defined	Description	Applicability
ProseKeyReqData	6.1.6.2.2	Representation of the input to request the keying material.	
ProseKeyRspData	6.1.6.2.3	Representation of the successfully requested keying material.	
PrukId	6.1.6.3	User Plane Prose Remote User Key ID	
Knrp	6.1.6.3	Key for NR PC5	
KnrpFreshnessParameter1	6.1.6.3	K <sub>NRP</sub> Freshness Parameter 1	
KnrpFreshnessParameter2	6.1.6.3	K <sub>NRP</sub> Freshness Parameter 2	
Gpi	6.1.6.3	GBA Push Information	

Table 6.1.6.1-2 specifies data types re-used by the Npkmf\_PKMFKeyRequest service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Npkmf\_PKMFKeyRequest service based interface.



Table 6.1.6.1-2: Npkmf\_PKMFKeyRequest re-used Data Types

Data type	Reference	Comments	Applicability
RelayServiceCode	3GPP TS 29.571 [15]	Relay Service Code	
ResynchronizationInfo	3GPP TS 29.503 [17]	Resynchronization Information	
Suci	3GPP TS 29.509 [18]	String contains the SUCI	

## 6.1.6.2 Structured data types

### 6.1.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

### 6.1.6.2.2 Type: ProseKeyReqData

Table 6.1.6.2.2-1: Definition of type ProseKeyReqData

Attribute name	Data type	P	Cardinality	Description	Applicability
relayServCode	RelayServiceCode	M	1	This IE shall indicate the Relay Service Code from the 5G ProSe Remote UE.	
knrpFreshness1	KnrpFreshnessParameter1	M	1	This IE shall carry the $K_{NRP}$ Freshness Parameter 1 in the 5G ProSe Remote UE.	
resyncInfo	ResynchronizationInfo	C	0..1	This IE shall be present in service request for subsequent key request handling synchronization failure.  When present, this IE shall carry information (RAND, AUTS) from the 5G ProSe Remote UE related to the synchronization Failure.	
prukId	PrukId	C	0..1	This IE may be present in service request for initial key request.  When present, this IE shall indicate the UP-PRUK ID from the 5G ProSe Remote UE. (See NOTE)	
suci	Suci	C	0..1	This IE may be present in service request for initial key request.  When present, this IE shall carry the SUCI of the 5G ProSe Remote UE (See NOTE).	

NOTE: Either prukId IE or suci IE shall be present in service request for initial key request.

## 6.1.6.2.3 Type: ProseKeyRspData

**Table 6.1.6.2.3-1: Definition of type ProseKeyRspData**

Attribute name	Data type	P	Cardinality	Description	Applicability
knrp	Knrp	M	1	This IE shall carry the $K_{NR}$ derived by the PKMF.	
knrpFreshness2	KnrpFreshnessParameter2	M	1	This IE shall carry the $K_{NR}$ Freshness Parameter 2 generated by the PKMF.	
gpi	Gpi	C	0..1	This IE shall be present if GPI is generated or requested.  When present, this IE shall carry the GPI.	

## 6.1.6.3 Simple data types and enumerations

## 6.1.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

## 6.1.6.3.2 Simple data types

The simple data types defined in table 6.1.6.3.2-1 shall be supported.

Table 6.1.6.3.2-1: Simple data types

Type Name	Type Definition	Description	Applicability
PrukId	string	User Plane Prose Remote User Key ID  String type as defined in OpenAPI Specification [7], carrying the value of the "UP-PRUK ID" parameter via PC8 (with "xs:string" type in XML schema) as specified in clause 11.6.2.3 of 3GPP TS 24.554 [16].	
Knrp	string	Key for NR PC5  String type as defined in OpenAPI Specification [7], carrying the value of the "KNRP" parameter via PC8 (with "xs:hexBinary" type in XML schema) as specified in clause 11.6.2.25 of 3GPP TS 24.554 [16].	
KnrpFreshnessParameter1	string	KNRP Freshness Parameter 1  String type as defined in OpenAPI Specification [7], carrying the value of the "KNRP freshness parameter 1" parameter via PC8 (with "xs:hexBinary" type in XML schema) as specified in clause 11.6.2.22 of 3GPP TS 24.554 [16].	
KnrpFreshnessParameter2	string	KNRP Freshness Parameter 2  String type as defined in OpenAPI Specification [7], carrying the value of the "KNRP freshness parameter 2" parameter via PC8 (with "xs:hexBinary" type in XML schema) as specified in clause 11.6.2.26 of 3GPP TS 24.554 [16].	
Gpi	string	GBA Push Information  String type as defined in OpenAPI Specification [7], carrying the value of the "GPI" parameter via PC8 (with "xs:hexBinary" type in XML schema) as specified in clause 11.6.2.16 of 3GPP TS 24.554 [16].	

#### 6.1.6.4 Data types describing alternative data types or combinations of data types

There is no data type describing alternative data types or combinations of data types in Npkmf\_PKMFKeyRequest Service.

#### 6.1.6.5 Binary data

There is no binary data type in Npkmf\_PKMFKeyRequest Service.

### 6.1.7 Error Handling

#### 6.1.7.1 General

For the Npkmf\_PKMFKeyRequest API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [6]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [5] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [5].

In addition, the requirements in the following clauses are applicable for the Npkmf\_PKMFKeyRequest API.

### 6.1.7.2 Protocol Errors

Protocol errors handling shall be supported as specified in clause 5.2.7 of 3GPP TS 29.500 [5].

### 6.1.7.3 Application Errors

The application errors defined for the Npkmf\_PKMFKeyRequest service are listed in Table 6.1.7.3-1.

**Table 6.1.7.3-1: Application errors**

Application Error	HTTP status code	Description
UE_NOT_AUTHORIZED	403 Forbidden	The UE is not authorized for the requested service.
UE_NOT_FOUND	404 Not Found	The UE indicated by the SUCI or related to the UP-PRUK ID is not found in the PKMF.

### 6.1.8 Feature negotiation

The optional features in table 6.1.8-1 are defined for the Npkmf\_PKMFKeyRequest API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [5].

**Table 6.1.8-1: Supported Features**

Feature number	Feature Name	Description
N/A		

### 6.1.9 Security

As indicated in 3GPP TS 33.501 [11] and 3GPP TS 29.500 [5], the access to the Npkmf\_PKMFKeyRequest API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [12]), based on local configuration, using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [13]) plays the role of the authorization server.

If OAuth2 is used, an NF Service Consumer, prior to consuming services offered by the Npkmf\_PKMFKeyRequest API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [13], clause 5.4.2.2.

**NOTE:** When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Npkmf\_PKMFKeyRequest service.

The Npkmf\_PKMFKeyRequest API defines a single scope "npkmf-keyrequest" for OAuth2 authorization (as specified in 3GPP TS 33.501 [11]) for the entire service, and it does not define any additional scopes at resource or operation level.

### 6.1.10 HTTP redirection

An HTTP request may be redirected to a different 5G PKMF service instance, within the same 5G PKMF or a different 5G PKMF of an 5G PKMF set, e.g. when an 5G PKMF service instance is part of an 5G PKMF (service) set or when using indirect communications (see 3GPP TS 29.500 [5]).

An SCP that reselects a different 5G PKMF producer instance will return the NF Instance ID of the new 5G PKMF producer instance in the 3gpp-Sbi-Producer-Id header, as specified in clause 6.10.3.4 of 3GPP TS 29.500 [5].

If an 5G PKMF within an 5G PKMF set redirects a service request to a different 5G PKMF of the set using an 307 Temporary Redirect or 308 Permanent Redirect status code, the identity of the new 5G PKMF towards which the service request is redirected shall be indicated in the 3gpp-Sbi-Target-Nf-Id header of the 307 Temporary Redirect or 308 Permanent Redirect response as specified in clause 6.10.9.1 of 3GPP TS 29.500 [5].

## 6.2 Npkmf\_ResolveRemoteUserId Service API

### 6.2.1 Introduction

The Npkmf\_ResolveRemoteUserId service shall use the Npkmf\_ResolveRemoteUserId API.

The API URI of the Npkmf\_ResolveRemoteUserId API shall be:

**{apiRoot}/<apiName>/<apiVersion>**

The request URIs used in HTTP requests from the NF service consumer towards the NF service producer shall have the Resource URI structure defined in clause 4.4.1 of 3GPP TS 29.501 [6], i.e.:

**{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>**

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [6].
- The <apiName> shall be "npkmf-userid".
- The <apiVersion> shall be "v1".
- The <apiSpecificResourceUriPart> shall be set as described in clause 6.2.3.

### 6.2.2 Usage of HTTP

#### 6.2.2.1 General

HTTP/2, IETF RFC 7540 [8], shall be used as specified in clause 5 of 3GPP TS 29.500 [5].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [5].

The OpenAPI [7] specification of HTTP messages and content bodies for the Npkmf\_ResolveRemoteUserId API is contained in Annex A.3.

#### 6.2.2.2 HTTP standard headers

##### 6.2.2.2.1 General

See clause 5.2.2 of 3GPP TS 29.500 [5] for the usage of HTTP standard headers.

##### 6.2.2.2.2 Content type

JSON, IETF RFC 8259 [9], shall be used as content type of the HTTP bodies specified in the present specification as specified in clause 5.4 of 3GPP TS 29.500 [5]. The use of the JSON format shall be signalled by the content type "application/json".

"Problem Details" JSON object shall be used to indicate additional details of the error in a HTTP response body and shall be signalled by the content type "application/problem+json", as defined in IETF RFC 7807 [10].

#### 6.2.2.3 HTTP custom headers


The mandatory HTTP custom header fields specified in clause 5.2.3.2 of 3GPP TS 29.500 [5] shall be supported, and the optional HTTP custom header fields specified in clause 5.2.3.3 of 3GPP TS 29.500 [5] may be supported.

## 6.2.3 Resources

### 6.2.3.1 Overview

This clause describes the structure for the Resource URIs and the resources and methods used for the service.

Figure 6.2.3.1-1 depicts the resource URIs structure for the Npkmf\_ResolveRemoteUserId API.



**Figure 6.2.3.1-1: Resource URI structure of the Npkmf\_ResolveRemoteUserId API**

Table 6.2.3.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 6.2.3.1-1: Resources and methods overview**

Resource name	Resource URI	HTTP method or custom operation	Description

## 6.2.4 Custom Operations without associated resources

### 6.2.4.1 Overview

**Table 6.2.4.1-1: Custom operations without associated resources**

Custom operation URI	Mapped HTTP method	Description
resolve-id	POST	Resolve ProSe Remote User ID (i.e., UP-PRUK ID) to SUPI

### 6.2.4.2 Operation: resolve-id

#### 6.2.4.2.1 Description

This custom operation is used by the NF service consumer (e.g., SMF, PKMF) to request to resolve ProSe Remote User ID (i.e., UP-PRUK) to SUPI.

The URI of this custom operation is: {apiRoot}/npkmf-userid/<apiVersion>/resolve-id

#### 6.2.4.2.2 Operation Definition

This operation shall support the response data structures and response codes specified in tables 6.2.4.2.2-1 and 6.2.4.2.2-2.

**Table 6.2.4.2.2-1: Data structures supported by the POST Request Body on this resource**

Data type	P	Cardinality	Description
ResolveRequest	M	1	Resolve Request data.

**Table 6.2.4.2.2-2: Data structures supported by the POST Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
ResolveResponse	M	1	200 OK	Upon success, the response data contain the SUPI of the ProSe Remote UE.
RedirectResponse	O	0..1	307 Temporary Redirect	Temporary redirection. (NOTE 2)
RedirectResponse	O	0..1	308 Permanent Redirect	Permanent redirection. (NOTE 2)
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute may be used to indicate one of the following application errors: - USER_NOT_FOUND See table 6.2.7.3-1 for the description of these errors.

NOTE 1: The mandatory HTTP error status code for the POST method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [5] also apply.

NOTE 2: RedirectResponse may be inserted by an SCP, see clause 6.10.9.1 of 3GPP TS 29.500 [5].

**Table 6.2.4.2.2-3: Headers supported by the 307 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	An alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. For the case, when a request is redirected to the same target resource via a different SCP, see clause 6.10.9.1 in 3GPP TS 29.500 [5].
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target PKMF (service) instance ID towards which the request is redirected

**Table 6.2.4.2.2-4: Headers supported by the 308 Response Code on this resource**

Name	Data type	P	Cardinality	Description
Location	string	M	1	An alternative URI of the resource located on an alternative service instance within the same PKMF or PKMF (service) set. For the case, when a request is redirected to the same target resource via a different SCP, see clause 6.10.9.1 in 3GPP TS 29.500 [5].
3gpp-Sbi-Target-Nf-Id	string	O	0..1	Identifier of the target PKMF (service) instance ID towards which the request is redirected

## 6.2.5 Notifications

There is no notification defined for Npkmf\_ResolveRemoteUserId service.

## 6.2.6 Data Model

### 6.2.6.1 General

This clause specifies the application data model supported by the API.

Table 6.2.6.1-1 specifies the data types defined for the Npkmf\_ResolveRemoteUserId service based interface protocol.

**Table 6.2.6.1-1: Npkmf\_ResolveRemoteUserId specific Data Types**

Data type	Clause defined	Description	Applicability
ResolveRequest	6.2.6.2.2	Request Data	
ResolveResponse	6.2.6.2.3	Response Data	

Table 6.2.6.1-2 specifies data types re-used by the Npkmf\_ResolveRemoteUserId service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Npkmf\_ResolveRemoteUserId service based interface.

**Table 6.2.6.1-2: Npkmf\_ResolveRemoteUserId re-used Data Types**

Data type	Reference	Comments	Applicability
PrukId	3GPP TS 29.559	See clause 6.1.6.3.2	
PlmnId	3GPP TS 29.571 [15]	PLMN ID	
Supi	3GPP TS 29.571 [15]	Subscription Permanent Identifier	

## 6.2.6.2 Structured data types

### 6.2.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

#### 6.2.6.2.2 Type: ResolveRequest

**Table 6.2.6.2.2-1: Definition of type ResolveRequest**

Attribute name	Data type	P	Cardinality	Description	Applicability
upPrukId	PrukId	M	1	UP-PRUK ID of the ProSe Remote UE	
plmnId	PlmnId	O	0..1	HPLMN ID of the 5G ProSe Remote UE	

#### 6.2.6.2.3 Type: ResolveResponse

**Table 6.2.6.2.2-1: Definition of type ResolveResponse**

Attribute name	Data type	P	Cardinality	Description	Applicability
supi	Supi	M	1	The SUPI of the UE	

## 6.2.6.3 Simple data types and enumerations

There are no simple data types and enumerations defined in Npkmf\_ResolveRemoteUserId Service.

## 6.2.6.4 Data types describing alternative data types or combinations of data types

There is no data type describing alternative data types or combinations of data types in Npkmf\_ResolveRemoteUserId Service.

## 6.2.6.5 Binary data

There is no binary data type in Npkmf\_ResolveRemoteUserId Service.



## 6.2.7 Error Handling

### 6.2.7.1 General

For the Npkmf\_ResolveRemoteUserId API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [6]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [5] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [5].

In addition, the requirements in the following clauses are applicable for the Npkmf\_ResolveRemoteUserId API.

### 6.2.7.2 Protocol Errors

No specific procedures for the Npkmf\_ResolveRemoteUserId service are specified.

### 6.2.7.3 Application Errors

The application errors defined for the Npkmf\_ResolveRemoteUserId service are listed in Table 6.2.7.3-1.

**Table 6.2.7.3-1: Application errors**

Application Error	HTTP status code	Description
USER_NOT_FOUND	404 Not Found	The provided subscriber identifier is not found.

## 6.2.8 Feature negotiation

The optional features in table 6.2.8-1 are defined for the Npkmf\_ResolveRemoteUserId API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [5].

**Table 6.2.8-1: Supported Features**

Feature number	Feature Name	Description

## 6.2.9 Security

As indicated in 3GPP TS 33.501 [8] and 3GPP TS 29.500 [5], the access to the Npkmf\_ResolveRemoteUserId API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [9]), based on local configuration, using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [13]) plays the role of the authorization server.

If OAuth2 is used, an NF Service Consumer, prior to consuming services offered by the Npkmf\_ResolveRemoteUserId API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [13], clause 5.4.2.2.

**NOTE:** When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Npkmf\_ResolveRemoteUserId service.

The Npkmf\_ResolveRemoteUserId API defines a single scope "npkmf-userid" for the entire service, and it does not define any additional scopes at resource or operation level.

## 6.2.10 HTTP redirection

An HTTP request may be redirected to a different 5G PKMF service instance, within the same 5G PKMF or a different 5G PKMF of an 5G PKMF set, e.g. when an 5G PKMF service instance is part of an 5G PKMF (service) set or when using indirect communications (see 3GPP TS 29.500 [5]).

An SCP that reselects a different 5G PKMF producer instance will return the NF Instance ID of the new 5G PKMF producer instance in the 3gpp-Sbi-Producer-Id header, as specified in clause 6.10.3.4 of 3GPP TS 29.500 [5].

If an 5G PKMF within an 5G PKMF set redirects a service request to a different 5G PKMF of the set using an 307 Temporary Redirect or 308 Permanent Redirect status code, the identity of the new 5G PKMF towards which the service request is redirected shall be indicated in the 3gpp-Sbi-Target-Nf-Id header of the 307 Temporary Redirect or 308 Permanent Redirect response as specified in clause 6.10.9.1 of 3GPP TS 29.500 [5].

# Annex A (normative): OpenAPI specification

## A.1 General

This Annex specifies the formal definition of the API(s) defined in the present specification. It consists of OpenAPI 3.0.0 specifications in YAML format.

This Annex takes precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

NOTE 1: The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on a Git-based repository that uses the GitLab software version control system (see clause 5.3.1 of 3GPP TS 29.501 [6] and clause 5B 3GPP TR 21.900 [14]).

## A.2 Npkmf\_PKMFKeyRequest API

```
openapi: 3.0.0
```

```
info:
```

```
  title: Npkmf_PKMFKeyRequest
  version: 1.0.1
  description: |
    PKMF KeyRequest Service.
    © 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.
```

```
externalDocs:
```

```
  description: 3GPP TS 29.559 V17.2.0; 5G System; 5G ProSe Key Management Services; Stage 3.
  url: https://www.3gpp.org/ftp/Specs/archive/29_series/29.559/
```

```
servers:
```

```
- url: '{apiRoot}/npkmf-keyrequest/v1'
  variables:
    apiRoot:
      default: https://example.com
      description: apiRoot as defined in clause 4.4 of 3GPP TS 29.501
```

```
security:
```

```
- {}
- oAuth2ClientCredentials:
  - npkmf-keyrequest
```

```
paths:
```

```
  /prose-keys/request:
    post:
      summary: Request Keying Materials for 5G ProSe
      operationId: ProseKey
      tags:
        - ProSe Keys Collection (Collection)
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/ProseKeyReqData'
      responses:
        '200':
          description: Success
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/ProseKeyRspData'
```

```

'307':
  $ref: 'TS29571_CommonData.yaml#/components/responses/307'
'308':
  $ref: 'TS29571_CommonData.yaml#/components/responses/308'
'400':
  $ref: 'TS29571_CommonData.yaml#/components/responses/400'
'401':
  $ref: 'TS29571_CommonData.yaml#/components/responses/401'
'403':
  $ref: 'TS29571_CommonData.yaml#/components/responses/403'
'404':
  $ref: 'TS29571_CommonData.yaml#/components/responses/404'
'411':
  $ref: 'TS29571_CommonData.yaml#/components/responses/411'
'413':
  $ref: 'TS29571_CommonData.yaml#/components/responses/413'
'415':
  $ref: 'TS29571_CommonData.yaml#/components/responses/415'
'429':
  $ref: 'TS29571_CommonData.yaml#/components/responses/429'
'500':
  $ref: 'TS29571_CommonData.yaml#/components/responses/500'
'502':
  $ref: 'TS29571_CommonData.yaml#/components/responses/502'
'503':
  $ref: 'TS29571_CommonData.yaml#/components/responses/503'
default:
  $ref: 'TS29571_CommonData.yaml#/components/responses/default'

```

```

components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            npkmf-keyrequest: Access to the Npkmf_PKMFKeyRequest API

```

```
schemas:
```

```

#
# Structured Data Types
#
ProseKeyReqData:
  description: Representation of the input to request the keying material.
  type: object
  properties:
    relayServCode:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/RelayServiceCode'
    knrpFreshness1:
      $ref: '#/components/schemas/KnrpFreshnessParameter1'
    resyncInfo:
      $ref: 'TS29503_Nudm_UEAU.yaml#/components/schemas/ResynchronizationInfo'
    prukId:
      $ref: '#/components/schemas/PrukId'
    suci:
      $ref: 'TS29509_Nausf_UEAuthentication.yaml#/components/schemas/Suci'
  required:
    - relayServCode
    - knrpFreshness1

ProseKeyRspData:
  description: Representation of the successfully requested keying material.
  type: object
  properties:
    knrp:
      $ref: '#/components/schemas/Knrp'
    knrpFreshness2:
      $ref: '#/components/schemas/KnrpFreshnessParameter2'
    gpi:
      $ref: '#/components/schemas/Gpi'
  required:
    - knrp
    - knrpFreshness2

#
# Simple Data Types
#

```

```

PrukId:
  description: User Plane Prose Remote User Key ID
  type: string

Knrp:
  description: Key for NR PC5
  type: string

KnrpFreshnessParameter1:
  description: KNRP Freshness Parameter 1
  type: string

KnrpFreshnessParameter2:
  description: KNRP Freshness Parameter 2
  type: string

Gpi:
  description: GBA Pushing Information
  type: string

```

```

#
# Enumeration Data Types
#

```

---

## A.3 Npkmf\_ResolveRemoteUserId API

openapi: 3.0.0

```

info:
  title: Npkmf_ResolveRemoteUserId
  version: 1.0.0
  description: |
    PKMF Resolve Remote User Id Service.
    © 2023, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.

externalDocs:
  description: 3GPP TS 29.559 V17.3.0; 5G System; 5G ProSe Anchor Services; Stage 3.
  url: https://www.3gpp.org/ftp/Specs/archive/29_series/29.559/

servers:
  - url: '{apiRoot}/npkmf-userid/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in clause 4.4 of 3GPP TS 29.501

security:
  - {}
  - oAuth2ClientCredentials:
    - npkmf-userid

paths:
  /resolve-id:
    post:
      summary: Retrieve the SUPI of the ProSe Remote UE
      operationId: RetrieveSUPI
      tags:
        - SUPI Retrieval
      requestBody:
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/ResolveRequest'
            required: true
      responses:
        '200':
          description: Expected response to a valid request
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/ResolveResponse'
        '307':
          $ref: 'TS29571_CommonData.yaml#/components/responses/307'
        '308':

```

```

    $ref: 'TS29571_CommonData.yaml#/components/responses/308'
  '400':
    $ref: 'TS29571_CommonData.yaml#/components/responses/400'
  '401':
    $ref: 'TS29571_CommonData.yaml#/components/responses/401'
  '403':
    $ref: 'TS29571_CommonData.yaml#/components/responses/403'
  '404':
    $ref: 'TS29571_CommonData.yaml#/components/responses/404'
  '411':
    $ref: 'TS29571_CommonData.yaml#/components/responses/411'
  '413':
    $ref: 'TS29571_CommonData.yaml#/components/responses/413'
  '415':
    $ref: 'TS29571_CommonData.yaml#/components/responses/415'
  '429':
    $ref: 'TS29571_CommonData.yaml#/components/responses/429'
  '500':
    $ref: 'TS29571_CommonData.yaml#/components/responses/500'
  '502':
    $ref: 'TS29571_CommonData.yaml#/components/responses/502'
  '503':
    $ref: 'TS29571_CommonData.yaml#/components/responses/503'
  default:
    description: Unexpected error

```

```

components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            npkmf-userid: Access to the Npkmf_ResolveRemoteUserId API

```

```
schemas:
```

```

#
# Structured Data Types
#

```

```

ResolveRequest:
  description: Request Data
  type: object
  properties:
    upPrukId:
      $ref: 'TS29559_Npkmf_PKMFKeyRequest.yaml#/components/schemas/PrukId'
    plmnId:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'
  required:
    - upPrukId

```

```

ResolveResponse:
  description: Response Data
  type: object
  properties:
    supi:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
  required:
    - supi

```

```

#
# Simple Data Types
#

```

```

#
# Enumeration Data Types
#

```

## Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2022-04	C4#109-e	C4-222345				Implementation of pCRs agreed in CT4#109-e including C4-222355, C4-222356, C4-222023, C4-222024, C4-222025, C4-222026, C4-222027, C4-222028, C4-222029, C4-222031, C4-222409, C4-222410, C4-222411, C4-222412, C4-222413, C4-222414	0.1.0
2022-05	C4#110-e	C4-223454				Implementation of pCRs agreed in CT4#110-e including C4-223135, C4-223157, C4-223158, C4-223160, C4-223351, C4-223352, C4-223416, C4-223417	0.2.0
2022-06	CT#96	CP-221082				TS presented for information and approval	1.0.0
2022-06	CT#96	CP-221082				TS approved in CT#96	17.0.0
2022-09	CT#97e	CP-222035	0001	-	F	Alignment on the service name used with template	17.1.0
2022-12	CT#98e	CP-223054	0003	2	F	PRUK Name Alignment	17.2.0
2022-12	CT#98e	CP-223054	0004	-	F	Correct the server url and some table styles	17.2.0
2022-12	CT#98e	CP-223054	0006	-	F	Update on the procedure title	17.2.0
2022-12	CT#98e	CP-223066	0007	-	F	29.559 Rel-17 API version and External doc update	17.2.0
2023-06	CT#100	CP-231202	0010	3	F	Add service Npkmf_ResolveRemoteUserId	17.3.0

---

# History

<b>Document history</b>		
V17.0.0	July 2022	Publication
V17.1.0	October 2022	Publication
V17.2.0	January 2023	Publication
V17.3.0	July 2023	Publication