

ETSI TS 132 509 V13.0.0 (2016-02)



**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Data formats for multi-vendor plug and play
eNode B connection to the network
(3GPP TS 32.509 version 13.0.0 Release 13)**



Reference

RTS/TSGS-0532509vd00

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Data formats for Multi-Vendor Plug and Connect (MvPnC).....	6
4.1 MvPnC client identification in DHCP requests.....	6
4.2 MvPnC entities information in DHCP replies	7
4.2.1 General.....	7
4.2.2 Certification Authority (CA/RA) server	8
4.2.3 Security Gateway (SeGW).....	8
4.2.4 Element Manager (EM)	10
4.3 MvPnC entities Fully Qualified Domain Names (FQDN)	11
4.3.1 General.....	11
4.3.2 Certification Authority (CA/RA) server	11
4.3.3 Security Gateway (SeGW).....	12
4.3.4 Element Manager (EM)	12
Annex A (informative): Change history	13
History	14

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; as identified below:

TS 32.501: "Self-configuration of network elements; Concepts and requirements".

TS 32.508: "Procedure flows for multi-vendor plug and play eNB connection to the network".

TS 32.509: "Data formats for multi-vendor plug and play eNB connection to the network".

1 Scope

The present document describes the data formats used between network entities involved in the multi-vendor plug and play eNB connection to network.

These data formats are based on requirements and use cases specified in 3GPP TS 32.501 [4].

The procedure flows where these data exchanged are defined in 3GPP TS 32.508 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [3] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [4] 3GPP TS 32.501: "Telecommunication management; Self-configuration of network elements; Concepts and requirements".
- [5] 3GPP TS 32.508: "Telecommunications management; Procedure flows for multi-vendor plug and play eNB connection to the network".
- [6] 3GPP TS 23.003: "Numbering, addressing and identification".
- [7] IETF RFC 1035: "Domain Names - Implementation and Specification".
- [8] IETF RFC 2131: "Dynamic Host Configuration Protocol".
- [9] IETF RFC 2132: "DHCP Options and BOOTP Vendor Extensions".
- [10] IETF RFC 3396: "Encoding Long Options in the Dynamic Host Configuration Protocol (DHCPv4)".
- [11] 3GPP TS 33.310: "Network Domain Security (NDS); Authentication Framework (AF)".
- [12] IETF RFC 6712: "Internet X.509 Public Key Infrastructure -- HTTP Transfer for the Certificate Management Protocol (CMP)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 32.501 [4] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1] and in TS 32.501 [4].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 32.501 [4] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1] and in TS 32.501 [4].

4 Data formats for Multi-Vendor Plug and Connect (MvPnC)

4.1 MvPnC client identification in DHCP requests

The eNB performing the Initial IP Autoconfiguration procedure specified in clause 5.2 of 3GPP TS 32.508 [5] identifies itself as MvPnC compatible DHCP client by using the Vendor Class Identifier DHCP option specified in clause 9.13 of RFC 2132 [9] in the following way:

- DHCP option code 60;
- Length 5 bytes;
- Vendor class identifier "MvPnC".

The use of Vendor Class Identifier DHCP option with specific value for MvPnC is illustrated in table 4.1.1.

Table 4.1.1: Use of Vendor Class Identifier

Code	Length	Vendor Class Identifier				
60	5	M	v	P	n	C

4.2 MvPnC entities information in DHCP replies

4.2.1 General

The information that eNB receives from the DHCP server while performing the Initial IP Autoconfiguration procedure specified in clause 5.2 of 3GPP TS 32.508 [5] may be classified in two categories: basic IP configuration and MvPnC specific configuration.

The basic IP configuration information is documented in RFC 2131 [8] and RFC 2132 [9] and may include the following:

- IP address ("yiaddr" field in [8]);
- Subnet Mask (option 1 in [9]);
- Router(s) (option 3 in [9]);
- IP address(es) of the DNS server(s) (option 6 in [9]);
- Domain Name (option 15 in [9]).

The MvPnC specific configuration information is described in detail in clauses 4.2.2, 4.2.3 and 4.2.4.

The DHCP option "Vendor Specific Information" specified in the clause 8.4 of RFC 2132 [9] is used as an opaque container carrying the MvPnC specific configuration from the DHCP server to the eNB performing the MvPnC procedure. The multiple pieces of MvPnC specific configuration within the Vendor Specific Information container are encoded as a sequence of code/length/value fields (also known as "Encapsulated vendor-specific options" specified in clause 8.4 of RFC 2132 [9]).

The use of Vendor Specific Information DHCP option container with encapsulated vendor-specific options encoding is illustrated in table 4.2.1.1.

Table 4.2.1.1: Use of the Vendor Specific Information

Code	Length 1-255	Vendor Specific Information						
		Configuration attribute 1			Configuration attribute 2			...
43	n	Type1	Length1	Data	Type2	Length2	Data	...
octet	octet	octet	octet	n octets	octet	octet	n octets	...

The content of the configuration attributes (specific type code value, valid length and data type) carried in the format illustrated in table 4.2.1.1 is specified in the clauses 4.2.2, 4.2.3 and 4.2.4 of the present document.

If the size of MvPnC configuration data contained in "Vendor Specific Information" option 43 is greater than 255 bytes, the RFC 3396 [10] encoding is used.

To avoid ambiguity in the interpretation of string MvPnC configuration attributes, the ASCII character encoding shall be used.

Standard network byte order shall be used with appropriate conversion function at the eNB (matching the local little-endian / big-endian byte order).

Some MvPnC configuration attributes may be missing (e.g. the SeGW FQDN attribute may be not present if the SeGW IP address is present) or just have zero length (type octet followed by length octet with value zero and no data octets).

The qualifiers identifying which attributes are mandatory, Optional (O), Conditional Mandatory (CM) or Conditional Optional (CO) and corresponding conditions are defined in the clauses 4.2.2, 4.2.3 and 4.2.4.

The order of MvPnC configuration attributes is not important (e.g. attribute of type "1" may appear after the attribute of type "5").

4.2.2 Certification Authority (CA/RA) server

This clause specifies the information about Certification Authority server that eNB receives from DHCP server in Initial IP Autoconfiguration procedure specified in clause 5.2 of 3GPP TS 32.508 [5] and uses for Certificate Enrolment procedure.

Table 4.2.2.1: CA/RA configuration attributes

Attribute name	Attribute tag (code)	Attribute length	Attribute qualifier	Attribute description
IP address of the CA/RA	01	Variable	CO	IP address of the CMP server. An IPv4 IP address is usually represented as 4 octets.
FQDN of the CA/RA	02	Variable	CO	ASCII string representing the Fully Qualified Domain Name of the CMP server. In case the FQDN is used, the IP address of the DNS server needs to be made available to the eNB before certificate enrolment.
Port number of the CA/RA	03	Variable	M	Integer representing the port number used by CMP server. The port for HTTP/HTTPSs transfer of CMP messages is not explicitly given in RFC 6712 [12], therefore this parameter is required. The port number is usually represented as 2 octets.
Path to the CA/RA directory	04	Variable	M	ASCII string representing the path to the CMP server directory. A CMP server may be located in an arbitrary path other than root.
Subject name of the CA/RA	05	Variable	M	ASCII string representing the subject name of the CA/RA. The use is described in 3GPP TS 33.310 [11] clause 9.5.3.
Protocol indication	06	Variable	CM	ASCII string representing the protocol (HTTP or HTTPS) to be used for certificate enrolment. The use is described in 3GPP TS 33.310 [11] clause 9.6.

Table 4.2.2.2: Attribute constraints

Name	Definition
IP address CO qualifier	The IP address is optional if the FQDN is present
FQDN CO qualifier	The FQDN is optional if the IP address is present
Protocol indication CM qualifier	The protocol indication is mandatory if HTTPS protocol is used

4.2.3 Security Gateway (SeGW)

This clause specifies the information about Security Gateway server that eNB receives from DHCP server in Initial IP Autoconfiguration procedure specified in clause 5.2 of 3GPP TS 32.508 [5] and uses for Establishing Secure Connection procedure.

Table 4.2.3.1: Security Gateway configuration attributes

Attribute name	Attribute tag (code)	Attribute length	Attribute qualifier	Attribute description
IP address of the SeGW	07	Variable	CO	IP address of the Security Gateway. An IPv4 IP address is usually represented as 4 octets.
FQDN of the SeGW	08	Variable	CO	ASCII string representing the Fully Qualified Domain Name of the Security Gateway. In case the FQDN is used, the IP address of the DNS server needs to be made available to the eNB before establishing secure connection.

Table 4.2.3.2: Attribute constraints

Name	Definition
IP address CO qualifier	The IP address is optional if the FQDN is present
FQDN CO qualifier	The FQDN is optional if the IP address is present

4.2.4 Element Manager (EM)

This clause specifies the information about Element Manager that eNB receives either from DHCP server in Initial IP Autoconfiguration procedure specified in clause 5.2 of 3GPP TS 32.508 [5] or from secure DHCP server in Establishing Connection to Element Manager procedure specified in clause 5.5 of 3GPP TS 32.508 [5] and uses for Establishing Connection to Element Manager procedure.

Table 4.2.4.1: Element Manager configuration attributes

Attribute name	Attribute tag (code)	Attribute length	Attribute qualifier	Attribute description
IP address of the EM	09	Variable	CO	IP address of the Element Manager. An IPv4 IP address is usually represented as 4 octets.
FQDN of the EM	10	Variable	CO	ASCII string representing the Fully Qualified Domain Name of the Element Manager. In case the FQDN is used, the IP address of the DNS server needs to be made available to the eNB before establishing connection to the Element Manager.

Table 4.2.4.2: Attribute constraints

Name	Definition
IP address CO qualifier	The IP address is optional if the FQDN is present
FQDN CO qualifier	The FQDN is optional if the IP address is present

4.3 MvPnC entities Fully Qualified Domain Names (FQDN)

4.3.1 General

This clause describes the Fully Qualified Domain Names (FQDNs) used in Multi Vendor Plug and Connect (MvPnC) procedures.

The FQDNs used in MvPnC are in the form of a domain name as specified in IETF RFC 1035 [7].

The sub-domains used in MvPnC are allocated within the ".3gppnetwork.org" domain.

The GSM Association is in charge of allocating the new sub-domains of ".3gppnetwork.org" domain name.

The procedure specified in Annex E of 3GPP TS 23.003 [6] is used for the sub-domain allocation.

The FQDNs used in MvPnC follow the general encoding rules specified in clause 19.4.2.1 of 3GPP TS 23.003 [6].

The format of FQDNs used in MvPnC follows the "<vendor ID>.<system>.<OAM realm>" pattern.

NOTE: Where "<vendor ID>.<system>.oam" represents the <service_id> shown in the first row of table E.1 of 3GPP TS 23.003 [6].

The <vendor ID> label is optional and is required in the operator deployments where multiple instances of a particular network entity type are not provided by the same vendor. If present, the <vendor ID> label is in the form "vendor<ViD>", where <ViD> field corresponds to the ID of the vendor. The specific deployment scenario (e.g. one network entity instance per vendor or one network entity instance for all vendors) is not known to the eNB when it connects to the network. Therefore, it should first try to resolve the FQDN containing the <vendor ID> label and if it fails, try to resolve the FQDN without the <vendor ID> label.

The details of the <system> label are described in clauses 4.3.2, 4.3.3 and 4.3.4.

The <OAM realm> label is the operator's OAM realm domain name in the form of "oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org", where "<MNC>" and "<MCC>" fields correspond to the MNC and MCC of the operator's PLMN. Both the "<MNC>" and "<MCC>" fields are 3 digits long. If the MNC of the PLMN is 2 digits, then a zero shall be added at the beginning.

An example of an OAM realm domain name is:

MCC = 123;

MNC = 45;

Which gives the OAM realm domain name: "oam.mnc045.mcc123.3gppnetwork.org".

4.3.2 Certification Authority (CA/RA) server

The Certification Authority server (CA/RA) FQDN is derived as follows. The "cara" <system> label is added in front of the operator's OAM realm domain name:

cara.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org

If particular operator deployment scenario has multiple CA/RA servers (one per vendor), the <vendor ID> label is added in front of the "cara" label:

vendor<ViD>.cara.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org

An example of a CA/RA FQDN is:

MCC = 123;

MNC = 45;

ViD = abcd;

Which gives the CA/RA FQDN: "cara.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.cara.mnc045.mcc123.3gppnetwork.org".

4.3.3 Security Gateway (SeGW)

The Security Gateway (SeGW) FQDN is derived as follows.

The "segw" <system> label is added in front of the operator's OAM realm domain name:

```
segw.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If particular operator deployment scenario has multiple Security Gateways (one per vendor), the <vendor ID> label is added in front of the "segw" label:

```
vendor<ViD>.segw.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

An example of a SeGW FQDN is:

```
MCC = 123;
```

```
MNC = 45;
```

```
ViD = abcd;
```

Which gives the SeGW FQDN: "segw.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.segw.mnc045.mcc123.3gppnetwork.org".

4.3.4 Element Manager (EM)

The Element Manager (EM) FQDN is derived as follows.

The "em" <system> label is added in front of the operator's OAM realm domain name:

```
em.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If particular operator deployment scenario has multiple Element Managers (one per vendor), the <vendor ID> label is added in front of the "em" label:

```
vendor<ViD>.em.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

An example of a EM FQDN is:

```
MCC = 123;
```

```
MNC = 45;
```

```
ViD = abcd;
```

Which gives the EM FQDN: "em.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.em.mnc045.mcc123.3gppnetwork.org".

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2013-12	SA#62	SP-130639			Submitted to SA#62 for information and approval	0.2.0	1.0.0
2013-12					Version after approval	1.0.0	12.0.0
2016-01	-	-	-	-	Update to Rel-13 version (MCC)	12.0.0	13.0.0

History

Document history		
V13.0.0	February 2016	Publication