
# ETSI TS 132 631 V6.0.0 (2004-09)

**Technical Specification** 

Universal Mobile Telecommunications System (UMTS); Telecommunication management; Configuration Management (CM); Core network resources Integration Reference Point (IRP): Requirements (3GPP TS 32.631 version 6.0.0 Release 6)



Reference RTS/TSGS-0532631v600

> Keywords UMTS

#### ETSI

#### 650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>http://portal.etsi.org/tb/status/status.asp</u>

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI\_support.asp

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2004. All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

### Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <u>http://webapp.etsi.org/key/queryform.asp</u>.

## Contents

| Intel           | lectual Property Rights                                       | 2           |
|-----------------|---|-------------|
| Fore            | word  | 2           |
| Fore            | word  | 4           |
| Intro           | duction   | 4           |
| 1               | Scope   | 5           |
| 2               | References  |             |
| 3<br>3.1<br>3.3 | Definitions and abbreviations<br>Definitions<br>Abbreviations | 5<br>5<br>6 |
| 4               | Requirements  | 7           |
| Ann             | ex A (informative): Change history                            | 8           |
| Histo           |   |             |

#### Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; Configuration Management (CM); as identified below:

| 32.631: | "Core network resources Integration Reference Point (IRP): Requirements";  |
|---------|--|
| 32.632: | "Core network resources Integration Reference Point (IRP): Network Resource Model (NRM)";  |
| 32.633: | "Core network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)"; |
| 32.634: | "Core network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".     |
| 32.635: | "Core network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".     |

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QOS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

#### 1 Scope

The present document defines , in addition to the requirements defined in [1], [2] and [3], the requirements for the present IRP: Core Network Resources IRP.

### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.602: "Telecommunication management; Configuration Management (CM); Basic Configuration Management Integration Reference Point (IRP): Information Service (IS)".

### 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

**Data:** is any information or set of information required to give software or equipment or combinations thereof a specific state of functionality.

**Element Manager (EM):** provides a package of end-user functions for management of a set of closely related types of Network Elements (NEs). These functions can be divided into two main categories:

- *Element Management Functions* for management of NEs on an individual basis. These are basically the same functions as supported by the corresponding local terminals.
- *Sub-Network Management Functions* that are related to a network model for a set of NEs constituting a clearly defined sub-network, which may include relations between the NEs. This model enables additional functions on the sub-network level (typically in the areas of network topology presentation, alarm correlation, service impact analysis and circuit provisioning).

**IRP:** See 3GPP TS 32.101 [1].

IRP Information Model: See 3GPP TS 32.101 [1].

IRP Information Service: See 3GPP TS 32.101 [1].

IRP Solution Set: See 3GPP TS 32.101 [1].

**Managed Object (MO):** an abstract entity, which may be accessed through an open interface between two or more systems, and representing a Network Resource (NR) for the purpose of management. The Managed Object (MO) is an instance of a Managed Object Class (MOC) as defined in a Management Information Model (MIM). The MIM does not define how the MO or NR is implemented; only what can be seen in the interface.

**Managed Object Class (MOC):** a description of all the common characteristics for a number of MOs, such as their attributes, operations, notifications and behaviour.

**Management Information Model (MIM)**: also referred to as NRM – see the definition below. There is a slight difference between the meaning of MIM and NRM – the term MIM is generic and can be used to denote any type of management model, while NRM denotes the model of the actual managed telecommunications Network Resources (NRs).

**Network Element (NE):** is a discrete telecommunications entity, which can be, managed over a specific interface e.g. the RNC.

**Network Manager (NM)**: provides a package of end-user functions with the responsibility for the management of a network, mainly as supported by the EM(s) but it may also involve direct access to the NEs. All communication with the network is based on open and well-standardised interfaces supporting management of multi-vendor and multi-technology NEs.

**Network Resource** (**NR**): is a component of a NE, which can be identified as a discrete separate entity and is in an object oriented environment for the purpose of management represented by an abstract entity called Managed Object (MO).

**Network Resource Model (NRM)**: a model representing the actual managed telecommunications Network Resources (NRs) that a System is providing through the subject IRP. An NRM describes Managed Object Classes (MOC), their associations, attributes and operations. The NRM is also referred to as "MIM" (see above) which originates from the ITU-T TMN.

Object Management Group (OMG): see http://www.omg.org.

**Operations System (OS):** indicates a generic management system, independent of its location level within the management hierarchy.

#### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| CM    | Configuration Management  |
|-------|---|
| CMIP  | Common Management Information Protocol  |
| CORBA | Common Object Request Broker Architecture                                       |
| EM    | Element Manager   |
| FM    | Fault Management  |
| GSM   | Global System for Mobile communication  |
| IRP   | Integration Reference Point   |
| IS    | Information Service (see [1])   |
| ITU-T | International Telecommunication Union, Telecommunication Standardisation Sector |
| MIB   | Management Information Base   |
| MIM   | Management Information Model  |
| MOC   | Managed Object Class  |
| MOI   | Managed Object Instance   |
| NE    | Network Element   |
| NM    | Network Manager   |
| NR    | Network Resource  |
| NRM   | Network Resource Model  |
| OMG   | Object Management Group   |
| OS    | Operations System   |
| PM    | Performance Management  |
| TM    | Telecom Management  |
| UML   | Unified Modelling Language (OMG)  |
| UMTS  | Universal Mobile Telecommunications System                                      |

### 4 Requirements

The following general and high-level requirements apply for the present IRP:

- A. IRP-related requirements in 3GPP TS 32.101 [1].
- B. IRP-related requirements in 3GPP TS 32.102 [2].
- C. IRP-related requirements in 3GPP TS 32.600 [3].

In addition to the above, the following more specific requirements apply:

- 1. The Network Resource Model defined by this IRP shall contain CN specific MOCs and related definitions, supporting Core Network entities in the current 3GPP Release.
- 2. The Network Resource Model defined by this IRP shall provide support for enabling consistency between UTRAN/GERAN and CN parameters, e.g. by defining relevant attributes.

# Annex A (informative): Change history

|          | Change history |           |     |     |   |       |       |  |
|----------|----------------|-----------|-----|-----|---|-------|-------|--|
| Date     | TSG #          | TSG Doc.  | CR  | Rev | Subject/Comment   | Old   | New   |  |
| Jun 2001 | S_12           | SP-010283 |     |     | Approved at TSG SA #12 and placed under Change Control  | 2.0.0 | 4.0.0 |  |
| Jun 2002 | S_16           | SP-020301 | 001 |     | Adding Core Network Management requirements over Interface-N for ReI-5                                    | 4.0.0 | 5.0.0 |  |
| Sep 2004 | S_25           | SP-040541 |     |     | Automatic upgrade to Rel- 6 (no CR) as per request in SP-<br>040541 SA5_presentation_SA_25.ppt (slide 17) | 5.0.0 | 6.0.0 |  |
|          |                |           |     |     |   |       |       |  |

# History

| Document history |                            |  |  |  |  |  |
|------------------|----------------------------|--|--|--|--|--|
| V6.0.0           | September 2004 Publication |  |  |  |  |  |
|                  |                            |  |  |  |  |  |
|                  |                            |  |  |  |  |  |
|                  |                            |  |  |  |  |  |
|                  |                            |  |  |  |  |  |