

ETSI TS 132 654 V5.4.0 (2004-06)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Telecommunication management;
Configuration Management (CM);
GERAN network resources Integration Reference Point (IRP):
Common Management Information Protocol (CMIP)
Solution Set (SS)
(3GPP TS 32.654 version 5.4.0 Release 5)**



Reference

RTS/TSGS-0532654v540

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Basic aspects	7
4.1 Architectural Aspects	7
4.2 Mapping	7
4.2.1 Mapping of Information Object Classes	7
4.2.2 Mapping of Information Object Class Attributes.....	8
4.2.2.1 Attribute Mapping of the IOC <i>BssFunction</i>	8
4.2.2.2 Attribute Mapping of the IOC <i>BtsSiteMgr</i>	8
4.2.2.3 Attribute Mapping of the IOC <i>GsmCell</i>	8
4.2.2.4 Attribute Mapping of the IOC <i>GsmRelation</i>	9
4.2.2.5 Attribute Mapping of the IOC <i>ExternalGsmCell</i>	9
4.2.2.6 Attribute Mapping of the IOC <i>ExternalBssFunction</i>	9
5 GDMO Definitions.....	10
5.1 Managed Object Classes	10
5.1.1 <i>bssFunction</i>	10
5.1.2 <i>btsSiteMgr</i>	10
5.1.3 <i>gsmCell</i>	10
5.1.4 <i>externalGsmCell</i>	11
5.1.5 <i>gsmRelation</i>	11
5.1.6 <i>externalBssFunction</i>	11
5.1.7 <i>gsmCellR54</i>	11
5.2 Packages	12
5.2.1 <i>bssFunctionBasicPackage</i>	12
5.2.2 <i>btsSiteMgrBasicPackage</i>	12
5.2.3 <i>btsSiteMgrGeoPositionPackage</i>	12
5.2.4 <i>gsmCellBasicPackage</i>	12
5.2.5 <i>gsmCellMandatoryPackage</i>	12
5.2.6 <i>gsmCellOptionalPackage</i>	13
5.2.7 <i>externalGsmCellBasicPackage</i>	13
5.2.8 <i>externalGsmCellMandatoryPackage</i>	13
5.2.9 <i>gsmRelationBasicPackage</i>	13
5.2.10 <i>gsmRelationOptionalPackage</i>	14
5.2.11 <i>ExternalBssFunctionBasicPackage</i>	14
5.2.12 <i>gsmCellMandatoryPackageR54</i>	14
5.3 Attributes	14
5.3.1 <i>bssFunctionId</i>	14
5.3.2 <i>btsSiteMgrId</i>	15
5.3.3 <i>longitude</i>	15
5.3.4 <i>latitude</i>	15
5.3.5 <i>gsmCellId</i>	15
5.3.6 <i>racc</i>	15
5.3.7 <i>gsmRelationId</i>	16
5.3.8 <i>externalGsmCellId</i>	16
5.3.9 <i>externalBssFunctionId</i>	16

5.3.10	plmnPermitted.....	16
5.4	Name Binding	16
5.4.1	bssFunction - managedElement	16
5.4.2	btsSiteMgr - bssFunction	17
5.4.3	gsmCell - btsSiteMgr	17
5.4.4	gsmRelation - gsmCell.....	17
5.4.5	externalGsmCell - subNetwork.....	18
5.4.6	externalBssFunction - subNetwork.....	18
5.4.7	gsmCellR54 - btsSiteMgr	18
5.4.8	gsmRelation - gsmCellR54	19
6	ASN.1 Definitions	20
Annex A (informative): Change history		21
History		22

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; Configuration Management (CM), as identified below:

- 32.651: "GERAN network resources Integration Reference Point (IRP): Requirements".
- 32.652: "GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- 32.653: "GERAN network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- 32.654: "GERAN network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**
- 32.655: "GERAN network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

The interface Itf-N, defined in 3GPP TS 32.102 [2], is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the GERAN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.652 [4]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.652 V5.3.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".
- [4] 3GPP TS 32.652: "Telecommunication management; Configuration Management (CM); GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".
- [10] GSM 12.20 (06/1996): "Digital cellular communication system (Phase 2); Base Station System (BSS) Management Information".
- [11] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

- [12] 3GPP TS 32.644: "Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 [11] and 3GPP TS 32.652 [4] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
GERAN	GSM-EDGE Radio Access Network
IDL	Interface Definition Language
IEC	International Electro-technical Commission
ISO	International Standards Organization
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	Universal Terrestrial Radio Access Network

4 Basic aspects

4.1 Architectural Aspects

A technology independent GERAN network resource model is defined in 3GPP TS 32.652 [4] for 3G networks. This document provides an implementation of this GERAN network resource model by using CMIP technology.

4.2 Mapping

The semantic of the GERAN Network Resource Model is defined in 3GPP TS 32.652 [4]. The specification of the information object classes defined there is independent of any implementation technology and protocol. This clause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the GERAN Network Resource IRP.

4.2.1 Mapping of Information Object Classes

The following table maps the information object classes defined in the GERAN Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

Table 4.1: Mapping of MOCs

IS IOC	CMIP SS MOC
BssFunction	bssFunction
BtsSiteMgr	btsSiteMgr
GsmCell	gsmCellR54
GsmRelation	gsmRelation
ExternalGsmCell	externalGsmCell
ExternalBssFunction	externalBssFunction

4.2.2 Mapping of Information Object Class Attributes

This clause depicts the mapping of the attributes defined in 3GPP TS 32.652 [4] on the corresponding attributes of the CMIP Solution Set.

4.2.2.1 Attribute Mapping of the IOC *BssFunction*

Table 4.2: Attribute mapping of the IOC *BssFunction*

IS Attribute	CMIP SS Attribute	Qualifier
bssFunctionId	bssFunctionId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M

4.2.2.2 Attribute Mapping of the IOC *BtsSiteMgr*

Table 4.3: Attribute mapping of the IOC *BtsSiteMgr*

IS Attribute	CMIP SS Attribute	Qualifier
btsSiteMgrId	btsSiteMgrId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
latitude	latitude	O
longitude	longitude	O

4.2.2.3 Attribute Mapping of the IOC *GsmCell*

Table 4.4: Attribute mapping of the IOC *GsmCell*

IS Attribute	CMIP SS Attribute	Qualifier
gsmCellId	gsmCellId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
cellIdentity	cellGlobalIdentity (GSM 12.20 [10])	M
lac		
mcc		
mnc		
cellAllocation	cellAllocation (GSM 12.20 [10])	M
ncc	bslIdentityCode.ncc (GSM 12.20 [10])	M
bcc	bslIdentityCode.bcc (GSM 12.20 [10])	M
rac	rac (3GPP TS 32.644 [12])	O
racc	racc	O
tsc	tsc (GSM 12.20 [10])	M
rxLevAccessMin	rxLevAccessMin (GSM 12.20 [10])	M
msTxPwrMaxCCH	msTxPwrMaxCCH (GSM 12.20 [10])	M
hoppingSequenceNumber	hoppingSequenceNumber (GSM 12.20 [10])	M
plmnPermitted	plmnPermitted	M

4.2.2.4 Attribute Mapping of the IOC *GsmRelation*Table 4.5: Attribute mapping of the IOC *GsmRelation*

IS Attribute	CMIP SS Attribute	Qualifier
gsmRelationId	gsmRelationId	M
adjacentCell	adjacentCell (3GPP TS 32.644 [12])	M
bcchFrequency	bcchFrequency (GSM 12.20 [10])	O
ncc	bsIdentityCode.ncc (GSM 12.20 [10])	O
bcc	bsIdentityCode.bcc (GSM 12.20 [10])	O
lac	lac (3GPP TS 32.644 [12])	O

4.2.2.5 Attribute Mapping of the IOC *ExternalGsmCell*Table 4.6: Attribute mapping of the IOC *ExternalGsmCell*

IS Attribute	CMIP SS Attribute	Qualifier
externalGsmCellId	externalGsmCellId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M
cellIdentity	cellGlobalIdentity (GSM 12.20 [10])	M
lac		
mcc		
mnc		
bcchFrequency	bcchFrequency (GSM 12.20 [10])	M
ncc	bsIdentityCode.ncc (GSM 12.20 [10])	M
bcc	bsIdentityCode.bcc (GSM 12.20 [10])	M
rac	rac (3GPP TS 32.644 [12])	O
racc	racc	O

4.2.2.6 Attribute Mapping of the IOC *ExternalBssFunction*Table 4.7: Attribute mapping of the IOC *ExternalBssFunction*

IS Attribute	CMIP SS Attribute	Qualifier
externalBssFunctionId	externalBssFunctionId	M
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M

5 GDMO Definitions

5.1 Managed Object Classes

5.1.1 bssFunction

```

bssFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  bssFunctionBasicPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 1};

```

5.1.2 btsSiteMgr

```

btsSiteMgr MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  btsSiteMgrBasicPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.",
  "3GPP TS 32.674 Release 5": operationalStateAttributePackage
    PRESENT IF
      "Instances of this MOC support operationalState attribute.",
  btsSiteMgrGeoPositionPackage
    PRESENT IF
      "the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 2};

```

5.1.3 gsmCell

```

gsmCell MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  gsmCellBasicPackage,
  gsmCellMandatoryPackage,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.",
  gsmCellOptionalPackage PRESENT IF
    "the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 3};

```

5.1.4 externalGsmCell

```
externalGsmCell MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  externalGsmCellBasicPackage,
  externalGsmCellMandatoryPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.",
  gsmCellOptionalPackage
    PRESENT IF
      "the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 4};
```

5.1.5 gsmRelation

```
gsmRelation MANAGED OBJECT CLASS
DERIVED FROM
  "Recommendation X.721: 1992":top;
CHARACTERIZED BY
  gsmRelationBasicPackage;
CONDITIONAL PACKAGES
  gsmRelationOptionalPackage
    PRESENT IF
      "the attributes defined in this package are supported by an instance of this class.",
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      are supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 5};
```

5.1.6 externalBssFunction

```
externalBssFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  externalBssFunctionBasicPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
      ITU-T Rec. X.721 are supported by an instance of this class.",
  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
      is supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 6};
```

5.1.7 gsmCellR54

```
gsmCellR54 MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624 Release 5": managedFunction;
CHARACTERIZED BY
  gsmCellBasicPackage,
  gsmCellMandatoryPackageR54,
  "3GPP TS 32.111-4 Release 5": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
```

```

    PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
        ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
        is supported by an instance of this class.",
    gsmCellOptionalPackage PRESENT IF
        "the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-654ObjectClass 7};

```

5.2 Packages

5.2.1 bssFunctionBasicPackage

```

bssFunctionBasicPackage PACKAGE
    BEHAVIOUR
        bssFunctionBasicPackageBehaviour;
    ATTRIBUTES
        bssFunctionId GET;
REGISTERED AS {ts32-654Package 1};

bssFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The Managed Object Class bssFunction represents BSS functionality.";

```

5.2.2 btsSiteMgrBasicPackage

```

btsSiteMgrBasicPackage PACKAGE
    BEHAVIOUR
        btsSiteMgrBasicPackageBehaviour;
    ATTRIBUTES
        btsSiteMgrId GET;
REGISTERED AS {ts32-654Package 2};

btsSiteMgrBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'BtsSiteMgr' managed object contains site specific information for a BTS site.";

```

5.2.3 btsSiteMgrGeoPositionPackage

```

btsSiteMgrGeoPositionPackage PACKAGE
    BEHAVIOUR
        btsSiteMgrGeoPositionPackageBehaviour;
    ATTRIBUTES
        longitude GET-REPLACE,
        latitude GET-REPLACE;
REGISTERED AS {ts32-654Package 3};

btsSiteMgrGeoPositionPackageBehaviour BEHAVIOUR
DEFINED AS
    "This package contains the attributes describing the geographic position of a BTS site.";

```

5.2.4 gsmCellBasicPackage

```

gsmCellBasicPackage PACKAGE
    BEHAVIOUR
        gsmCellBasicPackageBehaviour;
    ATTRIBUTES
        gsmCellId GET;
REGISTERED AS {ts32-654Package 4};

gsmCellBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The managed object class gsmCell represents the GSM radio cell.";

```

5.2.5 gsmCellMandatoryPackage

```

gsmCellMandatoryPackage PACKAGE

```

BEHAVIOUR

```
gsmCellMandatoryPackageBehaviour;
```

ATTRIBUTES

```
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellAllocation      GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode     GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellGlobalIdentity  GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": tsc                 GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": rxLevAccessMin      GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": msTxPwrMaxCCH       GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": hoppingSequenceNumber GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": plmnPermitted       GET-REPLACE;
```

```
REGISTERED AS {ts32-654Package 5};
```

```
gsmCellMandatoryPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This package contains the elementary mandatory attributes of a gsmCell.";
```

5.2.6 gsmCellOptionalPackage

```
gsmCellOptionalPackage PACKAGE
```

BEHAVIOUR

```
gsmCellOptionalPackageBehaviour;
```

ATTRIBUTES

```
"3GPP TS 32.644 Release 5": rac      GET-REPLACE,
racc                               GET-REPLACE;
```

```
REGISTERED AS {ts32-654Package 6};
```

```
gsmCellOptionalPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This package contains the optional GPRS attributes of a gsmCell.";
```

5.2.7 externalGsmCellBasicPackage

```
externalGsmCellBasicPackage PACKAGE
```

BEHAVIOUR

```
externalGsmCellBasicPackageBehaviour;
```

ATTRIBUTES

```
externalGsmCellId  GET;
```

```
REGISTERED AS {ts32-654Package 7};
```

```
externalGsmCellBasicPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This Managed Object Class represents a radio cell controlled by another IRPAgent. It is a necessary attribute for inter-system handover. This MOC is a subreplication of a MOC in another NEM.";
```

5.2.8 externalGsmCellMandatoryPackage

```
externalGsmCellMandatoryPackage PACKAGE
```

BEHAVIOUR

```
externalGsmCellMandatoryPackageBehaviour;
```

ATTRIBUTES

```
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode      GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellGlobalIdentity  GET-REPLACE,
"ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bcchFrequency       GET-REPLACE;
```

```
REGISTERED AS {ts32-654Package 8};
```

```
externalGsmCellMandatoryPackageBehaviour BEHAVIOUR
```

DEFINED AS

```
"This package contains the elementary mandatory attributes of a externalGsmCell.";
```

5.2.9 gsmRelationBasicPackage

```
gsmRelationBasicPackage PACKAGE
```

BEHAVIOUR

```
gsmRelationBasicPackageBehaviour;
```

ATTRIBUTES

```
gsmRelationId      GET,
"3GPP TS 32.644 Release 5": adjacentCell  GET-REPLACE;
```

```
REGISTERED AS {ts32-654Package 9};
```

```
gsmRelationBasicPackageBehaviour BEHAVIOUR
```

DEFINED AS

"The 'GsmRelation' managed object contains radio network related parameters for the relation to the 'GsmCell' or 'ExternalGsmCell' managed object. Note: In handover relation terms, the cell containing the GSM Relation object is the source cell for the handover. The cell referred to in the GSM relation object is the target cell for the handover. This defines a one-way handover relation where the direction is from source cell to target cell.";

5.2.10 gsmRelationOptionalPackage

```
gsmRelationOptionalPackage PACKAGE
  BEHAVIOUR
    gsmRelationOptionalPackageBehaviour;
  ATTRIBUTES
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode   GET-REPLACE,
    "3GPP TS 32.644 Release 5": lac                                       GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bcchFrequency   GET-REPLACE;
REGISTERED AS {ts32-654Package 10};
```

```
gsmRelationOptionalPackageBehaviour BEHAVIOUR
DEFINED AS
  "This package contains the optional attributes of a gsmRelation.";
```

5.2.11 ExternalBssFunctionBasicPackage

```
externalBssFunctionBasicPackage PACKAGE
  BEHAVIOUR
    externalBssFunctionBasicPackageBehaviour;
  ATTRIBUTES
    externalBssFunctionId   GET;
REGISTERED AS {ts32-654Package 11};
```

```
externalBssFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The Managed Object Class externalBssFunction represents external BSS functionality.";
```

5.2.12 gsmCellMandatoryPackageR54

```
gsmCellMandatoryPackageR54 PACKAGE
  BEHAVIOUR
    gsmCellMandatoryPackageR54Behaviour;
  ATTRIBUTES
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellAllocation   GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": bsIdentityCode   GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": cellGlobalIdentity GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": tsc               GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": rxLevAccessMin   GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": msTxPwrMaxCCH    GET-REPLACE,
    "ETS 300 622: JUNE 1996 (GSM 12.20 VERSION 4.2.1)": hoppingSequenceNumber GET-REPLACE,
    plmnPermitted
REGISTERED AS {ts32-654Package 12};
```

```
gsmCellMandatoryPackageR54Behaviour BEHAVIOUR
DEFINED AS
  "This package contains the elementary mandatory attributes of a gsmCell.";
```

5.3 Attributes

5.3.1 bssFunctionId

```
bssFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    bssFunctionIdBehaviour;
REGISTERED AS {ts32-654Attribute 1};
```

```
bssFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a bssFunction object.";
```

5.3.2 btsSiteMgrId

```
btsSiteMgrId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    btsSiteMgrIdBehaviour;
REGISTERED AS {ts32-654Attribute 2};

btsSiteMgrIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a btsSiteMgr object.";
```

5.3.3 longitude

```
longitude ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.Longitude;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    longitudeBehaviour;
REGISTERED AS {ts32-654Attribute 3};

longitudeBehaviour BEHAVIOUR
DEFINED AS
  "Used for geographical positioning of the sitemanager.";
```

5.3.4 latitude

```
latitude ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.Latitude;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    latitudeBehaviour;
REGISTERED AS {ts32-654Attribute 4};

latitudeBehaviour BEHAVIOUR
DEFINED AS
  "Used for geographical positioning of the sitemanager.";
```

5.3.5 gsmCellId

```
gsmCellId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gsmCellIdBehaviour;
REGISTERED AS {ts32-654Attribute 5};

gsmCellIdBehaviour BEHAVIOUR
DEFINED AS
  "Cell Identity (Ref GSM 03.03).";
```

5.3.6 racc

```
racc ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-654TypeModule.Racc;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    raccBehaviour;
REGISTERED AS {ts32-654Attribute 7};

raccBehaviour BEHAVIOUR
```


DEFINED AS
 "Routing Area Colour Code, RACC.";

5.3.7 gsmRelationId

gsmRelationId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
 TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 gsmRelationIdBehaviour;
REGISTERED AS {ts32-654Attribute 8};

gsmRelationIdBehaviour BEHAVIOUR
DEFINED AS
 "This attribute identifies a gsmRelation object.";

5.3.8 externalGsmCellId

externalGsmCellId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
 TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 externalGsmCellIdBehaviour;
REGISTERED AS {ts32-654Attribute 9};

externalGsmCellIdBehaviour BEHAVIOUR
DEFINED AS
 "This attribute identifies a externalGsmCell object.";

5.3.9 externalBssFunctionId

externalBssFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
 TS32-654TypeModule.GeneralObjectId;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 externalBssFunctionIdBehaviour;
REGISTERED AS {ts32-654Attribute 10};

externalBssFunctionIdBehaviour BEHAVIOUR
DEFINED AS
 "This attribute identifies an externalBssFunction object.";

5.3.10 plmnPermitted

plmnPermitted ATTRIBUTE
WITH ATTRIBUTE SYNTAX
 TS32-654TypeModule.PlmnPermitted;
MATCHES FOR
 EQUALITY;
BEHAVIOUR
 plmnPermittedBehaviour;
REGISTERED AS {ts32-654Attribute 11};

plmnPermittedBehaviour BEHAVIOUR
DEFINED AS
 "Network Color Code permitted as defined by the NCC_PERMITTED parameter specified in 3GPP TS 45.008";

5.4 Name Binding

5.4.1 bssFunction - managedElement

bssFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS

```

    bssFunction;
NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624 Release 5": managedElement;
WITH ATTRIBUTE
    bssFunctionId;
BEHAVIOUR
    bssFunction-managedElementBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 1};

```

```

bssFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a managedElement contains and controls a bssFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter."

5.4.2 btsSiteMgr - bssFunction

```

btsSiteMgr-bssFunction NAME BINDING
SUBORDINATE OBJECT CLASS
    btsSiteMgr;
NAMED BY SUPERIOR OBJECT CLASS
    bssFunction;
WITH ATTRIBUTE
    btsSiteMgrId;
BEHAVIOUR
    btsSiteMgr-bssFunctionBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 2};

```

```

btsSiteMgr-bssFunctionBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a bssFunction contains and controls a btsSiteMgr. When automatic instance naming is used, the choice of name bindings is left as a local matter."

5.4.3 gsmCell - btsSiteMgr

```

gsmCell-btsSiteMgr NAME BINDING
SUBORDINATE OBJECT CLASS
    gsmCell;
NAMED BY SUPERIOR OBJECT CLASS
    btsSiteMgr;
WITH ATTRIBUTE
    gsmCellId;
BEHAVIOUR
    gsmCell-btsSiteMgrBehaviour;
CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 3};

```

```

gsmCell-btsSiteMgrBehaviour BEHAVIOUR
DEFINED AS

```

"The name binding represents a relationship in which a btsSiteMgr contains and controls a gsmCell. When automatic instance naming is used, the choice of name bindings is left as a local matter."

5.4.4 gsmRelation - gsmCell

```

gsmRelation-gsmCell NAME BINDING
SUBORDINATE OBJECT CLASS
    gsmRelation;
NAMED BY SUPERIOR OBJECT CLASS
    gsmCell;
WITH ATTRIBUTE
    gsmRelationId;

```

```

BEHAVIOUR
  gsmRelation-gsmCellBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 4};

```

```

gsmRelation-gsmCellBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a gsmCell contains
  and controls a gsmRelation. When automatic instance naming is used, the choice
  of name bindings is left as a local matter.";

```

5.4.5 externalGsmCell - subNetwork

```

externalGsmCell-subNetwork NAME BINDING
SUBORDINATE OBJECT CLASS
  externalGsmCell;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624 Release 5": subNetwork;
WITH ATTRIBUTE
  externalGsmCellId;
BEHAVIOUR
  externalGsmCell-subNetworkBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 5};

```

```

externalGsmCell-subNetworkBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a subNetwork contains
  and controls an externalGsmCell. When automatic instance naming is used, the choice
  of name bindings is left as a local matter.";

```

5.4.6 externalBssFunction - subNetwork

```

externalBssFunction-subNetwork NAME BINDING
SUBORDINATE OBJECT CLASS
  externalBssFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624 Release 5": subNetwork;
WITH ATTRIBUTE
  externalBssFunctionId;
BEHAVIOUR
  externalBssFunction-subNetworkBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-654NameBinding 6};

```

```

externalBssFunction-subNetworkBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a subNetwork contains
  and controls an externalBssFunction. When automatic instance naming is used, the choice
  of name bindings is left as a local matter.";

```

5.4.7 gsmCellR54 - btsSiteMgr

```

gsmCellR54-btsSiteMgr NAME BINDING
SUBORDINATE OBJECT CLASS
  gsmCellR54;
NAMED BY SUPERIOR OBJECT CLASS
  btsSiteMgr;
WITH ATTRIBUTE
  gsmCellId;
BEHAVIOUR
  gsmCellR54-btsSiteMgrBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE

```

```
ONLY-IF-NO-CONTAINED-OBJECTS;  
REGISTERED AS {ts32-654NameBinding 7};
```

```
gsmCellR54-btsSiteMgrBehaviour BEHAVIOUR  
DEFINED AS
```

```
"The name binding represents a relationship in which a btsSiteMgr contains  
and controls a gsmCellR54. When automatic instance naming is used, the choice  
of name bindings is left as a local matter.";
```

5.4.8 gsmRelation - gsmCellR54

```
gsmRelation-gsmCellR54 NAME BINDING  
SUBORDINATE OBJECT CLASS  
gsmRelation;  
NAMED BY SUPERIOR OBJECT CLASS  
gsmCellR54;  
WITH ATTRIBUTE  
gsmRelationId;  
BEHAVIOUR  
gsmRelation-gsmCellR54Behaviour;  
CREATE  
WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;  
DELETE  
ONLY-IF-NO-CONTAINED-OBJECTS;  
REGISTERED AS {ts32-654NameBinding 8};
```

```
gsmRelation-gsmCellR54Behaviour BEHAVIOUR  
DEFINED AS
```

```
"The name binding represents a relationship in which a gsmCellR54 contains  
and controls a gsmRelation. When automatic instance naming is used, the choice  
of name bindings is left as a local matter.";
```

6 ASN.1 Definitions

```
TS32-654TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
umts-Operation-Maintenance(3) ts-32-654(654) informationModel(0) asn1Module(2) version1(1)}

DEFINITIONS IMPLICIT TAGS ::=
BEGIN

--EXPORTS everything

IMPORTS

GeneralObjectId
  FROM TS32-624TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
  umts-Operation-Maintenance(3) ts32-624(624) informationModel(0) asn1Module(2) version1(1)}

Rac
  FROM TS32-644TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
  umts-Operation-Maintenance(3) ts-32-644(644) informationModel(0) asn1Module(2) version1(1)};

-- 3GPP TS 32.654 related Object Identifiers

baseNodeUMTS          OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0)
mobileDomain(0) umts-Operation-Maintenance(3)}

ts32-654              OBJECT IDENTIFIER ::= {baseNodeUMTS ts32-654(654)}
ts32-654InfoModel    OBJECT IDENTIFIER ::= {ts32-654 informationModel(0)}

ts32-654ObjectClass  OBJECT IDENTIFIER ::= {ts32-654InfoModel managedObjectClass(3)}
ts32-654Package      OBJECT IDENTIFIER ::= {ts32-654InfoModel package(4)}
ts32-654Parameter    OBJECT IDENTIFIER ::= {ts32-654InfoModel parameter(5)}
ts32-654NameBinding  OBJECT IDENTIFIER ::= {ts32-654InfoModel nameBinding(6)}
ts32-654Attribute    OBJECT IDENTIFIER ::= {ts32-654InfoModel attribute(7)}
ts32-654Action       OBJECT IDENTIFIER ::= {ts32-654InfoModel action(9)}
ts32-654Notification OBJECT IDENTIFIER ::= {ts32-654InfoModel notification(10)}

-- Start of 3GPP SA5 own definitions

Longitude ::= INTEGER

Latitude ::= INTEGER

PlmnPermitted ::= INTEGER

Racc ::= INTEGER

END -- of TS32-654TypeModule
```

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Sep 2001	S_13	SP-010478	001	--	Correction due to TS renumbering	4.0.0	4.1.0
Sep 2001	S_13	SP-010477	002	--	Addition of mcc and mnc in the object model of GERAN	4.0.0	4.1.0
Dec 2002	S_18	SP-020749	003	--	Alignment of the CMIP SS with the Rel-5 version of the IS in 32.652	4.1.0	5.0.0
Jun 2003	S_20	SP-030283	005	--	Removal of relationType	5.0.0	5.1.0
Jun 2003	S_20	SP-030286	006	--	Alignment of object class names to externalGsmCell - Alignment with 32.624	5.0.0	5.1.0
Sep 2003	S_21	SP-030418	007	--	Inclusion of ExternalBssFunction - Alignment with 32.652	5.1.0	5.2.0
Dec 2003	S_22	SP-030642	008	--	Add notifications to functional objects - Align with 32.652 (IS)	5.2.0	5.3.0
Jun 2004	S_24	SP-040257	009	--	Correction of the type of the plmnPermittd attribute	5.3.0	5.4.0

History

Document history		
V5.0.0	December 2002	Publication
V5.1.0	June 2003	Publication
V5.2.0	September 2003	Publication
V5.3.0	December 2003	Publication
V5.4.0	June 2004	Publication