

# ETSI TS 132 673 V5.3.0 (2005-06)

---

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+);  
Universal Mobile Telecommunications System (UMTS);  
Telecommunication management;  
Configuration Management (CM);  
State Management Integration Reference Point (IRP);  
Common Object Request Broker Architecture (CORBA)  
Solution Set (SS)  
(3GPP TS 32.673 version 5.3.0 Release 5)**

---



---

Reference

RTS/TSGS-0532673v530

---

Keywords

GSM, UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.  
All rights reserved.

**DECT™**, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
3 Definitions and abbreviations.....	5
3.1 Definitions .....	5
3.2 Abbreviations .....	5
3.3 IRP document version number string .....	6
4 Architectural Features .....	6
5 Mapping .....	6
5.1 IOC Mapping.....	6
5.2 Mapping of Attributes .....	6
<b>Annex A (normative): IDL specifications .....</b>	<b>7</b>
A.1 IDL specification (file name "StateManagementIRPConstDefs.idl").....	7
A.2 IDL specification (file name "StateManagementIRPOptConstDefs.idl") .....	8
<b>Annex B (informative): Change history .....</b>	<b>10</b>
History .....	11

---

## Foreword

This Technical Specification (TS) has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; Configuration Management (CM); as identified below:

- 32.671: "State Management Integration Reference Point (IRP): Requirements";
- 32.672: "State Management Integration Reference Point (IRP): Information Service (IS)";
- 32.673: "State Management Integration Reference Point (IRP) : Common Object Request Broker Architecture (CORBA) Solution Set (SS)";**
- 32.674: "State Management Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of a deployment program (e.g. additions and deletions), as part of an optimisation program (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

---

# 1 Scope

The present document specifies the CORBA Solution Set (SS) for the IRP whose semantics is specified in State Management IRP: Information Service (IS) (3GPP TS 32.672 [2]).

Clause 1 to 3 provides background information. Clause 4 provides key architectural features supporting the SS. Clause 5 defines the mapping of operations, notification, parameters and attributes defined in IS to their SS equivalents. Annex A contains the IDL specification.

This Solution Set specification is related to 3GPP TS 32.672 (V5.0.X).

---

# 2 References

The following documents contain provisions, which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP) management; Requirements".
- [2] 3GPP TS 32.672: "Telecommunication management; Configuration Management (CM); State Management Integration Reference Point (IRP): Information Service (IS)".
- [3] ITU-T Recommendation X.721: "Information technology - Open Systems Interconnection - Structure of management information: Definition of management information".
- [4] ITU-T Recommendation M.3100: "Generic network information model".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions defined in 3GPP TS 32.672 [2] apply. There are no additional definitions applicable to the present document.

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CORBA	Common Object Request Broker Architecture
IDL	Interface Definition Language
IOC	Information Object Class
IRP	Integration Reference Point
IS	Information Service
NE	Network Element
OMG	Object Management Group
SS	Solution Set

### 3.3 IRP document version number string

The IRP document version number (sometimes called "IRP version" or "version number") string is used to identify this specification. The definition of "IRP document version number string" in 3GPP TS 32.311 [1] provides the rule to derive such a string.

As the State Management IRP IS as defined in 3GPP TS 32.672 [2] does not specify operations & notification (only State Management related data definitions), this string definition is stated here for potential future use only.

---

## 4 Architectural Features

The overall architectural feature of State Management IRP is specified in 3GPP TS 32.672 [2].

For this release there are no features identified that are specific to the CORBA SS.

---

## 5 Mapping

### 5.1 IOC Mapping

Table 1 provides the mapping of the information object classes defined in the IS of the State Management IRP [2] to the equivalent of this CORBA Solution Set.

**Table 1: Mapping of IOCs**

IOCs defined in State Management IRP IS [2]	CORBA SS Method
StateManagementEntity	No mapping applicable for this <<Archetyp>> class.

### 5.2 Mapping of Attributes

Table 2 provides the mapping of the IOC attributes defined in the IS of the State Management IRP [2] to their equivalents in this CORBA Solution Set. As [2] specified the Support Qualifier for these attributes as not applicable, mappings towards Mandatory and Optional are provided.

**Table 2: Mapping of Attributes**

Attributes defined in State Management IRP IS [2]	CORBA SS Method attributes	Qualifier
operationalState	OperationalState (ITU-T Recommendation X.721 [3])	M
operationalState	OperationalStateTypeOpt (ITU-T Recommendation X.721 [3])	O
usageState	UsageState (ITU-T Recommendation X.721 [3])	M
usageState	UsageStateTypeOpt (ITU-T Recommendation X.721 [3])	O
administrativeState	AdministrativeState (ITU-T Recommendation X.721 [3])	M
administrativeState	AdministrativeStateTypeOpt (ITU-T Recommendation X.721 [3])	O
alarmStatus	AlarmStatus (ITU-T Recommendation M.3100 [4])	M
alarmStatus	AlarmStatusTypeOpt (ITU-T Recommendation M.3100 [4])	O
proceduralStatus	ProceduralStatus (ITU-T Recommendation X.721 [3])	M
proceduralStatus	ProceduralStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
availabilityStatus	AvailabilityStatus (ITU-T Recommendation X.721 [3])	M
availabilityStatus	AvailabilityStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
controlStatus	ControlStatus (ITU-T Recommendation X.721 [3])	M
controlStatus	ControlStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
standbyStatus	StandbyStatus (ITU-T Recommendation X.721 [3])	M
standbyStatus	StandbyStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
unknownStatus	UnknownStatus (ITU-T Recommendation X.721 [3])	M
unknownStatus	UnknownStatusTypeOpt (ITU-T Recommendation X.721 [3])	O

---

## Annex A (normative): IDL specifications

### A.1 IDL specification (file name "StateManagementIRPConstDefs.idl")

```
#ifndef StateManagementIRPConstDefs_idl
#define StateManagementIRPConstDefs_idl

#include "CosNotification.idl"
#include "ManagedGenericIRPConstDefs.idl"

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

/* ## Module: StateManagementIRPConstDefs
This module contains commonly used definitions for State Management IRP
=====
*/
module StateManagementIRPConstDefs
{
    /*
    Definition of Operational State based on X.721 [3], if mandatory.
    */
    enum OperationalState
    {
        Disabled, Enabled
    };

    /*
    Definition of Usage State based on X.721 [3], if mandatory.
    */
    enum UsageState
    {
        Idle, Active, Busy
    };

    /*
    Definition of Administrative State based on X.721 [3], if mandatory.
    */
    enum AdministrativeState
    {
        Locked, Unlocked, ShuttingDown
    };

    /*
    Definition of Alarm Status based on M.3100 [4], if mandatory.
    */
    enum AlarmStatus
    {
        CLEARED, INDETERMINATE, WARNING, MINOR, MAJOR, CRITICAL
    };

    /*
    Definition of Procedural Status based on X.721 [3], if mandatory.
    */
    enum ProceduralStatusValues
    {
        InitializationRequired, NotInitialized, Initializing, Reporting,
        Terminating
    };
    typedef sequence <ProceduralStatusValues,5> ProceduralStatus;

    /*
    Definition of Availability Status based on X.721 [3], if mandatory.
    */
    enum AvailabilityStatusValues
    {
        InTest, Failed, PowerOff, OffLine, OffDuty, Dependency, Degraded,
```



```

    NotInstalled, LogFull
};
typedef sequence <AvailabilityStatusValues,9> AvailabilityStatus;

/*
Definition of Control Status based on X.721 [3], if mandatory.
*/
enum ControlStatusValues
{
    SubjectToTest, PartOfServicesLocked, ReservedForTest, Suspended
};
typedef sequence <ControlStatusValues,4> ControlStatus;

/*
Definition of Standby Status based on X.721 [3], if mandatory.
*/
enum StandbyStatus
{
    HotStandby, ColdStandby, ProvidingService
};

/*
Definition of Unknown Status based on X.721 [3], if mandatory
(if switch is TRUE then value equal to TRUE implies "unknown status").
*/
union UnknownStatus switch(boolean)
{
    case TRUE: boolean value;
};

};
#endif

```

---

## A.2 IDL specification (file name "StateManagementIRPOptConstDefs.idl")

```

#ifndef StateManagementIRPOptConstDefs_idl
#define StateManagementIRPOptConstDefs_idl

#include "CosNotification.idl"
#include "ManagedGenericIRPConstDefs.idl"
#include "StateManagementIRPConstDefs.idl"

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

/* ## Module: StateManagementIRPOptConstDefs
This module contains commonly used optional definitions for State Management IRP
=====
*/
module StateManagementIRPOptConstDefs
{
    /*
Definition of Operational State based on X.721 [3], if optional.
*/
union OperationalStateTypeOpt switch(boolean)
{
    case TRUE: StateManagementIRPConstDefs::OperationalState operational_state;
};

    /*
Definition of Usage State based on X.721 [3], if optional.
*/
union UsageStateTypeOpt switch(boolean)
{
    case TRUE: StateManagementIRPConstDefs::UsageState usage_state;
};

    /*
Definition of Administrative State based on X.721 [3], if optional.
*/
union AdministrativeStateTypeOpt switch(boolean)

```

```
{
  case TRUE: StateManagementIRPConstDefs::AdministrativeState administrative_state;
};

/*
Definition of Alarm Status based on M.3100 [4], if optional.
*/
union AlarmStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::AlarmStatus alarm_status;
};

/*
Definition of Procedural Status based on X.721 [3], if optional.
*/
union ProceduralStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::ProceduralStatus procedural_status;
};

/*
Definition of Availability Status based on X.721 [3], if optional.
*/
union AvailabilityStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::AvailabilityStatus availability_status;
};

/*
Definition of Control Status based on X.721 [3], if optional.
*/
union ControlStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::ControlStatus control_status;
};

/*
Definition of Standby Status based on X.721 [3], if optional.
*/
union StandbyStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::StandbyStatus standby_status;
};

/*
Definition of Unknown Status based on X.721 [3], if optional.
*/
union UnknownStatusTypeOpt switch(boolean)
{
  case TRUE: StateManagementIRPConstDefs::UnknownStatus unknown_status;
};
};
#endif
```

---

## Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Sep 2002	SA_17	SP-020470	--	--	Submitted to TSG SA #17 for Approval	1.0.0	5.0.0
Mar 2003	SA_19	SP-030143	0001	--	CORBA IDL Compiler Errors, Invalid CORBA IDL Include Reference	5.0.0	5.1.0
Sep 2004	SA_25	SP-040588	0002	--	Correction of the alarmStatus mapping – Align with 32.672 CM; State Management IRP Information Service	5.1.0	5.2.0
Jun 2005	SA_28	SP-050300	0006	--	Align AlarmStatus with the IS in TS 32.672	5.2.0	5.3.0

---

## History

<b>Document history</b>		
V5.0.0	September 2002	Publication
V5.1.0	March 2003	Publication
V5.2.0	September 2004	Publication
V5.3.0	June 2005	Publication