

ETSI TS 136 213 V12.10.0 (2016-08)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Physical layer procedures
(3GPP TS 36.213 version 12.10.0 Release 12)**



Reference

RTS/TSGR-0136213vca0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 6 |
| 1 Scope | 7 |
| 2 References | 7 |
| 3 Symbols and abbreviations..... | 7 |
| 3.1 Symbols..... | 7 |
| 3.2 Abbreviations | 8 |
| 4 Synchronization procedures | 10 |
| 4.1 Cell search | 10 |
| 4.2 Timing synchronization..... | 10 |
| 4.2.1 Radio link monitoring..... | 10 |
| 4.2.2 Inter-cell synchronization | 10 |
| 4.2.3 Transmission timing adjustments | 10 |
| 4.3 Timing for Secondary Cell Activation / Deactivation | 11 |
| 5 Power control | 12 |
| 5.1 Uplink power control..... | 12 |
| 5.1.1 Physical uplink shared channel..... | 12 |
| 5.1.1.1 UE behaviour | 12 |
| 5.1.1.2 Power headroom | 19 |
| 5.1.2 Physical uplink control channel | 21 |
| 5.1.2.1 UE behaviour | 22 |
| 5.1.3 Sounding Reference Symbol (SRS)..... | 25 |
| 5.1.3.1 UE behaviour | 25 |
| 5.1.4 Power allocation for dual connectivity | 26 |
| 5.1.4.1 Dual connectivity power control Mode 1..... | 27 |
| 5.1.4.2 Dual connectivity power control Mode 2..... | 34 |
| 5.2 Downlink power allocation | 38 |
| 5.2.1 eNodeB Relative Narrowband TX Power (RNTP) restrictions | 40 |
| 6 Random access procedure | 41 |
| 6.1 Physical non-synchronized random access procedure..... | 41 |
| 6.1.1 Timing | 41 |
| 6.2 Random Access Response Grant..... | 42 |
| 7 Physical downlink shared channel related procedures | 43 |
| 7.1 UE procedure for receiving the physical downlink shared channel | 44 |
| 7.1.1 Single-antenna port scheme | 51 |
| 7.1.2 Transmit diversity scheme | 52 |
| 7.1.3 Large delay CDD scheme | 52 |
| 7.1.4 Closed-loop spatial multiplexing scheme | 52 |
| 7.1.5 Multi-user MIMO scheme | 52 |
| 7.1.5A Dual layer scheme..... | 52 |
| 7.1.5B Up to 8 layer transmission scheme | 52 |
| 7.1.6 Resource allocation..... | 52 |
| 7.1.6.1 Resource allocation type 0 | 53 |
| 7.1.6.2 Resource allocation type 1 | 53 |
| 7.1.6.3 Resource allocation type 2 | 54 |
| 7.1.6.4 PDSCH starting position | 55 |
| 7.1.6.5 Physical Resource Block (PRB) bundling..... | 57 |
| 7.1.7 Modulation order and transport block size determination | 58 |
| 7.1.7.1 Modulation order determination..... | 58 |
| 7.1.7.2 Transport block size determination | 60 |

| | | |
|-----------|---|-----|
| 7.1.7.2.1 | Transport blocks not mapped to two or more layer spatial multiplexing | 61 |
| 7.1.7.2.2 | Transport blocks mapped to two-layer spatial multiplexing..... | 69 |
| 7.1.7.2.3 | Transport blocks mapped for DCI Format 1C | 69 |
| 7.1.7.2.4 | Transport blocks mapped to three-layer spatial multiplexing..... | 70 |
| 7.1.7.2.5 | Transport blocks mapped to four-layer spatial multiplexing | 71 |
| 7.1.7.3 | Redundancy Version determination for Format 1C | 71 |
| 7.1.8 | Storing soft channel bits | 72 |
| 7.1.9 | PDSCH resource mapping parameters..... | 72 |
| 7.1.10 | Antenna ports quasi co-location for PDSCH | 73 |
| 7.2 | UE procedure for reporting Channel State Information (CSI) | 74 |
| 7.2.1 | Aperiodic CSI Reporting using PUSCH..... | 77 |
| 7.2.2 | Periodic CSI Reporting using PUCCH | 85 |
| 7.2.3 | Channel Quality Indicator (CQI) definition..... | 102 |
| 7.2.4 | Precoding Matrix Indicator (PMI) definition..... | 108 |
| 7.2.5 | Channel-State Information – Reference Signal (CSI-RS) definition | 113 |
| 7.2.6 | Channel-State Information – Interference Measurement (CSI-IM) Resource definition | 114 |
| 7.2.7 | Zero Power CSI-RS Resource definition | 114 |
| 7.3 | UE procedure for reporting HARQ-ACK | 114 |
| 7.3.1 | FDD HARQ-ACK reporting procedure..... | 115 |
| 7.3.2 | TDD HARQ-ACK reporting procedure..... | 115 |
| 7.3.2.1 | TDD HARQ-ACK reporting procedure for same UL/DL configuration | 115 |
| 7.3.2.2 | TDD HARQ-ACK reporting procedure for different UL/DL configurations | 122 |
| 7.3.3 | FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 1..... | 126 |
| 7.3.4 | FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 2..... | 126 |
| 8 | Physical uplink shared channel related procedures | 127 |
| 8.0 | UE procedure for transmitting the physical uplink shared channel..... | 127 |
| 8.0.1 | Single-antenna port scheme | 133 |
| 8.0.2 | Closed-loop spatial multiplexing scheme | 133 |
| 8.1 | Resource allocation for PDCCH/EPDCCH with uplink DCI format | 134 |
| 8.1.1 | Uplink resource allocation type 0..... | 134 |
| 8.1.2 | Uplink resource allocation type 1..... | 134 |
| 8.2 | UE sounding procedure | 135 |
| 8.3 | UE HARQ-ACK procedure..... | 141 |
| 8.4 | UE PUSCH hopping procedure..... | 143 |
| 8.4.1 | Type 1 PUSCH hopping | 144 |
| 8.4.2 | Type 2 PUSCH hopping | 144 |
| 8.5 | UE Reference Symbol (RS) procedure..... | 144 |
| 8.6 | Modulation order, redundancy version and transport block size determination..... | 145 |
| 8.6.1 | Modulation order and redundancy version determination | 145 |
| 8.6.2 | Transport block size determination..... | 146 |
| 8.6.3 | Control information MCS offset determination..... | 148 |
| 8.7 | UE transmit antenna selection | 151 |
| 9 | Physical downlink control channel procedures | 151 |
| 9.1 | UE procedure for determining physical downlink control channel assignment | 151 |
| 9.1.1 | PDCCH assignment procedure | 151 |
| 9.1.2 | PHICH assignment procedure..... | 153 |
| 9.1.3 | Control Format Indicator (CFI) assignment procedure..... | 155 |
| 9.1.4 | EPDCCH assignment procedure | 156 |
| 9.1.4.1 | EPDCCH starting position | 161 |
| 9.1.4.2 | Antenna ports quasi co-location for EPDCCH..... | 162 |
| 9.1.4.3 | Resource mapping parameters for EPDCCH | 162 |
| 9.1.4.4 | PRB-pair indication for EPDCCH | 163 |
| 9.2 | PDCCH/EPDCCH validation for semi-persistent scheduling | 164 |
| 9.3 | PDCCH/EPDCCH control information procedure | 165 |
| 10 | Physical uplink control channel procedures | 166 |
| 10.1 | UE procedure for determining physical uplink control channel assignment..... | 166 |
| 10.1.1 | PUCCH format information..... | 168 |
| 10.1.2 | FDD HARQ-ACK feedback procedures..... | 170 |
| 10.1.2.1 | FDD HARQ-ACK procedure for one configured serving cell..... | 170 |
| 10.1.2.2 | FDD HARQ-ACK procedures for more than one configured serving cell | 172 |

| | | |
|-------------------------------|--|------------|
| 10.1.2.2.1 | PUCCH format 1b with channel selection HARQ-ACK procedure..... | 172 |
| 10.1.2.2.2 | PUCCH format 3 HARQ-ACK procedure | 175 |
| 10.1.3 | TDD HARQ-ACK feedback procedures | 177 |
| 10.1.3.1 | TDD HARQ-ACK procedure for one configured serving cell..... | 179 |
| 10.1.3.2 | TDD HARQ-ACK procedure for more than one configured serving cell..... | 188 |
| 10.1.3.2.1 | PUCCH format 1b with channel selection HARQ-ACK procedure..... | 188 |
| 10.1.3.2.2 | PUCCH format 3 HARQ-ACK procedure | 203 |
| 10.1.3A | FDD-TDD HARQ-ACK feedback procedures for primary cell frame structure type 2 | 211 |
| 10.1.4 | HARQ-ACK Repetition procedure..... | 212 |
| 10.1.5 | Scheduling Request (SR) procedure | 213 |
| 10.2 | Uplink HARQ-ACK timing | 214 |
| 11 | Physical Multicast Channel (PMCH) related procedures..... | 217 |
| 11.1 | UE procedure for receiving the PMCH | 217 |
| 11.2 | UE procedure for receiving MCCH change notification | 217 |
| 12 | Assumptions independent of physical channel..... | 217 |
| 13 | Uplink/Downlink configuration determination procedure for Frame Structure Type 2..... | 217 |
| 13.1 | UE procedure for determining eIMTA-uplink/downlink configuration..... | 218 |
| 14 | UE procedures related to Sidelink..... | 220 |
| 14.1 | Physical Sidelink Shared Channel related procedures..... | 220 |
| 14.1.1 | UE procedure for transmitting the PSSCH | 220 |
| 14.1.1.1 | UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 1 | 221 |
| 14.1.1.1.1 | Determination of subframe indicator bitmap..... | 221 |
| 14.1.1.2 | UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 1..... | 224 |
| 14.1.1.2.1 | PSSCH resource allocation for sidelink transmission mode 1 | 224 |
| 14.1.1.2.2 | PSSCH frequency hopping for sidelink transmission mode 1 | 224 |
| 14.1.1.3 | UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 2..... | 225 |
| 14.1.1.4 | UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 2..... | 226 |
| 14.1.1.5 | UE procedure for PSSCH power control | 226 |
| 14.1.2 | UE procedure for receiving the PSSCH..... | 226 |
| 14.1.3 | UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 2 | 227 |
| 14.2 | Physical Sidelink Control Channel related procedures..... | 228 |
| 14.2.1 | UE procedure for transmitting the PSCCH..... | 228 |
| 14.2.1.1 | UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 1 | 228 |
| 14.2.1.2 | UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 2 | 229 |
| 14.2.1.3 | UE procedure for PSCCH power control | 229 |
| 14.2.2 | UE procedure for receiving the PSCCH | 229 |
| 14.2.3 | UE procedure for determining resource block pool and subframe pool for PSCCH | 230 |
| Annex A (informative): | Change history | 234 |
| History | | 242 |

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies and establishes the characteristics of the physical layer procedures in the FDD and TDD modes of E-UTRA.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
 - [2] 3GPP TS 36.201: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Layer – General Description".
 - [3] 3GPP TS 36.211: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical channels and modulation".
 - [4] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding".
 - [5] 3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer – Measurements".
 - [6] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
 - [7] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
 - [8] 3GPP TS 36.321, "Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification".
 - [9] 3GPP TS 36.423, "Evolved Universal Terrestrial Radio Access (E-UTRA); X2 Application Protocol (X2AP)".
 - [10] 3GPP TS 36.133, "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management".
 - [11] 3GPP TS 36.331, "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) protocol specification".
 - [12] 3GPP TS 36.306: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio access capabilities".
-

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the following symbols apply:

- n_f System frame number as defined in [3]

| | |
|------------------|---|
| n_s | Slot number within a radio frame as defined in [3] |
| N_{cells}^{DL} | Number of configured cells |
| N_{RB}^{DL} | Downlink bandwidth configuration, expressed in units of N_{sc}^{RB} as defined in [3] |
| N_{RB}^{UL} | Uplink bandwidth configuration, expressed in units of N_{sc}^{RB} as defined in [3] |
| N_{symb}^{UL} | Number of SC-FDMA symbols in an uplink slot as defined in [3] |
| N_{sc}^{RB} | Resource block size in the frequency domain, expressed as a number of subcarriers as defined in [3] |
| T_s | Basic time unit as defined in [3] |

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

| | |
|--------|--|
| ACK | Acknowledgement |
| BCH | Broadcast Channel |
| CCE | Control Channel Element |
| CDD | Cyclic Delay Diversity |
| CG | Cell Group |
| CIF | Carrier Indicator Field |
| CQI | Channel Quality Indicator |
| CRC | Cyclic Redundancy Check |
| CSI | Channel State Information |
| CSI-IM | CSI-interference measurement |
| DAI | Downlink Assignment Index |
| DCI | Downlink Control Information |
| DL | Downlink |
| DL-SCH | Downlink Shared Channel |
| DTX | Discontinuous Transmission |
| EPDCCH | Enhanced Physical Downlink Control Channel |
| EPRE | Energy Per Resource Element |
| MCG | Master Cell Group |
| MCS | Modulation and Coding Scheme |
| NACK | Negative Acknowledgement |
| PBCH | Physical Broadcast Channel |
| PCFICH | Physical Control Format Indicator Channel |
| PDCCH | Physical Downlink Control Channel |
| PDSCH | Physical Downlink Shared Channel |
| PHICH | Physical Hybrid ARQ Indicator Channel |
| PMCH | Physical Multicast Channel |
| PMI | Precoding Matrix Indicator |
| PRACH | Physical Random Access Channel |
| PRS | Positioning Reference Signal |
| PRB | Physical Resource Block |
| PSBCH | Physical Sidelink Broadcast Channel |
| PSCCH | Physical Sidelink Control Channel |
| PSCell | Primary Secondary cell |
| PSDCH | Physical Sidelink Discovery Channel |
| PSSCH | Physical Sidelink Shared Channel |
| PSSS | Primary Sidelink Synchronisation Signal |
| PUCCH | Physical Uplink Control Channel |
| PUSCH | Physical Uplink Shared Channel |
| PTI | Precoding Type Indicator |
| RBG | Resource Block Group |
| RE | Resource Element |
| RI | Rank Indication |

| | |
|------------|---|
| RS | Reference Signal |
| SCG | Secondary Cell Group |
| SINR | Signal to Interference plus Noise Ratio |
| SPS C-RNTI | Semi-Persistent Scheduling C-RNTI |
| SR | Scheduling Request |
| SRS | Sounding Reference Symbol |
| SSSS | Secondary Sidelink Synchronisation Signal |
| TAG | Timing Advance Group |
| TBS | Transport Block Size |
| UCI | Uplink Control Information |
| UE | User Equipment |
| UL | Uplink |
| UL-SCH | Uplink Shared Channel |
| VRB | Virtual Resource Block |

4 Synchronization procedures

4.1 Cell search

Cell search is the procedure by which a UE acquires time and frequency synchronization with a cell and detects the physical layer Cell ID of that cell. E-UTRA cell search supports a scalable overall transmission bandwidth corresponding to 6 resource blocks and upwards.

The following signals are transmitted in the downlink to facilitate cell search: the primary and secondary synchronization signals.

A UE may assume the antenna ports 0 – 3 and the antenna port for the primary/secondary synchronization signals of a serving cell are quasi co-located (as defined in [3]) with respect to Doppler shift and average delay.

4.2 Timing synchronization

4.2.1 Radio link monitoring

The downlink radio link quality of the primary cell shall be monitored by the UE for the purpose of indicating out-of-sync/in-sync status to higher layers.

If the UE is configured with a SCG [11], the downlink radio link quality of the PSCell [11] of the SCG shall be monitored by the UE for the purpose of indicating out-of-sync/in-sync status to higher layers.

In non-DRX mode operation, the physical layer in the UE shall every radio frame assess the radio link quality, evaluated over the previous time period defined in [10], against thresholds (Q_{out} and Q_{in}) defined by relevant tests in [10].

In DRX mode operation, the physical layer in the UE shall at least once every DRX period assess the radio link quality, evaluated over the previous time period defined in [10], against thresholds (Q_{out} and Q_{in}) defined by relevant tests in [10].

If higher-layer signalling indicates certain subframes for restricted radio link monitoring, the radio link quality shall not be monitored in any subframe other than those indicated.

The physical layer in the UE shall in radio frames where the radio link quality is assessed indicate out-of-sync to higher layers when the radio link quality is worse than the threshold Q_{out} . When the radio link quality is better than the threshold Q_{in} , the physical layer in the UE shall in radio frames where the radio link quality is assessed indicate in-sync to higher layers.

4.2.2 Inter-cell synchronization

No functionality is specified in this subclause in this release.

4.2.3 Transmission timing adjustments

Upon reception of a timing advance command for a TAG containing the primary cell or PSCell, the UE shall adjust uplink transmission timing for PUCCH/PUSCH/SRS of the primary cell or PSCell based on the received timing advance command.

The UL transmission timing for PUSCH/SRS of a secondary cell is the same as the primary cell if the secondary cell and the primary cell belong to the same TAG. If the primary cell in a TAG has a frame structure type 1 and a secondary cell in the same TAG has a frame structure type 2, UE may assume that $N_{TA} \geq 624$.

If the UE is configured with a SCG, the UL transmission timing for PUSCH/SRS of a secondary cell other than the PSCell is the same as the PSCell if the secondary cell and the PSCell belong to the same TAG.

Upon reception of a timing advance command for a TAG not containing the primary cell or PSCell, if all the serving cells in the TAG have the same frame structure type, the UE shall adjust uplink transmission timing for PUSCH/SRS of all the secondary cells in the TAG based on the received timing advance command where the UL transmission timing for PUSCH/SRS is the same for all the secondary cells in the TAG.

Upon reception of a timing advance command for a TAG not containing the primary cell or PSCell, if a serving cell in the TAG has a different frame structure type compared to the frame structure type of another serving cell in the same TAG, the UE shall adjust uplink transmission timing for PUSCH/SRS of all the secondary cells in the TAG by using $N_{TAoffset} = 624$ regardless of the frame structure type of the serving cells and based on the received timing advance command where the UL transmission timing for PUSCH/SRS is the same for all the secondary cells in the TAG. $N_{TAoffset}$ is described in [3].

The timing advance command for a TAG indicates the change of the uplink timing relative to the current uplink timing for the TAG as multiples of $16 T_s$. The start timing of the random access preamble is specified in [3].

In case of random access response, an 11-bit timing advance command [8], T_A , for a TAG indicates N_{TA} values by index values of $T_A = 0, 1, 2, \dots, 256$ if the UE is configured with a SCG, and $T_A = 0, 1, 2, \dots, 1282$ otherwise, where an amount of the time alignment for the TAG is given by $N_{TA} = T_A \times 16$. N_{TA} is defined in [3].

In other cases, a 6-bit timing advance command [8], T_A , for a TAG indicates adjustment of the current N_{TA} value, $N_{TA,old}$, to the new N_{TA} value, $N_{TA,new}$, by index values of $T_A = 0, 1, 2, \dots, 63$, where $N_{TA,new} = N_{TA,old} + (T_A - 31) \times 16$. Here, adjustment of N_{TA} value by a positive or a negative amount indicates advancing or delaying the uplink transmission timing for the TAG by a given amount respectively.

For a timing advance command received on subframe n , the corresponding adjustment of the uplink transmission timing shall apply from the beginning of subframe $n+6$. For serving cells in the same TAG, when the UE's uplink PUCCH/PUSCH/SRS transmissions in subframe n and subframe $n+1$ are overlapped due to the timing adjustment, the UE shall complete transmission of subframe n and not transmit the overlapped part of subframe $n+1$.

If the received downlink timing changes and is not compensated or is only partly compensated by the uplink timing adjustment without timing advance command as specified in [10], the UE changes N_{TA} accordingly.

4.3 Timing for Secondary Cell Activation / Deactivation

When a UE receives an activation command [8] for a secondary cell in subframe n , the corresponding actions in [8] shall be applied no later than the minimum requirement defined in [10] and no earlier than subframe $n+8$, except for the following:

- the actions related to CSI reporting
- the actions related to the *sCellDeactivationTimer* associated with the secondary cell [8]

which shall be applied in subframe $n+8$.

When a UE receives a deactivation command [8] for a secondary cell or the *sCellDeactivationTimer* associated with the secondary cell expires in subframe n , the corresponding actions in [8] shall apply no later than the minimum requirement defined in [10], except for the actions related to CSI reporting which shall be applied in subframe $n+8$.

5 Power control

Downlink power control determines the Energy Per Resource Element (EPRE). The term resource element energy denotes the energy prior to CP insertion. The term resource element energy also denotes the average energy taken over all constellation points for the modulation scheme applied. Uplink power control determines the average power over a SC-FDMA symbol in which the physical channel is transmitted.

5.1 Uplink power control

Uplink power control controls the transmit power of the different uplink physical channels.

For PUSCH, the transmit power $\hat{P}_{\text{PUSCH},c}(i)$ defined in subclause 5.1.1, is first scaled by the ratio of the number of antennas ports with a non-zero PUSCH transmission to the number of configured antenna ports for the transmission scheme. The resulting scaled power is then split equally across the antenna ports on which the non-zero PUSCH is transmitted.

For PUCCH or SRS, the transmit power $\hat{P}_{\text{PUCCH}}(i)$, defined in subclause 5.1.1.1, or $\hat{P}_{\text{SRS},c}(i)$ is split equally across the configured antenna ports for PUCCH or SRS. $\hat{P}_{\text{SRS},c}(i)$ is the linear value of $P_{\text{SRS},c}(i)$ defined in subclause 5.1.3.

A cell wide overload indicator (OI) and a High Interference Indicator (HII) to control UL interference are defined in [9].

For a serving cell with frame structure type 1, a UE is not expected to be configured with *UplinkPowerControlDedicated-v12x0*.

5.1.1 Physical uplink shared channel

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG.

5.1.1.1 UE behaviour

The setting of the UE Transmit power for a Physical Uplink Shared Channel (PUSCH) transmission is defined as follows.

If the UE transmits PUSCH without a simultaneous PUCCH for the serving cell c , then the UE transmit power $P_{\text{PUSCH},c}(i)$ for PUSCH transmission in subframe i for the serving cell c is given by

$$P_{\text{PUSCH},c}(i) = \min \left\{ P_{\text{CMAX},c}(i), 10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i) \right\} \text{ [dBm]}$$

If the UE transmits PUSCH simultaneous with PUCCH for the serving cell c , then the UE transmit power $P_{\text{PUSCH},c}(i)$ for the PUSCH transmission in subframe i for the serving cell c is given by

$$P_{\text{PUSCH},c}(i) = \min \left\{ 10 \log_{10}(\hat{P}_{\text{CMAX},c}(i) - \hat{P}_{\text{PUCCH}}(i)), 10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i) \right\} \text{ [dBm]}$$

If the UE is not transmitting PUSCH for the serving cell c , for the accumulation of TPC command received with DCI format 3/3A for PUSCH, the UE shall assume that the UE transmit power $P_{\text{PUSCH},c}(i)$ for the PUSCH transmission in subframe i for the serving cell c is computed by

$$P_{\text{PUSCH},c}(i) = \min \left\{ P_{\text{CMAX},c}(i), P_{\text{O_PUSCH},c}(1) + \alpha_c(1) \cdot PL_c + f_c(i) \right\} \quad [\text{dBm}]$$

where,

- $P_{\text{CMAX},c}(i)$ is the configured UE transmit power defined in [6] in subframe i for serving cell c and $\hat{P}_{\text{CMAX},c}(i)$ is the linear value of $P_{\text{CMAX},c}(i)$. If the UE transmits PUCCH without PUSCH in subframe i for the serving cell c , for the accumulation of TPC command received with DCI format 3/3A for PUSCH, the UE shall assume $P_{\text{CMAX},c}(i)$ as given by subclause 5.1.2.1. If the UE does not transmit PUCCH and PUSCH in subframe i for the serving cell c , for the accumulation of TPC command received with DCI format 3/3A for PUSCH, the UE shall compute $P_{\text{CMAX},c}(i)$ assuming MPR=0dB, A-MPR=0dB, P-MPR=0dB and $\Delta T_C = 0\text{dB}$, where MPR, A-MPR, P-MPR and ΔT_C are defined in [6].
- $\hat{P}_{\text{PUCCH}}(i)$ is the linear value of $P_{\text{PUCCH}}(i)$ defined in subclause 5.1.2.1
- $M_{\text{PUSCH},c}(i)$ is the bandwidth of the PUSCH resource assignment expressed in number of resource blocks valid for subframe i and serving cell c .
- If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*,
 - when $j=0$, $P_{\text{O_PUSCH},c}(0) = P_{\text{O_UE_PUSCH},c,2}(0) + P_{\text{O_NOMINAL_PUSCH},c,2}(0)$, where $j=0$ is used for PUSCH (re)transmissions corresponding to a semi-persistent grant. $P_{\text{O_UE_PUSCH},c,2}(0)$ and $P_{\text{O_NOMINAL_PUSCH},c,2}(0)$ are the parameters *p0-UE-PUSCH-Persistent-SubframeSet2-r12* and *p0-NominalPUSCH-Persistent-SubframeSet2-r12* respectively provided by higher layers, for each serving cell c .
 - when $j=1$, $P_{\text{O_PUSCH},c}(1) = P_{\text{O_UE_PUSCH},c,2}(1) + P_{\text{O_NOMINAL_PUSCH},c,2}(1)$, where $j=1$ is used for PUSCH (re)transmissions corresponding to a dynamic scheduled grant. $P_{\text{O_UE_PUSCH},c,2}(1)$ and $P_{\text{O_NOMINAL_PUSCH},c,2}(1)$ are the parameters *p0-UE-PUSCH-SubframeSet2-r12* and *p0-NominalPUSCH-SubframeSet2-r12* respectively, provided by higher layers for serving cell c .
 - when $j=2$, $P_{\text{O_PUSCH},c}(2) = P_{\text{O_UE_PUSCH},c}(2) + P_{\text{O_NOMINAL_PUSCH},c}(2)$ where $P_{\text{O_UE_PUSCH},c}(2) = 0$ and $P_{\text{O_NOMINAL_PUSCH},c}(2) = P_{\text{O_PRE}} + \Delta_{\text{PREAMBLE_Msg3}}$, where the parameter *preambleInitialReceivedTargetPower* [8] ($P_{\text{O_PRE}}$) and $\Delta_{\text{PREAMBLE_Msg3}}$ are signalled from higher layers for serving cell c , where $j=2$ is used for PUSCH (re)transmissions corresponding to the random access response grant.

Otherwise

- $P_{\text{O_PUSCH},c}(j)$ is a parameter composed of the sum of a component $P_{\text{O_NOMINAL_PUSCH},c}(j)$ provided from higher layers for $j=0$ and 1 and a component $P_{\text{O_UE_PUSCH},c}(j)$ provided by higher layers for $j=0$ and 1 for serving cell c . For PUSCH (re)transmissions corresponding to a semi-persistent grant then $j=0$, for PUSCH (re)transmissions corresponding to a dynamic scheduled grant then $j=1$ and for PUSCH (re)transmissions corresponding to the random access response grant then $j=2$. $P_{\text{O_UE_PUSCH},c}(2) = 0$ and $P_{\text{O_NOMINAL_PUSCH},c}(2) = P_{\text{O_PRE}} + \Delta_{\text{PREAMBLE_Msg3}}$, where the parameter *preambleInitialReceivedTargetPower* [8] ($P_{\text{O_PRE}}$) and $\Delta_{\text{PREAMBLE_Msg3}}$ are signalled from higher layers for serving cell c .
- If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*,

- For $j=0$ or 1 , $\alpha_c(j) = \alpha_{c,2} \in \{0, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1\}$. $\alpha_{c,2}$ is the parameter *alpha-SubframeSet2-r12* provided by higher layers for each serving cell c .
- For $j=2$, $\alpha_c(j) = 1$.

Otherwise

- For $j=0$ or 1 , $\alpha_c \in \{0, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1\}$ is a 3-bit parameter provided by higher layers for serving cell c . For $j=2$, $\alpha_c(j) = 1$.
- PL_c is the downlink path loss estimate calculated in the UE for serving cell c in dB and $PL_c = referenceSignalPower - higher\ layer\ filtered\ RSRP$, where *referenceSignalPower* is provided by higher layers and RSRP is defined in [5] for the reference serving cell and the higher layer filter configuration is defined in [11] for the reference serving cell. If serving cell c belongs to a TAG containing the primary cell then, for the uplink of the primary cell, the primary cell is used as the reference serving cell for determining *referenceSignalPower* and higher layer filtered RSRP. For the uplink of the secondary cell, the serving cell configured by the higher layer parameter *pathlossReferenceLinking* defined in [11] is used as the reference serving cell for determining *referenceSignalPower* and higher layer filtered RSRP. If serving cell c belongs to a TAG containing the PSCell then, for the uplink of the PSCell, the PSCell is used as the reference serving cell for determining *referenceSignalPower* and higher layer filtered RSRP; for the uplink of the secondary cell other than PSCell, the serving cell configured by the higher layer parameter *pathlossReferenceLinking* defined in [11] is used as the reference serving cell for determining *referenceSignalPower* and higher layer filtered RSRP. If serving cell c belongs to a TAG not containing the primary cell or PSCell then serving cell c is used as the reference serving cell for determining *referenceSignalPower* and higher layer filtered RSRP.
- $\Delta_{TF,c}(i) = 10 \log_{10} \left(\left(2^{BPRE \cdot K_S} - 1 \right) \cdot \beta_{offset}^{PUSCH} \right)$ for $K_S = 1.25$ and 0 for $K_S = 0$ where K_S is given by the parameter *deltaMCS-Enabled* provided by higher layers for each serving cell c . $BPRE$ and β_{offset}^{PUSCH} , for each serving cell c , are computed as below. $K_S = 0$ for transmission mode 2.
 - $BPRE = O_{CQI} / N_{RE}$ for control data sent via PUSCH without UL-SCH data and $\sum_{r=0}^{C-1} K_r / N_{RE}$ for other cases.
 - where C is the number of code blocks, K_r is the size for code block r , O_{CQI} is the number of CQI/PMI bits including CRC bits and N_{RE} is the number of resource elements determined as $N_{RE} = M_{sc}^{PUSCH-initial} \cdot N_{symb}^{PUSCH-initial}$, where C , K_r , $M_{sc}^{PUSCH-initial}$ and $N_{symb}^{PUSCH-initial}$ are defined in [4].
 - $\beta_{offset}^{PUSCH} = \beta_{offset}^{CQI}$ for control data sent via PUSCH without UL-SCH data and 1 for other cases.
- $\delta_{PUSCH,c}$ is a correction value, also referred to as a TPC command and is included in PDCCH/EPDCCH with DCI format 0/4 for serving cell c or jointly coded with other TPC commands in PDCCH with DCI format 3/3A whose CRC parity bits are scrambled with TPC-PUSCH-RNTI. If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*, the current PUSCH power control adjustment state for serving cell c is given by $f_{c,2}(i)$, and the UE shall use $f_{c,2}(i)$ instead of $f_c(i)$ to determine $P_{PUSCH,c}(i)$. Otherwise, the current PUSCH power control adjustment state for serving cell c is given by $f_c(i)$. $f_{c,2}(i)$ and $f_c(i)$ are defined by:
 - $f_c(i) = f_c(i-1) + \delta_{PUSCH,c}(i - K_{PUSCH})$ and $f_{c,2}(i) = f_{c,2}(i-1) + \delta_{PUSCH,c}(i - K_{PUSCH})$ if accumulation is enabled based on the parameter *Accumulation-enabled* provided by higher layers or if the TPC command $\delta_{PUSCH,c}$ is included in a PDCCH/EPDCCH with DCI format 0 for serving cell c where the CRC is scrambled by the Temporary C-RNTI

- where $\delta_{\text{PUSCH},c}(i - K_{\text{PUSCH}})$ was signalled on PDCCH/EPDCCH with DCI format 0/4 or PDCCH with DCI format 3/3A on subframe $i - K_{\text{PUSCH}}$, and where $f_c(0)$ is the first value after reset of accumulation.
- The value of K_{PUSCH} is
 - For FDD or FDD-TDD and serving cell frame structure type 1, $K_{\text{PUSCH}} = 4$
 - For TDD, if the UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD and serving cell frame structure type 2, the "TDD UL/DL configuration" refers to the UL-reference UL/DL configuration (defined in subclause 8.0) for serving cell c .
 - For TDD UL/DL configurations 1-6, K_{PUSCH} is given in Table 5.1.1.1-1
 - For TDD UL/DL configuration 0
 - If the PUSCH transmission in subframe 2 or 7 is scheduled with a PDCCH/EPDCCH of DCI format 0/4 in which the LSB of the UL index is set to 1, $K_{\text{PUSCH}} = 7$
 - For all other PUSCH transmissions, K_{PUSCH} is given in Table 5.1.1.1-1.
- For serving cell c the UE attempts to decode a PDCCH/EPDCCH of DCI format 0/4 with the UE's C-RNTI or DCI format 0 for SPS C-RNTI and a PDCCH of DCI format 3/3A with this UE's TPC-PUSCH-RNTI in every subframe except when in DRX or where serving cell c is deactivated.
- If DCI format 0/4 for serving cell c and DCI format 3/3A are both detected in the same subframe, then the UE shall use the $\delta_{\text{PUSCH},c}$ provided in DCI format 0/4.
- $\delta_{\text{PUSCH},c} = 0$ dB for a subframe where no TPC command is decoded for serving cell c or where DRX occurs or i is not an uplink subframe in TDD or FDD-TDD and serving cell c frame structure type 2.
- The $\delta_{\text{PUSCH},c}$ dB accumulated values signalled on PDCCH/EPDCCH with DCI format 0/4 are given in Table 5.1.1.1-2. If the PDCCH/EPDCCH with DCI format 0 is validated as a SPS activation or release PDCCH/EPDCCH, then $\delta_{\text{PUSCH},c}$ is 0dB.
- The δ_{PUSCH} dB accumulated values signalled on PDCCH with DCI format 3/3A are one of SET1 given in Table 5.1.1.1-2 or SET2 given in Table 5.1.1.1-3 as determined by the parameter *TPC-Index* provided by higher layers.
- If UE has reached $P_{\text{CMAX},c}(i)$ for serving cell c , positive TPC commands for serving cell c shall not be accumulated
- If UE has reached minimum power, negative TPC commands shall not be accumulated
- If the UE is not configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c , the UE shall reset accumulation
 - For serving cell c , when $P_{\text{O_UE_PUSCH},c}$ value is changed by higher layers
 - For serving cell c , when the UE receives random access response message for serving cell c
- If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c ,
 - the UE shall reset accumulation corresponding to $f_c(*)$ for serving cell c
 - when $P_{\text{O_UE_PUSCH},c}$ value is changed by higher layers

- when the UE receives random access response message for serving cell c
- the UE shall reset accumulation corresponding to $f_{c,2}(*)$ for serving cell c
 - when $P_{O_UE_PUSCH,c,2}$ value is changed by higher layers
- If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and
 - if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12* $f_c(i) = f_c(i-1)$
 - if subframe i does not belong to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12* $f_{c,2}(i) = f_{c,2}(i-1)$
- $f_c(i) = \delta_{PUSCH,c}(i - K_{PUSCH})$ and $f_{c,2}(i) = \delta_{PUSCH,c}(i - K_{PUSCH})$ if accumulation is not enabled for serving cell c based on the parameter *Accumulation-enabled* provided by higher layers
 - where $\delta_{PUSCH,c}(i - K_{PUSCH})$ was signalled on PDCCH/EPDCCH with DCI format 0/4 for serving cell c on subframe $i - K_{PUSCH}$
 - The value of K_{PUSCH} is
 - For FDD or FDD-TDD and serving cell frame structure type 1, $K_{PUSCH} = 4$
 - For TDD, if the UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, or FDD-TDD and serving cell frame structure type 2, the "TDD UL/DL configuration" refers to the UL-reference UL/DL configuration (defined in subclause 8.0) for serving cell c .
 - For TDD UL/DL configurations 1-6, K_{PUSCH} is given in Table 5.1.1.1-1.
 - For TDD UL/DL configuration 0
 - If the PUSCH transmission in subframe 2 or 7 is scheduled with a PDCCH/EPDCCH of DCI format 0/4 in which the LSB of the UL index is set to 1, $K_{PUSCH} = 7$
 - For all other PUSCH transmissions, K_{PUSCH} is given in Table 5.1.1.1-1.
 - The $\delta_{PUSCH,c}$ dB absolute values signalled on PDCCH/EPDCCH with DCI format 0/4 are given in Table 5.1.1.1-2. If the PDCCH/EPDCCH with DCI format 0 is validated as a SPS activation or release PDCCH/EPDCCH, then $\delta_{PUSCH,c}$ is 0dB.
 - $f_c(i) = f_c(i-1)$ and $f_{c,2}(i) = f_{c,2}(i-1)$ for a subframe where no PDCCH/EPDCCH with DCI format 0/4 is decoded for serving cell c or where DRX occurs or i is not an uplink subframe in TDD or FDD-TDD and serving cell c frame structure type 2.
 - If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and
 - if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12* $f_c(i) = f_c(i-1)$
 - if subframe i does not belong to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12* $f_{c,2}(i) = f_{c,2}(i-1)$

- For both types of $f_c(*)$ (accumulation or current absolute) the first value is set as follows:
 - If $P_{O_UE_PUSCH,c}$ value is changed by higher layers and serving cell c is the primary cell or, if $P_{O_UE_PUSCH,c}$ value is received by higher layers and serving cell c is a Secondary cell
 - $f_c(0) = 0$
 - Else
 - If the UE receives the random access response message for a serving cell c
 - $f_c(0) = \Delta P_{rampup,c} + \delta_{msg2,c}$, where
 - $\delta_{msg2,c}$ is the TPC command indicated in the random access response corresponding to the random access preamble transmitted in the serving cell c , see subclause 6.2, and

$$\Delta P_{rampup,c} = \min \left[\left\{ \max \left(0, P_{CMAX,c} - \left(\begin{array}{l} 10 \log_{10}(M_{PUSCH,c}(0)) \\ + P_{O_PUSCH,c}(2) + \delta_{msg2} \\ + \alpha_c(2) \cdot PL + \Delta_{TF,c}(0) \end{array} \right) \right) \right\}, \Delta P_{rampuprequested,c} \right]$$

and $\Delta P_{rampuprequested,c}$ is provided by higher layers and

corresponds to the total power ramp-up requested by higher layers from the first to the last preamble in the serving cell c , $M_{PUSCH,c}(0)$ is the bandwidth of the PUSCH resource assignment expressed in number of resource blocks valid for the subframe of first PUSCH transmission in the serving cell c , and $\Delta_{TF,c}(0)$ is the power adjustment of first PUSCH transmission in the serving cell c .

- If $P_{O_UE_PUSCH,c,2}$ value is received by higher layers for a serving cell c .
 - $f_{c,2}(0) = 0$

Table 5.1.1.1-1: K_{PUSCH} for TDD configuration 0-6

| TDD UL/DL Configuration | subframe number i | | | | | | | | | |
|-------------------------|---------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | - | - | 6 | 7 | 4 | - | - | 6 | 7 | 4 |
| 1 | - | - | 6 | 4 | - | - | - | 6 | 4 | - |
| 2 | - | - | 4 | - | - | - | - | 4 | - | - |
| 3 | - | - | 4 | 4 | 4 | - | - | - | - | - |
| 4 | - | - | 4 | 4 | - | - | - | - | - | - |
| 5 | - | - | 4 | - | - | - | - | - | - | - |
| 6 | - | - | 7 | 7 | 5 | - | - | 7 | 7 | - |

Table 5.1.1.1-2: Mapping of TPC Command Field in DCI format 0/3/4 to absolute and accumulated $\delta_{\text{PUSCH},c}$ values

| TPC Command Field in DCI format 0/3/4 | Accumulated $\delta_{\text{PUSCH},c}$ [dB] | Absolute $\delta_{\text{PUSCH},c}$ [dB] only DCI format 0/4 |
|---------------------------------------|--|---|
| 0 | -1 | -4 |
| 1 | 0 | -1 |
| 2 | 1 | 1 |
| 3 | 3 | 4 |

Table 5.1.1.1-3: Mapping of TPC Command Field in DCI format 3A to accumulated $\delta_{\text{PUSCH},c}$ values

| TPC Command Field in DCI format 3A | Accumulated $\delta_{\text{PUSCH},c}$ [dB] |
|------------------------------------|--|
| 0 | -1 |
| 1 | 1 |

If the UE is not configured with an SCG, and if the total transmit power of the UE would exceed $\hat{P}_{\text{CMAX}}(i)$, the UE scales $\hat{P}_{\text{PUSCH},c}(i)$ for the serving cell c in subframe i such that the condition

$$\sum_c w(i) \cdot \hat{P}_{\text{PUSCH},c}(i) \leq \left(\hat{P}_{\text{CMAX}}(i) - \hat{P}_{\text{PUCCH}}(i) \right)$$

is satisfied where $\hat{P}_{\text{PUCCH}}(i)$ is the linear value of $P_{\text{PUCCH}}(i)$, $\hat{P}_{\text{PUSCH},c}(i)$ is the linear value of $P_{\text{PUSCH},c}(i)$, $\hat{P}_{\text{CMAX}}(i)$ is the linear value of the UE total configured maximum output power P_{CMAX} defined in [6] in subframe i and $w(i)$ is a scaling factor of $\hat{P}_{\text{PUSCH},c}(i)$ for serving cell c where $0 \leq w(i) \leq 1$. In case there is no PUCCH transmission in subframe i $\hat{P}_{\text{PUCCH}}(i) = 0$.

If the UE is not configured with an SCG and if the UE has PUSCH transmission with UCI on serving cell j and PUSCH without UCI in any of the remaining serving cells, and the total transmit power of the UE would exceed $\hat{P}_{\text{CMAX}}(i)$, the UE scales $\hat{P}_{\text{PUSCH},c}(i)$ for the serving cells without UCI in subframe i such that the condition

$$\sum_{c \neq j} w(i) \cdot \hat{P}_{\text{PUSCH},c}(i) \leq \left(\hat{P}_{\text{CMAX}}(i) - \hat{P}_{\text{PUSCH},j}(i) \right)$$

is satisfied where $\hat{P}_{\text{PUSCH},j}(i)$ is the PUSCH transmit power for the cell with UCI and $w(i)$ is a scaling factor of $\hat{P}_{\text{PUSCH},c}(i)$ for serving cell c without UCI. In this case, no power scaling is applied to $\hat{P}_{\text{PUSCH},j}(i)$ unless $\sum_{c \neq j} w(i) \cdot \hat{P}_{\text{PUSCH},c}(i) = 0$ and the total transmit power of the UE still would exceed $\hat{P}_{\text{CMAX}}(i)$.

For a UE not configured with a SCG, note that $w(i)$ values are the same across serving cells when $w(i) > 0$ but for certain serving cells $w(i)$ may be zero.

If the UE is not configured with an SCG, and if the UE has simultaneous PUCCH and PUSCH transmission with UCI on serving cell j and PUSCH transmission without UCI in any of the remaining serving cells, and the total transmit power of the UE would exceed $\hat{P}_{\text{CMAX}}(i)$, the UE obtains $\hat{P}_{\text{PUSCH},c}(i)$ according to

$$\hat{P}_{\text{PUSCH},j}(i) = \min\left(\hat{P}_{\text{PUSCH},j}(i), \left(\hat{P}_{\text{CMAX}}(i) - \hat{P}_{\text{PUCCH}}(i)\right)\right)$$

and

$$\sum_{c \neq j} w(i) \cdot \hat{P}_{\text{PUSCH},c}(i) \leq \left(\hat{P}_{\text{CMAX}}(i) - \hat{P}_{\text{PUCCH}}(i) - \hat{P}_{\text{PUSCH},j}(i) \right)$$

If the UE is not configured with a SCG, and

- If the UE is configured with multiple TAGs, and if the PUCCH/PUSCH transmission of the UE on subframe i for a given serving cell in a TAG overlaps some portion of the first symbol of the PUSCH transmission on subframe $i + 1$ for a different serving cell in another TAG the UE shall adjust its total transmission power to not exceed P_{CMAX} on any overlapped portion.
- If the UE is configured with multiple TAGs, and if the PUSCH transmission of the UE on subframe i for a given serving cell in a TAG overlaps some portion of the first symbol of the PUCCH transmission on subframe $i + 1$ for a different serving cell in another TAG the UE shall adjust its total transmission power to not exceed P_{CMAX} on any overlapped portion.
- If the UE is configured with multiple TAGs, and if the SRS transmission of the UE in a symbol on subframe i for a given serving cell in a TAG overlaps with the PUCCH/PUSCH transmission on subframe i or subframe $i + 1$ for a different serving cell in the same or another TAG the UE shall drop SRS if its total transmission power exceeds P_{CMAX} on any overlapped portion of the symbol.
- If the UE is configured with multiple TAGs and more than 2 serving cells, and if the SRS transmission of the UE in a symbol on subframe i for a given serving cell overlaps with the SRS transmission on subframe i for a different serving cell(s) and with PUSCH/PUCCH transmission on subframe i or subframe $i + 1$ for another serving cell(s) the UE shall drop the SRS transmissions if the total transmission power exceeds P_{CMAX} on any overlapped portion of the symbol.
- If the UE is configured with multiple TAGs, the UE shall, when requested by higher layers, to transmit PRACH in a secondary serving cell in parallel with SRS transmission in a symbol on a subframe of a different serving cell belonging to a different TAG, drop SRS if the total transmission power exceeds P_{CMAX} on any overlapped portion in the symbol.
- If the UE is configured with multiple TAGs, the UE shall, when requested by higher layers, to transmit PRACH in a secondary serving cell in parallel with PUSCH/PUCCH in a different serving cell belonging to a different TAG, adjust the transmission power of PUSCH/PUCCH so that its total transmission power does not exceed P_{CMAX} on the overlapped portion.

5.1.1.2 Power headroom

There are two types of UE power headroom reports defined. A UE power headroom PH is valid for subframe i for serving cell c .

If the UE is configured with a SCG, and if the higher layer parameter *phr-ModeOtherCG-r12* for a CG indicates ‘virtual’, for power headroom reports transmitted on that CG, the UE shall compute PH assuming that it does not transmit PUSCH/PUCCH on any serving cell of the other CG.

If the UE is configured with a SCG,

- For computing power headroom for cells belonging to MCG, the term ‘serving cell’ in this subclause refers to serving cell belonging to the MCG.
- For computing power headroom for cells belonging to SCG, the term ‘serving cell’ in this subclause refers to serving cell belonging to the SCG. The term ‘primary cell’ in this subclause refers to the PCell of the SCG.

Type 1:

If the UE transmits PUSCH without PUCCH in subframe i for serving cell c , power headroom for a Type 1 report is computed using

$$PH_{\text{type1},c}(i) = P_{\text{CMAX},c}(i) - \left\{ 10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i) \right\} \text{ [dB]}$$

where, $P_{\text{CMAX},c}(i)$, $M_{\text{PUSCH},c}(i)$, $P_{\text{O_PUSCH},c}(j)$, $\alpha_c(j)$, PL_c , $\Delta_{\text{TF},c}(i)$ and $f_c(i)$ are defined in subclause 5.1.1.1.

If the UE transmits PUSCH with PUCCH in subframe i for serving cell c , power headroom for a Type 1 report is computed using

$$PH_{\text{type1},c}(i) = \tilde{P}_{\text{CMAX},c}(i) - \left\{ 10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i) \right\} \text{ [dB]}$$

where, $M_{\text{PUSCH},c}(i)$, $P_{\text{O_PUSCH},c}(j)$, $\alpha_c(j)$, PL_c , $\Delta_{\text{TF},c}(i)$ and $f_c(i)$ are defined in subclause 5.1.1.1.

$\tilde{P}_{\text{CMAX},c}(i)$ is computed based on the requirements in [6] assuming a PUSCH only transmission in subframe i . For this case, the physical layer delivers $\tilde{P}_{\text{CMAX},c}(i)$ instead of $P_{\text{CMAX},c}(i)$ to higher layers.

If the UE does not transmit PUSCH in subframe i for serving cell c , power headroom for a Type 1 report is computed using

$$PH_{\text{type1},c}(i) = \tilde{P}_{\text{CMAX},c}(i) - \left\{ P_{\text{O_PUSCH},c}(1) + \alpha_c(1) \cdot PL_c + f_c(i) \right\} \text{ [dB]}$$

where, $\tilde{P}_{\text{CMAX},c}(i)$ is computed assuming MPR=0dB, A-MPR=0dB, P-MPR=0dB and $\Delta T_C = 0$ dB, where MPR, A-MPR, P-MPR and ΔT_C are defined in [6]. $P_{\text{O_PUSCH},c}(1)$, $\alpha_c(1)$, PL_c , and $f_c(i)$ are defined in subclause 5.1.1.1.

Type 2:

If the UE transmits PUSCH simultaneous with PUCCH in subframe i for the primary cell, power headroom for a Type 2 report is computed using

$$PH_{\text{type2}}(i) = P_{\text{CMAX},c}(i) - 10 \log_{10} \left(\frac{10^{(10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i))/10}}{+ 10^{(P_{\text{O_PUCCH}} + PL_c + h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) + \Delta_{\text{F_PUCCH}}(F) + \Delta_{\text{TXD}}(F') + g(i))/10}} \right) \text{ [dB]}$$

where, $P_{\text{CMAX},c}$, $M_{\text{PUSCH},c}(i)$, $P_{\text{O_PUSCH},c}(j)$, $\alpha_c(j)$, $\Delta_{\text{TF},c}(i)$ and $f_c(i)$ are the primary cell parameters as defined in subclause 5.1.1.1 and $P_{\text{O_PUCCH}}$, PL_c , $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}})$, $\Delta_{\text{F_PUCCH}}(F)$, $\Delta_{\text{TXD}}(F')$ and $g(i)$ are defined in subclause 5.1.2.1

If the UE transmits PUSCH without PUCCH in subframe i for the primary cell, power headroom for a Type 2 report is computed using

$$PH_{\text{type2}}(i) = P_{\text{CMAX},c}(i) - 10 \log_{10} \left(\frac{10^{(10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i))/10}}{+ 10^{(P_{\text{O_PUCCH}} + PL_c + g(i))/10}} \right) \text{ [dB]}$$

where, $P_{\text{CMAX},c}(i)$, $M_{\text{PUSCH},c}(i)$, $P_{\text{O_PUSCH},c}(j)$, $\alpha_c(j)$, $\Delta_{\text{TF},c}(i)$ and $f_c(i)$ are the primary cell parameters as defined in subclause 5.1.1.1 and $P_{\text{O_PUCCH}}$, PL_c and $g(i)$ are defined in subclause 5.1.2.1.

If the UE transmits PUCCH without PUSCH in subframe i for the primary cell, power headroom for a Type 2 report is computed using

$$PH_{\text{type2}}(i) = P_{\text{CMAX},c}(i) - 10 \log_{10} \left(\frac{10^{(P_{\text{O_PUSCH},c}(1) + \alpha_c(1) \cdot PL_c + f_c(i))/10}}{+ 10^{(P_{\text{O_PUCCH}} + PL_c + h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) + \Delta_{\text{F_PUCCH}}(F) + \Delta_{\text{TxD}}(F') + g(i))/10}} \right) \text{ [dB]}$$

where, $P_{\text{O_PUSCH},c}(1)$, $\alpha_c(1)$ and $f_c(i)$ are the primary cell parameters as defined in subclause 5.1.1.1, $P_{\text{CMAX},c}(i)$, $P_{\text{O_PUCCH}}$, PL_c , $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}})$, $\Delta_{\text{F_PUCCH}}(F)$, $\Delta_{\text{TxD}}(F')$ and $g(i)$ are also defined in subclause 5.1.2.1.

If the UE does not transmit PUCCH or PUSCH in subframe i for the primary cell, power headroom for a Type 2 report is computed using

$$PH_{\text{type2}}(i) = \tilde{P}_{\text{CMAX},c}(i) - 10 \log_{10} \left(\frac{10^{(P_{\text{O_PUSCH},c}(1) + \alpha_c(1) \cdot PL_c + f_c(i))/10}}{+ 10^{(P_{\text{O_PUCCH}} + PL_c + g(i))/10}} \right) \text{ [dB]}$$

where, $\tilde{P}_{\text{CMAX},c}(i)$ is computed assuming MPR=0dB, A-MPR=0dB, P-MPR=0dB and $\Delta T_C=0$ dB, where MPR, A-MPR, P-MPR and ΔT_C are defined in [6], $P_{\text{O_PUSCH},c}(1)$, $\alpha_c(1)$ and $f_c(i)$ are the primary cell parameters as defined in subclause 5.1.1.1 and $P_{\text{O_PUCCH}}$, PL_c and $g(i)$ are defined in subclause 5.1.2.1.

If the UE is unable to determine whether there is a PUCCH transmission corresponding to PDSCH transmission(s) or not, or which PUCCH resource is used, in subframe i for the primary cell, before generating power headroom for a Type 2 report, upon (E)PDCCH detection, with the following conditions:

- o if both PUCCH format 1b with channel selection and *simultaneousPUCCH-PUSCH* are configured for the UE, or
- o if PUCCH format 1b with channel selection is used for HARQ-ACK feedback for the UE configured with PUCCH format 3 and *simultaneousPUCCH-PUSCH* are configured,

then, UE is allowed to compute power headroom for a Type 2 using

$$PH_{\text{type2}}(i) = P_{\text{CMAX},c}(i) - 10 \log_{10} \left(\frac{10^{(10 \log_{10}(M_{\text{PUSCH},c}(i)) + P_{\text{O_PUSCH},c}(j) + \alpha_c(j) \cdot PL_c + \Delta_{\text{TF},c}(i) + f_c(i))/10}}{+ 10^{(P_{\text{O_PUCCH}} + PL_c + g(i))/10}} \right) \text{ [dB]}$$

where, $P_{\text{CMAX},c}(i)$, $M_{\text{PUSCH},c}(i)$, $P_{\text{O_PUSCH},c}(j)$, $\alpha_c(j)$, $\Delta_{\text{TF},c}(i)$ and $f_c(i)$ are the primary cell parameters as defined in subclause 5.1.1.1 and $P_{\text{O_PUCCH}}$, PL_c and $g(i)$ are defined in subclause 5.1.2.1.

The power headroom shall be rounded to the closest value in the range [40; -23] dB with steps of 1 dB and is delivered by the physical layer to higher layers.

If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*, the UE shall use $f_{c,2}(i)$ instead of $f_c(i)$ to compute $PH_{\text{type1},c}(i)$ and $PH_{\text{type2},c}(i)$ for subframe i and serving cell c , where $f_{c,2}(i)$ is defined in subclause 5.1.1.1.

5.1.2 Physical uplink control channel

If the UE is configured with a SCG, the UE shall apply the procedures described in this subclause for both MCG and SCG.

- When the procedures are applied for MCG, the term ‘serving cell’ in this subclause refers to serving cell belonging to the MCG.

- When the procedures are applied for SCG, the term ‘serving cell’ in this subclause refers to serving cell belonging to the SCG. The term ‘primary cell’ in this subclause refers to the PSCell of the SCG.

5.1.2.1 UE behaviour

If serving cell c is the primary cell, the setting of the UE Transmit power P_{PUCCH} for the physical uplink control channel (PUCCH) transmission in subframe i for serving cell c is defined by

$$P_{\text{PUCCH}}(i) = \min \left\{ P_{\text{CMAX},c}(i), P_{0_PUCCH} + PL_c + h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) + \Delta_{\text{F_PUCCH}}(F) + \Delta_{\text{TxD}}(F') + g(i) \right\} \quad [\text{dBm}]$$

If the UE is not transmitting PUCCH for the primary cell, for the accumulation of TPC command for PUCCH, the UE shall assume that the UE transmit power P_{PUCCH} for PUCCH in subframe i is computed by

$$P_{\text{PUCCH}}(i) = \min \{ P_{\text{CMAX},c}(i), P_{0_PUCCH} + PL_c + g(i) \} \quad [\text{dBm}]$$

where

- $P_{\text{CMAX},c}(i)$ is the configured UE transmit power defined in [6] in subframe i for serving cell c . If the UE transmits PUSCH without PUCCH in subframe i for the serving cell c , for the accumulation of TPC command for PUCCH, the UE shall assume $P_{\text{CMAX},c}(i)$ as given by subclause 5.1.1.1. If the UE does not transmit PUCCH and PUSCH in subframe i for the serving cell c , for the accumulation of TPC command for PUCCH, the UE shall compute $P_{\text{CMAX},c}(i)$ assuming MPR=0dB, A-MPR=0dB, P-MPR=0dB and $\Delta T_C=0$ dB, where MPR, A-MPR, P-MPR and ΔT_C are defined in [6].
- The parameter $\Delta_{\text{F_PUCCH}}(F)$ is provided by higher layers. Each $\Delta_{\text{F_PUCCH}}(F)$ value corresponds to a PUCCH format (F) relative to PUCCH format 1a, where each PUCCH format (F) is defined in Table 5.4-1 of [3].
- If the UE is configured by higher layers to transmit PUCCH on two antenna ports, the value of $\Delta_{\text{TxD}}(F')$ is provided by higher layers where each PUCCH format F' is defined in Table 5.4-1 of [3]; otherwise, $\Delta_{\text{TxD}}(F') = 0$.
- $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}})$ is a PUCCH format dependent value, where n_{CQI} corresponds to the number of information bits for the channel quality information defined in subclause 5.2.3.3 in [4]. $n_{\text{SR}} = 1$ if subframe i is configured for SR for the UE not having any associated transport block for UL-SCH, otherwise $n_{\text{SR}} = 0$. If the UE is configured with more than one serving cell, or the UE is configured with one serving cell and transmitting using PUCCH format 3, the value of n_{HARQ} is defined in subclause 10.1; otherwise, n_{HARQ} is the number of HARQ-ACK bits sent in subframe i .
 - For PUCCH format 1, 1a and 1b $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) = 0$
 - For PUCCH format 1b with channel selection, if the UE is configured with more than one serving cell, $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) = \frac{(n_{\text{HARQ}} - 1)}{2}$, otherwise, $h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) = 0$
 - For PUCCH format 2, 2a, 2b and normal cyclic prefix

$$h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) = \begin{cases} 10 \log_{10} \left(\frac{n_{\text{CQI}}}{4} \right) & \text{if } n_{\text{CQI}} \geq 4 \\ 0 & \text{otherwise} \end{cases}$$

- For PUCCH format 2 and extended cyclic prefix

$$h(n_{\text{CQI}}, n_{\text{HARQ}}, n_{\text{SR}}) = \begin{cases} 10 \log_{10} \left(\frac{n_{\text{CQI}} + n_{\text{HARQ}}}{4} \right) & \text{if } n_{\text{CQI}} + n_{\text{HARQ}} \geq 4 \\ 0 & \text{otherwise} \end{cases}$$

- For PUCCH format 3 and when UE transmits HARQ-ACK/SR without periodic CSI,
- If the UE is configured by higher layers to transmit PUCCH format 3 on two antenna ports, or if the UE transmits more than 11 bits of HARQ-ACK/SR

$$h(n_{CQI}, n_{HARQ}, n_{SR}) = \frac{n_{HARQ} + n_{SR} - 1}{3}$$

- Otherwise

$$h(n_{CQI}, n_{HARQ}, n_{SR}) = \frac{n_{HARQ} + n_{SR} - 1}{2}$$

- For PUCCH format 3 and when UE transmits HARQ-ACK/SR and periodic CSI,
- If the UE is configured by higher layers to transmit PUCCH format 3 on two antenna ports, or if the UE transmits more than 11 bits of HARQ-ACK/SR and CSI

$$h(n_{CQI}, n_{HARQ}, n_{SR}) = \frac{n_{HARQ} + n_{SR} + n_{CQI} - 1}{3}$$

- Otherwise

$$h(n_{CQI}, n_{HARQ}, n_{SR}) = \frac{n_{HARQ} + n_{SR} + n_{CQI} - 1}{2}$$

- P_{O_PUCCH} is a parameter composed of the sum of a parameter $P_{O_NOMINAL_PUCCH}$ provided by higher layers and a parameter $P_{O_UE_PUCCH}$ provided by higher layers.
- δ_{PUCCH} is a UE specific correction value, also referred to as a TPC command, included in a PDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D for the primary cell, or included in an EPDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D for the primary cell, or sent jointly coded with other UE specific PUCCH correction values on a PDCCH with DCI format 3/3A whose CRC parity bits are scrambled with TPC-PUCCH-RNTI.
 - If a UE is not configured for EPDCCH monitoring, the UE attempts to decode a PDCCH of DCI format 3/3A with the UE's TPC-PUCCH-RNTI and one or several PDCCHs of DCI format 1A/1B/1D/1/2A/2/2B/2C/2D with the UE's C-RNTI or SPS C-RNTI on every subframe except when in DRX.
 - If a UE is configured for EPDCCH monitoring, the UE attempts to decode
 - a PDCCH of DCI format 3/3A with the UE's TPC-PUCCH-RNTI and one or several PDCCHs of DCI format 1A/1B/1D/1/2A/2/2B/2C/2D with the UE's C-RNTI or SPS C-RNTI as described in subclause 9.1.1, and
 - one or several EPDCCHs of DCI format 1A/1B/1D/1/2A/2/2B/2C/2D with the UE's C-RNTI or SPS C-RNTI, as described in subclause 9.1.4.
 - If the UE decodes
 - a PDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D or
 - an EPDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D
 for the primary cell and the corresponding detected RNTI equals the C-RNTI or SPS C-RNTI of the UE and the TPC field in the DCI format is not used to determine the PUCCH resource as in subclause 10.1, the UE shall use the δ_{PUCCH} provided in that PDCCH/EPDCCH.

Else

- if the UE decodes a PDCCH with DCI format 3/3A, the UE shall use the δ_{PUCCH} provided in that PDCCH

else the UE shall set $\delta_{PUCCH} = 0$ dB.

- $g(i) = g(i-1) + \sum_{m=0}^{M-1} \delta_{PUCCH}(i-k_m)$ where $g(i)$ is the current PUCCH power control adjustment state and where $g(0)$ is the first value after reset.
- For FDD or FDD-TDD and primary cell frame structure type 1, $M = 1$ and $k_0 = 4$.
- For TDD, values of M and k_m are given in Table 10.1.3.1-1, where the “UL/DL configuration” in Table 10.1.3.1-1 corresponds to the *eimta-HARQ-ReferenceConfig-r12* for the primary cell when the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for the primary cell.
- The δ_{PUCCH} dB values signalled on PDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D or EPDCCH with DCI format 1A/1B/1D/1/2A/2/2B/2C/2D are given in Table 5.1.2.1-1. If the PDCCH with DCI format 1/1A/2/2A/2B/2C/2D or EPDCCH with DCI format 1/1A/2A/2/2B/2C/2D is validated as an SPS activation PDCCH/EPDCCH, or the PDCCH/EPDCCH with DCI format 1A is validated as an SPS release PDCCH/EPDCCH, then δ_{PUCCH} is 0dB.
- The δ_{PUCCH} dB values signalled on PDCCH with DCI format 3/3A are given in Table 5.1.2.1-1 or in Table 5.1.2.1-2 as semi-statically configured by higher layers.
- If $P_{O_UE_PUCCH}$ value is changed by higher layers,
 - $g(0) = 0$
- Else
 - $g(0) = \Delta P_{rampup} + \delta_{msg2}$, where
 - δ_{msg2} is the TPC command indicated in the random access response corresponding to the random access preamble transmitted in the primary cell, see subclause 6.2 and
 - if UE is transmitting PUCCH in subframe i ,

$$\Delta P_{rampup} = \min \left[\left[\max \left(0, P_{CMAX,c} - \left(\begin{array}{c} P_{0_PUCCH} \\ + PL_c + h(n_{CQI}, n_{HARQ}, n_{SR}) \\ + \Delta_{F_PUCCH}(F) + \Delta_{TXD}(F') \end{array} \right) \right) \right], \Delta P_{rampuprequested} \right]$$

Otherwise,

$$\Delta P_{rampup} = \min \left[\left[\max \left(0, P_{CMAX,c} - (P_{0_PUCCH} + PL_c) \right) \right], \Delta P_{rampuprequested} \right] \text{ and } \Delta P_{rampuprequested}$$

is provided by higher layers and corresponds to the total power ramp-up requested by higher layers from the first to the last preamble in the primary cell.

- If UE has reached $P_{CMAX,c}(i)$ for the primary cell, positive TPC commands for the primary cell shall not be accumulated.
- If UE has reached minimum power, negative TPC commands shall not be accumulated.

- UE shall reset accumulation
 - when $P_{O_UE_PUCCH}$ value is changed by higher layers
 - when the UE receives a random access response message for the primary cell
 - $g(i) = g(i-1)$ if i is not an uplink subframe in TDD or FDD-TDD and primary cell frame structure type 2.

Table 5.1.2.1-1: Mapping of TPC Command Field in DCI format 1A/1B/1D/1/2A/2B/2C/2D/2/3 to δ_{PUCCH} values

| TPC Command Field in DCI format 1A/1B/1D/1/2A/2B/2C/2D/2/3 | δ_{PUCCH} [dB] |
|--|-----------------------|
| 0 | -1 |
| 1 | 0 |
| 2 | 1 |
| 3 | 3 |

Table 5.1.2.1-2: Mapping of TPC Command Field in DCI format 3A to δ_{PUCCH} values

| TPC Command Field in DCI format 3A | δ_{PUCCH} [dB] |
|------------------------------------|-----------------------|
| 0 | -1 |
| 1 | 1 |

5.1.3 Sounding Reference Symbol (SRS)

5.1.3.1 UE behaviour

The setting of the UE Transmit power P_{SRS} for the SRS transmitted on subframe i for serving cell c is defined by

$$P_{SRS,c}(i) = \min \left\{ P_{CMAX,c}(i), P_{SRS_OFFSET,c}(m) + 10 \log_{10}(M_{SRS,c}) + P_{O_PUSCH,c}(j) + \alpha_c(j) \cdot PL_c + f_c(i) \right\} \quad [\text{dBm}]$$

where

- $P_{CMAX,c}(i)$ is the configured UE transmit power defined in [6] in subframe i for serving cell c .
- $P_{SRS_OFFSET,c}(m)$ is semi-statically configured by higher layers for $m=0$ and $m=1$ for serving cell c . For SRS transmission given trigger type 0 then $m=0$ and for SRS transmission given trigger type 1 then $m=1$.
- $M_{SRS,c}$ is the bandwidth of the SRS transmission in subframe i for serving cell c expressed in number of resource blocks.
- $f_c(i)$ is the current PUSCH power control adjustment state for serving cell c , see subclause 5.1.1.1.
- $P_{O_PUSCH,c}(j)$ and $\alpha_c(j)$ are parameters as defined in subclause 5.1.1.1 for subframe i , where $j=1$.

If the UE is not configured with an SCG, and if the total transmit power of the UE for the Sounding Reference Symbol in an SC-FDMA symbol would exceed $\hat{P}_{CMAX}(i)$, the UE scales $\hat{P}_{SRS,c}(i)$ for the serving cell c and the SC-FDMA symbol in subframe i such that the condition

$$\sum_c w(i) \cdot \hat{P}_{SRS,c}(i) \leq \hat{P}_{CMAX}(i)$$

is satisfied where $\hat{P}_{\text{SRS},c}(i)$ is the linear value of $P_{\text{SRS},c}(i)$, $\hat{P}_{\text{CMAX}}(i)$ is the linear value of P_{CMAX} defined in [6] in subframe i and $w(i)$ is a scaling factor of $\hat{P}_{\text{SRS},c}(i)$ for serving cell c where $0 < w(i) \leq 1$. Note that $w(i)$ values are the same across serving cells.

If the UE is not configured with an SCG, and if the UE is configured with multiple TAGs and the SRS transmission of the UE in an SC-FDMA symbol for a serving cell in subframe i in a TAG overlaps with the SRS transmission in another SC-FDMA symbol in subframe i for a serving cell in another TAG, and if the total transmit power of the UE for the Sounding Reference Symbol in the overlapped portion would exceed $\hat{P}_{\text{CMAX}}(i)$, the UE scales $\hat{P}_{\text{SRS},c}(i)$ for the serving cell c and each of the overlapped SRS SC-FDMA symbols in subframe i such that the condition

$$\sum_c w(i) \cdot \hat{P}_{\text{SRS},c}(i) \leq \hat{P}_{\text{CMAX}}(i)$$

is satisfied where $\hat{P}_{\text{SRS},c}(i)$ is the linear value of $P_{\text{SRS},c}(i)$, $\hat{P}_{\text{CMAX}}(i)$ is the linear value of P_{CMAX} defined in [6] in subframe i and $w(i)$ is a scaling factor of $\hat{P}_{\text{SRS},c}(i)$ for serving cell c where $0 < w(i) \leq 1$. Note that $w(i)$ values are the same across serving cells.

If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell c and if subframe i belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*, the UE shall use $f_{c,2}(i)$ instead of $f_c(i)$ to determine $P_{\text{SRS},c}(i)$ for subframe i and serving cell c , where $f_{c,2}(i)$ is defined in subclause 5.1.1.1.

5.1.4 Power allocation for dual connectivity

If a UE is configured with multiple cell groups,

- if the UE supports synchronous dual connectivity but does not support asynchronous dual connectivity, or if the UE supports both synchronous dual connectivity and asynchronous dual connectivity and if the higher layer parameter *powerControlMode* indicates dual connectivity power control mode 1
- if the maximum uplink timing difference between transmitted signals to different serving cells including serving cells belonging to different CGs is equal to or less than the minimum requirement for maximum transmission timing difference for synchronous dual connectivity defined in [10]
 - The UE shall use the procedures described in sub clause 5.1.4.1.
 - If a PRACH transmission of the UE on the Pcell starting in subframe $i1$ of MCG overlaps in time domain with another PRACH transmission of the UE starting in subframe $i2$ of SCG, and if subframe $i1$ and subframe $i2$ overlap in time with more than one symbol, and if the total power of both the PRACH transmissions would exceed $\hat{P}_{\text{CMAX}}(i1, i2)$, the UE shall transmit the PRACH on the Pcell using the preamble transmission power P_{PRACH} described in subclause 6.1. The UE may drop or adjust the power of the PRACH transmission in subframe $i2$ of SCG such that the total power does not exceed $\hat{P}_{\text{CMAX}}(i1, i2)$, where $\hat{P}_{\text{CMAX}}(i1, i2)$ is the linear value configured transmitted power for Dual Connectivity for the subframe pair $(i1, i2)$ as described in [6]. If the UE drops the PRACH transmission, it sends power ramping suspension indicator to the higher layers. If the UE adjusts the power of PRACH transmission, it may send power ramping suspension indicator to the higher layers.
- if the UE supports both synchronous dual connectivity and asynchronous dual connectivity and if the higher layer parameter *powerControlMode* does not indicate dual connectivity power control mode 1
 - The UE shall use the procedures described in sub clause 5.1.4.2 .
 - If a PRACH transmission on the Pcell in subframe $i1$ of MCG overlaps in time another PRACH transmission in subframe $i2$ of SCG, and if the time difference between the start of the two PRACH

transmissions is less than $30720 \cdot T_s$, and if the transmission timing of the PRACH on the Pcell (according to subclause 6.1.1) is such that the UE is ready to transmit the PRACH on Pcell at least one subframe before subframe $i1$ of MCG, and if the total power of both the PRACH transmissions exceeds $\hat{P}_{\text{CMAX}}(i1, i2)$, the UE shall transmit the PRACH on the Pcell using the preamble transmission power P_{PRACH} described in subclause 6.1. The UE may drop or adjust the power of the PRACH transmission in subframe $i2$ of SCG such that the total power does not exceed $\hat{P}_{\text{CMAX}}(i1, i2)$, where $\hat{P}_{\text{CMAX}}(i1, i2)$ is the linear value configured transmitted power for Dual Connectivity for the subframe pair $(i1, i2)$ as described in [6]. If the UE drops the PRACH transmissions, it sends power ramping suspension indicator to the higher layers. If the UE adjusts the power of PRACH transmission, it may send power ramping suspension indicator to the higher layers.

5.1.4.1 Dual connectivity power control Mode 1

If the UE PUSCH/PUCCH transmission(s) in subframe $i1$ of CG1 overlap in time with PUSCH/PUCCH transmission(s) in more than one symbol of subframe $i2$ of CG2 or if at least the last symbol the UE PUSCH/PUCCH transmission(s) in subframe $i1$ of CG1 overlap in time with SRS transmission(s) of subframe $i2$, and

- if the UE has a PUCCH/PUSCH transmission with UCI including HARQ-ACK/SR in subframe $i1$ of CG1: If the UE has a PUCCH transmission with UCI including HARQ-ACK/SR in subframe $i1$ of CG1 and if $\hat{P}_{\text{PUCCH_CG1}}(i1)$ would exceed $S1(i1)$, the UE scales $\hat{P}_{\text{PUCCH_CG1}}(i1)$ such that the condition $\alpha1(i1) \cdot \hat{P}_{\text{PUCCH_CG1}}(i1) = \max\{0, S1(i1)\}$ is satisfied where $0 \leq \alpha1(i1) \leq 1$ and $\hat{P}'_{\text{PUCCH_CG1}}(i1) = \alpha1(i1) \cdot \hat{P}_{\text{PUCCH_CG1}}(i1)$. If $\hat{P}_{\text{PUCCH_CG1}}(i1)$ would not exceed $S1(i1)$, $\hat{P}'_{\text{PUCCH_CG1}}(i1) = \hat{P}_{\text{PUCCH_CG1}}(i1)$. If the UE has a PUSCH transmission with UCI including HARQ-ACK in subframe $i1$ of serving cell $c_1 \in \text{CG1}$, and if $\hat{P}_{\text{PUSCH},c_1}(i1)$ would exceed $S1(i1)$, the UE scales $\hat{P}_{\text{PUSCH},c_1}(i1)$ such that the condition $\alpha1(i1) \cdot \hat{P}_{\text{PUSCH},c_1}(i1) = \max\{0, S1(i1)\}$ is satisfied where $0 \leq \alpha1(i1) \leq 1$ and $\hat{P}'_{\text{PUSCH},c_1}(i1) = \alpha1(i1) \cdot \hat{P}_{\text{PUSCH},c_1}(i1)$. If $\hat{P}_{\text{PUSCH},c_1}(i1)$ would not exceed $S1(i1)$, $\hat{P}'_{\text{PUSCH},c_1}(i1) = \hat{P}_{\text{PUSCH},c_1}(i1)$. $S1(i1)$ is determined as follows

$$S1(i1) = \hat{P}_{\text{CMAX}}(i1, i2) - \hat{P}_{u1}(i1) - \hat{P}_{q1}(i2) - \min \left\{ \max \left\{ 0, \hat{P}_{\text{CMAX}}(i1, i2) \cdot \frac{\gamma_{\text{CG2}}}{100} - \hat{P}_{q1}(i2) \right\}, \hat{P}'_{q1}(i2) \right\};$$

where

- $\hat{P}_{u1}(i1) = \hat{P}_{\text{PRACH_CG1}}(i1)$;
- if CG1 is MCG and CG2 is SCG,
 - $\hat{P}_{q1}(i2) = \hat{P}_{\text{PRACH_CG2}}(i2)$;
 - $\hat{P}'_{q1}(i2) = \hat{P}_{\text{PUCCH_CG2}}(i2) + \sum_{c_2 \in \text{CG2}} \left(\hat{P}_{\text{PUSCH},c_2}(i2) + \hat{P}_{\text{SRS},c_2}(i2) \right)$;
- if CG1 is SCG and CG2 is MCG
 - if the UE has a PUCCH transmission with UCI including HARQ-ACK/SR subframe $i2$ of CG2,

- $\hat{P}_{q1}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2);$
- $\hat{P}'_{q1}(i2) = \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\hat{P}}_{SRS,c_2}(i2) \right)$
- else if the UE has a PUSCH transmission with UCI including HARQ-ACK in subframe $i2$ of serving cell $j_2 \in CG2$,
- $\hat{P}_{q1}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUSCH,j_2}(i2);$
- $\hat{P}'_{q1}(i2) = \sum_{c_2 \in CG2, c_2 \neq j_2} \hat{P}_{PUSCH,c_2}(i2) + \sum_{c_2 \in CG2} \hat{\hat{P}}_{SRS,c_2}(i2);$
- otherwise,
- $\hat{P}_{q1}(i2) = \hat{P}_{PRACH_CG2}(i2);$
- $\hat{P}'_{q1}(i2) = \hat{P}_{PUCCH_CG2}(i2) + \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\hat{P}}_{SRS,c_2}(i2) \right)$
- if the UE has a PUCCH/PUSCH transmission with UCI not including HARQ-ACK/SR in subframe $i1$ of CG1:
If the UE has a PUCCH transmission with UCI not including HARQ-ACK/SR in subframe $i1$ of CG1 and if $\hat{P}_{PUCCH_CG1}(i1)$ would exceed $S2(i1)$, the UE scales $\hat{P}_{PUCCH_CG1}(i1)$ such that the condition $\alpha2(i1) \cdot \hat{P}_{PUCCH_CG1}(i1) = \max\{0, S2(i1)\}$ is satisfied where $0 \leq \alpha2(i1) \leq 1$ and $\hat{P}'_{PUCCH_CG1}(i1) = \alpha2(i1) \cdot \hat{P}_{PUCCH_CG1}(i1)$. If $\hat{P}_{PUCCH_CG1}(i1)$ would not exceed $S2(i1)$, $\hat{P}'_{PUCCH_CG1}(i1) = \hat{P}_{PUCCH_CG1}(i1)$. If the UE has a PUSCH transmission with UCI not including HARQ-ACK in subframe $i1$ of serving cell $c_1 \in CG1$, and if $\hat{P}_{PUSCH,c_1}(i1)$ would exceed $S2(i1)$, the UE scales $\hat{P}_{PUSCH,c_1}(i1)$ such that the condition $\alpha2(i1) \cdot \hat{P}_{PUSCH,c_1}(i1) = \max\{0, S2(i1)\}$ is satisfied where $0 \leq \alpha2(i1) \leq 1$ and $\hat{P}'_{PUSCH,c_1}(i1) = \alpha2(i1) \cdot \hat{P}_{PUSCH,c_1}(i1)$. If $\hat{P}_{PUSCH,c_1}(i1)$ would not exceed $S2(i1)$, $\hat{P}'_{PUSCH,c_1}(i1) = \hat{P}_{PUSCH,c_1}(i1)$.
 $S2(i1)$ is determined as follows

$$S2(i1) = \hat{P}_{CMAX}(i1, i2) - \hat{P}_{u2}(i1) - \hat{P}_{q2}(i2) - \min \left\{ \begin{array}{l} 0, \\ \max \left\{ \hat{P}_{CMAX}(i1, i2) \cdot \frac{\gamma_{CG2}}{100} - \hat{P}_{q2}(i2) \right\} \\ \hat{P}'_{q2}(i2) \end{array} \right\}$$

where

- $\hat{P}_{u2}(i1) = \hat{P}_{PRACH_CG1}(i1) + \hat{P}'_{PUCCH_CG1}(i1)$ if the UE has a PUCCH transmission with HARQ-ACK/SR and a PUSCH transmission with UCI not including HARQ-ACK in subframe $i1$ of CG1, otherwise, $\hat{P}_{u2}(i1) = \hat{P}_{PRACH_CG1}(i1)$.
- if CG1 is MCG and CG2 is SCG
 - if the UE has a PUCCH transmission with UCI including HARQ-ACK/SR in subframe $i2$ of CG2,

$$\hat{P}_{q2}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2)$$

$$\hat{P}'_{q2}(i2) = \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\tilde{P}}_{SRS,c_2}(i2) \right);$$

- else if the UE has a PUSCH transmission with UCI including HARQ-ACK in subframe $i2$ of serving cell $j_2 \in CG2$,

$$\hat{P}_{q2}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUSCH,j_2}(i2)$$

$$\hat{P}'_{q2}(i2) = \sum_{c_2 \in CG2, c_2 \neq j_2} \hat{P}_{PUSCH,c_2}(i2) + \sum_{c_2 \in CG2} \hat{\tilde{P}}_{SRS,c_2}(i2);$$

- otherwise,

$$\hat{P}_{q2}(i2) = \hat{P}_{PRACH_CG2}(i2)$$

$$\hat{P}'_{q2}(i2) = \hat{P}_{PUCCH_CG2}(i2) + \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\tilde{P}}_{SRS,c_2}(i2) \right)$$

- if CG1 is SCG and CG2 is MCG

- if the UE has a PUCCH transmission in subframe $i2$ of CG2 and/or a PUSCH transmission with UCI in subframe $i2$ of serving cell $j_2 \in CG2$

$$\hat{P}_{q2}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2) + \hat{P}'_{PUSCH,j_2}(i2)$$

$$\hat{P}'_{q2}(i2) = \sum_{c_2 \in CG2, c_2 \neq j_2} \hat{P}_{PUSCH,c_2}(i2) + \sum_{c_2 \in CG2} \hat{\tilde{P}}_{SRS,c_2}(i2)$$

where, $\hat{P}_{PUCCH_CG2}(i2) = 0$ if the UE does not have a PUCCH transmission in subframe $i2$ of CG2; $\hat{P}_{PUSCH,j_2}(i2) = 0$ if the UE does not have a PUSCH transmission with UCI in subframe $i2$ of CG2;

- otherwise

$$\hat{P}_{q2}(i2) = \hat{P}_{PRACH_CG2}(i2)$$

$$\hat{P}'_{q2}(i2) = \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\tilde{P}}_{SRS,c_2}(i2) \right)$$

- If the UE has PUSCH transmission(s) without UCI in subframe $i1$ of CG1, the UE shall determine

$$S3(i1) = \hat{P}_{CMAX}(i1, i2) - \hat{P}_{u3}(i1) - \hat{P}_{q3}(i2) - \min \left\{ \begin{array}{l} \max \left\{ 0, \hat{P}_{CMAX}(i1, i2) \cdot \frac{\gamma_{CG2}}{100} - \hat{P}_{q3}(i2) \right\} \\ \hat{P}'_{q3}(i2) \end{array} \right\}$$

where

- if the UE has a PUCCH transmission in subframe $i1$ of CG1 and/or a PUSCH transmission with UCI in subframe $i1$ of serving cell $j_1 \in CG1$ $\hat{P}_{u3}(i1) = \hat{P}_{PRACH_CG1}(i1) + \hat{P}'_{PUCCH_CG1}(i1) + \hat{P}'_{PUSCH,j_1}(i1)$, where $\hat{P}_{PUCCH_CG1}(i1) = 0$ if the UE does not have a PUCCH transmission in subframe $i1$ of CG1, $\hat{P}'_{PUSCH,j_1}(i1) = 0$ if the UE does not have a PUSCH transmission with UCI in subframe $i1$ of CG1; otherwise $\hat{P}_{u3}(i1) = \hat{P}_{PRACH_CG1}(i1)$;
- if CG1 is MCG and CG2 is SCG
 - if the UE has a PUCCH transmission in subframe $i2$ of CG2 and/or a PUSCH transmission with UCI in subframe $i2$ of serving cell $j_2 \in CG2$

$$\hat{P}_{q3}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2) + \hat{P}'_{PUSCH,j_2}(i2)$$

$$\hat{P}'_{q3}(i2) = \sum_{c_2 \in CG2, c_2 \neq j_2} \hat{P}_{PUSCH,c_2}(i2) + \sum_{c_2 \in CG2} \hat{\hat{P}}_{SRS,c_2}(i2)$$

where, $\hat{P}_{PUCCH_CG2}(i2) = 0$ if the UE does not have a PUCCH transmission in subframe $i2$ of CG2; $\hat{P}'_{PUSCH,j_2}(i2) = 0$ if the UE does not have a PUSCH transmission with UCI in subframe $i2$ of CG2;

- otherwise

$$\hat{P}_{q3}(i2) = \hat{P}_{PRACH_CG2}(i2)$$

$$\hat{P}'_{q3}(i2) = \sum_{c_2 \in CG2} \left(\hat{P}_{PUSCH,c_2}(i2) + \hat{\hat{P}}_{SRS,c_2}(i2) \right);$$

- if CG1 is SCG and CG2 is MCG

$$\hat{P}_{q3}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2) + \sum_{c_2 \in CG2} \hat{P}'_{PUSCH,c_2}(i2)$$

$$\hat{P}'_{q3}(i2) = \sum_{c_2 \in CG2} \hat{\hat{P}}_{SRS,c_2}(i2);$$

- If the total transmit power of all the PUSCH transmission(s) without UCI in subframe $i1$ of CG1 would exceed $S3(i1)$, the UE scales $\hat{P}_{PUSCH,c_1}(i1)$ for each serving cell $c_1 \in CG1$ with a PUSCH transmission without UCI in subframe $i1$ such that the condition $\sum_{c_1 \in CG1} w(i1) \cdot \hat{P}_{PUSCH,c_1}(i1) \leq \max\{0, S3(i1)\}$ is satisfied, where

$\hat{P}'_{PUSCH,c_1}(i1) = w(i1) \cdot \hat{P}_{PUSCH,c_1}(i1)$, and where $w(i1)$ is a scaling factor of $\hat{P}_{PUSCH,c_1}(i1)$ for serving cell c_1 where $0 \leq w(i1) \leq 1$. Note that $w(i1)$ values are the same across serving cells within a cell group when $w(i1) > 0$ but for certain serving cells within the cell group $w(i1)$ may be zero. If the total transmit power of all the PUSCH transmission(s) without UCI in subframe $i1$ of CG1 would not exceed $S3(i1)$,

$$\hat{P}'_{PUSCH,c_1}(i1) = \hat{P}_{PUSCH,c_1}(i1).$$

where

- $\hat{P}_{\text{CMAX}}(i1, i2)$ is the linear value of configured transmitted power for Dual Connectivity for the subframe pair $(i1, i2)$ as described in [6];
- if CG1 is MCG and CG2 is SCG
 - $\hat{P}_{\text{PUCCH_CG1}}(i1)$ is the linear value of $P_{\text{PUCCH}}(i1)$ corresponding to PUCCH transmission on the primary cell; $\hat{P}_{\text{PUCCH_CG2}}(i2)$ is the linear value of $P_{\text{PUCCH}}(i2)$ corresponding to PUCCH transmission on the PSCell.
 - $\gamma_{\text{CG1}} = \gamma_{\text{MCG}}$;
- if CG1 is SCG and CG2 is MCG;
 - $\hat{P}_{\text{PUCCH_CG1}}(i1)$ is the linear value of $P_{\text{PUCCH}}(i1)$ corresponding to PUCCH transmission on the PSCell; $\hat{P}_{\text{PUCCH_CG2}}(i2)$ is the linear value of $P_{\text{PUCCH}}(i2)$ corresponding to PUCCH transmission on the primary cell.
 - $\gamma_{\text{CG1}} = \gamma_{\text{SCG}}$;
- $\hat{P}_{\text{PUSCH},c_1}(i1)$ is the linear value of $P_{\text{PUSCH},c_1}(i1)$ for subframe $i1$ of serving cell of serving cell $c_1 \in \text{CG1}$, and $\hat{P}_{\text{PUSCH},c_2}(i2)$ is the linear value of $P_{\text{PUSCH},c_2}(i2)$ for subframe $i2$ of serving cell of serving cell $c_2 \in \text{CG2}$.
- γ_{MCG} and γ_{SCG} are given by Table 5.1.4.2-1 according to higher layer parameters p-MeNB and p-SeNB respectively;
- If the UE has a PRACH transmission for CG1 overlapping with subframe $i1$ of CG1, $\hat{P}_{\text{PRACH_CG1}}(i1)$ is the linear value of the transmission power of that PRACH transmission; otherwise, $\hat{P}_{\text{PRACH_CG1}}(i1) = 0$;
- If the UE has a PRACH transmission for CG2 overlapping with subframe $i2$ of CG2, $\hat{P}_{\text{PRACH_CG2}}(i2)$ is the linear value of the transmission power of that PRACH transmission; otherwise, $\hat{P}_{\text{PRACH_CG2}}(i2) = 0$.
- $\hat{\tilde{P}}_{\text{SRS},c_2}(i2)$ is determined as follows
 - if the PUSCH/PUCCH is not transmitted in the last symbol of subframe $i1$ of CG1, or if the UE does not have an SRS transmission in subframe $i2$ of serving cell $c_2 \in \text{CG2}$ or if the UE drops SRS transmission in subframe $i2$ of serving cell $c_2 \in \text{CG2}$ due to collision with PUCCH in subframe $i2$ of serving cell $c_2 \in \text{CG2}$
 - $\hat{\tilde{P}}_{\text{SRS},c_2}(i2) = 0$;
 - if the UE has an SRS transmission and does not have a PUCCH/PUSCH transmission in subframe $i2$ of serving cell $c_2 \in \text{CG2}$
 - $\hat{\tilde{P}}_{\text{SRS},c_2}(i2) = \hat{P}_{\text{SRS},c_2}(i2)$;
 - if the UE has an SRS transmission and has a PUCCH transmission, and does not have a PUSCH transmission in subframe $i2$ of serving cell $c_2 \in \text{CG2}$

$$\hat{\hat{P}}_{SRS,c_2}(i2) = \max \left\{ 0, \hat{P}_{SRS,c_2}(i2) - \hat{P}_{PUCCH_CG2}(i2) \right\}$$

- if the UE has an SRS transmission and a PUSCH transmission, and does not have a PUCCH transmission in subframe $i2$ of serving cell $c_2 \in CG2$

$$\hat{\hat{P}}_{SRS,c_2}(i2) = \max \left\{ 0, \hat{P}_{SRS,c_2}(i2) - \hat{P}_{PUSCH,c_2}(i2) \right\}$$

- if the UE has an SRS transmission and has a PUSCH transmission and a PUCCH transmission in subframe $i2$ of serving cell $c_2 \in CG2$

$$\hat{\hat{P}}_{SRS,c_2}(i2) = \max \left\{ 0, \hat{P}_{SRS,c_2}(i2) - \hat{P}_{PUSCH,c_2}(i2) - \hat{P}_{PUCCH_CG2}(i2) \right\}$$

If the total transmit power for the Sounding Reference Symbol in an SC-FDMA symbol across all the serving cells within a TAG of a cell group CG1 would exceed $S4(i1)$, the UE scales $\hat{P}_{SRS,c_1}(i1)$ for the serving cell

$c_1 \in CG1$ and the SC-FDMA symbol in subframe $i1$ such that the condition $\sum_{c_1 \in CG1} v(i1) \cdot \hat{P}_{SRS,c_1}(i1) \leq S4(i1)$

is satisfied, where $\hat{P}'_{SRS,c_1}(i1) = v(i1) \cdot \hat{P}_{SRS,c_1}(i1)$ is the transmission power of SRS after scaling and where $\hat{P}_{SRS,c_1}(i1)$ is the linear value of $P_{SRS,c_1}(i1)$ described in section 5.1.3.1, and $v(i)$ is a scaling factor of $\hat{P}_{SRS,c_1}(i1)$ for serving cell $c_1 \in CG1$ where $0 < v(i) \leq 1$. Note that $v(i)$ values are the same across serving cells within the same CG.

If the UE is configured with multiple TAGs within CG1 and the SRS transmission of the UE in an SC-FDMA symbol for a serving cell in subframe $i1$ in a TAG belonging to CG1 overlaps with the SRS transmission in another SC-FDMA symbol in subframe $i1$ for a serving cell in another TAG belonging to CG1, and if the total transmit power of the UE for the Sounding Reference Symbol in the overlapped portion would exceed $S4(i1)$, the UE scales $\hat{P}_{SRS,c_1}(i1)$ for the serving cell $c_1 \in CG1$ and each of the overlapped SRS SC-FDMA symbols in subframe $i1$ such that the condition

$\sum_{c_1 \in CG1} v(i1) \cdot \hat{P}_{SRS,c_1}(i1) \leq S4(i1)$ is satisfied, where $\hat{P}'_{SRS,c_1}(i1) = v(i1) \cdot \hat{P}_{SRS,c_1}(i1)$ is the transmission power of

SRS after scaling, and where $v(i1)$ is a scaling factor of $\hat{P}_{SRS,c_1}(i1)$ for serving cell c_1 where $0 \leq v(i1) \leq 1$. Note that $v(i1)$ values are the same across serving cells within a cell group.

$S4(i1)$ is determined as follows

$$S4(i1) = \hat{P}_{CMAX}(i1, i2) - \hat{P}_{q4}(i2) - \min \left\{ \max \left\{ 0, \hat{P}_{CMAX}(i1, i2) \cdot \frac{\gamma_{CG2}}{100} - \hat{P}_{q4}(i2) \right\}, \hat{P}'_{q4}(i2) \right\}$$

where

- if CG1 is MCG and CG2 is SCG

$$\hat{P}_{q4}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2) + \sum_{c_2 \in CG2} \hat{P}'_{PUSCH,c_2}(i2)$$

$$\hat{P}'_{q4}(i2) = \sum_{c_2 \in CG2} \hat{P}_{SRS,c_2}(i2)$$

- if CG1 is SCG and CG2 is MCG

$$\hat{P}_{q4}(i2) = \hat{P}_{PRACH_CG2}(i2) + \hat{P}'_{PUCCH_CG2}(i2) + \sum_{c_2 \in CG2} \hat{P}'_{PUSCH,c_2}(i2) + \sum_{c_2 \in CG2} \hat{P}'_{SRS,c_2}(i2)$$

$$\hat{P}'_{q4}(i2) = 0$$

- if the UE has no PUCCH transmission or has a shortened PUCCH transmission in subframe $i2$ of CG2,

$$\hat{P}'_{PUCCH_CG2}(i2) = 0; \text{ otherwise } \hat{P}'_{PUCCH_CG2}(i2) = \hat{P}_{PUCCH_CG2}(i2)$$

- if the UE has no PUSCH transmission in the last symbol of subframe $i2$ of serving cell $c_2 \in CG2$,

$$\hat{P}'_{PUSCH,c_2}(i2) = 0; \text{ otherwise } \hat{P}'_{PUSCH,c_2}(i2) = \hat{P}_{PUSCH,c_2}(i2)$$

- if the UE has PRACH transmission in CG2 that overlaps with the last symbol of subframe $i2$ of CG2,

$$\hat{P}_{PRACH_CG2}(i2) = \hat{P}_{PRACH_CG2}(i2); \text{ otherwise } \hat{P}_{PRACH_CG2}(i2) = 0$$

For both cell groups

- if the PUCCH/PUSCH transmission of the UE on subframe $i1$ for a given serving cell in a TAG of CG1 overlaps some portion of the first symbol of the PUSCH transmission on subframe $i1 + 1$ for a different serving cell in another TAG of CG1 and/or overlaps with the PUCCH/PUSCH transmission on subframe $i2 + 1$ for a serving cell in another TAG of CG2, the UE shall adjust its total transmission power of all CGs such that the total transmission power of the UE across all CGs does not exceed P_{CMAX} on any overlapped portion.
- if the PUSCH transmission of the UE on subframe $i1$ for a given serving cell in a TAG of CG1 overlaps some portion of the first symbol of the PUCCH transmission on subframe $i1 + 1$ for a different serving cell in another TAG of CG1 and/or overlaps with the PUCCH/PUSCH transmission on subframe $i2 + 1$ for a serving cell in another TAG of CG2, the UE shall adjust its total transmission power of all CGs such that the total transmission power of the UE across all CGs does not exceed P_{CMAX} on any overlapped portion.
- if the SRS transmission of the UE in a symbol on subframe $i1$ for a given serving cell in a TAG of CG1 overlaps with the PUCCH/PUSCH transmission on subframe $i1$ or subframe $i1 + 1$ for a different serving cell in the same or another TAG of CG1 and/or overlaps with the PUCCH/PUSCH transmission on subframe $i2 + 1$ for a serving cell of CG2, the UE shall drop the SRS in CG1 if its total transmission power across all CGs exceeds P_{CMAX} on any overlapped portion of the symbol.
- if the SRS transmission of the UE in a symbol on subframe $i1$ for a given serving cell in CG1 overlaps with the SRS transmission on subframe $i1$ for a different serving cell(s) in CG1 or overlaps with SRS transmission on subframe $i2$ for a serving cell(s) in CG2, and if the SRS transmissions overlap with PUSCH/PUCCH transmission on subframe $i1$ or subframe $i1 + 1$ for another serving cell(s) in CG1, and/or if the SRS transmissions overlap with PUSCH/PUCCH transmission on subframe $i2 + 1$ for a serving cell of CG2, the UE

shall drop the SRS transmissions in CG1 if its total transmission power across all CGs exceeds P_{CMAX} on any overlapped portion of the symbol.

- UE shall, when requested by higher layers, to transmit PRACH on subframe $i1$ or subframe $i1+1$ in a secondary serving cell in CG1 and/or to transmit PRACH on subframe $i2+1$ in a serving cell in CG2 in parallel with SRS transmission in a symbol on subframe $i1$ of a different serving cell belonging to a different TAG of CG1, drop SRS in CG1 if its total transmission power across all CGs exceeds P_{CMAX} on any overlapped portion of the symbol.
- UE shall, when requested by higher layers, to transmit PRACH on subframe $i1+1$ in a secondary serving cell in CG1 and/or to transmit PRACH on subframe $i2+1$ in a serving cell in CG2 in parallel with PUSCH/PUCCH on subframe $i1$ in a different serving cell belonging to a different TAG of CG1, adjust the transmission power of PUSCH/PUCCH in CG1 so that the total transmission power of the UE across all CGs does not exceed P_{CMAX} on the overlapped portion.

5.1.4.2 Dual connectivity power control Mode 2

If subframe $i1$ of CG1 overlaps in time with subframe $i2-1$ and subframe $i2$ of CG2, and if the UE has transmission(s) in subframe $i1$ of CG1,

- if the UE determines based on higher layer signalling that transmission(s) in subframe $i1$ of CG1 cannot overlap in time with transmission(s) in subframe $i2$ of CG2, the UE shall determine

$$\hat{P}_{CG1}^1(i1) = \min \left\{ \begin{array}{l} \hat{P}_{q1}(i1), \\ \hat{P}_{CMAX}(i1, i2-1) - \hat{P}_{PRACH_CG1}(i1) - \hat{P}_{CG2}^1(i2-1) - \hat{P}_{PRACH_CG2}(i2-1) \end{array} \right\}$$

- Otherwise, the UE shall determine

$$\hat{P}_{CG1}^1(i1) = \min \left\{ \begin{array}{l} \hat{P}_{q1}(i1), \\ \hat{P}_{CMAX}(i1, i2-1) - \hat{P}_{PRACH_CG1}(i1) - \max \left\{ \begin{array}{l} \hat{P}_{CMAX}(i1, i2-1) \cdot \frac{\gamma_{CG2}}{100}, \\ \hat{P}_{CG2}^1(i2-1) + \hat{P}_{PRACH_CG2}(i2-1), \\ \hat{P}_{PRACH_CG2}(i2) \end{array} \right\} \end{array} \right\}$$

where,

- $\hat{P}_{q1}(i1) = \hat{P}_{PUCCH_CG1}(i1) + \sum_{c \in CG1} \left(\hat{P}_{PUSCH,c}(i1) + \hat{P}_{SRS,c}(i1) \right)$
- $\hat{P}_{CMAX}(i1, i2-1)$ is the linear value of configured transmitted power for Dual Connectivity for the subframe pair $(i1, i2-1)$, as described in [6];
- $\hat{P}_{PUSCH,c}(i1) = 0$, if the UE does not have a PUSCH transmission in serving cell $c \in CG1$;
- $\hat{P}_{PUCCH_CG1}(i1) = 0$ if the UE does not have a PUCCH transmission in CG1;
- $\hat{P}_{CG2}^1(i2-1) = 0$ if the UE has no transmission of PUCCH, PUSCH, or SRS in subframe $i2-1$ of CG2;

- $\gamma_{CG1} = \gamma_{MCG}$, and $\gamma_{CG2} = \gamma_{SCG}$ if CG1 is MCG and CG2 is SCG;
- $\gamma_{CG1} = \gamma_{SCG}$, and $\gamma_{CG2} = \gamma_{MCG}$, if CG1 is SCG and CG2 is MCG;
- γ_{MCG} and γ_{SCG} are given by Table 5.1.4.2-1 according to higher layer parameters $p\text{-MeNB}$ and $p\text{-SeNB}$ respectively;
- If the UE has a PRACH transmission for CG1 overlapping with subframe $i1$ of CG1, $\hat{P}_{PRACH_CG1}(i1)$ is the linear value of the transmission power of that PRACH transmission; otherwise, $\hat{P}_{PRACH_CG1}(i1) = 0$.
- If the UE has a PRACH transmission for CG2 overlapping with subframe $i2$ of CG2, and if the transmission timing of the PRACH transmission (according to subclause 6.1.1) is such that the UE is ready to transmit the PRACH at least one subframe before subframe $i2$ of CG2, $\hat{P}_{PRACH_CG2}(i2)$ is the linear value of the transmission power of that PRACH transmission; otherwise, $\hat{P}_{PRACH_CG2}(i2) = 0$.
- If the UE has a PRACH transmission for CG2 overlapping with subframe $i2-1$ of CG2, $\hat{P}_{PRACH_CG2}(i2-1)$ is the linear value of the transmission power of that PRACH transmission; otherwise, $\hat{P}_{PRACH_CG2}(i2-1) = 0$.
- $\hat{P}_{SRS,c}(i1)$ is determined as follows
 - if the UE does not have an SRS transmission in subframe $i1$ of serving cell $c \in CG1$ or if the UE drops the SRS transmission in subframe $i1$ of serving cell $c \in CG1$ due to collision with a PUCCH transmission in subframe $i1$ of serving cell $c \in CG1$
 - $\hat{P}_{SRS,c}(i1) = 0$;
 - if the UE has an SRS transmission and does not have a PUCCH/PUSCH transmission in subframe $i1$ of serving cell $c \in CG1$
 - $\hat{P}_{SRS,c}(i1) = \hat{P}_{SRS,c}(i1)$;
 - if the UE has an SRS transmission and a has PUCCH transmission, and does not have a PUSCH transmission in subframe $i1$ of serving cell $c \in CG1$
 - $\hat{P}_{SRS,c}(i1) = \max \left\{ 0, \hat{P}_{SRS,c}(i1) - \hat{P}_{PUCCH_CG1}(i1) \right\}$
 - if the UE has an SRS transmission and a has PUSCH transmission, and does not have a PUCCH transmission in subframe $i1$ of serving cell $c \in CG1$
 - $\hat{P}_{SRS,c}(i1) = \max \left\{ 0, \hat{P}_{SRS,c}(i1) - \hat{P}_{PUSCH,c}(i1) \right\}$
 - if the UE has an SRS transmission and has a PUSCH transmission and a PUCCH transmission in subframe $i1$ of serving cell $c \in CG1$

$$- \hat{\tilde{P}}_{SRS,c}(i1) = \max \left\{ 0, \hat{P}_{SRS,c}(i1) - \hat{P}_{PUSCH,c}(i1) - \hat{P}_{PUCCH_CG1}(i1) \right\}$$

where $\hat{P}_{SRS,c}(i1)$ is the linear value of $P_{SRS,c}(i1)$ described in section 5.1.3.1.

If $\hat{P}_{PUCCH_CG1}(i)$ would exceed $\hat{P}_{CG1}^1(i)$, the UE scales $\hat{P}_{PUCCH_CG1}(i)$ such that the condition $\alpha 1(i) \cdot \hat{P}_{PUCCH_CG1}(i) \leq \hat{P}_{CG1}^1(i)$ is satisfied where

- if CG1 is MCG, $\hat{P}_{PUCCH_CG1}(i)$ is the linear value of $P_{PUCCH}(i)$ corresponding to PUCCH transmission on the primary cell, in case there is no PUCCH transmission in subframe i on the primary cell $\hat{P}_{PUCCH_CG1}(i) = 0$.
 - if CG1 is SCG, $\hat{P}_{PUCCH_CG1}(i)$ is the linear value of $P_{PUCCH}(i)$ corresponding to PUCCH transmission on PSCell, in case there is no PUCCH transmission in subframe i on the PSCell $\hat{P}_{PUCCH_CG1}(i) = 0$.
- $\hat{P}_{PUSCH,c}(i)$ is the linear value of $P_{PUSCH,c}(i)$
- $0 \leq \alpha 1(i) \leq 1$ is a scaling factor of $\hat{P}_{PUCCH_CG1}(i)$.

If the UE has PUSCH transmission with UCI on serving cell $j \in CG1$, and $\hat{P}_{PUSCH,j}(i)$ would exceed $\hat{P}_{CG1}^1(i)$ the UE scales $\hat{P}_{PUSCH,j}(i)$ such that the condition $\alpha 2(i) \cdot \hat{P}_{PUSCH,j}(i) \leq \hat{P}_{CG1}^1(i)$ is satisfied where $\hat{P}_{PUSCH,j}(i)$ is the linear value of the PUSCH transmit power for the cell with UCI, and $0 \leq \alpha 2(i) \leq 1$ is a scaling factor of $\hat{P}_{PUSCH,j}(i)$ for serving cell $j \in CG1$.

If the total transmit power across all the serving cells of a cell group CG1 would exceed $\hat{P}_{CG1}^1(i)$, the UE scales $\hat{P}_{PUSCH,c}(i)$ for the serving cell $c \in CG1$ in subframe i such that the condition $\sum_{c \in CG1} w(i) \cdot \hat{P}_{PUSCH,c}(i) \leq (\hat{P}_{CG1}^1(i) - \hat{P}_{PUCCH_CG1}(i))$ is satisfied; and $w(i)$ is a scaling factor of $\hat{P}_{PUSCH,c}(i)$ for serving cell c where $0 \leq w(i) \leq 1$.

If the UE has PUSCH transmission with UCI on serving cell $j \in CG1$ and PUSCH without UCI in any of the remaining serving cells belonging to CG1, and the total transmit power across all the serving cells of CG1 would exceed $\hat{P}_{CG1}^1(i)$, the UE scales $\hat{P}_{PUSCH,c}(i)$ for the serving cells belonging to CG1 without UCI in subframe i such that the condition $\sum_{c \in CG1, c \neq j} w(i) \cdot \hat{P}_{PUSCH,c}(i) \leq (\hat{P}_{CG1}^1(i) - \hat{P}_{PUSCH,j}(i))$ is satisfied;

where $\hat{P}_{PUSCH,j}(i)$ is the PUSCH transmit power for the cell with UCI and $w(i)$ is a scaling factor of $\hat{P}_{PUSCH,c}(i)$ for serving cell c without UCI. In this case, no power scaling is applied to $\hat{P}_{PUSCH,j}(i)$ unless $\sum_{c \in CG1, c \neq j} w(i) \cdot \hat{P}_{PUSCH,c}(i) = 0$ and the total transmit power across all of the serving cells of the CG1 still would exceed $\hat{P}_{CG1}^1(i)$.

If the UE has simultaneous PUCCH and PUSCH transmission with UCI on serving cell $j \in CG1$ and PUSCH transmission without UCI in any of the remaining serving cells belonging to CG1, and the total transmit power across all the serving cells of the CG1 would exceed $\hat{P}_{CG1}^1(i)$, the UE obtains $\hat{P}_{PUSCH,c}(i)$ according to

$$\hat{P}_{\text{PUSCH},j}(i) = \min\left(\hat{P}_{\text{PUSCH},j}(i), \left(\hat{P}_{\text{CG1}}^1(i) - \hat{P}_{\text{PUCCH_CG1}}(i)\right)\right) \text{ and}$$

$$\sum_{c \in \text{CG1}, c \neq j} w(i) \cdot \hat{P}_{\text{PUSCH},c}(i) \leq \left(\hat{P}_{\text{CG1}}^1(i) - \hat{P}_{\text{PUCCH_CG1}}(i) - \hat{P}_{\text{PUSCH},j}(i)\right)$$

where

- if CG1 is MCG, $\hat{P}_{\text{PUCCH_CG1}}(i)$ is the linear value of $P_{\text{PUCCH}}(i)$ corresponding to PUCCH transmission on the primary cell.
- if CG1 is SCG, $\hat{P}_{\text{PUCCH_CG1}}(i)$ is the linear value of $P_{\text{PUCCH}}(i)$ corresponding to PUCCH transmission on PSCell.

Note that $w(i)$ values are the same across serving cells within a cell group when $w(i) > 0$ but for certain serving cells within the cell group $w(i)$ may be zero.

If the total transmit power for the Sounding Reference Symbol in an SC-FDMA symbol across all the serving cells within a TAG of a cell group CG1 would exceed $\hat{P}_{\text{CG1}}^1(i)$, the UE scales $\hat{P}_{\text{SRS},c}(i)$ for the serving cell $c \in \text{CG1}$ and the SC-FDMA symbol in subframe i such that the condition

$$\sum_{c \in \text{CG1}} v(i) \cdot \hat{P}_{\text{SRS},c}(i) \leq \hat{P}_{\text{CG1}}^1(i)$$

is satisfied where $\hat{P}_{\text{SRS},c}(i)$ is the linear value of $P_{\text{SRS},c}(i)$ described in section 5.1.3.1, and $v(i)$ is a scaling factor of $\hat{P}_{\text{SRS},c}(i)$ for serving cell $c \in \text{CG1}$ where $0 < v(i) \leq 1$. Note that $v(i)$ values are the same across serving cells within the same CG.

If the UE is configured with multiple TAGs within CG1 and the SRS transmission of the UE in an SC-FDMA symbol for a serving cell in subframe i in a TAG belonging to CG1 overlaps with the SRS transmission in another SC-FDMA symbol in subframe i for a serving cell in another TAG belonging to CG1, and if the total transmit power of the UE for the Sounding Reference Symbol in the overlapped portion would exceed $\hat{P}_{\text{CG1}}^1(i)$, the UE scales $\hat{P}_{\text{SRS},c}(i)$ for the serving cell $c \in \text{CG1}$ and each of the overlapped SRS SC-FDMA symbols in subframe i such that the condition

$$\sum_{c \in \text{CG1}} v(i) \cdot \hat{P}_{\text{SRS},c}(i) \leq \hat{P}_{\text{CG1}}^1(i)$$

is satisfied where $\hat{P}_{\text{SRS},c}(i)$ is the linear value of $P_{\text{SRS},c}(i)$ described in section 5.1.3.1, and $v(i)$ is a scaling factor of $\hat{P}_{\text{SRS},c}(i)$ for serving cell $c \in \text{CG1}$ where $0 < v(i) \leq 1$. Note that $v(i)$ values are the same across serving cells within the same CG.

For a cell group CG1

- if the UE is configured with multiple TAGs within CG1, and if the PUCCH/PUSCH transmission of the UE on subframe i for a given serving cell in a TAG of CG1 overlaps some portion of the first symbol of the PUSCH transmission on subframe $i+1$ for a different serving cell in another TAG of CG1, the UE shall adjust its total transmission power of CG1 to not exceed \hat{P}_{CG1}^1 on any overlapped portion.
- if the UE is configured with multiple TAGs within CG1, and if the PUSCH transmission of the UE on subframe i for a given serving cell in a TAG of CG1 overlaps some portion of the first symbol of the PUCCH transmission on subframe $i+1$ for a different serving cell in another TAG of CG1 the UE shall adjust its total transmission power of CG1 to not exceed \hat{P}_{CG1}^1 on any overlapped portion.
- if the UE is configured with multiple TAGs within CG1, and if the SRS transmission of the UE in a symbol on subframe i for a given serving cell in a TAG of CG1 overlaps with the PUCCH/PUSCH transmission on

subframe i or subframe $i+1$ for a different serving cell in the same or another TAG of CG1 the UE shall drop SRS if its total transmission power of CG exceeds \hat{P}_{CG1}^1 on any overlapped portion of the symbol.

- if the UE is configured with multiple TAGs within CG1 and more than 2 serving cells within CG1, and if the SRS transmission of the UE in a symbol on subframe i for a given serving cell in the CG1 overlaps with the SRS transmission on subframe i for a different serving cell(s) in CG1 and with PUSCH/PUCCH transmission on subframe i or subframe $i+1$ for another serving cell(s) in CG1, the UE shall drop the SRS transmissions in CG1 if the total transmission power of CG1 exceeds \hat{P}_{CG1}^1 on any overlapped portion of the symbol.
- if the UE is configured with multiple TAGs within CG1, the UE shall, when requested by higher layers, to transmit PRACH in a secondary serving cell in CG1 in parallel with SRS transmission in a symbol on a subframe of a different serving cell belonging to a different TAG of CG1, drop SRS in CG1 if the total transmission power of CG1 exceeds \hat{P}_{CG1}^1 on any overlapped portion in the symbol.
- if the UE is configured with multiple TAGs within CG1, the UE shall, when requested by higher layers, to transmit PRACH in a secondary serving cell in CG1 in parallel with PUSCH/PUCCH in a different serving cell belonging to a different TAG in CG1, adjust the transmission power of PUSCH/PUCCH in CG1 so that its total transmission power of CG1 does not exceed \hat{P}_{CG1}^1 on the overlapped portion.

Table 5.1.4.2-1: γ_{MCG} (or γ_{SCG}) values for determining power allocation for dual connectivity

| p-MeNB (or p-SeNB) | γ_{MCG} (or γ_{SCG}) Value (in %) |
|-----------------------|--|
| 0 | 0 |
| 1 | 5 |
| 2 | 10 |
| 3 | 15 |
| 4 | 20 |
| 5 | 30 |
| 6 | 37 |
| 7 | 44 |
| 8 | 50 |
| 9 | 56 |
| 10 | 63 |
| 11 | 70 |
| 12 | 80 |
| 13 | 90 |
| 14 | 95 |
| 15 | 100 |

5.2 Downlink power allocation

The eNodeB determines the downlink transmit energy per resource element.

A UE may assume downlink cell-specific RS EPRE is constant across the downlink system bandwidth and constant across all subframes until different cell-specific RS power information is received. The downlink cell-specific reference-signal EPRE can be derived from the downlink reference-signal transmit power given by the parameter *referenceSignalPower* provided by higher layers. The downlink reference-signal transmit power is defined as the linear average over the power contributions (in [W]) of all resource elements that carry cell-specific reference signals within the operating system bandwidth.

The ratio of PDSCH EPRE to cell-specific RS EPRE among PDSCH REs (not applicable to PDSCH REs with zero EPRE) for each OFDM symbol is denoted by either ρ_A or ρ_B according to the OFDM symbol index as given by Table 5.2-2 and Table 5.2-3. In addition, ρ_A and ρ_B are UE-specific.

For a UE in transmission mode 8 - 10 when UE-specific RSs are not present in the PRBs upon which the corresponding PDSCH is mapped or in transmission modes 1 – 7, the UE may assume that for 16 QAM, 64 QAM, or 256QAM, spatial multiplexing with more than one layer or for PDSCH transmissions associated with the multi-user MIMO transmission scheme,

- ρ_A is equal to $\delta_{\text{power-offset}} + P_A + 10\log_{10}(2)$ [dB] when the UE receives a PDSCH data transmission using precoding for transmit diversity with 4 cell-specific antenna ports according to subclause 6.3.4.3 of [3];
- ρ_A is equal to $\delta_{\text{power-offset}} + P_A$ [dB] otherwise

where $\delta_{\text{power-offset}}$ is 0 dB for all PDSCH transmission schemes except multi-user MIMO and where P_A is a UE specific parameter provided by higher layers.

For a UE configured with higher layers parameter *servCellP-a-r12*, and the UE in transmission modes 8-10 when UE-specific RSs are not present in the PRBs upon which the corresponding PDSCH is mapped or in transmission modes 1-7, the UE may assume that for QPSK and transmission with single-antenna port or transmit diversity transmission schemes or spatial multiplexing using a single transmission layer, and the PDSCH transmission is not associated with the multi-user MIMO transmission scheme, and the PDSCH is scheduled by a PDCCH/EPDCCH with CRC scrambled by C-RNTI,

- ρ_A is equal to $P'_A + 10 \cdot \log_{10}(2)$ [dB] when the UE receives a PDSCH data transmission using precoding for transmit diversity with 4 cell-specific antenna ports according to subclause 6.3.4.3 of [3];
- ρ_A is equal to P'_A [dB] otherwise

and where P'_A is given by the parameter *servCellP-a-r12*.

For transmission mode 7, if UE-specific RSs are present in the PRBs upon which the corresponding PDSCH is mapped, the ratio of PDSCH EPRE to UE-specific RS EPRE within each OFDM symbol containing UE-specific RSs shall be a constant, and that constant shall be maintained over all the OFDM symbols containing the UE-specific RSs in the corresponding PRBs. In addition, the UE may assume that for 16QAM, 64QAM, or 256QAM, this ratio is 0 dB.

For transmission mode 8, if UE-specific RSs are present in the PRBs upon which the corresponding PDSCH is mapped, the UE may assume the ratio of PDSCH EPRE to UE-specific RS EPRE within each OFDM symbol containing UE-specific RSs is 0 dB.

For transmission mode 9 or 10, if UE-specific RSs are present in the PRBs upon which the corresponding PDSCH is mapped, the UE may assume the ratio of PDSCH EPRE to UE-specific RS EPRE within each OFDM symbol containing UE-specific RS is 0 dB for number of transmission layers less than or equal to two and -3 dB otherwise.

A UE may assume that downlink positioning reference signal EPRE is constant across the positioning reference signal bandwidth and across all OFDM symbols that contain positioning reference signals in a given positioning reference signal occasion [10].

If CSI-RS is configured in a serving cell then a UE shall assume downlink CSI-RS EPRE is constant across the downlink system bandwidth and constant across all subframes for each CSI-RS resource.

The cell-specific ratio ρ_B / ρ_A is given by Table 5.2-1 according to cell-specific parameter P_B signalled by higher layers and the number of configured eNodeB cell specific antenna ports.

Table 5.2-1: The cell-specific ratio ρ_B / ρ_A for 1, 2, or 4 cell specific antenna ports

| P_B | ρ_B / ρ_A | |
|-------|-------------------|----------------------------|
| | One Antenna Port | Two and Four Antenna Ports |
| 0 | 1 | 5/4 |
| 1 | 4/5 | 1 |
| 2 | 3/5 | 3/4 |
| 3 | 2/5 | 1/2 |

For PMCH with 16QAM, 64QAM, or 256QAM, the UE may assume that the ratio of PMCH EPRE to MBSFN RS EPRE is equal to 0 dB.

Table 5.2-2: OFDM symbol indices within a slot of a non-MBSFN subframe where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_A or ρ_B

| Number of antenna ports | OFDM symbol indices within a slot where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_A | | OFDM symbol indices within a slot where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_B | |
|-------------------------|---|------------------------|---|------------------------|
| | Normal cyclic prefix | Extended cyclic prefix | Normal cyclic prefix | Extended cyclic prefix |
| One or two | 1, 2, 3, 5, 6 | 1, 2, 4, 5 | 0, 4 | 0, 3 |
| Four | 2, 3, 5, 6 | 2, 4, 5 | 0, 1, 4 | 0, 1, 3 |

Table 5.2-3: OFDM symbol indices within a slot of an MBSFN subframe where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_A or ρ_B

| Number of antenna ports | OFDM symbol indices within a slot where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_A | | | | OFDM symbol indices within a slot where the ratio of the corresponding PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_B | | | |
|-------------------------|---|---------------------|------------------------|-------------------|---|-------------------|------------------------|-------------------|
| | Normal cyclic prefix | | Extended cyclic prefix | | Normal cyclic prefix | | Extended cyclic prefix | |
| | $n_s \bmod 2 = 0$ | $n_s \bmod 2 = 1$ | $n_s \bmod 2 = 0$ | $n_s \bmod 2 = 1$ | $n_s \bmod 2 = 0$ | $n_s \bmod 2 = 1$ | $n_s \bmod 2 = 0$ | $n_s \bmod 2 = 1$ |
| One or two | 1, 2, 3, 4, 5, 6 | 0, 1, 2, 3, 4, 5, 6 | 1, 2, 3, 4, 5 | 0, 1, 2, 3, 4, 5 | 0 | - | 0 | - |
| Four | 2, 3, 4, 5, 6 | 0, 1, 2, 3, 4, 5, 6 | 2, 4, 3, 5 | 0, 1, 2, 3, 4, 5 | 0, 1 | - | 0, 1 | - |

5.2.1 eNodeB Relative Narrowband TX Power (RNTP) restrictions

The determination of reported Relative Narrowband TX Power indication $RNTP(n_{PRB})$ is defined as follows:

$$RNTP(n_{PRB}) = \begin{cases} 0 & \text{if } \frac{E_A(n_{PRB})}{E_{\max_nom}^{(p)}} \leq RNTP_{\text{threshold}} \\ 1 & \text{if no promise about the upper limit of } \frac{E_A(n_{PRB})}{E_{\max_nom}^{(p)}} \text{ is made} \end{cases}$$

where $E_A(n_{PRB})$ is the maximum intended EPRE of UE-specific PDSCH REs in OFDM symbols not containing RS in this physical resource block on antenna port p in the considered future time interval; n_{PRB} is the physical resource block number $n_{PRB} = 0, \dots, N_{RB}^{DL} - 1$; $RNTP_{\text{threshold}}$ takes on one of the following values $RNTP_{\text{threshold}} \in \{-\infty, -11, -10, -9, -8, -7, -6, -5, -4, -3, -2, -1, 0, +1, +2, +3\}$ [dB] and

$$E_{\max_nom}^{(p)} = \frac{P_{\max}^{(p)} \cdot \Delta f}{N_{RB}^{DL} \cdot N_{SC}^{RB}}$$

where $P_{\max}^{(p)}$ is the base station maximum output power described in [7], and Δf , N_{RB}^{DL} and N_{SC}^{RB} are defined in [3].

6 Random access procedure

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG

Prior to initiation of the non-synchronized physical random access procedure, Layer 1 shall receive the following information from the higher layers:

- Random access channel parameters (PRACH configuration and frequency position)
- Parameters for determining the root sequences and their cyclic shifts in the preamble sequence set for the primary cell (index to logical root sequence table, cyclic shift (N_{CS}), and set type (unrestricted or restricted set))

6.1 Physical non-synchronized random access procedure

From the physical layer perspective, the L1 random access procedure encompasses the transmission of random access preamble and random access response. The remaining messages are scheduled for transmission by the higher layer on the shared data channel and are not considered part of the L1 random access procedure. A random access channel occupies 6 resource blocks in a subframe or set of consecutive subframes reserved for random access preamble transmissions. The eNodeB is not prohibited from scheduling data in the resource blocks reserved for random access channel preamble transmission.

The following steps are required for the L1 random access procedure:

- Layer 1 procedure is triggered upon request of a preamble transmission by higher layers.
- A preamble index, a target preamble received power (PREAMBLE_RECEIVED_TARGET_POWER), a corresponding RA-RNTI and a PRACH resource are indicated by higher layers as part of the request.
- A preamble transmission power P_{PRACH} is determined as $P_{PRACH} = \min\{ P_{CMAX,c}(i), PREAMBLE_RECEIVED_TARGET_POWER + PL_c \}$ [dBm], where $P_{CMAX,c}(i)$ is the configured UE transmit power defined in [6] for subframe i of serving cell c and PL_c is the downlink path loss estimate calculated in the UE for serving cell c .
- A preamble sequence is selected from the preamble sequence set using the preamble index.
- A single preamble is transmitted using the selected preamble sequence with transmission power P_{PRACH} on the indicated PRACH resource.
- Detection of a PDCCH with the indicated RA-RNTI is attempted during a window controlled by higher layers (see [8], subclause 5.1.4). If detected, the corresponding DL-SCH transport block is passed to higher layers. The higher layers parse the transport block and indicate the 20-bit uplink grant to the physical layer, which is processed according to subclause 6.2.

6.1.1 Timing

For the L1 random access procedure, UE's uplink transmission timing after a random access preamble transmission is as follows.

- a) If a PDCCH with associated RA-RNTI is detected in subframe n , and the corresponding DL-SCH transport block contains a response to the transmitted preamble sequence, the UE shall, according to the information in the response, transmit an UL-SCH transport block in the first subframe $n + k_1$, $k_1 \geq 6$, if the UL delay field in subclause 6.2 is set to zero where $n + k_1$ is the first available UL subframe for PUSCH transmission, where for TDD serving cell, the first UL subframe for PUSCH transmission is determined based on the UL/DL configuration (i.e., the

parameter *subframeAssignment*) indicated by higher layers. The UE shall postpone the PUSCH transmission to the next available UL subframe after $n + k_1$ if the field is set to 1.

- b) If a random access response is received in subframe n , and the corresponding DL-SCH transport block does not contain a response to the transmitted preamble sequence, the UE shall, if requested by higher layers, be ready to transmit a new preamble sequence no later than in subframe $n + 5$.
- c) If no random access response is received in subframe n , where subframe n is the last subframe of the random access response window, the UE shall, if requested by higher layers, be ready to transmit a new preamble sequence no later than in subframe $n + 4$.

In case a random access procedure is initiated by a "PDCCH order" in subframe n , the UE shall, if requested by higher layers, transmit random access preamble in the first subframe $n + k_2$, $k_2 \geq 6$, where a PRACH resource is available.

If a UE is configured with multiple TAGs, and if the UE is configured with the carrier indicator field for a given serving cell, the UE shall use the carrier indicator field value from the detected "PDCCH order" to determine the serving cell for the corresponding random access preamble transmission.

6.2 Random Access Response Grant

The higher layers indicate the 20-bit UL Grant to the physical layer, as defined in 3GPP TS 36.321 [8].

This is referred to the Random Access Response Grant in the physical layer.

The content of these 20 bits starting with the MSB and ending with the LSB are as follows:

- Hopping flag – 1 bit
- Fixed size resource block assignment – 10 bits
- Truncated modulation and coding scheme – 4 bits
- TPC command for scheduled PUSCH – 3 bits
- UL delay – 1 bit
- CSI request – 1 bit

The UE shall use the single-antenna port uplink transmission scheme for the PUSCH transmission corresponding to the Random Access Response Grant and the PUSCH retransmission for the same transport block.

The UE shall perform PUSCH frequency hopping if the single bit frequency hopping (FH) field in a corresponding Random Access Response Grant is set as 1 and the uplink resource block assignment is type 0, otherwise no PUSCH frequency hopping is performed. When the hopping flag is set, the UE shall perform PUSCH hopping as indicated via the fixed size resource block assignment detailed below.

The fixed size resource block assignment field is interpreted as follows:

if $N_{RB}^{UL} \leq 44$

Truncate the fixed size resource block assignment to its b least significant bits, where

$b = \left\lceil \log_2 \left(N_{RB}^{UL} \cdot (N_{RB}^{UL} + 1) / 2 \right) \right\rceil$, and interpret the truncated resource block assignment according to the rules for a regular DCI format 0

else

Insert b most significant bits with value set to '0' after the N_{UL_hop} hopping bits in the fixed size resource block assignment, where the number of hopping bits N_{UL_hop} is zero when the hopping flag bit is not set to 1, and is defined in Table 8.4-1 when the hopping flag bit is set to 1, and $b = \left(\left\lceil \log_2 \left(N_{RB}^{UL} \cdot (N_{RB}^{UL} + 1) / 2 \right) \right\rceil - 10 \right)$, and interpret the expanded resource block assignment according to the rules for a regular DCI format 0

end if

The truncated modulation and coding scheme field is interpreted such that the modulation and coding scheme corresponding to the Random Access Response grant is determined from MCS indices 0 through 15 in Table 8.6.1-1.

The TPC command δ_{msg2} shall be used for setting the power of the PUSCH, and is interpreted according to Table 6.2-1.

Table 6.2-1: TPC Command δ_{msg2} for Scheduled PUSCH

| TPC Command | Value (in dB) |
|-------------|---------------|
| 0 | -6 |
| 1 | -4 |
| 2 | -2 |
| 3 | 0 |
| 4 | 2 |
| 5 | 4 |
| 6 | 6 |
| 7 | 8 |

In non-contention based random access procedure, the CSI request field is interpreted to determine whether an aperiodic CQI, PMI, and RI report is included in the corresponding PUSCH transmission according to subclause 7.2.1. In contention based random access procedure, the CSI request field is reserved.

The UL delay applies for TDD, FDD and FDD-TDD and this field can be set to 0 or 1 to indicate whether the delay of PUSCH is introduced as shown in subclause 6.1.1.

7 Physical downlink shared channel related procedures

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG unless stated otherwise

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, and ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell or serving cells belonging to the MCG respectively unless stated otherwise. The terms ‘subframe’ and ‘subframes’ refer to subframe or subframes belonging to MCG.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’ and ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including the PSCell), serving cell, serving cells belonging to the SCG respectively unless stated otherwise. The term ‘primary cell’ in this clause refers to the PSCell of the SCG. The terms ‘subframe’ and ‘subframes’ refer to subframe or subframes belonging to SCG.

For FDD, there shall be a maximum of 8 downlink HARQ processes per serving cell.

For FDD-TDD and primary cell frame structure type 1, there shall be a maximum of 8 downlink HARQ processes per serving cell.

For TDD and a UE not configured with the parameter *EIMTA-MainConfigServCell-r12* for any serving cell, if the UE is configured with one serving cell, or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same, the maximum number of downlink HARQ processes per serving cell shall be determined by the UL/DL configuration (Table 4.2-2 of [3]), as indicated in Table 7-1.

For TDD, if a UE is configured with more than one serving cell and if the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD and primary cell frame structure type 2 and serving cell frame structure type 2, the maximum number of downlink HARQ processes for a serving cell shall be determined as indicated in Table 7-1, wherein the "TDD UL/DL configuration" in Table 7-1 refers to the DL-reference UL/DL configuration for the serving cell (as defined in subclause 10.2).

For FDD-TDD and primary cell frame structure type 2 and serving cell frame structure type 1, the maximum number of downlink HARQ processes for the serving cell shall be determined by the DL-reference UL/DL configuration for the serving cell (as defined in subclause 10.2), as indicated in Table 7-2.

The dedicated broadcast HARQ process defined in [8] is not counted as part of the maximum number of HARQ processes for FDD, TDD and FDD-TDD.

Table 7-1: Maximum number of DL HARQ processes for TDD

| TDD UL/DL configuration | Maximum number of HARQ processes |
|-------------------------|----------------------------------|
| 0 | 4 |
| 1 | 7 |
| 2 | 10 |
| 3 | 9 |
| 4 | 12 |
| 5 | 15 |
| 6 | 6 |

Table 7-2: Maximum number of DL HARQ processes for FDD-TDD, primary cell frame structure type 2, and serving cell frame structure type 1

| DL-reference UL/DL Configuration | Maximum number of HARQ processes |
|----------------------------------|----------------------------------|
| 0 | 10 |
| 1 | 11 |
| 2 | 12 |
| 3 | 15 |
| 4 | 16 |
| 5 | 16 |
| 6 | 12 |

7.1 UE procedure for receiving the physical downlink shared channel

Except the subframes indicated by the higher layer parameter *mbsfn-SubframeConfigList* or by *mbsfn-SubframeConfigList-v12x0* of serving cell *c*, a UE shall

- upon detection of a PDCCH of the serving cell with DCI format 1, 1A, 1B, 1C, 1D, 2, 2A, 2B, 2C, or 2D intended for the UE in a subframe, or
- upon detection of an EPDCCH of the serving cell with DCI format 1, 1A, 1B, 1D, 2, 2A, 2B, 2C, or 2D intended for the UE in a subframe

decode the corresponding PDSCH in the same subframe with the restriction of the number of transport blocks defined in the higher layers.

If a UE is configured with more than one serving cell and if the frame structure type of any two configured serving cells is different, then the UE is considered to be configured for FDD-TDD carrier aggregation.

Except for MBMS reception, the UE is not required to monitor PDCCH with CRC scrambled by the SI-RNTI on the PSCell.

A UE may assume that positioning reference signals are not present in resource blocks in which it shall decode PDSCH according to a detected PDCCH with CRC scrambled by the SI-RNTI or P-RNTI with DCI format 1A or 1C intended for the UE.

A UE configured with the carrier indicator field for a given serving cell shall assume that the carrier indicator field is not present in any PDCCH of the serving cell in the common search space that is described in subclause 9.1. Otherwise, the configured UE shall assume that for the given serving cell the carrier indicator field is present in PDCCH/EPDCCH located in the UE specific search space described in subclause 9.1 when the PDCCH/EPDCCH CRC is scrambled by C-RNTI or SPS C-RNTI.

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the SI-RNTI, the UE shall decode the PDCCH and the corresponding PDSCH according to any of the combinations defined in Table 7.1-1. The scrambling initialization of PDSCH corresponding to these PDCCHs is by SI-RNTI.

Table 7.1-1: PDCCH and PDSCH configured by SI-RNTI

| DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|---------------|--------------|--|
| DCI format 1C | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2). |
| DCI format 1A | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2). |

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the P-RNTI, the UE shall decode the PDCCH and the corresponding PDSCH according to any of the combinations defined in Table 7.1-2. The scrambling initialization of PDSCH corresponding to these PDCCHs is by P-RNTI.

The UE is not required to monitor PDCCH with CRC scrambled by the P-RNTI on the PSCell.

Table 7.1-2: PDCCH and PDSCH configured by P-RNTI

| DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|---------------|--------------|---|
| DCI format 1C | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| DCI format 1A | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the RA-RNTI, the UE shall decode the PDCCH and the corresponding PDSCH according to any of the combinations defined in Table 7.1-3. The scrambling initialization of PDSCH corresponding to these PDCCHs is by RA-RNTI.

When RA-RNTI and either C-RNTI or SPS C-RNTI are assigned in the same subframe, the UE is not required to decode a PDSCH on the primary cell indicated by a PDCCH/EPDCCH with a CRC scrambled by C-RNTI or SPS C-RNTI.

Table 7.1-3: PDCCH and PDSCH configured by RA-RNTI

| DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|---------------|--------------|---|
| DCI format 1C | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| DCI format 1A | Common | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |

The UE is semi-statically configured via higher layer signalling to receive PDSCH data transmissions signalled via PDCCH/EPDCCH according to one of the transmission modes, denoted mode 1 to mode 10.

For frame structure type 1,

- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 5 in any subframe in which the number of OFDM symbols for PDCCH with normal CP is equal to four;
- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 5, 7, 8, 9, 10, 11, 12, 13 or 14 in the two PRBs to which a pair of VRBs is mapped if either one of the two PRBs overlaps in frequency with a transmission of either PBCH or primary or secondary synchronization signals in the same subframe;
- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 7 for which distributed VRB resource allocation is assigned.

- The UE may skip decoding the transport block(s) if it does not receive all assigned PDSCH resource blocks. If the UE skips decoding, the physical layer indicates to higher layer that the transport block(s) are not successfully decoded.

For frame structure type 2,

- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 5 in any subframe in which the number of OFDM symbols for PDCCH with normal CP is equal to four;
- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 5 in the two PRBs to which a pair of VRBs is mapped if either one of the two PRBs overlaps in frequency with a transmission of PBCH in the same subframe;
- the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 7, 8, 9, 10, 11, 12, 13 or 14 in the two PRBs to which a pair of VRBs is mapped if either one of the two PRBs overlaps in frequency with a transmission of primary or secondary synchronization signals in the same subframe;
- with normal CP configuration, the UE is not expected to receive PDSCH on antenna port 5 for which distributed VRB resource allocation is assigned in the special subframe with configuration #1 or #6;
- the UE is not expected to receive PDSCH on antenna port 7 for which distributed VRB resource allocation is assigned;
- with normal cyclic prefix, the UE is not expected to receive PDSCH resource blocks transmitted on antenna port 5 in DwPTS when the UE is configured with special subframe configuration 9.
- The UE may skip decoding the transport block(s) if it does not receive all assigned PDSCH resource blocks. If the UE skips decoding, the physical layer indicates to higher layer that the transport block(s) are not successfully decoded.

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the C-RNTI, the UE shall decode the PDCCH and any corresponding PDSCH according to the respective combinations defined in Table 7.1-5. The scrambling initialization of PDSCH corresponding to these PDCCHs is by C-RNTI.

If a UE is configured by higher layers to decode EPDCCH with CRC scrambled by the C-RNTI, the UE shall decode the EPDCCH and any corresponding PDSCH according to the respective combinations defined in Table 7.1-5A. The scrambling initialization of PDSCH corresponding to these EPDCCHs is by C-RNTI.

If the UE is configured with the carrier indicator field for a given serving cell and, if the UE is configured by higher layers to decode PDCCH/EPDCCH with CRC scrambled by the C-RNTI, then the UE shall decode PDSCH of the serving cell indicated by the carrier indicator field value in the decoded PDCCH/EPDCCH.

When a UE configured in transmission mode 3, 4, 8, 9 or 10 receives a DCI Format 1A assignment, it shall assume that the PDSCH transmission is associated with transport block 1 and that transport block 2 is disabled.

When a UE is configured in transmission mode 7, scrambling initialization of UE-specific reference signals corresponding to these PDCCHs/EPDCCHs is by C-RNTI.

The UE does not support transmission mode 8 if extended cyclic prefix is used in the downlink.

When a UE is configured in transmission mode 9 or 10, in the downlink subframes indicated by the higher layer parameter *mbsfn-SubframeConfigList* or by *mbsfn-SubframeConfigList-v12x0* of serving cell *c* except in subframes for the serving cell

- indicated by higher layers to decode PMCH or,
- configured by higher layers to be part of a positioning reference signal occasion and the positioning reference signal occasion is only configured within MBSFN subframes and the cyclic prefix length used in subframe #0 is normal cyclic prefix,

the UE shall upon detection of a PDCCH with CRC scrambled by the C-RNTI with DCI format 1A/2C/2D intended for the UE or, upon detection of an EPDCCH with CRC scrambled by the C-RNTI with DCI format 1A/2C/2D intended for the UE, decode the corresponding PDSCH in the same subframe.

A UE configured in transmission mode 10 can be configured with scrambling identities, $n_{ID}^{DMRS,i}$, $i = 0,1$ by higher layers for UE-specific reference signal generation as defined in subclause 6.10.3.1 of [3] to decode PDSCH according to a detected PDCCH/EPDCCH with CRC scrambled by the C-RNTI with DCI format 2D intended for the UE.

Table 7.1-5: PDCCH and PDSCH configured by C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|-------------------|---------------|----------------------------------|--|
| Mode 1 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| Mode 2 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 3 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2A | UE specific by C-RNTI | Large delay CDD (see subclause 7.1.3) or Transmit diversity (see subclause 7.1.2) |
| Mode 4 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2 | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 7.1.4) or Transmit diversity (see subclause 7.1.2) |
| Mode 5 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1D | UE specific by C-RNTI | Multi-user MIMO (see subclause 7.1.5) |
| Mode 6 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1B | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 7.1.4) using a single transmission layer |
| Mode 7 | DCI format 1A | Common and UE specific by C-RNTI | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| Mode 8 | DCI format 1A | Common and UE specific by C-RNTI | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| | DCI format 2B | UE specific by C-RNTI | Dual layer transmission, port 7 and 8 (see subclause 7.1.5A) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 9 | DCI format 1A | Common and UE specific by C-RNTI | <ul style="list-style-type: none"> Non-MBSFN subframe: If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) MBSFN subframe: Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2C | UE specific by C-RNTI | Up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 10 | DCI format 1A | Common and UE specific by C-RNTI | <ul style="list-style-type: none"> Non-MBSFN subframe: If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) MBSFN subframe: Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2D | UE specific by C-RNTI | Up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |

Table 7.1-5A: EPDCCH and PDSCH configured by C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PDSCH corresponding to EPDCCH |
|-------------------|---------------|-----------------------|--|
| Mode 1 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| Mode 2 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 3 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2A | UE specific by C-RNTI | Large delay CDD (see subclause 7.1.3) or Transmit diversity (see subclause 7.1.2) |
| Mode 4 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2 | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 7.1.4) or Transmit diversity (see subclause 7.1.2) |
| Mode 5 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1D | UE specific by C-RNTI | Multi-user MIMO (see subclause 7.1.5) |
| Mode 6 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1B | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 7.1.4) using a single transmission layer |
| Mode 7 | DCI format 1A | UE specific by C-RNTI | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| Mode 8 | DCI format 1A | UE specific by C-RNTI | If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| | DCI format 2B | UE specific by C-RNTI | Dual layer transmission, port 7 and 8 (see subclause 7.1.5A) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 9 | DCI format 1A | UE specific by C-RNTI | <ul style="list-style-type: none"> Non-MBSFN subframe: If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) MBSFN subframe: Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2C | UE specific by C-RNTI | Up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 10 | DCI format 1A | UE specific by C-RNTI | <ul style="list-style-type: none"> Non-MBSFN subframe: If the number of PBCH antenna ports is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) MBSFN subframe: Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2D | UE specific by C-RNTI | Up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) or single-antenna port, port 7 or 8 (see subclause 7.1.1) |

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the SPS C-RNTI, the UE shall decode the PDCCH on the primary cell and any corresponding PDSCH on the primary cell according to the respective combinations defined in Table 7.1-6. The same PDSCH related configuration applies in the case that a PDSCH is transmitted without a corresponding PDCCH. The scrambling initialization of PDSCH corresponding to these PDCCHs and PDSCH without a corresponding PDCCH is by SPS C-RNTI.

If a UE is configured by higher layers to decode EPDCCH with CRC scrambled by the SPS C-RNTI, the UE shall decode the EPDCCH on the primary cell and any corresponding PDSCH on the primary cell according to the respective combinations defined in Table 7.1-6A. The same PDSCH related configuration applies in the case that a PDSCH is transmitted without a corresponding EPDCCH. The scrambling initialization of PDSCH corresponding to these EPDCCHs and PDSCH without a corresponding EPDCCH is by SPS C-RNTI.

When a UE is configured in transmission mode 7, scrambling initialization of UE-specific reference signals for PDSCH corresponding to these PDCCHs/EPDCCHs and for PDSCH without a corresponding PDCCH/EPDCCH is by SPS C-RNTI.

When a UE is configured in transmission mode 9 or 10, in the downlink subframes indicated by the higher layer parameter *mbsfn-SubframeConfigList* or by *mbsfn-SubframeConfigList-v12x0* of serving cell *c* except in subframes for the serving cell

- indicated by higher layers to decode PMCH or,
- configured by higher layers to be part of a positioning reference signal occasion and the positioning reference signal occasion is only configured within MBSFN subframes and the cyclic prefix length used in subframe #0 is normal cyclic prefix,

the UE shall upon detection of a PDCCH with CRC scrambled by the SPS C-RNTI with DCI format 1A/2C/2D, or upon detection of a EPDCCH with CRC scrambled by the SPS C-RNTI with DCI format 1A/2C/2D, or for a configured PDSCH without PDCCH intended for the UE, decode the corresponding PDSCH in the same subframe.

A UE configured in transmission mode 10 can be configured with scrambling identities, $n_{ID}^{DMRS,i}$, $i = 0,1$ by higher layers for UE-specific reference signal generation as defined in subclause 6.10.3.1 of [3] to decode PDSCH according to a detected PDCCH/EPDCCH with CRC scrambled by the SPS C-RNTI with DCI format 2D intended for the UE.

For PDSCH without a corresponding PDCCH/EPDCCH, the UE shall use the value of n_{SCID} and the scrambling identity of $n_{ID}^{(n_{SCID})}$ (as defined in subclause 6.10.3.1 of [3]) derived from the DCI format 2D corresponding to the associated SPS activation for UE-specific reference signal generation.

Table 7.1-6: PDCCH and PDSCH configured by SPS C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|-------------------|---------------|----------------------------------|---|
| Mode 1 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| Mode 2 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 3 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 4 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 5 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 6 | DCI format 1A | Common and UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 7 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| Mode 8 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2B | UE specific by C-RNTI | Single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 9 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2C | UE specific by C-RNTI | Single-antenna port, port 7 or 8, (see subclause 7.1.1) |
| Mode 10 | DCI format 1A | Common and UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2D | UE specific by C-RNTI | Single-antenna port, port 7 or 8, (see subclause 7.1.1) |

Table 7.1-6A: EPDCCH and PDSCH configured by SPS C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PDSCH corresponding to EPDCCH |
|-------------------|---------------|-----------------------|---|
| Mode 1 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 0 (see subclause 7.1.1) |
| Mode 2 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 1 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 3 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 4 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| | DCI format 2 | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 5 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 6 | DCI format 1A | UE specific by C-RNTI | Transmit diversity (see subclause 7.1.2) |
| Mode 7 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| | DCI format 1 | UE specific by C-RNTI | Single-antenna port, port 5 (see subclause 7.1.1) |
| Mode 8 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2B | UE specific by C-RNTI | Single-antenna port, port 7 or 8 (see subclause 7.1.1) |
| Mode 9 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2C | UE specific by C-RNTI | Single-antenna port, port 7 or 8, (see subclause 7.1.1) |
| Mode 10 | DCI format 1A | UE specific by C-RNTI | Single-antenna port, port 7 (see subclause 7.1.1) |
| | DCI format 2D | UE specific by C-RNTI | Single-antenna port, port 7 or 8, (see subclause 7.1.1) |

If a UE is configured by higher layers to decode PDCCH with CRC scrambled by the Temporary C-RNTI and is not configured to decode PDCCH with CRC scrambled by the C-RNTI, the UE shall decode the PDCCH and the corresponding PDSCH according to the combination defined in Table 7.1-7. The scrambling initialization of PDSCH corresponding to these PDCCHs is by Temporary C-RNTI.

Table 7.1-7: PDCCH and PDSCH configured by Temporary C-RNTI

| DCI format | Search Space | Transmission scheme of PDSCH corresponding to PDCCH |
|---------------|--|--|
| DCI format 1A | Common and UE specific by Temporary C-RNTI | If the number of PBCH antenna port is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |
| DCI format 1 | UE specific by Temporary C-RNTI | If the number of PBCH antenna port is one, Single-antenna port, port 0 is used (see subclause 7.1.1), otherwise Transmit diversity (see subclause 7.1.2) |

The transmission schemes of the PDSCH are described in the following sub-subclauses.

7.1.1 Single-antenna port scheme

For the single-antenna port transmission schemes (port 0, port 5, port 7 or port 8) of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed according to subclause 6.3.4.1 of [3].

In case an antenna port $p \in \{7,8\}$ is used, the UE cannot assume that the other antenna port in the set $\{7,8\}$ is not associated with transmission of PDSCH to another UE.

7.1.2 Transmit diversity scheme

For the transmit diversity transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed according to subclause 6.3.4.3 of [3].

7.1.3 Large delay CDD scheme

For the large delay CDD transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed according to large delay CDD as defined in subclause 6.3.4.2.2 of [3].

7.1.4 Closed-loop spatial multiplexing scheme

For the closed-loop spatial multiplexing transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed according to the applicable number of transmission layers as defined in subclause 6.3.4.2.1 of [3].

7.1.5 Multi-user MIMO scheme

For the multi-user MIMO transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed on one layer and according to subclause 6.3.4.2.1 of [3]. The $\delta_{\text{power-offset}}$ dB value signalled on PDCCH/EPDCCH with DCI format 1D using the downlink power offset field is given in Table 7.1.5-1.

Table 7.1.5-1: Mapping of downlink power offset field in DCI format 1D to the $\delta_{\text{power-offset}}$ value.

| Downlink power offset field | $\delta_{\text{power-offset}}$ [dB] |
|-----------------------------|-------------------------------------|
| 0 | $-10\log_{10}(2)$ |
| 1 | 0 |

7.1.5A Dual layer scheme

For the dual layer transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed with two transmission layers on antenna ports 7 and 8 as defined in subclause 6.3.4.4 of [3].

7.1.5B Up to 8 layer transmission scheme

For the up to 8 layer transmission scheme of the PDSCH, the UE may assume that an eNB transmission on the PDSCH would be performed with up to 8 transmission layers on antenna ports 7 - 14 as defined in subclause 6.3.4.4 of [3].

7.1.6 Resource allocation

The UE shall interpret the resource allocation field depending on the PDCCH/EPDCCH DCI format detected. A resource allocation field in each PDCCH/EPDCCH includes two parts, a resource allocation header field and information consisting of the actual resource block assignment.

PDCCH DCI formats 1, 2, 2A, 2B, 2C and 2D with type 0 and PDCCH DCI formats 1, 2, 2A, 2B, 2C and 2D with type 1 resource allocation have the same format and are distinguished from each other via the single bit resource allocation header field which exists depending on the downlink system bandwidth (subclause 5.3.3.1 of [4]), where type 0 is indicated by 0 value and type 1 is indicated otherwise. PDCCH with DCI format 1A, 1B, 1C and 1D have a type 2 resource allocation while PDCCH with DCI format 1, 2, 2A, 2B, 2C and 2D have type 0 or type 1 resource allocation. PDCCH DCI formats with a type 2 resource allocation do not have a resource allocation header field.

EPDCCH DCI formats 1, 2, 2A, 2B, 2C and 2D with type 0 and EPDCCH DCI formats 1, 2, 2A, 2B, 2C and 2D with type 1 resource allocation have the same format and are distinguished from each other via the single bit resource allocation header field which exists depending on the downlink system bandwidth (subclause 5.3.3.1 of [4]), where type 0 is indicated by 0 value and type 1 is indicated otherwise. EPDCCH with DCI format 1A, 1B, and 1D have a type 2 resource allocation while EPDCCH with DCI format 1, 2, 2A, 2B, 2C and 2D have type 0 or type 1 resource allocation. EPDCCH DCI formats with a type 2 resource allocation do not have a resource allocation header field.

A UE may assume, for any PDSCH transmission scheduled by a cell with physical cell identity given in *NAICS-AssistanceInfo-r12* and the PDSCH transmission mode belonging to *transmissionModeList-r12* associated with the cell except spatial multiplexing using up to 8 transmission layers in transmission mode 10, that the resource allocation granularity and precoding granularity in terms of PRB pairs in the frequency domain are both given by N , where N is given by the higher layer parameter *resAllocGranularity-r12* associated with the cell. The first set of N consecutive PRB pairs of the resource allocation starts from the lowest frequency of the system bandwidth and the UE may assume the same precoding applies to all PRB pairs within a set.

7.1.6.1 Resource allocation type 0

In resource allocations of type 0, resource block assignment information includes a bitmap indicating the Resource Block Groups (RBGs) that are allocated to the scheduled UE where a RBG is a set of consecutive virtual resource blocks (VRBs) of localized type as defined in subclause 6.2.3.1 of [3]. Resource block group size (P) is a function of the system bandwidth as shown in Table 7.1.6.1-1. The total number of RBGs (N_{RBG}) for downlink system bandwidth of $N_{\text{RB}}^{\text{DL}}$ is given by $N_{\text{RBG}} = \lceil N_{\text{RB}}^{\text{DL}} / P \rceil$ where $\lfloor N_{\text{RB}}^{\text{DL}} / P \rfloor$ of the RBGs are of size P and if $N_{\text{RB}}^{\text{DL}} \bmod P > 0$ then one of the RBGs is of size $N_{\text{RB}}^{\text{DL}} - P \cdot \lfloor N_{\text{RB}}^{\text{DL}} / P \rfloor$. The bitmap is of size N_{RBG} bits with one bitmap bit per RBG such that each RBG is addressable. The RBGs shall be indexed in the order of increasing frequency and non-increasing RBG sizes starting at the lowest frequency. The order of RBG to bitmap bit mapping is in such way that RBG 0 to RBG $N_{\text{RBG}} - 1$ are mapped to MSB to LSB of the bitmap. The RBG is allocated to the UE if the corresponding bit value in the bitmap is 1, the RBG is not allocated to the UE otherwise.

Table 7.1.6.1-1: Type 0 resource allocation RBG size vs. Downlink System Bandwidth

| System Bandwidth $N_{\text{RB}}^{\text{DL}}$ | RBG Size (P) |
|---|---------------------|
| ≤ 10 | 1 |
| 11 – 26 | 2 |
| 27 – 63 | 3 |
| 64 – 110 | 4 |

7.1.6.2 Resource allocation type 1

In resource allocations of type 1, a resource block assignment information of size N_{RBG} indicates to a scheduled UE the VRBs from the set of VRBs from one of P RBG subsets. The virtual resource blocks used are of localized type as defined in subclause 6.2.3.1 of [3]. Also P is the RBG size associated with the system bandwidth as shown in Table 7.1.6.1-1. A RBG subset p , where $0 \leq p < P$, consists of every P th RBG starting from RBG p . The resource block assignment information consists of three fields [4].

The first field with $\lceil \log_2(P) \rceil$ bits is used to indicate the selected RBG subset among P RBG subsets.

The second field with one bit is used to indicate a shift of the resource allocation span within a subset. A bit value of 1 indicates shift is triggered. Shift is not triggered otherwise.

The third field includes a bitmap, where each bit of the bitmap addresses a single VRB in the selected RBG subset in such a way that MSB to LSB of the bitmap are mapped to the VRBs in the increasing frequency order. The VRB is allocated to the UE if the corresponding bit value in the bit field is 1, the VRB is not allocated to the UE otherwise.

The portion of the bitmap used to address VRBs in a selected RBG subset has size $N_{\text{RB}}^{\text{TYPE1}}$ and is defined as

$$N_{\text{RB}}^{\text{TYPE1}} = \lceil N_{\text{RB}}^{\text{DL}} / P \rceil - \lceil \log_2(P) \rceil - 1$$

The addressable VRB numbers of a selected RBG subset start from an offset, $\Delta_{\text{shift}}(p)$ to the smallest VRB number within the selected RBG subset, which is mapped to the MSB of the bitmap. The offset is in terms of the number of VRBs and is done within the selected RBG subset. If the value of the bit in the second field for shift of the resource

allocation span is set to 0, the offset for RBG subset p is given by $\Delta_{\text{shift}}(p) = 0$. Otherwise, the offset for RBG subset p is given by $\Delta_{\text{shift}}(p) = N_{\text{RB}}^{\text{RBG subset}}(p) - N_{\text{RB}}^{\text{TYPE1}}$, where the LSB of the bitmap is justified with the highest VRB number within the selected RBG subset. $N_{\text{RB}}^{\text{RBG subset}}(p)$ is the number of VRBs in RBG subset p and can be calculated by the following equation,

$$N_{\text{RB}}^{\text{RBG subset}}(p) = \begin{cases} \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P^2} \right\rfloor \cdot P + P & , p < \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P} \right\rfloor \bmod P \\ \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P^2} \right\rfloor \cdot P + (N_{\text{RB}}^{\text{DL}} - 1) \bmod P + 1 & , p = \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P} \right\rfloor \bmod P \\ \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P^2} \right\rfloor \cdot P & , p > \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} - 1}{P} \right\rfloor \bmod P \end{cases}$$

Consequently, when RBG subset p is indicated, bit i for $i = 0, 1, \dots, N_{\text{RB}}^{\text{TYPE1}} - 1$ in the bitmap field indicates VRB number,

$$n_{\text{VRB}}^{\text{RBG subset}}(p) = \left\lfloor \frac{i + \Delta_{\text{shift}}(p)}{P} \right\rfloor P^2 + p \cdot P + (i + \Delta_{\text{shift}}(p)) \bmod P.$$

7.1.6.3 Resource allocation type 2

In resource allocations of type 2, the resource block assignment information indicates to a scheduled UE a set of contiguously allocated localized virtual resource blocks or distributed virtual resource blocks. In case of resource allocation signalled with PDCCH DCI format 1A, 1B or 1D, or for resource allocation signalled with EPDCCH DCI format 1A, 1B, or 1D, one bit flag indicates whether localized virtual resource blocks or distributed virtual resource blocks are assigned (value 0 indicates Localized and value 1 indicates Distributed VRB assignment) while distributed virtual resource blocks are always assigned in case of resource allocation signalled with PDCCH DCI format 1C. Localized VRB allocations for a UE vary from a single VRB up to a maximum number of VRBs spanning the system bandwidth. For DCI format 1A the distributed VRB allocations for a UE vary from a single VRB up to $N_{\text{VRB}}^{\text{DL}}$ VRBs, where $N_{\text{VRB}}^{\text{DL}}$ is defined in [3], if the DCI CRC is scrambled by P-RNTI, RA-RNTI, or SI-RNTI. With PDCCH DCI format 1B, 1D with a CRC scrambled by C-RNTI, or with DCI format 1A with a CRC scrambled with C-RNTI, SPS C-RNTI or Temporary C-RNTI distributed VRB allocations for a UE vary from a single VRB up to $N_{\text{VRB}}^{\text{DL}}$ VRBs if $N_{\text{RB}}^{\text{DL}}$ is 6-49 and vary from a single VRB up to 16 if $N_{\text{RB}}^{\text{DL}}$ is 50-110. With EPDCCH DCI format 1B, 1D with a CRC scrambled by C-RNTI, or with DCI format 1A with a CRC scrambled with C-RNTI, SPS C-RNTI distributed VRB allocations for a UE vary from a single VRB up to $N_{\text{VRB}}^{\text{DL}}$ VRBs if $N_{\text{RB}}^{\text{DL}}$ is 6-49 and vary from a single VRB up to 16 if $N_{\text{RB}}^{\text{DL}}$ is 50-110. With PDCCH DCI format 1C, distributed VRB allocations for a UE vary from $N_{\text{RB}}^{\text{step}}$ VRB(s) up to $\lfloor N_{\text{VRB}}^{\text{DL}} / N_{\text{RB}}^{\text{step}} \rfloor \cdot N_{\text{RB}}^{\text{step}}$ VRBs with an increment step of $N_{\text{RB}}^{\text{step}}$, where $N_{\text{RB}}^{\text{step}}$ value is determined depending on the downlink system bandwidth as shown in Table 7.1.6.3-1.

Table 7.1.6.3-1: $N_{\text{RB}}^{\text{step}}$ values vs. Downlink System Bandwidth

| System BW ($N_{\text{RB}}^{\text{DL}}$) | $N_{\text{RB}}^{\text{step}}$ |
|---|-------------------------------|
| | DCI format 1C |
| 6-49 | 2 |
| 50-110 | 4 |

For PDCCH DCI format 1A, 1B or 1D, or for EPDCCH DCI format 1A, 1B, or 1D, a type 2 resource allocation field consists of a resource indication value (RIV) corresponding to a starting resource block (RB_{start}) and a length in terms of virtually contiguously allocated resource blocks L_{CRBs} . The resource indication value is defined by

if $(L_{CRBs} - 1) \leq \lfloor N_{RB}^{DL} / 2 \rfloor$ then

$$RIV = N_{RB}^{DL} (L_{CRBs} - 1) + RB_{start}$$

else

$$RIV = N_{RB}^{DL} (N_{RB}^{DL} - L_{CRBs} + 1) + (N_{RB}^{DL} - 1 - RB_{start})$$

where $L_{CRBs} \geq 1$ and shall not exceed $N_{VRB}^{DL} - RB_{start}$.

For PDCCH DCI format 1C, a type 2 resource block assignment field consists of a resource indication value (RIV) corresponding to a starting resource block ($RB_{start} = 0, N_{RB}^{step}, 2N_{RB}^{step}, \dots, (\lfloor N_{VRB}^{DL} / N_{RB}^{step} \rfloor - 1)N_{RB}^{step}$) and a length in terms of virtually contiguously allocated resource blocks ($L_{CRBs} = N_{RB}^{step}, 2N_{RB}^{step}, \dots, \lfloor N_{VRB}^{DL} / N_{RB}^{step} \rfloor \cdot N_{RB}^{step}$).

The resource indication value is defined by:

if $(L'_{CRBs} - 1) \leq \lfloor N'_{VRB}^{DL} / 2 \rfloor$ then

$$RIV = N'_{VRB}^{DL} (L'_{CRBs} - 1) + RB'_{start}$$

else

$$RIV = N'_{VRB}^{DL} (N'_{VRB}^{DL} - L'_{CRBs} + 1) + (N'_{VRB}^{DL} - 1 - RB'_{start})$$

where $L'_{CRBs} = L_{CRBs} / N_{RB}^{step}$, $RB'_{start} = RB_{start} / N_{RB}^{step}$ and $N'_{VRB}^{DL} = \lfloor N_{VRB}^{DL} / N_{RB}^{step} \rfloor$. Here,

$L'_{CRBs} \geq 1$ and shall not exceed $N'_{VRB}^{DL} - RB'_{start}$.

7.1.6.4 PDSCH starting position

The starting OFDM symbol for the PDSCH of each activated serving cell is given by index $l_{DataStart}$ in the first slot in a subframe.

For a UE configured in transmission mode 1-9, for a given activated serving cell

- if the PDSCH is assigned by EPDCCH received in the same serving cell, or if the UE is configured to monitor EPDCCH in the subframe and the PDSCH is not assigned by a PDCCH/EPDCCH, and if the UE is configured with the higher layer parameter *epdcch-StartSymbol-r11*
 - $l_{DataStart}$ is given by the higher-layer parameter *epdcch-StartSymbol-r11*.
- else if PDSCH and the corresponding PDCCH/EPDCCH are received on different serving cells
 - $l_{DataStart}$ is given by the higher-layer parameter *pdsch-Start-r10* for the serving cell on which PDSCH is received,
- Otherwise
 - $l_{DataStart}$ is given by the CFI value in the subframe of the given serving cell when $N_{RB}^{DL} > 10$, and $l_{DataStart}$ is given by the CFI value + 1 in the subframe of the given serving cell when $N_{RB}^{DL} \leq 10$.

For a UE configured in transmission mode 10, for a given activated serving cell

- if the PDSCH is assigned by a PDCCH with DCI format 1C or by a PDCCH with DCI format 1A and with CRC scrambled with P-RNTI/RA-RNTI/SI-RNTI/Temporary C-RNTI

- $l_{\text{DataStart}}$ is given by the span of the DCI given by the CFI value in the subframe of the given serving cell according to subclause 5.3.4 of [4].
- if the PDSCH is assigned by a PDCCH/EPDCCH with DCI format 1A and with CRC scrambled with C-RNTI and if the PDSCH transmission is on antenna ports 0 - 3
 - if the PDSCH is assigned by EPDCCH received in the same serving cell
 - $l_{\text{DataStart}}$ is given by $l_{\text{EPDCCHStart}}$ for the EPDCCH-PRB-set where EPDCCH with the DCI format 1A was received ($l_{\text{EPDCCHStart}}$ as defined in subclause 9.1.4.1),
 - else if PDSCH and the corresponding PDCCH/EPDCCH are received on different serving cells
 - $l_{\text{DataStart}}$ is given by the higher-layer parameter *pdsch-Start-r10* for the serving cell on which PDSCH is received.
 - otherwise
 - $l_{\text{DataStart}}$ is given by the CFI value in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} > 10$, and $l_{\text{DataStart}}$ is given by the CFI value+1 in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} \leq 10$.
- if the PDSCH is assigned by or semi-statically scheduled by a PDCCH/EPDCCH with DCI format 1A and if the PDSCH transmission is on antenna port 7
 - if the value of the higher layer parameter *pdsch-Start-r11* determined from parameter set 1 in table 7.1.9-1 for the serving cell on which PDSCH is received belongs to {1,2,3,4},
 - $l'_{\text{DataStart}}$ is given by the higher layer parameter *pdsch-Start-r11* determined from parameter set 1 in table 7.1.9-1 for the serving cell on which PDSCH is received.
 - else,
 - if PDSCH and the corresponding PDCCH/EPDCCH are received on different serving cells,
 - $l'_{\text{DataStart}}$ is given by the higher-layer parameter *pdsch-Start-r10* for the serving cell on which PDSCH is received
 - otherwise
 - $l'_{\text{DataStart}}$ is given by the CFI value in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} > 10$, and $l'_{\text{DataStart}}$ is given by the CFI value + 1 in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} \leq 10$.
 - if the subframe on which PDSCH is received is indicated by the higher layer parameter *mbsfn-SubframeConfigList-r11* determined from parameter set 1 in table 7.1.9-1 for the serving cell on which PDSCH is received, or if the PDSCH is received on subframe 1 or 6 for the frame structure type 2,
 - $l_{\text{DataStart}} = \min(2, l'_{\text{DataStart}})$,
 - otherwise
 - $l_{\text{DataStart}} = l'_{\text{DataStart}}$.
- if the PDSCH is assigned by or semi-persistently scheduled by a PDCCH/EPDCCH with DCI format 2D,
 - if the value of the higher layer parameter *pdsch-Start-r11* determined from the DCI (according to subclause 7.1.9) for the serving cell on which PDSCH is received belongs to {1,2,3,4},
 - $l'_{\text{DataStart}}$ is given by parameter *pdsch-Start-r11* determined from the DCI (according to subclause 7.1.9) for the serving cell on which PDSCH is received

- else,
 - if PDSCH and the corresponding PDCCH/EPDCCH are received on different serving cells,
 - $l'_{\text{DataStart}}$ is given by the higher-layer parameter *pdsch-Start-r10* for the serving cell on which PDSCH is received
 - Otherwise
 - $l'_{\text{DataStart}}$ is given by the CFI value in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} > 10$, and $l_{\text{DataStart}}$ is given by the CFI value+1 in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} \leq 10$.
 - if the subframe on which PDSCH is received is indicated by the higher layer parameter *mbsfn-SubframeConfigList-r11* determined from the DCI (according to subclause 7.1.9) for the serving cell on which PDSCH is received, or if the PDSCH is received on subframe 1 or 6 for frame structure type 2,
 - $l_{\text{DataStart}} = \min(2, l'_{\text{DataStart}})$,
 - otherwise
 - $l_{\text{DataStart}} = l'_{\text{DataStart}}$.

7.1.6.5 Physical Resource Block (PRB) bundling

A UE configured for transmission mode 9 for a given serving cell c may assume that precoding granularity is multiple resource blocks in the frequency domain when PMI/RI reporting is configured.

For a given serving cell c , if a UE is configured for transmission mode 10

- if PMI/RI reporting is configured for all configured CSI processes for the serving cell c , the UE may assume that precoding granularity is multiple resource blocks in the frequency domain,
- otherwise, the UE shall assume the precoding granularity is one resource block in the frequency domain.

Fixed system bandwidth dependent Precoding Resource block Groups (PRGs) of size P' partition the system bandwidth and each PRG consists of consecutive PRBs. If $N_{\text{RB}}^{\text{DL}} \bmod P' > 0$ then one of the PRGs is of size $N_{\text{RB}}^{\text{DL}} - P' \lfloor N_{\text{RB}}^{\text{DL}} / P' \rfloor$. The PRG size is non-increasing starting at the lowest frequency. The UE may assume that the same precoder applies on all scheduled PRBs within a PRG.

The PRG size a UE may assume for a given system bandwidth is given by:

Table 7.1.6.5-1

| System Bandwidth ($N_{\text{RB}}^{\text{DL}}$) | PRG Size (P') (PRBs) |
|---|-----------------------------|
| ≤ 10 | 1 |
| 11 – 26 | 2 |
| 27 – 63 | 3 |
| 64 – 110 | 2 |

7.1.7 Modulation order and transport block size determination

To determine the modulation order and transport block size(s) in the physical downlink shared channel, the UE shall first

- read the 5-bit "modulation and coding scheme" field (I_{MCS}) in the DCI

and second if the DCI CRC is scrambled by P-RNTI, RA-RNTI, or SI-RNTI then

- for DCI format 1A:
 - set the Table 7.1.7.2.1-1 column indicator N_{PRB} to N_{PRB}^{1A} from subclause 5.3.3.1.3 in [4]
- for DCI format 1C:
 - use Table 7.1.7.2.3-1 for determining its transport block size.

else

- set N'_{PRB} to the total number of allocated PRBs based on the procedure defined in subclause 7.1.6.

if the transport block is transmitted in DwPTS of the special subframe in frame structure type 2, then

- for special subframe configuration 9 with normal cyclic prefix or special subframe configuration 7 with extended cyclic prefix:

$$N_{PRB} = \max \left\{ \left\lfloor N'_{PRB} \times 0.375 \right\rfloor, 1 \right\}$$

- set the Table 7.1.7.2.1-1 column indicator
- for other special subframe configurations:

$$N_{PRB} = \max \left\{ \left\lfloor N'_{PRB} \times 0.75 \right\rfloor, 1 \right\},$$

else, set the Table 7.1.7.2.1-1 column indicator $N_{PRB} = N'_{PRB}$.

The UE may skip decoding a transport block in an initial transmission if the effective channel code rate is higher than 0.931, where the effective channel code rate is defined as the number of downlink information bits (including CRC bits) divided by the number of physical channel bits on PDSCH. If the UE skips decoding, the physical layer indicates to higher layer that the transport block is not successfully decoded. For the special subframe configurations 0 and 5 with normal downlink CP or configurations 0 and 4 with extended downlink CP, shown in Table 4.2-1 of [3], there shall be no PDSCH transmission in DwPTS of the special subframe.

7.1.7.1 Modulation order determination

The UE shall use $Q_m = 2$ if the DCI CRC is scrambled by P-RNTI, RA-RNTI, or SI-RNTI, otherwise,

- if the higher layer parameter *altCQI-Table-r12* is configured, and if the PDSCH is assigned by a PDCCH/EPDCCH with DCI format 1/1B/1D/2/2A/2B/2C/2D with CRC scrambled by C-RNTI,
 - the UE shall use I_{MCS} and Table 7.1.7.1-1A to determine the modulation order (Q_m) used in the physical downlink shared channel.
- else
 - the UE shall use I_{MCS} and Table 7.1.7.1-1 to determine the modulation order (Q_m) used in the physical downlink shared channel.

Table 7.1.7.1-1: Modulation and TBS index table for PDSCH

| MCS Index I_{MCS} | Modulation Order Q_m | TBS Index I_{TBS} |
|------------------------|---------------------------|------------------------|
| 0 | 2 | 0 |
| 1 | 2 | 1 |
| 2 | 2 | 2 |
| 3 | 2 | 3 |
| 4 | 2 | 4 |
| 5 | 2 | 5 |
| 6 | 2 | 6 |
| 7 | 2 | 7 |
| 8 | 2 | 8 |
| 9 | 2 | 9 |
| 10 | 4 | 9 |
| 11 | 4 | 10 |
| 12 | 4 | 11 |
| 13 | 4 | 12 |
| 14 | 4 | 13 |
| 15 | 4 | 14 |
| 16 | 4 | 15 |
| 17 | 6 | 15 |
| 18 | 6 | 16 |
| 19 | 6 | 17 |
| 20 | 6 | 18 |
| 21 | 6 | 19 |
| 22 | 6 | 20 |
| 23 | 6 | 21 |
| 24 | 6 | 22 |
| 25 | 6 | 23 |
| 26 | 6 | 24 |
| 27 | 6 | 25 |
| 28 | 6 | 26/26A |
| 29 | 2 | reserved |
| 30 | 4 | |
| 31 | 6 | |

Table 7.1.7.1-1A. Modulation and TBS index table 2 for PDSCH

| MCS Index I_{MCS} | Modulation Order Q_m | TBS Index I_{TBS} |
|------------------------|---------------------------|------------------------|
| 0 | 2 | 0 |
| 1 | 2 | 2 |
| 2 | 2 | 4 |
| 3 | 2 | 6 |
| 4 | 2 | 8 |
| 5 | 4 | 10 |
| 6 | 4 | 11 |
| 7 | 4 | 12 |
| 8 | 4 | 13 |
| 9 | 4 | 14 |
| 10 | 4 | 15 |
| 11 | 6 | 16 |
| 12 | 6 | 17 |
| 13 | 6 | 18 |
| 14 | 6 | 19 |
| 15 | 6 | 20 |

| MCS Index I_{MCS} | Modulation Order Q_m | TBS Index I_{TBS} |
|------------------------|---------------------------|------------------------|
| 16 | 6 | 21 |
| 17 | 6 | 22 |
| 18 | 6 | 23 |
| 19 | 6 | 24 |
| 20 | 8 | 25 |
| 21 | 8 | 27 |
| 22 | 8 | 28 |
| 23 | 8 | 29 |
| 24 | 8 | 30 |
| 25 | 8 | 31 |
| 26 | 8 | 32 |
| 27 | 8 | 33/33A |
| 28 | 2 | reserved |
| 29 | 4 | |
| 30 | 6 | |
| 31 | 8 | |

7.1.7.2 Transport block size determination

If the DCI CRC is scrambled by P-RNTI, RA-RNTI, or SI-RNTI then

- for DCI format 1A:
 - the UE shall set the TBS index (I_{TBS}) equal to I_{MCS} and determine its TBS by the procedure in subclause 7.1.7.2.1 for $0 \leq I_{TBS} \leq 26$.
- for DCI format 1C:
 - the UE shall set the TBS index (I_{TBS}) equal to I_{MCS} and determine its TBS from Table 7.1.7.2.3-1.

else if the higher layer parameter *altCQI-Table-r12* is configured, then

- for DCI format 1A with CRC scrambled by C-RNTI and for DCI format 1/1A/2/2A/2B/2C/2D with CRC scrambled by SPS C-RNTI:
 - for $0 \leq I_{MCS} \leq 28$, the UE shall first determine the TBS index (I_{TBS}) using I_{MCS} and Table 7.1.7.1-1 except if the transport block is disabled in DCI formats 2, 2A, 2B, 2C and 2D as specified below. For a transport block that is not mapped to more than single-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.1.
 - for $29 \leq I_{MCS} \leq 31$, the TBS is assumed to be as determined from DCI transported in the latest PDCCH/EPDCCH for the same transport block using $0 \leq I_{TBS} \leq 33$. If there is no PDCCH/EPDCCH for the same transport block using $0 \leq I_{TBS} \leq 26$, and if the initial PDSCH for the same transport block is semi-persistently scheduled, the TBS shall be determined from the most recent semi-persistent scheduling assignment PDCCH/EPDCCH.
 - In DCI formats 2, 2A, 2B, 2C and 2D a transport block is disabled if $I_{MCS} = 0$ and if $rv_{idx} = 1$ otherwise the transport block is enabled.
- for DCI format 1/1B/1D/2/2A/2B/2C/2D with CRC scrambled by C-RNTI

- for $0 \leq I_{MCS} \leq 27$, the UE shall first determine the TBS index (I_{TBS}) using I_{MCS} and Table 7.1.7.1-1A except if the transport block is disabled in DCI formats 2, 2A, 2B, 2C and 2D as specified below. When $I_{MCS} = 27$, if the UE is scheduled by DCI formats 2C/2D and is configured with a33 in *tbsIndexAlt*, I_{TBS} is 33A; otherwise I_{TBS} is 33. For a transport block that is not mapped to more than single-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.1. For a transport block that is mapped to two-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.2. For a transport block that is mapped to three-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.4. For a transport block that is mapped to four-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.5.
- for $28 \leq I_{MCS} \leq 31$, the TBS is assumed to be as determined from DCI transported in the latest PDCCH/EPDCCH for the same transport block using $0 \leq I_{MCS} \leq 27$.
- In DCI formats 2, 2A, 2B, 2C and 2D a transport block is disabled if $I_{MCS} = 0$ and if $rv_{idx} = 1$ otherwise the transport block is enabled.

else

- for $0 \leq I_{MCS} \leq 28$, the UE shall first determine the TBS index (I_{TBS}) using I_{MCS} and Table 7.1.7.1-1 except if the transport block is disabled in DCI formats 2, 2A, 2B, 2C and 2D as specified below. When $I_{MCS} = 28$, if the UE is scheduled by DCI formats 2C/2D and is configured with a26 in *tbsIndexAlt*, I_{TBS} is 26A; otherwise I_{TBS} is 26. For a transport block that is not mapped to more than single-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.1. For a transport block that is mapped to two-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.2. For a transport block that is mapped to three-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.4. For a transport block that is mapped to four-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.5.
- for $29 \leq I_{MCS} \leq 31$, the TBS is assumed to be as determined from DCI transported in the latest PDCCH/EPDCCH for the same transport block using $0 \leq I_{MCS} \leq 28$. If there is no PDCCH/EPDCCH for the same transport block using $0 \leq I_{MCS} \leq 28$, and if the initial PDSCH for the same transport block is semi-persistently scheduled, the TBS shall be determined from the most recent semi-persistent scheduling assignment PDCCH/EPDCCH.
- In DCI formats 2, 2A, 2B, 2C and 2D a transport block is disabled if $I_{MCS} = 0$ and if $rv_{idx} = 1$ otherwise the transport block is enabled.

The NDI and HARQ process ID, as signalled on PDCCH/EPDCCH, and the TBS, as determined above, shall be delivered to higher layers.

7.1.7.2.1 Transport blocks not mapped to two or more layer spatial multiplexing

For $1 \leq N_{PRB} \leq 110$, the TBS is given by the (I_{TBS}, N_{PRB}) entry of Table 7.1.7.2.1-1.

Table 7.1.7.2.1-1: Transport block size table (dimension 34x110)

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-----|-----|-----|-----|-----|-----|-----|------|------|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 0 | 16 | 32 | 56 | 88 | 120 | 152 | 176 | 208 | 224 | 256 |
| 1 | 24 | 56 | 88 | 144 | 176 | 208 | 224 | 256 | 328 | 344 |
| 2 | 32 | 72 | 144 | 176 | 208 | 256 | 296 | 328 | 376 | 424 |
| 3 | 40 | 104 | 176 | 208 | 256 | 328 | 392 | 440 | 504 | 568 |
| 4 | 56 | 120 | 208 | 256 | 328 | 408 | 488 | 552 | 632 | 696 |
| 5 | 72 | 144 | 224 | 328 | 424 | 504 | 600 | 680 | 776 | 872 |
| 6 | 328 | 176 | 256 | 392 | 504 | 600 | 712 | 808 | 936 | 1032 |
| 7 | 104 | 224 | 328 | 472 | 584 | 712 | 840 | 968 | 1096 | 1224 |

| | | | | | | | | | | |
|-----|-----|------|------|------|------|------|------|------|------|------|
| 8 | 120 | 256 | 392 | 536 | 680 | 808 | 968 | 1096 | 1256 | 1384 |
| 9 | 136 | 296 | 456 | 616 | 776 | 936 | 1096 | 1256 | 1416 | 1544 |
| 10 | 144 | 328 | 504 | 680 | 872 | 1032 | 1224 | 1384 | 1544 | 1736 |
| 11 | 176 | 376 | 584 | 776 | 1000 | 1192 | 1384 | 1608 | 1800 | 2024 |
| 12 | 208 | 440 | 680 | 904 | 1128 | 1352 | 1608 | 1800 | 2024 | 2280 |
| 13 | 224 | 488 | 744 | 1000 | 1256 | 1544 | 1800 | 2024 | 2280 | 2536 |
| 14 | 256 | 552 | 840 | 1128 | 1416 | 1736 | 1992 | 2280 | 2600 | 2856 |
| 15 | 280 | 600 | 904 | 1224 | 1544 | 1800 | 2152 | 2472 | 2728 | 3112 |
| 16 | 328 | 632 | 968 | 1288 | 1608 | 1928 | 2280 | 2600 | 2984 | 3240 |
| 17 | 336 | 696 | 1064 | 1416 | 1800 | 2152 | 2536 | 2856 | 3240 | 3624 |
| 18 | 376 | 776 | 1160 | 1544 | 1992 | 2344 | 2792 | 3112 | 3624 | 4008 |
| 19 | 408 | 840 | 1288 | 1736 | 2152 | 2600 | 2984 | 3496 | 3880 | 4264 |
| 20 | 440 | 904 | 1384 | 1864 | 2344 | 2792 | 3240 | 3752 | 4136 | 4584 |
| 21 | 488 | 1000 | 1480 | 1992 | 2472 | 2984 | 3496 | 4008 | 4584 | 4968 |
| 22 | 520 | 1064 | 1608 | 2152 | 2664 | 3240 | 3752 | 4264 | 4776 | 5352 |
| 23 | 552 | 1128 | 1736 | 2280 | 2856 | 3496 | 4008 | 4584 | 5160 | 5736 |
| 24 | 584 | 1192 | 1800 | 2408 | 2984 | 3624 | 4264 | 4968 | 5544 | 5992 |
| 25 | 616 | 1256 | 1864 | 2536 | 3112 | 3752 | 4392 | 5160 | 5736 | 6200 |
| 26 | 712 | 1480 | 2216 | 2984 | 3752 | 4392 | 5160 | 5992 | 6712 | 7480 |
| 26A | 632 | 1288 | 1928 | 2600 | 3240 | 3880 | 4584 | 5160 | 5992 | 6456 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|
| | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| 0 | 288 | 328 | 344 | 376 | 392 | 424 | 456 | 488 | 504 | 536 |
| 1 | 376 | 424 | 456 | 488 | 520 | 568 | 600 | 632 | 680 | 712 |
| 2 | 472 | 520 | 568 | 616 | 648 | 696 | 744 | 776 | 840 | 872 |
| 3 | 616 | 680 | 744 | 808 | 872 | 904 | 968 | 1032 | 1096 | 1160 |
| 4 | 776 | 840 | 904 | 1000 | 1064 | 1128 | 1192 | 1288 | 1352 | 1416 |
| 5 | 968 | 1032 | 1128 | 1224 | 1320 | 1384 | 1480 | 1544 | 1672 | 1736 |
| 6 | 1128 | 1224 | 1352 | 1480 | 1544 | 1672 | 1736 | 1864 | 1992 | 2088 |
| 7 | 1320 | 1480 | 1608 | 1672 | 1800 | 1928 | 2088 | 2216 | 2344 | 2472 |
| 8 | 1544 | 1672 | 1800 | 1928 | 2088 | 2216 | 2344 | 2536 | 2664 | 2792 |
| 9 | 1736 | 1864 | 2024 | 2216 | 2344 | 2536 | 2664 | 2856 | 2984 | 3112 |
| 10 | 1928 | 2088 | 2280 | 2472 | 2664 | 2792 | 2984 | 3112 | 3368 | 3496 |
| 11 | 2216 | 2408 | 2600 | 2792 | 2984 | 3240 | 3496 | 3624 | 3880 | 4008 |
| 12 | 2472 | 2728 | 2984 | 3240 | 3368 | 3624 | 3880 | 4136 | 4392 | 4584 |
| 13 | 2856 | 3112 | 3368 | 3624 | 3880 | 4136 | 4392 | 4584 | 4968 | 5160 |
| 14 | 3112 | 3496 | 3752 | 4008 | 4264 | 4584 | 4968 | 5160 | 5544 | 5736 |
| 15 | 3368 | 3624 | 4008 | 4264 | 4584 | 4968 | 5160 | 5544 | 5736 | 6200 |
| 16 | 3624 | 3880 | 4264 | 4584 | 4968 | 5160 | 5544 | 5992 | 6200 | 6456 |
| 17 | 4008 | 4392 | 4776 | 5160 | 5352 | 5736 | 6200 | 6456 | 6712 | 7224 |
| 18 | 4392 | 4776 | 5160 | 5544 | 5992 | 6200 | 6712 | 7224 | 7480 | 7992 |
| 19 | 4776 | 5160 | 5544 | 5992 | 6456 | 6968 | 7224 | 7736 | 8248 | 8504 |
| 20 | 5160 | 5544 | 5992 | 6456 | 6968 | 7480 | 7992 | 8248 | 8760 | 9144 |
| 21 | 5544 | 5992 | 6456 | 6968 | 7480 | 7992 | 8504 | 9144 | 9528 | 9912 |
| 22 | 5992 | 6456 | 6968 | 7480 | 7992 | 8504 | 9144 | 9528 | 10296 | 10680 |
| 23 | 6200 | 6968 | 7480 | 7992 | 8504 | 9144 | 9912 | 10296 | 11064 | 11448 |
| 24 | 6712 | 7224 | 7992 | 8504 | 9144 | 9912 | 10296 | 11064 | 11448 | 12216 |
| 25 | 6968 | 7480 | 8248 | 8760 | 9528 | 10296 | 10680 | 11448 | 12216 | 12576 |
| 26 | 8248 | 8760 | 9528 | 10296 | 11064 | 11832 | 12576 | 13536 | 14112 | 14688 |
| 26A | 7224 | 7736 | 8504 | 9144 | 9912 | 10296 | 11064 | 11832 | 12576 | 12960 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|------|------|------|------|------|------|-------|-------|-------|
| | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 |
| 0 | 568 | 600 | 616 | 648 | 680 | 712 | 744 | 776 | 776 | 808 |
| 1 | 744 | 776 | 808 | 872 | 904 | 936 | 968 | 1000 | 1032 | 1064 |
| 2 | 936 | 968 | 1000 | 1064 | 1096 | 1160 | 1192 | 1256 | 1288 | 1320 |
| 3 | 1224 | 1256 | 1320 | 1384 | 1416 | 1480 | 1544 | 1608 | 1672 | 1736 |
| 4 | 1480 | 1544 | 1608 | 1736 | 1800 | 1864 | 1928 | 1992 | 2088 | 2152 |
| 5 | 1864 | 1928 | 2024 | 2088 | 2216 | 2280 | 2344 | 2472 | 2536 | 2664 |
| 6 | 2216 | 2280 | 2408 | 2472 | 2600 | 2728 | 2792 | 2984 | 2984 | 3112 |
| 7 | 2536 | 2664 | 2792 | 2984 | 3112 | 3240 | 3368 | 3368 | 3496 | 3624 |
| 8 | 2984 | 3112 | 3240 | 3368 | 3496 | 3624 | 3752 | 3880 | 4008 | 4264 |
| 9 | 3368 | 3496 | 3624 | 3752 | 4008 | 4136 | 4264 | 4392 | 4584 | 4776 |
| 10 | 3752 | 3880 | 4008 | 4264 | 4392 | 4584 | 4776 | 4968 | 5160 | 5352 |
| 11 | 4264 | 4392 | 4584 | 4776 | 4968 | 5352 | 5544 | 5736 | 5992 | 5992 |
| 12 | 4776 | 4968 | 5352 | 5544 | 5736 | 5992 | 6200 | 6456 | 6712 | 6712 |
| 13 | 5352 | 5736 | 5992 | 6200 | 6456 | 6712 | 6968 | 7224 | 7480 | 7736 |
| 14 | 5992 | 6200 | 6456 | 6968 | 7224 | 7480 | 7736 | 7992 | 8248 | 8504 |
| 15 | 6456 | 6712 | 6968 | 7224 | 7736 | 7992 | 8248 | 8504 | 8760 | 9144 |
| 16 | 6712 | 7224 | 7480 | 7736 | 7992 | 8504 | 8760 | 9144 | 9528 | 9912 |
| 17 | 7480 | 7992 | 8248 | 8760 | 9144 | 9528 | 9912 | 10296 | 10296 | 10680 |

| 26A | 26416 | 27376 | 27376 | 29296 | 29296 | 29296 | 30576 | 30576 | 31704 | 32856 |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 59 | 60 |
| 0 | 1416 | 1416 | 1480 | 1480 | 1544 | 1544 | 1608 | 1608 | 1608 | 1672 |
| 1 | 1864 | 1864 | 1928 | 1928 | 1992 | 1992 | 2024 | 2088 | 2088 | 2152 |
| 2 | 2280 | 2344 | 2344 | 2408 | 2472 | 2536 | 2536 | 2600 | 2664 | 2664 |
| 3 | 2984 | 2984 | 3112 | 3112 | 3240 | 3240 | 3368 | 3368 | 3496 | 3496 |
| 4 | 3624 | 3752 | 3752 | 3880 | 4008 | 4008 | 4136 | 4136 | 4264 | 4264 |
| 5 | 4584 | 4584 | 4776 | 4776 | 4776 | 4968 | 4968 | 5160 | 5160 | 5352 |
| 6 | 5352 | 5352 | 5544 | 5736 | 5736 | 5992 | 5992 | 5992 | 6200 | 6200 |
| 7 | 6200 | 6456 | 6456 | 6712 | 6712 | 6712 | 6968 | 6968 | 7224 | 7224 |
| 8 | 7224 | 7224 | 7480 | 7480 | 7736 | 7736 | 7992 | 7992 | 8248 | 8504 |
| 9 | 7992 | 8248 | 8248 | 8504 | 8760 | 8760 | 9144 | 9144 | 9144 | 9528 |
| 10 | 9144 | 9144 | 9144 | 9528 | 9528 | 9912 | 9912 | 10296 | 10296 | 10680 |
| 11 | 10296 | 10680 | 10680 | 11064 | 11064 | 11448 | 11448 | 11832 | 11832 | 12216 |
| 12 | 11832 | 11832 | 12216 | 12216 | 12576 | 12576 | 12960 | 12960 | 13536 | 13536 |
| 13 | 12960 | 13536 | 13536 | 14112 | 14112 | 14688 | 14688 | 14688 | 15264 | 15264 |
| 14 | 14688 | 14688 | 15264 | 15264 | 15840 | 15840 | 16416 | 16416 | 16992 | 16992 |
| 15 | 15840 | 15840 | 16416 | 16416 | 16992 | 16992 | 17568 | 17568 | 18336 | 18336 |
| 16 | 16416 | 16992 | 16992 | 17568 | 17568 | 18336 | 18336 | 19080 | 19080 | 19848 |
| 17 | 18336 | 19080 | 19080 | 19848 | 19848 | 20616 | 20616 | 20616 | 21384 | 21384 |
| 18 | 19848 | 20616 | 21384 | 21384 | 22152 | 22152 | 22920 | 22920 | 23688 | 23688 |
| 19 | 22152 | 22152 | 22920 | 22920 | 23688 | 24496 | 24496 | 25456 | 25456 | 25456 |
| 20 | 23688 | 24496 | 24496 | 25456 | 25456 | 26416 | 26416 | 27376 | 27376 | 28336 |
| 21 | 25456 | 26416 | 26416 | 27376 | 27376 | 28336 | 28336 | 29296 | 29296 | 30576 |
| 22 | 27376 | 28336 | 28336 | 29296 | 29296 | 30576 | 30576 | 31704 | 31704 | 32856 |
| 23 | 29296 | 29296 | 30576 | 30576 | 31704 | 31704 | 32856 | 32856 | 34008 | 34008 |
| 24 | 31704 | 31704 | 32856 | 32856 | 34008 | 34008 | 35160 | 35160 | 36696 | 36696 |
| 25 | 32856 | 32856 | 34008 | 34008 | 35160 | 35160 | 36696 | 36696 | 37888 | 37888 |
| 26 | 37888 | 37888 | 39232 | 40576 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 |
| 26A | 32856 | 34008 | 34008 | 35160 | 36696 | 36696 | 36696 | 37888 | 37888 | 39232 |

| | | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 61 | 62 | 63 | 64 | 65 | 66 | 67 | 68 | 69 | 70 |
| 0 | 1672 | 1736 | 1736 | 1800 | 1800 | 1800 | 1864 | 1864 | 1928 | 1928 |
| 1 | 2216 | 2280 | 2280 | 2344 | 2344 | 2408 | 2472 | 2472 | 2536 | 2536 |
| 2 | 2728 | 2792 | 2856 | 2856 | 2856 | 2984 | 2984 | 3112 | 3112 | 3112 |
| 3 | 3624 | 3624 | 3624 | 3752 | 3752 | 3880 | 3880 | 4008 | 4008 | 4136 |
| 4 | 4392 | 4392 | 4584 | 4584 | 4584 | 4776 | 4776 | 4968 | 4968 | 4968 |
| 5 | 5352 | 5544 | 5544 | 5736 | 5736 | 5736 | 5992 | 5992 | 5992 | 6200 |
| 6 | 6456 | 6456 | 6456 | 6712 | 6712 | 6968 | 6968 | 6968 | 7224 | 7224 |
| 7 | 7480 | 7480 | 7736 | 7736 | 7992 | 7992 | 8248 | 8248 | 8504 | 8504 |
| 8 | 8504 | 8760 | 8760 | 9144 | 9144 | 9144 | 9528 | 9528 | 9528 | 9912 |
| 9 | 9528 | 9912 | 9912 | 10296 | 10296 | 10296 | 10680 | 10680 | 11064 | 11064 |
| 10 | 10680 | 11064 | 11064 | 11448 | 11448 | 11448 | 11832 | 11832 | 12216 | 12216 |
| 11 | 12216 | 12576 | 12576 | 12960 | 12960 | 13536 | 13536 | 13536 | 14112 | 14112 |
| 12 | 14112 | 14112 | 14112 | 14688 | 14688 | 15264 | 15264 | 15264 | 15840 | 15840 |
| 13 | 15840 | 15840 | 16416 | 16416 | 16992 | 16992 | 17568 | 17568 | 18336 | 18336 |
| 14 | 17568 | 17568 | 18336 | 18336 | 18336 | 19080 | 19080 | 19848 | 19848 | 19848 |
| 15 | 18336 | 19080 | 19080 | 19848 | 19848 | 20616 | 20616 | 20616 | 21384 | 21384 |
| 16 | 19848 | 19848 | 20616 | 20616 | 21384 | 21384 | 22152 | 22152 | 22152 | 22920 |
| 17 | 22152 | 22152 | 22920 | 22920 | 23688 | 23688 | 24496 | 24496 | 24496 | 25456 |
| 18 | 24496 | 24496 | 24496 | 25456 | 25456 | 26416 | 26416 | 27376 | 27376 | 27376 |
| 19 | 26416 | 26416 | 27376 | 27376 | 28336 | 28336 | 29296 | 29296 | 29296 | 30576 |
| 20 | 28336 | 29296 | 29296 | 29296 | 30576 | 30576 | 31704 | 31704 | 31704 | 32856 |
| 21 | 30576 | 31704 | 31704 | 31704 | 32856 | 32856 | 34008 | 34008 | 35160 | 35160 |
| 22 | 32856 | 34008 | 34008 | 34008 | 35160 | 35160 | 36696 | 36696 | 36696 | 37888 |
| 23 | 35160 | 35160 | 36696 | 36696 | 37888 | 37888 | 37888 | 39232 | 39232 | 40576 |
| 24 | 36696 | 37888 | 37888 | 39232 | 39232 | 40576 | 40576 | 42368 | 42368 | 42368 |
| 25 | 39232 | 39232 | 40576 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 43816 |
| 26 | 45352 | 45352 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 52752 |
| 26A | 40576 | 40576 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 45352 | 45352 |

| | | | | | | | | | | |
|-----------|-----------|------|------|------|------|------|------|------|------|------|
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 80 |
| 0 | 1992 | 1992 | 2024 | 2088 | 2088 | 2088 | 2152 | 2152 | 2216 | 2216 |
| 1 | 2600 | 2600 | 2664 | 2728 | 2728 | 2792 | 2792 | 2856 | 2856 | 2856 |
| 2 | 3240 | 3240 | 3240 | 3368 | 3368 | 3368 | 3496 | 3496 | 3496 | 3624 |
| 3 | 4136 | 4264 | 4264 | 4392 | 4392 | 4392 | 4584 | 4584 | 4584 | 4776 |
| 4 | 5160 | 5160 | 5160 | 5352 | 5352 | 5544 | 5544 | 5544 | 5736 | 5736 |

| | | | | | | | | | | |
|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 5 | 6200 | 6200 | 6456 | 6456 | 6712 | 6712 | 6712 | 6968 | 6968 | 6968 |
| 6 | 7480 | 7480 | 7736 | 7736 | 7736 | 7992 | 7992 | 8248 | 8248 | 8248 |
| 7 | 8760 | 8760 | 8760 | 9144 | 9144 | 9144 | 9528 | 9528 | 9528 | 9912 |
| 8 | 9912 | 9912 | 10296 | 10296 | 10680 | 10680 | 10680 | 11064 | 11064 | 11064 |
| 9 | 11064 | 11448 | 11448 | 11832 | 11832 | 11832 | 12216 | 12216 | 12576 | 12576 |
| 10 | 12576 | 12576 | 12960 | 12960 | 12960 | 13536 | 13536 | 13536 | 14112 | 14112 |
| 11 | 14112 | 14688 | 14688 | 14688 | 15264 | 15264 | 15840 | 15840 | 15840 | 16416 |
| 12 | 16416 | 16416 | 16416 | 16992 | 16992 | 17568 | 17568 | 17568 | 18336 | 18336 |
| 13 | 18336 | 18336 | 19080 | 19080 | 19080 | 19848 | 19848 | 19848 | 20616 | 20616 |
| 14 | 20616 | 20616 | 20616 | 21384 | 21384 | 22152 | 22152 | 22152 | 22920 | 22920 |
| 15 | 22152 | 22152 | 22152 | 22920 | 22920 | 23688 | 23688 | 23688 | 24496 | 24496 |
| 16 | 22920 | 23688 | 23688 | 24496 | 24496 | 24496 | 25456 | 25456 | 25456 | 26416 |
| 17 | 25456 | 26416 | 26416 | 26416 | 27376 | 27376 | 27376 | 28336 | 28336 | 29296 |
| 18 | 28336 | 28336 | 29296 | 29296 | 29296 | 30576 | 30576 | 30576 | 31704 | 31704 |
| 19 | 30576 | 30576 | 31704 | 31704 | 32856 | 32856 | 32856 | 34008 | 34008 | 34008 |
| 20 | 32856 | 34008 | 34008 | 34008 | 35160 | 35160 | 35160 | 36696 | 36696 | 36696 |
| 21 | 35160 | 36696 | 36696 | 36696 | 37888 | 37888 | 39232 | 39232 | 39232 | 40576 |
| 22 | 37888 | 39232 | 39232 | 40576 | 40576 | 40576 | 42368 | 42368 | 42368 | 43816 |
| 23 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 43816 | 45352 | 45352 | 45352 |
| 24 | 43816 | 43816 | 45352 | 45352 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 |
| 25 | 45352 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 |
| 26 | 52752 | 52752 | 55056 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 |
| 26A | 45352 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 51024 | 52752 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 81 | 82 | 83 | 84 | 85 | 86 | 87 | 88 | 89 | 90 |
| 0 | 2280 | 2280 | 2280 | 2344 | 2344 | 2408 | 2408 | 2472 | 2472 | 2536 |
| 1 | 2984 | 2984 | 2984 | 3112 | 3112 | 3112 | 3240 | 3240 | 3240 | 3240 |
| 2 | 3624 | 3624 | 3752 | 3752 | 3880 | 3880 | 3880 | 4008 | 4008 | 4008 |
| 3 | 4776 | 4776 | 4776 | 4968 | 4968 | 4968 | 5160 | 5160 | 5160 | 5352 |
| 4 | 5736 | 5992 | 5992 | 5992 | 5992 | 6200 | 6200 | 6200 | 6456 | 6456 |
| 5 | 7224 | 7224 | 7224 | 7480 | 7480 | 7480 | 7736 | 7736 | 7736 | 7992 |
| 6 | 8504 | 8504 | 8760 | 8760 | 8760 | 9144 | 9144 | 9144 | 9144 | 9528 |
| 7 | 9912 | 9912 | 10296 | 10296 | 10296 | 10680 | 10680 | 10680 | 11064 | 11064 |
| 8 | 11448 | 11448 | 11448 | 11832 | 11832 | 12216 | 12216 | 12216 | 12576 | 12576 |
| 9 | 12960 | 12960 | 12960 | 13536 | 13536 | 13536 | 13536 | 14112 | 14112 | 14112 |
| 10 | 14112 | 14688 | 14688 | 14688 | 14688 | 15264 | 15264 | 15264 | 15840 | 15840 |
| 11 | 16416 | 16416 | 16992 | 16992 | 16992 | 17568 | 17568 | 17568 | 18336 | 18336 |
| 12 | 18336 | 19080 | 19080 | 19080 | 19080 | 19848 | 19848 | 19848 | 20616 | 20616 |
| 13 | 20616 | 21384 | 21384 | 21384 | 22152 | 22152 | 22152 | 22920 | 22920 | 22920 |
| 14 | 22920 | 23688 | 23688 | 24496 | 24496 | 24496 | 25456 | 25456 | 25456 | 25456 |
| 15 | 24496 | 25456 | 25456 | 25456 | 26416 | 26416 | 26416 | 27376 | 27376 | 27376 |
| 16 | 26416 | 26416 | 27376 | 27376 | 27376 | 28336 | 28336 | 28336 | 29296 | 29296 |
| 17 | 29296 | 29296 | 30576 | 30576 | 30576 | 30576 | 31704 | 31704 | 31704 | 32856 |
| 18 | 31704 | 32856 | 32856 | 32856 | 34008 | 34008 | 34008 | 35160 | 35160 | 35160 |
| 19 | 35160 | 35160 | 35160 | 36696 | 36696 | 36696 | 37888 | 37888 | 37888 | 39232 |
| 20 | 37888 | 37888 | 39232 | 39232 | 39232 | 40576 | 40576 | 40576 | 42368 | 42368 |
| 21 | 40576 | 40576 | 42368 | 42368 | 42368 | 43816 | 43816 | 43816 | 45352 | 45352 |
| 22 | 43816 | 43816 | 45352 | 45352 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 |
| 23 | 46888 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 51024 | 51024 |
| 24 | 48936 | 51024 | 51024 | 51024 | 52752 | 52752 | 52752 | 52752 | 55056 | 55056 |
| 25 | 51024 | 52752 | 52752 | 52752 | 55056 | 55056 | 55056 | 55056 | 57336 | 57336 |
| 26 | 59256 | 59256 | 61664 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 | 66592 |
| 26A | 52752 | 52752 | 55056 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 91 | 92 | 93 | 94 | 95 | 96 | 97 | 98 | 99 | 100 |
| 0 | 2536 | 2536 | 2600 | 2600 | 2664 | 2664 | 2728 | 2728 | 2728 | 2792 |
| 1 | 3368 | 3368 | 3368 | 3496 | 3496 | 3496 | 3496 | 3624 | 3624 | 3624 |
| 2 | 4136 | 4136 | 4136 | 4264 | 4264 | 4264 | 4392 | 4392 | 4392 | 4584 |
| 3 | 5352 | 5352 | 5352 | 5544 | 5544 | 5544 | 5736 | 5736 | 5736 | 5736 |
| 4 | 6456 | 6456 | 6712 | 6712 | 6712 | 6968 | 6968 | 6968 | 6968 | 7224 |
| 5 | 7992 | 7992 | 8248 | 8248 | 8248 | 8504 | 8504 | 8760 | 8760 | 8760 |
| 6 | 9528 | 9528 | 9528 | 9912 | 9912 | 9912 | 10296 | 10296 | 10296 | 10296 |
| 7 | 11064 | 11448 | 11448 | 11448 | 11448 | 11832 | 11832 | 11832 | 12216 | 12216 |
| 8 | 12576 | 12960 | 12960 | 12960 | 13536 | 13536 | 13536 | 13536 | 14112 | 14112 |
| 9 | 14112 | 14688 | 14688 | 14688 | 15264 | 15264 | 15264 | 15264 | 15840 | 15840 |
| 10 | 15840 | 16416 | 16416 | 16416 | 16992 | 16992 | 16992 | 16992 | 17568 | 17568 |
| 11 | 18336 | 18336 | 19080 | 19080 | 19080 | 19080 | 19848 | 19848 | 19848 | 19848 |
| 12 | 20616 | 21384 | 21384 | 21384 | 21384 | 22152 | 22152 | 22152 | 22920 | 22920 |
| 13 | 23688 | 23688 | 23688 | 24496 | 24496 | 24496 | 25456 | 25456 | 25456 | 25456 |
| 14 | 26416 | 26416 | 26416 | 27376 | 27376 | 27376 | 28336 | 28336 | 28336 | 28336 |

| | | | | | | | | | | |
|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 15 | 28336 | 28336 | 28336 | 29296 | 29296 | 29296 | 29296 | 30576 | 30576 | 30576 |
| 16 | 29296 | 30576 | 30576 | 30576 | 30576 | 31704 | 31704 | 31704 | 31704 | 32856 |
| 17 | 32856 | 32856 | 34008 | 34008 | 34008 | 35160 | 35160 | 35160 | 35160 | 36696 |
| 18 | 36696 | 36696 | 36696 | 37888 | 37888 | 37888 | 37888 | 39232 | 39232 | 39232 |
| 19 | 39232 | 39232 | 40576 | 40576 | 40576 | 40576 | 42368 | 42368 | 42368 | 43816 |
| 20 | 42368 | 42368 | 43816 | 43816 | 43816 | 45352 | 45352 | 45352 | 46888 | 46888 |
| 21 | 45352 | 46888 | 46888 | 46888 | 46888 | 48936 | 48936 | 48936 | 48936 | 51024 |
| 22 | 48936 | 48936 | 51024 | 51024 | 51024 | 51024 | 52752 | 52752 | 52752 | 55056 |
| 23 | 52752 | 52752 | 52752 | 55056 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 |
| 24 | 55056 | 57336 | 57336 | 57336 | 57336 | 59256 | 59256 | 59256 | 61664 | 61664 |
| 25 | 57336 | 59256 | 59256 | 59256 | 61664 | 61664 | 61664 | 61664 | 63776 | 63776 |
| 26 | 66592 | 68808 | 68808 | 68808 | 71112 | 71112 | 71112 | 73712 | 73712 | 75376 |
| 26A | 59256 | 59256 | 59256 | 61664 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 101 | 102 | 103 | 104 | 105 | 106 | 107 | 108 | 109 | 110 |
| 0 | 2792 | 2856 | 2856 | 2856 | 2984 | 2984 | 2984 | 2984 | 2984 | 3112 |
| 1 | 3752 | 3752 | 3752 | 3752 | 3880 | 3880 | 3880 | 4008 | 4008 | 4008 |
| 2 | 4584 | 4584 | 4584 | 4584 | 4776 | 4776 | 4776 | 4776 | 4968 | 4968 |
| 3 | 5992 | 5992 | 5992 | 5992 | 6200 | 6200 | 6200 | 6200 | 6456 | 6456 |
| 4 | 7224 | 7224 | 7480 | 7480 | 7480 | 7480 | 7736 | 7736 | 7736 | 7992 |
| 5 | 8760 | 9144 | 9144 | 9144 | 9144 | 9528 | 9528 | 9528 | 9528 | 9528 |
| 6 | 10680 | 10680 | 10680 | 10680 | 11064 | 11064 | 11064 | 11448 | 11448 | 11448 |
| 7 | 12216 | 12576 | 12576 | 12576 | 12960 | 12960 | 12960 | 12960 | 13536 | 13536 |
| 8 | 14112 | 14112 | 14688 | 14688 | 14688 | 14688 | 15264 | 15264 | 15264 | 15264 |
| 9 | 15840 | 16416 | 16416 | 16416 | 16416 | 16992 | 16992 | 16992 | 16992 | 17568 |
| 10 | 17568 | 18336 | 18336 | 18336 | 18336 | 18336 | 19080 | 19080 | 19080 | 19080 |
| 11 | 20616 | 20616 | 20616 | 21384 | 21384 | 21384 | 21384 | 22152 | 22152 | 22152 |
| 12 | 22920 | 23688 | 23688 | 23688 | 23688 | 24496 | 24496 | 24496 | 24496 | 25456 |
| 13 | 26416 | 26416 | 26416 | 26416 | 27376 | 27376 | 27376 | 27376 | 28336 | 28336 |
| 14 | 29296 | 29296 | 29296 | 29296 | 30576 | 30576 | 30576 | 30576 | 31704 | 31704 |
| 15 | 30576 | 31704 | 31704 | 31704 | 31704 | 32856 | 32856 | 32856 | 34008 | 34008 |
| 16 | 32856 | 32856 | 34008 | 34008 | 34008 | 34008 | 35160 | 35160 | 35160 | 35160 |
| 17 | 36696 | 36696 | 36696 | 37888 | 37888 | 37888 | 39232 | 39232 | 39232 | 39232 |
| 18 | 40576 | 40576 | 40576 | 40576 | 42368 | 42368 | 42368 | 42368 | 43816 | 43816 |
| 19 | 43816 | 43816 | 43816 | 45352 | 45352 | 45352 | 46888 | 46888 | 46888 | 46888 |
| 20 | 46888 | 46888 | 48936 | 48936 | 48936 | 48936 | 48936 | 51024 | 51024 | 51024 |
| 21 | 51024 | 51024 | 51024 | 52752 | 52752 | 52752 | 52752 | 55056 | 55056 | 55056 |
| 22 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 57336 | 59256 | 59256 | 59256 |
| 23 | 57336 | 59256 | 59256 | 59256 | 59256 | 61664 | 61664 | 61664 | 61664 | 63776 |
| 24 | 61664 | 61664 | 63776 | 63776 | 63776 | 63776 | 66592 | 66592 | 66592 | 66592 |
| 25 | 63776 | 63776 | 66592 | 66592 | 66592 | 66592 | 68808 | 68808 | 68808 | 71112 |
| 26 | 75376 | 75376 | 75376 | 75376 | 75376 | 75376 | 75376 | 75376 | 75376 | 75376 |
| 26A | 66592 | 66592 | 66592 | 68808 | 68808 | 68808 | 71112 | 71112 | 71112 | 71112 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|------|------|------|------|------|------|------|------|------|
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 27 | 648 | 1320 | 1992 | 2664 | 3368 | 4008 | 4584 | 5352 | 5992 | 6712 |
| 28 | 680 | 1384 | 2088 | 2792 | 3496 | 4264 | 4968 | 5544 | 6200 | 6968 |
| 29 | 712 | 1480 | 2216 | 2984 | 3752 | 4392 | 5160 | 5992 | 6712 | 7480 |
| 30 | 776 | 1544 | 2344 | 3112 | 3880 | 4776 | 5544 | 6200 | 6968 | 7736 |
| 31 | 808 | 1608 | 2472 | 3240 | 4136 | 4968 | 5736 | 6456 | 7480 | 8248 |
| 32 | 840 | 1672 | 2536 | 3368 | 4264 | 5160 | 5992 | 6712 | 7736 | 8504 |
| 33 | 968 | 1992 | 2984 | 4008 | 4968 | 5992 | 6968 | 7992 | 8760 | 9912 |
| 33A | 840 | 1736 | 2600 | 3496 | 4392 | 5160 | 5992 | 6968 | 7736 | 8760 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| 27 | 7224 | 7992 | 8504 | 9144 | 9912 | 10680 | 11448 | 11832 | 12576 | 12960 |
| 28 | 7736 | 8504 | 9144 | 9912 | 10680 | 11064 | 11832 | 12576 | 13536 | 14112 |
| 29 | 8248 | 8760 | 9528 | 10296 | 11064 | 11832 | 12576 | 13536 | 14112 | 14688 |
| 30 | 8504 | 9528 | 10296 | 11064 | 11832 | 12576 | 13536 | 14112 | 14688 | 15840 |
| 31 | 9144 | 9912 | 10680 | 11448 | 12216 | 12960 | 14112 | 14688 | 15840 | 16416 |
| 32 | 9528 | 10296 | 11064 | 11832 | 12960 | 13536 | 14688 | 15264 | 16416 | 16992 |
| 33 | 10680 | 11832 | 12960 | 13536 | 14688 | 15840 | 16992 | 17568 | 19080 | 19848 |
| 33A | 9528 | 10296 | 11448 | 12216 | 12960 | 14112 | 14688 | 15840 | 16416 | 17568 |

| I_{TBS} | N_{PRB} | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 |
| 27 | 14112 | 14688 | 15264 | 15840 | 16416 | 16992 | 17568 | 18336 | 19080 | 19848 |

| | | | | | | | | | | |
|-----------|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 28 | 14688 | 15264 | 16416 | 16992 | 17568 | 18336 | 19080 | 19848 | 20616 | 21384 |
| 29 | 15840 | 16416 | 16992 | 17568 | 18336 | 19080 | 19848 | 20616 | 21384 | 22152 |
| 30 | 16416 | 16992 | 18336 | 19080 | 19848 | 20616 | 21384 | 22152 | 22920 | 23688 |
| 31 | 17568 | 18336 | 19080 | 19848 | 20616 | 21384 | 22152 | 22920 | 23688 | 24496 |
| 32 | 17568 | 19080 | 19848 | 20616 | 21384 | 22152 | 22920 | 23688 | 24496 | 25456 |
| 33 | 20616 | 21384 | 22920 | 23688 | 24496 | 25456 | 26416 | 27376 | 28336 | 29296 |
| 33A | 18336 | 19080 | 19848 | 20616 | 22152 | 22920 | 23688 | 24496 | 25456 | 26416 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 |
| 27 | 20616 | 21384 | 22152 | 22920 | 22920 | 23688 | 24496 | 25456 | 25456 | 26416 |
| 28 | 22152 | 22152 | 22920 | 23688 | 24496 | 25456 | 26416 | 26416 | 27376 | 28336 |
| 29 | 22920 | 23688 | 24496 | 25456 | 26416 | 26416 | 27376 | 28336 | 29296 | 29296 |
| 30 | 24496 | 25456 | 25456 | 26416 | 27376 | 28336 | 29296 | 29296 | 30576 | 31704 |
| 31 | 25456 | 26416 | 27376 | 28336 | 29296 | 29296 | 30576 | 31704 | 31704 | 32856 |
| 32 | 26416 | 27376 | 28336 | 29296 | 29296 | 30576 | 31704 | 32856 | 32856 | 34008 |
| 33 | 30576 | 31704 | 32856 | 34008 | 35160 | 35160 | 36696 | 37888 | 39232 | 39232 |
| 33A | 27376 | 27376 | 29296 | 29296 | 30576 | 30576 | 31704 | 32856 | 34008 | 35160 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 |
| 27 | 27376 | 27376 | 28336 | 29296 | 29296 | 30576 | 31704 | 31704 | 32856 | 32856 |
| 28 | 29296 | 29296 | 30576 | 30576 | 31704 | 32856 | 32856 | 34008 | 34008 | 35160 |
| 29 | 30576 | 31704 | 31704 | 32856 | 34008 | 34008 | 35160 | 35160 | 36696 | 36696 |
| 30 | 31704 | 32856 | 34008 | 34008 | 35160 | 36696 | 36696 | 37888 | 37888 | 39232 |
| 31 | 34008 | 35160 | 35160 | 36696 | 36696 | 37888 | 39232 | 39232 | 40576 | 40576 |
| 32 | 35160 | 35160 | 36696 | 37888 | 37888 | 39232 | 40576 | 40576 | 42368 | 42368 |
| 33 | 40576 | 40576 | 42368 | 43816 | 43816 | 45352 | 46888 | 46888 | 48936 | 48936 |
| 33A | 35160 | 36696 | 36696 | 37888 | 39232 | 40576 | 40576 | 40576 | 42368 | 43816 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 51 | 52 | 53 | 54 | 55 | 56 | 57 | 58 | 59 | 60 |
| 27 | 34008 | 34008 | 35160 | 35160 | 36696 | 36696 | 37888 | 37888 | 39232 | 39232 |
| 28 | 35160 | 36696 | 36696 | 37888 | 39232 | 39232 | 40576 | 40576 | 42368 | 42368 |
| 29 | 37888 | 39232 | 39232 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 45352 |
| 30 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 45352 | 45352 | 46888 | 46888 |
| 31 | 42368 | 42368 | 43816 | 45352 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 |
| 32 | 43816 | 43816 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 | 51024 | 51024 |
| 33 | 51024 | 51024 | 52752 | 52752 | 55056 | 55056 | 57336 | 57336 | 59256 | 59256 |
| 33A | 43816 | 45352 | 45352 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 52752 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 61 | 62 | 63 | 64 | 65 | 66 | 67 | 68 | 69 | 70 |
| 27 | 40576 | 40576 | 42368 | 42368 | 43816 | 43816 | 43816 | 45352 | 45352 | 46888 |
| 28 | 42368 | 43816 | 43816 | 45352 | 45352 | 46888 | 46888 | 46888 | 48936 | 48936 |
| 29 | 45352 | 45352 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 52752 |
| 30 | 46888 | 48936 | 48936 | 51024 | 51024 | 51024 | 52752 | 52752 | 55056 | 55056 |
| 31 | 51024 | 51024 | 52752 | 52752 | 52752 | 55056 | 55056 | 55056 | 57336 | 57336 |
| 32 | 52752 | 52752 | 52752 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 | 59256 |
| 33 | 59256 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 | 66592 | 68808 | 68808 |
| 33A | 52752 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 | 59256 | 61664 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 71 | 72 | 73 | 74 | 75 | 76 | 77 | 78 | 79 | 80 |
| 27 | 46888 | 46888 | 48936 | 48936 | 48936 | 51024 | 51024 | 51024 | 52752 | 52752 |
| 28 | 48936 | 51024 | 51024 | 52752 | 52752 | 52752 | 55056 | 55056 | 55056 | 57336 |
| 29 | 52752 | 52752 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 | 59256 |
| 30 | 55056 | 57336 | 57336 | 57336 | 59256 | 59256 | 59256 | 61664 | 61664 | 63776 |
| 31 | 59256 | 59256 | 59256 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 | 66592 |
| 32 | 61664 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 | 66592 | 66592 | 68808 |
| 33 | 71112 | 71112 | 71112 | 73712 | 75376 | 76208 | 76208 | 76208 | 78704 | 78704 |
| 33A | 61664 | 61664 | 63776 | 63776 | 66592 | 66592 | 66592 | 68808 | 68808 | 68808 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 81 | 82 | 83 | 84 | 85 | 86 | 87 | 88 | 89 | 90 |
| 27 | 52752 | 55056 | 55056 | 55056 | 57336 | 57336 | 57336 | 59256 | 59256 | 59256 |
| 28 | 57336 | 57336 | 59256 | 59256 | 59256 | 61664 | 61664 | 61664 | 61664 | 63776 |
| 29 | 59256 | 61664 | 61664 | 61664 | 63776 | 63776 | 63776 | 66592 | 66592 | 66592 |

| | | | | | | | | | | |
|-----------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| 30 | 63776 | 63776 | 63776 | 66592 | 66592 | 66592 | 68808 | 68808 | 68808 | 71112 |
| 31 | 66592 | 68808 | 68808 | 68808 | 71112 | 71112 | 71112 | 73712 | 73712 | 73712 |
| 32 | 68808 | 71112 | 71112 | 71112 | 73712 | 73712 | 73712 | 75376 | 76208 | 76208 |
| 33 | 81176 | 81176 | 81176 | 81176 | 84760 | 84760 | 84760 | 87936 | 87936 | 87936 |
| 33A | 71112 | 71112 | 71112 | 73712 | 75376 | 75376 | 76208 | 76208 | 78704 | 78704 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 91 | 92 | 93 | 94 | 95 | 96 | 97 | 98 | 99 | 100 |
| 27 | 59256 | 61664 | 61664 | 61664 | 63776 | 63776 | 63776 | 63776 | 66592 | 66592 |
| 28 | 63776 | 63776 | 66592 | 66592 | 66592 | 66592 | 68808 | 68808 | 68808 | 71112 |
| 29 | 66592 | 68808 | 68808 | 68808 | 71112 | 71112 | 71112 | 73712 | 73712 | 73712 |
| 30 | 71112 | 71112 | 73712 | 73712 | 75376 | 75376 | 76208 | 76208 | 78704 | 78704 |
| 31 | 75376 | 76208 | 76208 | 78704 | 78704 | 78704 | 81176 | 81176 | 81176 | 81176 |
| 32 | 78704 | 78704 | 78704 | 81176 | 81176 | 81176 | 84760 | 84760 | 84760 | 84760 |
| 33 | 90816 | 90816 | 90816 | 93800 | 93800 | 93800 | 93800 | 97896 | 97896 | 97896 |
| 33A | 78704 | 81176 | 81176 | 81176 | 81176 | 84760 | 84760 | 84760 | 84760 | 87936 |
| I_{TBS} | N_{PRB} | | | | | | | | | |
| | 101 | 102 | 103 | 104 | 105 | 106 | 107 | 108 | 109 | 110 |
| 27 | 66592 | 66592 | 68808 | 68808 | 68808 | 71112 | 71112 | 71112 | 71112 | 73712 |
| 28 | 71112 | 71112 | 73712 | 73712 | 73712 | 75376 | 75376 | 76208 | 76208 | 76208 |
| 29 | 75376 | 76208 | 76208 | 76208 | 78704 | 78704 | 78704 | 81176 | 81176 | 81176 |
| 30 | 78704 | 81176 | 81176 | 81176 | 81176 | 84760 | 84760 | 84760 | 84760 | 87936 |
| 31 | 84760 | 84760 | 84760 | 84760 | 87936 | 87936 | 87936 | 87936 | 90816 | 90816 |
| 32 | 87936 | 87936 | 87936 | 87936 | 90816 | 90816 | 90816 | 93800 | 93800 | 93800 |
| 33 | 97896 | 97896 | 97896 | 97896 | 97896 | 97896 | 97896 | 97896 | 97896 | 97896 |
| 33A | 87936 | 87936 | 87936 | 90816 | 90816 | 90816 | 93800 | 93800 | 93800 | 97896 |

7.1.7.2.2 Transport blocks mapped to two-layer spatial multiplexing

For $1 \leq N_{\text{PRB}} \leq 55$, the TBS is given by the $(I_{\text{TBS}}, 2 \cdot N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1.

For $56 \leq N_{\text{PRB}} \leq 110$, a baseline TBS_L1 is taken from the $(I_{\text{TBS}}, N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1, which is then translated into TBS_L2 using the mapping rule shown in Table 7.1.7.2.2-1. The TBS is given by TBS_L2.

Table 7.1.7.2.2-1: One-layer to two-layer TBS translation table

| TBS_L1 | TBS_L2 | TBS_L1 | TBS_L2 | TBS_L1 | TBS_L2 | TBS_L1 | TBS_L2 |
|--------|--------|--------|--------|--------|--------|--------|--------|
| 1544 | 3112 | 3752 | 7480 | 10296 | 20616 | 28336 | 57336 |
| 1608 | 3240 | 3880 | 7736 | 10680 | 21384 | 29296 | 59256 |
| 1672 | 3368 | 4008 | 7992 | 11064 | 22152 | 30576 | 61664 |
| 1736 | 3496 | 4136 | 8248 | 11448 | 22920 | 31704 | 63776 |
| 1800 | 3624 | 4264 | 8504 | 11832 | 23688 | 32856 | 66592 |
| 1864 | 3752 | 4392 | 8760 | 12216 | 24496 | 34008 | 68808 |
| 1928 | 3880 | 4584 | 9144 | 12576 | 25456 | 35160 | 71112 |
| 1992 | 4008 | 4776 | 9528 | 12960 | 25456 | 36696 | 73712 |
| 2024 | 4008 | 4968 | 9912 | 13536 | 27376 | 37888 | 76208 |
| 2088 | 4136 | 5160 | 10296 | 14112 | 28336 | 39232 | 78704 |
| 2152 | 4264 | 5352 | 10680 | 14688 | 29296 | 40576 | 81176 |
| 2216 | 4392 | 5544 | 11064 | 15264 | 30576 | 42368 | 84760 |
| 2280 | 4584 | 5736 | 11448 | 15840 | 31704 | 43816 | 87936 |
| 2344 | 4776 | 5992 | 11832 | 16416 | 32856 | 45352 | 90816 |
| 2408 | 4776 | 6200 | 12576 | 16992 | 34008 | 46888 | 93800 |
| 2472 | 4968 | 6456 | 12960 | 17568 | 35160 | 48936 | 97896 |
| 2536 | 5160 | 6712 | 13536 | 18336 | 36696 | 51024 | 101840 |
| 2600 | 5160 | 6968 | 14112 | 19080 | 37888 | 52752 | 105528 |
| 2664 | 5352 | 7224 | 14688 | 19848 | 39232 | 55056 | 110136 |
| 2728 | 5544 | 7480 | 14688 | 20616 | 40576 | 57336 | 115040 |
| 2792 | 5544 | 7736 | 15264 | 21384 | 42368 | 59256 | 119816 |
| 2856 | 5736 | 7992 | 15840 | 22152 | 43816 | 61664 | 124464 |
| 2984 | 5992 | 8248 | 16416 | 22920 | 45352 | 63776 | 128496 |
| 3112 | 6200 | 8504 | 16992 | 23688 | 46888 | 66592 | 133208 |
| 3240 | 6456 | 8760 | 17568 | 24496 | 48936 | 68808 | 137792 |
| 3368 | 6712 | 9144 | 18336 | 25456 | 51024 | 71112 | 142248 |
| 3496 | 6968 | 9528 | 19080 | 26416 | 52752 | 73712 | 146856 |
| 3624 | 7224 | 9912 | 19848 | 27376 | 55056 | 75376 | 149776 |
| 76208 | 152976 | 81176 | 161760 | 87936 | 175600 | 93800 | 187712 |
| 78704 | 157432 | 84760 | 169544 | 90816 | 181656 | 97896 | 195816 |

7.1.7.2.3 Transport blocks mapped for DCI Format 1C

The TBS is given by the I_{TBS} entry of Table 7.1.7.2.3-1.

Table 7.1.7.2.3-1: Transport Block Size (TBS) table for DCI format 1C

| I_{TBS} | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
|------------------|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|
| TBS | 40 | 56 | 72 | 120 | 136 | 144 | 176 | 208 | 224 | 256 | 280 | 296 | 328 | 336 | 392 | 488 |
| I_{TBS} | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 |
| TBS | 552 | 600 | 632 | 696 | 776 | 840 | 904 | 1000 | 1064 | 1128 | 1224 | 1288 | 1384 | 1480 | 1608 | 1736 |

7.1.7.2.4 Transport blocks mapped to three-layer spatial multiplexing

For $1 \leq N_{\text{PRB}} \leq 36$, the TBS is given by the $(I_{\text{TBS}}, 3 \cdot N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1.

For $37 \leq N_{\text{PRB}} \leq 110$, a baseline TBS_L1 is taken from the $(I_{\text{TBS}}, N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1, which is then translated into TBS_L3 using the mapping rule shown in Table 7.1.7.2.4-1. The TBS is given by TBS_L3.

Table 7.1.7.2.4-1: One-layer to three-layer TBS translation table

| TBS_L1 | TBS_L3 | TBS_L1 | TBS_L3 | TBS_L1 | TBS_L3 | TBS_L1 | TBS_L3 |
|--------|--------|--------|--------|--------|--------|--------|--------|
| 1032 | 3112 | 2664 | 7992 | 8248 | 24496 | 26416 | 78704 |
| 1064 | 3240 | 2728 | 8248 | 8504 | 25456 | 27376 | 81176 |
| 1096 | 3240 | 2792 | 8248 | 8760 | 26416 | 28336 | 84760 |
| 1128 | 3368 | 2856 | 8504 | 9144 | 27376 | 29296 | 87936 |
| 1160 | 3496 | 2984 | 8760 | 9528 | 28336 | 30576 | 90816 |
| 1192 | 3624 | 3112 | 9144 | 9912 | 29296 | 31704 | 93800 |
| 1224 | 3624 | 3240 | 9528 | 10296 | 30576 | 32856 | 97896 |
| 1256 | 3752 | 3368 | 9912 | 10680 | 31704 | 34008 | 101840 |
| 1288 | 3880 | 3496 | 10296 | 11064 | 32856 | 35160 | 105528 |
| 1320 | 4008 | 3624 | 10680 | 11448 | 34008 | 36696 | 110136 |
| 1352 | 4008 | 3752 | 11064 | 11832 | 35160 | 37888 | 115040 |
| 1384 | 4136 | 3880 | 11448 | 12216 | 36696 | 39232 | 119816 |
| 1416 | 4264 | 4008 | 11832 | 12576 | 37888 | 40576 | 119816 |
| 1480 | 4392 | 4136 | 12576 | 12960 | 39232 | 42368 | 128496 |
| 1544 | 4584 | 4264 | 12960 | 13536 | 40576 | 43816 | 133208 |
| 1608 | 4776 | 4392 | 12960 | 14112 | 42368 | 45352 | 137792 |
| 1672 | 4968 | 4584 | 13536 | 14688 | 43816 | 46888 | 142248 |
| 1736 | 5160 | 4776 | 14112 | 15264 | 45352 | 48936 | 146856 |
| 1800 | 5352 | 4968 | 14688 | 15840 | 46888 | 51024 | 152976 |
| 1864 | 5544 | 5160 | 15264 | 16416 | 48936 | 52752 | 157432 |
| 1928 | 5736 | 5352 | 15840 | 16992 | 51024 | 55056 | 165216 |
| 1992 | 5992 | 5544 | 16416 | 17568 | 52752 | 57336 | 171888 |
| 2024 | 5992 | 5736 | 16992 | 18336 | 55056 | 59256 | 177816 |
| 2088 | 6200 | 5992 | 18336 | 19080 | 57336 | 61664 | 185728 |
| 2152 | 6456 | 6200 | 18336 | 19848 | 59256 | 63776 | 191720 |
| 2216 | 6712 | 6456 | 19080 | 20616 | 61664 | 66592 | 199824 |
| 2280 | 6712 | 6712 | 19848 | 21384 | 63776 | 68808 | 205880 |
| 2344 | 6968 | 6968 | 20616 | 22152 | 66592 | 71112 | 214176 |
| 2408 | 7224 | 7224 | 21384 | 22920 | 68808 | 73712 | 221680 |
| 2472 | 7480 | 7480 | 22152 | 23688 | 71112 | 75376 | 226416 |
| 2536 | 7480 | 7736 | 22920 | 24496 | 73712 | | |
| 2600 | 7736 | 7992 | 23688 | 25456 | 76208 | | |
| 76208 | 230104 | 81176 | 245648 | 87936 | 266440 | 93800 | 284608 |
| 78704 | 236160 | 84760 | 254328 | 90816 | 275376 | 97896 | 293736 |

7.1.7.2.5 Transport blocks mapped to four-layer spatial multiplexing

For $1 \leq N_{\text{PRB}} \leq 27$, the TBS is given by the $(I_{\text{TBS}}, 4 \cdot N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1.

For $28 \leq N_{\text{PRB}} \leq 110$, a baseline TBS_L1 is taken from the $(I_{\text{TBS}}, N_{\text{PRB}})$ entry of Table 7.1.7.2.1-1, which is then translated into TBS_L4 using the mapping rule shown in Table 7.1.7.2.5-1. The TBS is given by TBS_L4.

Table 7.1.7.2.5-1: One-layer to four-layer TBS translation table

| TBS_L1 | TBS_L4 | TBS_L1 | TBS_L4 | TBS_L1 | TBS_L4 | TBS_L1 | TBS_L4 |
|--------|--------|--------|--------|--------|--------|--------|--------|
| 776 | 3112 | 2280 | 9144 | 7224 | 29296 | 24496 | 97896 |
| 808 | 3240 | 2344 | 9528 | 7480 | 29296 | 25456 | 101840 |
| 840 | 3368 | 2408 | 9528 | 7736 | 30576 | 26416 | 105528 |
| 872 | 3496 | 2472 | 9912 | 7992 | 31704 | 27376 | 110136 |
| 904 | 3624 | 2536 | 10296 | 8248 | 32856 | 28336 | 115040 |
| 936 | 3752 | 2600 | 10296 | 8504 | 34008 | 29296 | 115040 |
| 968 | 3880 | 2664 | 10680 | 8760 | 35160 | 30576 | 124464 |
| 1000 | 4008 | 2728 | 11064 | 9144 | 36696 | 31704 | 128496 |
| 1032 | 4136 | 2792 | 11064 | 9528 | 37888 | 32856 | 133208 |
| 1064 | 4264 | 2856 | 11448 | 9912 | 39232 | 34008 | 137792 |
| 1096 | 4392 | 2984 | 11832 | 10296 | 40576 | 35160 | 142248 |
| 1128 | 4584 | 3112 | 12576 | 10680 | 42368 | 36696 | 146856 |
| 1160 | 4584 | 3240 | 12960 | 11064 | 43816 | 37888 | 151376 |
| 1192 | 4776 | 3368 | 13536 | 11448 | 45352 | 39232 | 157432 |
| 1224 | 4968 | 3496 | 14112 | 11832 | 46888 | 40576 | 161760 |
| 1256 | 4968 | 3624 | 14688 | 12216 | 48936 | 42368 | 169544 |
| 1288 | 5160 | 3752 | 15264 | 12576 | 51024 | 43816 | 175600 |
| 1320 | 5352 | 3880 | 15264 | 12960 | 51024 | 45352 | 181656 |
| 1352 | 5352 | 4008 | 15840 | 13536 | 55056 | 46888 | 187712 |
| 1384 | 5544 | 4136 | 16416 | 14112 | 57336 | 48936 | 195816 |
| 1416 | 5736 | 4264 | 16992 | 14688 | 59256 | 51024 | 203704 |
| 1480 | 5992 | 4392 | 17568 | 15264 | 61664 | 52752 | 211936 |
| 1544 | 6200 | 4584 | 18336 | 15840 | 63776 | 55056 | 220296 |
| 1608 | 6456 | 4776 | 19080 | 16416 | 66592 | 57336 | 230104 |
| 1672 | 6712 | 4968 | 19848 | 16992 | 68808 | 59256 | 236160 |
| 1736 | 6968 | 5160 | 20616 | 17568 | 71112 | 61664 | 245648 |
| 1800 | 7224 | 5352 | 21384 | 18336 | 73712 | 63776 | 254328 |
| 1864 | 7480 | 5544 | 22152 | 19080 | 76208 | 66592 | 266440 |
| 1928 | 7736 | 5736 | 22920 | 19848 | 78704 | 68808 | 275376 |
| 1992 | 7992 | 5992 | 23688 | 20616 | 81176 | 71112 | 284608 |
| 2024 | 7992 | 6200 | 24496 | 21384 | 84760 | 73712 | 293736 |
| 2088 | 8248 | 6456 | 25456 | 22152 | 87936 | 75376 | 299856 |
| 2152 | 8504 | 6712 | 26416 | 22920 | 90816 | | |
| 2216 | 8760 | 6968 | 28336 | 23688 | 93800 | | |
| 76208 | 305976 | 81176 | 324336 | 87936 | 351224 | 93800 | 375448 |
| 78704 | 314888 | 84760 | 339112 | 90816 | 363336 | 97896 | 391656 |

7.1.7.3 Redundancy Version determination for Format 1C

If the DCI Format 1C CRC is scrambled by P-RNTI or RA-RNTI, then

- the UE shall set the Redundancy Version to 0

Else if the DCI Format 1C CRC is scrambled by SI-RNTI, then

- the UE shall set the Redundancy Version as defined in [8].

7.1.8 Storing soft channel bits

For FDD, TDD and FDD-TDD, if the UE is configured with more than one serving cell or if the UE is configured with a SCG, then for each serving cell, for at least $K_{\text{MIMO}} \cdot \min(M_{\text{DL_HARQ}}, M_{\text{limit}})$ transport blocks, upon decoding failure of a code block of a transport block, the UE shall store received soft channel bits corresponding to a range of at least

$W_k, W_{k+1}, \dots, W_{\text{mod}(k+n_{\text{SB}}-1, N_{\text{cb}})}$, where:

$$n_{\text{SB}} = \min \left(N_{\text{cb}}, \left\lfloor \frac{N'_{\text{soft}}}{C \cdot N_{\text{cells}}^{\text{DL}} \cdot K_{\text{MIMO}} \cdot \min(M_{\text{DL_HARQ}}, M_{\text{limit}})} \right\rfloor \right),$$

W_k , C , N_{cb} , K_{MIMO} , and M_{limit} are defined in subclause 5.1.4.1.2 of [4].

$M_{\text{DL_HARQ}}$ is the maximum number of DL HARQ processes.

If the UE is configured with a SCG

- $N_{\text{cells}}^{\text{DL}}$ is the number of configured serving cells across both MCG and SCG.

else

- $N_{\text{cells}}^{\text{DL}}$ is the number of configured serving cells.

If the UE signals *ue-CategoryDL-r12*, N'_{soft} is the total number of soft channel bits [12] according to the UE category indicated by *ue-CategoryDL-r12* [11]. Else if the UE signals *ue-Category-v1170* and not *ue-CategoryDL-r12*, N'_{soft} is the total number of soft channel bits [12] according to the UE category indicated by *ue-Category-v1170* [11]. Else if the UE signals *ue-Category-v1020* and not *ue-Category-v1170* and not *ue-CategoryDL-r12*, N'_{soft} is the total number of soft channel bits [12] according to the UE category indicated by *ue-Category-v1020* [11]. Otherwise, N'_{soft} is the total number of soft channel bits [12] according to the UE category indicated by *ue-Category* (without suffix) [11].

In determining k , the UE should give priority to storing soft channel bits corresponding to lower values of k . W_k shall correspond to a received soft channel bit. The range $W_k, W_{k+1}, \dots, W_{\text{mod}(k+n_{\text{SB}}-1, N_{\text{cb}})}$ may include subsets not containing received soft channel bits.

7.1.9 PDSCH resource mapping parameters

A UE configured in transmission mode 10 for a given serving cell can be configured with up to 4 parameter sets by higher layer signaling to decode PDSCH according to a detected PDCCH/EPDCCH with DCI format 2D intended for the UE and the given serving cell. The UE shall use the parameter set according to the value of the 'PDSCH RE Mapping and Quasi-Co-Location indicator' field (mapping defined in Table 7.1.9-1) in the detected PDCCH/EPDCCH with DCI format 2D for determining the PDSCH RE mapping (defined in subclause 6.4 of [3]), and for determining PDSCH antenna port quasi co-location (defined in subclause 7.1.10) if the UE is configured with Type B quasi co-location type (defined in subclause 7.1.10). For PDSCH without a corresponding PDCCH/EPDCCH, the UE shall use the parameter set indicated in the PDCCH/EPDCCH with DCI format 2D corresponding to the associated SPS activation for determining the PDSCH RE mapping (defined in subclause 6.4 of [3]) and PDSCH antenna port quasi co-location (defined in subclause 7.1.10).

Table 7.1.9-1: PDSCH RE Mapping and Quasi-Co-Location Indicator field in DCI format 2D

| Value of 'PDSCH RE Mapping and Quasi-Co-Location Indicator' field | Description |
|---|---|
| '00' | Parameter set 1 configured by higher layers |
| '01' | Parameter set 2 configured by higher layers |
| '10' | Parameter set 3 configured by higher layers |
| '11' | Parameter set 4 configured by higher layers |

The following parameters for determining PDSCH RE mapping and PDSCH antenna port quasi co-location are configured via higher layer signaling for each parameter set:

- *crs-PortsCount-r11*.
- *crs-FreqShift-r11*.
- *mbsfn-SubframeConfigList-r11*.
- *csi-RS-ConfigZPID-r11*.
- *pdsch-Start-r11*.
- *qcl-CSI-RS-ConfigNZPID-r11*.

To decode PDSCH according to a detected PDCCH/EPDCCH with DCI format 1A with CRC scrambled with C-RNTI intended for the UE and the given serving cell and for PDSCH transmission on antenna port 7, a UE configured in transmission mode 10 for a given serving cell shall use the parameter set 1 in table 7.1.9-1 for determining the PDSCH RE mapping (defined in subclause 6.4 of [3]), and for determining PDSCH antenna port quasi co-location (defined in subclause 7.1.10) if the UE is configured with Type B quasi co-location type (defined in subclause 7.1.10).

To decode PDSCH corresponding to detected PDCCH/EPDCCH with DCI format 1A with CRC scrambled with SPS C-RNTI and PDSCH without a corresponding PDCCH/EPDCCH associated with SPS activation indicated in PDCCH/EPDCCH with DCI format 1A, a UE configured in transmission mode 10 for a given serving cell shall use the parameter set 1 in table 7.1.9-1 for determining the PDSCH RE mapping (defined in subclause 6.4 of [3]), and for determining PDSCH antenna port quasi co-location (defined in subclause 7.1.10) if the UE is configured with Type B quasi co-location type (defined in subclause 7.1.10).

To decode PDSCH according to a detected PDCCH/EPDCCH with DCI format 1A intended for the UE on a given serving cell and for PDSCH transmission on antenna port 0 – 3, a UE configured in transmission mode 10 for the given serving cell shall determine the PDSCH RE mapping (as described in subclause 6.4 of [3]) using the lowest indexed zero-power CSI-RS resource.

7.1.10 Antenna ports quasi co-location for PDSCH

A UE configured in transmission mode 8-10 for a serving cell may assume the antenna ports 7 – 14 of the serving cell are quasi co-located (as defined in [3]) for a given subframe with respect to delay spread, Doppler spread, Doppler shift, average gain, and average delay.

A UE configured in transmission mode 1-9 for a serving cell may assume the antenna ports 0 – 3, 5, 7 – 22 of the serving cell are quasi co-located (as defined in [3]) with respect to Doppler shift, Doppler spread, average delay, and delay spread.

A UE configured in transmission mode 10 for a serving cell is configured with one of two quasi co-location types for the serving cell by higher layer parameter *qcl-Operation* to decode PDSCH according to transmission scheme associated with antenna ports 7-14:

- Type A: The UE may assume the antenna ports 0 – 3, 7 – 22 of a serving cell are quasi co-located (as defined in [3]) with respect to delay spread, Doppler spread, Doppler shift, and average delay.
- Type B: The UE may assume the antenna ports 15 – 22 corresponding to the CSI-RS resource configuration identified by the higher layer parameter *qcl-CSI-RS-ConfigNZPID-r11* (defined in subclause 7.1.9) and the antenna ports 7 – 14 associated with the PDSCH are quasi co-located (as defined in [3]) with respect to Doppler shift, Doppler spread, average delay, and delay spread.

7.2 UE procedure for reporting Channel State Information (CSI)

The time and frequency resources that can be used by the UE to report CSI which consists of Channel Quality Indicator (CQI), precoding matrix indicator (PMI), precoding type indicator (PTI), and/or rank indication (RI) are controlled by the eNB. For spatial multiplexing, as given in [3], the UE shall determine a RI corresponding to the number of useful transmission layers. For transmit diversity as given in [3], RI is equal to one.

A UE in transmission mode 8 or 9 is configured with or without PMI/RI reporting by the higher layer parameter *pmi-RI-Report*.

A UE in transmission mode 10 can be configured with one or more CSI processes per serving cell by higher layers. Each CSI process is associated with a CSI-RS resource (defined in subclause 7.2.5) and a CSI-interference measurement (CSI-IM) resource (defined in subclause 7.2.6). A UE can be configured with up to two CSI-IM resources for a CSI process if the UE is configured with CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ by the higher layer parameter *csi-SubFramePatternConfig-r12* for the CSI process. A CSI reported by the UE corresponds to a CSI process configured by higher layers. Each CSI process can be configured with or without PMI/RI reporting by higher layer signalling.

A UE is configured with resource-restricted CSI measurements if the subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers.

For a serving cell with frame structure type 1, a UE is not expected to be configured with *csi-SubFramePatternConfig-r12*.

CSI reporting is periodic or aperiodic.

If the UE is configured with more than one serving cell, it transmits CSI for activated serving cell(s) only.

If a UE is not configured for simultaneous PUSCH and PUCCH transmission, it shall transmit periodic CSI reporting on PUCCH as defined hereafter in subframes with no PUSCH allocation.

If a UE is not configured for simultaneous PUSCH and PUCCH transmission, it shall transmit periodic CSI reporting on PUSCH of the serving cell with smallest *ServCellIndex* as defined hereafter in subframes with a PUSCH allocation, where the UE shall use the same PUCCH-based periodic CSI reporting format on PUSCH.

A UE shall transmit aperiodic CSI reporting on PUSCH if the conditions specified hereafter are met. For aperiodic CQI/PMI reporting, RI reporting is transmitted only if the configured CSI feedback type supports RI reporting.

Table 7.2-1: Void

In case both periodic and aperiodic CSI reporting would occur in the same subframe, the UE shall only transmit the aperiodic CSI report in that subframe.

If the higher layer parameter *altCQI-Table-r12* is configured and is set to *allSubframes-r12*,

- the UE shall report CQI according to Table 7.2.3-2.

Else if the higher layer parameter *altCQI-Table-r12* is configured and is set to *csi-SubframeSet1-r12* or *csi-SubframeSet2-r12*,

- the UE shall report CQI according to Table 7.2.3-2 for the corresponding CSI subframe set configured by *altCQI-Table-r12*
- the UE shall report CQI for the other CSI subframe set according to Table 7.2.3-1.

Else

- the UE shall report CQI according to Table 7.2.3-1.

When reporting RI the UE reports a single instance of the number of useful transmission layers. For each RI reporting interval when the UE is configured in transmission modes 4 or when the UE is configured in transmission mode 8, 9 or 10 with PMI/RI reporting, a UE shall determine a RI from the supported set of RI values as defined in subclause 5.2.2.6 of [4] and report the number in each RI report. For each RI reporting interval when the UE is configured in transmission

mode 3, a UE shall determine RI as defined in subclause 5.2.2.6 of [4] in each reporting interval and report the detected number in each RI report to support selection between transmit diversity and large delay CDD.

When reporting PMI the UE reports either a single or a multiple PMI report. The number of RBs represented by a single UE PMI report can be $N_{\text{RB}}^{\text{DL}}$ or a smaller subset of RBs. The number of RBs represented by a single PMI report is semi-statically configured by higher layer signalling. A UE is restricted to report PMI, RI and PTI within a precoder codebook subset specified by a bitmap parameter *codebookSubsetRestriction* configured by higher layer signalling. For a UE configured in transmission mode 10, the bitmap parameter *codebookSubsetRestriction* is configured for each CSI process and each subframe sets (if subframe sets $C_{\text{CSI},0}$ and $C_{\text{CSI},1}$ are configured by higher layers) by higher layer signaling. For a specific precoder codebook and associated transmission mode, the bitmap can specify all possible precoder codebook subsets from which the UE can assume the eNB may be using when the UE is configured in the relevant transmission mode. Codebook subset restriction is supported for transmission modes 3, 4, 5, 6 and for transmission modes 8, 9 and 10 with PMI/RI reporting. The resulting number of bits for each transmission mode is given in Table 7.2-1b. The bitmap forms the bit sequence $a_{A_c-1}, \dots, a_3, a_2, a_1, a_0$ where a_0 is the LSB and a_{A_c-1} is the MSB and where a bit value of zero indicates that the PMI and RI reporting is not allowed to correspond to precoder(s) associated with the bit. The association of bits to precoders for the relevant transmission modes are given as follows:

1. Transmission mode 3
 - a. 2 antenna ports: bit a_{v-1} , $v = 2$ is associated with the precoder in Table 6.3.4.2.3-1 of [3] corresponding to v layers and codebook index 0 while bit a_0 is associated with the precoder for 2 antenna ports in subclause 6.3.4.3 of [3].
 - b. 4 antenna ports: bit a_{v-1} , $v = 2,3,4$ is associated with the precoders in Table 6.3.4.2.3-2 of [3] corresponding to v layers and codebook indices 12, 13, 14, and 15 while bit a_0 is associated with the precoder for 4 antenna ports in subclause 6.3.4.3 of [3].
2. Transmission mode 4
 - a. 2 antenna ports: see Table 7.2-1c
 - b. 4 antenna ports: bit $a_{16(v-1)+i_c}$ is associated with the precoder for v layers and with codebook index i_c in Table 6.3.4.2.3-2 of [3].
3. Transmission modes 5 and 6
 - a. 2 antenna ports: bit a_{i_c} is associated with the precoder for $v = 1$ layer with codebook index i_c in Table 6.3.4.2.3-1 of [3].
 - b. 4 antenna ports: bit a_{i_c} is associated with the precoder for $v = 1$ layer with codebook index i_c in Table 6.3.4.2.3-2 of [3].
4. Transmission mode 8
 - a. 2 antenna ports: see Table 7.2-1c
 - b. 4 antenna ports except with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured: bit $a_{16(v-1)+i_c}$ is associated with the precoder for v layers and with codebook index i_c in Table 6.3.4.2.3-2 of [3], $v = 1,2$.
 - c. 4 antenna ports with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured: bit $a_{16(v-1)+i_1}$ is associated with the precoder for v layers ($v \in \{1,2\}$) and codebook index i_1 and bit $a_{32+16(v-1)+i_2}$ is associated with the precoder for v layers ($v \in \{1,2\}$) and codebook index i_2 . Codebook indices i_1 and i_2 are given in Table 7.2.4-0A or 7.2.4-0B, for $v=1$ or 2 respectively.

5. Transmission modes 9 and 10

- a. 2 antenna ports: see Table 7.2-1c
- b. 4 antenna ports except with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured: bit $a_{16(v-1)+i_c}$ is associated with the precoder for v layers and with codebook index i_c in Table 6.3.4.2.3-2 of [3].
- c. 4 antenna ports with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured: bit $a_{16(v-1)+i_1}$ is associated with the precoder for v layers ($v \in \{1,2\}$) and codebook index i_1 and bit $a_{32+16(v-1)+i_2}$ is associated with the precoder for v layers ($v \in \{1,2,3,4\}$) and codebook index i_2 . Codebook indices i_1 and i_2 are given in Table 7.2.4-0A, 7.2.4-0B, 7.2.4-0C or 7.2.4-0D, for $v=1,2,3$ or 4 respectively.
- d. 8 antenna ports: bit $a_{f1(v-1)+i_1}$ is associated with the precoder for v layers ($v \in \{1,2,3,4,5,6,7,8\}$) and codebook index i_1 where $f1(\cdot) = \{0,16,32,36,40,44,48,52\}$ and bit $a_{53+g1(v-1)+i_2}$ is associated with the precoder for v layers ($v \in \{1,2,3,4\}$) and codebook index i_2 where $g1(\cdot) = \{0,16,32,48\}$. Codebook indices i_1 and i_2 are given in Table 7.2.4-1, 7.2.4-2, 7.2.4-3, 7.2.4-4, 7.2.4-5, 7.2.4-6, 7.2.4-7, or 7.2.4-8, for $v=1,2,3,4,5,6,7$, or 8 respectively.

Table 7.2-1b: Number of bits in codebook subset restriction bitmap for applicable transmission modes

| | Number of bits A_c | | |
|-----------------------------|----------------------|---|-----------------|
| | 2 antenna ports | 4 antenna ports | 8 antenna ports |
| Transmission mode 3 | 2 | 4 | |
| Transmission mode 4 | 6 | 64 | |
| Transmission mode 5 | 4 | 16 | |
| Transmission mode 6 | 4 | 16 | |
| Transmission mode 8 | 6 | 64 with <i>alternativeCodeBookEnabledFor4TX-r12=TRUE</i> configured, otherwise 32 | |
| Transmission modes 9 and 10 | 6 | 96 with <i>alternativeCodeBookEnabledFor4TX-r12=TRUE</i> configured, otherwise 64 | 109 |

Table 7.2-1c: Association of bits in *codebookSubSetRestriction* bitmap to precoders in the 2 antenna port codebook of Table 6.3.4.2.3-1 in [3]

| Codebook index i_c | Number of layers v | |
|----------------------|----------------------|-------|
| | 1 | 2 |
| 0 | a_0 | - |
| 1 | a_1 | a_4 |
| 2 | a_2 | a_5 |
| 3 | a_3 | - |

The set of subbands (S) a UE shall evaluate for CQI reporting spans the entire downlink system bandwidth. A subband is a set of k contiguous PRBs where k is a function of system bandwidth. Note the last subband in set S may have fewer than k contiguous PRBs depending on N_{RB}^{DL} . The number of subbands for system bandwidth given by N_{RB}^{DL} is defined by $N = \lceil N_{RB}^{DL} / k \rceil$. The subbands shall be indexed in the order of increasing frequency and non-increasing sizes starting at the lowest frequency.

- For transmission modes 1, 2, 3 and 5, as well as transmission modes 8, 9 and 10 without PMI/RI reporting, transmission mode 4 with RI=1, and transmission modes 8, 9 and 10 with PMI/RI reporting and RI=1, a single 4-bit wideband CQI is reported.
- For transmission modes 3 and 4, as well as transmission modes 8, 9 and 10 with PMI/RI reporting, CQI is calculated assuming transmission of one codeword for RI=1 and two codewords for RI > 1.
- For RI > 1 with transmission mode 4, as well as transmission modes 8, 9 and 10 with PMI/RI reporting, PUSCH based triggered reporting includes reporting a wideband CQI which comprises:
 - A 4-bit wideband CQI for codeword 0
 - A 4-bit wideband CQI for codeword 1
- For RI > 1 with transmission mode 4, as well as transmission modes 8, 9 and 10 with PMI/RI reporting, PUCCH based reporting includes reporting a 4-bit wideband CQI for codeword 0 and a wideband spatial differential CQI. The wideband spatial differential CQI value comprises:
 - A 3-bit wideband spatial differential CQI value for codeword 1 offset level
 - Codeword 1 offset level = wideband CQI index for codeword 0 – wideband CQI index for codeword 1.
 - The mapping from the 3-bit wideband spatial differential CQI value to the offset level is shown in Table 7.2-2.

Table 7.2-2 Mapping spatial differential CQI value to offset level

| Spatial differential CQI value | Offset level |
|--------------------------------|--------------|
| 0 | 0 |
| 1 | 1 |
| 2 | 2 |
| 3 | ≥3 |
| 4 | ≤-4 |
| 5 | -3 |
| 6 | -2 |
| 7 | -1 |

7.2.1 Aperiodic CSI Reporting using PUSCH

The term “UL/DL configuration” in this subclause refers to the higher layer parameter *subframeAssignment* unless specified otherwise.

A UE shall perform aperiodic CSI reporting using the PUSCH in subframe $n+k$ on serving cell c , upon decoding in subframe n either:

- an uplink DCI format [4], or
- a Random Access Response Grant,

for serving cell c if the respective CSI request field is set to trigger a report and is not reserved.

If the CSI request field is 1 bit and the UE is configured in transmission mode 1-9 and the UE is not configured with *csi-SubframePatternConfig-r12* for any serving cell, a report is triggered for serving cell c , if the CSI request field is set to '1'.

If the CSI request field is 1 bit and the UE is configured in transmission mode 10 and the UE is not configured with *csi-SubframePatternConfig-r12* for any serving cell, a report is triggered for a set of CSI process(es) for serving cell c corresponding to the higher layer configured set of CSI process(es) associated with the value of CSI request field of '01' in Table 7.2.1-1B, if the CSI request field is set to '1'.

If the CSI request field size is 2 bits and the UE is configured in transmission mode 1-9 for all serving cells and the UE is not configured with *csi-SubframePatternConfig-r12* for any serving cell, a report is triggered according to the value in Table 7.2.1-1A corresponding to aperiodic CSI reporting.

If the CSI request field size is 2 bits and the UE is configured in transmission mode 10 for at least one serving cell and the UE is not configured with *csi-SubframePatternConfig-r12* for any serving cell, a report is triggered according to the value in Table 7.2.1-1B corresponding to aperiodic CSI reporting.

If the CSI request field is 1 bit and the UE is configured with the higher layer parameter *csi-SubframePatternConfig-r12* for at least one serving cell, - a report is triggered for a set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) for serving cell c corresponding to the higher layer configured set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) associated with the value of CSI request field of '01' in Table 7.2.1-1C, if the CSI request field is set to '1'.

If the CSI request field size is 2 bits and the UE is configured with the higher layer parameter *csi-SubframePatternConfig-r12* for at least one serving cell,

a report is triggered according to the value in Table 7.2.1-1C corresponding to aperiodic CSI reporting.

For a given serving cell, if the UE is configured in transmission modes 1-9, the "CSI process" in Table 7.2.1-1B and Table 7.2.1-1C refers to the aperiodic CSI configured for the UE on the given serving cell. A UE is not expected to be configured by higher layers with more than 5 CSI processes in each of the 1st and 2nd set of CSI process(es) in Table 7.2.1-1B. A UE is not expected to be configured by higher layers with more than 5 CSI processes and/or {CSI process, CSI subframe set}-pair(s) in each of the 1st and 2nd set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) in Table 7.2.1-1C. A UE is not expected to be configured by higher layers with more than one instance of the same CSI process in each of the higher layer configured sets associated with the value of CSI request field of '01', '10', and '11' in Table 7.2.1-1B and Table 7.2.1-1C respectively.

A UE is not expected to receive more than one aperiodic CSI report request for a given subframe.

If a UE is configured with more than one CSI process for a serving cell, the UE on reception of an aperiodic CSI report request triggering a CSI report according to Table 7.2.1-1B is not expected to update CSI corresponding to the CSI reference resource (defined in subclause 7.2.3) for all CSI processes except the $\max(N_x - N_u, 0)$ lowest-indexed CSI processes for the serving cell associated with the request when the UE has N_u unreported CSI processes associated with other aperiodic CSI requests for the serving cell, where a CSI process associated with a CSI request shall only be counted as unreported in a subframe before the subframe where the PUSCH carrying the corresponding CSI is transmitted, and N_{CSI-P} is the maximum number of CSI processes supported by the UE for the serving cell and:

- for FDD serving cell $N_x = N_{CSI-P}$;
- for TDD serving cell
 - if the UE is configured with four CSI processes for the serving cell, $N_x = N_{CSI-P}$
 - if the UE is configured with two or three CSI processes for the serving cell, $N_x = 3$.

If more than one value of N_{CSI-P} is included in the *UE-EUTRA-Capability*, the UE assumes a value of N_{CSI-P} that is consistent with its CSI process configuration. If more than one consistent value of N_{CSI-P} exists, the UE may assume any one of the consistent values.

If a UE is configured with multiple cell groups, and if the UE receives multiple aperiodic CSI report requests in a subframe for different cell groups triggering more than one CSI report, the UE is not required to update CSI for more than 5 CSI processes from the CSI processes corresponding to all the triggered CSI reports.

Table 7.2.1-1A: CSI Request field for PDCCH/EPDCCH with uplink DCI format in UE specific search space

| Value of CSI request field | Description |
|----------------------------|--|
| '00' | No aperiodic CSI report is triggered |
| '01' | Aperiodic CSI report is triggered for serving cell c |
| '10' | Aperiodic CSI report is triggered for a 1 st set of serving cells configured by higher layers |
| '11' | Aperiodic CSI report is triggered for a 2 nd set of serving cells configured by higher layers |

Table 7.2.1-1B: CSI Request field for PDCCH/EPDCCH with uplink DCI format in UE specific search space

| Value of CSI request field | Description |
|----------------------------|---|
| '00' | No aperiodic CSI report is triggered |
| '01' | Aperiodic CSI report is triggered for a set of CSI process(es) configured by higher layers for serving cell c |
| '10' | Aperiodic CSI report is triggered for a 1 st set of CSI process(es) configured by higher layers |
| '11' | Aperiodic CSI report is triggered for a 2 nd set of CSI process(es) configured by higher layers |

Table 7.2.1-1C: CSI Request field for PDCCH/EPDCCH with uplink DCI format in UE specific search space

| Value of CSI request field | Description |
|----------------------------|--|
| '00' | No aperiodic CSI report is triggered |
| '01' | Aperiodic CSI report is triggered for a set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) configured by higher layers for serving cell c |
| '10' | Aperiodic CSI report is triggered for a 1 st set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) configured by higher layers |
| '11' | Aperiodic CSI report is triggered for a 2 nd set of CSI process(es) and/or {CSI process, CSI subframe set}-pair(s) configured by higher layers |

NOTE: PDCCH/EPDCCH with DCI formats used to grant PUSCH transmissions as given by DCI format 0 and DCI format 4 are herein referred to as uplink DCI format when common behaviour is addressed.

When the CSI request field from an uplink DCI format is set to trigger a report, for FDD $k=4$, and for TDD UL/DL configuration 1-6, k is given in Table 8-2. For TDD UL/DL configuration 0, if the MSB of the UL index is set to 1 and LSB of the UL index is set to 0, k is given in Table 8-2; or if MSB of the UL index is set to 0 and LSB of the UL index is set to 1, k is equal to 7; or if both MSB and LSB of the UL index is set to 1, k is given in Table 8-2.

For TDD, if a UE is configured with more than one serving cell and if the UL/DL configurations of at least two serving cells are different, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD and serving cell frame structure type 2, the "TDD UL/DL Configuration" given in Table 8-2 refers to the UL-reference UL/DL configuration (defined in subclause 8.0).

When the CSI request field from a Random Access Response Grant is set to trigger a report and is not reserved, k is equal to k_1 if the UL delay field in subclause 6.2 is set to zero, where k_1 is given in subclause 6.1.1. The UE shall postpone aperiodic CSI reporting to the next available UL subframe if the UL delay field is set to 1.

The minimum reporting interval for aperiodic reporting of CQI and PMI and RI is 1 subframe. The subband size for CQI shall be the same for transmitter-receiver configurations with and without precoding.

If a UE is not configured for simultaneous PUSCH and PUCCH transmission, when aperiodic CSI report with no transport block associated as defined in subclause 8.6.2 and positive SR is transmitted in the same subframe, the UE shall transmit SR, and, if applicable, HARQ-ACK, on PUCCH resources as described in subclause 10.1

A UE is semi-statically configured by higher layers to feed back CQI and PMI and corresponding RI on the same PUSCH using one of the following CSI reporting modes given in Table 7.2.1-1 and described below.

Table 7.2.1-1: CQI and PMI Feedback Types for PUSCH CSI reporting Modes

| PUSCH CQI Feedback Type | | PMI Feedback Type | | |
|-------------------------|---------------------------------------|-------------------|------------|--------------|
| | | No PMI | Single PMI | Multiple PMI |
| | Wideband (wideband CQI) | | | Mode 1-2 |
| | UE Selected (subband CQI) | Mode 2-0 | | Mode 2-2 |
| | Higher Layer-configured (subband CQI) | Mode 3-0 | Mode 3-1 | Mode 3-2 |

For each of the transmission modes defined in subclause 7.1, the following reporting modes are supported on PUSCH:

- Transmission mode 1 : Modes 2-0, 3-0
- Transmission mode 2 : Modes 2-0, 3-0
- Transmission mode 3 : Modes 2-0, 3-0
- Transmission mode 4 : Modes 1-2, 2-2, 3-1, 3-2
- Transmission mode 5 : Mode 3-1
- Transmission mode 6 : Modes 1-2, 2-2, 3-1, 3-2
- Transmission mode 7 : Modes 2-0, 3-0
- Transmission mode 8 : Modes 1-2, 2-2, 3-1, 3-2 if the UE is configured with PMI/RI reporting; modes 2-0, 3-0 if the UE is configured without PMI/RI reporting
- Transmission mode 9 : Modes 1-2, 2-2, 3-1, 3-2 if the UE is configured with PMI/RI reporting and number of CSI-RS ports > 1; modes 2-0, 3-0 if the UE is configured without PMI/RI reporting or number of CSI-RS ports=1
- Transmission mode 10 : Modes 1-2, 2-2, 3-1, 3-2 if the UE is configured with PMI/RI reporting and number of CSI-RS ports > 1; modes 2-0, 3-0 if the UE is configured without PMI/RI reporting or number of CSI-RS ports=1.

The aperiodic CSI reporting mode is given by the parameter *cqi-ReportModeAperiodic* which is configured by higher-layer signalling.

For a serving cell with $N_{RB}^{DL} \leq 7$, PUSCH reporting modes are not supported for that serving cell.

RI is only reported for transmission modes 3 and 4, as well as transmission modes 8, 9 and 10 with PMI/RI reporting.

For serving cell c , a UE configured in transmission mode 10 with PMI/RI reporting for a CSI process can be configured with a 'RI-reference CSI process' for the CSI process. If the UE is configured with a 'RI-reference CSI process' for the CSI process, the reported RI for the CSI process shall be the same as the reported RI for the configured 'RI-reference CSI process'. The RI for the 'RI-reference CSI process' is not based on any other configured CSI process other than the 'RI-reference CSI process'. The UE is not expected to receive an aperiodic CSI report request for a given subframe triggering a CSI report including CSI associated with the CSI process and not including CSI associated with the configured 'RI-reference CSI process'. If the UE is configured with a 'RI-reference CSI process' for a CSI process and if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for only one of the CSI processes then the UE is not expected to receive configuration for the CSI process configured with the subframe subsets that have a different set of restricted RIs with precoder codebook subset restriction between the two subframe sets. The UE is not expected to receive configurations for the CSI process and the 'RI-reference CSI process' that have a different:

- Aperiodic CSI reporting mode, and/or
- number of CSI-RS antenna ports, and/or
- set of restricted RIs with precoder codebook subset restriction if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are not configured by higher layers for both CSI processes, and/or
- set of restricted RIs with precoder codebook subset restriction for each subframe set if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for both CSI processes, and/or
- set of restricted RIs with precoder codebook subset restriction if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for only one of the CSI processes, and the set of restricted RIs for the two subframe sets are the same.

A RI report for a serving cell on an aperiodic reporting mode is valid only for CQI/PMI report for that serving cell on that aperiodic reporting mode

- Wideband feedback
 - Mode 1-2 description:
 - For each subband a preferred precoding matrix is selected from the codebook subset assuming transmission only in the subband
 - A UE shall report one wideband CQI value per codeword which is calculated assuming the use of the corresponding selected precoding matrix in each subband and transmission on set S subbands.
 - The UE shall report the selected precoding matrix indicator for each set S subband except with 8 CSI-RS ports configured for transmission modes 9 and 10 or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10, in which case a first precoding matrix indicator i_1 is reported for the set S subbands and a second precoding matrix indicator i_2 is reported for each set S subband.
 - Subband size is given by Table 7.2.1-3.
 - For transmission modes 4, 8, 9 and 10, the reported PMI and CQI values are calculated conditioned on the reported RI. For other transmission modes they are reported conditioned on rank 1.
- Higher Layer-configured subband feedback
 - Mode 3-0 description:
 - A UE shall report a wideband CQI value which is calculated assuming transmission on set S subbands
 - The UE shall also report one subband CQI value for each set S subband. The subband CQI value is calculated assuming transmission only in the subband
 - Both the wideband and subband CQI represent channel quality for the first codeword, even when $RI > 1$.
 - For transmission mode 3 the reported CQI values are calculated conditioned on the reported RI. For other transmission modes they are reported conditioned on rank 1.
 - Mode 3-1 description:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands
 - A UE shall report one subband CQI value per codeword for each set S subband which are calculated assuming the use of the single precoding matrix in all subbands and assuming transmission in the corresponding subband.
 - A UE shall report a wideband CQI value per codeword which is calculated assuming the use of the single precoding matrix in all subbands and transmission on set S subbands
 - The UE shall report the selected single precoding matrix indicator except with 8 CSI-RS ports configured for transmission modes 9 and 10 or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10, in which case a first and second precoding matrix indicator are reported corresponding to the selected single precoding matrix.
 - For transmission modes 4, 8, 9 and 10, the reported PMI and CQI values are calculated conditioned on the reported RI. For other transmission modes they are reported conditioned on rank 1.

- Mode 3-2 description:
 - For each subband a preferred precoding matrix is selected from the codebook subset assuming transmission only in the subband
 - A UE shall report one wideband CQI value per codeword which is calculated assuming the use of the corresponding selected precoding matrix in each subband and transmission on set S subbands.
 - A UE shall report the selected single precoding matrix indicator for each set S subband except with 8 CSI-RS ports configured for transmission mode 9 and 10, or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10, in which case the UE shall report a first precoding matrix indicator for all set S subbands and also report a second precoding matrix indicator for each set S subband.
 - A UE shall report one subband CQI value per codeword for each set S subband reflecting transmission over the single subband and using the selected precoding matrix in the corresponding subband.
 - For transmission modes 4, 8, 9 and 10, the reported PMI and CQI values are calculated conditioned on the reported RI. For transmission mode 6 they are reported conditioned on rank 1.
- Subband CQI value for each codeword are encoded differentially with respect to their respective wideband CQI using 2-bits as defined by
 - Subband differential CQI offset level = subband CQI index – wideband CQI index. The mapping from the 2-bit subband differential CQI value to the offset level is shown in Table 7.2.1-2.

Table 7.2.1-2: Mapping subband differential CQI value to offset level

| Subband differential CQI value | Offset level |
|--------------------------------|--------------|
| 0 | 0 |
| 1 | 1 |
| 2 | ≥ 2 |
| 3 | ≤ -1 |

- Supported subband size (k) is given in Table 7.2.1-3.

Table 7.2.1-3: Subband Size (k) vs. System Bandwidth

| System Bandwidth | Subband Size |
|------------------|--------------|
| N_{RB}^{DL} | (k) |
| 6 - 7 | NA |
| 8 - 10 | 4 |
| 11 - 26 | 4 |
| 27 - 63 | 6 |
| 64 - 110 | 8 |

- UE-selected subband feedback
 - Mode 2-0 description:
 - The UE shall select a set of M preferred subbands of size k (where k and M are given in Table 7.2.1-5 for each system bandwidth range) within the set of subbands S .
 - The UE shall also report one CQI value reflecting transmission only over the M selected subbands determined in the previous step. The CQI represents channel quality for the first codeword, even when $RI > 1$.

- Additionally, the UE shall also report one wideband CQI value which is calculated assuming transmission on set S subbands. The wideband CQI represents channel quality for the first codeword, even when $RI > 1$.
 - For transmission mode 3 the reported CQI values are calculated conditioned on the reported RI. For other transmission modes they are reported conditioned on rank 1.
- Mode 2-2 description:
- The UE shall perform joint selection of the set of M preferred subbands of size k within the set of subbands S and a preferred single precoding matrix selected from the codebook subset that is preferred to be used for transmission over the M selected subbands.
 - The UE shall report one CQI value per codeword reflecting transmission only over the selected M preferred subbands and using the same selected single precoding matrix in each of the M subbands.
 - Except with 8 CSI-RS ports configured for transmission modes 9 and 10 or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10, the UE shall also report the selected single precoding matrix indicator preferred for the M selected subbands. A UE shall also report the selected single precoding matrix indicator for all set S subbands.
 - For transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8, 9 and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured, a UE shall report a first precoding matrix indicator for all set S subbands. A UE shall also report a second precoding matrix indicator for all set S subbands and another second precoding matrix indicator for the M selected subbands.
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands
 - A UE shall report a wideband CQI value per codeword which is calculated assuming the use of the single precoding matrix in all subbands and transmission on set S subbands
 - For transmission modes 4, 8, 9 and 10, the reported PMI and CQI values are calculated conditioned on the reported RI. For other transmission modes they are reported conditioned on rank 1.
- For all UE-selected subband feedback modes the UE shall report the positions of the M selected subbands using a combinatorial index r defined as

$$r = \sum_{i=0}^{M-1} \binom{N - s_i}{M - i}$$

- where the set $\{s_i\}_{i=0}^{M-1}$, $(1 \leq s_i \leq N, s_i < s_{i+1})$ contains the M sorted subband indices

$$\text{and } \binom{x}{y} = \begin{cases} \binom{x}{y} & x \geq y \\ 0 & x < y \end{cases} \text{ is the extended binomial coefficient, resulting in unique label}$$

$$r \in \left\{ 0, \dots, \binom{N}{M} - 1 \right\}.$$

- The CQI value for the M selected subbands for each codeword is encoded differentially using 2-bits relative to its respective wideband CQI as defined by
- Differential CQI offset level = M selected subbands CQI index – wideband CQI index
 - The mapping from the 2-bit differential CQI value to the offset level is shown in Table 7.2.1-4.

Table 7.2.1-4: Mapping differential CQI value to offset level

| Differential CQI value | Offset level |
|------------------------|--------------|
| 0 | ≤ 1 |
| 1 | 2 |
| 2 | 3 |
| 3 | ≥ 4 |

- Supported subband size k and M values include those shown in Table 7.2.1-5. In Table 7.2.1-5 the k and M values are a function of system bandwidth.

- The number of bits to denote the position of the M selected subbands is $L = \left\lceil \log_2 \binom{N}{M} \right\rceil$.

Table 7.2.1-5: Subband Size (k) and Number of Subbands (M) in S vs. Downlink System Bandwidth

| System Bandwidth N_{RB}^{DL} | Subband Size k (RBs) | M |
|-----------------------------------|------------------------|-----|
| 6 – 7 | NA | NA |
| 8 – 10 | 2 | 1 |
| 11 – 26 | 2 | 3 |
| 27 – 63 | 3 | 5 |
| 64 – 110 | 4 | 6 |

7.2.2 Periodic CSI Reporting using PUCCH

A UE is semi-statically configured by higher layers to periodically feed back different CSI components (CQI, PMI, PTI, and/or RI) on the PUCCH using the reporting modes given in Table 7.2.2-1 and described below. A UE in transmission mode 10 can be configured by higher layers for multiple periodic CSI reports corresponding to one or more CSI processes per serving cell on PUCCH.

Table 7.2.2-1: CQI and PMI Feedback Types for PUCCH CSI reporting Modes

| | | PMI Feedback Type | |
|-------------------------|---------------------------|-------------------|------------|
| | | No PMI | Single PMI |
| PUCCH CQI Feedback Type | Wideband (wideband CQI) | Mode 1-0 | Mode 1-1 |
| | UE Selected (subband CQI) | Mode 2-0 | Mode 2-1 |

For each of the transmission modes defined in subclause 7.1, the following periodic CSI reporting modes are supported on PUCCH:

- Transmission mode 1 : Modes 1-0, 2-0
- Transmission mode 2 : Modes 1-0, 2-0
- Transmission mode 3 : Modes 1-0, 2-0
- Transmission mode 4 : Modes 1-1, 2-1
- Transmission mode 5 : Modes 1-1, 2-1
- Transmission mode 6 : Modes 1-1, 2-1
- Transmission mode 7 : Modes 1-0, 2-0
- Transmission mode 8 : Modes 1-1, 2-1 if the UE is configured with PMI/RI reporting; modes 1-0, 2-0 if the UE is configured without PMI/RI reporting
- Transmission mode 9 : Modes 1-1, 2-1 if the UE is configured with PMI/RI reporting and number of CSI-RS ports>1; modes 1-0, 2-0 if the UE is configured without PMI/RI reporting or number of CSI-RS ports=1.
- Transmission mode 10 : Modes 1-1, 2-1 if the UE is configured with PMI/RI reporting and number of CSI-RS ports>1; modes 1-0, 2-0 if the UE is configured without PMI/RI reporting or number of CSI-RS ports=1.

For a UE configured in transmission mode 1-9, one periodic CSI reporting mode for each serving cell is configured by higher-layer signalling.

For a UE configured in transmission mode 10, one or more periodic CSI reporting modes for each serving cell are configured by higher-layer signalling.

For a UE configured with transmission mode 9 or 10, and with 8 CSI-RS ports, mode 1-1 is configured to be either submode 1 or submode 2 via higher-layer signaling using the parameter *PUCCH_format1-1_CSI_reporting_mode*.

For a UE configured with transmission mode 8, 9 or 10, and with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured, mode 1-1 is configured to be either submode 1 or submode 2 via higher-layer signaling using the parameter *PUCCH_format1-1_CSI_reporting_mode*.

For the UE-selected subband CQI, a CQI report in a certain subframe of a certain serving cell describes the channel quality in a particular part or in particular parts of the bandwidth of that serving cell described subsequently as bandwidth part (BP) or parts. The bandwidth parts shall be indexed in the order of increasing frequency and non-increasing sizes starting at the lowest frequency.

For each serving cell

- There are a total of N subbands for a serving cell system bandwidth given by N_{RB}^{DL} where $\lfloor N_{RB}^{DL} / k \rfloor$ subbands are of size k . If $\lfloor N_{RB}^{DL} / k \rfloor - \lfloor N_{RB}^{DL} / k \rfloor > 0$ then one of the subbands is of size $N_{RB}^{DL} - k \cdot \lfloor N_{RB}^{DL} / k \rfloor$.

- A bandwidth part j is frequency-consecutive and consists of N_j subbands where J bandwidth parts span S or N_{RB}^{DL} as given in Table 7.2.2-2. If $J=1$ then N_j is $\lceil N_{RB}^{DL} / k / J \rceil$. If $J>1$ then N_j is either $\lceil N_{RB}^{DL} / k / J \rceil$ or $\lceil N_{RB}^{DL} / k / J \rceil - 1$, depending on N_{RB}^{DL} , k and J .
- Each bandwidth part j , where $0 \leq j \leq J-1$, is scanned in sequential order according to increasing frequency.
- For UE selected subband feedback a single subband out of N_j subbands of a bandwidth part is selected along with a corresponding L -bit label indexed in the order of increasing frequency, where $L = \lceil \log_2 \lceil N_{RB}^{DL} / k / J \rceil \rceil$.

The CQI and PMI payload sizes of each PUCCH CSI reporting mode are given in Table 7.2.2-3.

The following CQI/PMI and RI reporting types with distinct periods and offsets are supported for the PUCCH CSI reporting modes given in Table 7.2.2-3:

- Type 1 report supports CQI feedback for the UE selected sub-bands
- Type 1a report supports subband CQI and second PMI feedback
- Type 2, Type 2b, and Type 2c report supports wideband CQI and PMI feedback
- Type 2a report supports wideband PMI feedback
- Type 3 report supports RI feedback
- Type 4 report supports wideband CQI
- Type 5 report supports RI and wideband PMI feedback
- Type 6 report supports RI and PTI feedback

For a UE configured in transmission mode 1-9 and for each serving cell, or for a UE configured in transmission mode 10 and for each CSI process in each serving cell, the periodicity N_{pd} (in subframes) and offset $N_{OFFSET,CQI}$ (in subframes) for CQI/PMI reporting are determined based on the parameter $cqi-pmi-ConfigIndex$ ($I_{CQI/PMI}$) given in Table 7.2.2-1A for FDD or for FDD-TDD with primary cell frame structure 1 and Table 7.2.2-1C for TDD or for FDD-TDD and primary cell frame structure type 2. The periodicity M_{RI} and relative offset $N_{OFFSET,RI}$ for RI reporting are determined based on the parameter $ri-ConfigIndex$ (I_{RI}) given in Table 7.2.2-1B. Both $cqi-pmi-ConfigIndex$ and $ri-ConfigIndex$ are configured by higher layer signalling. The relative reporting offset for RI $N_{OFFSET,RI}$ takes values from the set $\{0, -1, \dots, -(N_{pd} - 1)\}$. If a UE is configured to report for more than one CSI subframe set then parameter $cqi-pmi-ConfigIndex$ and $ri-ConfigIndex$ respectively correspond to the CQI/PMI and RI periodicity and relative reporting offset for subframe set 1 and $cqi-pmi-ConfigIndex2$ and $ri-ConfigIndex2$ respectively correspond to the CQI/PMI and RI periodicity and relative reporting offset for subframe set 2. For a UE configured with transmission mode 10, the parameters $cqi-pmi-ConfigIndex$, $ri-ConfigIndex$, $cqi-pmi-ConfigIndex2$ and $ri-ConfigIndex2$ can be configured for each CSI process.

In the case where wideband CQI/PMI reporting is configured:

- The reporting instances for wideband CQI/PMI are subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI}) \bmod(N_{pd}) = 0$.
- In case RI reporting is configured, the reporting interval of the RI reporting is an integer multiple M_{RI} of period N_{pd} (in subframes).
- The reporting instances for RI are subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI} - N_{OFFSET,RI}) \bmod(N_{pd} \cdot M_{RI}) = 0$.

In the case where both wideband CQI/PMI and subband CQI (or subband CQI/second PMI for transmission modes 9 and 10) reporting are configured:

- The reporting instances for wideband CQI/PMI and subband CQI (or subband CQI/second PMI for transmission modes 9 and 10) are subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI}) \bmod N_{pd} = 0$.
 - When PTI is not transmitted (due to not being configured) or the most recently transmitted PTI is equal to 1 for a UE configured in transmission modes 8 and 9, or for a UE configured in transmission mode 10 without a 'RI-reference CSI process' for a CSI process, or the transmitted PTI is equal to 1 reported in the most recent RI reporting instance for a CSI process when a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for the CSI process, or the transmitted PTI is equal to 1 for a 'RI-reference CSI process' reported in the most recent RI reporting instance for a CSI process when a UE is configured in transmission mode 10 with the 'RI-reference CSI process' for the CSI process, and the most recent type 6 report for the CSI process is dropped:
 - The wideband CQI/ wideband PMI (or wideband CQI/wideband second PMI for transmission modes 8, 9 and 10) report has period $H \cdot N_{pd}$, and is reported on the subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI}) \bmod (H \cdot N_{pd}) = 0$. The integer H is defined as $H = J \cdot K + 1$, where J is the number of bandwidth parts.
 - Between every two consecutive wideband CQI/ wideband PMI (or wideband CQI/wideband second PMI for transmission modes 8, 9 and 10) reports, the remaining $J \cdot K$ reporting instances are used in sequence for subband CQI (or subband CQI/second PMI for transmission modes 9 and 10) reports on K full cycles of bandwidth parts except when the gap between two consecutive wideband CQI/PMI reports contains less than $J \cdot K$ reporting instances due to a system frame number transition to 0, in which case the UE shall not transmit the remainder of the subband CQI (or subband CQI/second PMI for transmission modes 9 and 10) reports which have not been transmitted before the second of the two wideband CQI/ wideband PMI (or wideband CQI/wideband second PMI for transmission modes 8, 9 and 10) reports. Each full cycle of bandwidth parts shall be in increasing order starting from bandwidth part 0 to bandwidth part $J - 1$. The parameter K is configured by higher-layer signalling.
 - When the most recently transmitted PTI is 0 for a UE configured in transmission modes 8 and 9 or for a UE configured in transmission mode 10 without a 'RI-reference CSI process' for a CSI process, or the transmitted PTI is 0 reported in the most recent RI reporting instance for a CSI process when a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for the CSI process, or the transmitted PTI is 0 for a 'RI-reference CSI process' reported in the most recent RI reporting instance for a CSI process when a UE is configured in transmission mode 10 with the 'RI-reference CSI process' for the CSI process, and the most recent type 6 report for the CSI process is dropped:
 - The wideband first precoding matrix indicator report has period $H' \cdot N_{pd}$, and is reported on the subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI}) \bmod (H' \cdot N_{pd}) = 0$, where H' is signalled by higher layers.
 - Between every two consecutive wideband first precoding matrix indicator reports, the remaining reporting instances are used for a wideband second precoding matrix indicator with wideband CQI as described below
- In case RI reporting is configured, the reporting interval of RI is M_{RI} times the wideband CQI/PMI period $H \cdot N_{pd}$, and RI is reported on the same PUCCH cyclic shift resource as both the wideband CQI/PMI and subband CQI reports.
 - The reporting instances for RI are subframes satisfying $(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{OFFSET,CQI} - N_{OFFSET,RI}) \bmod (H \cdot N_{pd} \cdot M_{RI}) = 0$

In case of collision of a CSI report with PUCCH reporting type 3, 5, or 6 of one serving cell with a CSI report with PUCCH reporting type 1, 1a, 2, 2a, 2b, 2c, or 4 of the same serving cell the latter CSI report with PUCCH reporting type (1, 1a, 2, 2a, 2b, 2c, or 4) has lower priority and is dropped.

For a serving cell and UE configured in transmission mode 10, in case of collision between CSI reports of same serving cell with PUCCH reporting type of the same priority, and the CSI reports corresponding to different CSI processes, the CSI reports corresponding to all CSI processes except the CSI process with the lowest *csi-ProcessId-r11* are dropped.

For a serving cell and UE configured in transmission mode 1-9 and configured with CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ by the higher layer parameter *csi-SubframePatternConfig-r12* for the serving cell, in case of collision between CSI reports of same serving cell with PUCCH reporting type of the same priority, the CSI report corresponding to CSI subframe set $C_{CSI,1}$ is dropped.

For a serving cell and UE configured in transmission mode 10 and configured with CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ by the higher layer parameter *csi-SubframePatternConfig-r12* for the serving cell, in case of collision between CSI reports of same serving cell with PUCCH reporting type of the same priority and the CSI reports corresponding to CSI processes with same *csi-ProcessId-r11*, the CSI report corresponding to CSI subframe set $C_{CSI,1}$ is dropped.

If the UE is configured with more than one serving cell, the UE transmits a CSI report of only one serving cell in any given subframe. For a given subframe, in case of collision of a CSI report with PUCCH reporting type 3, 5, 6, or 2a of one serving cell with a CSI report with PUCCH reporting type 1, 1a, 2, 2b, 2c, or 4 of another serving cell, the latter CSI with PUCCH reporting type (1, 1a, 2, 2b, 2c, or 4) has lower priority and is dropped. For a given subframe, in case of collision of CSI report with PUCCH reporting type 2, 2b, 2c, or 4 of one serving cell with CSI report with PUCCH reporting type 1 or 1a of another serving cell, the latter CSI report with PUCCH reporting type 1, or 1a has lower priority and is dropped.

For a given subframe and serving cells with UE configured in transmission mode 1-9, in case of collision between CSI reports of these different serving cells with PUCCH reporting type of the same priority, the CSI reports for all these serving cells except the serving cell with lowest *ServCellIndex* are dropped.

For a given subframe and serving cells with UE configured in transmission mode 10, in case of collision between CSI reports of different serving cells with PUCCH reporting type of the same priority and the CSI reports corresponding to CSI processes with same *csi-ProcessId-r11*, the CSI reports of all serving cells except the serving cell with lowest *ServCellIndex* are dropped.

For a given subframe and serving cells with UE configured in transmission mode 10, in case of collision between CSI reports of different serving cells with PUCCH reporting type of the same priority and the CSI reports corresponding to CSI processes with different *csi-ProcessId-r11*, the CSI reports of all serving cells except the serving cell with CSI reports corresponding to CSI process with the lowest *csi-ProcessId-r11* are dropped.

For a given subframe, in case of collision between CSI report of a given serving cell with UE configured in transmission mode 1-9, and CSI report(s) corresponding to CSI process(es) of a different serving cell with the UE configured in transmission mode 10, and the CSI reports of the serving cells with PUCCH reporting type of the same priority, the CSI report(s) corresponding to CSI process(es) with *csi-ProcessId-r11* > 1 of the different serving cell are dropped.

For a given subframe, in case of collision between CSI report of a given serving cell with UE configured in transmission mode 1-9, and CSI report corresponding to CSI process with *csi-ProcessId-r11* = 1 of a different serving cell with the UE configured in transmission mode 10, and the CSI reports of the serving cells with PUCCH reporting type of the same priority, the CSI report of the serving cell with highest *ServCellIndex* is dropped.

See subclause 10.1 for UE behaviour regarding collision between CSI and HARQ-ACK and the corresponding PUCCH format assignment.

The CSI report of a given PUCCH reporting type shall be transmitted on the PUCCH resource $n_{\text{PUCCH}}^{(2,\tilde{p})}$ as defined in [3], where $n_{\text{PUCCH}}^{(2,\tilde{p})}$ is UE specific and configured by higher layers for each serving cell.

If the UE is not configured for simultaneous PUSCH and PUCCH transmission or, if the UE is configured for simultaneous PUSCH and PUCCH transmission and not transmitting PUSCH, in case of collision between CSI and positive SR in a same subframe, CSI is dropped.

Table 7.2.2-1A: Mapping of $I_{CQI/PMI}$ to N_{pd} and $N_{OFFSET,CQI}$ for FDD or for FDD-TDD and primary cell frame structure type 1

| $I_{CQI/PMI}$ | Value of N_{pd} | Value of $N_{OFFSET,CQI}$ |
|----------------------------------|-------------------|---------------------------|
| $0 \leq I_{CQI/PMI} \leq 1$ | 2 | $I_{CQI/PMI}$ |
| $2 \leq I_{CQI/PMI} \leq 6$ | 5 | $I_{CQI/PMI} - 2$ |
| $7 \leq I_{CQI/PMI} \leq 16$ | 10 | $I_{CQI/PMI} - 7$ |
| $17 \leq I_{CQI/PMI} \leq 36$ | 20 | $I_{CQI/PMI} - 17$ |
| $37 \leq I_{CQI/PMI} \leq 76$ | 40 | $I_{CQI/PMI} - 37$ |
| $77 \leq I_{CQI/PMI} \leq 156$ | 80 | $I_{CQI/PMI} - 77$ |
| $157 \leq I_{CQI/PMI} \leq 316$ | 160 | $I_{CQI/PMI} - 157$ |
| $I_{CQI/PMI} = 317$ | Reserved | |
| $318 \leq I_{CQI/PMI} \leq 349$ | 32 | $I_{CQI/PMI} - 318$ |
| $350 \leq I_{CQI/PMI} \leq 413$ | 64 | $I_{CQI/PMI} - 350$ |
| $414 \leq I_{CQI/PMI} \leq 541$ | 128 | $I_{CQI/PMI} - 414$ |
| $542 \leq I_{CQI/PMI} \leq 1023$ | Reserved | |

Table 7.2.2-1B: Mapping of I_{RI} to M_{RI} and $N_{OFFSET,RI}$

| I_{RI} | Value of M_{RI} | Value of $N_{OFFSET,RI}$ |
|-----------------------------|-------------------|--------------------------|
| $0 \leq I_{RI} \leq 160$ | 1 | $-I_{RI}$ |
| $161 \leq I_{RI} \leq 321$ | 2 | $-(I_{RI} - 161)$ |
| $322 \leq I_{RI} \leq 482$ | 4 | $-(I_{RI} - 322)$ |
| $483 \leq I_{RI} \leq 643$ | 8 | $-(I_{RI} - 483)$ |
| $644 \leq I_{RI} \leq 804$ | 16 | $-(I_{RI} - 644)$ |
| $805 \leq I_{RI} \leq 965$ | 32 | $-(I_{RI} - 805)$ |
| $966 \leq I_{RI} \leq 1023$ | Reserved | |

Table 7.2.2-1C: Mapping of $I_{CQI/PMI}$ to N_{pd} and $N_{OFFSET,CQI}$ for TDD or for FDD-TDD and primary cell frame structure type 2

| $I_{CQI/PMI}$ | Value of N_{pd} | Value of $N_{OFFSET,CQI}$ |
|----------------------------------|-------------------|---------------------------|
| $I_{CQI/PMI} = 0$ | 1 | $I_{CQI/PMI}$ |
| $1 \leq I_{CQI/PMI} \leq 5$ | 5 | $I_{CQI/PMI} - 1$ |
| $6 \leq I_{CQI/PMI} \leq 15$ | 10 | $I_{CQI/PMI} - 6$ |
| $16 \leq I_{CQI/PMI} \leq 35$ | 20 | $I_{CQI/PMI} - 16$ |
| $36 \leq I_{CQI/PMI} \leq 75$ | 40 | $I_{CQI/PMI} - 36$ |
| $76 \leq I_{CQI/PMI} \leq 155$ | 80 | $I_{CQI/PMI} - 76$ |
| $156 \leq I_{CQI/PMI} \leq 315$ | 160 | $I_{CQI/PMI} - 156$ |
| $316 \leq I_{CQI/PMI} \leq 1023$ | Reserved | |

For TDD or FDD-TDD and primary cell frame structure type 2 periodic CQI/PMI reporting, the following periodicity values apply for a serving cell c depending on the TDD UL/DL configuration of the primary cell [3], where the UL/DL configuration corresponds to the *eimta-HARQ-ReferenceConfig-r12* for the primary cell if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for the primary cell:

- The reporting period of $N_{pd} = 1$ is applicable for the serving cell c only if TDD UL/DL configuration of the primary cell belongs to $\{0, 1, 3, 4, 6\}$, and where all UL subframes of the primary cell in a radio frame are used for CQI/PMI reporting.
- The reporting period of $N_{pd} = 5$ is applicable for the serving cell c only if TDD UL/DL configuration of the primary cell belongs to $\{0, 1, 2, 6\}$.
- The reporting periods of $N_{pd} = \{10, 20, 40, 80, 160\}$ are applicable for the serving cell c for any TDD UL/DL configuration of the primary cell.

For a serving cell with $N_{RB}^{DL} \leq 7$, Mode 2-0 and Mode 2-1 are not supported for that serving cell.

The sub-sampled codebook for PUCCH mode 1-1 submode 2 for 8 CSI-RS ports is defined in Table 7.2.2-1D for first and second precoding matrix indicator i_1 and i_2 . Joint encoding of rank and first precoding matrix indicator i_1 for PUCCH mode 1-1 submode 1 for 8 CSI-RS ports is defined in Table 7.2.2-1E. The sub-sampled codebook for PUCCH mode 2-1 for 8 CSI-RS ports is defined in Table 7.2.2-1F for PUCCH Reporting Type 1a.

Table 7.2.2-1D: PUCCH mode 1-1 submode 2 codebook subsampling

| RI | Relationship between the first PMI value and codebook index i_1 | | Relationship between the second PMI value and codebook index i_2 | | total #bits |
|----|---|----------------------|--|---|-------------|
| | Value of the first PMI I_{PMI1} | Codebook index i_1 | Value of the second PMI I_{PMI2} | Codebook index i_2 | |
| 1 | 0-7 | $2I_{PMI1}$ | 0-1 | $2I_{PMI2}$ | 4 |
| 2 | 0-7 | $2I_{PMI1}$ | 0-1 | I_{PMI2} | 4 |
| 3 | 0-1 | $2I_{PMI1}$ | 0-7 | $4 \lfloor I_{PMI2}/4 \rfloor + I_{PMI2}$ | 4 |
| 4 | 0-1 | $2I_{PMI1}$ | 0-7 | I_{PMI2} | 4 |
| 5 | 0-3 | I_{PMI1} | 0 | 0 | 2 |
| 6 | 0-3 | I_{PMI1} | 0 | 0 | 2 |
| 7 | 0-3 | I_{PMI1} | 0 | 0 | 2 |
| 8 | 0 | 0 | 0 | 0 | 0 |

Table 7.2.2-1E: Joint encoding of RI and i_1 for PUCCH mode 1-1 submode 1

| Value of joint encoding of RI and the first PMI $I_{RI/PMI1}$ | RI | Codebook index i_1 |
|---|----------|----------------------|
| 0-7 | 1 | $2I_{RI/PMI1}$ |
| 8-15 | 2 | $2(I_{RI/PMI1}-8)$ |
| 16-17 | 3 | $2(I_{RI/PMI1}-16)$ |
| 18-19 | 4 | $2(I_{RI/PMI1}-18)$ |
| 20-21 | 5 | $2(I_{RI/PMI1}-20)$ |
| 22-23 | 6 | $2(I_{RI/PMI1}-22)$ |
| 24-25 | 7 | $2(I_{RI/PMI1}-24)$ |
| 26 | 8 | 0 |
| 27-31 | reserved | NA |

Table 7.2.2-1F: PUCCH mode 2-1 codebook subsampling

| RI | Relationship between the second PMI value and codebook index i_2 | |
|----|--|---|
| | Value of the second PMI I_{PMI2} | Codebook index i_2 |
| 1 | 0-15 | I_{PMI2} |
| 2 | 0-3 | $2I_{PMI2}$ |
| 3 | 0-3 | $8 \cdot \lfloor I_{PMI2} / 2 \rfloor + (I_{PMI2} \bmod 2) + 2$ |
| 4 | 0-3 | $2I_{PMI2}$ |
| 5 | 0 | 0 |
| 6 | 0 | 0 |
| 7 | 0 | 0 |
| 8 | 0 | 0 |

The sub-sampled codebook for PUCCH mode 1-1 submode 2 for transmission modes 8, 9 and 10 configured with *alternativeCodeBookEnabledFor4TX-r12=TRUE* is defined in Table 7.2.2-G for first and second precoding matrix indicator i_1 and i_2 . Joint encoding of rank and first precoding matrix indicator i_1 for PUCCH mode 1-1 submode 1 for transmission modes 8, 9 and 10 configured with *alternativeCodeBookEnabledFor4TX-r12=TRUE* is defined in Table 7.2.2-1H. The sub-sampled codebook for PUCCH mode 2-1 for transmission modes 8, 9 and 10 configured with *alternativeCodeBookEnabledFor4TX-r12=TRUE* is defined in Table 7.2.2-1I for PUCCH Reporting Type 1a.

Table 7.2.2-1G: PUCCH mode 1-1 submode 2 codebook subsampling with 4 antenna ports

| RI | Relationship between the first PMI value and codebook index i_1 | | Relationship between the second PMI value and codebook index i_2 | | total #bits |
|----|---|----------------------|--|--|-------------|
| | Value of the first PMI I_{PMI1} | Codebook index i_1 | Value of the second PMI I_{PMI2} | Codebook index i_2 | |
| 1 | 0-3 | $4I_{PMI1}$ | 0-3 | $2I_{PMI2} + 4 \cdot \lfloor I_{PMI2} / 2 \rfloor$ | 4 |
| 2 | 0-3 | $4I_{PMI1}$ | 0-3 | $I_{PMI2} + 2 \cdot \lfloor I_{PMI2} / 2 \rfloor$ | 4 |
| 3 | 0 | 0 | 0-15 | I_{PMI2} | 4 |
| 4 | 0 | 0 | 0-15 | I_{PMI2} | 4 |

Table 7.2.2-1 H: Joint encoding of RI and for PUCCH mode 1-1 submode 1 with 4 antenna ports

| Value of joint encoding of RI and the first PMI $I_{RI/PMI1}$ | RI | Codebook index i_1 |
|---|----------|----------------------|
| 0-7 | 1 | $I_{RI/PMI1}$ |
| 8-15 | 2 | $I_{RI/PMI1} - 8$ |
| 16 | 3 | 0 |
| 17 | 4 | 0 |
| 18-31 | reserved | NA |

Table 7.2.2-1 I: PUCCH mode 2-1 codebook subsampling with 4 antenna ports

| RI | Relationship between the second PMI value and codebook index i_2 | |
|----|--|--|
| | Value of the second PMI I_{PMI2} | Codebook index i_2 |
| 1 | 0-15 | I_{PMI2} |
| 2 | 0-3 | $I_{PMI2} + 2 \cdot \lfloor I_{PMI2} / 2 \rfloor$ |
| 3 | 0-3 | $2I_{PMI2} + 4 \cdot \lfloor I_{PMI2} / 2 \rfloor$ |
| 4 | 0-3 | $2I_{PMI2} + 4 \cdot \lfloor I_{PMI2} / 2 \rfloor$ |

An RI or PTI or any precoding matrix indicator reported for a serving cell in a periodic reporting mode is valid only for CSI reports for that serving cell on that periodic CSI reporting mode.

For serving cell c , a UE configured in transmission mode 10 with PMI/RI reporting for a CSI process can be configured with a 'RI-reference CSI process'. The RI for the 'RI-reference CSI process' is not based on any other configured CSI process other than the 'RI-reference CSI process'. If the UE is configured with a 'RI-reference CSI process' for a CSI process and if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for only one of the CSI processes then the UE is not expected to receive configuration for the CSI process configured with the subframe subsets that have a different set of restricted RIs with precoder codebook subset restriction between the two subframe sets. The UE is not expected to receive configurations for the CSI process and the 'RI-reference CSI process' that have a different:

- periodic CSI reporting mode (including sub-mode if configured), and/or
- number of CSI-RS antenna ports, and/or
- set of restricted RIs with precoder codebook subset restriction if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are not configured by higher layers for both CSI processes, and/or
- set of restricted RIs with precoder codebook subset restriction for each subframe set if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for both CSI processes, and/or
- set of restricted RIs with precoder codebook subset restriction if subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers for only one of the CSI processes, and the set of restricted RIs for the two subframe sets are the same.

For the calculation of CQI/PMI conditioned on the last reported RI, in the absence of a last reported RI the UE shall conduct the CQI/PMI calculation conditioned on the lowest possible RI as given by the bitmap parameter *codebookSubsetRestriction* and the parameter *alternativeCodeBookEnabledFor4TX-r12* if configured. If reporting for more than one CSI subframe set is configured, CQI/PMI is conditioned on the last reported RI linked to the same subframe set as the CSI report.

- Wideband feedback
 - Mode 1-0 description:
 - In the subframe where RI is reported (only for transmission mode 3):
 - A UE shall determine a RI assuming transmission on set S subbands.
 - The UE shall report a type 3 report consisting of one RI.
 - In the subframe where CQI is reported:

- A UE shall report a type 4 report consisting of one wideband CQI value which is calculated assuming transmission on set S subbands. The wideband CQI represents channel quality for the first codeword, even when $RI > 1$.
 - For transmission mode 3 the CQI is calculated conditioned on the last reported periodic RI. For other transmission modes it is calculated conditioned on transmission rank 1.
- o Mode 1-1 description:
- In the subframe where RI is reported (only for transmission modes 4, 8, 9 and 10):
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, the RI for the CSI process shall be the same as the RI in the most recent CSI report comprising RI for the configured 'RI-reference CSI process' irrespective of subframe sets if configured; otherwise, the UE shall determine a RI assuming transmission on set S subbands.
 - The UE shall report a type 3 report consisting of one RI.
 - In the subframe where RI and a first PMI are reported for transmission modes 9 and 10 configured with submode 1 and 8 CSI-RS ports, and for transmission modes 8, 9 and 10 configured with submode 1 and *alternativeCodeBookEnabledFor4TX-r12=TRUE*:
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, the RI for the CSI process shall be the same as the RI in the most recent CSI report comprising RI for the configured 'RI-reference CSI process' irrespective of subframe sets if configured; otherwise, the UE shall determine a RI assuming transmission on set S subbands.
 - The UE shall report a type 5 report consisting of jointly coded RI and a first PMI corresponding to a set of precoding matrices selected from the codebook subset assuming transmission on set S subbands.
 - If the UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process and in case of collision of type 5 report for the CSI process with type 5 report for the 'RI-reference CSI process', the wideband first PMI for the CSI process shall be the same as the wideband first PMI in the most recent type 5 report for the configured 'RI-reference CSI process'; otherwise, the wideband first PMI value is calculated conditioned on the reported periodic RI.
 - In the subframe where CQI/PMI is reported for all transmission modes except with 8 CSI-RS ports configured for transmission modes 9 and 10, or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands.
 - A UE shall report a type 2 report consisting of
 - o A single wideband CQI value which is calculated assuming the use of a single precoding matrix in all subbands and transmission on set S subbands.
 - o The selected single PMI (wideband PMI).
 - o When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
 - For transmission modes 4, 8, 9 and 10,
 - o If a UE is configured in transmission mode 10 with a "RI-reference CSI process" for a CSI process, and the most recent type 3 report for the CSI process is dropped, and a type 3 report for the "RI-reference CSI process" is reported in the most recent RI reporting instance for the CSI process, the PMI and CQI for the CSI process are calculated

conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process; otherwise the PMI and CQI are calculated conditioned on the last reported periodic RI.

- For other transmission modes the PMI and CQI are calculated conditioned on transmission rank 1.
- In the subframe where wideband CQI/second PMI is reported for transmission modes 9 and 10 with 8 CSI-RS ports and submode 1 configured and for transmission modes 8, 9 and 10 with submode 1 and *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set *S* subbands.
 - A UE shall report a type 2b report consisting of
 - A single wideband CQI value which is calculated assuming the use of the single precoding matrix in all subbands and transmission on set *S* subbands.
 - The wideband second PMI corresponding to the selected single precoding matrix.
 - When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 5 report for the CSI process is dropped, and a type 5 report for the 'RI-reference CSI process' is reported in the most recent RI reporting instance for the CSI process,
 - The wideband second PMI value for the CSI process is calculated conditioned on the reported periodic RI and the wideband first PMI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process.
 - The wideband CQI value is calculated conditioned on the selected precoding matrix for the CSI process and the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process.
 - Otherwise,
 - The wideband second PMI value is calculated conditioned on the last reported periodic RI and the wideband first PMI.
 - The wideband CQI value is calculated conditioned on the selected precoding matrix and the last reported periodic RI.
- In the subframe where wideband CQI/first PMI/second PMI is reported for transmission modes 9 and 10 with 8 CSI-RS ports and submode 2 configured, and for transmission modes 8, 9 and 10 with submode 2 and *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set *S* subbands.
 - A UE shall report a type 2c report consisting of
 - A single wideband CQI value which is calculated assuming the use of a single precoding matrix in all subbands and transmission on set *S* subbands.
 - The wideband first PMI and the wideband second PMI corresponding to the selected single precoding matrix as defined in subclause 7.2.4.
 - When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 3 report for the CSI

process is dropped, and a type 3 report for the 'RI-reference CSI process' is reported in the most recent RI reporting instance for the CSI process, the wideband first PMI, the wideband second PMI and the wideband CQI for the CSI process are calculated conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process; otherwise the wideband first PMI, the wideband second PMI and the wideband CQI are calculated conditioned on the last reported periodic RI.

- UE Selected subband feedback
 - Mode 2-0 description:
 - In the subframe where RI is reported (only for transmission mode 3):
 - A UE shall determine a RI assuming transmission on set S subbands.
 - The UE shall report a type 3 report consisting of one RI.
 - In the subframe where wideband CQI is reported:
 - The UE shall report a type 4 report on each respective successive reporting opportunity consisting of one wideband CQI value which is calculated assuming transmission on set S subbands. The wideband CQI represents channel quality for the first codeword, even when $RI > 1$.
 - For transmission mode 3 the CQI is calculated conditioned on the last reported periodic RI. For other transmission modes it is calculated conditioned on transmission rank 1.
 - In the subframe where CQI for the selected subbands is reported:
 - The UE shall select the preferred subband within the set of N_j subbands in each of the J bandwidth parts where J is given in Table 7.2.2-2.
 - The UE shall report a type 1 report consisting of one CQI value reflecting transmission only over the selected subband of a bandwidth part determined in the previous step along with the corresponding preferred subband L -bit label. A type 1 report for each bandwidth part will in turn be reported in respective successive reporting opportunities. The CQI represents channel quality for the first codeword, even when $RI > 1$.
 - For transmission mode 3 the preferred subband selection and CQI values are calculated conditioned on the last reported periodic RI. For other transmission modes they are calculated conditioned on transmission rank 1.
 - Mode 2-1 description:
 - In the subframe where RI is reported for transmission mode 4, transmission mode 8 except with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured, transmission modes 9 and 10 with 2 CSI-RS ports, and transmission modes 9 and 10 with 4 CSI-RS ports except with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, the RI for the CSI process shall be the same as the RI in the most recent CSI report comprising RI for the configured 'RI-reference CSI process' irrespective of subframe sets if configured; otherwise, the UE shall determine a RI assuming transmission on set S subbands.
 - The UE shall report a type 3 report consisting of one RI.
 - In the subframe where RI is reported for transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8, 9 and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured then:

- If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, the RI for the CSI process shall be the same as the RI in the most recent CSI report comprising RI for the configured 'RI-reference CSI process' irrespective of subframe sets if configured; otherwise, the UE shall determine a RI assuming transmission on set S subbands.
- If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, the PTI for the CSI process shall be the same as the PTI in the most recent type 6 report for the configured 'RI-reference CSI process'; otherwise, the UE shall determine a precoder type indication (PTI).
- The PTI for the CSI process shall be equal to 1 if the RI reported jointly with the PTI is greater than 2 for transmission modes 8, 9, 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured.
- The UE shall report a type 6 report consisting of one RI and the PTI.
- In the subframe where wideband CQI/PMI is reported for all transmission modes except with 8 CSI-RS ports configured for transmission modes 9 and 10, or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands.
 - A UE shall report a type 2 report on each respective successive reporting opportunity consisting of:
 - A wideband CQI value which is calculated assuming the use of a single precoding matrix in all subbands and transmission on set S subbands.
 - The selected single PMI (wideband PMI).
 - When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
 - For transmission modes 4, 8, 9 and 10,
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 3 report for the CSI process is dropped, and a type 3 report for the 'RI-reference CSI process' is reported in the most recent RI reporting instance for the CSI process, the PMI and CQI values for the CSI process are calculated conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process; otherwise the PMI and CQI values are calculated conditioned on the last reported periodic RI.
 - For other transmission modes the PMI and CQI values are calculated conditioned on transmission rank 1.
- In the subframe where the wideband first PMI is reported for transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8, 9 and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - A set of precoding matrices corresponding to the wideband first PMI is selected from the codebook subset assuming transmission on set S subbands.
 - A UE shall report a type 2a report on each respective successive reporting opportunity consisting of the wideband first PMI corresponding to the selected set of precoding matrices.
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 6 report for the CSI process is dropped, and a type 6 report for the 'RI-reference CSI process' with PTI=0 is reported in the most recent RI reporting instance for the CSI process, the wideband first PMI value for the CSI process is calculated conditioned on

the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process; otherwise with the last reported PTI=0, the wideband first PMI value is calculated conditioned on the last reported periodic RI.

- In the subframe where wideband CQI/second PMI is reported for transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8,9, and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands.
 - A UE shall report a type 2b report on each respective successive reporting opportunity consisting of:
 - A wideband CQI value which is calculated assuming the use of the selected single precoding matrix in all subbands and transmission on set S subbands.
 - The wideband second PMI corresponding to the selected single precoding matrix.
 - When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 6 report for the CSI process is dropped, and a type 6 report for the 'RI-reference CSI process' with PTI=1 is reported in the most recent RI reporting instance for the CSI process,
 - The wideband second PMI value for the CSI process is calculated conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process and the last reported wideband first PMI for the CSI process,
 - The wideband CQI value is calculated conditioned on the selected precoding matrix for the CSI process and the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process.
 - Otherwise, with the last reported PTI=1,
 - The wideband second PMI value is calculated conditioned on the last reported periodic RI and the wideband first PMI.
 - The wideband CQI value is calculated conditioned on the selected precoding matrix and the last reported periodic RI.
 - If the last reported first PMI was computed under an RI assumption that differs from the last reported periodic RI, or in the absence of a last reported first PMI, the conditioning of the second PMI value is not specified.
- In the subframe where CQI for the selected subband is reported for all transmission modes except with 8 CSI-RS ports configured for transmission modes 9 and 10, or with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured for transmission modes 8, 9 and 10:
 - The UE shall select the preferred subband within the set of N_j subbands in each of the J bandwidth parts where J is given in Table 7.2.2-2.
 - The UE shall report a type 1 report per bandwidth part on each respective successive reporting opportunity consisting of:

- CQI value for codeword 0 reflecting transmission only over the selected subband of a bandwidth part determined in the previous step along with the corresponding preferred subband L -bit label.
- When $RI > 1$, an additional 3-bit subband spatial differential CQI value for codeword 1 offset level
 - Codeword 1 offset level = subband CQI index for codeword 0 – subband CQI index for codeword 1.
 - Assuming the use of the most recently reported single precoding matrix in all subbands and transmission on the selected subband within the applicable bandwidth part.
- The mapping from the 3-bit subband spatial differential CQI value to the offset level is shown in Table 7.2-2.
- For transmission modes 4, 8, 9 and 10,
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 3 report for the CSI process is dropped, and a type 3 report for the 'RI-reference CSI process' is reported in the most recent RI reporting instance for the CSI process, the subband selection and CQI values for the CSI process are calculated conditioned on the last reported periodic wideband PMI for the CSI process and the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process; otherwise the subband selection and CQI values are calculated conditioned on the last reported periodic wideband PMI and RI.
- For other transmission modes the subband selection and CQI values are calculated conditioned on the last reported PMI and transmission rank 1.
- In the subframe where wideband CQI/second PMI is reported for transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8, 9 and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - A single precoding matrix is selected from the codebook subset assuming transmission on set S subbands.
 - The UE shall report a type 2b report on each respective successive reporting opportunity consisting of:
 - A wideband CQI value which is calculated assuming the use of the selected single precoding matrix in all subbands and transmission on set S subbands.
 - The wideband second PMI corresponding to the selected single precoding matrix.
 - When $RI > 1$, an additional 3-bit wideband spatial differential CQI, which is shown in Table 7.2-2.
- If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 6 report for the CSI process is dropped, and a type 6 report for the 'RI-reference CSI process' with $PTI=0$ is reported in the most recent RI reporting instance for the CSI process,
 - The wideband second PMI value for the CSI process is calculated conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process and the last reported wideband first PMI for the CSI process.

- The wideband CQI value is calculated conditioned on the selected precoding matrix for the CSI process and the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process.
- Otherwise, with the last reported PTI=0,
 - The wideband second PMI value is calculated conditioned on the last reported periodic RI and the wideband first PMI. The wideband CQI value is calculated conditioned on the selected precoding matrix and the last reported periodic RI.
- If the last reported first PMI was computed under an RI assumption that differs from the last reported periodic RI, or in the absence of a last reported first PMI, the conditioning of the second PMI value is not specified.
- In the subframe where subband CQI/second PMI for the selected subband is reported for transmission modes 9 and 10 with 8 CSI-RS ports configured and for transmission modes 8, 9 and 10 with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured:
 - The UE shall select the preferred subband within the set of N_j subbands in each of the J bandwidth parts where J is given in Table 7.2.2-2.
 - The UE shall report a type 1a report per bandwidth part on each respective successive reporting opportunity consisting of:
 - CQI value for codeword 0 reflecting transmission only over the selected subband of a bandwidth part determined in the previous step along with the corresponding preferred subband L -bit label.
 - When $RI > 1$, an additional 3-bit subband spatial differential CQI value for codeword 1 offset level
 - Codeword 1 offset level = subband CQI index for codeword 0 – subband CQI index for codeword 1.
 - Assuming the use of the precoding matrix corresponding to the selected second PMI and the most recently reported first PMI and transmission on the selected subband within the applicable bandwidth part.
 - The mapping from the 3-bit subband spatial differential CQI value to the offset level is shown in Table 7.2-2.
 - A second PMI of the preferred precoding matrix selected from the codebook subset assuming transmission only over the selected subband within the applicable bandwidth part determined in the previous step.
 - If a UE is configured in transmission mode 10 with a 'RI-reference CSI process' for a CSI process, and the most recent type 6 report for the CSI process is dropped, and a type 6 report for the 'RI-reference CSI process' with PTI=1 is reported in the most recent RI reporting instance for the CSI process,
 - The subband second PMI values for the CSI process are calculated conditioned on the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process and the last reported wideband first PMI for the CSI process.
 - The subband selection and CQI values are calculated conditioned on the selected precoding matrix for the CSI process and the reported periodic RI for the configured 'RI-reference CSI process' in the most recent RI reporting instance for the CSI process.

- Otherwise, with the last reported PTI=1
 - The subband second PMI values are calculated conditioned on the last reported periodic RI and the wideband first PMI.
 - The subband selection and CQI values are calculated conditioned on the selected precoding matrix and the last reported periodic RI.
- If the last reported first PMI was computed under an RI assumption that differs from the last reported periodic RI, or in the absence of a last reported first PMI, the conditioning of the second PMI value is not specified.

Table 7.2.2-2: Subband Size (k) and Bandwidth Parts (J) vs. Downlink System Bandwidth

| System Bandwidth N_{RB}^{DL} | Subband Size k (RBs) | Bandwidth Parts (J) |
|--------------------------------|------------------------|-------------------------|
| 6 – 7 | NA | NA |
| 8 – 10 | 4 | 1 |
| 11 – 26 | 4 | 2 |
| 27 – 63 | 6 | 3 |
| 64 – 110 | 8 | 4 |

If parameter *ttiBundling* provided by higher layers is set to *TRUE* and if an UL-SCH in subframe bundling operation collides with a periodic CSI reporting instance, then the UE shall drop the periodic CSI report of a given PUCCH reporting type in that subframe and shall not multiplex the periodic CSI report payload in the PUSCH transmission in that subframe. A UE is not expected to be configured with simultaneous PUCCH and PUSCH transmission when UL-SCH subframe bundling is configured.

Table 7.2.2-3: PUCCH Reporting Type Payload size per PUCCH Reporting Mode and Mode State

| PUCCH Reporting Type | Reported | Mode State | PUCCH Reporting Modes | | | |
|----------------------|---------------------------------------|---|------------------------|------------------------|------------------------|------------------------|
| | | | Mode 1-1 (bits/BP*) | Mode 2-1 (bits/BP*) | Mode 1-0 (bits/BP*) | Mode 2-0 (bits/BP*) |
| 1 | Sub-band CQI | RI = 1 | NA | 4+L | NA | 4+L |
| | | RI > 1 | NA | 7+L | NA | 4+L |
| 1a | Sub-band CQI / second PMI | 8 antenna ports RI = 1 | NA | 8+L | NA | NA |
| | | 8 antenna ports 1 < RI < 5 | NA | 9+L | NA | NA |
| | | 8 antenna ports RI > 4 | NA | 7+L | NA | NA |
| | | 4 antenna ports RI=1 | NA | 8+L | NA | NA |
| | | 4 antenna ports 1<RI≤4 | NA | 9+L | NA | NA |
| 2 | Wideband CQI/PMI | 2 antenna ports RI = 1 | 6 | 6 | NA | NA |
| | | 4 antenna ports RI = 1 | 8 | 8 | NA | NA |
| | | 2 antenna ports RI > 1 | 8 | 8 | NA | NA |
| | | 4 antenna ports RI > 1 | 11 | 11 | NA | NA |
| 2a | Wideband first PMI | 8 antenna ports RI < 3 | NA | 4 | NA | NA |
| | | 8 antenna ports 2 < RI < 8 | NA | 2 | NA | NA |
| | | 8 antenna ports RI = 8 | NA | 0 | NA | NA |
| | | 4 antenna ports 1≤RI≤2 | NA | 4 | NA | NA |
| | | 4 antenna ports 2≤RI≤4 | NA | NA | NA | NA |
| 2b | Wideband CQI / second PMI | 8 antenna ports RI = 1 | 8 | 8 | NA | NA |
| | | 8 antenna ports 1 < RI < 4 | 11 | 11 | NA | NA |
| | | 8 antenna ports RI = 4 | 10 | 10 | NA | NA |
| | | 8 antenna ports RI > 4 | 7 | 7 | NA | NA |
| | | 4 antenna ports RI=1 | 8 | 8 | NA | NA |
| | | 4 antenna port 1<RI≤4 | 11 | 11 | NA | NA |
| 2c | Wideband CQI / first PMI / second PMI | 8 antenna ports RI = 1 | 8 | NA | NA | NA |
| | | 8 antenna ports 1 < RI ≤ 4 | 11 | NA | NA | NA |
| | | 8 antenna ports 4 < RI ≤ 7 | 9 | NA | NA | NA |
| | | 8 antenna ports RI = 8 | 7 | NA | NA | NA |
| | | 4 antenna ports RI=1 | 8 | NA | NA | NA |
| | | 4 antenna port 1<RI≤4 | 11 | NA | NA | NA |
| 3 | RI | 2/4 antenna ports, 2-layer spatial multiplexing | 1 | 1 | 1 | 1 |
| | | 8 antenna ports, 2-layer spatial multiplexing | 1 | NA | NA | NA |
| | | 4 antenna ports, 4-layer spatial multiplexing | 2 | 2 | 2 | 2 |
| | | 8 antenna ports, 4-layer spatial multiplexing | 2 | NA | NA | NA |
| | | 8-layer spatial multiplexing | 3 | NA | NA | NA |
| 4 | Wideband CQI | RI = 1 or RI>1 | NA | NA | 4 | 4 |
| 5 | RI/ first PMI | 8 antenna ports, 2-layer spatial multiplexing | 4 | NA | NA | NA |
| | | 8 antenna ports, 4 and 8-layer spatial multiplexing | 5 | | | |
| | | 4 antenna ports, 2-layer spatial multiplexing | 4 | | | |
| | | 4 antenna ports, 4-layer spatial multiplexing | 5 | | | |
| 6 | RI/PTI | 8 antenna ports, 2-layer spatial multiplexing | NA | 2 | NA | NA |
| | | 8 antenna ports, 4-layer spatial multiplexing | NA | 3 | NA | NA |
| | | 8 antenna ports, 8-layer spatial multiplexing | NA | 4 | NA | NA |
| | | 4 antenna ports, 2-layer spatial multiplexing | NA | 2 | NA | NA |
| | | 4 antenna ports, 4-layer spatial multiplexing | NA | 3 | NA | NA |

NOTE : For wideband CQI reporting types, the stated payload size applies to the full bandwidth.

7.2.3 Channel Quality Indicator (CQI) definition

The CQI indices and their interpretations are given in Table 7.2.3-1 for reporting CQI based on QPSK, 16QAM and 64QAM. The CQI indices and their interpretations are given in Table 7.2.3-2 for reporting CQI based on QPSK, 16QAM, 64QAM and 256QAM.

Based on an unrestricted observation interval in time and frequency, the UE shall derive for each CQI value reported in uplink subframe n the highest CQI index between 1 and 15 in Table 7.2.3-1 or Table 7.2.3-2 which satisfies the following condition, or CQI index 0 if CQI index 1 does not satisfy the condition:

- A single PDSCH transport block with a combination of modulation scheme and transport block size corresponding to the CQI index, and occupying a group of downlink physical resource blocks termed the CSI reference resource, could be received with a transport block error probability not exceeding 0.1.

If CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers, each CSI reference resource belongs to either $C_{CSI,0}$ or $C_{CSI,1}$ but not to both. When CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ are configured by higher layers a UE is not expected to receive a trigger for which the CSI reference resource is in subframe that does not belong to either subframe set. For a UE in transmission mode 10 and periodic CSI reporting, the CSI subframe set for the CSI reference resource is configured by higher layers for each CSI process.

For a UE in transmission mode 9 when parameter *pmi-RI-Report* is configured by higher layers, the UE shall derive the channel measurements for computing the CQI value reported in uplink subframe n based on only the Channel-State Information (CSI) reference signals (CSI-RS) defined in [3] for which the UE is configured to assume non-zero power for the CSI-RS. For a UE in transmission mode 9 when the parameter *pmi-RI-Report* is not configured by higher layers or in transmission modes 1-8 the UE shall derive the channel measurements for computing CQI based on CRS.

For a UE in transmission mode 10, the UE shall derive the channel measurements for computing the CQI value reported in uplink subframe n and corresponding to a CSI process, based on only the non-zero power CSI-RS (defined in [3]) within a configured CSI-RS resource associated with the CSI process.

For a UE in transmission mode 10, the UE shall derive the interference measurements for computing the CQI value reported in uplink subframe n and corresponding to a CSI process, based on only the configured CSI-IM resource associated with the CSI process. If the UE in transmission mode 10 is configured by higher layers for CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ for the CSI process, the configured CSI-IM resource within the subframe subset belonging to the CSI reference resource is used to derive the interference measurement. For a UE configured with the parameter *EIMTA-MainConfigServCell-r12* for a serving cell, configured CSI-IM resource(s) within only downlink subframe(s) of a radio frame that are indicated by UL/DL configuration of the serving cell can be used to derive the interference measurement for the serving cell.

A combination of modulation scheme and transport block size corresponds to a CQI index if:

- the combination could be signalled for transmission on the PDSCH in the CSI reference resource according to the relevant Transport Block Size table, and
- the modulation scheme is indicated by the CQI index, and
- the combination of transport block size and modulation scheme when applied to the reference resource results in the effective channel code rate which is the closest possible to the code rate indicated by the CQI index. If more than one combination of transport block size and modulation scheme results in an effective channel code rate equally close to the code rate indicated by the CQI index, only the combination with the smallest of such transport block sizes is relevant.

The CSI reference resource for a serving cell is defined as follows:

- In the frequency domain, the CSI reference resource is defined by the group of downlink physical resource blocks corresponding to the band to which the derived CQI value relates.
- In the time domain,
 - for a UE configured in transmission mode 1-9 or transmission mode 10 with a single configured CSI process for the serving cell, the CSI reference resource is defined by a single downlink or special subframe $n-n_{CQI_ref}$

- where for periodic CSI reporting n_{CQI_ref} is the smallest value greater than or equal to 4, such that it corresponds to a valid downlink or valid special subframe,
- where for aperiodic CSI reporting, if the UE is not configured with the higher layer parameter *csi-SubframePatternConfig-r12*,
 - n_{CQI_ref} is such that the reference resource is in the same valid downlink or valid special subframe as the corresponding CSI request in an uplink DCI format.
 - n_{CQI_ref} is equal to 4 and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in a Random Access Response Grant.
- where for aperiodic CSI reporting, and the UE configured with the higher layer parameter *csi-SubframePatternConfig-r12*,
 - for the UE configured in transmission mode 1-9,
 - n_{CQI_ref} is the smallest value greater than or equal to 4 and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received on or after the subframe with the corresponding CSI request in an uplink DCI format;
 - n_{CQI_ref} is the smallest value greater than or equal to 4, and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in an Random Access Response Grant;
 - if there is no valid value for n_{CQI_ref} based on the above conditions, then n_{CQI_ref} is the smallest value such that the reference resource is in a valid downlink or valid special subframe $n-n_{CQI_ref}$ prior to the subframe with the corresponding CSI request, where subframe $n-n_{CQI_ref}$ is the lowest indexed valid downlink or valid special subframe within a radio frame;
 - for the UE configured in transmission mode 10,
 - n_{CQI_ref} is the smallest value greater than or equal to 4, such that it corresponds to a valid downlink or valid special subframe, and the corresponding CSI request is in an uplink DCI format;
 - n_{CQI_ref} is the smallest value greater than or equal to 4, and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in a Random Access Response Grant;
- for a UE configured in transmission mode 10 with multiple configured CSI processes for the serving cell, the CSI reference resource for a given CSI process is defined by a single downlink or special subframe $n-n_{CQI_ref}$,
 - where for FDD serving cell and periodic or aperiodic CSI reporting n_{CQI_ref} is the smallest value greater than or equal to 5, such that it corresponds to a valid downlink or valid special subframe, and for aperiodic CSI reporting the corresponding CSI request is in an uplink DCI format;
 - where for FDD serving cell and aperiodic CSI reporting n_{CQI_ref} is equal to 5 and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in a Random Access Response Grant.
 - where for TDD serving cell, and 2 or 3 configured CSI processes, and periodic or aperiodic CSI reporting, n_{CQI_ref} is the smallest value greater than or equal to 4, such that it corresponds to a valid downlink or valid special subframe, and for aperiodic CSI reporting the corresponding CSI request is in an uplink DCI format;
 - where for TDD serving cell, and 2 or 3 configured CSI processes, and aperiodic CSI reporting, n_{CQI_ref} is equal to 4 and subframe $n-n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n-n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in a Random Access Response Grant;
 - where for TDD serving cell, and 4 configured CSI processes, and periodic or aperiodic CSI reporting, n_{CQI_ref} is the smallest value greater than or equal to 5, such that it corresponds to a valid downlink or valid special subframe, and for aperiodic CSI reporting the corresponding CSI request is in an uplink DCI format;

- where for TDD serving cell, and 4 configured CSI processes, and aperiodic CSI reporting, n_{CQI_ref} is equal to 5 and subframe $n - n_{CQI_ref}$ corresponds to a valid downlink or valid special subframe, where subframe $n - n_{CQI_ref}$ is received after the subframe with the corresponding CSI request in a Random Access Response Grant.

A subframe in a serving cell shall be considered to be a valid downlink or a valid special subframe if:

- it is configured as a downlink subframe or a special subframe for that UE, and
- in case multiple cells with different uplink-downlink configurations are aggregated and the UE is not capable of simultaneous reception and transmission in the aggregated cells, the subframe in the primary cell is a downlink subframe or a special subframe with the length of DwPTS more than $7680 \cdot T_s$, and
- except for transmission mode 9 or 10, it is not an MBSFN subframe, and
- it does not contain a DwPTS field in case the length of DwPTS is $7680 \cdot T_s$ and less, and
- it does not fall within a configured measurement gap for that UE, and
- for periodic CSI reporting, it is an element of the CSI subframe set linked to the periodic CSI report when that UE is configured with CSI subframe sets, and
- for a UE configured in transmission mode 10 with multiple configured CSI processes, and aperiodic CSI reporting for a CSI process, it is an element of the CSI subframe set linked to the downlink or special subframe with the corresponding CSI request in an uplink DCI format, when that UE is configured with CSI subframe sets for the CSI process and UE is not configured with the higher layer parameter *csi-SubframePatternConfig-r12*, and
- for a UE configured in transmission mode 1-9, and aperiodic CSI reporting, it is an element of the CSI subframe set associated with the corresponding CSI request in an uplink DCI format, when that UE is configured with CSI subframe sets by the higher layer parameter *csi-SubframePatternConfig-r12*, and
- for a UE configured in transmission mode 10, and aperiodic CSI reporting for a CSI process, it is an element of the CSI subframe set associated with the corresponding CSI request in an uplink DCI format, when that UE is configured with CSI subframe sets by the higher layer parameter *csi-SubframePatternConfig-r12* for the CSI process.

If there is no valid downlink or no valid special subframe for the CSI reference resource in a serving cell, CSI reporting is omitted for the serving cell in uplink subframe n .

In the layer domain, the CSI reference resource is defined by any RI and PMI on which the CQI is conditioned.

In the CSI reference resource, the UE shall assume the following for the purpose of deriving the CQI index, and if also configured, PMI and RI:

- The first 3 OFDM symbols are occupied by control signalling
- No resource elements used by primary or secondary synchronization signals or PBCH or EPDCCH
- CP length of the non-MBSFN subframes
- Redundancy Version 0
- If CSI-RS is used for channel measurements, the ratio of PDSCH EPRE to CSI-RS EPRE is as given in subclause 7.2.5
- For transmission mode 9 CSI reporting:
 - CRS REs are as in non-MBSFN subframes;
 - If the UE is configured for PMI/RI reporting, the UE-specific reference signal overhead is consistent with the most recent reported rank if more than one CSI-RS port is configured, and is consistent with rank 1 transmission if only one CSI-RS port is configured; and PDSCH signals on antenna ports $\{7 \dots 6 + \nu\}$ for ν layers would result in signals equivalent to corresponding symbols transmitted on antenna ports

$$\{15 \dots 14 + P\}, \text{ as given by } \begin{bmatrix} y^{(15)}(i) \\ \vdots \\ y^{(14+P)}(i) \end{bmatrix} = W(i) \begin{bmatrix} x^{(0)}(i) \\ \vdots \\ x^{(v-1)}(i) \end{bmatrix}, \text{ where } x(i) = [x^{(0)}(i) \dots x^{(v-1)}(i)]^T \text{ is a}$$

vector of symbols from the layer mapping in subclause 6.3.3.2 of [3], $P \in \{1,2,4,8\}$ is the number of CSI-RS ports configured, and if only one CSI-RS port is configured, $W(i)$ is 1, otherwise $W(i)$ is the precoding matrix corresponding to the reported PMI applicable to $x(i)$. The corresponding PDSCH signals transmitted on antenna ports $\{15 \dots 14 + P\}$ would have a ratio of EPRE to CSI-RS EPRE equal to the ratio given in subclause 7.2.5.

- For transmission mode 10 CSI reporting, if a CSI process is configured without PMI/RI reporting:
 - If the number of antenna ports of the associated CSI-RS resource is one, a PDSCH transmission is on single-antenna port, port 7. The channel on antenna port $\{7\}$ is inferred from the channel on antenna port $\{15\}$ of the associated CSI-RS resource.
 - CRS REs are as in non-MBSFN subframes. The CRS overhead is assumed to be the same as the CRS overhead corresponding to the number of CRS antenna ports of the serving cell;
 - The UE-specific reference signal overhead is 12 REs per PRB pair.
 - Otherwise,
 - If the number of antenna ports of the associated CSI-RS resource is 2, the PDSCH transmission scheme assumes the transmit diversity scheme defined in subclause 7.1.2 on antenna ports $\{0,1\}$ except that the channels on antenna ports $\{0,1\}$ are inferred from the channels on antenna port $\{15, 16\}$ of the associated CSI resource respectively.
 - If the number of antenna ports of the associated CSI-RS resource is 4, the PDSCH transmission scheme assumes the transmit diversity scheme defined in subclause 7.1.2 on antenna ports $\{0,1,2,3\}$ except that the channels on antenna ports $\{0,1,2,3\}$ are inferred from the channels on antenna ports $\{15, 16, 17, 18\}$ of the associated CSI-RS resource respectively.
 - The UE is not expected to be configured with more than 4 antenna ports for the CSI-RS resource associated with the CSI process configured without PMI/RI reporting.
 - The overhead of CRS REs is assuming the same number of antenna ports as that of the associated CSI-RS resource.
 - UE-specific reference signal overhead is zero.

- For transmission mode 10 CSI reporting, if a CSI process is configured with PMI/RI reporting:

- CRS REs are as in non-MBSFN subframes. The CRS overhead is assumed to be the same as the CRS overhead corresponding to the number of CRS antenna ports of the serving cell;
- The UE-specific reference signal overhead is consistent with the most recent reported rank for the CSI process if more than one CSI-RS port is configured, and is consistent with rank 1 transmission if only one CSI-RS port is configured; and PDSCH signals on antenna ports $\{7 \dots 6 + v\}$ for v layers would result in signals equivalent to corresponding symbols transmitted on antenna ports $\{15 \dots 14 + P\}$, as given by

$$\begin{bmatrix} y^{(15)}(i) \\ \vdots \\ y^{(14+P)}(i) \end{bmatrix} = W(i) \begin{bmatrix} x^{(0)}(i) \\ \vdots \\ x^{(v-1)}(i) \end{bmatrix}, \text{ where } x(i) = [x^{(0)}(i) \dots x^{(v-1)}(i)]^T \text{ is a vector of symbols from the}$$

layer mapping in subclause 6.3.3.2 of [3], $P \in \{1,2,4,8\}$ is the number of antenna ports of the associated CSI-RS resource, and if $P=1$, $W(i)$ is 1, otherwise $W(i)$ is the precoding matrix corresponding to the reported PMI applicable to $x(i)$. The corresponding PDSCH signals transmitted on antenna ports $\{15 \dots 14 + P\}$ would have a ratio of EPRE to CSI-RS EPRE equal to the ratio given in subclause 7.2.5

- Assume no REs allocated for CSI-RS and zero-power CSI-RS
- Assume no REs allocated for PRS
- The PDSCH transmission scheme given by Table 7.2.3-0 depending on the transmission mode currently configured for the UE (which may be the default mode).
- If CRS is used for channel measurements, the ratio of PDSCH EPRE to cell-specific RS EPRE is as given in subclause 5.2 with the exception of ρ_A which shall be assumed to be
 - $\rho_A = P_A + \Delta_{offset} + 10\log_{10}(2)$ [dB] for any modulation scheme, if the UE is configured with transmission mode 2 with 4 cell-specific antenna ports, or transmission mode 3 with 4 cell-specific antenna ports and the associated RI is equal to one;
 - $\rho_A = P_A + \Delta_{offset}$ [dB] for any modulation scheme and any number of layers, otherwise.

The shift Δ_{offset} is given by the parameter *nomPDSCH-RS-EPRE-Offset* which is configured by higher-layer signalling.

Table 7.2.3-0: PDSCH transmission scheme assumed for CSI reference resource

| Transmission mode | Transmission scheme of PDSCH |
|-------------------|--|
| 1 | Single-antenna port, port 0 |
| 2 | Transmit diversity |
| 3 | Transmit diversity if the associated rank indicator is 1, otherwise large delay CDD |
| 4 | Closed-loop spatial multiplexing |
| 5 | Multi-user MIMO |
| 6 | Closed-loop spatial multiplexing with a single transmission layer |
| 7 | If the number of PBCH antenna ports is one, Single-antenna port, port 0; otherwise Transmit diversity |
| 8 | If the UE is configured without PMI/RI reporting: if the number of PBCH antenna ports is one, single-antenna port, port 0; otherwise transmit diversity If the UE is configured with PMI/RI reporting: closed-loop spatial multiplexing |
| 9 | If the UE is configured without PMI/RI reporting: if the number of PBCH antenna ports is one, single-antenna port, port 0; otherwise transmit diversity If the UE is configured with PMI/RI reporting: if the number of CSI-RS ports is one, single-antenna port, port 7; otherwise up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) |
| 10 | If a CSI process of the UE is configured without PMI/RI reporting: if the number of CSI-RS ports is one, single-antenna port, port 7; otherwise transmit diversity If a CSI process of the UE is configured with PMI/RI reporting: if the number of CSI-RS ports is one, single-antenna port, port 7; otherwise up to 8 layer transmission, ports 7-14 (see subclause 7.1.5B) |

Table 7.2.3-1: 4-bit CQI Table

| CQI index | modulation | code rate x 1024 | efficiency |
|-----------|--------------|------------------|------------|
| 0 | out of range | | |
| 1 | QPSK | 78 | 0.1523 |
| 2 | QPSK | 120 | 0.2344 |
| 3 | QPSK | 193 | 0.3770 |
| 4 | QPSK | 308 | 0.6016 |
| 5 | QPSK | 449 | 0.8770 |
| 6 | QPSK | 602 | 1.1758 |
| 7 | 16QAM | 378 | 1.4766 |
| 8 | 16QAM | 490 | 1.9141 |
| 9 | 16QAM | 616 | 2.4063 |
| 10 | 64QAM | 466 | 2.7305 |
| 11 | 64QAM | 567 | 3.3223 |
| 12 | 64QAM | 666 | 3.9023 |
| 13 | 64QAM | 772 | 4.5234 |
| 14 | 64QAM | 873 | 5.1152 |
| 15 | 64QAM | 948 | 5.5547 |

Table 7.2.3-2: 4-bit CQI Table 2

| CQI index | modulation | code rate x 1024 | efficiency |
|-----------|--------------|------------------|------------|
| 0 | out of range | | |
| 1 | QPSK | 78 | 0.1523 |
| 2 | QPSK | 193 | 0.3770 |
| 3 | QPSK | 449 | 0.8770 |
| 4 | 16QAM | 378 | 1.4766 |
| 5 | 16QAM | 490 | 1.9141 |
| 6 | 16QAM | 616 | 2.4063 |
| 7 | 64QAM | 466 | 2.7305 |
| 8 | 64QAM | 567 | 3.3223 |
| 9 | 64QAM | 666 | 3.9023 |
| 10 | 64QAM | 772 | 4.5234 |
| 11 | 64QAM | 873 | 5.1152 |
| 12 | 256QAM | 711 | 5.5547 |
| 13 | 256QAM | 797 | 6.2266 |
| 14 | 256QAM | 885 | 6.9141 |
| 15 | 256QAM | 948 | 7.4063 |

7.2.4 Precoding Matrix Indicator (PMI) definition

For transmission modes 4, 5 and 6, precoding feedback is used for channel dependent codebook based precoding and relies on UEs reporting precoding matrix indicator (PMI). For transmission mode 8, the UE shall report PMI if configured with PMI/RI reporting. For transmission modes 9 and 10, the UE shall report PMI if configured with PMI/RI reporting and the number of CSI-RS ports is larger than 1. A UE shall report PMI based on the feedback modes described in 7.2.1 and 7.2.2. For other transmission modes, PMI reporting is not supported.

For 2 antenna ports, each PMI value corresponds to a codebook index given in Table 6.3.4.2.3-1 of [3] as follows:

- For 2 antenna ports $\{0,1\}$ or $\{15,16\}$ and an associated RI value of 1, a PMI value of $n \in \{0,1,2,3\}$ corresponds to the codebook index n given in Table 6.3.4.2.3-1 of [3] with $\nu = 1$.
- For 2 antenna ports $\{0,1\}$ or $\{15,16\}$ and an associated RI value of 2, a PMI value of $n \in \{0,1\}$ corresponds to the codebook index $n + 1$ given in Table 6.3.4.2.3-1 of [3] with $\nu = 2$.

For 4 antenna ports $\{0,1,2,3\}$ or $\{15,16,17,18\}$, each PMI value corresponds to a codebook index given in Table 6.3.4.2.3-2 of [3] or a pair of codebook indices given in Table 7.2.4-0A, 7.2.4-0B, 7.2.4-0C, or 7.2.4-0D as follows:

- A PMI value of $n \in \{0,1,\dots,15\}$ corresponds to the codebook index n given in Table 6.3.4.2.3-2 of [3] with ν equal to the associated RI value except with *alternativeCodeBookEnabledFor4TX-r12=TRUE* configured.
- If *alternativeCodeBookEnabledFor4TX-r12=TRUE* is configured, each PMI value corresponds to a pair of codebook indices given in Table 7.2.4-0A, 7.2.4-0B, 7.2.4-0C, or 7.2.4-0D, where the quantities φ_n , φ'_n and v'_m in Table 7.2.4-0A and Table 7.2.4-0B are given by

$$\begin{aligned}\varphi_n &= e^{j\pi n/2} \\ \varphi'_n &= e^{j2\pi n/32} \\ v'_m &= \begin{bmatrix} 1 & e^{j2\pi m/32} \end{bmatrix}^T\end{aligned}$$

- A first PMI value of $i_1 \in \{0,1,\dots, f(\nu) - 1\}$ and a second PMI value of $i_2 \in \{0,1,\dots, g(\nu) - 1\}$ correspond to the codebook indices i_1 and i_2 respectively given in Table 7.2.4-0j with ν equal to the associated RI value and where $j = \{A,B,C,D\}$ respectively when $\nu = \{1,2,3,4\}$, $f(\nu) = \{16,16,1,1\}$ and $g(\nu) = \{16,16,16,16\}$.
- The quantity $W_n^{(s)}$ in Table 7.2.4-0C and Table 7.2.4-0D denotes the matrix defined by the columns given by the set $\{s\}$ from the expression $W_n = I - 2u_n u_n^H / u_n^H u_n$ where I is the 4×4 identity matrix and the vector u_n is given by Table 6.3.4.2.3-2 in [3] and $n = i_2$.
- In some cases codebook subsampling is supported. The sub-sampled codebook for PUCCH mode 1-1 submode 2 is defined in Table 7.2.2-1G for first and second precoding matrix indicators i_1 and i_2 . Joint encoding of rank and first precoding matrix indicator i_1 for PUCCH mode 1-1 submode 1 is defined in Table 7.2.2-1H. The sub-sampled codebook for PUCCH mode 2-1 is defined in Table 7.2.2-1I for PUCCH Reporting Type 1a.

Table 7.2.4-0A: Codebook for 1-layer CSI reporting using antenna ports 0 to 3 or 15 to 18

| i_1 | i_2 | | | | | | | |
|---|----------------------|-----------------------|-----------------------|-----------------------|----------------------|-----------------------|-----------------------|-----------------------|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 0 – 15 | $W_{i_1,0}^{(1)}$ | $W_{i_1,8}^{(1)}$ | $W_{i_1,16}^{(1)}$ | $W_{i_1,24}^{(1)}$ | $W_{i_1+8,2}^{(1)}$ | $W_{i_1+8,10}^{(1)}$ | $W_{i_1+8,18}^{(1)}$ | $W_{i_1+8,26}^{(1)}$ |
| i_1 | i_2 | | | | | | | |
| | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| 0 - 15 | $W_{i_1+16,4}^{(1)}$ | $W_{i_1+16,12}^{(1)}$ | $W_{i_1+16,20}^{(1)}$ | $W_{i_1+16,28}^{(1)}$ | $W_{i_1+24,6}^{(1)}$ | $W_{i_1+24,14}^{(1)}$ | $W_{i_1+24,22}^{(1)}$ | $W_{i_1+24,30}^{(1)}$ |
| where $W_{m,n}^{(1)} = \frac{1}{2} \begin{bmatrix} v'_m \\ \varphi'_n v'_m \end{bmatrix}$ | | | | | | | | |

Table 7.2.4-0B: Codebook for 2-layer CSI reporting using antenna ports 0 to 3 or 15 to 18

| | | | | |
|---|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| i_1 | i_2 | | i_2 | |
| | 0 | 1 | 2 | 3 |
| 0 – 15 | $W_{i_1, i_1, 0}^{(2)}$ | $W_{i_1, i_1, 1}^{(2)}$ | $W_{i_1+8, i_1+8, 0}^{(2)}$ | $W_{i_1+8, i_1+8, 1}^{(2)}$ |
| i_1 | i_2 | | i_2 | |
| | 4 | 5 | 6 | 7 |
| 0 – 15 | $W_{i_1+16, i_1+16, 0}^{(2)}$ | $W_{i_1+16, i_1+16, 1}^{(2)}$ | $W_{i_1+24, i_1+24, 0}^{(2)}$ | $W_{i_1+24, i_1+24, 1}^{(2)}$ |
| i_1 | i_2 | | i_2 | |
| | 8 | 9 | 10 | 11 |
| 0 – 15 | $W_{i_1, i_1+8, 0}^{(2)}$ | $W_{i_1, i_1+8, 1}^{(2)}$ | $W_{i_1+8, i_1+16, 0}^{(2)}$ | $W_{i_1+8, i_1+16, 1}^{(2)}$ |
| i_1 | i_2 | | i_2 | |
| | 12 | 13 | 14 | 15 |
| 0 – 15 | $W_{i_1, i_1+24, 0}^{(2)}$ | $W_{i_1, i_1+24, 1}^{(2)}$ | $W_{i_1+8, i_1+24, 0}^{(2)}$ | $W_{i_1+8, i_1+24, 1}^{(2)}$ |
| where $W_{m, m', n}^{(2)} = \frac{1}{\sqrt{8}} \begin{bmatrix} v'_m & v'_{m'} \\ \varphi_n v'_m & -\varphi_n v'_{m'} \end{bmatrix}$ | | | | |

Table 7.2.4-0C: Codebook for 3-layer CSI reporting using antenna ports 15 to 18

| | | | | | | | | |
|-------|--------------------------|--------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| i_1 | i_2 | | | | | | | |
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 0 | $W_0^{\{124\}}/\sqrt{3}$ | $W_1^{\{123\}}/\sqrt{3}$ | $W_2^{\{23\}}/\sqrt{3}$ | $W_3^{\{123\}}/\sqrt{3}$ | $W_4^{\{124\}}/\sqrt{3}$ | $W_5^{\{124\}}/\sqrt{3}$ | $W_6^{\{134\}}/\sqrt{3}$ | $W_7^{\{134\}}/\sqrt{3}$ |
| i_1 | i_2 | | | | | | | |
| | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| 0 | $W_8^{\{124\}}/\sqrt{3}$ | $W_9^{\{134\}}/\sqrt{3}$ | $W_{10}^{\{123\}}/\sqrt{3}$ | $W_{11}^{\{134\}}/\sqrt{3}$ | $W_{12}^{\{123\}}/\sqrt{3}$ | $W_{13}^{\{123\}}/\sqrt{3}$ | $W_{14}^{\{123\}}/\sqrt{3}$ | $W_{15}^{\{123\}}/\sqrt{3}$ |

Table 7.2.4-0D: Codebook for 4-layer CSI reporting using antenna ports 15 to 18

| | | | | | | | | |
|-------|--------------------|--------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| i_1 | i_2 | | | | | | | |
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 0 | $W_0^{\{1234\}}/2$ | $W_1^{\{1234\}}/2$ | $W_2^{\{3214\}}/2$ | $W_3^{\{3214\}}/2$ | $W_4^{\{1234\}}/2$ | $W_5^{\{1234\}}/2$ | $W_6^{\{1324\}}/2$ | $W_7^{\{1324\}}/2$ |
| i_1 | i_2 | | | | | | | |
| | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| 0 | $W_8^{\{1234\}}/2$ | $W_9^{\{1234\}}/2$ | $W_{10}^{\{1324\}}/2$ | $W_{11}^{\{1324\}}/2$ | $W_{12}^{\{1234\}}/2$ | $W_{13}^{\{1324\}}/2$ | $W_{14}^{\{3214\}}/2$ | $W_{15}^{\{1234\}}/2$ |

The UE is not expected to receive the configuration of *alternativeCodeBookEnabledFor4TX-r12* except for transmission mode 8 configured with 4 CRS ports, and transmission modes 9 and 10 configured with 4 CSI-RS ports. For a UE configured in transmission mode 10, the parameter *alternativeCodeBookEnabledFor4TX-r12* may be configured for each CSI process.

For 8 antenna ports, each PMI value corresponds to a pair of codebook indices given in Table 7.2.4-1, 7.2.4-2, 7.2.4-3, 7.2.4-4, 7.2.4-5, 7.2.4-6, 7.2.4-7, or 7.2.4-8, where the quantities φ_n and v_m are given by

$$\varphi_n = e^{j\pi n/2}$$

$$v_m = \begin{bmatrix} 1 & e^{j2\pi m/32} & e^{j4\pi m/32} & e^{j6\pi m/32} \end{bmatrix}^T$$

- as follows: For 8 antenna ports $\{15, 16, 17, 18, 19, 20, 21, 22\}$, a first PMI value of $i_1 \in \{0, 1, \dots, f(v) - 1\}$ and a second PMI value of $i_2 \in \{0, 1, \dots, g(v) - 1\}$ corresponds to the codebook indices i_1 and i_2 given in Table

7.2.4-*j* with *v* equal to the associated RI value and where $j = v$, $f(v) = \{16,16,4,4,4,4,1\}$ and $g(v) = \{16,16,16,8,1,1,1\}$.

- In some cases codebook subsampling is supported. The sub-sampled codebook for PUCCH mode 1-1 submode 2 is defined in Table 7.2.2-1D for first and second precoding matrix indicator i_1 and i_2 . Joint encoding of rank and first precoding matrix indicator i_1 for PUCCH mode 1-1 submode 1 is defined in Table 7.2.2-1E. The sub-sampled codebook for PUCCH mode 2-1 is defined in Table 7.2.2-1F for PUCCH Reporting Type 1a.

Table 7.2.4-1: Codebook for 1-layer CSI reporting using antenna ports 15 to 22

| i_1 | i_2 | | | | | | | |
|---|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 0 – 15 | $W_{2i_1,0}^{(1)}$ | $W_{2i_1,1}^{(1)}$ | $W_{2i_1,2}^{(1)}$ | $W_{2i_1,3}^{(1)}$ | $W_{2i_1+1,0}^{(1)}$ | $W_{2i_1+1,1}^{(1)}$ | $W_{2i_1+1,2}^{(1)}$ | $W_{2i_1+1,3}^{(1)}$ |
| i_1 | i_2 | | | | | | | |
| | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| 0 - 15 | $W_{2i_1+2,0}^{(1)}$ | $W_{2i_1+2,1}^{(1)}$ | $W_{2i_1+2,2}^{(1)}$ | $W_{2i_1+2,3}^{(1)}$ | $W_{2i_1+3,0}^{(1)}$ | $W_{2i_1+3,1}^{(1)}$ | $W_{2i_1+3,2}^{(1)}$ | $W_{2i_1+3,3}^{(1)}$ |
| where $W_{m,n}^{(1)} = \frac{1}{\sqrt{8}} \begin{bmatrix} v_m \\ \varphi_n v_m \end{bmatrix}$ | | | | | | | | |

Table 7.2.4-2: Codebook for 2-layer CSI reporting using antenna ports 15 to 22

| i_1 | i_2 | | | |
|--|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| | 0 | 1 | 2 | 3 |
| 0 – 15 | $W_{2i_1,2i_1,0}^{(2)}$ | $W_{2i_1,2i_1,1}^{(2)}$ | $W_{2i_1+1,2i_1+1,0}^{(2)}$ | $W_{2i_1+1,2i_1+1,1}^{(2)}$ |
| i_1 | i_2 | | | |
| | 4 | 5 | 6 | 7 |
| 0 – 15 | $W_{2i_1+2,2i_1+2,0}^{(2)}$ | $W_{2i_1+2,2i_1+2,1}^{(2)}$ | $W_{2i_1+3,2i_1+3,0}^{(2)}$ | $W_{2i_1+3,2i_1+3,1}^{(2)}$ |
| i_1 | i_2 | | | |
| | 8 | 9 | 10 | 11 |
| 0 – 15 | $W_{2i_1,2i_1+1,0}^{(2)}$ | $W_{2i_1,2i_1+1,1}^{(2)}$ | $W_{2i_1+1,2i_1+2,0}^{(2)}$ | $W_{2i_1+1,2i_1+2,1}^{(2)}$ |
| i_1 | i_2 | | | |
| | 12 | 13 | 14 | 15 |
| 0 – 15 | $W_{2i_1,2i_1+3,0}^{(2)}$ | $W_{2i_1,2i_1+3,1}^{(2)}$ | $W_{2i_1+1,2i_1+3,0}^{(2)}$ | $W_{2i_1+1,2i_1+3,1}^{(2)}$ |
| where $W_{m,m',n}^{(2)} = \frac{1}{4} \begin{bmatrix} v_m & v_{m'} \\ \varphi_n v_m & -\varphi_n v_{m'} \end{bmatrix}$ | | | | |

Table 7.2.4-3: Codebook for 3-layer CSI reporting using antenna ports 15 to 22

| i_1 | i_2 | | | |
|--|-------------------------------------|--------------------------------------|--|---|
| | 0 | 1 | 2 | 3 |
| 0 - 3 | $W_{8i_1, 8i_1, 8i_1+8}^{(3)}$ | $W_{8i_1+8, 8i_1, 8i_1+8}^{(3)}$ | $\tilde{W}_{8i_1, 8i_1+8, 8i_1+8}^{(3)}$ | $\tilde{W}_{8i_1+8, 8i_1, 8i_1}^{(3)}$ |
| i_1 | i_2 | | | |
| | 4 | 5 | 6 | 7 |
| 0 - 3 | $W_{8i_1+2, 8i_1+2, 8i_1+10}^{(3)}$ | $W_{8i_1+10, 8i_1+2, 8i_1+10}^{(3)}$ | $\tilde{W}_{8i_1+2, 8i_1+10, 8i_1+10}^{(3)}$ | $\tilde{W}_{8i_1+10, 8i_1+2, 8i_1+2}^{(3)}$ |
| i_1 | i_2 | | | |
| | 8 | 9 | 10 | 11 |
| 0 - 3 | $W_{8i_1+4, 8i_1+4, 8i_1+12}^{(3)}$ | $W_{8i_1+12, 8i_1+4, 8i_1+12}^{(3)}$ | $\tilde{W}_{8i_1+4, 8i_1+12, 8i_1+12}^{(3)}$ | $\tilde{W}_{8i_1+12, 8i_1+4, 8i_1+4}^{(3)}$ |
| i_1 | i_2 | | | |
| | 12 | 13 | 14 | 15 |
| 0 - 3 | $W_{8i_1+6, 8i_1+6, 8i_1+14}^{(3)}$ | $W_{8i_1+14, 8i_1+6, 8i_1+14}^{(3)}$ | $\tilde{W}_{8i_1+6, 8i_1+14, 8i_1+14}^{(3)}$ | $\tilde{W}_{8i_1+14, 8i_1+6, 8i_1+6}^{(3)}$ |
| where $W_{m,m',m''}^{(3)} = \frac{1}{\sqrt{24}} \begin{bmatrix} v_m & v_{m'} & v_{m''} \\ v_m & -v_{m'} & -v_{m''} \end{bmatrix}$, $\tilde{W}_{m,m',m''}^{(3)} = \frac{1}{\sqrt{24}} \begin{bmatrix} v_m & v_{m'} & v_{m''} \\ v_m & v_{m'} & -v_{m''} \end{bmatrix}$ | | | | |

Table 7.2.4-4: Codebook for 4-layer CSI reporting using antenna ports 15 to 22

| i_1 | i_2 | | | |
|---|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| | 0 | 1 | 2 | 3 |
| 0 - 3 | $W_{8i_1, 8i_1+8, 0}^{(4)}$ | $W_{8i_1, 8i_1+8, 1}^{(4)}$ | $W_{8i_1+2, 8i_1+10, 0}^{(4)}$ | $W_{8i_1+2, 8i_1+10, 1}^{(4)}$ |
| i_1 | i_2 | | | |
| | 4 | 5 | 6 | 7 |
| 0 - 3 | $W_{8i_1+4, 8i_1+12, 0}^{(4)}$ | $W_{8i_1+4, 8i_1+12, 1}^{(4)}$ | $W_{8i_1+6, 8i_1+14, 0}^{(4)}$ | $W_{8i_1+6, 8i_1+14, 1}^{(4)}$ |
| where $W_{m,m',n}^{(4)} = \frac{1}{\sqrt{32}} \begin{bmatrix} v_m & v_{m'} & v_m & v_{m'} \\ \varphi_n v_m & \varphi_n v_{m'} & -\varphi_n v_m & -\varphi_n v_{m'} \end{bmatrix}$ | | | | |

Table 7.2.4-5: Codebook for 5-layer CSI reporting using antenna ports 15 to 22.

| i_1 | i_2 | | | | |
|-------|--|--|--|--|--|
| | 0 | | | | |
| 0 - 3 | $W_{i_1}^{(5)} = \frac{1}{\sqrt{40}} \begin{bmatrix} v_{2i_1} & v_{2i_1} & v_{2i_1+8} & v_{2i_1+8} & v_{2i_1+16} \\ v_{2i_1} & -v_{2i_1} & v_{2i_1+8} & -v_{2i_1+8} & v_{2i_1+16} \end{bmatrix}$ | | | | |

Table 7.2.4-6: Codebook for 6-layer CSI reporting using antenna ports 15 to 22.

| i_1 | i_2 | | | | | |
|-------|---|--|--|--|--|--|
| | 0 | | | | | |
| 0 - 3 | $W_{i_1}^{(6)} = \frac{1}{\sqrt{48}} \begin{bmatrix} v_{2i_1} & v_{2i_1} & v_{2i_1+8} & v_{2i_1+8} & v_{2i_1+16} & v_{2i_1+16} \\ v_{2i_1} & -v_{2i_1} & v_{2i_1+8} & -v_{2i_1+8} & v_{2i_1+16} & -v_{2i_1+16} \end{bmatrix}$ | | | | | |

Table 7.2.4-7: Codebook for 7-layer CSI reporting using antenna ports 15 to 22.

| i_1 | i_2 | | | | | | |
|-------|---|--|--|--|--|--|--|
| | 0 | | | | | | |
| 0 - 3 | $W_{i_1}^{(7)} = \frac{1}{\sqrt{56}} \begin{bmatrix} v_{2i_1} & v_{2i_1} & v_{2i_1+8} & v_{2i_1+8} & v_{2i_1+16} & v_{2i_1+16} & v_{2i_1+24} \\ v_{2i_1} & -v_{2i_1} & v_{2i_1+8} & -v_{2i_1+8} & v_{2i_1+16} & -v_{2i_1+16} & v_{2i_1+24} \end{bmatrix}$ | | | | | | |

Table 7.2.4-8: Codebook for 8-layer CSI reporting using antenna ports 15 to 22.

| i_1 | i_2 | | | | | | |
|-------|--|--|--|--|--|--|--|
| | 0 | | | | | | |
| 0 | $W_{i_1}^{(8)} = \frac{1}{8} \begin{bmatrix} v_{2i_1} & v_{2i_1} & v_{2i_1+8} & v_{2i_1+8} & v_{2i_1+16} & v_{2i_1+16} & v_{2i_1+24} & v_{2i_1+24} \\ v_{2i_1} & -v_{2i_1} & v_{2i_1+8} & -v_{2i_1+8} & v_{2i_1+16} & -v_{2i_1+16} & v_{2i_1+24} & -v_{2i_1+24} \end{bmatrix}$ | | | | | | |

7.2.5 Channel-State Information – Reference Signal (CSI-RS) definition

For a serving cell and UE configured in transmission mode 9, the UE can be configured with one CSI-RS resource configuration. For a serving cell and UE configured in transmission mode 10, the UE can be configured with one or more CSI-RS resource configuration(s). The following parameters for which the UE shall assume non-zero transmission power for CSI-RS are configured via higher layer signaling for each CSI-RS resource configuration:

- CSI-RS resource configuration identity, if the UE is configured in transmission mode 10,
- Number of CSI-RS ports. The allowable values and port mapping are given in subclause 6.10.5 of [3].
- CSI RS Configuration (see Table 6.10.5.2-1 and Table 6.10.5.2-2 in [3])
- CSI RS subframe configuration $I_{\text{CSI-RS}}$. The allowable values are given in subclause 6.10.5.3 of [3].
- UE assumption on reference PDSCH transmitted power for CSI feedback P_c , if the UE is configured in transmission mode 9.
- UE assumption on reference PDSCH transmitted power for CSI feedback P_c for each CSI process, if the UE is configured in transmission mode 10. If CSI subframe sets $C_{\text{CSI},0}$ and $C_{\text{CSI},1}$ are configured by higher layers for a CSI process, P_c is configured for each CSI subframe set of the CSI process.
- Pseudo-random sequence generator parameter, n_{ID} . The allowable values are given in [11].
- Higher layer parameter *qcl-CRS-Info-r11* for Quasi co-location type B UE assumption of CRS antenna ports and CSI-RS antenna ports with the following parameters, if the UE is configured in transmission mode 10:
 - *qcl-ScramblingIdentity-r11*.
 - *crs-PortsCount-r11*.
 - *mbsfn-SubframeConfigList-r11*.

P_c is the assumed ratio of PDSCH EPRE to CSI-RS EPRE when UE derives CSI feedback and takes values in the range of [-8, 15] dB with 1 dB step size, where the PDSCH EPRE corresponds to the symbols for which the ratio of the PDSCH EPRE to the cell-specific RS EPRE is denoted by ρ_A , as specified in Table 5.2-2 and Table 5.2-3.

A UE should not expect the configuration of CSI-RS and PMCH in the same subframe of a serving cell.

For frame structure type 2 serving cell and 4 CRS ports, the UE is not expected to receive a CSI RS Configuration index (see Table 6.10.5.2-1 and Table 6.10.5.2-2 in [3]) belonging to the set [20-31] for the normal CP case or the set [16-27] for the extended CP case.

A UE may assume the CSI-RS antenna ports of a CSI-RS resource configuration are quasi co-located (as defined in [3]) with respect to delay spread, Doppler spread, Doppler shift, average gain, and average delay.

A UE configured in transmission mode 10 and with quasi co-location type B, may assume the antenna ports 0 – 3 associated with *qcl-CRS-Info-r11* corresponding to a CSI-RS resource configuration and antenna ports 15 – 22 corresponding to the CSI-RS resource configuration are quasi co-located (as defined in [3]) with respect to Doppler shift, and Doppler spread.

7.2.6 Channel-State Information – Interference Measurement (CSI-IM) Resource definition

For a serving cell and UE configured in transmission mode 10, the UE can be configured with one or more CSI-IM resource configuration(s). The following parameters are configured via higher layer signaling for each CSI-IM resource configuration:

- Zero-power CSI RS Configuration (see Table 6.10.5.2-1 and Table 6.10.5.2-2 in [3])
- Zero-power CSI RS subframe configuration $I_{\text{CSI-RS}}$. The allowable values are given in subclause 6.10.5.3 of [3].

For a serving cell, if a UE is not configured with the higher layer parameter *csi-SubframePatternConfig-r12*, the UE is not expected to receive CSI-IM resource configuration(s) that are not all completely overlapping with one zero-power CSI-RS resource configuration which can be configured for the UE.

A UE is not expected to receive a CSI-IM resource configuration that is not completely overlapping with one of the zero-power CSI-RS resource configurations defined in subclause 7.2.7.

For a serving cell, if a UE is not configured with CSI subframe sets $C_{\text{CSI},0}$ and $C_{\text{CSI},1}$ for any CSI process, and the UE is configured with four CSI-IM resources, then the UE is not expected to be configured with CSI processes that are associated with all of the four CSI-IM resources.

A UE should not expect the configuration of CSI-IM resource and PMCH in the same subframe of a serving cell.

7.2.7 Zero Power CSI-RS Resource definition

For a serving cell and UE configured in transmission mode 1-9 and UE not configured with *csi-SubframePatternConfig-r12* for the serving cell, the UE can be configured with one zero-power CSI-RS resource configuration. For a serving cell and UE configured in transmission mode 1-9 and UE configured with *csi-SubframePatternConfig-r12* for the serving cell, the UE can be configured with up to two zero-power CSI-RS resource configurations. For a serving cell and UE configured in transmission mode 10, the UE can be configured with one or more zero-power CSI-RS resource configuration(s).

For a serving cell, the UE can be configured with up to 5 additional zero-power CSI-RS resource configurations according to the higher layer parameter *ds-ZeroTxPowerCSI-RS-r12*.

The following parameters are configured via higher layer signaling for each zero-power CSI-RS resource configuration:

- Zero-power CSI RS Configuration list (16-bit bitmap *ZeroPowerCSI-RS* in [3])
- Zero-power CSI RS subframe configuration $I_{\text{CSI-RS}}$. The allowable values are given in subclause 6.10.5.3 of [3].

A UE should not expect the configuration of zero-power CSI-RS and PMCH in the same subframe of a serving cell.

For frame structure type 1 serving cell, the UE is not expected to receive the 16-bit bitmap *ZeroPowerCSI-RS* with any one of the 6 LSB bits set to 1 for the normal CP case, or with any one of the 8 LSB bits set to 1 for the extended CP case.

For frame structure type 2 serving cell and 4 CRS ports, the UE is not expected to receive the 16-bit bitmap *ZeroPowerCSI-RS* with any one of the 6 LSB bits set to 1 for the normal CP case, or with any one of the 8 LSB bits set to 1 for the extended CP case.

7.3 UE procedure for reporting HARQ-ACK

If each of the serving cell(s) configured for the UE has frame structure type 1, the UE procedure for HARQ-ACK reporting for frame structure type 1 is given in subclause 7.3.1.

If each of the serving cell(s) configured for the UE has frame structure type 2, the UE procedure for HARQ-ACK reporting for frame structure type 2 is given in subclause 7.3.2.

If the UE is configured with more than one serving cell, and if the frame structure type of any two configured serving cells is different, and if the primary cell is frame structure type 1, UE procedure for HARQ-ACK reporting is given in subclause 7.3.3.

If the UE is configured for more than one serving cell, and if the frame structure type of any two configured serving cells is different, and if the primary cell is frame structure type 2, UE procedure for HARQ-ACK reporting is given in subclause 7.3.4.

7.3.1 FDD HARQ-ACK reporting procedure

For FDD with PUCCH format 1a/1b transmission, when both HARQ-ACK and SR are transmitted in the same sub-frame, a UE shall transmit the HARQ-ACK on its assigned HARQ-ACK PUCCH format 1a/1b resource for a negative SR transmission and transmit the HARQ-ACK on its assigned SR PUCCH resource for a positive SR transmission.

For FDD with PUCCH format 1b with channel selection, when both HARQ-ACK and SR are transmitted in the same sub-frame a UE shall transmit the HARQ-ACK on its assigned HARQ-ACK PUCCH resource with channel selection as defined in subclause 10.1.2.2.1 for a negative SR transmission and transmit one HARQ-ACK bit per serving cell on its assigned SR PUCCH resource for a positive SR transmission according to the following:

- if only one transport block or a PDCCH/EPDCCH indicating downlink SPS release is detected on a serving cell, the HARQ-ACK bit for the serving cell is the HARQ-ACK bit corresponding to the transport block or the PDCCH/EPDCCH indicating downlink SPS release;
- if two transport blocks are received on a serving cell, the HARQ-ACK bit for the serving cell is generated by spatially bundling the HARQ-ACK bits corresponding to the transport blocks;
- if neither PDSCH transmission for which HARQ-ACK response shall be provided nor PDCCH/EPDCCH indicating downlink SPS release is detected for a serving cell, the HARQ-ACK bit for the serving cell is set to NACK;

and the HARQ-ACK bits for the primary cell and the secondary cell are mapped to $b(0)$ and $b(1)$, respectively, where $b(0)$ and $b(1)$ are specified in subclause 5.4.1 in [3].

For FDD, when a PUCCH format 3 transmission of HARQ-ACK coincides with a sub-frame configured to the UE by higher layers for transmission of a scheduling request, the UE shall multiplex HARQ-ACK and SR bits on HARQ-ACK PUCCH resource as defined in subclause 5.2.3.1 in [4], unless the HARQ-ACK corresponds to a PDSCH transmission on the primary cell only or a PDCCH/EPDCCH indicating downlink SPS release on the primary cell only, in which case the SR shall be transmitted as for FDD with PUCCH format 1a/1b.

For FDD and for a PUSCH transmission, a UE shall not transmit HARQ-ACK on PUSCH in subframe n if the UE does not receive PDSCH or PDCCH indicating downlink SPS release in subframe $n-4$.

When only a positive SR is transmitted, a UE shall use PUCCH Format 1 for the SR resource as defined in subclause 5.4.1 in [3].

7.3.2 TDD HARQ-ACK reporting procedure

For TDD and a UE not configured with the parameter *EIMTA-MainConfigServCell-r12* for any serving cell, if the UE is configured with one serving cell, or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same, UE procedure for reporting HARQ-ACK is given in subclause 7.3.2.1.

For TDD, if a UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, UE procedure for reporting HARQ-ACK is given in subclause 7.3.2.2.

When only a positive SR is transmitted, a UE shall use PUCCH Format 1 for the SR resource as defined in subclause 5.4.1 in [3].

7.3.2.1 TDD HARQ-ACK reporting procedure for same UL/DL configuration

For TDD, the UE shall upon detection of a PDSCH transmission or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$ and K is defined in Table 10.1.3.1-1

intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in UL subframe n .

For TDD, when PUCCH format 3 is configured for transmission of HARQ-ACK, for special subframe configurations 0 and 5 with normal downlink CP or configurations 0 and 4 with extended downlink CP in a serving cell, shown in table 4.2-1 [3], the special subframe of the serving cell is excluded from the HARQ-ACK codebook size determination. In this case, if the serving cell is the primary cell, there is no PDCCH/EPDCCH indicating downlink SPS release in the special subframe.

For TDD UL/DL configurations 1-6 and one configured serving cell, if the UE is not configured with PUCCH format 3, the value of the Downlink Assignment Index (DAI) in DCI format 0/4, V_{DAI}^{UL} , detected by the UE according to Table 7.3-X in subframe $n - k'$, where k' is defined in Table 7.3-Y, represents the total number of subframes with PDSCH transmissions and with PDCCH/EPDCCH indicating downlink SPS release to the corresponding UE within all the subframe(s) $n - k$, where $k \in K$. The value V_{DAI}^{UL} includes all PDSCH transmission with and without corresponding PDCCH/EPDCCH within all the subframe(s) $n - k$. In case neither PDSCH transmission, nor PDCCH/EPDCCH indicating the downlink SPS resource release is intended to the UE, the UE can expect that the value of the DAI in DCI format 0/4, V_{DAI}^{UL} , if transmitted, is set to 4.

For TDD UL/DL configuration 1-6 and a UE configured with more than one serving cell, or for TDD UL/DL configuration 1-6 and a UE configured with one serving cell and PUCCH format 3, a value W_{DAI}^{UL} is determined by the Downlink Assignment Index (DAI) in DCI format 0/4 according to Table 7.3-Z in subframe $n - k'$, where k' is defined in Table 7.3-Y. In case neither PDSCH transmission, nor PDCCH/EPDCCH indicating the downlink SPS resource release is intended to the UE, the UE can expect that the value of W_{DAI}^{UL} is set to 4 by the DAI in DCI format 0/4 if transmitted.

For TDD UL/DL configurations 1-6, the value of the DAI in DCI format 1/1A/1B/1D/2/2A/2B/2C/2D denotes the accumulative number of PDCCH/EPDCCH (s) with assigned PDSCH transmission(s) and PDCCH/EPDCCH indicating downlink SPS release up to the present subframe within subframe(s) $n - k$ of each configured serving cell, where $k \in K$, and shall be updated from subframe to subframe. Denote $V_{DAI,c}^{DL}$ as the value of the DAI in PDCCH/EPDCCH with DCI format 1/1A/1B/1D/2/2A/2B/2C/2D detected by the UE according to Table 7.3-X in subframe $n - k_m$ in serving cell c , where k_m is the smallest value in the set K (defined in Table 10.1.3.1-1) such that the UE detects a DCI format 1/1A/1B/1D/2/2A/2B/2C/2D. When configured with one serving cell, the subscript of c in $V_{DAI,c}^{DL}$ can be omitted.

For all TDD UL/DL configurations, denote $U_{DAI,c}$ as the total number of PDCCH/EPDCCH (s) with assigned PDSCH transmission(s) and PDCCH/EPDCCH indicating downlink SPS release detected by the UE within the subframe(s) $n - k$ in serving cell c , where $k \in K$. When configured with one serving cell, the subscript of c in $U_{DAI,c}$ can be omitted. Denote N_{SPS} , which can be zero or one, as the number of PDSCH transmissions without a corresponding PDCCH/EPDCCH within the subframe(s) $n - k$, where $k \in K$.

For TDD HARQ-ACK bundling or HARQ-ACK multiplexing and a subframe n with $M = 1$, the UE shall generate one or two HARQ-ACK bits by performing a logical AND operation per codeword across M downlink and special subframes associated with a single UL subframe, of all the corresponding $U_{DAI} + N_{SPS}$ individual PDSCH transmission HARQ-ACKs and individual ACK in response to received PDCCH/EPDCCH indicating downlink SPS release, where M is the number of elements in the set K defined in Table 10.1.3.1-1. The UE shall detect if at least one downlink assignment has been missed, and for the case that the UE is transmitting on PUSCH the UE shall also determine the parameter N_{bundled} .

- For TDD UL/DL configuration 0, N_{bundled} shall be 1 if the UE detects the PDSCH transmission with or without corresponding PDCCH/EPDCCH, or detects PDCCH indicating downlink SPS release within the subframe $n - k$, where $k \in K$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH indicating downlink SPS release within the subframe(s) $n - k$, where $k \in K$.

- For the case that the UE is not transmitting on PUSCH in subframe n and TDD UL/DL configurations 1-6, if $U_{DAI} > 0$ and $V_{DAI}^{DL} \neq (U_{DAI} - 1) \bmod 4 + 1$, the UE detects that at least one downlink assignment has been missed.
- For the case that the UE is transmitting on PUSCH and the PUSCH transmission is adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 intended for the UE and TDD UL/DL configurations 1-6, if $V_{DAI}^{UL} \neq (U_{DAI} + N_{SPS} - 1) \bmod 4 + 1$ the UE detects that at least one downlink assignment has been missed and the UE shall generate NACK for all codewords where N_{bundled} is determined by the UE as $N_{\text{bundled}} = V_{DAI}^{UL} + 2$. If the UE does not detect any downlink assignment missing, N_{bundled} is determined by the UE as $N_{\text{bundled}} = V_{DAI}^{UL}$. UE shall not transmit HARQ-ACK if $U_{DAI} + N_{SPS} = 0$ and $V_{DAI}^{UL} = 4$.
- For the case that the UE is transmitting on PUSCH, and the PUSCH transmission is not based on a detected PDCCH/EPDCCH with DCI format 0/4 intended for the UE and TDD UL/DL configurations 1-6, if $U_{DAI} > 0$ and $V_{DAI}^{DL} \neq (U_{DAI} - 1) \bmod 4 + 1$, the UE detects that at least one downlink assignment has been missed and the UE shall generate NACK for all codewords. The UE determines $N_{\text{bundled}} = (U_{DAI} + N_{SPS})$ as the number of assigned subframes. The UE shall not transmit HARQ-ACK if $U_{DAI} + N_{SPS} = 0$.

For TDD, when PUCCH format 3 is configured for transmission of HARQ-ACK, the HARQ-ACK feedback bits

$o_{c,0}^{ACK}, o_{c,1}^{ACK}, \dots, o_{c,O_c^{ACK}-1}^{ACK}$ for the c -th serving cell configured by RRC are constructed as follows, where $c \geq 0$,

$O_c^{ACK} = B_c^{DL}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied and $O_c^{ACK} = 2B_c^{DL}$ otherwise, where B_c^{DL} is the number of downlink and special subframes for which the UE needs to feedback HARQ-ACK bits for the c -th serving cell.

- For the case that the UE is transmitting on PUCCH, $B_c^{DL} = M$ where M is the number of elements in the set K defined in Table 10.1.3.1-1 associated with subframe n and the set K does not include a special subframe of configurations 0 and 5 with normal downlink CP or of configurations 0 and 4 with extended downlink CP; otherwise $B_c^{DL} = M - 1$.
- For TDD UL/DL configuration 0 or for a PUSCH transmission not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, the UE shall assume $B_c^{DL} = M$ where M is the number of elements in the set K defined in Table 10.1.3.1-1 associated with subframe n and the set K does not include a special subframe of configurations 0 and 5 with normal downlink CP or of configurations 0 and 4 with extended downlink CP; otherwise $B_c^{DL} = M - 1$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$, where $k \in K$.
- For TDD UL/DL configurations {1, 2, 3, 4, 6} and a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, the UE shall assume $B_c^{DL} = W_{DAI}^{UL}$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.
- For TDD UL/DL configurations 5 and a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, the UE shall assume $B_c^{DL} = W_{DAI}^{UL} + 4 \left\lceil \frac{U - W_{DAI}^{UL}}{4} \right\rceil$, where U denotes the maximum value of U_c among all the configured serving cells, U_c is the total number of received PDSCHs and PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ on the c -th serving cell, $k \in K$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.

For TDD, when PUCCH format 3 is configured for transmission of HARQ-ACK,

- for TDD UL/DL configurations 1-6, the HARQ-ACK for a PDSCH transmission with a corresponding PDCCH/EPDCCH or for a PDCCH/EPDCCH indicating downlink SPS release in subframe $n - k$ is associated with $o_{c,DAI(k)-1}^{ACK}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied, or associated with $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ otherwise, where $DAI(k)$ is the value of DAI in DCI format 1A/1B/1D/1/2/2A/2B/2C/2D detected in subframe $n - k$, $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ are the HARQ-ACK feedback for codeword 0 and codeword 1, respectively. For the case with $N_{SPS} > 0$, the HARQ-ACK associated with a PDSCH transmission without a corresponding PDCCH/EPDCCH is mapped to $o_{c,O_c^{ACK}-1}^{ACK}$. The HARQ-ACK feedback bits without any detected PDSCH transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK;
- for TDD UL/DL configuration 0, the HARQ-ACK for a PDSCH transmission or for a PDCCH/EPDCCH indicating downlink SPS release in subframe $n - k$ is associated with $o_{c,0}^{ACK}$ if transmission mode configured in the c -th serving cell supports one transport block or associated with $o_{c,0}^{ACK}$ and $o_{c,1}^{ACK}$ otherwise, where $o_{c,0}^{ACK}$ and $o_{c,1}^{ACK}$ are the HARQ-ACK feedback for codeword 0 and codeword 1, respectively. The HARQ-ACK feedback bits without any detected PDSCH transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK.

For TDD when format 1b with channel selection is configured for transmission of HARQ-ACK and for 2 configured serving cells, the HARQ-ACK feedback bits $o_0^{ACK}, o_1^{ACK}, \dots, o_{O_c^{ACK}-1}^{ACK}$ on PUSCH are constructed as follows.

- For TDD UL/DL configuration 0, $o_j^{ACK} = \text{HARQ-ACK}(j)$, $0 \leq j \leq A-1$ as defined in subclause 10.1.3.2.1. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n - k$ where $k \in K$.
- For TDD UL/DL configurations {1, 2, 3, 4, 6} and a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 with $W_{DAI}^{UL} = 1$ or 2, o_j^{ACK} is determined as if PUCCH format 3 is configured for transmission of HARQ-ACK, except that spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed for all serving cells configured with a downlink transmission mode that supports up to two transport blocks in case $W_{DAI}^{UL} = 2$.
- For TDD UL/DL configurations {1, 2, 3, 4, 6} and a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 with $W_{DAI}^{UL} = 3$ or 4, $o_j^{ACK} = o(j)$, $0 \leq j \leq 3$ as defined in Table 10.1.3.2-5 or in Table 10.1.3.2-6 respectively, where the value of M is replaced by W_{DAI}^{UL} . The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n - k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.
- For TDD UL/DL configurations {1, 2, 3, 4, 6} and a PUSCH transmission not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 and a subframe n with $M = 1$ or 2, $o_j^{ACK} = \text{HARQ-ACK}(j)$, $0 \leq j \leq A-1$ as defined in subclause 10.1.3.2.1. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n - k$ where $k \in K$.
- For TDD UL/DL configurations {1, 2, 3, 4, 6} and a PUSCH transmission not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 and a subframe n with $M = 3$ or 4, $o_j^{ACK} = o(j)$, $0 \leq j \leq 3$ as defined in Table 10.1.3.2-5 or in Table 10.1.3.2-6 respectively. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n - k$ where $k \in K$.

For TDD HARQ-ACK bundling, when the UE is configured by transmission mode 3, 4, 8, 9 or 10 defined in subclause 7.1 and HARQ-ACK bits are transmitted on PUSCH, the UE shall always generate 2 HARQ-ACK bits assuming both codeword 0 and 1 are enabled. For the case that the UE detects only the PDSCH transmission associated with codeword 0 within the bundled subframes, the UE shall generate NACK for codeword 1.

Table 7.3-X: Value of Downlink Assignment Index

| DAI MSB, LSB | V_{DAI}^{UL} or V_{DAI}^{DL} | Number of subframes with PDSCH transmission and with PDCCH/EPDCCH indicating DL SPS release |
|--------------|----------------------------------|---|
| 0,0 | 1 | 1 or 5 or 9 |
| 0,1 | 2 | 2 or 6 or 10 |
| 1,0 | 3 | 3 or 7 |
| 1,1 | 4 | 0 or 4 or 8 |

Table 7.3-Y: Uplink association index k' for TDD

| TDD UL/DL Configuration | subframe number n | | | | | | | | | |
|-------------------------|---------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 1 | | | 6 | 4 | | | | 6 | 4 | |
| 2 | | | 4 | | | | | 4 | | |
| 3 | | | 4 | 4 | 4 | | | | | |
| 4 | | | 4 | 4 | | | | | | |
| 5 | | | 4 | | | | | | | |
| 6 | | | 7 | 7 | 5 | | | 7 | 7 | |

Table 7.3-Z: Value of W_{DAI}^{UL} determined by the DAI field in DCI format 0/4

| DAI MSB, LSB | W_{DAI}^{UL} |
|--------------|----------------|
| 0,0 | 1 |
| 0,1 | 2 |
| 1,0 | 3 |
| 1,1 | 4 |

For TDD HARQ-ACK multiplexing and a subframe n with $M > 1$, spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed by a logical AND operation of all the corresponding individual HARQ-ACKs. In case the UE is transmitting on PUSCH, the UE shall determine the number of HARQ-ACK feedback bits O^{ACK} and the HARQ-ACK feedback bits o_n^{ACK} , $n = 0, \dots, O^{ACK} - 1$ to be transmitted in subframe n .

- If the PUSCH transmission is adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 intended for the UE, then $O^{ACK} = V_{DAI}^{UL}$ unless $V_{DAI}^{UL} = 4$ and $U_{DAI} + N_{SPS} = 0$ in which case the UE shall not transmit HARQ-ACK. The spatially bundled HARQ-ACK for a PDSCH transmission with a corresponding PDCCH/EPDCCH or for a PDCCH/EPDCCH indicating downlink SPS release in subframe $n - k$ is associated with $o_{DAI(k)-1}^{ACK}$ where $DAI(k)$ is the value of DAI in DCI format 1A/1B/1D/1/2/2A/2B/2C/2D detected in subframe $n - k$. For the case with $N_{SPS} > 0$, the HARQ-ACK associated with a PDSCH transmission without a corresponding PDCCH/EPDCCH is mapped to $o_{O^{ACK}-1}^{ACK}$. The HARQ-ACK feedback bits without any detected PDSCH transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK.
- If the PUSCH transmission is not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 intended for the UE, $O^{ACK} = M$, and o_i^{ACK} is associated with the spatially bundled HARQ-ACK for downlink or special subframe $n - k_i$, where $k_i \in K$. The HARQ-ACK feedback bits without any detected PDSCH

transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK. The UE shall not transmit HARQ-ACK if $U_{DAI} + N_{SPS} = 0$.

For TDD when a PUCCH format 3 transmission of HARQ-ACK coincides with a sub-frame configured to the UE by higher layers for transmission of a scheduling request, the UE shall multiplex HARQ-ACK and SR bits on HARQ-ACK PUCCH resource as defined in subclause 5.2.3.1 in [4], unless the HARQ-ACK corresponds to one of the following cases

- a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n - k_m$, where $k_m \in K$, and for TDD UL/DL configurations 1-6 the DAI value in the PDCCH/EPDCCH is equal to '1' (defined in Table 7.3-X), or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$, and for TDD UL/DL configurations 1-6 the DAI value in the PDCCH/EPDCCH is equal to '1', or
- a single PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n - k$, where $k \in K$ and no PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n - k$, where $k \in K$, or
- a PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n - k$, where $k \in K$ and an additional PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH/EPDCCH equal to '1' (defined in Table 7.3-X) or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in the subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH/EPDCCH equal to '1',

in which case the UE shall transmit the HARQ-ACK and scheduling request according to the procedure for PUCCH format 1b with channel selection in TDD.

For TDD when the UE is configured with HARQ-ACK bundling, HARQ-ACK multiplexing or PUCCH format 1b with channel selection, and when both HARQ-ACK and SR are transmitted in the same sub-frame, a UE shall transmit the bundled HARQ-ACK or the multiple HARQ-ACK responses (according to subclause 10.1) on its assigned HARQ-ACK PUCCH resources for a negative SR transmission. For a positive SR, the UE shall transmit $b(0), b(1)$ on its assigned SR PUCCH resource using PUCCH format 1b according to subclause 5.4.1 in [3]. The value of $b(0), b(1)$ are

generated according to Table 7.3-1 from the $N_{SPS} + \sum_{c=0}^{N_{cells}^{DL} - 1} U_{DAI,c}$ HARQ-ACK responses including ACK in response to PDCCH/EPDCCH indicating downlink SPS release by spatial HARQ-ACK bundling across multiple codewords

within each PDSCH transmission for all serving cells N_{cells}^{DL} . For TDD UL/DL configurations 1-6, if $\sum_{c=0}^{N_{cells}^{DL} - 1} U_{DAI,c} > 0$

and $V_{DAI,c}^{DL} \neq (U_{DAI,c} - 1) \bmod 4 + 1$ for a serving cell c , the UE detects that at least one downlink assignment has been missed.

Table 7.3-1: Mapping between multiple HARQ-ACK responses and $b(0), b(1)$

| Number of ACK among multiple ($N_{SPS} + \sum_{c=0}^{N_{cells}^{DL}-1} U_{DAI,c}$) HARQ-ACK responses | $b(0), b(1)$ |
|---|--------------|
| 0 or None (UE detect at least one DL assignment is missed) | 0, 0 |
| 1 | 1, 1 |
| 2 | 1, 0 |
| 3 | 0, 1 |
| 4 | 1, 1 |
| 5 | 1, 0 |
| 6 | 0, 1 |
| 7 | 1, 1 |
| 8 | 1, 0 |
| 9 | 0, 1 |

For TDD if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE*, and if the UE is configured with HARQ-ACK bundling, HARQ-ACK multiplexing or PUCCH format 1b with channel selection, and if the UE receives PDSCH and/or PDCCH/EPDCCH indicating downlink SPS release only on the primary cell within subframe(s) $n-k$, where $k \in K$, a UE shall transmit the CSI and $b(0), b(1)$ using PUCCH format 2b for normal CP or PUCCH format 2 for extended CP, according to subclause 5.2.3.4 in [4] with a_0'', a_1'' replaced by $b(0), b(1)$. The

value of $b(0), b(1)$ are generated according to Table 7.3-1 from the $N_{SPS} + \sum_{c=0}^{N_{cells}^{DL}-1} U_{DAI,c}$ HARQ-ACK responses including ACK in response to PDCCH/EPDCCH indicating downlink SPS release by spatial HARQ-ACK bundling across multiple codewords within each PDSCH transmission for all serving cells N_{cells}^{DL} . For TDD UL/DL

configurations 1-6, if $\sum_{c=0}^{N_{cells}^{DL}-1} U_{DAI,c} > 0$ and $V_{DAI,c}^{DL} \neq (U_{DAI,c} - 1) \bmod 4 + 1$ for a serving cell c , the UE detects that at least one downlink assignment has been missed.

For TDD if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE*, and if the UE is configured with PUCCH format 1b with channel selection and receives at least one PDSCH on the secondary cell within subframe(s) $n-k$, where $k \in K$, the UE shall drop the CSI and transmit HARQ-ACK according to subclause 10.1.3.

For TDD and a UE is configured with PUCCH format 3,

if the parameter *simultaneousAckNackAndCQI* is set *TRUE* and if the UE receives,

- a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n-k_m$, where $k_m \in K$, and for TDD UL/DL configurations 1-6 the DAI value in the PDCCH/EPDCCH is equal to '1' (defined in Table 7.3-X), or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$, and for TDD UL/DL configurations 1-6 the DAI value in the PDCCH/EPDCCH is equal to '1', or
- a single PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n-k$, where $k \in K$ and no PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$,

then the UE shall transmit the CSI and HARQ-ACK using PUCCH format 2/2a/2b according to subclause 5.2.3.4 in [4]; else if

- the parameter *simultaneousAckNackAndCQI-Format3-r11* is set *TRUE* and if PUCCH format 3 resource is determined according to subclause 10.1.3.1 or subclause 10.1.3.2.2 and
 - o if the total number of bits in the subframe corresponding to HARQ-ACKs, SR (if any), and the CSI is not larger than 22, or

- if the total number of bits in the subframe corresponding to spatially bundled HARQ-ACKs, SR (if any), and the CSI is not larger than 22

then the UE shall transmit the HARQ-ACKs, SR (if any) and the CSI using the determined PUCCH format 3 resource according to [4];

else,

the UE shall drop the CSI and transmit the HARQ-ACK according to subclause 10.1.3.

7.3.2.2 TDD HARQ-ACK reporting procedure for different UL/DL configurations

For a configured serving cell, the DL-reference UL/DL configuration as defined in subclause 10.2 is referred to as the "DL-reference UL/DL configuration" in the rest of this subclause.

For a configured serving cell, if the DL-reference UL/DL configuration is 0, then the DAI in DCI format 1/1A/1B/1D/2/2A/2B/2C/2D is not used.

The UE shall upon detection of a PDSCH transmission or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$ for serving cell c , where $k \in K_c$ intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in UL subframe n , wherein set K_c contains values of $k \in K$ such that subframe $n-k$ corresponds to a downlink subframe or a special subframe for serving cell c , where DL subframe or special subframe of serving cell c is according to the higher layer parameter *eimta-HARQ-ReferenceConfig-r12* if the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* for serving cell c ; K defined in Table 10.1.3.1-1 (where "UL/DL configuration" in Table 10.1.3.1-1 refers to the DL-reference UL/DL configuration) is associated with subframe n . M_c is the number of elements in set K_c associated with subframe n for serving cell c .

For the remainder of this subclause $K = K_c$.

If the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for the primary cell, "UL/DL configuration of the primary cell" in the rest of this subclause refers to "DL-reference UL/DL configuration of the primary cell".

When PUCCH format 3 is configured for transmission of HARQ-ACK, for special subframe configurations 0 and 5 with normal downlink CP or configurations 0 and 4 with extended downlink CP in a serving cell, shown in table 4.2-1 [3], the special subframe of the serving cell is excluded from the HARQ-ACK codebook size determination. In this case, if the serving cell is the primary cell, there is no PDCCH/EPDCCH indicating downlink SPS release in the special subframe.

If the UL-reference UL/DL configuration (defined in Sec 8.0) belongs to {1,2,3,4,5,6} for a serving cell, a value W_{DAI}^{UL} is determined by the Downlink Assignment Index (DAI) in DCI format 0/4 corresponding to a PUSCH on the serving cell according to Table 7.3-Z in subframe $n-k'$, where k' is defined in Table 7.3-Y and the "TDD UL/DL Configuration" in Table 7.3-Y refers to the UL-reference UL/DL configuration (defined in subclause 8.0) for the serving cell. In case neither PDSCH transmission, nor PDCCH/EPDCCH indicating the downlink SPS resource release is intended to the UE, the UE can expect that the value of W_{DAI}^{UL} is set to 4 by the DAI in DCI format 0/4 if transmitted.

If the DL-reference UL/DL configuration belongs to {1,2,3,4,5,6}, the value of the DAI in DCI format 1/1A/1B/1D/2/2A/2B/2C/2D denotes the accumulative number of PDCCH/EPDCCH (s) with assigned PDSCH transmission(s) and PDCCH/EPDCCH indicating downlink SPS release up to the present subframe within subframe(s) $n-k$ of each configured serving cell, where $k \in K$, and shall be updated from subframe to subframe. Denote $V_{DAI,c}^{DL}$ as the value of the DAI in PDCCH/EPDCCH with DCI format 1/1A/1B/1D/2/2A/2B/2C/2D detected by the UE according to Table 7.3-X in subframe $n-k_m$ in serving cell c , where k_m is the smallest value in the set K such that the UE detects a DCI format 1/1A/1B/1D/2/2A/2B/2C/2D.

For all TDD UL/DL configurations, denote $U_{DAI,c}$ as the total number of PDCCH/EPDCCH (s) with assigned PDSCH transmission(s) and PDCCH/EPDCCH indicating downlink SPS release detected by the UE within the subframe(s) $n-k$ in serving cell c , where $k \in K$. Denote N_{SPS} , which can be zero or one, as the number of PDSCH transmissions without a corresponding PDCCH/EPDCCH within the subframe(s) $n-k$, where $k \in K$.

If PUCCH format 3 is configured for transmission of HARQ-ACK, the HARQ-ACK feedback bits

$o_{c,0}^{ACK}, o_{c,1}^{ACK}, \dots, o_{c,O_c^{ACK}-1}^{ACK}$ for the c -th serving cell configured by RRC are constructed as follows, where $c \geq 0$,

$O_c^{ACK} = B_c^{DL}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied and $O_c^{ACK} = 2B_c^{DL}$ otherwise, where B_c^{DL} is the number of downlink and special subframes for which the UE needs to feedback HARQ-ACK bits for the c -th serving cell.

- For the case that the UE is transmitting in subframe n on PUCCH or a PUSCH transmission not adjusted based on a detected DCI format 0/4 or a PUSCH transmission adjusted based on an associated detected DCI format 0/4 with UL-reference UL/DL configuration 0 (defined in Sec 8.0), then $B_c^{DL} = M_c$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$, where $k \in K$.
- If DL-reference UL/DL configuration of each of the configured serving cells belongs to $\{0, 1, 2, 3, 4, 6\}$ and for a PUSCH transmission in a subframe n adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 using UL-reference UL/DL configuration belonging to $\{1,2,3,4,5,6\}$ (defined in Sec 8.0), the UE shall assume $B_c^{DL} = \min(W_{DAI}^{UL}, M_c)$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.
- If DL-reference UL/DL configuration of at least one configured serving cell belongs to $\{5\}$ and for a PUSCH transmission adjusted based on an associated detected PDCCH/EPDCCH with DCI format 0/4 using UL-reference UL/DL configuration belonging to $\{1,2,3,4,5,6\}$ (defined in Sec 8.0), the UE shall assume $B_c^{DL} = \min(W_{DAI}^{UL} + 4 \lfloor (U - W_{DAI}^{UL})/4 \rfloor, M_c)$, where U denotes the maximum value of U_c among all the configured serving cells, U_c is the total number of received PDSCHs and PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ for the c -th serving cell, $k \in K$. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.

When PUCCH format 3 is configured for transmission of HARQ-ACK,

- if DL-reference UL/DL configuration belongs to $\{1,2,3,4,5,6\}$, the HARQ-ACK for a PDSCH transmission with a corresponding PDCCH/EPDCCH or for a PDCCH/EPDCCH indicating downlink SPS release in subframe $n-k$ is associated with $o_{c,DAI(k)-1}^{ACK}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied, or associated with $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ otherwise, where $DAI(k)$ is the value of DAI in DCI format 1A/1B/1D/1/2/2A/2B/2C/2D detected in subframe $n-k$, $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ are the HARQ-ACK feedback for codeword 0 and codeword 1, respectively. For the case with $N_{SPS} > 0$, the HARQ-ACK associated with a PDSCH transmission without a corresponding PDCCH/EPDCCH is mapped to $o_{c,O_c^{ACK}-1}^{ACK}$. The HARQ-ACK feedback bits without any detected PDSCH transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK;
- if DL-reference UL/DL configuration is 0, the HARQ-ACK for a PDSCH transmission or for a PDCCH/EPDCCH indicating downlink SPS release in subframe $n-k$ is associated with $o_{c,0}^{ACK}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied, or associated with $o_{c,0}^{ACK}$ and $o_{c,1}^{ACK}$ otherwise, where $o_{c,0}^{ACK}$ and $o_{c,1}^{ACK}$ are the HARQ-ACK feedback for codeword 0 and codeword 1, respectively. The HARQ-ACK feedback bits without any detected PDSCH transmission or without detected PDCCH/EPDCCH indicating downlink SPS release are set to NACK.

If DL-reference UL/DL configuration of each of the serving cells belongs to $\{0,1,2,3,4,6\}$ and if PUCCH format 1b with channel selection is configured for transmission of HARQ-ACK and for two configured serving cells, the HARQ-ACK feedback bits $o_0^{ACK}, o_1^{ACK}, \dots, o_{ACK-1}^{ACK}$ on PUSCH are constructed as follows

- if UL-reference UL/DL configuration (defined in Sec 8.0) belongs to $\{1, 2, 3, 4, 6\}$, for a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 with $W_{DAI}^{UL}=1$ or 2, o_j^{ACK} is determined as if PUCCH format 3 is configured for transmission of HARQ-ACK, except that spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed for all serving cells configured with a downlink transmission mode that supports up to two transport blocks in case $W_{DAI}^{UL}=2$, where the UL-reference UL/DL configuration is the UL-reference UL/DL configuration of the serving cell corresponding to the PUSCH transmission.
- if UL-reference UL/DL configuration (defined in Sec 8.0) belongs to $\{1, 2, 3, 4, 6\}$, for a PUSCH transmission adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4 with $W_{DAI}^{UL}=3$ or 4, $o_j^{ACK} = o(j)$, $0 \leq j \leq 3$ as defined in Table 10.1.3.2-5 or in Table 10.1.3.2-6 respectively, where the value of M is replaced by W_{DAI}^{UL} where the UL-reference UL/DL configuration is the UL-reference UL/DL configuration of the serving cell corresponding to the PUSCH transmission. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$ and $W_{DAI}^{UL} = 4$.
- if UL-reference UL/DL configuration (defined in Sec 8.0) is 0, or if UL-reference UL/DL configuration (defined in Sec 8.0) belongs to $\{1, 2, 3, 4, 6\}$, for a PUSCH transmission not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, for a subframe n with $M=1$ or 2 (M defined in Sec 10.1.3.2.1), $o_j^{ACK} = \text{HARQ-ACK}(j)$, $0 \leq j \leq A-1$ as defined in subclause 10.1.3.2.1, where the UL-reference UL/DL configuration is the UL-reference UL/DL configuration of the serving cell corresponding to the PUSCH transmission. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$.
- if UL-reference UL/DL configuration (defined in Sec 8.0) is 0, or if UL-reference UL/DL configuration (defined in Sec 8.0) belongs to $\{1, 2, 3, 4, 6\}$ and, for a PUSCH transmission not adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, for a subframe n with $M=3$ or 4 (M defined in Sec 10.1.3.2.1), $o_j^{ACK} = o(j)$, $0 \leq j \leq 3$ as defined in Table 10.1.3.2-5 or in Table 10.1.3.2-6 respectively, where the UL-reference UL/DL configuration is the UL-reference UL/DL configuration of the serving cell corresponding to the PUSCH transmission. The UE shall not transmit HARQ-ACK on PUSCH if the UE does not receive PDSCH or PDCCH/EPDCCH indicating downlink SPS release in subframe(s) $n-k$ where $k \in K$.

When a PUCCH format 3 transmission of HARQ-ACK coincides with a sub-frame configured to the UE by higher layers for transmission of a scheduling request, the UE shall multiplex HARQ-ACK and SR bits on HARQ-ACK PUCCH resource as defined in subclause 5.2.3.1 in [4], unless the HARQ-ACK corresponds to one of the following cases

- a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n-k_m$, where $k_m \in K$, and for UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$, the DAI value in the PDCCH/EPDCCH is equal to '1' (defined in Table 7.3-X), or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$, and for UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$ the DAI value in the PDCCH/EPDCCH is equal to '1', or
- a single PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n-k$, where $k \in K$ and no PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, or
- a PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n-k$, where $k \in K$ and an additional PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n-k_m$, where $k_m \in K$ with the

DAI value in the PDCCH/EPDCCH equal to '1' (defined in Table 7.3-X) or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in the subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH/EPDCCH equal to '1',

in which case the UE shall transmit the HARQ-ACK and scheduling request according to the procedure for PUCCH format 1b with channel selection in TDD.

If the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE*, and if the UE is configured with PUCCH format 1b with channel selection, and if the UE receives PDSCH and/or PDCCH/EPDCCH indicating downlink SPS release only on the primary cell within subframe(s) $n - k$, where $k \in K$, a UE shall transmit the CSI and $b(0), b(1)$ using PUCCH format 2b for normal CP or PUCCH format 2 for extended CP, according to subclause 5.2.3.4 in [4] with a_0'', a_1'' replaced by $b(0), b(1)$. The value of $b(0), b(1)$ are generated according to Table 7.3-1 from

the $N_{SPS} + \sum_{c=0}^{N_{cells}^{DL} - 1} U_{DAI,c}$ HARQ-ACK responses including ACK in response to PDCCH/EPDCCH indicating downlink SPS release by spatial HARQ-ACK bundling across multiple codewords within each PDSCH transmission for

all serving cells N_{cells}^{DL} . If DL-reference UL/DL configuration belongs to $\{1,2,3,4,5,6\}$ and, if $\sum_{c=0}^{N_{cells}^{DL} - 1} U_{DAI,c} > 0$ and

$V_{DAI,c}^{DL} \neq (U_{DAI,c} - 1) \bmod 4 + 1$ for a serving cell c , the UE detects that at least one downlink assignment has been missed.

If the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE*, and if the UE is configured with PUCCH format 1b with channel selection and receives at least one PDSCH on the secondary cell within subframe(s) $n - k$, where $k \in K$, the UE shall drop the CSI and transmit HARQ-ACK according to subclause 10.1.3.

When both HARQ-ACK and CSI are configured to be transmitted in the same sub-frame and if a UE is configured with PUCCH format 3,

if the parameter *simultaneousAckNackAndCQI* is set *TRUE* and if the UE receives

- a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n - k_m$, where $k_m \in K$, and for UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$ the DAI value in the PDCCH/EPDCCH is equal to '1' (defined in Table 7.3-X), or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$, and for UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$ the DAI value in the PDCCH/EPDCCH is equal to '1', or
- a single PDSCH transmission only on the primary cell where there is not a corresponding PDCCH detected within subframe(s) $n - k$, where $k \in K$ and no PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n - k$, where $k \in K$,

then the UE shall transmit the CSI and HARQ-ACK using PUCCH format 2/2a/2b according to subclause 5.2.3.4 in [4];

else if

- the parameter *simultaneousAckNackAndCQI-Format3-r11* is set *TRUE* and if PUCCH format 3 resource is determined according to subclause 10.1.3.1 or subclause 10.1.3.2.2 and
 - o if the total number of bits in the subframe corresponding to HARQ-ACKs, SR (if any), and the CSI is not larger than 22, or
 - o if the total number of bits in the subframe corresponding to spatially bundled HARQ-ACKs, SR (if any), and the CSI is not larger than 22

then the UE shall transmit the HARQ-ACKs, SR (if any) and the CSI using the determined PUCCH format 3 resource according to [4];

else,

the UE shall drop the CSI and transmit the HARQ-ACK according to subclause 10.1.3.

7.3.3 FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 1

For FDD-TDD and the primary cell is frame structure type 1, with PUCCH format 1b with channel selection,

- for a negative SR transmission,
 - UE shall transmit the HARQ-ACK on its assigned HARQ-ACK PUCCH resource with channel selection as defined in subclause 10.1.2A.
- for a positive SR transmission,
 - if one transport block or two transport blocks or a PDCCH/EPDCCH indicating downlink SPS release is detected on the primary cell in subframe i , and if subframe i is an uplink or a special subframe of configurations 0 and 5 with normal downlink CP or of configurations 0 and 4 with extended downlink CP for the secondary cell according to the higher layer parameter *subframeAssignment* for UE not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* and according to the higher layer parameter *eimta-HARQ-ReferenceConfig-r12* for UE configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*,
 - UE shall transmit the HARQ-ACK and SR as for FDD with PUCCH format 1a/1b as described in subclause 7.3.1.
 - otherwise
 - UE shall transmit the HARQ-ACK and SR as for FDD with PUCCH format 1b with channel selection as described in subclause 7.3.1.

For FDD-TDD and the primary cell is frame structure type 1, when PUCCH format 3 is configured for transmission of HARQ-ACK, for special subframe configurations 0 and 5 with normal downlink CP or configurations 0 and 4 with extended downlink CP in a serving cell, shown in table 4.2-1 [3], the special subframe of the serving cell is excluded from the HARQ-ACK codebook size determination.

For FDD-TDD and the primary cell is frame structure type 1, when a PUCCH format 3 transmission of HARQ-ACK coincides with a sub-frame configured to the UE by higher layers for transmission of a scheduling request, the UE shall multiplex HARQ-ACK and SR bits on HARQ-ACK PUCCH resource as defined in subclause 5.2.3.1 in [4], unless the HARQ-ACK corresponds to a PDSCH transmission on the primary cell only or a PDCCH/EPDCCH indicating downlink SPS release on the primary cell only, in which case the SR shall be transmitted as for FDD with PUCCH format 1a/1b as described in subclause 7.3.1.

For FDD-TDD and for a PUSCH transmission, a UE shall not transmit HARQ-ACK on PUSCH in subframe n if the UE does not receive PDSCH or PDCCH indicating downlink SPS release in subframe $n-4$.

When only a positive SR is transmitted, a UE shall use PUCCH Format 1 for the SR resource as defined in subclause 5.4.1 in [3].

7.3.4 FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 2

When only a positive SR is transmitted, a UE shall use PUCCH Format 1 for the SR resource as defined in subclause 5.4.1 in [3].

The FDD-TDD HARQ-ACK reporting procedure follows the HARQ-ACK procedure described in subclause 7.3.2.2 with the following exceptions:

- for a serving cell with frame structure type 1, and a UE not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, K is defined in Table 10.1.3A-1, otherwise K is defined in Table 10.1.3.1-1.
- for a serving cell with frame structure type 1 and a UE not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, if the DL-reference UL/DL configuration of the serving cell in Table 10.1.3A-1 belongs to {2,3,4}, B_c^{DL} is determined as in subclause 7.3.2.2 for a serving cell with DL-reference UL/DL configuration {5}.

- for a serving cell with frame structure type 1, and if PUCCH format 3 is configured for transmission of HARQ-ACK, and for a PUSCH transmission in a subframe n adjusted based on a detected PDCCH/EPDCCH with DCI format 0/4, the UE shall assume the UL-reference UL/DL configuration of the serving cell belongs to $\{1,2,3,4,5,6\}$.
- for a serving cell with frame structure type 1, and if DL-reference UL/DL configuration of each of the serving cells belongs to $\{0,1,2,3,4,6\}$, and if PUCCH format 1b with channel selection is configured for transmission of HARQ-ACK and for two configured serving cells, the UE shall assume the UL-reference UL/DL configuration of the serving cell belongs to $\{1,2,3,4,6\}$.
- for a serving cell with frame structure type 1, a value W_{DAI}^{UL} is determined by the Downlink Assignment Index (DAI) in DCI format 0/4 corresponding to a PUSCH on the serving cell according to Table 7.3-Z in subframe $n - k'$, where $k' = 4$.
- for a serving cell with frame structure type 1, when PUCCH format 3 is configured for transmission of HARQ-ACK, if the DL-reference UL/DL configuration of the serving cell is 0, the HARQ-ACK for a PDSCH transmission with a corresponding PDCCH/EPDCCH in subframe $n - k$ is associated with $o_{c,DAI(k)-1}^{ACK}$ if transmission mode configured in the c -th serving cell supports one transport block or spatial HARQ-ACK bundling is applied, or associated with $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ otherwise, where $DAI(k)$ is the value of DAI in DCI format 1A/1B/1D/1/2/2A/2B/2C/2D detected in subframe $n - k$, $o_{c,2DAI(k)-2}^{ACK}$ and $o_{c,2DAI(k)-1}^{ACK}$ are the HARQ-ACK feedback for codeword 0 and codeword 1, respectively. For the case with $N_{SPS} > 0$, the HARQ-ACK associated with a PDSCH transmission without a corresponding PDCCH/EPDCCH is mapped to o_{c,O_c}^{ACK} . The HARQ-ACK feedback bits without any detected PDSCH transmission are set to NACK.

8 Physical uplink shared channel related procedures

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG.

For FDD and transmission mode 1, there shall be 8 uplink HARQ processes per serving cell for non-subframe bundling operation, i.e. normal HARQ operation, and 3 uplink HARQ processes for subframe bundling operation when parameter *e-HARQ-Pattern-r12* is set to *TRUE* and 4 uplink HARQ processes for subframe bundling operation otherwise. For FDD and transmission mode 2, there shall be 16 uplink HARQ processes per serving cell for non-subframe bundling operation and there are two HARQ processes associated with a given subframe as described in [8]. The subframe bundling operation is configured by the parameter *ttiBundling* provided by higher layers.

In case higher layers configure the use of subframe bundling for FDD and TDD, the subframe bundling operation is only applied to UL-SCH, such that four consecutive uplink subframes are used.

8.0 UE procedure for transmitting the physical uplink shared channel

The term “UL/DL configuration” in this subclause refers to the higher layer parameter *subframeAssignment* unless specified otherwise.

For FDD and normal HARQ operation, the UE shall upon detection on a given serving cell of a PDCCH/EPDCCH with DCI format 0/4 and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission in subframe $n+4$ according to the PDCCH/EPDCCH and PHICH information.

For FDD-TDD and normal HARQ operation and a PUSCH for serving cell c with frame structure type 1, the UE shall upon detection of a PDCCH/EPDCCH with DCI format 0/4 and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission for serving cell c in subframe $n+4$ according to the PDCCH/EPDCCH and PHICH information.

For normal HARQ operation, if the UE detects a PHICH transmission and if the most recent PUSCH transmission for the same transport block was using spatial multiplexing according to subclause 8.0.2 and the UE does not detect a PDCCH/EPDCCH with DCI format 4 in subframe n intended for the UE, the UE shall adjust the corresponding PUSCH retransmission in the associated subframe according to the PHICH information, and using the number of transmission layers and precoding matrix according to the most recent PDCCH/EPDCCH, if the number of negatively acknowledged transport blocks is equal to the number of transport blocks indicated in the most recent PDCCH/EPDCCH associated with the corresponding PUSCH.

For normal HARQ operation, if the UE detects a PHICH transmission and if the most recent PUSCH transmission for the same transport block was using spatial multiplexing according to subclause 8.0.2 and the UE does not detect a PDCCH/EPDCCH with DCI format 4 in subframe n intended for the UE, and if the number of negatively acknowledged transport blocks is not equal to the number of transport blocks indicated in the most recent PDCCH/EPDCCH associated with the corresponding PUSCH then the UE shall adjust the corresponding PUSCH retransmission in the associated subframe according to the PHICH information, using the precoding matrix with codebook index 0 and the number of transmission layers equal to number of layers corresponding to the negatively acknowledged transport block from the most recent PDCCH/EPDCCH. In this case, the UL DMRS resources are calculated according to the cyclic shift field for DMRS [3] in the most recent PDCCH/EPDCCH with DCI format 4 associated with the corresponding PUSCH transmission and number of layers corresponding to the negatively acknowledged transport block.

If a UE is configured with the carrier indicator field for a given serving cell, the UE shall use the carrier indicator field value from the detected PDCCH/EPDCCH with uplink DCI format to determine the serving cell for the corresponding PUSCH transmission.

For FDD and normal HARQ operation, if a PDCCH/EPDCCH with CSI request field set to trigger an aperiodic CSI report, as described in subclause 7.2.1, is detected by a UE on subframe n , then on subframe $n+4$ UCI is mapped on the corresponding PUSCH transmission, when simultaneous PUSCH and PUCCH transmission is not configured for the UE.

For FDD-TDD and normal HARQ operation, for a serving cell with frame structure type 1, if a PDCCH/EPDCCH with CSI request field set to trigger an aperiodic CSI report, as described in subclause 7.2.1, is detected by a UE on subframe n , then on subframe $n+4$ UCI is mapped on the corresponding PUSCH transmission, when simultaneous PUSCH and PUCCH transmission is not configured for the UE.

For TDD, if a UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, if the UE is configured with one serving cell or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same, then for a given serving cell, the serving cell UL/DL configuration is the UL-reference UL/DL configuration.

For TDD, if a UE is configured with more than one serving cell and if the UL/DL configurations of at least two serving cells are different, if the serving cell is a primary cell or if the UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, the serving cell UL/DL configuration is the UL-reference UL/DL configuration.

For TDD, if a UE is configured with more than one serving cell and if the UL/DL configurations of at least two serving cells are different and if the serving cell is a secondary cell and if the UE is configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, then for the serving cell, the UL reference UL/DL configuration is given in Table 8-0A corresponding to the pair formed by (other serving cell UL/DL configuration, serving cell UL/DL configuration).

For FDD-TDD and primary cell frame structure type 2, if a serving cell is a primary cell, the serving cell UL/DL configuration is the UL-reference UL/DL configuration for the serving cell.

For FDD-TDD if the UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling a secondary serving cell with frame structure type 2, the serving cell UL/DL configuration is the UL-reference UL/DL configuration for the serving cell.

For FDD-TDD, and for secondary serving cell c with frame structure type 2, if the UE is configured to monitor PDCCH/EPDCCH in another serving cell with frame structure type 1 for scheduling the serving cell, the serving cell UL/DL configuration is the UL-reference UL/DL configuration for the serving cell.

For FDD-TDD, if a UE is configured with more than one serving cell with frame structure type 2, and if the serving cell is a secondary cell with frame structure type 2 and if the UE is configured to monitor PDCCH/EPDCCH in another serving cell with frame structure type 2 for scheduling the serving cell, then for the serving cell, the UL reference UL/DL configuration is given in Table 8-0A corresponding to the pair formed by (other serving cell UL/DL configuration, serving cell UL/DL configuration).

Table 8-0A: UL-reference UL/DL Configuration for serving cell based on the pair formed by (other serving cell UL/DL configuration, serving cell UL/DL configuration)

| Set # | (other serving cell UL/DL configuration, serving cell UL/DL configuration) | UL-reference UL/DL configuration |
|-------|--|----------------------------------|
| Set 1 | (1,1),(1,2),(1,4),(1,5) | 1 |
| | (2,2),(2,5) | 2 |
| | (3,3),(3,4),(3,5) | 3 |
| | (4,4),(4,5) | 4 |
| | (5,5) | 5 |
| Set 2 | (1,0),(2,0),(3,0),(4,0),(5,0) | 0 |
| | (2,1),(4,1),(5,1) | 1 |
| | (5,2) | 2 |
| | (4,3),(5,3) | 3 |
| | (5,4) | 4 |
| | (1,6),(2,6),(3,6),(4,6),(5,6) | 6 |
| Set 3 | (3,1) | 1 |
| | (3,2),(4,2) | 2 |
| | (1,3),(2,3) | 3 |
| | (2,4) | 4 |
| Set 4 | (0,0),(6,0) | 0 |
| | (0,1),(0,2),(0,4),(0,5),(6,1),(6,2),(6,5) | 1 |
| | (0,3),(6,3) | 3 |
| | (6,4) | 4 |
| | (0,6),(6,6) | 6 |

If a UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for a serving cell, for a radio frame of the serving cell, PUSCH transmissions can occur only in subframes that are indicated by *eIMTA-UL/DL-configuration* as uplink subframe(s) for the serving cell unless specified otherwise.

For TDD and normal HARQ operation, if a PDCCH/EPDCCH with CSI request field set to trigger an aperiodic CSI report, as described in subclause 7.2.1, is detected by a UE on subframe n , then on subframe $n+k$ UCI is mapped on the corresponding PUSCH transmission where k is given by Table 8-2, when simultaneous PUSCH and PUCCH transmission is not configured for the UE.

For FDD-TDD normal HARQ operation, for a serving cell with frame structure type 2, if a PDCCH/EPDCCH with CSI request field set to trigger an aperiodic CSI report on the serving cell, as described in subclause 7.2.1, is detected by a UE on subframe n , then on subframe $n+k$ UCI is mapped on the corresponding PUSCH transmission where k is given by Table 8-2 and the “TDD UL/DL configuration” refers to the UL-reference UL/DL configuration for the serving cell, when simultaneous PUSCH and PUCCH transmission is not configured for the UE.

When a UE is configured with higher layer parameter *ttiBundling* and configured with higher layer parameter *e-HARQ-Pattern-r12* set to *FALSE* or not configured, for FDD and subframe bundling operation, the UE shall upon detection of a PDCCH/EPDCCH with DCI format 0 in subframe n intended for the UE, and/or a PHICH transmission in subframe $n-5$ intended for the UE, adjust the corresponding first PUSCH transmission in the bundle in subframe $n+4$ according to the PDCCH/EPDCCH and PHICH information.

When a UE is configured with higher layer parameter *ttiBundling* and configured with higher layer parameter *e-HARQ-Pattern-r12* set to *TRUE*, for FDD and subframe bundling operation, the UE shall upon detection of a PDCCH/EPDCCH with DCI format 0 in subframe n intended for the UE, and/or a PHICH transmission in subframe $n-1$

intended for the UE, adjust the corresponding first PUSCH transmission in the bundle in subframe $n+4$ according to the PDCCH/EPDCCH and PHICH information.

For both FDD and TDD serving cells, the NDI as signalled on PDCCH/EPDCCH, the RV as determined in subclause 8.6.1, and the TBS as determined in subclause 8.6.2, shall be delivered to higher layers.

For TDD and transmission mode 1, the number of HARQ processes per serving cell shall be determined by the UL/DL configuration (Table 4.2-2 of [3]), as indicated in Table 8-1. For TDD and transmission mode 2, the number of HARQ processes per serving cell for non-subframe bundling operation shall be twice the number determined by the UL/DL configuration (Table 4.2-2 of [3]) as indicated in Table 8-1 and there are two HARQ processes associated with a given subframe as described in [8]. For TDD and both transmission mode 1 and transmission mode 2, the "TDD UL/DL configuration" in Table 8-1 refers to the UL-reference UL/DL configuration for the serving cell if UL-reference UL/DL configuration is defined for the serving cell and refers to the serving cell UL/DL configuration otherwise.

Table 8-1: Number of synchronous UL HARQ processes for TDD

| TDD UL/DL configuration | Number of HARQ processes for normal HARQ operation | Number of HARQ processes for subframe bundling operation |
|-------------------------|--|--|
| 0 | 7 | 3 |
| 1 | 4 | 2 |
| 2 | 2 | N/A |
| 3 | 3 | N/A |
| 4 | 2 | N/A |
| 5 | 1 | N/A |
| 6 | 6 | 3 |

For TDD, if the UE is not configured with *EIMTA-MainConfigServCell-r12* for any serving cell, and if a UE is configured with one serving cell, or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same,

- For TDD UL/DL configurations 1-6 and normal HARQ operation, the UE shall upon detection of a PDCCH/EPDCCH with uplink DCI format and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission in subframe $n+k$, with k given in Table 8-2, according to the PDCCH/EPDCCH and PHICH information.
- For TDD UL/DL configuration 0 and normal HARQ operation the UE shall upon detection of a PDCCH/EPDCCH with uplink DCI format and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission in subframe $n+k$ if the MSB of the UL index in the PDCCH/EPDCCH with uplink DCI format is set to 1 or PHICH is received in subframe $n=0$ or 5 in the resource corresponding to $I_{PHICH} = 0$, as defined in subclause 9.1.2, with k given in Table 8-2. If, for TDD UL/DL configuration 0 and normal HARQ operation, the LSB of the UL index in the DCI format 0/4 is set to 1 in subframe n or a PHICH is received in subframe $n=0$ or 5 in the resource corresponding to $I_{PHICH} = 1$, as defined in subclause 9.1.2, or PHICH is received in subframe $n=1$ or 6, the UE shall adjust the corresponding PUSCH transmission in subframe $n+7$. If, for TDD UL/DL configuration 0, both the MSB and LSB of the UL index in the PDCCH/EPDCCH with uplink DCI format are set in subframe n , the UE shall adjust the corresponding PUSCH transmission in both subframes $n+k$ and $n+7$, with k given in Table 8-2.

For TDD, if a UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same or if the UE is configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell, or FDD-TDD,

- For a serving cell with an UL-reference UL/DL configurations belonging to $\{1,2,3,4,5,6\}$ and normal HARQ operation, the UE shall upon detection of a PDCCH/EPDCCH with uplink DCI format and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission in subframe $n+k$ for the serving cell, with k given in Table 8-2, according to the PDCCH/EPDCCH and PHICH information, where the "TDD UL/DL Configuration" given in Table 8-2 refers to the UL-reference UL/DL configuration.
- For a serving cell with UL-reference UL/DL configuration 0 and normal HARQ operation the UE shall upon detection of a PDCCH/EPDCCH with uplink DCI format and/or a PHICH transmission in subframe n intended for the UE, adjust the corresponding PUSCH transmission in subframe $n+k$ for the serving cell if the MSB of the UL index in the PDCCH/EPDCCH with uplink DCI format is set to 1 or PHICH is received in subframe $n=0$ or 5 in the resource corresponding to $I_{PHICH} = 0$, as defined in subclause 9.1.2, with k given in Table 8-2. If, for a

-serving cell with UL-reference UL/DL configuration 0 and normal HARQ operation, the LSB of the UL index in the DCI format 0/4 is set to 1 in subframe n or a PHICH is received in subframe $n=0$ or 5 in the resource corresponding to $I_{PHICH} = 1$, as defined in subclause 9.1.2, or PHICH is received in subframe $n=1$ or 6, the UE shall adjust the corresponding PUSCH transmission in subframe $n+7$ for the serving cell. If, for a serving cell with UL-reference UL/DL configuration 0, both the MSB and LSB of the UL index in the PDCCH/EPDCCH with uplink DCI format are set in subframe n , the UE shall adjust the corresponding PUSCH transmission in both subframes $n+k$ and $n+7$ for the serving cell, with k given in Table 8-2, where the TDD UL/DL Configuration" given in Table 8-2 refers to the UL-reference UL/DL configuration.

For TDD UL/DL configurations 1 and 6 and subframe bundling operation, the UE shall upon detection of a PDCCH/EPDCCH with DCI format 0 in subframe n intended for the UE, and/or a PHICH transmission intended for the UE in subframe $n-l$ with l given in Table 8-2a, adjust the corresponding first PUSCH transmission in the bundle in subframe $n+k$, with k given in Table 8-2, according to the PDCCH/EPDCCH and PHICH information.

For TDD UL/DL configuration 0 and subframe bundling operation, the UE shall upon detection of a PDCCH/EPDCCH with DCI format 0 in subframe n intended for the UE, and/or a PHICH transmission intended for the UE in subframe $n-l$ with l given in Table 8-2a, adjust the corresponding first PUSCH transmission in the bundle in subframe $n+k$, if the MSB of the UL index in the DCI format 0 is set to 1 or if $I_{PHICH} = 0$, as defined in subclause 9.1.2, with k given in Table 8-2, according to the PDCCH/EPDCCH and PHICH information. If, for TDD UL/DL configuration 0 and subframe bundling operation, the LSB of the UL index in the PDCCH/EPDCCH with DCI format 0 is set to 1 in subframe n or if $I_{PHICH} = 1$, as defined in subclause 9.1.2, the UE shall adjust the corresponding first PUSCH transmission in the bundle in subframe $n+7$, according to the PDCCH/EPDCCH and PHICH information.

Table 8-2 k for TDD configurations 0-6

| TDD UL/DL Configuration | subframe number n | | | | | | | | | |
|-------------------------|---------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | 4 | 6 | | | | 4 | 6 | | | |
| 1 | | 6 | | | 4 | | 6 | | | 4 |
| 2 | | | | 4 | | | | | 4 | |
| 3 | 4 | | | | | | | | 4 | 4 |
| 4 | | | | | | | | | 4 | 4 |
| 5 | | | | | | | | | 4 | |
| 6 | 7 | 7 | | | | 7 | 7 | | | 5 |

Table 8-2a l for TDD configurations 0, 1 and 6

| TDD UL/DL Configuration | subframe number n | | | | | | | | | |
|-------------------------|---------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | 9 | 6 | | | | 9 | 6 | | | |
| 1 | | 2 | | | 3 | | 2 | | | 3 |
| 6 | 5 | 5 | | | | 6 | 6 | | | 8 |

A UE is semi-statically configured via higher layer signalling to transmit PUSCH transmissions signalled via PDCCH/EPDCCH according to one of two uplink transmission modes, denoted mode 1 - 2.

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the C-RNTI, the UE shall decode the PDCCH according to the combination defined in Table 8-3 and transmit the corresponding PUSCH. The scrambling initialization of this PUSCH corresponding to these PDCCHs and the PUSCH retransmission for the same transport block is by C-RNTI.

If a UE is configured by higher layers to decode EPDCCHs with the CRC scrambled by the C-RNTI, the UE shall decode the EPDCCH according to the combination defined in Table 8-3A and transmit the corresponding PUSCH. The scrambling initialization of this PUSCH corresponding to these EPDCCHs and the PUSCH retransmission for the same transport block is by C-RNTI.

Transmission mode 1 is the default uplink transmission mode for a UE until the UE is assigned an uplink transmission mode by higher layer signalling.

When a UE configured in transmission mode 2 receives a DCI Format 0 uplink scheduling grant, it shall assume that the PUSCH transmission is associated with transport block 1 and that transport block 2 is disabled.

Table 8-3: PDCCH and PUSCH configured by C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PUSCH corresponding to PDCCH |
|-------------------|--------------|----------------------------------|--|
| Mode 1 | DCI format 0 | Common and UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| Mode 2 | DCI format 0 | Common and UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| | DCI format 4 | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 8.0.2) |

Table 8-3A: EPDCCH and PUSCH configured by C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PUSCH corresponding to EPDCCH |
|-------------------|--------------|-----------------------|--|
| Mode 1 | DCI format 0 | UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| Mode 2 | DCI format 0 | UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| | DCI format 4 | UE specific by C-RNTI | Closed-loop spatial multiplexing (see subclause 8.0.2) |

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the C-RNTI and is also configured to receive random access procedures initiated by "PDCCH orders", the UE shall decode the PDCCH according to the combination defined in Table 8-4.

If a UE is configured by higher layers to decode EPDCCHs with the CRC scrambled by the C-RNTI and is also configured to receive random access procedures initiated by "PDCCH orders", the UE shall decode the EPDCCH according to the combination defined in Table 8-4A.

Table 8-4: PDCCH configured as "PDCCH order" to initiate random access procedure

| DCI format | Search Space |
|---------------|----------------------------------|
| DCI format 1A | Common and UE specific by C-RNTI |

Table 8-4A: EPDCCH configured as "PDCCH order" to initiate random access procedure

| DCI format | Search Space |
|---------------|-----------------------|
| DCI format 1A | UE specific by C-RNTI |

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the SPS C-RNTI, the UE shall decode the PDCCH according to the combination defined in Table 8-5 and transmit the corresponding PUSCH. The scrambling initialization of this PUSCH corresponding to these PDCCHs and PUSCH retransmission for the same transport block is by SPS C-RNTI. The scrambling initialization of initial transmission of this PUSCH without a corresponding PDCCH and the PUSCH retransmission for the same transport block is by SPS C-RNTI.

If a UE is configured by higher layers to decode EPDCCHs with the CRC scrambled by the SPS C-RNTI, the UE shall decode the EPDCCH according to the combination defined in Table 8-5A and transmit the corresponding PUSCH. The scrambling initialization of this PUSCH corresponding to these EPDCCHs and PUSCH retransmission for the same transport block is by SPS C-RNTI. The scrambling initialization of initial transmission of this PUSCH without a corresponding EPDCCH and the PUSCH retransmission for the same transport block is by SPS C-RNTI.

Table 8-5: PDCCH and PUSCH configured by SPS C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PUSCH corresponding to PDCCH |
|-------------------|--------------|----------------------------------|---|
| Mode 1 | DCI format 0 | Common and UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| Mode 2 | DCI format 0 | Common and UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |

Table 8-5A: EPDCCH and PUSCH configured by SPS C-RNTI

| Transmission mode | DCI format | Search Space | Transmission scheme of PUSCH corresponding to PDCCH |
|-------------------|--------------|-----------------------|---|
| Mode 1 | DCI format 0 | UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |
| Mode 2 | DCI format 0 | UE specific by C-RNTI | Single-antenna port, port 10 (see subclause 8.0.1) |

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the Temporary C-RNTI regardless of whether UE is configured or not configured to decode PDCCHs with the CRC scrambled by the C-RNTI, the UE shall decode the PDCCH according to the combination defined in Table 8-6 and transmit the corresponding PUSCH. The scrambling initialization of PUSCH corresponding to these PDCCH is by Temporary C-RNTI.

If a Temporary C-RNTI is set by higher layers, the scrambling of PUSCH corresponding to the Random Access Response Grant in subclause 6.2 and the PUSCH retransmission for the same transport block is by Temporary C-RNTI. Else, the scrambling of PUSCH corresponding to the Random Access Response Grant in subclause 6.2 and the PUSCH retransmission for the same transport block is by C-RNTI.

Table 8-6: PDCCH configured by Temporary C-RNTI

| DCI format | Search Space |
|--------------|--------------|
| DCI format 0 | Common |

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the TPC-PUCCH-RNTI, the UE shall decode the PDCCH according to the combination defined in table 8-7. The notation 3/3A implies that the UE shall receive either DCI format 3 or DCI format 3A depending on the configuration.

Table 8-7: PDCCH configured by TPC-PUCCH-RNTI

| DCI format | Search Space |
|-----------------|--------------|
| DCI format 3/3A | Common |

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the TPC-PUSCH-RNTI, the UE shall decode the PDCCH according to the combination defined in table 8.8. The notation 3/3A implies that the UE shall receive either DCI format 3 or DCI format 3A depending on the configuration.

Table 8-8: PDCCH configured by TPC-PUSCH-RNTI

| DCI format | Search Space |
|-----------------|--------------|
| DCI format 3/3A | Common |

8.0.1 Single-antenna port scheme

For the single-antenna port transmission schemes (port 10) of the PUSCH, the UE transmission on the PUSCH is performed according to subclause 5.3.2A.1 of [3].

8.0.2 Closed-loop spatial multiplexing scheme

For the closed-loop spatial multiplexing transmission scheme of the PUSCH, the UE transmission on the PUSCH is performed according to the applicable number of transmission layers as defined in subclause 5.3.2A.2 of [3].

8.1 Resource allocation for PDCCH/EPDCCH with uplink DCI format

Two resource allocation schemes Type 0 and Type 1 are supported for PDCCH/EPDCCH with uplink DCI format.

If the resource allocation type bit is not present in the uplink DCI format, only resource allocation type 0 is supported.

If the resource allocation type bit is present in the uplink DCI format, the selected resource allocation type for a decoded PDCCH/EPDCCH is indicated by a resource allocation type bit where type 0 is indicated by 0 value and type 1 is indicated otherwise. The UE shall interpret the resource allocation field depending on the resource allocation type bit in the PDCCH/EPDCCH with uplink DCI format detected.

8.1.1 Uplink resource allocation type 0

The resource allocation information for uplink resource allocation type 0 indicates to a scheduled UE a set of contiguously allocated virtual resource block indices denoted by n_{VRB} . A resource allocation field in the scheduling grant consists of a resource indication value (RIV) corresponding to a starting resource block (RB_{START}) and a length in terms of contiguously allocated resource blocks ($L_{\text{CRBs}} \geq 1$). The resource indication value is defined by

if $(L_{\text{CRBs}} - 1) \leq \lfloor N_{\text{RB}}^{\text{UL}} / 2 \rfloor$ then

$$RIV = N_{\text{RB}}^{\text{UL}} (L_{\text{CRBs}} - 1) + RB_{\text{START}}$$

else

$$RIV = N_{\text{RB}}^{\text{UL}} (N_{\text{RB}}^{\text{UL}} - L_{\text{CRBs}} + 1) + (N_{\text{RB}}^{\text{UL}} - 1 - RB_{\text{START}})$$

8.1.2 Uplink resource allocation type 1

The resource allocation information for uplink resource allocation type 1 indicates to a scheduled UE two sets of resource blocks with each set including one or more consecutive resource block groups of size P as given in table

7.1.6.1-1 assuming $N_{\text{RB}}^{\text{UL}}$ as the system bandwidth. A combinatorial index r consists of $\left\lceil \log_2 \left(\binom{\lfloor N_{\text{RB}}^{\text{UL}} / P + 1 \rfloor}{4} \right) \right\rceil$ bits.

The bits from the resource allocation field in the scheduling grant represent r unless the number of bits in the resource allocation field in the scheduling grant is

- smaller than required to fully represent r , in which case the bits in the resource allocation field in the scheduling grant occupy the LSBs of r and the value of the remaining bits of r shall be assumed to be 0; or
- larger than required to fully represent r , in which case r occupies the LSBs of the resource allocation field in the scheduling grant.

The combinatorial index r corresponds to a starting and ending RBG index of resource block set 1, s_0 and $s_1 - 1$, and

resource block set 2, s_2 and $s_3 - 1$ respectively, where r is given by equation $r = \sum_{i=0}^{M-1} \binom{N - s_i}{M - i}$ defined in subclause

7.2.1 with $M=4$ and $N = \lfloor N_{\text{RB}}^{\text{UL}} / P \rfloor + 1$. subclause 7.2.1 also defines ordering properties and range of values that s_i

(RBG indices) map to. Only a single RBG is allocated for a set at the starting RBG index if the corresponding ending RBG index equals the starting RBG index.

8.2 UE sounding procedure

A UE shall transmit Sounding Reference Symbol (SRS) on per serving cell SRS resources based on two trigger types:

- trigger type 0: higher layer signalling
- trigger type 1: DCI formats 0/4/1A for FDD and TDD and DCI formats 2B/2C/2D for TDD.

In case both trigger type 0 and trigger type 1 SRS transmissions would occur in the same subframe in the same serving cell, the UE shall only transmit the trigger type 1 SRS transmission.

A UE may be configured with SRS parameters for trigger type 0 and trigger type 1 on each serving cell. The following SRS parameters are serving cell specific and semi-statically configurable by higher layers for trigger type 0 and for trigger type 1.

- Transmission comb \bar{k}_{TC} , as defined in subclause 5.5.3.2 of [3] for trigger type 0 and each configuration of trigger type 1
- Starting physical resource block assignment n_{RRC} , as defined in subclause 5.5.3.2 of [3] for trigger type 0 and each configuration of trigger type 1
- *duration*: single or indefinite (until disabled), as defined in [11] for trigger type 0
- *srs-ConfigIndex* I_{SRS} for SRS periodicity T_{SRS} and SRS subframe offset T_{offset} , as defined in Table 8.2-1 and Table 8.2-2 for trigger type 0 and SRS periodicity $T_{SRS,1}$ and SRS subframe offset $T_{offset,1}$, as defined in Table 8.2-4 and Table 8.2-5 trigger type 1
- SRS bandwidth B_{SRS} , as defined in subclause 5.5.3.2 of [3] for trigger type 0 and each configuration of trigger type 1
- Frequency hopping bandwidth, b_{hop} , as defined in subclause 5.5.3.2 of [3] for trigger type 0
- Cyclic shift n_{SRS}^{cs} , as defined in subclause 5.5.3.1 of [3] for trigger type 0 and each configuration of trigger type 1
- Number of antenna ports N_p for trigger type 0 and each configuration of trigger type 1

For trigger type 1 and DCI format 4 three sets of SRS parameters, *srs-ConfigApDCI-Format4*, are configured by higher layer signalling. The 2-bit SRS request field [4] in DCI format 4 indicates the SRS parameter set given in Table 8.1-1. For trigger type 1 and DCI format 0, a single set of SRS parameters, *srs-ConfigApDCI-Format0*, is configured by higher layer signalling. For trigger type 1 and DCI formats 1A/2B/2C/2D, a single common set of SRS parameters, *srs-ConfigApDCI-Format1a2b2c*, is configured by higher layer signalling. The SRS request field is 1 bit [4] for DCI formats 0/1A/2B/2C/2D, with a type 1 SRS triggered if the value of the SRS request field is set to '1'. A 1-bit SRS request field shall be included in DCI formats 0/1A for frame structure type 1 and 0/1A/2B/2C/2D for frame structure type 2 if the UE is configured with SRS parameters for DCI formats 0/1A/2B/2C/2D by higher-layer signalling.

Table 8.1-1: SRS request value for trigger type 1 in DCI format 4

| Value of SRS request field | Description |
|----------------------------|---|
| '00' | No type 1 SRS trigger |
| '01' | The 1 st SRS parameter set configured by higher layers |
| '10' | The 2 nd SRS parameter set configured by higher layers |
| '11' | The 3 rd SRS parameter set configured by higher layers |

The serving cell specific SRS transmission bandwidths C_{SRS} are configured by higher layers. The allowable values are given in subclause 5.5.3.2 of [3].

The serving cell specific SRS transmission sub-frames are configured by higher layers. The allowable values are given in subclause 5.5.3.3 of [3].

For a TDD serving cell, SRS transmissions can occur in UpPTS and uplink subframes of the UL/DL configuration indicated by the higher layer parameter *subframeAssignment* for the serving cell.

When closed-loop UE transmit antenna selection is enabled for a given serving cell for a UE that supports transmit antenna selection, the index $a(n_{SRS})$, of the UE antenna that transmits the SRS at time n_{SRS} is given by

$a(n_{SRS}) = n_{SRS} \bmod 2$, for both partial and full sounding bandwidth, and when frequency hopping is disabled (i.e., $b_{hop} \geq B_{SRS}$),

$$a(n_{SRS}) = \begin{cases} (n_{SRS} + \lfloor n_{SRS}/2 \rfloor + \beta \cdot \lfloor n_{SRS}/K \rfloor) \bmod 2 & \text{when } K \text{ is even} \\ n_{SRS} \bmod 2 & \text{when } K \text{ is odd} \end{cases}, \quad \beta = \begin{cases} 1 & \text{where } K \bmod 4 = 0 \\ 0 & \text{otherwise} \end{cases}$$

when frequency hopping is enabled (i.e., $b_{hop} < B_{SRS}$),

where values B_{SRS} , b_{hop} , N_b , and n_{SRS} are given in subclause 5.5.3.2 of [3], and $K = \prod_{b'=b_{hop}}^{B_{SRS}} N_{b'}$ (where $N_{b_{hop}} = 1$ regardless of the N_b value), except when a single SRS transmission is configured for the UE. If a UE is configured with more than one serving cell, the UE is not expected to transmit SRS on different antenna ports simultaneously.

A UE may be configured to transmit SRS on N_p antenna ports of a serving cell where N_p may be configured by higher layer signalling. For PUSCH transmission mode 1 $N_p \in \{0,1,2,4\}$ and for PUSCH transmission mode 2 $N_p \in \{0,1,2\}$ with two antenna ports configured for PUSCH and $N_p \in \{0,1,4\}$ with 4 antenna ports configured for PUSCH. A UE configured for SRS transmission on multiple antenna ports of a serving cell shall transmit SRS for all the configured transmit antenna ports within one SC-FDMA symbol of the same subframe of the serving cell. The SRS transmission bandwidth and starting physical resource block assignment are the same for all the configured antenna ports of a given serving cell.

A UE not configured with multiple TAGs shall not transmit SRS in a symbol whenever SRS and PUSCH transmissions happen to overlap in the same symbol.

For TDD serving cell, when one SC-FDMA symbol exists in UpPTS of the given serving cell, it can be used for SRS transmission. When two SC-FDMA symbols exist in UpPTS of the given serving cell, both can be used for SRS transmission and for trigger type 0 SRS both can be assigned to the same UE.

If a UE is not configured with multiple TAGs, or if a UE is configured with multiple TAGs and SRS and PUCCH format 2/2a/2b happen to coincide in the same subframe in the same serving cell,

- The UE shall not transmit type 0 triggered SRS whenever type 0 triggered SRS and PUCCH format 2/2a/2b transmissions happen to coincide in the same subframe;
- The UE shall not transmit type 1 triggered SRS whenever type 1 triggered SRS and PUCCH format 2a/2b or format 2 with HARQ-ACK transmissions happen to coincide in the same subframe;
- The UE shall not transmit PUCCH format 2 without HARQ-ACK whenever type 1 triggered SRS and PUCCH format 2 without HARQ-ACK transmissions happen to coincide in the same subframe.

If a UE is not configured with multiple TAGs, or if a UE is configured with multiple TAGs and SRS and PUCCH happen to coincide in the same subframe in the same serving cell,

- The UE shall not transmit SRS whenever SRS transmission and PUCCH transmission carrying HARQ-ACK and/or positive SR happen to coincide in the same subframe if the parameter *ackNackSRS-SimultaneousTransmission* is *FALSE*;

- For FDD-TDD and primary cell frame structure 1, the UE shall not transmit SRS in a symbol whenever SRS transmission and PUCCH transmission carrying HARQ-ACK and/or positive SR using shortened format as defined in subclauses 5.4.1 and 5.4.2A of [3] happen to overlap in the same symbol if the parameter *ackNackSRS-SimultaneousTransmission* is *TRUE*.
- Unless otherwise prohibited, the UE shall transmit SRS whenever SRS transmission and PUCCH transmission carrying HARQ-ACK and/or positive SR using shortened format as defined in subclauses 5.4.1 and 5.4.2A of [3] happen to coincide in the same subframe if the parameter *ackNackSRS-SimultaneousTransmission* is *TRUE*.

A UE not configured with multiple TAGs shall not transmit SRS whenever SRS transmission on any serving cells and PUCCH transmission carrying HARQ-ACK and/or positive SR using normal PUCCH format as defined in subclauses 5.4.1 and 5.4.2A of [3] happen to coincide in the same subframe.

In UpPTS, whenever SRS transmission instance overlaps with the PRACH region for preamble format 4 or exceeds the range of uplink system bandwidth configured in the serving cell, the UE shall not transmit SRS.

The parameter *ackNackSRS-SimultaneousTransmission* provided by higher layers determines if a UE is configured to support the transmission of HARQ-ACK on PUCCH and SRS in one subframe. If it is configured to support the transmission of HARQ-ACK on PUCCH and SRS in one subframe, then in the cell specific SRS subframes of the primary cell UE shall transmit HARQ-ACK and SR using the shortened PUCCH format as defined in subclauses 5.4.1 and 5.4.2A of [3], where the HARQ-ACK or the SR symbol corresponding to the SRS location is punctured. This shortened PUCCH format shall be used in a cell specific SRS subframe of the primary cell even if the UE does not transmit SRS in that subframe. The cell specific SRS subframes are defined in subclause 5.5.3.3 of [3]. Otherwise, the UE shall use the normal PUCCH format 1/1a/1b as defined in subclause 5.4.1 of [3] or normal PUCCH format 3 as defined in subclause 5.4.2A of [3] for the transmission of HARQ-ACK and SR.

Trigger type 0 SRS configuration of a UE in a serving cell for SRS periodicity, T_{SRS} , and SRS subframe offset, T_{offset} , is defined in Table 8.2-1 and Table 8.2-2, for FDD and TDD serving cell, respectively. The periodicity T_{SRS} of the SRS transmission is serving cell specific and is selected from the set {2, 5, 10, 20, 40, 80, 160, 320} ms or subframes. For the SRS periodicity T_{SRS} of 2 ms in TDD serving cell, two SRS resources are configured in a half frame containing UL subframe(s) of the given serving cell.

Type 0 triggered SRS transmission instances in a given serving cell for TDD serving cell with $T_{\text{SRS}} > 2$ and for FDD serving cell are the subframes satisfying $(10 \cdot n_f + k_{\text{SRS}} - T_{\text{offset}}) \bmod T_{\text{SRS}} = 0$, where for FDD $k_{\text{SRS}} = \{0, 1, \dots, 9\}$ is the subframe index within the frame, for TDD serving cell k_{SRS} is defined in Table 8.2-3. The SRS transmission instances for TDD serving cell with $T_{\text{SRS}} = 2$ are the subframes satisfying $(k_{\text{SRS}} - T_{\text{offset}}) \bmod 5 = 0$.

For TDD serving cell, and a UE configured for type 0 triggered SRS transmission in serving cell c , and the UE configured with the parameter *EIMTA-MainConfigServCell-r12* for serving cell c , if the UE does not detect an UL/DL configuration indication for radio frame m (as described in section 13.1), the UE shall not transmit trigger type 0 SRS in a subframe of radio frame m that is indicated by the parameter *eimta-HARQ-ReferenceConfig-r12* as a downlink subframe unless the UE transmits PUSCH in the same subframe.

Trigger type 1 SRS configuration of a UE in a serving cell for SRS periodicity, $T_{\text{SRS},1}$, and SRS subframe offset, $T_{\text{offset},1}$, is defined in Table 8.2-4 and Table 8.2-5, for FDD and TDD serving cell, respectively. The periodicity $T_{\text{SRS},1}$ of the SRS transmission is serving cell specific and is selected from the set {2, 5, 10} ms or subframes. For the SRS periodicity $T_{\text{SRS},1}$ of 2 ms in TDD serving cell, two SRS resources are configured in a half frame containing UL subframe(s) of the given serving cell.

A UE configured for type 1 triggered SRS transmission in serving cell c and not configured with a carrier indicator field shall transmit SRS on serving cell c upon detection of a positive SRS request in PDCCH/EPDCCH scheduling PUSCH/PDSCH on serving cell c .

A UE configured for type 1 triggered SRS transmission in serving cell c and configured with a carrier indicator field shall transmit SRS on serving cell c upon detection of a positive SRS request in PDCCH/EPDCCH scheduling PUSCH/PDSCH with the value of carrier indicator field corresponding to serving cell c .

A UE configured for type 1 triggered SRS transmission on serving cell c upon detection of a positive SRS request in subframe n of serving cell c shall commence SRS transmission in the first subframe satisfying $n + k, k \geq 4$ and

$(10 \cdot n_f + k_{\text{SRS}} - T_{\text{offset},1}) \bmod T_{\text{SRS},1} = 0$ for TDD serving cell c with $T_{\text{SRS},1} > 2$ and for FDD serving cell c ,

$(k_{\text{SRS}} - T_{\text{offset},1}) \bmod 5 = 0$ for TDD serving cell c with $T_{\text{SRS},1} = 2$

where for FDD serving cell c $k_{\text{SRS}} = \{0,1,\dots,9\}$ is the subframe index within the frame n_f , for TDD serving cell c k_{SRS} is defined in Table 8.2-3.

A UE configured for type 1 triggered SRS transmission is not expected to receive type 1 SRS triggering events associated with different values of trigger type 1 SRS transmission parameters, as configured by higher layer signalling, for the same subframe and the same serving cell.

For TDD serving cell c , and a UE configured with *EIMTA-MainConfigServCell-r12* for a serving cell c , the UE shall not transmit SRS in a subframe of a radio frame that is indicated by the corresponding eIMTA-UL/DL-configuration as a downlink subframe.

A UE shall not transmit SRS whenever SRS and a PUSCH transmission corresponding to a Random Access Response Grant or a retransmission of the same transport block as part of the contention based random access procedure coincide in the same subframe.

Table 8.2-1: UE Specific SRS Periodicity T_{SRS} and Subframe Offset Configuration T_{offset} for trigger type 0, FDD

| SRS Configuration Index I_{SRS} | SRS Periodicity T_{SRS} (ms) | SRS Subframe Offset T_{offset} |
|--|---------------------------------------|---|
| 0 – 1 | 2 | I_{SRS} |
| 2 – 6 | 5 | $I_{\text{SRS}} - 2$ |
| 7 – 16 | 10 | $I_{\text{SRS}} - 7$ |
| 17 – 36 | 20 | $I_{\text{SRS}} - 17$ |
| 37 – 76 | 40 | $I_{\text{SRS}} - 37$ |
| 77 – 156 | 80 | $I_{\text{SRS}} - 77$ |
| 157 – 316 | 160 | $I_{\text{SRS}} - 157$ |
| 317 – 636 | 320 | $I_{\text{SRS}} - 317$ |
| 637 – 1023 | reserved | reserved |

Table 8.2-2: UE Specific SRS Periodicity T_{SRS} and Subframe Offset Configuration T_{offset} for trigger type 0, TDD

| SRS Configuration Index I_{SRS} | SRS Periodicity T_{SRS} (ms) | SRS Subframe Offset T_{offset} |
|---|--|--|
| 0 | 2 | 0, 1 |
| 1 | 2 | 0, 2 |
| 2 | 2 | 1, 2 |
| 3 | 2 | 0, 3 |
| 4 | 2 | 1, 3 |
| 5 | 2 | 0, 4 |
| 6 | 2 | 1, 4 |
| 7 | 2 | 2, 3 |
| 8 | 2 | 2, 4 |
| 9 | 2 | 3, 4 |
| 10 – 14 | 5 | $I_{\text{SRS}} - 10$ |
| 15 – 24 | 10 | $I_{\text{SRS}} - 15$ |
| 25 – 44 | 20 | $I_{\text{SRS}} - 25$ |
| 45 – 84 | 40 | $I_{\text{SRS}} - 45$ |
| 85 – 164 | 80 | $I_{\text{SRS}} - 85$ |
| 165 – 324 | 160 | $I_{\text{SRS}} - 165$ |
| 325 – 644 | 320 | $I_{\text{SRS}} - 325$ |
| 645 – 1023 | reserved | reserved |

Table 8.2-3: k_{SRS} for TDD

| | subframe index n | | | | | | | | | | | |
|---|--------------------|------------------------|------------------------|---|---|---|---|------------------------|------------------------|---|---|---|
| | 0 | 1 | | 2 | 3 | 4 | 5 | 6 | | 7 | 8 | 9 |
| | | 1st symbol of UpPTS | 2nd symbol of UpPTS | | | | | 1st symbol of UpPTS | 2nd symbol of UpPTS | | | |
| k_{SRS} in case UpPTS length of 2 symbols | 0 | 1 | 2 | 3 | 4 | | 5 | 6 | 7 | 8 | 9 | |
| k_{SRS} in case UpPTS length of 1 symbol | 1 | | 2 | 3 | 4 | | 6 | | 7 | 8 | 9 | |

Table 8.2-4: UE Specific SRS Periodicity $T_{\text{SRS},1}$ and Subframe Offset Configuration $T_{\text{offset},1}$ for trigger type 1, FDD

| SRS Configuration Index I_{SRS} | SRS Periodicity $T_{\text{SRS},1}$ (ms) | SRS Subframe Offset $T_{\text{offset},1}$ |
|---|--|--|
| 0 – 1 | 2 | I_{SRS} |
| 2 – 6 | 5 | $I_{\text{SRS}} - 2$ |
| 7 – 16 | 10 | $I_{\text{SRS}} - 7$ |
| 17 – 31 | reserved | reserved |

Table 8.2-5: UE Specific SRS Periodicity $T_{\text{SRS},1}$ and Subframe Offset Configuration $T_{\text{offset},1}$ for trigger type 1, TDD

| SRS Configuration Index l_{SRS} | SRS Periodicity $T_{\text{SRS},1}$ (ms) | SRS Subframe Offset $T_{\text{offset},1}$ |
|---|--|--|
| 0 | reserved | reserved |
| 1 | 2 | 0, 2 |
| 2 | 2 | 1, 2 |
| 3 | 2 | 0, 3 |
| 4 | 2 | 1, 3 |
| 5 | 2 | 0, 4 |
| 6 | 2 | 1, 4 |
| 7 | 2 | 2, 3 |
| 8 | 2 | 2, 4 |
| 9 | 2 | 3, 4 |
| 10 – 14 | 5 | $l_{\text{SRS}} - 10$ |
| 15 – 24 | 10 | $l_{\text{SRS}} - 15$ |
| 25 – 31 | reserved | reserved |

8.3 UE HARQ-ACK procedure

For FDD, and serving cell with frame structure type 1, an HARQ-ACK received on the PHICH assigned to a UE in subframe i is associated with the PUSCH transmission in subframe $i-4$.

For FDD-TDD, and serving cell with frame structure type 1, and UE not configured to monitor PDCCH/EPDCCH in another serving cell with frame structure type 2 for scheduling the serving cell, an HARQ-ACK received on the PHICH assigned to a UE in subframe i is associated with the PUSCH transmission in subframe $i-4$.

For FDD-TDD, if a serving cell is a secondary cell with frame structure type 1 and if the UE is configured to monitor PDCCH/EPDCCH in another serving cell with frame structure type 2 for scheduling the serving cell, then an HARQ-ACK received on the PHICH assigned to a UE in subframe i is associated with PUSCH transmission on the serving cell in subframe $i-6$.

For TDD, if the UE is not configured with *EIMTA-MainConfigServCell-r12* for any serving cell and, if a UE is configured with one serving cell, or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same,

- For frame structure type 2 UL/DL configuration 1-6, an HARQ-ACK received on the PHICH assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-k$ as indicated by the following Table 8.3-1.
- For frame structure type 2 UL/DL configuration 0, an HARQ-ACK received on the PHICH in the resource corresponding to $I_{PHICH} = 0$, as defined in subclause 9.1.2, assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-k$ as indicated by the following Table 8.3-1. For frame structure type 2 UL/DL configuration 0, an HARQ-ACK received on the PHICH in the resource corresponding to $I_{PHICH} = 1$, as defined in subclause 9.1.2, assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-6$.

For TDD, if a UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell, or FDD-TDD and serving cell is frame structure type 2,

- For serving cell with an UL-reference UL/DL configuration (defined in subclause 8.0) belonging to $\{1,2,3,4,5,6\}$, an HARQ-ACK received on the PHICH assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-k$ for the serving cell as indicated by the following Table 8.3-1, where "TDD UL/DL Configuration" in Table 8.3-1 refers to the UL-reference UL/DL Configuration.
- For a serving cell with UL-reference UL/DL configuration 0 (defined in subclause 8.0), an HARQ-ACK received on the PHICH in the resource corresponding to $I_{PHICH} = 0$, as defined in subclause 9.1.2, assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-k$ for the serving cell as indicated by the following Table 8.3-1, where "TDD UL/DL Configuration" in Table 8.3-1 refers to the UL-reference UL/DL configuration. For a serving cell with UL-reference UL/DL configuration 0, an HARQ-ACK received on the PHICH in the resource corresponding to $I_{PHICH} = 1$, as defined in subclause 9.1.2, assigned to a UE in subframe i is associated with the PUSCH transmission in the subframe $i-6$ for the serving cell.
- For FDD-TDD, if a serving cell is a secondary cell with UL-reference UL/DL configuration 0 and if the UE is configured to monitor PDCCH/EPDCCH in another serving cell with frame structure type 1 for scheduling the serving cell, for downlink subframe i , if a transport block was transmitted in the associated PUSCH subframe $i-6$ for the serving cell then PHICH resource corresponding to that transport block is not present in subframe i .

Table 8.3-1 *k* for TDD configurations 0-6

| TDD UL/DL Configuration | subframe number <i>i</i> | | | | | | | | | |
|----------------------------|--------------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | 7 | 4 | | | | 7 | 4 | | | |
| 1 | | 4 | | | 6 | | 4 | | | 6 |
| 2 | | | | 6 | | | | | | 6 |
| 3 | 6 | | | | | | | | 6 | 6 |
| 4 | | | | | | | | | 6 | 6 |
| 5 | | | | | | | | | 6 | |
| 6 | 6 | 4 | | | | 7 | 4 | | | 6 |

The physical layer in the UE shall deliver indications to the higher layers as follows:

For FDD, and for TDD with a UE configured with one serving cell, and for TDD with a UE configured with more than one serving cell and with TDD UL/DL configuration of all configured serving cells the same, and UE is not configured with *EIMTA-MainConfigServCell-r12* for any serving cell, for downlink or special subframe *i*, if a transport block was transmitted in the associated PUSCH subframe then:

if ACK is decoded on the PHICH corresponding to that transport block in subframe *i*, or if that transport block is disabled by PDCCH/EPDCCH received in downlink or special subframe *i*, ACK for that transport block shall be delivered to the higher layers; else NACK for that transport block shall be delivered to the higher layers.

For TDD, if the UE is configured with more than one serving cell, and if at least two serving cells have different UL/DL configurations, or the UE is configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD, for downlink or special subframe *i*, if a transport block was transmitted in the associated PUSCH subframe then:

if ACK is decoded on the PHICH corresponding to that transport block in subframe *i*, or if that transport block is disabled by PDCCH/EPDCCH received in downlink or special subframe *i*, ACK for that transport block shall be delivered to the higher layers; or

if a PHICH resource corresponding to that transport block is not present in subframe *i* or if UE is not expected to receive PHICH corresponding to that transport block in subframe *i*, ACK for that transport block shall be delivered to the higher layers.

else NACK for that transport block shall be delivered to the higher layers.

8.4 UE PUSCH hopping procedure

The UE shall perform PUSCH frequency hopping if the single bit Frequency Hopping (FH) field in a corresponding PDCCH/EPDCCH with DCI format 0 is set to 1 and the uplink resource block assignment is type 0 otherwise no PUSCH frequency hopping is performed.

A UE performing PUSCH frequency hopping shall determine its PUSCH Resource Allocation (RA) for the first slot of a subframe (SI) including the lowest index PRB ($n_{PRB}^{SI}(n)$) in subframe n from the resource allocation field in the latest PDCCH/EPDCCH with DCI format 0 for the same transport block. If there is no PDCCH/EPDCCH for the same transport block, the UE shall determine its hopping type based on

- the hopping information in the most recent semi-persistent scheduling assignment PDCCH/EPDCCH, when the initial PUSCH for the same transport block is semi-persistently scheduled or
- the random access response grant for the same transport block, when the PUSCH is initiated by the random access response grant.

The resource allocation field in DCI format 0 excludes either 1 or 2 bits used for hopping information as indicated by Table 8.4-1 below where the number of PUSCH resource blocks is defined as

$$N_{RB}^{PUSCH} = \begin{cases} N_{RB}^{UL} - \tilde{N}_{RB}^{HO} - (N_{RB}^{UL} \bmod 2) & \text{Type 1 PUSCH hopping} \\ N_{RB}^{UL} & \text{Type 2 } N_{sb} = 1 \text{ PUSCH hopping} \\ N_{RB}^{UL} - \tilde{N}_{RB}^{HO} & \text{Type 2 } N_{sb} > 1 \text{ PUSCH hopping} \end{cases}$$

For type 1 and type 2 PUSCH hopping, $\tilde{N}_{RB}^{HO} = N_{RB}^{HO} + 1$ if N_{RB}^{HO} is an odd number where N_{RB}^{HO} defined in [3].

$\tilde{N}_{RB}^{HO} = N_{RB}^{HO}$ in other cases. The size of the resource allocation field in DCI format 0 after excluding either 1 or 2 bits shall be $y = \lceil \log_2(N_{RB}^{UL}(N_{RB}^{UL} + 1)/2) \rceil - N_{UL_hop}$, where $N_{UL_hop} = 1$ or 2 bits. The number of contiguous RBs that can be assigned to a type-1 hopping user is limited to $\lfloor 2^y / N_{RB}^{UL} \rfloor$. The number of contiguous RBs that can be assigned to a type-2 hopping user is limited to $\min(\lfloor 2^y / N_{RB}^{UL} \rfloor, \lfloor N_{RB}^{PUSCH} / N_{sb} \rfloor)$, where the number of sub-bands N_{sb} is given by higher layers.

A UE performing PUSCH frequency hopping shall use one of two possible PUSCH frequency hopping types based on the hopping information. PUSCH hopping type 1 is described in subclause 8.4.1 and type 2 is described in subclause 8.4.2.

Table 8.4-1: Number of Hopping Bits N_{UL_hop} vs. System Bandwidth

| System BW N_{RB}^{UL} | #Hopping bits for 2nd slot RA (N_{UL_hop}) |
|----------------------------|--|
| 6-49 | 1 |
| 50-110 | 2 |

The parameter *Hopping-mode* provided by higher layers determines if PUSCH frequency hopping is "inter-subframe" or "intra and inter-subframe".

8.4.1 Type 1 PUSCH hopping

For PUSCH hopping type 1 the hopping bit or bits indicated in Table 8.4-1 determine $\tilde{n}_{PRB}(i)$ as defined in Table 8.4-2.

The lowest index PRB ($n_{PRB}^{S1}(i)$) of the 1st slot RA in subframe i is defined as $n_{PRB}^{S1}(i) = \tilde{n}_{PRB}^{S1}(i) + \tilde{N}_{RB}^{HO} / 2$, where $n_{PRB}^{S1}(i) = RB_{START}$, and RB_{START} is obtained from the uplink scheduling grant as in subclause 8.4 and subclause 8.1.

The lowest index PRB ($n_{PRB}(i)$) of the 2nd slot RA in subframe i is defined as $n_{PRB}(i) = \tilde{n}_{PRB}(i) + \tilde{N}_{RB}^{HO} / 2$.

The set of physical resource blocks to be used for PUSCH transmission are L_{CRBs} contiguously allocated resource blocks from PRB index $n_{PRB}^{S1}(i)$ for the 1st slot, and from PRB index $n_{PRB}(i)$ for the 2nd slot, respectively, where L_{CRBs} is obtained from the uplink scheduling grant as in subclause 8.4 and subclause 8.1.

If the *Hopping-mode* is "inter-subframe", the 1st slot RA is applied to even CURRENT_TX_NB, and the 2nd slot RA is applied to odd CURRENT_TX_NB, where CURRENT_TX_NB is defined in [8].

8.4.2 Type 2 PUSCH hopping

In PUSCH hopping type 2 the set of physical resource blocks to be used for transmission in slot n_s is given by the scheduling grant together with a predefined pattern according to [3] subclause 5.3.4.

If the system frame number is not acquired by the UE yet, the UE shall not transmit PUSCH with type-2 hopping and $N_{sb} > 1$ for TDD, where N_{sb} is defined in [3].

Table 8.4-2: PDCCH/EPDCCH DCI format 0 hopping bit definition

| System BW N_{RB}^{UL} | Number of Hopping bits | Information in hopping bits | $\tilde{n}_{PRB}(i)$ |
|----------------------------|---------------------------|--------------------------------|---|
| 6 – 49 | 1 | 0 | $\left(\left\lfloor N_{RB}^{PUSCH} / 2 \right\rfloor + \tilde{n}_{PRB}^{S1}(i) \right) \bmod N_{RB}^{PUSCH}$, |
| | | 1 | Type 2 PUSCH Hopping |
| 50 – 110 | 2 | 00 | $\left(\left\lfloor N_{RB}^{PUSCH} / 4 \right\rfloor + \tilde{n}_{PRB}^{S1}(i) \right) \bmod N_{RB}^{PUSCH}$ |
| | | 01 | $\left(- \left\lfloor N_{RB}^{PUSCH} / 4 \right\rfloor + \tilde{n}_{PRB}^{S1}(i) \right) \bmod N_{RB}^{PUSCH}$ |
| | | 10 | $\left(\left\lfloor N_{RB}^{PUSCH} / 2 \right\rfloor + \tilde{n}_{PRB}^{S1}(i) \right) \bmod N_{RB}^{PUSCH}$ |
| | | 11 | Type 2 PUSCH Hopping |

8.5 UE Reference Symbol (RS) procedure

If UL sequence-group hopping or sequence hopping is configured in a serving cell, it applies to all Reference Symbols (SRS, PUSCH and PUCCH RS). If disabling of the sequence-group hopping and sequence hopping is configured for the UE in the serving cell through the higher-layer parameter *Disable-sequence-group-hopping*, the sequence-group hopping and sequence hopping for PUSCH RS are disabled.

8.6 Modulation order, redundancy version and transport block size determination

To determine the modulation order, redundancy version and transport block size for the physical uplink shared channel, the UE shall first

- read the "modulation and coding scheme and redundancy version" field (I_{MCS}), and
- check the "CSI request" bit field, and
- compute the total number of allocated PRBs (N_{PRB}) based on the procedure defined in subclause 8.1, and
- compute the number of coded symbols for control information.

8.6.1 Modulation order and redundancy version determination

For $0 \leq I_{MCS} \leq 28$, the modulation order (Q_m) is determined as follows:

- If the UE is capable of supporting 64QAM in PUSCH and has not been configured by higher layers to transmit only QPSK and 16QAM, the modulation order is given by Q_m in Table 8.6.1-1.
- If the UE is not capable of supporting 64QAM in PUSCH or has been configured by higher layers to transmit only QPSK and 16QAM, Q_m is first read from Table 8.6.1-1. The modulation order is set to $Q_m = \min(4, Q_m)$.
- If the parameter *ttiBundling* provided by higher layers is set to *TRUE*, then the modulation order is set to $Q_m = 2$. Resource allocation size is restricted to $N_{PRB} \leq 3$ applies in this case if the UE does not indicate support by higher layers to operate without it.

For $29 \leq I_{MCS} \leq 31$ the modulation order (Q_m) is determined as follows:

- if DCI format 0 is used and $I_{MCS} = 29$ or, if DCI format 4 is used and only 1 TB is enabled and $I_{MCS} = 29$ for the enabled TB and the signalled number of transmission layers is 1, and if
 - the "CSI request" bit field is 1 bit and the bit is set to trigger an aperiodic report and, $N_{PRB} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one serving cell according to Table 7.2.1-1A, and, $N_{PRB} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for more than one serving cell according to Table 7.2.1-1A and, $N_{PRB} \leq 20$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one CSI process according to Table 7.2.1-1B and $N_{PRB} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for more than one CSI process according to Table 7.2.1-1B and $N_{PRB} \leq 20$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one CSI process or {CSI process, CSI subframe set}-pair according to Table 7.2.1-1C and $N_{PRB} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for more than one CSI process and/or {CSI process, CSI subframe set}-pair according to Table 7.2.1-1C and $N_{PRB} \leq 20$,

then the modulation order is set to $Q_m = 2$.

- Otherwise, the modulation order shall be determined from the DCI transported in the latest PDCCH/EPDCCH with DCI format 0/4 for the same transport block using $0 \leq I_{MCS} \leq 28$. If there is no PDCCH/EPDCCH with DCI format 0/4 for the same transport block using $0 \leq I_{MCS} \leq 28$, the modulation order shall be determined from
 - the most recent semi-persistent scheduling assignment PDCCH/EPDCCH, when the initial PUSCH for the same transport block is semi-persistently scheduled, or,
 - the random access response grant for the same transport block, when the PUSCH is initiated by the random access response grant.

The UE shall use I_{MCS} and Table 8.6.1-1 to determine the redundancy version (rv_{idx}) to use in the physical uplink shared channel.

Table 8.6.1-1: Modulation, TBS index and redundancy version table for PUSCH

| MCS Index I_{MCS} | Modulation Order Q_m | TBS Index I_{TBS} | Redundancy Version rv_{idx} |
|------------------------|---------------------------|------------------------|----------------------------------|
| 0 | 2 | 0 | 0 |
| 1 | 2 | 1 | 0 |
| 2 | 2 | 2 | 0 |
| 3 | 2 | 3 | 0 |
| 4 | 2 | 4 | 0 |
| 5 | 2 | 5 | 0 |
| 6 | 2 | 6 | 0 |
| 7 | 2 | 7 | 0 |
| 8 | 2 | 8 | 0 |
| 9 | 2 | 9 | 0 |
| 10 | 2 | 10 | 0 |
| 11 | 4 | 10 | 0 |
| 12 | 4 | 11 | 0 |
| 13 | 4 | 12 | 0 |
| 14 | 4 | 13 | 0 |
| 15 | 4 | 14 | 0 |
| 16 | 4 | 15 | 0 |
| 17 | 4 | 16 | 0 |
| 18 | 4 | 17 | 0 |
| 19 | 4 | 18 | 0 |
| 20 | 4 | 19 | 0 |
| 21 | 6 | 19 | 0 |
| 22 | 6 | 20 | 0 |
| 23 | 6 | 21 | 0 |
| 24 | 6 | 22 | 0 |
| 25 | 6 | 23 | 0 |
| 26 | 6 | 24 | 0 |
| 27 | 6 | 25 | 0 |
| 28 | 6 | 26 | 0 |
| 29 | reserved | | 1 |
| 30 | | | 2 |
| 31 | | | 3 |

8.6.2 Transport block size determination

For $0 \leq I_{MCS} \leq 28$, the UE shall first determine the TBS index (I_{TBS}) using I_{MCS} and Table 8.6.1-1 except if the transport block is disabled in DCI format 4 as specified below. For a transport block that is not mapped to two-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.1.7.2.1. For a transport block that is mapped to two-layer spatial multiplexing, the TBS is determined by the procedure in subclause 7.17.2.2.

For $29 \leq I_{MCS} \leq 31$,

- if DCI format 0 is used and $I_{\text{MCS}} = 29$ or, if DCI format 4 is used and only 1 TB is enabled and $I_{\text{MCS}} = 29$ for the enabled TB and the number of transmission layers is 1, and if
 - the "CSI request" bit field is 1 bit and is set to trigger an aperiodic CSI report and $N_{\text{PRB}} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one serving cell according to Table 7.2.1-1A, and , $N_{\text{PRB}} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering aperiodic CSI report for more than one serving cell according to Table 7.2.1-1A and, $N_{\text{PRB}} \leq 20$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one CSI process according to Table 7.2.1-1B and $N_{\text{PRB}} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for more than one CSI process according to Table 7.2.1-1B and, $N_{\text{PRB}} \leq 20$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for one CSI process or {CSI process, CSI subframe set}-pair according to Table 7.2.1-1C and $N_{\text{PRB}} \leq 4$ or,
 - the "CSI request" bit field is 2 bits and is triggering an aperiodic CSI report for more than one CSI process and/or {CSI process, CSI subframe set}-pair according to Table 7.2.1-1C and $N_{\text{PRB}} \leq 20$,

then there is no transport block for the UL-SCH and only the control information feedback for the current PUSCH reporting mode is transmitted by the UE.

- Otherwise, the transport block size shall be determined from the initial PDCCH/EPDCCH for the same transport block using $0 \leq I_{\text{MCS}} \leq 28$. If there is no initial PDCCH/EPDCCH with an uplink DCI format for the same transport block using $0 \leq I_{\text{MCS}} \leq 28$, the transport block size shall be determined from
 - the most recent semi-persistent scheduling assignment PDCCH/EPDCCH, when the initial PUSCH for the same transport block is semi-persistently scheduled, or,
 - the random access response grant for the same transport block, when the PUSCH is initiated by the random access response grant.

In DCI format 4 a transport block is disabled if either the combination of $I_{\text{MCS}} = 0$ and $N_{\text{PRB}} > 1$ or the combination of $I_{\text{MCS}} = 28$ and $N_{\text{PRB}} = 1$ is signalled, otherwise the transport block is enabled.

8.6.3 Control information MCS offset determination

Offset values are defined for single codeword PUSCH transmission and multiple codeword PUSCH transmission.

Single codeword PUSCH transmission offsets $\beta_{offset}^{HARQ-ACK}$, β_{offset}^{RI} and β_{offset}^{CQI} shall be configured to values according to Table 8.6.3-1,2,3 with the higher layer signalled indexes $I_{offset}^{HARQ-ACK}$, I_{offset}^{RI} , and I_{offset}^{CQI} , respectively.

Multiple codeword PUSCH transmission offsets $\beta_{offset}^{HARQ-ACK}$, β_{offset}^{RI} and β_{offset}^{CQI} shall be configured to values according to Table 8.6.3-1,2,3 with the higher layer signalled indexes $I_{offset,MC}^{HARQ-ACK}$, $I_{offset,MC}^{RI}$ and $I_{offset,MC}^{CQI}$, respectively.

If the UE is configured with higher layer parameter *UplinkPowerControlDedicated-v12x0* for serving cell *c*, and if a subframe belongs to uplink power control subframe set 2 as indicated by the higher layer parameter *tpc-SubframeSet-r12*, then for that subframe, the UE shall use

- the higher layer indexes $I_{offset,set2}^{HARQ-ACK}$, $I_{offset,set2}^{RI}$ and $I_{offset,set2}^{CQI}$ in place of $I_{offset}^{HARQ-ACK}$, I_{offset}^{RI} , and I_{offset}^{CQI} respectively in Tables 8.6.3-1,2,3, to determine $\beta_{offset}^{HARQ-ACK}$, β_{offset}^{RI} and β_{offset}^{CQI} respectively for single codeword PUSCH transmissions, and
- the higher layer indexes $I_{offset,MC,set2}^{HARQ-ACK}$, $I_{offset,MC,set2}^{RI}$ and $I_{offset,MC,set2}^{CQI}$ in place of $I_{offset,MC}^{HARQ-ACK}$, $I_{offset,MC}^{RI}$ and $I_{offset,MC}^{CQI}$ respectively in Tables 8.6.3-1,2,3, to determine $\beta_{offset}^{HARQ-ACK}$, β_{offset}^{RI} and β_{offset}^{CQI} respectively for multiple codeword PUSCH transmissions.

Table 8.6.3-1: Mapping of HARQ-ACK offset values and the index signalled by higher layers

| $I_{offset}^{HARQ-ACK}$ or $I_{offset,MC}^{HARQ-ACK}$ | $\beta_{offset}^{HARQ-ACK}$ |
|---|-----------------------------|
| 0 | 2.000 |
| 1 | 2.500 |
| 2 | 3.125 |
| 3 | 4.000 |
| 4 | 5.000 |
| 5 | 6.250 |
| 6 | 8.000 |
| 7 | 10.000 |
| 8 | 12.625 |
| 9 | 15.875 |
| 10 | 20.000 |
| 11 | 31.000 |
| 12 | 50.000 |
| 13 | 80.000 |
| 14 | 126.000 |
| 15 | 1.0 |

Table 8.6.3-2: Mapping of RI offset values and the index signalled by higher layers

| I_{offset}^{RI} or $I_{offset,MC}^{RI}$ | β_{offset}^{RI} |
|---|-----------------------|
| 0 | 1.250 |
| 1 | 1.625 |
| 2 | 2.000 |
| 3 | 2.500 |
| 4 | 3.125 |
| 5 | 4.000 |
| 6 | 5.000 |
| 7 | 6.250 |
| 8 | 8.000 |
| 9 | 10.000 |
| 10 | 12.625 |
| 11 | 15.875 |
| 12 | 20.000 |
| 13 | reserved |
| 14 | reserved |
| 15 | reserved |

Table 8.6.3-3: Mapping of CQI offset values and the index signalled by higher layers

| I_{offset}^{CQI} or $I_{offset,MC}^{CQI}$ | β_{offset}^{CQI} |
|---|------------------------|
| 0 | reserved |
| 1 | reserved |
| 2 | 1.125 |
| 3 | 1.250 |
| 4 | 1.375 |
| 5 | 1.625 |
| 6 | 1.750 |
| 7 | 2.000 |
| 8 | 2.250 |
| 9 | 2.500 |
| 10 | 2.875 |
| 11 | 3.125 |
| 12 | 3.500 |
| 13 | 4.000 |
| 14 | 5.000 |
| 15 | 6.250 |

8.7 UE transmit antenna selection

UE transmit antenna selection is configured by higher layers via parameter *ue-TransmitAntennaSelection*.

A UE configured with transmit antenna selection for a serving cell is not expected to

- be configured with more than one antenna port for any uplink physical channel or signal for any configured serving cell, or
- be configured with trigger type 1 SRS transmission on any configured serving cell, or
- be configured with simultaneous PUCCH and PUSCH transmission, or
- be configured with demodulation reference signal for PUSCH with OCC for any configured serving cell (see [3], subclause 5.5.2.1.1), or
- receive DCI Format 0 indicating uplink resource allocation type 1 for any serving cell, or
- be configured with a SCG.

If UE transmit antenna selection is disabled or not supported by the UE, the UE shall transmit from UE port 0.

If closed-loop UE transmit antenna selection is enabled by higher layers the UE shall perform transmit antenna selection for PUSCH in response to the most recent command received via DCI Format 0 in subclause 5.3.3.2 of [4].

If a UE is configured with more than one serving cell, the UE may assume the same transmit antenna port value is indicated in each PDCCH/EPDCCH with DCI format 0 in a given subframe.

If open-loop UE transmit antenna selection is enabled by higher layers, the transmit antenna for PUSCH/SRS to be selected by the UE is not specified.

9 Physical downlink control channel procedures

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG.

9.1 UE procedure for determining physical downlink control channel assignment

9.1.1 PDCCH assignment procedure

The control region of each serving cell consists of a set of CCEs, numbered from 0 to $N_{\text{CCE},k} - 1$ according to subclause 6.8.1 in [3], where $N_{\text{CCE},k}$ is the total number of CCEs in the control region of subframe k .

The UE shall monitor a set of PDCCH candidates on one or more activated serving cells as configured by higher layer signalling for control information, where monitoring implies attempting to decode each of the PDCCHs in the set according to all the monitored DCI formats.

The set of PDCCH candidates to monitor are defined in terms of search spaces, where a search space $S_k^{(L)}$ at aggregation level $L \in \{1,2,4,8\}$ is defined by a set of PDCCH candidates. For each serving cell on which PDCCH is monitored, the CCEs corresponding to PDCCH candidate m of the search space $S_k^{(L)}$ are given by

$$L \left\{ (Y_k + m') \bmod \lfloor N_{\text{CCE},k} / L \rfloor \right\} + i$$

where Y_k is defined below, $i = 0, \dots, L-1$. For the common search space $m' = m$. For the PDCCH UE specific search space, for the serving cell on which PDCCH is monitored, if the monitoring UE is configured with carrier indicator field then $m' = m + M^{(L)} \cdot n_{CI}$ where n_{CI} is the carrier indicator field value, else if the monitoring UE is not configured with carrier indicator field then $m' = m$, where $m = 0, \dots, M^{(L)} - 1$. $M^{(L)}$ is the number of PDCCH candidates to monitor in the given search space.

Note that the carrier indicator field value is the same as *ServCellIndex* given in [11].

The UE shall monitor one common search space in every non-DRX subframe at each of the aggregation levels 4 and 8 on the primary cell.

A UE shall monitor common search space on a cell to decode the PDCCHs necessary to receive MBMS on that cell when configured by higher layers.

If a UE is not configured for EPDCCH monitoring, and if the UE is not configured with a carrier indicator field, then the UE shall monitor one PDCCH UE-specific search space at each of the aggregation levels 1, 2, 4, 8 on each activated serving cell in every non-DRX subframe.

If a UE is not configured for EPDCCH monitoring, and if the UE is configured with a carrier indicator field, then the UE shall monitor one or more UE-specific search spaces at each of the aggregation levels 1, 2, 4, 8 on one or more activated serving cells as configured by higher layer signalling in every non-DRX subframe.

If a UE is configured for EPDCCH monitoring on a serving cell, and if that serving cell is activated, and if the UE is not configured with a carrier indicator field, then the UE shall monitor one PDCCH UE-specific search space at each of the aggregation levels 1, 2, 4, 8 on that serving cell in all non-DRX subframes where EPDCCH is not monitored on that serving cell.

If a UE is configured for EPDCCH monitoring on a serving cell, and if that serving cell is activated, and if the UE is configured with a carrier indicator field, then the UE shall monitor one or more PDCCH UE-specific search spaces at each of the aggregation levels 1, 2, 4, 8 on that serving cell as configured by higher layer signalling in all non-DRX subframes where EPDCCH is not monitored on that serving cell.

The common and PDCCH UE-specific search spaces on the primary cell may overlap.

A UE configured with the carrier indicator field associated with monitoring PDCCH on serving cell c shall monitor PDCCH configured with carrier indicator field and with CRC scrambled by C-RNTI in the PDCCH UE specific search space of serving cell c .

A UE configured with the carrier indicator field associated with monitoring PDCCH on the primary cell shall monitor PDCCH configured with carrier indicator field and with CRC scrambled by SPS C-RNTI in the PDCCH UE specific search space of the primary cell.

The UE shall monitor the common search space for PDCCH without carrier indicator field.

For the serving cell on which PDCCH is monitored, if the UE is not configured with a carrier indicator field, it shall monitor the PDCCH UE specific search space for PDCCH without carrier indicator field, if the UE is configured with a carrier indicator field it shall monitor the PDCCH UE specific search space for PDCCH with carrier indicator field.

A UE is not expected to monitor the PDCCH of a secondary cell if it is configured to monitor PDCCH with carrier indicator field corresponding to that secondary cell in another serving cell. For the serving cell on which PDCCH is monitored, the UE shall monitor PDCCH candidates at least for the same serving cell.

A UE configured to monitor PDCCH candidates with CRC scrambled by C-RNTI or SPS C-RNTI with a common payload size and with the same first CCE index n_{CCE} (as described in subclause 10.1) but with different sets of DCI information fields as defined in [4] in the

- common search space
- PDCCH UE specific search space

on the primary cell shall assume that for the PDCCH candidates with CRC scrambled by C-RNTI or SPS C-RNTI,

- if the UE is configured with the carrier indicator field associated with monitoring the PDCCH on the primary cell, only the PDCCH in the common search space is transmitted by the primary cell;

- otherwise, only the PDCCH in the UE specific search space is transmitted by the primary cell.

A UE configured to monitor PDCCH candidates in a given serving cell with a given DCI format size with CIF, and CRC scrambled by C-RNTI, where the PDCCH candidates may have one or more possible values of CIF for the given DCI format size, shall assume that a PDCCH candidate with the given DCI format size may be transmitted in the given serving cell in any PDCCH UE specific search space corresponding to any of the possible values of CIF for the given DCI format size.

The aggregation levels defining the search spaces are listed in Table 9.1.1-1. The DCI formats that the UE shall monitor depend on the configured transmission mode per each serving cell as defined in subclause 7.1.

Table 9.1.1-1: PDCCH candidates monitored by a UE

| Search space $S_k^{(L)}$ | | | Number of PDCCH candidates $M^{(L)}$ |
|--------------------------|-----------------------|----------------|--------------------------------------|
| Type | Aggregation level L | Size [in CCEs] | |
| UE-specific | 1 | 6 | 6 |
| | 2 | 12 | 6 |
| | 4 | 8 | 2 |
| | 8 | 16 | 2 |
| Common | 4 | 16 | 4 |
| | 8 | 16 | 2 |

For the common search spaces, Y_k is set to 0 for the two aggregation levels $L=4$ and $L=8$.

For the UE-specific search space $S_k^{(L)}$ at aggregation level L , the variable Y_k is defined by

$$Y_k = (A \cdot Y_{k-1}) \bmod D$$

where $Y_{-1} = n_{\text{RNTI}} \neq 0$, $A = 39827$, $D = 65537$ and $k = \lfloor n_s/2 \rfloor$, n_s is the slot number within a radio frame.

The RNTI value used for n_{RNTI} is defined in subclause 7.1 in downlink and subclause 8 in uplink.

9.1.2 PHICH assignment procedure

If a UE is not configured with multiple TAGs, or if a UE is configured with multiple TAGs and PUSCH transmissions scheduled from serving cell c in subframe n are not scheduled by a Random Access Response Grant corresponding to a random access preamble transmission for a secondary cell

- For PUSCH transmissions scheduled from serving cell c in subframe n , the UE shall determine the corresponding PHICH resource of serving cell c in subframe $n+k_{\text{PHICH}}$, where
 - k_{PHICH} is always 4 for FDD.
 - k_{PHICH} is 6 for FDD-TDD and serving cell c frame structure type 2 and the PUSCH transmission is for another serving cell with frame structure type 1.
 - k_{PHICH} is 4 for FDD-TDD and serving cell c frame structure type 1 and the PUSCH transmission is for a serving cell with frame structure type 1.
 - k_{PHICH} is given in table 9.1.2-1 for FDD-TDD and serving cell c frame structure type 1 and the PUSCH transmission is for another serving cell with frame structure type 2.
- For TDD, if the UE is not configured with *EIMTA-MainConfigServCell-r12* for any serving cell and, if the UE is configured with one serving cell, or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same, for PUSCH transmissions scheduled from serving cell c in subframe n , the UE shall determine the corresponding PHICH resource of serving cell c in subframe $n+k_{\text{PHICH}}$, where k_{PHICH} is given in table 9.1.2-1.
- For TDD, if the UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with *EIMTA-MainConfigServCell-r12* for

at least one serving cell , or for FDD-TDD and serving cell c frame structure type 2, for PUSCH transmissions scheduled from serving cell c in subframe n , the UE shall determine the corresponding PHICH resource of serving cell c in subframe $n + k_{PHICH}$, where k_{PHICH} is given in table 9.1.2-1, where the "TDD UL/DL Configuration" in the rest of this subclause refers to the UL-reference UL/DL configuration (defined in subclause 8.0) of the serving cell corresponding to the PUSCH transmission.

If a UE is configured with multiple TAGs, for PUSCH transmissions on subframe n for a secondary cell c scheduled by a Random Access Response grant corresponding to a random access preamble transmission for the secondary cell c ,

- For TDD, if the UE is configured with more than one serving cell and the TDD UL/DL configuration of at least two configured serving cells is not the same, or if the UE is configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD and serving cell c frame structure type 2, the "TDD UL/DL Configuration" in the rest of this subclause refers to the UL-reference UL/DL configuration (defined in subclause 8.0) of secondary cell c .
- If the UE is not configured to monitor PDCCH/EPDCCH with carrier indicator field corresponding to secondary cell c in another serving cell, the UE shall determine the corresponding PHICH resource on the secondary cell c in subframe $n + k_{PHICH}$, where
 - k_{PHICH} is always 4 for FDD and where k_{PHICH} is given in table 9.1.2-1 for TDD.
 - k_{PHICH} is 4 for FDD-TDD and secondary cell c frame structure type 1.
 - k_{PHICH} is given in table 9.1.2-1 for FDD-TDD and secondary cell c frame structure type 2
- If the UE is configured to monitor PDCCH/EPDCCH with carrier indicator field corresponding to secondary cell c in another serving cell $c1$, the UE configured with multiple TAGs shall determine the corresponding PHICH resource on the serving cell $c1$ in subframe $n + k_{PHICH}$, where
 - k_{PHICH} is always 4 for FDD and where k_{PHICH} is given in table 9.1.2-1 for TDD.
 - k_{PHICH} is 4 for FDD-TDD and primary cell frame structure type 1 and frame structure type 1 for secondary cell c and serving cell $c1$
 - k_{PHICH} is given in table 9.1.2-1 for FDD-TDD and serving cell c frame structure type 2
 - k_{PHICH} is 6 for FDD-TDD and serving cell c frame structure type 1 and serving cell $c1$ frame structure type 2

For subframe bundling operation, the corresponding PHICH resource is associated with the last subframe in the bundle.

Table 9.1.2-1: k_{PHICH} for TDD

| TDD UL/DL Configuration | subframe index n | | | | | | | | | |
|-------------------------|--------------------|---|---|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | | | 4 | 7 | 6 | | | 4 | 7 | 6 |
| 1 | | | 4 | 6 | | | | 4 | 6 | |
| 2 | | | 6 | | | | | 6 | | |
| 3 | | | 6 | 6 | 6 | | | | | |
| 4 | | | 6 | 6 | | | | | | |
| 5 | | | 6 | | | | | | | |
| 6 | | | 4 | 6 | 6 | | | 4 | 7 | |

The PHICH resource is identified by the index pair $(n_{PHICH}^{group}, n_{PHICH}^{seq})$ where n_{PHICH}^{group} is the PHICH group number and n_{PHICH}^{seq} is the orthogonal sequence index within the group as defined by:

$$n_{PHICH}^{group} = (I_{PRB_RA} + n_{DMRS}) \bmod N_{PHICH}^{group} + I_{PHICH} N_{PHICH}^{group}$$

$$n_{PHICH}^{seq} = (\lfloor I_{PRB_RA} / N_{PHICH}^{group} \rfloor + n_{DMRS}) \bmod 2N_{SF}^{PHICH}$$

where

- n_{DMRS} is mapped from the cyclic shift for DMRS field (according to Table 9.1.2-2) in the most recent PDCCH/EPDCCH with uplink DCI format [4] for the transport block(s) associated with the corresponding PUSCH transmission. n_{DMRS} shall be set to zero, if there is no PDCCH/EPDCCH with uplink DCI format for the same transport block, and
 - if the initial PUSCH for the same transport block is semi-persistently scheduled, or
 - if the initial PUSCH for the same transport block is scheduled by the random access response grant .
- N_{SF}^{PHICH} is the spreading factor size used for PHICH modulation as described in subclause 6.9.1 in [3].

- $I_{PRB_RA} = \begin{cases} I_{PRB_RA}^{lowest_index} & \text{for the first TB of a PUSCH with associated PDCCH/EPDCCH or for the case of no associated PDCCH/EPDCCH when the number of negatively acknowledged TBs is not equal to the number of TBs indicated in the most recent PDCCH/EPDCCH associated with the corresponding PUSCH} \\ I_{PRB_RA}^{lowest_index} + 1 & \text{for a second TB of a PUSCH with associated PDCCH/EPDCCH} \end{cases}$

where $I_{PRB_RA}^{lowest_index}$ is the lowest PRB index in the first slot of the corresponding PUSCH transmission

- N_{PHICH}^{group} is the number of PHICH groups configured by higher layers as described in subclause 6.9 of [3],
- $I_{PHICH} = \begin{cases} 1 & \text{for TDD UL/DL configuration 0 with PUSCH transmission in subframe } n = 4 \text{ or } 9 \\ 0 & \text{otherwise} \end{cases}$

Table 9.1.2-2: Mapping between n_{DMRS} and the cyclic shift for DMRS field in PDCCH/EPDCCH with uplink DCI format in [4]

| Cyclic Shift for DMRS Field in PDCCH/EPDCCH with uplink DCI format in [4] | n_{DMRS} |
|---|------------|
| 000 | 0 |
| 001 | 1 |
| 010 | 2 |
| 011 | 3 |
| 100 | 4 |
| 101 | 5 |
| 110 | 6 |
| 111 | 7 |

9.1.3 Control Format Indicator (CFI) assignment procedure

PHICH duration is signalled by higher layers according to Table 6.9.3-1 in [3]. The duration signalled puts a lower limit on the size of the control region determined from the control format indicator (CFI). When $N_{RB}^{DL} > 10$, if extended PHICH duration is indicated by higher layers then the UE shall assume that CFI is equal to PHICH duration.

In subframes indicated by higher layers to decode PMCH, when $N_{RB}^{DL} > 10$, a UE may assume that CFI is equal to the value of the higher layer parameter *non-MBSFNregionLength* [11].

9.1.4 EPDCCH assignment procedure

For each serving cell, higher layer signalling can configure a UE with one or two EPDCCH-PRB-sets for EPDCCH monitoring. The PRB-pairs corresponding to an EPDCCH-PRB-set are indicated by higher layers as described in subclause 9.1.4.4. Each EPDCCH-PRB-set consists of set of ECCEs numbered from 0 to $N_{ECCE,p,k} - 1$ where $N_{ECCE,p,k}$ is the number of ECCEs in EPDCCH-PRB-set p of subframe k . Each EPDCCH-PRB-set can be configured for either localized EPDCCH transmission or distributed EPDCCH transmission.

The UE shall monitor a set of EPDCCH candidates on one or more activated serving cells as configured by higher layer signalling for control information, where monitoring implies attempting to decode each of the EPDCCHs in the set according to the monitored DCI formats.

The set of EPDCCH candidates to monitor are defined in terms of EPDCCH UE-specific search spaces.

For each serving cell, the subframes in which the UE monitors EPDCCH UE-specific search spaces are configured by higher layers.

The UE shall not monitor EPDCCH

- For TDD and normal downlink CP, in special subframes for the special subframe configurations 0 and 5 shown in Table 4.2-1 of [3].
- For TDD and extended downlink CP, in special subframes for the special subframe configurations 0, 4 and 7 shown in Table 4.2-1 of [3].
- In subframes indicated by higher layers to decode PMCH.
- For TDD and if the UE is configured with different UL/DL configurations for the primary and a secondary cell, in a downlink subframe on the secondary cell when the same subframe on the primary cell is a special subframe and the UE is not capable of simultaneous reception and transmission on the primary and secondary cells.

An EPDCCH UE-specific search space $ES_k^{(L)}$ at aggregation level $L \in \{1,2,4,8,16,32\}$ is defined by a set of EPDCCH candidates.

For an EPDCCH-PRB-set p , the ECCEs corresponding to EPDCCH candidate m of the search space $ES_k^{(L)}$ are given by

$$L \left\{ \left(Y_{p,k} + \left\lfloor \frac{m \cdot N_{ECCE,p,k}}{L \cdot M_p^{(L)}} \right\rfloor + b \right) \bmod \left\lfloor \frac{N_{ECCE,p,k}}{L} \right\rfloor \right\} + i$$

where

$Y_{p,k}$ is defined below,

$$i = 0, \dots, L-1$$

$b = n_{CI}$ if the UE is configured with a carrier indicator field for the serving cell on which EPDCCH is monitored, otherwise $b = 0$

n_{CI} is the carrier indicator field value,

$$m = 0, 1, \dots, M_p^{(L)} - 1,$$

If the UE is not configured with a carrier indicator field for the serving cell on which EPDCCH is monitored, $M_p^{(L)}$ is the number of EPDCCH candidates to monitor at aggregation level L in EPDCCH-PRB-set p for the serving cell on

which EPDCCH is monitored, as given in Tables 9.1.4-1a, 9.1.4-1b, 9.1.4-2a, 9.1.4-2b, 9.1.4-3a, 9.1.4-3b, 9.1.4-4a, 9.4.4-4b, 9.1.4-5a, 9.1.4-5b below; otherwise, $M_p^{(L)}$ is the number of EPDCCH candidates to monitor at aggregation level L in EPDCCH-PRB-set p for the serving cell indicated by n_{CI} .

Note that the carrier indicator field value is the same as *ServCellIndex* given in [11].

A UE is not expected to monitor an EPDCCH candidate, if an ECCE corresponding to that EPDCCH candidate is mapped to a PRB pair that overlaps in frequency with a transmission of either PBCH or primary or secondary synchronization signals in the same subframe.

If a UE is configured with two EPDCCH-PRB-sets with the same $n_{ID,i}^{EPDCCH}$ value (where $n_{ID,i}^{EPDCCH}$ is defined in subclause 6.10.3A.1 in [3]), if the UE receives an EPDCCH candidate with a given DCI payload size corresponding to one of the EPDCCH-PRB-sets and mapped only to a given set of REs (as described in subclause 6.8A.5 in [3]), and if the UE is also configured to monitor an EPDCCH candidate with the same DCI payload size and corresponding to the other EPDCCH-PRB-set and which is mapped only to the same set of REs, and if the number of the first ECCE of the received EPDCCH candidate is used for determining PUCCH resource for HARQ-ACK transmission (as described in subclause 10.1.2 and subclause 10.1.3), the number of the first ECCE shall be determined based on EPDCCH-PRB-set $p = 0$.

The variable $Y_{p,k}$ is defined by

$$Y_{p,k} = (A_p \cdot Y_{p,k-1}) \bmod D$$

where $Y_{p,-1} = n_{RNTI} \neq 0$, $A_0 = 39827$, $A_1 = 39829$, $D = 65537$ and $k = \lfloor n_s/2 \rfloor$, n_s is the slot number within a radio frame. The RNTI value used for n_{RNTI} is defined in subclause 7.1 in downlink and subclause 8 in uplink. The DCI formats that the UE shall monitor depend on the configured transmission mode per each serving cell as defined in subclause 7.1.

The aggregation levels defining the search spaces and the number of monitored EPDCCH candidates is given as follows

- For a UE configured with only one EPDCCH-PRB-set for distributed transmission, the aggregation levels defining the search spaces and the number of monitored EPDCCH candidates are listed in Table 9.1.4-1a, Table 9.1.4-1b.
- For a UE configured with only one EPDCCH-PRB-set for localized transmission, the aggregation levels defining the search spaces and the number of monitored EPDCCH candidates are listed in Table 9.1.4-2a, Table 9.1.4-2b.
- For a UE configured with two EPDCCH-PRB-sets for distributed transmission, the aggregation levels defining the search spaces and the number of monitored EPDCCH candidates are listed in Table 9.1.4-3a, 9.1.4-3b.
- For a UE configured with two EPDCCH-PRB-sets for localized transmission, the aggregation levels defining the search spaces and the number of monitored EPDCCH candidates are listed in Table 9.1.4-4a, 9.4.4-4b.
- For a UE configured with one EPDCCH-PRB-set for distributed transmission, and one EPDCCH-PRB-set for localized transmission, the aggregation levels defining the search spaces and the number of monitored EPDCCH candidates are listed in Table 9.1.4-5a, 9.1.4-5b.

If the UE is not configured with a carrier indicator field for the serving cell on which EPDCCH is monitored,

$\hat{N}_{RB}^{DL} = N_{RB}^{DL}$ of the serving cell on which EPDCCH is monitored. If the UE is configured with a carrier indicator field for the serving cell on which EPDCCH is monitored, $\hat{N}_{RB}^{DL} = N_{RB}^{DL}$ of the serving cell indicated by n_{CI} .

For Tables 9.1.4-1a, 9.1.4-1b, 9.1.4-2a, 9.1.4-2b, 9.1.4-3a, 9.1.4-3b, 9.1.4-4a, 9.4.4-4b, 9.1.4-5a, 9.1.4-5b

- Case 1 applies
 - for normal subframes and normal downlink CP when DCI formats 2/2A/2B/2C/2D are monitored and $\hat{N}_{RB}^{DL} \geq 25$, or

- for special subframes with special subframe configuration 3,4,8 and normal downlink CP when DCI formats 2/2A/2B/2C/2D are monitored and $\hat{N}_{RB}^{DL} \geq 25$, or
- for normal subframes and normal downlink CP when DCI formats 1A/1B/1D/1/2/2A/2B/2C/2D/0/4/5 are monitored, and when $n_{EPDCCH} < 104$ (n_{EPDCCH} defined in subclause 6.8A.1 in [3]), or
- for special subframes with special subframe configuration 3, 4, 8 and normal downlink CP when DCI formats 1A/1B/1D/1/2A/2/2B/2C/2D/0/4/5 are monitored, and when $n_{EPDCCH} < 104$ (n_{EPDCCH} defined in subclause 6.8A.1 in [3]);
- Case 2 applies
 - for normal subframes and extended downlink CP when DCI formats 1A/1B/1D/1/2A/2/2B/2C/2D/0/4/5 are monitored or,
 - for special subframes with special subframe configuration 1,2,6,7,9 and normal downlink CP when DCI formats 1A/1B/1D/1/2A/2/2B/2C/2D/0/4/5 are monitored , or
 - for special subframes with special subframe configuration 1,2,3,5,6 and extended downlink CP when DCI formats 1A/1B/1D/1/2A/2/2B/2C/2D/0/4/5 are monitored;
- otherwise
 - Case 3 is applied.

$N_{RB}^{X_p}$ is the number of PRB-pairs constituting EPDCCH-PRB-set p .

Table 9.1.4-1a: EPDCCH candidates monitored by a UE (One Distributed EPDCCH-PRB-set - Case1, Case 2)

| $N_{RB}^{X_p}$ | Number of EPDCCH candidates $M_p^{(L)}$ for Case 1 | | | | | Number of EPDCCH candidates $M_p^{(L)}$ for Case 2 | | | | |
|----------------|--|-----|-----|------|------|--|-----|-----|-----|------|
| | L=2 | L=4 | L=8 | L=16 | L=32 | L=1 | L=2 | L=4 | L=8 | L=16 |
| | 2 | 4 | 2 | 1 | 0 | 0 | 4 | 2 | 1 | 0 |
| 4 | 8 | 4 | 2 | 1 | 0 | 8 | 4 | 2 | 1 | 0 |
| 8 | 6 | 4 | 3 | 2 | 1 | 6 | 4 | 3 | 2 | 1 |

Table 9.1.4-1b: EPDCCH candidates monitored by a UE (One Distributed EPDCCH-PRB-set – Case 3)

| $N_{RB}^{X_p}$ | Number of EPDCCH candidates $M_p^{(L)}$ for Case 3 | | | | |
|----------------|--|-----|-----|-----|------|
| | L=1 | L=2 | L=4 | L=8 | L=16 |
| 2 | 8 | 4 | 2 | 1 | 0 |
| 4 | 4 | 5 | 4 | 2 | 1 |
| 8 | 4 | 4 | 4 | 2 | 2 |

Table 9.1.4-2a: EPDCCH candidates monitored by a UE (One Localized EPDCCH-PRB-set - Case1, Case 2)

| $N_{RB}^{X_p}$ | Number of EPDCCH candidates $M_p^{(L)}$ for Case 1 | | | | Number of EPDCCH candidates $M_p^{(L)}$ for Case 2 | | | |
|----------------|--|-----|-----|------|--|-----|-----|-----|
| | L=2 | L=4 | L=8 | L=16 | L=1 | L=2 | L=4 | L=8 |
| 2 | 4 | 2 | 1 | 0 | 4 | 2 | 1 | 0 |
| 4 | 8 | 4 | 2 | 1 | 8 | 4 | 2 | 1 |
| 8 | 6 | 6 | 2 | 2 | 6 | 6 | 2 | 2 |

**Table 9.1.4-2b: EPDCCH candidates monitored by a UE
(One Localized EPDCCH-PRB-set – Case 3)**

| $N_{RB}^{X_p}$ | Number of EPDCCH candidates $M_p^{(L)}$ for Case 3 | | | |
|----------------|---|-----|-----|-----|
| | L=1 | L=2 | L=4 | L=8 |
| 2 | 8 | 4 | 2 | 1 |
| 4 | 6 | 6 | 2 | 2 |
| 8 | 6 | 6 | 2 | 2 |

**Table 9.1.4-3a: EPDCCH candidates monitored by a UE
(Two Distributed EPDCCH-PRB-sets - Case1, Case 2)**

| $N_{RB}^{X_{p1}}$ | $N_{RB}^{X_{p2}}$ | Number of EPDCCH candidates $[M_{p1}^{(L)}, M_{p2}^{(L)}]$ for Case 1 | | | | | Number of EPDCCH candidates $[M_{p1}^{(L)}, M_{p2}^{(L)}]$ for Case 2 | | | | |
|-------------------|-------------------|--|-----|-----|------|------|--|-----|-----|-----|------|
| | | L=2 | L=4 | L=8 | L=16 | L=32 | L=1 | L=2 | L=4 | L=8 | L=16 |
| 2 | 2 | 4,4 | 2,2 | 1,1 | 0,0 | 0,0 | 4,4 | 2,2 | 1,1 | 0,0 | 0,0 |
| 4 | 4 | 3,3 | 3,3 | 1,1 | 1,1 | 0,0 | 3,3 | 3,3 | 1,1 | 1,1 | 0,0 |
| 8 | 8 | 3,3 | 2,2 | 1,1 | 1,1 | 1,1 | 3,3 | 2,2 | 1,1 | 1,1 | 1,1 |
| 4 | 2 | 5,3 | 3,2 | 1,1 | 1,0 | 0,0 | 5,3 | 3,2 | 1,1 | 1,0 | 0,0 |
| 8 | 2 | 4,2 | 4,2 | 1,1 | 1,0 | 1,0 | 4,2 | 4,2 | 1,1 | 1,0 | 1,0 |
| 8 | 4 | 3,3 | 2,2 | 2,1 | 1,1 | 1,0 | 3,3 | 2,2 | 2,1 | 1,1 | 1,0 |

**Table 9.1.4-3b: EPDCCH candidates monitored by a UE
(Two Distributed EPDCCH-PRB-sets – Case 3)**

| $N_{RB}^{X_{p1}}$ | $N_{RB}^{X_{p2}}$ | Number of EPDCCH candidates $[M_{p1}^{(L)}, M_{p2}^{(L)}]$ for Case 3 | | | | |
|-------------------|-------------------|--|-----|-----|-----|------|
| | | L=1 | L=2 | L=4 | L=8 | L=16 |
| 2 | 2 | 2,2 | 3,3 | 2,2 | 1,1 | 0,0 |
| 4 | 4 | 2,2 | 2,2 | 2,2 | 1,1 | 1,1 |
| 8 | 8 | 2,2 | 2,2 | 2,2 | 1,1 | 1,1 |
| 4 | 2 | 3,1 | 3,2 | 3,1 | 1,1 | 1,0 |
| 8 | 2 | 3,1 | 4,1 | 3,1 | 1,1 | 1,0 |
| 8 | 4 | 2,2 | 2,2 | 2,2 | 1,1 | 1,1 |

**Table 9.1.4-4a: EPDCCH candidates monitored by a UE
(Two Localized EPDCCH-PRB-sets - Case1, Case 2)**

| $N_{RB}^{X_{p1}}$ | $N_{RB}^{X_{p2}}$ | Number of EPDCCH candidates $[M_{p1}^{(L)}, M_{p2}^{(L)}]$ for Case 1 | | | | Number of EPDCCH candidates $[M_{p1}^{(L)}, M_{p2}^{(L)}]$ for Case 2 | | | |
|-------------------|-------------------|--|-----|-----|------|--|-----|-----|-----|
| | | L=2 | L=4 | L=8 | L=16 | L=1 | L=2 | L=4 | L=8 |
| 2 | 2 | 4,4 | 2,2 | 1,1 | 0,0 | 4,4 | 2,2 | 1,1 | 0,0 |
| 4 | 4 | 3,3 | 3,3 | 1,1 | 1,1 | 3,3 | 3,3 | 1,1 | 1,1 |
| 8 | 8 | 3,3 | 3,3 | 1,1 | 1,1 | 3,3 | 3,3 | 1,1 | 1,1 |
| 4 | 2 | 4,3 | 4,2 | 1,1 | 1,0 | 4,3 | 4,2 | 1,1 | 1,0 |
| 8 | 2 | 5,2 | 4,2 | 1,1 | 1,0 | 5,2 | 4,2 | 1,1 | 1,0 |
| 8 | 4 | 3,3 | 3,3 | 1,1 | 1,1 | 3,3 | 3,3 | 1,1 | 1,1 |

Table 9.1.4-4b: EPDCCH candidates monitored by a UE (Two Localized EPDCCH-PRB-sets – Case 3)

| $N_{RB}^{Xp_1}$ | $N_{RB}^{Xp_2}$ | Number of EPDCCH candidates $[M_{p_1}^{(L)}, M_{p_2}^{(L)}]$ for Case 3 | | | |
|-----------------|-----------------|--|-----|-----|-----|
| | | L=1 | L=2 | L=4 | L=8 |
| 2 | 2 | 3,3 | 3,3 | 1,1 | 1,1 |
| 4 | 4 | 3,3 | 3,3 | 1,1 | 1,1 |
| 8 | 8 | 3,3 | 3,3 | 1,1 | 1,1 |
| 4 | 2 | 4,2 | 4,2 | 1,1 | 1,1 |
| 8 | 2 | 4,2 | 4,2 | 1,1 | 1,1 |
| 8 | 4 | 3,3 | 3,3 | 1,1 | 1,1 |

Table 9.1.4-5a: EPDCCH candidates monitored by a UE (NOTE)

| $N_{RB}^{Xp_1}$ | $N_{RB}^{Xp_2}$ | Number of EPDCCH candidates $[M_{p_1}^{(L)}, M_{p_2}^{(L)}]$ for Case 1 | | | | | Number of EPDCCH candidates $[M_{p_1}^{(L)}, M_{p_2}^{(L)}]$ for Case 2 | | | | |
|-----------------|-----------------|--|-----|-----|------|------|--|-----|-----|-----|------|
| | | L=2 | L=4 | L=8 | L=16 | L=32 | L=1 | L=2 | L=4 | L=8 | L=16 |
| 2 | 2 | 4,4 | 2,2 | 1,1 | 0,0 | 0,0 | 4,4 | 2,2 | 1,1 | 0,0 | 0,0 |
| 4 | 4 | 4,2 | 4,3 | 0,2 | 0,1 | 0,0 | 4,2 | 4,3 | 0,2 | 0,1 | 0,0 |
| 8 | 8 | 4,1 | 4,2 | 0,2 | 0,2 | 0,1 | 4,1 | 4,2 | 0,2 | 0,2 | 0,1 |
| 2 | 4 | 4,3 | 2,4 | 0,2 | 0,1 | 0,0 | 4,3 | 2,4 | 0,2 | 0,1 | 0,0 |
| 2 | 8 | 4,1 | 2,2 | 0,4 | 0,2 | 0,1 | 4,1 | 2,2 | 0,4 | 0,2 | 0,1 |
| 4 | 2 | 5,2 | 4,2 | 1,1 | 1,0 | 0,0 | 5,2 | 4,2 | 1,1 | 1,0 | 0,0 |
| 4 | 8 | 4,1 | 4,2 | 0,2 | 0,2 | 0,1 | 4,1 | 4,2 | 0,2 | 0,2 | 0,1 |
| 8 | 2 | 5,1 | 4,2 | 2,1 | 1,0 | 0,0 | 5,1 | 4,2 | 2,1 | 1,0 | 0,0 |
| 8 | 4 | 6,1 | 4,2 | 0,2 | 0,1 | 0,0 | 6,1 | 4,2 | 0,2 | 0,1 | 0,0 |

NOTE: One localized EPDCCH-PRB-set and one distributed EPDCCH-PRB-set, - Case1, Case 2;
 p_1 is the identity of the localized EPDCCH-PRB-set,
 p_2 is the identity of the distributed EPDCCH-PRB-set

Table 9.1.4-5b: EPDCCH candidates monitored by a UE (NOTE)

| $N_{RB}^{Xp_1}$ | $N_{RB}^{Xp_2}$ | Number of EPDCCH candidates $[M_{p_1}^{(L)}, M_{p_2}^{(L)}]$ for Case 3 | | | | |
|-----------------|-----------------|--|-----|-----|-----|------|
| | | L=1 | L=2 | L=4 | L=8 | L=16 |
| 2 | 2 | 4,1 | 4,2 | 2,2 | 0,1 | 0,0 |
| 4 | 4 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |
| 8 | 8 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |
| 2 | 4 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |
| 2 | 8 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |
| 4 | 2 | 4,1 | 4,1 | 2,2 | 1,1 | 0,0 |
| 4 | 8 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |
| 8 | 2 | 4,1 | 4,1 | 4,1 | 0,1 | 0,0 |
| 8 | 4 | 4,1 | 4,1 | 2,2 | 0,1 | 0,1 |

NOTE: One localized EPDCCH-PRB-set and one distributed EPDCCH-PRB-set - Case 3);
 p_1 is the identity of the localized EPDCCH-PRB-set,
 p_2 is the identity of the distributed EPDCCH-PRB-set)

If the UE is not configured with a carrier indicator field, then the UE shall monitor one EPDCCH UE-specific search space at each of the aggregation levels given by Tables 9.1.4-1a to 9.1.4-5b on each activated serving cell for which it is configured to monitor EPDCCH.

If a UE is configured for EPDCCH monitoring, and if the UE is configured with a carrier indicator field, then the UE shall monitor one or more EPDCCH UE-specific search spaces at each of the aggregation levels given by Tables 9.1.4-1a to 9.1.4-5b on one or more activated serving cells as configured by higher layer signalling.

A UE configured with the carrier indicator field associated with monitoring EPDCCH on serving cell c shall monitor EPDCCH configured with carrier indicator field and with CRC scrambled by C-RNTI in the EPDCCH UE specific search space of serving cell c .

A UE configured with the carrier indicator field associated with monitoring EPDCCH on the primary cell shall monitor EPDCCH configured with carrier indicator field and with CRC scrambled by SPS C-RNTI in the EPDCCH UE specific search space of the primary cell.

For the serving cell on which EPDCCH is monitored, if the UE is not configured with a carrier indicator field, it shall monitor the EPDCCH UE specific search space for EPDCCH without carrier indicator field, if the UE is configured with a carrier indicator field it shall monitor the EPDCCH UE specific search space for EPDCCH with carrier indicator field.

A UE is not expected to monitor the EPDCCH of a secondary cell if it is configured to monitor EPDCCH with carrier indicator field corresponding to that secondary cell in another serving cell. For the serving cell on which EPDCCH is monitored, the UE shall monitor EPDCCH candidates at least for the same serving cell.

A UE configured to monitor EPDCCH candidates in a given serving cell with a given DCI format size with CIF, and CRC scrambled by C-RNTI, where the EPDCCH candidates may have one or more possible values of CIF for the given DCI format size, shall assume that an EPDCCH candidate with the given DCI format size may be transmitted in the given serving cell in any EPDCCH UE specific search space corresponding to any of the possible values of CIF for the given DCI format size.

For the serving cell on which EPDCCH is monitored, a UE is not required to monitor the EPDCCH in a subframe which is configured by higher layers to be part of a positioning reference signal occasion if the positioning reference signal occasion is only configured within MBSFN subframes and the cyclic prefix length used in subframe #0 is normal cyclic prefix.

A UE may assume the same c_{init} value (described in subclause 6.10.3A.1 of [3]) is used for antenna ports 107,108 while monitoring an EPDCCH candidate associated with either antenna port 107 or antenna port 108.

A UE may assume the same c_{init} value (described in subclause 6.10.3A.1 of [3]) is used for antenna ports 109,110 while monitoring an EPDCCH candidate associated with either antenna port 109 or antenna port 110.

9.1.4.1 EPDCCH starting position

For a given serving cell, if the UE is configured via higher layer signalling to receive PDSCH data transmissions according to transmission modes 1-9,

- if the UE is configured with a higher layer parameter *epdcch-StartSymbol-r11*,
 - the starting OFDM symbol for EPDCCH given by index $l_{\text{EPDCCHStart}}$ in the first slot in a subframe is determined from the higher layer parameter,
- otherwise
 - the starting OFDM symbol for EPDCCH given by index $l_{\text{EPDCCHStart}}$ in the first slot in a subframe is given by the CFI value in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} > 10$, and $l_{\text{EPDCCHStart}}$ is given by the CFI value+1 in the subframe of the given serving cell when $N_{\text{RB}}^{\text{DL}} \leq 10$

For a given serving cell, if the UE is configured via higher layer signalling to receive PDSCH data transmissions according to transmission mode 10, for each EPDCCH-PRB-set, the starting OFDM symbol for monitoring EPDCCH in subframe k is determined from the higher layer parameter *pdsch-Start-r11* (defined in subclause 9.1.4.3) as follows

- if the value of the parameter *pdsch-Start-r11* belongs to {1,2,3,4},
 - $l'_{\text{EPDCCHStart}}$ is given by the higher layer parameter *pdsch-Start-r11*
- otherwise

- $l'_{EPDCCHStart}$ is given by the CFI value in subframe k of the given serving cell when $N_{RB}^{DL} > 10$, and
- $l'_{EPDCCHStart}$ is given by the CFI value+1 in subframe k of the given serving cell when $N_{RB}^{DL} \leq 10$
- if subframe k is indicated by the higher layer parameter $mbsfn-SubframeConfigList-r11$ (defined in subclause 9.1.4.3), or if subframe k is subframe 1 or 6 for frame structure type 2,
 - $l_{EPDCCHStart} = \min(2, l'_{EPDCCHStart})$,
- otherwise
 - $l_{EPDCCHStart} = l'_{EPDCCHStart}$.

9.1.4.2 Antenna ports quasi co-location for EPDCCH

For a given serving cell, if the UE is configured via higher layer signalling to receive PDSCH data transmissions according to transmission modes 1-9, and if the UE is configured to monitor EPDCCH,

- the UE may assume the antenna ports 0 – 3, 107 – 110 of the serving cell are quasi co-located (as defined in [3]) with respect to Doppler shift, Doppler spread, average delay, and delay spread.

For a given serving cell, if the UE is configured via higher layer signalling to receive PDSCH data transmissions according to transmission mode 10, and if the UE is configured to monitor EPDCCH, for each EPDCCH-PRB-set,

- if the UE is configured by higher layers to decode PDSCH according to quasi co-location Type-A as described in subclause 7.1.10
 - the UE may assume the antenna ports 0 – 3, 107 – 110 of the serving cell are quasi co-located (as defined in [3]) with respect to Doppler shift, Doppler spread, average delay, and delay spread.
- if the UE is configured by higher layers to decode PDSCH according to quasi co-location Type-B as described in subclause 7.1.10
 - the UE may assume antenna ports 15 – 22 corresponding to the higher layer parameter $qcl-CSI-RS-ConfigNZPId-r11$ (defined in subclause 9.1.4.3) and antenna ports 107-110 are quasi co-located (as defined in [3]) with respect to Doppler shift, Doppler spread, average delay, and delay spread.

9.1.4.3 Resource mapping parameters for EPDCCH

For a given serving cell, if the UE is configured via higher layer signalling to receive PDSCH data transmissions according to transmission mode 10, and if the UE is configured to monitor EPDCCH, for each EPDCCH-PRB-set, the UE shall use the parameter set indicated by the higher layer parameter $re-MappingQCL-ConfigId-r11$ for determining the EPDCCH RE mapping (defined in subclause 6.8A.5 of [3]) and EPDCCH antenna port quasi co-location. The following parameters for determining EPDCCH RE mapping (as described in subclause 6.8A.5 of [3]) and EPDCCH antenna port quasi co-location are included in the parameter set:

- $crs-PortsCount-r11$.
- $crs-FreqShift-r11$.
- $mbsfn-SubframeConfigList-r11$.
- $csi-RS-ConfigZPID-r11$.
- $pdsch-Start-r11$.
- $qcl-CSI-RS-ConfigNZPId-r11$.
- $csi-RS-ConfigZPID-Second-r12$ if the UE is configured with CSI subframe sets $C_{CSI,0}$ and $C_{CSI,1}$ by the higher layer parameter $csi-SubframePatternConfig-r12$ for the serving cell.

9.1.4.4 PRB-pair indication for EPDCCH

For a given serving cell, for each EPDCCH-PRB-pair set p , the UE is configured with a higher layer parameter *resourceBlockAssignment-r11* indicating a combinatorial index r corresponding to the PRB index $\{k_i\}_{i=0}^{N_{RB}^{X_p}-1}$,

($1 \leq k_i \leq N_{RB}^{DL}$, $k_i < k_{i+1}$) and given by equation $r = \sum_{i=0}^{N_{RB}^{X_p}-1} \binom{N_{RB}^{DL} - k_i}{N_{RB}^{X_p} - i}$, where N_{RB}^{DL} is the number of PRB pairs

associated with the downlink bandwidth, $N_{RB}^{X_p}$ is the number of PRB-pairs constituting EPDCCH-PRB-set p , and is

configured by the higher layer parameter *numberPRBPairs-r11*, and $\binom{x}{y} = \begin{cases} \binom{x}{y} & x \geq y \\ 0 & x < y \end{cases}$ is the extended binomial

coefficient, resulting in unique label $r \in \left\{ 0, \dots, \binom{N_{RB}^{DL}}{N_{RB}^{X_p}} - 1 \right\}$.

9.2 PDCCH/EPDCCH validation for semi-persistent scheduling

A UE shall validate a Semi-Persistent Scheduling assignment PDCCH only if all the following conditions are met:

- the CRC parity bits obtained for the PDCCH payload are scrambled with the Semi-Persistent Scheduling C-RNTI
- the new data indicator field is set to '0'. In case of DCI formats 2, 2A, 2B, 2C and 2D, the new data indicator field refers to the one for the enabled transport block.

A UE shall validate a Semi-Persistent Scheduling assignment EPDCCH only if all the following conditions are met:

- the CRC parity bits obtained for the EPDCCH payload are scrambled with the Semi-Persistent Scheduling C-RNTI
- the new data indicator field is set to '0'. In case of DCI formats 2, 2A, 2B, 2C and 2D, the new data indicator field refers to the one for the enabled transport block.

Validation is achieved if all the fields for the respective used DCI format are set according to Table 9.2-1 or Table 9.2-1A.

If validation is achieved, the UE shall consider the received DCI information accordingly as a valid semi-persistent activation or release.

If validation is not achieved, the received DCI format shall be considered by the UE as having been received with a non-matching CRC.

Table 9.2-1: Special fields for Semi-Persistent Scheduling Activation PDCCH/EPDCCH Validation

| | DCI format 0 | DCI format 1/1A | DCI format 2/2A/2B/2C/2D |
|--|-------------------|---|---|
| TPC command for scheduled PUSCH | set to '00' | N/A | N/A |
| Cyclic shift DM RS | set to '000' | N/A | N/A |
| Modulation and coding scheme and redundancy version | MSB is set to '0' | N/A | N/A |
| HARQ process number | N/A | FDD: set to '000' TDD: set to '0000' | FDD: set to '000' TDD: set to '0000' |
| Modulation and coding scheme | N/A | MSB is set to '0' | For the enabled transport block: MSB is set to '0' |
| Redundancy version | N/A | set to '00' | For the enabled transport block: set to '00' |

Table 9.2-1A: Special fields for Semi-Persistent Scheduling Release PDCCH/EPDCCH Validation

| | DCI format 0 | DCI format 1A |
|--|-----------------|---|
| TPC command for scheduled PUSCH | set to '00' | N/A |
| Cyclic shift DM RS | set to '000' | N/A |
| Modulation and coding scheme and redundancy version | set to '11111' | N/A |
| Resource block assignment and hopping resource allocation | Set to all '1's | N/A |
| HARQ process number | N/A | FDD: set to '000' TDD: set to '0000' |
| Modulation and coding scheme | N/A | set to '11111' |
| Redundancy version | N/A | set to '00' |
| Resource block assignment | N/A | Set to all '1's |

For the case that the DCI format indicates a semi-persistent downlink scheduling activation, the TPC command for PUCCH field shall be used as an index to one of the four PUCCH resource values configured by higher layers, with the mapping defined in Table 9.2-2

Table 9.2-2: PUCCH resource value for downlink semi-persistent scheduling

| Value of 'TPC command for PUCCH' | $n_{\text{PUCCH}}^{(1,p)}$ |
|----------------------------------|---|
| '00' | The first PUCCH resource value configured by the higher layers |
| '01' | The second PUCCH resource value configured by the higher layers |
| '10' | The third PUCCH resource value configured by the higher layers |
| '11' | The fourth PUCCH resource value configured by the higher layers |

9.3 PDCCH/EPDCCH control information procedure

A UE shall discard the PDCCH/EPDCCH if consistent control information is not detected.

10 Physical uplink control channel procedures

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.
- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG.

10.1 UE procedure for determining physical uplink control channel assignment

If the UE is configured for a single serving cell and is not configured for simultaneous PUSCH and PUCCH transmissions, then in subframe n uplink control information (UCI) shall be transmitted

- on PUCCH using format 1/1a/1b/3 or 2/2a/2b if the UE is not transmitting PUSCH
- on PUSCH if the UE is transmitting PUSCH in subframe n unless the PUSCH transmission corresponds to a Random Access Response Grant or a retransmission of the same transport block as part of the contention based random access procedure, in which case UCI is not transmitted

If the UE is configured for a single serving cell and simultaneous PUSCH and PUCCH transmission, then in subframe n UCI shall be transmitted

- on PUCCH using format 1/1a/1b/3 if the UCI consists only of HARQ-ACK and/or SR
- on PUCCH using format 2 if the UCI consists only of periodic CSI
- on PUCCH using format 2/2a/2b/3 if the UCI consists of periodic CSI and HARQ-ACK and if the UE is not transmitting PUSCH
- on PUCCH and PUSCH if the UCI consists of HARQ-ACK/HARQ-ACK+SR/positive SR and periodic/aperiodic CSI and if the UE is transmitting PUSCH in subframe n , in which case the HARQ-ACK/HARQ-ACK+SR/positive SR is transmitted on PUCCH using format 1/1a/1b/3 and the periodic/aperiodic CSI transmitted on PUSCH unless the PUSCH transmission corresponds to a Random Access Response Grant or a retransmission of the same transport block as part of the contention based random access procedure, in which case periodic/aperiodic CSI is not transmitted

If the UE is configured with more than one serving cell and is not configured for simultaneous PUSCH and PUCCH transmission, then in subframe n UCI shall be transmitted

- on PUCCH using format 1/1a/1b/3 or 2/2a/2b if the UE is not transmitting PUSCH
- on PUSCH of the serving cell given in subclause 7.2.1 if the UCI consists of aperiodic CSI or aperiodic CSI and HARQ-ACK
- on primary cell PUSCH if the UCI consists of periodic CSI and/or HARQ-ACK and if the UE is transmitting on the primary cell PUSCH in subframe n unless the primary cell PUSCH transmission corresponds to a Random Access Response Grant or a retransmission of the same transport block as part of the contention based random access procedure, in which case UCI is not transmitted
- on PUSCH of the secondary cell with smallest *SCellIndex* if the UCI consists of periodic CSI and/or HARQ-ACK and if the UE is not transmitting PUSCH on primary cell but is transmitting PUSCH on at least one secondary cell

If the UE is configured with more than one serving cell and simultaneous PUSCH and PUCCH transmission, then in subframe n UCI shall be transmitted

- on PUCCH using format 1/1a/1b/3 if the UCI consists only of HARQ-ACK and/or SR

- on PUCCH using format 2 if the UCI consists only of periodic CSI
- as described in subclause 10.1.1, if the UCI consists of periodic CSI and HARQ-ACK and if the UE is not transmitting on PUSCH
- on PUCCH and primary cell PUSCH if the UCI consists of HARQ-ACK and periodic CSI and the UE is transmitting PUSCH on the primary cell, in which case the HARQ-ACK is transmitted on PUCCH using format 1a/1b/3 and the periodic CSI is transmitted on PUSCH unless the primary cell PUSCH transmission corresponds to a Random Access Response Grant or a retransmission of the same transport block as part of the contention based random access procedure, in which case periodic CSI is not transmitted
- on PUCCH and PUSCH of the secondary cell with the smallest *SCellIndex* if the UCI consists of HARQ-ACK and periodic CSI and if the UE is not transmitting PUSCH on primary cell but is transmitting PUSCH on at least one secondary cell, in which case, the HARQ-ACK is transmitted on PUCCH using format 1a/1b/3 and the periodic CSI is transmitted on PUSCH
- on PUCCH and PUSCH if the UCI consists of HARQ-ACK/HARQ-ACK+SR/positive SR and aperiodic CSI in which case the HARQ-ACK/HARQ-ACK+SR/positive SR is transmitted on PUCCH using format 1/1a/1b/3 and the aperiodic CSI is transmitted on PUSCH of the serving cell given in subclause 7.2.1

If the UE is configured with more than one serving cell, then reporting prioritization and collision handling of periodic CSI reports of a certain PUCCH reporting type is given in subclause 7.2.2.

A UE transmits PUCCH only on the primary cell.

A UE is configured by higher layers to transmit PUCCH on one antenna port ($p = p_0$) or two antenna ports ($p \in \{p_0, p_1\}$).

For FDD or FDD-TDD and primary cell frame structure 1, with two configured serving cells and PUCCH format 1b with channel selection or for FDD with two or more configured serving cells and PUCCH format 3,

$$n_{\text{HARQ}} = \sum_{c=0}^{N_{\text{cells}}^{\text{DL}}-1} N_c^{\text{received}} \quad \text{where } N_{\text{cells}}^{\text{DL}} \text{ is the number of configured cells and } N_c^{\text{received}} \text{ is the number of transport}$$

blocks or the SPS release PDCCH/EPDCCH, if any, received in subframe $n - 4$ in serving cell c .

For TDD and a UE not configured with the parameter *EIMTA-MainConfigServCell-r12* for any serving cell, if a UE is configured with one serving cell, or the UE is configured with more than one serving cell and the UL/DL configurations of all serving cells are the same, then

- For TDD with two configured serving cells and PUCCH format 1b with channel selection and a subframe n with

$$M = 1, \text{ or for TDD UL/DL configuration 0 and PUCCH format 3, } n_{\text{HARQ}} = \sum_{c=0}^{N_{\text{cells}}^{\text{DL}}-1} \sum_{k \in K} N_{k,c}^{\text{received}}, \text{ where}$$

$N_{k,c}^{\text{received}}$ is the number of transport blocks or the SPS release PDCCH/EPDCCH, if any, received in subframe $n - k$ in serving cell c , where $k \in K$, and M is the number of elements in K .

- For TDD UL/DL configurations 1-6 and PUCCH format 3, or for TDD with two configured serving cells and PUCCH format 1b with channel selection and $M = 2$,

$$n_{\text{HARQ}} = \sum_{c=0}^{N_{\text{cells}}^{\text{DL}}-1} \left(\left((V_{\text{DAI},c}^{\text{DL}} - U_{\text{DAI},c}) \bmod 4 \right) \cdot n_c^{\text{ACK}} + \sum_{k \in K} N_{k,c}^{\text{received}} \right) \quad \text{where } V_{\text{DAI},c}^{\text{DL}} \text{ is the } V_{\text{DAI}}^{\text{DL}} \text{ in serving cell } c,$$

$U_{\text{DAI},c}$ is the U_{DAI} in serving cell c , and n_c^{ACK} is the number of HARQ-ACK bits corresponding to the configured DL transmission mode on serving cell c . In case spatial HARQ-ACK bundling is applied,

$n_c^{\text{ACK}} = 1$ and $N_{k,c}^{\text{received}}$ is the number of PDCCH/EPDCCH or PDSCH without a corresponding

PDCCH/EPDCCH received in subframe $n - k$ and serving cell c , where $k \in K$ and M is the number of

elements in K . In case spatial HARQ-ACK bundling is not applied, $N_{k,c}^{\text{received}}$ is the number of transport blocks

received or the SPS release PDCCH/EPDCCH received in subframe $n - k$ in serving cell c , where $k \in K$

and M is the number of elements in K . $V_{\text{DAI},c}^{\text{DL}}=0$ if no transport block or SPS release PDCCH/EPDCCH is detected in subframe(s) $n-k$ in serving cell c , where $k \in K$.

- For TDD with two configured serving cells and PUCCH format 1b with channel selection and $M = 3$ or 4 , $n_{\text{HARQ}} = 2$ if UE receives PDSCH or PDCCH/EPDCCH indicating downlink SPS release only on one serving cell within subframes $n-k$, where $k \in K$; otherwise $n_{\text{HARQ}} = 4$.

For TDD if the UE is configured with more than one serving cell and if at least two serving cells have different UL/DL configurations, or if the UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, or for FDD-TDD and primary cell frame structure 2, then

- For PUCCH format 3, or for two configured serving cells and PUCCH format 1b with channel selection and $M \leq 2$ (defined in subclause 10.1.3.2.1 for TDD and subclause 10.1.3A for FDD-TDD),

$$n_{\text{HARQ}} = \sum_{c=0}^{N_{\text{cells}}^{\text{DL}}-1} \left(\left(\left(V_{\text{DAI},c}^{\text{DL}} - U_{\text{DAI},c} \right) \bmod 4 \right) \cdot n_c^{\text{ACK}} + \sum_{k \in K} N_{k,c}^{\text{received}} \right) \text{ where } V_{\text{DAI},c}^{\text{DL}} \text{ is the } V_{\text{DAI}}^{\text{DL}} \text{ in serving cell } c,$$

$U_{\text{DAI},c}$ is the U_{DAI} in serving cell c , and n_c^{ACK} is the number of HARQ-ACK bits corresponding to the configured DL transmission mode on serving cell c . In case spatial HARQ-ACK bundling is applied, $n_c^{\text{ACK}} = 1$ and $N_{k,c}^{\text{received}}$ is the number of PDCCH/EPDCCH or PDSCH without a corresponding PDCCH/EPDCCH received in subframe $n-k$ and serving cell c , where $k \in K$ and $K = K_c$ (defined in subclause 7.3.2.2 for TDD and subclause 7.3.4 for FDD-TDD). In case spatial HARQ-ACK bundling is not applied, $N_{k,c}^{\text{received}}$ is the number of transport blocks received or the SPS release PDCCH/EPDCCH received in subframe $n-k$ in serving cell c , where $k \in K$ and $K = K_c$ (defined in subclause 7.3.2.2 for TDD and subclause 7.3.4 for FDD-TDD). $V_{\text{DAI},c}^{\text{DL}}=0$ if no transport block or SPS release PDCCH/EPDCCH is detected in subframe(s) $n-k$ in serving cell c , where $k \in K$ and $K = K_c$ (defined in subclause 7.3.2.2 for TDD and subclause 7.3.4 for FDD-TDD). For a serving cell c , set $V_{\text{DAI},c}^{\text{DL}} = U_{\text{DAI},c}$ if the DL-reference UL/DL configuration (defined in subclause 10.2) for serving cell c is TDD UL/DL configuration 0,

- For two configured serving cells and PUCCH format 1b with channel selection and $M = 3$ or 4 (defined in subclause 10.1.3.2.1 for TDD and subclause 10.1.3A for FDD-TDD), $n_{\text{HARQ}} = 2$ if UE receives PDSCH or PDCCH/EPDCCH indicating downlink SPS release only on one serving cell within subframes $n-k$, where $k \in K$ and $K = K_c$ (defined in subclause 7.3.2.2 for TDD and subclause 7.3.4 for FDD-TDD); otherwise $n_{\text{HARQ}} = 4$.

Throughout the following subclauses, subframes are numbered in monotonically increasing order; if the last subframe of a radio frame is denoted as k , the first subframe of the next radio frame is denoted as $k+1$.

Throughout the following subclauses, if the UE is configured with higher layer parameter *nIPUCCH-AN-r11* then $N_{\text{PUCCH}}^{(1)}$ is given by *nIPUCCH-AN-r11*, else $N_{\text{PUCCH}}^{(1)}$ is given by higher layer parameter *nIPUCCH-AN*.

10.1.1 PUCCH format information

Using the PUCCH formats defined in subclause 5.4.1 and 5.4.2 in [3], the following combinations of UCI on PUCCH are supported:

- Format 1a for 1-bit HARQ-ACK or in case of FDD or FDD-TDD primary cell frame structure type 1 for 1-bit HARQ-ACK with positive SR.
- Format 1b for 2-bit HARQ-ACK or for 2-bit HARQ-ACK with positive SR.
- Format 1b for up to 4-bit HARQ-ACK with channel selection when the UE is configured with more than one serving cell or, in the case of TDD, when the UE is configured with a single serving cell.
- Format 1 for positive SR.

- Format 2 for a CSI report when not multiplexed with HARQ-ACK.
- Format 2a for a CSI report multiplexed with 1-bit HARQ-ACK for normal cyclic prefix.
- Format 2b for a CSI report multiplexed with 2-bit HARQ-ACK for normal cyclic prefix.
- Format 2 for a CSI report multiplexed with HARQ-ACK for extended cyclic prefix.
- Format 3 for up to 10-bit HARQ-ACK for FDD or FDD-TDD primary cell frame structure type 1 and for up to 20-bit HARQ-ACK for TDD and for up to 21 bit HARQ-ACK for FDD-TDD primary cell frame structure type 2.
- Format 3 for up to 11-bit corresponding to 10-bit HARQ-ACK and 1-bit positive/negative SR for FDD or FDD-TDD and for up to 21-bit corresponding to 20-bit HARQ-ACK and 1-bit positive/negative SR for TDD and for up to 22-bit corresponding to 21-bit HARQ-ACK and 1-bit positive/negative SR for FDD-TDD primary cell frame structure type 2.
- Format 3 for HARQ-ACK, 1-bit positive/negative SR (if any) and a CSI report for one serving cell.

For a UE configured with PUCCH format 3 and HARQ-ACK transmission on PUSCH or using PUCCH format 3, or for a UE configured with two serving cells and PUCCH format 1b with channel selection and HARQ-ACK transmission on PUSCH, or for UE configured with one serving cell and PUCCH format 1b with channel selection according to Tables 10.1.3-5, 10.1.3-6, 10.1.3-7 and HARQ-ACK transmission on PUSCH:

- if the configured downlink transmission mode for a serving cell supports up to 2 transport blocks and only one transport block is received in a subframe, the UE shall generate a NACK for the other transport block if spatial HARQ-ACK bundling is not applied.
- if neither PDSCH nor PDCCH/EPDCCH indicating downlink SPS release is detected in a subframe for a serving cell, the UE shall generate two NACKs when the configured downlink transmission mode supports up to 2 transport blocks and the UE shall generate a single NACK when the configured downlink transmission mode supports a single transport block.

The scrambling initialization of PUCCH format 2, 2a, 2b and 3 is by C-RNTI.

For a UE that is configured with a single serving cell and is not configured with PUCCH format 3, in case of collision between a periodic CSI report and an HARQ-ACK in a same subframe without PUSCH, the periodic CSI report is multiplexed with HARQ-ACK on PUCCH if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE*, otherwise the CSI is dropped.

For TDD and for a UE that is configured with a single serving cell and with PUCCH format 3, in case of collision between a periodic CSI report and an HARQ-ACK in a same subframe without PUSCH, if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE* or if the parameter *simultaneousAckNackAndCQI-Format3-r11* provided by higher layers is set *TRUE*, the periodic CSI report is multiplexed with HARQ-ACK or dropped as described in subclause 7.3, otherwise the CSI is dropped.

For FDD or for FDD-TDD and primary cell frame structure type 1 and for a UE that is configured with more than one serving cell, in case of collision between a periodic CSI report and an HARQ-ACK in a same subframe without PUSCH,

- if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE* and if the HARQ-ACK corresponds to a PDSCH transmission or PDCCH/EPDCCH indicating downlink SPS release only on the primary cell,
then the periodic CSI report is multiplexed with HARQ-ACK on PUCCH using PUCCH format 2/2a/2b
- else if the UE is configured with PUCCH format 3 and if the parameter *simultaneousAckNackAndCQI-Format3-r11* provided by higher layers is set *TRUE*, and if PUCCH resource is determined according to subclause 10.1.2.2.2, and
 - if the total number of bits in the subframe corresponding to HARQ-ACKs, SR (if any), and the CSI is not larger than 22 or
 - if the total number of bits in the subframe corresponding to spatially bundled HARQ-ACKs, SR (if any), and the CSI is not larger than 22

then the periodic CSI report is multiplexed with HARQ-ACK on PUCCH using the determined PUCCH format 3 resource according to [4]

- otherwise,

CSI is dropped.

For TDD or for FDD-TDD and primary cell frame structure type 2 and for a UE that is configured with more than one serving cell, in case of collision between a periodic CSI report and an HARQ-ACK in a same subframe without PUSCH, if the parameter *simultaneousAckNackAndCQI* provided by higher layers is set *TRUE* or if the parameter *simultaneousAckNackAndCQI-Format3-r11* provided by higher layers is set *TRUE*, the periodic CSI report is multiplexed with HARQ-ACK or dropped as described in subclause 7.3, otherwise the CSI is dropped.

In case of collision between a periodic CSI report and an HARQ-ACK in a same subframe with PUSCH, the periodic CSI is multiplexed with the HARQ-ACK in the PUSCH transmission in that subframe if the UE is not configured by higher layers for simultaneous PUCCH and PUSCH transmissions. Otherwise, if the UE is configured by higher layers for simultaneous PUCCH and PUSCH transmissions, the HARQ-ACK is transmitted in the PUCCH and the periodic CSI is transmitted in the PUSCH.

If each of the serving cells configured for the UE has frame structure type 1, UE procedures for HARQ-ACK feedback are given in subclause 10.1.2.

If each of the serving cells configured for the UE has frame structure type 2, UE procedures for HARQ-ACK feedback are given in subclause 10.1.3.

If the UE is configured for more than one serving cell, and if the frame structure type of any two configured serving cells is different, and if the primary cell is frame structure type 1, UE procedure for HARQ-ACK feedback is given in subclause 10.1.2A.

If the UE is configured for more than one serving cell, and if the frame structure type of any two configured serving cells is different, and if the primary cell is frame structure type 2, UE procedure for HARQ-ACK feedback is given in subclause 10.1.3A.

10.1.2 FDD HARQ-ACK feedback procedures

For FDD and for a UE transmitting HARQ-ACK using PUCCH format 1b with channel selection or PUCCH format 3, the UE shall determine the number of HARQ-ACK bits, o , based on the number of configured serving cells and the downlink transmission modes configured for each serving cell. The UE shall use two HARQ-ACK bits for a serving cell configured with a downlink transmission mode that support up to two transport blocks; and one HARQ-ACK bit otherwise.

A UE that supports aggregating at most 2 serving cells with frame structure type 1 shall use PUCCH format 1b with channel selection for transmission of HARQ-ACK when configured with more than one serving cell with frame structure type 1.

A UE that supports aggregating more than 2 serving cells with frame structure type 1 is configured by higher layers to use either PUCCH format 1b with channel selection or PUCCH format 3 for transmission of HARQ-ACK when configured with more than one serving cell with frame structure type 1.

The FDD HARQ-ACK feedback procedure for one configured serving cell is given in subclause 10.1.2.1 and procedures for more than one configured serving cell are given in subclause 10.1.2.2.

10.1.2.1 FDD HARQ-ACK procedure for one configured serving cell

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1a/1b.

For FDD and one configured serving cell, the UE shall use PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ for transmission of HARQ-ACK in subframe n for \tilde{p} mapped to antenna port p for PUCCH format 1a/1b [3], where

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH in subframe $n-4$, or for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$, the UE shall use $n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = n_{\text{CCE}} + N_{\text{PUCCH}}^{(1)}$ for antenna port p_0 , where n_{CCE} is the number of the first CCE (i.e. lowest CCE

index used to construct the PDCCH) used for transmission of the corresponding DCI assignment and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers. For two antenna port transmission the PUCCH resource for antenna port p_1 is given by $n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{CCE}} + 1 + N_{\text{PUCCH}}^{(1)}$.

- for a PDSCH transmission on the primary cell where there is not a corresponding PDCCH/EPDCCH detected in subframe $n-4$, the value of $n_{\text{PUCCH}}^{(1,\tilde{p})}$ is determined according to higher layer configuration and Table 9.2-2. For a UE configured for two antenna port transmission, a PUCCH resource value in Table 9.2-2 maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_0)}$ for antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_0)}$ for antenna port p_0 .
- for a PDSCH transmission indicated by the detection of a corresponding EPDCCH in subframe $n-4$, or for an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$, the UE shall use

- o if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = n_{\text{ECCE},q} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- o if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

for antenna port p_0 , where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q , Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for localized EPDCCH transmission which is described in subclause 6.8A.5 in [3]. For two antenna port transmission the PUCCH resource for antenna port p_1 is given by

- o if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{ECCE},q} + 1 + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- o if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + 1 + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

Table 10.1.2.1-1: Mapping of ACK/NACK Resource offset Field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D to Δ_{ARO} values

| ACK/NACK Resource offset field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D | Δ_{ARO} |
|---|-----------------------|
| 0 | 0 |
| 1 | -1 |
| 2 | -2 |
| 3 | 2 |

10.1.2.2 FDD HARQ-ACK procedures for more than one configured serving cell

The FDD HARQ-ACK feedback procedures for more than one configured serving cell are either based on a PUCCH format 1b with channel selection HARQ-ACK procedure as described in subclause 10.1.2.2.1 or a PUCCH format 3 HARQ-ACK procedure as described in subclause 10.1.2.2.2.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 3.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1b with channel selection and FDD with two configured serving cells.

10.1.2.2.1 PUCCH format 1b with channel selection HARQ-ACK procedure

For two configured serving cells and PUCCH format 1b with channel selection, the UE shall transmit $b(0)b(1)$ on PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p})}$ for \tilde{p} mapped to antenna port p using PUCCH format 1b where

- $n_{\text{PUCCH}}^{(1, \tilde{p}_0)} = n_{\text{PUCCH}}^{(1)}$ for antenna port p_0 where $n_{\text{PUCCH}}^{(1)}$ is selected from A PUCCH resources, $n_{\text{PUCCH}, j}^{(1)}$ where $0 \leq j \leq A-1$ and $A \in \{2, 3, 4\}$, according to Table 10.1.2.2.1-3, Table 10.1.2.2.1-4, Table 10.1.2.2.1-5 in subframe n . HARQ-ACK(j) denotes the ACK/NACK/DTX response for a transport block or SPS release PDCCH/EPDCCH associated with serving cell c , where the transport block and serving cell for HARQ-ACK(j) and A PUCCH resources are given by Table 10.1.2.2.1-1.
- $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ for antenna port p_1 , where $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ is selected from A PUCCH resources, $n_{\text{PUCCH}, j}^{(1, \tilde{p}_1)}$ configured by higher layers where $0 \leq j \leq A-1$ and $A \in \{2, 3, 4\}$, according to Table 10.1.2.2.1-3, Table 10.1.2.2.1-4, Table 10.1.2.2.1-5 by replacing $n_{\text{PUCCH}}^{(1)}$ with $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ and replacing $n_{\text{PUCCH}, i}^{(1)}$ with $n_{\text{PUCCH}, i}^{(1, \tilde{p}_1)}$ in subframe n , when the UE is configured with two antenna port transmission for PUCCH format 1b with channel selection.

A UE configured with a transmission mode that supports up to two transport blocks on serving cell, c , shall use the same HARQ-ACK response for both the transport blocks in response to a PDSCH transmission with a single transport block or a PDCCH/EPDCCH indicating downlink SPS release associated with the serving cell c .

Table 10.1.2.2.1-1: Mapping of Transport Block and Serving Cell to HARQ-ACK(j) for PUCCH format 1b HARQ-ACK channel selection

| A | HARQ-ACK(j) | | | |
|---|-------------------|--------------------|--------------------|--------------------|
| | HARQ-ACK(0) | HARQ-ACK(1) | HARQ-ACK(2) | HARQ-ACK(3) |
| 2 | TB1 Primary cell | TB1 Secondary cell | NA | NA |
| 3 | TB1 Serving cell1 | TB2 Serving cell1 | TB1 Serving cell2 | NA |
| 4 | TB1 Primary cell | TB2 Primary cell | TB1 Secondary cell | TB2 Secondary cell |

The UE shall determine the A PUCCH resources, $n_{\text{PUCCH}, j}^{(1)}$ associated with HARQ-ACK(j) where $0 \leq j \leq A-1$ in Table 10.1.2.2.1-1, according to

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH in subframe $n-4$ on the primary cell, or for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$ on the primary cell, the PUCCH resource is $n_{\text{PUCCH}, j}^{(1)} = n_{\text{CCE}} + N_{\text{PUCCH}}^{(1)}$, and for transmission mode that supports up to two transport blocks, the PUCCH resource $n_{\text{PUCCH}, j+1}^{(1)}$ is given by $n_{\text{PUCCH}, j+1}^{(1)} = n_{\text{CCE}} + 1 + N_{\text{PUCCH}}^{(1)}$ where n_{CCE} is the number of the first CCE used for transmission of the corresponding PDCCH and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers.

- for a PDSCH transmission on the primary cell where there is not a corresponding PDCCH/EPDCCH detected in subframe $n-4$, the value of $n_{\text{PUCCH},j}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.

For transmission mode that supports up to two transport blocks, the PUCCH resource $n_{\text{PUCCH},j+1}^{(1)}$ is given by

$$n_{\text{PUCCH},j+1}^{(1)} = n_{\text{PUCCH},j}^{(1)} + 1$$

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n-4$ on the secondary cell, the value of $n_{\text{PUCCH},j}^{(1)}$, and the value of $n_{\text{PUCCH},j+1}^{(1)}$ for the transmission mode that supports up to two transport blocks is determined according to higher layer configuration and Table 10.1.2.2.1-2. The TPC field in the DCI format of the corresponding PDCCH/EPDCCH shall be used to determine the PUCCH resource values from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.1-2. For a UE configured for a transmission mode that supports up to two transport blocks a PUCCH resource value in Table 10.1.2.2.1-2 maps to two PUCCH resources $(n_{\text{PUCCH},j}^{(1)}, n_{\text{PUCCH},j+1}^{(1)})$, otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH},j}^{(1)}$.
- for a PDSCH transmission indicated by the detection of a corresponding EPDCCH in subframe $n-4$ on the primary cell, or for an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$ on the primary cell, the PUCCH resource is given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},j}^{(1)} = n_{\text{ECCE},q} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},j}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q , Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for localized EPDCCH transmission which is described in subclause 6.8A.5 in [3].

For transmission mode that supports up to two transport blocks, the PUCCH resource $n_{\text{PUCCH},j+1}^{(1)}$ is given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},j+1}^{(1)} = n_{\text{ECCE},q} + 1 + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},j+1}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + 1 + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

Table 10.1.2.2.1-2: PUCCH Resource Value for HARQ-ACK Resource for PUCCH

| Value of 'TPC command for PUCCH' | $n_{\text{PUCCH},j}^{(1)}$ or $(n_{\text{PUCCH},j}^{(1)}, n_{\text{PUCCH},j+1}^{(1)})$ |
|---|--|
| '00' | The 1st PUCCH resource value configured by the higher layers |
| '01' | The 2 nd PUCCH resource value configured by the higher layers |
| '10' | The 3 rd PUCCH resource value configured by the higher layers |
| '11' | The 4 th PUCCH resource value configured by the higher layers |
| NOTE: $(n_{\text{PUCCH},j}^{(1)}, n_{\text{PUCCH},j+1}^{(1)})$ are determined from the first and second PUCCH resource lists configured by $n1\text{PUCCH-AN-CS-List-r10}$ in [11], respectively. | |

Table 10.1.2.2.1-3: Transmission of Format 1b HARQ-ACK channel selection for $A = 2$

| HARQ-ACK(0) | HARQ-ACK(1) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|-------------|-------------|----------------------------|------------|
| ACK | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1,1 |
| NACK/DTX | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0,0 |
| NACK | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,0 |
| DTX | NACK/DTX | No Transmission | |

Table 10.1.2.2.1-4: Transmission of Format 1b HARQ-ACK channel selection for $A = 3$

| HARQ-ACK(0) | HARQ-ACK(1) | HARQ-ACK(2) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|-------------|-------------|-------------|----------------------------|------------|
| ACK | ACK | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1,0 |
| NACK/DTX | ACK | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0,1 |
| NACK/DTX | NACK/DTX | ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1,1 |
| ACK | ACK | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1,0 |
| NACK/DTX | ACK | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,1 |
| NACK/DTX | NACK/DTX | NACK | $n_{\text{PUCCH},2}^{(1)}$ | 0,0 |
| NACK | NACK/DTX | DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,0 |
| NACK/DTX | NACK | DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,0 |
| DTX | DTX | DTX | No Transmission | |

Table 10.1.2.2.1-5: Transmission of Format 1b HARQ-ACK channel selection for $A = 4$

| HARQ-ACK(0) | HARQ-ACK(1) | HARQ-ACK(2) | HARQ-ACK(3) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|-------------|-------------|-------------|-------------|----------------------------|------------|
| ACK | ACK | ACK | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | ACK | ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0,1 |
| NACK/DTX | ACK | ACK | ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0,1 |
| NACK/DTX | NACK/DTX | ACK | ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1,1 |
| ACK | ACK | ACK | NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1,0 |
| ACK | NACK/DTX | ACK | NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0,0 |
| NACK/DTX | ACK | ACK | NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0,0 |
| NACK/DTX | NACK/DTX | ACK | NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 1,0 |
| ACK | ACK | NACK/DTX | ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | NACK/DTX | ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1,0 |
| NACK/DTX | ACK | NACK/DTX | ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0,1 |
| NACK/DTX | NACK/DTX | NACK/DTX | ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0,0 |
| ACK | ACK | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1,1 |
| ACK | NACK/DTX | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1,0 |
| NACK/DTX | ACK | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,1 |
| NACK/DTX | NACK | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,0 |
| NACK | NACK/DTX | NACK/DTX | NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0,0 |
| DTX | DTX | NACK/DTX | NACK/DTX | No Transmission | |

10.1.2.2.2 PUCCH format 3 HARQ-ACK procedure

For PUCCH format 3, the UE shall use PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ or $n_{\text{PUCCH}}^{(1,\tilde{p})}$ for transmission of HARQ-ACK in subframe n for \tilde{p} mapped to antenna port p where

- for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n-4$, or for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$ on the primary cell, the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ with $n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = n_{\text{CCE}} + N_{\text{PUCCH}}^{(1)}$ for antenna port p_0 , where n_{CCE} is the number of the first CCE (i.e. lowest CCE index used to construct the PDCCH) used for transmission of the corresponding PDCCH and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by $n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{CCE}} + 1 + N_{\text{PUCCH}}^{(1)}$.
- for a PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected in subframe $n-4$, the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(1,\tilde{p})}$ is determined according to higher layer configuration and Table 9.2-2. For a UE configured for two antenna port transmission for PUCCH format 1a/1b, a PUCCH resource value in Table 9.2-2 maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_0)}$ for antenna port p_0 and the second PUCCH

resource $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_0)}$ for antenna port p_0 .

- for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding PDCCH/EPDCCH in subframe $n-4$, the UE shall use PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(3,\tilde{p})}$ is determined according to higher layer configuration and Table 10.1.2.2.2-1. The TPC field in the DCI format of the corresponding PDCCH/EPDCCH shall be used to determine the PUCCH resource values from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. For a UE configured for two antenna port transmission for PUCCH format 3, a PUCCH resource value in Table 10.1.2.2.2-1 maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_0)}$ for antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_0)}$ for antenna port p_0 . A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted in each DCI format of the corresponding secondary cell PDCCH/EPDCCH assignments in a given subframe.
- for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n-4$, or for a EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-4$ on the primary cell, the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = n_{\text{ECCE},q} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

for antenna port p_0 , where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q , Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for localized EPDCCH transmission which is described in subclause 6.8A.5 in [3]. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by.

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{ECCE},q} + 1 + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + 1 + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

Table 10.1.2.2.2-1: PUCCH Resource Value for HARQ-ACK Resource for PUCCH

| Value of 'TPC command for PUCCH' or 'HARQ-ACK resource offset' | $n_{\text{PUCCH}}^{(3,\tilde{p})}$ |
|--|--|
| '00' | The 1st PUCCH resource value configured by the higher layers |
| '01' | The 2 nd PUCCH resource value configured by the higher layers |
| '10' | The 3 rd PUCCH resource value configured by the higher layers |
| '11' | The 4 th PUCCH resource value configured by the higher layers |

10.1.2A FDD-TDD HARQ-ACK feedback procedures for primary cell frame structure type 1

For a UE transmitting HARQ-ACK using PUCCH format 1b with channel selection, the UE shall determine the number of HARQ-ACK bits, o in subframe n , based on the number of configured serving cells with subframe $n-4$ configured as a downlink or special subframe according to the DL-reference UL/DL configuration (defined in subclause 10.2) of each serving cell and the downlink transmission modes configured for each serving cell. For a UE transmitting HARQ-ACK using PUCCH format 3, the UE shall determine the number of HARQ-ACK bits, o in subframe n , based on the number of configured serving cells with subframe $n-4$ configured as a downlink or special subframe except a special subframe of configurations 0 and 5 with normal downlink CP or of configurations 0 and 4 with extended downlink CP according to the DL-reference UL/DL configuration (defined in subclause 10.2) of each serving cell and the downlink transmission modes configured for each serving cell. The UE shall use two HARQ-ACK bits for a serving cell configured with a downlink transmission mode that support up to two transport blocks; and one HARQ-ACK bit otherwise.

A UE that supports aggregating at most 2 serving cells shall use PUCCH format 1b with channel selection for transmission of HARQ-ACK when configured with primary cell frame structure type 1 and secondary cell frame structure type 2.

A UE that supports aggregating more than 2 serving cells with primary cell frame structure type 1 is configured by higher layers to use either PUCCH format 1b with channel selection or PUCCH format 3 for transmission of HARQ-ACK when configured with more than one serving cell and primary cell frame structure type 1 and at least one secondary cell with frame structure type 2.

For HARQ-ACK transmission in subframe n with PUCCH format 1b with channel selection, the FDD-TDD HARQ-ACK procedure follows HARQ-ACK procedure described in subclause 10.1.2.1 if subframe $n-4$ is an uplink or a special subframe of configurations 0 and 5 with normal downlink CP or of configurations 0 and 4 with extended downlink CP for the secondary cell according to the higher layer parameter *subframeAssignment* for UE not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, and according to the higher layer parameter *eimta-HARQ-ReferenceConfig-r12* for UE configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, and HARQ-ACK procedure described in subclause 10.1.2.2.1 otherwise.

The FDD-TDD HARQ-ACK feedback procedure for PUCCH format 3 HARQ-ACK procedure as described in subclause 10.1.2.2.2.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 3.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1b with channel selection and with two configured serving cells.

10.1.3 TDD HARQ-ACK feedback procedures

For TDD and a UE that does not support aggregating more than one serving cell with frame structure type 2, two HARQ-ACK feedback modes are supported by higher layer configuration.

- HARQ-ACK bundling and
- HARQ-ACK multiplexing

For TDD UL/DL configuration 5 and a UE that does not support aggregating more than one serving cell with frame structure type 2 and the UE is not configured with *EIMTA-MainConfigServCell-r12* for the serving cell, only HARQ-ACK bundling is supported.

A UE that supports aggregating more than one serving cell with frame structure type 2 is configured by higher layers to use either PUCCH format 1b with channel selection or PUCCH format 3 for transmission of HARQ-ACK when configured with more than one serving cell with frame structure type 2.

A UE that supports aggregating more than one serving cell with frame structure type 2 and is not configured with the parameter *EIMTA-MainConfigServCell-r12* for any serving cell is configured by higher layers to use HARQ-ACK bundling, PUCCH format 1b with channel selection according to the set of Tables 10.1.3-2/3/4 or according to the set of Tables 10.1.3-5/6/7, or PUCCH format 3 for transmission of HARQ-ACK when configured with one serving cell with frame structure type 2.

A UE that is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell is configured by higher layers to use PUCCH format 1b with channel selection according to the set of Tables 10.1.3-5/6/7, or PUCCH format 3 for transmission of HARQ-ACK.

PUCCH format 1b with channel selection according to the set of Tables 10.1.3-2/3/4 or according to the set of Tables 10.1.3-5/6/7 is not supported for TDD UL/DL configuration 5.

TDD HARQ-ACK bundling is performed per codeword across M multiple downlink or special subframes associated with a single UL subframe n , where M is the number of elements in the set K defined in Table 10.1.3.1-1, by a logical AND operation of all the individual PDSCH transmission (with and without corresponding PDCCH/EPDCCH) HARQ-ACKs and ACK in response to PDCCH/EPDCCH indicating downlink SPS release. For one configured serving cell the bundled 1 or 2 HARQ-ACK bits are transmitted using PUCCH format 1a or PUCCH format 1b, respectively.

For TDD HARQ-ACK multiplexing and a subframe n with $M > 1$, where M is the number of elements in the set K defined in Table 10.1.3.1-1, spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed by a logical AND operation of all the corresponding individual HARQ-ACKs. PUCCH format 1b with channel selection is used in case of one configured serving cell. For TDD HARQ-ACK multiplexing and a subframe n with $M = 1$, spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is not performed, 1 or 2 HARQ-ACK bits are transmitted using PUCCH format 1a or PUCCH format 1b, respectively for one configured serving cell.

In the case of TDD and more than one configured serving cell with PUCCH format 1b with channel selection and more than 4 HARQ-ACK bits for M multiple downlink or special subframes associated with a single UL subframe n , where M is defined in subclause 10.1.3.2.1, and for the configured serving cells, spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe for all configured cells is performed and the bundled HARQ-ACK bits for each configured serving cell is transmitted using PUCCH format 1b with channel selection. For TDD and more than one configured serving cell with PUCCH format 1b with channel selection and up to 4 HARQ-ACK bits for M multiple downlink or special subframes associated with a single UL subframe n , where M is defined in subclause 10.1.3.2.1, and for the configured serving cells, spatial HARQ-ACK bundling is not performed and the HARQ-ACK bits are transmitted using PUCCH format 1b with channel selection.

In the case of TDD and more than one configured serving cell with PUCCH format 3 and more than 20 HARQ-ACK bits for M multiple downlink or special subframes associated with a single UL subframe n , where M is the number of elements in the set K defined in subclause 10.1.3.2.2 and for the configured serving cells, spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed for each serving cell by a logical AND operation of all of the corresponding individual HARQ-ACKs and PUCCH format 3 is used. For TDD and more than one configured serving cell with PUCCH format 3 and up to 20 HARQ-ACK bits for M multiple downlink or special subframes associated with a single UL subframe n , where M is the number of elements in the set K defined in subclause 10.1.3.2.2 and for the configured serving cells, spatial HARQ-ACK bundling is not performed and the HARQ-ACK bits are transmitted using PUCCH format 3.

For TDD with PUCCH format 3, a UE shall determine the number of HARQ-ACK bits, O , associated with an UL subframe n

according to
$$O = \sum_{c=1}^{N_{cells}^{DL}} O_c^{ACK}$$
 where N_{cells}^{DL} is the number of configured cells, and O_c^{ACK} is the number of HARQ-bits

for the c -th serving cell defined in subclause 7.3.

TDD HARQ-ACK feedback procedures for one configured serving cell are given in subclause 10.1.3.1 and procedures for more than one configured serving cell are given in subclause 10.1.3.2.

10.1.3.1 TDD HARQ-ACK procedure for one configured serving cell

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1a/1b with TDD HARQ-ACK bundling feedback mode and for PUCCH format 3.

A UE that supports aggregating more than one serving cell with frame structure type 2 can be configured by higher layers for HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) for PUCCH format 1b with channel selection.

The TDD HARQ-ACK procedure for a UE configured with PUCCH format 3 is as described in subclause 10.1.3.2.2 when the UE receives PDSCH and/or SPS release PDCCH/EPDCCH only on the primary cell.

If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, for TDD HARQ-ACK bundling or TDD HARQ-ACK multiplexing for one configured serving cell and a subframe n with $M = 1$ where M is the number of elements in the set K defined in Table 10.1.3.1-1, the UE shall use PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p})}$ for transmission of HARQ-ACK in subframe n for \tilde{p} mapped to antenna port p for PUCCH format 1a/1b, where

- If there is PDSCH transmission indicated by the detection of corresponding PDCCH/EPDCCH or there is PDCCH/EPDCCH indicating downlink SPS release within subframe(s) $n-k$, where $k \in K$ and K (defined in Table 10.1.3.1-1) is a set of M elements $\{k_0, k_1, \dots, k_{M-1}\}$ depending on the subframe n and the UL/DL configuration (defined in Table 4.2-2 in [3]), and if PDCCH indicating PDSCH transmission or downlink SPS release is detected in subframe $n-k_m$, where k_m is the smallest value in set K such that UE detects a PDCCH/EPDCCH indicating PDSCH transmission or downlink SPS release within subframe(s) $n-k$ and $k \in K$, the UE first selects a c value out of $\{0, 1, 2, 3\}$ which makes $N_c \leq n_{\text{CCE}} < N_{c+1}$ and shall use $n_{\text{PUCCH}}^{(1, \tilde{p}_0)} = (M - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE}} + N_{\text{PUCCH}}^{(1)}$ for antenna port p_0 , where $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, and n_{CCE} is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n-k_m$ and the corresponding m . When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for HARQ-ACK bundling for antenna port p_1 is given by $n_{\text{PUCCH}}^{(1, \tilde{p}_1)} = (M - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE}} + 1 + N_{\text{PUCCH}}^{(1)}$.
- If there is only a PDSCH transmission where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n-k$, where $k \in K$ and K is defined in Table 10.1.3.1-1, the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p})}$ with the value of $n_{\text{PUCCH}}^{(1, \tilde{p})}$ is determined according to higher layer configuration and Table 9.2-2. For a UE configured for two antenna port transmission for PUCCH format 1a/1b and HARQ-ACK bundling, a PUCCH resource value in Table 9.2-2 maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p}_0)}$ for antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p}_0)}$ for antenna port p_0 .
- If there is PDSCH transmission indicated by the detection of corresponding PDCCH/EPDCCH or there is PDCCH/EPDCCH indicating downlink SPS release within subframe(s) $n-k$, where $k \in K$ and K (defined in Table 10.1.3.1-1) is a set of M elements $\{k_0, k_1, \dots, k_{M-1}\}$ depending on the subframe n and the UL/DL configuration (defined in Table 4.2-2 in [3]), and if EPDCCH indicating PDSCH transmission or downlink SPS release is detected in subframe $n-k_m$, where k_m is the smallest value in set K such that UE detects a PDCCH/EPDCCH indicating PDSCH transmission or downlink SPS release within subframe(s) $n-k$ and $k \in K$, the UE shall use
 - if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1, \tilde{p}_0)} = n_{\text{ECCE}, q} + \sum_{i=1}^{m-1} N_{\text{ECCE}, q, n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH}, q}^{(e1)}$$
 - if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1, \tilde{p}_0)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

for antenna port p_0 , where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n-k_m$ and the corresponding m , $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n-k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n-k_m$ which is described in subclause 6.8A.5 in [3]. If $m=0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m>0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n-k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n-k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n-k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n-k_{i1}$. For normal downlink CP, if subframe $n-k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n-k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for HARQ-ACK bundling for antenna port p_1 is given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1, \tilde{p}_1)} = n_{\text{ECCE},q} + 1 + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1, \tilde{p}_1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + 1 + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

Table 10.1.3.1-1: Downlink association set $K : \{k_0, k_1, \dots, k_{M-1}\}$ for TDD

| UL/DL Configuration | Subframe n | | | | | | | | | |
|------------------------|--------------|---|------------------------------|------------|------|---|---|------------|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | - | - | 6 | - | 4 | - | - | 6 | - | 4 |
| 1 | - | - | 7, 6 | 4 | - | - | - | 7, 6 | 4 | - |
| 2 | - | - | 8, 7, 4, 6 | - | - | - | - | 8, 7, 4, 6 | - | - |
| 3 | - | - | 7, 6, 11 | 6, 5 | 5, 4 | - | - | - | - | - |
| 4 | - | - | 12, 8, 7, 11 | 6, 5, 4, 7 | - | - | - | - | - | - |
| 5 | - | - | 13, 12, 9, 8, 7, 5, 4, 11, 6 | - | - | - | - | - | - | - |
| 6 | - | - | 7 | 7 | 5 | - | - | 7 | 7 | - |

Table 10.1.3.1-1A: eIMTA downlink association set $K^A := \{k_0^A, k_1^A, \dots, k_{M^A-1}^A\}$ for TDD

| Higher layer parameter 'eIMTA-HARQ-ReferenceConfig-r12' | Higher layer parameter 'subframeAssignment' | Subframe n | | | | | | | | | |
|--|--|--------------|---|--------------------|---------|---|---|---|-------|---|---|
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 2 | 0 | - | - | 7,8,4 | - | - | - | - | 7,8,4 | - | - |
| | 1 | - | - | 8,4 | - | - | - | - | 8,4 | - | - |
| | 6 | - | - | 6,8,4 | - | - | - | - | 8,6,4 | - | - |
| 4 | 0 | - | - | 12,7,11,8 | 7,4,5,6 | - | - | - | - | - | - |
| | 1 | - | - | 12,8,11 | 7,5,6 | - | - | - | - | - | - |
| | 3 | - | - | 12,8 | 4,7 | - | - | - | - | - | - |
| | 6 | - | - | 12,11,8 | 4,5,6 | - | - | - | - | - | - |
| 5 | 0 | - | - | 12,7,11,13,8,4,9,5 | - | - | - | - | - | - | - |
| | 1 | - | - | 13,12,8,11,4,9,5 | - | - | - | - | - | - | - |
| | 2 | - | - | 13,12,9,11,5 | - | - | - | - | - | - | - |
| | 3 | - | - | 13,12,5,4,8,9 | - | - | - | - | - | - | - |
| | 4 | - | - | 13,5,4,6,9 | - | - | - | - | - | - | - |
| | 6 | - | - | 13,12,11,6,8,4,9,5 | - | - | - | - | - | - | - |

Table 10.1.3.1-2: Mapping of ACK/NACK Resource offset Field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D to Δ_{ARO} values for TDD when $m > 0$

| ACK/NACK Resource offset field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D | Δ_{ARO} |
|---|--|
| 0 | 0 |
| 1 | $-\sum_{i1=0}^{m-1} N_{ECCE,q,n-k_{i1}} - 2$ |
| 2 | $-\sum_{i1=m-\lceil m/3 \rceil}^{m-1} N_{ECCE,q,n-k_{i1}} - 1$ |
| 3 | 2 |

Table 10.1.3.1-3: Mapping of ACK/NACK Resource offset Field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D to Δ'_{ARO} values for TDD when $i4 = M'$ and $i5 \neq 0$

| ACK/NACK Resource offset field in DCI format 1A/1B/1D/1/2A/2/2B/2C/2D | Δ'_{ARO} |
|---|--|
| 0 | 0 |
| 1 | $-\sum_{i1=0}^{i4-1} N'_{ECCE,q,n-k'_{i1}} - \sum_{i1=0}^{i5-1} N'_{ECCE,q,n-k'_i} - 2$ |
| 2 | $-\sum_{i1=\min(i4, i4-\delta+i5)}^{i4-1} N'_{ECCE,q,n-k'_{i1}} - \sum_{i1=\max(0, i5-\delta)}^{i5-1} N'_{ECCE,q,n-k'_i} - 1, \delta = \left\lceil \frac{(i4+i5)}{3} \right\rceil$ |
| 3 | 2 |

If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, for TDD HARQ-ACK multiplexing and sub-frame n with $M > 1$ and one configured serving cell, where M is the number of elements in the set K defined in Table 10.1.3.1-1, denote $n_{PUCCH,i}^{(1)}$ as the PUCCH resource derived from sub-frame $n - k_i$ and HARQ-ACK(i) as the ACK/NACK/DTX response from sub-frame $n - k_i$, where $k_i \in K$ (defined in Table 10.1.3.1-1) and $0 \leq i \leq M - 1$.

- For a PDSCH transmission indicated by the detection of corresponding PDCCH or a PDCCH indicating downlink SPS release in sub-frame $n - k_i$ where $k_i \in K$, the PUCCH resource

$n_{\text{PUCCH},i}^{(1)} = (M - i - 1) \cdot N_c + i \cdot N_{c+1} + n_{\text{CCE},i} + N_{\text{PUCCH}}^{(1)}$, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},i} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, $n_{\text{CCE},i}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_i$, and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers.

- For a PDSCH transmission where there is not a corresponding PDCCH/EPDCCH detected in subframe $n - k_i$, the value of $n_{\text{PUCCH},i}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.
- For a PDSCH transmission indicated by the detection of corresponding EPDCCH or a EPDCCH indicating downlink SPS release in sub-frame $n - k_i$ where $k_i \in K$, the UE shall use
 - if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{i-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{i-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_i$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_i$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_i$ which is described in subclause 6.8A.5 in [3]. If $i = 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $i > 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2, where the variable m in the table is substituted with i . If the UE is configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0.

If a UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, then $K' = K$ where the set K is defined in Table 10.1.3.1-1 (where “UL/DL configuration” in the table refers to the higher layer parameter *subframeAssignment*), and M' is the number of elements in set K' .

If a UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, then the set K for the rest of this subclause is as defined in Sec 10.2, and M is the number of elements for subframe n in the set K

If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, for TDD HARQ-ACK multiplexing and sub-frame n , denote $n_{\text{PUCCH},i0}^{(1)}$ as the PUCCH resource derived from sub-frame $n - k_i$ and HARQ-ACK(i0) as the ACK/NACK/DTX response from sub-frame $n - k_i$, where $k_i \in K$, and $0 \leq i \leq M - 1$.

- $i0$ corresponding to each subframe $n - k_i$, $\forall i, 0 \leq i \leq M - 1$ is determined as follows

Set $b = 0$;

for $i2 = 0, 1, \dots, M' - 1$

if the value of k'_{i2} is the same as the value of an element k_i in set K , where $k'_{i2} \in K'$,

$i0$ corresponding to subframe $n - k_i = b$;

$b = b + 1$

end if

end for

for $i3 = 0, 1, \dots, M^A - 1$

if the value of k^A_{i3} is same as the value of an element k_i in set K , where $k^A_{i3} \in K^A$ (defined in Table 10.1.3.1-1A)

$i0$ corresponding to subframe $n - k_i = b$;

$b = b + 1$

end if

end for

- For a PDSCH transmission indicated by the detection of corresponding PDCCH or a PDCCH indicating downlink SPS release in sub-frame $n - k_i$,
- if the value of k_i is same as the value of an element k'_{i2} in set K' , the PUCCH resource $n_{\text{PUCCH},i0}^{(1)}$ is given by $n_{\text{PUCCH},i0}^{(1)} = (M' - i2 - 1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},i} + N_{\text{PUCCH}}^{(1)}$;
- otherwise, if the value of k_i is same as the value of an element k^A_{i3} in set K^A , where $k^A_{i3} \in K^A$ (defined in Table 10.1.3.1-1A), the UE shall set, the PUCCH resource $n_{\text{PUCCH},i0}^{(1)}$ is given by $n_{\text{PUCCH},i0}^{(1)} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},i} + N_{\text{PUCCH}}^{K^A}$;

where M^A is the number of elements in the set K^A defined in Table 10.1.3.1-1A, c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},i} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, $n_{\text{CCE},i}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_i$, and $N_{\text{PUCCH}}^{K^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers.

- For a PDSCH transmission where there is not a corresponding PDCCH/EPDCCH detected in subframe $n - k_i$, the value of $n_{\text{PUCCH},i0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.
- For a PDSCH transmission indicated by the detection of corresponding EPDCCH or a EPDCCH indicating downlink SPS release in sub-frame $n - k_i$ where $k_i \in K$, the UE shall use
- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i0}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k^A_{i1}} + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i0}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k_{i1}^A} + n' + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where

- if the value of k_i is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$ and $i5 = 0$;
- otherwise, if the value of k_i is same as the value of an index k_{i3}^A , where $k_{i3}^A \in K^A$, then $i4 = M'$ and $i5 = i3$;

, and where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_i$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_i$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_i$ which is described in subclause 6.8A.5 in [3].

Δ'_{ARO} is determined as follows

- If $i4 = 0$ and $i5 = 0$, Δ'_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1.
- If $0 < i4 < M'$ and $i5 = 0$, Δ'_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2, where the variable Δ_{ARO} in the table is substituted with Δ'_{ARO} , the variable m in the table is substituted with $i4$, the variable N in the table is substituted with N' and the variable k_{i1} in the table is substituted with k'_{i1} .
- If $i4 = M'$ and $i5 \neq 0$, Δ'_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-3,

For a given subframe u , $N'_{\text{ECCE},q,u}$ is determined as follows

- If the UE is configured to monitor EPDCCH in subframe u , $N'_{\text{ECCE},q,u}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe u .
- If the UE is not configured to monitor EPDCCH in subframe u , $N'_{\text{ECCE},q,u}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe u .
- For normal downlink CP, if subframe u is a special subframe with special subframe configuration 0 or 5, $N'_{\text{ECCE},q,u}$ is equal to 0.
- For extended downlink CP, if subframe u is a special subframe with special subframe configuration 0 or 4 or 7, $N'_{\text{ECCE},q,u}$ is equal to 0.

If a UE is not configured with two antenna port transmission for PUCCH format 1b with channel selection, and if the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, based on higher layer signalling the UE configured with a single serving cell will perform channel selection either according to the set of Tables 10.1.3-2, 10.1.3-3, and 10.1.3-4 or according to the set of Tables 10.1.3-5, 10.1.3-6, and 10.1.3-7.

If a UE is configured with two antenna port transmission for PUCCH format 1b with channel selection, and if the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, then the UE will perform channel selection according to the set of Tables 10.1.3-5, 10.1.3-6, and 10.1.3-7.

If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, the UE configured with a single serving cell will perform channel selection according to the set of Tables 10.1.3-5, 10.1.3-6, and 10.1.3-7.

For the selected table set, the UE shall transmit $b(0), b(1)$ on PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p})}$ in sub-frame n for \tilde{p} mapped to antenna port p using PUCCH format 1b according to subclause 5.4.1 in [3] where

- $n_{\text{PUCCH}}^{(1, \tilde{p})} = n_{\text{PUCCH}}^{(1)}$ for antenna port p_0 and the value of $b(0), b(1)$ and the PUCCH resource $n_{\text{PUCCH}}^{(1)}$ are generated by channel selection according to the selected set of Tables for $M = 2, 3$, and 4 respectively
- $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ for antenna port p_1 , where $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ is selected from PUCCH resources $n_{\text{PUCCH}, i}^{(1, \tilde{p}_1)}$ configured by higher layers where $0 \leq i \leq M - 1$, according to selected set of Tables for $M = 2, 3$, and 4 respectively by replacing $n_{\text{PUCCH}}^{(1)}$ with $n_{\text{PUCCH}}^{(1, \tilde{p}_1)}$ and replacing $n_{\text{PUCCH}, i}^{(1)}$ with $n_{\text{PUCCH}, i}^{(1, \tilde{p}_1)}$, when the UE is configured with two antenna port transmission for PUCCH format 1b with channel selection.

Table 10.1.3-2: Transmission of HARQ-ACK multiplexing for $M = 2$

| HARQ-ACK(0), HARQ-ACK(1) | $n_{\text{PUCCH}}^{(1)}$ | $b(0), b(1)$ |
|--------------------------|-----------------------------|--------------|
| ACK, ACK | $n_{\text{PUCCH}, 1}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX | $n_{\text{PUCCH}, 0}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK | $n_{\text{PUCCH}, 1}^{(1)}$ | 0, 0 |
| NACK/DTX, NACK | $n_{\text{PUCCH}, 1}^{(1)}$ | 1, 0 |
| NACK, DTX | $n_{\text{PUCCH}, 0}^{(1)}$ | 1, 0 |
| DTX, DTX | No transmission | |

Table 10.1.3-3: Transmission of HARQ-ACK multiplexing for $M = 3$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2) | $n_{\text{PUCCH}}^{(1)}$ | $b(0), b(1)$ |
|---------------------------------------|-----------------------------|--------------|
| ACK, ACK, ACK | $n_{\text{PUCCH}, 2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX | $n_{\text{PUCCH}, 1}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX, ACK | $n_{\text{PUCCH}, 0}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH}, 0}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK, ACK | $n_{\text{PUCCH}, 2}^{(1)}$ | 1, 0 |
| NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH}, 1}^{(1)}$ | 0, 0 |
| NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH}, 2}^{(1)}$ | 0, 0 |
| DTX, DTX, NACK | $n_{\text{PUCCH}, 2}^{(1)}$ | 0, 1 |
| DTX, NACK, NACK/DTX | $n_{\text{PUCCH}, 1}^{(1)}$ | 1, 0 |
| NACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH}, 0}^{(1)}$ | 1, 0 |
| DTX, DTX, DTX | No transmission | |

Table 10.1.3-4: Transmission of HARQ-ACK multiplexing for $M = 4$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2), HARQ-ACK(3) | $n_{\text{PUCCH}}^{(1)}$ | $b(0), b(1)$ |
|--|----------------------------|--------------|
| ACK, ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 1 |
| ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| NACK/DTX, NACK/DTX, NACK, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| NACK, DTX, DTX, DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 0 |
| ACK, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, NACK/DTX, NACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 |
| ACK, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 |
| ACK, NACK/DTX, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK, DTX, DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 0 |
| NACK/DTX, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 |
| NACK/DTX, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 0 |
| NACK/DTX, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 |
| NACK/DTX, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 |
| DTX, DTX, DTX, DTX | No transmission | |

Table 10.1.3-5: Transmission of HARQ-ACK multiplexing for $M = 2$

| HARQ-ACK(0), HARQ-ACK(1) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|--------------------------|----------------------------|------------|
| ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX | No Transmission | |

Table 10.1.3-6: Transmission of HARQ-ACK multiplexing for $M = 3$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|---------------------------------------|----------------------------|------------|
| ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 |
| NACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX, NACK/DTX | No Transmission | |

Table 10.1.3-7: Transmission of HARQ-ACK multiplexing for $M = 4$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2), HARQ-ACK(3) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|--|----------------------------|------------|
| ACK, ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 1 |
| ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},0}^{(1)}$ | 1, 0 |
| ACK, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 |
| ACK, NACK/DTX, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0, 0 |
| NACK/DTX, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 0 |
| NACK/DTX, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 |
| NACK/DTX, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 |
| NACK, NACK/DTX, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX, NACK/DTX, NACK/DTX | No Transmission | |

10.1.3.2 TDD HARQ-ACK procedure for more than one configured serving cell

If a UE configured with *EIMTA-MainConfigServCell-r12* for a serving cell, "UL/DL configuration" of the serving cell in the rest of this subclause refers to the UL/DL configuration given by the parameter *eimta-HARQ-ReferenceConfig-r12* for the serving cell unless specified otherwise.

The TDD HARQ-ACK feedback procedures for more than one configured serving cell are either based on a PUCCH format 1b with channel selection HARQ-ACK procedure as described in subclause 10.1.3.2.1 or a PUCCH format 3 HARQ-ACK procedure as described in subclause 10.1.3.2.2.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 3 and TDD with more than one configured serving cell.

If a UE is configured with more than one serving cell and the TDD UL/DL configurations of all serving cells are the same, TDD UL/DL configuration 5 with PUCCH format 3 is only supported for up to two configured serving cells. If a UE is configured with two serving cells and the TDD UL/DL configuration of the two serving cells is the same, TDD UL/DL configuration 5 with PUCCH format 1b with channel selection for two configured serving cells is not supported. If a UE is configured with two serving cells and if the TDD UL/DL configuration of the two serving cells are not the same and if the DL-reference UL/DL configuration (as defined in subclause 10.2) of at least one serving cell is TDD UL/DL Configuration 5, PUCCH format 1b with channel selection is not supported.

If a UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, the UE is not expected to be configured with more than two serving cells having UL/DL Configuration 5 as a DL-reference UL/DL configuration.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1b with channel selection and TDD with two configured serving cells.

10.1.3.2.1 PUCCH format 1b with channel selection HARQ-ACK procedure

If a UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, then $K' = K$ where the set K is defined in Table 10.1.3.1-1 (where "UL/DL configuration" in the table refers to the higher layer parameter *subframeAssignment*), and M' is the number of elements in set K' .

If a UE is configured with two serving cells with the same UL/DL configurations, then in the rest of this subclause, K is as defined in Sec 10.2 and M is the number of elements for subframe n in the set K , and $M_{primary} = M$.

If a UE is configured with two serving cells with different UL/DL configurations,

- then the UE shall determine M for a subframe n in this subclause as $M = \max(M_{primary}, M_{secondary})$, where
 - $M_{primary}$ denotes the number of elements for subframe n in the set K for the primary cell (as defined in subclause 10.2)
 - $M_{secondary}$ denotes the number of elements for subframe n in the set K_c for the secondary serving cell (as defined in subclause 10.2)
- if $M_{secondary} < M$, then the UE shall, for the secondary serving cell, set HARQ-ACK(j) to DTX for $j = M_{secondary}$ to $M - 1$.
- if $M_{primary} < M$, then the UE shall, for the primary cell, set HARQ-ACK(j) to DTX for $j = M_{primary}$ to $M - 1$.

If the UE is configured with two serving cells with different UL/DL configurations, then in the rest of this subclause, $K = K_c$ where K_c is defined in subclause 10.2.

For TDD HARQ-ACK multiplexing with PUCCH format 1b with channel selection and two configured serving cells and a subframe n with $M = 1$, a UE shall determine the number of HARQ-ACK bits, O , based on the number of configured serving cells and the downlink transmission modes configured for each serving cell. The UE shall use two

HARQ-ACK bits for a serving cell configured with a downlink transmission mode that supports up to two transport blocks; and one HARQ-ACK bit otherwise.

For TDD HARQ-ACK multiplexing with PUCCH format 1b with channel selection and two configured serving cells and a subframe n with $M \leq 2$, the UE shall transmit $b_{(0)b(1)}$ on PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ for \tilde{p} mapped to antenna port p using PUCCH format 1b where

- $n_{\text{PUCCH}}^{(1,\tilde{p})} = n_{\text{PUCCH}}^{(1)}$ for antenna port p_0 , where $n_{\text{PUCCH}}^{(1)}$ selected from A PUCCH resources, $n_{\text{PUCCH},j}^{(1)}$ where $0 \leq j \leq A-1$ and $A \in \{2,3,4\}$, according to Tables 10.1.3.2-1, 10.1.3.2-2, and 10.1.3.2-3 in subframe n using PUCCH format 1b.
- $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ for antenna port p_1 , where $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ selected from A PUCCH resources, $n_{\text{PUCCH},j}^{(1,\tilde{p}_1)}$ configured by higher layers where $0 \leq j \leq A-1$ and $A \in \{2,3,4\}$, according to Tables 10.1.3.2-1, 10.1.3.2-2, and 10.1.3.2-3 by replacing $n_{\text{PUCCH}}^{(1)}$ with $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ and replacing $n_{\text{PUCCH},i}^{(1)}$ with $n_{\text{PUCCH},i}^{(1,\tilde{p}_1)}$ in subframe n , when the UE is configured with two antenna port transmission for PUCCH format 1b with channel selection,

and for a subframe n with $M = 1$, HARQ-ACK(j) denotes the ACK/NACK/DTX response for a transport block or SPS release PDCCH/EPDCCH associated with serving cell, where the transport block and serving cell for HARQ-ACK(j) and A PUCCH resources are given by Table 10.1.2.2.1-1. For a subframe n with $M = 2$, HARQ-ACK(j) denotes the ACK/NACK/DTX response for a PDSCH transmission or SPS release PDCCH/EPDCCH within subframe(s) given by set K on each serving cell, where the subframes on each serving cell for HARQ-ACK(j) and A PUCCH resources are given by Table 10.1.3.2-4.

If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, the UE shall determine the A PUCCH resources, $n_{\text{PUCCH},j}^{(1)}$ associated with HARQ-ACK(j) where $0 \leq j \leq A-1$ in Table 10.1.2.2.1-1 for $M = 1$ and Table 10.1.3.2-4 for $M = 2$, according to

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$ on the primary cell, or for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ on the primary cell, the PUCCH resource is $n_{\text{PUCCH},j}^{(1)} = (M_{\text{primary}} - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$ where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, and for a subframe n with $M = 1$ and a transmission mode that supports up to two transport blocks on the serving cell where the corresponding PDSCH transmission occurs, the PUCCH resource $n_{\text{PUCCH},j+1}^{(1)}$ is given by $n_{\text{PUCCH},j+1}^{(1)} = (M_{\text{primary}} - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + 1 + N_{\text{PUCCH}}^{(1)}$ where $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding DCI assignment and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers.
- for a PDSCH transmission on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n - k$, where $k \in K$, the value of $n_{\text{PUCCH},j}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.
- For a PDSCH transmission indicated by the detection of corresponding EPDCCH or a EPDCCH indicating downlink SPS release in sub-frame $n - k_m$ where $k_m \in K$ on the primary cell, the PUCCH resource $n_{\text{PUCCH},j}^{(1)}$ is given by
 - if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},j}^{(1)} = n_{\text{ECCE},q} + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},j}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n-k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n-k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n-k_m$ which is described in subclause 6.8A.5 in [3]. If $m=0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m>0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n-k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n-k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n-k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n-k_{i1}$. For normal downlink CP, if subframe $n-k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n-k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For a subframe n with $M=1$ and a transmission mode that supports up to two transport blocks on the serving cell where the corresponding PDSCH transmission occurs, the PUCCH resource $n_{\text{PUCCH},j+1}^{(1)}$ is given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{ECCE},q} + 1 + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + 1 + \sum_{i=1}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH/EPDCCH within subframe(s) $n-k$, where $k \in K$ on the secondary cell, the value of $n_{\text{PUCCH},j}^{(1)}$, and the value of $n_{\text{PUCCH},j+1}^{(1)}$ for a subframe n with $M=2$ or for a subframe n with $M=1$ and a transmission mode on the secondary cell that supports up to two transport blocks is determined according to higher layer configuration and Table 10.1.2.2.1-2. The TPC field in the DCI format of the corresponding PDCCH/EPDCCH shall be used to determine the PUCCH resource values from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.1-2. For a UE configured for a transmission mode on the secondary cell that supports up to two transport blocks and a subframe n with $M=1$, or for a subframe n with $M=2$, a PUCCH resource value in Table 10.1.2.2.1-2 maps to two PUCCH resources ($n_{\text{PUCCH},j}^{(1)}, n_{\text{PUCCH},j+1}^{(1)}$), otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH},j}^{(1)}$. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted in the TPC field on all PDCCH/EPDCCH assignments on the secondary cell within subframe(s) $n-k$, where $k \in K$.

Table 10.1.3.2-1: Transmission of HARQ-ACK multiplexing for $A=2$

| HARQ-ACK(0), HARQ-ACK(1) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|--------------------------|----------------------------|------------|
| ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX | No Transmission | |

Table 10.1.3.2-2: Transmission of HARQ-ACK multiplexing for $A = 3$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|---------------------------------------|----------------------------|------------|
| ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 |
| NACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX, NACK/DTX | No Transmission | |

Table 10.1.3.2-3: Transmission of HARQ-ACK multiplexing for $A = 4$

| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2), HARQ-ACK(3) | $n_{\text{PUCCH}}^{(1)}$ | $b(0)b(1)$ |
|--|----------------------------|------------|
| ACK, ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 1 |
| ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 |
| ACK, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},0}^{(1)}$ | 1, 0 |
| ACK, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 |
| ACK, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 |
| ACK, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 |
| ACK, NACK/DTX, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 |
| NACK/DTX, ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0, 0 |
| NACK/DTX, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 |
| NACK/DTX, ACK, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 0 |
| NACK/DTX, ACK, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 |
| NACK/DTX, NACK/DTX, ACK, NACK/DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 |
| NACK/DTX, NACK/DTX, NACK/DTX, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 |
| NACK, NACK/DTX, NACK/DTX, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 |
| DTX, NACK/DTX, NACK/DTX, NACK/DTX | No Transmission | |

Table 10.1.3.2-4: Mapping of subframes on each serving cell to HARQ-ACK(j) for PUCCH format 1b HARQ-ACK channel selection for TDD with $M = 2$

| A | HARQ-ACK(j) | | | |
|---|------------------------------------|-------------------------------------|--------------------------------------|---------------------------------------|
| | HARQ-ACK(0) | HARQ-ACK(1) | HARQ-ACK(2) | HARQ-ACK(3) |
| 4 | The first subframe of Primary cell | The second subframe of Primary cell | The first subframe of Secondary cell | The second subframe of Secondary cell |

For TDD HARQ-ACK multiplexing with PUCCH format 1b with channel selection and sub-frame n with $M > 2$ and two configured serving cells, denotes $n_{\text{PUCCH},i}^{(1)}$ $0 \leq i \leq 3$ as the PUCCH resource derived from the transmissions in M downlink or special sub-frames associated with the UL subframe n . $n_{\text{PUCCH},0}^{(1)}$ and $n_{\text{PUCCH},1}^{(1)}$ are associated with the PDSCH transmission(s) or a PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) on the primary cell and $n_{\text{PUCCH},2}^{(1)}$ and $n_{\text{PUCCH},3}^{(1)}$ are associated with the PDSCH transmission(s) on the secondary cell.

For Primary cell:

- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, and if there is a PDSCH transmission on the primary cell without a corresponding PDCCH/EPDCCH detected within the subframe(s) $n-k$, where $k \in K$,
- the value of $n_{\text{PUCCH},0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.

- for a PDSCH transmission on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1' (defined in Table 7.3-X) or a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1', the PUCCH resource $n_{\text{PUCCH},1}^{(1)} = (M_{\text{primary}} - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$ where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, where $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_m$ and $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers.
- for a PDSCH transmission on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1' (defined in Table 7.3-X) or an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1', the PUCCH resource is given by

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},1}^{(1)} = n_{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},1}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. If $m = 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m > 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0.

- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, and if there is a PDSCH transmission on the primary cell without a corresponding PDCCH/EPDCCH detected within the subframe(s) $n - k$, where $k \in K$,
- the value of $n_{\text{PUCCH},0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2.

- for a PDSCH transmission on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_i$, where $k_i \in K$ with the DAI value in the PDCCH equal to '1' (defined in Table 7.3-X) or a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_i$, where $k_i \in K$ with the DAI value in the PDCCH equal to '1',
 - if the value of k_i is same as the value of an element k'_{i2} , where $k'_{i2} \in K'$, the PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is given by $n_{\text{PUCCH},1}^{(1)} = (M' - i2 - 1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},i} + N_{\text{PUCCH}}^{(1)}$;
 - otherwise, if the value of k_i is same as the value of an element k'_{i3} in set K^A , where $k'_{i3} \in K^A$ (defined in Table 10.1.3.1-1A), the PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is given by $n_{\text{PUCCH},1}^{(1)} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},i} + N_{\text{PUCCH}}^{K^A}$;

where M^A is the number of elements in the set K^A defined in Table 10.1.3.1-1A, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},i} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$

where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, $n_{\text{CCE},i}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_i$, and $N_{\text{PUCCH}}^{K^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers.

- for a PDSCH transmission on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_i$, where $k_i \in K$ with the DAI value in the EPDCCH equal to '1' (defined in Table 7.3-X) or an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_i$, where $k_i \in K$ with the DAI value in the EPDCCH equal to '1', the PUCCH resource is given by
 - If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},1}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k'_{i1}} + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},1}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k'_{i1}} + n' + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where

- if the value of k_i is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$ and $i5 = 0$;
- otherwise, if the value of k_i is same as the value of an index k'_{i3} , where $k'_{i3} \in K^A$, then $i4 = M'$ and $i5 = i3$;

, and where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_i$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_i$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. Δ'_{ARO} , $N'_{\text{ECCE},q,n-k'_{i1}}$, $N'_{\text{ECCE},q,n-k'_{i1}}$ are determined as described in section 10.1.3.1.

- HARQ-ACK(0) is the ACK/NACK/DTX response for the PDSCH transmission without a corresponding PDCCH/EPDCCH. For $1 \leq j \leq M-1$, if a PDSCH transmission with a corresponding PDCCH/EPDCCH and DAI value in the PDCCH/EPDCCH equal to 'j' or a PDCCH/EPDCCH indicating downlink SPS release and with DAI value in the PDCCH/EPDCCH equal to 'j' is received, HARQ-ACK(j) is the corresponding ACK/NACK/DTX response; otherwise HARQ-ACK(j) shall be set to DTX.
 - Otherwise,
 - If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n-k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the PDCCH equal to either '1' or '2' or a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the PDCCH equal to either '1' or '2', the PUCCH resource $n_{\text{PUCCH},i}^{(1)} = (M_{\text{primary}} - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$, where c is selected from {0, 1, 2, 3} such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$,

$$N_c = \max\left\{0, \left\lfloor \left[N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4) \right] / 36 \right\rfloor \right\}$$
, where $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n-k_m$, $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6}, $i=0$ for the corresponding PDCCH with the DAI value equal to '1' and $i=1$ for the corresponding PDCCH with the DAI value equal to '2', and for the primary cell with TDD UL/DL configuration 0 $i=0$ for the corresponding PDCCH.
 - If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n-k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the PDCCH equal to either '1' or '2' or a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the PDCCH equal to either '1' or '2',
 - if the value of k_m is same as the value of an element k'_{i2} , where $k'_{i2} \in K'$, the PUCCH resource $n_{\text{PUCCH},i}^{(1)}$ is given by $n_{\text{PUCCH},i}^{(1)} = (M' - i2 - 1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$;
 - otherwise, if the value of k_m is same as the value of an element k'_{i3} in set K^A , where $k'_{i3} \in K^A$ (defined in Table 10.1.3.1-1A), the PUCCH resource $n_{\text{PUCCH},i}^{(1)}$ is given by

$$n_{\text{PUCCH},i}^{(1)} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{\text{K}^A}$$
;
- where M^A is the number of elements in the set K^A , where c is selected from {0, 1, 2, 3} such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \left[N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4) \right] / 36 \right\rfloor \right\}$ where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n-k_m$, and $N_{\text{PUCCH}}^{\text{K}^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers. Here, for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6}, $i=0$ for the corresponding PDCCH with the DAI value equal to '1' and $i=1$ for the corresponding PDCCH with the DAI value equal to '2', and for the primary cell with TDD UL/DL configuration 0 $i=0$ for the corresponding PDCCH.
- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell for a PDSCH transmission on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n-k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the EPDCCH equal to either '1' or '2' or an EPDCCH indicating downlink SPS

release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the EPDCCH equal to either '1' or '2', the PUCCH resource is given by

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. If $m = 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m > 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. Here, for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} $i = 0$ for the corresponding EPDCCH with the DAI value equal to '1' and $i = 1$ for the corresponding EPDCCH with the DAI value equal to '2', and for the primary cell with TDD UL/DL configuration 0 $i = 0$ for the corresponding EPDCCH.

- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell for a PDSCH transmission on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the EPDCCH equal to either '1' or '2' or an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ and for TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,6} the DAI value in the EPDCCH equal to either '1' or '2', the PUCCH resource is given by

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N_{\text{ECCE},q,n-k_{i1}} + \sum_{i1=0}^{i5-1} N_{\text{ECCE},q,n-k_{i1}^A} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N_{\text{ECCE},q,n-k'_{i1}^A} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where

- if the value of k_m is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$;
- otherwise, if the value of k_m is same as the value of an index k'_{i3} , where $k'_{i3} \in K^A$, then $i4 = i3$;

, and where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. Δ'_{ARO} , $N_{\text{ECCE},q,n-k'_{i1}}$, $N_{\text{ECCE},q,n-k'_{i1}^A}$ are determined as described in section 10.1.3.1. Here, for TDD UL/DL configuration of the primary cell belonging to $\{1,2,3,4,6\}$ $i = 0$ for the corresponding EPDCCH with the DAI value equal to '1' and $i = 1$ for the corresponding EPDCCH with the DAI value equal to '2', and for the primary cell with TDD UL/DL configuration 0 $i = 0$ for the corresponding EPDCCH.

- For $0 \leq j \leq M - 1$ and TDD UL/DL configuration of the primary cell belonging to $\{1,2,3,4,6\}$, if a PDSCH transmission with a corresponding PDCCH/EPDCCH and DAI value in the PDCCH/EPDCCH equal to ' $j+1$ ' or a PDCCH/EPDCCH indicating downlink SPS release and with DAI value in the PDCCH/EPDCCH equal to ' $j+1$ ' is received, HARQ-ACK(j) is the corresponding ACK/NACK/DTX response; otherwise HARQ-ACK(j) shall be set to DTX. For $0 \leq j \leq M - 1$ and the primary cell with TDD UL/DL configuration 0, if a PDSCH transmission with a corresponding PDCCH/EPDCCH or a PDCCH/EPDCCH indicating downlink SPS release is received, HARQ-ACK(0) is the corresponding ACK/NACK/DTX response; otherwise HARQ-ACK(j) shall be set to DTX.

For Secondary cell:

- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding PDCCH on the primary cell in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to either '1' or '2', the PUCCH resources $n_{\text{PUCCH},i}^{(1)} = (M_{\text{primary}} - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{[N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)]}{36} \right\rfloor \right\}$, where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_m$, $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers, $i = 2$ for the corresponding PDCCH with the DAI value equal to '1' and $i = 3$ for the corresponding PDCCH with the DAI value equal to '2'.
- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding PDCCH on the primary cell in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to either '1' or '2',
 - if the value of k_m is same as the value of an element k'_{i2} , where $k'_{i2} \in K'$, the PUCCH resource $n_{\text{PUCCH},i}^{(1)}$ is given by $n_{\text{PUCCH},i}^{(1)} = (M' - i2 - 1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$;
 - otherwise, if the value of k_m is same as the value of an element k'_{i3} in set K^A , where $k'_{i3} \in K^A$ (defined in Table 10.1.3.1-1A, where "UL/DL configuration" in the table refers to the higher layer parameter

subframeAssignment), the PUCCH resource $n_{\text{PUCCH},i}^{(1)}$ is given by

$$n_{\text{PUCCH},i}^{(1)} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{K^A};$$

where M^A is the number of elements in the set K^A defined in Table 10.1.3.1-1A, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{[N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)]}{36} \right\rfloor\right\}$ where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_m$, and $N_{\text{PUCCH}}^{K^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers. Here, $i = 2$ for the corresponding PDCCH with the DAI value equal to '1' and $i = 3$ for the corresponding PDCCH the DAI value in the PDCCH equal to either '1' or '2'.

- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding EPDCCH on the primary cell in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to either '1' or '2', the PUCCH resources are given by

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. If $m = 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m > 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. Here, $i = 2$ for the corresponding EPDCCH with the DAI value equal to '1' and $i = 3$ for the corresponding EPDCCH with the DAI value equal to '2'.

- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding EPDCCH on the primary cell in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to either '1' or '2', the PUCCH resources are given by
- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},i}^{(1)} = n_{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k_{i1}^A} + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},i}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i1=0}^{i4-1} N'_{\text{ECCE},q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{\text{ECCE},q,n-k_{i1}^A} + n' + \Delta'_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where

- if the value of k_m is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$;
- otherwise, if the value of k_m is same as the value of an index k_{i3}^A , where $k_{i3}^A \in K^A$, then $i4 = i3$;

and where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$,

$N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. Δ'_{ARO} , $N'_{\text{ECCE},q,n-k'_{i1}}$, $N'_{\text{ECCE},q,n-k_{i1}^A}$ are determined as described in subclause 10.1.3.1. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N'_{\text{ECCE},q,n-k_{i1}}$ is equal to 0. Here, $i = 2$ for the corresponding EPDCCH with the DAI value equal to '1' and $i = 3$ for the corresponding EPDCCH with the DAI value equal to '2'.

- for a PDSCH transmission indicated by the detection of a corresponding PDCCH/EPDCCH within the subframe(s) $n - k$, where $k \in K$ on the secondary cell, the value of $n_{\text{PUCCH},2}^{(1)}$ and $n_{\text{PUCCH},3}^{(1)}$ is determined according to higher layer configuration and Table 10.1.2.2.1-2. The TPC field in the DCI format of the corresponding PDCCH/EPDCCH shall be used to determine the PUCCH resource values from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.1-2. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted in the TPC field on all PDCCH/EPDCCH assignments on the secondary cell within subframe(s) $n - k$, where $k \in K$.
- For $0 \leq j \leq M - 1$, if a PDSCH transmission with a corresponding PDCCH/EPDCCH and DAI value in the PDCCH/EPDCCH equal to ' $j + 1$ ' is received, HARQ-ACK(j) is the corresponding ACK/NACK/DTX response; otherwise HARQ-ACK(j) shall be set to DTX.

A UE shall perform channel selection according to the Tables 10.1.3.2-5, and 10.1.3.2-6 and transmit $b(0), b(1)$ on PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ for \tilde{p} mapped to antenna port p using PUCCH format 1b according to subclause 5.4.1 in [3] where

- $n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = n_{\text{PUCCH}}^{(1)}$ in sub-frame n for \tilde{p} mapped to antenna port p_0 where "any" in Tables 10.1.3.2-5, and 10.1.3.2-6 represents any response of ACK, NACK, or DTX. The value of $b(0), b(1)$ and the PUCCH resource $n_{\text{PUCCH}}^{(1)}$ are generated by channel selection according to Tables 10.1.3.2-5, and 10.1.3.2-6 for $M = 3$, and 4 respectively.
- $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ for antenna port p_1 , where $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ selected from PUCCH resources, $n_{\text{PUCCH},i}^{(1,\tilde{p}_1)}$ configured by higher layers where $0 \leq i \leq 3$ according Tables 10.1.3.2-5, and 10.1.3.2-6 for $M = 3$, and 4 respectively by replacing $n_{\text{PUCCH}}^{(1)}$ with $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ and replacing $n_{\text{PUCCH},i}^{(1)}$ with $n_{\text{PUCCH},i}^{(1,\tilde{p}_1)}$, where "any" in Tables 10.1.3.2-5, and 10.1.3.2-6 represents any response of ACK, NACK, or DTX, when the UE is configured with two antenna port transmission for PUCCH format 1b with channel selection.

Table 10.1.3.2-5: Transmission of HARQ-ACK multiplexing for $M = 3$

| Primary Cell | Secondary Cell | Resource | Constellation | RM Code Input Bits |
|--|--|----------------------------|---------------|--------------------------|
| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2) | HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2) | $n_{\text{PUCCH}}^{(1)}$ | $b(0), b(1)$ | $o(0), o(1), o(2), o(3)$ |
| ACK, ACK, ACK | ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 1, 1 | 1,1,1,1 |
| ACK, ACK, NACK/DTX | ACK, ACK, ACK | $n_{\text{PUCCH},1}^{(1)}$ | 0, 0 | 1,0,1,1 |
| ACK, NACK/DTX, any | ACK, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 | 0,1,1,1 |
| NACK/DTX, any, any | ACK, ACK, ACK | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 | 0,0,1,1 |
| ACK, ACK, ACK | ACK, ACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 1, 0 | 1,1,1,0 |
| ACK, ACK, NACK/DTX | ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 1, 0 | 1,0,1,0 |
| ACK, NACK/DTX, any | ACK, ACK, NACK/DTX | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 | 0,1,1,0 |
| NACK/DTX, any, any | ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 | 0,0,1,0 |
| ACK, ACK, ACK | ACK, NACK/DTX, any | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 | 1, 1, 0, 1 |
| ACK, ACK, NACK/DTX | ACK, NACK/DTX, any | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 | 1, 0, 0, 1 |
| ACK, NACK/DTX, any | ACK, NACK/DTX, any | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 | 0, 1, 0, 1 |
| NACK/DTX, any, any | ACK, NACK/DTX, any | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 | 0, 0, 0, 1 |
| ACK, ACK, ACK | NACK/DTX, any, any | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 | 1, 1, 0, 0 |
| ACK, ACK, NACK/DTX | NACK/DTX, any, any | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 | 1, 0, 0, 0 |
| ACK, NACK/DTX, any | NACK/DTX, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 | 0, 1, 0, 0 |
| NACK, any, any | NACK/DTX, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 | 0, 0, 0, 0 |
| DTX, any, any | NACK/DTX, any, any | No Transmission | | 0, 0, 0, 0 |

Table 10.1.3.2-6: Transmission of HARQ-ACK multiplexing for $M = 4$

| Primary Cell | Secondary Cell | Resource | Constellation | RM Code Input Bits |
|---|---|----------------------------|---------------|--------------------------|
| HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2), HARQ-ACK(3) | HARQ-ACK(0), HARQ-ACK(1), HARQ-ACK(2), HARQ-ACK(3) | $n_{\text{PUCCH}}^{(1)}$ | $b(0), b(1)$ | $o(0), o(1), o(2), o(3)$ |
| ACK, ACK, ACK, NACK/DTX | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 1, 1 | 1, 1, 1, 1 |
| ACK, ACK, NACK/DTX, any | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},1}^{(1)}$ | 0, 0 | 1, 0, 1, 1 |
| ACK, DTX, DTX, DTX | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 | 0, 1, 1, 1 |
| ACK, ACK, ACK, ACK | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 1, 1 | 0, 1, 1, 1 |
| NACK/DTX, any, any, any | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 | 0, 0, 1, 1 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | ACK, ACK, ACK, NACK/DTX | $n_{\text{PUCCH},3}^{(1)}$ | 0, 1 | 0, 0, 1, 1 |
| ACK, ACK, ACK, NACK/DTX | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},0}^{(1)}$ | 1, 0 | 1, 1, 1, 0 |
| ACK, ACK, NACK/DTX, any | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},3}^{(1)}$ | 1, 0 | 1, 0, 1, 0 |
| ACK, DTX, DTX, DTX | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 | 0, 1, 1, 0 |
| ACK, ACK, ACK, ACK | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},0}^{(1)}$ | 0, 1 | 0, 1, 1, 0 |
| NACK/DTX, any, any, any | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 | 0, 0, 1, 0 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | ACK, ACK, NACK/DTX, any | $n_{\text{PUCCH},3}^{(1)}$ | 0, 0 | 0, 0, 1, 0 |
| ACK, ACK, ACK, NACK/DTX | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 | 1, 1, 0, 1 |
| ACK, ACK, ACK, NACK/DTX | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 1 | 1, 1, 0, 1 |
| ACK, ACK, NACK/DTX, any | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 | 1, 0, 0, 1 |
| ACK, ACK, NACK/DTX, any | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 1 | 1, 0, 0, 1 |
| ACK, DTX, DTX, DTX | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 | 0, 1, 0, 1 |
| ACK, DTX, DTX, DTX | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 | 0, 1, 0, 1 |
| ACK, ACK, ACK, ACK | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 | 0, 1, 0, 1 |
| ACK, ACK, ACK, ACK | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 1, 0 | 0, 1, 0, 1 |
| NACK/DTX, any, any, any | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 | 0, 0, 0, 1 |
| NACK/DTX, any, any, any | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 | 0, 0, 0, 1 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | ACK, DTX, DTX, DTX | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 | 0, 0, 0, 1 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | ACK, ACK, ACK, ACK | $n_{\text{PUCCH},2}^{(1)}$ | 0, 0 | 0, 0, 0, 1 |
| ACK, ACK, ACK, NACK/DTX | NACK/DTX, any, any, any | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 | 1, 1, 0, 0 |
| ACK, ACK, ACK, NACK/DTX | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},1}^{(1)}$ | 1, 0 | 1, 1, 0, 0 |
| ACK, ACK, NACK/DTX, any | NACK/DTX, any, any, any | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 | 1, 0, 0, 0 |

| | | | | |
|--|--|----------------------------|------|------------|
| ACK, ACK, NACK/DTX, any | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},1}^{(1)}$ | 0, 1 | 1, 0, 0, 0 |
| ACK, DTX, DTX, DTX | NACK/DTX, any, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 | 0, 1, 0, 0 |
| ACK, DTX, DTX, DTX | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 | 0, 1, 0, 0 |
| ACK, ACK, ACK, ACK | NACK/DTX, any, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 | 0, 1, 0, 0 |
| ACK, ACK, ACK, ACK | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},0}^{(1)}$ | 1, 1 | 0, 1, 0, 0 |
| NACK, any, any, any | NACK/DTX, any, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 | 0, 0, 0, 0 |
| NACK, any, any, any | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 | 0, 0, 0, 0 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | NACK/DTX, any, any, any | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 | 0, 0, 0, 0 |
| (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | $n_{\text{PUCCH},0}^{(1)}$ | 0, 0 | 0, 0, 0, 0 |
| DTX, any, any, any | NACK/DTX, any, any, any | No Transmission | | 0, 0, 0, 0 |
| DTX, any, any, any | (ACK, NACK/DTX, any, any), except for (ACK, DTX, DTX, DTX) | No Transmission | | 0, 0, 0, 0 |

10.1.3.2.2 PUCCH format 3 HARQ-ACK procedure

If a UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*, then $K'=K$ where the set K is defined in Table 10.1.3.1-1 (where "UL/DL configuration" in the table refers to the higher layer parameter *subframeAssignment*), and M' is the number of elements in set K' .

If a UE is configured with one serving cell, or if a UE is configured with more than one serving cells and the UL/DL configuration of all serving cells is same, then in the rest of this subclause K is as defined in Sec 10.2, and M is the number of elements in the set K .

If a UE is configured with more than one serving cell and if at least two cells have different UL/DL configurations, then K in this subclause refers to K_c (as defined in subclause 10.2), and M is the number of elements in the set K .

For TDD HARQ-ACK transmission with PUCCH format 3 and sub-frame n with $M \geq 1$ and more than one configured serving cell, where M is the number of elements in the set K , the UE shall use PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ or $n_{\text{PUCCH}}^{(1,\tilde{p})}$ for transmission of HARQ-ACK in subframe n for \tilde{p} mapped to antenna port p where

- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell,
 - for a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the PDCCH is equal to '1' (defined in Table 7.3-X), or
 - for a single PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the PDCCH is equal to '1',
 - the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ with

$$n_{\text{PUCCH}}^{(1,\tilde{p}_0)} = (M - m - 1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$$
 for antenna port p_0 , where $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers, c is selected from {0, 1, 2, 3} such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$,

$$N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$$
, and $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_m$ where $k_m \in K$. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by $n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{PUCCH}}^{(1,\tilde{p}_0)} + 1$
- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell,
 - for a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the PDCCH is equal to '1' (defined in Table 7.3-X), or
 - for a single PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the PDCCH is equal to '1',
 - the UE shall use PUCCH format 1a/1b, and
 - if the value of k_m is same as the value of an element k'_{i2} , where $k'_{i2} \in K'$, the PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ is given by $n_{\text{PUCCH}}^{(1,\tilde{p})} = (M' - i2 - 1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$;
 - otherwise, if the value of k_m is same as the value of an element k^A_{i3} in set K^A , where $k^A_{i3} \in K^A$ (defined in Table 10.1.3.1-1A, where "UL/DL configuration" in the table refers to the higher

layer parameter *subframeAssignment*), the PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ is given by

$$n_{\text{PUCCH}}^{(1,\tilde{p})} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{K^A};$$

where M^A is the number of elements in the set K^A defined in Table 10.1.3.1-1A, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$,

$N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$ where $N_{\text{RB}}^{\text{DL}}$ is determined from the primary cell, $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n - k_m$, and $N_{\text{PUCCH}}^{K^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by $n_{\text{PUCCH}}^{(1,\tilde{p}_1)} = n_{\text{PUCCH}}^{(1,\tilde{p}_0)} + 1$

- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell,
 - for a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$ the DAI value in the EPDCCH is equal to '1' (defined in Table 7.3-X), or
 - for a single PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to $\{1,2,3,4,5,6\}$ the DAI value in the EPDCCH is equal to '1',
- the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p})}$ given by

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p})} = n_{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH}}^{(1,\tilde{p})} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. If $m = 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m > 0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{\text{ECCE},q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5,

$N_{ECCE,q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n-k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{ECCE,q,n-k_{i1}}$ is equal to 0. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by $n_{PUCCH}^{(1,\tilde{p}_1)} = n_{PUCCH}^{(1,\tilde{p}_0)} + 1$.

- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell,
 - for a single PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n-k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the EPDCCH is equal to '1' (defined in Table 7.3-X), or
 - for a single PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$, and for a TDD UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} the DAI value in the EPDCCH is equal to '1',

- the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{PUCCH}^{(1,\tilde{p})}$ given by

- if EPDCCH-PRB-set q is configured for distributed transmission

$$n_{PUCCH}^{(1,\tilde{p})} = n_{ECCE,q} + \sum_{i1=0}^{i4-1} N'_{ECCE,q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{ECCE,q,n-k^A_{i1}} + \Delta'_{ARO} + N_{PUCCH,q}^{(e1)}$$

- if EPDCCH-PRB-set q is configured for localized transmission

$$n_{PUCCH}^{(1,\tilde{p})} = \left\lfloor \frac{n_{ECCE,q}}{N_{RB}^{ECCE,q}} \right\rfloor \cdot N_{RB}^{ECCE,q} + \sum_{i1=0}^{i4-1} N'_{ECCE,q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{ECCE,q,n-k^A_{i1}} + n' + \Delta'_{ARO} + N_{PUCCH,q}^{(e1)}$$

where

- if the value of k_m is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$;
- otherwise, if the value of k_m is same as the value of an index k^A_{i3} , where $k^A_{i3} \in K^A$, then $i4 = i3$;

and where $n_{ECCE,q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n-k_m$, $N_{PUCCH,q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{RB}^{ECCE,q}$ for EPDCCH-PRB-set q in subframe $n-k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n-k_m$ which is described in subclause 6.8A.5 in [3]. Δ'_{ARO} , $N'_{ECCE,q,n-k'_{i1}}$, $N'_{ECCE,q,n-k^A_{i1}}$ are determined as described in section 10.1.3.1. When two antenna port transmission is configured for PUCCH format 1a/1b, the PUCCH resource for antenna port p_1 is given by $n_{PUCCH}^{(1,\tilde{p}_1)} = n_{PUCCH}^{(1,\tilde{p}_0)} + 1$.

- for a single PDSCH transmission only on the primary cell where there is not a corresponding PDCCH/EPDCCH detected within subframe(s) $n-k$, where $k \in K$ and no PDCCH/EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, the UE shall use PUCCH format 1a/1b and PUCCH resource $n_{PUCCH}^{(1,\tilde{p})}$ with the value of $n_{PUCCH}^{(1,\tilde{p})}$ is determined according to higher layer configuration and Table 9.2-2. For a UE configured for two antenna port transmission for PUCCH format 1a/1b, a PUCCH resource value in Table 9.2-2 maps to two PUCCH resources with the first PUCCH resource $n_{PUCCH}^{(1,\tilde{p}_0)}$ for

antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(1,\tilde{p}_0)}$ for antenna port p_0 .

- for $M > 1$, and
- for a PDSCH transmission only on the primary cell where there is not a corresponding PDCCH detected within subframe(s) $n-k$, where $k \in K$, and
- for an additional PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n-k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1' (defined in Table 7.3-X), or
- for an additional PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1',
- the UE shall transmit $b(0), b(1)$ in subframe n using PUCCH format 1b on PUCCH resource $n_{\text{PUCCH}}^{(1)}$ selected from A PUCCH resources $n_{\text{PUCCH},i}^{(1)}$ where $0 \leq i \leq A-1$, according to Table 10.1.3.2-1 and Table 10.1.3.2-2 for $A=2$ and $A=3$, respectively. For a UE configured with a transmission mode that supports up to two transport blocks on the primary cell, $A=3$; otherwise, $A=2$.
- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, the PUCCH resource $n_{\text{PUCCH},0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2. The PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is determined as $n_{\text{PUCCH},1}^{(1)} = (M-m-1) \cdot N_c + m \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$, where $N_{\text{PUCCH}}^{(1)}$ is configured by higher layers, c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$, $N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, and $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n-k_m$ where $k_m \in K$.
- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, the PUCCH resource $n_{\text{PUCCH},0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2. The PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is determined as
 - if the value of k_m is same as the value of an element k'_{i2} , where $k'_{i2} \in K'$, the PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is given by $n_{\text{PUCCH},1}^{(1)} = (M'-i2-1) \cdot N_c + i2 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{(1)}$;
 - otherwise, if the value of k_m is same as the value of an element k'_{i3} in set K^A , where $k'_{i3} \in K^A$ (defined in Table 10.1.3.1-1A, where "UL/DL configuration" in the table refers to the higher layer parameter *subframeAssignment*), the PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is given by $n_{\text{PUCCH},1}^{(1)} = (M^A - i3 - 1) \cdot N_c + i3 \cdot N_{c+1} + n_{\text{CCE},m} + N_{\text{PUCCH}}^{K^A}$;

where M^A is the number of elements in the set K^A defined in Table 10.1.3.1-1A, where c is selected from $\{0, 1, 2, 3\}$ such that $N_c \leq n_{\text{CCE},m} < N_{c+1}$,

$N_c = \max\left\{0, \left\lfloor \frac{N_{\text{RB}}^{\text{DL}} \cdot (N_{\text{sc}}^{\text{RB}} \cdot c - 4)}{36} \right\rfloor\right\}$, $n_{\text{CCE},m}$ is the number of the first CCE used for transmission of the corresponding PDCCH in subframe $n-k_m$, and $N_{\text{PUCCH}}^{K^A}$, $N_{\text{PUCCH}}^{(1)}$, are configured by higher layers.

- For a UE configured with a transmission mode that supports up to two transport blocks on the primary cell, the PUCCH resource $n_{\text{PUCCH},2}^{(1)}$ is determined as $n_{\text{PUCCH},2}^{(1)} = n_{\text{PUCCH},1}^{(1)} + 1$. HARQ-ACK(0) is the ACK/NACK/DTX response for the PDSCH without a corresponding PDCCH detected. HARQ-ACK(1) is the ACK/NACK/DTX response for the first transport block of the PDSCH indicated by the detection of a corresponding PDCCH for which the value of the DAI field in the corresponding DCI format is equal to '1' or for the PDCCH indicating downlink SPS release for which the value of the DAI field in the corresponding DCI format is equal to '1'. HARQ-ACK(2) is the ACK/NACK/DTX response for the second transport block of the PDSCH indicated by the detection of a corresponding PDCCH for which the value of the DAI field in the corresponding DCI format is equal to '1'.
- for $M > 1$, and
- for a PDSCH transmission only on the primary cell where there is not a corresponding EPDCCH detected within subframe(s) $n-k$, where $k \in K$, and
- for an additional PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n-k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1' (defined in Table 7.3-X), or
- for an additional EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n-k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1',
- the UE shall transmit $b(0), b(1)$ in subframe n using PUCCH format 1b on PUCCH resource $n_{\text{PUCCH}}^{(1)}$ selected from A PUCCH resources $n_{\text{PUCCH},i}^{(1)}$ where $0 \leq i \leq A-1$, according to Table 10.1.3.2-1 and Table 10.1.3.2-2 for $A=2$ and $A=3$, respectively. For a UE configured with a transmission mode that supports up to two transport blocks on the primary cell, $A=3$; otherwise, $A=2$.
- If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, the PUCCH resource $n_{\text{PUCCH},0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2. The PUCCH resource $n_{\text{PUCCH},1}^{(1)}$ is determined as

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{\text{PUCCH},1}^{(1)} = n_{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{\text{PUCCH},1}^{(1)} = \left\lfloor \frac{n_{\text{ECCE},q}}{N_{\text{RB}}^{\text{ECCE},q}} \right\rfloor \cdot N_{\text{RB}}^{\text{ECCE},q} + \sum_{i=0}^{m-1} N_{\text{ECCE},q,n-k_{i1}} + n' + \Delta_{\text{ARO}} + N_{\text{PUCCH},q}^{(e1)}$$

where $n_{\text{ECCE},q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n-k_m$, $N_{\text{PUCCH},q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{\text{RB}}^{\text{ECCE},q}$ for EPDCCH-PRB-set q in subframe $n-k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n-k_m$ which is described in subclause 6.8A.5 in [3]. If $m=0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.2.1-1. If $m>0$, Δ_{ARO} is determined from the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH as given in Table 10.1.3.1-2. If the UE is configured to monitor EPDCCH in subframe $n-k_{i1}$,

$N_{ECCE,q,n-k_{i1}}$ is equal to the number of ECCEs in EPDCCH-PRB-set q configured for that UE in subframe $n - k_{i1}$. If the UE is not configured to monitor EPDCCH in subframe $n - k_{i1}$, $N_{ECCE,q,n-k_{i1}}$ is equal to the number of ECCEs computed assuming EPDCCH-PRB-set q is configured for that UE in subframe $n - k_{i1}$. For normal downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 5, $N_{ECCE,q,n-k_{i1}}$ is equal to 0. For extended downlink CP, if subframe $n - k_{i1}$ is a special subframe with special subframe configuration 0 or 4 or 7, $N_{ECCE,q,n-k_{i1}}$ is equal to 0.

- If the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* on the primary cell, the PUCCH resource $n_{PUCCH,0}^{(1)}$ is determined according to higher layer configuration and Table 9.2-2. The PUCCH resource $n_{PUCCH,1}^{(1)}$ is determined as

- If EPDCCH-PRB-set q is configured for distributed transmission

$$n_{PUCCH,i}^{(1)} = n_{ECCE,q} + \sum_{i1=0}^{i4-1} N'_{ECCE,q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{ECCE,q,n-k'_{i1}^A} + \Delta'_{ARO} + N_{PUCCH,q}^{(e1)}$$

- If EPDCCH-PRB-set q is configured for localized transmission

$$n_{PUCCH,i}^{(1)} = \left\lfloor \frac{n_{ECCE,q}}{N_{RB}^{ECCE,q}} \right\rfloor \cdot N_{RB}^{ECCE,q} + \sum_{i1=0}^{i4-1} N'_{ECCE,q,n-k'_{i1}} + \sum_{i1=0}^{i5-1} N'_{ECCE,q,n-k'_{i1}^A} + n' + \Delta'_{ARO} + N_{PUCCH,q}^{(e1)}$$

where

- if the value of k_m is same as the value of an index k'_{i2} , where $k'_{i2} \in K'$, then $i4 = i2$;
- otherwise, if the value of k_m is same as the value of an index k'_{i3}^A , where $k'_{i3}^A \in K^A$, then $i4 = i3$;
- and where $n_{ECCE,q}$ is the number of the first ECCE (i.e. lowest ECCE index used to construct the EPDCCH) used for transmission of the corresponding DCI assignment in EPDCCH-PRB-set q in subframe $n - k_m$, $N_{PUCCH,q}^{(e1)}$ for EPDCCH-PRB-set q is configured by the higher layer parameter *pucch-ResourceStartOffset-r11*, $N_{RB}^{ECCE,q}$ for EPDCCH-PRB-set q in subframe $n - k_m$ is given in subclause 6.8A.1 in [3], n' is determined from the antenna port used for EPDCCH transmission in subframe $n - k_m$ which is described in subclause 6.8A.5 in [3]. Δ'_{ARO} , $N'_{ECCE,q,n-k'_{i1}}$, $N'_{ECCE,q,n-k'_{i1}^A}$ are determined as described in section 10.1.3.1.
- For a UE configured with a transmission mode that supports up to two transport blocks on the primary cell, the PUCCH resource $n_{PUCCH,2}^{(1)}$ is determined as $n_{PUCCH,2}^{(1)} = n_{PUCCH,1}^{(1)} + 1$. HARQ-ACK(0) is the ACK/NACK/DTX response for the PDSCH without a corresponding EPDCCH detected. HARQ-ACK(1) is the ACK/NACK/DTX response for the first transport block of the PDSCH indicated by the detection of a corresponding EPDCCH for which the value of the DAI field in the corresponding DCI format is equal to '1' or for the EPDCCH indicating downlink SPS release for which the value of the DAI field in the corresponding DCI format is equal to '1'. HARQ-ACK(2) is the ACK/NACK/DTX response for the second transport block of the PDSCH indicated by the detection of a corresponding EPDCCH for which the value of the DAI field in the corresponding DCI format is equal to '1'.

- for $M > 1$, and

- for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH greater than '1' (defined in Table 7.3-X), or
- for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH greater than '1', or
- for $M = 9$ and for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding PDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1' (defined in Table 7.3-X) not being the first PDCCH/EPDCCH transmission in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', or
- for $M = 9$ and for a PDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the PDCCH equal to '1' (defined in Table 7.3-X) not being the first PDCCH/EPDCCH transmission in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', or
- the UE shall use PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(3,\tilde{p})}$ is determined according to higher layer configuration and Table 10.1.2.2.2-1 and the TPC field in a PDCCH assignment with DAI value greater than '1' (defined in Table 7.3-X) or with DAI value equal to '1', not being the first PDCCH/EPDCCH assignment in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', shall be used to determine the PUCCH resource value from one of the four PUCCH resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all PDCCH assignments used to determine the PUCCH resource values within the subframe(s) $n - k$, where $k \in K$.
- for $M > 1$, and
 - for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH greater than '1' (defined in Table 7.3-X), or
 - for an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH greater than '1', or
 - for $M = 9$ and for a PDSCH transmission only on the primary cell indicated by the detection of a corresponding EPDCCH in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1' (defined in Table 7.3-X) not being the first PDCCH/EPDCCH transmission in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', or
 - for $M = 9$ and for an EPDCCH indicating downlink SPS release (defined in subclause 9.2) in subframe $n - k_m$, where $k_m \in K$ with the DAI value in the EPDCCH equal to '1' (defined in Table 7.3-X) not being the first PDCCH/EPDCCH transmission in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', or
 - the UE shall use PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(3,\tilde{p})}$ is determined according to higher layer configuration and Table 10.1.2.2.2-1 and the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH assignment with DAI value greater than '1' or with DAI value equal to '1' (defined in Table 7.3-X), not being the first PDCCH/EPDCCH assignment in subframe(s) $n - k$, where $k \in K$ with the DAI value equal to '1', shall be used to determine the PUCCH resource value from one of the four PUCCH resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all EPDCCH assignments used to determine the PUCCH resource values within the subframe(s) $n - k$, where $k \in K$.
- If the UL/DL configurations of all serving cells are the same, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding PDCCH/EPDCCH within subframe(s) $n - k$, where $k \in K$, the UE shall use PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(3,\tilde{p})}$ is determined according to higher layer configuration and Table 10.1.2.2.2-1 and the TPC field in the corresponding

PDCCH/EPDCCH shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. For TDD UL/DL configurations 1-6, if a PDCCH corresponding to a PDSCH on the primary cell within subframe(s) $n-k$, where $k \in K$, or a PDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, is detected, the TPC field in the PDCCH with the DAI value greater than '1' or with DAI value equal to '1', not being the first PDCCH/EPDCCH transmission in subframe(s) $n-k$, where $k \in K$ with the DAI value equal to '1' (defined in Table 7.3-X), shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all PDCCH assignments in the primary cell and in each secondary cell that are used to determine the PUCCH resource value within the subframe(s) $n-k$, where $k \in K$. For TDD UL/DL configurations 1-6, if an EPDCCH corresponding to a PDSCH on the primary cell within subframe(s) $n-k$, where $k \in K$, or an EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, is detected, the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH assignment with the DAI value greater than '1' (defined in Table 7.3-X) or with DAI value equal to '1', not being the first PDCCH/EPDCCH transmission in subframe(s) $n-k$, where $k \in K$ with the DAI value equal to '1', shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all EPDCCH assignments in the primary cell and in each secondary cell that are used to determine the PUCCH resource value within the subframe(s) $n-k$, where $k \in K$.

- If the UL/DL configurations of at least two serving cells are different, for a PDSCH transmission on the secondary cell indicated by the detection of a corresponding PDCCH/EPDCCH within subframe(s) $n-k$, where $k \in K$, the UE shall use PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ where the value of $n_{\text{PUCCH}}^{(3,\tilde{p})}$ is determined according to higher layer configuration and Table 10.1.2.2.2-1 and the TPC field in the corresponding PDCCH/EPDCCH shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. For a UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} as defined in subclause 10.2, if a PDCCH corresponding to a PDSCH on the primary cell within subframe(s) $n-k$, where $k \in K$, or a PDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, is detected, the TPC field in the PDCCH with the DAI value greater than '1' (defined in Table 7.3-X) or with DAI value equal to '1', not being the first PDCCH/EPDCCH transmission in subframe(s) $n-k$, where $k \in K$ with the DAI value equal to '1', shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all PDCCH assignments in the primary cell and in each secondary cell that are used to determine the PUCCH resource value within the subframe(s) $n-k$, where $k \in K$. For a UL/DL configuration of the primary cell belonging to {1,2,3,4,5,6} as defined in subclause 10.2, if an EPDCCH corresponding to a PDSCH on the primary cell within subframe(s) $n-k$, where $k \in K$, or an EPDCCH indicating downlink SPS release (defined in subclause 9.2) within subframe(s) $n-k$, where $k \in K$, is detected, the HARQ-ACK resource offset field in the DCI format of the corresponding EPDCCH assignment with the DAI value greater than '1' or with DAI value equal to '1', not being the first PDCCH/EPDCCH transmission in subframe(s) $n-k$, where $k \in K$ with the DAI value equal to '1', shall be used to determine the PUCCH resource value from one of the four resource values configured by higher layers, with the mapping defined in Table 10.1.2.2.2-1. A UE shall assume that the same HARQ-ACK PUCCH resource value is transmitted on all EPDCCH assignments in the primary cell and in each secondary cell that are used to determine the PUCCH resource value within the subframe(s) $n-k$, where $k \in K$.
- For PUCCH format 3 and PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p})}$ and a UE configured for two antenna port transmission, a PUCCH resource value in Table 10.1.2.2.2-1 maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_0)}$ for antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH}}^{(3,\tilde{p}_0)}$ for antenna port p_0 .

10.1.3A FDD-TDD HARQ-ACK feedback procedures for primary cell frame structure type 2

A UE is configured by higher layers to use either PUCCH format 1b with channel selection or PUCCH format 3 for transmission of HARQ-ACK.

For a serving cell, if the serving cell is frame structure type 1, and a UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, set K is defined in Table 10.1.3A-1, otherwise set K is defined in Table 10.1.3.1-1.

PUCCH format 1b with channel selection is not supported if a UE is configured with more than two serving cells, or if the DL-reference UL/DL configuration 5 (as defined in subclause 10.2) is defined for any serving cell, or if the DL-reference UL/DL configuration of a serving cell with frame structure type 1 belongs to {2, 3, 4} and the UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell.

If a UE is configured with the parameter *EIMTA-MainConfigServCell-r12* for at least one serving cell, the UE is not expected to be configured with more than two serving cells having DL-reference UL/DL configuration 5.

If a UE is configured to use PUCCH format 1b with channel selection for HARQ-ACK transmission, for the serving cells,

- if more than 4 HARQ-ACK bits for M multiple downlink and special subframes associated with a single UL subframe n , where M is as defined in subclause 10.1.3.2.1 for case where the UE is configured with two serving cells with different UL/DL configurations,
- spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed for each serving cell by a logical AND operation of all the corresponding individual HARQ-ACKs, and the bundled HARQ-ACK bits for each serving cell is transmitted using PUCCH format 1b with channel selection,
- otherwise,
- spatial HARQ-ACK bundling is not performed, and the HARQ-ACK bits are transmitted using PUCCH format 1b with channel selection.

If a UE is configured to use PUCCH format 3 for HARQ-ACK transmission, for the serving cells,

- if more than 21 HARQ-ACK bits for M multiple downlink and special subframes associated with a single UL subframe n , where M as defined in subclause 10.1.3.2.2 for the case of UE configured with more than one serving cell and if at least two cells have different UL/DL configurations,
- spatial HARQ-ACK bundling across multiple codewords within a downlink or special subframe is performed for each serving cell by a logical AND operation of all of the corresponding individual HARQ-ACKs, and PUCCH format 3 is used,
- otherwise,
- spatial HARQ-ACK bundling is not performed, and the HARQ-ACK bits are transmitted using PUCCH format 3.

- UE shall determine the number of HARQ-ACK bits, O , associated with an UL subframe n according to

$$O = \sum_{c=1}^{N_{cells}^{DL}} O_c^{ACK} \quad \text{where } N_{cells}^{DL} \text{ is the number of configured cells, and } O_c^{ACK} \text{ is the number of HARQ-bits for}$$

the c -th serving cell defined in subclause 7.3.4. If a UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling a serving cell with frame structure type 1, and the DL-reference UL/DL configuration of the serving cell belongs to {2, 3, 4, 5}, then the UE is not expected to be configured with N_{cells}^{DL} which result in $O > 21$.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 3.

HARQ-ACK transmission on two antenna ports ($p \in [p_0, p_1]$) is supported for PUCCH format 1b with channel selection and with two configured serving cells.

The FDD-TDD HARQ-ACK feedback procedure for PUCCH format 1b with channel selection follows the HARQ-ACK procedure described in subclause 10.1.3.2.1 for the case of UE configured with two serving cells with different UL/DL configurations, and for PUCCH format 3 follows the HARQ-ACK procedure described in subclause 10.1.3.2.2 for the case of UE configured with more than one serving cell and if at least two cells have different UL/DL configurations.

Table 10.1.3A-1: Downlink association set $K : \{k_0, k_1, \dots, k_{M-1}\}$ for FDD-TDD and serving cell frame structure type 1

| DL-reference UL/DL Configuration | Subframe n | | | | | | | | | |
|----------------------------------|--------------|---|----------------------------------|------------|------|---|---|---------------|---------|---|
| | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0 | - | - | 6, 5 | 5, 4 | 4 | - | - | 6, 5 | 5, 4 | 4 |
| 1 | - | - | 7, 6 | 6, 5, 4 | - | - | - | 7, 6 | 6, 5, 4 | - |
| 2 | - | - | 8, 7, 6, 5, 4 | - | - | - | - | 8, 7, 6, 5, 4 | - | - |
| 3 | - | - | 11, 10, 9, 8, 7, 6 | 6, 5 | 5, 4 | - | - | - | - | - |
| 4 | - | - | 12, 11, 10, 9, 8, 7 | 7, 6, 5, 4 | - | - | - | - | - | - |
| 5 | - | - | 13, 12, 11, 10, 9, 8, 7, 6, 5, 4 | - | - | - | - | - | - | - |
| 6 | - | - | 8, 7 | 7, 6 | 6, 5 | - | - | 7 | 7, 6, 5 | - |

10.1.4 HARQ-ACK Repetition procedure

HARQ-ACK repetition is enabled or disabled by a UE specific parameter *ackNackRepetition* configured by higher layers. Once enabled, the UE shall repeat any HARQ-ACK transmission with a repetition factor N_{ANRep} , where N_{ANRep} is provided by higher layers and includes the initial HARQ-ACK transmission, until HARQ-ACK repetition is disabled by higher layers. For a PDSCH transmission without a corresponding PDCCH/EPDCCH detected, the UE shall transmit the corresponding HARQ-ACK response N_{ANRep} times using PUCCH resource $n_{\text{PUCCH}}^{(1, \tilde{p})}$ configured by higher layers. For a PDSCH transmission with a corresponding PDCCH/EPDCCH detected, or for a PDCCH/EPDCCH indicating downlink SPS release, the UE shall first transmit the corresponding HARQ-ACK response once using PUCCH resource derived from the corresponding PDCCH CCE index or EPDCCH ECCE index (as described in subclauses 10.1.2 and 10.1.3), and repeat the transmission of the corresponding HARQ-ACK response $N_{\text{ANRep}} - 1$ times always using PUCCH resource $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p})}$, where $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p})}$ is configured by higher layers.

HARQ-ACK repetition is only applicable for UEs configured with one serving cell for FDD and TDD. For TDD, HARQ-ACK repetition is only applicable for HARQ-ACK bundling.

HARQ-ACK repetition can be enabled with PUCCH format 1a/1b on two antenna ports. For a UE configured for two antenna port transmission for HARQ-ACK repetition with PUCCH format 1a/1b, a PUCCH resource value $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p})}$ maps to two PUCCH resources with the first PUCCH resource $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p}_0)}$ for antenna port p_0 and the second PUCCH resource $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p}_1)}$ for antenna port p_1 , otherwise, the PUCCH resource value maps to a single PUCCH resource $n_{\text{PUCCH,ANRep}}^{(1, \tilde{p}_0)}$ for antenna port p_0 .

10.1.5 Scheduling Request (SR) procedure

A UE is configured by higher layers to transmit the SR on one antenna port or two antenna ports.

The scheduling request shall be transmitted on the PUCCH resource(s) $n_{\text{PUCCH}}^{(1,\tilde{p})} = n_{\text{PUCCH,SRI}}^{(1,\tilde{p})}$ for \tilde{p} mapped to antenna port p as defined in [3], where $n_{\text{PUCCH,SRI}}^{(1,\tilde{p})}$ is configured by higher layers unless the SR coincides in time with the transmission of HARQ-ACK using PUCCH Format 3 in which case the SR is multiplexed with HARQ-ACK according to subclause 5.2.3.1 of [4]. The SR configuration for SR transmission periodicity $SR_{\text{PERIODICITY}}$ and SR subframe offset $N_{\text{OFFSET,SR}}$ is defined in Table 10.1.5-1 by the parameter *sr-ConfigIndex* I_{SR} given by higher layers.

SR transmission instances are the uplink subframes satisfying

$$(10 \times n_f + \lfloor n_s / 2 \rfloor - N_{\text{OFFSET,SR}}) \bmod SR_{\text{PERIODICITY}} = 0.$$

Table 10.1.5-1: UE-specific SR periodicity and subframe offset configuration

| SR configuration Index I_{SR} | SR periodicity (ms) $SR_{\text{PERIODICITY}}$ | SR subframe offset $N_{\text{OFFSET,SR}}$ |
|---|--|--|
| 0 – 4 | 5 | I_{SR} |
| 5 – 14 | 10 | $I_{\text{SR}} - 5$ |
| 15 – 34 | 20 | $I_{\text{SR}} - 15$ |
| 35 – 74 | 40 | $I_{\text{SR}} - 35$ |
| 75 – 154 | 80 | $I_{\text{SR}} - 75$ |
| 155 – 156 | 2 | $I_{\text{SR}} - 155$ |
| 157 | 1 | $I_{\text{SR}} - 157$ |

10.2 Uplink HARQ-ACK timing

For TDD or for FDD-TDD and primary cell frame structure type 2 or for FDD-TDD and primary cell frame structure type 1, if a UE configured with *EIMTA-MainConfigServCell-r12* for a serving cell, “UL/DL configuration” of the serving cell in subclause 10.2 refers to the UL/DL configuration given by the parameter *eimta-HARQ-ReferenceConfig-r12* for the serving cell unless specified otherwise.

For FDD or for FDD-TDD and primary cell frame structure type 1, the UE shall upon detection of a PDSCH transmission in subframe $n-4$ intended for the UE and for which an HARQ-ACK shall be provided, transmit the HARQ-ACK response in subframe n . If HARQ-ACK repetition is enabled, upon detection of a PDSCH transmission in subframe $n-4$ intended for the UE and for which HARQ-ACK response shall be provided, and if the UE is not repeating the transmission of any HARQ-ACK in subframe n corresponding to a PDSCH transmission in subframes $n - N_{\text{ANRep}} - 3, \dots, n - 5$, the UE:

- shall transmit only the HARQ-ACK response (corresponding to the detected PDSCH transmission in subframe $n - 4$) on PUCCH in subframes $n, n+1, \dots, n + N_{\text{ANRep}} - 1$;
- shall not transmit any other signal/channel in subframes $n, n+1, \dots, n + N_{\text{ANRep}} - 1$; and
- shall not transmit any HARQ-ACK response repetitions corresponding to any detected PDSCH transmission in subframes $n - 3, \dots, n + N_{\text{ANRep}} - 5$.

For TDD and a UE configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell, if the UE is configured with one serving cell or if the UE is configured with more than one serving cell and the TDD UL/DL configuration of all the configured serving cells is the same, the DL-reference UL/DL configuration for a serving cell is the UL/DL configuration of the serving cell.

For FDD-TDD and primary cell frame structure type 1, if a serving cell is a secondary serving cell with frame structure type 2, the DL-reference UL/DL configuration for the serving cell is the UL/DL configuration of the serving cell.

For TDD, if the UE is configured with more than one serving cell and if at least two serving cells have different UL/DL configurations and if a serving cell is a primary cell, then the primary cell UL/DL configuration is the DL-reference UL/DL configuration for the serving cell.

For FDD-TDD and primary cell frame structure type 2, if a serving cell is a primary cell or if a serving cell is a secondary cell with frame structure type 1, then the primary cell UL/DL configuration is the DL-reference UL/DL configuration for the serving cell.

For TDD and if the UE is configured with more than one serving cell and if at least two serving cells have different UL/DL configurations and if a serving cell is a secondary cell, or for FDD-TDD and primary cell frame structure type 2 and if a serving cell is a secondary cell with frame structure type 2

- if the pair formed by (primary cell UL/DL configuration, serving cell UL/DL configuration) belongs to Set 1 in Table 10.2-1 or
- if the UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, and if the pair formed by (primary cell UL/DL configuration, serving cell UL/DL configuration) belongs to Set 2 or Set 3 in Table 10.2-1 or
- if the UE is configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell, and if the pair formed by (primary cell UL/DL configuration, serving cell UL/DL configuration) belongs to Set 4 or Set 5 in Table 10.2-1

then the DL-reference UL/DL configuration for the serving cell is defined in the corresponding Set in Table 10.2-1.

For TDD and if a UE is configured with more than one serving cell and if at least two serving cells have different UL/DL configurations or for FDD-TDD and primary cell frame structure type 2, if the DL-reference UL/DL configuration for at least one serving cell is TDD UL/DL Configuration 5, then the UE is not expected to be configured with more than two serving cells.

For TDD and a UE not configured with *EIMTA-MainConfigServCell-r12* for any serving cell, if the UE is configured with one serving cell, or the UE is configured with more than one serving cell and the UL/DL configurations of all serving cells is same, then the UE shall upon detection of a PDSCH transmission within subframe(s) $n - k$, where

$k \in K$ and K is defined in Table 10.1.3.1-1 intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in UL subframe n .

For TDD and if a UE is configured with more than one serving cell and if at least two serving cells have different UL/DL configurations, or if a UE is configured with *EIMTA-MainConfigServCell-r12* for at least one serving cell. or for FDD-TDD and primary cell frame structure type 2 and if a serving cell c is frame structure type 2, then the UE shall upon detection of a PDSCH transmission within subframe(s) $n-k$ for serving cell c , where $k \in K_c$ intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in UL subframe n , wherein set K_c contains values of $k \in K$ such that subframe $n-k$ corresponds to a DL subframe or a special subframe for serving cell c , where DL subframe or special subframe of serving cell c is according to the higher layer parameter *eimta-HARQ-ReferenceConfig-r12* if the UE is configured with the higher layer parameter *EIMTA-MainConfigServCell-r12* for serving cell c ; K defined in Table 10.1.3.1-1 (where "UL/DL configuration" in Table 10.1.3.1-1 refers to the "DL-reference UL/DL configuration") is associated with subframe n .

For FDD-TDD and primary cell frame structure type 2, if a serving cell c is frame structure type 1 and a UE is not configured to monitor PDCCH/EPDCCH in another serving cell for scheduling the serving cell c , then the UE shall upon detection of a PDSCH transmission within subframe(s) $n-k$ for serving cell c , where $k \in K_c$, $K_c = K$ and K is defined in Table 10.1.3A-1 intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in subframe n .

For FDD-TDD and primary cell frame structure type 2, if a serving cell c is frame structure type 1 and a UE is configured to monitor PDCCH/EPDCCH in another serving cell for scheduling serving cell c , then the UE shall upon detection of a PDSCH transmission within subframe(s) $n-k$ for serving cell c , where $k \in K_c$, $K_c = K$ and K is defined in Table 10.1.3.1-1, intended for the UE and for which HARQ-ACK response shall be provided, transmit the HARQ-ACK response in subframe n , where "UL/DL configuration" in Table 10.1.3.1-1 refers to the "DL-reference UL/DL configuration" of serving cell c .

For TDD, if HARQ-ACK repetition is enabled, upon detection of a PDSCH transmission within subframe(s) $n-k$, where $k \in K$ and K is defined in Table 10.1.3.1-1 intended for the UE and for which HARQ-ACK response shall be provided, and if the UE is not repeating the transmission of any HARQ-ACK in subframe n corresponding to a PDSCH transmission in a downlink or special subframe earlier than subframe $n-k$, the UE:

- shall transmit only the HARQ-ACK response (corresponding to the detected PDSCH transmission in subframe $n-k$) on PUCCH in UL subframe n and the next $N_{\text{ANRep}} - 1$ UL subframes denoted as $n_1, \dots, n_{N_{\text{ANRep}} - 1}$;
- shall not transmit any other signal/channel in UL subframe $n, n_1, \dots, n_{N_{\text{ANRep}} - 1}$; and
- shall not transmit any HARQ-ACK response repetitions corresponding to any detected PDSCH transmission in subframes $n_i - k$, where $k \in K_i$, K_i is the set defined in Table 10.1.3.1-1 corresponding to UL subframe n_i , and $1 \leq i \leq N_{\text{ANRep}} - 1$.

For TDD, HARQ-ACK bundling, if the UE detects that at least one downlink assignment has been missed as described in subclause 7.3, the UE shall not transmit HARQ-ACK on PUCCH if HARQ-ACK is the only UCI present in a given subframe.

The uplink timing for the ACK corresponding to a detected PDCCH/EPDCCH indicating downlink SPS release shall be the same as the uplink timing for the HARQ-ACK corresponding to a detected PDSCH, as defined above.

Table 10.2-1: DL-reference UL/DL configuration for serving cell based on pair formed by (primary cell UL/DL configuration, secondary cell UL/DL configuration)

| Set # | (Primary cell UL/DL configuration, Secondary cell UL/DL configuration) | DL-reference UL/DL configuration |
|-------|---|-------------------------------------|
| Set 1 | (0,0) | 0 |
| | (1,0),(1,1),(1,6) | 1 |
| | (2,0),(2,2),(2,1),(2,6) | 2 |
| | (3,0),(3,3),(3,6) | 3 |
| | (4,0),(4,1),(4,3),(4,4),(4,6) | 4 |
| | (5,0),(5,1),(5,2),(5,3),(5,4),(5,5),(5,6) | 5 |
| | (6,0),(6,6) | 6 |
| Set 2 | (0,1),(6,1) | 1 |
| | (0,2),(1,2),(6,2) | 2 |
| | (0,3),(6,3) | 3 |
| | (0,4),(1,4),(3,4),(6,4) | 4 |
| | (0,5),(1,5),(2,5),(3,5),(4,5),(6,5) | 5 |
| | (0,6) | 6 |
| Set 3 | (3,1),(1,3) | 4 |
| | (3,2),(4,2),(2,3),(2,4) | 5 |
| Set 4 | (0,1),(0,2),(0,3),(0,4),(0,5),(0,6) | 0 |
| | (1,2),(1,4),(1,5) | 1 |
| | (2,5) | 2 |
| | (3,4),(3,5) | 3 |
| | (4,5) | 4 |
| | (6,1),(6,2),(6,3),(6,4),(6,5) | 6 |
| Set 5 | (1,3) | 1 |
| | (2,3),(2,4) | 2 |
| | (3,1),(3,2) | 3 |
| | (4,2) | 4 |

11 Physical Multicast Channel (PMCH) related procedures

11.1 UE procedure for receiving the PMCH

The UE shall decode the PMCH when configured by higher layers. The UE may assume that an eNB transmission on the PMCH is performed according to subclause 6.5 of [3].

The I_{MCS} for the PMCH is configured by higher layers. If the UE is configured by higher layers to decode the PMCH based on QPSK, 16QAM, 64QAM, and 256QAM then the UE shall use I_{MCS} and Table 7.1.7.1-1A to determine the modulation order (Q_m) and TBS index (I_{TBS}) used in the PMCH. Else the UE shall use I_{MCS} for the PMCH and Table 7.1.7.1-1 to determine the modulation order (Q_m) and TBS index (I_{TBS}) used in the PMCH.

The UE shall then follow the procedure in subclause 7.1.7.2.1 to determine the transport block size, assuming N_{PRB} is equal to N_{RB}^{DL} . The UE shall set the redundancy version to 0 for the PMCH.

11.2 UE procedure for receiving MCCH change notification

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the M-RNTI, the UE shall decode the PDCCH according to the combination defined in Table 11.2-1.

Table 11.2-1: PDCCH configured by M-RNTI

| DCI format | Search Space |
|---------------|--------------|
| DCI format 1C | Common |

The 8-bit information for MCCH change notification [11], as signalled on the PDCCH, shall be delivered to higher layers.

12 Assumptions independent of physical channel

A UE shall not assume that two antenna ports are quasi co-located unless specified otherwise.

A UE may assume the antenna ports 0 – 3 of a serving cell are quasi co-located (as defined in [3]) with respect to delay spread, Doppler spread, Doppler shift, average gain, and average delay.

For the purpose of discovery-signal-based measurements, a UE shall not assume any other signals or physical channels are present other than the discovery signal.

If a UE supports *discoverySignalsInDeactSCell-r12*, and if the UE is configured with discovery-signal-based RRM measurements on a carrier frequency applicable for a secondary cell on the same carrier frequency, and if the secondary cell is deactivated, and if the UE is not configured by higher layers to receive MBMS on the secondary cell, the UE shall, except for discovery-signal transmissions, assume that PSS, SSS, PBCH, CRS, PCFICH, PDSCH, PDCCH, EPDCCH, PHICH, DMRS and CSI-RS may be not transmitted by the secondary cell until the subframe where an activation command is received for the secondary cell.

13 Uplink/Downlink configuration determination procedure for Frame Structure Type 2

If the UE is configured with a SCG, the UE shall apply the procedures described in this clause for both MCG and SCG

- When the procedures are applied for MCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells, serving cell, serving cells belonging to the MCG respectively.

- When the procedures are applied for SCG, the terms ‘secondary cell’, ‘secondary cells’, ‘serving cell’, ‘serving cells’ in this clause refer to secondary cell, secondary cells (not including PSCell), serving cell, serving cells belonging to the SCG respectively. The term ‘primary cell’ in this clause refers to the PSCell of the SCG.

For each serving cell

If the UE is not configured with the higher layer parameter *EIMTA-MainConfigServCell-r12*,

- the UE shall set the UL/DL configuration equal to the UL/DL configuration (i.e., the parameter *subframeAssignment*) indicated by higher layers.

If the UE is configured by higher layers with the parameter *EIMTA-MainConfigServCell-r12*, then for each radio frame,

- the UE shall determine eIMTA-UL/DL-configuration as described in subclause 13.1.
- the UE shall set the UL/DL configuration for each radio frame equal to the eIMTA-UL/DL-configuration of that radio frame.

13.1 UE procedure for determining eIMTA-uplink/downlink configuration

If a UE is configured by higher layers to decode PDCCHs with the CRC scrambled by the eIMTA-RNTI, the UE shall decode the PDCCH according to the combination defined in Table 13.1-1.

Table 13.1-1: PDCCH configured by eIMTA-RNTI

| DCI format | Search Space |
|---------------|--------------|
| DCI format 1C | Common |

The subframes in which the UE monitors PDCCH with CRC scrambled by eIMTA-RNTI are configured by higher layers.

For each serving cell,

- if $T=10$,
 - if the UE detects PDCCH with CRC scrambled by eIMTA-RNTI in subframe 0 of a radio frame m or if the UE detects PDCCH with CRC scrambled by eIMTA-RNTI in a subframe other than subframe 0 of a radio frame $m-1$,
 - the eIMTA-UL/DL-configuration for radio frame m is given by the UL/DL configuration indication signalled on the PDCCH as described in [4],
 - the UE may assume that the same UL/DL configuration indication is indicated by PDCCH with CRC scrambled by eIMTA-RNTI in subframe 0 of radio frame m and in all the subframes other than subframe 0 of radio frame $m-1$ in which PDCCH with CRC scrambled by eIMTA-RNTI is monitored,
 - otherwise
 - the eIMTA-UL/DL-configuration for radio frame m is same as the UL/DL configuration (i.e., the parameter *subframeAssignment*) indicated by higher layers;
- if T is a value other than 10,
 - if the UE detects PDCCH with CRC scrambled by eIMTA-RNTI in a subframe in radio frame $mT/10$,
 - the eIMTA-UL/DL-configuration for radio frames $\{mT/10+1, mT/10+2, \dots, (m+1)T/10\}$ is given by the UL/DL configuration indication signalled on the PDCCH as described [4],
 - the UE may assume that the same UL/DL configuration indication is indicated by PDCCH with CRC scrambled by eIMTA-RNTI in all the subframes of radio frame $mT/10$ in which PDCCH with CRC scrambled by eIMTA-RNTI is monitored,

- otherwise
 - the eIMTA-UL/DL-configuration for radio frames $\{mT/10+1, mT/10+2, \dots, (m+1)T/10\}$ is same as the UL/DL configuration (i.e., the parameter *subframeAssignment*) indicated by higher layers.

where T denotes the value of parameter *eimta-CommandPeriodicity-r12*.

For a serving cell c , if subframe i is indicated as uplink subframe or a special subframe by higher layer parameter *eimta-HARQ-ReferenceConfig-r12*, the UE is not expected to receive a PDCCH with CRC scrambled by eIMTA-RNTI containing an UL/DL configuration for serving cell c that would indicate subframe i as a downlink subframe.

For a serving cell c , if subframe i is indicated as downlink subframe or a special subframe by higher layer parameter *subframeAssignment*, the UE is not expected to receive a PDCCH with CRC scrambled by eIMTA-RNTI containing an UL/DL configuration for serving cell c that would indicate subframe i as an uplink subframe.

For a serving cell c , a UE is not expected to be configured with parameter *eimta-HARQ-ReferenceConfig-r12* if a subframe indicated as an uplink subframe by *eimta-HARQ-ReferenceConfig-r12* is not indicated as an uplink subframe by the UL-reference UL/DL configuration.

If UE is not configured with the parameter *EIMTA-MainConfigServCell-r12* for any activated serving cell, the UE is not expected to monitor PDCCH with CRC scrambled by eIMTA-RNTI.

14 UE procedures related to Sidelink

A UE can be configured by higher layers with one or more PSSCH resource configuration(s). A PSSCH resource configuration can be for reception of PSSCH, or for transmission of PSSCH. The physical sidelink shared channel related procedures are described in subclause 14.1.

A UE can be configured by higher layers with one or more PSCCH resource configuration(s). A PSCCH resource configuration can be for reception of PSCCH, or for transmission of PSCCH and the PSCCH resource configuration is associated with either sidelink transmission mode 1 or sidelink transmission mode 2. The physical sidelink control channel related procedures are described in subclause 14.2.

A UE can be configured by higher layers with one or more PSDCH resource configuration(s). A PSDCH resource configuration can be for reception of PSDCH, or for transmission of PSDCH. The transmissions of PSDCH according to a PSDCH resource configuration are associated with either sidelink discovery type 1 or sidelink discovery type 2B. The physical sidelink discovery channel related procedures are described in subclause 14.3.

The physical sidelink synchronization related procedures are described in subclause 14.4.

For a UE transmitting PSBCH, the transmit power of PSBCH (P_{PSBCH}) is same as the transmit power of primary sidelink synchronisation signal P_{PSSS} .

A UE is not expected to be configured with PSCCH resource configuration(s) such that, in a given subframe, the total number of resource blocks across the resource block pools (as described in subclause 14.2.3) indicated by the PSCCH resource configuration(s) exceeds 50.

If a UE uplink transmission in subframe $n+1$ of a serving cell overlaps in time domain with sidelink transmission/reception by the UE in subframe n of the serving cell, then the UE shall drop the sidelink transmission/reception in subframe n .

For a given carrier frequency, a UE is not expected to receive sidelink physical channels/signals with different cyclic prefix lengths in the same sidelink subframe.

For a given carrier frequency, in a sidelink subframe, if a UE has a sidelink transmission, the sidelink transmission shall occur only in contiguous physical resource blocks.

14.1 Physical Sidelink Shared Channel related procedures

14.1.1 UE procedure for transmitting the PSSCH

If the UE transmits SCI format 0 on PSCCH according to a PSCCH resource configuration in subframe n belonging to a PSCCH period (described in subclause 14.2.3), then for the corresponding PSSCH transmissions

- the transmissions occur in a set of subframes in the PSCCH period and in a set of resource blocks within the set of subframes. The first PSSCH transport block is transmitted in the first four subframes in the set, the second transport block is transmitted in the next four subframes in the set, and so on.
- for sidelink transmission mode 1,
 - the set of subframes is determined using the subframe pool indicated by the PSSCH resource configuration (described in subclause 14.1.4) and using time resource pattern (I_{TRP}) in the SCI format 0 as described in subclause 14.1.1.1.
 - the set of resource blocks is determined using Resource block assignment and hopping allocation in the SCI format 0 as described in subclause 14.1.1.2.
- for sidelink transmission mode 2,
 - the set of subframes is determined using the subframe pool indicated by the PSSCH resource configuration (described in subclause 14.1.3) and using time resource pattern (I_{TRP}) in the SCI format 0 as described in subclause 14.1.1.3.

- the set of resource blocks is determined using the resource block pool indicated by the PSSCH resource configuration (described in subclause 14.1.3) and using Resource block assignment and hopping allocation in the SCI format 0 as described in subclause 14.1.1.4.
- the modulation order is determined using the "modulation and coding scheme" field (I_{MCS}) in SCI format 0. For $0 \leq I_{MCS} \leq 28$, the modulation order is set to $Q' = \min(4, Q'_m)$, where Q'_m is determined from Table 8.6.1-1.
- the TBS index (I_{TBS}) is determined based on I_{MCS} and Table 8.6.1-1, and the transport block size is determined using I_{TBS} and the number of allocated resource blocks (N_{PRB}) using the procedure in subclause 7.1.7.2.1.

14.1.1.1 UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 1

Within the PSCCH period (described in subclause 14.2.3), the subframes used for PSSCH are determined as follows:

- a subframe indicator bitmap $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ and N_{TRP} are determined using the procedure described in subclause 14.1.1.1.1.
- a bitmap $(b_0, b_1, \dots, b_{L_{PSSCH}-1})$ is determined using $b_j = b'_{j \bmod N_{TRP}}$ and a subframe l_j^{PSSCH} in the subframe pool is used for PSSCH if $b_j = 1$, otherwise the subframe l_j^{PSSCH} is not used for PSSCH, where $(l_0^{PSSCH}, l_1^{PSSCH}, \dots, l_{L_{PSSCH}-1}^{PSSCH})$ and L_{PSSCH} are described in subclause 14.1.4. The subframes used for PSSCH are denoted by $(n_0^{PSSCH}, n_1^{PSSCH}, \dots, n_{N_{PSSCH}-1}^{PSSCH})$ arranged in increasing order of subframe index and where N_{PSSCH} is the number of subframes that can be used for PSSCH transmission in a PSCCH period and is a multiple of 4.

14.1.1.1.1 Determination of subframe indicator bitmap

For FDD and TDD with UL/DL configuration belonging to {1,2,4,5}, N_{TRP} is 8, and the mapping between Time Resource pattern Index (I_{TRP}) and subframe indicator bitmap $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ is given by table 14.1.1.1.1-1.

For TDD with UL/DL configuration 0, N_{TRP} is 7, and the mapping between Time Resource pattern Index (I_{TRP}) and subframe indicator bitmap $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ is given by table 14.1.1.1.1-2.

For TDD with UL/DL configuration belonging to {3,6}, N_{TRP} is 6, and the mapping between Time Resource pattern Index (I_{TRP}) and subframe indicator bitmap $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ is given by table 14.1.1.1.1-3.

Table 14.1.1.1.1-1: Time Resource pattern Index mapping for $N_{TRP} = 8$

| I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ |
|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|
| 0 | 1 | (1,0,0,0,0,0,0,0) | 37 | 4 | (1,1,1,0,1,0,0,0) | 74 | 4 | (0,1,1,1,0,0,0,1) |
| 1 | 1 | (0,1,0,0,0,0,0,0) | 38 | 4 | (1,1,0,1,1,0,0,0) | 75 | 4 | (1,1,0,0,1,0,0,1) |
| 2 | 1 | (0,0,1,0,0,0,0,0) | 39 | 4 | (1,0,1,1,1,0,0,0) | 76 | 4 | (1,0,1,0,1,0,0,1) |
| 3 | 1 | (0,0,0,1,0,0,0,0) | 40 | 4 | (0,1,1,1,1,0,0,0) | 77 | 4 | (0,1,1,0,1,0,0,1) |
| 4 | 1 | (0,0,0,0,1,0,0,0) | 41 | 4 | (1,1,1,0,0,1,0,0) | 78 | 4 | (1,0,0,1,1,0,0,1) |
| 5 | 1 | (0,0,0,0,0,1,0,0) | 42 | 4 | (1,1,0,1,0,1,0,0) | 79 | 4 | (0,1,0,1,1,0,0,1) |
| 6 | 1 | (0,0,0,0,0,0,1,0) | 43 | 4 | (1,0,1,1,0,1,0,0) | 80 | 4 | (0,0,1,1,1,0,0,1) |
| 7 | 1 | (0,0,0,0,0,0,0,1) | 44 | 4 | (0,1,1,1,0,1,0,0) | 81 | 4 | (1,1,0,0,0,1,0,1) |
| 8 | 2 | (1,1,0,0,0,0,0,0) | 45 | 4 | (1,1,0,0,1,1,0,0) | 82 | 4 | (1,0,1,0,0,1,0,1) |
| 9 | 2 | (1,0,1,0,0,0,0,0) | 46 | 4 | (1,0,1,0,1,1,0,0) | 83 | 4 | (0,1,1,0,0,1,0,1) |

| | | | | | | | | |
|----|---|-------------------|----|---|-------------------|---------|----------|-------------------|
| 10 | 2 | (0,1,1,0,0,0,0) | 47 | 4 | (0,1,1,0,1,1,0,0) | 84 | 4 | (1,0,0,1,0,1,0,1) |
| 11 | 2 | (1,0,0,1,0,0,0,0) | 48 | 4 | (1,0,0,1,1,1,0,0) | 85 | 4 | (0,1,0,1,0,1,0,1) |
| 12 | 2 | (0,1,0,1,0,0,0,0) | 49 | 4 | (0,1,0,1,1,1,0,0) | 86 | 4 | (0,0,1,1,0,1,0,1) |
| 13 | 2 | (0,0,1,1,0,0,0,0) | 50 | 4 | (0,0,1,1,1,1,0,0) | 87 | 4 | (1,0,0,0,1,1,0,1) |
| 14 | 2 | (1,0,0,0,1,0,0,0) | 51 | 4 | (1,1,1,0,0,0,1,0) | 88 | 4 | (0,1,0,0,1,1,0,1) |
| 15 | 2 | (0,1,0,0,1,0,0,0) | 52 | 4 | (1,1,0,1,0,0,1,0) | 89 | 4 | (0,0,1,0,1,1,0,1) |
| 16 | 2 | (0,0,1,0,1,0,0,0) | 53 | 4 | (1,0,1,1,0,0,1,0) | 90 | 4 | (0,0,0,1,1,1,0,1) |
| 17 | 2 | (0,0,0,1,1,0,0,0) | 54 | 4 | (0,1,1,1,0,0,1,0) | 91 | 4 | (1,1,0,0,0,0,1,1) |
| 18 | 2 | (1,0,0,0,0,1,0,0) | 55 | 4 | (1,1,0,0,1,0,1,0) | 92 | 4 | (1,0,1,0,0,0,1,1) |
| 19 | 2 | (0,1,0,0,0,1,0,0) | 56 | 4 | (1,0,1,0,1,0,1,0) | 93 | 4 | (0,1,1,0,0,0,1,1) |
| 20 | 2 | (0,0,1,0,0,1,0,0) | 57 | 4 | (0,1,1,0,1,0,1,0) | 94 | 4 | (1,0,0,1,0,0,1,1) |
| 21 | 2 | (0,0,0,1,0,1,0,0) | 58 | 4 | (1,0,0,1,1,0,1,0) | 95 | 4 | (0,1,0,1,0,0,1,1) |
| 22 | 2 | (0,0,0,0,1,1,0,0) | 59 | 4 | (0,1,0,1,1,0,1,0) | 96 | 4 | (0,0,1,1,0,0,1,1) |
| 23 | 2 | (1,0,0,0,0,0,1,0) | 60 | 4 | (0,0,1,1,1,0,1,0) | 97 | 4 | (1,0,0,0,1,0,1,1) |
| 24 | 2 | (0,1,0,0,0,0,1,0) | 61 | 4 | (1,1,0,0,0,1,1,0) | 98 | 4 | (0,1,0,0,1,0,1,1) |
| 25 | 2 | (0,0,1,0,0,0,1,0) | 62 | 4 | (1,0,1,0,0,1,1,0) | 99 | 4 | (0,0,1,0,1,0,1,1) |
| 26 | 2 | (0,0,0,1,0,0,1,0) | 63 | 4 | (0,1,1,0,0,1,1,0) | 100 | 4 | (0,0,0,1,1,0,1,1) |
| 27 | 2 | (0,0,0,0,1,0,1,0) | 64 | 4 | (1,0,0,1,0,1,1,0) | 101 | 4 | (1,0,0,0,0,1,1,1) |
| 28 | 2 | (0,0,0,0,0,1,1,0) | 65 | 4 | (0,1,0,1,0,1,1,0) | 102 | 4 | (0,1,0,0,0,1,1,1) |
| 29 | 2 | (1,0,0,0,0,0,0,1) | 66 | 4 | (0,0,1,1,0,1,1,0) | 103 | 4 | (0,0,1,0,0,1,1,1) |
| 30 | 2 | (0,1,0,0,0,0,0,1) | 67 | 4 | (1,0,0,0,1,1,1,0) | 104 | 4 | (0,0,0,1,0,1,1,1) |
| 31 | 2 | (0,0,1,0,0,0,0,1) | 68 | 4 | (0,1,0,0,1,1,1,0) | 105 | 4 | (0,0,0,0,1,1,1,1) |
| 32 | 2 | (0,0,0,1,0,0,0,1) | 69 | 4 | (0,0,1,0,1,1,1,0) | 106 | 8 | (1,1,1,1,1,1,1,1) |
| 33 | 2 | (0,0,0,0,1,0,0,1) | 70 | 4 | (0,0,0,1,1,1,1,0) | 107-127 | reserved | reserved |
| 34 | 2 | (0,0,0,0,0,1,0,1) | 71 | 4 | (1,1,1,0,0,0,0,1) | | | |
| 35 | 2 | (0,0,0,0,0,0,1,1) | 72 | 4 | (1,1,0,1,0,0,0,1) | | | |
| 36 | 4 | (1,1,1,1,0,0,0,0) | 73 | 4 | (1,0,1,1,0,0,0,1) | | | |

Table 14.1.1.1-2: Time Resource pattern Index mapping for $N_{TRP} = 7$

| I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ |
|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|
| 0 | reserved | reserved | 44 | 3 | (0,0,1,1,0,1,0) | 88 | 3 | (0,0,0,1,1,0,1) |
| 1 | 1 | (1,0,0,0,0,0,0) | 45 | 4 | (1,0,1,1,0,1,0) | 89 | 4 | (1,0,0,1,1,0,1) |
| 2 | 1 | (0,1,0,0,0,0,0) | 46 | 4 | (0,1,1,1,0,1,0) | 90 | 4 | (0,1,0,1,1,0,1) |
| 3 | 2 | (1,1,0,0,0,0,0) | 47 | 5 | (1,1,1,1,0,1,0) | 91 | 5 | (1,1,0,1,1,0,1) |
| 4 | 1 | (0,0,1,0,0,0,0) | 48 | 2 | (0,0,0,0,1,1,0) | 92 | 4 | (0,0,1,1,1,0,1) |
| 5 | 2 | (1,0,1,0,0,0,0) | 49 | 3 | (1,0,0,0,1,1,0) | 93 | 5 | (1,0,1,1,1,0,1) |
| 6 | 2 | (0,1,1,0,0,0,0) | 50 | 3 | (0,1,0,0,1,1,0) | 94 | 5 | (0,1,1,1,1,0,1) |
| 7 | 3 | (1,1,1,0,0,0,0) | 51 | 4 | (1,1,0,0,1,1,0) | 95 | 6 | (1,1,1,1,1,0,1) |
| 8 | 1 | (0,0,0,1,0,0,0) | 52 | 3 | (0,0,1,0,1,1,0) | 96 | 2 | (0,0,0,0,0,1,1) |
| 9 | 2 | (1,0,0,1,0,0,0) | 53 | 4 | (1,0,1,0,1,1,0) | 97 | 3 | (1,0,0,0,0,1,1) |
| 10 | 2 | (0,1,0,1,0,0,0) | 54 | 4 | (0,1,1,0,1,1,0) | 98 | 3 | (0,1,0,0,0,1,1) |
| 11 | 3 | (1,1,0,1,0,0,0) | 55 | 5 | (1,1,1,0,1,1,0) | 99 | 4 | (1,1,0,0,0,1,1) |
| 12 | 2 | (0,0,1,1,0,0,0) | 56 | 3 | (0,0,0,1,1,1,0) | 100 | 3 | (0,0,1,0,0,1,1) |
| 13 | 3 | (1,0,1,1,0,0,0) | 57 | 4 | (1,0,0,1,1,1,0) | 101 | 4 | (1,0,1,0,0,1,1) |

| | | | | | | | | |
|----|---|-----------------|----|---|-----------------|-----|---|-----------------|
| 14 | 3 | (0,1,1,1,0,0,0) | 58 | 4 | (0,1,0,1,1,1,0) | 102 | 4 | (0,1,1,0,0,1,1) |
| 15 | 4 | (1,1,1,1,0,0,0) | 59 | 5 | (1,1,0,1,1,1,0) | 103 | 5 | (1,1,1,0,0,1,1) |
| 16 | 1 | (0,0,0,0,1,0,0) | 60 | 4 | (0,0,1,1,1,1,0) | 104 | 3 | (0,0,0,1,0,1,1) |
| 17 | 2 | (1,0,0,0,1,0,0) | 61 | 5 | (1,0,1,1,1,1,0) | 105 | 4 | (1,0,0,1,0,1,1) |
| 18 | 2 | (0,1,0,0,1,0,0) | 62 | 5 | (0,1,1,1,1,1,0) | 106 | 4 | (0,1,0,1,0,1,1) |
| 19 | 3 | (1,1,0,0,1,0,0) | 63 | 6 | (1,1,1,1,1,1,0) | 107 | 5 | (1,1,0,1,0,1,1) |
| 20 | 2 | (0,0,1,0,1,0,0) | 64 | 1 | (0,0,0,0,0,0,1) | 108 | 4 | (0,0,1,1,0,1,1) |
| 21 | 3 | (1,0,1,0,1,0,0) | 65 | 2 | (1,0,0,0,0,0,1) | 109 | 5 | (1,0,1,1,0,1,1) |
| 22 | 3 | (0,1,1,0,1,0,0) | 66 | 2 | (0,1,0,0,0,0,1) | 110 | 5 | (0,1,1,1,0,1,1) |
| 23 | 4 | (1,1,1,0,1,0,0) | 67 | 3 | (1,1,0,0,0,0,1) | 111 | 6 | (1,1,1,1,0,1,1) |
| 24 | 2 | (0,0,0,1,1,0,0) | 68 | 2 | (0,0,1,0,0,0,1) | 112 | 3 | (0,0,0,0,1,1,1) |
| 25 | 3 | (1,0,0,1,1,0,0) | 69 | 3 | (1,0,1,0,0,0,1) | 113 | 4 | (1,0,0,0,1,1,1) |
| 26 | 3 | (0,1,0,1,1,0,0) | 70 | 3 | (0,1,1,0,0,0,1) | 114 | 4 | (0,1,0,0,1,1,1) |
| 27 | 4 | (1,1,0,1,1,0,0) | 71 | 4 | (1,1,1,0,0,0,1) | 115 | 5 | (1,1,0,0,1,1,1) |
| 28 | 3 | (0,0,1,1,1,0,0) | 72 | 2 | (0,0,0,1,0,0,1) | 116 | 4 | (0,0,1,0,1,1,1) |
| 29 | 4 | (1,0,1,1,1,0,0) | 73 | 3 | (1,0,0,1,0,0,1) | 117 | 5 | (1,0,1,0,1,1,1) |
| 30 | 4 | (0,1,1,1,1,0,0) | 74 | 3 | (0,1,0,1,0,0,1) | 118 | 5 | (0,1,1,0,1,1,1) |
| 31 | 5 | (1,1,1,1,1,0,0) | 75 | 4 | (1,1,0,1,0,0,1) | 119 | 6 | (1,1,1,0,1,1,1) |
| 32 | 1 | (0,0,0,0,0,1,0) | 76 | 3 | (0,0,1,1,0,0,1) | 120 | 4 | (0,0,0,1,1,1,1) |
| 33 | 2 | (1,0,0,0,0,1,0) | 77 | 4 | (1,0,1,1,0,0,1) | 121 | 5 | (1,0,0,1,1,1,1) |
| 34 | 2 | (0,1,0,0,0,1,0) | 78 | 4 | (0,1,1,1,0,0,1) | 122 | 5 | (0,1,0,1,1,1,1) |
| 35 | 3 | (1,1,0,0,0,1,0) | 79 | 5 | (1,1,1,1,0,0,1) | 123 | 6 | (1,1,0,1,1,1,1) |
| 36 | 2 | (0,0,1,0,0,1,0) | 80 | 2 | (0,0,0,0,1,0,1) | 124 | 5 | (0,0,1,1,1,1,1) |
| 37 | 3 | (1,0,1,0,0,1,0) | 81 | 3 | (1,0,0,0,1,0,1) | 125 | 6 | (1,0,1,1,1,1,1) |
| 38 | 3 | (0,1,1,0,0,1,0) | 82 | 3 | (0,1,0,0,1,0,1) | 126 | 6 | (0,1,1,1,1,1,1) |
| 39 | 4 | (1,1,1,0,0,1,0) | 83 | 4 | (1,1,0,0,1,0,1) | 127 | 7 | (1,1,1,1,1,1,1) |
| 40 | 2 | (0,0,0,1,0,1,0) | 84 | 3 | (0,0,1,0,1,0,1) | | | |
| 41 | 3 | (1,0,0,1,0,1,0) | 85 | 4 | (1,0,1,0,1,0,1) | | | |
| 42 | 3 | (0,1,0,1,0,1,0) | 86 | 4 | (0,1,1,0,1,0,1) | | | |
| 43 | 4 | (1,1,0,1,0,1,0) | 87 | 5 | (1,1,1,0,1,0,1) | | | |

Table 14.1.1.1-3: Time Resource pattern Index mapping for $N_{TRP} = 6$

| I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ | I_{TRP} | k_{TRP} | $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ |
|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|-----------|-----------|---------------------------------------|
| 0 | reserved | reserved | 22 | 3 | (0,1,1,0,1,0) | 44 | 3 | (0,0,1,1,0,1) |
| 1 | 1 | (1,0,0,0,0,0) | 23 | 4 | (1,1,1,0,1,0) | 45 | 4 | (1,0,1,1,0,1) |
| 2 | 1 | (0,1,0,0,0,0) | 24 | 2 | (0,0,0,1,1,0) | 46 | 4 | (0,1,1,1,0,1) |
| 3 | 2 | (1,1,0,0,0,0) | 25 | 3 | (1,0,0,1,1,0) | 47 | 5 | (1,1,1,1,0,1) |
| 4 | 1 | (0,0,1,0,0,0) | 26 | 3 | (0,1,0,1,1,0) | 48 | 2 | (0,0,0,0,1,1) |
| 5 | 2 | (1,0,1,0,0,0) | 27 | 4 | (1,1,0,1,1,0) | 49 | 3 | (1,0,0,0,1,1) |
| 6 | 2 | (0,1,1,0,0,0) | 28 | 3 | (0,0,1,1,1,0) | 50 | 3 | (0,1,0,0,1,1) |
| 7 | 3 | (1,1,1,0,0,0) | 29 | 4 | (1,0,1,1,1,0) | 51 | 4 | (1,1,0,0,1,1) |
| 8 | 1 | (0,0,0,1,0,0) | 30 | 4 | (0,1,1,1,1,0) | 52 | 3 | (0,0,1,0,1,1) |
| 9 | 2 | (1,0,0,1,0,0) | 31 | 5 | (1,1,1,1,1,0) | 53 | 4 | (1,0,1,0,1,1) |
| 10 | 2 | (0,1,0,1,0,0) | 32 | 1 | (0,0,0,0,0,1) | 54 | 4 | (0,1,1,0,1,1) |

| | | | | | | | | |
|----|---|---------------|----|---|---------------|--------|----------|---------------|
| 11 | 3 | (1,1,0,1,0,0) | 33 | 2 | (1,0,0,0,0,1) | 55 | 5 | (1,1,1,0,1,1) |
| 12 | 2 | (0,0,1,1,0,0) | 34 | 2 | (0,1,0,0,0,1) | 56 | 3 | (0,0,0,1,1,1) |
| 13 | 3 | (1,0,1,1,0,0) | 35 | 3 | (1,1,0,0,0,1) | 57 | 4 | (1,0,0,1,1,1) |
| 14 | 3 | (0,1,1,1,0,0) | 36 | 2 | (0,0,1,0,0,1) | 58 | 4 | (0,1,0,1,1,1) |
| 15 | 4 | (1,1,1,1,0,0) | 37 | 3 | (1,0,1,0,0,1) | 59 | 5 | (1,1,0,1,1,1) |
| 16 | 1 | (0,0,0,0,1,0) | 38 | 3 | (0,1,1,0,0,1) | 60 | 4 | (0,0,1,1,1,1) |
| 17 | 2 | (1,0,0,0,1,0) | 39 | 4 | (1,1,1,0,0,1) | 61 | 5 | (1,0,1,1,1,1) |
| 18 | 2 | (0,1,0,0,1,0) | 40 | 2 | (0,0,0,1,0,1) | 62 | 5 | (0,1,1,1,1,1) |
| 19 | 3 | (1,1,0,0,1,0) | 41 | 3 | (1,0,0,1,0,1) | 63 | 6 | (1,1,1,1,1,1) |
| 20 | 2 | (0,0,1,0,1,0) | 42 | 3 | (0,1,0,1,0,1) | 64-127 | reserved | reserved |
| 21 | 3 | (1,0,1,0,1,0) | 43 | 4 | (1,1,0,1,0,1) | | | |

14.1.1.2 UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 1

The set of resource blocks is determined using the procedure described in subclause 14.1.1.2.1 and 14.1.1.2.2.

14.1.1.2.1 PSSCH resource allocation for sidelink transmission mode 1

The resource allocation and hopping field of the SCI format 0 is used to determine a set of indices denoted by n'_{VRB} ($0 \leq n'_{\text{VRB}} < N_{\text{RB}}^{\text{SL}}$), a starting index RB'_{START} , and a number of allocated PRBs L'_{CRBs} and $N_{\text{RB}}^{\text{PSSCH}}$ using the procedure in subclause 8.1.1, and 8.4 (for sidelink frequency hopping with type 1 or type 2 hopping) with the following exceptions:

- the term 'PUSCH' in subclauses 8.1.1 and 8.4 is replaced with 'PSSCH'.
- the quantity n_{VRB} in subclause 8.1.1 is replaced with n'_{VRB} .
- the quantity $N_{\text{RB}}^{\text{UL}}$ in subclauses 8.1.1 and 8.4 is replaced with $N_{\text{RB}}^{\text{SL}}$.
- the quantity RB_{START} in subclauses 8.1.1 and 8.4 is replaced with RB'_{START} .
- the quantity L_{CRBs} in subclauses 8.1.1 and 8.4 is replaced with L'_{CRBs} .
- the quantity $N_{\text{RB}}^{\text{PUSCH}}$ in subclause 8.4 is replaced with $N_{\text{RB}}^{\text{PSSCH}}$.
- the quantity $N_{\text{RB}}^{\text{HO}}$ is given by higher layer parameter *rb-Offset-r12* associated with the corresponding PSSCH resource configuration.
- the quantity N_{sb} is given by higher layer parameter *numSubbands-r12* associated with the corresponding PSSCH resource configuration.

14.1.1.2.2 PSSCH frequency hopping for sidelink transmission mode 1

If sidelink frequency hopping with type 1 hopping is enabled, the set of physical resource blocks for PSSCH transmission is determined using subclause 8.4 with the following exceptions:

- the term 'PUSCH' is replaced with 'PSSCH'.
- only inter-subframe hopping shall be used.
- the quantity RB_{START} is replaced with RB'_{START} .

- the quantity N_{RB}^{UL} is replaced with N_{RB}^{SL} .
- the quantity N_{RB}^{PUSCH} is replaced with N_{RB}^{PSSCH} .
- the quantity N_{RB}^{HO} is given by higher layer parameter *rb-Offset-r12* associated with the PSSCH resource configuration.
- the frequency hopping field in the SCI format 0 is used instead of DCI format 0.
- the quantity $n_{PRB}^{S1}(i)$ is replaced with n_{PRB}^{SL0} .
- the quantity $n_{PRB}(i)$ is replaced with n_{PRB}^{SL1} .
- for odd n_{ssf}^{PSSCH} (described in subclause 9.2.4 of [3]), the set of physical resource blocks for PSSCH transmission are L'_{CRBs} contiguous resource blocks starting from PRB with index n_{PRB}^{SL0} .
- for even n_{ssf}^{PSSCH} (described in subclause 9.2.4 of [3]), the set of physical resource blocks for PSSCH transmission are L'_{CRBs} contiguous resource blocks starting from PRB with index n_{PRB}^{SL1} .

14.1.1.3 UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 2

For FDD or for TDD, and the UE not configured with the higher layer parameter *trpt-Subset-r12*

- The allowed values of I_{TRP} correspond to the values of k_{TRP} satisfying $k_{TRP} = k_i$, for a value of i in $0 \leq i < X_{TRP}$, where k_i and X_{TRP} are determined from table 14.1.1.3-1.

For FDD or for TDD with UL/DL configuration belonging to {0,1,2,3,4,6}, and the UE configured with the higher layer parameter *trpt-Subset-r12*

- The allowed values of I_{TRP} correspond to the values of k_{TRP} satisfying $k_{TRP} = k_i$, for values of i in $0 \leq i < X_{TRP}$ satisfying $a_i = 1$, $0 \leq i < X_{TRP}$ and where k_i and X_{TRP} are determined from table 14.1.1.3-1, and $(a_0, a_1, \dots, a_{X_{TRP}-1})$ is the bitmap indicated by *trpt-Subset-r12*.

Table 14.1.1.3-1: Determination of X_{TRP} and k_i for sidelink transmission mode 2

| | X_{TRP} | k_0 | k_1 | k_2 | k_3 | k_4 |
|--|-----------|-------|-------|-------|-------|-------|
| FDD and TDD with UL/DL configuration 1,2,4,5 | 3 | 1 | 2 | 4 | - | - |
| TDD with UL/DL configuration 0 | 5 | 1 | 2 | 3 | 4 | 5 |
| TDD with UL/DL configuration 3,6 | 4 | 1 | 2 | 3 | 4 | - |

Within a PSSCH period, the subframes used for PSSCH are determined as follows:

- a subframe indicator bitmap $(b'_0, b'_1, \dots, b'_{N_{TRP}-1})$ and N_{TRP} are determined using the procedure described in subclause 14.1.1.1.1 from the allowed values of I_{TRP} described in this subclause.
- a bitmap $(b_0, b_1, \dots, b_{L_{PSSCH}-1})$ is determined using $b_j = b'_{j \bmod N_{TRP}}$ and a subframe l_j^{PSSCH} in the subframe pool is used for PSSCH if $b_j = 1$, otherwise the subframe l_j^{PSSCH} is not used for PSSCH, where $(l_0^{PSSCH}, l_1^{PSSCH}, \dots, l_{L_{PSSCH}-1}^{PSSCH})$ and L_{PSSCH} are described in subclause 14.1.3. The subframes used for PSSCH are denoted by $(n_0^{PSSCH}, n_1^{PSSCH}, \dots, n_{N_{PSSCH}-1}^{PSSCH})$ arranged in increasing order of subframe index and

where N_{PSSCH} is the number of subframes that can be used for PSSCH transmission in a PSCCH period and is a multiple of 4.

14.1.1.4 UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 2

The set of resource blocks within the resource block pool (defined in 14.1.3) is determined using the subclause 14.1.1.2.1 .

If sidelink frequency hopping with type 1 hopping is enabled, the set of physical resource blocks for PSSCH transmission is determined using subclause 14.1.1.2.2 with the following exceptions

- the quantity N_{RB}^{UL} is replaced with $M_{RB}^{PSSCH-RP}$ (defined in 14.1.3).
- for odd n_{ssf}^{PSSCH} , the set of physical resource blocks for PSSCH transmission are given by L'_{CRBs} contiguous resource blocks $m_x, m_{x+1}, \dots, m_{x+L'_{CRBs}-1}$ belonging to the resource block pool, where $x = n_{PRB}^{SL0}$.
- for even n_{ssf}^{PSSCH} , the set of physical resource blocks for PSSCH transmission are given by L'_{CRBs} contiguous resource blocks $m_x, m_{x+1}, \dots, m_{x+L'_{CRBs}-1}$ belonging to the resource block pool, where $x = n_{PRB}^{SL1}$.

14.1.1.5 UE procedure for PSSCH power control

For sidelink transmission mode 1 and PSCCH period i , the UE transmit power P_{PSSCH} is given by the following

- if the TPC command field in configured sidelink grant (described in [8]) for PSCCH period i is set to 0

$$P_{PSSCH} = P_{C_{MAX,PSSCH}}$$

- if the TPC command field in configured sidelink grant (described in [8]) for PSCCH period i is set to 1

$$P_{PSSCH} = \min\{P_{C_{MAX,PSSCH}}, 10\log_{10}(M_{PSSCH}) + P_{O_{PSSCH,1}} + \alpha_{PSSCH,1} \cdot PL\} \text{ [dBm]}$$

where $P_{C_{MAX,PSSCH}}$ is defined in [6], and M_{PSSCH} is the bandwidth of the PSSCH resource assignment expressed in number of resource block and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1. $P_{O_{PSSCH,1}}$ and $\alpha_{PSSCH,1}$ are provided by higher layer parameters $p0-r12$ and $alpha-r12$, respectively and that are associated with the corresponding PSSCH resource configuration.

For sidelink transmission mode 2, the UE transmit power P_{PSSCH} is given by

$$P_{PSSCH} = \min\{P_{C_{MAX,PSSCH}}, 10\log_{10}(M_{PSSCH}) + P_{O_{PSSCH,2}} + \alpha_{PSSCH,2} \cdot PL\} \text{ [dBm]},$$

where $P_{C_{MAX,PSSCH}}$ is defined in [6], and M_{PSSCH} is the bandwidth of the PSSCH resource assignment expressed in number of resource blocks and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1. $P_{O_{PSSCH,2}}$ and $\alpha_{PSSCH,2}$ are provided by higher layer parameter $p0-r12$ and $alpha-r12$, respectively and that are associated with the corresponding PSSCH resource configuration.

14.1.2 UE procedure for receiving the PSSCH

For sidelink transmission mode 1, a UE upon detection of SCI format 0 on PSCCH can decode PSSCH according to the detected SCI format 0.

For sidelink transmission mode 2, a UE upon detection of SCI format 0 on PSCCH can decode PSSCH according to the detected SCI format 0, and associated PSSCH resource configuration configured by higher layers.

14.1.3 UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 2

For a PSCCH period associated with the PSCCH resource configuration (determined in subclause 14.2.3) which is also associated with the PSSCH resource configuration, the UE determines a PSSCH pool consisting of a subframe pool and resource block pool as follows.

- For TDD, if the parameter *tdd-Config-r12* is indicated by the PSCCH resource configuration, the TDD UL/DL configuration used for determining the subframe pool is given by the parameter *tdd-Config-r12*, otherwise, the TDD UL/DL configuration used for determining the subframe pool is given by the UL/DL configuration (i.e. parameter *subframeAssignment*) for the serving cell.
- Within the PSCCH period, the uplink subframes with subframe index greater than or equal to $j_{begin} + O_2$ are denoted by $(l_0, l_1, \dots, l_{N'-1})$ arranged in increasing order of subframe index, where j_{begin} is described in subclause 14.2.3 and O_2 is the *offsetIndicator-r12* indicated by the PSSCH resource configuration, where N' denotes the number of uplink subframes within the PSCCH period with subframe index greater than or equal to $j_{begin} + O_2$.
- A bitmap $b_0, b_1, b_2, \dots, b_{N'-1}$ is determined using $b_j = a_{j \bmod N_B}$, for $0 \leq j < N'$, where $a_0, a_1, a_2, \dots, a_{N_B-1}$ and N_B are the bitmap and the length of the bitmap indicated by *subframeBitmap-r12*, respectively.
- A subframe l_j ($0 \leq j < N'$) belongs to the subframe pool if $b_j = 1$. The subframes in the subframe pool are denoted by $(l_0^{PSSCH}, l_1^{PSSCH}, \dots, l_{L_{PSSCH}-1}^{PSSCH})$ arranged in increasing order of subframe index and L_{PSSCH} denotes the number of subframes in the subframe pool.
- A PRB with index q ($0 \leq q < N_{RB}^{SL}$) belongs to the resource block pool if $S1 \leq q < S1 + M$ or if $S2 - M < q \leq S2$, where $S1$, $S2$, and M denote the *prb-Start-r12*, *prb-End-r12* and *prb-Num-r12* indicated by the PSSCH resource configuration respectively.
- The resource blocks in the resource block pool are denoted by $(m_0^{PSSCH}, m_1^{PSSCH}, \dots, m_{M_{RB}^{PSSCH-RP}-1}^{PSSCH})$ arranged in increasing order of resource block indices and $M_{RB}^{PSSCH-RP}$ is the number of resource blocks in the resource block pool.

14.1.4 UE procedure for determining subframe pool for sidelink transmission mode 1

For a PSCCH period associated with the PSCCH resource configuration (described in subclause 14.2.3) which is also associated with the PSSCH resource configuration, the UE determines a PSSCH pool consisting of a subframe pool as follows.

- For TDD, if the parameter *tdd-Config-r12* is indicated by the PSCCH resource configuration, the TDD UL/DL configuration used for determining the subframe pool is given by the parameter *tdd-Config-r12*, otherwise, the TDD UL/DL configuration used for determining the subframe pool is given by the UL/DL configuration (i.e. parameter *subframeAssignment*) for the serving cell.
- Each uplink subframe with subframe index greater than or equal to $l_{L_{PSCCH}-1}^{PSCCH} + 1$ belongs to the subframe pool for PSSCH, where $l_{L_{PSCCH}-1}^{PSCCH} + 1$ and L_{PSCCH} are described in subclause 14.2.3.
- The subframes in the subframe pool for PSSCH are denoted by $(l_0^{PSSCH}, l_1^{PSSCH}, \dots, l_{L_{PSSCH}-1}^{PSSCH})$ arranged in increasing order of subframe index and L_{PSSCH} denotes the number of subframes in the subframe pool.

14.2 Physical Sidelink Control Channel related procedures

For sidelink transmission mode 1, if a UE is configured by higher layers to receive DCI format 5 with the CRC scrambled by the SL-RNTI, the UE shall decode the PDCCH/EPDCCH according to the combination defined in Table 14.2-1.

Table 14.2-1: PDCCH/EPDCCH configured by SL-RNTI

| DCI format | Search Space |
|--------------|--|
| DCI format 5 | For PDCCH: Common and UE specific by C-RNTI For EPDCCH: UE specific by C-RNTI |

14.2.1 UE procedure for transmitting the PSCCH

For sidelink transmission mode 1 and PSCCH period i ,

- the UE shall determine the subframes and resource blocks for transmitting SCI format 0 as follows.
 - SCI format 0 is transmitted in two subframes in the subframe pool and one physical resource block per slot in each of the two subframes, wherein the physical resource blocks belong to the resource block pool, where the subframe pool and the resource block pool are indicated by the PSCCH resource configuration (as defined in subclause 14.2.3)
 - the two subframes and the resource blocks are determined using “Resource for PSCCH” field (n_{PSCCH}) in the configured sidelink grant (described in [8]) as described in subclause 14.2.1.1.
- the UE shall set the contents of the SCI format 0 as follows:
 - the UE shall set the Modulation and coding scheme field according to the Modulation and coding scheme indicated by the higher layer parameter $mcs-r12$ if the parameter is configured by higher layers.
 - the UE shall set the Frequency hopping flag according to the “Frequency hopping flag” field in the configured sidelink grant.
 - the UE shall set the Resource block assignment and hopping resource allocation according to the “Resource block assignment and hopping resource allocation” field in the configured sidelink grant.
 - the UE shall set the Time resource pattern according to the “Time resource pattern” field in the configured sidelink grant .
 - the UE shall set the eleven-bit Timing advance indication to $I_{TAI} = \left\lfloor \frac{N_{TA}}{16} \right\rfloor$ to indicate sidelink reception timing adjustment value using the N_{TA} (defined in [3]) value for the UE in the subframe that is no earlier than subframe $l_{b1}^{PSCCH} - 4$ (l_{b1}^{PSCCH} described in subclause 14.2.1.1).

For sidelink transmission mode 2,

- SCI format 0 is transmitted in two subframes in the subframe pool and one physical resource block per slot in each of the two subframes, wherein the physical resource blocks belongs to the resource block pool, where the subframe pool and the resource block pool are indicated by the PSCCH resource configuration (as defined in subclause 14.2.3)
- the two subframes and the resource blocks are determined using the procedure described in subclause 14.2.1.2
- the UE shall set the eleven-bit Timing advance indication I_{TAI} in the SCI format 0 to zero.

14.2.1.1 UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 1

For $0 \leq n_{PSCCH} < \left\lfloor M_{RB}^{PSCCH} - RP / 2 \right\rfloor \cdot L_{PSCCH}$,

- one transmission of the PSCCH is in resource block m_{a1}^{PSCCH} of subframe l_{b1}^{PSCCH} of the PSCCH period, where $a1 = \lfloor n_{PSCCH} / L_{PSCCH} \rfloor$ and $b1 = n_{PSCCH} \bmod L_{PSCCH}$.
- the other transmission of the PSCCH is in resource block m_{a2}^{PSCCH} of subframe l_{b2}^{PSCCH} of the PSCCH period, where $a2 = \lfloor n_{PSCCH} / L_{PSCCH} \rfloor + \lfloor M_{RB}^{PSCCH-RP} / 2 \rfloor$ and $b2 = (n_{PSCCH} + 1 + \lfloor n_{PSCCH} / L_{PSCCH} \rfloor \bmod (L_{PSCCH} - 1)) \bmod L_{PSCCH}$.

where $(l_0^{PSCCH}, l_1^{PSCCH}, \dots, l_{L_{PSCCH}-1}^{PSCCH})$, $(m_0^{PSCCH}, m_1^{PSCCH}, \dots, m_{M_{RB}^{PSCCH-RP}-1}^{PSCCH})$, L_{PSCCH} and $M_{RB}^{PSCCH-RP}$ are described in subclause 14.2.3.

14.2.1.2 UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 2

The allowed values for PSCCH resource selection are given by $0, 1, \dots, (\lfloor M_{RB}^{PSCCH-RP} / 2 \rfloor \cdot L_{PSCCH} - 1)$ where L_{PSCCH} and $M_{RB}^{PSCCH-RP}$ described in subclause 14.2.3. The two subframes and the resource blocks are determined using selected resource value n_{PSCCH} (described in [8]) and the procedure described in subclause 14.2.1.1.

14.2.1.3 UE procedure for PSCCH power control

For sidelink transmission mode 1 and PSCCH period i , the UE transmit power P_{PSCCH} is given by the following

- if the TPC command field in the configured sidelink grant (described in [8]) for PSCCH period i is set to 0

$$P_{PSCCH} = P_{C_{MAX},PSCCH}$$
- if the TPC command field in the configured sidelink grant (described in [8]) for PSCCH period i is set to 1

$$P_{PSCCH} = \min\{P_{C_{MAX},PSCCH}, 10\log_{10}(M_{PSCCH}) + P_{O_PSCCH,1} + \alpha_{PSCCH,1} \cdot PL\} \text{ [dBm]}$$

where $P_{C_{MAX},PSCCH}$ is defined in [6], and $M_{PSCCH} = 1$ and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1. $P_{O_PSCCH,1}$ and $\alpha_{PSCCH,1}$ are provided by higher layer parameters $p0-r12$ and $alpha-r12$, respectively and are associated with the corresponding PSCCH resource configuration.

For sidelink transmission mode 2, the UE transmit power P_{PSCCH} is given by

$$P_{PSCCH} = \min\{P_{C_{MAX},PSCCH}, 10\log_{10}(M_{PSCCH}) + P_{O_PSCCH,2} + \alpha_{PSCCH,2} \cdot PL\} \text{ [dBm]},$$

where $P_{C_{MAX},PSCCH}$ is the $P_{C_{MAX},c}$ configured by higher layers and $M_{PSCCH} = 1$ and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1. $P_{O_PSCCH,2}$ and $\alpha_{PSCCH,2}$ are provided by higher layer parameters $p0-r12$ and $alpha-r12$, respectively and are associated with the corresponding PSCCH resource configuration.

14.2.2 UE procedure for receiving the PSCCH

For each PSCCH resource configuration associated with sidelink transmission mode 1, a UE configured by higher layers to detect SCI format 0 on PSCCH shall attempt to decode the PSCCH according to the PSCCH resource configuration, and using the Group destination IDs indicated by higher layers.

For each PSCCH resource configuration associated with sidelink transmission mode 2, a UE configured by higher layers to detect SCI format 0 on PSCCH shall attempt to decode the PSCCH according to the PSCCH resource configuration, and using the Group destination IDs indicated by higher layers.

14.2.3 UE procedure for determining resource block pool and subframe pool for PSCCH

A PSCCH resource configuration for transmission/reception is associated with a set of periodically occurring time-domain periods (known as PSCCH periods). The i -th PSCCH period begins at subframe with subframe index $j_{begin} = O + i \cdot P$ and ends in subframe with subframe index $j_{end} = O + (i + 1) \cdot P - 1$, where

- $0 \leq j_{begin}, j_{end} < 10240$,
- the subframe index is relative to subframe#0 of the radio frame corresponding to SFN 0 of the serving cell or DFN 0 (described in [11]),
- O is the *offsetIndicator-r12* indicated by the PSCCH resource configuration,
- P is the *sc-Period-r12* indicated by the PSCCH resource configuration.

For a PSCCH period, the UE determines a PSCCH pool consisting of a subframe pool and a resource block pool as follows.

- For TDD, if the parameter *tdd-Config-r12* is indicated by the PSCCH resource configuration, the TDD UL/DL configuration used for determining the subframe pool is given by the parameter *tdd-Config-r12*, otherwise, the TDD UL/DL configuration used for determining the subframe pool is given by the UL/DL configuration (i.e. parameter *subframeAssignment*) for the serving cell.
- The first N' uplink subframes are denoted by $(l_0, l_1, \dots, l_{N'-1})$ arranged in increasing order of subframe index, where N' is the length of the bitmap *subframeBitmap-r12* indicated by the PSCCH resource configuration.
- A subframe l_j ($0 \leq j < N'$) belongs to the subframe pool if $a_j = 1$, where $(a_0, a_1, a_2, \dots, a_{N'-1})$ is the bitmap *subframeBitmap-r12* indicated by the PSCCH resource configuration. The subframes in the subframe pool are denoted by $(l_0^{PSCCH}, l_1^{PSCCH}, \dots, l_{L_{PSCCH}-1}^{PSCCH})$ arranged in increasing order of subframe index and L_{PSCCH} is the number of subframes in the subframe pool. A PRB with index q ($0 \leq q < N_{RB}^{SL}$) belongs to the resource block pool if $S1 \leq q < S1 + M$ or if $S2 - M < q \leq S2$, where $S1$, $S2$, and M denote the *prb-Start-r12*, *prb-End-r12* and *prb-Num-r12* indicated by the PSCCH resource configuration respectively.
- The resource blocks in the resource block pool are denoted by $(m_0^{PSCCH}, m_1^{PSCCH}, \dots, m_{M_{PSCCH-RP}-1}^{PSCCH})$ arranged in increasing order of resource block indices and $M_{PSCCH-RP}^{PSCCH}$ is the number of resource blocks in the resource block pool.

14.3 Physical Sidelink Discovery Channel related procedures

14.3.1 UE procedure for transmitting the PSDCH

If a UE is configured by higher layers to transmit PSDCH according to a PSDCH resource configuration, in a PSDCH period i ,

- the number of transmissions for a transport block on PSDCH is $N_{SLD}^{TX} = n + 1$ where n is given by the higher layer parameter *numRetx-r12*, and each transmission corresponds to one subframe belonging to a set of subframes, and in each subframe, the PSDCH is transmitted on two physical resource blocks per slot.
- for sidelink discovery type 1,
 - the allowed values for PSDCH resource selection are given by $0, 1, \dots, (N_i \cdot N_f - 1)$, where $N_i = \lfloor L_{PSDCH} / N_{SLD}^{TX} \rfloor$ and $N_f = \lfloor M_{PSCCH-RP}^{PSCCH} / 2 \rfloor$, and

- the j -th transmission ($1 \leq j \leq N_{\text{SLD}}^{\text{TX}}$) for the transport block occurs in contiguous resource blocks $m_{2 \cdot a_j^{(i)}}^{\text{PSDCH}}$ and $m_{2 \cdot a_j^{(i)}+1}^{\text{PSDCH}}$ of subframe $l_{N_{\text{SLD}}^{\text{TX}} \cdot b_1^{(i)}+j-1}^{\text{PSDCH}}$ of the PSDCH period, where
 - $a_j^{(i)} = ((j-1) \cdot \lfloor N_f / N_{\text{SLD}}^{\text{TX}} \rfloor + \lfloor n_{\text{PSDCH}} / N_t \rfloor) \bmod N_f$ and $b_1^{(i)} = n_{\text{PSDCH}} \bmod N_t$ and using selected resource value n_{PSDCH} (described in [8]).
 - $(l_0^{\text{PSDCH}}, l_1^{\text{PSDCH}}, \dots, l_{L_{\text{PSDCH}}-1}^{\text{PSDCH}}), (m_0^{\text{PSDCH}}, m_1^{\text{PSDCH}}, \dots, m_{M_{\text{RB}}^{\text{PSDCH}}-RP-1}^{\text{PSDCH}}), L_{\text{PSDCH}}$ and $M_{\text{RB}}^{\text{PSDCH}}-RP$ are described in subclause 14.3.3.
- for sidelink discovery type 2B,
 - The j -th transmission ($1 \leq j \leq N_{\text{SLD}}^{\text{TX}}$) for the transport block occurs in contiguous resource blocks $m_{2 \cdot a_j^{(i)}}^{\text{PSDCH}}$ and $m_{2 \cdot a_j^{(i)}+1}^{\text{PSDCH}}$ of subframe $l_{N_{\text{SLD}}^{\text{TX}} \cdot b_1^{(i)}+j-1}^{\text{PSDCH}}$ of the PSDCH period, where
 - $a_1^{(i)} = ((N_{\text{PSDCH}}^{(2)} + n') \bmod 10 + \lfloor (a_1^{(i-1)} + N_f \cdot b_1^{(i-1)}) / N_t \rfloor) \bmod N_f$
 - $b_1^{(i)} = (N_{\text{PSDCH}}^{(1)} + N_{\text{PSDCH}}^{(3)} \cdot a_1^{(i-1)} + N_f \cdot b_1^{(i-1)}) \bmod N_t$
 - $a_j^{(i)} = ((j-1) \cdot \lfloor N_f / N_{\text{SLD}}^{\text{TX}} \rfloor + a_1^{(i)}) \bmod N_f$ for $1 < j \leq N_{\text{SLD}}^{\text{TX}}$
 - $N_t = \lfloor L_{\text{PSDCH}} / N_{\text{SLD}}^{\text{TX}} \rfloor$ and $N_f = \lfloor M_{\text{RB}}^{\text{PSDCH}}-RP / 2 \rfloor$, and $(l_0^{\text{PSDCH}}, l_1^{\text{PSDCH}}, \dots, l_{L_{\text{PSDCH}}-1}^{\text{PSDCH}}), (m_0^{\text{PSDCH}}, m_1^{\text{PSDCH}}, \dots, m_{M_{\text{RB}}^{\text{PSDCH}}-RP-1}^{\text{PSDCH}}), L_{\text{PSDCH}}$ and $M_{\text{RB}}^{\text{PSDCH}}-RP$ are described in subclause 14.3.3.
 - $a_1^{(0)}$ and $b_1^{(0)}$ are given by higher layer parameters *discPRB-Index* and *discSF-Index*, respectively and that associated with the PSDCH resource configuration.
 - $N_{\text{PSDCH}}^{(1)}, N_{\text{PSDCH}}^{(2)}$ and $N_{\text{PSDCH}}^{(3)}$ are given by higher layer parameters *a-r12*, *b-r12*, and *c-r12*, respectively and that are associated with the PSDCH resource configuration.
 - n' is the number of PSDCH periods since $N_{\text{PSDCH}}^{(2)}$ was received.
- the transport block size is 232

For sidelink discovery, the UE transmit power P_{PSDCH} is given by the following

$$P_{\text{PSDCH}} = \min \left\{ P_{\text{CMAX,PSDCH}}, 10 \log_{10} (M_{\text{PSDCH}}) + P_{\text{O_PSDCH,1}} + \alpha_{\text{PSDCH,1}} \cdot PL \right\} \text{ [dBm]}$$

where $P_{\text{CMAX,PSDCH}}$ is defined in [6], and $M_{\text{PSDCH}}=2$ and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1.

$P_{\text{O_PSDCH,1}}$ and $\alpha_{\text{PSDCH,1}}$ are provided by higher layer parameters *p0-r12* and *alpha-r12*, respectively and are associated with the corresponding PSDCH resource configuration.

A UE shall drop any PSDCH transmissions that are associated with sidelink discovery type 1 in a sidelink subframe if the UE has a PSDCH transmission associated with sidelink discovery type 2B in that subframe.

14.3.2 UE procedure for receiving the PSDCH

For sidelink discovery type 1, for each PSDCH resource configuration associated with reception of PSDCH, a UE configured by higher layers to detect a transport block on PSDCH can decode the PSDCH according to the PSDCH resource configuration.

For sidelink discovery type 2B, for each PSDCH resource configuration associated with reception of PSDCH, a UE configured by higher layers to detect a transport block on PSDCH can decode the PSDCH according to the PSDCH resource configuration.

14.3.3 UE procedure for determining resource block pool and subframe pool for sidelink discovery

A PSDCH resource configuration for transmission/reception is associated with a set of periodically occurring time-domain periods (known as PSDCH periods). The i -th PSDCH period begins at subframe with subframe index $j_{begin} = O_3 + i \cdot P$ and ends in subframe with subframe index $j_{end} = O_3 + (i + 1) \cdot P - 1$, where

$$0 \leq j_{begin} < 10240,$$

- the subframe index is relative to subframe#0 of a radio frame corresponding to SFN 0 of the serving cell or DFN 0 (described in [11]),
- O_3 is the *offsetIndicator-r12* indicated by the PSDCH resource configuration
- P is the *discPeriod-r12* indicated by the PSDCH resource configuration.

For a PSDCH period, the UE determines a discovery pool consisting of a subframe pool and a resource block pool for PSDCH as follows.

- For TDD, if the parameter *tdd-Config-r12* is indicated by the PSDCH resource configuration, the TDD UL/DL configuration used for determining the subframe pool is given by the parameter *tdd-Config-r12*, otherwise, the TDD UL/DL configuration used for determining the subframe pool is given by the UL/DL configuration (i.e. parameter *subframeAssignment*) for the serving cell.
- A bitmap $b_0, b_1, b_2, \dots, b_{N'-1}$ is obtained using $b_j = a_{j \bmod N_B}$, for $0 \leq j < N'$, where $a_0, a_1, a_2, \dots, a_{N_B-1}$ and N_B are the bitmap and the length of the bitmap indicated by *subframeBitmap-r12*, respectively, and $N' = N_B \cdot N_R$, where N_R is the *numRepetition-r12* indicated by the PSDCH resource configuration.
- The first N' uplink subframes are denoted by $(l_0, l_1, \dots, l_{N'-1})$ arranged in increasing order of subframe index.
- A subframe l_j ($0 \leq j < N'$) belongs to the subframe pool if $b_j = 1$. The subframes in the subframe pool are denoted by $(l_0^{PSDCH}, l_1^{PSDCH}, \dots, l_{L_{PSDCH}-1}^{PSDCH})$ arranged in increasing order of subframe index and L_{PSDCH} denotes the number of subframes in the subframe pool.
- A PRB with index q ($0 \leq q < N_{RB}^{SL}$) belongs to the resource block pool if $S1 \leq q < S1 + M$ or if $S2 - M < q \leq S2$, where $S1$, $S2$, and M denote the *prb-Start-r12*, *prb-End-r12* and *prb-Num-r12* indicated by the PSDCH resource configuration respectively.
- The resource blocks in the resource block pool are denoted by $(m_0^{PSDCH}, m_1^{PSDCH}, \dots, m_{M_{RB}^{PSDCH}-1}^{PSDCH})$ arranged in increasing order of resource block indices and M_{RB}^{PSDCH} is the number of resource blocks in the resource block pool.

14.4 Physical Sidelink Synchronization related procedures

The synchronization resource configuration(s) for the UE are given by the higher layer parameter *SL-SyncConfig-r12*.

A UE shall transmit sidelink synchronisation signals according to subclause 5.10.7 in [11].

A UE may assume that sidelink synchronization signals are signals transmitted by an eNB as described in subclause 6.11 of [3] or are signals transmitted by a UE as described in [11].

A UE is not expected to blindly detect the cyclic prefix length of sidelink synchronization signals transmitted by another UE.

For a sidelink synchronization resource configuration associated with PSDCH reception, if cell c is indicated by the parameter $physCellId-r12$ and if the parameter $discSyncWindow-r12$ is configured with value $w1$ for cell c , the UE may assume that sidelink synchronization signals are transmitted in cell c and that they are received within a reference synchronization window of size $\pm w1$ ms with respect to the sidelink synchronization resource of cell c indicated by higher layers. The sidelink synchronization identity associated with the sidelink synchronization resource is indicated by higher layers.

For PSDCH reception, if cell c is indicated by the parameter $physCellId-r12$ and if the parameter $discSyncWindow-r12$ is configured with value $w2$ for cell c , the UE may assume that PSDCH of UE in cell c is received within a reference synchronization window of size $\pm w2$ ms with respect to the discovery resource of cell c indicated by higher layers.

The UE transmit power of primary sidelink synchronization signal P_{PSSS} and the UE transmit power of secondary synchronization signal P_{SSSS} are given by

- If the UE is configured with sidelink transmission mode 1, and if the UE transmits sidelink synchronization signals in PSCCH period i , and if the TPC command field in the configured sidelink grant (described in [8]) for the PSCCH period i is set to 0

$$P_{\text{PSSS}} = P_{\text{C}_{\text{MAX,PSBCH}}}$$

$$P_{\text{SSSS}} = P_{\text{C}_{\text{MAX,SSSS}}}$$

- otherwise

$$P_{\text{PSSS}} = \min\left\{P_{\text{C}_{\text{MAX,PSBCH}}}, 10\log_{10}(M_{\text{PSSS}}) + P_{\text{O}_{\text{PSSS}}} + \alpha_{\text{PSSS}} \cdot PL\right\} \text{ [dBm]},$$

$$P_{\text{SSSS}} = \min\left\{P_{\text{C}_{\text{MAX,SSSS}}}, 10\log_{10}(M_{\text{PSSS}}) + P_{\text{O}_{\text{PSSS}}} + \alpha_{\text{PSSS}} \cdot PL\right\} \text{ [dBm]},$$

where $P_{\text{C}_{\text{MAX,PSBCH}}}$ and $P_{\text{C}_{\text{MAX,SSSS}}}$ are defined in [6]. $M_{\text{PSSS}} = 6$ and $PL = PL_c$ where PL_c is defined in subclause 5.1.1.1. $P_{\text{O}_{\text{PSSS}}}$ and α_{PSSS} are provided by higher layer parameters associated with the corresponding sidelink synchronization signal resource configuration.

Annex A (informative): Change history

| Change history | | | | | | | |
|----------------|--------|-----------|------|-----|---|-------|-------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 2006-09 | | | | | Draft version created | | 0.0.0 |
| 2006-10 | | | | | Endorsed by RAN1 | 0.0.0 | 0.1.0 |
| 2007-01 | | | | | Inclusion of decisions from RAN1#46bis and RAN1#47 | 0.1.0 | 0.1.1 |
| 2007-01 | | | | | Endorsed by RAN1 | 0.1.1 | 0.2.0 |
| 2007-02 | | | | | Inclusion of decisions from RAN1#47bis | 0.2.0 | 0.2.1 |
| 2007-02 | | | | | Endorsed by RAN1 | 0.2.1 | 0.3.0 |
| 2007-02 | | | | | Editor's version including decisions from RAN1#48 & RAN1#47bis | 0.3.0 | 0.3.1 |
| 2007-03 | | | | | Updated Editor's version | 0.3.1 | 0.3.2 |
| 2007-03 | RAN-35 | RP-070171 | | | For information at RAN#35 | 0.3.2 | 1.0.0 |
| 2007-03 | | | | | Random access text modified to better reflect RAN1 scope | 1.0.0 | 1.0.1 |
| 2007-03 | | | | | Updated Editor's version | 1.0.1 | 1.0.2 |
| 2007-03 | | | | | Endorsed by RAN1 | 1.0.2 | 1.1.0 |
| 2007-05 | | | | | Updated Editor's version | 1.1.0 | 1.1.1 |
| 2007-05 | | | | | Updated Editor's version | 1.1.1 | 1.1.2 |
| 2007-05 | | | | | Endorsed by RAN1 | 1.1.2 | 1.2.0 |
| 2007-08 | | | | | Updated Editor's version | 1.2.0 | 1.2.1 |
| 2007-08 | | | | | Updated Editor's version – uplink power control from RAN1#49bis | 1.2.1 | 1.2.2 |
| 2007-08 | | | | | Endorsed by RAN1 | 1.2.2 | 1.3.0 |
| 2007-09 | | | | | Updated Editor's version reflecting RAN#50 decisions | 1.3.0 | 1.3.1 |
| 2007-09 | | | | | Updated Editor's version reflecting comments | 1.3.1 | 1.3.2 |
| 2007-09 | | | | | Updated Editor's version reflecting further comments | 1.3.2 | 1.3.3 |
| 2007-09 | | | | | Updated Editor's version reflecting further comments | 1.3.3 | 1.3.4 |
| 2007-09 | | | | | Updated Editor's version reflecting further comments | 1.3.4 | 1.3.5 |
| 2007-09 | RAN-37 | RP-070731 | | | Endorsed by RAN1 | 1.3.5 | 2.0.0 |
| 2007-09 | RAN-37 | RP-070737 | | | For approval at RAN#37 | 2.0.0 | 2.1.0 |
| 12/09/07 | RP-37 | RP-070737 | - | - | Approved version | 2.1.0 | 8.0.0 |
| 28/11/07 | RP-38 | RP-070949 | 0001 | 2 | Update of 36.213 | 8.0.0 | 8.1.0 |
| 05/03/08 | RP-39 | RP-080145 | 0002 | - | Update of TS 36.213 according to changes listed in cover sheet | 8.1.0 | 8.2.0 |
| 28/05/08 | RP-40 | RP-080434 | 0003 | 1 | PUCCH timing and other formatting and typo corrections | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0006 | 1 | PUCCH power control for non-unicast information | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0008 | - | UE ACK/NACK Procedure | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0009 | - | UL ACK/NACK timing for TDD | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0010 | - | Specification of UL control channel assignment | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0011 | - | Precoding Matrix for 2Tx Open-loop SM | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0012 | - | Clarifications on UE selected CQI reports | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0013 | 1 | UL HARQ Operation and Timing | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0014 | - | SRS power control | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0015 | 1 | Correction of UE PUSCH frequency hopping procedure | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0017 | 4 | Blind PDCCH decoding | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0019 | 1 | Tx Mode vs DCI format is clarified | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0020 | - | Resource allocation for distributed VRB | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0021 | 2 | Power Headroom | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0022 | - | Clarification for RI reporting in PUCCH and PUSCH reporting modes | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0025 | - | Correction of the description of PUSCH power control for TDD | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0026 | - | UL ACK/NACK procedure for TDD | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0027 | - | Indication of radio problem detection | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0028 | - | Definition of Relative Narrowband TX Power Indicator | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0029 | - | Calculation of $\Delta_{TF}(i)$ for UL-PC | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0030 | - | CQI reference and set S definition, CQI mode removal, and Miscellaneous | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0031 | - | Modulation order and TBS determination for PDSCH and PUSCH | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080434 | 0032 | - | On Sounding RS | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080426 | 0033 | - | Multiplexing of rank and CQI/PMI reports on PUCCH | 8.2.0 | 8.3.0 |
| 28/05/08 | RP-40 | RP-080466 | 0034 | - | Timing advance command responding time | 8.2.0 | 8.3.0 |
| 09/09/08 | RP-41 | RP-080670 | 37 | 2 | SRS hopping pattern for closed loop antenna selection | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 39 | 2 | Clarification on uplink power control | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 41 | - | Clarification on DCI formats using resource allocation type 2 | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 43 | 2 | Clarification on tree structure of CCE aggregations | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 46 | 2 | Correction of the description of PUCCH power control for TDD | 8.3.0 | 8.4.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|---|-------|-------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 09/09/08 | RP-41 | RP-080670 | 47 | 1 | Removal of CR0009 | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 48 | 1 | Correction of mapping of cyclic shift value to PHICH modifier | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 49 | - | TBS disabling for DCI formats 2 and 2A | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 50 | - | Correction of maximum TBS sizes | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 51 | - | Completion of the table specifying the number of bits for the periodic feedback | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 54 | - | Clarification of RNTI for PUSCH/PUCCH power control with DCI formats 3/3A | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 55 | 1 | Clarification on mapping of Differential CQI fields | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 59 | 1 | PUSCH Power Control | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 60 | - | RB restriction and modulation order for CQI-only transmission on PUSCH | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 61 | - | Modulation order determination for uplink retransmissions | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 62 | 2 | Introducing missing L1 parameters into 36.213 | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 63 | 2 | Correcting the range and representation of delta_TF_PUCCH | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 64 | 1 | Adjusting TBS sizes to for VoIP | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 67 | - | Correction to the downlink resource allocation | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 68 | - | Removal of special handling for PUSCH mapping in PUCCH region | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 69 | - | Correction to the formulas for uplink power control | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 70 | 1 | Definition of Bit Mapping for DCI Signalling | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 71 | - | Clarification on PUSCH TPC commands | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 72 | 1 | Reference for CQI/PMI Reporting Offset | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 74 | - | Correction to the downlink/uplink timing | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 75 | - | Correction to the time alignment command | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 77 | 1 | Correction of offset signalling of UL Control information MCS | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 78 | 2 | DCI format1C | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 80 | - | Correction to Precoder Cycling for Open-loop Spatial Multiplexing | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 81 | 1 | Clarifying Periodic CQI Reporting using PUCCH | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 84 | 1 | CQI reference measurement period | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 86 | - | Correction on downlink multi-user MIMO | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 87 | - | PUCCH Reporting | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 88 | 1 | Handling of Uplink Grant in Random Access Response | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 89 | - | Correction to UL Hopping operation | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 90 | - | DRS EPRE | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 92 | - | Uplink ACK/NACK mapping for TDD | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 93 | - | UL SRI Parameters Configuration | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 94 | - | Miscellaneous updates for 36.213 | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 95 | - | Clarifying Requirement for Max PDSCH Coding Rate | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 96 | - | UE Specific SRS Configuration | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 97 | - | DCI Format 1A changes needed for scheduling Broadcast Control | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 98 | - | Processing of TPC bits in the random access response | 8.3.0 | 8.4.0 |
| 09/09/08 | RP-41 | RP-080670 | 100 | 1 | Support of multi-bit ACK/NAK transmission in TDD | 8.3.0 | 8.4.0 |
| 03/12/08 | RP-42 | RP-081075 | 82 | 3 | Corrections to RI for CQI reporting | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 83 | 2 | Moving description of large delay CDD to 36.211 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 102 | 3 | Reception of DCI formats | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 105 | 8 | Alignment of RAN1/RAN2 specification | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 107 | 1 | General correction of reset of power control and random access response message | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 108 | 2 | Final details on codebook subset restrictions | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 109 | - | Correction on the definition of Pmax | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 112 | 2 | CQI/PMI reference measurement periods | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 113 | - | Correction of introduction of shortened SR | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 114 | - | RAN1/2 specification alignment on HARQ operation | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 115 | - | Introducing other missing L1 parameters in 36.213 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 116 | - | PDCCH blind decoding | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 117 | - | PDCCH search space | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 119 | - | Delta_TF for PUSCH | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 120 | - | Delta_preamble_msg3 parameter values and TPC command in RA response | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 122 | 1 | Correction of offset signaling of uplink control information MCS | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 124 | - | Miscellaneous Corrections | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 125 | - | Clarification of the uplink index in TDD mode | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 126 | - | Clarification of the uplink transmission configurations | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 127 | 2 | Correction to the PHICH index assignment | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 128 | - | Clarification of type-2 PDSCH resource allocation for format 1C | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 129 | - | Clarification of uplink grant in random access response | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 130 | - | UE sounding procedure | 8.4.0 | 8.5.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|---|-------|-------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 03/12/08 | RP-42 | RP-081075 | 134 | - | Change for determining DCI format 1A TBS table column indicator for broadcast control | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 135 | - | Clarifying UL VRB Allocation | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 136 | 1 | Correction for Aperiodic CQI | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 137 | 1 | Correction for Aperiodic CQI Reporting | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 138 | 1 | Correction to PUCCH CQI reporting mode for $N^{DL_RB} \leq 7$ | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 140 | 1 | On sounding procedure in TDD | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 141 | 1 | Alignment of RAN1/RAN3 specification | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 143 | 1 | TTI bundling | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 144 | 1 | ACK/NACK transmission on PUSCH for LTE TDD | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 145 | 1 | Timing relationship between PHICH and its associated PUSCH | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 147 | 1 | Definition of parameter for downlink reference signal transmit power | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 148 | 1 | Radio link monitoring | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 149 | 1 | Correction in 36.213 related to TDD downlink HARQ processes | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 151 | - | Nominal PDSCH-to-RS EPRE Offset for CQI Reporting | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 152 | 1 | Support of UL ACK/NAK repetition in Rel-8 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 155 | - | Clarification of misconfiguration of aperiodic CQI and SR | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 156 | 1 | Correction of control information multiplexing in subframe bundling mode | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 157 | - | Correction to the PHICH index assignment | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 158 | 1 | UE transmit antenna selection | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 159 | - | Clarification of spatial different CQI for CQI reporting Mode 2-1 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 160 | 1 | Corrections for TDD ACK/NACK bundling and multiplexing | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 161 | - | Correction to RI for Open-Loop Spatial Multiplexing | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 162 | - | Correction of differential CQI | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 163 | - | Inconsistency between PMI definition and codebook index | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 164 | - | PDCCH validation for semi-persistent scheduling | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 165 | 1 | Correction to the UE behavior of PUCCH CQI piggybacked on PUSCH | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 166 | - | Correction on SRS procedure when shortened PUCCH format is used | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 167 | 1 | Transmission overlapping of physical channels/signals with PDSCH for transmission mode 7 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 169 | - | Clarification of SRS and SR transmission | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 171 | - | Clarification on UE behavior when skipping decoding | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 172 | 1 | PUSCH Hopping operation corrections | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 173 | - | Clarification on message 3 transmission timing | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 174 | - | MCS handling for DwPTS | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 175 | - | Clarification of UE-specific time domain position for SR transmission | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 176 | 1 | Physical layer parameters for CQI reporting | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 177 | - | A-periodic CQI clarification for TDD UL/DL configuration 0 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 179 | 1 | Correction to the definitions of rho_A and rho_B (downlink power allocation) | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 180 | - | Clarification of uplink A/N resource indication | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 181 | - | PDCCH format 0 for message 3 adaptive retransmission and transmission of control information in message 3 during contention based random access procedure | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081075 | 182 | - | To Fix the Discrepancy of Uplink Power Control and Channel Coding of Control Information in PUSCH | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081122 | 183 | 1 | CQI reporting for antenna port 5 | 8.4.0 | 8.5.0 |
| 03/12/08 | RP-42 | RP-081110 | 168 | 1 | Clarification on path loss definition | 8.4.0 | 8.5.0 |
| 04/03/09 | RP-43 | RP-090236 | 184 | 1 | Corrections to Transmitted Rank Indication | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 185 | 4 | Corrections to transmission modes | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 186 | 2 | Delta_TF configuration for control only PUSCH | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 187 | 1 | Correction to concurrent SRS and ACK/NACK transmission | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 191 | 1 | PDCCH release for semi-persistent scheduling | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 192 | 1 | Correction on ACKNACK transmission on PUSCH for LTE TDD | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 193 | - | Correction to subband differential CQI value to offset level mapping for aperiodic CQI reporting | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 194 | - | Correction for DRS Collision handling | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 196 | 2 | Alignment of RAN1/RAN4 specification on UE maximum output power | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 197 | - | Transmission scheme for transmission mode 7 with SPS C-RNTI | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 198 | - | Clarifying bandwidth parts for periodic CQI reporting and CQI reference period | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 199 | 2 | Correction to the ACK/NACK bundling in case of transmission mode 3 and 4 | 8.5.0 | 8.6.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|---|-------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 04/03/09 | RP-43 | RP-090236 | 200 | - | ACK/NAK repetition for TDD ACK/NAK multiplexing | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 201 | - | Clarifying UL ACK/NAK transmission in TDD | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 202 | - | Corrections to UE Transmit Antenna Selection | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 203 | - | Correction to UE PUSCH hopping procedure | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 204 | - | Correction to PHICH resource association in TTI bundling | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 205 | - | Clarification of the length of resource assignment | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 206 | - | Correction on ACK/NACK transmission for downlink SPS resource release | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 207 | - | Introduction of additional values of wideband CQI/PMI periodicities | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 208 | 2 | Correction to CQI/PMI/RI reporting field | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 209 | 2 | Correction to rho_A definition for CQI calculation | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 210 | - | Correction to erroneous cases in PUSCH linear block codes | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 211 | 1 | Removing RL monitoring start and stop | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 214 | 1 | Correction to type-1 and type-2 PUSCH hopping | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 215 | - | Contradicting statements on determination of CQI subband size | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 216 | - | Corrections to SRS | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 219 | 2 | Miscellaneous corrections on TDD ACKNACK | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 221 | 1 | CR for Redundancy Version mapping function for DCI 1C | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 223 | - | Scrambling of PUSCH corresponding to Random Access Response Grant | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 225 | - | Removal of SRS with message 3 | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 226 | 3 | PRACH retransmission timing | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 227 | - | Clarifying error handling of PDSCH and PUSCH assignments | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 228 | - | Clarify PHICH index mapping | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 229 | - | Correction of CQI timing | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 230 | - | Alignment of CQI parameter names with RRC | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 231 | 1 | Removal of 'Off' values for periodic reporting in L1 | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 232 | - | Default value of RI | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 233 | 1 | Clarification of uplink timing adjustments | 8.5.0 | 8.6.0 |
| 04/03/09 | RP-43 | RP-090236 | 234 | - | Clarification on ACK/NAK repetition | 8.5.0 | 8.6.0 |
| 27/05/09 | RP-44 | RP-090529 | 235 | 1 | Correction to the condition of resetting accumulated uplink power correction | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 236 | - | Correction to the random access channel parameters received from higher layer | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 237 | - | Correction on TDD ACKNACK | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 238 | 1 | Correction on CQI reporting | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 239 | - | Correction on the HARQ process number | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 241 | 1 | CR correction of the description on TTI-bundling | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 242 | 1 | Clarify latest and initial PDCCH for PDSCH and PUSCH transmissions, and NDI for SPS activation | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 243 | - | Clarify DRS EPRE | 8.6.0 | 8.7.0 |
| 27/05/09 | RP-44 | RP-090529 | 244 | 1 | Clarification on TPC commands for SPS | 8.6.0 | 8.7.0 |
| 15/09/09 | RP-45 | RP-090888 | 245 | 1 | Correction to PUSCH hopping and PHICH mapping procedures | 8.7.0 | 8.8.0 |
| 15/09/09 | RP-45 | RP-090888 | 246 | - | Clarification on subband indexing in periodic CQI reporting | 8.7.0 | 8.8.0 |
| 15/09/09 | RP-45 | RP-090888 | 247 | 2 | Correction to DVRB operation in TDD transmission mode 7 | 8.7.0 | 8.8.0 |
| 15/09/09 | RP-45 | RP-090888 | 249 | - | Clarification of concurrent ACKNACK and periodic PMI/RI transmission on PUCCH for TDD | 8.7.0 | 8.8.0 |
| 15/09/09 | RP-45 | RP-090888 | 250 | - | Clarify Inter-cell synchronization text | 8.7.0 | 8.8.0 |
| 01/12/09 | RP-46 | RP-091172 | 248 | 1 | Introduction of LTE positioning | 8.8.0 | 9.0.0 |
| 01/12/09 | RP-46 | RP-091172 | 254 | - | Clarification of PDSCH and PRS in combination for LTE positioning | 8.8.0 | 9.0.0 |
| 01/12/09 | RP-46 | RP-091177 | 255 | 5 | Editorial corrections to 36.213 | 8.8.0 | 9.0.0 |
| 01/12/09 | RP-46 | RP-091257 | 256 | 1 | Introduction of enhanced dual layer transmission | 8.8.0 | 9.0.0 |
| 01/12/09 | RP-46 | RP-091177 | 257 | 1 | Add shorter SR periodicity | 8.8.0 | 9.0.0 |
| 01/12/09 | RP-46 | RP-091256 | 258 | - | Introduction of LTE MBMS | 8.8.0 | 9.0.0 |
| 17/12/09 | RP-46 | RP-091257 | 256 | 1 | Correction by MCC due to wrong implementation of CR0256r1 – Sentence is added to Single-antenna port scheme subclause 7.1.1 | 9.0.0 | 9.0.1 |
| 16/03/10 | RP-47 | RP-100211 | 259 | 3 | UE behavior when collision of antenna port 7/8 with PBCH or SCH happened and when distributed VRB is used with antenna port 7 | 9.0.1 | 9.1.0 |
| 16/03/10 | RP-47 | RP-100210 | 260 | 1 | MCCH change notification using DCI format 1C | 9.0.1 | 9.1.0 |
| 16/03/10 | RP-47 | RP-100211 | 263 | - | Correction on PDSCH EPRE and UE-specific RS EPRE for Rel-9 enhanced DL transmissions | 9.0.1 | 9.1.0 |
| 01/06/10 | RP-48 | RP-100589 | 265 | - | Clarification for TDD when multiplexing ACK/NACK with SR of ACK/NACK with CQI/PMI or RI | 9.1.0 | 9.2.0 |
| 01/06/10 | RP-48 | RP-100590 | 268 | 1 | Clarification of PRS EPRE | 9.1.0 | 9.2.0 |
| 14/09/10 | RP-49 | RP-100900 | 269 | - | Clarification on Extended CP support with Transmission Mode 8 | 9.2.0 | 9.3.0 |
| 07/12/10 | RP-50 | RP-101320 | 270 | - | Introduction of Rel-10 LTE-Advanced features in 36.213 | 9.3.0 | 10.0.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|---|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 27/12/10 | - | - | - | - | Editorial change to correct a copy/past error in subclause 7.2.2 | 10.0.0 | 10.0.1 |
| 15/03/11 | RP-51 | RP-110255 | 271 | 1 | A clarification for redundancy version of PMCH | 10.0.1 | 10.1.0 |
| 15/03/11 | RP-51 | RP-110258 | 272 | - | RLM Procedure with restricted measurements | 10.0.1 | 10.1.0 |
| 15/03/11 | RP-51 | RP-110256 | 273 | - | Corrections to Rel-10 LTE-Advanced features in 36.213 | 10.0.1 | 10.1.0 |
| 01/06/11 | RP-52 | RP-110819 | 274 | 3 | Correction to HARQ-ACK procedure for TDD mode b with M=2 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 275 | 3 | Determination of PUSCH A/N codebook size for TDD | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110823 | 276 | - | The triggering of aperiodic SRS in DCI formats 2B and 2C | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 278 | 3 | Corrections to power headroom | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 279 | 1 | Removal of square brackets for PUCCH format 3 ACK/NACK | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 281 | 1 | Correction of AN repetition and PUCCH format 3 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 282 | 2 | Correction to timing for secondary cell activation and deactivation | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110823 | 283 | 1 | Correction to MCS offset for multiple TBs | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110820 | 286 | 1 | Miscellaneous Corrections | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 288 | 1 | Corrections on UE procedure for determining PUCCH Assignment | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 289 | 2 | Correction to Multi-cluster flag in DCI format 0 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 290 | 2 | Joint transmission of ACK/NACK and SR with PUCCH format 3 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 291 | 3 | Correction of uplink resource allocation type 1 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 292 | 1 | Correction on CSI-RS configuration | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110818 | 294 | - | ACK/NACK and CQI simultaneous transmission in ACK/NACK bundling in TDD | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110823 | 295 | - | UE specific disabling of UL DMRS sequence hopping | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 296 | - | PDSCH transmission in MBSFN subframes | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 297 | - | Introduction of PCMAX for PUSCH power scaling | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 298 | - | Power control for SR and ACK/NACK with PUCCH format 3 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 299 | 2 | CR on power control for HARQ-ACK transmission on PUCCH | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 300 | 2 | Correction to handling of search space overlap | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 301 | 1 | Correction to simultaneous transmission of SRS and PUCCH format 2/2a/2b | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 302 | 1 | Correction for Simultaneous PUCCH and SRS Transmissions on CA | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 303 | - | Correction on 8Tx Codebook Sub-sampling for PUCCH Mode 1-1 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 304 | 1 | Corrections on CQI type in PUCCH mode 2-1 and clarification on simultaneous PUCCH and PUSCH transmission for UL-SCH subframe bundling | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110818 | 305 | 1 | Correction on UE behaviour upon reporting periodic CSI using PUCCH Mode1-1 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110818 | 306 | - | Clarification for the definition of CQI | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110818 | 307 | - | Clarification for the definition of Precoding Matrix Indicator | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 308 | - | Simultaneous SRS transmissions in more than one cell | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 310 | 1 | Miscellaneous Corrections for TS 36.213 | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 311 | 1 | Configuration of pmi-RI-Report | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 312 | 1 | Correction on the support of PUCCH format 3 and channel selection | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110821 | 313 | - | Correction on UE behaviour during DM-RS transmission on subframes carrying synchronization signals | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110820 | 314 | 1 | 36.213 CR on antenna selection | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110823 | 316 | 1 | Number of HARQ process for UL spatial multiplexing | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 317 | - | PUCCH format 3 Fallback procedure in TDD | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 318 | - | Clarification on CSI reporting under an invalid downlink subframe | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 320 | - | Multiple Aperiodic SRS Triggers for Same Configuration | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110823 | 321 | - | UE antenna switch in UL MIMO | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110819 | 322 | - | UE behaviour for PDSCH reception with limited soft buffer in CA | 10.1.0 | 10.2.0 |
| 01/06/11 | RP-52 | RP-110859 | 323 | - | Joint transmission of ACK/NACK and SR or CSI with PUCCH format 3 and channel selection | 10.1.0 | 10.2.0 |
| 15/09/11 | RP-53 | RP-111229 | 277 | 1 | Correction to reception of PRS in MBSFN subframes | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 325 | 3 | Corrections on UE procedure for reporting HARQ-ACK | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 326 | 2 | Corrections on Physical Uplink Control Channel Procedure | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111231 | 331 | 1 | Correction to uplink transmission scheme usage for random access response and PHICH-triggered retransmissions | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111229 | 336 | - | Corrections on transmission mode 9 | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 339 | - | Corrections on HARQ-ACK codebook size determination | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 340 | - | Corrections on TDD PUCCH format 1b with channel selection and HARQ-ACK transmission on PUSCH | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 341 | - | Corrections on NACK generation | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 342 | - | Corrections on power headroom reporting | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111229 | 346 | - | Correction on TBS translation table | 10.2.0 | 10.3.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|--|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 15/09/11 | RP-53 | RP-111229 | 347 | 2 | Correction to the condition of enabling PMI feedback | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111232 | 348 | - | Miscellaneous corrections to 36.213 | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111229 | 349 | - | Corrections on PUSCH and PUCCH modes | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111231 | 350 | 1 | CR on UL HARQ ACK determination | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111231 | 351 | 1 | Correction on UL DMRS resources for PHICH-triggered retransmission | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 352 | - | Clarification on the common search space description | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111232 | 353 | 1 | Clarification on ambiguous DCI information between UE-specific search space and common search space for DCI formats 0 and 1A | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111229 | 354 | - | Clarification of Reference PDSCH Power for CSI-RS based CSI Feedback | 10.2.0 | 10.3.0 |
| 15/09/11 | RP-53 | RP-111230 | 355 | 2 | Corrections on reporting Channel State Information | 10.2.0 | 10.3.0 |
| 05/12/11 | RP-54 | RP-111669 | 324 | 3 | Accumulation of power control commands from DCI format 3/3A | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 357 | 1 | Miscellaneous corrections on uplink power control | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 358 | - | Corrections on N_c {received} | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 359 | - | Corrections on TDD PUCCH format 1b with channel selection and two configured serving cells | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 360 | - | Corrections on the notation of k and k_m | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111668 | 361 | 1 | Corrections on PUCCH mode 2-1 | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111668 | 362 | 3 | A correction to PDSCH transmission assumption for CQI calculation | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 363 | 1 | Corrections on PUCCH Resource Notation | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111667 | 364 | - | Correction on the notation of SRS transmission comb | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 365 | - | Clarification on the HARQ-ACK procedure of TDD UL-DL configuration 5 | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 366 | 2 | Clarification on the determination of resource for PUCCH Format 1b with channel selection in TDD mode | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 367 | 1 | Correction on HARQ-ACK procedure | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 368 | - | Correction for A/N on PUSCH with $W=1,2$ in case of TDD channel selection | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111668 | 369 | - | Clarification of PUCCH 2-1 Operation | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111668 | 370 | 1 | Correction on PMI index | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 371 | 2 | Correction to periodic CSI reports for carrier aggregation | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 373 | 1 | Removal of square bracket in HARQ-ACK procedure | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 374 | 1 | Clarification on UE's capability of supporting PUCCH format 3 | 10.3.0 | 10.4.0 |
| 05/12/11 | RP-54 | RP-111666 | 375 | 1 | Clarifications of UE behavior on PUSCH power control | 10.3.0 | 10.4.0 |
| 28/02/12 | RP-55 | RP-120286 | 376 | 1 | RNTI Configuration associated with DL Resource Allocation Type 2 | 10.4.0 | 10.5.0 |
| 28/02/12 | RP-55 | RP-120283 | 377 | 2 | Correction for ACK/NACK related procedure in case of TDD UL-DL configuration 0 | 10.4.0 | 10.5.0 |
| 13/06/12 | RP-56 | RP-120737 | 378 | 3 | Correction of FDD channel selection HARQ-ACK and SR transmission | 10.5.0 | 10.6.0 |
| 13/06/12 | RP-56 | RP-120738 | 379 | - | Removal of description with square brackets | 10.5.0 | 10.6.0 |
| 13/06/12 | RP-56 | RP-120738 | 381 | - | Correction on transmission mode 9 with a single antenna port transmission | 10.5.0 | 10.6.0 |
| 04/09/12 | RP-57 | RP-121265 | 382 | - | Clarification of codebook subsampling for PUCCH 2-1 | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121266 | 383 | - | Correction to UE transmit antenna selection | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121264 | 384 | - | TDD HARQ-ACK procedure for PUCCH format 1b with channel selection in carrier aggregation | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121265 | 385 | - | Corrections for Handling CSI-RS patterns | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121264 | 386 | 1 | Reference serving cell for pathloss estimation | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121264 | 387 | - | Power control for PUCCH format 3 with single configured cell | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121264 | 388 | - | ACK/NACK resource in case of channel selection | 10.6.0 | 10.7.0 |
| 04/09/12 | RP-57 | RP-121274 | 380 | 4 | Introduction of an additional special subframe configuration | 10.7.0 | 11.0.0 |
| 04/09/12 | RP-57 | RP-121272 | 389 | - | Introduction of Rel-11 features | 10.7.0 | 11.0.0 |
| 04/12/12 | RP-58 | RP-121839 | 393 | - | Correction to the parameter ue-Category-v10xy | 11.0.0 | 11.1.0 |
| 04/12/12 | RP-58 | RP-121837 | 395 | - | Correction of reference signal scrambling sequence initialization for SPS in transmission mode 7 | 11.0.0 | 11.1.0 |
| 04/12/12 | RP-58 | RP-121846 | 396 | - | Finalisation for introducing Rel-11 features | 11.0.0 | 11.1.0 |
| 26/02/13 | RP-59 | RP-130254 | 398 | - | Correction on UE procedure for reporting HARQ-ACK | 11.1.0 | 11.2.0 |
| 26/02/13 | RP-59 | RP-130252 | 400 | - | Corrections for SRS power scaling in UpPTS | 11.1.0 | 11.2.0 |
| 26/02/13 | RP-59 | RP-130252 | 403 | - | CR on UE specific search and Common search space overlap on PDCCH | 11.1.0 | 11.2.0 |
| 26/02/13 | RP-59 | RP-130358 | 404 | - | Additional clarifications/corrections for introducing Rel-11 features | 11.1.0 | 11.2.0 |
| 11/06/13 | RP-60 | RP-130752 | 405 | - | Correction to EPDCCH monitoring in case of cross-carrier scheduling | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130751 | 407 | 1 | Correction on the RI bit width | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 408 | - | Correction on parallel reception of PDSCH and Msg 2 | 11.2.0 | 11.3.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|--|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 11/06/13 | RP-60 | RP-130747 | 409 | - | Correction on zero power CSI-RS resource configuration | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 410 | 1 | Corrections on different TDD UL-DL configurations on different bands | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130752 | 411 | - | Correction on EPDCCH PRB pair indication | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130752 | 412 | - | Correction on EPDCCH hashing function | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130752 | 413 | - | Correction on PUCCH resource determination for FDD EPDCCH | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130752 | 414 | 2 | CR on ambiguity in EPDCCH decoding candidates under two overlapped EPDCCH resource sets | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130749 | 415 | - | Removal of the case for spatial domain bundling in TDD UL/DL configuration 0 | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130752 | 416 | - | Corrections to EPDCCH PRB pair indication | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130753 | 417 | 1 | Correction to PUSCH/PUCCH transmit power after PRACH power ramping | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130747 | 418 | - | CR on RI-Reference CSI Process with Subframe Sets | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130747 | 420 | - | Correction on UE-specific RS scrambling for SPS PDSCH in TM10 | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130747 | 421 | - | CR on resolving ambiguous UE capability signaling for CoMP | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 422 | - | Correction of valid downlink subframe | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130749 | 424 | - | Correction on HARQ-ACK transmission for a UE configured with PUCCH format 3 | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 425 | - | Correction of PHICH resource for half duplex TDD UE | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 426 | - | Correction on n_{HARQ} for TDD CA with different UL-DL configurations | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 427 | - | Correction on implicit HARQ-ACK resource determination for PUCCH format 1b with channel selection for TDD CA with different UL-DL configurations | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130750 | 428 | - | Correction on SRS power scaling with multiple TAGs | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130747 | 429 | - | Correction on MBSFN subframe configuration | 11.2.0 | 11.3.0 |
| 11/06/13 | RP-60 | RP-130749 | 430 | - | CR on SCell activation timing | 11.2.0 | 11.3.0 |
| 03/09/13 | | | | | MCC clean-up | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131249 | 432 | - | Correction for EPDCCH Search Space | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131250 | 433 | - | Correction to QCL behaviour on CRS | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131250 | 434 | - | Correction on PUCCH power control | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131248 | 435 | - | Correction on the ratio of PDSCH EPRE to CRS EPRE for TM10 | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131249 | 436 | - | CR on EPDCCH Search Space for Cross-Carrier Scheduling | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131249 | 437 | - | Correction to the UE behaviour in case of collision between PRS and EPDCCH in different CP case | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131249 | 438 | - | On correction to higher layer parameter name for EPDCCH resource mapping | 11.3.0 | 11.4.0 |
| 03/09/13 | RP-61 | RP-131248 | 439 | - | Correction to PDSCH mapping for CoMP | 11.3.0 | 11.4.0 |
| 03/12/13 | RP-62 | RP-131893 | 440 | 1 | Correction on parameter ue-Category | 11.4.0 | 11.5.0 |
| 03/12/13 | RP-62 | RP-131892 | 442 | 1 | Correction on determination of modulation order and transport block size | 11.4.0 | 11.5.0 |
| 03/12/13 | RP-62 | RP-132024 | 445 | 3 | Correction on CSI reporting type and parameters | 11.4.0 | 11.5.0 |
| 03/12/13 | RP-62 | RP-131894 | 446 | - | Correction on deriving the length of the non-MBSFN region | 11.4.0 | 11.5.0 |
| 03/12/13 | RP-62 | RP-131896 | 431 | 5 | Introduction of Rel 12 feature for Downlink MIMO Enhancement | 11.5.0 | 12.0.0 |
| 03/03/14 | RP-63 | RP-140286 | 447 | - | Correction to CSI Reporting | 12.0.0 | 12.1.0 |
| 03/03/14 | RP-63 | RP-140291 | 448 | - | Clarification on PUCCH Mode 1-1 for 4Tx Dual Codebook | 12.0.0 | 12.1.0 |
| 03/03/14 | RP-63 | RP-140287 | 450 | 1 | Common search space monitoring for MBMS | 12.0.0 | 12.1.0 |
| 03/03/14 | RP-63 | RP-140290 | 452 | - | Introduction of new UE categories | 12.0.0 | 12.1.0 |
| 03/03/14 | RP-63 | RP-140288 | 455 | 1 | Modification to l_SRS = 0 for trigger type 1 SRS and TDD | 12.0.0 | 12.1.0 |
| 03/03/14 | RP-63 | RP-140289 | 458 | - | Correction to CSI processing in TM10 | 12.0.0 | 12.1.0 |
| 10/06/14 | RP-64 | RP-140858 | 459 | 1 | Clarification on PUCCH reporting type payload size | 12.1.0 | 12.2.0 |
| 10/06/14 | RP-64 | RP-140858 | 461 | - | Clarification on SRS colliding with PUCCH in the same cell when the UE is configured with multiple TAGs | 12.1.0 | 12.2.0 |
| 10/06/14 | RP-64 | RP-140858 | 462 | 1 | Clarification on SRS antenna switching | 12.1.0 | 12.2.0 |
| 10/06/14 | RP-64 | RP-140862 | 463 | - | Introduction of Rel-12 LTE-Advanced features in 36.213 | 12.1.0 | 12.2.0 |
| 10/09/14 | RP-65 | RP-141479 | 464 | - | Correction on SRS transmission for TDD-FDD CA | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141478 | 465 | - | Correction on beta_{offset}^{HARQ-ACK} determination for a UE configured with two uplink power control subframe sets | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141478 | 466 | - | Corrections for TDD eIMTA | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141479 | 467 | 3 | CR on HARQ-ACK Multiplexing in PUSCH for TDD-FDD CA | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141474 | 469 | - | Correction to UCI embedding in case of a single serving cell and simultaneous PUSCH and PUCCH transmission | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141478 | 470 | - | Corrections on UL-reference UL/DL configuration | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141473 | 471 | - | CR for Clarification of special subframe and usage alignment | 12.2.0 | 12.3.0 |
| 10/09/14 | RP-65 | RP-141485 | 472 | - | Introduction of low-cost MTC and 256QAM features | 12.2.0 | 12.3.0 |
| 08/12/14 | RP-66 | RP-142104 | 482 | 5 | Introduction of Dual Connectivity, Small Cell Enhancements, | 12.3.0 | 12.4.0 |

| Change history | | | | | | | |
|----------------|-------|-----------|-----|-----|--|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| | | | | | NAICS, eIMTA, and TDD-FDD CA features | | |
| 08/12/14 | RP-66 | RP-142097 | 487 | 1 | Clarification of periodic CSI feedback for subband CQI and PMI | 12.3.0 | 12.4.0 |
| 08/12/14 | RP-66 | RP-142100 | 491 | - | Correction of the parameter CSIProcessIndex | 12.3.0 | 12.4.0 |
| 09/03/15 | RP-67 | RP-150366 | 492 | 2 | Introduction of D2D feature into 36.213 | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150363 | 494 | 1 | Correction to PUCCH procedures in case of FDD Pcell and TDD Scell in TDD-FDD CA | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150364 | 498 | - | Correction on higher layer parameter names for 256QAM | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150359 | 500 | - | TM10 CSI-IM Interference Measurements | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150358 | 502 | - | Clarification on common search reception related to MBMS | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150364 | 503 | - | Correction to Discovery in Small Cell Enhancement feature | 12.4.0 | 12.5.0 |
| 09/03/15 | RP-67 | RP-150365 | 504 | 1 | Corrections to Dual Connectivity feature | 12.4.0 | 12.5.0 |
| 15/06/15 | RP-68 | RP-150931 | 493 | 2 | Clarification on HARQ-ACK repetition | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150932 | 497 | 3 | Clarification on PUCCH Format 3 Resource Derivation for TDD UL/DL Configuration 5 | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 506 | - | Clarification on the PRACH power in subframe i2-1 for PCM2 | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 507 | - | Clarification on the MTA operation in PCM1 | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 512 | - | Correction of higher layer parameter names in dual connectivity | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150935 | 513 | 1 | Correction on UE procedure of determining subframe pool for PSCCH and PSSCH in ProSe | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150935 | 514 | 1 | Correction on UE procedure of transmitting PSCCH in ProSe | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 515 | 1 | Correction on UL Power Control for Synchronous Dual Connectivity | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 516 | 1 | Correction on UL Power Control for Asynchronous Dual Connectivity | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150937 | 517 | - | Correction to Rel-12 UE category signal name | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150936 | 520 | - | Corrections on eIMTA RRC parameter naming | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150933 | 521 | - | Correction on Closed Loop Antenna Selection for Dual Connectivity | 12.5.0 | 12.6.0 |
| 15/06/15 | RP-68 | RP-150935 | 523 | - | Alignment of ProSe parameter names | 12.5.0 | 12.6.0 |
| 14/09/15 | RP-69 | RP-151470 | 525 | - | UE processing time relaxation on Type 2 Power Headroom Reporting | 12.6.0 | 12.7.0 |
| 14/09/15 | RP-69 | RP-151468 | 527 | - | Correction of ProSe parameters | 12.6.0 | 12.7.0 |
| 14/09/15 | RP-69 | RP-151471 | 528 | 2 | Clarification on power control for PCM2 | 12.6.0 | 12.7.0 |
| 07/12/15 | RP-70 | RP-152034 | 530 | 1 | Clarification of PUCCH resource allocation related to EPDCCH SCells | 12.7.0 | 12.8.0 |
| 07/12/15 | RP-70 | RP-152037 | 531 | - | Clarification on the parameter notations for eIMTA | 12.7.0 | 12.8.0 |
| 07/12/15 | RP-70 | RP-152037 | 534 | - | Correction on aperiodic CSI transmission without UL-SCH according to table 7.2.1-1C | 12.7.0 | 12.8.0 |
| 07/12/15 | RP-70 | RP-152038 | 535 | 1 | Introduction of new maximum TBS for TM9/10 | 12.7.0 | 12.8.0 |
| 07/12/15 | RP-70 | RP-152034 | 542 | - | Clarification of PHICH resource assignment related to EPDCCH scheduled PUSCH | 12.7.0 | 12.8.0 |
| 07/12/15 | RP-70 | RP-152036 | 543 | 1 | Modify max TA for dual connectivity | 12.7.0 | 12.8.0 |

| Change history | | | | | | | |
|----------------|-------------|-----------|------|-----|-----|---|-------------|
| Date | Meeting | TDoc | CR | Rev | Cat | Subject/Comment | New version |
| 2016-03 | RAN#71 | RP-160363 | 0583 | - | F | Clarification on T_threshold in dual connectivity | 12.9.0 |
| 2016-03 | Post RAN#71 | | | | | MCC update to show correct version of the spec in the headers of all subparts and get all of them aligned with coversheet | 12.9.1 |
| 2016-06 | RAN#72 | RP-161068 | 0612 | | F | Correction on RRC parameter for configuring new TBSs | 12.10.0 |

History

| Document history | | |
|-------------------------|----------------|-------------|
| V12.3.0 | October 2014 | Publication |
| V12.4.0 | February 2015 | Publication |
| V12.5.0 | April 2015 | Publication |
| V12.6.0 | September 2015 | Publication |
| V12.7.0 | October 2015 | Publication |
| V12.8.0 | May 2016 | Publication |
| V12.9.1 | May 2016 | Publication |
| V12.10.0 | August 2016 | Publication |