

# ETSI TS 136 306 V10.2.0 (2011-06)

---

*Technical Specification*

**LTE;  
Evolved Universal Terrestrial Radio Access (E-UTRA);  
User Equipment (UE) radio access capabilities  
(3GPP TS 36.306 version 10.2.0 Release 10)**

---



---

Reference

RTS/TSGR-0236306va20

---

Keywords

LTE

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	6
1 Scope .....	7
2 References .....	7
3 Definitions, symbols and abbreviations .....	7
3.1 Definitions .....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 UE radio access capability parameters.....	8
4.1 ue-Category .....	8
4.2 Parameters set by the field <i>ue-Category</i> .....	10
4.2.1 Transport channel parameters in downlink.....	10
4.2.1.1 Maximum number of DL-SCH transport block bits received within a TTI.....	10
4.2.1.2 Maximum number of bits of a DL-SCH transport block received within a TTI.....	10
4.2.1.3 Total number of DL-SCH soft channel bits .....	10
4.2.1.4 Maximum number of bits of a MCH transport block received within a TTI .....	10
4.2.2 Transport channel parameters in uplink.....	10
4.2.2.1 Maximum number of bits of an UL-SCH transport block transmitted within a TTI.....	10
4.2.2.2 Maximum number of UL-SCH transport block bits transmitted within a TTI.....	10
4.2.3 Physical channel parameters in downlink (DL).....	11
4.2.3.1 Maximum number of supported layers for spatial multiplexing in DL.....	11
4.2.4 Physical channel parameters in uplink (UL).....	11
4.2.4.1 Support for 64QAM in UL.....	11
4.2.5 Total layer 2 buffer size .....	11
4.3 Parameters independent of the field <i>ue-Category</i> .....	11
4.3.1 PDCP Parameters.....	11
4.3.1.1 supportedROHC-Profiles .....	11
4.3.1.2 maxNumberROHC-ContextSessions .....	12
4.3.2 RLC parameters .....	12
4.3.2.1 Void.....	12
4.3.3 Void .....	12
4.3.4 Physical layer parameters .....	12
4.3.4.1 ue-TxAntennaSelectionSupported .....	12
4.3.4.2 ue-SpecificRefSigsSupported.....	12
4.3.4.3 Void.....	12
4.3.4.4 enhancedDualLayerFDD.....	12
4.3.4.5 enhancedDualLayerTDD .....	12
4.3.4.6 supportedMIMO-CapabilityUL-r10.....	12
4.3.4.7 supportedMIMO-CapabilityDL-r10.....	12
4.3.4.8 two-AntennaPortsForPUCCH-r10 .....	12
4.3.4.9 tm9-With-8Tx-FDD-r10 .....	12
4.3.4.10 pmi-Disabling-r10.....	13
4.3.4.11 crossCarrierScheduling-r10.....	13
4.3.4.12 simultaneousPUCCH-PUSCH-r10.....	13
4.3.4.13 multiClusterPUSCH-WithinCC-r10.....	13
4.3.4.13 nonContiguousUL-RA-WithinCC-Info-r10.....	13
4.3.5 RF parameters .....	13
4.3.5.1 supportedBandListEUTRA .....	13
4.3.5.2 supportedBandCombination.....	13
4.3.6 Measurement parameters .....	14
4.3.6.1 interFreqNeedForGaps and interRAT-NeedForGaps.....	14
4.3.7 Inter-RAT parameters .....	14

4.3.7.1	Support of UTRA FDD .....	14
4.3.7.2	supportedBandListUTRA-FDD .....	14
4.3.7.3	Support of UTRA TDD 1.28 Mcps .....	14
4.3.7.4	supportedBandListUTRA-TDD128 .....	14
4.3.7.5	Support of UTRA TDD 3.84 Mcps .....	14
4.3.7.6	supportedBandListUTRA-TDD384 .....	14
4.3.7.7	Support of UTRA TDD 7.68 Mcps .....	14
4.3.7.8	supportedBandListUTRA-TDD768 .....	15
4.3.7.9	Support of GERAN .....	15
4.3.7.10	supportedBandListGERAN .....	15
4.3.7.11	interRAT-PS-HO-ToGERAN .....	15
4.3.7.12	Support of HRPD .....	15
4.3.7.13	supportedBandListHRPD .....	15
4.3.7.14	tx-ConfigHRPD .....	15
4.3.7.15	rx-ConfigHRPD .....	15
4.3.7.16	Support of 1xRTT .....	15
4.3.7.17	supportedBandList1XRTT .....	15
4.3.7.18	tx-Config1XRTT .....	15
4.3.7.19	rx-Config1XRTT .....	15
4.3.7.20	e-CSFB-1XRTT .....	16
4.3.7.21	e-CSFB-ConcPS-Mob1XRTT .....	16
4.3.7.22	e-RedirectionUTRA .....	16
4.3.7.23	e-RedirectionGERAN .....	16
4.3.7.24	<i>dtm</i> .....	16
4.3.7.25	e-CSFB-dual-1XRTT .....	16
4.3.7.26	e-RedirectionUTRA-TDD .....	16
4.3.8	General parameters .....	16
4.3.8.1	accessStratumRelease .....	16
4.3.8.2	deviceType .....	16
4.3.9	Void .....	16
4.3.10	CSG Proximity Indication parameters .....	16
4.3.10.1	intraFreqProximityIndication .....	16
4.3.10.2	interFreqProximityIndication .....	17
4.3.10.3	utran-ProximityIndication .....	17
4.3.11	Neighbour cell SI acquisition parameters .....	17
4.3.11.1	intraFreqSI-AcquisitionForHO .....	17
4.3.11.2	interFreqSI-AcquisitionForHO .....	17
4.3.11.3	utran-SI-AcquisitionForHO .....	17
4.3.12	SON parameters .....	17
4.3.12.1	rach-Report .....	17
4.3.13	UE-based network performance measurement parameters .....	17
4.3.13.1	loggedMeasurementsIdle .....	17
4.3.13.2	standaloneGNSS-Location .....	17
5	Void .....	18
6	Optional features without UE radio access capability parameters .....	18
6.1	CSG features .....	18
6.2	PWS features .....	18
6.2.1	ETWS .....	18
6.2.2	CMAS .....	18
6.3	MBMS features .....	18
6.4	SON Features .....	18
6.5	Positioning features .....	18
6.5.1	OTDOA inter-freq RSTD measurement indication .....	18
7	Conditionally Mandatory features .....	18
7.1	Access control features .....	18
7.1.1	SSAC .....	18
7.1.2	CSFB Access Barring Control .....	19
7.2	Emergency call features .....	19
7.2.1	IMS emergency call .....	19
7.3	MAC features .....	19

7.3.1 SR mask ..... 19

7.3.2 Power Management Indicator in PHR ..... 19

7.4 Inter-RAT Mobility features..... 19

7.4.1 High Priority CSFB redirection ..... 19

7.5 Delay Tolerant Access Features ..... 19

7.5.1 extendedWaitTime..... 19

**Annex A (informative): Guideline on maximum number of DL PDCP SDUs per TTI.....20**

**Annex B (informative): Change history .....21**

History .....22

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document defines the E-UTRA UE Radio Access Capability Parameters.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.323: "Evolved Universal Terrestrial Radio Access (E-UTRA) Packet Data Convergence Protocol (PDCP) specification".
- [3] 3GPP TS 36.322: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Link Control (RLC) specification".
- [4] 3GPP TS 36.321: "Evolved Universal Terrestrial Radio Access (E-UTRA) Medium Access Control (MAC) specification".
- [5] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA) Radio Resource Control (RRC) specification".
- [6] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA) radio transmission and reception".
- [7] IETF RFC 4995: "The RObust Header Compression (ROHC) Framework".
- [8] IETF RFC 4996: "RObust Header Compression (ROHC): A Profile for TCP/IP (ROHC-TCP)".
- [9] IETF RFC 3095: "RObust Header Compression (RoHC): Framework and four profiles: RTP, UDP, ESP and uncompressed".
- [10] IETF RFC 3843: "RObust Header Compression (RoHC): A Compression Profile for IP".
- [11] IETF RFC 4815: "RObust Header Compression (ROHC): Corrections and Clarifications to RFC 3095".
- [12] IETF RFC 5225: "RObust Header Compression (ROHC) Version 2: Profiles for RTP, UDP, IP, ESP and UDP Lite".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

*<defined term>*: *<definition>*.



## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

<symbol>            <Explanation>

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

1xRTT	CDMA2000 1x Radio Transmission Technology
BCCH	Broadcast Control Channel
CSG	Closed Subscriber Group
DL-SCH	Downlink Shared Channel
E-UTRA	Evolved Universal Terrestrial Radio Access
E-UTRAN	Evolved Universal Terrestrial Radio Access Network
FDD	Frequency Division Duplex
GERAN	GSM/EDGE Radio Access Network
HARQ	Hybrid Automatic Repeat Request
HRPD	High Rate Packet Data
MAC	Medium Access Control
PDCP	Packet Data Convergence Protocol
PHR	Power Headroom Reporting
RACH	Random Access CHannel
RAT	Radio Access Technology
RLC	Radio Link Control
ROHC	RObust Header Compression
RRC	Radio Resource Control
SI	System Information
SON	Self Organizing Networks
SSAC	Service Specific Access Control
TDD	Time Division Duplex
TTI	Transmission Time Interval
UE	User Equipment
UL-SCH	Uplink Shared Channel
UMTS	Universal Mobile Telecommunications System
UTRA	UMTS Terrestrial Radio Access

---

## 4 UE radio access capability parameters

The following subclauses define the UE radio access capability parameters and minimum capabilities for MBMS capable UE. Only parameters for which there is the possibility for UEs to signal different values are considered as UE radio access capability parameters. Therefore, mandatory capabilities that are the same for all UEs are not listed here. Also capabilities which are optional or conditionally mandatory for UEs to implement but do not have UE radio access capability parameter are listed in this specification.

E-UTRAN needs to respect the signalled UE radio access capability parameters when configuring the UE and when scheduling the UE.

All parameters shown in italics are signalled and correspond to a field defined in TS 36.331 [5].

### 4.1 ue-Category

The field *ue-Category* defines a combined uplink and downlink capability. The parameters set by the UE Category are defined in subclause 4.2. Tables 4.1-1 and 4.1-2 define the downlink and, respectively, uplink physical layer parameter values for each UE Category. A UE indicating category 6 or 7 shall also indicate category 4. A UE indicating category

8 shall also indicate category 5. Table 4.1-4 defines the minimum capability for the maximum number of bits of a MCH transport block received within a TTI for an MBMS capable UE.

**Table 4.1-1: Downlink physical layer parameter values set by the field *ue-Category***

UE Category	Maximum number of DL-SCH transport block bits received within a TTI	Maximum number of bits of a DL-SCH transport block received within a TTI	Total number of soft channel bits	Maximum number of supported layers for spatial multiplexing in DL
Category 1	10296	10296	250368	1
Category 2	51024	51024	1237248	2
Category 3	102048	75376	1237248	2
Category 4	150752	75376	1827072	2
Category 5	299552	149776	3667200	4
Category 6	301504	149776 (4 layers) 75376 (2 layers)	3654144	2 or 4
Category 7	301504	149776 (4 layers) 75376 (2 layers)	3654144	2 or 4
Category 8	2998560	299856	35982720	8

**Table 4.1-2: Uplink physical layer parameter values set by the field *ue-Category***

UE Category	Maximum number of UL-SCH transport block bits transmitted within a TTI	Maximum number of bits of an UL-SCH transport block transmitted within a TTI	Support for 64QAM in UL
Category 1	5160	5160	No
Category 2	25456	25456	No
Category 3	51024	51024	No
Category 4	51024	51024	No
Category 5	75376	75376	Yes
Category 6	51024	51024	No
Category 7	102048	51024	No
Category 8	1497760	149776	Yes

**Table 4.1-3: Total layer 2 buffer sizes set by the field *ue-Category***

UE Category	Total layer 2 buffer size [bytes]
Category 1	150 000
Category 2	700 000
Category 3	1 400 000
Category 4	1 900 000
Category 5	3 500 000
Category 6	3 300 000
Category 7	3 800 000
Category 8	42 200 000

**Table 4.1-4: Maximum number of bits of a MCH transport block received within a TTI set by the field *ue-Category* for an MBMS capable UE**

UE Category	Maximum number of bits of a MCH transport block received within a TTI
Category 1	10296
Category 2	51024
Category 3	75376
Category 4	75376
Category 5	75376
Category 6	(75376 TBD)
Category 7	(75376 TBD)
Category 8	(75376 TBD)

## 4.2 Parameters set by the field *ue-Category*

### 4.2.1 Transport channel parameters in downlink

#### 4.2.1.1 Maximum number of DL-SCH transport block bits received within a TTI

Defines the maximum number of DL-SCH transport blocks bits that the UE is capable of receiving within a DL-SCH TTI.

This number does not include the bits of a DL-SCH transport block carrying BCCH in the same subframe.

#### 4.2.1.2 Maximum number of bits of a DL-SCH transport block received within a TTI

Defines the maximum number of DL-SCH transport block bits that the UE is capable of receiving in a single transport block within a DL-SCH TTI.

#### 4.2.1.3 Total number of DL-SCH soft channel bits

Defines the total number of soft channel bits available for HARQ processing.

#### 4.2.1.4 Maximum number of bits of a MCH transport block received within a TTI

Defines the maximum number of MCH transport block bits that the UE is capable of receiving within a MCH TTI.

### 4.2.2 Transport channel parameters in uplink

#### 4.2.2.1 Maximum number of bits of an UL-SCH transport block transmitted within a TTI

Defines the maximum number of UL-SCH transport block bits that the UE is capable of transmitting in a single transport block within an UL-SCH TTI.

#### 4.2.2.2 Maximum number of UL-SCH transport block bits transmitted within a TTI

Defines the maximum number of UL-SCH transport blocks bits that the UE is capable of transmitting within an UL-SCH TTI.

## 4.2.3 Physical channel parameters in downlink (DL)

### 4.2.3.1 Maximum number of supported layers for spatial multiplexing in DL

This field defines the maximum number of supported layers for spatial multiplexing per UE. The UE shall support the number of layers according to its Rel-8/9 category (Cat. 1-5) in all non-CA band combinations. Further requirements on the number of supported layers for spatial multiplexing are provided in section 4.3.5.2.

For each band and band combination specified in *supportedBandCombination*, the UE provides the corresponding MIMO capability.

## 4.2.4 Physical channel parameters in uplink (UL)

### 4.2.4.1 Support for 64QAM in UL

Defines if 64QAM is supported in UL.

## 4.2.5 Total layer 2 buffer size

This parameter defines the total layer 2 buffer size. The total layer 2 buffer size is defined as the sum of the number of bytes that the UE is capable of storing in the RLC transmission windows and RLC reception and reordering windows for all radio bearers.

## 4.3 Parameters independent of the field *ue-Category*

### 4.3.1 PDCP Parameters

#### 4.3.1.1 supportedROHC-Profiles

This field defines which ROHC profiles from the list below are supported by the UE.

- 0x0000 ROHC uncompressed (RFC 4995)
- 0x0001 ROHC RTP (RFC 3095, RFC 4815)
- 0x0002 ROHC UDP (RFC 3095, RFC 4815)
- 0x0003 ROHC ESP (RFC 3095, RFC 4815)
- 0x0004 ROHC IP (RFC 3843, RFC 4815)
- 0x0006 ROHC TCP (RFC 4996)
- 0x0101 ROHCv2 RTP (RFC 5225)
- 0x0102 ROHCv2 UDP (RFC 5225)
- 0x0103 ROHCv2 ESP (RFC 5225)
- 0x0104 ROHCv2 IP (RFC 5225)

A UE that supports one or more of the listed ROHC profiles shall support ROHC profile 0x0000 ROHC uncompressed (RFC 4995).

'IMS capable UEs supporting voice' shall support ROHC profiles 0x0000, 0x0001, 0x0002 and be able to compress and decompress headers of PDCP SDUs at a PDCP SDU rate corresponding to supported IMS voice codecs.

#### 4.3.1.2 maxNumberROHC-ContextSessions

This field defines the maximum number of header compression context sessions supported by the UE, excluding context sessions that leave all headers uncompressed.

### 4.3.2 RLC parameters

#### 4.3.2.1 Void

#### 4.3.3 Void

### 4.3.4 Physical layer parameters

#### 4.3.4.1 ue-TxAntennaSelectionSupported

This field defines whether the UE supports transmit antenna selection.

#### 4.3.4.2 ue-SpecificRefSigsSupported

This field defines whether the UE supports PDSCH transmission mode 7 for FDD.

#### 4.3.4.3 Void

#### 4.3.4.4 enhancedDualLayerFDD

This field defines whether the UE supports enhanced dual layer (PDSCH transmission mode 8) for FDD.

#### 4.3.4.5 enhancedDualLayerTDD

This field defines whether the UE supports enhanced dual layer (PDSCH transmission mode 8) for TDD.

NOTE: Enhanced dual layer should be supported by Rel-9 UEs supporting TDD.

#### 4.3.4.6 supportedMIMO-CapabilityUL-r10

This field defines the number of spatial multiplexing layers in the uplink direction in a certain supportedBandCombination supported by the UE.

#### 4.3.4.7 supportedMIMO-CapabilityDL-r10

This field defines the number of spatial multiplexing layers in the downlink direction in a certain supportedBandCombination supported by the UE.

The support for more layers in *supportedMIMO-CapabilityDL* than given by the 'maximum number of supported layers for spatial multiplexing in DL' derived from the *ue-Category* in the *UE-EUTRA-Capability* IE is only applicable to transmission mode 9.

#### 4.3.4.8 two-AntennaPortsForPUCCH-r10

This field defines whether the UE supports transmit diversity for PUCCH formats 1/1a/1b/2/2a/2b, and if the UE supports PUCCH format 3, transmit diversity for PUCCH format 3.

#### 4.3.4.9 tm9-With-8Tx-FDD-r10

This field defines whether the UE supports PDSCH transmission mode 9 with 8 CSI reference signal ports for FDD.

#### 4.3.4.10 pmi-Disabling-r10

This field defines whether the UE supports PMI disabling.

#### 4.3.4.11 crossCarrierScheduling-r10

This field defines whether the UE supports cross carrier scheduling operation for carrier aggregation, including (if the UE supports carrier aggregation in UL) the use of PCell as the pathloss reference for a SCell when *pathlossReference-r10* within *UplinkPowerControlDedicatedSCell-r10* is configured as 'pCell'.

NOTE: Regardless of whether the UE supports cross carrier scheduling operation or not, it is mandatory for a UE supporting carrier aggregation in UL to support the configuration where *pathlossReference-r10* within *UplinkPowerControlDedicatedSCell-r10* is set to 'sCell'.

#### 4.3.4.12 simultaneousPUCCH-PUSCH-r10

This field defines whether the UE baseband supports simultaneous transmission of PUCCH and PUSCH, and is band agnostic. If the UE indicates support of baseband capability for simultaneous transmission of PUCCH and PUSCH using this field, and if the UE indicates support of RF capability for non-contiguous UL resource allocation within a component carrier for a particular E-UTRA radio frequency band, then the UE supports simultaneous transmission of PUCCH and PUSCH within each component carrier of the band. If the UE indicates support of baseband capability for simultaneous transmission of PUCCH and PUSCH using this field, and if the UE indicates support of carrier aggregation in UL, then the UE supports simultaneous transmission of PUCCH and PUSCH across any UL component carriers which the UE can aggregate.

#### 4.3.4.13 multiClusterPUSCH-WithinCC-r10

This field defines whether the UE baseband supports multi-cluster PUSCH transmission within a component carrier (i.e. PUSCH resource allocation type 1), and is band agnostic. If the UE indicates support of baseband capability for multi-cluster PUSCH transmission within a component carrier using this field, and if the UE indicates support of RF capability for non-contiguous UL resource allocation within a component carrier for a particular E-UTRA radio frequency band, then the UE supports multi-cluster PUSCH transmission within each component carrier of the band.

NOTE: If the UE indicates support of carrier aggregation in UL, then the UE supports PUSCH transmissions over non-contiguous resource blocks across any UL component carriers which the UE can aggregate, regardless of whether or not the UE indicates support of baseband capability for multi-cluster PUSCH transmission within a component carrier using this field..

#### 4.3.4.13 nonContiguousUL-RA-WithinCC-Info-r10

This field defines whether the UE RF supports non-contiguous UL resource allocations within a component carrier, and is signalled per E-UTRA radio frequency band which the UE supports.

### 4.3.5 RF parameters

#### 4.3.5.1 supportedBandListEUTRA

This field defines which E-UTRA radio frequency bands [6] are supported by the UE. For each band, support for either only half duplex operation, or full duplex operation is indicated. For TDD, the half duplex indication is not applicable.

#### 4.3.5.2 supportedBandCombination

This field defines the carrier aggregation and MIMO capabilities supported by the UE for configurations with inter-band, intra-band non-contiguous, intra-band contiguous carrier aggregation and without carrier aggregation. For each band in a band combination the UE provides for uplink and downlink the supported CA bandwidth classes and the corresponding MIMO capabilities. A MIMO capability applies to all carriers of a band in a band combination.

In all non-CA band combinations the UE shall indicate a bandwidth class supporting the maximum channel bandwidth defined for the band.

In all non-CA band combinations the UE shall indicate at least the number of layers for spatial multiplexing according to the UE's Rel-8/9 category (Cat. 1-5). If the UE provides a Rel-10 category (Cat. 6-8) it shall indicate at least the number of layers according to that category for at least one band combination. In all other band combinations a UE indicating a category between 2 and 8 shall indicate support for at least 2 layers for spatial multiplexing for all bands. The indicated number of layers for spatial multiplexing may exceed the number of layers required according to the category indicated by the UE. The carrier aggregation and MIMO capabilities indicated for at least one band combination shall meet the processing requirements defined by the physical layer parameter values in the UE category (i.e., maximum number of DL-SCH/UL-SCH transport block bits received/transmitted within a TTI, maximum number of bits of a DL-SCH/UL-SCH transport block received/transmitted within a TTI, and total number of soft channel bits for downlink).

## 4.3.6 Measurement parameters

### 4.3.6.1 interFreqNeedForGaps and interRAT-NeedForGaps

These fields define for each supported E-UTRA band whether measurement gaps are required to perform measurements on each other supported E-UTRA radio frequency band and on each supported RAT/band combination. A UE also indicates for each band combination as in the *supportedBandCombination* whether measurement gaps are required to perform measurements on each supported E-UTRA radio frequency band and on each supported RAT/band combination.

## 4.3.7 Inter-RAT parameters

### 4.3.7.1 Support of UTRA FDD

This parameter defines whether the UE supports UTRA FDD.

A UE that supports UTRAN FDD shall support inter-RAT PS handover to UTRAN.

### 4.3.7.2 supportedBandListUTRA-FDD

Only applicable if the UE supports UTRA FDD. This field defines which UTRA FDD radio frequency bands are supported by the UE.

### 4.3.7.3 Support of UTRA TDD 1.28 Mcps

This parameter defines whether the UE supports UTRA TDD 1.28 Mcps.

A UE that supports UTRAN TDD 1.28 Mcps shall support inter-RAT PS handover to UTRAN.

### 4.3.7.4 supportedBandListUTRA-TDD128

Only applicable if the UE supports UTRA TDD 1.28 Mcps. This field defines which UTRA TDD 1.28 Mcps radio frequency bands are supported by the UE.

### 4.3.7.5 Support of UTRA TDD 3.84 Mcps

This parameter defines whether the UE supports UTRA TDD 3.84 Mcps.

A UE that supports UTRAN TDD 3.84 Mcps shall support inter-RAT PS handover to UTRAN.

### 4.3.7.6 supportedBandListUTRA-TDD384

Only applicable if the UE supports UTRA TDD 3.84 Mcps. This field defines which UTRA TDD 3.84 Mcps radio frequency bands are supported by the UE.

### 4.3.7.7 Support of UTRA TDD 7.68 Mcps

This parameter defines whether the UE supports UTRA TDD 7.68 Mcps.

A UE that supports UTRAN TDD 7.68 Mcps shall support inter-RAT PS handover to UTRAN.

#### 4.3.7.8 supportedBandListUTRA-TDD768

Only applicable if the UE supports UTRA TDD 7.68 Mcps. This field defines which UTRA TDD 7.68 Mcps radio frequency bands are supported by the UE.

#### 4.3.7.9 Support of GERAN

This parameter defines whether the UE supports GERAN.

#### 4.3.7.10 supportedBandListGERAN

Only applicable if the UE supports GERAN. This field defines which GERAN radio frequency bands are supported by the UE.

#### 4.3.7.11 interRAT-PS-HO-ToGERAN

Only applicable if the UE supports GERAN. This field defines whether the UE supports inter-RAT PS handover to GERAN.

#### 4.3.7.12 Support of HRPD

This parameter defines whether the UE supports HRPD.

#### 4.3.7.13 supportedBandListHRPD

Only applicable if the UE supports HRPD. This field defines which HRPD radio frequency bands are supported by the UE.

#### 4.3.7.14 tx-ConfigHRPD

Only applicable if the UE supports HRPD. This field defines whether the UE supports single or dual transmitter. With dual transmitter, UE can transmit simultaneously on both E-UTRAN and HRPD.

#### 4.3.7.15 rx-ConfigHRPD

Only applicable if the UE supports HRPD. This field defines whether the UE supports single or dual receiver. With dual receiver, UE can receive simultaneously on both E-UTRAN and HRPD.

#### 4.3.7.16 Support of 1xRTT

This parameter defines whether the UE supports 1xRTT.

#### 4.3.7.17 supportedBandList1XRTT

Only applicable if the UE supports 1xRTT. This field defines which 1xRTT radio frequency bands are supported by the UE.

#### 4.3.7.18 tx-Config1XRTT

Only applicable if the UE supports 1xRTT. This field defines whether the UE supports single or dual transmitter. With dual transmitter, UE can transmit simultaneously on both E-UTRAN and 1xRTT.

#### 4.3.7.19 rx-Config1XRTT

Only applicable if the UE supports 1xRTT. This field defines whether the UE supports single or dual receiver. With dual receiver, UE can receive simultaneously on both E-UTRAN and 1xRTT.



#### 4.3.7.20 e-CSFB-1XRTT

Only applicable if the UE supports CDMA2000 1xRTT. This field defines whether the UE supports enhanced 1xRTT CS fallback.

#### 4.3.7.21 e-CSFB-ConcPS-Mob1XRTT

Only applicable if the UE supports CDMA2000 1xRTT and CDMA2000 HRPD simultaneously. This field defines whether the UE supports concurrent enhanced CS fallback to CDMA2000 1xRTT and handover/redirection to CDMA2000 HRPD.

#### 4.3.7.22 e-RedirectionUTRA

This parameter defines whether the UE supports use of UTRA system information provided by *RRCConnectionRelease* upon redirection.

#### 4.3.7.23 e-RedirectionGERAN

This parameter defines whether the UE supports use of GERAN system information provided by *RRCConnectionRelease* upon redirection.

A UE that supports CS fallback to GERAN shall support e-Redirection to GERAN.

#### 4.3.7.24 *dtm*

This parameter defines whether the UE supports Dual Transfer Mode (DTM) in GERAN.

#### 4.3.7.25 e-CSFB-dual-1XRTT

Only applicable if the UE supports CDMA2000 1xRTT, dual transmitter (i.e. UE can transmit simultaneously on both E-UTRAN and 1xRTT) and dual receiver (i.e. UE can receive simultaneously on both E-UTRAN and 1xRTT). This field defines whether the UE supports dual receiver/transmitter enhanced 1xRTT CS fallback (dual Rx/Tx e1xCSFB).

#### 4.3.7.26 e-RedirectionUTRA-TDD

This parameter defines whether the UE supports redirection by using UTRA TDD system information for cells on multiple carrier frequencies provided by *RRCConnectionRelease*.

### 4.3.8 General parameters

#### 4.3.8.1 accessStratumRelease

This field defines the release of the E-UTRA layer 1, 2, and 3 specifications supported by the UE e.g. Rel-8, Rel-9, etc.

#### 4.3.8.2 deviceType

This field defines whether the device does not benefit from NW-based battery consumption optimisation.

#### 4.3.9 Void

### 4.3.10 CSG Proximity Indication parameters

#### 4.3.10.1 intraFreqProximityIndication

This parameter defines whether the UE supports proximity indication for intra-frequency E-UTRAN cells whose CSG Identities are in the UE's CSG Whitelist.

Conditions for setting this bit are FFS.

#### 4.3.10.2 interFreqProximityIndication

This parameter defines whether the UE supports proximity indication for inter-frequency E-UTRAN cells whose CSG Identities are in the UE's CSG Whitelist.

Conditions for setting this bit are FFS.

#### 4.3.10.3 utran-ProximityIndication

This parameter defines whether the UE supports proximity indication for UTRAN cells whose CSG IDs are in the UE's CSG Whitelist.

### 4.3.11 Neighbour cell SI acquisition parameters

#### 4.3.11.1 intraFreqSI-AcquisitionForHO

This parameter defines whether the UE supports, upon configuration of *si-RequestForHO* by the network, acquisition of relevant information from a neighbouring intra-frequency cell by reading the SI of the neighbouring cell using autonomous gaps and reporting the acquired information to the network as specified in [5].

Conditions for setting this bit are FFS.

#### 4.3.11.2 interFreqSI-AcquisitionForHO

This parameter defines whether the UE supports, upon configuration of *si-RequestForHO* by the network, acquisition of relevant information from a neighbouring inter-frequency cell by reading the SI of the neighbouring cell using autonomous gaps and reporting the acquired information to the network as specified in [5].

Conditions for setting this bit are FFS.

#### 4.3.11.3 utran-SI-AcquisitionForHO

This parameter defines whether the UE supports, upon configuration of *si-RequestForHO* by the network, acquisition of relevant information from a neighbouring UMTS cell by reading the SI of the neighbouring cell using autonomous gaps and reporting the acquired information to the network as specified in [5].

### 4.3.12 SON parameters

#### 4.3.12.1 rach-Report

This parameter defines whether the UE supports delivery of *rachReport* upon request from the network.

### 4.3.13 UE-based network performance measurement parameters

#### 4.3.13.1 loggedMeasurementsIdle

This parameter defines whether the UE supports logged measurements in RRC\_IDLE upon request from the network. A UE that supports logged measurements in RRC\_IDLE shall also support a minimum of 64kB memory for log storage.

#### 4.3.13.2 standaloneGNSS-Location

This parameter defines whether the UE is equipped with a standalone GNSS receiver that may be used to provide detailed location information in RRC measurement report and logged measurements in RRC\_IDLE.

---

## 5 Void

---

## 6 Optional features without UE radio access capability parameters

The following subclauses list the optional UE features not having UE radio access capability.

NOTE: This chapter does not yet contain complete analysis of all features of this release of specification.

### 6.1 CSG features

It is optional for UE to support some parts of CSG cell and hybrid cell reselection features as specified in [5, B.2].

### 6.2 PWS features

#### 6.2.1 ETWS

It is optional for UE to support ETWS reception as specified in [5].

#### 6.2.2 CMAS

It is optional for UE to support CMAS reception as specified in [5].

### 6.3 MBMS features

It is optional for UE to support MBMS procedures as specified in [5].

### 6.4 SON Features

### 6.5 Positioning features

#### 6.5.1 OTDOA inter-freq RSTD measurement indication

It is optional for UE to support delivery of *InterFreqRSTDMeasurementIndication* as specified in [5, 5.5.7].

---

## 7 Conditionally Mandatory features

### 7.1 Access control features

#### 7.1.1 SSAC

It is mandatory to support Service Specific Access Control as specified in [5, 5.3.3.10] for UEs which are IMS voice capable in LTE.

## 7.1.2 CSFB Access Barring Control

It is mandatory to support CSFB Access Barring Control as specified in [5, 5.3.3.2] for UEs which are supporting CSFB to UTRA or GERAN.

## 7.2 Emergency call features

### 7.2.1 IMS emergency call

It is mandatory to support IMS emergency call for UEs which are IMS voice capable in LTE.

## 7.3 MAC features

### 7.3.1 SR mask

It is mandatory to support configuration indicated by *logicalChannelSR-Mask* for UE which have set bit number 3 of *featureGroupIndicators* to '1' as specified in [5].

### 7.3.2 Power Management Indicator in PHR

Power management indicator in PHR is mandatory to support for UE applying additional power backoff due to power management (as allowed by P-MPR [6]).

## 7.4 Inter-RAT Mobility features

### 7.4.1 High Priority CSFB redirection

It is mandatory to support the *RRConnectionRelease* indicating '*cs-FallbackHighPriority*' for UEs which are supporting CSFB to UTRA as specified in [5].

## 7.5 Delay Tolerant Access Features

### 7.5.1 extendedWaitTime

It is mandatory to support the *RRConnectionRelease* with *extendedWaitTime* or *RRConnectionReject* with *extendedWaitTime* for UEs which do support Delay Tolerant Access as specified in [5].

---

## Annex A (informative): Guideline on maximum number of DL PDCP SDUs per TTI

In order to help the dimensioning of the UE design, values for the maximum number of DL PDCP SDUs per TTI from Table A-1 may be used.

Note: Due to the need for the network buffer data for efficient scheduling, values for Category 1 and 2 are same. It is not expected that category 1 UE has to sustain the same rate of PDCP SDUs per TTI as category 2 for prolonged period of time.

**Table A-1: Maximum values for DL PDCP SDUs per TTI**

<b>UE Category</b>	<b>Maximum number of PDCP SDUs per TTI</b>
Category 1	10
Category 2	10
Category 3	20
Category 4	30
Category 5	50

## Annex B (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	
11/2007	RP-38	RP-070916			Presented for approval at TSG RAN-38	0.2.0	1.0.0	
12/2007		-			Approved at TSG RAN-38 and placed under change control	1.0.0	8.0.0	
03/2008	RP-39	RP-080194	0001	1	CR to 36.306 with Update to E-UTRA UE capabilities	8.0.0	8.1.0	
05/2008	RP-40	RP-080409	0002	1	Update to E-UTRA UE capabilities: CR 0002r1 to 36.306 with status after RAN2 #62	8.1.0	8.2.0	
03/2009	RP-43	RP-090126	0007	-	CR to remove the sections on MBMS	8.2.0	8.3.0	
	RP-43	RP-090126	0008	-	Final values for L2 buffer sizes	8.2.0	8.3.0	
	RP-43	RP-090126	0009	-	Various Corrections	8.2.0	8.3.0	
	RP-43	RP-090126	0010	-	CR to update uplink transmit diversity (UE transmit antenna selection)	8.2.0	8.3.0	
	RP-43	RP-090126	0011	-	Downlink PDCP SDU limitation	8.2.0	8.3.0	
	RP-43	RP-090126	0014	-	Thoughts on UE capability for RoHC	8.2.0	8.3.0	
	RP-43	RP-090126	0015	1	Capturing USIMless UE to stage 3	8.2.0	8.3.0	
06/2009	RP-44	RP-090511	0016	2	Support of inter-RAT PS handover to GERAN Editor Note Removal	8.3.0	8.4.0	
	RP-44	RP-090511	0017	1	Clarification of Half Duplex in TDD	8.3.0	8.4.0	
	RP-44	RP-090511	0018	-	Correcting the maximum number of bits received during one TTI	8.3.0	8.4.0	
	RP-44	RP-090511	0019	-	Clarification of field names used in TS 36.331	8.3.0	8.4.0	
	RP-44	RP-090511	0021	-	Clarification on disabling E-UTRA capabilities with a USIM	8.3.0	8.4.0	
09/2009	RP-45	RP-090906	0023	-	Unit for "Total layer 2 buffer size"	8.4.0	8.5.0	
12/2009	RP-46	-	-	-	Upgrade to the Release 9 - no technical change	8.5.0	9.0.0	
03/2010	RP-47	RP-100308	0024	1	CR to 36.306 on Optionality of Rel-9 UE features	9.0.0	9.1.0	
	RP-47	RP-100308	0025	-	Introduction of power-limited device indication in UE capability.	9.0.0	9.1.0	
	RP-47	RP-100308	0026	-	UE capability for enhanced 1xRTT CS fallback	9.0.0	9.1.0	
	RP-47	RP-100285	0028	1	Bounds to RoHC requirements for IMS capable UEs supporting voice	9.0.0	9.1.0	
	RP-47	RP-100309	0029	1	CR to 36.306 on Redirection enhancements to UTRAN	9.0.0	9.1.0	
	RP-47	RP-100188	0030	1	Redirection enhancements to GERAN	9.0.0	9.1.0	
06/2010	RP-48	RP-100556	0031	1	Clarification regarding / alignment of REL-9 UE capabilities	9.1.0	9.2.0	
	RP-48	RP-100531	0033	-	Correction on the definition of ue-SpecificRefSigsSupported	9.1.0	9.2.0	
09/2010	RP-49	RP-100853	0035	-	Clarification of MBMS UE capability	9.2.0	9.3.0	
12/2010	RP-50	RP-101268	0037	-	Inclusion of new UE categories in Rel-10	9.3.0	10.0.0	
03/2011	RP-51	RP-110290	0038	-	Description of carrier aggregation and MIMO capabilities	10.0.0	10.1.0	
	RP-51	RP-110290	0039	-	L2 buffer sizes for Rel-10 categories	10.0.0	10.1.0	
	RP-51	RP-110280	0041	-	CR to 36.306 adding UE capability indicator for dual Rx/Tx e1xCsFB	10.0.0	10.1.0	
	RP-51	RP-110288	0042	1	UE UL&DL MIMO Capabilities	10.0.0	10.1.0	
	RP-51	RP-110282	0043	-	Counter proposal to R2-110795 on UE capabilities for MDT	10.0.0	10.1.0	
06/2011	RP-52	RP-110828	0048	-	Clarification of optionality of UE features without capability	10.1.0	10.2.0	
	RP-52	RP-110830	0051	-	Options for CSFB to GSM	10.1.0	10.2.0	
	RP-52	RP-110840	0056	1	CR to 36.306 on UE capabilities for Rel-10 LTE features	10.1.0	10.2.0	
	RP-52	RP-110701	0058	2	CA and MIMO Capabilities in LTE Rel-10	10.1.0	10.2.0	
	RP-52	RP-110839	0062	-	Introduction of UE capability for enhanced redirection to UTRA TDD	10.1.0	10.2.0	
	RP-52	RP-110834	0063	2	Clarification of "supportedMIMO-CapabilityDL"	10.1.0	10.2.0	
	RP-52	RP-110627	0064	-	Correction of "total number of soft channel bits" for category 6 and 7	10.1.0	10.2.0	

---

## History

<b>Document history</b>		
V10.0.0	January 2011	Publication
V10.1.0	April 2011	Publication
V10.2.0	June 2011	Publication