

ETSI TS 137 571-5 V13.2.0 (2017-04)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Universal Terrestrial Radio Access (UTRA) and
Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC);
User Equipment (UE) conformance specification
for UE positioning;
Part 5: Test scenarios and assistance data
(3GPP TS 37.571-5 version 13.2.0 Release 13)**



Reference

RTS/TSGR-0537571-5vd20

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	6
Introduction	6
1 Scope	7
2 References	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Symbols.....	8
3.3 Abbreviations	8
4 General	9
4.1 GPS and GNSS orbital model information, assistance data and assistance data files	9
4.2 OTDOA assistance data	10
5 GPS information.....	10
5.1 GPS Scenario and Assistance data for Assisted GPS signalling tests	10
5.1.1 General.....	10
5.1.2 GPS Scenario	10
5.1.3 Assistance Data.....	10
5.1.3.1 Assistance Data Reference Time.....	11
5.1.3.2 Assistance Data Reference UE Position.....	11
5.1.3.3 Assistance Data Navigation Model.....	11
5.1.3.4 Assistance Data Ionospheric Model.....	12
5.1.3.5 Assistance Data Almanac.....	13
5.1.3.6 Assistance Data Acquisition Assistance.....	13
5.2 GPS Scenarios and Assistance Data for Assisted GPS Minimum Performance tests	14
5.2.1 General.....	14
5.2.1.1 Satellite constellations and assistance data for A-GPS minimum performance testing	14
5.2.1.2 GPS Scenarios for A-GPS minimum performance testing.....	15
5.2.1.2.1 GPS Scenario #1	15
5.2.1.2.2 GPS Scenario #2.....	15
5.2.1.2.3 GPS Scenario #3.....	15
5.2.1.2.4 UE Location for TTFF test cases.....	16
5.2.1.2.4.1 UE Location Offset.....	16
5.2.1.2.4.2 UE Altitude	16
5.2.1.2.5 Satellites to be simulated in each test case	16
5.2.2 Information elements required for normal UE based testing	17
5.2.3 Information elements required for UE based Sensitivity Fine Time Assistance test case	18
5.2.4 Information elements available for normal UE assisted testing.....	18
5.2.5 Information elements available for UE assisted Sensitivity Fine Time Assistance test case	19
5.2.6 Contents of Information elements for A-GPS Minimum performance testing	20
5.2.6.1 General	20
5.2.6.2 IE Random Offset Values	20
5.2.6.2.1 GPS TOW msec	21
5.2.6.2.2 UTRAN GPS timing of cell frames.....	21
5.2.6.3 Assistance Data Reference Time.....	21
5.2.6.4 Assistance Data Reference UE Position.....	23
5.2.6.5 Assistance Data Navigation Model.....	23
5.2.6.6 Assistance Data Ionospheric Model.....	24
5.2.6.7 Assistance Data Almanac.....	25
5.2.6.8 Assistance Data Acquisition Assistance.....	25
6 GNSS information.....	27

6.1	GNSS Scenarios and Assistance Data for Assisted GNSS signalling tests	27
6.1.1	General.....	27
6.1.2	GNSS Scenario	28
6.1.3	Assistance Data.....	29
6.1.3.1	Default Assistance Data for TS 37.571-2 subclauses 6.2.1 to 6.2.3.....	29
6.1.3.2	Assistance Data values for TS 37.571-2 subclauses 6.2.1 to 6.2.3.....	30
6.1.3.3	Default Assistance Data for TS 37.571-2 subclause 7	47
6.1.3.4	Assistance Data values for TS 37.571-2 subclause 7	47
6.2	GNSS Scenarios and Assistance Data for Assisted GNSS Minimum Performance tests.....	61
6.2.1	General.....	61
6.2.1.1	Satellite constellations and assistance data for A-GNSS minimum performance testing	62
6.2.1.2	GNSS Scenarios for A-GNSS minimum performance testing.....	62
6.2.1.2.1	GNSS Scenario #1	63
6.2.1.2.2	GNSS Scenario #2.....	65
6.2.1.2.3	GNSS Scenario #3.....	67
6.2.1.2.3.1	GNSS Scenario #3A	68
6.2.1.2.3.2	GNSS Scenario #3B.....	68
6.2.1.2.3.3	QZSS Scenario #1.....	68
6.2.1.2.3.4	WAAS Scenario.....	68
6.2.1.2.3.5	EGNOS Scenario	68
6.2.1.2.3.6	MSAS Scenario.....	68
6.2.1.2.3.7	GAGAN Scenario	69
6.2.1.2.4	GNSS Scenario #4.....	69
6.2.1.2.4.1	GNSS Scenario #4A	69
6.2.1.2.4.2	GNSS Scenario #4B.....	69
6.2.1.2.4.3	GNSS Scenario #4C.....	69
6.2.1.2.4.4	GNSS Scenario #4D	69
6.2.1.2.4.5	QZSS Scenario #2.....	69
6.2.1.2.4.6	WAAS Scenario.....	69
6.2.1.2.4.7	EGNOS Scenario	70
6.2.1.2.4.8	MSAS Scenario.....	70
6.2.1.2.4.9	GAGAN Scenario	70
6.2.1.2.5	GNSS Scenario #5.....	70
6.2.1.2.6	UE Location for TTFF test cases.....	72
6.2.1.2.6.1	UE Location Offset	72
6.2.1.2.6.2	UE Altitude	72
6.2.2	Information elements required for normal UE based testing for TS 37.571-1 subclause 6	72
6.2.3	Information elements required for UE based Sensitivity Fine Time Assistance test case for TS 37.571-1 subclause 6.....	74
6.2.4	Information elements available for normal UE assisted testing for TS 37.571-1 subclause 6.....	75
6.2.5	Information elements available for UE assisted Sensitivity Fine Time Assistance test case for TS 37.571-1 subclause 6.....	78
6.2.6	Information elements available for A-GNSS test cases in TS 37.571-1 subclause 7	79
6.2.7	Contents of Information elements for A-GNSS Minimum performance testing	82
6.2.7.1	General	82
6.2.7.2	IE Random Offset Values	82
6.2.7.2.1	GNSS TOW	82
6.2.7.2.2	GNSS/cellular time offset.....	82
6.2.7.3	Contents of Information elements for A-GNSS Minimum performance testing in TS 37.571-1 subclause 6	84
6.2.7.4	Contents of Information elements for A-GNSS Minimum performance testing in TS 37.571-1 subclause 7	108
7	OTDOA.....	130
7.1	OTDOA Assistance data for OTDOA signalling tests	130
7.1.1	General.....	130
7.2	OTDOA Assistance data for OTDOA measurement tests.....	130
7.2.1	General.....	130
7.2.2	OTDOA Assistance Data.....	130
7.3	OTDOA Assistance data for OTDOA measurement tests for Carrier Aggregation	138
7.3.1	General.....	138
7.3.2	OTDOA Assistance Data.....	139

8	MBS information.....	161
8.1.2	MBS Signalling Scenario.....	161
9	WLAN information.....	162
9.1	WLAN Scenario for WLAN signalling tests.....	162
9.1.1	WLAN Signalling Scenario.....	162
10	Bluetooth information.....	162
10.1	Bluetooth Scenario for Bluetooth signalling tests.....	162
10.1.1	Bluetooth Signalling Scenario.....	162
Annex A (normative): GPS data files.....		164
A.1	GPS data files for signalling tests.....	164
A.2	GPS data files for Minimum Performance tests.....	164
Annex B (normative): GNSS data files.....		165
B.1	GNSS data files for signalling tests.....	165
B.2	GNSS data files for Minimum Performance tests.....	165
Annex C (informative): Change history.....		166
History.....		170

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part 5 of a multi-part TS:

3GPP TS 37. 571-1: Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 1: Conformance test specification.

3GPP TS 37. 571-2: Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 2: Protocol conformance.

3GPP TS 37. 571-3: Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 3: Implementation Conformance Statement (ICS).

3GPP TS 37. 571-4: Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 4: Test suites.

3GPP TS 37. 571-5: Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 5: Test scenarios and assistance data.

1 Scope

The present document specifies the test scenarios and assistance data required for the conformance test for FDD or TDD mode of UTRA and E-UTRA for the User Equipment (UE) that supports one or more of the defined positioning methods. For UTRA these are Assisted Global Positioning System (A-GPS) and Assisted Global Navigation Satellite System (A-GNSS). For E-UTRA these are A-GNSS, Observed Time Difference of Arrival (OTDOA), Enhanced Cell ID (ECID), Wireless Local Area Network (WLAN), Metropolitan Beacon Systems (MBS) and Bluetooth.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document unless the context in which the reference is made suggests a different Release is relevant (information on the applicable release in a particular context can be found in e.g. test case title, description or applicability, message description or content).

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [3] Void
- [4] Void
- [5] Void
- [6] 3GPP TS 37.571-1: "Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 1: Terminal conformance".
- [7] 3GPP TS 37.571-2: "Universal Terrestrial Radio Access (UTRA) and Evolved UTRA (E-UTRA) and Evolved Packet Core (EPC); User Equipment (UE) conformance specification for UE positioning; Part 2: Protocol conformance".
- [8] 3GPP TS 36.355: "Evolved Universal Terrestrial Radio Access (E-UTRA); LTE Positioning Protocol (LPP)".
- [9] IS-GPS-200, Revision D, Navstar GPS Space Segment/Navigation User Interfaces, March 7th, 2006.
- [10] IS-GPS-705, Navstar GPS Space Segment/User Segment L5 Interfaces, September 22, 2005.
- [11] IS-GPS-800, Navstar GPS Space Segment/User Segment L1C Interfaces, September 4, 2008.
- [12] IS-QZSS, Quasi Zenith Satellite System Navigation Service Interface Specifications for QZSS, Ver.1.1, July 31, 2009.
- [13] Galileo OS Signal in Space ICD (OS SIS ICD), Issue 1.2, February 2014, European Union.
- [14] Global Navigation Satellite System GLONASS Interface Control Document, Version 5.1, 2008.
- [15] Specification for the Wide Area Augmentation System (WAAS), US Department of Transportation, Federal Aviation Administration, DTFA01-96-C-00025, 2001.

- [16] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol specification"
- [17] STANAG 4294: NATO STANAG 4294. Navstar Global Positioning System (GPS) System Characteristics.
- [18] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [19] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
- [20] 3GPP TS 36.508: "Common test environments for User Equipment (UE) conformance testing".
- [21] ATIS-0500027: "Recommendations for Establishing Wide Scale Indoor Location Performance", May 2015.
- [22] IEEE 802.11, Part 11: "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [23] Bluetooth Special Interest Group (SIG): "Bluetooth Core Specification v4.2", December 2014.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1], TS 36.101 [2], 3GPP TS 36.104 [18] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Horizontal Dilution Of Precision (HDOP): measure of position determination accuracy that is a function of the geometrical layout of the satellites used for the fix, relative to the receiver antenna

3.2 Symbols

For the purposes of the present document, the following symbols apply:

E1	Galileo E1 navigation signal with carrier frequency of 1575.420 MHz.
E5	Galileo E5 navigation signal with carrier frequency of 1191.795 MHz.
E6	Galileo E6 navigation signal with carrier frequency of 1278.750 MHz.
G1	GLONASS navigation signal in the L1 sub-bands with carrier frequencies $1602 \text{ MHz} \pm k \times 562.5 \text{ kHz}$.
G2	GLONASS navigation signal in the L2 sub-bands with carrier frequencies $1246 \text{ MHz} \pm k \times 437.5 \text{ kHz}$.
k	GLONASS channel number, $k = -7 \dots 13$.
L1 C/A	GPS or QZSS L1 navigation signal carrying the Coarse/Acquisition code with carrier frequency of 1575.420 MHz.
L1C	GPS or QZSS L1 Civil navigation signal with carrier frequency of 1575.420 MHz.
L2C	GPS or QZSS L2 Civil navigation signal with carrier frequency of 1227.600 MHz.
L5	GPS or QZSS L5 navigation signal with carrier frequency of 1176.450 MHz.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

A-Galileo	Assisted-Galileo
A-GANSS	Assisted- Galileo and Additional Navigation Satellite Systems
A-GLONASS	Assisted- GLObal'naya NAvigatsionnaya Sputnikovaya Sistema (English: Global Navigation Satellite System)
A-GNSS	Assisted Global Navigation Satellite System

A-GPS	Assisted - Global Positioning System
AP	Access Point
AWGN	Additive White Gaussian Noise
BDS	BeiDou Navigation Satellite System
C/A	Coarse/Acquisition
DUT	Device Under Test
ECEF	Earth Centred, Earth Fixed
ENB	Evolved Node B
E-UTRA	Evolved UMTS Terrestrial Radio Access
E-UTRAN	Evolved UMTS Terrestrial Radio Access Network
FDD	Frequency Division Duplex
FFS	For further study
GANSS	Galileo and Additional Navigation Satellite Systems
GEO	Geostationary Earth Orbit
GLONASS	GLObal'naya NAVigatsionnaya Sputnikovaya Sistema (English: Global Navigation Satellite System)
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
GSS	GNSS System Simulator
HDOP	Horizontal Dilution Of Precision
ICD	Interface Control Document
ICS	Implementation Conformance Statement
IS	Interface Specification
LOS	Line Of Sight
LPP	LTE Positioning Protocol
MBS	Metropolitan Beacon System
PPM	Parts per million
PRS	Positioning Reference Signal
QZSS	Quasi-Zenith Satellite System
RRC	Radio Resource Control
SBAS	Space Based Augmentation System
SCC	Secondary Component Carrier
SFN	System Frame Number
SS	System simulator
SV	Space Vehicle
SV ID	Space Vehicle Identification
TDD	Time Division Duplex
TOD	Time Of Day
TOW	Time of Week TTFF Time To First Fix
UE	User Equipment
UTRA	Universal Terrestrial Radio Access
UTRAN	Universal Terrestrial Radio Access Network
WAAS	Wide Area Augmentation System
WGS-84	World Geodetic System 1984
WLAN	Wireless Local Area Network

4 General

4.1 GPS and GNSS orbital model information, assistance data and assistance data files

The following subclauses 5 and 6 define the GPS and GNSS orbital model information, the assistance data and the assistance data files for the test cases as follows:

Subclause 5.1: data for UTRA A-GPS Signalling test cases defined in TS 37.571-2 [7] subclauses 6.1.1 to 6.1.3.

Subclause 5.2: data for UTRA A-GPS Minimum Performance test cases defined in TS 37.571-1 [6] subclause 5.

Subclause 6.1: data for UTRA and E-UTRA A-GNSS Signalling test cases defined in TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and subclause 7.

Subclause 6.2: data for UTRA and E-UTRA A-GNSS Minimum Performance test cases defined in TS 37.571-1 [6] subclauses 6 and 7.

The orbital model information is defined and where appropriate is given in Yuma format in .txt files for each scenario in the appropriate data file specified in Annex A or Annex B.

Where the assistance data is fixed or is not required on a per-satellite basis, then it is defined in the following subclauses. Where assistance data is required on a per-satellite basis, or where the values of the data also vary with time then it is specified in comma-separated-variable files in the appropriate data file specified in Annex A or Annex B. These files specify the values to be used for each satellite, indexed by satellite PRN or SV ID, and, where applicable, the values to be used indexed by both time and satellite PRN or SV ID.

4.2 OTDOA assistance data

The following subclause 7 defines the OTDOA assistance data for the test cases as follows:

Subclause 7.1: data for OTDOA Signalling test cases defined in TS 37.571-2 [7].

Subclause 7.2: data for OTDOA Measurement test cases defined in TS 37.571-1 [6].

Subclause 7.3: data for OTDOA Measurement test cases for Carrier Aggregation defined in TS 37.571-1 [6].

5 GPS information

5.1 GPS Scenario and Assistance data for Assisted GPS signalling tests

5.1.1 General

This subclause defines the GPS scenario and the associated assistance data that shall be used where required for UTRA Assisted GPS signalling tests defined in TS 37.571-2 [7] subclauses 6.1.1 to 6.1.3.

The satellite simulator shall generate the six satellite signals defined in subclause 5.1.2 and/or shall provide assistance data as defined in subclause 5.1.3. Note that some tests require assistance data to be provided even though satellite signals are not required.

5.1.2 GPS Scenario

The following GPS scenario shall be used. The assistance data specified in the following subclauses is consistent with this GPS scenario:

- Yuma Almanac data: see file Tokyo Yuma.txt in the GPS data sig zip file specified in Annex A
- UE location and Reference location: static at latitude: 35 degrees 40 minutes north, longitude: 139 degrees 45 minutes east, (Tokyo) height: = 50m
- Start time: 12th September 2003 21:30:00
- Visible satellites simulated: PRNs: 4, 6, 9, 10, 13, 22.
- Ionospheric model: see values in subclause 5.1.3.4
- The levels of the simulated satellites shall all be at -125dBm +/- 6dB

5.1.3 Assistance Data

Where assistance data is required on a per-satellite basis, or where the values of the data also varies with time it is specified in comma-separated-variable files in the GPS data sig zip file specified in Annex A. These files specify the

values to be used for each satellite, indexed by satellite PRN, and, where applicable, the values to be used indexed by both time and satellite PRN.

Assistance data that is marked as “time varying” and the GPS TOW msec field are only specified and used in 1 second increments. Interpolation between these values shall not be used.

The accuracy of the GPS TOW msec and assistance data that is marked as “time varying” in the provided assistance data shall be within +/- 2 s relative to the GPS time in the system simulator. In the case that assistance data is required but satellite signals are not required then this clause does not apply.

Assistance data Information Elements and fields that are not specified shall not be used.

The information elements detailed below are fully defined in 3GPP TS 25.331 [16]

5.1.3.1 Assistance Data Reference Time

Reference Time

Reference Time (Fields occurring once per message)

Information Element	Units	Value/remark	Release
GPS Week	weeks	211	
GPS Week Cycle Number		1	Rel-10 onwards
GPS TOW msec	msec	509400 s. Start time. Add integer number of 1 seconds as required. (Note)	
UE Positioning GPS ReferenceTime Uncertainty		125 (2.127 seconds)	Rel-7 onwards
Note: GPS TOW msec This is the value of GPS TOW msec when the GPS scenario is started in the GPS simulator. The value of GPS TOW msec to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GPS simulator to this value, rounded up to the next 1 second interval. This “current GPS TOW msec” is then also used to determine the value of any other Information Elements marked as “Time varying” in subclause 5.1.3. In the case that the (hardware) GPS simulator is switched off or not present then the value of GPS TOW msec given above may be used.			

5.1.3.2 Assistance Data Reference UE Position

Reference UE Position

Information Element	Units	Value/remark
Latitude sign		0
Degrees Of Latitude	degrees	3.566666666666667 10E1
Degrees Of Longitude	degrees	1.397500000000000 10E2
Altitude Direction		0
Altitude	m	50
Uncertainty semi-major	m	3000
Uncertainty semi-minor	m	3000
Orientation of major axis	degrees	0
Uncertainty Altitude	m	500
Confidence	%	68

5.1.3.3 Assistance Data Navigation Model

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

Navigation Model (Fields occurring once per satellite)

Information Element	Units	Value/remark
SatID	-	PRNs: 4, 6, 9, 10, 13, 22.
Satellite Status		0 (see note)
Note: For consistency Satellite Status is also given in file: Navigation model.csv		

Ephemeris and Clock correction Information Elements (Fields occurring once per satellite)

Information Element	Units	Value/remark
C/A or P on L2		See file: Navigation model.csv
URA Index		See file: Navigation model.csv
SV Health		See file: Navigation model.csv
IODC	-	See file: Navigation model.csv
L2 P Data Flag		See file: Navigation model.csv
SF 1 Reserved	-	See file: Navigation model.csv
T_{GD}	sec	See file: Navigation model.csv
t_{oc}	sec	See file: Navigation model.csv
af_2	sec/sec ²	See file: Navigation model.csv
af_1	sec/sec	See file: Navigation model.csv
af_0	sec	See file: Navigation model.csv
C_{rs}	meters	See file: Navigation model.csv
Δn	semi-circles/sec	See file: Navigation model.csv
M_0	semi-circles	See file: Navigation model.csv
C_{uc}	radians	See file: Navigation model.csv
E	-	See file: Navigation model.csv
C_{us}	radians	See file: Navigation model.csv
$(A)^{1/2}$	meters ^{1/2}	See file: Navigation model.csv
t_{oe}	sec	See file: Navigation model.csv
Fit Interval Flag		See file: Navigation model.csv
AODO	sec	See file: Navigation model.csv
C_{ic}	radians	See file: Navigation model.csv
OMEGA ₀	semi-circles	See file: Navigation model.csv
C_{is}	radians	See file: Navigation model.csv
i_0	semi-circles	See file: Navigation model.csv
C_{rc}	meters	See file: Navigation model.csv
ω	semi-circles	See file: Navigation model.csv
OMEGA _{dot}	semi-circles/sec	See file: Navigation model.csv
l_{dot}	semi-circles/sec	See file: Navigation model.csv

5.1.3.4 Assistance Data Ionospheric Model**Ionospheric Model**

Information Element	Units	Value/remark
α_0	seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	seconds	79872
β_1	sec/semi-circle	65536
β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

5.1.3.5 Assistance Data Almanac

Almanac (Fields occurring once per message)

Information Element	Units	Value/remark	Release
WN _a	weeks	212	
Complete Almanac Provided		TRUE	Rel-10 onwards

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	24

Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark
DataID	-	See file: Almanac.csv
SatID	-	PRNs: 1 to 24
e	dimensionless	See file: Almanac.csv
t _{0a}	sec	See file: Almanac.csv
δi	semi-circles	See file: Almanac.csv
OMEGADOT	semi-circles/sec	See file: Almanac.csv
SV Health		See file: Almanac.csv
A ^{1/2}	meters ^{1/2}	See file: Almanac.csv
OMEGA ₀	semi-circles	See file: Almanac.csv
M ₀	semi-circles	See file: Almanac.csv
ω	semi-circles	See file: Almanac.csv
af ₀	seconds	See file: Almanac.csv
af ₁	sec/sec	See file: Almanac.csv

5.1.3.6 Assistance Data Acquisition Assistance

GPS Acquisition Assist - Information Elements appearing once per message

Information Element	Units	Value/remark	Release
GPS TOW msec	msec	509400 s. Start time. Add integer number of 1 seconds as required. (Note)	
UE Positioning GPS ReferenceTime Uncertainty		125 (2.127 seconds)	Rel-7 onwards
Note: GPS TOW msec This is the value of GPS TOW msec when the GPS scenario is started in the GPS simulator. The value of GPS TOW msec to be used in the Acquisition Assistance IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GPS simulator to this value, rounded up to the next 1 second interval. In the case that the (hardware) GPS simulator is switched off or not present then the value of GPS TOW msec given above may be used.			

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GPS Acquisition Assist - Information Elements appearing once per satellite

Information Element	Units	Value/remark	Release
SatID	-	PRNs: 4, 6, 9, 10, 13, 22.	
Doppler (0 th order term)	Hz	Time varying. See file: Acquisition assist .csv (Note)	
Doppler (1 st order term)	Hz/s	Time varying. See file: Acquisition assist .csv (Note)	
Doppler Uncertainty	Hz	Time varying. See file: Acquisition assist .csv (Note)	
Code Phase	chips	Time varying. See file: Acquisition assist .csv (Note)	
Integer Code Phase	-	Time varying. See file: Acquisition assist .csv (Note)	
GPS Bit number	-	Time varying. See file: Acquisition assist .csv (Note)	
Code Phase Search Window	chips	Time varying. See file: Acquisition assist .csv (Note)	
Azimuth	Degrees	Time varying. See file: Acquisition assist .csv (Note)	
Elevation	Degrees	Time varying. See file: Acquisition assist .csv (Note)	
Azimuth LSB	Degrees	Time varying. Calculated from "Azimuth", see file: Acquisition assist .csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. Calculated from "Elevation", see file: Acquisition assist .csv (Note)	Rel-10 onwards
Note: Acquisition Assist Information Elements This field is "Time varying" and its value depends on the "current GPS TOW msec". The value of this field to be used shall be determined by taking the "current GPS TOW msec" value and selecting the field value in the Acquisition assist.csv file corresponding to the value of "current GPS TOW msec".			

5.2 GPS Scenarios and Assistance Data for Assisted GPS Minimum Performance tests

5.2.1 General

This subclause defines the GPS scenarios and assistance data IEs which shall be available for use as specified in all UTRA A-GPS Minimum Performance test cases defined in TS 37.571-1 [6] subclause 5.

Subclauses 5.2.2 and 5.2.3 list the assistance data IEs required for minimum performance testing of UE-based mode, and subclauses 5.2.4 and 5.2.5 list the assistance data available for minimum performance testing of UE-assisted mode. Subclause 5.2.6 lists the values of the assistance data IE fields for all minimum performance testing.

The A-GPS minimum performance requirements are defined by assuming that all relevant and valid assistance data is received by the UE in order to perform GPS measurements and/or position calculation. This subclause does not include nor consider delays occurring in the various signalling interfaces of the network.

5.2.1.1 Satellite constellations and assistance data for A-GPS minimum performance testing

The satellite constellations for minimum performance testing shall consist of 24 satellites. Almanac assistance data shall be available for all these 24 satellites. At least 9 of the satellites shall be visible to the UE (that is above 5 degrees elevation with respect to the UE). Other assistance data shall be available for 9 of these visible satellites. In each test, signals are generated for only a sub-set of these satellites for which other assistance data is available. The number of satellites in this sub-set is specified in the test. The satellites in this sub-set shall all be above 15 degrees elevation with respect to the UE. The HDOP for the test shall be calculated using this sub-set of satellites. The selection of satellites for this sub-set shall be selected consistent with achieving the required HDOP for the test.

5.2.1.2 GPS Scenarios for A-GPS minimum performance testing

This subclause defines the GPS scenarios that shall be used for all Assisted GPS minimum performance tests defined in TS 37.571-1 [6] subclause 5.

The GPS scenarios achieve the required HDOP for the Test Cases and they also satisfy the requirement that for each test instance that the reference location shall change sufficiently such that the UE shall have to use the new assistance data.

The satellites to be simulated in each test case are specified in subclause 5.2.1.2.5.

The viable running time during which the scenario maintains the required HDOP or HDOPs is given. Once this time has been reached the scenario shall be restarted from its nominal start time.

5.2.1.2.1 GPS Scenario #1

The following GPS scenario #1 shall be used during the TTFF tests defined in TS 37.571-1 [6] subclauses 5.2 to 5.5. The assistance data specified in the following subclauses for GPS scenario #1 is consistent with this GPS scenario.

Yuma Almanac data: see file GPS 1 Yuma.txt in the GPS data perf zip file specified in Annex A.

UE location: the UE location is calculated as a random offset from the reference location using the method described in subclause 5.2.1.2.4. The reference location is: latitude: 33 degrees 45 minutes 0.019 seconds north, longitude: 84 degrees 23 minutes 0.011 seconds west, (Atlanta USA), height: = 300m.

Nominal start time: 22nd January 2005 (Saturday) 00:08:00.

Viable running time to maintain specified HDOP values: 19 minutes.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated: PRNs: 2, 6, 10, 17, 18, 21, 26, 29, 30.

Ionospheric model: see values in subclause 5.2.6.6.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

5.2.1.2.2 GPS Scenario #2

The following GPS scenario #2 shall be used during the TTFF tests defined in TS 37.571-1 [6] subclauses 5.2 to 5.5. The assistance data specified in the following subclauses for GPS scenario #2 is consistent with this GPS scenario.

Yuma Almanac data: see file GPS 2 Yuma.txt in the GPS data perf zip file specified in Annex A.

UE location: the UE location is calculated as a random offset from the reference location using the method described in subclause 5.2.1.2.4. The reference location is: latitude: 37 degrees 48 minutes 59.988 seconds south, longitude: 144 degrees 58 minutes 0.013 seconds east, (Melbourne Australia), height: = 100m.

Nominal start time: 22nd January 2004 (Thursday) 00:08:00.

Viable running time to maintain specified HDOP values: 19 minutes.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated: PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31.

Ionospheric model: see values in subclause 5.2.6.6.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

5.2.1.2.3 GPS Scenario #3

The following GPS scenario #3 shall be used during the Moving Scenario and Periodic Location test case defined in TS 37.571-1 [6] subclause 5.6. The assistance data specified in the following subclauses for GPS scenario #3 is consistent with this GPS scenario.

Yuma Almanac data: see file GPS 3 Yuma.txt in the GPS data perf zip file specified in Annex A.

UE location: the UE location is given as a trajectory as shown in Figure 5.6.1 of TS 37.571-1 [6]. The reference location is at the centre of the trajectory and is at: latitude: 37 degrees 48 minutes 59.988 seconds south, longitude: 144 degrees 58 minutes 0.013 seconds east, (Melbourne Australia), height: = 100m.

Start time: 22nd January 2004 (Thursday) 00:08:00.

Start location: at the point between I_{11} and I_{12} in Figure 5.6.1 of TS 37.571-1 [6], going in a clock-wise direction.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated: PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31.

Viable running time to maintain specified HDOP values: 19 minutes.

Ionospheric model: see values in subclause 5.2.6.6.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

5.2.1.2.4 UE Location for TTFF test cases

This subclause defines the method for generating the random UE locations that are required to be used for the TTFF tests defined in TS 37.571-1 [6] subclauses 5.2 to 5.5.

For every Test Instance in each TTFF test case, the UE location shall be randomly selected to be within 3 km of the Reference Location. The Altitude of the UE shall be randomly selected between 0 m to 500 m above WGS-84 reference ellipsoid. These values shall have uniform random distributions.

The UE location is calculated as an offset from the Reference Location.

5.2.1.2.4.1 UE Location Offset

The UE location offset shall be calculated by selecting the next pair of random numbers, representing a pair of latitude and longitude offsets in degrees, from a standard uniform random number generator, with the following properties:

The ranges of the latitude and longitude offsets values shall be such that when translated onto the surface of the earth they shall lie within a 3km radius circle, centred on the Reference location specified for the GPS scenario under consideration. For the purposes of this calculation make the following assumptions:

- a) Over the 3km radius circle at the Reference location the earth is flat and the meridians and parallels form a rectangular grid
- b) The earth is spherical with a radius of 6371141m (equal to the WGS 84 value at 35 degrees latitude)

The resolution used for the latitude and longitude offsets values shall be 90/2E23 for the latitude offset values and 360/2E24 for the longitude offset values, representing the coding resolution in degrees specified in 3GPP TS 23.032 [19].

5.2.1.2.4.2 UE Altitude

The UE altitude value shall be calculated by selecting the next random number from a standard uniform random number generator, in the range 0 to 500, representing meters. The resolution used for the random number shall be 1, representing 1 meter.

5.2.1.2.5 Satellites to be simulated in each test case

The satellites to be simulated in each test case have been selected in order to achieve the required HDOP for that test case.

Satellites to be simulated

Test case	PRNs GPS #1	PRNs GPS #2	PRNs GPS #3
Sensitivity Coarse Time Assistance	2, 6, 10, 17, 18, 21, 26, 29	3, 11, 14, 15, 22, 23, 25, 31	-
Sensitivity Fine Time Assistance	2, 6, 10, 17, 18, 21, 26, 29	3, 11, 14, 15, 22, 23, 25, 31	-
Nominal Accuracy	2, 6, 10, 17, 18, 21, 26, 29	3, 11, 14, 15, 22, 23, 25, 31	-
Dynamic Range	2, 6, 10, 17, 26, 29	3, 14, 15, 22, 25, 31	-
Multi-Path scenario	2, 6, 17, 21, 26	3, 14, 15, 22, 25	-
Moving Scenario and Periodic location	-	-	3, 14, 15, 22, 25

5.2.2 Information elements required for normal UE based testing

The following A-GPS assistance data IEs and fields shall be present for each test. Fields not specified shall not be present. The values of the fields are specified in subclause 5.2.6.

a) UE positioning GPS reference time IE

Name of the IE	Fields of the IE	Release
Reference time		
	GPS Week	
	GPS Week Cycle Number	Rel-10 onwards
	GPS TOW msec	
	UE Positioning GPS ReferenceTime Uncertainty	Rel-7 onwards
	GPS TOW Assist	
	SatID	
	TLM Message	
	TLM Reserved	
	Alert	
	Anti-Spoof	

b) UE positioning GPS reference UE position IE

Name of the IE	Fields of the IE
Reference UE position	Ellipsoid point with Altitude and uncertainty ellipsoid

c) UE positioning GPS navigation model IE

Name of the IE	Fields of the IE
Navigation Model	All satellite information

d) UE positioning GPS ionospheric model IE

Name of the IE	Fields of the IE
Ionospheric Model	All

5.2.3 Information elements required for UE based Sensitivity Fine Time Assistance test case

The A-GPS assistance data IEs and fields that shall be present for the Sensitivity Fine Time Assistance test case shall be those specified in subclause 5.2.2 with the following exception. Fields not specified shall not be present. The values of the fields are specified in subclause 5.2.6.

UE positioning GPS reference time IE

Name of the IE	Fields of the IE	Release
Reference time		
	GPS Week	
	GPS Week Cycle Number	Rel-10 onwards
	GPS TOW msec	
	UTRAN GPS reference time	
	UTRAN GPS timing of cell frames	
	CHOICE mode	
	FDD: Primary CPICH Info	
	SFN	
	UE Positioning GPS ReferenceTime Uncertainty	Rel-7 onwards
	SFN-TOW Uncertainty	Not present Rel-7 onwards
	TUTRAN-GPS drift rate	
	GPS TOW Assist	
	SatID	
	TLM Message	
	TLM Reserved	
	Alert	
	Anti-Spoof	

5.2.4 Information elements available for normal UE assisted testing

The following A-GPS assistance data IEs and fields shall be available for use in each test. Fields not specified shall not be present. The values of the fields are specified in subclause 5.2.6.

a) UE positioning GPS reference time IE

Name of the IE	Fields of the IE	Release
Reference time		
	GPS Week	
	GPS Week Cycle Number	Rel-10 onwards
	GPS TOW msec	
	UE Positioning GPS ReferenceTime Uncertainty	Rel-7 onwards
	GPS TOW Assist	
	SatID	
	TLM Message	
	TLM Reserved	
	Alert	
	Anti-Spoof	

b) UE positioning GPS reference UE position IE

Name of the IE	Fields of the IE
Reference UE position	Ellipsoid point with Altitude and uncertainty ellipsoid

c) UE positioning GPS almanac IE

Name of the IE	Fields of the IE	Release
Almanac		
	Almanac Reference Week	
	Complete Almanac Provided	Rel-10 onwards
	All Satellite information	

d) UE positioning GPS navigation model IE

Name of the IE	Fields of the IE
Navigation Model	All satellite information

e) UE positioning GPS acquisition assistance IE

Name of the IE	Fields of the IE	Release
Acquisition Assistance		
	GPS TOW msec	
	UE Positioning GPS ReferenceTime Uncertainty	Rel-7 onwards
	Satellite information	
	SatID	
	Doppler (0 th order term)	
	Extra Doppler	
	Doppler (1 st order term)	
	Doppler Uncertainty	
	Code Phase	
	Integer Code Phase	
	GPS Bit number	
	Code Phase Search Window	
	Azimuth and Elevation	
	Azimuth	
	Elevation	
	Azimuth LSB	Rel-10 onwards
	Elevation LSB	Rel-10 onwards

5.2.5 Information elements available for UE assisted Sensitivity Fine Time Assistance test case

The A-GPS assistance data IEs and fields that shall be available for use for the Sensitivity Fine Time Assistance test case shall be those specified in subclause 5.2.4 with the following exceptions. Fields not specified shall not be present. The values of the fields are specified in subclause 5.2.6.

a) UE positioning GPS reference time IE

Name of the IE	Fields of the IE	Release
Reference time		
	GPS Week	
	GPS Week Cycle Number	Rel-10 onwards
	GPS TOW msec	
	UTRAN GPS reference time	
	UTRAN GPS timing of cell frames	
	CHOICE mode	
	FDD: Primary CPICH Info	
	SFN	
	UE Positioning GPS ReferenceTime Uncertainty	Rel-7 onwards
	SFN-TOW Uncertainty	Not present Rel-7 onwards
	TUTRAN-GPS drift rate	
	GPS TOW Assist	
	SatID	

	TLM Message	
	TLM Reserved	
	Alert	
	Anti-Spoof	

b) UE positioning GPS acquisition assistance IE

Name of the IE	Fields of the IE	Release
Acquisition Assistance		
	GPS TOW msec	
	UTRAN GPS reference time	
	UTRAN GPS timing of cell frames	
	CHOICE mode	
	FDD: Primary CPICH Info	
	SFN	
	UE Positioning GPS ReferenceTime Uncertainty.	Rel-7 onwards
	Satellite information	
	SatID	
	Doppler (0 th order term)	
	Extra Doppler	
	Doppler (1 st order term)	
	Doppler Uncertainty	
	Code Phase	
	Integer Code Phase	
	GPS Bit number	
	Code Phase Search Window	
	Azimuth and Elevation	
	Azimuth	
	Elevation	
	Azimuth LSB	Rel-10 onwards
	Elevation LSB	Rel-10 onwards

5.2.6 Contents of Information elements for A-GPS Minimum performance testing

5.2.6.1 General

This subclause defines the assistance data values that shall be used for all Assisted GPS minimum performance tests. It is given for GPS scenarios #1, #2 and #3 where it is different for each scenario; otherwise it is marked “All” where the same value is used for all scenarios.

Where assistance data is required on a per-satellite basis, or where the values of the data also varies with time it is specified in comma-separated-variable files with suffixes XX in the GPS data perf zip file specified in Annex A, where XX is 01, 02 and 03 for GPS scenarios #1, #2 and #3 respectively. These files specify the values to be used for each satellite, indexed by satellite PRN, and, where applicable, the values to be used indexed by both time and satellite PRN.

Assistance data that is marked as “time varying” is specified and used in 80 ms increments. Interpolation between these values shall not be used.

Assistance data Information Elements and fields that are not specified shall not be used.

The information elements detailed below are fully defined in 3GPP TS 25.331 [16]

5.2.6.2 IE Random Offset Values

This subclause defines the methods for generating the random offsets that are required to be applied to some assistance data IEs for certain tests.

5.2.6.2.1 GPS TOW msec

For every Test Instance in each TTFF test case, the IE GPS TOW msec shall have a random offset, relative to GPS system time, within the allowed error range of Coarse Time Assistance defined in the test case. This offset value shall have a uniform random distribution.

Note: For the Moving Scenario and Periodic Update Test Case the value of the IE GPS TOW msec shall be set to the nominal value, i.e. no offset shall be used.

The offset value shall be calculated by selecting the next random number from a standard uniform random number generator, in the range specified for the GPS Coarse Time assistance error range in the Test Requirements, Test parameters table for the test under consideration. The resolution used for the random number shall be 0.01, representing 10ms.

5.2.6.2.2 UTRAN GPS timing of cell frames

In addition, for every Fine Time Assistance Test Instance the IE UTRAN GPS timing of cell frames shall have a random offset, relative to the true value of the relationship between the two time references, within the allowed error range of Fine Time Assistance defined in the test case. This offset value shall have a uniform random distribution.

The offset value shall be calculated by selecting the next random number from a standard uniform random number generator with the following properties:

The range shall be the number of UMTS chips whose duration is less than the range specified for the GPS Fine Time assistance error range in the Test Requirements, Test parameters table for the test under consideration.

The resolution used for the random number shall be 1, representing 1 UMTS chip.

5.2.6.3 Assistance Data Reference Time

Contents of UE positioning GPS reference time IE

Reference Time (Fields occurring once per message)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
GPS Week	weeks	282	230	230
GPS Week Cycle Number (Note 5)		1	1	1
GPS TOW msec	msec	518880000. Start time. Add number of ms as required. (Note 1)	346080000. Start time. Add number of ms as required. (Note 1)	346080000. Start time. Add number of ms as required. (Note 1)
UTRAN GPS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GPS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
SFN		Note 2	Note 2	-
UE Positioning GPS ReferenceTime Uncertainty. Note 3		For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	'125' (2.127s)
SFN-TOW Uncertainty. Note 4		lessThan10. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	lessThan10. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
TUTRAN-GPS drift rate		0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
<p>Note 1: GPS TOW msec</p> <p>This is the value in ms of GPS TOW msec when the GPS scenario is initially started in the GPS simulator. For all TTFF test cases, each time a GPS scenario is used, the GPS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.</p> <p>The actual value of GPS TOW msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GPS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>For all TTFF test cases a random offset is then added to the value of GPS TOW msec as described in subclause 5.2.6.2</p> <p>Note 2: UTRAN GPS timing of cell frames and SFN</p> <p>The values of UTRAN GPS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 5.2.6.2</p> <p>Note 3: This IE only present for Rel-7 onwards.</p> <p>Note 4: This IE not present for Rel-7 onwards.</p> <p>Note 5: This IE is only present for Rel-10 onwards.</p>				

Satellite Information

Information Element	Units	Value/remark GPS All
Number of satellites	-	9

Reference Time - GPS TOW Assist (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
SatID		PRNs: 2, 6, 10, 17, 18, 21, 26, 29, 30	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31

Reference Time - GPS TOW Assist (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS All
TLM Message	Bit string	10922
TLM Reserved	Bit string	2
Alert		0
Anti-Spoof		1

5.2.6.4 Assistance Data Reference UE Position

Contents of UE positioning GPS reference UE position IE

The uncertainty of the semi-major axis is 3 km. The uncertainty of the semi-minor axis is 3 km. The orientation of the major axis is 0 degrees. The uncertainty of the altitude information is 500 m. The confidence factor is 68%.

Reference UE Position

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
Latitude sign		0	1	1
Degrees of latitude	degrees	33.750005	37.816663	37.816663
Degrees of longitude	degrees	-84.383336	144.966670	144.966670
Altitude Direction		0	0	0
Altitude	m	300	100	100
Uncertainty semi-major	m	3000	3000	3000
Uncertainty semi-minor	m	3000	3000	3000
Orientation of major axis	degrees	0	0	0
Uncertainty altitude	m	500	500	500
Confidence	%	68	68	68

5.2.6.5 Assistance Data Navigation Model

Contents of UE positioning GPS navigation model IE

Satellite Information

Information Element	Units	Value/remark GPS All
Number of satellites	-	9

Navigation Model (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
SatID	-	PRNs: 2, 6, 10, 17, 18, 21, 26, 29, 30	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31
Satellite Status		0 (Note)	0 (Note)	0 (Note)
Note: For consistency Satellite Status is also given in file: Navigation model XX.csv				

Ephemeris and Clock Correction Information Elements (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS All
C/A or P on L2		See file: Navigation model XX.csv
URA Index		See file: Navigation model XX.csv
SV Health		See file: Navigation model XX.csv
IODC	-	See file: Navigation model XX.csv
L2 P Data Flag		See file: Navigation model XX.csv
SF 1 Reserved	-	See file: Navigation model XX.csv
T _{GD}	sec	See file: Navigation model XX.csv
t _{oc}	sec	See file: Navigation model XX.csv
af ₂	sec/sec ²	See file: Navigation model XX.csv
af ₁	sec/sec	See file: Navigation model XX.csv
af ₀	sec	See file: Navigation model XX.csv
C _{rs}	meters	See file: Navigation model XX.csv
Δn	semi-circles/sec	See file: Navigation model XX.csv
M ₀	semi-circles	See file: Navigation model XX.csv
C _{uc}	radians	See file: Navigation model XX.csv
e	-	See file: Navigation model XX.csv
C _{us}	radians	See file: Navigation model XX.csv
(A) ^{1/2}	meters ^{1/2}	See file: Navigation model XX.csv
t _{oe}	sec	See file: Navigation model XX.csv
Fit Interval Flag		See file: Navigation model XX.csv
AODO	sec	See file: Navigation model XX.csv
C _{ic}	radians	See file: Navigation model XX.csv
OMEGA ₀	semi-circles	See file: Navigation model XX.csv
C _{is}	radians	See file: Navigation model XX.csv
i ₀	semi-circles	See file: Navigation model XX.csv
C _{rc}	meters	See file: Navigation model XX.csv
ω	semi-circles	See file: Navigation model XX.csv
OMEGA _{dot}	semi-circles/sec	See file: Navigation model XX.csv
Idot	semi-circles/sec	See file: Navigation model XX.csv

5.2.6.6 Assistance Data Ionospheric Model

Contents of UE positioning GPS ionospheric model IE

Ionospheric Model

Information Element	Units	Value/remark GPS All
α ₀	seconds	4.6566129 10E-9
α ₁	sec/semi-circle	1.4901161 10E-8
α ₂	sec/(semi-circle) ²	-5.96046 10E-8
α ₃	sec/(semi-circle) ³	-5.96046 10E-8
β ₀	seconds	79872
β ₁	sec/semi-circle	65536
β ₂	sec/(semi-circle) ²	-65536
β ₃	sec/(semi-circle) ³	-393216

5.2.6.7 Assistance Data Almanac

Contents of UE positioning GPS almanac

Almanac (Field occurring once per message)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
WN _a	weeks	27	230	230
Complete Almanac Provided (Note 1)		TRUE	TRUE	TRUE
Note 1: This IE is only present for Rel-10 onwards.				

Satellite Information

Information Element	Units	Value/remark GPS All
Number of satellites	-	24

Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS All
DataID	-	See file: Almanac XX.csv

Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
SatID	-	PRNs: 1, 2, 4, 5, 6, 7, 9, 10, 11, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26, 27, 29, 30	PRNs: 1, 2, 3, 4, 5, 6, 7, 8, 11, 13, 14, 15, 16, 17, 18, 20, 21, 22, 23, 25, 27, 28, 30, 31	PRNs: 1, 2, 3, 4, 5, 6, 7, 8, 11, 13, 14, 15, 16, 17, 18, 20, 21, 22, 23, 25, 27, 28, 30, 31

Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS All
e	dimensionless	See file: Almanac XX.csv
t _{oa}	sec	See file: Almanac XX.csv
δi	semi-circles	See file: Almanac XX.csv
OMEGADOT	semi-circles/sec	See file: Almanac XX.csv
SV Health		See file: Almanac XX.csv
A ^{1/2}	meters ^{1/2}	See file: Almanac XX.csv
OMEGA ₀	semi-circles	See file: Almanac XX.csv
M ₀	semi-circles	See file: Almanac XX.csv
ω	semi-circles	See file: Almanac XX.csv
af ₀	seconds	See file: Almanac XX.csv
af ₁	sec/sec	See file: Almanac XX.csv

5.2.6.8 Assistance Data Acquisition Assistance

Contents of UE positioning GPS acquisition assistance IE

GPS Acquisition Assistance (Fields occurring once per message)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
GPS TOW msec	msec	51888000 ms. Start time. Add number of ms as required. (Note 1)	346080000 ms. Start time. Add number of ms as required. (Note 1)	346080000 ms. Start time. Add number of ms as required. (Note 1)
UTRAN GPS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GPS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
SFN		Note 2	Note 2	-
UE Positioning GPS ReferenceTime Uncertainty. Note 3		For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	'125' (2.127s)
<p>Note 1: GPS TOW msec</p> <p>This is the value in ms of GPS TOW msec when the GPS scenario is initially started in the GPS simulator. For all TTFF test cases, each time a GPS scenario is used, the GPS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.</p> <p>The actual value of GPS TOW msec to be used in the Acquisition Assistance IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GPS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>For all TTFF test cases a random offset is then added to the value of GPS TOW msec as described in subclause 5.2.6.2</p> <p>This "final GPS TOW msec" value is then also used to determine the value of the Acquisition Assistance Information Elements marked as "Time varying"</p> <p>Note 2: UTRAN GPS timing of cell frames and SFN.</p> <p>The values of UTRAN GPS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 5.2.6.2</p> <p>Note 3: This IE only present for Rel-7 onwards.</p>				

Satellite Information

Information Element	Units	Value/remark GPS All
Number of satellites	-	9

GPS Acquisition Assistance (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS #1	Value/remark GPS #2	Value/remark GPS #3
SatID	-	PRNs: 2, 6, 10, 17, 18, 21, 26, 29, 30	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31	PRNs: 3, 11, 14, 15, 18, 22, 23, 25, 31

GPS Acquisition Assistance (Fields occurring once per satellite)

Information Element	Units	Value/remark GPS All	Release
Doppler (0 th order term)	Hz	Time varying. See file: Acquisition assist XX.csv (Note)	
Doppler (1 st order term)	Hz/sec	Time varying. See file: Acquisition assist XX.csv (Note)	
Doppler Uncertainty	Hz	Time varying. See file: Acquisition assist XX.csv (Note)	
Code Phase	chips	Time varying. See file: Acquisition assist XX.csv (Note)	
Integer Code Phase	-	Time varying. See file: Acquisition assist XX.csv (Note)	
GPS Bit number	-	Time varying. See file: Acquisition assist XX.csv (Note)	
Code Phase Search Window	chips	Time varying. See file: Acquisition assist XX.csv (Note)	
Azimuth	deg	Time varying. See file: Acquisition assist XX.csv (Note)	
Elevation	deg	Time varying. See file: Acquisition assist XX.csv (Note)	
Azimuth LSB	deg	Time varying. Calculated from "Azimuth", see file: Acquisition assist XX.csv (Note)	Rel-10 onwards
Elevation LSB	deg	Time varying. Calculated from "Elevation", see file: Acquisition assist XX.csv (Note)	Rel-10 onwards
Note: Acquisition Assistance Information Elements. This field is "Time varying" and its value depends on the "final GPS TOW msec" as described above. The value of this field to be used shall be determined by taking the "final GPS TOW msec" value and selecting the nearest field value in the Acquisition assist.csv file corresponding to the value of "final current GPS TOW msec".			

6 GNSS information

6.1 GNSS Scenarios and Assistance Data for Assisted GNSS signalling tests

6.1.1 General

This subclause defines the GNSS scenario and the associated assistance data that shall be used where required for UTRA and E-UTRA Assisted GNSS signalling tests defined in TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and subclause 7.

In all cases the Assistance Data is given in the two necessary formats, RRC format for TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and LPP format for TS 37.571-2 [7] subclause 7. Other information is also given separately for TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and subclause 7 where it differs between the subclauses.

The satellite simulator shall generate all the UE supported GNSS satellite signals defined in subclause 6.1.2 and/or shall provide assistance data dependent on the UE capabilities defined in subclause 6.1.3. Note that some tests require assistance data to be provided even though satellite signals are not required.

The A-GNSS signalling test cases may include several sub-test cases dependent on the GNSS supported by the UE. Each sub-test case is identified by a Sub-Test Case Number as defined below. In some cases the detailed assistance data content defined in subclause 6.1.3 depends on the particular sub-test case.

Table 6.1.1-1: Sub-Test Case Number Definition for TS 37.571-2 subclauses 6.2.1 to 6.2.3

Sub-Test Case Number	Supported GNSS
1	UE supporting A-GLONASS only
2	UE supporting A-Galileo only
3	UE supporting A-GPS and Modernized GPS only
4	UE supporting A-GPS and A-GLONASS only
8	UE supporting A-GPS and A-Galileo only
9	UE supporting A-BDS only
10	UE supporting A-GPS and A-BDS only

Table 6.1.1-2: Sub-Test Case Number Definition for TS 37.571-2 subclause 7

Sub-Test Case Number	Supported GNSS
1	UE supporting GNSS with A-GPS only
2	UE supporting GNSS with A-GLONASS only
3	UE supporting GNSS with A-Galileo only
4	UE supporting GNSS with A-GPS and A-GLONASS only
7	UE supporting GNSS ⁽¹⁾ and OTDOA
8	UE supporting A-GPS and A-Galileo only
9	UE supporting A-BDS only
10	UE supporting A-GPS and A-BDS only
Note 1: Any GNSS of GPS, GLONASS, Galileo or BDS	

The term SV ID used in this subclause is defined as the satellite PRN for GPS, as Code Number for Galileo, as the satellite Slot Number for GLONASS and as the Ranging Code Number for BDS.

6.1.2 GNSS Scenario

The following GNSS scenario shall be used. The assistance data specified in the following subclauses is consistent with this GNSS scenario:

- Yuma Almanac data: the required file(s) in the GNSS data sig zip file specified in Annex B are given below.

Table 6.1.2-1: Yuma / AGL Almanac data files for TS 37.571-2 subclauses 6.2.1 to 6.2.3

Sub-Test Case Number	Yuma / AGL file(s)
1	Sig GNSS 1-1 AGL.txt
2	Sig GNSS 1-2 Yuma.txt
3	Sig GNSS 1-3 Yuma.txt
4	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-1 AGL.txt
8	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-2 Yuma.txt
9	Sig GNSS 1-9 Yuma.txt
10	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-9 Yuma.txt

Table 6.1.2-2: Yuma / AGL Almanac data files for TS 37.571-2 subclause 7

Sub-Test Case Number	Yuma / AGL file(s)
1	Sig GNSS 1-3 Yuma.txt
2	Sig GNSS 1-1 AGL.txt
3	Sig GNSS 1-2 Yuma.txt
4	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-1 AGL.txt
7	[FFS]
8	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-2 Yuma.txt
9	Sig GNSS 1-9 Yuma.txt
10	Sig GNSS 1-3 Yuma.txt and Sig GNSS 1-9 Yuma.txt

- UE location and Reference location:

Static at latitude: 35 degrees 44 minutes 39.432 seconds north, longitude: 139 degrees 40 minutes 48.633 seconds east, (Tokyo Japan 2012), height: = 300m.

- Nominal start time:

1st January 2012 00:31:00 (GPS time).

- Visible satellites simulated are given below

Table 6.1.2-3: Satellites to be simulated for TS 37.571-2 subclauses 6.2.1 to 6.2.3

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	3, 4, 9, 10, 18, 20
2	5, 10, 11, 18, 19, 20
3	1, 11, 17, 20, 23, 28 (Note)
4	GPS: 1, 17, 20, 28. GLONASS: 3, 10, 18, 20
8	GPS: 1, 17, 20, 28. Galileo: 5, 10, 11, 18.
9	1, 2, 7, 18, 21, 27
10	GPS: 1, 17, 20, 28. BDS: 1, 7, 18, 21.
Note: For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.	

Table 6.1.2-4: Satellites to be simulated for TS 37.571-2 subclause 7

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	1, 11, 17, 20, 23, 28
2	3, 4, 9, 10, 18, 20
3	5, 10, 11, 18, 19, 20
4	GPS: 1, 17, 20, 28. GLONASS: 3, 10, 18, 20
7	[FFS]
8	GPS: 1, 17, 20, 28. Galileo: 5, 10, 11, 18.
9	1, 2, 7, 18, 21, 27
10	GPS: 1, 17, 20, 28. BDS: 1, 7, 18, 21.

- Ionospheric model: see values in subclause 6.1.3
- The levels of the simulated satellites shall all be at -125dBm +/- 6dB

6.1.3 Assistance Data

This subclause defines the GNSS scenarios and assistance data IEs which shall be available for use where required in A-GNSS signalling test cases defined in TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and subclause 7.

6.1.3.1 Default Assistance Data for TS 37.571-2 subclauses 6.2.1 to 6.2.3

The assistance data listed in subclause 6.1.3.1 are the assistance data elements pushed by the SS in some tests defined in TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3. During the test the UE may request additional assistance data as specified in the tests and the SS shall then provide any other assistance data available as defined in subclause 6.1.3.

Table 6.1.3.1-1: GNSS assistance data to be provided to the UE

GNSS Assistance Data IE to be provided to the UE	Mode used in test case	
	UE-based	UE-assisted

GPS reference time	Yes for sub-tests 3, 4, 8, 10	Yes for sub-tests 3, 4, 8, 10
GPS reference UE position	Yes for sub-tests 3, 4, 8, 10	No
GPS navigation model	Yes for sub-tests 3, 4, 8, 10	No
GPS ionospheric model	Yes for sub-tests 3, 4, 8, 10	No
GPS UTC model	Yes for sub-test 4, 8	Yes for sub-test 4, 8
GPS acquisition assistance	No	Yes for sub-tests 3, 4, 8, 10
GANSS reference time	Yes for sub-tests 1, 2, 9	Yes for sub-tests 1, 2, 9
GANSS reference UE position	Yes for sub-tests 1, 2, 9	No
GANSS ionospheric model	Yes for sub-test 2, 8	No
GANSS additional ionospheric model	Yes for sub-test 1, 9, 10	No
GANSS Time Models	Yes for sub-test 4, 8, 10	No
GANSS navigation model	Yes for sub-test 2, 8	No
GANSS additional navigation models	Yes for sub-tests 1, 4, 9, 10	No
GANSS reference measurement information	No	Yes for sub-tests 1, 2, 4, 8, 9, 10
GANSS auxiliary information	Yes for sub-tests 1, 3, 4. Note.	Yes for sub-tests 1, 3, 4. Note.
Note: Also if UE supports multiple signals per GNSS		

6.1.3.2 Assistance Data values for TS 37.571-2 subclauses 6.2.1 to 6.2.3

Where assistance data is required on a per-satellite basis, or where the values of the data also varies with time it is specified in comma-separated-variable files in the GNSS data sig zip file specified in Annex B. These files specify the values to be used for each satellite, indexed by satellite PRN or SV ID, and, where applicable, the values to be used indexed by both time and satellite PRN or SV ID.

Assistance data that is marked as “time varying” and the GPS TOW msec or GANSS TOD field are only specified and used in 1 second increments. Interpolation between these values shall not be used.

The accuracy of the GPS TOW msec or GANSS TOD and assistance data that is marked as “time varying” in the provided assistance data shall be within +/- 2 s relative to the GNSS time in the system simulator. In the case that assistance data is required but satellite signals are not required then this clause does not apply.

Assistance data Information Elements and fields that are not specified shall not be used.

The information elements detailed below are fully defined in 3GPP TS 25.331 [16]

Assistance Data GPS Reference Time

GPS Reference Time (Fields occurring once per message)

Information Element	Units	Value/remark	Release
GPS Week	weeks	1669	
GPS Week Cycle Number		1	Rel-10 onwards
GPS TOW msec	msec	1860000 ms. Start time. Add integer number of 1 seconds as required. (Note)	
UE Positioning GPS Reference Time Uncertainty		125 (2.127 seconds)	
Note: GPS TOW msec This is the value of GPS TOW msec when the GNSS scenario is started in the GNSS simulator. The value of GPS TOW msec to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This “current GPS TOW msec” is then also used to determine the value of any other Information Elements marked as “Time varying” in subclause 6.1.3.2. In the case that the (hardware) GPS simulator is switched off or not present then the value of GPS TOW msec given above may be used.			

Assistance Data GPS Reference UE Position

GPS Reference UE Position

Information Element	Units	Value/remark
Latitude sign		0
Degrees Of Latitude	degrees	35.744287
Degrees Of Longitude	degrees	139.680176
Altitude Direction		0
Altitude	m	300
Uncertainty semi-major	m	3000
Uncertainty semi-minor	m	3000
Orientation of major axis	degrees	0
Uncertainty Altitude	m	500
Confidence	%	68

Assistance Data GPS Navigation Model

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GPS Navigation Model (Fields occurring once per satellite)

Information Element	Units	Value/remark
SatID	-	PRNs: 1, 11, 17, 20, 23, 28
Satellite Status		0 (see note)

Note: For consistency Satellite Status is also given in file: Sig GPS Navigation model.csv

GPS Ephemeris and Clock correction Information Elements (Fields occurring once per satellite)

Information Element	Units	Value/remark
C/A or P on L2		See file: Sig GPS Navigation model.csv
URA Index		See file: Sig GPS Navigation model.csv
SV Health		See file: Sig GPS Navigation model.csv
IODC	-	See file: Sig GPS Navigation model.csv
L2 P Data Flag		See file: Sig GPS Navigation model.csv
SF 1 Reserved	-	See file: Sig GPS Navigation model.csv
SF 2 Reserved	-	See file: Sig GPS Navigation model.csv
SF 3 Reserved	-	See file: Sig GPS Navigation model.csv
SF 4 Reserved	-	See file: Sig GPS Navigation model.csv
T _{GD}	sec	See file: Sig GPS Navigation model.csv
t _{oc}	sec	See file: Sig GPS Navigation model.csv
af ₂	sec/sec ²	See file: Sig GPS Navigation model.csv
af ₁	sec/sec	See file: Sig GPS Navigation model.csv
af ₀	sec	See file: Sig GPS Navigation model.csv
C _{rs}	meters	See file: Sig GPS Navigation model.csv
Δn	semi-circles/sec	See file: Sig GPS Navigation model.csv
M ₀	semi-circles	See file: Sig GPS Navigation model.csv
C _{uc}	radians	See file: Sig GPS Navigation model.csv
e	-	See file: Sig GPS Navigation model.csv
C _{us}	radians	See file: Sig GPS Navigation model.csv
(A) ^{1/2}	meters ^{1/2}	See file: Sig GPS Navigation model.csv
t _{oe}	sec	See file: Sig GPS Navigation model.csv
Fit Interval Flag		See file: Sig GPS Navigation model.csv
AODO	sec	See file: Sig GPS Navigation model.csv
C _{ic}	radians	See file: Sig GPS Navigation model.csv
OMEGA ₀	semi-circles	See file: Sig GPS Navigation model.csv
C _{is}	radians	See file: Sig GPS Navigation model.csv
i ₀	semi-circles	See file: Sig GPS Navigation model.csv
C _{rc}	meters	See file: Sig GPS Navigation model.csv
ω	semi-circles	See file: Sig GPS Navigation model.csv
OMEGAdot	semi-circles/sec	See file: Sig GPS Navigation model.csv
Idot	semi-circles/sec	See file: Sig GPS Navigation model.csv

Assistance Data GPS Ionospheric Model

GPS Ionospheric Model

Information Element	Units	Value/remark
α ₀	seconds	4.6566129 10E-9
α ₁	sec/semi-circle	1.4901161 10E-8
α ₂	sec/(semi-circle) ²	-5.96046 10E-8
α ₃	sec/(semi-circle) ³	-5.96046 10E-8
β ₀	seconds	79872
β ₁	sec/semi-circle	65536
β ₂	sec/(semi-circle) ²	-65536
β ₃	sec/(semi-circle) ³	-393216

Assistance Data GPS UTC model

GPS UTC Model

Information Element	Units	Value/remark
A ₁	sec/sec	0
A ₀	seconds	0
t _{ot}	seconds	249856
WN _t	weeks	133
Δt _{LS}	seconds	15
WN _{LSF}	weeks	158
DN	days	7
Δt _{LSF}	seconds	16

Assistance Data GPS Almanac

GPS Almanac (Fields occurring once per message)

Information Element	Units	Value/remark	Release
WN _a	weeks	1669	
Complete Almanac Provided		TRUE	Rel-10 onwards

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	31

GPS Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark
DataID	-	See file: Sig GPS Almanac.csv
SatID	-	PRNs: 1, 2, 3...21, 22, 23, 25, 26, 27...30, 31, 32
e	dimensionless	See file: Sig GPS Almanac.csv
t _{oa}	sec	See file: Sig GPS Almanac.csv
δi	semi-circles	See file: Sig GPS Almanac.csv
OMEGADOT	semi-circles/sec	See file: Sig GPS Almanac.csv
SV Health		See file: Sig GPS Almanac.csv
A ^{1/2}	meters ^{1/2}	See file: Sig GPS Almanac.csv
OMEGA ₀	semi-circles	See file: Sig GPS Almanac.csv
M ₀	semi-circles	See file: Sig GPS Almanac.csv
ω	semi-circles	See file: Sig GPS Almanac.csv
af ₀	seconds	See file: Sig GPS Almanac.csv
af ₁	sec/sec	See file: Sig GPS Almanac.csv

Assistance Data GPS Acquisition Assistance

GPS Acquisition Assist - Information Elements appearing once per message

Information Element	Units	Value/remark
GPS TOW msec	msec	1860000 ms. Start time. Add integer number of 1 seconds as required. (Note)
UE Positioning GPS Reference Time Uncertainty		125 (2.127 seconds)
Note: GPS TOW msec This is the value of GPS TOW msec when the GNSS scenario is started in the GNSS simulator. The value of GPS TOW msec to be used in the Acquisition Assistance IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. In the case that the (hardware) GPS simulator is switched off or not present then the value of GPS TOW msec given above may be used.		

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GPS Acquisition Assist - Information Elements appearing once per satellite

Information Element	Units	Value/remark	Release
SatID	-	PRNs: 1, 11, 17, 20, 23, 28.	
Doppler (0 th order term)	Hz	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Doppler (1 st order term)	Hz/s	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Doppler Uncertainty	Hz	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Code Phase	chips	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Integer Code Phase	-	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
GPS Bit number	-	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Code Phase Search Window	chips	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Azimuth	Degrees	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Elevation	Degrees	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. See file: Sig GPS Acquisition assist .csv (Note)	Rel-10 onwards
Note: This field is "Time varying" and its value depends on the "current GPS TOW msec". The value of this field to be used shall be determined by taking the "current GPS TOW msec" value and selecting the field value in the Sig GPS Acquisition assist.csv file corresponding to the value of "current GPS TOW msec".			

Assistance Data GANSS reference time

GANSS reference time: sub-test 1

Information Element	Units	Value/remark	Release
GANSS Day		5844	
GANSS Day Cycle Number		0	Rel-10 onwards
GANSS TOD	Seconds	12645 s. Start time. Add integer number of 1 seconds as required. (Note)	
GANSS TOD Uncertainty		125 (2.127 seconds)	
GANSS Time ID		2 (GLONASS)	
Note: GANSS TOD This is the value of GANSS TOD when the GNSS scenario is started in the GNSS simulator. The value of GANSS TOD to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This "current GANSS TOD" is then also used to determine the value of any other Information Elements marked as "Time varying" in subclause 6.1.3.3. In the case that the (hardware) GNSS simulator is switched off or not present then the value of GANSS TOD given above may be used.			

GANSS reference time: sub-test 2

Information Element	Units	Value/remark	Release
GANSS Day		4515	
GANSS Day Cycle Number		0	Rel-10 onwards
GANSS TOD	Seconds	1860. Start time. Add integer number of 1 seconds as required. (Note)	
GANSS TOD Uncertainty		125 (2.127 seconds)	
GANSS Time ID		Not present (Galileo)	
Note: GANSS TOD This is the value of GANSS TOD when the GNSS scenario is started in the GNSS simulator. The value of GANSS TOD to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This "current GANSS TOD" is then also used to determine the value of any other Information Elements marked as "Time varying" in subclause 6.1.3.3. In the case that the (hardware) GNSS simulator is switched off or not present then the value of GANSS TOD given above may be used.			

GANSS reference time: sub-test 9

Information Element	Units	Value/remark	Release
GANSS Day		2191	
GANSS Day Cycle Number		0	Rel-12 onwards
GANSS TOD	Seconds	1846. Start time. Add integer number of 1 second as required. (Note)	
GANSS TOD Uncertainty		125 (2.127 seconds)	
GANSS Time ID		3 (BDS system time)	
Note: GANSS TOD This is the value of GANSS TOD when the GNSS scenario is started in the GNSS simulator. The value of GANSS TOD to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This "current GANSS TOD" is then also used to determine the value of any other Information Elements marked as "Time varying" in subclause 6.1.3.3. In the case that the (hardware) GNSS simulator is switched off or not present then the value of GANSS TOD given above may be used.			

Assistance Data GANSS reference UE position

GANSS reference UE position

Information Element	Units	Value/remark
Latitude sign		0
Degrees Of Latitude	degrees	35.744287

Degrees Of Longitude	degrees	139.680176
Altitude Direction		0
Altitude	m	300
Uncertainty semi-major	m	3000
Uncertainty semi-minor	m	3000
Orientation of major axis	degrees	0
Uncertainty Altitude	m	500
Confidence	%	68

Assistance Data GANSS ionospheric model

GANSS ionospheric model

Information Element	Units	Value/remark
a _{i0}		64.4
a _{i1}		0
a _{i2}		0
Storm Flag 1		0
Storm Flag 2		0
Storm Flag 3		0
Storm Flag 4		0
Storm Flag 5		0

Assistance Data GANSS additional ionospheric model

GANSS additional ionospheric model (QZSS)

Information Element	Units	Value/remark
Data Id		00
α_0	Seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	Seconds	79872
β_1	sec/semi-circle	65536
β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

GANSS additional ionospheric model (BDS)

Information Element	Units	Value/remark
Data Id		01
α_0	Seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	Seconds	79872
β_1	sec/semi-circle	65536
β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

Assistance Data GANSS time model

GANSS time model (GLONASS)

Information Element	Units	Value/remark	Release
GANSS Time Model Reference Time	s	1860 (s)	
T _{A0}	Seconds	0	
GNSS_TO_ID		0 (GPS)	
Delta_T	Seconds	15	Rel-10 onwards

GANSS time model (Galileo)

Information Element	Units	Value/remark	Release
GANSS Time Model Reference Time	s	1860 (s)	
T _{A0}	Seconds	0	
GNSS_TO_ID		0 (GPS)	
Delta_T	Seconds	0	Rel-10 onwards

GANSS time model (BDS)

Information Element	Units	Value/remark	Release
GANSS Time Model Reference Time	s	1860 (s)	
T _{A0}	Seconds	0	
GNSS_TO_ID		0 (GPS)	
Delta_T	Seconds	13	Rel-12 onwards

Assistance Data GANSS navigation model

GANSS navigation model (Galileo)

Information Element	Units	Value/remark
Non-Broadcast Indication		Not present

Satellite Information (Galileo)

Information Element	Units	Value/remark
Number of satellites	-	6

Satellite Information (Fields occurring once per satellite) (Galileo)

Information Element	Units	Value/remark
SatID		SV IDs: 5, 10, 11, 18, 19, 20
SV Health		0 (Note)
IOD		0 (Note)
Note: For consistency SV Health and IOD are also given in file: Sig GANSS Navigation model.csv		

GANSS Clock Model (Fields occurring once per satellite) (Galileo)

Information Element	Units	Value/remark
Satellite clock model		
t_{oc}	seconds	See file: Sig GANSS Navigation model.csv
a_{i2}	sec/sec ²	See file: Sig GANSS Navigation model.csv
a_{i1}	sec/sec	See file: Sig GANSS Navigation model.csv
a_{i0}	sec	See file: Sig GANSS Navigation model.csv
T_{GD}	sec	See file: Sig GANSS Navigation model.csv
SISA		See file: Sig GANSS Navigation model.csv
Model ID		See file: Sig GANSS Navigation model.csv

GANSS Orbit Model (Fields occurring once per satellite) (Galileo)

Information Element	Units	Value/remark
t_{oe}	seconds	See file: Sig GANSS Navigation model.csv
ω	semi-circles	See file: Sig GANSS Navigation model.csv
Δn	semi-circles/sec	See file: Sig GANSS Navigation model.csv
M_0	semi-circles	See file: Sig GANSS Navigation model.csv
OMEGAdot	semi-circles/sec	See file: Sig GANSS Navigation model.csv
e		See file: Sig GANSS Navigation model.csv
ldot	semi-circles/sec	See file: Sig GANSS Navigation model.csv
sqrtA	meters ^{1/2}	See file: Sig GANSS Navigation model.csv
i_0	semi-circles	See file: Sig GANSS Navigation model.csv
OMEGA ₀	semi-circles	See file: Sig GANSS Navigation model.csv
C_{rs}	meters	See file: Sig GANSS Navigation model.csv
C_{is}	radians	See file: Sig GANSS Navigation model.csv
C_{us}	radians	See file: Sig GANSS Navigation model.csv
C_{rc}	meters	See file: Sig GANSS Navigation model.csv
C_{ic}	radians	See file: Sig GANSS Navigation model.csv
C_{uc}	radians	See file: Sig GANSS Navigation model.csv

Assistance Data GANSS additional navigation models

GANSS additional navigation models (GLONASS)

Information Element	Units	Value/remark
Non-Broadcast Indication		Not present

Satellite Information (GLONASS)

Information Element	Units	Value/remark
Number of satellites	-	6

Satellite Information (Fields occurring once per satellite) (GLONASS)

Information Element	Units	Value/remark
SatID		Slot Numbers: 3, 4, 9, 10, 18, 20
SV Health		000000 (Note)
IOD		225 (Note)
Note: For consistency SV Health and IOD are also given in file: Sig GANSS Additional Navigation model.csv		

GANSS additional Clock Models (Fields occurring once per satellite) (GLONASS)

Information Element	Units	Value/remark
GLONASS Satellite Clock Model		
$\tau_n(t_b)$	seconds	See file: Sig GANSS Additional Navigation model.csv
$\gamma_n(t_b)$		See file: Sig GANSS Additional Navigation model.csv
$\Delta\tau_n$	seconds	See file: Sig GANSS Additional Navigation model.csv

GANSS additional orbit models (Fields occurring once per satellite) (GLONASS)

Information Element	Units	Value/remark
GLONASS Earth-Centered, Earth-fixed Parameters		
E_n	days	See file: Sig GANSS Additional Navigation model.csv
P1	minutes	See file: Sig GANSS Additional Navigation model.csv
P2		See file: Sig GANSS Additional Navigation model.csv
M		See file: Sig GANSS Additional Navigation model.csv
$x_n(t_b)$	kilometers	See file: Sig GANSS Additional Navigation model.csv
$\dot{x}_n(t_b)$	kilometers/sec	See file: Sig GANSS Additional Navigation model.csv
$\ddot{x}_n(t_b)$	kilometers/sec ²	See file: Sig GANSS Additional Navigation model.csv
$y_n(t_b)$	kilometers	See file: Sig GANSS Additional Navigation model.csv
$\dot{y}_n(t_b)$	kilometers/sec	See file: Sig GANSS Additional Navigation model.csv
$\ddot{y}_n(t_b)$	kilometers/sec ²	See file: Sig GANSS Additional Navigation model.csv
$z_n(t_b)$	kilometers	See file: Sig GANSS Additional Navigation model.csv
$\dot{z}_n(t_b)$	kilometers/sec	See file: Sig GANSS Additional Navigation model.csv
$\ddot{z}_n(t_b)$	kilometers/sec ²	See file: Sig GANSS Additional Navigation model.csv

GANSS additional navigation model (BDS)

Information Element	Units	Value/remark
Non-Broadcast Indication		Not present

Satellite Information (BDS)

Information Element	Units	Value/remark
Number of satellites	-	6

Satellite Information (Fields occurring once per satellite) (BDS)

Information Element	Units	Value/remark
SatID		SV IDs: 1, 2, 7, 18, 21, 27
SV Health		0 (Note)
IOD		0 (Note)
Note: For consistency SV Health and IOD are also given in file: Sig GANSS Navigation model.csv		

GANSS additional Clock Model (Fields occurring once per satellite) (BDS)

Information Element	Units	Value/remark
Satellite clock model		
AODC		See file: Sig GANSS Additional Navigation model subtest 9_10.csv
t_{oc}	seconds	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
a_0	sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
a_1	sec/sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
a_2	sec/sec ²	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
T_{GD1}	sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv

GANSS additional Orbit Models (Fields occurring once per satellite) (BDS)

Information Element	Units	Value/remark
AODE		See file: Sig GANSS Additional Navigation model subtest 9_10.csv
URA Index		See file: Sig GANSS Additional Navigation model subtest 9_10.csv
t_{oe}	seconds	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
$A^{1/2}$	meters ^{1/2}	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
e		See file: Sig GANSS Additional Navigation model subtest 9_10.csv
ω	semi-circles	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
Δn	semi-circles/sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
M_0	semi-circles	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
Ω_0	semi-circles	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
Ω_{dot}	semi-circles/sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
i_0	semi-circles	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
i_{dot}	semi-circles/sec	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{uc}	radians	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{us}	radians	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{rc}	meters	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{rs}	meters	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{ic}	radians	See file: Sig GANSS Additional Navigation model subtest 9_10.csv
C_{is}	radians	See file: Sig GANSS Additional Navigation model subtest 9_10.csv

Assistance Data GANSS reference measurement information

GANSS reference measurement information: sub-test 1, 4 (Fields occurring once per message)

Information Element	Units	Value/remark
GANSS Signal ID		Not present

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GANSS reference measurement information: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark	Release
SatID		Slot Numbers: 3, 4, 9, 10, 18, 20	
Doppler (0 th order term)	m/s	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Code Phase Search Window		Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Azimuth	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Elevation	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest1_4.csv (Note)	Rel-10 onwards
<p>Note:</p> <p>For sub-test 1: this field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Sig GANSS reference measurement information subtest1_4.csv file corresponding to the value of "current GANSS TOD".</p> <p>For sub-test 4: this field is "Time varying" and its value depends on the "current GPS TOW msec". The value of this field to be used shall be determined by taking the "current GPS TOW msec" value and selecting the field value in the Sig GANSS reference measurement information subtest1_4.csv file corresponding to the value of "current GPS TOW msec".</p>			

GANSS reference measurement information: sub-test 2, 8 (Fields occurring once per message)

Information Element	Units	Value/remark
GANSS Signal ID		Not present

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GANSS reference measurement information: sub-test 2, 8 (Fields occurring once per satellite)

Information Element	Units	Value/remark	Release
SatID		SV IDs: 5, 10, 11, 18, 19, 20.	
Doppler (0 th order term)	m/s	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Code Phase Search Window		Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Azimuth	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Elevation	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest2.csv (Note)	Rel-10 onwards
Note: This field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Sig GANSS reference measurement information subtest2.csv file corresponding to the value of "current GANSS TOD".			

GANSS reference measurement information: sub-test 9, 10 (Fields occurring once per message)

Information Element	Units	Value/remark
GANSS Signal ID		Not present

Satellite Information

Information Element	Units	Value/remark
Number of satellites	-	6

GANSS reference measurement information: sub-test 9, 10 (Fields occurring once per satellite)

Information Element	Units	Value/remark	Release
SatID		SV IDs: 1, 2, 7, 18, 21, 27.	
Doppler (0 th order term)	m/s	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Code Phase Search Window		Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Azimuth	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Elevation	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	Rel-12 onwards
Elevation LSB	Degrees	Time varying. See file: Sig GANSS reference measurement information subtest9.csv (Note)	Rel-12 onwards
Note: This field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Sig GANSS reference measurement information subtest9.csv file corresponding to the value of "current GANSS TOD".			

Assistance Data GANSS almanac

GANSS almanac: sub-test 1, 4 (Fields occurring once per message)

Information Element	Units	Value/remark
Week Number	Weeks	N/A

Satellite Information GLO-KP: sub-tests 1, 4

Information Element	Units	Value/remark
Number of satellites	-	24

GANSS almanac: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark
N^A	Days	See file: Sig GANSS Almanac subtest1_4.csv
n^A	-	Slot Numbers: 1, 2, 322, 23, 24
H_n^A	-	See file: Sig GANSS Almanac subtest1_4.csv
λ_n^A	semi-circles	See file: Sig GANSS Almanac subtest1_4.csv
$t_{\lambda_n}^A$	seconds	See file: Sig GANSS Almanac subtest1_4.csv
Δi_n^A	semi-circles	See file: Sig GANSS Almanac subtest1_4.csv
ΔT_n^A	sec/orbit period	See file: Sig GANSS Almanac subtest1_4.csv
$\Delta T_DOT_n^A$	sec/orbit period ²	See file: Sig GANSS Almanac subtest1_4.csv
ϵ_n^A		See file: Sig GANSS Almanac subtest1_4.csv
ω_n^A	semi-circles	See file: Sig GANSS Almanac subtest1_4.csv
τ_n^A	seconds	See file: Sig GANSS Almanac subtest1_4.csv
C_n^A		See file: Sig GANSS Almanac subtest1_4.csv
M_n^A		See file: Sig GANSS Almanac subtest1_4.csv

GANSS almanac: sub-test 2, 8 (Fields occurring once per message)

Information Element	Units	Value/remark	Release
Week Number	Weeks	645	
Complete Almanac Provided		TRUE	Rel-10 onwards

GANSS almanac: sub-test 2, 8 (Field occurring once per message)

Information Element	Units	Value/remark
T_{oa}		147000
IOD_a		0

Satellite Information KP: sub-test 2, 8

Information Element	Units	Value/remark
Number of satellites	-	30

GANSS almanac: sub-test 2, 8 (Fields occurring once per satellite)

Information Element	Units	Value/remark
SV ID		SV IDs: 1, 2, 3, ..., 29, 30
e		See file: Sig GANSS Almanac subtest2.csv
δi	semi-circles	See file: Sig GANSS Almanac subtest2.csv
OMEGADOT	semi-circles/sec	See file: Sig GANSS Almanac subtest2.csv
SV Health KP		See file: Sig GANSS Almanac subtest2.csv
$\delta A^{1/2}$	meters ^{1/2}	See file: Sig GANSS Almanac subtest2.csv
Ω_0	semi-circles	See file: Sig GANSS Almanac subtest2.csv
M_0	semi-circles	See file: Sig GANSS Almanac subtest2.csv
ω	semi-circles	See file: Sig GANSS Almanac subtest2.csv
af_0	Seconds	See file: Sig GANSS Almanac subtest2.csv
af_1	sec/sec	See file: Sig GANSS Almanac subtest2.csv

GANSS almanac: sub-test 9, 10 (Fields occurring once per message)

Information Element	Units	Value/remark	Release
Week Number	Weeks	313	
Complete Almanac Provided		TRUE	Rel-12 onwards

GANSS almanac: sub-test 9, 10 (Field occurring once per message)

Information Element	Units	Value/remark
T_{oa}		147456
IOD_a		0

Satellite Information KP: sub-test 9, 10

Information Element	Units	Value/remark
Number of satellites	-	30

GANSS almanac: sub-test 9, 10 (Fields occurring once per satellite)

Information Element	Units	Value/remark
SV ID		SV IDs: 1, 2, 3, ..., 29, 30
e		See file: Sig GANSS Almanac subtest9.csv
δi	semi-circles	See file: Sig GANSS Almanac subtest9.csv
OMEGADOT	semi-circles/sec	See file: Sig GANSS Almanac subtest9.csv
SV Health KP		See file: Sig GANSS Almanac subtest9.csv
delta A ^{1/2}	meters ^{1/2}	See file: Sig GANSS Almanac subtest9.csv
OMEGA ₀	semi-circles	See file: Sig GANSS Almanac subtest9.csv
M ₀	semi-circles	See file: Sig GANSS Almanac subtest9.csv
ω	semi-circles	See file: Sig GANSS Almanac subtest9.csv
a ₀	Seconds	See file: Sig GANSS Almanac subtest9.csv
a ₁	sec/sec	See file: Sig GANSS Almanac subtest9.csv

Assistance Data GANSS auxiliary information

GANSS auxiliary information: sub-test 1, 4 (Fields occurring once per message)

Information Element	Units	Value/remark
GANSS-ID-3		Present (GLONASS)

Aux Info List: sub-test 1, 4

Information Element	Units	Value/remark
Number of satellites	-	6

GANSS auxiliary information: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark
Sat ID		Slot Numbers: 3, 4, 9, 10, 18, 20
Signals Available		G1
Channel Number		5, 6, -2, -7, -3, 2

GANSS auxiliary information: sub-test 3 (Fields occurring once per message)

Information Element	Units	Value/remark
GANSS-ID-1		Present (Modernized GPS)

Aux Info List: sub-test 3

Information Element	Units	Value/remark
Number of satellites	-	6

GANSS auxiliary information: sub-test 3 (Fields occurring once per satellite)

Information Element	Units	Value/remark
Sat ID		PRNs: 1, 11, 17, 20, 23, 28
Signals Available		L1C and others as supported by the UE

Assistance Data GANSS ID

GANSS ID: sub-test 1, 4

Information Element	Units	Value/remark
GANSS ID		3 (GLONASS)

GANSS ID: sub-test 2, 8

Information Element	Units	Value/remark
GANSS ID		Not present (Galileo)

GANSS ID: sub-test 3

Information Element	Units	Value/remark
GANSS ID		1 (Modernized GPS)

GANSS ID: sub-test 9, 10

Information Element	Units	Value/remark
GANSS ID		4 (BDS)

6.1.3.3 Default Assistance Data for TS 37.571-2 subclause 7

This subclause defines the GNSS assistance data elements which shall be provided to the UE in certain tests in TS 37.571-2 [7] subclause 7 in the LPP Provide Assistance Data messages in the absence of a corresponding LPP Request Assistance Data message. The GNSS assistance data provided depends on the mode being used in the test case, the assistance data supported by the UE and the GNSS(s) supported by the UE. GNSS assistance data IEs not supported by the UE shall not be sent. GNSS assistance data IEs supported by the UE but not listed below shall not be sent.

Table 6.1.3.3-1: Default GNSS assistance data to be provided to the UE

GNSS Assistance Data IE supported by UE	Mode used in test case		
	UE-based	UE-assisted. GNSS-Acquisition Assistance supported by UE	UE-assisted. GNSS-Acquisition Assistance not supported by UE
GNSS-Reference Time	Yes	Yes	Yes
GNSS-ReferenceLocation	Yes	No	Yes
GNSS-IonosphericModel	Yes	No	No
GNSS-TimeModelList	Yes for sub-test 4, 8, 10	No	Yes for sub-test 4, 8, 10
GNSS-NavigationModel	Yes	No	Yes
GNSS-AcquisitionAssistance	No	Yes	No
GNSS-Almanac	No	No	Yes
GNSS-UTC-Model	Yes for sub-test 4	Yes for sub-test 4	Yes for sub-test 4
GNSS-AuxiliaryInformation	Yes for sub-tests 2, 4. Note.	Yes for sub-tests 2, 4. Note.	Yes for sub-tests 2, 4. Note.

Note: Also if UE supports multiple signals per GNSS

6.1.3.4 Assistance Data values for TS 37.571-2 subclause 7

Where assistance data is required on a per-satellite basis, or where the values of the data also varies with time it is specified in comma-separated-variable files in the GNSS data zip file specified in Annex B. These files specify the values to be used for each satellite, indexed by satellite SV ID, and, where applicable, the values to be used indexed by both time and satellite SV ID.

Assistance data that is marked as “time varying” and the gnss-TimeOfDay field are only specified and used in 1 second increments. Interpolation between these values shall not be used.

The accuracy of the gnss-TimeOfDay and assistance data that is marked as “time varying” in the provided assistance data shall be within +/- 2 s relative to the GNSS time in the system simulator. In the case that assistance data is required but satellite signals are not required then this clause does not apply.

Assistance data Information Elements and fields that are not specified shall not be used.

The information elements detailed below are fully defined in 3GPP TS 36.355 [8]

GNSS REFERENCE TIME:

GNSS-ReferenceTime: sub-tests 1, 4, 8, 10

Information Element	Units	Value/remark
gnss-SystemTime		
gnss-TimeID		0 (gps)
gnss-DayNumber		11683
gnss-TimeOfDay		1860 s. Start time. Add integer number of 1 seconds as required. (Note)
gnss-TimeOfDayFrac-msec		Not present
notificationOfLeapSecond		Not present
gps-TOW-Assist		
satelliteID		PRNs: 1, 11, 17, 20, 23, 28.
tlmWord		10922 (for all PRNs)
antiSpoof		1 (for all PRNs)
alert		0 (for all PRNs)
tlmRsvdBits		2 (for all PRNs)
referenceTimeUnc		'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Not present
<p>Note: gnss-TimeOfDay</p> <p>This is the value of gnss-TimeOfDay when the GNSS scenario is started in the GNSS simulator. The value of gnss-TimeOfDay to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This “current gnss-TimeOfDay” is then also used to determine the value of any other Information Elements marked as “Time varying” in subclause 6.1.3.4. In the case that the (hardware) GNSS simulator is switched off or not present then the value of gnss-TimeOfDay given above may be used.</p>		

GNSS-ReferenceTime: sub-test 2

Information Element	Units	Value/remark
gnss-SystemTime		
gnss-TimeID		4 (glonass)
gnss-DayNumber		5844
gnss-TimeOfDay		12645 s. Start time. Add integer number of 1 seconds as required. (Note)
gnss-TimeOfDayFrac-msec		Not present
notificationOfLeapSecond		00
gps-TOW-Assist		Not present
referenceTimeUnc		'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Not present
<p>Note: gnss-TimeOfDay</p> <p>This is the value of gnss-TimeOfDay when the GNSS scenario is started in the GNSS simulator. The value of gnss-TimeOfDay to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This “current gnss-TimeOfDay” is then also used to determine the value of any other Information Elements marked as “Time varying” in subclause 6.1.3.4. In the case that the (hardware) GNSS simulator is switched off or not present then the value of gnss-TimeOfDay given above may be used.</p>		

GNSS-ReferenceTime: sub-test 3

Information Element	Units	Value/remark
gnss-SystemTime		
gnss-TimeID		3 (galileo)
gnss-DayNumber		4536
gnss-TimeOfDay		1860 s. Start time. Add integer number of 1 seconds as required. (Note)
gnss-TimeOfDayFrac-msec		Not present
notificationOfLeapSecond		Not present
gps-TOW-Assist		Not present
referenceTimeUnc		'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Not present
<p>Note: gnss-TimeOfDay</p> <p>This is the value of gnss-TimeOfDay when the GNSS scenario is started in the GNSS simulator. The value of gnss-TimeOfDay to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This "current gnss-TimeOfDay" is then also used to determine the value of any other Information Elements marked as "Time varying" in subclause 6.1.3.4. In the case that the (hardware) GNSS simulator is switched off or not present then the value of gnss-TimeOfDay given above may be used.</p>		

GNSS-ReferenceTime: sub-test 9

Information Element	Units	Value/remark
gnss-SystemTime		
gnss-TimeID		5 (bds)
gnss-DayNumber		2191
gnss-TimeOfDay		1847 s. Start time. Add integer number of 1 seconds as required. (Note)
gnss-TimeOfDayFrac-msec		Not present
notificationOfLeapSecond		Not present
gps-TOW-Assist		Not present
referenceTimeUnc		'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Not present
<p>Note: gnss-TimeOfDay</p> <p>This is the value of gnss-TimeOfDay when the GNSS scenario is started in the GNSS simulator. The value of gnss-TimeOfDay to be used in the Reference Time IE shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value, rounded up to the next 1 second interval. This "current gnss-TimeOfDay" is then also used to determine the value of any other Information Elements marked as "Time varying" in subclause 6.1.3.4. In the case that the (hardware) GNSS simulator is switched off or not present then the value of gnss-TimeOfDay given above may be used.</p>		

GNSS REFERENCE LOCATION:**GNSS-ReferenceLocation**

Information Element	Units	Value/remark
threeDlocation		
latitudeSign		0
degreesLatitude	degrees	35.744287
degreesLongitude	degrees	139.680176
altitudeDirection		0
altitude	m	300
uncertaintySemiMajor	m	3000
uncertaintySemiMinor	m	3000
orientationMajorAxis	degrees	0
uncertaintyAltitude	m	500
confidence	%	68

GNSS IONOSPHERIC MODEL:

GNSS-IonosphericModel: sub-tests 1, 2, 4, 9, 10

Information Element	Units	Value/remark
klobucharModel		
datalD		00
alfa0	seconds	4.6566129 10E-9
alfa1	sec/semi-circle	1.4901161 10E-8
alfa2	sec/(semi-circle) ²	-5.96046 10E-8
alfa3	sec/(semi-circle) ³	-5.96046 10E-8
beta0	seconds	79872
beta1	sec/semi-circle	65536
beta2	sec/(semi-circle) ²	-65536
beta3	sec/(semi-circle) ³	-393216
neQuickModel		Not present

GNSS-IonosphericModel: sub-test 3

Information Element	Units	Value/remark
GNSS-IonospericModel		
klobucharModel		Not present
neQuickModel		
ai0		64.4
ai1		0
ai2		0
ionoStormFlag1		0
ionoStormFlag2		0
ionoStormFlag3		0
ionoStormFlag4		0
ionoStormFlag5		0

GNSS TIME MODEL:

GNSS-TimeModelList: sub-test 4

Information Element	Units	Value/remark
gnss-TimeModelRefTime	seconds	1860 (s)
tA0		0
gnss-TO-ID		1 (GPS)
weekNumber		1669
deltaT		15

GNSS-TimeModelList: sub-test 8

Information Element	Units	Value/remark
gnss-TimeModelRefTime	Seconds	1860 (s)
tA0		0
gnss-TO-ID		1 (GPS)
weekNumber		1669
deltaT		0

GNSS-TimeModelList: sub-test 10

Information Element	Units	Value/remark
gnss-TimeModelRefTime	seconds	1860 (s)
tA0		0
gnss-TO-ID		1 (GPS)
weekNumber		1669
deltaT		13

GNSS NAVIGATION MODEL:

GNSS-NavigationModel: sub-test 1

Information Element	Units	Value/remark
nonBroadcastFlag		0
gnss-SatelliteList		(SIZE) 6

GNSS-NavModelSatelliteElement: sub-test 1

Information Element	Units	Value/remark
svID		PRNs: 1, 11, 17, 20, 23, 28
svHealth		0
iod		0
gnss-ClockModel		
nav-ClockModel		
navToc		See file: Sig GNSS Navigation Model subtest1.csv
navaf2		See file: Sig GNSS Navigation Model subtest1.csv
navaf1		See file: Sig GNSS Navigation Model subtest1.csv
navaf0		See file: Sig GNSS Navigation Model subtest1.csv
navTgd		See file: Sig GNSS Navigation Model subtest1.csv
gnss-OrbitModel		
nav-KeplerianSet		
navURA		See file: Sig GNSS Navigation Model subtest1.csv
navFitFlag		See file: Sig GNSS Navigation Model subtest1.csv
navToe		See file: Sig GNSS Navigation Model subtest1.csv
navOmega		See file: Sig GNSS Navigation Model subtest1.csv
navDeltaN		See file: Sig GNSS Navigation Model subtest1.csv
navM0		See file: Sig GNSS Navigation Model subtest1.csv
navOmegaADot		See file: Sig GNSS Navigation Model subtest1.csv
navE		See file: Sig GNSS Navigation Model subtest1.csv
navIDot		See file: Sig GNSS Navigation Model subtest1.csv
navAPowerHalf		See file: Sig GNSS Navigation Model subtest1.csv
navI0		See file: Sig GNSS Navigation Model subtest1.csv
navOmegaA0		See file: Sig GNSS Navigation Model subtest1.csv
navCrs		See file: Sig GNSS Navigation Model subtest1.csv
navCis		See file: Sig GNSS Navigation Model subtest1.csv
navCus		See file: Sig GNSS Navigation Model subtest1.csv
navCrc		See file: Sig GNSS Navigation Model subtest1.csv
navCic		See file: Sig GNSS Navigation Model subtest1.csv
navCuc		See file: Sig GNSS Navigation Model subtest1.csv
addNAVparam		
ephemCodeOnL2		See file: Sig GNSS Navigation Model subtest1.csv
ephemL2Pflag		See file: Sig GNSS Navigation Model subtest1.csv
reserved1		See file: Sig GNSS Navigation Model subtest1.csv
reserved2		See file: Sig GNSS Navigation Model subtest1.csv
reserved3		See file: Sig GNSS Navigation Model subtest1.csv
reserved4		See file: Sig GNSS Navigation Model subtest1.csv
ephemAODA		See file: Sig GNSS Navigation Model subtest1.csv

GNSS-NavigationModel: sub-test 2

Information Element	Units	Value/remark
nonBroadcastFlag		0
gnss-SatelliteList		(SIZE) 6

GNSS-NavModelSatelliteElement: sub-test 2

Information Element	Units	Value/remark
svID		Slot Numbers: 3, 4, 9, 10, 18, 20
svHealth		00000000
iod		225
gnss-ClockModel		
glonass-ClockModel		
gloTau		See file: Sig GNSS Navigation Model subtest2.csv
gloGamma		See file: Sig GNSS Navigation Model subtest2.csv
gloDeltaTau		See file: Sig GNSS Navigation Model subtest2.csv
gnss-OrbitModel		
glonass-ECEF		
gloEn		See file: Sig GNSS Navigation Model subtest2.csv
gloP1		See file: Sig GNSS Navigation Model subtest2.csv
gloP2		See file: Sig GNSS Navigation Model subtest2.csv
glom		See file: Sig GNSS Navigation Model subtest2.csv
gloX		See file: Sig GNSS Navigation Model subtest2.csv
gloXdot		See file: Sig GNSS Navigation Model subtest2.csv
gloXdotdot		See file: Sig GNSS Navigation Model subtest2.csv
gloY		See file: Sig GNSS Navigation Model subtest2.csv
gloYdot		See file: Sig GNSS Navigation Model subtest2.csv
gloYdotdot		See file: Sig GNSS Navigation Model subtest2.csv
gloZ		See file: Sig GNSS Navigation Model subtest2.csv
gloZdot		See file: Sig GNSS Navigation Model subtest2.csv
gloZdotdot		See file: Sig GNSS Navigation Model subtest2.csv

GNSS-NavigationModel: sub-test 3

Information Element	Units	Value/remark
nonBroadcastFlag		0
gnss-SatelliteList		(SIZE) 6

GNSS-NavModelSatelliteElement: sub-test 3

Information Element	Units	Value/remark
svID		SV IDs: 5, 10, 11, 18, 19, 20
svHealth		0
iod		0
gnss-ClockModel		
standardClockModelList		(SIZE) 1
stanClockToc		See file: Sig GNSS Navigation Model subtest3.csv
stanClockAF2		See file: Sig GNSS Navigation Model subtest3.csv
stanClockAF1		See file: Sig GNSS Navigation Model subtest3.csv
stanClockAF0		See file: Sig GNSS Navigation Model subtest3.csv
stanClockTgd		See file: Sig GNSS Navigation Model subtest3.csv
sisa		See file: Sig GNSS Navigation Model subtest3.csv
gnss-OrbitModel		
keplerianSet		
keplerToe		See file: Sig GNSS Navigation Model subtest3.csv
keplerW		See file: Sig GNSS Navigation Model subtest3.csv
keplerDeltaN		See file: Sig GNSS Navigation Model subtest3.csv
keplerM0		See file: Sig GNSS Navigation Model subtest3.csv
keplerOmegaDot		See file: Sig GNSS Navigation Model subtest3.csv
keplerE		See file: Sig GNSS Navigation Model subtest3.csv
keplerIDot		See file: Sig GNSS Navigation Model subtest3.csv
keplerAPowerHalf		See file: Sig GNSS Navigation Model subtest3.csv
keplerI0		See file: Sig GNSS Navigation Model subtest3.csv
keplerOmega0		See file: Sig GNSS Navigation Model subtest3.csv
keplerCrs		See file: Sig GNSS Navigation Model subtest3.csv
keplerCis		See file: Sig GNSS Navigation Model subtest3.csv
keplerCus		See file: Sig GNSS Navigation Model subtest3.csv
keplerCrc		See file: Sig GNSS Navigation Model subtest3.csv
keplerCic		See file: Sig GNSS Navigation Model subtest3.csv
keplerCuc		See file: Sig GNSS Navigation Model subtest3.csv

GNSS-NavigationModel: sub-test 4

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 1
gnss-ID		4 (glonass)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 2

GNSS-NavigationModel: sub-test 8

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 1
gnss-ID		3 (galileo)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 3

GNSS-NavigationModel: sub-test 9

Information Element	Units	Value/remark
nonBroadcastFlag		0
gnss-SatelliteList		(SIZE) 6

GNSS-NavModelSatelliteElement: sub-test 9

Information Element	Units	Value/remark
svID		SV IDs: 1, 2, 7, 18, 21, 27
svHealth		0
iod		0
gnss-ClockModel		
BDS-ClockModel-r12		(SIZE) 1
bdsAODC-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsToc-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsA0-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsA1-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsA2-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsTgd1-r12		See file: Sig GNSS Navigation Model subtest9.csv
gnss-OrbitModel		
BDS-KeplerianSet-r12		
bdsAODE-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsURAI-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsToe-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsAPowerHalf-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsE-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsW-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsDeltaN-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsM0-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsOmega0-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsOmegaDot-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsI0-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsIDot-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCuc-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCus-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCrc-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCrs-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCic-r12		See file: Sig GNSS Navigation Model subtest9.csv
bdsCis-r12		See file: Sig GNSS Navigation Model subtest9.csv

GNSS-NavigationModel: sub-test 10

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 1
gnss-ID		5 (bds)
GNSS-NavigationModel		See GNSS-NavigationModel: sub-test 9

GNSS ACQUISITION ASSISTANCE:

GNSS-AcquisitionAssistance: sub-test 1

Information Element	Units	Value/remark
GNSS-AcquisitionAssistance		
gnss-SignalID		0 (GPS L1 C/A)
gnss-AcquisitionAssistList		(SIZE) 6
confidence-r10	%	98

GNSS-AcquisitionAssistElement: sub-test 1

Information Element	Units	Value/remark
svID		PRNs: 1, 11, 17, 20, 23, 28.
doppler0		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
doppler1		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
dopplerUncertainty		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
codePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
intCodePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
codePhaseSearchWindow		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
azimuth		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
elevation		Time varying. See file: Sig GNSS Acquisition Assistance subtest1.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Sig GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 2

Information Element	Units	Value/remark
GNSS-AcquisitionAssistance		
gnss-SignallD		0 (GLONASS G1)
gnss-AcquisitionAssistList		(SIZE) 6
confidence-r10	%	98

GNSS-AcquisitionAssistElement: sub-test 2

Information Element	Units	Value/remark
svID		Slot Numbers: 3, 4, 9, 10, 18, 20
doppler0		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
doppler1		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
dopplerUncertainty		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
codePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
intCodePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
codePhaseSearchWindow		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
azimuth		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
elevation		Time varying. See file: Sig GNSS Acquisition Assistance subtest2.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Sig GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 3

Information Element	Units	Value/remark
GNSS-AcquisitionAssistance		
gnss-SignalID		0 (Galileo E1)
gnss-AcquisitionAssistList		(SIZE) 6
confidence-r10	%	98

GNSS-AcquisitionAssistElement: sub-test 3

Information Element	Units	Value/remark
svID		SV IDs: 5, 10, 11, 18, 19, 20
doppler0		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
doppler1		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
dopplerUncertainty		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
codePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
intCodePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
codePhaseSearchWindow		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
azimuth		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
elevation		Time varying. See file: Sig GNSS Acquisition Assistance subtest3.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Sig GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 4

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 1
gnss-ID		4 (glonass)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 2

GNSS-AcquisitionAssistance: sub-test 8

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 1
gnss-ID		3 (galileo)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 3

GNSS-AcquisitionAssistance: sub-test 9

Information Element	Units	Value/remark
GNSS-AcquisitionAssistance		
gnss-SignalID		0 (BDS B1)
gnss-AcquisitionAssistList		(SIZE) 6
confidence-r10	%	98

GNSS-AcquisitionAssistElement: sub-test 9

Information Element	Units	Value/remark
svID		SV IDs: 1, 2, 7, 18, 21, 27
doppler0		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
doppler1		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
dopplerUncertainty		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
codePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
intCodePhase		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
codePhaseSearchWindow		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
azimuth		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
elevation		Time varying. See file: Sig GNSS Acquisition Assistance subtest9.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest9.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Sig GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 10

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 1
gnss-ID		5(bds)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 9

GNSS ALMANAC:

GNSS-Almanac: sub-test 1

Information Element	Units	Value/remark
GNSS-Almanac		
weekNumber		1669
toa		249856
ioda		Not present
completeAlmanacProvided		1 (TRUE)
gnss-AlmanacList		(SIZE) 31

GNSS-AlmanacElement: sub-test 1

Information Element	Units	Value/remark
keplerianNAV-Almanac		
svID		PRNs: 1, 2, 3 ...21, 22, 23, 25, 26, 27... 30, 31, 32
navAlmE		See file: Sig GNSS Almanac subtest1.csv
navAlmDeltal		See file: Sig GNSS Almanac subtest1.csv
navAlmOMEGADOT		See file: Sig GNSS Almanac subtest1.csv
navAlmSVHealth		See file: Sig GNSS Almanac subtest1.csv
navAlmSqrtA		See file: Sig GNSS Almanac subtest1.csv
navAlmOMEGAo		See file: Sig GNSS Almanac subtest1.csv
navAlmOmega		See file: Sig GNSS Almanac subtest1.csv
navAlmMo		See file: Sig GNSS Almanac subtest1.csv
navAlmaf0		See file: Sig GNSS Almanac subtest1.csv
navAlmaf1		See file: Sig GNSS Almanac subtest1.csv

GNSS-Almanac: sub-test 2

Information Element	Units	Value/remark
GNSS-Almanac		
completeAlmanacProvided		1 (TRUE)
gnss-AlmanacList		(SIZE) 24

GNSS-AlmanacElement: sub-test 2

Information Element	Units	Value/remark
keplerianGLONASS		
gloAlm-NA		See file: Sig GNSS Almanac subtest2.csv
gloAlmNA		Slot Numbers: 1, 2, 322, 23, 24
gloAlmHA		See file: Sig GNSS Almanac subtest2.csv
gloAlmLambdaA		See file: Sig GNSS Almanac subtest2.csv
gloAlmLambdaA		See file: Sig GNSS Almanac subtest2.csv
gloAlmDeltala		See file: Sig GNSS Almanac subtest2.csv
gloAlmDeltaTA		See file: Sig GNSS Almanac subtest2.csv
gloAlmDeltaTdotA		See file: Sig GNSS Almanac subtest2.csv
gloAlmEpsilonA		See file: Sig GNSS Almanac subtest2.csv
gloAlmOmegaA		See file: Sig GNSS Almanac subtest2.csv
gloAlmTauA		See file: Sig GNSS Almanac subtest2.csv
gloAlmCA		See file: Sig GNSS Almanac subtest2.csv
gloAlmMA		See file: Sig GNSS Almanac subtest2.csv

GNSS-Almanac: sub-test 3

Information Element	Units	Value/remark
GNSS-Almanac		
weekNumber		645
toa		147000
ioda		0
completeAlmanacProvided		1 (TRUE)
gnss-AlmanacList		(SIZE) 30

GNSS-AlmanacElement: sub-test 3

Information Element	Units	Value/remark
keplerianAlmanacSet		
svID		SV IDs: 1, 2, 3, ..., 30
kepAlmanacE		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacDeltal		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacOmegaDot		See file: Sig GNSS Almanac subtest3.csv
kepSVHealth		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacAPowerHalf		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacOmega0		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacW		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacM0		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacAF0		See file: Sig GNSS Almanac subtest3.csv
kepAlmanacAF1		See file: Sig GNSS Almanac subtest3.csv

GNSS-Almanac: sub-test 4

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-Almanac		See GNSS-Almanac: sub-test 1
gnss-ID		4 (glonass)
GNSS-Almanac		See GNSS-Almanac: sub-test 2

GNSS-Almanac: sub-test 8

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-Almanac		See GNSS-Almanac: sub-test 1
gnss-ID		3 (galileo)
GNSS-Almanac		See GNSS-Almanac: sub-test 3

GNSS-Almanac: sub-test 9

Information Element	Units	Value/remark
GNSS-Almanac		
weekNumber		313
toa		147456
ioda		0
completeAlmanacProvided		1 (TRUE)
gnss-AlmanacList		(SIZE) 30

GNSS-AlmanacElement: sub-test 9

Information Element	Units	Value/remark
BDS-AlmanacSet-r12		
svID		SV IDs: 1, 2, 3, ..., 29, 30
bdsAlmToa-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmSqrtA-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmE-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmW-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmM0-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmOmega0-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmOmegaDot-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmDeltal-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmA0-r12		See file: Sig GNSS Almanac subtest9.csv
bdsAlmA1-r12		See file: Sig GNSS Almanac subtest9.csv
bdsSvHealth-r12		See file: Sig GNSS Almanac subtest9.csv

GNSS-Almanac: sub-test 10

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-Almanac		See GNSS-Almanac: sub-test 1
gnss-ID		5 (bds)
GNSS-Almanac		See GNSS-Almanac: sub-test 9

GNSS UTC MODEL:

GNSS-UTC-Model: sub-test 4

Information Element	Units	Value/remark
GNSS-UTC-Model		
utcModel1		

UTC-ModelSet1: sub-test 4

Information Element	Units	Value/remark
gnss-Utc-A1		0
gnss-Utc-A0		0
gnss-Utc-Tot		249856
gnss-Utc-WNt		133
gnss-Utc-DeltaTIs		15
gnss-Utc-WNIsf		158
gnss-Utc-DN		7
gnss-Utc-DeltaTIsf		16

GNSS AUXILIARY INFORMATION:

GNSS-AuxiliaryInformation: sub-test 1 if UE supports multiple GPS signals

Information Element	Units	Value/remark
GNSS-AuxiliaryInformation		
gnss-ID-GPS		(SIZE) 6
svID		PRNs: 1, 11, 17, 20, 23, 28.
signalsAvailable		L1C and others as supported by the UE

GNSS-AuxiliaryInformation: sub-test 2

Information Element	Units	Value/remark
GNSS-AuxiliaryInformation		
gnss-ID-GLONASS		(SIZE) 6
svID		Slot Numbers: 3, 4, 9, 10, 18, 20
signalsAvailable		G1
channelNumber		5, 6, -2, -7, -3, 2

GNSS- AuxiliaryInformation: sub-test 4

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 1, or 2 if UE supports multiple GPS signals
gnss-ID		0 (gps) if UE supports multiple GPS signals
GNSS-AuxiliaryInformation		See GNSS-AuxiliaryInformation: sub-test 1
gnss-ID		4 (glonass)
GNSS-AuxiliaryInformation		See GNSS-AuxiliaryInformation: sub-test 2

GNSS GENERIC ASSISTANCE DATA

GNSS- GenericAssistData: sub-test 1

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		0 (gps)

GNSS- GenericAssistData: sub-test 2

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		4 (glonass)

GNSS- GenericAssistData: sub-test 3

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		3 (galileo)

GNSS- GenericAssistData: sub-test 4

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		4 (glonass)

GNSS- GenericAssistData: sub-test 8

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		3 (galileo)

GNSS- GenericAssistData: sub-test 9

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		5 (bds)

GNSS- GenericAssistData: sub-test 10

Information Element	Units	Value/remark
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		5 (bds)

6.2 GNSS Scenarios and Assistance Data for Assisted GNSS Minimum Performance tests

6.2.1 General

This subclause defines the GNSS scenarios and assistance data IEs which shall be available for use as specified in all UTRA and E-UTRA A-GNSS Minimum Performance test cases defined in TS 37.571-1 [6] subclauses 6 and 7.

Subclauses 6.2.2 and 6.2.3 list the assistance data IEs required for minimum performance testing of UE-based mode, and subclauses 6.2.4 and 6.2.5 list the assistance data available for minimum performance testing of UE-assisted mode. Subclause 6.2.7 lists the values of the assistance data IE fields for all minimum performance testing.

In all cases the Assistance Data is given in the two necessary formats, RRC format for TS 37.571-1 [6] subclause 6 and LPP format for TS 37.571-1 [6] subclause 7. Other information is also given separately for TS 37.571-1 [6] subclauses 6 and 7 where it differs between the subclauses.

The A-GNSS minimum performance requirements are defined by assuming that all relevant and valid assistance data is received by the UE in order to perform GNSS measurements and/or position calculation. This subclause does not include nor consider delays occurring in the various signalling interfaces of the network.

The term SV ID used in this subclause is defined as the satellite PRN for GPS and Modernized GPS, as Code Number for Galileo, as the satellite Slot Number for GLONASS and as the Ranging Code Number for BDS.

6.2.1.1 Satellite constellations and assistance data for A-GNSS minimum performance testing

For all Assisted GNSS minimum performance tests defined in TS 37.571-1 [6] subclause 6 and for Assisted GNSS minimum performance Sub-Test Case Numbers 2, 3, 4 and 5 defined in TS 37.571-1 [6] subclause 7, the satellite constellation shall consist of 24 satellites for GLONASS; 27 satellites for GPS, Modernized GPS and Galileo; 5 GEO, 3 IGSO and 22 MEO Satellites for BDS; 3 satellites for QZSS; and 2 satellites for SBAS. Almanac assistance data shall be available for all these satellites. At least 7 of the satellites per GPS, Modernized GPS, Galileo, GLONASS or BDS constellation shall be visible to the UE (that is, above 15 degrees elevation with respect to the UE). At least 1 of the satellites for QZSS shall be within 15 degrees of zenith; and at least 1 of the satellites for SBAS shall be visible to the UE. All other satellite specific assistance data shall be available for all visible satellites. In each test, signals are generated for only 6 satellites (or 7 if SBAS is included). The HDOP for the test shall be calculated using these satellites. The simulated satellites for GPS, Modernized GPS, Galileo, GLONASS and BDS shall be selected from the visible satellites for each constellation, consistent with achieving the required HDOP for the test.

For Assisted GNSS minimum performance Sub-Test Case Number 1 defined in TS 37.571-1 [6] subclause 7, the satellite constellations for minimum performance testing shall consist of 24 satellites. Almanac assistance data shall be available for all these 24 satellites. At least 9 of the satellites shall be visible to the UE (that is above 5 degrees elevation with respect to the UE). Other assistance data shall be available for 9 of these visible satellites. In each test, signals are generated for only a sub-set of these satellites for which other assistance data is available. The number of satellites in this sub-set is specified in the test. The satellites in this sub-set shall all be above 15 degrees elevation with respect to the UE. The HDOP for the test shall be calculated using this sub-set of satellites. The selection of satellites for this sub-set shall be selected consistent with achieving the required HDOP for the test.

6.2.1.2 GNSS Scenarios for A-GNSS minimum performance testing

This subclause defines the GNSS scenarios that shall be used for all Assisted GNSS minimum performance tests defined in TS 37.571-1 [6] subclauses 6 and 7.

The GNSS scenarios achieve the required HDOP for the Test Cases and they also satisfy the requirement that for each test instance the reference location shall change sufficiently such that the UE shall have to use the new assistance data.

The viable running time during which the scenario maintains the required HDOP or HDOPs is given. Once this time has been reached the scenario shall be restarted from its nominal start time.

The test cases include sub-test cases dependent on the GNSS supported by the UE. Each sub-test case is identified by a Sub-Test Case Number as defined below. For each GNSS scenario the parameters that vary with the sub-test are given for each sub-test.

Table 6.2.1.2-1: Sub-Test Case Number Definition for TS 37.571-1 subclause 6

Sub-Test Case Number	Supported GNSS
1	UE supporting A-GLONASS only
2	UE supporting A-Galileo only
3	UE supporting A-GPS and Modernized GPS only
4	UE supporting A-GPS and A-GLONASS only
8	UE supporting A-GPS and A-Galileo only
9	UE supporting A-BDS only
10	UE supporting A-GPS and A-BDS only

Table 6.2.1.2-2: Sub-Test Case Number Definition for TS 37.571-1 subclause 7

Sub-Test Case Number	Supported GNSS
1	UE supporting A-GPS L1C/A only
2	UE supporting A-GLONASS only
3	UE supporting A-Galileo only
4	UE supporting A-GPS and Modernized GPS only
5	UE supporting A-GPS and A-GLONASS only
8	UE supporting A-GPS and A-Galileo only
9	UE supporting A-BDS only
10	UE supporting A-GPS and A-BDS only

6.2.1.2.1 GNSS Scenario #1

The following GNSS scenario #1 shall be used during the TTFB tests defined in TS 37.571-1 [6] subclauses 6 and 7 with the exception of the Nominal Accuracy test. The assistance data specified in the following subclauses for GNSS scenario #1 is consistent with this GNSS scenario.

Yuma / AGL Almanac data: the required file(s) in the GNSS data perf zip file specified in Annex B are given below.

Table 6.2.1.2.1-1: Yuma / AGL Almanac data files for TS 37.571-1 subclause 6

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 1-1 AGL.txt
2	Perf GNSS 1-2 Yuma.txt
3	Perf GNSS 1-3 Yuma.txt
4	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-1 AGL.txt
8	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-2 Yuma.txt
9	Perf GNSS 1-9 Yuma.txt
10	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-9 Yuma.txt

Table 6.2.1.2.1-2: Yuma / AGL Almanac data files for TS 37.571-1 subclause 7

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 1-3 Yuma.txt
2	Perf GNSS 1-1 AGL.txt
3	Perf GNSS 1-2 Yuma.txt
4	Perf GNSS 1-3 Yuma.txt
5	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-1 AGL.txt
8	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-2 Yuma.txt
9	Perf GNSS 1-9 Yuma.txt
10	Perf GNSS 1-3 Yuma.txt and Perf GNSS 1-9 Yuma.txt

UE location: the UE location is calculated as a random offset from the reference location using the method described in subclause 6.2.1.2.6. The reference location is: latitude: 35 degrees 44 minutes 39.432 seconds north, longitude: 139 degrees 40 minutes 48.633 seconds east, (Tokyo Japan 2012), height: = 300m.

Nominal start time: 1st January 2012 00:31:00 (GPS time).

Viable running time to maintain specified HDOP values: 19 minutes.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated are given below.

Table 6.2.1.2.1-3: Visible satellites for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Visible satellites
1	3, 4, 5, 9, 10, 18, 19, 20
2	4, 5, 10, 11, 18, 19, 20, 21
3	1, 4, 11, 17, 19, 20, 23, 28, 32
4	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. GLONASS: 3, 4, 5, 9, 10, 18, 19, 20
8	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. Galileo: 4, 5, 10, 11, 18, 19, 20, 21.
9	1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28
10	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. BDS: 1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28.

Table 6.2.1.2.1-4: Visible satellites for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Visible satellites
1	1, 4, 11, 17, 19, 20, 23, 28, 32
2	3, 4, 5, 9, 10, 18, 19, 20
3	4, 5, 10, 11, 18, 19, 20, 21
4	1, 4, 11, 17, 19, 20, 23, 28, 32
5	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. GLONASS: 3, 4, 5, 9, 10, 18, 19, 20
8	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. Galileo: 4, 5, 10, 11, 18, 19, 20, 21.
9	1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28
10	GPS: 1, 4, 11, 17, 19, 20, 23, 28, 32. BDS: 1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28.

The satellites to be simulated in each test case have been selected in order to achieve the required HDOP. They are defined below.

Table 6.2.1.2.1-5: Satellites to be simulated for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	3, 4, 9, 10, 18, 20
2	5, 10, 11, 18, 19, 20
3	1, 11, 17, 19, 23, 28 (Note)
4	GPS: 20, 28, 32. GLONASS: 5, 10, 20
8	GPS: 20, 28, 32. Galileo: 5, 11, 18.
9	1, 2, 7, 18, 21, 27
10	GPS: 20, 28, 32. BDS: 1, 7, 21.
Note:	For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.

Table 6.2.1.2.1-6: Satellites to be simulated for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	Test case dependant. See Table 6.2.1.2.1-7
2	3, 4, 9, 10, 18, 20
3	5, 10, 11, 18, 19, 20
4	1, 11, 17, 19, 23, 28 (Note)
5	GPS: 20, 28, 32. GLONASS: 5, 10, 20
8	GPS: 20, 28, 32. Galileo: 5, 11, 18.
9	1, 2, 7, 18, 21, 27
10	GPS: 20, 28, 32. BDS: 1, 7, 21.
Note:	For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.

Table 6.2.1.2.1-7: Satellites to be simulated for TS 37.571-1 subclause 7, sub-test 1

Test case	SV IDs of Satellites to be simulated
Sensitivity Coarse Time Assistance	1, 4, 11, 17, 19, 20, 23, 28
Sensitivity Fine Time Assistance	1, 4, 11, 17, 19, 20, 23, 28
Nominal Accuracy	1, 4, 11, 17, 19, 20, 23, 28
Dynamic Range	1, 11, 17, 19, 23, 28
Multi-Path scenario	1, 17, 19, 23, 28

Ionospheric model: see values in subclause 6.2.7.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

6.2.1.2.2 GNSS Scenario #2

The following GNSS scenario #2 shall be used during the TTFF tests defined in TS 37.571-1 [6] subclauses 6 and 7 with the exception of the Nominal Accuracy test. The assistance data specified in the following subclauses for GNSS scenario #2 is consistent with this GNSS scenario.

Yuma / AGL Almanac data: the required file(s) in the GNSS data perf zip file specified in Annex B are below.

Table 6.2.1.2.2-1: Yuma / AGL Almanac data files for TS 37.571-1 subclause 6

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 2-1 AGL.txt
2	Perf GNSS 2-2 Yuma.txt
3	Perf GNSS 2-3 Yuma.txt
4	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-1 AGL.txt
8	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-2 Yuma.txt
9	Perf GNSS 2-9 Yuma.txt
10	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-9 Yuma.txt

Table 6.2.1.2.2-2: Yuma / AGL Almanac data files for TS 37.571-1 subclause 7

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 2-3 Yuma.txt
2	Perf GNSS 2-1 AGL.txt
3	Perf GNSS 2-2 Yuma.txt
4	Perf GNSS 2-3 Yuma.txt
5	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-1 AGL.txt
8	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-2 Yuma.txt
9	Perf GNSS 2-9 Yuma.txt
10	Perf GNSS 2-3 Yuma.txt and Perf GNSS 2-9 Yuma.txt

UE location: the UE location is calculated as a random offset from the reference location using the method described in subclause 6.2.1.2.6. The reference location is: latitude: 37 degrees 24 minutes 53.391 seconds north, longitude: 122 degrees 1 minutes 3.722 seconds west, (Sunnyvale, USA), height: = 50m.

Nominal start time: 1st June 2012, 00:01:00 (GPS time).

Viable running time to maintain specified HDOP values: 19 minutes.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated are given below.

Table 6.2.1.2.2-3: Visible satellites for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Visible satellites
1	1, 8, 9, 10, 16, 19, 20, 21
2	4, 5, 14, 15, 16, 26, 29, 30
3	1, 7, 8, 11, 15, 17, 26, 27, 28
4	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. GLONASS: 1, 8, 9, 10, 16, 19, 20, 21
8	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. Galileo: 4, 5, 14, 15, 16, 26, 29, 30.
9	4, 15, 16, 17, 18, 25, 26, 27
10	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. BDS: 4, 15, 16, 17, 18, 25, 26, 27.

Table 6.2.1.2.2-4: Visible satellites for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Visible satellites
1	1, 7, 8, 11, 15, 17, 26, 27, 28
2	1, 8, 9, 10, 16, 19, 20, 21
3	4, 5, 14, 15, 16, 26, 29, 30
4	1, 7, 8, 11, 15, 17, 26, 27, 28
5	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. GLONASS: 1, 8, 9, 10, 16, 19, 20, 21
8	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. Galileo: 4, 5, 14, 15, 16, 26, 29, 30.
9	4, 15, 16, 17, 18, 25, 26, 27
10	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. BDS: 4, 15, 16, 17, 18, 25, 26, 27.

The satellites to be simulated in each test case have been selected in order to achieve the required HDOP. They are defined below.

Table 6.2.1.2.2-5: Satellites to be simulated for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	1, 8, 9, 10, 19, 20
2	[4, 15, 16, 26, 29, 30
3	1, 7, 8, 17, 27, 28 (Note)
4	GPS: 1, 8, 26. GLONASS: 8, 10, 20
8	GPS: 1, 8, 26. Galileo: 15, 26, 30.
9	15, 16, 17, 25, 26, 27
10	GPS: 1, 8, 26. BDS: 15, 25, 27.
Note: For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.	

Table 6.2.1.2.2-6: Satellites to be simulated for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	Test case dependant. See Table 6.2.1.2.2-7
2	1, 8, 9, 10, 19, 20
3	4, 15, 16, 26, 29, 30
4	1, 7, 8, 17, 27, 28 (Note)
5	GPS: 1, 8, 26. GLONASS: 8, 10, 20
8	GPS: 1, 8, 26. Galileo: 15, 26, 30.
9	15, 16, 17, 25, 26, 27
10	GPS: 1, 8, 26. BDS: 15, 25, 27.
Note: For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.	

Table 6.2.1.2.2-7: Satellites to be simulated for TS 37.571-1 subclause 7, sub-test 1

Test case	SV IDs of Satellites to be simulated
Sensitivity Coarse Time Assistance	1, 7, 8, 15, 17, 26, 27, 28
Sensitivity Fine Time Assistance	1, 7, 8, 15, 17, 26, 27, 28
Nominal Accuracy	1, 7, 8, 15, 17, 26, 27, 28
Dynamic Range	1, 7, 8, 17, 27, 28
Multi-Path scenario	1, 7, 8, 17, 27

Ionospheric model: see values in subclause 6.2.7.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

6.2.1.2.3 GNSS Scenario #3

The following GNSS scenario #3 shall be used during the Nominal Accuracy test defined in TS 37.571-1 [6] subclauses 6 and 7. The assistance data specified in the following subclauses for GNSS scenario #3 is consistent with this GNSS scenario.

The scenario used varies dependent on the SBAS supported by the UE and also whether QZSS is supported. The scenario to be used is defined below. Where more than one SBAS is supported use the scenario for MSAS if MSAS and QZSS are supported, otherwise use the scenario for the first supported SBAS in the list.

Table 6.2.1.2.3-1: Scenarios used for Scenario #3

SBAS supported	Scenarios used	
	UE supports QZSS	UE does not support QZSS
None	GNSS Scenario #1 with QZSS Scenario #1	GNSS Scenario #1
WAAS	[FFS]	GNSS Scenario #2 with WAAS
EGNOS	[FFS]	GNSS Scenario #3A with EGNOS
MSAS	GNSS Scenario #1 with QZSS Scenario #1 and MSAS	GNSS Scenario #1 with MSAS
GAGAN	[FFS]	GNSS Scenario #3B with GAGAN

6.2.1.2.3.1 GNSS Scenario #3A

[FFS]

6.2.1.2.3.2 GNSS Scenario #3B

[FFS]

6.2.1.2.3.3 QZSS Scenario #1

Almanac data: see file Perf GNSS 1-3 Yuma_QZSS.txt in the GNSS data perf zip file specified in Annex B.

Ephemeris data: see file Perf GNSS Navigation Model subtest1 01_QZSS.csv in the GNSS data perf zip file specified in Annex B.

Acquisition Assistance: see file Perf GNSS Acquisition Assistance subtest1 01_QZSS.csv in the GNSS data perf zip file specified in Annex B.

UE location: as for GNSS scenario #1.

Nominal start time: as for GNSS scenario #1.

Viable running time to maintain specified requirements: as for GNSS scenario #1.

Satellite meeting specified requirements to be used for simulation and for which Assistance Data (other than Almanac) shall be generated: PRN 195.

6.2.1.2.3.4 WAAS Scenario

Satellite positions: (PRN 135)133.0 degrees west, height: 35786037.417m, (PRN 138)107.3 degrees west, height: 35786037.417m.

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 135.

6.2.1.2.3.5 EGNOS Scenario

Satellite positions: (PRN 120)15.5 degrees west, height: 35786037.417m, (PRN 124) 21.5 degrees west, height: 35786037.417m.

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 120.

6.2.1.2.3.6 MSAS Scenario

Satellite positions: (PRN 129)140.0 degrees east, height: 35786037.417m, (PRN 137)145 degrees east, height: 35786037.417m

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 129.

6.2.1.2.3.7 GAGAN Scenario

[FFS]

6.2.1.2.4 GNSS Scenario #4

The following GNSS scenario #4 shall be used during the Nominal Accuracy test defined in TS 37.571-1 [6] subclauses 6 and 7. The assistance data specified in the following subclauses for GNSS scenario #4 is consistent with this GNSS scenario.

The scenario used varies dependent on the SBAS supported by the UE and also whether QZSS is supported. The scenario to be used is defined below. Where more than one SBAS is supported use the scenario for MSAS if MSAS and QZSS are supported, otherwise use the scenario for the first supported SBAS in the list.

Table 6.2.1.2.4-1: Scenarios used for Scenario #4

SBAS supported	Scenarios used	
	UE supports QZSS	UE does not support QZSS
None	GNSS Scenario #4D with QZSS Scenario #2	GNSS Scenario #2
WAAS	[FFS]	GNSS Scenario #4C with WAAS
EGNOS	[FFS]	GNSS Scenario #4A with EGNOS
MSAS	GNSS Scenario #4D with QZSS Scenario #2 and MSAS	GNSS Scenario #4D with MSAS
GAGAN	[FFS]	GNSS Scenario #4B with GAGAN

6.2.1.2.4.1 GNSS Scenario #4A

[FFS]

6.2.1.2.4.2 GNSS Scenario #4B

[FFS]

6.2.1.2.4.3 GNSS Scenario #4C

[FFS]

6.2.1.2.4.4 GNSS Scenario #4D

[FFS]

6.2.1.2.4.5 QZSS Scenario #2

Almanac data: see file Perf QZSS 2 Yuma.txt in the GNSS data perf zip file specified in Annex B.

UE location: as for GNSS scenario #4D.

Nominal start time: as for GNSS scenario #4D.

Viable running time to maintain specified requirements: as for GNSS scenario #4D.

Satellite meeting specified requirements to be used for simulation and for which Assistance Data (other than Almanac) shall be generated: PRN [FFS].

6.2.1.2.4.6 WAAS Scenario

Satellite positions: (PRN 135)133.0 degrees west, height: 35786037.417m, (PRN 138)107.3 degrees west, height: 35786037.417m.

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 138.

6.2.1.2.4.7 EGNOS Scenario

Satellite positions: (PRN 120)15.5 degrees west, height: 35786037.417m, (PRN 124) 21.5 degrees west, height: 35786037.417m.

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 124.

6.2.1.2.4.8 MSAS Scenario

Satellite positions: (PRN 129)140.0 degrees east, height: 35786037.417m, (PRN 137)145 degrees east, height: 35786037.417m.

UE location: as for related GNSS scenario.

Satellite used for simulation: PRN 137.

6.2.1.2.4.9 GAGAN Scenario

[FFS]

6.2.1.2.5 GNSS Scenario #5

The following GNSS scenario #5 shall be used during the Moving Scenario and Periodic Update test cases defined in TS 37.571-1 [6] subclauses 6 and7. The assistance data specified in the following subclauses for GNSS scenario #5 is consistent with this GNSS scenario.

Yuma / AGL Almanac data: the required file(s) in the GNSS data perf zip file specified in Annex B are below.

Table 6.2.1.2.5-1: Yuma / AGL Almanac data files for TS 37.571-1 subclause 6

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 5-1 AGL.txt
2	Perf GNSS 5-2 Yuma.txt
3	Perf GNSS 5-3 Yuma.txt
4	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-1 AGL.txt
8	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-2 Yuma.txt
9	Perf GNSS 5-9 Yuma.txt
10	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-9 Yuma.txt

Table 6.2.1.2.5-2: Yuma / AGL Almanac data files for TS 37.571-1 subclause 7

Sub-Test Case Number	Yuma / AGL file(s)
1	Perf GNSS 5-3 Yuma.txt
2	Perf GNSS 5-1 AGL.txt
3	Perf GNSS 5-2 Yuma.txt
4	Perf GNSS 5-3 Yuma.txt
5	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-1 AGL.txt
8	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-2 Yuma.txt
9	Perf GNSS 5-9 Yuma.txt
10	Perf GNSS 5-3 Yuma.txt and Perf GNSS 5-9 Yuma.txt

UE location: the UE location is given as a trajectory as shown in Figure 6.6.1 and Figure 7.1 of TS 37.571-1 [6]. The reference location is at the centre of the trajectory and is at: latitude: 37 degrees 24 minutes 53.391 seconds north, longitude: 122 degrees 1 minutes 3.722 seconds west, (Sunnyvale, USA), height: = 50m.

Start location: at the point between l_{11} and l_{12} in Figure 6.6.1 and Figure 7.1 of TS 37.571-1 [6], going in a clock-wise direction.

Nominal start time: 1st June 2012, 00:01:00 (GPS time).

Viable running time to maintain specified HDOP values: 20 minutes.

Visible satellites available for simulation and for which Assistance Data (other than Almanac) shall be generated are given below.

Table 6.2.1.2.5-3: Visible satellites for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Visible satellites
1	1, 8, 9, 10, 16, 19, 20, 21
2	4, 5, 14, 15, 16, 26, 29, 30
3	1, 7, 8, 11, 15, 17, 26, 27, 28
4	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. GLONASS: 1, 8, 9, 10, 16, 19, 20, 21
8	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. Galileo: 4, 5, 14, 15, 16, 26, 29, 30.
9	4, 15, 16, 17, 18, 25, 26, 27
10	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. BDS: 4, 15, 16, 17, 18, 25, 26, 27.

Table 6.2.1.2.5-4: Visible satellites for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Visible satellites
1	1, 7, 8, 11, 15, 17, 26, 27, 28
2	1, 8, 9, 10, 16, 19, 20, 21
3	4, 5, 14, 15, 16, 26, 29, 30
4	1, 7, 8, 11, 15, 17, 26, 27, 28
5	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. GLONASS: 1, 8, 9, 10, 16, 19, 20, 21
8	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. Galileo: 4, 5, 14, 15, 16, 26, 29, 30.
9	4, 15, 16, 17, 18, 25, 26, 27
10	GPS: 1, 7, 8, 11, 15, 17, 26, 27, 28. BDS: 4, 15, 16, 17, 18, 25, 26, 27.

The satellites to be simulated in each test case have been selected in order to achieve the required HDOP. They are defined below.

Table 6.2.1.2.5-5: Satellites to be simulated for TS 37.571-1 subclause 6

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	1, 8, 9, 10, 19, 20
2	4, 15, 16, 26, 29, 30
3	1, 7, 8, 17, 27, 28 (Note)
4	GPS: 1, 8, 26. GLONASS: 8, 10, 20
8	GPS: 1, 8, 26. Galileo: 15, 26, 30.
9	15, 16, 17, 25, 26, 27
10	GPS: 1, 8, 26. BDS: 15, 25, 27.
Note: For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.	

Table 6.2.1.2.5-6: Satellites to be simulated for TS 37.571-1 subclause 7

Sub-Test Case Number	SV IDs of Satellites to be simulated
1	7, 8, 17, 27, 28
2	1, 8, 9, 10, 19, 20
3	4, 15, 16, 26, 29, 30
4	1, 7, 8, 17, 27, 28 (Note)
5	GPS: 1, 8, 26. GLONASS: 8, 10, 20
8	GPS: 1, 8, 26. Galileo: 15, 26, 30.
9	15, 16, 17, 25, 26, 27
10	GPS: 1, 8, 26. BDS: 15, 25, 27.
Note: For this sub-test the satellite simulator shall generate all the GPS signals supported by the UE for all the simulated satellites.	

Ionospheric model: see values in subclause 6.2.7.

Tropospheric model: STANAG with SRI equal to 324.8, as defined in STANAG 4294 [17].

6.2.1.2.6 UE Location for TTFF test cases

This subclause defines the method for generating the random UE locations that are required to be used for the TTFF tests defined in TS 37.571-1 [6] subclauses 6 and 7.

For every Test Instance in each TTFF test case, the UE location shall be randomly selected to be within 3 km of the Reference Location. The Altitude of the UE shall be randomly selected between 0 m to 500 m above WGS-84 reference ellipsoid. These values shall have uniform random distributions.

The UE location is calculated as an offset from the Reference Location.

6.2.1.2.6.1 UE Location Offset

The UE location offset shall be calculated by selecting the next pair of random numbers, representing a pair of latitude and longitude offsets in degrees, from a standard uniform random number generator, with the following properties:

The ranges of the latitude and longitude offsets values shall be such that when translated onto the surface of the earth they shall lie within a 3km radius circle, centred on the Reference location specified for the GNSS scenario under consideration. For the purposes of this calculation make the following assumptions:

- Over the 3km radius circle at the Reference location the earth is flat and the meridians and parallels form a rectangular grid
- The earth is spherical with a radius of 6371141m (equal to the WGS 84 value at 35 degrees latitude)

The resolution used for the latitude and longitude offsets values shall be $90/2^{23}$ for the latitude offset values and $360/2^{24}$ for the longitude offset values, representing the coding resolution in degrees specified in 3GPP TS 23.032.

6.2.1.2.6.2 UE Altitude

The UE altitude value shall be calculated by selecting the next random number from a standard uniform random number generator, in the range 0 to 500, representing meters. The resolution used for the random number shall be 1, representing 1 meter.

6.2.2 Information elements required for normal UE based testing for TS 37.571-1 subclause 6

The following A-GPS and A-GANSS assistance data IEs and fields shall be present for each test as appropriate for the GNSS(s) used during the test. Fields not specified shall not be present. The values of the fields are specified in subclause 6.2.7.

The information elements are given with reference to 3GPP TS 25.331 [34], where the details are defined.

a) **GPS Reference Time IE**

Fields of the IE	Release
GPS Week	
GPS Week Cycle Number	Rel-10 onwards
GPS TOW msec	
UE Positioning GPS ReferenceTime Uncertainty	
GPS TOW Assist	
SatID	
TLM Message	
TLM Reserved	
Alert	
Anti-Spoof	

b) **GANSS Reference Time IE**

Fields of the IE	Release
GANSS Day	
GANSS Day Cycle Number	Rel-10 onwards
GANSS TOD	
GANSS TOD Uncertainty	
GANSS Time ID	

c) **GANSS Time Model IE** This information element is only required for multi system tests.

Fields of the IE	Release
GANSS Time Model Reference Time	
T_{A0}	
GNSS_TOD_ID For each GNSS included in the test.	
Delta_T	Rel-10 onwards

d) **GPS Reference UE Position IE**

Fields of the IE
Ellipsoid point with Altitude and uncertainty ellipsoid

e) **GANSS Reference UE Position IE**

Fields of the IE
Ellipsoid point with Altitude and uncertainty ellipsoid

f) **GPS Navigation Model IE**

Fields of the IE
All satellite information

g) **GANSS Navigation Model IE**

Fields of the IE
All satellite information

GANSS	Clock and Orbit Model Choice
Galileo	Model-1

h) GANSS Additional Navigation Model IE

Fields of the IE
All satellite information

GANSS	Clock and Orbit Model Choice
Modernized GPS	Model-3
GLONASS	Model-4
QZSS QZS-L1	Model-2
QZSS QZS-L1C/L2C/L5	Model-3
SBAS	Model-5
BDS	Model-6

i) GPS Ionospheric Model IE

Fields of the IE
All

j) GANSS Ionospheric Model IE

Fields of the IE
All

k) GANSS Additional Ionospheric Model IE

Fields of the IE
All

l) GPS UTC Model IE

Fields of the IE
All

m) GANSS Auxiliary Information IE

Fields of the IE
GANSS Auxiliary Information

6.2.3 Information elements required for UE based Sensitivity Fine Time Assistance test case for TS 37.571-1 subclause 6

The A-GPS and A-GANSS assistance data IEs and fields that shall be present for the Sensitivity Fine Time Assistance test case shall be those specified in subclause 6.2.2 with the following exception. Fields not specified shall not be present. The values of the fields are specified in subclause 6.2.7.

a) GPS Reference Time IE

Fields of the IE	Release
GPS Week	
GPS Week Cycle Number	Rel-10 onwards
GPS TOW msec	
UTRAN GPS reference time	
UTRAN GPS timing of cell frames	
CHOICE mode	
FDD: Primary CPICH Info	
TDD: cell parameters id	

SFN	
UE Positioning GPS ReferenceTime Uncertainty	
TUTRAN-GPS drift rate	
GPS TOW Assist	
SatID	
TLM Message	
TLM Reserved	
Alert	
Anti spoof	

b) GANSS Reference Time IE

Fields of the IE	Release
GANSS Day	
GANSS Day Cycle Number	Rel-10 onwards
GANSS TOD	
GANSS TOD Uncertainty	
GANSS Time ID	
UTRAN GANSS reference time	
UTRAN GANSS timing of cell frames	
CHOICE mode	
FDD: Primary CPICH Info	
TDD: cell parameters id	
SFN	
TUTRAN-GANSS drift rate	

6.2.4 Information elements available for normal UE assisted testing for TS 37.571-1 subclause 6

The following A-GPS and A-GANSS assistance data IEs and fields shall be present for each test as appropriate for the GNSS(s) used during the test. Fields not specified shall not be present. The values of the fields are specified in subclause 6.2.7.

a) GPS Reference Time IE

Fields of the IE	Release
GPS Week	
GPS Week Cycle Number	Rel-10 onwards
GPS TOW msec	
UE Positioning GPS ReferenceTime Uncertainty	
GPS TOW Assist	
SatID	
TLM Message	
TLM Reserved	
Alert	
Anti-Spoof	

b) GANSS Reference Time IE

Fields of the IE	Release
GANSS Day	
GANSS Day Cycle Number	Rel-10 onwards
GANSS TOD	
GANSS TOD Uncertainty	
GANSS Time ID	

c) GANSS Time Model IE This information element is only required for multi system tests.

Fields of the IE	Release
GANSS Time Model Reference Time	
T _{A0}	
GNSS_TOD_ID For each GNSS included in the test.	
Delta_T	Rel-10 onwards

d) GPS Reference UE Position IE

Fields of the IE
Ellipsoid point with Altitude and uncertainty ellipsoid

e) GANSS Reference UE Position IE

Fields of the IE
Ellipsoid point with Altitude and uncertainty ellipsoid

f) GPS Almanac IE

Fields of the IE	Release
Almanac Reference Week	
Complete Almanac Provided	Rel-10 onwards
All Satellite information	

g) GANSS Almanac IE

Fields of the IE
GANSS Almanac Model

GANSS	Almanac Model Choice
Galileo	Model-1
Modernized GPS	Model-3,4
GLONASS	Model-5
QZSS QZS-L1	Model-2
QZSS QZS-L1C/L2C/L5	Model-3,4
SBAS	Model-6
BDS	Model-7

h) GPS Navigation Model IE

Fields of the IE
All satellite information

i) GANSS Navigation Model IE

Fields of the IE
All satellite information

GNSS	Clock and Orbit Model Choice
Galileo	Model-1
Modernized GPS	Model-3
GLONASS	Model-4
QZSS QZS-L1	Model-2
QZSS QZS-L1C/L2C/L5	Model-3
SBAS	Model-5
BDS	Model-6

j) GPS Acquisition Assistance IE

Fields of the IE	Release
GPS TOW msec	
UE Positioning GPS ReferenceTime Uncertainty	
Satellite information	
SatID	
Doppler (0 th order term)	
Extra Doppler	
Doppler (1 st order term)	
Doppler Uncertainty	
Code Phase	
Integer Code Phase	
GPS Bit number	
Code Phase Search Window	
Azimuth and Elevation	
Azimuth	
Elevation	
Azimuth LSB	Rel-10 onwards
Elevation LSB	Rel-10 onwards

k) GNSS Reference Measurement Information IE

Fields of the IE	Release
Satellite information	
SatID	
Doppler (0 th order term)	
Extra Doppler	
Doppler (1 st order term)	
Doppler Uncertainty	
Code Phase	
Integer Code Phase	
Code Phase Search Window	
Azimuth and Elevation	
Azimuth	
Elevation	
Azimuth LSB	Rel-10 onwards
Elevation LSB	Rel-10 onwards

l) GNSS Auxiliary Information IE

Fields of the IE
GNSS Auxiliary Information

m) GPS UTC Model IE

Fields of the IE
GPS UTC Model

6.2.5 Information elements available for UE assisted Sensitivity Fine Time Assistance test case for TS 37.571-1 subclause 6

The A-GPS and A-GANSS assistance data IEs and fields that shall be available for use for the Sensitivity Fine Time Assistance test case shall be those specified in subclause 6.2.4 with the following exceptions. Fields not specified shall not be present. The values of the fields are specified in subclause 6.2.7.

a) GPS Reference Time IE

Fields of the IE	Release
GPS Week	
GPS Week Cycle Number	Rel-10 onwards
GPS TOW msec	
UTRAN GPS reference time	
UTRAN GPS timing of cell frames	
CHOICE mode	
FDD: Primary CPICH Info	
TDD: cell parameters id	
SFN	
UE Positioning GPS ReferenceTime Uncertainty	
TUTRAN-GPS drift rate	
GPS TOW Assist	
SatID	
TLM Message	
TLM Reserved	

b) GANSS Reference Time IE

Fields of the IE	Release
GANSS Day	
GANSS Day Cycle Number	Rel-10 onwards
GANSS TOD	
GANSS TOD Uncertainty	
GANSS Time ID	
UTRAN GANSS timing of cell frames	
CHOICE mode	
FDD: Primary CPICH Info	
TDD: cell parameters id	
SFN	
TUTRAN-GANSS drift rate	

c) GPS Acquisition Assistance IE

Fields of the IE	Release
GPS TOW msec	
UTRAN GPS reference time	
UTRAN GPS timing of cell frames	
CHOICE mode	
FDD: Primary CPICH Info	
TDD: cell parameters id	
SFN	
UE Positioning GPS ReferenceTime Uncertainty	
Satellite information	
SatID	
Doppler (0 th order term)	
Extra Doppler	
Doppler (1 st order term)	
Doppler Uncertainty	
Code Phase	
Integer Code Phase	

GPS Bit number	
Code Phase Search Window	
Azimuth and Elevation	
Azimuth	
Elevation	
Azimuth LSB	Rel-10 onwards
Elevation LSB	Rel-10 onwards

6.2.6 Information elements available for A-GNSS test cases in TS 37.571-1 subclause 7

The following A-GNSS assistance data elements shall be provided to the UE in the tests. The assistance data provided depends on the mode being used in the test case, the assistance data supported by the UE and the GNSSs supported by the UE. Assistance data IEs not supported by the UE shall not be sent. Assistance data IEs supported by the UE but not listed below shall not be sent. The values of the fields are specified in subclause 6.2.7.

The information elements are given with reference to 3GPP TS 36.355 [8], where the details are defined.

Assistance Data to be provided to the UE for A-GNSS test cases in TS 37.571-1 subclause 7

Assistance Data IE supported by UE	Mode used in test case		
	UE-based	UE-assisted, GNSS-AcquisitionAssistance supported by UE	UE-assisted, GNSS-AcquisitionAssistance not supported by UE
GNSS-Reference Time	Yes	Yes	Yes
GNSS-ReferenceLocation	Yes	No	Yes
GNSS-IonosphericModel	Yes	No	No
GNSS-TimeModelList	Yes for sub-test 5, 8, 10	No	Yes for sub-test 5, 8, 10
GNSS-NavigationModel	Yes	No	Yes
GNSS-AcquisitionAssistance	No	Yes	No
GNSS-Almanac	No	No	Yes
GNSS-UTC-Model	Yes for sub-test 5	Yes for sub-test 5	Yes for sub-test 5
GNSS-AuxiliaryInformation	Yes for sub-tests 2, 4, 5. Note.	Yes for sub-tests 2, 4, 5. Note.	Yes for sub-tests 2, 4, 5. Note.
Note: Also if UE supports multiple signals per GNSS.			

a) GNSS- Reference Time IE

GNSS- Reference Time IE

Information Element	All tests except Sensitivity Fine Time Assistance	Sensitivity Fine Time Assistance test
GNSS-ReferenceTime		
gnss-SystemTime		
gnss-TimeID	Yes	Yes
gnss-DayNumber	Yes	Yes
gnss-TimeOfDay	Yes	Yes
gnss-TimeOfDayFrac-msec	Yes	Yes
notificationOfLeapSecond	Yes if gnss-TimeID = 'glonass'	Yes if gnss-TimeID = 'glonass'
gps-TOW-Assist	Yes if gnss-TimeID = 'gps'	Yes if gnss-TimeID = 'gps'
referenceTimeUnc	Yes	No
gnss-ReferenceTimeForOneCell	No	Yes
networkTime		Yes
secondsFromFrameStructureStart		Yes
fractionalSecondsFromFrameStructureStart		Yes
frameDrift		Yes
cellID		Yes
physCellId		Yes
cellGlobalIdEUTRA		Yes
earfcn		Yes
referenceTimeUnc		Yes

b) **GNSS-ReferenceLocation IE****GNSS-ReferenceLocation IE**

Name of the IE	Fields of the IE
GNSS-ReferenceLocation	threeDlocation

c) **GNSS-IonosphericModel IE****GNSS-IonosphericModel IE**

Name of the IE	Fields of the IE
GNSS-IonosphericModel	KlobucharModelParameter
	NeQuickModelParameter ⁽¹⁾
Note 1: Only required if GNSSs supported include Galileo.	

d) **GNSS-TimeModelList IE** This information element is only required for multi system tests.**GNSS-TimeModelList IE**

Name of the IE	Fields of the IE
GNSS-TimeModelList	
	gnss-TO-ID For each GNSS included in the test.
	deltaT

e) **GNSS-NavigationModel IE**

GNSS-NavigationModel IE

Name of the IE	Fields of the IE
GNSS-NavigationModel	

GNSS Clock and Orbit Model Choices

GNSS	Clock and Orbit Model Choice
GPS	Model-2
Modernized GPS	Model-3
GLONASS	Model-4
QZSS QZS-L1	Model-2
QZSS QZS-L1C/L2C/L5	Model-3
SBAS	Model-5
Galileo	Model-1
BDS	Model-6

f) **GNSS-AcquisitionAssistance IE****GNSS-AcquisitionAssistance IE**

Name of the IE	Fields of the IE
GNSS-AcquisitionAssistance	

g) **GNSS-Almanac IE****GNSS-Almanac IE**

Name of the IE	Fields of the IE
GNSS-Almanac	

GNSS Almanac Choices

GNSS	Almanac Model Choice
GPS	Model-2
Modernized GPS	Model-3,4
GLONASS	Model-5
QZSS QZS-L1	Model-2
QZSS QZS-L1C/L2C/L5	Model-3,4
SBAS	Model-6
Galileo	Model-1
BDS	Model-7

h) **GNSS-UTC-Model IE****GNSS-UTC-Model IE**

Name of the IE	Fields of the IE
GNSS-UTC-Model	

GNSS UTC Model Choices

GNSS	UTC Model Choice
GPS	Model-1
Modernized GPS	Model-2
GLONASS	Model-3
QZSS QZS-L1	Model-1
QZSS QZS-L1C/L2C/L5	Model-2
SBAS	Model-4
Galileo	Model-1
BDS	Model-5

i) GNSS-AuxiliaryInformation IE

GNSS-AuxiliaryInformation IE

Name of the IE	Fields of the IE
GNSS-AuxiliaryInformation	

6.2.7 Contents of Information elements for A-GNSS Minimum performance testing

6.2.7.1 General

This subclause defines the assistance data values that shall be used for all Assisted GNSS minimum performance tests defined in TS 37.571-1 [6] subclauses 6 and 7. It is given for GNSS scenarios #1, #2, #3, #4 and #5 and QZSS Scenarios #1 and #2, where it is different for each scenario; otherwise it is marked “All” where the same value is used for all scenarios.

Where assistance data is required on a per-satellite basis, or where the values of the data also varies with time it is specified in comma-separated-variable files in the GNSS data perf zip file specified in Annex B. These files specify the values to be used for each satellite, indexed by satellite PRN or SV ID, and, where applicable, the values to be used indexed by both time and satellite PRN or SV ID.

Assistance data that is marked as “time varying” is specified and used in 80ms increments. Interpolation between these values shall not be used.

Assistance data Information Elements and fields that are not specified shall not be used.

6.2.7.2 IE Random Offset Values

This subclause defines the methods for generating the random offsets that are required to be applied to some assistance data IEs for certain tests defined in TS 37.571-1 [6] subclauses 6 and 7.

6.2.7.2.1 GNSS TOW

For every Test Instance in each TTFF test case, the IE GPS TOW msec or GANSS TOD or gnss-TimeofDay plus gnss-TimeofDayFrac-msec shall have a random offset, relative to GNSS system time, within the allowed error range of Coarse Time Assistance defined in the test case. This offset value shall have a uniform random distribution.

The offset value shall be calculated by selecting the next random number from a standard uniform random number generator, in the range specified for the GNSS Coarse Time assistance error range in the Test Requirements, Test parameters table for the test under consideration. The resolution used for the random number shall be 0.01, representing 10ms.

6.2.7.2.2 GNSS/cellular time offset

In addition, for every Fine Time Assistance Test Instance the IE UTRAN GPS timing of cell frames or the UTRAN GANSS timing of cell frames or fractionalSecondsFromFrameStructureStart shall have a random offset, relative to the

true value of the relationship between the two time references, within the allowed error range of Fine Time Assistance defined in the test case. This offset value shall have a uniform random distribution.

The offset value shall be calculated by selecting the next random number from a standard uniform random number generator with the following properties:

For UTRAN GPS timing of cell frames the range shall be the number of UMTS chips whose duration is less than the range specified for the GNSS Fine Time assistance error range in the Test Requirements, Test parameters table for the test under consideration. For UTRAN GANSS timing of cell frames or fractionalSecondsFromFrameStructureStart the range shall be the range specified for the GNSS Fine Time assistance error range in the Test Requirements, Test parameters table for the test under consideration.

For UTRAN GPS timing of cell frames the resolution used for the random number shall be 1, representing 1 UMTS bit. For UTRAN GANSS timing of cell frames or fractionalSecondsFromFrameStructureStart the resolution used for the random number shall be 1 μ s.

6.2.7.3 Contents of Information elements for A-GNSS Minimum performance testing in TS 37.571-1 subclause 6

Assistance Data Reference Time

Contents of UE positioning GPS reference time (sub-tests 3 and 4)

Reference Time (Fields occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GPS Week	Weeks	1669	1690	1690
GPS Week Cycle Number (Note 3)		1	1	1
GPS TOW msec	msec	1860000 ms. Start time. Add number of ms as required. (Note 1)	432060000 ms. Start time. Add number of ms as required. (Note 1)	432060000 ms. Start time. Add number of ms as required. (Note 1)
UTRAN GPS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GPS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
TDD: cell parameters id		0	0	
SFN		Note 2	Note 2	-
UE Positioning GPS ReferenceTime Uncertainty		For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	'125' (2.127s)
TUTRAN-GPS drift rate		0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent

Note 1: GPS TOW msec

This is the value in ms of GPS TOW msec when the GPS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GPS scenario is used, the GPS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.

The actual value of GPS TOW msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

For all TTFF test cases a random offset is then added to the value of GPS TOW msec as described in subclause 6.2.7.2.

Note 2: UTRAN GPS timing of cell frames and SFN.

The values of UTRAN GPS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 6.2.7.2.

Note 3: This IE is only present for Rel-10 onwards.

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	9	9	9

Reference Time - GPS TOW Assist (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28

Reference Time - GPS TOW Assist (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All
TLM Message	Bit string	10922
TLM Reserved	Bit string	2
Alert	Boolean	0
Anti-Spoof	Boolean	1

Contents of UE positioning GANSS reference time (sub-tests 1 and 2)

GANSS reference time: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS Day	days	5844	5996	5996
GNSS Day Cycle Number (note 3)		0	0	0
GNSS TOD	seconds	12645 Start time. (Note 1)	10845 Start time. (Note 1)	10845 Start time. (Note 1)
GNSS TOD Uncertainty		125 (2.127 seconds)	125 (2.127 seconds)	125 (2.127 seconds)
GNSS Time ID		2 (GLONASS)	2 (GLONASS)	2 (GLONASS)
UTRAN GANSS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GANSS timing of cell frames		Note 2	Note 2	-
HOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
CD: Primary CPICH Info		100	100	-
CD: cell parameters id		0	0	-
SFN		Note 2	Note 2	-
UTRAN-GANSS drift rate		0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent

Note 1: GANSS TOD

This is the value in seconds of GANSS TOD when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.

The actual value of GANSS TOD to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1[6], shall be met.

For all TTFF test cases a random offset is then added to the value of GANSS TOD as described in subclause 6.2.7.2.

Note 2: UTRAN GANSS timing of cell frames and SFN.

The values of UTRAN GANSS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 6.2.7.2.

Note 3: This IE is only present for Rel-10 onwards.

GANSS reference time: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GANSS Day	days	4536	4688	4688
GANSS Day Cycle Number (Note 3)		0	0	0
GANSS TOD	seconds	1860. Start time. (Note 1)	60. Start time. (Note 1)	60. Start time. (Note 1)
GANSS TOD Uncertainty		125 (2.127 seconds)	125 (2.127 seconds)	125 (2.127 seconds)
GANSS Time ID		Not present (Galileo)	Not present (Galileo)	Not present (Galileo)
UTRAN GANSS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GANSS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
TDD: cell parameters id		0	0	
SFN		Note 2	Note 2	-
TUTRAN-GANSS drift rate		0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent

Note 1: GANSS TOD

This is the value in seconds of GANSS TOD when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.

The actual value of GANSS TOD to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

For all TTFF test cases a random offset is then added to the value of GANSS TOD as described in subclause 6.2.7.2.

Note 2: UTRAN GANSS timing of cell frames and SFN.

The values of UTRAN GANSS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 6.2.7.2.

Note 3: This IE is only present for Rel-10 onwards.

GANSS reference time: sub-test 9

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GANSS Day	days	2191	2343	2343
GANSS Day Cycle Number (Note 3)		0	0	0
GANSS TOD	seconds	1846. Start time. (Note 1)	432046. Start time. (Note 1)	432046. Start time. (Note 1)
GANSS TOD Uncertainty		125 (2.127 seconds)	125 (2.127 seconds)	125 (2.127 seconds)
GANSS Time ID		3 (BDS system time)	3 (BDS system time)	3 (BDS system time)
UTRAN GANSS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GANSS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
TDD: cell parameters id		0	0	
SFN		Note 2	Note 2	-
TUTRAN-GANSS drift rate		0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	0. Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent

Note 1: GANSS TOD

This is the value in seconds of GANSS TOD when the GNSS scenario is initially started in the GNSS simulator. For all TTFB test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.

The actual value of GANSS TOD to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

For all TTFB test cases a random offset is then added to the value of GANSS TOD as described in subclause 6.2.7.2.

Note 2: UTRAN GANSS timing of cell frames and SFN.

The values of UTRAN GANSS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.

A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 6.2.7.2.

Note 3: This IE is only present for Rel-10 onwards.

Assistance Data Time Model

Contents of UE positioning GANSS time model (sub-test 4)

GANSS time model

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GANSS Time Model Reference Time		1860 (s)	432060 (s)	432060 (s)
T _{A0}	seconds	0	0	0
GNSS_TOD_ID		0 (GPS)	0 (GPS)	0 (GPS)
Delta_T (Note 1)	seconds	15	15	15
Note 1: This IE is only present for Rel-10 onwards.				

Contents of UE positioning GANSS time model (sub-test 8)

GANSS time model

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GANSS Time Model Reference Time		1860 (s)	432060 (s)	432060 (s)
T _{A0}	seconds	0	0	0
GNSS_TOD_ID		0 (GPS)	0 (GPS)	0 (GPS)
Delta_T (Note 1)	seconds	0	0	0
Note 1: This IE is only present for Rel-10 onwards.				

Contents of UE positioning GANSS time model (sub-test 10)

GANSS time model

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GANSS Time Model Reference Time		1860 (s)	432060 (s)	432060 (s)
T _{A0}	seconds	0	0	0
GNSS_TOD_ID		0 (GPS)	0 (GPS)	0 (GPS)
Delta_T (Note 1)	seconds	13	13	13
Note 1: This IE is only present for Rel-12 onwards.				

Assistance Data Reference UE Position

The uncertainty of the semi-major axis is 3 km. The uncertainty of the semi-minor axis is 3 km. The orientation of the major axis is 0 degrees. The uncertainty of the altitude information is 500 m. The confidence factor is 68%.

Contents of UE positioning GPS reference UE position (sub-tests 3, 4 and 10)

GPS reference UE position

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Latitude sign		0	0	0
Degrees of latitude	degrees	35.744287	37.414831	37.414831
Degrees of longitude	degrees	139.680176	-122.017701	-122.017701
Altitude Direction		0	0	0
Altitude	m	300	50	50
Uncertainty semi-major	m	3000	3000	3000
Uncertainty semi-minor	m	3000	3000	3000
Orientation of major axis	degrees	0	0	0
Uncertainty altitude	m	500	500	500
Confidence	%	68	68	68

Contents of UE positioning GANSS reference UE position (sub-tests 1, 2 and 9)

GANSS reference UE position

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Latitude sign		0	0	0
Degrees Of Latitude	degrees	35.744287	37.414831	37.414831
Degrees Of Longitude	degrees	139.680176	-122.017701	-122.017701
Altitude Direction		0	0	0
Altitude	m	300	50	50
Uncertainty semi-major	m	3000	3000	3000
Uncertainty semi-minor	m	3000	3000	3000
Orientation of major axis	degrees	0	0	0
Uncertainty Altitude	m	500	500	500
Confidence	%	68	68	68

Assistance Data Navigation Model

Contents of UE positioning GPS navigation model (sub-tests 3, 4 and 10)

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	9	9	9

GPS Navigation Model (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
Satellite Status	Boolean	0 (Note)	0 (Note)	0 (Note)

Note: For consistency Satellite Status is also given in file: Perf GPS Navigation model XX.csv

GPS Ephemeris and Clock Correction parameters (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All
C/A or P on L2	Boolean	See file: Perf GPS Navigation model XX.csv
URA Index	Boolean	See file: Perf GPS Navigation model XX.csv
SV Health	Boolean	See file: Perf GPS Navigation model XX.csv
IODC	-	See file: Perf GPS Navigation model XX.csv
L2 P Data Flag	Boolean	See file: Perf GPS Navigation model XX.csv
SF 1 Reserved	-	See file: Perf GPS Navigation model XX.csv
SF 2 Reserved	-	See file: Perf GPS Navigation model XX.csv
SF 3 Reserved	-	See file: Perf GPS Navigation model XX.csv
SF 4 Reserved	-	See file: Perf GPS Navigation model XX.csv
T _{GD}	Sec	See file: Perf GPS Navigation model XX.csv
t _{oc}	Sec	See file: Perf GPS Navigation model XX.csv
af ₂	sec/sec ²	See file: Perf GPS Navigation model XX.csv
af ₁	sec/sec	See file: Perf GPS Navigation model XX.csv
af ₀	Sec	See file: Perf GPS Navigation model XX.csv
C _{rs}	Meters	See file: Perf GPS Navigation model XX.csv
Δn	semi-circles/sec	See file: Perf GPS Navigation model XX.csv
M ₀	semi-circles	See file: Perf GPS Navigation model XX.csv
C _{uc}	Radians	See file: Perf GPS Navigation model XX.csv
E	-	See file: Perf GPS Navigation model XX.csv
C _{us}	Radians	See file: Perf GPS Navigation model XX.csv
(A) ^{1/2}	meters ^{1/2}	See file: Perf GPS Navigation model XX.csv
t _{oe}	Sec	See file: Perf GPS Navigation model XX.csv
Fit Interval Flag	Boolean	See file: Perf GPS Navigation model XX.csv
AODO	Sec	See file: Perf GPS Navigation model XX.csv
C _{ic}	Radians	See file: Perf GPS Navigation model XX.csv
OMEGA ₀	semi-circles	See file: Perf GPS Navigation model XX.csv
C _{is}	Radians	See file: Perf GPS Navigation model XX.csv
i ₀	semi-circles	See file: Perf GPS Navigation model XX.csv
C _{rc}	Meters	See file: Perf GPS Navigation model XX.csv
ω	semi-circles	See file: Perf GPS Navigation model XX.csv
OMEGA _{dot}	semi-circles/sec	See file: Perf GPS Navigation model XX.csv
Idot	semi-circles/sec	See file: Perf GPS Navigation model XX.csv

Contents of UE positioning GANSS navigation model (sub-test 2, 8)

GANSS navigation model

Information Element	Units	Value/remark GNSS All
Non-Broadcast Indication	-	Not present

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	8	8	8

GANSS navigation model (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	4, 5, 10, 11, 18, 19, 20, 21	4, 5, 14, 15, 16, 26, 29, 30	4, 5, 14, 15, 16, 26, 29, 30
SV Health		0 (Note)	0 (Note)	0 (Note)
IOD		0 (Note)	0 (Note)	0 (Note)

Note: For consistency SV Health and IOD are also given in file: Perf Galileo Navigation model XX.csv

GANSS Clock Model (Fields occurring once per satellite)**Galileo Satellite clock model ("Model 1")**

Information Element	Units	Value/remark GNSS All
toc		See file: Perf Galileo Navigation model XX.csv
af2		See file: Perf Galileo Navigation model XX.csv
af1		See file: Perf Galileo Navigation model XX.csv
af0		See file: Perf Galileo Navigation model XX.csv
TGD		See file: Perf Galileo Navigation model XX.csv
SISA		See file: Perf Galileo Navigation model XX.csv

GANSS Orbit Model (Fields occurring once per satellite)**Galileo orbit model: Keplerian Parameters ("Model 1")**

Information Element	Units	Value/remark GNSS All
toe		See file: Perf Galileo Navigation model XX.csv
ω		See file: Perf Galileo Navigation model XX.csv
Δn		See file: Perf Galileo Navigation model XX.csv
M0		See file: Perf Galileo Navigation model XX.csv
OMEGA _{dot}		See file: Perf Galileo Navigation model XX.csv
e		See file: Perf Galileo Navigation model XX.csv
ldot		See file: Perf Galileo Navigation model XX.csv
sqrtA		See file: Perf Galileo Navigation model XX.csv
i0		See file: Perf Galileo Navigation model XX.csv
OMEGA0		See file: Perf Galileo Navigation model XX.csv
Crs		See file: Perf Galileo Navigation model XX.csv
Cis		See file: Perf Galileo Navigation model XX.csv
Cus		See file: Perf Galileo Navigation model XX.csv
Crc		See file: Perf Galileo Navigation model XX.csv
Cic		See file: Perf Galileo Navigation model XX.csv
Cuc		See file: Perf Galileo Navigation model XX.csv

Contents of UE positioning GANSS additional navigation models (sub-tests 1 and 4)

GANSS additional navigation models

Information Element	Units	Value/remark GNSS All
Non-Broadcast Indication	-	Not present

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	8	8	8

GANSS additional navigation models (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21
SV Health		000000 (Note)	000000 (Note)	000000 (Note)
IOD		225 (Note)	195 (Note)	195 (Note)

Note: For consistency SV Health and IOD are also given in file: Perf GLONASS Navigation model XX.csv

GANSS additional clock models (Fields occurring once per satellite)

GLONASS Satellite Clock Model ("Model 4")

Information Element	Units	Value/remark GNSS All
$\tau_n(t_b)$	Seconds	See file: Perf GLONASS Navigation model XX.csv
$\gamma_n(t_b)$		See file: Perf GLONASS Navigation model XX.csv
$\Delta\tau_n$	Seconds	See file: Perf GLONASS Navigation model XX.csv

GANSS additional orbit models (Fields occurring once per satellite)

GLONASS Earth-Centered, Earth-fixed Parameters (“Model 4”)

Information Element	Units	Value/remark GNSS All
E_n	Days	See file: Perf GLONASS Navigation model XX.csv
P1	Minutes	See file: Perf GLONASS Navigation model XX.csv
P2		See file: Perf GLONASS Navigation model XX.csv
M		See file: Perf GLONASS Navigation model XX.csv
$x_n(t_b)$	Km	See file: Perf GLONASS Navigation model XX.csv
$\dot{x}_n(t_b)$	km/sec	See file: Perf GLONASS Navigation model XX.csv
$\ddot{x}_n(t_b)$	km/sec ²	See file: Perf GLONASS Navigation model XX.csv
$y_n(t_b)$	Km	See file: Perf GLONASS Navigation model XX.csv
$\dot{y}_n(t_b)$	km/sec	See file: Perf GLONASS Navigation model XX.csv
$\ddot{y}_n(t_b)$	km/sec ²	See file: Perf GLONASS Navigation model XX.csv
$z_n(t_b)$	Km	See file: Perf GLONASS Navigation model XX.csv
$\dot{z}_n(t_b)$	km/sec	See file: Perf GLONASS Navigation model XX.csv
$\ddot{z}_n(t_b)$	km/sec ²	See file: Perf GLONASS Navigation model XX.csv

Contents of UE positioning GANSS additional navigation model (sub-test 9, 10)

GANSS additional navigation model

Information Element	Units	Value/remark GNSS All
Non-Broadcast Indication	-	Not present

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	14	8	8

GANSS additional navigation model (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28	4, 15, 16, 17, 18, 25, 26, 27	4, 15, 16, 17, 18, 25, 26, 27
SV Health		0 (Note)	0 (Note)	0 (Note)
IOD		0 (Note)	843 (Note)	843 (Note)

Note: For consistency SV Health and IOD are also given in file: Perf Beidou Navigation model XX.csv

GNSS additional Clock Model (Fields occurring once per satellite)**BDS Satellite clock model ("Model 6")**

Information Element	Units	Value/remark GNSS All
AODC		See file: Perf Beidou Navigation model XX.csv
toc	seconds	See file: Perf Beidou Navigation model XX.csv
a0	sec	See file: Perf Beidou Navigation model XX.csv
a1	sec/sec	See file: Perf Beidou Navigation model XX.csv
a2	sec/sec ²	See file: Perf Beidou Navigation model XX.csv
TGD1	sec	See file: Perf Beidou Navigation model XX.csv

GNSS additional Orbit Model (Fields occurring once per satellite)**BDS orbit model: BDS Keplerian Parameters ("Model 6")**

Information Element	Units	Value/remark GNSS All
AODE		See file: Perf Beidou Navigation model XX.csv
URA Index		See file: Perf Beidou Navigation model XX.csv
t _{oe}	seconds	See file: Perf Beidou Navigation model XX.csv
A ^{1/2}	meters ^{1/2}	See file: Perf Beidou Navigation model XX.csv
e		See file: Perf Beidou Navigation model XX.csv
ω	semi-circles	See file: Perf Beidou Navigation model XX.csv
Δn	semi-circles/sec	See file: Perf Beidou Navigation model XX.csv
M ₀	semi-circles	See file: Perf Beidou Navigation model XX.csv
Ω ₀	semi-circles	See file: Perf Beidou Navigation model XX.csv
Ω _{dot}	semi-circles/sec	See file: Perf Beidou Navigation model XX.csv
i ₀	semi-circles	See file: Perf Beidou Navigation model XX.csv
ldot	semi-circles/sec	See file: Perf Beidou Navigation model XX.csv
C _{uc}	radians	See file: Perf Beidou Navigation model XX.csv
C _{us}	radians	See file: Perf Beidou Navigation model XX.csv
C _{rc}	meters	See file: Perf Beidou Navigation model XX.csv
C _{rs}	meters	See file: Perf Beidou Navigation model XX.csv
C _{ic}	radians	See file: Perf Beidou Navigation model XX.csv
C _{is}	radians	See file: Perf Beidou Navigation model XX.csv

Assistance Data Ionospheric Model

Contents of UE positioning GPS ionospheric model (sub-tests 3 and 4)

GPS Ionospheric Model Information Element	Units	Value/remark GNSS All
α_0	Seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	Seconds	79872
β_1	sec/semi-circle	65536
β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

Contents of UE positioning GANSS ionospheric model (sub-test 2, 8)

GANSS ionospheric model

Information Element	Units	Value/remark GNSS All
a_{i0}		64.4
a_{i1}		0
a_{i2}		0
GANSS Ionosphere Regional Storm Flags		
Storm Flag 1		0
Storm Flag 2		0
Storm Flag 3		0
Storm Flag 4		0
Storm Flag 5		0

Contents of UE positioning GANSS additional ionospheric model (sub-test 1, 9, 10)

GANSS additional ionospheric model (QZSS)

Information Element	Units	Value/remark GNSS All
Data Id		00
α_0	Seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	Seconds	79872
β_1	sec/semi-circle	65536
β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

GANSS additional ionospheric model (BDS)

Information Element	Units	Value/remark GNSS All
Data Id		01
α_0	Seconds	4.6566129 10E-9
α_1	sec/semi-circle	1.4901161 10E-8
α_2	sec/(semi-circle) ²	-5.96046 10E-8
α_3	sec/(semi-circle) ³	-5.96046 10E-8
β_0	Seconds	79872
β_1	sec/semi-circle	65536

β_2	sec/(semi-circle) ²	-65536
β_3	sec/(semi-circle) ³	-393216

Assistance Data Almanac

Contents of UE positioning GPS almanac (sub-tests 3 and 4)

GPS Almanac (Field occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
WN _a	Weeks	1669	1691	1691
Complete Almanac Provided (Note 1)		TRUE	TRUE	TRUE
Note 1: This IE is only present for Rel-10 onwards.				

Satellite Information

Information Element	Units	Value/remark GNSS All
Number of satellites	-	27

GPS Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All
DataID	-	See file: Perf GPS Almanac XX.csv

GPS Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	PRNs: 1, 2, 4, 5, 6, 7, 8, 9, 10, 11, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 30, 32	PRNs: 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 30	PRNs: 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 30

GPS Almanac (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All
e	Dimensionless	See file: Perf GPS Almanac XX.csv
toa	Sec	See file: Perf GPS Almanac XX.csv
δi	semi-circles	See file: Perf GPS Almanac XX.csv
OMEGADOT	semi-circles/sec	See file: Perf GPS Almanac XX.csv
SV Health	Boolean	See file: Perf GPS Almanac XX.csv
$A^{1/2}$	meters ^{1/2}	See file: Perf GPS Almanac XX.csv
OMEGA ₀	semi-circles	See file: Perf GPS Almanac XX.csv
M ₀	semi-circles	See file: Perf GPS Almanac XX.csv
ω	semi-circles	See file: Perf GPS Almanac XX.csv
af ₀	Seconds	See file: Perf GPS Almanac XX.csv
af ₁	sec/sec	See file: Perf GPS Almanac XX.csv

Contents of UE positioning GANSS almanac (sub-tests 1, 2 and 4)

GANSS almanac: sub-tests 1, 4 (Field occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Week Number	Weeks	N/A	N/A	N/A
Complete Almanac Provided (Note 1)		TRUE	TRUE	TRUE
Note 1: This IE is only present for Rel-10 onwards.				

Satellite Information GLO-KP: sub-tests 1, 4

Information Element	Units	Value/remark GNSS All
Number of satellites	-	24

GANSS almanac: sub-tests 1, 4 (Fields occurring once per satellite)**GLONASS Keplerian Parameters (“Model 5”)**

Information Element	Units	Value/remark GNSS All
N^A	Days	See file: Perf GLONASS Almanac XX.csv
n^A	-	Slot Numbers: 1, 2, 322, 23, 24
H_n^A	-	See file: Perf GLONASS Almanac XX.csv
λ_n^A	semi-circles	See file: Perf GLONASS Almanac XX.csv
$t_{\lambda_n^A}$	Seconds	See file: Perf GLONASS Almanac XX.csv
Δi_n^A	semi-circles	See file: Perf GLONASS Almanac XX.csv
ΔT_n^A	sec/orbit-period	See file: Perf GLONASS Almanac XX.csv
$\Delta T_DOT_n^A$	sec/orbit-period	See file: Perf GLONASS Almanac XX.csv
ε_n^A	dimensionless	See file: Perf GLONASS Almanac XX.csv
ω_n^A	semi-circles	See file: Perf GLONASS Almanac XX.csv
τ_n^A	Seconds	See file: Perf GLONASS Almanac XX.csv
C_n^A	dimensionless	See file: Perf GLONASS Almanac XX.csv
M_n^A	dimensionless	See file: Perf GLONASS Almanac XX.csv

GANSS almanac: sub-test 2, 8 (Field occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Week Number	Weeks	645	666	666
Complete Almanac Provided (Note 1)		TRUE	TRUE	TRUE

Note 1: This IE is only present for Rel-10 onwards.

GANSS almanac: sub-test 2, 8 (Field occurring once per message)**Galileo Keplerian Parameters (“Model 1”)**

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
T_{oa}		147000	147000	147000
IOD_a		0	0	0

Satellite Information KP: sub-test 2, 8

Information Element	Units	Value/remark GNSS All
Number of satellites	-	30

GNSS almanac: sub-test 2, 8 (Fields occurring once per satellite)**Galileo Keplerian Parameters (“Model 1”)**

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SV ID	-	PRN: 1, 2, 3, ..., 29, 30	PRN: 1, 2, 3, ..., 29, 30	PRN: 1, 2, 3, ..., 29, 30

GNSS almanac: sub-test 2, 8 (Fields occurring once per satellite)**Galileo Keplerian Parameters (“Model 1”)**

Information Element	Units	Value/remark GNSS All
E	-	See file: Perf Galileo Almanac XX.csv
δi	semi-circles	See file: Perf Galileo Almanac XX.csv
OMEGADOT	semi-circles/sec	See file: Perf Galileo Almanac XX.csv
SV Health KP	-	See file: Perf Galileo Almanac XX.csv
$\delta A^{1/2}$	(meters) ^{1/2}	See file: Perf Galileo Almanac XX.csv
OMEGA ₀	semi-circles	See file: Perf Galileo Almanac XX.csv
M ₀	semi-circles	See file: Perf Galileo Almanac XX.csv
ω	semi-circles	See file: Perf Galileo Almanac XX.csv
af ₀	Seconds	See file: Perf Galileo Almanac XX.csv
af ₁	sec/sec	See file: Perf Galileo Almanac XX.csv

GNSS almanac: sub-test 9, 10 (Field occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Week Number	Weeks	313	335	335
Complete Almanac Provided (Note 1)		TRUE	TRUE	TRUE
Note 1: This IE is only present for Rel-10 onwards.				

GNSS almanac: sub-test 9, 10 (Field occurring once per message)**BDS Keplerian Parameters (“Model 7”)**

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
T _{oa}		147456	147456	147456
IOD _a		0	0	0

Satellite Information KP: sub-test 9, 10

Information Element	Units	Value/remark GNSS All
Number of satellites	-	30

GNSS almanac: sub-test 9, 10 (Fields occurring once per satellite)**BDS Keplerian Parameters (“Model 7”)**

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SV ID	-	PRN: 1, 2, 3, ..., 29, 30	PRN: 1, 2, 3, ..., 29, 30	PRN: 1, 2, 3, ..., 29, 30

GNSS almanac: sub-test 9, 10 (Fields occurring once per satellite)**BDS Keplerian Parameters (“Model 7”)**

Information Element	Units	Value/remark GNSS All
E	-	See file: Perf Beidou Almanac XX.csv
δi	semi-circles	See file: Perf Beidou Almanac XX.csv
OMEGADOT	semi-circles/sec	See file: Perf Beidou Almanac XX.csv
SV Health KP	-	See file: Perf Beidou Almanac XX.csv
$\text{delta } A^{1/2}$	(meters) ^{1/2}	See file: Perf Beidou Almanac XX.csv
OMEGA ₀	semi-circles	See file: Perf Beidou Almanac XX.csv
M ₀	semi-circles	See file: Perf Beidou Almanac XX.csv
ω	semi-circles	See file: Perf Beidou Almanac XX.csv
af ₀	Seconds	See file: Perf Beidou Almanac XX.csv
af ₁	sec/sec	See file: Perf Beidou Almanac XX.csv

Assistance Data UTC Model

Contents of UE positioning GPS UTC model (sub-test 4)

GPS UTC model

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
A ₁	sec/sec	0	0	0
A ₀	Seconds	0	0	0
t _{tot}	Seconds	249856	77824	77824
WN _t	Weeks	133	155	155
Δt_{LS}	Seconds	15	15	15
WN _{LSF}	Weeks	158	158	158
DN	Days	7	7	7
Δt_{LSF}	Seconds	16	16	16

Assistance Data Acquisition Assistance and Reference Measurement Information

Contents of UE positioning GPS acquisition assistance (sub-tests 3 and 4)

GPS Acquisition Assistance (Fields occurring once per message)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GPS TOW msec	msec	1860000 ms. Start time. Add number of ms as required. (Note 1)	432060000 ms. Start time. Add number of ms as required. (Note 1)	432060000ms. Start time. Add number of ms as required. (Note 1)
UTRAN GPS reference time		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
UTRAN GPS timing of cell frames		Note 2	Note 2	-
CHOICE mode		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	-
FDD: Primary CPICH Info		100	100	-
TDD: cell parameters id		0	0	
SFN		Note 2	Note 2	-
UE Positioning GPS ReferenceTime Uncertainty		For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	For Sensitivity Fine Time Assistance test case: '51' (10.2uS). Otherwise: '125' (2.127s)	'125' (2.127s)
<p>Note 1: GPS TOW msec</p> <p>This is the value in ms of GPS TOW msec when the GPS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GPS scenario is used, the GPS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario.</p> <p>The actual value of GPS TOW msec to be used in the Acquisition Assistance IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>For all TTFF test cases a random offset is then added to the value of GPS TOW msec as described in subclause 6.2.7.2.</p> <p>This "final GPS TOW msec" value is then also used to determine the value of the Acquisition Assistance Information Elements marked as "Time varying".</p> <p>Note 2: UTRAN GPS timing of cell frames and SFN</p> <p>The values of UTRAN GPS timing of cell frames (before the addition of the random offset) and SFN shall be calculated at the time the IE is required. The accuracy of the relationship between the two fields shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met.</p> <p>A random offset is then added to the value of UTRAN GPS timing of cell frames as described in subclause 6.2.7.2</p>				

Satellite Information

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	9	9	9

GPS Acquisition Assistance (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28

GPS Acquisition Assistance (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All	Release
Doppler (0 th order term)	Hz	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Doppler (1 st order term)	Hz/sec	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Doppler Uncertainty	Hz	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Code Phase	Chips	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Integer Code Phase	-	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
GPS Bit number	-	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Code Phase Search Window	Chips	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Azimuth	Deg	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Elevation	Deg	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	
Azimuth LSB	Deg	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	Rel-10 onwards
Elevation LSB	Deg	Time varying. See file: Perf GPS Acquisition assist XX.csv (Note)	Rel-10 onwards
Note: Acquisition Assistance Information Elements This field is "Time varying" and its value depends on the "final GPS TOW msec" as described above. The value of this field to be used shall be determined by taking the "final GPS TOW msec" value and selecting the nearest field value in the Perf GPS Acquisition assist.csv file corresponding to the value of "final current GPS TOW msec".			

Contents of UE positioning GANSS reference measurement information (sub-tests 1, 2 and 4)

GANSS reference measurement information: sub-test 1, 4 (Fields occurring once per message)

Information Element	Units	Value/remark GNSS All
GANSS Signal ID		Not present

Satellite Information: sub-test 1, 4

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	8	8	8

GANSS reference measurement information: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21

GANSS reference measurement information: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All	Release
Doppler (0 th order term)	m/s	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Code Phase Search Window		Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Azimuth	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Elevation	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest1_4_XX.csv (Note)	Rel-10 onwards
<p>Note: For sub-test 1: this field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Perf GANSS reference measurement information subtest1_4.csv file corresponding to the value of "current GANSS TOD".</p> <p>For sub-test 4: this field is "Time varying" and its value depends on the "current GPS TOW msec". The value of this field to be used shall be determined by taking the "current GPS TOW msec" value and selecting the field value in the Perf GANSS reference measurement information subtest1_4.csv file corresponding to the value of "current GPS TOW msec".</p>			

GANSS reference measurement information: sub-test 2, 8 (Fields occurring once per message)

Information Element	Units	Value/remark GNSS All
GANSS Signal ID		Not present

Satellite Information: sub-test 2, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	8	8	8

GANSS reference measurement information: sub-test 2, 8 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	4, 5, 10, 11, 18, 19, 20, 21	4, 5, 14, 15, 16, 26, 29, 30	4, 5, 14, 15, 16, 26, 29, 30

GANSS reference measurement information: sub-test 2, 8 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All	Release
Doppler (0 th order term)	m/s	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Code Phase Search Window		Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Azimuth	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Elevation	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	Rel-10 onwards
Elevation LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest2 XX.csv (Note)	Rel-10 onwards
Note: This field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Perf GANSS reference measurement information subtest2.csv file corresponding to the value of "current GANSS TOD".			

GANSS reference measurement information: sub-test 9, 10 (Fields occurring once per message)

Information Element	Units	Value/remark GNSS All
GANSS Signal ID		Not present

Satellite Information: sub-test 9, 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	14	8	8

GANSS reference measurement information: sub-test 9, 10 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28	4, 15, 16, 17, 18, 25, 26, 27	4, 15, 16, 17, 18, 25, 26, 27

GANSS reference measurement information: sub-test 9, 10 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS All	Release
Doppler (0 th order term)	m/s	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Doppler (1 st order term)	m/s ²	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Doppler Uncertainty	m/s	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Integer Code Phase	ms	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Code Phase Search Window		Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Azimuth	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Elevation	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	
Azimuth LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	Rel-12 onwards
Elevation LSB	Degrees	Time varying. See file: Perf GANSS reference measurement information subtest9 XX.csv (Note)	Rel-12 onwards
Note: This field is "Time varying" and its value depends on the "current GANSS TOD". The value of this field to be used shall be determined by taking the "current GANSS TOD" value and selecting the field value in the Perf GANSS reference measurement information subtest9.csv file corresponding to the value of "current GANSS TOD".			

Assistance Data Auxiliary Information

Contents of UE positioning GANSS auxiliary information (sub-tests 1, 3 and 4)

GANSS auxiliary information: sub-test 1, 4 (Fields occurring once per message)

Information Element	Units	Value/remark GNSS All
GANSS-ID-3		Present (GLONASS)

Aux Info List: sub-test 1, 4

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	8	8	8

GANSS auxiliary information: sub-test 1, 4 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21
Signals Available	-	10000000 (G1)	10000000 (G1)	10000000 (G1)
Channel number	-	5, 6, 1, -2, -7, -3, 3, 2	1, 6, -2, -7, -1, 3, 2, 4	1, 6, -2, -7, -1, 3, 2, 4

GANSS auxiliary information: sub-test 3 (Fields occurring once per message)

Information Element	Units	Value/remark GNSS All
GANSS-ID-1		Present (Modernized GPS)

Aux Info List: sub-test 3

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
Number of satellites	-	9	9	9

GNSS auxiliary information: sub-test 3 (Fields occurring once per satellite)

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
SatID	-	PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
Signals Available	-	L1C and others as supported by the UE	L1C and others as supported by the UE	L1C and others as supported by the UE

Assistance Data GNSS ID

Contents of GNSS ID

GNSS ID: sub-test 1, 4

Information Element	Units	Value/remark GNSS All
GNSS ID		3 (GLONASS)

GNSS ID: sub-test 2, 8

Information Element	Units	Value/remark GNSS All
GNSS ID		Not present (Galileo)

GNSS ID: sub-test 3

Information Element	Units	Value/remark GNSS All
GNSS ID		1 (Modernized GPS)

GNSS ID: sub-test 9, 10

Information Element	Units	Value/remark GNSS All
GNSS ID		4 (BDS)

6.2.7.4 Contents of Information elements for A-GNSS Minimum performance testing in TS 37.571-1 subclause 7

GNSS REFERENCE TIME:

GNSS-ReferenceTime: sub-tests 1, 5, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-SystemTime				
gnss-TimeID		0 (gps)	0 (gps)	0 (gps)
gnss-DayNumber	days	11683	11835	11835
gnss-TimeOfDay	s	1860s. Start time. (Note 1)	60s. Start time. (Note 1)	60s. Start time. (Note 1)
gnss-TimeOfDayFrac-msec	ms	0 (Note 1)	0 (Note 1)	0 (Note 1)
notificationOfLeapSecond		Not present	Not present	Not present
gps-TOW-Assist				
satelliteID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
tlmWord		10922 (for all PRNs)	10922 (for all PRNs)	10922 (for all PRNs)
antiSpooF		1 (for all PRNs)	1 (for all PRNs)	1 (for all PRNs)
alert		0 (for all PRNs)	0 (for all PRNs)	0 (for all PRNs)
tlmRsvdBits		2 (for all PRNs)	2 (for all PRNs)	2 (for all PRNs)
referenceTimeUnc		'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
GNSS-ReferenceTimeForOneCell				
networkTime				
secondsFromFrameStructureStart	s	Note 2	Note 2	
fractionalSecondsFromFrameStructureStart	250ns	Note 2	Note 2	
frameDrift		0	0	
cellID				
CHOICE eUTRA				
physCellId		0	0	
cellGlobalIdEUTRA		'0000 0000'B	'0000 0000'B	
earfcn		Note 3	Note 3	
referenceTimeUnc		'24' (11.11us)	'24' (11.11us)	
<p>Note 1: gnss-TimeOfDay and gnss-TimeOfDayFrac-msec. This is the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario. The actual value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met. For all TTFF test cases a random offset is then added to the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec as described in subclause 6.2.7.2.</p> <p>Note 2: secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart. The values of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart (before the addition of the random offset) shall be calculated at the time the IE is required. The accuracy of the values used shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of 37.571-1 [6], shall be met. A random offset is then added to the value of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart as described in subclause 6.2.7.2.</p> <p>Note 3: earfcn is defined in TS 36.508 [20] subclause 4.3.1 for the frequency band under test (see TS 37.571-1 [6] subclause 4.1.1)</p>				

GNSS-ReferenceTime: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-SystemTime				
gnss-TimeID		4 (glonass)	4 (glonass)	4 (glonass)
gnss-DayNumber	days	5844	5996	5996
gnss-TimeOfDay	s	12645 s. Start time. (Note 1)	10845 s. Start time. (Note 1)	10845 s. Start time. (Note 1)
gnss-TimeOfDayFrac-msec	ms	0 (Note 1)	0 (Note 1)	0 (Note 1)
notificationOfLeapSecond		00	00	00
gps-TOW-Assist		Not present	Not present	Not present
referenceTimeUnc		'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
GNSS-ReferenceTimeForOneCell networkTime				
secondsFromFrameStructure Start	s	Note 2	Note 2	
fractionalSecondsFromFrame StructureStart	250ns	Note 2	Note 2	
frameDrift		0	0	
cellID				
CHOICE eUTRA				
physCellId		0	0	
cellGlobalIdEUTRA		'0000 0000'B	'0000 0000'B	
earfcn		Note 3	Note 3	
referenceTimeUnc		'24' (11.11us)	'24' (11.11us)	
<p>Note 1: gnss-TimeOfDay and gnss-TimeOfDayFrac-msec This is the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario. The actual value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met. For all TTFF test cases a random offset is then added to the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec as described in subclause 6.2.7.2.</p> <p>Note 2: secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart. The values of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart (before the addition of the random offset) shall be calculated at the time the IE is required. The accuracy of the values used shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of 37.571-1 [6], shall be met. A random offset is then added to the value of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart as described in subclause 6.2.7.2.</p> <p>Note 3: earfcn is defined in TS 36.508 [20] subclause 4.3.1 for the frequency band under test (see TS 37.571-1 [6] subclause 4.1.1)</p>				

GNSS-ReferenceTime: sub-test 3

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-SystemTime				
gnss-TimeID		3 (galileo)	3 (galileo)	3 (galileo)
gnss-DayNumber		4536	4688	4688
gnss-TimeOfDay		1860 s. Start time. (Note 1)	60 s. Start time. (Note 1)	60 s. Start time. (Note 1)
gnss-TimeOfDayFrac-msec		0 (Note 1)	0 (Note 1)	0 (Note 1)
notificationOfLeapSecond		Not present	Not present	Not present
gps-TOW-Assist		Not present	Not present	Not present
referenceTimeUnc		'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
GNSS-ReferenceTimeForOneCell networkTime				
secondsFromFrameStructureStart	s	Note 2	Note 2	
fractionalSecondsFromFrameStructureStart	250ns	Note 2	Note 2	
frameDrift		0	0	
cellID				
CHOICE eUTRA				
physCellId		0	0	
cellGlobalIdEUTRA		'0000 0000'B	'0000 0000'B	
earfcn		Note 3	Note 3	
referenceTimeUnc		'24' (11.11us)	'24' (11.11us)	
<p>Note 1: gnss-TimeOfDay and gnss-TimeOfDayFrac-msec This is the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario. The actual value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met. For all TTFF test cases a random offset is then added to the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec as described in subclause 6.2.7.2.</p> <p>Note 2: secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart. The values of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart (before the addition of the random offset) shall be calculated at the time the IE is required. The accuracy of the values used shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of 37.571-1 [6], shall be met. A random offset is then added to the value of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart as described in subclause 6.2.7.2.</p> <p>Note 3: earfcn is defined in TS 36.508 [20] subclause 4.3.1 for the frequency band under test (see TS 37.571-1 [6] subclause 4.1.1)</p>				

GNSS-ReferenceTime: sub-tests 9

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-SystemTime				
gnss-TimeID		5 (bds)	5 (bds)	5 (bds)
gnss-DayNumber	days	2191	2343	2343
gnss-TimeOfDay	s	1846s. Start time. (Note 1)	46s. Start time. (Note 1)	46s. Start time. (Note 1)
gnss-TimeOfDayFrac-msec	ms	0 (Note 1)	0 (Note 1)	0 (Note 1)
notificationOfLeapSecond		Not present	Not present	Not present
gps-TOW-Assist		Not present	Not present	Not present
referenceTimeUnc		'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds) Absent for Sensitivity Fine Time Assistance test case. Present otherwise	'117' (2.274 seconds)
gnss-ReferenceTimeForCells		Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Present for Sensitivity Fine Time Assistance test case. Absent otherwise	Absent
GNSS-ReferenceTimeForOneCell networkTime				
secondsFromFrameStructureStart	s	Note 2	Note 2	
fractionalSecondsFromFrameStructureStart	250ns	Note 2	Note 2	
frameDrift		0	0	
cellID				
CHOICE eUTRA physCellId		0	0	
cellGlobalIdEUTRA		'0000 0000'B	'0000 0000'B	
earfcn		Note 3	Note 3	
referenceTimeUnc		'24' (11.11us)	'24' (11.11us)	
<p>Note 1: gnss-TimeOfDay and gnss-TimeOfDayFrac-msec. This is the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec when the GNSS scenario is initially started in the GNSS simulator. For all TTFF test cases, each time a GNSS scenario is used, the GNSS start time shall be advanced by 120 seconds from the value last used so that, at the time the fix is made, it is at least 2 minutes later than the previous fix made with that scenario. The actual value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec to be used in the Reference Time IE (before the addition of the random offset, if applicable) shall be calculated at the time the IE is required by adding the elapsed time since the time the scenario was started in the GNSS simulator to this value. The accuracy shall be such that the Maximum Test System Uncertainty for Coarse Time Assistance, specified in Table C.1.2 of TS 37.571-1 [6], shall be met. For all TTFF test cases a random offset is then added to the value of gnss-TimeOfDay and gnss-TimeOfDayFrac-msec as described in subclause 6.2.7.2.</p> <p>Note 2: secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart. The values of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart (before the addition of the random offset) shall be calculated at the time the IE is required. The accuracy of the values used shall be such that the Maximum Test System Uncertainty for Fine Time Assistance, specified in Table C.1.2 of 37.571-1 [6], shall be met. A random offset is then added to the value of secondsFromFrameStructureStart and fractionalSecondsFromFrameStructureStart as described in subclause 6.2.7.2.</p> <p>Note 3: earfcn is defined in TS 36.508 [20] subclause 4.3.1 for the frequency band under test (see TS 37.571-1 [6] subclause 4.1.1)</p>				

GNSS REFERENCE LOCATION:

GNSS-ReferenceLocation

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
threeDlocation				
latitudeSign		0	0	0
degreesLatitude	degrees	35.744287	37.414831	37.414831
degreesLongitude	degrees	139.680176	-122.017701	-122.017701
altitudeDirection		0	0	0
altitude	m	300	50	50
uncertaintySemiMajor	m	3000	3000	3000
uncertaintySemiMinor	m	3000	3000	3000
orientationMajorAxis	degrees	0	0	0
uncertaintyAltitude	m	500	500	500
confidence	%	68	68	68

GNSS IONOSPHERIC MODEL:

GNSS-IonosphericModel: sub-tests 1, 2, 4, 5, 9, 10

Information Element	Units	Value/remark GNSS All
klobucharModel		
dataID		00
alfa0	Seconds	4.6566129 10E-9
alfa1	sec/semi-circle	1.4901161 10E-8
alfa2	sec/(semi-circle) ²	-5.96046 10E-8
alfa3	sec/(semi-circle) ³	-5.96046 10E-8
beta0	Seconds	79872
beta1	sec/semi-circle	65536
beta2	sec/(semi-circle) ²	-65536
beta3	sec/(semi-circle) ³	-393216
neQuickModel		Not present

GNSS-IonosphericModel: sub-test 3, 8

Information Element	Units	Value/remark GNSS All
GNSS-IonospericModel		
klobucharModel		Not present
neQuickModel		
ai0		64.4
ai1		0
ai2		0
ionoStormFlag1		0
ionoStormFlag2		0
ionoStormFlag3		0
ionoStormFlag4		0
ionoStormFlag5		0

GNSS TIME MODEL LIST:

GNSS-TimeModelList: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-TimeModelRefTime		1860 (s)	432060 (s)	432060 (s)
tA0		0	0	0
gnss-TO-ID		1 (GPS)	1 (GPS)	1 (GPS)
weekNumber		1669	1690	1690
deltaT		15	15	15

GNSS-TimeModelList: sub-test 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-TimeModelRefTime		1860 (s)	432060 (s)	432060 (s)
tA0		0	0	0
gnss-TO-ID		1 (GPS)	1 (GPS)	1 (GPS)
weekNumber		1669	1690	1690
deltaT		0	0	0

GNSS-TimeModelList: sub-test 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-TimeModelRefTime		1860 (s)	432060 (s)	432060 (s)
tA0		0	0	0
gnss-TO-ID		1 (GPS)	1 (GPS)	1 (GPS)
weekNumber		1669	1690	1690
deltaT		13	13	13

GNSS NAVIGATION MODEL:

GNSS-NavigationModel: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
nonBroadcastFlag		0	0	0
gnss-SatelliteList		(SIZE) 9	(SIZE) 9	(SIZE) 9

GNSS-NavModelSatelliteElement: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
svHealth		0	0	0
iod		0	0	0

GNSS-NavModelSatelliteElement: sub-test 1

Information Element	Units	Value/remark GNSS All
gnss-ClockModel		
nav-ClockModel		
navToc		See file: Perf GNSS Navigation Model subtest1 XX.csv
navaf2		See file: Perf GNSS Navigation Model subtest1 XX.csv
navaf1		See file: Perf GNSS Navigation Model subtest1 XX.csv
navaf0		See file: Perf GNSS Navigation Model subtest1 XX.csv
navTgd		See file: Perf GNSS Navigation Model subtest1 XX.csv
gnss-OrbitModel		
nav-KeplerianSet		
navURA		See file: Perf GNSS Navigation Model subtest1 XX.csv
navFitFlag		See file: Perf GNSS Navigation Model subtest1 XX.csv
navToe		See file: Perf GNSS Navigation Model subtest1 XX.csv
navOmega		See file: Perf GNSS Navigation Model subtest1 XX.csv
navDeltaN		See file: Perf GNSS Navigation Model subtest1 XX.csv
navM0		See file: Perf GNSS Navigation Model subtest1 XX.csv
navOmegaADot		See file: Perf GNSS Navigation Model subtest1 XX.csv
navE		See file: Perf GNSS Navigation Model subtest1 XX.csv
navIDot		See file: Perf GNSS Navigation Model subtest1 XX.csv
navAPowerHalf		See file: Perf GNSS Navigation Model subtest1 XX.csv
navI0		See file: Perf GNSS Navigation Model subtest1 XX.csv
navOmegaA0		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCrs		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCis		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCus		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCrc		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCic		See file: Perf GNSS Navigation Model subtest1 XX.csv
navCuc		See file: Perf GNSS Navigation Model subtest1 XX.csv
addNAVparam		
ephemCodeOnL2		See file: Perf GNSS Navigation Model subtest1 XX.csv
ephemL2Pflag		See file: Perf GNSS Navigation Model subtest1 XX.csv
reserved1		See file: Perf GNSS Navigation Model subtest1 XX.csv
reserved2		See file: Perf GNSS Navigation Model subtest1 XX.csv
reserved3		See file: Perf GNSS Navigation Model subtest1 XX.csv
reserved4		See file: Perf GNSS Navigation Model subtest1 XX.csv
ephemAODA		See file: Perf GNSS Navigation Model subtest1 XX.csv

GNSS-NavigationModel: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
nonBroadcastFlag		0	0	0
gnss-SatelliteList		(SIZE) 8	(SIZE) 8	(SIZE) 8

GNSS-NavModelSatelliteElement: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21
svHealth		00000000	00000000	00000000
iod		225	195	195

GNSS-NavModelSatelliteElement: sub-test 2

Information Element	Units	Value/remark GNSS All
gnss-ClockModel		
glonass-ClockModel		
gloTau		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloGamma		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloDeltaTau		See file: Perf GNSS Navigation Model subtest2 XX.csv
gnss-OrbitModel		
glonass-ECEF		
gloEn		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloP1		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloP2		See file: Perf GNSS Navigation Model subtest2 XX.csv
glom		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloX		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloXdot		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloXdotdot		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloY		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloYdot		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloYdotdot		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloZ		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloZdot		See file: Perf GNSS Navigation Model subtest2 XX.csv
gloZdotdot		See file: Perf GNSS Navigation Model subtest2 XX.csv

GNSS-NavigationModel: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
nonBroadcastFlag		0	0	0
gnss-SatelliteList		(SIZE) 8	(SIZE) 8	(SIZE) 8

GNSS-NavModelSatelliteElement: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		4, 5, 10, 11, 18, 19, 20, 21	4, 5, 14, 15, 16, 26, 29, 30	4, 5, 14, 15, 16, 26, 29, 30
svHealth		0	0	0
iod		0	0	0

GNSS-NavModelSatelliteElement: sub-test 3

Information Element	Units	Value/remark GNSS All
gnss-ClockModel		
standardClockModelList		(SIZE) 1
stanClockToc		See file: Perf GNSS Navigation Model subtest3 XX.csv
stanClockAF2		See file: Perf GNSS Navigation Model subtest3 XX.csv
stanClockAF1		See file: Perf GNSS Navigation Model subtest3 XX.csv
stanClockAF0		See file: Perf GNSS Navigation Model subtest3 XX.csv
stanClockTgd		See file: Perf GNSS Navigation Model subtest3 XX.csv
sisa		See file: Perf GNSS Navigation Model subtest3 XX.csv
gnss-OrbitModel		
keplerianSet		
keplerToe		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerW		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerDeltaN		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerM0		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerOmegaDot		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerE		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerIDot		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerAPowerHalf		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerI0		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerOmega0		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCrs		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCis		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCus		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCrc		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCic		See file: Perf GNSS Navigation Model subtest3 XX.csv
keplerCuc		See file: Perf GNSS Navigation Model subtest3 XX.csv

GNSS-NavModel: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-NavModel		See GNSS-NavModel: sub-test 5
gnss-ID		4 (glonass)
GNSS-NavModel		See GNSS-NavModel: sub-test 2

GNSS-NavModel: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
nonBroadcastFlag		0	0	0
gnss-SatelliteList		(SIZE) 9	(SIZE) 9	(SIZE) 9

GNSS-NavModelSatelliteElement: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
svHealth		0	0	0
iod		0	0	0

GNSS-NavModelSatelliteElement: sub-test 5

Information Element	Units	Value/remark GNSS All
gnss-ClockModel		
nav-ClockModel		
navToc		See file: Perf GNSS Navigation Model subtest5 XX.csv
navaf2		See file: Perf GNSS Navigation Model subtest5 XX.csv
navaf1		See file: Perf GNSS Navigation Model subtest5 XX.csv
navaf0		See file: Perf GNSS Navigation Model subtest5 XX.csv
navTgd		See file: Perf GNSS Navigation Model subtest5 XX.csv
gnss-OrbitModel		
nav-KeplerianSet		
navURA		See file: Perf GNSS Navigation Model subtest5 XX.csv
navFitFlag		See file: Perf GNSS Navigation Model subtest5 XX.csv
navToe		See file: Perf GNSS Navigation Model subtest5 XX.csv
navOmega		See file: Perf GNSS Navigation Model subtest5 XX.csv
navDeltaN		See file: Perf GNSS Navigation Model subtest5 XX.csv
navM0		See file: Perf GNSS Navigation Model subtest5 XX.csv
navOmegaADot		See file: Perf GNSS Navigation Model subtest5 XX.csv
navE		See file: Perf GNSS Navigation Model subtest5 XX.csv
navIDot		See file: Perf GNSS Navigation Model subtest5 XX.csv
navAPowerHalf		See file: Perf GNSS Navigation Model subtest5 XX.csv
navI0		See file: Perf GNSS Navigation Model subtest5 XX.csv
navOmegaA0		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCrs		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCis		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCus		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCrc		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCic		See file: Perf GNSS Navigation Model subtest5 XX.csv
navCuc		See file: Perf GNSS Navigation Model subtest5 XX.csv
addNAVparam		
ephemCodeOnL2		See file: Perf GNSS Navigation Model subtest5 XX.csv
ephemL2Pflag		See file: Perf GNSS Navigation Model subtest5 XX.csv
reserved1		See file: Perf GNSS Navigation Model subtest5 XX.csv
reserved2		See file: Perf GNSS Navigation Model subtest5 XX.csv
reserved3		See file: Perf GNSS Navigation Model subtest5 XX.csv
reserved4		See file: Perf GNSS Navigation Model subtest5 XX.csv
ephemAODA		See file: Perf GNSS Navigation Model subtest5 XX.csv

GNSS-NavigationModel: sub-test 9, 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
nonBroadcastFlag		0	0	0
gnss-SatelliteList		(SIZE) 14	(SIZE) 8	(SIZE) 8

GNSS-NavModelSatelliteElement: sub-test 9, 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28	4, 15, 16, 17, 18, 25, 26, 27	4, 15, 16, 17, 18, 25, 26 27
svHealth		0	0	0
iod		0	843	843

GNSS-NavModelSatelliteElement: sub-test 9, 10

Information Element	Units	Value/remark
gnss-ClockModel		
BDS-ClockModel-r12		(SIZE) 1
bdsAODC-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsToc-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsA0-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsA1-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsA2-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsTgd1-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
gnss-OrbitModel		
BDS-KeplerianSet-r12		
bdsAODE-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsURAI-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsToe-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsAPowerHalf-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsE-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsW-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsDeltaN-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsM0-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsOmega0-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsOmegaDot-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsI0-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsIDot-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCuc-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCus-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCrc-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCrs-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCic-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv
bdsCis-r12		See file: Perf GNSS Navigation Model subtest9 XX.csv

GNSS ACQUISITION ASSISTANCE:**GNSS-AcquisitionAssistance: sub-test 1**

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AcquisitionAssistance				
gnss-SignalID		0 (GPS L1 C/A)	0 (GPS L1 C/A)	0 (GPS L1 C/A)
gnss-AcquisitionAssistList		(SIZE) 9	(SIZE) 9	(SIZE) 9
confidence-r10	%	98	98	98

GNSS-AcquisitionAssistElement: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28

GNSS-AcquisitionAssistElement: sub-test 1

Information Element	Units	Value/remark GNSS All
doppler0		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
doppler1		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertainty		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
codePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
intCodePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
codePhaseSearchWindow		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
azimuth		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
elevation		Time varying. See file: Perf GNSS Acquisition Assistance subtest1 XX.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Perf GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AcquisitionAssistance				
gnss-SignalID		0 (GLONASS G1)	0 (GLONASS G1)	0 (GLONASS G1)
gnss-AcquisitionAssistList		(SIZE) 8	(SIZE) 8	(SIZE) 8
confidence-r10	%	98	98	98

GNSS-AcquisitionAssistElement: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21

GNSS-AcquisitionAssistElement: sub-test 2

Information Element	Units	Value/remark GNSS All
doppler0		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
doppler1		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
dopplerUncertainty		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
codePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
intCodePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
codePhaseSearchWindow		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
azimuth		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
elevation		Time varying. See file: Perf GNSS Acquisition Assistance subtest2 XX.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Perf GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AcquisitionAssistance				
gnss-SignalID		0 (Galileo E1)	0 (Galileo E1)	0 (Galileo E1)
gnss-AcquisitionAssistList		(SIZE) 8	(SIZE) 8	(SIZE) 8
confidence-r10	%	98	98	98

GNSS-AcquisitionAssistElement: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		SV IDs: 4, 5, 10, 11, 18, 19, 20, 21	SV IDs: 4, 5, 14, 15, 16, 26, 29, 30	SV IDs: 4, 5, 14, 15, 16, 26, 29, 30

GNSS-AcquisitionAssistElement: sub-test 3, 8

Information Element	Units	Value/remark GNSS All
doppler0		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
doppler1		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
dopplerUncertainty		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
codePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
intCodePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
codePhaseSearchWindow		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
azimuth		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
elevation		Time varying. See file: Perf GNSS Acquisition Assistance subtest3 XX.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Perf GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistance: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 5
gnss-ID		4 (glonass)
GNSS-AcquisitionAssistance		See GNSS-AcquisitionAssistance: sub-test 2

GNSS-AcquisitionAssistance: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AcquisitionAssistance				
gnss-SignalID		0 (GPS L1 C/A)	0 (GPS L1 C/A)	0 (GPS L1 C/A)
gnss-AcquisitionAssistList		(SIZE) 9	(SIZE) 9	(SIZE) 9
confidence-r10	%	98	98	98

GNSS-AcquisitionAssistElement: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28

GNSS-AcquisitionAssistElement: sub-test 5

Information Element	Units	Value/remark GNSS All
doppler0		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
doppler1		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
dopplerUncertainty		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
codePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
intCodePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
codePhaseSearchWindow		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
azimuth		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
elevation		Time varying. See file: Perf GNSS Acquisition Assistance subtest5 XX.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest1 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Perf GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS-AcquisitionAssistElement: sub-test 9, 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		SV IDs: 1, 2, 3, 4, 6, 7, 17, 18, 21, 22, 23, 26, 27, 28	SV IDs: 4, 15, 16, 17, 18, 25, 26, 27	SV IDs: 4, 15, 16, 17, 18, 25, 26, 27

GNSS-AcquisitionAssistElement: sub-test 9, 10

Information Element	Units	Value/remark GNSS All
doppler0		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
doppler1		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
dopplerUncertainty		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
codePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
intCodePhase		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
codePhaseSearchWindow		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
azimuth		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
elevation		Time varying. See file: Perf GNSS Acquisition Assistance subtest9 XX.csv (Note)
codePhase1023		Time varying. Calculated from "codePhase", see file: GNSS Acquisition Assistance subtest9 XX.csv (Note)
dopplerUncertaintyExt-r10		Not present
Note: This field is "Time varying" and its value depends on the "current gnss-TimeOfDay". The value of this field to be used shall be determined by taking the "current gnss-TimeOfDay" value and selecting the field value in the Perf GNSS Acquisition Assistance subtestX.csv file corresponding to the value of "current gnss-TimeOfDay".		

GNSS ALMANAC:

GNSS-Almanac: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-Almanac				
weekNumber		1669	1691	1691
toa		249856	77824	77824
ioda		Not present	Not present	Not present
completeAlmanacProvided		1 (TRUE)	1 (TRUE)	1 (TRUE)
gnss-AlmanacList		(SIZE) 24	(SIZE) 24	(SIZE) 24

GNSS-AlmanacElement: sub-test 1

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
keplerianNAV-Almanac				
svID		PRNs: 1, 4, 5, 6, 7, 8, 9, 10, 11, 14, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 32	PRNs: 1, 2, 3, 5, 6, 7, 8, 10, 11, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 25, 26, 27, 28, 30	PRNs: 1, 2, 3, 5, 6, 7, 8, 10, 11, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 25, 26, 27, 28, 30

GNSS-AlmanacElement: sub-test 1

Information Element	Units	Value/remark GNSS All
navAlmE		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmDeltal		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmOMEGADOT		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmSVHealth		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmSqrtA		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmOMEGAo		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmOmega		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmMo		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmaf0		See file: Perf GNSS Almanac subtest1 XX.csv
navAlmaf1		See file: Perf GNSS Almanac subtest1 XX.csv

GNSS-Almanac: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-Almanac				
completeAlmanacProvided		1 (TRUE)	1 (TRUE)	1 (TRUE)
gnss-AlmanacList		(SIZE) 24	(SIZE) 24	(SIZE) 24

GNSS-AlmanacElement: sub-test 2

Information Element	Units	Value/remark GNSS All
keplerianGLONASS		
gloAlm-NA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmNA		Slot Numbers: 1, 2, 322, 23, 24
gloAlmHA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmLambdaA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmtlambdaA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmDeltala		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmDeltaTA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmDeltaTdotA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmEpsilonA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmOmegaA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmTauA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmCA		See file: Perf GNSS Almanac subtest2 XX.csv
gloAlmMA		See file: Perf GNSS Almanac subtest2 XX.csv

GNSS-Almanac: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-Almanac				
weekNumber		645	666	666
toa		147000	147000	147000
iota		Not present	Not present	Not present
completeAlmanacProvided		1 (TRUE)	1 (TRUE)	1 (TRUE)
gnss-AlmanacList		(SIZE) 30	(SIZE) 30	(SIZE) 30

GNSS-Almanac: sub-test 3, 8

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
keplerianAlmanacSet				
svID		SV IDs: 1, 2, 3, ..., 29, 30	SV IDs: 1, 2, 3, ..., 29, 30	SV IDs: 1, 2, 3, ..., 29, 30

GNSS-AlmanacElement: sub-test 3, 8

Information Element	Units	Value/remark GNSS All
kepAlmanacE		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacDeltal		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacOmegaDot		See file: Perf GNSS Almanac subtest3 XX.csv
kepSVHealth		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacAPowerHalf		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacOmega0		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacW		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacM0		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacAF0		See file: Perf GNSS Almanac subtest3 XX.csv
kepAlmanacAF1		See file: Perf GNSS Almanac subtest3 XX.csv

GNSS-Almanac: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
GNSS-Almanac		See GNSS-Almanac: sub-test 5
gnss-ID		4 (glonass)
GNSS-Almanac		See GNSS-Almanac: sub-test 2

GNSS-Almanac: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-Almanac				
weekNumber		1669	1691	1691
toa		249856	77824	77824
ioda		Not present	Not present	Not present
completeAlmanacProvided		1 (TRUE)	1 (TRUE)	1 (TRUE)
gnss-AlmanacList		(SIZE) 27	(SIZE) 27	(SIZE) 27

GNSS-AlmanacElement: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
keplerianNAV-Almanac				
svID		PRNs: 1, 2, 4, 5, 6, 7, 8, 9, 10, 11, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 30, 32	PRNs: 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 30	PRNs: 1, 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 25, 26, 27, 28, 30

GNSS-AlmanacElement: sub-test 5

Information Element	Units	Value/remark GNSS All
navAlmE		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmDeltal		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmOMEGADOT		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmSVHealth		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmSqrtA		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmOMEGAo		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmOmega		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmMo		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmaf0		See file: Perf GNSS Almanac subtest5 XX.csv
navAlmaf1		See file: Perf GNSS Almanac subtest5 XX.csv

GNSS-Almanac: sub-test 9, 10

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-Almanac				
weekNumber		312	334	334
toa		147000	147000	147000
ioda		0	0	0
completeAlmanacProvided		1 (TRUE)	1 (TRUE)	1 (TRUE)
gnss-AlmanacList		(SIZE) 30	(SIZE) 30	(SIZE) 30

GNSS-AlmanacElement: sub-test 9, 10

Information Element	Units	Value/remark
BDS-AlmanacSet-r12		
svID		SV IDs: 1, 2, 3, ..., 29, 30
bdsAlmToa-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmSqrtA-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmE-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmW-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmM0-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmOmega0-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmOmegaDot-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmDeltal-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmA0-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsAlmA1-r12		See file: Perf GNSS Almanac subtest9 XX.csv
bdsSvHealth-r12		See file: Perf GNSS Almanac subtest9 XX.csv

GNSS UTC MODEL:

GNSS-UTC-Model: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-UTC-Model		
utcModel1		

UTC-ModelSet1: sub-test 5

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
gnss-Utc-A1		0	0	0
gnss-Utc-A0		0	0	0
gnss-Utc-Tot		249856	77824	77824
gnss-Utc-WNt		133	155	155
gnss-Utc-DeltaTIs		15	15	15
gnss-Utc-WNIsf		158	158	158
gnss-Utc-DN		7	7	7
gnss-Utc-DeltaTIsf		16	16	16

GNSS AUXILIARY INFORMATION:

GNSS-AuxiliaryInformation: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AuxiliaryInformation				
gnss-ID-GLONASS		(SIZE) 8	(SIZE) 8	(SIZE) 8

GNSS-ID-GLONASS-SatElement: sub-test 2

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		Slot Numbers: 3, 4, 5, 9, 10, 18, 19, 20	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21	Slot Numbers: 1, 8, 9, 10, 16, 19, 20, 21
signalsAvailable		G1	G1	G1
channelNumber		5, 6, 1, -2, -7, -3, 3, 2	1, 6, -2, -7, -1, 3, 2, 4	1, 6, -2, -7, -1, 3, 2, 4

GNSS-AuxiliaryInformation: sub-test 4

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
GNSS-AuxiliaryInformation				
gnss-ID-GPS		(SIZE) 9	(SIZE) 9	(SIZE) 9

GNSS-ID-GPS-SatElement: sub-test 4

Information Element	Units	Value/remark GNSS #1	Value/remark GNSS #2	Value/remark GNSS #5
svID		PRNs: 1, 4, 11, 17, 19, 20, 23, 28, 32	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28	PRNs: 1, 7, 8, 11, 15, 17, 26, 27, 28
signalsAvailable		L1C and others as supported by the UE	L1C and others as supported by the UE	L1C and others as supported by the UE

GNSS- AuxiliaryInformation: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 1, or 2 if UE supports multiple GPS signals
gnss-ID		0 (gps) if UE supports multiple GPS signals
GNSS-AuxiliaryInformation		See GNSS-AuxiliaryInformation: sub-test 4
gnss-ID		4 (glonass)
GNSS-AuxiliaryInformation		See GNSS-AuxiliaryInformation: sub-test 2

GNSS GENERIC ASSISTANCE DATA

GNSS- GenericAssistData: sub-test 1

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		0 (gps)

GNSS- GenericAssistData: sub-test 2

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		4 (glonass)

GNSS- GenericAssistData: sub-test 3

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		3 (galileo)

GNSS- GenericAssistData: sub-test 5

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		4 (glonass)

GNSS- GenericAssistData: sub-test 8

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		3 (galileo)

GNSS- GenericAssistData: sub-test 9

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 1
gnss-ID		5 (bds)

GNSS- GenericAssistData: sub-test 10

Information Element	Units	Value/remark GNSS All
GNSS-GenericAssistData		(SIZE) 2
gnss-ID		0 (gps)
gnss-ID		5 (bds)

7 OTDOA

7.1 OTDOA Assistance data for OTDOA signalling tests

7.1.1 General

The OTDOA assistance data that shall be used for the OTDOA signalling tests is defined in TS 37.571-2 [7].

7.2 OTDOA Assistance data for OTDOA measurement tests

7.2.1 General

This subclause defines the OTDOA assistance data that shall be used for the OTDOA measurement tests defined in TS 37.571-1 [6].

7.2.2 OTDOA Assistance Data

This subclause defines the OTDOA assistance data elements which shall be provided to the UE in the OTDOA measurement tests defined in TS 37.571-1 [6].

OTDOA REFERENCE CELL INFO:

OTDOA-ReferenceCellInfo for test cases 9.1.1, 9.1.2, 9.2.1 and 9.2.2

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 1
physCellId	0	Set according to sub-clause 4.7.1 and Table 9.1.1.4.1-1, Table 9.1.2.4.1-1, Table 9.2.1.4.1-1 and Table 9.2.2.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0001'B Cell Identity: '0000 0000'B	
earfcnRef	Not present	Same as the serving cell
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth	n50	
prs-ConfigurationIndex	Test case 9.1.1: 171 Test case 9.1.2: 174 Test case 9.2.1: 181 Test case 9.2.2: 184	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	Test cases 9.1.1 and 9.1.2: '1111 0000'	
po16-r9	Test cases 9.2.1 and 9.2.2: '11111111 00000000'	

OTDOA-ReferenceCellInfo for test cases 9.1.3 and 9.1.4

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 1
physCellId	0	Set according to sub-clause 4.7.1 and Table 9.1.3.4.1-1 and Table 9.1.4.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0001'B Cell Identity: '0000 0000'B	
earfcnRef	Not present	Same as the serving cell
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth	Test 1, 2: n6 Test 3, 4: n50	
prs-ConfigurationIndex	Test case 9.1.3: Test 1, 2: 12, Test 3, 4: 2 Test case 9.1.4: Test 1, 2: 9, Test 3, 4: 14	
numDL-Frames	Test1, 2: sf-6 Test 3, 4: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	'1111 0000'	

OTDOA-ReferenceCellInfo for test cases 9.2.4 and 9.2.5

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 1
physCellId	0	Set according to sub-clause 4.7.1 and Table 9.2.4.4.1-1 and Table 9.2.5.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0000 0001'B Cell Identity: '0000 0000'B	
earfcnRef	Not present	Same as the serving cell
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth	Test 1: n6 Test 2: n50	
prs-ConfigurationIndex	Test case 9.2.4: Test 1: 12, Test 2: 2 Test case 9.2.5: Test 1: 15, Test 2: 4	
numDL-Frames	Test1: sf-6 Test 2: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	'1111 0000'	

OTDOA NEIGHBOUR CELL INFO LIST:

OTDOA-NeighbourCellInfoList for test cases 9.1.1, 9.1.2, 9.2.1 and 9.2.2

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See tables of Sequence data values below	
cellGlobalId	For values of cellidentity see tables of Sequence data values below	
earfcn	Test case 9.1.1: Not present Test case 9.1.2: Not present Test case 9.2.1: 2 Test case 9.2.2: 2	Test cases 9.1.1 and 9.1.2: same as for the reference cell
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	n50	
prs-ConfigurationIndex	Test case 9.1.1: 171 Test case 9.1.2: 174 Test case 9.2.1: 171 Test case 9.2.2: 174	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See tables of Sequence data values below	
po16-r9	See tables of Sequence data values below	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Test case 9.1.1: Not present Test case 9.1.2: Not present Test case 9.2.1: 0 Test case 9.2.2: 0	Test cases 9.1.1 and 9.1.2: slot timing is the same as for reference cell
prs-SubframeOffset	Test case 9.1.1: Not present Test case 9.1.2: Not present Test case 9.2.1: 310 Test case 9.2.2: 310	
expectedRSTD	See tables of Sequence data values below	
expectedRSTD-Uncertainty	51	About 5 μ s

Sequence data values for 15 instances of sequence for test cases 9.1.1 and 9.1.2

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 2	6 (Note 1)	'0000 0000 0000 0000 0100'B	'0000 0110'B	'0000 1111'	8222	Note 2
Cell 3	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	'1111 0000'	8222	Note 3
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'0000 1111'	8162	Note 4
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	Note 4
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	Note 4
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	Note 4
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8190	Note 4
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	Note 4
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	Note 4
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	Note 4
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	Note 4
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	Note 4
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	Note 4
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	Note 4
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	Note 4

Note 1: Set according to sub-clause 4.7.1 and Table 9.1.1.4.1-1 and Table 9.1.2.4.1-1 in TS 37.571-1 [6]
Note 2: Data for cell 2 is used at a random position in the first 7 instances of the sequence
Note 3: Data for cell 3 is used at a random position in the final 8 instances of the sequence
Note 4: Data for this cell is used at any position in the 15 instances of the sequence

Sequence data values for 15 instances of sequence for test cases 9.2.1 and 9.2.2

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po16-r9	Value expectedR STD	Comment
		Value eNB ID	Value Cell Identity			
Cell 2	6 (Note 1)	'0000 0000 0000 0000 0100'B	'0000 0110'B	'00000000 11111111'	8172	Note 2
Cell 3	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	'11111111 00000000'	8212	Note 3
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'00000000 11111111'	8162	Note 4
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'11111111 00000000'	8218	Note 4
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'00000000 11111111'	8211	Note 4
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'11111111 00000000'	8175	Note 4
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'00000000 11111111'	8190	Note 4
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'11111111 00000000'	8200	Note 4
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'00000000 11111111'	8182	Note 4
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'11111111 00000000'	8207	Note 4
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'00000000 11111111'	8182	Note 4
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'11111111 00000000'	8218	Note 4
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'00000000 11111111'	8182	Note 4
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'11111111 00000000'	8192	Note 4
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'00000000 11111111'	8162	Note 4

Note 1: Set according to sub-clause 4.7.1 and Table 9.2.1.4.1-1 and Table 9.2.2.4.1-1 in TS 37.571-1 [6]
Note 2: Data for cell 2 is used at a random position in the first 7 instances of the sequence
Note 3: Data for cell 3 is used at a random position in the final 8 instances of the sequence
Note 4: Data for this cell is used at any position in the 15 instances of the sequence

OTDOA-NeighbourCellInfoList for test cases 9.1.3 and 9.1.4

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See table of Sequence data values below	
cellGlobalId	For values of cellidentity see table of Sequence data values below	
earfcn	Not present	Same as for the reference cell
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test 1, 2: n6 Test 3, 4: n50	
prs-ConfigurationIndex	Test case 9.1.3: 2 Test case 9.1.4: Test 1, 2: 9, Test 3, 4: 14	
numDL-Frames	Test 1, 2: sf-6 Test 3, 4: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values below	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	Not present	
expectedRSTD	See table of Sequence data values below	
expectedRSTD-Uncertainty	51	About 5 μ s

OTDOA-NeighbourCellInfoList for test cases 9.2.4 and 9.2.5

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See table of Sequence data values below	
cellGlobalId	For values of cellidentity see table of Sequence data values below	
earfcn	2	
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test 1: n6 Test 2: n50	
prs-ConfigurationIndex	Test case 9.2.4: Test1: 19, Test 2: 12 Test case 9.2.5: Test 1: 35, Test 2: 14	
numDL-Frames	Test 1: sf-6 Test 2: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values below	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	Test case 9.2.4: Test 1: 7, Test 2: 10 Test case 9.2.5: Test 1: 20, Test 2: 10	
expectedRSTD	See table of Sequence data values below	
expectedRSTD-Uncertainty	51	About 5 μ s

Sequence data values for 15 instances of sequence for test cases 9.1.3 and 9.1.4

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedR STD	Comment
		Value eNB ID	Value Cell Identity			
Cell 2 (Test 1)	6 (Note)	'0000 0000 0000 0000 0100'B	'0000 0110'B	'1111 0000'	8202	
Cell 2 (Test 2)	7 (Note)	'0000 0000 0000 0000 0110'B	'0000 0111'B	'1111 0000'	8182	
Cell 2 (Test 3)	6 (Note)	'0000 0000 0000 0000 0100'B	'0000 0110'B	'1111 0000'	8182	
Cell 2 (Test 4)	9 (Note)	'0000 0000 0000 0000 0100'B	'0000 1001'B	'1111 0000'	8202	
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'0000 1111'	8162	
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8190	
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	
Dummy cell	126	'0000 0000 0000 0000 1100'B	'0111 1110'B	'1111 0000'	8208	

Note: Set according to sub-clause 4.7.1 and Table 9.1.3.4.1-1 and Table 9.1.4.4.1-1 in TS 37.571-1 [6]

Sequence data values for 15 instances of sequence for test cases 9.2.4 and 9.2.5

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 2	1 (Note)	'0000 0000 0000 0000 0001'B	'0000 0001'B	'1111 0000'	8202	
Dummy cell	6	'0000 0000 0000 0000 0100'B	'0000 0110'B	'0000 1111'	8162	
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8190	
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	
Dummy cell	126	'0000 0000 0000 0000 1100'B	'0111 1110'B	'1111 0000'	8208	

Note: Set according to sub-clause 4.7.1 and Table 9.2.4.4.1-1 and Table 9.2.5.4.1-1 in TS 37.571-1 [6]

7.3 OTDOA Assistance data for OTDOA measurement tests for Carrier Aggregation

7.3.1 General

This subclause defines the OTDOA assistance data that shall be used for the OTDOA measurement tests for Carrier aggregation defined in TS 37.571-1 [6].

7.3.2 OTDOA Assistance Data

This subclause defines the OTDOA assistance data elements which shall be provided to the UE in the OTDOA measurement tests for Carrier Aggregation defined in TS 37.571-1 [6].

OTDOA REFERENCE CELL INFO:

Table 7.3.2-1: OTDOA-ReferenceCellInfo for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 2
physCellId	6	Set according to sub-clause 4.7.1 and Table 10.1.4.1-1 and Table 10.2.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0100'B Cell Identity: '0000 0110'B	
earfcnRef	2	SCC
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth	Test cases 10.1, 10.2, 10.2D: n50 Test cases 10.1A, 10.2A: n100 Test cases 10.1B, 10.1C, 10.2B, 10.2C: n25	
prs-ConfigurationIndex	Test cases 10.1, 10.1A, 10.1B,10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	Test 1: '00001111'	
po16-r9	Test 2: '000000011111111'	

Table 7.3.2-2: OTDOA-ReferenceCellInfo for test cases 10.3, 10.3A, 10.3A_1, 10.3B, 10.3C, 10.4, 10.4A, 10.4A_1, 10.4B, 10.4C, 10.4D

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 2
physCellId	7	Set according to sub-clause 4.7.1 and Table 10.3.4.1-1 and Table 10.4.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0110'B Cell Identity: '0000 0111'B	
earfcnRef	2	
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth	Test cases 10.3, 10.4, 10.4D: n50 Test cases 10.3A, 10.3A_1, 10.4A, 10.4A_1: n100 Test cases 10.3B, 10.3C, 10.4B, 10.4C: n25	
prs-ConfigurationIndex	Test cases 10.3, 10.3A, 10.3A_1, 10.3B, 10.3C: 2 Test cases 10.4, 10.4A, 10.4A_1, 10.4B, 10.4C, 10.4D: 14	
numDL-Frames	Test cases 10.3, 10.3A, 10.3A_1, 10.4, 10.4A, 10.4A_1, 10.4D: sf-1 Test cases 10.3B, 10.3C, 10.4B, 10.4C: sf-2	
prs-MutingInfo-r9 CHOICE		
po8-r9	'1111 0000'	

Table 7.3.2-3: OTDOA-ReferenceCellInfo for test cases 10.5, 10.6

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 3
physCellId	6	Set according to sub-clause 4.7.1 and Table 10.5.4.1-1 and Table 10.6.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0010'B Cell Identity: '0000 0110'B	
earfcnRef	3	SCC2
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	Test case 10.5: 191 Test case 10.6: 194	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	Test 1: '11110000'	
po16-r9	Test 2: '1111111100000000'	

Table 7.3.2-4: OTDOA-ReferenceCellInfo for test cases 10.7, 10.8

Information Element	Value/remark	Comment
OTDOA-ReferenceCellInfo		Cell 3
physCellId	7	Set according to sub-clause 4.7.1 and Table 10.7.4.1-1 and Table 10.8.4.1-1 in TS 37.571-1 [6]
cellGlobalId	cellidentity (E-UTRAN Cell Identity): eNB ID: '0000 0000 0000 0000 0010'B Cell Identity: '0000 00111'B	
earfcnRef	3	SCC2
antennaPortConfig	Not present	Same as the serving cell
cpLength	Normal	
prsInfo SEQUENCE		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	191	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz: sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	'1111 0000'	

OTDOA NEIGHBOUR CELL INFO LIST:

Table 7.3.2-5: OTDOA-NeighbourCellInfoList for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D, Test 1

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See table of Sequence data values below in Table 7.3.2-6	
cellGlobalId	For values of cellidentity see table of Sequence data values below in Table 7.3.2-6	
earfcn	Not present	Same as for the reference cell (SCC)
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test cases 10.1, 10.2, 10.2D: n50 Test cases 10.1A, 10.2A: n100 Test cases 10.1B, 10.1C, 10.2B, 10.2C: n25	
prs-ConfigurationIndex	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values below in Table 7.3.2-6	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	0	
expectedRSTD	See table of Sequence data values below in Table 7.3.2-6	
expectedRSTD-Uncertainty	51	About 5 μ s

Table 7.3.2-6: Sequence data values for 15 instances of sequence for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D, Test 1

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 3	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	'1111 0000'	8212	Note 2
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'0000 1111'	8162	Note 3
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	Note 3
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	Note 3
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	Note 3
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8190	Note 3
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	Note 3
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	Note 3
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	Note 3
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	Note 3
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	Note 3
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	Note 3
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	Note 3
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	Note 3
Dummy cell	127	'0000 0000 0000 0000 1100'B	'0111 1111'B	'1111 0000'	8192	Note 3

Note 1: Set according to sub-clause 4.7.1 and Table 10.1.4.1-1 and Table 10.2.4.1-1 in TS 37.571-1 [6]
Note 2: Data for Cell 3 is used at a random position in the last 8 instances of the sequence
Note 3: Data for this cell is used at any position in the 15 instances of the sequence

Table 7.3.2-7: OTDOA-NeighbourCellInfoList for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D, Test 2

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(2)) OF SEQUENCE		
SEQUENCE (SIZE(8)) OF SEQUENCE	Sequence contains 8 instances of the following data.	
physCellId	See table of Sequence data values for sequence 1 below in Table 7.3.2-8	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 1 below in Table 7.3.2-8	
earfcn	1	earfcn 1 is PCC
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test cases 10.1, 10.2, 10.1C, 10.2C: n50 Test cases 10.1A, 10.2A, 10.2D: n100 Test cases 10.1B, 10.2B: n25	
prs-ConfigurationIndex	See table of Sequence data values for sequence 1 below in Table 7.3.2-8	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po16-r9	See table of Sequence data values for sequence 1 below in Table 7.3.2-8	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	See table of Sequence data values for sequence 1 below in Table 7.3.2-8	
expectedRSTD	See table of Sequence data values for sequence 1 below in Table 7.3.2-8	
expectedRSTD-Uncertainty	51	About 5 μ s
SEQUENCE (SIZE(7)) OF SEQUENCE	Sequence contains 7 instances of the following data.	
physCellId	See table of Sequence data values for sequence 2 below in Table 7.3.2-9	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 2 below in Table 7.3.2-9	
earfcn	Not present	Same as for the reference cell (SCC)
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test cases 10.1, 10.2, 10.2D: n50 Test cases 10.1A, 10.2A: n100 Test cases 10.1B, 10.1C, 10.2B, 10.2C: n25	
prs-ConfigurationIndex	See table of Sequence data values for sequence 2 below in Table 7.3.2-9	
numDL-Frames	sf-1	
prs-MutingInfo-r9 CHOICE		
po16-r9	See table of Sequence data values for sequence 2 below in Table 7.3.2-9	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	

prs-SubframeOffset	See table of Sequence data values for sequence 2 below in Table 7.3.2-9	
expectedRSTD	See table of Sequence data values for sequence 2 below in Table 7.3.2-9	
expectedRSTD-Uncertainty	51	About 5 μ s

Table 7.3.2-8: Sequence data values for 8 instances of sequence for sequence 1 for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D, Test 2

Cell	Value phys CellId	Value cellidentity (E-UTRAN Cell Identity)		Value prs-ConfigurationIndex	Value po16-r9	Value prs-SubframeOffset	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity					
Cell 1	0 (Note 1)	'0000 0000 0000 0000 0001'B	'0000 0000'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'1111111 1 0000000 0'	310	8172	Note 2
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8162	Note 4
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8211	Note 4
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8190	Note 4
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8182	Note 4
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8182	Note 4
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8182	Note 4
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 171 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 174	'0000000 0 1111111 1'	310	8162	Note 4

Note 1: Set according to sub-clause 4.7.1 and Table 10.1.4.1-1 and Table 10.2.4.1-1 in TS 37.571-1 [6]
Note 2: Data for Cell 1 is used at a random position in the first 7 instances of the sequence
Note 3: Void
Note 4: Data for this cell is used at any position in the 8 instances of the sequence

Table 7.3.2-9: Sequence data values for 7 instances of sequence for sequence 2 for test cases 10.1, 10.1A, 10.1B, 10.1C, 10.2, 10.2A, 10.2B, 10.2C, 10.2D, Test 2

Cell	Value phys CellId	Value cellidentity (E-UTRAN Cell Identity)		Value prs-ConfigurationIndex	Value po16-r9	Value prs-SubframeOffset	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity					
Cell 3	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8212	Note 3
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8218	Note 4
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8175	Note 4
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8200	Note 4
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8207	Note 4
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8218	Note 4
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	Test cases 10.1, 10.1A, 10.1B, 10.1C: 181 Test cases 10.2, 10.2A, 10.2B, 10.2C, 10.2D: 184	'1111111 1 0000000 0'	0	8192	Note 4
<p>Note 1: Set according to sub-clause 4.7.1 and Table 10.1.4.1-1 and Table 10.2.4.1-1 in TS 37.571-1 [6]</p> <p>Note 2: Void</p> <p>Note 3: Data for Cell 3 is used at a random position in the 7 instances of the sequence</p> <p>Note 4: Data for this cell is used at any position in the 7 instances of the sequence</p>								

Table 7.3.2-10: OTDOA-NeighbourCellInfoList for test cases 10.3, 10.3A, 10.3A_1, 10.3B, 10.3C, 10.4, 10.4A, 10.4A_1, 10.4B, 10.4C, 10.4D

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See table of Sequence data values below in Table 7.3.2-11	
cellGlobalId	For values of cellidentity see table of Sequence data values below in Table 7.3.2-11	
earfcn	Not present	Same as for the reference cell
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth	Test cases 10.3, 10.4, 10.4D: n50 Test cases 10.3A, 10.3A_1, 10.4A, 10.4A_1: n100 Test cases 10.3B, 10.3C, 10.4B, 10.4C: n25	
prs-ConfigurationIndex	Test cases 10.3, 10.3A, 10.3A_1, 10.3B, 10.3C: 2 Test cases 10.4, 10.4A, 10.4A_1, 10.4B, 10.4C, 10.4D: 14	
numDL-Frames	Test cases 10.3, 10.3A, 10.3A_1, 10.4, 10.4A, 10.4A_1, 10.4D: sf-1 Test cases 10.3B, 10.3C, 10.4B, 10.4C: sf-2	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values below in Table 7.3.2-11	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	Not present	
expectedRSTD	See table of Sequence data values below in Table 7.3.2-11	
expectedRSTD-Uncertainty	51	About 5 μ s

Table 7.3.2-11: Sequence data values for 15 instances of sequence for test cases 10.3, 10.3A, 10.3A_1, 10.3B, 10.3C, 10.4, 10.4A, 10.4A_1, 10.4B, 10.4C, 10.4D

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 3	10 (Note)	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8172	
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'0000 1111'	8162	
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	
Dummy cell	9	'0000 0000 0000 0000 0100'B	'0000 1001'B	'1111 0000'	8190	
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	
Dummy cell	126	'0000 0000 0000 0000 1100'B	'0111 1110'B	'1111 0000'	8208	

Note: Set according to sub-clause 4.7.1 and Table 10.3.4.1-1 and Table 10.4.4.1-1 in TS 37.571-1 [6]

Table 7.3.2-12: OTDOA-NeighbourCellInfoList for test cases 10.5, 10.6, Test 1

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(1)) OF SEQUENCE		
SEQUENCE (SIZE(15)) OF SEQUENCE	Sequence contains 15 instances of the following data.	
physCellId	See table of Sequence data values below in Table 7.3.2-13	
cellGlobalId	For values of cellidentity see table of Sequence data values below in Table 7.3.2-13	
earfcn	Not present	Same as for the reference cell (SCC2)
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	Test case 10.5: 191 Test case 10.6: 194	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values below in Table 7.3.2-13	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	0	
expectedRSTD	See table of Sequence data values below in Table 7.3.2-13	
expectedRSTD-Uncertainty	51	About 5 μ s

Table 7.3.2-13: Sequence data values for 15 instances of sequence for test cases 10.5, 10.6, Test 1

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 4	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	'00001111'	8212	Note 2
Dummy cell	1	'0000 0000 0000 0000 0001'B	'0000 0001'B	'0000 1111'	8162	Note 3
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'1111 0000'	8218	Note 3
Dummy cell	3	'0000 0000 0000 0000 0010'B	'0000 0011'B	'0000 1111'	8211	Note 3
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'1111 0000'	8175	Note 3
Dummy cell	10	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8190	Note 3
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'0000 1111'	8200	Note 3
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	Note 3
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'0000 1111'	8207	Note 3
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	Note 3
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'1111 0000'	8218	Note 3
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	Note 3
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	Note 3
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	Note 3
Dummy cell	127	'0000 0000 0000 0000 1100'B	'0111 1111'B	'1111 0000'	8192	Note 3

Note 1: Set according to sub-clause 4.7.1 and Table 10.5.4.1-1 and Table 10.6.4.1-1 in TS 37.571-1 [6]
Note 2: Data for Cell 4 is used at a random position in the last 8 instances of the sequence
Note 3: Data for this cell is used at any position in the 15 instances of the sequence

Table 7.3.2-14: OTDOA-NeighbourCellInfoList for test cases 10.5, 10.6, Test 2

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(3)) OF SEQUENCE		
SEQUENCE (SIZE(4)) OF SEQUENCE	Sequence contains 4 instances of the following data.	
physCellId	See table of Sequence data values for sequence 1 below in Table 7.3.2-15	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 1 below in Table 7.3.2-15	
earfcn	1	PCC
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	See table of Sequence data values for sequence 1 below in Table 7.3.2-15	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po16-r9	See table of Sequence data values for sequence 1 below in Table 7.3.2-15	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	310	
expectedRSTD	See table of Sequence data values for sequence 1 below in Table 7.3.2-15	
expectedRSTD-Uncertainty	51	About 5 μ s
SEQUENCE (SIZE(4)) OF SEQUENCE	Sequence contains 4 instances of the following data.	
physCellId	See table of Sequence data values for sequence 2 below in Table 7.3.2-16	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 2 below in Table 7.3.2-16	
earfcn	2	SCC1
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	See table of Sequence data values for sequence 2 below in Table 7.3.2-16	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po16-r9	See table of Sequence data values for sequence 2 below in Table 7.3.2-16	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	320	
expectedRSTD	See table of Sequence data values for sequence 2 below in Table 7.3.2-16	
expectedRSTD-Uncertainty	51	About 5 μ s

SEQUENCE (SIZE(7)) OF SEQUENCE	Sequence contains 7 instances of the following data.	
physCellId	See table of Sequence data values for sequence 3 below in Table 7.3.2-17	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 3 below in Table 7.3.2-17	
earfcn	Not present	Same as for the reference cell (SCC2)
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	See table of Sequence data values for sequence 3 below in Table 7.3.2-17	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po16-r9	See table of Sequence data values for sequence 3 below in Table 7.3.2-17	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	0	
prs-SubframeOffset	Not present	
expectedRSTD	See table of Sequence data values for sequence 3 below in Table 7.3.2-17	
expectedRSTD-Uncertainty	51	About 5 μs

Table 7.3.2-15: Sequence data values for 4 instances of sequence for sequence 1 for test cases 10.5, 10.6, Test 2

Cell	Value phys CellId	Value cellidentity (E-UTRAN Cell Identity)		Value prs-ConfigurationIndex	Value po16-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity				
Cell 1	0 (Note 1)	'0000 0000 0000 0000 0001'B	'0000 0000'B	Test cases 10.5: 171 Test cases 10.6: 174	'11111111 00000000'	8172	Note 2
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	Test cases 10.5: 171 Test cases 10.6: 174	'00000000 11111111'	8182	Note 3
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	Test cases 10.5: 171 Test cases 10.6: 174	'00000000 11111111'	8182	Note 3
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	Test cases 10.5: 171 Test cases 10.6: 174	'00000000 11111111'	8162	Note 3
Note 1: Set according to sub-clause 4.7.1 and Table 10.5.4.1-1 and Table 10.6.4.1-1 in TS 37.571-1 [6] Note 2: Data for Cell 1 is used at a random position in the 4 instances of the sequence Note 3: Data for this cell is used at any position in the 4 instances of the sequence							

Table 7.3.2-16: Sequence data values for 4 instances of sequence for sequence 2 for test cases 10.5, 10.6, Test 2

Cell	Value phys CellId	Value cellidentity (E-UTRAN Cell Identity)		Value prs-ConfigurationIndex	Value po16-r9	Value expectedR STD	Comment
		Value eNB ID	Value Cell Identity				
Cell 2	3 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 0011'B	Test cases 10.5: 181 Test cases 10.6: 184	'0000000011 111111'	8212	Note 2
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	Test cases 10.5: 181 Test cases 10.6: 184	'11111111 00000000'	8207	Note 3
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	Test cases 10.5: 181 Test cases 10.6: 184	'11111111 00000000'	8218	Note 3
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	Test cases 10.5: 181 Test cases 10.6: 184	'11111111 00000000'	8192	Note 3
Note 1: Set according to sub-clause 4.7.1 and Table 10.5.4.1-1 and Table 10.6.4.1-1 in TS 37.571-1 [6]							
Note 2: Data for Cell 2 is used at a random position in the 4 instances of the sequence							
Note 3: Data for this cell is used at any position in the 4 instances of the sequence							

Table 7.3.2-17: Sequence data values for 7 instances of sequence for sequence 3 for test cases 10.5, 10.6, Test 2

Cell	Value phys CellId	Value cellidentity (E-UTRAN Cell Identity)		Value prs-ConfigurationIndex	Value po16-r9	Value expectedR STD	Comment
		Value eNB ID	Value Cell Identity				
Cell 4	12 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 1100'B	Test cases 10.5: 191 Test cases 10.6: 194	'0000000011 111111'	8212	Note 2
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8218	Note 3
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8175	Note 3
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8200	Note 3
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8207	Note 3
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8218	Note 3
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	Test cases 10.5: 191 Test cases 10.6: 194	'11111111 00000000'	8192	Note 3
Note 1: Set according to sub-clause 4.7.1 and Table 10.5.4.1-1 and Table 10.6.4.1-1 in TS 37.571-1 [6]							
Note 2: Data for Cell 4 is used at a random position in the 7 instances of the sequence							
Note 3: Data for this cell is used at any position in the 7 instances of the sequence							

Table 7.3.2-18: OTDOA-NeighbourCellInfoList for test cases 10.7, 10.8

Information Element	Value/remark	Comment
OTDOA-NeighbourCellInfoList ::= SEQUENCE (SIZE(3)) OF SEQUENCE		
SEQUENCE (SIZE(4)) OF SEQUENCE	Sequence contains 4 instances of the following data.	
physCellId	See table of Sequence data values for sequence 1 below in Table 7.3.2-19	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 1 below in Table 7.3.2-19	
earfcn	1	PCC
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	171	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values for sequence 1 below in Table 7.3.2-19	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	310	
expectedRSTD	See table of Sequence data values for sequence 1 below in Table 7.3.2-19	
expectedRSTD-Uncertainty	51	About 5 μ s
SEQUENCE (SIZE(4)) OF SEQUENCE	Sequence contains 4 instances of the following data.	
physCellId	See table of Sequence data values for sequence 2 below in Table 7.3.2-20	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 2 below in Table 7.3.2-20	
earfcn	2	SCC1
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	181	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values for sequence 2 below in Table 7.3.2-20	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	320	
expectedRSTD	See table of Sequence data values for sequence 2 below in Table 7.3.2-20	
expectedRSTD-Uncertainty	51	About 5 μ s
SEQUENCE (SIZE(7)) OF SEQUENCE	Sequence contains 7 instances of the following data.	

physCellId	See table of Sequence data values for sequence 3 below in Table 7.3.2-21	
cellGlobalId	For values of cellidentity see table of Sequence data values for sequence 3 below in Table 7.3.2-21	
earfcn	Not present	Same as for the reference cell (SCC2)
cpLength	Not present	Same as for the reference cell
prsInfo		
prs-Bandwidth (prs-Bandwidth depends on selected channel bandwidth)	5MHz: n25 10MHz: n50 20MHz: n100	
prs-ConfigurationIndex	191	
numDL-Frames (numDL-Frames depends on selected channel bandwidth)	5MHz: sf-2 10MHz: sf-1 20MHz:sf-1	
prs-MutingInfo-r9 CHOICE		
po8-r9	See table of Sequence data values for sequence 3 below in Table 7.3.2-21	
antennaPortConfig	Not present	Same as for the reference cell
slotNumberOffset	Not present	Slot timing is the same as for reference cell
prs-SubframeOffset	Not present	
expectedRSTD	See table of Sequence data values for sequence 3 below in Table 7.3.2-21	
expectedRSTD-Uncertainty	51	About 5 µs

Table 7.3.2-19: Sequence data values for 4 instances of sequence for sequence 1 for test cases 10.7, 10.8

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRSTD	Comment
		Value eNB ID	Value Cell Identity			
Cell 1	0 (Note 1)	'0000 0000 0000 0000 0001'B	'0000 0000'B	'1111 0000'	8172	Note 2
Dummy cell	8	'0000 0000 0000 0000 0010'B	'0000 1000'B	'0000 1111'	8175	Note 3
Dummy cell	16	'0000 0000 0000 0000 0010'B	'0001 0000'B	'1111 0000'	8182	Note 3
Dummy cell	119	'0000 0000 0000 0000 1110'B	'0111 0111'B	'0000 1111'	8218	Note 3
Note 1: Set according to sub-clause 4.7.1 and Table 10.7.4.1-1 and Table 10.8.4.1-1 in TS 37.571-1 [6] Note 2: Data for this cell is used at a random position in the 4 instances of the sequence Note 3: Data for this cell is used at any position in the 4 instances of the sequence						

Table 7.3.2-20: Sequence data values for 4 instances of sequence for sequence 2 for test cases 10.7, 10.8

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRS TD	Comment
		Value eNB ID	Value Cell Identity			
Cell 2	3 (Note 1)	'0000 0000 0000 0000 0010'B	'0000 0011'B	'1111 0000'	8192	Note 2
Dummy cell	9	'0000 0000 0000 0000 0100'B	'0000 1001'B	'0000 1111'	8190	Note 3
Dummy cell	111	'0000 0000 0000 0000 1100'B	'0110 1111'B	'1111 0000'	8207	Note 3
Dummy cell	120	'0000 0000 0000 0000 1111'B	'0111 1000'B	'0000 1111'	8182	Note 3

Note 1: Set according to sub-clause 4.7.1 and Table 10.7.4.1-1 and Table 10.8.4.1-1 in TS 37.571-1 [6]
Note 2: Data for this cell is used at a random position in the 4 instances of the sequence
Note 3: Data for this cell is used at any position in the 4 instances of the sequence

Table 7.3.2-21: Sequence data values for 7 instances of sequence for sequence 3 for test cases 10.7, 10.8

Cell	Value physCellId	Value cellidentity (E-UTRAN Cell Identity)		Value po8-r9	Value expectedRS TD	Comment
		Value eNB ID	Value Cell Identity			
Cell 4	10 (Note 1)	'0000 0000 0000 0000 0101'B	'0000 1010'B	'1111 0000'	8212	Note 2
Dummy cell	2	'0000 0000 0000 0000 0001'B	'0000 0010'B	'0000 1111'	8211	Note 3
Dummy cell	11	'0000 0000 0000 0000 0110'B	'0000 1011'B	'1111 0000'	8200	Note 3
Dummy cell	118	'0000 0000 0000 0000 1111'B	'0111 0110'B	'0000 1111'	8182	Note 3
Dummy cell	122	'0000 0000 0000 0000 1010'B	'0111 1010'B	'1111 0000'	8192	Note 3
Dummy cell	125	'0000 0000 0000 0000 1011'B	'0111 1101'B	'0000 1111'	8162	Note 3
Dummy cell	126	'0000 0000 0000 0000 1100'B	'0111 1110'B	'1111 0000'	8208	Note 3

Note 1: Set according to sub-clause 4.7.1 and Table 10.7.4.1-1 and Table 10.8.4.1-1 in TS 37.571-1 [6]
Note 2: Data for Cell 4 is used at a random position in the 7 instances of the sequence
Note 3: Data for this cell is used at any position in the 7 instances of the sequence

8 MBS information

8.1 MBS Scenarios for MBS signalling tests

This clause defines the Metropolitan Beacon System (MBS) scenario that shall be used where required for E-UTRA MBS signalling tests defined in TS 37.571-2 [7] subclause 7.

The beacon simulator shall generate all the UE supported MBS beacon signals defined in subclause 8.1.2.

The MBS sub-test case is identified by a Sub-Test Case Number 12 as defined in Table 8.1-1.

Table 8.1-1: Sub-Test Case Number Definition for TS 37.571-2 subclause 7

Sub-Test Case Number	Supported Positioning Method
12	UE supporting MBS
NOTE: Metropolitan Beacon System (MBS) is a specific type of Terrestrial Beacon System (TBS) [21]	

8.1.2 MBS Signalling Scenario

The following MBS scenario shall be used:

- UE location and Reference location: N/A
- The levels of the simulated beacons shall all be at the power levels shown in Table 8.1.2-1 +/- 6dB

Table 8.1.2-1: General test parameters for the beacons to be simulated for TS 37.571-2 clause 7

Parameter	Unit	Value	Comment
Number of Beacons		4	Beacons 1 to 4. Transmitted in the first four consecutive beacon slots in the MBS beacon transmission period. Other slots contain no simulated beacons.
Centre Frequency	MHz	925.977	
RF Channel		AWGN	
MBS Beacon Configuration		TB1 (2 MHz)	For details see [21]
MBS Packet Type		Type 2	For details see [21]
Beacon PN Code	Integer	Chosen for each beacon from the PN code list for TB1	Each of the 4 beacons uses a different PN code. For details see [21]
Transmit power	dBm	-90	

Table 8.1.2-2: MBS Beacon Payload fields and code phase delay for the beacons to be simulated for TS 37.571-2 clause 7

Beacon	MBS Tx ID [21]	Slot Index [21]	All Other fields [21]	Code phase delay (ms)
1	Equal to Slot number	Equal to Slot number	min value (bit_value = 0)	0
2	Equal to Slot number	Equal to Slot number	min value (bit_value = 0)	0
3	Equal to Slot number	Equal to Slot number	min value (bit_value = 0)	0
4	Equal to Slot number	Equal to Slot number	min value (bit_value = 0)	0

Note: bit_value is the conversion of the binary number represented by the corresponding bits in the payload to decimal.

9 WLAN information

9.1 WLAN Scenario for WLAN signalling tests

This clause defines the WLAN scenario that shall be used where required for E-UTRA WLAN signalling tests defined in TS 37.571-2 [7] subclause 7.

The WLAN simulator shall generate at least one of the UE supported WLAN signals defined in subclause 9.1.1.

The WLAN sub-test case is identified by a Sub-Test Case Number 11 as defined in Table 9.1-1.

Table 9.1-1: Sub-Test Case Number Definition for TS 37.571-2 subclause 7

Sub-Test Case Number	Supported Positioning Method
11	UE supporting WLAN

9.1.1 WLAN Signalling Scenario

The following WLAN scenario defined in Table 9.1.1-1 shall be used.

Table 9.1.1-1: General test parameters for the WLAN APs to be simulated for TS 37.571-2 clause 7

Parameter	Unit	Value	Comment
Number of WLAN APs		1	
AP Channel Frequency	MHz	Any supported by the UE	
RF Channel		AWGN	
AP BSSID		Any suitable value	For details see [22]
Other parameters		Any suitable value	For details see [22]

10 Bluetooth information

10.1 Bluetooth Scenario for Bluetooth signalling tests

This clause defines the Bluetooth scenario that shall be used where required for E-UTRA Bluetooth signalling tests defined in TS 37.571-2 [7] subclause 7.

The Bluetooth simulator shall generate the Bluetooth signals defined in subclause 10.1.1.

The Bluetooth sub-test case is identified by a Sub-Test Case Number 13 as defined in Table 10.1-1.

Table 10.1-1: Sub-Test Case Number Definition for TS 37.571-2 subclause 7

Sub-Test Case Number	Supported Positioning Method
13	UE supporting Bluetooth

10.1.1 Bluetooth Signalling Scenario

The following Bluetooth scenario defined in Table 10.1.1-1 shall be used.

Table 10.1.1-1: General test parameters for the Bluetooth beacons to be simulated for TS 37.571-2 clause 7

Parameter	Unit	Value	Comment
Number of Bluetooth beacons		1	
RF Channel		AWGN	
Public address of Bluetooth beacon		Any suitable value	For details see [23]
Other Bluetooth beacon parameters		Any suitable value	For details see [23]

Annex A (normative): GPS data files

A.1 GPS data files for signalling tests

The GPS data files for use in GPS signalling tests defined in TS 37.571-2 [7] subclauses 6.1.1 to 6.1.3 are contained in archive GPS_Data_Sig_V6.zip which accompanies this document.

The acquisition assistance data files contained in the archive are recommended but not mandatory.

A.2 GPS data files for Minimum Performance tests

The GPS data files for use in GPS Minimum Performance tests defined in TS 37.571-1 [6] subclause 5 are contained in archive GPS_Data_Perf_V9.zip which accompanies this document. The different scenarios are designated with suffixes XX in the zip file, where XX is 01, 02, 03 etc. for scenarios #1, #2, #3 etc.

The acquisition assistance data files contained in the archive are recommended but not mandatory.

Annex B (normative): GNSS data files

B.1 GNSS data files for signalling tests

The GNSS data files for use in GNSS signalling tests defined in TS 37.571-2 [7] subclauses 6.2.1 to 6.2.3 and subclause 7 are contained in archive GNSS_Data_Sig_V15.zip which accompanies the present document.

The acquisition assistance and reference measurement information data files contained in the archive are recommended but not mandatory.

Moreover there are currently two sets of the file Sig GANSS reference measurement information subtest1_4.csv supplied in the archive designated _set1 and _set2. Either set can be used for testing.

B.2 GNSS data files for Minimum Performance tests

The GNSS data files for use in GNSS Minimum Performance tests defined in TS 37.571-1 [6] subclauses 6 and 7 are contained in archive GNSS_Data_Perf_V14.zip which accompanies the present document. The different scenarios are designated with suffixes XX in the zip file, where XX is 01, 02, 03 etc. for scenarios #1, #2, #3 etc. The acquisition assistance and reference measurement information data files contained in the archive are recommended but not mandatory.

Moreover there are currently two sets of the files Perf GANSS reference measurement information subtest1_4 01.csv and Perf GANSS reference measurement information subtest1_4 02.csv supplied in the archive, designated _set1 and _set2. Either set can be used for testing.

Annex C (informative): Change history

Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2010-08	RAN5#48	R5-104318			Initial draft created as TS 36.571-5		0.0.0
2010-11	RAN5#49	R5-106146			Initial draft created from TS 36.571-5 with minor updates	0.0.0	0.1.0
2010-11	RAN5#49	R5-106615			Editor's notes added	0.1.0	0.1.1
2010-11	RAN5#49	R5-106614			Version 1.0.0 prepared for presentation to RAN Plenary	0.1.1	1.0.0
2011-05	RAN5#51	R5-112807			Version 1.1.0 with additional values and editorial changes	1.0.0	1.1.0
2011-08	RAN5#52	R5-113136			Additional values and editorial changes	1.1.0	-
2011-08	RAN5#52	R5-113137			Version 2.0.0 prepared for presentation to RAN Plenary	1.1.0	2.0.0
2011-09	RAN#53	RP-111127			v2.0.0 approved at RAN#53 and raised to v9.0.0 with no change	2.0.0	9.0.0
2011-12	RAN5#53	R5-115203	0001	-	Removal of editor's notes on OTDOA values	9.0.0	9.1.0
2011-12	RAN5#53	R5-115204	0002	-	Correction of references	9.0.0	9.1.0
2012-03	RAN5#54	R5-120085	0003	-	OTDOA reference corrections	9.1.0	9.2.0
2012-03	RAN5#54	R5-120086	0004	-	Update references	9.1.0	9.2.0
2012-03	RAN5#54	R5-120092	0005	-	OTDOA parameter corrections	9.1.0	9.2.0
2012-06	RAN5#55	R5-121136	0006	-	Corrections to GPS Almanac data file	9.2.0	9.3.0
2012-06	RAN5#55	R5-121137	0007	-	Removal of OTDOA data for signalling test cases	9.2.0	9.3.0
2012-06	RAN5#55	R5-121249	0008	-	LBS: Corrections to gnss-SystemTime message	9.2.0	9.3.0
2012-06	RAN5#55	R5-121853	0009	-	Additions and corrections to GNSS data	9.2.0	9.3.0
2012-06	RAN5#55	R5-121910	0010	-	Additions and corrections to GNSS data	9.2.0	9.3.0
2012-06	RAN5#55	R5-121911	0011	-	Reduction in size of GPS data file	9.2.0	9.3.0
2012-06	RAN5#55	-	-	-	Upgraded to v10.0.0 with no change.	9.3.0	10.0.0
2012-09	RAN5#56	R5-123097	0012	-	Addition of missing Assistance Data	10.0.0	10.1.0
2012-09	RAN5#56	R5-123699	0013	-	Addition of Rel-10 Information Elements	10.0.0	10.1.0
2012-09	RAN5#56	R5-123914	0014	-	Addition of missing Assistance Data	10.0.0	10.1.0
2012-12	RAN5#57	R5-125577	0015	-	Correction to Reference UE Position value	10.1.0	10.2.0
2012-12	RAN5#57	R5-125779	0017	-	LBS Sig: Corrections to GLONASS acquisition assistance data	10.1.0	10.2.0
2012-12	RAN5#57	R5-125780	0018	-	LBS Sig: Corrections to GNSS assistance data	10.1.0	10.2.0
2012-12	RAN5#57	R5-125849	0019	-	LBS Perf: Correction of coordinates for GNSS Scenario #2 and #5	10.1.0	10.2.0
2012-12	RAN5#57	R5-125850	0020	-	LBS Perf: Corrections to GNSS assistance data	10.1.0	10.2.0
2012-12	RAN5#57	R5-125917	0021	-	LBS Perf: Corrections to GLONASS acquisition assistance data	10.1.0	10.2.0
2012-12	RAN5#56 bis	R5-124122	0022	-	OTDOA data for new test cases 10.1 - 10.4 for RSTD for Carrier Aggregation	10.1.0	10.2.0
2013-03	RAN5#58	R5-130118	0023	-	Addition of Rel-10 IEs	10.2.0	10.3.0
2013-03	RAN5#58	R5-130119	0024	-	Addition of Rel-10 IEs	10.2.0	10.3.0
2013-03	RAN5#58	R5-130122	0025	-	Change of file names for assistance data	10.2.0	10.3.0
2013-03	RAN5#58	R5-130123	0026	-	Change of file names for assistance data	10.2.0	10.3.0
2013-03	RAN5#58	R5-130529	0027	-	Correction to GPS assistance data	10.2.0	10.3.0
2013-03	RAN5#58	R5-130689	0028	-	Correction to GLONASS assistance data	10.2.0	10.3.0
2013-03	RAN5#58	R5-130690	0029	-	Correction to GPS assistance data	10.2.0	10.3.0
2013-03	RAN5#58	R5-130960	0030	-	Correction to GLONASS assistance data	10.2.0	10.3.0
2013-06	RAN5#59	R5-131103	0031	-	Additional OTDOA assistance data for new inter-frequency tests	10.3.0	10.4.0
2013-06	RAN5#59	R5-131108	0032	-	Correction to GLONASS ToD	10.3.0	10.4.0
2013-06	RAN5#59	R5-131329	0033	-	Correction to available GNSS assistance data elements for signalling tests	10.3.0	10.4.0
2013-06	RAN5#59	R5-131330	0034	-	Addition of missing Rel-10 IE	10.3.0	10.4.0
2013-06	RAN5#59	R5-131509	0035	-	Corrections to UTC Model assistance data values	10.3.0	10.4.0
2013-06	RAN5#59	R5-131511	0036	-	Corrections and clarifications to use of UTC Model and Auxiliary Information	10.3.0	10.4.0
2013-06	RAN5#59	R5-131948	0037	-	OTDOA assistance data alignment with RAN 4	10.3.0	10.4.0
2013-06	RAN5#59	R5-131949	0038	-	Corrections to UTC Model assistance data values	10.3.0	10.4.0
2013-06	RAN5#59	R5-131997	0039	-	LBS Perf: Introduction of GLONASS acquisition assistance data	10.3.0	10.4.0
2013-06	RAN5#59	R5-131998	0040	-	Addition of GLONASS Acquisition Assistance data	10.3.0	10.4.0
2013-06	RAN5#59	R5-132060	0041	-	Addition of GLONASS Acquisition Assistance data	10.3.0	10.4.0
2013-06	RAN5#59	R5-132061	0042	-	LBS Sig: Introduction of GLONASS acquisition assistance data	10.3.0	10.4.0
2013-06	RAN5#59	R5-132100	0043	-	Corrections and clarifications to use of UTC Model and Auxiliary Information	10.3.0	10.4.0
2013-06	RAN5#59	R5-132101	0044	-	Correction to GLONASS SV Health value in data file	10.3.0	10.4.0
2013-09	RAN5#60	R5-133177	0045	-	Removal of old Assistance Data files	10.4.0	10.5.0
2013-09	RAN5#60	R5-133179	0046	-	Addition of missing Assistance Data files	10.4.0	10.5.0
2013-09	RAN5#60	R5-133180	0047	-	Correction of Doppler 1 values for RRC	10.4.0	10.5.0
2013-09	RAN5#60	R5-133341	0048	-	Change of SV for GNSS Scenario #2 for Multi-path test	10.4.0	10.5.0
2013-09	RAN5#60	R5-133487	0050	-	Correction of Doppler 1 values for RRC	10.4.0	10.5.0
2013-09	RAN5#60	R5-133488	0051	-	Correction of Doppler values for LPP	10.4.0	10.5.0
2013-09	RAN5#60	R5-133726	0052	-	Correction of Doppler values for LPP	10.4.0	10.5.0
2013-12	RAN5#61	R5-134206	0053	-	Correction to GPS Almanac WNa value for scenarios #2 and #5	10.5.0	10.6.0
2013-12	RAN5#61	R5-134251	0054	-	Correction of OmegaA0 value for SV1 in scenario #1	10.5.0	10.6.0
2013-12	RAN5#61	R5-134257	0055	-	Deletion of FFS and Editor's note in clause 6.2.7	10.5.0	10.6.0
2013-12	RAN5#61	R5-134357	0057	-	Correction to GLONASS Navigation Model for scenario #2 and #5	10.5.0	10.6.0
2013-12	RAN5#61	R5-134443	0058	-	LBS Perf: Corrections to the headers of GPS acquisition assistance data files	10.5.0	10.6.0

Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2013-12	RAN5#61	R5-134444	0059	-	LBS Sig: Corrections to the headers of GPS acquisition assistance data files	10.5.0	10.6.0
2013-12	RAN5#61	R5-134851	0060	-	Addition of OTDOA Assistance Data for new 20MHz CA test cases	10.5.0	10.6.0
2013-12	RAN5#61	R5-134912	0061	-	Correction of OmegaA0 value for SV1	10.5.0	10.6.0
2013-12	RAN5#61	R5-134913	0062	-	Correction to GNSS Navigation Model (sub-test 1)	10.5.0	10.6.0
2013-12	RAN5#61	R5-135064	0063	-	LBS Perf: Corrections to the GNSS acquisition assistance data - CR 1	10.5.0	10.6.0
2013-12	RAN5#61	R5-135065	0064	-	LBS Perf: Corrections to the GNSS acquisition assistance data - CR 2	10.5.0	10.6.0
2013-12	RAN5#61	R5-135072	0065	-	LBS Sig: Corrections to the GNSS acquisition assistance data	10.5.0	10.6.0
2014-03	RAN5#62	R5-140198	0066	-	Adjustment of SV IDs of Satellites to be simulated	10.6.0	10.7.0
2014-03	RAN5#62	R5-140377	0067	-	LBS Perf: Update of headers of some GNSS acquisition assistance data files	10.6.0	10.7.0
2014-03	RAN5#62	R5-140378	0068	-	LBS Sig: Removal of redundant inappropriate files from GNSS_Data_Sig_V7.zip file	10.6.0	10.7.0
2014-03	RAN5#62	R5-140383	0069	-	LBS Perf: Introducing Ephemeris files in Rinex format	10.6.0	10.7.0
2014-03	RAN5#62	R5-140384	0070	-	LBS Sig: Introducing Ephemeris files in Rinex format	10.6.0	10.7.0
2014-03	RAN5#62	R5-140794	0071	-	LBS Sig: Clarification on usage of acquisition assistance files	10.6.0	10.7.0
2014-03	RAN5#62	R5-140795	0072	-	LBS Sig: Changing the name of Almanac files not in Yuma format	10.6.0	10.7.0
2014-03	RAN5#62	R5-140873	0073	-	LBS Perf: Clarification on usage of acquisition assistance files	10.6.0	10.7.0
2014-03	RAN5#62	R5-140874	0074	-	LBS Perf: Changing the name of Almanac files not in Yuma format	10.6.0	10.7.0
2014-03	RAN5#62	R5-140879	0075	-	Corrections to GLONASS GANSS Day and gnss-DayNumber values	10.6.0	10.7.0
2014-03	RAN5#62	R5-140900	0076	-	Corrections to GLONASS GANSS Day and gnss-DayNumber values	10.6.0	10.7.0
2014-03	RAN5#62	R5-141034	0077	-	RSTD value updates	10.6.0	10.7.0
2014-06	RAN5#63	R5-142097	0078	-	Corrections to prs-MutingInfo	10.7.0	10.8.0
2014-06	RAN5#63	R5-142249	0079	-	Correction to T_lamda_n_A values for scenario #1	10.7.0	10.8.0
2014-06	RAN5#63	R5-142250	0080	-	Correction to T_lamda_n_A values	10.7.0	10.8.0
2014-06	RAN5#63	R5-142252	0081	-	Clarification of use of satellite simulator	10.7.0	10.8.0
2014-06	RAN5#63	R5-142884	0082	-	LBS Sig: Correction of FT values in GLONASS scenarios and RINEX file update	10.7.0	10.8.0
2014-06	RAN5#63	R5-142885	0083	-	LBS Sig: Moving some .rnx files to the right .zip file	10.7.0	10.8.0
2014-06	RAN5#63	R5-143110	0084	-	LBS Perf: Moving some .rnx files to the right .zip file	10.7.0	10.8.0
2014-06	RAN5#63	R5-143128	0085	-	LBS Perf: Correction of FT values in GLONASS scenarios and RINEX file update	10.7.0	10.8.0
2014-09	RAN5#64	R5-144133	0086	-	LBS Perf: Adding missing information for QZSS	10.8.0	10.9.0
2014-09	RAN5#64	R5-144135	0087	-	LBS Perf: Adding missing files for QZSS	10.8.0	10.9.0
2014-09	RAN5#64	R5-144136	0088	-	LBS Sig: Adding missing files for QZSS	10.8.0	10.9.0
2014-09	RAN5#64	R5-144139	0091	-	LBS Perf: Adding missing files for Galileo	10.8.0	10.9.0
2014-09	RAN5#64	R5-144140	0092	-	LBS Sig: Adding missing files for Galileo	10.8.0	10.9.0
2014-09	RAN5#64	R5-144793	0089	-	LBS Perf: Adding missing information for Galileo and introduction of Galileo hybrid-subtest	10.8.0	10.9.0
2014-09	RAN5#64	R5-144795	0090	-	LBS Sig: Adding missing information for Galileo and introduction of Galileo hybrid-subtest	10.8.0	10.9.0
2014-09	RAN5#64	R5-144872	0097	-	Updates OTDOA Neighbour Cell Info List	10.8.0	10.9.0
2014-12	RAN5#65	R5-145101	0102	-	LBS Perf: Adding missing information for Galileo	10.9.0	10.10.0
2014-12	RAN5#65	R5-145102	0103	-	LBS Sig: Adding missing information for Galileo	10.9.0	10.10.0
2014-12	RAN5#65	R5-145135	0104	-	Clarification to OTDOA Assistance Data	10.9.0	10.10.0
2014-12	RAN5#65	R5-145136	0105	-	Update Galileo ICD reference	10.9.0	10.10.0
2014-12	RAN5#65	-	-	-	Raised to v11.0.0 with no change	10.10.0	11.0.0
2014-12	RAN5#65	R5-145978	0098	-	LBS Perf: Adding test scenarios for Beidou	11.0.0	12.0.0
2014-12	RAN5#65	R5-145098	0099	-	LBS Sig: Adding test scenarios for Beidou	11.0.0	12.0.0
2014-12	RAN5#65	R5-145099	0100	-	LBS Perf: Adding data files for Beidou	11.0.0	12.0.0
2014-12	RAN5#65	R5-145100	0101	-	LBS Sig: Adding data files for Beidou	11.0.0	12.0.0
2014-12	RAN5#65	R5-145895	0106	-	Addition of Editor's Note concerning missing data for TDD in sections 5.2 and 6.2	11.0.0	12.0.0
2015-03	RAN5#66	R5-150052	0107	-	Updates to expectedRSTD values following changes in RAN 4	12.0.0	12.1.0
2015-03	RAN5#66	R5-150106	0108	-	Change Nprs value in tests 10.3B, 10.3C, 10.4B, 10.4C	12.0.0	12.1.0
2015-03	RAN5#66	R5-150237	0109	-	LBS Perf: Correction to simulated BDS satellites	12.0.0	12.1.0
2015-03	RAN5#66	R5-150839	0110	-	Missing Abbreviations in Specification	12.0.0	12.1.0
2015-03	RAN5#66	R5-150840	0111	-	Missing OTDOA CA Test Cases	12.0.0	12.1.0
2015-03	RAN5#66	R5-150891	0112	-	Abbreviation Corrections for BDS in 37.571-5	12.0.0	12.1.0
2015-06	RAN5#67	R5-151069	0113	-	Add TDD to A-GNSS Assistance Data	12.1.0	12.2.0
2015-06	RAN5#67	R5-151091	0114	-	Missing RSTD new tests for 10.2D and 10.4D	12.1.0	12.2.0
2015-06	RAN5#67	R5-151910	0117	1	Corrections to the Ionospheric Model of BDS	12.1.0	12.2.0
2015-09	RAN5#68	R5-153108	0118	-	Corrections to UTC Model and Time Model	12.2.0	12.3.0
2015-09	RAN5#68	R5-153109	0119	-	Update to Galileo Assistance Data IEs	12.2.0	12.3.0

Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2015-09	RAN5#68	R5-153112	0120	-	Corrections to UTC Model	12.2.0	12.3.0
2015-09	RAN5#68	R5-153113	0121	-	Update to Galileo Assistance Data IEs	12.2.0	12.3.0
2015-09	RAN5#68	R5-153150	0122	-	Missing RSTD information for multiple test cases	12.2.0	12.3.0
2015-09	RAN5#68	R5-153151	0123	-	Missing BDS reference in the A-GNSS Minimum Performance Testing	12.2.0	12.3.0
2015-09	RAN5#68	R5-153664	0126	-	Update of Galileo OS SIS ICD reference	12.2.0	12.3.0
2015-09	RAN5#68	R5-153791	0124	1	Corrections to BDS Clock Model and Navigation Model for SIG tests	12.2.0	12.3.0
2015-09	RAN5#68	R5-153866	0127	1	Corrections to BDS Clock Model and Navigation Model for Perf tests	12.2.0	12.3.0
2015-09	RAN#69	-	-	-	update of the "non-specific references" in section 2 according to the approved R5-153582 and an action point on ETSI MCC	12.2.0	12.3.0
2015-12	RAN#70	R5-155185	0131	-	Values for two new 3 DL CA RSTD Measurement Accuracy test cases	12.3.0	12.4.0
2015-12	RAN#70	R5-155877	0130	1	Values for two new 3 DL CA RSTD Measurement Reporting Delay test cases	12.3.0	12.4.0
2015-12	RAN#70	R5-156186	0133	2	LBS-Sig: Corrections to A-BDS navigation files	12.3.0	12.4.0
2015-12	RAN#70	R5-156187	0132	2	LBS-Perf: Corrections to A-BDS navigation files	12.3.0	12.4.0
2016-03	RAN#71	R5-160173	0136	-	LBS Perf: Correction of assistance data files for A-BDS scenario 1	12.4.0	12.5.0
2016-03	RAN#71	R5-160174	0137	-	LBS Sig: Correction of assistance data files for A-BDS	12.4.0	12.5.0
2016-03	RAN#71	R5-160899	0138	1	LBS Perf: Correction of assistance data files for A-GALILEO scenario 1	12.4.0	12.5.0
2016-03	RAN#71	R5-160973	0140	1	LBS Sig: Correction of assistance data files for A-GALILEO	12.4.0	12.5.0
2016-03	RAN#71	R5-161000	0139	1	LBS Perf: Correction of assistance data files for A-GALILEO scenario 2	12.4.0	12.5.0
2016-09	RAN#73	R5-165088	0145	-	Correction of BDS Almanac di values for geostationary satellites	12.5.0	12.6.0
2016-09	RAN#73	R5-165089	0146	-	Correction of BDS Almanac di values for geostationary satellites	12.5.0	12.6.0
2016-09	RAN#73	R5-165994	0147	1	Aligning GNSS and GPS UE reference position	12.5.0	12.6.0
2016-09	RAN#73	R5-165998	0149	1	Addition of Indoor Positioning Enhancements (MBS) (protocol)	12.6.0	13.0.0
2016-12	RAN#74	R5-168470	0150	-	Add WLAN signalling sub-test and references for Indoor Positioning	13.0.0	13.1.0
2016-12	RAN#74	R5-169095	0156	1	LBS-Sig: correction of the URA value and rinex file format for BDS	13.0.0	13.1.0
2016-12	RAN#74	R5-169096	0157	1	LBS-Sig: correction of the rinex file format for GLONASS	13.0.0	13.1.0
2016-12	RAN#74	R5-169097	0158	1	LBS-Sig: correction of the rinex file for GPS	13.0.0	13.1.0
2016-12	RAN#74	R5-169098	0159	1	LBS-Sig: correction of the rinex file for Galileo	13.0.0	13.1.0
2016-12	RAN#74	R5-169099	0160	1	LBS-Sig: correction of the QZSS scenario	13.0.0	13.1.0
2016-12	RAN#74	R5-169642	0151	1	LBS-Perf: correction of the URA value and rinex file format for BDS	13.0.0	13.1.0
2016-12	RAN#74	R5-169643	0152	1	LBS-Perf: correction of the rinex file format for GLONASS	13.0.0	13.1.0
2016-12	RAN#74	R5-169644	0153	1	LBS-Perf: correction of the rinex file for GPS	13.0.0	13.1.0
2016-12	RAN#74	R5-169645	0154	1	LBS-Perf: correction of the rinex file for Galileo	13.0.0	13.1.0
2016-12	RAN#74	R5-169646	0155	1	LBS-Perf: correction of the QZSS scenario	13.0.0	13.1.0
2017-03	RAN#75	R5-170739	0161	-	Add Bluetooth signalling subtests and references	13.1.0	13.2.0
2017-03	RAN#75	R5-171907	0162	1	Correction OTDOA Assistance Data for 3CC test cases	13.1.0	13.2.0

History

Document history		
V13.0.0	November 2016	Publication
V13.1.0	January 2017	Publication
V13.2.0	April 2017	Publication