

# ETSI TS 138 101-4 v15.0.0 (2019-04)



5G;  
NR;

**User Equipment (UE) radio transmission and reception;**  
**Part 4: Performance requirements**  
**(3GPP TS 38.101-4 version 15.0.0 Release 15)**



---

Reference

DTS/TSGR-0438101-4vf00

---

Keywords

5G

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and  
of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under  
<http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1    Scope .....	10
2    References .....	10
3    Definitions, symbols and abbreviations .....	10
3.1    Definitions .....	10
3.2    Symbols.....	11
3.3    Abbreviations .....	11
4    General .....	12
4.1    Relationship between minimum requirements and test requirements .....	12
4.2    Applicability of minimum requirements .....	12
4.3    Specification suffix information.....	12
4.4    Conducted requirements.....	13
4.4.1    Conducted requirement reference point.....	13
4.4.3    Noc.....	13
4.5    Radiated requirements .....	13
4.5.1    Radiated requirement reference point.....	13
4.5.2    SNR definition .....	14
4.5.3    Noc.....	14
4.5.3.1    Introduction .....	14
4.5.3.2    Noc for NR operating bands in FR2.....	14
4.5.3.3    Derivation of Noc values for NR operating bands in FR2 .....	14
4.5.4    Angle of arrival .....	15
5    Demodulation performance requirements (Conducted requirements) .....	15
5.1    General .....	15
5.1.1    Applicability of requirements .....	15
5.2    PDSCH demodulation requirements .....	15
5.2.1    1RX requirements .....	18
5.2.2    2RX requirements .....	18
5.2.2.1    FDD.....	18
5.2.2.1.1    Minimum requirements for PDSCH Mapping Type A.....	18
5.2.2.1.2    Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	20
5.2.2.1.3    Minimum requirements for PDSCH Mapping Type B.....	21
5.2.2.1.4    Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	21
5.2.2.2    TDD .....	22
5.2.2.2.1    Minimum requirements for PDSCH Mapping Type A.....	22
5.2.2.2.2    Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	24
5.2.2.2.3    Minimum requirements for PDSCH Mapping Type B .....	25
5.2.3    4RX requirements .....	26
5.2.3.1    FDD.....	26
5.2.3.1.1    Minimum requirements for PDSCH Mapping Type A.....	26
5.2.3.1.2    Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	28
5.2.3.1.3    Minimum requirements for PDSCH Mapping Type B.....	29
5.2.3.1.4    Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence .....	30
5.2.3.2    TDD .....	31
5.2.3.2.1    Minimum requirements for PDSCH Mapping Type A.....	31
5.2.3.2.2    Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH .....	33
5.2.3.2.3    Minimum requirements for PDSCH Mapping Type B .....	34
5.3    PDCCH demodulation requirements .....	35
5.3.1    1RX requirements .....	36
5.3.2    2RX requirements .....	36
5.3.2.1    FDD.....	36

5.3.2.1.1	1 Tx Antenna performances .....	37
5.3.2.1.2	2 Tx Antenna performances .....	37
5.3.2.2	TDD .....	37
5.3.2.2.1	1 Tx Antenna performances .....	37
5.3.2.2.2	2 Tx Antenna performances .....	38
5.3.3	4RX requirements .....	38
5.3.3.1	FDD.....	38
5.3.3.1.1	1 Tx Antenna performances .....	38
5.3.3.1.2	2 Tx Antenna performances .....	39
5.3.3.2	TDD .....	39
5.3.3.2.1	1 Tx Antenna performances .....	39
5.3.3.2.2	2 Tx Antenna performances .....	39
5.4	PBCH demodulation requirements .....	40
5.4.1	1RX requirements .....	40
5.4.2	2RX requirements .....	40
5.4.2.1	FDD.....	40
5.4.2.2	TDD .....	40
5.5	Sustained downlink data rate provided by lower layers .....	41
5.5.1	FR1 single carrier requirements.....	41
5.5A	Sustained downlink data rate provided by lower layers .....	41
5.5A.1	FR1 CA requirements .....	41
6	CSI reporting requirements (Conducted requirements) .....	46
6.1	General .....	46
6.1.1	Applicability of requirements .....	47
6.1.2	Common test parameters .....	47
6.2	Reporting of Channel Quality Indicator (CQI).....	50
6.2.1	1RX requirements .....	50
6.2.2	2RX requirements .....	50
6.2.2.1	FDD.....	50
6.2.2.1.1	CQI reporting definition under AWGN conditions .....	50
6.2.2.1.1.1	Minimum requirement for periodic CQI reporting .....	50
6.2.2.1.2	CQI reporting under fading conditions.....	52
6.2.2.1.2.1	Minimum requirement for wideband CQI reporting.....	52
6.2.2.1.2.2	Minimum requirement for sub-band CQI reporting.....	54
6.2.2.2	TDD .....	56
6.2.2.2.1	CQI reporting definition under AWGN conditions .....	56
6.2.2.2.1.1	Minimum requirement for periodic CQI reporting .....	56
6.2.2.2.2	Wideband CQI reporting under fading conditions .....	58
6.2.2.2.2.1	Minimum requirement for wideband CQI reporting.....	58
6.2.2.2.2.2	Minimum requirement for sub-band CQI reporting.....	60
6.2.3	4RX requirements .....	62
6.2.3.1	FDD.....	62
6.2.3.1.1	CQI reporting definition under AWGN conditions .....	62
6.2.3.1.1.1	Minimum requirement for period CQI reporting .....	62
6.2.3.1.2	Wideband CQI reporting under fading conditions .....	64
6.2.3.1.2.1	Minimum requirement for wideband CQI reporting.....	64
6.2.3.1.2.2	Minimum requirement for sub-band CQI reporting.....	66
6.2.3.2	TDD .....	68
6.2.3.2.1	CQI reporting definition under AWGN.....	68
6.2.3.2.1.1	Minimum requirement for CQI periodic reporting .....	68
6.2.3.2.2	Wideband CQI reporting under fading conditions .....	70
6.2.3.2.2.1	Minimum requirement for wideband CQI reporting.....	70
6.2.3.2.2.2	Minimum requirement for sub-band CQI reporting.....	72
6.3	Reporting of Precoding Matrix Indicator (PMI).....	74
6.3.1	1RX requirements .....	74
6.3.2	2RX requirements .....	74
6.3.2.1	FDD.....	74
6.3.2.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	74
6.3.2.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	77
6.3.2.2	TDD .....	80
6.3.2.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	80

6.3.2.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	83
6.3.3	4RX requirements .....	86
6.3.3.1	FDD.....	86
6.3.3.1.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	86
6.3.3.1.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	89
6.3.3.2	TDD .....	92
6.3.3.2.1	Single PMI with 4TX TypeI-SinglePanel Codebook .....	92
6.3.3.2.2	Single PMI with 8TX TypeI-SinglePanel Codebook .....	95
6.4	Reporting of Rank Indicator (RI) .....	98
6.4.1	1RX requirements .....	98
6.4.2	2RX requirements .....	98
6.4.2.1	FDD.....	98
6.4.2.2	TDD .....	100
6.4.3	4RX requirements .....	102
6.4.3.1	FDD.....	102
6.4.3.2	TDD .....	104
7	Demodulation performance requirements (Radiated requirements) .....	107
7.1	General .....	107
7.1.1	Applicability of requirements .....	107
7.2	PDSCH demodulation requirements .....	107
7.2.1	1RX requirements .....	109
7.2.2	2RX requirements .....	109
7.2.2.1	FDD.....	109
7.2.2.2	TDD .....	109
7.2.2.2.1	Minimum requirements for PDSCH Mapping Type-A .....	109
7.3	PDCCH demodulation requirements .....	111
7.3.1	1RX requirements .....	112
7.3.2	2RX requirements .....	112
7.3.2.1	FDD.....	112
7.3.2.2	TDD .....	112
7.3.2.2.1	1 Tx Antenna performances .....	112
7.3.2.2.2	2 Tx Antenna performances .....	113
7.4	PBCH demodulation requirements .....	113
7.4.1	1RX requirements .....	113
7.4.2	2RX requirements .....	113
7.4.2.1	FDD.....	113
7.4.2.2	TDD .....	114
7.5	Sustained downlink data rate provided by lower layers .....	114
8	CSI reporting requirements (Radiated requirements).....	114
8.1	General .....	114
8.1.1	Applicability of requirements .....	114
8.1.2	Common test parameters .....	114
8.2	Reporting of Channel Quality Indicator (CQI).....	116
8.2.1	1RX requirements .....	116
8.2.2	2RX requirements .....	116
8.2.2.1	FDD.....	116
8.2.2.2	TDD .....	116
8.2.2.2.1	CQI reporting under AWGN conditions.....	116
8.2.2.2.1.1	Minimum requirement for periodic CQI reporting .....	116
8.2.2.2.2	CQI reporting under fading conditions.....	118
8.2.2.2.2.1	Minimum requirement for wideband CQI reporting.....	118
8.3	Reporting of Precoding Matrix Indicator (PMI).....	120
8.3.1	1RX requirements .....	120
8.3.2	2RX requirements .....	120
8.3.2.1	FDD.....	120
8.3.2.2	TDD .....	120
8.3.2.2.1	Single PMI with 2TX TypeI-SinglePanel Codebook .....	120
8.4	Reporting of Rank Indicator (RI) .....	123
8.4.1	1RX requirements .....	123
8.4.2	2RX requirements .....	123

8.4.2.1	FDD .....	123
8.4.2.2	TDD .....	123
9	Demodulation performance requirements for interworking .....	125
9.1	General .....	125
9.1.1	Applicability of requirements .....	125
9.1.2	LTE Pcell setup .....	125
9.1.2.1	FDD .....	125
9.1.2.2	TDD .....	126
9.2	Void .....	127
9.2A	PDSCH demodulation for CA .....	127
9.2A.1	NR CA between FR1 and FR2 .....	127
9.2B	PDSCH demodulation for DC .....	127
9.2B.1	EN-DC .....	127
9.2B.1.1	EN-DC within FR1 .....	127
9.2B.1.1.1	PDSCH .....	127
9.2B.1.2	EN-DC including FR2 NR carrier only .....	128
9.2B.1.2.1	PDSCH .....	128
9.2B.1.3	EN-DC including FR1 and FR2 NR carriers .....	128
9.2B.2	NR DC between FR1 and FR2 .....	128
9.3	Void .....	128
9.3A	PDCCH demodulation for CA .....	128
9.3A.1	NR CA between FR1 and FR2 .....	128
9.3B	PDCCH demodulation for DC .....	128
9.3B.1	EN-DC .....	128
9.3B.1.1	EN-DC within FR1 .....	128
9.3B.1.1.1	PDCCH .....	128
9.3B.1.2	EN-DC including FR2 NR carrier only .....	128
9.3B.1.2.1	PDCCH .....	128
9.3B.1.3	EN-DC including FR1 and FR2 NR carriers .....	128
9.3B.2	NR DC between FR1 and FR2 .....	128
9.4	Void .....	129
9.4A	SDR test for CA .....	129
9.4A.1	NR CA between FR1 and FR2 .....	129
9.4B	SDR test for DC .....	129
9.4B.1	EN-DC .....	129
9.4B.1.1	EN-DC within FR1 .....	129
9.4B.1.1.1	SDR test .....	129
9.4B.1.2	EN-DC including FR2 NR carrier .....	129
9.4B.1.2.1	SDR test .....	129
9.4B.1.3	EN-DC including FR1 and FR2 NR carriers .....	129
9.4B.2	NR DC between FR1 and FR2 .....	129
10	CSI reporting requirements for interworking .....	129
10.1	General .....	129
10.1.1	Applicability of requirements .....	129
10.2	Void .....	130
10.2A	Reporting of Channel Quality Indicator (CQI) for CA .....	130
10.2B	Reporting of Channel Quality Indicator (CQI) for DC .....	130
10.2B.1	EN-DC .....	130
10.2B.1.1	EN-DC within FR1 .....	130
10.2B.1.2	EN-DC including FR2 NR carrier .....	130
10.2B.1.3	EN-DC including FR1 and FR2 NR carriers .....	130
10.3	Void .....	130
10.3A	Reporting of Precoding Matrix Indicator (PMI) for CA .....	130
10.3B	Reporting of Precoding Matrix Indicator (PMI) for DC .....	130
10.3B.1	EN-DC .....	130
10.3B.1.1	EN-DC within FR1 .....	130
10.3B.1.2	EN-DC including NR FR2 carrier .....	130
10.3B.1.3	EN-DC including FR1 and FR2 NR carriers .....	130
10.4	Void .....	131
10.4A	Reporting of Rank Indicator (RI) for CA .....	131

10.4B	Reporting of Rank Indicator (RI) for DC .....	131
10.4B.1	EN-DC .....	131
10.4B.1.1	EN-DC within FR1 .....	131
10.4B.1.2	EN-DC including NR FR2 carrier .....	131
10.4B.1.3	EN-DC including FR1 and FR2 NR carriers .....	131

## **Annex A (normative): Measurement channels ..... 132**

A.1	General .....	132
A.1.1	Throughput definition .....	132
A.1.2	TDD UL-DL patterns for FR1 .....	132
A.1.3	TDD UL-DL patterns for FR2 .....	134
A.2	Void.....	134
A.3	DL reference measurement channels.....	134
A.3.1	General.....	134
A.3.2	Reference measurement channels for PDSCH performance requirements.....	135
A.3.2.1	FDD.....	135
A.3.2.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	135
A.3.2.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	141
A.3.2.2	TDD .....	142
A.3.2.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	142
A.3.2.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	142
A.3.2.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	150
A.3.2.2.4	Reference measurement channels for SCS 60 kHz FR2.....	150
A.3.2.2.5	Reference measurement channels for SCS 120 kHz FR2.....	151
A.3.3	Reference measurement channels for PDCCH performance requirements .....	158
A.3.3.1	FDD.....	158
A.3.3.1.1	Reference measurement channels for SCS 15 kHz FR1 .....	158
A.3.3.1.2	Reference measurement channels for SCS 30 kHz FR1 .....	158
A.3.3.2	TDD .....	159
A.3.3.2.1	Reference measurement channels for SCS 15 kHz FR1 .....	159
A.3.3.2.2	Reference measurement channels for SCS 30 kHz FR1 .....	160
A.3.3.2.3	Reference measurement channels for SCS 60 kHz FR1 .....	160
A.3.3.2.4	Reference measurement channels for SCS 60 kHz FR2.....	160
A.3.3.2.5	Reference measurement channels for SCS 120 kHz FR2.....	160
A.3.4	Reference measurement channels for PBCH demodulation requirements.....	161
A.3.4.1	Reference measurement channels for FR1 .....	161
A.3.4.2	Reference measurement channels for FR2 .....	161
A.4	CSI reference measurement channels.....	161
A.5	OFDMA Channel Noise Generator (OCNG) .....	163
A.5.1	OCNG Patterns for FDD.....	163
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused rEs .....	163
A.5.2	OCNG Patterns for TDD .....	163
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused rEs.....	163

## **Annex B (normative): Propagation conditions..... 164**

B.1	Static propagation condition.....	164
B.1.1	UE Receiver with 2Rx.....	164
B.1.2	UE Receiver with 4Rx.....	164
B.2	Multi-path fading propagation conditions .....	165
B.2.1	Delay profiles .....	165
B.2.1.1	Delay profiles for FR1 .....	165
B.2.1.2	Delay profiles for FR2 .....	166
B.2.2	Combinations of channel model parameters .....	167
B.2.3	MIMO Channel Correlation Matrices.....	168
B.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA).....	168
B.2.3.1.1	Definition of MIMO Correlation Matrices .....	168
B.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level .....	169
B.2.3.2	MIMO Correlation Matrices using Cross Polarized Antennas (X-pol).....	173
B.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas.....	174
B.2.3.2.2	MIMO Correlation Matrices using cross polarized antennas .....	175
B.2.3.2.3	Beam steering approach.....	177

B.2.4	Two-tap propagation conditions for CQI tests .....	178
<b>Annex C (normative):</b>	<b>Downlink physical channels .....</b>	<b>179</b>
C.1	General .....	179
C.2	Setup (Conducted).....	179
C.3	Connection (Conducted).....	179
C.3.1	Measurement of Performance requirements .....	179
C.4	Setup (Radiated).....	179
C.5	Connection (Radiated).....	180
C.5.1	Measurement of Receiver Characteristics .....	180
<b>Annex D:</b>	<b>Void .....</b>	<b>181</b>
<b>Annex E (normative):</b>	<b>Environmental conditions .....</b>	<b>182</b>
E.1	General .....	182
E.2	Environmental (Conducted).....	182
E.2.1	Temperature .....	182
E.2.2	Voltage .....	182
E.2.3	Vibration.....	183
E.3	Environmental (Radiated) .....	183
E.3.1	Temperature .....	183
E.3.2	Voltage .....	183
E.3.3	Void.....	183
<b>Annex G:</b>	<b>Void .....</b>	<b>184</b>
<b>Annex H:</b>	<b>Void .....</b>	<b>184</b>
<b>Annex I:</b>	<b>Void .....</b>	<b>184</b>
<b>Annex J (informative):</b>	<b>Change history .....</b>	<b>185</b>
History .....	187	

---

## Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## 1 Scope

The present document establishes the minimum performance requirements for NR User Equipment (UE).

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.521-4: "NR; User Equipment (UE) radio transmission and reception; Part 4: Performance requirements".
- [3] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [4] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [5] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [6] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [7] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [8] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [11] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [12] 3GPP TS 38.214: "NR; Physical layer procedures for data".
- [13] 3GPP TS 37.340: "Evolved Universal Terrestrial Radio Access (E-UTRA) and NR; Multi-connectivity", Stage 2.
- [14] 3GPP TS 38.306: "NR; User Equipment (UE) radio access capabilities".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**DL BWP:** DL bandwidth part as defined in TS 38.213 [11].

**EN-DC:** E-UTRA-NR Dual Connectivity as defined in TS 37.340 [13, Section 4.1.2].

**FR1:** Frequency range 1 as defined in TS 38.101-3 [8, Section 5.1].

**FR2:** Frequency range 2 as defined in TS 38.101-3 [8, Section 5.1].

**SSB:** SS/PBCH block as defined in TS 38.211 [9, Section 7.8.3].

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

$\mu$	Subcarrier spacing configuration as defined in TS 38.211 [9, Section 4.2]
$N_{oc}$	The power spectral density of a white noise source with average power per RE normalized to the subcarrier spacing as defined in Section 4.4.3 for conducted requirements and Section 4.5.3 for radiated requirements

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

CA	Carrier Aggregation
CC	Component Carrier
CCE	Control Channel Element
CORESET	Control Resource Set
CP	Cyclic Prefix
CSI	Channel-State Information
CSI-IM	CSI Interference Measurement
CSI-RS	CSI Reference Signal
CW	Codeword
CQI	Channel Quality Indicator
CRC	Cyclic Redundancy Check
CRI	CSI-RS Resource Indicator
DC	Dual Connectivity
DCI	Downlink Control Information
DL	Downlink
DMRS	Demodulation Reference Signal
EPRE	Energy Per Resource Element
EN-DC	E-UTRA-NR Dual Connectivity
FR	Frequency Range
FRC	Fixed Reference Channel
HARQ	Hybrid Automatic Repeat Request
LI	Layer Indicator
MAC	Medium Access Control
MCS	Modulation and Coding Scheme
MIB	Master Information Block
NR	New Radio
NSA	Non-Standalone Operation Mode
OCNG	OFDMA Channel Noise Generator
OFDM	Orthogonal Frequency Division Multiplexing
OFDMA	Orthogonal Frequency Division Multiple Access
PBCH	Physical Broadcast Channel
Pcell	Primary Cell
PDCCH	Physical Downlink Control Channel
PDSCH	Physical Downlink Shared Channel

PMI	Precoding Matrix Indicator
PRB	Physical Resource Block
PRG	Physical resource block group
PSS	Primary Synchronization Signal
PTRS	Phase Tracking Reference Signal
PUCCH	Physical Uplink Control Channel
PUSCH	Physical Uplink Shared Channel
QCL	Quasi Co-location
RB	Resource Block
RBG	Resource Block Group
RE	Resource Element
REG	Resource Element Group
RI	Rank Indicator
RRC	Radio Resource Control
SA	Standalone operation mode
SCS	Subcarrier Spacing
SINR	Signal-to-Interference-and-Noise Ratio
SNR	Signal-to-Noise Ratio
SS	Synchronization Signal
SSB	Synchronization Signal Block
SSS	Secondary Synchronization Signal
TCI	Transmission Configuration Indicator
TDM	Time division multiplexing
TTI	Transmission Time Interval
UL	Uplink
VRB	Virtual Resource Block

## 4 General

### 4.1 Relationship between minimum requirements and test requirements

The present document is a Single-RAT and interwork specification for NR UE, covering minimum performance requirements of both conducted and radiated requirements. Conformance to the present specification is demonstrated by fulfilling the test requirements specified in the conformance specification TS 38.521-4 [2].

The Minimum Requirements given in this specification make no allowance for measurement uncertainty. The test specification TS 38.521-4 [2] defines test tolerances. These test tolerances are individually calculated for each test. The test tolerances are used to relax the minimum requirements in this specification to create test requirements.

The measurement results returned by the test system are compared – without any modification – against the test requirements as defined by the shared risk principle.

The shared risk principle is defined in Recommendation ITU-R M.1545 [3].

The applicability of each requirement is described under each sub-clause in [5.1, 6.1, 7.1 and 8.1].

### 4.2 Applicability of minimum requirements

The conducted minimum requirements specified in this specification shall be met in all applicable scenarios for FR1. The radiated minimum requirements specified in this specification shall be met in all applicable scenarios for FR2. The interwork minimum requirement specified in this specification shall be met in all applicable scenarios for NR interworking operation.

### 4.3 Specification suffix information

Unless stated otherwise the following suffixes are used for indicating at 2<sup>nd</sup> level subclause, shown in table 4.3-1.

**Table 4.3-1: Definition of suffixes**

Clause suffix	Variant
None	Single Carrier
A	Carrier Aggregation (CA)
B	Dual-Connectivity (DC)
C	Supplement Uplink (SUL)

A terminal which supports the above features needs to meet the requirement defined in the additional subclause (suffix A, B, C) in clauses 5, 6, 7, 8, 9, 10.

## 4.4 Conducted requirements

### 4.4.1 Conducted requirement reference point

The reference point for SNR and Noc of DL signal is the UE antenna connector or connectors.

### 4.4.2 SNR definition

UE demodulation and CSI requirements define the SNR as:

$$SNR = \frac{\sum_{j=1}^{N_{RX}} E_s^{(j)}}{\sum_{j=1}^{N_{RX}} N_{oc}^{(j)}}$$

$N_{RX}$  denotes the number of receiver antenna connectors and the superscript receiver antenna connector  $j$ .

The above SNR definition assumes that the REs are not precoded, and does not account for any gain which can be associated to the precoding operation.

$E_s$  denotes the averaged received energy per resource element (EPRE) of the wanted signal. Unless otherwise stated, the SNR refers to the SSS wanted signal. The downlink SSS transmit power is defined as the linear average over the power contributions in [W] of all resource elements that carry the SSS within the operating system bandwidth.

The power ratio of other wanted signals to the SSS is defined in each requirement.

$N_{oc}$  denotes the power spectral density of a white noise source, with average power per RE normalized to the subcarrier spacing.


### 4.4.3 Noc

Unless otherwise stated, the spectral density of Noc is [-142dBm/Hz].

## 4.5 Radiated requirements

### 4.5.1 Radiated requirement reference point

The reference point for SNR and Noc of DL signal from the UE perspective is the input of UE antenna array.

**Figure 4.5.1-1: Reference point for radiated Demodulation and CSI requirements**

Radiated performance requirements are specified at the Reference point, with signal-to-noise ratio (SNR)  $\text{SNR}_{\text{RP}} = \text{SNR}_{\text{BB}} + \Delta_{\text{BB}}$

where  $\text{SNR}_{\text{BB}}$  is the baseband SNR level specified by the Minimum performance requirement in clause 7, 8, 9 and 10, and  $\Delta_{\text{BB}}$  is specified in clause 4.5.3.2. The noise spectral density for Noc is specified in Table 4.5.3.2-1.

## 4.5.2 SNR definition

UE demodulation and CSI requirements define the SNR as:

$$\text{SNR}_{\langle\text{signal}\rangle} = \frac{\sum_{j=1}^{N_{\text{RX}}} \hat{E}_{\langle\text{signal}\rangle}^{(j)}}{\sum_{j=1}^{N_{\text{RX}}} N_{\text{oc}}^{(j)}}$$

$N_{\text{RX}}$  denotes the number of receiver reference points, and the super script receiver reference point  $j$ .

The above SNR definition assumes that the REs are not precoded, and does not account for any gain which can be associated to the precoding operation.

$\hat{E}_{\langle\text{signal}\rangle}$  denotes the averaged received energy per resource element (EPRE) of the wanted signal. Unless otherwise stated, the SNR refers to the SSS wanted signal. The downlink SSS transmit power is defined as the linear average over the power contributions in [W] of all resource elements that carry the SSS within the operating system bandwidth.

The power ratio of other wanted signals to the SSS is defined in each requirement.

$N_{\text{oc}}$  denotes the power spectral density of a white noise source, with average power per RE normalized to the subcarrier spacing.

## 4.5.3 Noc

### 4.5.3.1 Introduction

For radiated testing of demodulation and CSI requirements it is not feasible in practice to use signal levels high enough to make the noise contribution of the UE negligible. Demodulation requirements are therefore specified with the applied noise higher than the UE peak EIS level in TS 38.101-2 [7] by a defined amount, so that the impact of UE noise floor is limited to no greater than a value  $\Delta_{\text{BB}}$  at the specified Noc level. As UEs have EIS levels that are dependent on operating band and power class, Noc level is dependent on operating band and power class.

### 4.5.3.2 Noc for NR operating bands in FR2

Values for Noc according to operating band and power class for single carrier requirements are specified in Table 4.5.3.2-1 for  $\Delta_{\text{BB}} = 1\text{dB}$ .

**Table 4.5.3.2-1: Noc power level for different UE power classes and frequency bands**

Operating band	UE Power class			
	1	2	3	4
n257	-166.8	-163.8	-157.6	-166.3
n258	-166.8	-163.8	-157.6	-166.3
n260	-163.8		-155.0	-164.3
n261	-166.8	-163.8	-157.6	-166.3

Note 1: Noc levels are specified in dBm/Hz

The handling of Carrier Aggregation is FFS, and the handling of multi-band relaxation is FFS.

### 4.5.3.3 Derivation of Noc values for NR operating bands in FR2

The Noc values in Table 4.5.3.2-1 are based on Refsens for the Operating band and on the UE Power class, and taking a baseline of UE Power class 3 in Band n260.

$$\text{Spectral density of Noc} = \text{Refsens}_{\text{PC3}, \text{n260, 50MHz}} - 10\log_{10}(\text{SCS}_{\text{Refsens}} \times \text{PRB}_{\text{Refsens}} \times 12) - \text{SNR}_{\text{Refsens}} + \Delta_{\text{thermal}}$$

where:

$\text{Refsens}_{\text{PC3, n260, 50MHz}}$  is the Refsens value in dBm specified for Power Class 3 in Band n260 for 50MHz Channel bandwidth in TS 38.101-2 [7, Table 7.3.2.3-1].

$\text{SCS}_{\text{Refsens}}$  is a subcarrier spacing associated with  $N_{\text{RB}}$  for 50MHz in TS 38.101-2 [7, Table 5.3.2-1], chosen as 120kHz.

$\text{PRB}_{\text{Refsens}}$  is  $N_{\text{RB}}$  associated with subcarrier spacing 120 kHz for 50MHz in TS 38.101-2 [7, Table 5.3.2-1] and is 32.

12 is the number of subcarriers in a PRB

$\text{SNR}_{\text{Refsens}}$  is the SNR used for simulation of Refsens, and is -1dB

$\Delta_{\text{thermal}}$  is the amount of dB that the wanted noise is set above UE thermal noise, giving a rise in total noise of  $\Delta_{\text{BB}}$ .  $\Delta_{\text{thermal}}$  is chosen as 6dB, giving a rise in total noise of 1dB.

The calculated Noc value for the baseline of UE Power class 3 in Band n260 in Group Y is rounded to -155 dBm/Hz.

The following methodology to define the Noc level for operating band X (Band\_X) and power class Y (PC\_Y) is used for the single carrier case:

$$\text{Noc}(\text{Band}_X, \text{PC}_Y) = -155 \text{ dBm/Hz} + \text{Refsens}_{\text{PC}_Y, \text{Band}_X, 50\text{MHz}} - \text{Refsens}_{\text{PC3, n260, 50MHz}}$$

#### 4.5.4 Angle of arrival

Unless otherwise stated, the downlink signal and noise are aligned to arrive in the UE Rx beam peak direction as defined in TS 38.101-2 [7].

## 5 Demodulation performance requirements (Conducted requirements)

### 5.1 General

#### 5.1.1 Applicability of requirements

### 5.2 PDSCH demodulation requirements

The parameters specified in Table 5.2-1 are valid for all PDSCH tests unless otherwise stated.

**Table 5.2-1: Common test parameters**

Parameter		Unit	Value
PDSCH transmission scheme			Transmission scheme 1
EPRE ratio of PTRS to PDSCH		dB	N/A
Common serving cell parameters	Cyclic prefix		Normal
	Physical Cell ID		0
	SSB position in burst		First SSB in Slot #0
	SSB periodicity	ms	20
PDCCH configuration	First DMRS position for Type A PDSCH mapping		2
	Slots for PDCCH monitoring		Each slot
	Symbols with PDCCH	Symbols	0, 1
	Number of PDCCH candidates and aggregation levels		TBD
DCI format			TBD
Cross carrier scheduling			Not configured
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS		$k_0=0$ for CSI-RS resource 1,2,3,4
	First OFDM symbol in the PRB used for CSI-RS		$l_0 = 6$ for CSI-RS resource 1 and 3 $l_0 = 10$ for CSI-RS resource 2 and 4
	Number of CSI-RS ports (X)		1 for CSI-RS resource 1,2,3,4
	CDM Type		'No CDM' for CSI-RS resource 1,2,3,4
	Density ( $\rho$ )		3 for CSI-RS resource 1,2,3,4
	CSI-RS periodicity	Slots	15 kHz SCS: 20 for CSI-RS resource 1,2,3,4 30 kHz SCS: 40 for CSI-RS resource 1,2,3,4
	CSI-RS offset	Slots	15 kHz SCS: 10 for CSI-RS resource 1 and 2 11 for CSI-RS resource 3 and 4  30 kHz SCS: 20 for CSI-RS resource 1 and 2 21 for CSI-RS resource 3 and 4
NZP CSI-RS for CSI acquisition	First subcarrier index in the PRB used for CSI-RS		$k_0 = 0$
	First OFDM symbol in the PRB used for CSI-RS		$l_0 = 12$
	Number of CSI-RS ports (X)		Same as number of transmit antenna
	CDM Type		'FD-CDM2'
	Density ( $\rho$ )		1
	CSI-RS periodicity	Slots	15 kHz SCS: 20 30 kHz SCS: 40
ZP CSI-RS for CSI acquisition	CSI-RS offset	Slots	0
	First subcarrier index in the PRB used for CSI-RS		$k_0 = 4$
	First OFDM symbol in the PRB used for CSI-RS		$l_0 = 12$
	Number of CSI-RS ports (X)		4
	CDM Type		'FD-CDM2'
	Density ( $\rho$ )		1
	CSI-RS periodicity	Slots	15 kHz SCS: 20 30 kHz SCS: 40
PDSCH DMRS configuration	CSI-RS offset	Slots	0
	Antenna ports indexes		{1000} for Rank 1 tests {1000, 1001} for Rank 2 tests {1000-1002} for Rank 3 tests {1000-1003} for Rank 4 tests
	Number of PDSCH DMRS CDM group(s) without data		1 for Rank 1 and Rank 2 tests 2 for Rank 3 and Rank 4 tests
PTRS configuration			PTRS is not configured
Maximum number of code block groups for ACK/NACK feedback			1
Maximum number of HARQ transmission			4
Redundancy version coding sequence			{0,2,3,1}
Precoding configuration			SP Type I, Random per slot with PRB bundling granularity

Symbols for all unused Res		OCNG Annex A.5
----------------------------	--	----------------

## 5.2.1 1RX requirements

(Void)

## 5.2.2 2RX requirements

### 5.2.2.1 FDD

#### 5.2.2.1.1 Minimum requirements for PDSCH Mapping Type A

The performance requirements are specified in Table 5.2.2.1.1-3 and Table 5.2.2.1.1-4, with the addition of test parameters in table 5.2.2.1.1-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.1.1-1.

**Table 5.2.2.1.1-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 2 receive antenna conditions and with different channel models, MCSs and number of MIMO layers]	[1-1, 1-2, 1-3, 2-1, 2-3]
[Verify the PDSCH mapping Type A HARQ soft combining performance under 2 receive antenna conditions.]	[1-4]
[Verify the PDSCH mapping Type A enhanced performance requirement Type X under 2 receive antenna conditions and with 2 MIMO layers.]	[2-2]

**Table 5.2.2.1.1-2: Test parameters**

Parameter		Unit	Value
Channel bandwidth		MHz	20 for Test 2-3 10 for other tests
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	51 for Test 2-3 52 for other tests
	Subcarrier spacing	kHz	30 for Test 2-3 15 for other tests
PDCCH configuration	Number of PRBs in CORESET	PRBs	48
PDSCH configuration	Mapping type		Type A
	k0		0
	Starting symbol (S)		2
	Length (L)		12
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		4 for Test 1-1 2 for other tests
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		2 for Test 1-1 1 for other tests
	Length		Single symbol
Number of HARQ Processes			8 for Tests 1-4, [2-1] [4 for other tests]
K1 value (PDSCH-to-HARQ-timing-indicator)			TBD

**Table 5.2.2.1.1-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-1.1 FDD	QPSK, 0.30	TDLB100-400	2x2, ULA Low	70	[-0.9]
1-2	R.PDSCH.1-1.2 FDD	QPSK, 0.30	TDLC300-100	2x2, ULA Low	70	[0.5]
1-3	R.PDSCH.1-4.1 FDD	256QAM, 0.82	TDLA30-10	2x2, ULA Low	70	[24.5]
1-4	R.PDSCH.1-2.1 FDD	16QAM, 0.48	TDLC300-100	2x2, ULA Low	30	[1.3]

**Table 5.2.2.1.1-4: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
2-1	R.PDSCH.1-3.1 FDD	64QAM, 0.51	TDLA30-10	2x2, ULA Low	70	TBD
2-2	R.PDSCH.1-2.2 FDD	16QAM, 0.48	TDLA30-10	2x2, ULA Medium	70	[17.5]
2-3	R.PDSCH.2-1.1 FDD	64QAM, 0.51	TDLA30-10	2x2, ULA Low	70	TBD

**5.2.2.1.2 Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH**

The performance requirements are specified in Table 5.2.2.1.2-3, with the addition of test parameters in table 5.2.2.1.2-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.1.2-1.

**Table 5.2.2.1.2-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 2 receive antenna conditions and CSI-RS overlapped with PDSCH]	[1-1]

**Table 5.2.2.1.2-2: Test parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	10
Duplex mode		FDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	52
	Subcarrier spacing	15 kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs 48
PDSCH configuration	Mapping type	Type A
	k <sub>0</sub>	0
	Starting symbol (S)	2
	Length (L)	12
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	2
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
NZP CSI-RS for CSI acquisition	OFDM symbols in the PRB used for CSI-RS	l <sub>0</sub> = 13
	CSI-RS periodicity	5
ZP CSI-RS for CSI acquisition	Subcarrier index in the PRB used for CSI-RS	(k <sub>0</sub> , k <sub>1</sub> , k <sub>2</sub> , k <sub>3</sub> )=(2, 4, 6, 8)
	Number of CSI-RS ports (X)	8
	CSI-RS periodicity	5
Number of HARQ Processes		4
K1 value (PDSCH-to-HARQ-timing-indicator)		TBD

**Table 5.2.2.1.2-3: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-5.1 FDD	16QAM, 0.48	TDLC300-100	2x2, ULA Low	70	[14.7]

### 5.2.2.1.3 Minimum requirements for PDSCH Mapping Type B

The performance requirements are specified in Table 5.2.2.1.3-3, with the addition of test parameters in Table 5.2.2.1.3-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.1.3-1.

**Table 5.2.2.1.3-1: Tests purpose**

Purpose	Test index
[Verify PDSCH mapping Type B performance under 2 receive antenna conditions]	[1-1]

**Table 5.2.2.1.3-2: Test parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	10
Duplex mode		FDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	52
	Subcarrier spacing	15 kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs
PDSCH configuration	Mapping type	Type B
	k0	0
	Starting symbol (S)	5
	Length (L)	7
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	2
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
Number of HARQ Processes		4
K1 value (PDSCH-to-HARQ-timing-indicator)		2

**Table 5.2.2.1.3-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-1.4 FDD	QPSK, 0.30	TDLA30-10	2x2, ULA Low	70	[-1.0]

### 5.2.2.1.4 Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence

The performance requirements are specified in Table 5.2.2.1.4-3, with the addition of test parameters in Table 5.2.2.1.4-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.1.4-1.

**Table 5.2.2.1.4-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 2 receive antenna conditions with CRS rate matching configured]	[1-1]

**Table 5.2.2.1.4-2: Test parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	10
Duplex mode		FDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	52
	Subcarrier spacing	15 kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs 48
PDSCH configuration	Mapping type	Type A
	k0	0
	Starting symbol (S)	3
	Length (L)	[9]
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	2
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
CRS for rate matching	LTE carrier Center	[Same as NR carrier]
	LTE carrier BW	MHz 10
	Number of antenna ports	4
	v-shift	0
Number of HARQ Processes		4
K1 value (PDSCH-to-HARQ-timing-indicator)		2

**Table 5.2.2.1.4-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-1.4 FDD	QPSK, 0.30	TDLA30-10	4x2, ULA Low	70	[-0.8]

## 5.2.2.2 TDD

### 5.2.2.2.1 Minimum requirements for PDSCH Mapping Type A

The performance requirements are specified in Table 5.2.2.2.1-3 and Table 5.2.2.2.1-4, with the addition of test parameters in Table 5.2.2.2.1-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.2.1-1.

**Table 5.2.2.2.1-1: Tests purpose**

<b>Purpose</b>	<b>Test index</b>
[Verify the PDSCH mapping Type A normal performance under 2 receive antenna conditions and with different channel models, MCSs and number of MIMO layers.]	[1-1, 1-2, 1-3, 1-5, 1-6, 2-1]
[Verify the PDSCH mapping Type A HARQ soft combining performance under 2 receive antenna conditions.]	[1-4]
[Verify the PDSCH mapping Type A enhanced performance requirement Type X under 2 receive antenna conditions and with 2 MIMO layers.]	[2-2]

**Table 5.2.2.2.1-2: Test parameters**

<b>Parameter</b>	<b>Unit</b>	<b>Value</b>
Channel bandwidth	MHz	20 for Test 2-3 40 for other tests
Duplex mode		TDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	51 for Test 2-3 106 for other tests
	Subcarrier spacing	kHz 30
PDCCH configuration	Number of PRBs in CORESET	PRBs 48 for Test 2-3 102 for other tests
PDSCH configuration	Mapping type	Type A
	k0	0
	Starting symbol (S)	2
	Length (L)	Specific to each Reference channel
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	4 for Tests 1-1 2 for other tests
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	2 for Test 1-1 1 for other tests
	Length	1
Number of HARQ Processes		16 for Test 1-4, [2-1] 8 for other tests
K1 value (PDSCH-to-HARQ-timing-indicator)		Specific to each UL-DL pattern

**Table 5.2.2.2.1-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.2-1.1 TDD	QPSK, 0.30	FR1.30-1	TDLB100-400	2x2, ULA Low	70	[-0.9]
1-2	R.PDSCH.2-1.2 TDD	QPSK, 0.30	FR1.30-1	TDLC300-100	2x2, ULA Low	70	[0.3]
1-3	R.PDSCH.2-4.1 TDD	256QAM, 0.82	FR1.30-1	TDLA30-10	2x2, ULA Low	70	TBD
1-4	R.PDSCH.2-2.1 TDD	16QAM, 0.48	FR1.30-1	TDLC300-100	2x2, ULA Low	30	[1.5]
1-5	[R.PDSCH.2-5.1 TDD]	QPSK, 0.3	FR1.30-2	TDLA30-10	2x2, ULA Low	70	[-0.9]
1-6	[R.PDSCH.2-6.1 TDD]	QPSK, 0.30	FR1.30-3	TDLA30-10	2x2, ULA Low	70	[-0.9]

**Table 5.2.2.2.1-4: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
2-1	R.PDSCH.2-3.1 TDD	64QAM, 0.51	FR1.30-1	TDLA30-10	2x2, ULA Low	70	TBD
2-2	R.PDSCH.2-2.2 TDD	16QAM, 0.48	FR1.30-1	TDLA30-10	2x2, ULA Medium	70	[18.0]
2-3	R.PDSCH.2-3.2 TDD	64QAM, 0.51	FR1.30-1	TDLA30-10	2x2, ULA Low	70	[19.2]

## 5.2.2.2.2 Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH

The performance requirements are specified in Table 5.2.2.2-3, with the addition of test parameters in Table 5.2.2.2-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.2.2-1.

**Table 5.2.2.2.2-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 2 receive antenna conditions and CSI-RS overlapped with PDSCH]	[1-1]

**Table 5.2.2.2.2-2: Test parameters**

<b>Parameter</b>		<b>Unit</b>	<b>Value</b>
Channel bandwidth		MHz	40
Duplex mode			TDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	106
	Subcarrier spacing	kHz	30
PDCCH configuration	Number of PRBs in CORESET	PRBs	102
PDSCH configuration	Mapping type		Type A
	$k_0$		0
	Starting symbol (S)		2
	Length (L)		Specific to each Reference channel
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	Length		1
NZP CSI-RS for CSI acquisition	OFDM symbols in the PRB used for CSI-RS		$l_0 = 13$
	CSI-RS periodicity		5
ZP CSI-RS for CSI acquisition	Subcarrier index in the PRB used for CSI-RS		$(k_0, k_1, k_2, k_3) = (2, 4, 6, 8)$
	Number of CSI-RS ports (X)		8
	CSI-RS periodicity		5
Number of HARQ Processes			8
K1 value (PDSCH-to-HARQ-timing-indicator)			Specific to each UL-DL pattern

**Table 5.2.2.2.2-3: Minimum performance for Rank 2**

<b>Test num.</b>	<b>Reference channel</b>	<b>Modulation format and code rate</b>	<b>TDD UL-DL pattern</b>	<b>Propagation condition</b>	<b>Correlation matrix and antenna configuration</b>	<b>Reference value</b>	
						<b>Fraction of maximum throughput (%)</b>	<b>SNR (dB)</b>
1-1	R.PDSCH.2-7.1 TDD	16QAM, 0.48	FR1.30-1	TDLC300-100	2x2, ULA Low	70	TBD

### 5.2.2.2.3 Minimum requirements for PDSCH Mapping Type B

The performance requirements are specified in Table 5.2.2.2.3-3, with the addition of test parameters in Table 5.2.2.2.3-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.2.2.3-1.

**Table 5.2.2.2.3-1: Tests purpose**

<b>Purpose</b>	<b>Test index</b>
[Verify PDSCH mapping Type B performance under 2 receive antenna conditions]	[1-1]

**Table 5.2.2.2.3-2: Test parameters**

Parameter		Unit	Value
Channel bandwidth		MHz	40
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	106
	Subcarrier spacing	kHz	30
PDCCH configuration	Number of PRBs in CORESET	PRBs	102
PDSCH configuration	Mapping type		Type B
	k0		0
	Starting symbol (S)		5
	Length (L)		7
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	Length		1
Number of HARQ Processes			4
K1 value (PDSCH-to-HARQ-timing-indicator)			2

**Table 5.2.2.2.3-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH,2-1.3 TDD	QPSK, 0.30	FR1.30-1	TDLA30-10	2x2, ULA Low	70	[-1.0]

## 5.2.3 4RX requirements

### 5.2.3.1 FDD

#### 5.2.3.1.1 Minimum requirements for PDSCH Mapping Type A

The performance requirements are specified in Table 5.2.3.1.1-3, Table 5.2.3.1.1-4, Table 5.2.3.1.1-5 and Table 5.2.3.1.1-6, with the addition of test parameters in Table 5.2.3.1.1-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.1.1-1.

**Table 5.2.3.1.1-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 4 receive antenna conditions and with different channel models, MCSs and number of MIMO layers.]	[1-1, 1-2, 1-3, 2-1, 2-2, 3-1, 4-1]
[Verify the PDSCH mapping Type A HARQ soft combining performance under 4 receive antenna conditions.]	[1-4]
[Verify the PDSCH mapping Type A enhanced performance requirement Type X under 4 receive antenna conditions and with 3 MIMO layers.]	[3-2]

**Table 5.2.3.1.1-2: Test parameters**

<b>Parameter</b>		<b>Unit</b>	<b>Value</b>
Channel bandwidth		MHz	20 for Test 2-2 10 for other tests
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	51 for Test 2-2 52 for other tests
	Subcarrier spacing	kHz	30 for Test 2-2 15 for other tests
PDCCH configuration	Number of PRBs in CORESET	PRBs	51 for Test 2-2 52 for other tests
PDSCH configuration	Mapping type		Type A
	k0		0
	Starting symbol (S)		2
	Length (L)		12
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		4 for Test 1-1 WB for Test 3-1 2 for other tests
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		2 for Test 1-1 1 for other tests
	Length		1
Number of HARQ Processes			8 for Test 1-4, [2-1] 4 for other tests
K1 value (PDSCH-to-HARQ-timing-indicator)			2

**Table 5.2.3.1.1-3: Minimum performance for Rank 1**

<b>Test num.</b>	<b>Reference channel</b>	<b>Modulation format and code rate</b>	<b>Propagation condition</b>	<b>Correlation matrix and antenna configuration</b>	<b>Reference value</b>	
					<b>Fraction of maximum throughput (%)</b>	<b>SNR (dB)</b>
1-1	R.PDSCH.1-1.1 FDD	QPSK, 0.30	TDLB100-400	2x4, ULA Low	70	[-3.7]
1-2	R.PDSCH.1-1.2 FDD	QPSK, 0.30	TDLC300-100	2x4, ULA Low	70	[-2.7]
1-3	R.PDSCH.1-4.1 FDD	256QAM, 0.82	TDLA30-10	2x4, ULA Low	70	[21.0]
1-4	R.PDSCH.1-2.1 FDD	16QAM, 0.48	TDLC300-100	2x4, ULA Low	30	[-1.5]

**Table 5.2.3.1.1-4: Minimum performance for Rank 2**

<b>Test num.</b>	<b>Reference channel</b>	<b>Modulation format and code rate</b>	<b>Propagation condition</b>	<b>Correlation matrix and antenna configuration</b>	<b>Reference value</b>	
					<b>Fraction of maximum throughput (%)</b>	<b>SNR (dB)</b>
2-1	R.PDSCH.1-3.1 FDD	64QAM, 0.51	TDLA30-10	2x4, ULA Low	70	[TBD]
2-2	R.PDSCH.2-1.1 FDD	64QAM, 0.51	TDLA30-10	2x4, ULA Low	70	TBD

**Table 5.2.3.1.1-5: Minimum performance for Rank 3**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
3-1	R.PDSCH.1-2.3 FDD	16QAM, 0.48	TDLA30-10	4x4, ULA Low	70	[10.9]
3-2	R.PDSCH.1-2.3 FDD	16QAM, 0.48	TDLA30-10	4x4, ULA Medium A	70	[22.2]

**Table 5.2.3.1.1-6: Minimum performance for Rank 4**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
4-1	R.PDSCH.1-2.4 FDD	16QAM, 0.48	TDLA30-10	4x4, ULA Low	70	[15.5]

### 5.2.3.1.2 Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH

The performance requirements are specified in Table 5.2.3.1.2-3, with the addition of test parameters in table 5.2.3.1.2-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.1.2-1.

**Table 5.2.3.1.2-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 4 receive antenna conditions and CSI-RS overlapped with PDSCH]	[1-1]

**Table 5.2.3.1.2-2: Test parameters**

Parameter		Unit	Value
Channel bandwidth		MHz	10
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	52
	Subcarrier spacing	kHz	15
PDCCH configuration	Number of PRBs in CORESET	PRBs	48
PDSCH configuration	Mapping type		Type A
	$k_0$		0
	Starting symbol (S)		2
	Length (L)		12
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	Length		1
NZP CSI-RS for CSI acquisition	OFDM symbols in the PRB used for CSI-RS		$l_0 = 13$
	CSI-RS periodicity		5
ZP CSI-RS for CSI acquisition	Subcarrier index in the PRB used for CSI-RS		$(k_0, k_1, k_2, k_3) = (2, 4, 6, 8)$
	Number of CSI-RS ports (X)		8
	CSI-RS periodicity		5
Number of HARQ Processes			4
K1 value (PDSCH-to-HARQ-timing-indicator)			TBD

**Table 5.2.3.1.2-3: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-5.1 FDD	16QAM, 0.48	TDLC300-100	4x4, ULA Low	70	[9.0]

### 5.2.3.1.3 Minimum requirements for PDSCH Mapping Type B

The performance requirements are specified in Table 5.2.3.1.3-3, with the addition of test parameters in Table 5.2.3.1.3-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.1.3-1.

**Table 5.2.3.1.3-1: Tests purpose**

Purpose	Test index
[PDSCH mapping Type B performance under 4 receive antenna conditions]	[1-1]

**Table 5.2.3.1.3-2: Test parameters**

Parameter		Unit	Value
Channel bandwidth		MHz	10
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	52
	Subcarrier spacing	kHz	15
PDCCH configuration	Number of PRBs in CORESET	PRBs	48
PDSCH configuration	Mapping type		Type B
	k0		0
	Starting symbol (S)		5
	Length (L)		7
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		Type 0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		N/A
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	Length		1
Number of HARQ Processes			4
K1 value (PDSCH-to-HARQ-timing-indicator)			2

**Table 5.2.3.1.3-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	Propagation condition	Correlation matrix and antenna configuration	Reference value	
					Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.1-1.4 FDD	QPSK, 0.30	TDLA30-10	4x4, ULA Low	70	[-4.0]

#### 5.2.3.1.4 Minimum requirements for PDSCH Mapping Type A and LTE-NR coexistence

The performance requirements are specified in Table 5.2.3.1.4-3, with the addition of test parameters in Table 5.2.3.1.4-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.1.4-1.

**Table 5.2.3.1.3-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 4 receive antenna conditions with CRS rate matching configured]	[1-1]

**Table 5.2.3.1.3-2: Test parameters**

<b>Parameter</b>		<b>Unit</b>	<b>Value</b>
Channel bandwidth		MHz	10
Duplex mode			FDD
Active DL BWP index			1
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB	PRBs	52
	Subcarrier spacing	kHz	15
PDCCH configuration	Number of PRBs in CORESET	PRBs	48
PDSCH configuration	Mapping type		0
	k0		52
	Starting symbol (S)		15
	Length (L)		48
	PDSCH aggregation factor		Type A
	PRB bundling type		0
	PRB bundling size		3
	Resource allocation type		[9]
	VRB-to-PRB mapping type		1
	VRB-to-PRB mapping interleaver bundle size		Static
PDSCH DMRS configuration	DMRS Type		2
	Number of additional DMRS		Type 0
	Length		Non-interleaved
CRS for rate matching	LTE carrier Center		[Same as NR carrier]
	LTE carrier BW	MHz	10
	Number of antenna ports		4
	v-shift		0
Number of HARQ Processes			4
K1 value (PDSCH-to-HARQ-timing-indicator)			2

**Table 5.2.3.1.3-3: Minimum performance for Rank 1**

<b>Test num.</b>	<b>Reference channel</b>	<b>Modulation format and code rate</b>	<b>Propagation condition</b>	<b>Correlation matrix and antenna configuration</b>	<b>Reference value</b>	
					<b>Fraction of maximum throughput (%)</b>	<b>SNR (dB)</b>
1-1	R.PDSCH.1-1.4 FDD	QPSK, 0.30	TDLA30-10	4x4, ULA Low	70	[-3.9]

### 5.2.3.2 TDD

#### 5.2.3.2.1 Minimum requirements for PDSCH Mapping Type A

The performance requirements are specified in Table 5.2.3.2.1-3, Table 5.2.3.2.1-4, Table 5.2.3.2.1-5 and Table 5.2.3.2.1-6, with the addition of test parameters in Table 5.2.3.2.1-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.2.1-1.

**Table 5.2.3.2.1-1: Tests purpose**

<b>Purpose</b>	<b>Test index</b>
[Verify the PDSCH mapping Type A normal performance under 4 receive antenna conditions and with different channel models, MCSs and number of MIMO layers.]	[1-1, 1-2, 1-3, 1-5, 1-6, 2-1, 2-2, 3-1, 4-1]
[Verify the PDSCH mapping Type A HARQ soft combining performance under 4 receive antenna conditions.]	[1-4]
[Verify the PDSCH mapping Type A enhanced performance requirement Type X under 4 receive antenna conditions and with 3 MIMO layers.]	[3-2]

**Table 5.2.3.2.1-2: Test parameters**

<b>Parameter</b>	<b>Unit</b>	<b>Value</b>
Channel bandwidth	MHz	20 for Test 2-2 40 for other tests
Duplex mode		TDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	PRBs 51 for Test 2-2 106 for other tests
	Subcarrier spacing	kHz 30
PDCCH configuration	Number of PRBs in CORESET	PRBs 48 for Test 2-2 102 for other tests
PDSCH configuration	Mapping type	Type A
	k0	0
	Starting symbol (S)	2
	Length (L)	Specific to each Reference channel
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	4 for Test 1-1 2 for other tests
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	2 for Tests 1-1 1 for other tests
	Length	1
Number of HARQ Processes		16 for Test 1-4, [2-1] 8 for other tests
K1 value (PDSCH-to-HARQ-timing-indicator)		Specific to each UL-DL pattern

**Table 5.2.3.2.1-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.2-1.1 TDD	QPSK, 0.30	FR1.30-1	TDLB100-400	2x4, ULA Low	70	[-3.9]
1-2	R.PDSCH.2-1.2 TDD	QPSK, 0.30	FR1.30-1	TDLC300-100	2x4, ULA Low	70	[-2.7]
1-3	R.PDSCH.2-4.1 TDD	256QAM, 0.82	FR1.30-1	TDLA30-10	2x4, ULA Low	70	[TBD]
1-4	R.PDSCH.2-2.1 TDD	16QAM, 0.48	FR1.30-1	TDLC300-100	2x4, ULA Low	30	[-1.1]
1-5	[R.PDSCH.2-5.1 TDD]	QPSK, 0.3	FR1.30-2	TDLA30-10	2x4, ULA Low	70	[-3.9]
1-6	[R.PDSCH.2-6.1 TDD]	QPSK, 0.30	FR1.30-3	TDLA30-10	2x4, ULA Low	70	[-3.9]

**Table 5.2.3.2.1-4: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
2-1	R.PDSCH.2-3.1 TDD	64QAM, 0.51	FR1.30-1	TDLA30-10	2x4, ULA Low	70	TBD
2-2	R.PDSCH.2-3.2 TDD	64QAM, 0.51	FR1.30-1	TDLA30-10	2x4, ULA Low	70	[13.8]

**Table 5.2.3.2.1-5: Minimum performance for Rank 3**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
3-1	R.PDSCH.2-2.3 TDD	16QAM, 0.48	FR1.30-1	TDLA30-10	4x4, ULA Low	70	[11.4]
3-2	R.PDSCH.2-2.3 TDD	16QAM, 0.48	FR1.30-1	TDLA30-10	4x4, ULA Medium A	70	[22.9]

**Table 5.2.3.2.1-6: Minimum performance for Rank 4**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
4-1	R.PDSCH.2-2.4 TDD	16QAM, 0.48	FR1.30-1	TDLA30-10	4x4, ULA Low	70	[16.1]

### 5.2.3.2.2 Minimum requirements for PDSCH Mapping Type A and CSI-RS overlapped with PDSCH

The performance requirements are specified in Table 5.2.3.2.2-3, with the addition of test parameters in table 5.2.3.2.2-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.2.2-1.

**Table 5.2.3.2.2-1: Tests purpose**

Purpose	Test index
[Verify the PDSCH mapping Type A normal performance under 4 receive antenna conditions and CSI-RS overlapped with PDSCH]	[1-1]

**Table 5.2.3.2.2-2: Test parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	40
Duplex mode		TDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	30 kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs
	Mapping type	Type A
	k <sub>0</sub>	0
	Starting symbol (S)	2
	Length (L)	12
PDSCH configuration	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	2
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
NZP CSI-RS for CSI acquisition	OFDM symbols in the PRB used for CSI-RS	$l_0 = 13$
	CSI-RS periodicity	5
ZP CSI-RS for CSI acquisition	Subcarrier index in the PRB used for CSI-RS	$(k_0, k_1, k_2, k_3) = (2, 4, 6, 8)$
	Number of CSI-RS ports (X)	8
	CSI-RS periodicity	5
Number of HARQ Processes		8
K1 value (PDSCH-to-HARQ-timing-indicator)		Specific to each UL-DL pattern

**Table 5.2.3.2.2-3: Minimum performance for Rank 2**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH.2-7.1 TDD	16QAM, 0.48	FR1.30-1	TDLC300-100	4x4, ULA Low	70	TBD

### 5.2.3.2.3 Minimum requirements for PDSCH Mapping Type B

The performance requirements are specified in Table 5.2.3.2.3-3, with the addition of test parameters in Table 5.2.3.2.3-2 and the downlink physical channel setup according to Annex C.3.1.

The test purposes are specified in Table 5.2.3.2.3-1.

**Table 5.2.3.2.3-1: Tests purpose**

Purpose	Test index
[PDSCH mapping Type B performance under 4 receive antenna conditions]	[1-1]

**Table 5.2.3.2.3-2: Test parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	40
Duplex mode		FDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	30 kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs 102
PDSCH configuration	Mapping type	Type B
	k0	0
	Starting symbol (S)	5
	Length (L)	7
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	2
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
PDSCH DMRS configuration	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
Number of HARQ Processes		8
K1 value (PDSCH-to-HARQ-timing-indicator)		Specific to each UL-DL pattern

**Table 5.2.3.2.3-3: Minimum performance for Rank 1**

Test num.	Reference channel	Modulation format and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR (dB)
1-1	R.PDSCH,2-1.3 TDD	QPSK, 0.30	FR1.30-1	TDLA30-10	2x4, ULA Low	70	[-4.0]

## 5.3 PDCCH demodulation requirements

The receiver characteristics of the PDCCH are determined by the probability of miss-detection of the Downlink Scheduling Grant (Pm-dsg).

The parameters specified in Table 5.3-1 are valid for all PDCCH tests unless otherwise stated.

**Table 5.3-1: Common test Parameters**

Parameter		Unit	Value
DL BWP configuration #1	Cyclic prefix		Normal
Common serving cell parameters	Physical Cell ID		0
	SSB position in burst		1
	SSB periodicity	ms	20
PDCCH configuration	Slots for PDCCH monitoring		TBD
	Number of PDCCH candidates		TBD
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		0
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		CSI-RS resource 1: 4 CSI-RS resource 2: 8 CSI-RS resource 3: 4 CSI-RS resource 4: 8
	Number of CSI-RS ports ( $X$ )		1
	CDM Type		No CDM
	Density ( $\rho$ )		3
	CSI-RS periodicity	Slots	15 kHz SCS: 20 30 kHz SCS: 40
	CSI-RS offset	Slots	15 kHz SCS: 10 for CSI-RS resource 1 and 2 11 for CSI-RS resource 3 and 4  30 kHz SCS: 20 for CSI-RS resource 1 and 2 21 for CSI-RS resource 3 and 4
	Precoding configuration		SP Type I, Random per slot with REG bundling granularity for number of Tx larger than 1
	Symbols for all unused Res		OCNG in Annex A.5

### 5.3.1 1RX requirements

(Void)

### 5.3.2 2RX requirements

#### 5.3.2.1 FDD

The parameters specified in Table 5.3.2.1-1 are valid for all FDD tests unless otherwise stated.

**Table 5.3.2.1-1: Test Parameters**

Parameter	Unit	1 Tx Antenna	2 Tx Antenna
CCE to REG mapping type		nonInterleaved	
REG bundle size		6	
Shift index		0	

### 5.3.2.1.1 1 Tx Antenna performances

For the parameters specified in Table 5.3.2.1-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.2.1.1-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.2.1.1-1: Minimum performance for PDCCH with 15 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	10 MHz	24	2	2	R.PDCCH. 1-2.1 FDD	TDLA30-10	1x2 Low	1	[8.2]
2	10 MHz	24	2	2	R.PDCCH. 1-2.3 FDD	TDLC300-100	1x2 Low	1	[8.1]
3	10 MHz	48	2	4	R.PDCCH. 1-2.4 FDD	TDLA30-10	1x2 Low	1	[5.7]
4	10 MHz	48	1	4	R.PDCCH. 1-1.1 FDD	TDLA30-10	1x2 Low	1	[4.6]
5	10MHz	48	2	16	R.PDCCH. 1-2.6 FDD	TDLA30-10	1x2 Low	1	TBD

### 5.3.2.1.2 2 Tx Antenna performances

For the parameters specified in Table 5.3.2.1-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.2.1.2-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.2.1.2-1: Minimum performance for PDCCH with 15 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	10 MHz	24	2	4	R.PDCCH. 1-2.2 FDD	TDLC300-100	2x2 Low	1	[1.6]
2	10 MHz	48	2	8	R.PDCCH. 1-2.5 FDD	TDLC300-100	2x2 Low	1	[-1.6]
3	10 MHz	48	1	8	R.PDCCH. 1-1.3 FDD	TDLA30-10	2x2 Low	1	TBD

### 5.3.2.2 TDD

The parameters specified in Table 5.3.2.2-1 are valid for all TDD tests unless otherwise stated.

**Table 5.3.2.2-1: Test Parameters**

Parameter	Unit	1 Tx Antenna	2 Tx Antenna
TDD UL-DL pattern		FR1.30-1	
CCE to REG mapping type		interleaved	
Interleaver size		3	
REG bundle size		2	6
Shift Index		0	

### 5.3.2.2.1 1 Tx Antenna performances

For the parameters specified in Table 5.3.2.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.2.2.1-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.2.2.1-1: Minimum performance for PDCCH with 30 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	40 MHz	102	1	2	R.PDCCH. 2-1.1 TDD	TDLA30-10	1x2 Low	1	[7.0]
2	40 MHz	102	1	4	R.PDCCH. 2-1.2 TDD	TDLC300-100	1x2 Low	1	[3.2]
3	40 MHz	48	2	16	R.PDCCH. 2-2.1 TDD	TDLC300-100	1x2 Low	1	[-4.5]

### 5.3.2.2.2 2 Tx Antenna performances

For the parameters specified in Table 5.3.2.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.2.2.2-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.2.2.2-1: Minimum performance for PDCCH with 30 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	40 MHz	[90]	1	8	R.PDCCH. 2-1.3 TDD	TDLC300-100	2x2 Low	1	TBD

## 5.3.3 4RX requirements

### 5.3.3.1 FDD

The parameters specified in Table 5.3.3.1-1 are valid for all FDD tests unless otherwise stated.

**Table 5.3.3.1-1: Test Parameters**

Parameter	Unit	1 Tx Antenna	2 Tx Antenna
CCE to REG mapping type			nonInterleaved
REG bundle size		6	
Shift index		0	

### 5.3.3.1.1 1 Tx Antenna performances

For the parameters specified in Table 5.3.3.1-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.3.1.1-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.3.1.1-1: Minimum performance for PDCCH with 15 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	10 MHz	24	2	2	R.PDCCH. 1-2.1 FDD	TDLA30-10	1x4 Low	1	[2.1]
2	10 MHz	24	2	2	R.PDCCH. 1-2.3 FDD	TDLC300-100	1x4 Low	1	[2.3]
3	10 MHz	48	2	4	R.PDCCH. 1-2.4 FDD	TDLA30-10	1x4 Low	1	[0.0]
4	10 MHz	48	1	4	R.PDCCH. 1-1.1 FDD	TDLA30-10	1x4 Low	1	TBD

### 5.3.3.1.2 2 Tx Antenna performances

For the parameters specified in Table 5.3.3.1-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.3.1.2-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.3.1.2-1: Minimum performance for PDCCH with 15 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	10 MHz	24	2	4	R.PDCCH. 1-2.2 FDD	TDLC300-100	2x4 Low	1	TBD
2	10 MHz	48	2	8	R.PDCCH. 1-2.5 FDD	TDLC300-100	2x4 Low	1	[-4.9]
3	10 MHz	48	1	4	R.PDCCH. 1-1.3 FDD	TDLA30-10	2x4 Low	1	TBD

### 5.3.3.2 TDD

The parameters specified in Table 5.3.3.2-1 are valid for all TDD tests unless otherwise stated.

**Table 5.3.3.2-1: Common Test Parameters**

Parameter	Unit	1 Tx Antenna	2 Tx Antenna
TDD UL-DL pattern		FR1.30-1	
CCE to REG mapping type		interleaved	
Interleaver size		3	
REG bundle size		2	6
Shift Index		0	

### 5.3.3.2.1 1 Tx Antenna performances

For the parameters specified in Table 5.3.3.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.3.2.1-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.3.2.1-1: Minimum performance for PDCCH with 30 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	40 MHz	90	1	8	TBD	TDLC300-100	2x4 Low	1	TBD

### 5.3.3.2.2 2 Tx Antenna performances

For the parameters specified in Table 5.3.3.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 5.3.3.2.2-1. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.3.3.2.2-1: Minimum performance for PDCCH with 30 kHz SCS**

Test number	Bandwidth	CORE SET RB	CORES ET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR (dB)
1	40 MHz	90	1	8	TBD	TDLC300-100	2x4 Low	1	TBD

## 5.4 PBCH demodulation requirements

The receiver characteristics of PBCH are determined by the probability of miss-detection of the PBCH (Pm-bch), which is defined as

$$P_{m-bch} = 1 - \frac{A}{B}$$

Where A is the number of correctly decoded MIB PDUs and B is the number of transmitted MIB PDUs. The Pm-bch is derived with the assumption UE combines the PBCH symbols of the same SS/PBCH block index within the MIB TTI (80ms).

### 5.4.1 1RX requirements

(Void)

### 5.4.2 2RX requirements

#### 5.4.2.1 FDD

**Table 5.4.2.1-1: Test parameters for PBCH**

Parameter	Unit	Single antenna port
Physical Cell ID		0
Cyclic prefix		Normal
Number of SS/PBCH blocks within an SS burst set periodicity		1
SS/PBCH block index <sup>Note1</sup>		0
SS/PBCH block periodicity	ms	20
Note 1: as specified in TS 38.213 [11, Section 4.1]		

For the parameters specified in Table 5.4.2.1-1 the average probability of a miss-detected PBCH (Pm-bch) shall be below the specified values in Table 5.4.2.1-2 in case SS/PBCH block index is not known. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.4.2.1-2: Minimum performance PBCH in case SS/PBCH block index is not known**

Test number	Bandwidth	Reference channel	Propagation condition	Antenna configuration and correlation matrix	Reference value	
					Pm-bch (%)	SNR (dB)
1	10 MHz	[R.PBCH.1]	TDLC300-100	1 x 2 Low	1	TBD

#### 5.4.2.2 TDD

**Table 5.4.2.2-1: Test parameters for PBCH**

Parameter	Unit	Single antenna port
Physical Cell ID		0
Cyclic prefix		Normal
Number of SS/PBCH blocks within an SS burst set periodicity		1
SS/PBCH block index <sup>Note1</sup>		0
SS/PBCH block periodicity	ms	20
TDD UL-DL pattern		FR1.30-1
Note 1: as specified in TS 38.213 [11, Section 4.1]		
Note 2: as specified in TS 38.213 [11, Section 11.1]		

For the parameters specified in Table 5.4.2.2-1 the average probability of a miss-detected PBCH (Pm-bch) shall be below the specified values in Table 5.4.2.2-2 in case SS/PBCH block index is not known. The downlink physical setup is in accordance with Annex C.3.1.

**Table 5.4.2.2-2: Minimum performance PBCH in case SS/BPCH block index is not known**

Test number	Bandwidth	Reference channel	Propagation condition	Antenna configuration and correlation matrix	Reference value	
					Pm-bch (%)	SNR (dB)
1	40 MHz	R.PBCH.2	TDLA30-10	1 x 2 Low	1	TBD

## 5.5 Sustained downlink data rate provided by lower layers

### 5.5.1 FR1 single carrier requirements

The requirements in this clause are applicable to the FR1 single carrier case.

The requirements and procedure defined in Clause 5.5A.1 apply using operating band instead of CA configuration, and bandwidth instead of bandwidth combination.

## 5.5A Sustained downlink data rate provided by lower layers

### 5.5A.1 FR1 CA requirements

*<Editor's note: Open issues to be resolved:*

*Procedure to select CA bandwidth combination in multiple combinations have same largest data rate*

*Sustained rate minimum duration*

*PDCCH configuration (AL and DCI format)*

*MCS values for requirements*

*Whether same requirements apply for FR1 DC>*

The Sustained Data Rate (SDR) requirements in this clause are applicable to the FR1 CA.

The purpose of the test is to verify that the Layer 1 and Layer 2 correctly process in a sustained manner the received packets corresponding to the maximum data rate indicated by UE capabilities. The sustained downlink data rate shall be verified in terms of the success rate of delivered PDCP SDU(s) by Layer 2. The test case below specifies the RF conditions and the required success rate of delivered TB by Layer 1 to meet the sustained data rate requirement.

The test parameters are determined by the following procedure:

- Select one CA bandwidth combination among all supported CA configurations and set of per component carrier (CC) UE capabilities among all supported UE capabilities that provides the largest data rate [TS 38.306 [14, Section 4.1.2]].
- Set of per CC UE capabilities includes channel bandwidth, subcarrier spacing, number of PDSCH MIMO layers, modulation format and scaling factor [TS 38.306 [14, Section 4.1.2]].
- When there are multiple sets of CA bandwidth combinations and UE capabilities (channel bandwidth, subcarrier spacing, number of MIMO layer, modulation format, scaling factor) with same largest data rate, select TBD
- For each CC in CA bandwidth combination, use Table 5.5A-5 to determine MCS based on test parameters and indicated UE capabilities.

The TB success rate shall be higher than 85% when PDSCH is scheduled with MCS defined for the selected CA bandwidth combination and with the downlink physical channel setup according to Annex C.3.1.

The TB success rate is defined as  $100\% * N_{DL\_correct\_rx} / (N_{DL\_newtx} + N_{DL\_retx})$ , where  $N_{DL\_newtx}$  is the number of newly transmitted DL transport blocks,  $N_{DL\_retx}$  is the number of retransmitted DL transport blocks, and  $N_{DL\_correct\_rx}$  is the number of correctly received DL transport blocks. The TB success rate shall be sustained during at least TBD ms.

The common test parameters are specified in Table 5.5A-1. The parameters specified in Table 5.5A-2 are applicable for tests on FDD CCs and parameters specified in Table 5.5A-3 are applicable for tests on TDD CCs.

Unless otherwise stated, no user data is scheduled on slot #0 within 10 ms.

**Table 5.5A-1: Common test parameters for FDD and TDD component carriers**

Parameter	Unit	Value
PDSCH transmission scheme		Transmission scheme 1
EPRE ratio of PTRS to PDSCH	dB	N/A
Channel bandwidth	MHz	Channel bandwidth from selected CA bandwidth combination
Common serving cell parameters	Physical Cell ID	0
	SSB position in burst	First SSB in Slot #0
	SSB periodicity	ms 20
	First DMRS position for Type A PDSCH mapping	2
Cross carrier scheduling		Not configured
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	Maximum transmission bandwidth configuration as specified in TS 38.101-1 [6, Section 5.3.2] for tested channel bandwidth and subcarrier spacing
	Subcarrier spacing	kHz [15 or 30]
	Cyclic prefix	Normal
PDCCH configuration	Slots for PDCCH monitoring	Each slot
	Symbols with PDCCH	Symbols #0
	Number of PRBs in CORESET	Table 5.5A-4
	Number of PDCCH candidates and aggregation levels	TBD
	DCI format	TBD
PDSCH configuration	Mapping type	Type A
	k <sub>0</sub>	0
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	WB
	Resource allocation type	Type 0
	VRB-to-PRB mapping type	Non-interleaved
PDSCH DMRS configuration	VRB-to-PRB mapping interleaver bundle size	N/A
	DMRS Type	Type 1
	Number of additional DMRS	1
	Length	1
	Antenna ports indexes	{1000} for 1 Layer CCs {1000, 1001} for 2 Layers CCs {1000 – 1003} for 4 Layers CCs
PTRS configuration	Number of PDSCH DMRS CDM group(s) without data	1 for 1 layer and 2 layers CCs 2 for 4 Layers CCs
		PTRS is not configured
CSI-RS for tracking	Subcarrier indexes in the PRB used for CSI-RS	k <sub>0</sub> = 3 for CSI-RS resource 1,2,3,4
	OFDM symbols in the PRB used for CSI-RS	I <sub>0</sub> = 6 for CSI-RS resource 1 and 3 I <sub>0</sub> = 10 for CSI-RS resource 2 and 4
	Number of CSI-RS ports (X)	1 for CSI-RS resource 1,2,3,4
	CDM Type	'No CDM' for CSI-RS resource 1,2,3,4
	Density (ρ)	3 for CSI-RS resource 1,2,3,4
	CSI-RS periodicity	Slots 15 kHz SCS: 20 for CSI-RS resource 1,2,3,4 30 kHz SCS: 40 for CSI-RS resource 1,2,3,4
	CSI-RS offset	Slots 15 kHz SCS: 10 for CSI-RS resource 1 and 2 11 for CSI-RS resource 3 and 4  30 kHz SCS: 20 for CSI-RS resource 1 and 2 21 for CSI-RS resource 3 and 4
NZP CSI-RS for CSI acquisition	Subcarrier indexes in the PRB used for CSI-RS	k <sub>0</sub> = 4

	OFDM symbols in the PRB used for CSI-RS		$l_0 = 12$
	Number of CSI-RS ports (X)		Same as number of transmit antenna
	CDM Type		'FD-CDM2'
	Density ( $\rho$ )		1
	CSI-RS periodicity		15 kHz SCS: 20 30 kHz SCS: 40
	CSI-RS offset		0
ZP CSI-RS for CSI acquisition	Subcarrier indexes in the PRB used for CSI-RS		$k_0 = 0$
	OFDM symbols in the PRB used for CSI-RS		$l_0 = 12$
	Number of CSI-RS ports (X)		4
	CDM Type		'FD-CDM2'
	Density ( $\rho$ )		1
	CSI-RS periodicity		15 kHz SCS: 20 30 kHz SCS: 40
	CSI-RS offset		0
	Maximum number of code block groups for ACK/NACK feedback		1
	Maximum number of HARQ transmission		4
	HARQ ACK/NACK bundling		
Redundancy version coding sequence			{0,2,3,1}
Precoding configuration			SP Type I, Random per slot with PRB bundling granularity
Symbols for all unused Res			OCNG Annex A.5
Propagation condition			Static propagation condition No external noise sources are applied
Antenna configuration	1 layer CCs		[1x2 or 1x4]
	2 layers CCs		[2x2 or 2x4]
	4 layers CCs		[4x4]

**Table 5.5A-2: Additional test parameters for FDD CC**

Parameter	Unit	Value
Duplex mode		FDD
PDSCH configuration	Starting symbol (S)	1
	Length (L)	13
Number of HARQ Processes		TBD
K1 value		2

**Table 5.5A-3: Additional test parameters for TDD CC**

Parameter	Unit	Value
Duplex mode		TDD
PDSCH configuration	Starting symbol (S)	1
	Length (L)	13
Number of HARQ Processes		TBD
K1 value		Specific to each UL-DL pattern
TDD UL-DL pattern		15 kHz SCS: FR1.15-1 30 kHz SCS: FR1.30-1
Note 1: PDSCH is scheduled only on full DL slots		

**Table 5.5A-4: Number of PRBs in CORESET**

SCS (kHz)	5MHz	10MHz	15MHz	20 MHz	25 MHz	30 MHz	40 MHz	50MHz	60 MHz	80 MHz	100 MHz
15	24	48	78	102	132	156	216	270	N/A	N/A	N/A
30	6	24	36	48	60	78	102	132	162	216	270

**Table 5.5A-5: MCS indexes for indicated UE capabilities**

<b>Maximum number of PDSCH MIMO layers</b>	<b>Maximum modulation format</b>	<b>Scaling factor</b>	<b>MCS</b>
1	8	1	TBD
1	8	0.8	TBD
1	8	0.75	TBD
1	8	0.4	TBD
1	6	1	TBD
1	6	0.8	TBD
1	6	0.75	TBD
1	6	0.4	TBD
1	4	1	TBD
1	4	0.8	TBD
1	4	0.75	TBD
1	4	0.4	TBD
1	2	1	TBD
1	2	0.8	TBD
1	2	0.75	TBD
1	2	0.4	TBD
2	8	1	TBD
2	8	0.8	TBD
2	8	0.75	TBD
2	8	0.4	TBD
2	6	1	TBD
2	6	0.8	TBD
2	6	0.75	TBD
2	6	0.4	TBD
2	4	1	TBD
2	4	0.8	TBD
2	4	0.75	TBD
2	4	0.4	TBD
2	2	1	TBD
2	2	0.8	TBD
2	2	0.75	TBD
2	2	0.4	TBD
4	8	1	TBD
4	8	0.8	TBD
4	8	0.75	TBD
4	8	0.4	TBD
4	6	1	TBD
4	6	0.8	TBD
4	6	0.75	TBD
4	6	0.4	TBD
4	4	1	TBD
4	4	0.8	TBD
4	4	0.75	TBD
4	4	0.4	TBD
4	2	1	TBD
4	2	0.8	TBD
4	2	0.75	TBD
4	2	0.4	TBD

---

## 6 CSI reporting requirements (Conducted requirements)

### 6.1 General

This section includes conducted requirements for the reporting of channel state information (CSI).

### 6.1.1 Applicability of requirements

### 6.1.2 Common test parameters

Parameters specified in Table 6.1.2-1 are applied for all test cases in this section unless otherwise stated.

**Table 6.1.2-1: Test parameters for CSI test cases**

Parameter		Unit	Value
PDSCH transmission scheme			Transmission scheme 1
EPRE ratio of PTRS to PDSCH		dB	
Active DL BWP index			1
Cyclic prefix			Normal
Common serving cell parameters	Physical Cell ID		0
	SSB position in burst		First SSB in Slot #0
	SSB periodicity	ms	20
PDCCH configuration	Slots for PDCCH monitoring		Each slot
	Symbols with PDCCH		0,1
	Number of PDCCH candidates and aggregation levels		TBD
	DCI format		TBD
Cross carrier scheduling			Not configured
PDSCH configuration	Mapping type		Type A
	$k_0$		0
	Starting symbol (S)		2
	Length (L)		12
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		TBD
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	Length		Single-symbol DM-RS
	DMRS ports indexes		{1000} for Rank1 {1000,1001} for Rank2 {1000,1001,1002} for Rank3 {1000,1001,1002,1003} for Rank4
	Number of PDSCH DMRS CDM group(s) without data		2
PTRS configuration	Frequency density ( $K_{PT-RS}$ )		N/A
	Time density ( $L_{PT-RS}$ )		N/A
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		[0]
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		[4]
	Number of CSI-RS ports ( $X$ )		1
	CDM Type		No CDM
	Density ( $\rho$ )		3
	CSI-RS periodicity	slot	15 kHz SCS: 20 30 kHz SCS: 40
	CSI-RS offset	slot	15 kHz SCS: 10 for CSI-RS resource 1 and 2 11 for CSI-RS resource 3 and 4  30 kHz SCS: 20 for CSI-RS resource 1 and 2 21 for CSI-RS resource 3 and 4
	Number of HARQ Processes		4 For FDD 8 for TDD
HARQ ACK/NACK bundling			TBD
Redundancy version coding sequence			{0,2,3,1}

K1 value (PDSCH-to-HARQ-timing-indicator)		2 for FDD TBD for TDD
Symbols for unused Res		OCNG as specified in A.5

## 6.2 Reporting of Channel Quality Indicator (CQI)

*<Editor's note: The requirements were introduced based on current results from companies; these requirements can be revised based on more results from companies.>*

This section includes the requirements for the reporting of channel quality indicator (CQI).

### 6.2.1 1RX requirements

(Void)

### 6.2.2 2RX requirements

This sub-clause includes the requirements for reporting of CQI for UE equipped with 2 receiver antennas.

#### 6.2.2.1 FDD

##### 6.2.2.1.1 CQI reporting definition under AWGN conditions

The reporting accuracy of the channel quality indicator (CQI) under frequency non-selective conditions is determined by the reporting variance and the BLER performance using the transport format indicated by the reported CQI median. The purpose is to verify that the reported CQI values are in accordance with the CQI definition given in TS 38.214 [12]. To account for sensitivity of the input SNR the reporting definition is considered to be verified if the reporting accuracy is met for at least one of two SNR levels separated by an offset of [1] dB.

##### 6.2.2.1.1.1 Minimum requirement for periodic CQI reporting

For the parameters specified in Table 6.2.2.1.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) The reported CQI value according to the reference channel shall be in the range of  $\pm 1$  of the reported median more than [90)% of the time.
- b) If the PDSCH BLER using the transport format indicated by median CQI is less than or equal to 0.1, then the BLER using the transport format indicated by the (median CQI+1) shall be greater than 0.1. If the PDSCH BLER using the transport format indicated by the median CQI is greater than 0.1, then the BLER using transport format indicated by (median CQI-1) shall be less than or equal to 0.1.

**Table 6.2.2.1.1-1: CQI reporting definition test**

Parameter	Unit	Test 1		Test 2	
Bandwidth	MHz	10			
Duplex Mode		FDD			
DL BWP configuration #1	First PRB			0	
	Number of contiguous PRB			52	
	Subcarrier spacing	kHz		15	
SNR	dB	[8]	[9]	[14]	[15]
Propagation channel		AWGN			
Antenna configuration		2x2 with static channel specified in Annex B.1			
Beamforming Model		TBD			
ZP CSI-RS configuration	CSI-RS resource Type			Periodic	
	Number of CSI-RS ports (X)			4	
	CDM Type			FD-CDM2	
	Density ( $\rho$ )			1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )			Row 5,4	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )			9	
	CSI-RS periodicity and offset	slot		5/1	
NZP CSI-RS for CSI acquisition	CSI-RS resource Type			Periodic	
	Number of CSI-RS ports (X)			2	
	CDM Type			FD-CDM2	
	Density ( $\rho$ )			1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )			Row 3,(6,-)	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )			13	
	NZP CSI-RS-timeConfig periodicity and offset	slot		5/1	
CSI-IM configuration	CSI-IM RE pattern			0	
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )			(4, 9)	
	CSI-IM timeConfig periodicity and offset	slot		5/1	
ReportConfigType				Periodic	
CQI-table				Table 2	
reportQuantity				cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements				Not configured	
timeRestrictionForInterferenceMeasurements				Not configured	
cqi-FormatIndicator				Wideband	
pmi-FormatIndicator				Wideband	
Sub-band Size	RB			N/A	
CSI-Report periodicity and offset	slot			5/1	
aperiodicTriggeringOffset				Not configured	
Codebook configuration	Codebook Type			typel-SinglePanel	
	Codebook Mode			1	
	(CodebookConfig-N1,CodebookConfig-N2)			Not configured	
	CodebookSubsetRestriction			[010000]	
	RI Restriction			[N/A]	
Physical channel for CSI report				[PUCCH]	
CQI/RI/PMI delay	ms			8	
Maximum number of HARQ transmission				1	
Measurement channel				[TBD]	

### 6.2.2.1.2 CQI reporting under fading conditions

#### 6.2.2.1.2.1 Minimum requirement for wideband CQI reporting

The purpose of the requirements is to verify that the UE is tracking the channel variations and selecting the largest transport format possible according to the prevailing channel state for the frequency non-selective scheduling.

The reporting accuracy of CQI under frequency non-selective fading conditions is determined by the reporting variance, the relative increase of the throughput obtained when the transport format is indicated by the reported CQI compared to the throughput obtained when a fixed transport format is configured according to the reported median CQI, and a minimum BLER using the transport formats indicated by the reported CQI. To account for sensitivity of the input SNR the sub-band CQI reporting under frequency selective fading conditions is considered to be verified if the reporting accuracy is met for at least one of two SNR levels separated by an offset of [1] dB.

For the parameters specified in Table 6.2.2.1.2.1-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A CQI index not in the set {median CQI -1, median CQI, median CQI +1} shall be reported at least  $\alpha\%$  of the time where  $\alpha\%$  is specified in Table 6.2.2.1.2-2;
- b) The ratio of the throughput obtained when transmitting the transport format indicated by each reported wideband CQI index and that obtained when transmitting a fixed transport format configured according to the wideband CQI median shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.2.1.2-1-2;
- c) When transmitting the transport format indicated by each reported wideband CQI index, the average BLER for the indicated transport formats shall be greater than or equal to [0.02].

**Table 6.2.2.1.2.1-1: Wideband CQI reporting test under frequency non-selective fading conditions**

Parameter	Unit	Test 1	Test 2
Bandwidth	MHz	10	
Duplex Mode		FDD	
DL BWP configuration #1	First PRB	0	
	Number of contiguous PRB	52	
	Subcarrier spacing	kHz	15
SNR	dB	[6] [7] [12] [13]	
Propagation channel		TDLA30-5	
Antenna configuration		2x2	
Correlation configuration		ULA high	
Beamforming Model		TBD	
ZP CSI-RS configuration	CSI-RS resource Type		Periodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9
	CSI-RS periodicity and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic
	Number of CSI-RS ports ( $X$ )		2
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1
CSI-IM configuration	CSI-IM RE pattern		0
	CSI-IM Resource Mapping ( $(k_{CSI-IM}, l_{CSI-IM})$ )		(4, 9)
	CSI-IM timeConfig periodicity and offset	slot	5/1
ReportConfigType			Periodic
CQI-table			Table 2
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
Sub-band Size	RB		N/A
CSI-Report periodicity and offset	slot		5/1
aperiodicTriggeringOffset			Not configured
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured
	CodebookSubsetRestriction		000001
	RI Restriction		[N/A]
Physical channel for CSI report			[PUCCH]
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			1
Measurement channel			TBD

**Table 6.2.2.1.2.1-2: Minimum requirements**

Parameters	Test 1	Test 2
$\alpha [\%]$	[20]	[20]
$\gamma$	[1.05]	[1.05]

#### 6.2.2.1.2.2 Minimum requirement for sub-band CQI reporting

The purpose of the requirements is to verify that the preferred sub-bands can be used for frequency-selective scheduling under the frequency-selective fading conditions.

The accuracy of sub-band channel CQI reporting under the frequency-selective fading conditions is determined by a double-sided percentile of the reported differential CQI offset level 0 per sub-band, and the relative increase of the throughput obtained when transmitting the transport format indicated by the corresponding reported sub-band CQI on a randomly selected sub-band among the sub-bands with the highest reported differential CQI offset level compared to the throughput when transmitting a fixed transport format according to the wideband CQI median on a randomly selected sub-band among all the sub-bands.

For the parameters specified in Table 6.2.2.1.2.2-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A sub-band differential CQI offset level of 0 shall be reported at least  $\alpha\%$  of the time but less than  $\beta\%$  of the time for each sub-band, where  $\alpha$  and  $\beta$  are specified in Table 6.2.2.1.2.2-2;
- b) The ratio of the throughput obtained when transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level and that obtained when transmitting the transport format indicated by the reported wideband CQI median on a randomly selected sub-band among all the sub-bands shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.2.1.2.2-2;
- c) When transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level, the average BLER for the indicated transport format shall be greater than or equal to TBD.

**Table 6.2.2.1.2.2-1: Sub-band CQI reporting test under frequency-selective fading conditions**

Parameter	Unit	Test 1	Test 2
Bandwidth	MHz	10	
Duplex Mode		FDD	
DL BWP configuration #1	First PRB	0	
	Number of contiguous PRB	52	
	Subcarrier spacing	kHz	15
SNR	dB	TBD	TBD
Propagation channel		[Two tap model specified in Annex B.2.4 with $a=1$ , $f_d = 5\text{Hz}$ , and $\tau_d = 0.45\mu\text{s}$ ]	
Antenna configuration		TBD	
Correlation configuration		TBD	
Beamforming Model		TBD	
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports ( $X$ )	4	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	Row 5,4	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	9	
	CSI-RS periodicity and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports ( $X$ )	2	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 3,(6,-)	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	13	
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1
CSI-IM configuration	CSI-IM RE pattern	0	
	CSI-IM Resource Mapping ( $(k_{\text{CSI-IM}}, l_{\text{CSI-IM}})$ )	(4, 9)	
	CSI-IM timeConfig periodicity and offset	slot	5/1
ReportConfigType		Periodic	
CQI-table		Table 2	
reportQuantity		cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements		Not configured	
timeRestrictionForInterferenceMeasurements		Not configured	
cqi-FormatIndicator		Subband	
pmi-FormatIndicator		Wideband	
Sub-band Size	RB	8	
CSI-Report periodicity and offset	slot	5/1	
aperiodicTriggeringOffset		Not configured	
Codebook configuration	Codebook Type	typel-SinglePanel	
	Codebook Mode	1	
	(CodebookConfig-N1,CodebookConfig-N2)	Not configured	
	CodebookSubsetRestriction	000001	
	RI Restriction	[N/A]	
Physical channel for CSI report		TBD	
CQI/RI/PMI delay	ms	8	
Maximum number of HARQ transmission		1	
Measurement channel		TBD	

**Table 6.2.2.1.2.2-2: Minimum requirements**

<b>Parameters</b>	<b>Test 1</b>	<b>Test 2</b>
$\alpha$ [%]	TBD	TBD
$\beta$ [%]	TBD	TBD
$\gamma$	TBD	TBD

## 6.2.2.2 TDD

### 6.2.2.2.1 CQI reporting definition under AWGN conditions

#### 6.2.2.2.1.1 Minimum requirement for periodic CQI reporting

The purpose of the requirements is to verify that the reported CQI values are in accordance with the CQI definition given in TS38.214 [12]. The reporting accuracy of CQI under AWGN condition is determined by the reporting variance and BLER performance using the transport format indicated by the reported CQI median.

For the parameters specified in Table 6.2.2.2.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) The reported CQI value according to the reference channel shall be in the range of  $\pm 1$  of the reported median more than [90]% of the time.
- b) If the PDSCH BLER using the transport format indicated by median CQI is less than or equal to 0.1, then the BLER using the transport format indicated by the (median CQI+1) shall be greater than 0.1. If the PDSCH BLER using the transport format indicated by the median CQI is greater than 0.1, then the BLER using transport format indicated by (median CQI-1) shall be less than or equal to 0.1.

Table 6.2.2.2.1.1-1: CQI reporting definition test

Parameter	Unit	Test 1	Test 2
Bandwidth	MHz	40	
Duplex Mode		TDD	
TDD UL-DL pattern		FR1.30-1	
DL BWP configuration #1	First PRB	0	
	Number of contiguous PRB	106	
	Subcarrier spacing	kHz	30
SNR	dB	[8] [9] [14] [15]	
Propagation channel		AWGN	
Antenna configuration		2x2 with static channel specified in Annex B.1	
Beamforming Model		TBD	
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports (X)	4	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9
	CSI-RS periodicity and offset	slot	10/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports (X)	2	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1
CSI-IM configuration	CSI-IM RE pattern	0	
	CSI-IM Resource Mapping ( $(k_{CSI-IM}, l_{CSI-IM})$ )		(4, 9)
	CSI-IM timeConfig periodicity and offset	slot	10/1
ReportConfigType		Periodic	
CQI-table		Table 2	
reportQuantity		cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements		Not configured	
timeRestrictionForInterferenceMeasurements		Not configured	
cqi-FormatIndicator		Wideband	
pmi-FormatIndicator		Wideband	
Sub-band Size	RB	N/A	
CSI-Report periodicity and offset	slot	10/1	
aperiodicTriggeringOffset		Not configured	
Codebook configuration	Codebook Type	typel-SinglePanel	
	Codebook Mode	1	
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured
	CodebookSubsetRestriction		[010000]
	RI Restriction		[N/A]
Physical channel for CSI report		[PUCCH]	
CQI/RI/PMI delay	ms	[9.5]	
Maximum number of HARQ transmission		1	
Measurement channel		TBD	

### 6.2.2.2.2 Wideband CQI reporting under fading conditions

#### 6.2.2.2.2.1 Minimum requirement for wideband CQI reporting

The purpose of the requirements is to verify that the UE is tracking the channel variations and selecting the largest transport format possible according to the prevailing channel state for the frequency non-selective scheduling.

The reporting accuracy of CQI under frequency non-selective fading conditions is determined by the reporting variance, the relative increase of the throughput obtained when the transport format is indicated by the reported CQI compared to the throughput obtained when a fixed transport format is configured according to the reported median CQI, and a minimum BLER using the transport formats indicated by the reported CQI.

For the parameters specified in Table 6.2.2.2.2.1-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A CQI index not in the set {median CQI -1, median CQI, median CQI +1} shall be reported at least  $\alpha\%$  of the time where  $\alpha\%$  is specified in Table 6.2.2.2.1-2;
- b) The ratio of the throughput obtained when transmitting the transport format indicated by each reported wideband CQI index and that obtained when transmitting a fixed transport format configured according to the wideband CQI median shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.2.2.1-2;
- c) When transmitting the transport format indicated by each reported wideband CQI index, the average BLER for the indicated transport formats shall be greater than or equal to TBD.

**Table 6.2.2.2.1-1: Wideband CQI reporting test under frequency non-selective fading conditions**

Parameter		Unit	Test 1		Test 2	
Bandwidth		MHz	40			
Duplex Mode			TDD			
TDD UL-DL pattern			FR1.30-1			
DL BWP configuration #1	First PRB			0		
	Number of contiguous PRB			106		
	Subcarrier spacing	kHz		30		
SNR		dB	TBD	TBD	TBD	TBD
Propagation channel			[TDLA30-5]			
Antenna configuration			2x2			
Correlation configuration			ULA high			
Beamforming Model			TBD			
ZP CSI-RS configuration	CSI-RS resource Type		Periodic			
	Number of CSI-RS ports ( $X$ )		4			
	CDM Type		FD-CDM2			
	Density ( $\rho$ )		1			
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4			
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9			
	CSI-RS periodicity and offset	slot	10/1			
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic			
	Number of CSI-RS ports ( $X$ )		2			
	CDM Type		FD-CDM2			
	Density ( $\rho$ )		1			
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)			
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13			
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1			
CSI-IM configuration	CSI-IM RE pattern		0			
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4, 9)			
	CSI-IM timeConfig periodicity and offset	slot	10/1			
ReportConfigType			Periodic			
CQI-table			Table 2			
reportQuantity			cri-RI-PMI-CQI			
timeRestrictionForChannelMeasurements			Not configured			
timeRestrictionForInterferenceMeasurements			Not configured			
cqi-FormatIndicator			Wideband			
pmi-FormatIndicator			Wideband			
Sub-band Size		RB	N/A			
CSI-Report periodicity and offset		slot	10/1			
aperiodicTriggeringOffset			Not configured			
Codebook configuration	Codebook Type		typel-SinglePanel			
	Codebook Mode		1			
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured			
	CodebookSubsetRestriction		000001			
	RI Restriction		[N/A]			
Physical channel for CSI report			[PUCCH]			
CQI/RI/PMI delay		ms	[9.5]			
Maximum number of HARQ transmission			1			
Measurement channel			TBD			

**Table 6.2.2.2.1-2: Minimum requirements**

Parameters	Test 1	Test 2
$\alpha [\%]$	TBD	TBD
$\gamma$	TBD	TBD

#### 6.2.2.2.2.2 Minimum requirement for sub-band CQI reporting

The purpose of the requirements is to verify that the preferred sub-bands can be used for frequency-selective scheduling under the frequency-selective fading conditions.

The accuracy of sub-band channel CQI reporting under the frequency-selective fading conditions is determined by a double-sided percentile of the reported differential CQI offset level 0 per sub-band, and the relative increase of the throughput obtained when transmitting the transport format indicated by the corresponding reported sub-band CQI on a randomly selected sub-band among the sub-bands with the highest reported differential CQI offset level compared to the throughput when transmitting a fixed transport format according to the wideband CQI median on a randomly selected sub-band among all the sub-bands.

For the parameters specified in Table 6.2.2.2.2.2-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A sub-band differential CQI offset level of 0 shall be reported at least  $\alpha\%$  of the time but less than  $\beta\%$  of the time for each sub-band, where  $\alpha$  and  $\beta$  are specified in Table 6.2.2.2.2-2;
- b) The ratio of the throughput obtained when transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level and that obtained when transmitting the transport format indicated by the reported wideband CQI median on a randomly selected sub-band among all the sub-bands shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.2.2.2-2;
- c) When transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level, the average BLER for the indicated transport format shall be greater than or equal to TBD.

**Table 6.2.2.2.2.2-1: Sub-band CQI reporting test under frequency-selective fading conditions**

Parameter	Unit	Test 1		Test 2	
Bandwidth	MHz	40			
Duplex Mode		TDD			
TDD UL-DL pattern		FR1.30-1			
DL BWP configuration #1		First PRB		0	
		Number of contiguous PRB		106	
		Subcarrier spacing	kHz	30	
SNR	dB	TBD	TBD	TBD	TBD
Propagation channel		[Two tap model specified in Annex B.2.4 with $a=1$ , $f_d = 5\text{Hz}$ , and $\tau_d = 0.1125\mu\text{s}$ ]			
Antenna configuration		TBD			
Correlation configuration		TBD			
Beamforming Model		TBD			
ZP CSI-RS configuration		CSI-RS resource Type		Periodic	
		Number of CSI-RS ports ( $X$ )		4	
		CDM Type		FD-CDM2	
		Density ( $\rho$ )		1	
		First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4	
		First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9	
		CSI-RS periodicity and offset	slot	10/1	
NZP CSI-RS for CSI acquisition		CSI-RS resource Type		Periodic	
		Number of CSI-RS ports ( $X$ )		2	
		CDM Type		FD-CDM2	
		Density ( $\rho$ )		1	
		First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)	
		First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13	
		NZP CSI-RS-timeConfig periodicity and offset	slot	10/1	
CSI-IM configuration		CSI-IM RE pattern		0	
		CSI-IM Resource Mapping ( $(k_{\text{CSI-IM}}, l_{\text{CSI-IM}})$ )		(4, 9)	
		CSI-IM timeConfig periodicity and offset	slot	10/1	
ReportConfigType				Periodic	
CQI-table				Table 2	
reportQuantity				cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements				Not configured	
timeRestrictionForInterferenceMeasurements				Not configured	
cqi-FormatIndicator				Subband	
pmi-FormatIndicator				Wideband	
Sub-band Size	RB			16	
CSI-Report periodicity and offset	slot			10/1	
aperiodicTriggeringOffset				Not configured	
Codebook configuration		Codebook Type		typel-SinglePanel	
		Codebook Mode		1	
		(CodebookConfig-N1,CodebookConfig-N2)		Not configured	
		CodebookSubsetRestriction		000001	
		RI Restriction		[N/A]	
Physical channel for CSI report				TBD	
CQI/RI/PMI delay	ms			[9.5]	
Maximum number of HARQ transmission				1	
Measurement channel				TBD	

**Table 6.2.2.2.2-2: Minimum requirements**

<b>Parameters</b>	<b>Test 1</b>	<b>Test 2</b>
$\alpha$ [%]	TBD	TBD
$\beta$ [%]	TBD	TBD
$\gamma$	TBD	TBD

## 6.2.3 4RX requirements

This sub-clause includes the requirements for reporting of CQI for UE equipped with 4 receiver antennas.

### 6.2.3.1 FDD

#### 6.2.3.1.1 CQI reporting definition under AWGN conditions

The purpose of the requirements is to verify that the reported CQI values are in accordance with the CQI definition given in TS38.214 [12]. The reporting accuracy of CQI under AWGN condition is determined by the reporting variance and BLER performance using the transport format indicated by the reported CQI median.

##### 6.2.3.1.1.1 Minimum requirement for period CQI reporting

For the parameters specified in Table 6.2.3.1.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) The reported CQI value according to the reference channel shall be in the range of  $\pm 1$  of the reported median more than [90]% of the time.
- b) If the PDSCH BLER using the transport format indicated by median CQI is less than or equal to 0.1, then the BLER using the transport format indicated by the (median CQI+1) shall be greater than 0.1. If the PDSCH BLER using the transport format indicated by the median CQI is greater than 0.1, then the BLER using transport format indicated by (median CQI-1) shall be less than or equal to 0.1.

**Table 6.2.2.1.1-1: CQI reporting definition test**

Parameter	Unit	Test 1		Test 2	
Bandwidth	MHz	10			
Duplex Mode		FDD			
DL BWP configuration #1	First PRB			0	
	Number of contiguous PRB			52	
	Subcarrier spacing	kHz		15	
SNR	dB	[5]	[6]	[11]	[12]
Propagation channel		AWGN			
Antenna configuration		2x4 with static channel specified in Annex B.1			
Beamforming Model		TBD			
ZP CSI-RS configuration	CSI-RS resource Type			Periodic	
	Number of CSI-RS ports (X)			4	
	CDM Type			FD-CDM2	
	Density ( $\rho$ )			1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )			Row 5,4	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )			9	
	CSI-RS periodicity and offset	slot		5/1	
NZP CSI-RS for CSI acquisition	CSI-RS resource Type			Periodic	
	Number of CSI-RS ports (X)			2	
	CDM Type			FD-CDM2	
	Density ( $\rho$ )			1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )			Row 3,(6,-)	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )			13	
CSI-IM configuration	NZP CSI-RS-timeConfig periodicity and offset	slot		5/1	
	CSI-IM RE pattern			0	
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )			(4, 9)	
CSI-IM timeConfig periodicity and offset	CSI-IM timeConfig periodicity and offset	slot		5/1	
ReportConfigType				Periodic	
CQI-table				Table 2	
reportQuantity				cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements				Not configured	
timeRestrictionForInterferenceMeasurements				Not configured	
cqi-FormatIndicator				Wideband	
pmi-FormatIndicator				Wideband	
Sub-band Size	RB			N/A	
CSI-Report periodicity and offset	slot			5/1	
aperiodicTriggeringOffset				Not configured	
Codebook configuration	Codebook Type			typel-SinglePanel	
	Codebook Mode			1	
	(CodebookConfig-N1,CodebookConfig-N2)			Not configured	
	CodebookSubsetRestriction			[010000]	
	RI Restriction			[N/A]	
Physical channel for CSI report				[PUCCH]	
CQI/RI/PMI delay	ms			8	
Maximum number of HARQ transmission				1	
Measurement channel				TBD	

### 6.2.3.1.2 Wideband CQI reporting under fading conditions

#### 6.2.3.1.2.1 Minimum requirement for wideband CQI reporting

The purpose of the requirements is to verify that the UE is tracking the channel variations and selecting the largest transport format possible according to the prevailing channel state for the frequency non-selective scheduling.

The reporting accuracy of CQI under frequency non-selective fading conditions is determined by the reporting variance, the relative increase of the throughput obtained when the transport format is indicated by the reported CQI compared to the throughput obtained when a fixed transport format is configured according to the reported median CQI, and a minimum BLER using the transport formats indicated by the reported CQI.

For the parameters specified in Table 6.2.3.1.2.1-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A CQI index not in the set {median CQI -1, median CQI, median CQI +1} shall be reported at least  $\alpha\%$  of the time where  $\alpha\%$  is specified in Table 6.2.3.1.2.1-2;
- b) The ratio of the throughput obtained when transmitting the transport format indicated by each reported wideband CQI index and that obtained when transmitting a fixed transport format configured according to the wideband CQI median shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.3.1.2.1-2;
- c) When transmitting the transport format indicated by each reported wideband CQI index, the average BLER for the indicated transport formats shall be greater than or equal to TBD.

**Table 6.2.3.1.2.1-1: Wideband CQI reporting test under frequency non-selective fading conditions**

Parameter	Unit	Test 1	Test 2
Bandwidth	MHz	10	
Duplex Mode		FDD	
DL BWP configuration #1	First PRB	0	
	Number of contiguous PRB	52	
	Subcarrier spacing	kHz	15
SNR	dB	TBD	TBD
Propagation channel		TDLA30-5	
Antenna configuration		2x4	
Correlation configuration		XP High	
Beamforming Model		TBD	
ZP CSI-RS configuration	CSI-RS resource Type		Periodic
	Number of CSI-RS ports (X)		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9
	CSI-RS periodicity and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic
	Number of CSI-RS ports (X)		2
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1
CSI-IM configuration	CSI-IM RE pattern		0
	CSI-IM Resource Mapping ( $(k_{CSI-IM}, l_{CSI-IM})$ )		(4, 9)
	CSI-IM timeConfig periodicity and offset	slot	5/1
ReportConfigType			Periodic
CQI-table			Table 2
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
Sub-band Size	RB		N/A
CSI-Report periodicity and offset	slot		5/1
aperiodicTriggeringOffset			Not configured
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured
	CodebookSubsetRestriction		000001
	RI Restriction		[N/A]
Physical channel for CSI report			[PUCCH]
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			1
Measurement channel			TBD

**Table 6.2.3.1.2.1-2: Minimum requirements**

Parameters	Test 1	Test 2
$\alpha [\%]$	TBD	TBD
$\gamma$	TBD	TBD

### 6.2.3.1.2.2 Minimum requirement for sub-band CQI reporting

The purpose of the requirements is to verify that the preferred sub-bands can be used for frequency-selective scheduling under the frequency-selective fading conditions.

The accuracy of sub-band channel CQI reporting under the frequency-selective fading conditions is determined by a double-sided percentile of the reported differential CQI offset level 0 per sub-band, and the relative increase of the throughput obtained when transmitting the transport format indicated by the corresponding reported sub-band CQI on a randomly selected sub-band among the sub-bands with the highest reported differential CQI offset level compared to the throughput when transmitting a fixed transport format according to the wideband CQI median on a randomly selected sub-band among all the sub-bands.

For the parameters specified in Table 6.2.3.1.2.2-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A sub-band differential CQI offset level of 0 shall be reported at least  $\alpha\%$  of the time but less than  $\beta\%$  of the time for each sub-band, where  $\alpha$  and  $\beta$  are specified in Table 6.2.3.1.2.2-2;
- b) The ratio of the throughput obtained when transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level and that obtained when transmitting the transport format indicated by the reported wideband CQI median on a randomly selected sub-band among all the sub-bands shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.3.1.2.2-2;
- c) When transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level, the average BLER for the indicated transport format shall be greater than or equal to TBD.

**Table 6.2.3.1.2.2-1: Sub-band CQI reporting test under frequency-selective fading conditions**

Parameter	Unit	Test 1		Test 2				
Bandwidth	MHz	10						
Duplex Mode		FDD						
DL BWP configuration #1	First PRB	0						
	Number of contiguous PRB	52						
	Subcarrier spacing	kHz	15					
SNR	dB	TBD	TBD	TBD	TBD			
Propagation channel		[Two tap model specified in Annex B.2.4 with $a=1$ , $f_d = 5\text{Hz}$ , and $\tau_d = 0.45\mu\text{s}$ ]						
Antenna configuration		TBD						
Correlation configuration		TBD						
Beamforming Model		TBD						
ZP CSI-RS configuration	CSI-RS resource Type	Periodic						
	Number of CSI-RS ports ( $X$ )	4						
	CDM Type	FD-CDM2						
	Density ( $p$ )	1						
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	Row 5,4						
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	9						
	CSI-RS periodicity and offset	slot	5/1					
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic						
	Number of CSI-RS ports ( $X$ )	2						
	CDM Type	FD-CDM2						
	Density ( $p$ )	1						
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 3,(6,-)						
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	13						
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1					
CSI-IM configuration	CSI-IM RE pattern	0						
	CSI-IM Resource Mapping ( $(k_{\text{CSI-IM}}, l_{\text{CSI-IM}})$ )	(4, 9)						
	CSI-IM timeConfig periodicity and offset	slot	5/1					
ReportConfigType		Periodic						
CQI-table		Table 2						
reportQuantity		cri-RI-PMI-CQI						
timeRestrictionForChannelMeasurements		Not configured						
timeRestrictionForInterferenceMeasurements		Not configured						
cqi-FormatIndicator		Subband						
pmi-FormatIndicator		Wideband						
Sub-band Size	RB	8						
CSI-Report periodicity and offset	slot	5/1						
aperiodicTriggeringOffset		Not configured						
Codebook configuration	Codebook Type	typel-SinglePanel						
	Codebook Mode	1						
	(CodebookConfig-N1,CodebookConfig-N2)	Not configured						
	CodebookSubsetRestriction	000001						
	RI Restriction	[N/A]						
Physical channel for CSI report		TBD						
CQI/RI/PMI delay	ms	8						
Maximum number of HARQ transmission		1						
Measurement channel		TBD						

**Table 6.2.3.1.2.2-2: Minimum requirements**

<b>Parameters</b>	<b>Test 1</b>	<b>Test 2</b>
$\alpha$ [%]	TBD	TBD
$\beta$ [%]	TBD	TBD
$\gamma$	TBD	TBD

### 6.2.3.2 TDD

#### 6.2.3.2.1 CQI reporting definition under AWGN

##### 6.2.3.2.1.1 Minimum requirement for CQI periodic reporting

The purpose of the requirements is to verify that the reported CQI values are in accordance with the CQI definition given in TS38.214 [12]. The reporting accuracy of CQI under AWGN condition is determined by the reporting variance and BLER performance using the transport format indicated by the reported CQI median.

For the parameters specified in Table 6.2.3.2.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) The reported CQI value according to the reference channel shall be in the range of  $\pm 1$  of the reported median more than [90]% of the time.
- b) If the PDSCH BLER using the transport format indicated by median CQI is less than or equal to 0.1, then the BLER using the transport format indicated by the (median CQI+1) shall be greater than 0.1. If the PDSCH BLER using the transport format indicated by the median CQI is greater than 0.1, then the BLER using transport format indicated by (median CQI-1) shall be less than or equal to 0.1.

Table 6.2.3.2.1.1-1: CQI reporting definition test

Parameter	Unit	Test 1	Test 2
Bandwidth	MHz	40	
Duplex Mode		TDD	
TDD UL-DL pattern		FR1.30-1	
DL BWP configuration #1	First PRB	0	
	Number of contiguous PRB	106	
	Subcarrier spacing	kHz	30
SNR	dB	[5] [6] [11] [12]	
Propagation channel		AWGN	
Antenna configuration		2x4 with static channel specified in Annex B.1	
Beamforming Model		TBD	
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports (X)	4	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9
	CSI-RS periodicity and offset	slot	10/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	
	Number of CSI-RS ports (X)	2	
	CDM Type	FD-CDM2	
	Density ( $\rho$ )	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1
CSI-IM configuration	CSI-IM RE pattern	0	
	CSI-IM Resource Mapping ( $(k_{CSI-IM}, l_{CSI-IM})$ )		(4, 9)
	CSI-IM timeConfig periodicity and offset	slot	10/1
ReportConfigType		Periodic	
CQI-table		Table 2	
reportQuantity		cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements		Not configured	
timeRestrictionForInterferenceMeasurements		Not configured	
cqi-FormatIndicator		Wideband	
pmi-FormatIndicator		Wideband	
Sub-band Size	RB	N/A	
CSI-Report periodicity and offset	slot	10/1	
aperiodicTriggeringOffset		Not configured	
Codebook configuration	Codebook Type	typel-SinglePanel	
	Codebook Mode	1	
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured
	CodebookSubsetRestriction		[010000]
	RI Restriction		[N/A]
Physical channel for CSI report		[PUCCH]	
CQI/RI/PMI delay	ms	[9.5]	
Maximum number of HARQ transmission		1	
Measurement channel		TBD	

### 6.2.3.2.2 Wideband CQI reporting under fading conditions

#### 6.2.3.2.2.1 Minimum requirement for wideband CQI reporting

The purpose of the requirements is to verify that the UE is tracking the channel variations and selecting the largest transport format possible according to the prevailing channel state for the frequency non-selective scheduling.

The reporting accuracy of CQI under frequency non-selective fading conditions is determined by the reporting variance, the relative increase of the throughput obtained when the transport format is indicated by the reported CQI compared to the throughput obtained when a fixed transport format is configured according to the reported median CQI, and a minimum BLER using the transport formats indicated by the reported CQI.

For the parameters specified in Table 6.2.3.2.2.1-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A CQI index not in the set {median CQI -1, median CQI, median CQI +1} shall be reported at least  $\alpha\%$  of the time where  $\alpha\%$  is specified in Table 6.2.3.2.2.1-2;
- b) The ratio of the throughput obtained when transmitting the transport format indicated by each reported wideband CQI index and that obtained when transmitting a fixed transport format configured according to the wideband CQI median shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.3.2.2.1-2;
- c) When transmitting the transport format indicated by each reported wideband CQI index, the average BLER for the indicated transport formats shall be greater than or equal to TBD.

**Table 6.2.3.2.2.1-1: Wideband CQI reporting test under frequency non-selective fading conditions**

Parameter	Unit	Test 1		Test 2	
Bandwidth	MHz	40			
Duplex Mode		TDD			
TDD UL-DL pattern		FR1.30-1			
DL BWP configuration #1	First PRB			0	
	Number of contiguous PRB			106	
	Subcarrier spacing	kHz		30	
SNR	dB	TBD	TBD	TBD	TBD
Propagation channel		[TDLA30-5]			
Antenna configuration		2x4			
Correlation configuration		XP High			
Beamforming Model		TBD			
ZP CSI-RS configuration	CSI-RS resource Type		Periodic		
	Number of CSI-RS ports ( $X$ )		4		
	CDM Type		FD-CDM2		
	Density ( $\rho$ )		1		
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4		
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9		
	CSI-RS periodicity and offset	slot	10/1		
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic		
	Number of CSI-RS ports ( $X$ )		2		
	CDM Type		FD-CDM2		
	Density ( $\rho$ )		1		
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)		
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13		
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1		
CSI-IM configuration	CSI-IM RE pattern		0		
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4, 9)		
	CSI-IM timeConfig periodicity and offset	slot	10/1		
ReportConfigType		Periodic			
CQI-table		Table 2			
reportQuantity		cri-RI-PMI-CQI			
timeRestrictionForChannelMeasurements		Not configured			
timeRestrictionForInterferenceMeasurements		Not configured			
cqi-FormatIndicator		Wideband			
pmi-FormatIndicator		Wideband			
Sub-band Size	RB	N/A			
CSI-Report periodicity and offset	slot	10/1			
aperiodicTriggeringOffset		Not configured			
Codebook configuration	Codebook Type		typel-SinglePanel		
	Codebook Mode		1		
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured		
	CodebookSubsetRestriction		000001		
	RI Restriction		[N/A]		
Physical channel for CSI report		[PUCCH]			
CQI/RI/PMI delay	ms	[9.5]			
Maximum number of HARQ transmission		1			
Measurement channel		TBD			

**Table 6.2.3.2.2.1-2: Minimum requirements**

Parameters	Test 1	Test 2
$\alpha [\%]$	TBD	TBD
$\gamma$	TBD	TBD

#### 6.2.3.2.2.2 Minimum requirement for sub-band CQI reporting

The purpose of the requirements is to verify that the preferred sub-bands can be used for frequency-selective scheduling under the frequency-selective fading conditions.

The accuracy of sub-band channel CQI reporting under the frequency-selective fading conditions is determined by a double-sided percentile of the reported differential CQI offset level 0 per sub-band, and the relative increase of the throughput obtained when transmitting the transport format indicated by the corresponding reported sub-band CQI on a randomly selected sub-band among the sub-bands with the highest reported differential CQI offset level compared to the throughput when transmitting a fixed transport format according to the wideband CQI median on a randomly selected sub-band among all the sub-bands.

For the parameters specified in Table 6.2.3.2.2.2-1 and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified by the following:

- a) A sub-band differential CQI offset level of 0 shall be reported at least  $\alpha\%$  of the time but less than  $\beta\%$  of the time for each sub-band, where  $\alpha$  and  $\beta$  are specified in Table 6.2.3.2.2.2-2;
- b) The ratio of the throughput obtained when transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level and that obtained when transmitting the transport format indicated by the reported wideband CQI median on a randomly selected sub-band among all the sub-bands shall be  $\geq \gamma$ , where  $\gamma$  is specified in Table 6.2.3.2.2.2-2;
- c) When transmitting the corresponding transport format on a randomly selected sub-band among the sub-bands with the highest differential CQI offset level, the average BLER for the indicated transport format shall be greater than or equal to TBD.

**Table 6.2.3.2.2.2-1: Sub-band CQI reporting test under frequency-selective fading conditions**

Parameter	Unit	Test 1		Test 2	
Bandwidth	MHz	40			
Duplex Mode		TDD			
TDD UL-DL pattern		FR1.30-1			
DL BWP configuration #1		First PRB		0	
		Number of contiguous PRB		106	
		Subcarrier spacing	kHz	30	
SNR	dB	TBD	TBD	TBD	TBD
Propagation channel		[Two tap model specified in Annex B.2.4 with $a=1$ , $f_D = 5\text{Hz}$ , and $\tau_d = 0.1125\mu\text{s}$ ]			
Antenna configuration		TBD			
Correlation configuration		TBD			
Beamforming Model		[TBD]			
ZP CSI-RS configuration		CSI-RS resource Type		Periodic	
		Number of CSI-RS ports ( $X$ )		4	
		CDM Type		FD-CDM2	
		Density ( $\rho$ )		1	
		First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		Row 5,4	
		First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		9	
		CSI-RS periodicity and offset	slot	10/1	
NZP CSI-RS for CSI acquisition		CSI-RS resource Type		Periodic	
		Number of CSI-RS ports ( $X$ )		2	
		CDM Type		FD-CDM2	
		Density ( $\rho$ )		1	
		First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3,(6,-)	
		First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		13	
		NZP CSI-RS-timeConfig periodicity and offset	slot	10/1	
CSI-IM configuration		CSI-IM RE pattern		0	
		CSI-IM Resource Mapping ( $(k_{\text{CSI-IM}}, l_{\text{CSI-IM}})$ )		(4, 9)	
		CSI-IM timeConfig periodicity and offset	slot	10/1	
ReportConfigType				Periodic	
CQI-table				Table 2	
reportQuantity				cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements				Not configured	
timeRestrictionForInterferenceMeasurements				Not configured	
cqi-FormatIndicator				Subband	
pmi-FormatIndicator				Wideband	
Sub-band Size	RB			16	
CSI-Report periodicity and offset	slot			10/1	
aperiodicTriggeringOffset				Not configured	
Codebook configuration		Codebook Type		typel-SinglePanel	
		Codebook Mode		1	
		(CodebookConfig-N1,CodebookConfig-N2)		Not configured	
		CodebookSubsetRestriction		000001	
		RI Restriction		[N/A]	
Physical channel for CSI report				TBD	
CQI/RI/PMI delay	ms			[9.5]	
Maximum number of HARQ transmission				1	
Measurement channel				TBD	

**Table 6.2.2.1.2.2-2: Minimum requirements**

Parameters	Test 1	Test 2
$\alpha$ [%]	TBD	TBD
$\beta$ [%]	TBD	TBD
$\gamma$	TBD	TBD

## 6.3 Reporting of Precoding Matrix Indicator (PMI)

*<Editor's note: The requirements were introduced based on current results from companies; these requirements can be revised based on more results from companies.>*

The minimum performance requirements of PMI reporting are defined based on the precoding gain, expressed as the relative increase in throughput when the transmitter is configured according to the UE reports compared to the case when the transmitter is using random precoding, respectively. When the transmitter uses random precoding, for each PDSCH allocation a precoder is randomly generated and applied to the PDSCH. A fixed transport format (FRC) is configured for all requirements.

The requirements for transmission mode 1 with higher layer parameter *codebookType* set to ‘typeI-SinglePanel’ are specified in terms of the ratio:

$$\gamma = \frac{t_{ue, follow1, follow2}}{t_{rnd1, rnd2}}$$

In the definition of  $\gamma$ , for 4TX and 8TX PMI requirements,  $t_{follow1, follow2}$  is [90] % of the maximum throughput obtained at  $SNR_{follow1, follow2}$  using the precoders configured according to the UE reports, and  $t_{rnd1, rnd2}$  is the throughput measured at  $SNR_{follow1, follow2}$  with random precoding.

### 6.3.1 1RX requirements

(Void)

### 6.3.2 2RX requirements

#### 6.3.2.1 FDD

##### 6.3.2.1.1 Single PMI with 4TX TypeI-SinglePanel Codebook

For the parameters specified in Table 6.3.2.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.3.2.1.1-2.

**Table 6.3.2.1.1-1: Test parameters (single layer)**

Parameter		Unit	Test 1
Bandwidth		MHz	10
Duplex Mode			FDD
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB		52
	Subcarrier spacing	kHz	15
Propagation channel			TDLA30-5
Antenna configuration			High XP 4 x 2 (N1,N2) = (2,1)
Beamforming Model			TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)
	CSI-RS interval and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 4, (0,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)
CSI-IM configuration	CSI-IM RE pattern		Patten 0
	CSI-IM Resource Mapping ( $K_{CSI-IM}, L_{CSI-IM}$ )		(4,9)
	CSI-IM timeConfig interval and offset	slot	5/1
ReportConfigType			Aperiodic
CQI-table			Table 1
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
CSI-Report interval and offset		slot	5/1
aperiodicTriggeringOffset			0
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		(2,1)

	CodebookSubset Restriction		11111111
	RI Restriction		00000001
Physical channel for CSI report			PUSCH
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			4
Measurement channel			MCS 13, TBD for reference channel
Note 1:	For random precoder selection, the precoder shall be updated in each slot (1 ms granularity).		
Note 2:	If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-4)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+4)].		
Note 3:	Randomization of the principle beam direction shall be used as specified in TBD.		

**Table 6.3.2.1.1-2: Minimum requirement**

Parameter	Test 1
$\gamma$	[1.3]

### 6.3.2.1.2 Single PMI with 8TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.2.1.2-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.3.2.1.2-2.

**Table 6.3.2.1.2-1: Test parameters (dual-layer)**

Parameter		Unit	Test 1
Bandwidth		MHz	10
Duplex Mode			FDD
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB		52
	Subcarrier spacing	kHz	15
Propagation channel			TDLA30-5
Antenna configuration			High XP 8 x 2 (N1,N2) = (4,1)
Beamforming Model			TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)
	CSI-RS interval and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		8
	CDM Type		CDM4 (FD2, TD2)
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 8, (4,6)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(5,-)
CSI-IM configuration	CSI-IM RE pattern		Patten 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4,9)
	CSI-IM timeConfig interval and offset	slot	5/1
ReportConfigType			Aperiodic
CQI-table			Table 1
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
CSI-Report interval and offset		slot	5/1
aperiodicTriggeringOffset			0
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		(4,1)

	CodebookSubset Restriction		0x FFFF
	RI Restriction		00000010
Physical channel for CSI report			PUSCH
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			4
Measurement channel			MCS13, TBD for reference channel
Note 1:	For random precoder selection, the precoder shall be updated in each slot (1 ms granularity).		
Note 2:	If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-4)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+4)].		
Note 3:	Randomization of the principle beam direction shall be used as specified in TBD.		

**Table 6.3.2.1.2-2: Minimum requirement**

Parameter	Test 1
$\gamma$	TBD

### 6.3.2.2 TDD

#### 6.3.2.2.1 Single PMI with 4TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.2.2.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.3.2.2.1-2.

**Table 6.3.2.2.1-1: Test parameters (single layer)**

Parameter	Unit	Test 1
Bandwidth	MHz	40
Duplex Mode		TDD
TDD DL-UL configuration		FR1.30-1 as specified in Annex A
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	kHz
Propagation channel		TDLA30-5
Antenna configuration		High XP 4 x 2 (N1,N2) = (2,1)
Beamforming Model		TBD
ZP CSI-RS configuration	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)
	CSI-RS interval and offset	slot
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 4, (0,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(13,-)
	CSI-RS interval and offset	slot
CSI-IM configuration	CSI-IM RE pattern	Patten 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )	(4,9)
	CSI-IM timeConfig interval and offset	slot
ReportConfigType		Aperiodic
CQI-table		Table 1
reportQuantity		cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		Not configured
timeRestrictionForInterferenceMeasurements		Not configured
cqi-FormatIndicator		Wideband
pmi-FormatIndicator		Wideband
CSI-Report interval and offset	slot	10/1
aperiodicTriggeringOffset		0
	Codebook Type	typel-SinglePanel
	Codebook Mode	1

Codebook configuration	(CodebookConfig-N1,CodebookConfig-N2)		(2,1)
	CodebookSubset Restriction		11111111
	RI Restriction		00000001
Physical channel for CSI report		PUSCH	
CQI/RI/PMI delay	ms	9.5	
Maximum number of HARQ transmission		4	
Measurement channel		MCS13, TBD for reference channel	
Note 1: For random precoder selection, the precoder shall be updated in each slot (0.5 ms granularity). Note 2: If the UE reports in an available uplink reporting instance at slot #n based on PMI estimation at a downlink slot not later than slot#[(n-6)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+6)]. Note 3: Randomization of the principle beam direction shall be used as specified in TBD.			

**Table 6.3.2.2.1-2: Minimum requirement**

Parameter	Test 1
$\gamma$	[1.3]

### 6.3.2.2.2 Single PMI with 8TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.2.2.2-1, and using the downlink physical channels specified in Annex TBD, the minimum requirements are specified in Table 6.3.2.2.2-2.

**Table 6.3.2.2-1: Test parameters (dual-layer)**

Parameter	Unit	Test 1
Bandwidth	MHz	40
Duplex Mode		TDD
TDD DL-UL configurations		FR1.30-1 as specified in Annex A
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	kHz
Propagation channel		TDLA30-5
Antenna configuration		High XP 8 x 2 (N1,N2) = (4,1)
Beamforming Model		TBD
ZP CSI-RS configuration	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)
	CSI-RS interval and offset	slot
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	8
	CDM Type	CDM4 (FD2, TD2)
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 8, (4,6)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(5,-)
	CSI-RS interval and offset	slot
CSI-IM configuration	CSI-IM RE pattern	Patten 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )	(4,9)
	CSI-IM timeConfig interval and offset	slot
ReportConfigType		Aperiodic
CQI-table		Table 1
reportQuantity		cri-RI-PMI-CQI
timeRestrictionForIChannelMeasurements		Not configured
timeRestrictionForInterferenceMeasurements		Not configured
cqi-FormatIndicator		Wideband
pmi-FormatIndicator		Wideband
CSI-Report interval and offset	slot	10/1
aperiodicTriggeringOffset		0
	Codebook Type	typel-SinglePanel
	Codebook Mode	1

Codebook configuration	(CodebookConfig-N1,CodebookConfig-N2)		(4,1)
	CodebookSubset Restriction		0x FFFF
	RI Restriction		00000010
Physical channel for CSI report		PUSCH	
CQI/RI/PMI delay	ms	9.5	
Maximum number of HARQ transmission		4	
Measurement channel		MCS13, TBD for reference channel	
Note 1: For random precoder selection, the precoder shall be updated in each slot (0.5 ms granularity). Note 2: If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-6)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+6)]. Note 3: Randomization of the principle beam direction shall be used as specified in TBD.			

**Table 6.3.2.2-2: Minimum requirement**

Parameter	Test 1
$\gamma$	TBD

### 6.3.3 4RX requirements

#### 6.3.3.1 FDD

##### 6.3.3.1.1 Single PMI with 4TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.3.1.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.3.3.1.1-2.

**Table 6.3.3.1.1-1: Test parameters (single layer)**

Parameter		Unit	Test 1
Bandwidth		MHz	10
Duplex Mode			FDD
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB		52
	Subcarrier spacing	kHz	15
Propagation channel			TDLA30-5
Antenna configuration			High XP 4 x 4 (N1,N2) = (2,1)
Beamforming Model			TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)
	CSI-RS interval and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 4, (0,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)
CSI-IM configuration	CSI-IM RE pattern		Patten 0
	CSI-IM Resource Mapping ( $K_{CSI-IM}, L_{CSI-IM}$ )		(4,9)
	CSI-IM timeConfig interval and offset	slot	5/1
ReportConfigType			Aperiodic
CQI-table			Table 1
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
CSI-Report interval and offset		slot	5/1
aperiodicTriggeringOffset			0
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		(2,1)

	CodebookSubset Restriction		11111111
	RI Restriction		00000001
Physical channel for CSI report			PUSCH
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			4
Measurement channel			MCS13, TBD for reference channel
Note 1:	For random precoder selection, the precoder shall be updated in each slot (1 ms granularity).		
Note 2:	If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-4)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+4)].		
Note 3:	Randomization of the principle beam direction shall be used as specified in TBD.		

**Table 6.3.3.1.1-2: Minimum requirement**

Parameter	Test 1
$\gamma$	[1.3]

### 6.3.3.1.2 Single PMI with 8TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.3.1.2-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.3.3.1.2-2.

**Table 6.3.3.1.2-1: Test parameters (dual-layer)**

Parameter		Unit	Test 1
Bandwidth		MHz	10
Duplex Mode			FDD
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB		52
	Subcarrier spacing	kHz	15
Propagation channel			TDLA30-5
Antenna configuration			High XP 8 x 4 (N1,N2) = (4,1)
Beamforming Model			TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)
	CSI-RS interval and offset	slot	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		8
	CDM Type		CDM4 (FD2, TD2)
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 8, (4,6)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(5,-)
CSI-IM configuration	CSI-IM RE pattern		Patten 0
	CSI-IM Resource Mapping ( $K_{CSI-IM}, L_{CSI-IM}$ )		(4,9)
	CSI-IM timeConfig interval and offset	slot	5/1
ReportConfigType			Aperiodic
CQI-table			Table 1
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
CSI-Report interval and offset		slot	5/1
aperiodicTriggeringOffset			0
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1,CodebookConfig-N2)		(4,1)

	CodebookSubset Restriction		0x FFFF
	RI Restriction		00000010
Physical channel for CSI report			PUSCH
CQI/RI/PMI delay	ms		8
Maximum number of HARQ transmission			4
Measurement channel			MCS13, TBD for reference channel
Note 1:	For random precoder selection, the precoder shall be updated in each slot (1 ms granularity).		
Note 2:	If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-4)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+4)].		
Note 3:	Randomization of the principle beam direction shall be used as specified in TBD.		

**Table 6.3.3.1.2-2: Minimum requirement**

Parameter	Test 1
$\gamma$	TBD

### 6.3.3.2 TDD

#### 6.3.3.2.1 Single PMI with 4TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.3.2.1-1, and using the downlink physical channels specified in Annex TBD, the minimum requirements are specified in Table 6.3.3.2.1-2.

**Table 6.3.3.2.1-1: Test parameters (single layer)**

Parameter	Unit	Test 1
Bandwidth	MHz	40
Duplex Mode		TDD
TDD DL-UL configuration		FR1.30-1 as specified in Annex A
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	kHz
Propagation channel		TDLA30-5
Antenna configuration		High XP 4 x 4 (N1,N2) = (2,1)
Beamforming Model		TBD
ZP CSI-RS configuration	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)
	CSI-RS interval and offset	slot
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 4, (0,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(13,-)
	CSI-RS interval and offset	10/1
CSI-IM configuration	CSI-IM RE pattern	Patten 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )	(4,9)
	CSI-IM timeConfig interval and offset	slot
ReportConfigType		Aperiodic
CQI-table		Table 1
reportQuantity		cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		Not configured
timeRestrictionForInterferenceMeasurements		Not configured
cqi-FormatIndicator		Wideband
pmi-FormatIndicator		Wideband
CSI-Report interval and offset	slot	10/1
aperiodicTriggeringOffset		0
	Codebook Type	typel-SinglePanel
	Codebook Mode	1

Codebook configuration	(CodebookConfig-N1,CodebookConfig-N2)		(2,1)
	CodebookSubset Restriction		11111111
	RI Restriction		00000001
Physical channel for CSI report		PUSCH	
CQI/RI/PMI delay	ms	9.5	
Maximum number of HARQ transmission		4	
Measurement channel		MCS13, TBD for reference channel	
Note 1: For random precoder selection, the precoder shall be updated in each slot (0.5 ms granularity). Note 2: If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-6)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+6)]. Note 3: Randomization of the principle beam direction shall be used as specified in TBD.			

**Table 6.3.3.2.1-2: Minimum requirement**

Parameter	Test 1
$\gamma$	[1.3]

### 6.3.3.2.2 Single PMI with 8TX Type1-SinglePanel Codebook

For the parameters specified in Table 6.3.3.2.2-1, and using the downlink physical channels specified in Annex TBD, the minimum requirements are specified in Table 6.3.3.2.2-2.

**Table 6.3.3.2.2-1: Test parameters (dual-layer)**

Parameter	Unit	Test 1
Bandwidth	MHz	40
Duplex Mode		TDD
TDD DL-UL configurations		FR1.30-1 as specified in Annex A
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	106
	Subcarrier spacing	kHz
Propagation channel		TDLA30-5
Antenna configuration		High XP 8 x 4 (N1,N2) = (4,1)
Beamforming Model		TBD
ZP CSI-RS configuration	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)
	CSI-RS interval and offset	slot
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Aperiodic
	Number of CSI-RS ports ( $X$ )	8
	CDM Type	CDM4 (FD2, TD2)
	Density ( $\rho$ )	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 8, (4,6)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(5,-)
	CSI-RS interval and offset	slot
CSI-IM configuration	CSI-IM RE pattern	Patten 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )	(4,9)
	CSI-IM timeConfig interval and offset	slot
ReportConfigType		Aperiodic
CQI-table		Table 1
reportQuantity		cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		Not configured
timeRestrictionForInterferenceMeasurements		Not configured
cqi-FormatIndicator		Wideband
pmi-FormatIndicator		Wideband
CSI-Report interval and offset	slot	10/1
aperiodicTriggeringOffset		0
	Codebook Type	typel-SinglePanel
	Codebook Mode	1

Codebook configuration	(CodebookConfig-N1,CodebookConfig-N2)		(4,1)
	CodebookSubset Restriction		0x FFFF
	RI Restriction		00000010
Physical channel for CSI report		PUSCH	
CQI/RI/PMI delay	ms	9.5	
Maximum number of HARQ transmission		4	
Measurement channel		MCS13, TBD for reference channel	
Note 1: For random precoder selection, the precoder shall be updated in each slot (0.5 ms granularity). Note 2: If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-6)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+6)]. Note 3: Randomization of the principle beam direction shall be used as specified in TBD.			

**Table 6.3.3.2.2-2: Minimum requirement**

Parameter	Test 1
$\gamma$	TBD

## 6.4 Reporting of Rank Indicator (RI)

The purpose of this test is to verify that the reported rank indicator accurately represents the channel rank. The accuracy of RI reporting is determined by the relative increase of the throughput obtained when transmitting based on the reported rank compared to the case for which a fixed rank is used for transmission.

### 6.4.1 1RX requirements

(Void)

### 6.4.2 2RX requirements

#### 6.4.2.1 FDD

The minimum performance requirement in Table 6.4.2.1-2 is defined as

- a) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 1 shall be  $\geq \gamma_1$ ;
- b) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 2 shall be  $\geq \gamma_2$ ;

For the parameters specified in Table 6.4.2.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.4.2.1-2.

Table 6.4.2.1-1: RI Test (FDD)

Parameter	Unit	Test 1	Test 2	Test 3
Bandwidth	MHz	10	10	10
Duplex Mode		FDD	FDD	FDD
DL BWP configuration #1	First PRB	0	0	0
	Number of contiguous PRB	52	52	52
	Subcarrier spacing	kHz	15	15
SNR	dB	TBD	TBD	TBD
Propagation channel		TDLA30-5	TDLA30-5	TDLA30-5
Antenna configuration		ULA Low 2x2	ULA Low 2x2	ULA High 2x2
Beamforming Model		TBD	TBD	TBD
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )	4	4	4
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)	Row 5, (4,-)	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)	(9,-)	(9,-)
	CSI-RS periodicity and offset	slot	5/1	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )	2	2	2
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 3 (6,-)	Row 3 (6,-)	Row 3 (6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(13,-)	(13,-)	(13,-)
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1	5/1
CSI-IM configuration	CSI-IM RE pattern	Pattern 0	Pattern 0	Pattern 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )	(4,9)	(4,9)	(4,9)
	CSI-IM timeConfig periodicity and offset	slot	5/1	5/1
ReportConfigType		Periodic	Periodic	Periodic
CQI-table		Table 2	Table 2	Table 2
reportQuantity		cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		not configured	not configured	not configured
timeRestrictionForInterferenceMeasurements		not configured	not configured	not configured
cqi-FormatIndicator		Wideband	Wideband	Wideband
pmi-FormatIndicator		Wideband	Wideband	Wideband
CSI-Report periodicity and offset	slot	5/1	5/1	5/1
Codebook configuration	Codebook Type	typel-SinglePanel	typel-SinglePanel	typel-SinglePanel
	Codebook Mode	1	1	1
	(CodebookConfig-N1,CodebookConfig-N2)	N/A	N/A	N/A
	CodebookSubsetRestriction	TBD	TBD	TBD
	RI Restriction	N/A	N/A	N/A
Physical channel for CSI report		PUCCH	PUCCH	PUCCH
CQI/RI/PMI delay	ms	8	8	8
Maximum number of HARQ transmission		1	1	1
RI Configuration		Fixed RI = 2 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 1 and follow RI

**Table 6.4.2.1-2: Minimum requirement (FDD)**

	<b>Test 1</b>	<b>Test 2</b>	<b>Test 3</b>
$\gamma_1$	N/A	TBD	TBD
$\gamma_2$	TBD	N/A	N/A

#### 6.4.2.2 TDD

The minimum performance requirement in Table 6.4.2.2-2 is defined as

- a) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 1 shall be  $\geq \gamma_1$ ;
- b) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 2 shall be  $\geq \gamma_2$ ;

For the parameters specified in Table 6.4.2.2-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.4.2.2-2.

Table 6.4.2.2-1: RI Test (TDD)

Parameter		Unit	Test 1	Test 2	Test 3
Bandwidth		MHz	40	40	40
Duplex Mode			TDD	TDD	TDD
TDD Slot Configuration			FR1.30-1	FR1.30-1	FR1.30-1
DL BWP configuration #1	First PRB		0	0	0
	Number of contiguous PRB		106	106	106
	Subcarrier spacing	kHz	30	30	30
SNR		dB	TBD	TBD	TBD
Propagation channel			TDLA30-5	TDLA30-5	TDLA30-5
Antenna configuration			ULA Low 2x2	ULA Low 2x2	ULA High 2x2
Beamforming Model			TBD	TBD	TBD
ZP CSI-RS configuration	CSI-RS resource Type		Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )		4	4	4
	CDM Type		FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )		1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)	Row 5, (4,-)	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)	(9,-)	(9,-)
	CSI-RS periodicity and offset	slot	10/1	10/1	10/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )		2	2	2
	CDM Type		FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )		1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3 (6,-)	Row 3 (6,-)	Row 3 (6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)	(13,-)	(13,-)
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1	10/1	10/1
CSI-IM configuration	CSI-IM RE pattern		Pattern 0	Pattern 0	Pattern 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4,9)	(4,9)	(4,9)
	CSI-IM timeConfig periodicity and offset	slot	10/1	10/1	10/1
ReportConfigType			Periodic	Periodic	Periodic
CQI-table			Table 2	Table 2	Table 2
reportQuantity			cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			not configured	not configured	not configured
timeRestrictionForInterferenceMeasurements			not configured	not configured	not configured
cqi-FormatIndicator			Wideband	Wideband	Wideband
pmi-FormatIndicator			Wideband	Wideband	Wideband
CSI-Report periodicity and offset		slot	10/1	10/1	10/1
Codebook configuration	Codebook Type		typel-SinglePanel	typel-SinglePanel	typel-SinglePanel
	Codebook Mode		1	1	1
	(CodebookConfig-N1,CodebookConfig-N2)		N/A	N/A	N/A
	CodebookSubsetRestriction		TBD	TBD	TBD
	RI Restriction		N/A	N/A	N/A
Physical channel for CSI report			PUCCH	PUCCH	PUCCH
CQI/RI/PMI delay		ms	9.5	9.5	9.5
Maximum number of HARQ transmission			1	1	1
RI Configuration			Fixed RI = 2 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 1 and follow RI

**Table 6.4.2.2-2: Minimum requirement (TDD)**

	<b>Test 1</b>	<b>Test 2</b>	<b>Test 3</b>
$\gamma_1$	N/A	TBD	TBD
$\gamma_2$	TBD	N/A	N/A

## 6.4.3 4RX requirements

### 6.4.3.1 FDD

The minimum performance requirement in Table 6.4.3.1-2 is defined as

- a) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 1 shall be  $\geq \gamma_1$ ;
- b) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 2 shall be  $\geq \gamma_2$ ;

For the parameters specified in Table 6.4.3.1-1, and using the downlink physical channels specified in Annex C.3.1, the minimum requirements are specified in Table 6.4.3.1-2.

Table 6.4.3.1-1: RI Test (FDD)

Parameter	Unit	Test 1	Test 2	Test 3	Test 4
Bandwidth	MHz	10	10	10	10
Duplex Mode		FDD	FDD	FDD	FDD
DL BWP configuration #1	First PRB	0	0	0	0
	Number of contiguous PRB	52	52	52	52
	Subcarrier spacing	kHz	15	15	15
SNR	dB	TBD	TBD	TBD	TBD
Propagation channel		TDLA30-5	TDLA30-5	TDLA30-5	TDLA30-5
Antenna configuration		ULA Low 2x4	ULA Low 2x4	ULA High 2x4	ULA Low 4x4
Beamforming Model		TBD	TBD	TBD	TBD
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	Periodic	Periodic	Periodic
	Number of CSI-RS ports (X)	4	4	4	4
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 5, (4,-)	Row 5, (4,-)	Row 5, (4,-)	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(9,-)	(9,-)	(9,-)	(9,-)
	CSI-RS periodicity and offset	slot	5/1	5/1	5/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	Periodic	Periodic	Periodic
	Number of CSI-RS ports (X)	2	2	2	4
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )	Row 3 (6,-)	Row 3 (6,-)	Row 3 (6,-)	Row 4 (0,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )	(13,-)	(13,-)	(13,-)	(13,-)
	NZP CSI-RS-timeConfig periodicity and offset	slot	5/1	5/1	5/1
CSI-IM configuration	CSI-IM RE pattern		Pattern 0	Pattern 0	Pattern 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4,9)	(4,9)	(4,9)
	CSI-IM timeConfig periodicity and offset	slot	5/1	5/1	5/1
ReportConfigType		Periodic	Periodic	Periodic	Periodic
CQI-table		Table 2	Table 2	Table 2	Table 2
reportQuantity		cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		not configured	not configured	not configured	not configured
timeRestrictionForInterferenceMeasurements		not configured	not configured	not configured	not configured
cqi-FormatIndicator		Wideband	Wideband	Wideband	Wideband
pmi-FormatIndicator		Wideband	Wideband	Wideband	Wideband
CSI-Report periodicity and offset	slot	5/1	5/1	5/1	5/1
Codebook configuration	Codebook Type		typel-SinglePanel	typel-SinglePanel	typel-SinglePanel
	Codebook Mode		1	1	1
	(CodebookConfig-N1,CodebookConfig-N2)		N/A	N/A	N/A
	CodebookSubsetRestriction		TBD	TBD	TBD
	RI Restriction		N/A	N/A	N/A
Physical channel for CSI report		PUCCH	PUCCH	PUCCH	PUCCH
CQI/RI/PMI delay	ms	8	8	8	8
Maximum number of HARQ transmission		1	1	1	1
RI Configuration		Fixed RI = 2 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 2 and follow RI

**Table 6.4.3.1-2: Minimum requirement (FDD)**

	<b>Test 1</b>	<b>Test 2</b>	<b>Test 3</b>	<b>Test 4</b>
$\gamma_1$	N/A	TBD	TBD	N/A
$\gamma_2$	TBD	N/A	N/A	TBD

### 6.4.3.2 TDD

The minimum performance requirement in Table 6.4.3.2-2 is defined as

- a) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 1 shall be  $\geq \gamma_1$ ;
- b) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 2 shall be  $\geq \gamma_2$ ;

For the parameters specified in Table 6.4.3.2-1, and using the downlink physical channels specified in Annex TBD, the minimum requirements are specified in Table 6.4.3.2-2.

**Table 6.4.3.2-1: RI Test (TDD)**

Parameter	Unit	Test 1	Test 2	Test 3	Test 4
Bandwidth	MHz	40	40	40	40
Duplex Mode		TDD	TDD	TDD	TDD
TDD Slot Configuration		FR1.30-1	FR1.30-1	FR1.30-1	FR1.30-1
DL BWP configuration #1	First PRB	0	0	0	0
	Number of contiguous PRB	106	106	106	106
	Subcarrier spacing	kHz	30	30	30
SNR	dB	TBD	TBD	TBD	TBD
Propagation channel		TDLA30-5	TDLA30-5	TDLA30-5	TDLA30-5
Antenna configuration		ULA Low 2x4	ULA Low 2x4	ULA High 2x4	ULA Low 4x4
Beamforming Model		TBD	TBD	TBD	TBD
ZP CSI-RS configuration	CSI-RS resource Type	Periodic	Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )	4	4	4	4
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 5, (4,-)	Row 5, (4,-)	Row 5, (4,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(9,-)	(9,-)	(9,-)
	CSI-RS periodicity and offset	slot	10/1	10/1	10/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type	Periodic	Periodic	Periodic	Periodic
	Number of CSI-RS ports ( $X$ )	2	2	2	2
	CDM Type	FD-CDM2	FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )	1	1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3 (6,-)	Row 3 (6,-)	Row 3 (6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)	(13,-)	(13,-)
	NZP CSI-RS-timeConfig periodicity and offset	slot	10/1	10/1	10/1
CSI-IM configuration	CSI-IM RE pattern		Pattern 0	Pattern 0	Pattern 0
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(4,9)	(4,9)	(4,9)
	CSI-IM timeConfig periodicity and offset	slot	10/1	10/1	10/1
ReportConfigType		Periodic	Periodic	Periodic	Periodic
CQI-table		Table 2	Table 2	Table 2	Table 2
reportQuantity		cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements		not configured	not configured	not configured	not configured
timeRestrictionForInterferenceMeasurements		not configured	not configured	not configured	not configured
cqi-FormatIndicator		Wideband	Wideband	Wideband	Wideband
pmi-FormatIndicator		Wideband	Wideband	Wideband	Wideband
CSI-Report periodicity and offset	slot	10/1	10/1	10/1	10/1
Codebook configuration	Codebook Type	typel-SinglePanel	typel-SinglePanel	typel-SinglePanel	typel-SinglePanel
	Codebook Mode	1	1	1	1
	(CodebookConfig-N1, CodebookConfig-N2)	N/A	N/A	N/A	(2,1)
	CodebookSubsetRestriction	TBD	TBD	TBD	11111111
	RI Restriction		N/A	N/A	00000010 for fixed Rank 2 and 00001111 for follow RI
Physical channel for CSI report		PUCCH	PUCCH	PUCCH	PUCCH
CQI/RI/PMI delay	ms	9.5	9.5	9.5	9.5
Maximum number of HARQ transmission		1	1	1	1
RI Configuration		Fixed RI = 2 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 2 and follow RI

**Table 6.4.3.2-2: Minimum requirement (TDD)**

	<b>Test 1</b>	<b>Test 2</b>	<b>Test 3</b>	<b>Test 4</b>
$\gamma_1$	N/A	TBD	TBD	N/A
$\gamma_2$	TBD	N/A	N/A	TBD

---

## 7 Demodulation performance requirements (Radiated requirements)

### 7.1 General

#### 7.1.1 Applicability of requirements

### 7.2 PDSCH demodulation requirements

The parameters specified in Table 7.2-1 are valid for all PDSCH demodulation tests unless otherwise stated.

Table 7.2-1: Common Test Parameters

Parameter	Unit	Value
PDSCH transmission scheme		Transmission scheme 1
EPRE ratio of PTRS to PDSCH	dB	0
DL BWP configuration #1	Cyclic prefix	Normal
Common serving cell parameters	Physical Cell ID	0
	SSB position in burst	1
	SSB periodicity	ms 20
	First DMRS position for Type A PDSCH mapping	2
PDCCH configuration	Slots for PDCCH monitoring	TBD
	Symbols with PDCCH	0
	Number of PDCCH candidates and aggregation levels	TBD
	DCI format	TBD
Cross carrier scheduling		Not configured
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	0
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	CSI-RS resource 1: 6 CSI-RS resource 2: 10 CSI-RS resource 3: 6 CSI-RS resource 4: 10
	Number of CSI-RS ports (X)	1
	CDM Type	No CDM
	Density ( $\rho$ )	3
	CSI-RS periodicity	Slots 160
	CSI-RS offset	Slots 80 for CSI-RS resource 1 and 2 81 for CSI-RS resource 3 and 4
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	0
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	12
NZP CSI-RS for CSI acquisition	Number of CSI-RS ports (X)	2
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	CSI-RS periodicity	Slots 160
	CSI-RS offset	0
	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	4
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	12
ZP CSI-RS for CSI acquisition	Number of CSI-RS ports (X)	4
	CDM Type	FD-CDM2
	Density ( $\rho$ )	1
	CSI-RS periodicity	Slots 160
	CSI-RS offset	0
	Antenna ports indexes	{1000} for Rank 1 tests {1000, 1001} for Rank 2 tests
PDSCH DMRS configuration	Number of PDSCH DMRS CDM group(s) without data	1
	Frequency density ( $K_{PT-RS}$ )	2
PTRS configuration	Time density ( $L_{PT-RS}$ )	1
	Maximum number of code block groups for ACK/NACK feedback	1
Maximum number of HARQ transmission		4
HARQ ACK/NACK bundling		Multiplexed
Redundancy version coding sequence		{0,2,3,1}
Precoding configuration		SP Type I, Random per slot with PRB bundling granularity
Symbols for all unused Res		OCNG in Annex A.5

### 7.2.1 1RX requirements

(Void)

### 7.2.2 2RX requirements

#### 7.2.2.1 FDD

(Void)

#### 7.2.2.2 TDD

##### 7.2.2.2.1 Minimum requirements for PDSCH Mapping Type-A

For PDSCH Type-A scheduling, the requirements are specified in Table 7.2.2.2.1-3, 7.2.2.2.1-4 and 7.2.2.2.1-5, with the addition of the parameters in Table 7.2.2.2.1-2 and the downlink physical channel setup according to Annex C.5.1. The purpose is to verify the performance of PDSCH Type-A scheduling.

The test purposes are specified in Table 7.2.2.1.1-1.

**Table 7.2.2.1.1-1: Tests purpose**

Purpose	Test index
TBD	TBD

**Table 7.2.2.2.1-2: Test Parameters**

Parameter	Unit	Value
Channel bandwidth	MHz	50 for 2-3 and 2-5, 200 for 2-4, 100 for other tests
Duplex mode		TDD
Active DL BWP index		1
DL BWP configuration #1	First PRB	0
	Number of contiguous PRB	32 for 2-3, 132 for 2-4, 66 for other tests
	Subcarrier spacing	kHz
PDCCH configuration	Number of PRBs in CORESET	PRBs
PDSCH configuration	Mapping type	Type A
	$k_0$	0
	Starting symbol (S)	1
	Length (L)	As defined in Annex A.1.3
	PDSCH aggregation factor	1
	PRB bundling type	Static
	PRB bundling size	TBD
	Resource allocation type	Type 1
	VRB-to-PRB mapping type	Non-interleaved
	VRB-to-PRB mapping interleaver bundle size	N/A
	DMRS Type	Type 1
	Number of additional DMRS	1
PDSCH DMRS configuration	Length	Single-symbol DM-RS
	Antenna ports indexes	{1000} for Rank1 {1000,1001} for Rank2
	Number of PDSCH DMRS CDM group(s) without data	1
	Number of HARQ Processes	8 for Test 1-1, 1-3, 2-4 10 for Test 2-1, 2-3, 2-5, 2-6, 3-1 16 for Test 1-2 TBD for Test 2-2
	K1 value (PDSCH-to-HARQ-timing-indicator)	As defined in Annex A.1.3

**Table 7.2.2.2.1-3: Minimum performance for Rank 1 (FRC)**

Test num.	Reference channel	Modulation and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR <sub>BB</sub> (dB)
1-1	TBD	QPSK, 0.30	FR2.120-1	TDLC60-300	2x2 ULA Low	70	[−0.5]
1-2	TBD	16QAM, 0.48	FR2.120-1	TDLA30-300	2x2 ULA Low	30	[1.6]
1-3	TBD	64QAM, 0.45	FR2.120-1	TDLA30-300	2x2 XPL Med-A	70	[TBD]

**Table 7.2.2.2.1-4: Minimum performance for Rank 2 (FRC)**

Test num.	Reference channel	Modulation and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR <sub>BB</sub> (dB)
2-1	TBD	QPSK, 0.30	FR2.120-2	TDLA30-75	2x2 ULA Low	70	[TBD]
2-2	TBD	16QAM, 0.48	FR2.120-1	TDLA30-300	2x2 ULA Low	70	[TBD]
2-3	TBD	16QAM, 0.48	FR2.120-2	TDLA30-75	2x2 ULA Low	70	[13 .9]
2-4	TBD	16QAM, 0.48	FR2.120-1	TDLA30-300	2x2 ULA Low	70	[TBD]
2-5	TBD	16QAM, 0.48	FR2.60-1	TDLA30-75	2x2 ULA Low	70	[14.3]
2-6	TBD	64QAM, 0.43	FR2.120-2	TBD	2x2 ULA Low	70	[TBD]

**Table 7.2.2.2.1-5: Minimum performance for Rank 2 (FRC) for Enhanced Type X Receiver**

Test num.	Reference channel	Modulation and code rate	TDD UL-DL pattern	Propagation condition	Correlation matrix and antenna configuration	Reference value	
						Fraction of maximum throughput (%)	SNR <sub>BB</sub> (dB)
3-1	TBD	16QAM, 0.48	FR2.120-2	TDLA30-75	2x2 ULA Med	70	[19.5]

## 7.3 PDCCH demodulation requirements

The receiver characteristics of the PDCCH are determined by the probability of miss-detection of the Downlink Scheduling Grant (Pm-dsg).

The parameters specified in Table 7.3-1 are valid for all PDCCH tests unless otherwise stated.

**Table 7.3-1: Common test Parameters**

Parameter	Unit	Value	
DL BWP configuration #1	Cyclic prefix	Normal	
Common serving cell parameters	Physical Cell ID	0	
	SSB position in burst	1	
	SSB periodicity	ms	20
PDCCH configuration	Slots for PDCCH monitoring	TBD	
	Number of PDCCH candidates	TBD	
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )	0	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )	CSI-RS resource 1: 4 CSI-RS resource 2: 8 CSI-RS resource 3: 4 CSI-RS resource 4: 8	
	Number of CSI-RS ports ( $X$ )	1	
	CDM Type	No CDM	
	Density ( $\rho$ )	3	
	CSI-RS periodicity	Slots	160
	CSI-RS offset	Slots	80 for CSI-RS resource 1 and 2 81 for CSI-RS resource 3 and 4
	Precoding configuration		SP Type I, Random per slot with REG bundling granularity for number of Tx larger than 1
Symbols for all unused Res		OCNG in Annex A.5	

### 7.3.1 1RX requirements

(Void)

### 7.3.2 2RX requirements

#### 7.3.2.1 FDD

(Void)

#### 7.3.2.2 TDD

The parameters specified in Table 7.3.2.2-1 are valid for all TDD tests unless otherwise stated.

**Table 7.3.2.2-1: Test Parameters**

Parameter	Unit	1 Tx Antenna	2 Tx Antenna
TDD UL-DL pattern		FR2.120-1	
CCE to REG mapping type		Interleaved	
REG bundle size		2 for test 1-1 6 for test 1-2	2
Interleaver size		3 for test 1-1 2 for test 1-2	3
Shift index		0	

#### 7.3.2.2.1 1 Tx Antenna performances

For the parameters specified in Table 7.3.2.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 7.3.2.2.1-1. The downlink physical setup is in accordance with Annex C.5.1.

**Table 7.3.2.2.1-1: Minimum performance requirements with 120 kHz SCS**

Test number	Bandwidth	CORES ET RB	CORESET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR <sub>BB</sub> (dB)
1-1	100 MHz	60	1	2 CCE	R.PDCCH. 5-1.1 TDD	TDLA30-75	1x2 Low	1	TBD
1-2	100 MHz	60	1	4 CCE	R.PDCCH. 5-1.2 TDD	TDLA30-300	1x2 Low	1	TBD

### 7.3.2.2.2 2 Tx Antenna performances

For the parameters specified in Table 7.3.2.2-1, the average probability of a missed downlink scheduling grant (Pm-dsg) shall be below the specified value in Table 7.3.2.2.2-1. The downlink physical setup is in accordance with Annex C.5.1.

**Table 7.3.2.2.2-1: Minimum performance requirements with 120 kHz SCS**

Test number	Bandwidth	CORESE T RB	CORESET duration	Aggregation level	Reference Channel	Propagation Condition	Antenna configuration and correlation Matrix	Reference value	
								Pm-dsg (%)	SNR <sub>BB</sub> (dB)
2-1	100 MHz	60	1	8 CCE	R.PDCCH. 5-1.3 TDD	TDLA30-75	2x2 Low	1	[-0.3]
2-2	100 MHz	60	2	16 CCE	R.PDCCH. 5-2.1 TDD	TDLA30-75	2x2 Low	1	[-3.6]

## 7.4 PBCH demodulation requirements

The receiver characteristics of PBCH are determined by the probability of miss-detection of the PBCH (Pm-bch), which is defined as

$$Pm - bch = 1 - \frac{A}{B}$$

Where A is the number of correctly decoded MIB PDUs and B is the number of transmitted MIB PDUs. The Pm-bch is derived with the assumption UE combines the PBCH symbols of the same SS/PBCH block index within the MIB TTI (80ms).

### 7.4.1 1RX requirements

(Void)

### 7.4.2 2RX requirements

#### 7.4.2.1 FDD

(Void)

### 7.4.2.2 TDD

**Table 7.4.2.2-1: Test parameters for PBCH**

Parameter	Unit	Single antenna port
Physical Cell ID		0
Cyclic prefix		Normal
Number of SS/PBCH blocks within an SS burst set periodicity		1
SS/PBCH block index <sup>Note1</sup>		0
SS/PBCH block periodicity	ms	20
TDD UL-DL pattern		FR2.120-1
Note 1: as specified in TS 38.213 [11, Section 4.1]		
Note 2: as specified in TS 38.213 [11, Section 11.1]		

For the parameters specified in Table 7.4.2.2-1 the average probability of a miss-detected PBCH (Pm-bch) shall be below the specified values in Table 7.4.2.2-2 in case SS/PBCH block index is not known. The downlink physical setup is in accordance with Annex C.5.1.

**Table 7.4.2.2-2: Minimum performance PBCH in case SS/PBCH block index is not known**

Test number	Bandwidth	Reference channel	Propagation condition	Antenna configuration and correlation matrix	Reference value	
					Pm-bch (%)	SNR <sub>BB</sub> (dB)
1	100 MHz	R.PBCH.5	[TDLA30-300]	1 x 2 Low	1	TBD
2	100 MHz	R.PBCH.6	[TDLA30-75]	1 x 2 Low	1	TBD

## 7.5 Sustained downlink data rate provided by lower layers

<TBA>

---

## 8 CSI reporting requirements (Radiated requirements)

### 8.1 General

This section includes radiated requirements for the reporting of channel state information (CSI).

#### 8.1.1 Applicability of requirements

<TBA>

#### 8.1.2 Common test parameters

Parameters specified in Table 8.1.2-1 are applied for all test cases in this section unless otherwise stated.

Table 8.1.2-1: Test parameters for CSI test cases

Parameter		Unit	Value
PDSCH transmission scheme			Transmission scheme 1
Duplex Mode			TDD
EPRE ratio of PTRS to PDSCH	dB		TBD
Active DL BWP index			1
Cyclic prefix			Normal
Common serving cell parameters	Physical Cell ID		0
	SSB position in burst		First SSB in Slot #0
	SSB periodicity	ms	20
PDCCH configuration	Slots for PDCCH monitoring		Each slot
	Symbols with PDCCH		0,1
	Number of PDCCH candidates and aggregation levels		TBD
	DCI format		TBD
Cross carrier scheduling			Not configured
PDSCH configuration	Mapping type		Type A
	$k_0$		0
	Starting symbol (S)		2
	Length (L)		12
	PDSCH aggregation factor		1
	PRB bundling type		Static
	PRB bundling size		2
	Resource allocation type		0
	VRB-to-PRB mapping type		Non-interleaved
	VRB-to-PRB mapping interleaver bundle size		TBD
PDSCH DMRS configuration	DMRS Type		Type 1
	Number of additional DMRS		1
	DMRS ports indexes		{1000} for Rank1 {1000,1001} for Rank2
	Length		Single-symbol DM-RS
	Number of PDSCH DMRS CDM group(s) without data		2
PTRS configuration	Frequency density ( $K_{PT-RS}$ )		TBD
	Time density ( $L_{PT-RS}$ )		TBD
CSI-RS for tracking	First subcarrier index in the PRB used for CSI-RS ( $k_0$ )		[0]
	First OFDM symbol in the PRB used for CSI-RS ( $l_0$ )		[4]
	Number of CSI-RS ports ( $X$ )		1
	CDM Type		No CDM
	Density ( $\rho$ )		3
	CSI-RS periodicity	slot	120kHz SCS: 160
	CSI-RS offset	slot	120 kHz SCS: 80 for CSI-RS resource 1 and 2 81 for CSI-RS resource 3 and 4
	Number of HARQ Processes		8
HARQ ACK/NACK bundling			TBD
Redundancy version coding sequence			{0,2,3,1}
K1 value (PDSCH-to-HARQ-timing-indicator)			TBD
Symbols for unused Res			OCNG as specified in A.5

## 8.2 Reporting of Channel Quality Indicator (CQI)

### 8.2.1 1RX requirements

(Void)

### 8.2.2 2RX requirements

#### 8.2.2.1 FDD

(Void)

#### 8.2.2.2 TDD

##### 8.2.2.2.1 CQI reporting under AWGN conditions

*<Editor's note: The requirements were introduced based on current results from companies; these requirements can be revised based on more results from companies.>*

The reporting accuracy of the channel quality indicator (CQI) under frequency non-selective conditions is determined by the reporting variance and the BLER performance using the transport format indicated by the reported CQI median. The purpose is to verify that the reported CQI values are in accordance with the CQI definition given in TS 38.214 [12]. To account for sensitivity of the input SNR the reporting definition is considered to be verified if the reporting accuracy is met for at least one of two SNR levels separated by an offset of [1] dB.

###### 8.2.2.2.1.1 Minimum requirement for periodic CQI reporting

For the parameters specified in Table 8.2.2.2.1.1-1, and using the downlink physical channels specified in Annex C.5.1, the minimum requirements are specified by the following:

- a) the reported CQI value shall be in the range of  $\pm 1$  of the reported median more than [90%] of the time;
- b) if the PDSCH BLER using the transport format indicated by median CQI is less than or equal to 0.1, the BLER using the transport format indicated by the (median CQI + 1) shall be greater than 0.1. If the PDSCH BLER using the transport format indicated by the median CQI is greater than 0.1, the BLER using transport format indicated by (median CQI – 1) shall be less than or equal to 0.1.

Table 8.2.2.2.1.1-1 Test parameters

Parameter		Unit	Test 1	Test 2
Bandwidth		MHz	100	100
Duplex Mode			TDD	TDD
TDD Slot Configuration			FR2.120-2 [Annex A.1.3]	FR2.120-2 [Annex A.1.3]
DL BWP configuration #1	First PRB		[TBD]	[TBD]
	Number of contiguous PRB		[TBD]	[TBD]
	Subcarrier spacing	kHz	120	120
SNR <sub>BB</sub>	dB	[8]	[9]	[14] [15]
Propagation channel			AWGN	AWGN
Antenna configuration			2x2 with static channel specified in [Annex TBD]	2x2 with static channel specified in [Annex TBD]
Beamforming Model			[TBD]	[TBD]
ZP CSI-RS configuration	CSI-RS resource Type		Periodic	Periodic
	Number of CSI-RS ports ( $X$ )		4	4
	CDM Type		FD-CDM2	FD-CDM2
	Density ( $\rho$ )		1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		8	8
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		13	13
	CSI-RS periodicity and offset	slot	8/1	8/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Periodic	Periodic
	Number of CSI-RS ports ( $X$ )		2	2
	CDM Type		fd-CDM2	fd-CDM2
	Density ( $\rho$ )		1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		6	6
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		13	13
	NZP CSI-RS-timeConfig periodicity and offset	slot	8/1	8/1
CSI-IM configuration	CSI-IM RE pattern		1	1
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(8, 13)	(8, 13)
	CSI-IM timeConfig periodicity and offset	slot	8/1	8/1
ReportConfigType			Periodic	Periodic
CQI-table			Table 1	Table 1
reportQuantity			cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured	Not configured
timeRestrictionForInterferenceMeasurements			Not configured	Not configured
cqi-FormatIndicator			Wideband	Wideband
pmi-FormatIndicator			Wideband	Wideband
Sub-band Size		RB	N/A	N/A
CSI-Report periodicity and offset		slot	8/1	8/1
aperiodicTriggeringOffset			Not configured	Not configured
Codebook configuration	Codebook Type		typel-SinglePanel	typel-SinglePanel
	Codebook Mode		1	1
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured	Not configured
	CodebookSubsetRestriction		[010000]	[010000]
	RI Restriction		[N/A]	[N/A]
Physical channel for CSI report			[PUCCH]	[PUCCH]
CQI/RI/PMI delay		ms	[TBD]	[TBD]
Maximum number of HARQ transmission			1	1
Measurement channel			[TBD]	[TBD]

### 8.2.2.2.2 CQI reporting under fading conditions

#### 8.2.2.2.2.1 Minimum requirement for wideband CQI reporting

<Editor's note: Open issues to be resolved:

- *SNR levels*
- *Test parameters*
- *Requirements values (BLER,  $\alpha$ ,  $\gamma$ )>*

The purpose of the requirements is to verify that the UE is tracking the channel variations and selecting the largest transport format possible according to the prevailing channel state for the frequency non-selective scheduling.

The reporting accuracy of CQI under frequency non-selective fading conditions is determined by the reporting variance, the relative increase of the throughput obtained when the transport format is indicated by the reported CQI compared to the throughput obtained when a fixed transport format is configured according to the reported median CQI, and a minimum BLER using the transport formats indicated by the reported CQI. To account for sensitivity of the input SNR the CQI reporting under frequency non-selective fading conditions is considered to be verified if the reporting accuracy is met for at least one of two SNR levels separated by an offset of [1] dB.

For the parameters specified in Table 8.2.2.2.2.1-1 and using the downlink physical channels specified in Annex C.5.1, the minimum requirements are specified by the following:

- a) a CQI index not in the set {median CQI -1, median CQI, median CQI +1} shall be reported at least  $\alpha$  % of the time;
- b) the ratio of the throughput obtained when transmitting the transport format indicated by each reported wideband CQI index and that obtained when transmitting a fixed transport format configured according to the wideband CQI median shall be  $\geq \gamma$ ;
- c) when transmitting the transport format indicated by each reported wideband CQI index, the average BLER for the indicated transport formats shall be greater or equal to TBD.

Table 8.2.2.2.2.1-1 Test parameters

Parameter		Unit	Test 1	Test 2	
Bandwidth		MHz	100	100	
Duplex Mode			TDD	TDD	
TDD Slot Configuration			FR2.120-2 [Annex A.1.3]	FR2.120-2 [Annex A.1.3]	
DL BWP configuration #1	First PRB		[TBD]	[TBD]	
	Number of contiguous PRB		[TBD]	[TBD]	
	Subcarrier spacing	kHz	120	120	
SNR <sub>BB</sub>	dB	[TBD]	[TBD]	[TBD]	[TBD]
Propagation channel			[TDLA30-35]	[TDLA30-35]	
Antenna configuration			2x2 [ULA High]	2x2 [ULA High]	
Beamforming Model			[TBD]	[TBD]	
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic	Aperiodic	
	Number of CSI-RS ports ( $X$ )		4	4	
	CDM Type		FD-CDM2	FD-CDM2	
	Density ( $\rho$ )		1	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		8	8	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		13	13	
	CSI-RS interval and offset	slot	[8/1]	[8/1]	
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic	Aperiodic	
	Number of CSI-RS ports ( $X$ )		2	2	
	CDM Type		fd-CDM2	fd-CDM2	
	Density ( $\rho$ )		1	1	
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		6	6	
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		13	13	
	NZP CSI-RS-timeConfig interval and offset	slot	[8/1]	[8/1]	
CSI-IM configuration	CSI-IM RE pattern		1	1	
	CSI-IM Resource Mapping ( $(k_{\text{CSI-IM}}, l_{\text{CSI-IM}})$ )		(8, 13)	(8, 13)	
	CSI-IM timeConfig interval and offset	slot	[8/1]	[8/1]	
ReportConfigType			Aperiodic	Aperiodic	
CQI-table			Table 1	Table 1	
reportQuantity			cri-RI-PMI-CQI	cri-RI-PMI-CQI	
timeRestrictionForChannelMeasurements			Not configured	Not configured	
timeRestrictionForInterferenceMeasurements			Not configured	Not configured	
cqi-FormatIndicator			Wideband	Wideband	
pmi-FormatIndicator			Wideband	Wideband	
Sub-band Size		RB	N/A	N/A	
CSI-Report periodicity and offset		slot	8/1	8/1	
aperiodicTriggeringOffset			Not configured	Not configured	
Codebook configuration	Codebook Type		typel-SinglePanel	typel-SinglePanel	
	Codebook Mode		1	1	
	(CodebookConfig-N1,CodebookConfig-N2)		Not configured	Not configured	
	CodebookSubsetRestriction		[000001]	[000001]	
	RI Restriction		[N/A]	[N/A]	
Physical channel for CSI report			[PUSCH]	[PUSCH]	
CQI/RI/PMI delay		ms	[1.375]	[1.375]	
Maximum number of HARQ transmission			1	1	
Measurement channel			[TBD]	[TBD]	

**Table 8.2.2.2.1-2 Minimum requirements**

	<b>Test 1</b>	<b>Test 2</b>
$\alpha [\%]$	[TBD]	[TBD]
$\gamma$	[TBD]	[TBD]

## 8.3 Reporting of Precoding Matrix Indicator (PMI)

The minimum performance requirements of PMI reporting are defined based on the precoding gain, expressed as the relative increase in throughput when the transmitter is configured according to the UE reports compared to the case when the transmitter is using random precoding, respectively. When the transmitter uses random precoding, for each PDSCH allocation a precoder is randomly generated and applied to the PDSCH. A fixed transport format (FRC) is configured for all requirements.

The requirements for transmission mode 1 with 2TX and higher layer parameter *codebookType* set to ‘typeI-SinglePanel’ are specified in terms of the ratio

$$\gamma = \frac{t_{ue}}{t_{rnd}}$$

In the definition of  $\gamma$ , for 2TX PMI requirements,  $t_{ue}$  is [90] % of the maximum throughput obtained at  $SNR_{ue}$  using the precoders configured according to the UE reports, and  $t_{rnd}$  is the throughput measured at  $SNR_{ue}$  with random precoding.

### 8.3.1 1RX requirements

(Void)

### 8.3.2 2RX requirements

#### 8.3.2.1 FDD

(Void)

#### 8.3.2.2 TDD

##### 8.3.2.2.1 Single PMI with 2TX TypeI-SinglePanel Codebook

For the parameters specified in Table 8.3.2.2.1-1, and using the downlink physical channels specified in Annex C.5.1, the minimum requirements are specified in Table 8.3.2.2.1-2.

**Table 8.3.2.2.1-1: Test parameters (single layer)**

Parameter		Unit	Test 1
Bandwidth		MHz	100
TDD DL-UL configuration			FR2.120-2 as specified in Annex A
DL BWP configuration #1	First PRB		0
	Number of contiguous PRB		66
	Subcarrier spacing	kHz	120
Propagation channel			[TDLA30-35]
Antenna configuration			TBD
Beamforming Model			TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		4
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 4, (8,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)
	CSI-RS interval and offset	slot	8/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic
	Number of CSI-RS ports ( $X$ )		2
	CDM Type		FD-CDM2
	Density ( $\rho$ )		1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3, (6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)
CSI-IM configuration	CSI-IM RE pattern		Patten 0
	CSI-IM Resource Mapping ( $K_{CSI-IM}, L_{CSI-IM}$ )		(8,13)
	CSI-IM timeConfig interval and offset	slot	8/1
ReportConfigType			Aperiodic
CQI-table			Table 1
reportQuantity			cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			Not configured
timeRestrictionForInterferenceMeasurements			Not configured
cqi-FormatIndicator			Wideband
pmi-FormatIndicator			Wideband
CSI-Report interval and offset		slot	8/1
aperiodicTriggeringOffset			0
Codebook configuration	Codebook Type		typel-SinglePanel
	Codebook Mode		1
	(CodebookConfig-N1, CodebookConfig-N2)		N/A

	CodebookSubset Restriction		001111
	RI Restriction		N/A
Physical channel for CSI report			PUSCH
CQI/RI/PMI delay	ms		1.375
Maximum number of HARQ transmission			4
Measurement channel			MCS13, TBD for reference channel
Note 1:	For random precoder selection, the precoder shall be updated in each slot (0.125 ms granularity).		
Note 2:	If the UE reports in an available uplink reporting instance at slot#n based on PMI estimation at a downlink slot not later than slot#[(n-12)], this reported PMI cannot be applied at the eNB downlink before slot#[(n+12)].		
Note 3:	Randomization of the principle beam direction shall be used as specified in TBD.		

**Table 8.3.2.2.1-2: Minimum requirement**

Parameter	Test 1
$\gamma$	TBD

## 8.4 Reporting of Rank Indicator (RI)

The purpose of this test is to verify that the reported rank indicator accurately represents the channel rank. The accuracy of RI reporting is determined by the relative increase of the throughput obtained when transmitting based on the reported rank compared to the case for which a fixed rank is used for transmission.

### 8.4.1 1RX requirements

(Void)

### 8.4.2 2RX requirements

#### 8.4.2.1 FDD

(Void)

#### 8.4.2.2 TDD

The minimum performance requirement in Table 8.4.2.2-2 is defined as

- a) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 1 shall be  $\geq \gamma_1$ ;
- b) The ratio of the throughput obtained when transmitting based on UE reported RI and that obtained when transmitting with fixed rank 2 shall be  $\geq \gamma_2$ ;

For the parameters specified in Table 8.4.2.2-1, and using the downlink physical channels specified in Annex C.5.1, the minimum requirements are specified in Table 8.4.2.2-2.

Table 8.4.2.2-1: RI Test (TDD)

Parameter		Unit	Test 1	Test 2	Test 3
Bandwidth		MHz	100	100	100
Duplex Mode			TDD	TDD	TDD
TDD Slot Configuration			FR1.120-2	FR1.120-2	FR1.120-2
DL BWP configuration #1	First PRB		0	0	0
	Number of contiguous PRB		66	66	66
	Subcarrier spacing	kHz	120	120	120
SNR		dB	TBD	TBD	TBD
Propagation channel			[TDLA30-35]	[TDLA30-35]	[TDLA30-35]
Antenna configuration			ULA Low 2x2	ULA Low 2x2	XP High 2x2
Beamforming Model			TBD	TBD	TBD
ZP CSI-RS configuration	CSI-RS resource Type		Aperiodic	Aperiodic	Aperiodic
	Number of CSI-RS ports ( $X$ )		4	4	4
	CDM Type		FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )		1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 4, (8,-)	Row 4, (8,-)	Row 4, (8,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)	(13,-)	(13,-)
	CSI-RS interval and offset	slot	8/1	8/1	8/1
NZP CSI-RS for CSI acquisition	CSI-RS resource Type		Aperiodic	Aperiodic	Aperiodic
	Number of CSI-RS ports ( $X$ )		2	2	2
	CDM Type		FD-CDM2	FD-CDM2	FD-CDM2
	Density ( $\rho$ )		1	1	1
	First subcarrier index in the PRB used for CSI-RS ( $k_0, k_1$ )		Row 3 (6,-)	Row 3 (6,-)	Row 3 (6,-)
	First OFDM symbol in the PRB used for CSI-RS ( $l_0, l_1$ )		(13,-)	(13,-)	(13,-)
	NZP CSI-RS-timeConfig interval and offset	slot	8/1	8/1	8/1
CSI-IM configuration	CSI-IM RE pattern		Pattern 1	Pattern 1	Pattern 1
	CSI-IM Resource Mapping ( $k_{CSI-IM}, l_{CSI-IM}$ )		(8,13)	(8,13)	(8,13)
	CSI-IM timeConfig interval and offset	slot	8/1	8/1	8/1
ReportConfigType			Aperiodic	Aperiodic	Aperiodic
CQI-table			Table 1	Table 1	Table 1
reportQuantity			cri-RI-PMI-CQI	cri-RI-PMI-CQI	cri-RI-PMI-CQI
timeRestrictionForChannelMeasurements			not configured	not configured	not configured
timeRestrictionForInterferenceMeasurements			not configured	not configured	not configured
cqi-FormatIndicator			Wideband	Wideband	Wideband
pmi-FormatIndicator			Wideband	Wideband	Wideband
CSI-Report interval and offset		slot	TBD	TBD	TBD
aperiodicTriggeringOffset			0	0	0
Codebook configuration	Codebook Type		typeI-SinglePanel	typeI-SinglePanel	typeI-SinglePanel
	Codebook Mode		1	1	1
	(CodebookConfig-N1, CodebookConfig-N2)		N/A	N/A	N/A
	CodebookSubsetRestriction		TBD	TBD	TBD
	RI Restriction		N/A	N/A	N/A
Physical channel for CSI report			PUSCH	PUSCH	PUSCH
CQI/RI/PMI delay		ms	1.375	1.375	1.375
Maximum number of HARQ transmission			1	1	1
RI Configuration			Fixed RI = 2 and follow RI	Fixed RI = 1 and follow RI	Fixed RI = 1 and follow RI

**Table 8.4.2.2-2: Minimum requirement (TDD)**

	<b>Test 1</b>	<b>Test 2</b>	<b>Test 3</b>
$\gamma_1$	N/A	TBD	TBD
$\gamma_2$	TBD	N/A	TBD

## 9 Demodulation performance requirements for interworking

### 9.1 General

This clause covers the UE demodulation performance requirements for EN-DC, NE-DC, inter-band NR-DC between FR1 and FR2, and inter-band NR CA between FR1 and FR2.

#### 9.1.1 Applicability of requirements

The following applicability rules are specified for demodulation performance requirements for interworking:

- For UEs supporting both SA and NSA,
  - The performance requirements specified in Section 5 will be verified only for SA except for the sustained downlink data rate test specified in Section 5.5
  - The sustained downlink data rate tests specified in Section 5.5 for SA and in Section 9.4B are verified separately.
- The FR1 EN-DC test cases with the NR TDD DL-UL configurations which are not aligned with LTE's can be tested on the corresponding EN-DC band combinations where UE supports simultaneous transmission and reception.

#### 9.1.2 LTE Pcell setup

This sub-clause provides the parameters for LTE Pcell during the demodulation performance test for EN-DC unless otherwise stated. For EN-DC with multiple LTE carriers or bands, randomly selected one carrier or band that can be used for Pcell as LTE Pcell for the connection setup.

##### 9.1.2.1 FDD

The parameters specified in Table 9.1.2.1-1 and Table 9.1.2.1-2 are used to setup an LTE Pcell. One of test setup in Table 9.1.2.1-2 will be selected for the LTE Pcell depending on the maximum bandwidth of an LTE carrier for all the EN-DC band combinations supported by the UE.

The measurement channels in Table 9.1.2.1-2 and OCNG pattern OP.1 FDD are specified in TS 36.101 [4]. The physical channel setup with downlink power allocation is according to TS36.101 [4, Annex C.3.2].

**Table 9.1.2.1-1: Common Test Parameters (FDD)**

Parameter	Unit	Value
Cyclic prefix		Normal
Physical Cell ID		0
Number of PDCCH symbols	symbols	1
PHICH Ng (Note 1)		1
PHICH duration		Normal
Number of HARQ processes per component carrier	Processes	[8]
Maximum number of HARQ transmission		[4]
Redundancy version coding sequence		{0,0,1,2} for [64QAM]
Propagation condition		Static propagation condition No external noise sources are applied
Transmission mode		[3]
Transmission time difference between LTE cell and NR cell(s)	μs	0
Antenna configuration		2x2
Codebook subset restriction		[10]
Symbols for all unused Res		OCNG in Annex A.5

**Table 9.1.2.1-2: Specific Test Parameters (FDD [64QAM])**

Test setup	Bandwidth (MHz)	Downlink power allocation (dB)		
		$\rho_A$	$\rho_B$	$\sigma$
1	5	-3	-3	0
2	10	-3	-3	0
3	15	-3	-3	0
4	20	-3	-3	0

### 9.1.2.2 TDD

The parameters specified in Table 9.1.2.2-1 and Table 9.1.2.2-2 are used to setup an LTE Pcell. One of test setup in Table 9.1.2.2-2 will be selected for the LTE Pcell depending on the maximum bandwidth of an LTE carrier for all the EN-DC band combinations supported by the UE.

The measurement channels in Table 9.1.2.2-2 and OCNG pattern OP.1 TDD are specified in TS36.101 [4]. The physical channel setup with downlink power allocation is according to TS36.101 [4, Annex C.3.2].

**Table 9.1.2.2-1: Common Test Parameters (TDD)**

Parameter	Unit	Value
UL DL configuration		2 (Note1)
Special subframe configuration		7
Number of PDCCH symbols	symbols	1
PHICH Ng (Note 3)		1
PHICH duration		Normal
Cyclic prefix		Normal
Cell ID		0
Maximum number of HARQ transmission		[4]
Redundancy version coding sequence		{0,0,1,2} for [64QAM]
Propagation condition		Static propagation condition No external noise sources are applied
Transmission mode		[3]
Transmission time difference between LTE cell and NR cell(s)	μs	0
Antenna configuration		2x2
Codebook subset restriction		[10]
Symbols for all unused Res		OCNG in Annex A.5
NOTE 1: The start of transmission of LTE frame is delayed by 2 LTE subframes with respect to the start of transmission of NR frame when TDD-TDD EN-DC configuration is configured during the test.		

**Table 9.1.2.2-2: Specific Test Parameters (FDD [64QAM])**

Test setup	Bandwidth (MHz)	Downlink power allocation (dB)		
		$\rho_A$	$\rho_B$	$\sigma$
1	10	-3	-3	0
2	15	-3	-3	0
3	20	-3	-3	0

## 9.2 Void

### 9.2A PDSCH demodulation for CA

#### 9.2A.1 NR CA between FR1 and FR2

### 9.2B PDSCH demodulation for DC

#### 9.2B.1 EN-DC

<Editor note: which NR PDSCH test case(s) will be selected for EN-DC test need FFS.>

##### 9.2B.1.1 EN-DC within FR1

###### 9.2B.1.1.1 PDSCH

The test setup for LTE Pcell is specified in Section 9.1.2. The NR PDSCH demodulation performance requirements for NR are specified in Section 5.2. During the test, only the PDSCH performance on the NR cell(s) shall be verified.

### 9.2B.1.2 EN-DC including FR2 NR carrier only

#### 9.2B.1.2.1 PDSCH

The test setup for LTE Pcell is specified in Section 9.1.2. The NR PDSCH demodulation performance requirements for NR are specified in Section 7.2. During the test, only the PDSCH performance on the NR cell(s) on FR2 carriers shall be verified.

### 9.2B.1.3 EN-DC including FR1 and FR2 NR carriers

The demodulation performance requirements are verified according to Section 9.2B.1.1 for EN-DC with FR1 NR carrier only and Section 9.2B.1.2 for EN-DC with FR2 NR carrier only. During the test for EN-DC with FR2 NR carriers, only demodulation performance requirements on the FR2 carriers are verified. No demodulation requirement for FR1 NR or LTE carriers is specified for EN-DC including FR2 carrier(s).

## 9.2B.2 NR DC between FR1 and FR2

### 9.3 Void

## 9.3A PDCCH demodulation for CA

### 9.3A.1 NR CA between FR1 and FR2

During the test, only the demodulation performance requirements on FR2 carriers are verified. The demodulation performance requirements for NR FR2 are specified in Section 7.3.

## 9.3B PDCCH demodulation for DC

### 9.3B.1 EN-DC

*<Editor note: which NR PDCCH test case(s) will be selected for EN-DC test need FFS.>*

#### 9.3B.1.1 EN-DC within FR1

##### 9.3B.1.1.1 PDCCH

The test setup for LTE Pcell is specified in Section 9.1.2. The NR PDCCH demodulation performance requirements for NR are specified in Section 5.3. During the test, only the PDCCH performance on the single NR cell shall be verified.

#### 9.3B.1.2 EN-DC including FR2 NR carrier only

##### 9.3B.1.2.1 PDCCH

The test setup for LTE Pcell is specified in Section 9.1.2. The NR PDCCH demodulation performance requirements are specified in Section 7.3. During the test, only the PDCCH performance on the single NR cell shall be verified.

#### 9.3B.1.3 EN-DC including FR1 and FR2 NR carriers

The demodulation performance requirements are verified according to Section 9.3B.1.1 for EN-DC with FR1 NR carrier only and Section 9.3B.1.2 for EN-DC with FR2 NR carrier only. During the test for EN-DC with FR2 NR carriers, only demodulation performance requirements on the FR2 carriers are verified. No demodulation requirement for FR1 NR or LTE carriers is specified for EN-DC including FR2 carrier(s).

## 9.3B.2 NR DC between FR1 and FR2

## 9.4 Void

### 9.4A SDR test for CA

#### 9.4A.1 NR CA between FR1 and FR2

During the test, only the demodulation performance requirements on FR2 carriers are verified. The demodulation performance requirements for FR2 are specified in Section 7.5.

## 9.4B SDR test for DC

### 9.4B.1 EN-DC

*<Editor note: which NR SDR test case(s) will be selected for EN-DC test need FFS.>*

#### 9.4B.1.1 EN-DC within FR1

##### 9.4B.1.1.1 SDR test

The test setup for LTE Pcell is specified in Section 9.1.2. The NR SDR tests are specified in [Section 5.5](#). During the test, the PDSCH performance on both the NR cell(s) and LTE cell(s) shall be verified.

#### 9.4B.1.2 EN-DC including FR2 NR carrier

##### 9.4B.1.2.1 SDR test

The test setup for LTE Pcell is specified in Section 9.1.2. The NR PDSCH SDR tests are specified in Section 7.5. During the test, only the PDSCH performance on the NR cell(s) on FR2 carriers is verified.

#### 9.4B.1.3 EN-DC including FR1 and FR2 NR carriers

The SDR tests are verified according to Section 9.4B.1.1 for EN-DC with FR1 NR carrier only and Section 9.4B.1.2 for EN-DC with FR2 NR carrier only. During the test for EN-DC with FR2 NR carriers, only SDR tests on the FR2 carriers are verified. No SDR requirement for FR1 NR or LTE carriers is tested for EN-DC including FR2 carrier(s).

## 9.4B.2 NR DC between FR1 and FR2

## 10 CSI reporting requirements for interworking

### 10.1 General

This clause specifies CSI performance requirements for EN-DC, NE-DC, inter-band NR-DC between FR1 and FR2, and inter-band NR CA between FR1 and FR2.

The definition of frequency ranges (FR1 and FR2) are specified in TS38.101-3 [8, table 5.1-1].

### 10.1.1 Applicability of requirements

*<TBA>*

## 10.2 Void

### 10.2A Reporting of Channel Quality Indicator (CQI) for CA

### 10.2B Reporting of Channel Quality Indicator (CQI) for DC

#### 10.2B.1 EN-DC

*<Editor's note: FFS which test cases from SA will be applied for EN-DC >*

##### 10.2B.1.1 EN-DC within FR1

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR CQI requirements and test configurations defined in Subclause 6.2 apply to NR cell(s).

Unless otherwise stated, only NR requirements on NR cell(s) shall be verified during test.

##### 10.2B.1.2 EN-DC including FR2 NR carrier

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR CQI requirements and test configurations defined in Subclause 8.2 apply to NR cell(s).

Unless otherwise stated, only NR requirements on NR cell(s) shall be verified during test.

##### 10.2B.1.3 EN-DC including FR1 and FR2 NR carriers

## 10.3 Void

### 10.3A Reporting of Precoding Matrix Indicator (PMI) for CA

### 10.3B Reporting of Precoding Matrix Indicator (PMI) for DC

#### 10.3B.1 EN-DC

*<Editor's note: FFS which test cases from SA will be applied for EN-DC >*

##### 10.3B.1.1 EN-DC within FR1

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR PMI requirements and test configurations defined in Subclause 6.3 apply to NR cell(s).

Unless otherwise stated, only NR requirements on NR carrier(s) shall be verified during test.

##### 10.3B.1.2 EN-DC including NR FR2 carrier

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR PMI requirements and test configurations defined in Subclause 8.3 apply to NR cell(s).

Unless otherwise stated, only NR requirements on NR cell(s) shall be verified during test.

##### 10.3B.1.3 EN-DC including FR1 and FR2 NR carriers

## 10.4 Void

### 10.4A Reporting of Rank Indicator (RI) for CA

### 10.4B Reporting of Rank Indicator (RI) for DC

#### 10.4B.1 EN-DC

*<Editor's note: FFS which test cases from SA will be applied for EN-DC >*

##### 10.4B.1.1 EN-DC within FR1

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR RI requirements and test configurations defined in Subclause 6.4 apply to NR cell(s).

Unless otherwise stated, only NR requirements on NR cell(s) shall be verified during test.

##### 10.4B.1.2 EN-DC including NR FR2 carrier

Unless otherwise stated, the configuration of LTE Pcell specified in [X] applies to LTE carrier.

Unless otherwise stated, NR RI requirements and test configurations defined in Subclause 8.4 apply to NR cell(s) for EN-DC operation with NR carrier(s) in FR2.

Unless otherwise stated, only NR requirements on NR cell(s) shall be verified during test.

##### 10.4B.1.3 EN-DC including FR1 and FR2 NR carriers

## Annex A (normative): Measurement channels

### A.1 General

#### A.1.1 Throughput definition

The throughput values defined in the measurement channels specified in Annex A, are calculated and are valid per codeword. For multi-codeword transmissions, the throughput referenced in the minimum requirements is the sum of throughputs of all codewords.

#### A.1.2 TDD UL-DL patterns for FR1

TDD UL-DL patterns configurations for performance requirements are provided in Tables A.1.2-1, A.1.2-2, and A.1.2-3.

**Table A.1.2-1: TDD UL-DL pattern for SCS 15 kHz**

Parameter	Unit	UL-DL pattern	
		FR1.15-1	
TDD Slot Configuration pattern (Note 1)		DDDSU	
Special Slot Configuration (Note 2)		10D+2G+2U	
UL-DL configuration ( <i>tdd-UL-DL-ConfigurationCommon</i> )	<i>referenceSubcarrierSpacing</i> <i>dl-UL-TransmissionPeriodicity</i> <i>nrofDownlinkSlots</i> <i>nrofDownlinkSymbols</i> <i>nrofUplinkSlot</i> <i>nrofUplinkSymbols</i>	kHz ms — — — —	15 5 3 10 1 2
K1 value (PDSCH-to-HARQ-timing-indicator)			[4] if mod(i,5) = 0 [3] if mod(i,5) = 1 [2] if mod(i,5) = 2 [6] if mod(i,5) = 3
Note 1: D denotes a slot with all DL symbols; S denotes a slot with a mix of DL, UL and guard symbols; U denotes a slot with all UL symbols. The field is for information. Note 2: D, G, U denote DL, guard and UL symbols, respectively. The field is for information. Note 3: i is the slot index per frame; i = {0,...,9}			

Table A.1.2-2: TDD UL-DL pattern for SCS 30 kHz

Parameter	Unit	UL-DL pattern					
		FR1.30-1	FR1.30-2	FR1.30-3	FR1.30-4	FR1.30-5	FR1.30-6
TDD Slot Configuration pattern (Note 1)		7DS2U	DDDSU	DDDSUDDSUU	SU	DDSU	DS <sub>1</sub> S <sub>2</sub> U
Special Slot Configuration (Note 2)		6D+4G+4U	10D+2G+2U	10D+2G+2U	12D+2G+0U	10D+2G+2U	S1: 10D+2G+2U S2: 12D+2G+0U
UL-DL configuration ( <i>tdd-UL-DL-ConfigurationCommon</i> )	<i>referenceSubcarrierSpacing</i>	kHz	30	30	30	30	30
	<i>dl-UL-TransmissionPeriodicity</i>	ms	5	2.5	2.5	1	2
	<i>nrofDownlinkSlots</i>		7	3	3	0	2
	<i>nrofDownlinkSymbols</i>		6	10	10	12	10
	<i>nrofUplinkSlot</i>		2	1	1	1	0
	<i>nrofUplinkSymbols</i>		4	2	2	0	2
UL-DL configuration2 ( <i>tdd-UL-DL-ConfigurationCommon2</i> )	<i>referenceSubcarrierSpacing</i>	kHz	N/A	N/A	30	N/A	N/A
	<i>dl-UL-TransmissionPeriodicity</i>	ms	N/A	N/A	2.5	N/A	N/A
	<i>nrofDownlinkSlots</i>		N/A	N/A	2	N/A	N/A
	<i>nrofDownlinkSymbols</i>		N/A	N/A	10	N/A	N/A
	<i>nrofUplinkSlot</i>		N/A	N/A	2	N/A	N/A
	<i>nrofUplinkSymbols</i>		N/A	N/A	2	N/A	N/A
K1 value (PDSCH-to-HARQ-timing-indicator)		[7] if mod(i,10) = 0 [6] if mod(i,10) = 1 [5] if mod(i,10) = 2 [5] if mod(i,10) = 3 [4] if mod(i,10) = 4 [3] if mod(i,10) = 5 [3] if mod(i,10) = 6 [2] if mod(i,10) = 7	[4] if mod(i,5) = 0 [3] if mod(i,5) = 1 [2] if mod(i,5) = 2 [6] if mod(i,5) = 3	[4] if mod(i,10) = 0 [3] if mod(i,10) = 1 [2] if mod(i,10) = 2 [5] if mod(i,10) = 3 [3] if mod(i,10) = 5 [3] if mod(i,10) = 6 [2] if mod(i,10) = 7	[3] if mod(i,2) = 0 [2] if mod(i,4) = 1 [5] if mod(i,4) = 3	[3] if mod(i,4) = 0 [2] if mod(i,4) = 1 [5] if mod(i,4) = 3	[3] if mod(i,4) = 0 [2] if mod(i,4) = 1 [3] if mod(i,4) = 3
<p>Note 1: D denotes a slot with all DL symbols; S denotes a slot with a mix of DL, UL and guard symbols; U denotes a slot with all UL symbols. The field is for information.</p> <p>Note 2: D, G, U denote DL, guard and UL symbols, respectively. The field is for information.</p> <p>Note 3: i is the slot index per frame; i = {0,...,19}</p>							

### A.1.3 TDD UL-DL patterns for FR2

TDD UL-DL patterns configurations for performance requirements are provided in Tables A.1.3-1, A.1.3-2.

**Table A.1.3-1: TDD UL-DL pattern for SCS 60 kHz**

Parameter	Unit	UL-DL pattern	
		FR2.60-1	
TDD Slot Configuration pattern (Note 1)		DDSU	
Special Slot Configuration (Note 2)		11D+3G+0U	
UL-DL configuration ( <i>tdd-UL-DL-ConfigurationCommon</i> )	<i>referenceSubcarrierSpacing</i>	kHz	60
	<i>dl-UL-TransmissionPeriodicity</i>	ms	1
	<i>nrofDownlinkSlots</i>		2
	<i>nrofDownlinkSymbols</i>		11
	<i>nrofUplinkSlot</i>		1
	<i>nrofUplinkSymbols</i>		0
K1 value (PDSCH-to-HARQ-timing-indicator)			K1 = [3] if mod(i,4) = 0 K1 = [2] if mod(i,4) = 1 K1 = [5] if mod(i,4) = 3
Note 1: D denotes a slot with all DL symbols; S denotes a slot with a mix of DL, UL and guard symbols; U denotes a slot with all UL symbols. The field is for information.			
Note 2: D, G, U denote DL, guard and UL symbols, respectively. The field is for information.			
Note 3: i is the slot index per frame; i = {0,...,39}			

**Table A.3.1-5: TDD UL-DL pattern for SCS 120 kHz**

Parameter	Unit	UL-DL pattern	
		FR2.120-1	FR2.120-2
TDD Slot Configuration pattern (Note 1)		DDDSU	DDSU
Special Slot Configuration (Note 2)		10D+2G+2U	11D+3G+0U
UL-DL configuration ( <i>tdd-UL-DL-ConfigurationCommon</i> )	<i>referenceSubcarrierSpacing</i>	kHz	120
	<i>dl-UL-TransmissionPeriodicity</i>	ms	0.625
	<i>nrofDownlinkSlots</i>		3
	<i>nrofDownlinkSymbols</i>		10
	<i>nrofUplinkSlot</i>		1
	<i>nrofUplinkSymbols</i>		2
K1 value (PDSCH-to-HARQ-timing-indicator)		K1 = [4] if mod(i,5) = 0 K1 = [3] if mod(i,5) = 1 K1 = [2] if mod(i,5) = 2 K1 = [6] if mod(i,5) = 3	K1 = [3] if mod(i,4) = 0 K1 = [2] if mod(i,4) = 1 K1 = [5] if mod(i,4) = 3
Note 1: D denotes a slot with all DL symbols; S denotes a slot with a mix of DL, UL and guard symbols; U denotes a slot with all UL symbols. The field is for information.			
Note 2: D, G, U denote DL, guard and UL symbols, respectively. The field is for information.			
Note 3: i is the slot index per frame; i = {0,...,79}			

## A.2 Void

<Editor's note: Clause A.2 is a placeholder for UL Measurement channels>

## A.3 DL reference measurement channels

### A.3.1 General

The transport block size (TBS) determination procedure is described in TS 38.214 [12, Section 5.1.3.2].

[Unless otherwise stated, no user data is scheduled on slot #0 within 20 ms in order to avoid SSB and PDSCH transmissions in one slot and simplify test configuration.]

### A.3.2 Reference measurement channels for PDSCH performance requirements

For PDSCH reference channels if more than one Code Block is present, an additional CRC sequence of L = 24 Bits is attached to each Code Block (otherwise L = 0 Bit).

#### A.3.2.1 FDD

##### A.3.2.1.1 Reference measurement channels for SCS 15 kHz FR1

**Table A.3.2.1.1-1: PDSCH Reference Channel for FDD (QPSK)**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 1-1.1 FDD	R.PDSCH. 1-1.2 FDD	R.PDSCH. 1-1.3 FDD	R.PDSCH. 1-1.4 FDD
Channel bandwidth	MHz	10	10	10	10
Subcarrier spacing	kHz	15	15	15	15
Number of allocated resource blocks	PRBs	52	6	52	52
Number of consecutive PDSCH symbols		12	12	7	[9]
Allocated slots per 2 frames	Slots	19	19	19	19
MCS table		64QAM	64QAM	64QAM	64QAM
MCS index		4	4	4	4
Modulation		QPSK	QPSK	QPSK	QPSK
Target Coding Rate		0.30	0.30	0.30	0.30
Number of MIMO layers		1	1	1	1
Number of DMRS rEs		18	12	12	12
Overhead for TBS determination		0	0	0	18
Information Bit Payload per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	Bits	3904	480	2280	[2472]
Transport block CRC per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	Bits	24	16	16	16
Number of Code Blocks per Slot					
For Slot i = 0	CBs	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	CBs	1	1	1	1
Binary Channel Bits Per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 10, 11	Bits	12480	1512	6864	[7760]
For Slots i = 3,..., 9, 12, ..., 19	Bits	13104	1584	7488	[8384]
Max. Throughput averaged over 2 frames	Mbps	3.709	0.456	2.166	[2.348]
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.1.1-2: PDSCH Reference Channel for FDD (16QAM)**

<b>Parameter</b>	<b>Unit</b>	<b>Value</b>			
Reference channel		R.PDSCH. 1-2.1 FDD	R.PDSCH. 1-2.2 FDD	R.PDSCH. 1-2.3 FDD	R.PDSCH. 1-2.4 FDD
Channel bandwidth	MHz	10	10	10	10
Subcarrier spacing	kHz	15	15	15	15
Number of allocated resource blocks	PRBs	52	52	52	52
Number of consecutive PDSCH symbols		12	12	12	12
Allocated slots per 2 frames	Slots	19	19	19	19
MCS table		64QAM	64QAM	64QAM	64QAM
MCS index		13	13	13	13
Modulation		16QAM	16QAM	16QAM	16QAM
Target Coding Rate		0.48	0.48	0.48	0.48
Number of MIMO layers		1	2	3	4
Number of DMRS rEs		12	12	24	24
Overhead for TBS determination		0	0	0	0
Information Bit Payload per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	Bits	13064	26120	35856	48168
Transport block CRC per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	Bits	24	24	24	24
Number of Code Blocks per Slot					
For Slot i = 0	CBs	N/A	N/A	N/A	N/A
For Slots i = 1,..., 19	CBs	2	4	5	6
Binary Channel Bits Per Slot					
For Slot i = 0	Bits	N/A	N/A	N/A	N/A
For Slots i = 10, 11	Bits	26208	52416	71136	94848
For Slots i = 1,..., 9, 12, ..., 19	Bits	27456	54912	74880	99840
Max. Throughput averaged over 2 frames	Mbps	12.411	24.814	34.063	45.760
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.1.1-3: PDSCH Reference Channel for FDD (64QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 1-3.1 FDD				
Channel bandwidth	MHz	10				
Subcarrier spacing	kHz	15				
Number of allocated resource blocks	PRBs	52				
Number of consecutive PDSCH symbols		12				
Allocated slots per 2 frames	Slots	19				
MCS table		64QAM				
MCS index		19				
Modulation		64QAM				
Target Coding Rate		0.51				
Number of MIMO layers		2				
Number of DMRS rEs		12				
Overhead for TBS determination		0				
Information Bit Payload per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	42016				
Transport block CRC per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	24				
Number of Code Blocks per Slot						
For Slot i = 0	CBs	N/A				
For Slots i = 1,..., 19	CBs	5				
Binary Channel Bits Per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 10, 11	Bits	78624				
For Slots i = 1,..., 9, 12, ..., 19	Bits	82368				
Max. Throughput averaged over 2 frames	Mbps	39.915				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

**Table A.3.2.1.1-4: PDSCH Reference Channel for FDD (256QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 1-4.1 FDD				
Channel bandwidth	MHz	10				
Subcarrier spacing	kHz	15				
Number of allocated resource blocks	PRBs	52				
Number of consecutive PDSCH symbols		12				
Allocated slots per 2 frames	Slots	19				
MCS table		256QAM				
MCS index		24				
Modulation		256QAM				
Target Coding Rate		0.82				
Number of MIMO layers		1				
Number of DMRS rEs		12				
Overhead for TBS determination		0				
Information Bit Payload per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	45096				
Transport block CRC per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	24				
Number of Code Blocks per Slot						
For Slot i = 0	CBs	N/A				
For Slots i = 1,..., 19	CBs	6				
Binary Channel Bits Per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 10, 11	Bits	52416				
For Slots i = 1,..., 9, 12, ..., 19	Bits	54912				
Max. Throughput averaged over 2 frames	Mbps	42.841				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

**Table A.3.2.1.1-5: PDSCH Reference Channel for FDD and CSI-RS overlapped with PDSCH**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 1-5.1 FDD				
Channel bandwidth	MHz	10				
Subcarrier spacing	kHz	15				
Number of allocated resource blocks	PRBs	52				
Number of consecutive PDSCH symbols		12				
Allocated slots per 2 frames	Slots	19				
MCS table		64QAM				
MCS index		13				
Modulation		16QAM				
Target Coding Rate		0.48				
Number of MIMO layers		2				
Number of DMRS rEs		12				
Overhead for TBS determination		0				
Information Bit Payload per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	26120				
Transport block CRC per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	24				
Number of Code Blocks per Slot						
For Slot i = 0	CBs	N/A				
For Slots i = 1,..., 19	CBs	4				
Binary Channel Bits Per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 5, 15	Bits	50752				
For Slots i = 10	Bits	48256				
For Slots i = 11	Bits	52416				
For Slots i = 1,...,4,6,..., 9,12,...14,16,...,19	Bits	54912				
Max. Throughput averaged over 2 frames	Mbps	24.814				

Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms  
Note 2: Slot i is slot index per 2 frames

**Table A.3.2.1.1-6: PDSCH Reference Channel for FDD PMI reporting requirements**

Parameter	Unit	Value		
Reference channel		R.PDSCH. 1-6.1 FDD	R.PDSCH. 1-6.2 FDD	
Channel bandwidth	MHz	10	10	
Subcarrier spacing	kHz	15	15	
Number of allocated resource blocks	PRBs	52	52	
Number of consecutive PDSCH symbols		12	12	
Allocated slots per 2 frames	Slots	15	15	
MCS table		64QAM	64QAM	
MCS index		13	13	
Modulation		16QAM	16QAM	
Target Coding Rate		0.48	0.48	
Number of MIMO layer		1	2	
Number of DMRS rEs (Note 3)		24	24	
Overhead for TBS determination		0	0	
Information Bit Payload per Slot				
For Slot i = 0	Bits	N/A	N/A	
For CSI Slots i, if mod (i,5) =1, i={0,...,19}		N/A	N/A	
For Non CSI-RS Slot i, if mod (i,5) ={0,2,3,4}, i={1,...,19}	Bits	12040	24072	
Transport block CRC per Slot				
For Slot i = 0	Bits	N/A	N/A	
For CSI Slots i, if mod (i,5) =1, i={0,...,19}		N/A	N/A	
For Non CSI-RS Slot i, if mod (i,5) ={0,2,3,4}, i={1,...,19}	Bits	24	24	
Number of Code Blocks per Slot				
For Slot i = 0	CBs	N/A	N/A	
For CSI Slots i, if mod (i,5) =1, i={0,...,19}		N/A	N/A	
For Non CSI-RS Slot i, if mod (i,5) ={0,2,3,4}, i={1,...,19}	CBs	2	3	
Binary Channel Bits Per Slot				
For Slot i = 0	Bits	N/A	N/A	
For CSI Slots i, if mod (i,5) =1, i={0,...,19}		N/A	N/A	
For Slots i = 10	Bits	23712	47424	
For Non CSI-RS Slot i, if mod (i,5) ={0,2,3,4}, i={1,...,9,11,...,19}	Bits	24960	49920	
Max. Throughput averaged over 2 frames	Mbps	9.030	18.054	
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms				
Note 2: Slot i is slot index per 2 frames				
Note 3: Number of DMRS rEs includes the overhead of the DM-RS CDM groups without data				

## A.3.2.1.2 Reference measurement channels for SCS 30 kHz FR1

**Table A.3.2.1.2-1: PDSCH Reference Channel for FDD (64QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 2-1.1 FDD				
Channel bandwidth	MHz	20				
Subcarrier spacing	kHz	30				
Number of allocated resource blocks	PRBs	51				
Number of consecutive PDSCH symbols		12				
Allocated slots per 2 frames	Slots	39				
MCS table		64QAM				
MCS index		19				
Modulation		64QAM				
Target Coding Rate		0.51				
Number of MIMO layers		2				
Number of DMRS rEs		12				
Overhead for TBS determination		0				
Information Bit Payload per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	40976				
Transport block CRC per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 1,..., 19	Bits	24				
Number of Code Blocks per Slot						
For Slot i = 0	CBs	N/A				
For Slots i = 1,..., 19	CBs	5				
Binary Channel Bits Per Slot						
For Slot i = 0	Bits	N/A				
For Slots i = 10, 11	Bits	77112				
For Slots i = 1,..., 9, 12, ..., 19	Bits	80784				
Max. Throughput averaged over 2 frames	Mbps	79.903				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

### A.3.2.2 TDD

A.3.2.2.1 Reference measurement channels for SCS 15 kHz FR1

A.3.2.2.2 Reference measurement channels for SCS 30 kHz FR1

**Table A.3.2.2.2-1: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-1 (QPSK)**

Parameter	Unit	Value		
Reference channel		R.PDSCH. 2-1.1 TDD	R.PDSCH. 2-1.2 TDD	R.PDSCH. 2-1.3 TDD
Channel bandwidth	MHz	40	40	40
Subcarrier spacing	kHz	30	30	30
Allocated resource blocks	PRBs	106	6	106
Number of consecutive PDSCH symbols				
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		4	4	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12	12	7
Allocated slots per 2 frames		31	31	[27]
MCS table		64QAM	64QAM	64QAM
MCS index		4	4	4
Modulation		QPSK	QPSK	QPSK
Target Coding Rate		0.30	0.30	0.30
Number of MIMO layers		1	1	1
Number of DMRS rEs				
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		6	6	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		18	12	12
Overhead for TBS determination		0	0	0
Information Bit Payload per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	2664	144	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	8064	480	4608
Transport block CRC per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	16	16	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	24	16	24
Number of Code Blocks per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	CBs	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	CBs	1	1	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	CBs	2	1	2
Binary Channel Bits Per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A
For Slots i = 20, 21	Bits	25440	1512	13992
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	8904	504	[N/A]
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,19,22,...,39}	Bits	26712	1584	15264
Max. Throughput averaged over 2 frames	Mbps	11.419	0.677	[6.221]

Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms

Note 2: Slot i is slot index per 2 frames

**Table A.3.2.2.2-2: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-1 (16QAM)**

Parameter	Unit	Value			
		R.PDSCH. 2-2.1 TDD	R.PDSCH. 2-2.2 TDD	R.PDSCH. 2-2.3 TDD	R.PDSCH. 2-2.4 TDD
Reference channel					
Channel bandwidth	MHz	40	40	40	40
Subcarrier spacing	KHz	30	30	30	30
Allocated resource blocks	PRBs	106	106	106	106
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		4	4	4	4
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12	12	12	12
Allocated slots per 2 frames		31	31	31	31
MCS table		64QAM	64QAM	64QAM	64QAM
MCS index		13	13	13	13
Modulation		16QAM	16QAM	16QAM	16QAM
Target Coding Rate		0.48	0.48	0.48	0.48
Number of MIMO layers		1	2	3	4
Number of DMRS rEs					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		6	6	12	12
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12	12	24	24
Overhead for TBS determination		0	0	0	0
Information Bit Payload per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	8456	16896	22032	29192
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	26632	53288	73776	98376
Transport block CRC per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	24	24	24	24
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	24	24	24	24
Number of Code Blocks per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	CBs	N/A	N/A	N/A	N/A
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	CBs	1	2	3	4
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	CBs	4	7	10	13
Binary Channel Bits Per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	N/A	N/A
For Slots i = 20, 21	Bits	53424	106848	144008	193344
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	17808	35616	45792	61056
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,19,22,...,39}	Bits	55968	111936	152640	203520
Max. Throughput averaged over 2 frames	Mbps	37.644	75.318	104.719	138.646
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.2.2-3: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-1 (64QAM)**

Parameter	Unit	Value		
Reference channel		R.PDSCH. 2-3.1 TDD	R.PDSCH. 2-3.2 TDD	
Channel bandwidth	MHz	40	20	
Subcarrier spacing	kHz	30	30	
Allocated resource blocks	PRBs	106	51	
Number of consecutive PDSCH symbols				
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		4	4	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12	12	
Allocated slots per 2 frames		31	31	
MCS table		64QAM	64QAM	
MCS index		19	19	
Modulation		64QAM	64QAM	
Target Coding Rate		0.51	0.51	
Number of MIMO layers		2	2	
Number of DMRS rEs				
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		6	6	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12	12	
Overhead for TBS determination		0	0	
Information Bit Payload per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	27144	13064	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	83976	40976	
Transport block CRC per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	24	24	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	24	24	
Number of Code Blocks per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	CBs	N/A	N/A	
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	CBs	3	2	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	CBs	10	5	
Binary Channel Bits Per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A	N/A	
For Slots i = 20, 21	Bits	160272	77112	
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	53424	25704	
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,19,22,...,39}	Bits	167904	80784	
Max. Throughput averaged over 2 frames	Mbps	118.796	57.930	
Note 1:	SS/PBCH block is transmitted in slot #0 with periodicity 20 ms			
Note 2:	Slot i is slot index per 2 frames			

**Table A.3.2.2.2-4: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-1 (256QAM)**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 2-4.1 TDD			
Channel bandwidth	MHz	40			
Subcarrier spacing	kHz	30			
Allocated resource blocks	PRBs	106			
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		4			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12			
Allocated slots per 2 frames		31			
MCS table		256QAM			
MCS index		24			
Modulation		256QAM			
Target Coding Rate		0.82			
Number of MIMO layers		1			
Number of DMRS rEs					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		6			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12			
Overhead for TBS determination		0			
Maximum number of HARQ transmissions		4			
Information Bit Payload per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	29192			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	92200			
Transport block CRC per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	24			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	24			
Number of Code Blocks per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	CBs	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	CBs	3			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	CBs	11			
Binary Channel Bits Per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slots i = 20, 21	Bits	106848			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	35616			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,19,22,...,39}	Bits	111936			
Max. Throughput averaged over 2 frames	Mbps	130.308			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.2.2-5: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-2**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 2-5.1 TDD			
Channel bandwidth	MHz	40			
Subcarrier spacing	kHz	30			
Allocated resource blocks	PRBs	106			
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}		8			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,39}		12			
Allocated slots per 2 frames		31			
MCS table		64QAM			
MCS index		4			
Modulation		QPSK			
Target Coding Rate		0.30			
Number of MIMO layers		1			
Number of DMRS rEs					
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}		12			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,39}		12			
Overhead for TBS determination		0			
Information Bit Payload per Slot					
For Slot 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}	Bits	5376			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,39}	Bits	8456			
Transport block CRC per Slot					
For Slot 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}	Bits	24			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,39}	Bits	24			
Number of Code Blocks per Slot					
For Slot 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,39}	CBs	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}	CBs	1			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,39}	CBs	2			
Binary Channel Bits Per Slot					
For Slot 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,39}	Bits	N/A			
For Slot i = 20, 21	Bits	26712			
For Slot i, if mod(i, 5) = 3 for i from {0,...,39}	Bits	17808			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,19,22,...,39}	Bits	27984			
Max. Throughput averaged over 2 frames	Mbps	11.875			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

Table A.3.2.2.2-6: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-3

Parameter	Unit	Value			
Reference channel		R.PDSCH. 2-6.1 TDD			
Channel bandwidth	MHz	40			
Subcarrier spacing	kHz	30			
Allocated resource blocks	PRBs	106			
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}		8			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,39}		12			
Allocated slots per 2 frames		27			
MCS table		64QAM			
MCS index		4			
Modulation		QPSK			
Target Coding Rate		0.30			
Number of MIMO layers		1			
Number of DMRS rEs					
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}		12			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,39}		12			
Overhead for TBS determination		0			
Maximum number of HARQ transmissions		4			
Information Bit Payload per Slot					
For Slot 0 and Slot i, if mod(i, 10) = {4,8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}	Bits	5376			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,39}	Bits	8456			
Transport block CRC per Slot					
For Slot 0 and Slot i, if mod(i, 10) = {4,8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}	Bits	24			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,39}	Bits	24			
Number of Code Blocks per Slot					
For Slot 0 and Slot i, if mod(i, 10) = {4,8,9} for i from {0,...,39}	CBs	N/A			
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}	CBs	1			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,39}	CBs	2			
Binary Channel Bits Per Slot					
For Slot 0 and Slot i, if mod(i, 10) = {4,8,9} for i from {0,...,39}	Bits	N/A			
For Slot i = 20, 21	Bits	26712			
For Slot i, if mod(i, 10) = {3,7} for i from {0,...,39}	Bits	17808			
For Slot i, if mod(i, 10) = {0,1,2,5,} for i from {1,...,19,22,...,39}	Bits	27984			
Max. Throughput averaged over 2 frames	Mbps	10.184			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.2.2-7: PDSCH Reference Channel for TDD UL-DL pattern FR1.30-1 and CSI-RS overlapped with PDSCH**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 2-7.1 TDD			
Channel bandwidth	MHz	40			
Subcarrier spacing	kHz	30			
Allocated resource blocks	PRBs	106			
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		4			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12			
Allocated slots per 2 frames		31			
MCS table		64QAM			
MCS index		13			
Modulation		16QAM			
Target Coding Rate		0.48			
Number of MIMO layers		2			
Number of DMRS rEs					
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}		6			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}		12			
Overhead for TBS determination		0			
Information Bit Payload per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	16896			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	53288			
Transport block CRC per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	24			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	Bits	24			
Number of Code Blocks per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	CBs	N/A			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	CBs	2			
For Slot i, if mod(i, 10) = {0,1,2,3,4,5,} for i from {1,...,39}	CBs	7			
Binary Channel Bits Per Slot					
For Slots 0 and Slot i, if mod(i, 10) = {8,9} for i from {0,...,39}	Bits	N/A			
For Slot i, if mod(i, 10) = {0,} for i from {1,...,19,22,...,39}	Bits	103456			
For Slots i = 20	Bits	98368			
For Slots i = 21	Bits	106848			
For Slot i, if mod(i, 10) = 7 for i from {0,...,39}	Bits	35616			
For Slot i, if mod(i, 10) = {1,2,3,4,} for i from {1,...,19,22,...,39}	Bits	111936			
Max. Throughput averaged over 2 frames	Mbps	75.318			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.2.2-8: PDSCH Reference Channel for TDD PMI reporting requirements with UL-DL pattern FR1.30-1 (16QAM)**

Parameter	Unit	Value		
Reference channel		R.PDSCH. 2-8.1 TDD	R.PDSCH. 2-8.2 TDD	
Channel bandwidth	MHz	40	40	
Subcarrier spacing	kHz	30	30	
Allocated resource blocks	PRBs	106	106	
Number of consecutive PDSCH symbols		12	12	
Allocated slots per 2 frames		21	21	
MCS table		64QAM	64QAM	
MCS index		13	13	
Modulation		16QAM	16QAM	
Target Coding Rate		0.48	0.48	
Number of MIMO layers		1	2	
Number of DMRS rEs (Note 3)		24	24	
Overhead for TBS determination		0	0	
Information Bit Payload per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {7,8,9} for i from {0,...,39}	Bits	N/A	N/A	
For CSI-RS Slot i, if mod(i,5) =1 for i from {0,...,39}	Bits	N/A	N/A	
For Slot i = 20	Bits	24576	49176	
For Slot i, if mod(i, 10) = {0,2,3,4,} for i from {1,...,19,22,...,39}	Bits	24576	49176	
Transport block CRC per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {7,8,9} for i from {0,...,39}	Bits	N/A	N/A	
For CSI-RS Slot i, if mod(i,5) =1 for i from {0,...,39}		N/A	N/A	
For Slot i = 20	Bits	24	24	
For Slot i, if mod(i, 10) = {0,2,3,4,} for i from {1,...,19,22,...,39}	Bits	24	24	
Number of Code Blocks per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {7,8,9} for i from {0,...,39}	CBs	N/A	N/A	
For CSI-RS Slot i, if mod(i,5) =1 for i from {0,...,39}		N/A	N/A	
For Slot i = 20	CBs	3	6	
For Slot i, if mod(i, 10) = {0,2,3,4,} for i from {1,...,19,22,...,39}	CBs	3	6	
Binary Channel Bits Per Slot				
For Slots 0 and Slot i, if mod(i, 10) = {7,8,9} for i from {0,...,39}	Bits	N/A	N/A	
For CSI-RS Slot i, if mod(i,5) =1 for i from {0,...,39}	Bits	N/A	N/A	
For Slot i = 20	Bits	48336	96672	
For Slot i, if mod(i, 10) = {0,2,3,4,} for i from {1,...,19,22,...,39}	Bits	50880	101760	
Max. Throughput averaged over 2 frames	Mbps	25.8048	51.6348	
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms				
Note 2: Slot i is slot index per 2 frames				
Note 3: Number of DMRS rEs includes the overhead of the DM-RS CDM groups without data				

A.3.2.2.3 Reference measurement channels for SCS 60 kHz FR1

A.3.2.2.4 Reference measurement channels for SCS 60 kHz FR2

**Table A.3.2.2.4-1: PDSCH Reference Channel for TDD UL-DL pattern FR2.60-1 (16QAM)**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 4-1.1 TDD			
Channel bandwidth	MHz	50			
Subcarrier spacing	kHz	60			
Allocated resource blocks	PRBs	66			
Number of consecutive PDSCH symbols					
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {1,..., 79}		10			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,79}		13			
Allocated slots per 2 frames		59			
MCS table		64QAM			
MCS index		13			
Modulation		16QAM			
Target Coding Rate		0.48			
Number of MIMO layers		2			
Number of DMRS rEs					
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {1,..., 79}		12			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,79}		12			
Overhead for TBS determination		6			
Information Bit Payload per Slot					
For Slots 0 and Slot i, if $\text{mod}(i, 4) = 3$ for i from {0,...,79}	Bits	N/A			
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {1,..., 79}	Bits	25608			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,79}	Bits	34816			
Transport block CRC per Slot					
For Slots 0 and Slot i, if $\text{mod}(i, 4) = 3$ for i from {0,...,79}	Bits	N/A			
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {1,..., 79}	Bits	24			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,79}	Bits	24			
Number of Code Blocks per Slot					
For Slots 0 and Slot i, if $\text{mod}(i, 4) = 3$ for i from {0,...,79}	CBs	N/A			
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {1,..., 79}	CBs	4			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,79}	CBs	5			
Binary Channel Bits Per Slot					
For Slots 0 and Slot i, if $\text{mod}(i, 4) = 3$ for i from {0,...,79}	Bits	N/A			
For Slot i = 40, 41	Bits	69960			
For Slot i, if $\text{mod}(i, 4) = 2$ for i from {4,..., 79}	Bits	54912			
For Slot i, if $\text{mod}(i, 4) = \{0,\}$ for i from {1,...,39,42,...,79}	Bits	73128			
Max. Throughput averaged over 2 frames	Mbps	93.499			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

## A.3.2.2.5 Reference measurement channels for SCS 120 kHz FR2

**Table A.3.2.2.5-1: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-1 (QPSK)**

Parameter	Unit	Value			
Reference channel		R.PDSCH. 5-1.1 TDD			
Channel bandwidth	MHz	100			
Subcarrier spacing	kHz	120			
Allocated resource blocks	PRBs	66			
Number of consecutive PDSCH symbols					
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		9			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		13			
Allocated slots per 2 frames		127			
MCS table		64QAM			
MCS index		4			
Modulation		QPSK			
Target Coding Rate		0.30			
Number of MIMO layers		1			
Number of DMRS rEs					
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		12			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		12			
Overhead for TBS determination		6			
Information Bit Payload per Slot					
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	3624			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	5504			
Transport block CRC per Slot					
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	16			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	24			
Number of Code Blocks per Slot					
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	CBs	N/A			
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	CBs	1			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	CBs	1			
Binary Channel Bits Per Slot					
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A			
For Slots i = 80, 81	Bits	17490			
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	12210			
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,79,82,...,159}	Bits	18282			
Max. Throughput averaged over 2 frames	Mbps	31.942			
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms					
Note 2: Slot i is slot index per 2 frames					

**Table A.3.2.2.5-2: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-1 (16QAM)**

Parameter	Unit	Value		
		R.PDSCH. 5-2.1 TDD	R.PDSCH. 5-2.2 TDD	R.PDSCH. 5-2.3 TDD
Reference channel				
Channel bandwidth	MHz	100	100	200
Subcarrier spacing	kHz	120	120	120
Allocated resource blocks	PRBs	66	66	132
Number of consecutive PDSCH symbols				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		9	9	9
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		13	13	13
Allocated slots per 2 frames		127	127	127
MCS table		64QAM	64QAM	64QAM
MCS index		13	13	13
Modulation		16QAM	16QAM	16QAM
Target Coding Rate		0.48	0.48	0.48
Number of MIMO layers		1	2	2
Number of DMRS rEs				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		12	12	12
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		12	12	12
Overhead for TBS determination		6	6	6
Information Bit Payload per Slot				
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A	N/A	N/A
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	11272	22536	45096
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	17424	34816	69672
Transport block CRC per Slot				
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A	N/A	N/A
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	24	24	24
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	24	24	24
Number of Code Blocks per Slot				
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	CBs	N/A	N/A	N/A
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	CBs	2	3	6
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	CBs	3	5	9
Binary Channel Bits Per Slot				
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A	N/A	N/A
For Slots i = 80, 81	Bits	34980	69960	139920
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	24420	48840	97680
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,79,82,...,159}	Bits	36564	73128	146256
Max. Throughput averaged over 2 frames	Mbps	100.799	201.434	403.096
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms				
Note 2: Slot i is slot index per 2 frames				

**Table A.3.2.2.5-3: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-1 (64QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 5-3.1 TDD				
Channel bandwidth	MHz	100				
Subcarrier spacing	KHz	120				
Allocated resource blocks	PRBs	66				
Number of consecutive PDSCH symbols						
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		9				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		13				
Allocated slots per 2 frames		127				
MCS table		64QAM				
MCS index		18				
Modulation		64QAM				
Target Coding Rate		0.46				
Number of MIMO layers		1				
Number of DMRS rEs						
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}		12				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}		12				
Overhead for TBS determination		6				
Information Bit Payload per Slot						
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	16136				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	25104				
Transport block CRC per Slot						
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	24				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	Bits	24				
Number of Code Blocks per Slot						
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	CBs	N/A				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	CBs	3				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,159}	CBs	3				
Binary Channel Bits Per Slot						
For Slots 0 and Slot i, if mod(i, 5) = 4 for i from {0,...,159}	Bits	N/A				
For Slots i = 80, 81	Bits	52470				
For Slot i, if mod(i, 5) = 3 for i from {0,..., 159}	Bits	36630				
For Slot i, if mod(i, 5) = {0,1,} for i from {1,...,79,82,...,159}	Bits	54846				
Max. Throughput averaged over 2 frames	Mbps	145.062				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

**Table A.3.2.2.5-4: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-2 (QPSK)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 5-4.1 TDD				
Channel bandwidth	MHz	100				
Subcarrier spacing	kHz	120				
Allocated resource blocks	PRBs	6				
Number of consecutive PDSCH symbols						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		10				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		13				
Allocated slots per 2 frames		119				
MCS table		64QAM				
MCS index		4				
Modulation		QPSK				
Target Coding Rate		0.30				
Number of MIMO layers		2				
Number of DMRS rEs						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		12				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		12				
Overhead for TBS determination		6				
Information Bit Payload per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	736				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	1032				
Transport block CRC per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	16				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	16				
Number of Code Blocks per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	CBs	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	CBs	1				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	CBs	1				
Binary Channel Bits Per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i = 80, 81	Bits	3180				
For Slot i, if mod(i, 4) = 2 for i from {4,..., 159}	Bits	2496				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,79,82,...,159}	Bits	3324				
Max. Throughput averaged over 2 frames	Mbps	5.548				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

**Table A.3.2.2.5-5: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-2 (16QAM)**

Parameter	Unit	Value		
		R.PDSCH. 5-5.1 TDD	R.PDSCH. 5-5.2 TDD	
Reference channel				
Channel bandwidth	MHz	100	50	
Subcarrier spacing	kHz	120	120	
Allocated resource blocks	PRBs	66	32	
Number of consecutive PDSCH symbols				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		10	10	
For Slot i, if mod(i, 4) = {0,} for i from {1,..., 159}		13	13	
Allocated slots per 2 frames		119	119	
MCS table		64QAM	64QAM	
MCS index		13	13	
Modulation		16QAM	16QAM	
Target Coding Rate		0.48	0.48	
Number of MIMO layers		2	2	
Number of DMRS rEs				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		12	12	
For Slot i, if mod(i, 4) = {0,} for i from {1,..., 159}		12	12	
Overhead for TBS determination		6	6	
Information Bit Payload per Slot				
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A	N/A	
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	25608	12552	
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	34816	16896	
Transport block CRC per Slot				
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A	N/A	
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	24	24	
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	24	24	
Number of Code Blocks per Slot				
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	CBs	N/A	N/A	
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	CBs	4	2	
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	CBs	5	3	
Binary Channel Bits Per Slot				
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A	N/A	
For Slot i = 80, 81	Bits	69960	33920	
For Slot i, if mod(i, 4) = 2 for i from {4,..., 159}	Bits	54912	26624	
For Slot i, if mod(i, 4) = {0,} for i from {1,...,79,82,...,159}	Bits	73128	35456	
Max. Throughput averaged over 2 frames	Mbps	188.739	91.843	
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms				
Note 2: Slot i is slot index per 2 frames				

**Table A.3.2.2.5-6: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-2 (64QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 5-6.1 TDD				
Channel bandwidth	MHz	100				
Subcarrier spacing	KHz	120				
Allocated resource blocks	PRBs	66				
Number of consecutive PDSCH symbols						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		10				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		13				
Allocated slots per 2 frames		119				
MCS table		64QAM				
MCS index		17				
Modulation		64QAM				
Target Coding Rate		0.43				
Number of MIMO layers		2				
Number of DMRS rEs						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		12				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		12				
Overhead for TBS determination		6				
Information Bit Payload per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	34816				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	47112				
Transport block CRC per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	24				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	24				
Number of Code Blocks per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	CBs	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	CBs	5				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	CBs	6				
Binary Channel Bits Per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i = 80, 81	Bits	114940				
For Slot i, if mod(i, 4) = 2 for i from {4,..., 159}	Bits	82368				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,79,82,...,159}	Bits	109692				
Max. Throughput averaged over 2 frames	Mbps	255.724				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

**Table A.3.2.2.5-6: PDSCH Reference Channel for TDD UL-DL pattern FR2.120-2 (64QAM)**

Parameter	Unit	Value				
Reference channel		R.PDSCH. 5-6.1 TDD				
Channel bandwidth	MHz	100				
Subcarrier spacing	KHz	120				
Allocated resource blocks	PRBs	66				
Number of consecutive PDSCH symbols						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		10				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		13				
Allocated slots per 2 frames		119				
MCS table		64QAM				
MCS index		17				
Modulation		64QAM				
Target Coding Rate		0.43				
Number of MIMO layers		2				
Number of DMRS rEs						
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}		12				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}		12				
Overhead for TBS determination		6				
Information Bit Payload per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	34816				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	47112				
Transport block CRC per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	Bits	24				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	Bits	24				
Number of Code Blocks per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	CBs	N/A				
For Slot i, if mod(i, 4) = 2 for i from {1,..., 159}	CBs	5				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,159}	CBs	6				
Binary Channel Bits Per Slot						
For Slots 0 and Slot i, if mod(i, 4) = 3 for i from {0,...,159}	Bits	N/A				
For Slot i = 80, 81	Bits	114940				
For Slot i, if mod(i, 4) = 2 for i from {4,..., 159}	Bits	82368				
For Slot i, if mod(i, 4) = {0,} for i from {1,...,79,82,...,159}	Bits	109692				
Max. Throughput averaged over 2 frames	Mbps	255.724				
Note 1: SS/PBCH block is transmitted in slot #0 with periodicity 20 ms						
Note 2: Slot i is slot index per 2 frames						

### A.3.3 Reference measurement channels for PDCCH performance requirements

#### A.3.3.1 FDD

##### A.3.3.1.1 Reference measurement channels for SCS 15 kHz FR1

**Table A.3.3.1.1-1: PDCCH Reference Channels (Time domain allocation 1 symbol)**

Parameter	Unit	Value				
Reference channel		R.PDCCH.1-1.1 FDD	R.PDCCH.1-1.2 FDD	R.PDCCH.1-1.3 FDD		
Subcarrier spacing	kHz	15	15	15		
CORESET frequency domain allocation		48	48	48		
CORESET time domain allocation		1	1	1		
Aggregation level		4	4	8		
DCI Format		1_0	1_1	1_1		
Payload (without CRC)	Bits	39	[51]	[51]		

**Table A.3.3.1.1-2: PDCCH Reference Channel (Time domain allocation 2 symbols)**

Parameter	Unit	Value					
Parameter	Unit	R.PDCCH.1-2.1 FDD	R.PDCCH.1-2.2 FDD	R.PDCCH.1-2.3 FDD	R.PDCCH.1-2.4 FDD	R.PDCCH.1-2.5 FDD	R.PDCCH.1-2.6 FDD
Reference channel							
Subcarrier spacing	kHz	15	15	15	15	15	15
CORESET frequency domain allocation		24	24	24	48	48	48
CORESET time domain allocation		2	2	2	2	2	2
Aggregation level		2	4	2	4	8	16
DCI Format		1_0	1_0	1_1	1_1	1_1	1_0
Payload (without CRC)	Bits	39	39	[51]	[51]	[51]	39

##### A.3.3.1.2 Reference measurement channels for SCS 30 kHz FR1

**Table A.3.3.1.2-1: PDCCH Reference Channels (Time domain allocation 1 symbol)**

Parameter	Unit	Value				
Reference channel		R.PDCCH.2-1.1 FDD	R.PDCCH.2-1.2 FDD	R.PDCCH.2-1.3 FDD		
Subcarrier spacing	kHz	30	30	30		
CORESET frequency domain allocation		[102]	[102]	90		
CORESET time domain allocation		1	1	1		
Aggregation level		2	4	8		
DCI Format		1_0	1_1	1_1		
Payload (without CRC)	Bits	41	[53]	[53]		

**Table A.3.3.1.2-2: PDCCH Reference Channel (Time domain allocation 2 symbols)**

Parameter	Unit	Value					
Reference channel		R.PDCCH.2-2.1 FDD					
Subcarrier spacing	kHz	30					
CORESET frequency domain allocation		48					
CORESET time domain allocation		2					
Aggregation level		16					
DCI Format		1_0					
Payload (without CRC)	Bits	41					

### A.3.3.2 TDD

#### A.3.3.2.1 Reference measurement channels for SCS 15 kHz FR1

**Table A.3.3.2.1-1: PDCCH Reference Channels (Time domain allocation 1 symbol)**

Parameter	Unit	Value					
Reference channel		R.PDCCH.1-1.1 TDD	R.PDCCH.1-1.2 TDD	R.PDCCH.1-1.3 TDD			
Subcarrier spacing	kHz	15	15	15			
CORESET frequency domain allocation		48	48	48			
CORESET time domain allocation		1	1	1			
Aggregation level		4	4	8			
DCI Format		1_0	1_1	1_1			
Payload (without CRC)	Bits	[39]	[51]	[51]			

**Table A.3.3.2.1-2: PDCCH Reference Channel (Time domain allocation 2 symbols)**

Parameter	Unit	Value					
Reference channel		R.PDCCH.1-2.1 TDD	R.PDCCH.1-2.2 TDD	R.PDCCH.1-2.3 TDD	R.PDCCH.1-2.4 TDD	R.PDCCH.1-2.5 TDD	R.PDCCH.1-2.6 TDD
Subcarrier spacing	kHz	15	15	15	15	15	15
CORESET frequency domain allocation		24	24	24	48	48	48
CORESET time domain allocation		2	2	2	2	2	2
Aggregation level		2	4	2	4	8	16
DCI Format		1_0	1_0	1_1	1_1	1_1	1_0
Payload (without CRC)	Bits	[39]	[39]	[51]	[51]	[51]	[39]

## A.3.3.2.2 Reference measurement channels for SCS 30 kHz FR1

**Table A.3.3.2.2-1: PDCCH Reference Channels (Time domain allocation 1 symbol)**

Parameter	Unit	Value			
Reference channel		R.PDCCH. 2-1.1 TDD	R.PDCCH. 2-1.2 TDD	R.PDCCH. 2-1.3 TDD	
Subcarrier spacing	kHz	30	30	30	
CORESET frequency domain allocation		[102]	[102]	90	
CORESET time domain allocation		1	1	1	
Aggregation level		2	4	8	
DCI Format		1_0	1_1	1_1	
Payload (without CRC)	Bits	[41]	[53]	[53]	

**Table A.3.3.2.2-2: PDCCH Reference Channel (Time domain allocation 2 symbols)**

Parameter	Unit	Value			
Reference channel		R.PDCCH. 2-2.1 TDD			
Subcarrier spacing	kHz	30			
CORESET frequency domain allocation		48			
CORESET time domain allocation		2			
Aggregation level		16			
DCI Format		1_0			
Payload (without CRC)	Bits	[41]			

## A.3.3.2.3 Reference measurement channels for SCS 60 kHz FR1

## A.3.3.2.4 Reference measurement channels for SCS 60 kHz FR2

## A.3.3.2.5 Reference measurement channels for SCS 120 kHz FR2

**Table A.3.3.2.5-1: PDCCH Reference Channels (Time domain allocation 1 symbol)**

Parameter	Unit	Value			
Reference channel		R.PDCCH. 5-1.1 TDD	R.PDCCH. 5-1.2 TDD	R.PDCCH. 5-1.3 TDD	
Subcarrier spacing	kHz	120	120	120	
CORESET frequency domain allocation		60	60	60	
CORESET time domain allocation		1	1	1	
Aggregation level		2	4	8	
DCI Format		1_0	1_1	1_1	
Payload (without CRC)	Bits	41	[52]	[52]	

**Table A.3.3.2.5-2: PDCCH Reference Channel (Time domain allocation 2 symbols)**

Parameter	Unit	Value					
Reference channel		R.PDCCH.5-2.1 TDD					
Subcarrier spacing	kHz	120					
CORESET frequency domain allocation		60					
CORESET time domain allocation		2					
Aggregation level		16					
DCI Format		1_0					
Payload (without CRC)	Bits	40					

### A.3.4 Reference measurement channels for PBCH demodulation requirements

#### A.3.4.1 Reference measurement channels for FR1

**Table A.3.4.1-1: PBCH Reference Channel**

Parameter	Unit	Value	
Reference channel		[R.PBCH.1]	[R.PBCH.2]
SS/PBCH block subcarrier spacing	kHz	15	30
Modulation		QPSK	QPSK
Target coding rate		56/864	56/864
Payload (without CRC and timing related PBCH payload bits)	bits	24	24

#### A.3.4.2 Reference measurement channels for FR2

**Table A.3.4.2-1: PBCH Reference Channel**

Parameter	Unit	Value	
Reference channels		[R.PBCH.5]	[R.PBCH.6]
SS/PBCH block subcarrier spacing	kHz	120	240
Modulation		QPSK	QPSK
Target coding rate		56/864	56/864
Payload (without CRC and timing related PBCH payload bits)	bits	24	24

## A.4 CSI reference measurement channels

This section defines the DL signal applicable to the reporting of channel status information (Clause X).

Tables in this section specifies the mapping of CQI index to Information Bit payload, which complies with the CQI definition specified in TS 38.214 [12, Section 5.2.2.1] and with MCS definition specified in TS 38.214 [12, Section 5.1.3].

**Table A.4-1: Mapping of CQI Index to Information Bit payload (CQI table 1)**

TBS Scheme				TBS.1-1	TBS.1-2				
MCS table				64QAM					
Number of allocated PDSCH resource blocks		66		66					
Number of consecutive PDSCH symbols		12		12					
Number of PDSCH MIMO layers		1		2					
Number of DMRS rEs (Note 1)		24		24					
Overhead for TBS determination		6		6					
Available RE-s				7920	7920				
CQI index	Spectral efficiency	MCS index	Modulation	Information Bit Payload per Slot					
0	OOR	OOR	OOR	N/A	N/A				
1	0.1523	0	QPSK	1800	3624				
2	0.2344	0		1800	3624				
3	0.3770	2		2856	5640				
4	0.6016	4		4480	8968				
5	0.8770	6		6528	13064				
6	1.1758	8		8712	17928				
7	1.4766	11	16QAM	11016	22032				
8	1.9141	13		14343	28680				
9	2.4063	15		17928	35856				
10	2.7305	18	64QAM	20496	40976				
11	3.3223	20		25104	50184				
12	3.9023	22		29192	58384				
13	4.5234	24		33816	67584				
14	5.1152	26		38936	77896				
15	5.5547	28		42016	83976				

Note 1: Number of DMRS rEs includes the overhead of the DM-RS CDM groups without data

**Table A.4-2: Mapping of CQI Index to Information Bit payload (CQI table 2)**

TBS Scheme				TBS.2-1	TBS.2-2	TBS.2-3	TBS.2-4		
MCS table				256QAM					
Number of allocated PDSCH resource blocks		52		52		106		106	
Number of consecutive PDSCH symbols		12		12		12		12	
Number of PDSCH MIMO layers		1		2		1		2	
Number of DMRS rEs (Note 1)		24		24		24		24	
Overhead for TBS determination		0		0		0		0	
Available RE-s for PDSCH				7920	7920	12720	12720		
CQI index	Spectral efficiency	MCS index	Modulation	Information Bit Payload per Slot					
0	OOR	OOR	OOR	N/A	N/A	N/A	N/A		
1	0.1523	0	QPSK	1480	2976	2976	5896		
2	0.3770	1		2408	4744	4744	9480		
3	0.8770	3		5504	11016	11016	22536		
4	1.4766	5	16QAM	9224	18432	18960	37896		
5	1.9141	7		12040	24072	24576	49176		
6	2.4063	9		15112	30216	30728	61480		
7	2.7305	11	64QAM	16896	33816	34816	69672		
8	3.3223	13		20496	40976	42016	83976		
9	3.9023	15		24576	49176	49176	98376		
10	4.5234	17		28168	56368	57376	114776		
11	5.1152	19		31752	63528	65576	131176		
12	5.5547	21	256QAM	34816	69672	69672	139376		
13	6.2266	23		38936	77896	79896	159880		
14	6.9141	25		43032	86040	88064	176208		
15	7.4063	27		46104	92200	94248	188576		

Note 1: Number of DMRS rEs includes the overhead of the DM-RS CDM groups without data

## A.5 OFDMA Channel Noise Generator (OCNG)

### A.5.1 OCNG Patterns for FDD

#### A.5.1.1 OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused rEs

**Table A.5.1.1-1: OP.1 FDD: Generic OCNG FDD Pattern for all unused rEs**

OCNG Parameters \ OCNG Appliance	Control Region (CORESET)	Data Region
Resources allocated	All unused rEs (Note 1)	All unused rEs (Note 2)
Structure	PDCCH	PDSCH
Content	Uncorrelated pseudo random QPSK modulated data	Uncorrelated pseudo random QPSK modulated data
Transmission scheme for multiple antennas ports transmission	Single Tx port transmission	Spatial multiplexing using any precoding matrix with dimensions same as the precoding matrix for PDSCH
Subcarrier Spacing	Same as for RMC PDCCH in the active BWP	Same as for RMC PDSCH in the active BWP
Power Level	Same as for RMC PDCCH	Same as for RMC PDSCH
Note 1: All unused rEs in the active CORESETS appointed by the search spaces in use. Note 2: Unused available rEs refer to rEs in PRBs not allocated for any physical channels, CORESETs, synchronization signals or reference signals in channel bandwidth.		

### A.5.2 OCNG Patterns for TDD

#### A.5.2.1 OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused rEs

**Table A.5.2.1-1: OP.1 TDD: Generic OCNG TDD Pattern for all unused rEs**

OCNG Parameters \ OCNG Appliance	Control Region (CORESET)	Data Region
Resources allocated	All unused rEs (Note 1)	All unused rEs (Note 2)
Structure	PDCCH	PDSCH
Content	Uncorrelated pseudo random QPSK modulated data	Uncorrelated pseudo random QPSK modulated data
Transmission scheme for multiple antennas ports transmission	Single Tx port transmission	Spatial multiplexing using any precoding matrix with dimensions same as the precoding matrix for PDSCH
Subcarrier Spacing	Same as for RMC PDCCH in the active BWP	Same as for RMC PDSCH in the active BWP
Power Level	Same as for RMC PDCCH	Same as for RMC PDSCH
Note 1: All unused rEs in the active CORESETS appointed by the search spaces in use. Note 2: Unused available rEs refer to rEs in PRBs not allocated for any physical channels, CORESETs, synchronization signals or reference signals in channel bandwidth.		

---

## Annex B (normative): Propagation conditions

### B.1 Static propagation condition

#### B.1.1 UE Receiver with 2Rx

For 1 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{pmatrix} 1 \\ 1 \end{pmatrix}.$$

For 2 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{pmatrix} 1 & j \\ 1 & -j \end{pmatrix}.$$

For 4 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 & 1 & j & j \\ 1 & 1 & -j & -j \end{bmatrix}$$

For 8 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 & 1 & 1 & 1 & j & j & j & j \\ 1 & 1 & 1 & 1 & -j & -j & -j & -j \end{bmatrix}$$

#### B.1.2 UE Receiver with 4Rx

For 1 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 \\ 1 \\ 1 \\ 1 \end{bmatrix}.$$

For 2 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 & j \\ 1 & -j \\ 1 & j \\ 1 & -j \end{bmatrix}.$$

For 4 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 & 1 & j & j \\ 1 & 1 & -j & -j \\ 1 & -1 & j & -j \\ 1 & -1 & -j & j \end{bmatrix}.$$

For 8 port transmission the channel matrix is defined in the frequency domain by

$$\mathbf{H} = \begin{bmatrix} 1 & 1 & 1 & 1 & j & j & j & j \\ 1 & 1 & 1 & 1 & -j & -j & -j & -j \\ 1 & 1 & -1 & -1 & j & j & -j & -j \\ 1 & 1 & -1 & -1 & -j & -j & j & j \end{bmatrix}$$

## B.2 Multi-path fading propagation conditions

The multipath propagation conditions consist of several parts:

- A delay profile in the form of a "tapped delay-lin", characterized by a number of taps at fixed positions on a sampling grid. The profile can be further characterized by the r.m.s. delay spread and the maximum delay spanned by the taps.
- A combination of channel model parameters that include the Delay profile and the Doppler spectrum that is characterized by a classical spectrum shape and a maximum Doppler frequency.
- Different models are used for FR1 (below 6 GHz) and FR2 (above 6 GHz).

### B.2.1 Delay profiles

The delay profiles are simplified from the TR 38.901 [5] TDL models. The simplification steps are shown below for information. These steps are only used when new delay profiles are created. Otherwise, the delay profiles specified in B.2.1.1 and B.2.1.2 can be used as such.

Step 1: Use the original TDL model from TR 38.901[5].

Step 2: Re-order the taps in ascending delays

Step 3: Perform delay scaling according to the procedure described in section 7.7.3 in TR38.901.

Step 4: Apply the quantization to the delay resolution 5 ns. This is done simply by rounding the tap delays to the nearest multiple of the delay resolution.

Step 5: If multiple taps are rounded to the same delay bin, merge them by calculating their linear power sum.

Step 6: If there are more than 12 taps in the quantized model, merge the taps as follows

- Keep first tap as such, and the last tap delay as such.
- Merge two parallel taps with different delays (average delay, sum power) starting from the weakest ones. If the average delay is not in the sampling grid, round up/down it towards the direction of the higher power original tap (e.g. 10 ns & 20 ns → 15 ns, 10 ns & 25 ns → 20 ns, if 25 ns had higher or equal power; 15 ns, if 10 ns had higher power)
- Continue as long as the final number of taps is 12.

Step 7: Round the amplitudes of taps to one decimal (e.g. -8.78 dB → -8.8 dB)

Step 8: If the delay spread has slightly changed due to the tap merge, adjust the final delay spread by increasing or decreasing the power of the last tap so that the delay spread is corrected.

Step 9: Re-normalize tap powers such that the strongest tap is at 0dB.

#### B.2.1.1 Delay profiles for FR1

The delay profiles for FR1 are selected to be representative of low, medium and high delay spread environment. The resulting model parameters are specified in B.2.1.1-1 and the tapped delay line models are specified in Tables B.2.1.1-2 ~ Table B.2.1.1-4.

**Table B.2.1.1-1: Delay profiles for NR channel models**

Model	Number of channel taps	Delay spread (r.m.s.)	Maximum excess tap delay (span)	Delay resolution
TDLA30	12	30 ns	290 ns	5 ns
TDLB100	12	100 ns	480 ns	5 ns
TDLC300	12	300 ns	2595 ns	5 ns

**Table B.2.1.1-2 TDLA30 (DS = 30 ns)**

Tap #	Delay [ns]	Power [dB]	Fading distribution
1	0	-15.5	Rayleigh
2	10	0	Rayleigh
3	15	-5.1	Rayleigh
4	20	-5.1	Rayleigh
5	25	-9.6	Rayleigh
6	50	-8.2	Rayleigh
7	65	-13.1	Rayleigh
8	75	-11.5	Rayleigh
9	105	-11.0	Rayleigh
10	135	-16.2	Rayleigh
11	150	-16.6	Rayleigh
12	290	-26.2	Rayleigh

**Table B.2.1.1-3 TDLB100 (DS = 100ns)**

Tap #	Delay [ns]	Power [dB]	Fading distribution
1	0	0	Rayleigh
2	10	-2.2	Rayleigh
3	20	-0.6	Rayleigh
4	30	-0.6	Rayleigh
5	35	-0.3	Rayleigh
6	45	-1.2	Rayleigh
7	55	-5.9	Rayleigh
8	120	-2.2	Rayleigh
9	170	-0.8	Rayleigh
10	245	-6.3	Rayleigh
11	330	-7.5	Rayleigh
12	480	-7.1	Rayleigh

**Table B.2.1.1-4 TDLC300 (DS = 300 ns)**

Tap #	Delay [ns]	Power [dB]	Fading distribution
1	0	-6.9	Rayleigh
2	65	0	Rayleigh
3	70	-7.7	Rayleigh
4	190	-2.5	Rayleigh
5	195	-2.4	Rayleigh
6	200	-9.9	Rayleigh
7	240	-8.0	Rayleigh
8	325	-6.6	Rayleigh
9	520	-7.1	Rayleigh
10	1045	-13.0	Rayleigh
11	1510	-14.2	Rayleigh
12	2595	-16.0	Rayleigh

## B.2.1.2 Delay profiles for FR2

The delay profiles for FR2 are specified in B.2.1.2-1 and the tapped delay line models are specified in Tables B.2.1.2-2 and table B.2.1.2-3.

**Table B.2.1.2-1: Delay profiles for NR channel models**

Model	Number of channel taps	Delay spread (r.m.s.)	Maximum excess tap delay (span)	Delay resolution
TDLA30	12	30 ns	290 ns	5 ns
TDLC60	12	60 ns	520 ns	5 ns

**Table B.2.1.2-2 TDLA30 (DS = 30 ns)**

Tap #	Delay [ns]	Power [dB]	Fading distribution
1	0	-15.5	Rayleigh
2	10	0	Rayleigh
3	15	-5.1	Rayleigh
4	20	-5.1	Rayleigh
5	25	-9.6	Rayleigh
6	50	-8.2	Rayleigh
7	65	-13.1	Rayleigh
8	75	-11.5	Rayleigh
9	105	-11.0	Rayleigh
10	135	-16.2	Rayleigh
11	150	-16.6	Rayleigh
12	290	-26.2	Rayleigh

**Table B.2.1.2-3 TDLC60 (DS = 60 ns)**

Tap #	Delay [ns]	Power [dB]	Fading distribution
1	0	-7.8	Rayleigh
2	15	-0.3	Rayleigh
3	40	0	Rayleigh
4	50	-8.9	Rayleigh
5	55	-14.5	Rayleigh
6	75	-8.5	Rayleigh
7	80	-10.2	Rayleigh
8	130	-12.1	Rayleigh
9	210	-13.9	Rayleigh
10	300	-15.2	Rayleigh
11	360	-16.9	Rayleigh
12	520	-19.4	Rayleigh

## B.2.2 Combinations of channel model parameters

The propagation conditions used for the performance measurements in multi-path fading environment are indicated as a combination of a channel model name and a maximum Doppler frequency, i.e., TDLA<DS>-<Doppler>, TDLB<DS>-<Doppler> or TDLC<DS>-<Doppler> where ‘<DS>’ indicates the desired delay spread and ‘<Doppler>’ indicates the maximum Doppler frequency (Hz).

Table B.2.2-1 and Table B.2.2-2 show the propagation conditions that are used for the performance measurements in multi-path fading environment for low, medium and high Doppler frequencies for FR1 and FR2, respectively.

**Table B.2.2-1 Channel model parameters for FR1**

Combination name	Model	Maximum Doppler frequency
TDLA30-5	TDLA30	5 Hz
TDLA30-10	TDLA30	10 Hz
TDLB100-400	TDLB100	400 Hz
TDLC300-100	TDLC300	100 Hz

**Table B.2.2-2 Channel model parameters for FR2**

Combination name	Model	Maximum Doppler frequency
TDLA30-35	TDLA30	35 Hz
TDLA30-75	TDLA30	75 Hz
TDLA30-300	TDLA30	300 Hz
TDLC60-300	TDLC60	300 Hz

## B.2.3 MIMO Channel Correlation Matrices

The MIMO channel correlation matrices defined in B.2.3 apply for the antenna configuration using uniform linear arrays at both gNB and UE and for the antenna configuration using cross polarized antennas.

### B.2.3.1 MIMO Correlation Matrices using Uniform Linear Array (ULA)

The MIMO channel correlation matrices defined in B.2.3.1 apply for the antenna configuration using uniform linear array (ULA) at both gNB and UE.

#### B.2.3.1.1 Definition of MIMO Correlation Matrices

Table B.2.3.1.1-1 defines the correlation matrix for the gNB.

**Table B.2.3.1.1-1 gNB correlation matrix**

	One antenna	Two antennas	Four antennas
gNB Correlation	$R_{gNB} = 1$	$R_{gNB} = \begin{pmatrix} 1 & \alpha \\ \alpha^* & 1 \end{pmatrix}$	$R_{gNB} = \begin{pmatrix} 1 & \alpha^{1/9} & \alpha^{4/9} & \alpha \\ \alpha^{1/9*} & 1 & \alpha^{1/9} & \alpha^{4/9} \\ \alpha^{4/9*} & \alpha^{1/9*} & 1 & \alpha^{1/9} \\ \alpha^* & \alpha^{4/9*} & \alpha^{1/9*} & 1 \end{pmatrix}$

Table B.2.3.1.1-2 defines the correlation matrix for the UE:

**Table B.2.3.1.1-2 UE correlation matrix**

	One antenna	Two antennas	Four antennas
UE Correlation	$R_{UE} = 1$	$R_{UE} = \begin{pmatrix} 1 & \beta \\ \beta^* & 1 \end{pmatrix}$	$R_{UE} = \begin{pmatrix} 1 & \beta^{1/9} & \beta^{4/9} & \beta \\ \beta^{1/9*} & 1 & \beta^{1/9} & \beta^{4/9} \\ \beta^{4/9*} & \beta^{1/9*} & 1 & \beta^{1/9} \\ \beta^* & \beta^{4/9*} & \beta^{1/9*} & 1 \end{pmatrix}$

Table B.2.3.1.1-3 defines the channel spatial correlation matrix  $R_{spat}$ . The parameters,  $\alpha$  and  $\beta$  in Table B.2.3.1-3 defines the spatial correlation between the antennas at the gNB and UE.

**Table B.2.3.1.1-3:**  $R_{spat}$  correlation matrices

<b>1x2 case</b>	$R_{spat} = R_{UE} = \begin{bmatrix} 1 & \beta \\ \beta^* & 1 \end{bmatrix}$
<b>1x4 case</b>	$R_{spat} = R_{UE} = \begin{pmatrix} 1 & \beta^{1/9} & \beta^{4/9} & \beta \\ \beta^{1/9*} & 1 & \beta^{1/9} & \beta^{4/9} \\ \beta^{4/9*} & \beta^{1/9*} & 1 & \beta^{1/9} \\ \beta^* & \beta^{4/9*} & \beta^{1/9*} & 1 \end{pmatrix}$
<b>2x1 case</b>	$R_{spat} = R_{gNB} = \begin{bmatrix} 1 & \alpha \\ \alpha^* & 1 \end{bmatrix}$
<b>2x2 case</b>	$R_{spat} = R_{gNB} \otimes R_{UE} = \begin{bmatrix} 1 & \alpha \\ \alpha^* & 1 \end{bmatrix} \otimes \begin{bmatrix} 1 & \beta \\ \beta^* & 1 \end{bmatrix} = \begin{bmatrix} 1 & \beta & \alpha & \alpha\beta \\ \beta^* & 1 & \alpha\beta^* & \alpha \\ \alpha^* & \alpha^*\beta & 1 & \beta \\ \alpha^*\beta^* & \alpha^* & \beta^* & 1 \end{bmatrix}$
<b>2x4 case</b>	$R_{spat} = R_{gNB} \otimes R_{UE} = \begin{bmatrix} 1 & \alpha \\ \alpha^* & 1 \end{bmatrix} \otimes \begin{bmatrix} 1 & \beta^{1/9} & \beta^{4/9} & \beta \\ \beta^{1/9*} & 1 & \beta^{1/9} & \beta^{4/9} \\ \beta^{4/9*} & \beta^{1/9*} & 1 & \beta^{1/9} \\ \beta^* & \beta^{4/9*} & \beta^{1/9*} & 1 \end{bmatrix}$
<b>4x1 case</b>	$R_{spat} = R_{gNB} = \begin{bmatrix} 1 & \alpha^{1/9} & \alpha^{4/9} & \alpha \\ \alpha^{1/9*} & 1 & \alpha^{1/9} & \alpha^{4/9} \\ \alpha^{4/9*} & \alpha^{1/9*} & 1 & \alpha^{1/9} \\ \alpha^* & \alpha^{4/9*} & \alpha^{1/9*} & 1 \end{bmatrix}$
<b>4x2 case</b>	$R_{spat} = R_{gNB} \otimes R_{UE} = \begin{bmatrix} 1 & \alpha^{1/9} & \alpha^{4/9} & \alpha \\ \alpha^{1/9*} & 1 & \alpha^{1/9} & \alpha^{4/9} \\ \alpha^{4/9*} & \alpha^{1/9*} & 1 & \alpha^{1/9} \\ \alpha^* & \alpha^{4/9*} & \alpha^{1/9*} & 1 \end{bmatrix} \otimes \begin{bmatrix} 1 & \beta \\ \beta^* & 1 \end{bmatrix}$
<b>4x4 case</b>	$R_{spat} = R_{gNB} \otimes R_{UE} = \begin{bmatrix} 1 & \alpha^{1/9} & \alpha^{4/9} & \alpha \\ \alpha^{1/9*} & 1 & \alpha^{1/9} & \alpha^{4/9} \\ \alpha^{4/9*} & \alpha^{1/9*} & 1 & \alpha^{1/9} \\ \alpha^* & \alpha^{4/9*} & \alpha^{1/9*} & 1 \end{bmatrix} \otimes \begin{pmatrix} 1 & \beta^{1/9} & \beta^{4/9} & \beta \\ \beta^{1/9*} & 1 & \beta^{1/9} & \beta^{4/9} \\ \beta^{4/9*} & \beta^{1/9*} & 1 & \beta^{1/9} \\ \beta^* & \beta^{4/9*} & \beta^{1/9*} & 1 \end{pmatrix}$

For cases with more antennas at either gNB or UE or both, the channel spatial correlation matrix can still be expressed as the Kronecker product of  $R_{gNB}$  and  $R_{UE}$  according to  $R_{spat} = R_{gNB} \otimes R_{UE}$ .

### B.2.3.1.2 MIMO Correlation Matrices at High, Medium and Low Level

The  $\alpha$  and  $\beta$  for different correlation types are given in Table B.2.3.1.2-1.

**Table B.2.3.1.2-1: The  $\alpha$  and  $\beta$  parameters for ULA MIMO correlation matrices**

Correlation Model	$\alpha$	$\beta$
<b>Low correlation</b>	0	0
<b>Medium Correlation</b>	0.3	0.9
<b>Medium Correlation A</b>	0.3	0.3874
<b>High Correlation</b>	0.9	0.9

The correlation matrices for high, medium, medium A and low correlation are defined in Table B.2.3.1.2-2, B.2.3.1.2-3, B.2.3.1.2-4 and B.2.3.1.2-5 as below.

The values in Table B.2.3.1.2-2 have been adjusted for the 4x2 and 4x4 high correlation cases to insure the correlation matrix is positive semi-definite after round-off to 4 digit precision. This is done using the equation:

$$R_{high} = [R_{spat} + aI_n]/(1+a)$$

Where the value “ $a$ ” is a scaling factor such that the smallest value is used to obtain a positive semi-definite result. For the 4x2 high correlation case,  $a=0.00010$ . For the 4x4 high correlation case,  $a=0.00012$ .

The same method is used to adjust the 2x4 and 4x4 medium correlation matrix in Table B.2.3.1.2-3 to insure the correlation matrix is positive semi-definite after round-off to 4 digit precision with  $a = 0.00010$  and  $a = 0.00012$ .

**Table B.2.3.1.2-2: MIMO correlation matrices for high correlation**

<b>1x2 case</b>	$R_{high} = \begin{pmatrix} 1 & 0.9 \\ 0.9 & 1 \end{pmatrix}$
<b>2x1 case</b>	$R_{high} = \begin{pmatrix} 1 & 0.9 \\ 0.9 & 1 \end{pmatrix}$
<b>2x2 case</b>	$R_{high} = \begin{pmatrix} 1 & 0.9 & 0.9 & 0.81 \\ 0.9 & 1 & 0.81 & 0.9 \\ 0.9 & 0.81 & 1 & 0.9 \\ 0.81 & 0.9 & 0.9 & 1 \end{pmatrix}$
<b>4x2 case</b>	$R_{high} = \begin{bmatrix} 1.0000 & 0.8999 & 0.9883 & 0.8894 & 0.9542 & 0.8587 & 0.8999 & 0.8099 \\ 0.8999 & 1.0000 & 0.8894 & 0.9883 & 0.8587 & 0.9542 & 0.8099 & 0.8999 \\ 0.9883 & 0.8894 & 1.0000 & 0.8999 & 0.9883 & 0.8894 & 0.9542 & 0.8587 \\ 0.8894 & 0.9883 & 0.8999 & 1.0000 & 0.8894 & 0.9883 & 0.8587 & 0.9542 \\ 0.9542 & 0.8587 & 0.9883 & 0.8894 & 1.0000 & 0.8999 & 0.9883 & 0.8894 \\ 0.8587 & 0.9542 & 0.8894 & 0.9883 & 0.8999 & 1.0000 & 0.8894 & 0.9883 \\ 0.8999 & 0.8099 & 0.9542 & 0.8587 & 0.9883 & 0.8894 & 1.0000 & 0.8999 \\ 0.8099 & 0.8999 & 0.8587 & 0.9542 & 0.8894 & 0.9883 & 0.8999 & 1.0000 \end{bmatrix}$
<b>4x4 case</b>	$R_{high} = \begin{bmatrix} 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.9882 & 0.9767 & 0.9430 & 0.8894 & 0.9541 & 0.9430 & 0.9105 & 0.8587 & 0.8999 & 0.8894 & 0.8587 & 0.8099 \\ 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9430 & 0.9541 & 0.9430 & 0.9105 & 0.8894 & 0.8999 & 0.8894 & 0.8587 \\ 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.9105 & 0.9430 & 0.9541 & 0.9430 & 0.8587 & 0.8894 & 0.8999 & 0.8894 & 0.8999 \\ 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8587 & 0.9105 & 0.9430 & 0.9541 & 0.8099 & 0.8587 & 0.8894 & 0.8999 & 0.8999 \\ 0.9882 & 0.9767 & 0.9430 & 0.8894 & 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.9882 & 0.9767 & 0.9430 & 0.8894 & 0.9541 & 0.9430 & 0.9105 & 0.8587 \\ 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9430 & 0.9541 & 0.9430 & 0.9105 \\ 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.9105 & 0.9430 & 0.9541 & 0.9430 & 0.9430 \\ 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8587 & 0.9105 & 0.9430 & 0.9541 & 0.9541 \\ 0.9541 & 0.9430 & 0.9105 & 0.8587 & 0.9882 & 0.9767 & 0.9430 & 0.8894 & 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.9882 & 0.9767 & 0.9430 & 0.8894 & 0.8999 \\ 0.9430 & 0.9541 & 0.9430 & 0.9105 & 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9430 \\ 0.9105 & 0.9430 & 0.9541 & 0.9430 & 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.8587 \\ 0.8587 & 0.9105 & 0.9430 & 0.9541 & 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8999 \\ 0.8999 & 0.8894 & 0.8587 & 0.8099 & 0.9541 & 0.9430 & 0.9105 & 0.8587 & 0.9882 & 0.9767 & 0.9430 & 0.8894 & 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.8999 \\ 0.8894 & 0.8999 & 0.8894 & 0.8587 & 0.9430 & 0.9541 & 0.9430 & 0.9105 & 0.9767 & 0.9882 & 0.9767 & 0.9430 & 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.8999 \\ 0.8587 & 0.8894 & 0.8999 & 0.8894 & 0.9105 & 0.9430 & 0.9541 & 0.9430 & 0.9430 & 0.9767 & 0.9882 & 0.9767 & 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.8099 \\ 0.8099 & 0.8587 & 0.8894 & 0.8999 & 0.8587 & 0.9105 & 0.9430 & 0.9541 & 0.8894 & 0.9430 & 0.9767 & 0.9882 & 0.8999 & 0.9541 & 0.9882 & 1.0000 \end{bmatrix}$

Table B.2.3.1.2-3: MIMO correlation matrices for medium correlation

<b>1x2 case</b>	N/A
<b>2x1 case</b>	N/A
<b>2x2 case</b>	$R_{medium} = \begin{pmatrix} 1 & 0.9 & 0.3 & 0.27 \\ 0.9 & 1 & 0.27 & 0.3 \\ 0.3 & 0.27 & 1 & 0.9 \\ 0.27 & 0.3 & 0.9 & 1 \end{pmatrix}$
<b>2x4 case</b>	$R_{medium} = \begin{pmatrix} 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.3000 & 0.2965 & 0.2862 & 0.2700 \\ 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.2965 & 0.3000 & 0.2965 & 0.2862 \\ 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.2862 & 0.2965 & 0.3000 & 0.2965 \\ 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.2700 & 0.2862 & 0.2965 & 0.3000 \\ 0.3000 & 0.2965 & 0.2862 & 0.2700 & 1.0000 & 0.9882 & 0.9541 & 0.8999 \\ 0.2965 & 0.3000 & 0.2965 & 0.2862 & 0.9882 & 1.0000 & 0.9882 & 0.9541 \\ 0.2862 & 0.2965 & 0.3000 & 0.2965 & 0.9541 & 0.9882 & 1.0000 & 0.9882 \\ 0.2700 & 0.2862 & 0.2965 & 0.3000 & 0.8999 & 0.9541 & 0.9882 & 1.0000 \end{pmatrix}$
<b>4x2 case</b>	$R_{medium} = \begin{pmatrix} 1.0000 & 0.9000 & 0.8748 & 0.7873 & 0.5856 & 0.5271 & 0.3000 & 0.2700 \\ 0.9000 & 1.0000 & 0.7873 & 0.8748 & 0.5271 & 0.5856 & 0.2700 & 0.3000 \\ 0.8748 & 0.7873 & 1.0000 & 0.9000 & 0.8748 & 0.7873 & 0.5856 & 0.5271 \\ 0.7873 & 0.8748 & 0.9000 & 1.0000 & 0.7873 & 0.8748 & 0.5271 & 0.5856 \\ 0.5856 & 0.5271 & 0.8748 & 0.7873 & 1.0000 & 0.9000 & 0.8748 & 0.7873 \\ 0.5271 & 0.5856 & 0.7873 & 0.8748 & 0.9000 & 1.0000 & 0.7873 & 0.8748 \\ 0.3000 & 0.2700 & 0.5856 & 0.5271 & 0.8748 & 0.7873 & 1.0000 & 0.9000 \\ 0.2700 & 0.3000 & 0.5271 & 0.5856 & 0.7873 & 0.8748 & 0.9000 & 1.0000 \end{pmatrix}$
<b>4x4 case</b>	$R_{medium} = \begin{pmatrix} 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.8747 & 0.8645 & 0.8347 & 0.7872 & 0.5855 & 0.5787 & 0.5588 & 0.5270 & 0.3000 & 0.2965 & 0.2862 & 0.2700 \\ 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.8645 & 0.8747 & 0.8645 & 0.8347 & 0.5787 & 0.5855 & 0.5787 & 0.5588 & 0.2965 & 0.3000 & 0.2965 & 0.2862 \\ 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.5588 & 0.5787 & 0.5855 & 0.5787 & 0.2862 & 0.2965 & 0.3000 & 0.2965 \\ 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.5270 & 0.5588 & 0.5787 & 0.5855 & 0.2700 & 0.2862 & 0.2965 & 0.3000 \\ 0.8747 & 0.8645 & 0.8347 & 0.7872 & 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.8747 & 0.8645 & 0.8347 & 0.7872 & 0.5855 & 0.5787 & 0.5588 & 0.5270 \\ 0.8645 & 0.8747 & 0.8645 & 0.8347 & 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.8645 & 0.8747 & 0.8645 & 0.8347 & 0.5787 & 0.5855 & 0.5787 & 0.5588 \\ 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.5588 & 0.5787 & 0.5855 & 0.5787 \\ 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.5270 & 0.5588 & 0.5787 & 0.5855 \\ 0.5855 & 0.5787 & 0.5588 & 0.5270 & 0.8747 & 0.8645 & 0.8347 & 0.7872 & 1.0000 & 0.9882 & 0.9541 & 0.8999 & 0.8747 & 0.8645 & 0.8347 & 0.7872 \\ 0.5787 & 0.5855 & 0.5787 & 0.5588 & 0.8645 & 0.8747 & 0.8645 & 0.8347 & 0.9882 & 1.0000 & 0.9882 & 0.9541 & 0.8645 & 0.8747 & 0.8645 & 0.8347 \\ 0.5588 & 0.5787 & 0.5855 & 0.5787 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.9541 & 0.9882 & 1.0000 & 0.9882 & 0.8347 & 0.8645 & 0.8747 & 0.8645 \\ 0.5270 & 0.5588 & 0.5787 & 0.5855 & 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.8999 & 0.9541 & 0.9882 & 1.0000 & 0.7872 & 0.8347 & 0.8645 & 0.8747 \\ 0.3000 & 0.2965 & 0.2862 & 0.2700 & 0.5855 & 0.5787 & 0.5588 & 0.5270 & 0.8747 & 0.8645 & 0.8347 & 0.7872 & 1.0000 & 0.9882 & 0.9541 & 0.8999 \\ 0.2965 & 0.3000 & 0.2965 & 0.2862 & 0.5787 & 0.5855 & 0.5787 & 0.5855 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.8347 & 0.9882 & 1.0000 & 0.9541 \\ 0.2862 & 0.2965 & 0.3000 & 0.2965 & 0.5588 & 0.5787 & 0.5855 & 0.5787 & 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.9541 & 0.9882 & 1.0000 \\ 0.2700 & 0.2862 & 0.2965 & 0.3000 & 0.5270 & 0.5588 & 0.5787 & 0.5855 & 0.7872 & 0.8347 & 0.8645 & 0.8747 & 0.8645 & 0.8747 & 0.8999 & 0.9541 \end{pmatrix}$

**Table B.2.3.1.2-4: MIMO correlation matrices for medium correlation A**

**Table B.2.3.1.2-5: MIMO correlation matrices for low correlation**

<b>1x2 case</b>	$R_{low} = \mathbf{I}_2$
<b>1x4 case</b>	$R_{low} = \mathbf{I}_4$
<b>2x1 case</b>	$R_{low} = \mathbf{I}_2$
<b>2x2 case</b>	$R_{low} = \mathbf{I}_4$
<b>2x4 case</b>	$R_{low} = \mathbf{I}_8$
<b>4x1 case</b>	$R_{low} = \mathbf{I}_4$
<b>4x2 case</b>	$R_{low} = \mathbf{I}_8$
<b>4x4 case</b>	$R_{low} = \mathbf{I}_{16}$

In Table B.2.3.1.2-5,  $\mathbf{I}_d$  is the  $d \times d$  identity matrix.

### B.2.3.2 MIMO Correlation Matrices using Cross Polarized Antennas (X-pol)

The MIMO channel correlation matrices defined in B.2.3.2 apply for the antenna configuration using cross polarized (XP/X-pol) antennas at both gNB and UE. The cross-polarized antenna elements with +/-45 degrees polarization slant angles are deployed at gNB and cross-polarized antenna elements with +90/0 degrees polarization slant angles are deployed at UE.

For the 2D cross-polarized antenna array at eNodeB, the  $N$  antennas are indexed by  $(N_1, N_2, P)$ , and total number of antennas is  $N = P \cdot N_1 \cdot N_2$ , where

- $N_1$  is the number of antenna elements in first dimension with same polarization,

- $N_2$  is the number of antenna elements in second dimension with same polarization, and
- $P$  is the number of polarization groups.

For the 2D cross-polarized antennas at gNB, the  $N$  antennas are labelled such that antennas shall be in increasing order of the second dimension firstly, then the first dimension, and finally the polarization group. For a specific antenna element at  $p$ -th polarization,  $n_1$ -th row, and  $n_2$ -th column within the 2D antenna array, the following index number is used for antenna labelling:

$$\text{Index}(p, n_1, n_2) = p \cdot N_1 \cdot N_2 + n_1 \cdot N_2 + n_2 + 1; \quad p = 0, 1; \quad n_1 = 0, \dots, N_1 - 1; \quad n_2 = 0, \dots, N_2 - 1.$$

where  $N$  is the number of transmit antennas,  $p$  is the polarization group index,  $n_1$  is the row index, and  $n_2$  is the column index of the antenna element.

For the linear (single dimension, 1D) cross-polarized antenna, the  $N$  antennas are labelled following the above equations with  $N_2=1$ .

#### B.2.3.2.1 Definition of MIMO Correlation Matrices using cross polarized antennas

For the channel spatial correlation matrix, the following is used:

$$R_{\text{spat}} = P \left( R_{gNB} \otimes \Gamma \otimes R_{UE} \right) P^T$$

where

- $R_{UE}$  is the spatial correlation matrix at the UE with same polarization,
- $R_{gNB}$  is the spatial correlation matrix at the gNB with same polarization,
- $\Gamma$  is a polarization correlation matrix, and
- $(\bullet)^T$  denotes transpose.

The matrix  $\Gamma$  is defined as

$$\Gamma = \begin{bmatrix} 1 & 0 & -\gamma & 0 \\ 0 & 1 & 0 & \gamma \\ -\gamma & 0 & 1 & 0 \\ 0 & \gamma & 0 & 1 \end{bmatrix}$$

A permutation matrix  $P$  elements are defined as

$$P(a, b) = \begin{cases} 1 & \text{for } a = (j-1)Nr + i \text{ and } b = 2(j-1)Nr + i, \quad i = 1, \dots, Nr, j = 1, \dots, Nt/2 \\ 1 & \text{for } a = (j-1)Nr + i \text{ and } b = 2(j-Nt/2)Nr - Nr + i, \quad i = 1, \dots, Nr, j = Nt/2 + 1, \dots, Nt \\ 0 & \text{otherwise} \end{cases}$$

where  $Nt$  and  $Nr$  is the number of transmitter and receiver respectively. This is used to map the spatial correlation coefficients in accordance with the antenna element labelling system described in B.2.3.2.

For the 2D cross-polarized antenna array at gNB, the spatial correlation matrix at the gNB is further expressed as following for 2D cross-polarized antenna array at gNB:

$$R_{gNB} = R_{gNB\_Dim,1} \otimes R_{gNB\_Dim,2}$$

where

- $R_{gNB\_Dim,1}$  is the correlation matrix of antenna elements in first dimension with same polarization, and
- $R_{gNB\_Dim,2}$  is the correlation matrix of antenna elements in second dimension with same polarization.

For the 2D cross polarized antenna array at gNB side, the spatial correlation matrices in one direction of antenna array are as follows:

- For 1 antenna element with the same polarization in one direction,

$$R_{gNB\_Dim,i} = 1.$$

- For 2 antenna elements with the same polarization in one direction,

$$R_{gNB\_Dim,i} = \begin{pmatrix} 1 & \alpha_i \\ \alpha_i^* & 1 \end{pmatrix}.$$

- For 3 antenna elements with the same polarization in one direction,

$$R_{gNB\_Dim,i} = \begin{pmatrix} 1 & \alpha_i^{1/4} & \alpha_i \\ \alpha_i^{1/4*} & 1 & \alpha_i^{1/4} \\ \alpha_i^* & \alpha_i^{1/4*} & 1 \end{pmatrix}.$$

- For 4 antenna elements with the same polarization in one direction,

$$R_{gNB\_Dim,i} = \begin{pmatrix} 1 & \alpha_i^{1/9} & \alpha_i^{4/9} & \alpha_i \\ \alpha_i^{1/9*} & 1 & \alpha_i^{1/9} & \alpha_i^{4/9} \\ \alpha_i^{4/9*} & \alpha_i^{1/9*} & 1 & \alpha_i^{1/9} \\ \alpha_i^* & \alpha_i^{4/9*} & \alpha_i^{1/9*} & 1 \end{pmatrix}.$$

where the index  $i = 1,2$  stands for first dimension and second dimension respectively.

For the 1D cross-polarized antenna array at gNB, the matrix of  $R_{gNB}$  is determined by follow the equations for 2D cross-polarized antenna array and letting  $R_{gNB\_Dim,2} = 1$ , i.e.,

$$R_{gNB} = R_{gNB\_Dim,1}$$

The spatial correlation matrices at UE side are as follows:

- For 1 antenna element with the same polarization,

$$R_{UE} = 1.$$

- For 2 antenna elements with the same polarization,

$$R_{UE} = \begin{pmatrix} 1 & \beta \\ \beta^* & 1 \end{pmatrix}.$$

### B.2.3.2.2 MIMO Correlation Matrices using cross polarized antennas

The values for parameters  $\alpha$ ,  $\beta$  and  $\gamma$  for the cross polarized antenna models are given in Table B.2.3.2.2-1.

**Table B.2.3.2.2-1: The  $\alpha$  and  $\beta$  parameters for cross-polarized MIMO correlation matrices**

Correlation Model	$\alpha_1$	$\alpha_2$	$\beta$	$\gamma$
<b>Medium Correlation A</b>	0.3	N/A	0.6	0.2
<b>High Correlation</b>	0.9	0.9	0.9	0.3
Note 1:	Value of $\alpha_1$ applies when more than one pair of cross-polarized antenna elements in first dimension at gNB side.			
Note 2:	Value of $\alpha_2$ applies when more than one pair of cross-polarized antenna elements in second dimension at gNB side.			
Note 3:	Value of $\beta$ applies when more than one pair of cross-polarized antenna elements at UE side.			

For the 1D cross polarized antenna array at gNB side, the correlation matrices for high spatial correlation and medium correlation A are defined in Table B.2.3.2.2-2 and Table B.2.3.2.2-3 as below.

The values in Table B.2.3.2.2-2 have been adjusted to insure the correlation matrix is positive semi-definite after round-off to 4 digit precision. This is done using the equation:

$$R_{high} = [R_{spat} + aI_n]/(1+a) \text{ or } R_{mediumA} = [R_{spat} + aI_n]/(1+a)$$

Where the value “ $a$ ” is a scaling factor such that the smallest value is used to obtain a positive semi-definite result. For the 8x2 high spatial correlation case,  $a=0.00010$ .

**Table B.2.3.2.2-2: MIMO correlation matrices for high spatial correlation**

4x2 case	$R_{high} =$	$\begin{bmatrix} 1.0000 & 0.0000 & 0.9000 & 0.0000 & -0.3000 & 0.0000 & -0.2700 & 0.0000 \\ 0.0000 & 1.0000 & 0.0000 & 0.9000 & 0.0000 & 0.3000 & 0.0000 & 0.2700 \\ 0.9000 & 0.0000 & 1.0000 & 0.0000 & -0.2700 & 0.0000 & -0.3000 & 0.0000 \\ 0.0000 & 0.9000 & 0.0000 & 1.0000 & 0.0000 & 0.2700 & 0.0000 & 0.3000 \\ -0.3000 & 0.0000 & -0.2700 & 0.0000 & 1.0000 & 0.0000 & 0.9000 & 0.0000 \\ 0.0000 & 0.3000 & 0.0000 & 0.2700 & 0.0000 & 1.0000 & 0.0000 & 0.9000 \\ -0.2700 & 0.0000 & -0.3000 & 0.0000 & 0.9000 & 0.0000 & 1.0000 & 0.0000 \\ 0.0000 & 0.2700 & 0.0000 & 0.3000 & 0.0000 & 0.9000 & 0.0000 & 1.0000 \end{bmatrix}$
	$R_{high} =$	$\begin{bmatrix} 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & 0.8999 & 0.0000 & -0.3000 & 0.0000 & -0.2965 & 0.0000 & -0.2862 & 0.0000 & -0.2700 & 0.0000 \\ 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & 0.8999 & 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 & 0.2862 & 0.0000 & 0.2700 & 0.0000 \\ 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & -0.2965 & 0.0000 & -0.3000 & 0.0000 & -0.2965 & 0.0000 & -0.2862 & 0.0000 & -0.2700 & 0.0000 \\ 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 & 0.2862 & 0.0000 \\ 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & -0.2862 & 0.0000 & -0.2965 & 0.0000 & -0.3000 & 0.0000 & -0.2965 & 0.0000 \\ 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.2862 & 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 \\ 0.8999 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & -0.2700 & 0.0000 & -0.2862 & 0.0000 & -0.2965 & 0.0000 & -0.3000 & 0.0000 \\ 0.0000 & 0.8999 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.2700 & 0.0000 & 0.2862 & 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 \\ -0.3000 & 0.0000 & -0.2965 & 0.0000 & -0.2862 & 0.0000 & -0.2700 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & 0.8999 & 0.0000 \\ 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 & 0.2862 & 0.0000 & 0.2700 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 & 0.8999 & 0.0000 \\ -0.2965 & 0.0000 & -0.3000 & 0.0000 & -0.2965 & 0.0000 & -0.2862 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 \\ 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 & 0.2862 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 & 0.9542 & 0.0000 \\ -0.2862 & 0.0000 & -0.2965 & 0.0000 & -0.3000 & 0.0000 & -0.2965 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 \\ 0.0000 & 0.2862 & 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 & 0.2965 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 & 0.9883 & 0.0000 \\ -0.2700 & 0.0000 & -0.2862 & 0.0000 & -0.2965 & 0.0000 & -0.3000 & 0.0000 & 0.8999 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 \\ 0.0000 & 0.2700 & 0.0000 & 0.2862 & 0.0000 & 0.2965 & 0.0000 & 0.3000 & 0.0000 & 0.8999 & 0.0000 & 0.9542 & 0.0000 & 0.9883 & 0.0000 & 1.0000 & 0.0000 \end{bmatrix}$

### B.2.3.2.3 Beam steering approach

For the 2D cross-polarized antenna array at gNB, given the channel spatial correlation matrix in B.2.3.2.1 and B.2.3.2.2, the corresponding random channel matrix  $H$  can be calculated. The signal model for the  $k$ -th slot is denoted as

$$y = HD_{\theta_{k,1}, \theta_{k,2}} Wx + n$$

And the steering matrix is further expressed as following:

$$D_{\theta_{k,1}, \theta_{k,2}} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \otimes (D_{\theta_{k,1}}(N_1) \otimes D_{\theta_{k,2}}(N_2))$$

where

- $H$  is the  $Nr \times Nt$  channel matrix per subcarrier.
- $D_{\theta_{k,1}, \theta_{k,2}}$  is the steering matrix,
- $D_{\theta_{k,1}}(N_1)$  is the steering matrix in first dimension with same polarization,
- $D_{\theta_{k,2}}(N_2)$  is the steering matrix in second dimension with same polarization,
- $N_1$  is the number of antenna elements in first dimension with same polarization,
- $N_2$  is the number of antenna elements in second dimension with same polarization,
- For antenna array with only one direction, number of antenna element in second direction  $N_2$  equals 1.

For 1 antenna element with the same polarization in one direction,

$$D_{\theta_{k,i}}(1) = 1.$$

For 2 antenna elements with the same polarization in one direction,

$$D_{\theta_{k,i}}(2) = \begin{bmatrix} 1 & 0 \\ 0 & e^{j3\theta_{k,i}} \end{bmatrix}.$$

For 3 antenna elements with the same polarization in one direction,

$$D_{\theta_{k,i}}(3) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & e^{j1.5\theta_{k,i}} & 0 \\ 0 & 0 & e^{j3\theta_{k,i}} \end{bmatrix}.$$

For 4 antenna elements with the same polarization in one direction,

$$D_{\theta_{k,i}}(4) = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & e^{j\theta_{k,i}} & 0 & 0 \\ 0 & 0 & e^{j2\theta_{k,i}} & 0 \\ 0 & 0 & 0 & e^{j3\theta_{k,i}} \end{bmatrix}.$$

where the index  $i=1,2$  stands for first dimension and second dimension respectively.

- $\theta_{k,i}$  controls the phase variation in first dimension and second dimension respectively, and the phase for  $k$ -th subframe is denoted by  $\theta_{k,i} = \theta_{0,i} + \Delta\theta \cdot k$ , where  $\theta_{0,i}$  is the random start value with the uniform distribution, i.e.,

$\theta_{0,i} \in [0, 2\pi]$ ,  $\Delta\theta$  is the step of phase variation, which is defined in Table B.2.3B.4-1, and  $k$  is the linear increment of  $1/(\mu+1)$  for every slot throughout the simulation, the index  $i=1,2$  stands for first dimension and second dimension respectively.

- $W$  is the precoding matrix for  $N_t$  transmission antennas,
- $y$  is the received signal,  $x$  is the transmitted signal, and  $n$  is AWGN.
- $\mu$  corresponds to subcarrier spacing configuration,  $\Delta f = 2^\mu \cdot 15$  [kHz]

For the 1D cross-polarized antenna array at gNB, the corresponding random channel matrix  $H$  can be calculated by letting  $N_2=1$ , i.e.,

$$D_{\theta_{k,1}} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \otimes D_{\theta_{k,1}}(N_1)$$

**Table B.2.3B.4-1: The step of phase variation**

Variation Step	Value (rad/ms)
$\Delta\theta$	$1.2566 \times 10^{-3}$

## B.2.4 Two-tap propagation conditions for CQI tests

For Channel Quality Indication (CQI) tests, the following additional multi-path profile is used:

$$h(t, \tau) = \delta(\tau) + a \exp(-i2\pi f_D t) \delta(\tau - \tau_d)$$

in continuous time  $(t, \tau)$  representation, with  $\tau_d$  the delay, a constant value of  $a$  and  $f_D$  the Doppler frequency. The same  $h(t, \tau)$  is used to describe the fading channel between every pair of Tx and Rx.

## B.3 High Speed Train Scenario

## B.4 Beamforming Model

---

## Annex C (normative): Downlink physical channels

### C.1 General

This annex specifies the downlink physical channels that are needed for setting a connection and channels that are needed during a connection.

---

### C.2 Setup (Conducted)

Table C.2-1 describes the downlink Physical Channels that are required for connection set up.

**Table C.2-1: Downlink Physical Channels required for connection set-up**

Physical Channel
PBCH
SSS
PSS
PDCCH
PDSCH
PBCH DMRS
PDCCH DMRS
PDSCH DMRS
CSI-RS

---

### C.3 Connection (Conducted)

The following clauses, describes the downlink Physical Channels that are transmitted during a connection i.e., when measurements are done.

#### C.3.1 Measurement of Performance requirements

*<Editor's note: OCNG for DMRS is FFS in Annex A.>*

Table C.3.1-1 is applicable for measurements in which uniform RS-to-EPRE boosting for all downlink physical channels, unless otherwise stated.

**Table C.3.1-1: Downlink Physical Channels transmitted during a connection (FDD and TDD)**

Parameter	Unit	Value
SSS transmit power	W	Test specific
EPRE ratio of PSS to SSS	dB	0
EPRE ratio of PBCH DMRS to SSS	dB	0
EPRE ratio of PBCH to PBCH DMRS	dB	0
EPRE ratio of PDCCH DMRS to SSS	dB	0
EPRE ratio of PDCCH to PDCCH DMRS	dB	0
EPRE ratio of PDSCH DMRS to SSS	dB	0
EPRE ratio of PDSCH to PDSCH DMRS	dB	0
EPRE ratio of CSI-RS to SSS	dB	0
EPRE ratio of OCNG to SSS	dB	0

---

### C.4 Setup (Radiated)

Table C.4-1 describes the downlink Physical Channels that are required for connection set up.

**Table C.4-1: Downlink Physical Channels required for connection set-up**

Physical Channel
PBCH
SSS
PSS
PDCCH
PDSCH
PBCH DMRS
PDCCH DMRS
PDSCH DMRS
CSI-RS
PTRS

## C.5 Connection (Radiated)

The following clauses, describes the downlink Physical Channels that are transmitted during a connection i.e., when measurements are done.

### C.5.1 Measurement of Receiver Characteristics

*<Editor's note: OCNG for DMRS is FFS in Annex A.>*

Table C.5.1-1 is applicable for measurements in which uniform RS-to-EPRE boosting for all downlink physical channels, unless otherwise stated.

**Table C.5.1-1: Downlink Physical Channels transmitted during a connection (TDD)**

Parameter	Unit	Value
SSS transmit power	W	Test specific
EPRE ratio of PSS to SSS	dB	0
EPRE ratio of PBCH DMRS to SSS	dB	0
EPRE ratio of PBCH to PBCH DMRS	dB	0
EPRE ratio of PDCCH DMRS to SSS	dB	0
EPRE ratio of PDCCH to PDCCH DMRS	dB	0
EPRE ratio of PDSCH DMRS to SSS	dB	0
EPRE ratio of PDSCH to PDSCH DMRS	dB	0
EPRE ratio of CSI-RS to SSS	dB	0
EPRE ratio of PTRS to PDSCH	dB	Test specific
EPRE ratio of OCNG to SSS	dB	0

---

## Annex D: Void

## Annex E (normative): Environmental conditions

### E.1 General

This annex specifies the environmental requirements of the UE. Within these limits the requirements of the present documents shall be fulfilled.

### E.2 Environmental (Conducted)

The requirements in this clause apply to all types of UE(s).

#### E.2.1 Temperature

The UE shall fulfil all the requirements in the full temperature range of:

**Table E.2.1-1 Temperature conditions**

+15°C to +35°C	For normal conditions (with relative humidity of 25 % to 75 %)
-10°C to +55°C	For extreme conditions (see IEC publications 68-2-1 and 68-2-2)

Outside this temperature range the UE, if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the UE exceed the transmitted levels as defined in TS 38.101-1 [6, Section 6.2] for extreme operation.

#### E.2.2 Voltage

The UE shall fulfil all the requirements in the full voltage range, i.e. the voltage range between the extreme voltages.

The manufacturer shall declare the lower and higher extreme voltages and the approximate shutdown voltage. For the equipment that can be operated from one or more of the power sources listed below, the lower extreme voltage shall not be higher, and the higher extreme voltage shall not be lower than that specified below.

**Table E.2.2-1 Voltage conditions**

Power source	Lower extreme voltage	Higher extreme voltage	Normal conditions voltage
AC mains	0,9 * nominal	1,1 * nominal	nominal
Regulated lead acid battery	0,9 * nominal	1,3 * nominal	1,1 * nominal
Non regulated batteries: Leclanché Lithium Mercury/nickel & cadmium	0,85 * nominal 0,95 * nominal 0,90 * nominal	Nominal 1,1 * Nominal	Nominal 1,1 * Nominal Nominal

Outside this voltage range the UE if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the UE exceed the transmitted levels as defined in TS 38.101-1[6, Section 6.2] for extreme operation. In particular, the UE shall inhibit all RF transmissions when the power supply voltage is below the manufacturer declared shutdown voltage.

## E.2.3 Vibration

The UE shall fulfil all the requirements when vibrated at the following frequency/amplitudes.

**Table E.2.3-1 Vibration conditions**

Frequency	ASD (Acceleration Spectral Density) random vibration
5 Hz to 20 Hz	0,96 m <sup>2</sup> /s <sup>3</sup>
20 Hz to 500 Hz	0,96 m <sup>2</sup> /s <sup>3</sup> at 20 Hz, thereafter –3 dB/Octave

Outside the specified frequency range the UE, if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the UE exceed the transmitted levels as defined in TS 38.101-1[6] for extreme operation.

---

## E.3 Environmental (Radiated)

The requirements in this clause apply to all types of UE(s).

### E.3.1 Temperature

All requirements for UEs operating in FR2 are defined over the air and can only be tested in an OTA chamber.

The UE shall fulfil all the requirements in the temperature range defined in Table E.3.1-1.

**Table E.3.1-1: Temperature conditions**

+ 25 °C ± 10 °C	For normal (room temperature) conditions with relative humidity of 25% to 75%
-10°C to +55°C	For extreme conditions

Outside this temperature range the UE, if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the UE exceed the transmitted levels as defined in TS38.101-2 [7, Section 6.2] for extreme operation.

### E.3.2 Voltage

### E.3.3 Void

---

## Annex G: Void

---

## Annex H: Void

---

## Annex I: Void

## Annex J (informative): Change history

Change history							
Date	Meeting	tDoc	CR	Rev	Cat	Subject/Comment	New version
2018-07	RAN4 AH18-07	R4-1809554				Draft skeleton	0.0.1
2018-08	RAN4#88	R4-1811357				Skeleton update	0.0.2
2018-10	RAN4#88 bis	R4-1814237				Approved Text Proposal in RAN4#88bis: R4-1814053, "TP on performance specification 38.101-4 Chapter 4 general part" R4-1814054, "TP to TS 38.101-4: FR1 PDSCH demodulation requirements (5.2)" R4-1813924, "TP for introducing FR1 PDCCH requirements in TS 38.101-4 section 5.3" R4-1814058, "TP for 38.101-4 section 6.3 FR1 PMI test cases" R4-1814060, "Draft TP on FR1 Rank Indication Reporting Performance Requirements" R4-1814055, "Draft TP on FR2 PDSCH Demodulation Performance Requirements" R4-1814022, "TP to TS38.101-4 Section 7.3: PDCCH demodulation requirements" R4-1814059, "TP for 38.101-4 section 8.3 FR2 PMI test cases" R4-1814061, "Draft TP on FR2 Rank Indication Reporting Performance Requirements" R4-1813925, "TP for introducing demodulation performance requirements for interworking TS 38.101-4 section 9" R4-1814052, "TP for 38.101-4 section 10 CSI test cases of interworking" R4-1814066, "TP on channel models for TS38.101-4" R4-1814023, "TP to TS38.101-4 Annex C: Downlink physical channels" R4-1814024, "TP to TS38.101-4 Annex E: Environmental conditions"	0.1.0
2018-11	RAN4#89	R4-1816559				Approved Text Proposal in RAN4#89: R4-1814053, "TP on performance specification 38.101-4 Chapter 4 general part" R4-1814487, "TP for TS38.101-4 section 2 (Reference)" R4-1814488, "TP for TS38.101-4 section 3 (Definitions, symbols and abbreviations)" R4-1814579, "TP to TS 38.101-4: Annex A Measurement channels – PDSCH" R4-1814580, "TP to TS 38.101-4: Annex A Measurement channels - DL Control" R4-1814581, "TP to TS 38.101-4: Annex A Measurement channels – CSI" R4-1816395, "FR2 demod: Noc, Band groups and Ref point - TP for TS 38.101-4" R4-1816692, "TP to TS 38.101-4: Requirements applicability" R4-1816693, "TP for performance requirements for interworking (9)" R4-1816694, "TP to TS 38.101-4: FR1 PDSCH demodulation requirements (5.2)" R4-1816695, "Draft TP on FR2 PDSCH Demodulation Performance Requirements" R4-1816697, "TP for updating FR1 PDCCH requirements in TS 38.101-4 section 5.3" R4-1816699, "TP to TS 38.101-4: 5.4 FR1 PBCH demodulation requirements" R4-1816700, "TP to TS 38.101-4: 7.4 FR2 PBCH demodulation requirements" R4-1816701, "TP of introduction of FR1 CQI requirement (6.2)" R4-1816702, "TP to TS 38.101-4: FR2 CQI requirements (8.2)" R4-1816703, "Draft TP on FR1 Rank Indication Reporting Performance Requirements" R4-1816704, "Draft TP on FR2 Rank Indication Reporting Performance Requirements" R4-1816705, "TP for TS 38.101-4 FR1 PMI test requirement" R4-1816706, "TP to TS 38.101-4 FR2 PMI requirements" R4-1816712, "TP to TS 38.101-4: FR1 SDR requirements (5.5)" R4-1816713, "TP to TS38.101-4 Section 7.3: PDCCH demodulation requirements" R4-1816714, "TP for propagation conditions in TS 38.104-4(Annex B)"	0.2.0

2018-12	RAN#82	RP-182408			V1.0.0 is submitted to RAN for 1-step approval	1.0.0
2018-12	RAN#82	RP-182704			V1.0.1 with editorial changes	1.0.1
2018-12	RAN#82				Approved by plenary – Rel-15 spec under change control	15.0.0

---

## History

<b>Document history</b>		
V15.0.0	April 2019	Publication