

ETSI TS 138 212 V16.7.0 (2021-10)



**5G;
NR;
Multiplexing and channel coding
(3GPP TS 38.212 version 16.7.0 Release 16)**



Reference

RTS/TSGR-0138212vg70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 6 |
| 1 Scope | 7 |
| 2 References | 7 |
| 3 Definitions, symbols and abbreviations | 7 |
| 3.1 Definitions | 7 |
| 3.2 Symbols..... | 7 |
| 3.3 Abbreviations | 8 |
| 4 Mapping to physical channels | 9 |
| 4.1 Uplink..... | 9 |
| 4.2 Downlink | 9 |
| 4.3 Sidelink | 9 |
| 5 General procedures..... | 10 |
| 5.1 CRC calculation | 10 |
| 5.2 Code block segmentation and code block CRC attachment | 10 |
| 5.2.1 Polar coding | 10 |
| 5.2.2 Low density parity check coding | 11 |
| 5.3 Channel coding..... | 13 |
| 5.3.1 Polar coding | 13 |
| 5.3.1.1 Interleaving | 14 |
| 5.3.1.2 Polar encoding..... | 15 |
| 5.3.2 Low density parity check coding | 19 |
| 5.3.3 Channel coding of small block lengths | 26 |
| 5.3.3.1 Encoding of 1-bit information..... | 26 |
| 5.3.3.2 Encoding of 2-bit information..... | 26 |
| 5.3.3.3 Encoding of other small block lengths | 27 |
| 5.4 Rate matching..... | 27 |
| 5.4.1 Rate matching for Polar code..... | 27 |
| 5.4.1.1 Sub-block interleaving | 27 |
| 5.4.1.2 Bit selection..... | 29 |
| 5.4.1.3 Interleaving of coded bits..... | 29 |
| 5.4.2 Rate matching for LDPC code..... | 30 |
| 5.4.2.1 Bit selection..... | 30 |
| 5.4.2.2 Bit interleaving..... | 33 |
| 5.4.3 Rate matching for channel coding of small block lengths | 33 |
| 5.5 Code block concatenation | 33 |
| 6 Uplink transport channels and control information..... | 34 |
| 6.1 Random access channel..... | 34 |
| 6.2 Uplink shared channel | 34 |
| 6.2.1 Transport block CRC attachment..... | 34 |
| 6.2.2 LDPC base graph selection..... | 34 |
| 6.2.3 Code block segmentation and code block CRC attachment | 34 |
| 6.2.4 Channel coding of UL-SCH..... | 34 |
| 6.2.5 Rate matching | 35 |
| 6.2.6 Code block concatenation | 35 |
| 6.2.7 Data and control multiplexing | 35 |
| 6.3 Uplink control information..... | 47 |
| 6.3.1 Uplink control information on PUCCH..... | 47 |
| 6.3.1.1 UCI bit sequence generation | 47 |
| 6.3.1.1.1 HARQ-ACK/SR only | 47 |

| | | |
|-------------|--|----|
| 6.3.1.1.2 | CSI only..... | 47 |
| 6.3.1.1.3 | HARQ-ACK/SR and CSI | 55 |
| 6.3.1.2 | Code block segmentation and CRC attachment | 56 |
| 6.3.1.2.1 | UCI encoded by Polar code..... | 56 |
| 6.3.1.2.2 | UCI encoded by channel coding of small block lengths..... | 57 |
| 6.3.1.3 | Channel coding of UCI | 57 |
| 6.3.1.3.1 | UCI encoded by Polar code..... | 57 |
| 6.3.1.3.2 | UCI encoded by channel coding of small block lengths..... | 57 |
| 6.3.1.4 | Rate matching | 57 |
| 6.3.1.4.1 | UCI encoded by Polar code..... | 58 |
| 6.3.1.4.2 | UCI encoded by channel coding of small block lengths..... | 58 |
| 6.3.1.5 | Code block concatenation | 59 |
| 6.3.1.6 | Multiplexing of coded UCI bits to PUCCH | 59 |
| 6.3.2 | Uplink control information on PUSCH | 62 |
| 6.3.2.1 | UCI bit sequence generation | 62 |
| 6.3.2.1.1 | HARQ-ACK..... | 62 |
| 6.3.2.1.2 | CSI..... | 62 |
| 6.3.2.1.3 | CG-UCI | 68 |
| 6.3.2.1.4 | HARQ-ACK and CG-UCI..... | 69 |
| 6.3.2.2 | Code block segmentation and CRC attachment | 69 |
| 6.3.2.2.1 | UCI encoded by Polar code..... | 69 |
| 6.3.2.2.2 | UCI encoded by channel coding of small block lengths..... | 69 |
| 6.3.2.3 | Channel coding of UCI | 69 |
| 6.3.2.3.1 | UCI encoded by Polar code..... | 69 |
| 6.3.2.3.2 | UCI encoded by channel coding of small block lengths..... | 70 |
| 6.3.2.4 | Rate matching | 70 |
| 6.3.2.4.1 | UCI encoded by Polar code..... | 70 |
| 6.3.2.4.1.1 | HARQ-ACK | 70 |
| 6.3.2.4.1.2 | CSI part 1..... | 72 |
| 6.3.2.4.1.3 | CSI part 2..... | 75 |
| 6.3.2.4.1.4 | CG-UCI..... | 78 |
| 6.3.2.4.1.5 | HARQ-ACK and CG-UCI..... | 79 |
| 6.3.2.4.2 | UCI encoded by channel coding of small block lengths..... | 80 |
| 6.3.2.4.2.1 | HARQ-ACK | 80 |
| 6.3.2.4.2.2 | CSI part 1..... | 80 |
| 6.3.2.4.2.3 | CSI part 2..... | 80 |
| 6.3.2.4.2.4 | CG-UCI..... | 80 |
| 6.3.2.4.2.5 | HARQ-ACK and CG-UCI..... | 81 |
| 6.3.2.5 | Code block concatenation | 81 |
| 6.3.2.6 | Multiplexing of coded UCI bits to PUSCH..... | 81 |
| 7 | Downlink transport channels and control information..... | 81 |
| 7.1 | Broadcast channel..... | 81 |
| 7.1.1 | PBCH payload generation | 81 |
| 7.1.2 | Scrambling | 83 |
| 7.1.3 | Transport block CRC attachment..... | 84 |
| 7.1.4 | Channel coding | 84 |
| 7.1.5 | Rate matching | 84 |
| 7.2 | Downlink shared channel and paging channel | 84 |
| 7.2.1 | Transport block CRC attachment..... | 84 |
| 7.2.2 | LDPC base graph selection..... | 84 |
| 7.2.3 | Code block segmentation and code block CRC attachment | 85 |
| 7.2.4 | Channel coding | 85 |
| 7.2.5 | Rate matching | 85 |
| 7.2.6 | Code block concatenation..... | 85 |
| 7.3 | Downlink control information..... | 85 |
| 7.3.1 | DCI formats | 86 |
| 7.3.1.0 | DCI size alignment..... | 86 |
| 7.3.1.0.1 | DCI size alignment for DCI formats for scheduling of sidelink..... | 89 |
| 7.3.1.1 | DCI formats for scheduling of PUSCH..... | 90 |
| 7.3.1.1.1 | Format 0_0 | 90 |
| 7.3.1.1.2 | Format 0_1 | 93 |

| | | |
|-----------------|---|------------|
| 7.3.1.1.3 | Format 0_2 | 114 |
| 7.3.1.2 | DCI formats for scheduling of PDSCH..... | 120 |
| 7.3.1.2.1 | Format 1_0 | 120 |
| 7.3.1.2.2 | Format 1_1 | 123 |
| 7.3.1.2.3 | Format 1_2 | 138 |
| 7.3.1.3 | DCI formats for other purposes..... | 141 |
| 7.3.1.3.1 | Format 2_0 | 141 |
| 7.3.1.3.2 | Format 2_1 | 142 |
| 7.3.1.3.3 | Format 2_2 | 142 |
| 7.3.1.3.4 | Format 2_3 | 142 |
| 7.3.1.3.5 | Format 2_4 | 143 |
| 7.3.1.3.7 | Format 2_6 | 143 |
| 7.3.1.4 | DCI formats for scheduling of sidelink..... | 144 |
| 7.3.1.4.1 | Format 3_0 | 144 |
| 7.3.1.4.2 | Format 3_1 | 145 |
| 7.3.2 | CRC attachment..... | 145 |
| 7.3.3 | Channel coding | 146 |
| 7.3.4 | Rate matching | 146 |
| 8 | Sidelink transport channels and control information..... | 146 |
| 8.1 | Sidelink broadcast channel | 146 |
| 8.1.1 | (void) | 146 |
| 8.2 | Sidelink shared channel..... | 146 |
| 8.2.1 | Data and control multiplexing | 146 |
| 8.3 | Sidelink control information on PSCCH | 147 |
| 8.3.1 | 1 st -stage SCI formats..... | 148 |
| 8.3.1.1 | SCI format 1-A..... | 148 |
| 8.3.2 | CRC attachment..... | 149 |
| 8.3.3 | Channel coding | 149 |
| 8.3.4 | Rate Matching..... | 149 |
| 8.4 | Sidelink control information on PSSCH | 149 |
| 8.4.1 | 2 nd -stage SCI formats..... | 149 |
| 8.4.1.1 | SCI format 2-A..... | 149 |
| 8.4.1.2 | SCI format 2-B..... | 150 |
| 8.4.2 | CRC attachment..... | 150 |
| 8.4.3 | Channel coding | 150 |
| 8.4.4 | Rate Matching..... | 150 |
| 8.4.5 | Multiplexing of coded 2 nd -stage SCI bits to PSSCH..... | 151 |
| Annex A: | Change history | 152 |
| History | | 156 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the coding, multiplexing and mapping to physical channels for 5G NR.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.201: "NR; Physical Layer – General Description"
- [3] 3GPP TS 38.202: "NR; Services provided by the physical layer"
- [4] 3GPP TS 38.211: "NR; Physical channels and modulation"
- [5] 3GPP TS 38.213: "NR; Physical layer procedures for control"
- [6] 3GPP TS 38.214: "NR; Physical layer procedures for data"
- [7] 3GPP TS 38.215: "NR; Physical layer measurements"
- [8] 3GPP TS 38.321: "NR; Medium Access Control (MAC) protocol specification"
- [9] 3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification"
- [10] 3GPP TS 38.473: "NG-RAN; F1 Application Protocol (F1AP)"
- [11] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding"
- [12] 3GPP TS 23.287: "Architecture enhancements for 5G System (5GS) to support Vehicle-to-Everything (V2X) services"

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

3.2 Symbols

For the purposes of the present document, the following symbols apply:

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

| | |
|----------|---|
| BCH | Broadcast channel |
| CBG | Code block group |
| CBGTI | Code block group transmission information |
| CG | Configured grant |
| CG-DFI | CG downlink feedback information |
| CG-UCI | CG uplink control information |
| CORESET | Control resource set |
| COT | Channel occupancy time |
| CQI | Channel quality indicator |
| CRC | Cyclic redundancy check |
| CRI | CSI-RS resource indicator |
| CSI | Channel state information |
| CSI-RS | CSI reference signal |
| DAI | Downlink assignment index |
| DCI | Downlink control information |
| DL | Downlink |
| DL-SCH | Downlink shared channel |
| DMRS | Dedicated demodulation reference signal |
| HARQ | Hybrid automatic repeat request |
| HARQ-ACK | Hybrid automatic repeat request acknowledgement |
| LDPC | Low density parity check |
| LI | Layer indicator |
| MCS | Modulation and coding scheme |
| OFDM | Orthogonal frequency division multiplex |
| PBCH | Physical broadcast channel |
| PCH | Paging channel |
| PDCCH | Physical downlink control channel |
| PDSCH | Physical downlink shared channel |
| PMI | Precoding matrix indicator |
| PRB | Physical resource block |
| PRACH | Physical random access channel |
| PSBCH | Physical sidelink broadcast channel |
| PSCCH | Physical sidelink control channel |
| PSFCH | Physical sidelink feedback channel |
| PSSCH | Physical sidelink shared channel |
| PTRS | Phase-tracking reference signal |
| PUCCH | Physical uplink control channel |
| PUSCH | Physical uplink shared channel |
| RACH | Random access channel |
| RI | Rank indicator |
| RSRP | Reference signal received power |
| SCI | Sidelink control information |
| SFCI | Sidelink feedback control information |
| SFN | System frame number |
| SL | Sidelink |
| SL-BCH | Sidelink broadcast channel |
| SL-SCH | Sidelink shared channel |
| SR | Scheduling request |
| SRS | Sounding reference signal |
| SS | Synchronisation signal |
| SUL | Supplementary uplink |
| TPC | Transmit power control |
| TrCH | Transport channel |
| UCI | Uplink control information |
| UE | User equipment |

| | |
|-----------|------------------------|
| UL | Uplink |
| UL-SCH | Uplink shared channel |
| VRB | Virtual resource block |
| ZP CSI-RS | Zero power CSI-RS |

4 Mapping to physical channels

4.1 Uplink

Table 4.1-1 specifies the mapping of the uplink transport channels to their corresponding physical channels. Table 4.1-2 specifies the mapping of the uplink control channel information to its corresponding physical channel.

Table 4.1-1

| TrCH | Physical Channel |
|--------|------------------|
| UL-SCH | PUSCH |
| RACH | PRACH |

Table 4.1-2

| Control information | Physical Channel |
|---------------------|------------------|
| UCI | PUCCH, PUSCH |

4.2 Downlink

Table 4.2-1 specifies the mapping of the downlink transport channels to their corresponding physical channels. Table 4.2-2 specifies the mapping of the downlink control channel information to its corresponding physical channel.

Table 4.2-1

| TrCH | Physical Channel |
|--------|------------------|
| DL-SCH | PDSCH |
| BCH | PBCH |
| PCH | PDSCH |

Table 4.2-2

| Control information | Physical Channel |
|---------------------|------------------|
| DCI | PDCCH |

4.3 Sidelink

Table 4.3-1 specifies the mapping of the sidelink transport channels to their corresponding physical channels. Table 4.3-2 specifies the mapping of the sidelink control information and sidelink feedback control information to their corresponding physical channels.

Table 4.3-1

| TrCH | Physical Channel |
|--------|------------------|
| SL-SCH | PSSCH |
| SL-BCH | PSBCH |

Table 4.3-2

| Control information | Physical Channel |
|----------------------------|------------------|
| 1 st -stage SCI | PSCCH |
| 2 nd -stage SCI | PSSCH |
| SFCI | PSFCH |

5 General procedures

Data and control streams from/to MAC layer are encoded /decoded to offer transport and control services over the radio transmission link. Channel coding scheme is a combination of error detection, error correcting, rate matching, interleaving and transport channel or control information mapping onto/splitting from physical channels.

5.1 CRC calculation

Denote the input bits to the CRC computation by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, and the parity bits by $p_0, p_1, p_2, p_3, \dots, p_{L-1}$, where A is the size of the input sequence and L is the number of parity bits. The parity bits are generated by one of the following cyclic generator polynomials:

- $g_{\text{CRC24A}}(D) = [D^{24} + D^{23} + D^{18} + D^{17} + D^{14} + D^{11} + D^{10} + D^7 + D^6 + D^5 + D^4 + D^3 + D + 1]$ for a CRC length $L = 24$;
- $g_{\text{CRC24B}}(D) = [D^{24} + D^{23} + D^6 + D^5 + D + 1]$ for a CRC length $L = 24$;
- $g_{\text{CRC24C}}(D) = [D^{24} + D^{23} + D^{21} + D^{20} + D^{17} + D^{15} + D^{13} + D^{12} + D^8 + D^4 + D^2 + D + 1]$ for a CRC length $L = 24$;
- $g_{\text{CRC16}}(D) = [D^{16} + D^{12} + D^5 + 1]$ for a CRC length $L = 16$;
- $g_{\text{CRC11}}(D) = [D^{11} + D^{10} + D^9 + D^5 + 1]$ for a CRC length $L = 11$;
- $g_{\text{CRC6}}(D) = [D^6 + D^5 + 1]$ for a CRC length $L = 6$.

The encoding is performed in a systematic form, which means that in GF(2), the polynomial:

$$a_0 D^{A+L-1} + a_1 D^{A+L-2} + \dots + a_{A-1} D^L + p_0 D^{L-1} + p_1 D^{L-2} + \dots + p_{L-2} D^1 + p_{L-1}$$

yields a remainder equal to 0 when divided by the corresponding CRC generator polynomial.

The bits after CRC attachment are denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$, where $B = A + L$. The relation between a_k and b_k is:

$$b_k = a_k \quad \text{for } k = 0, 1, 2, \dots, A-1$$

$$b_k = p_{k-A} \quad \text{for } k = A, A+1, A+2, \dots, A+L-1.$$

5.2 Code block segmentation and code block CRC attachment

5.2.1 Polar coding

The input bit sequence to the code block segmentation is denoted by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, where $A > 0$.

if $I_{\text{seg}} = 1$

Number of code blocks: $C = 2$;

else

Number of code blocks: $C=1$

end if

$A' = \lceil A/C \rceil \cdot C$;

for $i = 0$ to $A'-A-1$

$a'_i = 0$;

end for

for $i = A'-A$ to $A'-1$

$a'_i = a_{i-(A'-A)}$;

end for

$s = 0$;

for $r = 0$ to $C-1$

for $k = 0$ to $A'/C-1$

$c_{rk} = a'_s$;

$s = s + 1$;

end for

The sequence $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(A'/C-1)}$ is used to calculate the CRC parity bits $p_{r0}, p_{r1}, p_{r2}, \dots, p_{r(L-1)}$ according to Clause 5.1 with a generator polynomial of length L .

for $k = A'/C$ to $A'/C+L-1$

$c_{rk} = p_{r(k-A'/C)}$;

end for

end for

The value of A is no larger than 1706.

5.2.2 Low density parity check coding

The input bit sequence to the code block segmentation is denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$, where $B > 0$. If B is larger than the maximum code block size K_{cb} , segmentation of the input bit sequence is performed and an additional CRC sequence of $L=24$ bits is attached to each code block.

For LDPC base graph 1, the maximum code block size is:

- $K_{cb} = 8448$.

For LDPC base graph 2, the maximum code block size is:

- $K_{cb} = 3840$.

Total number of code blocks C is determined by:

if $B \leq K_{cb}$

$$L=0$$

Number of code blocks: $C=1$

$$B'=B$$

else

$$L=24$$

Number of code blocks: $C=\lceil B/(K_{cb}-L) \rceil$.

$$B'=B+C \cdot L$$

end if

The bits output from code block segmentation are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where $0 \leq r < C$ is the code block number, and $K_r = K$ is the number of bits for the code block number r .

The number of bits K in each code block is calculated as:

$$K'=B'/C;$$

For LDPC base graph 1,

$$K_b=22.$$

For LDPC base graph 2,

if $B > 640$

$$K_b=10;$$

elseif $B > 560$

$$K_b=9;$$

elseif $B > 192$

$$K_b=8;$$

else

$$K_b=6;$$

end if

find the minimum value of Z in all sets of lifting sizes in Table 5.3.2-1, denoted as Z_c , such that $K_b \cdot Z_c \geq K'$, and set $K=22Z_c$ for LDPC base graph 1 and $K=10Z_c$ for LDPC base graph 2;

The bit sequence c_{rk} is calculated as:

$$s=0;$$

for $r=0$ to $C-1$

for $k=0$ to $K'-L-1$

$$c_{rk}=b_s;$$

```

    s = s + 1;
end for
if C > 1
    The sequence  $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K'-L-1)}$  is used to calculate the CRC parity bits  $p_{r0}, p_{r1}, p_{r2}, \dots, p_{r(L-1)}$ 
    according to Clause 5.1 with the generator polynomial  $g_{\text{CRC24B}}(D)$ .

    for  $k = K' - L$  to  $K' - 1$ 
         $c_{rk} = p_{r(k+L-K')}$ ;
    end for
end if
for  $k = K'$  to  $K - 1$  -- Insertion of filler bits
     $c_{rk} = \langle \text{NULL} \rangle$ ;
end for
end for

```

5.3 Channel coding

Usage of coding scheme for the different types of TrCH is shown in table 5.3-1. Usage of coding scheme for the different control information types is shown in table 5.3-2.

Table 5.3-1: Usage of channel coding scheme for TrCHs

| TrCH | Coding scheme |
|--------|---------------|
| UL-SCH | LDPC |
| DL-SCH | |
| PCH | |
| BCH | Polar code |

Table 5.3-2: Usage of channel coding scheme for control information

| Control Information | Coding scheme |
|---------------------|---------------|
| DCI | Polar code |
| UCI | Block code |
| | Polar code |

5.3.1 Polar coding

The bit sequence input for a given code block to channel coding is denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits to encode. After encoding the bits are denoted by $d_0, d_1, d_2, \dots, d_{N-1}$, where $N = 2^n$ and the value of n is determined by the following:

Denote by E the rate matching output sequence length as given in Clause 5.4.1;

If $E \leq (9/8) \cdot 2^{\lceil \log_2 E \rceil - 1}$ and $K/E < 9/16$

$$n_1 = \lceil \log_2 E \rceil - 1;$$

else

$$n_1 = \lceil \log_2 E \rceil;$$

end if

$$R_{\min} = 1/8;$$

$$n_2 = \lceil \log_2 (K / R_{\min}) \rceil;$$

$$n = \max\{\min\{n_1, n_2, n_{\max}\}, n_{\min}\}$$

where $n_{\min} = 5$.

UE is not expected to be configured with $K + n_{PC} > E$, where n_{PC} is the number of parity check bits defined in Clause 5.3.1.2.

5.3.1.1 Interleaving

The bit sequence $c_0, c_1, c_2, c_3, \dots, c_{K-1}$ is interleaved into bit sequence $c'_0, c'_1, c'_2, c'_3, \dots, c'_{K-1}$ as follows:

$$c'_k = c_{\Pi(k)}, \quad k = 0, 1, \dots, K-1$$

where the interleaving pattern $\Pi(k)$ is given by the following:

if $I_{LL} = 0$

$$\Pi(k) = k, \quad k = 0, 1, \dots, K-1$$

else

$$k = 0;$$

for $m = 0$ to $K_{LL}^{\max} - 1$

if $\Pi_{LL}^{\max}(m) \geq K_{LL}^{\max} - K$

$$\Pi(k) = \Pi_{LL}^{\max}(m) - (K_{LL}^{\max} - K);$$

$$k = k + 1;$$

end if

end for

end if

where $\Pi_{LL}^{\max}(m)$ is given by Table 5.3.1.1-1 and $K_{LL}^{\max} = 164$.

Table 5.3.1.1-1: Interleaving pattern $\Pi_{LL}^{\max}(m)$

| m | $\Pi_{LL}^{\max}(m)$ | m | $\Pi_{LL}^{\max}(m)$ | m | $\Pi_{LL}^{\max}(m)$ | m | $\Pi_{LL}^{\max}(m)$ | m | $\Pi_{LL}^{\max}(m)$ | m | $\Pi_{LL}^{\max}(m)$ |
|-----|----------------------|-----|----------------------|-----|----------------------|-----|----------------------|-----|----------------------|-----|----------------------|
| 0 | 0 | 28 | 67 | 56 | 122 | 84 | 68 | 112 | 33 | 140 | 38 |
| 1 | 2 | 29 | 69 | 57 | 123 | 85 | 73 | 113 | 36 | 141 | 144 |
| 2 | 4 | 30 | 70 | 58 | 126 | 86 | 78 | 114 | 44 | 142 | 39 |
| 3 | 7 | 31 | 71 | 59 | 127 | 87 | 84 | 115 | 47 | 143 | 145 |
| 4 | 9 | 32 | 72 | 60 | 129 | 88 | 90 | 116 | 64 | 144 | 40 |
| 5 | 14 | 33 | 76 | 61 | 132 | 89 | 92 | 117 | 74 | 145 | 146 |
| 6 | 19 | 34 | 77 | 62 | 134 | 90 | 94 | 118 | 79 | 146 | 41 |
| 7 | 20 | 35 | 81 | 63 | 138 | 91 | 96 | 119 | 85 | 147 | 147 |
| 8 | 24 | 36 | 82 | 64 | 139 | 92 | 99 | 120 | 97 | 148 | 148 |
| 9 | 25 | 37 | 83 | 65 | 140 | 93 | 102 | 121 | 100 | 149 | 149 |
| 10 | 26 | 38 | 87 | 66 | 1 | 94 | 105 | 122 | 103 | 150 | 150 |
| 11 | 28 | 39 | 88 | 67 | 3 | 95 | 107 | 123 | 117 | 151 | 151 |
| 12 | 31 | 40 | 89 | 68 | 5 | 96 | 109 | 124 | 125 | 152 | 152 |
| 13 | 34 | 41 | 91 | 69 | 8 | 97 | 112 | 125 | 131 | 153 | 153 |
| 14 | 42 | 42 | 93 | 70 | 10 | 98 | 114 | 126 | 136 | 154 | 154 |
| 15 | 45 | 43 | 95 | 71 | 15 | 99 | 116 | 127 | 142 | 155 | 155 |
| 16 | 49 | 44 | 98 | 72 | 21 | 100 | 121 | 128 | 12 | 156 | 156 |
| 17 | 50 | 45 | 101 | 73 | 27 | 101 | 124 | 129 | 17 | 157 | 157 |
| 18 | 51 | 46 | 104 | 74 | 29 | 102 | 128 | 130 | 23 | 158 | 158 |
| 19 | 53 | 47 | 106 | 75 | 32 | 103 | 130 | 131 | 37 | 159 | 159 |
| 20 | 54 | 48 | 108 | 76 | 35 | 104 | 133 | 132 | 48 | 160 | 160 |
| 21 | 56 | 49 | 110 | 77 | 43 | 105 | 135 | 133 | 75 | 161 | 161 |
| 22 | 58 | 50 | 111 | 78 | 46 | 106 | 141 | 134 | 80 | 162 | 162 |
| 23 | 59 | 51 | 113 | 79 | 52 | 107 | 6 | 135 | 86 | 163 | 163 |
| 24 | 61 | 52 | 115 | 80 | 55 | 108 | 11 | 136 | 137 | | |
| 25 | 62 | 53 | 118 | 81 | 57 | 109 | 16 | 137 | 143 | | |
| 26 | 65 | 54 | 119 | 82 | 60 | 110 | 22 | 138 | 13 | | |
| 27 | 66 | 55 | 120 | 83 | 63 | 111 | 30 | 139 | 18 | | |

5.3.1.2 Polar encoding

The Polar sequence $\mathbf{Q}_0^{N_{\max}-1} = \{Q_0^{N_{\max}}, Q_1^{N_{\max}}, \dots, Q_{N_{\max}-1}^{N_{\max}}\}$ is given by Table 5.3.1.2-1, where $0 \leq Q_i^{N_{\max}} \leq N_{\max} - 1$ denotes a bit index before Polar encoding for $i = 0, 1, \dots, N_{\max} - 1$ and $N_{\max} = 1024$. The Polar sequence $\mathbf{Q}_0^{N_{\max}-1}$ is in ascending order of reliability $W(Q_0^{N_{\max}}) < W(Q_1^{N_{\max}}) < \dots < W(Q_{N_{\max}-1}^{N_{\max}})$, where $W(Q_i^{N_{\max}})$ denotes the reliability of bit index $Q_i^{N_{\max}}$.

For any code block encoded to N bits, a same Polar sequence $\mathbf{Q}_0^{N-1} = \{Q_0^N, Q_1^N, Q_2^N, \dots, Q_{N-1}^N\}$ is used. The Polar sequence \mathbf{Q}_0^{N-1} is a subset of Polar sequence $\mathbf{Q}_0^{N_{\max}-1}$ with all elements $Q_i^{N_{\max}}$ of values less than N , ordered in ascending order of reliability $W(Q_0^N) < W(Q_1^N) < W(Q_2^N) < \dots < W(Q_{N-1}^N)$.

Denote $\overline{\mathbf{Q}}_I^N$ as a set of bit indices in Polar sequence \mathbf{Q}_0^{N-1} , and $\overline{\mathbf{Q}}_F^N$ as the set of other bit indices in Polar sequence \mathbf{Q}_0^{N-1} , where $\overline{\mathbf{Q}}_I^N$ and $\overline{\mathbf{Q}}_F^N$ are given in Clause 5.4.1.1, $|\overline{\mathbf{Q}}_I^N| = K + n_{PC}$, $|\overline{\mathbf{Q}}_F^N| = N - |\overline{\mathbf{Q}}_I^N|$, and n_{PC} is the number of parity check bits.

Denote $\mathbf{G}_N = (\mathbf{G}_2)^{\otimes n}$ as the n -th Kronecker power of matrix \mathbf{G}_2 , where $\mathbf{G}_2 = \begin{bmatrix} 1 & 0 \\ 1 & 1 \end{bmatrix}$.

For a bit index j with $j = 0, 1, \dots, N - 1$, denote \mathbf{g}_j as the j -th row of \mathbf{G}_N and $w(\mathbf{g}_j)$ as the row weight of \mathbf{g}_j , where $w(\mathbf{g}_j)$ is the number of ones in \mathbf{g}_j . Denote the set of bit indices for parity check bits as \mathbf{Q}_{PC}^N , where $|\mathbf{Q}_{PC}^N| = n_{PC}$. A number of $(n_{PC} - n_{PC}^{wm})$ parity check bits are placed in the $(n_{PC} - n_{PC}^{wm})$ least reliable bit indices in $\overline{\mathbf{Q}}_I^N$. A number of n_{PC}^{wm} other parity check bits are placed in the bit indices of minimum row weight in $\tilde{\mathbf{Q}}_I^N$, where $\tilde{\mathbf{Q}}_I^N$ denotes the $(|\overline{\mathbf{Q}}_I^N| - n_{PC})$ most reliable bit indices in $\overline{\mathbf{Q}}_I^N$; if there are more than n_{PC}^{wm} bit indices of the same minimum row weight in $\tilde{\mathbf{Q}}_I^N$, the n_{PC}^{wm} other parity check bits are placed in the n_{PC}^{wm} bit indices of the highest reliability and the minimum row weight in $\tilde{\mathbf{Q}}_I^N$.

Generate $\mathbf{u} = [u_0 \ u_1 \ u_2 \ \dots \ u_{N-1}]$ according to the following:

$$k = 0;$$

if $n_{PC} > 0$

$y_0 = 0; y_1 = 0; y_2 = 0; y_3 = 0; y_4 = 0;$

for $n=0$ to $N-1$

$y_t = y_0; y_0 = y_1; y_1 = y_2; y_2 = y_3; y_3 = y_4; y_4 = y_t;$

if $n \in \overline{\mathbf{Q}}_t^N$

if $n \in \mathbf{Q}_{PC}^N$

$u_n = y_0;$

else

$u_n = c_k';$

$k = k + 1;$

$y_0 = y_0 \oplus u_n;$

end if

else

$u_n = 0;$

end if

end for

else

for $n=0$ to $N-1$

if $n \in \overline{\mathbf{Q}}_t^N$

$u_n = c_k';$

$k = k + 1;$

else

$u_n = 0;$

end if

end for

end if

The output after encoding $\mathbf{d} = [d_0 \ d_1 \ d_2 \ \dots \ d_{N-1}]$ is obtained by $\mathbf{d} = \mathbf{u}\mathbf{G}_N$. The encoding is performed in GF(2).

Table 5.3.1.2-1: Polar sequence $Q_0^{N_{\max}-1}$ and its corresponding reliability $W(Q_i^{N_{\max}})$

| $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ | $W(Q_i^{N_{\max}})$ | $Q_i^{N_{\max}}$ |
|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|---------------------|------------------|
| 0 | 0 | 128 | 518 | 256 | 94 | 384 | 214 | 512 | 364 | 640 | 414 | 768 | 819 | 896 | 966 |
| 1 | 1 | 129 | 54 | 257 | 204 | 385 | 309 | 513 | 654 | 641 | 223 | 769 | 814 | 897 | 955 |
| 2 | 2 | 130 | 83 | 258 | 298 | 386 | 188 | 514 | 659 | 642 | 663 | 770 | 439 | 898 | 859 |
| 3 | 4 | 131 | 57 | 259 | 400 | 387 | 449 | 515 | 335 | 643 | 692 | 771 | 929 | 899 | 940 |
| 4 | 8 | 132 | 521 | 260 | 608 | 388 | 217 | 516 | 480 | 644 | 835 | 772 | 490 | 900 | 830 |
| 5 | 16 | 133 | 112 | 261 | 352 | 389 | 408 | 517 | 315 | 645 | 619 | 773 | 623 | 901 | 911 |
| 6 | 32 | 134 | 135 | 262 | 325 | 390 | 609 | 518 | 221 | 646 | 472 | 774 | 671 | 902 | 871 |
| 7 | 3 | 135 | 78 | 263 | 533 | 391 | 596 | 519 | 370 | 647 | 455 | 775 | 739 | 903 | 639 |
| 8 | 5 | 136 | 289 | 264 | 155 | 392 | 551 | 520 | 613 | 648 | 796 | 776 | 916 | 904 | 888 |
| 9 | 64 | 137 | 194 | 265 | 210 | 393 | 650 | 521 | 422 | 649 | 809 | 777 | 463 | 905 | 479 |
| 10 | 9 | 138 | 85 | 266 | 305 | 394 | 229 | 522 | 425 | 650 | 714 | 778 | 843 | 906 | 946 |
| 11 | 6 | 139 | 276 | 267 | 547 | 395 | 159 | 523 | 451 | 651 | 721 | 779 | 381 | 907 | 750 |
| 12 | 17 | 140 | 522 | 268 | 300 | 396 | 420 | 524 | 614 | 652 | 837 | 780 | 497 | 908 | 969 |
| 13 | 10 | 141 | 58 | 269 | 109 | 397 | 310 | 525 | 543 | 653 | 716 | 781 | 930 | 909 | 508 |
| 14 | 18 | 142 | 168 | 270 | 184 | 398 | 541 | 526 | 235 | 654 | 864 | 782 | 821 | 910 | 861 |
| 15 | 128 | 143 | 139 | 271 | 534 | 399 | 773 | 527 | 412 | 655 | 810 | 783 | 726 | 911 | 757 |
| 16 | 12 | 144 | 99 | 272 | 537 | 400 | 610 | 528 | 343 | 656 | 606 | 784 | 961 | 912 | 970 |
| 17 | 33 | 145 | 86 | 273 | 115 | 401 | 657 | 529 | 372 | 657 | 912 | 785 | 872 | 913 | 919 |
| 18 | 65 | 146 | 60 | 274 | 167 | 402 | 333 | 530 | 775 | 658 | 722 | 786 | 492 | 914 | 875 |
| 19 | 20 | 147 | 280 | 275 | 225 | 403 | 119 | 531 | 317 | 659 | 696 | 787 | 631 | 915 | 862 |
| 20 | 256 | 148 | 89 | 276 | 326 | 404 | 600 | 532 | 222 | 660 | 377 | 788 | 729 | 916 | 758 |
| 21 | 34 | 149 | 290 | 277 | 306 | 405 | 339 | 533 | 426 | 661 | 435 | 789 | 700 | 917 | 948 |
| 22 | 24 | 150 | 529 | 278 | 772 | 406 | 218 | 534 | 453 | 662 | 817 | 790 | 443 | 918 | 977 |
| 23 | 36 | 151 | 524 | 279 | 157 | 407 | 368 | 535 | 237 | 663 | 319 | 791 | 741 | 919 | 923 |
| 24 | 7 | 152 | 196 | 280 | 656 | 408 | 652 | 536 | 559 | 664 | 621 | 792 | 845 | 920 | 972 |
| 25 | 129 | 153 | 141 | 281 | 329 | 409 | 230 | 537 | 833 | 665 | 812 | 793 | 920 | 921 | 761 |
| 26 | 66 | 154 | 101 | 282 | 110 | 410 | 391 | 538 | 804 | 666 | 484 | 794 | 382 | 922 | 877 |
| 27 | 512 | 155 | 147 | 283 | 117 | 411 | 313 | 539 | 712 | 667 | 430 | 795 | 822 | 923 | 952 |
| 28 | 11 | 156 | 176 | 284 | 212 | 412 | 450 | 540 | 834 | 668 | 838 | 796 | 851 | 924 | 495 |
| 29 | 40 | 157 | 142 | 285 | 171 | 413 | 542 | 541 | 661 | 669 | 667 | 797 | 730 | 925 | 703 |
| 30 | 68 | 158 | 530 | 286 | 776 | 414 | 334 | 542 | 808 | 670 | 488 | 798 | 498 | 926 | 935 |
| 31 | 130 | 159 | 321 | 287 | 330 | 415 | 233 | 543 | 779 | 671 | 239 | 799 | 880 | 927 | 978 |
| 32 | 19 | 160 | 31 | 288 | 226 | 416 | 555 | 544 | 617 | 672 | 378 | 800 | 742 | 928 | 883 |
| 33 | 13 | 161 | 200 | 289 | 549 | 417 | 774 | 545 | 604 | 673 | 459 | 801 | 445 | 929 | 762 |
| 34 | 48 | 162 | 90 | 290 | 538 | 418 | 175 | 546 | 433 | 674 | 622 | 802 | 471 | 930 | 503 |
| 35 | 14 | 163 | 545 | 291 | 387 | 419 | 123 | 547 | 720 | 675 | 627 | 803 | 635 | 931 | 925 |
| 36 | 72 | 164 | 292 | 292 | 308 | 420 | 658 | 548 | 816 | 676 | 437 | 804 | 932 | 932 | 878 |
| 37 | 257 | 165 | 322 | 293 | 216 | 421 | 612 | 549 | 836 | 677 | 380 | 805 | 687 | 933 | 735 |
| 38 | 21 | 166 | 532 | 294 | 416 | 422 | 341 | 550 | 347 | 678 | 818 | 806 | 903 | 934 | 993 |
| 39 | 132 | 167 | 263 | 295 | 271 | 423 | 777 | 551 | 897 | 679 | 461 | 807 | 825 | 935 | 885 |
| 40 | 35 | 168 | 149 | 296 | 279 | 424 | 220 | 552 | 243 | 680 | 496 | 808 | 500 | 936 | 939 |
| 41 | 258 | 169 | 102 | 297 | 158 | 425 | 314 | 553 | 662 | 681 | 669 | 809 | 846 | 937 | 994 |
| 42 | 26 | 170 | 105 | 298 | 337 | 426 | 424 | 554 | 454 | 682 | 679 | 810 | 745 | 938 | 980 |
| 43 | 513 | 171 | 304 | 299 | 550 | 427 | 395 | 555 | 318 | 683 | 724 | 811 | 826 | 939 | 926 |
| 44 | 80 | 172 | 296 | 300 | 672 | 428 | 673 | 556 | 675 | 684 | 841 | 812 | 732 | 940 | 764 |
| 45 | 37 | 173 | 163 | 301 | 118 | 429 | 583 | 557 | 618 | 685 | 629 | 813 | 446 | 941 | 941 |
| 46 | 25 | 174 | 92 | 302 | 332 | 430 | 355 | 558 | 898 | 686 | 351 | 814 | 962 | 942 | 967 |
| 47 | 22 | 175 | 47 | 303 | 579 | 431 | 287 | 559 | 781 | 687 | 467 | 815 | 936 | 943 | 886 |
| 48 | 136 | 176 | 267 | 304 | 540 | 432 | 183 | 560 | 376 | 688 | 438 | 816 | 475 | 944 | 831 |
| 49 | 260 | 177 | 385 | 305 | 389 | 433 | 234 | 561 | 428 | 689 | 737 | 817 | 853 | 945 | 947 |
| 50 | 264 | 178 | 546 | 306 | 173 | 434 | 125 | 562 | 665 | 690 | 251 | 818 | 867 | 946 | 507 |
| 51 | 38 | 179 | 324 | 307 | 121 | 435 | 557 | 563 | 736 | 691 | 462 | 819 | 637 | 947 | 889 |
| 52 | 514 | 180 | 208 | 308 | 553 | 436 | 660 | 564 | 567 | 692 | 442 | 820 | 907 | 948 | 984 |
| 53 | 96 | 181 | 386 | 309 | 199 | 437 | 616 | 565 | 840 | 693 | 441 | 821 | 487 | 949 | 751 |
| 54 | 67 | 182 | 150 | 310 | 784 | 438 | 342 | 566 | 625 | 694 | 469 | 822 | 695 | 950 | 942 |
| 55 | 41 | 183 | 153 | 311 | 179 | 439 | 316 | 567 | 238 | 695 | 247 | 823 | 746 | 951 | 996 |
| 56 | 144 | 184 | 165 | 312 | 228 | 440 | 241 | 568 | 359 | 696 | 683 | 824 | 828 | 952 | 971 |
| 57 | 28 | 185 | 106 | 313 | 338 | 441 | 778 | 569 | 457 | 697 | 842 | 825 | 753 | 953 | 890 |
| 58 | 69 | 186 | 55 | 314 | 312 | 442 | 563 | 570 | 399 | 698 | 738 | 826 | 854 | 954 | 509 |
| 59 | 42 | 187 | 328 | 315 | 704 | 443 | 345 | 571 | 787 | 699 | 899 | 827 | 857 | 955 | 949 |
| 60 | 516 | 188 | 536 | 316 | 390 | 444 | 452 | 572 | 591 | 700 | 670 | 828 | 504 | 956 | 973 |
| 61 | 49 | 189 | 577 | 317 | 174 | 445 | 397 | 573 | 678 | 701 | 783 | 829 | 799 | 957 | 1000 |
| 62 | 74 | 190 | 548 | 318 | 554 | 446 | 403 | 574 | 434 | 702 | 849 | 830 | 255 | 958 | 892 |
| 63 | 272 | 191 | 113 | 319 | 581 | 447 | 207 | 575 | 677 | 703 | 820 | 831 | 964 | 959 | 950 |
| 64 | 160 | 192 | 154 | 320 | 393 | 448 | 674 | 576 | 349 | 704 | 728 | 832 | 909 | 960 | 863 |
| 65 | 520 | 193 | 79 | 321 | 283 | 449 | 558 | 577 | 245 | 705 | 928 | 833 | 719 | 961 | 759 |
| 66 | 288 | 194 | 269 | 322 | 122 | 450 | 785 | 578 | 458 | 706 | 791 | 834 | 477 | 962 | 1008 |
| 67 | 528 | 195 | 108 | 323 | 448 | 451 | 432 | 579 | 666 | 707 | 367 | 835 | 915 | 963 | 510 |
| 68 | 192 | 196 | 578 | 324 | 353 | 452 | 357 | 580 | 620 | 708 | 901 | 836 | 638 | 964 | 979 |
| 69 | 544 | 197 | 224 | 325 | 561 | 453 | 187 | 581 | 363 | 709 | 630 | 837 | 748 | 965 | 953 |
| 70 | 70 | 198 | 166 | 326 | 203 | 454 | 236 | 582 | 127 | 710 | 685 | 838 | 944 | 966 | 763 |
| 71 | 44 | 199 | 519 | 327 | 63 | 455 | 664 | 583 | 191 | 711 | 844 | 839 | 869 | 967 | 974 |
| 72 | 131 | 200 | 552 | 328 | 340 | 456 | 624 | 584 | 782 | 712 | 633 | 840 | 491 | 968 | 954 |
| 73 | 81 | 201 | 195 | 329 | 394 | 457 | 587 | 585 | 407 | 713 | 711 | 841 | 699 | 969 | 879 |
| 74 | 50 | 202 | 270 | 330 | 527 | 458 | 780 | 586 | 436 | 714 | 253 | 842 | 754 | 970 | 981 |
| 75 | 73 | 203 | 641 | 331 | 582 | 459 | 705 | 587 | 626 | 715 | 691 | 843 | 858 | 971 | 982 |
| 76 | 15 | 204 | 523 | 332 | 556 | 460 | 126 | 588 | 571 | 716 | 824 | 844 | 478 | 972 | 927 |
| 77 | 320 | 205 | 275 | 333 | 181 | 461 | 242 | 589 | 465 | 717 | 902 | 845 | 968 | 973 | 995 |
| 78 | 133 | 206 | 580 | 334 | 295 | 462 | 565 | 590 | 681 | 718 | 686 | 846 | 383 | 974 | 765 |
| 79 | 52 | 207 | 291 | 335 | 285 | 463 | 398 | 591 | 246 | 719 | 740 | 847 | 910 | 975 | 956 |
| 80 | 23 | 208 | 59 | 336 | 232 | 464 | 346 | 592 | 707 | 720 | 850 | 848 | 815 | 976 | 887 |
| 81 | 134 | 209 | 169 | 337 | 124 | 465 | 456 | 593 | 350 | 721 | 375 | 849 | 976 | 977 | 985 |
| 82 | 384 | 210 | 560 | 338 | 205 | 466 | 358 | 594 | 599 | 722 | 444 | 850 | 870 | 978 | 997 |
| 83 | 76 | 211 | 114 | 339 | 182 | 467 | 405 | 595 | 668 | 723 | 470 | 851 | 917 | 979 | 986 |
| 84 | 137 | 212 | 277 | 340 | 643 | 468 | 303 | 596 | 790 | 724 | 483 | 852 | 727 | 980 | 943 |
| 85 | 82 | 213 | 156 | 341 | 562 | 469 | 569 | 597 | 460 | 725 | 415 | 853 | 493 | 981 | 891 |
| 86 | 56 | 214 | 87 | 342 | 286 | 470 | 244 | 598 | 249 | 726 | 485 | 854 | 873 | 982 | 998 |

| | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| 87 | 27 | 215 | 197 | 343 | 585 | 471 | 595 | 599 | 682 | 727 | 905 | 855 | 701 | 983 | 766 |
| 88 | 97 | 216 | 116 | 344 | 299 | 472 | 189 | 600 | 573 | 728 | 795 | 856 | 931 | 984 | 511 |
| 89 | 39 | 217 | 170 | 345 | 354 | 473 | 566 | 601 | 411 | 729 | 473 | 857 | 756 | 985 | 988 |
| 90 | 259 | 218 | 61 | 346 | 211 | 474 | 676 | 602 | 803 | 730 | 634 | 858 | 860 | 986 | 1001 |
| 91 | 84 | 219 | 531 | 347 | 401 | 475 | 361 | 603 | 789 | 731 | 744 | 859 | 499 | 987 | 951 |
| 92 | 138 | 220 | 525 | 348 | 185 | 476 | 706 | 604 | 709 | 732 | 852 | 860 | 731 | 988 | 1002 |
| 93 | 145 | 221 | 642 | 349 | 396 | 477 | 589 | 605 | 365 | 733 | 960 | 861 | 823 | 989 | 893 |
| 94 | 261 | 222 | 281 | 350 | 344 | 478 | 215 | 606 | 440 | 734 | 865 | 862 | 922 | 990 | 975 |
| 95 | 29 | 223 | 278 | 351 | 586 | 479 | 786 | 607 | 628 | 735 | 693 | 863 | 874 | 991 | 894 |
| 96 | 43 | 224 | 526 | 352 | 645 | 480 | 647 | 608 | 689 | 736 | 797 | 864 | 918 | 992 | 1009 |
| 97 | 98 | 225 | 177 | 353 | 593 | 481 | 348 | 609 | 374 | 737 | 906 | 865 | 502 | 993 | 955 |
| 98 | 515 | 226 | 293 | 354 | 535 | 482 | 419 | 610 | 423 | 738 | 715 | 866 | 933 | 994 | 1004 |
| 99 | 88 | 227 | 388 | 355 | 240 | 483 | 406 | 611 | 466 | 739 | 807 | 867 | 743 | 995 | 1010 |
| 100 | 140 | 228 | 91 | 356 | 206 | 484 | 464 | 612 | 793 | 740 | 474 | 868 | 760 | 996 | 957 |
| 101 | 30 | 229 | 584 | 357 | 95 | 485 | 680 | 613 | 250 | 741 | 636 | 869 | 881 | 997 | 983 |
| 102 | 146 | 230 | 769 | 358 | 327 | 486 | 801 | 614 | 371 | 742 | 694 | 870 | 494 | 998 | 958 |
| 103 | 71 | 231 | 198 | 359 | 564 | 487 | 362 | 615 | 481 | 743 | 254 | 871 | 702 | 999 | 987 |
| 104 | 262 | 232 | 172 | 360 | 800 | 488 | 590 | 616 | 574 | 744 | 717 | 872 | 921 | 1000 | 1012 |
| 105 | 265 | 233 | 120 | 361 | 402 | 489 | 409 | 617 | 413 | 745 | 575 | 873 | 501 | 1001 | 999 |
| 106 | 161 | 234 | 201 | 362 | 356 | 490 | 570 | 618 | 603 | 746 | 913 | 874 | 876 | 1002 | 1016 |
| 107 | 576 | 235 | 336 | 363 | 307 | 491 | 788 | 619 | 366 | 747 | 798 | 875 | 847 | 1003 | 767 |
| 108 | 45 | 236 | 62 | 364 | 301 | 492 | 597 | 620 | 468 | 748 | 811 | 876 | 992 | 1004 | 989 |
| 109 | 100 | 237 | 282 | 365 | 417 | 493 | 572 | 621 | 655 | 749 | 379 | 877 | 447 | 1005 | 1003 |
| 110 | 640 | 238 | 143 | 366 | 213 | 494 | 219 | 622 | 900 | 750 | 697 | 878 | 733 | 1006 | 990 |
| 111 | 51 | 239 | 103 | 367 | 568 | 495 | 311 | 623 | 805 | 751 | 431 | 879 | 827 | 1007 | 1005 |
| 112 | 148 | 240 | 178 | 368 | 832 | 496 | 708 | 624 | 615 | 752 | 607 | 880 | 934 | 1008 | 959 |
| 113 | 46 | 241 | 294 | 369 | 588 | 497 | 598 | 625 | 684 | 753 | 489 | 881 | 882 | 1009 | 1011 |
| 114 | 75 | 242 | 93 | 370 | 186 | 498 | 601 | 626 | 710 | 754 | 866 | 882 | 937 | 1010 | 1013 |
| 115 | 266 | 243 | 644 | 371 | 646 | 499 | 651 | 627 | 429 | 755 | 723 | 883 | 963 | 1011 | 895 |
| 116 | 273 | 244 | 202 | 372 | 404 | 500 | 421 | 628 | 794 | 756 | 486 | 884 | 747 | 1012 | 1006 |
| 117 | 517 | 245 | 592 | 373 | 227 | 501 | 792 | 629 | 252 | 757 | 908 | 885 | 505 | 1013 | 1014 |
| 118 | 104 | 246 | 323 | 374 | 896 | 502 | 802 | 630 | 373 | 758 | 718 | 886 | 855 | 1014 | 1017 |
| 119 | 162 | 247 | 392 | 375 | 594 | 503 | 611 | 631 | 605 | 759 | 813 | 887 | 924 | 1015 | 1018 |
| 120 | 53 | 248 | 297 | 376 | 418 | 504 | 602 | 632 | 848 | 760 | 476 | 888 | 734 | 1016 | 991 |
| 121 | 193 | 249 | 770 | 377 | 302 | 505 | 410 | 633 | 690 | 761 | 856 | 889 | 829 | 1017 | 1020 |
| 122 | 152 | 250 | 107 | 378 | 649 | 506 | 231 | 634 | 713 | 762 | 839 | 890 | 965 | 1018 | 1007 |
| 123 | 77 | 251 | 180 | 379 | 771 | 507 | 688 | 635 | 632 | 763 | 725 | 891 | 938 | 1019 | 1015 |
| 124 | 164 | 252 | 151 | 380 | 360 | 508 | 653 | 636 | 482 | 764 | 698 | 892 | 884 | 1020 | 1019 |
| 125 | 768 | 253 | 209 | 381 | 539 | 509 | 248 | 637 | 806 | 765 | 914 | 893 | 506 | 1021 | 1021 |
| 126 | 268 | 254 | 284 | 382 | 111 | 510 | 369 | 638 | 427 | 766 | 752 | 894 | 749 | 1022 | 1022 |
| 127 | 274 | 255 | 648 | 383 | 331 | 511 | 190 | 639 | 904 | 767 | 868 | 895 | 945 | 1023 | 1023 |

5.3.2 Low density parity check coding

The bit sequence input for a given code block to channel coding is denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits to encode as defined in Clause 5.2.2. After encoding the bits are denoted by $d_0, d_1, d_2, \dots, d_{N-1}$, where $N = 66Z_c$ for LDPC base graph 1 and $N = 50Z_c$ for LDPC base graph 2, and the value of Z_c is given in Clause 5.2.2.

For a code block encoded by LDPC, the following encoding procedure applies:

1) Find the set with index i_{LS} in Table 5.3.2-1 which contains Z_c .

2) for $k = 2Z_c$ to $K-1$

if $c_k \neq \text{NULL}$

$d_{k-2Z_c} = c_k$;

else

$c_k = 0$;

$d_{k-2Z_c} = \text{NULL}$;

end if

end for

3) Generate $N + 2Z_c - K$ parity bits $\mathbf{w} = [w_0, w_1, w_2, \dots, w_{N+2Z_c-K-1}]^T$ such that $\mathbf{H} \times \begin{bmatrix} \mathbf{c} \\ \mathbf{w} \end{bmatrix} = \mathbf{0}$, where

$\mathbf{c} = [c_0, c_1, c_2, \dots, c_{K-1}]^T$; $\mathbf{0}$ is a column vector of all elements equal to 0. The encoding is performed in GF(2).

For LDPC base graph 1, a matrix of \mathbf{H}_{BG} has 46 rows with row indices $i = 0, 1, 2, \dots, 45$ and 68 columns with column indices $j = 0, 1, 2, \dots, 67$. For LDPC base graph 2, a matrix of \mathbf{H}_{BG} has 42 rows with row indices $i = 0, 1, 2, \dots, 41$ and 52 columns with column indices $j = 0, 1, 2, \dots, 51$. The elements in \mathbf{H}_{BG} with row and column indices given in Table 5.3.2-2 (for LDPC base graph 1) and Table 5.3.2-3 (for LDPC base graph 2) are of value 1, and all other elements in \mathbf{H}_{BG} are of value 0.

The matrix \mathbf{H} is obtained by replacing each element of \mathbf{H}_{BG} with a $Z_c \times Z_c$ matrix, according to the following:

- Each element of value 0 in \mathbf{H}_{BG} is replaced by an all zero matrix $\mathbf{0}$ of size $Z_c \times Z_c$;
- Each element of value 1 in \mathbf{H}_{BG} is replaced by a circular permutation matrix $\mathbf{I}(P_{i,j})$ of size $Z_c \times Z_c$, where i and j are the row and column indices of the element, and $\mathbf{I}(P_{i,j})$ is obtained by circularly shifting the identity matrix \mathbf{I} of size $Z_c \times Z_c$ to the right $P_{i,j}$ times. The value of $P_{i,j}$ is given by $P_{i,j} = \text{mod}(V_{i,j}, Z_c)$. The value of $V_{i,j}$ is given by Tables 5.3.2-2 and 5.3.2-3 according to the set index i_{LS} and LDPC base graph.

4) for $k = K$ to $N + 2Z_c - 1$

$$d_{k-2Z_c} = w_{k-K};$$

end for

Table 5.3.2-1: Sets of LDPC lifting size Z

| Set index (i_{LS}) | Set of lifting sizes (Z) |
|------------------------|----------------------------------|
| 0 | {2, 4, 8, 16, 32, 64, 128, 256} |
| 1 | {3, 6, 12, 24, 48, 96, 192, 384} |
| 2 | {5, 10, 20, 40, 80, 160, 320} |
| 3 | {7, 14, 28, 56, 112, 224} |
| 4 | {9, 18, 36, 72, 144, 288} |
| 5 | {11, 22, 44, 88, 176, 352} |
| 6 | {13, 26, 52, 104, 208} |
| 7 | {15, 30, 60, 120, 240} |

Table 5.3.2-2: LDPC base graph 1 (H_{BG}) and its parity check matrices ($V_{i,j}$)

| H_{BG} | | $V_{i,j}$ | | | | | | | | H_{BG} | | $V_{i,j}$ | | | | | | | | | |
|---------------|------------------|--------------------|-----|-----|-----|-----|-----|-----|-----|---------------|------------------|--------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Row index i | Column index j | Set index i_{LS} | | | | | | | | Row index i | Column index j | Set index i_{LS} | | | | | | | | | |
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | | |
| 0 | 0 | 250 | 307 | 73 | 223 | 211 | 294 | 0 | 135 | 15 | 1 | 96 | 2 | 290 | 120 | 0 | 348 | 6 | 138 | | |
| | 1 | 69 | 19 | 15 | 16 | 198 | 118 | 0 | 227 | | 10 | 65 | 210 | 60 | 131 | 183 | 15 | 81 | 220 | | |
| | 2 | 226 | 50 | 103 | 94 | 188 | 167 | 0 | 126 | | 13 | 63 | 318 | 130 | 209 | 108 | 81 | 182 | 173 | | |
| | 3 | 159 | 369 | 49 | 91 | 186 | 330 | 0 | 134 | | 18 | 75 | 55 | 184 | 209 | 68 | 176 | 53 | 142 | | |
| | 5 | 100 | 181 | 240 | 74 | 219 | 207 | 0 | 84 | | 25 | 179 | 269 | 51 | 81 | 64 | 113 | 46 | 49 | | |
| | 6 | 10 | 216 | 39 | 10 | 4 | 165 | 0 | 83 | | 37 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| | 9 | 59 | 317 | 15 | 0 | 29 | 243 | 0 | 53 | | 1 | 64 | 13 | 69 | 154 | 270 | 190 | 88 | 78 | | |
| | 10 | 229 | 288 | 162 | 205 | 144 | 250 | 0 | 225 | | 3 | 49 | 338 | 140 | 164 | 13 | 293 | 198 | 152 | | |
| | 11 | 110 | 109 | 215 | 216 | 116 | 1 | 0 | 205 | | 11 | 49 | 57 | 45 | 43 | 99 | 332 | 160 | 84 | | |
| | 12 | 191 | 17 | 164 | 21 | 216 | 339 | 0 | 128 | | 20 | 51 | 289 | 115 | 189 | 54 | 331 | 122 | 5 | | |
| | 13 | 9 | 357 | 133 | 215 | 115 | 201 | 0 | 75 | | 22 | 154 | 57 | 300 | 101 | 0 | 114 | 182 | 205 | | |
| | 15 | 195 | 215 | 298 | 14 | 233 | 53 | 0 | 135 | | 38 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| | 16 | 23 | 106 | 110 | 70 | 144 | 347 | 0 | 217 | | 0 | 7 | 260 | 257 | 56 | 153 | 110 | 91 | 183 | | |
| | 18 | 190 | 242 | 113 | 141 | 95 | 304 | 0 | 220 | | 14 | 164 | 303 | 147 | 110 | 137 | 228 | 184 | 112 | | |
| | 19 | 35 | 180 | 16 | 198 | 216 | 167 | 0 | 90 | | 16 | 59 | 81 | 128 | 200 | 0 | 247 | 30 | 106 | | |
| | 20 | 239 | 330 | 189 | 104 | 73 | 47 | 0 | 105 | | 17 | 1 | 358 | 51 | 63 | 0 | 116 | 3 | 219 | | |
| | 21 | 31 | 346 | 32 | 81 | 261 | 188 | 0 | 137 | | 21 | 144 | 375 | 228 | 4 | 162 | 190 | 155 | 129 | | |
| | 22 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | | 39 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| | 23 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 1 | 42 | 130 | 260 | 199 | 161 | 47 | 1 | 183 | | |
| | 1 | 0 | 2 | 76 | 303 | 141 | 179 | 77 | 22 | | 96 | 18 | 12 | 233 | 163 | 294 | 110 | 151 | 286 | 41 | 215 |
| | | 2 | 239 | 76 | 294 | 45 | 162 | 225 | 11 | | 236 | | 13 | 8 | 280 | 291 | 200 | 0 | 246 | 167 | 180 |
| | | 3 | 117 | 73 | 27 | 151 | 223 | 96 | 124 | | 136 | | 18 | 155 | 132 | 141 | 143 | 241 | 181 | 68 | 143 |
| | | 4 | 124 | 288 | 261 | 46 | 256 | 338 | 0 | | 221 | | 19 | 147 | 4 | 295 | 186 | 144 | 73 | 148 | 14 |
| 5 | | 71 | 144 | 161 | 119 | 160 | 268 | 10 | 128 | 40 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 7 | | 222 | 331 | 133 | 157 | 76 | 112 | 0 | 92 | 0 | 60 | | 145 | 64 | 8 | 0 | 87 | 12 | 179 | | |
| 8 | | 104 | 331 | 4 | 133 | 202 | 302 | 0 | 172 | 1 | 73 | | 213 | 181 | 6 | 0 | 110 | 6 | 108 | | |
| 9 | | 173 | 178 | 80 | 87 | 117 | 50 | 2 | 56 | 7 | 72 | | 344 | 101 | 103 | 118 | 147 | 166 | 159 | | |
| 11 | | 220 | 295 | 129 | 206 | 109 | 167 | 16 | 11 | 8 | 127 | | 242 | 270 | 198 | 144 | 258 | 184 | 138 | | |
| 12 | | 102 | 342 | 300 | 93 | 15 | 253 | 60 | 189 | 10 | 224 | | 197 | 41 | 8 | 0 | 204 | 191 | 196 | | |
| 14 | | 109 | 217 | 76 | 79 | 72 | 334 | 0 | 95 | 41 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 15 | | 132 | 99 | 266 | 9 | 152 | 242 | 6 | 85 | 0 | 151 | | 187 | 301 | 105 | 265 | 89 | 6 | 77 | | |
| 16 | | 142 | 354 | 72 | 118 | 158 | 257 | 30 | 153 | 3 | 186 | | 206 | 162 | 210 | 81 | 65 | 12 | 187 | | |
| 17 | | 155 | 114 | 83 | 194 | 147 | 133 | 0 | 87 | 9 | 217 | | 264 | 40 | 121 | 90 | 155 | 15 | 203 | | |
| 19 | | 255 | 331 | 260 | 31 | 156 | 9 | 168 | 163 | 11 | 47 | | 341 | 130 | 214 | 144 | 244 | 5 | 167 | | |
| 21 | | 28 | 112 | 301 | 187 | 119 | 302 | 31 | 216 | 22 | 160 | | 59 | 10 | 183 | 228 | 30 | 30 | 130 | | |
| 22 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 105 | 0 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 23 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 42 | 1 | | 249 | 205 | 79 | 192 | 64 | 162 | 6 | 197 | |
| 24 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 5 | 121 | | 102 | 175 | 131 | 46 | 264 | 86 | 122 | | |
| 2 | | 0 | 106 | 205 | 68 | 207 | 258 | 226 | 132 | 189 | 21 | | 16 | 109 | 328 | 132 | 220 | 266 | 346 | 96 | 215 |
| | | 1 | 111 | 250 | 7 | 203 | 167 | 35 | 37 | 4 | | | 20 | 131 | 213 | 283 | 50 | 9 | 143 | 42 | 65 |
| | | 2 | 185 | 328 | 80 | 31 | 220 | 213 | 21 | 225 | | | 21 | 171 | 97 | 103 | 106 | 18 | 109 | 199 | 216 |
| | | 4 | 63 | 332 | 280 | 176 | 133 | 302 | 180 | 151 | | | 43 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | | 5 | 117 | 256 | 38 | 180 | 243 | 111 | 4 | 236 | | | 0 | 64 | 30 | 177 | 53 | 72 | 280 | 44 | 25 |
| | 6 | 93 | 161 | 227 | 186 | 202 | 265 | 149 | 117 | 12 | | 142 | 11 | 20 | 0 | 189 | 157 | 58 | 47 | | |
| | 7 | 229 | 267 | 202 | 95 | 218 | 128 | 48 | 179 | 13 | | 188 | 233 | 55 | 3 | 72 | 236 | 130 | 126 | | |
| | 8 | 177 | 160 | 200 | 153 | 63 | 237 | 38 | 92 | 17 | | 158 | 22 | 316 | 148 | 257 | 113 | 131 | 178 | | |
| | 9 | 95 | 63 | 71 | 177 | 0 | 294 | 122 | 24 | 44 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| | 10 | 39 | 129 | 106 | 70 | 3 | 127 | 195 | 68 | 1 | | 156 | 24 | 249 | 88 | 180 | 18 | 45 | 185 | | |
| | 13 | 142 | 200 | 295 | 77 | 74 | 110 | 155 | 6 | 2 | | 147 | 89 | 50 | 203 | 0 | 6 | 18 | 127 | | |
| | 14 | 225 | 88 | 283 | 214 | 229 | 286 | 28 | 101 | 10 | | 170 | 61 | 133 | 168 | 0 | 181 | 132 | 117 | | |
| | 15 | 225 | 53 | 301 | 77 | 0 | 125 | 85 | 33 | 18 | | 152 | 27 | 105 | 122 | 165 | 304 | 100 | 199 | | |
| | 17 | 245 | 131 | 184 | 198 | 216 | 131 | 47 | 96 | 45 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| | 18 | 205 | 240 | 246 | 117 | 269 | 163 | 179 | 125 | 0 | | 112 | 298 | 289 | 49 | 236 | 38 | 9 | 32 | | |
| | 19 | 251 | 205 | 230 | 223 | 200 | 210 | 42 | 67 | 3 | | 86 | 158 | 280 | 157 | 199 | 170 | 125 | 178 | | |
| | 20 | 117 | 13 | 276 | 90 | 234 | 7 | 66 | 230 | 4 | | 236 | 235 | 110 | 64 | 0 | 249 | 191 | 2 | | |
| | 24 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | | 116 | 339 | 187 | 193 | 266 | 288 | 28 | 156 | | |
| | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 22 | | 222 | 234 | 281 | 124 | 0 | 194 | 6 | 58 | | |
| | 3 | 0 | 121 | 276 | 220 | 201 | 187 | 97 | 4 | 46 | | 22 | 46 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | | 1 | 89 | 87 | 208 | 18 | 145 | 94 | 6 | 23 | | | 1 | 23 | 72 | 172 | 1 | 205 | 279 | 4 | 27 |
| | | 3 | 84 | 0 | 30 | 165 | 166 | 49 | 33 | 162 | | | 6 | 136 | 17 | 295 | 166 | 0 | 255 | 74 | 141 |
| | | 4 | 20 | 275 | 197 | 5 | 108 | 279 | 113 | 220 | | | 7 | 116 | 383 | 96 | 65 | 0 | 111 | 16 | 11 |
| | | 6 | 150 | 199 | 61 | 45 | 82 | 139 | 49 | 43 | | | 14 | 182 | 312 | 46 | 81 | 183 | 54 | 28 | 181 |
| | | 7 | 131 | 153 | 175 | 142 | 132 | 166 | 21 | 186 | | | 47 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 8 | | 243 | 56 | 79 | 16 | 197 | 91 | 6 | 96 | 0 | 195 | | 71 | 270 | 107 | 0 | 325 | 21 | 163 | | |
| 10 | | 136 | 132 | 281 | 34 | 41 | 106 | 151 | 1 | 2 | 243 | | 81 | 110 | 176 | 0 | 326 | 142 | 131 | | |
| 11 | | 86 | 305 | 303 | 155 | 162 | 246 | 83 | 216 | 4 | 215 | | 76 | 318 | 212 | 0 | 226 | 192 | 169 | | |
| 12 | | 246 | 231 | 253 | 213 | 57 | 345 | 154 | 22 | 15 | 61 | | 136 | 67 | 127 | 277 | 99 | 197 | 98 | | |
| 13 | | 219 | 341 | 164 | 147 | 36 | 269 | 87 | 24 | 48 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 14 | | 211 | 212 | 53 | 69 | 115 | 185 | 5 | 167 | 1 | 25 | | 194 | 210 | 208 | 45 | 91 | 98 | 165 | | |
| 16 | | 240 | 304 | 44 | 96 | 242 | 249 | 92 | 200 | 6 | 104 | | 194 | 29 | 141 | 36 | 326 | 140 | 232 | | |
| 17 | | 76 | 300 | 28 | 74 | 165 | 215 | 173 | 32 | 8 | 194 | | 101 | 304 | 174 | 72 | 268 | 22 | 9 | | |
| 18 | | 244 | 271 | 77 | 99 | 0 | 143 | 120 | 235 | 49 | 0 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 20 | | 144 | 39 | 319 | 30 | 113 | 121 | 2 | 172 | 0 | 128 | | 222 | 11 | 146 | 275 | 102 | 4 | 32 | | |
| 21 | | 12 | 357 | 68 | 158 | 108 | 121 | 142 | 219 | 4 | 165 | | 19 | 293 | 153 | 0 | 1 | 1 | 43 | | |
| 22 | | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | 19 | 181 | | 244 | 50 | 217 | 155 | 40 | 40 | 200 | | |
| 25 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 21 | 63 | | 274 | 234 | 114 | 62 | 167 | 93 | 205 | | |
| 4 | | 0 | 157 | 332 | 233 | 170 | 246 | 42 | 24 | 50 | 29 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | | 1 | 102 | 181 | 205 | 10 | 235 | 256 | 204 | 1 | | | 86 | 252 | 27 | 150 | 0 | 273 | 92 | 232 | |
| | | 26 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | | 14 | 236 | 5 | 308 | 11 | 180 | 104 | 136 | 32 |
| | | 0 | 205 | 195 | 83 | 164 | 261 | 219 | 185 | 2 | | | 18 | 84 | 147 | 117 | 53 | 0 | 243 | 106 | 118 |
| | | 1 | 236 | 14 | 292 | 59 | 181 | 130 | 100 | 171 | | | 25 | 6 | 78 | 29 | 68 | 42 | 107 | 6 | 103 |
| 5 | | 3 | 194 | 115 | 50 | 86 | 72 | 251 | 24 | 47 | 51 | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | | 12 | 231 | 166 | 318 | 80 | 283 | 322 | 65 | 143 | 30 | | 0 | 216 | 159 | 91 | 34 | 0 | 171 | 2 | 170 |

| | | | | | | | | | | | | | | | | | | | |
|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | 16 | 28 | 241 | 201 | 182 | 254 | 295 | 207 | 210 | | 10 | 73 | 229 | 23 | 130 | 90 | 16 | 88 | 199 |
| | 21 | 123 | 51 | 267 | 130 | 79 | 258 | 161 | 180 | | 13 | 120 | 260 | 105 | 210 | 252 | 95 | 112 | 26 |
| | 22 | 115 | 157 | 279 | 153 | 144 | 283 | 72 | 180 | | 24 | 9 | 90 | 135 | 123 | 173 | 212 | 20 | 105 |
| | 27 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 52 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 6 | 0 | 183 | 278 | 289 | 158 | 80 | 294 | 6 | 199 | 31 | 1 | 95 | 100 | 222 | 175 | 144 | 101 | 4 | 73 |
| | 6 | 22 | 257 | 21 | 119 | 144 | 73 | 27 | 22 | | 7 | 177 | 215 | 308 | 49 | 144 | 297 | 49 | 149 |
| | 10 | 28 | 1 | 293 | 113 | 169 | 330 | 163 | 23 | | 22 | 172 | 258 | 66 | 177 | 166 | 279 | 125 | 175 |
| | 11 | 67 | 351 | 13 | 21 | 90 | 99 | 50 | 100 | | 25 | 61 | 256 | 162 | 128 | 19 | 222 | 194 | 108 |
| | 13 | 244 | 92 | 232 | 63 | 59 | 172 | 48 | 92 | | 53 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 17 | 11 | 253 | 302 | 51 | 177 | 150 | 24 | 207 | | 0 | 221 | 102 | 210 | 192 | 0 | 351 | 6 | 103 |
| | 18 | 157 | 18 | 138 | 136 | 151 | 284 | 38 | 52 | | 12 | 112 | 201 | 22 | 209 | 211 | 265 | 126 | 110 |
| | 20 | 211 | 225 | 235 | 116 | 108 | 305 | 91 | 13 | | 14 | 199 | 175 | 271 | 58 | 36 | 338 | 63 | 151 |
| 7 | 28 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 32 | 24 | 121 | 287 | 217 | 30 | 162 | 83 | 20 | 211 | |
| | 0 | 220 | 9 | 12 | 17 | 169 | 3 | 145 | | 77 | 54 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 1 | 44 | 62 | 88 | 76 | 189 | 103 | 88 | | 146 | 1 | 2 | 323 | 170 | 114 | 0 | 56 | 10 | 199 |
| | 4 | 159 | 316 | 207 | 104 | 154 | 224 | 112 | | 209 | 2 | 187 | 8 | 20 | 49 | 0 | 304 | 30 | 132 |
| | 7 | 31 | 333 | 50 | 100 | 184 | 297 | 153 | | 32 | 11 | 41 | 361 | 140 | 161 | 76 | 141 | 6 | 172 |
| | 8 | 167 | 290 | 25 | 150 | 104 | 215 | 159 | | 166 | 21 | 211 | 105 | 33 | 137 | 18 | 101 | 92 | 65 |
| | 14 | 104 | 114 | 76 | 158 | 164 | 39 | 76 | | 18 | 55 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 29 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | 0 | 0 | 127 | 230 | 187 | 82 | 197 | 60 | 4 | 161 |
| 8 | 0 | 112 | 307 | 295 | 33 | 54 | 348 | 172 | 181 | 33 | 7 | 167 | 148 | 296 | 186 | 0 | 320 | 153 | 237 |
| | 1 | 4 | 179 | 133 | 95 | 0 | 75 | 2 | 105 | | 15 | 164 | 202 | 5 | 68 | 108 | 112 | 197 | 142 |
| | 3 | 7 | 165 | 130 | 4 | 252 | 22 | 131 | 141 | | 17 | 159 | 312 | 44 | 150 | 0 | 54 | 155 | 180 |
| | 12 | 211 | 18 | 231 | 217 | 41 | 312 | 141 | 223 | | 56 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 16 | 102 | 39 | 296 | 204 | 98 | 224 | 96 | 177 | | 1 | 161 | 320 | 207 | 192 | 199 | 100 | 4 | 231 |
| | 19 | 164 | 224 | 110 | 39 | 46 | 17 | 99 | 145 | | 6 | 197 | 335 | 158 | 173 | 278 | 210 | 45 | 174 |
| | 21 | 109 | 368 | 269 | 58 | 15 | 59 | 101 | 199 | | 12 | 207 | 2 | 55 | 26 | 0 | 195 | 168 | 145 |
| | 22 | 241 | 67 | 245 | 44 | 230 | 314 | 35 | 153 | | 22 | 103 | 266 | 285 | 187 | 205 | 268 | 185 | 100 |
| 9 | 24 | 90 | 170 | 154 | 201 | 54 | 244 | 116 | 38 | 57 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 37 | 210 | 259 | 222 | 216 | 135 | 6 | 11 | |
| | 0 | 103 | 366 | 189 | 9 | 162 | 156 | 6 | 169 | 14 | 105 | 313 | 179 | 157 | 16 | 15 | 200 | 207 | |
| | 1 | 182 | 232 | 244 | 37 | 159 | 88 | 10 | 12 | 15 | 51 | 297 | 178 | 0 | 0 | 35 | 177 | 42 | |
| | 10 | 109 | 321 | 36 | 213 | 93 | 293 | 145 | 206 | 18 | 120 | 21 | 160 | 6 | 0 | 188 | 43 | 100 | |
| | 11 | 21 | 133 | 286 | 105 | 134 | 111 | 53 | 221 | 58 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 13 | 142 | 57 | 151 | 89 | 45 | 92 | 201 | 17 | 1 | 198 | 269 | 298 | 81 | 72 | 319 | 82 | 59 | |
| | 17 | 14 | 303 | 267 | 185 | 132 | 152 | 4 | 212 | 13 | 220 | 82 | 15 | 195 | 144 | 236 | 2 | 204 | |
| 10 | 18 | 61 | 63 | 135 | 109 | 76 | 23 | 164 | 92 | 23 | 122 | 115 | 115 | 138 | 0 | 85 | 135 | 161 | |
| | 20 | 216 | 82 | 209 | 218 | 209 | 337 | 173 | 205 | 59 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 167 | 185 | 151 | 123 | 190 | 164 | 91 | 121 | |
| | 1 | 98 | 101 | 14 | 82 | 178 | 175 | 126 | 116 | 9 | 151 | 177 | 179 | 90 | 0 | 196 | 64 | 90 | |
| | 2 | 149 | 339 | 80 | 165 | 1 | 253 | 77 | 151 | 10 | 157 | 289 | 64 | 73 | 0 | 209 | 198 | 26 | |
| | 4 | 167 | 274 | 211 | 174 | 28 | 27 | 156 | 70 | 12 | 163 | 214 | 181 | 10 | 0 | 246 | 100 | 140 | |
| | 7 | 160 | 111 | 75 | 19 | 267 | 231 | 16 | 230 | 60 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 8 | 49 | 383 | 161 | 194 | 234 | 49 | 12 | 115 | 1 | 173 | 258 | 102 | 12 | 153 | 236 | 4 | 115 | |
| 11 | 14 | 58 | 354 | 311 | 103 | 201 | 267 | 70 | 84 | 3 | 139 | 93 | 77 | 77 | 0 | 264 | 28 | 188 | |
| | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 149 | 346 | 192 | 49 | 165 | 37 | 109 | 168 | |
| | 0 | 77 | 48 | 16 | 52 | 55 | 25 | 184 | 45 | 19 | 0 | 297 | 208 | 114 | 117 | 272 | 188 | 52 | |
| | 1 | 41 | 102 | 147 | 11 | 23 | 322 | 194 | 115 | 61 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 12 | 83 | 8 | 290 | 2 | 274 | 200 | 123 | 134 | 0 | 157 | 175 | 32 | 67 | 216 | 304 | 10 | 4 | |
| | 16 | 182 | 47 | 289 | 35 | 181 | 351 | 16 | 1 | 8 | 137 | 37 | 80 | 45 | 144 | 237 | 84 | 103 | |
| | 21 | 78 | 188 | 177 | 32 | 273 | 166 | 104 | 152 | 17 | 149 | 312 | 197 | 96 | 2 | 135 | 12 | 30 | |
| | 22 | 252 | 334 | 43 | 84 | 39 | 338 | 109 | 165 | 62 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 12 | 23 | 22 | 115 | 280 | 201 | 26 | 192 | 124 | 107 | 1 | 167 | 52 | 154 | 23 | 0 | 123 | 2 | 53 | |
| | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 3 | 173 | 314 | 47 | 215 | 0 | 77 | 75 | 189 | |
| | 0 | 160 | 77 | 229 | 142 | 225 | 123 | 6 | 186 | 9 | 139 | 139 | 124 | 60 | 0 | 25 | 142 | 215 | |
| | 1 | 42 | 186 | 235 | 175 | 162 | 217 | 20 | 215 | 18 | 151 | 288 | 207 | 167 | 183 | 272 | 128 | 24 | |
| | 10 | 21 | 174 | 169 | 136 | 244 | 142 | 203 | 124 | 63 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 11 | 32 | 232 | 48 | 3 | 151 | 110 | 153 | 180 | 0 | 149 | 113 | 226 | 114 | 27 | 288 | 163 | 222 | |
| | 13 | 234 | 50 | 105 | 28 | 238 | 176 | 104 | 98 | 4 | 157 | 14 | 65 | 91 | 0 | 83 | 10 | 170 | |
| | 18 | 7 | 74 | 52 | 182 | 243 | 76 | 207 | 80 | 24 | 137 | 218 | 126 | 78 | 35 | 17 | 162 | 71 | |
| 13 | 34 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 64 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 0 | 177 | 313 | 39 | 81 | 231 | 311 | 52 | 220 | 1 | 151 | 113 | 228 | 206 | 52 | 210 | 1 | 22 | |
| | 3 | 248 | 177 | 302 | 56 | 0 | 251 | 147 | 185 | 16 | 163 | 132 | 69 | 22 | 243 | 3 | 163 | 127 | |
| | 7 | 151 | 266 | 303 | 72 | 216 | 265 | 1 | 154 | 18 | 173 | 114 | 176 | 134 | 0 | 53 | 99 | 49 | |
| | 20 | 185 | 115 | 160 | 217 | 47 | 94 | 16 | 178 | 25 | 139 | 168 | 102 | 161 | 270 | 167 | 98 | 125 | |
| | 23 | 62 | 370 | 37 | 78 | 36 | 81 | 46 | 150 | 65 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 139 | 80 | 234 | 84 | 18 | 79 | 4 | 191 | |
| | 0 | 206 | 142 | 78 | 14 | 0 | 22 | 1 | 124 | 7 | 157 | 78 | 227 | 4 | 0 | 244 | 6 | 211 | |
| 14 | 12 | 55 | 248 | 299 | 175 | 186 | 322 | 202 | 144 | 9 | 163 | 163 | 259 | 9 | 0 | 293 | 142 | 187 | |
| | 15 | 206 | 137 | 54 | 211 | 253 | 277 | 118 | 182 | 22 | 173 | 274 | 260 | 12 | 57 | 272 | 3 | 148 | |
| | 16 | 127 | 89 | 61 | 191 | 16 | 156 | 130 | 95 | 66 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 17 | 16 | 347 | 179 | 51 | 0 | 66 | 1 | 72 | 1 | 149 | 135 | 101 | 184 | 168 | 82 | 181 | 177 | |
| | 21 | 229 | 12 | 258 | 43 | 79 | 78 | 2 | 76 | 6 | 151 | 149 | 228 | 121 | 0 | 67 | 45 | 114 | |
| | 36 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 10 | 167 | 15 | 126 | 29 | 144 | 235 | 153 | 93 | |
| | 15 | 0 | 40 | 241 | 229 | 90 | 170 | 176 | 173 | 39 | 45 | 67 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | | 0 | 40 | 241 | 229 | 90 | 170 | 176 | 173 | 39 | | 67 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

Table 5.3.2-3: LDPC base graph 2 (H_{BG}) and its parity check matrices ($V_{i,j}$)

| H_{BG} | | $V_{i,j}$ | | | | | | | | H_{BG} | | $V_{i,j}$ | | | | | | | |
|------------------|---------------------|--------------------|-----|-----|-----|-----|-----|-----|-----|------------------|---------------------|--------------------|-----|-----|-----|-----|-----|-----|-----|
| Row index i | Column index j | Set index i_{LS} | | | | | | | | Row index i | Column index j | Set index i_{LS} | | | | | | | |
| | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | | | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 0 | 0 | 9 | 174 | 0 | 72 | 3 | 156 | 143 | 145 | 16 | 26 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 1 | 117 | 97 | 0 | 110 | 26 | 143 | 19 | 131 | 17 | 1 | 254 | 158 | 0 | 48 | 120 | 134 | 57 | 196 |
| | 2 | 204 | 166 | 0 | 23 | 53 | 14 | 176 | 71 | 5 | 124 | 23 | 24 | 132 | 43 | 23 | 201 | 173 | |
| | 3 | 26 | 66 | 0 | 181 | 35 | 3 | 165 | 21 | 11 | 114 | 9 | 109 | 206 | 65 | 62 | 142 | 195 | |
| | 6 | 189 | 71 | 0 | 95 | 115 | 40 | 196 | 23 | 12 | 64 | 6 | 18 | 2 | 42 | 163 | 35 | 218 | |
| | 9 | 205 | 172 | 0 | 8 | 127 | 123 | 13 | 112 | 27 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 10 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 0 | 167 | 27 | 137 | 53 | 19 | 17 | 18 | 142 | 18 | 220 | 186 | 0 | 68 | 17 | 173 | 129 | 128 | |
| | 3 | 166 | 36 | 124 | 156 | 94 | 65 | 27 | 174 | 6 | 194 | 6 | 18 | 16 | 106 | 31 | 203 | 211 | |
| | 4 | 253 | 48 | 0 | 115 | 104 | 63 | 3 | 183 | 7 | 50 | 46 | 86 | 156 | 142 | 22 | 140 | 210 | |
| 5 | 125 | 92 | 0 | 156 | 66 | 1 | 102 | 27 | 28 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 6 | 226 | 31 | 88 | 115 | 84 | 55 | 185 | 96 | 0 | 87 | 58 | 0 | 35 | 79 | 13 | 110 | 39 | | |
| 7 | 156 | 187 | 0 | 200 | 98 | 37 | 17 | 23 | 1 | 20 | 42 | 158 | 138 | 28 | 135 | 124 | 84 | | |
| 8 | 224 | 185 | 0 | 29 | 69 | 171 | 14 | 9 | 10 | 185 | 156 | 154 | 86 | 41 | 145 | 52 | 88 | | |
| 9 | 252 | 3 | 55 | 31 | 50 | 133 | 180 | 167 | 29 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 11 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 26 | 76 | 0 | 6 | 2 | 128 | 196 | 117 | | |
| 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 4 | 105 | 61 | 148 | 20 | 103 | 52 | 35 | 227 | | |
| 0 | 81 | 25 | 20 | 152 | 95 | 98 | 126 | 74 | 11 | 29 | 153 | 104 | 141 | 78 | 173 | 114 | 6 | | |
| 1 | 114 | 114 | 94 | 131 | 106 | 168 | 163 | 31 | 30 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 3 | 44 | 117 | 99 | 46 | 92 | 107 | 47 | 3 | 0 | 76 | 157 | 0 | 80 | 91 | 156 | 10 | 238 | | |
| 4 | 52 | 110 | 9 | 191 | 110 | 82 | 183 | 53 | 8 | 42 | 175 | 17 | 43 | 75 | 166 | 122 | 13 | | |
| 8 | 240 | 114 | 108 | 91 | 111 | 142 | 132 | 155 | 13 | 210 | 67 | 33 | 81 | 81 | 40 | 23 | 11 | | |
| 10 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 31 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 12 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 8 | 222 | 20 | 0 | 49 | 54 | 18 | 202 | 195 | | |
| 1 | 8 | 136 | 38 | 185 | 120 | 53 | 36 | 239 | 2 | 63 | 52 | 4 | 1 | 132 | 163 | 126 | 44 | | |
| 2 | 58 | 175 | 15 | 6 | 121 | 174 | 48 | 171 | 32 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 4 | 158 | 113 | 102 | 36 | 22 | 174 | 18 | 95 | 0 | 23 | 106 | 0 | 156 | 68 | 110 | 52 | 5 | | |
| 5 | 104 | 72 | 146 | 124 | 4 | 127 | 111 | 110 | 3 | 3 | 235 | 86 | 75 | 54 | 115 | 132 | 170 | 94 | |
| 6 | 209 | 123 | 12 | 124 | 73 | 17 | 203 | 159 | 5 | 238 | 95 | 158 | 134 | 56 | 150 | 13 | 111 | | |
| 7 | 54 | 118 | 57 | 110 | 49 | 89 | 3 | 199 | 33 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 8 | 18 | 28 | 53 | 156 | 128 | 17 | 191 | 43 | 1 | 46 | 182 | 0 | 153 | 30 | 113 | 113 | 81 | | |
| 9 | 128 | 186 | 46 | 133 | 79 | 105 | 160 | 75 | 2 | 139 | 153 | 69 | 88 | 42 | 108 | 161 | 19 | | |
| 10 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 9 | 8 | 64 | 87 | 63 | 101 | 61 | 88 | 130 | | |
| 13 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 34 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 0 | 179 | 72 | 0 | 200 | 42 | 86 | 43 | 29 | 0 | 228 | 45 | 0 | 211 | 128 | 72 | 197 | 66 | | |
| 1 | 214 | 74 | 136 | 16 | 24 | 67 | 27 | 140 | 5 | 156 | 21 | 65 | 94 | 63 | 136 | 194 | 95 | | |
| 11 | 71 | 29 | 157 | 101 | 51 | 83 | 117 | 180 | 35 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | | |
| 14 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 29 | 67 | 0 | 90 | 142 | 36 | 164 | 146 | | |
| 0 | 231 | 10 | 0 | 185 | 40 | 79 | 136 | 121 | 7 | 143 | 137 | 100 | 6 | 28 | 38 | 172 | 66 | | |
| 1 | 41 | 44 | 131 | 138 | 140 | 84 | 49 | 41 | 12 | 160 | 55 | 13 | 221 | 100 | 53 | 49 | 190 | | |
| 5 | 194 | 121 | 142 | 170 | 84 | 35 | 36 | 169 | 13 | 122 | 85 | 7 | 6 | 133 | 145 | 161 | 86 | | |
| 7 | 159 | 80 | 141 | 219 | 137 | 103 | 132 | 88 | 36 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 11 | 103 | 48 | 64 | 193 | 71 | 60 | 62 | 207 | 0 | 8 | 103 | 0 | 27 | 13 | 42 | 168 | 64 | | |
| 15 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 6 | 151 | 50 | 32 | 118 | 10 | 104 | 193 | 181 | | |
| 0 | 155 | 129 | 0 | 123 | 109 | 47 | 7 | 137 | 37 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 5 | 228 | 92 | 124 | 55 | 87 | 154 | 34 | 72 | 1 | 98 | 70 | 0 | 216 | 106 | 64 | 14 | 7 | | |
| 7 | 45 | 100 | 99 | 31 | 107 | 10 | 198 | 172 | 2 | 101 | 111 | 126 | 212 | 77 | 24 | 186 | 144 | | |
| 9 | 28 | 49 | 45 | 222 | 133 | 155 | 168 | 124 | 5 | 135 | 168 | 110 | 193 | 43 | 149 | 46 | 16 | | |
| 11 | 158 | 184 | 148 | 209 | 139 | 29 | 12 | 56 | 38 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 16 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 18 | 110 | 0 | 108 | 133 | 139 | 50 | 25 | | |
| 1 | 129 | 80 | 0 | 103 | 97 | 48 | 163 | 86 | 4 | 28 | 17 | 154 | 61 | 25 | 161 | 27 | 57 | | |
| 5 | 147 | 186 | 45 | 13 | 135 | 125 | 78 | 186 | 39 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 7 | 140 | 16 | 148 | 105 | 35 | 24 | 143 | 87 | 2 | 71 | 120 | 0 | 106 | 87 | 84 | 70 | 37 | | |
| 11 | 3 | 102 | 96 | 150 | 108 | 47 | 107 | 172 | 5 | 240 | 154 | 35 | 44 | 56 | 173 | 17 | 139 | | |
| 13 | 116 | 143 | 78 | 181 | 65 | 55 | 58 | 154 | 7 | 9 | 52 | 51 | 185 | 104 | 93 | 50 | 221 | | |
| 17 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 9 | 84 | 56 | 134 | 176 | 70 | 29 | 6 | 17 | | |
| 0 | 142 | 118 | 0 | 147 | 70 | 53 | 101 | 176 | 40 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 1 | 94 | 70 | 65 | 43 | 69 | 31 | 177 | 169 | 1 | 106 | 3 | 0 | 147 | 80 | 117 | 115 | 201 | | |
| 12 | 230 | 152 | 87 | 152 | 88 | 161 | 22 | 225 | 13 | 1 | 170 | 20 | 182 | 139 | 148 | 189 | 46 | | |
| 18 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 41 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 1 | 203 | 28 | 0 | 2 | 97 | 104 | 186 | 167 | 0 | 242 | 84 | 0 | 108 | 32 | 116 | 110 | 179 | | |
| 8 | 205 | 132 | 97 | 30 | 40 | 142 | 27 | 238 | 5 | 44 | 8 | 20 | 21 | 89 | 73 | 0 | 14 | | |
| 10 | 61 | 185 | 51 | 184 | 24 | 99 | 205 | 48 | 12 | 166 | 17 | 122 | 110 | 71 | 142 | 163 | 116 | | |
| 11 | 247 | 178 | 85 | 83 | 49 | 64 | 81 | 68 | 42 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 19 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 132 | 165 | 0 | 71 | 135 | 105 | 163 | 46 | | |
| 0 | 11 | 59 | 0 | 174 | 46 | 111 | 125 | 38 | 7 | 164 | 179 | 88 | 12 | 6 | 137 | 173 | 2 | | |
| 1 | 185 | 104 | 17 | 150 | 41 | 25 | 60 | 217 | 10 | 235 | 124 | 13 | 109 | 2 | 29 | 179 | 106 | | |
| 6 | 0 | 22 | 156 | 8 | 101 | 174 | 177 | 208 | 43 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 7 | 117 | 52 | 20 | 56 | 96 | 23 | 51 | 232 | 0 | 147 | 173 | 0 | 29 | 37 | 11 | 197 | 184 | | |
| 20 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 12 | 85 | 177 | 19 | 201 | 25 | 41 | 191 | 135 | | |
| 0 | 11 | 32 | 0 | 99 | 28 | 91 | 39 | 178 | 13 | 36 | 12 | 78 | 69 | 114 | 162 | 193 | 141 | | |
| 7 | 236 | 92 | 7 | 138 | 30 | 175 | 29 | 214 | 44 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 9 | 210 | 174 | 4 | 110 | 116 | 24 | 35 | 168 | 1 | 57 | 77 | 0 | 91 | 60 | 126 | 157 | 85 | | |
| 13 | 56 | 154 | 2 | 99 | 64 | 141 | 8 | 51 | 5 | 40 | 184 | 157 | 165 | 137 | 152 | 167 | 225 | | |
| 21 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 11 | 63 | 18 | 6 | 55 | 93 | 172 | 181 | 175 | | |
| 1 | 63 | 39 | 0 | 46 | 33 | 122 | 18 | 124 | 45 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 3 | 111 | 93 | 113 | 217 | 122 | 11 | 155 | 122 | 0 | 140 | 25 | 0 | 1 | 121 | 73 | 197 | 178 | | |
| 11 | 14 | 11 | 48 | 109 | 131 | 4 | 49 | 72 | 2 | 38 | 151 | 63 | 175 | 129 | 154 | 167 | 112 | | |
| 22 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 7 | 154 | 170 | 82 | 83 | 26 | 129 | 179 | 106 | | |
| 0 | 83 | 49 | 0 | 37 | 76 | 29 | 32 | 48 | 46 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 1 | 2 | 125 | 112 | 113 | 37 | 91 | 53 | 57 | 10 | 219 | 37 | 0 | 40 | 97 | 167 | 181 | 154 | | |
| 0 | 83 | 49 | 0 | 37 | 76 | 29 | 32 | 48 | 13 | 151 | 31 | 144 | 12 | 56 | 38 | 193 | 114 | | |
| 1 | 2 | 125 | 112 | 113 | 37 | 91 | 53 | 57 | 47 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| 1 | 2 | 125 | 112 | 113 | 37 | 91 | 53 | 57 | 38 | 1 | 31 | 84 | 0 | 37 | 1 | 112 | 157 | 42 | |

| | | | | | | | | | | | | | | | | | | | |
|----|----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 8 | 8 | 38 | 35 | 102 | 143 | 62 | 27 | 95 | 167 | 5 | 5 | 66 | 151 | 93 | 97 | 70 | 7 | 173 | 41 |
| | 13 | 222 | 166 | 26 | 140 | 47 | 127 | 186 | 219 | | 11 | 38 | 190 | 19 | 46 | 1 | 19 | 191 | 105 |
| 14 | 23 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 48 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | 1 | 115 | 19 | 0 | 36 | 143 | 11 | 91 | 82 | 0 | 239 | 93 | 0 | 106 | 119 | 109 | 181 | 167 | |
| | 6 | 145 | 118 | 138 | 95 | 51 | 145 | 20 | 232 | 7 | 172 | 132 | 24 | 181 | 32 | 6 | 157 | 45 | |
| | 11 | 3 | 21 | 57 | 40 | 130 | 8 | 52 | 204 | 12 | 34 | 57 | 138 | 154 | 142 | 105 | 173 | 189 | |
| | 13 | 232 | 163 | 27 | 116 | 97 | 166 | 109 | 162 | 49 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 24 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 2 | 0 | 103 | 0 | 98 | 6 | 160 | 193 | 78 | |
| 15 | 0 | 51 | 68 | 0 | 116 | 139 | 137 | 174 | 38 | 10 | 75 | 107 | 36 | 35 | 73 | 156 | 163 | 67 | |
| | 10 | 175 | 63 | 73 | 200 | 96 | 103 | 108 | 217 | 13 | 120 | 163 | 143 | 36 | 102 | 82 | 179 | 180 | |
| | 11 | 213 | 81 | 99 | 110 | 128 | 40 | 102 | 157 | 50 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 25 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 129 | 147 | 0 | 120 | 48 | 132 | 191 | 53 | |
| 16 | 1 | 203 | 87 | 0 | 75 | 48 | 78 | 125 | 170 | 5 | 229 | 7 | 2 | 101 | 47 | 6 | 197 | 215 | |
| | 9 | 142 | 177 | 79 | 158 | 9 | 158 | 31 | 23 | 11 | 118 | 60 | 55 | 81 | 19 | 8 | 167 | 230 | |
| | 11 | 8 | 135 | 111 | 134 | 28 | 17 | 54 | 175 | 51 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | |
| | 12 | 242 | 64 | 143 | 97 | 8 | 165 | 176 | 202 | | | | | | | | | | |

5.3.3 Channel coding of small block lengths

The bit sequence input for a given code block to channel coding is denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits to encode. After encoding the bits are denoted by $d_0, d_1, d_2, \dots, d_{N-1}$.

5.3.3.1 Encoding of 1-bit information

For $K = 1$, the code block is encoded according to Table 5.3.3.1-1, where $N = Q_m$ and Q_m is the modulation order for the code block.

Table 5.3.3.1-1: Encoding of 1-bit information

| Q_m | Encoded bits $d_0, d_1, d_2, \dots, d_{N-1}$ |
|-------|--|
| 1 | $[c_0]$ |
| 2 | $[c_0 y]$ |
| 4 | $[c_0 y x x]$ |
| 6 | $[c_0 y x x x x]$ |
| 8 | $[c_0 y x x x x x x]$ |

The "x" and "y" in Table 5.3.3.1-1 are placeholders for Clause 6.3.1.1 of [4, TS 38.211] to scramble the information bits in a way that maximizes the Euclidean distance of the modulation symbols carrying the information bits.

5.3.3.2 Encoding of 2-bit information

For $K = 2$, the code block is encoded according to Table 5.3.3.2-1, where $c_2 = (c_0 + c_1) \bmod 2$, $N = 3Q_m$, and Q_m is the modulation order for the code block.

Table 5.3.3.2-1: Encoding of 2-bit information

| Q_m | Encoded bits $d_0, d_1, d_2, \dots, d_{N-1}$ |
|-------|---|
| 1 | $[c_0 c_1 c_2]$ |
| 2 | $[c_0 c_1 c_2 c_0 c_1 c_2]$ |
| 4 | $[c_0 c_1 x x c_2 c_0 x x c_1 c_2 x x]$ |
| 6 | $[c_0 c_1 x x x x c_2 c_0 x x x x c_1 c_2 x x x x]$ |
| 8 | $[c_0 c_1 x x x x x x c_2 c_0 x x x x x x c_1 c_2 x x x x x x]$ |

The "x" in Table 5.3.3.2-1 are placeholders for Clause 6.3.1.1 of [4, TS 38.211] to scramble the information bits in a way that maximizes the Euclidean distance of the modulation symbols carrying the information bits.

5.3.3.3 Encoding of other small block lengths

For $3 \leq K \leq 11$, the code block is encoded by $d_i = \left(\sum_{k=0}^{K-1} c_k \cdot M_{i,k} \right) \bmod 2$, where $i = 0, 1, \dots, N-1$, $N = 32$, and $M_{i,k}$ represents the basis sequences as defined in Table 5.3.3.3-1.

Table 5.3.3.3-1: Basis sequences for (32, K) code

| i | $M_{i,0}$ | $M_{i,1}$ | $M_{i,2}$ | $M_{i,3}$ | $M_{i,4}$ | $M_{i,5}$ | $M_{i,6}$ | $M_{i,7}$ | $M_{i,8}$ | $M_{i,9}$ | $M_{i,10}$ |
|-----|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|
| 0 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 |
| 2 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | 1 | 1 |
| 3 | 1 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 1 |
| 4 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 1 |
| 5 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 1 |
| 6 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 1 | 1 |
| 7 | 1 | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 1 |
| 8 | 1 | 1 | 0 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 1 |
| 9 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 1 | 1 |
| 10 | 1 | 0 | 1 | 0 | 0 | 1 | 1 | 1 | 0 | 1 | 1 |
| 11 | 1 | 1 | 1 | 0 | 0 | 1 | 1 | 0 | 1 | 0 | 1 |
| 12 | 1 | 0 | 0 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 1 |
| 13 | 1 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 0 | 1 | 1 |
| 14 | 1 | 0 | 0 | 0 | 1 | 1 | 0 | 1 | 0 | 0 | 1 |
| 15 | 1 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | 1 |
| 16 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 0 |
| 17 | 1 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 |
| 18 | 1 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 |
| 19 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 |
| 20 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 |
| 21 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 |
| 22 | 1 | 0 | 0 | 0 | 1 | 0 | 0 | 1 | 1 | 0 | 1 |
| 23 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 1 | 1 |
| 24 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 1 | 0 |
| 25 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 1 |
| 26 | 1 | 0 | 1 | 1 | 0 | 1 | 0 | 0 | 1 | 1 | 0 |
| 27 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 |
| 28 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 0 | 0 |
| 29 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 |
| 30 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 31 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

5.4 Rate matching

5.4.1 Rate matching for Polar code

The rate matching for Polar code is defined per coded block and consists of sub-block interleaving, bit collection, and bit interleaving. The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$. The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

5.4.1.1 Sub-block interleaving

The bits input to the sub-block interleaver are the coded bits $d_0, d_1, d_2, \dots, d_{N-1}$. The coded bits $d_0, d_1, d_2, \dots, d_{N-1}$ are divided into 32 sub-blocks. The bits output from the sub-block interleaver are denoted as $y_0, y_1, y_2, \dots, y_{N-1}$, generated as follows:

for $n=0$ to $N-1$

$$i = \lfloor 32n / N \rfloor;$$

$$J(n) = P(i) \times (N/32) + \text{mod}(n, N/32);$$

$$y_n = d_{J(n)};$$

end for

where the sub-block interleaver pattern $P(i)$ is given by Table 5.4.1.1-1.

Table 5.4.1.1-1: Sub-block interleaver pattern $P(i)$

| i | $P(i)$ | i | $P(i)$ | i | $P(i)$ | i | $P(i)$ | i | $P(i)$ | i | $P(i)$ | i | $P(i)$ | i | $P(i)$ |
|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|
| 0 | 0 | 4 | 3 | 8 | 8 | 12 | 10 | 16 | 12 | 20 | 14 | 24 | 24 | 28 | 27 |
| 1 | 1 | 5 | 5 | 9 | 16 | 13 | 18 | 17 | 20 | 21 | 22 | 25 | 25 | 29 | 29 |
| 2 | 2 | 6 | 6 | 10 | 9 | 14 | 11 | 18 | 13 | 22 | 15 | 26 | 26 | 30 | 30 |
| 3 | 4 | 7 | 7 | 11 | 17 | 15 | 19 | 19 | 21 | 23 | 23 | 27 | 28 | 31 | 31 |

The sets of bit indices $\overline{\mathbf{Q}}_I^N$ and $\overline{\mathbf{Q}}_F^N$ are determined as follows, where K , n_{PC} , and \mathbf{Q}_0^{N-1} are defined in Clause 5.3.1

$$\overline{\mathbf{Q}}_{F,imp}^N = \emptyset$$

if $E < N$

if $K/E \leq 7/16$ -- puncturing

for $n=0$ to $N-E-1$

$$\overline{\mathbf{Q}}_{F,imp}^N = \overline{\mathbf{Q}}_{F,imp}^N \cup \{J(n)\};$$

end for

if $E \geq 3N/4$

$$\overline{\mathbf{Q}}_{F,imp}^N = \overline{\mathbf{Q}}_{F,imp}^N \cup \{0,1,\dots,\lceil 3N/4 - E/2 \rceil - 1\};$$

else

$$\overline{\mathbf{Q}}_{F,imp}^N = \overline{\mathbf{Q}}_{F,imp}^N \cup \{0,1,\dots,\lceil 9N/16 - E/4 \rceil - 1\};$$

end if

else -- shortening

for $n=E$ to $N-1$

$$\overline{\mathbf{Q}}_{F,imp}^N = \overline{\mathbf{Q}}_{F,imp}^N \cup \{J(n)\};$$

end for

end if

end if

$$\overline{\mathbf{Q}}_{I,imp}^N = \mathbf{Q}_0^{N-1} \setminus \overline{\mathbf{Q}}_{F,imp}^N;$$

$\overline{\mathbf{Q}}_I^N$ comprises $(K + n_{PC})$ most reliable bit indices in $\overline{\mathbf{Q}}_{I,imp}^N$;

$$\overline{\mathbf{Q}}_F^N = \mathbf{Q}_0^{N-1} \setminus \overline{\mathbf{Q}}_I^N;$$

5.4.1.2 Bit selection

The bit sequence after the sub-block interleaver $y_0, y_1, y_2, \dots, y_{N-1}$ from Clause 5.4.1.1 is written into a circular buffer of length N .

Denoting by E the rate matching output sequence length, the bit selection output bit sequence $e_k, k=0,1,2,\dots,E-1$, is generated as follows:

```

if  $E \geq N$  -- repetition
  for  $k=0$  to  $E-1$ 
     $e_k = y_{\text{mod}(k,N)}$ ;
  end for
else
  if  $K/E \leq 7/16$  -- puncturing
    for  $k=0$  to  $E-1$ 
       $e_k = y_{k+N-E}$ ;
    end for
  else -- shortening
    for  $k=0$  to  $E-1$ 
       $e_k = y_k$ ;
    end for
  end if
end if

```

5.4.1.3 Interleaving of coded bits

The bit sequence $e_0, e_1, e_2, \dots, e_{E-1}$ is interleaved into bit sequence $f_0, f_1, f_2, \dots, f_{E-1}$, as follows:

If $I_{BL} = 1$

Denote T as the smallest integer such that $T(T+1)/2 \geq E$;

$k=0$;

for $i=0$ to $T-1$

for $j=0$ to $T-1-i$

if $k < E$

$v_{i,j} = e_k$;

else

$v_{i,j} = \langle \text{NULL} \rangle$;

end if

```

        k = k + 1;
    end for
end for
k = 0;
for j = 0 to T - 1
    for i = 0 to T - 1 - j
        if vi,j ≠ < NULL >
            fk = vi,j;
            k = k + 1
        end if
    end for
end for
else
    for i = 0 to E - 1
        fi = ei;
    end for
end if

```

The value of E is no larger than 8192.

5.4.2 Rate matching for LDPC code

The rate matching for LDPC code is defined per coded block and consists of bit selection and bit interleaving. The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$. The output bit sequence after rate matching is denoted as

$f_0, f_1, f_2, \dots, f_{E-1}$.

5.4.2.1 Bit selection

The bit sequence after encoding $d_0, d_1, d_2, \dots, d_{N-1}$ from Clause 5.3.2 is written into a circular buffer of length N_{cb} for the r -th coded block, where N is defined in Clause 5.3.2.

For the r -th code block, let $N_{cb} = N$ if $I_{LBRM} = 0$ and $N_{cb} = \min(N, N_{ref})$ otherwise, where $N_{ref} = \left\lfloor \frac{TBS_{LBRM}}{C \cdot R_{LBRM}} \right\rfloor$,

$R_{LBRM} = 2/3$, TBS_{LBRM} is determined according to Clause 6.1.4.2 in [6, TS 38.214] for UL-SCH and Clause 5.1.3.2 in [6, TS 38.214] for DL-SCH/PCH, assuming the following:

- maximum number of layers for one TB for UL-SCH is given by X , where
 - if the higher layer parameter *maxMIMO-Layers* of *PUSCH-ServingCellConfig* of the serving cell is configured, X is given by that parameter
 - elseif the higher layer parameter *maxRank* of *pusch-Config* of the serving cell is configured, X is given by the maximum value of *maxRank* across all BWPs of the serving cell
 - otherwise, X is given by the maximum number of layers for PUSCH supported by the UE for the serving cell

- maximum number of layers for one TB for DL-SCH/PCH is given by the minimum of X and 4, where
 - if the higher layer parameter *maxMIMO-Layers* of *PDSCH-ServingCellConfig* of the serving cell is configured, X is given by that parameter
 - otherwise, X is given by the maximum number of layers for PDSCH supported by the UE for the serving cell
- if the higher layer parameter *mcs-Table* or *mcs-TableDCI-1-2* given by a *pdsch-Config* for at least one DL BWP of the serving cell is set to 'qam256', maximum modulation order $Q_m = 8$ is assumed for DL-SCH; otherwise a maximum modulation order $Q_m = 6$ is assumed for DL-SCH;
- if the higher layer parameter *mcs-Table* or *mcs-TableTransformPrecoder* or *mcs-TableDCI-0-2* or *mcs-TableTransformPrecoderDCI-0-2* given by a *pusch-Config* or the higher layer parameter *mcs-Table* or *mcs-TableTransformPrecoder* given by *configuredGrantConfig* for at least one UL BWP of the serving cell is set to 'qam256', maximum modulation order $Q_m = 8$ is assumed for UL-SCH; otherwise a maximum modulation order $Q_m = 6$ is assumed for UL-SCH
- maximum coding rate of 948/1024;
- $n_{PRB} = n_{PRB,LBRM}$ is given by Table 5.4.2.1-1, where the value of $n_{PRB,LBRM}$ for DL-SCH is determined according to the initial downlink bandwidth part if there is no other downlink bandwidth part configured to the UE;
- $N_{RE} = 156 \cdot n_{PRB}$;
- C is the number of code blocks of the transport block determined according to Clause 5.2.2.

Table 5.4.2.1-1: Value of $n_{PRB,LBRM}$

| Maximum number of PRBs across all configured DL BWPs and UL BWPs of a carrier for DL-SCH and UL-SCH, respectively | $n_{PRB,LBRM}$ |
|---|----------------|
| Less than 33 | 32 |
| 33 to 66 | 66 |
| 67 to 107 | 107 |
| 108 to 135 | 135 |
| 136 to 162 | 162 |
| 163 to 217 | 217 |
| Larger than 217 | 273 |

Denoting by E_r the rate matching output sequence length for the r -th coded block, where the value of E_r is determined as follows:

Set $j = 0$

for $r = 0$ to $C - 1$

if the r -th coded block is not scheduled for transmission as indicated by CBGTI according to Clause 5.1.7.2 for DL-SCH and 6.1.5.2 for UL-SCH in [6, TS 38.214]

$E_r = 0$;

else

if $j \leq C' - \text{mod}(G / (N_L \cdot Q_m), C') - 1$

$$E_r = N_L \cdot Q_m \cdot \left\lfloor \frac{G}{N_L \cdot Q_m \cdot C'} \right\rfloor;$$

else

$$E_r = N_L \cdot Q_m \cdot \left\lceil \frac{G}{N_L \cdot Q_m \cdot C'} \right\rceil;$$

end if

$j = j + 1;$

end if

end for

where

- N_L is the number of transmission layers that the transport block is mapped onto;
- Q_m is the modulation order;
- G is the total number of coded bits available for transmission of the transport block;
- $C' = C$ if CBGTI is not present in the DCI scheduling the transport block and C' is the number of scheduled code blocks of the transport block if CBGTI is present in the DCI scheduling the transport block.

Denote by rv_{id} the redundancy version number for this transmission ($rv_{id} = 0, 1, 2$ or 3), the rate matching output bit sequence e_k , $k=0,1,2,\dots,E-1$, is generated as follows, where k_0 is given by Table 5.4.2.1-2 according to the value of rv_{id} and LDPC base graph:

$k = 0;$

$j = 0;$

while $k < E$

if $d_{(k_0+j) \bmod N_{cb}} \neq \langle NULL \rangle$

$e_k = d_{(k_0+j) \bmod N_{cb}};$

$k = k + 1;$

end if

$j = j + 1;$

end while

Table 5.4.2.1-2: Starting position of different redundancy versions, k_0

| rv_{id} | k_0 | |
|-----------|---|---|
| | LDPC base graph 1 | LDPC base graph 2 |
| 0 | 0 | 0 |
| 1 | $\left\lfloor \frac{17N_{cb}}{66Z_c} \right\rfloor Z_c$ | $\left\lfloor \frac{13N_{cb}}{50Z_c} \right\rfloor Z_c$ |
| 2 | $\left\lfloor \frac{33N_{cb}}{66Z_c} \right\rfloor Z_c$ | $\left\lfloor \frac{25N_{cb}}{50Z_c} \right\rfloor Z_c$ |
| 3 | $\left\lfloor \frac{56N_{cb}}{66Z_c} \right\rfloor Z_c$ | $\left\lfloor \frac{43N_{cb}}{50Z_c} \right\rfloor Z_c$ |

5.4.2.2 Bit interleaving

The bit sequence $e_0, e_1, e_2, \dots, e_{E-1}$ is interleaved to bit sequence $f_0, f_1, f_2, \dots, f_{E-1}$, according to the following, where the value of Q_m is the modulation order.

for $j = 0$ to $E / Q_m - 1$

for $i = 0$ to $Q_m - 1$

$$f_{i+jQ_m} = e_{i+E/Q_m+j};$$

end for

end for

5.4.3 Rate matching for channel coding of small block lengths

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$. The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$, where E is the rate matching output sequence length. The bit sequence $f_0, f_1, f_2, \dots, f_{E-1}$ is obtained by the following:

for $k = 0$ to $E - 1$

$$f_k = d_{k \bmod N};$$

end for

5.5 Code block concatenation

The input bit sequence for the code block concatenation block are the sequences f_{rk} , for $r = 0, \dots, C - 1$ and $k = 0, \dots, E_r - 1$, where E_r is the number of rate matched bits for the r -th code block. The output bit sequence from the code block concatenation block is the sequence g_k for $k = 0, \dots, G - 1$.

The code block concatenation consists of sequentially concatenating the rate matching outputs for the different code blocks. Therefore,

Set $k = 0$ and $r = 0$

while $r < C$

Set $j = 0$

while $j < E_r$

$$g_k = f_{rj}$$

$$k = k + 1$$

$$j = j + 1$$

end while

$$r = r + 1$$

end while

6 Uplink transport channels and control information

6.1 Random access channel

The sequence index for the random access channel is received from higher layers and is processed according to [4, TS 38.211].

6.2 Uplink shared channel

6.2.1 Transport block CRC attachment

Error detection is provided on each UL-SCH transport block through a Cyclic Redundancy Check (CRC).

The entire transport block is used to calculate the CRC parity bits. Denote the bits in a transport block delivered to layer 1 by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, and the parity bits by $p_0, p_1, p_2, p_3, \dots, p_{L-1}$, where A is the payload size and L is the number of parity bits. The lowest order information bit a_0 is mapped to the most significant bit of the transport block as defined in Clause 6.1.1 of [TS38.321].

The parity bits are computed and attached to the UL-SCH transport block according to Clause 5.1, by setting L to 24 bits and using the generator polynomial $g_{\text{CRC24A}}(D)$ if $A > 3824$; and by setting L to 16 bits and using the generator polynomial $g_{\text{CRC16}}(D)$ otherwise.

The bits after CRC attachment are denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$, where $B = A + L$.

6.2.2 LDPC base graph selection

For initial transmission of a transport block with coding rate R indicated by the MCS index according to Clause 6.1.4.1 in [6, TS 38.214] and subsequent re-transmission of the same transport block, each code block of the transport block is encoded with either LDPC base graph 1 or 2 according to the following:

- if $A \leq 292$, or if $A \leq 3824$ and $R \leq 0.67$, or if $R \leq 0.25$, LDPC base graph 2 is used;
- otherwise, LDPC base graph 1 is used,

where A is the payload size as described in Clause 6.2.1.

6.2.3 Code block segmentation and code block CRC attachment

The bits input to the code block segmentation are denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$ where B is the number of bits in the transport block (including CRC).

Code block segmentation and code block CRC attachment are performed according to Clause 5.2.2.

The bits after code block segmentation are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where r is the code block number and K_r is the number of bits for code block number r according to Clause 5.2.2.

6.2.4 Channel coding of UL-SCH

Code blocks are delivered to the channel coding block. The bits in a code block are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where r is the code block number, and K_r is the number of bits in code block number r .

The total number of code blocks is denoted by C and each code block is individually LDPC encoded according to Clause 5.3.2.

After encoding the bits are denoted by $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$, where the values of N_r is given in Clause 5.3.2.

6.2.5 Rate matching

Coded bits for each code block, denoted as $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$, are delivered to the rate match block, where r is the code block number, and N_r is the number of encoded bits in code block number r . The total number of code blocks is denoted by C and each code block is individually rate matched according to Clause 5.4.2 by setting $I_{LBRM} = 1$ if higher layer parameter *rateMatching* is set to *limitedBufferRM* and by setting $I_{LBRM} = 0$ otherwise.

After rate matching, the bits are denoted by $f_{r0}, f_{r1}, f_{r2}, f_{r3}, \dots, f_{r(E_r-1)}$, where E_r is the number of rate matched bits for code block number r .

6.2.6 Code block concatenation

The input bit sequence for the code block concatenation block are the sequences $f_{r0}, f_{r1}, f_{r2}, f_{r3}, \dots, f_{r(E_r-1)}$, for $r = 0, \dots, C-1$ and where E_r is the number of rate matched bits for the r -th code block.

Code block concatenation is performed according to Clause 5.5.

The bits after code block concatenation are denoted by $g_0, g_1, g_2, g_3, \dots, g_{G-1}$, where G is the total number of coded bits for transmission.

6.2.7 Data and control multiplexing

Denote the coded bits for UL-SCH as $g_0^{\text{UL-SCH}}, g_1^{\text{UL-SCH}}, g_2^{\text{UL-SCH}}, g_3^{\text{UL-SCH}}, \dots, g_{G^{\text{UL-SCH}}-1}^{\text{UL-SCH}}$.

Denote the coded bits for HARQ-ACK or jointly coded bits for HARQ-ACK and CG-UCI when the high layer parameter *cg-UCI-Multiplexing* is configured, if any, as $g_0^{\text{ACK}}, g_1^{\text{ACK}}, g_2^{\text{ACK}}, g_3^{\text{ACK}}, \dots, g_{G^{\text{ACK}}-1}^{\text{ACK}}$.

Denote the coded bits for CSI part 1, if any, as $g_0^{\text{CSI-part1}}, g_1^{\text{CSI-part1}}, g_2^{\text{CSI-part1}}, g_3^{\text{CSI-part1}}, \dots, g_{G^{\text{CSI-part1}}-1}^{\text{CSI-part1}}$.

Denote the coded bits for CSI part 2, if any, as $g_0^{\text{CSI-part2}}, g_1^{\text{CSI-part2}}, g_2^{\text{CSI-part2}}, g_3^{\text{CSI-part2}}, \dots, g_{G^{\text{CSI-part2}}-1}^{\text{CSI-part2}}$.

Denote the coded bits for CG-UCI without HARQ-ACK, if any, as $g_0^{\text{CG-UCI}}, g_1^{\text{CG-UCI}}, g_2^{\text{CG-UCI}}, g_3^{\text{CG-UCI}}, \dots, g_{G^{\text{CG-UCI}}-1}^{\text{CG-UCI}}$.

Denote the multiplexed data and control coded bit sequence as $g_0, g_1, g_2, g_3, \dots, g_{G-1}$.

Denote l as the OFDM symbol index of the scheduled PUSCH, starting from 0 to $N_{\text{symb,all}}^{\text{PUSCH}} - 1$, where $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS.

Denote k as the subcarrier index of the scheduled PUSCH, starting from 0 to $M_{\text{sc}}^{\text{PUSCH}} - 1$, where $M_{\text{sc}}^{\text{PUSCH}}$ is expressed as a number of subcarriers.

Denote $\Phi_l^{\text{UL-SCH}}$ as the set of resource elements, in ascending order of indices k , available for transmission of data in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$.

Denote $M_{\text{sc}}^{\text{UL-SCH}}(l) = |\Phi_l^{\text{UL-SCH}}|$ as the number of elements in set $\Phi_l^{\text{UL-SCH}}$. Denote $\Phi_l^{\text{UL-SCH}}(j)$ as the j -th element in $\Phi_l^{\text{UL-SCH}}$.

Denote Φ_l^{UCI} as the set of resource elements, in ascending order of indices k , available for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$. Denote $M_{\text{sc}}^{\text{UCI}}(l) = |\Phi_l^{\text{UCI}}|$ as the number of elements in set Φ_l^{UCI} . Denote $\Phi_l^{\text{UCI}}(j)$ as the j -th element in Φ_l^{UCI} . For any OFDM symbol that carries DMRS of the PUSCH, $\Phi_l^{\text{UCI}} = \emptyset$. For any OFDM symbol that does not carry DMRS of the PUSCH, $\Phi_l^{\text{UCI}} = \Phi_l^{\text{UL-SCH}}$.

If frequency hopping is configured for the PUSCH,

- denote $l^{(1)}$ as the OFDM symbol index of the first OFDM symbol after the first set of consecutive OFDM symbol(s) carrying DMRS in the first hop;
- denote $l^{(2)}$ as the OFDM symbol index of the first OFDM symbol after the first set of consecutive OFDM symbol(s) carrying DMRS in the second hop.
- denote $l_{\text{CSI}}^{(1)}$ as the OFDM symbol index of the first OFDM symbol that does not carry DMRS in the first hop;
- denote $l_{\text{CSI}}^{(2)}$ as the OFDM symbol index of the first OFDM symbol that does not carry DMRS in the second hop;
- if HARQ-ACK is present for transmission on the PUSCH with UL-SCH or if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH, let
 - $G^{\text{ACK}}(1) = N_L \cdot Q_m \cdot \lceil G^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rceil$ and $G^{\text{ACK}}(2) = N_L \cdot Q_m \cdot \lceil G^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rceil$;
- if CSI is present for transmission on the PUSCH with UL-SCH, let
 - $G^{\text{CSI-part1}}(1) = N_L \cdot Q_m \cdot \lceil G^{\text{CSI-part1}} / (2 \cdot N_L \cdot Q_m) \rceil$;
 - $G^{\text{CSI-part1}}(2) = N_L \cdot Q_m \cdot \lceil G^{\text{CSI-part1}} / (2 \cdot N_L \cdot Q_m) \rceil$;
 - $G^{\text{CSI-part2}}(1) = N_L \cdot Q_m \cdot \lceil G^{\text{CSI-part2}} / (2 \cdot N_L \cdot Q_m) \rceil$; and
 - $G^{\text{CSI-part2}}(2) = N_L \cdot Q_m \cdot \lceil G^{\text{CSI-part2}} / (2 \cdot N_L \cdot Q_m) \rceil$;
- if CG-UCI is present for transmission on the PUSCH with UL-SCH and without HARQ-ACK, let
 - $G^{\text{CG-UCI}}(1) = N_L \cdot Q_m \cdot \lceil G^{\text{CG-UCI}} / (2 \cdot N_L \cdot Q_m) \rceil$ and $G^{\text{CG-UCI}}(2) = N_L \cdot Q_m \cdot \lceil G^{\text{CG-UCI}} / (2 \cdot N_L \cdot Q_m) \rceil$
- if only HARQ-ACK and CSI part 1 are present for transmission on the PUSCH without UL-SCH, let
 - $G^{\text{ACK}}(1) = \min\left(N_L \cdot Q_m \cdot \lceil G^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rceil, M_3 \cdot N_L \cdot Q_m\right)$;
 - $G^{\text{ACK}}(2) = G^{\text{ACK}} - G^{\text{ACK}}(1)$;
 - $G^{\text{CSI-part1}}(1) = M_1 \cdot N_L \cdot Q_m - G^{\text{ACK}}(1)$; and
 - $G^{\text{CSI-part1}}(2) = G^{\text{CSI-part1}} - G^{\text{CSI-part1}}(1)$;
- if HARQ-ACK, CSI part 1 and CSI part 2 are present for transmission on the PUSCH without UL-SCH, let
 - $G^{\text{ACK}}(1) = \min\left(N_L \cdot Q_m \cdot \lceil G^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rceil, M_3 \cdot N_L \cdot Q_m\right)$;
 - $G^{\text{ACK}}(2) = G^{\text{ACK}} - G^{\text{ACK}}(1)$;
 - if the number of HARQ-ACK information bits is more than 2 or if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH,

- $$G^{\text{CSI-part1}}(1) = \min\left(N_L \cdot Q_m \cdot \left\lfloor \frac{G^{\text{CSI-part1}}}{2 \cdot N_L \cdot Q_m} \right\rfloor, M_1 \cdot N_L \cdot Q_m - G^{\text{ACK}}(1)\right); \text{ otherwise,}$$
- $$G^{\text{CSI-part1}}(1) = \min\left(N_L \cdot Q_m \cdot \left\lfloor \frac{G^{\text{CSI-part1}}}{2 \cdot N_L \cdot Q_m} \right\rfloor, M_1 \cdot N_L \cdot Q_m - G_{\text{rvd}}^{\text{ACK}}(1)\right)$$
- $G^{\text{CSI-part1}}(2) = G^{\text{CSI-part1}} - G^{\text{CSI-part1}}(1)$;
 - $G^{\text{CSI-part2}}(1) = M_1 \cdot N_L \cdot Q_m - G^{\text{CSI-part1}}(1)$ if the number of HARQ-ACK information bits is no more than 2, and $G^{\text{CSI-part2}}(1) = M_1 \cdot N_L \cdot Q_m - G^{\text{ACK}}(1) - G^{\text{CSI-part1}}(1)$ otherwise; and
 - $G^{\text{CSI-part2}}(2) = M_2 \cdot N_L \cdot Q_m - G^{\text{CSI-part1}}(2)$ if the number of HARQ-ACK information bits is no more than 2, and $G^{\text{CSI-part2}}(2) = M_2 \cdot N_L \cdot Q_m - G^{\text{ACK}}(2) - G^{\text{CSI-part1}}(2)$ otherwise;
 - if CG-UCI is present for transmission on the PUSCH with UL-SCH and without HARQ-ACK, let
 - $G^{\text{CSI-part1}}(1) = \min(N_L \cdot Q_m \cdot \lfloor G^{\text{CSI-part1}} / (2 \cdot N_L \cdot Q_m) \rfloor, M_1 \cdot N_L \cdot Q_m - G^{\text{CG-UCI}}(1))$;
 - $G^{\text{CSI-part1}}(2) = G^{\text{CSI-part1}} - G^{\text{CSI-part1}}(1)$;
 - $G^{\text{CSI-part2}}(1) = M_1 \cdot N_L \cdot Q_m - G^{\text{CG-UCI}}(1) - G^{\text{CSI-part1}}(1)$; and
 - $G^{\text{CSI-part2}}(2) = M_2 \cdot N_L \cdot Q_m - G^{\text{CG-UCI}}(2) - G^{\text{CSI-part1}}(2)$;
 - if only CSI part 1 and CSI part 2 are present for transmission on the PUSCH without UL-SCH, let
 - $G^{\text{CSI-part1}}(1) = \min\left(N_L \cdot Q_m \cdot \left\lfloor \frac{G^{\text{CSI-part1}}}{2 \cdot N_L \cdot Q_m} \right\rfloor, M_1 \cdot N_L \cdot Q_m - G_{\text{rvd}}^{\text{ACK}}(1)\right)$;
 - $G^{\text{CSI-part1}}(2) = G^{\text{CSI-part1}} - G^{\text{CSI-part1}}(1)$;
 - $G^{\text{CSI-part2}}(1) = M_1 \cdot N_L \cdot Q_m - G^{\text{CSI-part1}}(1)$; and
 - $G^{\text{CSI-part2}}(2) = M_2 \cdot N_L \cdot Q_m - G^{\text{CSI-part1}}(2)$;
 - let $N_{\text{hop}}^{\text{PUSCH}} = 2$, and denote $N_{\text{sybm,hop}}^{\text{PUSCH}}(1)$, $N_{\text{sybm,hop}}^{\text{PUSCH}}(2)$ as the number of OFDM symbols of the PUSCH in the first and second hop, respectively;
 - N_L is the number of transmission layers of the PUSCH;
 - Q_m is the modulation order of the PUSCH;
 - $M_1 = \sum_{l=0}^{N_{\text{sybm,hop}}^{\text{PUSCH}}(1)-1} M_{\text{SC}}^{\text{UCI}}(l)$;
 - $M_2 = \sum_{l=N_{\text{sybm,hop}}^{\text{PUSCH}}(1)}^{N_{\text{sybm,hop}}^{\text{PUSCH}}(1)+N_{\text{sybm,hop}}^{\text{PUSCH}}(2)-1} M_{\text{SC}}^{\text{UCI}}(l)$
 - $M_3 = \sum_{l=l^{(1)}}^{N_{\text{sybm,hop}}^{\text{PUSCH}}(1)-1} M_{\text{SC}}^{\text{UCI}}(l)$

If frequency hopping is not configured for the PUSCH,

- denote $l^{(1)}$ as the OFDM symbol index of the first OFDM symbol after the first set of consecutive OFDM symbol(s) carrying DMRS;
- denote $l_{\text{CSI}}^{(1)}$ as the OFDM symbol index of the first OFDM symbol that does not carry DMRS;
- if HARQ-ACK is present for transmission on the PUSCH or if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH, let $G^{\text{ACK}}(1) = G^{\text{ACK}}$;

- if CSI is present for transmission on the PUSCH, let $G^{\text{CSI-part1}}(1) = G^{\text{CSI-part1}}$ and $G^{\text{CSI-part2}}(1) = G^{\text{CSI-part2}}$;
- if CG-UCI is present for transmission on the PUSCH without HARQ-ACK, let $G^{\text{CG-UCI}}(1) = G^{\text{CG-UCI}}$;
- let $N_{\text{hop}}^{\text{PUSCH}} = 1$ and $N_{\text{symp,hop}}^{\text{PUSCH}}(1) = N_{\text{symp,all}}^{\text{PUSCH}}$.

The multiplexed data and control coded bit sequence $g_0, g_1, g_2, g_3, \dots, g_{G-1}$ is obtained according to the following:

Step 1:

Set $\bar{\Phi}_l^{\text{UL-SCH}} = \Phi_l^{\text{UL-SCH}}$ for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

Set $\bar{M}_{\text{sc}}^{\text{UL-SCH}}(l) = |\bar{\Phi}_l^{\text{UL-SCH}}|$ for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

Set $\bar{\Phi}_l^{\text{UCI}} = \Phi_l^{\text{UCI}}$ for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

Set $\bar{M}_{\text{sc}}^{\text{UCI}}(l) = |\bar{\Phi}_l^{\text{UCI}}|$ for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

if the number of HARQ-ACK information bits to be transmitted on PUSCH is 0, 1 or 2 bits and without CG-UCI

the number of reserved resource elements for potential HARQ-ACK transmission is calculated according to Clause 6.3.2.4.2.1, by setting $O_{\text{ACK}} = 2$;

denote $G_{\text{rvd}}^{\text{ACK}}$ as the number of coded bits for potential HARQ-ACK transmission using the reserved resource elements;

if frequency hopping is configured for the PUSCH, let $G_{\text{rvd}}^{\text{ACK}}(1) = N_L \cdot Q_m \cdot \lfloor G_{\text{rvd}}^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rfloor$ and

$$G_{\text{rvd}}^{\text{ACK}}(2) = N_L \cdot Q_m \cdot \lceil G_{\text{rvd}}^{\text{ACK}} / (2 \cdot N_L \cdot Q_m) \rceil;$$

if frequency hopping is not configured for the PUSCH, let $G_{\text{rvd}}^{\text{ACK}}(1) = G_{\text{rvd}}^{\text{ACK}}$;

denote $\bar{\Phi}_l^{\text{rvd}}$ as the set of reserved resource elements for potential HARQ-ACK transmission, in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

Set $m_{\text{count}}^{\text{ACK}}(1) = 0$;

Set $m_{\text{count}}^{\text{ACK}}(2) = 0$;

$\bar{\Phi}_l^{\text{rvd}} = \emptyset$ for $l = 0, 1, 2, \dots, N_{\text{symp,all}}^{\text{PUSCH}} - 1$;

for $i = 1$ to $N_{\text{hop}}^{\text{PUSCH}}$

$$l = l^{(i)};$$

while $m_{\text{count}}^{\text{ACK}}(i) < G_{\text{rvd}}^{\text{ACK}}(i)$

if $\bar{M}_{\text{sc}}^{\text{UCI}}(l) > 0$

if $G_{\text{rvd}}^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) \geq \bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m$

$$d = 1;$$

$$m_{\text{count}}^{\text{RE}} = \bar{M}_{\text{sc}}^{\text{UL-SCH}}(l);$$

end if

if $G_{\text{rvd}}^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) < \bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m$

$$d = \left\lfloor \bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m / (G_{\text{rvd}}^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)) \right\rfloor;$$

$$m_{\text{count}}^{\text{RE}} = \left\lceil (G_{\text{rvd}}^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)) / (N_L \cdot Q_m) \right\rceil;$$

end if

for $j = 0$ to $m_{\text{count}}^{\text{RE}} - 1$

$$\bar{\Phi}_l^{\text{rvd}} = \bar{\Phi}_l^{\text{rvd}} \cup \{\bar{\Phi}_l^{\text{UL-SCH}}(j \cdot d)\}$$

$$m_{\text{count}}^{\text{ACK}}(i) = m_{\text{count}}^{\text{ACK}}(i) + N_L \cdot Q_m;$$

end for

end if

$l = l + 1$;

end while

end for

else

$$\bar{\Phi}_l^{\text{rvd}} = \emptyset \text{ for } l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1;$$

end if

Denote $\bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) = |\bar{\Phi}_l^{\text{rvd}}|$ as the number of elements in $\bar{\Phi}_l^{\text{rvd}}$.

Step 2:

if HARQ-ACK is present for transmission on the PUSCH and the number of HARQ-ACK information bits is more than 2 or if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH,

Set $m_{\text{count}}^{\text{ACK}}(1) = 0$;

Set $m_{\text{count}}^{\text{ACK}}(2) = 0$;

Set $m_{\text{count,all}}^{\text{ACK}} = 0$;

for $i = 1$ to $N_{\text{hop}}^{\text{PUSCH}}$

$l = l^{(i)}$;

while $m_{\text{count}}^{\text{ACK}}(i) < G^{\text{ACK}}(i)$

if $\bar{M}_{\text{sc}}^{\text{UCI}}(l) > 0$

if $G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) \geq \bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m$

$d = 1$;

$$m_{\text{count}}^{\text{RE}} = \bar{M}_{\text{sc}}^{\text{UCI}}(l);$$

end if

if $G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) < \bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m$

$$d = \left\lfloor \frac{\bar{M}_{\text{sc}}^{\text{UCI}}(l) \cdot N_L \cdot Q_m}{G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)} \right\rfloor;$$

$$m_{\text{count}}^{\text{RE}} = \left\lceil \frac{G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)}{N_L \cdot Q_m} \right\rceil;$$

end if

for $j = 0$ to $m_{\text{count}}^{\text{RE}} - 1$

$$k = \bar{\Phi}_l^{\text{UCI}}(j \cdot d);$$

for $v = 0$ to $N_L \cdot Q_m - 1$

$$\bar{g}_{l,k,v} = g_{m_{\text{count,all}}^{\text{ACK}}};$$

$$m_{\text{count,all}}^{\text{ACK}} = m_{\text{count,all}}^{\text{ACK}} + 1;$$

$$m_{\text{count}}^{\text{ACK}}(i) = m_{\text{count}}^{\text{ACK}}(i) + 1;$$

end for

end for

$$\bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} = \emptyset;$$

for $j = 0$ to $m_{\text{count}}^{\text{RE}} - 1$

$$\bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} = \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} \cup \bar{\Phi}_l^{\text{UCI}}(j \cdot d);$$

end for

$$\bar{\Phi}_l^{\text{UCI}} = \bar{\Phi}_l^{\text{UCI}} \setminus \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}};$$

$$\bar{\Phi}_l^{\text{UL-SCH}} = \bar{\Phi}_l^{\text{UL-SCH}} \setminus \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}};$$

$$\bar{M}_{\text{sc}}^{\text{UCI}}(l) = |\bar{\Phi}_l^{\text{UCI}}|;$$

$$\bar{M}_{\text{sc}}^{\text{UL-SCH}}(l) = |\bar{\Phi}_l^{\text{UL-SCH}}|;$$

end if

$$l = l + 1;$$

end while

end for

end if

Step 2A:

If CG-UCI is present for transmission on the PUSCH without HARQ-ACK,

Set $m_{count}^{CG-UCI}(1) = 0$;

Set $m_{count}^{CG-UCI}(2) = 0$;

Set $m_{count,all}^{CG-UCI} = 0$;

for $i = 1$ to N_{hop}^{PUSCH}

$l = l^{(i)}$;

while $m_{count}^{CG-UCI}(i) < G^{CG-UCI}(i)$

if $\bar{M}_{sc}^{UCI}(l) > 0$

if $G^{CG-UCI}(i) - m_{count}^{CG-UCI}(1) \geq \bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m$

$d = 1$;

$m_{count}^{RE} = \bar{M}_{sc}^{UCI}(l)$;

end if

if $G^{CG-UCI}(i) - m_{count}^{CG-UCI}(1) < \bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m$

$d = \lceil \bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m / (G^{CG-UCI}(i) - m_{count}^{CG-UCI}(i)) \rceil$;

$m_{count}^{RE} = \lceil (G^{CG-UCI}(i) - m_{count}^{CG-UCI}(i)) / (N_L \cdot Q_m) \rceil$;

end if

for $j = 0$ to $m_{count}^{RE} - 1$

$k = \bar{\Phi}_l^{UCI}(j, d)$;

for $v = 0$ to $N_L \cdot Q_m - 1$

$\bar{g}_{l,k,v} = g_{m_{count,all}^{CG-UCI}}^{CG-UCI}$;

$m_{count,all}^{CG-UCI} = m_{count,all}^{CG-UCI} + 1$;

$m_{count}^{CG-UCI}(i) = m_{count}^{CG-UCI}(i) + 1$;

end for

end for

$\bar{\Phi}_{l,tmp}^{UCI} = \emptyset$;

for $j = 0$ to $m_{count}^{RE} - 1$

$\bar{\Phi}_{l,tmp}^{UCI} = \bar{\Phi}_{l,tmp}^{UCI} \cup \bar{\Phi}_l^{UCI}(j, d)$;

end for

$\bar{\Phi}_l^{UCI} = \bar{\Phi}_l^{UCI} \setminus \bar{\Phi}_{l,tmp}^{UCI}$;

$\bar{\Phi}_l^{UL-SCH} = \bar{\Phi}_l^{UL-SCH} \setminus \bar{\Phi}_{l,tmp}^{UCI}$;

$\bar{M}_{sc}^{UCI}(l) = |\bar{\Phi}_l^{UCI}|$;

$\bar{M}_{sc}^{UL-SCH}(l) = |\bar{\Phi}_l^{UL-SCH}|$;

end if
 $l = l + 1;$
end while
end for
end if

Step 3:

if CSI is present for transmission on the PUSCH,

Set $m_{\text{count}}^{\text{CSI-part1}}(1) = 0;$

Set $m_{\text{count}}^{\text{CSI-part1}}(2) = 0;$

Set $m_{\text{count,all}}^{\text{CSI-part1}} = 0;$

for $i = 1$ to $N_{\text{hop}}^{\text{PUSCH}}$

$l = l_{\text{CSI}}^{(i)};$

while $\bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) \leq 0$

$l = l + 1;$

end while

while $m_{\text{count}}^{\text{CSI-part1}}(i) < G^{\text{CSI-part1}}(i)$

if $\bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) > 0$

if $G^{\text{CSI-part1}}(i) - m_{\text{count}}^{\text{CSI-part1}}(i) \geq (\bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l)) \cdot N_L \cdot Q_m$

$d = 1;$

$m_{\text{count}}^{\text{RE}} = \bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l);$

end if

if $G^{\text{CSI-part1}}(i) - m_{\text{count}}^{\text{CSI-part1}}(i) < (\bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l)) \cdot N_L \cdot Q_m$

$d = \left\lceil \frac{(\bar{M}_{\text{sc}}^{\text{UCI}}(l) - \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l)) \cdot N_L \cdot Q_m}{(G^{\text{CSI-part1}}(i) - m_{\text{count}}^{\text{CSI-part1}}(i))} \right\rceil;$

$m_{\text{count}}^{\text{RE}} = \left\lceil \frac{(G^{\text{CSI-part1}}(i) - m_{\text{count}}^{\text{CSI-part1}}(i))}{(N_L \cdot Q_m)} \right\rceil;$

end if

$\bar{\Phi}_l^{\text{temp}} = \bar{\Phi}_l^{\text{UCI}} \setminus \bar{\Phi}_l^{\text{rvd}};$

for $j = 0$ to $m_{\text{count}}^{\text{RE}} - 1$

$k = \bar{\Phi}_l^{\text{temp}}(j \cdot d);$

for $v=0$ to $N_L \cdot Q_m - 1$

$$\bar{g}_{l,k,v} = g_{m_{\text{count,all}}^{\text{CSI-part1}}};$$

$$m_{\text{count,all}}^{\text{CSI-part1}} = m_{\text{count,all}}^{\text{CSI-part1}} + 1;$$

$$m_{\text{count}}^{\text{CSI-part1}}(i) = m_{\text{count}}^{\text{CSI-part1}}(i) + 1;$$

end for

end for

$$\bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} = \emptyset;$$

for $j=0$ to $m_{\text{count}}^{\text{RE}} - 1$

$$\bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} = \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}} \cup \bar{\Phi}_l^{\text{temp}}(j \cdot d);$$

end for

$$\bar{\Phi}_l^{\text{UCI}} = \bar{\Phi}_l^{\text{UCI}} \setminus \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}};$$

$$\bar{\Phi}_l^{\text{UL-SCH}} = \bar{\Phi}_l^{\text{UL-SCH}} \setminus \bar{\Phi}_{l,\text{tmp}}^{\text{UCI}};$$

$$\bar{M}_{\text{sc}}^{\text{UCI}}(l) = |\bar{\Phi}_l^{\text{UCI}}|;$$

$$\bar{M}_{\text{sc}}^{\text{UL-SCH}}(l) = |\bar{\Phi}_l^{\text{UL-SCH}}|;$$

end if

$$l = l + 1;$$

end while

end for

$$\text{Set } m_{\text{count}}^{\text{CSI-part2}}(1) = 0;$$

$$\text{Set } m_{\text{count}}^{\text{CSI-part2}}(2) = 0;$$

$$\text{Set } m_{\text{count,all}}^{\text{CSI-part2}} = 0;$$

for $i=1$ to $N_{\text{hop}}^{\text{PUSCH}}$

$$l = l_{\text{CSI}}^{(i)};$$

while $\bar{M}_{\text{sc}}^{\text{UCI}}(l) \leq 0$

$$l = l + 1;$$

end while

while $m_{\text{count}}^{\text{CSI-part2}}(i) < G^{\text{CSI-part2}}(i)$

if $\bar{M}_{sc}^{UCI}(l) > 0$

if $G^{CSI-part2}(i) - m_{count}^{CSI-part2}(i) \geq \bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m$

$d = 1$;

$m_{count}^{RE} = \bar{M}_{sc}^{UCI}(l)$;

end if

if $G^{CSI-part2}(i) - m_{count}^{CSI-part2}(i) < \bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m$

$d = \left\lfloor \frac{\bar{M}_{sc}^{UCI}(l) \cdot N_L \cdot Q_m}{G^{CSI-part2}(i) - m_{count}^{CSI-part2}(i)} \right\rfloor$;

$m_{count}^{RE} = \left\lceil \frac{G^{CSI-part2}(i) - m_{count}^{CSI-part2}(i)}{N_L \cdot Q_m} \right\rceil$;

end if

for $j = 0$ to $m_{count}^{RE} - 1$

$k = \bar{\Phi}_l^{UCI}(j \cdot d)$;

for $v = 0$ to $N_L \cdot Q_m - 1$

$\bar{g}_{l,k,v} = g_{m_{count,all}^{CSI-part2}}^{CSI-part2}$;

$m_{count,all}^{CSI-part2} = m_{count,all}^{CSI-part2} + 1$;

$m_{count}^{CSI-part2}(i) = m_{count}^{CSI-part2}(i) + 1$;

end for

end for

$\bar{\Phi}_{l,tmp}^{UCI} = \emptyset$;

for $j = 0$ to $m_{count}^{RE} - 1$

$\bar{\Phi}_{l,tmp}^{UCI} = \bar{\Phi}_{l,tmp}^{UCI} \cup \bar{\Phi}_l^{UCI}(j \cdot d)$;

end for

$\bar{\Phi}_l^{UCI} = \bar{\Phi}_l^{UCI} \setminus \bar{\Phi}_{l,tmp}^{UCI}$;

$\bar{\Phi}_l^{UL-SCH} = \bar{\Phi}_l^{UL-SCH} \setminus \bar{\Phi}_{l,tmp}^{UCI}$;

$\bar{M}_{sc}^{UCI}(l) = |\bar{\Phi}_l^{UCI}|$;

$\bar{M}_{sc}^{UL-SCH}(l) = |\bar{\Phi}_l^{UL-SCH}|$;

end if

$l = l + 1$;

end while

end for

end if

Step 4:

if UL-SCH is present for transmission on the PUSCH,

Set $m_{\text{count}}^{\text{UL-SCH}} = 0$;

for $l = 0$ to $N_{\text{symb,all}}^{\text{PUSCH}} - 1$

if $\bar{M}_{\text{sc}}^{\text{UL-SCH}}(l) > 0$

for $j = 0$ to $\bar{M}_{\text{sc}}^{\text{UL-SCH}}(l) - 1$

$k = \bar{\Phi}_l^{\text{UL-SCH}}(j)$;

for $v = 0$ to $N_L \cdot Q_m - 1$

$\bar{g}_{l,k,v} = g_{m_{\text{count}}}^{\text{UL-SCH}}$;

$m_{\text{count}}^{\text{UL-SCH}} = m_{\text{count}}^{\text{UL-SCH}} + 1$;

end for

end for

end if

end for

end if

Step 5:

if HARQ-ACK is present for transmission on the PUSCH without CG-UCI and the number of HARQ-ACK information bits is no more than 2,

Set $m_{\text{count}}^{\text{ACK}}(1) = 0$;

Set $m_{\text{count}}^{\text{ACK}}(2) = 0$;

Set $m_{\text{countall}}^{\text{ACK}} = 0$;

for $i = 1$ to $N_{\text{hop}}^{\text{PUSCH}}$

$l = l^{(i)}$;

while $m_{\text{count}}^{\text{ACK}}(i) < G^{\text{ACK}}(i)$

if $\bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) > 0$

if $G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) \geq \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) \cdot N_L \cdot Q_m$

$d = 1;$

$$m_{\text{count}}^{\text{RE}} = \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l);$$

end if

if $G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i) < \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) \cdot N_L \cdot Q_m$

$$d = \left\lceil \bar{M}_{\text{sc,rvd}}^{\bar{\Phi}}(l) \cdot N_L \cdot Q_m / (G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)) \right\rceil;$$

$$m_{\text{count}}^{\text{RE}} = \left\lceil (G^{\text{ACK}}(i) - m_{\text{count}}^{\text{ACK}}(i)) / (N_L \cdot Q_m) \right\rceil;$$

end if

for $j = 0$ to $m_{\text{count}}^{\text{RE}} - 1$

$$k = \bar{\Phi}_i^{\text{rvd}}(j \cdot d);$$

for $v = 0$ to $N_L \cdot Q_m - 1$

$$\bar{g}_{l,k,v} = g_{m_{\text{count,all}}^{\text{ACK}}};$$

$$m_{\text{count,all}}^{\text{ACK}} = m_{\text{count,all}}^{\text{ACK}} + 1;$$

$$m_{\text{count}}^{\text{ACK}}(i) = m_{\text{count}}^{\text{ACK}}(i) + 1;$$

end for

end for

end if

$$l = l + 1;$$

end while

end for

end if

Step 6:

Set $t = 0;$

for $l = 0$ to $N_{\text{symb,all}}^{\text{PUSCH}} - 1$

for $j = 0$ to $M_{\text{sc}}^{\text{UL-SCH}}(l) - 1$

$$k = \Phi_i^{\text{UL-SCH}}(j);$$

for $v = 0$ to $N_L \cdot Q_m - 1$

$$g_t = \bar{g}_{l,k,v};$$

$$t = t + 1;$$

end for

end for

end for

6.3 Uplink control information

6.3.1 Uplink control information on PUCCH

The procedure in this clause applies to PUCCH formats 2/3/4.

6.3.1.1 UCI bit sequence generation

6.3.1.1.1 HARQ-ACK/SR only

If only HARQ-ACK bits are transmitted on a PUCCH, the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is determined by setting $a_i = \tilde{o}_i^{ACK}$ for $i = 0, 1, \dots, O^{ACK} - 1$ and $A = O^{ACK}$, where the HARQ-ACK bit sequence $\tilde{o}_0^{ACK}, \tilde{o}_1^{ACK}, \dots, \tilde{o}_{O^{ACK}-1}^{ACK}$ is given by Clause 9.1 of [5, TS38.213].

If only HARQ-ACK and SR bits are transmitted on a PUCCH, the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is determined by setting $a_i = \tilde{o}_i^{ACK}$ for $i = 0, 1, \dots, O^{ACK} - 1$, $a_i = \tilde{o}_{i-O^{ACK}}^{SR}$ for $i = O^{ACK}, O^{ACK} + 1, \dots, O^{ACK} + O^{SR} - 1$, and $A = O^{ACK} + O^{SR}$, where the HARQ-ACK bit sequence $\tilde{o}_0^{ACK}, \tilde{o}_1^{ACK}, \dots, \tilde{o}_{O^{ACK}-1}^{ACK}$ is given by Clause 9.1 of [5, TS 38.213], and the SR bit sequence $\tilde{o}_0^{SR}, \tilde{o}_1^{SR}, \dots, \tilde{o}_{O^{SR}-1}^{SR}$ is given by Clause 9.2.5.1 of [5, TS 38.213].

6.3.1.1.2 CSI only

The bitwidth for PMI of *codebookType=typeI-SinglePanel* with 2 CSI-RS ports is 2 for Rank=1 and 1 for Rank=2, according to Clause 5.2.2.2.1 in [6, TS 38.214].

The bitwidth for PMI of *codebookType=typeI-SinglePanel* with more than 2 CSI-RS ports is provided in Tables 6.3.1.1.2-1, where the values of (N_1, N_2) and (O_1, O_2) are given by Clause 5.2.2.2.1 in [6, TS 38.214].

Table 6.3.1.1.2-1: PMI of *codebookType=typeI-SinglePanel*

| | Information field X_1 for wideband PMI | | | Information field X_2 for wideband PMI or per subband PMI | |
|--|--|--|-----------|---|------------------------|
| | $(i_{1,1}, i_{1,2})$ | | $i_{1,3}$ | i_2 | |
| | <i>codebookMode</i> =1 | <i>codebookMode</i> =2 | | <i>codebookMode</i> =1 | <i>codebookMode</i> =2 |
| Rank = 1 with >2 CSI-RS ports, $N_2 > 1$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | $(\lceil \log_2 \frac{N_1 O_1}{2} \rceil, \lceil \log_2 \frac{N_2 O_2}{2} \rceil)$ | N/A | 2 | 4 |
| Rank = 1 with >2 CSI-RS ports, $N_2 = 1$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | $(\lceil \log_2 (\frac{N_1 O_1}{2}) \rceil, 0)$ | N/A | 2 | 4 |

| | | | | | |
|--|--|--|-----|---|---|
| Rank=2 with 4 CSI-RS ports, $N_2 = 1$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | $(\lceil \log_2 \left(\frac{N_1 O_1}{2}\right) \rceil, 0)$ | 1 | 1 | 3 |
| Rank=2 with >4 CSI-RS ports, $N_2 > 1$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | $(\lceil \log_2 \frac{N_1 O_1}{2} \rceil, \lceil \log_2 \frac{N_2 O_2}{2} \rceil)$ | 2 | 1 | 3 |
| Rank=2 with >4 CSI-RS ports, $N_2 = 1$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | $(\lceil \log_2 \left(\frac{N_1 O_1}{2}\right) \rceil, 0)$ | 2 | 1 | 3 |
| Rank=3 or 4, with 4 CSI-RS ports | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | 0 | | 1 |
| Rank=3 or 4, with 8 or 12 CSI-RS ports | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | 2 | | 1 |
| Rank=3 or 4, with >=16 CSI-RS ports | $(\lceil \log_2 \frac{N_1 O_1}{2} \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | 2 | | 1 |
| Rank=5 or 6 | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | N/A | | 1 |
| Rank=7 or 8, $N_1 = 4, N_2 = 1$ | $(\lceil \log_2 \frac{N_1 O_1}{2} \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | N/A | | 1 |
| Rank=7 or 8, $N_1 > 2, N_2 = 2$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 \frac{N_2 O_2}{2} \rceil)$ | | N/A | | 1 |
| Rank=7 or 8, with $N_1 > 4, N_2 = 1$ or $N_1 = 2, N_2 = 2$ or $N_1 > 2, N_2 > 2$ | $(\lceil \log_2 N_1 O_1 \rceil, \lceil \log_2 N_2 O_2 \rceil)$ | | N/A | | 1 |

The bandwidth for PMI of *codebookType= typeI-MultiPanel* is provided in Tables 6.3.1.1.2-2, where the values of (N_g, N_1, N_2) and (O_1, O_2) are given by Clause 5.2.2.2.2 in [6, TS 38.214].

Table 6.3.1.1.2-2: PMI of *codebookType= typeI-MultiPanel*

| | Information fields X_1 for wideband | | | | | Information fields X_2 for wideband or per subband | | | |
|--|---------------------------------------|-----------|-------------|-------------|-------------|--|-----------|-----------|-----------|
| | $(i_{1,1}, i_{1,2})$ | $i_{1,3}$ | $i_{1,4,1}$ | $i_{1,4,2}$ | $i_{1,4,3}$ | i_2 | $i_{2,0}$ | $i_{2,1}$ | $i_{2,2}$ |
| | | | | | | | | | |

| | | | | | | | | | |
|--|---|-----|---|-----|-----|-----|-----|-----|-----|
| Rank=1 with $N_g = 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | N/A | 2 | N/A | N/A | 2 | N/A | N/A | N/A |
| Rank=1 with $N_g = 4$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | N/A | 2 | 2 | 2 | 2 | N/A | N/A | N/A |
| Rank=2 with $N_g = 2,$ $N_1 N_2 = 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 1 | 2 | N/A | N/A | 1 | N/A | N/A | N/A |
| Rank=3 or 4 with $N_g = 2,$ $N_1 N_2 = 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 0 | 2 | N/A | N/A | 1 | N/A | N/A | N/A |
| Rank=2 or 3 or 4 with $N_g = 2,$ $N_1 N_2 > 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 2 | 2 | N/A | N/A | 1 | N/A | N/A | N/A |
| Rank=2 with $N_g = 4,$ $N_1 N_2 = 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 1 | 2 | 2 | 2 | 1 | N/A | N/A | N/A |
| Rank=3 or 4 with $N_g = 4,$ $N_1 N_2 = 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 0 | 2 | 2 | 2 | 1 | N/A | N/A | N/A |
| Rank=2 or 3 or 4 with $N_g = 4,$ $N_1 N_2 > 2$ <i>codebookMode=1</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 2 | 2 | 2 | 2 | 1 | N/A | N/A | N/A |
| Rank=1 with $N_g = 2$ <i>codebookMode=2</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | N/A | 2 | 2 | N/A | N/A | 2 | 1 | 1 |
| Rank=2 with $N_g = 2,$ $N_1 N_2 = 2$ <i>codebookMode=2</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 1 | 2 | 2 | N/A | N/A | 1 | 1 | 1 |
| Rank=3 or 4 with $N_g = 2,$ $N_1 N_2 = 2$ <i>codebookMode=2</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 0 | 2 | 2 | N/A | N/A | 1 | 1 | 1 |
| Rank=2 or 3 or 4 with $N_g = 2,$ $N_1 N_2 > 2$ <i>codebookMode=2</i> | $(\lceil \log_2 N_1 O_1 \rceil,$ $\lceil \log_2 N_2 O_2 \rceil)$ | 2 | 2 | 2 | N/A | N/A | 1 | 1 | 1 |

The bitwidth for PMI with 1 CSI-RS port is 0.

The bitwidth for RI/LI/CQI/CRI of *codebookType=typeI-SinglePanel* is provided in Tables 6.3.1.1.2-3.

Table 6.3.1.1.2-3: RI, LI, CQI, and CRI of *codebookType=typeI-SinglePanel*

| Field | Bitwidth | | | | |
|--|--|---|---|--|--|
| | 1 antenna port | 2 antenna ports | 4 antenna ports | >4 antenna ports | |
| | | | | Rank1~4 | Rank5~8 |
| Rank Indicator | 0 | $\min(1, \lceil \log_2 n_{\text{RI}} \rceil)$ | $\min(2, \lceil \log_2 n_{\text{RI}} \rceil)$ | $\lceil \log_2 n_{\text{RI}} \rceil$ | $\lceil \log_2 n_{\text{RI}} \rceil$ |
| Layer Indicator | 0 | $\lceil \log_2 v \rceil$ | $\min(2, \lceil \log_2 v \rceil)$ | $\min(2, \lceil \log_2 v \rceil)$ | $\min(2, \lceil \log_2 v \rceil)$ |
| Wide-band CQI for the first TB | 4 | 4 | 4 | 4 | 4 |
| Wideband CQI for the second TB | 0 | 0 | 0 | 0 | 4 |
| Subband differential CQI for the first TB | 2 | 2 | 2 | 2 | 2 |
| Subband differential CQI for the second TB | 0 | 0 | 0 | 0 | 2 |
| CRI | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ |

n_{RI} in Table 6.3.1.1.2-3 is the number of allowed rank indicator values according to Clause 5.2.2.2.1 [6, TS 38.214].

v is the value of the rank. The value of $K_s^{\text{CSI-RS}}$ is the number of CSI-RS resources in the corresponding resource set. The values of the rank indicator field are mapped to allowed rank indicator values with increasing order, where '0' is mapped to the smallest allowed rank indicator value.

The bitwidth for RI/LI/CQI/CRI of *codebookType=typeI-MultiPanel* is provided in Table 6.3.1.1.2-4.

Table 6.3.1.1.2-4: RI, LI, CQI, and CRI of *codebookType=typeI-MultiPanel*

| Field | Bitwidth |
|--------------------------|---|
| Rank Indicator | $\min(2, \lceil \log_2 n_{\text{RI}} \rceil)$ |
| Layer Indicator | $\min(2, \lceil \log_2 v \rceil)$ |
| Wide-band CQI | 4 |
| Subband differential CQI | 2 |
| CRI | $\lceil \log_2 (K_s^{\text{CSI-RS}}) \rceil$ |

where n_{RI} is the number of allowed rank indicator values according to Clause 5.2.2.2.2 [6, TS 38.214], v is the value of the rank, and $K_s^{\text{CSI-RS}}$ is the number of CSI-RS resources in the corresponding resource set. The values of the rank indicator field are mapped to allowed rank indicator values with increasing order, where '0' is mapped to the smallest allowed rank indicator value.

The bitwidth for RI/LI/CQI of *codebookType=typeII* or *codebookType=typeII-PortSelection* is provided in Table 6.3.1.1.2-5.

Table 6.3.1.1.2-5: RI, LI, and CQI of *codebookType=type1* or *type1-PortSelection*

| Field | Bitwidth |
|---|---|
| Rank Indicator | $\min(1, \lceil \log_2 n_{\text{RI}} \rceil)$ |
| Layer Indicator | $\min(2, \lceil \log_2 v \rceil)$ |
| Wide-band CQI | 4 |
| Subband differential CQI | 2 |
| Indicator of the number of non-zero wideband amplitude coefficients M_l for layer l | $\lceil \log_2(2L-1) \rceil$ |

where n_{RI} is the number of allowed rank indicator values according to Clauses 5.2.2.2.3 and 5.2.2.2.4 [6, TS 38.214] and v is the value of the rank. The values of the rank indicator field are mapped to allowed rank indicator values with increasing order, where '0' is mapped to the smallest allowed rank indicator value.

The bitwidth for CRI, SSBRI, RSRP, and differential RSRP are provided in Table 6.3.1.1.2-6.

Table 6.3.1.1.2-6: CRI, SSBRI, and RSRP

| Field | Bitwidth |
|-------------------|---|
| CRI | $\lceil \log_2(K_s^{\text{CSI-RS}}) \rceil$ |
| SSBRI | $\lceil \log_2(K_s^{\text{SSB}}) \rceil$ |
| RSRP | 7 |
| Differential RSRP | 4 |

where $K_s^{\text{CSI-RS}}$ is the number of CSI-RS resources in the corresponding resource set, and K_s^{SSB} is the configured number of SS/PBCH blocks in the corresponding resource set for reporting 'ssb-Index-RSRP'.

The bitwidth for CRI, SSBRI, SINR, and differential SINR are provided in Table 6.3.1.1.2-6A.

Table 6.3.1.1.2-6A: CRI, SSBRI, and SINR

| Field | Bitwidth |
|-------------------|---|
| CRI | $\lceil \log_2(K_s^{\text{CSI-RS}}) \rceil$ |
| SSBRI | $\lceil \log_2(K_s^{\text{SSB}}) \rceil$ |
| SINR | 7 |
| Differential SINR | 4 |

where $K_s^{\text{CSI-RS}}$ is the number of CSI-RS resources in the corresponding resource set, and K_s^{SSB} is the configured number of SS/PBCH blocks in the corresponding resource set for reporting 'ssb-Index-SINR'.

Table 6.3.1.1.2-7: Mapping order of CSI fields of one CSI report, *pmi-FormatIndicator=widebandPMI* and *cqi-FormatIndicator=widebandCQI*

| CSI report number | CSI fields |
|-------------------|--|
| CSI report #n | CRI as in Tables 6.3.1.1.2-3/4, if reported |
| | Rank Indicator as in Tables 6.3.1.1.2-3/4, if reported |
| | Layer Indicator as in Tables 6.3.1.1.2-3/4, if reported |
| | Zero padding bits O_p , if needed |
| | PMI wideband information fields X_1 , from left to right as in Tables 6.3.1.1.2-1/2, if reported |
| | PMI wideband information fields X_2 , from left to right as in Tables 6.3.1.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214], if reported |
| | Wideband CQI for the first TB as in Tables 6.3.1.1.2-3/4, if reported |
| | Wideband CQI for the second TB as in Tables 6.3.1.1.2-3/4, if reported |

The number of zero padding bits O_p in Table 6.3.1.1.2-7 is 0 for 1 CSI-RS port and $O_p = N_{\max} - N_{\text{reported}}$ for more than 1 CSI-RS port, where

- $N_{\max} = \max_{r \in S_{\text{Rank}}} B(r)$ and S_{Rank} is the set of rank values r that are allowed to be reported;
- $N_{\text{reported}} = B(R)$, where R is the reported rank;
- For 2 CSI-RS ports, $B(r) = N_{\text{PMI}}(r) + N_{\text{CQI}}(r) + N_{\text{LI}}(r)$;
- For more than 2 CSI-RS ports, $B(r) = N_{\text{PMI}i_1}(r) + N_{\text{PMI}i_2}(r) + N_{\text{CQI}}(r) + N_{\text{LI}}(r)$;
- if PMI is reported, $N_{\text{PMI}}(1) = 2$ and $N_{\text{PMI}}(2) = 1$; otherwise, $N_{\text{PMI}}(r) = 0$;
- if PMI i_1 is reported, $N_{\text{PMI}i_1}(r)$ is obtained according to Tables 6.3.1.1.2-1/2; otherwise, $N_{\text{PMI}i_1}(r) = 0$;
- if PMI i_2 is reported, $N_{\text{PMI}i_2}(r)$ is obtained according to Tables 6.3.1.1.2-1/2; otherwise, $N_{\text{PMI}i_2}(r) = 0$;
- if CQI is reported, $N_{\text{CQI}}(r)$ is obtained according to Tables 6.3.1.1.2-3/4; otherwise, $N_{\text{CQI}}(r) = 0$;
- if LI is reported, $N_{\text{LI}}(r)$ is obtained according to Tables 6.3.1.1.2-3/4; otherwise, $N_{\text{LI}}(r) = 0$.

Table 6.3.1.1.2-8: Mapping order of CSI fields of one report for CRI/RSRP or SSBRI/RSRP reporting

| CSI report number | CSI fields |
|-------------------|---|
| CSI report #n | CRI or SSBRI #1 as in Table 6.3.1.1.2-6, if reported |
| | CRI or SSBRI #2 as in Table 6.3.1.1.2-6, if reported |
| | CRI or SSBRI #3 as in Table 6.3.1.1.2-6, if reported |
| | CRI or SSBRI #4 as in Table 6.3.1.1.2-6, if reported |
| | RSRP #1 as in Table 6.3.1.1.2-6, if reported |
| | Differential RSRP #2 as in Table 6.3.1.1.2-6, if reported |
| | Differential RSRP #3 as in Table 6.3.1.1.2-6, if reported |
| | Differential RSRP #4 as in Table 6.3.1.1.2-6, if reported |

Table 6.3.1.1.2-8A: Mapping order of CSI fields of one report for CRI/SINR or SSBRI/SINR reporting

| CSI report number | CSI fields |
|-------------------|--|
| CSI report #n | CRI or SSBRI #1 as in Table 6.3.1.1.2-6A, if reported |
| | CRI or SSBRI #2 as in Table 6.3.1.1.2-6A, if reported |
| | CRI or SSBRI #3 as in Table 6.3.1.1.2-6A, if reported |
| | CRI or SSBRI #4 as in Table 6.3.1.1.2-6A, if reported |
| | SINR #1 as in Table 6.3.1.1.2-6A, if reported |
| | Differential SINR #2 as in Table 6.3.1.1.2-6A, if reported |
| | Differential SINR #3 as in Table 6.3.1.1.2-6A, if reported |
| | Differential SINR #4 as in Table 6.3.1.1.2-6A, if reported |

Table 6.3.1.1.2-9: Mapping order of CSI fields of one CSI report, CSI part 1, *pmi-FormatIndicator= subbandPMI* or *cqi-FormatIndicator=subbandCQI*

| CSI report number | CSI fields |
|-----------------------------|---|
| CSI report #n CSI part 1 | CRI as in Tables 6.3.1.1.2-3/4, if reported |
| | Rank Indicator as in Tables 6.3.1.1.2-3/4/5, if reported |
| | Wideband CQI for the first TB as in Tables 6.3.1.1.2-3/4/5, if reported |
| | Subband differential CQI for the first TB with increasing order of subband number as in Tables 6.3.1.1.2-3/4/5, if reported |
| | Indicator of the number of non-zero wideband amplitude coefficients M_0 for layer 0 as in Table 6.3.1.1.2-5, if reported |
| | Indicator of the number of non-zero wideband amplitude coefficients M_1 for layer 1 as in Table 6.3.1.1.2-5 (if the rank according to the reported RI is equal to one, this field is set to all zeros), if 2-layer PMI reporting is allowed according to the rank restriction in Clauses 5.2.2.2.3 and 5.2.2.2.4 [6, TS 38.214] and if reported |
| Note: | Subbands for given CSI report n indicated by the higher layer parameter <i>csi-ReportingBand</i> are numbered continuously in the increasing order with the lowest subband of <i>csi-ReportingBand</i> as subband 0. |

Table 6.3.1.1.2-10: Mapping order of CSI fields of one CSI report, CSI part 2 wideband, *pmi-FormatIndicator= subbandPMI* or *cqi-FormatIndicator=subbandCQI*

| CSI report number | CSI fields |
|---|---|
| CSI report #n CSI part 2 wideband | Wideband CQI for the second TB as in Tables 6.3.1.1.2-3/4/5, if present and reported |
| | Layer Indicator as in Tables 6.3.1.1.2-3/4/5, if reported |
| | PMI wideband information fields X_1 , from left to right as in Tables 6.3.1.1.2-1/2, if reported |
| | PMI wideband information fields X_2 , from left to right as in Tables 6.3.1.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214], if <i>pmi-FormatIndicator= widebandPMI</i> and if reported |

Table 6.3.1.1.2-11: Mapping order of CSI fields of one CSI report, CSI part 2 subband, *pmi-FormatIndicator*= *subbandPMI* or *cqi-FormatIndicator*=*subbandCQI*

| | |
|---------------------------------|--|
| CSI report #n Part 2 subband | Subband differential CQI for the second TB of all even subbands with increasing order of subband number, as in Tables 6.3.1.1.2-3/4/5, if <i>cqi-FormatIndicator</i> = <i>subbandCQI</i> and if reported |
| | PMI subband information fields X_2 of all even subbands with increasing order of subband number, from left to right as in Tables 6.3.1.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214] of all even subbands with increasing order of subband number, if <i>pmi-FormatIndicator</i> = <i>subbandPMI</i> and if reported |
| | Subband differential CQI for the second TB of all odd subbands with increasing order of subband number, as in Tables 6.3.1.1.2-3/4/5, if <i>cqi-FormatIndicator</i> = <i>subbandCQI</i> and if reported |
| | PMI subband information fields X_2 of all odd subbands with increasing order of subband number, from left to right as in Tables 6.3.1.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214] of all odd subbands with increasing order of subband number, if <i>pmi-FormatIndicator</i> = <i>subbandPMI</i> and if reported |

Note: Subbands for given CSI report n indicated by the higher layer parameter *csi-ReportingBand* are numbered continuously in the increasing order with the lowest subband of *csi-ReportingBand* as subband 0.

If none of the CSI reports for transmission on a PUCCH is of two parts, the CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-12, are mapped to the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ starting with a_0 . The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to a_0 .

Table 6.3.1.1.2-12: Mapping order of CSI reports to UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, without two-part CSI report(s)

| UCI bit sequence | CSI report number |
|------------------|--|
| a_0 | CSI report #1 as in Table 6.3.1.1.2-7/8 |
| a_1 | |
| a_2 | CSI report #2 as in Table 6.3.1.1.2-7/8 |
| a_3 | ... |
| \vdots | |
| a_{A-1} | CSI report #n as in Table 6.3.1.1.2-7/8 |

If at least one of the CSI reports for transmission on a PUCCH is of two parts, two UCI bit sequences are generated, $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ and $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$. The CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-13, are mapped to the UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ starting with $a_0^{(1)}$. The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to $a_0^{(1)}$. The CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-14, are mapped to the UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ starting with $a_0^{(2)}$. The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to $a_0^{(2)}$. If the length of UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ is less than 3 bits, zeros shall be appended to the UCI bit sequence until its length equals 3.

Table 6.3.1.1.2-13: Mapping order of CSI reports to UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$, with two-part CSI report(s)

| UCI bit sequence | CSI report number |
|-----------------------|---|
| $a_0^{(1)}$ | CSI report #1 if CSI report #1 is not of two parts, or CSI report #1, CSI part 1, if CSI report #1 is of two parts, as in Table 6.3.1.1.2-7/8/9 |
| $a_1^{(1)}$ | CSI report #2 if CSI report #2 is not of two parts, or CSI report #2, CSI part 1, if CSI report #2 is of two parts, as in Table 6.3.1.1.2-7/8/9 |
| $a_2^{(1)}$ | ... |
| $a_3^{(1)}$ | ... |
| \vdots | ... |
| $a_{A^{(1)}-1}^{(1)}$ | CSI report #n if CSI report #n is not of two parts, or CSI report #n, CSI part 1, if CSI report #n is of two parts, as in Table 6.3.1.1.2-7/8/9 |

where CSI report #1, CSI report #2, ..., CSI report #n in Table 6.3.1.1.2-13 correspond to the CSI reports in increasing order of CSI report priority values according to Clause 5.2.5 of [6, TS38.214].

Table 6.3.1.1.2-14: Mapping order of CSI reports to UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$, with two-part CSI report(s)

| UCI bit sequence | CSI report number |
|---|---|
| $a_0^{(2)}$ $a_1^{(2)}$ $a_2^{(2)}$ $a_3^{(2)}$ \vdots $a_{A^{(2)}-1}^{(2)}$ | CSI report #1, CSI part 2 wideband, as in Table 6.3.1.1.2-10 if CSI part 2 exists for CSI report #1 |
| | CSI report #2, CSI part 2 wideband, as in Table 6.3.1.1.2-10 if CSI part 2 exists for CSI report #2 |
| | ... |
| | CSI report #n, CSI part 2 wideband, as in Table 6.3.1.1.2-10 if CSI part 2 exists for CSI report #n |
| | CSI report #1, CSI part 2 subband, as in Table 6.3.1.1.2-11 if CSI part 2 exists for CSI report #1 |
| | CSI report #2, CSI part 2 subband, as in Table 6.3.1.1.2-11 if CSI part 2 exists for CSI report #2 |
| | ... |
| | CSI report #n, CSI part 2 subband, as in Table 6.3.1.1.2-11 if CSI part 2 exists for CSI report #n |

where CSI report #1, CSI report #2, ..., CSI report #n in Table 6.3.1.1.2-14 correspond to the CSI reports in increasing order of CSI report priority values according to Clause 5.2.5 of [6, TS38.214].

6.3.1.1.3 HARQ-ACK/SR and CSI

If none of the CSI reports for transmission on a PUCCH is of two parts, the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is generated according to the following, where $A = O^{ACK} + O^{SR} + O^{CSI}$:

- if there is HARQ-ACK for transmission on the PUCCH, the HARQ-ACK bits are mapped to the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{O^{ACK}-1}$, where $a_i = \tilde{o}_i^{ACK}$ for $i = 0, 1, \dots, O^{ACK} - 1$, the HARQ-ACK bit sequence $\tilde{o}_0^{ACK}, \tilde{o}_1^{ACK}, \dots, \tilde{o}_{O^{ACK}-1}^{ACK}$ is given by Clause 9.1 of [5, TS38.213], and O^{ACK} is number of HARQ-ACK bits; if there is no HARQ-ACK for transmission on the PUCCH, set $O^{ACK} = 0$;

- if there is SR for transmission on the PUCCH, set $a_i = \tilde{\delta}_{i-O^{\text{ACK}}}^{\text{SR}}$ for $i = O^{\text{ACK}}, O^{\text{ACK}} + 1, \dots, O^{\text{ACK}} + O^{\text{SR}} - 1$, where the SR bit sequence $\tilde{\delta}_0^{\text{SR}}, \tilde{\delta}_1^{\text{SR}}, \dots, \tilde{\delta}_{O^{\text{SR}}-1}^{\text{SR}}$ is given by Clause 9.2.5.1 of [5, TS 38.213]; if there is no SR for transmission on the PUCCH, set $O^{\text{SR}} = 0$;
- the CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-12, are mapped to the UCI bit sequence $a_{O^{\text{ACK}}+O^{\text{SR}}}, a_{O^{\text{ACK}}+O^{\text{SR}}+1}, \dots, a_{O^{\text{ACK}}+O^{\text{SR}}+O^{\text{CSI}}-1}$ starting with $a_{O^{\text{ACK}}+O^{\text{SR}}}$, where O^{CSI} is the number of CSI bits.

If at least one of the CSI reports for transmission on a PUCCH is of two parts, two UCI bit sequences are generated, $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ and $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$, according to the following, where

$A^{(1)} = O^{\text{ACK}} + O^{\text{SR}} + O^{\text{CSI-part1}}$ and $A^{(2)} = O^{\text{CSI-part2}}$:

- if there is HARQ-ACK for transmission on the PUCCH, the HARQ-ACK bits are mapped to the UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{O^{\text{ACK}}-1}^{(1)}$, where $a_i^{(1)} = \tilde{\delta}_i^{\text{ACK}}$ for $i = 0, 1, \dots, O^{\text{ACK}} - 1$, the HARQ-ACK bit sequence $\tilde{\delta}_0^{\text{ACK}}, \tilde{\delta}_1^{\text{ACK}}, \dots, \tilde{\delta}_{O^{\text{ACK}}-1}^{\text{ACK}}$ is given by Clause 9.1 of [5, TS38.213], and O^{ACK} is number of HARQ-ACK bits; if there is no HARQ-ACK for transmission on the PUCCH, set $O^{\text{ACK}} = 0$;
- if there is SR for transmission on the PUCCH, set $a_i = \tilde{\delta}_{i-O^{\text{ACK}}}^{\text{SR}}$ for $i = O^{\text{ACK}}, O^{\text{ACK}} + 1, \dots, O^{\text{ACK}} + O^{\text{SR}} - 1$, where the SR bit sequence $\tilde{\delta}_0^{\text{SR}}, \tilde{\delta}_1^{\text{SR}}, \dots, \tilde{\delta}_{O^{\text{SR}}-1}^{\text{SR}}$ is given by Clause 9.2.5.1 of [5, TS 38.213]; if there is no SR for transmission on the PUCCH, set $O^{\text{SR}} = 0$;
- the CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-13, are mapped to the UCI bit sequence $a_{O^{\text{ACK}}+O^{\text{SR}}}, a_{O^{\text{ACK}}+O^{\text{SR}}+1}, \dots, a_{O^{\text{ACK}}+O^{\text{SR}}+O^{\text{CSI-part1}}-1}$ starting with $a_{O^{\text{ACK}}+O^{\text{SR}}}$, where $O^{\text{CSI-part1}}$ is the number of CSI bits in CSI part 1 of all CSI reports;
- the CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.1.1.2-14, are mapped to the UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ starting with $a_0^{(2)}$, where $O^{\text{CSI-part2}}$ is the number of CSI bits in CSI part 2 of all CSI reports. If the length of UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ is less than 3 bits, zeros shall be appended to the UCI bit sequence until its length equals 3.

6.3.1.2 Code block segmentation and CRC attachment

The UCI bit sequence from clause 6.3.1.1 is denoted by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, where A is the payload size. The procedure in 6.3.1.2.1 applies for $A \geq 12$ and the procedure in Clause 6.3.1.2.2 applies for $A \leq 11$.

6.3.1.2.1 UCI encoded by Polar code

If the payload size $A \geq 12$, code block segmentation and CRC attachment is performed according to Clause 5.2.1. If ($A \geq 360$ and $E \geq 1088$) or if $A \geq 1013$, $I_{\text{seg}} = 1$; otherwise $I_{\text{seg}} = 0$, where E is the rate matching output sequence length as given in Clause 6.3.1.4.1.

If $12 \leq A \leq 19$, the parity bits $p_{r0}, p_{r1}, p_{r2}, \dots, p_{r(L-1)}$ in Clause 5.2.1 are computed by setting L to 6 bits and using the generator polynomial $g_{\text{CRC6}}(D)$ in Clause 5.1, resulting in the sequence $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$ where r is the code block number and K_r is the number of bits for code block number r .

If $A \geq 20$, the parity bits $p_{r0}, p_{r1}, p_{r2}, \dots, p_{r(L-1)}$ in Clause 5.2.1 are computed by setting L to 11 bits and using the generator polynomial $g_{\text{CRC11}}(D)$ in Clause 5.1, resulting in the sequence $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$ where r is the code block number and K_r is the number of bits for code block number r .

6.3.1.2.2 UCI encoded by channel coding of small block lengths

If the payload size $A \leq 11$, CRC bits are not attached.

The output bit sequence is denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where $c_i = a_i$ for $i = 0, 1, \dots, A-1$ and $K = A$.

6.3.1.3 Channel coding of UCI

6.3.1.3.1 UCI encoded by Polar code

Information bits are delivered to the channel coding block. They are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where r is the code block number, and K_r is the number of bits in code block number r . The total number of code blocks is denoted by C and each code block is individually encoded by the following:

If $18 \leq K_r \leq 25$, the information bits are encoded via Polar coding according to Clause 5.3.1, by setting $n_{\max} = 10$, $I_{LL} = 0$, $n_{PC} = 3$, $n_{PC}^{wm} = 1$ if $E_r - K_r + 3 > 192$ and $n_{PC}^{wm} = 0$ if $E_r - K_r + 3 \leq 192$, where E_r is the rate matching output sequence length as given in Clause 6.3.1.4.1.

If $K_r > 30$, the information bits are encoded via Polar coding according to Clause 5.3.1, by setting $n_{\max} = 10$, $I_{LL} = 0$, $n_{PC} = 0$, and $n_{PC}^{wm} = 0$.

After encoding the bits are denoted by $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$, where N_r is the number of coded bits in code block number r .

6.3.1.3.2 UCI encoded by channel coding of small block lengths

Information bits are delivered to the channel coding block. They are denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits.

The information bits are encoded according to Clause 5.3.3.

After encoding the bits are denoted by $d_0, d_1, d_2, d_3, \dots, d_{N-1}$, where N is the number of coded bits.

6.3.1.4 Rate matching

For PUCCH formats 2/3/4, the total rate matching output sequence length E_{tot} is given by Table 6.3.1.4-1, where

$N_{\text{symb,UCI}}^{\text{PUCCH}2}$, $N_{\text{symb,UCI}}^{\text{PUCCH}3}$, and $N_{\text{symb,UCI}}^{\text{PUCCH}4}$ are the number of symbols carrying UCI for PUCCH formats 2/3/4 respectively; $N_{\text{PRB}}^{\text{PUCCH}2}$ and $N_{\text{PRB}}^{\text{PUCCH}3}$ are the number of PRBs that are determined by the UE for PUCCH formats 2/3 transmission respectively according to Clause 9.2 of [5, TS38.213]; and $N_{\text{SF}}^{\text{PUCCH}2}$, $N_{\text{SF}}^{\text{PUCCH}3}$, and $N_{\text{SF}}^{\text{PUCCH}4}$ are the spreading factors for PUCCH format 2, PUCCH format 3, and PUCCH format 4, respectively.

Table 6.3.1.4-1: Total rate matching output sequence length E_{tot}

| PUCCH format | Modulation order | |
|----------------|---|---|
| | QPSK | $\pi/2$ -BPSK |
| PUCCH format 2 | $16 \cdot N_{\text{symb,UCI}}^{\text{PUCCH}2} \cdot N_{\text{PRB}}^{\text{PUCCH}2} / N_{\text{SF}}^{\text{PUCCH}2}$ | N/A |
| PUCCH format 3 | $24 \cdot N_{\text{symb,UCI}}^{\text{PUCCH}3} \cdot N_{\text{PRB}}^{\text{PUCCH}3} / N_{\text{SF}}^{\text{PUCCH}3}$ | $12 \cdot N_{\text{symb,UCI}}^{\text{PUCCH}3} \cdot N_{\text{PRB}}^{\text{PUCCH}3} / N_{\text{SF}}^{\text{PUCCH}3}$ |
| PUCCH format 4 | $24 \cdot N_{\text{symb,UCI}}^{\text{PUCCH}4} / N_{\text{SF}}^{\text{PUCCH}4}$ | $12 \cdot N_{\text{symb,UCI}}^{\text{PUCCH}4} / N_{\text{SF}}^{\text{PUCCH}4}$ |

6.3.1.4.1 UCI encoded by Polar code

The input bit sequence to rate matching is $d_{r_0}, d_{r_1}, d_{r_2}, d_{r_3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Table 6.3.1.4.1-1: Rate matching output sequence length E_{UCI}

| UCI(s) for transmission on a PUCCH | UCI for encoding | Value of E_{UCI} |
|--|--------------------------|---|
| HARQ-ACK | HARQ-ACK | $E_{\text{UCI}} = E_{\text{tot}}$ |
| HARQ-ACK, SR | HARQ-ACK, SR | $E_{\text{UCI}} = E_{\text{tot}}$ |
| CSI (CSI not of two parts) | CSI | $E_{\text{UCI}} = E_{\text{tot}}$ |
| HARQ-ACK, CSI (CSI not of two parts) | HARQ-ACK, CSI | $E_{\text{UCI}} = E_{\text{tot}}$ |
| HARQ-ACK, SR, CSI (CSI not of two parts) | HARQ-ACK, SR, CSI | $E_{\text{UCI}} = E_{\text{tot}}$ |
| CSI (CSI of two parts) | CSI part 1 | $E_{\text{UCI}} = \min(E_{\text{tot}}, \lceil (O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |
| | CSI part 2 | $E_{\text{UCI}} = E_{\text{tot}} - \min(E_{\text{tot}}, \lceil (O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |
| HARQ-ACK, CSI (CSI of two parts) | HARQ-ACK, CSI part 1 | $E_{\text{UCI}} = \min(E_{\text{tot}}, \lceil (O^{\text{ACK}} + O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |
| | CSI part 2 | $E_{\text{UCI}} = E_{\text{tot}} - \min(E_{\text{tot}}, \lceil (O^{\text{ACK}} + O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |
| HARQ-ACK, SR, CSI (CSI of two parts) | HARQ-ACK, SR, CSI part 1 | $E_{\text{UCI}} = \min(E_{\text{tot}}, \lceil (O^{\text{ACK}} + O^{\text{SR}} + O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |
| | CSI part 2 | $E_{\text{UCI}} = E_{\text{tot}} - \min(E_{\text{tot}}, \lceil (O^{\text{ACK}} + O^{\text{SR}} + O^{\text{CSI-part1}} + L) / R_{\text{UCI}}^{\text{max}} / Q_m \rceil \cdot Q_m)$ |

Rate matching is performed according to Clause 5.4.1 by setting $I_{\text{BL}} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{\text{UCI}} / C_{\text{UCI}} \rfloor$, where C_{UCI} is the number of code blocks for UCI determined according to Clause 6.3.1.2.1 and the value of E_{UCI} is given by Table 6.3.1.4.1-1:

- O^{ACK} is the number of bits for HARQ-ACK for transmission on the current PUCCH;
- O^{SR} is the number of bits for SR for transmission on the current PUCCH;
- $O^{\text{CSI-part1}}$ is the number of bits for CSI part 1 for transmission on the current PUCCH;
- $O^{\text{CSI-part2}}$ is the number of bits for CSI part 2 for transmission on the current PUCCH;
- if $A \geq 360$, $L = 11$; otherwise, L is the number of CRC bits determined according to clause 6.3.1.2.1, where A equals $O^{\text{CSI-part1}}$ for "CSI (CSI of two parts)", equals $O^{\text{ACK}} + O^{\text{CSI-part1}}$ for "HARQ-ACK, CSI (CSI of two parts)", and equals $O^{\text{ACK}} + O^{\text{SR}} + O^{\text{CSI-part1}}$ for "HARQ-ACK, SR, CSI (CSI of two parts)" respectively in Table 6.3.1.4.1-1;;
- $R_{\text{UCI}}^{\text{max}}$ is the configured maximum PUCCH coding rate;
- E_{tot} is given by Table 6.3.1.4-1.

The output bit sequence after rate matching is denoted as $f_{r_0}, f_{r_1}, f_{r_2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.1.4.2 UCI encoded by channel coding of small block lengths

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

The value of E_{UCI} is determined according to Table 6.3.1.4.1-1 by setting $L = 0$.

Rate matching is performed according to Clause 5.4.3 by setting the rate matching output sequence length $E = E_{UCI}$.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.1.5 Code block concatenation

The input bit sequence for the code block concatenation block are the sequences $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$, for $r = 0, \dots, C-1$ and where E_r is the number of rate matched bits for the r -th code block.

Code block concatenation is performed according to Clause 5.5.

The bits after code block concatenation are denoted by $g_0, g_1, g_2, g_3, \dots, g_{G'-1}$, where $G' = \lfloor E_{UCI} / C_{UCI} \rfloor \cdot C_{UCI}$ with the values of E_{UCI} and C_{UCI} given in Clause 6.3.1.4.1. Let G be the total number of coded bits for transmission and $G = G' + \text{mod}(E_{UCI}, C_{UCI})$. Set $g_i = 0$ for $i = G', G'+1, \dots, G-1$.

6.3.1.6 Multiplexing of coded UCI bits to PUCCH

If CSI of two parts are transmitted on a PUCCH, the coded bits corresponding to UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ is denoted by $g_0^{(1)}, g_1^{(1)}, g_2^{(1)}, g_3^{(1)}, \dots, g_{G^{(1)}-1}^{(1)}$ and the coded bits corresponding to UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ is denoted by $g_0^{(2)}, g_1^{(2)}, g_2^{(2)}, g_3^{(2)}, \dots, g_{G^{(2)}-1}^{(2)}$. The coded bit sequence $g_0, g_1, g_2, g_3, \dots, g_{G-1}$, where $G = G^{(1)} + G^{(2)}$, is generated according to the following.

Table 6.3.1.6-1: PUCCH DMRS and UCI symbols

| PUCCH duration (symbols) | PUCCH DMRS symbol indices | Number of UCI symbol indices sets N_{UCI}^{set} | 1 st UCI symbol indices set $S_{UCI}^{(1)}$ | 2 nd UCI symbol indices set $S_{UCI}^{(2)}$ | 3 rd UCI symbol indices set $S_{UCI}^{(3)}$ |
|--------------------------|---------------------------|---|--|--|--|
| 4 | {1} | 2 | {0,2} | {3} | - |
| 4 | {0,2} | 1 | {1,3} | - | - |
| 5 | {0, 3} | 1 | {1, 2, 4} | - | - |
| 6 | {1, 4} | 1 | {0, 2, 3, 5} | - | - |
| 7 | {1, 4} | 2 | {0, 2, 3, 5} | {6} | - |
| 8 | {1, 5} | 2 | {0, 2, 4, 6} | {3, 7} | - |
| 9 | {1, 6} | 2 | {0, 2, 5, 7} | {3, 4, 8} | - |
| 10 | {2, 7} | 2 | {1, 3, 6, 8} | {0, 4, 5, 9} | - |
| 10 | {1, 3, 6, 8} | 1 | {0,2,4,5,7,9} | - | - |
| 11 | {2, 7} | 3 | {1,3,6,8} | {0,4,5,9} | {10} |
| 11 | {1,3,6,9} | 1 | {0,2,4,5,7,8,10} | - | - |
| 12 | {2, 8} | 3 | {1,3,7,9} | {0,4,6,10} | {5, 11} |
| 12 | {1,4,7,10} | 1 | {0,2,3,5,6,8,9,11} | - | - |
| 13 | {2, 9} | 3 | {1,3,8,10} | {0,4,7,11} | {5,6,12} |
| 13 | {1,4,7,11} | 2 | {0,2,3,5,6,8,10,12} | {9} | - |
| 14 | {3, 10} | 3 | {2,4,9,11} | {1,5,8,12} | {0,6,7,13} |
| 14 | {1,5,8,12} | 2 | {0,2,4,6,7,9,11,13} | {3, 10} | - |

Denote s_i as UCI OFDM symbol index. Denote $N_{UCI}^{(i)}$ as the number of elements in UCI symbol indices set $S_{UCI}^{(i)}$ for $i = 1, \dots, N_{UCI}^{set}$, where $S_{UCI}^{(i)}$ and N_{UCI}^{set} are given by Table 6.3.1.6-1 according to the PUCCH duration and the PUCCH

DMRS configuration. Denote $N_{\text{symb,UCI}}^{PUCCH} = \sum_{i=1}^{N_{UCI}^{set}} N_{UCI}^{(i)}$ as the number of OFDM symbols carrying UCI in the PUCCH.

Denote Q_m as the modulation order of the PUCCH.

For PUCCH format 3, set $N_{\text{UCI}}^{\text{symbol}} = 12 \cdot N_{\text{PRB}}^{\text{PUCCH},3} / N_{\text{SF}}^{\text{PUCCH},3}$, where $N_{\text{PRB}}^{\text{PUCCH},3}$ is the number of PRBs that is determined by the UE for PUCCH format 3 transmission according to Clause 9.2 of [5, TS 38.213], and $N_{\text{SF}}^{\text{PUCCH},3}$ is the spreading factor for PUCCH format 3 [4, TS 38.211].

For PUCCH format 4, set $N_{\text{UCI}}^{\text{symbol}} = 12 / N_{\text{SF}}^{\text{PUCCH},4}$, where $N_{\text{SF}}^{\text{PUCCH},4}$ is the spreading factor for PUCCH format 4.

Find the smallest $j > 0$ such that $\left(\sum_{i=1}^j N_{\text{UCI}}^{(i)} \right) \cdot N_{\text{UCI}}^{\text{symbol}} \cdot Q_m \geq G^{(1)}$.

Set $n_1 = 0$;

Set $n_2 = 0$;

Set $\bar{N}_{\text{UCI}}^{\text{symbol}} = \left\lceil \left(G^{(1)} - \left(\sum_{i=1}^{j-1} N_{\text{UCI}}^{(i)} \right) \cdot N_{\text{UCI}}^{\text{symbol}} \cdot Q_m \right) / \left(N_{\text{UCI}}^{(j)} \cdot Q_m \right) \right\rceil$;

Set $M = \text{mod} \left(\left(G^{(1)} - \left(\sum_{i=1}^{j-1} N_{\text{UCI}}^{(i)} \right) \cdot N_{\text{UCI}}^{\text{symbol}} \cdot Q_m \right) / Q_m, N_{\text{UCI}}^{(j)} \right)$;

for $l = 0$ to $N_{\text{symb,UCI}}^{\text{PUCCH}} - 1$

if $s_l \in \bigcup_{i=1}^{j-1} S_{\text{UCI}}^{(i)}$

for $k = 0$ to $N_{\text{UCI}}^{\text{symbol}} - 1$

for $v = 0$ to $Q_m - 1$

$\bar{g}_{l,k,v} = g_{n_1}^{(1)}$;

$n_1 = n_1 + 1$;

end for

end for

elseif $s_l \in S_{\text{UCI}}^{(j)}$

if $M > 0$

$\gamma = 1$;

else

$\gamma = 0$;

end if

$M = M - 1$;

for $k = 0$ to $\bar{N}_{\text{UCI}}^{\text{symbol}} + \gamma - 1$

for $v = 0$ to $Q_m - 1$

$\bar{g}_{l,k,v} = g_{n_1}^{(1)}$;

```

     $n_1 = n_1 + 1;$ 
  end for
end for
for  $k = \bar{N}_{\text{UCI}}^{\text{symbol}} + \gamma$  to  $N_{\text{UCI}}^{\text{symbol}} - 1$ 
  for  $v = 0$  to  $Q_m - 1$ 
     $\bar{g}_{l,k,v} = g_{n_2}^{(2)};$ 
     $n_2 = n_2 + 1;$ 
  end for
end for
else
  for  $k = 0$  to  $N_{\text{UCI}}^{\text{symbol}} - 1$ 
    for  $v = 0$  to  $Q_m - 1$ 
       $\bar{g}_{l,k,v} = g_{n_2}^{(2)};$ 
       $n_2 = n_2 + 1;$ 
    end for
  end for
end if
end for
Set  $n = 0$ 
for  $l = 0$  to  $N_{\text{symp,UCI}}^{\text{PUCCH}} - 1$ 
  for  $k = 0$  to  $N_{\text{UCI}}^{\text{symbol}} - 1$ 
    for  $v = 0$  to  $Q_m - 1$ 
       $g_n = \bar{g}_{l,k,v};$ 
       $n = n + 1;$ 
    end for
  end for
end for
end for

```

6.3.2 Uplink control information on PUSCH

6.3.2.1 UCI bit sequence generation

6.3.2.1.1 HARQ-ACK

If HARQ-ACK bits are transmitted on a PUSCH, the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is determined as follows:

- If UCI is transmitted on PUSCH without UL-SCH and the UCI includes CSI part 1 without CSI part 2,
- if there is no HARQ-ACK bit given by Clause 9.1 of [5, TS 38.213], set $a_0 = 0$, $a_1 = 0$, and $A = 2$;
- if there is only one HARQ-ACK bit \tilde{o}_0^{ACK} given by Clause 9.1 of [5, TS 38.213], set $a_0 = \tilde{o}_0^{ACK}$, $a_1 = 0$, and $A = 2$;
- otherwise, set $a_i = \tilde{o}_i^{ACK}$ for $i = 0, 1, \dots, O^{ACK} - 1$ and $A = O^{ACK}$, where the HARQ-ACK bit sequence $\tilde{o}_0^{ACK}, \tilde{o}_1^{ACK}, \dots, \tilde{o}_{O^{ACK}-1}^{ACK}$ is given by Clause 9.1 of [5, TS 38.213].

6.3.2.1.2 CSI

The bitwidth for PMI of *codebookType=typeI-SinglePanel* and *codebookType=typeI-MultiPanel* is specified in Clause 6.3.1.1.2.

The bitwidth for RI/LI/CQI/CRI of *codebookType=typeI-SinglePanel* and *codebookType=typeI-MultiPanel* is specified in Clause 6.3.1.1.2.

The bitwidth for PMI of *codebookType=typeII* is provided in Tables 6.3.2.1.2-1, where the values of (N_1, N_2) , (O_1, O_2) , L , N_{PSK} , M_1 , M_2 , and $K^{(2)}$ are given by Clause 5.2.2.2.3 in [6, TS 38.214].

Table 6.3.2.1.2-1: PMI of *codebookType= typeII*

| | Information fields X_1 for wideband PMI | | | | | | Information fields X_2 for wideband PMI or per subband PMI | | | |
|-------------------------|---|---|----------------------------|-------------|----------------------------|-------------|---|---|--------------------------|--------------------------|
| | $i_{1,1}$ | $i_{1,2}$ | $i_{1,3,1}$ | $i_{1,4,1}$ | $i_{1,3,2}$ | $i_{1,4,2}$ | $i_{2,1,1}$ | $i_{2,1,2}$ | $i_{2,2,1}$ | $i_{2,2,2}$ |
| Rank=1 SBAmpp off | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | N/A | N/A | $(M_1 - 1) \cdot \log_2 N_{PSK}$ | N/A | N/A | N/A |
| Rank=2 SBAmpp off | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $(M_1 - 1) \cdot \log_2 N_{PSK}$ | $(M_2 - 1) \cdot \log_2 N_{PSK}$ | N/A | N/A |
| Rank=1 SBAmpp on | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | N/A | N/A | $\min(M_1, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_1 - \min(M_1, K^{(2)}))$ | N/A | $\min(M_1, K^{(2)}) - 1$ | N/A |
| Rank=2 SBAmpp on | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\min(M_1, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_1 - \min(M_1, K^{(2)}))$ | $\min(M_2, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_2 - \min(M_2, K^{(2)}))$ | $\min(M_1, K^{(2)}) - 1$ | $\min(M_2, K^{(2)}) - 1$ |

The bitwidth for PMI of *codebookType=typeII-r16* is provided in Tables 6.3.2.1.2-1A, where the values of (N_1, N_2) , (O_1, O_2) , L , K^{NZ} , N_3 , and $\{M_l\}_{l=1, \dots, v}$ are given by Clause 5.2.2.2.5 in [6, TS 38.214].

Table 6.3.2.1.2-1A: PMI of *codebookType= typell-r16*

| | Information fields X_1 | | | | | | | | | | | |
|-------------------------|---------------------------------|---|-------------------------------|----------------------------|------------------------------|--|--|---|---|-------------------------------|-------------------------------|-------------------------------|
| | $i_{1,1}$ | $i_{1,2}$ | $i_{1,8,1}$ | $i_{1,8,2}$ | $i_{1,8,3}$ | $i_{1,8,4}$ | | | | | | |
| Rank=1 $N_3 \leq 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2 K^{NZ} \rceil$ | N/A | N/A | N/A | | | | | | |
| Rank=2 $N_3 \leq 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | N/A | | | | | | |
| Rank=3 $N_3 \leq 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | | | | | | |
| Rank=4 $N_3 \leq 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | | | | | | |
| Rank=1 $N_3 > 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2 K^{NZ} \rceil$ | N/A | N/A | N/A | | | | | | |
| Rank=2 $N_3 > 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | N/A | | | | | | |
| Rank=3 $N_3 > 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | | | | | | |
| Rank=4 $N_3 > 19$ | $\lceil \log_2(O_1 O_2) \rceil$ | $\lceil \log_2 \left(\frac{N_1 N_2}{L} \right) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | | | | | | |
| | Information fields X_2 | | | | | | | | | | | |
| | $i_{2,3,1}$ | $i_{2,3,2}$ | $i_{2,3,3}$ | $i_{2,3,4}$ | $i_{1,5}$ | $i_{1,6,1}$ | $i_{1,6,2}$ | $i_{1,6,3}$ | $i_{1,6,4}$ | $\{i_{2,4,i}\}_{i=1,\dots,v}$ | $\{i_{2,5,i}\}_{i=1,\dots,v}$ | $\{i_{1,7,i}\}_{i=1,\dots,v}$ |
| Rank=1 $N_3 \leq 19$ | 4 | N/A | N/A | N/A | N/A | $\lceil \log_2 \left(\frac{N_3 - 1}{M_1 - 1} \right) \rceil$ | N/A | N/A | N/A | $3(K^{NZ} - 1)$ | $4(K^{NZ} - 1)$ | $2LM_1$ |
| Rank=2 $N_3 \leq 19$ | 4 | 4 | N/A | N/A | N/A | $\lceil \log_2 \left(\frac{N_3 - 1}{M_2 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_2 - 1} \right) \rceil$ | N/A | N/A | $3(K^{NZ} - 2)$ | $4(K^{NZ} - 2)$ | $4LM_2$ |
| Rank=3 $N_3 \leq 19$ | 4 | 4 | 4 | N/A | N/A | $\lceil \log_2 \left(\frac{N_3 - 1}{M_3 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_3 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_3 - 1} \right) \rceil$ | N/A | $3(K^{NZ} - 3)$ | $4(K^{NZ} - 3)$ | $6LM_3$ |
| Rank=4 $N_3 \leq 19$ | 4 | 4 | 4 | 4 | N/A | $\lceil \log_2 \left(\frac{N_3 - 1}{M_4 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_4 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_4 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{N_3 - 1}{M_4 - 1} \right) \rceil$ | $3(K^{NZ} - 4)$ | $4(K^{NZ} - 4)$ | $8LM_4$ |
| Rank=1 $N_3 > 19$ | 4 | N/A | N/A | N/A | $\lceil \log_2(2M_1) \rceil$ | $\lceil \log_2 \left(\frac{2M_1 - 1}{M_1 - 1} \right) \rceil$ | N/A | N/A | N/A | $3(K^{NZ} - 1)$ | $4(K^{NZ} - 1)$ | $2LM_1$ |
| Rank=2 $N_3 > 19$ | 4 | 4 | N/A | N/A | $\lceil \log_2(2M_2) \rceil$ | $\lceil \log_2 \left(\frac{2M_2 - 1}{M_2 - 1} \right) \rceil$ | $\lceil \log_2 \left(\frac{2M_2 - 1}{M_2 - 1} \right) \rceil$ | N/A | N/A | $3(K^{NZ} - 2)$ | $4(K^{NZ} - 2)$ | $4LM_2$ |

| | | | | | | | | | | | | |
|----------------------|---|---|---|-----|------------------------------|--|--|--|--|-----------------|-----------------|---------|
| Rank=3 $N_3 > 19$ | 4 | 4 | 4 | N/A | $\lceil \log_2(2M_3) \rceil$ | $\lceil \log_2 \binom{2M_3-1}{M_3-1} \rceil$ | $\lceil \log_2 \binom{2M_3-1}{M_3-1} \rceil$ | $\lceil \log_2 \binom{2M_3-1}{M_3-1} \rceil$ | N/A | $3(K^{NZ} - 3)$ | $4(K^{NZ} - 3)$ | $6LM_3$ |
| Rank=4 $N_3 > 19$ | 4 | 4 | 4 | 4 | $\lceil \log_2(2M_4) \rceil$ | $\lceil \log_2 \binom{2M_4-1}{M_4-1} \rceil$ | $\lceil \log_2 \binom{2M_4-1}{M_4-1} \rceil$ | $\lceil \log_2 \binom{2M_4-1}{M_4-1} \rceil$ | $\lceil \log_2 \binom{2M_4-1}{M_4-1} \rceil$ | $3(K^{NZ} - 4)$ | $4(K^{NZ} - 4)$ | $8LM_4$ |

Note: the bandwidth for $\{i_{1,7,l}\}_{l=1,\dots,v}$, $\{i_{2,4,l}\}_{l=1,\dots,v}$ and $\{i_{2,5,l}\}_{l=1,\dots,v}$ shown in Table 6.3.2.1.2-1A is the total bandwidth of $\{i_{1,7,l}\}$, $\{i_{2,4,l}\}$ and $\{i_{2,5,l}\}$ up to Rank = v , respectively, and the corresponding per layer bandwidths are $2LM_v$, $3(K_l^{NZ} - 1)$, and $4(K_l^{NZ} - 1)$, (i.e., 1, 3, and 4 bits for each respective indicator elements $k_{l,i,f}^{(3)}$, $k_{l,i,f}^{(2)}$, and $c_{l,i,f}$, respectively), where K_l^{NZ} as defined in Clause 5.2.2.2.5 in [6, TS 38.214] is the number of nonzero coefficients for layer l such that $K^{NZ} = \sum_{l=1}^v K_l^{NZ}$.

The bandwidth for PMI of *codebookType=typeII-PortSelection* is provided in Tables 6.3.2.1.2-2, where the values of P_{CSI-RS} , d , L , N_{PSK} , M_1 , M_2 , and $K^{(2)}$ are given by Clause 5.2.2.2.4 in [6, TS 38.214].

Table 6.3.2.1.2-2: PMI of *codebookType=typeII-PortSelection*

| | Information fields X_1 for wideband PMI | | | | | Information fields X_2 for wideband PMI or per subband PMI | | | |
|--------------------------|---|----------------------------|-------------|----------------------------|-------------|---|---|--------------------------|--------------------------|
| | $i_{1,1}$ | $i_{1,3,1}$ | $i_{1,4,1}$ | $i_{1,3,2}$ | $i_{1,4,2}$ | $i_{2,1,1}$ | $i_{2,1,2}$ | $i_{2,2,1}$ | $i_{2,2,2}$ |
| Rank=1 SBAmpon off | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | N/A | N/A | $(M_1-1) \cdot \log_2 N_{PSK}$ | N/A | N/A | N/A |
| Rank=2 SBAmpon off | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $(M_1-1) \cdot \log_2 N_{PSK}$ | $(M_2-1) \cdot \log_2 N_{PSK}$ | N/A | N/A |
| Rank=1 SBAmpon on | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | N/A | N/A | $\min(M_1, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_1 - \min(M_1, K^{(2)}))$ | N/A | $\min(M_1, K^{(2)}) - 1$ | N/A |
| Rank=2 SBAmpon on | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\lceil \log_2(2L) \rceil$ | $3(2L-1)$ | $\min(M_1, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_1 - \min(M_1, K^{(2)}))$ | $\min(M_2, K^{(2)}) \cdot \log_2 N_{PSK} - \log_2 N_{PSK} + 2 \cdot (M_2 - \min(M_2, K^{(2)}))$ | $\min(M_1, K^{(2)}) - 1$ | $\min(M_2, K^{(2)}) - 1$ |

The bandwidth for PMI of *codebookType=typeII-PortSelection-r16* is provided in Tables 6.3.2.1.2-2A, where the values of P_{CSI-RS} , d , L , K^{NZ} , N_3 , and $\{M_l\}_{l=1,\dots,v}$ are given by Clause 5.2.2.2.6 in [6, TS 38.214].

Table 6.3.2.1.2-2A: PMI of *codebookType=typeII-PortSelection-r16*

| | Information fields X_1 | | | | |
|-------------------------|---|-------------------------------|----------------------------|-------------|-------------|
| | $i_{1,1}$ | $i_{1,8,1}$ | $i_{1,8,2}$ | $i_{1,8,3}$ | $i_{1,8,4}$ |
| Rank=1 $N_3 \leq 19$ | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2 K^{NZ} \rceil$ | N/A | N/A | N/A |
| Rank=2 $N_3 \leq 19$ | $\lceil \log_2 \left\lceil \frac{P_{CSI-RS}}{2d} \right\rceil \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | N/A |

| | | | | | | | | | | | | |
|--------------------------|--|-------------|-------------|-------------|-------------------------------|---|---|---|---|-------------------------------|-------------------------------|-------------------------------|
| Rank=3 $N_3 \leq 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | | | | |
| Rank=4 $N_3 \leq 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | | | | |
| Rank=1 $N_3 > 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2 K^{NZ} \rceil$ | N/A | N/A | N/A | | | | |
| Rank=2 $N_3 > 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | N/A | | | | |
| Rank=3 $N_3 > 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | N/A | | | | |
| Rank=4 $N_3 > 19$ | $\left\lceil \log_2 \left[\frac{P_{CSI-RS}}{2d} \right] \right\rceil$ | | | | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | $\lceil \log_2(2L) \rceil$ | | | | |
| Information fields X_2 | | | | | | | | | | | | |
| | $i_{2,3,1}$ | $i_{2,3,2}$ | $i_{2,3,3}$ | $i_{2,3,4}$ | $i_{1,5}$ | $i_{1,6,1}$ | $i_{1,6,2}$ | $i_{1,6,3}$ | $i_{1,6,4}$ | $\{i_{2,4,i}\}_{i=1,\dots,v}$ | $\{i_{2,5,i}\}_{i=1,\dots,v}$ | $\{i_{1,7,i}\}_{i=1,\dots,v}$ |
| Rank=1 $N_3 \leq 19$ | 4 | N/A | N/A | N/A | N/A | $\left\lceil \log_2 \binom{N_3-1}{M_1-1} \right\rceil$ | N/A | N/A | N/A | $3(K^{NZ}-1)$ | $4(K^{NZ}-1)$ | $2LM_1$ |
| Rank=2 $N_3 \leq 19$ | 4 | 4 | N/A | N/A | N/A | $\left\lceil \log_2 \binom{N_3-1}{M_2-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_2-1} \right\rceil$ | N/A | N/A | $3(K^{NZ}-2)$ | $4(K^{NZ}-2)$ | $4LM_2$ |
| Rank=3 $N_3 \leq 19$ | 4 | 4 | 4 | N/A | N/A | $\left\lceil \log_2 \binom{N_3-1}{M_3-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_3-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_3-1} \right\rceil$ | N/A | $3(K^{NZ}-3)$ | $4(K^{NZ}-3)$ | $6LM_3$ |
| Rank=4 $N_3 \leq 19$ | 4 | 4 | 4 | 4 | N/A | $\left\lceil \log_2 \binom{N_3-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{N_3-1}{M_4-1} \right\rceil$ | $3(K^{NZ}-4)$ | $4(K^{NZ}-4)$ | $8LM_4$ |
| Rank=1 $N_3 > 19$ | 4 | N/A | N/A | N/A | $\lceil \log_2(2M_1) \rceil$ | $\left\lceil \log_2 \binom{2M_1-1}{M_1-1} \right\rceil$ | N/A | N/A | N/A | $3(K^{NZ}-1)$ | $4(K^{NZ}-1)$ | $2LM_1$ |
| Rank=2 $N_3 > 19$ | 4 | 4 | N/A | N/A | $\lceil \log_2(2M_2) \rceil$ | $\left\lceil \log_2 \binom{2M_2-1}{M_2-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_2-1}{M_2-1} \right\rceil$ | N/A | N/A | $3(K^{NZ}-2)$ | $4(K^{NZ}-2)$ | $4LM_2$ |
| Rank=3 $N_3 > 19$ | 4 | 4 | 4 | N/A | $\lceil \log_2(2M_3) \rceil$ | $\left\lceil \log_2 \binom{2M_3-1}{M_3-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_3-1}{M_3-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_3-1}{M_3-1} \right\rceil$ | N/A | $3(K^{NZ}-3)$ | $4(K^{NZ}-3)$ | $6LM_3$ |
| Rank=4 $N_3 > 19$ | 4 | 4 | 4 | 4 | $\lceil \log_2(2M_4) \rceil$ | $\left\lceil \log_2 \binom{2M_4-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_4-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_4-1}{M_4-1} \right\rceil$ | $\left\lceil \log_2 \binom{2M_4-1}{M_4-1} \right\rceil$ | $3(K^{NZ}-4)$ | $4(K^{NZ}-4)$ | $8LM_4$ |

Note: the bitwidth for $\{i_{1,7,l}\}_{l=1,\dots,v}$, $\{i_{2,4,l}\}_{l=1,\dots,v}$ and $\{i_{2,5,l}\}_{l=1,\dots,v}$ shown in Table 6.3.2.1.2-2A is the total bitwidth of $\{i_{1,7,l}\}$, $\{i_{2,4,l}\}$ and $\{i_{2,5,l}\}$ up to Rank = v , respectively, and the corresponding per layer bitwidths are $2LM_v$, $3(K_l^{NZ} - 1)$, and $4(K_l^{NZ} - 1)$, (i.e., 1, 3, and 4 bits for each respective indicator elements $k_{l,i,f}^{(3)}$, $k_{l,i,f}^{(2)}$, and $c_{l,i,f}$, respectively), where K_l^{NZ} as defined in Clause 5.2.2.2.5 in [6, TS 38.214] is the number of nonzero coefficients for layer l such that $K^{NZ} = \sum_{l=1}^v K_l^{NZ}$.

For CSI on PUSCH, two UCI bit sequences are generated, $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ and $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$. The CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.2.1.2-6, are mapped to the UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$ starting with $a_0^{(1)}$. The CSI fields of all CSI reports, in the order from upper part to lower part in Table 6.3.2.1.2-7, are mapped to the UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$ starting with $a_0^{(2)}$.

The mapping order of CSI fields of one report for CRI/RSRP or SSBRI/RSRP reporting is provided in Table 6.3.1.1.2-8. The mapping order of CSI fields of one report for CRI/SINR or SSBRI/SINR reporting is provided in Table 6.3.1.1.2-8A. The procedure in clause 6.3.2 described for CSI part 1 is also applicable for one report for CRI/RSRP, SSBRI/RSRP, CRI/SINR, or SSBRI/SINR reporting.

Table 6.3.2.1.2-3: Mapping order of CSI fields of one CSI report, CSI part 1

| CSI report number | CSI fields |
|-----------------------------|---|
| CSI report #n CSI part 1 | CRI as in Tables 6.3.1.1.2-3/4/6, if reported |
| | Rank Indicator as in Tables 6.3.1.1.2-3/4/5 or 6.3.2.1.2-8, if reported |
| | Wideband CQI for the first TB as in Tables 6.3.1.1.2-3/4/5 or 6.3.2.1.2-8, if reported |
| | Subband differential CQI for the first TB with increasing order of subband number as in Tables 6.3.1.1.2-3/4/5 or 6.3.2.1.2-8, if reported |
| | Indicator of the number of non-zero wideband amplitude coefficients M_0 for layer 0 as in Table 6.3.1.1.2-5, if reported |
| | Indicator of the number of non-zero wideband amplitude coefficients M_1 for layer 1 as in Table 6.3.1.1.2-5 (if the rank according to the reported RI is equal to one, this field is set to all zeros), if 2-layer PMI reporting is allowed according to the rank restriction in Clauses 5.2.2.2.3 and 5.2.2.2.4 [6, TS 38.214] and if reported |
| | Indicator of the total number of non-zero coefficients summed across all layers K^{NZ} as in Table 6.3.2.1.2-8, if reported |
| Note: | Subbands for given CSI report n indicated by the higher layer parameter <i>csi-ReportingBand</i> are numbered continuously in the increasing order with the lowest subband of <i>csi-ReportingBand</i> as subband 0. |

Table 6.3.2.1.2-4: Mapping order of CSI fields of one CSI report, CSI part 2 wideband

| CSI report number | CSI fields |
|---|--|
| CSI report #n CSI part 2 wideband | Wideband CQI for the second TB as in Tables 6.3.1.1.2-3/4/5, if present and reported |
| | Layer Indicator as in Tables 6.3.1.1.2-3/4/5, if reported |
| | PMI wideband information fields X_1 , from left to right as in Tables 6.3.1.1.2-1/2 or 6.3.2.1.2-1/2, if reported |
| | PMI wideband information fields X_2 , from left to right as in Tables 6.3.1.1.2-1/2 or 6.3.2.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214], if <i>pmi-FormatIndicator</i> = <i>widebandPMI</i> and if reported |

Table 6.3.2.1.2-5: Mapping order of CSI fields of one CSI report, CSI part 2 subband

| | |
|---------------------------------|---|
| CSI report #n Part 2 subband | Subband differential CQI for the second TB of all even subbands with increasing order of subband number, as in Tables 6.3.1.1.2-3/4/5, if <i>cqi-FormatIndicator=subbandCQI</i> and if reported |
| | PMI subband information fields X_2 of all even subbands with increasing order of subband number, from left to right as in Tables 6.3.1.1.2-1/2 or 6.3.2.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214] of all even subbands with increasing order of subband number, if <i>pmi-FormatIndicator= subbandPMI</i> and if reported |
| | Subband differential CQI for the second TB of all odd subbands with increasing order of subband number, as in Tables 6.3.1.1.2-3/4/5, if <i>cqi-FormatIndicator=subbandCQI</i> and if reported |
| | PMI subband information fields X_2 of all odd subbands with increasing order of subband number, from left to right as in Tables 6.3.1.1.2-1/2 or 6.3.2.1.2-1/2, or codebook index for 2 antenna ports according to Clause 5.2.2.2.1 in [6, TS38.214] of all odd subbands with increasing order of subband number, if <i>pmi-FormatIndicator= subbandPMI</i> and if reported |

Note: Subbands for given CSI report *n* indicated by the higher layer parameter *csi-ReportingBand* are numbered continuously in the increasing order with the lowest subband of *csi-ReportingBand* as subband 0.

Table 6.3.2.1.2-5A: Mapping order of CSI fields of one CSI report, CSI part 2 of *codebookType=typell-r16* or *typell-PortSelection-r16*

| CSI report number | CSI fields |
|--------------------------------------|---|
| CSI report #n CSI part 2, group 0 | PMI fields X_1 , from left to right as in Tables 6.3.2.1.2-1A/2A, if reported |
| CSI report #n CSI part 2, group 1 | The following PMI fields X_2 , from left to right, as in Tables 6.3.2.1.2-1A/2A: $\{i_{2,3,l}: l = 1, \dots, v\}$, $i_{1,5}$, $\{i_{1,6,l}: l = 1, \dots, v\}$ and $(\lfloor \frac{K^{NZ}}{2} \rfloor - v) \times 3$ highest priority bits of $\{i_{2,4,l}: l = 1, \dots, v\}$, $(\lfloor \frac{K^{NZ}}{2} \rfloor - v) \times 4$ highest priority bits of $\{i_{2,5,l}: l = 1, \dots, v\}$ and $v * 2LM_v - \lfloor \frac{K^{NZ}}{2} \rfloor$ highest priority bits of $\{i_{1,7,l}: l = 1, \dots, v\}$, in decreasing order of priority based on function $Pri(l, i, f)$ defined in clause 5.2.3 of TS38.214, if reported |
| CSI report #n CSI part 2, group 2 | The following PMI fields X_2 , from left to right, as in Tables 6.3.2.1.2-1A/2A: $\lfloor \frac{K^{NZ}}{2} \rfloor \times 3$ lowest priority bits of $\{i_{2,4,l}: l = 1, \dots, v\}$, $\lfloor \frac{K^{NZ}}{2} \rfloor \times 4$ lowest priority bits of $\{i_{2,5,l}: l = 1, \dots, v\}$ and $\lfloor \frac{K^{NZ}}{2} \rfloor$ lowest priority bits of $\{i_{1,7,l}: l = 1, \dots, v\}$, in decreasing order of priority based on function $Pri(l, i, f)$ defined in clause 5.2.3 of TS38.214, if reported |

Table 6.3.2.1.2-6: Mapping order of CSI reports to UCI bit sequence $a_0^{(1)}, a_1^{(1)}, a_2^{(1)}, a_3^{(1)}, \dots, a_{A^{(1)}-1}^{(1)}$, with two-part CSI report(s)

| UCI bit sequence | CSI report number |
|-----------------------|--|
| $a_0^{(1)}$ | CSI part 1 of CSI report #1 as in Table 6.3.2.1.2-3 or Table 6.3.1.1.2-8 or Table 6.3.1.1.2-8A |
| $a_1^{(1)}$ | CSI part 1 of CSI report #2 as in Table 6.3.2.1.2-3 or Table 6.3.1.1.2-8 or Table 6.3.1.1.2-8A |
| $a_2^{(1)}$ | |
| $a_3^{(1)}$ | ... |
| \vdots | |
| $a_{A^{(1)}-1}^{(1)}$ | CSI part 1 of CSI report #n as in Table 6.3.2.1.2-3 or Table 6.3.1.1.2-8 or Table 6.3.1.1.2-8A |

where CSI report #1, CSI report #2, ..., CSI report #n in Table 6.3.2.1.2-6 correspond to the CSI reports in increasing order of CSI report priority values according to Clause 5.2.5 of [6, TS38.214].

Table 6.3.2.1.2-7: Mapping order of CSI reports to UCI bit sequence $a_0^{(2)}, a_1^{(2)}, a_2^{(2)}, a_3^{(2)}, \dots, a_{A^{(2)}-1}^{(2)}$, with two-part CSI report(s)

| UCI bit sequence | CSI report number |
|---|--|
| $a_0^{(2)}$ $a_1^{(2)}$ $a_2^{(2)}$ $a_3^{(2)}$ \vdots $a_{A^{(2)}-1}^{(2)}$ | CSI report #1, CSI part 2 wideband, as in Table 6.3.2.1.2-4, or CSI part 2 with group 0, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #1 |
| | CSI report #2, CSI part 2 wideband, as in Table 6.3.2.1.2-4, or CSI part 2 with group 0, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #2 |
| | ... |
| | CSI report #n, CSI part 2 wideband, as in Table 6.3.2.1.2-4, or CSI part 2 with group 0, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #n |
| | CSI report #1, CSI part 2 subband, as in Table 6.3.2.1.2-5, or CSI part 2 with group 1 and 2, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #1 |
| | CSI report #2, CSI part 2 subband, as in Table 6.3.2.1.2-5, or CSI part 2 with group 1 and 2, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #2 |
| | ... |
| | CSI report #n, CSI part 2 subband, as in Table 6.3.2.1.2-5, or CSI part 2 with group 1 and 2, as in Table 6.3.2.1.2-5A, if CSI part 2 exists for CSI report #n |

where CSI report #1, CSI report #2, ..., CSI report #n in Table 6.3.2.1.2-7 correspond to the CSI reports in increasing order of CSI report priority values according to Clause 5.2.5 of [6, TS38.214].

The bandwidth for RI/CQI of *codebookType= typeII-r16* or *codebookType=typeII-PortSelection-r16* is provided in Table 6.3.2.1.2-8.

Table 6.3.2.1.2-8: RI and CQI of *codebookType=typeII-r16* or *typeII-PortSelection-r16*

| Field | Bitwidth |
|--|---|
| Rank Indicator | $\min(2, \lceil \log_2 n_{RI} \rceil)$ |
| Wide-band CQI | 4 |
| Subband differential CQI | 2 |
| Indicator of the total number of non-zero coefficients summed across all layers K^{NZ} | $\lceil \log_2(K_0) \rceil$ if max allowed rank is 1; $\lceil \log_2(2K_0) \rceil$ otherwise |

where n_{RI} is the number of allowed rank indicator values according to Clauses 5.2.2.2.5 and 5.2.2.2.6 [6, TS 38.214], $K_0 = \left\lceil 2L \left[p_1 \times \frac{N_3}{R} \right] \beta \right\rceil$, where p_1 , N_3 , R , and β are given by Clause 5.2.2.2.5 and 5.2.2.2.6 in [6, TS 38.214]. The values of the rank indicator field are mapped to allowed rank indicator values with increasing order, where '0' is mapped to the smallest allowed rank indicator value.

6.3.2.1.3 CG-UCI

For CG-UCI bits transmitted on a CG PUSCH, the CG-UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is determined as follows:

- set $a_i = \tilde{o}_i^{CG-UCI}$ for $i = 0, 1, \dots, O^{CG-UCI} - 1$ and $A = O^{CG-UCI}$, where the CG-UCI bit sequence $\tilde{o}_0^{CG-UCI}, \tilde{o}_1^{CG-UCI}, \dots, \tilde{o}_{O^{CG-UCI}-1}^{CG-UCI}$ is given by Table 6.3.2.1.3-1, mapped in the order from upper part to lower part.

Table 6.3.2.1.3-1: Mapping order of CG-UCI fields

| Field | Bitwidth |
|--|--|
| HARQ process number | 4 |
| Redundancy version | 2 |
| New data indicator | 1 |
| Channel Occupancy Time (COT) sharing information | <p>$\lceil \log_2 C \rceil$ if both higher layer parameter <i>ul-toDL-COT-SharingED-Threshold</i> and higher layer parameter <i>cg-COT-SharingList</i> are configured, where <i>C</i> is the number of combinations configured in <i>cg-COT-SharingList</i>;</p> <p>1 if higher layer parameter <i>ul-toDL-COT-SharingED-Threshold</i> is not configured and higher layer parameter <i>cg-COT-SharingOffset</i> is configured;</p> <p>0 otherwise;</p> <p>If a UE indicates COT sharing other than "no sharing" in a CG PUSCH within the UE's initiated COT, the UE should provide consistent COT sharing information in all the subsequent CG PUSCHs, if any, occurring within the same UE's initiated COT such that the same DL starting point and duration are maintained.</p> |

6.3.2.1.4 HARQ-ACK and CG-UCI

When higher layer parameter *cg-UCI-Multiplexing* is configured, the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is determined as follows, where $A = O^{CG-UCI} + O^{ACK}$.

- The CG-UCI bits are mapped to the UCI bit sequence $a_0, a_1, a_2, a_3, \dots, a_{O^{CG-UCI}-1}$, where $a_i = \tilde{\delta}_i^{CG-UCI}$ for $i = 0, 1, \dots, O^{CG-UCI} - 1$. The CG-UCI bit sequence $\tilde{\delta}_0^{CG-UCI}, \tilde{\delta}_1^{CG-UCI}, \dots, \tilde{\delta}_{O^{CG-UCI}-1}^{CG-UCI}$ is given by Table 6.3.2.1.3-1 mapped in the order from upper part to lower part, and O^{CG-UCI} is number of CG-UCI bits;
- The HARQ-ACK bits are mapped to the UCI bit sequence $a_{O^{CG-UCI}}, a_{O^{CG-UCI}+1}, \dots, a_{O^{CG-UCI}+O^{ACK}-1}$, where $a_{i+O^{CG-UCI}} = \tilde{\delta}_i^{ACK}$ for $i = 0, 1, \dots, O^{ACK} - 1$. The HARQ-ACK bit sequence $\tilde{\delta}_0^{ACK}, \tilde{\delta}_1^{ACK}, \dots, \tilde{\delta}_{O^{ACK}-1}^{ACK}$ is given by Clause 9.1 of [5, TS38.213], and O^{ACK} is number of HARQ-ACK bits.

6.3.2.2 Code block segmentation and CRC attachment

Denote the bits of the payload by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, where A is the payload size. The procedure in 6.3.2.2.1 applies for $A \geq 12$ and the procedure in Clause 6.3.2.2.2 applies for $A \leq 11$.

6.3.2.2.1 UCI encoded by Polar code

Code block segmentation and CRC attachment is performed according to Clause 6.3.1.2.1.

6.3.2.2.2 UCI encoded by channel coding of small block lengths

The procedure in Clause 6.3.1.2.2 applies.

6.3.2.3 Channel coding of UCI

6.3.2.3.1 UCI encoded by Polar code

Channel coding is performed according to Clause 6.3.1.3.1, except that the rate matching output sequence length E_r is given in Clause 6.3.2.4.1.

6.3.2.3.2 UCI encoded by channel coding of small block lengths

Information bits are delivered to the channel coding block. They are denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits.

The information bits are encoded according to Clause 5.3.3.

After encoding the bits are denoted by $d_0, d_1, d_2, d_3, \dots, d_{N-1}$, where N is the number of coded bits.

6.3.2.4 Rate matching

6.3.2.4.1 UCI encoded by Polar code

6.3.2.4.1.1 HARQ-ACK

For HARQ-ACK transmission on PUSCH not using repetition type B with UL-SCH, the number of coded modulation symbols per layer for HARQ-ACK transmission, denoted as Q'_{ACK} , is determined as follows:

$$Q'_{\text{ACK}} = \min \left\{ \left[\frac{(O_{\text{ACK}} + L_{\text{ACK}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{sym,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}}-1} K_r} \right], \left\lceil \alpha \cdot \sum_{l=l_0}^{N_{\text{sym,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l) \right\rceil \right\}$$

where

- O_{ACK} is the number of HARQ-ACK bits;
- if $O_{\text{ACK}} \geq 360$, $L_{\text{ACK}} = 11$; otherwise L_{ACK} is the number of CRC bits for HARQ-ACK determined according to Clause 6.3.1.2.1;
- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{HARQ-ACK}}$;
- $C_{\text{UL-SCH}}$ is the number of code blocks for UL-SCH of the PUSCH transmission;
- if the DCI format scheduling the PUSCH transmission includes a CBGTI field indicating that the UE shall not transmit the r -th code block, $K_r = 0$; otherwise, K_r is the r -th code block size for UL-SCH of the PUSCH transmission;
- $M_{\text{sc}}^{\text{PUSCH}}$ is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{\text{sc}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{sym,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{sym,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$;
- α is configured by higher layer parameter *scaling*;

- l_0 is the symbol index of the first OFDM symbol that does not carry DMRS of the PUSCH, after the first DMRS symbol(s), in the PUSCH transmission.

For HARQ-ACK transmission on an actual repetition of a PUSCH with repetition Type B with UL-SCH, the number of coded modulation symbols per layer for HARQ-ACK transmission, denoted as Q'_{ACK} , is determined as follows:

$$Q'_{ACK} = \min \left\{ \left[\frac{(O_{ACK} + L_{ACK}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}} - 1} M_{\text{sc,nominal}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}} - 1} K_r} \right], \left[\alpha \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}} - 1} M_{\text{sc,nominal}}^{\text{UCI}}(l) \right], \left[\sum_{l=0}^{N_{\text{symb,actual}}^{\text{PUSCH}} - 1} M_{\text{sc,actual}}^{\text{UCI}}(l) \right] \right\}$$

where

- $M_{\text{sc,nominal}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,nominal}}^{\text{PUSCH}} - 1$, in the PUSCH transmission assuming a nominal repetition without segmentation, and $N_{\text{symb,nominal}}^{\text{PUSCH}}$ is the total number of OFDM symbols in a nominal repetition of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{\text{sc,nominal}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{\text{sc,nominal}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc,nominal}}^{\text{PT-RS}}(l)$ where $M_{\text{sc,nominal}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission assuming a nominal repetition without segmentation;
- $M_{\text{sc,actual}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,actual}}^{\text{PUSCH}} - 1$, in the actual repetition of the PUSCH transmission, and $N_{\text{symb,actual}}^{\text{PUSCH}}$ is the total number of OFDM symbols in the actual repetition of the PUSCH transmission, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the actual repetition of the PUSCH transmission, $M_{\text{sc,actual}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the actual repetition of the PUSCH transmission, $M_{\text{sc,actual}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc,actual}}^{\text{PT-RS}}(l)$ where $M_{\text{sc,actual}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the actual repetition of the PUSCH transmission;
- and all the other notations in the formula are defined the same as for PUSCH not using repetition type B.

For HARQ-ACK transmission on PUSCH without UL-SCH, the number of coded modulation symbols per layer for HARQ-ACK transmission, denoted as Q'_{ACK} , is determined as follows:

$$Q'_{ACK} = \min \left\{ \left[\frac{(O_{ACK} + L_{ACK}) \cdot \beta_{\text{offset}}^{\text{PUSCH}}}{R \cdot Q_m} \right], \left[\alpha \cdot \sum_{l=l_0}^{N_{\text{symb,all}}^{\text{PUSCH}} - 1} M_{\text{sc}}^{\text{UCI}}(l) \right] \right\}$$

where

- O_{ACK} is the number of HARQ-ACK bits;
- if $O_{ACK} \geq 360$, $L_{ACK} = 11$; otherwise L_{ACK} is the number of CRC bits for HARQ-ACK defined according to Clause 6.3.1.2.1;;

- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{HARQ-ACK}}$;
- $M_{\text{sc}}^{\text{PUSCH}}$ is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{\text{sc}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
- for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
- for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$;
- l_0 is the symbol index of the first OFDM symbol that does not carry DMRS of the PUSCH, after the first DMRS symbol(s), in the PUSCH transmission;
- R is the code rate of the PUSCH, determined according to Clause 6.1.4.1 of [6, TS38.214];
- Q_m is the modulation order of the PUSCH;
- α is configured by higher layer parameter *scaling*.

The input bit sequence to rate matching is $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Rate matching is performed according to Clause 5.4.1 by setting $I_{\text{BL}} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{\text{UCI}} / C_{\text{UCI}} \rfloor$, where

- C_{UCI} is the number of code blocks for UCI determined according to Clause 5.2.1;
- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH;
- $E_{\text{UCI}} = N_L \cdot Q'_{\text{ACK}} \cdot Q_m$.

The output bit sequence after rate matching is denoted as $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.2.4.1.2 CSI part 1

For CSI part 1 transmission on PUSCH not using repetition type B with UL-SCH, the number of coded modulation symbols per layer for CSI part 1 transmission, denoted as $Q'_{\text{CSI-part1}}$, is determined as follows:

$$Q'_{\text{CSI-1}} = \min \left\{ \left\lceil \frac{(O_{\text{CSI-1}} + L_{\text{CSI-1}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}} - 1} M_{\text{sc}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}} - 1} K_r} \right\rceil, \left\lceil \alpha \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}} - 1} M_{\text{sc}}^{\text{UCI}}(l) \right\rceil - Q'_{\text{ACK/CG-UCI}} \right\}$$

where

- $O_{\text{CSI-1}}$ is the number of bits for CSI part 1;

- if $O_{\text{CSI-1}} \geq 360$, $L_{\text{CSI-1}} = 11$; otherwise $L_{\text{CSI-1}}$ is the number of CRC bits for CSI part 1 determined according to Clause 6.3.1.2.1;
- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{CSI-part1}}$;
- $C_{\text{UL-SCH}}$ is the number of code blocks for UL-SCH of the PUSCH transmission;
- if the DCI format scheduling the PUSCH transmission includes a CBGTI field indicating that the UE shall not transmit the r -th code block, $K_r = 0$; otherwise, K_r is the r -th code block size for UL-SCH of the PUSCH transmission;
- $M_{\text{sc}}^{\text{PUSCH}}$ is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{\text{sc}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{ACK}}$ if HARQ-ACK is present for transmission on the same PUSCH with UL-SCH and without CG-UCI, where Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK transmitted on the PUSCH as defined in clause 6.3.2.4.1.1 if number of HARQ-ACK information bits is more than 2, and

$$Q'_{\text{ACK}} = \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} \bar{M}_{\text{sc,rvd}}^{\text{ACK}}(l)$$
 if the number of HARQ-ACK information bits is no more than 2 bits, where $\bar{M}_{\text{sc,rvd}}^{\text{ACK}}(l)$ is the number of reserved resource elements for potential HARQ-ACK transmission in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission, defined in Clause 6.2.7; or
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{ACK}}$ if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH, where Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK and CG-UCI transmitted on the PUSCH as defined in clause 6.3.2.4.1.5; or
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{CG-UCI}}$ if CG-UCI is present on the same PUSCH with UL-SCH and without HARQ-ACK, where $Q'_{\text{CG-UCI}}$ is the number of coded modulation symbols per layer for CG-UCI transmitted on the PUSCH as defined in clause 6.3.2.4.1.4;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$;
- α is configured by higher layer parameter *scaling*.

For CSI part 1 transmission on an actual repetition of a PUSCH with repetition Type B with UL-SCH, the number of coded modulation symbols per layer for CSI part 1 transmission, denoted as $Q'_{\text{CSI-part1}}$, is determined as follows:

$$Q'_{\text{CSI-1}} = \min \left\{ \left[\frac{(O_{\text{CSI-1}} + L_{\text{CSI-1}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}}-1} M_{\text{sc,nominal}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}}-1} K_r} \right], \left[\alpha \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}}-1} M_{\text{sc,nominal}}^{\text{UCI}}(l) \right] \right. \\ \left. - Q'_{\text{ACK/CG-UCI}}, \sum_{l=0}^{N_{\text{symb,actual}}^{\text{PUSCH}}-1} M_{\text{sc,actual}}^{\text{UCI}}(l) - Q'_{\text{ACK/CG-UCI}} \right\}$$

where

- $M_{sc,nominal}^{UCI}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,nominal}}^{\text{PUSCH}} - 1$, in the PUSCH transmission assuming a nominal repetition without segmentation, and $N_{\text{symb,nominal}}^{\text{PUSCH}}$ is the total number of OFDM symbols in a nominal repetition of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{sc,nominal}^{UCI}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{sc,nominal}^{UCI}(l) = M_{sc}^{\text{PUSCH}} - M_{sc,nominal}^{\text{PT-RS}}(l)$ where $M_{sc,nominal}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission assuming a nominal repetition without segmentation;
- $M_{sc,actual}^{UCI}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,actual}}^{\text{PUSCH}} - 1$, in the actual repetition of the PUSCH transmission, and $N_{\text{symb,actual}}^{\text{PUSCH}}$ is the total number of OFDM symbols in the actual repetition of the PUSCH transmission, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the actual repetition of the PUSCH transmission, $M_{sc,actual}^{UCI}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the actual repetition of the PUSCH transmission, $M_{sc,actual}^{UCI}(l) = M_{sc}^{\text{PUSCH}} - M_{sc,actual}^{\text{PT-RS}}(l)$ where $M_{sc,actual}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the actual repetition of the PUSCH transmission;
- and all the other notations in the formula are defined the same as for PUSCH not using repetition type B.

For CSI part 1 transmission on PUSCH without UL-SCH, the number of coded modulation symbols per layer for CSI part 1 transmission, denoted as $Q'_{\text{CSI-part1}}$, is determined as follows:

if there is CSI part 2 to be transmitted on the PUSCH,

$$Q'_{\text{CSI-1}} = \min \left\{ \left\lceil \frac{(O_{\text{CSI-1}} + L_{\text{CSI-1}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}}}{R \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{sc}^{UCI}(l) - Q'_{\text{ACK}} \right\}$$

else

$$Q'_{\text{CSI-1}} = \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{sc}^{UCI}(l) - Q'_{\text{ACK}}$$

end if

where

- $O_{\text{CSI-1}}$ is the number of bits for CSI part 1;
- if $O_{\text{CSI-1}} \geq 360$, $L_{\text{CSI-1}} = 11$; otherwise $L_{\text{CSI-1}}$ is the number of CRC bits for CSI part 1 determined according to Clause 6.3.1.2.1;
- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{CSI-part1}}$;
- M_{sc}^{PUSCH} is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{sc}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;

- Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK transmitted on the PUSCH if number of HARQ-ACK information bits is more than 2, and $Q'_{\text{ACK}} = \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} \bar{M}_{\text{sc,rvd}}^{\text{ACK}}(l)$ if the number of HARQ-ACK information bits is no more than 2 bits, where $\bar{M}_{\text{sc,rvd}}^{\text{ACK}}(l)$ is the number of reserved resource elements for potential HARQ-ACK transmission in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission, defined in Clause 6.2.7;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$;
- R is the code rate of the PUSCH, determined according to Clause 6.1.4.1 of [6, TS38.214];
- Q_m is the modulation order of the PUSCH.

The input bit sequence to rate matching is $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Rate matching is performed according to Clause 5.4.1 by setting $I_{\text{BL}} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{\text{UCI}} / C_{\text{UCI}} \rfloor$, where

- C_{UCI} is the number of code blocks for UCI determined according to Clause 5.2.1;
- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH;
- $E_{\text{UCI}} = N_L \cdot Q'_{\text{CSI-1}} \cdot Q_m$.

The output bit sequence after rate matching is denoted as $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.2.4.1.3 CSI part 2

For CSI part 2 transmission on PUSCH not using repetition type B with UL-SCH, the number of coded modulation symbols per layer for CSI part 2 transmission, denoted as $Q'_{\text{CSI-part2}}$, is determined as follows:

$$Q'_{\text{CSI-2}} = \min \left\{ \left\lceil \frac{(O_{\text{CSI-2}} + L_{\text{CSI-2}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}}-1} K_r} \right\rceil, \left[\alpha \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l) \right] - Q'_{\text{ACK/CG-UCI}} - Q'_{\text{CSI-1}} \right\}$$

where

- $O_{\text{CSI-2}}$ is the number of bits for CSI part 2;
- if $O_{\text{CSI-2}} \geq 360$, $L_{\text{CSI-2}} = 11$; otherwise $L_{\text{CSI-2}}$ is the number of CRC bits for CSI part 2 determined according to Clause 6.3.1.2.1;

- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{CSI-part2}}$;
- $C_{\text{UL-SCH}}$ is the number of code blocks for UL-SCH of the PUSCH transmission;
- if the DCI format scheduling the PUSCH transmission includes a CBGTI field indicating that the UE shall not transmit the r -th code block, $K_r=0$; otherwise, K_r is the r -th code block size for UL-SCH of the PUSCH transmission;
- $M_{\text{sc}}^{\text{PUSCH}}$ is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{\text{sc}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{ACK}}$ if HARQ-ACK is present for transmission on the same PUSCH with UL-SCH and without CG-UCI, where Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK transmitted on the PUSCH as defined in clause 6.3.2.4.1.1 if number of HARQ-ACK information bits is more than 2, and $Q'_{\text{ACK}} = 0$ if the number of HARQ-ACK information bits is 1 or 2 bits; or
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{ACK}}$ if both HARQ-ACK and CG-UCI are present on the same PUSCH with UL-SCH, where Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK and CG-UCI transmitted on the PUSCH as defined in clause 6.3.2.4.1.5; or
- $Q'_{\text{ACK/CG-UCI}} = Q'_{\text{CG-UCI}}$ if CG-UCI is present on the same PUSCH with UL-SCH and without HARQ-ACK, where $Q'_{\text{CG-UCI}}$ is the number of coded modulation symbols per layer for CG-UCI transmitted on the PUSCH as defined in clause 6.3.2.4.1.4;
- $Q'_{\text{CSI-1}}$ is the number of coded modulation symbols per layer for CSI part 1 transmitted on the PUSCH;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$.
- α is configured by higher layer parameter *scaling*.

For CSI part 2 transmission on an actual repetition of a PUSCH with repetition Type B with UL-SCH, the number of coded modulation symbols per layer for CSI part 2 transmission, denoted as $Q'_{\text{CSI-part2}}$, is determined as follows:

$$Q'_{\text{CSI-2}} = \min \left\{ \left[\frac{(O_{\text{CSI-2}} + L_{\text{CSI-2}}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}} - 1} M_{\text{sc,nominal}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{\text{UL-SCH}} - 1} K_r} \right], \left[\alpha \cdot \sum_{l=0}^{N_{\text{symb,nominal}}^{\text{PUSCH}} - 1} M_{\text{sc,nominal}}^{\text{UCI}}(l) \right] \right. \\ \left. - Q'_{\text{ACK/CG-UCI}} - Q'_{\text{CSI-1}}, \sum_{l=0}^{N_{\text{symb,actual}}^{\text{PUSCH}} - 1} M_{\text{sc,actual}}^{\text{UCI}}(l) - Q'_{\text{ACK/CG-UCI}} - Q'_{\text{CSI-1}} \right\}$$

where

- $M_{\text{sc,nominal}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{\text{symb,nominal}}^{\text{PUSCH}} - 1$, in the PUSCH transmission assuming a nominal repetition without segmentation, and $N_{\text{symb,nominal}}^{\text{PUSCH}}$ is the total number of OFDM symbols in a nominal repetition of the PUSCH, including all OFDM symbols used for DMRS;

- for any OFDM symbol that carries DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{sc,nominal}^{UCI}(l) = 0$;
- for any OFDM symbol that does not carry DMRS of the PUSCH assuming a nominal repetition without segmentation, $M_{sc,nominal}^{UCI}(l) = M_{sc}^{PUSCH} - M_{sc,nominal}^{PT-RS}(l)$ where $M_{sc,nominal}^{PT-RS}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission assuming a nominal repetition without segmentation;
- $M_{sc,actual}^{UCI}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{symb,actual}^{PUSCH} - 1$, in the actual repetition of the PUSCH transmission, and $N_{symb,actual}^{PUSCH}$ is the total number of OFDM symbols in the actual repetition of the PUSCH transmission, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the actual repetition of the PUSCH transmission, $M_{sc,actual}^{UCI}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the actual repetition of the PUSCH transmission, $M_{sc,actual}^{UCI}(l) = M_{sc}^{PUSCH} - M_{sc,actual}^{PT-RS}(l)$ where $M_{sc,actual}^{PT-RS}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the actual repetition of the PUSCH transmission;
- and all the other notations in the formula are defined the same as for PUSCH not using repetition type B.

For CSI part 2 transmission on PUSCH without UL-SCH, the number of coded modulation symbols per layer for CSI part 2 transmission, denoted as $Q'_{CSI-part2}$, is determined as follows:

$$Q'_{CSI-2} = \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) - Q'_{ACK} - Q'_{CSI-1}$$

where

- M_{sc}^{PUSCH} is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{sc}^{PT-RS}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- Q'_{ACK} is the number of coded modulation symbols per layer for HARQ-ACK transmitted on the PUSCH if number of HARQ-ACK information bits is more than 2, and $Q'_{ACK} = 0$ if the number of HARQ-ACK information bits is 1 or 2 bits;
- Q'_{CSI-1} is the number of coded modulation symbols per layer for CSI part 1 transmitted on the PUSCH;
- $M_{sc}^{UCI}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{symb,all}^{PUSCH} - 1$, in the PUSCH transmission and $N_{symb,all}^{PUSCH}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{sc}^{UCI}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{sc}^{UCI}(l) = M_{sc}^{PUSCH} - M_{sc}^{PT-RS}(l)$.

The input bit sequence to rate matching is $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Rate matching is performed according to Clause 5.4.1 by setting $I_{BL} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{UCI} / C_{UCI} \rfloor$, where

- C_{UCI} is the number of code blocks for UCI determined according to Clause 5.2.1;
- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH;
- $E_{UCI} = N_L \cdot Q_{CSI,2} \cdot Q_m$.

The output bit sequence after rate matching is denoted as $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.2.4.1.4 CG-UCI

For CG-UCI transmission on PUSCH with UL-SCH, the number of coded modulation symbols per layer for CG-UCI transmission, denoted as Q'_{CG-UCI} , is determined as follows:

$$Q'_{CG-UCI} = \min \left\{ \left\lfloor \frac{(O_{CG-UCI} + L_{CG-UCI}) \beta_{offset}^{PUSCH} \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l)}{\sum_{r=0}^{C_{UL-SCH}-1} K_r} \right\rfloor, \left\lfloor \alpha \cdot \sum_{l=l_0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) \right\rfloor \right\}$$

where

- O_{CG-UCI} is the number of CG-UCI bits;
- L_{CG-UCI} is the number of CRC bits for CG-UCI determined according to Clause 6.3.1.2.1;
- $\beta_{offset}^{PUSCH} = \beta_{offset}^{CG-UCI}$;
- C_{UL-SCH} is the number of code blocks for UL-SCH of the PUSCH transmission;
- K_r is the r -th code block size for UL-SCH of the PUSCH transmission;
- M_{sc}^{PUSCH} is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{sc}^{PT-RS}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $M_{sc}^{UCI}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l=0,1,2,\dots,N_{symb,all}^{PUSCH}-1$, in the PUSCH transmission and $N_{symb,all}^{PUSCH}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{sc}^{UCI}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{sc}^{UCI}(l) = M_{sc}^{PUSCH} - M_{sc}^{PT-RS}(l)$;
- α is configured by higher layer parameter *scaling*;
- l_0 is the symbol index of the first OFDM symbol that does not carry DMRS of the PUSCH, after the first DMRS symbol(s), in the PUSCH transmission.

The input bit sequence to rate matching is $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Rate matching is performed according to Clause 5.4.1 by setting $I_{BL} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{UCI} / C_{UCI} \rfloor$, where

- C_{UCI} is the number of code blocks for UCI determined according to Clause 5.2.1;
- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH;

$$- E_{UCI} = N_L \cdot Q'_{CG-UCI} \cdot Q_m.$$

The output bit sequence after rate matching is denoted as $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.2.4.1.5 HARQ-ACK and CG-UCI

For HARQ-ACK and CG-UCI transmission on PUSCH with UL-SCH, the number of coded modulation symbols per layer for HARQ-ACK and CG-UCI transmission, denoted as Q'_{ACK} , is determined as follows:

$$Q'_{ACK} = \min \left\{ \left\lceil \frac{(O_{ACK} + O_{CG-UCI} + L_{ACK}) \cdot \beta_{\text{offset}}^{\text{PUSCH}} \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}} - 1} M_{\text{sc}}^{\text{UCI}}(l)}{\sum_{r=0}^{C_{UL-SCH} - 1} K_r} \right\rceil, \left\lceil \alpha \cdot \sum_{l=l_0}^{N_{\text{symb,all}}^{\text{PUSCH}} - 1} M_{\text{sc}}^{\text{UCI}}(l) \right\rceil \right\}$$

where

- O_{ACK} is the number of HARQ-ACK bits;
- O_{CG-UCI} is the number of CG-UCI bits;
- if $O_{ACK} + O_{CG-UCI} > 360$, $L_{ACK} = 11$; otherwise L_{ACK} is the number of CRC bits for HARQ-ACK and CG-UCI determined according to Clause 6.3.1.2.1;
- $\beta_{\text{offset}}^{\text{PUSCH}} = \beta_{\text{offset}}^{\text{HARQ-ACK}}$;
- C_{UL-SCH} is the number of code blocks for UL-SCH of the PUSCH transmission;
- K_r is the r -th code block size for UL-SCH of the PUSCH transmission;
- $M_{\text{sc}}^{\text{PUSCH}}$ is the scheduled bandwidth of the PUSCH transmission, expressed as a number of subcarriers;
- $M_{\text{sc}}^{\text{PT-RS}}(l)$ is the number of subcarriers in OFDM symbol l that carries PTRS, in the PUSCH transmission;
- $M_{\text{sc}}^{\text{UCI}}(l)$ is the number of resource elements that can be used for transmission of UCI in OFDM symbol l , for $l=0,1,2,\dots, N_{\text{symb,all}}^{\text{PUSCH}} - 1$, in the PUSCH transmission and $N_{\text{symb,all}}^{\text{PUSCH}}$ is the total number of OFDM symbols of the PUSCH, including all OFDM symbols used for DMRS;
 - for any OFDM symbol that carries DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = 0$;
 - for any OFDM symbol that does not carry DMRS of the PUSCH, $M_{\text{sc}}^{\text{UCI}}(l) = M_{\text{sc}}^{\text{PUSCH}} - M_{\text{sc}}^{\text{PT-RS}}(l)$;
- α is configured by higher layer parameter *scaling*;
- l_0 is the symbol index of the first OFDM symbol that does not carry DMRS of the PUSCH, after the first DMRS symbol(s), in the PUSCH transmission.

The input bit sequence to rate matching is $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$ where r is the code block number, and N_r is the number of coded bits in code block number r .

Rate matching is performed according to Clause 5.4.1 by setting $I_{\text{BIL}} = 1$ and the rate matching output sequence length to $E_r = \lfloor E_{UCI} / C_{UCI} \rfloor$, where

- C_{UCI} is the number of code blocks for UCI determined according to Clause 5.2.1;
- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH;
- $E_{UCI} = N_L \cdot Q'_{ACK} \cdot Q_m$.

The output bit sequence after rate matching is denoted as $f_{r0}, f_{r1}, f_{r2}, \dots, f_{r(E_r-1)}$ where E_r is the length of rate matching output sequence in code block number r .

6.3.2.4.2 UCI encoded by channel coding of small block lengths

6.3.2.4.2.1 HARQ-ACK

For HARQ-ACK transmission on PUSCH, the number of coded modulation symbols per layer for HARQ-ACK transmission, denoted as Q'_{ACK} , is determined according to Clause 6.3.2.4.1.1, by setting the number of CRC bits $L = 0$.

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

Rate matching is performed according to Clause 5.4.3, by setting the rate matching output sequence length $E = N_L \cdot Q'_{ACK} \cdot Q_m$, where

- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.2.4.2.2 CSI part 1

For CSI part 1 transmission on PUSCH, the number of coded modulation symbols per layer for CSI part 1 transmission, denoted as $Q'_{CSI,1}$, is determined according to Clause 6.3.2.4.1.2, by setting the number of CRC bits $L = 0$.

Rate matching is performed according to Clause 5.4.3, by setting the rate matching output sequence length $E = N_L \cdot Q'_{CSI,1} \cdot Q_m$, where

- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.2.4.2.3 CSI part 2

For CSI part 2 transmission on PUSCH, the number of coded modulation symbols per layer for CSI part 2 transmission, denoted as $Q'_{CSI,2}$, is determined according to Clause 6.3.2.4.1.3, by setting the number of CRC bits $L = 0$.

Rate matching is performed according to Clause 5.4.3, by setting the rate matching output sequence length $E = N_L \cdot Q'_{CSI,2} \cdot Q_m$, where

- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.2.4.2.4 CG-UCI

For CG-UCI transmission on PUSCH, the number of coded modulation symbols per layer for CG-UCI transmission, denoted as Q'_{CG-UCI} , is determined according to Clause 6.3.2.4.1.4, by setting the number of CRC bits $L_{CG-UCI} = 0$.

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

Rate matching is performed according to Clause 5.4.3, by setting the rate matching output sequence length

$E = N_L \cdot Q'_{CG-UCI} \cdot Q_m$, where

- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.2.4.2.5 HARQ-ACK and CG-UCI

For HARQ-ACK and CG-UCI transmission on PUSCH, the number of coded modulation symbols per layer for HARQ-ACK and CG-UCI transmission, denoted as Q'_{ACK} , is determined according to Clause 6.3.2.4.1.5, by setting the number of CRC bits $L_{ACK} = 0$.

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

Rate matching is performed according to Clause 5.4.3, by setting the rate matching output sequence length $E = N_L \cdot Q'_{ACK} \cdot Q_m$, where

- N_L is the number of transmission layers of the PUSCH;
- Q_m is the modulation order of the PUSCH.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

6.3.2.5 Code block concatenation

Code block concatenation is performed according to Clause 6.3.1.5, except that the values of E_{UCI} and C_{UCI} given in Clause 6.3.2.4.1.

6.3.2.6 Multiplexing of coded UCI bits to PUSCH

The coded UCI bits are multiplexed onto PUSCH according to the procedures in Clause 6.2.7.

7 Downlink transport channels and control information

7.1 Broadcast channel

Data arrives to the coding unit in the form of a maximum of one transport block every 80ms. The following coding steps can be identified:

- Payload generation
- Scrambling
- Transport block CRC attachment
- Channel coding
- Rate matching

7.1.1 PBCH payload generation

Denote the bits in a transport block delivered to layer 1 by $\bar{a}_0, \bar{a}_1, \bar{a}_2, \bar{a}_3, \dots, \bar{a}_{\bar{A}-1}$, where \bar{A} is the payload size generated by higher layers. The lowest order information bit \bar{a}_0 is mapped to the most significant bit of the transport block as defined in Clause 6.1.1 of [8, TS 38.321].

Generate the following additional timing related PBCH payload bits $\bar{a}_{\bar{A}}, \bar{a}_{\bar{A}+1}, \bar{a}_{\bar{A}+2}, \bar{a}_{\bar{A}+3}, \dots, \bar{a}_{\bar{A}+7}$, where:

- $\bar{a}_{\bar{A}}, \bar{a}_{\bar{A}+1}, \bar{a}_{\bar{A}+2}, \bar{a}_{\bar{A}+3}$ are the 4th, 3rd, 2nd, and 1st LSB of SFN, respectively;
- $\bar{a}_{\bar{A}+4}$ is the half frame bit \bar{a}_{HRF} ;
- if $\bar{L}_{max} = 10$ as defined in Clause 4.1 of [5, TS38.213],
 $\bar{a}_{\bar{A}+5}$ is the MSB of k_{SSB} as defined in Clause 7.4.3.1 of [4, TS 38.211].
 $\bar{a}_{\bar{A}+6}$ is reserved.
 $\bar{a}_{\bar{A}+7}$ is the MSB of candidate SS/PBCH block index.
- else if $\bar{L}_{max} = 20$ as defined in Clause 4.1 of [5, TS38.213],
 $\bar{a}_{\bar{A}+5}$ is the MSB of k_{SSB} as defined in Clause 7.4.3.1 of [4, TS 38.211].
 $\bar{a}_{\bar{A}+6}, \bar{a}_{\bar{A}+7}$ are the 5th and 4th bits of the candidate SS/PBCH block index, respectively.
- else if $\bar{L}_{max} = 64$ as defined in Clause 4.1 of [5, TS38.213],
 $\bar{a}_{\bar{A}+5}, \bar{a}_{\bar{A}+6}, \bar{a}_{\bar{A}+7}$ are the 6th, 5th, and 4th bits of the candidate SS/PBCH block index, respectively.
- else
 $\bar{a}_{\bar{A}+5}$ is the MSB of k_{SSB} as defined in Clause 7.4.3.1 of [4, TS 38.211].
 $\bar{a}_{\bar{A}+6}, \bar{a}_{\bar{A}+7}$ are reserved.
- end if

Let $A = \bar{A} + 8$; $j_{\text{SFN}} = 0$; $j_{\text{HRF}} = 10$; $j_{\text{SSB}} = 11$; $j_{\text{other}} = 14$;

for $i = 0$ to $A-1$

if \bar{a}_i is an SFN bit

$$a_{G(j_{\text{SFN}})} = \bar{a}_i;$$

$$j_{\text{SFN}} = j_{\text{SFN}} + 1;$$

elseif \bar{a}_i is the half radio frame bit

$$a_{G(j_{\text{HRF}})} = \bar{a}_i$$

elseif $\bar{A} + 5 \leq i \leq \bar{A} + 7$

$$a_{G(j_{\text{SSB}})} = \bar{a}_i;$$

$$j_{\text{SSB}} = j_{\text{SSB}} + 1;$$

else

$$a_{G(j_{\text{Other}})} = \bar{a}_i;$$

$$j_{\text{Other}} = j_{\text{Other}} + 1;$$

end if

end for

where \bar{L}_{max} is the number of candidate SS/PBCH blocks in a half frame according to Clause 4.1 of [5, TS38.213], and the value of $G(j)$ is given by Table 7.1.1-1.

Table 7.1.1-1: Value of PBCH payload interleaver pattern $G(j)$

| j | $G(j)$ | j | $G(j)$ | j | $G(j)$ | j | $G(j)$ | j | $G(j)$ | j | $G(j)$ | j | $G(j)$ | j | $G(j)$ |
|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|
| 0 | 16 | 4 | 8 | 8 | 24 | 12 | 3 | 16 | 9 | 20 | 14 | 24 | 21 | 28 | 27 |
| 1 | 23 | 5 | 30 | 9 | 7 | 13 | 2 | 17 | 11 | 21 | 15 | 25 | 22 | 29 | 28 |
| 2 | 18 | 6 | 10 | 10 | 0 | 14 | 1 | 18 | 12 | 22 | 19 | 26 | 25 | 30 | 29 |
| 3 | 17 | 7 | 6 | 11 | 5 | 15 | 4 | 19 | 13 | 23 | 20 | 27 | 26 | 31 | 31 |

7.1.2 Scrambling

For PBCH transmission in a frame, the bit sequence $a_0, a_1, a_2, a_3, \dots, a_{A-1}$ is scrambled into a bit sequence $a'_0, a'_1, a'_2, a'_3, \dots, a'_{A-1}$, where $a'_i = (a_i + s_i) \bmod 2$ for $i=0,1,\dots,A-1$ and $s_0, s_1, s_2, s_3, \dots, s_{A-1}$ is generated according to the following:

$i = 0$;

$j = 0$;

while $i < A$

if a_i corresponds to any one of the bits belonging to the candidate SS/PBCH block index, the half frame index, and 2nd and 3rd least significant bits of the system frame number

$s_i = 0$;

else

$s_i = c(j + vM)$;

$j = j + 1$;

end if

$i = i + 1$;

end while

The scrambling sequence $c(i)$ is given by Clause 5.2.1of [4, TS38.211] and initialized with $c_{init} = N_{ID}^{cell}$ at the start of each SFN satisfying $\text{mod}(SFN, 8) = 0$; $M = A - 3$ for $\bar{L}_{max} = 4$ or $\bar{L}_{max} = 8$, $M = A - 4$ for $\bar{L}_{max} = 10$, $M = A - 5$ for $\bar{L}_{max} = 20$, and $M = A - 6$ for $\bar{L}_{max} = 64$, where \bar{L}_{max} is the number of candidate SS/PBCH blocks in a half frame according to Clause 4.1 of [5, TS38.213]; and v is determined according to Table 7.1.2-1 using the 3rd and 2nd LSB of the SFN in which the PBCH is transmitted.

Table 7.1.2-1: Value of v for PBCH scrambling

| (3 rd LSB of SFN, 2 nd LSB of SFN) | Value of v |
|--|--------------|
| (0, 0) | 0 |
| (0, 1) | 1 |
| (1, 0) | 2 |
| (1, 1) | 3 |

7.1.3 Transport block CRC attachment

Error detection is provided on BCH transport blocks through a Cyclic Redundancy Check (CRC).

The entire transport block is used to calculate the CRC parity bits. The input bit sequence is denoted by $a'_0, a'_1, a'_2, a'_3, \dots, a'_{A-1}$, and the parity bits by $p_0, p_1, p_2, p_3, \dots, p_{L-1}$, where A is the payload size and L is the number of parity bits.

The parity bits are computed and attached to the BCH transport block according to Clause 5.1 by setting L to 24 bits and using the generator polynomial $g_{\text{CRC24C}}(D)$, resulting in the sequence $b_0, b_1, b_2, b_3, \dots, b_{B-1}$, where $B = A + L$.

The bit sequence $b_0, b_1, b_2, b_3, \dots, b_{B-1}$ is the input bit sequence $c_0, c_1, c_2, c_3, \dots, c_{K-1}$ to the channel encoder, where $c_i = b_i$ for $i = 0, 1, \dots, B-1$ and $K = B$.

7.1.4 Channel coding

Information bits are delivered to the channel coding block. They are denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits, and they are encoded via Polar coding according to Clause 5.3.1, by setting $n_{\text{max}} = 9$, $I_{\text{IL}} = 1$, $n_{\text{PC}} = 0$, and $n_{\text{PC}}^{\text{wm}} = 0$.

After encoding the bits are denoted by $d_0, d_1, d_2, d_3, \dots, d_{N-1}$, where N is the number of coded bits.

7.1.5 Rate matching

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

The rate matching output sequence length $E = 864$.

Rate matching is performed according to Clause 5.4.1 by setting $I_{\text{BL}} = 0$.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

7.2 Downlink shared channel and paging channel

7.2.1 Transport block CRC attachment

Error detection is provided on each transport block through a Cyclic Redundancy Check (CRC).

The entire transport block is used to calculate the CRC parity bits. Denote the bits in a transport block delivered to layer 1 by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, and the parity bits by $p_0, p_1, p_2, p_3, \dots, p_{L-1}$, where A is the payload size and L is the number of parity bits. The lowest order information bit a_0 is mapped to the most significant bit of the transport block as defined in Clause 6.1.1 of [TS38.321].

The parity bits are computed and attached to the DL-SCH transport block according to Clause 5.1, by setting L to 24 bits and using the generator polynomial $g_{\text{CRC24A}}(D)$ if $A > 3824$; and by setting L to 16 bits and using the generator polynomial $g_{\text{CRC16}}(D)$ otherwise.

The bits after CRC attachment are denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$, where $B = A + L$.

7.2.2 LDPC base graph selection

For initial transmission of a transport block with coding rate R indicated by the MCS index according to Clause 5.1.3.1 in [6, TS 38.214] and subsequent re-transmission of the same transport block, each code block of the transport block is encoded with either LDPC base graph 1 or 2 according to the following:

- if $A \leq 292$, or if $A \leq 3824$ and $R \leq 0.67$, or if $R \leq 0.25$, LDPC base graph 2 is used;
- otherwise, LDPC base graph 1 is used,

where A is the payload size in Clause 7.2.1.

7.2.3 Code block segmentation and code block CRC attachment

The bits input to the code block segmentation are denoted by $b_0, b_1, b_2, b_3, \dots, b_{B-1}$ where B is the number of bits in the transport block (including CRC).

Code block segmentation and code block CRC attachment are performed according to Clause 5.2.2.

The bits after code block segmentation are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where r is the code block number and K_r is the number of bits for code block number r according to Clause 5.2.2.

7.2.4 Channel coding

Code blocks are delivered to the channel coding block. The bits in a code block are denoted by $c_{r0}, c_{r1}, c_{r2}, c_{r3}, \dots, c_{r(K_r-1)}$, where r is the code block number, and K_r is the number of bits in code block number r . The total number of code blocks is denoted by C and each code block is individually LDPC encoded according to Clause 5.3.2.

After encoding the bits are denoted by $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$, where the values of N_r is given in Clause 5.3.2.

7.2.5 Rate matching

Coded bits for each code block, denoted as $d_{r0}, d_{r1}, d_{r2}, d_{r3}, \dots, d_{r(N_r-1)}$, are delivered to the rate match block, where r is the code block number, and N_r is the number of encoded bits in code block number r . The total number of code blocks is denoted by C and each code block is individually rate matched according to Clause 5.4.2 by setting $I_{LBRM} = 1$.

After rate matching, the bits are denoted by $f_{r0}, f_{r1}, f_{r2}, f_{r3}, \dots, f_{r(E_r-1)}$, where E_r is the number of rate matched bits for code block number r .

7.2.6 Code block concatenation

The input bit sequence for the code block concatenation block are the sequences $f_{r0}, f_{r1}, f_{r2}, f_{r3}, \dots, f_{r(E_r-1)}$, for $r = 0, \dots, C-1$ and where E_r is the number of rate matched bits for the r -th code block.

Code block concatenation is performed according to Clause 5.5.

The bits after code block concatenation are denoted by $g_0, g_1, g_2, g_3, \dots, g_{G-1}$, where G is the total number of coded bits for transmission.

7.3 Downlink control information

A DCI transports downlink control information for one or more cells with one RNTI.

The following coding steps can be identified:

- Information element multiplexing
- CRC attachment
- Channel coding

- Rate matching

7.3.1 DCI formats

The DCI formats defined in table 7.3.1-1 are supported.

Table 7.3.1-1: DCI formats

| DCI format | Usage |
|------------|--|
| 0_0 | Scheduling of PUSCH in one cell |
| 0_1 | Scheduling of one or multiple PUSCH in one cell, or indicating downlink feedback information for configured grant PUSCH (CG-DFI) |
| 0_2 | Scheduling of PUSCH in one cell |
| 1_0 | Scheduling of PDSCH in one cell |
| 1_1 | Scheduling of PDSCH in one cell, and/or triggering one shot HARQ-ACK codebook feedback |
| 1_2 | Scheduling of PDSCH in one cell |
| 2_0 | Notifying a group of UEs of the slot format, available RB sets, COT duration and search space set group switching |
| 2_1 | Notifying a group of UEs of the PRB(s) and OFDM symbol(s) where UE may assume no transmission is intended for the UE |
| 2_2 | Transmission of TPC commands for PUCCH and PUSCH |
| 2_3 | Transmission of a group of TPC commands for SRS transmissions by one or more UEs |
| 2_4 | Notifying a group of UEs of the PRB(s) and OFDM symbol(s) where UE cancels the corresponding UL transmission from the UE |
| 2_5 | Notifying the availability of soft resources as defined in Clause 9.3.1 of [10, TS 38.473] |
| 2_6 | Notifying the power saving information outside DRX Active Time for one or more UEs |
| 3_0 | Scheduling of NR sidelink in one cell |
| 3_1 | Scheduling of LTE sidelink in one cell |

The fields defined in the DCI formats below are mapped to the information bits a_0 to a_{A-1} as follows.

Each field is mapped in the order in which it appears in the description, including the zero-padding bit(s), if any, with the first field mapped to the lowest order information bit a_0 and each successive field mapped to higher order information bits. The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to a_0 .

If the number of information bits in a DCI format is less than 12 bits, zeros shall be appended to the DCI format until the payload size equals 12.

The size of each DCI format is determined by the configuration of the corresponding active bandwidth part of the scheduled cell and shall be adjusted as described in clause 7.3.1.0 if necessary.

If a UE is configured with *pdsch-HARQ-ACK-CodebookList-r16*, *pdsch-HARQ-ACK-Codebook* is replaced by the relevant entry in *pdsch-HARQ-ACK-CodebookList-r16* in this clause.

7.3.1.0 DCI size alignment

If necessary, padding or truncation shall be applied to the DCI formats according to the following steps executed in the order below:

Step 0:

- Determine DCI format 0_0 monitored in a common search space according to clause 7.3.1.1.1 where $N_{RB}^{UL,BWP}$ is the size of the initial UL bandwidth part.
- Determine DCI format 1_0 monitored in a common search space according to clause 7.3.1.2.1 where $N_{RB}^{DL,BWP}$ is given by
 - the size of CORESET 0 if CORESET 0 is configured for the cell; and
 - the size of initial DL bandwidth part if CORESET 0 is not configured for the cell.
- If DCI format 0_0 is monitored in common search space and if the number of information bits in the DCI format 0_0 prior to padding is less than the payload size of the DCI format 1_0 monitored in common search space for scheduling the same serving cell, a number of zero padding bits are generated for the DCI format 0_0 until the payload size equals that of the DCI format 1_0.
- If DCI format 0_0 is monitored in common search space and if the number of information bits in the DCI format 0_0 prior to truncation is larger than the payload size of the DCI format 1_0 monitored in common search space for scheduling the same serving cell, the bitwidth of the frequency domain resource assignment field in the DCI format 0_0 is reduced by truncating the first few most significant bits such that the size of DCI format 0_0 equals the size of the DCI format 1_0.

Step 1:

- Determine DCI format 0_0 monitored in a UE-specific search space according to clause 7.3.1.1.1 where $N_{RB}^{UL,BWP}$ is the size of the active UL bandwidth part.
- Determine DCI format 1_0 monitored in a UE-specific search space according to clause 7.3.1.2.1 where $N_{RB}^{DL,BWP}$ is the size of the active DL bandwidth part.
- For a UE configured with *supplementaryUplink* in *ServingCellConfig* in a cell, if PUSCH is configured to be transmitted on both the SUL and the non-SUL of the cell and if the number of information bits in DCI format 0_0 in UE-specific search space for the SUL is not equal to the number of information bits in DCI format 0_0 in UE-specific search space for the non-SUL, a number of zero padding bits are generated for the smaller DCI format 0_0 until the payload size equals that of the larger DCI format 0_0.
- If DCI format 0_0 is monitored in UE-specific search space and if the number of information bits in the DCI format 0_0 prior to padding is less than the payload size of the DCI format 1_0 monitored in UE-specific search space for scheduling the same serving cell, a number of zero padding bits are generated for the DCI format 0_0 until the payload size equals that of the DCI format 1_0.
- If DCI format 1_0 is monitored in UE-specific search space and if the number of information bits in the DCI format 1_0 prior to padding is less than the payload size of the DCI format 0_0 monitored in UE-specific search space for scheduling the same serving cell, zeros shall be appended to the DCI format 1_0 until the payload size equals that of the DCI format 0_0

Step 2:

- Determine DCI format 0_1 monitored in a UE-specific search space according to clause 7.3.1.1.2.
- Determine DCI format 1_1 monitored in a UE-specific search space according to clause 7.3.1.2.2.
- For a UE configured with *supplementaryUplink* in *ServingCellConfig* in a cell, if PUSCH is configured to be transmitted on both the SUL and the non-SUL of the cell and if the number of information bits in format 0_1 for the SUL is not equal to the number of information bits in format 0_1 for the non-SUL, zeros shall be appended to smaller format 0_1 until the payload size equals that of the larger format 0_1.
- If the size of DCI format 0_1 monitored in a UE-specific search space equals that of a DCI format 0_0/1_0 monitored in another UE-specific search space, one bit of zero padding shall be appended to DCI format 0_1.
- If the size of DCI format 1_1 monitored in a UE-specific search space equals that of a DCI format 0_0/1_0 monitored in another UE-specific search space, one bit of zero padding shall be appended to DCI format 1_1.

Step 2A:

- Determine DCI format 0_2 monitored in a UE-specific search space according to clause 7.3.1.1.3.
- Determine DCI format 1_2 monitored in a UE-specific search space according to clause 7.3.1.2.3.
- For a UE configured with *supplementaryUplink* in *ServingCellConfig* in a cell, if PUSCH is configured to be transmitted on both the SUL and the non-SUL of the cell and if the number of information bits in format 0_2 for the SUL is not equal to the number of information bits in format 0_2 for the non-SUL, zeros shall be appended to smaller format 0_2 until the payload size equals that of the larger format 0_2.

Step 3:

- If both of the following conditions are fulfilled the size alignment procedure is complete
 - the total number of different DCI sizes configured to monitor is no more than 4 for the cell
 - the total number of different DCI sizes with C-RNTI configured to monitor is no more than 3 for the cell

Step 4:

- Otherwise

Step 4A:

- Remove the padding bit (if any) introduced in step 2 above.
- Determine DCI format 1_0 monitored in a UE-specific search space according to clause 7.3.1.2.1 where $N_{RB}^{DL,BWP}$ is given by
 - the size of CORESET 0 if CORESET 0 is configured for the cell; and
 - the size of initial DL bandwidth part if CORESET 0 is not configured for the cell.
- Determine DCI format 0_0 monitored in a UE-specific search space according to clause 7.3.1.1.1 where $N_{RB}^{UL,BWP}$ is the size of the initial UL bandwidth part.
- If the number of information bits in the DCI format 0_0 monitored in a UE-specific search space prior to padding is less than the payload size of the DCI format 1_0 monitored in UE-specific search space for scheduling the same serving cell, a number of zero padding bits are generated for the DCI format 0_0 monitored in a UE-specific search space until the payload size equals that of the DCI format 1_0 monitored in a UE-specific search space.
- If the number of information bits in the DCI format 0_0 monitored in a UE-specific search space prior to truncation is larger than the payload size of the DCI format 1_0 monitored in UE-specific search space for scheduling the same serving cell, the bitwidth of the frequency domain resource assignment field in the DCI format 0_0 is reduced by truncating the first few most significant bits such that the size of DCI format 0_0 monitored in a UE-specific search space equals the size of the DCI format 1_0 monitored in a UE-specific search space.

Step 4B:

- If the total number of different DCI sizes configured to monitor is more than 4 for the cell after applying the above steps, or if the total number of different DCI sizes with C-RNTI configured to monitor is more than 3 for the cell after applying the above steps
 - If the number of information bits in the DCI format 0_2 prior to padding is less than the payload size of the DCI format 1_2 for scheduling the same serving cell, a number of zero padding bits are generated for the DCI format 0_2 until the payload size equals that of the DCI format 1_2.
 - If the number of information bits in the DCI format 1_2 prior to padding is less than the payload size of the DCI format 0_2 for scheduling the same serving cell, zeros shall be appended to the DCI format 1_2 until the payload size equals that of the DCI format 0_2.

Step 4C:

- If the total number of different DCI sizes configured to monitor is more than 4 for the cell after applying the above steps, or if the total number of different DCI sizes with C-RNTI configured to monitor is more than 3 for the cell after applying the above steps
 - If the number of information bits in the DCI format 0_1 prior to padding is less than the payload size of the DCI format 1_1 for scheduling the same serving cell, a number of zero padding bits are generated for the DCI format 0_1 until the payload size equals that of the DCI format 1_1.
 - If the number of information bits in the DCI format 1_1 prior to padding is less than the payload size of the DCI format 0_1 for scheduling the same serving cell, zeros shall be appended to the DCI format 1_1 until the payload size equals that of the DCI format 0_1.

The UE is not expected to handle a configuration that, after applying the above steps, results in

- the total number of different DCI sizes configured to monitor is more than 4 for the cell; or
- the total number of different DCI sizes with C-RNTI configured to monitor is more than 3 for the cell; or
- the size of DCI format 0_0 in a UE-specific search space is equal to DCI format 0_1 in another UE-specific search space; or
- the size of DCI format 1_0 in a UE-specific search space is equal to DCI format 1_1 in another UE-specific search space; or
- the size of DCI format 0_0 in a UE-specific search space is equal to DCI format 0_2 in another UE-specific search space when at least one pair of the corresponding PDCCH candidates of DCI formats 0_0 and 0_2 are mapped to the same resource; or
- the size of DCI format 1_0 in a UE-specific search space is equal to DCI format 1_2 in another UE-specific search space when at least one pair of the corresponding PDCCH candidates of DCI formats 1_0 and 1_2 are mapped to the same resource; or
- the size of DCI format 0_1 in a UE-specific search space is equal to DCI format 0_2 in the same or another UE-specific search space when at least one pair of the corresponding PDCCH candidates of DCI formats 0_1 and 0_2 are mapped to the same resource; or
- the size of DCI format 1_1 in a UE-specific search space is equal to DCI format 1_2 in the same or another UE-specific search space when at least one pair of the corresponding PDCCH candidates of DCI formats 1_1 and 1_2 are mapped to the same resource.

7.3.1.0.1 DCI size alignment for DCI formats for scheduling of sidelink

If DCI format 3_0 or DCI format 3_1 is monitored on a cell, DCI size alignment for DCI format 3_0 and DCI format 3_1 is performed as described in this clause after performing the DCI size alignment described in Clause 7.3.1.0. The size(s) of the DCI formats configured to monitor for a cell in this clause refers to that after performing the DCI size alignment described in Clause 7.3.1.0.

If DCI format 3_0 or DCI format 3_1 is monitored on a cell and the total number of DCI sizes of the DCI formats configured to monitor for the cell and DCI format 3_0 or DCI format 3_1 is more than 4, zeros shall be appended to DCI format 3_0 if configured and DCI format 3_1 if configured, until the payload size of DCI format 3_0 or DCI format 3_1 equals that of the smallest DCI format configured to monitor for the cell that is larger than DCI format 3_0 or DCI format 3_1.

The UE is not expected to handle a configuration that results in:

- the total number of different DCI sizes configured to monitor for the cell and DCI format 3_0 or DCI format 3_1 is more than 4; and
- the payload size of DCI format 3_0 or DCI format 3_1 is larger than the payload size of all other DCI formats configured to monitor for the cell.

7.3.1.1 DCI formats for scheduling of PUSCH

7.3.1.1.1 Format 0_0

DCI format 0_0 is used for the scheduling of PUSCH in one cell.

The following information is transmitted by means of the DCI format 0_0 with CRC scrambled by C-RNTI or CS-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bit
 - The value of this bit field is always set to 0, indicating an UL DCI format
- Frequency domain resource assignment – number of bits determined by the following:
 - $\left\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \right\rceil$ bits if neither of the higher layer parameters *useInterlacePUCCH-PUSCH* in *BWP-UplinkCommon* and *useInterlacePUCCH-PUSCH* in *BWP-UplinkDedicated* is configured, where $N_{RB}^{UL,BWP}$ is defined in clause 7.3.1.0
 - For PUSCH hopping with resource allocation type 1:
 - N_{UL_hop} MSB bits are used to indicate the frequency offset according to Clause 6.3 of [6, TS 38.214], where $N_{UL_hop} = 1$ if the higher layer parameter *frequencyHoppingOffsetLists* contains two offset values and $N_{UL_hop} = 2$ if the higher layer parameter *frequencyHoppingOffsetLists* contains four offset values
 - $\left\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \right\rceil - N_{UL_hop}$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - For non-PUSCH hopping with resource allocation type 1:
 - $\left\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \right\rceil$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - If any of the higher layer parameters *useInterlacePUCCH-PUSCH* in *BWP-UplinkCommon* and *useInterlacePUCCH-PUSCH* in *BWP-UplinkDedicated* is configured
 - 5+Y bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 30 kHz.
 - 6+Y bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 15 kHz.

If the DCI format 0_0 is monitored in a UE-specific search space, the value of Y is determined by

$\left\lceil \log_2 \left(\frac{N_{RB-set,UL}^{BWP}(N_{RB-set,UL}^{BWP} + 1)}{2} \right) \right\rceil$ where $N_{RB-set,UL}^{BWP}$ is the number of RB sets contained in the active UL BWP as defined in clause 7 of [6, TS38.214]. If the DCI 0_0 is monitored in a common search space Y = 0.

- Time domain resource assignment – 4 bits as defined in Clause 6.1.2.1 of [6, TS 38.214]
- Frequency hopping flag – 1 bit according to Table 7.3.1.1.1-3, as defined in Clause 6.3 of [6, TS 38.214]
- Modulation and coding scheme – 5 bits as defined in Clause 6.1.4.1 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2
- HARQ process number – 4 bits
- TPC command for scheduled PUSCH – 2 bits as defined in Clause 7.1.1 of [5, TS 38.213]

- ChannelAccess-CPext – 2 bits indicating combinations of channel access type and CP extension as defined in Table 7.3.1.1.1-4, or Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; 0 bit otherwise.
- Padding bits, if required.
- UL/SUL indicator – 1 bit for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell as defined in Table 7.3.1.1.1-1 and the number of bits for DCI format 1_0 before padding is larger than the number of bits for DCI format 0_0 before padding; 0 bit otherwise. The UL/SUL indicator, if present, locates in the last bit position of DCI format 0_0, after the padding bit(s).
 - If the UL/SUL indicator is present in DCI format 0_0 and the higher layer parameter *pusch-Config* is not configured on both UL and SUL the UE ignores the UL/SUL indicator field in DCI format 0_0, and the corresponding PUSCH scheduled by the DCI format 0_0 is for the UL or SUL for which high layer parameter *pucch-Config* is configured;
 - If the UL/SUL indicator is not present in DCI format 0_0 and *pucch-Config* is configured, the corresponding PUSCH scheduled by the DCI format 0_0 is for the UL or SUL for which high layer parameter *pucch-Config* is configured.
 - If the UL/SUL indicator is not present in DCI format 0_0 and *pucch-Config* is not configured, the corresponding PUSCH scheduled by the DCI format 0_0 is for the uplink on which the latest PRACH is transmitted.

The following information is transmitted by means of the DCI format 0_0 with CRC scrambled by TC-RNTI:

- Identifier for DCI formats – 1 bit
 - The value of this bit field is always set to 0, indicating an UL DCI format
- Frequency domain resource assignment – number of bits determined by the following:
 - $\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \rceil$ bits if the higher layer parameter *useInterlacePUCCH-PUSCH* in *BWP-UplinkCommon* is not configured, where
 - $N_{RB}^{UL,BWP}$ is the size of the initial UL bandwidth part.
 - For PUSCH hopping with resource allocation type 1:
 - N_{UL_hop} MSB bits are used to indicate the frequency offset according to Table 8.3-1 in Clause 8.3 of [5, TS 38.213], where $N_{UL_hop} = 1$ if $N_{RB}^{UL,BWP} < 50$ and $N_{UL_hop} = 2$ otherwise
 - $\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \rceil - N_{UL_hop}$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - For non-PUSCH hopping with resource allocation type 1:
 - $\lceil \log_2(N_{RB}^{UL,BWP}(N_{RB}^{UL,BWP} + 1)/2) \rceil$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - If the higher layer parameter *useInterlacePUCCH-PUSCH* in *BWP-UplinkCommon* is configured
 - 5 bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 30 kHz
 - 6 bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 15 kHz
- Time domain resource assignment – 4 bits as defined in Clause 6.1.2.1 of [6, TS 38.214]
- Frequency hopping flag – 1 bit according to Table 7.3.1.1.1-3, as defined in Clause 6.3 of [6, TS 38.214]

- Modulation and coding scheme – 5 bits as defined in Clause 6.1.4.1 of [6, TS 38.214]
- New data indicator – 1 bit, reserved
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2
- HARQ process number – 4 bits, reserved
- TPC command for scheduled PUSCH – 2 bits as defined in Clause 7.1.1 of [5, TS 38.213]
- ChannelAccess-CPext – 2 bits indicating combinations of channel access type and CP extension as defined in Table 7.3.1.1.1-4, or Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; 0 bit otherwise
- Padding bits, if required.
- UL/SUL indicator – 1 bit if the cell has two ULs and the number of bits for DCI format 1_0 before padding is larger than the number of bits for DCI format 0_0 before padding; 0 bit otherwise. The UL/SUL indicator, if present, locates in the last bit position of DCI format 0_0, after the padding bit(s).
- If 1 bit, reserved, and the corresponding PUSCH is always on the same UL carrier as the previous transmission of the same TB

Table 7.3.1.1.1-1: UL/SUL indicator

| Value of UL/SUL indicator | Uplink |
|---------------------------|------------------------------|
| 0 | The non-supplementary uplink |
| 1 | The supplementary uplink |

Table 7.3.1.1.1-2: Redundancy version

| Value of the Redundancy version field | Value of rv_{id} to be applied |
|---------------------------------------|----------------------------------|
| 00 | 0 |
| 01 | 1 |
| 10 | 2 |
| 11 | 3 |

Table 7.3.1.1.1-3: Frequency hopping indication

| Bit field mapped to index | PUSCH frequency hopping |
|---------------------------|-------------------------|
| 0 | Disabled |
| 1 | Enabled |

Table 7.3.1.1.1-4: Channel access type & CP extension for DCI format 0_0 and DCI format 1_0

| Bit field mapped to index | Channel Access Type | The CP extension T_"ext" index defined in Clause 5.3.1 of [4, TS 38.211] |
|---------------------------|--|--|
| 0 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 |
| 1 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 |
| 2 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 |
| 3 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 |

Table 7.3.1.1.1-4A: Channel access type & CP extension if *ChannelAccessMode-r16* = "semistatic" is provided

| Bit field mapped to index | Channel Access Type | The CP extension T_"ext" index defined in Clause 5.3.1 of [4, TS 38.211] |
|---------------------------|--|--|
| 0 | No sensing as defined in Clause 4.3 in TS 37.213 | 0 |
| 1 | No sensing as defined in Clause 4.3 in TS 37.213 | 2 |
| 2 | 9us sensing within a 25us interval as defined in Clause 4.3 in TS 37.213 | 0 |
| 3 | - | - |

7.3.1.1.2 Format 0_1

DCI format 0_1 is used for the scheduling of one or multiple PUSCH in one cell, or indicating CG downlink feedback information (CG-DFI) to a UE.

The following information is transmitted by means of the DCI format 0_1 with CRC scrambled by C-RNTI or CS-RNTI or SP-CSI-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bit
 - The value of this bit field is always set to 0, indicating an UL DCI format
- Carrier indicator – 0 or 3 bits, as defined in Clause 10.1 of [5, TS38.213].
- DFI flag – 0 or 1 bit
 - 1 bit if the UE is configured to monitor DCI format 0_1 with CRC scrambled by CS-RNTI and for operation in a cell with shared spectrum channel access. For a DCI format 0_1 with CRC scrambled by CS-RNTI, the bit value of 0 indicates activating or releasing type 2 CG transmission and the bit value of 1 indicates CG-DFI. For a DCI format 0_1 with CRC scrambled by C-RNTI/SP-CSI-RNTI/MCS-C-RNTI and for operation in a cell with shared spectrum channel access, the bit is reserved.
 - 0 bit otherwise;

If DCI format 0_1 is used for indicating CG-DFI, all the remaining fields are set as follows:

- HARQ-ACK bitmap – 16 bits, where the order of the bitmap to HARQ process index mapping is such that HARQ process indices are mapped in ascending order from MSB to LSB of the bitmap. For each bit of the bitmap, value 1 indicates ACK, and value 0 indicates NACK.
- TPC command for scheduled PUSCH – 2 bits as defined in Clause 7.1.1 of [5, TS38.213]

- All the remaining bits in format 0_1 are set to zero.

Otherwise, all the remaining fields are set as follows:

- UL/SUL indicator – 0 bit for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell or UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell but only one carrier in the cell is configured for PUSCH transmission; otherwise, 1 bit as defined in Table 7.3.1.1.1-1.
- Bandwidth part indicator – 0, 1 or 2 bits as determined by the number of UL BWPs $n_{\text{BWP,RRC}}$ configured by higher layers, excluding the initial UL bandwidth part. The bitwidth for this field is determined as $\lceil \log_2(n_{\text{BWP}}) \rceil$ bits, where
 - $n_{\text{BWP}} = n_{\text{BWP,RRC}} + 1$ if $n_{\text{BWP,RRC}} \leq 3$, in which case the bandwidth part indicator is equivalent to the ascending order of the higher layer parameter *BWP-Id*;
 - otherwise $n_{\text{BWP}} = n_{\text{BWP,RRC}}$, in which case the bandwidth part indicator is defined in Table 7.3.1.1.2-1;

If a UE does not support active BWP change via DCI, the UE ignores this bit field.

- Frequency domain resource assignment – number of bits determined by the following, where $N_{\text{RB}}^{\text{UL,BWP}}$ is the size of the active UL bandwidth part:
 - If higher layer parameter *useInterlacePUCCH-PUSCH* in *BWP-UplinkDedicated* is not configured
 - N_{RBG} bits if only resource allocation type 0 is configured, where N_{RBG} is defined in Clause 6.1.2.2.1 of [6, TS 38.214],
 - $\lceil \log_2(N_{\text{RB}}^{\text{UL,BWP}}(N_{\text{RB}}^{\text{UL,BWP}} + 1)/2) \rceil$ bits if only resource allocation type 1 is configured, or $\max(\lceil \log_2(N_{\text{RB}}^{\text{UL,BWP}}(N_{\text{RB}}^{\text{UL,BWP}} + 1)/2) \rceil, N_{\text{RBG}}) + 1$ bits if *resourceAllocation* is configured as '*dynamicSwitch*'.
 - If *resourceAllocation* is configured as '*dynamicSwitch*', the MSB bit is used to indicate resource allocation type 0 or resource allocation type 1, where the bit value of 0 indicates resource allocation type 0 and the bit value of 1 indicates resource allocation type 1.
 - For resource allocation type 0, the N_{RBG} LSBs provide the resource allocation as defined in Clause 6.1.2.2.1 of [6, TS 38.214].
 - For resource allocation type 1, the $\lceil \log_2(N_{\text{RB}}^{\text{UL,BWP}}(N_{\text{RB}}^{\text{UL,BWP}} + 1)/2) \rceil$ LSBs provide the resource allocation as follows:
 - For PUSCH hopping with resource allocation type 1:
 - $N_{\text{UL,hop}}$ MSB bits are used to indicate the frequency offset according to Clause 6.3 of [6, TS 38.214], where $N_{\text{UL,hop}} = 1$ if the higher layer parameter *frequencyHoppingOffsetLists* contains two offset values and $N_{\text{UL,hop}} = 2$ if the higher layer parameter *frequencyHoppingOffsetLists* contains four offset values
 - $\lceil \log_2(N_{\text{RB}}^{\text{UL,BWP}}(N_{\text{RB}}^{\text{UL,BWP}} + 1)/2) \rceil - N_{\text{UL,hop}}$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - For non-PUSCH hopping with resource allocation type 1:
 - $\lceil \log_2(N_{\text{RB}}^{\text{UL,BWP}}(N_{\text{RB}}^{\text{UL,BWP}} + 1)/2) \rceil$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and if *resourceAllocation* is configured as '*dynamicSwitch*' for the indicated bandwidth part, the UE assumes resource allocation type 0 for the indicated bandwidth part if the bitwidth of the "Frequency domain resource

assignment" field of the active bandwidth part is smaller than the bitwidth of the "Frequency domain resource assignment" field of the indicated bandwidth part.

- If the higher layer parameter *useInterlacePUCCH-PUSCH* in *BWP-UplinkDedicated* is configured
 - 5 + Y bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 30 kHz. The 5 MSBs provide the interlace allocation and the Y LSBs provide the RB set allocation.
 - 6 + Y bits provide the frequency domain resource allocation according to Clause 6.1.2.2.3 of [6, TS 38.214] if the subcarrier spacing for the active UL bandwidth part is 15 kHz. The 6 MSBs provide the interlace allocation and the Y LSBs provide the RB set allocation.

The value of Y is determined by $\left\lceil \log_2 \left(\frac{N_{\text{RB-set,UL}}^{\text{BWP}} (N_{\text{RB-set,UL}}^{\text{BWP}} + 1)}{2} \right) \right\rceil$ where $N_{\text{RB-set,UL}}^{\text{BWP}}$ is the number of RB sets contained in the active UL BWP as defined in clause 7 of [6, TS38.214].

- Time domain resource assignment – 0, 1, 2, 3, 4, 5, or 6 bits
 - If the higher layer parameter *pusch-TimeDomainAllocationListDCI-0-1* is not configured and if the higher layer parameter *pusch-TimeDomainAllocationListForMultiPUSCH* is not configured and if the higher layer parameter *pusch-TimeDomainAllocationList* is configured, 0, 1, 2, 3, or 4 bits as defined in Clause 6.1.2.1 of [6, TS38.214]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *pusch-TimeDomainAllocationList*;
 - If the higher layer parameter *pusch-TimeDomainAllocationListDCI-0-1* is configured or if the higher layer parameter *pusch-TimeDomainAllocationListForMultiPUSCH* is configured, 0, 1, 2, 3, 4, 5 or 6 bits as defined in Clause 6.1.2.1 of [6, TS38.214]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *pusch-TimeDomainAllocationListDCI-0-1* or *pusch-TimeDomainAllocationListForMultiPUSCH*;
 - otherwise the bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the default table.
- Frequency hopping flag – 0 or 1 bit:
 - 0 bit if only resource allocation type 0 is configured, or if the higher layer parameter *frequencyHopping* is not configured and the higher layer parameter *pusch-RepTypeIndicatorDCI-0-1* is not configured to *pusch-RepTypeB*, or if the higher layer parameter *frequencyHoppingDCI-0-1* is not configured and *pusch-RepTypeIndicatorDCI-0-1* is configured to *pusch-RepTypeB*, or if only resource allocation type 2 is configured;
 - 1 bit according to Table 7.3.1.1.1-3 otherwise, only applicable to resource allocation type 1, as defined in Clause 6.3 of [6, TS 38.214].
- Modulation and coding scheme – 5 bits as defined in Clause 6.1.4.1 of [6, TS 38.214]
- New data indicator – 1 bit if the number of scheduled PUSCH indicated by the Time domain resource assignment field is 1; otherwise 2, 3, 4, 5, 6, 7 or 8 bits determined based on the maximum number of schedulable PUSCH among all entries in the higher layer parameter *pusch-TimeDomainAllocationListForMultiPUSCH*, where each bit corresponds to one scheduled PUSCH as defined in clause 6.1.4 in [6, TS 38.214].
- Redundancy version – number of bits determined by the following:
 - 2 bits as defined in Table 7.3.1.1.1-2 if the number of scheduled PUSCH indicated by the Time domain resource assignment field is 1;
 - otherwise 2, 3, 4, 5, 6, 7 or 8 bits determined by the maximum number of schedulable PUSCHs among all entries in the higher layer parameter *pusch-TimeDomainAllocationListForMultiPUSCH*, where each bit corresponds to one scheduled PUSCH as defined in clause 6.1.4 in [6, TS 38.214] and redundancy version is determined according to Table 7.3.1.1.2-34.
- HARQ process number – 4 bits

- 1st downlink assignment index – 1, 2 or 4 bits:
 - 1 bit for semi-static HARQ-ACK codebook;
 - 2 bits for dynamic HARQ-ACK codebook, or for enhanced dynamic HARQ-ACK codebook without *UL-TotalDAI-Included* configured;
 - 4 bits for enhanced dynamic HARQ-ACK codebook and with *UL-TotalDAI-Included = true*.

When two HARQ-ACK codebooks are configured for the same serving cell and if higher layer parameter *priorityIndicatorDCI-0-1* is configured, if the bit width of the 1st downlink assignment index in DCI format 0_1 for one HARQ-ACK codebook is not equal to that of the 1st downlink assignment index in DCI format 0_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller 1st downlink assignment index until the bit width of the 1st downlink assignment index in DCI format 0_1 for the two HARQ-ACK codebooks are the same.

- 2nd downlink assignment index – 0, 2 or 4 bits:
 - 2 bits for dynamic HARQ-ACK codebook with two HARQ-ACK sub-codebooks, or for enhanced dynamic HARQ-ACK codebook with two HARQ-ACK sub-codebooks and without *UL-TotalDAI-Included* configured;
 - 4 bits for enhanced dynamic HARQ-ACK codebook with two HARQ-ACK sub-codebooks and with *UL-TotalDAI-Included = true*;
 - 0 bit otherwise.

When two HARQ-ACK codebooks are configured for the same serving cell and if higher layer parameter *priorityIndicatorDCI-0-1* is configured, if the bit width of the 2nd downlink assignment index in DCI format 0_1 for one HARQ-ACK codebook is not equal to that of the 2nd downlink assignment index in DCI format 0_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller 2nd downlink assignment index until the bit width of the 2nd downlink assignment index in DCI format 0_1 for the two HARQ-ACK codebooks are the same.

- TPC command for scheduled PUSCH – 2 bits as defined in Clause 7.1.1 of [5, TS38.213]

- SRS resource indicator – $\left\lceil \log_2 \left(\sum_{k=1}^{\min\{L_{max}, N_{SRS}\}} \binom{N_{SRS}}{k} \right) \right\rceil$ or $\lceil \log_2(N_{SRS}) \rceil$ bits, where N_{SRS} is the number of

configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, and associated with the higher layer parameter *usage* of value '*codeBook*' or '*nonCodeBook*',

- $\left\lceil \log_2 \left(\sum_{k=1}^{\min\{L_{max}, N_{SRS}\}} \binom{N_{SRS}}{k} \right) \right\rceil$ bits according to Tables 7.3.1.1.2-28/29/30/31 if the higher layer parameter

txConfig = nonCodebook, where N_{SRS} is the number of configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, and associated with the higher layer parameter *usage* of value '*nonCodeBook*' and

- if UE supports operation with *maxMIMO-Layers* and the higher layer parameter *maxMIMO-Layers of PUSCH-ServingCellConfig* of the serving cell is configured, L_{max} is given by that parameter
- otherwise, L_{max} is given by the maximum number of layers for PUSCH supported by the UE for the serving cell for non-codebook based operation.
- $\lceil \log_2(N_{SRS}) \rceil$ bits according to Tables 7.3.1.1.2-32, 7.3.1.1.2-32A and 7.3.1.1.2-32B if the higher layer parameter *txConfig = codebook*, where N_{SRS} is the number of configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, and associated with the higher layer parameter *usage* of value '*codeBook*'.
- Precoding information and number of layers – number of bits determined by the following:
 - 0 bits if the higher layer parameter *txConfig = nonCodeBook*;

- 0 bits for 1 antenna port and if the higher layer parameter $txConfig = codebook$;
- 4, 5, or 6 bits according to Table 7.3.1.1.2-2 for 4 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission$ is not configured or configured to $fullpowerMode2$ or configured to $fullpower$, transform precoder is disabled, and according to the values of higher layer parameters $maxRank$, and $codebookSubset$;
- 4 or 5 bits according to Table 7.3.1.1.2-2A for 4 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission = fullpowerMode1$, $maxRank=2$, transform precoder is disabled, and according to the values of higher layer parameter $codebookSubset$;
- 4 or 6 bits according to Table 7.3.1.1.2-2B for 4 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission = fullpowerMode1$, $maxRank=3$ or 4 , transform precoder is disabled, and according to the values of higher layer parameter $codebookSubset$;
- 2, 4, or 5 bits according to Table 7.3.1.1.2-3 for 4 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission$ is not configured or configured to $fullpowerMode2$ or configured to $fullpower$, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameters $maxRank$, and $codebookSubset$;
- 3 or 4 bits according to Table 7.3.1.1.2-3A for 4 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission = fullpowerMode1$, $maxRank=1$, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameter $codebookSubset$;
- 2 or 4 bits according to Table 7.3.1.1.2-4 for 2 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission$ is not configured or configured to $fullpowerMode2$ or configured to $fullpower$, transform precoder is disabled, and according to the values of higher layer parameters $maxRank$ and $codebookSubset$;
- 2 bits according to Table 7.3.1.1.2-4A for 2 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission = fullpowerMode1$, transform precoder is disabled, $maxRank=2$, and $codebookSubset=nonCoherent$;
- 1 or 3 bits according to Table 7.3.1.1.2-5 for 2 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission$ is not configured or configured to $fullpowerMode2$ or configured to $fullpower$, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameters $maxRank$ and $codebookSubset$;
- 2 bits according to Table 7.3.1.1.2-5A for 2 antenna ports, if $txConfig = codebook$, $ul-FullPowerTransmission = fullpowerMode1$, $maxRank=1$, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameter $codebookSubset$;

For the higher layer parameter $txConfig=codebook$, if $ul-FullPowerTransmission$ is configured to $fullpowerMode2$, $maxRank$ is configured to be larger than 2, and at least one SRS resource with 4 antenna ports is configured in an SRS resource set with usage set to 'codebook' and an SRS resource with 2 antenna ports is indicated via SRI in the same SRS resource set, then Table 7.3.1.1.2-4 is used.

For the higher layer parameter $txConfig = codebook$, if different SRS resources with different number of antenna ports are configured, the bitwidth is determined according to the maximum number of ports in an SRS resource among the configured SRS resources in an SRS resource set with usage set to 'codebook'. If the number of ports for a configured SRS resource in the set is less than the maximum number of ports in an SRS resource among the configured SRS resources, a number of most significant bits with value set to '0' are inserted to the field.

- Antenna ports – number of bits determined by the following
 - 2 bits as defined by Tables 7.3.1.1.2-6, if transform precoder is enabled, $dmrs-Type=1$, and $maxLength=1$, except that $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured and $\pi/2$ BPSK modulation is used;
 - 2 bits as defined by Tables 7.3.1.1.2-6A, if transform precoder is enabled and $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured, $\pi/2$ BPSK modulation is used, $dmrs-Type=1$, and $maxLength=1$, where n_{SCID} is the scrambling identity for antenna ports defined in [Clause 6.4.1.1.1.2, TS38.211];

- 4 bits as defined by Tables 7.3.1.1.2-7, if transform precoder is enabled, $dmrs\text{-}Type=1$, and $maxLength=2$, except that $dmrs\text{-}UplinkTransformPrecoding$ and $tp\text{-}pi2BPSK$ are both configured and $\pi/2$ BPSK modulation is used;
- 4 bits as defined by Tables 7.3.1.1.2-7A, if transform precoder is enabled and $dmrs\text{-}UplinkTransformPrecoding$ and $tp\text{-}pi2BPSK$ are both configured, $\pi/2$ BPSK modulation is used, $dmrs\text{-}Type=1$, and $maxLength=2$, where n_{SCID} is the scrambling identity for antenna ports defined in [Clause 6.4.1.1.1.2, TS38.211];
- 3 bits as defined by Tables 7.3.1.1.2-8/9/10/11, if transform precoder is disabled, $dmrs\text{-}Type=1$, and $maxLength=1$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
- 4 bits as defined by Tables 7.3.1.1.2-12/13/14/15, if transform precoder is disabled, $dmrs\text{-}Type=1$, and $maxLength=2$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
- 4 bits as defined by Tables 7.3.1.1.2-16/17/18/19, if transform precoder is disabled, $dmrs\text{-}Type=2$, and $maxLength=1$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
- 5 bits as defined by Tables 7.3.1.1.2-20/21/22/23, if transform precoder is disabled, $dmrs\text{-}Type=2$, and $maxLength=2$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$.

where the number of CDM groups without data of values 1, 2, and 3 in Tables 7.3.1.1.2-6 to 7.3.1.1.2-23 refers to CDM groups $\{0\}$, $\{0,1\}$, and $\{0, 1,2\}$ respectively.

If a UE is configured with both $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeA$ and $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeB$, the bitwidth of this field equals $\max\{x_A, x_B\}$, where x_A is the "Antenna ports" bitwidth derived according to $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeA$ and x_B is the "Antenna ports" bitwidth derived according to $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeB$. A number of $|x_A - x_B|$ zeros are padded in the MSB of this field, if the mapping type of the PUSCH corresponds to the smaller value of x_A and x_B .

- SRS request – 2 bits as defined by Table 7.3.1.1.2-24 for UEs not configured with $supplementaryUplink$ in $ServingCellConfig$ in the cell; 3 bits for UEs configured with $supplementaryUplink$ in $ServingCellConfig$ in the cell where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second and third bits are defined by Table 7.3.1.1.2-24. This bit field may also indicate the associated CSI-RS according to Clause 6.1.1.2 of [6, TS 38.214].
- CSI request – 0, 1, 2, 3, 4, 5, or 6 bits determined by higher layer parameter $reportTriggerSize$.
- CBG transmission information (CBGTI) – 0 bit if higher layer parameter $codeBlockGroupTransmission$ for PUSCH is not configured or if the number of scheduled PUSCH indicated by the Time domain resource assignment field is larger than 1; otherwise, 2, 4, 6, or 8 bits determined by higher layer parameter $maxCodeBlockGroupsPerTransportBlock$ for PUSCH.
- PTRS-DMRS association – number of bits determined as follows
 - 0 bit if $PTRS\text{-}UplinkConfig$ is not configured in either $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeA$ or $dmrs\text{-}UplinkForPUSCH\text{-}MappingTypeB$ and transform precoder is disabled, or if transform precoder is enabled, or if $maxRank=1$;
 - 2 bits otherwise, where Table 7.3.1.1.2-25 and 7.3.1.1.2-26 are used to indicate the association between PTRS port(s) and DMRS port(s) when one PT-RS port and two PT-RS ports are configured by $maxNrofPorts$ in $PTRS\text{-}UplinkConfig$ respectively, and the DMRS ports are indicated by the Antenna ports field.

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and the "PTRS-DMRS association" field is present for the indicated bandwidth part but not present for the active bandwidth part, the UE assumes the "PTRS-DMRS association" field is not present for the indicated bandwidth part.

- beta_offset indicator – 0 if the higher layer parameter *betaOffsets* = *semiStatic*; otherwise 2 bits as defined by Table 9.3-3 in [5, TS 38.213].

When two HARQ-ACK codebooks are configured for the same serving cell and if higher layer parameter *priorityIndicatorDCI-0-1* is configured, if the bit width of the beta_offset indicator in DCI format 0_1 for one HARQ-ACK codebook is not equal to that of the beta_offset indicator in DCI format 0_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller beta_offset indicator until the bit width of the beta_offset indicator in DCI format 0_1 for the two HARQ-ACK codebooks are the same.

- DMRS sequence initialization – 0 bit if transform precoder is enabled; 1 bit if transform precoder is disabled.
- UL-SCH indicator – 0 or 1 bit as follows
 - 0 bit if the number of scheduled PUSCH indicated by the Time domain resource assignment field is larger than 1;
 - 1 bit otherwise. A value of "1" indicates UL-SCH shall be transmitted on the PUSCH and a value of "0" indicates UL-SCH shall not be transmitted on the PUSCH. Except for DCI format 0_1 with CRC scrambled by SP-CSI-RNTI, a UE is not expected to receive a DCI format 0_1 with UL-SCH indicator of "0" and CSI request of all zero(s).
- ChannelAccess-CPext-CAPC – 0, 1, 2, 3, 4, 5 or 6 bits. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *ul-AccessConfigListDCI-0-1* or in Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; otherwise 0 bit. One or more entries from Table 7.3.1.1.2-35 are configured by the higher layer parameter *ul-AccessConfigListDCI-0-1*.
- Open-loop power control parameter set indication – 0 or 1 or 2 bits.
 - 0 bit if the higher layer parameter *p0-PUSCH-SetList* is not configured;
 - 1 or 2 bits otherwise,
 - 1 bit if SRS resource indicator is present in the DCI format 0_1;
 - 1 or 2 bits as determined by higher layer parameter *olpc-ParameterSetDCI-0-1* if SRS resource indicator is not present in the DCI format 0_1.
- Priority indicator – 0 bit if higher layer parameter *priorityIndicatorDCI-0-1* is not configured; otherwise 1 bit as defined in Clause 9 in [5, TS 38.213].
- Invalid symbol pattern indicator – 0 bit if higher layer parameter *invalidSymbolPatternIndicatorDCI-0-1* is not configured; otherwise 1 bit as defined in Clause 6.1.2.1 in [6, TS 38.214].
- Minimum applicable scheduling offset indicator – 0 or 1 bit
 - 0 bit if higher layer parameter *minimumSchedulingOffsetK2* is not configured;
 - 1 bit if higher layer parameter *minimumSchedulingOffsetK2* is configured. The 1 bit indication is used to determine the minimum applicable K2 for the active UL BWP and the minimum applicable K0 value for the active DL BWP, if configured respectively, according to Table 7.3.1.1.2-33. If the minimum applicable K0 is indicated, the minimum applicable value of the aperiodic CSI-RS triggering offset for an active DL BWP shall be the same as the minimum applicable K0 value.
- SCell dormancy indication – 0 bit if higher layer parameter *dormancyGroupWithinActiveTime* is not configured; otherwise 1, 2, 3, 4 or 5 bits bitmap determined according to higher layer parameter *dormancyGroupWithinActiveTime*, where each bit corresponds to one of the SCell group(s) configured by higher layers parameter *dormancyGroupWithinActiveTime*, with MSB to LSB of the bitmap corresponding to the first to last configured SCell group. The field is only present when this format is carried by PDCCH on the primary cell within DRX Active Time and the UE is configured with at least two DL BWPs for an SCell.

- Sidelink assignment index – 0, 1 or 2 bits:
 - 1 bit if the UE is configured with *pdsch-HARQ-ACK-Codebook* = *semi-static* and, in addition, the UE is configured with a SL configured grant type 1 or to monitor DCI format 3_0 with CRC scrambled by SL-RNTI or SL-CS-RNTI;
 - 2 bits if the UE is configured with *pdsch-HARQ-ACK-Codebook* = *dynamic* and, in addition, the UE is configured with a SL configured grant type 1 or to monitor DCI format 3_0 with CRC scrambled by SL-RNTI or SL-CS-RNTI;
 - 0 bit otherwise.

A UE does not expect that the bit width of a field in DCI format 0_1 with CRC scrambled by CS-RNTI is larger than corresponding bit width of same field in DCI format 0_1 with CRC scrambled by C-RNTI for the same serving cell. If the bit width of a field in the DCI format 0_1 with CRC scrambled by CS-RNTI is not equal to that of the corresponding field in the DCI format 0_1 with CRC scrambled by C-RNTI for the same serving cell, a number of most significant bits with value set to '0' are inserted to the field in DCI format 0_1 with CRC scrambled by CS-RNTI until the bit width equals that of the corresponding field in the DCI format 0_1 with CRC scrambled by C-RNTI for the same serving cell.

If the number of information bits in DCI format 0_1 scheduling a single PUSCH prior to padding is not equal to the number of information bits in DCI format 0_1 scheduling multiple PUSCHs for the same serving cell, zeros shall be appended to the DCI format 0_1 with smaller size until the payload size is the same for scheduling a single PUSCH and multiple PUSCHs.

Table 7.3.1.1.2-1: Bandwidth part indicator

| Value of BWP indicator field 2 bits | Bandwidth part |
|--|--------------------------------|
| 00 | Configured BWP with BWP-Id = 1 |
| 01 | Configured BWP with BWP-Id = 2 |
| 10 | Configured BWP with BWP-Id = 3 |
| 11 | Configured BWP with BWP-Id = 4 |

Table 7.3.1.1.2-2: Precoding information and number of layers, for 4 antenna ports, if transform precoder is disabled, *maxRank* = 2 or 3 or 4, and *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*

| Bit field mapped to index | <i>codebookSubset = fullyAndPartialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = partialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| ... | ... | ... | ... | ... | ... |
| 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 |
| 4 | 2 layers: TPMI=0 | 4 | 2 layers: TPMI=0 | 4 | 2 layers: TPMI=0 |
| ... | ... | ... | ... | ... | ... |
| 9 | 2 layers: TPMI=5 | 9 | 2 layers: TPMI=5 | 9 | 2 layers: TPMI=5 |
| 10 | 3 layers: TPMI=0 | 10 | 3 layers: TPMI=0 | 10 | 3 layers: TPMI=0 |
| 11 | 4 layers: TPMI=0 | 11 | 4 layers: TPMI=0 | 11 | 4 layers: TPMI=0 |
| 12 | 1 layer: TPMI=4 | 12 | 1 layer: TPMI=4 | 12-15 | reserved |
| ... | ... | ... | ... | ... | ... |
| 19 | 1 layer: TPMI=11 | 19 | 1 layer: TPMI=11 | | |
| 20 | 2 layers: TPMI=6 | 20 | 2 layers: TPMI=6 | | |
| ... | ... | ... | ... | | |
| 27 | 2 layers: TPMI=13 | 27 | 2 layers: TPMI=13 | | |
| 28 | 3 layers: TPMI=1 | 28 | 3 layers: TPMI=1 | | |
| 29 | 3 layers: TPMI=2 | 29 | 3 layers: TPMI=2 | | |
| 30 | 4 layers: TPMI=1 | 30 | 4 layers: TPMI=1 | | |
| 31 | 4 layers: TPMI=2 | 31 | 4 layers: TPMI=2 | | |
| 32 | 1 layer: TPMI=12 | | | | |
| ... | ... | | | | |
| 47 | 1 layers: TPMI=27 | | | | |
| 48 | 2 layers: TPMI=14 | | | | |
| ... | ... | | | | |
| 55 | 2 layers: TPMI=21 | | | | |
| 56 | 3 layers: TPMI=3 | | | | |
| ... | ... | | | | |
| 59 | 3 layers: TPMI=6 | | | | |
| 60 | 4 layers: TPMI=3 | | | | |
| 61 | 4 layers: TPMI=4 | | | | |
| 62-63 | reserved | | | | |

Table 7.3.1.1.2-2A: Precoding information and number of layers for 4 antenna ports, if transform precoder is disabled, *maxRank* = 2, and *ul-FullPowerTransmission* = *fullpowerMode1*

| Bit field mapped to index | <i>codebookSubset = partialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| ... | ... | ... | ... |
| 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 |
| 4 | 2 layers: TPMI=0 | 4 | 2 layers: TPMI=0 |
| ... | ... | ... | ... |
| 9 | 2 layers: TPMI=5 | 9 | 2 layers: TPMI=5 |
| 10 | 1 layer: TPMI=13 | 10 | 1 layer: TPMI=13 |
| 11 | 2 layer: TPMI=6 | 11 | 2 layer: TPMI=6 |
| 12 | 1 layer: TPMI=4 | 12-15 | Reserved |
| ... | ... | | |
| 20 | 1 layer: TPMI=12 | | |
| 21 | 1 layer: TPMI=14 | | |
| 22 | 1 layer: TPMI=15 | | |
| 23 | 2 layers: TPMI=7 | | |
| ... | ... | | |
| 29 | 2 layers: TPMI=13 | | |
| 30-31 | Reserved | | |

Table 7.3.1.1.2-2B: Precoding information and number of layers for 4 antenna ports, if transform precoder is disabled, $maxRank = 3$ or 4, and $ul-FullPowerTransmission = fullpowerMode1$

| Bit field mapped to index | <i>codebookSubset = partialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| ... | ... | ... | ... |
| 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 |
| 4 | 2 layers: TPMI=0 | 4 | 2 layers: TPMI=0 |
| ... | ... | ... | ... |
| 9 | 2 layers: TPMI=5 | 9 | 2 layers: TPMI=5 |
| 10 | 3 layers: TPMI=0 | 10 | 3 layers: TPMI=0 |
| 11 | 4 layers: TPMI=0 | 11 | 4 layers: TPMI=0 |
| 12 | 1 layer: TPMI=13 | 12 | 1 layer: TPMI=13 |
| 13 | 2 layer: TPMI=6 | 13 | 2 layer: TPMI=6 |
| 14 | 3 layer: TPMI=1 | 14 | 3 layer: TPMI=1 |
| 15 | 1 layer: TPMI=4 | 15 | Reserved |
| ... | ... | | |
| 23 | 1 layer: TPMI=12 | | |
| 24 | 1 layer: TPMI=14 | | |
| 25 | 1 layer: TPMI=15 | | |
| 26 | 2 layers: TPMI=7 | | |
| ... | ... | | |
| 32 | 2 layers: TPMI=13 | | |
| 33 | 3 layers: TPMI=2 | | |
| 34 | 4 layers: TPMI=1 | | |
| 35 | 4 layers: TPMI=2 | | |
| 36-63 | Reserved | | |

Table 7.3.1.1.2-3: Precoding information and number of layers for 4 antenna ports, if transform precoder is enabled and $ul-FullPowerTransmission$ is either not configured or configured to $fullpowerMode2$, or if transform precoder is disabled, $maxRank = 1$, and $ul-FullPowerTransmission$ is not configured or configured to $fullpowerMode2$ or configured to $fullpower$

| Bit field mapped to index | <i>codebookSubset = fullyAndPartialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = partialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| ... | ... | ... | ... | ... | ... |
| 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 |
| 4 | 1 layer: TPMI=4 | 4 | 1 layer: TPMI=4 | | |
| ... | ... | ... | ... | | |
| 11 | 1 layer: TPMI=11 | 11 | 1 layer: TPMI=11 | | |
| 12 | 1 layers: TPMI=12 | 12-15 | reserved | | |
| ... | ... | | | | |
| 27 | 1 layers: TPMI=27 | | | | |
| 28-31 | reserved | | | | |

Table 7.3.1.1.2-3A: Precoding information and number of layers for 4 antenna ports, if transform precoder is enabled and *ul-FullPowerTransmission* = *fullpowerMode1*, or if transform precoder is disabled, *maxRank* = 1, and *ul-FullPowerTransmission* = *fullpowerMode1*

| Bit field mapped to index | <i>codebookSubset= partialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset= nonCoherent</i> |
|---------------------------|--|---------------------------|------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| ... | ... | ... | ... |
| 3 | 1 layer: TPMI=3 | 3 | 1 layer: TPMI=3 |
| 4 | 1 layer: TPMI=13 | 4 | 1 layer: TPMI=13 |
| 5 | 1 layer: TPMI=4 | 5-7 | Reserved |
| ... | ... | | |
| 13 | 1 layer: TPMI=12 | | |
| 14 | 1 layer: TPMI=14 | | |
| 15 | 1 layer: TPMI=15 | | |

Table 7.3.1.1.2-4: Precoding information and number of layers, for 2 antenna ports, if transform precoder is disabled, *maxRank* = 2, and *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*

| Bit field mapped to index | <i>codebookSubset = fullyAndPartialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| 2 | 2 layers: TPMI=0 | 2 | 2 layers: TPMI=0 |
| 3 | 1 layer: TPMI=2 | 3 | reserved |
| 4 | 1 layer: TPMI=3 | | |
| 5 | 1 layer: TPMI=4 | | |
| 6 | 1 layer: TPMI=5 | | |
| 7 | 2 layers: TPMI=1 | | |
| 8 | 2 layers: TPMI=2 | | |
| 9-15 | reserved | | |

Table 7.3.1.1.2-4A: Precoding information and number of layers, for 2 antenna ports, if transform precoder is disabled, *maxRank* = 2, and *ul-FullPowerTransmission* = *fullpowerMode1*

| Bit field mapped to index | <i>codebookSubset= nonCoherent</i> |
|---------------------------|------------------------------------|
| 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 |
| 2 | 2 layers: TPMI=0 |
| 3 | 1 layer: TPMI=2 |

Table 7.3.1.1.2-5: Precoding information and number of layers, for 2 antenna ports, if transform precoder is enabled and *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*, or if transform precoder is disabled, *maxRank* = 1, and *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*

| Bit field mapped to index | <i>codebookSubset = fullyAndPartialAndNonCoherent</i> | Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|---|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 | 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 | 1 | 1 layer: TPMI=1 |
| 2 | 1 layer: TPMI=2 | | |
| 3 | 1 layer: TPMI=3 | | |
| 4 | 1 layer: TPMI=4 | | |
| 5 | 1 layer: TPMI=5 | | |
| 6-7 | reserved | | |

Table 7.3.1.1.2-5A: Precoding information and number of layers, for 2 antenna ports, if transform precoder is enabled and *ul-FullPowerTransmission = fullpowerMode1*, or if transform precoder is disabled, *maxRank* = 1, and *ul-FullPowerTransmission = fullpowerMode1*

| Bit field mapped to index | <i>codebookSubset = nonCoherent</i> |
|---------------------------|-------------------------------------|
| 0 | 1 layer: TPMI=0 |
| 1 | 1 layer: TPMI=1 |
| 2 | 1 layer: TPMI=2 |
| 3 | Reserved |

Table 7.3.1.1.2-6: Antenna port(s), transform precoder is enabled, *dmrs-Type=1*, *maxLength=1*, except that *dmrs-UplinkTransformPrecoding* and *tp-pi2BPSK* are both configured and $\pi/2$ -BPSK modulation is used

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 2 | 0 |
| 1 | 2 | 1 |
| 2 | 2 | 2 |
| 3 | 2 | 3 |

Table 7.3.1.1.2-6A: Antenna port(s), transform precoder is enabled, *dmrs-UplinkTransformPrecoding* and *tp-pi2BPSK* are both configured, $\pi/2$ -BPSK modulation is used, *dmrs-Type=1*, *maxLength=1*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|-------------------|
| 0 | 2 | 0, $n_{SCID} = 0$ |
| 1 | 2 | 0, $n_{SCID} = 1$ |
| 2 | 2 | 2, $n_{SCID} = 0$ |
| 3 | 2 | 2, $n_{SCID} = 1$ |

Table 7.3.1.1.2-7: Antenna port(s), transform precoder is enabled, *dmrs-Type=1*, *maxLength=2*, except that *dmrs-UplinkTransformPrecoding* and *tp-pi2BPSK* are both configured and $\pi/2$ -BPSK modulation is used

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 2 | 0 | 1 |
| 1 | 2 | 1 | 1 |
| 2 | 2 | 2 | 1 |
| 3 | 2 | 3 | 1 |
| 4 | 2 | 0 | 2 |
| 5 | 2 | 1 | 2 |
| 6 | 2 | 2 | 2 |
| 7 | 2 | 3 | 2 |
| 8 | 2 | 4 | 2 |
| 9 | 2 | 5 | 2 |
| 10 | 2 | 6 | 2 |
| 11 | 2 | 7 | 2 |
| 12-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-7A: Antenna port(s), transform precoder is enabled, *dmrs-UplinkTransformPrecoding* and *tp-pi2BPSK* are both configured, $\pi/2$ -BPSK modulation is used, *dmrs-Type=1*, *maxLength=2*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|------------------------|------------------------------|
| 0 | 2 | 0, $n_{\text{SCID}}=0$ | 1 |
| 1 | 2 | 0, $n_{\text{SCID}}=1$ | 1 |
| 2 | 2 | 2, $n_{\text{SCID}}=0$ | 1 |
| 3 | 2 | 2, $n_{\text{SCID}}=1$ | 1 |
| 4 | 2 | 0, $n_{\text{SCID}}=0$ | 2 |
| 5 | 2 | 0, $n_{\text{SCID}}=1$ | 2 |
| 6 | 2 | 2, $n_{\text{SCID}}=0$ | 2 |
| 7 | 2 | 2, $n_{\text{SCID}}=1$ | 2 |
| 8 | 2 | 4, $n_{\text{SCID}}=0$ | 2 |
| 9 | 2 | 4, $n_{\text{SCID}}=1$ | 2 |
| 10 | 2 | 6, $n_{\text{SCID}}=0$ | 2 |
| 11 | 2 | 6, $n_{\text{SCID}}=1$ | 2 |
| 12-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-8: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=1*, rank = 1

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 1 | 0 |
| 1 | 1 | 1 |
| 2 | 2 | 0 |
| 3 | 2 | 1 |
| 4 | 2 | 2 |
| 5 | 2 | 3 |
| 6-7 | Reserved | Reserved |

Table 7.3.1.1.2-9: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=1*, rank = 2

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 1 | 0,1 |
| 1 | 2 | 0,1 |
| 2 | 2 | 2,3 |
| 3 | 2 | 0,2 |
| 4-7 | Reserved | Reserved |

Table 7.3.1.1.2-10: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=1*, rank = 3

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 2 | 0-2 |
| 1-7 | Reserved | Reserved |

Table 7.3.1.1.2-11: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=1*, rank = 4

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 2 | 0-3 |
| 1-7 | Reserved | Reserved |

Table 7.3.1.1.2-12: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=2*, rank = 1

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 1 | 0 | 1 |
| 1 | 1 | 1 | 1 |
| 2 | 2 | 0 | 1 |
| 3 | 2 | 1 | 1 |
| 4 | 2 | 2 | 1 |
| 5 | 2 | 3 | 1 |
| 6 | 2 | 0 | 2 |
| 7 | 2 | 1 | 2 |
| 8 | 2 | 2 | 2 |
| 9 | 2 | 3 | 2 |
| 10 | 2 | 4 | 2 |
| 11 | 2 | 5 | 2 |
| 12 | 2 | 6 | 2 |
| 13 | 2 | 7 | 2 |
| 14-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-13: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=2*, rank = 2

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 1 | 0,1 | 1 |
| 1 | 2 | 0,1 | 1 |
| 2 | 2 | 2,3 | 1 |
| 3 | 2 | 0,2 | 1 |
| 4 | 2 | 0,1 | 2 |
| 5 | 2 | 2,3 | 2 |
| 6 | 2 | 4,5 | 2 |
| 7 | 2 | 6,7 | 2 |
| 8 | 2 | 0,4 | 2 |
| 9 | 2 | 2,6 | 2 |
| 10-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-14: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=2*, rank = 3

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 2 | 0-2 | 1 |
| 1 | 2 | 0,1,4 | 2 |
| 2 | 2 | 2,3,6 | 2 |
| 3-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-15: Antenna port(s), transform precoder is disabled, *dmrs-Type=1*, *maxLength=2*, rank = 4

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 2 | 0-3 | 1 |
| 1 | 2 | 0,1,4,5 | 2 |
| 2 | 2 | 2,3,6,7 | 2 |
| 3 | 2 | 0,2,4,6 | 2 |
| 4-15 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-16: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=1*, rank=1

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 1 | 0 |
| 1 | 1 | 1 |
| 2 | 2 | 0 |
| 3 | 2 | 1 |
| 4 | 2 | 2 |
| 5 | 2 | 3 |
| 6 | 3 | 0 |
| 7 | 3 | 1 |
| 8 | 3 | 2 |
| 9 | 3 | 3 |
| 10 | 3 | 4 |
| 11 | 3 | 5 |
| 12-15 | Reserved | Reserved |

Table 7.3.1.1.2-17: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=1*, rank=2

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 1 | 0,1 |
| 1 | 2 | 0,1 |
| 2 | 2 | 2,3 |
| 3 | 3 | 0,1 |
| 4 | 3 | 2,3 |
| 5 | 3 | 4,5 |
| 6 | 2 | 0,2 |
| 7-15 | Reserved | Reserved |

Table 7.3.1.1.2-18: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=1*, rank =3

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 2 | 0-2 |
| 1 | 3 | 0-2 |
| 2 | 3 | 3-5 |
| 3-15 | Reserved | Reserved |

Table 7.3.1.1.2-19: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=1*, rank =4

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
|-------|--|--------------|
| 0 | 2 | 0-3 |
| 1 | 3 | 0-3 |
| 2-15 | Reserved | Reserved |

Table 7.3.1.1.2-20: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=2*, *rank=1*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 1 | 0 | 1 |
| 1 | 1 | 1 | 1 |
| 2 | 2 | 0 | 1 |
| 3 | 2 | 1 | 1 |
| 4 | 2 | 2 | 1 |
| 5 | 2 | 3 | 1 |
| 6 | 3 | 0 | 1 |
| 7 | 3 | 1 | 1 |
| 8 | 3 | 2 | 1 |
| 9 | 3 | 3 | 1 |
| 10 | 3 | 4 | 1 |
| 11 | 3 | 5 | 1 |
| 12 | 3 | 0 | 2 |
| 13 | 3 | 1 | 2 |
| 14 | 3 | 2 | 2 |
| 15 | 3 | 3 | 2 |
| 16 | 3 | 4 | 2 |
| 17 | 3 | 5 | 2 |
| 18 | 3 | 6 | 2 |
| 19 | 3 | 7 | 2 |
| 20 | 3 | 8 | 2 |
| 21 | 3 | 9 | 2 |
| 22 | 3 | 10 | 2 |
| 23 | 3 | 11 | 2 |
| 24 | 1 | 0 | 2 |
| 25 | 1 | 1 | 2 |
| 26 | 1 | 6 | 2 |
| 27 | 1 | 7 | 2 |
| 28-31 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-21: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=2*, *rank=2*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 1 | 0,1 | 1 |
| 1 | 2 | 0,1 | 1 |
| 2 | 2 | 2,3 | 1 |
| 3 | 3 | 0,1 | 1 |
| 4 | 3 | 2,3 | 1 |
| 5 | 3 | 4,5 | 1 |
| 6 | 2 | 0,2 | 1 |
| 7 | 3 | 0,1 | 2 |
| 8 | 3 | 2,3 | 2 |
| 9 | 3 | 4,5 | 2 |
| 10 | 3 | 6,7 | 2 |
| 11 | 3 | 8,9 | 2 |
| 12 | 3 | 10,11 | 2 |
| 13 | 1 | 0,1 | 2 |
| 14 | 1 | 6,7 | 2 |
| 15 | 2 | 0,1 | 2 |
| 16 | 2 | 2,3 | 2 |
| 17 | 2 | 6,7 | 2 |
| 18 | 2 | 8,9 | 2 |
| 19-31 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-22: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=2*, *rank=3*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 2 | 0-2 | 1 |
| 1 | 3 | 0-2 | 1 |
| 2 | 3 | 3-5 | 1 |
| 3 | 3 | 0,1,6 | 2 |
| 4 | 3 | 2,3,8 | 2 |
| 5 | 3 | 4,5,10 | 2 |
| 6-31 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-23: Antenna port(s), transform precoder is disabled, *dmrs-Type=2*, *maxLength=2*, *rank=4*

| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
|-------|--|--------------|------------------------------|
| 0 | 2 | 0-3 | 1 |
| 1 | 3 | 0-3 | 1 |
| 2 | 3 | 0,1,6,7 | 2 |
| 3 | 3 | 2,3,8,9 | 2 |
| 4 | 3 | 4,5,10,11 | 2 |
| 5-31 | Reserved | Reserved | Reserved |

Table 7.3.1.1.2-24: SRS request

| Value of SRS request field | Triggered aperiodic SRS resource set(s) for DCI format 0_1, 0_2, 1_1, 1_2, and 2_3 configured with higher layer parameter <i>srs-TPC-PDCCH-Group</i> set to 'typeB' | Triggered aperiodic SRS resource set(s) for DCI format 2_3 configured with higher layer parameter <i>srs-TPC-PDCCH-Group</i> set to 'typeA' |
|----------------------------|---|---|
| 00 | No aperiodic SRS resource set triggered | No aperiodic SRS resource set triggered |
| 01 | SRS resource set(s) configured by <i>SRS-ResourceSet</i> with higher layer parameter <i>aperiodicSRS-ResourceTrigger</i> set to 1 or an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 1 SRS resource set(s) configured by <i>SRS-PosResourceSet</i> with an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 1 when triggered by DCI formats 0_1, 0_2, 1_1, and 1_2 | SRS resource set(s) configured with higher layer parameter <i>usage</i> in <i>SRS-ResourceSet</i> set to 'antennaSwitching' and <i>resourceType</i> in <i>SRS-ResourceSet</i> set to 'aperiodic' for a 1 st set of serving cells configured by higher layers |
| 10 | SRS resource set(s) configured by <i>SRS-ResourceSet</i> with higher layer parameter <i>aperiodicSRS-ResourceTrigger</i> set to 2 or an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 2 SRS resource set(s) configured by <i>SRS-PosResourceSet</i> with an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 2 when triggered by DCI formats 0_1, 0_2, 1_1, and 1_2 | SRS resource set(s) configured with higher layer parameter <i>usage</i> in <i>SRS-ResourceSet</i> set to 'antennaSwitching' and <i>resourceType</i> in <i>SRS-ResourceSet</i> set to 'aperiodic' for a 2 nd set of serving cells configured by higher layers |
| 11 | SRS resource set(s) configured by <i>SRS-ResourceSet</i> with higher layer parameter <i>aperiodicSRS-ResourceTrigger</i> set to 3 or an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 3 SRS resource set(s) configured by <i>SRS-PosResourceSet</i> with an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 3 when triggered by DCI formats 0_1, 0_2, 1_1, and 1_2 | SRS resource set(s) configured with higher layer parameter <i>usage</i> in <i>SRS-ResourceSet</i> set to 'antennaSwitching' and <i>resourceType</i> in <i>SRS-ResourceSet</i> set to 'aperiodic' for a 3 rd set of serving cells configured by higher layers |

Table 7.3.1.1.2-25: PTRS-DMRS association for UL PTRS port 0

| Value | DMRS port |
|-------|-------------------------------------|
| 0 | 1 st scheduled DMRS port |
| 1 | 2 nd scheduled DMRS port |
| 2 | 3 rd scheduled DMRS port |
| 3 | 4 th scheduled DMRS port |

Table 7.3.1.1.2-26: PTRS-DMRS association for UL PTRS ports 0 and 1

| Value of MSB | DMRS port | | Value of LSB | DMRS port |
|--------------|--|--|--------------|--|
| 0 | 1 st DMRS port which shares PTRS port 0 | | 0 | 1 st DMRS port which shares PTRS port 1 |
| 1 | 2 nd DMRS port which shares PTRS port 0 | | 1 | 2 nd DMRS port which shares PTRS port 1 |

Table 7.3.1.1.2-27: void

Table 7.3.1.1.2-28: SRI indication for non-codebook based PUSCH transmission, $L_{\max} = 1$

| Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 2$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 3$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 4$ |
|---------------------------|------------------------------|---------------------------|------------------------------|---------------------------|------------------------------|
| 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 |
| | | 2 | 2 | 2 | 2 |
| | | 3 | reserved | 3 | 3 |

Table 7.3.1.1.2-29: SRI indication for non-codebook based PUSCH transmission, $L_{\max} = 2$

| Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 2$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 3$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 4$ |
|---------------------------|------------------------------|---------------------------|------------------------------|---------------------------|------------------------------|
| 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 |
| 2 | 0,1 | 2 | 2 | 2 | 2 |
| 3 | reserved | 3 | 0,1 | 3 | 3 |
| | | 4 | 0,2 | 4 | 0,1 |
| | | 5 | 1,2 | 5 | 0,2 |
| | | 6-7 | reserved | 6 | 0,3 |
| | | | | 7 | 1,2 |
| | | | | 8 | 1,3 |
| | | | | 9 | 2,3 |
| | | | | 10-15 | reserved |

Table 7.3.1.1.2-30: SRI indication for non-codebook based PUSCH transmission, $L_{\max} = 3$

| Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 2$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 3$ | Bit field mapped to index | SRI(s), $N_{\text{SRS}} = 4$ |
|---------------------------|------------------------------|---------------------------|------------------------------|---------------------------|------------------------------|
| 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 |
| 2 | 0,1 | 2 | 2 | 2 | 2 |
| 3 | reserved | 3 | 0,1 | 3 | 3 |
| | | 4 | 0,2 | 4 | 0,1 |
| | | 5 | 1,2 | 5 | 0,2 |
| | | 6 | 0,1,2 | 6 | 0,3 |
| | | 7 | reserved | 7 | 1,2 |
| | | | | 8 | 1,3 |
| | | | | 9 | 2,3 |
| | | | | 10 | 0,1,2 |
| | | | | 11 | 0,1,3 |
| | | | | 12 | 0,2,3 |
| | | | | 13 | 1,2,3 |
| | | | | 14-15 | reserved |

Table 7.3.1.1.2-31: SRI indication for non-codebook based PUSCH transmission, $L_{\max} = 4$

| Bit field mapped to index | SRI(s), $N_{SRS} = 2$ | Bit field mapped to index | SRI(s), $N_{SRS} = 3$ | Bit field mapped to index | SRI(s), $N_{SRS} = 4$ |
|---------------------------|-----------------------|---------------------------|-----------------------|---------------------------|-----------------------|
| 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 |
| 2 | 0,1 | 2 | 2 | 2 | 2 |
| 3 | reserved | 3 | 0,1 | 3 | 3 |
| | | 4 | 0,2 | 4 | 0,1 |
| | | 5 | 1,2 | 5 | 0,2 |
| | | 6 | 0,1,2 | 6 | 0,3 |
| | | 7 | reserved | 7 | 1,2 |
| | | | | 8 | 1,3 |
| | | | | 9 | 2,3 |
| | | | | 10 | 0,1,2 |
| | | | | 11 | 0,1,3 |
| | | | | 12 | 0,2,3 |
| | | | | 13 | 1,2,3 |
| | | | | 14 | 0,1,2,3 |
| | | | | 15 | reserved |

Table 7.3.1.1.2-32: SRI indication for codebook based PUSCH transmission, if *ul-FullPowerTransmission* is not configured, or *ul-FullPowerTransmission* = *fullpowerMode1*, or *ul-FullPowerTransmission* = *fullpowerMode2*, or *ul-FullPowerTransmission* = *fullpower* and $N_{SRS} = 2$

| Bit field mapped to index | SRI(s), $N_{SRS} = 2$ |
|---------------------------|-----------------------|
| 0 | 0 |
| 1 | 1 |

Table 7.3.1.1.2-32A: SRI indication for codebook based PUSCH transmission, if *ul-FullPowerTransmission* = *fullpowerMode2* and $N_{SRS} = 3$

| Bit field mapped to index | SRI(s), $N_{SRS} = 3$ |
|---------------------------|-----------------------|
| 0 | 0 |
| 1 | 1 |
| 2 | 2 |
| 3 | Reserved |

Table 7.3.1.1.2-32B: SRI indication for codebook based PUSCH transmission, if *ul-FullPowerTransmission* = *fullpowerMode2* and $N_{SRS} = 4$

| Bit field mapped to index | SRI(s), $N_{SRS} = 4$ |
|---------------------------|-----------------------|
| 0 | 0 |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |

Table 7.3.1.1.2-33: Joint indication of minimum applicable scheduling offset K0/K2

| Bit field mapped to index | Minimum applicable K0 for the active DL BWP, if <i>minimumSchedulingOffsetK0</i> is configured for the DL BWP | Minimum applicable K2 for the active UL BWP, if <i>minimumSchedulingOffsetK2</i> is configured for the UL BWP |
|---------------------------|--|--|
| 0 | The first value configured by <i>minimumSchedulingOffsetK0</i> for the active DL BWP | The first value configured by <i>minimumSchedulingOffsetK2</i> for the active UL BWP |
| 1 | The second value configured by <i>minimumSchedulingOffsetK0</i> for the active DL BWP if the second value is configured; 0 otherwise | The second value configured by <i>minimumSchedulingOffsetK2</i> for the active UL BWP if the second value is configured; 0 otherwise |

Table 7.3.1.1.2-34: Redundancy version

| Value of the Redundancy version field | Value of rv_{id} to be applied |
|---------------------------------------|----------------------------------|
| 0 | 0 |
| 1 | 2 |

Table 7.3.1.1.2-35: Allowed entries for DCI format 0_1, configured by higher layer parameter *ul-AccessConfigListDCI-0-1*

| Entry index | Channel Access Type | The CP extension T_"ext" index defined in Clause 5.3.1 of [4, 38.211] | CAPC |
|-------------|--|---|------|
| 0 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 1 |
| 1 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 2 |
| 2 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 3 |
| 3 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 4 |
| 4 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 1 |
| 5 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 2 |
| 6 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 3 |
| 7 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 4 |
| 8 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 1 |
| 9 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 2 |
| 10 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 3 |
| 11 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 | 4 |
| 12 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 1 |
| 13 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 2 |
| 14 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 3 |
| 15 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 | 4 |
| 16 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 0 | 1 |
| 17 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 0 | 2 |
| 18 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 0 | 3 |
| 19 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 0 | 4 |
| 20 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 | 1 |
| 21 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 | 2 |
| 22 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 | 3 |
| 23 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 | 4 |
| 24 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 | 1 |
| 25 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 | 2 |
| 26 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 | 3 |
| 27 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 | 4 |
| 28 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 | 1 |
| 29 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 | 2 |
| 30 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 | 3 |
| 31 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 | 4 |
| 32 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 1 | 1 |
| 33 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 1 | 2 |
| 34 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 1 | 3 |
| 35 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 1 | 4 |
| 36 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 2 | 1 |
| 37 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 2 | 2 |
| 38 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 2 | 3 |
| 39 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 2 | 4 |
| 40 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 3 | 1 |
| 41 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 3 | 2 |
| 42 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 3 | 3 |
| 43 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 3 | 4 |

7.3.1.1.3 Format 0_2

DCI format 0_2 is used for the scheduling of PUSCH in one cell.

The following information is transmitted by means of the DCI format 0_2 with CRC scrambled by C-RNTI or CS-RNTI or SP-CSI-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bit
 - The value of this bit field is always set to 0, indicating an UL DCI format
- Carrier indicator – 0, 1, 2 or 3 bits determined by higher layer parameter *carrierIndicatorSizeDCI-0-2*, as defined in Clause 10.1 of [5, TS38.213].
- UL/SUL indicator – 0 bit for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell or UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell but only one carrier in the cell is configured for PUSCH transmission; otherwise, 1 bit as defined in Table 7.3.1.1.1-1.

- Bandwidth part indicator – 0, 1 or 2 bits as determined by the number of UL BWPs $n_{BWP,RRC}$ configured by higher layers, excluding the initial UL bandwidth part. The bitwidth for this field is determined as $\lceil \log_2(n_{BWP}) \rceil$ bits, where
 - $n_{BWP} = n_{BWP,RRC} + 1$ if $n_{BWP,RRC} \leq 3$, in which case the bandwidth part indicator is equivalent to the ascending order of the higher layer parameter *BWP-Id*;
 - otherwise $n_{BWP} = n_{BWP,RRC}$, in which case the bandwidth part indicator is defined in Table 7.3.1.1.2-1;

If a UE does not support active BWP change via DCI, the UE ignores this bit field.

- Frequency domain resource assignment – number of bits determined by the following:
 - N_{RBG} bits if only resource allocation type 0 is configured, where N_{RBG} is defined in Clause 6.1.2.2.1 of [6, TS 38.214]
 - $\lceil \log_2(N_{RBG,K1}(N_{RBG,K1} + 1)/2) \rceil$ bits if only resource allocation type 1 is configured, or $\max(\lceil \log_2(N_{RBG,K1}(N_{RBG,K1} + 1)/2) \rceil, N_{RBG}) + 1$ bits if *resourceAllocationDCI-0-2-r16* is configured as 'dynamicSwitch', where $N_{RBG,K1} = \lceil (N_{RB}^{UL,BWP} + (N_{UL,BWP}^{start} \bmod K1)) / K1 \rceil$, $N_{RB}^{UL,BWP}$ is the size of the active UL bandwidth part, $N_{UL,BWP}^{start}$ is defined as in clause 4.4.4.4 of [4, TS 38.211] and $K1$ is given by higher layer parameter *resourceAllocationType1GranularityDCI-0-2*. If the higher layer parameter *resourceAllocationType1GranularityDCI-0-2* is not configured, $K1$ is equal to 1.
 - If *resourceAllocationDCI-0-2-r16* is configured as 'dynamicSwitch', the MSB bit is used to indicate resource allocation type 0 or resource allocation type 1, where the bit value of 0 indicates resource allocation type 0 and the bit value of 1 indicates resource allocation type 1.
 - For resource allocation type 0, the N_{RBG} LSBs provide the resource allocation as defined in Clause 6.1.2.2.1 of [6, TS 38.214].
 - For resource allocation type 1, the $\lceil \log_2(N_{RBG,K1}(N_{RBG,K1} + 1)/2) \rceil$ LSBs provide the resource allocation as follows:
 - For PUSCH hopping with resource allocation type 1:
 - $N_{UL,hop}$ MSB bits are used to indicate the frequency offset according to Clause 6.3 of [6, TS 38.214], where $N_{UL,hop} = 1$ if the higher layer parameter *frequencyHoppingOffsetListsDCI-0-2* contains two offset values and $N_{UL,hop} = 2$ if the higher layer parameter *frequencyHoppingOffsetListsDCI-0-2* contains four offset values
 - $\lceil \log_2(N_{RBG,K1}(N_{RBG,K1} + 1)/2) \rceil - N_{UL,hop}$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]
 - For non-PUSCH hopping with resource allocation type 1:
 - $\lceil \log_2(N_{RBG,K1}(N_{RBG,K1} + 1)/2) \rceil$ bits provide the frequency domain resource allocation according to Clause 6.1.2.2.2 of [6, TS 38.214]

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and if *resourceAllocationDCI-0-2-r16* is configured as 'dynamicSwitch' for the indicated bandwidth part, the UE assumes resource allocation type 0 for the indicated bandwidth part if the bitwidth of the "Frequency domain resource assignment" field of the active bandwidth part is smaller than the bitwidth of the "Frequency domain resource assignment" field of the indicated bandwidth part.

- Time domain resource assignment – 0, 1, 2, 3, 4, 5 or 6 bits as defined in Clause 6.1.2.1 of [6, TS38.214]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *pusch-TimeDomainAllocationListDCI-0-2* if the higher layer parameter is configured, or I is the number of entries in the higher layer parameter *PUSCH-TimeDomainResourceAllocationList* if the higher layer parameter *PUSCH-TimeDomainResourceAllocationList* is configured and the higher layer parameter *pusch-TimeDomainAllocationListDCI-0-2* is not configured; otherwise I is the number of entries in the default table.
- Frequency hopping flag – 0 or 1 bit:

- 0 bit if the higher layer parameter *frequencyHoppingDCI-0-2* is not configured;
- 1 bit according to Table 7.3.1.1.1-3 otherwise, only applicable to resource allocation type 1, as defined in Clause 6.3 of [6, TS 38.214].
- Modulation and coding scheme – 5 bits as defined in Clause 6.1.4.1 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 0, 1 or 2 bits determined by higher layer parameter *numberOfBitsForRV-DCI-0-2*
 - If 0 bit is configured, *rv_{id}* to be applied is 0;
 - 1 bit according to Table 7.3.1.2.3-1;
 - 2 bits according to Table 7.3.1.1.1-2.
- HARQ process number – 0, 1, 2, 3 or 4 bits determined by higher layer parameter *harq-ProcessNumberSizeDCI-0-2*
- Downlink assignment index – 0, 1, 2 or 4 bits
 - 0 bit if the higher layer parameter *downlinkAssignmentIndexDCI-0-2* is not configured;
 - 1, 2 or 4 bits otherwise,
 - 1st downlink assignment index – 1 or 2 bits:
 - 1 bit for semi-static HARQ-ACK codebook;
 - 2 bits for dynamic HARQ-ACK codebook.
 - 2nd downlink assignment index – 0 or 2 bits
 - 2 bits for dynamic HARQ-ACK codebook with two HARQ-ACK sub-codebooks;
 - 0 bit otherwise.

When two HARQ-ACK codebooks are configured for the same serving cell and if higher layer parameter *priorityIndicatorDCI-0-2* is configured, if the bit width of the Downlink assignment index in DCI format 0_2 for one HARQ-ACK codebook is not equal to that of the Downlink assignment index in DCI format 0_2 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller Downlink assignment index until the bit width of the Downlink assignment index in DCI format 0_2 for the two HARQ-ACK codebooks are the same.

- TPC command for scheduled PUSCH – 2 bits as defined in Clause 7.1.1 of [5, TS38.213]
- SRS resource indicator – $\left\lceil \log_2 \left(\sum_{k=1}^{\min\{L_{max}, N_{SRS,0,2}\}} \binom{N_{SRS,0,2}}{k} \right) \right\rceil$ or $\left\lceil \log_2 N_{SRS,0,2} \right\rceil$ bits, where $N_{SRS,0,2}$ is the number of configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModListDCI-0-2*, and associated with the higher layer parameter *usage* of value 'codeBook' or 'nonCodeBook', where the SRS resource set is composed of the first $N_{SRS,0,2}$ SRS resources together with other configurations in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, if any, and associated with the higher layer parameter *usage* of value 'codeBook' or 'nonCodeBook', respectively, except for the higher layer parameters '*srs-ResourceSetId*' and '*srs-ResourceIdList*'
- $\left\lceil \log_2 \left(\sum_{k=1}^{\min\{L_{max}, N_{SRS,0,2}\}} \binom{N_{SRS,0,2}}{k} \right) \right\rceil$ bits according to Tables 7.3.1.1.2-28/29/30/31 if the higher layer parameter *txConfig = nonCodebook*, where $N_{SRS,0,2}$ is the number of configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModListDCI-0-2*, and associated with the higher layer parameter *usage* of value 'nonCodeBook', where the SRS resource set is composed of the first $N_{SRS,0,2}$ SRS resources together with other configurations in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, if any, and associated with the higher layer parameter *usage* of value 'nonCodeBook', except for the higher layer parameters '*srs-ResourceSetId*' and '*srs-ResourceIdList*', and

- if UE supports operation with *maxMIMO-LayersDCI-0-2* and the higher layer parameter *maxMIMO-LayersDCI-0-2* of *PUSCH-ServingCellConfig* of the serving cell is configured, L_{max} is given by that parameter
- otherwise, L_{max} is given by the maximum number of layers for PUSCH supported by the UE for the serving cell for non-codebook based operation.
- $\lceil \log_2 N_{SRS,0,2} \rceil$ bits according to Tables 7.3.1.1.2-32 if the higher layer parameter *txConfig* = *codebook*, where $N_{SRS,0,2}$ is the number of configured SRS resources in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModListDCI-0-2*, and associated with the higher layer parameter *usage* of value '*codeBook*', where the SRS resource set is composed of the first $N_{SRS,0,2}$ SRS resources together with other configurations in the SRS resource set configured by higher layer parameter *srs-ResourceSetToAddModList*, if any, and associated with the higher layer parameter *usage* of value '*codeBook*', except for the higher layer parameters '*srs-ResourceSetId*' and '*srs-ResourceIdList*'.
- Precoding information and number of layers – number of bits determined by the following:
 - 0 bits if the higher layer parameter *txConfig* = *nonCodeBook*;
 - 0 bits for 1 antenna port and if the higher layer parameter *txConfig* = *codebook*;
 - 4, 5, or 6 bits according to Table 7.3.1.1.2-2 for 4 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*, transform precoder is disabled, and according to the values of higher layer parameters *maxRankDCI-0-2*, and *codebookSubsetDCI-0-2*;
 - 4 or 5 bits according to Table 7.3.1.1.2-2A for 4 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* = *fullpowerMode1*, the values of higher layer parameters *maxRankDCI-0-2*=2, transform precoder is disabled, and according to the value of higher layer parameter *codebookSubsetDCI-0-2*;
 - 4 or 6 bits according to Table 7.3.1.1.2-2B for 4 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* = *fullpowerMode1*, the values of higher layer parameters *maxRankDCI-0-2*=3 or 4, transform precoder is disabled, and according to the value of higher layer parameter *codebookSubsetDCI-0-2*;
 - 2, 4, or 5 bits according to Table 7.3.1.1.2-3 for 4 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameters *maxRankDCI-0-2* and *codebookSubsetDCI-0-2*;
 - 3 or 4 bits according to Table 7.3.1.1.2-3A for 4 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* = *fullpowerMode1*, *maxRankDCI-0-2*=1, and according to whether transform precoder is enabled or disabled, and the value of higher layer parameter *codebookSubsetDCI-0-2*;
 - 2 or 4 bits according to Table 7.3.1.1.2-4 for 2 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*, transform precoder is disabled, and according to the values of higher layer parameters *maxRankDCI-0-2* and *codebookSubsetDCI-0-2*;
 - 2 bits according to Table 7.3.1.1.2-4A for 2 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* = *fullpowerMode1*, transform precoder is disabled, the *maxRankDCI-0-2*=2, and *codebookSubsetDCI-0-2*=*nonCoherent*;
 - 1 or 3 bits according to Table 7.3.1.1.2-5 for 2 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* is not configured or configured to *fullpowerMode2* or configured to *fullpower*, and according to whether transform precoder is enabled or disabled, and the values of higher layer parameters *maxRankDCI-0-2* and *codebookSubsetDCI-0-2*;
 - 2 bits according to Table 7.3.1.1.2-5A for 2 antenna ports, if *txConfig* = *codebook*, *ul-FullPowerTransmission* = *fullpowerMode1*, *maxRankDCI-0-2*=1, and according to whether transform precoder is enabled or disabled, and the value of higher layer parameter *codebookSubsetDCI-0-2*.

For the higher layer parameter *txConfig*=*codebook*, if *ul-FullPowerTransmission* is configured to *fullpowerMode2*, the values of higher layer parameters *maxRankDCI-0-2* is configured to be larger than 2, and at least one SRS resource with 4 antenna ports is configured in an SRS resource set with usage set to '*codebook*' and an SRS resource with 2 antenna ports is indicated via SRI in the same SRS resource set, then Table 7.3.1.1.2-4 is used.

For the higher layer parameter $txConfig = codebook$, if different SRS resources with different number of antenna ports are configured, the bitwidth is determined according to the maximum number of ports in an SRS resource among the configured SRS resources in an SRS resource set with usage set to 'codebook'. If the number of ports for a configured SRS resource in the set is less than the maximum number of ports in an SRS resource among the configured SRS resources, a number of most significant bits with value set to '0' are inserted to the field.

- Antenna ports – number of bits determined by the following:
 - 0 bit if higher layer parameter $antennaPortsFieldPresenceDCI-0-2$ is not configured;
 - 2, 3, 4, or 5 bits otherwise,
 - 2 bits as defined by Tables 7.3.1.1.2-6, if transform precoder is enabled, $dmrs-Type=1$, and $maxLength=1$, except that $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured and $\pi/2$ BPSK modulation is used;
 - 2 bits as defined by 7.3.1.1.2-6A, if transform precoder is enabled, and $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured, $\pi/2$ BPSK modulation is used, $dmrs-Type=1$, and $maxLength=1$, where n_{SCID} is the scrambling identity for antenna ports defined in Clause 6.4.1.1.1.2, in [4, TS38.211];
 - 4 bits as defined by Tables 7.3.1.1.2-7, if transform precoder is enabled, $dmrs-Type=1$, and $maxLength=2$, except that $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured and $\pi/2$ BPSK modulation is used;
 - 4 bits as defined by Tables 7.3.1.1.2-7A, if transform precoder is enabled, and $dmrs-UplinkTransformPrecoding$ and $tp-pi2BPSK$ are both configured, $\pi/2$ BPSK modulation is used, $dmrs-Type=1$, and $maxLength=2$, where n_{SCID} is the scrambling identity for antenna ports defined in Clause 6.4.1.1.1.2, in [4, TS38.211];
 - 3 bits as defined by Tables 7.3.1.1.2-8/9/10/11, if transform precoder is disabled, $dmrs-Type=1$, and $maxLength=1$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
 - 4 bits as defined by Tables 7.3.1.1.2-12/13/14/15, if transform precoder is disabled, $dmrs-Type=1$, and $maxLength=2$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
 - 4 bits as defined by Tables 7.3.1.1.2-16/17/18/19, if transform precoder is disabled, $dmrs-Type=2$, and $maxLength=1$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$;
 - 5 bits as defined by Tables 7.3.1.1.2-20/21/22/23, if transform precoder is disabled, $dmrs-Type=2$, and $maxLength=2$, and the value of rank is determined according to the SRS resource indicator field if the higher layer parameter $txConfig = nonCodebook$ and according to the Precoding information and number of layers field if the higher layer parameter $txConfig = codebook$.

where the number of CDM groups without data of values 1, 2, and 3 in Tables 7.3.1.1.2-6 to 7.3.1.1.2-23 refers to CDM groups {0}, {0,1}, and {0, 1,2} respectively.

If a UE is configured with both $dmrs-UplinkForPUSCH-MappingTypeA-DCI-0-2$ and $dmrs-UplinkForPUSCH-MappingTypeB-DCI-0-2$ and is configured with $antennaPortsFieldPresenceDCI-0-2$, the bitwidth of this field equals $\max\{x_A, x_B\}$, where x_A is the "Antenna ports" bitwidth derived according to $dmrs-UplinkForPUSCH-MappingTypeA-DCI-0-2$ and x_B is the "Antenna ports" bitwidth derived according to $dmrs-UplinkForPUSCH-MappingTypeB-DCI-0-2$. A number of $|x_A - x_B|$ zeros are padded in the MSB of this field, if the mapping type of the PUSCH corresponds to the smaller value of x_A and x_B .

If a UE is not configured with higher layer parameter $antennaPortsFieldPresenceDCI-0-2$, antenna port(s) are defined assuming bit field index value 0 in Tables 7.3.1.1.2-6 to 7.3.1.1.2-23.

- SRS request – 0, 1, 2 or 3 bits
 - 0 bit if the higher layer parameter $srs-RequestDCI-0-2$ is not configured;

- 1 bit as defined by Table 7.3.1.1.3-1 if higher layer parameter *srs-RequestDCI-0-2* = 1 and for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell;
- 2 bits if higher layer parameter *srs-RequestDCI-0-2* = 1 and for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell, where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second bit is defined by Table 7.3.1.1.3-1;
- 2 bits as defined by Table 7.3.1.1.2-24 if higher layer parameter *srs-RequestDCI-0-2* = 2 and for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell;
- 3 bits if higher layer parameter *srs-RequestDCI-0-2* = 2 and for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell, where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second and third bits are defined by Table 7.3.1.1.2-24;
- CSI request – 0, 1, 2, 3, 4, 5, or 6 bits determined by higher layer parameter *reportTriggerSizeDCI-0-2*.
- PTRS-DMRS association – number of bits determined as follows
 - 0 bit if *PTRS-UplinkConfig* is not configured in either *dmrs-UplinkForPUSCH-MappingTypeA* or *dmrs-UplinkForPUSCH-MappingTypeB* and transform precoder is disabled, or if transform precoder is enabled, or if *maxRankDCI-0-2*=1;
 - 2 bits otherwise, where Table 7.3.1.1.2-25 and 7.3.1.1.2-26 are used to indicate the association between PTRS port(s) and DMRS port(s) when one PT-RS port and two PT-RS ports are configured by *maxNrofPorts* in *PTRS-UplinkConfig* respectively, and the DMRS ports are indicated by the Antenna ports field.

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and the "PTRS-DMRS association" field is present for the indicated bandwidth part but not present for the active bandwidth part, the UE assumes the "PTRS-DMRS association" field is not present for the indicated bandwidth part.

- beta_offset indicator – 0 bit if the higher layer parameter *betaOffsets* = *semiStatic*; otherwise 1 bit if 2 offset indexes are configured by higher layer parameter *dynamicDCI-0-2* as defined by Table 9.3-3A in [5, TS 38.213], and 2 bits if 4 offset indexes are configured by higher layer parameter *dynamicDCI-0-2* as defined by Table 9.3-3 in [5, TS 38.213].

When two HARQ-ACK codebooks are configured for the same serving cell and if higher layer parameter *priorityIndicatorDCI-0-2* is configured, if the bit width of the beta_offset indicator in DCI format 0_2 for one HARQ-ACK codebook is not equal to that of the beta_offset indicator in DCI format 0_2 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller beta_offset indicator until the bit width of the beta_offset indicator in DCI format 0_2 for the two HARQ-ACK codebooks are the same.

- DMRS sequence initialization – 0 or 1 bit
 - 0 bit if the higher layer parameter *dmrs-SequenceInitializationDCI-0-2* is not configured or if transform precoder is enabled;
 - 1 bit if transform precoder is disabled and the higher layer parameter *dmrs-SequenceInitializationDCI-0-2* is configured.
- UL-SCH indicator – 1 bit. A value of "1" indicates UL-SCH shall be transmitted on the PUSCH and a value of "0" indicates UL-SCH shall not be transmitted on the PUSCH. Except for DCI format 0_2 with CRC scrambled by SP-CSI-RNTI, a UE is not expected to receive a DCI format 0_2 with UL-SCH indicator of "0" and CSI request of all zero(s).
- Open-loop power control parameter set indication – 0 or 1 or 2 bits.
 - 0 bit if the higher layer parameter *p0-PUSCH-SetList* is not configured;
 - 1 or 2 bits otherwise,
 - 1 bit if SRS resource indicator is present in the DCI format 0_2;

- 1 or 2 bits as determined by higher layer parameter *olpc-ParameterSetDCI-0-2* if SRS resource indicator is not present in the DCI format 0_2;
- Priority indicator – 0 bit if higher layer parameter *priorityIndicatorDCI-0-2* is not configured; otherwise 1 bit as defined in Clause 9 in [5, TS 38.213].
- Invalid symbol pattern indicator – 0 bit if higher layer parameter *invalidSymbolPatternIndicatorDCI-0-2* is not configured; otherwise 1 bit as defined in Clause 6.1.2.1 in [6, TS 38.214].

A UE does not expect that the bit width of a field in DCI format 0_2 with CRC scrambled by CS-RNTI is larger than corresponding bit width of same field in DCI format 0_2 with CRC scrambled by C-RNTI for the same serving cell. If the bit width of a field in the DCI format 0_2 with CRC scrambled by CS-RNTI is not equal to that of the corresponding field in the DCI format 0_2 with CRC scrambled by C-RNTI for the same serving cell, a number of most significant bits with value set to '0' are inserted to the field in DCI format 0_2 with CRC scrambled by CS-RNTI until the bit width equals that of the corresponding field in the DCI format 0_2 with CRC scrambled by C-RNTI for the same serving cell.

Table 7.3.1.1.3-1: 1 bit SRS request in DCI format 0_2 and DCI format 1_2

| Value of SRS request field | Triggered aperiodic SRS resource set(s) for DCI format 0_2 and 1_2 |
|----------------------------|---|
| 0 | No aperiodic SRS resource set triggered |
| 1 | SRS resource set(s) configured with higher layer parameter <i>aperiodicSRS-ResourceTrigger</i> set to 1 or an entry in <i>aperiodicSRS-ResourceTriggerList</i> set to 1 |

7.3.1.2 DCI formats for scheduling of PDSCH

7.3.1.2.1 Format 1_0

DCI format 1_0 is used for the scheduling of PDSCH in one DL cell.

The following information is transmitted by means of the DCI format 1_0 with CRC scrambled by C-RNTI or CS-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bits
 - The value of this bit field is always set to 1, indicating a DL DCI format
- Frequency domain resource assignment – $\left\lceil \log_2(N_{RB}^{DL,BWP}(N_{RB}^{DL,BWP} + 1)/2) \right\rceil$ bits where $N_{RB}^{DL,BWP}$ is given by clause 7.3.1.0

If the CRC of the DCI format 1_0 is scrambled by C-RNTI and the "Frequency domain resource assignment" field are of all ones, the DCI format 1_0 is for random access procedure initiated by a PDCCH order, with all remaining fields set as follows:

- Random Access Preamble index – 6 bits according to *ra-PreambleIndex* in Clause 5.1.2 of [8, TS38.321]
- UL/SUL indicator – 1 bit. If the value of the "Random Access Preamble index" is not all zeros and if the UE is configured with *supplementaryUplink* in *ServingCellConfig* in the cell, this field indicates which UL carrier in the cell to transmit the PRACH according to Table 7.3.1.1.1-1; otherwise, this field is reserved
- SS/PBCH index – 6 bits. If the value of the "Random Access Preamble index" is not all zeros, this field indicates the SS/PBCH that shall be used to determine the RACH occasion for the PRACH transmission; otherwise, this field is reserved.
- PRACH Mask index – 4 bits. If the value of the "Random Access Preamble index" is not all zeros, this field indicates the RACH occasion associated with the SS/PBCH indicated by "SS/PBCH index" for the PRACH transmission, according to Clause 5.1.1 of [8, TS38.321]; otherwise, this field is reserved

- Reserved bits – 12 bits for operation in a cell with shared spectrum channel access; otherwise 10 bits

Otherwise, all remaining fields are set as follows:

- Time domain resource assignment – 4 bits as defined in Clause 5.1.2.1 of [6, TS 38.214]
- VRB-to-PRB mapping – 1 bit according to Table 7.3.1.2.2-5
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2
- HARQ process number – 4 bits
- Downlink assignment index – 2 bits as defined in Clause 9.1.3 of [5, TS 38.213], as counter DAI
- TPC command for scheduled PUCCH – 2 bits as defined in Clause 7.2.1 of [5, TS 38.213]
- PUCCH resource indicator – 3 bits as defined in Clause 9.2.3 of [5, TS 38.213]
- PDSCH-to-HARQ_feedback timing indicator – 3 bits as defined in Clause 9.2.3 of [5, TS38.213]
- ChannelAccess-CPext – 2 bits indicating combinations of channel access type and CP extension as defined in Table 7.3.1.1.1-4, or Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; 0 bits otherwise

The following information is transmitted by means of the DCI format 1_0 with CRC scrambled by P-RNTI:

- Short Messages Indicator – 2 bits according to Table 7.3.1.2.1-1.
- Short Messages – 8 bits, according to Clause 6.5 of [9, TS38.331]. If only the scheduling information for Paging is carried, this bit field is reserved.
- Frequency domain resource assignment – $\lceil \log_2(N_{RB}^{DL,BWP}(N_{RB}^{DL,BWP} + 1)/2) \rceil$ bits. If only the short message is carried, this bit field is reserved.
 - $N_{RB}^{DL,BWP}$ is the size of CORESET 0
- Time domain resource assignment – 4 bits as defined in Clause 5.1.2.1 of [6, TS38.214]. If only the short message is carried, this bit field is reserved.
- VRB-to-PRB mapping – 1 bit according to Table 7.3.1.2.2-5. If only the short message is carried, this bit field is reserved.
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3 of [6, TS38.214], using Table 5.1.3.1-1. If only the short message is carried, this bit field is reserved.
- TB scaling – 2 bits as defined in Clause 5.1.3.2 of [6, TS38.214]. If only the short message is carried, this bit field is reserved.
- Reserved bits – 8 bits for operation in a cell with shared spectrum channel access; otherwise 6 bits

The following information is transmitted by means of the DCI format 1_0 with CRC scrambled by SI-RNTI:

- Frequency domain resource assignment – $\lceil \log_2(N_{RB}^{DL,BWP}(N_{RB}^{DL,BWP} + 1)/2) \rceil$ bits
 - $N_{RB}^{DL,BWP}$ is the size of CORESET 0
- Time domain resource assignment – 4 bits as defined in Clause 5.1.2.1 of [6, TS38.214]

- VRB-to-PRB mapping – 1 bit according to Table 7.3.1.2.2-5
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3 of [6, TS38.214], using Table 5.1.3.1-1
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2
- System information indicator – 1 bit as defined in Table 7.3.1.2.1-2
- Reserved bits – 17 bits for operation in a cell with shared spectrum channel access; otherwise 15 bits

The following information is transmitted by means of the DCI format 1_0 with CRC scrambled by RA-RNTI or MsgB-RNTI:

- Frequency domain resource assignment – $\lceil \log_2(N_{RB}^{DL,BWP}(N_{RB}^{DL,BWP} + 1)/2) \rceil$ bits
 - $N_{RB}^{DL,BWP}$ is the size of CORESET 0 if CORESET 0 is configured for the cell and $N_{RB}^{DL,BWP}$ is the size of initial DL bandwidth part if CORESET 0 is not configured for the cell
- Time domain resource assignment – 4 bits as defined in Clause 5.1.2.1 of [6, TS38.214]
- VRB-to-PRB mapping – 1 bit according to Table 7.3.1.2.2-5
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3 of [6, TS38.214], using Table 5.1.3.1-1
- TB scaling – 2 bits as defined in Clause 5.1.3.2 of [6, TS38.214]
- LSBs of SFN – 2 bits for the DCI format 1_0 with CRC scrambled by MsgB-RNTI as defined in Clause 8.2A of [5, TS 38.213] if *msgB-responseWindow* is configured to be larger than 10 ms; or 2 bits for the DCI format 1_0 with CRC scrambled by RA-RNTI as defined in Clause 8.2 of [5, TS 38.213] for operation in a cell with shared spectrum channel access if *ra-ResponseWindow* or *ra-ResponseWindow-v1610* is configured to be larger than 10 ms; 0 bit otherwise
- Reserved bits – (16 – A) bits for operation in a cell without shared spectrum access, (18 – A) for operation in a cell with shared spectrum access, where the value of A is the number of bits for the field of 'LSBs of SFN' as defined above

The following information is transmitted by means of the DCI format 1_0 with CRC scrambled by TC-RNTI:

- Identifier for DCI formats – 1 bit
 - The value of this bit field is always set to 1, indicating a DL DCI format
- Frequency domain resource assignment – $\lceil \log_2(N_{RB}^{DL,BWP}(N_{RB}^{DL,BWP} + 1)/2) \rceil$ bits
 - $N_{RB}^{DL,BWP}$ is the size of CORESET 0
- Time domain resource assignment – 4 bits as defined in Clause 5.1.2.1 of [6, TS38.214]
- VRB-to-PRB mapping – 1 bit according to Table 7.3.1.2.2-5
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3 of [6, TS38.214], using Table 5.1.3.1-1
- New data indicator – 1 bit
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2
- HARQ process number – 4 bits
- Downlink assignment index – 2 bits, reserved
- TPC command for scheduled PUCCH – 2 bits as defined in Clause 7.2.1 of [5, TS38.213]
- PUCCH resource indicator – 3 bits as defined in Clause 9.2.3 of [5, TS38.213]

- PDSCH-to-HARQ_feedback timing indicator – 3 bits as defined in Clause 9.2.3 of [5, TS38.213]
- ChannelAccess-CPext – 2 bits indicating combinations of channel access type and CP extension as defined in Table 7.3.1.1.1-4, or Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; otherwise 0 bit

Table 7.3.1.2.1-1: Short Message indicator

| Bit field | Short Message indicator |
|-----------|---|
| 00 | Reserved |
| 01 | Only scheduling information for Paging is present in the DCI |
| 10 | Only short message is present in the DCI |
| 11 | Both scheduling information for Paging and short message are present in the DCI |

Table 7.3.1.2.1-2: System information indicator

| Bit field | System information indicator |
|-----------|--|
| 0 | SIB1 [9, TS38.331, Clause 5.2.1] |
| 1 | SI message [9, TS38.331, Clause 5.2.1] |

7.3.1.2.2 Format 1_1

DCI format 1_1 is used for the scheduling of PDSCH in one cell.

The following information is transmitted by means of the DCI format 1_1 with CRC scrambled by C-RNTI or CS-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bits
 - The value of this bit field is always set to 1, indicating a DL DCI format
- Carrier indicator – 0 or 3 bits as defined in Clause 10.1 of [5, TS 38.213].
- Bandwidth part indicator – 0, 1 or 2 bits as determined by the number of DL BWPs $n_{\text{BWP,RRC}}$ configured by higher layers, excluding the initial DL bandwidth part. The bitwidth for this field is determined as $\lceil \log_2(n_{\text{BWP}}) \rceil$ bits, where
 - $n_{\text{BWP}} = n_{\text{BWP,RRC}} + 1$ if $n_{\text{BWP,RRC}} \leq 3$, in which case the bandwidth part indicator is equivalent to the ascending order of the higher layer parameter *BWP-Id*;
 - otherwise $n_{\text{BWP}} = n_{\text{BWP,RRC}}$, in which case the bandwidth part indicator is defined in Table 7.3.1.1.2-1;

If a UE does not support active BWP change via DCI, the UE ignores this bit field.

- Frequency domain resource assignment – number of bits determined by the following, where $N_{\text{RB}}^{\text{DL,BWP}}$ is the size of the active DL bandwidth part:
 - N_{RBG} bits if only resource allocation type 0 is configured, where N_{RBG} is defined in Clause 5.1.2.2.1 of [6, TS38.214],
 - $\lceil \log_2(N_{\text{RB}}^{\text{DL,BWP}}(N_{\text{RB}}^{\text{DL,BWP}} + 1)/2) \rceil$ bits if only resource allocation type 1 is configured, or
 - $\max(\lceil \log_2(N_{\text{RB}}^{\text{DL,BWP}}(N_{\text{RB}}^{\text{DL,BWP}} + 1)/2) \rceil, N_{\text{RBG}}) + 1$ bits if *resourceAllocation* is configured as 'dynamicSwitch'.

- If *resourceAllocation* is configured as *dynamicSwitch*, the MSB bit is used to indicate resource allocation type 0 or resource allocation type 1, where the bit value of 0 indicates resource allocation type 0 and the bit value of 1 indicates resource allocation type 1.
- For resource allocation type 0, the N_{RBG} LSBs provide the resource allocation as defined in Clause 5.1.2.2.1 of [6, TS 38.214].
- For resource allocation type 1, the $\lceil \log_2(N_{\text{RB}}^{\text{DL,BWP}}(N_{\text{RB}}^{\text{DL,BWP}} + 1)/2) \rceil$ LSBs provide the resource allocation as defined in Clause 5.1.2.2.2 of [6, TS 38.214]

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and if *resourceAllocation* is configured as *dynamicSwitch* for the indicated bandwidth part, the UE assumes resource allocation type 0 for the indicated bandwidth part if the bitwidth of the "Frequency domain resource assignment" field of the active bandwidth part is smaller than the bitwidth of the "Frequency domain resource assignment" field of the indicated bandwidth part.

- Time domain resource assignment – 0, 1, 2, 3, or 4 bits as defined in Clause 5.1.2.1 of [6, TS 38.214]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *pdsch-TimeDomainAllocationList* if the higher layer parameter is configured; otherwise I is the number of entries in the default table.
- VRB-to-PRB mapping – 0 or 1 bit:
 - 0 bit if only resource allocation type 0 is configured or if interleaved VRB-to-PRB mapping is not configured by high layers;
 - 1 bit according to Table 7.3.1.2.2-5 otherwise, only applicable to resource allocation type 1, as defined in Clause 7.3.1.6 of [4, TS 38.211].
- PRB bundling size indicator – 0 bit if the higher layer parameter *prb-BundlingType* is not configured or is set to 'staticBundling', or 1 bit if the higher layer parameter *prb-BundlingType* is set to 'dynamicBundling' according to Clause 5.1.2.3 of [6, TS 38.214].
- Rate matching indicator – 0, 1, or 2 bits according to higher layer parameters *rateMatchPatternGroup1* and *rateMatchPatternGroup2*, where the MSB is used to indicate *rateMatchPatternGroup1* and the LSB is used to indicate *rateMatchPatternGroup2* when there are two groups.
- ZP CSI-RS trigger – 0, 1, or 2 bits as defined in Clause 5.1.4.2 of [6, TS 38.214]. The bitwidth for this field is determined as $\lceil \log_2(n_{\text{ZP}} + 1) \rceil$ bits, where n_{ZP} is the number of aperiodic ZP CSI-RS resource sets configured by higher layer.

For transport block 1:

- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3.1 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2

For transport block 2 (only present if *maxNrofCodeWordsScheduledByDCI* equals 2):

- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3.1 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and the value of *maxNrofCodeWordsScheduledByDCI* for the indicated bandwidth part equals 2 and the value of *maxNrofCodeWordsScheduledByDCI* for the active bandwidth part equals 1, the UE assumes zeros are padded when interpreting the "Modulation and coding scheme", "New data indicator", and "Redundancy version" fields of transport block 2 according to Clause 12 of [5, TS38.213], and the UE ignores the "Modulation and coding scheme", "New data indicator", and "Redundancy version" fields of transport block 2 for the indicated bandwidth part.

- HARQ process number – 4 bits
- Downlink assignment index – number of bits as defined in the following
 - 6 bits if more than one serving cell are configured in the DL and the higher layer parameter *nfi-TotalDAI-Included* is configured. The 4 MSB bits are the counter DAI and the total DAI for the scheduled PDSCH group, and the 2 LSB bits are the total DAI for the non-scheduled PDSCH group.
 - 4 bits if only one serving cell is configured in the DL and the higher layer parameter *nfi-TotalDAI-Included* is configured. The 2 MSB bits are the counter DAI for the scheduled PDSCH group, and the 2 LSB bits are the total DAI for the non-scheduled PDSCH group;
 - 4 bits if more than one serving cell are configured in the DL, the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic* or *pdsch-HARQ-ACK-Codebook-r16=enhancedDynamic*, and *nfi-TotalDAI-Included* is not configured, where the 2 MSB bits are the counter DAI and the 2 LSB bits are the total DAI;
 - 4 bits if one serving cell is configured in the DL, and the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic*, and the UE is not provided *coresetPoolIndex* or is provided *coresetPoolIndex* with value 0 for one or more first CORESETs and is provided *coresetPoolIndex* with value 1 for one or more second CORESETs, and is provided *ackNackFeedbackMode = joint*, where the 2 MSB bits are the counter DAI and the 2 LSB bits are the total DAI;
 - 2 bits if only one serving cell is configured in the DL, the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic* or *pdsch-HARQ-ACK-Codebook-r16=enhancedDynamic*, and *nfi-TotalDAI-Included* is not configured, when the UE is not configured with *coresetPoolIndex* or the value of *coresetPoolIndex* is the same for all CORESETs if *coresetPoolIndex* is provided or the UE is not configured with *ackNackFeedbackMode = joint*, where the 2 bits are the counter DAI;
 - 0 bits otherwise.

If the UE is configured with a PUCCH-SCell, the number of serving cells is determined within a PUCCH group.

If the UE is configured with a PUCCH-SCell, *pdsch-HARQ-ACK-Codebook* is replaced by *pdsch-HARQ-ACK-Codebook-secondaryPUCCHgroup-r16* if present for the secondary PUCCH group.

If higher layer parameter *priorityIndicatorDCI-1-1* is configured, if the bit width of the Downlink assignment index in DCI format 1_1 for one HARQ-ACK codebook is not equal to that of the Downlink assignment index in DCI format 1_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller Downlink assignment index until the bit width of the Downlink assignment index in DCI format 1_1 for the two HARQ-ACK codebooks are the same.

- TPC command for scheduled PUCCH – 2 bits as defined in Clause 7.2.1 of [5, TS 38.213]
- PUCCH resource indicator – 3 bits as defined in Clause 9.2.3 of [5, TS 38.213]
- PDSCH-to-HARQ_feedback timing indicator – 0, 1, 2, or 3 bits as defined in Clause 9.2.3 of [5, TS 38.213]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where *I* is the number of entries in the higher layer parameter *dl-DataToUL-ACK*.

If higher layer parameter *priorityIndicatorDCI-1-1* is configured, if the bit width of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_1 for one HARQ-ACK codebook is not equal to that of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller PDSCH-to-HARQ_feedback timing indicator until the bit width of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_1 for the two HARQ-ACK codebooks are the same.

- One-shot HARQ-ACK request – 0 or 1 bit.
 - 1 bit if higher layer parameter *pdsch-HARQ-ACK-OneShotFeedback-r16* is configured;
 - 0 bit otherwise.
- PDSCH group index – 0 or 1 bit.
 - 1 bit if the higher layer parameter *pdsch-HARQ-ACK-Codebook-r16=enhancedDynamic*;

- 0 bit otherwise.
- New feedback indicator – 0, 1 or 2 bits.
 - 1 bit if the higher layer parameter *pdsch-HARQ-ACK-Codebook-r16*= *enhancedDynamic* and the higher layer parameter *nfi-TotalDAI-Included* is not configured;
 - 2 bits if the higher layer parameter *pdsch-HARQ-ACK-Codebook-r16*= *enhancedDynamic* and the higher layer parameter *nfi-TotalDAI-Included*=*true*; the MSB corresponds to the scheduled PDSCH group, and the LSB corresponds to the non-scheduled PDSCH group, as defined in [TS38.213] clause 9.1.3.3
 - 0 bit otherwise.
- Number of requested PDSCH group(s) – 0 or 1 bit.
 - 1 bit if the higher layer parameter *pdsch-HARQ-ACK-Codebook-r16*= *enhancedDynamic*;
 - 0 bit otherwise.
- Antenna port(s) – 4, 5, or 6 bits as defined by Tables 7.3.1.2.2-1/2/3/4 and Tables 7.3.1.2.2-1A/2A/3A/4A, where the number of CDM groups without data of values 1, 2, and 3 refers to CDM groups {0}, {0,1}, and {0, 1,2} respectively. The antenna ports $\{p_0, \dots, p_{v-1}\}$ shall be determined according to the ordering of DMRS port(s) given by Tables 7.3.1.2.2-1/2/3/4 or Tables 7.3.1.2.2-1A/2A/3A/4A. When a UE receives an activation command that maps at least one codepoint of DCI field '*Transmission Configuration Indication*' to two TCI states, the UE shall use Table 7.3.1.2.2-1A/2A/3A/4A; otherwise, it shall use Tables 7.3.1.2.2-1/2/3/4. The UE can receive an entry with DMRS ports equals to 1000, 1002, 1003 when two TCI states are indicated in a codepoint of DCI field '*Transmission Configuration Indication*'.

If a UE is configured with both *dmrs-DownlinkForPDSCH-MappingTypeA* and *dmrs-DownlinkForPDSCH-MappingTypeB*, the bitwidth of this field equals $\max\{x_A, x_B\}$, where x_A is the "Antenna ports" bitwidth derived according to *dmrs-DownlinkForPDSCH-MappingTypeA* and x_B is the "Antenna ports" bitwidth derived according to *dmrs-DownlinkForPDSCH-MappingTypeB*. A number of $|x_A - x_B|$ zeros are padded in the MSB of this field, if the mapping type of the PDSCH corresponds to the smaller value of x_A and x_B .

- Transmission configuration indication – 0 bit if higher layer parameter *tci-PresentInDCI* is not enabled; otherwise 3 bits as defined in Clause 5.1.5 of [6, TS38.214].

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part,

- if the higher layer parameter *tci-PresentInDCI* is not enabled for the CORESET used for the PDCCH carrying the DCI format 1_1,
 - the UE assumes *tci-PresentInDCI* is not enabled for all CORESETs in the indicated bandwidth part;
- otherwise,
 - the UE assumes *tci-PresentInDCI* is enabled for all CORESETs in the indicated bandwidth part.
- SRS request – 2 bits as defined by Table 7.3.1.1.2-24 for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell; 3 bits for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second and third bits are defined by Table 7.3.1.1.2-24. This bit field may also indicate the associated CSI-RS according to Clause 6.1.1.2 of [6, TS 38.214].
- CBG transmission information (CBGTI) – 0 bit if higher layer parameter *codeBlockGroupTransmission* for PDSCH is not configured, otherwise, 2, 4, 6, or 8 bits as defined in Clause 5.1.7 of [6, TS38.214], determined by the higher layer parameters *maxCodeBlockGroupsPerTransportBlock* and *maxNrofCodeWordsScheduledByDCI* for the PDSCH.

If higher layer parameter *priorityIndicatorDCI-1-1* is configured, if the bit width of the CBG transmission information in DCI format 1_1 for one HARQ-ACK codebook is not equal to that of the CBG transmission information in DCI format 1_1 for the other HARQ-ACK codebook, a number of most significant bits with

value set to '0' are inserted to smaller CBG transmission information until the bit width of the CBG transmission information in DCI format 1_1 for the two HARQ-ACK codebooks are the same.

- CBG flushing out information (CBGFI) – 1 bit if higher layer parameter *codeBlockGroupFlushIndicator* is configured as "TRUE", 0 bit otherwise.

If higher layer parameter *priorityIndicatorDCI-1-1* is configured, if the bit width of the CBG flushing out information in DCI format 1_1 for one HARQ-ACK codebook is not equal to that of the CBG flushing out information in DCI format 1_1 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller CBG flushing out information until the bit width of the CBG flushing out information in DCI format 1_1 for the two HARQ-ACK codebooks are the same.

- DMRS sequence initialization – 1 bit.
- Priority indicator – 0 bit if higher layer parameter *priorityIndicatorDCI-1-1* is not configured; otherwise 1 bit as defined in Clause 9 in [5, TS 38.213].
- ChannelAccess-CPext – 0, 1, 2, 3 or 4 bits. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *ul-AccessConfigListDCI-1-1* or in Table 7.3.1.1.1-4A if *ChannelAccessMode-r16* = "semistatic" is provided, for operation in a cell with shared spectrum channel access; otherwise 0 bit. One or more entries from Table 7.3.1.2.2-6 are configured by the higher layer parameter *ul-AccessConfigListDCI-1-1*.
- Minimum applicable scheduling offset indicator – 0 or 1 bit
 - 0 bit if higher layer parameter *minimumSchedulingOffsetK0* is not configured;
 - 1 bit if higher layer parameter *minimumSchedulingOffsetK0* is configured. The 1 bit indication is used to determine the minimum applicable K0 for the active DL BWP and the minimum applicable K2 value for the active UL BWP, if configured respectively, according to Table 7.3.1.1.2-33. If the minimum applicable K0 is indicated, the minimum applicable value of the aperiodic CSI-RS triggering offset for an active DL BWP shall be the same as the minimum applicable K0 value.
- SCell dormancy indication – 0 bit if higher layer parameter *dormancyGroupWithinActiveTime* is not configured; otherwise 1, 2, 3, 4 or 5 bits bitmap determined according to higher layer parameter *dormancyGroupWithinActiveTime*, where each bit corresponds to one of the SCell group(s) configured by higher layers parameter *dormancyGroupWithinActiveTime*, with MSB to LSB of the bitmap corresponding to the first to last configured SCell group. The field is only present when this format is carried by PDCCH on the primary cell within DRX Active Time and the UE is configured with at least two DL BWPs for an SCell.

If one-shot HARQ-ACK request is not present or set to '0', and all bits of frequency domain resource assignment are set to 0 for resource allocation type 0 or set to 1 for resource allocation type 1 or set to 0 or 1 for dynamic switch resource allocation type, this field is reserved and the following fields among the fields above are used for SCell dormancy indication, where each bit corresponds to one of the configured SCell(s), with MSB to LSB of the following fields concatenated in the order below corresponding to the SCell with lowest to highest SCell index

- Modulation and coding scheme of transport block 1
- New data indicator of transport block 1
- Redundancy version of transport block 1
- HARQ process number
- Antenna port(s)
- DMRS sequence initialization

If DCI formats 1_1 are monitored in multiple search spaces associated with multiple CORESETs in a BWP for scheduling the same serving cell, zeros shall be appended until the payload size of the DCI formats 1_1 monitored in the multiple search spaces equal to the maximum payload size of the DCI format 1_1 monitored in the multiple search spaces.

Table 7.3.1.2.2-1: Antenna port(s) (1000 + DMRS port), *dmrs-Type=1*, *maxLength=1*

| One Codeword: Codeword 0 enabled, Codeword 1 disabled | | |
|---|--|-----------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
| 0 | 1 | 0 |
| 1 | 1 | 1 |
| 2 | 1 | 0,1 |
| 3 | 2 | 0 |
| 4 | 2 | 1 |
| 5 | 2 | 2 |
| 6 | 2 | 3 |
| 7 | 2 | 0,1 |
| 8 | 2 | 2,3 |
| 9 | 2 | 0-2 |
| 10 | 2 | 0-3 |
| 11 | 2 | 0,2 |
| 12-15 | Reserved | Reserved |

Table 7.3.1.2.2-1A: Antenna port(s) (1000 + DMRS port), *dmrs-Type=1*, *maxLength=1*

| One Codeword: Codeword 0 enabled, Codeword 1 disabled | | |
|---|--|-----------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
| 0 | 1 | 0 |
| 1 | 1 | 1 |
| 2 | 1 | 0,1 |
| 3 | 2 | 0 |
| 4 | 2 | 1 |
| 5 | 2 | 2 |
| 6 | 2 | 3 |
| 7 | 2 | 0,1 |
| 8 | 2 | 2,3 |
| 9 | 2 | 0-2 |
| 10 | 2 | 0-3 |
| 11 | 2 | 0,2 |
| 12 | 2 | 0,2,3 |
| 13-15 | Reserved | Reserved |

Table 7.3.1.2.2-2: Antenna port(s) (1000 + DMRS port), *dmrs-Type=1*, *maxLength=2*

| One Codeword: Codeword 0 enabled, Codeword 1 disabled | | | | Two Codewords: Codeword 0 enabled, Codeword 1 enabled | | | |
|---|---|-----------------|------------------------------------|---|---|-----------------|------------------------------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols | Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
| 0 | 1 | 0 | 1 | 0 | 2 | 0-4 | 2 |
| 1 | 1 | 1 | 1 | 1 | 2 | 0,1,2,3,4,6 | 2 |
| 2 | 1 | 0,1 | 1 | 2 | 2 | 0,1,2,3,4,5,6 | 2 |
| 3 | 2 | 0 | 1 | 3 | 2 | 0,1,2,3,4,5,6,7 | 2 |
| 4 | 2 | 1 | 1 | 4-31 | reserved | reserved | reserved |
| 5 | 2 | 2 | 1 | | | | |
| 6 | 2 | 3 | 1 | | | | |
| 7 | 2 | 0,1 | 1 | | | | |
| 8 | 2 | 2,3 | 1 | | | | |
| 9 | 2 | 0-2 | 1 | | | | |
| 10 | 2 | 0-3 | 1 | | | | |
| 11 | 2 | 0,2 | 1 | | | | |
| 12 | 2 | 0 | 2 | | | | |
| 13 | 2 | 1 | 2 | | | | |
| 14 | 2 | 2 | 2 | | | | |
| 15 | 2 | 3 | 2 | | | | |
| 16 | 2 | 4 | 2 | | | | |
| 17 | 2 | 5 | 2 | | | | |
| 18 | 2 | 6 | 2 | | | | |
| 19 | 2 | 7 | 2 | | | | |
| 20 | 2 | 0,1 | 2 | | | | |
| 21 | 2 | 2,3 | 2 | | | | |
| 22 | 2 | 4,5 | 2 | | | | |
| 23 | 2 | 6,7 | 2 | | | | |
| 24 | 2 | 0,4 | 2 | | | | |
| 25 | 2 | 2,6 | 2 | | | | |
| 26 | 2 | 0,1,4 | 2 | | | | |
| 27 | 2 | 2,3,6 | 2 | | | | |
| 28 | 2 | 0,1,4,5 | 2 | | | | |
| 29 | 2 | 2,3,6,7 | 2 | | | | |
| 30 | 2 | 0,2,4,6 | 2 | | | | |
| 31 | Reserved | Reserved | Reserved | | | | |

Table 7.3.1.2.2-2A: Antenna port(s) (1000 + DMRS port), *dmrs-Type=1*, *maxLength=2*

| One Codeword: Codeword 0 enabled, Codeword 1 disabled | | | | Two Codewords: Codeword 0 enabled, Codeword 1 enabled | | | |
|---|---|-----------------|------------------------------------|---|---|-----------------|------------------------------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols | Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
| 0 | 1 | 0 | 1 | 0 | 2 | 0-4 | 2 |
| 1 | 1 | 1 | 1 | 1 | 2 | 0,1,2,3,4,6 | 2 |
| 2 | 1 | 0,1 | 1 | 2 | 2 | 0,1,2,3,4,5,6 | 2 |
| 3 | 2 | 0 | 1 | 3 | 2 | 0,1,2,3,4,5,6,7 | 2 |
| 4 | 2 | 1 | 1 | 4-31 | reserved | reserved | reserved |
| 5 | 2 | 2 | 1 | | | | |
| 6 | 2 | 3 | 1 | | | | |
| 7 | 2 | 0,1 | 1 | | | | |
| 8 | 2 | 2,3 | 1 | | | | |
| 9 | 2 | 0-2 | 1 | | | | |
| 10 | 2 | 0-3 | 1 | | | | |
| 11 | 2 | 0,2 | 1 | | | | |
| 12 | 2 | 0 | 2 | | | | |
| 13 | 2 | 1 | 2 | | | | |
| 14 | 2 | 2 | 2 | | | | |
| 15 | 2 | 3 | 2 | | | | |
| 16 | 2 | 4 | 2 | | | | |
| 17 | 2 | 5 | 2 | | | | |
| 18 | 2 | 6 | 2 | | | | |
| 19 | 2 | 7 | 2 | | | | |
| 20 | 2 | 0,1 | 2 | | | | |
| 21 | 2 | 2,3 | 2 | | | | |
| 22 | 2 | 4,5 | 2 | | | | |
| 23 | 2 | 6,7 | 2 | | | | |
| 24 | 2 | 0,4 | 2 | | | | |
| 25 | 2 | 2,6 | 2 | | | | |
| 26 | 2 | 0,1,4 | 2 | | | | |
| 27 | 2 | 2,3,6 | 2 | | | | |
| 28 | 2 | 0,1,4,5 | 2 | | | | |
| 29 | 2 | 2,3,6,7 | 2 | | | | |
| 30 | 2 | 0,2,4,6 | 2 | | | | |
| 31 | 2 | 0,2,3 | 1 | | | | |

Table 7.3.1.2.2-3: Antenna port(s) (1000 + DMRS port), *dmrs-Type=2*, *maxLength=1*

| One codeword: Codeword 0 enabled, Codeword 1 disabled | | | Two codewords: Codeword 0 enabled, Codeword 1 enabled | | |
|---|---|-----------------|---|---|--------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
| 0 | 1 | 0 | 0 | 3 | 0-4 |
| 1 | 1 | 1 | 1 | 3 | 0-5 |
| 2 | 1 | 0,1 | 2-31 | reserved | reserved |
| 3 | 2 | 0 | | | |
| 4 | 2 | 1 | | | |
| 5 | 2 | 2 | | | |
| 6 | 2 | 3 | | | |
| 7 | 2 | 0,1 | | | |
| 8 | 2 | 2,3 | | | |
| 9 | 2 | 0-2 | | | |
| 10 | 2 | 0-3 | | | |
| 11 | 3 | 0 | | | |
| 12 | 3 | 1 | | | |
| 13 | 3 | 2 | | | |
| 14 | 3 | 3 | | | |
| 15 | 3 | 4 | | | |
| 16 | 3 | 5 | | | |
| 17 | 3 | 0,1 | | | |
| 18 | 3 | 2,3 | | | |
| 19 | 3 | 4,5 | | | |
| 20 | 3 | 0-2 | | | |
| 21 | 3 | 3-5 | | | |
| 22 | 3 | 0-3 | | | |
| 23 | 2 | 0,2 | | | |
| 24-31 | Reserved | Reserved | | | |

Table 7.3.1.2.2-3A: Antenna port(s) (1000 + DMRS port), *dmrs-Type=2*, *maxLength=1*

| One codeword: Codeword 0 enabled, Codeword 1 disabled | | | Two codewords: Codeword 0 enabled, Codeword 1 enabled | | |
|---|---|-----------------|---|---|--------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Value | Number of DMRS CDM group(s) without data | DMRS port(s) |
| 0 | 1 | 0 | 0 | 3 | 0-4 |
| 1 | 1 | 1 | 1 | 3 | 0-5 |
| 2 | 1 | 0,1 | 2-31 | reserved | reserved |
| 3 | 2 | 0 | | | |
| 4 | 2 | 1 | | | |
| 5 | 2 | 2 | | | |
| 6 | 2 | 3 | | | |
| 7 | 2 | 0,1 | | | |
| 8 | 2 | 2,3 | | | |
| 9 | 2 | 0-2 | | | |
| 10 | 2 | 0-3 | | | |
| 11 | 3 | 0 | | | |
| 12 | 3 | 1 | | | |
| 13 | 3 | 2 | | | |
| 14 | 3 | 3 | | | |
| 15 | 3 | 4 | | | |
| 16 | 3 | 5 | | | |
| 17 | 3 | 0,1 | | | |
| 18 | 3 | 2,3 | | | |
| 19 | 3 | 4,5 | | | |
| 20 | 3 | 0-2 | | | |
| 21 | 3 | 3-5 | | | |
| 22 | 3 | 0-3 | | | |
| 23 | 2 | 0,2 | | | |
| 24 | 2 | 0,2,3 | | | |
| 25-31 | Reserved | Reserved | | | |

Table 7.3.1.2.2-4: Antenna port(s) (1000 + DMRS port), *dmrs-Type=2*, *maxLength=2*

| One codeword: Codeword 0 enabled, Codeword 1 disabled | | | | Two Codewords: Codeword 0 enabled, Codeword 1 enabled | | | |
|---|---|-----------------|------------------------------------|---|---|-----------------|------------------------------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols | Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
| 0 | 1 | 0 | 1 | 0 | 3 | 0-4 | 1 |
| 1 | 1 | 1 | 1 | 1 | 3 | 0-5 | 1 |
| 2 | 1 | 0,1 | 1 | 2 | 2 | 0,1,2,3,6 | 2 |
| 3 | 2 | 0 | 1 | 3 | 2 | 0,1,2,3,6,8 | 2 |
| 4 | 2 | 1 | 1 | 4 | 2 | 0,1,2,3,6,7,8 | 2 |
| 5 | 2 | 2 | 1 | 5 | 2 | 0,1,2,3,6,7,8,9 | 2 |
| 6 | 2 | 3 | 1 | 6-63 | Reserved | Reserved | Reserved |
| 7 | 2 | 0,1 | 1 | | | | |
| 8 | 2 | 2,3 | 1 | | | | |
| 9 | 2 | 0-2 | 1 | | | | |
| 10 | 2 | 0-3 | 1 | | | | |
| 11 | 3 | 0 | 1 | | | | |
| 12 | 3 | 1 | 1 | | | | |
| 13 | 3 | 2 | 1 | | | | |
| 14 | 3 | 3 | 1 | | | | |
| 15 | 3 | 4 | 1 | | | | |
| 16 | 3 | 5 | 1 | | | | |
| 17 | 3 | 0,1 | 1 | | | | |
| 18 | 3 | 2,3 | 1 | | | | |
| 19 | 3 | 4,5 | 1 | | | | |
| 20 | 3 | 0-2 | 1 | | | | |
| 21 | 3 | 3-5 | 1 | | | | |
| 22 | 3 | 0-3 | 1 | | | | |
| 23 | 2 | 0,2 | 1 | | | | |
| 24 | 3 | 0 | 2 | | | | |
| 25 | 3 | 1 | 2 | | | | |
| 26 | 3 | 2 | 2 | | | | |
| 27 | 3 | 3 | 2 | | | | |
| 28 | 3 | 4 | 2 | | | | |
| 29 | 3 | 5 | 2 | | | | |
| 30 | 3 | 6 | 2 | | | | |
| 31 | 3 | 7 | 2 | | | | |
| 32 | 3 | 8 | 2 | | | | |
| 33 | 3 | 9 | 2 | | | | |
| 34 | 3 | 10 | 2 | | | | |
| 35 | 3 | 11 | 2 | | | | |
| 36 | 3 | 0,1 | 2 | | | | |
| 37 | 3 | 2,3 | 2 | | | | |
| 38 | 3 | 4,5 | 2 | | | | |
| 39 | 3 | 6,7 | 2 | | | | |
| 40 | 3 | 8,9 | 2 | | | | |
| 41 | 3 | 10,11 | 2 | | | | |
| 42 | 3 | 0,1,6 | 2 | | | | |
| 43 | 3 | 2,3,8 | 2 | | | | |
| 44 | 3 | 4,5,10 | 2 | | | | |
| 45 | 3 | 0,1,6,7 | 2 | | | | |
| 46 | 3 | 2,3,8,9 | 2 | | | | |
| 47 | 3 | 4,5,10,11 | 2 | | | | |
| 48 | 1 | 0 | 2 | | | | |
| 49 | 1 | 1 | 2 | | | | |
| 50 | 1 | 6 | 2 | | | | |
| 51 | 1 | 7 | 2 | | | | |
| 52 | 1 | 0,1 | 2 | | | | |
| 53 | 1 | 6,7 | 2 | | | | |
| 54 | 2 | 0,1 | 2 | | | | |
| 55 | 2 | 2,3 | 2 | | | | |
| 56 | 2 | 6,7 | 2 | | | | |

| | | | | | | | |
|-------|----------|----------|----------|--|--|--|--|
| 57 | 2 | 8,9 | 2 | | | | |
| 58-63 | Reserved | Reserved | Reserved | | | | |

Table 7.3.1.2.2-4A: Antenna port(s) (1000 + DMRS port), *dmrs-Type=2*, *maxLength=2*

| One codeword: Codeword 0 enabled, Codeword 1 disabled | | | | Two Codewords: Codeword 0 enabled, Codeword 1 enabled | | | |
|---|---|-----------------|------------------------------------|---|---|-----------------|------------------------------------|
| Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols | Value | Number of DMRS CDM group(s) without data | DMRS port(s) | Number of front-load symbols |
| 0 | 1 | 0 | 1 | 0 | 3 | 0-4 | 1 |
| 1 | 1 | 1 | 1 | 1 | 3 | 0-5 | 1 |
| 2 | 1 | 0,1 | 1 | 2 | 2 | 0,1,2,3,6 | 2 |
| 3 | 2 | 0 | 1 | 3 | 2 | 0,1,2,3,6,8 | 2 |
| 4 | 2 | 1 | 1 | 4 | 2 | 0,1,2,3,6,7,8 | 2 |
| 5 | 2 | 2 | 1 | 5 | 2 | 0,1,2,3,6,7,8,9 | 2 |
| 6 | 2 | 3 | 1 | 6-63 | Reserved | Reserved | Reserved |
| 7 | 2 | 0,1 | 1 | | | | |
| 8 | 2 | 2,3 | 1 | | | | |
| 9 | 2 | 0-2 | 1 | | | | |
| 10 | 2 | 0-3 | 1 | | | | |
| 11 | 3 | 0 | 1 | | | | |
| 12 | 3 | 1 | 1 | | | | |
| 13 | 3 | 2 | 1 | | | | |
| 14 | 3 | 3 | 1 | | | | |
| 15 | 3 | 4 | 1 | | | | |
| 16 | 3 | 5 | 1 | | | | |
| 17 | 3 | 0,1 | 1 | | | | |
| 18 | 3 | 2,3 | 1 | | | | |
| 19 | 3 | 4,5 | 1 | | | | |
| 20 | 3 | 0-2 | 1 | | | | |
| 21 | 3 | 3-5 | 1 | | | | |
| 22 | 3 | 0-3 | 1 | | | | |
| 23 | 2 | 0,2 | 1 | | | | |
| 24 | 3 | 0 | 2 | | | | |
| 25 | 3 | 1 | 2 | | | | |
| 26 | 3 | 2 | 2 | | | | |
| 27 | 3 | 3 | 2 | | | | |
| 28 | 3 | 4 | 2 | | | | |
| 29 | 3 | 5 | 2 | | | | |
| 30 | 3 | 6 | 2 | | | | |
| 31 | 3 | 7 | 2 | | | | |
| 32 | 3 | 8 | 2 | | | | |
| 33 | 3 | 9 | 2 | | | | |
| 34 | 3 | 10 | 2 | | | | |
| 35 | 3 | 11 | 2 | | | | |
| 36 | 3 | 0,1 | 2 | | | | |
| 37 | 3 | 2,3 | 2 | | | | |
| 38 | 3 | 4,5 | 2 | | | | |
| 39 | 3 | 6,7 | 2 | | | | |
| 40 | 3 | 8,9 | 2 | | | | |
| 41 | 3 | 10,11 | 2 | | | | |
| 42 | 3 | 0,1,6 | 2 | | | | |
| 43 | 3 | 2,3,8 | 2 | | | | |
| 44 | 3 | 4,5,10 | 2 | | | | |
| 45 | 3 | 0,1,6,7 | 2 | | | | |
| 46 | 3 | 2,3,8,9 | 2 | | | | |
| 47 | 3 | 4,5,10,11 | 2 | | | | |
| 48 | 1 | 0 | 2 | | | | |
| 49 | 1 | 1 | 2 | | | | |
| 50 | 1 | 6 | 2 | | | | |
| 51 | 1 | 7 | 2 | | | | |
| 52 | 1 | 0,1 | 2 | | | | |
| 53 | 1 | 6,7 | 2 | | | | |
| 54 | 2 | 0,1 | 2 | | | | |
| 55 | 2 | 2,3 | 2 | | | | |
| 56 | 2 | 6,7 | 2 | | | | |

| | | | | | | | |
|-------|----------|----------|----------|--|--|--|--|
| 57 | 2 | 8,9 | 2 | | | | |
| 58 | 2 | 0,2,3 | 1 | | | | |
| 59-63 | Reserved | Reserved | Reserved | | | | |

Table 7.3.1.2.2-5: VRB-to-PRB mapping

| Bit field mapped to index | VRB-to-PRB mapping |
|---------------------------|--------------------|
| 0 | Non-interleaved |
| 1 | Interleaved |

Table 7.3.1.2.2-6: Allowed entries for DCI format 1_1, configured by higher layer parameter *ul-AccessConfigListDCI-1-1*

| Entry index | Channel Access Type | The CP extension Text index defined in Clause 5.3.1 of [4, TS 38.211] |
|-------------|--|---|
| 0 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 |
| 1 | Type2C-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 |
| 2 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 0 |
| 3 | Type2B-ULChannelAccess defined in [clause 4.2.1.2.3 in 37.213] | 2 |
| 4 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 0 |
| 5 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 1 |
| 6 | Type2A-ULChannelAccess defined in [clause 4.2.1.2.1 in 37.213] | 3 |
| 7 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 0 |
| 8 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 1 |
| 9 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 2 |
| 10 | Type1-ULChannelAccess defined in [clause 4.2.1.1 in 37.213] | 3 |

7.3.1.2.3 Format 1_2

DCI format 1_2 is used for the scheduling of PDSCH in one cell.

The following information is transmitted by means of the DCI format 1_2 with CRC scrambled by C-RNTI or CS-RNTI or MCS-C-RNTI:

- Identifier for DCI formats – 1 bits
 - The value of this bit field is always set to 1, indicating a DL DCI format.
- Carrier indicator – 0, 1, 2 or 3 bits determined by higher layer parameter *carrierIndicatorSizeDCI-1-2*, as defined in Clause 10.1 of [5, TS38.213].
- Bandwidth part indicator – 0, 1 or 2 bits as determined by the number of DL BWPs $n_{BWP,RRC}$ configured by higher layers, excluding the initial DL bandwidth part. The bitwidth for this field is determined as $\lceil \log_2(n_{BWP}) \rceil$ bits, where
 - $n_{BWP} = n_{BWP,RRC} + 1$ if $n_{BWP,RRC} \leq 3$, in which case the bandwidth part indicator is equivalent to the ascending order of the higher layer parameter *BWP-Id*;
 - otherwise $n_{BWP} = n_{BWP,RRC}$, in which case the bandwidth part indicator is defined in Table 7.3.1.1.2-1;

If a UE does not support active BWP change via DCI, the UE ignores this bit field.

- Frequency domain resource assignment – number of bits determined by the following:
 - N_{RBG} bits if only resource allocation type 0 is configured, where N_{RBG} is defined in Clause 5.1.2.2.1 of [6, TS 38.214];
 - $\lceil \log_2(N_{RBG,K2}(N_{RBG,K2} + 1)/2) \rceil$ bits if only resource allocation type 1 is configured, or $\max(\lceil \log_2(N_{RBG,K2}(N_{RBG,K2} + 1)/2) \rceil, N_{RBG}) + 1$ bits if *resourceAllocationDCI-1-2-r16* is configured as

'dynamicSwitch', where $N_{RBG,K2} = \left[\left(N_{RB}^{DL,BWP} + (N_{DL,BWP}^{start} \bmod K2) \right) / K2 \right]$, $N_{RB}^{DL,BWP}$ is the size of the active DL bandwidth part, $N_{DL,BWP}^{start}$ is defined as in clause 4.4.4.4 of [4, TS 38.211] and $K2$ is determined by higher layer parameter *resourceAllocationType1GranularityDCI-1-2*. If the higher layer parameter *resourceAllocationType1GranularityDCI-1-2* is not configured, $K2$ is equal to 1.

- If *resourceAllocationDCI-1-2-r16* is configured as 'dynamicSwitch', the MSB bit is used to indicate resource allocation type 0 or resource allocation type 1, where the bit value of 0 indicates resource allocation type 0 and the bit value of 1 indicates resource allocation type 1.
- For resource allocation type 0, the N_{RBG} LSBs provide the resource allocation as defined in Clause 5.1.2.2.1 of [6, TS 38.214].
- For resource allocation type 1, the $\lceil \log_2(N_{RBG,K2}(N_{RBG,K2} + 1)/2) \rceil$ LSBs provide the resource allocation as defined in Clause 5.1.2.2.2 of [6, TS 38.214]

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part and if *resourceAllocationDCI-1-2-r16* is configured as 'dynamicSwitch' for the indicated bandwidth part, the UE assumes resource allocation type 0 for the indicated bandwidth part if the bitwidth of the "Frequency domain resource assignment" field of the active bandwidth part is smaller than the bitwidth of the "Frequency domain resource assignment" field of the indicated bandwidth part.

- Time domain resource assignment – 0, 1, 2, 3, or 4 bits as defined in Clause 5.1.2.1 of [6, TS 38.214]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *pdsch-TimeDomainAllocationListDCI-1-2* if the higher layer parameter is configured, or I is the number of entries in the higher layer parameter *pdsch-TimeDomainAllocationList* if the higher layer parameter *pdsch-TimeDomainAllocationListDCI-1-2* is not configured; otherwise I is the number of entries in the default table.
- VRB-to-PRB mapping – 0 or 1 bit:
 - 0 bit if the higher layer parameter *vrB-ToPRB-InterleaverDCI-1-2* is not configured;
 - 1 bit according to Table 7.3.1.2.2-5 otherwise, only applicable to resource allocation type 1, as defined in Clause 7.3.1.6 of [4, TS 38.211].
- PRB bundling size indicator – 0 bit if the higher layer parameter *prB-BundlingTypeDCI-1-2* is not configured or is set to 'static', or 1 bit if the higher layer parameter *prB-BundlingTypeDCI-1-2* is set to 'dynamic' according to Clause 5.1.2.3 of [6, TS 38.214].
- Rate matching indicator – 0, 1, or 2 bits according to higher layer parameters *rateMatchPatternGroup1DCI-1-2* and *rateMatchPatternGroup2DCI-1-2*, where the MSB is used to indicate *rateMatchPatternGroup1DCI-1-2* and the LSB is used to indicate *rateMatchPatternGroup2DCI-1-2* when there are two groups.
- ZP CSI-RS trigger – 0, 1, or 2 bits as defined in Clause 5.1.4.2 of [6, TS 38.214]. The bitwidth for this field is determined as $\lceil \log_2(n_{ZP} + 1) \rceil$ bits, where n_{ZP} is the number of aperiodic ZP CSI-RS resource sets configured by higher layer parameter *aperiodicZP-CSI-RS-ResourceSetsToAddModListDCI-1-2*.
- Modulation and coding scheme – 5 bits as defined in Clause 5.1.3.1 of [6, TS 38.214]
- New data indicator – 1 bit
- Redundancy version – 0, 1 or 2 bits determined by higher layer parameter *numberOfBitsForRV-DCI-1-2*
 - If 0 bit is configured, rv_{id} to be applied is 0;
 - 1 bit according to Table 7.3.1.2.3-1;
 - 2 bits according to Table 7.3.1.1.1-2.
- HARQ process number – 0, 1, 2, 3 or 4 bits determined by higher layer parameter *harq-ProcessNumberSizeDCI-1-2*
- Downlink assignment index – 0, 1, 2 or 4 bits
 - 0 bit if the higher layer parameter *downlinkAssignmentIndexDCI-1-2* is not configured;

- 1, 2 or 4 bits determined by higher layer parameter *downlinkAssignmentIndexDCI-1-2* otherwise,
- 4 bits if more than one serving cell are configured in the DL and the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic*, where the 2 MSB bits are the counter DAI and the 2 LSB bits are the total DAI
- 4 bits if only one serving cell is configured in the DL and the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic*, and the UE is not provided *coresetPoolIndex* or is provided *coresetPoolIndex* with value 0 for one or more first CORESETs and is provided *coresetPoolIndex* with value 1 for one or more second CORESETs, and is provided *ackNackFeedbackMode = joint*, where the 2 MSB bits are the counter DAI and the 2 LSB bits are the total DAI.
- 1 or 2 bits if only one serving cell is configured in the DL and the higher layer parameter *pdsch-HARQ-ACK-Codebook=dynamic*, when the UE is not configured with *coresetPoolIndex* or the value of *coresetPoolIndex* is the same for all CORESETs if *coresetPoolIndex* is provided or the UE is not configured with *ackNackFeedbackMode = joint*, where the 1 bit or 2 bits are the counter DAI.

If the UE is configured with a PUCCH-SCell, the number of serving cells is determined within a PUCCH group.

If the UE is configured with a PUCCH-SCell, *pdsch-HARQ-ACK-Codebook* is replaced by *pdsch-HARQ-ACK-Codebook-secondaryPUCCHgroup-r16* if present for the secondary PUCCH group.

If higher layer parameter *priorityIndicatorDCI-1-2* is configured, if the bit width of the Downlink assignment index in DCI format 1_2 for one HARQ-ACK codebook is not equal to that of the Downlink assignment index in DCI format 1_2 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller Downlink assignment index until the bit width of the Downlink assignment index in DCI format 1_2 for the two HARQ-ACK codebooks are the same.

- TPC command for scheduled PUCCH – 2 bits as defined in Clause 7.2.1 of [5, TS 38.213]
- PUCCH resource indicator – 0 or 1 or 2 or 3 bits determined by higher layer parameter *numberOfBitsForPUCCH-ResourceIndicatorDCI-1-2*
- PDSCH-to-HARQ_feedback timing indicator – 0, 1, 2, or 3 bits as defined in Clause 9.2.3 of [5, TS 38.213]. The bitwidth for this field is determined as $\lceil \log_2(I) \rceil$ bits, where I is the number of entries in the higher layer parameter *DL-DataToUL-ACK-DCI-1-2*.

If higher layer parameter *priorityIndicatorDCI-1-2* is configured, if the bit width of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_2 for one HARQ-ACK codebook is not equal to that of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_2 for the other HARQ-ACK codebook, a number of most significant bits with value set to '0' are inserted to smaller PDSCH-to-HARQ_feedback timing indicator until the bit width of the PDSCH-to-HARQ_feedback timing indicator in DCI format 1_2 for the two HARQ-ACK codebooks are the same.

- Antenna port(s) – 0, 4, 5, or 6 bits
 - 0 bit if higher layer parameter *antennaPortsFieldPresenceDCI-1-2* is not configured;
 - Otherwise 4, 5 or 6 bits as defined by Tables 7.3.1.2.2-1/2/3/4, where the number of CDM groups without data of values 1, 2, and 3 refers to CDM groups {0}, {0,1}, and {0, 1,2} respectively. The antenna ports $\{p_0, \dots, p_{v-1}\}$ shall be determined according to the ordering of DMRS port(s) given by Tables 7.3.1.2.2-1/2/3/4. If a UE is configured with both *dmrs-DownlinkForPDSCH-MappingTypeA-DCI-1-2* and *dmrs-DownlinkForPDSCH-MappingTypeB-DCI-1-2* and is configured with higher layer parameter *antennaPortsFieldPresenceDCI-1-2*, the bitwidth of this field equals $\max\{x_A, x_B\}$, where x_A is the "Antenna ports" bitwidth derived according to *dmrs-DownlinkForPDSCH-MappingTypeA-DCI-1-2* and x_B is the "Antenna ports" bitwidth derived according to *dmrs-DownlinkForPDSCH-MappingTypeB-DCI-1-2*. A number of $|x_A - x_B|$ zeros are padded in the MSB of this field, if the mapping type of the PDSCH corresponds to the smaller value of x_A and x_B .

If a UE is not configured with higher layer parameter *antennaPortsFieldPresenceDCI-1-2*, antenna port(s) are defined assuming bit field index value 0 in Tables 7.3.1.2.2-1/2/3/4.

- Transmission configuration indication – 0 bit if higher layer parameter *tci-PresentDCI-1-2* is not configured; otherwise 1 or 2 or 3 bits determined by higher layer parameter *tci-PresentDCI-1-2* as defined in Clause 5.1.5 of [6, TS38.214].

If "Bandwidth part indicator" field indicates a bandwidth part other than the active bandwidth part,

- if the higher layer parameter *tci-PresentDCI-1-2* is not configured for the CORESET used for the PDCCH carrying the DCI format 1_2,
 - the UE assumes *tci-PresentDCI-1-2* is not configured for all CORESETs in the indicated bandwidth part;
- otherwise,
 - the UE assumes *tci-PresentDCI-1-2* is configured for all CORESETs in the indicated bandwidth part with the same value configured for the CORESET used for the PDCCH carrying the DCI format 1_2.
- SRS request – 0, 1, 2 or 3 bits
 - 0 bit if the higher layer parameter *srs-RequestDCI-1-2* is not configured;
 - 1 bit as defined by Table 7.3.1.1.3-1 if the higher layer parameter *srs-RequestDCI-1-2* = 1 and for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell;
 - 2 bits if the higher layer parameter *srs-RequestDCI-1-2* = 1 and for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell, where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second bit is defined by Table 7.3.1.1.3-1;
 - 2 bits as defined by Table 7.3.1.1.2-24 if the higher layer parameter *srs-RequestDCI-1-2* = 2 and for UEs not configured with *supplementaryUplink* in *ServingCellConfig* in the cell;
 - 3 bits if the higher layer parameter *srs-RequestDCI-1-2* = 2 and for UEs configured with *supplementaryUplink* in *ServingCellConfig* in the cell, where the first bit is the non-SUL/SUL indicator as defined in Table 7.3.1.1.1-1 and the second and third bits are defined by Table 7.3.1.1.2-24;
- DMRS sequence initialization – 0 or 1 bit
 - 0 bit if the higher layer parameter *dmrs-SequenceInitializationDCI-1-2* is not configured;
 - 1 bit otherwise.
- Priority indicator – 0 bit if higher layer parameter *priorityIndicatorDCI-1-2* is not configured; otherwise 1 bit as defined in Clause 9 in [5, TS 38.213].

If DCI formats 1_2 are monitored in multiple search spaces associated with multiple CORESETs in a BWP for scheduling the same serving cell, zeros shall be appended until the payload size of the DCI formats 1_2 monitored in the multiple search spaces equal to the maximum payload size of the DCI format 1_2 monitored in the multiple search spaces.

Table 7.3.1.2.3-1: Redundancy version

| Value of the Redundancy version field | Value of rv_{id} to be applied |
|---------------------------------------|----------------------------------|
| 0 | 0 |
| 1 | 3 |

7.3.1.3 DCI formats for other purposes

7.3.1.3.1 Format 2_0

DCI format 2_0 is used for notifying the slot format, COT duration, available RB set, and search space set group switching.

The following information is transmitted by means of the DCI format 2_0 with CRC scrambled by SFI-RNTI:

- If the higher layer parameter *slotFormatCombToAddModList* is configured,
 - Slot format indicator 1, Slot format indicator 2, ..., Slot format indicator *N*,
- If the higher layer parameter *availableRB-SetsToAddModList* is configured,
 - Available RB set Indicator 1, Available RB set Indicator 2, ..., Available RB set Indicator *NI*,
- If the higher layer parameter *co-DurationsPerCellToAddModList* is configured
 - COT duration indicator 1, COT duration indicator 2, ..., COT duration indicator *N2*.
- If the higher layer parameter *switchTriggerToAddModList* is configured
 - Search space set group switching flag 1, Search space set group switching flag 2, ..., Search space set group switching flag *M*.

The size of DCI format 2_0 is configurable by higher layers up to 128 bits, according to Clause 11.1.1 of [5, TS 38.213].

7.3.1.3.2 Format 2_1

DCI format 2_1 is used for notifying the PRB(s) and OFDM symbol(s) where UE may assume no transmission is intended for the UE.

The following information is transmitted by means of the DCI format 2_1 with CRC scrambled by INT-RNTI:

- Pre-emption indication 1, Pre-emption indication 2, ..., Pre-emption indication *N*.

The size of DCI format 2_1 is configurable by higher layers up to 126 bits, according to Clause 11.2 of [5, TS 38.213]. Each pre-emption indication is 14 bits.

7.3.1.3.3 Format 2_2

DCI format 2_2 is used for the transmission of TPC commands for PUCCH and PUSCH.

The following information is transmitted by means of the DCI format 2_2 with CRC scrambled by TPC-PUSCH-RNTI or TPC-PUCCH-RNTI:

- block number 1, block number 2, ..., block number *N*

The parameter *tpc-PUSCH* or *tpc-PUCCH* provided by higher layers determines the index to the block number for an UL of a cell, with the following fields defined for each block:

- Closed loop indicator – 0 or 1 bit.
 - For DCI format 2_2 with TPC-PUSCH-RNTI, 0 bit if the UE is not configured with high layer parameter *twoPUSCH-PC-AdjustmentStates*, in which case UE assumes each block in the DCI format 2_2 is of 2 bits; 1 bit otherwise, in which case UE assumes each block in the DCI format 2_2 is of 3 bits;
 - For DCI format 2_2 with TPC-PUCCH-RNTI, 0 bit if the UE is not configured with high layer parameter *twoPUCCH-PC-AdjustmentStates*, in which case UE assumes each block in the DCI format 2_2 is of 2 bits; 1 bit otherwise, in which case UE assumes each block in the DCI format 2_2 is of 3 bits;
- TPC command – 2 bits

The number of information bits in format 2_2 shall be equal to or less than the payload size of format 1_0 monitored in common search space in the same serving cell. If the number of information bits in format 2_2 is less than the payload size of format 1_0 monitored in common search space in the same serving cell, zeros shall be appended to format 2_2 until the payload size equals that of format 1_0 monitored in common search space in the same serving cell.

7.3.1.3.4 Format 2_3

DCI format 2_3 is used for the transmission of a group of TPC commands for SRS transmissions by one or more UEs. Along with a TPC command, a SRS request may also be transmitted.

The following information is transmitted by means of the DCI format 2_3 with CRC scrambled by TPC-SRS-RNTI:

- block number 1, block number 2, ..., block number B

where the starting position of a block is determined by the parameter *startingBitOfFormat2-3* or *startingBitOfFormat2-3SUL-v1530* provided by higher layers for the UE configured with the block.

If the UE is configured with higher layer parameter *srs-TPC-PDCCH-Group = typeA* for an UL without PUCCH and PUSCH or an UL on which the SRS power control is not tied with PUSCH power control, one block is configured for the UE by higher layers, with the following fields defined for the block:

- SRS request – 0 or 2 bits. The presence of this field is according to the definition in Clause 11.4 of [5, TS38.213]. If present, this field is interpreted as defined by Table 7.3.1.1.2-24.
- TPC command number 1, TPC command number 2, ..., TPC command number N , where each TPC command applies to a respective UL carrier provided by higher layer parameter *cc-IndexInOneCC-Set*

If the UE is configured with higher layer parameter *srs-TPC-PDCCH-Group = typeB* for an UL without PUCCH and PUSCH or an UL on which the SRS power control is not tied with PUSCH power control, one block or more blocks is configured for the UE by higher layers where each block applies to an UL carrier, with the following fields defined for each block:

- SRS request – 0 or 2 bits. The presence of this field is according to the definition in Clause 11.4 of [5, TS38.213]. If present, this field is interpreted as defined by Table 7.3.1.1.2-24.
- TPC command – 2 bits

The number of information bits in format 2_3 shall be equal to or less than the payload size of format 1_0 monitored in common search space in the same serving cell. If the number of information bits in format 2_3 is less than the payload size of format 1_0 monitored in common search space in the same serving cell, zeros shall be appended to format 2_3 until the payload size equals that of format 1_0 monitored in common search space in the same serving cell.

7.3.1.3.5 Format 2_4

DCI format 2_4 is used for notifying the PRB(s) and OFDM symbol(s) where UE cancels the corresponding UL transmission from the UE according to Clause 11.2A of [5, TS 38.213].

The following information is transmitted by means of the DCI format 2_4 with CRC scrambled by ci-RNTI:

- Cancellation indication 1, Cancellation indication 2, ..., Cancellation indication N .

The size of DCI format 2_4 is configurable by higher layers parameter *dci-PayloadSizeForCI* up to 126 bits, according to Clause 11.2A of [5, TS 38.213]. The number of bits for each cancellation indication is configurable by higher layer parameter *ci-PayloadSize*. For a UE, there is at most one cancellation indication for an UL carrier.

7.3.1.3.6 Format 2_5

DCI format 2_5 is used for notifying the availability of soft resources as defined in Clause 9.3.1 of [10, TS 38.473]

The following information is transmitted by means of the DCI format 2_5 with CRC scrambled by AI-RNTI:

- Availability indicator 1, Availability indicator 2, ..., Availability indicator N .

The size of DCI format 2_5 is configurable by higher layers up to 128 bits, according to Clause 14 of [5, TS 38.213].

7.3.1.3.7 Format 2_6

DCI format 2_6 is used for notifying the power saving information outside DRX Active Time for one or more UEs.

The following information is transmitted by means of the DCI format 2_6 with CRC scrambled by PS-RNTI:

- block number 1, block number 2, ..., block number N

where the starting position of a block is determined by the parameter *ps-PositionDCI-2-6* provided by higher layers for the UE configured with the block.

If the UE is configured with higher layer parameter *ps-RNTI* and *dci-Format2-6*, one block is configured for the UE by higher layers, with the following fields defined for the block:

- Wake-up indication - 1 bit
- SCell dormancy indication – 0 bit if higher layer parameter *dormancyGroupOutsideActiveTime* is not configured; otherwise 1, 2, 3, 4 or 5 bits bitmap determined according to higher layer parameter *dormancyGroupOutsideActiveTime*, where each bit corresponds to one of the SCell group(s) configured by higher layers parameter *dormancyGroupOutsideActiveTime*, with MSB to LSB of the bitmap corresponding to the first to last configured SCell group.

The size of DCI format 2_6 is indicated by the higher layer parameter *sizeDCI-2-6*, according to Clause 10.3 of [5, TS 38.213].

7.3.1.4 DCI formats for scheduling of sidelink

7.3.1.4.1 Format 3_0

DCI format 3_0 is used for scheduling of NR PSCCH and NR PSSCH in one cell.

The following information is transmitted by means of the DCI format 3_0 with CRC scrambled by SL-RNTI or SL-CS-RNTI:

- Resource pool index $-\lceil \log_2 I \rceil$ bits, where I is the number of resource pools for transmission configured by the higher layer parameter *sl-TxPoolScheduling*.
- Time gap – 3 bits determined by higher layer parameter *sl-DCI-ToSL-Trans*, as defined in clause 8.1.2.1 of [6, TS 38.214]
- HARQ process number – 4 bits.
- New data indicator – 1 bit.
- Lowest index of the subchannel allocation to the initial transmission $-\lceil \log_2 (N_{\text{subChannel}}^{\text{SL}}) \rceil$ bits as defined in clause 8.1.2.2 of [6, TS 38.214]
- SCI format 1-A fields according to clause 8.3.1.1:
 - Frequency resource assignment.
 - Time resource assignment.
- PSFCH-to-HARQ feedback timing indicator $-\lceil \log_2 N_{\text{fb,timing}} \rceil$ bits, where $N_{\text{fb,timing}}$ is the number of entries in the higher layer parameter *sl-PSFCH-ToPUCCH*, as defined in clause 16.5 of [5, TS 38.213]
- PUCCH resource indicator – 3 bits as defined in clause 16.5 of [5, TS 38.213].
- Configuration index – 0 bit if the UE is not configured to monitor DCI format 3_0 with CRC scrambled by SL-CS-RNTI; otherwise 3 bits as defined in clause 8.1.2 of [6, TS 38.214]. If the UE is configured to monitor DCI format 3_0 with CRC scrambled by SL-CS-RNTI, this field is reserved for DCI format 3_0 with CRC scrambled by SL-RNTI.
- Counter sidelink assignment index – 2 bits
 - 2 bits as defined in clause 16.5.2 of [5, TS 38.213] if the UE is configured with *pdsch-HARQ-ACK-Codebook = dynamic*
 - 2 bits as defined in clause 16.5.1 of [5, TS 38.213] if the UE is configured with *pdsch-HARQ-ACK-Codebook = semi-static*
- Padding bits, if required

If multiple transmit resource pools are provided in *sl-TxPoolScheduling*, zeros shall be appended to the DCI format 3_0 until the payload size is equal to the size of a DCI format 3_0 given by a configuration of the transmit resource pool resulting in the largest number of information bits for DCI format 3_0.

If the UE is configured to monitor DCI format 3_1 and the number of information bits in DCI format 3_0 is less than the payload of DCI format 3_1, zeros shall be appended to DCI format 3_0 until the payload size equals that of DCI format 3_1.

7.3.1.4.2 Format 3_1

DCI format 3_1 is used for scheduling of LTE PSCCH and LTE PSSCH in one cell.

The following information is transmitted by means of the DCI format 3_1 with CRC scrambled by SL Semi-Persistent Scheduling V-RNTI:

- Timing offset – 3 bits determined by higher layer parameter *sl-TimeOffsetEUTRA*, as defined in clause 16.6 of [5, TS 38.213]
- Carrier indicator – 3 bits as defined in 5.3.3.1.9A of [11, TS 36.212].
- Lowest index of the subchannel allocation to the initial transmission - $\lceil \log_2(N_{\text{subchannel}}^{\text{SL}}) \rceil$ bits as defined in 5.3.3.1.9A of [11, TS 36.212].
- Frequency resource location of initial transmission and retransmission, as defined in 5.3.3.1.9A of [11, TS 36.212]
- Time gap between initial transmission and retransmission, as defined in 5.3.3.1.9A of [11, TS 36.212]
- SL index – 2 bits as defined in 5.3.3.1.9A of [11, TS 36.212]
- SL SPS configuration index – 3 bits as defined in clause 5.3.3.1.9A of [11, TS 36.212].
- Activation/release indication – 1 bit as defined in clause 5.3.3.1.9A of [11, TS 36.212].

If the UE is configured to monitor DCI format 3_0 and the number of information bits in DCI format 3_1 is less than the payload of DCI format 3_0, zeros shall be appended to DCI format 3_1 until the payload size equals that of DCI format 3_0.

7.3.2 CRC attachment

Error detection is provided on DCI transmissions through a Cyclic Redundancy Check (CRC).

The entire payload is used to calculate the CRC parity bits. Denote the bits of the payload by $a_0, a_1, a_2, a_3, \dots, a_{A-1}$, and the parity bits by $p_0, p_1, p_2, p_3, \dots, p_{L-1}$, where A is the payload size and L is the number of parity bits. Let $a'_0, a'_1, a'_2, a'_3, \dots, a'_{A+L-1}$ be a bit sequence such that $a'_i = 1$ for $i = 0, 1, \dots, L-1$ and $a'_i = a_{i-L}$ for $i = L, L+1, \dots, A+L-1$. The parity bits are computed with input bit sequence $a'_0, a'_1, a'_2, a'_3, \dots, a'_{A+L-1}$ and attached according to Clause 5.1 by setting L to 24 bits and using the generator polynomial $g_{\text{CRC24C}}(D)$. The output bit $b_0, b_1, b_2, b_3, \dots, b_{K-1}$ is

$$b_k = a_k \quad \text{for } k = 0, 1, 2, \dots, A-1$$

$$b_k = p_{k-A} \quad \text{for } k = A, A+1, A+2, \dots, A+L-1,$$

where $K = A + L$.

After attachment, the CRC parity bits are scrambled with the corresponding RNTI $x_{\text{mti},0}, x_{\text{mti},1}, \dots, x_{\text{mti},15}$, where $x_{\text{mti},0}$ corresponds to the MSB of the RNTI, to form the sequence of bits $c_0, c_1, c_2, c_3, \dots, c_{K-1}$. The relation between c_k and b_k is:

$$c_k = b_k \quad \text{for } k = 0, 1, 2, \dots, A+7$$

$$c_k = (b_k + x_{\text{mti},k-A-8}) \bmod 2 \quad \text{for } k = A+8, A+9, A+10, \dots, A+23.$$

7.3.3 Channel coding

Information bits are delivered to the channel coding block. They are denoted by $c_0, c_1, c_2, c_3, \dots, c_{K-1}$, where K is the number of bits, and they are encoded via Polar coding according to Clause 5.3.1, by setting $n_{\max} = 9$, $I_{IL} = 1$, $n_{PC} = 0$, and $n_{PC}^{wm} = 0$.

After encoding the bits are denoted by $d_0, d_1, d_2, d_3, \dots, d_{N-1}$, where N is the number of coded bits.

7.3.4 Rate matching

The input bit sequence to rate matching is $d_0, d_1, d_2, \dots, d_{N-1}$.

Rate matching is performed according to Clause 5.4.1 by setting $I_{BL} = 0$.

The output bit sequence after rate matching is denoted as $f_0, f_1, f_2, \dots, f_{E-1}$.

8 Sidelink transport channels and control information

8.1 Sidelink broadcast channel

The processing for SL-BCH transport channel follows the BCH according to clause 7.1, with the following changes:

- In Clause 7.1, 'maximum of one transport block every 80ms' is replaced with 'maximum of one transport block'.
- Clause 7.1.1 for PBCH payload generation is not performed.
- Clause 7.1.2 for scrambling is not performed.
- In clause 7.1.5, the rate matching output sequence length $E = 1386$ when higher layer parameter *cyclicPrefix* is configured, otherwise, $E = 1782$.

8.1.1 (void)

8.2 Sidelink shared channel

The processing for SL-SCH transport channel follows the UL-SCH according to clause 6.2, with the following changes:

- Rate matching of SL-SCH follows the rate matching according to clause 6.2.5 by setting $I_{LBRM} = 0$
- Clause 6.2.7 is replaced by clause 8.2.1

8.2.1 Data and control multiplexing

Denote the coded bits for SL-SCH as $g_0^{SL-SCH}, g_1^{SL-SCH}, g_2^{SL-SCH}, g_3^{SL-SCH}, \dots, g_{G^{SL-SCH}-1}^{SL-SCH}$.

Denote the coded bits for the 2nd-stage SCI, as $g_0^{SCI2}, g_1^{SCI2}, g_2^{SCI2}, g_3^{SCI2}, \dots, g_{G^{SCI2}-1}^{SCI2}$.

Denote the multiplexed data and control coded bit sequence as g_0, g_1, \dots, g_{G-1} , where G is the total number of coded bits for transmission.

Assuming that N_L is the number of layers onto which the SL-SCH transport block is mapped, the multiplexed data and control coded bit sequence g_0, g_1, \dots, g_{G-1} is obtained as follows:

Denote Q_m^{SCI2} is modulation order of the 2nd-stage SCI.

if $N_L = 1$,

```

for  $i = 0$  to  $G^{SCI2} + G^{SL-SCH} - 1$ 
  if  $0 \leq i < G^{SCI2}$ 
     $g_i = g_i^{SCI2}$ 
  end if
  if  $G^{SCI2} \leq i \leq G^{SCI2} + G^{SL-SCH} - 1$ 
     $g_i = g_{i-G^{SCI2}}^{SL-SCH}$ 
  end if
end for
end if
if  $N_L = 2$ ,
  let  $M_{count,SCI2}^{RE} = G^{SCI2} / Q_m^{SCI2}$ 
  set  $m_{count}^{RE} = 0$ 
  for  $i = 0$  to  $M_{count,SCI2}^{RE} - 1$ 
    for  $v = 0$  to  $N_L - 1$ 
      for  $q = 0$  to  $Q_m^{SCI2} - 1$ 
        if  $v = 0$ 
           $g_{m_{count}^{RE}} = g_{i \cdot Q_m^{SCI2} + q}^{SCI2}$ 
        else
           $g_{m_{count}^{RE}} = x$  // placeholder bit
        end if
         $m_{count}^{RE} = m_{count}^{RE} + 1$ 
      end for
    end for
  end for
end for
for  $i = 0$  to  $G^{SL-SCH} - 1$ 
   $g_{m_{count}^{RE}} = g_i^{SL-SCH}$ 
   $m_{count}^{RE} = m_{count}^{RE} + 1$ 
end for
end if

```

8.3 Sidelink control information on PSCCH

SCI carried on PSCCH is a 1st-stage SCI, which transports sidelink scheduling information.

8.3.1 1st-stage SCI formats

The fields defined in each of the 1st-stage SCI formats below are mapped to the information bits a_0 to a_{A-1} as follows:

Each field is mapped in the order in which it appears in the description, with the first field mapped to the lowest order information bit a_0 and each successive field mapped to higher order information bits. The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to a_0 .

8.3.1.1 SCI format 1-A

SCI format 1-A is used for the scheduling of PSSCH and 2nd-stage-SCI on PSSCH

The following information is transmitted by means of the SCI format 1-A:

- Priority – 3 bits as specified in clause 5.4.3.3 of [12, TS 23.287] and clause 5.22.1.3.1 of [8, TS 38.321].
- Frequency resource assignment – $\left\lceil \log_2 \left(\frac{N_{\text{subChannel}}^{\text{SL}} (N_{\text{subChannel}}^{\text{SL}} + 1)}{2} \right) \right\rceil$ bits when the value of the higher layer parameter $sl\text{-}MaxNumPerReserve$ is configured to 2; otherwise $\left\lceil \log_2 \left(\frac{N_{\text{subChannel}}^{\text{SL}} (N_{\text{subChannel}}^{\text{SL}} + 1) (2N_{\text{subChannel}}^{\text{SL}} + 1)}{6} \right) \right\rceil$ bits when the value of the higher layer parameter $sl\text{-}MaxNumPerReserve$ is configured to 3, as defined in clause 8.1.5 of [6, TS 38.214].
- Time resource assignment – 5 bits when the value of the higher layer parameter $sl\text{-}MaxNumPerReserve$ is configured to 2; otherwise 9 bits when the value of the higher layer parameter $sl\text{-}MaxNumPerReserve$ is configured to 3, as defined in clause 8.1.5 of [6, TS 38.214].
- Resource reservation period – $\lceil \log_2 N_{\text{rsv_period}} \rceil$ bits as defined in clause 16.4 of [5, TS 38.213], where $N_{\text{rsv_period}}$ is the number of entries in the higher layer parameter $sl\text{-}ResourceReservePeriodList$, if higher layer parameter $sl\text{-}MultiReserveResource$ is configured; 0 bit otherwise.
- DMRS pattern – $\lceil \log_2 N_{\text{pattern}} \rceil$ bits as defined in clause 8.4.1.1.2 of [4, TS 38.211], where N_{pattern} is the number of DMRS patterns configured by higher layer parameter $sl\text{-}PSSCH\text{-}DMRS\text{-}TimePatternList$.
- 2nd-stage SCI format – 2 bits as defined in Table 8.3.1.1-1.
- Beta_offset indicator – 2 bits as provided by higher layer parameter $sl\text{-}BetaOffsets2ndSCI$ and Table 8.3.1.1-2.
- Number of DMRS port – 1 bit as defined in Table 8.3.1.1-3.
- Modulation and coding scheme – 5 bits as defined in clause 8.1.3 of [6, TS 38.214].
- Additional MCS table indicator – as defined in clause 8.1.3.1 of [6, TS 38.214]: 1 bit if one MCS table is configured by higher layer parameter $sl\text{-}Additional\text{-}MCS\text{-}Table$; 2 bits if two MCS tables are configured by higher layer parameter $sl\text{-}Additional\text{-}MCS\text{-}Table$; 0 bit otherwise.
- PSFCH overhead indication – 1 bit as defined clause 8.1.3.2 of [6, TS 38.214] if higher layer parameter $sl\text{-}PSFCH\text{-}Period = 2$ or 4; 0 bit otherwise.
- Reserved – a number of bits as determined by higher layer parameter $sl\text{-}NumReservedBits$, with value set to zero.

Table 8.3.1.1-1: 2nd-stage SCI formats

| Value of 2nd-stage SCI format field | 2nd-stage SCI format |
|-------------------------------------|----------------------|
| 00 | SCI format 2-A |
| 01 | SCI format 2-B |
| 10 | Reserved |
| 11 | Reserved |

Table 8.3.1.1-2: Mapping of Beta_offset indicator values to indexes in Table 9.3-2 of [5, TS38.213]

| Value of Beta_offset indicator | Beta_offset index in Table 9.3-2 of [5, TS38.213] |
|--------------------------------|--|
| 00 | 1st index provided by higher layer parameter <i>sl-BetaOffsets2ndSCI</i> |
| 01 | 2nd index provided by higher layer parameter <i>sl-BetaOffsets2ndSCI</i> |
| 10 | 3rd index provided by higher layer parameter <i>sl-BetaOffsets2ndSCI</i> |
| 11 | 4th index provided by higher layer parameter <i>sl-BetaOffsets2ndSCI</i> |

Table 8.3.1.1-3: Number of DMRS port(s)

| Value of the Number of DMRS port field | Antenna ports |
|--|---------------|
| 0 | 1000 |
| 1 | 1000 and 1001 |

8.3.2 CRC attachment

CRC attachment is performed according to clause 7.3.2 except that scrambling is not performed.

8.3.3 Channel coding

Channel coding is performed according to clause 7.3.3.

8.3.4 Rate Matching

Rate matching is performed according to clause 7.3.4.

8.4 Sidelink control information on PSSCH

SCI carried on PSSCH is a 2nd-stage SCI, which transports sidelink scheduling information.

8.4.1 2nd-stage SCI formats

The fields defined in each of the 2nd-stage SCI formats below are mapped to the information bits a_0 to a_{A-1} as follows:

Each field is mapped in the order in which it appears in the description, with the first field mapped to the lowest order information bit a_0 and each successive field mapped to higher order information bits. The most significant bit of each field is mapped to the lowest order information bit for that field, e.g. the most significant bit of the first field is mapped to a_0 .

8.4.1.1 SCI format 2-A

SCI format 2-A is used for the decoding of PSSCH, with HARQ operation when HARQ-ACK information includes ACK or NACK, when HARQ-ACK information includes only NACK, or when there is no feedback of HARQ-ACK information.

The following information is transmitted by means of the SCI format 2-A:

- HARQ process number – 4 bits.
- New data indicator – 1 bit.
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2.
- Source ID – 8 bits as defined in clause 8.1 of [6, TS 38.214].

- Destination ID – 16 bits as defined in clause 8.1 of [6, TS 38.214].
- HARQ feedback enabled/disabled indicator – 1 bit as defined in clause 16.3 of [5, TS 38.213].
- Cast type indicator – 2 bits as defined in Table 8.4.1.1-1 and in clause 8.1 of [6, TS 38.214].
- CSI request – 1 bit as defined in clause 8.2.1 of [6, TS 38.214] and in clause 8.1 of [6, TS 38.214].

Table 8.4.1.1-1: Cast type indicator

| Value of Cast type indicator | Cast type |
|------------------------------|---|
| 00 | Broadcast |
| 01 | Groupcast when HARQ-ACK information includes ACK or NACK |
| 10 | Unicast |
| 11 | Groupcast when HARQ-ACK information includes only NACK |

8.4.1.2 SCI format 2-B

SCI format 2-B is used for the decoding of PSSCH, with HARQ operation when HARQ-ACK information includes only NACK, or when there is no feedback of HARQ-ACK information.

The following information is transmitted by means of the SCI format 2-B:

- HARQ process number – 4 bits.
- New data indicator – 1 bit.
- Redundancy version – 2 bits as defined in Table 7.3.1.1.1-2.
- Source ID – 8 bits as defined in clause 8.1 of [6, TS 38.214].
- Destination ID – 16 bits as defined in clause 8.1 of [6, TS 38.214].
- HARQ feedback enabled/disabled indicator – 1 bit as defined in clause 16.3 of [5, TS 38.213].
- Zone ID – 12 bits as defined in clause 5.8.11 of [9, TS 38.331].
- Communication range requirement – 4 bits determined by higher layer parameter *sl-ZoneConfigMCR-Index*.

8.4.2 CRC attachment

CRC attachment is performed according to clause 7.3.2 except that scrambling is not performed.

8.4.3 Channel coding

Channel coding is performed according to clause 7.3.3.

8.4.4 Rate Matching

For 2nd-stage SCI transmission on PSSCH with SL-SCH, the number of coded modulation symbols generated for 2nd-stage SCI transmission prior to duplication for the 2nd layer if present, denoted as Q'_{SC12} , is determined as follows:

$$Q'_{SC12} = \min \left\{ \left\lceil \frac{(O_{SC12} + L_{SC12}) \cdot \beta_{offset}^{SC12}}{Q_m^{SC12} \cdot R} \right\rceil, \left\lceil \alpha \sum_{l=0}^{N_{symbol}^{PSSCH}-1} M_{sc}^{SC12}(l) \right\rceil \right\} + \gamma$$

where

- O_{SCI2} is the number of the 2nd-stage SCI bits
- L_{SCI2} is the number of CRC bits for the 2nd-stage SCI, which is 24 bits.
- β_{offset}^{SCI2} is indicated in the corresponding 1st-stage SCI.
- $M_{sc}^{PSSCH}(l)$ is the scheduled bandwidth of PSSCH transmission, expressed as a number of subcarriers.
- $M_{sc}^{PSCCH}(l)$ is the number of subcarriers in OFDM symbol l that carry PSCCH and PSCCH DMRS associated with the PSSCH transmission.
- $M_{sc}^{SCI2}(l)$ is the number of resource elements that can be used for transmission of the 2nd-stage SCI in OFDM symbol l , for $l = 0, 1, 2, \dots, N_{symbol}^{PSSCH} - 1$ and for $N_{symbol}^{PSSCH} = N_{symbol}^{sh} - N_{symbol}^{PSFCH}$, in PSSCH transmission, where $N_{symbol}^{sh} = sl-lengthSymbols - 2$, where $sl-lengthSymbols$ is the number of sidelink symbols within the slot provided by higher layers as defined in [6, TS 38.214]. If higher layer parameter $sl-PSFCH-Period = 2$ or 4 , $N_{symbol}^{PSFCH} = 3$ if "PSFCH overhead indication" field of SCI format 1-A indicates "1", and $N_{symbol}^{PSFCH} = 0$ otherwise. If higher layer parameter $sl-PSFCH-Period = 0$, $N_{symbol}^{PSFCH} = 0$. If higher layer parameter $sl-PSFCH-Period$ is 1, $N_{symbol}^{PSFCH} = 3$.
- $M_{sc}^{SCI2}(l) = M_{sc}^{PSSCH}(l) - M_{sc}^{PSCCH}(l)$
- γ is the number of vacant resource elements in the resource block to which the last coded symbol of the 2nd-stage SCI belongs.
- R is the coding rate as indicated by "Modulation and coding scheme" field in SCI format 1-A.
- α is configured by higher layer parameter $sl-Scaling$.

The input bit sequence to rate matching is $d_0, d_1, d_2, d_3, \dots, d_{N-1}$, where N is the number of coded bits.

Rate matching is performed according to Clause 5.4.1 by setting $I_{BL} = 1$.

The output bit sequence after rate matching is denoted as $g_0^{SCI2}, g_1^{SCI2}, g_2^{SCI2}, g_3^{SCI2}, \dots, g_{G^{SCI2}-1}^{SCI2}$, where $G^{SCI2} = Q'_{SCI2} \cdot Q_m^{SCI2}$ and Q_m^{SCI2} is modulation order of the 2nd-stage SCI. A UE is not expected to have $G^{SCI2} > 4096$.

8.4.5 Multiplexing of coded 2nd-stage SCI bits to PSSCH

The coded 2nd-stage SCI bits are multiplexed onto PSSCH according to the procedures in Clause 8.2.1.

Annex A: Change history

| Change history | | | | | | | |
|----------------|----------|------------|------|-----|-----|--|-------------|
| Date | Meeting | TDoc | CR | Rev | Cat | Subject/Comment | New version |
| 2017-05 | RAN1#89 | R1-1707082 | | | | Draft skeleton | 0.0.0 |
| 2017-07 | AH_NR2 | R1-1712014 | | | | Inclusion of LDPC related agreements | 0.0.1 |
| 2017-08 | RAN1#90 | R1-1714564 | | | | Inclusion of Polar coding related agreements | 0.0.2 |
| 2017-08 | RAN1#90 | R1-1714659 | | | | Endorsed version by RAN1#90 as basis for further updates | 0.1.0 |
| 2017-09 | RAN1#90 | R1-1715322 | | | | Capturing additional agreements on LDPC and Polar code from RAN1 #90 | 0.1.1 |
| 2017-09 | RAN#77 | RP-171991 | | | | For information to plenary | 1.0.0 |
| 2017-09 | RAN1#90b | R1-1716928 | | | | Capturing additional agreements on LDPC and Polar code from RAN1 NR AH#3 | 1.0.1 |
| 2017-10 | RAN1#90b | R1-1719106 | | | | Endorsed as v1.1.0 | 1.1.0 |
| 2017-11 | RAN1#91 | R1-1719225 | | | | Capturing additional agreements on channel coding, etc. | 1.1.1 |
| 2017-11 | RAN1#91 | R1-1719245 | | | | Capturing additional agreements on DCI format, channel coding, etc. | 1.1.2 |
| 2017-11 | RAN1#91 | R1-1721049 | | | | Endorsed as v1.2.0 | 1.2.0 |
| 2017-12 | RAN1#91 | R1-1721342 | | | | Capturing additional agreements on UCI, DCI, channel coding, etc. | 1.2.1 |
| 2017-12 | RAN#78 | RP-172668 | | | | Endorsed version for approval by plenary. | 2.0.0 |
| 2017-12 | RAN#78 | | | | | Approved by plenary – Rel-15 spec under change control | 15.0.0 |
| 2018-03 | RAN#79 | RP-180200 | 0001 | - | F | CR capturing the Jan18 ad-hoc and RAN1#92 meeting agreements | 15.1.0 |
| 2018-04 | RAN#79 | | | | | MCC: correction of typo in DCI format 0_1 (time domain resource assignment) – higher layer parameter should be <i>pusch-AllocationList</i> | 15.1.1 |
| 2018-06 | RAN#80 | RP-181172 | 0002 | 1 | F | CR to 38.212 capturing the RAN1#92bis and RAN1#93 meeting agreements | 15.2.0 |
| 2018-06 | RAN#80 | RP-181257 | 0003 | - | B | CR to 38.212 capturing the RAN1#92bis and RAN1#93 meeting agreements related to URLLC | 15.2.0 |
| 2018-09 | RAN#81 | RP-181789 | 0004 | - | F | CR to 38.212 capturing the RAN1#94 meeting agreements | 15.3.0 |
| 2018-12 | RAN#82 | RP-182523 | 0005 | 3 | F | Combined CR of all essential corrections to 38.212 from RAN1#94bis and RAN1#95 | 15.4.0 |
| 2019-03 | RAN#83 | RP-190448 | 0006 | - | F | Correction of wrong implementation on frequency domain resource assignment bitwidth | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0008 | - | F | Correction to UCI multiplexing | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0009 | - | F | Correction on DCI format 2_3 for SUL cell in TS 38.212 | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0010 | - | F | Corrections to TS38.212 | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0011 | - | F | On bitwidth calculation for DCI fields using RRC parameter indicating maximum number of MIMO layers per serving cell | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0012 | - | F | CR on zero-padding of DCI 1_1 in cross-carrier scheduling case | 15.5.0 |
| 2019-03 | RAN#83 | RP-190448 | 0013 | - | F | Clarification on UL_SUL indicator field and SRS request field | 15.5.0 |
| 2019-06 | RAN#84 | RP-191282 | 0014 | - | F | CR on correction to bitwidth of NNZC indicator | 15.6.0 |
| 2019-06 | RAN#84 | RP-191282 | 0015 | - | F | Correction on DCI size alignment in TS 38.212 | 15.6.0 |
| 2019-06 | RAN#84 | RP-191282 | 0016 | - | F | Correction on UL/SUL indicator in DCI format 0_0 | 15.6.0 |
| 2019-06 | RAN#84 | RP-191282 | 0017 | - | F | Corrections to 38.212 including alignment of terminology across specifications | 15.6.0 |
| 2019-06 | RAN#84 | RP-191282 | 0018 | - | F | CR on maximum modulation order configured for serving cell | 15.6.0 |
| 2019-06 | RAN#84 | RP-191282 | 0019 | 1 | F | Corrections to 38.212 including alignment of terminology across specifications from RAN1#97 | 15.6.0 |
| 2019-09 | RAN#85 | RP-191941 | 0020 | - | F | Corrections to 38.212 including alignment of terminology across specifications in RAN1#98 | 15.7.0 |
| 2019-12 | RAN#86 | RP-192625 | 0021 | - | F | CR on UL/SUL indicator in DCI format 0_1 | 15.8.0 |
| 2019-12 | RAN#86 | RP-192625 | 0022 | - | F | Corrections to 38.212 including alignment of terminology across specifications in RAN1#98bis and RAN1#99 | 15.8.0 |
| 2019-12 | RAN#86 | RP-192636 | 0023 | - | B | Introduction of NR based access to unlicensed spectrum into 38.212 | 16.0.0 |
| 2019-12 | RAN#86 | RP-192637 | 0024 | - | B | Introduction of IAB into 38.212 | 16.0.0 |
| 2019-12 | RAN#86 | RP-192638 | 0025 | - | B | Introduction of 5G V2X sidelink features into TS 38.212 | 16.0.0 |
| 2019-12 | RAN#86 | RP-192639 | 0026 | - | B | Introduction of Physical Layer Enhancements for NR URLLC | 16.0.0 |
| 2019-12 | RAN#86 | RP-192641 | 0027 | - | B | Introduction of Enhancements on NR MIMO | 16.0.0 |
| 2019-12 | RAN#86 | RP-192642 | 0028 | - | B | Introduction of power saving in 38.212 | 16.0.0 |
| 2019-12 | RAN#86 | RP-192645 | 0029 | - | B | Introduction of MR DC/CA | 16.0.0 |
| 2019-12 | RAN#86 | RP-192643 | 0030 | - | B | Introduction of NR positioning support | 16.0.0 |
| 2019-12 | RAN#86 | RP-192635 | 0031 | - | B | Introduction of two-step RACH | 16.0.0 |
| 2020-03 | RAN#87-e | RP-200185 | 0032 | - | F | Corrections for Rel-16 NR-U after RAN1#100-e | 16.1.0 |

| | | | | | | | |
|---------|----------|-----------|------|---|---|--|--------|
| 2020-03 | RAN#87-e | RP-200190 | 0033 | - | F | Corrections for NR MIMO after RAN1#100-e | 16.1.0 |
| 2020-03 | RAN#87-e | RP-200188 | 0034 | - | F | Corrections for URLLC after RAN1#100-e | 16.1.0 |
| 2020-03 | RAN#87-e | RP-200191 | 0035 | - | F | Corrections for power saving after RAN1#100-e | 16.1.0 |
| 2020-03 | RAN#87-e | RP-200187 | 0036 | - | F | Corrections on 5G V2X sidelink features after RAN1#100-e | 16.1.0 |
| 2020-06 | RAN#88-e | RP-200683 | 0038 | - | A | CR on L1-RSRP report on PUSCH | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200693 | 0039 | 1 | F | Corrections for power saving | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200689 | 0040 | 1 | F | Corrections on 5G V2X sidelink features after RAN1#100bis-e and RAN1#101-e | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200694 | 0041 | 1 | F | Corrections in TS 38.212 for NR positioning | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200692 | 0042 | 1 | F | Corrections in TS 38.212 for NR MIMO | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200696 | 0043 | - | F | Corrections for Rel-16 MR-DC/CA after RAN1#100bis-e | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200690 | 0044 | 1 | F | Corrections on NR eURLLC | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200687 | 0045 | 1 | F | Corrections for Rel-16 NR-U | 16.2.0 |
| 2020-06 | RAN#88-e | RP-200688 | 0046 | - | F | Corrections for NR IAB | 16.2.0 |
| 2020-09 | RAN#89-e | RP-201814 | 0047 | - | F | Correction on UCI bit sequence generation | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201803 | 0049 | - | A | CR on PTRS for TS 38.212 | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201810 | 0050 | - | F | Alignment of RRC parameter <i>ps-RNTI</i> | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201813 | 0051 | - | F | CR to 38.212 on RRC parameter alignment for SCell dormancy | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201807 | 0052 | - | F | Corrections on 5G V2X sidelink features | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201809 | 0053 | - | F | Corrections to MIMO enhancements | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201805 | 0054 | - | F | Corrections to MIMO enhancements | 16.3.0 |
| 2020-09 | RAN#89-e | RP-201808 | 0055 | - | F | Corrections on NR eURLLC | 16.3.0 |
| 2020-12 | RAN#90-e | RP-202390 | 0056 | - | F | RRC IE name fix to dynamic frequency domain resource allocation type selection (Rel-15 origin) | 16.4.0 |
| 2020-12 | RAN#90-e | RP-202384 | 0057 | - | F | Correction on Transmission configuration indication in DCI format 1_2 | 16.4.0 |
| 2020-12 | RAN#90-e | RP-202398 | 0058 | - | F | Alignment CR for TS 38.212 | 16.4.0 |
| 2021-03 | RAN#91-e | RP-210052 | 0059 | - | F | CR on DMRS | 16.5.0 |
| 2021-03 | RAN#91-e | RP-210049 | 0060 | - | F | Correction to description of FDRA field size in DCI 0_0 | 16.5.0 |
| 2021-03 | RAN#91-e | RP-210049 | 0061 | - | F | Correction to description of FDRA field interpretation in DCI 0_1 | 16.5.0 |
| 2021-03 | RAN#91-e | RP-210050 | 0062 | - | F | Correction on Sidelink Broadcast channel | 16.5.0 |
| 2021-03 | RAN#91-e | RP-210049 | 0063 | - | F | Correction on LBT Type and CP Extension Indication for Semi-Static Channel Occupancy | 16.5.0 |
| 2021-03 | RAN#91-e | RP-210059 | 0064 | - | F | Alignment CR for TS 38.212 | 16.5.0 |
| 2021-06 | RAN#92-e | RP-211252 | 0066 | - | F | 38.212 CR on DAI size determination for DCI format 1_1/1-2 in CA | 16.6.0 |
| 2021-06 | RAN#92-e | RP-211236 | 0067 | - | F | Corrections on parameter of MCS table set to qam256 | 16.6.0 |
| 2021-06 | RAN#92-e | RP-211234 | 0068 | - | D | Alignment CR for TS 38.212 (post RAN1#104bis-e) | 16.6.0 |
| 2021-06 | RAN#92-e | RP-211234 | 0069 | - | F | Correction on HARQ-ACK codebook RRC parameter | 16.6.0 |
| 2021-06 | RAN#92-e | RP-211236 | 0070 | - | F | Correction on SRS resource set configuration in TS 38.212 | 16.6.0 |

| | | | | | | | |
|---------|----------|-----------|------|---|---|--|--------|
| 2021-06 | RAN#92-e | RP-211243 | 0071 | - | F | Alignment CR for TS 38.212 (post RAN1#105-e) | 16.6.0 |
| 2021-09 | RAN#93-e | RP-211843 | 0072 | - | F | Correction on SRS resource set configuration for DCI format 0_2 in TS 38.212 | 16.7.0 |
| 2021-09 | RAN#93-e | RP-211841 | 0074 | - | A | Rel-15 editorial corrections for TS 38.212 (mirrored to Rel-16) | 16.7.0 |
| 2021-09 | RAN#93-e | RP-211850 | 0075 | - | F | Alignment CR for TS 38.212 | 16.7.0 |

History

| Document history | | |
|-------------------------|---------------|-------------|
| V16.2.0 | July 2020 | Publication |
| V16.3.0 | November 2020 | Publication |
| V16.4.0 | January 2021 | Publication |
| V16.5.0 | April 2021 | Publication |
| V16.6.0 | August 2021 | Publication |
| V16.7.0 | October 2021 | Publication |