

# ETSI TS 138 307 V17.12.0 (2024-05)



**5G;  
NR;  
Requirements on User Equipments (UEs)  
supporting a release-independent frequency band  
(3GPP TS 38.307 version 17.12.0 Release 17)**



---

**Reference**

RTS/TSGR-0438307vhc0

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope .....	7
2 References .....	7
3 Definitions, symbols and abbreviations .....	7
3.1 Definitions .....	7
3.2 Symbols.....	8
3.3 Abbreviations .....	8
4 General .....	8
5 Release independent features for NR frequency range 1 .....	9
5.1 Additional NR operating bands and UE power classes for NR frequency range 1 .....	9
5.2 Additional NR CA configurations for NR frequency range 1 .....	10
5.2.1 Intra-band CA .....	10
5.2.2 Inter-band CA .....	10
5.3 Additional NR SUL configurations for NR frequency range 1 .....	11
5.4 Other release independent features for NR frequency range 1 .....	12
5.5 Additional Inter-band NR-DC configurations for NR frequency range 1 .....	13
5.6 Void.....	14
5.7 Additional Inter-band EN-DC or NR CA configurations involving shared spectrum access.....	14
5.8 Additional V2X configurations for NR frequency range 1 .....	15
6 Release independent features for NR frequency range 2 .....	15
6.1 Additional NR operating bands and UE power classes for NR frequency range 2 .....	15
6.2 Additional NR CA configurations for NR frequency range 2 .....	16
6.2.1 Intra-band CA .....	16
7 Release independent features for NR interworking between NR frequency range 1 and NR frequency range 2 .....	17
7.1 Additional NR inter-band CA configurations between frequency range 1 and frequency range 2 .....	17
7.2 Additional Inter-band NR-DC configurations between frequency range 1 and frequency range 2.....	18
8 Release independent features for NR interworking between NR and E-UTRA .....	19
8.1 Additional EN-DC configurations.....	19
8.1.1 Intra-band EN-DC .....	19
8.1.2 Inter-band EN-DC .....	20
8.1.2.1 Inter-band EN-DC within frequency range 1 .....	20
8.1.2.2 Inter-band EN-DC including frequency range 2 .....	21
8.1.2.3 Inter-band EN-DC including frequency range 1 and frequency range 2.....	21
8.2 Additional NE-DC configurations.....	21
8.2.1 Interband NE-DC.....	21
8.2.1.1 Interband NE-DC within frequency range 1 .....	21
8.2.1.2 Interband NE-DC including frequency range 2.....	22
9 Release independent features for NR UE supporting satellite access operation .....	22
9.1 Additional NR operating bands for NR NTN in frequency range 1 .....	22
<b>Annex A: Frequency arrangement for overlapping operating bands .....</b>	<b>24</b>
<b>Annex B (normative): Common Requirements for bands, CA, SUL or DC .....</b>	<b>25</b>
B.1 Purpose of annex .....	25
B.2 Common RRM requirements .....	25

B.3	Common UE performance requirements.....	25
B.3.1	Common UE performance requirements for different CA configurations and combination sets.....	25
B.3.2	Common UE performance requirements for interworking between NR and E-UTRA.....	25
B.3.3	Common PDSCH demodulation and CSI requirements with inter cell interference and intra cell inter user interference .....	26
B.4	Common UE RF requirements .....	26
B.4.1	Common UE RF requirements for a release independent band.....	26
B.4.2	Common UE RF requirements for CA configurations within NR frequency range 1 or NR frequency range 2 .....	27
B.4.3	Common UE RF requirements for SUL .....	28
B.4.4	Common UE RF requirements for interband CA configurations between NR frequency range 1 and NR frequency range 2 .....	28
B.4.5	Common UE RF requirements for Inter-band NR-DC configurations between frequency range 1 and frequency range 2 .....	29
B.4.5a	Common UE RF requirements for Inter-band NR-DC configurations within frequency range 1 .....	29
B.4.6	Common UE RF requirements for NR interworking between NR and E-UTRA.....	30
B.4.7	Common UE RF requirements for UL 7.5KHz shift for TDD band n40 .....	30
B.4.8	Common UE RF requirements shared spectrum access .....	31
B.4.9	Common UE RF requirements for Intra-band and Inter-band NR CA configurations involving shared spectrum access .....	31
B.4.10	Common UE RF requirements for 4Rx .....	31
B.4.11	Common UE RF requirements for transparent Tx diversity.....	32
B.4.12	Common UE RF requirements for NR V2X .....	33
B.4.13	Common UE RF requirements for UL MIMO bands in FR1 .....	34
B.4.14	Common UE RF requirements for Inter-band CA configurations with Tx switching within NR FR1 .....	34
B.4.15	Common UE RF requirements for SUL configurations with Tx switching within NR FR1 .....	35
B.4.16	Common UE RF requirements for Inter-band EN-DC with tx switching .....	35
<b>Annex C (normative): Common Requirements for high speed train scenario .....</b>		<b>36</b>
C.1	Common RRM requirements for high speed train scenario .....	36
C.2	Common UE demodulation requirements for high speed train scenario .....	36
C.3	Common RRM requirements for FR1 high speed train scenario enhancement .....	37
C.4	Common UE demodulation requirements for FR1 high speed train scenario enhancement .....	37
<b>Annex D (normative): Common PMI reporting requirements for 16TX and 32TX.....</b>		<b>39</b>
D.1	Common UE PMI reporting requirements for 16TX and 32TX TypeI-SinglePanel Codebook.....	39
D.2	Common UE PMI reporting requirements for 16TX TypeII Codebook .....	39
<b>Annex E (normative): Common PDSCH demodulation requirements with LTE CRS rate matching .....</b>		<b>40</b>
E.1	Common PDSCH demodulation requirements with LTE CRS rate matching.....	40
<b>Annex F (Informative): Change history .....</b>		<b>41</b>
History .....		44

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

---

# 1 Scope

The present document specifies requirements for Rel-17 UEs supporting release independent features like:

- additional NR operating bands and power classes on top of Rel-16 of TS 38.101-1/-2/-3/-4 [2-5] and TS 38.133 [6];

Furthermore, for Rel-17 UEs supporting satellite access operation, the present document specifies requirements supporting release independent features like:

- additional NR operating bands on top of Rel-17 of TS 38.101-5 [8] and TS 38.133 [6].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [3] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [4] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [5] 3GPP TS 38.101-4: "NR; User Equipment (UE) radio transmission and reception; Part 4: UE performance requirements".
- [6] 3GPP TS 38.133: "NR; Requirements for support of radio resource management".
- [7] 3GPP TS 38.306: "NR; User Equipment (UE) radio access capabilities".
- [8] 3GPP TS 38.101-5: "NR; User Equipment (UE) radio transmission and reception; Part 5: Satellite access Radio Frequency (RF) and performance requirements".

---

# 3 Definitions, symbols and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

**release independent:** applicable to some frozen releases, starting from a certain release Rel-M



NOTE 1: Normally, a feature is introduced only in the latest open release Rel-N and future releases are based on the previous one so that future releases inherit the requirements of this feature. Introducing a feature "in a release independent way from Rel-M onwards" ( $M < N$ ) means it was decided by TSG RAN that this feature would be also beneficial in previous, already frozen releases starting with Rel-M until Rel-(N-1). In order to avoid touching TS 38.101 [2-5] or TS 38.133 [6] of these frozen releases, the corresponding requirements are captured in TS 38.307 via pointers to [2-5] or [6] of the release in which the feature was introduced.

NOTE 2: Release independent does not mean applicable to all releases.

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

N	Release in which a feature is introduced into TS 38.101 [2-5] or TS 38.133 [6]
M	Release from which onwards (including release M) a feature is release independent

## 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

BW	Bandwidth
CA	Carrier Aggregation
CC	Component carrier
DL	Downlink
EN-DC	Dual connectivity between E-UTRA and NR
FDD	Frequency Division Duplex
FR1	Frequency range 1
FR2	Frequency range 2
NR	New radio
REL	Release
SDL	Supplementary downlink
SUL	Supplementary uplink
TDD	Time Division Duplex
UE	User Equipment
UL	Uplink

---

## 4 General

TSG-RAN has agreed for certain features (see the following clauses) to introduce them in a "release independent way".

This means for each feature:

- it is "introduced" in a release N, i.e. TS 38.101 [2-5] and TS 38.133 [6] of release N define certain UE requirements for this feature; the feature is indicated in the tables of the following clauses;
- it is "release independent" starting from a release M ( $M < N$ ); M for the given feature is provided in the tables of the following clauses;
- UEs supporting this feature have to fulfil additional requirements in release M or higher which are specified in one or more Annexes of TS 38.307 of release N; the applicable Annexes for a given feature are provided in the tables of the following clauses.

The applicable UE Categories are specified in TS 38.306 [7] according to the release to which the UE conforms.

In the table of release independent features in subsequent clauses, "FDD, TDD" refers to CA or EN-DC configuration composed by only FDD bands or only TDD bands, respectively. "FDD and TDD" refers to CA or EN-DC configuration

including both FDD and TDD bands. "SDL and FDD, SDL and TDD" refers to CA configuration including both SDL and FDD bands or both SDL and TDD bands, respectively. "TDD and SUL" refers to SUL configuration including both TDD and SUL bands. "FDD and TDD and SUL" refers to EN-DC configuration including both FDD, TDD and SUL bands. Unless stated otherwise, the release independent for the band combinations are from Rel-15. Configurations with BCSs other than BCS5 are release independent from Rel-15, where the BCSs for configurations are defined in TS 38.101-1 [2] and/or TS 38.101-3 [4]. Configurations with BCS5 are release independent from Rel-17, and BCS5 with signalling is allowed for early implementation from Rel-15. Note that BCS4/BCS5 is not applicable to intra-band EN-DC configurations.

When a new feature is introduced only the latest release of release independent spec needs to be updated. The latest release of release independent spec refers to the release which the new feature is introduced in. If an RF feature introduced in the same release as the release which the feature is independent from, (i.e. M=N), the common UE RF requirements table in annex B.4 is specified from release N+1, otherwise the common UE RF requirements table is specified from release N.

## 5 Release independent features for NR frequency range 1

### 5.1 Additional NR operating bands and UE power classes for NR frequency range 1

Requirements for a Rel-17 UE for additional NR operating bands and power classes compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

**Table 5.1-1: NR operating bands**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Operating bands	FDD, TDD, SDL, SUL	Rel-15	Table B.4.1-1, Table B.4.3-1
Shared spectrum access operating bands	TDD	Rel-16	Table B.4.7-1
UL MIMO operating bands without ULFPTx	FDD, TDD	Rel-15	Table B.4.13-1
UL MIMO operating bands with ULFPTx	FDD, TDD	Rel-16	
UL MIMO operating bands with or without ULFPTx	SUL	Rel-17	

**Table 5.1-2: NR UE power class**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the power class was introduced)
Power Class 1	FDD	Rel-15	Table B.4.1-1
Power Class 1.5	TDD	Rel-15	Table B.4.1-1, Table B.4.3-1
Power Class 2	FDD, TDD	Rel-15	Table B.4.1-1, Table B.4.3-1
Power Class 3	FDD, TDD, SUL	Rel-15	Table B.4.1-1, Table B.4.3-1

## 5.2 Additional NR CA configurations for NR frequency range 1

### 5.2.1 Intra-band CA

Requirements for a Rel-17 UE for additional NR intraband CA configurations within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

Requirements for a Rel-17 UE for additional NR intraband CA configurations with UL MIMO within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

**Table 5.2.1-1: NR intra-band contiguous CA within FR1**

Feature	DL/UL	CA BW Class	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band contiguous CA configurations within FR1	DL	B, C, D, E, M, N, O	FDD,TDD	Rel-15	Table B.4.2-1
	UL	A,B,C	FDD,TDD	Rel-15	
Intra-band contiguous CA configurations with UL MIMO within FR1	UL	C	TDD	Rel-15	Table B.4.2-2

**Table 5.2.1-2: NR intra-band non-contiguous CA within FR1**

Feature	DL/UL	number of sub-blocks	maximum number of CCs within a sub-block	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band non-contiguous CA configurations within FR1	DL	2	1	FDD, TDD	Rel-15	Table B.4.2-1
		3	1	FDD, TDD	Rel-15	
		4	1	TDD	Rel-15	
	UL	1	1	FDD, TDD	Rel-15	
		2	1	TDD	Rel-15	

### 5.2.2 Inter-band CA

Requirements for a Rel-17 UE for additional NR inter-band CA configurations within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

**Table 5.2.2-0: NR inter-band CA UE power class within FR1**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the power class was introduced)
Inter-band CA Power Class 2	TDD, FDD and TDD	Rel-15	Table B.4.2-1
Inter-band CA Power Class 3	FDD, TDD, SDL and TDD, FDD and TDD	Rel-15	

**Table 5.2.2-1: NR inter-band CA within FR1**

Feature	DL/UL	Maximum number of bands	Maximum number of CCs	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band CA configurations within NR FR1	DL	5	8	A, B, C	TDD, FDD, SDL and FDD, SDL and TDD, FDD and TDD, FDD and SDL and TDD	Rel-15	Table B.4.2-1
	UL	2	2	A	TDD, FDD, FDD and TDD	Rel-15	
		1	2	B, C, 2A			
		2	3	A, B, C			
Inter-band CA configurations with 1Tx-2Tx switching within NR FR1	UL	2	2	A	TDD, FDD, FDD and TDD	Rel-16	Table B.4.14-1

## 5.3 Additional NR SUL configurations for NR frequency range 1

Requirements for a Rel-17 UE for additional NR SUL configurations within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

When a UE is configured with both NR UL and NR SUL carriers in a serving cell with active transmission either on the UL carrier or SUL carrier, the release independent features in clause 5.1 are applicable for the UL carrier and the SUL carrier, respectively.

Table 5.3-1: NR SUL within FR1

Feature	DL/UL	number of bands	number of CCs	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the SUL configuration was introduced)
Inter-band SUL configurations within NR FR1	DL	3	3	A, C	TDD, FDD, FDD and TDD	Rel-15	Table B.4.3-1
	UL	2	3	A, C	TDD and SUL, FDD and SUL	Rel-15	
Inter-band SUL configurations with 1Tx-2Tx switching within NR FR1	UL	2	2	A	TDD and SUL	Rel-16	Table B.4.15-1

## 5.4 Other release independent features for NR frequency range 1

This clause covers requirements for a Rel-17 UE coming from all other release independent features that are not covered under clause 5.1, 5.2 and 5.3, e.g. generic baseband requirements or requirements that are not band/CA/SUL configuration specific.

**Table 5.4-1: Additional requirements of other release independent features**

Feature	Release independent from	Requirements to be fulfilled (see 38.307 of the REL when the feature was introduced)	Further information
RRM requirements for high speed train scenario	Rel-15 (NOTE 1)	Table C.1-1	Rel-16 WI NR_HST introduced band independent RRM requirements: see Table C.1-1
UE demodulation requirements for high speed train scenario	Rel-15 (NOTE 1)	Table C.2-1	Rel-16 WI NR_HST introduced band independent UE demodulation requirements: see Table C.2-1
RF requirements for 4Rx UEs	Rel-15	Table B.4.10-1, Table B.4.10-2	
Transparent Tx diversity	Rel-15	Table B.4.11-1	Rel-17 WI NR_RF_TxD introduced transparent Tx diversity requirements: see Table B.4.11-1
UE demodulation and CSI requirements for MMSE-IRC receiver for scenarios with inter cell and intra cell inter user interference	Rel-15	Table B.3.3-1	Rel-17 WI NR_demod_enh2-Perf: see Table B.3.3-1. These requirements are optional for Rel-15 and Rel-16 UEs and can be executed based on UE declaration.
RRM enhancement for FR1 high speed train scenario enhancement	Rel-16 (NOTE 2)	Table C.3-1	Rel-17 WI NR_HST_FR1_enh introduced band independent RRM enhancement: see Table C.3-1
HST-SFN CA demodulation enhancement for FR1 high speed train scenario enhancement	Rel-16 (NOTE 3)	Table C.4-1	Rel-17 WI NR_HST_FR1_enh introduced band independent HST-SFN CA demodulation enhancement: see Table C.4-1
HST-DPS CA demodulation enhancement for FR1 high speed train scenario enhancement	Rel-15 (NOTE 4)	Table C.4-1	Rel-17 WI NR_HST_FR1_enh introduced band independent HST-DPS CA demodulation enhancement: see Table C.4-1
<p>NOTE 1: Rel-15 UEs supporting the high speed train are assumed to read the Rel-16 high speed train scenario information, which is broadcast to all UEs.</p> <p>NOTE 2: Rel-16 UEs supporting the high speed train are assumed to read the Rel-17 high speed train scenario information, which is broadcast to all UEs.</p> <p>NOTE 3: Rel-16 UEs supporting the high speed train are assumed to read the Rel-17 high speed train scenario information, which is broadcast to all UEs.</p> <p>NOTE 4: Rel-15 UEs supporting the high speed train are assumed to read the Rel-17 high speed train scenario information, which is broadcast to all UEs.</p>			

## 5.5 Additional Inter-band NR-DC configurations for NR frequency range 1

Requirements for a Rel-17 UE for additional NR-DC configurations within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause.

**Table 5.5.1-1: NR-DC within FR1**

Feature	DL/UL	Maximum number of bands	Maximum number of CCs	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the DC configuration was introduced)
NR-DC configurations within NR FR1	DL	4	6	A, B, C, D, E, N	FDD, TDD, FDD and TDD	Rel-16	Table B.4.5a-1
	UL	2	3	A, B	FDD, TDD, FDD and TDD	Rel-16	

5.6 UL 7.5KHz shift for TDD band n40 Requirements for a Rel-17 UE for UL 7.5KHz shift for TDD band n40 within FR1 compared to TS 38.101-1 of Rel-17 [2] are introduced via this clause. For Band n40, UL shift is only applicable to uplink transmissions using a 15 kHz SCS.

**Table 5.3-2: UL 7.5KHz shift for band n40 in FR1**

Feature	DL/UL	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the configuration was introduced)
7.5KHz UL shift for band n40 in FR1	UL	TDD	Rel-15	Table B.4.7-1

## 5.6 Void

## 5.7 Additional Inter-band EN-DC or NR CA configurations involving shared spectrum access

Requirements for a Rel-17 UE for additional NR CA, EN-DC, and NR DC configurations involving shared spectrum access compared to TS 38.101-1 of Rel-17 [2] or TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 5.7-1: NR CA, EN-DC, and NR DC configurations involving shared spectrum access**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see 38.307 of the REL in which the NR CA, EN-DC, or NR DC configuration was introduced)
Intra-band and Inter-band NR CA configurations involving shared spectrum access	FDD and TDD, TDD	Rel-16	Table B.3.1-1, Table B.4.2-1, Table B.4.8-1
Inter-band EN-DC configurations involving shared spectrum access	FDD and TDD, TDD	Rel-16	Table B.4.6-1
Inter-band NR DC configurations involving shared spectrum access	FDD and TDD, TDD	Rel-16	Table B.4.5-1, Table B.4.5a-1

## 5.8 Additional V2X configurations for NR frequency range 1

Requirements for a Rel-17 UE for additional NR SL configurations involving V2X con-current operation compared to TS 38.101-1 of Rel-17 [4] are introduced via this clause.

**Table 5.8-1: NR V2X con-current operation within in FR1**

Feature	Release independent from	Requirements to be fulfilled (see 38.307 of the REL when the feature was introduced)	Further information
Operating bands for V2X communication with con-current operation	Rel-16	Table B.4.12-1, Table B.4.12-2	NR V2X new bands, intra-band/inter-band con-current operation, SL MIMO/TxD are release independent according to requirements in Table B.4.12-1, Table B.4.12-2

## 6 Release independent features for NR frequency range 2

### 6.1 Additional NR operating bands and UE power classes for NR frequency range 2

Requirements for a Rel-17 UE for additional NR operating bands and power classes compared to TS 38.101-2 of Rel-17 [3] are introduced via this clause.



**Table 6.1-1: NR operating bands**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Operating bands	TDD	Rel-15	Table B.4.1-1

**Table 6.1-2: NR UE power class**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Power Class 1, 2, 3, 4, 5	TDD	Rel-15	Table B.4.1-1

## 6.2 Additional NR CA configurations for NR frequency range 2

### 6.2.1 Intra-band CA

Requirements for a Rel-17 UE for additional NR intra-band CA configurations within FR2 compared to TS 38.101-2 of Rel-17 [3] are introduced via this clause.

**Table 6.2.1-1: NR intra-band contiguous CA within FR2**

Feature	DL/UL	CA BW Class	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band contiguous CA configurations within FR2	DL	B, C, D, E, F, G, H, I, J, K, L, M, O, P, Q	TDD	Rel-15	Table B.4.2-1
	UL	A, B, D, E, F, G, H, I, J, K, L, M, O, P, Q	TDD	Rel-15	

Table 6.2.1-2: NR non-contiguous intra-band CA within FR2

Feature	DL/UL	number of sub-blocks	maximum number of CCs within a sub-block	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band non-contiguous CA configurations within FR2	DL	2	7	TDD	Rel-15	Table B.4.2-1
		3	4	TDD	Rel-15	
		4	4	TDD	Rel-15	
		5	4	TDD	Rel-15	
		6	4	TDD	Rel-15	
		7	3	TDD	Rel-15	
		8	3	TDD	Rel-15	
		9	2	TDD	Rel-15	
		10	2	TDD	Rel-15	
		UL	1	4	TDD	
	2		1	TDD	Rel-15	
	3		1	TDD	Rel-15	

Table 6.2.1-3: NR inter-band CA within FR2

Feature	DL/UL	Maximum number of bands	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band CA configurations within NR FR2	DL	2	A, G, H, I, J, K, L, M	TDD	Rel-16	Table B.4.2-1
	UL	2	A, G, H, I, J, K, L, M	TDD	Rel-16	

## 7 Release independent features for NR interworking between NR frequency range 1 and NR frequency range 2

### 7.1 Additional NR inter-band CA configurations between frequency range 1 and frequency range 2

Requirements for a Rel-17 UE for additional NR inter-band CA configurations between FR1 and FR2 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

Table 7.1-1: NR inter-band CA between FR1 and FR2

Feature	DL/UL	maximum number of bands	maximum number of CCs	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band CA configurations for NR interworking between FR1 and FR2	DL FR1	4	5	A, B, C	FDD, TDD, FDD and TDD	Rel-15	Table B.4.4-1
	DL FR2	1	8	A, B, C, D, E, F, G, H, I, J, K, L, M, O, P, Q	TDD	Rel-15	
	UL FR1	2	3	A, B, C	FDD, TDD, FDD and TDD	Rel-15	
	UL FR2	1	8	A, B, C, D, E, F, G, H, I, J, K, L, M	TDD	Rel-15	

## 7.2 Additional Inter-band NR-DC configurations between frequency range 1 and frequency range 2

Requirements for a Rel-17 UE for additional Inter-band NR-DC configurations between FR1 and FR2 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

Table 7.2-1: Inter-band NR-DC between FR1 and FR2

Feature	DL/UL	maximum number of bands	maximum number of CCs	CA BW Classes	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band DC configurations for NR interworking between FR1 and FR2	DL FR1	3	4	A, B, C	FDD, TDD, FDD and TDD	Rel-15	Table B.4.5-1
	DL FR2	1	8	A, B, C, D, E, F, G, H, I, J, K, L, M, O, P, Q	TDD	Rel-15	
	UL FR1	1	2	A, B	FDD, TDD	Rel-15	
	UL FR2	1	8	A, D, E, F, G, H, I, J, K, L, M	TDD	Rel-15	

## 8 Release independent features for NR interworking between NR and E-UTRA

### 8.1 Additional EN-DC configurations

#### 8.1.1 Intra-band EN-DC

Requirements for a Rel-17 UE for additional EN-DC intra-band configurations within FR1 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.1.1-0: EN-DC intra-band UE power class**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Intra-band contiguous EN-DC power class 1.5	TDD	Rel-15	Table B.4.6-1
Intra-band contiguous EN-DC power class 2	TDD	Rel-15	
Intra-band contiguous EN-DC power class 3	FDD, TDD	Rel-15	
Intra-band non-contiguous EN-DC power class 1.5	TDD	Rel-15	
Intra-band non-contiguous EN-DC power class 2	TDD	Rel-15	
Intra-band non-contiguous EN-DC power class 3	FDD, TDD	Rel-15	

**Table 8.1.1-1: EN-DC contiguous intra-band configurations within FR1**

Feature	DL/UL	maximum number of E-UTRA CCs	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band contiguous EN-DC	DL	3	2	FDD, TDD	Rel-15	Table B.3.2-1, Table B.4.6-1
	UL	1	1	FDD, TDD	Rel-15	

**Table 8.1.1-2: EN-DC non-contiguous intra-band configurations within FR1**

Feature	DL/UL	maximum number of sub-blocks	maximum number of E-UTRA CCs	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Intra-band non-contiguous EN-DC	DL	3	3	1	FDD, TDD	Rel-15	Table B.3.2-2, Table B.4.6-1
	UL	2	1	1	FDD, TDD	Rel-15	

## 8.1.2 Inter-band EN-DC

### 8.1.2.1 Inter-band EN-DC within frequency range 1

Requirements for a Rel-17 UE for additional EN-DC inter-band configurations within FR1 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.1.2.1-0: EN-DC inter-band UE power class**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Inter-band EN-DC Power Class 2	TDD, FDD and TDD	Rel-15	Table B.4.6-1
Inter-band EN-DC Power Class 3	FDD, TDD, FDD and TDD	Rel-15	

**Table 8.1.2.1-1: EN-DC inter-band configurations without SUL within FR1**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band EN-DC	DL	5	6	4	4	FDD, TDD, FDD and TDD, FDD and SDL, FDD and SDL and TDD	Rel-15	Table B.4.6-1
	UL	1	2 contiguous	1	2 contiguous	FDD, TDD, FDD and TDD	Rel-15	
Inter-band EN-DC with 1Tx-2Tx switching	UL	1	1	1	1	TDD, FDD and TDD	Rel-16	Table B.4.16-1

**Table 8.1.2.1-2: EN-DC inter-band configurations with SUL within FR1**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band EN-DC	DL	2	3	1	1	FDD, TDD, FDD and TDD	Rel-15	Table B.4.6-1
	UL	1	1	2	2 contiguous	FDD, TDD, FDD and TDD and SUL	Rel-15	

### 8.1.2.2 Inter-band EN-DC including frequency range 2

Requirements for a Rel-17 UE for additional EN-DC inter-band configurations including FR2 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.1.2.2-1: EN-DC inter-band configurations including FR2**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band EN-DC	DL	4	6	1	15	TDD, FDD and TDD, FDD and SDL and TDD	Rel-15	Table B.4.6-1
	UL	1	4	1	8	TDD, FDD and TDD	Rel-15	

### 8.1.2.3 Inter-band EN-DC including frequency range 1 and frequency range 2

Requirements for a Rel-17 UE for additional EN-DC inter-band configurations including FR1 and FR2 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.1.2.3-1: EN-DC inter-band configurations including FR1 and FR2**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Inter-band EN-DC	DL FR1	4	6	2	2	TDD, FDD, FDD and TDD	Rel-15	Table B.4.6-1
	DL FR2			1	8	TDD	Rel-15	
	UL FR1	1	2	1	1	FDD, TDD, FDD and TDD	Rel-15	
	UL FR2	1	8	1	8	TDD	Rel-15	

## 8.2 Additional NE-DC configurations

### 8.2.1 Interband NE-DC

#### 8.2.1.1 Interband NE-DC within frequency range 1

Requirements for a Rel-17 UE for additional NE-DC interband configurations within FR1 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.2.1.1-0: NE-DC interband UE power class**

Feature	Duplex-mode	Release independent from	Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)
Interband NE-DC Power Class 3	FDD, TDD, FDD and TDD	Rel-15	Table B.4.6-1

**Table 8.2.1.1-1: NE-DC interband configurations without SUL within FR1**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Interband NE-DC	DL	4	5	1	2	FDD, TDD, FDD and TDD	Rel-15	Table B.4.6-1
	UL	1	1	1	1	FDD, TDD, FDD and TDD	Rel-15	

### 8.2.1.2 Interband NE-DC including frequency range 2

Requirements for a Rel-17 UE for additional NE-DC interband configurations including FR2 compared to TS 38.101-3 of Rel-17 [4] are introduced via this clause.

**Table 8.2.1.2-1: NE-DC interband configurations including FR2**

Feature	DL/UL	maximum number of E-UTRA bands	maximum number of E-UTRA CCs	maximum number of NR bands	maximum number of NR CCs	Duplex-mode	Release independent from	requirements to be fulfilled (see 38.307 of the REL in which the CA configuration was introduced)
Interband NE-DC	DL	4	5	1	8	FDD and TDD	Rel-15	Table B.4.6-1
	UL	1	2	1	8	FDD and TDD	Rel-15	

## 9 Release independent features for NR UE supporting satellite access operation

### 9.1 Additional NR operating bands for NR NTN in frequency range 1

Requirements for a Rel-17 NR UE supporting satellite access operation, for additional NTN operating bands compared to TS 38.101-5 of Rel-17 [8] are introduced via this clause.

**Table 9.1-1: Additional NR operating bands for NR NTN in FR1**

<b>Feature</b>	<b>Duplex-mode</b>	<b>Release independent from</b>	<b>Requirements to be fulfilled (see TS 38.307 of the release in which the band was introduced)</b>
NTN operating bands	FDD	Rel-17	

**Table 9.1-2: NR NTN UE power class in FR1**

<b>Feature</b>	<b>Duplex-mode</b>	<b>Release independent from</b>	<b>Requirements to be fulfilled (see TS 38.307 of the release in which the power class was introduced)</b>
Power Class 3	FDD	Rel-17	

**Table 9.1-3: NR NTN UE channel bandwidth in FR1**

<b>Feature</b>	<b>Duplex-mode</b>	<b>Release independent from</b>	<b>Requirements to be fulfilled (see TS 38.307 of the release in which the UE channel bandwidth was introduced)</b>
UE channel bandwidth	FDD	Rel-17	



## Annex A: Frequency arrangement for overlapping operating bands

The following information is provided in order to assist a UE derive the DL NR-ARFCN and UL NR-ARFCN in a multi-band environment, in which multiple overlapping operating bands may be indicated in the fields *freqBandIndicatorNR* and *MultiFrequencyBandListNR-SIB*.

The overlapping bands, independent of release, which may be indicated in a cell are shown in Table A-1 for applicable NR operating bands. The DL NR-ARFCN and UL NR-ARFCN are derived according to TS 38.101-1 and TS 38.101-2.

**Table A-1: Overlapping bands (multi-band environments) for each NR band**

NR Operating Band	Overlapping NR operating bands	Duplex Mode
n2	n25	FDD
n5	n18, n26	FDD
n18	n5, n26	FDD
n12	n85	FDD
n25	n2	FDD
n26	n5, n18	FDD
n38	n41, n90	TDD
n41	n38, n90	TDD
n48	n78, n77	TDD
n78	n48, n77	TDD
n77	n48, n78	TDD
n80	n86	SUL
n85	n12	FDD
n86	n80	SUL
n96	n102	TDD
n102	n96	TDD
n257	n258	TDD
n257	n261	TDD
n259	n260	TDD

## Annex B (normative): Common Requirements for bands, CA, SUL or DC

### B.1 Purpose of annex

The purpose of Annex B is to group the requirements that are common for several bands or CA configurations in this specification and use the common tables as references.

### B.2 Common RRM requirements

### B.3 Common UE performance requirements

#### B.3.1 Common UE performance requirements for different CA configurations and combination sets

The requirements and test cases listed in Table B.3.1-1 are specified in Rel-7 version of TS 38.101-4 [5].

**Table B.3.1-1: Common UE performance requirements for different CA configurations and combination sets**

Section / Clause	Description
5.2A.2.1	PDSCH 2RX demodulation requirements for NR FR1 CA configurations <sup>(Note 1)</sup>
5.2A.3.1	PDSCH 4RX demodulation requirements for NR FR1 CA configurations <sup>(Note 1)</sup>
7.2A.2	PDSCH 2RX demodulation requirements for NR FR2 CA configurations <sup>(Note 1)</sup>
5.2A.2.2	PDSCH 2RX demodulation requirements for NR FR1 intra-band contiguous CA with power imbalance <sup>(Note 2)</sup>
5.2A.3.2	PDSCH 4RX demodulation requirements for NR FR1 intra-band contiguous CA with power imbalance <sup>(Note 2)</sup>
6.2A	Channel Quality Indicator (CQI) reporting requirements for NR FR1 CA <sup>(Note 3)</sup>
8.2A	Channel Quality Indicator (CQI) reporting requirements for NR FR2 CA <sup>(Note 3)</sup>
NOTE 1: The applicability of requirements for different CA configurations and bandwidth combination sets is specified in Section 5.1.1.5 and 7.1.1.5.	
NOTE 2: The applicability of PDSCH performance requirements with power imbalance for intra-band contiguous CA is specified in Section 5.1.1.6.	
NOTE 3: The applicability of Channel Quality Indicator (CQI) reporting requirements for CA specified in Section 6.1.1.5 and 8.1.1.5.	

#### B.3.2 Common UE performance requirements for interworking between NR and E-UTRA

The requirements and test cases listed in Table B.3.2-1 and Table B.3.2-2 are specified in Rel-17 version of TS 38.101-4 [5].

**Table B.3.2-1: Common UE performance requirements for intra-band contiguous EN-DC within FR1**

Section / Clause	Description
9.5B.1.1	PDSCH demodulation for FR1 intra-band contiguous EN-DC with power imbalance <sup>(Note 1)</sup>
NOTE 1: The requirements applicability for UE supporting FR1 intra-band and inter-band EN-DC is specified in Section 9.1.1.	

**Table B.3.2-2: Common UE performance requirements for intra-band non-contiguous EN-DC within FR1**

Section / Clause	Description
9.5B.1.2	PDSCH demodulation for FR1 intra-band non-contiguous EN-DC with power imbalance <sup>(Note 1)</sup>
NOTE 1: The requirements applicability for UE supporting FR1 intra-band and inter-band EN-DC is specified in Section 9.1.1.	

### B.3.3 Common PDSCH demodulation and CSI requirements with inter cell interference and intra cell inter user interference

The requirements and test cases listed in Table B.3.3-1 are specified in Rel-17 version of TS 38.101-4 [5].

**Table B.3.3-1: UE PDSCH demodulation and CSI requirements with MMSE-IRC receiver for scenarios with inter cell interference and intra cell inter user interference**

Section / Clause	Description
5.2.2.1.15	PDSCH demodulation requirements with inter cell interference for 2RX FDD
5.2.3.1.15	PDSCH demodulation requirements with inter cell interference for 4RX FDD
5.2.2.2.16	PDSCH demodulation requirements with inter cell interference for 2RX TDD
5.2.3.2.16	PDSCH demodulation requirements with inter cell interference for 4RX TDD
5.2.2.1.16	PDSCH demodulation requirements with intra cell inter user interference for 2RX FDD
5.2.3.1.16	PDSCH demodulation requirements with intra cell inter user interference for 4RX FDD
5.2.2.2.17	PDSCH demodulation requirements with intra cell inter user interference for 2RX TDD
5.2.3.2.17	PDSCH demodulation requirements with intra cell inter user interference for 4RX TDD
6.2.2.1.2.3	CQI requirements with inter cell interference for 2RX FDD
6.2.3.1.2.3	CQI requirements with inter cell interference for 4RX FDD
6.2.2.2.2	CQI requirements with inter cell interference for 2RX TDD
6.2.3.2.2	CQI requirements with inter cell interference for 4RX TDD

## B.4 Common UE RF requirements

### B.4.1 Common UE RF requirements for a release independent band

The requirements and test cases listed in Table B.4.1-1 are specified in REL-17 version of TS 38.101-1 [2] or TS 38.101-2 [3].

**Table B.4.1-1: Common UE RF requirements for a release independent band**

Clause / Clause	Description
5.2	Operating bands
5.3	UE Channel bandwidth
5.4	Channel arrangement
6.2	Transmitter power
6.3	Output power dynamics
6.4	Transmit signal quality
6.5	Output RF spectrum emissions
6.6 of [3]	Beam correspondence
7.3	Reference sensitivity
7.4	Maximum input level
7.5	Adjacent Channel Selectivity
7.6	Blocking characteristics
7.7 of [2]	Spurious response
7.8 of [2]	Intermodulation characteristics
7.9	Spurious emissions
L.1	Indication of modified MPR behavior
NOTE:	A UE which supports any FR2 band introduced in release N, where N > 15, shall meet the requirements according to the FR2 UE multi-band relaxation factors defined in Table 6.2.1.3-4 of the release N version of [3] for all FR2 bands which it supports.

## B.4.2 Common UE RF requirements for CA configurations within NR frequency range 1 or NR frequency range 2

The requirements and test cases listed in Table B.4.2-1 are specified in in REL-17 version of TS 38.101-1 [2] or TS 38.101-2 [3].

**Table B.4.2-1: Common UE RF requirements for a release independent CA configurations within NR frequency range 1 or NR frequency range 2**

Clause	Description
5.2A	Operating bands for CA
5.3A	UE channel bandwidth for CA
5.4A	Channel arrangement for CA
5.5A	Configurations for CA
6.2A	Transmitter power for CA
6.3A	Output power dynamics for CA
6.4A	Transmit signal quality for CA
6.5A	Output RF spectrum emissions for CA
6.6A of [3]	Beam correspondence for CA
7.3A	Reference sensitivity for CA
7.4A	Maximum input level for CA
7.5A	Adjacent Channel Selectivity for CA
7.6A	Blocking characteristics for CA
7.7A of [2]	Spurious response for CA
7.8A of [2]	Intermodulation characteristics for CA
7.9A of [2]	Spurious emissions for CA

The requirements and test cases listed in Table B.4.2-2 are specified in in REL-17 version of TS 38.101-1 [2].

**Table B.4.2-2: Common UE RF requirements for a release independent intra-band contiguous UL CA configurations with UL MIMO within NR frequency range 1**

Clause	Description
6.2H	Transmitter power for CA with UL MIMO
6.2H.1	Transmitter power for intra-band UL contiguous CA for UL MIMO
6.3H	Output power dynamics for intra-band UL contiguous CA for UL MIMO
6.4H	Transmit signal quality for CA with UL MIMO
6.4H.1	Transmit signal quality for intra-band UL contiguous CA for UL MIMO
6.5H	Output RF spectrum emissions for CA with UL MIMO
6.5H.1	Output RF spectrum emissions for intra-band UL contiguous CA for UL MIMO

### B.4.3 Common UE RF requirements for SUL

The requirements and test cases listed in Table B.4.3-1 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.3-1: Common UE RF requirements for a release independent SUL**

Clause	Description
5.2	Operating bands
5.2C	Operating band combination for SUL
5.4.2.1	NR-ARFCN and channel raster (7.5kHz frequency shift for SUL)
5.5C	Configurations for SUL
6.2C	Transmitter power for SUL
6.4.2.2	Carrier leakage (7.5 kHz shift with the carrier frequency.)
7.3.3	$\Delta RIB,c$
7.3C	Reference sensitivity for SUL
7.6C	Blocking characteristics for SUL

### B.4.4 Common UE RF requirements for interband CA configurations between NR frequency range 1 and NR frequency range 2

The requirements and test cases listed in Table B.4.4-1 are specified in in REL-17 version of TS 38.101-3 [4].

**Table B.4.4-1: Common UE RF requirements for a release independent interband CA configurations between NR frequency range 1 and NR frequency range 2**

Clause	Description
5.2A	Operating bands for CA
5.3A	UE channel bandwidth for CA
5.4A	Channel arrangement for CA
5.5A	Configuration for CA
6.2A	Transmitter power for CA
6.3A	Output power dynamics for CA
6.4A	Transmit signal quality for CA
6.5A	Output RF spectrum emissions for CA
7.3A	Reference sensitivity for CA
7.4A	Maximum input level for CA
7.5A	Adjacent Channel Selectivity for CA
7.6A	Blocking characteristics for CA
7.7A	Spurious response for CA
7.8A	Intermodulation characteristics for CA
7.9A	Spurious emissions for CA

## B.4.5 Common UE RF requirements for Inter-band NR-DC configurations between frequency range 1 and frequency range 2

The requirements and test cases listed in Table B.4.5-1 are specified in in REL-17 version of TS 38.101-3 [4].

**Table B.4.5-1: Common UE RF requirements for a release independent Inter-band NR-DC configurations between frequency range 1 and frequency range 2**

Clause	Description
4.2	Applicability of minimum requirements
5.2B	Operating bands for DC
5.5B	Configuration for DC
6.2B.5	Configured output power for NR-DC

### B.4.5a Common UE RF requirements for Inter-band NR-DC configurations within frequency range 1

The requirements and test cases listed in Table B.4.5a-1 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.5a-1: Common UE RF requirements for release independent Inter-band NR-DC configurations within frequency range 1**

Clause	Description
5.2B	Operating bands for DC
5.5B	Configurations for DC
6.2B	Transmitter power for NR-DC
6.3B	Output power dynamics for NR-DC
6.4B	Transmit signal quality for NR-DC
6.5B	Output RF spectrum emissions for NR-DC
7.3B	Reference sensitivity for NR-DC
7.4B	Maximum input level for NR-DC
7.5B	Adjacent channel selectivity for NR-DC
7.6B	Blocking characteristics for NR-DC
7.7B	Spurious response for NR-DC
7.8B	Intermodulation characteristics for NR-DC
7.9B	Spurious emissions for NR-DC

## B.4.6 Common UE RF requirements for NR interworking between NR and E-UTRA

The requirements and test cases listed in Table B.4.6-1 are specified in REL-17 version of TS 38.101-3 [4].

**Table B.4.6-1: Common UE RF requirements for a release independent NR interworking between NR and E-UTRA**

Clause	Description
4.2	Applicability of minimum requirements
5.2B	Operating bands for DC
5.3B	UE channel bandwidth for DC
5.4B	Channel arrangement for DC
5.5B	Configuration for DC
6.2B	Transmitter power for DC
6.3B	Output power dynamics for DC
6.4B	Transmit signal quality for DC
6.5B	Output RF spectrum emissions for DC
6.6B	Beam correspondence for DC
7.3B	Reference sensitivity level for DC
7.4B	Maximum input level for DC in FR1
7.5B	Adjacent Channel Selectivity for DC in FR1
7.6B	Blocking characteristics for DC in FR1
7.7B	Spurious response for DC in FR1
7.8B	Intermodulation characteristics for DC in FR1
7.9A	Spurious emissions for CA in FR1

## B.4.7 Common UE RF requirements for UL 7.5KHz shift for TDD band n40

The requirements and test cases listed in Table B.4.7-1 are specified in REL-17 version of TS 38.101-1 [2]. For Band n40, UL shift is only applicable to uplink transmissions using a 15 kHz SCS.

**Table B.4.7-1: Common UE RF requirements for UL 7.5KHz shift for TDD Band n40**

Clause	Description
5.4.2.1	NR-ARFCN and channel raster (7.5kHz frequency shift for TDD band n40)

## B.4.8 Common UE RF requirements shared spectrum access

The requirements and test cases listed in Table B.4.8-1 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.8-1: Common UE RF requirements for shared spectrum access**

Clause	Description
5.2A	Operating bands for CA
5.3A	UE channel bandwidth for CA
5.4A	Channel arrangement for CA
5.5A	Configurations for CA
6.2F	Transmitter power for shared spectrum channel access
6.3F	Output power dynamics for shared spectrum channel access
6.4F	Transmit signal quality for shared spectrum channel access
6.5F	Output RF spectrum emissions
7.3F	Reference sensitivity for shared spectrum channel access
7.4	Maximum input level
7.5F	Adjacent channel selectivity
7.6F	Blocking characteristics
7.7F	Spurious response for shared spectrum channel access
7.8F	Intermodulation characteristics for shared spectrum channel access
7.9	Spurious emissions

## B.4.9 Common UE RF requirements for Intra-band and Inter-band NR CA configurations involving shared spectrum access

The requirements and test cases listed in Table B.4.9-1 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.9-1: Common UE RF requirements for Intra-band and Inter-band NR CA configurations involving shared spectrum access**

Clause	Description
6.2F.1A.1	UE maximum output power for inter-band CA
6.2F.2A.1	UE maximum output power reduction for inter-band CA
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA
6.3F.3A.1	General ON/OFF mask for inter-band CA
6.4F.2A.1	Transmit modulation quality for inter-band CA
7.3F.3	$\Delta R_{IB,c}$
7.3F.4	Intra-band contiguous shared spectrum channel access CA
7.3G.5	Inter-band CA with shared spectrum channel access
7.5F.2	Intra-band contiguous shared spectrum channel access CA
7.7F.2	Intra-band contiguous shared spectrum channel access CA

## B.4.10 Common UE RF requirements for 4Rx

The requirements and test cases listed in Table B.4.10-1 are specified in REL-17 version of TS 38.101-1 [2].



**Table B.4.10-1: Common UE RF requirements for 4Rx for single band in FR1**

Clause	Description
6.2.4	Configured transmitted power
7.3	Reference sensitivity
7.4	Maximum input level
7.5	Adjacent Channel Selectivity
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.9	Spurious emissions

The requirements and test cases listed in Table B.4.10-2 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.10-2: Common UE RF requirements for 4Rx for CA in FR1**

Clause	Description
6.2A.4	Configured output power for CA
7.3A	Reference sensitivity for CA
7.4A	Maximum input level for CA
7.5A	Adjacent Channel Selectivity for CA
7.6A	Blocking characteristics for CA
7.7A	Spurious response for CA
7.8A	Intermodulation characteristics for CA
7.9A	Spurious emissions for CA

## B.4.11 Common UE RF requirements for transparent Tx diversity

The requirements and test cases listed in Table B.4.11-1 are specified in in REL-17 version of TS 38.101-1 [2].

**Table B.4.11-1: Common UE RF requirements for a release independent transparent Tx diversity**

Clause	Description
6.2G	Transmitter power for Tx Diversity
6.2G.1	UE maximum output power for Tx Diversity
6.2G.2	UE maximum output power reduction for Tx Diversity
6.2G.3	UE additional maximum output power reduction for Tx Diversity
6.2G.4	Configured transmitted power for Tx Diversity
6.3G	Output power dynamics for Tx Diversity
6.3G.1	Minimum output power for Tx Diversity
6.3G.2	Transmit OFF power for Tx Diversity
6.3G.3	Transmit ON/OFF time mask for Tx Diversity
6.3G.4	Power control for Tx Diversity
6.4G	Transmit signal quality for Tx Diversity
6.4G.1	Frequency error for Tx Diversity
6.4G.2	Transmit modulation quality for Tx Diversity
6.4G.2.1	Error Vector Magnitude
6.4G.2.2	Carrier leakage
6.4G.2.3	In-band emissions
6.4G.2.4	EVM equalizer spectrum flatness for Tx Diversity
6.5G	Output RF spectrum emissions for Tx Diversity
6.5G.1	Occupied bandwidth for Tx Diversity
6.5G.2	Out of band emission for Tx Diversity
6.5G.3	Spurious emission for Tx Diversity
6.5G.4	Transmit intermodulation for Tx Diversity
7.3G	Reference sensitivity for Tx Diversity
F.8	EVM measurement for dual Tx

## B.4.12 Common UE RF requirements for NR V2X

The requirements and test cases listed in Table B.4.12-1 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.12-1: Common UE RF requirements for release independent operating bands and concurrent operation for NR V2X**

Clause	Description
5.2E	Operating band for V2X
5.2E.1	V2X operating bands
5.2E.2	V2X operating bands for con-current operation
6.2E	Transmitter power for V2X
6.3E	Output power dynamics for V2X
6.4E	Transmit signal quality for V2X
6.5E	Output RF spectrum emissions for V2X
7.3E	Reference sensitivity for V2X
7.4E	Maximum input level for V2X
7.5E	Adjacent channel selectivity for V2X
7.6E	Blocking characteristics for V2X
7.7E	Spurious response for V2X
7.8E	Intermodulation characteristics for V2X

The requirements and test cases listed in Table B.4.12-2 are specified in REL-17 version of TS 38.101-3 [2].

**Table B.4.12-2: Common UE RF requirements for release independent intra-band and inter-band concurrent operation for NR V2X**

Clause	Description
6.2E	Transmitter power for V2X in FR1
6.3E	Output power dynamics for V2X
6.4E	Transmit signal quality for V2X operation in FR1
6.5E	Output RF spectrum emissions for V2X operation in FR1
7.3E	Reference sensitivity for V2X operation in FR1
7.4E	Maximum input level for V2X operation in FR1
7.5E	Adjacent channel selectivity for V2X operation in FR1
7.6E	Blocking characteristics for V2X in FR1
7.7E	Spurious response for V2X in FR1
7.8E	Intermodulation characteristics for V2X operation in FR1

### B.4.13 Common UE RF requirements for UL MIMO bands in FR1

The requirements and test cases listed in Table B.4.13-1 and Table B.4.13-2 are specified in REL-17 version of TS 38.101-1 [2].

**Table B.4.13-1: Common UE RF requirements for UL MIMO band in FR1**

Clause	Description
6.2D	Transmitter power for UL MIMO
6.3D	Output power dynamics for UL MIMO
6.4D	Transmit signal quality for UL MIMO
6.5D	Output RF spectrum emissions for UL MIMO
7.3D	Reference sensitivity for UL MIMO
7.4D	Maximum input level for UL MIMO
7.5D	Adjacent channel selectivity for UL MIMO
7.6D	Blocking characteristics for UL MIMO
7.7D	Spurious response for UL MIMO
7.8D	Intermodulation characteristics for UL MIMO

**Table B.4.13-2: Common UL MIMO requirements for shared spectrum channel access in FR1**

Clause	Description
6.2F.1D	UE maximum output power for UL MIMO
6.2F.2D	UE maximum output power reduction for UL MIMO
6.2F.3D	UE additional maximum output power reduction for UL MIMO
6.2F.4D	Configured transmitted power UL MIMO

### B.4.14 Common UE RF requirements for Inter-band CA configurations with Tx switching within NR FR1

The requirements and test cases listed in Table B.4.14-1 are specified in Rel-17 version of TS 38.101-1 [2].

**Table B.4.14-1: Common UE RF requirements for Inter-band CA configurations with Tx switching within NR FR1**

Clause	Description
5.2A.2	Operating bands for inter-band CA
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA

## B.4.15 Common UE RF requirements for SUL configurations with Tx switching within NR FR1

The requirements and test cases listed in Table B.4.15-1 are specified in Rel-17 version of TS 38.101-1 [2].

**Table B.4.15-1: Common UE RF requirements for SUL configurations with Tx switching within NR FR1**

Clause	Description
6.3C.3	Transmit ON/OFF time mask for SUL

## B.4.16 Common UE RF requirements for Inter-band EN-DC with tx switching

The requirements and test cases listed in Table B.4.16-1 are specified in REL-17 version of TS 38.101-3 [4].

**Table B.4.16-1: Common UE RF requirements for Inter-band EN-DC with tx switching**

Clause	Description
5.5B.4	Configuration for Inter-band EN-DC within FR1
6.3B.4	Output power dynamics for switching between two uplink carriers

## Annex C (normative): Common Requirements for high speed train scenario

### C.1 Common RRM requirements for high speed train scenario

The requirements and test cases listed in Table C.1-1 are specified in TS 38.133 Rel-17 and TS 36.133 Rel-17.

**Table C.1-1: RRM requirements for high speed train scenario**

Clause	Description
4.2.2.2 in TS 38.133	Cell Re-selection requirements for intra-frequency NR cells for high speed train scenario
9.2.5 in TS 38.133	NR intra-frequency measurements without measurement gaps for high speed train scenario
9.2.6 in TS 38.133	NR intra-frequency measurements with measurement gaps for high speed train scenario
4.2.2.5 in TS 38.133	Cell Re-selection measurements of inter-RAT E-UTRAN cells for high speed train scenario
9.4.2 in TS 38.133	NR – E-UTRAN FDD measurements for high speed train scenario
9.4.3 in TS 38.133	NR – E-UTRAN TDD measurements for high speed train scenario
9.5.4 in TS 38.133	L1-RSRP measurement requirements for high speed train scenario
4.2.2.5.6 in TS 36.133	Cell Re-selection measurements of inter-RAT NR cells for high speed train scenario
8.1.2.4.21 in TS 36.133	E-UTRAN FDD – NR measurements for high speed train scenario
8.1.2.4.22 in TS 36.133	E-UTRAN TDD – NR measurements for high speed train scenario

### C.2 Common UE demodulation requirements for high speed train scenario

The requirements and test cases listed in Table C.2-1 are specified in TS 38.101-4 Rel-17.

**Table C.2-1: UE demodulation requirements for high speed train scenario**

Clause	Description
5.2.2.2.9 test 1-1	TDD PDSCH requirements for HST-SFN for high speed train scenario with 2RX
5.2.3.2.9 test 1-1	TDD PDSCH requirements for HST-SFN for high speed train scenario with 4RX
5.2.2.1.9 test 1-1	FDD PDSCH requirements for HST-SFN for high speed train scenario with 2RX
5.2.3.1.9 test 1-1	FDD PDSCH requirements for HST-SFN for high speed train scenario with 4RX
5.2.2.2.1 test 1-10, 1-11	TDD PDSCH requirements for HST single tap and multi-path for high speed train scenario with 2RX
5.2.3.2.1 test 1-10, 1-11	TDD PDSCH requirements for HST single tap and multi-path for high speed train scenario with 4RX
5.2.2.1.1 test 1-6, 1-7	FDD PDSCH requirements for HST single tap and multi-path for high speed train scenario with 2RX
5.2.3.1.1 test 1-6, 1-7	FDD PDSCH requirements for HST single tap and multi-path for high speed train scenario with 4RX
5.2.2.1.10 test 1-1, test 1-2	FDD PDSCH requirements for HST DPS for high speed train scenario with 2RX
5.2.2.2.10 test 1-1, test 1-2	TDD PDSCH requirements for HST DPS for high speed train scenario with 2RX
5.2.3.1.10 test 1-1, test 1-2	FDD PDSCH requirements for HST DPS for high speed train scenario with 4RX
5.2.3.2.10 test 1-1, test 1-2	TDD PDSCH requirements for HST DPS for high speed train scenario with 4RX

### C.3 Common RRM requirements for FR1 high speed train scenario enhancement

The requirements and test cases listed in Table C.3-1 are specified in TS 38.133 Rel-17.

**Table C.3-1: RRM requirements for FR1 high speed train scenario enhancement**

Clause	Description
4.2.2.4 in TS 38.133	Cell Re-selection requirements for inter-frequency NR cells for FR1 high speed train scenario
9.2.5 in TS 38.133	NR intra-frequency measurements without measurement gaps for activated SCell and deactivated SCell for FR1 high speed train scenario
9.2.6 in TS 38.133	NR intra-frequency measurements with measurement gaps for active SCell for FR1 high speed train scenario
9.3.4 in TS 38.133	Inter-frequency measurement with measurement gaps for FR1 high speed train scenario
9.3.5 in TS 38.133	Inter-frequency measurement with measurement gaps for FR1 high speed train scenario
9.3.9 in TS 38.133	Inter frequency measurements without measurement gaps for FR1 high speed train scenario
9.5.4 in TS 38.133	L1-RSRP measurement requirements for FR1 high speed train scenario

### C.4 Common UE demodulation requirements for FR1 high speed train scenario enhancement

The requirements and test cases listed in Table C.4-1 are specified in TS 38.101-4 Rel-17.

**Table C.4-1: CA demodulation requirements for FR1 high speed train scenario enhancement**

<b>Clause</b>	<b>Description</b>
5.2A.2.4	PDSCH requirements for HST-SFN CA for FR1 high speed train scenario with 2RX
5.2A.3.4	PDSCH requirements for HST-SFN CA for FR1 high speed train scenario with 4RX
5.2A.2.5	PDSCH requirements for HST-DPS CA for FR1 high speed train scenario with 2RX
5.2A.3.5	PDSCH requirements for HST-DPS CA for FR1 high speed train scenario with 4RX

## Annex D (normative): Common PMI reporting requirements for 16TX and 32TX

### D.1 Common UE PMI reporting requirements for 16TX and 32TX TypeI-SinglePanel Codebook

The requirements and test cases listed in Table D.1-1 are specified in Rel-17 version of TS 38.101-4 [5].

**Table D.1-1: UE PMI reporting requirements for 16TX and 32TX TypeI-SinglePanel Codebook**

Section / Clause	Description
6.3.2.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook for 2Rx FDD
6.3.2.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook for 2Rx FDD
6.3.2.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook for 2Rx TDD
6.3.2.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook for 2Rx TDD
6.3.3.1.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook for 4Rx FDD
6.3.3.1.4	Single PMI with 32TX TypeI-SinglePanel Codebook for 4Rx FDD
6.3.3.2.3	Multiple PMI with 16TX TypeI-SinglePanel Codebook for 4Rx TDD
6.3.3.2.4	Single PMI with 32TX TypeI-SinglePanel Codebook for 4Rx TDD

### D.2 Common UE PMI reporting requirements for 16TX TypeII Codebook

The requirements and test cases listed in Table D.2-1 are specified in Rel-17 version of TS 38.101-4 [5].

**Table D.2-1: UE PMI reporting requirements for 16TX TypeII Codebook**

Section / Clause	Description
6.3.2.1.5	Multiple PMI with 16TX TypeII Codebook for 2Rx FDD
6.3.2.2.5	Multiple PMI with 16TX TypeII Codebook for 2Rx TDD
6.3.3.1.5	Multiple PMI with 16TX TypeII Codebook for 4Rx FDD
6.3.3.2.5	Multiple PMI with 16TX TypeII Codebook for 4Rx TDD



---

## Annex E (normative): Common PDSCH demodulation requirements with LTE CRS rate matching

---

### E.1 Common PDSCH demodulation requirements with LTE CRS rate matching

The requirements and test cases listed in Table E.1-1 are specified in Rel-17 version of TS 38.101-4 [5].

**Table E.1-1: UE PDSCH demodulation requirements with LTE CRS rate matching for TDD band**

Section / Clause	Description
5.2.2.2.4	PDSCH demodulation requirements with LTE CRS rate matching for 2Rx TDD
5.2.3.2.4	PDSCH demodulation requirements with LTE CRS rate matching for 4Rx TDD

## Annex F (Informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-09	RAN#85	R4-1712166				Skeleton TS	0.0.1
2018-03	RAN#86	R4-1802107				TS 38.307 v0.1.0	0.1.0
2018-06	RAN#80	RP-180988				v1.0.0 submitted for plenary approval	1.0.0
2018-06	RAN#80					Approved by plenary – Rel-15 spec under change control	15.0.0
2018-09	RAN#81	RP-181896	0001		F	CR for FR2 Power Classes in TS38.307	15.1.0
2018-12	RAN#82	RP-182362	0002	2	B	CR for TS 38.307	15.2.0
2019-06	RAN#84	RP-191237	0005		B	Addition of missing features for TS 38.307	15.3.0
2019-09	RAN#85	RP-192046	0007	1	B	REL-16 TS 38.307 addition of Annexes for UE RF requirements	16.0.0
2019-12	RAN#86	RP-193019	0009		B	CR for REL-16 TS 38.307 for PC2 EN-DC TDD+TDD	16.1.0
2019-12	RAN#86	RP-193018	0012		B	CR for TS 38.307: additional UE channel bandwidth	16.1.0
2019-12	RAN#86	RP-193036	0014		A	Adding SDL to 38.307	16.1.0
2020-03	RAN#87	RP-200404	0016		A	38.307 CR power class	16.2.0
2020-06	RAN#88	RP-201046	0018		F	CR to 38.307 on clarification of the FR2 multi-band requirement framework	16.3.0
2020-06	RAN#88	RP-200986	0022		A	Maintenance CR to 38307 on a reference spec number R16	16.3.0
2020-06	RAN#88	RP-200959	0023		F	Endorsed CR to 38307 on applicable SUL requirements	16.3.0
2020-06	RAN#88	RP-200965	0019	1	B	CR for 38.307: Introduction of Power Class 1.5	16.3.0
2020-09	RAN#89	RP-201503	0028		B	CR for 38.307: Introduction of Power Class 1.5	16.4.0
2020-12	RAN#90	RP-202485	0032	1	F	CR on adding NR overlapping bands list in TS38.307 in Rel-16	16.5.0
2020-12	RAN#90	RP-202428	0040	1	B	CR to TS 38.307 on release independent update for the Rel.16 EN-DC and NR CA/DC	16.5.0
2020-12	RAN#90	RP-202429	0041		B	CR to TS 38.307 on Release independence of FDD-TDD EN-DC High Power UE	16.5.0
2020-12	RAN#90	RP-202422	0035	1	B	CR on release independent for Rel.16 NR HST RRM requirements	16.5.0
2020-12	RAN#90	RP-202422	0036	1	B	CR on release independent for Rel.16 NR HST UE demodulation requirements	16.5.0
2020-12	RAN#90		0024	3	B	LTE/NR spectrum sharing in Band 40/n40	17.0.0
2021-03	RAN#91	RP-210093	0042		B	CR for 38.307: introduction of power class 5 for FR2	17.1.0
2021-03	RAN#91	RP-210065	0045		A	Draft CR for TS 38.307 on UE demodulation performance requirements (Rel-17)	17.1.0
2021-03	RAN#91	RP-210078	0048		A	CR on release independent for Rel-16 NR HST UE demodulation requirements	17.1.0
2021-03	RAN#91	RP-210098	0051	1	B	CR to 38.307 Release independent for UE power class 2 NR inter-band CA and SUL configurations (R17)	17.1.0
2021-06	RAN#92	RP-211104	0062		A	CR to 38.307 to add interband CA R17 CATA	17.2.0
2021-09	RAN#93	RP-211921	0071		A	CR to TS 38.307 on the definition of the duplex-mode for the band configurations	17.3.0
2021-09	RAN#93	RP-211922	0077		A	CR Correction of common UE RF requirement 38.307 Annex tables R17	17.3.0
2021-12	RAN#94	RP-212828	0080	1	B	CR for REL-17 TS 38.307 for FR1 NE-DC	17.4.0
2021-12	RAN#94	RP-212837	0085		F	Big CR for TS 38.307 Maintenance (Rel-17)	17.4.0
2022-03	RAN#95	RP-220353	0087	1	B	CR to TS 38.307 on Release independence of BCS4 and BCS5	17.5.0
2022-03	RAN#95	RP-220343	0088		B	CR to TS38.307: Release independent for PC2 FDD bands	17.5.0
2022-03	RAN#95	RP-220349	0090	1	B	Big CR for TS 38.307: release independent requirements for TxD	17.5.0
2022-03	RAN#95	RP-220337	0093		A	Big CR for TS 38.307 Maintenance (Rel-17)	17.5.0
2022-03	RAN#95	RP-220352	0096		F	CR for release independent for 4Rx support for NR band	17.5.0
2022-06	RAN#96	RP-221685	0098		B	CR for release independent of Rel.17 NE-DC FR1 and FR2 combinations	17.6.0
2022-06	RAN#96	RP-221686	0099		B	CR for 38.307 to update the release independence for R17 SUL band combinations	17.6.0
2022-06	RAN#96	RP-221670	0100	1	B	Big CR for TS 38.307: release independent for UL MIMO bands (R17)	17.6.0
2022-06	RAN#96	RP-221661	0101	1	B	Big CR to TS 38.307: intra-band CA with MIMO requirements (R17)	17.6.0
2022-06	RAN#96	RP-221677	0102	1	F	CR to TS 38.307: SL requirements (R17)	17.6.0
2022-06	RAN#96	RP-221663	0104		A	Big CR for TS 38.307 Maintenance (Rel-17)	17.6.0
2022-06	RAN#96	RP-221680	0106		B	CR to 38.307: release independent for FR1 HST demodulation (Rel-17)	17.6.0
2022-09	RAN#97	RP-222036	0107		F	CR to R17 38307 to add UL configurations for inter-band combinations and overlapping bands	17.7.0
2022-09	RAN#97	RP-222049	0109		B	CR for introduction of release independence for MMSE-IRC receiver requirements	17.7.0
2022-12	RAN#98-e	RP-223310	0111	1	F	CR on release independent for Rel-17 FR1 HST RRM	17.8.0
2022-12	RAN#98-e	RP-223310	0112		F	CR on release independent for FR1 HST demodulation	17.8.0
2023-03	RAN#99	RP-230501	0115		A	CR 38.307 Addition of FR2 overlapping bands into Annex-A R17	17.9.0
2023-06	RAN#100	RP-231341	0117	1	F	Correction to Frequency arrangement for overlapping operating bands information R17	17.10.0
2023-06	RAN#100	RP-231350	0119		F	CR on 38.307: Cleanup the brackets of section number in UE PDSCH requirements with inter cell interference	17.10.0
2023-12	RAN#102	RP-233351	0129		F	[NR_RF_TxD-Core] Removing brackets from TxD release independent information	17.11.0

2023-12	RAN#102	RP-233332	0138		A	[NR_newRAT-Core] Common UE RF requirements for 4Rx	17.11.0
2023-12	RAN#102	RP-233349	0145	1	F	[NR_NTN_solutions-Core] CR to TS 38.307: release independent requirements for NTN FR1, Rel-17	17.11.0
2024-04	RAN#103	RP-240569	0149		F	(NR_NTN_solutions-Core) CR on TS 38.307 for NR NTN bands release independent, Rel-17	17.12.0
2024-04	RAN#103	RP-240552	0151		F	CR for 38.307 necessary fixes for release pointers R17	17.12.0
2024-04	RAN#103	RP-240555	0153		F	CR to R17 38.307 Release independent requirements for 2CC 1Tx-2Tx switching	17.12.0
2024-04	RAN#103	RP-240557	0155		F	(NR_CADC_R17_2BDL_xBUL-Core) CR for TS38.307: Update and correct the requirements for inter-band NR-DC configurations	17.12.0
2024-04	RAN#103	RP-240557	0160		F	(NR_CA_R17_Intra-Core) Rel-17 Cat F CR for 38.307 Correct and update the requirements for EN-DC and NR-CA	17.12.0

---

# History

<b>Document history</b>		
V17.5.0	April 2022	Publication
V17.6.0	August 2022	Publication
V17.7.0	October 2022	Publication
V17.8.0	January 2023	Publication
V17.9.0	May 2023	Publication
V17.10.0	July 2023	Publication
V17.11.0	February 2024	Publication
V17.12.0	May 2024	Publication