## ETSI TS 148 004 V15.0.0 (2018-07)



Digital cellular telecommunications system (Phase 2+) (GSM);
Base Station System - Mobile-services
Switching Centre (BSS - MSC) interface;
Layer 1 specification
(3GPP TS 48.004 version 15.0.0 Release 15)



# Reference RTS/TSGR-0648004vf00 Keywords GSM

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

The present document can be downloaded from: <u>http://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <a href="https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx">https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</a>

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

#### **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018. All rights reserved.

DECT<sup>™</sup>, PLUGTESTS<sup>™</sup>, UMTS<sup>™</sup> and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP<sup>™</sup> and LTE<sup>™</sup> are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

**GSM**<sup>®</sup> and the GSM logo are trademarks registered and owned by the GSM Association.

## Intellectual Property Rights

#### **Essential patents**

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Trademarks**

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

#### **Foreword**

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <a href="http://webapp.etsi.org/key/queryform.asp">http://webapp.etsi.org/key/queryform.asp</a>.

### Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## Contents

Intell	ectual Property Rights	2
	vord	
	al verbs terminology	
	vord	
	Scope	
	References	
3	Abbreviations	5
4	Layer 1 Specification	6
	ex A (informative): Change History	
	rv	

#### **Foreword**

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

#### where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### 1 Scope

The present document defines the structure of the physical layer (layer 1) of the BSS-MSC interface for supporting traffic channels. Use of the physical layer for supporting Signalling System No.7 signalling links is covered in Technical Specification 3GPP TS 48.006.

The physical layer is the lowest layer in the OSI Reference Model and it supports all functions required for transmission of bit streams on the physical medium.

For the present document only digital transmission will be considered, the use of analogue transmission is a national concern.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- 3GPP TR 21.905: "Vocabulary for 3GPP Specifications". [1] [2] ITU-T Recommendation G.705: "Characteristics of plesiochronous digital hierarchy (PDH) equipment functional blocks". [3] ITU-T Recommendation G.709: "Interfaces for the Optical Transport Network (OTN)". ITU-T Recommendation G.711: "Pulse Code Modulation (PCM) of voice frequencies". [4] [5] ITU-T Recommendation G.732: "Characteristics of primary PCM multiplex equipment operating at 2 048 kbit/s". 3GPP TS 48.006: "Signalling transport mechanism specification for the Base Station System -[6] Mobile-services Switching Centre (BSS - MSC) interface". ANSI T1.102-1993: "Digital Hierarchy - Electrical Interface". [7] [8] ANSI T1.403.01-1999: "Title: Network and Customer Installation Interfaces - (ISDN) Primary Rate Layer 1 Electrical Interfaces Specification (Includes revision of ANSI T1.408-1990 and partial revision of ANSI T1.403-1995)". [9] ANSI T1.107-1995: "Digital Hierarchy - Formats Specifications".
- [10] 3GPP TS 48.020: "Rate adaption on the Base Station System Mobile-services Switching Centre (BSS MSC) interface".

#### 3 Abbreviations

For the purposes of the present document, the abbreviations gieven in 3GPP TR 21.905 [1] apply.

## 4 Layer 1 Specification

All ITU-T recommendations referred to are Blue Book.

Layer 1 shall utilise digital transmission:

- at a rate of 2 048 kbit/s with a frame structure of 32 x 64kbit/s time slots, as specified in ITU-T Recommendation G.705 clause 3 for E1 interface; or
- at a rate of 1 544 kbit/s with a frame structure of 24 x 64 kbit/s time slots, as specified in T1.102 specification for T1 interface.

Therefore the physical/electrical characteristics are defined in ITU-T Recommendation G.703 for E1 interface or ANSI T1.403 specification T1 interface.

The functional characteristics are defined in ITU-T Recommendation G.732 clauses 2 and 3 for E1 interface or ANSI T1.107 specification for T1 interface.

Fault conditions should be treated in accordance with ITU-T Recommendation G.732 clause 4 for E1 interface or ANSI T1.403 specification for T1 interface.

Speech encoding shall be the A-law or Mu-law (for North America) as defined in ITU-T Recommendation G.711.

The idle pattern must be transmitted on every timeslot that is not assigned to a channel, and to every timeslot of a channel that is not allocated to a call. The idle pattern shall be 01010100 in ITU-T based systems and 01111111 in ANSI based systems.

Synchronisation at the BSS for the transmitted 2 048/1544 kbit/s bit stream shall be derived from the received 2 048/1 544 kbit/s bit stream.

Data encoding is covered in Technical Specification 3GPP TS 48.020.

NOTE: A predetermined number of the 56/64kbit/s time slots may be used for signalling, to one or more base station systems. 56kbit/s is applicable to T1 interface only.

## Annex A (informative): Change History

TSG #		TSG Doc.	CR	Rev	,	Subject/Comment		New version	
January 2	2016	-	-	-	Rel	lease	13 version created based on v12.0.0		13.0.0
	Change history								
Date	Meeting	TDoc	(	CR	Rev	Cat	Subject/Comment	1	New
								\	ersion
2017-03	75						Version for Release 14 (frozen at TSG-75)	1	14.0.0
2018-06	SA-80	-	-			-	Update to Rel-15 version (MCC)	1	15.0.0

## History

Document history									
V15.0.0	July 2018	Publication							