

ETSI TS 148 051 V14.0.0 (2017-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Base Station Controller -
Base Transceiver Station (BSC - BTS) interface;
General aspects
(3GPP TS 48.051 version 14.0.0 Release 14)**



Reference

RTS/TSGR-0648051ve00

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Abbreviations	6
4 Interface capabilities.....	6
5 Interface specification objectives	6
6 Interface characteristics.....	7
7 Other technical specifications on the BSC-BTS interface.....	7
7.1 3GPP TS 48.052 BSC-BTS Interface Principles	7
7.2 3GPP TS 48.054 BSC-BTS Layer 1 Specification.....	7
7.3 3GPP TS 48.056 BSC-BTS Layer 2 Specification.....	7
7.4 3GPP TS 48.058 BSC-BTS Layer 3 Specification.....	7
7.5 3GPP TS 12.21 BSC-BTS Operation/Maintenance Signalling	8
7.6 3GPP TS 48.060 Inband Control of Remote Transcoders and Rate Adaptors	8
7.7 3GPP TS 48.061 Inband Control of Remote Transcoders and Rate Adaptors for Half Rate Traffic Channels	8
Annex A (informative): Change History	9
History	10

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document is an introduction to the 48.5xx - 48.6xx series of 3GPP Technical Specifications and deals with the definition of the Base Station Controller (BSC) to Base Transceiver Station (BTS) interface defined inside the Base Station System (BSS) for the GSM system. These Technical Specifications define the basic interface with some identified options requiring further elaboration. The BSC-BTS interface is mandatory within GSM only if the BSC and the BTS are not colocated.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 43.050: "Transmission planning aspects of the speech service in the GSM Public Land Mobile Network (PLMN) system".
- [3] 3GPP TS 48.008: "Mobile Switching Centre - Base Station System (MSC-BSS) interface; Layer 3 specification".
- [4] Void.
- [5] 3GPP TS 48.052: "Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Interface principles".
- [6] 3GPP TS 48.054: "Base Station Controller - Base Transceiver Station (BSC - BTS) interface Layer 1 structure of physical circuits".
- [7] 3GPP TS 48.056: "Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 2 specification".
- [8] 3GPP TS 48.058: "Base Station Controller - Base Transceiver Station (BSC - BTS) interface; Layer 3 specification".
- [9] 3GPP TS 48.060: "Inband control of remote transcoders and rate adaptors for full rate traffic channels".
- [10] 3GPP TS 48.061: "Inband control of remote transcoders and rate adaptors for half rate traffic channels".
- [11] Void.
- [12] Void.
- [13] Void.
- [14] Void.
- [15] Void.
- [16] Void.
- [17] Void.

- [18] Void.
- [19] Void.
- [20] Void.
- [21] Void.
- [22] Void.
- [23] Void.
- [24] 3GPP TS 12.21: "Network Management (NM) procedures and messages on the A-bis interface".
- [25] Void.
- [26] ITU-T Recommendation Q.920: "ISDN user-network interface data link layer - General aspects".
- [27] ITU-T Recommendation Q.921: "ISDN user-network interface - Data link layer specification".

3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 apply.

4 Interface capabilities

The BSC-BTS interface shall be capable of supporting all the services offered to the GSM users and subscribers. In addition it shall also allow control of the radio equipment and radio frequency allocation in the BTS.

5 Interface specification objectives

The BSC to BTS interface specifications should allow the following:

- (I) Connection of various manufacturers BTS/TRX to the same BSC, according to the location of the transcoder.
- (II) The use of several manufacturers BSC to the same type of BTS/TRX, according to the location of the transcoder.
- (III) The use of the same BTS/TRX in any PLMN, according to the location of the transcoder.
- (IV) The use of the same BSC in any PLMN.
- (V) Separate evolution of BSC and BTS/TRX technology.
- (VI) Separate evolution of O & M facilities.
- (VII) Sub-multiplexing of speech channels on a 64 kbit circuit.
- (VIII) Evolution towards lower speech coding rates.
- (IX) Location of transcoders either in BSC or in BTS.
- (X) Support of all services defined in the 02 series of 3GPP TS Technical Specifications.
- (XI) A stepwise expansion of capacity in a BTS.
- (XII) Different physical solution of the various equipment in the BTS.
- (XIII) Support of a single TRX forming a BTS.
- (XIV) Support of a set of TRX'S forming a BTS.
- (XV) Support of a BTS as one entity.

6 Interface characteristics

The interface is defined to be at the terrestrial link of a remote BTS connected to the BSC.

The BSC to BTS interface is specified by a set of characteristics, including:

- a) physical and electrical parameters;
- b) channel structures;
- c) signalling transfer procedures;
- d) configuration and control procedures;
- e) operation and maintenance information support.

The definition of the BSC to BTS/TRX interface follows a layered approach similar to the ISDN. Layer 3 is for the most part based on Technical Specification 3GPP TS 48.008 with additional procedures for control of radio resources. Layer 2 is based on the LAPD protocol. Layer 1 is either digital (at a rate 2 048 kbit/s with a frame structure of 32 x 64 kbit/s time slots or at a rate of 64 kbit/s) or analogue with the data being passed by the use of modems (this latter case is a national option).

In the case that the transcoder is positioned outside the BTS, the overall one way propagation delay between the Point of Interconnection to PSTN/ISDN and the MS is limited to 1,5 ms (approximately 300 km). With the transcoder in the BTS, the limit is 6,5 ms (approximately 1 300 km). These limits may be subject to increase resulting from savings made in the overall network. See also Technical Specification 3GPP TS 43.050.

7 Other technical specifications on the BSC-BTS interface

The full structure of the Technical Specifications specifying the BSC to BTS interface are as follows:

7.1 3GPP TS 48.052 BSC-BTS Interface Principles

3GPP TS 48.052 gives the principle basis for the rest of the specifications specifying the interface between the base station controller and the base transceiver station. It gives the functional split between these two entities.

7.2 3GPP TS 48.054 BSC-BTS Layer 1 Specification

3GPP TS 48.054 defines the structure of the physical layer at the BSC - BTS interface. The physical interface is either chosen as 2 048 kbit/s or as 64 kbit/s, both according to standard ITU-T recommendations.

Depending on location of transcoders, speech is standard A-law or it is 16 kbit/s remote control protocol multiplexed or rate adapted to 64 kbit/s in the same way as data.

7.3 3GPP TS 48.056 BSC-BTS Layer 2 Specification

At layer 2 the signalling information is passed by a standard LAPD protocol mechanism in accordance with the ITU-T Recommendations Q.920 and Q.921.

7.4 3GPP TS 48.058 BSC-BTS Layer 3 Specification

3GPP TS 48.058 specifies the layer 3 procedures used on the BSC-BTS interface for control of the GSM services. The functional split between BSC and BTS is defined in Technical Specification 3GPP TS 48.052.

7.5 3GPP TS 12.21 BSC-BTS Operation/Maintenance Signalling

3GPP TS 12.21 defines the transport mechanism for O&M messages over the Abis interface. O&M procedures and messages are defined in 3GPP TS 12 series.

7.6 3GPP TS 48.060 Inband Control of Remote Transcoders and Rate Adaptors

The transcoder is a part of the BSS and may optionally be located outside the BTS (e.g. at MSC-site or at BSC-site) in order to make it possible to multiplex speech and data channels on the links within the BSS and on the BSC-BTS link.

3GPP TS 48.060 describes the protocol which carries the full rate speech and data frames between the transcoder and the radio link codec across a 16 kbit/sec interface. Both full rate speech and full rate data services are covered. It also defines the signals needed for remote controlling the timing of the transcoder in accordance to the transmission time at the radio link. It also addresses the signals for voice activity and comfort noise. It interfaces the 06- series to the 05-series.

7.7 3GPP TS 48.061 Inband Control of Remote Transcoders and Rate Adaptors for Half Rate Traffic Channels

3GPP TS 48.061 describes the protocol which carries the half rate speech and data frames between the transcoder and the radio link codec across a 16 kbit/s or an 8 kbit/s interface. Both half rate speech and half rate data services are covered. It also defines the signals needed for remote controlling the timing of the transcoder in accordance to the transmission time at the radio link. It also addresses the signals for voice activity and comfort noise.

Annex A (informative): Change History

TSG #	TSG Doc.	CR	Rev	Subject/Comment	New
January 2016	-	-	-	Rel-13 version created based on v12.0.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	75					Version for Release 14 (frozen at TSG-75)	14.0.0

History

Document history		
V14.0.0	April 2017	Publication