

ETSI TS 151 010-2 V5.6.0 (2003-11)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Mobile Station (MS) conformance specification;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification
(3GPP TS 51.010-2 version 5.6.0 Release 5)**



Reference

RTS/TSGG-0351010-2v560

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the TIPHON logo are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	12
3.1 Definitions	12
3.2 Abbreviations	13
4 Conformance to this PICS proforma specification.....	13
Annex A (normative): PICS proforma for GSM mobile stations	14
A.1 Guidance for completing the PICS proforma.....	14
A.1.1 Purposes and structure.....	14
A.1.2 Abbreviations and conventions	14
A.1.3 Instructions for completing the PICS proforma.....	16
A.2 Identification of the implementation	16
A.2.1 Date of the statement	16
A.2.2 Implementation Under Test (IUT) identification	16
A.2.3 System Under Test (SUT) identification	17
A.2.4 Product supplier.....	17
A.2.5 Client	17
A.2.6 PICS contact person	18
A.3 Identification of the protocol.....	18
A.4 PICS proforma tables	18
A.4.1 Global statement of conformance.....	18
A.4.2 Types of Mobile Stations	20
A.4.3 Mobile Station Features.....	29
A.4.4 Teleservices.....	32
A.4.5 Bearer Services.....	33
A.4.6 Supplementary Services	35
A.4.7 Bearer Capability Information.....	37
A.4.8 Additional Information.....	57
A.4.9 SIM Application Toolkit	64
A.4.9.1 SIM Application Toolkit mechanism.....	65
A.4.9.1.1 Terminal Profile	65
A.4.9.1.2 Proactive commands	65
A.4.9.1.2.1 Display Text	66
A.4.9.1.2.2 Get Inkey	67
A.4.9.1.2.3 Get Input.....	67
A.4.9.1.2.4 More Time.....	67
A.4.9.1.2.5 Play Tone.....	68
A.4.9.1.2.6 Poll Interval	68
A.4.9.1.2.7 Refresh.....	69
A.4.9.1.2.8 Set Up Menu.....	69
A.4.9.1.2.9 Select Item.....	69
A.4.9.1.2.10 Send Short Message	70
A.4.9.1.2.11 Send SS.....	70
A.4.9.1.2.12 Send USSD.....	70
A.4.9.1.2.13 Set Up Call	71

A.4.9.1.2.14	Polling Offl.....	71
A.4.9.1.2.15	Provide Local Information.....	71
A.4.9.1.2.20	Get Reader Status	72
A.4.9.1.2.22	Set Up Idle Mode Text	72
A.4.9.1.2.24	Send DTMF.....	72
A.4.9.1.2.27	Open Channel.....	72
A.4.9.1.3	Data Download	73
A.4.9.1.4	Menu Selection	73
A.4.9.1.5	Call Control.....	73
A.4.9.1.6	Timer Expiration.....	74
A.4.9.1.7	Event Download.....	74
A.4.10	Support of UTRAN Radio Access Technology.....	74
Annex B (normative):	Applicability of the individual test	75
Annex C (informative):	Guidance for updating the PICS specification.....	155
C.1	Update of tables of annex A	155
C.2	Identification of PICS items	155
C.3	Update of PICS items.....	155
C.4	Update of table B.1 of annex B	155
C.5	Update of the listed tests of table B.1.....	156
C.6	Update of the applicability conditions of table B.1	156
Annex D (informative):	Change history	157
History		161

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

This 3GPP TS provides the Protocol Implementation Conformance Statement (PICS) proforma for Mobile Stations (MSs), operating in the 400 MHz, 700 MHz, 850 MHz, 900 MHz, 1 800 MHz and 1 900 MHz frequency band (GSM 400, GSM 700, GSM 850, GSM 900, DCS 1 800 and PCS 1 900) within the digital cellular telecommunications system.

The present document is part 2 of a multi-part 3GPP TS covering the digital cellular telecommunications system (GSM Phase2 and Phase 2+ Releases 96, 97, 98, 99, 3GPP Release 4 and 3GPP Release 5); Mobile Station (MS) conformance specification, as identified below:

- Part 1: Conformance specification
Reference: 3GPP TS 51.010-1.
- Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification.
Reference: 3GPP TS 51.010-2.**
- Part 3: Layer 3 (L3) Abstract Test Suite (ATS).
Reference: 3GPP TS 51.010-3.
- Part 4: SIM Application Toolkit conformance specification
Reference: 3GPP TS 11.10-4.

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for Global System for Mobile Stations (MSs), operating in the 450 MHz, 480 MHz, 700 MHz, 750 MHz, 850 MHz, 900 MHz, 1 800 MHz and 1 900 MHz frequency band (GSM 400, GSM 700, GSM 750, GSM 850, GSM 900, DCS 1 800 and PCS 1 900) within the European digital cellular telecommunications system, in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3] and ETS 300 406 [1].

The present document is valid for MS implemented according to GSM Phase2 or Phase2+ R96, or R97, or R98, or R99 or 3GPP Release 4 or 3GPP Release 5.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the relevant Release*.
 - For a GSM Phase 2+ Release 5 MS, references to GSM documents are to version 5.x.y, when available.
 - For a GSM Phase 2+ Release 4 MS, references to GSM documents are to version 4.x.y, when available.
 - For a GSM Phase 2+ Release 1999 MS, references to GSM documents are to version 8.x.y (for 01.-series to 12.-series) or (3.x.y for 21.-series to 35.-series), when available.
 - For a GSM Phase 2+ Release 1998 MS, references to GSM documents are to version 7.x.y, when available.
 - For a GSM Phase 2+ Release 1997 MS, references to GSM documents are to version 6.x.y, when available.
 - For a GSM Phase 2+ Release 1996 MS, references to GSM documents are to version 5.x.y, when available.
 - For a GSM Phase 2 MS, references to GSM documents are to version 4.x.y.

NOTE: References to 3GPP Technical Specifications and Technical Reports throughout this document shall be interpreted according to the Release shown in the formal reference in this clause, based upon the Release of the implementation under test.

Example 1: References for a Ph2 MS shall be interpreted as:

[1] 3GPP TS 01.04 Ph2

[2] 3GPP TS 02.02 Ph2

etc

Example 2: References for a Rel-4 MS shall be interpreted as:

[1] 3GPP TS 21.905 Rel-4

[2] 3GPP TS 22.002 Rel-4

etc

- [1] ETS 300 406 (January 1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

- [2] ISO/IEC 9646-1 (1995): "Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 1: General concepts".
- [3] ISO/IEC 9646-7 (1995): "Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 7: Implementation Conformance Statements".
- [4] 3GPP TS 02.01 (Ph2 to R98): "Principles of telecommunication services supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.001 (R99 onwards): "Principles of circuit telecommunication services supported by a Public Land Mobile Network (PLMN)".
- [5] 3GPP TS 02.02 (Ph2 to R98): "Bearer Services (BS) supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.002 (R99 onwards): "Circuit Bearer Services (BS) supported by a Public Land Mobile Network (PLMN)".
- [6] 3GPP TS 02.03 (Ph2 to R98): "Teleservices supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.003 (R99 onwards): "Circuit Teleservices supported by a Public Land Mobile Network (PLMN)".
- [7] 3GPP TS 02.04 (Ph2 to R98): "General on supplementary services".
3GPP TS 22.004 (R99 onwards): "General on supplementary services".
- [8] 3GPP TS 02.06 (Ph2 to R98): "Types of Mobile Stations (MS)".
- [8a] 3GPP TS 22.101 (R99 onwards): "Service aspects; Service principles".
- [9] 3GPP TS 02.07 (Ph2 to R98): "Mobile Station (MS) features".
- [10] 3GPP TS 02.09 (Ph2 to R99): "Security aspects".
3GPP TS 42.009 (Rel-4 onwards): "Security aspects".
- [11] 3GPP TS 02.11 (Ph2 to R98): "Service accessibility".
3GPP TS 22.011 (R99 onwards): "Service accessibility".
- [12] 3GPP TS 02.16 (Ph2 to R98): "International Mobile station Equipment Identities (IMEI)".
3GPP TS 22.016 (R99 onwards): "International Mobile Equipment Identities (IMEI)".
- [13] 3GPP TS 02.17 (Ph2 to R99): "Subscriber Identity Modules (SIM); Functional characteristics".
3GPP TS 42.017 (Rel-4 onwards): "Subscriber Identity Modules (SIM); Functional characteristics".
- [14] 3GPP TS 02.24 (Ph2 to R98): "Description of Charge Advice Information (CAI)".
3GPP TS 22.024 (R99 onwards): "Description of Charge Advice Information (CAI)".
- [15] 3GPP TS 02.30 (Ph2 to R98): "Man-Machine Interface (MMI) of the Mobile Station (MS)".
3GPP TS 22.030 (R99 onwards): "Man-Machine Interface (MMI) of the User Equipment (UE)".
- [16] 3GPP TS 02.40 (Ph2 to R98): "Procedures for call progress indications".
- [17] 3GPP TS 02.41 (Ph2 to R98): "Operator determined barring".
3GPP TS 22.041 (R99 onwards): "Operator determined barring".
- [18] 3GPP TS 02.81 (Ph2 to R98): "Line identification supplementary services; Stage 1".
3GPP TS 22.081 (R99 onwards): "Line identification supplementary services; Stage 1".

- [19] 3GPP TS 02.82 (Ph2 to R98): "Call Forwarding (CF) supplementary services; Stage 1".
3GPP TS 22.082 (R99 onwards): "Call Forwarding (CF) supplementary services; Stage 1".
- [20] 3GPP TS 02.83 (Ph2 to R98): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 1".
3GPP TS 22.083 (R99 onwards): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 1".
- [21] 3GPP TS 02.84 (Ph2 to R98): "MultiParty (MPTY) supplementary services; Stage 1".
3GPP TS 22.084 (R99 onwards): "MultiParty (MPTY) supplementary services; Stage 1".
- [22] 3GPP TS 02.85 (Ph2 to R98): "Closed User Group (CUG) supplementary services; Stage 1".
3GPP TS 22.085 (R99 onwards): "Closed User Group (CUG) supplementary services; Stage 1".
- [23] 3GPP TS 02.86 (Ph2 to R98): "Advice of Charge (AoC) supplementary services; Stage 1".
3GPP TS 22.086 (R99 onwards): "Advice of Charge (AoC) supplementary services; Stage 1".
- [24] 3GPP TS 03.40 (Ph2 to R98): "Technical realization of the Short Message Service (SMS) Point to Point (PP)".
3GPP TS 23.040 (R99 onwards): "Technical realization of Short Message Service".
- [25] 3GPP TS 03.41 (Ph2 to R98): "Technical realization of Short Message Service Cell Broadcast (SMSCB)".
3GPP TS 23.041 (R99 onwards): "Technical realization of Cell Broadcast Service (CBS)".
- [26] 3GPP TS 03.45 (Ph2 to R99): "Technical Realization of Facsimile Group 3-transparent".
3GPP TS 43.045 (Rel-4 onwards): "Technical Realization of Facsimile Group 3 Service - transparent".
- [27] 3GPP TS 03.46 (Ph2 to R99): "Technical Realization of Facsimile Group 3 Service-non transparent".
3GPP TS 23.146 (Rel-4 onwards): "Technical realization of facsimile group 3 service-non-transparent".
- [28] 3GPP TS 04.02 (Ph2 to R98): "GSM Public Land Mobile Network (PLMN) access reference configuration".
3GPP TS 24.002 (R99 onwards): "GSM-UMTS Public Land Mobile Network (PLMN) Access Reference Configuration".
- [29] 3GPP TS 04.04 (Ph2 to R99): "Layer 1; General requirements".
3GPP TS 44.004 (Rel-4 onwards): "Layer 1; General requirements".
- [30] 3GPP TS 04.05 (Ph2 to R99): "Data Link (DL) layer; General aspects".
3GPP TS 44.005 (Rel-4 onwards): "Data Link (DL) layer; General aspects".
- [31] 3GPP TS 04.06 (Ph2 to R99): "Mobile Station – Base Station System (MS – BSS) interface Data Link (DL) layer specification".
3GPP TS 44.006 (Rel-4 onwards): "Mobile Station - Base Station System (MS - BSS) interface Data Link (DL) layer specification".
- [32] 3GPP TS 04.07 (Ph2 to R98): "Mobile radio interface signalling layer 3; General aspects".
3GPP TS 24.007 (R99 onwards): "Mobile radio interface signalling layer 3; General Aspects".
- [33] 3GPP TS 04.08 (Ph2 to R99): "Mobile radio interface layer 3 specification". (see note)

- 3GPP TS 24.008 (R99 onwards): "Mobile radio interface layer 3 specification; Core network protocols; Stage 3". (see note)
- 3GPP TS 44.008 (Rel-4): "Mobile radio interface layer 3 specification". (see note)
- [34] 3GPP TS 04.10 (Ph2 to R98): "Mobile radio interface layer 3; Supplementary services specification; General aspects".
- 3GPP TS 24.010 (R99 onwards): "Mobile radio interface Layer 3; Supplementary services specification; General aspects".
- [35] 3GPP TS 04.11 (Ph2 to R98): "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- 3GPP TS 24.011 (R99 onwards): "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- [36] 3GPP TS 04.12 (Ph2 to R99): "Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
- 3GPP TS 44.012 (Rel-4 onwards): "Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
- [37] 3GPP TS 04.13 (Ph2 to R99): "Performance requirements on mobile radio interface".
- 3GPP TS 44.013 (Rel-4 onwards): "Performance requirements on the mobile radio interface".
- [37a] 3GPP TS 04.14 (R96 to R99): "Individual equipment type requirements and interworking; Special conformance testing functions".
- 3GPP TS 44.014 (Rel-4 onwards): "Individual equipment type requirements and interworking; Special conformance testing functions".
- [38] 3GPP TS 04.21 (Ph2 to R99): "Rate adaption on the Mobile Station – Base Station System (MS – BSS) interface".
- 3GPP TS 44.021 (Rel-4 onwards): "Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [39] 3GPP TS 04.22 (Ph2 to R98): "Radio Link Protocol (RLP) for data and telematic services on the Mobile Station – Base Station System (MS – BSS) interface and the Base Station System – Mobile-services Switching Centre (BSS – MSC) interface".
- 3GPP TS 24.022 (R99 onwards): "Radio Link Protocol (RLP) for circuit switched bearer and teleservices".
- [40] 3GPP TS 04.80 (Ph2 to R98): "Mobile radio interface layer 3; supplementary services specification; Formats and coding". (See Note 1)
- 3GPP TS 24.080 (R99 onwards): "Mobile radio Layer 3; supplementary service specification; Formats and coding".
- [41] 3GPP TS 04.81 (Ph2 to R98): "Line identification supplementary services; Stage 3".
- 3GPP TS 24.081 (R99 onwards): "Line identification supplementary service; Stage 3".
- [42] 3GPP TS 04.82 (Ph2 to R98): "Call Forwarding (CF) supplementary services; Stage 3".
- 3GPP TS 24.082 (R99 onwards): "Call Forwarding (CF) supplementary service; Stage 3".
- [43] 3GPP TS 04.83 (Ph2 to R98): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 3".
- 3GPP TS 24.083 (R99 onwards): "Call Waiting (CW) and Call Hold (HOLD) supplementary service; Stage 3".
- [44] 3GPP TS 04.84 (Ph2 to R98): "MultiParty (MPTY) supplementary services; Stage 3".

- 3GPP TS 24.084 (R99 onwards): "Multiparty (MPTY) supplementary service; Stage 3".
- [45] 3GPP TS 04.85 (Ph2 to R98): "Closed User Group (CUG) supplementary services; Stage 3".
- 3GPP TS 24.085 (R99 onwards): "Closed User Group (CUG) supplementary services; Stage 3".
- [46] 3GPP TS 04.86 (Ph2 to R98): "Advice of Charge (AoC) supplementary services; Stage 3".
- 3GPP TS 24.086 (R99 onwards): "Advice of Charge (AoC) supplementary service; Stage 3";
- [47] 3GPP TS 04.88 (Ph2 to R98): "Call Barring (CB) supplementary services; Stage 3".
- 3GPP TS 24.088 (R99 onwards): "Call Barring (CB) supplementary service; Stage 3".
- [48] 3GPP TS 04.90 (Ph2 to R98): "Unstructured Supplementary Services Data (USSD)".
- 3GPP TS 24.090 (R99 onwards): "Unstructured Supplementary Service Data (USSD); Stage 3".
- [49] 3GPP TS 05.01 (Ph2 to R99): "Physical layer on the radio path (General description)".
- GPP TS 45.001 (Rel-4 onwards): "Physical layer on the radio path (General description)".
- [50] 3GPP TS 05.02 (Ph2 to R99): "Multiplexing and multiple access on the radio path".
- GPP TS 45.002 (Rel-4 onwards): "Multiplexing and multiple access on the radio path".
- [51] 3GPP TS 05.03 (Ph2 to R99): "Channel coding".
- 3GPP TS 45.003 (Rel-4 onwards): "Channel coding".
- [52] 3GPP TS 05.04 (Ph2 to R99): "Modulation".
- 3GPP TS 45.004 (Rel-4 onwards): "Modulation".
- [53] 3GPP TS 05.05 (Ph2 to R99): "Radio transmission and reception".
- 3GPP TS 45.005 (Rel-4 onwards): "Radio transmission and reception".
- [54] 3GPP TS 05.08 (Ph2 to R99): "Radio subsystem link control".
- 3GPP TS 45.008 (Rel-4 onwards): "Radio subsystem link control".
- [56] 3GPP TS 05.10 (Ph2 to R99): "Radio subsystem synchronisation".
- 3GPP TS 45.010 (Rel-4 onwards): "Radio subsystem synchronization".
- [57] 3GPP TS 05.09 (Ph2 to R99): "Link adaptation".
- 3GPP TS 45.009 (Rel-4 onwards): "Link adaptation".
- [58] 3GPP TS 07.01 (Ph2 to R98): "General on Terminal Adaptation Functions (TAF) for Mobile Stations (MS)".
- 3GPP TS 27.001 (R99 onwards): "General on Terminal Adaptation Functions (TAF) for Mobile Stations (MS)".
- [57] 3GPP TS 02.68 (R96 to R99): "Voice Group Call Service (VGCS); Stage 1".
- 3GPP TS 42.068 (Rel-4 onwards): "Voice Group Call Service (VGCS); Stage 1".
- [58] 3GPP TS 02.69 (R96 to R99): "Voice Broadcast Service (VBS); Stage 1".
- 3GPP TS 42.069 (Rel-4 onwards): "Voice Broadcast Service (VBS); Stage 1".
- [59] 3GPP TS 02.87 (R98): "User-to-User Signalling (UUS); Service description; Stage 1".
- 3GPP TS 22.087 (R99 onwards): "User-to-User Signalling (UUS); Service description, Stage 1".
- [60] 3GPP TS 22.094 (R99 onwards): "Follow Me service description; Stage 1".

- [61] 3GPP TS 03.68 (R96 to R99): "Voice Group Call Service (VGCS); Stage 2".
GPP TS 43.068 (Rel-4 onwards): "Voice Group Call Service (VGCS); Stage 2".
- [62] 3GPP TS 03.69 (R96 to R99): "Digital cellular telecommunications system (See Note 1); Voice Broadcast Service (VBS); Stage 2".
3GPP TS 43.069 (Rel-4 onwards): "Voice Broadcast Service (VBS); Stage 2".
- [63] 3GPP TS 03.87 (R98): "User-to-User Signalling (UUS); Stage 2".
3GPP TS 23.087 (R99 onwards): "User-to-User Signalling (UUS) supplementary service; Stage 2".
- [64] 3GPP TS 23.094 (R99 onwards): "Follow-Me (FM); Stage 2".
- [65] 3GPP TS 04.68 (R96 to R98): "Group Call Control (GCC) protocol".
3GPP TS 44.068 (Rel-4 onwards): "Group Call Control (GCC) protocol".
- [66] 3GPP TS 04.69 (R96 to R99): "Broadcast Call Control (BCC) protocol".
GPP TS 44.069 (Rel-4 onwards): "Broadcast Call Control (BCC) protocol".
- [67] 3GPP TS 04.87 (R98): "User-to-User Signalling (UUS) Supplementary Service; Stage 3".
3GPP TS 24.087: "User-to-User Signalling (UUS); Stage 3".
- [68] 3GPP TS 02.43 (R98 to R99): "Support of Localised Service Area (SoLSA); Service description; Stage 1".
- [69] Void
- [70] 3GPP TS 02.60 (R97 to R98): "General Packet Radio Service; Stage 1; Description".
3GPP TS 22.060 (R99 onwards): "General Packet Radio Service (GPRS); Service Description; Stage 1".
- [71] Void
- [72] 3GPP TS 02.67 (R96 to R98): "enhanced Multi-Level Precedence and Pre-emption service (eMLPP); Stage 1".
3GPP TS 22.067: "enhanced Multi-Level Precedence and Pre-emption service (eMLPP); Stage 1".
- [73] Void.
- [74] 3GPP TS 02.72 (R98): "Call Deflection Service description, Stage 1".
3GPP TS 22.072 (R99 onwards): "Call Deflection (CD); Stage 1".
- [75] Void.
- [76] Void.
- [77] 3GPP TS 02.91 (R96 to R98): "Explicit Call Transfer (ECT)".
3GPP TS 22.091 (R99 onwards): "Explicit Call Transfer (ECT)".
- [78] Void.
- [79] Void.
- [80] Void.
- [81] 3GPP TS 03.38 (Ph2 to R98): "Alphabets and language-specific information for GSM".
3GPP TS 23.038 (R99 onwards): "Alphabets and language-specific information".

- [82] Void.
- [83] Void.
- [84] Void.
- [85] 3GPP TS 03.73 (R98): "Support of Localised Service Area (SoLSA); Stage 2".
3GPP TS 23.073 (R99 onwards): "Support of Localised Service Area (SoLSA); Stage 2".
- [86] Void.
- [87] 3GPP TS 04.65 (R97 to R99): "General Packet Radio Service (GPRS); Mobile Station (MS) - Serving GPRS Support Node (SGSN); Subnetwork Dependent Convergence Protocol (SNDCCP)".
3GPP TS 44.065 (Rel-4 onwards): General Packet Radio Service (GPRS); Mobile Station (MS) - Serving GPRS Support Node (SGSN); Subnetwork Dependent Convergence Protocol (SNDCCP)".
- [88] Void.
- [89] 3GPP TS 09.07 (Ph2 to R98): "General Requirements on Interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
3GPP TS 29.007 (R99 onwards): "General requirements on Interworking between the Public Land Mobile Network (PLMN) and the Intergrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
- [91] 3GPP TS 11.11 (Ph2 to R99): "Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
3GPP TS 51.011 (Rel-4 onwards): "Specification of the Subscriber Identity Module - Mobile Equipment (SIM-ME) interface".
- [92] 3GPP TS 11.12 (Ph2): "Specification of the 3 Volt Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
- [93] 3GPP TS 11.14 (R96 to R99): "Specification of the SIM application toolkit for the Subscriber Identity Module – Mobile Equipment (SIM – ME) interface".
- [94] 3GPP TS 25.331 (R99 onwards): "Radio Resource Control (RRC) protocol specification".
- [95] 3GPP TS 04.18 (R99): "Mobile radio interface layer 3 specification, Radio Resource Control Protocol". (See note)
3GPP TS 44.018 (Rel-4 onwards): "Mobile radio interface layer 3 specification, Radio Resource Control Protocol". (See note).
- [96] 3GPP TS 11.10-4 (R99): " Digital cellular telecommunications system - Mobile Station (MS) conformance specification Part 4: SIM Application Toolkit conformance specification".

NOTE: From Rel-4 onwards, references to 3GPP TS 04.08 are replaced by references to 3GPP TS 44.018 (for RR) and 3GPP TS 24.008 (for CN).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in GSM references, ISO/IEC 9646-1 [2], ISO/IEC 9646-7 [3] and the following apply:

Implementation Conformance Statement (ICS): A statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented.

NOTE: The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: A document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

Protocol ICS (PICS): An ICS for an implementation or system claimed to conform to a given protocol specification.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ICS	Implementation Conformance Statement
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
SCS	System Conformance Statement
SUT	System Under Test

4 Conformance to this PICS proforma specification

If it claims to conform to the present document, the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

A PICS which conforms to this 3GPP TS shall be a conforming PICS proforma completed in accordance with the instructions for completion given in clause A.1.

Annex A (normative): PICS proforma for GSM mobile stations

Notwithstanding the provisions of the copyright clause related to the text of the present document, 3GPP grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.
--

A.1 Guidance for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in relevant specifications may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into subclauses for the following categories of information:

- instructions for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- PICS proforma tables:
 - global statement of conformance;
 - types of mobile stations;
 - support of basic services;
 - support of supplementary services;
 - mobile station features;
 - additional information.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7.

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Reference column

The reference column gives reference to the relevant GSM or 3GPP specifications.

Release column

The Release column indicates the earliest release from which the capability or option is relevant.

Status column

The following notations, defined in ISO/IEC 9646-7, are used for the status column:

M	mandatory – the capability is required to be supported.
O	optional – the capability may be supported or not.
N/A	not applicable – in the given context, it is impossible to use the capability.
X	prohibited (excluded) – there is a requirement not to use this capability in the given context.
O.i	qualified optional – for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table.
Ci	conditional – the requirement on the capability ("M", "O", "X" or "N/A") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." shall be used to avoid ambiguities.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7, are used for the support column:

Y or y	supported by the implementation
N or n	not supported by the implementation
N/A, n/a or -	no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status)

It is also possible to provide a comment to an answer in the space provided at the bottom of the table.

NOTE: As stated in ISO/IEC 9646-7, support for a PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the values or the ranges of values allowed.

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

References to items

For each possible item answer (answer in the support column) within the PICS proforma there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns shall be discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table A.5.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table A.6.

Comments column

This column contains a verbal description of the condition included in the applicability column.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.2.3 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

A.2.4 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.2.5 Client

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.2.6 PICS contact person

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

A.3 Identification of the protocol

This PICS proforma applies to the GSM/3GPP standards listed in the normative references clause of the present document.

A.4 PICS proforma tables

An explicit answer shall be entered, in each of the support column boxes provided, using the notation described in subclause A.1.2.

A.4.1 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the relevant GSM/3GPP specifications. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

A.4.2 Types of Mobile Stations

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the types of a mobile station given in the table below.

Table A.1: Types of Mobile Stations

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
1	Standard GSM Band (P-GSM)	3GPP TS 05.05, 2 3GPP TS 45.005, 2	Phase 2	O.101		TSPC_Type_GSM_P_Band
2	Extended GSM Band (E-GSM), (including standard Band)	3GPP TS 05.05, 2 3GPP TS 45.005, 2	Phase 2	O.101		TSPC_Type_GSM_E_Band
3	R-GSM Band (including standard and E-GSM Band)	3GPP TS 05.05, 2 3GPP TS 45.005, 2	R96	O.101		TSPC_Type_GSM_R_Band
4	DCS 1800 band	3GPP TS 05.05 3GPP TS 45.005, 2	Phase 2	O.101		TSPC_Type_DCS_Band
5	Multiple-band, not simultaneously	3GPP TS 05.05 3GPP TS 45.005, 2	Phase 2	O.102		TSPC_Type_MB_Non Simul
6	Multiple-band, simultaneously	3GPP TS 05.05 3GPP TS 45.005, 2	Phase 2	O.102		TSPC_Type_MB_Simul
7	Small Mobile Station	3GPP TS 05.05, 1.1 3GPP TS 45.005, 1.1	Phase 2	O		TSPC_Type_SmallIMS
8	GSM Power Class 2	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	C101		TSPC_Type_GSM_Class2
9	GSM Power Class 3	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	C101		TSPC_Type_GSM_Class3
10	GSM Power Class 4	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	O		TSPC_Type_GSM_Class4
11	GSM Power Class 5	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	O		TSPC_Type_GSM_Class5
12	DCS Power Class 1	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	O		TSPC_Type_DCS_Class1
13	DCS Power Class 2	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	O		TSPC_Type_DCS_Class2
14	DCS Power Class 3	3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1	Phase 2	O		TSPC_Type_DCS_Class3
15	HSCSD Multislot MS	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	C102		TSPC_Type_HSCSD_Multislot

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
16	GSM 450 band	3GPP TS 05.05, 2 3GPP TS 45.005, 2	R99	O.101		TSPC_Type_GSM_450_Band
17	GSM 480 band	3GPP TS 05.05, 2 3GPP TS 45.005, 2	R99	O.101		TSPC_Type_GSM_480_Band
18	PCS 1900 band	3GPP TS 05.05, 2 3GPP TS 45.005, 2	R98	O.101		TSPC_Type_PCS_Band
19	PCS Power Class 1	3GPP TS 05.05, 4 3GPP TS 45.005, 4	R98	O		TSPC_Type_PCS_Class1
20	PCS Power Class 2	3GPP TS 05.05, 4 3GPP TS 45.005, 4	R98	O		TSPC_Type_PCS_Class2
21	PCS Power Class 3	3GPP TS 05.05, 4 3GPP TS 45.005, 4	R98	O		TSPC_Type_PCS_Class3
22	Multislot Class1	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class1
23	Multislot Class2	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class2
24	Multislot Class3	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class3
25	Multislot Class4	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class4
26	Multislot Class5	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class5
27	Multislot Class6	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class6
28	Multislot Class7	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class7
29	Multislot Class8	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class8
30	Multislot Class9	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class9
31	Multislot Class10	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_Class10

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
32	Multislot Class11	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class11
33	Multislot Class12	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class12
34	Multislot Class13	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class13
35	Multislot Class14	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class14
36	Multislot Class15	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class15
37	Multislot Class16	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class16
38	Multislot Class17	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class17
39	Multislot Class18	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R96	O		TSPC_Type_Multislot_ Class18
40	Multislot Class19	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class19
41	Multislot Class20	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class20
42	Multislot Class21	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class21
43	Multislot Class22	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class22
44	Multislot Class23	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class23
45	Multislot Class24	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class24
46	Multislot Class25	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class25
47	Multislot Class26	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class26

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
48	Multislot Class27	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class27
49	Multislot Class28	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class28
50	Multislot Class29	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_Multislot_ Class29
51	GPRS Multislot operation	3GPP TS 02.60 3GPP TS 22.060	R97	C103		TSPC_Type_GPRS_M ultislot_operation
52	EGPRS capable of 8PSK in Uplink, of all Multislot classes	3GPP TS 04.60 3GPP TS 44.060	R99	O		TSPC_Type_EGPRS_ 8PSK_uplink
53	GSM 700 band	3GPP TS 45.005, 2	Release 4	O.101		TSPC_Type_GSM_70 0_Band
54	GSM 750 band	3GPP TS 45.005, 2	Release 4	O.101		TSPC_Type_GSM_75 0_Band
55	GSM 850 band	3GPP TS 05.05, 2 3GPP TS 45.005, 2	R99	O.101		TSPC_Type_GSM_85 0_Band
56	Support of UTRAN Radio Access Technology	3GPP TS 25.301	R99	O		TSPC_Type_UTRAN
57	Support of GPRS Multislot class on the uplink	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	C105		TSPC_Type_GPRS_M ultislot_uplink
58	Support of COMPACT	3GPP TS 05.08 3GPP TS 45.008	R99	O		TSPC_COMPACT
59	DTM Multislot Class 1	3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4	R99	C107		TSPC_DTM_Multislot_ Class_1
60	DTM Multislot Class 5	3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4	R99	C108		TSPC_DTM_Multislot_ Class_5
61	DTM Multislot Class 9	3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4	R99	O		TSPC_DTM_Multislot_ Class_9
62	Support of singleslot allocation in DTM	3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4	R99	O		TSPC_DTM_Singleslot _Allocation
63	Support of UTRAN FDD	3GPP TS 25.301	R99	O		TSPC_Type_UTRAN_ FDD
64	Support of UTRAN TDD	3GPP TS 25.301	R99	O		TSPC_Type_UTRAN_ TDD
65	Support of Conventional GPS	3GPP 03.71	R98	O		TSPC_Conv-GPS
66	EGPRS Multislot operation	3GPP TS 02.60 3GPP TS 22.060	R99	C104		TSPC_Type_EGPRS_ Multislot_operation
67	GPRS Multislot Class1	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class1
68	GPRS Multislot Class2	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class2

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
69	GPRS Multislot Class3	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class3
70	GPRS Multislot Class4	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class4
71	GPRS Multislot Class5	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class5
72	GPRS Multislot Class6	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class6
73	GPRS Multislot Class7	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class7
74	GPRS Multislot Class8	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class8
75	GPRS Multislot Class9	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class9
76	GPRS Multislot Class10	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class10
77	GPRS Multislot Class11	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class11
78	GPRS Multislot Class12	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class12
79	GPRS Multislot Class13	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class13
80	GPRS Multislot Class14	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class14
81	GPRS Multislot Class15	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class15
82	GPRS Multislot Class16	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class16
83	GPRS Multislot Class17	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class17
84	GPRS Multislot Class18	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class18

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
85	GPRS Multislot Class19	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class19
86	GPRS Multislot Class20	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class20
87	GPRS Multislot Class21	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class21
88	GPRS Multislot Class22	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class22
89	GPRS Multislot Class23	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class23
90	GPRS Multislot Class24	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class24
91	GPRS Multislot Class25	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class25
92	GPRS Multislot Class26	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class26
93	GPRS Multislot Class27	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class27
94	GPRS Multislot Class28	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class28
95	GPRS Multislot Class29	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R97	O		TSPC_Type_GPRS_M ultislot_Class29
96	EGPRS Multislot Class1	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class1
97	EGPRS Multislot Class2	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class2
98	EGPRS Multislot Class3	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class3
99	EGPRS Multislot Class4	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class4
100	EGPRS Multislot Class5	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class5

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
101	EGPRS Multislot Class6	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class6
102	EGPRS Multislot Class7	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class7
103	EGPRS Multislot Class8	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class8
104	EGPRS Multislot Class9	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class9
105	EGPRS Multislot Class10	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class10
106	EGPRS Multislot Class11	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class11
107	EGPRS Multislot Class12	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class12
108	EGPRS Multislot Class13	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class13
109	EGPRS Multislot Class14	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class14
110	EGPRS Multislot Class15	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class15
111	EGPRS Multislot Class16	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class16
112	EGPRS Multislot Class17	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class17
113	EGPRS Multislot Class18	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class18
114	EGPRS Multislot Class19	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class19
115	EGPRS Multislot Class20	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class20
116	EGPRS Multislot Class21	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class21

Item	Type of Mobile Station	Ref.	Release	Status	Support	Mnemonic
117	EGPRS Multislot Class22	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class22
118	EGPRS Multislot Class23	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class23
119	EGPRS Multislot Class24	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class24
120	EGPRS Multislot Class25	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class25
121	EGPRS Multislot Class26	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class26
122	EGPRS Multislot Class27	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class27
123	EGPRS Multislot Class28	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class28
124	EGPRS Multislot Class29	3GPP TS 05.02, B.1 3GPP TS 45.002, B.1	R99	O		TSPC_Type_EGPRS_ Multislot_Class29
O.101	At least one of these items shall be supported					
O.102	At least two of the following items shall be supported:					
O.103	A.1/1 OR A.1/2 OR A.1/3 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/53 OR A.1/54 OR A.1/55 IF A.2/41 THEN at least one of these items shall be supported ELSE N/A					-- TSPC_GPRS
C101	IF A.1/7 THEN X ELSE O					-- TSPC_Type_SmallMS
C102	IF (A.1/22 OR A.1/23 OR A.1/24 OR A.1/25 OR A.1/26 OR A.1/27 OR A.1/28 OR A.1/29 OR A.1/30 OR A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39) THEN M ELSE N/A					-- (TSPC_Type_Multislot_Class1 OR ...OR TSPC_Type_Multislot_Class18)
C103	IF A.2/41 AND (A.1/67 OR A.1/68 OR A.1/69 OR A.1/70 OR A.1/71 OR A.1/72 OR A.1/73 OR A.1/74 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN M ELSE N/A					-- (TSPC_Type_GPRS_Multislot_Class1 OR ...OR Type_GPRS_Multislot_Class29) AND TSPC_GPRS
C104	IF A.2/42 AND (A.1/96 OR A.1/97 OR A.1/98 OR A.1/99 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/103 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124) THEN M ELSE N/A					-- (TSPC_Type_EGPRS_Multislot_Class1 OR ...OR Type_EGPRS_Multislot_Class29) AND TSPC_EGPRS
C105	IF A.1/51 THEN O ELSE N/A					-- TSPC_Type_GPRS_Multislot_uplink
C106	VOID					VOID
C107	IF A.1/62 THEN M ELSE N/A					-- TSPC_DTM_Singleslot_Allocation
C108	IF A.2/62 THEN M ELSE N/A					-- TSPC_DTM

Comments:

Table A.1b: MS Feature Release Supported

Item	MS Feature Release Supported	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Release of GPRS supported.	3GPP TS 02.06 3GPP TS 22.060	R97	C1b01		TSPC_MS_GPRS_RELEASE	R97, R98, R99, Release 4, Release 5	
2	Release of AMR supported.	3GPP TS 05.09, 3.4	R98	C1b02		TSPC_MS_AMR_RELEASE	R98, R99, Release 4, Release 5	
3	Release of EGPRS supported.	3GPP TS 02.06 3GPP TS 22.060	R99	C1b03		TSPC_MS_EGPRS_RELEASE	R99, Release 4, Release 5	
C1b01	IF A2/41 THEN M ELSE N/A				-- TSPC_GPRS			
C1b02	IF A25/79 THEN M ELSE N/A				-- TSPC_AddInfo_Full_rate_version_3			
C1b03	IF A.2/42 THEN M ELSE N/A				-- TSPC_EGPRS			

A.4.3 Mobile Station Features

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the mobile station features given in the table below.

Table A.2: Mobile Station Features

Item	Mobile Station Feature	Ref.	Release	Status	Support	Mnemonic
1	Display of Called Number.	3GPP TS 02.07 B.1.1	Phase 2	C202		TSPC_Feat_DCN
2	Indication of Call Progress Signals.	3GPP TS 02.07 B.1.2	Phase 2	C204		TSPC_Feat_CPSind
3	Country/PLMN Indication.	3GPP TS 02.07 B.1.3	Phase 2	C202		TSPC_Feat_PLMNind
4	Country/PLMN Selection.	3GPP TS 02.07 B.1.4	Phase 2	M		TSPC_Feat_PLMNsel
5	Keypad.	3GPP TS 02.07 B.1.5	Phase 2	O		TSPC_Feat_Keypad
6	IMEI.	3GPP TS 02.07 B.1.6	Phase 2	M		TSPC_Feat_IMEI
7	Short Message Overflow Indication.	3GPP TS 02.07 B.1.8	Phase 2	M		TSPC_Feat_SMoverflow
8	DTE /DCE Interface.	3GPP TS 02.07 B.1.9	Phase 2	O		TSPC_Feat_DTE_DCE
9	ISDN "S" Interface.	3GPP TS 02.07 B.1.10	Phase 2	O		TSPC_Feat_Sinterface
10	International Access Function.	3GPP TS 02.07 B.1.11	Phase 2	O		TSPC_Feat_IntAccess
11	Service Indicator.	3GPP TS 02.07 B.1.12	Phase 2	C203		TSPC_Feat_ServInd
12	Autocalling restriction capabilities.	3GPP TS 02.07 annex A	Phase 2	C205		TSPC_Feat_AutocallRestrict
13	Dual Tone Multi Frequency function.	3GPP TS 02.07 B.1.15	Phase 2	C201		TSPC_Feat_DTMF
14	Subscription Identity Management.	3GPP TS 02.07 B.1.16	Phase 2	M		TSPC_Feat_SIM
15	On/Off switch.	3GPP TS 02.07 B.1.17	Phase 2	O		TSPC_Feat_OnOff
16	Subaddress.	3GPP TS 02.07 B.1.18	Phase 2	O		TSPC_Feat_Subaddresses
17	Support of Encryption A5/1.	3GPP TS 02.07 B.1.19	Phase 2	M		TSPC_Feat_A51
18	Support of Encryption A5/2.	3GPP TS 02.07 B.1.19	Phase 2	M		TSPC_Feat_A52
19	Short Message Service Cell Broadcast DRX.	3GPP TS 02.07 B.1.20	Phase 2	O		TSPC_Feat_SMS_CB_DRX
20	Abbreviated Dialling.	3GPP TS 02.07 B.3.1	Phase 2	O		TSPC_Feat_AD
21	Fixed Number Dialling.	3GPP TS 02.07 B.3.2	Phase 2	O		TSPC_Feat_FND
22	Barring of Outgoing Calls.	3GPP TS 02.07 B.3.3	Phase 2	O		TSPC_Feat_BO
23	DTMF Control Digits Separator.	3GPP TS 02.07 B.3.4	Phase 2	O		TSPC_Feat_DTMF_CDS
24	Selection of Directory No in Short Messages.	3GPP TS 02.07 B.3.5	Phase 2	O		TSPC_Feat_SM_Dir
25	Last Numbers Dialed.	3GPP TS 02.07 B.3.6	Phase 2	O		TSPC_Feat_LND
26	At least one autocalling feature.	3GPP TS 02.07 annex A	Phase 2	O		TSPC_Feat_Autocall
27	Alphanumeric display.	3GPP TS 02.07 2	Phase 2	O		TSPC_Feat_Alphanumeric_Display
28	Other means of display.	3GPP TS 02.07 2	Phase 2	O		TSPC_Feat_Other_Means_of_Display

Item	Mobile Station Feature	Ref.	Release	Status	Support	Mnemonic
29	Speech indicator.	3GPP TS 02.07 2	Phase 2	O		TSPC_Feat_Speech_Indicator
30	Support of the extended Short message cell broadcast channel	3GPP TS 02.07 B.1.23	R96	O		TSPC_Ext_SMcell_BC
31	Support of Additional Call Set-up MMI Procedures	3GPP TS 02.07 B.1.24	R96	O		TSPC_AddCall_Su_MMI_Proc
32	Network Identity and Timezone	3GPP TS 02.07 B.1.25	R96	O		TSPC_Feat_NID_Timezone
33	Ciphering Indicator	3GPP TS 02.07 B.1.22(B.1.2.26)	Phase 2 (R96)	C202		TSPC_Feat_Ciphering
34	Network's indication of alerting in the MS \$(NI Alert in MS)\$	3GPP TS 02.07 B.1.27	R96	O		TSPC_Feat_NI_Alertin MS
35	ME-SIM lock	3GPP TS 02.07 B.3.7	R96	O		TSPC_SIM_Lock
36	Service Dialling Numbers	3GPP TS 02.07 B.3.8	R96	O		TSPC_Service_No
37	Extended timing advance	3GPP TS 05.10, 5.5	R99	C206		TSPC_Feat_Ext_TA
38	Support of SoLSA	3GPP TS 02.43, 3GPP TS 22.043 B.1.27 3GPP TS 03.73 3GPP TS 23.073	R98	O		TSPC_SoLSA
39	Audible Indication of Service Tones	3GPP TS 02.07, B.1.27	R96	O		TSPC_Feat_audible_tone
40	Autocalling_Cause 27 Implemented in Cat 3	3GPP TS 02.07 annex A	Phase 2	O		TSPC_Feat_Cause27Cat3
41	Support of GPRS	3GPP TS 02.60 3GPP TS 22.060	R97	O		TSPC_GPRS
42	Support of EGPRS	3GPP TS 02.60 3GPP TS 22.060	R99	O		TSPC_EGPRS
43	Support of GPRS Encryption	3GPP TS 02.60 3GPP TS 22.060	R98	C207		TSPC_GPRS_Encryp
44	Control of Supplementary Services	3GPP TS 02.07, 2	Phase 2	O		TSPC_Control_SS
45	Short message	3GPP TS 02.07, 2	Phase 2	O		TSPC_Supp_SM
46	Emergency calls capabilities	3GPP TS 02.07, B.1.14	Phase 2	C211		TSPC_Emergency_call_cap
47	GPRS operation mode class A	3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5	R97	C209		TSPC_operation_mode_A
48	GPRS operation mode class B	3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5	R97	C209		TSPC_operation_mode_B
49	GPRS operation mode class C	3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5	R97	C209		TSPC_operation_mode_C
50	MS supporting SMS over GPRS	3GPP TS 22.060, 5.4	R99	O		TSPC_SMS_over_GPRS
51	void					
52	Support of GSM-CTS	3GPP TS 05.08 11 3GPP TS 45.008, 11	R98	O		TSPC_GSM_CTS
53	Support of ECSD	3GPP TS 05.08, B.6 3GPP TS 45.008, B.6	R99	O		TSPC_ECSD
54	GPRS test mode A	3GPP TS 04.14 5.4	R97	C208		TSPC_GPRS_Testmode_A

Item	Mobile Station Feature	Ref.	Release	Status	Support	Mnemonic
55	GPRS test mode B	3GPP TS 04.14 5.4	R97	C208		TSPC_GPRS_Testmode_B
56	EGPRS test mode	3GPP TS 04.14		C210		TSPC_EGPRS_Testmode
57	Support of MS-Assisted E-OTD	3GPP TS 03.71 7.6.1	R98	O		TSPC_EOTD_ASSIST
58	Non-zero value of Non_DRX_Timer	3GPP TS 04.60	R97	C208		TSPC_non_zero_Non_DRX_Timer
59	Support of MS-Based GPS	3GPP TS 03.71 7.6.1	R98	O		TSPC_A-GPS_Based
60	Support of MS-Assisted GPS	3GPP TS 03.71 7.6.1	R98	O		TSPC_A-GPS_Assist
61	Privacy Option Supported	3GPP TS 03.71 7.6.1	R98	O		TSPC_PRIVACY
62	Support of DTM	3GPP TS 24.008 10.5.1.7	R99	O		TSPC_DTM
63	Support MS Assisted EOTD Performance for GMSK	3GPP TS 05.05 Annex I	R98	O		TSPC_EOTD_ASSIST AND TSPC_PERF_GMSK
64	Support MS Assisted EOTD Performance for 8PSK	3GPP TS 05.05 Annex I	R99	O		TSPC_EOTD_ASSIST AND TSPC_PERF_8PSK
65	Support of EGPRS Packet Access enhancement	3GPP TS 04.18 3.5.2.1.2 3GPP TS 04.60 7.1.2.1	R99 only	O		TSPC_EGPRS_ENHANC
66	Support of Network Assisted Cell Change	3GPP TS 24.008 10.5.1.7, 10.5.5.12a	Rel-4	O		TSPC_NACC
67	Support of MT SMS over GPRS	3GPP TS 22.060, 5.4	R99	O		TSPC_MT_SMS_over_GPRS
C201	IF A.3/1 OR A.3/2 OR A.4/20 OR A.4/21 THEN M ELSE N/A					-- TSPC_Serv_TS11 OR TSPC_Serv_TS12 OR TSPC_Serv_BS61 OR TSPC_Serv_BS81
C202	IF A.2/27 THEN M ELSE N/A					-- TSPC_Feat_Alphanum_Display
C203	IF A.2/27 OR A.2/28 THEN M ELSE N/A					-- TSPC_AlphaNum_Display OR TSPC_Other_Means_of_Display
C204	IF A.2/29 THEN M ELSE N/A					-- TSPC_Speech_Indicator
C205	IF A.2/26 OR A.2/40 THEN M ELSE N/A					-- TSPC_Feat_Autocall
C206	IF A.1/16 OR A.1/17 THEN M ELSE N/A					-- TSPC_Feat_Ext_TA
C207	IF A.2/41 OR A.2/42 THEN M ELSE N/A					-- TSPC_GPRS OR TSPC_EGPRS
C208	IF A.2/41 THEN O ELSE N/A					-- TSPC_GPRS
C209	IF A.2/41 or A.2/42 THEN at least one of these items shall be supported ELSE N/A					-- TSPC_GPRS OR TSPC_EGPRS
C210	IF A.2/42 THEN O ELSE N/A					-- TSPC_EGPRS
C211	IF A.3/2 THEN M ELSE N/A					-- TSPC_Serv_TS12

Comments:

A.4.4 Teleservices

The supplier of the implementation shall state the support of the implementation for each of the teleservices given in the table below.

Table A.3: Teleservices

Item	Teleservice	Ref.	Release	Status	Support	Mnemonic
1	Telephony.	3GPP TS 02.03 A.1.1 3GPP TS 22.003, A.1.1	Phase 2	O		TSPC_Serv_TS11
2	Emergency Call.	3GPP TS 02.03 A.1.2 3GPP TS 22.003, A.1.2	Phase 2	C301		TSPC_Serv_TS12
3	Short Message MT/PP.	3GPP TS 02.03 A.1.3.1 3GPP TS 22.003, A.1.3.1	Phase 2	O		TSPC_Serv_TS21
4	Short Message MO/PP.	3GPP TS 02.03 A.1.3.2 3GPP TS 22.003, A.1.3.2	Phase 2	O		TSPC_Serv_TS22
5	SMS Cell Broadcast.	3GPP TS 02.03 A.1.3.3 3GPP TS 22.003, A.1.3.3	Phase 2	O		TSPC_Serv_TS23
6	Teleservice Alternate Speech and G3 fax.	3GPP TS 02.03 A.1.4 3GPP TS 22.003, A.1.4	Phase 2	O		TSPC_Serv_TS61
7	Teleservice Automatic G3 fax.	3GPP TS 02.03 A.1.5 3GPP TS 22.003, A.1.5	Phase 2	O		TSPC_Serv_TS62
8	Voice Group Call Service (VGCS)	3GPP TS 02.03 A.1.6 3GPP TS 22.003, A.1.6	R96	O		TSPC_Serv_TS91
9	Voice Broadcast Service (VBS)	3GPP TS 02.03 A.1.7 3GPP TS 22.003, A.1.7	R96	O		TSPC_Serv_TS92
10	SMS description	3GPP TS 02.03 A.1.3.4 3GPP TS 22.003, A.1.3.4	R96	O		TSPC_SMS_description
C301		IF A.3/1 THEN M ELSE O		-- TSPC_Serv_TS11		

Comments:

A.4.5 Bearer Services

The supplier of the implementation shall state the support of the implementation for each of the bearer services given in the table below.

Table A.4: Bearer Services

Item	Bearer Service	Ref.	Release	Status	Support	Mnemonic
1	Data circuit duplex async. 300 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS21
2	Data circuit duplex async. 1 200 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS22
3	Data circuit duplex async. 1 200/75 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS23
4	Data circuit duplex async. 2 400 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS24
5	Data circuit duplex async. 4 800 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS25
6	Data circuit duplex async. 9 600 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS26
7	Data circuit duplex sync. 1 200 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS31
8	Data circuit duplex sync. 2 400 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS32
9	Data circuit duplex sync. 4 800 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS33
10	Data circuit duplex sync. 9 600 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS34
11	PAD Access 300 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS41
12	PAD Access 1 200 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS42
13	PAD Access 1 200/75 bits/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS43
14	PAD Access 2 400 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS44
15	PAD Access 4 800 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS45
16	PAD Access 9 600 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS46
17	Packet Access 2 400 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS51
18	Packet Access 4 800 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS52
19	Packet Access 9 600 bit/s.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS53

Item	Bearer Service	Ref.	Release	Status	Support	Mnemonic
20	Alternate Speech/Data.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS61
21	Speech Followed by Data.	3GPP TS 02.02 3 3GPP TS 22.002, 3	Phase 2	O		TSPC_Serv_BS81
22	GPRS	3GPP TS 02.02 3 3GPP TS 22.002, 3	R97	O		TSPC_Serv_BS70

Comments:

A.4.6 Supplementary Services

The supplier of the implementation shall state the support of the implementation for each of the supplementary services given in the table below.

Table A.5: Supplementary Services

Prerequisite: A.25/29 -- TSPC_AddInfo_SS (3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1, (3GPP TS 22.004 4)).

Item	Supplementary Service	Ref.	Release	Status	Support	Mnemonic
1	Calling Line Identification Presentation.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_CLIP
2	Calling Line Identification Restriction.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_CLIR
3	Connected Line Identification Presentation.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_COLP
4	Connected Line Identification Restriction.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_COLR
5	Call Forwarding Unconditional.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_CFU
6	Call Forwarding on Mobile Subscriber Busy.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_CFB
7	Call Forwarding on No Reply.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_CFNRey
8	Call Forwarding on Mobile Subscriber Not Reachable.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_CFNRey
9	Call Waiting.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_CW
10	Call Hold.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_HOLD
11	Multi Party Service.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_MPTY
12	Closed User Group.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_CUG
13	Advice of Charge (Information).	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_AoCI
14	Advice of Charge (Charging).	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_Serv_SS_AoCC

Item	Supplementary Service	Ref.	Release	Status	Support	Mnemonic
15	Barring of All Outgoing Calls.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_BAOC
16	Barring of Outgoing International Calls.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_BOIC
17	Barring of Outgoing International Calls except those directed to the Home PLMN Country.	3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_BOICexHC
18	Barring of All Incoming Calls.	3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_BAIC
19	Barring of Incoming Calls when Roaming Outside the Home PLMN Country.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	M		TSPC_Serv_SS_BICRoam
20	Unstructured SS Data.	3GPP TS 02.30, 4.5.2.2, 3GPP TS 02.07 B.2.1	Phase 2	O		TSPC_Serv_SS_unstructured
21	enhanced Multi-Level Precedence and Pre-emption service (eMLPP)	3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.67, 3.1 3GPP TS 22.067, 43.1	R96	O		TSPC_Serv_SS_eMLPP
22	Call Deflection	3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.72, 3.2 3GPP TS 22.072, 3.2	R96	O		TSPC_Serv_SS_CD
23	User-to-User signalling	3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.87, 5.1 3GPP TS 22.087, 5.1	R96	O		TSPC_Serv_SS_UUS
24	Explicit Call Transfer	3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.91 3GPP TS 22.091,	R96	O		TSPC_Serv_SS_ECT
25	Implicit UUS1	3GPP TS 02.87 5.1 3GPP TS 22.087, 5.1	R96	O		TSPC_Serv_SS_ImpUUS1
26	Sending of implicit UUS1 in the ALERTING message	3GPP TS 03.87 5.3.2 3GPP TS 23.087, 5.3.1	R98	O		TSPC_Serv_SS_Send_UUS1_ALERTING

Item	Supplementary Service	Ref.	Release	Status	Support	Mnemonic
27	Sending of implicit UUS1 in the CONNECT message	3GPP TS 03.87 5.3.2 3GPP TS 23.087, 5.3.2	R98	O		TSPC_Serv_SS_Send_UUS1_CONNECT
28	Follow Me	3GPP TS 02.94 3GPP TS 22.094,	R99	O		TSPC_Serv_SS_Follow Me
29	User-to-Dispatcher Information	3GPP TS 43.068, 3.1 3GPP TS 43.069, 3.1	Release 4	O		TSPC_Serv_UTDI
30	Compressed User-to-Dispatcher	3GPP TS 43.068 4.2.7 3GPP TS 43.069, 4.2.7	Release 4	O		TSPC_Serv_Compr_UTDI
31	Completion of Calls to Busy SS	3GPP TS 02.04 4 3GPP TS 22.004, 4	R97	O		TSPC_CCBS_SS
32	Completion of Calls to Busy Requests	3GPP TS 02.04 4 3GPP TS 22.004, 4	R97	O		TSPC_CCBS_Req
33	Support of Private Numbering Plan SS	3GPP TS 02.04 4 3GPP TS 22.004, 4	R97	O		TSPC_SPNP_SS
34	Support of Private Numbering Plan, Numbering Plans	3GPP TS 02.04 4 3GPP TS 22.004, 4	R97	O		TSPC_Num_plans
35	Name Identification SS	3GPP TS 02.04 4 3GPP TS 22.004, 4	R97	O		TSPC_CNAP

Comments:

A.4.7 Bearer Capability Information

The supplier of the implementation shall state the support of possible bearer capabilities in the tables below. The allowed Bearer Capabilities are defined by diagrams given in 3GPP TS 07.01 (3GPP TS 27.001) annex 2. The support of Bearer Capabilities shall be stated by selecting supported coding of Bearer Capability Elements for each group of Bearer Capabilities associated with one diagram.

This clause provides a table for each diagram where the supplier shall state which element values are supported for the bearer capability if more than one element value is allowed. It is assumed that in many cases, all allowed combinations defined by the diagram with respect to the supported values are implemented. If this is not the case, the supplier shall state the restrictions immediately following the table. The abbreviations of element values are defined 3GPP TS 07.01(3GPP TS 27.001) table II.5. For detailed description of element values and coding, please refer to 3GPP TS 04.08 (3GPP TS 24.008), 10.5.4.5.

[Editor's note: Table A.6 to be updated according to the information in the following tables. The Releases and allowed values in brackets refer to the PICS items in brackets]

Table A.6: Groups for possible bearer capabilities

Item	Bearer Capability Group	Ref.	Release	Status	Support	Mnemonic
1	Bearer Service 21(20) .. 26, unrestricted digital information transfer capability.	3GPP TS 07.01 B.1.2.1 3GPP TS 27.001, B.1.2.1	Phase 2 (R96)	O		TSPC_BS2x_UDI
2	Bearer Service 21(20) .. 26, 3.1 kHz audio ex-PLMN information transfer capability.	3GPP TS 07.01 B.1.2.2 3GPP TS 27.001, B.1.2.2	Phase 2 (R96)	O		TSPC_BS2x_3.1kHz
3	Bearer Service 31(30) .. 34, unrestricted digital information transfer capability; Non-X.32 Cases (BS 31 .. BS 34).	3GPP TS 07.01 B.1.3.1.1 3GPP TS 27.001, B.1.3.1.1	Phase 2 (R96)	O		TSPC_BS3x_UDI_no nX.32
4	Bearer Service 31(30) .. 34, unrestricted digital information transfer capability; X.32 Cases.	3GPP TS 07.01 B.1.3.1.2 3GPP TS 27.001, B.1.3.1.1	Phase 2 (R96)	O		TSPC_BS3x_UDI_X. 32
5	Bearer Service 31(30) .. 34, 3.1 kHz audio ex-PLMN information transfer capability; Non-X.32 Cases.	3GPP TS 07.01 B.1.3.2.1 3GPP TS 27.001, B.1.3.2.1	Phase 2 (R96)	O		TSPC_BS3x_3.1kHz_ nonX.32
6	Bearer Service 31(30) .. 34, 3.1 kHz audio ex-PLMN information transfer capability; X.32 Cases.	3GPP TS 07.01 B.1.3.2.2 3GPP TS 27.001, B.1.3.2.2	Phase 2 (R96)	O		TSPC_BS3x_3.1kHz_ X.32
7	Bearer Service 41(40)..46, PAD Access Asynchronous.	3GPP TS 07.01 B.1.4 3GPP TS 27.001, B.1.5	Phase 2 (R96)	O		TSPC_BS4x_PAD
8	Bearer Service 51(50)..53, Data Packet Duplex Synchronous.	3GPP TS 07.01 B.1.5 3GPP TS 27.001, B.1.5	Phase 2 (R96)	O		TSPC_BS5x_Packet
9	Bearer Service 61, Alternate Speech/Data, "Speech".	3GPP TS 07.01 B.1.6.1 3GPP TS 27.001, B.1.6.1	Phase 2	O		TSPC_BS61_Speech
10	Bearer Service 61, Alternate Speech/Data, .3.1 kHz audio ex-PLMN information transfer capability; Asynchronous.	3GPP TS 07.01 B.1.6.2.1 3GPP TS 27.001, B.1.6.2.1	Phase 2	O		TSPC_BS61_3.1kHz _Async
11	Bearer Service 61, Alternate Speech/Data, .3.1 kHz audio ex-PLMN information transfer capability; Synchronous.	3GPP TS 07.01 B.1.6.2.2 3GPP TS 27.001, B.1.26.2.2	Phase 2	O		TSPC_BS61_3.1kHz _Sync
12	Bearer Service 81, Speech followed by Data, "Speech".	3GPP TS 07.01 B.1.7.1 3GPP TS 27.001, B.1.7.1	Phase 2	O		TSPC_BS81_Speech
13	Bearer Service 81, Speech followed by Data, .3.1 kHz audio ex-PLMN information transfer capability; Asynchronous.	3GPP TS 07.01 B.1.7.2.1 3GPP TS 27.001, B.1.7.2.1	Phase 2	O		TSPC_BS81_3.1kHz _Async

Item	Bearer Capability Group	Ref.	Release	Status	Support	Mnemonic
14	Bearer Service 81, Speech followed by Data, .3.1 kHz audio ex-PLMN information transfer capability; Synchronous.	3GPP TS 07.01 B.1.7.2.2 3GPP TS 27.001, B.1.7.2.2	Phase 2	O		TSPC_BS81_3.1kHz_Sync
15	Teleservice 11..12, Speech.	3GPP TS 07.01 B.1.8 3GPP TS 27.001, B.1.8	Phase 2	O		TSPC_TS1x_Speech
16	Teleservice 61, Alternate Speech and Facsimile group 3; "Speech".	3GPP TS 07.01 B.1.10.1 3GPP TS 27.001, B.1.8	Phase 2	O		TSPC_TS61_Speech
17	Teleservice 61, Alternate Speech and Facsimile group 3; Facsimile group 3.	3GPP TS 07.01 B.1.10.2 3GPP TS 27.001, B.1.10.2	Phase 2	O		TSPC_TS61_G3FAX
18	Teleservice 62, Automatic Facsimile group 3	3GPP TS 07.01 1.11 3GPP TS 27.001, B.1.11	Phase 2	O		TSPC_TS62_G3FAX

Comments:

Table A.7: Bearer Service 20..26, UDI/RDI

Prerequisite: A.6/1 -- BS2x_UDI (diagram in 3GPP TS 07.01 B.1.2.1 (3GPP TS 27.001 B.1.2.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Signalling Access Protocol (SAP).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		I.440, X.28nond	
2	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
3	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		ISO6429, COPnoFICt, NAV	
4	Number of Data Bits(NDB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		7 bits, 8 bits	
5	Parity Information (NPB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		odd, even, 0, 1, none	
6	Number of Stop Bits (NSB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1 bit, 2 bits	
7	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
8	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
9	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
10	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, 38.4 48.56, NAV	
11	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C701		9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV	
12	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
13	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C702		1, 2, 3, 4, NAV	
10a	all allowed combinations according to 3GPP TS 07.01 B.1.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

C701 IF A.7/10 AND A.25/7 THEN M ELSE N/A

C702 IF A.7/10 THEN M ELSE N/A

Detailed description (if not all allowed combinations are implemented):

Table A.8: Bearer Service 20..26, 3.1 kHz

Prerequisite: A.6/2 -- BS2x_3.1kHz (diagram in 3GPP TS 07.01 B.1.2.2 (3GPP TS 27.001 B.1.2.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Signalling Access Protocol (SAP).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		I.440, X.28nond	
2	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
3	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex A 3GPP TS 27.001, annex B	Phase 2	M		ISO6429, COPnoFICt, NAV	
4	Number of Data Bits (NDB).	3GPP TS 07.01 annex B	Phase 2	M		7 bits, 8 bits	
5	Parity Information (NPB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		odd, even, 0, 1, none	
6	Number of Stop Bits (NSB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1 bit, 2 bits	
7	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
8	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
9	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
10	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		V.21, V.22, V.22bis, V.26ter, V.32, V.23, auto	
11	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, NAV	
12	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C801		9.6, 14.4, 19.2, 28.8, 38.4, 43.2	
13	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
14	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
15	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C802		1, 2, 3, 4, NAV	

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
11a	all allowed combinations according to 3GPP TS 07.01 B.1.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C801 IF A.8/10 AND A.25/7 THEN M ELSE N/A C802 IF A.8/10 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.9: Bearer Service 30..34, UDI, Non-X.32

Prerequisite: A.6/3 -- BS3x_UDI_nonX.32 (diagram in 3GPP TS 07.01 B.1.3.1.1 (3GPP TS 27.001 B.1.3.1.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Signalling Access Protocol (SAP).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1.440, X.21	
2	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
3	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
4	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1.2, 2.4, 4.8, 9.6	
5	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV	
6	Acceptable channel codings (ACC)	3GPP TS 07.01 annexB 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
7	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C901		1, 2, 3, 4, NAV	
5a	all allowed combinations according 3GPP TS 07.01 A2 1.3.1.1 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C901 IF A.9/5 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.10: Bearer Service 30..34, UDI, X-32

Prerequisite: A.6/4 -- BS3x_UDI_X.32 (diagram in 3GPP TS 07.01 B.1.3.1.2 (3GPP TS 27.001 B.1.3.1.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
2	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
3	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		2.4, 4.8, 9.6	
4	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2 (R96)	M		X.25, (X.75)	
5	Rate Adaptation (RA)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2 (R96)	O		X.31Flag, (V.120)	
6	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV	
7	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1001		9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57, NAV	
8	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
9	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
10	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1001		1, 2, 3, 4, NAV	
4a	all allowed combinations according to 3GPP TS 07.01 B.1.3.1.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C1001 IF A.10/6 AND A.25/7 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.10a: Bearer Service 30..34, UDI, 48 kbps and 56 kbps bit transparent

Prerequisite: A.6/4 -- BS3x_UDI_X.32[tbd] (diagram in 3GPP TS 07.01 B.1.3.1.4 (3GPP TS 27.001 B.1.3.1.4)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Signalling Access Protocol (SAP).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		I.440, X.21	
2	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		48, 56	
3	all allowed combinations according to 3GPP TS 07.01 B.1.3.1.4 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.10b: Bearer Service 30..34, UDI, 64 kbps bit transparent

Prerequisite: A.6/4 -- BS3x_UDI_X.32[tbd] (diagram in 3GPP TS 07.01 B.1.3.1.5 (3GPP TS 27.001 B.1.3.1.5)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Signalling Access Protocol (SAP).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		I.440, X.21	
2	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4	
3	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		5, 6	
4	all allowed combinations according to 3GPP TS 07.01 B.1.3.1.5 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.11: Bearer Service 30..34, 3.1 kHz, Non-X-32

Prerequisite: A.6/5 -- BS3x_3.1kHz_nonX.32 (diagram in 3GPP TS 07.01 B.1.3.2.1 (3GPP TS 27.001 B.1.3.2.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
2	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
3	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1.2, 2.4, 4.8, 9.6	
4	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		V.22, V.22bis, V.26ter, V.32	
5	Other Modem Type (OMT)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		no other MT, V.34, NAV	
6	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, NAV	
7	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
8	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1101		1, 2, 3, 4, NAV	
5a	all allowed combinations according to 3GPP TS 07.01 B.1.3.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C1101 IF A.11/6 AND A.25/7 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.12: Bearer Service 30..34, 3.1kHz, X-32

Prerequisite: A.6/6 -- BS3x_3.1kHz_X.32 (diagram in 3GPP TS 07.01 B.1.3.2.2 (3GPP TS 27.001 B.3.2.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
3	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
4	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		2.4, 4.8, 9.6	
5	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		V.22bis, V.26ter, V.32	
6	Other Modem Type (OMT)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		no other MT, V.34, NAV	
7	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, NAV	
8	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1201		9.6, 14.4, 19.2, 28.8, NAV	
9	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
10	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
11	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1202		1, 2, 3, 4, NAV	
6a	all allowed combinations according to 3GPP TS 07.01 B.1.3.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C1201 IF A.12/7 AND A.25/7 THEN M ELSE N/A							
C1202 IF A.12/7 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.13: Bearer Service 40..46, PAD Access

Prerequisite: A.6/7 -- BS4x_PAD (diagram in 3GPP TS 07.01 B.1.4 (3GPP TS 27.001 B.1.4)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		ISO6429, COPnoFICt, NAV	
3	Number of Data Bits(NDB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		7 bits, 8 bits	
4	Parity Information (NPB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		odd, even, 0, 1, none	
5	Number of Stop Bits (NSB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1 bit, 2 bits	
6	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
7	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
8	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
9	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV	
10	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1301		9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV	
11	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
12	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
13	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1302		1, 2, 3, 4, NAV	
9a	all allowed combinations according to 3GPP TS 07.01 B.1.4 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			
C1301 IF A.13/9 AND A.25/7 THEN M ELSE N/A							
C1302 IF A.13/9 THEN M ELSE N/A							

Detailed description (if not all allowed combinations are implemented):

Table A.14: Bearer Service 50..53, Data Packet Duplex Synchronous

Prerequisite: A.6/8 -- BS5x_Packet (diagram in 3GPP TS 07.01 B.1.5 (3GPP TS 27.001 B.1.5)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
2	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
3	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
4	Fixed Network User Rate (FNUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV	
5	Wanted Air Interface User Rate (WAIUR)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1401		9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV	
6	Acceptable channel codings (ACC)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		4.8, 9.6, 14.4, NAV	
7	User Initiated Modification Indication (UIMI)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	O		not req., upto1, upto2, upto3, upto4, NAV	
8	Maximum number of Traffic Channels (MaxNumTCH)	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	C1402		1, 2, 3, 4, NAV	
4a	all allowed combinations according to 3GPP TS 07.01 B.1.5 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

C1401 IF A.14/4 AND A.25/7 THEN M ELSE N/A

C1402 IF A.14/4 THEN M ELSE N/A

Detailed description (if not all allowed combinations are implemented):

Table A.15: Bearer Service 61, Alternate Speech/Data, "Speech"

Prerequisite: A.6/9 -- BS61_Speech (diagram in 3GPP TS 07.01 B.1.6.1 (3GPP TS 27.001 B.1.6.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	

Comments:

Table A.16: Bearer Service 61, Alternate Speech/Data, 3.1kHz, Async

Prerequisite: A.6/10 -- BS61_3.1kHz_Async (diagram in 3GPP TS 07.01 B.1.6.2.1 (3GPP TS 27.001 B.1.6.2.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		ISO6429, COPnoFICt, NAV	
3	Number of Data Bits (NDB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		7 bits, 8 bits	
4	Parity Information (NPB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		odd, even, 0, 1, none	
5	Number of Stop Bits (NSB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1 bit, 2 bits	
6	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
7	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
8	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
9	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	M		V.21, V.22, V.22bis, V.26ter V.32, V.23, auto1	
10	all allowed combinations according to 3GPP TS 07.01 B.1.6.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.17: Bearer Service 61, Alternate Speech/Data, 3.1kHz, Sync

Prerequisite: A.6/11 -- BS61_3.1kHz_Sync (diagram in 3GPP TS 07.01 B.1.6.2.2 (3GPP TS 27.001 B.1.6.2.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
2	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
3	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1.2, 2.4, 4.8, 9.6	
4	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	M		V.22, V.22bis, V.26ter, V.32	
5	all allowed combinations according to 3GPP TS 07.01 B.1.6.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.18: Bearer Service 81, Speech followed by Data, "Speech"

Prerequisite: A.6/12 -- BS81_Speech (diagram in 3GPP TS 07.01 B.1.7.1 (3GPP TS 27.001 B.1.7.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	

Comments:

Table A.19: Bearer Service 81, Speech followed by Data, 3.1kHz, Async

Prerequisite: A.6/13 -- BS81_3.1kHz_Async (diagram in 3GPP TS 07.01 B.1.7.2.1 (3GPP TS 27.001 B.1.7.2.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		ISO6429, COPnoFICt, NAV	
3	Number of Data Bits(NDB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		7 bits, 8 bits	
4	Parity Information (NPB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		odd, even, 0, 1, none	
5	Number of Stop Bits (NSB).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1 bit, 2 bits	
6	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	
7	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
8	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075	
9	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	M		V.21, V.22, V.22bis, V.26ter V.32, V.23, auto1	
10	all allowed combinations according to 3GPP TS 07.01 B.1.7.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.20: Bearer Service 81, Speech followed by Data, 3.1kHz, Sync

Prerequisite: A.6/14 -- BS81_3.1kHz_Sync (diagram in 3GPP TS 07.01 B.1.7.2.2 (3GPP TS 27.001 B.1.7.2.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR,FR, dualFR	
2	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
3	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		1.2, 2.4, 4.8, 9.6	
4	Modem Type (MT).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	R96	M		V.22, V.22bis, V.26ter, V.32	
5	all allowed combinations according 3GPP TS 07.01 B.1.7.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.21: Teleservice 11..12, Speech

Prerequisite: A.6/15 -- TS1x_Speech (diagram in 3GPP TS 07.01 B.1.8 (3GPP TS 27.001 B.1.8)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		dualHR, FR, dualFR	

Comments:

Table A.22: Alternate Speech and Facsimile group 3, Speech

Prerequisite: A.6/16 -- TS61_Speech (diagram in 3GPP TS 07.01 B.1.10.1 (3GPP TS 27.001 B.1.10.1)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Radio Channel Requirement (RCR).	3GPP TS 07.01 B1 3GPP TS 27.001, annex B 1	Phase 2	M		dualHR, FR, dualFR	

Comments:

Table A.23: Alternate Speech and Facsimile group 3, Facsimile group 3

Prerequisite: A.6/17 -- TS61_G3FAX (diagram in 3GPP TS 07.01 B.1.10.2 (3GPP TS 27.001 B.1.10.2)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		X.25 NAV	
3	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
4	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		2.4, 4.8, 9.6,	
5	all allowed combinations according 3GPP TS 07.01 B.1.10.2 (3GPP TS 27.001) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

Table A.24: Teleservice 62, Automatic G3 fax

Prerequisite: A.3/7 -- Serv_TS62 (diagram in 3GPP TS 07.01 B.1.11 (3GPP TS 27.001 B.1.11)).

Item	Bearer Capability Elements	Reference	Release	Status	Support	Values	
						Allowed	Supported
1	Connection Element (CE).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		NT, bothNT, T, bothT	
2	User Info Layer 2 Protocol (UIL2P).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		X.25 NAV	
3	Intermediate Rate (IR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		8 kbps, 16 kbps	
4	User Rate (UR).	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	M		2.4, 4.8, 9.6	
5	all allowed combinations according to 3GPP TS 07.01 B.1.11 (3GPP TS 27.001, annex B) implemented (if not, provide detailed description).			O			

Detailed description (if not all allowed combinations are implemented):

A.4.8 Additional Information

The supplier of the implementation shall state the support of the implementation for each of the questions concerning additional information given in the table below.

Table A.25: Additional Information

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
1	at least one half rate service.	3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2	Phase 2	O		TSPC_AddInfo_HalfRate
2	Speech supported for Full rate version 1 (GSM FR).	3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5	Phase 2	C2501		TSPC_AddInfo_Full_rate_version_1
3	Speech supported for Half rate version 1 (GSM HR).	3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5	Phase 2	O		TSPC_AddInfo_Half_rate_version_1
4	at least one data service.	3GPP TS 07.01 annex D, 3GPP TS 09.07, 3	Phase 2	O		TSPC_AddInfo_DataSvc
5	at least one full rate data service.	3GPP TS 07.01 annex D, 3GPP TS 27.001, D 3GPP TS 09.07, 10 3GPP TS 29.007, 10	Phase 2	O		TSPC_AddInfo_FullRateData
6	at least one half rate data service.	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_HalfRateData
7	at least one non transparent data service.	3GPP TS 02.02 3, 3GPP TS 22.002, D.2 3GPP TS 02.03 6 3GPP TS 22.001, D.2	Phase 2	O		TSPC_AddInfo_NonTransData
8	at least one transparent data service.	3GPP TS 02.02 3, 3GPP TS 22.002, 3, 3GPP TS 02.03 6 3GPP TS 22.003, 6	Phase 2	O		TSPC_AddInfo_TransData
9	only transparent data service	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 02.03 6 3GPP TS 22.003, 6	Phase 2	O		TSPC_AddInfo_TranspDataOnly
10	at least one asynchronous data service.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_AsyncData

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
11	at least one asynchronous non transparent data service.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_AsyncNonTransData
12	2.4 k full rate data mode.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_24DataF
13	2.4 k half rate data mode.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_24DataH
14	4.8 k full rate data mode.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_48DataF
15	4.8 k half rate data mode.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_48DataH
16	9.6 k full rate data mode.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_96Data
17	non transparent service with full rate channel at a user rate of 4.8 kbit/s.	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B, 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_fullRate4.8
18	at least one bearer capability.	3GPP TS 07.01 annex B 3GPP TS 27.001, annex B	Phase 2	O		TSPC_AddInfo_BC
19	at least one MT circuit switched basic service.	3GPP TS 04.08 5.3.4.2.2 3GPP TS 24.008, 5.3.4.2.2	Phase 2	O		TSPC_AddInfo_MTsvc

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
20	at least one MO circuit switched basic service.	3GPP TS 04.08 5.3.4.2.1 3GPP TS 24.008, 5.3.4.2.1	Phase 2	O		TSPC_AddInfo_MOsvc
21	only SDCCH.	3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2	Phase 2	O		TSPC_AddInfo_SDCCHOnly
22	at least one service on traffic channel supported	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 02.03 annex A 3GPP TS 22.003, annex A	Phase 2	O		TSPC_AddInfo_SvcOnTCH
23	dual rate ratio channel types (no relation to supported speech codecs).	3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2	Phase 2	O		TSPC_AddInfo_DualRate
24	only full rate radio channel type (no relation to supported speech codecs).	3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2	Phase 2	O		TSPC_AddInfo_FullRateOnly
25	at least one teleservice.	3GPP TS 02.03 6 3GPP TS 22.003, 6	Phase 2	O		TSPC_AddInfo_TeleSvc
26	CC protocol for at least one BC.	3GPP TS 04.08 5 3GPP TS 24.008, 5	Phase 2	O		TSPC_AddInfo_CCprotocol_oneBC
27	only circuit switched basic service supported by the mobile is emergency call.	3GPP TS 02.03 6, A.1.2 3GPP TS 22.003, 6, A.1.2	Phase 2	C2505		TSPC_AddInfo_EmgOnly
28	Fax Error Correction Mode.	3GPP TS 03.45,4 .2.2 3GPP TS 23.045, 4.2.2 3GPP TS 03.46,2 .6	Phase 2	O		TSPC_AddInfo_FaxErrCorr
29	at least one supplementary service.	3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1	Phase 2	O		TSPC_AddInfo_SS
30	non call related supplementary service.	3GPP TS 02.04 4 3GPP TS 22.004, 4	Phase 2	O		TSPC_AddInfo_NonCallSS
31	at least one short message service.	3GPP TS 02.03 B.1.7, A.1.3 3GPP TS 22.003, B.1.3, A.1.3	Phase 2	O		TSPC_AddInfo_SMS
32	(SMS) reply procedure.	3GPP TS 03.40 3 3GPP TS 23.040, 3	Phase 2	O		TSPC_AddInfo_ReplyProc
33	replace SMS.	3GPP TS 03.40 3 3GPP TS 23.040, 3	Phase 2	O		TSPC_AddInfo_ReplaceSMS

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
34	display of received SMS.	3GPP TS 03.40 9, 3GPP TS 23.040, 9 3GPP TS 03.41 8 3GPP TS 23.041, 8	Phase 2	O		TSPC_AddInfo_DispRcvSMS
35	SMS status report capabilities.	3GPP TS 03.40 3.2.9 3GPP TS 23.040, 3.2.9	Phase 2	O		TSPC_AddInfo_SMSStatusRepCap
36	Storing of short messages in the SIM.	3GPP TS 03.38 4 3GPP TS 23.038, 4	Phase 2	O		TSPC_AddInfo_StoreRcvSMS SIM
37	Storing of short messages in the ME.	3GPP TS 03.38 4 3GPP TS 23.038, 4 3GPP TS 03.40, 10 3GPP TS 23.040, 10	Phase 2	O		TSPC_AddInfo_StoreRcvSMS ME
38	detach on power down.	3GPP TS 04.08 4.3.4 3GPP TS 24.008, 4.3.4	Phase 2	O		TSPC_AddInfo_DetachOnPwr Dn
39	detach on SIM remove.	3GPP TS 04.08 4.3.4 3GPP TS 24.008, 4.3.4	Phase 2	O		TSPC_AddInfo_DetachOnSIM Rmv
40	SIM removable without power down.	3GPP TS 02.17 5.7		O		TSPC_AddInfo_SIMRmv
41	ID-1 SIM.	3GPP TS 02.17 4.1.1	Phase 2	O.2502		TSPC_AddInfo_ID1
42	Plug-In SIM.	3GPP TS 02.17 4.1.2	Phase 2	O.2502		TSPC_AddInfo_PlugIn
43	Disable PIN feature.	3GPP TS 02.17 5.6	Phase 2	O		TSPC_AddInfo_DisablePin
44	PIN2 feature.	3GPP TS 02.17 5.6	Phase 2	O		TSPC_AddInfo_Pin2
45	Feature requiring entry of PIN2.	3GPP TS 02.17 5.6	Phase 2	O		TSPC_AddInfo_Pin2Feature
46	Chars 0-9, *, # supported	3GPP TS 02.30 2.3, 3GPP TS 22.030, 2.3 3GPP TS 02.07 B.1.5	Phase 2	O	Phase 2	TSPC_AddInfo_BasCharSet
47	A, B, C, D chars. supported	3GPP TS 02.30 2.3 3GPP TS 22.030, 2.3	Phase 2	O	Phase 2	TSPC_AddInfo_AddCharSet
48	automatically enter automatic selection of PLMN mode.	3GPP TS 02.11 3.2 3GPP TS 22.011, 3.2	Phase 2	O	Phase 2	TSPC_AddInfo_AutoAutoMode
49	alerting indication to the user.	3GPP TS 04.08 5.2.1.5 3GPP TS 24.008, 5.2.1.5	Phase 2	O	Phase 2	TSPC_AddInfo_AlertInd
50	Appl. Layer is always running.	3GPP TS 11.10-1 18.1 3GPP TS 51.010- 1, 18.1	R98	O		TSPC_AddInfo_ApplAlwaysRun

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
51	Immediate connect supported for all circuit switched basic services.	3GPP TS 04.08 5.2.1.6 3GPP TS 24.008, 5.2.1.6	Phase 2	O		TSPC_AddInfo_ImmConn
52	In-Call modification.	3GPP TS 04.08 5.3.4.3 3GPP TS 24.008, 5.3.4.3	Phase 2	O		TSPC_AddInfo_InCallMod
53	follow-on request procedure.	3GPP TS 04.08 4.4.4.6 3GPP TS 24.008, 4.4.4.6	Phase 2	O		TSPC_AddInfo_followOnReq
54	refusal of call.	3GPP TS 04.08 5.2.2.3.1 3GPP TS 24.008, 5.2.2.3.1	Phase 2	O		TSPC_AddInfo_RefusalCall
55	RF amplification.	3GPP TS 04.08 3.4.10 3GPP TS 44.018, 3.4.10	Phase 2	O		TSPC_AddInfo_RFAmp
56	Number of B-party number for autocalling is greater than the number of entries in the blacklist.	3GPP TS 02.07 annex A	Phase 2	O		TSPC_AddInfo_AutocallBnoGreaterM
57	Handset MS supporting speech.	3GPP TS 03.50 3.1.1	Phase 2	O		TSPC_AddInfo_SpeechHandset
58	MT2 Configuration.	3GPP TS 04.02 3 3GPP TS 24.002, 3	Phase 2	O		TSPC_AddInfo_MT2
59	MT2 Configuration or any other possibility to send data over Um interface.	3GPP TS 04.02 3 3GPP TS 24.002, 3	Phase 2	O		TSPC_AddInfo_MT2orOther
60	Permanent Antenna Connector.	3GPP TS 51.010-1 12.1.1, 12.1.2	Release 4	O.2504		TSPC_AddInfo_PermAntenna
61	Pseudo-synchronized handover supported.	3GPP TS 05.10 2, annex A	Phase 2	O		TSPC_AddInfo_PseudoSynch
62	5V only SIM/ME interface.	3GPP TS 11.11	R96	O.2503		TSPC_AddInfo_5V
63	3V only SIM/ME interface.	3GPP TS 11.12	R96	O.2503		TSPC_AddInfo_3V
64	3V/5V SIM/ME interface.	3GPP TS 11.12	R96	O.2503		TSPC_AddInfo_3V5V
65	Speech supported for Full rate version 2 (GSM EFR).	3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5	Phase 2	C2502		TSPC_AddInfo_Full_rate_version_2
66a	RLP supports non default parameters	3GPP TS 04.22 5.2.2.6 3GPP TS 24.022, 3	Phase 2	O		TSPC_AddInfo_NonDefaultRlpParam
66b	Support of listening to voice broadcast calls (VBS listening)	3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1	R 96	O		TSPC_AddInfo_VBS_Listening
67	Support of originating voice broadcast call (VBS originating)	3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1	R 96	O		TSPC_AddInfo_VBS_Originating
68	Support of listening to voice group calls (VGCS listening)	3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1	R96	C2503		TSPC_AddInfo_VGCS_Listening
69	Support of talking in voice group calls (VGCS talking)	3GPP TS 04.08, 0.7.1 3GPP TS 24.008, 1.7.1	R96	C2504		TSPC_AddInfo_VGCS_Talking

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
70	Support of originating voice group call (VGCS originating)	3GPP TS 04.08, 0.7 3GPP TS 24.008, 0.7	R96	O		TSPC_AddInfo_VGCS_Originating
71	Support reduced NCH monitoring	3GPP TS 04.08, 3.3.3.3 3GPP TS 44.018, 3.3.3.3	R96	O		TSPC_AddInfo_NCH_ReducedMonitor
72	14.4 k data mode	3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 Annex B, 3GPP TS 27.001, Annex B	R 96	O		TSPC_AddInfo_144Data
73	Implementation of cause number 27 of busy autocalled in category 2	3GPP TS 02.07, Annex A	Phase 2	O		TSPC_AddInfo_Impl_CNr27_Cat2
74	Implementation of cause number 27 of busy autocalled in category 3	3GPP TS 02.07, Annex A	Phase 2	O		TSPC_AddInfo_Impl_CNr27_Cat3
75	Support of immediate connect	3GPP TS 04.08, 5.2.1.6 3GPP TS 24.008, 5.2.1.6	Phase 2	O		TSPC_AddInfo_imm_Con
76	Artificial ear type 1	3GPP TS 03.50	Phase 2 up to and including release 4	O		TSPC_AddInfo_Ear_type1
77	Artificial ear type 3.2, Low leak option	3GPP TS 03.50	Phase 2	O		TSPC_AddInfo_Ear_type32_LL
78	Artificial ear type 3.4	3GPP TS 03.50	R96	O		TSPC_AddInfo_Ear_type34
79	Speech supported for Full rate version 3 (FR AMR).	3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5	R98	C2502		TSPC_AddInfo_Full_rate_version_3
80	NCH monitoring in group receive mode	3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3	R 96	O		TSPC_AddInfo_NCH_Monit_Rev
81	NCH monitoring in group transmit mode	3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3	R 96	O		TSPC_AddInfo_NCH_Monit_Tra
82	NCH monitoring in dedicated mode	3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3	R 96	O		TSPC_AddInfo_NCH_Monit_Ded
83	Support of one PDP context activation	3GPP TS 04.08, 6.1.3.1 3GPP TS 24.008, 6.1.3.1	R 97	O		TSPC_AddInfo_1PDP_CA
84	Support of more than one PDP context activation	3GPP TS 04.08 3GPP TS 24.008	R 97	O		TSPC_AddInfo_mor1PDP CA
85	Support of more than one PDP context activation simultaneously on the same SAPI	3GPP TS 04.08 3GPP TS 24.008	R 97	O		TSPC_AddInfo_mor1PDP CA_SAPI
86	Support of GPRS data compression	3GPP TS 04.65, 6.6 3GPP TS 24.065, 6.6	R 97	O		TSPC_AddInfo_GPRS_Data_Compr
87	Support of GPRS header compression	3GPP TS 04.65 3GPP TS 24.065	R 98	O		TSPC_AddInfo_GPRS_Header_Compr

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
88	Support of Network requested PDP context activation	3GPP TS 04.08, 6.1.3.1.2 3GPP TS 24.008, 6.1.3.1.2	R 97	O		TSPC_AddInfo_N_req_PDP_CA
89	Support for user settings of minimum QoS	3GPP TS 02.60 3GPP TS 22.060	R 97	O		TSPC_AddInfo_min_QoS
90	Automatic GPRS attach procedure at switch-on/power-on	3GPP TS 04.08, 4.7.3 3GPP TS 24.008, 4.7.3	R 97	O		TSPC_AddInfo_on_auto_GPRS_AP
91	MMI controlled attach/detach procedures for non-GPRS services	3GPP TS 04.08, 4.7.3.1.4 3GPP TS 24.008, 4.7.3.1.4	R 97	O		TSPC_AddInfo_MMI_contr_A/DProc_Non GPRS
92	Automatic attach procedure when MS identity cannot be derived by the network	3GPP TS 04.08, 4.7.5.1.4 3GPP TS 24.008, 4.7.5.1.4	R 97	O		TSPC_AddInfo_auto_AP_no_MS ID
93	Automatic MM IMSI attach procedure at switch-on/power-on	3GPP TS 04.08, 4.7.3.2.4 3GPP TS 24.008, 4.7.3.2.4	R98	O		TSPC_AddInfo_auto_MM_IMSI_AP_on/off
94	Support of SIM Application Toolkit	3GPP TS 11.11, 11.6	R96	O		TSPC_AddInfo_SIM_Appl_Toolkit
95	1,8V only SIM/ME interface.	3GPP TS 11.18	R98	O.2503		TSPC_AddInfo_1,8V
96	1,8V/3V SIM/ME interface.	3GPP TS 11.18	R98	O.2503		TSPC_AddInfo_1,8V3V
97	Multiple SM MO/PP on same RR link	3GPP TS 03.40 3.7 3GPP TS 23.040, 3.7	Phase 2	O		TSPC_AddInfo_MultSMsame RR
98	Support of stored list cell selection	3GPP TS 05.08 3GPP TS 45.008	Phase 2	O		TSPC_AddInfo_StoredListCell Sel
99	at least one service not support immediate connection	3GPP TS 04.08 3GPP TS 24.008	Phase 2	O		TSPC_AddInfo_NoimmConn
100	Void					
101	Void					
102	EFR_EmgCallSetup message contains the bearer capability	3GPP TS 06.51	Phase 2	O		TSPC_AddInfo_EFR_EmgCall Bcap
103	Support of MonitorPCH_GroupTransmit Mode	3GPP TS 11.10-1 3GPP TS 51.010-1	Phase 2	O		TSPC_AddInfo_MonitorPCH_GroupTransmitMode
104	Integral_Antenna Connector	3GPP TS 51.010-1 12	Release 4	O.2504		TSPC_AddInfo_IntegrAntenna
105	User requested combined GPRS and non-GPRS detached without powering off	3GPP TS 04.08, 4.7.4 3GPP TS 24.008, 4.7.4	R97	O		TSPC_AddInfo_Comb_DP_no_pwr_off
106	User requested non-GPRS detached	3GPP TS 04.08, 4.7.4 3GPP TS 24.008, 4.7.4	R97	O		TSPC_AddInfo_Usr_non_GPRS_DP
107	Artificial ear type 3.2, High leak option	3GPP TS 43.050	Phase 2	O		TSPC_AddInfo_Ear_type32_HL
108	Artificial ear type 3.3	3GPP TS 43.050	R96	O		TSPC_AddInfo_Ear_type33
109	Support of Multiple SMS	3GPP TS 03.40 3.7 3GPP TS 23.040, 3.7	Phase2	O		TSPC_Addinfo_MultSMS
110	Cell Reselection after T3184 Expiry	3GPP TS 04.60	R97	O		TSPC_Cell_Resel

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
111	GPRS attach attempted automatically due to outstanding request	3GPP TS 04.08, 4.7.3 3GPP TS 24.008, 4.7.3	R97	O		TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding
112	Speech supported for Half rate version 3 (HR AMR)	3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5	R98	O		TSPC_AddInfo_Half_rate_version_3
113	AMR LoopBack I	3GPP TS 44.014	R5	C2502		TSPC_AMR_LoopBack_I
114	TTY services	3GPP TS 24.008	R99	O		TSPC_AddInfo_TTY
C2501	IF A.25/3 THEN M ELSE O					-- TSPC_AddInfo_Half_rate_version_1
C2502	IF A.25/2 THEN O ELSE N/A					-- TSPC_AddInfo_Full_rate_version_1
O.2502	At least one of the requirements shall be supported.					
O.2503	At least one of these items shall be supported.					
O.2504	At least one of these items shall be supported.					
C2503	IF A.25/69 OR A.25/70 THEN M ELSE O					-- TSPC_AddInfo_VGCS OR TSPC_AddInfo_VGCS_Talking
C2504	IF A.25/70 THEN M ELSE O					-- TSPC_AddInfo_VGCS
C2505	IF A.3/2 THEN O ELSE N/A					-- TSPC_Serv_TS12

Comments:

A.4.9 SIM Application Toolkit

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the information given in the tables below.

A.4.9.1 SIM Application Toolkit mechanism

The PICS tables for SIM Application Toolkit mechanism are contained in document 3GPP TS 11.10-4.

A.4.9.1.1 Terminal Profile

The contents of TERMINAL PROFILE used in the Profile Download instruction is detailed in document 3GPP TS 11.10-4 [96]

A.4.9.1.2 Proactive commands

The supplier of the implementation shall state which of the proactive commands are supported of the implementation in the table below.

Table A.26.3: Proactive commands

Prerequisite: A.25/94: TSPC_ Addinfo_ SIM_Appl_Toolkit

Item	Proactive commands	Ref.	Release	Status	Support	Mnemonic
1	Display Text	3GPP TS 11.14, 6.4.1	R96	M		Pro_Display_Text
2	Get Inkey	3GPP TS 11.14, 6.4.2	R96	M		Pro_Get_Inkey
3	Get Input	3GPP TS 11.14, 6.4.3	R96	M		Pro_Get_Input
4	More Time	3GPP TS 11.14, 6.4.4	R96	M		Pro_More_Time
5	Play Tone	3GPP TS 11.14, 6.4.5	R96	M		Pro_Play_Tone
6	Poll Interval	3GPP TS 11.14, 6.4.6	R96	M		Pro_Poll_Interval
7	Refresh	3GPP TS 11.14, 6.4.7	R96	M		Pro_Refresh
8	Set up Menu	3GPP TS 11.14, 6.4.8	R96	M		Pro_Setup_Menu
9	Select Item	3GPP TS 11.14, 6.4.9	R96	M		Pro_Select_Item
10	Send Short Message	3GPP TS 11.14, 6.4.10	R96	M		Pro_Send_SMS
11	Send SS	3GPP TS 11.14, 6.4.11	R96	M		Pro_Send_SS
12	Set Up Call	3GPP TS 11.14, 6.4.13	R96	M		Pro_Setup_Call
13	Polling off	3GPP TS 11.14, 6.4.14	R96	M		Pro_Polling_Off
14	Provide Local Information	3GPP TS 11.14, 6.4.15	R96	M		Pro_Provide_Local
15	Send USSD	3GPP TS 11.14, 6.4.12	R97	M		Pro_Send_USSD
16	Set Up Event List	3GPP TS 11.14, 6.4.16	R98	M		Pro_Setup_Evt_List
17	Perform Card APDU	3GPP TS 11.14, 6.4.17	R98	O		Class_A_C_APDU
18	Power Off Card	3GPP TS 11.14, 6.4.18	R98	O		Class_A_C_OFF
19	Power On Card	3GPP TS 11.14, 6.4.19	R98	O		Class_A_C_ON
20	Get Reader Status	3GPP TS 11.14, 6.4.20	R99	O		Class_A_Get_Rdr_Status
21	Timer Management	3GPP TS 11.14, 6.4.21	R98	M		Pro_Timer_Mgt
22	Set Up Idle Mode Text	3GPP TS 11.14, 6.4.22	R98	M		Pro_Stup_IdMod_Txt

Item	Proactive commands	Ref.	Release	Status	Support	Mnemonic
23	Run AT Command	3GPP TS 11.14, 6.4.23	R98	M		Class_B_Run_AT
24	Send DTMF	3GPP TS 11.14, 6.4.24	R98	M		Pro_Send_DTMF
25	Language Notification	3GPP TS 11.14, 6.4.25	R99	M		Pro_Lang_Notif
26	Launch Browser	3GPP TS 11.14, 6.4.26	R99	O		Class_C_LB
27	Open Channel	3GPP TS 11.14, 6.4.27	R99	O		Class_E_Open_Ch
28	Close Channel	3GPP TS 11.14, 6.4.28	R99	O		Class_E_Close_Ch
29	Receive Data	3GPP TS 11.14, 6.4.29	R99	O		Class_E_Rx_Data
30	Send Data	3GPP TS 11.14, 6.4.30	R99	O		Class_E_Send_Data
31	Get Channel Status	3GPP TS 11.14, 6.4.31	R99	O		Class_E_Get_Ch_Status

Comments:

A.4.9.1.2.1 Display Text

The supplier of the implementation shall state the support of possible qualifiers for the Display Text in the table below.

Table A.26.4: Display Text

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Display Text	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	void							
2	Immediate Response	3GPP TS 11.14, 6.4.1	R98	O		Display_Text_Imm_Resp		
3	UCS2 coding scheme supported	3GPP TS 11.14, 12.15.3	R97	O		Display_Text_Ucs2		
4	Extended string	3GPP TS 11.14, 6.4.1 and 12.6	R98	O		Display_Text_Ext_Text	1..240	
5	Sustained Text	3GPP TS 11.14, 6.4.1 and 6.9	R98	M		Display_Text_Sustained		

Comments:

Item 1: This clause means that it is mandatory for the implementation to support the command Display Text. The "Value" column allows the implementation to truncate the text string when displayed. The Value supported shall indicate how many characters the implementation is able to display. Due to different styles/fonts used in the implementations, it is allowed to specify a mean number of characters. If no "truncation" is applied by the implementation, the value supported shall be 160.

A.4.9.1.2.2 Get Inkey

The supplier of the implementation shall state the support of possible qualifiers for the Get Inkey in the table below.

Table A.26.5: Get Inkey

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Get Inkey	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	Void							
3	Void							
4	Binary Choice	3GPP TS 11.14, 6.4.2	R98	M		Get_Inkey_Yes_no		
5	UCS2 Display	3GPP TS 11.14, 12.15.3	R97	O		Get_Inkey_Ucs2_Dispatch		
6	UCS2 Entry	3GPP TS 11.14, 12.15.3	R97	O		Get_Inkey_Ucs2_Entry		

Comments:

Item 1: See comment table A.26.4/1

Item 3: If appropriate, the characters not supported can be stated.

A.4.9.1.2.3 Get Input

The supplier of the implementation shall state the support of possible qualifiers for the Get Input in the table below.

Table A.26.6: Get Input

Prerequisite: A.26.3/3 AND A.25/94: Pro_Get_Input AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Get Input	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	Void							
3	Void							
4	UCS2 Display	3GPP TS 11.14, 12.15.3	R97	O		Get_Input_Ucs2_Dispatch		
5	UCS2 Entry	3GPP TS 11.14, 12.15.3	R97	O		Get_Input_Ucs2_Entry		

Comments:

Item 1: See comment table A.26.4/1

Item 3: If appropriate, the characters not supported can be stated.

A.4.9.1.2.4 More Time

Not necessary.

A.4.9.1.2.5 Play Tone

The supplier of the implementation shall state the support of possible qualifiers for the Play Tone in the table below.

Table A.26.7: Play Tone

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Play Tone	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	UCS2 Display	3GPP TS 11.14, 6.4.5, 6.6.5	R97	O		Play_Tone_ Ucs2		

Comments:

Item 1: This clause means that it is mandatory for the implementation to support this command. The "Value" column allows the implementation to truncate the alpha string when displayed. The Value supported shall indicate how many characters the implementation is able to display. Due to different styles/fonts used in the implementations, it is allowed to specify a mean number of characters. If no truncation is applied by the implementation, the value supported shall be 241.

241 = 256-1-2-5-4-3

Editors Note: Supervisory tones not included.

A.4.9.1.2.6 Poll Interval

The supplier of the implementation shall state the polling interval supported by the implementation in the table below.

Table A.26.8: Poll Interval

Prerequisite: A.26.3/6 AND A.25/94: Pro_Poll_Interval AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Poll Interval	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Maximum poll interval	3GPP TS 11.14, 6.4.6	R96	M		Poll_Max	0.1 s.. 255 min	
2	Minimum poll interval	3GPP TS 11.14, 6.4.6	R96	M		Poll_Min	0.1 s.. 255 min	
The supported value for Maximum poll interval shall be greater or equal to the Minimum poll interval.								

Comments:

A.4.9.1.2.7 Refresh

Not necessary.

A.4.9.1.2.8 Set Up Menu

The supplier of the implementation shall state the support of possible qualifiers for the Set Up Menu in the table below.

Table A.26.10: Set Up Menu

Prerequisite: A.25/94: TSPC_ Addinfo_ SIM_ Appl_ Toolkit

Item	Set Up Menu	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	Void							
3	Help Information	3GPP TS 11.14, 6.4.8	R97	O		Setup_Menu_Help_Info		
4	Soft Key support	3GPP TS 11.14, 6.4.8	R99	O		Setup_Menu_Soft_key		
5	UCS2 Display	3GPP TS 11.14, 6.4.8, 6.6.7	R98	O		Setup_Menu_Ucs2		

Comments:

Item 1: See comment for table A.26.7/1
238 = 256-1-2-5-4-3-3

Item 2: 240 = 256-1-2-5-4-4

A.4.9.1.2.9 Select Item

The supplier of the implementation shall state the support of possible qualifiers for the Select Item in the table below.

Table A.26.11: Select Item

Prerequisite: A.25/94: TSPC_ Addinfo_ SIM_ Appl_ Toolkit

Item	Select Item	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	Void							
3	Soft Key Support	3GPP TS 11.14, 6.4.9	R99	O		Select_Item_Soft_key		
4	UCS2 Display	3GPP TS 11.14, 6.4.9	R98	O		Select_Item_Ucs2		

Comments:

Item 1: See comment for table A.26.7/1
238 = 256-1-2-5-4-3-3

Item 2: 240 = 256-1-2-5-4-4

A.4.9.1.2.10 Send Short Message

The supplier of the implementation shall state the support of possible qualifiers for the Send Short Message in the table below.

Table A.26.12: Send Short Message

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Send Short Message	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1								
2	UCS2 Display	3GPP TS 11.14, 6.4.10 6.6.9	R97	O		Send_SMS_Ucs2		

Comments:

Item 1: See comment for table A.26.7/1

X = 256-1-2-5-4-3-length(SMS TPDU simple TLV)

(Minimum length of length(SMS TPDU simple TLV) is 9 octets, i.e. maximum of X=232).

A.4.9.1.2.11 Send SS

The supplier of the implementation shall state the support of possible qualifiers for the Send SS in the table below.

Table A.26.13: Send SS

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Send SS	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1								
2	UCS2 Display	3GPP TS 11.14, 6.4.10 6.6.9	R97	O		Send_SS_Ucs2		

Comments:

Item 1: See comment for table A.26.7/1

X = 256-1-2-5-4-3- length(SS/USSD string simple TLV)

(Minimum length of length (SS/USSD string simple TLV) is 4 octets, (one octet for the SS/USSD string) i.e. maximum of X = 237).

A.4.9.1.2.12 Send USSD

The supplier of the implementation shall state the support of possible qualifiers for the Send USSD in the table below.

Table A.26.19: Send USSD

Prerequisite: A.26.3/15 AND A.25/94: Pro_Send_USSD AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Send SS	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	UCS2 Display	3GPP TS 11.14, 6.4.12 6.6.11	R97	O		Send_USSD_Ucs2		

A.4.9.1.2.13 Set Up Call

The supplier of the implementation shall state the support of possible qualifiers for the Set Up Call in the table below.

Table A.26.14: Set Up Call

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Set up Call	Reference	Release	Status	Support	Mnemonic	Value	
							Allowed	Supported
1	Void							
2	Void							
3	Void							
4	UCS2 Display	3GPP TS 11.14, 6.4.13, 6.6.12	R97	O		Setup_Call_Ucs2		
5	2 nd Alpha Identifier	3GPP TS 11.14, 6.4.13, 6.6.12	R98	O		Setup_Call_Sec_Alpha_Id		
C26.1401	A.2/16	-- TSPC_Feat_Subaddress						
C26.1402	A.2/26	-- TSPC_Feat_Subaddress						

Comments:

Item 1: See comment for table A.26.7/1
240 = 256-1-2-5-4-4

A.4.9.1.2.14 Polling Off

Not necessary.

A.4.9.1.2.15 Provide Local Information

Table A.26.17: Provide Local Information

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Provide Local Information	Reference	Release	Status	Support	Mnemonic
1	Network Measurements (NMR)	3GPP TS 11.14 6.4.15	R97	M		Provide_Local_NMR
2	Date Time and Time Zone	3GPP TS 11.14 6.4.15	R98	M		Provide_Local_D_Time
3	BCCH Channel List	3GPP TS 11.14 6.4.15	R98	M		Provide_Local_BCCH_List
4	Language Settings	3GPP TS 11.14 6.4.15	R99	M		Provide_Local_LS
5	Timing Advance	3GPP TS 11.14 6.4.15	R99	M		Provide_Local_TA

A.4.9.1.2.20 Get Reader Status

Table A.26.20: Get Reader Status

Prerequisite: A.26.3/20 AND A.25/94: Class_A_Get_Rdr_Status AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Get Reader Status	Reference	Release	Status	Support	Mnemonic
1	Detachable Reader	3GPP TS 11.14 6.4.20, 6.6.20	R98	O		Class_A_Get_Rdr_Status_Detach

A.4.9.1.2.22 Set Up Idle Mode Text

Table A.26.23: Set Up Idle Mode Text

Prerequisite: A.26.3/22 AND A.25/94: Pro_Stup_IdMod_Txt AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Set Up Idle Mode Text	Reference	Release	Status	Support	Mnemonic
1	UCS2 Display	3GPP TS 11.14 6.4.22	R98	O		Stup_IdMod_Txt_Ucs2

A.4.9.1.2.24 Send DTMF

Table A.26.21: Send DTMF

Prerequisite: A.26.3/24 AND A.25/94: Pro_Send_DTMF AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Send DTMF	Reference	Release	Status	Support	Mnemonic
1	UCS2 Display	3GPP TS 11.14 6.4.24	R98	O		Send_DTMF_Ucs2

A.4.9.1.2.27 Open Channel

Table A.26.22: Open Channel

Prerequisite: A.26.3/27 AND A.25/94: Class_E_Open_Ch AND TSPC_Addinfo_SIM_Appl_Toolkit

Item	Get Reader Status	Reference	Release	Status	Support	Mnemonic
1	For CSD	3GPP TS 11.14 6.4.27.1	R99	O		Class_E_Open_Ch_CSD
2	For GPRS	3GPP TS 11.14 6.4.27.2	R99	O		Class_E_Open_Ch_GPRS
3	TCP Transport Protocol	3GPP TS 11.14 6.4.27, 12.59	R99	O		Class_E_Open_Ch_TCP
4	UDP Transport Protocol	3GPP TS 11.14 6.4.27, 12.59	R99	O		Class_E_Open_Ch_UDP

A.4.9.1.3 Data Download

The supplier of the implementation shall state the support of possible qualifiers for the Data Download in the table below.

Table A.26.15: Data Download

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Data Download	Ref.	Release	Status	Support	Mnemonic
1	The SIMPLE-TLV Address used in BER-TLV ENVELOPE for SMS-PP Download.	3GPP TS 11.14, 7.1.2	R96	O		DDSIM_SubAddr
2	"9EXX" response code for SIM data download error	3GPP TS 11.14, 7.1.1 , 7.1.2	R97	O		DD_9EXX

Comments:

A.4.9.1.4 Menu Selection

Not necessary.

A.4.9.1.5 Call Control

The supplier of the implementation shall state the support of possible qualifiers for the Call Control in the table below.

Table A.26.16: Call Control

Prerequisite: A.25/94: TSPC_Addinfo_SIM_Appl_Toolkit

Item	Call Control	Ref.	Release	Status	Support	Mnemonic
1	SIMPLE-TLV "Called Party Subaddress" used in BER-TLV ENVELOPE.	3GPP TS 11.14, 9.5	R96	C26.160 1		CC_SubAddr
2	Emergency Call Codes (ECC).	3GPP TS 11.14, 9. 3GPP TS 11.11, 10.3.27	R96	M		CC_ECC
3	Fixed Number Dialling	3GPP TS 02.07 B.3.2	R96	C26.160 2		Feat_FDN
4	Cell Identity	3GPP TS 11.14, 9.6	R97	M		CC_Cell_Id
5	USSD String	3GPP TS 11.14, 9.1.2	R98	M		CC_USSD_Str
6	Automatic Redial	3GPP TS 11.14, 9.1.1	R99	M		CC_Auto_Redial
7	MO SMS Control	3GPP TS 11.14, 9.1.1	R98	M		CC_MO_SMS_Ctrl
8	2nd capability configuration parameter	3GPP TS 11.14, 9.1.6	R98	M		CC_Sec_Cap_Param
9	Handling of the alpha identifier	3GPP TS 11.14, 9.1.3	R97	M		CC_Alpha_Id
C26.1601	IFA.2/16 THEN O ELSE X			-- TSPC_Feat_Subaddress		
C26.1602	IFA.2/21 THEN O ELSE X			-- TSPC_Feat_Subaddress		

Comments:

A.4.9.1.6 Timer Expiration

Not necessary.

A.4.9.1.7 Event Download

The supplier of the implementation shall state which of the proactive events are supported of the implementation in the table below.

Table A.26.18: Event Download

Item	Event Download	Ref.	Release	Status	Support	Mnemonic
1	Event : Card reader status	3GPP TS 11.14, 11.7	R99	O		Class_A_Evt_Rdr_Status
2	Event – Language Selection	3GPP TS 11.14, 11.8	R99	M		Evt_Lang_Select
3	Event : Browser Termination	3GPP TS 11.14, 11.9	R99	O		Class_C_Evt_Br_Term
4	Event : Data available	3GPP TS 11.14, 11.10	R99	O		Class_E_Evt_Data_Avail
5	Event : Channel Status	3GPP TS 11.14, 11.11	R99	O		Class_E_Evt_Ch_Status

A.4.10 Support of UTRAN Radio Access Technology

The supplier of the implementation shall state the support of the implementation for each of the questions concerning Support of UTRAN Radio Access Technology given in the table below.

Table A.27: Support of UTRAN Radio Access Technology

Prerequisite: A.1/56 -- TSPC_Type_UTRAN

Item	Additional Information	Ref.	Release	Status	Support	Mnemonic
1	Conversational / speech / UL:12.2 DL:12.2 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH	3GPP TS 34.123-2, A.18c/4 3GPP TS 34.108 6.10.2.4.1.4	R99	O		TSPC_Conversational_12_2_CSRAB_3_4_SRAB
2	Streaming / unknown / UL:14.4/DL:14.4 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH	3GPP TS 34.123-2, A.18c/15 3GPP TS 34.108 6.10.2.4.1.15	R99	O		TSPC_Streaming_14_4_CSRAB_3_4_SRAB
3	Streaming / unknown / UL:28.8/DL:28.8 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH	3GPP TS 34.123-2, A.18c/16 3GPP TS 34.108, 6.10.2.4.1.16	R99	O		TSPC_Streaming_28_8_CSRAB_3_4_SRAB
4	Streaming / unknown / UL:57.6/DL:57.6 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH	3GPP TS 34.123-2, A.18c/17 3GPP TS 34.108, 6.10.2.4.1.17	R99	O		TSPC_Streaming_57_6_CSRAB_3_4_SRAB

Annex B (normative): Applicability of the individual test

The applicability of each individual test is identified in the table B.1.

The applicability of every test is formally expressed by the use of Boolean expression that are based on parameters (ICS) included in annex A of the present document.

The columns in Table B.1 have the following meaning:

Clause column

The clause column indicates the clause number for each test case as described in the 3GPP TS 51.010-1 or 3GPP TS 11.10-4 (tests 27.22.x) for which the applicability is identified.

Title column

The title column indicates the title of each test case as described in the 3GPP TS 51.010-1 or 3GPP TS 11.10-4 (tests 27.22.x) for which the applicability is identified.

Release column

The Release column indicates the earliest release from which each testcase is applicable, except if otherwise stated of an individual test case.

Applicability column

The Applicability column describes the applicability of the test in a verbal way.

Status column

The following notations, are used for the status column:

A	applicable - the test is applicable.
N/A	not applicable – in the given context, the test case is not applicable.
Ci	conditional – the test is applicable ("A") or not ("N/A") depending on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is used to avoid ambiguities.

Supported column

The following common notations, are used for the support column:

Y or y	test is supported by the implementation
N or n	test is not supported by the implementation
N/A, n/a or -	no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status)

Table B.1: Applicability of tests

Clause	Title	Release	Applicability	Status	Supported
11.1.1	Mobile Terminated (MT) calls	Phase 2	Each MT Bearer Service and MT Teleservice supported by the MS	C31	
11.1.2	Mobile Originated (MO) calls	Phase 2	Each MO Bearer Service and MO Teleservice supported by the MS	C36	
11.2	Verification of support of the single numbering scheme	Phase 2	MS supporting at least one MT circuit switched basic service	C31	
11.3	Verification of non-support of services (Advice of Charge Charging (AOCC))	Phase 2	MS which do not support AOCC	C32	
11.4	Verification of non-support of services (call hold)	Phase 2	MS which support AOCC and do not support the Call Hold supplementary service	C33	
11.5	Verification of non-support of services (multiparty)	Phase 2	MS which support Call Hold and AOCC, but do not support the Multi-Party supplementary service	C34	
11.6	Verification of non-support of feature (Fixed Dialling Number (FDN))	Phase 2	MS which do not support FDN	C35	
11.7	IMEI Security	Phase 2	All MS	A	
12.1.1	Conducted spurious emissions, MS allocated a channel	Phase 2	All MS with a permanent antenna connector	C99	
12.1.2	Conducted spurious emissions, MS in idle mode	Phase 2	All MS with a permanent antenna connector	C99	
12.2.1	Radiated spurious emissions, MS allocated a channel	Phase 2	All MS not supporting R-GSM. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible	C102	
12.2.2	Radiated spurious emissions, MS in idle mode	Phase 2	All MS not supporting R-GSM. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible	C102	
12.3.1	Conducted spurious emissions, MS allocated a channel for MS supporting the R-GSM band	R96	R-GSM MS with a permanent antenna connector	C115	
12.3.2	Conducted spurious emissions, MS in idle mode for MS supporting the R-GSM band	R96	R-GSM MS with a permanent antenna connector	C115	
12.4.1	Radiated spurious emissions, MS allocated a channel for MS supporting the R-GSM band	R96	R-GSM MS. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible	C103	
12.4.2	Radiated spurious emissions, MS in idle mode for MS supporting the R-GSM band	R96	R-GSM MS. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible	C103	
13.1	Frequency error and phase error	Phase 2	All MS	A	
13.2	Frequency error under multipath and interference conditions	Phase 2	All MS	A	
13.3-1	Transmitter output power and burst timing - MS with permanent antenna connector	Phase 2	All MS with a permanent antenna connector	C20	
13.3-2	Transmitter output power and burst timing - MS with integral antenna	Phase 2	All MS with integral antenna connector	C92	

Clause	Title	Release	Applicability	Status	Supported
13.4	Output RF spectrum	Phase 2	All MS not supporting R-GSM	C102	
13.6	Frequency error and phase error in HSCSD multislot configuration	R96	HSCSD Multislot MS	C86	
13.7-1	Transmitter output power and burst timing in HSCSD configurations - MS with permanent antenna connector	R96	HSCSD Multislot MS with permanent antenna connector	C93	
13.7-2	Transmitter output power and burst timing in HSCSD configurations - MS with integral antenna	R96	HSCSD Multislot MS with integral antenna	C94	
13.8	Output RF spectrum in HSCSD multislot configuration	R96	HSCSD Multislot MS	C86	
13.9	Output RF spectrum for MS supporting the R-GSM band	R96	R-GSM MS	C103	
13.10	Reserved for future use				
13.11	Reserved for future use				
13.12	Reserved for future use				
13.13	Reserved for future use				
13.14	Reserved for future use				
13.15	Reserved for future use				
13.16.1	Frequency error and phase error in GPRS multislot configuration	R97	GPRS MS supporting multislot operation on the uplink	C204	
13.16.2-1	Transmitter output power in GPRS multislot configuration - MS with permanent antenna connector	R97	GPRS MS supporting multislot operation on the uplink - MS with permanent antenna connector	C95	
13.16.2-2	Transmitter output power in GPRS multislot configuration - MS with integral antenna connector	R97	GPRS MS supporting multislot operation on the uplink - MS with integral antenna connector	C96	
13.16.3	Output RF spectrum in GPRS multislot configuration	R97	GPRS MS supporting multislot operation on the uplink	C204	
13.17.1	Frequency error and Modulation accuracy	R99	EGPRS MS capable of 8PSK in Uplink, of all Multislot classes	C238	
13.17.2	Frequency error under multipath and interference conditions	R99	All EGPRS MS	C216	
13.17.3-1	EGPRS Transmitter output power-MS with permanent antenna connector	R99	EGPRS MS capable of 8PSK in Uplink, of all Multislot classes with permanent antenna connector	C97	
13.17.3-2	EGPRS Transmitter output power-MS with integral antenna connector	R99	EGPRS MS capable of 8PSK in Uplink, of all Multislot classes with integral antenna connector	C98	
13.17.4	Output RF spectrum	R99	EGPRS MS capable of 8PSK in Uplink, of all Multislot classes	C238	
14.1.1.1	Bad frame indication - TCH/FS - Random RF input	Phase 2	MS supporting full rate speech	C24	
14.1.1.2	Bad frame indication - TCH/FS - Frequency hopping and downlink DTX	Phase 2	MS supporting full rate speech	C24	
14.1.2.1	Bad frame indication - TCH/HS - Random RF input	Phase 2	MS supporting half-rate speech	C13	
14.1.2.2	Bad frame indication - TCH/HS - Frequency hopping and downlink DTX	Phase 2	MS supporting half-rate speech	C13	
14.1.3	Bad frame indication - TCH/FS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network	Phase 2	MS supporting full rate speech	C24	

Clause	Title	Release	Applicability	Status	Supported
14.1.4	Bad frame indication - TCH/HS - Frequency hopping and downlink DTX - Phase 2 MS in a phase 1 network	Phase 2	MS supporting half-rate speech	C13	
14.1.5.1	Bad frame indication - TCH/AFS - Random RF input	R98	MS supporting AMR	C203	
14.1.6.1	Bad frame indication - TCH/AHS - Random RF input	R98	MS supporting AMR Half Rate	C319	
14.2.1	Reference sensitivity - TCH/FS	Phase 2	MS supporting full rate speech	C24	
14.2.2	Reference sensitivity - TCH/HS (Speech frames)	Phase 2	MS supporting half-rate speech	C13	
14.2.3	Reference sensitivity - FACCH/F	Phase 2	All MS	A	
14.2.4	Reference sensitivity - FACCH/H	Phase 2	MS supporting half rate service	C2	
14.2.5	Reference sensitivity - full rate data channels	Phase 2	MS supporting data	C11	
14.2.6	Reference sensitivity - half rate data channels	Phase 2	MS supporting half-rate data	C12	
14.2.7	Reference sensitivity - TCH/EFS	Phase 2	MS supporting EFR speech	C83	
14.2.8	Reference sensitivity - full rate data channels in multislot configuration	R98	HSCSD Multislot MS	C86	
14.2.9	Reference sensitivity - TCH/FS for MS supporting the R-GSM band	R98	R-GSM MS supporting full rate speech	C116	
14.2.10	Reference Sensitivity – TCH/AFS	R98	MS supporting AMR	C203	
14.2.18	Reference Sensitivity – TCH/AHS	R98	MS supporting AMR	C319	
14.2.19	Reference Sensitivity – TCH/AFS-INB	R98 AND Loop I	MS supporting AMR and Loop I	C321	
14.2.20	Reference Sensitivity – TCH/AHS-INB	R98 AND Loop I	MS supporting AMR and Loop I	C321	
14.3	Usable receiver input level range	Phase 2	MS supporting full rate speech	C24	
14.4.1	Co-channel rejection - TCH/FS	Phase 2	MS supporting full rate speech	C24	
14.4.2	Co-channel rejection - TCH/HS	Phase 2	MS supporting half-rate speech	C13	
14.4.3	Co-channel rejection - TCH/HS (SID frames)	Phase 2	MS supporting half-rate speech	C13	
14.4.4	Co-channel rejection - FACCH/F	Phase 2	All MS	A	
14.4.5	Co-channel rejection - FACCH/H	Phase 2	MS supporting half rate service	C2	
14.4.6	Co-channel rejection - TCH/EFS	Phase 2	MS supporting EFR speech	C83	
14.4.7	Receiver performance in the case of frequency hopping and co-channel interference on one carrier	R97	MS supporting speech	C52	
14.4.8	Co-channel rejection – TCH/AFS	R98	MS supporting AMR	C203	14.4.8
14.4.16	Co-channel rejection – TCH/AHS	R98	MS supporting AMR	C319	14.4.16
14.4.17	Co-channel rejection – TCH/AFS-INB	R98 AND Loop I	MS supporting AMR and Loop I	C321	14.4.17
14.4.18	Co-channel rejection – TCH/AHS-INB	R98 AND Loop I	MS supporting AMR and Loop I	C321	14.4.18

Clause	Title	Release	Applicability	Status	Supported
14.5.1.1	Adjacent channel rejection - speech channels – TCH/FS	Phase 2	MS supporting speech	C52	
14.5.1.2	Adjacent channel rejection - speech channels – TCH/AFS	R98	MS supporting AMR	C203	
14.5.1.3	Adjacent channel rejection - speech channels – TCH/AHS	R98	MS supporting AMR Half Rate	C319	
14.5.2	Adjacent channel rejection - control channels	Phase 2	MS not supporting speech	C53	
14.6.1	Intermodulation rejection - speech channels	Phase 2	MS supporting speech	C52	
14.6.2	Intermodulation rejection - control channels	Phase 2	MS not supporting speech	C53	
14.7.1	Blocking and spurious response - speech channels	Phase 2	Non R-GSM MS supporting speech	C100	
14.7.2	Blocking and spurious response - control channels	Phase 2	MS not supporting speech	C53	
14.7.3	Blocking and spurious response - speech channels for MS supporting the R-GSM band	R97	R-GSM MS supporting speech	C116	
14.7.4	Blocking and spurious response - control channels for MS supporting the R-GSM band	R97	R-GSM MS not supporting speech	C119	
14.8.1	AM suppression - speech channels	Phase 2	MS supporting speech	C52	
14.8.2	AM suppression - control channels	Phase 2	MS not supporting speech	C53	
14.9	Paging performance at high input levels	Phase 2	All MS	A	
14.10.1	Performance of the Codec Mode Request Generation – TCH/AFS	R98	MS supporting AMR	C203	
14.10.2	Performance of the Codec Mode Request Generation – TCH/AHS	R98	MS supporting AMR	C203	
14.11	Reserved for future use				
14.12	Reserved for future use				
14.13	Reserved for future use				
14.14	Reserved for future use				
14.15	Reserved for future use				
14.16.1	Minimum Input level for Reference Performance	R97	All GPRS MS	C215	
14.16.2.1	Co-channel rejection for packet channels	R97	All GPRS MS	C215	
14.18.1	Minimum Input Level for Reference Performance	R99	All EGPRS MS	C216	
14.18.2	Co-channel Rejection	R99	All EGPRS MS	C216	
14.18.3	Adjacent channel Rejection	R99	All EGPRS MS	C216	
14.18.4	Intermodulation Rejection	R99	All EGPRS MS	C216	
14.18.5	Blocking and spurious response	R99	All EGPRS MS	C216	
14.18.6	EGPRS Usable receiver input level range	R99	All EGRS MS	C216	
14.18.7	Incremental redundancy performance	R99	All EGRS MS	C216	
15.1-15.5	Timing advance and absolute delay	Phase 2	All MS	A	
15.6	GPRS Timing advance and absolute delay	R97	All GPRS MS	C215	
15.7	ECSD Timing advance and absolute delay	R99	All ECSD MS	C214	
15.8	EGPRS Timing advance and absolute delay	R99	All EGPRS MS	C216	
15.9	Timing advance whilst in DTM	R99	All DTM capable MS	C305	
16	Reception time tracking speed	Phase 2	All MS	A	
17.1	Intra cell channel change	Phase 2	All MS	A	
17.2	Inter cell handover	Phase 2	All MS	A	
18.1	Temporary reception gaps, single slot	Phase 2	MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic	C1	

Clause	Title	Release	Applicability	Status	Supported
18.2	Temporary reception gaps in HSCSD multislot configurations	R98	HSCSD Multislot MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic	C90	
19.1	Channel release after unrecoverable errors - 1	Phase 2	MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic	C1	
19.2	Channel release after unrecoverable errors - 2	Phase 2	MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic	C1	
19.3	Channel release after unrecoverable errors - 3	Phase 2	MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic	C1	
20.1	Cell selection	Phase 2	All MS	A	
20.2	Cell selection with varying signal strength values	Phase 2	All MS	A	
20.3	Basic cell reselection	Phase 2	All MS	A	
20.4	Cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters	Phase 2	All MS	A	
20.5	Cell reselection using parameters transmitted in the System Information type 2bis, type 7 and type 8 messages	Phase 2	All MS. Test purpose 2 is only applicable to EGSM900 and DCS 1 800 MS. Test purpose 4 is only applicable to E-GSM MS	A	
20.6	Cell reselection timings	Phase 2	All MS	A	
20.7	Priority of cells	Phase 2	All MS	A	
20.8	Cell reselection when C1 (serving cell) < 0 for 5 seconds	Phase 2	All MS		
20.9	Running average of the surrounding cell BCCH carrier signal levels	Phase 2	All MS	A	
20.10	Running average of the serving cell BCCH carrier signal level	Phase 2	All MS	A	
20.11	Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list	Phase 2	All MS	A	
20.12	Decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers	Phase 2	All MS	A	
20.13	Decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers	Phase 2	All MS	A	
20.14	Emergency calls	Phase 2	MS supporting speech	C52	
20.15	Cell reselection due to MS rejection "LA not allowed"	Phase 2	All MS	A	
20.16	Downlink signalling failure	Phase 2	All MS	A	
20.17	Cell selection if no suitable cell found in 10 s	Phase 2	All MS	A	
20.18	Cell reselection due to MS rejection "Roaming not allowed in this LA"	Phase 2	All MS	A	
20.19	Cell selection on release of SDCCH and TCH	Phase 2	All MS	A	
20.20.1	Multiband cell selection and reselection/Cell selection	Phase 2	MS supporting simultaneous multiband operation	C76	

Clause	Title	Release	Applicability	Status	Supported
20.20.2	Multiband cell selection and reselection/Cell reselection	Phase 2	MS supporting simultaneous multiband operation	C76	
20.21.1	R-GSM cell selection	R96	R-GSM MS	C103	
20.21.2	R-GSM cell selection with varying signal strength values		R-GSM MS	C103	
20.21.3	R-GSM basic cell reselection	R96	R-GSM MS	C103	
20.21.4	R-GSM cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters	R96	R-GSM MS	C103	
20.21.5	R-GSM cell reselection using parameters transmitted in the System Information type 2bis, type 7 and type 8 messages	R96	R-GSM MS	C103	
20.21.6	R-GSM cell reselection timing	R96	R-GSM MS	C103	
20.21.7	R-GSM priority of cells	R96	R-GSM MS	C103	
20.21.8	R-GSM cell reselection when C1 (serving cell) < 0 for 5 seconds	R96	R-GSM MS	C103	
20.21.9	R-GSM running average of the surrounding cell BCCH carrier signal levels	R96	R-GSM MS	C103	
20.21.10	R-GSM running average of the serving cell BCCH carrier signal level	R96	R-GSM MS	C103	
20.21.11	R-GSM updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list	R96	R-GSM MS	C103	
20.21.12	R-GSM decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers	R96	R-GSM MS	C103	
20.21.13	R-GSM decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers	R96	R-GSM MS	C103	
20.21.14	R-GSM emergency calls	R96	R-GSM MS supporting speech	C116	
20.21.15	R-GSM cell reselection due to MS rejection "LA not allowed"	R96	R-GSM MS	C103	
20.21.16	R-GSM downlink signalling failure	R96	R-GSM MS	C103	
20.21.17	R-GSM cell selection if no suitable cell found in 10 s	R96	R-GSM MS	C103	
20.21.18	R-GSM cell reselection due to MS rejection "Roaming not allowed in this LA"	R96	R-GSM MS	C103	
20.21.19	R-GSM cell selection on release of SDCCH and TCH	R96	R-GSM MS	C103	
20.22.1	Cell selection	R97	All GPRS MS	C215	
20.22.2	Cell reselection in Packet Idle mode	R97	All GPRS MS	C215	
20.22.3	Priority of cells	R97	All GPRS MS	C215	
20.22.4	Cell re-selection with cells in different routing area	R97	All GPRS MS	C215	
20.22.5	Network controlled Cell re-selection in Idle Mode	R97	All GPRS MS	C215	
20.22.6	Cell reselection timings	R97	All GPRS MS	C215	
20.22.7	Downlink signalling failure	R97	All GPRS MS	C215	
20.22.8	Cell selection when the best cell does not support GPRS	R99	All GPRS MS	C215	
20.22.9	Cell reselection when the best cell does not support GPRS	R99	All GPRS MS	C215	
20.22.10	Cell Selection-Search for Suitable Cell/ cell priority	R97	All GPRS MS	C215	
20.22.11	Cell Selection/No normal priority cell	R97	All GPRS MS	C215	
20.22.12	Cell Selection on "LA not allowed"	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
20.22.13	Cell Reselection based on C32 quality	R97	All GPRS MS	C215	
20.22.14	Cell Reselection in case Cell reselection occurred in the previous 15 seconds	R97	All GPRS MS	C215	
20.22.15	Cell Reselection/ ready state/no reselection	R97	All GPRS MS	C215	
20.22.16	Cell Reselection/ ready state/ Reselection and Cell update procedure	R97	All GPRS MS	C215	
20.22.17	C2 reselection in another RA - no cell reselection	R97	All GPRS MS	C215	
20.22.18	C2 reselection in another Routing Area - Routing Area Update	R97	All GPRS MS	C215	
20.22.19	Borders between routing areas - reselection of a GPRS cell in a homogenous network	R97	All GPRS MS	C215	
20.22.20	Cell Reselection based on C32 - Cell Reselection on CCCH - PBCCH not present	R97	All GPRS MS	C215	
20.22.21	Cell Reselection based on C32/GCRH value - Cell Reselection on CCCH - PBCCH not present	R97	All GPRS MS	C215	
20.22.22	Cell Reselection with cells in different Routing area - Cell Reselection on CCCH - PBCCH not present	R97	All GPRS MS	C215	
20.22.23	Cell Reselection based on C32 - Cell Reselection on CCCH - PBCCH not supported	R97	All GPRS MS	C215	
20.22.24	Cell Reselection based on C32/cell of same priority/ Cell Reselection on CCCH - PBCCH not supported	R97	All GPRS MS	C215	
20.22.25	Cell Reselection based on C32/C31<0/ Cell Reselection on CCCH - PBCCH not supported	R97	All GPRS MS	C215	
20.22.26	Cell Reselection based on C32 quality/Cell Reselection on CCCH - PBCCH not supported	R97	All GPRS MS	C215	
20.22.28	Cell Reselection/no suitable cell found/cell selection	R97	All GPRS MS	C215	
20.22.29	Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters	R99	MS supporting both GPRS and UTRAN	C324	
20.22.30.1	Cell Reselection/usage of BA(GPRS)	R97	All GPRS MS	C215	
20.22.30.2	Cell Reselection / usage of BA(GPRS) / Change of BA(GPRS)	R97	All GPRS MS	C215	
20.22.30.3	Cell Reselection/usage of BA(GPRS)/ Measurement on first 32 entries	R97	All GPRS MS	C215	
20.23.1	COMPACT Cell Selection	R99	All COMPACT MS without GSM CS	C213	
20.23.2	COMPACT Cell reselection in Packet Idle mode	R99	All COMPACT MS	C213	
20.23.3	Priority of cells	R99	All COMPACT MS	C213	
20.23.4	Cell re-selection with cells in different routing area	R99	All COMPACT MS	C213	
20.23.5	COMPACT Network controlled Cell re-selection in Transfer Mode	R99	All COMPACT MS	C213	
20.23.6	COMPACT Cell reselection timings	R99	All COMPACT MS	C213	
20.23.7	COMPACT Downlink signalling failure	R99	All COMPACT MS	C213	

Clause	Title	Release	Applicability	Status	Supported
20.23.8	COMPACT Cell re-selection when target cell is BCCH supporting EGPRS and different routing area	R99	All COMPACT MS	C213	
20.23.9	Cell re-selection when target cell is COMPACT CPBCH in different routing area	R99	All COMPACT MS	C213	
20.24.1	SoLSA Cell Selection suitable cell	R99	All SoLSA MS	C207	
20.24.2	SoLSA Cell (Re)Selection emergency call	R99	All SoLSA MS	C207	
20.24.3	SoLSA Cell Reselection/idle mode support enabled	R99	All SoLSA MS	C207	
20.24.4	SoLSA Cell Reselection/idle mode support any	R99	All SoLSA MS	C207	
20.24.5	SoLSA Cell Reselection/LSA indication for idle mode	R99	All SoLSA MS	C207	
21.1	Signal strength	Phase 2	All MS	A	
21.2	Signal strength selectivity	Phase 2	All MS	A	
21.3.1	Signal quality under static conditions - TCH/FS	Phase 2	MS supporting full rate speech	C24	
21.3.2	Signal quality under static conditions - TCH/HS	Phase 2	MS supporting half rate speech	C13	
21.3.3	Signal quality under static conditions -TCH/AFS	R98	MS supporting AMR	C203	
21.3.4	Signal quality under static conditions -TCH/AHS	R98	MS supporting AMR	C203	
21.4.1	Signal quality under TUhigh propagation conditions	Phase 2	All MS supporting speech	C52	
21.4.2	Signal quality under TUhigh propagation conditions -TCH/AFS	R98	MS supporting AMR	C203	
21.4.3	Signal quality under TUhigh propagation conditions -TCH/AHS	R98	MS supporting AMR	C203	
21.5.1	Received signal measurements in HSCSD multislot configuration, signal strength	R96	HSCSD Multislot MS	C86	
21.6	COMPACT Signal Strength	R99	All COMPACT MS	C213	
21.7	COMPACT Signal Strength Selectivity	R99	All COMPACT MS	C213	
22.1	Transmit power control timing and confirmation, single slot	R96	All MS	A	
22.2	Transmit power control timing and confirmation in HSCSD multi slot configuration	R96	HSCSD Multislot MS	C86	
22.3	GPRS Uplink Power Control – Use of α and Γ_{CH} parameters	R97	All GPRS MS	C215	
22.4	GPRS Uplink Power Control – Independence of TS Power Control	R97	All GPRS MS supporting GPRS multislot operation on the uplink	C204	
22.5	<i>Reserved for future use</i>				
22.6	Normal transmit power control timing and confirmation in ECSD	R99	All ECSD MS	C214	
22.7	ECSD Fast Power Control timing and interworking with normal power control	R99	All MS capable of class B ECSD operation	C214	
22.8	EGPRS Uplink Power Control – Use of α and Γ_{CH} parameters	R99	All EGPRS MS	C216	
22.9	EGPRS Uplink Power Control – Independence of TS Power Control	R99	All EGPRS MS	C216	
22.10	<i>Reserved for future use</i>				
22.11	Power control in exclusive allocation mode.	R99	MS supporting singleslot allocation in DTM	C310	
22.12	Downlink power control, PR mode A, GPRS TBF	R99	All GPRS MS	C215	
23	Single frequency reference	Phase 2	All MS	A	

Clause	Title	Release	Applicability	Status	Supported
25.2.1.1.1	Initialization when contention resolution required, Normal initialization	Phase 2	All MS	A	
25.2.1.1.2.1	Initialization failure, Loss of UA frame	Phase 2	All MS	A	
25.2.1.1.2.2	Initialization failure, UA frame with different information field	Phase 2	All MS	A	
25.2.1.1.2.3	Initialization failure, Information frame and supervisory frames in response to an SABM frame	Phase 2	All MS	A	
25.2.1.1.3	Initialization denial	Phase 2	All MS	A	
25.2.1.1.4	Total initialization failure	Phase 2	All MS	A	
25.2.1.2.1	Normal initialization without contention resolution	Phase 2	All MS	A	
25.2.1.2.2	Initialization failure	Phase 2	All MS	A	
25.2.1.2.3	Initialization denial	Phase 2	All MS	A	
25.2.1.2.4	Total initialization failure	Phase 2	All MS	A	
25.2.2.1	Sequence counting and I frame acknowledgements	Phase 2	All MS	A	
25.2.2.2	Receipt of an I frame in the timer recovery state	Phase 2	All MS	A	
25.2.2.3	Segmentation and concatenation	Phase 2	All MS	A	
25.2.3	Normal layer 2 disconnection	Phase 2	All MS	A	
25.2.4.1	I frame loss (MS to SS)	Phase 2	All MS	A	
25.2.4.2	RR response frame loss (SS to MS)	Phase 2	All MS [covered in 25.2.2.2]	A	
25.2.4.3	RR response frame loss (MS to SS)	Phase 2	All MS	A	
25.2.5.1	I frame with C bit set to zero	Phase 2	All MS	A	
25.2.5.2	SABM frame with C bit set to zero	Phase 2	All MS	A	
25.2.6.1	N(S) sequence error	Phase 2	All MS	A	
25.2.6.2	N(R) sequence error	Phase 2	All MS	A	
25.2.6.3	Improper F bit	Phase 2	All MS [covered in 25.2.2.2]	A	
25.2.7	Test on receipt of invalid frames	Phase 2	All MS	A	
26.2.1.1	Channel request/initial time	Phase 2	All MS	A	
26.2.1.2	Channel request/repetition time	Phase 2	All MS	A	
26.2.1.3	Channel request/random reference	Phase 2	All MS	A	
26.2.2-p1	IMSI detach and IMSI attach	Phase 2	All MS	A	
26.2.2-p2	IMSI detach and IMSI attach	Phase 2	MS where SIM removal is possible without powering down	C51	
26.2.2-p3	IMSI detach and IMSI attach	Phase 2	All MS	A	
26.2.2-p4	IMSI detach and IMSI attach	Phase 2	All MS	A	
26.2.3	Sequenced MM/CC message transfer	Phase 2	All MS	C52	
26.2.4 pr1	Establishment cause, Procedure 1 (TCH)	Phase 2	MS supporting a service on a traffic channel	C37	
26.2.4 pr2	Establishment cause, Procedure 2 (TCH/H)	Phase 2	MS supporting a service on a half-rate channel	C38	
26.2.4 pr3	Establishment cause, Procedure 3 (TCH/FS)	Phase 2	MS supporting speech teleservices	C42	
26.2.4 pr4	Establishment cause, Procedure 4 (data)	Phase 2	MS supporting a data service	C39	
26.2.4 pr5	Establishment cause, Procedure 5	Phase 2	All MS	A	
26.2.4 pr6	Establishment cause, Procedure 6	Phase 2	All MS	A	
26.2.4 pr7	Establishment cause, Procedure 7 (non-call-SS)	Phase 2	MS supporting a non call related supplementary service operation	C40	
26.2.4 pr8	Establishment cause, Procedure 8 (SMS/PP MO)	Phase 2	MS supporting SMS/PP MO	C41	
26.3.2	MS indication of available PLMNs	Phase 2	All MS	A	
26.3.3 steps a - c	MS will send only if BSS is "on air"	Phase 2	All MS	A	
26.3.3 step d	MS will send only if BSS is "on air"	Phase 2	MS supporting speech	C52	

Clause	Title	Release	Applicability	Status	Supported
26.3.4	Manual mode of PLMN selection	Phase 2	All MS	A	
26.6.3.8	Enhanced Measurement /all neighbours present	R99	MS supporting both GSM and UTRAN	C289	
26.5.1	Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions/unknown protocol discriminator	Phase 2	All MS	A	
26.5.2.1.1	TI and skip indicator/RR/Idle Mode	Phase 2	All MS	A	
26.5.2.1.2	TI and skip indicator/RR/RR-Connection established	Phase 2	All MS	A	
26.5.2.2	TI and skip indicator/MM	Phase 2	All MS	A	
26.5.2.3	TI and skip indicator/CC	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.3.1	Undefined or unexpected message type/undefined message type/CC	Phase 2	MS supporting CC protocol for at least one Bearer Capability [Not specified in TC body]	C43	
26.5.3.2	Undefined or unexpected message type/undefined message type/MM	Phase 2	MS supporting CC protocol for at least one Bearer Capability [Not specified in TC body]	C43	
26.5.3.3	Undefined or unexpected message type/undefined message type/RR	Phase 2	All MS	A	
26.5.3.4	Undefined or unexpected message type/unexpected message type/CC	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.4.1	Unforeseen information elements in the non-imperative message part/duplicated information elements	Phase 2	All MS	A	
26.5.5.1.1.1	Non-semantic mandatory IE errors/RR/missing mandatory IE error/special case	Phase 2	All MS	A	
26.5.5.1.1.2	Non-semantic mandatory IE errors/RR/missing mandatory IE error/general case	Phase 2	All MS	A	
26.5.5.1.2	Non-semantic mandatory IE errors/RR/comprehension required	Phase 2	All MS	A	
26.5.5.2.1	Non-semantic mandatory IE errors/MM/syntactically incorrect mandatory IE	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.5.2.2	Non-semantic mandatory IE errors/MM/syntactically incorrect mandatory IE	Phase 2	All MS	A	
26.5.5.2.3	Non-semantic mandatory IE errors/MM/comprehension required	Phase 2	All MS	A	
26.5.5.3.1.1	Non-semantic mandatory IE errors/CC/missing mandatory IE/disconnect message	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.5.3.1.2	Non-semantic mandatory IE errors/CC/missing mandatory IE/general case	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.5.3.2	Non-semantic mandatory IE errors/CC/comprehension required	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.6.1.1	Unknown IE, comprehension not required/MM/IE unknown in the protocol	Phase 2	All MS	A	
26.5.6.1.2	Unknown IE, comprehension not required/MM/IE unknown in the message	Phase 2	All MS	A	
26.5.6.2.1	Unknown information elements in the non-imperative message part/CC/Call establishment	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	

Clause	Title	Release	Applicability	Status	Supported
26.5.6.2.2	Unknown information elements in the non-imperative message part/CC/disconnect	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.6.2.3	Unknown information elements in the non-imperative message part/CC/release	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.6.2.4	Unknown information elements in the non-imperative message part/CC/release complete	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.5.6.3	Unknown IE in the non-imperative message part, comprehension not required/RR	Phase 2	All MS	A	
26.5.7.1.1	Spare bits/RR/paging channel	Phase 2	All MS	A	
26.5.7.1.2	Spare bits/RR/BCCH	Phase 2	All MS	A	
26.5.7.1.3	Spare bits/RR/AGCH	Phase 2	All MS	A	
26.5.7.1.4	Spare bits/RR/Connected Mode	Phase 2	All MS	A	
26.5.7.2	Spare bits/MM	Phase 2	All MS	A	
26.5.7.3	Spare bits/CC	Phase 2	MS supporting at least one MT circuit switched basic service.	C31	
26.6.1.1	Immediate assignment/SDCCH or TCH assignment	Phase 2	First test, All MS Second test, MS supporting TCH/F Third test, MS supporting TCH/H	A	
26.6.1.2	Immediate assignment/extended assignment	Phase 2	All MS	A	
26.6.1.3	Immediate assignment/assignment rejection	Phase 2	All MS	A	
26.6.1.4	Immediate assignment/ignore assignment	Phase 2	All MS	A	
26.6.1.5	Immediate assignment after immediate assignment reject	Phase 2	All MS	A	
26.6.2.1.1	Paging/normal/type 1	Phase 2	All MS	A	
26.6.2.1.2	Paging/normal/type 2	Phase 2	All MS	A	
26.6.2.1.3	Paging/normal/type 3	Phase 2	All MS	A	
26.6.2.2	Paging/extended	Phase 2	All MS	A	
26.6.2.3.1	Paging/reorganization/procedure 1	Phase 2	All MS	A	
26.6.2.3.2	Paging/reorganization/procedure 2	Phase 2	All MS	A	
26.6.2.4	Paging/same as before	Phase 2	All MS	A	
26.6.2.5	Paging/multislot CCCH	Phase 2	All MS	A	
26.6.3.1	Measurement/no neighbours	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.6.3.2	Measurement/all neighbours present	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.6.3.3	Measurement/barred cells and non-permitted NCCs	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.6.3.4	Measurement/DTX	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.6.3.5	Measurement/Frequency Formats	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.6.3.6	Measurement/Multiband environment	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.3.7	Measurement/New Cell Reporting	R96	MS supporting CC protocol for at least one bearer capability	C43	
26.6.4.1	Dedicated assignment/successful case	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	

Clause	Title	Release	Applicability	Status	Supported
26.6.4.2.1	Dedicated assignment/failure/failure during active state	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.4.2.2	Dedicated assignment/failure/general case	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.1-1	Handover/successful/active call/non-synchronized, M = 1	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.1-2	Handover/successful/active call/non-synchronized, M = 2	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.1-3	Handover/successful/active call/non-synchronized, M = 3	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.1-4	Handover/successful/active call/non-synchronized, M = 4	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.1-5	Handover/successful/active call/non-synchronized, M = 5	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.1-6	Handover/successful/active call/non-synchronized, M = 6	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.1-7	Handover/successful/active call/non-synchronized, M = 7	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.1-8	Handover/successful/active call/non-synchronized, M = 8	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.2-1	Handover/successful/call under establishment/non-synchronized, M = 1	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.2-2	Handover/successful/call under establishment/non-synchronized, M = 2	Phase 2	MS which support at least one MO circuit switched basic service and support dual rate channel type	C323	
26.6.5.2-3	Handover/successful/call under establishment/non-synchronized, M = 3	Phase 2	MS which support at least one MO circuit switched basic service	C323	
26.6.5.2-4	Handover/successful/call under establishment/non-synchronized, M = 4	Phase 2	MS which support at least one MO circuit switched basic service	C323	
26.6.5.2-5	Handover/successful/call under establishment/non-synchronized, M = 5	Phase 2	MS which support at least one MO circuit switched basic service and support dual rate channel type	C323	
26.6.5.2-6	Handover/successful/call under establishment/non-synchronized, M = 6	Phase 2	MS which support at least one MO circuit switched basic service and support dual rate channel type	C123	
26.6.5.2-7	Handover/successful/call under establishment/non-synchronized, M = 7	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.2-8	Handover/successful/call under establishment/non-synchronized, M = 8	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.2-9	Handover/successful/call under establishment/non-synchronized, M = 9	Phase 2	MS which support at least one MO circuit switched basic service	C36	

Clause	Title	Release	Applicability	Status	Supported
26.6.5.2-10	Handover/successful/call under establishment/non-synchronized, M = 10	Phase 2	MS which support at least one MO circuit switched basic service and support dual rate channel type	C123	
26.6.5.3-1	Handover/successful/active call/finely synchronized, M = 1	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.3-2	Handover/successful/active call/finely synchronized, M = 2	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.5.4-1	Handover/successful/call under establishment/finely synchronized, M = 1	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.4-2	Handover/successful/call under establishment/finely synchronized, M = 2	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.4-3	Handover/successful/call under establishment/finely synchronized, M = 3	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.4-4	Handover/successful/call under establishment/finely synchronized, M = 4	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.5.1	Handover/successful/active call/pre-synchronized/Timing Advance IE not included	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.5.2	Handover/successful/call being established/pre-synchronized/timing advance IE is included/reporting of observed time difference requested.	Phase 2	MS which support at least one MO circuit switched basic service	C36	
26.6.5.6	Handover/successful/active call/pseudo synchronized	Phase 2	MS supporting CC protocol for at least one bearer capability and supporting the pseudo synchronized handover procedure	C79	
26.6.5.7	Handover/successful/active call/non-synchronized/reporting of observed time difference requested.	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.8	Handover/layer 3 failure	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.5.9	Handover/layer 1 failure	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.6.1	Frequency redefinition	Phase 2	All MS	A	
26.6.7.1	Test of the channel mode modify procedure/full rate	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.7.2	Test of the channel mode modify procedure/half rate	Phase 2	MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec	C50	
26.6.8.1	Ciphering mode/start ciphering	Phase 2	MS supporting CC protocol for at least one bearer capability and supporting encryption algorithm A5/1 and/or A5/2	C47	
26.6.8.2	Ciphering mode/no ciphering	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.8.3	Ciphering mode/old cipher key	Phase 2	MS supporting CC state U10 and supporting encryption algorithm A5/1 and/or A5/2	C47	
26.6.8.4	Ciphering mode/change of mode, algorithm and key	Phase 2	All MS	A	

Clause	Title	Release	Applicability	Status	Supported
26.6.8.5	Ciphering mode/IMEISV request	Phase 2	All MS	A	
26.6.11.1	Classmark change	Phase 2	MS supporting CC protocol for at least one bearer capability and supporting RF amplification	C48	
26.6.11.2	Classmark interrogation	Phase 2	All MS	A	
26.6.11.3	Classmark interrogation / UTRAN Classmark Change	R99	MS supporting both GSM and UTRAN	C285	
26.6.11.4	Early UTRAN Classmark Sending	R99	MS supporting both GSM and UTRAN	C285	
26.6.12.1	Channel release/SDCCH	Phase 2	All MS	A	
26.6.12.2	Channel release/SDCCH - no L2 ACK	Phase 2	All MS	A	
26.6.12.3	Channel release/TCH-F	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.12.4	Channel release/TCH-F - no L2 ACK	Phase 2	MS supporting CC protocol for at least one bearer capability	C43	
26.6.13.1	Dedicated assignment with starting time/successful case/time not elapsed	Phase 2	All MS	A	
26.6.13.2	Dedicated assignment with starting time/successful case/time elapsed	Phase 2	All MS	A	
26.6.13.3	Dedicated assignment with starting time and frequency redefinition/failure case/time not elapsed	Phase 2	All MS	A	
26.6.13.4	Dedicated assignment with starting time and frequency redefinition/failure case/time elapsed	Phase 2	All MS	A	
26.6.13.5	Handover with starting time/successful case/time not elapsed	Phase 2	All MS	A	
26.6.13.6	Handover with starting time/successful case/time elapsed	Phase 2	All MS	A	
26.6.13.7	Handover with starting time and frequency redefinition/failure case/time not elapsed	Phase 2	All MS	A	
26.6.13.8	Handover with starting time and frequency redefinition/failure case/time elapsed	Phase 2	All MS	A	
26.6.13.9	Immediate assignment with starting time/successful case/time not elapsed	Phase 2	All MS	A	
26.6.13.10	Immediate assignment with starting time/successful case/time elapsed	Phase 2	All MS	A	
26.7.1	TMSI reallocation	Phase 2	All MS	A	
26.7.2.1	Authentication accepted	Phase 2	All MS	A	
26.7.2.2	Authentication rejected	Phase 2	All MS	A	
26.7.3.1	General Identification	Phase 2	All MS	A	
26.7.3.2	Handling of IMSI shorter than the maximum length	Phase 2	All MS	A	
26.7.4.1	Location updating/accepted	Phase 2	All MS	A	
26.7.4.2.1	Location updating/rejected/IMSI invalid	Phase 2	All MS	A	
26.7.4.2.2-1	Location updating/rejected/PLMN not allowed, test 1	Phase 2	All MS	A	
26.7.4.2.2-2	Location updating/rejected/PLMN not allowed, test 2	Phase 2	All MS	A	
26.7.4.2.3	Location updating/rejected/location area not allowed	Phase 2	All MS	A	
26.7.4.2.4 pr1	Location updating/rejected/national roaming, Procedure 1	Phase 2	All MS	A	

Clause	Title	Release	Applicability	Status	Supported
26.7.4.2.4 pr2	Location updating/rejected/national roaming, Procedure 2	Phase 2	All MS	A	
26.7.4.2.4 pr3	Location updating/rejected/national roaming, Procedure 3	Phase 2	All MS	A	
26.7.4.2.4 pr4	Location updating/rejected/national roaming, Procedure 4	Phase 2	All MS	A	
26.7.4.2.4 pr5	Location updating/rejected/national roaming, Procedure 5	Phase 2	MS supporting SIM removal without powering down	C51	
26.7.4.3.1	Location updating/abnormal cases/random access fails	Phase 2	All MS	A	
26.7.4.3.2	Location updating/abnormal cases/attempt counter less or equal to 4, LAI different	Phase 2	All MS	A	
26.7.4.3.3	Location updating/abnormal cases/attempt counter equal to 4	Phase 2	All MS	A	
26.7.4.3.4	Location updating/abnormal cases/attempt counter less or equal to 4, stored LAI equal to broadcast LAI	Phase 2	All MS	A	
26.7.4.4	Location updating/release/expiry of T3240	Phase 2	All MS	A	
26.7.4.5.1	Location updating/periodic spread	Phase 2	All MS	A	
26.7.4.5.2	Location updating/periodic normal/test 1	Phase 2	All MS	A	
26.7.4.5.3	Location updating/periodic normal/test 2	Phase 2	All MS	A	
26.7.4.5.4.1	Location updating/periodic HPLMN search/MS waits time T	Phase 2	All MS	A	
26.7.4.5.4.2	Location updating/periodic HPLMN search/MS in manual mode	Phase 2	All MS	A	
26.7.4.5.4.3	Location updating/periodic HPLMN search/MS waits at least two minutes and at most T minutes	Phase 2	All MS	A	
26.7.4.5.4.4	Location updating/periodic search of the higher priority PLMN, when a MS is receiving foreign country's VPLMN/MS is in automatic mode.	R99	All MS	A	
26.7.4.5.4.5	Location updating/periodic search of the HPLMN, when a MS is receiving foreign country's VPLMN/MS is in automatic mode	R99	All MS	A	
26.7.4.5.4.6	Location updating/periodic search for higher priority PLMN when the list of equivalent PLMNs includes the HPLMN, when a MS is registered in a foreign country's VPLMN/MS is in automatic mode	R99	All MS	A	
26.7.4.6	Location updating/interworking of attach and periodic	Phase 2	All MS	A	
26.7.5.2	MM connection/establishment with cipher	Phase 2	All MS	A	
26.7.5.3	MM connection/establishment without cipher	Phase 2	All MS	A	
26.7.5.4	MM connection/establishment rejected	Phase 2	All MS	A	
26.7.5.5	MM connection/establishment rejected cause 4	Phase 2	All MS	A	
26.7.5.6	MM connection/expiry T3230	Phase 2	All MS	A	
26.7.5.7.1	MM connection/abortion by the network/cause #6	Phase 2	All MS	A	
26.7.5.7.2	MM connection/abortion by the network/cause not equal to #6	Phase 2	MS supporting a non call related supplementary service operation	C40	
26.7.5.8.1	MM connection/follow-on request pending/test 1	Phase 2	All MS	A	

Clause	Title	Release	Applicability	Status	Supported
26.7.5.8.2	MM connection/follow-on request pending/test 2	Phase 2	All MS	A	
26.7.5.8.3	MM connection/follow-on request pending/test 3	Phase 2	All MS	A	
26.8.1.2.1.1	Outgoing call/U0 null state/MM connection requested	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.2.1	Outgoing call/U0.1 MM connection pending/CM service rejected	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.2.2	Outgoing call/U0.1 MM connection pending/CM service accepted	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.2.3	Outgoing call/U0.1 MM connection pending/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.1	Outgoing call/U1 call initiated/receiving CALL PROCEEDING	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.2	Outgoing call/U1 call initiated/rejecting with RELEASE COMPLETE	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.3	Outgoing call/U1 call initiated/T303 expiry	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.4	Outgoing call/U1 call initiated/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.5	Outgoing call/U1 call initiated/receiving ALERTING	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.6	Outgoing call/U1 call initiated/entering state U10	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.3.7	Outgoing call/U1 call initiated/unknown message received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.1	Outgoing call/U3 MS originating call proceeding/ALERTING received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.2	Outgoing call/U3 MS originating call proceeding/CONNECT received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.3	Outgoing call/U3 MS originating call proceeding/PROGRESS received without in band information	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.4	Outgoing call/U3 MS originating call proceeding/PROGRESS with in band information	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.5	Outgoing call/U3 MS originating call proceeding/DISCONNECT with in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.6	Outgoing call/U3 MS originating call proceeding/DISCONNECT without in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.7	Outgoing call/U3 MS originating call proceeding/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.8	Outgoing call/U3 MS originating call proceeding/termination requested by the user	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.9	Outgoing call/U3 MS originating call proceeding/traffic channel allocation	Phase 2	MS supporting at least one MO circuit switched basic service	C36	

Clause	Title	Release	Applicability	Status	Supported
26.8.1.2.4.1 0	Outgoing call/U3 MS originating call proceeding/timer T310 time-out	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.1 1	Outgoing call/U3 MS originating call proceeding/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.1 2	Outgoing call/U3 MS originating call proceeding/unknown message received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.4.1 3	Outgoing call/U3 MS originating call proceeding/Internal alerting indication	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.2.5.1	Outgoing call/U4 call delivered/CONNECT received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.2	Outgoing call/U4 call delivered/termination requested by the user	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.3	Outgoing call/U4 call delivered/DISCONNECT with in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.4	Outgoing call/U4 call delivered/DISCONNECT without in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.5	Outgoing call/U4 call delivered/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.6	Outgoing call/U4 call delivered/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.7	Outgoing call/U4 call delivered/traffic channel allocation	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.5.8	Outgoing call/U4 call delivered/unknown message received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.1	U10 call active/termination requested by the user	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.2	U10 call active/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.3	U10 call active/DISCONNECT with in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.4	U10 call active/DISCONNECT without in band tones	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.5	U10 call active/RELEASE COMPLETE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.6.6	U10 call active/SETUP received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.7.1	U11 disconnect request/clear collision	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.7.2	U11 disconnect request/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.7.3	U11 disconnect request/timer T305 time-out	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.7.4	U11 disconnect request/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	

Clause	Title	Release	Applicability	Status	Supported
26.8.1.2.7.5	U11 disconnect request/unknown message received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.8.1	U12 disconnect indication/call releasing requested by the user	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.2.8.2	U12 disconnect indication/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.2.8.3	U12 disconnect indication/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.2.8.4	U12 disconnect indication/unknown message received	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.2.9.1	Outgoing call/U19 release request/timer T308 time-out	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.9.2	Outgoing call/U19 release request/2nd timer T308 time-out	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.9.3	Outgoing call/U19 release request/RELEASE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.9.4	Outgoing call/U19 release request/RELEASE COMPLETE received	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.2.9.5	Outgoing call/U19 release request/lower layer failure	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.1.3.1.1	Incoming call/U0 null state/SETUP received with a non supported bearer capability	Phase 2	MS supporting CC protocol for at least one Bearer Capability	C43	
26.8.1.3.2.1	Incoming call/U6 call present/automatic call rejection	Phase 2	MS supporting at least one MT circuit switched basic service and supporting refusal of call	C130	
26.8.1.3.3.1	Incoming call/U9 mobile terminating call confirmed/alerting or immediate connecting	Phase 2	MS supporting at least one MT circuit switched basic service	C31	
26.8.1.3.3.2	Incoming call/U9 mobile terminating call confirmed/TCH assignment	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.3.3	Void				
26.8.1.3.3.4	Incoming call/U9 mobile terminating call confirmed/DISCONNECT received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.3.5	Incoming call/U9 mobile terminating call confirmed/RELEASE received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.3.6	Incoming call/U9 mobile terminating call confirmed/lower layer failure	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.3.7	Incoming call/U9 mobile terminating call confirmed/unknown message received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.1	Incoming call/U7 call received/call accepted	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	

Clause	Title	Release	Applicability	Status	Supported
26.8.1.3.4.2	Incoming call/U7 call received/termination requested by the user	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.3	Incoming call/U7 call received/DISCONNECT received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.4	Incoming call/U7 call received/RELEASE received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.5	Incoming call/U7 call received/lower layer failure	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.6	Incoming call/U7 call received/unknown message received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.7	Incoming call/U7 call received/TCH assignment	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.4.8	Incoming call/U7 call received/RELEASE COMPLETE received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.1	Incoming call/U8 connect request/CONNECT acknowledged	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.2	Incoming call/U8 connect request/timer T313 time-out	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.3	Incoming call/U8 connect request/termination requested by the user	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.4	Incoming call/U8 connect request/DISCONNECT received with in-band information	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.5	Incoming call/U8 connect request/DISCONNECT received without in-band information	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.6	Incoming call/U8 connect request/RELEASE received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.7	Incoming call/U8 connect request/lower layer failure	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.8	Incoming call/U8 connect request/TCH assignment	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	
26.8.1.3.5.9	Incoming call/U8 connect request/unknown message received	Phase 2	MS supporting at least one MT circuit switched basic service for which immediate connect is not used	C55	

Clause	Title	Release	Applicability	Status	Supported
26.8.1.4.1.1	In-call functions/DTMF information transfer/basic procedures	Phase 2	MS supporting at least one MO circuit switched basic service for telephony	C56	
26.8.1.4.2.1	In-call functions/User notification/MS terminated	Phase 2	MS supporting at least one MT circuit switched basic service	C31	
26.8.1.4.3.1	In-call functions/channel changes/a successful channel change in active state/ Handover and Assignment Command	Phase 2	MS supporting at least one MT circuit switched basic service	C31	
26.8.1.4.3.2	In-call functions/channel changes/an unsuccessful channel change in active mode/ Handover and Assignment Command	Phase 2	MS supporting at least one MT circuit switched basic service	C31	
26.8.1.4.4.1	In-call functions/MS terminated in-call modification/modify when new mode is not supported	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.1	In-call functions/MS originated in-call modification/a successful case of modifying	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.2	In-call functions/MS originated in-call modification/modify rejected	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.3	In-call functions/MS originated in-call modification/an abnormal case of acceptance	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.4	In-call functions/MS originated in-call modification/an abnormal case of rejection	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.5	In-call functions/MS originated in-call modification/time-out of timer T323	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.6	In-call functions/MS originated in-call modification/a successful channel change in state mobile originating modify	Phase 2v	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.7	In-call functions/MS originated in-call modification/an unsuccessful channel change in state mobile originating modify	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.8	In-call functions/MS originated in-call modification/unknown message received	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.1.4.5.9	In-call functions/MS originated in-call modification/a release complete received	Phase 2	MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61)	C58	
26.8.2.1	Call Re-establishment/call present, re-establishment allowed	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.2.2	Call Re-establishment/call present, re-establishment not allowed	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.2.3	Call Re-establishment/call under establishment, transmission stopped	Phase 2	MS supporting at least one MO circuit switched basic service	C36	
26.8.3	User to user signalling	Phase 2	MS supporting at least one MT circuit switched basic service	C31	

Clause	Title	Release	Applicability	Status	Supported
26.9.2	Structured procedures/MS originated call/early assignment	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.9.3	Structured procedures/MS originated call/late assignment	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.9.4	Structured procedures/MS terminated call/early assignment	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.9.5	Structured procedures/MS terminated call/late assignment	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.9.6.1.1	Structured procedures/emergency call/idle updated/preferred channel rate	Phase 2	MS supporting speech	C52	
26.9.6.1.2	Structured procedures/emergency call/idle updated, non-preferred channel rate	Phase 2	MS supporting half-rate speech	C13	
26.9.6.2.1	Structured procedures/emergency call/idle, no IMSI/accept case	Phase 2	MS supporting speech	C52	
26.9.6.2.2	Structured procedures/emergency call/idle, no IMSI/reject case	Phase 2	MS supporting speech	C52	
26.9.7	Directed Retry/Mobile Originated Call	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.9.8	Directed Retry/Mobile Terminated Call	Phase 2	MS supporting at least one teleservice (except emergency call and dual service)	C131	
26.10.2.1	E-GSM or R-GSM signalling/RR/Measurement	Phase 2	MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability	C123	
26.10.2.2	E-GSM or R-GSM signalling/RR/Immediate assignment	Phase 2	MS supporting E-GSM or R-GSM	C124	
26.10.2.3	E-GSM or R-GSM signalling/RR/channel assignment procedure	Phase 2	MS supporting E-GSM or R-GSM	C124	
26.10.2.4.1	E-GSM or R-GSM signalling/RR/Handover/Successful handover	Phase 2	MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability	C123	
26.10.2.4.2	E-GSM or R-GSM signalling/RR/Handover/layer 1 failure	Phase 2	MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability	C123	
26.10.2.5	E-GSM or R-GSM signalling/RR/Frequency Redefinition	Phase 2	MS supporting E-GSM or R-GSM	C124	
26.10.3.1	E-GSM or R-GSM signalling/Structured procedure/Mobile originated call	Phase 2	MS supporting E-GSM or R-GSM and supporting at least one MO teleservice	C125	
26.10.3.2	E-GSM or R-GSM signalling/Structured procedures/emergency call	Phase 2	MS supporting E-GSM or R-GSM and supporting speech	C126	
26.11.2.1	Multiband signalling/RR/Immediate assignment procedure	Phase 2	MS supporting simultaneous multiband operation	C76	

Clause	Title	Release	Applicability	Status	Supported
26.11.2.2.1	Multiband signalling/RR/Handover/successful/active call/non-synchronized	Phase 2	MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability	C78	
26.11.2.2.2	Multiband signalling/RR/Handover/layer 1 failure	Phase 2	MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability	C78	
26.11.2.2.3	Multiband signalling/RR/Handover/Multiband BCCH/successful/active call/non synchronized	Phase 2	MS supporting simultaneous multiband operation and supporting CC protocol	C78	
26.11.2.2.4	Multiband signalling/RR/Handover/Multiband BCCH/Intracell Handover - Interband Assignment	Phase 2	MS supporting simultaneous multiband operation and supporting CC protocol	C78	
26.11.2.3	Multiband signalling/RR/Measurement reporting	Phase 2	MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability	C78	
26.11.3.1.1	Multiband signalling/MM/Location updating/accepted	Phase 2	MS supporting simultaneous multiband operation	C76	
26.11.3.1.2	Multiband signalling/MM/Location updating/periodic	Phase 2	MS supporting simultaneous multiband operation	C76	
26.11.5.1	Multiband signalling/Structured procedures/MS originated call/early assignment	Phase 2	MS supporting simultaneous multiband operation and supporting at least one MO teleservice	C127	
26.11.5.2	Multiband signalling/Structured procedures/MS terminated call/late assignment	Phase 2	MS supporting simultaneous multiband operation and supporting at least one MT teleservice	C127	
26.12.1	EFR signalling/test of the channel mode modify procedure	Phase 2	MS supporting EFR speech	C83	
26.12.2.1	EFR signalling/Handover/active call/successful case	Phase 2	MS supporting EFR speech	C83	
26.12.3	EFR signalling/Structured procedures/MS originated call/late assignment	Phase 2	MS supporting EFR speech and at least one MO circuit switched basic service	C84	
26.12.4	EFR signalling/Structured procedures/MS terminated call/early assignment	Phase 2	MS supporting EFR speech and at least one MT circuit switched basic service	C85	
26.12.5	EFR signalling/Structured procedures/emergency call	Phase 2	MS supporting EFR speech	C83	
26.12.6	EFR Signalling/Directed Retry/Mobile Originated Call	Phase 2	MS supporting EFR speech	C83	
26.12.7	EFR Signalling/Directed Retry/Mobile Terminated Call	Phase 2	MS supporting EFR speech	C83	
26.13.1.1.1	Multislot signalling/RR/Measurement symmetric	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.1.2	Multislot signalling/RR/Measurement asymmetric	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.1.3	Multislot signalling/RR/Measurement asymmetric/Change of the reported subchannel	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.2.1	Multislot signalling/RR/Dedicated assignment/successful case	R96	HSCSD Multislot MS	C86	
26.13.1.2.2	Multislot signalling/RR/Dedicated assignment/failure/general case	R96	HSCSD Multislot MS	C86	

Clause	Title	Release	Applicability	Status	Supported
26.13.1.3.1	Multislot signalling/RR/Handover/successful/active call/non-synchronized	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.3.2	Multislot signalling/RR/Handover/successful/call under establishment/non-synchronized/resource upgrading	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.3.3	Multislot signalling/RR/Handover/successful/active call/finely synchronized/resource downgrading	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.3.4	Multislot signalling/RR/Handover/successful/call under establishment/finely synchronized/relocation of channels	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.3.5	Multislot signalling/RR/Handover/successful/call under establishment/pre-synchronized/resource upgrading	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.4	Multislot signalling/RR/Test of the channel mode modify procedure	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.1.5	Multislot signalling/RR/Early classmark sending	R96	HSCSD Multislot MS	C86	
26.13.2.1.1	Multislot signalling/CC/In-call functions/User initiated service level upgrade/successful	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.2.1.2	Multislot signalling/CC/In-call functions/User initiated service level downgrade/successful	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.2.1.3	Multislot signalling/CC/In-call functions/User initiated service level upgrade/Time-out of T323	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.2.1.4	Multislot signalling/CC/In-call functions/User initiated service level upgrade/modify reject	R96	MS supporting Multislot class and CC protocol for at least one Bearer Capability	C87	
26.13.3.1	Multislot signalling/Structured procedures/MS originated call/early assignment/HSCSD/non-transparent	R96	MS supporting Multislot class and at least one MO circuit switched basic service	C88	
26.13.3.2	Multislot signalling/Structured procedures/MS originated call/late assignment/HSCSD/non-transparent	R96	MS supporting Multislot class and at least one MO circuit switched basic service	C88	
26.13.3.3	Multislot signalling/Structured procedures/MS originated call/early assignment/HSCSD/transparent	R96	MS supporting Multislot class and at least one MO circuit switched basic service	C88	
26.13.3.4	Multislot signalling/Structured procedures/MS terminated call/early assignment/HSCSD/non-transparent	R96	MS supporting Multislot class and at least one MT circuit switched basic service	C89	
26.13.3.5	Multislot signalling/Structured procedures/MS terminated call/early assignment/HSCSD/transparent	R96	MS supporting Multislot class and at least one MT circuit switched basic service	C89	
26.14.1.1	Notification/notification indication	R96	MS supporting VGCS or VBS listening	C104	
26.14.1.2	Notification/NCH position	R96	MS supporting VGCS or VBS listening	C104	
26.14.1.3	Notification/Reduced NCH monitoring	R96	MS supporting VGCS or VBS listening and reduced monitoring	C105	
26.14.1.4	Notification/limited service	R96	MS supporting VGCS or VBS listening	C104	

Clause	Title	Release	Applicability	Status	Supported
26.14.2.1	Paging/Paging indication	R96	MS supporting VGCS or VBS listening	C104	
26.14.2.2	Paging/Notification	R96	MS supporting VGCS or VBS listening	C104	
26.14.3.1	RR Procedures/frequency redefinition	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.3.2	RR Procedures/assignment	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.3.3	RR Procedures/handover/successful in group transmit mode	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.3.4	RR Procedures/handover/successful at group call establishment	R96	MS supporting VGCS/VBS originating	C107	
26.14.3.5	RR Procedures/handover/failure	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.3.6.1	RR Procedures/Measurement/all neighbours present	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.4.1	Uplink Access/uplink investigation	R96	MS supporting VGCS talking	C108	
26.14.4.2	Uplink Access/uplink access	R96	MS supporting VGCS talking	C108	
26.14.4.3	Uplink Reply in VGCS receive mode	R96	MS supporting VGCS talking	C108	
26.14.5.1	Leaving group receive mode	R96	MS supporting VGCS/VBS listening	C104	
26.14.5.2	Leaving group transmit mode	R96	MS supporting VGCS talking	C108	
26.14.6.1	GCC/BCC Procedures/MO call establishment	R96	MS supporting VGCS/VBS originating	C107	
26.14.6.2	GCC/BCC Procedures/Transaction Identifier	R96	MS supporting VGCS talking or VBS originating	C106	
26.14.6.3	GCC/BCC Procedures/Call Termination/originator/group transmit mode	R96	MS supporting VGCS/VBS originating	C107	
26.14.6.4	GCC/BCC Procedures/Call Termination/originator/ group receive mode	R96	MS supporting VGCS originating	C109	
26.14.6.5	GCC/BCC Procedures/Call Termination/not originator	R96	MS supporting VGCS listening	C128	
26.14.6.6	GCC/BCC Procedures/GCC states	R96	MS supporting VGCS talking	C108	
26.14.6.7	GCC/BCC Procedures/BCC states	R96	MS supporting VBS originating	C110	
26.14.7.1	Error Handling/short message length, unknown message type and TI	R96	MS supporting VGCS or VBS originating	C107	
26.14.7.2	Error Handling/incorrect information elements	R96	MS supporting VGCS or VBS listening	C104	
26.14.7.3	Error Handling/Message not addressing VGCS receive mode	R96	MS supporting VGCS or VBS listening	C104	
26.14.8.1	Structured procedures/very early and early assignments	R96	MS supporting VGCS or VBS originating	C107	
26.14.9.1	Cell change/same LA	R96	MS supporting VGCS or VBS listening	C104	
26.14.9.2	Cell change/different LA	R96	MS supporting VGCS or VBS listening	C104	
26.14.9.3	Cell change/different PLMN	R96	MS supporting VGCS or VBS listening	C104	
26.14.11.1	VGCS-VBS/User-to-Dispatcher Information/BCC MO call	Release 4	MS supporting VGCS or VBS originating	C104	
26.14.11.2	VGCS-VBS/User-to-Dispatcher information/GCC MO call	Release 4	MS supporting VGCS or VBS listening	C104	
26.14.11.3	VGCS-VBS/User-to-Dispatcher information/Compressed user information in VBS fast call set-up	Release 4	MS supporting VGCS or VBS listening	C104	

Clause	Title	Release	Applicability	Status	Supported
26.14.11.4	VGCS-VBS/User-to-Dispatcher information/Compressed User-to-Dispatcher information in VGCS fast call set-up	Release 4	MS supporting VGCS or VBS listening	C104	
26.15.2.1	SoLSA signalling// RR/classmark interrogation	R99	MS supporting SoLSA	C207	
26.15.3.1.1	SoLSA signalling/ MM/location updating	R99	MS supporting SoLSA	C207	
26.15.3.2	SoLSA signalling/ MM/MM information	R99	MS supporting SoLSA	C207	
26.15.4.1	SoLSA signalling/ CC/call re-establishment/call present	R99	MS supporting SoLSA	C207	
26.15.5.1	SoLSA signalling/ structured procedures/MS originated call/early assignment	R99	MS supporting SoLSA	C207	
26.15.5.2	SoLSA signalling/ structured procedures/MS originated call/late assignment	R99	MS supporting SoLSA	C207	
26.15.5.3	SoLSA signalling/ structured procedures/MS terminated call/early assignment	R99	MS supporting SoLSA	C207	
26.15.5.4	SoLSA signalling/ structured procedures/MS terminated call/late assignment	R99	MS supporting SoLSA	C207	
26.15.5.5	SoLSA signalling/ structured procedures/emergency call/idle updated	R99	MS supporting SoLSA	C207	
26.15.5.6	SoLSA signalling/ structured procedures/emergency call/idle, no IMSI	R99	MS supporting SoLSA	C207	
26.16.1	Adaptive Multi Rate Signalling/ Adaptive Multi Rate Signalling/	R98	MS supporting AMR	C203	
26.16.2	Adaptive Multi Rate Signalling/ Inband Signalling, Uplink Codec Adaptation	R98	MS supporting AMR	C203	
26.16.3	Adaptive Multi Rate Signalling/ Structured procedures/MS terminated call/early assignment/no initial codec mode	R98	MS supporting AMR	C203	
26.16.3a	Structured procedures / MS terminated call / early assignment / specified initial codec mode	R98	MS supporting AMR	C203	
26.16.4	Adaptive Multi Rate Signalling/ Structured procedures/MS originated call/late assignment/specified initial codec mode	R98	MS supporting AMR	C203	
26.16.4a	Structured procedures / MS originated call / late assignment / no initial codec mode	R98	MS supporting AMR	C203	
26.16.5	Adaptive Multi Rate Signalling/ AMR signalling/Handover/active call/successful case	R98	MS supporting AMR	C203	
26.16.6	Adaptive Multi Rate Signalling/ Structured procedures/emergency call	R98	MS supporting AMR	C203	
26.16.7	Adaptive Multi Rate Signalling/ AMR Signalling/Directed Retry/Mobile Originated Call	R98	MS supporting AMR	C203	
26.16.8	Adaptive Multi Rate Signalling/ AMR Signalling/Directed Retry/Mobile Terminated Call	R98	MS supporting AMR	C203	

Clause	Title	Release	Applicability	Status	Supported
26.16.9.1	AMR Configuration Change (normal)	R98	MS supporting AMR	C203	
26.16.9.2	AMR Configuration Change (abnormal)	R98	MS supporting AMR	C203	
26.16.9.3	Codec Mode Phase Change (normal)	R98	MS supporting AMR	C203	
26.16.9.4	Codec Mode Phase Change (abnormal)	R98	MS supporting AMR	C203	
26.16.9.5	Threshold change (normal)	R98	MS supporting AMR	C203	
26.16.9.6	Threshold change (abnormal)	R98	MS supporting AMR	C203	
26.16.9.7	Unknown RATSCCH REQ message	R98	MS supporting AMR	C203	
26.16.9.8	Ignore subsequent REQ prior to expiry of REQ_Activation counter	R98	MS supporting AMR	C203	
26.16.9.9	Initialization of Transaction with ACK_OK, ACK_ERR or ACK_UNKNOWN	R98	MS supporting AMR	C203	
26.16.9.10	Inversion of the Phase of the CMR/CMI	R98	MS supporting AMR	C203	
26.16.9.11	Change of Active Codec Set	R98	MS supporting AMR	C203	
26.16.9.12	Change of Thresholds without changing ACS	R98	MS supporting AMR	C203	
26.16.10.1	AMR signalling/ test of the channel mode modify procedure/full rate	R98	MS supporting AMR	C203	
26.16.10.2	AMR signalling/ test of the channel mode modify procedure/half rate	R98	MS supporting AMR	C327	
26.16.11	Handover/layer 1 failure (AMR signalling)	R98	MS supporting AMR	C203	
27.1.1	MS identification by short IMSI - Normal case	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.1.2	MS identification by short IMSI - Phase 1 DCS SIM	Phase 2	DCS ME supporting either ID-1 or Plug-in SIM	C129	
27.2	MS identification by short TMSI	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.3	MS identification by long TMSI	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.4	MS identification by long IMSI, TMSI updating and cipher key sequence number assignment	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.5	Forbidden PLMNs, location updating and undefined cipher key	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.6	MS updating forbidden PLMNs	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.7	MS deleting forbidden PLMNs	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.8	MS updating the PLMN selector list	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.9	MS recognizing the priority order of the PLMN selector list	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.10	MS access control management	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.1.1	Bit/character duration during the transmission from the ME to the SIM	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.1.2	Bit/character duration during the transmission from the SIM simulator to the ME	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.1.3	Inter-character delay	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.1.4	Error handling during the transmission from the ME to the SIM simulator	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.1.5	Error handling during transmission from the SIM simulator to the ME	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.2.2	Acceptance of SIMs with active low RST	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	

Clause	Title	Release	Applicability	Status	Supported
27.11.2.3	Characters of the answer to reset	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.2.4	PTS procedure	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.2.5	Reset repetition	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.2.6	Speed Enhancement	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.11.3	Command processing, procedure bytes	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.12.1	Operating speed in authentication procedure	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.12.2	Clock stop	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.13.1	Contact pressure	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.13.2	Shape of contacts for IC card SIM card reader	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.14.1	Entry of PIN	Phase 2	All ME	A	
27.14.2	Change of PIN	Phase 2	All ME	A	
27.14.3	Disabling the PIN	Phase 2	ME supporting either ID-1 or Plug-in SIM and supporting a feature to disable the PIN	C15	
27.14.4	PUK entry	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.14.5	Entry of PIN2	Phase 2	ME supporting a feature requiring entry of PIN2 (e.g. AoC or FDN)	C21	
27.14.6	Change of PIN2	Phase 2	ME supporting PIN2	C132	
27.14.7	PUK2 entry	Phase 2	ME supporting either ID-1 or Plug-in SIM and supporting PIN2	C17	
27.15	Abbreviated Dialling Numbers (ADN)	Phase 2	ME supporting either ID-1 or Plug-in SIM and supporting ADN	C14	
27.16	MMI reaction to SIM status encoding	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.17.1.1	Electrical tests - Phase preceding ME power on	Phase 2	All ME	A	
27.17.1.2 (a)	Electrical tests - Phase during SIM power on - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.1.2 (b)	Electrical tests - Phase during SIM power on - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.1.2 (c-1)	Electrical tests - Phase during SIM power on - 3V/5V SIM interface	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.2 (c-2)	Electrical tests - Phase during SIM power on - 3V/5V SIM interface	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.2 (d)	Electrical tests - Phase during SIM power on - 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.1.2 (e)	Electrical tests - Phase during SIM power on - 1,8V/3V SIM interface	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.1.3 (a)	Electrical tests - Phase during ME power off with clock stop forbidden - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.1.3 (c)	Electrical tests - Phase during ME power off with clock stop forbidden - 3V/5V SIM interface	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.4 (a)	Phase during ME power off with clock stop allowed - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.1.4 (b)	Phase during ME power off with clock stop allowed - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.1.4 (c-1)	Phase during ME power off with clock stop allowed - 3V/5V SIM interface, soft power down	Phase 2	ME with a 3V/5V SIM interface	C82	

Clause	Title	Release	Applicability	Status	Supported
27.17.1.4 (c-2)	Phase during ME power off with clock stop allowed - 3V/5V SIM interface, 3V/5V switching	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.4 (d)	Phase during ME power off with clock stop allowed – 1,8V SIM interface, soft power down	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.1.4 (e)	Phase during ME power off with clock stop allowed - 1,8V/3V SIM interface, soft power down	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.1.5.1	Reaction of 3V only MEs on SIM type recognition failure	Phase 2	ME with a 3V SIM interface	C81	
27.17.1.5.2	Reaction of 3V only MEs on type recognition of 5V only SIMs	Phase 2	ME with a 3V SIM interface	C81	
27.17.1.5.3	Reaction of 3V technology MEs on type recognition of 5V only SIMs	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.5.4	Reaction of 3V technology MEs on type recognition of 3V technology SIMs	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.1.5.5	Reaction of 1,8V only MEs on SIM type recognition failure	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.1.5.6	Reaction of 1,8V only MEs on type recognition of 3V only SIMs	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.1.5.7	Reaction of 1,8V technology MEs on type recognition of 3V technology SIMs	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.1.5.8	Reaction of 1,8V technology MEs on type recognition of 1,8V technology SIMs	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.2.1.1 (a)	Electrical tests on contact C1, Test 1 - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.2.1.1 (b)	Electrical tests on contact C1, Test 1 - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.2.1.1 (c-1)	Electrical tests on contact C1, Test 1 - 3V/5V SIM interface, 5V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.1.1 (c-2)	Electrical tests on contact C1, Test 1- 3V/5V SIM interface, 3V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.1.1 (d)	Electrical tests on contact C1, Test 1 – 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.2.1.1 (e)	Electrical tests on contact C1, Test 1 – 1,8V/3V SIM interface, 3V operation mode	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.2.1.2 (a)	Electrical tests on contact C1, Test 2 - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.2.1.2 (b)	Electrical tests on contact C1, Test 2 - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.2.1.2 (c-1)	Electrical tests on contact C1, Test 2 - 3V/5V SIM interface, 5V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.1.2 (c-2)	Electrical tests on contact C1, Test 2 - 3V/5V SIM interface, 3V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.1.2 (d)	Electrical tests on contact C1, Test 2 – 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.2.1.2 (e)	Electrical tests on contact C1, Test 2 – 1,8V/3V SIM interface, 3V operation mode	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.2.2 (a)	Electrical tests on contact C2 - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.2.2 (b)	Electrical tests on contact C2 - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.2.2 (c-1)	Electrical tests on contact C2 - 3V/5V SIM interface, 5V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	

Clause	Title	Release	Applicability	Status	Supported
27.17.2.2 (c-2)	Electrical tests on contact C2 - 3V/5V SIM interface, 3V operation mode	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.2 (d)	Electrical tests on contact C2 - 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.2.2 (e)	Electrical tests on contact C2 - 1,8V/3V SIM interface, 3V operation mode	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.2.3 (a)	Electrical tests on contact C3 - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.2.3 (b)	Electrical tests on contact C3 - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.2.3 (c)	Electrical tests on contact C3 - 3V/5V SIM interface	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.3 (d)	Electrical tests on contact C3 - 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.2.3 (e)	Electrical tests on contact C3 - 1,8V/3V SIM interface, 3V operation mode	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.17.2.5 (a)	Electrical tests on contact C7 - 5V SIM interface	Phase 2	ME with a 5V SIM interface	C80	
27.17.2.5 (b)	Electrical tests on contact C7 - 3V SIM interface	Phase 2	ME with a 3V SIM interface	C81	
27.17.2.5 (c)	Electrical tests on contact C7 - 3V/5V SIM interface	Phase 2	ME with a 3V/5V SIM interface	C82	
27.17.2.5 (d)	Electrical tests on contact C7- 1,8V SIM interface	Phase 2	ME with a 1,8V SIM interface	C91	
27.17.2.5 (e)	Electrical tests on contact C7 - 1,8V/3V SIM interface, 3V operation mode	Phase 2	ME with a 1,8V/3V SIM interface	C101	
27.18.1.1	ME and SIM with FND activated, EF _{ADN} invalidated and not readable or updatable	R96	ME supporting either ID-1 or Plug-in SIM and supporting FDN	C16	
27.18.2	ME and SIM with FND deactivated	Phase 2	ME supporting either ID-1 or Plug-in SIM and supporting FDN	C16	
27.18.3	Enabling, disabling and updating of FND	Phase 2	ME supporting either ID-1 or Plug-in SIM and supporting FDN	C16	
27.19	Phase identification	Phase 2	ME supporting either ID-1 or Plug-in SIM	C14	
27.20	SIM presence detection	Phase 2	All ME	A	
27.21.1	AoC not supported by SIM	Phase 2	ME supporting AoCC	C4	
27.21.2	Maximum frequency of ACM updating	Phase 2	ME supporting AoC (AoCC & AoCI)	C3	
27.21.3	Call terminated when ACM greater than ACM _{max}	Phase 2	ME supporting AoCC	C4	
27.21.4	Response codes of increase command	Phase 2	ME supporting AoCC	C4	
27.22	SIM Application Toolkit	R96	The applicability for SIM Toolkit is found in 11.10-4 clause 3, table B.1		
28.2	Constraining the access to a single number (GSM 02.07 category 3)	Phase 2	MS supporting autocalling	C7	
28.3	Constraining the access to a single number (GSM 02.07 categories 1 and 2)	Phase 2	MS supporting autocalling	C7	
28.4	Behaviour of the MS when its list of blacklisted numbers is full	Phase 2	MS capable of autocalling more than M B-party numbers	C8	
29.2.1	Verification of synchronization	Phase 2	MS supporting data services in transparent mode	C23	
29.2.2	Filtering of channel control information for transparent BCs	Phase 2	MS supporting the MT2 configuration	C122	

Clause	Title	Release	Applicability	Status	Supported
29.2.3.1	Negotiation of Radio Channel Requirement (RCR)	Phase 2	MS supporting data services in transparent mode	C23	
29.2.3.2	Negotiation of Connection Element (CE)	Phase 2	MS supporting at least one transparent data service and supporting the MT2 configuration	C25	
29.2.3.3	Negotiation of Number of Stop Bits, Number of Data bits, and Parity	Phase 2	MS supporting asynchronous data services	C6	
29.2.3.4	Negotiation of Modem Type	Phase 2	MS supporting non-transparent data services	C22	
29.2.3.5	Negotiation of Intermediate Rate	Phase 2	MS supporting non-transparent services on a TCH/F with a user rate of 4,8 kbit/s or lower	C10	
29.2.3.6	Negotiation of User Information Layer 2 Protocol	Phase 2	MS supporting asynchronous bearer services in non-transparent mode	C5	
29.2.3.7	Negotiation between TS 61 and TS 62: Mobile Originated call.	Phase 2	MS supporting TS 61	C26	
29.2.3.8	Negotiation between TS 61 and TS 62: Mobile Terminated call.	Phase 2	MS supporting TS 62 and not supporting TS 61	C28	
29.2.4	Data Rate Adaptation for Synchronous Transparent Bearer Capabilities	Phase 2	MS supporting MT2 configuration or any other possibility to send data over Um interface	C18	
29.2.6.1	Data Rate Adaptation	Phase 2	MS supporting MT0 or MT2 configuration and supporting data over the Um-interface and supporting asynchronous data Bearer services	C18	
29.2.6.2	Passage of the Break Signal	Phase 2	MS supporting MT2 configuration	C122	
29.2.6.3	Overspeed/Underspeed Handling (Local Terminal)	Phase 2	MS supporting MT2 configuration	C122	
29.2.6.4	Overspeed/Underspeed Handling (Remote Terminal)	Phase 2	MS supporting MT2 configuration	C122	
29.2.7	Interchange circuit mapping for transparent bearer capabilities	Phase 2	MS supporting MT2 configuration	C122	
29.3.1.1	Normal initialization done by the MS	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.1.2.1	Loss of UA frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.1.2.2	Total loss of UA frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.2.1	N(S) sequence number	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.2.2	Transmission window	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.2.3	Busy condition	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.3.1	N(R) sequence number	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.3.2	Busy condition	Phase 2	MS supporting at least one non-transparent bearer service	C22	

Clause	Title	Release	Applicability	Status	Supported
29.3.2.4.1	REJ frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.4.2	SREJ frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.4.3	I+S reject frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.5.1	Rejection with REJ or SREJ supervisory frames	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.5.2	Retransmission of REJ or SREJ frames	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.5.3	I+S reject frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.1	SS in checkpoint recovery mode	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.2	End of the window	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.3	End of a sequence	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.4	Time-out of one frame	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.5	No response to checkpointing	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.6	Incorrect response to checkpointing	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.7	Total loss of response to checkpointing	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.8	Retransmission of a sequence	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.2.6.9	N2 retransmission of a sequence	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.3.1	Negotiation initiated by the SS	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.3.2	Negotiation initiated by the MS	Phase 2	MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters	C120	
29.3.3.3	Collision of XID frames	Phase 2	MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters	C120	
29.3.3.4	Loss of XID frames	Phase 2	MS supporting at least one non-transparent bearer service	C22	
29.3.3.5	Total loss of XID frames	Phase 2	MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters	C120	

Clause	Title	Release	Applicability	Status	Supported
29.4.2.1.1	Mobile originated call, Call establishment procedure, Alternate speech/facsimile	Phase 2	MS supporting TS61	C26	
29.4.2.1.2	Mobile originated call, Call establishment procedure, Automatic facsimile	Phase 2	MS supporting TS62	C27	
29.4.2.2	Pre-message procedure	Phase 2	MS supporting TS 61 and/or TS62	C29	
29.4.2.3	Message procedure	Phase 2	MS supporting TS 61 and/or TS62	C29	
29.4.2.4	Post-message procedure	Phase 2	MS supporting TS 61 and/or TS62	C29	
29.4.2.5	Call release procedure	Phase 2	MS supporting TS 61 and/or TS62	C29	
29.4.2.6	CTC processing - 4th PPR for the same block	Phase 2	MS supporting TS 61 and/or TS62 and supporting the error correction mode	C30	
29.4.2.7	Transition from Facsimile to Speech - Procedure interrupt generated by receiving station	Phase 2	MS supporting TS61	C26	
29.4.2.8	Transition from Facsimile to Speech - Procedure interrupt generated by transmitting station	Phase 2	MS supporting TS61	C26	
29.4.2.9	Quality check	Phase 2	MS supporting transparent facsimile group 3 (TS62)	C27	
29.4.3.1.1.1	Mobile terminated call, Call Establishment Procedure, Alternate Speech/Facsimile, DCD Mobile Terminated	Phase 2	MS supporting TS61	C26	
29.4.3.1.1.2	Mobile terminated call, Call Establishment Procedure, Alternate Speech/Facsimile, DCD mobile originated	Phase 2	MS supporting TS61	C26	
29.4.3.1.2	Mobile terminated call, Call Establishment Procedure, Automatic facsimile	Phase 2	MS supporting TS62	C27	
29.4.3.2	Pre-message procedure	Phase 2	MS supporting TS61 and/or TS62	C29	
29.4.3.3	Message procedure	Phase 2	MS supporting TS61 and/or TS62	C29	
29.4.3.4	Post-message procedure	Phase 2	MS supporting TS61 and/or TS62	C29	
29.4.3.5	Call release procedure	Phase 2	MS supporting TS61 and/or TS62	C29	
29.4.3.6	Speed conversion factor	Phase 2	MS supporting TS61 and/or TS62	C29	
29.4.3.7	Quality Check	Phase 2	MS supporting TS61	C26	
30.1	Sending sensitivity/frequency response	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.2	Sending loudness rating	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.3	Receiving sensitivity/frequency response	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.4	Receiving loudness rating	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	

Clause	Title	Release	Applicability	Status	Supported
30.5.1	Side Tone Masking Rating (STMR)	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.5.2	Listener Side Tone Rating (LSTR)	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.6.1	Echo Loss (EL)	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.6.2	Stability margin	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.7.1	Distortion, Sending	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.7.2	Distortion, Receiving	Phase 2	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.8	Sidetone distortion	Phase 2	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.9.1	Out-of-band signals, Sending	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.9.2	Out-of-band signals, Receiving	Phase 2 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.10.1	Idle channel noise, Sending	Phase 2	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.10.2	Idle channel noise, Receiving	Phase 2	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.11	Ambient Noise Rejection	R96 up to and including release 1999	MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets	C280	
30.12	Sending sensitivity/frequency response	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.13	Sending loudness rating	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.14	Receiving sensitivity/frequency response	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.15	Receiving loudness rating	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	

Clause	Title	Release	Applicability	Status	Supported
30.16	Side Tone Masking Rating (STMR)	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.17.1	Echo Loss (EL)	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.17.2	Stability margin	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.18	Distortion, Sending	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
30.19	Ambient Noise Rejection	Release 4	MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets	C280	
31.1.1.1	CLIP/ Normal operation	Phase 2	MS supporting the SS CLIP	C197	
31.1.1.2.1	CLIP/ Interrogation accepted	Phase 2	MS supporting the SS CLIP	C197	
31.1.1.2.2	CLIP/ Interrogation rejected	Phase 2	MS supporting the SS CLIP	C197	
31.1.2.1	CLIR/ Normal operation - requesting presentation of CLI	Phase 2	MS supporting the SS CLIR	C197	
31.1.2.2	CLIR/ Normal operation - requesting restriction of CLI presentation	Phase 2	MS supporting the SS CLIR	C198	
31.1.2.3.1	CLIR/Interrogation accepted	Phase 2	MS supporting the SS CLIR	C198	
31.1.2.3.2	CLIR/Interrogation rejected	Phase 2	MS supporting the SS CLIR	C198	
31.1.3.1	COLP/ Interrogation accepted	Phase 2	MS supporting the SS COLP	C199	
31.1.3.2.1	COLP/ Interrogation accepted	Phase 2	MS supporting the SS COLP	C199	
31.1.3.2.2	COLP/ Interrogation rejected	Phase 2	MS supporting the SS COLP	C199	
31.1.4.1.1	COLR/ Interrogation accepted	Phase 2	MS supporting the SS COLR	C200	
31.1.4.1.2	COLR/ Interrogation rejected	Phase 2	MS supporting the SS COLR	C200	
31.1.4.2	COLR - Normal operation	Phase 2	All MS	A	
31.2.1.1.1	Call forwarding supplementary services, Registration accepted	Phase 2	MS supporting the SSs CFNRy or CFU	C64	
31.2.1.1.2	Call forwarding supplementary services, Registration rejected	Phase 2	MS supporting the SSs CFB or CFU or CFNRc or CFNRy	C65	
31.2.1.2.1	Call forwarding supplementary services, Erasure accepted	Phase 2	MS supporting the SSs CFB or CFNRc or CFNRy	C66	
31.2.1.2.2	Call forwarding supplementary services, Erasure rejected	Phase 2	MS supporting the SSs CFNRy or CFU	C64	
31.2.1.3	Call forwarding supplementary services, Activation	Phase 2	MS supporting the SSs CFB or CFU or CFNRc or CFNRy	C65	
31.2.1.4	Call forwarding supplementary services, Deactivation	Phase 2	MS supporting the SSs CFB or CFNRc or CFNRy	C66	
31.2.1.6.1	Call forwarding supplementary services, Interrogation accepted	Phase 2	MS supporting the SSs CFB or CFNRc or CFNRy	C66	
31.2.1.6.2	Call forwarding supplementary services, Interrogation rejected	Phase 2	MS supporting the SSs CFB or CFNRc	C133	
31.2.1.7.1.1	Call forwarding supplementary services, Notification during an incoming call	Phase 2	MS supporting CFB	C67	
31.2.1.7.1.2	Call forwarding supplementary services, Notification during an outgoing call	Phase 2	MS supporting the SSs CFB or CFU or CFNRc or CFNRy	C65	

Clause	Title	Release	Applicability	Status	Supported
31.2.1.7.2	Call forwarding supplementary services, Forwarded-to mobile subscriber side	Phase 2	MS supporting the SSs CFB or CFU or CFNRc or CFNRy	C65	
31.2.2	Call transfer and mobile access hunting supplementary services	Phase 2	Reserved		
31.3.1.1	Call completion supplementary services, Waiting call indication and confirmation	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.2.1	Call completion supplementary services, Waiting call accepted; existing call released	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.2.2.1	Call completion supplementary services; Waiting call accepted; existing call on hold, no additional calls	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.2.3	Call completion supplementary services, Existing call released by user A; waiting call accepted	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.3.1	Call completion supplementary services, Waiting call released by subscriber B	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.3.2	Call completion supplementary services, Waiting call released by calling user C	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.4	Call completion supplementary services, Activation	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.5	Call completion supplementary services, Deactivation	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.6.1	Call completion supplementary services, Interrogation accepted	Phase 2	MS supporting Call Waiting SS	C196	
31.3.1.6.2	Call completion supplementary services, Interrogation rejected	Phase 2	MS supporting Call Waiting SS	C196	
31.3.2.1	Call completion supplementary services, Hold invocation	Phase 2	MS supporting Call Hold SS	C195	
31.3.2.2	Call completion supplementary services, Retrieve procedure	Phase 2	MS supporting Call Hold SS	C195	
31.3.2.3	Call completion supplementary services, Alternate from one call to the other	Phase 2	MS supporting Call Hold SS	C195	
31.4.1.1	Multi-party supplementary services, Beginning the MultiParty service, successful case	Phase 2	MS supporting Multi Party SS	C194	
31.4.1.2	Multi-party supplementary services, Beginning the MultiParty service, unsuccessful case	Phase 2	MS supporting Multi Party SS	C194	
31.4.1.3	Multi-party supplementary services, Beginning the MultiParty service, expiry of timer T(BuildMPTY)	Phase 2	MS supporting Multi Party SS	C194	
31.4.2.1.1	Multi-party supplementary services, Put the MultiParty call on hold	Phase 2	MS supporting Multi Party SS	C194	
31.4.2.1.2	Multi-party supplementary services, Create a private communication with one of the remote parties	Phase 2	MS supporting Multi Party SS	C194	
31.4.2.1.3	Multi-party supplementary services, Terminate the entire MultiParty call	Phase 2	MS supporting Multi Party SS	C194	
31.4.2.1.4	Multi-party supplementary services, Explicitly disconnect a remote party	Phase 2	MS supporting Multi Party SS	C194	
31.4.2.2.1	Multi-party supplementary services, Release from the MultiParty call	Phase 2	MS supporting Multi Party SS	C194	
31.4.3.1.1	Multi-party supplementary services, Retrieve the held MultiParty call, successful case	Phase 2	MS supporting Multi Party SS	C194	
31.4.3.1.2	Multi-party supplementary services, Retrieve the held MultiParty call, unsuccessful case	Phase 2	MS supporting Multi Party SS	C194	

Clause	Title	Release	Applicability	Status	Supported
31.4.3.1.3	Multi-party supplementary services, Retrieve the held MultiParty call, expiry of timer T(RetrieveMPTY)	Phase 2	MS supporting Multi Party SS	C194	
31.4.3.2	Multi-party supplementary services, Initiate a new call	Phase 2	MS supporting Multi Party SS	C194	
31.4.3.3	Multi-party supplementary services, Process a call waiting request	Phase 2	MS supporting Multi Party SS	C194	
31.4.3.4	Multi-party supplementary services, Terminate the held MultiParty call	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.1.1	Multi-party supplementary services, Disconnect the single call	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.1.2.3	Clear all parties of held MultiParty call	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.1.2.4	Clear all parties of active MultiParty call	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.2	Multi-party supplementary services, Disconnect all calls	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.3.1	Multi-party supplementary services, Add the single call to the MPTY, successful case	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.3.2	Multi-party supplementary services, Add the single call to the MPTY, maximum number of participants exceeded	Phase 2	MS supporting Multi Party SS	C194	
31.4.4.4	Multi-party supplementary services, Alternate between the MPTY call and the single call	Phase 2	MS supporting Multi Party SS	C194	
31.4.5	Multi-party supplementary services, Adding extra remote parties	Phase 2	MS supporting Multi Party SS	C194	
31.5	Community of interest supplementary services	Phase 2	<i>Reserved</i>		
31.6.1.1	AOC time related charging/MS originated call	Phase 2	MS supporting AoCC	C4	
31.6.1.2	AOC time related charging/MS terminated call	Phase 2	MS supporting AoCC	C4	
31.6.1.3	AOC volume related charging/MS originated call	Phase 2	<i>Reserved</i>		
31.6.1.4	AOC volume related charging/MS terminated call	Phase 2	<i>Reserved</i>		
31.6.1.5	Change in charging information during a call	Phase 2	MS supporting AoCC	C4	
31.6.1.6	Different formats of charging information	Phase 2	MS supporting AoCC	C4	
31.6.1.7	AOC on a Call Hold call	Phase 2	MS supporting AoCC and call hold	C70	
31.6.1.8	AOC on a Multi-party call	Phase 2	MS supporting AoCC and multiparty service	C71	
31.6.2.1	Removal of SIM during an active call	Phase 2	MS supporting AoCC and SIM removal without powering down	C69	
31.6.2.2	Interruption of power supply during an active call	Phase 2	MS supporting AoCC	C4	
31.6.2.3	MS going out of coverage during an active AOCC call	Phase 2	MS supporting AoCC	C4	
31.6.2.4	ACMmax operation/Mobile Originating	Phase 2	MS supporting AoCC	C4	
31.6.2.5	ACMmax operation/Mobile Terminating	Phase 2	MS supporting AoCC	C4	
31.6.3.1	AoCI time related charging/MS originated call	Phase 2	MS supporting AoCI	C59	
31.6.3.2	AoCI time related charging/MS terminated call	Phase 2	MS supporting AoCI	C59	
31.6.3.5	Change in charging information during a call	Phase 2	MS supporting AoCI	C59	

Clause	Title	Release	Applicability	Status	Supported
31.6.3.6	Different formats of charging information	Phase 2	MS supporting AoCI	C59	
31.6.3.7	AoCI on a Call Hold call	Phase 2	MS supporting AoCI	C59	
31.6.3.8	AoCI on a Multi-party call	Phase 2	MS supporting AoCI	C59	
31.7	Additional information transfer supplementary services	Phase 2	<i>Reserved</i>		
31.8.1.1	Registration accepted	Phase 2	MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC	C62	
31.8.1.2.1	Rejection after invoke of the RegisterPassword operation	Phase 2	MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC	C62	
31.8.1.2.2	Rejection after password check with negative result	Phase 2	MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC	C62	
31.8.1.2.3	Rejection after new password mismatch	Phase 2	MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC	C62	
31.8.3.1	Activation accepted	Phase 2	MS supporting the SSs BIC Roam and BAOC	C68	
31.8.3.2.1	Rejection after invoke of ActivateSS operation	Phase 2	MS supporting the SS BOIC (Barring of Outgoing International Calls)	C134	
31.8.3.2.2	Rejection after use of password procedure	Phase 2	MS supporting the SS BAIC (Barring of All Incoming Calls)	C135	
31.8.4.1	Deactivation accepted	Phase 2	MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC	C62	
31.8.4.2.1	Rejection after invoke of DeactivateSS operation	Phase 2	MS supporting the SS BOIC (Barring of Outgoing International Calls)	C134	
31.8.4.2.2	Rejection after use of password procedure	Phase 2	MS supporting the SS BOICextHC	C136	
31.8.6.1	Interrogation accepted	Phase 2	MS supporting the SS BOICextHC or BAIC	C137	
31.8.6.2	Interrogation rejected	Phase 2	MS supporting the SS BOIC or BICRoam	C138	
31.8.7	Normal operation	Phase 2	MS supporting the SS BOIC (Barring of Outgoing International Calls)	C134	
31.9.1.1	ProcessUnstructuredSS-request/accepted	Phase 2	MS supporting USSD	C139	
31.9.1.2	ProcessUnstructuredSS-request/cross phase compatibility and error handling	Phase 2	MS supporting USSD and supporting CC protocol for at least one Bearer Capability	C140	
31.9.2.1	UnstructuredSS-Notify/accepted	Phase 2	MS supporting USSD and supporting CC protocol for at least one Bearer Capability	C140	
31.9.2.2	UnstructuredSS-Notify/rejected on user busy	Phase 2	MS supporting USSD and supporting CC protocol for at least one Bearer Capability	C140	
31.9.2.3	UnstructuredSS-Request/accepted	Phase 2	MS supporting USSD and supporting CC protocol for at least one Bearer Capability	C140	
31.9.2.4	UnstructuredSS-Request/rejected on user busy	Phase 2	MS supporting USSD and supporting CC protocol for at least one Bearer Capability	C140	
31.10	MMI input for USSD	Phase 2	All MS	A	
31.12.1	eMLPP Service/priority level of MO call	R96	MS supporting eMLPP and TS11	C111	

Clause	Title	Release	Applicability	Status	Supported
31.12.2	eMLPP Service/automatic answering point-to-point MT call	R96	MS supporting eMLPP, HOLD, CW and TS11	C112	
31.12.3	eMLPP Service/automatic answering MT VGCS or VBS call	R96	MS supporting eMLPP and supporting VGCS or VBS listening	C113	
31.12.4	eMLPP Service/registration	R96	MS supporting eMLPP	C114	
31.12.5	eMLPP Service/interrogation	R96	MS supporting eMLPP	C114	
31.13.1.1	Explicit Call Transfer invocation, successful case, both calls active, clearing using DISCONNECT	R96	MS supporting Explicit Call Transfer SS	C193	
31.13.1.2	Explicit Call Transfer invocation, successful case, both calls active, clearing using RELEASE	R96	MS supporting Explicit Call Transfer SS	C193	
31.13.1.3	Explicit Call Transfer invocation, successful case, both calls active, clearing using RELEASE COMPLETE	R96	MS supporting Explicit Call Transfer SS	C193	
31.13.1.4	Explicit Call Transfer invocation, successful case, second call alerting	R96	MS supporting Explicit Call Transfer SS	C193	
31.13.1.5	Explicit Call Transfer invocation, unsuccessful case	R96	MS supporting Explicit Call Transfer SS	C193	
31.13.1.6	Explicit Call Transfer invocation, expiry of T(ECT)	R96	MS supporting Explicit Call Transfer SS	C193	
31.14.1.1	UUS/Implicit UUS1/CC MO call	R99	MS supporting Implicit User-to-User Signaling SS	C192	
31.14.1.2	UUS/Implicit UUS1/CC MT call	R99	MS supporting Implicit User-to-User Signaling SS	C192	
31.14.1.3	UUS/Implicit UUS1/Interactions with Call Waiting and call HOLD supplementary services	R99	MS supporting Implicit User-to-User Signaling SS	C192	
31.15.1	Follow Me (FM)/Registration	R99	MS supporting Follow Me SS	C191	
31.15.2	Follow Me (FM)/Interrogation	R99	MS supporting Follow Me SS	C191	
31.15.3	Follow Me (FM)/Erasure	R99	MS supporting Follow Me SS	C191	
32.1	Full Rate Downlink speech transcoding	Phase 2	MS supporting speech	C24	
32.2	Full Rate Downlink receiver DTX functions	Phase 2	MS supporting speech	C24	
32.3	Full Rate Uplink speech transcoding	Phase 2	MS supporting speech	C24	
32.4	Full Rate Uplink transmitter DTX functions	Phase 2	MS supporting speech	C24	
32.5.4	Full Rate Speech channel transmission delay - Downlink processing delay	Phase 2	MS supporting speech	C24	
32.5.5	Full Rate Speech channel transmission delay -Downlink coding delay	Phase 2	MS supporting speech	C24	
32.5.6	Full Rate Speech channel transmission delay -Uplink processing delay	Phase 2	MS supporting speech	C24	
32.5.7	Full Rate Speech channel transmission delay -Uplink coding delay	Phase 2	MS supporting speech	C24	
32.6	Half Rate Downlink speech transcoding	Phase 2	MS supporting half rate speech	C13	
32.7	Half Rate Downlink receiver DTX functions	Phase 2	MS supporting half rate speech	C13	
32.8	Half Rate Uplink speech transcoding	Phase 2	MS supporting half rate speech	C13	
32.9	Half Rate Uplink transmitter DTX functions	Phase 2	MS supporting half rate speech	C13	

Clause	Title	Release	Applicability	Status	Supported
32.10.4	Half Rate Speech channel transmission delay - Downlink processing delay	Phase 2	MS supporting half rate speech	C13	
32.10.5	Half Rate Speech channel transmission delay - Downlink coding delay	Phase 2	MS supporting half rate speech	C13	
32.10.6	Half Rate Speech channel transmission delay - Uplink processing delay	Phase 2	MS supporting half rate speech	C13	
32.10.7	Half Rate Speech channel transmission delay - Uplink coding delay	Phase 2	MS supporting half rate speech	C13	
32.11	Intra cell channel change from a TCH/HS to a TCH/FS	Phase 2	MS supporting half rate speech	C13	
32.12	Intra cell channel change from a TCH/FS to a TCH/HS	Phase 2	MS supporting half rate speech	C13	
33.1	Entry and display of called number	Phase 2	All MS supporting display of called number	C190	
33.2.4	Ringling tone	Phase 2	All MSMS supporting audible indication of service tones	C206	
33.2.5	Busy tone	Phase 2	MS supporting audible indication of service tones All MS	C206	

Clause	Title	Release	Applicability	Status	Supported
33.2.6	Congestion tone	Phase 2	MS supporting audible indication of service tones All MS	C206	
33.2.7	Authentication failure tone	Phase 2	MS supporting audible indication of service tones All MS	C206	
33.2.8	Number unobtainable tone	Phase 2	MS supporting audible indication of service tones All MS	C206	
33.2.9	Call dropped tone	Phase 2	MS supporting audible indication of service tones All MS	C206	
33.3	Network selection/indication	Phase 2	All MS	A	
33.4	Invalid and blocked PIN indicators	Phase 2	All MS	A	
33.5	Service indicator	Phase 2	All MS supporting Service indicator	C201	
33.6	Subscription identity management	Phase 2	All MS supporting Subscription identity management	C202	
33.7	Barring of outgoing calls	Phase 2	MS supporting barring of outgoing calls	C9	
33.8	Prevention of unauthorized calls	Phase 2	MS supporting barring of outgoing calls	C9	
34.2.1	SMS mobile terminated	Phase 2	MS supporting SMS MT/PP and supporting CC protocol for at least one Bearer Capability	C72	
34.2.2	SMS mobile originated	Phase 2	MS supporting SMS MO/PP and supporting CC protocol for at least one Bearer Capability	C73	
34.2.3	Test of memory full condition and memory available notification:	Phase 2	MS supporting SMS MT/PP and storing of short messages in the SIM	C74	
34.2.4	Test of the status report capabilities and of SMS-COMMAND:	Phase 2	MS supporting SMS MT/PP and SMS MO/PP and supporting SMS status report capabilities	C141	
34.2.5.1	Short message class 0	Phase 2	MS supporting SMS MT/PP and display of received short messages	C142	
34.2.5.2	Test of class 1 short messages	Phase 2	MS supporting storing of received Class I Short Messages and display of stored Short Messages	C143	
34.2.5.3	Test of class 2 short messages	Phase 2	MS supporting storing of received Class II Short Messages in the SIM	C74	
34.2.6	Test of short message type 0 (Ph2, R96...R99 and REL-4)	Phase 2, R96...R99 & REL-4 only	MS supporting SMS MT/PP	C290	
34.2.6a	Test of short message type 0 (\geq REL 5)	REL-5	MS supporting SMS MT/PP	C290	
34.2.7	Test of the replace mechanism for SM type 1-7	Phase 2	MS supporting Replace Short Messages and display of received Short Messages	C144	
34.2.8	Test of the reply path scheme	Phase 2	MS supporting reply procedures, display of received Short Messages and submitting Short Messages	C145	

Clause	Title	Release	Applicability	Status	Supported
34.2.9.1	Multiple SMS mobile originated/MS in idle mode	Phase 2	MS supporting the ability of sending multiple short messages on the same RR connection	C272	
34.2.9.2	Multiple SMS mobile originated/MS in active mode	Phase 2	MS supporting the ability of sending multiple short messages when there is a call in progress	C220	
34.3	Short message service cell broadcast	Phase 2	All MS supporting SMS CB	C300	
34.4.1	SMS mobile terminated	R97	MS supporting MT SMS over GPRS	C251	
34.4.2	SMS mobile originated	R97	All GPRS MS	C215	
34.4.3	Test of the status report capabilities and of SMS-COMMAND over GPRS:	R97	MS supporting MT SMS over GPRS and supporting SMS status report capabilities	C252	
34.4.4	Test of capabilities of simultaneously receiving a short message whilst sending a mobile originated short message	R97	MS supporting MT SMS over GPRS	C251	
34.4.5	Attach initiated by SMS mobile originated	R97	All GPRS MS	C215	
34.4.6	Concatenated MO SMS over GPRS	R97	GPRS MS Supporting SMS over GPRS	C253	
34.4.7	Concatenated MT SMS over GPRS	R97	GPRS MS Supporting SMS over GPRS	C253	
34.4.8.1	CP Error Handling	R97	GPRS MS Supporting SMS over GPRS	C253	
34.4.8.2	RP Error Handling	R97	GPRS MS Supporting SMS over GPRS	C253	
35	Low battery voltage detection	Phase 2	All MS	A	
36	Individual equipment type requirements and interworking - special conformance testing functions	Phase 2	<i>Reserved</i>		
37	Reserved for future use				
38	Reserved for future use				
39..2.1	PLMN interface/CTS not allowed by the network	R98	MS supporting GSM-CTS	C208	
39.3.1	PLMN interface/CTS not allowed by the network	R98	MS supporting GSM-CTS supporting GSM 900, R-GSM or DCS 1800	C209	
39.3.2	PLMN interface/CTS not allowed by the network	R98	MS supporting GSM-CTS supporting GSM 900, R-GSM or DCS 1800	C209	
39.3.3	PLMN interface/CTS not allowed by the network	R98	MS supporting GSM-CTS supporting GSM 900, R-GSM or DCS 1800	C209	
39.3.4	PLMN interface/CTS not allowed by the network	R98	MS supporting GSM-CTS supporting GSM 900, R-GSM or DCS 1800	C209	
39.5.3.1.1.1	Elementary Procedures/System Access/Not corresponding FPBI	R98	MS supporting GSM-CTS	C208	
39.5.3.1.1.2	Elementary Procedures/Retransmission of CTS Access Request	R98	MS supporting GSM-CTS	C208	
39.5.3.1.1.3	Elementary Procedures/No Access Request FP in busy state	R98	MS supporting GSM-CTS	C208	
39.5.3.1.2.1	Immediate Assignment/ Immediate Assignment success	R98	MS supporting GSM-CTS	C208	
39.5.3.1.2.2	Immediate Assignment/ Immediate Assignment rejection	R98	MS supporting GSM-CTS	C208	
39.5.3.1.2.3	Immediate Assignment/ Ignore Assignment	R98	MS supporting GSM-CTS	C208	

Clause	Title	Release	Applicability	Status	Supported
39.5.3.1.3.1	Paging/paging with current CTS-MSI	R98	MS supporting GSM-CTS	C208	
39.5.3.1.3.2	Paging/paging with invalid CTS-MSI	R98	MS supporting GSM-CTS	C208	
39.5.3.1.4	Reserved				
39.5.3.1.5	Reserved				
39.5.3.1.6	Reserved				
39.5.3.1.7	Reserved				
39.5.3.1.8	Reserved				
39.5.3.1.9.1	Channel Release/TCH-F L2 Ack	R98	MS supporting GSM-CTS	C208	
39.5.3.1.9.2	Channel Release/TCH-F no L2 Ack	R98	MS supporting GSM-CTS	C208	
39.5.3.1.10.1	Authentication/Local Mutual Authentication failure	R98	MS supporting GSM-CTS	C208	
39.5.3.1.11	Reserved				
39.5.3.1.12	Reserved				
39.5.3.1.13.1	Radio Link Management/Measurement and Reporting	R98	MS supporting GSM-CTS	C208	
39.5.3.1.13.2	Total Frequency Hopping list update	R98	MS supporting GSM-CTS	C208	
39.5.3.2.1.1	Structured Procedures/Attachment	R98	MS supporting GSM-CTS	C208	
39.5.3.2.2.1	Detachment/CTS detachment upon CTS-MS power off	R98	MS supporting GSM-CTS	C208	
39.5.3.2.3	Reserved				
39.5.3.2.4	Reserved				
39.5.3.2.5	Reserved				
39.5.3.2.6	Reserved				
39.5.3.2.7.1	Handover/successful/active call	R98	MS supporting GSM-CTS	C208	
39.5.3.2.8	Handover/Layer 1 failure	R98	MS supporting GSM-CTS	C208	
39.5.3.3.1.1	Initialisation/enrolment/Enrolment with non CTS SIM	R98	MS supporting GSM-CTS	C208	
39.5.3.3.1.2	CTS-FP not ready for Enrolment	R98	MS supporting GSM-CTS	C208	
39.5.3.3.2	Reserved				
39.5.3.3.3.1	De-enrolment/Attached CTS_MS de-enrolment	R98	MS supporting GSM-CTS	C208	
41.1.1.1	RR/Paging/on PCCCH for GPRS service/normal paging with P-TMSI successful.	R97	All GPRS MS	C215	
41.1.1.2	RR/Paging/on PCCCH for GPRS service/normal paging with IMSI successful	R97	All GPRS MS	C215	
41.1.1.3	RR/Paging/on PCCCH for GPRS service/extended paging with P-TMSI successful	R97	All GPRS MS	C215	
41.1.1.4	RR/Paging/on PCCCH for GPRS service/paging reorganisation successful	R97	All GPRS MS	C215	
41.1.2	RR/Paging/on PCCCH for circuit-switched services/paging successful	R97	MS supporting GPRS mode A or B	C226	
41.1.3	RR/Paging/on PCCCH/paging ignored	R97	All GPRS MS	C215	
41.1.4.1	RR/Paging/on PACCH for circuit-switched services/ paging successful	R97	MS supporting GPRS mode A or mode B	C226	
41.1.4.2	RR/Paging/on PACCH for circuit-switched services/ paging ignored	R97	MS supporting GPRS mode A or B	C226	
41.1.5.1.1	RR/Paging/on CCCH for GPRS service/normal paging with P-TMSI successful	R97	All GPRS MS	C215	
41.1.5.1.2	RR/Paging/on CCCH for GPRS service/normal paging with IMSI successful	R97	All GPRS MS	C215	
41.1.5.1.3	RR/Paging/on CCCH for GPRS service/normal paging with P-TMSI ignored	R97	All GPRS MS	C215	
41.1.5.2.1	RR/Paging/on CCCH for GPRS service/extended paging with P-TMSI successful	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
41.1.5.3	RR/Paging/on CCCH for GPRS service/paging reorganisation	R97	All GPRS MS	C215	
41.1.5.4	RR/Paging/on CCCH for GPRS service/default message contents	R97	All GPRS MS	C215	
41.1.6	RR/Paging/Before T3172 expiry	R97	All GPRS MS	C215	
41.2.1.1	Permission to access the network/priority classes	R97	All GPRS MS	C215	
41.2.2.1	Initiation of the packet access procedure/establishment causes	R97	All GPRS MS	C215	
41.2.2.2	Random references for single block packet access	R97	All GPRS MS	C215	
41.2.2.3	Random references for one phase packet access	R97	All GPRS MS	C215	
41.2.2.4	Initiation of the packet access procedure/timer T3146	R97	All GPRS MS	C215	
41.2.2.5	Initiation of the packet access procedure/Request Reference	R97	All GPRS MS	C215	
41.2.3.1	Two-message assignment/Successful case	R97	All GPRS MS	C215	
41.2.3.2	Two-message assignment/Failure cases	R97	All GPRS MS	C215	
41.2.3.3	Packet uplink assignment/Polling bit set	R97	All GPRS MS	C215	
41.2.3.4	One phase packet access/Contention resolution/Successful case	R97	All GPRS MS	C215	
41.2.3.5	One phase packet access/Contention resolution/TLLI mismatch	R97	All GPRS MS	C215	
41.2.3.6	One phase packet access/Contention resolution/Counter N3104	R97	All GPRS MS	C215	
41.2.3.7	One phase packet access/Contention resolution/Timer T3166	R97	All GPRS MS	C215	
41.2.3.8	One phase packet access/Contention resolution/4 access repetition attempts	R97	All GPRS MS	C215	
41.2.3.9	One phase packet access/TBF starting time	R97	All GPRS MS	C215	
41.2.3.10	One phase packet access/Timing Advance Index present	R97	All GPRS MS	C215	
41.2.3.11	One phase packet access/Timing Advance Index not present	R97	All GPRS MS	C215	
41.2.4.1	Single block packet access/Packet Resource Request	R97	All GPRS MS	C215	
41.2.4.2	Single block packet access/Packet Measurement Report	R97	All GPRS MS	C215	
41.2.5.1	Packet access rejection/wait indication	R97	All GPRS MS	C215	
41.2.5.2	Packet access rejection/assignment before T3142 expires	R97	All GPRS MS	C215	
41.2.6.1	Initiation of packet downlink assignment procedure/MS listens to correct CCCH block	R97	All GPRS MS	C215	
41.2.6.2	Initiation of packet downlink assignment procedure/timer T3190	R97	All GPRS MS	C215	
41.2.6.3	Initiation of packet downlink assignment procedure/TBF starting time	R97	All GPRS MS	C215	
41.2.6.4	Initiation of packet downlink assignment procedure/incorrect TFI	R97	All GPRS MS	C215	
41.2.7.1	Single block packet downlink assignment/TBF Starting Time	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
41.2.7.2	Single block packet downlink assignment/MS returns to packet idle mode	R97	All GPRS MS	C215	
41.3.1.1	TBF Release/Uplink/Normal/MS initiated/Acknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.1.2	TBF Release/Uplink/Normal/MS initiated/Unacknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.1.3	TBF Release/Uplink/Normal/MS initiated/Channel coding change during countdown	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.1.4	TBF release / Uplink / Normal / MS initiated / Whilst in DTM	R99	All DTM capable MS	C305	
41.3.2.1	TBF Release/Uplink/Normal/Network initiated/Acknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.2.2	TBF Release/Uplink/Normal/Network initiated/Unacknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.2.3	TBF release / Uplink / Normal / Network initiated / Whilst in DTM	R99	All DTM capable MS	C305	
41.3.3	TBF Release/Uplink/Network initiated/Abnormal release	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.4.1	TBF Release/Downlink/Normal/Network initiated/Acknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.4.2	TBF Release/Downlink/Normal/Network initiated/Unacknowledged mode	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.4.3	TBF release / Downlink / Normal / Network initiated / Whilst in DTM	R99	All DTM capable MS	C305	
41.3.5.1	PDCH Release/Without TIMESLOTS_AVAILABLE	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.5.2	PDCH Release/With TIMESLOTS_AVAILABLE	R97	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.6.1	TBF Release / Extended Uplink / Recalculation of CV before CV = 0	Rel-4	All GPRS MS supporting activation of at least one PDP context	C222	
41.3.6.2	TBF Release / Extended Uplink / Recalculation of CV after CV = 0	Release 4	All GPRS MS supporting activation of at least one PDP context	C222	
41.5.1.1.1.1	Uplink TBF establishment with no reallocation of CS resources / Successful case / Uplink resources assigned	R99	All DTM capable MS	C305	
41.5.1.1.1.2	Uplink TBF establishment with no reallocation of CS resources / Successful case / Downlink resources assigned	R99	All DTM capable MS	C305	
41.5.1.1.1.3	Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / DTM reject	R99	All DTM capable MS	C305	
41.5.1.1.1.4	Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Inter System to UTRAN Handover Command	R99	MS supporting both UTRAN and DTM	C315	
VOID	VOID				
VOID	VOID				
41.5.1.1.1.5	Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Assignment Command	R99	All DTM capable MS	C305	

Clause	Title	Release	Applicability	Status	Supported
41.5.1.1.1.6	Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Handover Command	R99	All DTM capable MS	C305	
41.5.1.1.1.7	Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Channel Release	R99	All DTM capable MS	C305	
41.5.1.1.2.1	Uplink TBF establishment with reallocation of CS resources / Successful case	R99	All DTM capable MS	C305	
41.5.1.1.2.2	Uplink TBF establishment with reallocation of CS resources / Abnormal case / Assignment Failure	R99	All DTM capable MS	C305	
VOID	VOID				
VOID	VOID				
VOID	VOID				
41.5.1.1.2.3.4	Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Singleslot allocation	R99	MS not supporting singleslot allocation in DTM	C311	
41.5.1.1.2.3.5	Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Incorrect allocation	R99	MS supporting both DTM multislot Class 5 and 9	C308	
41.5.1.1.3	Uplink TBF establishment required whilst in DM / DTM not supported in cell	R99	All DTM capable MS	C305	
41.5.1.2.1.1	Downlink TBF establishment in Ready State / Successful case	R99	All DTM capable MS	C305	
41.5.1.2.1.2	Downlink TBF establishment in Ready State / Abnormal cases / No cell allocation available	R99	All DTM capable MS	C305	
41.5.1.2.2	Whilst in Standby State / Downlink TBF establishment	R99	All DTM capable MS	C305	
41.5.2.1	MT CS establishment whilst in packet transfer mode with a downlink TBF established	R99	All DTM capable MS	C305	
41.5.2.2	MT CS establishment whilst in packet transfer mode with a uplink TBF established	R99	All DTM capable MS	C305	
41.5.2.3	MO CS establishment whilst in packet transfer mode with uplink and downlink TBFs established	R99	All DTM capable MS	C305	
41.5.2.4	MO CS establishment whilst in packet transfer mode and DTM is not supported in current cell	R99	All DTM capable MS	C305	
41.5.3.1.1	Uplink TBF establishment with a downlink TBF established and no PS downlink reallocation	R99	All DTM capable MS	C305	
41.5.3.1.2	Uplink TBF establishment with a downlink TBF established and PS downlink reallocation	R99	All DTM capable MS	C305	
41.5.3.2.1	Downlink TBF establishment with a uplink TBF established and no PS uplink reallocation	R99	All DTM capable MS	C305	
41.5.3.2.2	Downlink TBF establishment with a uplink TBF established and PS uplink reallocation	R99	All DTM capable MS	C305	
42.1.1.1	Packet Channel Request/Message format	R97	All GPRS MS	C215	
42.1.1.2	Packet Channel Request/Response to Packet Paging	R97	All GPRS MS	C215	
42.1.1.3	Packet Channel Request/Access type	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.1.1.4.1	Packet Channel Request/Access persistence control on PRACH/M+1 attempts	R97	All GPRS MS	C215	
42.1.1.4.2	Packet Channel Request/Access persistence control on PRACH/Persistence level	R97	All GPRS MS	C215	
42.1.1.4.3	Packet Channel Request/Access persistence control on PRACH/Successive Attempts	R97	All GPRS MS	C215	
42.1.2.1.1.1	Packet Uplink Assignment/Packet queuing notification/Stop sending Packet Channel Requests	R97	All GPRS MS	C215	
42.1.2.1.1.2	Packet Uplink Assignment/Packet queuing notification/Ignoring Packet Queuing Notification	R97	All GPRS MS	C215	
42.1.2.1.1.3	Packet Uplink Assignment/Packet queuing notification/Assigned PDCHs	R97	All GPRS MS	C215	
42.1.2.1.1.4	Packet Uplink Assignment/Packet queuing notification/Expiry of timer T3162	R97	All GPRS MS	C215	
42.1.2.1.2	Packet Uplink Assignment/Response to packet polling request	R97	All GPRS MS	C215	
42.1.2.1.3.1	Packet Uplink Assignment/Packet access reject/Action during Wait_Indication	R97	All GPRS MS	C215	
42.1.2.1.3.2	Packet Uplink Assignment/Packet access reject/No respond	R97	All GPRS MS	C215	
42.1.2.1.3.3	Void				
42.1.2.1.4	Packet Uplink Assignment/Packet Uplink Assignment handling	R97	All GPRS MS	C215	
42.1.2.1.5	Packet Uplink Assignment/One or two phase access	R97	All GPRS MS	C215	
42.1.2.1.6	Packet Uplink Assignment/Decoding of frequency parameters	R97	All GPRS MS	C215	
42.1.2.1.7	Packet Uplink Assignment/Most recently received Packet Uplink Assignment	R97	All GPRS MS	C215	
42.1.2.1.8.1 .1	Packet Uplink Assignment/One phase access/Contention resolution/Inclusion of TLLI in RLC data blocks	R97	All GPRS MS	C215	
42.1.2.1.8.1 .2	Packet Uplink Assignment/One phase access/Contention resolution/Counter N3104	R97	All GPRS MS	C215	
42.1.2.1.8.1 .3	Packet Uplink Assignment/One phase access/Contention resolution/Timer T3166	R97	All GPRS MS	C215	
42.1.2.1.8.1 .4	Packet Uplink Assignment/One phase access/Contention resolution/TLLI mismatch	R97	All GPRS MS	C215	
42.1.2.1.8.1 .5	Packet Uplink Assignment/One phase access/Contention resolution/3 or 4 access repetition attempts	R97	All GPRS MS	C215	
42.1.2.1.8.1 .6	Packet Uplink Assignment / One phase access / Contention resolution / Retransmission / Inclusion of TLLI in RLC data blocks after completion	R97	All GPRS MS	C215	
42.1.2.1.8.2 .1	Packet Uplink Assignment/One phase access/Timing Advance/TA Index present	R97	All GPRS MS	C215	
42.1.2.1.8.2 .2	Packet Uplink Assignment/One phase access/Timing Advance/TA Index not present	R98	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.1.2.1.9.1	Packet Uplink Assignment/Two phase access/Packet Resource Request/RLC Octet Count	R97	All GPRS MS	C215	
42.1.2.1.9.2.1	Packet Uplink Assignment/Two phase access/Contention resolution/Expiry of timer T3168	R97	All GPRS MS	C215	
42.1.2.1.9.2.2	Packet Uplink Assignment/Two phase access/Contention resolution/TLLI mismatch	R97	All GPRS MS	C215	
42.1.2.1.9.3	Packet Uplink Assignment/Two phase access/Packet Resource Request/No respond to Packet Downlink Assignment	R99	All GPRS MS	C215	
42.1.2.1.10.1	Packet Uplink Assignment/Abnormal cases/Incorrect PDCH assignment	R97	All GPRS MS	C215	
42.1.2.1.10.2	Packet Uplink Assignment/Abnormal cases/Expiry of timer T3164	R97	All GPRS MS	C215	
42.1.2.1.11	Non DRX mode on PCCCH	R97	All GPRS MS	C19	
42.1.2.1.12	Variable PBCCH and PSI scheduling	R97	All GPRS MS	C215	
42.1.2.1.13	Several PCCCHs supported by the cell	R97	All GPRS MS	C215	
42.1.2.1.14	Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 0	R97	All GPRS MS	C215	
42.1.2.1.15	Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 3	R97	All GPRS MS	C215	
42.1.2.1.16	Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 7	R97	All GPRS MS	C215	
42.1.2.1.17	Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 4	R97	All GPRS MS	C215	
42.1.2.1.18	Several Hopping PCCCHs and non-Hopping PCCCHs supported by the cell	R97	All GPRS MS	C215	
42.1.2.2.1	Packet Downlink Assignment/Response to poll bit	R97	All GPRS MS	C215	
42.1.2.2.2	Packet Downlink Assignment/PCCCH monitoring	R97	All GPRS MS	C215	
42.1.2.2.3	Packet Downlink Assignment/Frequency hopping	R97	All GPRS MS	C215	
42.1.2.2.4	Packet Downlink Assignment/Response to Packet Polling	R97	All GPRS MS	C215	
42.1.2.2.5.1	Packet Downlink Assignment/Abnormal cases/Incorrect PDCH assignment	R97	All GPRS MS	C215	
42.1.2.2.5.2	Packet Downlink Assignment/Abnormal cases/Expiry of timer T3190	R97	All GPRS MS	C215	
42.1.2.2.6	Packet Downlink Assignment Timing Advance/TA value field not provided	R97	All GPRS MS	C215	
42.2.1.1	One phase access	R97 and R98 only	All GPRS MS	C215	
42.2.1.2	Two phase access	R97 and R98 only	All GPRS MS	C215	
42.2.2.1.1	Fixed Allocation/Uplink Transfer/Normal operation/Blocks	R97 and R98 only	All GPRS MS	C215	
42.2.2.1.2-p1	Fixed Allocation/Uplink Transfer/Normal operation/Block Periods	R97 and R98 only	Procedure 1: All GPRS MS	C215	
42.2.2.1.2-p2	Fixed Allocation/Uplink Transfer/Normal operation/Block Periods	R97 and R98 only	Procedure 2: GPRS MS not operating in multislot classes 1,2,4 or 8	C227	

Clause	Title	Release	Applicability	Status	Supported
42.2.2.2	Fixed Allocation/Uplink Transfer/Operation with TS_OVERRIDE for single-slot TX	R97 and R98 only	All GPRS MS	C215	
42.2.2.3	Fixed Allocation/Uplink Transfer/Operation with TS_OVERRIDE for multi-slot TX	R97 and R98 only	GPRS MS not operating in multislot classes 1,2,4 or 8	C227	
42.2.2.4	Fixed Allocation/Uplink Transfer/T3184 Expiry	R97 and R98 only	All GPRS MS	C282	
42.2.2.5.1	Fixed Allocation/Uplink Transfer/T3188/Expiry	R97 and R98 only	All GPRS MS	C215	
42.2.2.5.2	Fixed Allocation/Uplink Transfer/T3188/Stop with Packet Uplink Assignment	R97 and R98 only	All GPRS MS	C215	
42.2.2.5.3	Fixed Allocation/Uplink Transfer/T3188/Stop with Packet Uplink Ack/Nack with REPEAT_ALLOCATION	R97 and R98 only	All GPRS MS	C215	
42.2.2.6.1	Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Expiry	R97 and R98 only	All GPRS MS	C215	
42.2.2.6.2	Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Uplink Assignment	R97 and R98 only	All GPRS MS	C215	
42.2.2.6.3	Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Uplink Ack/Nack with REPEAT_ALLOCATION	R97 and R98 only	All GPRS MS	C215	
42.2.2.6.4	Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Access Reject	R97 and R98 only	All GPRS MS	C215	
42.2.2.6.5	Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Continue with Packet Uplink Ack/Nack without REPEAT_ALLOCATION and without ALLOCATION_BITMAP	R97 and R98 only	All GPRS MS	C215	
42.2.2.7.1	Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Packet Uplink Assignment with ALLOCATION_BITMAP	R97 and R98 only	All GPRS MS	C215	
42.2.2.7.2	Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/Multiple Packet Uplink Assignments	R97 and R98 only	All GPRS MS	C215	
42.2.2.7.3	Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Packet Uplink Ack/Nack with ALLOCATION_BITMAP	R97 and R98 only	All GPRS MS	C215	
42.2.2.7.4	Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/Multiple Packet Uplink Ack/Nack with ALLOCATION_BITMAP	R97 and R98 only	All GPRS MS	C215	
42.2.2.7.5	Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/Multiple Packet Uplink Ack/Nack with REPEAT_ALLOCATION	R97 and R98 only	All GPRS MS	C215	
42.2.2.8.1	Fixed Allocation/Uplink Transfer/MS requests new resources/ Failure/ Packet Access Reject	R97 and R98 only	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.2.2.8.2	Fixed Allocation/Uplink Transfer/MS requests new resources/ Failure/Packet Access Reject with WAIT_INDICATION during allocation in progress	R97 and R98 only	All GPRS MS	C215	
42.2.2.9	Fixed Allocation/Uplink Transfer/Network initiates new resources	R97 and R98 only	All GPRS MS	C215	
42.2.2.10.1	Fixed Allocation/Uplink Transfer/PACCH operation/ Normal Operation	R97 and R98 only	GPRS MS supporting multislot class 3 and above	C228	
42.2.2.10.2	Fixed Allocation/Uplink Transfer/PACCH operation/ PACCH message addressed to another MS	R97 and R98 only	GPRS MS supporting multislot class 3 and above	C228	
42.2.2.10.3	Fixed Allocation/ Uplink Transfer/Abnormal cases/PACCH timeslot removed	R97 and R98 only	GPRS MS supporting multislot class 3 and above	C228	
42.2.2.11.1	Fixed Allocation/ Uplink Transfer/Abnormal cases/Assignment without fixed allocation	R97 and R98 only	All GPRS MS	C215	
42.2.2.11.2	Fixed Allocation/ Uplink Transfer/Abnormal cases/Frequency not supported	R97 and R98 only	All GPRS MS	C215	
42.2.2.11.3	Fixed Allocation/ Uplink Transfer/Abnormal cases/Invalid MA_NUMBER	R97 and R98 only	All GPRS MS	C215	
42.2.3.1.1	Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ T3190/Half-Duplex	R97 and R98 only	GPRS MS supporting multislot class 19 and 24.	C229	
42.2.3.1.2	Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ T3190/Non Half-Duplex	R97 and R98 only	GPRS MS supporting multislot class 10 and above	C230	
42.2.3.2.1	Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ Ending uplink TBF/ Half-Duplex	R97 and R98 only	GPRS MS supporting multislot class 19 and 24	C229	
42.2.3.2.2	Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ Ending uplink TBF/ Non Half-Duplex	R97 and R98 only	GPRS MS supporting multislot class 10 and above	C230	
42.2.3.3.1	Fixed Allocation/ Uplink Transfer with Downlink TBF Establishment/ Abnormal cases/Violation of multi-slot capabilities	R97 and R98 only	All GPRS MS	C215	
42.2.3.3.2	Fixed Allocation/ Uplink Transfer with Downlink TBF Establishment/ Abnormal cases/No defined PDCH	R97 and R98 only	GPRS MS supporting multislot class 2	C231	
42.2.4.2.1	Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Uplink Assignment/ Non half-duplex	R97 and R98 only	All GPRS MS	C215	
42.2.4.2.2	Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Uplink Assignment/ Half-duplex	R97 and R98 only	GPRS MS supporting multislot classes 19-29	C232	
42.2.4.3.1	Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Timeslot Reconfigure/Starting time with AFN encoding	R97 and R98 only	All GPRS MS	C215	
42.2.4.3.2	Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Timeslot Reconfigure/Starting time with relative encoding	R97 and R98 only	All GPRS MS	C215	
42.3.1.1.1	Dynamic Allocation/Uplink Transfer/Normal/Successful	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.3.1.1.2	Dynamic Allocation/Uplink Transfer/Normal/Request new resources	R97	All GPRS MS	C215	
42.3.1.1.3	Dynamic Allocation/Uplink Transfer/Normal/Starting frame number encoding	R97	All GPRS MS	C215	
42.3.1.1.4	Dynamic Allocation/Uplink Transfer/Normal/Starting time	R97	All GPRS MS	C215	
42.3.1.1.5	Void				
42.3.1.1.6	Dynamic Allocation/Uplink Transfer/Normal/T3180 expiry	R97	All GPRS MS	C215	
42.3.1.1.7	Dynamic Allocation/Uplink Transfer/Normal/PACCH operation	R97	All GPRS MS	C215	
42.3.1.1.8	Dynamic Allocation/Uplink Transfer/Normal/Two uplink timeslots	R97	All GPRS MS supporting Multislot classes: 5,6,7,9,...., 29)	C325	
42.3.1.1.9	Dynamic Allocation/Uplink Transfer/Normal/Frequency parameters	R97	All GPRS MS	C215	
42.3.1.2.2	Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in acknowledged mode	R97	All GPRS MS	C215	
42.3.1.2.3	Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in unacknowledged mode	R97	All GPRS MS	C215	
42.3.2.1.1	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Successful	R97	All GPRS MS	C215	
42.3.2.1.2	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Multislot capabilities	R97	All GPRS MS supporting Multislot classes: 2,3,4,5,6,8,9,10,19,24)	C234	
42.3.2.2.1	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/with random access	R97	All GPRS MS	C215	
42.3.2.2.2	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/Continuation of normal operation	R97	All GPRS MS	C215	
42.3.3.1.1	Dynamic Allocation/Resource reallocation/Successful/Higher throughput class or higher radio priority	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	
42.3.3.1.2	Dynamic Allocation/Resource reallocation/Successful/Lower throughput class	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	
42.3.3.1.3	Dynamic Allocation/Resource reallocation/Successful/Different RLC mode and higher radio priority	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	
42.3.3.2.1	Dynamic Allocation/Resource reallocation/Abnormal/T3168 expiry	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	
42.3.3.2.2	Dynamic Allocation/Resource reallocation/Abnormal/Invalid assignment	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	
42.3.3.3	Dynamic Allocation/Resource reallocation/Reject	R97	GPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C235	

Clause	Title	Release	Applicability	Status	Supported
42.3.3.4	Dynamic Allocation / Resource reallocation / Successful / Lower Coding Scheme Command	R97	All GPRS MS	C215	
42.4.1.1	Network Control measurement reporting/Uplink/Normal case	R97	All GPRS MS	C215	
42.4.1.2	Network Control measurement reporting/Idle mode/New cell reselection	R97	All GPRS MS	C215	
42.4.1.3	Network Control measurement reporting/Downlink transfer/ Normal case	R97	All GPRS MS	C215	
42.4.1.4	Network Control measurement reporting / Uplink transfer / Continuation in Idle mode	R97	All GPRS MS	C215	
42.4.1.5	Network Control measurement reporting / Idle mode / DSC failure/ reselection	R97	All GPRS MS	C215	
42.4.2.1.1	Cell change order procedure/Uplink transfer/Normal case	R97	All GPRS MS	C215	
42.4.2.1.2	Void				
42.4.2.1.3	Cell change order procedure/Uplink transfer/Failure cases/REJECT from the new cell	R97	All GPRS MS	C215	
42.4.2.1.4	Cell change order procedure/Uplink transfer/Failure cases/Contention resolution failure	R97	All GPRS MS	C215	
42.4.2.1.5	Void				
42.4.2.1.6	Cell change order procedure/Uplink transfer/Failure cases/Frequency not implemented	R97	All GPRS MS	C215	
42.4.2.2.1	Cell change order procedure/Downlink transfer/Normal case	R97	All GPRS MS	C215	
42.4.2.2.2	Cell change order procedure/Downlink transfer/Failure cases/REJECT from the new cell	R97	All GPRS MS	C215	
42.4.2.2.3	Cell change order procedure/Downlink transfer/Failure cases/Frequency not implemented	R97	All GPRS MS	C215	
42.4.2.3.1	Cell change order procedure/Simultaneous uplink and downlink transfer/Normal case	R97	All GPRS MS	C215	
42.4.2.3.2	Void				
42.4.2.3.3	Packet Measurement order procedure / Downlink transfer / Normal case/ Dedicated parameters	R97	All GPRS MS	C215	
42.4.2.3.4	Packet Measurement order procedure / Downlink transfer / Normal case/ Routing Area Update/ NMO II	R97	All GPRS MS	C215	
42.4.2.3.5	Packet Measurement order procedure / Downlink transfer / Normal case/ Routing Area Update/ NMO I	R97	All GPRS MS	C215	
42.4.2.3.6	MT CS establishment whilst in NC2 with a downlink TBF established	R97	All GPRS MS	C215	
42.4.2.3.7	MT CS establishment whilst in NC2 with a uplink TBF established	R97	All GPRS MS	C215	
42.4.3.1.1	Uplink packet transfer mode/Dynamic allocation	R97	All GPRS MS	C215	
42.4.4.1	Cell Change Order Procedures without PBCCH /Network Controlled Cell Reselection – Packet Measurement Order Procedure	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.4.4.2	Cell Change Order Procedures without PBCCH /Network Controlled Cell Reselection/validity of reselection parameters/MS enters standby state	R97	All GPRS MS	C215	
42.4.4.3	Network Control measurement reporting / Idle mode / Returning to Broadcast parameters	R97	All GPRS MS	C215	
42.4.4.4	Network Control measurement reporting / Idle mode / Reselection due to RA failure	R99	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.4.5.1	Network Assisted Cell Change / Expiry of T3206	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.2	Network Assisted Cell Change / No Packet Neighbouring Cell Data and Packet Cell Change Continue	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.3	Network Assisted Cell Change / Packet Neighbour Cell Data and Packet Cell Change Continue	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.4	Network Assisted Cell Change / Packet Neighbour Cell Data and Packet Cell Change Order	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.5	Network Assisted Cell Change / Expiry of T3208 and T3210	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.6	Network Assisted Cell Change / Entering packet idle mode	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.7	Network Assisted Cell Change / CCN not supported towards target cell	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.8	Network Assisted Cell Change / NC mode change	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.5.9	Network Assisted Cell Change / NC mode change / Packet Neighbour Cell Data	Rel-4	All GPRS MS's supporting Network Assisted Cell Change	C322	
42.4.6.1	Network Control PEMR– Activation with SI Messages	R99	All GPRS MS	C215	
42.4.6.2	Network Control PEMR - Activation with PSI messages	R99	All GPRS MS	C215	
42.4.6.3	Network Control PEMR– Packet Measurement Order	R99	All GPRS MS	C215	
42.4.6.4	Network Control PEMR– Uplink Data Transfer	R99	All GPRS MS	C215	
42.4.6.5	Network Control PEMR– Downlink Data Transfer	R99	All GPRS MS	C215	
42.4.7.1	Inter-RAT Cell Change Order (Known Cell) – Uplink Data Transfer	R99	MS supporting both GPRS and UTRAN	C324	
42.4.7.2	Inter-RAT Cell Change Order (Unknown Cell) – Uplink Data Transfer	R99	MS supporting both GPRS and UTRAN	C324	
42.4.7.3	Inter-RAT Cell Change Order (Unknown Cell) – Downlink Data Transfer	R99	MS supporting both GPRS and UTRAN	C324	
42.4.7.4	Inter-RAT Cell Change Order (Unknown Cell) – Simultaneous uplink and downlink transfer	R99	MS supporting both GPRS and UTRAN	C324	
42.4.8.1.1	NC2 and DRX / NC_NON_DRX_PERIOD / Respect of NC2 non-DRX mode period	R97	All GPRS MS	C215	
42.4.8.1.2	NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period ordered in Packet Cell Change Order	R97	All GPRS MS	C215	
42.4.8.1.3	NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period broadcast in PSI5	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.4.8.1.4	NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period broadcast in SI2Quater	R99	All GPRS MS	C215	
42.4.8.1.5	NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period / PBCCH present / Default Value	R97	All GPRS MS	C215	
42.4.8.1.6	NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period / PBCCH absent / Default Value	R99	All GPRS MS	C215	
42.4.8.2.1	User Data Vs Measurement Report Sending / Conflict situation / DL TBF Establishment and Packet Access for Measurement Report Sending	R97	All GPRS MS	C215	
42.4.8.2.2	User Data vs Measurement Report Sending / Conflict situation / Expiry of T3192 and T3158	R97	All GPRS MS	C215	
42.4.8.2.3	User Data vs Measurement Report Sending / Conflict situation / Expiry of T3182 and T3158	R97	All GPRS MS	C215	
42.4.8.2.4	User Data vs Measurement Report Sending / Conflict situation / Random Access procedure for PMR sending and User Data transmission	R99	All GPRS MS	C215	
42.5.1.1	Downlink Transfer/ Normal Operation/Relative Encoding TBF starting time	R97	All GPRS MS	C215	
42.5.1.2	Downlink Transfer/ Normal Operation/Without TBF starting time	R97	All GPRS MS	C215	
42.5.2.1	Downlink Transfer/ Polling/ Normal operation/RLC data block	R97	All GPRS MS	C215	
42.5.2.2	Downlink Transfer/ Polling/ Packet Polling Request/ Access Burst format	R97	All GPRS MS	C215	
42.5.2.3	Downlink Transfer/ Polling/ Packet Polling Request/ Control block format	R97	All GPRS MS	C215	
42.5.3.1	Downlink Transfer/ T3190 Expiry/Initial allocation/Restart with valid RLC data block	R97	All GPRS MS	C215	
42.5.4.1	Downlink Transfer/ T3190 Expiry/Resource reallocation/Without TBF starting time	R97	All GPRS MS	C215	
42.5.4.2	Downlink Transfer/ T3190 Expiry/Resource reallocation/With TBF starting time	R97	All GPRS MS	C215	
42.5.4.3	Downlink Transfer/ T3190 Expiry/Resource reallocation/Restart with valid RLC data block	R97	All GPRS MS	C215	
42.5.5.1	Downlink Transfer/ Reestablishment/ T3192 Expiry	R97	All GPRS MS	C215	
42.5.5.2	Downlink Transfer/ Reestablishment/ Packet Downlink Assignment	R97	All GPRS MS	C215	
42.5.5.3	Downlink Transfer/ Reestablishment/ Invalid Frequency Parameters IE	R97	All GPRS MS	C215	
42.6.1	Exclusive allocation in single-slot configuration	R99	All DTM capable MS	C305	
42.7.1	Packet Assignment / TA Value/TA present in second Packet downlink assignment	R97	All GPRS MS	C215	
42.7.2	Packet Assignment / TA Value/TA not present in Packet uplink assignment sent in the downlink TBF	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
42.7.3	Packet Assignment / TA Value/ PACKET POWER CONTROL/TIMING ADVANCE during contention resolution	R97	All GPRS MS	C215	
42.7.4	Packet Assignment / TA Value/TAI present/ multislot Applicability	R97	All GPRS MS supporting Multislot classes: 5,6,7,9,...., 29	C325	
42.7.5	Packet Assignment / TA Value/ Update of TA using PACKET POWER CONTROL/TIMING ADVANCE	R97	All GPRS MS	C215	
42.7.6	Packet Uplink Assignment / One phase access / Timing Advance / TA Index present	R97	All GPRS MS	C215	
42.7.7	Packet Uplink Assignment / One phase access / Timing Advance / TA value field not provided	R97	All GPRS MS	C215	
42.8.1	Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Expiry	R97	All GPRS MS	C215	
42.8.2	Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Stop with Packet Uplink Assignment	R97	All GPRS MS	C215	
42.8.3	Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Packet Access Reject/ With WAIT_INDICATION	R97	All GPRS MS	C215	
42.8.4	Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Packet Access Reject/No WAIT_INDICATION	R97	All GPRS MS	C215	
42.8.5	Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/T3168/ Packet Access Reject/With Polling	R97	All GPRS MS	C215	
43.1.1.1	Acknowledged mode/Uplink TBF/Send state variable V(S)	R97	All GPRS MS	C215	
43.1.1.2	Acknowledged mode/Uplink TBF/Transmit window size	R97	All GPRS MS	C215	
43.1.1.3	Acknowledged mode/Uplink TBF/Acknowledge state variable V(A)	R97	All GPRS MS	C215	
43.1.1.4	Acknowledged mode/Uplink TBF/Negatively acknowledged RLC data blocks	R97	All GPRS MS	C215	
43.1.1.5	Acknowledged mode/Uplink TBF/Invalid Negative Acknowledgement	R97	All GPRS MS	C215	
43.1.1.6	Acknowledged mode/Uplink TBF/Decoding of Received Block Bitmap	R97	All GPRS MS	C215	
43.1.2.1	Acknowledged mode/Downlink TBF/Receive state variable V(R)	R97	All GPRS MS	C215	
43.1.2.2	Acknowledged mode/Downlink TBF/Receive window state variable V(Q)	R97	All GPRS MS	C215	
43.1.2.3	Acknowledged mode/Downlink TBF/Re-assembly of RLC data blocks	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
43.1.2.4	Acknowledged mode/Downlink TBF/Re-assembly/Length Indicator	R97	All GPRS MS	C215	
43.2.1	Control Blocks Re-assembly	R97	All GPRS MS	C215	
44.2.1.1.1	GPRS attach/accepted	R97	All GPRS MS	C215	
44.2.1.1.2	GPRS attach/rejected/IMSI invalid/illegal MS	R97	All GPRS MS	C215	
44.2.1.1.3	GPRS attach/rejected/IMSI invalid/GPRS services not allowed	R97	All GPRS MS	C215	
44.2.1.1.4	GPRS attach/rejected/PLMN not allowed	R97	All GPRS MS	C215	
44.2.1.1.5	GPRS attach/rejected/roaming not allowed in this location area	R97	All GPRS MS	C215	
44.2.1.1.6	GPRS attach/abnormal cases/access barred due to access class control	R97	All GPRS MS	C215	
44.2.1.1.7	GPRS attach/abnormal cases/change of cell into new routing area	R97	All GPRS MS	C215	
44.2.1.1.8	GPRS attach/abnormal cases/power off	R97	GPRS MS that supports On/Off switch	C317	
44.2.1.1.9	GPRS attach/abnormal cases/GPRS detach procedure collision	R97	All GPRS MS	C215	
44.2.1.1.10	GPRS attach / rejected / GPRS services not allowed in this PLMN	R97	All GPRS MS	C215	
44.2.1.2.1	Combined GPRS attach/GPRS and non-GPRS attach accepted	R97	All GPRS MS	C215	
44.2.1.2.2	Combined GPRS attach/GPRS only attach accepted	R97	All GPRS MS	C215	
44.2.1.2.3	Combined GPRS attach/GPRS attach while IMSI attach	R97	GPRS MS which do not auto GPRS attach on power up or switch on	C236	
44.2.1.2.4	Combined GPRS attach/rejected/IMSI invalid/illegal ME	R97	All GPRS MS	C215	
44.2.1.2.5	Combined GPRS attach/rejected/GPRS services and non-GPRS services not allowed	R97	All GPRS MS	C215	
44.2.1.2.6	Combined GPRS attach/rejected/GPRS services not allowed	R97	All GPRS MS	C215	
44.2.1.2.7	Combined GPRS attach/rejected/location area not allowed	R97	All GPRS MS	C215	
44.2.1.2.8	Combined GPRS attach/abnormal cases/attempt counter check/miscellaneous reject causes	R97	All GPRS MS	C215	
44.2.1.2.9	Combined GPRS attach/abnormal cases/GPRS detach procedure collision	R97	All GPRS MS	C215	
44.2.2.1.1	GPRS detach/power off/accepted	R97	All GPRS MS	C215	
44.2.2.1.2	GPRS detach/accepted	R97	All GPRS MS	C215	
44.2.2.1.3	GPRS detach/abnormal cases/attempt counter check/procedure timeout	R97	All GPRS MS	C215	
44.2.2.1.4	GPRS detach/abnormal cases/GMM common procedure collision	R97	All GPRS MS	C215	
44.2.2.1.5	GPRS detach/power off/accepted	R97	All GPRS MS	C215	
44.2.2.1.6	GPRS detach/accepted/GPRS/IMSI detach	R97	All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off.	C274	
44.2.2.1.7	GPRS detach/accepted/IMSI detach	R97	All GPRS MS supporting user requested non-GPRS detach.	C275	

Clause	Title	Release	Applicability	Status	Supported
44.2.2.1.8	GPRS detach/abnormal cases/change of cell into new routing area	R97	All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off.	C274	
44.2.2.1.9	GPRS detach/abnormal cases/GPRS detach procedure collision	R97	All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off.	C274	
44.2.2.2.1	GPRS detach/re-attach not required/accepted	R97	All GPRS MS	C215	
44.2.2.2.2	GPRS detach/rejected/IMSI invalid/GPRS services not allowed	R97	All GPRS MS	C215	
44.2.2.2.3	GPRS detach/IMSI detach/accepted	R97	All GPRS MS	C215	
44.2.2.2.4	GPRS detach/re-attach requested/accepted	R97	All GPRS MS	C215	
44.2.2.2.5	GPRS detach/rejected/location area not allowed	R97	All GPRS MS	C215	
44.2.2.2.6	GPRS detach / rejected / GPRS services not allowed in this PLMN	R97	All GPRS MS	C215	
44.2.3.1.1	Routing area updating/accepted	R97	All GPRS MS	C215	
44.2.3.1.1a	Routing area updating/accepted / old P-TMSI	R97	All GPRS MS	C215	
44.2.3.1.2	Routing area updating/rejected/IMSI invalid/illegal ME	R97	All GPRS MS	C215	
44.2.3.1.3	Routing area updating/rejected/MS identity cannot be derived by the network	R97	All GPRS MS	C215	
44.2.3.1.4	Routing area updating/rejected/location area not allowed	R97	All GPRS MS	C215	
44.2.3.1.5	Routing area updating/abnormal cases/attempt counter check/miscellaneous reject causes	R97	All GPRS MS	C215	
44.2.3.1.6	Routing area updating/abnormal cases/change of cell into new routing area	R97	All GPRS MS	C215	
44.2.3.1.7	Routing area updating/abnormal cases/change of cell during routing area updating procedure	R97	All GPRS MS	C215	
44.2.3.1.8	Routing area updating/abnormal cases/P-TMSI reallocation procedure collision	R97	All GPRS MS	C215	
44.2.3.2.1	Combined routing area updating/combined RA/LA accepted	R97	All GPRS MS	C215	
44.2.3.2.2	Combined routing area updating/MS in CS operation at change of RA	R97	All GPRS MS supporting CS operation	C210	
44.2.3.2.3-p1	Combined routing area updating/RA only accepted	R97	All GPRS MS	C215	
44.2.3.2.3-p2	Combined routing area updating/RA only accepted	R97	All GPRS MS	C215	
44.2.3.2.4	Combined routing area updating/rejected/PLMN not allowed	R97	All GPRS MS	C215	
44.2.3.2.5	Combined routing area updating/rejected/roaming not allowed in this location area	R97	All GPRS MS	C215	
44.2.3.2.6	Combined routing area updating/abnormal cases/access barred due to access class control	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
44.2.3.2.7	Combined routing area updating/abnormal cases/attempt counter check/procedure timeout	R97	All GPRS MS	C215	
44.2.3.2.8	Combined routing area updating/abnormal cases/change of cell into new routing area	R97	All GPRS MS	C215	
44.2.3.2.9	Combined routing area updating/abnormal cases/change of cell during routing area updating procedure	R97	All GPRS MS	C215	
44.2.3.2.10	Combined routing area updating/abnormal cases/GPRS detach procedure collision	R97	All GPRS MS	C215	
44.2.3.3.1	Periodic routing area updating/accepted	R97	All GPRS MS	C215	
44.2.3.3.2	Periodic routing area updating/accepted/T3312 default value	R97	All GPRS MS	C215	
44.2.3.3.3	Periodic routing area updating/no cell available/network mode I	R97	All GPRS MS	C215	
44.2.3.3.4	Periodic routing area updating/no cell available	R97	All GPRS MS	C215	
44.2.4	P-TMSI reallocation	R97	All GPRS MS	C215	
44.2.5.1.1	Authentication accepted	R97	All GPRS MS	C215	
44.2.5.1.2	Authentication rejected	R97	All GPRS MS	C215	
44.2.5.2.1	Ciphering mode/start ciphering	R97	All GPRS MS	C215	
44.2.5.2.2	Ciphering mode/stop ciphering	R97	All GPRS MS	C215	
44.2.5.2.3	Ciphering mode/IMEISV request	R97	All GPRS MS	C215	
44.2.6.1	General Identification	R97	All GPRS MS	C215	
44.2.7	GMM READY timer handling	R97	All GPRS MS	C215	
44.2.8.1.1	Change of cell between two LAs in idle mode / RAU completes first	R99	All DTM capable MS	C305	
44.2.8.1.2	Change of cell between two LAs in idle mode / LAU completes first / SS releases channel	R99	All DTM capable MS	C305	
44.2.8.1.3	Change of cell between two LAs in idle mode / LAU completes first / SS maintains channel	R99	All DTM capable MS	C305	
44.2.8.2	Change of routing area whilst in dedicated mode	R99	All DTM capable MS	C305	
45.2.1.1	Attach initiated by context activation/QoS Offered by Network is the QoS Requested	R97	All GPRS MS	C215	
45.2.1.2.1	QoS Accepted by MS	R97	All GPRS MS supporting user settings of minimum QoS	C248	
45.2.1.2.2	QoS Rejected by MS	R97	All GPRS MS supporting user settings of minimum QoS	C248	
45.2.2-c1	PDP context activation requested by the network, successful and unsuccessful	R97	All GPRS MS	C225	
45.2.2-c2	PDP context activation requested by the network, successful and unsuccessful	R97	All GPRS MS not supporting Network requested PDP context activation	C237	
45.2.4.1	T3380 Expiry	R97	All GPRS MS	C215	
45.2.4.2-c1	Collision of MS initiated and network requested PDP context activation	R97	All GPRS MS	C225	
45.2.4.2-c2	Collision of MS initiated and network requested PDP context activation	R97	All GPRS MS not supporting Network requested PDP context activation	C237	

Clause	Title	Release	Applicability	Status	Supported
45.2.4.3	Network initiated PDP context activation request for an already activated PDP context (on the MS side)	R99	GPRS MS supporting two or more PDP contexts	C224	
45.2.5.1.1	QoS Offered by Network is the QoS Requested	R99	GPRS MS supporting two or more PDP contexts	C224	
45.2.5.1.2.1	QoS accepted by MS	R99	GPRS MS supporting two or more PDP contexts	C224	
45.2.5.1.2.2	QoS rejected by MS	R99	GPRS MS supporting two or more PDP contexts	C224	
45.2.5.2	Unsuccessful Secondary PDP Context Activation Procedure Initiated by the MS	R99	GPRS MS supporting two or more PDP contexts	C224	
45.2.5.3.1	T3380 Expiry	R99	GPRS MS supporting two or more PDP contexts	C224	
45.3.1	Network PDP context modification	R97	All GPRS MS supporting user settings of minimum QoS	C248	
45.3.2.1	MS initiated PDP Context Modification accepted by network	R99	All GPRS MS	C215	
45.3.2.2	MS initiated PDP Context Modification not accepted by the network	R99	All GPRS MS	C215	
45.3.3.1	T3381 Expiry	R99	All GPRS MS	C215	
45.3.3.2	Collision of MS and network initiated PDP context modification procedures	R99	All GPRS MS	C215	
45.4.1	PDP context deactivation initiated by the MS	R97	All GPRS MS	C215	
45.4.2	PDP context deactivation initiated by the network	R97	All GPRS MS	C215	
45.4.3.1	T3390 Expiry	R97	All GPRS MS	C215	
45.4.3.2	Collision of MS and network initiated PDP context deactivation requests	R97	All GPRS MS	C215	
45.4.4	PDP context deactivation initiated by the network / Tear down indicator	R99	GPRS MS supporting two or more PDP contexts	C224	
45.5.1	Error cases	R97	All GPRS MS	C215	
46.1.2.1.1	Data transmission in protected mode	R97	All GPRS MS	C215	
46.1.2.1.2	Data transmission in unprotected mode	R97	All GPRS MS	C215	
46.1.2.1.3	Reception of I frame in ADM	R97	All GPRS MS	C215	
46.1.2.2.1.1	Link establishment from MS to SS	R97	All GPRS MS	C215	
46.1.2.2.1.2	Link establishment from SS to MS	R97	All GPRS MS	C215	
46.1.2.2.1.3	Loss of UA frame	R97	All GPRS MS	C215	
46.1.2.2.1.4	Total loss of UA frame	R97	All GPRS MS	C215	
46.1.2.2.1.5	DM response	R97	All GPRS MS	C215	
46.1.2.2.2.1	Checking N(S)	R97	All GPRS MS	C215	
46.1.2.2.2.2	Busy condition at the peer, with RR sent for resumption of transmission	R97	All GPRS MS	C215	
46.1.2.2.2.3	Busy condition at the peer, with ACK sent for resumption of transmission	R97	All GPRS MS	C215	
46.1.2.2.2.4	SACK frame	R97	All GPRS MS	C215	
46.1.2.2.3.1	Checking N(R)	R97	All GPRS MS	C215	
46.1.2.2.3.2	MS handling busy condition during bi-directional data transfer	R97	All GPRS MS	C215	
46.1.2.2.3.3	SACK frame	R97	All GPRS MS	C215	
46.1.2.2.3.4	ACK frame	R97	All GPRS MS	C215	
46.1.2.2.4.1	Reestablishment due to reception of SABM	R97	All GPRS MS	C215	
46.1.2.2.4.2	Reestablishment due to N200 failures	R97	All GPRS MS	C215	
46.1.2.2.4.3	Reestablishment due to reception of DM	R97	All GPRS MS	C215	
46.1.2.3.1	Collision of SABM	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
46.1.2.3.2	Collision of SABM and DISC	R97	All GPRS MS	C215	
46.1.2.3.3	Collision of SABM and XID commands	R97	All GPRS MS	C215	
46.1.2.4.1	Unsolicited DM	R97	All GPRS MS	C215	
46.1.2.5.1	Sending FRMR due to undefined command control field	R97	All GPRS MS	C215	
46.1.2.5.2	Sending FRMR due to reception of an S frame with incorrect length	R97	All GPRS MS	C215	
46.1.2.5.3	Sending FRMR due to reception of an I frame information field exceeding the maximum length	R97	All GPRS MS	C215	
46.1.2.5.4	Frame reject condition during establishment of ABM	R97	All GPRS MS	C215	
46.1.2.6.1	Simultaneous acknowledged and unacknowledged data transfer on the same SAPI	R97	GPRS MS supporting two or more PDP contexts	C224	
46.1.2.6.2	Simultaneous acknowledged and unacknowledged data transfer on different SAPIs	R97	GPRS MS supporting two or more PDP contexts	C223	
46.1.2.7.1	Negotiation initiated by the SS during ABM, for T200 and N200	R97	All GPRS MS	C215	
46.1.2.7.2	Negotiation initiated by the SS during ADM, for N201-I	R97	GPRS MS supporting network initiated PDP context activation	C215	
46.1.2.7.3	Negotiation initiated by the SS (using SABM, for IOV-I)	R97	All GPRS MS	C215	
46.1.2.7.4	Negotiation initiated by the SS (during ADM, for N201-U)	R97	All GPRS MS	C215	
46.1.2.7.5	Negotiation initiated by the SS (during ADM, for IOV-UI)	R97	All GPRS MS	C215	
46.1.2.7.6	Negotiation initiated by the SS (during ABM, for Reset)	R97	GPRS MS supporting two or more PDP contexts	C223	
46.1.2.7.7	XID command with unrecognised type field	R97	All GPRS MS	C215	
46.1.2.7.8	XID Response with out of range values	R97	All GPRS MS	C215	
46.2.2.1.1	Mobile originated normal data transfer with LLC in acknowledged mode	R97	All GPRS MS	C215	
46.2.2.1.2	Mobile originated normal data transfer with LLC in unacknowledged mode	R97	All GPRS MS	C215	
46.2.2.1.3	Usage of acknowledged mode for data transmission before and after PDP Context modification, on different SAPIs	R97	All GPRS MS	C215	
46.2.2.1.4	Reset indication during unacknowledged mode	R97	All GPRS MS	C215	
46.2.2.1.5	Reset indication during acknowledged mode	R97	All GPRS MS	C215	
46.2.2.2.1	LLC link re-establishment on reception of SN-DATA PDU with F=0 in ack mode in the Receive First Segment state	R97	All GPRS MS	C215	
46.2.2.2.2	LLC link re-establishment on receiving second segment with F=1 and with different PCOMP and DCOMP values in the acknowledged mode data transfer	R97	All GPRS MS	C215	
46.2.2.2.3	Single segment N-PDU from MS	R97	All GPRS MS	C215	
46.2.2.3.1	LLC link release on receiving DM from the SS during acknowledged data transfer	R97	All GPRS MS	C215	
46.2.2.4.1	Response from MS on receiving XID request from the SS	R97	All GPRS MS	C215	

Clause	Title	Release	Applicability	Status	Supported
46.2.2.4.2	Response from MS on receiving an XID request from the SS with an unassigned entity number	R97	All GPRS MS	C215	
46.2.2.4.3	Response from MS on receiving an XID response from the SS with unrecognised type field	R97	All GPRS MS	C215	
46.2.2.5	LLC link release on receiving "Invalid XID response" from the network during link establishment procedure	R97	All GPRS MS	C215	
47.1.1	Intra frequency reallocation of CS resources / Assignment Cmd	R99	All DTM capable MS	C305	
47.1.2	Intra frequency reallocation of CS resources / Handover	R99	All DTM capable MS	C305	
47.1.3	Reallocation of CS resources / DTM Assignment Command / Intra frequency	R99	All DTM capable MS	C305	
47.1.4	Inter frequency reallocation of CS resources / DTM Assignment	R99	All DTM capable MS	C305	
47.2.1	Mobile Originating CS Release	R99	All DTM capable MS	C305	
47.2.2	Network Originating CS Release	R99	All DTM capable MS	C305	
47.3.1.1	Handover to same routing area whilst in dedicated mode & MM Ready / Completed on the main DCCH	R99	All DTM capable MS	C305	
47.3.1.2	Handover to same routing area whilst in DTM with DL TBF only	R99	All DTM capable MS	C305	
47.3.1.3.1	Handover to same routing area whilst in DTM with both DL & UL TBFs / Successful case	R99	All DTM capable MS	C305	
47.3.1.3.2	Handover to same routing area whilst in DTM with both DL & UL TBFs / Abnormal case / Handover Failure	R99	All DTM capable MS	C305	
47.3.2.1	Handover to different routing area whilst in DM / Performed on main DCCH / RAU complete before CS release	R99	All DTM capable MS	C305	
47.3.2.2	Handover to different routing area whilst in DM / Performed on main DCCH / CS release before RAU complete	R99	All DTM capable MS	C305	
47.3.3.1.1	Handover to different routing area whilst in DTM / Performed on TBFs / RAU complete before CS release	R99	All DTM capable MS	C305	
47.3.3.1.2	Handover to different routing area whilst in DTM / Performed on TBFs / CS release before RAU complete	R99	All DTM capable MS	C305	
47.3.4.1	Handover to UTRAN while in DTM / Downlink TBF	R99	MS supporting both UTRAN and DTM	C315	
47.3.4.2	Handover to UTRAN while in DTM / Uplink TBF	R99	MS supporting both UTRAN and DTM	C315	
47.4.1	PDP Context Activation / Performed on main DCCH and TBFs	R99	All DTM capable MS	C305	
51.1.1.1	RR/Paging/on PCCCH for EGPRS service/normal paging with P-TMSI successful	R99	All EGPRS MS	C216	
51.1.1.2	RR/Paging/on PCCCH for EGPRS service/normal paging with IMSI successful	R99	All EGPRS MS	C216	
51.1.1.3	RR/Paging/on PCCCH for EGPRS service/extended paging with P-TMSI successful	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
51.1.1.4	RR/Paging/on PCCCH for EGPRS service/paging reorganisation successful	R99	All EGPRS MS	C216	
51.1.2	RR/Paging/on PCCCH for circuit-switched services/paging successful	R99	All EGPRS MS	C216	
51.1.3	RR/Paging/on PCCCH/paging ignored	R99	All EGPRS MS	C216	
51.1.4.1	RR/Paging/on PACCH for circuit-switched services/ paging successful	R99	All EGPRS MS	C216	
51.1.4.2	RR/Paging/on PACCH for circuit-switched services/ paging ignored	R99	All EGPRS MS	C216	
51.1.5.1.1	RR/Paging/on CCCH for EGPRS service/normal paging with P-TMSI successful	R99	All EGPRS MS	C216	
51.1.5.1.2	RR/Paging/on CCCH for EGPRS service/normal paging with IMSI successful	R99	All EGPRS MS	C216	
51.1.5.1.3	RR/Paging/on CCCH for EGPRS service/normal paging with P-TMSI ignored	R99	All EGPRS MS	C216	
51.1.5.2.1	RR/Paging/on CCCH for EGPRS service/extended paging with P-TMSI successful	R99	All EGPRS MS	C216	
51.1.5.3	RR/Paging/on CCCH for EGPRS service/paging reorganisation	R99	All EGPRS MS	C216	
51.1.6	RR/Paging/Before T3172 expiry	R99	All EGPRS MS	C216	
51.2.1.1	Permission to access the network/priority classes	R99	All EGPRS MS	C216	
51.2.2.1	Initiation of the packet access procedure/establishment causes	R99	All EGPRS MS	C216	
51.2.2.2	Random references for two phase packet access	R99	All EGPRS MS	C216	
51.2.2.3	Random references for one phase packet access and for Access Type "signalling"	R99	All EGPRS MS	C216	
51.2.2.4	Initiation of the packet access procedure/timer T3146	R99	All EGPRS MS	C216	
51.2.2.5	Initiation of the packet access procedure/Request Reference	R99	All EGPRS MS	C216	
51.2.2.6	Two phase packet access / establishment cause	R99	All EGPRS MS	C216	
51.2.3.1	Two-message assignment/Successful case	R99	All EGPRS MS	C216	
51.2.3.2	Two-message assignment/Failure cases	R99	All EGPRS MS	C216	
51.2.3.3	Packet uplink assignment/Polling bit set	R99	All EGPRS MS	C216	
51.2.3.4	One phase packet access/Contention resolution/Successful case	R99	All EGPRS MS	C216	
51.2.3.5	One phase packet access/Contention resolution/TLLI mismatch	R99	All EGPRS MS	C216	
51.2.3.6	One phase packet access/Contention resolution/Counter N3104	R99	All EGPRS MS	C216	
51.2.3.7	One phase packet access/Contention resolution/Timer T3166	R99	All EGPRS MS	C216	
51.2.3.8	One phase packet access/Contention resolution/4 access repetition attempts	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
51.2.3.9	One phase packet access/TBF starting time	R99	All EGPRS MS	C216	
51.2.3.10	One phase packet access/Timing Advance Index present	R99	All EGPRS MS	C216	
51.2.3.11	One phase packet access/Timing Advance Index not present	R99	All EGPRS MS	C216	
51.2.4.1	Multiblock packet access/Package Resource Request	R99	All EGPRS MS	C216	
51.2.5.1	Packet access rejection/wait indication	R99	All EGPRS MS	C216	
51.2.5.2	Packet access rejection/assignment before T3142 expires	R99	All EGPRS MS	C216	
51.2.5.3	Packet access rejection / Interpretation of Extended RA i / Correct value of Extended RA i	R99	All EGPRS MS	C216	
51.2.5.4	Packet access rejection / Interpretation of Extended RA i / Extended RA i not included	R99	All EGPRS MS	C216	
51.2.6.1	Initiation of packet downlink assignment procedure/MS listens to correct CCCH block	R99	All EGPRS MS	C216	
51.2.6.2	Initiation of packet downlink assignment procedure/timer T3190	R99	All EGPRS MS	C216	
51.2.6.3	Initiation of packet downlink assignment procedure/TBF starting time	R99	All EGPRS MS	C216	
51.2.6.4	Initiation of packet downlink assignment procedure/incorrect TFI	R99	All EGPRS MS	C216	
51.2.7.1	Single block packet downlink assignment/TBF Starting Time	R99	All EGPRS MS	C216	
51.2.7.2	Single block packet downlink assignment/MS returns to packet idle mode	R99	All EGPRS MS	C216	
51.3.1.1	TBF Release/Uplink/Normal/MS initiated/Acknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.1.2	TBF Release/Uplink/Normal/MS initiated/Unacknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.1.3	TBF Release/Uplink/Normal/MS initiated/Channel coding change during countdown	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.2.1	TBF Release/Uplink/Normal/Network initiated/Acknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.2.2	TBF Release/Uplink/Normal/Network initiated/Unacknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.3	TBF Release/Uplink/Network initiated/Abnormal release	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.4.1	TBF Release/Downlink/Normal/Network initiated/Acknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.4.2	TBF Release/Downlink/Normal/Network initiated/Unacknowledged mode	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
51.3.5.2	PDCH Release/With TIMESLOTS_AVAILABLE	R99	All EGPRS MS supporting activation of at least one PDP context	C279	
52.1.1.1	Void				
52.1.1.2	Packet Channel Request/Support of EGPRS PACKET CHANNEL REQUEST	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
52.1.1.3	Packet Channel Request/Response to Packet Paging/Non-RR Connection Paging	R99	All EGPRS MS	C216	
52.1.1.4	Packet Channel Request/Response to Packet Paging/RR Connection Paging	R99	All EGPRS MS	C216	
52.1.1.5	EGPRS Packet Channel Request/Access type	R99	All EGPRS MS	C216	
52.1.1.6.1	Packet Channel Request/Access persistence control on PRACH/M+1 attempts	R99	All EGPRS MS	C216	
52.1.1.6.2	Packet Channel Request/Access persistence control on PRACH/Persistence level	R99	All EGPRS MS	C216	
52.1.1.6.3	Packet Channel Request/Access persistence control on PRACH/Successive Attempts	R99	All EGPRS MS	C216	
52.1.1.7	Packet Channel Request / EGPRS Packet Channel Request	R99	All EGPRS MS	C216	
52.1.2.1.1.1	Packet Uplink Assignment/Packet queuing notification/Stop sending Packet Channel Requests	R99	All EGPRS MS	C216	
52.1.2.1.1.2	Packet Uplink Assignment/Packet queuing notification/Ignoring Packet Queuing Notification	R99	All EGPRS MS	C216	
52.1.2.1.1.3	Packet Uplink Assignment/Packet queuing notification/Assigned PDCHs	R99	All EGPRS MS	C216	
52.1.2.1.1.4	Packet Uplink Assignment/Packet queuing notification/Expiry of timer T3162	R99	All EGPRS MS	C216	
52.1.2.1.2	Packet Uplink Assignment/Response to packet polling request	R99	All EGPRS MS	C216	
52.1.2.1.3.1	Packet Uplink Assignment/Packet access reject/Action during Wait_Indication	R99	All EGPRS MS	C216	
52.1.2.1.3.2	Packet Uplink Assignment/Packet access reject/No respond	R99	All EGPRS MS	C216	
52.1.2.1.3.3	Void				
52.1.2.1.4	Packet Uplink Assignment/Packet Uplink Assignment handling	R99	All EGPRS MS	C216	
52.1.2.1.5	Packet Uplink Assignment/One or two phase access	R99	All EGPRS MS	C216	
52.1.2.1.6	Packet Uplink Assignment/Decoding of frequency parameters	R99	All EGPRS MS	C216	
52.1.2.1.7	Packet Uplink Assignment/Most recently received Packet Uplink Assignment	R99	All EGPRS MS	C216	
52.1.2.1.8.1.1	Packet Uplink Assignment/One phase access/Contention resolution/Inclusion of TLLI in RLC data blocks	R99	All EGPRS MS	C216	
52.1.2.1.8.1.2	Packet Uplink Assignment/One phase access/Contention resolution/Counter N3104	R99	All EGPRS MS	C216	
52.1.2.1.8.1.3	Packet Uplink Assignment/One phase access/Contention resolution/Timer T3166	R99	All EGPRS MS	C216	
52.1.2.1.8.1.4	Packet Uplink Assignment/One phase access/Contention resolution/TLLI mismatch	R99	All EGPRS MS	C216	
52.1.2.1.8.1.5	Packet Uplink Assignment/One phase access/Contention resolution/3 or 4 access repetition attempts	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
52.1.2.1.8.1.6	Packet Uplink Assignment / One phase access / Contention resolution / Retransmission / Inclusion of TLLI in RLC data blocks after completion	R99	All EGPRS MS	C216	
52.1.2.1.8.1.7	Packet Uplink Assignment / One phase access / Contention resolution / MCS-7 to MCS-9 / Inclusion of TLLI in both RLC data blocks	R99	All EGPRS MS	C216	
52.1.2.1.8.1.8	Packet Uplink Assignment / One phase access / Contention resolution / TLLI in Packet Resource Request message retransmission	R99	All EGPRS MS	C216	
52.1.2.1.8.2.1	Packet Uplink Assignment/One phase access/Timing Advance/TA Index present	R99	All EGPRS MS	C216	
52.1.2.1.8.2.2	Packet Uplink Assignment/One phase access/Timing Advance/TA Index not present	R99	All EGPRS MS	C216	
52.1.2.1.9.1	Packet Uplink Assignment/Two phase access/Packet Resource Request/RLC Octet Count	R99	All EGPRS MS	C216	
52.1.2.1.9.2.1	Packet Uplink Assignment/Two phase access/Contention resolution/Expiry of timer T3168	R99	All EGPRS MS	C216	
52.1.2.1.9.2.2	Packet Uplink Assignment/Two phase access/Contention resolution/TLLI in Packet Resource Request message	R99	All EGPRS MS	C216	
52.1.2.1.9.2.3	Packet Uplink Assignment/Two phase access/Contention resolution/TLLI mismatch	R99	All EGPRS MS	C216	
52.1.2.1.9.3	Packet Uplink Assignment/Two phase access/Radio Access Capabilities	R99	All EGPRS MS	C216	
52.1.2.1.9.4	Packet Uplink Assignment/Two phase access/Radio Access Capabilities/ Frequency band not supported..	R99	All EGPRS MS	C216	
52.1.2.1.9.5	Packet Uplink Assignment/Two phase access/Packet Resource Request/No respond to Packet Downlink Assignment	R99	All EGPRS MS	C216	
52.1.2.1.10.1	Packet Uplink Assignment/Abnormal cases/Incorrect PDCH assignment	R99	All EGPRS MS	C216	
52.1.2.1.10.2	Packet Uplink Assignment/Abnormal cases/Expiry of timer T3164	R99	All EGPRS MS	C216	
52.1.2.2.1	Packet Downlink Assignment/Response to poll bit	R99	All EGPRS MS	C216	
52.1.2.2.2	Packet Downlink Assignment/PCCCH monitoring	R99	All EGPRS MS	C216	
52.1.2.2.4	Packet Downlink Assignment/Response to Packet Polling	R99	All EGPRS MS	C216	
52.1.2.2.5.1	Packet Downlink Assignment/Abnormal cases/Incorrect PDCH assignment	R99	All EGPRS MS	C216	
52.1.2.2.5.2	Packet Downlink Assignment/Abnormal cases/Expiry of timer T3190	R99	All EGPRS MS	C216	
52.1.2.2.6	Packet Downlink Timing Advance / TA value field not provided	R99	All EGPRS MS	C216	
52.3.1.1.1	Dynamic Allocation/Uplink Transfer/Normal/Successful	R99	All EGPRS MS	C216	
52.3.1.1.2	Dynamic Allocation/Uplink Transfer/Normal/Request new resources	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
52.3.1.1.3	Dynamic Allocation/Uplink Transfer/Normal/Starting frame number encoding	R99	All EGPRS MS	C216	
52.3.1.1.4	Dynamic Allocation/Uplink Transfer/Normal/Starting time	R99	All EGPRS MS	C216	
52.3.1.1.5	Void				
52.3.1.1.6	Dynamic Allocation/Uplink Transfer/Normal/T3180 expiry	R99	All EGPRS MS	C216	
52.3.1.1.7	Dynamic Allocation/Uplink Transfer/Normal/PACCH operation	R99	All EGPRS MS	C216	
52.3.1.1.8	Dynamic Allocation/Uplink Transfer/Normal/Two uplink timeslots	R99	All EGPRS MS supporting Multislot classes: 5,6,7,9,..., 29)	C326	
52.3.1.2.2	Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in acknowledged mode	R99	All EGPRS MS	C216	
52.3.1.2.3	Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in unacknowledged mode	R99	All EGPRS MS	C216	
52.3.2.1.1	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Successful	R99	All EGPRS MS	C216	
52.3.2.1.2	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Multislot capabilities	R99	All EGPRS MS supporting Multislot classes: 2,3,4,5,6,8,9,10,19,24)	C277	
52.3.2.2.1	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/with random access	R99	All EGPRS MS	C216	
52.3.2.2.2	Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/Continuation of normal operation	R99	All EGPRS MS	C216	
52.3.3.1.1	Dynamic Allocation/Resource reallocation/Successful/Higher throughput class or higher radio priority	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.3.3.1.2	Dynamic Allocation/Resource reallocation/Successful/Lower throughput class	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.3.3.1.3	Dynamic Allocation/Resource reallocation/Successful/Different RLC mode and higher radio priority	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.3.3.2.1	Dynamic Allocation/Resource reallocation/Abnormal/T3168 expiry	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.3.3.2.2	Dynamic Allocation/Resource reallocation/Abnormal/Invalid assignment	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.3.3.3	Dynamic Allocation/Resource reallocation/Reject	R99	EGPRS MS supporting two PDP contexts or supporting SMS over GPRS and at least one PDP context	C278	
52.4	Void				
52.5.5.1	Downlink Transfer/ Reestablishment/ T3192 Expiry	R99	All EGPRS MS	C216	
52.5.5.2	Downlink Transfer/ Reestablishment/ Packet Downlink Assignment	R99	All EGPRS MS	C216	
52.5.5.3	Downlink Transfer/ Reestablishment/ Invalid Frequency Parameters IE	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
52.6.1	EGPRS Packet Access for signalling / EGPRS Packet Channel Request not supported / CCCH case	R99	For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS	For R99: C316 For Rel-4 and onwards: C216	
52.6.2	EGPRS Packet Access for signalling / EGPRS Packet Channel Request supported / CCCH case	R99	For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS	For R99: C316 For Rel-4 and onwards: C216	
52.6.3	EGPRS Packet Access for signalling / EGPRS Packet Channel Request not supported / PCCCH case	R99	For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS	For R99: C316 For Rel-4 and onwards: C216	
52.6.4	EGPRS Packet Access for signalling / EGPRS Packet Channel Request supported / PCCCH case	R99	For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS	For R99: C316 For Rel-4 and onwards: C216	
52.8.1.1	One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Inclusion of TLLI in RLC data blocks	R99	All EGPRS MS	C216	
52.8.1.2	One phase access/ PBCCH present / CONTENTION_RESOLUTION_TLLI Contention resolution / Counter N3104	R99	All EGPRS MS	C216	
52.8.1.3	One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Timer T3166	R99	All EGPRS MS	C216	
52.8.1.4	One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI /Contention resolution / TLLI mismatch	R99	All EGPRS MS	C216	
52.8.1.5	One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI / Contention resolution /4 access repetition attempts	R99	All EGPRS MS	C216	
52.8.1.6	One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Inclusion of TLLI in RLC data blocks	R99	All EGPRS MS	C216	
52.8.1.7	One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI /Contention resolution / Counter N3104	R99	All EGPRS MS	C216	
52.8.1.8	One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Timer T3166	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
52.8.1.9	One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / TLLI mismatch	R99	All EGPRS MS	C216	
52.8.1.10	One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / 4 access repetition attempts	R99	All EGPRS MS	C216	
52.8.1.11	One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Successful Resource Reallocation	R99	All EGPRS MS	C216	
52.8.1.12	One phase access/PBCCH absent/ CONTENTION_RESOLUTION_TLLI / Contention resolution / Successful Resource Reallocation	R99	All EGPRS MS	C216	
53.1.1.1	Acknowledged Mode/ Uplink TBF/ Send State Variable V(S)	R99	All EGPRS MS	C216	
53.1.1.2	Acknowledged Mode/ Uplink TBF/ Acknowledge State Variable V(A)	R99	All EGPRS MS	C216	
53.1.1.3	Acknowledged Mode/ Uplink TBF/ Window Size/ Default Value	R99	All EGPRS MS	C216	
53.1.1.4	Acknowledged Mode/ Uplink TBF/ Window Size/ Assigned Value	R99	All EGPRS MS	C216	
53.1.1.5	Acknowledged mode/ Uplink TBF/ Invalid Negative Acknowledgement	R99	All EGPRS MS	C216	
53.1.1.6	Acknowledged Mode/ Uplink TBF/ Countdown Value	R99	All EGPRS MS	C216	
53.1.1.7	Acknowledged Mode/ Uplink TBF/ Interpretation of Receive Block Bitmap	R99	All EGPRS MS	C216	
53.1.1.8	Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission/ Default Mode	R99	All EGPRS MS	C216	
53.1.1.9	Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '1'	R99	All EGPRS MS	C216	
53.1.1.10	Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '0'/ PENDING_ACK Blocks	R99	All EGPRS MS	C216	
53.1.1.11	Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '0'/ Negative Acknowledgement	R99	All EGPRS MS	C216	
53.1.1.12	Acknowledged Mode/ Uplink TBF/ Retransmission/ Split RLC Data Block	R99	All EGPRS MS	C216	
53.1.1.13	Acknowledged Mode/ Uplink TBF/ Calculation of BSN2	R99	All EGPRS MS	C216	
53.1.1.14	Acknowledged Mode/ Uplink TBF/ Verification of Coding Schemes	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
53.1.1.15	Acknowledged Mode/ Uplink TBF/ Recalculation of CV on MCS change	R99	All EGPRS MS	C216	
53.1.1.16	Acknowledged Mode/ Uplink TBF/ Retransmission/ Padding in the Data Field	R99	All EGPRS MS	C216	
53.1.1.17	Acknowledged Mode/ Uplink TBF/ Retransmission/ Puncturing Scheme Cycle	R99	All EGPRS MS	C216	
53.1.1.18	EGPRS Acknowledged mode/Uplink TBF/Link Adaptation Procedure for retransmission	R99	All EGPRS MS	C216	
53.1.1.19	EGPRS Acknowledged mode/Uplink TBF/Link Adaptation Procedure for initial transmission	R99	All EGPRS MS	C216	
53.1.1.20	Acknowledged Mode/ Uplink TBF/ Retransmission/ MCS Selection without Re-segmentation	R99	All EGPRS MS	C216	
53.1.1.21	Acknowledged Mode/ Uplink TBF/ Initial Puncturing Scheme After MCS Switching	R99	All EGPRS MS	C216	
53.1.1.22	Acknowledged Mode/ Uplink TBF/ Recalculation of CV on TBC change	R99	All EGPRS MS	C216	
53.1.1.23	Acknowledged Mode/ Uplink TBF/ Interpretation of Compressed Bitmap	R99	All EGPRS MS	C216	
53.1.1.24	Acknowledged Mode/ Uplink TBF/ Interpretation of PBSN	R99	All EGPRS MS	C216	
53.1.1.25	Acknowledged Mode/ Uplink TBF/ TBF Reallocation/Window Size	R99	All EGPRS MS supporting Multislot classes: 5,6,7,9,..., 29)	C326	
53.1.2.1	Acknowledged Mode/ Downlink TBF/ Receive State Variable V(R)	R99	All EGPRS MS	C216	
53.1.2.2	Acknowledged Mode/ Downlink TBF/ Receive Window State Variable V(Q)	R99	All EGPRS MS	C216	
53.1.2.3	Acknowledged Mode/ Downlink TBF/ Window Size/ Default Value	R99	All EGPRS MS	C216	
53.1.2.4	Acknowledged Mode/ Downlink TBF/ Window Size/ Assigned Value	R99	All EGPRS MS	C216	
53.1.2.5	Acknowledged Mode/ Downlink TBF/ BOW	R99	All EGPRS MS	C216	
53.1.2.6	Acknowledged Mode/ Downlink TBF/ EOW	R99	All EGPRS MS	C216	
53.1.2.7	Acknowledged Mode/ Downlink TBF/ Measurement Report	R99	All EGPRS MS	C216	
53.1.2.8	Acknowledged Mode/ Downlink TBF/ Generation of Bitmap	R99	All EGPRS MS	C216	
53.1.2.9	Acknowledged Mode/ Downlink TBF/ Interpretation of BSN2	R99	All EGPRS MS	C216	
53.1.2.10	Acknowledged Mode/ Downlink TBF/ Split RLC Data Block	R99	All EGPRS MS	C216	
53.1.2.11	Acknowledged Mode/ Downlink TBF/ First Partial Bitmap and Next Partial Bitmap	R99	All EGPRS MS	C216	
53.1.2.12	Acknowledged Mode/ Downlink TBF/ Decoding of Coding Schemes	R99	All EGPRS MS	C216	
53.1.2.13	Acknowledged Mode/ Downlink TBF/ IR Operation	R99	All EGPRS MS	C216	
53.1.2.14	Acknowledged Mode/ Downlink TBF/ Received Bitmap/ Compressed	R99	All EGPRS MS	C216	
53.1.2.15	Acknowledged Mode/ Downlink TBF/ Received Bitmap/ Uncompressed	R99	All EGPRS MS	C216	
53.1.2.16	Acknowledged Mode/ Downlink TBF/ Received Block Bitmap/ Compressed Bitmap Starting Colour Code	R99	All EGPRS MS	C216	

Clause	Title	Release	Applicability	Status	Supported
53.1.2.17	Acknowledged Mode/ Downlink TBF/ Received Block Bitmap/ Terminating Code and Make-up Code	R99	All EGPRS MS	C216	
53.1.2.18	Acknowledged Mode/ Downlink TBF/ Retransmission/Padding	R99	All EGPRS MS	C216	
53.1.2.19	Acknowledged Mode/ Downlink TBF/ Retransmission/Padding	R99	All EGPRS MS supporting Multislot classes higher than 1	C211	
53.2.1.1	Unacknowledged Mode/ Uplink TBF/ Stall Indicator	R99	All EGPRS MS	C216	
53.2.1.2	Unacknowledged Mode/ Uplink TBF/ RBB and SSN	R99	All EGPRS MS	C216	
53.2.2.1	Unacknowledged Mode/ Downlink TBF/ V(R) and V(Q)	R99	All EGPRS MS	C216	
60.1	Inter system handover to UTRAN/From GSM/Speech/Success	R99	MS supporting both GSM and UTRAN	C285	
60.2	Inter system handover to UTRAN/From GSM/Data/Same data rate/Success	R99	MS supporting both GSM and UTRAN	C286	
60.3	Inter system handover to UTRAN/From GSM/ Data/Same data rate upgrading/Success	R99	MS supporting both GSM and UTRAN	C287	
60.4	Inter system handover to UTRAN/From GSM/Speech/Establishment/Success	R99	MS supporting both GSM and UTRAN	C288	
60.5	Inter system handover to UTRAN/From GSM/Speech/Blind HO/Success	R99	MS supporting both GSM and UTRAN	C288	
60.6	Inter system handover to UTRAN/From GSM/Speech/Failure	R99	MS supporting both GSM and UTRAN	C288	
60.7	Inter system handover to UTRAN/From GSM/Failure/Cause: Frequency not implemented	R99	MS supporting both GSM and UTRAN	C289	
60.8	Inter system handover to UTRAN/From GSM/Failure/Cause: UTRAN preconfiguration unknown	R99	MS supporting both GSM and UTRAN	C289	
60.9	Inter system handover to UTRAN/From GSM/Failure/Cause: Protocol Error	R99	MS supporting both GSM and UTRAN	C289	
70.2.1	Network Induced E-OTD emergency call test on an SDCCH, Idle, no IMSI	R98	MSs supporting MS-Assisted EOTD	C281	
70.2.2	Positioning/RR/Classmark Interrogation tests	R98	MSs supporting MS-Assisted EOTD	C281	
70.2.3	Network Induced E-OTD emergency call test on an SDCCH	R98	MSs supporting MS-Assisted EOTD	C281	
70.2.4	E-OTD test for NI-LR on the TCH	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.1.1	MO_LR Basic Self Location Request In Idle Mode (Normal Case)	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.1.2	MO_LR Basic Self Location Request In Dedicated Mode (Normal Case)	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.2	MO_LR Transfer to 3 rd Party	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.3	MOLR_Autonomous Location	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.4.1	MO_LR Positioning Measurement / Protocol Error	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.4.2	MO_LR Positioning Measurement / Location Error	R98	MSs supporting MS-Assisted EOTD and do not support LCS MS-Assisted GPS	C318	

Clause	Title	Release	Applicability	Status	Supported
70.3.4.3	MO_LR Positioning Measurement / Multiple RRLP REQUEST with same Reference Number	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.4.4	MO_LR Positioning Measurement / Multiple RRLP REQUEST with different Reference Number	R98	MSs supporting MS-Assisted EOTD	C281	
70.3.4.5	MO_LR Positioning Measurement / RR Management Commands	R98	MSs supporting MS-Assisted EOTD	C281	
70.4.1	E-OTD test for MT-LR Location Notification	R98	MSs supporting MS-Assisted EOTD	C281	
70.4.2.1	E-OTD test for MT-LR Privacy Options – Location Allowed.	R98	MSs supporting MS-Assisted EOTD and Privacy Options	C304	
70.4.2.2	E-OTD test for MT-LR Privacy Options – Location Not Allowed.	R98	MSs supporting MS-Assisted EOTD and Privacy Options	C304	
70.6.1	E-OTD Sensitivity Performance Tests for GMSK	R98	All MSs supporting MS-Assisted EOTD for GMSK	C313	
70.6.2	E-OTD Interference performance test for GMSK	R98	All MSs supporting MS-Assisted EOTD for GMSK	C313	
70.6.3	E-OTD Multipath performance test for GMSK	R98	All MSs supporting MS-Assisted EOTD for GMSK	C313	
70.6.4	E-OTD Interference performance test for 8PSK	R99	All MSs supporting MS-Assisted EOTD for 8PSK	C314	
70.6.5	E-OTD Multipath performance test for 8PSK	R98	All MSs supporting MS-Assisted EOTD for 8PSK	C314	
70.6.6	E-OTD Sensitivity Performance Tests for 8PSK	R99	All MSs supporting MS-Assisted EOTD for 8PSK	C314	
70.7.1.1	A-GPS LCS Network Induced test case for MS-Based GPS for Emergency Call on an SDCCH, Idle, no IMSI state	R98	All MSs supporting LCS MS-Based GPS	C283	
70.7.1.2	A-GPS LCS Network Induced test case for MS-Assisted GPS for Emergency Call on an SDCCH, Idle, no IMSI state	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.7.2.1	A-GPS LCS Classmark Interrogation test case for MS-Based GPS	R98	All MSs supporting LCS MS-Based GPS	C283	
70.7.2.2	A-GPS LCS Classmark Interrogation test case for MS-Assisted GPS	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.7.3.1	A-GPS LCS Network Induced test case for MS-Based GPS test on an SDCCH radio channel	R98	All MSs supporting LCS MS-Based GPS	C283	
70.7.3.2	A-GPS LCS Network Induced test case for MS-Assisted GPS test on an SDCCH radio channel	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.7.4.1	Network Induced Location Request Emergency Call on TCH for mobiles supporting MS-Based GPS	R98	All MSs supporting LCS MS-Based GPS	C283	
70.7.4.2	Network Induced Location Request Emergency Call on TCH for mobiles supporting MS-Assisted GPS	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.8.1	Basic Self Location	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.8.2	Basic Self Location in Dedicated Mode	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.8.3	Transfer to 3 rd Party	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.8.4.1	MO-LR Positioning Measurement / Protocol Error	R98	All MSs supporting MS-Assisted GPS	C284	
70.8.4.2.1	MO-LR Positioning Measurement / Location Error: Requested Method not Supported	R98	All MSs supporting MS-Assisted GPS and not supporting MS-Assisted EOTD	C320	

Clause	Title	Release	Applicability	Status	Supported
70.8.4.2.2	MO-LR Positioning Measurement / Location Error: GPS Assistance Data Missing	R98	All MSs supporting MS-Assisted GPS	C284	
70.8.4.3	MO-LR Positioning Measurement / Multiple RRLP Requests with Same Reference Number	R98	All MSs supporting MS-Assisted GPS	C284	
70.8.4.4	MO-LR Positioning Measurement / Multiple RRLP Requests with Different Reference Number	R98	All MSs supporting MS-Assisted GPS	C284	
70.8.4.5	MO-LR Positioning Measurement / RR Management Commands	R98	All MSs supporting MS-Assisted GPS	C284	
70.8.5.1	MO_LR Basic Self Location Request in Idle Mode (Normal Case)	R98	All MSs supporting LCS MS-Based GPS	C283	
70.8.5.2	MO_LR Basic Self Location Request in Dedicated Mode (Normal Case)	R98	All MSs supporting LCS MS-Based GPS	C283	
70.9.1.1	MT-LR Location Notification for mobiles supporting MS-Based GPS	R98	All MSs supporting LCS MS-Based GPS	C283	
70.9.1.2	MT-LR Location Notification for mobiles supporting MS-Assisted GPS	R98	All MSs supporting LCS MS-Assisted GPS	C284	
70.9.2.1	MT-LR Privacy Options/Verification-Location Allowed If No Response for MS-Based GPS	R98	MSs supporting LCS MS-Based GPS and Privacy Options	C302	
70.9.2.2	MT-LR Privacy Options/Verification-Location Allowed If No Response for MS-Assisted GPS	R98	MSs supporting LCS MS-Assisted GPS and Privacy Options	C303	
70.9.3.1	MT-LR Privacy Options/Verification-Location Not Allowed If No Response for MS-Based GPS	R98	MSs supporting LCS MS-Based GPS and Privacy Options	C302	
70.9.3.2	MT-LR Privacy Options/Verification-Location Not Allowed If No Response for MS-Assisted GPS	R98	MSs supporting LCS MS-Assisted GPS and Privacy Options	C303	
70.10.1.1	Network Induced Location Request Emergency Call on an SDCCH.	R98	All MSs supporting LCS conventional GPS	C328	
70.10.2.1	Network Induced Location Request Emergency Call on TCH Radio Channel	R98	All MSs supporting LCS conventional GPS	C328	
80.1.1	Transmission of CTM Bearer Code – Mobile Originated TTY Call	R99	All MS supporting TTY text telephony services	C329	
80.1.2	Transmission of CTM Bearer Code – Mobile Terminated TTY Call	R99	All MS supporting TTY text telephony services	C329	
C1	IF NOT A.25/50 THEN A ELSE N/A		-- NOT TSPC_AddInfo_ApplAlwaysRun		
C2	IF A.25/1 THEN A ELSE N/A		-- TSPC_AddInfo_HalfRate		
C3	IF A.5/14 AND A.5/13 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_AoCI		
C4	IF A.5/14 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC		
C5	IF A.25/11 THEN A ELSE N/A		-- TSPC_AddInfo_AsyncNonTransData		
C6	IF A.25/10 THEN A ELSE N/A		-- TSPC_AddInfo_AsyncData		
C7	IF A.2/26 THEN A ELSE N/A		-- TSPC_Feat_Autocall		
C8	IF A.25/56 THEN A ELSE N/A		-- TSPC_AddInfo_AutocallBnoGreaterM		
C9	IF A.2/22 THEN A ELSE N/A		-- TSPC_Feat_BO		
C10	IF A.25/17 THEN A ELSE N/A		-- TSPC_AddInfo_fullRate4.8		
C11	IF A.25/5 THEN A ELSE N/A		-- TSPC_AddInfo_FullRateData		
C12	IF A.25/6 THEN A ELSE N/A		-- TSPC_AddInfo_HalfRateData		
C13	IF A.25/3 THEN A ELSE N/A		-- TSPC_AddInfo_Half_rate_version_1		
C14	IF A.25/41 OR A.25/42 THEN A ELSE N/A		-- TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin		
C15	IF (A.25/41 OR A.25/42) AND A.25/43 THEN A ELSE N/A		-- (TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin) AND TSPC_AddInfo_DisablePin		
C16	IF (A.25/41 OR A.25/42) AND A.2/21 THEN A ELSE N/A		-- (TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin) AND TSPC_Feat_FND		
C17	IF (A.25/41 OR A.25/42) AND A.25/44 THEN A ELSE N/A		-- (TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin) AND TSPC_AddInfo_Pin2		
C18	IF A.25/59 THEN A ELSE N/A		-- TSPC_AddInfo_MT2orOther		
C19	IF A.2/41 AND A.2/58 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_non_zero_NON_DRX_TIMER		
C20	IF A.25/60 THEN A ELSE N/A		-- TSPC_AddInfo_PermAntenna		
C21	IF A.25/45 THEN A ELSE N/A		-- TSPC_AddInfo_Pin2Feature		

Clause	Title	Release	Applicability	Status	Supported
C22	IF A.25/7 THEN A ELSE N/A		-- TSPC_AddInfo_NonTransData		
C23	IF A.25/8 THEN A ELSE N/A		-- TSPC_AddInfo_TransData		
C24	IF A.25/2 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_1		
C25	IF A.25/8 AND A.25/58 THEN A ELSE N/A		-- TSPC_AddInfo_TransData AND TSPC_AddInfo_MT2		
C26	IF A.3/6 THEN A ELSE N/A		-- TSPC_Serv_TS61		
C27	IF A.3/7 THEN A ELSE N/A		-- TSPC_Serv_TS62		
C28	IF A.3/7 AND NOT A.3/6 THEN A ELSE N/A		-- TSPC_Serv_TS62 AND NOT TSPC_Serv_TS61		
C29	IF A.3/7 OR A.3/6 THEN A ELSE N/A		-- TSPC_Serv_TS62 OR TSPC_Serv_TS61		
C30	IF (A.3/7 OR A.3/6) AND A.25/28 THEN A ELSE N/A		-- (TSPC_Serv_TS62 OR TSPC_Serv_TS61) AND TSPC_AddInfo_FaxErrCor		
C31	IF A.25/19 THEN A ELSE N/A		-- TSPC_Addinfo_MTsvc		
C32	IF NOT A.5/14 THEN A ELSE N/A		-- NOT TSPC_Serv_SS_AoCC		
C33	IF A.5/14 AND (NOT A.5/10) THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND (NOT TSPC_Serv_SS_HOLD)		
C34	IF A.5/14 AND A.5/10 AND (NOT A.5/11) THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_HOLD AND (NOT TSPC_Serv_SS_MPTY)		
C35	IF NOT A.2/21 THEN A ELSE N/A		-- NOT TSPC_Feat_FND		
C36	IF A.25/20 THEN A ELSE N/A		-- TSPC_Addinfo_MOsvc		
C37	IF A.25/22 THEN A ELSE N/A		-- TSPC_Addinfo_SvcOnTCH		
C38	IF A.25/23 THEN A ELSE N/A		-- TSPC_Addinfo_DualRate		
C39	IF A.25/4 THEN A ELSE N/A		-- TSPC_Addinfo_DataSvc		
C40	IF A.25/30 THEN A ELSE N/A		-- TSPC_Addinfo_NonCallSS		
C41	IF A.3/4 THEN A ELSE N/A		-- TSPC_Serv_TS22		
C42	IF A.3/1 OR A.3/2 THEN A ELSE N/A		-- TSPC_Serv_TS11 OR TSPC_Serv_TS12		
C43	IF A.25/26 THEN A ELSE N/A		-- TSPC_AddInfo_CC		
C47	IF A.25/26 AND (A.2/17 OR A.2/18) THEN A ELSE N/A		-- TSPC_AddInfo_CC AND (TSPC_Feat_A51 OR TSPC_Feat_A52)		
C48	IF A.25/26 AND A.25/55 THEN A ELSE N/A		-- TSPC_AddInfo_CC AND TSPC_Addinfo_RFAmp		
C50	IF A.25/26 AND A.25/3 THEN A ELSE N/A		-- TSPC_AddInfo_CC AND TSPC_AddInfo_Half_rate_version_1		
C51	IF A.25/40 THEN A ELSE N/A		-- TSPC_Addinfo_SIMRmv		
C52	IF A.25/2 OR A.25/3 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1		
C53	IF NOT A.25/2 THEN A ELSE N/A		-- NOT TSPC_AddInfo_Full_rate_version_1		
C55	IF (NOT A.25/27) AND (NOT A.25/51) AND A.25/19 THEN A ELSE N/A		-- (NOT TSPC_Addinfo_EmgOnly) AND (NOT TSPC_Addinfo_ImmConn) AND TSPC_ Addinfo_MTsvc		
C56	IF A.3/1 OR A.3/2 OR A.3/6 OR A.4/20 THEN A ELSE N/A		-- TSPC_Serv_TS11 OR TSPC_Serv_TS12 OR TSPC_Serv_TS61 OR TSPC_Serv_BS61		
C58	IF A.3/6 OR A.4/20 OR A.4/21 THEN A ELSE N/A		-- TSPC_Serv_TS61 OR TSPC_Serv_BS61 OR TSPC_Serv_BS81		
C59	IF A.5/13 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCI		
C62	IF A.5/16 OR A.5/18 OR A.5/17 OR A.5/19 OR A.5/15 THEN A ELSE N/A		-- TSPC_Serv_SS_BOIC OR TSPC_Serv_SS_BAIC OR TSPC_Serv_SS_BOICexHC OR TSPC_Serv_SS_BICRoam OR TSPC_Serv_SS_BAOC		
C64	IF A.5/7 OR A.5/5 THEN A ELSE N/A		-- TSPC_Serv_SS_CFNRY OR TSPC_Serv_SS_CFU		
C65	IF A.5/6 OR A.5/5 OR A.5/8 OR A.5/7 THEN A ELSE N/A		-- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFU OR TSPC_Serv_SS_CFNRC OR TSPC_Serv_SS_CFNRY		
C66	IF A.5/6 OR A.5/8 OR A.5/7 THEN A ELSE N/A		-- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFNRC OR TSPC_Serv_SS_CFNRY		
C67	IF A.5/6 THEN A ELSE N/A		-- TSPC_Serv_SS_CFB		
C68	IF A.5/19 AND A.5/15 THEN A ELSE N/A		-- TSPC_Serv_SS_BICRoam AND TSPC_Serv_SS_BAOC		
C69	IF A.5/14 AND A.25/40 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND TSPC_ Addinfo_SIMRmv		
C70	IF A.5/14 AND A.5/10 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_HOLD		
C71	IF A.5/14 AND A.5/11 THEN A ELSE N/A		-- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_MPTY		
C72	IF A.3/3 AND A.25/26 THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_AddInfo_CC		
C73	IF A.3/4 AND A.25/26 THEN A ELSE N/A		-- TSPC_Serv_TS22 AND TSPC_AddInfo_CC		
C74	IF A.3/3 AND (A.25/36) THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_ AddInfo_StoreRcvSMSSIM		

Clause	Title	Release	Applicability	Status	Supported
C76	IF A.1/6 THEN A ELSE N/A		-- Type_MB_Simul		
C78	IF A.1/6 AND A.25/26 THEN A ELSE N/A		-- Type_MB_Simul AND TSPC_AddInfo_CC		
C79	IF A.25/26 AND A.25/61 THEN A ELSE N/A		-- TSPC_AddInfo_CC AND TSPC_AddInfo_PseudoSynch		
C80	IF A.25/62 THEN A ELSE N/A		-- TSPC_AddInfo_5V		
C81	IF A.25/63 THEN A ELSE N/A		-- TSPC_AddInfo_3V		
C82	IF A.25/64 THEN A ELSE N/A		-- TSPC_AddInfo_5V3V		
C83	IF A.25/65 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_2		
C84	IF A.25/20 AND A.25/65 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_2 AND TSPC_AddInfo_MOsvc		
C85	IF A.25/19 AND A.25/65 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_2 AND TSPC_AddInfo_MTsvc		
C86	IF A.1/15 THEN A ELSE N/A		-- TSPC_Type_HSCSD_Multislot		
C87	IF A.1/15 AND A.25/26 THEN A ELSE N/A		-- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_CC		
C88	IF A.1/15 AND A.25/20 THEN A ELSE N/A		-- Type_HSCSD_Multislot AND TSPC_AddInfo_Mosvc		
C89	IF A.1/15 AND A.25/19 THEN A ELSE N/A		-- Type_HSCSD_Multislot AND TSPC_AddInfo_MTsvc		
C90	IF A.1/15 AND NOT A.25/50 THEN A ELSE N/A		-- TSPC_Type_GPRS_Multislot_operation AND NOT TSPC_AddInfo_ApplAlwaysRun		
C91	IF A.25/95 THEN A ELSE N/A		-- TSPC_AddInfo_1,8V		
C92	IF A.25/104 THEN A ELSE N/A		-- TSPC_AddInfo_IntegrAntenna		
C93	IF A.1/15 AND A.25/60 THEN A ELSE N/A		-- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_PermAntenna		
C94	IF A.1/15 AND A.25/104 THEN A ELSE N/A		-- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_IntegrAntenna		
C95	IF A.1/51 AND A.25/60 AND A.1/57 THEN A ELSE N/A		-- TSPC_Type_GPRS_Multislot_operation AND TSPC_AddInfo_PermAntenna AND TSPC_Type_GPRS_Multislot_uplink		
C96	IF A.1/51 AND A.25/104 AND A.1/57 THEN A ELSE N/A		-- TSPC_Type_GPRS_Multislot_operation AND TSPC_AddInfo_IntegrAntenna AND TSPC_Type_GPRS_Multislot_uplink		
C97	IF A.1/52 AND A.25/60 THEN A ELSE N/A		-- TSPC_Type_EGPRS_8PSK_uplink AND TSPC_AddInfo_PermAntenna		
C98	IF A.1/52 AND A.25/104 THEN A ELSE N/A		-- Type_EGPRS_8PSK_uplink AND TSPC_AddInfo_IntegrAntenna		
C99	IF (NOT A.1/3) AND A.25/60 THEN A ELSE N/A		-- NOT TSPC_Type_GSM_R_Band AND TSPC_AddInfo_PermAntenna		
C100	IF (NOT A.1/3) AND (A.25/2 OR A.25/3) THEN A ELSE N/A		-- NOT TSPC_Type_GSM_R_Band AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1)		
C101	IF A.25/96 THEN A ELSE N/A		-- TSPC_AddInfo_1,8V3V		
C102	IF NOT A.1/3 THEN A ELSE N/A		-- NOT Type_GSM_R_Band		
C103	IF A.1/3 THEN A ELSE N/A		-- TSPC_Type_GSM_R_Band		
C104	IF A.25/66b OR A.25/68 THEN A ELSE N/A		-- TSPC_AddInfo_VBS_Listening OR TSPC_AddInfo_VGCS_Listening		
C105	IF (A.25/66b OR A.25/68) AND A.25/71 AND A.25/80 AND A.25/81 AND A.25/82 THEN A ELSE N/A		-- (TSPC_AddInfo_VBS_Listening OR TSPC_AddInfo_VGCS_Listening) AND TSPC_AddInfo_NCH_ReducedMonitor AND TSPC_AddInfo_NCH_Monit_Rev AND TSPC_AddInfo_NCH_Monit_Tra AND TSPC_AddInfo_NCH_Monit_Ded		
C106	IF A.25/67 OR A.25/69 THEN A ELSE N/A		-- TSPC_AddInfo_VBS_Originating OR TSPC_AddInfo_VGCS_Talking		
C107	IF A.25/67 OR A.25/70 THEN A ELSE N/A		-- TSPC_AddInfo_VBS_Originating OR TSPC_AddInfo_VGCS_Originating		
C108	IF A.25/69 THEN A ELSE N/A		-- TSPC_AddInfo_VGCS_Talking		
C109	IF A.25/70 THEN A ELSE N/A		-- TSPC_AddInfo_VGCS_Originating		
C110	IF A.25/67 THEN A ELSE N/A		-- TSPC_AddInfo_VBS_Originating		
C111	IF A.5/21 AND A.3/1 THEN A ELSE N/A		-- TSPC_Serv_eMLPP AND TSPC_Serv_TS11		
C112	IF A.5/21 AND A.5/10 AND A.5/9 AND A.3/1 THEN A ELSE N/A		-- TSPC_Serv_eMLPP AND TSPC_Serv_SS_HOLD AND TSPC_Serv_SS_CW AND TSPC_Serv_TS11		
C113	IF (A.25/66b OR A.25/68) AND A.5/21 THEN A ELSE N/A		-- (TSPC_AddInfo_VBS_Listening OR TSPC_AddInfo_VGCS_Listening) AND TSPC_Serv_eMLPP		
C114	IF A.5/21 THEN A ELSE N/A		-- TSPC_Serv_eMLPP		

Clause	Title	Release	Applicability	Status	Supported
C115	IF A.25/60 AND A.1/3 THEN A ELSE N/A		-- TSPC_AddInfo_PermAntenna AND TSPC_Type_GSM_R_Band		
C116	IF (A.25/2 OR A.25/3) AND A.1/3 THEN A ELSE N/A		-- (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) AND TSPC_Type_GSM_R_Band		
C119	IF A.1/3 AND NOT (A.25/2 OR A.25/3) THEN A ELSE N/A		-- TSPC_Type_GSM_R_Band AND NOT (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1)		
C120	IF A.25/7 AND A.25/66a THEN A ELSE N/A		-- TSPC_AddInfo_NonTransData AND TSPC_AddInfo_NonDefaultRlpParam		
C121	IF A.25/57 THEN A ELSE N/A		-- TSPC_AddInfo_SpeechHandset		
C122	IF A.25/58 THEN A ELSE N/A		-- TSPC_AddInfo_MT2		
C123	IF (A.1/2 OR A.1/3) AND A.25/26 THEN A ELSE N/A		-- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND TSPC_AddInfo_CC		
C124	IF A.1/2 OR A.1/3 THEN A ELSE N/A		-- TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band		
C125	IF (A.1/2 OR A.1/3) AND (A.3/1 OR A.3/6 OR A.3/7) THEN A ELSE N/A		-- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND (TSPC_Serv_TS11 OR TSPC_Serv_TS61 OR TSPC_Serv_TS62)		
C126	IF (A.1/2 OR A.1/3) AND A.3/1 THEN A ELSE N/A		-- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND TSPC_Serv_TS11		
C127	IF A.1/6 AND (A.3/1 OR A.3/7) THEN A ELSE N/A		-- TSPC_Type_MB_Simul AND (TSPC_Serv_TS11 OR TSPC_Serv_TS62)		
C128	IF A.25/68 THEN A ELSE N/A		-- TSPC_AddInfo_VGCS_Listening		
C129	IF (A.1/1 OR A.1/6) AND (A.25/41 OR A.25/42) THEN A ELSE N/A		-- (TSPC_Type_DCS_Band OR TSPC_Type_MB_Simul) AND (TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin)		
C130	IF A.25/19 AND A.25/54 THEN A ELSE N/A		-- TSPC_AddInfo_MTsvc AND TSPC_ AddInfo_RefusalCall		
C131	IF A.3/1 OR A.3/7 THEN A ELSE N/A		-- TSPC_Serv_TS11 OR TSPC_Serv_TS62		
C132	IF A.25/44 THEN A ELSE N/A		-- TSPC_AddInfo_Pin2		
C133	IF A.5/6 OR A.5/8 THEN A ELSE N/A		-- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFNRY		
C134	IF A.5/16 THEN A ELSE N/A		-- TSPC_Serv_SS_BAOC		
C135	IF A.5/18 THEN A ELSE N/A		-- TSPC_Serv_SS_BAIC		
C136	IF A.5/17 THEN A ELSE N/A		-- TSPC_Serv_SS_BOICexHC		
C137	IF A.5/17 OR A.5/18 THEN A ELSE N/A		-- TSPC_Serv_SS_BOICexHC OR TSPC_Serv_SS_BAIC		
C138	IF A.5/16 OR A.5/19 THEN A ELSE N/A		-- TSPC_Serv_SS_BOIC OR TSPC_Serv_SS_BICRoam		
C139	IF A.5/20 THEN A ELSE N/A		-- TSPC_Serv_SS_unstruct		
C140	IF A.5/20 AND A.25/26 THEN A ELSE N/A		-- TSPC_Serv_SS_unstruct AND TSPC_AddInfo_CC		
C141	IF A.3/3 AND A.3/4 AND A.25/35 THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_Serv_TS22 AND TSPC_AddInfo_SMSStatusRepCap		
C142	IF A.3/3 AND A.25/34 THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_AddInfo_DispRcvSMS		
C143	IF A.3/3 AND A.25/34 AND (A.25/36 OR A.25/37) THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_ AddInfo_DispRcvSMS AND (TSPC_ AddInfo_StoreRcvSMSSIM OR TSPC_ AddInfo_StoreRcvSMSME)		
C144	IF A.3/3 AND A.25/33 AND A.25/34 THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_ AddInfo_ReplaceSMS AND TSPC_ AddInfo_DispRcvSMS		
C145	IF A.3/3 AND A.3/4 AND A.25/32 AND A.25/34 THEN A ELSE N/A		-- TSPC_Serv_TS21 AND TSPC_Serv_TS22 AND TSPC_AddInfo_ReplyProc AND TSPC_ AddInfo_DispRcvSMS		
C190	IF A.2/1 THEN A ELSE N/A		-- TSPC_Feat_DCN		
C191	IF A.5/28 THEN A ELSE N/A		-- TSPC_Serv_SS_FollowMe		
C192	IF A.5/25 THEN A ELSE N/A		-- TSPC_Serv_SS_ImpUUS1		
C193	IF A.5/24 THEN A ELSE N/A		-- TSPC_Serv_SS_ECT		
C194	IF A.5/11 THEN A ELSE N/A		-- TSPC_Serv_SS_MPTY		
C195	IF A.5/10 THEN A ELSE N/A		-- TSPC_Serv_SS_HOLD		
C196	IF A.5/9 THEN A ELSE N/A		-- TSPC_Serv_SS_CW		
C197	IF A.5/1 THEN A ELSE N/A		-- TSPC_Serv_SS_CLIP		
C198	IF A.5/2 THEN A ELSE N/A		-- TSPC_Serv_SS_CLIR		
C199	IF A.5/3 THEN A ELSE N/A		-- TSPC_Serv_SS_COLP		
C200	IF A.5/4 THEN A ELSE N/A		-- TSPC_Serv_SS_COLR		
C201	IF A.2/11 THEN A ELSE N/A		-- TSPC_Feat_ServInd		

Clause	Title	Release	Applicability	Status	Supported
C202	IF A.2/14 THEN A ELSE N/A		-- TSPC_Feat_SIM		
C203	IF A.25/79 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_3		
C204	IF A.1/57 THEN A ELSE N/A		-- TSPC_Type_GPRS_Multislot_uplink		
C206	IF A.2/39 THEN A ELSE N/A		-- TSPC_Feat_audible_tone		
C207	IF A.2/38 THEN A ELSE N/A		-- TSPC_SoLSA		
C208	IF A.2/52 THEN A ELSE N/A		-- TSPC_GSM_CTS		
C209	IF A.2/52 AND (A.1/1 OR A.1/2 OR A.1/3 OR A.1/4) THEN A ELSE N/A		-- TSPC_GSM_CTS AND (TSPC_Type_GSM_P_Band OR TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band OR TSPC_Type_DCS_Band)		
C210	IF A.2/41 AND A.25/26 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_AddInfo_CC		
C211	IF A.2/42 AND NOT A.1/18 THEN A ELSE N/A		-- TSPC_EGPRS AND TSPC_Type_GPRS_Multislot_operation		
C213	IF A.2/58 THEN A ELSE N/A		-- TSPC_COMPACT		
C214	IF A.2/53 THEN A ELSE N/A		-- TSPC_ECSD		
C215	IF A.2/41 THEN A ELSE N/A		-- TSPC_GPRS		
C216	IF A.2/42 THEN A ELSE N/A		-- TSPC_EGPRS		
C220	IF A.25/109 THEN A ELSE N/A		-- TSPC_AddInfo_MultSMS		
C221	IF A.2/41 AND A.2/48 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_operation_mode_B		
C222	IF A.2/41 AND A.25/83 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Addinfo_1PDP_CA		
C223	IF A.2/41 AND A.25/84 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Addinfo_mor1PDP CA		
C224	IF A.2/41 AND A.25/85 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Addinfo_mor1PDP CA_SAPI		
C225	IF A.2/41 AND A.25/88 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Addinfo_N_req_PDP_CA		
C226	IF A.2/41 AND A.2/47 OR A.2/48 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_operation_mode_A OR TSPC_operation_mode_B		
C227	IF A.2/41 AND NOT (A.1/22 OR A.1/23 OR A.1/25 OR A.1/29) THEN A ELSE N/A		-- TSPC_GPRS AND NOT (TSPC_Type_GPRS_Multislot_Class1 AND TSPC_Type_GPRS_Multislot_Class2 AND TSPC_Type_GPRS_Multislot_Class4 AND TSPC_Type_GPRS_Multislot_Class8)		
C228	IF A.2/41 AND (A.1/24 OR A.1/25 OR A.1/26 OR A.1/27 OR A.1/28 OR A.1/29 OR A.1/30 OR A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class4 OR...OR TSPC_Type_GPRS_Multislot_Class29)		
C229	IF A.2/41 AND (A.1/40 OR A.1/45) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class19 OR TSPC_Type_GPRS_Multislot_Class24)		
C230	IF A.2/41 AND (A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29)		
C231	IF A.2/41 AND A.1/22 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Type_GPRS_Multislot_Class1		
C232	IF A.2/41 AND (A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class19 OR...OR TSPC_Type_GPRS_Multislot_Class29)		
C233	IF A.2/41 AND (A.1/24 OR A.1/26 OR A.1/27 OR A.1/28 OR A.1/30 A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class7 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29)		

Clause	Title	Release	Applicability	Status	Supported
C234	IF A.2/41 AND (A.1/23 OR A.1/24 OR A.1/25 OR A.1/26 OR A.1/27 OR A.1/29 OR A.1/30 OR A.1/31 OR A.1/40 OR A.1/45) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class2 OR TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class4 OR TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class8 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR TSPC_Type_GPRS_Multislot_Class19 OR TSPC_Type_GPRS_Multislot_Class24)		
C235	IF A.2/41 AND (A.25/83 OR A.25/84 OR A.2/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_AddInfo_1PDP_CA OR TSPC_AddInfo_mor1PDP_CA OR TSPC_SMS_over_GPRS)		
C236	IF A.2/41 AND NOT A.25/90 THEN A ELSE N/A		-- TSPC_GPRS AND NOT TSPC_AddInfo_on_auto_GPRS_AP		
C237	IF A.2/41 AND NOT A.25/88 THEN A ELSE N/A		-- TSPC_GPRS AND NOT TSPC_AddInfo_N_req_PDP_CA		
C238	IF A.1/52 THEN A ELSE N/A		-- TSPC_Type_EGPRS_8PSK_uplink Multislot_operation		
C248	IF A.2/41 AND A.25/89 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_AddInfo_min_QoS		
C251	IF A.2/67 THEN A ELSE N/A		TSPC_MT_SMS_over_GPRS		
C252	IF A.2/67 AND A.25/35 THEN A ELSE N/A		TSPC_MT_SMS_over_GPRS AND TSPC_AddInfo_SMSStatusRepCap		
C253	IF (A.2/41 AND A.2/50) THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_SMS_over_GPRS		
C254	Void				
C255	Void				
C256	Void				
C257	Void				
C258	Void				
C259	Void				
C260	Void				
C261	Void				
C262	Void				
C263	Void				
C264	Void				
C265	Void				
C266	Void				
C267	Void				
C268	Void				
C269	Void				
C270	Void				
C271	Void				
C272	IF A.25/97 THEN A ELSE N/A		-- TSPC_AddInfo_MultSMsameRR		
C273	IF A.1/56 THEN A ELSE N/A		-- TSPC_Type_UTRAN		
C274	IF A.2/41 AND A.25/105 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_AddInfo_Comb_DP_no_pwr_off		
C275	IF A.2/41 AND A.25/106 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_AddInfo_Usr_non_GPRS_DP		
C276	IF A.2/42 AND (A.1/24 OR A.1/26 OR A.1/27 OR A.1/28 OR A.1/30 A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR...OR TSPC_Type_EGPRS_Multislot_Class29)		

Clause	Title	Release	Applicability	Status	Supported
C277	IF A.2/42 AND (A.1/23 OR A.1/24 OR A.1/25 OR A.1/26 OR A.1/27 OR A.1/29 OR A.1/30 OR A.1/31 OR A.1/40 OR A.1/45) THEN A ELSE N/A		-- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class2 OR TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class4 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class8 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR TSPC_Type_EGPRS_Multislot_Class19 OR TSPC_Type_EGPRS_Multislot_Class24)		
C278	IF A.2/42 AND (A.25/83 OR A.25/84 OR A.2/50) THEN A ELSE N/A		-- TSPC_EGPRS AND (TSPC_AddInfo_1PDP_CA OR TSPC_AddInfo_mor1PDP_CA OR TSPC_SMS_over_GPRS)		
C279	IF A.2/42 AND A.25/83 THEN A ELSE N/A		-- TSPC_EGPRS AND TSPC_AddInfo_1PDP_CA		
C280	IF A.25/57 AND NOT A.1/56 THEN A ELSE N/A		--TSPC_AddInfo_SpeechHandset AND NOT TSPC_Type_UTRAN		
C281	IF A.2/57 THEN A ELSE N/A		-- TSPC_EOTD_ASSIST		
C282	IF A.2/41 AND A.25/88 AND A.25/110 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Addinfo_N_req_PDP_CA AND TSPC_Cell_Resel		
C283	IF A.2/59 THEN A ELSE N/A		-- TSPC_A-GPS_Based		
C284	IF A.2/60 THEN A ELSE N/A		-- TSPC_A-GPS_Assist		
C285	IF (A.1/56 AND A.27/1 AND (A.25/2 OR A.25/3 OR A.25/65 OR A.25/79) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/6 OR A.1/17)) THEN A ELSE N/A		-- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1 OR TSPC_AddInfo_Full_rate_version_2 OR TSPC_AddInfo_Full_rate_version_3) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND)		
C286	IF (A.1/56 AND (A.27/2 AND ((A.1/15 OR A25/5) AND A.25/72)) OR (A.27/3 AND (A.1/15 OR A25/5) OR (A.27/4 AND A.25/4) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17)) THEN A ELSE N/A		-- TSPC_Type_UTRAN AND () AND TSPC_Streaming_14_4_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateSpeech) AND TSPC_AddInfo_144Data) OR (TSPC_Streaming_28_8_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateSpeech) OR (TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_AddInfo_DataSvc) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND)		
C287	IF (A.1/56 AND (A.27/2 AND ((A.1/15 OR A25/5) AND A.25/72) OR (A.27/4 AND (A.1/15 OR A25/5) AND A.25/72) OR (A.27/4 AND AND (A.1/15 OR A25/5) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17)) THEN A ELSE N/A		-- TSPC_Type_UTRAN AND (TSPC_STREAMING_28_8_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateSpeech) AND TSPC_AddInfo_144Data) OR ((TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateSpeech) AND TSPC_AddInfo_144Data) OR (TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateSpeech) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND)		

Clause	Title	Release	Applicability	Status	Supported
C288	IF (A.1/56 AND A.27/1 AND A.25/2 AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17)) THEN A ELSE N/A		-- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND TSPC_AddInfo_Full_rate_version_1 AND (TSPC_Type_GSM_P_BAND OR TSPC_Type_GSM_E_BAND OR TSPC_Type_DCS_BAND OR TSPC_Type_GSM_450_BAND OR TSPC_Type_GSM_480_BAND)		
C289	IF (A.1/56 AND A.27/1 AND A.25/2 AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/53 OR A.1/55)) THEN A ELSE N/A		-- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND TSPC_AddInfo_Full_rate_version_1 AND (TSPC_Type_GSM_P_BAND OR TSPC_Type_GSM_E_BAND OR TSPC_Type_DCS_BAND OR TSPC_Type_GSM_450_BAND OR TSPC_Type_GSM_480_BAND OR TSPC_Type_PCS_BAND OR TSPC_Type_GSM_700_BAND OR TSPC_Type_GSM_850_BAND)		
C290	IF A.3/3 THEN A ELSE N/A		-- TSPC_Serv_TS21		
C300	IF A.3/5 THEN A ELSE N/A		-- TSPC_Serv_TS23		
C301	Void				
C302	IF A.2/59 AND A.2/61 THEN A ELSE N/A		-- TSPC_A-GPS_BASE AND TSPC_PRIVACY		
C303	IF A.2/60 AND A.2/61 THEN A ELSE N/A		-- TSPC_A-GPS_ASSIST AND TSPC_PRIVACY		
C304	IF A.2/57 AND A.2/61 THEN A ELSE N/A		-- TSPC_EOTD AND TSPC_PRIVACY		
C305	IF A.2/62 THEN A ELSE N/A		-- TSPC_DTM		
C306	IF A.1/59 THEN A ELSE N/A		-- TSPC_DTM_Multislot_Class_1		
C307	IF A.1/60 THEN A ELSE N/A		-- TSPC_DTM_Multislot_Class_5		
C308	IF A.1/61 THEN A ELSE N/A		-- TSPC_DTM_Multislot_Class_9		
C309	void				
C310	IF A.1/62 THEN A ELSE N/A		-- TSPC_DTM_Singleslot_Allocation		
C311	IF NOT A.1/62 THEN A ELSE N/A		-- NOT TSPC_DTM_Singleslot_Allocation		
C312	void				
C313	IF A.2/63 THEN A ELSE N/A		TSPC_EOTD_ASSIST AND TSPC_PERF_GMSK		
C314	IF A.2/64 THEN A ELSE N/A		TSPC_EOTD_ASSIST AND TSPC_PERF_8PSK		
C315	IF A.2/62 AND A.1/56 THEN A ELSE N/A		-- TSPC_Type_UTRAN AND TSPC_DTM		
C316	IF A.2/42 AND A.2/65 THEN A ELSE N/A		-- TSPC_EGPRS AND TSPC_EGPRS_ENHANC		
C317	IF A.2/41 AND A.2/15 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Feat_OnOff		
C318	IF (A.2/57 AND NOT A.2/60) THEN A ELSE N/A		-- TSPC_EOTD_ASSIST AND NOT -- TSPC_A-GPS_Assist		
C319	IF A.25/112 THEN A ELSE N/A		-- TSPC_AddInfo_Half_rate_version_3		
C320	IF (A.2/60 AND NOT A.2/57) THEN A ELSE N/A		-- TSPC_A-GPS_Assist AND NOT -- TSPC_EOTD_ASSIST		
C321	IF A.25/79 AND A.25/113 THEN A ELSE N/A		-- TSPC_AddInfo_Full_rate_version_3 AND TSPC_LoopBack_I		
C322	IF A.2/41 AND A.2/66 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_NACC		
C323	IF (A.25/23) AND A.25/26 THEN A ELSE N/A		-- TSPC_AddInfo_DualRate AND TSPC_AddInfo_CC		
C324	IF A.2/41 AND A.1/56 THEN A ELSE N/A		-- TSPC_GPRS AND TSPC_Type_UTRAN		
C325	IF A.2/41 AND (A.1/26 OR A.1/27 OR A.1/28 OR A.1/30 A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class7 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29)		
C326	IF A.2/42 AND (A.1/26 OR A.1/27 OR A.1/28 OR A.1/30 A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39 OR A.1/40 OR A.1/41 OR A.1/42 OR A.1/43 OR A.1/44 OR A.1/45 OR A.1/46 OR A.1/47 OR A.1/48 OR A.1/49 OR A.1/50) THEN A ELSE N/A		-- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR...OR TSPC_Type_EGPRS_Multislot_Class29)		
C327	IF A.25/3 AND A.25/112 THEN A ELSE N/A		-- TSPC_AddInfo_Half_rate_version_1 AND TSPC_AddInfo_Half_rate_version_3		
C328	IF A.2/65 THEN A ELSE N/A		-- TSPC_Conv-GPS		
C329	IF A.25/114 THEN A ELSE N/A		-- TSPC_AddInfo_TTY		

Annex C (informative): Guidance for updating the PICS specification

The purpose of this Guidance for updating the PICS specification is to check the influence of a newly created, deleted or modified test case to the PICS specification and to fit the tables according the change.

This Guidance for updating the PICS specification shall give a recommendation, how to check and update all relevant tables and columns.

C.1 Update of tables of annex A

In annex A, all PICS items are listed and structured in tables of options and features.

If a test case is newly created, modified or deleted, the PICS items used for this test case has to be identified or known to update annex A.

C.2 Identification of PICS items

Support of PICS items can either be necessary to perform a test case, these PICS can be called Applicability PICS, or the support of PICS items can be inquired within a test case, these PICS can be called Capability PICS.

Applicability PICS are mostly described in clause "Definition and Applicability" in a test case description.

Capability PICS should be defined in clause "Related PICS/PIXIT statements" which is mostly a part for the "Method of test" description.

C.3 Update of PICS items

It shall be checked, in which table of annex A the identified PICS items can be assigned to.

If there are new PICS to be added where no existing tables refer to, a new table shall be created. Here, the given prerequisites have to be considered and checked for assigning a table of annex A.

For newly inserted PICS items, a Mnemonic shall be created and the Status column shall be checked and set (M, O,X, N/A, O.i, Ci). For a Status "Ci: conditional", the logical expression has to be defined on the end of the table.

The Status of a PICS could either be mentioned in the PICS Reference (Reference column) or in the test case description or it should be set by the test case writer.

The PICS Reference refers to a certain Release (Release column), i.e. when the PICS appears for the first time in the GSM and/or 3GPP reference.

C.4 Update of table B.1 of annex B

In annex B, all test cases as described in 3GPP TS 51.010-1, 3GPP TS 11.10-1 or 3GPP TS 11.10-4 are listed in table B.1.

If a test case is newly created, modified or deleted, the table B.1 has to be updated accordingly.

C.5 Update of the listed tests of table B.1

For newly created or modified test cases, the test case title and the clause number has to be listed or updated in table B.1.

If a newly created or modified test case is separated in sub-procedures dependent on different applicability conditions, the test case should be listed accordingly.

A test case is grouped to test a certain feature. Therefore the Release column shall indicate, in which Release of the core specification the tested feature was included for the first time. For instance, if a newly created test case tests a GPRS feature, the Release column is to set to R97, where the feature GPRS was added in the core specification.

C.6 Update of the applicability conditions of table B.1

For newly created or modified test cases, the Status column shall be checked (A, N/A, Ci).

I.e. the updated applicability status for the test case has to be set in the Status column.

If there is no applicability PICS necessary to perform a test case, the status "A" should be assigned.

If there is a logical combination of PICS items necessary to perform a test case, this combination shall be defined and updated as Status "Ci: conditional" on the end of the table and assigned to this test case. For instance, if a newly created test case needs the support of GPRS, the Status is conditional "Ci" and the logical combination has to use the PICS item "Support of GPRS".

The applicability column shall be checked and updated towards the Status of the test case.

It gives a short overview, when this test case is applicable.

If a deleted test cases was assigned with a Status "Ci:conditional", it should be checked, if this condition is used for further test cases, if not, the logical expression on the end of table B.1 can be deleted.

If a logical expression is deleted, it should be checked, if the used PICS items of tables A are also be removable.

Annex D (informative): Change history

Change history									
TSG #	TSG Doc	CR	Rev	Subject/Comment	Cat	Old	New	WG Doc	Work item
GP-04	GP-010465			Approved as v4.0.0		2.0.0	4.0.0		
GP-05	GP-011151	001		Update to applicability table in 51.010-2 due to TDoc G4-010225	F	4.0.0	4.1.0	G4-010242	GPRS
GP-05	GP-011151	002		Addition of EDGE test cases to the applicability table	F	4.0.0	4.1.0	G4-010329	EDGE
GP-05	GP-011151	004		Deletion of Test cases 13.5 and 13.17.5 from the Applicability Table	F	4.0.0	4.1.0	G4-010311	TEI
GP-05	GP-011151	005		Update of the Applicability Table with test cases for GPRS Cell Selection/Reselection 20.22	F	4.0.0	4.1.0	G4-010315	GPRS
GP-05	GP-011151	006		Recommendation for updating the PICS specification 3GPP TS 51.010-2 according to changes in 3GPP TS 51.010-1 or 3GPP TS 11.10-4	B	4.0.0	4.1.0	G4-010302	TEI
GP-06	GP-011466	007		Harmonisation of conformance tests related to terminal acoustics in GSM and 3G	F	4.1.0	4.2.0	G4-010336	TEI
GP-06	GP-011466	008		Correction of title for clause 44.2.3.3.4	F	4.1.0	4.2.0	G4-010369	GPRS
GP-06	GP-011466	009		Correction of conditional statement C226	F	4.1.0	4.2.0	G4-010436	GPRS
GP-06	GP-011466	010		Addition of new EGPRS test cases for section 51.3 (TBF Release)	F	4.1.0	4.2.0	G4-010419	EDGE
GP-06	GP-011466	011		Addition of new EGPRS test cases for section 52.4 (Measurement reports and Cell change order procedures)	F	4.1.0	4.2.0	G4-010420	EDGE
GP-06	GP-011466	012		Applicability table for EGPRS RR Paging Procedures	F	4.1.0	4.2.0	G4-010423	EDGE
GP-06	GP-011466	013		Applicability table for EGPRS Medium Access Control (MAC) Protocol/ Fixed Allocation	F	4.1.0	4.2.0	G4-010425	EDGE
GP-06	GP-011466	014		Addition of new EGPRS test cases for section 53 (EGPRS RLC Testcases)	F	4.1.0	4.2.0	G4-010429	EDGE
GP-06	GP-011466	015		Addition of new EGPRS test cases for section 52.3 (EGPRS MAC Dynamic Allocation)	F	4.1.0	4.1.0	G4-010534	EDGE
GP-06	GP-011466	016		Applicability table for Handover Test Cases	F	4.1.0	4.2.0	G4-010453	GSM/UMTS interworking
GP-06	GP-011466	017		Addition of 1,8V and 1,8V/3V SIM-ME interface test cases into 51.010-2 section A4.8 and Annex B (applicability table)	F	4.1.0	4.2.0	G4-010494	TEI
GP-06	GP-011466	018		Correction of COMPACT and SoLSA tests in the Release column of table B.1	F	4.1.0	4.2.0	G4-010448	TEI
GP-07	GP-012116	019		deletion of test case 27.11.2.1	F	4.2.0	4.3.0	G5-010043	TEI
GP-07	GP-012117	020		Correction of applicability condition C220 in Annex B.1	F	4.2.0	4.3.0	G5-010027	TEI
GP-07	GP-012118	021		Correction of applicability condition C52 in Annex B.1	F	4.2.0	4.3.0	G5-010028	TEI
GP-07	GP-012119	022		Changes to applicability of test case 44.2.1.2.3	F	4.2.0	4.3.0	G5-010149	GPRS
GP-07	GP-012120	023		45.2.1.2.1 – This Test Case Should Only Be Applicable To Mobiles That Support Configuration of Their QoS.	F	4.2.0	4.3.0	G5-010159	GPRS
GP-07	GP-012609	034		Applicability Table for E-OTD Test Cases for LCS Clause 70 (Rel-4)	F	4.2.0	4.3.0	-	LCS
GP-07	GP-012273	024		CR 51.010-2-024 on Annex B - removal of test case 51.2.4.2 (related to G4-010594) Rel-4	F	4.2.0	4.3.0	G4-010622	EDGE
GP-07	GP-012274	025		CR 51.010-2-025 on GSM 700 and GSM850 inclusion into forward Rel-4	B	4.2.0	4.3.0	G4-010649	GSM 700
GP-07	GP-012275	026		CR 51.010-2-026 on New test cases for clause 42.1 Rel-4	B	4.2.0	4.3.0	G4-010649	GPRS
GP-07	GP-012276	027		CR 51.010-2-027 on change of test case name for clause 51.2.2.2. Rel-4	F	4.2.0	4.3.0	G4-010663	EDGE
GP-07	GP-012277	028		CR 51.010-2-028 on Table B1 - Addition of section 52.1 testcases to the applicability table Rel-4	B	4.2.0	4.3.0	G4-010669	EGPRS
GP-07	GP-012191	030		CR 51.010-2-030 Correction to the Applicability of test cases 13.17.1; 13.17.3 and 13.17.4 (Rel 4)	F	4.2.0	4.3.0	GP-012191	EDGE
GP-07	GP-012201	031		CR 51.010-2-31 Annex B - renaming of test case 51.2.4.1 (Rel 4)	F	4.2.0	4.3.0	GP-012201	EDGE
GP-07	GP-012722	034	1	CR 51.010-2-034r1 Bad frame indication - TCH/AFS -	B	4.2.0	4.3.0	GP-012722	AMR

Change history									
TSG #	TSG Doc	CR	Rev	Subject/Comment	Cat	Old	New	WG Doc	Work item
				Random RF input 51.010-2					
GP-07	GP-012732	035		CR 51.010-2-035 14.18.7 Incremental Redundancy Performance, (addition of a new test) (Rel-4)	B	4.2.0	4.3.0	GP-012732	EGPRS
GP-07	GP-012784	036		CR 51.010-2-036 Applicability of test 42.2.2.4; Fixed Allocation/Uplink Transfer/T3184 Expiry	F	4.2.0	4.3.0	GP-012784	GPRS
GP-07	GP-012296	037		CR 51.010-2-035 Bad frame indication - TCH/AHS - Random RF input 51.010-2	B	4.2.0	4.3.0	GP-012296	AMR
GP-08	GP-020367	041	1	Applicability Table for E-OTD Test Cases for LCS Clause 70 (Rel-4)	F	4.3.0	4.4.0	GP-020367	LCS
GP-08	GP-020064	042		Update of references	F	4.3.0	4.4.0	GP-020064	TEI
GP-08	GP-020148	044		Additional Test Case	B	4.3.0	4.4.0	GP-020148	GPRS
GP-08	GP-020378	045	1	Addition of LCS test cases to the Applicability Tables A2 and B.1	F	4.3.0	4.4.0	GP-020378	LCS
GP-09	GP-021053	047	1	Applicability Table B.1: Addition of test of short message type 0 (34.2.6)	F	4.4.0	4.5.0	GP-021053	TEI
GP-09	GP-020549	048	-	Correction to reference clause	F	4.4.0	4.5.0	GP-020549	TEI
GP-09	GP-021213	049	1	CR 51.010-2-049 Addition of LCS performance test cases to the Applicability Table B.1	F	4.4.0	4.5.0		LCS
GP-09	GP-020605	051	-	51.010-2 Annex B: Correction of applicability table for section 46	F	4.4.0	4.8.0	GP-020605	GPRS
GP-09	GP-020665	052		Removal of applicability of GPRS Fixed Allocation tests (42.2.x) for R99 and Rel-4 - (Rel-4).	F	4.4.0	4.5.0		GPRS
GP-09	GP-020666	053		Removal of EGPRS Fixed Allocation tests (52.2.x) for R99 and Rel-4 - (Rel-4).	F	4.4.0	4.5.0		EDGE
GP-09	GP-020728	054	-	PICS update for GERAN to UTRAN Handover test cases	F	4.4.0	4.5.0	GP-020728	GERAN>UTRAN HO
GP-09	GP-020784	057		Removal of testcase 20.22.27 of 51.010-1	F	4.4.0	4.5.0		GPRS
GP-09	GP-021181	058	3	Applicability Table for A-GPS Test Cases for LCS Clause 70 (Rel 4)	F	4.4.0	4.5.0	GP-021181	LCS
GP-10	GP-021840	059	1	CR to Applicability Table B.1: Correction of various stati	F	4.5.0	4.6.0	GP-021840	TEI
GP-10	GP-021842	060	1	51.010-2-060 Correct the Applicability Tables B.1 and	F	4.5.0	4.6.0	GP-021842	LCS
GP-10	GP-021561	061	-	PICS update for AMR RATSCCH Test Cases	F	4.5.0	4.6.0	GP-021561	AMR
GP-10	GP-021871	062	1	Annex B – Renaming of testcase 41.4.3.3.2	F	4.5.0	4.6.0	GP-021561	GPRS
GP-11	GP-022747	069	2	51.010-2 PICS additions to section A.4.8 to better characterise non auto GPRS attach behaviour.	F	4.6.0	4.7.0	GP-022747	GPRS
GP-11	GP-022735	070	1	CR 51.010-2-070 r1 Modification of Applicability Table for E-OTD Performance Tests	F	4.6.0	4.7.0	GP-022735	LCS
GP-11	GP-022621	071	1	DTM additons to the PICS proforma tables for GSM mobile stations.	F	4.6.0	4.7.0	GP-022621	DTM
GP-11	GP-022294	072	-	DTM additons to the test applicability tables for GSM mobile stations (WG5).	F	4.6.0	4.7.0	GP-022294	DTM
GP-11	GP-022320	073		CR 51.010-2-073 DTM additons to the test applicability tables for GSM mobile stations (WG4).	F	4.6.0	4.7.0	GP-022320	DTM
GP-11	GP-022342	074		CR 51.010-2-074 Removal of 5 EGPRS test cases from Annex B, Table B.1. - Rel-4	F	4.6.0	4.7.0	GP-022342	EDGE
GP-11	GP-022693	075	1	Correction of PICS conditions and corrected applicability of test case 45.2.1.2.2 in TS 51.010-2	F	4.6.0	4.7.0	GP-022693	TEI4
GP-11	GP-022424	077	-	Applicability Table Update	F	4.6.0	4.7.0	GP-022424	LCS
GP-11	GP-022602	078	1	CR 51.010-2-078 r1 Removal of TBF establishment via DCCH in Annex B, Table B.1	F	4.6.0	4.7.0	GP-022602	GPRS
GP-11	GP-022734	079	1	CR 51.010-2-079 r1 Addition of new layer 1 tests to matrix	F	4.6.0	4.7.0	GP-022734	AMR
GP-11	GP-022635	080	1	Addition of new layer 3 tests to matrix	F	4.6.0	4.7.0	GP-022635	AMR
GP-11	GP-022473	081	-	Applicability Table for E-OTD MOLR test cases	F	4.6.0	4.7.0	GP-022473	LCS
GP									
GP-11	GP-022625	066	1	CR to 51.010-2: Addition of test of short message type 0 REL-5 (34.2.6a) to Applicability Table B.1	F	4.6.0	5.0.0	GP-022625	TEI
GP-11	GP-022128	067	-	Creation of 51.010-2 REL-5: Merging of REL-5, REL-4, R99 etc. PICS proforma Specifications	F	4.6.0	5.0.0	GP-022128	TEI
GP-12	GP-023335	083	1	CR 51.010-2-083 r1 Addition of WG4 DTM Conformance Tests to the Applicability table (Rel-5)	F	5.0.0	5.1.0	GP-023335	DTM
GP-12	GP-022948	084	-	Addition of WG5 DTM Conformance Tests to the Applicability Table	F	5.0.0	5.1.0	GP-022948	DTM
GP-12	GP-023388	086	1	Applicability Table Update	F	5.0.0	5.1.0	GP-023388	LCS
GP-12	GP-023033	087		CR 51.010-2-087 Changed the name of clause 51.2.2.3.	F	5.0.0	5.1.0	GP-023033	EDGE
GP-12	GP-023047	088	-	Change of Applicability for test case 44.2.1.1.8 - GPRS	F	5.0.0	5.1.0	GP-023047	GPRS

Change history									
TSG #	TSG Doc	CR	Rev	Subject/Comment	Cat	Old	New	WG Doc	Work item
				attach/abnormal cases/power off					
GP-12	GP-023295	089	1	Add AMR half rate optional applicability	F	5.0.0	5.1.0	GP-023295	AMR
GP-12	GP-023385	091	1	Introduction of UTRAN Classmark Change test cases in section 26.6.11	F	5.0.0	5.1.0	GP-023385	TEI
GP-12	GP-023096	092		CR 51.010-2-092 Addition of Extended Uplink TBF Mode test cases to matrix	F	5.0.0	5.1.0	GP-023096	GPRS
GP-12	GP-023142	093	-	Applicability Table for GMM Test Cases	F	5.0.0	5.1.0	GP-023142	GPRS
GP-12	GP-023393	094	2	Applicability Table for E-OTD MOLR test cases	F	5.0.0	5.1.0	GP-023393	LCS
GP-12	GP-023334	095	1	CR 51.010-2-095 r1 Error in Conditional Expression C53 in Table B.1	F	5.0.0	5.1.0	GP-023334	GPRS
GP-12	GP-023392	096	2	Modifications to allow introduction of the 11.10-4 R99 Test Spec	F	5.0.0	5.1.0	GP-023392	TEI
GP-12	GP-023338	097		CR 51.010-2-097 Addition of 4 new EGPRS test cases.	F	5.0.0	5.1.0	GP-023338	EDGE
GP-13	GP-030368	099	2	Applicability of 'Speech teleservices' test cases in Annex B	F	5.1.0	5.2.0	GP-030368	TEI
GP-13	GP-030394	100	2	CR 51.010-2-100 r2 Update of applicability table	B	5.1.0	5.2.0		EDGE
GP-13	GP-030167	101		Update to Applicability Table Indicating Tests for MS-Assisted E-OTD	F	5.1.0	5.2.0	GP-030167	LCS
GP-13	GP-030363	102	1	Update to Applicability Table for Assisted GPS MO-LR Tests	F	5.1.0	5.2.0	GP-030363	LCS
GP-13	GP-030359	103	1	suppression of table A.26.2 Terminal Profile	F	5.1.0	5.2.0	GP-030359	SAT
GP-13	GP-030348	104		CR 51.010-2-104 Updating PICS for AMR test cases	B	5.1.0	5.2.0		AMR-NB
GP-13	GP-030389	105		CR 51.010-2-105 Updating PICS for EMR cases	B	5.1.0	5.2.0		TEI
GP-13	GP-030395	106	1	CR 51.010-2 106 r1 Addition of test case on NC2 and Re-allocation in uplink	B	5.1.0	5.2.0		GPRS (S42)
GP-14	GP-030499	107	-	Clarification to speech codec definitions	F	5.2.0	5.3.0	GP-030499	TEI
GP-14	GP-030500	108	-	Correction of Applicability column for clause 14.2.4.	F	5.2.0	5.3.0	GP-030500	TEI
GP-14	GP-030966	109	1	Addition of some DTM test cases to the applicability table.	F	5.2.0	5.3.0	GP-030966	DTM
GP-14	GP-030639	110	-	Deletion of test cases 42.4.2.1.5 and 52.4.2.1.5 from Table B.1.	F	5.2.0	5.3.0	GP-030639	GPRS
GP-14	GP-031044	111	2	Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1	F	5.2.0	5.3.0	GP-031044	GPRS
GP-14	GP-031017	113	2	Addition of test case in TS 51.010 S42: Packet Uplink Assignment containing a new Coding Scheme command.	F	5.2.0	5.3.0	GP-031017	GPRS
GP-14	GP-030841	114	-	Updating PICS for RxQual test cases	F	5.2.0	5.3.0	GP-030841	AMR
GP-14	GP-030999	115	1	Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1	F	5.2.0	5.3.0	GP-030999	GSM
GP-14	GP-030994	116	1	Addition of test cases for Network Assisted Cell Change	B	5.2.0	5.3.0	GP-030994	NACC
GP-14	GP-031013	117	-	CR 51.010-2 Incorrect applicability for 6 test cases of section 42.3.1.1.*	F	5.2.0	5.3.0	GP-031013	GPRS
GP-14	GP-031050	118	2	Update PICS for GPRS EMR Test case	F	5.2.0	5.3.0	GP-031050	GPRS
GP-15	GP-031086	119		CR 51.010-2-119 Table B.1: Conditions for TCs 14.2.18, 14.4.16, 26.6.5.2-2, 26.6.5.2-5, 26.6.5.2-6, 26.6.5.2-10 corrected; Missing TC 31.3.1.2.2.1 added	F	5.3.0	5.4.0	GP-031086	TEI
GP-15	GP-031287	122		CR 51.010-2-122 B1 Add new TC - 44.2.3.1.1a - Routing area updating / accepted / old P-TMSI	F	5.3.0	5.4.0	GP-031287	GPRS
GP-15	GP-031314	123		CR 51.010-2-123 Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1 and change of some testcases titles	F	5.3.0	5.4.0	GP-031314	GPRS
GP-15	GP-031460	124		CR 51.010-2-124 Update of Applicability Table for PEMR Test Cases (Rel-5)	F	5.3.0	5.4.0	GP-031460	GPRS
GP-15	GP-031714	125	1	CR 51.010-2-125 rev1 Update of Applicability Table for SMS over GPRS (Rel-5)	F	5.3.0	5.4.0	GP-031714	GPRS
GP-15	GP-031493	126		CR 51.010-2-126 Deletion of clauses 42.4.2.1.2 and 42.4.2.3.2 from Table B.1.	F	5.3.0	5.4.0	GP-031493	GPRS
GP-15	GP-031506	127		CR 51.010-2-127 Deletion of clause 52.4 from Table B.1	F	5.3.0	5.4.0	GP-031506	EDGE
GP-15	GP-031615	128		CR 51.010-2-1128 Deletion of test case 52.1.1.1 from Table B.1	F	5.3.0	5.4.0	GP-031615	EDGE
GP-15	GP-031629	129		CR 51.010-2 129 Update PICS for 22.12	F	5.3.0	5.4.0	GP-031629	GPRS
GP-15	GP-031631	130		CR 51.010-2 "Multiple PCCCH test cases 42.1.2.1.14, 42.1.2.1.15, 42.1.2.1.16, 42.1.2.1.17 and 42.1.2.1.18"	F	5.3.0	5.4.0	GP-031631	GPRS
GP-15	GP-031638	131	2	CR 51.010-2-131 rev2 Update PICS for 20.22.29	F	5.3.0	5.4.0	GP-031638	Cell selection
GP-16	GP-031952	121	1	CR 51.010-2-121 rev 1 Removal of the close-ended TBF feature in annex B, table B1	C	5.4.0	5.5.0		TEI
GP-16	GP-032156	135	1	CR 51.010-2-135 rev1 Modification in the applicability of	F	5.4.0	5.5.0		GPRS

Change history									
TSG #	TSG Doc	CR	Rev	Subject/Comment	Cat	Old	New	WG Doc	Work item
				the following testcases: 42.3.1.1.8, 42.7.4, 52.3.1.1.8. Changing the name of the testcase 20.22.5.					
GP-16	GP-031875	136		CR 51.010-2-136 Editorial changes to Packet Enhanced Measurement Reporting	F	5.4.0	5.5.0		GPRS
GP-16	GP-031961	137		CR 51.010-2-137 Applicability for 2G to 3G Cell Change Order Test Cases	F	5.4.0	5.5.0		GPRS
GP-16	GP-031974	138		CR 51.010-2-138 Update corresponding to changes to the DTM feature	F	5.4.0	5.5.0		DTM
GP-16	GP-032157	140		CR 51.010-2-140 Section 42: "New test cases: NC2 in Packet transfer mode	F	5.4.0	5.5.0		GPRS
GP-16	GP-032178	141	1	CR 51.010-2-141 rev1 Section 70: "New test case: Conventional GPS	F	5.4.0	5.5.0		LCS
GP-16	GP-032160	143		CR 51.010-2-143 26.16.10 splitted in two test cases	F	5.4.0	5.5.0		AMR
GP-17	GP-032307	144	-	Adding TTY test cases	B	5.5.0	5.6.0	GP-032307	TTY
GP-17	GP-032334	145	-	Addition of new NC2 cases	F	5.5.0	5.6.0	GP-032334	GPRS
GP-17	GP-032776	146	1	Modification to Applicability Table due to introduction of new testcases in 3GPP TS 51.010-1	F	5.5.0	5.6.0	GP-032776	GPRS
GP-17	GP-032425	147	-	CR 51.010-2 Test cases from section 53 missing	F	5.5.0	5.6.0	GP-032425	GPRS
GP-17	GP-032457	148	-	Update PICS for MOLR MS-Based AGPS Test cases	F	5.5.0	5.6.0	GP-032457	LCS
GP-17	GP-032495	149	-	Spilt of Multislot Classes for HSCSD, GPRS and EGPRS.	F	5.5.0	5.6.0	GP-032495	EGPRS
GP-17	GP-032566	150	-	CR 51.010-2 Correction of test numbers in section 21.3	F	5.5.0	5.6.0	GP-032566	GPRS
GP-17	GP-032643	151	-	New test cases: NACC	B	5.5.0	5.6.0	GP-032643	GPRS
GP-17	GP-032784	153	1	Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1	F	5.5.0	5.6.0	GP-032784	GSM
GP-17	GP-032779	154	-	Removal of test case 26.8.1.3.3.3 Incoming call / U9 mobile terminating call confirmed / termination requested by the user	F	5.5.0	5.6.0	GP-032779	TEI

History

Document history		
V5.0.0	September 2002	Publication
V5.1.0	December 2002	Publication
V5.2.0	February 2003	Publication
V5.3.0	April 2003	Publication
V5.4.0	July 2003	Publication
V5.5.0	September 2003	Publication
V5.6.0	November 2003	Publication