

ETSI TS 151 010-2 V7.9.0 (2008-04)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Mobile Station (MS) conformance specification;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification
(3GPP TS 51.010-2 version 7.9.0 Release 7)**



Reference

RTS/TSGG-0351010-2v790

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/legal/home.htm>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

| | |
|---|------------|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Foreword..... | 5 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions and abbreviations..... | 13 |
| 3.1 Definitions | 13 |
| 3.2 Abbreviations | 13 |
| 4 Conformance to this PICS proforma specification..... | 13 |
| Annex A (normative): PICS proforma for GSM mobile stations | 14 |
| A.1 Guidance for completing the PICS proforma..... | 14 |
| A.1.1 Purposes and structure..... | 14 |
| A.1.2 Abbreviations and conventions | 14 |
| A.1.3 Instructions for completing the PICS proforma..... | 16 |
| A.2 Identification of the implementation | 16 |
| A.2.1 Date of the statement | 16 |
| A.2.2 Implementation Under Test (IUT) identification | 16 |
| A.2.3 System Under Test (SUT) identification | 17 |
| A.2.4 Product supplier..... | 17 |
| A.2.5 Client | 17 |
| A.2.6 PICS contact person | 18 |
| A.3 Identification of the protocol..... | 18 |
| A.4 PICS proforma tables | 18 |
| A.4.1 Global statement of conformance..... | 18 |
| A.4.2 Types of Mobile Stations | 20 |
| A.4.3 Mobile Station Features..... | 33 |
| A.4.4 Teleservices..... | 37 |
| A.4.5 Bearer Services..... | 38 |
| A.4.6 Supplementary Services | 40 |
| A.4.7 Bearer Capability Information..... | 42 |
| A.4.8 Additional Information..... | 62 |
| A.4.9 SIM Application Toolkit | 72 |
| A.4.9.1 SIM Application Toolkit mechanism..... | 72 |
| A.4.9.1.1 Terminal Profile | 72 |
| A.4.10 Support of UTRAN Radio Access Technology..... | 72 |
| Annex B (normative): Applicability of the individual test | 73 |
| Annex C (informative): Guidance for updating the PICS specification..... | 231 |
| C.1 Update of tables of annex A | 231 |
| C.2 Identification of PICS items | 231 |
| C.3 Update of PICS items..... | 231 |
| C.4 Update of table B.1 of annex B | 231 |
| C.5 Update of the listed tests of table B.1..... | 232 |
| C.6 Update of the applicability conditions of table B.1 | 232 |

Annex D (informative): Labelling of Inter-RAT signalling test cases233
D.1 GERAN/UTRAN band combinations for inter-RAT tests.....233
Annex E (informative): Change history234
History247

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

This 3GPP TS provides the Protocol Implementation Conformance Statement (PICS) proforma for Mobile Stations (MSs), operating in the 400 MHz, 700 MHz, 850 MHz, 900 MHz, 1 800 MHz and 1 900 MHz frequency band (GSM 400, GSM 700, GSM 850, GSM 900, DCS 1 800 and PCS 1 900) within the digital cellular telecommunications system.

The present document is part 2 of a multi-part deliverable covering the Digital cellular telecommunications system (GSM Phase2 and Phase 2+ Releases 1996, 1997, 1998, 1999, 3GPP Release 4, 3GPP Release 5, 3GPP Release 6 and 3GPP Release 7); Mobile Station (MS) conformance specification, as identified below:

- Part 1: Conformance specification
Reference: 3GPP TS 51.010-1.
- Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification.
Reference: 3GPP TS 51.010-2.**
- Part 3: Layer 3 (L3) Abstract Test Suite (ATS).
Reference: 3GPP TS 51.010-3.
- Part 4: SIM Application Toolkit conformance specification
Reference: 3GPP TS 11.10-4.
- Part 5: Inter-RAT (GERAN to UTRAN) Abstract Test Suite (ATS)
Reference: 3GPP TS 51.010-5.

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for Global System for Mobile Stations (MSs), operating in the 450 MHz, 480 MHz, 700 MHz, 750 MHz, 850 MHz, 900 MHz, 1 800 MHz and 1 900 MHz frequency band (GSM 400, GSM 700, GSM 750, GSM 850, GSM 900, DCS 1 800 and PCS 1 900) within the European digital cellular telecommunications system, in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3] and ETS 300 406 [1].

The present document is valid for MS implemented according to GSM Phase2 or Phase2+ R96, or R97, or R98, or R99 or 3GPP Release 4 or 3GPP Release 5 or 3GPP Release 6 or 3GPP Release 7.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the relevant Release*.
 - For a GSM Phase 2+ Release 7 MS, references to GSM documents are to version 7.x.y, when available.
 - For a GSM Phase 2+ Release 6 MS, references to GSM documents are to version 6.x.y, when available.
 - For a GSM Phase 2+ Release 5 MS, references to GSM documents are to version 5.x.y, when available.
 - For a GSM Phase 2+ Release 4 MS, references to GSM documents are to version 4.x.y, when available.
 - For a GSM Phase 2+ Release 1999 MS, references to GSM documents are to version 8.x.y (for 01.-series to 12.-series) or (3.x.y for 21.-series to 35.-series), when available.
 - For a GSM Phase 2+ Release 1998 MS, references to GSM documents are to version 7.x.y, when available.
 - For a GSM Phase 2+ Release 1997 MS, references to GSM documents are to version 6.x.y, when available.
 - For a GSM Phase 2+ Release 1996 MS, references to GSM documents are to version 5.x.y, when available.
 - For a GSM Phase 2 MS, references to GSM documents are to version 4.x.y.

NOTE: References to 3GPP Technical Specifications and Technical Reports throughout this document shall be interpreted according to the Release shown in the formal reference in this clause, based upon the Release of the implementation under test.

Example 1: References for a Ph2 MS shall be interpreted as:

[1] 3GPP TS 01.04 Ph2

[2] 3GPP TS 02.02 Ph2

etc

Example 2: References for a Rel-4 MS shall be interpreted as:

[1] 3GPP TS 21.905 Rel-4

[2] 3GPP TS 22.002 Rel-4

etc

- [1] ETS 300 406 (January 1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [2] ISO/IEC 9646-1 (1995): "Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 1: General concepts".
- [3] ISO/IEC 9646-7 (1995): "Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 7: Implementation Conformance Statements".
- [4] 3GPP TS 02.01 (Ph2 to R98): "Principles of telecommunication services supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.001 (R99 onwards): "Principles of circuit telecommunication services supported by a Public Land Mobile Network (PLMN)".
- [5] 3GPP TS 02.02 (Ph2 to R98): "Bearer Services (BS) supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.002 (R99 onwards): "Circuit Bearer Services (BS) supported by a Public Land Mobile Network (PLMN)".
- [6] 3GPP TS 02.03 (Ph2 to R98): "Teleservices supported by a GSM Public Land Mobile Network (PLMN)".
3GPP TS 22.003 (R99 onwards): "Circuit Teleservices supported by a Public Land Mobile Network (PLMN)".
- [7] 3GPP TS 02.04 (Ph2 to R98): "General on supplementary services".
3GPP TS 22.004 (R99 onwards): "General on supplementary services".
- [8] 3GPP TS 02.06 (Ph2 to R98): "Types of Mobile Stations (MS)".
- [8a] 3GPP TS 22.101 (R99 onwards): "Service aspects; Service principles".
- [9] 3GPP TS 02.07 (Ph2 to R98): "Mobile Station (MS) features".
- [10] 3GPP TS 02.09 (Ph2 to R99): "Security aspects".
3GPP TS 42.009 (Rel-4 onwards): "Security aspects".
- [11] 3GPP TS 02.11 (Ph2 to R98): "Service accessibility".
3GPP TS 22.011 (R99 onwards): "Service accessibility".
- [12] 3GPP TS 02.16 (Ph2 to R98): "International Mobile station Equipment Identities (IMEI)".
3GPP TS 22.016 (R99 onwards): "International Mobile Equipment Identities (IMEI)".
- [13] 3GPP TS 02.17 (Ph2 to R99): "Subscriber Identity Modules (SIM); Functional characteristics".
3GPP TS 42.017 (Rel-4 onwards): "Subscriber Identity Modules (SIM); Functional characteristics".
- [14] 3GPP TS 02.24 (Ph2 to R98): "Description of Charge Advice Information (CAI)".
3GPP TS 22.024 (R99 onwards): "Description of Charge Advice Information (CAI)".
- [15] 3GPP TS 02.30 (Ph2 to R98): "Man-Machine Interface (MMI) of the Mobile Station (MS)".
3GPP TS 22.030 (R99 onwards): "Man-Machine Interface (MMI) of the User Equipment (UE)".
- [16] 3GPP TS 02.40 (Ph2 to R98): "Procedures for call progress indications".
- [17] 3GPP TS 02.41 (Ph2 to R98): "Operator determined barring".

- 3GPP TS 22.041 (R99 onwards): "Operator determined barring".
- [18] 3GPP TS 02.81 (Ph2 to R98): "Line identification supplementary services; Stage 1".
3GPP TS 22.081 (R99 onwards): "Line identification supplementary services; Stage 1".
- [19] 3GPP TS 02.82 (Ph2 to R98): "Call Forwarding (CF) supplementary services; Stage 1".
3GPP TS 22.082 (R99 onwards): "Call Forwarding (CF) supplementary services; Stage 1".
- [20] 3GPP TS 02.83 (Ph2 to R98): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 1".
3GPP TS 22.083 (R99 onwards): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 1".
- [21] 3GPP TS 02.84 (Ph2 to R98): "MultiParty (MPTY) supplementary services; Stage 1".
3GPP TS 22.084 (R99 onwards): "MultiParty (MPTY) supplementary services; Stage 1".
- [22] 3GPP TS 02.85 (Ph2 to R98): "Closed User Group (CUG) supplementary services; Stage 1".
3GPP TS 22.085 (R99 onwards): "Closed User Group (CUG) supplementary services; Stage 1".
- [23] 3GPP TS 02.86 (Ph2 to R98): "Advice of Charge (AoC) supplementary services; Stage 1".
3GPP TS 22.086 (R99 onwards): "Advice of Charge (AoC) supplementary services; Stage 1".
- [24] 3GPP TS 03.40 (Ph2 to R98): "Technical realization of the Short Message Service (SMS) Point to Point (PP)".
3GPP TS 23.040 (R99 onwards): "Technical realization of Short Message Service".
- [25] 3GPP TS 03.41 (Ph2 to R98): "Technical realization of Short Message Service Cell Broadcast (SMSCB)".
3GPP TS 23.041 (R99 onwards): "Technical realization of Cell Broadcast Service (CBS)".
- [26] 3GPP TS 03.45 (Ph2 to R99): "Technical Realization of Facsimile Group 3-transparent".
3GPP TS 43.045 (Rel-4 onwards): "Technical Realization of Facsimile Group 3 Service - transparent".
- [27] 3GPP TS 03.46 (Ph2 to R99): "Technical Realization of Facsimile Group 3 Service-non transparent".
3GPP TS 23.146 (Rel-4 onwards): "Technical realization of facsimile group 3 service-non-transparent".
- [28] 3GPP TS 04.02 (Ph2 to R98): "GSM Public Land Mobile Network (PLMN) access reference configuration".
3GPP TS 24.002 (R99 onwards): "GSM-UMTS Public Land Mobile Network (PLMN) Access Reference Configuration".
- [29] 3GPP TS 04.04 (Ph2 to R99): "Layer 1; General requirements".
3GPP TS 44.004 (Rel-4 onwards): "Layer 1; General requirements".
- [30] 3GPP TS 04.05 (Ph2 to R99): "Data Link (DL) layer; General aspects".
3GPP TS 44.005 (Rel-4 onwards): "Data Link (DL) layer; General aspects".
- [31] 3GPP TS 04.06 (Ph2 to R99): "Mobile Station – Base Station System (MS – BSS) interface Data Link (DL) layer specification".
3GPP TS 44.006 (Rel-4 onwards): "Mobile Station - Base Station System (MS - BSS) interface Data Link (DL) layer specification".

- [32] 3GPP TS 04.07 (Ph2 to R98): "Mobile radio interface signalling layer 3; General aspects".
3GPP TS 24.007 (R99 onwards): "Mobile radio interface signalling layer 3; General Aspects".
- [33] 3GPP TS 04.08 (Ph2 to R99): "Mobile radio interface layer 3 specification". (see note)
3GPP TS 24.008 (R99 onwards): "Mobile radio interface layer 3 specification; Core network protocols; Stage 3". (see note)
3GPP TS 44.008 (Rel-4): "Mobile radio interface layer 3 specification". (see note)
- [34] 3GPP TS 04.10 (Ph2 to R98): "Mobile radio interface layer 3; Supplementary services specification; General aspects".
3GPP TS 24.010 (R99 onwards): "Mobile radio interface Layer 3; Supplementary services specification; General aspects".
- [35] 3GPP TS 04.11 (Ph2 to R98): "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
3GPP TS 24.011 (R99 onwards): "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- [36] 3GPP TS 04.12 (Ph2 to R99): "Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
3GPP TS 44.012 (Rel-4 onwards): "Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
- [37] 3GPP TS 04.13 (Ph2 to R99): "Performance requirements on mobile radio interface".
3GPP TS 44.013 (Rel-4 onwards): "Performance requirements on the mobile radio interface".
- [37a] 3GPP TS 04.14 (R96 to R99): "Individual equipment type requirements and interworking; Special conformance testing functions".
3GPP TS 44.014 (Rel-4 onwards): "Individual equipment type requirements and interworking; Special conformance testing functions".
- [38] 3GPP TS 04.21 (Ph2 to R99): "Rate adaption on the Mobile Station – Base Station System (MS – BSS) interface".
3GPP TS 44.021 (Rel-4 onwards): "Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [39] 3GPP TS 04.22 (Ph2 to R98): "Radio Link Protocol (RLP) for data and telematic services on the Mobile Station – Base Station System (MS – BSS) interface and the Base Station System – Mobile-services Switching Centre (BSS – MSC) interface".
3GPP TS 24.022 (R99 onwards): "Radio Link Protocol (RLP) for circuit switched bearer and teleservices".
- [40] 3GPP TS 04.80 (Ph2 to R98): "Mobile radio interface layer 3; supplementary services specification; Formats and coding". (See Note 1)
3GPP TS 24.080 (R99 onwards): "Mobile radio Layer 3; supplementary service specification; Formats and coding".
- [41] 3GPP TS 04.81 (Ph2 to R98): "Line identification supplementary services; Stage 3".
3GPP TS 24.081 (R99 onwards): "Line identification supplementary service; Stage 3".
- [42] 3GPP TS 04.82 (Ph2 to R98): "Call Forwarding (CF) supplementary services; Stage 3".
3GPP TS 24.082 (R99 onwards): "Call Forwarding (CF) supplementary service; Stage 3".

- [43] 3GPP TS 04.83 (Ph2 to R98): "Call Waiting (CW) and Call Hold (HOLD) supplementary services; Stage 3".
3GPP TS 24.083 (R99 onwards): "Call Waiting (CW) and Call Hold (HOLD) supplementary service; Stage 3".
- [44] 3GPP TS 04.84 (Ph2 to R98): "MultiParty (MPTY) supplementary services; Stage 3".
3GPP TS 24.084 (R99 onwards): "Multiparty (MPTY) supplementary service; Stage 3".
- [45] 3GPP TS 04.85 (Ph2 to R98): "Closed User Group (CUG) supplementary services; Stage 3".
3GPP TS 24.085 (R99 onwards): "Closed User Group (CUG) supplementary services; Stage 3".
- [46] 3GPP TS 04.86 (Ph2 to R98): "Advice of Charge (AoC) supplementary services; Stage 3".
3GPP TS 24.086 (R99 onwards): "Advice of Charge (AoC) supplementary service; Stage 3";
- [47] 3GPP TS 04.88 (Ph2 to R98): "Call Barring (CB) supplementary services; Stage 3".
3GPP TS 24.088 (R99 onwards): "Call Barring (CB) supplementary service; Stage 3".
- [48] 3GPP TS 04.90 (Ph2 to R98): "Unstructured Supplementary Services Data (USSD)".
3GPP TS 24.090 (R99 onwards): "Unstructured Supplementary Service Data (USSD); Stage 3".
- [49] 3GPP TS 05.01 (Ph2 to R99): "Physical layer on the radio path (General description)".
GPP TS 45.001 (Rel-4 onwards): "Physical layer on the radio path (General description)".
- [50] 3GPP TS 05.02 (Ph2 to R99): "Multiplexing and multiple access on the radio path".
GPP TS 45.002 (Rel-4 onwards): "Multiplexing and multiple access on the radio path".
- [51] 3GPP TS 05.03 (Ph2 to R99): "Channel coding".
3GPP TS 45.003 (Rel-4 onwards): "Channel coding".
- [52] 3GPP TS 05.04 (Ph2 to R99): "Modulation".
3GPP TS 45.004 (Rel-4 onwards): "Modulation".
- [53] 3GPP TS 05.05 (Ph2 to R99): "Radio transmission and reception".
3GPP TS 45.005 (Rel-4 onwards): "Radio transmission and reception".
- [54] 3GPP TS 05.08 (Ph2 to R99): "Radio subsystem link control".
3GPP TS 45.008 (Rel-4 onwards): "Radio subsystem link control".
- [56] 3GPP TS 05.10 (Ph2 to R99): "Radio subsystem synchronisation".
3GPP TS 45.010 (Rel-4 onwards): "Radio subsystem synchronization".
- [57] 3GPP TS 05.09 (Ph2 to R99): "Link adaptation".
3GPP TS 45.009 (Rel-4 onwards): "Link adaptation".
- [58] 3GPP TS 07.01 (Ph2 to R98): "General on Terminal Adaptation Functions (TAF) for Mobile Stations (MS)".
3GPP TS 27.001 (R99 onwards): "General on Terminal Adaptation Functions (TAF) for Mobile Stations (MS)".
- [57] 3GPP TS 02.68 (R96 to R99): "Voice Group Call Service (VGCS); Stage 1".
3GPP TS 42.068 (Rel-4 onwards): "Voice Group Call Service (VGCS); Stage 1".
- [58] 3GPP TS 02.69 (R96 to R99): "Voice Broadcast Service (VBS); Stage 1".

- 3GPP TS 42.069 (Rel-4 onwards): "Voice Broadcast Service (VBS); Stage 1".
- [59] 3GPP TS 02.87 (R98): "User-to-User Signalling (UUS); Service description; Stage 1".
- 3GPP TS 22.087 (R99 onwards): "User-to-User Signalling (UUS); Service description, Stage 1".
- [60] 3GPP TS 22.094 (R99 onwards): "Follow Me service description; Stage 1".
- [61] 3GPP TS 03.68 (R96 to R99): "Voice Group Call Service (VGCS); Stage 2".
- GPP TS 43.068 (Rel-4 onwards): "Voice Group Call Service (VGCS); Stage 2".
- [62] 3GPP TS 03.69 (R96 to R99): "Digital cellular telecommunications system (See Note 1); Voice Broadcast Service (VBS); Stage 2".
- 3GPP TS 43.069 (Rel-4 onwards): "Voice Broadcast Service (VBS); Stage 2".
- [63] 3GPP TS 03.87 (R98): "User-to-User Signalling (UUS); Stage 2".
- 3GPP TS 23.087 (R99 onwards): "User-to-User Signalling (UUS) supplementary service; Stage 2".
- [64] 3GPP TS 23.094 (R99 onwards): "Follow-Me (FM); Stage 2".
- [65] 3GPP TS 04.68 (R96 to R98): "Group Call Control (GCC) protocol".
- 3GPP TS 44.068 (Rel-4 onwards): "Group Call Control (GCC) protocol".
- [66] 3GPP TS 04.69 (R96 to R99): "Broadcast Call Control (BCC) protocol".
- GPP TS 44.069 (Rel-4 onwards): "Broadcast Call Control (BCC) protocol".
- [67] 3GPP TS 04.87 (R98): "User-to-User Signalling (UUS) Supplementary Service; Stage 3".
- 3GPP TS 24.087: "User-to-User Signalling (UUS); Stage 3".
- [68] 3GPP TS 02.43 (R98 to R99): "Support of Localised Service Area (SoLSA); Service description; Stage 1".
- [69] Void
- [70] 3GPP TS 02.60 (R97 to R98): "General Packet Radio Service; Stage 1; Description".
- 3GPP TS 22.060 (R99 onwards): "General Packet Radio Service (GPRS); Service Description; Stage 1".
- [71] Void
- [72] 3GPP TS 02.67 (R96 to R98): "enhanced Multi-Level Precedence and Pre-emption service (eMLPP); Stage 1".
- 3GPP TS 22.067: "enhanced Multi-Level Precedence and Pre-emption service (eMLPP); Stage 1".
- [73] Void.
- [74] 3GPP TS 02.72 (R98): "Call Deflection Service description, Stage 1".
- 3GPP TS 22.072 (R99 onwards): "Call Deflection (CD); Stage 1".
- [75] Void.
- [76] Void.
- [77] 3GPP TS 02.91 (R96 to R98): "Explicit Call Transfer (ECT)".
- 3GPP TS 22.091 (R99 onwards): "Explicit Call Transfer (ECT)".
- [78] Void.

- [79] Void.
- [80] Void.
- [81] 3GPP TS 03.38 (Ph2 to R98): "Alphabets and language-specific information for GSM".
3GPP TS 23.038 (R99 onwards): "Alphabets and language-specific information".
- [82] Void.
- [83] Void.
- [84] Void.
- [85] 3GPP TS 03.73 (R98): "Support of Localised Service Area (SoLSA); Stage 2".
3GPP TS 23.073 (R99 onwards): "Support of Localised Service Area (SoLSA); Stage 2".
- [86] Void.
- [87] 3GPP TS 04.65 (R97 to R99): "General Packet Radio Service (GPRS); Mobile Station (MS) - Serving GPRS Support Node (SGSN); Subnetwork Dependent Convergence Protocol (SNDCCP)".
3GPP TS 44.065 (Rel-4 onwards): General Packet Radio Service (GPRS); Mobile Station (MS) - Serving GPRS Support Node (SGSN); Subnetwork Dependent Convergence Protocol (SNDCCP)".
- [88] Void.
- [89] 3GPP TS 09.07 (Ph2 to R98): "General Requirements on Interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
3GPP TS 29.007 (R99 onwards): "General requirements on Interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
- [91] 3GPP TS 11.11 (Ph2 to R99): "Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
3GPP TS 51.011 (Rel-4 onwards): "Specification of the Subscriber Identity Module - Mobile Equipment (SIM-ME) interface".
- [92] 3GPP TS 11.12 (Ph2): "Specification of the 3 Volt Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
- [93] 3GPP TS 11.14 (R96 to R99): "Specification of the SIM application toolkit for the Subscriber Identity Module – Mobile Equipment (SIM – ME) interface".
- [94] 3GPP TS 25.331 (R99 onwards): "Radio Resource Control (RRC) protocol specification".
- [95] 3GPP TS 04.18 (R99): "Mobile radio interface layer 3 specification, Radio Resource Control Protocol". (See note)
3GPP TS 44.018 (Rel-4 onwards): "Mobile radio interface layer 3 specification, Radio Resource Control Protocol". (See note).
- [96] 3GPP TS 11.10-4 (R99): " Digital cellular telecommunications system - Mobile Station (MS) conformance specification Part 4: SIM Application Toolkit conformance specification".

NOTE: From Rel-4 onwards, references to 3GPP TS 04.08 are replaced by references to 3GPP TS 44.018 (for RR) and 3GPP TS 24.008 (for CN).

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in GSM references, ISO/IEC 9646-1 [2], ISO/IEC 9646-7 [3] and the following apply:

Implementation Conformance Statement (ICS): A statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented.

NOTE: The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: A document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

Protocol ICS (PICS): An ICS for an implementation or system claimed to conform to a given protocol specification.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|------|---|
| ICS | Implementation Conformance Statement |
| IUT | Implementation Under Test |
| PICS | Protocol Implementation Conformance Statement |
| SCS | System Conformance Statement |
| SUT | System Under Test |

4 Conformance to this PICS proforma specification

If it claims to conform to the present document, the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

A PICS which conforms to this 3GPP TS shall be a conforming PICS proforma completed in accordance with the instructions for completion given in clause A.1.

Annex A (normative): PICS proforma for GSM mobile stations

Notwithstanding the provisions of the copyright clause related to the text of the present document, The Organizational Partners of 3GPP grant that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Guidance for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in relevant specifications may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into subclauses for the following categories of information:

- instructions for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- PICS proforma tables:
 - global statement of conformance;
 - types of mobile stations;
 - support of basic services;
 - support of supplementary services;
 - mobile station features;
 - additional information.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7.

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Reference column

The reference column gives reference to the relevant GSM or 3GPP specifications.

Release column

The Release column indicates the earliest release from which the capability or option is relevant.

Status column

The following notations, defined in ISO/IEC 9646-7, are used for the status column:

| | |
|-----|---|
| M | mandatory – the capability is required to be supported. |
| O | optional – the capability may be supported or not. |
| N/A | not applicable – in the given context, it is impossible to use the capability. |
| X | prohibited (excluded) – there is a requirement not to use this capability in the given context. |
| O.i | qualified optional – for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table. |
| C.i | conditional – the requirement on the capability ("M", "O", "X" or "N/A") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." shall be used to avoid ambiguities. |

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7, are used for the support column:

| | |
|---------------|--|
| Y or y | supported by the implementation |
| N or n | not supported by the implementation |
| N/A, n/a or - | no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status) |

It is also possible to provide a comment to an answer in the space provided at the bottom of the table.

NOTE: As stated in ISO/IEC 9646-7, support for a PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the values or the ranges of values allowed.

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

References to items

For each possible item answer (answer in the support column) within the PICS proforma there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns shall be discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table A.5.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table A.6.

Comments column

This column contains a verbal description of the condition included in the applicability column.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.2.3 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

A.2.4 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.2.5 Client

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.2.6 PICS contact person

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

A.3 Identification of the protocol

This PICS proforma applies to the GSM/3GPP standards listed in the normative references clause of the present document.

A.4 PICS proforma tables

An explicit answer shall be entered, in each of the support column boxes provided, using the notation described in subclause A.1.2.

A.4.1 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the relevant GSM/3GPP specifications. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

A.4.2 Types of Mobile Stations

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the types of a mobile station given in the table below.

Table A.1: Types of Mobile Stations

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|---------|--------|---------|---------------------------|
| 1 | Standard GSM Band (P-GSM) | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | Phase 2 | O.101 | | TSPC_Type_GSM_P_Band |
| 2 | Extended GSM Band (E-GSM), (including standard Band) | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | Phase 2 | O.101 | | TSPC_Type_GSM_E_Band |
| 3 | R-GSM Band (including standard and E-GSM Band) | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | R96 | O.101 | | TSPC_Type_GSM_R_Band |
| 4 | DCS 1800 band | 3GPP TS 05.05 3GPP TS 45.005, 2 | Phase 2 | O.101 | | TSPC_Type_DCS_Band |
| 5 | Multiple-band, not simultaneously | 3GPP TS 05.05 3GPP TS 45.005, 2 | Phase 2 | O.102 | | TSPC_Type_MB_NonSimul |
| 6 | Multiple-band, simultaneously | 3GPP TS 05.05 3GPP TS 45.005, 2 | Phase 2 | O.102 | | TSPC_Type_MB_Simul |
| 7 | Small Mobile Station | 3GPP TS 05.05, 1.1 3GPP TS 45.005, 1.1 | Phase 2 | O | | TSPC_Type_SmallIMS |
| 8 | GSM Power Class 2 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | C.101 | | TSPC_Type_GSM_Class2 |
| 9 | GSM Power Class 3 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | C.101 | | TSPC_Type_GSM_Class3 |
| 10 | GSM Power Class 4 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | O | | TSPC_Type_GSM_Class4 |
| 11 | GSM Power Class 5 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | O | | TSPC_Type_GSM_Class5 |
| 12 | DCS Power Class 1 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | O | | TSPC_Type_DCS_Class1 |
| 13 | DCS Power Class 2 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | O | | TSPC_Type_DCS_Class2 |
| 14 | DCS Power Class 3 | 3GPP TS 05.05, 4.1.2 3GPP TS 45.005, 4.1.1 | Phase 2 | O | | TSPC_Type_DCS_Class3 |
| 15 | HSCSD Multislot MS | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | C.102 | | TSPC_Type_HSCSD_Multislot |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|------------------------|---|---------|--------|---------|-----------------------------|
| 16 | GSM 450 band | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | R99 | O.101 | | TSPC_Type_GSM_450_Band |
| 17 | GSM 480 band | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | R99 | O.101 | | TSPC_Type_GSM_480_Band |
| 18 | PCS 1900 band | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | R98 | O.101 | | TSPC_Type_PCS_Band |
| 19 | PCS Power Class 1 | 3GPP TS 05.05, 4 3GPP TS 45.005, 4 | R98 | O | | TSPC_Type_PCS_Class1 |
| 20 | PCS Power Class 2 | 3GPP TS 05.05, 4 3GPP TS 45.005, 4 | R98 | O | | TSPC_Type_PCS_Class2 |
| 21 | PCS Power Class 3 | 3GPP TS 05.05, 4 3GPP TS 45.005, 4 | R98 | O | | TSPC_Type_PCS_Class3 |
| 22 | Multislot Class1 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class1 |
| 23 | Multislot Class2 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class2 |
| 24 | Multislot Class3 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class3 |
| 25 | Multislot Class4 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class4 |
| 26 | Multislot Class5 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class5 |
| 27 | Multislot Class6 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class6 |
| 28 | Multislot Class7 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class7 |
| 29 | Multislot Class8 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class8 |
| 30 | Multislot Class9 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class9 |
| 31 | Multislot Class10 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_Class10 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|------------------------|---|---------|--------|---------|---------------------------------|
| 32 | Multislot Class11 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class11 |
| 33 | Multislot Class12 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class12 |
| 34 | Multislot Class13 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class13 |
| 35 | Multislot Class14 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class14 |
| 36 | Multislot Class15 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class15 |
| 37 | Multislot Class16 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class16 |
| 38 | Multislot Class17 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class17 |
| 39 | Multislot Class18 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R96 | O | | TSPC_Type_Multislot_ Class18 |
| 40 | Multislot Class19 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class19 |
| 41 | Multislot Class20 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class20 |
| 42 | Multislot Class21 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class21 |
| 43 | Multislot Class22 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class22 |
| 44 | Multislot Class23 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class23 |
| 45 | Multislot Class24 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class24 |
| 46 | Multislot Class25 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class25 |
| 47 | Multislot Class26 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class26 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|--------------|--------|---------|---|
| 48 | Multislot Class27 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class27 |
| 49 | Multislot Class28 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class28 |
| 50 | Multislot Class29 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_Multislot_ Class29 |
| 51 | GPRS Multislot operation | 3GPP TS 02.60 3GPP TS 22.060 | R97 | C.103 | | TSPC_Type_GPRS_M ultislot_operation |
| 52 | EGPRS capable of 8PSK in Uplink, of all Multislot classes | 3GPP TS 04.60 3GPP TS 44.060 | R99 | O | | TSPC_Type_EGPRS_ 8PSK_uplink |
| 53 | GSM 700 band | 3GPP TS 45.005, 2 | Release 4 | O.101 | | TSPC_Type_GSM_70 0_Band |
| 54 | GSM 750 band | 3GPP TS 45.005, 2 | Release 4 | O.101 | | TSPC_Type_GSM_75 0_Band |
| 55 | GSM 850 band | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | R99 | O.101 | | TSPC_Type_GSM_85 0_Band |
| 56 | Support of UTRAN Radio Access Technology | 3GPP TS 25.301 | R99 | O | | TSPC_Type_UTRAN |
| 57 | Support of GPRS Multislot class on the uplink | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | C.105 | | TSPC_Type_GPRS_M ultislot_uplink |
| 58 | Support of COMPACT | 3GPP TS 05.08 3GPP TS 45.008 | R99 | O | | TSPC_COMPACT |
| 59 | DTM/GPRS Multislot Class 1 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | C.107 | | TSPC_DTM_GPRS_M ultislot_Class_1 |
| 60 | DTM/GPRS Multislot Class 5 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | C.108 | | TSPC_DTM_GPRS_M ultislot_Class_5 |
| 61 | DTM/GPRS Multislot Class 9 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_GPRS_M ultislot_Class_9 |
| 62 | Support of singleslot allocation in DTM/GPRS | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_GPRS_Si ngleslot_Allocation |
| 63 | Support of UTRAN FDD | 3GPP TS 25.301 | R99 | O | | TSPC_Type_UTRAN_ FDD |
| 64 | Support of UTRAN TDD | 3GPP TS 25.301 | R99 | O | | TSPC_Type_UTRAN_ TDD |
| 65 | Support of Conventional GPS | 3GPP 03.71 | R98 | O | | TSPC_Conv-GPS |
| 66 | EGPRS Multislot operation | 3GPP TS 02.60 3GPP TS 22.060 | R99 | C.104 | | TSPC_Type_EGPRS_ Multislot_operation |
| 67 | GPRS Multislot Class1 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class1 |
| 68 | GPRS Multislot Class2 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class2 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|------------------------|---|---------|--------|---------|--------------------------------------|
| 69 | GPRS Multislot Class3 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class3 |
| 70 | GPRS Multislot Class4 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class4 |
| 71 | GPRS Multislot Class5 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class5 |
| 72 | GPRS Multislot Class6 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class6 |
| 73 | GPRS Multislot Class7 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class7 |
| 74 | GPRS Multislot Class8 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class8 |
| 75 | GPRS Multislot Class9 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class9 |
| 76 | GPRS Multislot Class10 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class10 |
| 77 | GPRS Multislot Class11 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class11 |
| 78 | GPRS Multislot Class12 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class12 |
| 79 | GPRS Multislot Class13 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class13 |
| 80 | GPRS Multislot Class14 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class14 |
| 81 | GPRS Multislot Class15 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class15 |
| 82 | GPRS Multislot Class16 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class16 |
| 83 | GPRS Multislot Class17 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class17 |
| 84 | GPRS Multislot Class18 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class18 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|------------------------|---|---------|--------|---------|--------------------------------------|
| 85 | GPRS Multislot Class19 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class19 |
| 86 | GPRS Multislot Class20 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class20 |
| 87 | GPRS Multislot Class21 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class21 |
| 88 | GPRS Multislot Class22 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class22 |
| 89 | GPRS Multislot Class23 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class23 |
| 90 | GPRS Multislot Class24 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class24 |
| 91 | GPRS Multislot Class25 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class25 |
| 92 | GPRS Multislot Class26 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class26 |
| 93 | GPRS Multislot Class27 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class27 |
| 94 | GPRS Multislot Class28 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class28 |
| 95 | GPRS Multislot Class29 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R97 | O | | TSPC_Type_GPRS_M ultislot_Class29 |
| 96 | EGPRS Multislot Class1 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class1 |
| 97 | EGPRS Multislot Class2 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class2 |
| 98 | EGPRS Multislot Class3 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class3 |
| 99 | EGPRS Multislot Class4 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class4 |
| 100 | EGPRS Multislot Class5 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class5 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|-------------------------|---|---------|--------|---------|---------------------------------------|
| 101 | EGPRS Multislot Class6 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class6 |
| 102 | EGPRS Multislot Class7 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class7 |
| 103 | EGPRS Multislot Class8 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class8 |
| 104 | EGPRS Multislot Class9 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class9 |
| 105 | EGPRS Multislot Class10 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class10 |
| 106 | EGPRS Multislot Class11 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class11 |
| 107 | EGPRS Multislot Class12 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class12 |
| 108 | EGPRS Multislot Class13 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class13 |
| 109 | EGPRS Multislot Class14 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class14 |
| 110 | EGPRS Multislot Class15 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class15 |
| 111 | EGPRS Multislot Class16 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class16 |
| 112 | EGPRS Multislot Class17 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class17 |
| 113 | EGPRS Multislot Class18 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class18 |
| 114 | EGPRS Multislot Class19 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class19 |
| 115 | EGPRS Multislot Class20 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class20 |
| 116 | EGPRS Multislot Class21 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class21 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|--------------------------|---|---------|--------|---------|---------------------------------------|
| 117 | EGPRS Multislot Class22 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class22 |
| 118 | EGPRS Multislot Class23 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class23 |
| 119 | EGPRS Multislot Class24 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class24 |
| 120 | EGPRS Multislot Class25 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class25 |
| 121 | EGPRS Multislot Class26 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class26 |
| 122 | EGPRS Multislot Class27 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class27 |
| 123 | EGPRS Multislot Class28 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class28 |
| 124 | EGPRS Multislot Class29 | 3GPP TS 05.02, B.1 3GPP TS 45.002, B.1 | R99 | O | | TSPC_Type_EGPRS_ Multislot_Class29 |
| 125 | GSM 850 Power Class 2 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | C.101 | | TSPC_Type_GSM_85 0_Class2 |
| 126 | GSM 850 Power Class 3 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | C.101 | | TSPC_Type_GSM_85 0_Class3 |
| 127 | GSM 850 Power Class 4 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_85 0_Class4 |
| 128 | GSM 850 Power Class 5 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_85 0_Class5 |
| 129 | 8-PSK GSM Power Class E1 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_Cla ssE1 |
| 130 | 8-PSK GSM Power Class E2 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_Cla ssE2 |
| 131 | 8-PSK GSM Power Class E3 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_Cla ssE3 |
| 132 | 8-PSK DCS Power Class E1 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_DCS_Cla ssE1 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|---------|--------|---------|--|
| 133 | 8-PSK DCS Power Class E2 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_DCS_Cla ssE2 |
| 134 | 8-PSK DCS Power Class E3 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_DCS_Cla ssE3 |
| 135 | 8-PSK PCS Power Class E1 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_PCS_Cla ssE1 |
| 136 | 8-PSK PCS Power Class E2 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_PCS_Cla ssE2 |
| 137 | 8-PSK PCS Power Class E3 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_PCS_Cla ssE3 |
| 138 | 8-PSK GSM 850 Power Class E1 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_85 0_ClassE1 |
| 139 | 8-PSK GSM 850 Power Class E2 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_85 0_ClassE2 |
| 140 | 8-PSK GSM 850 Power Class E3 | 3GPP TS 05.05, 4.1.1 3GPP TS 45.005, 4.1.1 | R99 | O | | TSPC_Type_GSM_85 0_ClassE3 |
| 141 | GSM850 and GSM1800 Band Interworking | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | Phase 2 | O | | TSPC_GSM850_GSM 1800_Interworking |
| 142 | GSM900 and GSM1900 Band Interworking | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | Phase 2 | O | | TSPC_GSM900_GSM 1900_Interworking |
| 143 | GSM850 and GSM900 Band Interworking | 3GPP TS 05.05, 2 3GPP TS 45.005, 2 | Phase 2 | O | | TSPC_GSM850_GSM 900_Interworking |
| 144 | DTM/EGPRS Multislot Class 1 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_EGPRS_ Multislot_Class_1 |
| 145 | DTM/EGPRS Multislot Class 5 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_EGPRS_ Multislot_Class_5 |
| 146 | DTM/EGPRS Multislot Class 9 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_EGPRS_ Multislot_Class_9 |
| 147 | Support of singleslot allocation in DTM/EGPRS | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_EGPRS_ Singleslot_Allocation |
| 148 | DTM/GPRS Multislot Class 11 | 3GPP TS 05.02, 6.4 3GPP TS 45.002, 6.4 | R99 | O | | TSPC_DTM_GPRS_M ultislot_Class_11 |
| 149 | GPRS Multislot Class30 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class30 |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|------|-------------------------|------------------------|---------|--------|---------|---------------------------------------|
| 150 | GPRS Multislot Class31 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class31 |
| 151 | GPRS Multislot Class32 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class32 |
| 152 | GPRS Multislot Class33 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class33 |
| 153 | GPRS Multislot Class34 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class34 |
| 154 | GPRS Multislot Class35 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class35 |
| 155 | GPRS Multislot Class36 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class36 |
| 156 | GPRS Multislot Class37 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class37 |
| 157 | GPRS Multislot Class38 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class38 |
| 158 | GPRS Multislot Class39 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class39 |
| 159 | GPRS Multislot Class40 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class40 |
| 160 | GPRS Multislot Class41 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class41 |
| 161 | GPRS Multislot Class42 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class42 |
| 162 | GPRS Multislot Class43 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class43 |
| 163 | GPRS Multislot Class44 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class44 |
| 164 | GPRS Multislot Class45 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_GPRS_M ultislot_Class45 |
| 165 | EGPRS Multislot Class30 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class30 |
| 166 | EGPRS Multislot Class31 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class31 |
| 167 | EGPRS Multislot Class32 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class32 |
| 168 | EGPRS Multislot Class33 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class33 |
| 169 | EGPRS Multislot Class34 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class34 |
| 170 | EGPRS Multislot Class35 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class35 |
| 171 | EGPRS Multislot Class36 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class36 |
| 172 | EGPRS Multislot Class37 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class37 |
| 173 | EGPRS Multislot Class38 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class38 |
| 174 | EGPRS Multislot Class39 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class39 |
| 175 | EGPRS Multislot Class40 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class40 |
| 176 | EGPRS Multislot Class41 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class41 |
| 177 | EGPRS Multislot Class42 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class42 |
| 178 | EGPRS Multislot Class43 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class43 |
| 179 | EGPRS Multislot Class44 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class44 |
| 180 | EGPRS Multislot Class45 | 3GPP TS 45.002, B.1 | Rel-5 | O | | TSPC_Type_EGPRS_ Multislot_Class45 |
| 181 | void | | | | | |
| 182 | GSM 710 band | 3GPP TS 45.005, 2 | Rel-7 | O | | TSPC_Type_GSM_71 0_Band |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|-------|---|------------------------|---------|---|---------|-----------------------------------|
| 183 | T GSM 810 band | 3GPP TS 45.005, 2 | Rel-7 | O | | TSPC_Type_T_GSM_810_Band |
| 184 | DTM/EGPRS Multislot Class 11 | 3GPP TS 45.002, 6.4 | Rel-4 | O | | TSPC_DTM_EGPRS_Multislot_Class_11 |
| 185 | T-GSM 380 band | 3GPP TS 45.005, 2 | Rel-6 | O | | TSPC_Type_T_GSM_380_Band |
| 186 | T-GSM 410 band | 3GPP TS 45.005, 2 | Rel-6 | O | | TSPC_Type_T_GSM_410_Band |
| 187 | T-GSM 900 band | 3GPP TS 45.005, 2 | Rel-6 | O | | TSPC_Type_T_GSM_900_Band |
| 188 | EGPRS Multislot Operation in Uplink Direction | 3GPP TS 45.002, B.1 | R99 | C.111 | | TSPC_EGPRS_Multislot_Uplink |
| O.101 | At least one of these items shall be supported | | | | | |
| O.102 | At least two of the following items shall be supported: A.1/1 OR A.1/2 OR A.1/3 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/53 OR A.1/54 OR A.1/55 | | | | | |
| O.103 | Void | | | | | |
| C.101 | IF A.1/7 THEN X ELSE O | | | -- TSPC_Type_SmallMS | | |
| C.102 | IF (A.1/22 OR A.1/23 OR A.1/24 OR A.1/25 OR A.1/26 OR A.1/27 OR A.1/28 OR A.1/29 OR A.1/30 OR A.1/31 OR A.1/32 OR A.1/33 OR A.1/34 OR A.1/35 OR A.1/36 OR A.1/37 OR A.1/38 OR A.1/39) THEN M ELSE N/A | | | -- (TSPC_Type_Multislot_Class1 OR ...OR TSPC_Type_Multislot_Class18) | | |
| C.103 | IF A.2/41 AND (A.1/67 OR A.1/68 OR A.1/69 OR A.1/70 OR A.1/71 OR A.1/72 OR A.1/73 OR A.1/74 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95 OR A.1/149 OR A.1/150 OR A.1/151 OR A.1/152 OR A.1/153 OR A.1/154 OR A.1/155 OR A.1/156 OR A.1/157 OR A.1/158 OR A.1/159 OR A.1/160 OR A.1/161 OR A.1/162 OR A.1/163 OR A.1/164) THEN M ELSE N/A | | | -- (TSPC_Type_GPRS_Multislot_Class1 OR ...OR TSPC_Type_GPRS_Multislot_Class45) AND TSPC_GPRS | | |
| C.104 | IF A.2/42 AND (A.1/96 OR A.1/97 OR A.1/98 OR A.1/99 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/103 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124 OR A.1/165 OR A.1/166 OR A.1/167 OR A.1/168 OR A.1/169 OR A.1/170 OR A.1/171 OR A.1/172 OR A.1/173 OR A.1/174 OR A.1/175 OR A.1/176 OR A.1/177 OR A.1/178 OR A.1/179 OR A.1/180) THEN M ELSE N/A | | | -- (TSPC_Type_EGPRS_Multislot_Class1 OR ...OR TSPC_Type_EGPRS_Multislot_Class45) AND TSPC_EGPRS | | |
| C.105 | IF A.1/51 THEN O ELSE N/A | | | -- TSPC_Type_GPRS_Multislot_uplink | | |
| C.106 | VOID | | | VOID | | |
| C.107 | IF A.1/62 THEN M ELSE N/A | | | -- TSPC_DTM_GPRS_Singleslot_Allocation | | |
| C.108 | IF A.2/62 THEN M ELSE N/A | | | -- TSPC_DTM_GPRS | | |
| C.109 | Void | | | | | |
| C.110 | Void | | | | | |

| Item | Type of Mobile Station | Ref. | Release | Status | Support | Mnemonic |
|-----------|---|------|---------|--------|------------------|---|
| C.111 | IF A.2/42 AND (A.1/98 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124 OR A.1/166 OR A.1/167 OR A.1/168 OR A.1/169 OR A.1/171 OR A.1/172 OR A.1/173 OR A.1/174 OR A.1/176 OR A.1/177 OR A.1/178 OR A.1/179 OR A.1/180) THEN M ELSE N/A | | | -- | TSPC_EGPRS AND (| TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR TSPC_Type_EGPRS_Multislot_Class11 OR TSPC_Type_EGPRS_Multislot_Class12 OR TSPC_Type_EGPRS_Multislot_Class13 OR TSPC_Type_EGPRS_Multislot_Class14 OR TSPC_Type_EGPRS_Multislot_Class15 OR TSPC_Type_EGPRS_Multislot_Class16 OR TSPC_Type_EGPRS_Multislot_Class17 OR TSPC_Type_EGPRS_Multislot_Class18 OR TSPC_Type_EGPRS_Multislot_Class19 OR TSPC_Type_EGPRS_Multislot_Class20 OR TSPC_Type_EGPRS_Multislot_Class21 OR TSPC_Type_EGPRS_Multislot_Class22 OR TSPC_Type_EGPRS_Multislot_Class23 OR TSPC_Type_EGPRS_Multislot_Class24 OR TSPC_Type_EGPRS_Multislot_Class25 OR TSPC_Type_EGPRS_Multislot_Class26 OR TSPC_Type_EGPRS_Multislot_Class27 OR TSPC_Type_EGPRS_Multislot_Class28 OR TSPC_Type_EGPRS_Multislot_Class29 OR TSPC_Type_EGPRS_Multislot_Class31 OR TSPC_Type_EGPRS_Multislot_Class32 OR TSPC_Type_EGPRS_Multislot_Class33 OR TSPC_Type_EGPRS_Multislot_Class34 OR TSPC_Type_EGPRS_Multislot_Class36 OR TSPC_Type_EGPRS_Multislot_Class37 OR TSPC_Type_EGPRS_Multislot_Class38 OR TSPC_Type_EGPRS_Multislot_Class39 OR TSPC_Type_EGPRS_Multislot_Class41 OR TSPC_Type_EGPRS_Multislot_Class42 OR TSPC_Type_EGPRS_Multislot_Class43 OR TSPC_Type_EGPRS_Multislot_Class44 OR TSPC_Type_EGPRS_Multislot_Class45) |
| Comments: | | | | | | |

Table A.1b: MS Feature Release Supported

| Item | MS Feature Release Supported | Reference | Release | Status | Support | Mnemonic | Value | |
|--------|------------------------------|---------------------------------|---------|--------|-------------------------------------|-----------------------|---|-----------|
| | | | | | | | Allowed | Supported |
| 1 | Release of GPRS supported. | 3GPP TS 02.06 3GPP TS 22.060 | R97 | C.1b01 | | TSPC_MS_GPRS_RELEASE | R97, R98, R99, Release 4, Release 5, Release 6, Release 7 | |
| 2 | Release of AMR supported. | 3GPP TS 05.09, 3.4 | R98 | C.1b02 | | TSPC_MS_AMR_RELEASE | R98, R99, Release 4, Release 5, Release 6, Release 7 | |
| 3 | Release of EGPRS supported. | 3GPP TS 02.60 3GPP TS 22.060 | R99 | C.1b03 | | TSPC_MS_EGPRS_RELEASE | R99, Release 4, Release 5, Release 6, Release 7 | |
| C.1b01 | IF A.2/41 THEN M ELSE N/A | | | | -- TSPC_GPRS | | | |
| C.1b02 | IF A.25/79 THEN M ELSE N/A | | | | -- TSPC_AddInfo_Full_rate_version_3 | | | |
| C.1b03 | IF A.2/42 THEN M ELSE N/A | | | | -- TSPC_EGPRS | | | |

A.4.3 Mobile Station Features

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the mobile station features given in the table below.

Table A.2: Mobile Station Features

| Item | Mobile Station Feature | Ref. | Release | Status | Support | Mnemonic |
|------|--|--------------------------|---------|--------|---------|--------------------------------------|
| 1 | Display of Called Number. | 3GPP TS 02.07 B.1.1 | Phase 2 | C.202 | | TSPC_Feat_DCN |
| 2 | Indication of Call Progress Signals. | 3GPP TS 02.07 B.1.2 | Phase 2 | C.204 | | TSPC_Feat_CPSind |
| 3 | Country/PLMN Indication. | 3GPP TS 02.07 B.1.3 | Phase 2 | C.202 | | TSPC_Feat_PLMNind |
| 4 | Country/PLMN Selection. | 3GPP TS 02.07 B.1.4 | Phase 2 | M | | TSPC_Feat_PLMNsel |
| 5 | Keypad. | 3GPP TS 02.07 B.1.5 | Phase 2 | O | | TSPC_Feat_Keypad |
| 6 | IMEI. | 3GPP TS 02.07 B.1.6 | Phase 2 | M | | TSPC_Feat_IMEI |
| 7 | Short Message Overflow Indication. | 3GPP TS 02.07 B.1.8 | Phase 2 | M | | TSPC_Feat_SMoverflow |
| 8 | DTE /DCE Interface. | 3GPP TS 02.07 B.1.9 | Phase 2 | O | | TSPC_Feat_DTE_DCE |
| 9 | ISDN "S" Interface. | 3GPP TS 02.07 B.1.10 | Phase 2 | O | | TSPC_Feat_Sinterface |
| 10 | International Access Function. | 3GPP TS 02.07 B.1.11 | Phase 2 | O | | TSPC_Feat_IntAccess |
| 11 | Service Indicator. | 3GPP TS 02.07 B.1.12 | Phase 2 | C.203 | | TSPC_Feat_ServInd |
| 12 | Autocalling restriction capabilities. | 3GPP TS 02.07 annex A | Phase 2 | C.205 | | TSPC_Feat_AutocallRest ric |
| 13 | Dual Tone Multi Frequency function. | 3GPP TS 02.07 B.1.15 | Phase 2 | C.201 | | TSPC_Feat_DTMF |
| 14 | Subscription Identity Management. | 3GPP TS 02.07 B.1.16 | Phase 2 | M | | TSPC_Feat_SIM |
| 15 | On/Off switch. | 3GPP TS 02.07 B.1.17 | Phase 2 | O | | TSPC_Feat_OnOff |
| 16 | Subaddress. | 3GPP TS 02.07 B.1.18 | Phase 2 | O | | TSPC_Feat_Subaddress |
| 17 | Support of Encryption A5/1. | 3GPP TS 02.07 B.1.19 | Phase 2 | M | | TSPC_Feat_A51 |
| 18 | Void | | | | | |
| 19 | Short Message Service Cell Broadcast DRX. | 3GPP TS 02.07 B.1.20 | Phase 2 | O | | TSPC_Feat_SMS_CB_D RX |
| 20 | Abbreviated Dialling. | 3GPP TS 02.07 B.3.1 | Phase 2 | O | | TSPC_Feat_AD |
| 21 | Fixed Number Dialling. | 3GPP TS 02.07 B.3.2 | Phase 2 | O | | TSPC_Feat_FND |
| 22 | Barring of Outgoing Calls. | 3GPP TS 02.07 B.3.3 | Phase 2 | O | | TSPC_Feat_BO |
| 23 | DTMF Control Digits Separator. | 3GPP TS 02.07 B.3.4 | Phase 2 | O | | TSPC_Feat_DTMF_CDS |
| 24 | Selection of Directory No in Short Messages. | 3GPP TS 02.07 B.3.5 | Phase 2 | O | | TSPC_Feat_SM_Dir |
| 25 | Last Numbers Dialed. | 3GPP TS 02.07 B.3.6 | Phase 2 | O | | TSPC_Feat_LND |
| 26 | At least one autocalling feature. | 3GPP TS 02.07 annex A | Phase 2 | O | | TSPC_Feat_Autocall |
| 27 | Alphanumeric display. | 3GPP TS 02.07 2 | Phase 2 | O | | TSPC_Feat_Alphanum_ Display |
| 28 | Other means of display. | 3GPP TS 02.07 2 | Phase 2 | O | | TSPC_Feat_Other_Mean s_of_Display |
| 29 | Speech indicator. | 3GPP TS 02.07 2 | Phase 2 | O | | TSPC_Feat_Speech_Indi cator |

| Item | Mobile Station Feature | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|---------------|--------|---------|--------------------------------|
| 30 | Support of the extended Short message cell broadcast channel | 3GPP TS 02.07 B.1.23 | R96 | O | | TSPC_Ext_SMcell_BC |
| 31 | Support of Additional Call Set-up MMI Procedures | 3GPP TS 02.07 B.1.24 | R96 | O | | TSPC_AddCall_Su_MMi_Proc |
| 32 | Void | | | | | |
| 33 | Ciphering Indicator | 3GPP TS 02.07 B.1.22(B.1.2.26) | Phase 2 (R96) | C.202 | | TSPC_Feat_Ciphering |
| 34 | Network's indication of alerting in the MS \$(NI Alert in MS)\$ | 3GPP TS 02.07 B.1.27 | R96 | O | | TSPC_Feat_NI_AlertinMS |
| 35 | ME-SIM lock | 3GPP TS 02.07 B.3.7 | R96 | O | | TSPC_SIM_Lock |
| 36 | Service Dialling Numbers | 3GPP TS 02.07 B.3.8 | R96 | O | | TSPC_Service_No |
| 37 | Extended timing advance | 3GPP TS 05.10, 5.5 | R99 | C.206 | | TSPC_Feat_Ext_TA |
| 38 | Support of SoLSA | 3GPP TS 02.43, 3GPP TS 22.043 B.1.27 3GPP TS 03.73 3GPP TS 23.073 | R98 | O | | TSPC_SoLSA |
| 39 | Audible Indication of Service Tones | 3GPP TS 02.07, B.1.27 | R96 | O | | TSPC_Feat_audible_tone |
| 40 | Autocalling_Cause 27 Implemented in Cat 3 | 3GPP TS 02.07 annex A | Phase 2 | O | | TSPC_Feat_Cause27Cat3 |
| 41 | Support of GPRS | 3GPP TS 02.60 3GPP TS 22.060 | R97 | O | | TSPC_GPRS |
| 42 | Support of EGPRS | 3GPP TS 02.60 3GPP TS 22.060 | R99 | O | | TSPC_EGPRS |
| 43 | Support of GPRS Encryption | 3GPP TS 02.60 3GPP TS 22.060 | R98 | C.207 | | TSPC_GPRS_Encryp |
| 44 | Control of Supplementary Services | 3GPP TS 02.07, 2 | Phase 2 | O | | TSPC_Control_SS |
| 45 | Short message | 3GPP TS 02.07, 2 | Phase 2 | O | | TSPC_Supp_SM |
| 46 | Emergency calls capabilities | 3GPP TS 02.07, B.1.14 | Phase 2 | C.211 | | TSPC_Emergency_call_capability |
| 47 | GPRS operation mode class A | 3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5 | R97 | C.209 | | TSPC_operation_mode_A |
| 48 | GPRS operation mode class B | 3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5 | R97 | C.209 | | TSPC_operation_mode_B |
| 49 | GPRS operation mode class C | 3GPP TS 02.60, 5.4.5 3GPP TS 22.060, 5.4.5 | R97 | C.209 | | TSPC_operation_mode_C |
| 50 | MS supporting SMS over GPRS | 3GPP TS 22.060, 5.4 | R99 | O | | TSPC_SMS_over_GPRS |
| 51 | void | | | | | |
| 52 | Void | | | | | |
| 53 | Support of ECSD | 3GPP TS 05.08, B.6 3GPP TS 45.008, B.6 | R99 | O | | TSPC_ECSD |
| 54 | GPRS test mode A | 3GPP TS 04.14 5.4 | R97 | C.208 | | TSPC_GPRS_Testmode_A |
| 55 | GPRS test mode B | 3GPP TS 04.14 5.4 | R97 | C.208 | | TSPC_GPRS_Testmode_B |
| 56 | EGPRS test mode | 3GPP TS 04.14 | | C.210 | | TSPC_EGPRS_Testmode |

| Item | Mobile Station Feature | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|------------------------|--------|---------|---|
| 57 | Support of MS-Assisted E-OTD | 3GPP TS 03.71 7.6.1 | R98 | O | | TSPC_EOTD_ASSIST |
| 58 | Non-zero value of Non_DRX_Timer | 3GPP TS 04.60 | R97 | C.208 | | TSPC_non_zero_Non_D RX_Timer |
| 59 | Support of MS-Based GPS | 3GPP TS 03.71 7.6.1 | R98 | O | | TSPC_A-GPS_Based |
| 60 | Support of MS-Assisted GPS | 3GPP TS 03.71 7.6.1 | R98 | O | | TSPC_A-GPS_Assist |
| 61 | Privacy Option Supported | 3GPP TS 03.71 7.6.1 | R98 | O | | TSPC_PRIVACY |
| 62 | Support of DTM/GPRS | 3GPP TS 24.008 10.5.1.7 | R99 | C.212 | | TSPC_DTM_GPRS |
| 63 | Support MS Assisted EOTD Performance for GSMK | 3GPP TS 05.05 Annex I | R98 | O | | TSPC_EOTD_ASSIST AND TSPC_PERF_GSMK |
| 64 | Support MS Assisted EOTD Performance for 8PSK | 3GPP TS 05.05 Annex I | R99 | O | | TSPC_EOTD_ASSIST AND TSPC_PERF_8PSK |
| 65 | Support of EGPRS Packet Access enhancement | 3GPP TS 04.18 3.5.2.1.2 3GPP TS 04.60 7.1.2.1 | R99 only | O | | TSPC_EGPRS_ENHAN C |
| 66 | void | | | | | |
| 67 | Support of MT SMS over GPRS | 3GPP TS 22.060, 5.4 | R99 | O | | TSPC_MT_SMS_over_G PRS |
| 68 | void | | | | | |
| 69 | Support of DTM/EGPRS | 3GPP TS 24.008 10.5.1.7 | R99 | C.213 | | TSPC_DTM_EGPRS |
| 70 | Support of Extended dynamic allocation | 3GPP TS 45.002, B.1 | R99 | C.214 | | TSPC_Extended_Dynam ic_Allocation |
| 71 | Support of GERAN | 3GPP TS 44.318 | Rel-6 | O | | TSPC_GERAN |
| 72 | Support of GERAN FEATURE PACKAGE 1 | 3GPP TS 44.060 5.5.1.1a, 9.3.1b.1 | Rel-4 | M | | TSPC_GERAN_FEATU RE_PACKAGE_1 |
| 73 | Support of Encryption A5/3 | 3GPP TS 43.020 | Rel-6 | M | | TSPC_Feat_A53 |
| 74 | Support of Fine Time Assistance | 3GPP TS 44.031 A.4.2.4 | Rel-4 | C.215 | | TSPC_Fine_Time_Assist |
| 75 | Support of Encryption GEA2 | 3GPP TS 43.020 | R97 | O | | TSPC_Feat_GEA2 |
| 76 | Support of Encryption GEA3 | 3GPP TS 43.020 | Rel-6 | M | | TSPC_Feat_GEA3 |
| 77 | Use of R99 Emergency numbers | 3GPP TS 22.101 8 | Phase2 up to R98 | O | | TSPC_R99_Emerg |
| 78 | Support of GERAN FEATURE PACKAGE 2 | 3GPP TS 45.008 | Rel-5 | O | | TSPC_GERAN_FEATU RE_PACKAGE_2 |
| 79 | Support of GERAN to UTRAN CS Handover | 3GPP TS 44.318 | Rel-6 | O | | TSPC_GERAN_TO_UTRA N_CS_Handover |
| 80 | Support of UTRAN to GERAN CS Handover | 3GPP TS 44.318 | Rel-6 | O | | TSPC_UTRAN_TO_GA N_CS_Handover |
| 81 | Support of Enhanced DTM CS | 3GPP TS 43.055 | Rel-6 | O | | TSPC_Enhanced_DTM_ CS |
| 82 | Support of PS Handover | 3GPP TS 43.129 | Rel-6 | O | | TSPC_PS_Handover |

| Item | Mobile Station Feature | Ref. | Release | Status | Support | Mnemonic |
|-------|--|------|---------|--------|--|----------|
| C.201 | IF A.3/1 OR A.3/2 OR A.4/20 OR A.4/21 THEN M ELSE N/A | | | -- | TSPC_Serv_TS11 OR TSPC_Serv_TS12 OR TSPC_Serv_BS61 OR TSPC_Serv_BS81 | |
| C.202 | IF A.2/27 THEN M ELSE N/A | | | -- | TSPC_Feat_Alphanum_Display | |
| C.203 | IF A.2/27 OR A.2/28 THEN M ELSE N/A | | | -- | TSPC_AlphaNum_Display OR TSPC_Other_Means_of_Display | |
| C.204 | IF A.2/29 THEN M ELSE N/A | | | -- | TSPC_Speech_Indicator | |
| C.205 | IF A.2/26 OR A.2/40 THEN M ELSE N/A | | | -- | TSPC_Feat_Autocall | |
| C.206 | IF A.1/16 OR A.1/17 THEN M ELSE N/A | | | -- | TSPC_Feat_Ext_TA | |
| C.207 | IF A.2/41 OR A.2/42 THEN M ELSE N/A | | | -- | TSPC_GPRS OR TSPC_EGPRS | |
| C.208 | IF A.2/41 THEN O ELSE N/A | | | -- | TSPC_GPRS | |
| C.209 | IF A.2/41 or A.2/42 THEN at least one of these items shall be supported ELSE N/A | | | -- | TSPC_GPRS OR TSPC_EGPRS | |
| C.210 | IF A.2/42 THEN O ELSE N/A | | | -- | TSPC_EGPRS | |
| C.211 | IF A.3/2 THEN M ELSE N/A | | | -- | TSPC_Serv_TS12 | |
| C.212 | IF A.2/41 THEN O ELSE N/A | | | -- | TSPC_GPRS | |
| C.213 | IF A.2/42 THEN O ELSE N/A | | | -- | TSPC_EGPRS | |
| C.214 | IF (A.2/41 AND A.1/51) OR (A.2/42 AND A.1/66) THEN O ELSE N/A | | | -- | (TSPC_GPRS AND TSPC_Type_GPRS_Multislot_operation) OR (TSPC_EGPRS AND TSPC_Type_EGPRS_Multislot_operation) | |
| C.215 | IF A.2/59 OR A.2/60 THEN O ELSE N/A | | | -- | TSPC_A-GPS_Based OR TSPC_A-GPS_Assist | |

A.4.4 Teleservices

The supplier of the implementation shall state the support of the implementation for each of the teleservices given in the table below.

Table A.3: Teleservices

| Item | Teleservice | Ref. | Release | Status | Support | Mnemonic |
|-------|--|--|---------|-------------------|---------|----------------------|
| 1 | Telephony. | 3GPP TS 02.03 A.1.1 3GPP TS 22.003, A.1.1 | Phase 2 | O | | TSPC_Serv_TS11 |
| 2 | Emergency Call. | 3GPP TS 02.03 A.1.2 3GPP TS 22.003, A.1.2 | Phase 2 | C.301 | | TSPC_Serv_TS12 |
| 3 | Short Message MT/PP. | 3GPP TS 02.03 A.1.3.1 3GPP TS 22.003, A.1.3.1 | Phase 2 | O | | TSPC_Serv_TS21 |
| 4 | Short Message MO/PP. | 3GPP TS 02.03 A.1.3.2 3GPP TS 22.003, A.1.3.2 | Phase 2 | O | | TSPC_Serv_TS22 |
| 5 | SMS Cell Broadcast. | 3GPP TS 02.03 A.1.3.3 3GPP TS 22.003, A.1.3.3 | Phase 2 | O | | TSPC_Serv_TS23 |
| 6 | Teleservice Alternate Speech and G3 fax. | 3GPP TS 02.03 A.1.4 3GPP TS 22.003, A.1.4 | Phase 2 | O | | TSPC_Serv_TS61 |
| 7 | Teleservice Automatic G3 fax. | 3GPP TS 02.03 A.1.5 3GPP TS 22.003, A.1.5 | Phase 2 | O | | TSPC_Serv_TS62 |
| 8 | Voice Group Call Service (VGCS) | 3GPP TS 02.03 A.1.6 3GPP TS 22.003, A.1.6 | R96 | O | | TSPC_Serv_TS91 |
| 9 | Voice Broadcast Service (VBS) | 3GPP TS 02.03 A.1.7 3GPP TS 22.003, A.1.7 | R96 | O | | TSPC_Serv_TS92 |
| 10 | SMS description | 3GPP TS 02.03 A.1.3.4 3GPP TS 22.003, A.1.3.4 | R96 | O | | TSPC_SMS_description |
| C.301 | IF A.3/1 THEN M ELSE O | | | -- TSPC_Serv_TS11 | | |

Comments:

A.4.5 Bearer Services

The supplier of the implementation shall state the support of the implementation for each of the bearer services given in the table below.

Table A.4: Bearer Services

| Item | Bearer Service | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|---------|--------|---------|----------------|
| 1 | Data circuit duplex async. 300 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS21 |
| 2 | Data circuit duplex async. 1 200 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS22 |
| 3 | Data circuit duplex async. 1 200/75 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS23 |
| 4 | Data circuit duplex async. 2 400 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS24 |
| 5 | Data circuit duplex async. 4 800 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS25 |
| 6 | Data circuit duplex async. 9 600 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS26 |
| 7 | Data circuit duplex sync. 1 200 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS31 |
| 8 | Data circuit duplex sync. 2 400 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS32 |
| 9 | Data circuit duplex sync. 4 800 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS33 |
| 10 | Data circuit duplex sync. 9 600 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS34 |
| 11 | PAD Access 300 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS41 |
| 12 | PAD Access 1 200 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS42 |
| 13 | PAD Access 1 200/75 bits/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS43 |
| 14 | PAD Access 2 400 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS44 |
| 15 | PAD Access 4 800 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS45 |
| 16 | PAD Access 9 600 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS46 |
| 17 | Packet Access 2 400 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS51 |
| 18 | Packet Access 4 800 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS52 |
| 19 | Packet Access 9 600 bit/s. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS53 |

| Item | Bearer Service | Ref. | Release | Status | Support | Mnemonic |
|------|--------------------------|---|---------|--------|---------|----------------|
| 20 | Alternate Speech/Data. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS61 |
| 21 | Speech Followed by Data. | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | Phase 2 | O | | TSPC_Serv_BS81 |
| 22 | GPRS | 3GPP TS 02.02 3 3GPP TS 22.002, 3 | R97 | O | | TSPC_Serv_BS70 |
| 23 | Bluetooth data rate | 3GPP TS 44.318 | Rel-6 | O | | TSPC_Serv_BS71 |
| 24 | WLAN data rate | 3GPP TS 44.318 | Rel-6 | O | | TSPC_Serv_BS72 |

Comments:

A.4.6 Supplementary Services

The supplier of the implementation shall state the support of the implementation for each of the supplementary services given in the table below.

Table A.5: Supplementary Services

Prerequisite: A.25/29 -- TSPC_AddInfo_SS (3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1, (3GPP TS 22.004 4)).

| Item | Supplementary Service | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|---------|--------|---------|---------------------|
| 1 | Calling Line Identification Presentation. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_CLIP |
| 2 | Calling Line Identification Restriction. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_CLIR |
| 3 | Connected Line Identification Presentation. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_COLP |
| 4 | Connected Line Identification Restriction. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_COLR |
| 5 | Call Forwarding Unconditional. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_CFU |
| 6 | Call Forwarding on Mobile Subscriber Busy. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_CFB |
| 7 | Call Forwarding on No Reply. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_CFNRey |
| 8 | Call Forwarding on Mobile Subscriber Not Reachable. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_CFNRey |
| 9 | Call Waiting. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_CW |
| 10 | Call Hold. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_HOLD |
| 11 | Multi Party Service. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_MPTY |
| 12 | Closed User Group. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_CUG |
| 13 | Advice of Charge (Information). | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_AoCI |
| 14 | Advice of Charge (Charging). | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_Serv_SS_AoCC |

| Item | Supplementary Service | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|---------|--------|---------|---------------------------------|
| 15 | Barring of All Outgoing Calls. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_BAOC |
| 16 | Barring of Outgoing International Calls. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_BOIC |
| 17 | Barring of Outgoing International Calls except those directed to the Home PLMN Country. | 3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_BOICexHC |
| 18 | Barring of All Incoming Calls. | 3GPP TS 02.04 4, 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_BAIC |
| 19 | Barring of Incoming Calls when Roaming Outside the Home PLMN Country. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | M | | TSPC_Serv_SS_BICRoam |
| 20 | Unstructured SS Data. | 3GPP TS 02.30, 4.5.2.2, 3GPP TS 02.07 B.2.1 | Phase 2 | O | | TSPC_Serv_SS_unstructured |
| 21 | enhanced Multi-Level Precedence and Pre-emption service (eMLPP) | 3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.67, 3.1 3GPP TS 22.067, 43.1 | R96 | O | | TSPC_Serv_SS_eMLPP |
| 22 | Call Deflection | 3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.72, 3.2 3GPP TS 22.072, 3.2 | R96 | O | | TSPC_Serv_SS_CD |
| 23 | User-to-User signalling | 3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.87, 5.1 3GPP TS 22.087, 5.1 | R96 | O | | TSPC_Serv_SS_UUS |
| 24 | Explicit Call Transfer | 3GPP TS 02.04 4 3GPP TS 22.004, 4 3GPP TS 02.91 3GPP TS 22.091, | R96 | O | | TSPC_Serv_SS_ECT |
| 25 | Implicit UUS1 | 3GPP TS 02.87 5.1 3GPP TS 22.087, 5.1 | R96 | O | | TSPC_Serv_SS_ImpUUS1 |
| 26 | Sending of implicit UUS1 in the ALERTING message | 3GPP TS 03.87 5.3.2 3GPP TS 23.087, 5.3.1 | R98 | O | | TSPC_Serv_SS_Send_UUS1_ALERTING |

| Item | Supplementary Service | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|-----------|--------|---------|--------------------------------|
| 27 | Sending of implicit UUS1 in the CONNECT message | 3GPP TS 03.87 5.3.2 3GPP TS 23.087, 5.3.2 | R98 | O | | TSPC_Serv_SS_Send_UUS1_CONNECT |
| 28 | Follow Me | 3GPP TS 02.94 3GPP TS 22.094, | R99 | O | | TSPC_Serv_SS_Follow Me |
| 29 | User-to-Dispatcher Information | 3GPP TS 43.068, 3.1 3GPP TS 43.069, 3.1 | Release 4 | O | | TSPC_Serv_UTDI |
| 30 | Compressed User-to-Dispatcher | 3GPP TS 43.068 4.2.7 3GPP TS 43.069, 4.2.7 | Release 4 | O | | TSPC_Serv_Compr_UTDI |
| 31 | Completion of Calls to Busy SS | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | R97 | O | | TSPC_CCBS_SS |
| 32 | Completion of Calls to Busy Requests | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | R97 | O | | TSPC_CCBS_Req |
| 33 | Support of Private Numbering Plan SS | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | R97 | O | | TSPC_SPNP_SS |
| 34 | Support of Private Numbering Plan, Numbering Plans | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | R97 | O | | TSPC_Num_plans |
| 35 | Name Identification SS | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | R97 | O | | TSPC_CNAP |
| 36 | Void | | | | | |
| 37 | Support of MO-LR request for a position estimate | 3GPP TS 03.71, 7.13 | R98 | O | | TSPC_MOLR_POS |
| 38 | Support of MO-LR request for transfer to 3rd party | 3GPP TS 03.71, 7.13 | R98 | O | | TSPC_MOLR_3RD |
| 39 | Support of MT-LR | 3GPP TS 04.30 | R98 | O | | TSPC_MTLR |
| 40 | Support of MO-LR request for assistance data | 3GPP TS 03.71, 7.13 | R98 | O | | TSPC_MOLR_ASSIS |

Comments:

A.4.7 Bearer Capability Information

The supplier of the implementation shall state the support of possible bearer capabilities in the tables below. The allowed Bearer Capabilities are defined by diagrams given in 3GPP TS 07.01 (3GPP TS 27.001) annex 2. The support of Bearer Capabilities shall be stated by selecting supported coding of Bearer Capability Elements for each group of Bearer Capabilities associated with one diagram.

This clause provides a table for each diagram where the supplier shall state which element values are supported for the bearer capability if more than one element value is allowed. It is assumed that in many cases, all allowed combinations defined by the diagram with respect to the supported values are implemented. If this is not the case, the supplier shall state the restrictions immediately following the table. The abbreviations of element values are defined 3GPP TS 07.01(3GPP TS 27.001) table II.5. For detailed description of element values and coding, please refer to 3GPP TS 04.08 (3GPP TS 24.008), 10.5.4.5.

[Editor's note: Table A.6 to be updated according to the information in the following tables. The Releases and allowed values in brackets refer to the PICS items in brackets]

Table A.6: Groups for possible bearer capabilities

| Item | Bearer Capability Group | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|------------------|--------|---------|----------------------------|
| 1 | Bearer Service 21(20) .. 26, unrestricted digital information transfer capability. | 3GPP TS 07.01 B.1.2.1 3GPP TS 27.001, B.1.2.1 | Phase 2 (R96) | O | | TSPC_BS2x_UDI |
| 2 | Bearer Service 21(20) .. 26, 3.1 kHz audio ex-PLMN information transfer capability. | 3GPP TS 07.01 B.1.2.2 3GPP TS 27.001, B.1.2.2 | Phase 2 (R96) | O | | TSPC_BS2x_31kHz |
| 3 | Bearer Service 31(30) .. 34, unrestricted digital information transfer capability; Non-X.32 Cases (BS 31 .. BS 34). | 3GPP TS 07.01 B.1.3.1.1 3GPP TS 27.001, B.1.3.1.1 | Phase 2 (R96) | O | | TSPC_BS3x_UDI_no nX32 |
| 4 | Bearer Service 31(30) .. 34, unrestricted digital information transfer capability; X.32 Cases. | 3GPP TS 07.01 B.1.3.1.2 3GPP TS 27.001, B.1.3.1.1 | Phase 2 (R96) | O | | TSPC_BS3x_UDI_X3 2 |
| 5 | Bearer Service 31(30) .. 34, 3.1 kHz audio ex-PLMN information transfer capability; Non-X.32 Cases. | 3GPP TS 07.01 B.1.3.2.1 3GPP TS 27.001, B.1.3.2.1 | Phase 2 (R96) | O | | TSPC_BS3x_31kHz_ nonX32 |
| 6 | Bearer Service 31(30) .. 34, 3.1 kHz audio ex-PLMN information transfer capability; X.32 Cases. | 3GPP TS 07.01 B.1.3.2.2 3GPP TS 27.001, B.1.3.2.2 | Phase 2 (R96) | O | | TSPC_BS3x_31kHz_ X32 |
| 7 | Bearer Service 41(40)..46, PAD Access Asynchronous. | 3GPP TS 07.01 B.1.4 3GPP TS 27.001, B.1.5 | Phase 2 (R96) | O | | TSPC_BS4x_PAD |
| 8 | Bearer Service 51(50)..53, Data Packet Duplex Synchronous. | 3GPP TS 07.01 B.1.5 3GPP TS 27.001, B.1.5 | Phase 2 (R96) | O | | TSPC_BS5x_Packet |
| 9 | Bearer Service 61, Alternate Speech/Data, "Speech". | 3GPP TS 07.01 B.1.6.1 3GPP TS 27.001, B.1.6.1 | Phase 2 | O | | TSPC_BS61_Speech |
| 10 | Bearer Service 61, Alternate Speech/Data, .3.1 kHz audio ex-PLMN information transfer capability; Asynchronous. | 3GPP TS 07.01 B.1.6.2.1 3GPP TS 27.001, B.1.6.2.1 | Phase 2 | O | | TSPC_BS61_31kHz_ Async |
| 11 | Bearer Service 61, Alternate Speech/Data, .3.1 kHz audio ex-PLMN information transfer capability; Synchronous. | 3GPP TS 07.01 B.1.6.2.2 3GPP TS 27.001, B.1.26.2.2 | Phase 2 | O | | TSPC_BS61_31kHz_ Sync |
| 12 | Bearer Service 81, Speech followed by Data, "Speech". | 3GPP TS 07.01 B.1.7.1 3GPP TS 27.001, B.1.7.1 | Phase 2 | O | | TSPC_BS81_Speech |
| 13 | Bearer Service 81, Speech followed by Data, .3.1 kHz audio ex-PLMN information transfer capability; Asynchronous. | 3GPP TS 07.01 B.1.7.2.1 3GPP TS 27.001, B.1.7.2.1 | Phase 2 | O | | TSPC_BS81_31kHz_ Async |

| Item | Bearer Capability Group | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|---------|--------|---------|----------------------|
| 14 | Bearer Service 81, Speech followed by Data, .31 kHz audio ex-PLMN information transfer capability; Synchronous. | 3GPP TS 07.01 B.1.7.2.2 3GPP TS 27.001, B.1.7.2.2 | Phase 2 | O | | TSPC_BS81_31kHz_Sync |
| 15 | Teleservice 11..12, Speech. | 3GPP TS 07.01 B.1.8 3GPP TS 27.001, B.1.8 | Phase 2 | O | | TSPC_TS1x_Speech |
| 16 | Teleservice 61, Alternate Speech and Facsimile group 3; "Speech". | 3GPP TS 07.01 B.1.10.1 3GPP TS 27.001, B.1.8 | Phase 2 | O | | TSPC_TS61_Speech |
| 17 | Teleservice 61, Alternate Speech and Facsimile group 3; Facsimile group 3. | 3GPP TS 07.01 B.1.10.2 3GPP TS 27.001, B.1.10.2 | Phase 2 | O | | TSPC_TS61_G3FAX |
| 18 | Teleservice 62, Automatic Facsimile group 3 | 3GPP TS 07.01 1.11 3GPP TS 27.001, B.1.11 | Phase 2 | O | | TSPC_TS62_G3FAX |

Comments:

Table A.7: Bearer Service 20..26, UDI/RDI

Prerequisite: A.6/1 -- BS2x_UDI (diagram in 3GPP TS 07.01 B.1.2.1 (3GPP TS 27.001 B.1.2.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|--|--|--|---------|--------|---------|--|-----------|
| | | | | | | Allowed | Supported |
| 1 | Signalling Access Protocol (SAP). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | I.440, X.28nond | |
| 2 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 3 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | ISO6429, COPnoFICt, NAV | |
| 4 | Number of Data Bits(NDB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 7 bits, 8 bits | |
| 5 | Parity Information (NPB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | odd, even, 0, 1, none | |
| 6 | Number of Stop Bits (NSB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1 bit, 2 bits | |
| 7 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 8 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 9 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 10 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV | |
| 11 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.701 | | 9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV | |
| 12 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 13 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.702 | | 1, 2, 3, 4, NAV | |
| 10a | all allowed combinations according to 3GPP TS 07.01 B.1.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.701 IF A.7/10 AND A.25/7 THEN M ELSE N/A | | | | | | | |
| C.702 IF A.7/10 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.8: Bearer Service 20..26, 3.1 kHz

Prerequisite: A.6/2 -- BS2x_3.1kHz (diagram in 3GPP TS 07.01 B.1.2.2 (3GPP TS 27.001 B.1.2.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|--|-----------|
| | | | | | | Allowed | Supported |
| 1 | Signalling Access Protocol (SAP). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | I.440, X.28nond | |
| 2 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 3 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex A 3GPP TS 27.001, annex B | Phase 2 | M | | ISO6429, COPnoFICt, NAV | |
| 4 | Number of Data Bits (NDB). | 3GPP TS 07.01 annex B | Phase 2 | M | | 7 bits, 8 bits | |
| 5 | Parity Information (NPB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | odd, even, 0, 1, none | |
| 6 | Number of Stop Bits (NSB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1 bit, 2 bits | |
| 7 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 8 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 9 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 10 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | V.21, V.22, V.22bis, V.26ter, V.32, V.23, auto | |
| 11 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, NAV | |
| 12 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.801 | | 9.6, 14.4, 19.2, 28.8, 38.4, 43.2 | |
| 13 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|--|--|--|---------|--------|---------|---|--|
| 14 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 15 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.802 | | 1, 2, 3, 4, NAV | |
| 11a | all allowed combinations according to 3GPP TS 07.01 B.1.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.801 IF A.8/10 AND A.25/7 THEN M ELSE N/A | | | | | | | |
| C.802 IF A.8/10 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.9: Bearer Service 30..34, UDI, Non-X.32

Prerequisite: A.6/3 -- BS3x_UDI_nonX.32 (diagram in 3GPP TS 07.01 B.1.3.1.1 (3GPP TS 27.001 B.1.3.1.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|--------------------------------|--|--|---------|--------|---------|--|-----------|
| | | | | | | Allowed | Supported |
| 1 | Signalling Access Protocol (SAP). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1.440, X.21 | |
| 2 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 3 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 4 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1.2, 2.4, 4.8, 9.6 | |
| 5 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV | |
| 6 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annexB 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 7 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.901 | | 1, 2, 3, 4, NAV | |
| 5a | all allowed combinations according 3GPP TS 07.01 A2 1.3.1.1 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.901 IF A.9/5 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.10: Bearer Service 30..34, UDI, X-32

Prerequisite: A.6/4 -- BS3x_UDI_X.32 (diagram in 3GPP TS 07.01 B.1.3.1.2 (3GPP TS 27.001 B.1.3.1.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|---|--|--|---------------|--------|---------|--|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 2 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 3 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 2.4, 4.8, 9.6 | |
| 4 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 (R96) | M | | X.25, (X.75) | |
| 5 | Rate Adaptation (RA) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 (R96) | O | | X.31Flag, (V.120) | |
| 6 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV | |
| 7 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1001 | | 9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57, NAV | |
| 8 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 9 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 10 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1001 | | 1, 2, 3, 4, NAV | |
| 4a | all allowed combinations according to 3GPP TS 07.01 B.1.3.1.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.1001 IF A.10/6 AND A.25/7 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.10a: Bearer Service 30..34, UDI, 48 kbps and 56 kbps bit transparent

Prerequisite: A.6/4 -- BS3x_UDI_X.32[tbd] (diagram in 3GPP TS 07.01 B.1.3.1.4 (3GPP TS 27.001 B.1.3.1.4)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|-------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Signalling Access Protocol (SAP). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | I.440, X.21 | |
| 2 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 48, 56 | |
| 3 | all allowed combinations according to 3GPP TS 07.01 B.1.3.1.4 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.10b: Bearer Service 30..34, UDI, 64 kbps bit transparent

Prerequisite: A.6/4 -- BS3x_UDI_X.32[tbd] (diagram in 3GPP TS 07.01 B.1.3.1.5 (3GPP TS 27.001 B.1.3.1.5)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|-------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Signalling Access Protocol (SAP). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | I.440, X.21 | |
| 2 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4 | |
| 3 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 5, 6 | |
| 4 | all allowed combinations according to 3GPP TS 07.01 B.1.3.1.5 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.11: Bearer Service 30..34, 3.1 kHz, Non-X-32

Prerequisite: A.6/5 -- BS3x_3.1kHz_nonX.32 (diagram in 3GPP TS 07.01 B.1.3.2.1 (3GPP TS 27.001 B.1.3.2.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|---|--|--|---------|--------|---------|------------------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 2 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 3 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1.2, 2.4, 4.8, 9.6 | |
| 4 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | V.22, V.22bis, V.26ter, V.32 | |
| 5 | Other Modem Type (OMT) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | no other MT, V.34, NAV | |
| 6 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, NAV | |
| 7 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 8 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1101 | | 1, 2, 3, 4, NAV | |
| 5a | all allowed combinations according to 3GPP TS 07.01 B.1.3.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.1101 IF A.11/6 AND A.25/7 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.12: Bearer Service 30..34, 3.1kHz, X-32

Prerequisite: A.6/6 -- BS3x_3.1kHz_X.32 (diagram in 3GPP TS 07.01 B.1.3.2.2 (3GPP TS 27.001 B.3.2.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|---|--|--|---------|--------|---------|---|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 3 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 4 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 2.4, 4.8, 9.6 | |
| 5 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | V.22bis, V.26ter, V.32 | |
| 6 | Other Modem Type (OMT) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | no other MT, V.34, NAV | |
| 7 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, NAV | |
| 8 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1201 | | 9.6, 14.4, 19.2, 28.8, NAV | |
| 9 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 10 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 11 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1202 | | 1, 2, 3, 4, NAV | |
| 6a | all allowed combinations according to 3GPP TS 07.01 B.1.3.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.1201 IF A.12/7 AND A.25/7 THEN M ELSE N/A | | | | | | | |
| C.1202 IF A.12/7 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.13: Bearer Service 40..46, PAD Access

Prerequisite: A.6/7 -- BS4x_PAD (diagram in 3GPP TS 07.01 B.1.4 (3GPP TS 27.001 B.1.4)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|---|--|--|---------|--------|---------|---|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | ISO6429, COPnoFICt, NAV | |
| 3 | Number of Data Bits(NDB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 7 bits, 8 bits | |
| 4 | Parity Information (NPB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | odd, even, 0, 1, none | |
| 5 | Number of Stop Bits (NSB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1 bit, 2 bits | |
| 6 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 7 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 8 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 9 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV | |
| 10 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1301 | | 9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV | |
| 11 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 12 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 13 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1302 | | 1, 2, 3, 4, NAV | |
| 9a | all allowed combinations according to 3GPP TS 07.01 B.1.4 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |
| C.1301 IF A.13/9 AND A.25/7 THEN M ELSE N/A | | | | | | | |
| C.1302 IF A.13/9 THEN M ELSE N/A | | | | | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.14: Bearer Service 50..53, Data Packet Duplex Synchronous

Prerequisite: A.6/8 -- BS5x_Packet (diagram in 3GPP TS 07.01 B.1.5 (3GPP TS 27.001 B.1.5)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|--|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 2 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 3 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 4 | Fixed Network User Rate (FNUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 9.6, 14.4, 19.2, 28.8, 38.4, 48, 56, NAV | |
| 5 | Wanted Air Interface User Rate (WAIUR) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1401 | | 9.6, 14.4, 19.2, 28.8, 38.4, 43.2, 57.6, NAV | |
| 6 | Acceptable channel codings (ACC) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | 4.8, 9.6, 14.4, NAV | |
| 7 | User Initiated Modification Indication (UIMI) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | O | | not req., upto1, upto2, upto3, upto4, NAV | |
| 8 | Maximum number of Traffic Channels (MaxNumTCH) | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | C.1402 | | 1, 2, 3, 4, NAV | |
| 4a | all allowed combinations according to 3GPP TS 07.01 B.1.5 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

C.1401 IF A.14/4 AND A.25/7 THEN M ELSE N/A

C.1402 IF A.14/4 THEN M ELSE N/A

Detailed description (if not all allowed combinations are implemented):

Table A.15: Bearer Service 61, Alternate Speech/Data, "Speech"

Prerequisite: A.6/9 -- BS61_Speech (diagram in 3GPP TS 07.01 B.1.6.1 (3GPP TS 27.001 B.1.6.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|----------------------------------|--|---------|--------|---------|-----------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |

Comments:

Table A.16: Bearer Service 61, Alternate Speech/Data, 3.1kHz, Async

Prerequisite: A.6/10 -- BS61_3.1kHz_Async (diagram in 3GPP TS 07.01 B.1.6.2.1 (3GPP TS 27.001 B.1.6.2.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|---|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | ISO6429, COPnoFICt, NAV | |
| 3 | Number of Data Bits (NDB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 7 bits, 8 bits | |
| 4 | Parity Information (NPB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | odd, even, 0, 1, none | |
| 5 | Number of Stop Bits (NSB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1 bit, 2 bits | |
| 6 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 7 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 8 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 9 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | M | | V.21, V.22, V.22bis, V.26ter, V.32, V.23, auto1 | |
| 10 | all allowed combinations according to 3GPP TS 07.01 B.1.6.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.17: Bearer Service 61, Alternate Speech/Data, 3.1kHz, Sync

Prerequisite: A.6/11 -- BS61_3.1kHz_Sync (diagram in 3GPP TS 07.01 B.1.6.2.2 (3GPP TS 27.001 B.1.6.2.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|------------------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 2 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 3 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1.2, 2.4, 4.8, 9.6 | |
| 4 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | M | | V.22, V.22bis, V.26ter, V.32 | |
| 5 | all allowed combinations according to 3GPP TS 07.01 B.1.6.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.18: Bearer Service 81, Speech followed by Data, "Speech"

Prerequisite: A.6/12 -- BS81_Speech (diagram in 3GPP TS 07.01 B.1.7.1 (3GPP TS 27.001 B.1.7.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|----------------------------------|--|---------|--------|---------|--------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |

Comments:

Table A.19: Bearer Service 81, Speech followed by Data, 3.1kHz, Async

Prerequisite: A.6/13 -- BS81_3.1kHz_Async (diagram in 3GPP TS 07.01 B.1.7.2.1 (3GPP TS 27.001 B.1.7.2.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|---|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | ISO6429, COPnoFICt, NAV | |
| 3 | Number of Data Bits(NDB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 7 bits, 8 bits | |
| 4 | Parity Information (NPB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | odd, even, 0, 1, none | |
| 5 | Number of Stop Bits (NSB). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1 bit, 2 bits | |
| 6 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |
| 7 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 8 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 0.3, 1.2, 2.4, 4.8, 9.6, 1.2/0.075 | |
| 9 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | M | | V.21, V.22, V.22bis, V.26ter, V.32, V.23, auto1 | |
| 10 | all allowed combinations according to 3GPP TS 07.01 B.1.7.2.1 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.20: Bearer Service 81, Speech followed by Data, 3.1kHz, Sync

Prerequisite: A.6/14 -- BS81_3.1kHz_Sync (diagram in 3GPP TS 07.01 B.1.7.2.2 (3GPP TS 27.001 B.1.7.2.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|---|--|---------|--------|---------|------------------------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR,FR, dualFR | |
| 2 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 3 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 1.2, 2.4, 4.8, 9.6 | |
| 4 | Modem Type (MT). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | R96 | M | | V.22, V.22bis, V.26ter, V.32 | |
| 5 | all allowed combinations according 3GPP TS 07.01 B.1.7.2.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.21: Teleservice 11..12, Speech

Prerequisite: A.6/15 -- TS1x_Speech (diagram in 3GPP TS 07.01 B.1.8 (3GPP TS 27.001 B.1.8)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|----------------------------------|--|---------|--------|---------|-----------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | dualHR, FR, dualFR | |

Comments:

Table A.22: Alternate Speech and Facsimile group 3, Speech

Prerequisite: A.6/16 -- TS61_Speech (diagram in 3GPP TS 07.01 B.1.10.1 (3GPP TS 27.001 B.1.10.1)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|----------------------------------|---|---------|--------|---------|--------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Radio Channel Requirement (RCR). | 3GPP TS 07.01 B1 3GPP TS 27.001, annex B 1 | Phase 2 | M | | dualHR, FR, dualFR | |

Comments:

Table A.23: Alternate Speech and Facsimile group 3, Facsimile group 3

Prerequisite: A.6/17 -- TS61_G3FAX (diagram in 3GPP TS 07.01 B.1.10.2 (3GPP TS 27.001 B.1.10.2)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|----------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | X.25 NAV | |
| 3 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 4 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 2.4, 4.8, 9.6, | |
| 5 | all allowed combinations according 3GPP TS 07.01 B.1.10.2 (3GPP TS 27.001) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

Table A.24: Teleservice 62, Automatic G3 fax

Prerequisite: A.3/7 -- Serv_TS62 (diagram in 3GPP TS 07.01 B.1.11 (3GPP TS 27.001 B.1.11)).

| Item | Bearer Capability Elements | Reference | Release | Status | Support | Values | |
|------|--|--|---------|--------|---------|-------------------------|-----------|
| | | | | | | Allowed | Supported |
| 1 | Connection Element (CE). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | NT, bothNT, T, bothT | |
| 2 | User Info Layer 2 Protocol (UIL2P). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | X.25 NAV | |
| 3 | Intermediate Rate (IR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 8 kbps, 16 kbps | |
| 4 | User Rate (UR). | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | M | | 2.4, 4.8, 9.6 | |
| 5 | all allowed combinations according to 3GPP TS 07.01 B.1.11 (3GPP TS 27.001, annex B) implemented (if not, provide detailed description). | | | O | | | |

Detailed description (if not all allowed combinations are implemented):

A.4.8 Additional Information

The supplier of the implementation shall state the support of the implementation for each of the questions concerning additional information given in the table below.

Table A.25: Additional Information

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|---------|--------|---------|----------------------------------|
| 1 | at least one half rate service. | 3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2 | Phase 2 | O | | TSPC_AddInfo_HalfRate |
| 2 | Speech supported for Full rate version 1 (GSM FR). | 3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5 | Phase 2 | C.2501 | | TSPC_AddInfo_Full_rate_version_1 |
| 3 | Speech supported for Half rate version 1 (GSM HR). | 3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5 | Phase 2 | O | | TSPC_AddInfo_Half_rate_version_1 |
| 4 | at least one data service. | 3GPP TS 07.01 annex D, 3GPP TS 09.07, 3 | Phase 2 | O | | TSPC_AddInfo_DataSvc |
| 5 | at least one full rate data service. | 3GPP TS 07.01 annex D, 3GPP TS 27.001, D 3GPP TS 09.07, 10 3GPP TS 29.007, 10 | Phase 2 | O | | TSPC_AddInfo_FullRateData |
| 6 | at least one half rate data service. | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_HalfRateData |
| 7 | at least one non transparent data service. | 3GPP TS 02.02 3, 3GPP TS 22.002, D.2 3GPP TS 02.03 6 3GPP TS 22.001, D.2 | Phase 2 | O | | TSPC_AddInfo_NonTransData |
| 8 | at least one transparent data service. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3, 3GPP TS 02.03 6 3GPP TS 22.003, 6 | Phase 2 | O | | TSPC_AddInfo_TransData |
| 9 | only transparent data service | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 02.03 6 3GPP TS 22.003, 6 | Phase 2 | O | | TSPC_AddInfo_TranspDataOnly |
| 10 | at least one asynchronous data service. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_AsyncData |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|--|--|---------|--------|---------|--------------------------------|
| 11 | at least one asynchronous non transparent data service. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_AsyncNonTransData |
| 12 | 2.4 k full rate data mode. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_24DataF |
| 13 | 2.4 k half rate data mode. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_24DataH |
| 14 | 4.8 k full rate data mode. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_48DataF |
| 15 | 4.8 k half rate data mode. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_48DataH |
| 16 | 9.6 k full rate data mode. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_96Data |
| 17 | non transparent service with full rate channel at a user rate of 4.8 kbit/s. | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 annex B, 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_fullRate48 |
| 18 | at least one bearer capability. | 3GPP TS 07.01 annex B 3GPP TS 27.001, annex B | Phase 2 | O | | TSPC_AddInfo_BC |
| 19 | at least one MT circuit switched basic service. | 3GPP TS 04.08 5.3.4.2.2 3GPP TS 24.008, 5.3.4.2.2 | Phase 2 | O | | TSPC_AddInfo_MTsvc |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|---------|--------|---------|-------------------------------|
| 20 | at least one MO circuit switched basic service. | 3GPP TS 04.08 5.3.4.2.1 3GPP TS 24.008, 5.3.4.2.1 | Phase 2 | O | | TSPC_AddInfo_MOsvc |
| 21 | only SDCCH. | 3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2 | Phase 2 | O | | TSPC_AddInfo_SDCCHOnly |
| 22 | at least one service on traffic channel supported | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 02.03 annex A 3GPP TS 22.003, annex A | Phase 2 | O | | TSPC_AddInfo_SvcOnTCH |
| 23 | dual rate ratio channel types (no relation to supported speech codecs). | 3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2 | Phase 2 | O | | TSPC_AddInfo_DualRate |
| 24 | only full rate radio channel type (no relation to supported speech codecs). | 3GPP TS 02.06 3.2.2 3GPP TS 22.101, 3.2.2 | Phase 2 | O | | TSPC_AddInfo_FullRateOnly |
| 25 | at least one teleservice. | 3GPP TS 02.03 6 3GPP TS 22.003, 6 | Phase 2 | O | | TSPC_AddInfo_TeleSvc |
| 26 | CC protocol for at least one BC. | 3GPP TS 04.08 5 3GPP TS 24.008, 5 | Phase 2 | O | | TSPC_AddInfo_CCprotocol_oneBC |
| 27 | only circuit switched basic service supported by the mobile is emergency call. | 3GPP TS 02.03 6, A.1.2 3GPP TS 22.003, 6, A.1.2 | Phase 2 | C.2505 | | TSPC_AddInfo_EmgOnly |
| 28 | Fax Error Correction Mode. | 3GPP TS 03.45,4 .2.2 3GPP TS 23.045, 4.2.2 3GPP TS 03.46,2 .6 | Phase 2 | O | | TSPC_AddInfo_FaxErrCorr |
| 29 | at least one supplementary service. | 3GPP TS 02.04 4, 3GPP TS 22.004, 4 3GPP TS 02.07 B.2.1 | Phase 2 | O | | TSPC_AddInfo_SS |
| 30 | non call related supplementary service. | 3GPP TS 02.04 4 3GPP TS 22.004, 4 | Phase 2 | O | | TSPC_AddInfo_NonCallSS |
| 31 | at least one short message service. | 3GPP TS 02.03 B.1.7, A.1.3 3GPP TS 22.003, B.1.3, A.1.3 | Phase 2 | O | | TSPC_AddInfo_SMS |
| 32 | (SMS) reply procedure. | 3GPP TS 03.40 3 3GPP TS 23.040, 3 | Phase 2 | O | | TSPC_AddInfo_ReplyProc |
| 33 | replace SMS. | 3GPP TS 03.40 3 3GPP TS 23.040, 3 | Phase 2 | O | | TSPC_AddInfo_ReplaceSMS |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|---------|--------|---------|----------------------------------|
| 34 | display of received SMS. | 3GPP TS 03.40 9, 3GPP TS 23.040, 9 3GPP TS 03.41 8 3GPP TS 23.041, 8 | Phase 2 | O | | TSPC_AddInfo_DispRcvSMS |
| 35 | SMS status report capabilities. | 3GPP TS 03.40 3.2.9 3GPP TS 23.040, 3.2.9 | Phase 2 | O | | TSPC_AddInfo_SMSStatusRe pCap |
| 36 | Storing of short messages in the SIM. | 3GPP TS 03.38 4 3GPP TS 23.038, 4 | Phase 2 | O | | TSPC_AddInfo_StoreRcvSMS SIM |
| 37 | Storing of short messages in the ME. | 3GPP TS 03.38 4 3GPP TS 23.038, 4 3GPP TS 03.40, 10 3GPP TS 23.040, 10 | Phase 2 | O | | TSPC_AddInfo_StoreRcvSMS ME |
| 38 | detach on power down. | 3GPP TS 04.08 4.3.4 3GPP TS 24.008, 4.3.4 | Phase 2 | O | | TSPC_AddInfo_DetachOnPwr Dn |
| 39 | detach on SIM remove. | 3GPP TS 04.08 4.3.4 3GPP TS 24.008, 4.3.4 | Phase 2 | O | | TSPC_AddInfo_DetachOnSIM Rmv |
| 40 | SIM removable without power down. | 3GPP TS 02.17 5.7 | | O | | TSPC_AddInfo_SIMRmv |
| 41 | ID-1 SIM. | 3GPP TS 02.17 4.1.1 | Phase 2 | O.2502 | | TSPC_AddInfo_ID1 |
| 42 | Plug-In SIM. | 3GPP TS 02.17 4.1.2 | Phase 2 | O.2502 | | TSPC_AddInfo_PlugIn |
| 43 | Disable PIN feature. | 3GPP TS 02.17 5.6 | Phase 2 | O | | TSPC_AddInfo_DisablePin |
| 44 | PIN2 feature. | 3GPP TS 02.17 5.6 | Phase 2 | O | | TSPC_AddInfo_Pin2 |
| 45 | Feature requiring entry of PIN2. | 3GPP TS 02.17 5.6 | Phase 2 | O | | TSPC_AddInfo_Pin2Feature |
| 46 | Chars 0-9, *, # supported | 3GPP TS 02.30 2.3, 3GPP TS 22.030, 2.3 3GPP TS 02.07 B.1.5 | Phase 2 | O | Phase 2 | TSPC_AddInfo_BasCharSet |
| 47 | A, B, C, D chars. supported | 3GPP TS 02.30 2.3 3GPP TS 22.030, 2.3 | Phase 2 | O | Phase 2 | TSPC_AddInfo_AddCharSet |
| 48 | automatically enter automatic selection of PLMN mode. | 3GPP TS 02.11 3.2 3GPP TS 22.011, 3.2 | Phase 2 | O | Phase 2 | TSPC_AddInfo_AutoAutoMod e |
| 49 | alerting indication to the user. | 3GPP TS 04.08 5.2.1.5 3GPP TS 24.008, 5.2.1.5 | Phase 2 | O | Phase 2 | TSPC_AddInfo_AlertInd |
| 50 | Appl. Layer is always running. | 3GPP TS 11.10-1 18.1 3GPP TS 51.010- 1, 18.1 | R98 | O | | TSPC_AddInfo_ApplAlwaysRu n |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|--|--|--------------|--------|---------|----------------------------------|
| 51 | Immediate connect supported for all circuit switched basic services. | 3GPP TS 04.08 5.2.1.6 3GPP TS 24.008, 5.2.1.6 | Phase 2 | O | | TSPC_AddInfo_ImmConn |
| 52 | In-Call modification. | 3GPP TS 04.08 5.3.4.3 3GPP TS 24.008, 5.3.4.3 | Phase 2 | O | | TSPC_AddInfo_InCallMod |
| 53 | follow-on request procedure. | 3GPP TS 04.08 4.4.4.6 3GPP TS 24.008, 4.4.4.6 | Phase 2 | O | | TSPC_AddInfo_followOnReq |
| 54 | refusal of call. | 3GPP TS 04.08 5.2.2.3.1 3GPP TS 24.008, 5.2.2.3.1 | Phase 2 | O | | TSPC_AddInfo_RefusalCall |
| 55 | RF amplification. | 3GPP TS 04.08 3.4.10 3GPP TS 44.018, 3.4.10 | Phase 2 | O | | TSPC_AddInfo_RFAmp |
| 56 | Number of B-party number for autocalling is greater than the number of entries in the blacklist. | 3GPP TS 02.07 annex A | Phase 2 | O | | TSPC_AddInfo_AutocallBnoGreaterM |
| 57 | Handset MS supporting speech. | 3GPP TS 03.50 3.1.1 | Phase 2 | O | | TSPC_AddInfo_SpeechHandset |
| 58 | MT2 Configuration. | 3GPP TS 04.02 3 3GPP TS 24.002, 3 | Phase 2 | O | | TSPC_AddInfo_MT2 |
| 59 | MT2 Configuration or any other possibility to send data over Um interface. | 3GPP TS 04.02 3 3GPP TS 24.002, 3 | Phase 2 | O | | TSPC_AddInfo_MT2orOther |
| 60 | Permanent Antenna Connector. | 3GPP TS 51.010-1 12.1.1, 12.1.2 | Release 4 | O.2504 | | TSPC_AddInfo_PermAntenna |
| 61 | Pseudo-synchronized handover supported. | 3GPP TS 05.10 2, annex A | Phase 2 | O | | TSPC_AddInfo_PseudoSynch |
| 62 | 5V only SIM/ME interface. | 3GPP TS 11.11 | R96 | O.2503 | | TSPC_AddInfo_5V |
| 63 | 3V only SIM/ME interface. | 3GPP TS 11.12 | R96 | O.2503 | | TSPC_AddInfo_3V |
| 64 | 3V/5V SIM/ME interface. | 3GPP TS 11.12 | R96 | O.2503 | | TSPC_AddInfo_3V5V |
| 65 | Speech supported for Full rate version 2 (GSM EFR). | 3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5 | Phase 2 | C.2502 | | TSPC_AddInfo_Full_rate_version_2 |
| 66a | RLP supports non default parameters | 3GPP TS 04.22 5.2.2.6 3GPP TS 24.022, 3 | Phase 2 | O | | TSPC_AddInfo_NonDefaultRlpParam |
| 66b | Support of listening to voice broadcast calls (VBS listening) | 3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1 | R 96 | O | | TSPC_AddInfo_VBS_Listening |
| 67 | Support of originating voice broadcast call (VBS originating) | 3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1 | R 96 | O | | TSPC_AddInfo_VBS_Originating |
| 68 | Support of listening to voice group calls (VGCS listening) | 3GPP TS 04.08, 0.7 3GPP TS 24.008, 1.7.1 | R96 | C.2503 | | TSPC_AddInfo_VGCS_Listening |
| 69 | Support of talking in voice group calls (VGCS talking) | 3GPP TS 04.08, 0.7.1 3GPP TS 24.008, 1.7.1 | R96 | C.2504 | | TSPC_AddInfo_VGCS_Talking |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|---------------------------------------|--------|---------|----------------------------------|
| 70 | Support of originating voice group call (VGCS originating) | 3GPP TS 04.08, 0.7 3GPP TS 24.008, 0.7 | R96 | O | | TSPC_AddInfo_VGCS_Originating |
| 71 | Support reduced NCH monitoring | 3GPP TS 04.08, 3.3.3.3 3GPP TS 44.018, 3.3.3.3 | R96 | O | | TSPC_AddInfo_NCH_ReducedMonitor |
| 72 | 14.4 k data mode | 3GPP TS 02.02 3, 3GPP TS 22.002, 3 3GPP TS 07.01 Annex B, 3GPP TS 27.001, Annex B | R 96 | O | | TSPC_AddInfo_144Data |
| 73 | Implementation of cause number 27 of busy autocalling in category 2 | 3GPP TS 02.07, Annex A | Phase 2 | O | | TSPC_AddInfo_Impl_CNr27_Cat2 |
| 74 | Implementation of cause number 27 of busy autocalling in category 3 | 3GPP TS 02.07, Annex A | Phase 2 | O | | TSPC_AddInfo_Impl_CNr27_Cat3 |
| 75 | void | | | | | |
| 76 | Artificial ear type 1 | 3GPP TS 03.50 | Phase 2 up to and including release 4 | O | | TSPC_AddInfo_Ear_type1 |
| 77 | Artificial ear type 3.2, Low leak option | 3GPP TS 03.50 | Phase 2 | O | | TSPC_AddInfo_Ear_type32_LL |
| 78 | Artificial ear type 3.4 | 3GPP TS 03.50 | R96 | O | | TSPC_AddInfo_Ear_type34 |
| 79 | Speech supported for Full rate version 3 (FR AMR). | 3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5 | R98 | C.2502 | | TSPC_AddInfo_Full_rate_version_3 |
| 80 | NCH monitoring in group receive mode | 3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3 | R 96 | O | | TSPC_AddInfo_NCH_Monit_Rev |
| 81 | NCH monitoring in group transmit mode | 3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3 | R 96 | O | | TSPC_AddInfo_NCH_Monit_Tra |
| 82 | NCH monitoring in dedicated mode | 3GPP TS 03.68 11.3.1.3.a 3GPP TS 43.068, 11.3.1.3 | R 96 | O | | TSPC_AddInfo_NCH_Monit_Ded |
| 83 | Support of one PDP context activation | 3GPP TS 04.08, 6.1.3.1 3GPP TS 24.008, 6.1.3.1 | R 97 | O | | TSPC_AddInfo_1PDP_CA |
| 84 | Support of more than one PDP context activation | 3GPP TS 04.08 3GPP TS 24.008 | R 97 | O | | TSPC_AddInfo_mor1PDP CA |
| 85 | Support of more than one PDP context activation simultaneously on the same SAPI | 3GPP TS 04.08 3GPP TS 24.008 | R 97 | O | | TSPC_AddInfo_mor1PDP CA_SAPI |
| 86 | Support of GPRS data compression | 3GPP TS 04.65, 6.6 3GPP TS 24.065, 6.6 | R 97 | O | | TSPC_AddInfo_GPRS_Data_Compr |
| 87 | Support of GPRS header compression | 3GPP TS 04.65 3GPP TS 24.065 | R 98 | O | | TSPC_AddInfo_GPRS_Header_Compr |
| 88 | Support of Network requested PDP context activation | 3GPP TS 04.08, 6.1.3.1.2 3GPP TS 24.008, 6.1.3.1.2 | R 97 | O | | TSPC_AddInfo_N_req_PDP_CA |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|--|---|--------------|--------|---------|--|
| 89 | Support for user settings of minimum QoS | 3GPP TS 02.60 3GPP TS 22.060 | R 97 | O | | TSPC_AddInfo_min_QoS |
| 90 | Automatic GPRS attach procedure at switch-on/power-on | 3GPP TS 04.08, 4.7.3 3GPP TS 24.008, 4.7.3 | R 97 | O | | TSPC_AddInfo_on_auto_GPRS_AP |
| 91 | MMI controlled attach/detach procedures for non-GPRS services | 3GPP TS 04.08, 4.7.3.1.4 3GPP TS 24.008, 4.7.3.1.4 | R 97 | O | | TSPC_AddInfo_MMI_contr_A_DProc_Non GPRS |
| 92 | Automatic attach procedure when MS identity cannot be derived by the network | 3GPP TS 04.08, 4.7.5.1.4 3GPP TS 24.008, 4.7.5.1.4 | R 97 | O | | TSPC_AddInfo_auto_AP_no_MS ID |
| 93 | Automatic MM IMSI attach procedure at switch-on/power-on | 3GPP TS 04.08, 4.7.3.2.4 3GPP TS 24.008, 4.7.3.2.4 | R98 | O | | TSPC_AddInfo_auto_MM_IMSI_AP_on_off |
| 94 | Support of SIM Application Toolkit | 3GPP TS 11.11, 11.6 | R96 | O | | TSPC_AddInfo_SIM_Appl_Toolkit |
| 95 | 1,8V only SIM/ME interface. | 3GPP TS 11.18 | R98 | O.2503 | | TSPC_AddInfo_1_8V |
| 96 | 1,8V/3V SIM/ME interface. | 3GPP TS 11.18 | R98 | O.2503 | | TSPC_AddInfo_1_8V3V |
| 97 | Multiple SM MO/PP on same RR link | 3GPP TS 03.40 3.7 3GPP TS 23.040, 3.7 | Phase 2 | O | | TSPC_AddInfo_MultSMsame RR |
| 98 | Support of stored list cell selection | 3GPP TS 05.08 3GPP TS 45.008 | Phase 2 | O | | TSPC_AddInfo_StoredListCell Sel |
| 99 | at least one service not support immediate connection | 3GPP TS 04.08 3GPP TS 24.008 | Phase 2 | O | | TSPC_AddInfo_NoimmConn |
| 100 | Void | | | | | |
| 101 | Void | | | | | |
| 102 | EFR_EmgCallSetup message contains the bearer capability | 3GPP TS 06.51 | Phase 2 | O | | TSPC_AddInfo_EFR_EmgCall Bcap |
| 103 | Support of MonitorPCH_GroupTransmit Mode | 3GPP TS 11.10-1 3GPP TS 51.010-1 | Phase 2 | O | | TSPC_AddInfo_MonitorPCH_GroupTransmitMode |
| 104 | Integral_Antenna | 3GPP TS 51.010-1 12 | Release 4 | O.2504 | | TSPC_AddInfo_IntegrAntenna |
| 105 | User requested combined GPRS and non-GPRS detached without powering off | 3GPP TS 04.08, 4.7.4 3GPP TS 24.008, 4.7.4 | R97 | O | | TSPC_AddInfo_Comb_DP_no_pwr_off |
| 106 | User requested non-GPRS detached | 3GPP TS 04.08, 4.7.4 3GPP TS 24.008, 4.7.4 | R97 | O | | TSPC_AddInfo_Usr_non_GPRS_DP |
| 107 | Artificial ear type 3.2, High leak option | 3GPP TS 43.050 | Phase 2 | O | | TSPC_AddInfo_Ear_type32_HL |
| 108 | Artificial ear type 3.3 | 3GPP TS 43.050 | R96 | O | | TSPC_AddInfo_Ear_type33 |
| 109 | Support of Multiple SMS | 3GPP TS 03.40 3.7 3GPP TS 23.040, 3.7 | Phase2 | O | | TSPC_AddInfo_MultSMS |
| 110 | Cell Reselection after T3184 Expiry | 3GPP TS 04.60 | R97 | O | | TSPC_Cell_Resel |
| 111 | GPRS attach attempted automatically due to outstanding request | 3GPP TS 04.08, 4.7.3 3GPP TS 24.008, 4.7.3 | R97 | O | | TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|---|---|---------|--------|---------|---|
| 112 | Speech supported for Half rate version 3 (HR AMR) | 3GPP TS 04.08, 10.5.4.5 3GPP TS 24.008, 10.5.4.5 | R98 | O | | TSPC_AddInfo_Half_rate_version_3 |
| 113 | AMR LoopBack Modes | 3GPP TS 44.014 | R5 | C.2506 | | TSPC_AMR_LoopBack |
| 114 | TTY services | 3GPP TS 24.008 | R99 | O | | TSPC_AddInfo_TTY |
| 115 | Support of Secondary PDP Context Activation | 3GPP TS 24.008, 6.1.3 | R99 | O | | TSPC_SEC_PDP_CONTEXT |
| 116 | Support of MO SMS Concatenation | 3GPP TS 23.040 9.2.3.24.1 | Phase2 | O | | TSPC_SMS_MO_CONCATENATION |
| 117 | Support of MT SMS Concatenation | 3GPP TS 23.040 9.2.3.24.1 | Phase2 | O | | TSPC_SMS_MT_CONCATENATION |
| 118 | NITZ Supported | 3GPP TS 2.42 3GPP TS 22.042 | R97 | C.2507 | | TSPC_NITZ |
| 119 | Use of NITZ DST (Daylight Saving Time) | 3GPP TS 2.42 3GPP TS 22.042 | R97 | O | | TSPC_NITZ_DST |
| 120 | Void | | | | | |
| 121 | Re-attach automatically when the network commands a detach with no cause value | 3GPP TS 04.08, 4.7.3 | R97 | O | | TSPC_AddInfo_GPRS_Attach_on_NW_Detach_NoCause |
| 122 | Support of GPRS header compression algorithm type RFC 1144 | 3GPP TS 04.65 3GPP TS 44.065 | R98 | O | | TSPC_AddInfo_GPRS_Head_r_Compr_Type_RFC1144 |
| 123 | Support of GPRS header compression algorithm type RFC 2507 | 3GPP TS 04.65 3GPP TS 44.065 | R99 | O | | TSPC_AddInfo_GPRS_Head_r_Compr_Type_RFC2507 |
| 124 | Support of ROHC algorithm type RFC 3241 | 3GPP TS 44.065 | Rel-6 | O | | TSPC_AddInfo_ROHC_Type_RFC3241 |
| 125 | Support of ROHC algorithm type RFC 3242 | 3GPP TS 44.065 | Rel-6 | O | | TSPC_AddInfo_ROHC_Type_RFC3242 |
| 126 | Support of ROHC algorithm type RFC 3408 | 3GPP TS 44.065 | Rel-6 | O | | TSPC_AddInfo_ROHC_Type_RFC3408 |
| 127 | Support of ROHC algorithm type RFC 3095 | 3GPP TS 44.065 | Rel-6 | O | | TSPC_AddInfo_ROHC_Type_RFC3095 |
| 128 | The way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | 3GPP TS 04.08 3GPP TS 24.008 | R97 | O | | TSPC_AddInfo_NewULDataInNewPDP_while_ULTransferInOldPDP |
| 129 | Support of DARP phase 1 | 3GPP TS 05.15 3GPP TS 45.015 3GPP TS 24.008 3GPP TS 45.005 | R99 | O | | TSPC_DARP_Phase1 |
| 130 | Support of Card Application | 3GPP TS 22.100 | R99 | O | | TSPC_Card_Appl |
| 131 | Support of GSM speech half rate version 6 (O-TCH/AHS) | 3GPP TS 24.008, 10.5.4.5 | Rel-5 | O | | TSPC_O-TCH_AHS |
| 132 | MS with improved receiver performance | 3GPP TS 05.09 3GPP TS 45.009 | R99 | O | | TSPC_Improv_RX_perform |
| 133 | Support of GSM speech full rate version 4 (O-TCH/WFS) | 3GPP TS 24.008, 10.5.4.5 | Rel-5 | O | | TSPC_O-TCH_WFS |
| 134 | Verification for correct repetition of new password | 3GPP TS 02.30 3GPP TS 22.030, 4.5.1 | R97 | O | | TSPC_Verification_correct_new_password |
| 135 | MS using reduced interslot dynamic range in multislot configurations | 3GPP TS 45.005 | R99 | O | | TSPC_AddInfo_Red_IntSlotRange_Mult_Conf |
| 136 | Support of GSM speech Half rate version 4 (O-TCH/WHS) | 3GPP TS 24.008, 10.5.4.5 | Rel-5 | O | | TSPC_O-TCH_WHS |
| 137 | Support of GSM Speech Full Rate version 5 (TCH/WFS) | 3GPP TS 45.005 | Rel-5 | O | | TSPC_TCH_WFS |
| 138 | Support of overwriting the existing Class 2 SMS | 3GPP TS 03.40, subclause 10.3 (operation 14) | Phase 2 | O | | TSPC_AddInfo_OverwriteRcvClass2SMSSIM |

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|-----------|--|--|---------|--------|--|--|
| 139 | Support of Repeated SACCH | 3GPP TS 24.008, Subclause 10.5.1.7 | Rel-6 | O | | TSPC_Repeated_SACCH |
| 140 | Support for a method for resetting stored A-GPS assistance data | 3GPP TS 03.71, 7.6.1 | R98 | O | | TSPC_A-GPS_Data_Reset |
| 141 | Support of DARP phase 2 | 3GPP TS 24.008 3GPP TS 45.005 | Rel-7 | O | | TSPC_DARP_Phase2 |
| 142 | Support of Rel-4 acoustic implementation | 3GPP TS 26.131 3GPP TS 26.132 | Rel-4 | O | | TSPC_AddInfo_Rel4_Acoustic |
| 143 | MS with no components having RF performance sensitive to vibration condition during testing | 3GPP TS45.005, D2.3 | R99 | O | | TSPC_No_Vibration_Sensitive _Components |
| 144 | Use of NITZ Full Name | 3GPP TS 2.42 3GPP TS 22.042 | R97 | O | | TSPC_NITZ_Full_Name |
| 145 | Use of NITZ Short Name | 3GPP TS 2.42 3GPP TS 22.042 | R97 | O | | TSPC_NITZ_Short_Name |
| 146 | Use of NITZ Universal Time | 3GPP TS 2.42 3GPP TS 22.042 | R97 | O | | TSPC_NITZ_Universal_Time |
| 147 | Use of NITZ Local Time Zone | 3GPP TS 2.42 3GPP TS 22.042 | R97 | O | | TSPC_NITZ_Time_Zone |
| 148 | MS using a temporary antenna connector | 3GPP TS 51.010- 1 | R99 | O.2504 | | TSPC_AddInfo_TempAntenna |
| 149 | Support of Repeated FACCH | 3GPP TS 24.008, Subclause 10.5.1.7 | Rel-6 | M | | TSPC_Repeated_FACCH |
| O.2502 | At least one of the requirements shall be supported. | | | | | |
| O.2503 | At least one of these items shall be supported. | | | | | |
| O.2504 | At least one of these items shall be supported. | | | | | |
| C.2501 | IF A.25/3 THEN M ELSE O | | | | -- TSPC_AddInfo_Half_rate_version_1 | |
| C.2502 | IF A.25/2 THEN O ELSE N/A | | | | -- TSPC_AddInfo_Full_rate_version_1 | |
| C.2503 | IF A.25/69 OR A.25/70 THEN M ELSE O | | | | -- TSPC_AddInfo_VGCS OR TSPC_AddInfo_VGCS_Talking | |
| C.2504 | IF A.25/70 THEN M ELSE O | | | | -- TSPC_AddInfo_VGCS | |
| C.2505 | IF A.3/2 THEN O ELSE N/A | | | | -- TSPC_Serv_TS12 | |
| C.2506 | IF A.25/79 THEN M ELSE N/A | | | | -- TSPC_AddInfo_Full_rate_version_3 | |
| C.2507 | IF A.25/144 OR A.25/145 OR A.25/146 OR A.25/147 OR A.25/119 THEN O ELSE N/A | | | | -- TSPC_NITZ_Full_Name OR TSPC_NITZ_Short_Name OR TSPC_NITZ_Universal_Time OR TSPC_NITZ_Time_Zone OR TSPC_NITZ_DST | |
| Comments: | | | | | | |

Table A.25.1: Additional Information (requiring values)

| Item | Additional information | Reference | Release | Status | Support | Values | |
|------|---|--|---------|--------|---------|---|-----------|
| | | | | | | Allowed | Supported |
| 1 | AMR C/I normalization factor (units: dB) | 3GPP TS 05.09, 3.3.1 3GPP TS 45.009, 3.3.1 | R98 | O | | 0 ... ∞ | |
| 2 | Loop C delay Full rate (round trip delay, in number of TDMA frames) | 3GPP TS 04.14, 5.1.4.4 3GPP TS 44.014, 5.1.4.4 | R98 | O | | 1 ... ∞ | |
| 3 | AMR C/I normalization factors (AFS, DARP) 12 values representing SS adjustment of variable normalisation factors for C/I values as stated in 14.10.3 (units: dB) | 3GPP TS 05.09, 3.3.1 3GPP TS 45.009, 3.3.1 | R99 | O | | 0 ... ∞, 0 ... ∞, 0 ... ∞ | |
| 4 | AMR C/I normalization factors (AHS, DARP) 10 values representing SS adjustment of variable normalisation factors for C/I values as stated in 14.10.4 (units: dB) | 3GPP TS 05.09, 3.3.1 3GPP TS 45.009, 3.3.1 | R99 | O | | 0 ... ∞, 0 ... ∞, 0 ... ∞ | |
| 5 | O-TCH/F C/I normalisation factor (units: dB) | 3GPP TS 45.009, 3.3.1 | Rel-5 | O | | 0 ... ∞ | |
| 6 | Loop C delay Half rate (round trip delay, in number of TDMA frames) | 3GPP TS 04.14, 5.1.4.4 3GPP TS 44.014, 5.1.4.4 | R98 | O | | 1 ... ∞ | |
| 7 | Averaging time T_{av} This time is the time between the first and the last measurement sample taken on one carrier during one averaging period when measuring received signal strength | 3GPP TS 05.08, 6.1 & 6.2 3GPP TS 45.008, 6.1 & 6.2 | R99 | O | | 0 ... ∞ | |
| 8 | TCH/WFS C/I normalisation factor | 3GPP TS 05.09, 3.3.1 3GPP TS 45.009, 3.3.1 | Rel-5 | O | | 0 ... ∞ | |
| 9 | TCH/WFS C/I normalization factors (TCH/WFS, DARP) 12 values representing SS adjustment of variable normalisation factors for C/I values as stated in 14.10.9 (units: dB) | 3GPP TS 05.09, 3.3.1 3GPP TS 45.009, 3.3.1 | Rel-5 | O | | 0 ... ∞, 0 ... ∞, 0 ... ∞ | |

Comments:

A.4.9 SIM Application Toolkit

The supplier of the implementation shall state the support of the implementation for each of the questions concerning the information given in the tables below.

A.4.9.1 SIM Application Toolkit mechanism

The PICS tables for SIM Application Toolkit mechanism are contained in document 3GPP TS 11.10-4.

The 'Applicability of Test' tables for the SIM Application Toolkit mechanism are contained in document 3GPP TS 11.10-4 R99.

A.4.9.1.1 Terminal Profile

The contents of TERMINAL PROFILE used in the Profile Download instruction is detailed in document 3GPP TS 11.10-4 [96]

A.4.10 Support of UTRAN Radio Access Technology

The supplier of the implementation shall state the support of the implementation for each of the questions concerning Support of UTRAN Radio Access Technology given in the table below.

Table A.27: Support of UTRAN Radio Access Technology

Prerequisite: A.1/56 -- TSPC_Type_UTRAN

| Item | Additional Information | Ref. | Release | Status | Support | Mnemonic |
|------|---|--|---------|--------|---------|---|
| 1 | Conversational / speech / UL:12.2 DL:12.2 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH | 3GPP TS 34.123-2, A.18c/4 3GPP TS 34.108 6.10.2.4.1.4 | R99 | O | | TSPC_Conversational_12_2_CSRAB_3_4_SRAB |
| 2 | Streaming / unknown / UL:14.4/DL:14.4 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH | 3GPP TS 34.123-2, A.18c/15 3GPP TS 34.108 6.10.2.4.1.15 | R99 | O | | TSPC_Streaming_14_4_CSRAB_3_4_SRAB |
| 3 | Streaming / unknown / UL:28.8/DL:28.8 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH | 3GPP TS 34.123-2, A.18c/16 3GPP TS 34.108, 6.10.2.4.1.16 | R99 | O | | TSPC_Streaming_28_8_CSRAB_3_4_SRAB |
| 4 | Streaming / unknown / UL:57.6/DL:57.6 kbps / CS RAB + UL:3.4 DL:3.4 kbps SRBs for DCCH | 3GPP TS 34.123-2, A.18c/17 3GPP TS 34.108, 6.10.2.4.1.17 | R99 | O | | TSPC_Streaming_57_6_CSRAB_3_4_SRAB |

Annex B (normative): Applicability of the individual test

The applicability of each individual test is identified in the table B.1.

The applicability of every test is formally expressed by the use of Boolean expression that are based on parameters (ICS) included in annex A of the present document.

The columns in Table B.1 have the following meaning:

Clause column

The Clause column indicates the clause number for each test case as described in the 3GPP TS 51.010-1 or 3GPP TS 11.10-4 (tests 27.22.x) for which the applicability is identified.

Title column

The Title column indicates the title of each test case as described in the 3GPP TS 51.010-1 or 3GPP TS 11.10-4 (tests 27.22.x) for which the applicability is identified.

Release column

The Release column indicates the earliest release from which each test case is applicable, except if otherwise stated of an individual test case.

Applicability column

The Applicability column describes the applicability of the test in a verbal way.

Applicability Limitations column

The Applicability Limitations column describes limitations to or redundancies of the applicability of the test using the following notations:

| | |
|----|--|
| R | redundant – the requirement in this test is verified in another test. |
| Ri | Reduced applicability – the test is applicable ("A") or redundant ("R") depending on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is used to avoid ambiguities. |
| Li | Limited execution – the test is applicable ("A"). The execution may be limited depending on the support of other optional or conditional items, e.g. some tests may not be repeated for all execution counters. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. |

Status column

The following notations are used for the Status column:

| | |
|-----|--|
| A | applicable - the test is applicable. |
| N/A | not applicable – in the given context, the test case is not applicable. |
| Ci | conditional – the test is applicable ("A") or not ("N/A") depending on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is used to avoid ambiguities. |

Specific PICS Statements column

The Specific PICS Statements column shows PICS statements in their mnemonics form that are used in 3GPP TS 51.010-1 to specify or influence the performance or behaviour of the test.

Supported column

The following common notations are used for the Supported column:

| | |
|---------------|--|
| Y or y | test is supported by the implementation |
| N or n | test is not supported by the implementation |
| N/A, n/a or - | no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status) |

Table B.1: Applicability of tests

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------|---|---------|---|---------------------------|--------|--|-----------|
| 11.1.1 | Mobile Terminated (MT) calls | Phase 2 | Each MT Bearer Service and MT Teleservice supported by the MS | | C31 | | |
| 11.1.2 | Mobile Originated (MO) calls | Phase 2 | Each MO Bearer Service and MO Teleservice supported by the MS | | C36 | | |
| 11.2 | Verification of support of the single numbering scheme | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | | |
| 11.3 | Verification of non-support of services (Advice of Charge Charging (AOCC)) | Phase 2 | MS which support at least one circuit switched basic service and do not support AOCC | | C32 | TSPC_Addinfo_MTsvc TSPC_Addinfo_MOsvc | |
| 11.4 | Verification of non-support of services (call hold) | Phase 2 | MS which support AOCC and MO Teleservices and do not support the Call Hold supplementary service | | C33 | | |
| 11.5 | Verification of non-support of services (multiparty) | Phase 2 | MS which support Call Hold and AOCC and MO Teleservices and, but do not support the Multi-Party supplementary service | | C34 | | |
| 11.6 | Verification of non-support of feature (Fixed Dialling Number (FDN)) | Phase 2 | MS which support MO Teleservices and do not support FDN | | C35 | | |
| 11.7 | IMEI Security | Phase 2 | All MS | | A | | |
| 12.1.1 | Conducted spurious emissions, MS allocated a channel | Phase 2 | All MS with a permanent antenna connector which do not support R-GSM. | | C99 | | |
| 12.1.2 | Conducted spurious emissions, MS in idle mode | Phase 2 | All MS with a permanent antenna connector which do not support R-GSM. | | C99 | | |
| 12.2.1 | Radiated spurious emissions, MS allocated a channel | Phase 2 | All MS not supporting R-GSM. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible | | C102 | | |
| 12.2.2 | Radiated spurious emissions, MS in idle mode | Phase 2 | All MS not supporting R-GSM. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible | | C102 | | |
| 12.3.1 | Conducted spurious emissions, MS allocated a channel for MS supporting the R-GSM band | R96 | R-GSM MS with a permanent antenna connector | | C115 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 12.3.2 | Conducted spurious emissions, MS in idle mode for MS supporting the R-GSM band | R96 | R-GSM MS with a permanent antenna connector | | C115 | | |
| 12.4.1 | Radiated spurious emissions, MS allocated a channel for MS supporting the R-GSM band | R96 | R-GSM MS. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible | | C103 | | |
| 12.4.2 | Radiated spurious emissions, MS in idle mode for MS supporting the R-GSM band | R96 | R-GSM MS. The test at extreme voltages does not apply to MS where a practical connection to an external power supply is not possible | | C103 | | |
| 13.1 | Frequency error and phase error | Phase 2 | All MS | R2, L6 | A | | |
| 13.2 | Frequency error under multipath and interference conditions | Phase 2 | All MS | | A | | |
| 13.3.4.1 | Transmitter output power and burst timing - MS with permanent- or temporary antenna connector | Phase 2 | All MS with a permanent- or temporary antenna connector | R2 | C413 | | |
| 13.3.4.2 | Transmitter output power and burst timing - MS with integral antenna | Phase 2 | All MS with integral antenna | R2 | C92 | | |
| 13.4 | Output RF spectrum | Phase 2 | All MS not supporting R-GSM | R2 | C375 | | |
| 13.6 | Frequency error and phase error in HSCSD multislot configuration | R96 | HSCSD Multislot MS | R3, L6 | C380 | | |
| 13.7-1 | Transmitter output power and burst timing in HSCSD configurations - MS with permanent- or temporary antenna connector | R96 | HSCSD Multislot MS with permanent- or temporary antenna connector | R4 | C377 | | |
| 13.7-2 | Transmitter output power and burst timing in HSCSD configurations - MS with integral antenna | R96 | HSCSD Multislot MS with integral antenna | R4 | C378 | | |
| 13.8 | Output RF spectrum in HSCSD multislot configuration | R96 | HSCSD Multislot MS | R4 | C376 | | |
| 13.9 | Output RF spectrum for MS supporting the R-GSM band | R96 | R-GSM MS | | C103 | | |
| 13.10 | Void | | | | | | |
| 13.11 | Void | | | | | | |
| 13.12 | Void | | | | | | |
| 13.13 | Void | | | | | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|-------------------|---|---------------------------|--------|---|-----------|
| 13.14 | Void | | | | | | |
| 13.15 | Void | | | | | | |
| 13.16.1 | Frequency error and phase error in GPRS multislot configuration | R97 | GPRS MS supporting multislot operation on the uplink | L6 | C204 | | |
| 13.16.2-1 | Transmitter output power in GPRS multislot configuration - MS with permanent- or temporary antenna connector | R97 | GPRS MS supporting multislot operation on the uplink - MS with permanent- or temporary antenna connector | | C95 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 13.16.2-2 | Transmitter output power in GPRS multislot configuration - MS with integral antenna | R97 | GPRS MS supporting multislot operation on the uplink - MS with integral antenna | | C96 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 13.16.3 | Output RF spectrum in GPRS multislot configuration | R97 | GPRS MS supporting multislot operation on the uplink | | C204 | | |
| 13.17.1 | Frequency error and Modulation accuracy | R99 | EGPRS MS capable of 8PSK in Uplink, of all Multislot classes | | C238 | | |
| 13.17.2 | Frequency error under multipath and interference conditions | R99 | All EGPRS MS | | C216 | | |
| 13.17.3-1 | EGPRS Transmitter output power- MS with permanent- or temporary antenna connector | R99 | EGPRS MS capable of 8PSK in Uplink, of all Multislot classes with permanent- or temporary antenna connector | | C97 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 13.17.3-2 | EGPRS Transmitter output power- MS with integral antenna | R99 | EGPRS MS capable of 8PSK in Uplink, of all Multislot classes with integral antenna | | C98 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 13.17.4 | Output RF spectrum | R99 | EGPRS MS capable of 8PSK in Uplink, of all Multislot classes | | C238 | | |
| 14.1.1.1 | Bad frame indication - TCH/FS - Random RF input | Phase 2 | MS supporting full rate speech | R12 | C24 | | |
| 14.1.1.2 | Bad frame indication - TCH/FS - Frequency hopping and downlink DTX | Phase 2 | MS supporting full rate speech | R12 | C24 | | |
| 14.1.2.1 | Bad frame indication - TCH/HS - Random RF input | Phase 2 | MS supporting half-rate speech | | C13 | | |
| 14.1.2.2 | Bad frame indication - TCH/HS - Frequency hopping and downlink DTX | Phase 2 | MS supporting half-rate speech | | C13 | | |
| 14.1.3 | Void | | | | | | |
| 14.1.4 | Void | | | | | | |
| 14.1.5.1 | Bad frame indication - TCH/AFS - Random RF input | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | | C321 | | |
| 14.1.6.1 | Bad frame indication - TCH/AHS - Random RF input | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | R9 | C333 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------|--|-------------------|--|---------------------------|--------|--------------------------------------|-----------|
| 14.2.1 | Reference sensitivity - TCH/FS | Phase 2 | MS supporting full rate speech | | C24 | | |
| 14.2.2 | Reference sensitivity - TCH/HS (Speech frames) | Phase 2 | MS supporting half-rate speech | | C13 | | |
| 14.2.3 | Reference sensitivity - FACCH/F | Phase 2 | All MS | | A | | |
| 14.2.4 | Reference sensitivity - FACCH/H | Phase 2 | MS supporting half rate service | | C2 | | |
| 14.2.5 | Reference sensitivity - full rate data channels | Phase 2 | MS supporting data | R5 | C372 | | |
| 14.2.6 | Reference sensitivity - half rate data channels | Phase 2 | MS supporting half-rate data | | C12 | | |
| 14.2.7 | Reference sensitivity - TCH/EFS | Phase 2 | MS supporting EFR speech | | C83 | | |
| 14.2.8 | Reference sensitivity - full rate data channels in multislot configuration | R98 | HSCSD Multislot MS | | C86 | | |
| 14.2.9 | Reference sensitivity - TCH/FS for MS supporting the R-GSM band | R98 | R-GSM MS supporting full rate speech | | C116 | | |
| 14.2.10 | Reference Sensitivity – TCH/AFS | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | | C321 | | |
| 14.2.18 | Reference Sensitivity – TCH/AHS | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | | C333 | | |
| 14.2.19 | Reference Sensitivity – TCH/AFS-INB | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | R10 | C321 | | |
| 14.2.20 | Reference Sensitivity – TCH/AHS-INB | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | | C333 | | |
| 14.2.21 | Reference Sensitivity – O-TCH/AHS | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 14.2.22 | Reference Sensitivity – O-TCH/WFS | Rel-5 | MS supporting O-TCH/WFS | | C366 | | |
| 14.2.23 | Reference sensitivity – O-TCH/WHS | Rel-5 | MS supporting O-TCH/WHS | | C383 | | |
| 14.2.24 | Reference Sensitivity – TCH/WFS | Rel-5 | MS supporting TCH/WFS | | C387 | | |
| 14.2.25 | Reference Sensitivity – Repeated FACCH/F | Rel-6 | MS supporting Repeated FACCH | | C466 | | |
| 14.2.26 | Reference Sensitivity – Repeated SACCH | Rel-6 | MS supporting Repeated SACCH | | C414 | | |
| 14.2.27 | Reference Sensitivity – TCH/FS – DARP Phase II | Rel-7 | MS supporting full rate speech and DARP phase II | | C451 | | |
| 14.3 | Usable receiver input level range | Phase 2 | MS supporting full rate speech | | C24 | | |
| 14.4.1 | Co-channel rejection - TCH/FS | Phase 2 | MS supporting full rate speech | L3 | C24 | TSPC_DARP_Phase1 TSPC_DARP_Phase2 | |
| 14.4.2 | Co-channel rejection - TCH/HS | Phase 2 | MS supporting half-rate speech | | C13 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------|--|---------------------|--|---------------------------|--------|---|-----------|
| 14.4.3 | Void | | | | | | |
| 14.4.4 | Co-channel rejection - FACCH/F | Phase 2 | All MS | | A | | |
| 14.4.5 | Co-channel rejection - FACCH/H | Phase 2 | MS supporting half rate service | | C2 | | |
| 14.4.6 | Co-channel rejection - TCH/EFS | Phase 2 | MS supporting EFR speech | | C83 | | |
| 14.4.7 | Receiver performance in the case of frequency hopping and co-channel interference on one carrier | R97 | MS supporting speech | | C52 | | |
| 14.4.8 | Co-channel rejection – TCH/AFS | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | L3 | C321 | TSPC_DARP_Phase1 TSPC_DARP_Phase2 | |
| 14.4.16 | Co-channel rejection – TCH/AHS | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | R7 | C333 | | |
| 14.4.17 | Co-channel rejection – TCH/AFS-INB | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | L4 | C321 | TSPC_AddInfo_Half_rate_version_3 | |
| 14.4.18 | Co-channel rejection – TCH/AHS-INB | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | | C333 | | |
| 14.4.19 | Co-channel rejection – O-TCH/AHS | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 14.4.20 | Co-channel rejection – O-TCH/AHS-INB | Rel-5 AND AMR Loops | MS supporting O-TCH/AHS and AMR Test-Loops | | C369 | | |
| 14.4.21 | Co-channel rejection – O-FACCH/H | Rel-5 | MS supporting O-TCH/AHS or O-TCH/WHS | | C391 | TSPC_O-TCH_WHS TSPC_O-TCH_AHS | |
| 14.4.24 | Co-channel interference – O-TCH/WFS | Rel-5 | MS supporting O-TCH/WFS | | C366 | | |
| 14.4.25 | Co-channel interference – O-TCH/WHS | Rel-5 | MS supporting O-TCH/WHS | | C383 | | |
| 14.4.26 | Co-channel rejection - O-TCH/WFS-INB | Rel-5 | MS supporting O-TCH/WFS and AMR Test-Loops | | C395 | | |
| 14.4.27 | Void | | | | | | |
| 14.4.28 | Co-channel Interference – TCH/WFS | Rel-5 | MS supporting TCH/WFS | | C387 | TSPC_Type_SmallMS TSPC_Type_DCS_Class1 TSPC_Type_DCS_Class2 TSPC_Type_DCS_Class3 TSPC_Type_PCS_Class1 TSPC_Type_PCS_Class2 | |
| 14.4.29 | Co-channel Interference – TCH/WFS-INB | Rel-5 | MS supporting TCH/WFS | | C387 | | |
| 14.4.30 | Co-Channel Rejection O-FACCH/F | Rel-5 | MS supporting O-TCH/WFS | | C366 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|-------------------|--|---------------------------|--------|---|-----------|
| 14.4.31 | Co-channel rejection – Repeated FACCH/F | Rel-6 | MS supporting Repeated FACCH | | C466 | TSPC_Type_SmallMS TSPC_Type_DCS_Class1 TSPC_Type_DCS_Class2 TSPC_Type_DCS_Class3 TSPC_Type_PCS_Class1 TSPC_Type_PCS_Class2 | |
| 14.4.32 | Co-channel rejection – Repeated SACCH | Rel-6 | MS supporting Repeated SACCH | | C414 | TSPC_Type_SmallMS TSPC_Type_DCS_Class1 TSPC_Type_DCS_Class2 TSPC_Type_DCS_Class3 TSPC_Type_PCS_Class1 TSPC_Type_PCS_Class2 | |
| 14.5.1.1 | Adjacent channel rejection - speech channels – TCH/FS | Phase 2 | MS supporting speech | R12 | C24 | | |
| 14.5.1.2 | Adjacent channel rejection - speech channels – TCH/AFS | R98 AND AMR Loops | MS supporting AMR and AMR Test-Loops | | C321 | | |
| 14.5.1.3 | Adjacent channel rejection - speech channels – TCH/AHS | R98 AND AMR Loops | MS supporting AMR Half Rate and AMR Test-Loops | | C333 | | |
| 14.5.1.4 | Adjacent channel rejection - speech channels – O-TCH/AHS | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 14.5.1.5 | Adjacent Channel Rejection - speech channels - O-TCH/WFS | Rel-5 | MS supporting O-TCH/WFS | | C366 | | |
| 14.5.1.6 | Adjacent channel interference O-TCH/WHS | Rel-5 | MS supporting O-TCH/WHS | | C383 | | |
| 14.5.1.7 | Adjacent Channel Interference – TCH/WFS | Rel-5 | MS supporting TCH/WFS | | C387 | | |
| 14.5.2 | Adjacent channel rejection - control channels | Phase 2 | MS not supporting speech | | C53 | | |
| 14.6.1 | Intermodulation rejection - speech channels | Phase 2 | MS supporting speech | | C52 | | |
| 14.6.2 | Intermodulation rejection - control channels | Phase 2 | MS not supporting speech | | C53 | | |
| 14.7.1 | Blocking and spurious response - speech channels | Phase 2 | Non R-GSM MS supporting speech | | C100 | | |
| 14.7.2 | Blocking and spurious response - control channels | Phase 2 | MS not supporting speech | | C53 | | |
| 14.7.3 | Blocking and spurious response - speech channels for MS supporting the R-GSM band | R97 | R-GSM MS supporting speech | | C116 | | |
| 14.7.4 | Blocking and spurious response - control channels for MS supporting the R-GSM band | R97 | R-GSM MS not supporting speech | | C119 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 14.8.1 | AM suppression - speech channels | Phase 2 | MS supporting speech | | C52 | | |
| 14.8.2 | AM suppression - control channels | Phase 2 | MS not supporting speech | | C53 | | |
| 14.9 | Paging performance at high input levels | Phase 2 | All MS | | A | | |
| 14.10.1 | Performance of the Codec Mode Request Generation – TCH/AFS | R98 | MS supporting AMR full rate and not MS with DARP | | C362 | | |
| 14.10.2 | Performance of the Codec Mode Request Generation – TCH/AHS | R98 | MS supporting AMR half rate and not MS with DARP | | C363 | | |
| 14.10.3 | Performance of the Codec Mode Request Generation – TCH/AFS - DARP | R99 | MS supporting AMR full rate and DARP | | C434 | | |
| 14.10.4 | Performance of the Codec Mode Request Generation – TCH/AHS - DARP | R99 | MS supporting AMR half rate and DARP | | C435 | | |
| 14.10.5 | Performance of the Codec Mode Request Generation – O-TCH/AHS | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 14.10.6 | Performance of the Codec Mode Request Generation – O-TCH/WFS | Rel-5 | MS supporting O-TCH/WFS | | C366 | | |
| 14.10.7 | Performance of the Codec Mode Request Generation – O-TCH/WHS | Rel-5 | MS supporting O-TCH/WHS | | C383 | | |
| 14.10.8 | Performance of the Codec Mode Request Generation – TCH/WFS | Rel-5 | MS supporting TCH/WFS and not MS with DARP | | C396 | | |
| 14.10.9 | Performance of the Codec Mode Request Generation – TCH/WFS - DARP | Rel-5 | MS supporting TCH/WFS and DARP | | C436 | | |
| 14.11.1.1 | DARP ph1 Speech bearer tests / TCH/FS / DTS-1 | R99 | MS supporting full rate speech and DARP phase 1 OR DARP phase 2 | | C350 | | |
| 14.11.2.1 | DARP ph1 Speech bearer tests / TCH/AFS / DTS-1 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C344 | | |
| 14.11.2.2 | DARP ph1 Speech bearer tests / TCH/AFS / DTS-4 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C344 | | |
| 14.11.2.3 | DARP ph1 Speech bearer tests / TCH/AFS / DTS-2/3/5 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C344 | | |
| 14.11.3.1 | DARP ph1 Speech bearer tests / TCH/AHS / DTS-1 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C351 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 14.11.3.3 | DARP ph1 Speech bearer tests / TCH/AHS / DTS-2/3 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C351 | | |
| 14.12.1.1 | DARP Ph1 Signalling bearer tests / FACCH DTS-1 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C350 | | |
| 14.12.1.2 | DARP Ph1 Signalling bearer tests / FACCH DTS-2-3 | R99 | MS supporting AMR and DARP phase 1 OR DARP phase 2 | | C350 | | |
| 14.13 | Void | | | | | | |
| 14.14 | Void | | | | | | |
| 14.15 | Void | | | | | | |
| 14.16.1 | Minimum Input level for Reference Performance | R97 | All GPRS MS | | C215 | | |
| 14.16.2.1 | Co-channel rejection for packet channels | R97 | All GPRS MS | | C215 | TSPC_DARP_Phase1 | |
| 14.16.3 | Acknowledged mode / Downlink TBF / I_LEVEL measurement report | R97 | All GPRS MS | | C215 | | |
| 14.16.4.1 | DARP Ph1 GPRS test / DTS-1 | R99 | All GPRS MS supporting DARP phase 1 or DARP phase 2 | | C349 | | |
| 14.16.4.2 | DARP Ph1 GPRS tests / DTS-2 / DTS-3 | R99 | All GPRS MS supporting DARP phase 1 or DARP phase 2 | | C349 | | |
| 14.16.5.1 | DARP phase II GPRS test / DTS-1 | Rel-7 | All GPRS MS supporting DARP phase II | | C448 | | |
| 14.16.5.2 | DARP phase II GPRS test / DTS-2 / DTS-5 | Rel-7 | All GPRS MS supporting DARP phase II | | C448 | | |
| 14.18.1 | Minimum Input Level for Reference Performance | R99 | All EGPRS MS | | C216 | | |
| 14.18.2 | Co-channel Rejection | R99 | All EGPRS MS | | C216 | TSPC_DARP_Phase1 | |
| 14.18.3 | Adjacent channel Rejection | R99 | All EGPRS MS | | C216 | | |
| 14.18.4 | Intermodulation Rejection | R99 | All EGPRS MS | | C216 | | |
| 14.18.5 | Blocking and spurious response | R99 | All EGPRS MS | | C216 | | |
| 14.18.6 | EGPRS Usable receiver input level range | R99 | All EGPRS MS | | C216 | | |
| 14.18.7 | Incremental redundancy performance | R99 | All EGPRS MS | | C216 | | |
| 14.18.8.1 | DARP Ph1 EGPRS tests / DTS-1 | R99 | All EGPRS MS supporting DARP phase 1 | | C364 | | |
| 14.18.8.2 | DARP Ph1 EGPRS tests / DTS-2 / DTS-3 | R99 | All EGPRS MS supporting DARP phase 1 | | C364 | | |
| 14.18.9.1 | DARP Phase II EGPRS tests / DTS-1 | Rel-7 | All EGPRS MS supporting DARP phase II | | C449 | | |
| 14.18.9.2 | DARP Phase II EGPRS tests / DTS-1b | Rel-7 | All EGPRS MS supporting DARP phase II | | C449 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|---|---------------------------|--------|--|-----------|
| 14.18.9.3 | DARP Phase II EGPRS tests / DTS-2 / DTS-5 | Rel-7 | All EGPRS MS supporting DARP phase II | | C449 | | |
| 14.19.1.1 | DARP phase II Speech bearer tests / TCH/FS / DTS-1 | Rel-7 | MS supporting full rate speech and DARP phase II | | C451 | | |
| 14.19.2.1 | DARP phase II Speech bearer tests / TCH/AFS / DTS-1 | Rel-7 | MS supporting AMR and DARP phase II | | C453 | | |
| 14.19.2.2 | DARP phase II Speech bearer tests / TCH/AFS / DTS-2/5 | Rel-7 | MS supporting AMR and DARP phase II | | C453 | | |
| 14.19.3.1 | DARP phase II Speech bearer tests / TCH/AHS / DTS-1 | Rel-7 | MS supporting AMR and DARP phase II | | C454 | | |
| 14.19.3.2 | DARP phase II Speech bearer tests / TCH/AHS / DTS-2 | Rel-7 | MS supporting AMR and DARP phase II | | C454 | | |
| 15.1 | Timing advance and absolute delay | Phase 2 | All MS | | A | | |
| 15.2 | void | | | | | | |
| 15.3 | void | | | | | | |
| 15.4 | void | | | | | | |
| 15.5 | void | | | | | | |
| 15.6 | GPRS Timing advance and absolute delay | R97 | All GPRS MS | | C215 | | |
| 15.7 | ECSD Timing advance and absolute delay | R99 | All ECSD MS | | C214 | | |
| 15.8 | EGPRS Timing advance and absolute delay | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 15.9 | Timing advance whilst in DTM | R99 | All DTM/GPRS capable MS | | C305 | TSPC_DTM_GPRS_Multislot_Class_5 TSPC_DTM_GPRS_Multislot_Class_9 | |
| 16 | Reception time tracking speed | Phase 2 | All MS | | A | | |
| 17.1 | Intra cell channel change | Phase 2 | All MS | | A | | |
| 17.2 | Inter cell handover | Phase 2 | All MS | | A | | |
| 18.1 | Temporary reception gaps, single slot | Phase 2 | MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic | | C1 | | |
| 18.2 | Temporary reception gaps in HSCSD multislot configurations | R98 | HSCSD Multislot MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic | | C90 | | |
| 19.1 | Channel release after unrecoverable errors -1 | Phase 2 | MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic | | C1 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 19.2 | Channel release after unrecoverable errors - 2 | Phase 2 | MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic | | C1 | | |
| 19.3 | Channel release after unrecoverable errors - 3 | Phase 2 | MS which do not have an application layer always running which performs a normal release of the call due to loss of traffic | | C1 | | |
| 20.1 | Cell selection | Phase 2 | All MS | | A | | |
| 20.2 | Cell selection with varying signal strength values | Phase 2 | All MS | | A | | |
| 20.3 | Basic cell reselection | Phase 2 | All MS | | A | | |
| 20.4 | Cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters | Phase 2 | All MS | | A | TSPC_Type_DCS_Class3 | |
| 20.5 | Cell reselection using parameters transmitted in the System Information type 2bis, type 7 and type 8 messages | Phase 2 | All MS. Test purpose 2 is only applicable to EGSM900 and DCS 1 800 MS. Test purpose 4 is only applicable to E-GSM MS | | A | | |
| 20.6 | Cell reselection timings | Phase 2 | All MS | | A | | |
| 20.7 | Priority of cells | Phase 2 | All MS | | A | | |
| 20.8 | Cell reselection when C1 (serving cell) < 0 for 5 seconds | Phase 2 | All MS | | | | |
| 20.9 | Running average of the surrounding cell BCCH carrier signal levels | Phase 2 | All MS | | A | | |
| 20.10 | Running average of the serving cell BCCH carrier signal level | Phase 2 | All MS | | A | | |
| 20.11 | Updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list | Phase 2 | All MS | | A | | |
| 20.12 | Decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers | Phase 2 | All MS | | A | | |
| 20.13 | Decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers | Phase 2 | All MS | | A | | |
| 20.14 | Emergency calls | Phase 2 | MS supporting speech | | C52 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--|---------------------------|--------|--------------------------------|-----------|
| 20.15 | Cell reselection due to MS rejection "LA not allowed" | Phase 2 | MS supporting speech | | C52 | | |
| 20.16 | Downlink signalling failure | Phase 2 | All MS | | A | | |
| 20.17 | Cell selection if no suitable cell found in 10 s | Phase 2 | All MS | | A | | |
| 20.18 | Cell reselection due to MS rejection "Roaming not allowed in this LA" | Phase 2 | All MS | | A | | |
| 20.19 | Cell selection on release of SDCCH and TCH | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 20.20.1 | Multiband cell selection and reselection/Cell selection | Phase 2 | MS supporting simultaneous multiband operation | | C76 | TSPC_AddInfo_StoredListCellSel | |
| 20.20.2 | Multiband cell selection and reselection/Cell reselection | Phase 2 | MS supporting simultaneous multiband operation | | C76 | | |
| 20.21.1 | R-GSM cell selection | R96 | R-GSM MS | | C103 | | |
| 20.21.2 | R-GSM cell selection with varying signal strength values | | R-GSM MS | | C103 | | |
| 20.21.3 | R-GSM basic cell reselection | R96 | R-GSM MS | | C103 | | |
| 20.21.4 | R-GSM cell reselection using TEMPORARY_OFFSET, CELL_RESELECT_OFFSET, POWER_OFFSET and PENALTY_TIME parameters | R96 | R-GSM MS | | C103 | | |
| 20.21.5 | R-GSM cell reselection using parameters transmitted in the System Information type 2bis, type 7 and type 8 messages | R96 | R-GSM MS | | C103 | | |
| 20.21.6 | R-GSM cell reselection timing | R96 | R-GSM MS | | C103 | | |
| 20.21.7 | R-GSM priority of cells | R96 | R-GSM MS | | C103 | | |
| 20.21.8 | R-GSM cell reselection when C1 (serving cell) < 0 for 5 seconds | R96 | R-GSM MS | | C103 | | |
| 20.21.9 | R-GSM running average of the surrounding cell BCCH carrier signal levels | R96 | R-GSM MS | | C103 | | |
| 20.21.10 | R-GSM running average of the serving cell BCCH carrier signal level | R96 | R-GSM MS | | C103 | | |
| 20.21.11 | R-GSM updating the list of six strongest neighbour carriers and decoding the BCCH information of a new carrier on the list | R96 | R-GSM MS | | C103 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|-------------------------------|---------------------------|--------|------------------------------|-----------|
| 20.21.12 | R-GSM decoding the BCCH information of the neighbour carriers on the list of six strongest neighbour carriers | R96 | R-GSM MS | | C103 | | |
| 20.21.13 | R-GSM decoding the BSIC of the neighbour carriers on the list of six strongest neighbour carriers | R96 | R-GSM MS | | C103 | | |
| 20.21.14 | R-GSM emergency calls | R96 | R-GSM MS supporting speech | | C116 | | |
| 20.21.15 | R-GSM cell reselection due to MS rejection "LA not allowed" | R96 | R-GSM MS | | C103 | | |
| 20.21.16 | R-GSM downlink signalling failure | R96 | R-GSM MS | | C103 | | |
| 20.21.17 | R-GSM cell selection if no suitable cell found in 10 s | R96 | R-GSM MS | | C103 | | |
| 20.21.18 | R-GSM cell reselection due to MS rejection "Roaming not allowed in this LA" | R96 | R-GSM MS | | C103 | | |
| 20.21.19 | R-GSM cell selection on release of SDCCH and TCH | R96 | R-GSM MS | | C103 | | |
| 20.22.1 | Cell selection | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.2 | Cell reselection in Packet Idle mode | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.3 | Priority of cells | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.4 | Cell re-selection with cells in different routing area | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.5 | Network controlled Cell re-selection in Idle Mode | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.6 | Cell reselection timings | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.7 | Downlink signalling failure | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.8 | Cell selection when the best cell does not support GPRS | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.9-1 | Cell reselection when the best cell does not support GPRS | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.9-2 | Cell reselection when the best cell does not support GPRS | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.10 | Cell Selection-Search for Suitable Cell/ cell priority | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.11 | Cell Selection/No normal priority cell | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.12 | Cell Selection on "LA not allowed" | R97 | All GPRS MS supporting speech | | C456 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.13 | Cell Reselection based on C32 quality | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|-----------------------------------|---------------------------|--------|------------------------------|-----------|
| 20.22.14 | Void | | | | | | |
| 20.22.15 | Cell Reselection/ ready state/no reselection | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.16 | Cell Reselection/ ready state/ Reselection and Cell update procedure | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.17 | C2 reselection in another RA - no cell reselection | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.18 | C2 reselection in another Routing Area - Routing Area Update | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.19 | Borders between routing areas - reselection of a GPRS cell in a homogenous network | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.20 | Void | | | | | | |
| 20.22.21 | Void | | | | | | |
| 20.22.22 | Cell Reselection with cells in different Routing area - Cell Reselection on CCCH - PBCCH not present | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.23 | Void | | | | | | |
| 20.22.24 | Void | | | | | | |
| 20.22.25 | Void | | | | | | |
| 20.22.26 | Void | | | | | | |
| 20.22.28 | Void | | | | | | |
| 20.22.29 | Packet Measurement order procedure / Downlink transfer / Normal case/ 3G cell reselection dedicated parameters | R99 | MS supporting both GPRS and UTRAN | | C324 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.30.1 | Cell Reselection/usage of BA(GPRS) | R99 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.30.2 | Cell Reselection / usage of BA(GPRS) / Change of BA(GPRS) | R99 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.30.3 | Cell Reselection/usage of BA(GPRS)/ Measurement on first 32 entries | R99 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.22.31.1 | Network controlled cell reselection / Downlink transfer / Normal case/ Location and Routing Area Update/ NMO I | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|----------------------------------|---------------------------|--------|------------------------------|-----------|
| 20.22.31.2 | Network controlled cell reselection / Downlink transfer / Normal case/ Location and Routing Area Update/ NMO II | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 20.23.1 | COMPACT Cell Selection | R99 | All COMPACT MS | | C213 | | |
| 20.23.2 | COMPACT Cell reselection in Packet Idle mode | R99 | All COMPACT MS | | C213 | | |
| 20.23.3 | Priority of cells | R99 | All COMPACT MS | | C213 | | |
| 20.23.4 | Cell re-selection with cells in different routing area | R99 | All COMPACT MS | | C213 | | |
| 20.23.5 | COMPACT Network controlled Cell re-selection in Transfer Mode | R99 | All COMPACT MS | | C213 | | |
| 20.23.6 | COMPACT Cell reselection timings | R99 | All COMPACT MS | | C213 | | |
| 20.23.7 | COMPACT Downlink signalling failure | R99 | All COMPACT MS | | C213 | | |
| 20.23.8 | COMPACT Cell re-selection when target cell is BCCH supporting EGPRS and different routing area | R99 | All COMPACT MS | | C213 | | |
| 20.23.9 | Cell re-selection when target cell is COMPACT CPBCH in different routing area | R99 | All COMPACT MS | | C213 | | |
| 20.24.1 | SoLSA Cell Selection suitable cell | R99 | All SoLSA MS | | C207 | | |
| 20.24.2 | SoLSA Cell (Re)Selection emergency call | R99 | All SoLSA MS | | C207 | | |
| 20.24.3 | SoLSA Cell Reselection/idle mode support enabled | R99 | All SoLSA MS | | C207 | | |
| 20.24.4 | SoLSA Cell Reselection/idle mode support any | R99 | All SoLSA MS | | C207 | | |
| 20.24.5 | SoLSA Cell Reselection/LSA indication for idle mode | R99 | All SoLSA MS | | C207 | | |
| 20.25.2 | Intersystem Cell Reselection/Idle Mode/FDD_Qmin | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 20.25.3 | Intersystem Cell Reselection/Idle Mode/FDD_Qoffset | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 20.25.4 | Intersystem Cell Reselection/Idle Mode/Qsearch_I | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 21.1 | Signal strength | Phase 2 | All MS | | A | | |
| 21.2 | Signal strength selectivity | Phase 2 | All MS | | A | | |
| 21.3.1 | Signal quality under static conditions - TCH/FS | Phase 2 | MS supporting full rate speech | R9 | C24 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------|---|---------|--|---------------------------|--------|---|-----------|
| 21.3.2 | Signal quality under static conditions - TCH/HS | Phase 2 | MS supporting half rate speech | R10 | C13 | | |
| 21.3.3 | Signal quality under static conditions -TCH/AFS – DTX off | R98 | MS supporting AMR | | C203 | | |
| 21.3.4 | Signal quality under static conditions -TCH/AHS – DTX off | R98 | MS supporting AMR Half Rate | | C319 | | |
| 21.3.5 | Signal quality under static conditions -TCH/AFS – DTX on | R98 | MS supporting AMR | | C203 | | |
| 21.3.6 | Signal quality under static conditions -TCH/AHS – DTX on | R98 | MS supporting AMR Half Rate | | C319 | | |
| 21.4.1 | Signal quality under TUhigh propagation conditions | Phase 2 | All MS supporting speech | R11 | C52 | | |
| 21.4.2 | Signal quality under TUhigh propagation conditions -TCH/AFS | R98 | MS supporting AMR | | C203 | | |
| 21.4.3 | Signal quality under TUhigh propagation conditions - TCH/AHS | R98 | MS supporting AMR Half Rate | | C319 | | |
| 21.4.4 | Signal Quality Under TU High Propagation Conditions O-TCH/WFS | Rel-5 | MS supporting WB-AMR | | C366 | | |
| 21.8 | GMSK_MEAN_BEP Measurement for PDTCH | R99 | MS supporting EGPRS | | C216 | | |
| 21.9 | 8PSK_MEAN_BEP Measurement for PDTCH | R99 | MS supporting EGPRS | | C216 | | |
| 22.1 | Transmit power control timing and confirmation, single slot | R96 | All MS | | A | | |
| 22.2 | Void | | | | | | |
| 22.3 | GPRS Uplink Power Control – Use of α and Γ_{CH} parameters | R97 | All GPRS MS | R6 | C215 | | |
| 22.4 | GPRS Uplink Power Control – Independence of TS Power Control | R97 | All GPRS MS supporting GPRS multislots operation on the uplink | R6 | C385 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 22.5 | Void | | | | | | |
| 22.6 | Normal transmit power control timing and confirmation in ECSD | R99 | All ECSD MS | | C214 | | |
| 22.7 | ECSD Fast Power Control timing and interworking with normal power control | R99 | All MS capable of class B ECSD operation | | C214 | | |
| 22.8 | EGPRS Uplink Power Control – Use of α and Γ_{CH} parameters | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|---|---------------------------|--------|--|-----------|
| 22.9 | EGPRS Uplink Power Control – Independence of TS Power Control | R99 | All EGPRS MS supporting EGPRS Multislot Operation in Uplink Direction | | C410 | TSPC_Addinfo_Red_IntSlotRange_Mult_Conf | |
| 22.10 | Void | | | | | | |
| 22.11 | Power control in exclusive allocation mode. | R99 | MS supporting singleslot allocation in DTM/GPRS | | C310 | | |
| 22.12 | Downlink power control, PR mode A, GPRS TBF | R99 | All GPRS MS | | C215 | | |
| 22.13 | Enhanced Power Control (EPC) timing and measurement reporting in single slot operation | Rel-5 | MS supporting GERAN FEATURE PACKAGE 2 | | C426 | | |
| 22.14 | Enhanced Power Control (EPC) timing and measurement reporting in multislot operation | Rel-5 | MS supporting GERAN FEATURE PACKAGE 2 and HSCSD Multislot | | C427 | | |
| 23 | Single frequency reference | Phase 2 | All MS | | A | | |
| 25.2.1.1.1 | Initialization when contention resolution required, Normal initialization | Phase 2 | All MS | | A | | |
| 25.2.1.1.2.1 | Initialization failure, Loss of UA frame | Phase 2 | All MS | | A | | |
| 25.2.1.1.2.2 | Initialization failure, UA frame with different information field | Phase 2 | All MS | | A | | |
| 25.2.1.1.2.3 | Initialization failure, Information frame and supervisory frames in response to an SABM frame | Phase 2 | All MS | | A | | |
| 25.2.1.1.3 | Initialization denial | Phase 2 | All MS | | A | | |
| 25.2.1.1.4 | Total initialization failure | Phase 2 | All MS | | A | | |
| 25.2.1.2.1 | Normal initialization without contention resolution | Phase 2 | All MS | | A | | |
| 25.2.1.2.2 | Initialization failure | Phase 2 | All MS | | A | | |
| 25.2.1.2.3 | Initialization denial | Phase 2 | All MS | | A | | |
| 25.2.1.2.4 | Total initialization failure | Phase 2 | All MS | | A | | |
| 25.2.2.1 | Sequence counting and I frame acknowledgements | Phase 2 | All MS | | A | | |
| 25.2.2.2 | Receipt of an I frame in the timer recovery state | Phase 2 | All MS | | A | | |
| 25.2.2.3 | Segmentation and concatenation | Phase 2 | MS supporting USSD or CC protocol for at least one Bearer Capability | | C457 | TSPC_Serv_SS_unstruct TSPC_Addinfo_CCprotocol_oneBC | |
| 25.2.3 | Normal layer 2 disconnection | Phase 2 | All MS | | A | | |
| 25.2.4.1 | I frame loss (MS to SS) | Phase 2 | All MS | | A | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--|---------------------------|--------|--|-----------|
| 25.2.4.2 | RR response frame loss (SS to MS) | Phase 2 | All MS [covered in 25.2.2.2] | | A | | |
| 25.2.4.3 | RR response frame loss (MS to SS) | Phase 2 | All MS | | A | | |
| 25.2.5.1 | I frame with C bit set to zero | Phase 2 | All MS | | A | | |
| 25.2.5.2 | SABM frame with C bit set to zero | Phase 2 | All MS | | A | | |
| 25.2.6.1 | N(S) sequence error | Phase 2 | All MS | | A | | |
| 25.2.6.2 | N(R) sequence error | Phase 2 | All MS | | A | | |
| 25.2.6.3 | Improper F bit | Phase 2 | All MS [covered in 25.2.2.2] | | A | | |
| 25.2.7 | Test on receipt of invalid frames | Phase 2 | All MS | | A | | |
| 26.2.1.1 | Channel request/initial time | Phase 2 | All MS | | A | | |
| 26.2.1.2 | Channel request/repetition time | Phase 2 | All MS | | A | | |
| 26.2.1.3 | Channel request/random reference | Phase 2 | All MS | | A | | |
| 26.2.2-1 | IMSI detach and IMSI attach | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |
| 26.2.2-2 | IMSI detach and IMSI attach | Phase 2 | MS where SIM removal is possible without powering down | | C51 | TSPC_AddInfo_SIMRmv | |
| 26.2.2-3 | IMSI detach and IMSI attach | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_DetachOnPwrDn | |
| 26.2.2-4 | IMSI detach and IMSI attach | Phase 2 | All MS | | A | TSPC_AddInfo_SIMRmv TSPC_AddInfo_DetachOnSIMRmv TSPC_AddInfo_DetachOnPwrDn | |
| 26.2.3 | Sequenced MM/CC message transfer | Phase 2 | All MS | | C52 | | |
| 26.2.4-1 | Establishment cause, Procedure 1 (TCH) | Phase 2 | MS supporting a service on a traffic channel | | C37 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 | |
| 26.2.4-2 | Establishment cause, Procedure 2 (TCH/H) | Phase 2 | MS supporting a service on a half-rate channel | | C38 | TSPC_AddInfo_Half_rate_version_1 | |
| 26.2.4-3 | Establishment cause, Procedure 3 (TCH/FS) | Phase 2 | MS supporting speech teleservices | | C42 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Full_rate_version_3 TSPC_AddInfo_Half_rate_version_3 | |
| 26.2.4-4 | Establishment cause, Procedure 4 (data) | Phase 2 | MS supporting a data service | | C39 | TSPC_AddInfo_FullRateData TSPC_AddInfo_HalfRateData | |
| 26.2.4-5 | Establishment cause, Procedure 5 | Phase 2 | All MS | | A | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_SDCCHOnly | |
| 26.2.4-6 | Establishment cause, Procedure 6 | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |
| 26.2.4-7 | Establishment cause, Procedure 7 (non-call-SS) | Phase 2 | MS supporting a non call related supplementary service operation | | C40 | TSPC_AddInfo_SS | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.2.4-8 | Establishment cause, Procedure 8 (SMS/PP MO) | Phase 2 | MS supporting SMS/PP MO | | C41 | TSPC_Serv_TS22 | |
| 26.3.2 | MS indication of available PLMNs | Phase 2 | All MS | | A | | |
| 26.3.3.3.2.1 | MS will send only if BSS is "on air" | Phase 2 | All MS | | A | | |
| 26.3.3.3.2.2 | MS will send only if BSS is "on air" | Phase 2 | MS supporting speech | | C52 | | |
| 26.3.4 | Manual mode of PLMN selection | Phase 2 | All MS | | A | Type_MB_Simul | |
| 26.5.1 | Handling of unknown, unforeseen, and erroneous protocol data, and of parallel transactions/unknown protocol discriminator | Phase 2 | MS supporting at least one circuit switched basic service | | C412 | | |
| 26.5.2.1.1 | TI and skip indicator/RR/Idle Mode | Phase 2 | All MS | | A | | |
| 26.5.2.1.2 | TI and skip indicator/RR/RR-Connection established | Phase 2 | All MS | | A | | |
| 26.5.2.2 | TI and skip indicator/MM | Phase 2 | MS supporting at least one circuit switched basic service | | C412 | | |
| 26.5.2.3 | TI and skip indicator/CC | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.3.1 | Undefined or unexpected message type/undefined message type/CC | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.3.2 | Undefined or unexpected message type/undefined message type/MM | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.3.3 | Undefined or unexpected message type/undefined message type/RR | Phase 2 | MS supporting at least one circuit switched basic serv | | C412 | | |
| 26.5.3.4 | Undefined or unexpected message type/undefined message type/CC | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.4.1 | Unforeseen information elements in the non-imperative message part/duplicated information elements | Phase 2 | All MS | | A | | |
| 26.5.5.1.1.1 | Non-semantic mandatory IE errors/RR/missing mandatory IE error/special case | Phase 2 | All MS | | A | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 26.5.5.1.1.2 | Non-semantic mandatory IE errors/RR/missing mandatory IE error/general case | Phase 2 | All MS | | A | | |
| 26.5.5.1.2 | Non-semantic mandatory IE errors/RR/comprehension required | Phase 2 | MS supporting at least one circuit switched basic serv | | C412 | | |
| 26.5.5.2.1 | Non-semantic mandatory IE errors/MM/syntactically incorrect mandatory IE | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.5.2.2 | Non-semantic mandatory IE errors/MM/syntactically incorrect mandatory IE | Phase 2 | MS supporting at least one circuit switched basic serv | | C412 | | |
| 26.5.5.2.3 | Non-semantic mandatory IE errors/MM/comprehension required | Phase 2 | All MS | | A | | |
| 26.5.5.3.1.1 | Non-semantic mandatory IE errors/CC/missing mandatory IE/disconnect message | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.5.3.1.2 | Non-semantic mandatory IE errors/CC/missing mandatory IE/general case | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.5.3.2 | Non-semantic mandatory IE errors/CC/comprehension required | Phase 2 | MS supporting CC protocol for at least one Bearer Capability and at least one MO circuit switched basic service | | C411 | | |
| 26.5.6.1.1 | Unknown IE, comprehension not required/MM/IE unknown in the protocol | Phase 2 | All MS | | A | | |
| 26.5.6.1.2 | Unknown IE, comprehension not required/MM/IE unknown in the message | Phase 2 | All MS | | A | | |
| 26.5.6.2.1 | Unknown information elements in the non-imperative message part/CC/Call establishment | Phase 2 | MS supporting CC protocol for at least one Bearer Capability and at least one MO circuit switched basic service | | C411 | | |
| 26.5.6.2.2 | Unknown information elements in the non-imperative message part/CC/disconnect | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.6.2.3 | Unknown information elements in the non-imperative message part/CC/release | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|--|-----------|
| 26.5.6.2.4 | Unknown information elements in the non-imperative message part/CC/release complete | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.5.6.3 | Unknown IE in the non-imperative message part, comprehension not required/RR | Phase 2 | All MS | | A | | |
| 26.5.7.1.1 | Spare bits/RR/paging channel | Phase 2 | All MS | | A | | |
| 26.5.7.1.2 | Spare bits/RR/BCCH | Phase 2 | All MS | | A | | |
| 26.5.7.1.3 | Spare bits/RR/AGCH | Phase 2 | All MS | | A | | |
| 26.5.7.1.4 | Spare bits/RR/Connected Mode | Phase 2 | All MS | | A | | |
| 26.5.7.2 | Spare bits/MM | Phase 2 | All MS | | A | | |
| 26.5.7.3 | Spare bits/CC | Phase 2 | MS supporting at least one MT circuit switched basic service. | | C31 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 | |
| 26.6.1.1 | Immediate assignment/SDCCH or TCH assignment | Phase 2 | All MS | | A | TSPC_AddInfo_SDCCHOnly TSPC_AddInfo_HalfRate | |
| 26.6.1.2 | Immediate assignment/extended assignment | Phase 2 | All MS | | A | | |
| 26.6.1.3 | Immediate assignment/assignment rejection | Phase 2 | All MS | | A | | |
| 26.6.1.4 | Immediate assignment/ignore assignment | Phase 2 | All MS | | A | | |
| 26.6.1.5 | Immediate assignment after immediate assignment reject | Phase 2 | All MS | | A | | |
| 26.6.2.1.1 | Paging/normal/type 1 | Phase 2 | All MS | | A | | |
| 26.6.2.1.2 | Paging/normal/type 2 | Phase 2 | All MS | | A | | |
| 26.6.2.1.3 | Paging/normal/type 3 | Phase 2 | All MS | | A | | |
| 26.6.2.2 | Paging/extended | Phase 2 | All MS | | A | | |
| 26.6.2.3.1 | Paging/reorganization/procedure 1 | Phase 2 | All MS | | A | | |
| 26.6.2.3.2 | Paging/reorganization/procedure 2 | Phase 2 | All MS | | A | | |
| 26.6.2.4 | Paging/same as before | Phase 2 | All MS | | A | | |
| 26.6.2.5 | Paging/multislot CCCH | Phase 2 | All MS | | A | | |
| 26.6.3.1 | Measurement/no neighbours | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.6.3.2 | Measurement/all neighbours present | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.6.3.3 | Measurement/barred cells and non-permitted NCCs | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.6.3.4 | Measurement/DTX | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C464 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---|---------------------------|--------|--|-----------|
| 26.6.3.5 | Measurement/Frequency Formats | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.6.3.6 | Measurement/Multiband environment | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.3.7 | Measurement/New Cell Reporting | R96 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.3.8 | Enhanced Measurement /all neighbours present | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 26.6.3.9 | Enhanced Measurement Report / Measurement Parameters | R99 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.3.10 | Enhanced Measurement Report / EMR Reporting after Handover | R99 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.4.1 | Dedicated assignment/successful case | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_Halfrate | |
| 26.6.4.2.1 | Dedicated assignment/failure/failure during active state | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_Halfrate TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.4.2.2 | Dedicated assignment/failure/general case | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_Halfrate | |
| 26.6.5.1-1 | Handover/successful/active call/non-synchronized, M = 1 | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-2 | Handover/successful/active call/non-synchronized, M = 2 | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-3 | Handover/successful/active call/non-synchronized, M = 3 | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-4 | Handover/successful/active call/non-synchronized, M = 4 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-5 | Handover/successful/active call/non-synchronized, M = 5 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-6 | Handover/successful/active call/non-synchronized, M = 6 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-7 | Handover/successful/active call/non-synchronized, M = 7 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.1-8 | Handover/successful/active call/non-synchronized, M = 8 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_AddInfo_SDCCHOnly | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|---|---------|--|---------------------------|--------|---|-----------|
| 26.6.5.2-1 | Handover/successful/call under establishment/non-synchronized, M = 1 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-2 | Handover/successful/call under establishment/non-synchronized, M = 2 | Phase 2 | MS which support at least one MO circuit switched basic service and half rate version 1 speech codec | | C384 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-3 | Handover/successful/call under establishment/non-synchronized, M = 3 | Phase 2 | MS which support at least one MO circuit switched basic service and support dual rate channel type | | C323 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-4 | Handover/successful/call under establishment/non-synchronized, M = 4 | Phase 2 | MS which support at least one MO circuit switched basic service and support dual rate channel type | | C323 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-5 | Handover/successful/call under establishment/non-synchronized, M = 5 | Phase 2 | MS which support at least one MO circuit switched basic service and support dual rate channel type | | C323 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-6 | Handover/successful/call under establishment/non-synchronized, M = 6 | Phase 2 | MS which support at least one MO circuit switched basic service and support dual rate channel type | | C323 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-7 | Handover/successful/call under establishment/non-synchronized, M = 7 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-8 | Handover/successful/call under establishment/non-synchronized, M = 8 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-9 | Handover/successful/call under establishment/non-synchronized, M = 9 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.2-10 | Handover/successful/call under establishment/non-synchronized, M = 10 | Phase 2 | MS which support at least one MO circuit switched basic service and half rate version 1 speech codec | | C384 | TSPC_AddInfo_SDCCHOnly | |
| 26.6.5.3-1 | Handover/successful/active call/finely synchronized, M = 1 | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.5.3-2 | Handover/successful/active call/finely synchronized, M = 2 | Phase 2 | MS supporting CC protocol for at least one bearer capability and half rate version 1 speech codec | | C50 | TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.5.4-1 | Handover/successful/call under establishment/finely synchronized, M = 1 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.5.4-2 | Handover/successful/call under establishment/finely synchronized, M = 2 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_Type_xxx (all appropriate power classes) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|---|-----------|
| 26.6.5.4-3 | Handover/successful/call under establishment/finely synchronized, M = 3 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.5.4-4 | Handover/successful/call under establishment/finely synchronized, M = 4 | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.5.5.1 | Handover/successful/active call/pre-synchronized/Timing Advance IE not included | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.5.5.2 | Handover/successful/call being established/pre-synchronized/timing advance IE is included/reporting of observed time difference requested. | Phase 2 | MS which support at least one MO circuit switched basic service | | C36 | | |
| 26.6.5.6 | Handover/successful/active call/pseudo synchronized | Phase 2 | MS supporting CC protocol for at least one bearer capability and supporting the pseudo synchronized handover procedure | | C79 | | |
| 26.6.5.7 | Handover/successful/active call/non-synchronized/reporting of observed time difference requested. | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.5.8 | Handover/layer 3 failure | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.5.9 | Handover/layer 1 failure | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |
| 26.6.6.1 | Frequency redefinition | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate | |
| 26.6.7.1 | Test of the channel mode modify procedure/full rate | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_96Data TSPC_AddInfo_48DataF TSPC_AddInfo_24DataF | |
| 26.6.7.2 | Test of the channel mode modify procedure/half rate | Phase 2 | MS supporting a service on a half-rate channel | | C38 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_96Data TSPC_AddInfo_48DataF TSPC_AddInfo_24DataF | |
| 26.6.8.1 | Ciphering mode/start ciphering | Phase 2 | MS supporting CC protocol for at least one bearer capability and supporting encryption algorithm A5/1 | | C47 | TSPC_Feat_A53 | |
| 26.6.8.2 | Ciphering mode/no ciphering | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C43 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|--|---------------------------|--------|---|-----------|
| 26.6.8.3 | Ciphering mode/old cipher key | Phase 2 | MS supporting CC state U10 and supporting encryption algorithm A5/1 | | C47 | TSPC_Feat_A53 | |
| 26.6.8.4 | Ciphering mode/change of mode, algorithm and key | Phase 2 | All MS | | A | TSPC_Feat_A53 TSPC_Type_xxx (all appropriate power classes) | |
| 26.6.8.5 | Ciphering mode/IMEISV request | Phase 2 | All MS | | A | | |
| 26.6.8.6 | Ciphering mode / Non support of algorithm A5/2 | Phase2 | All MS | | A | | |
| 26.6.11.1 | Classmark change | Phase 2 | MS supporting CC protocol for at least one bearer capability and supporting RF amplification | | C48 | TSPC_Type_xxx (all appropriate power classes) TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Full_rate_version_2 TSPC_AddInfo_Full_rate_version_3 | |
| 26.6.11.2 | Classmark interrogation | Phase 2 | All MS | | A | | |
| 26.6.11.3 | Classmark interrogation / UTRAN Classmark Change | R99 | MS supporting both GSM and UTRAN | | C285 | | |
| 26.6.11.4 | Early UTRAN Classmark Sending | R99 | MS supporting both GSM and UTRAN | | C285 | | |
| 26.6.12.1 | Channel release/SDCCH | Phase 2 | All MS | | A | | |
| 26.6.12.2 | Channel release/SDCCH - no L2 ACK | Phase 2 | All MS | | A | | |
| 26.6.12.3 | Channel release/TCH-F | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C339 | | |
| 26.6.12.4 | Channel release/TCH-F - no L2 ACK | Phase 2 | MS supporting CC protocol for at least one bearer capability | | C339 | | |
| 26.6.13.1 | Dedicated assignment with starting time/successful case/time not elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.2 | Dedicated assignment with starting time/successful case/time elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.3 | Dedicated assignment with starting time and frequency redefinition/failure case/time not elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.4 | Dedicated assignment with starting time and frequency redefinition/failure case/time elapsed | Phase 2 | All MS | | A | | |
| 26.6.13.5 | Handover with starting time/successful case/time not elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|---|-----------|
| 26.6.13.6 | Handover with starting time/successful case/time elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.7 | Handover with starting time and frequency redefinition/failure case/time not elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.8 | Handover with starting time and frequency redefinition/failure case/time elapsed | Phase 2 | All MS | | A | | |
| 26.6.13.9 | Immediate assignment with starting time/successful case/time not elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.13.10 | Immediate assignment with starting time/successful case/time elapsed | Phase 2 | All MS | | A | TSPC_AddInfo_Halfrate TSPC_AddInfo_SDCCHOnly | |
| 26.6.23.1 | Repeated SACCH / Downlink Repeated SACCH | Rel 6 | All MS supporting Repeated SACCH | | C414 | | |
| 26.6.23.2 | Repeated SACCH / Uplink Repeated SACCH | Rel 6 | All MS supporting Repeated SACCH | | C414 | | |
| 26.6.23.3 | Repeated SACCH / Uplink Repeated SACCH with SAPI 3 frames | Rel 6 | All MS supporting Repeated SACCH | | C414 | | |
| 26.7.1 | TMSI reallocation | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.2.1 | Authentication accepted | Phase 2 | All MS | | A | | |
| 26.7.2.2 | Authentication rejected | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.3.1-1 | General Identification | Phase 2 | All MS | R1 | A | | |
| 26.7.3.1-2 | General Identification | Phase 2 | All MS | R1 | A | | |
| 26.7.3.2 | Handling of IMSI shorter than the maximum length | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | TSPC_Feat_OnOff | |
| 26.7.4.1 | Location updating/accepted | Phase 2 | All MS | R1 | A | | |
| 26.7.4.2.1 | Location updating/rejected/IMSI invalid | Phase 2 | All MS | R1 | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.4.2.2-1 | Location updating/rejected/PLMN not allowed, test 1 | Phase 2 | All MS | R1 | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_AutoAutoMode | |
| 26.7.4.2.2-2 | Location updating/rejected/PLMN not allowed, test 2 | Phase 2 | All MS | R1 | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_AutoAutoMode | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|--|-----------|
| 26.7.4.2.3 | Location updating/rejected/location area not allowed | Phase 2 | All MS | R1 | A | TSPC_Feat_OnOff TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.4.2.4-1 | Location updating/rejected/national roaming, Procedure 1 | Phase 2 | All MS | R1 | A | TSPC_Feat_OnOff TSPC_AddInfo_AutoAutoMode | |
| 26.7.4.2.4-2 | Location updating/rejected/national roaming, Procedure 2 | Phase 2 | All MS | | A | TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.4.2.4-3 | Location updating/rejected/national roaming, Procedure 3 | Phase 2 | All MS | | A | | |
| 26.7.4.2.4-4 | Location updating/rejected/national roaming, Procedure 4 | Phase 2 | All MS | | A | | |
| 26.7.4.2.4-5 | Location updating/rejected/national roaming, Procedure 5 | Phase 2 | MS supporting SIM removal without powering down | | C51 | | |
| 26.7.4.3.1 | Location updating/abnormal cases/random access fails | Phase 2 | All MS | | A | | |
| 26.7.4.3.2 | Location updating/abnormal cases/attempt counter less or equal to 4, LAI different | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.4.3.3 | Location updating/abnormal cases/attempt counter equal to 4 | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.4.3.4 | Location updating/abnormal cases/attempt counter less or equal to 4, stored LAI equal to broadcast LAI | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 26.7.4.4 | Location updating/release/expiry of T3240 | Phase 2 | All MS | | A | | |
| 26.7.4.5.1 | Location updating/periodic spread | Phase 2 | All MS | | A | | |
| 26.7.4.5.2 | Location updating/periodic normal/test 1 | Phase 2 | All MS | | A | | |
| 26.7.4.5.3 | Location updating/periodic normal/test 2 | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 26.7.4.5.4.1 | Location updating/periodic HPLMN search/MS waits time T | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.4.5.4.2 | Location updating/periodic HPLMN search/MS in manual mode | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|--|---------------------------|--------|--|-----------|
| 26.7.4.5.4.3 | Location updating/periodic HPLMN search/MS waits at least two minutes and at most T minutes | Phase 2 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.4.5.4.4 | Location updating/periodic search of the higher priority PLMN, when a MS is receiving foreign country's VPLMN/MS is in automatic mode. | R99 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.4.5.4.5 | Location updating/periodic search of the HPLMN, when a MS is receiving foreign country's VPLMN/MS is in automatic mode | R99 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.4.5.4.6 | Location updating/periodic search for higher priority PLMN when the list of equivalent PLMNs includes the HPLMN, when a MS is registered in a foreign country's VPLMN/MS is in automatic mode | R99 | All MS | | A | TSPC_Feat_OnOff | |
| 26.7.4.6 | Location updating/interworking of attach and periodic | Phase 2 | All MS | | A | | |
| 26.7.5.2 | MM connection/establishment with cipher and repeated FACCH | Phase 2 | All MS | | A | TSPC_AddInfo_HalfRate | |
| 26.7.5.3 | MM connection/establishment without cipher | Phase 2 | All MS | | A | | |
| 26.7.5.4 | MM connection/establishment rejected | Phase 2 | All MS | | A | | |
| 26.7.5.5 | MM connection/establishment rejected cause 4 | Phase 2 | All MS | | A | | |
| 26.7.5.6 | MM connection/expiry T3230 | Phase 2 | All MS | | A | | |
| 26.7.5.7.1 | MM connection/abortion by the network/cause #6 | Phase 2 | All MS | | A | TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_AddInfo_Full_rate_version_1 | |
| 26.7.5.7.2 | MM connection/abortion by the network/cause not equal to #6 | Phase 2 | MS supporting a non call related supplementary service operation | | C40 | | |
| 26.7.5.8.1 | MM connection/follow-on request pending/test 1 | Phase 2 | All MS | | A | | |
| 26.7.5.8.2 | MM connection/follow-on request pending/test 2 | Phase 2 | All MS | | A | TSPC_AddInfo_followOnReq | |
| 26.7.5.8.3 | MM connection/follow-on request pending/test 3 | Phase 2 | All MS | | A | TSPC_Addinfo_MOsvc | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|--|---------------------------|--------|---|-----------|
| 26.7.6.1.1 | Network Identity and Timezone (NITZ) | R97 | All NITZ (Time) capable MS | | C335 | TSPC_NITZ_DST TSPC_NITZ_Universal_Time TSPC_NITZ_Time_Zone TSPC_Feat_OnOff | |
| 26.8.1.2.1.1 | Outgoing call/U0 null state/MM connection requested | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.2.1 | Outgoing call/U0.1 MM connection pending/CM service rejected | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.2.2 | Outgoing call/U0.1 MM connection pending/CM service accepted | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.2.3 | Outgoing call/U0.1 MM connection pending/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | TSPC_Type_UTRAN | |
| 26.8.1.2.3.1 | Outgoing call/U1 call initiated/receiving CALL PROCEEDING | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.3.2 | Outgoing call/U1 call initiated/rejecting with RELEASE COMPLETE | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.3.3 | Outgoing call/U1 call initiated/T303 expiry | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.3.4 | Outgoing call/U1 call initiated/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.3.5 | Outgoing call/U1 call initiated/receiving ALERTING | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.3.6 | Outgoing call/U1 call initiated/entering state U10 | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.3.7 | Outgoing call/U1 call initiated/unknown message received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.1 | Outgoing call/U3 MS originating call proceeding/ALERTING received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.2 | Outgoing call/U3 MS originating call proceeding/CONNECT received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.3 | Outgoing call/U3 MS originating call proceeding/PROGRESS received without in band information | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.8.1.2.4.4 | Outgoing call/U3 MS originating call proceeding/PROGRESS with in band information | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.4.5 | Outgoing call/U3 MS originating call proceeding/DISCONNECT with in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.6 | Outgoing call/U3 MS originating call proceeding/DISCONNECT without in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.4.7 | Outgoing call/U3 MS originating call proceeding/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.4.8 | Outgoing call/U3 MS originating call proceeding/termination requested by the user | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.4.9 | Outgoing call/U3 MS originating call proceeding/traffic channel allocation | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.10 | Outgoing call/U3 MS originating call proceeding/timer T310 timeout | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.11 | Outgoing call/U3 MS originating call proceeding/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.12 | Outgoing call/U3 MS originating call proceeding/unknown message received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.4.13 | Outgoing call/U3 MS originating call proceeding/Internal alerting indication | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |
| 26.8.1.2.5.1 | Outgoing call/U4 call delivered/CONNECT received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.5.2 | Outgoing call/U4 call delivered/termination requested by the user | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.5.3 | Outgoing call/U4 call delivered/DISCONNECT with in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.5.4 | Outgoing call/U4 call delivered/DISCONNECT without in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.5.5 | Outgoing call/U4 call delivered/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.8.1.2.5.6 | Outgoing call/U4 call delivered/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.5.7 | Outgoing call/U4 call delivered/traffic channel allocation | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.5.8 | Outgoing call/U4 call delivered/unknown message received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.6.1 | U10 call active/termination requested by the user | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.6.2 | U10 call active/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.6.3 | U10 call active/DISCONNECT with in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.6.4 | U10 call active/DISCONNECT without in band tones | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.6.5 | U10 call active/RELEASE COMPLETE received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.6.6 | U10 call active/SETUP received | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | TSPC_Serv_SS_CW | |
| 26.8.1.2.7.1 | U11 disconnect request/clear collision | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.7.2 | U11 disconnect request/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.7.3 | U11 disconnect request/timer T305 time-out | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.7.4 | U11 disconnect request/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.7.5 | U11 disconnect request/unknown message received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.8.1 | U12 disconnect indication/call releasing requested by the user | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |
| 26.8.1.2.8.2 | U12 disconnect indication/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |
| 26.8.1.2.8.3 | U12 disconnect indication/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |
| 26.8.1.2.8.4 | U12 disconnect indication/unknown message received | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.8.1.2.9.1 | Outgoing call/U19 release request/timer T308 time-out | Phase 2 | MS supporting at least one MO circuit switched basic service | R1 | C36 | | |
| 26.8.1.2.9.2 | Outgoing call/U19 release request/2nd timer T308 time-out | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.9.3 | Outgoing call/U19 release request/RELEASE received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.9.4 | Outgoing call/U19 release request/RELEASE COMPLETE received | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.2.9.5 | Outgoing call/U19 release request/lower layer failure | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.1.3.1.1 | Incoming call/U0 null state/SETUP received with a non supported bearer capability | Phase 2 | MS supporting CC protocol for at least one Bearer Capability | | C43 | | |
| 26.8.1.3.2.1 | Incoming call/U6 call present/automatic call rejection | Phase 2 | MS supporting at least one MT circuit switched basic service and supporting refusal of call | | C130 | | |
| 26.8.1.3.3.1 | Incoming call/U9 mobile terminating call confirmed/alerting or immediate connecting | Phase 2 | MS supporting at least one MT circuit switched basic service | R1 | C31 | TSPC_AddInfo_ImmConn | |
| 26.8.1.3.3.2 | Incoming call/U9 mobile terminating call confirmed/TCH assignment | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.3.3 | Void | | | | | | |
| 26.8.1.3.3.4 | Incoming call/U9 mobile terminating call confirmed/DISCONNECT received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | R1 | C55 | | |
| 26.8.1.3.3.5 | Incoming call/U9 mobile terminating call confirmed/RELEASE received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.3.6 | Incoming call/U9 mobile terminating call confirmed/lower layer failure | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | TSPC_Type_UTRAN | |
| 26.8.1.3.3.7 | Incoming call/U9 mobile terminating call confirmed/unknown message received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.8.1.3.4.1 | Incoming call/U7 call received/call accepted | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.2 | Incoming call/U7 call received/termination requested by the user | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.3 | Incoming call/U7 call received/DISCONNECT received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.4 | Incoming call/U7 call received/RELEASE received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.5 | Incoming call/U7 call received/lower layer failure | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | TSPC_Type_UTRAN | |
| 26.8.1.3.4.6 | Incoming call/U7 call received/unknown message received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.7 | Incoming call/U7 call received/TCH assignment | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.4.8 | Incoming call/U7 call received/RELEASE COMPLETE received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.5.1 | Incoming call/U8 connect request/CONNECT acknowledged | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | TSPC_AddInfo_ImmConn | |
| 26.8.1.3.5.2 | Incoming call/U8 connect request/timer T313 time-out | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | TSPC_AddInfo_ImmConn | |
| 26.8.1.3.5.3 | Incoming call/U8 connect request/termination requested by the user | Phase 2 | MS supporting at least one MT circuit switched basic | | C31 | TSPC_AddInfo_ImmConn | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 26.8.1.3.5.4 | Incoming call/U8 connect request/DISCONNECT received with in-band information | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.5.5 | Incoming call/U8 connect request/DISCONNECT received without in-band information | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.5.6 | Incoming call/U8 connect request/RELEASE received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.5.7 | Incoming call/U8 connect request/lower layer failure | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | TSPC_Type_UTRAN | |
| 26.8.1.3.5.8 | Incoming call/U8 connect request/TCH assignment | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.3.5.9 | Incoming call/U8 connect request/unknown message received | Phase 2 | MS supporting at least one MT circuit switched basic service for which immediate connect is not used | | C55 | | |
| 26.8.1.4.1.1 | In-call functions/DTMF information transfer/basic procedures | Phase 2 | MS supporting at least one MO circuit switched basic service for telephony | | C56 | | |
| 26.8.1.4.2.1 | In-call functions/User notification/MS terminated | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | | |
| 26.8.1.4.3.1 | In-call functions/channel changes/a successful channel change in active state/ Handover and Assignment Command | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | | |
| 26.8.1.4.3.2 | In-call functions/channel changes/an unsuccessful channel change in active mode/ Handover and Assignment Command | Phase 2 | MS supporting at least one MT circuit switched basic service | | C31 | | |
| 26.8.1.4.4.1 | In-call functions/MS terminated in-call modification/modify when new mode is not supported | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | TSPC_AddInfo_InCallMod | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 26.8.1.4.5.1 | In-call functions/MS originated in-call modification/a successful case of modifying | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.2 | In-call functions/MS originated in-call modification/modify rejected | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.3 | In-call functions/MS originated in-call modification/an abnormal case of acceptance | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.4 | In-call functions/MS originated in-call modification/an abnormal case of rejection | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.5 | In-call functions/MS originated in-call modification/time-out of timer T323 | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.6 | In-call functions/MS originated in-call modification/a successful channel change in state mobile originating modify | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.7 | In-call functions/MS originated in-call modification/an unsuccessful channel change in state mobile originating modify | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.8 | In-call functions/MS originated in-call modification/unknown message received | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.1.4.5.9 | In-call functions/MS originated in-call modification/a release complete received | Phase 2 | MS supporting at least one dual mode bearer capability service (BS61, BS81 or TS61) | | C58 | | |
| 26.8.2.1 | Call Re-establishment/call present, re-establishment allowed | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.2.2 | Call Re-establishment/call present, re-establishment not allowed | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.2.3 | Call Re-establishment/call under establishment, transmission stopped | Phase 2 | MS supporting at least one MO circuit switched basic service | | C36 | | |
| 26.8.3 | User to user signalling | R96 | MS supporting at least one MT circuit switched basic service and support of User-to-User signalling | | C450 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--|-----------|
| 26.9.2 | Structured procedures/MS originated call/early assignment | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 | |
| 26.9.3 | Structured procedures/MS originated call/late assignment | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 | |
| 26.9.4 | Structured procedures/MS terminated call/early assignment | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_ImmConn | |
| 26.9.5 | Structured procedures/MS terminated call/late assignment | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_ImmConn | |
| 26.9.6.1.1 | Structured procedures/emergency call/idle updated/preferred channel rate | Phase 2 | MS supporting speech | | C52 | TSPC_AddInfo_Half_rate_version_1 TSPC_R99_Emerg | |
| 26.9.6.1.2 | Structured procedures/emergency call/idle updated, non-preferred channel rate | Phase 2 | MS supporting half-rate speech | | C13 | TSPC_AddInfo_Half_rate_version_1 TSPC_R99_Emerg | |
| 26.9.6.2.1 | Structured procedures/emergency call/idle, no IMSI/accept case | Phase 2 | MS supporting speech | | C52 | | |
| 26.9.6.2.2 | Structured procedures/emergency call/idle, no IMSI/reject case | Phase 2 | MS supporting speech | | C52 | | |
| 26.9.7 | Directed Retry/Mobile Originated Call | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Half_rate_version_1 | |
| 26.9.8 | Directed Retry/Mobile Terminated Call | Phase 2 | MS supporting at least one teleservice (except emergency call and dual service) | | C131 | TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_ImmConn | |
| 26.10.2.1 | E-GSM or R-GSM signalling/RR/Measurement | Phase 2 | MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability | L5 | C123 | TSPC_Type_GSM_R_Band | |
| 26.10.2.2 | E-GSM or R-GSM signalling/RR/Immediate assignment | Phase 2 | MS supporting E-GSM or R-GSM | L5 | C124 | TSPC_Type_GSM_R_Band | |
| 26.10.2.3 | E-GSM or R-GSM signalling/RR/channel assignment procedure | Phase 2 | MS supporting E-GSM or R-GSM | L5 | C124 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|---|---------|--|---------------------------|--------|--|-----------|
| 26.10.2.4.1 | E-GSM or R-GSM signalling/RR/Handover/Successful handover | Phase 2 | MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability | L5 | C123 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |
| 26.10.2.4.2 | E-GSM or R-GSM signalling/RR/Handover/layer 1 failure | Phase 2 | MS supporting E-GSM or R-GSM and supporting CC protocol for at least one Bearer Capability | L5 | C123 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |
| 26.10.2.5 | E-GSM or R-GSM signalling/RR/Frequency Redefinition | Phase 2 | MS supporting E-GSM or R-GSM | L5 | C124 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |
| 26.10.3.1 | E-GSM or R-GSM signalling/Structured procedure/Mobile originated call | Phase 2 | MS supporting E-GSM or R-GSM and supporting at least one MO teleservice | L5 | C125 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |
| 26.10.3.2 | E-GSM or R-GSM signalling/Structured procedures/emergency call | Phase 2 | MS supporting E-GSM or R-GSM and supporting speech | L5 | C126 | TSPC_Type_GSM_R_Band TSPC_AddInfo_Full_rate_version_1 | |
| 26.11.2.1 | Multiband signalling/RR/Immediate assignment procedure | Phase 2 | MS supporting simultaneous multiband operation | | C76 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.2.2.1 | Multiband signalling/RR/Handover/successful/active call/non-synchronized | Phase 2 | MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability | | C78 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.2.2.2 | Multiband signalling/RR/Handover/layer 1 failure | Phase 2 | MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability | | C78 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.2.2.3 | Multiband signalling/RR/Handover/Multiband BCCH/successful/active call/non synchronized | Phase 2 | MS supporting simultaneous multiband operation and supporting CC protocol | | C78 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|---------|---|---------------------------|--------|---|-----------|
| 26.11.2.2.4 | Multiband signalling/RR/Handover/ Multiband BCCH/Intracell Handover - Interband Assignment | Phase 2 | MS supporting simultaneous multiband operation and supporting CC protocol | | C78 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band TSPC_AddInfo_HalfRate | |
| 26.11.2.3 | Multiband signalling/RR/Measurement reporting | Phase 2 | MS supporting simultaneous multiband operation and supporting CC protocol for at least one Bearer Capability | | C78 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.3.1.1 | Multiband signalling/MM/Location updating/accepted | Phase 2 | MS supporting simultaneous multiband operation | | C76 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.3.1.2 | Multiband signalling/MM/Location updating/periodic | Phase 2 | MS supporting simultaneous multiband operation | | C76 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.5.1 | Multiband signalling/Structured procedures/MS originated call/early assignment | Phase 2 | MS supporting simultaneous multiband operation and supporting at least one MO teleservice | | C127 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |
| 26.11.5.2 | Multiband signalling/Structured procedures/MS terminated call/late assignment | Phase 2 | MS supporting simultaneous multiband operation and supporting at least one MT teleservice | | C127 | TSPC_Type_GSM_450_Band TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_480_Band TSPC_Type_DCS_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_710_Band | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|---------|--|---------------------------|--------|---|-----------|
| 26.12.1 | EFR signalling/test of the channel mode modify procedure | Phase 2 | MS supporting EFR speech | | C83 | TSPC_AddInfo_Full_rate_version_3 TSPC_AddInfo_24DataF TSPC_AddInfo_48DataF TSPC_AddInfo_96Data | |
| 26.12.2.1 | EFR signalling/Handover/active call/successful case | Phase 2 | MS supporting EFR speech | | C83 | TSPC_AddInfo_Half_rate_version_1 | |
| 26.12.3 | EFR signalling/Structured procedures/MS originated call/late assignment | Phase 2 | MS supporting EFR speech and at least one MO circuit switched basic service | | C84 | TSPC_AddInfo_Half_rate_version_1 | |
| 26.12.4 | EFR signalling/Structured procedures/MS terminated call/early assignment | Phase 2 | MS supporting EFR speech and at least one MT circuit switched basic service | | C85 | TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_ImmConn | |
| 26.12.5 | EFR signalling/Structured procedures/emergency call | Phase 2 | MS supporting EFR speech | | C83 | TSPC_AddInfo_Half_rate_version_1 TSPC_R99_Emerg | |
| 26.12.6 | EFR Signalling/Directed Retry/Mobile Originated Call | Phase 2 | MS supporting EFR speech | | C83 | | |
| 26.12.7 | EFR Signalling/Directed Retry/Mobile Terminated Call | Phase 2 | MS supporting EFR speech | | C83 | TSPC_AddInfo_ImmConn | |
| 26.13.1.1.1 | Multislot signalling/RR/Measurement symmetric | R96 | MS supporting Multislot class and CC protocol for at least one Bearer Capability | | C87 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.1.2 | Multislot signalling/RR/Measurement asymmetric | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.1.1.3 | Multislot signalling/RR/Measurement asymmetric/Change of the reported subchannel | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.1.2.1 | Multislot signalling/RR/Dedicated assignment/successful case | R96 | HSCSD Multislot MS | | C86 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.2.2 | Multislot signalling/RR/Dedicated assignment/failure/general case | R96 | HSCSD Multislot MS | | C86 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.3.1 | Multislot signalling/RR/Handover/successful/active call/non-synchronized | R96 | MS supporting Multislot class and CC protocol for at least one Bearer Capability | | C87 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.3.2 | Multislot signalling/RR/Handover/successful/call under establishment/non-synchronized/resource upgrading | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|---|---------|--|---------------------------|--------|--|-----------|
| 26.13.1.3.3 | Multislot signalling/RR/Handover/successful/active call/finely synchronized/resource downgrading | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.1.3.4 | Multislot signalling/RR/Handover/successful/call under establishment/finely synchronized/relocation of channels | R96 | MS supporting Multislot class and CC protocol for at least one Bearer Capability | | C87 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.3.5 | Multislot signalling/RR/Handover/successful/call under establishment/pre-synchronized/resource upgrading | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.1.4 | Multislot signalling/RR/Test of the channel mode modify procedure | R96 | MS supporting Multislot class and CC protocol for at least one Bearer Capability | | C87 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.1.5 | Multislot signalling/RR/Early classmark sending | R96 | HSCSD Multislot MS | | C86 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.2.1.1 | Multislot signalling/CC/In-call functions/User initiated service level upgrade/successful | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.2.1.2 | Multislot signalling/CC/In-call functions/User initiated service level downgrade/successful | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.2.1.3 | Multislot signalling/CC/In-call functions/User initiated service level upgrade/Time-out of T323 | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.2.1.4 | Multislot signalling/CC/In-call functions/User initiated service level upgrade/modify reject | R96 | MS supporting Multislot class 2 and above and CC protocol for at least one Bearer Capability | | C455 | TSPC_Type_Multislot_ClassX (where X = 2..18) | |
| 26.13.3.1 | Multislot signalling/Structured procedures/MS originated call/early assignment/HSCSD/non-transparent | R96 | MS supporting Multislot class and at least one MO circuit switched basic service | | C88 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.3.2 | Multislot signalling/Structured procedures/MS originated call/late assignment/HSCSD/non-transparent | R96 | MS supporting Multislot class and at least one MO circuit switched basic service | | C88 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|---------|--|---------------------------|--------|---|-----------|
| 26.13.3.3 | Multislot signalling/Structured procedures/MS originated call/early assignment/HSCSD/transparent | R96 | MS supporting Multislot class and at least one MO circuit switched basic service | | C88 | TSPC_Type_Multislot_ClassX (where X = 1..18) | |
| 26.13.3.4 | Multislot signalling/Structured procedures/MS terminated call/early assignment/HSCSD/non-transparent | R96 | MS supporting Multislot class and at least one MT circuit switched basic service | | C89 | TSPC_Type_Multislot_ClassX (where X = 1..18) TSPC_AddInfo_ImmConn | |
| 26.13.3.5 | Multislot signalling/Structured procedures/MS terminated call/early assignment/HSCSD/transparent | R96 | MS supporting Multislot class and at least one MT circuit switched basic service | | C89 | TSPC_Type_Multislot_ClassX (where X = 1..18) TSPC_AddInfo_ImmConn | |
| 26.14.1.1 | Notification/notification indication | R96 | MS supporting VGCS or VBS listening | | C104 | TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking | |
| 26.14.1.2 | Notification/NCH position | R96 | MS supporting VGCS or VBS listening | | C104 | | |
| 26.14.1.3 | Notification/Reduced NCH monitoring | R96 | MS supporting VGCS or VBS listening and reduced monitoring | | C105 | TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking | |
| 26.14.1.4 | Notification/limited service | R96 | MS supporting VGCS or VBS listening | | C104 | TSPC_Addinfo_VGCS_Originating TSPC_Addinfo_VBS_Originating | |
| 26.14.2.1 | Paging/Paging indication | R96 | MS supporting VGCS or VBS listening | | C104 | TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking TSPC_Serv_eMLPP TSPC_AddInfo_MonitorPCH_GroupTransmitMode | |
| 26.14.2.2 | Paging/Notification | R96 | MS supporting VGCS or VBS listening | | C104 | TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking | |
| 26.14.3.1 | RR Procedures/frequency redefinition | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |
| 26.14.3.2 | RR Procedures/assignment | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |
| 26.14.3.3 | RR Procedures/handover/successful in group transmit mode | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |
| 26.14.3.4 | RR Procedures/handover/successful at group call establishment | R96 | MS supporting VGCS/VBS originating | | C107 | | |
| 26.14.3.5 | RR Procedures/handover/failure | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |
| 26.14.3.6.1 | RR Procedures/Measurement/all neighbours present | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|---|---------------------------|--------|---|-----------|
| 26.14.4.1 | Uplink Access/uplink investigation | R96 | MS supporting VGCS talking | | C108 | | |
| 26.14.4.2 | Uplink Access/uplink access | R96 | MS supporting VGCS talking | | C108 | | |
| 26.14.4.3 | Uplink Reply in VGCS receive mode | R96 | MS supporting VGCS talking | | C108 | | |
| 26.14.5.1 | Leaving group receive mode | R96 | MS supporting VGCS/VBS listening | | C104 | | |
| 26.14.5.2 | Leaving group transmit mode | R96 | MS supporting VGCS talking | | C108 | | |
| 26.14.6.1 | GCC/BCC Procedures/MO call establishment | R96 | MS supporting VGCS/VBS originating | | C107 | TSPC_Serv_eMLPP | |
| 26.14.6.2 | GCC/BCC Procedures/Transaction Identifier | R96 | MS supporting VGCS talking or VBS originating | | C106 | | |
| 26.14.6.3 | GCC/BCC Procedures/Call Termination/originator/group transmit mode | R96 | MS supporting VGCS/VBS originating | | C107 | | |
| 26.14.6.4 | GCC/BCC Procedures/Call Termination/originator/ group receive mode | R96 | MS supporting VGCS originating | | C109 | TSPC_AddInfo_Half_rate_version_1 | |
| 26.14.6.5 | GCC/BCC Procedures/Call Termination/not originator | R96 | MS supporting VGCS listening | | C128 | | |
| 26.14.6.6 | GCC/BCC Procedures/GCC states | R96 | MS supporting VGCS talking | | C108 | TSPC_Addinfo_VGCS_Listening TSPC_Addinfo_VGCS_Originating | |
| 26.14.6.7 | GCC/BCC Procedures/BCC states | R96 | MS supporting VBS originating | | C110 | | |
| 26.14.7.1 | Error Handling/short message length, unknown message type and TI | R96 | MS supporting VGCS or VBS originating | | C107 | TSPC_Addinfo_VGCS_Originating TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking | |
| 26.14.7.2 | Error Handling/incorrect information elements | R96 | MS supporting VGCS or VBS listening | | C104 | TSPC_Addinfo_VGCS_Originating TSPC_Addinfo_VBS_Originating TSPC_Addinfo_VGCS_Talking TSPC_Addinfo_VGCS_Listening TSPC_Addinfo_VBS_Listening | |
| 26.14.7.3 | Error Handling/Message not addressing VGCS receive mode | R96 | MS supporting VGCS or VBS listening | | C104 | | |
| 26.14.8.1 | Structured procedures/very early and early assignments | R96 | MS supporting VGCS or VBS originating | | C107 | TSPC_Serv_eMLPP TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Full_rate_version_2 TSPC_Type_GSM_R_Band | |
| 26.14.9.1 | Cell change/same LA | R96 | MS supporting VGCS or VBS listening | | C104 | | |
| 26.14.9.2 | Cell change/different LA | R96 | MS supporting VGCS or VBS listening | | C104 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|-----------|--|---------------------------|--------|--|-----------|
| 26.14.9.3 | Cell change/different PLMN | R96 | MS supporting VGCS or VBS listening | | C104 | | |
| 26.14.11.1 | VGCS-VBS/User-to-Dispatcher Information/BCC MO call | Release 4 | MS supporting VBS originating and User-To-Dispatcher-Information | | C437 | | |
| 26.14.11.2 | VGCS-VBS/User-to-Dispatcher information/GCC MO call | Release 4 | MS supporting VGCS originating and User-To-Dispatcher-Information | | C438 | | |
| 26.14.11.3 | VGCS-VBS/User-to-Dispatcher information/Compressed user information in VBS fast call set-up | Release 4 | MS supporting VBS originating and Compressed User-To-Dispatcher-Information | | C439 | | |
| 26.14.11.4 | VGCS-VBS/User-to-Dispatcher information/Compressed User-to-Dispatcher information in VGCS fast call set-up | Release 4 | MS supporting VGCS originating and Compressed User-To-Dispatcher-Information | | C440 | | |
| 26.15.2.1 | SoLSA signalling// RR/classmark interrogation | R99 | MS supporting SoLSA | | C207 | TSPC_Feat_OnOff | |
| 26.15.3.1.1 | SoLSA signalling/ MM/location updating | R99 | MS supporting SoLSA | | C207 | | |
| 26.15.3.2 | SoLSA signalling/ MM/MM information | R99 | MS supporting SoLSA | | C207 | | |
| 26.15.4.1 | SoLSA signalling/ CC/call re-establishment/call present | R99 | MS supporting SoLSA | | C207 | | |
| 26.15.5.1 | SoLSA signalling/ structured procedures/MS originated call/early assignment | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 | |
| 26.15.5.2 | SoLSA signalling/ structured procedures/MS originated call/late assignment | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 | |
| 26.15.5.3 | SoLSA signalling/ structured procedures/MS terminated call/early assignment | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_ImmConn | |
| 26.15.5.4 | SoLSA signalling/ structured procedures/MS terminated call/late assignment | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_ImmConn | |
| 26.15.5.5 | SoLSA signalling/ structured procedures/emergency call/idle updated | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 TSPC_R99_Emerg | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|---------------------|---------------------------|--------|--|-----------|
| 26.15.5.6 | SoLSA signalling/ structured procedures/emergency call/idle, no IMSI | R99 | MS supporting SoLSA | | C207 | TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Half_rate_version_3 TSPC_R99_Emerg | |
| 26.16.1 | Void | | | | | | |
| 26.16.2 | Adaptive Multi Rate Signalling/ Inband Signalling, Uplink Codec Adaptation | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.3 | Adaptive Multi Rate Signalling/ Structured procedures/MS terminated call/early assignment/no initial codec mode | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_ImmConn | |
| 26.16.3a | Structured procedures / MS terminated call / early assignment / specified initial codec mode | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_ImmConn | |
| 26.16.4 | Adaptive Multi Rate Signalling/ Structured procedures/MS originated call/late assignment/specified initial codec mode | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.4a | Structured procedures / MS originated call / late assignment / no initial codec mode | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.5 | Adaptive Multi Rate Signalling/ AMR signalling/Handover/active call/successful case | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_Full_rate_version_2 TSPC_AddInfo_Half_rate_version_1 | |
| 26.16.6 | Adaptive Multi Rate Signalling/ Structured procedures/emergency call | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.7 | Adaptive Multi Rate Signalling/ AMR Signalling/Directed Retry/Mobile Originated Call | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.8 | Adaptive Multi Rate Signalling/ AMR Signalling/Directed Retry/Mobile Terminated Call | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_ImmConn | |
| 26.16.9.1 | AMR Configuration Change (normal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.2 | AMR Configuration Change (abnormal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.3 | Codec Mode Phase Change (normal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.4 | Codec Mode Phase Change (abnormal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---------------------------------------|---------------------------|--------|--|-----------|
| 26.16.9.5 | Threshold change (normal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.6 | Threshold change (abnormal) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.7 | Unknown RATSCCH REQ message | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.8 | Ignore subsequent REQ prior to expiry of REQ_Activation counter | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.9 | Initiation of Transaction with ACK_ERR or ACK_UNKNOWN | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.10 | Inversion of the Phase of the CMR/CMI | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.11 | Change of Active Codec Set | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 | |
| 26.16.9.12 | Void | | | | | | |
| 26.16.10.1 | AMR signalling/ test of the channel mode modify procedure/full rate | R98 | MS supporting AMR | | C203 | | |
| 26.16.10.2 | AMR signalling/ test of the channel mode modify procedure/half rate | R98 | MS supporting Half rate AMR (TCH/AHS) | | C319 | | |
| 26.16.11 | Handover/layer 1 failure (AMR signalling) | R98 | MS supporting AMR | | C203 | TSPC_AddInfo_Half_rate_version_3 TSPC_AddInfo_Full_rate_version_2 TSPC_AddInfo_Half_rate_version_1 | |
| 26.17.1 | Void | | | | | | |
| 26.17.2 | Adaptive Multi Rate Signalling – 8PSK/ Inband Signalling, Uplink Codec Adaptation | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.3 | 8-PSK AMR HR / Structured procedures / MS terminated call / early assignment / no initial codec mode | Rel-5 | MS supporting O-TCH/AHS | | C358 | TSPC_AddInfo_ImmConn | |
| 26.17.3a | 8-PSK AMR HR / Structured procedures / MS terminated call / early assignment / specified initial codec mode | Rel-5 | MS supporting O-TCH/AHS | | C358 | TSPC_AddInfo_ImmConn | |
| 26.17.4 | 8-PSK AMR HR / Structured procedures / MS originated call / late assignment / specified initial codec mode | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.4a | 8-PSK AMR HR / Structured procedures / MS originated call / late assignment / no initial codec mode | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.5 | Void | | | | | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|-------------------------|---------------------------|--------|--------------------------|-----------|
| 26.17.6 | 8-PSK AMR HR / Structured procedures / emergency call | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.1 | 8-PSK AMR HR / RATSCCH Protocol / AMR Configuration Change (normal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.2 | 8-PSK AMR HR / RATSCCH Protocol / AMR Configuration Change (abnormal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.3 | 8-PSK AMR HR / RATSCCH Protocol / Codec Mode Phase Change (normal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.4 | 8-PSK AMR HR / RATSCCH Protocol / Codec Mode Phase Change (abnormal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.5 | 8-PSK AMR HR / RATSCCH Protocol / Threshold change (normal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.6 | 8-PSK AMR HR / RATSCCH Protocol / Threshold change (abnormal) | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.7 | 8-PSK AMR HR / RATSCCH Protocol / Unknown RATSCCH REQ message | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.8 | 8-PSK AMR HR / RATSCCH Protocol / Ignore subsequent REQ prior to expiry of REQ_Activation counter | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.9 | 8-PSK AMR HR / RATSCCH Protocol / Initiation of Transaction with ACK_ERR or ACK_UNKNOWN | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.10 | 8-PSK AMR HR / RATSCCH Protocol / Inversion of the Phase of the CMR/CMI | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.9.11 | 8-PSK AMR HR / RATSCCH Protocol / Change of Active Codec Set | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |
| 26.17.10.1 | Void | | | | | | |
| 26.17.10.2 | 8-PSK AMR HR signalling/ test of the channel mode modify procedure | Rel-5 | MS supporting O-TCH/AHS | | C358 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|--|-----------|
| 26.18.1 | Control of dynamic ARFCN mapping with SI14 and SI15 | Rel-4 | MS supporting T-GSM 810 band or GSM 710 band or GSM 750 band or T-GSM 380 or T-GSM 410 or T-GSM 900 | | C381 | | |
| 26.19.3a | WB AMR / Structured procedures / MS terminated call / early assignment / specified initial codec mode | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS TSPC_AddInfo_ImmConn | |
| 26.19.5 | WB AMR / Adaptive Multi Rate Signalling / AMR signalling / Handover / active call / successful case | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS TSPC_AddInfo_Full_rate_version_2 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Full_rate_version_3 TSPC_AddInfo_Half_rate_version_3 | |
| 26.19.9.1 | WB AMR Configuration Change (normal) | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.9.2 | WB AMR Configuration Change (abnormal) | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.9.3 | Codec Mode Phase Change (normal) | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.9.5 | Threshold Change (normal) | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.9.10 | Inversion of the Phase of the CMR/CMI | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.9.11 | Change of Active Codec Set | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.19.10.1 | WB AMR signalling test of the channel mode modify procedure / full rate | Rel-5 | MS supporting TCH/WFS or O-TCH/WFS or O-TCH/WH5 | | C390 | TSPC_O-TCH_WFS TSPC_O-TCH_WHS TSPC_TCH_WFS | |
| 26.20.1 | Enhanced Power Control / MS Supports EPC | Rel-5 | MS supporting GERAN FEATURE PACKAGE 2 | | C426 | | |
| 27.1.1 | MS identification by short IMSI - Normal case | Phase 2 | All ME | | A | | |
| 27.1.2 | MS identification by short IMSI - Phase 1 DCS SIM | Phase 2 | All ME supporting DCS or Simultaneous MultiBand operation | | C129 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|------------------------------------|---------------------------|--------|--------------------------|-----------|
| 27.2 | MS identification by short TMSI | Phase 2 | All ME | | A | | |
| 27.3 | MS identification by long TMSI | Phase 2 | All ME | | A | | |
| 27.4 | MS identification by long IMSI, TMSI updating and cipher key sequence number assignment | Phase 2 | All ME | | A | | |
| 27.5 | Forbidden PLMNs, location updating and undefined cipher key | Phase 2 | All ME | | A | | |
| 27.6 | MS updating forbidden PLMNs | Phase 2 | All ME | | A | | |
| 27.7 | MS deleting forbidden PLMNs | Phase 2 | All ME | | A | | |
| 27.8 | MS updating the PLMN selector list | Phase 2 | All ME | | A | | |
| 27.9 | MS recognizing the priority order of the PLMN selector list | Phase 2 | All ME | | A | | |
| 27.10-1 | MS access control management Case a | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-2 | MS access control management Case b | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-3 | MS access control management Case c | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-4 | MS access control management Case d | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-5 | MS access control management Case e | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-6 | MS access control management Case f | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-7 | MS access control management Case g | Phase 2 | MS supporting speech | | C52 | | |
| 27.10-8 | MS access control management Case h | Phase 2 | MS supporting speech | | C52 | | |
| 27.11.1.1 | Bit/character duration during the transmission from the ME to the SIM | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.1.2 | Bit/character duration during the transmission from the SIM simulator to the ME | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.1.3 | Inter-character delay | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.1.4 | Error handling during the transmission from the ME to the SIM simulator | Phase 2 | ME not supporting Card Application | | C356 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 27.11.1.5 | Error handling during transmission from the SIM simulator to the ME | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.2.2 | Acceptance of SIMs with active low RST | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.2.3 | Characters of the answer to reset | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.2.4 | PTS procedure | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.2.5 | Reset repetition | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.2.6 | Speed Enhancement | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.11.3 | Command processing, procedure bytes | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.12.1 | Operating speed in authentication procedure | Phase 2 | All ME | | A | | |
| 27.12.2 | Clock stop | Phase 2 | All ME | | A | TSPC_AddInfo_5V | |
| 27.13.1 | Contact pressure | Phase 2 | ME not supporting Card Application | | C356 | | |
| 27.13.2 | Shape of contacts for IC card SIM card reader | Phase 2 | All ME | | A | | |
| 27.14.1 | Entry of PIN | Phase 2 | All ME | | A | | |
| 27.14.2 | Change of PIN | Phase 2 | All ME | | A | | |
| 27.14.3 | Disabling the PIN | Phase 2 | ME supporting a feature to disable the PIN | | C15 | | |
| 27.14.4 | PUK entry | Phase 2 | All ME | | C14 | | |
| 27.14.5 | Entry of PIN2 | Phase 2 | ME supporting a feature requiring entry of PIN2 (e.g. AoC or FDN) | | C21 | | |
| 27.14.6 | Change of PIN2 | Phase 2 | ME supporting PIN2 | | C17 | | |
| 27.14.7 | PUK2 entry | Phase 2 | ME supporting PIN2 | | C17 | | |
| 27.15 | Abbreviated Dialling Numbers (ADN) | Phase 2 | ME supporting ADN | | C14 | | |
| 27.16 | MMI reaction to SIM status encoding | Phase 2 | All ME | | C14 | | |
| 27.17.1.1 | Electrical tests - Phase preceding ME power on | Phase 2 | All ME | | A | | |
| 27.17.1.2-1 | Electrical tests - Phase during SIM power on - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.1.2-2 | Electrical tests - Phase during SIM power on - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 27.17.1.2-3.1) | Electrical tests - Phase during SIM power on - 3V/5V SIM interface | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.2-3.2 | Electrical tests - Phase during SIM power on - 3V/5V SIM interface | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.2-4 | Electrical tests - Phase during SIM power on – 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.1.2-5.1 | Electrical tests - Phase during SIM power on – 1,8V/3V SIM interface | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.1.2-5.2 | Electrical tests - Phase during SIM power on – 1,8V/3V SIM interface | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.1.3-1 | Electrical tests - Phase during ME power off with clock stop forbidden - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.1.3-2 | Electrical tests - Phase during ME power off with clock stop forbidden - 3V/5V SIM interface | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.4-1 | Phase during ME power off with clock stop allowed - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.1.4-2 | Phase during ME power off with clock stop allowed - 3V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C81 | | |
| 27.17.1.4-3.1 | Phase during ME power off with clock stop allowed - 3V/5V SIM interface, soft power down | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.4-3.2 | Phase during ME power off with clock stop allowed - 3V/5V SIM interface, 3V/5V switching | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.4-4 | Phase during ME power off with clock stop allowed – 1,8V SIM interface, soft power down | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.1.4-5.1 | Phase during ME power off with clock stop allowed - 1,8V/3V SIM interface, soft power down | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C101 | | |
| 27.17.1.4-5.2 | Phase during ME power off with clock stop allowed - 1,8V/3V SIM interface, soft power down | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C101 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 27.17.1.5.1 | Reaction of 3V only MEs on SIM type recognition failure | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.1.5.2 | Reaction of 3V only MEs on type recognition of 5V only SIMs | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.1.5.3 | Reaction of 3V technology MEs on type recognition of 5V only SIMs | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.5.4 | Reaction of 3V technology MEs on type recognition of 3V technology SIMs | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C82 | | |
| 27.17.1.5.5 | Reaction of 1,8V only MEs on SIM type recognition failure | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.1.5.6 | Reaction of 1,8V only MEs on type recognition of 3V only SIMs | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.1.5.7 | Reaction of 1,8V technology MEs on type recognition of 3V technology SIMs | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C101 | | |
| 27.17.1.5.8 | Reaction of 1,8V technology MEs on type recognition of 1,8V technology SIMs | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.1.1-1 | Electrical tests on contact C1, Test 1 - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.2.1.1-2 | Electrical tests on contact C1, Test 1 - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.2.1.1-3.1 | Electrical tests on contact C1, Test 1 - 3V/5V SIM interface, 5V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.1.1-3.2 | Electrical tests on contact C1, Test 1- 3V/5V SIM interface, 3V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.1.1-4 | Electrical tests on contact C1, Test 1 – 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.2.1.1-5.1 | Electrical tests on contact C1, Test 1 – 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.1.1-5.2 | Electrical tests on contact C1, Test 1 – 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.1.2-1 | Electrical tests on contact C1, Test 2 - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.2.1.2-2 | Electrical tests on contact C1, Test 2 - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 27.17.2.1.2-3.1 | Electrical tests on contact C1, Test 2 - 3V/5V SIM interface, 5V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.1.2-3.2 | Electrical tests on contact C1, Test 2 - 3V/5V SIM interface, 3V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.1.2-4 | Electrical tests on contact C1, Test 2 – 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.2.1.2-5.1 | Electrical tests on contact C1, Test 2 – 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.1.2-5.2 | Electrical tests on contact C1, Test 2 – 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.2-1 | Electrical tests on contact C2 - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.2.2-2 | Electrical tests on contact C2 - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.2.2-3.1 | Electrical tests on contact C2 - 3V/5V SIM interface, 5V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.2-3.2 | Electrical tests on contact C2 - 3V/5V SIM interface, 3V operation mode | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.2-4 | Electrical tests on contact C2 - 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.2.2-5.1 | Electrical tests on contact C2 - 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.2-5.2 | Electrical tests on contact C2 - 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.3-1 | Electrical tests on contact C3 - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.2.3-2 | Electrical tests on contact C3 - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.2.3-3 | Electrical tests on contact C3 - 3V/5V SIM interface | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.3-4 | Electrical tests on contact C3 - 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|---------|---|---------------------------|--------|--|-----------|
| 27.17.2.3-5 | Electrical tests on contact C3 - 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.17.2.5-1 | Electrical tests on contact C7 - 5V SIM interface | Phase 2 | ME with a 5V SIM interface not supporting Card Application | | C80 | | |
| 27.17.2.5-2 | Electrical tests on contact C7 - 3V SIM interface | Phase 2 | ME with a 3V SIM interface not supporting Card Application | | C81 | | |
| 27.17.2.5-3 | Electrical tests on contact C7 - 3V/5V SIM interface | Phase 2 | ME with a 3V/5V SIM interface not supporting Card Application | | C82 | | |
| 27.17.2.5-4 | Electrical tests on contact C7- 1,8V SIM interface | Phase 2 | ME with a 1,8V SIM interface not supporting Card Application | | C91 | | |
| 27.17.2.5-5 | Electrical tests on contact C7 - 1,8V/3V SIM interface, 3V operation mode | Phase 2 | ME with a 1,8V/3V SIM interface not supporting Card Application | | C101 | | |
| 27.18.1.1 | ME and SIM with FND activated, EF _{ADN} invalidated and not readable or updatable | R96 | ME supporting FDN | | C16 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_Half_rate_version_1 TSPC_AddInfo_Full_rate_version_2 TSPC_AddInfo_Full_rate_version_3 TSPC_AddInfo_Half_rate_version_3 | |
| 27.18.1.2. | EF _{ADN} invalidated but readable and updatable | R96 | ME supporting FDN | | C16 | | |
| 27.18.2 | ME and SIM with FND deactivated | Phase 2 | ME supporting FDN | | C16 | | |
| 27.18.3 | Enabling, disabling and updating of FND | Phase 2 | ME supporting FDN | | C16 | | |
| 27.19 | Phase identification | Phase 2 | All ME | | C14 | | |
| 27.20 | SIM presence detection | Phase 2 | All ME | | A | | |
| 27.21.1 | AoC not supported by SIM | Phase 2 | ME supporting AoCC | | C4 | | |
| 27.21.2 | Maximum frequency of ACM updating | Phase 2 | ME supporting AoC (AoCC & AoCI) | | C3 | | |
| 27.21.3 | Call terminated when ACM greater than ACM _{max} | Phase 2 | ME supporting AoCC | | C4 | | |
| 27.21.4 | Response codes of increase command | Phase 2 | ME supporting AoCC | | C4 | | |
| 27.22 | SIM Application Toolkit | R96 | The applicability for SIM Toolkit is found in 11.10-4 clause 3, table B.1 | | | | |
| 28.2 | Constraining the access to a single number (GSM 02.07 category 3) | Phase 2 | MS supporting autocalling | | C7 | TSPC_AddInfo_Impl_CNr27_Cat2 TSPC_AddInfo_Impl_CNr27_Cat3 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|---|---------------------------|--------|--|-----------|
| 28.3 | Constraining the access to a single number (GSM 02.07 categories 1 and 2) | Phase 2 | MS supporting autocalling | | C7 | TSPC_AddInfo_Impl_CNr27_Cat2 TSPC_AddInfo_Impl_CNr27_Cat3 | |
| 28.4 | Behaviour of the MS when its list of blacklisted numbers is full | Phase 2 | MS capable of autocalling more than M B-party numbers | | C8 | TSPC_AddInfo_Impl_CNr27_Cat2 TSPC_AddInfo_Impl_CNr27_Cat3 | |
| 29.2.1 | Verification of synchronization | Phase 2 | MS supporting data services in transparent mode | | C23 | | |
| 29.2.2 | Filtering of channel control information for transparent BCs | Phase 2 | MS supporting the MT2 configuration | | C122 | | |
| 29.2.3.1 | Negotiation of Radio Channel Requirement (RCR) | Phase 2 | MS supporting data services in transparent mode | | C23 | | |
| 29.2.3.2 | Negotiation of Connection Element (CE) | Phase 2 | MS supporting at least one transparent data service and supporting the MT2 configuration | | C25 | | |
| 29.2.3.3 | Negotiation of Number of Stop Bits, Number of Data bits, and Parity | Phase 2 | MS supporting asynchronous data services | | C6 | | |
| 29.2.3.4 | Negotiation of Modem Type | Phase 2 | MS supporting non-transparent data services | | C22 | | |
| 29.2.3.5 | Negotiation of Intermediate Rate | Phase 2 | MS supporting non-transparent services on a TCH/F with a user rate of 4,8 kbit/s or lower | | C10 | | |
| 29.2.3.6 | Negotiation of User Information Layer 2 Protocol | Phase 2 | MS supporting asynchronous bearer services in non-transparent mode | | C5 | | |
| 29.2.3.7 | Negotiation between TS 61 and TS 62: Mobile Originated call. | Phase 2 | MS supporting TS 61 | | C26 | | |
| 29.2.3.8 | Negotiation between TS 61 and TS 62: Mobile Terminated call. | Phase 2 | MS supporting TS 62 and not supporting TS 61 | | C28 | | |
| 29.2.4 | Data Rate Adaptation for Synchronous Transparent Bearer Capabilities | Phase 2 | MS supporting MT2 configuration or any other possibility to send data over Um interface | | C18 | | |
| 29.2.6.1 | Data Rate Adaptation | Phase 2 | MS supporting MT0 or MT2 configuration and supporting data over the Um-interface and supporting asynchronous data Bearer services | | C18 | | |
| 29.2.6.2 | Passage of the Break Signal | Phase 2 | MS supporting MT2 configuration | | C122 | | |
| 29.2.6.3 | Overspeed/Underspeed Handling (Local Terminal) | Phase 2 | MS supporting MT2 configuration | | C122 | | |
| 29.2.6.4 | Overspeed/Underspeed Handling (Remote Terminal) | Phase 2 | MS supporting MT2 configuration | | C122 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 29.2.7 | Interchange circuit mapping for transparent bearer capabilities | Phase 2 | MS supporting MT2 configuration | | C122 | | |
| 29.3.1.1 | Normal initialization done by the MS | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.1.2.1 | Loss of UA frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.1.2.2 | Total loss of UA frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.2.1 | N(S) sequence number | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.2.2 | Transmission window | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.2.3 | Busy condition | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.3.1 | N(R) sequence number | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.3.2 | Busy condition | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.4.1 | REJ frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.4.2 | SREJ frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.4.3 | I+S reject frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.5.1 | Rejection with REJ or SREJ supervisory frames | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.5.2 | Retransmission of REJ or SREJ frames | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.5.3 | I+S reject frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.1 | SS in checkpoint recovery mode | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.2 | End of the window | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.3 | End of a sequence | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.4 | Time-out of one frame | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.5 | No response to checkpointing | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.6 | Incorrect response to checkpointing | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 29.3.2.6.7 | Total loss of response to checkpointing | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.8 | Retransmission of a sequence | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.2.6.9 | N2 retransmission of a sequence | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.3.1 | Negotiation initiated by the SS | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.3.2 | Negotiation initiated by the MS | Phase 2 | MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters | | C120 | | |
| 29.3.3.3 | Collision of XID frames | Phase 2 | MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters | | C120 | | |
| 29.3.3.4 | Loss of XID frames | Phase 2 | MS supporting at least one non-transparent bearer service | | C22 | | |
| 29.3.3.5 | Total loss of XID frames | Phase 2 | MS supporting at least one non-transparent bearer service and supporting the use of non-default RLP parameters | | C120 | | |
| 29.4.2.1.1 | Mobile originated call, Call establishment procedure, Alternate speech/facsimile | Phase 2 | MS supporting TS61 | | C26 | | |
| 29.4.2.1.2 | Mobile originated call, Call establishment procedure, Automatic facsimile | Phase 2 | MS supporting TS62 | | C27 | | |
| 29.4.2.2 | Pre-message procedure | Phase 2 | MS supporting TS 61 and/or TS62 | | C29 | | |
| 29.4.2.3 | Message procedure | Phase 2 | MS supporting TS 61 and/or TS62 | | C29 | | |
| 29.4.2.4 | Post-message procedure | Phase 2 | MS supporting TS 61 and/or TS62 | | C29 | | |
| 29.4.2.5 | Call release procedure | Phase 2 | MS supporting TS 61 and/or TS62 | | C29 | | |
| 29.4.2.6 | CTC processing - 4th PPR for the same block | Phase 2 | MS supporting TS 61 and/or TS62 and supporting the error correction mode | | C30 | | |
| 29.4.2.7 | Transition from Facsimile to Speech - Procedure interrupt generated by receiving station | Phase 2 | MS supporting TS61 | | C26 | | |
| 29.4.2.8 | Transition from Facsimile to Speech - Procedure interrupt generated by transmitting station | Phase 2 | MS supporting TS61 | | C26 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|--|---|---------------------------|--------|--------------------------|-----------|
| 29.4.2.9 | Quality check | Phase 2 | MS supporting transparent facsimile group 3 (TS62) | | C27 | | |
| 29.4.3.1.1.1 | Mobile terminated call, Call Establishment Procedure, Alternate Speech/Facsimile, DCD Mobile Terminated | Phase 2 | MS supporting TS61 | | C26 | | |
| 29.4.3.1.1.2 | Mobile terminated call, Call Establishment Procedure, Alternate Speech/Facsimile, DCD mobile originated | Phase 2 | MS supporting TS61 | | C26 | | |
| 29.4.3.1.2 | Mobile terminated call, Call Establishment Procedure, Automatic facsimile | Phase 2 | MS supporting TS62 | | C27 | | |
| 29.4.3.2 | Pre-message procedure | Phase 2 | MS supporting TS61 and/or TS62 | | C29 | | |
| 29.4.3.3 | Message procedure | Phase 2 | MS supporting TS61 and/or TS62 | | C29 | | |
| 29.4.3.4 | Post-message procedure | Phase 2 | MS supporting TS61 and/or TS62 | | C29 | | |
| 29.4.3.5 | Call release procedure | Phase 2 | MS supporting TS61 and/or TS62 | | C29 | | |
| 29.4.3.6 | Speed conversion factor | Phase 2 | MS supporting TS61 and/or TS62 | | C29 | | |
| 29.4.3.7 | Quality Check | Phase 2 | MS supporting TS61 | | C26 | | |
| 30.1 | Sending sensitivity/frequency response | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.2 | Sending loudness rating | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.3 | Receiving sensitivity/frequency response | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.4 | Receiving loudness rating | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.5.1 | Side Tone Masking Rating (STMR) | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------|----------------------------------|--|---|---------------------------|--------|--------------------------|-----------|
| 30.5.2 | Listener Side Tone Rating (LSTR) | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C280 | | |
| 30.6.1 | Echo Loss (EL) | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.6.2 | Stability margin | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.7.1 | Distortion, Sending | Phase 2 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.7.2 | Distortion, Receiving | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C280 | | |
| 30.8 | Sidetone distortion | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C280 | | |
| 30.9.1 | Out-of-band signals, Sending | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C280 | | |
| 30.9.2 | Out-of-band signals, Receiving | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C280 | | |
| 30.10.1 | Idle channel noise, Sending | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C280 | | |
| 30.10.2 | Idle channel noise, Receiving | Phase 2 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C280 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|--------------------------------------|---|---------------------------|--------|--------------------------|-----------|
| 30.11 | Ambient Noise Rejection | R96 up to and including release 1999 | MS with handset and supporting speech except dual mode GSM/3GPP release 1999 handsets | R1 | C433 | | |
| 30.12 | Sending sensitivity/frequency response | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.13 | Sending loudness rating | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.14 | Receiving sensitivity/frequency response | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.15 | Receiving loudness rating | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.16 | Side Tone Masking Rating (STMR) | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.17.1 | Echo Loss (EL) | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.17.2 | Stability margin | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.18 | Distortion, Sending | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 30.19 | Ambient Noise Rejection | Release 4 | MS with handset and supporting speech except dual mode GSM/3GPP release 4 or later handsets | R1 | C432 | | |
| 31.1.1.1 | CLIP/ Normal operation | Phase 2 | MS supporting the SS CLIP | | C197 | TSPC_AddInfo_MTsvc | |
| 31.1.1.2.1 | CLIP/ Interrogation accepted | Phase 2 | MS supporting the SS CLIP | | C197 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 31.1.1.2.2 | CLIP/ Interrogation rejected | Phase 2 | MS supporting the SS CLIP | | C197 | | |
| 31.1.2.1 | CLIR/ Normal operation - requesting presentation of CLI | Phase 2 | MS supporting the SS CLIR | | C198 | TSPC_AddInfo_MOsvc | |
| 31.1.2.2 | CLIR/ Normal operation - requesting restriction of CLI presentation | Phase 2 | MS supporting the SS CLIR | | C198 | TSPC_AddInfo_MOsvc | |
| 31.1.2.3.1 | CLIR/Interrogation accepted | Phase 2 | MS supporting the SS CLIR | | C198 | | |
| 31.1.2.3.2 | CLIR/Interrogation rejected | Phase 2 | MS supporting the SS CLIR | | C198 | | |
| 31.1.3.1 | COLP/ Interrogation accepted | Phase 2 | MS supporting the SS COLP | | C199 | TSPC_AddInfo_MOsvc | |
| 31.1.3.2.1 | COLP/ Interrogation accepted | Phase 2 | MS supporting the SS COLP | | C199 | | |
| 31.1.3.2.2 | COLP/ Interrogation rejected | Phase 2 | MS supporting the SS COLP | | C199 | | |
| 31.1.4.1.1 | COLR/ Interrogation accepted | Phase 2 | MS supporting the SS COLR | | C200 | | |
| 31.1.4.1.2 | COLR/ Interrogation rejected | Phase 2 | MS supporting the SS COLR | | C200 | | |
| 31.1.4.2 | Void | | | | | | |
| 31.1.5.1.1 | CNAP/Normal Operation – Name indication contained in Setup message | R97 | MS supporting the SS CNAP | | C386 | TSPC_AddInfo_MTsvc | |
| 31.1.5.1.2 | CNAP/Normal Operation – Name indication contained in Facility message | R97 | MS supporting the SS CNAP | | C386 | TSPC_AddInfo_MTsvc | |
| 31.1.5.2.1 | CNAP/Interrogation accepted | R97 | MS supporting the SS CNAP | | C386 | | |
| 31.1.5.2.2 | CNAP/Interrogation rejected | R97 | MS supporting the SS CNAP | | C386 | | |
| 31.2.1.1.1 | Call forwarding supplementary services, Registration accepted | Phase 2 | MS supporting the SSs CFNRy or CFU | | C64 | | |
| 31.2.1.1.2 | Call forwarding supplementary services, Registration rejected | Phase 2 | MS supporting the SSs CFB or CFU or CFNRc or CFNRy | | C65 | | |
| 31.2.1.2.1 | Call forwarding supplementary services, Erasure accepted | Phase 2 | MS supporting the SSs CFB or CFNRc or CFNRy | | C66 | | |
| 31.2.1.2.2 | Call forwarding supplementary services, Erasure rejected | Phase 2 | MS supporting the SSs CFNRy or CFU | | C64 | | |
| 31.2.1.3 | Call forwarding supplementary services, Activation | Phase 2 | MS supporting the SSs CFB or CFU or CFNRc or CFNRy | | C65 | | |
| 31.2.1.4 | Call forwarding supplementary services, Deactivation | Phase 2 | MS supporting the SSs CFB or CFNRc or CFNRy | | C66 | | |
| 31.2.1.6.1 | Call forwarding supplementary services, Interrogation accepted | Phase 2 | MS supporting the SSs CFB or CFNRc or CFNRy | | C66 | | |
| 31.2.1.6.2 | Call forwarding supplementary services, Interrogation rejected | Phase 2 | MS supporting the SSs CFB or CFNRc | | C133 | | |
| 31.2.1.7.1.1 | Call forwarding supplementary services, Notification during an incoming call | Phase 2 | MS supporting CFB | | C67 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 31.2.1.7.1.2 | Call forwarding supplementary services, Notification during an outgoing call | Phase 2 | MS supporting the SSs CFB or CFU or CFNRc or CFNRy | | C65 | | |
| 31.2.1.7.2 | Call forwarding supplementary services, Forwarded-to mobile subscriber side | Phase 2 | MS supporting the SSs CFB or CFU or CFNRc or CFNRy | | C65 | | |
| 31.2.2 | Call transfer and mobile access hunting supplementary services | Phase 2 | Reserved | | | | |
| 31.3.1.1 | Call completion supplementary services, Waiting call indication and confirmation | Phase 2 | MS supporting Call Waiting SS | | C196 | TSPC_AddInfo_MTsvc | |
| 31.3.1.2.1 | Call completion supplementary services, Waiting call accepted; existing call released | Phase 2 | MS supporting Call Waiting SS | | C196 | TSPC_AddInfo_MTsvc | |
| 31.3.1.2.2.1 | Call completion supplementary services; Waiting call accepted; existing call on hold, no additional calls | Phase 2 | MS supporting Speech and Call Waiting SS | | C462 | | |
| 31.3.1.2.3 | Call completion supplementary services, Existing call released by user A; waiting call accepted | Phase 2 | MS supporting Call Waiting SS | | C196 | TSPC_AddInfo_MTsvc | |
| 31.3.1.3.1 | Call completion supplementary services, Waiting call released by subscriber B | Phase 2 | MS supporting Call Waiting SS | | C196 | TSPC_AddInfo_MTsvc | |
| 31.3.1.3.2 | Call completion supplementary services, Waiting call released by calling user C | Phase 2 | MS supporting Call Waiting SS | | C196 | TSPC_AddInfo_MTsvc | |
| 31.3.1.4 | Call completion supplementary services, Activation | Phase 2 | MS supporting Call Waiting SS | | C196 | | |
| 31.3.1.5 | Call completion supplementary services, Deactivation | Phase 2 | MS supporting Call Waiting SS | | C196 | | |
| 31.3.1.6.1 | Call completion supplementary services, Interrogation accepted | Phase 2 | MS supporting Call Waiting SS | | C196 | | |
| 31.3.1.6.2 | Call completion supplementary services, Interrogation rejected | Phase 2 | MS supporting Call Waiting SS | | C196 | | |
| 31.3.2.1 | Call completion supplementary services, Hold invocation | Phase 2 | MS supporting Call Hold SS | | C195 | | |
| 31.3.2.2 | Call completion supplementary services, Retrieve procedure | Phase 2 | MS supporting Call Hold SS | | C195 | | |
| 31.3.2.3 | Call completion supplementary services, Alternate from one call to the other | Phase 2 | MS supporting Call Hold SS | | C195 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|------------------------------|---------------------------|--------|--------------------------|-----------|
| 31.4.1.1 | Multi-party supplementary services, Beginning the MultiParty service, successful case | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.1.2 | Multi-party supplementary services, Beginning the MultiParty service, unsuccessful case | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.1.3 | Multi-party supplementary services, Beginning the MultiParty service, expiry of timer T(BuildMPTY) | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.2.1.1 | Multi-party supplementary services, Put the MultiParty call on hold | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.2.1.2 | Multi-party supplementary services, Create a private communication with one of the remote parties | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.2.1.3 | Multi-party supplementary services, Terminate the entire MultiParty call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.2.1.4 | Multi-party supplementary services, Explicitly disconnect a remote party | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.2.2.1 | Multi-party supplementary services, Release from the MultiParty call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.3.1.1 | Multi-party supplementary services, Retrieve the held MultiParty call, successful case | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.3.1.2 | Multi-party supplementary services, Retrieve the held MultiParty call, unsuccessful case | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.3.1.3 | Multi-party supplementary services, Retrieve the held MultiParty call, expiry of timer T(RetrieveMPTY) | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.3.2 | Multi-party supplementary services, Initiate a new call | Phase 2 | MS supporting Multi Party SS | | C194 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 31.4.3.3 | Multi-party supplementary services, Process a call waiting request | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.3.4 | Multi-party supplementary services, Terminate the held MultiParty call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.1.1 | Multi-party supplementary services, Disconnect the single call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.1.2.3 | Clear all parties of held MultiParty call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.1.2.4 | Clear all parties of active MultiParty call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.2 | Multi-party supplementary services, Disconnect all calls | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.3.1 | Multi-party supplementary services, Add the single call to the MPTY, successful case | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.3.2 | Multi-party supplementary services, Add the single call to the MPTY, maximum number of participants exceeded | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.4.4 | Multi-party supplementary services, Alternate between the MPTY call and the single call | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.4.5 | Multi-party supplementary services, Adding extra remote parties | Phase 2 | MS supporting Multi Party SS | | C194 | | |
| 31.5 | Community of interest supplementary services | Phase 2 | <i>Reserved</i> | | | | |
| 31.6.1.1 | AOC time related charging/MS originated call | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.1.2 | AOC time related charging/MS terminated call | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.1.5 | Change in charging information during a call | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.1.6 | Different formats of charging information | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.1.7 | AOC on a Call Hold call | Phase 2 | MS supporting AoCC and call hold | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.1.8 | AOC on a Multi-party call | Phase 2 | MS supporting AoCC and multiparty service | | C340 | TSPC_AddInfo_TeleSvc | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 31.6.2.1 | Removal of SIM during an active call | Phase 2 | MS supporting AoCC and SIM removal without powering down | | C368 | TSPC_AddInfo_TeleSvc | |
| 31.6.2.2 | Interruption of power supply during an active call | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.2.3 | MS going out of coverage during an active AOCC call | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.2.4 | ACMmax operation/Mobile Originating | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.2.5 | ACMmax operation/Mobile Terminating | Phase 2 | MS supporting AoCC | | C340 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.1 | AoCI time related charging/MS originated call | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.2 | AoCI time related charging/MS terminated call | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.5 | Change in charging information during a call | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.6 | Different formats of charging information | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.7 | AoCI on a Call Hold call | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.6.3.8 | AoCI on a Multi-party call | Phase 2 | MS supporting AoCI | | C341 | TSPC_AddInfo_TeleSvc | |
| 31.7 | Additional information transfer supplementary services | Phase 2 | <i>Reserved</i> | | | | |
| 31.8.1.1 | Registration accepted | Phase 2 | MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC | | C62 | | |
| 31.8.1.2.1 | Rejection after invoke of the RegisterPassword operation | Phase 2 | MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC | | C62 | | |
| 31.8.1.2.2 | Rejection after password check with negative result | Phase 2 | MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC | | C62 | | |
| 31.8.1.2.3 | Rejection after new password mismatch | Phase 2 | MS supporting the SS BOIC or BAIC or BOICextHC or BICRoam or BAOC and not verification for correct repetition of new password | | C370 | | |
| 31.8.3.1 | Activation accepted | Phase 2 | MS supporting the SSs BIC Roam and BAOC | | C68 | | |
| 31.8.3.2.1 | Rejection after invoke of ActivateSS operation | Phase 2 | MS supporting the SS BOIC (Barring of Outgoing International Calls) | | C134 | | |
| 31.8.3.2.2 | Rejection after use of password procedure | Phase 2 | MS supporting the SS BAIC (Barring of All Incoming Calls) | | C135 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|---|-----------|
| 31.8.4.1 | Deactivation accepted | Phase 2 | MS supporting the SS BOIC or BAIC or BOICexHC or BICRoam or BAOC | | C62 | | |
| 31.8.4.2.1 | Rejection after invoke of DeactivateSS operation | Phase 2 | MS supporting the SS BOIC (Barring of Outgoing International Calls) | | C134 | | |
| 31.8.4.2.2 | Rejection after use of password procedure | Phase 2 | MS supporting the SS BOICexHC | | C136 | | |
| 31.8.6.1 | Interrogation accepted | Phase 2 | MS supporting the SS BOICexHC or BAIC | | C137 | TSPC_Serv_SS_BAIC TSPC_Serv_SS_BOICexHC | |
| 31.8.6.2 | Interrogation rejected | Phase 2 | MS supporting the SS BOIC or BICRoam | | C138 | TSPC_Serv_SS_BICRoam TSPC_Serv_SS_BOIC | |
| 31.8.7 | Normal operation | Phase 2 | MS supporting the SS BOIC (Barring of Outgoing International Calls) | | C134 | | |
| 31.9.1.1 | ProcessUnstructuredSS-request/accepted | Phase 2 | MS supporting USSD | | C139 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.9.1.2 | ProcessUnstructuredSS-request/cross phase compatibility and error handling | Phase 2 | MS supporting USSD and supporting CC protocol for at least one Bearer Capability | | C140 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.9.2.1 | UnstructuredSS-Notify/accepted | Phase 2 | MS supporting USSD and supporting CC protocol for at least one Bearer Capability | | C140 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.9.2.2 | UnstructuredSS-Notify/rejected on user busy | Phase 2 | MS supporting USSD and supporting CC protocol for at least one Bearer Capability | | C140 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.9.2.3 | UnstructuredSS-Request/accepted | Phase 2 | MS supporting USSD and supporting CC protocol for at least one Bearer Capability | | C140 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.9.2.4 | UnstructuredSS-Request/rejected on user busy | Phase 2 | MS supporting USSD and supporting CC protocol for at least one Bearer Capability | | C140 | TSPC_AddInfo_Full_rate_version_1 TSPC_AddInfo_TeleSvc | |
| 31.10 | MMI input for USSD | Phase 2 | All MS | | A | | |
| 31.12.1 | eMLPP Service/priority level of MO call | R96 | MS supporting eMLPP and TS11 | | C111 | TSPC_AddInfo_MOsvc TSPC_Serv_TS12 TSPC_AddInfo_VGCS_Originating TSPC_AddInfo_VBS_Originating | |
| 31.12.2 | eMLPP Service/automatic answering point-to-point MT call | R96 | MS supporting eMLPP, HOLD, CW and TS11 | | C112 | TSPC_AddInfo_VGCS_Listening TSPC_AddInfo_VBS_Listening | |
| 31.12.3 | eMLPP Service/automatic answering MT VGCS or VBS call | R96 | MS supporting eMLPP and supporting VGCS or VBS listening | | C113 | | |
| 31.12.4 | eMLPP Service/registration | R96 | MS supporting eMLPP | | C114 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|---|---------------------------|--------|--|-----------|
| 31.12.5 | eMLPP Service/interrogation | R96 | MS supporting eMLPP | | C114 | | |
| 31.13.1.1 | Explicit Call Transfer invocation, successful case, both calls active, clearing using DISCONNECT | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.13.1.2 | Explicit Call Transfer invocation, successful case, both calls active, clearing using RELEASE | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.13.1.3 | Explicit Call Transfer invocation, successful case, both calls active, clearing using RELEASE COMPLETE | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.13.1.4 | Explicit Call Transfer invocation, successful case, second call alerting | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.13.1.5 | Explicit Call Transfer invocation, unsuccessful case | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.13.1.6 | Explicit Call Transfer invocation, expiry of T(ECT) | R96 | MS supporting Explicit Call Transfer SS | | C193 | | |
| 31.14.1.1 | UUS/Implicit UUS1/CC MO call | R99 | MS supporting Implicit User-to-User Signalling SS | | C192 | TSPC_AddInfo_MOsvc TSPC_Serv_SS_UUS | |
| 31.14.1.2 | UUS/Implicit UUS1/CC MT call | R99 | MS supporting Implicit User-to-User Signalling SS | | C192 | TSPC_AddInfo_MTsvc TSPC_Serv_SS_UUS | |
| 31.14.1.3 | UUS/Implicit UUS1/Interactions with Call Waiting and call HOLD supplementary services | R99 | MS supporting Implicit User-to-User Signalling SS | | C192 | TSPC_AddInfo_MOsvc TSPC_AddInfo_MTsvc TSPC_Serv_SS_UUS TSPC_Serv_SS_HOLD | |
| 31.15.1 | Follow Me (FM)/Registration | R99 | MS supporting Follow Me SS | | C191 | | |
| 31.15.2 | Follow Me (FM)/Interrogation | R99 | MS supporting Follow Me SS | | C191 | | |
| 31.15.3 | Follow Me (FM)/Erasure | R99 | MS supporting Follow Me SS | | C191 | | |
| 32.1 | Full Rate Downlink speech transcoding | Phase 2 | MS supporting speech | | C24 | | |
| 32.2 | Full Rate Downlink receiver DTX functions | Phase 2 | MS supporting speech | | C24 | | |
| 32.3 | Full Rate Uplink speech transcoding | Phase 2 | MS supporting speech | | C24 | | |
| 32.4 | Full Rate Uplink transmitter DTX functions | Phase 2 | MS supporting speech | | C24 | | |
| 32.5.4 | Full Rate Speech channel transmission delay - Downlink processing delay | Phase 2 | MS supporting speech | | C24 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 32.5.5 | Full Rate Speech channel transmission delay -Downlink coding delay | Phase 2 | MS supporting speech | | C24 | | |
| 32.5.6 | Full Rate Speech channel transmission delay -Uplink processing delay | Phase 2 | MS supporting speech | | C24 | | |
| 32.5.7 | Full Rate Speech channel transmission delay -Uplink coding delay | Phase 2 | MS supporting speech | | C24 | | |
| 32.6 | Half Rate Downlink speech transcoding | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.7 | Half Rate Downlink receiver DTX functions | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.8 | Half Rate Uplink speech transcoding | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.9 | Half Rate Uplink transmitter DTX functions | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.10.4 | Half Rate Speech channel transmission delay - Downlink processing delay | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.10.5 | Half Rate Speech channel transmission delay - Downlink coding delay | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.10.6 | Half Rate Speech channel transmission delay - Uplink processing delay | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.10.7 | Half Rate Speech channel transmission delay - Uplink coding delay | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.11 | Intra cell channel change from a TCH/HS to a TCH/FS | Phase 2 | MS supporting half rate speech | | C13 | | |
| 32.12 | Intra cell channel change from a TCH/FS to a TCH/HS | Phase 2 | MS supporting half rate speech | | C13 | | |
| 33.1 | Entry and display of called number | Phase 2 | MS supporting display of called number | | C190 | | |
| 33.2.4 | Ringling tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |
| 33.2.5 | Busy tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |
| 33.2.6 | Congestion tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------------------------------|---|---------------------------|--------|---|-----------|
| 33.2.7 | Authentication failure tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |
| 33.2.8 | Number unobtainable tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |
| 33.2.9 | Call dropped tone | Phase 2 | MS supporting audible indication of service tones | | C206 | | |
| 33.3-1 | Network selection/indication | Phase 2 | All MS | | A | TSPC_Feat_PLMNind | |
| 33.3-2 | Network selection/indication | Phase 2 | All MS | | A | TSPC_Feat_PLMNind | |
| 33.4 | Invalid and blocked PIN indicators | Phase 2 | All MS | | A | | |
| 33.5 | Service indicator | Phase 2 | MS supporting Service indicator | | C201 | | |
| 33.6 | Subscription identity management | Phase 2 | MS supporting Subscription identity management | | C202 | | |
| 33.7 | Barring of outgoing calls | Phase 2 | MS supporting barring of outgoing calls | | C9 | | |
| 33.8 | Prevention of unauthorized calls | Phase 2 | MS supporting barring of outgoing calls | | C9 | | |
| 34.2.1 | SMS mobile terminated | Phase 2 | MS supporting SMS MT/PP and supporting CC protocol for at least one Bearer Capability | | C72 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.2 | SMS mobile originated | Phase 2 | MS supporting SMS MO/PP and supporting CC protocol for at least one Bearer Capability | | C73 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.3 | Test of memory full condition and memory available notification: | Phase 2 | MS supporting SMS MT/PP and storing of short messages in the SIM | | C397 | TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.4 | Test of the status report capabilities and of SMS-COMMAND: | Phase 2 | MS supporting SMS MT/PP and SMS MO/PP and supporting SMS status report capabilities | | C141 | | |
| 34.2.5.1 | Short message class 0 | Phase 2 | MS supporting SMS MT/PP and display of received short messages | | C142 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.5.2 | Test of class 1 short messages | Phase 2 | MS supporting storing of received Class I Short Messages and display of stored Short Messages | | C143 | TSPC_Serv_TS21 TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.5.3 | Test of class 2 short messages | Phase 2 | MS supporting storing of received Class II Short Messages in the SIM | | C74 | TSPC_Serv_TS21 TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.6 | Test of short message type 0 (Ph2, R96...R99 and REL-4) | Phase 2, R96...R99 & REL-4 only | MS supporting SMS MT/PP | | C290 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|---|---------------------------|--------|---|-----------|
| 34.2.6a | Test of short message type 0 (\geq REL 5) | REL-5 | MS supporting SMS MT/PP | | C290 | | |
| 34.2.7 | Test of the replace mechanism for SM type 1-7 | Phase 2 | MS supporting SMS MT/PP and Replace Short Messages and display of received Short Messages | | C144 | | |
| 34.2.8 | Test of the reply path scheme | Phase 2 | MS supporting SMS MT/PP and SMS MO/PP and reply procedures and display of received Short Messages | | C145 | | |
| 34.2.9.1 | Multiple SMS mobile originated/MS in idle mode | Phase 2 | MS supporting the ability of sending multiple short messages on the same RR connection | | C272 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.2.9.2 | Multiple SMS mobile originated/MS in active mode | Phase 2 | MS supporting the ability of sending multiple short messages on the same RR connection and CC protocol for at least one Bearer Capability | | C458 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.3 | Short message service cell broadcast | Phase 2 | All MS supporting SMS CB | | C300 | | |
| 34.4.1 | SMS mobile terminated | R97 | MS supporting MT SMS over GPRS | | C251 | TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.4.2 | SMS mobile originated | R97 | All GPRS MS | | C215 | TSPC_SMS_over_GPRS TSPC_AddInfo_StoreRcvSMSSIM TSPC_AddInfo_StoreRcvSMSME | |
| 34.4.3 | Test of the status report capabilities and of SMS-COMMAND over GPRS: | R97 | MS supporting MT SMS over GPRS and supporting SMS status report capabilities | | C252 | | |
| 34.4.4 | Test of capabilities of simultaneously receiving a short message whilst sending a mobile originated short message | R97 | MS supporting MT SMS over GPRS | | C251 | | |
| 34.4.5 | Void | | | | | | |
| 34.4.6 | Concatenated MO SMS over GPRS | R97 | MS Supporting GPRS and SMS over GPRS and MO SMS Concatenation | | C254 | | |
| 34.4.7 | Concatenated MT SMS over GPRS | R97 | MS Supporting GPRS and SMS over GPRS and MT SMS Concatenation | | C255 | | |
| 34.4.8.1 | CP Error Handling | R97 | MS Supporting GPRS and SMS over GPRS | | C253 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--------------------------------------|---------------------------|--------|---|-----------|
| 34.4.8.2 | RP Error Handling | R97 | MS Supporting GPRS and SMS over GPRS | | C253 | | |
| 35 | Low battery voltage detection | Phase 2 | All MS | | A | | |
| 36 | Individual equipment type requirements and interworking - special conformance testing functions | Phase 2 | <i>Reserved</i> | | | | |
| 37 | Void | | | | | | |
| 38 | Void | | | | | | |
| 39 | Void | | | | | | |
| 41.1.1.1 | RR/Paging/on PCCCH for GPRS service/normal paging with P-TMSI successful. | R97 | All GPRS MS | | C215 | | |
| 41.1.1.2 | RR/Paging/on PCCCH for GPRS service/normal paging with IMSI successful | R97 | All GPRS MS | R6 | C215 | | |
| 41.1.1.3 | RR/Paging/on PCCCH for GPRS service/extended paging with P-TMSI successful | R97 | All GPRS MS | R6 | C215 | | |
| 41.1.1.4 | RR/Paging/on PCCCH for GPRS service/paging reorganisation successful | R97 | All GPRS MS | | C215 | | |
| 41.1.2 | RR/Paging/on PCCCH for circuit-switched services/paging successful | R97 | MS supporting GPRS mode A or B | | C226 | TSPC_MS_GPRS_RELEASE | |
| 41.1.3 | RR/Paging/on PCCCH/paging ignored | R97 | All GPRS MS | | C215 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C | |
| 41.1.4.1 | RR/Paging/on PACCH for circuit-switched services/ paging successful | R97 | MS supporting GPRS mode B | | C221 | | |
| 41.1.4.2 | RR/Paging/on PACCH for circuit-switched services/ paging ignored | R97 | MS supporting GPRS mode A or B | | C226 | | |
| 41.1.5.1.1 | RR/Paging/on CCCH for GPRS service/normal paging with P-TMSI successful | R97 | All GPRS MS | | C215 | | |
| 41.1.5.1.2 | RR/Paging/on CCCH for GPRS service/normal paging with IMSI successful | R97 | All GPRS MS | | C215 | | |
| 41.1.5.1.3 | RR/Paging/on CCCH for GPRS service/normal paging with P-TMSI ignored | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---------------|---------------------------|--------|---|-----------|
| 41.1.5.2.1 | RR/Paging/on CCCH for GPRS service/extended paging with P-TMSI successful | R97 | All GPRS MS | | C215 | | |
| 41.1.5.3 | RR/Paging/on CCCH for GPRS service/paging reorganisation | R97 | All GPRS MS | | C215 | | |
| 41.1.5.4 | Void | | | | | | |
| 41.1.6 | RR/Paging/Before T3172 expiry | R97 | All GPRS MS | R6 | C215 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C | |
| 41.2.1.1 | Permission to access the network/priority classes | R97 | All GPRS MS | | C215 | | |
| 41.2.2.1 | Initiation of the packet access procedure/establishment causes | R97 | All GPRS MS | | C215 | | |
| 41.2.2.2 | Random references for single block packet access | R97 | All GPRS MS | | C215 | | |
| 41.2.2.3 | Random references for one phase packet access | R97 | All GPRS MS | | C215 | | |
| 41.2.2.4 | Initiation of the packet access procedure/timer T3146 | R97 | All GPRS MS | | C215 | | |
| 41.2.2.5 | Initiation of the packet access procedure/Request Reference | R97 | All GPRS MS | | C215 | | |
| 41.2.3.1 | Two-message assignment/Successful case | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.2 | Two-message assignment/Failure cases | R97 | All GPRS MS | | C215 | | |
| 41.2.3.3 | Packet uplink assignment/Polling bit set | R97 | All GPRS MS | R6 R6 | C215 | TSPC_operation_mode_B TSPC_AddInfo_on_auto_GPRS_AP | |
| 41.2.3.4 | One phase packet access/Contention resolution/Successful case | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.5 | One phase packet access/Contention resolution/TLLI mismatch | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.6 | One phase packet access/Contention resolution/Counter N3104 | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.7 | One phase packet access/Contention resolution/Timer T3166 | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.8 | One phase packet access/Contention resolution/4 access repetition attempts | R97 | All GPRS MS | R6 | C215 | TSPC_MS_GPRS_RELEASE | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|---------------|---------------------------|--------|---|-----------|
| 41.2.3.9 | One phase packet access/TBF starting time | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.10 | One phase packet access/Timing Advance Index present | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.3.11 | One phase packet access/Timing Advance Index not present | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.4.1 | Single block packet access/Packet Resource Request | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.4.2 | Single block packet access/Packet Measurement Report | R97 | All GPRS MS | | C215 | | |
| 41.2.5.1 | Packet access rejection/wait indication | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.5.2 | Packet access rejection/assignment before T3142 expires | R97 | All GPRS MS | | C215 | | |
| 41.2.6.1 | Initiation of packet downlink assignment procedure/MS listens to correct CCCH block | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.6.2 | Initiation of packet downlink assignment procedure/timer T3190 | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.6.3 | Initiation of packet downlink assignment procedure/TBF starting time | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.6.4 | Initiation of packet downlink assignment procedure/incorrect TFI | R97 | All GPRS MS | R6 | C215 | | |
| 41.2.7.1 | Single block packet downlink assignment/TBF Starting Time | R97 | All GPRS MS | | C215 | | |
| 41.2.7.2 | Single block packet downlink assignment/MS returns to packet idle mode | R97 | All GPRS MS | | C215 | | |
| 41.3.1.1 | TBF Release/Uplink/Normal/MS initiated/Acknowledged mode | R97 | All GPRS MS | | C215 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 41.3.1.2 | TBF Release/Uplink/Normal/MS initiated/Unacknowledged mode | R97 | All GPRS MS | | C215 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 41.3.1.3 | TBF Release/Uplink/Normal/MS initiated/Channel coding change during countdown | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|---|-----------|
| 41.3.1.4-1 | TBF release / Uplink / Normal / MS initiated / Whilst in DTM, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.3.1.4-2 | TBF release / Uplink / Normal / MS initiated / Whilst in DTM, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.3.2.1 | TBF Release/Uplink/Normal/Network initiated/Acknowledged mode | R97 | All GPRS MS | | C215 | | |
| 41.3.2.2 | TBF Release/Uplink/Normal/Network initiated/Unacknowledged mode | R97 | All GPRS MS | | C215 | | |
| 41.3.2.3-1 | TBF release / Uplink / Normal / Network initiated / Whilst in DTM, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.3.2.3-2 | TBF release / Uplink / Normal / Network initiated / Whilst in DTM, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.3.3 | TBF Release/Uplink/Network initiated/Abnormal release | R97 | All GPRS MS | | C215 | | |
| 41.3.4.1 | TBF Release/Downlink/Normal/Network initiated/Acknowledged mode | R97 | All GPRS MS | | C215 | | |
| 41.3.4.2 | TBF Release/Downlink/Normal/Network initiated/Unacknowledged mode | R97 | All GPRS MS | | C215 | | |
| 41.3.4.3-1 | TBF release / Downlink / Normal / Network initiated / Whilst in DTM, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.3.4.3-2 | TBF release / Downlink / Normal / Network initiated / Whilst in DTM, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.3.5.2 | PDCH Release/With TIMESLOTS_AVAILABLE | R97 | All GPRS MS | | C215 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 41.3.6.1 | TBF Release / Extended Uplink / Recalculation of CV before CV = 0 | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.2 | TBF Release / Extended Uplink / Recalculation of CV after CV = 0 | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.3 | TBF Release / Extended Uplink / CS change order while CV=0 | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 41.3.6.4 | TBF Release / Extended Uplink / TBF reconfigure by PACKET TIMESLOT RECONFIGURE | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.5 | TBF Release / Extended Uplink / TBF reconfigure by PACKET UPLINK ASSIGNMENT | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.6 | Extended Uplink TBF / Cell Change while in Extended Uplink/ No Packet Neighbouring Cell Data | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.7 | Extended Uplink TBF / Cell Change failure while in Extended Uplink/ No Packet Neighbouring Cell Data | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | R6 | C322 | | |
| 41.3.6.8 | Extended Uplink TBF / Cell Change while in Extended Uplink/ With Packet Neighbouring Cell Data | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 41.3.6.9 | TBF Release / Extended Uplink / Change of RLC mode / normal release | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 and supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C337 | | |
| 41.3.6.10 | TBF Release / Extended Uplink / Change of RLC mode / abnormal release | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 and supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | R6 | C337 | | |
| 41.5.1.1.1.1-1 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Uplink resources assigned, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.1.1-2 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Uplink resources assigned, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 41.5.1.1.1.2-1 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Downlink resources assigned, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.1.2-2 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Downlink resources assigned, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.1.3-1 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / DTM reject, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.1.3-2 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / DTM reject, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.1.4 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Inter System to UTRAN Handover Command | R99 | MS supporting both UTRAN and DTM/GPRS | | C315 | | |
| 41.5.1.1.1.5-1 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Assignment Command, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.1.5-2 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Assignment Command, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.1.6-1 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Handover Command, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.1.6-2 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Handover Command, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.1.7 | Uplink TBF establishment with no reallocation of CS resources / Abnormal cases / Channel Release | R99 | All DTM/GPRS capable MS | | C305 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|--|---------------------------|--------|--|-----------|
| 41.5.1.1.2.1-1 | Uplink TBF establishment with reallocation of CS resources / Successful case, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.2.1-2 | Uplink TBF establishment with reallocation of CS resources / Successful case, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.2.2-1 | Uplink TBF establishment with reallocation of CS resources / Abnormal case / Assignment Failure, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.1.2.2-2 | Uplink TBF establishment with reallocation of CS resources / Abnormal case / Assignment Failure, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.1.2.3-4 | Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Singleslot allocation | R99 | All DTM/GPRS capable MS not supporting singleslot allocation in DTM/GPRS | | C353 | | |
| 41.5.1.1.2.3-5 | Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Incorrect allocation | R99 | MS supporting DTM/GPRS supporting DTM multislot Class 5 or 9 or 11 | | C308 | | |
| 41.5.1.1.3 | Uplink TBF establishment required whilst in DM / DTM not supported in cell | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.2.1.1-1 | Downlink TBF establishment in Ready State / Successful case | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.2.1.1-2 | Downlink TBF establishment in Ready State / Successful case | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.1.2.1.2 | Downlink TBF establishment in Ready State / Abnormal cases / No cell allocation available | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.1.2.2 | Whilst in Standby State / Packet Notification | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.2.1-1 | MT CS establishment whilst in packet transfer mode with a downlink TBF established, test 1 | R99 | All DTM/GPRS capable MS | | C305 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 41.5.2.1-2 | MT CS establishment whilst in packet transfer mode with a downlink TBF established, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 41.5.2.2-1 | MT CS establishment whilst in packet transfer mode with a uplink TBF established, test 1 | R99 | All DTM/GPRS capable MS | | C305 | TSPC_AddInfo_ImmConn | |
| 41.5.2.2-2 | MT CS establishment whilst in packet transfer mode with a uplink TBF established, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | TSPC_AddInfo_ImmConn | |
| 41.5.2.3-1 | MO CS establishment whilst in packet transfer mode with uplink and downlink TBFs established, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.2.3-2 | MO CS establishment whilst in packet transfer mode with uplink and downlink TBFs established, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.2.4 | MO CS establishment whilst in packet transfer mode and DTM is not supported in current cell | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.3.1.1-1 | Uplink TBF establishment with a downlink TBF established and no PS downlink reallocation, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.3.1.1-2 | Uplink TBF establishment with a downlink TBF established and no PS downlink reallocation, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.3.1.2 | Uplink TBF establishment with a downlink TBF established and PS downlink reallocation | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.3.2.1-1 | Downlink TBF establishment with a uplink TBF established and no PS uplink reallocation, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.3.2.1-2 | Downlink TBF establishment with a uplink TBF established and no PS uplink reallocation, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 41.5.3.2.2 | Downlink TBF establishment with a uplink TBF established and PS uplink reallocation | R99 | All DTM/GPRS capable MS | | C305 | | |
| 41.5.4.1 | MT Call Establishment - No Reallocation of PS Resources | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | TSPC_AddInfo_ImmConn | |
| 41.5.4.2 | Reallocation of PS Resources - Allocation of New Downlink TBF | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | TSPC_AddInfo_ImmConn | |
| 41.5.4.3 | MT Call Establishment - Allocation of CS Resources Only - Downlink TBF | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | TSPC_AddInfo_ImmConn | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|---|-----------|
| 41.5.4.4 | MO Call Establishment - No Reallocation of PS Resources | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.4.5 | MO Call Establishment - Reallocation of PS Resources | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.4.6 | MO Call Establishment - Allocation of CS Resources Only - Downlink TBF | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.4.7 | MO Call Establishment - IMMEDIATE ASSIGNMENT REJECT | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.4.8 | MO Call Establishment – Dedicated Channel Establishment Failure | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.5.1 | SI Acquisition - No Reallocation of PS Resources | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.5.2 | Reallocation of PS Resources for Uplink and Downlink TBFs | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.5.3 | Change of LA in NW Mode II | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.5.5.4 | MS Requests PS Release Following Change of LA in NW Mode I | Rel-6 | All DTM/GPRS capable MS supporting Enhanced DTM CS | | C441 | | |
| 41.6.1.1 | Intra SGSN PS Handover / Synchronized cell case / successful | Rel-6 | All GPRS MS supporting PS Handover | | C463 | | |
| 41.6.2.1 | Intra SGSN PS Handover / Pre-synchronized cell case / successful / RLC reset | Rel-6 | All GPRS MS supporting PS Handover | | C463 | | |
| 42.1.1.1 | Packet Channel Request/Message format | R97 | All GPRS MS | | C215 | | |
| 42.1.1.2 | Packet Channel Request/Response to Packet Paging | R97 | All GPRS MS | | C215 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C | |
| 42.1.1.4.1 | Packet Channel Request/Access persistence control on PRACH/M+1 attempts | R97 | All GPRS MS | | C215 | | |
| 42.1.1.4.2 | Packet Channel Request/Access persistence control on PRACH/Persistence level | R97 | All GPRS MS | | C215 | | |
| 42.1.1.4.3 | Packet Channel Request/Access persistence control on PRACH/Successive Attempts | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|---------------|---------------------------|--------|--------------------------|-----------|
| 42.1.2.1.1.1 | Packet Uplink Assignment/Packet queuing notification/Stop sending Packet Channel Requests | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.1.2 | Packet Uplink Assignment/Packet queuing notification/Ignoring Packet Queuing Notification | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.1.3 | Packet Uplink Assignment/Packet queuing notification/Assigned PDCHs | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.1.4 | Packet Uplink Assignment/Packet queuing notification/Expiry of timer T3162 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.2 | Packet Uplink Assignment/Response to packet polling request | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.3.1 | Packet Uplink Assignment/Packet access reject/Action during Wait_Indication | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.3.2 | Packet Uplink Assignment/Packet access reject/No respond | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.3.3 | Void | | | | | | |
| 42.1.2.1.4 | Packet Uplink Assignment/Packet Uplink Assignment handling | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.5 | Packet Uplink Assignment/One or two phase access | R97 | All GPRS MS | | C215 | TSPC_Feat_OnOff | |
| 42.1.2.1.6 | Packet Uplink Assignment/Decoding of frequency parameters | R97 | All GPRS MS | | C215 | TSPC_Feat_OnOff | |
| 42.1.2.1.7 | Packet Uplink Assignment/Most recently received Packet Uplink Assignment | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.1.1 | Packet Uplink Assignment/One phase access/Contention resolution/Inclusion of TLLI in RLC data blocks | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.1.2 | Packet Uplink Assignment/One phase access/Contention resolution/Counter N3104 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.1.3 | Packet Uplink Assignment/One phase access/Contention resolution/Timer T3166 | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|---|---------------------------|--------|---|-----------|
| 42.1.2.1.8.1.4 | Packet Uplink Assignment/One phase access/Contention resolution/TLLI mismatch | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.1.5 | Packet Uplink Assignment/One phase access/Contention resolution/3 or 4 access repetition attempts | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.1.6 | Packet Uplink Assignment / One phase access / Contention resolution / Retransmission / Inclusion of TLLI in RLC data blocks after completion | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.2.1 | Packet Uplink Assignment/One phase access/Timing Advance/TA Index present | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.8.2.2 | Packet Uplink Assignment/One phase access/Timing Advance/TA Index not present | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.9.1 | Packet Uplink Assignment/Two phase access/Packet Resource Request/RLC Octet Count | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.9.2.1 | Packet Uplink Assignment/Two phase access/Contention resolution/Expiry of timer T3168 | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 42.1.2.1.9.2.2 | Packet Uplink Assignment/Two phase access/Contention resolution/TLLI mismatch | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 42.1.2.1.9.3 | Packet Uplink Assignment/Two phase access/Packet Resource Request/No respond to Packet Downlink Assignment | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.10.1 | Packet Uplink Assignment/Abnormal cases/Incorrect PDCH assignment | R97 | All GPRS MS not operating in GPRS multislots classes 18 or 29 | | C417 | TSPC_MS_GPRS_RELEASE TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.1.2.1.10.2 | Packet Uplink Assignment/Abnormal cases/Expiry of timer T3164 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.11 | Non DRX mode on PCCCH | R97 | All GPRS MS supporting non-zero value of non-DRX timer. | | C19 | | |
| 42.1.2.1.12 | Variable PBCCH and PSI scheduling | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|------------------|--|---------------------------|--------|---|-----------|
| 42.1.2.1.13 | Several PCCCHs supported by the cell | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.14 | Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 0 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.15 | Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 3 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.16 | Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 7 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.17 | Several Non-hopping PCCCHs supported by the cell, PBCCH on timeslot 4 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.18 | Several Hopping PCCCHs and non-Hopping PCCCHs supported by the cell | R97 | All GPRS MS | | C215 | | |
| 42.1.2.1.19 | Packet Uplink/downlink Assignment using Variable Bitmap format / PBCCH Cell | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.1 | Packet Downlink Assignment/Response to poll bit | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.2 | Packet Downlink Assignment/PCCCH monitoring | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.3 | Packet Downlink Assignment/Frequency hopping | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.4 | Packet Downlink Assignment/Response to Packet Polling | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.5.1 | Packet Downlink Assignment/Abnormal cases/Incorrect PDCH assignment | R97 | All GPRS MS not operating in GPRS multislots classes 18 and 24 to 29 | | C418 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.1.2.2.5.2 | Packet Downlink Assignment/Abnormal cases/Expiry of timer T3190 | R97 | All GPRS MS | | C215 | | |
| 42.1.2.2.6 | Packet Downlink Assignment Timing Advance/TA value field not provided | R97 | All GPRS MS | | C215 | | |
| 42.2.2.1.1 | Fixed Allocation/Uplink Transfer/Normal operation/Blocks | R97 and R98 only | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|------------------|--|---------------------------|--------|--------------------------|-----------|
| 42.2.2.1.2-1 | Fixed Allocation/Uplink Transfer/Normal operation/Block Periods | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.1.2-2 | Fixed Allocation/Uplink Transfer/Normal operation/Block Periods | R97 and R98 only | GPRS MS not operating in GPRS multislot classes 1,2,4 or 8 | | C227 | | |
| 42.2.2.2 | Fixed Allocation/Uplink Transfer/Operation with TS_OVERRIDE for single-slot TX | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.3 | Fixed Allocation/Uplink Transfer/Operation with TS_OVERRIDE for multi-slot TX | R97 and R98 only | GPRS MS not operating in GPRS multislot classes 1,2,4 or 8 | | C227 | | |
| 42.2.2.4 | Fixed Allocation/Uplink Transfer/T3184 Expiry | R97 and R98 only | All GPRS MS | | C282 | | |
| 42.2.2.5.1 | Fixed Allocation/Uplink Transfer/T3188/Expiry | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.5.2 | Fixed Allocation/Uplink Transfer/T3188/Stop with Packet Uplink Assignment | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.5.3 | Fixed Allocation/Uplink Transfer/T3188/Stop with Packet Uplink Ack/Nack with REPEAT_ALLOCATION | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.6.1 | Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Expiry | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.6.2 | Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Uplink Assignment | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.6.3 | Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Uplink Ack/Nack with REPEAT_ALLOCATION | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.6.4 | Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Stop with Packet Access Reject | R97 and R98 only | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|------------------|---------------|---------------------------|--------|--------------------------|-----------|
| 42.2.2.6.5 | Fixed Allocation/Uplink Transfer/MS requests new resources/ T3168/Continue with Packet Uplink Ack/Nack without REPEAT_ALLOCATION and without ALLOCATION_BITMAP | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.7.1 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Packet Uplink Assignment with ALLOCATION_BITMAP | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.7.2 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Multiple Packet Uplink Assignments | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.7.3 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Packet Uplink Ack/Nack with ALLOCATION_BITMAP | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.7.4 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Multiple Packet Uplink Ack/Nack with ALLOCATION_BITMAP | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.7.5 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Successful/ Multiple Packet Uplink Ack/Nack with REPEAT_ALLOCATION | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.8.1 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Failure/ Packet Access Reject | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.8.2 | Fixed Allocation/Uplink Transfer/MS requests new resources/ Failure/ Packet Access Reject with WAIT_INDICATION during allocation in progress | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.9 | Fixed Allocation/Uplink Transfer/Network initiates new resources | R97 and R98 only | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|------------------|--|---------------------------|--------|--------------------------|-----------|
| 42.2.2.10.1 | Fixed Allocation/Uplink Transfer/PACCH operation/ Normal Operation | R97 and R98 only | GPRS MS supporting GPRS multislot class 3 and above | | C228 | | |
| 42.2.2.10.2 | Fixed Allocation/Uplink Transfer/PACCH operation/ PACCH message addressed to another MS | R97 and R98 only | GPRS MS supporting GPRS multislot class 3 and above | | C228 | | |
| 42.2.2.10.3 | Fixed Allocation/ Uplink Transfer/Abnormal cases/PACCH timeslot removed | R97 and R98 only | GPRS MS supporting GPRS multislot class 3 and above | | C228 | | |
| 42.2.2.11.1 | Fixed Allocation/ Uplink Transfer/Abnormal cases/Assignment without fixed allocation | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.11.2 | Fixed Allocation/ Uplink Transfer/Abnormal cases/Frequency not supported | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.2.11.3 | Fixed Allocation/ Uplink Transfer/Abnormal cases/Invalid MA_NUMBER | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.3.1.1 | Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ T3190/Half-Duplex | R97 and R98 only | GPRS MS supporting GPRS multislot class 19 and 24. | | C229 | | |
| 42.2.3.1.2 | Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ T3190/Non Half-Duplex | R97 and R98 only | GPRS MS supporting GPRS multislot class 10 and above | | C230 | | |
| 42.2.3.2.1 | Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ Ending uplink TBF/ Half-Duplex | R97 and R98 only | GPRS MS supporting GPRS multislot class 19 and 24 | | C229 | | |
| 42.2.3.2.2 | Fixed Allocation/Uplink Transfer with Downlink TBF Establishment/ Ending uplink TBF/ Non Half-Duplex | R97 and R98 only | GPRS MS supporting GPRS multislot class 10 and above | | C230 | | |
| 42.2.3.3.1 | Fixed Allocation/ Uplink Transfer with Downlink TBF Establishment/ Abnormal cases/Violation of multi-slot capabilities | R97 and R98 only | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|------------------|---|---------------------------|--------|--------------------------|-----------|
| 42.2.3.3.2 | Fixed Allocation/ Uplink Transfer with Downlink TBF Establishment/ Abnormal cases/No defined PDCH | R97 and R98 only | GPRS MS supporting GPRS multislot class 2 | | C231 | | |
| 42.2.4.2.1 | Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Uplink Assignment/ Non half-duplex | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.4.2.2 | Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Uplink Assignment/ Half-duplex | R97 and R98 only | GPRS MS supporting GPRS multislot classes 19 to 29 | | C232 | | |
| 42.2.4.3.1 | Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Timeslot Reconfigure/ Starting time with AFN encoding | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.2.4.3.2 | Fixed Allocation/ Downlink Transfer with Uplink TBF Establishment/ Packet Timeslot Reconfigure/ Starting time with relative encoding | R97 and R98 only | All GPRS MS | | C215 | | |
| 42.3.1.1.1 | Dynamic Allocation/ Uplink Transfer/ Normal/ Successful | R97 | All GPRS MS | | C215 | | |
| 42.3.1.1.3 | Dynamic Allocation/ Uplink Transfer/ Normal/ Starting frame number encoding | R97 | All GPRS MS | | C215 | | |
| 42.3.1.1.4 | Dynamic Allocation/ Uplink Transfer/ Normal/ Starting time | R97 | All GPRS MS | | C215 | | |
| 42.3.1.1.5 | Void | | | | | | |
| 42.3.1.1.6 | Dynamic Allocation/ Uplink Transfer/ Normal/ T3180 expiry | R97 | All GPRS MS | | C215 | | |
| 42.3.1.1.7 | Dynamic Allocation/ Uplink Transfer/ Normal/ PACCH operation | R97 | All GPRS MS | | C215 | | |
| 42.3.1.1.8 | Dynamic Allocation/ Uplink Transfer/ Normal/ Two uplink timeslots | R97 | All GPRS MS supporting GPRS multislot classes 5 to 7, 9 to 29 | | C325 | | |
| 42.3.1.1.9 | Dynamic Allocation/ Uplink Transfer/ Normal/ Frequency parameters | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|--|---------|---|---------------------------|--------|---|-----------|
| 42.3.1.1.10 | Dynamic Allocation / Uplink Transfer / Normal / USF assigned with MCS-1 to MCS-4 | R99 | All GPRS MS | | C215 | | |
| 42.3.1.2.2 | Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in acknowledged mode | R97 | All GPRS MS | | C215 | | |
| 42.3.1.2.3 | Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in unacknowledged mode | R97 | All GPRS MS | | C215 | | |
| 42.3.2.1.1 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Successful | R97 | All GPRS MS | | C215 | | |
| 42.3.2.1.2 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Multislot capabilities | R97 | All GPRS MS supporting GPRS multislot classes 2,3,4,5,6,8,9,10,19 and 24 | | C234 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.3.2.2.1 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/with random access | R97 | All GPRS MS | | C215 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.3.2.2.2 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/Continuation of normal operation | R97 | All GPRS MS | | C215 | | |
| 42.3.3.1.1 | Dynamic Allocation/Resource reallocation/Successful/Higher throughput class or higher radio priority | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |
| 42.3.3.1.2 | Dynamic Allocation/Resource reallocation/Successful/Lower throughput class | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |
| 42.3.3.1.3 | Dynamic Allocation/Resource reallocation/Successful/Different RLC mode and higher radio priority | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|--|-----------|
| 42.3.3.2.1 | Dynamic Allocation/Resource reallocation/Abnormal/T3168 expiry | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |
| 42.3.3.2.2 | Dynamic Allocation/Resource reallocation/Abnormal/Invalid assignment | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | TSPC_Type_GSM_P_Band TSPC_Type_DCS_Band TSPC_Type_GSM_700_Band TSPC_Type_GSM_850_Band TSPC_Type_T_GSM_810_Band | |
| 42.3.3.3 | Dynamic Allocation/Resource reallocation/Reject | R97 | GPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |
| 42.3.3.4 | Dynamic Allocation / Resource reallocation / Successful / Lower Coding Scheme Command | R97 | All GPRS MS | | C215 | | |
| 42.4.1.1 | Network Control measurement reporting/Uplink/Normal case | R97 | All GPRS MS | | C215 | | |
| 42.4.1.2 | Network Control measurement reporting/Idle mode/New cell reselection | R97 | All GPRS MS | | C215 | | |
| 42.4.1.3 | Network Control measurement reporting/Downlink transfer/Normal case | R97 | All GPRS MS | | C215 | | |
| 42.4.1.4 | Network Control measurement reporting / Uplink transfer / Continuation in Idle mode | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 42.4.1.5 | Network Control measurement reporting / Idle mode / DSC failure/ reselection | R97 | All GPRS MS | | C215 | | |
| 42.4.2.1.1 | Cell change order procedure/Uplink transfer/Normal case | R97 | All GPRS MS | | C215 | | |
| 42.4.2.1.2 | Void | | | | | | |
| 42.4.2.1.3 | Cell change order procedure/Uplink transfer/Failure cases/REJECT from the new cell | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--|-----------|
| 42.4.2.1.4 | Cell change order procedure/Uplink transfer/Failure cases/Contention resolution failure | R97 | All GPRS MS | | C215 | | |
| 42.4.2.1.5 | Void | | | | | | |
| 42.4.2.1.6 | Cell change order procedure/Uplink transfer/Failure cases/Frequency not implemented | R97 | All GPRS MS | | C215 | | |
| 42.4.2.2.1 | Cell change order procedure/Downlink transfer/Normal case | R97 | All GPRS MS | | C215 | | |
| 42.4.2.2.2 | Cell change order procedure/Downlink transfer/Failure cases/REJECT from the new cell | R97 | All GPRS MS | | C215 | | |
| 42.4.2.2.3 | Cell change order procedure/Downlink transfer/Failure cases/Frequency not implemented | R97 | All GPRS MS | | C215 | | |
| 42.4.2.3.1 | Cell change order procedure/Simultaneous uplink and downlink transfer/Normal case | R97 | All GPRS MS | | C215 | | |
| 42.4.2.3.2 | Void | | | | | | |
| 42.4.2.3.3 | Packet Measurement order procedure / Downlink transfer / Normal case/ Dedicated parameters | R97 | All GPRS MS | | C215 | | |
| 42.4.2.3.4 | Packet Measurement order procedure / Downlink transfer / Normal case/ Routing Area Update/ NMO II | R97 | All GPRS MS | | C215 | | |
| 42.4.2.3.5 | Packet Measurement order procedure / Downlink transfer / Normal case/ Routing Area Update/ NMO I | R97 | All GPRS MS | | C215 | | |
| 42.4.2.3.6 | MT CS establishment whilst in NC2 with a downlink TBF established | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|--|-----------|
| 42.4.2.3.7 | MT CS establishment whilst in NC2 with a uplink TBF established | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.3.1.1 | Void | | | | | | |
| 42.4.4.1 | Cell Change Order Procedures without PBCCH /Network Controlled Cell Reselection – Packet Measurement Order Procedure | R97 | All GPRS MS | | C215 | | |
| 42.4.4.2 | Cell Change Order Procedures without PBCCH /Network Controlled Cell Reselection/validity of reselection parameters/MS enters standby state | R97 | All GPRS MS | | C215 | | |
| 42.4.4.3 | Network Control measurement reporting / Idle mode / Returning to Broadcast parameters | R97 | All GPRS MS | | C215 | | |
| 42.4.4.4 | Void | | | | | | |
| 42.4.4.5 | Network Control measurement reporting / Idle mode / Reselection due to RA failure | Rel-6 | All GPRS MS | | C215 | | |
| 42.4.5.1 | Network Assisted Cell Change / Expiry of T3206 | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.2 | Network Assisted Cell Change / No Packet Neighbouring Cell Data and Packet Cell Change Continue | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.3 | Network Assisted Cell Change / Packet Neighbour Cell Data and Packet Cell Change Continue | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.4 | Network Assisted Cell Change / Packet Neighbour Cell Data and Packet Cell Change Order | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.5 | Network Assisted Cell Change / Expiry of T3208 and T3210 | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.6 | Network Assisted Cell Change / Entering packet idle mode | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.7 | Network Assisted Cell Change / CCN not supported towards target cell | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 42.4.5.8 | Network Assisted Cell Change / NC mode change | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.5.9 | Network Assisted Cell Change / NC mode change / Packet Neighbour Cell Data | Rel-4 | All GPRS MS supporting GERAN FEATURE PACKAGE 1 | | C322 | | |
| 42.4.6.1 | Network Control PEMR– Activation with SI Messages | R99 | All GPRS MS | | C215 | | |
| 42.4.6.2 | Network Control PEMR - Activation with PSI messages | R99 | All GPRS MS | | C215 | | |
| 42.4.6.3 | Network Control PEMR– Packet Measurement Order | R99 | All GPRS MS | | C215 | | |
| 42.4.6.4 | Network Control PEMR– Uplink Data Transfer | R99 | All GPRS MS | | C215 | | |
| 42.4.6.5 | Network Control PEMR– Downlink Data Transfer | R99 | All GPRS MS | | C215 | | |
| 42.4.6.6 | Network Control PEMR / Packet Cell Change Order | R99 | All GPRS MS | | C215 | | |
| 42.4.6.7 | Network Control PEMR / Packet Enhanced Measurement Report / Measurement reporting with PBCCH / Invalid BSIC | R99 | All GPRS MS | | C215 | | |
| 42.4.7.1 | Inter-RAT Cell Change Order (Known Cell) – Uplink Data Transfer | R99 | MS supporting both GPRS and UTRAN | | C324 | | |
| 42.4.7.2 | Inter-RAT Cell Change Order (Unknown Cell) – Uplink Data Transfer | R99 | MS supporting both GPRS and UTRAN | | C324 | | |
| 42.4.7.3 | Inter-RAT Cell Change Order (Unknown Cell) – Downlink Data Transfer | R99 | MS supporting both GPRS and UTRAN | | C324 | | |
| 42.4.7.4 | Inter-RAT Cell Change Order (Unknown Cell) – Simultaneous uplink and downlink transfer | R99 | MS supporting both GPRS and UTRAN | | C324 | | |
| 42.4.7.5.1 | Inter-RAT (GPRS to UTRAN) Cell Change Order (Known cell) / Failure / Uplink transfer / T3174 expiry | R99 | MS supporting both GPRS and UTRAN | | C324 | | |
| 42.4.7.5.2 | Inter-RAT (GPRS to UTRAN) Cell Change Order (Known cell) / Failure / Downlink transfer / REJECT from target UTRAN cell with Inter-RAT info set to GSM | R99 | MS supporting both GPRS and UTRAN | | C324 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---------------|---------------------------|--------|--------------------------|-----------|
| 42.4.8.1.1 | NC2 and DRX / NC_NON_DRX_PERIOD / Respect of NC2 non-DRX mode period | R97 | All GPRS MS | | C215 | | |
| 42.4.8.1.2 | NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period ordered in Packet Cell Change Order | R97 | All GPRS MS | | C215 | | |
| 42.4.8.1.3 | NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period broadcast in PSI5 | R97 | All GPRS MS | | C215 | | |
| 42.4.8.1.4 | NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period broadcast in SI2Quater | R99 | All GPRS MS | | C215 | | |
| 42.4.8.1.5 | NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period / PBCCH present / Default Value | R97 | All GPRS MS | | C215 | | |
| 42.4.8.1.6 | NC2 and DRX / NC_NON_DRX_PERIOD / NC2 non-DRX mode period / PBCCH absent / Default Value | R99 | All GPRS MS | | C215 | | |
| 42.4.8.2.1 | User Data Vs Measurement Report Sending / Conflict situation / DL TBF Establishment and Packet Access for Measurement Report Sending | R97 | All GPRS MS | | C215 | | |
| 42.4.8.2.2 | User Data vs. Measurement Report Sending / Conflict situation / Expiry of T3192 and T3158 | R97 | All GPRS MS | | C215 | | |
| 42.4.8.2.3 | User Data vs. Measurement Report Sending / Conflict situation / Expiry of T3182 and T3158 | R97 | All GPRS MS | | C215 | | |
| 42.4.8.2.4 | User Data vs. Measurement Report Sending / Conflict situation / Random Access procedure for PMR sending and User Data transmission | R99 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--|-----------|
| 42.4.8.3.1 | Network Control measurement reporting / Dedicated connection / Timer Ready expiry | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.8.3.2 | Network Control measurement reporting / Dedicated connection / Different NC parameters / No T3158 expiry | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.8.3.3 | Network Control measurement reporting / Dedicated connection / Handover / No T3158 expiry | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.8.3.4 | Network Control measurement reporting / Dedicated connection / Different NC parameters / T3158 expiry | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.8.3.5 | Network Control measurement reporting / Dedicated connection / Handover / T3158 expiry | R97 | All GPRS MS supporting class A or B mode of operation and at least one MT circuit switched basic service | | C459 | TSPC_MS_GPRS_RELEASE TSPC_AddInfo_ImmConn | |
| 42.4.8.3.6 | Network Control measurement reporting / Dedicated connection / Assignment Reject | R97 | All GPRS MS supporting class A or B mode of operation | | C226 | | |
| 42.4.8.4.1 | Network Control measurement reporting / NC_FREQUENCY_LIST / NC_FREQUENCY_LIST in Packet measurement order. | R97 | All GPRS MS | | C215 | | |
| 42.4.8.4.2 | Network Control measurement reporting / NC_FREQUENCY_LIST / NC_FREQUENCY_LIST in Packet Cell Change Order. | R97 | All GPRS MS | | C215 | | |
| 42.4.8.4.3 | Network Control measurement reporting / NC_FREQUENCY_LIST / PMO with empty NC_FREQUENCY_LIST/ Return to BA(GPRS). | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 42.4.8.4.4. | Network Control measurement reporting / NC_FREQUENCY_LIST / Changes in BA(GPRS)/ Return to BA(GPRS). | R97 | All GPRS MS | | C215 | | |
| 42.4.8.4.5 | Network Control measurement reporting / NC_FREQUENCY_LIST / Dedicated connection/ Return to BA(GPRS) | R99 | All GPRS MS supporting class A or B mode of operation operation and at least one MT circuit switched basic service | | C459 | TSPC_AddInfo_ImmConn | |
| 42.4.8.4.6 | Network Control measurement reporting / NC_FREQUENCY_LIST / PMO sent in multiple instances. | R97 | All GPRS MS | | C215 | | |
| 42.4.8.4.7 | Network Control measurement reporting / NC_FREQUENCY_LIST / same cell present twice in the list | R97 | All GPRS MS | | C215 | | |
| 42.4.8.5.1-1 | Ignoring Packet Measurement Order and Packet Cell Change Order whilst in DTM, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 42.4.8.5.1-2 | Ignoring Packet Measurement Order and Packet Cell Change Order whilst in DTM, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 42.5.1.1 | Downlink Transfer/ Normal Operation/Relative Encoding TBF starting time | R97 | All GPRS MS | | C215 | | |
| 42.5.1.2 | Downlink Transfer/ Normal Operation/Without TBF starting time | R97 | All GPRS MS | | C215 | | |
| 42.5.2.1 | Downlink Transfer/ Polling/ Normal operation/RLC data block | R97 | All GPRS MS | | C215 | | |
| 42.5.2.2 | Downlink Transfer/ Polling/ Packet Polling Request/ Access Burst format | R97 | All GPRS MS | | C215 | | |
| 42.5.2.3 | Downlink Transfer/ Polling/ Packet Polling Request/ Control block format | R97 | All GPRS MS | | C215 | | |
| 42.5.3.1 | Downlink Transfer/ T3190 Expiry/Initial allocation/Restart with valid RLC data block | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 42.5.4.1 | Downlink Transfer/ T3190 Expiry/Resource reallocation/Without TBF starting time | R97 | All GPRS MS | | C215 | | |
| 42.5.4.2 | Downlink Transfer/ T3190 Expiry/Resource reallocation/With TBF starting time | R97 | All GPRS MS | | C215 | | |
| 42.5.4.3 | Downlink Transfer/ T3190 Expiry/Resource reallocation/Restart with valid RLC data block | R97 | All GPRS MS | | C215 | | |
| 42.5.5.1 | Downlink Transfer/ Reestablishment/ T3192 Expiry | R97 | All GPRS MS | | C215 | | |
| 42.5.5.2 | Downlink Transfer/ Reestablishment/ Packet Downlink Assignment | R97 | All GPRS MS | | C215 | | |
| 42.5.5.3 | Downlink Transfer/ Reestablishment/ Invalid Frequency Parameters IE | R97 | All GPRS MS | | C215 | | |
| 42.6.1 | Exclusive allocation in single-slot configuration | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 42.7.1 | Packet Assignment / TA Value/TA present in second Packet downlink assignment | R97 | All GPRS MS | | C215 | | |
| 42.7.2 | Packet Assignment / TA Value/TA not present in Packet uplink assignment sent on the PACCH | R97 | All GPRS MS | | C215 | | |
| 42.7.3 | Packet Assignment / TA Value/ PACKET POWER CONTROL/TIMING ADVANCE during contention resolution | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 42.7.4 | Packet Assignment / TA Value/TAI present/ multislot Applicability | R97 | All GPRS MS not operating in GPRS multislot class 1, 2, 3, 4 or 8 and 30 to 45 | | C419 | | |
| 42.7.5 | Packet Assignment / TA Value/ Update of TA using PACKET POWER CONTROL/TIMING ADVANCE | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|------------------|--|---------------------------|--------|---|-----------|
| 42.7.6 | Packet Uplink Assignment / One phase access / Timing Advance / TA Index present | R97 | All GPRS MS | | C215 | | |
| 42.7.7 | Packet Uplink Assignment / One phase access / Timing Advance / TA value field not provided | R97 | All GPRS MS | | C215 | | |
| 42.8.1 | Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Expiry | R97 | All GPRS MS | | C215 | | |
| 42.8.2 | Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Stop with Packet Uplink Assignment | R97 | All GPRS MS | | C215 | | |
| 42.8.3 | Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Packet Access Reject/ With WAIT_INDICATION | R97 | All GPRS MS | | C215 | | |
| 42.8.4 | Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Packet Access Reject/ No WAIT_INDICATION | R97 | All GPRS MS | | C215 | | |
| 42.8.5 | Dynamic Allocation/ Downlink Transfer with Uplink TBF Establishment/ T3168/ Packet Access Reject/ With Polling | R97 | All GPRS MS | | C215 | | |
| 42.9.2.1.1 | Extended Dynamic Allocation / Uplink Transfer / Normal / Successful | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.1.2 | Extended Dynamic Allocation / Uplink Transfer / Normal / USF_GRANULARITY = 4 blocks | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3, 5, 6, 7, 9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | | |
| 42.9.2.1.3 | Extended Dynamic Allocation / Uplink Transfer / Normal / Allocation via polling mechanism | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.1.4 | Extended Dynamic Allocation / Uplink Transfer / Normal / | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|------------------|--|---------------------------|--------|---|-----------|
| | PACCH operation in downlink | | GPRS multislot classes: 3, 5, 6, 7, 9 to 29, 31 to 34, 36 to 39, 41 to 45 | | | | |
| 42.9.2.1.5 | Extended Dynamic Allocation / Uplink Transfer / Normal / Polling for PDAN | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3, 5, 6, 7, 9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.2.1 | Extended Dynamic Allocation / Uplink Transfer / configuration change / Changes in the Allocation from Dynamic to Extended Dynamic. | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.2.2 | Extended Dynamic Allocation / Uplink Transfer / configuration change / Changes in the Allocation from Extended Dynamic to Dynamic. | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.2.3 | Extended Dynamic Allocation / Uplink Transfer / configuration change / Reduction in number of uplink slots using PACKET UPLINK ASSIGNMENT. | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.2.4 | Extended Dynamic Allocation / Uplink Transfer / configuration change / Reduction in number of uplink slots using PACKET PDCH RELEASE. | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRSmultislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.2.2.5 | Extended Dynamic Allocation / Uplink Transfer / configuration change / Increase in number of uplink slots | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation and GPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C348 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.3.1.1 | Extended Dynamic Allocation / Shifted USF / PACCH management / Successful | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation AND GPRS multislot classes: 34, 39 and 45 | | C420 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 42.9.3.1.2 | Extended Dynamic Allocation / Shifted USF / Normal / USF assignment on 2 nd PDCH | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation AND GPRS multislot classes: 34, 39 and 45 | | C420 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|------------------|--|---------------------------|--------|---|-----------|
| 42.9.3.1.3 | Extended Dynamic Allocation / Shifted USF / Normal / Release of 2 nd PDCH | R99 (see note 1) | All GPRS MS supporting Extended Dynamic Allocation AND GPRS multislot classes: 34, 39 and 45 | | C420 | TSPC_Type_GPRS_Multislot_ClassX (where X = 1..45) | |
| 43.1.1.1 | Acknowledged mode/Uplink TBF/Send state variable V(S) | R97 | All GPRS MS | | C215 | | |
| 43.1.1.2 | Acknowledged mode/Uplink TBF/Transmit window size | R97 | All GPRS MS | | C215 | | |
| 43.1.1.3 | Acknowledged mode/Uplink TBF/Acknowledge state variable V(A) | R97 | All GPRS MS | | C215 | | |
| 43.1.1.4 | Acknowledged mode/Uplink TBF/Negatively acknowledged RLC data blocks | R97 | All GPRS MS | | C215 | | |
| 43.1.1.5 | Acknowledged mode/Uplink TBF/Invalid Negative Acknowledgement | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 43.1.1.6 | Acknowledged mode/Uplink TBF/Decoding of Received Block Bitmap | R97 | All GPRS MS | | C215 | | |
| 43.1.2.1 | Acknowledged mode/Downlink TBF/Receive state variable V(R) | R97 | All GPRS MS | | C215 | | |
| 43.1.2.2 | Acknowledged mode/Downlink TBF/Receive window state variable V(Q) | R97 | All GPRS MS | | C215 | | |
| 43.1.2.3 | Acknowledged mode/Downlink TBF/Re-assembly of RLC data blocks | R97 | All GPRS MS | | C215 | | |
| 43.1.2.4 | Acknowledged mode/Downlink TBF/Re-assembly/Length Indicator | R97 | All GPRS MS | | C215 | | |
| 43.2.1 | Control Blocks Re-assembly | R97 | All GPRS MS | | C215 | | |
| 44.2.1.1.1 | GPRS attach/accepted | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.2 | GPRS attach/rejected/IMSI invalid/illegal MS | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---------------|---------------------------|--------|--|-----------|
| 44.2.1.1.3 | GPRS attach/rejected/IMSI invalid/GPRS services not allowed | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 44.2.1.1.4-1 | GPRS attach/rejected/PLMN not allowed | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.4-2 | GPRS attach/rejected/PLMN not allowed | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.5-1 | GPRS attach/rejected/roaming not allowed in this location area | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.5-2 | GPRS attach/rejected/roaming not allowed in this location area | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.5-3 | GPRS attach/rejected/roaming not allowed in this location area | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.5-4 | GPRS attach/rejected/roaming not allowed in this location area | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.6-1 | GPRS attach/abnormal cases/access barred due to access class control | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.6-2 | GPRS attach/abnormal cases/access barred due to access class control | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.1.7 | GPRS attach/abnormal cases/change of cell into new routing area | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|---------|---|---------------------------|--------|--|-----------|
| 44.2.1.1.8 | GPRS attach/abnormal cases/power off | R97 | GPRS MS that supports On/Off switch | | C317 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP | |
| 44.2.1.1.9 | GPRS attach/abnormal cases/GPRS detach procedure collision | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_on_NW_Detach_NoCause | |
| 44.2.1.1.10 | GPRS attach / rejected / GPRS services not allowed in this PLMN | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.2.1 | Combined GPRS attach/GPRS and non-GPRS attach accepted | R97 | GPRS MS and Class A or B Mode of Operation | R1 | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.2.2-1 | Combined GPRS attach/GPRS only attach accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.2.2-2 | Combined GPRS attach/GPRS only attach accepted | R97 | GPRS MS and A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_auto_MM_IMSI_AP_on_off | |
| 44.2.1.2.3 | Combined GPRS attach/GPRS attach while IMSI attach | R97 | A Class A or B GPRS MS which do not auto GPRS attach on power up or switch on | | C236 | TSPC_Feat_OnOff | |
| 44.2.1.2.4 | Combined GPRS attach/rejected/IMSI invalid/illegal ME | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 44.2.1.2.5 | Combined GPRS attach/rejected/GPRS services and non-GPRS services not allowed | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.2.6 | Combined GPRS attach/rejected/GPRS services not allowed | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.1.2.7 | Combined GPRS attach/rejected/location area not allowed | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding | |
| 44.2.1.2.8 | Combined GPRS attach/abnormal cases/attempt counter check/miscellaneous reject causes | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|---|-----------|
| 44.2.1.2.9 | Combined GPRS attach/abnormal cases/GPRS detach procedure collision | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_on_NW_Detach_NoCause | |
| 44.2.2.1.1 | GPRS detach/power off/accepted | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.2 | GPRS detach/accepted | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_MS_GPRS_RELEASE | |
| 44.2.2.1.3 | GPRS detach/abnormal cases/attempt counter check/procedure timeout | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.4 | GPRS detach/abnormal cases/GMM common procedure collision | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.5 | GPRS detach/power off/accepted | R97 | GPRS MS and Class A or B Mode of Operation | R1 | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.6 | GPRS detach/accepted/GPRS/IMSI detach | R97 | All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off. | | C274 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.7 | GPRS detach/accepted/IMSI detach | R97 | All GPRS MS supporting user requested non-GPRS detach. | | C275 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.8 | GPRS detach/abnormal cases/change of cell into new routing area | R97 | All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off. | | C274 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.1.9 | GPRS detach/abnormal cases/GPRS detach procedure collision | R97 | All GPRS MS supporting user requested combined circuit switch and packet switch detach without power off. | | C274 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.2.1 | GPRS detach/re-attach not required/accepted | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-------------|---|---------|--|---------------------------|--------|--|-----------|
| 44.2.2.2.2 | GPRS detach/rejected/IMSI invalid/GPRS services not allowed | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 44.2.2.2.3 | GPRS detach/IMSI detach/accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.2.4 | GPRS detach/re-attach requested/accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.2.2.5 | GPRS detach/rejected/location area not allowed | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding | |
| 44.2.2.2.6 | GPRS detach / rejected / GPRS services not allowed in this PLMN | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.1 | Routing area updating/accepted | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.1a | Routing area updating/accepted / old P-TMSI | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.2 | Routing area updating/rejected/IMSI invalid/illegal ME | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |
| 44.2.3.1.3 | Routing area updating/rejected/MS identity cannot be derived by the network | R97 | All GPRS MS | R1, L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_auto_AP_no_MS ID | |
| 44.2.3.1.4 | Routing area updating/rejected/location area not allowed | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|---|-----------|
| 44.2.3.1.5 | Routing area updating/abnormal cases/attempt counter check/miscellaneous reject causes | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.6 | Routing area updating/abnormal cases/change of cell into new routing area | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.7 | Routing area updating/abnormal cases/change of cell during routing area updating procedure | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.1.8 | Routing area updating/abnormal cases/P-TMSI reallocation procedure collision | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.1 | Combined routing area updating/combined RA/LA accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.2 | Combined routing area updating/MS in CS operation at change of RA | R97 | All GPRS MS supporting CC protocol for at least one Bearer Capability | R1 | C210 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.3-1 | Combined routing area updating/RA only accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.3-2 | Combined routing area updating/RA only accepted | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_auto_MM_IMSI_AP_on_off | |
| 44.2.3.2.4 | Combined routing area updating/rejected/PLMN not allowed | R97 | GPRS MS and Class A or B Mode of Operation | R1 | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding | |
| 44.2.3.2.5-1 | Combined routing area updating/rejected/roaming not allowed in this location area | R97 | GPRS MS and Class A or B Mode of Operation | R1 | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_GPRS_Attach_Attempt_Outstanding TSPC_MS_GPRS_RELEASE | |
| 44.2.3.2.5-2 | Combined routing area updating/rejected/roaming not allowed in this location area | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_AddInfo_SIMRmv TSPC_MS_GPRS_RELEASE | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------------|---|---------|--|---------------------------|--------|---|-----------|
| 44.2.3.2.6-1 | Combined routing area updating/abnormal cases/access barred due to access class control | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.6-2 | Combined routing area updating/abnormal cases/access barred due to access class control | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.7 | Combined routing area updating/abnormal cases/attempt counter check/procedure timeout | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.8 | Combined routing area updating/abnormal cases/change of cell into new routing area | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.9 | Combined routing area updating/abnormal cases/change of cell during routing area updating procedure | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.10-1 | Combined routing area updating/abnormal cases/GPRS detach procedure collision | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.2.10-2 | Combined routing area updating/abnormal cases/GPRS detach procedure collision | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.3.1 | Periodic routing area updating/accepted | R97 | All GPRS MS | R1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.3.2 | Periodic routing area updating/accepted/T3312 default value | R97 | GPRS MS and Class B Mode of Operation | | C221 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.3.3 | Periodic routing area updating/no cell available/network mode I | R97 | GPRS MS and Class B Mode of Operation | | C221 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.3.3.4 | Periodic routing area updating/no cell available | R97 | GPRS MS and Class A or B Mode of Operation | | C226 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.4 | P-TMSI reallocation | R97 | All GPRS MS | R1, L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|-------------------------------------|---------|-----------------------------|---------------------------|--------|---|-----------|
| 44.2.5.1.1 | Authentication accepted | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.5.1.2 | Authentication rejected | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.5.2.1-1 | Ciphering mode/start ciphering/GEA1 | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.5.2.1-2 | Ciphering mode/start ciphering/GEA2 | R97 | All GPRS MS supporting GEA2 | | C415 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_Feat_GEA2 | |
| 44.2.5.2.1-3 | Ciphering mode/start ciphering/GEA3 | Rel-6 | All GPRS MS supporting GEA3 | | C416 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_Feat_GEA3 | |
| 44.2.5.2.2 | Ciphering mode/stop ciphering | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.5.2.3 | Ciphering mode/IMEISV request | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.6.1 | General Identification | R97 | All GPRS MS | | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.7-1 | GMM READY timer handling | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.7-2 | GMM READY timer handling | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---|---------------------------|--------|--|-----------|
| 44.2.7-3 | GMM READY timer handling | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.7-4 | GMM READY timer handling | R97 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.7-5 | GMM READY timer handling | R97 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.8.1.1 | Change of cell between two LAs in idle mode / RAU completes first | R99 | All DTM/GPRS capable MS | | C305 | | |
| 44.2.8.1.2 | Change of cell between two LAs in idle mode / LAU completes first / SS releases channel | R99 | All DTM/GPRS capable MS | | C305 | | |
| 44.2.8.1.3 | Change of cell between two LAs in idle mode / LAU completes first / SS maintains channel | R99 | All DTM/GPRS capable MS | | C305 | | |
| 44.2.8.2 | Void | | | | | | |
| 44.2.9.1.1 | NITZ / GPRS / Timezone, Time and DST Handling | R97 | All NITZ (Time) and GPRS capable MS | | C442 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_NITZ_DST TSPC_NITZ_Universal_Time TSPC_NITZ_Time_Zone | |
| 44.2.9.1.2 | NITZ / GPRS / NITZ Parameters / Storage / Deletion | R97 | All NITZ (Name) and GPRS capable MS | | C443 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_NITZ_Short_Name TSPC_NITZ_Full_Name | |
| 44.2.9.1.3 | NITZ / GPRS / MM and GMM Signalling | R97 | All NITZ (Time and/or Name) and GPRS capable MS | | C334 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff TSPC_NITZ_DST TSPC_NITZ_Universal_Time TSPC_NITZ_Time_Zone TSPC_NITZ_Short_Name TSPC_NITZ_Full_Name | |
| 44.2.10 | MS Radio Access Capability Interrogation | R97 | All GPRS MS | | C215 | TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|------------------|---|---------------------------|--------|---|-----------|
| 44.2.11-1 | Cell Notification – Ready Timer Behaviour | R99 | All GPRS MS | L2 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 44.2.11-2 | Cell Notification – Use of LLC NULLFrame | R99 | All GPRS MS | L1 | C215 | TSPC_operation_mode_B TSPC_operation_mode_C TSPC_AddInfo_on_auto_GPRS_AP TSPC_Feat_OnOff | |
| 45.2.1.1 | Attach initiated by context activation/QoS Offered by Network is the QoS Requested | R97 | All GPRS MS | R1 | C215 | TSPC_AddInfo_on_auto_GPRS_AP | |
| 45.2.1.2.1 | QoS Accepted by MS | R97 and R98 only | All GPRS MS supporting user settings of minimum QoS | | C248 | | |
| 45.2.1.2.2 | QoS Rejected by MS | R97 and R98 only | All GPRS MS supporting user settings of minimum QoS | | C248 | | |
| 45.2.2-1 | PDP context activation requested by the network, successful and unsuccessful | R97 | All GPRS MS supporting Network requested PDP context activation | | C405 | | |
| 45.2.2-2 | PDP context activation requested by the network, successful and unsuccessful | R97 | All GPRS MS not supporting Network requested PDP context activation | | C237 | | |
| 45.2.3 | Void | | | | | | |
| 45.2.4.1 | T3380 Expiry | R97 | All GPRS MS | | C215 | | |
| 45.2.4.2-1 | Collision of MS initiated and network requested PDP context activation | R97 | All GPRS MS supporting Network requested PDP context activation | | C405 | | |
| 45.2.4.2-2 | Collision of MS initiated and network requested PDP context activation | R97 | All GPRS MS not supporting Network requested PDP context activation | | C237 | | |
| 45.2.4.3 | Network initiated PDP context activation request for an already activated PDP context (on the MS side) | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation | | C332 | TSPC_AddInfo_N_req_PDP_CA | |
| 45.2.5.1.1 | QoS Offered by Network is the QoS Requested | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation | | C332 | | |
| 45.2.5.1.2.1 | QoS accepted by MS | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation and supporting user settings of minimum QoS | | C406 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|---|------------------|---|---------------------------|--------|--------------------------|-----------|
| 45.2.5.1.2.2 | QoS rejected by MS | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation and supporting user settings of minimum QoS | | C406 | | |
| 45.2.5.2 | Unsuccessful Secondary PDP Context Activation Procedure Initiated by the MS | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation | | C332 | | |
| 45.2.5.3.1 | T3380 Expiry | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation | | C332 | | |
| 45.3.1 | Network PDP context modification | R97 and R98 only | All GPRS MS supporting user settings of minimum QoS | | C248 | | |
| 45.3.2.1 | MS initiated PDP Context Modification accepted by network | R99 | All GPRS MS supporting user settings of minimum QoS | | C248 | | |
| 45.3.2.2 | MS initiated PDP Context Modification not accepted by the network | R99 | All GPRS MS | | C215 | | |
| 45.3.3.1 | T3381 Expiry | R99 | All GPRS MS | | C215 | | |
| 45.3.3.2 | Collision of MS and network initiated PDP context modification procedures | R99 | All GPRS MS | | C215 | | |
| 45.4.1 | PDP context deactivation initiated by the MS | R97 | All GPRS MS | R1 | C215 | | |
| 45.4.2 | PDP context deactivation initiated by the network | R97 | All GPRS MS | R1 | C215 | | |
| 45.4.3.1 | T3390 Expiry | R97 | All GPRS MS | | C215 | | |
| 45.4.3.2 | Collision of MS and network initiated PDP context deactivation requests | R97 | All GPRS MS | | C215 | | |
| 45.4.4 | PDP context deactivation initiated by the network / Tear down indicator | R99 | GPRS MS supporting two or more PDP contexts and GPRS MS supporting Secondary PDP Context Activation | | C332 | | |
| 45.5.1 | Error cases | R97 | All GPRS MS | | C215 | TSPC_MS_GPRS_RELEASE | |
| 46.1.2.1.1-1 | Data transmission in protected mode/GEA1 | R97 | All GPRS MS | | C215 | | |
| 46.1.2.1.1-2 | Data transmission in protected mode/GEA2 | R97 | All GPRS MS supporting GEA2 | | C415 | TSPC_Feat_GEA2 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|-----------------------------|---------------------------|--------|--------------------------|-----------|
| 46.1.2.1.1-3 | Data transmission in protected mode/GEA3 | Rel-6 | All GPRS MS supporting GEA3 | | C416 | TSPC_Feat_GEA3 | |
| 46.1.2.1.2 | Data transmission in unprotected mode | R97 | All GPRS MS | | C215 | | |
| 46.1.2.1.3 | Reception of I frame in ADM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.1.1 | Link establishment from MS to SS | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.1.2 | Link establishment from SS to MS | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.1.3 | Loss of UA frame | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.1.4 | Total loss of UA frame | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.1.5 | DM response | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.2.1 | Checking N(S) | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.2.2 | Busy condition at the peer, with RR sent for resumption of transmission | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.2.3 | Busy condition at the peer, with ACK sent for resumption of transmission | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.2.4 | SACK frame | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.3.1 | Checking N(R) | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.3.2 | MS handling busy condition during bi-directional data transfer | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.3.3 | SACK frame | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.3.4 | ACK frame | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.4.1 | Reestablishment due to reception of SABM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.4.2 | Reestablishment due to N200 failures | R97 | All GPRS MS | | C215 | | |
| 46.1.2.2.4.3 | Reestablishment due to reception of DM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.3.1 | Collision of SABM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.3.2 | Collision of SABM and DISC | R97 | All GPRS MS | | C215 | | |
| 46.1.2.3.3 | Collision of SABM and XID commands | R97 | All GPRS MS | | C215 | | |
| 46.1.2.4.1 | Unsolicited DM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.5.1 | Sending FRMR due to undefined command control field | R97 | All GPRS MS | | C215 | | |
| 46.1.2.5.2 | Sending FRMR due to reception of an S frame with incorrect length | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 46.1.2.5.3 | Sending FRMR due to reception of an I frame information field exceeding the maximum length | R97 | All GPRS MS | | C215 | | |
| 46.1.2.5.4 | Frame reject condition during establishment of ABM | R97 | All GPRS MS | | C215 | | |
| 46.1.2.6.1 | Simultaneous acknowledged and unacknowledged data transfer on the same SAPI | R97 | GPRS MS supporting two or more PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C224 | | |
| 46.1.2.6.2 | Simultaneous acknowledged and unacknowledged data transfer on different SAPIs | R97 | GPRS MS supporting two or more PDP contexts | | C223 | | |
| 46.1.2.7.1 | Negotiation initiated by the SS during ABM, for T200 and N200 | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.2 | Negotiation initiated by the SS during ADM, for N201-I | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.3-1 | Negotiation initiated by the SS (using SABM, for IOV-I) /GEA1 | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.3-2 | Negotiation initiated by the SS (using SABM, for IOV-I)/GEA2 | R97 | All GPRS MS supporting GEA2 | | C415 | TSPC_Feat_GEA2 | |
| 46.1.2.7.3-3 | Negotiation initiated by the SS (using SABM, for IOV-I)/GEA3 | Rel-6 | All GPRS MS supporting GEA3 | | C416 | TSPC_Feat_GEA3 | |
| 46.1.2.7.4 | Negotiation initiated by the SS (during ADM, for N201-U) | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.5-1 | Negotiation initiated by the SS (during ADM, for IOV-U) /GEA1 | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.5-2 | Negotiation initiated by the SS (during ADM, for IOV-U)/GEA2 | R97 | All GPRS MS supporting GEA2 | | C415 | TSPC_Feat_GEA2 | |
| 46.1.2.7.5-3 | Negotiation initiated by the SS (during ADM, for IOV-U)/GEA3 | Rel-6 | All GPRS MS supporting GEA3 | | C416 | TSPC_Feat_GEA3 | |
| 46.1.2.7.6 | Negotiation initiated by the SS (during ABM, for Reset) | R97 | GPRS MS supporting two or more PDP contexts | | C223 | | |
| 46.1.2.7.7 | XID command with unrecognised type field | R97 | All GPRS MS | | C215 | | |
| 46.1.2.7.8 | XID Response with out of range values | R97 | All GPRS MS | | C215 | | |
| 46.2.2.1.1 | Mobile originated normal data transfer with LLC in acknowledged mode | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|---|---------------------------|--------|--|-----------|
| 46.2.2.1.2 | Mobile originated normal data transfer with LLC in unacknowledged mode | R97 | All GPRS MS | | C215 | | |
| 46.2.2.1.3 | Usage of acknowledged mode for data transmission before and after PDP Context modification, on different SAPIs | R97 | All GPRS MS | | C215 | | |
| 46.2.2.1.4 | Reset indication during unacknowledged mode | R97 | All GPRS MS | | C215 | | |
| 46.2.2.1.5 | Reset indication during acknowledged mode | R97 | All GPRS MS | | C215 | | |
| 46.2.2.2.1 | LLC link re-establishment on reception of SN-DATA PDU with F=0 in ack mode in the Receive First Segment state | R97 | All GPRS MS | | C215 | | |
| 46.2.2.2.2 | LLC link re-establishment on receiving second segment with F=1 and with different PCOMP and DCOMP values in the acknowledged mode data transfer | R97 | All GPRS MS | | C215 | | |
| 46.2.2.2.3 | Single segment N-PDU from MS | R97 | All GPRS MS | | C215 | | |
| 46.2.2.3.1 | LLC link release on receiving DM from the SS during acknowledged data transfer | R97 | All GPRS MS | | C215 | | |
| 46.2.2.4.1 | Response from MS on receiving XID request from the SS | R97 | All GPRS MS | | C215 | TSPC_AddInfo_GPRS_Data_Compr TSPC_AddInfo_GPRS_Header_Compr TSPC_AddInfo_GPRS_Header_Compr_Type_RFC1144 TSPC_AddInfo_GPRS_Header_Compr_Type_RFC2507 TSPC_AddInfo_ROHC_Type_RFC3241 TSPC_AddInfo_ROHC_Type_RFC3242 TSPC_AddInfo_ROHC_Type_RFC3408 TSPC_AddInfo_ROHC_Type_RFC3095 | |
| 46.2.2.4.2 | Response from MS on receiving an XID request from the SS with an unassigned entity number | R97 | All GPRS MS supporting Header Compression | | C336 | | |
| 46.2.2.4.3 | Response from MS on receiving an XID response from the SS with unrecognised type field | R97 | All GPRS MS | | C215 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 46.2.2.5 | LLC link release on receiving "Invalid XID response" from the network during link establishment procedure | R97 | All GPRS MS | | C215 | | |
| 47.1.1-1 | Intra frequency reallocation of CS resources / Assignment Cmd, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.1.1-2 | Intra frequency reallocation of CS resources / Assignment Cmd, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.1.2-1 | Intra frequency reallocation of CS resources / Handover, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.1.2-2 | Intra frequency reallocation of CS resources / Handover, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.1.3-1 | Reallocation of CS resources / DTM Assignment Command / Intra frequency, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.1.3-2 | Reallocation of CS resources / DTM Assignment Command / Intra frequency, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.1.4-1 | Inter frequency reallocation of CS resources / DTM Assignment, test 1 | R99 | All DTM/GPRS capable MS and supporting simultaneous multiband operation | | C354 | | |
| 47.1.4-2 | Inter frequency reallocation of CS resources / DTM Assignment, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation and supporting simultaneous multiband operation | | C355 | | |
| 47.2.1-1 | Mobile Originating CS Release, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.2.1-2 | Mobile Originating CS Release, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.2.2 | Void | | | | | | |
| 47.3.1.1 | Handover to same routing area whilst in dedicated mode & MM Ready / Completed on the main DCCH | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.1.2-1 | Handover to same routing area whilst in DTM with DL TBF only, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.1.2-2 | Handover to same routing area whilst in DTM with DL TBF only, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 47.3.1.3.1-1 | Handover to same routeing area whilst in DTM with both DL & UL TBFs / Successful case, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.1.3.1-2 | Handover to same routeing area whilst in DTM with both DL & UL TBFs / Successful case, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.3.1.3.2-1 | Handover to same routeing area whilst in DTM with both DL & UL TBFs / Abnormal case / Handover Failure, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.1.3.2-2 | Handover to same routeing area whilst in DTM with both DL & UL TBFs / Abnormal case / Handover Failure, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.3.2.1 | Handover to different routeing area whilst in DM / Performed on main DCCH / RAU complete before CS release | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.2.2 | Handover to different routeing area whilst in DM / Performed on main DCCH / CS release before RAU complete | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.3.1.1-1 | Handover to different routeing area whilst in DTM / Performed on TBFs / RAU complete before CS release, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.3.1.1-2 | Handover to different routeing area whilst in DTM / Performed on TBFs / RAU complete before CS release, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.3.3.1.2-1 | Handover to different routeing area whilst in DTM / Performed on TBFs / CS release before RAU complete, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.3.3.1.2-2 | Handover to different routeing area whilst in DTM / Performed on TBFs / CS release before RAU complete, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 47.3.4.1 | Handover to UTRAN while in DTM / Downlink TBF | R99 | MS supporting both UTRAN and DTM/GPRS | | C315 | | |
| 47.3.4.2 | Handover to UTRAN while in DTM / Uplink TBF | R99 | MS supporting both UTRAN and DTM/GPRS | | C315 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|---|-----------|
| 47.4.1-1 | PDP Context Activation / Performed on main DCCH and TBFs, test 1 | R99 | All DTM/GPRS capable MS | | C305 | | |
| 47.4.1-2 | PDP Context Activation / Performed on main DCCH and TBFs, test 2 | R99 | All DTM/GPRS capable MS supporting singleslot allocation | | C310 | | |
| 51.1.1.1 | RR/Paging/on PCCCH for EGPRS service/normal paging with P-TMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.1.2 | RR/Paging/on PCCCH for EGPRS service/normal paging with IMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.1.3 | RR/Paging/on PCCCH for EGPRS service/extended paging with P-TMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.1.4 | RR/Paging/on PCCCH for EGPRS service/paging reorganisation successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.2 | RR/Paging/on PCCCH for circuit-switched services/paging successful | R99 | All EGPRS MS operating in mode A or mode B | | C421 | | |
| 51.1.3 | RR/Paging/on PCCCH/paging ignored | R99 | All EGPRS MS | | C216 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.4.1 | RR/Paging/on PACCH for circuit-switched services/ paging successful | R99 | All EGPRS MS operating in mode B | | C422 | | |
| 51.1.4.2 | RR/Paging/on PACCH for circuit-switched services/ paging ignored | R99 | All EGPRS MS operating in mode A or mode B | | C421 | | |
| 51.1.5.1.1 | RR/Paging/on CCCH for EGPRS service/normal paging with P-TMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.5.1.2 | RR/Paging/on CCCH for EGPRS service/normal paging with IMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.5.1.3 | RR/Paging/on CCCH for EGPRS service/normal paging with P-TMSI ignored | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|---------------|---------------------------|--------|---|-----------|
| 51.1.5.2.1 | RR/Paging/on CCCH for EGPRS service/extended paging with P-TMSI successful | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.5.3 | RR/Paging/on CCCH for EGPRS service/paging reorganisation | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.1.6 | RR/Paging/Before T3172 expiry | R99 | All EGPRS MS | | C216 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.2.1.1 | Permission to access the network/priority classes | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.1 | Initiation of the packet access procedure/establishment causes | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.2 | Random references for two phase packet access | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.3 | Random references for one phase packet access and for Access Type "signalling" | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.4 | Initiation of the packet access procedure/timer T3146 | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.5 | Initiation of the packet access procedure/Request Reference | R99 | All EGPRS MS | | C216 | | |
| 51.2.2.6 | Two phase packet access / establishment cause | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.1 | Two-message assignment/Successful case | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.2 | Two-message assignment/Failure cases | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.3 | Packet uplink assignment/Polling bit set | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.4 | One phase packet access/Contention resolution/Successful case | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.5 | One phase packet access/Contention resolution/TLLI mismatch | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.6 | One phase packet access/Contention resolution/Counter N3104 | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|---------------|---------------------------|--------|--|-----------|
| 51.2.3.7 | One phase packet access/Contention resolution/Timer T3166 | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.8 | One phase packet access/Contention resolution/4 access repetition attempts | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE | |
| 51.2.3.9 | One phase packet access/TBF starting time | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.10 | One phase packet access/Timing Advance Index present | R99 | All EGPRS MS | | C216 | | |
| 51.2.3.11 | One phase packet access/Timing Advance Index not present | R99 | All EGPRS MS | | C216 | | |
| 51.2.4.1 | Multiblock packet access/Package Resource Request | R99 | All EGPRS MS | | C216 | | |
| 51.2.5.1 | Packet access rejection/wait indication | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 51.2.5.2 | Packet access rejection/assignment before T3142 expires | R99 | All EGPRS MS | | C216 | | |
| 51.2.5.3 | Packet access rejection / Interpretation of Extended RA i / Correct value of Extended RA i | R99 | All EGPRS MS | | C216 | | |
| 51.2.5.4 | Packet access rejection / Interpretation of Extended RA i / Extended RA i not included | R99 | All EGPRS MS | | C216 | | |
| 51.2.6.1 | Initiation of packet downlink assignment procedure/MS listens to correct CCCH block | R99 | All EGPRS MS | | C216 | | |
| 51.2.6.2 | Initiation of packet downlink assignment procedure/timer T3190 | R99 | All EGPRS MS | | C216 | | |
| 51.2.6.3 | Initiation of packet downlink assignment procedure/TBF starting time | R99 | All EGPRS MS | | C216 | | |
| 51.2.6.4 | Initiation of packet downlink assignment procedure/incorrect TFI | R99 | All EGPRS MS | | C216 | | |
| 51.3.1.1 | TBF Release/Uplink/Normal/MS initiated/Acknowledged mode | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX (where X = 1..45) | |
| 51.3.1.2 | TBF Release/Uplink/Normal/MS initiated/Unacknowledged mode | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX (where X = 1..45) | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|---|---------------------------|--------|--|-----------|
| 51.3.1.3 | TBF Release/Uplink/Normal/MS initiated/Channel coding change during countdown | R99 | All EGPRS MS | | C216 | | |
| 51.3.2.1 | TBF Release/Uplink/Normal/Network initiated/Acknowledged mode | R99 | All EGPRS MS | | C216 | | |
| 51.3.2.2 | TBF Release/Uplink/Normal/Network initiated/Unacknowledged mode | R99 | All EGPRS MS | | C216 | | |
| 51.3.3 | TBF Release/Uplink/Network initiated/Abnormal release | R99 | All EGPRS MS | | C216 | | |
| 51.3.4.1 | TBF Release/Downlink/Normal/Network initiated/Acknowledged mode | R99 | All EGPRS MS | | C216 | | |
| 51.3.4.2 | TBF Release/Downlink/Normal/Network initiated/Unacknowledged mode | R99 | All EGPRS MS | | C216 | | |
| 51.3.5.2 | PDCH Release/With TIMESLOTS_AVAILABLE | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX (where X = 1..45) | |
| 51.3.6.1 | TBF Release / Extended Uplink / Recalculation of CV before CV = 0 | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.2 | TBF Release / Extended Uplink / Recalculation of CV after CV = 0 | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.3 | TBF Release / Extended Uplink / MCS change order while CV=0 | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.4 | TBF Release / Extended Uplink / TBF reconfigure by PACKET TIMESLOT RECONFIGURE | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.5 | TBF Release / Extended Uplink / TBF reconfigure by PACKET UPLINK ASSIGNMENT | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.6 | Extended Uplink TBF / Cell Change while in Extended Uplink/ No Packet Neighbouring Cell Data | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.7 | Extended Uplink TBF / Cell Change failure while in Extended Uplink/ No Packet Neighbouring Cell Data | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 51.3.6.8 | Extended Uplink TBF / Cell Change while in Extended Uplink/ With Packet Neighbouring Cell Data | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 | | C331 | | |
| 51.3.6.9 | TBF Release / Extended Uplink / Change of RLC mode / normal release | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 and supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C338 | | |
| 51.3.6.10 | TBF Release / Extended Uplink / Change of RLC mode / abnormal release | Rel-4 | All EGPRS MS supporting GERAN FEATURE PACKAGE 1 and supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C338 | | |
| 51.5.1.1.1.1-1 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Uplink resources assigned, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 51.5.1.1.1.1-2 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Uplink resources assigned, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.5.1.1.1.2-1 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Downlink resources assigned, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 51.5.1.1.1.2-2 | Uplink TBF establishment with no reallocation of CS resources / Successful case / Downlink resources assigned, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.5.1.1.2.1-1 | Uplink TBF establishment with reallocation of CS resources / Successful case, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 51.5.1.1.2.1-2 | Uplink TBF establishment with reallocation of CS resources / Successful case, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.5.1.2.1.1-1 | Downlink TBF establishment in Ready State / Successful case, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|--|---------------------------|--------|---|-----------|
| 51.5.1.2.1.1-2 | Downlink TBF establishment in Ready State / Successful case, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.5.3.1.1-1 | Uplink TBF establishment with a downlink TBF established and no PS downlink reallocation, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 51.5.3.1.1-2 | Uplink TBF establishment with a downlink TBF established and no PS downlink reallocation, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.5.3.2.1-1 | Downlink TBF establishment with a uplink TBF established and no PS uplink reallocation, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 51.5.3.2.1-2 | Downlink TBF establishment with a uplink TBF established and no PS uplink reallocation, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 51.6.1 | Control of dynamic ARFCN mapping with PSI8 | Rel-4 | EGPRS MS supporting T GSM band or GSM 700 band or GSM 750 band | | C382 | | |
| 52.1.1.1 | Void | | | | | | |
| 52.1.1.2 | Packet Channel Request/Support of EGPRS PACKET CHANNEL REQUEST | R99 | All EGPRS MS | | C216 | | |
| 52.1.1.3 | Packet Channel Request/Response to Packet Paging/Non-RR Connection Paging | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.1.4 | Packet Channel Request/Response to Packet Paging/RR Connection Paging | R99 | All EGPRS MS | | C216 | TSPC_operation_mode_A TSPC_operation_mode_B TSPC_operation_mode_C | |
| 52.1.1.6.1 | Packet Channel Request/Access persistence control on PRACH/M+1 attempts | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.1.6.2 | Packet Channel Request/Access persistence control on PRACH/Persistence level | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.1.6.3 | Packet Channel Request/Access persistence control on PRACH/Successive Attempts | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.1.7 | Packet Channel Request / EGPRS Packet Channel Request | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|---------------|---------------------------|--------|---|-----------|
| 52.1.2.1.1.1 | Packet Uplink Assignment/Packet queuing notification/Stop sending Packet Channel Requests | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.1.2 | Packet Uplink Assignment/Packet queuing notification/Ignoring Packet Queuing Notification | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.1.3 | Packet Uplink Assignment/Packet queuing notification/Assigned PDCHs | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.1.4 | Packet Uplink Assignment/Packet queuing notification/Expiry of timer T3162 | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.2 | Packet Uplink Assignment/Response to packet polling request | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.3.1 | Packet Uplink Assignment/Packet access reject/Action during Wait_Indication | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.3.2 | Packet Uplink Assignment/Packet access reject/No respond | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.3.3 | Void | | | | | | |
| 52.1.2.1.4 | Packet Uplink Assignment/Packet Uplink Assignment handling | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.5 | Packet Uplink Assignment/One or two phase access | R99 | All EGPRS MS | | C216 | TSPC_Feat_OnOff TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.6 | Packet Uplink Assignment/Decoding of frequency parameters | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.7 | Packet Uplink Assignment/Most recently received Packet Uplink Assignment | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.1.2.1.8.1.1 | Packet Uplink Assignment/One phase access/Contention resolution/Inclusion of TLLI in RLC data blocks | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.1.2 | Packet Uplink Assignment/One phase access/Contention resolution/Counter N3104 | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.1.3 | Packet Uplink Assignment/One phase access/Contention resolution/Timer T3166 | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------------|--|---------|------------------------------------|---------------------------|--------|--------------------------|-----------|
| 52.1.2.1.8.1.4 | Packet Uplink Assignment/One phase access/Contention resolution/TLLI mismatch | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.1.5 | Packet Uplink Assignment/One phase access/Contention resolution/3 or 4 access repetition attempts | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.1.6 | Packet Uplink Assignment / One phase access / Contention resolution / Retransmission / Inclusion of TLLI in RLC data blocks after completion | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.1.7 | Packet Uplink Assignment / One phase access / Contention resolution / MCS-7 to MCS-9 / Inclusion of TLLI in both RLC data blocks | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 52.1.2.1.8.1.8 | Packet Uplink Assignment / One phase access / Contention resolution / TLLI in Packet Resource Request message retransmission | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.2.1 | Packet Uplink Assignment/One phase access/Timing Advance/TA Index present | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.8.2.2 | Packet Uplink Assignment/One phase access/Timing Advance/TA Index not present | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.9.1 | Packet Uplink Assignment/Two phase access/Packet Resource Request/RLC Octet Count | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.9.2.1 | Packet Uplink Assignment/Two phase access/Contention resolution/Expiry of timer T3168 | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE | |
| 52.1.2.1.9.2.2 | Packet Uplink Assignment/Two phase access/Contention resolution/TLLI in Packet Resource Request message | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.9.2.3 | Packet Uplink Assignment/Two phase access/Contention resolution/TLLI mismatch | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|---------------|---|---------|---|---------------------------|--------|--|-----------|
| 52.1.2.1.9.3 | Packet Uplink Assignment/Two phase access/Radio Access Capabilities | R99 | All EGPRS MS | | C216 | TSPC_Type_GSM_P_Band TSPC_Type_GSM_E_Band TSPC_Type_GSM_R_Band TSPC_Type_DCS_Band TSPC_Type_GSM_450_Band TSPC_Type_GSM_480_Band TSPC_Type_PCS_Band TSPC_Type_GSM_700_Band TSPC_Type_GSM_750_Band TSPC_Type_GSM_850_Band TSPC_Type_GSM_710_Band TSPC_Type_T_GSM_810_Band TSPC_Type_T_GSM_380_Band TSPC_Type_T_GSM_410_Band TSPC_Type_T_GSM_900_Band TSPC_GSM850_GSM1800_Interworking TSPC_GSM900_GSM1900_Interworking TSPC_GSM850_GSM900_Interworking TSPC_MS_EGPRS_RELEASE | |
| 52.1.2.1.9.4 | Packet Uplink Assignment/Two phase access/Radio Access Capabilities/ Frequency band not supported.. | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.9.5 | Packet Uplink Assignment/Two phase access/ Packet Resource Request/No respond to Packet Downlink Assignment | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.1.10.1 | Packet Uplink Assignment/Abnormal cases/Incorrect PDCH assignment | R99 | All EGPRS MS not operating in EGPRS multislots classes 18 or 29 | | C423 | TSPC_MS_EGPRS_RELEASE TSPC_Type_EGPRS_Multislot_ClassX (where X = 1..45) | |
| 52.1.2.1.10.2 | Packet Uplink Assignment/Abnormal cases/Expiry of timer T3164 | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.2.1 | Packet Downlink Assignment/Response to poll bit | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.2.2 | Packet Downlink Assignment/PCCCH monitoring | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.2.4 | Packet Downlink Assignment/Response to Packet Polling | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|--------------|--|---------|---|---------------------------|--------|--|-----------|
| 52.1.2.2.5.1 | Packet Downlink Assignment/Abnormal cases/Incorrect PDCH assignment | R99 | All EGPRS MS not operating in EGPRS multislot classes 18 and 24 to 29 | | C424 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 52.1.2.2.5.2 | Packet Downlink Assignment/Abnormal cases/Expiry of timer T3190 | R99 | All EGPRS MS | | C216 | | |
| 52.1.2.2.6 | Packet Downlink Timing Advance / TA value field not provided | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.1 | Dynamic Allocation/Uplink Transfer/Normal/Successful | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.3 | Dynamic Allocation/Uplink Transfer/Normal/Starting frame number encoding | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.4 | Dynamic Allocation/Uplink Transfer/Normal/Starting time | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.5 | Void | | | | | | |
| 52.3.1.1.6 | Dynamic Allocation/Uplink Transfer/Normal/T3180 expiry | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.7 | Dynamic Allocation/Uplink Transfer/Normal/PACCH operation | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.1.8 | Dynamic Allocation/Uplink Transfer/Normal/Two uplink timeslots | R99 | All EGPRS MS supporting EGPRS multislot classes 5, 6, 7 and 9 to 29 | | C326 | | |
| 52.3.1.2.2 | Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in acknowledged mode | R99 | All EGPRS MS | | C216 | | |
| 52.3.1.2.3 | Dynamic Allocation/Uplink Transfer/Abnormal/with cell reselection in unacknowledged mode | R99 | All EGPRS MS | | C216 | TSPC_MS_EGPRS_RELEASE TSPC_EGPRS_ENHANC | |
| 52.3.2.1.1 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Successful | R99 | All EGPRS MS | | C216 | | |
| 52.3.2.1.2 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Normal/Multislot capabilities | R99 | All EGPRS MS supporting EGPRS multislot classes 2 to 6, 8 to 10 and 19 and 24 | | C277 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|--|-----------|
| 52.3.2.2.1 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/with random access | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 52.3.2.2.2 | Dynamic Allocation/Uplink Transfer with Downlink TBF establishment/Abnormal/Continuation of normal operation | R99 | All EGPRS MS | | C216 | | |
| 52.3.3.1.1 | Dynamic Allocation/Resource reallocation/Successful/Higher throughput class or higher radio priority | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | | |
| 52.3.3.1.2 | Dynamic Allocation/Resource reallocation/Successful/Lower throughput class | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | | |
| 52.3.3.1.3 | Dynamic Allocation/Resource reallocation/Successful/Different RLC mode and higher radio priority | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | | |
| 52.3.3.2.1 | Dynamic Allocation/Resource reallocation/Abnormal/T3168 expiry | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | | |
| 52.3.3.2.2 | Dynamic Allocation/Resource reallocation/Abnormal/Invalid assignment | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | TSPC_Type_GSM_P_Band TSPC_Type_DCS_Band TSPC_Type_GSM_700_Band TSPC_Type_GSM_850_Band TSPC_Type_T_GSM_810_Band | |
| 52.3.3.3 | Dynamic Allocation/Resource reallocation/Reject | R99 | EGPRS MS supporting two PDP contexts and has a way to trigger transferring of new user data in a different PDP context while an uplink transfer is in progress | | C278 | | |
| 52.4 | Void | | | | | | |
| 52.5.5.1 | Downlink Transfer/Reestablishment/ T3192 Expiry | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|---|---------------------------|--|--------------------------|-----------|
| 52.5.5.2 | Downlink Transfer/ Reestablishment/ Packet Downlink Assignment | R99 | All EGPRS MS | | C216 | | |
| 52.5.5.3 | Downlink Transfer/ Reestablishment/ Invalid Frequency Parameters IE | R99 | All EGPRS MS | | C216 | | |
| 52.6.1 | EGPRS Packet Access for signalling / EGPRS Packet Channel Request not supported / CCCH case | R99 | For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS | | For R99: C316 For Rel-4 and onwards: C216 | | |
| 52.6.2 | EGPRS Packet Access for signalling / EGPRS Packet Channel Request supported / CCCH case | R99 | For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS | | For R99: C316 For Rel-4 and onwards: C216 | | |
| 52.6.3 | EGPRS Packet Access for signalling / EGPRS Packet Channel Request not supported / PCCCH case | R99 | For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS | | For R99: C316 For Rel-4 and onwards: C216 | | |
| 52.6.4 | EGPRS Packet Access for signalling / EGPRS Packet Channel Request supported / PCCCH case | R99 | For R99: All EGPRS MS that supports the access type 'signalling' in EGPRS PACKET CHANNEL REQUEST For Rel-4 and onwards: All EGPRS MS | | For R99: C316 For Rel-4 and onwards: C216 | | |
| 52.8.1.1 | One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution / Inclusion of TLLI in RLC data blocks | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|---------------|---------------------------|--------|--------------------------|-----------|
| 52.8.1.2 | One phase access/ PBCCH present / CONTENTION_RESOLUTION_TLLI Contention resolution / Counter N3104 | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.3 | One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution / Timer T3166 | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.4 | One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI/Contention resolution / TLLI mismatch | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.5 | One phase access/PBCCH present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution /4 access repetition attempts | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.6 | One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution / Inclusion of TLLI in RLC data blocks | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.7 | One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI/Contention resolution / Counter N3104 | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.8 | One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution / Timer T3166 | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.9 | One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI/ Contention resolution / TLLI mismatch | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|---|---------|--|---------------------------|--------|--|-----------|
| 52.8.1.10 | One phase access/ PBCCH not present/ CONTENTION_RESOLUTION_TLLI/Contention resolution / 4 access repetition attempts | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.11 | One phase access/PBCCH present/CONTENTION_RESOLUTION_TLLI/ Contention resolution / Successful Resource Reallocation | R99 | All EGPRS MS | | C216 | | |
| 52.8.1.12 | One phase access/PBCCH absent/CONTENTION_RESOLUTION_TLLI/ Contention resolution / Successful Resource Reallocation | R99 | All EGPRS MS | | C216 | | |
| 52.9.2.1.1 | Extended Dynamic Allocation / Uplink Transfer / Normal / Successful | R99 | All EGPRS MS supporting Extended Dynamic Allocation and EGPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45) | | C357 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 52.9.2.1.2 | Extended Dynamic Allocation / Uplink Transfer / Normal / USF_GRANULARITY = 4 blocks | R99 | All EGPRS MS supporting Extended Dynamic Allocation and EGPRS multislot classes: 3, 5, 6, 7, 9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C357 | | |
| 52.9.2.1.4 | Extended Dynamic Allocation / Uplink Transfer / Normal / PACCH operation in downlink | R99 | All EGPRS MS supporting Extended Dynamic Allocation and EGPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45) | | C357 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 52.9.2.1.5 | Extended Dynamic Allocation / Uplink Transfer / Normal / Polling for EPDAN | R99 | All EGPRS MS supporting Extended Dynamic Allocation and EGPRS multislot classes: 3,5,6,7,9 to 29, 31 to 34, 36 to 39, 41 to 45) | | C357 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.1.1 | Acknowledged Mode/ Uplink TBF/ Send State Variable V(S) | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.2 | Acknowledged Mode/ Uplink TBF/ Acknowledge State Variable V(A) | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.3 | Acknowledged Mode/ Uplink TBF/ Window Size/ Default Value | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|------------------------------------|---------------------------|--------|--|-----------|
| 53.1.1.4 | Acknowledged Mode/ Uplink TBF/ Window Size/ Assigned Value | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.1.5 | Acknowledged mode/ Uplink TBF/ Invalid Negative Acknowledgement | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.6 | Acknowledged Mode/ Uplink TBF/ Countdown Value | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.7 | Acknowledged Mode/ Uplink TBF/ Interpretation of Receive Block Bitmap | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.8 | Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission/ Default Mode | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.9 | Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '1' | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.10 | Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '0'/ PENDING_ACK Blocks | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.11 | Acknowledged Mode/ Uplink TBF/ Pre-emptive Transmission Bit Set to '0'/ Negative Acknowledgement | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.12 | Acknowledged Mode/ Uplink TBF/ Retransmission/ Split RLC Data Block | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.13 | Acknowledged Mode/ Uplink TBF/ Calculation of BSN2 | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.14 | Acknowledged Mode/ Uplink TBF/ Verification of Coding Schemes | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_8PSK_uplink | |
| 53.1.1.15 | Acknowledged Mode/ Uplink TBF/ Recalculation of CV on MCS change | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.16 | Acknowledged Mode/ Uplink TBF/ Retransmission/ Padding in the Data Field | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.17 | Acknowledged Mode/ Uplink TBF/ Retransmission/ Puncturing Scheme Cycle | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_8PSK_uplink | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|--|---------------------------|--------|--|-----------|
| 53.1.1.18 | EGPRS Acknowledged mode/Uplink TBF/Link Adaptation Procedure for retransmission | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_8PSK_uplink | |
| 53.1.1.19 | EGPRS Acknowledged mode/Uplink TBF/Link Adaptation Procedure for initial transmission | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_8PSK_uplink | |
| 53.1.1.20 | Acknowledged Mode/ Uplink TBF/ Retransmission/ MCS Selection without Re-segmentation | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_8PSK_uplink | |
| 53.1.1.21 | Acknowledged Mode/ Uplink TBF/ Initial Puncturing Scheme After MCS Switching | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.22 | Acknowledged Mode/ Uplink TBF/ Recalculation of CV on TBC change | R99 | EGPRS MS capable of 8PSK in Uplink | | C238 | | |
| 53.1.1.23 | Acknowledged Mode/ Uplink TBF/ Interpretation of Compressed Bitmap | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.24 | Acknowledged Mode/ Uplink TBF/ Interpretation of PBSN | R99 | All EGPRS MS | | C216 | | |
| 53.1.1.25 | Acknowledged Mode/ Uplink TBF/ TBF Reallocation/Window Size | R99 | All EGPRS MS supporting EGPRS multislot classes 5,6,7, 9 to 29, 31 to 34, 36 to 39, 41 to 45 | | C425 | | |
| 53.1.2.1 | Acknowledged Mode/ Downlink TBF/ Receive State Variable V(R) | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.2 | Acknowledged Mode/ Downlink TBF/ Receive Window State Variable V(Q) | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.3 | Acknowledged Mode/ Downlink TBF/ Window Size/ Default Value | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.4 | Acknowledged Mode/ Downlink TBF/ Window Size/ Assigned Value | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.5 | Acknowledged Mode/ Downlink TBF/ BOW | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.6 | Acknowledged Mode/ Downlink TBF/ EOW | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.7 | Acknowledged Mode/ Downlink TBF/ Measurement Report | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.8 | Acknowledged Mode/ Downlink TBF/ Generation of Bitmap | R99 | All EGPRS MS | | C216 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|--|---------|---|---------------------------|--------|--|-----------|
| 53.1.2.9 | Acknowledged Mode/ Downlink TBF/ Interpretation of BSN2 | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.10 | Acknowledged Mode/ Downlink TBF/ Split RLC Data Block | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.11 | Acknowledged Mode/ Downlink TBF/ First Partial Bitmap and Next Partial Bitmap | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.12 | Acknowledged Mode/ Downlink TBF/ Decoding of Coding Schemes | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.14 | Acknowledged Mode/ Downlink TBF/ Received Bitmap/ Compressed | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.15 | Acknowledged Mode/ Downlink TBF/ Received Bitmap/ Uncompressed | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.16 | Acknowledged Mode/ Downlink TBF/ Received Block Bitmap/ Compressed Bitmap Starting Colour Code | R99 | All EGPRS MS | | C216 | | |
| 53.1.2.17 | Acknowledged Mode/ Downlink TBF/ Received Block Bitmap/ Terminating Code and Make-up Code | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.18 | Acknowledged Mode/ Downlink TBF/ Retransmission/Padding | R99 | All EGPRS MS | | C216 | TSPC_Type_EGPRS_Multislot_ClassX where X = 1..45 | |
| 53.1.2.19 | Acknowledged Mode/ Downlink TBF/ Retransmission/Padding | R99 | All EGPRS MS supporting EGPRS Multislot classes higher than 1 | | C277 | | |
| 53.2.1.1 | Unacknowledged Mode/ Uplink TBF/ Stall Indicator | R99 | All EGPRS MS | | C216 | | |
| 53.2.1.2 | Unacknowledged Mode/ Uplink TBF/ RBB and SSN | R99 | All EGPRS MS | | C216 | | |
| 53.2.2.1 | Unacknowledged Mode/ Downlink TBF/ V(R) and V(Q) | R99 | All EGPRS MS | | C216 | | |
| 57.1.3-1 | Intra frequency reallocation of CS resources / DTM Assignment Command, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 57.1.3-2 | Intra frequency reallocation of CS resources / DTM Assignment Command, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|---|---------------------------|--------|---|-----------|
| 57.1.4-1 | Inter frequency reallocation of CS resources / DTM Assignment Command, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 57.1.4-2 | Inter frequency reallocation of CS resources / DTM Assignment Command, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 57.2.1-1 | Network originating CS release, test 1 | R99 | All DTM/EGPRS capable MS | | C342 | | |
| 57.2.1-2 | Network originating CS release, test 2 | R99 | All DTM/EGPRS capable MS supporting singleslot allocation | | C343 | | |
| 60.1 | Inter system handover to UTRAN/From GSM/Speech/Success | R99 | MS supporting both GSM and UTRAN | | C285 | TSPC_AddInfo_Full_rate_version_1; TSPC_AddInfo_Half_rate_version_1; TSPC_AddInfo_Full_rate_version_2; TSPC_AddInfo_Full_rate_version_3 | |
| 60.2a | Inter system handover to UTRAN/From GSM/Data/Same data rate/Success | R99 | MS supporting both GSM and UTRAN | | C430 | TSPC_Streaming_14_4_CSRAB_3_4_SRAB | |
| 60.2b | Inter system handover to UTRAN/From GSM/Data/Same data rate/Success | R99 | MS supporting both GSM and UTRAN | | C286 | TSPC_Streaming_14_4_CSRAB_3_4_SRAB; TSPC_Streaming_28_8_CSRAB_3_4_SRAB; TSPC_Streaming_57_6_CSRAB_3_4_SRAB; TSPC_Type_HSCSD_Multislot | |
| 60.3a | Inter system handover to UTRAN/From GSM/ Data/Same data rate upgrading/Success | R99 | MS supporting both GSM and UTRAN | | C431 | TSPC_STREAMING_28_8_CSRAB_3_4_SRAB; TSPC_Streaming_57_6_CSRAB_3_4_SRAB; | |
| 60.3b | Inter system handover to UTRAN/From GSM/ Data/Same data rate upgrading/Success | R99 | MS supporting both GSM and UTRAN | | C287 | TSPC_STREAMING_28_8_CSRAB_3_4_SRAB; TSPC_Streaming_57_6_CSRAB_3_4_SRAB; TSPC_Type_HSCSD_Multislot | |
| 60.4 | Inter system handover to UTRAN/From GSM/Speech/Establishment/Success | R99 | MS supporting both GSM and UTRAN | | C288 | | |
| 60.5 | Inter system handover to UTRAN/From GSM/Speech/Blind HO/Success | R99 | MS supporting both GSM and UTRAN | | C288 | | |
| 60.6 | Inter system handover to UTRAN/From GSM/Speech/Failure | R99 | MS supporting both GSM and UTRAN | | C288 | | |
| 60.7 | Inter system handover to UTRAN/From GSM/Failure/Cause: Frequency not implemented | R99 | MS supporting both GSM and UTRAN | | C289 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 60.8 | Inter system handover to UTRAN/From GSM/Failure/Cause: UTRAN preconfiguration unknown | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 60.9 | Inter system handover to UTRAN/From GSM/Failure/Cause: Protocol Error | R99 | MS supporting both GSM and UTRAN | | C289 | | |
| 60.10 | Inter system handover to UTRAN/From GSM/Integrity Protection Activation | R99 | MS supporting both GSM and UTRAN | | C285 | | |
| 70.2.1 | Network Induced E-OTD emergency call test on an SDCCH, Idle, no IMSI | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.2.2 | Positioning/RR/Classmark Interrogation tests | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.2.3 | Network Induced E-OTD emergency call test on an SDCCH | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.2.4 | E-OTD test for NI-LR on the TCH | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.1.1 | MO_LR Basic Self Location Request In Idle Mode (Normal Case) | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.1.2 | MO_LR Basic Self Location Request In Dedicated Mode (Normal Case) | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.2 | MO_LR Transfer to 3 rd Party | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.3 | MOLR_Autonomous Location | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.4.1 | MO_LR Positioning Measurement / Protocol Error | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.4.2 | MO_LR Positioning Measurement / Location Error | R98 | MSs supporting MS-Assisted EOTD and do not support LCS MS-Assisted GPS | | C318 | | |
| 70.3.4.3 | MO_LR Positioning Measurement / Multiple RRLP REQUEST with same Reference Number | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.3.4.4 | MO_LR Positioning Measurement / Multiple RRLP REQUEST with different Reference Number | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|---|---------------------------|--------|--------------------------|-----------|
| 70.3.4.5 | MO_LR Positioning Measurement / RR Management Commands | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.4.1 | E-OTD test for MT-LR Location Notification | R98 | MSs supporting MS-Assisted EOTD | | C281 | | |
| 70.4.2.1 | E-OTD test for MT-LR Privacy Options – Location Allowed. | R98 | MSs supporting MS-Assisted EOTD and Privacy Options | | C304 | | |
| 70.4.2.2 | E-OTD test for MT-LR Privacy Options – Location Not Allowed. | R98 | MSs supporting MS-Assisted EOTD and Privacy Options | | C304 | | |
| 70.6.1 | E-OTD Sensitivity Performance Tests for GMSK | R98 | All MSs supporting MS-Assisted EOTD for GMSK | | C313 | | |
| 70.6.2 | E-OTD Interference performance test for GMSK | R98 | All MSs supporting MS-Assisted EOTD for GMSK | | C313 | | |
| 70.6.3 | E-OTD Multipath performance test for GMSK | R98 | All MSs supporting MS-Assisted EOTD for GMSK | | C313 | | |
| 70.6.4 | E-OTD Interference performance test for 8PSK | R99 | All MSs supporting MS-Assisted EOTD for 8PSK | | C314 | | |
| 70.6.5 | E-OTD Multipath performance test for 8PSK | R98 | All MSs supporting MS-Assisted EOTD for 8PSK | | C314 | | |
| 70.6.6 | E-OTD Sensitivity Performance Tests for 8PSK | R99 | All MSs supporting MS-Assisted EOTD for 8PSK | | C314 | | |
| 70.7.2.1 | A-GPS LCS Classmark Interrogation test case for MS-Based GPS | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.7.2.2 | A-GPS LCS Classmark Interrogation test case for MS-Assisted GPS | R98 | All MSs supporting LCS MS-Assisted GPS | | C284 | | |
| 70.7.4.1 | Network Induced Location Request Emergency Call on TCH for mobiles supporting MS-Based GPS | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.7.4.2 | Network Induced Location Request Emergency Call on TCH for mobiles supporting MS-Assisted GPS | R98 | All MSs supporting LCS MS-Assisted GPS | | C284 | | |
| 70.7.4.3 | Network Induced Location Request Emergency Call on TCH, no IMSI for mobiles supporting MS-Based GPS | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.7.4.4 | Network Induced Location Request Emergency Call on TCH, no IMSI for mobiles supporting MS-Assisted GPS | R98 | All MSs supporting LCS MS-Assisted GPS | | C284 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|------------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 70.8.1 | Basic Self Location | R98 | All MSs supporting LCS MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.2 | Basic Self Location in Dedicated Mode | R98 | All MSs supporting LCS MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.3 | Transfer to 3 rd Party | R98 | All MSs supporting LCS MS-Assisted GPS and Support of MO-LR request for transfer to 3rd party | | C447 | | |
| 70.8.4.1 | MO-LR Positioning Measurement / Protocol Error | R98 | All MSs supporting MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.4.2.1 | MO-LR Positioning Measurement / Location Error: Requested Method not Supported | R98 | All MSs supporting MS-Assisted GPS and not supporting MS-Assisted EOTD and Support of MO-LR request for a position estimate | | C320 | | |
| 70.8.4.2.2 | MO-LR Positioning Measurement / Location Error: GPS Assistance Data Missing | R98 | All MSs supporting MS-Assisted GPS and supporting a method for resetting stored A-GPS assistance data and Support of MO-LR request for a position estimate | | C402 | | |
| 70.8.4.3 | MO-LR Positioning Measurement / Multiple RRLP Requests with Same Reference Number | R98 | All MSs supporting MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.4.4 | MO-LR Positioning Measurement / Multiple RRLP Requests with Different Reference Number | R98 | All MSs supporting MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.4.5 | MO-LR Positioning Measurement / RR Management Commands | R98 | All MSs supporting MS-Assisted GPS and Support of MO-LR request for a position estimate | | C445 | | |
| 70.8.5.1 | MO_LR Basic Self Location Request in Idle Mode (Normal Case) | R98 | All MSs supporting LCS MS-Based GPS and Support of MO-LR request for a assistance data | | C465 | | |
| 70.8.5.2 | MO_LR Basic Self Location Request in Dedicated Mode (Normal Case) | R98 | All MSs supporting LCS MS-Based GPS and Support of MO-LR request for a assistance data | | C465 | | |
| 70.8.5.3 | MO_LR Basic Self Location Request in Idle Mode (Alternative Case) | R98 | All MSs supporting LCS MS-Based GPS and Support of MO-LR request for a position estimate | | C444 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 70.8.5.4 | MO_LR Basic Self Location Request in Dedicated Mode (Alternative Case) | R98 | All MSs supporting LCS MS-Based GPS and Support of MO-LR request for a position estimate | | C444 | | |
| 70.8.6 | MO-LR Transfer to 3 rd Party for MS-Based A-GPS | R98 | All MSs supporting LCS MS-Based GPS and Support of MO-LR request for transfer to 3rd party | | C446 | | |
| 70.9.1.1 | MT-LR Location Notification for mobiles supporting MS-Based GPS | R98 | All MSs supporting LCS MS-Based GPS and MT-LR | | C460 | | |
| 70.9.1.2 | MT-LR Location Notification for mobiles supporting MS-Assisted GPS | R98 | All MSs supporting LCS MS-Assisted GPS and MT-LR | | C461 | | |
| 70.9.2.1 | MT-LR Privacy Options/Verification- Location Allowed If No Response for MS-Based GPS | R98 | MSs supporting LCS MS-Based GPS and Privacy Options and MT-LR | | C302 | | |
| 70.9.2.2 | MT-LR Privacy Options/Verification- Location Allowed If No Response for MS-Assisted GPS | R98 | MSs supporting LCS MS-Assisted GPS and Privacy Options and MT-LR | | C303 | | |
| 70.9.3.1 | MT-LR Privacy Options/Verification- Location Not Allowed If No Response for MS-Based GPS | R98 | MSs supporting LCS MS-Based GPS and Privacy Options and MT-LR | | C302 | | |
| 70.9.3.2 | MT-LR Privacy Options/Verification- Location Not Allowed If No Response for MS-Assisted GPS | R98 | MSs supporting LCS MS-Assisted GPS and Privacy Options and MT-LR | | C303 | | |
| 70.9.4.1 | RRLP Error Handling for MS-Based A-GPS / RRLP Protocol Error | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.9.4.2 | RRLP Error Handling for MS-Based A-GPS / RRLP Location Error: Requested Method Not Supported | R98 | All MSs supporting MS-Based GPS and not supporting MS-Assisted EOTD | | C365 | | |
| 70.9.4.3 | RRLP Error Handling for MS-Based A-GPS / RRLP Location Error: GPS Assistance Data Missing | R98 | All MSs supporting LCS MS-Based GPS and supporting a method for resetting stored A-GPS assistance data | | C403 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|--|---------------------------|--------|--------------------------|-----------|
| 70.9.4.4 | RRLP Error Handling for MS-Based A-GPS / Multiple RRLP Requests with same Reference Number | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.9.4.5 | RRLP Error Handling for MS-Based A-GPS / Multiple RRLP Requests with different Reference Number | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.9.4.6 | RRLP Error Handling for MS-Based A-GPS / RR management commands | R98 | All MSs supporting LCS MS-Based GPS | | C283 | | |
| 70.10.2.1 | Network Induced Location Request Emergency Call on TCH Radio Channel | R98 | All MSs supporting LCS conventional GPS and not supporting MS-based Assisted-GPS | | C328 | | |
| 70.11.5.1 | Sensitivity Coarse Time Assistance | Rel-7 | All MSs supporting MS-Based A-GPS or MS-Assisted A-GPS | | C398 | | |
| 70.11.5.2 | Sensitivity Fine Time Assistance | Rel-7 | All MSs supporting MS-Based A-GPS or MS-Assisted A-GPS and Fine Time Assistance | | C399 | | |
| 70.11.6 | Nominal Accuracy | Rel-7 | All MSs supporting MS-Based A-GPS or MS-Assisted A-GPS | | C398 | | |
| 70.11.7 | Dynamic Range | Rel-7 | All MSs supporting MS-Based A-GPS or MS-Assisted A-GPS | | C398 | | |
| 70.11.8 | Multi-Path scenario | Rel-7 | All MSs supporting MS-Based A-GPS or MS-Assisted A-GPS | | C398 | | |
| 81.1.1.1 | Discovery procedure, MS holds the IP address of the provisioning SEGW and FQDN of the provisioning GANC and default GANC belong to the same SEGW | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.1.1.2 | Discovery procedure, MS holds the IP address of the provisioning SEGW and FQDN of the provisioning GANC and default GANC belong to different SEGW | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.1.1.3 | Discovery procedure, MS is not provisioned | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.1.2.1 | Discovery procedure, Discovery Rejected, Net congestion | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.1.2.2 | Discovery procedure, Discovery Rejected, IMSI not allowed | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--------------------------------------|---------------------------|--------|--------------------------|-----------|
| 81.1.2.3 | Void | | | | | | |
| 81.1.3.1 | Discovery Procedure, TU3901/3903 expiration | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.1.3.2 | Void | | | | | | |
| 81.1.3.3 | Void | | | | | | |
| 81.1.3.4 | Void | | | | | | |
| 81.1.3.5 | Void | | | | | | |
| 81.1.3.6 | Void | | | | | | |
| 81.1.3.7 | 81.1.3.7 SEGW certificate checking, the MS holds the 'invalid' FQDN of the provisioning SEGW | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.1.1 | Registration procedure, MS in GSM Coverage, Serving GANC for CGI known | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.1.2 | Registration Procedure, MS in GSM Coverage, Serving GANC for CGI Not Known MS not in GSM Coverage, Serving GANC for AP Known | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.1.3 | Void | | | | | | |
| 81.2.1.4 | Registration procedure, MS holds the IP address to the Serving SEGW and FQDN to the serving GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.1.5 | Registration procedure, MS holds the FQDN to the serving SEGW and IP address to the serving GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.2.1 | Registration procedure Redirected, Not possible to reuse secure connection | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.2.2 | Registration procedure, Redirected, current and received GANC belong to the same SEGW, IP address matches | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.2.3 | Registration procedure, Redirected, current and received GANC belong to the same SEGW, FQDN matches | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--------------------------------------|---------------------------|--------|--------------------------|-----------|
| 81.2.3.1 | Registration Procedure, Registration rejected, Network Congestion | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.3.2 | Registration Procedure, Registration rejected, AP not allowed | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.3.3 | Registration Procedure, Registration rejected, Location not allowed | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.3.4 | Registration Procedure, Registration rejected, IMSI not allowed | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.3.5 | Void | | | | | | |
| 81.2.3.6 | Registration Procedure, Registration rejected, invalid GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.3.7 | Registration Procedure, Registration rejected, Geo location not known | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.4.1 | Registration Procedure, TU3904/3905 expiry | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.4.2 | Registration Procedure, Registration rejected Network congestion | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.4.3 | Void | | | | | | |
| 81.2.4.4 | Void | | | | | | |
| 81.2.4.5 | Void | | | | | | |
| 81.2.4.6 | Void | | | | | | |
| 81.2.4.7 | Void | | | | | | |
| 81.2.5.1 | Registration Procedure, registration update, Rejected | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.5.2 | Registration Procedure, registration update, Redirection | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.1 | Registration Procedure, Deregister, Network Congestion, MS in State GA-CSR DEDICATED | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.2 | Registration Procedure, Deregister, AP not allowed, MS in State GA-RC REGISTERED | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|--------------------------------------|---------------------------|--------|--------------------------|-----------|
| 81.2.6.3 | Registration Procedure, Deregister, Location not allowed, MS in State GA-CSR IDLE | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.4 | Registration Procedure, Deregister, IMSI not allowed | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.5 | Registration Procedure, Deregister, Unspecified | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.6 | Registration Procedure, Deregister, Unspecified, Persistent Fault, Default GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.7 | Registration Procedure, Deregister, Invalid GANC, Serving GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.8 | Registration Procedure, Deregister, Geo Location Not Known | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.2.6.9 | Registration Procedure, Deregister, MS Initiated | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.3.1.1 | TCP Reset, Successful re-establishment, MS in State GA-CSR DEDICATED | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.3.1.2 | TCP Reset, Unsuccessful re-establishment, MS in State GA-CSR IDLE | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.3.2.1 | IPsec Tunnel failure, MS in GA-CSR IDLE | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 81.3.2.2 | TCP Failure, MS in State GA-CSR DEDICATED | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.1.1.1 | GA-CSR connection establishment, Upper Layer Message Transmission and GA-CRS connection release by GANC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.1.2.1 | GA-CSR REQUEST rejected | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.1.2.2 | MS receives GA-CSR REQUEST ACCEPT message after TU3908 expiry | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.2.1.1 | Void | | | | | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|--|---------|--|---------------------------|--------|--------------------------|-----------|
| 82.2.2.1 | MS receives GA-CSR DOWNLINK DIRECT TRANSFER message when not in GA-CSR-DEDICATED state | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.3.1.1 | Paging for CS domain | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.3.2.1 | Void | | | | | | |
| 82.3.2.2 | MS receives GA-CSR PAGING REQUEST when TU3908 is active | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.3.2.3 | MS receives GA-CSR PAGING REQUEST when in GA-CSR DEDICATED state | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.3.2.4 | MS receives GA-CSR PAGING REQUEST when in GA-RC REGISTERED state | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.4.1.1 | Traffic Channel assignment and Release | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.4.2.1 | MS fails to establish the traffic channel | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.5.1.1 | Void | | | | | | |
| 82.5.1.2 | Void | | | | | | |
| 82.6.1.1 | Classmark Indication, Initiation of Classmark Interrogation by MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.7.1.1 | Handover from GERAN to GAN | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.7.1.2 | Handover from GERAN to GAN signalling case | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.7.1.3 | Handover from UTRAN to GAN | Rel-6 | Applicable to MS supporting UTRAN to GAN CS handover | | C428 | | |
| 82.7.2.1 | Void | | | | | | |
| 82.7.2.2 | TU3920 expires during handover procedure | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.8.1.1 | Handover from GAN to GERAN | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.8.1.2 | Handover from GAN to UTRAN | Rel-6 | Applicable to MS supporting GAN to UTRAN CS handover | | C429 | | |
| 82.8.2.1 | Connection establishment fails on GERAN cell | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.8.2.2 | Handover command with non-supported configuration | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|-----------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 82.9.1.1 | Ciphering Configuration Procedure | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.9.1.2 | Void | | | | | | |
| 82.9.2.1 | Ciphering Configuration Procedure, Invalid Ciphering Mode Command | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.10.1.1 | Channel mode modify / successful case | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 82.10.2.1 | Channel mode modify indicates non-supported mode | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.1.1 | MS initiated GA-PSR TC activation | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.2.1 | GA-PSR TC activation collision | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.2.2 | UNC rejects GA-PSR TC activation | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.3.1 | Processing of the GA-PSR TC activation request by the MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.4.1 | Void | | | | | | |
| 83.1.4.2 | MS rejects GA-PSR TC activation when GPRS service is suspended | Rel-6 | Applicable to all MSs supporting GAN and not supporting operation mode A and not supporting DTM | | C404 | | |
| 83.1.4.3 | MS receives GA-PSR TC activation request while GA-PSR TC active | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.5.1 | GA-PSR TC deactivation initiation by the MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.6.1 | Uplink user data transfer while GA-PSR TC deactivation is in progress | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.6.2 | Downlink user data transfer while GA-PSR TC deactivation is in progress | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.6.3 | Unexpected GA-PSR-DEACTIVATE-UTC-ACK response | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.6.4 | Unexpected GA-PSR-ACTIVATE-UTC-REQ | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.1.7.1 | GA-PSR TC deactivation initiation by the UNC | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.2.1.1 | MS initiates uplink GPRS user data transfer | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |

| Clause | Title | Release | Applicability | Applicability Limitations | Status | Specific PICS Statements | Supported |
|----------|---|---------|---|---------------------------|--------|--------------------------|-----------|
| 83.2.1.2 | Void | | | | | | |
| 83.2.2.1 | Void | | | | | | |
| 83.2.2.2 | Void | | | | | | |
| 83.3.1.1 | PS paging request processed by the MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.4.1.1 | GPRS suspension initiation by the MS | Rel-6 | Applicable to all MSs supporting GAN and not supporting operation mode A and not supporting DTM | | C404 | | |
| 83.5.1.1 | Initiation of the downlink flow control and processing of the TU4003 timer expiry by the MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.6.1.1 | Processing of the uplink flow control request by the MS | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 83.6.2.1 | GA-PSR TC is not active | Rel-6 | Applicable to all MSs supporting GAN | | C359 | | |
| 90.1.1 | Transmission of CTM Bearer Code – Mobile Originated TTY Call | R99 | All MS supporting TTY text telephony services and MO circuit switched basic service | | C407 | | |
| 90.1.2 | Transmission of CTM Bearer Code – Mobile Terminated TTY Call | R99 | All MS supporting TTY text telephony services and MT circuit switched basic service | | C408 | | |

Table B.1a: Applicability of tests - Conditions definitions

| | | |
|-----|--|--|
| C1 | IF NOT A.25/50 THEN A ELSE N/A | -- NOT TSPC_AddInfo_ApplAlwaysRun |
| C2 | IF A.25/1 THEN A ELSE N/A | -- TSPC_AddInfo_HalfRate |
| C3 | IF A.5/14 AND A.5/13 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_AoCI |
| C4 | IF A.5/14 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC |
| C5 | IF A.25/11 THEN A ELSE N/A | -- TSPC_AddInfo_AsyncNonTransData |
| C6 | IF A.25/10 THEN A ELSE N/A | -- TSPC_AddInfo_AsyncData |
| C7 | IF A.2/26 THEN A ELSE N/A | -- TSPC_Feat_Autocall |
| C8 | IF A.2/26 AND A.25/56 THEN A ELSE N/A | -- TSPC_Feat_Autocall AND TSPC_AddInfo_AutocallBnoGreaterM |
| C9 | IF A.2/22 THEN A ELSE N/A | -- TSPC_Feat_BO |
| C10 | IF A.25/17 THEN A ELSE N/A | -- TSPC_AddInfo_fullRate48 |
| C11 | IF A.25/5 THEN A ELSE N/A | -- TSPC_AddInfo_FullRateData |
| C12 | IF A.25/6 THEN A ELSE N/A | -- TSPC_AddInfo_HalfRateData |
| C13 | IF A.25/3 THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_1 |
| C14 | IF A.25/41 OR A.25/42 THEN A ELSE N/A | -- TSPC_AddInfo_ID1 OR TSPC_AddInfo_Plugin |
| C15 | IF A.25/43 THEN A ELSE N/A | -- TSPC_AddInfo_DisablePin |
| C16 | IF (A.2/21 THEN A ELSE N/A | -- TSPC_Feat_FND |
| C17 | IF A.25/44 THEN A ELSE N/A | -- TSPC_AddInfo_Pin2 |
| C18 | IF A.25/59 THEN A ELSE N/A | -- TSPC_AddInfo_MT2orOther |
| C19 | IF A.2/41 AND A.2/58 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_non_zero_NON_DRX_TIMER |
| C20 | void | |
| C21 | IF A.25/45 THEN A ELSE N/A | -- TSPC_AddInfo_Pin2Feature |
| C22 | IF A.25/7 THEN A ELSE N/A | -- TSPC_AddInfo_NonTransData |
| C23 | IF A.25/8 THEN A ELSE N/A | -- TSPC_AddInfo_TransData |
| C24 | IF A.25/2 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_1 |
| C25 | IF A.25/8 AND A.25/58 THEN A ELSE N/A | -- TSPC_AddInfo_TransData AND TSPC_AddInfo_MT2 |
| C26 | IF A.3/6 THEN A ELSE N/A | -- TSPC_Serv_TS61 |
| C27 | IF A.3/7 THEN A ELSE N/A | -- TSPC_Serv_TS62 |
| C28 | IF A.3/7 AND NOT A.3/6 THEN A ELSE N/A | -- TSPC_Serv_TS62 AND NOT TSPC_Serv_TS61 |
| C29 | IF A.3/7 OR A.3/6 THEN A ELSE N/A | -- TSPC_Serv_TS62 OR TSPC_Serv_TS61 |
| C30 | IF (A.3/7 OR A.3/6) AND A.25/28 THEN A ELSE N/A | -- (TSPC_Serv_TS62 OR TSPC_Serv_TS61) AND TSPC_AddInfo_FaxErrCor |
| C31 | IF A.25/19 THEN A ELSE N/A | -- TSPC_AddInfo_MTsvc |
| C32 | IF (A.25/19 OR A.25/20) AND NOT A.5/14 THEN A ELSE N/A | -- (TSPC_AddInfo_MTsvc OR TSPC_AddInfo_MOsvc) AND NOT TSPC_Serv_SS_AoCC |
| C33 | IF A.5/14 AND A.25/20 AND (NOT A.5/10) THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_AddInfo_MOsvc AND (NOT TSPC_Serv_SS_HOLD) |
| C34 | IF A.5/14 AND A.5/10 AND A.25/20 AND (NOT A.5/11) THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_HOLD AND TSPC_AddInfo_MOsvc AND (NOT TSPC_Serv_SS_MPTY) |
| C35 | IF A.25/20 AND NOT A.2/21 THEN A ELSE N/A | -- TSPC_AddInfo_MOsvc AND NOT TSPC_Feat_FND |
| C36 | IF A.25/20 THEN A ELSE N/A | -- TSPC_AddInfo_MOsvc |
| C37 | IF A.25/22 THEN A ELSE N/A | -- TSPC_AddInfo_SvcOnTCH |
| C38 | IF A.25/23 THEN A ELSE N/A | -- TSPC_AddInfo_DualRate |
| C39 | IF A.25/4 THEN A ELSE N/A | -- TSPC_AddInfo_DataSvc |
| C40 | IF A.25/30 THEN A ELSE N/A | -- TSPC_AddInfo_NonCallSS |
| C41 | IF A.3/4 THEN A ELSE N/A | -- TSPC_Serv_TS22 |
| C42 | IF A.3/1 OR A.3/2 THEN A ELSE N/A | -- TSPC_Serv_TS11 OR TSPC_Serv_TS12 |
| C43 | IF A.25/26 THEN A ELSE N/A | -- TSPC_AddInfo_CCprotocol_oneBC |
| C47 | IF A.25/26 AND A.2/17 THEN A ELSE N/A | -- TSPC_AddInfo_CCprotocol_oneBC AND TSPC_Feat_A51 |
| C48 | IF A.25/26 AND A.25/55 THEN A ELSE N/A | -- TSPC_AddInfo_CCprotocol_oneBC AND TSPC_AddInfo_RFamp |
| C50 | IF A.25/26 AND A.25/3 THEN A ELSE N/A | -- TSPC_AddInfo_CCprotocol_oneBC AND TSPC_AddInfo_Half_rate_version_1 |

| | | |
|-----|--|---|
| C51 | IF A.25/40 THEN A ELSE N/A | -- TSPC_Addinfo_SIMRmv |
| C52 | IF A.25/2 OR A.25/3 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1 |
| C53 | IF A.25/4 AND NOT A.25/2 THEN A ELSE N/A | -- TSPC_AddInfo_DataSvc AND NOT TSPC_AddInfo_Full_rate_version_1 |
| C55 | IF (NOT A.25/27) AND (NOT A.25/51) AND A.25/19 THEN A ELSE N/A | -- (NOT TSPC_Addinfo_EmgOnly) AND (NOT TSPC_Addinfo_ImmConn) AND TSPC_Addinfo_MTsvc |
| C56 | IF A.3/1 OR A.3/2 OR A.3/6 OR A.4/20 THEN A ELSE N/A | -- TSPC_Serv_TS11 OR TSPC_Serv_TS12 OR TSPC_Serv_TS61 OR TSPC_Serv_BS61 |
| C58 | IF A.3/6 OR A.4/20 OR A.4/21 THEN A ELSE N/A | -- TSPC_Serv_TS61 OR TSPC_Serv_BS61 OR TSPC_Serv_BS81 |
| C59 | IF A.5/13 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCI |
| C62 | IF A.5/16 OR A.5/18 OR A.5/17 OR A.5/19 OR A.5/15 THEN A ELSE N/A | -- TSPC_Serv_SS_BOIC OR TSPC_Serv_SS_BAIC OR TSPC_Serv_SS_BOICexHC OR TSPC_Serv_SS_BICRoam OR TSPC_Serv_SS_BAOC |
| C64 | IF A.5/7 OR A.5/5 THEN A ELSE N/A | -- TSPC_Serv_SS_CFNRY OR TSPC_Serv_SS_CFU |
| C65 | IF A.5/6 OR A.5/5 OR A.5/8 OR A.5/7 THEN A ELSE N/A | -- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFU OR TSPC_Serv_SS_CFNRC OR TSPC_Serv_SS_CFNRY |
| C66 | IF A.5/6 OR A.5/8 OR A.5/7 THEN A ELSE N/A | -- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFNRC OR TSPC_Serv_SS_CFNRY |
| C67 | IF A.5/6 THEN A ELSE N/A | -- TSPC_Serv_SS_CFB |
| C68 | IF A.5/19 AND A.5/15 THEN A ELSE N/A | -- TSPC_Serv_SS_BICRoam AND TSPC_Serv_SS_BAOC |
| C69 | IF A.5/14 AND A.25/40 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_Addinfo_SIMRmv |
| C70 | IF A.5/14 AND A.5/10 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_HOLD |
| C71 | IF A.5/14 AND A.5/11 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND TSPC_Serv_SS_MPTY |
| C72 | IF A.3/3 AND A.25/26 THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Addinfo_CCprotocol_oneBC |
| C73 | IF A.3/4 AND A.25/26 THEN A ELSE N/A | -- TSPC_Serv_TS22 AND TSPC_Addinfo_CCprotocol_oneBC |
| C74 | IF A.3/3 AND (A.25/36) THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Addinfo_StoreRcvSMSSIM |
| C76 | IF A.1/6 THEN A ELSE N/A | -- Type_MB_Simul |
| C78 | IF A.1/6 AND A.25/26 THEN A ELSE N/A | -- Type_MB_Simul AND TSPC_AddInfo_CC |
| C79 | IF A.25/26 AND A.25/61 THEN A ELSE N/A | -- TSPC_Addinfo_CCprotocol_oneBC AND TSPC_Addinfo_PseudoSynch |
| C80 | IF A.25/62 AND (NOT A.25/130) THEN A ELSE N/A | -- TSPC_AddInfo_5V AND (NOT TSPC_Card_Appl) |
| C81 | IF A.25/63 AND (NOT A.25/130) THEN A ELSE N/A | -- TSPC_AddInfo_3V AND (NOT TSPC_Card_Appl) |
| C82 | IF A.25/64 AND (NOT A.25/130) THEN A ELSE N/A | -- TSPC_AddInfo_5V3V AND (NOT TSPC_Card_Appl) |
| C83 | IF A.25/65 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_2 |
| C84 | IF A.25/20 AND A.25/65 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_2 AND TSPC_Addinfo_MOsvc |
| C85 | IF A.25/19 AND A.25/65 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_2 AND TSPC_Addinfo_MTsvc |
| C86 | IF A.1/15 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot |
| C87 | IF A.1/15 AND A.25/26 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot AND TSPC_Addinfo_CCprotocol_oneBC |
| C88 | IF A.1/15 AND A.25/20 THEN A ELSE N/A | -- Type_HSCSD_Multislot AND TSPC_Addinfo_Mosvc |
| C89 | IF A.1/15 AND A.25/19 THEN A ELSE N/A | -- Type_HSCSD_Multislot AND TSPC_Addinfo_MTsvc |
| C90 | IF A.1/15 AND NOT A.25/50 THEN A ELSE N/A | -- TSPC_Type_GPRS_Multislot_operation AND NOT TSPC_AddInfo_AppiAlwaysRun |

| | | |
|------|--|---|
| C91 | IF A.25/95 AND (NOT A.25/130) THEN A ELSE N/A | -- TSPC_AddInfo_1_8V AND (NOT TSPC_Card_Appl) |
| C92 | IF A.25/104 THEN A ELSE N/A | -- TSPC_AddInfo_IntegrAntenna |
| C93 | IF A.1/15 AND A.25/60 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_PermAntenna |
| C94 | IF A.1/15 AND A.25/104 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_IntegrAntenna |
| C95 | IF A.1/51 AND (A.25/60 OR A.25/148) AND A.1/57 THEN A ELSE N/A | -- TSPC_Type_GPRS_Multislot_operation AND (TSPC_AddInfo_PermAntenna OR TSPC_AddInfo_TempAntenna) AND TSPC_Type_GPRS_Multislot_uplink |
| C96 | IF A.1/51 AND A.25/104 AND A.1/57 THEN A ELSE N/A | -- TSPC_Type_GPRS_Multislot_operation AND TSPC_AddInfo_IntegrAntenna AND TSPC_Type_GPRS_Multislot_uplink |
| C97 | IF A.1/52 AND (A.25/60 OR A.25/148) THEN A ELSE N/A | -- TSPC_Type_EGPRS_8PSK_uplink AND (TSPC_AddInfo_PermAntenna OR TSPC_AddInfo_TempAntenna) |
| C98 | IF A.1/52 AND A.25/104 THEN A ELSE N/A | -- Type_EGPRS_8PSK_uplink AND TSPC_AddInfo_IntegrAntenna |
| C99 | IF (NOT A.1/3) AND A.25/60 THEN A ELSE N/A | -- NOT TSPC_Type_GSM_R_Band AND TSPC_AddInfo_PermAntenna |
| C100 | IF (NOT A.1/3) AND (A.25/2 OR A.25/3) THEN A ELSE N/A | -- NOT TSPC_Type_GSM_R_Band AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) |
| C101 | IF A.25/96 AND (NOT A.25/130) THEN A ELSE N/A | -- TSPC_AddInfo_1_8V3V AND (NOT TSPC_Card_Appl) |
| C102 | IF NOT A.1/3 THEN A ELSE N/A | -- NOT Type_GSM_R_Band |
| C103 | IF A.1/3 THEN A ELSE N/A | -- TSPC_Type_GSM_R_Band |
| C104 | IF A.25/66b OR A.25/68 THEN A ELSE N/A | -- TSPC_Addinfo_VBS_Listening OR TSPC_Addinfo_VGCS_Listening |
| C105 | IF (A.25/66b OR A.25/68) AND A.25/71 AND A.25/80 AND A.25/81 AND A.25/82 THEN A ELSE N/A | -- (TSPC_Addinfo_VBS_Listening OR TSPC_Addinfo_VGCS_Listening) AND TSPC_Addinfo_NCH_ReducedMonitor AND TSPC_Addinfo_NCH_Monit_Rev AND TSPC_Addinfo_NCH_Monit_Tra AND TSPC_Addinfo_NCH_Monit_Ded |
| C106 | IF A.25/67 OR A.25/69 THEN A ELSE N/A | -- TSPC_Addinfo_VBS_Originating OR TSPC_Addinfo_VGCS_Talking |
| C107 | IF A.25/67 OR A.25/70 THEN A ELSE N/A | -- TSPC_Addinfo_VBS_Originating OR TSPC_Addinfo_VGCS_Originating |
| C108 | IF A.25/69 THEN A ELSE N/A | -- TSPC_Addinfo_VGCS_Talking |
| C109 | IF A.25/70 THEN A ELSE N/A | -- TSPC_Addinfo_VGCS_Originating |
| C110 | IF A.25/67 THEN A ELSE N/A | -- TSPC_Addinfo_VBS_Originating |
| C111 | IF A.5/21 AND A.3/1 THEN A ELSE N/A | -- TSPC_Serv_eMLPP AND TSPC_Serv_TS11 |
| C112 | IF A.5/21 AND A.5/10 AND A.5/9 AND A.3/1 THEN A ELSE N/A | -- TSPC_Serv_eMLPP AND TSPC_Serv_SS_HOLD AND TSPC_Serv_SS_CW AND TSPC_Serv_TS11 |
| C113 | IF (A.25/66b OR A.25/68) AND A.5/21 THEN A ELSE N/A | -- (TSPC_Addinfo_VBS_Listening OR TSPC_Addinfo_VGCS_Listening) AND TSPC_Serv_eMLPP |
| C114 | IF A.5/21 THEN A ELSE N/A | -- TSPC_Serv_eMLPP |
| C115 | IF A.25/60 AND A.1/3 THEN A ELSE N/A | -- TSPC_AddInfo_PermAntenna AND TSPC_Type_GSM_R_Band |
| C116 | IF (A.25/2 OR A.25/3) AND A.1/3 THEN A ELSE N/A | -- (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) AND TSPC_Type_GSM_R_Band |
| C119 | IF A.1/3 AND NOT (A.25/2 OR A.25/3) THEN A ELSE N/A | -- TSPC_Type_GSM_R_Band AND NOT (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) |
| C120 | IF A.25/7 AND A.25/66a THEN A ELSE N/A | -- TSPC_AddInfo_NonTransData AND TSPC_AddInfo_NonDefaultRlpParam |
| C121 | IF A.25/57 THEN A ELSE N/A | -- TSPC_AddInfo_SpeechHandset |
| C122 | IF A.25/58 THEN A ELSE N/A | -- TSPC_AddInfo_MT2 |
| C123 | IF (A.1/2 OR A.1/3) AND A.25/26 THEN A ELSE N/A | -- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND TSPC_Addinfo_CCprotocol_oneBC |

| | | |
|------|--|--|
| C124 | IF A.1/2 OR A.1/3 THEN A ELSE N/A | -- TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band |
| C125 | IF (A.1/2 OR A.1/3) AND (A.3/1 OR A.3/6 OR A.3/7) THEN A ELSE N/A | -- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND (TSPC_Serv_TS11 OR TSPC_Serv_TS61 OR TSPC_Serv_TS62) |
| C126 | IF (A.1/2 OR A.1/3) AND A.3/1 THEN A ELSE N/A | -- (TSPC_Type_GSM_E_Band OR TSPC_Type_GSM_R_Band) AND TSPC_Serv_TS11 |
| C127 | IF A.1/6 AND (A.3/1 OR A.3/7) THEN A ELSE N/A | -- TSPC_Type_MB_Simul AND (TSPC_Serv_TS11 OR TSPC_Serv_TS62) |
| C128 | IF A.25/68 THEN A ELSE N/A | -- TSPC_Addinfo_VGCS_Listening |
| C129 | IF (A.1/4 OR A.1/6) THEN A ELSE N/A | -- (TSPC_Type_DCS_Band OR TSPC_Type_MB_Simul) |
| C130 | IF A.25/19 AND A.25/54 THEN A ELSE N/A | -- TSPC_Addinfo_MTsvc AND TSPC_Addinfo_RefusalCall |
| C131 | IF A.3/1 OR A.3/7 THEN A ELSE N/A | -- TSPC_Serv_TS11 OR TSPC_Serv_TS62 |
| C132 | void | |
| C133 | IF A.5/6 OR A.5/8 THEN A ELSE N/A | -- TSPC_Serv_SS_CFB OR TSPC_Serv_SS_CFNry |
| C134 | IF A.5/16 THEN A ELSE N/A | -- TSPC_Serv_SS_BAOC |
| C135 | IF A.5/18 THEN A ELSE N/A | -- TSPC_Serv_SS_BAIC |
| C136 | IF A.5/17 THEN A ELSE N/A | -- TSPC_Serv_SS_BOICexHC |
| C137 | IF A.5/17 OR A.5/18 THEN A ELSE N/A | -- TSPC_Serv_SS_BOICexHC OR TSPC_Serv_SS_BAIC |
| C138 | IF A.5/16 OR A.5/19 THEN A ELSE N/A | -- TSPC_Serv_SS_BOIC OR TSPC_Serv_SS_BICRoam |
| C139 | IF A.5/20 THEN A ELSE N/A | -- TSPC_Serv_SS_unstruct |
| C140 | IF A.5/20 AND A.25/26 THEN A ELSE N/A | -- TSPC_Serv_SS_unstruct AND TSPC_Addinfo_CCprotocol_oneBC |
| C141 | IF A.3/3 AND A.3/4 AND A.25/35 THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Serv_TS22 AND TSPC_Addinfo_SMSStatusRepCap |
| C142 | IF A.3/3 AND A.25/34 THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Addinfo_DisprcvSMS |
| C143 | IF A.3/3 AND A.25/34 AND (A.25/36 OR A.25/37) THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Addinfo_DisprcvSMS AND (TSPC_Addinfo_StoreRcvSMSSIM OR TSPC_Addinfo_StoreRcvSMSME) |
| C144 | IF A.3/3 AND A.25/33 AND A.25/34 THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Addinfo_ReplaceSMS AND TSPC_Addinfo_DisprcvSMS |
| C145 | IF A.3/3 AND A.3/4 AND A.25/32 AND A.25/34 THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_Serv_TS22 AND TSPC_Addinfo_ReplyProc AND TSPC_Addinfo_DisprcvSMS |
| C190 | IF A.2/1 THEN A ELSE N/A | -- TSPC_Feat_DCN |
| C191 | IF A.5/28 THEN A ELSE N/A | -- TSPC_Serv_SS_FollowMe |
| C192 | IF A.5/25 THEN A ELSE N/A | -- TSPC_Serv_SS_ImpUUS1 |
| C193 | IF A.5/24 THEN A ELSE N/A | -- TSPC_Serv_SS_ECT |
| C194 | IF A.5/11 THEN A ELSE N/A | -- TSPC_Serv_SS_MPTY |
| C195 | IF A.5/10 THEN A ELSE N/A | -- TSPC_Serv_SS_HOLD |
| C196 | IF A.5/9 THEN A ELSE N/A | -- TSPC_Serv_SS_CW |
| C197 | IF A.5/1 THEN A ELSE N/A | -- TSPC_Serv_SS_CLIP |
| C198 | IF A.5/2 THEN A ELSE N/A | -- TSPC_Serv_SS_CLIR |
| C199 | IF A.5/3 THEN A ELSE N/A | -- TSPC_Serv_SS_COLP |
| C200 | IF A.5/4 THEN A ELSE N/A | -- TSPC_Serv_SS_COLR |
| C201 | IF A.2/11 THEN A ELSE N/A | -- TSPC_Feat_ServInd |
| C202 | IF A.2/14 THEN A ELSE N/A | -- TSPC_Feat_SIM |
| C203 | IF A.25/79 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_3 |
| C204 | IF A.1/57 THEN A ELSE N/A | -- TSPC_Type_GPRS_Multislot_uplink |
| C206 | IF A.2/39 THEN A ELSE N/A | -- TSPC_Feat_audible_tone |
| C207 | IF A.2/38 THEN A ELSE N/A | -- TSPC_SoLSA |
| C208 | Void | |
| C209 | Void | |
| C210 | IF A.2/41 AND A.25/26 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Addinfo_CCprotocol_oneBC |

| | | |
|------|--|---|
| C211 | IF A.2/42 AND NOT A.1/18 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_Type_GPRS_Multislot_operation |
| C213 | IF A.1/58 THEN A ELSE N/A | -- TSPC_COMPACT |
| C214 | IF A.2/53 THEN A ELSE N/A | -- TSPC_ECSD |
| C215 | IF A.2/41 THEN A ELSE N/A | -- TSPC_GPRS |
| C216 | IF A.2/42 THEN A ELSE N/A | -- TSPC_EGPRS |
| C220 | IF A.25/109 AND A.25/97 THEN A ELSE N/A | -- TSPC_AddInfo_MultSMS AND TSPC_AddInfo_MultSMsameRR |
| C221 | IF A.2/41 AND A.2/48 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_operation_mode_B |
| C222 | Void | |
| C223 | IF A.2/41 AND A.25/84 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Addinfo_mor1PDP CA |
| C224 | IF A.2/41 AND A.25/85 AND A.25/128 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Addinfo_mor1PDP CA_SAPI AND TSPC_AddInfo_NewULDataInNewPDP_while_UL TransferInOldPDP |
| C225 | IF A.2/41 AND A.25/88 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Addinfo_N_req_PDP_CA |
| C226 | IF A.2/41 AND A.2/47 OR A.2/48 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_operation_mode_A OR TSPC_operation_mode_B |
| C227 | IF A.2/41 AND NOT (A.1/67 OR A.1/68 OR A.1/70 OR A.1/74) THEN A ELSE N/A | -- TSPC_GPRS AND NOT (TSPC_Type_GPRS_Multislot_Class1 OR TSPC_Type_GPRS_Multislot_Class2 OR TSPC_Type_GPRS_Multislot_Class4 OR TSPC_Type_GPRS_Multislot_Class8) |
| C228 | IF A.2/41 AND (A.1/69 OR A.1/70 OR A.1/71 OR A.1/72 OR A.1/73 OR A.1/74 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class4 OR...OR TSPC_Type_GPRS_Multislot_Class29) |
| C229 | IF A.2/41 AND (A.1/85 OR A.1/90) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class19 OR TSPC_Type_GPRS_Multislot_Class24) |
| C230 | IF A.2/41 AND (A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29) |
| C231 | IF A.2/41 AND A.1/67 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Type_GPRS_Multislot_Class1 |
| C232 | IF A.2/41 AND (A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class19 OR...OR TSPC_Type_GPRS_Multislot_Class29) |
| C233 | IF A.2/41 AND (A.1/69 OR A.1/71 OR A.1/72 OR A.1/73 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class7 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29) |
| C234 | IF A.2/41 AND (A.1/68 OR A.1/69 OR A.1/70 OR A.1/71 OR A.1/72 OR A.1/74 OR A.1/75 OR A.1/76 OR A.1/85 OR A.1/90) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class2 OR TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class4 OR TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class8 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR TSPC_Type_GPRS_Multislot_Class19 OR TSPC_Type_GPRS_Multislot_Class24) |
| C235 | Void | |

| | | |
|------|--|--|
| C236 | IF (A.2/41 AND (A.2/47 OR A.2/48)) AND NOT A.25/90 THEN A ELSE N/A | -- (TSPC_GPRS AND TSPC_operation_mode_A OR TSPC_operation_mode_B) AND NOT TSPC_AddInfo_on_auto_GPRS_AP |
| C237 | IF A.2/41 AND NOT A.25/88 THEN A ELSE N/A | -- TSPC_GPRS AND NOT TSPC_AddInfo_N_req_PDP_CA |
| C238 | IF A.1/52 THEN A ELSE N/A | -- TSPC_Type_EGPRS_8PSK_uplink Multislot_operation |
| C248 | IF A.2/41 AND A.25/89 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_min_QoS |
| C251 | IF A.2/67 THEN A ELSE N/A | TSPC_MT_SMS_over_GPRS |
| C252 | IF A.2/67 AND A.25/35 THEN A ELSE N/A | -- TSPC_MT_SMS_over_GPRS AND TSPC_AddInfo_SMSStatusRepCap |
| C253 | IF (A.2/41 AND A.2/50) THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_SMS_over_GPRS |
| C254 | IF (A.2/41 AND A.2/50 AND A.25/116) THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_SMS_over_GPRS AND TSPC_SMS_MO_CONCATENATION |
| C255 | IF (A.2/41 AND A.2/50 AND A.25/117) THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_SMS_over_GPRS AND TSPC_SMS_MT_CONCATENATION |
| C256 | Void | |
| C257 | Void | |
| C258 | Void | |
| C259 | Void | |
| C260 | Void | |
| C261 | Void | |
| C262 | Void | |
| C263 | Void | |
| C264 | Void | |
| C265 | Void | |
| C266 | Void | |
| C267 | Void | |
| C268 | Void | |
| C269 | Void | |
| C270 | Void | |
| C271 | Void | |
| C272 | IF A.25/97 THEN A ELSE N/A | -- TSPC_AddInfo_MultSMsameRR |
| C273 | IF A.1/56 THEN A ELSE N/A | -- TSPC_Type_UTRAN |
| C274 | IF A.2/41 AND A.25/105 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_Comb_DP_no_pwr_off |
| C275 | IF A.2/41 AND A.25/106 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_Usr_non_GPRS_DP |
| C276 | IF A.2/42 AND (A.1/98 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR...OR TSPC_Type_EGPRS_Multislot_Class29) |
| C277 | IF A.2/42 AND (A.1/97 OR A.1/98 OR A.1/99 OR A.1/100 OR A.1/101 OR A.1/103 OR A.1/104 OR A.1/105 OR A.1/114 OR A.1/119) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class2 OR TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class4 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class8 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR TSPC_Type_EGPRS_Multislot_Class19 OR TSPC_Type_EGPRS_Multislot_Class24) |
| C278 | IF A.2/42 AND A.25/84 AND A.25/128 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_AddInfo_mor1PDP CA AND TSPC_AddInfo_NewULDataInNewPDP_while_UL TransferInOldPDP |
| C279 | Void | |
| C280 | IF A.25/57 THEN A ELSE N/A | -- TSPC_AddInfo_SpeechHandset |
| C281 | IF A.2/57 THEN A ELSE N/A | -- TSPC_EOTD_ASSIST |

| | | |
|------|---|--|
| C282 | IF A.2/41 AND A.25/88 AND A.25/110 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_N_req_PDP_CA AND TSPC_Cell_Resel |
| C283 | IF A.2/59 THEN A ELSE N/A | -- TSPC_A-GPS_Based |
| C284 | IF A.2/60 THEN A ELSE N/A | -- TSPC_A-GPS_Assist |
| C285 | IF (A.1/56 AND A.27/1 AND (A.25/2 OR A.25/3 OR A.25/65 OR A.25/79) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1 OR TSPC_AddInfo_Full_rate_version_2 OR TSPC_AddInfo_Full_rate_version_3) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND OR TSPC_TYPE_PCS_BAND OR TSPC_TYPE_GSM_850_BAND OR TSPC_TYPE_GSM_710_BAND OR TSPC_TYPE_GSM_750_BAND OR TSPC_TYPE_T_GSM_810_BAND) |
| C286 | IF (A.1/56 AND A.27/2 AND (((A.1/15 OR A.25/5) AND A.25/72) OR (A.27/3 AND (A.1/15 OR A.25/5)) OR (A.27/4 AND A.25/4)) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_Streaming_14_4_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateData) AND TSPC_AddInfo_144Data) OR (TSPC_Streaming_28_8_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateData) OR (TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_AddInfo_DataSvc) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND OR TSPC_TYPE_PCS_BAND OR TSPC_TYPE_GSM_850_BAND OR TSPC_TYPE_GSM_710_BAND OR TSPC_TYPE_GSM_750_BAND OR TSPC_TYPE_T_GSM_810_BAND) |
| C287 | IF (A.1/56 AND ((A.27/3 AND (A.1/15 OR A.25/5) AND A.25/72) OR (A.27/4 AND (A.1/15 OR A.25/5) AND A.25/72) OR (A.27/4 AND (A.1/15 OR A.25/5))) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND (TSPC_STREAMING_28_8_CSRAB_3_4_SRAB AND (TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateData) AND TSPC_AddInfo_144Data) OR ((TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateData) AND TSPC_AddInfo_144Data) OR (TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_Type_HSCSD_Multislot OR TSPC_AddInfo_FullRateData) AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND OR TSPC_TYPE_PCS_BAND OR TSPC_TYPE_GSM_850_BAND OR TSPC_TYPE_GSM_710_BAND OR TSPC_TYPE_GSM_750_BAND OR TSPC_TYPE_T_GSM_810_BAND) |

| | | |
|------|---|---|
| C288 | IF (A.1/56 AND A.27/1 AND A.25/2 AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND TSPC_AddInfo_Full_rate_version_1 AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND OR TSPC_TYPE_PCS_BAND OR TSPC_TYPE_GSM_850_BAND OR TSPC_TYPE_GSM_710_BAND OR TSPC_TYPE_GSM_750_BAND OR TSPC_TYPE_T_GSM_810_BAND) |
| C289 | IF (A.1/56 AND A.27/1 AND A.25/2 AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/53 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_Conversational_12_2_CSRAB_3_4_SRAB AND TSPC_AddInfo_Full_rate_version_1 AND (TSPC_TYPE_GSM_P_BAND OR TSPC_TYPE_GSM_E_BAND OR TSPC_TYPE_DCS_BAND OR TSPC_TYPE_GSM_450_BAND OR TSPC_TYPE_GSM_480_BAND OR TSPC_TYPE_PCS_BAND OR TSPC_TYPE_GSM_700_BAND OR TSPC_TYPE_GSM_850_BAND OR TSPC_TYPE_GSM_710_BAND OR TSPC_TYPE_GSM_750_BAND OR TSPC_TYPE_T_GSM_810_BAND) |
| C290 | IF A.3/3 THEN A ELSE N/A | -- TSPC_Serv_TS21 |
| C300 | IF A.3/5 THEN A ELSE N/A | -- TSPC_Serv_TS23 |
| C301 | Void | |
| C302 | IF A.2/59 AND A.2/61 AND A.5/39 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_PRIVACY AND TSPC_MTLR |
| C303 | IF A.2/60 AND A.2/61 AND A.5/39 THEN A ELSE N/A | -- TSPC_A-GPS_Assist AND TSPC_PRIVACY AND TSPC_MTLR |
| C304 | IF A.2/57 AND A.2/61 THEN A ELSE N/A | -- TSPC_EOTD AND TSPC_PRIVACY |
| C305 | IF A.2/62 THEN A ELSE N/A | -- TSPC_DTM_GPRS |
| C306 | IF A.1/59 THEN A ELSE N/A | -- TSPC_DTM_GPRS_Multislot_Class_1 |
| C307 | IF A.1/60 THEN A ELSE N/A | -- TSPC_DTM_GPRS_Multislot_Class_5 |
| C308 | IF A.1/61 OR A.1/60 OR A.1/148 THEN A ELSE N/A | -- TSPC_DTM_GPRS_Multislot_Class_9 OR TSPC_DTM_GPRS_Multislot_Class_5 OR TSPC_DTM_GPRS_Multislot_Class_11 |
| C309 | void | |
| C310 | IF A.1/62 THEN A ELSE N/A | -- TSPC_DTM_GPRS_Singleslot_Allocation |
| C311 | IF A.2/62 AND NOT A.1/62 THEN A ELSE N/A | -- TSPC_DTM_GPRS AND NOT TSPC_DTM_GPRS_Singleslot_Allocation |
| C312 | void | |
| C313 | IF A.2/63 THEN A ELSE N/A | -- TSPC_EOTD_ASSIST_AND TSPC_PERF_GMSK |
| C314 | IF A.2/64 THEN A ELSE N/A | -- TSPC_EOTD_ASSIST AND TSPC_PERF_8PSK |
| C315 | IF A.2/62 AND A.1/56 THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_DTM_GPRS |
| C316 | IF A.2/42 AND A.2/65 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_EGPRS_ENHANC |
| C317 | IF A.2/41 AND A.2/15 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Feat_OnOff |
| C318 | IF (A.2/57 AND NOT A.2/60) THEN A ELSE N/A | -- TSPC_EOTD_ASSIST AND NOT TSPC_A- GPS_Assist |
| C319 | IF A.25/112 THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_3 |
| C320 | IF (A.2/60 AND NOT A.2/57) AND A.5/37 THEN A ELSE N/A | -- (TSPC_A-GPS_Assist AND NOT TSPC_EOTD_ASSIST) AND TSPC_MOLR_POS |
| C321 | IF A.25/79 AND A.25/113 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_3 AND TSPC_AMR_LoopBack |
| C322 | IF A.2/41 AND A.2/72 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 |
| C323 | IF (A.25/23) AND A.25/26 THEN A ELSE N/A | -- TSPC_Addinfo_DualRate AND TSPC_Addinfo_CCprotocol_oneBC |
| C324 | IF A.2/41 AND A.1/56 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Type_UTRAN |

| | | |
|------|--|--|
| C325 | IF A.2/41 AND (A.1/71 OR A.1/72 OR A.1/73 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class7 OR TSPC_Type_GPRS_Multislot_Class9 OR TSPC_Type_GPRS_Multislot_Class10 OR...OR TSPC_Type_GPRS_Multislot_Class29) |
| C326 | IF A.2/42 AND (A.1/100 OR A.1/101 OR A.1/102 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR TSPC_Type_EGPRS_Multislot_Class10 OR...OR TSPC_Type_EGPRS_Multislot_Class29) |
| C327 | void | |
| C328 | IF A.1/65 AND NOT A.2/59 THEN A ELSE N/A | -- TSPC_Conv-GPS AND NOT TSPC_A-GPS_Based |
| C329 | void | |
| C330 | void | |
| C331 | IF A.2/42 AND A.2/72 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 |
| C332 | IF A.2/41 AND A.25/85 AND A.25/115 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_mor1PDP CA_SAPI AND TSPC_SEC_PDP_CONTEXT |
| C333 | IF A.25/112 AND A.25/113 THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_3 AND TSPC_AMR_LoopBack |
| C334 | IF A.2/41 AND A.25/118 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_NITZ |
| C335 | IF A.25/119 OR A.25/146 OR A.25/147 THEN A ELSE N/A | -- TSPC_NITZ_DST OR TSPC_NITZ_Time_Zone OR TSPC_NITZ_Universal_Time |
| C336 | IF A.2/41 AND A.25/87 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_GPRS_Header_Compr |
| C337 | IF A.2/41 AND A.2/72 AND A.25/84 AND A.25/128 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 AND TSPC_AddInfo_mor1PDP_CA AND TSPC_AddInfo_NewULDataInNewPDP_while_UL TransferInOldPDP |
| C338 | IF A.2/42 AND A.2/72 AND A.25/84 AND A.25/128 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 AND TSPC_AddInfo_mor1PDP_CA AND TSPC_AddInfo_NewULDataInNewPDP_while_UL TransferInOldPDP |
| C339 | IF A.25/26 AND A.25/2 THEN A ELSE N/A | -- TSPC_AddInfo_CC AND TSPC_AddInfo_Full_rate_version_1 |
| C340 | IF A.5/14 AND (A.25/2 OR A.25/3) THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) |
| C341 | IF A.5/13 AND (A.25/2 OR A.25/3) THEN A ELSE N/A | -- TSPC_Serv_SS_AoCI AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) |
| C342 | IF A.2/69 THEN A ELSE N/A | -- TSPC_DTM_EGPRS |
| C343 | IF A.2/69 AND A.1/62 THEN A ELSE N/A | -- TSPC_DTM_EGPRS AND TSPC DTM_GPRS_Singleslot_Allocation |
| C344 | IF A.25/79 AND A.25/113 AND (A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_3 AND TSPC_AMR_LoopBack AND (TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C345 | void | |
| C346 | Void | |
| C347 | Void | |

| | | |
|------|--|--|
| C348 | IF A.2/41 AND A.2/70 AND (A.1/69 OR A.1/71 OR A.1/72 OR A.1/73 OR A.1/75 OR A.1/76 OR A.1/77 OR A.1/78 OR A.1/79 OR A.1/80 OR A.1/81 OR A.1/82 OR A.1/83 OR A.1/84 OR A.1/85 OR A.1/86 OR A.1/87 OR A.1/88 OR A.1/89 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95 OR A.1/150 OR A.1/151 OR A.1/152 OR A.1/153 OR A.1/155 OR A.1/156 OR A.1/157 OR A.1/158 OR A.1/160 OR A.1/161 OR A.1/162 OR A.1/163 OR A.1/164) THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_ExtendedDynamic_Allocation AND (TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class5 OR TSPC_Type_GPRS_Multislot_Class6 OR TSPC_Type_GPRS_Multislot_Class7 OR TSPC_Type_GPRS_Multislot_Class9 OR...OR TSPC_Type_GPRS_Multislot_Class29 OR TSPC_Type_GPRS_Multislot_Class31 OR...OR TSPC_Type_GPRS_Multislot_Class34 OR TSPC_Type_GPRS_Multislot_Class36 OR...OR TSPC_Type_GPRS_Multislot_Class39 OR TSPC_Type_GPRS_Multislot_Class41 OR...OR TSPC_Type_GPRS_Multislot_Class45) |
| C349 | IF (A.2/41) AND (A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C350 | IF A.25/2 AND (A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_1 AND (TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C351 | IF A.25/112 AND A.25/113 AND (A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_3 AND TSPC_AMR_LoopBack AND (TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C352 | voidq | |
| C353 | IF A.2/62 AND NOT A.1/62 THEN A ELSE N/A | -- TSPC_DTM_GPRS AND NOT TSPC_DTM_GPRS_Singleslot_Allocation |
| C354 | IF A.2/62 AND A.1/6 THEN A ELSE N/A | -- TSPC_DTM_GPRS AND Type_MB_Simul |
| C355 | IF A.1/62 AND A.1/6 THEN A ELSE N/A | -- TSPC_DTM_GPRS_Singleslot_Allocation AND Type_MB_Simul |
| C356 | IF NOT A.25/130 THEN A ELSE N/A | -- (NOT TSPC_Card_Appl) |
| C357 | IF A.2/42 AND A.2/70 AND (A.1/98 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124 OR A.1/166 OR A.1/167 OR A.1/168 OR A.1/169 OR A.1/171 OR A.1/172 OR A.1/173 OR A.1/174 OR A.1/176 OR A.1/177 OR A.1/178 OR A.1/179 OR A.1/180) THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_ExtendedDynamic_Allocation AND (TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR...OR TSPC_Type_EGPRS_Multislot_Class29 OR TSPC_Type_EGPRS_Multislot_Class31 OR...OR TSPC_Type_EGPRS_Multislot_Class34 OR TSPC_Type_EGPRS_Multislot_Class36 OR...OR TSPC_Type_EGPRS_Multislot_Class39 OR TSPC_Type_EGPRS_Multislot_Class41 OR...OR TSPC_Type_EGPRS_Multislot_Class45) |
| C358 | IF A.25/131 THEN A ELSE N/A | -- TSPC_O-TCH_AHS |
| C359 | IF A.2/71 THEN A ELSE N/A | -- TSPC_GAN |
| C360 | void | |
| C361 | void | |
| C362 | IF A.25/79 AND NOT (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_full_rate_version_3 AND NOT (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C363 | IF A.25/112 AND NOT (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_half_rate_version_3 AND NOT (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C364 | IF A.2/42 AND (A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C365 | IF A.2/59 AND NOT A.2/57 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND NOT TSPC_EOTD_ASSIST |
| C366 | IF A.25/133 THEN A ELSE N/A | TSPC_O-TCH_WFS |
| C367 | void | |
| C368 | IF A.5/14 AND (A.25/2 OR A.25/3) AND A.25/40 THEN A ELSE N/A | -- TSPC_Serv_SS_AoCC AND (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) AND TSPC_AddInfo_SIMRmv |
| C369 | IF A.25/131 AND A.25/113 THEN A ELSE N/A | -- TSPC_O-TCH_AHS AND TSPC_AMR_LoopBack |

| | | |
|------|---|--|
| C370 | IF (A.5/16 OR A.5/18 OR A.5/17 OR A.5/19 OR A.5/15) AND NOT A.25/134 THEN A ELSE N/A | -- (TSPC_Serv_SS_BOIC OR TSPC_Serv_SS_BAIC OR TSPC_Serv_SS_BOICexHC OR TSPC_Serv_SS_BICRoam OR TSPC_Serv_SS_BAOC) AND NOT TSPC_Verification_correct_new_password |
| C371 | void | |
| C372 | IF A.25/5 THEN A ELSE N/A | -- TSPC_AddInfo_FullRateData |
| C373 | void | |
| C374 | void | |
| C375 | IF NOT A.1/3 THEN A ELSE N/A | -- NOT Type_GSM_R_Band |
| C376 | IF A.1/15 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot |
| C377 | IF A.1/15 AND (A.25/60 OR A.25/148) THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot AND (TSPC_AddInfo_PermAntenna OR TSPC_AddInfo_TempAntenna) |
| C378 | IF A.1/15 AND A.25/104 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot AND TSPC_AddInfo_IntegrAntenna |
| C379 | IF A.2/41 AND NOT A.2/42 THEN A ELSE N/A | -- TSPC_GPRS AND NOT TSPC_EGPRS |
| C380 | IF A.1/15 THEN A ELSE N/A | -- TSPC_Type_HSCSD_Multislot |
| C381 | IF A.1/183 OR A.1/182 OR A.1/54 OR A.1/185 OR A.1/186 OR A.1/187 THEN A ELSE N/A | -- TSPC_Type_T_GSM_810_Band OR TSPC_Type_GSM_710_Band OR TSPC_Type_GSM_750_Band OR TSPC_Type_T_GSM_380_Band OR TSPC_Type_T_GSM_410_Band OR TSPC_Type_T_GSM_900_Band |
| C382 | IF (A.1/183 OR A.1/182 OR A.1/54 OR A.1/185 OR A.1/186 OR A.1/187) AND A.2/42 THEN A ELSE N/A | -- (TSPC_Type_T_GSM_810_Band OR TSPC_Type_GSM_710_Band OR TSPC_Type_GSM_750_Band OR TSPC_Type_T_GSM_380_Band OR TSPC_Type_T_GSM_410_Band OR TSPC_Type_T_GSM_900_Band) AND TSPC_EGPRS |
| C383 | IF A.25/136 THEN A ELSE N/A | TSPC_O-TCH_WHS |
| C384 | IF (A.25/1) AND A.25/26 THEN A ELSE N/A | -- TSPC_AddInfo_HalfRate AND TSPC_AddInfo_CCprotocol_oneBC |
| C385 | IF A.1/57 THEN A ELSE N/A | -- TSPC_Type_GPRS_Multislot_uplink |
| C386 | IF A.5/35 THEN A ELSE N/A | -- TSPC_CNAP |
| C387 | IF A.25/137 THEN A ELSE NA | TSPC_TCH_WFS |
| C388 | IF A.2/41 AND A.2/72 AND NOT A.2/42 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 AND NOT TSPC_EGPRS |
| C389 | IF A.2/41 AND A.2/72 AND A.25/84 AND A.25/128 AND NOT A.2/42 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_GERAN_FEATURE_PACKAGE_1 AND TSPC_AddInfo_mor1PDP_CA AND TSPC_AddInfo_NewULDataInNewPDP_while_UL TransferInOldPDP AND NOT TSPC_EGPRS |
| C390 | IF A.25/137 OR A.25/133 OR A.25/136 THEN A ELSE N/A | -- TSPC_TCH_WFS OR TSPC_O-TCH_WFS OR TSPC_O-TCH_WHS |
| C391 | IF (A.25/136 OR A.25/131) THEN A ELSE N/A | -- TSPC_O-TCH_WHS OR TSPC_O-TCH_AHS |
| C392 | void | |
| C393 | void | |
| C394 | void | |
| C395 | IF A.25/133 AND A.25/113 THEN A ELSE N/A | -- TSPC_O-TCH_WFS AND TSPC_AMR_LoopBack |
| C396 | IF A.25/137 AND NOT (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_TCH_WFS AND NOT (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C397 | IF A.3/3 AND (A.25/36) AND NOT (A.25/138) THEN A ELSE N/A | -- TSPC_Serv_TS21 AND TSPC_AddInfo_StoreRcvSMSSIM AND NOT (TSPC_AddInfo_OverwriteRcvClass2SMSSIM) |
| C398 | IF A.2/59 OR A.2/60 THEN A ELSE N/A | -- TSPC_A-GPS_Based OR TSPC_A-GPS_Assist |
| C399 | IF (A.2/59 OR A.2/60) AND A.2/74 THEN A ELSE N/A | -- (TSPC_A-GPS_Based OR TSPC_A-GPS_Assist) AND TSPC_Fine_Time_Assist |
| C400 | Void | |
| C401 | void | |

| | | |
|------|--|---|
| C402 | IF A.2/60 AND A.25/140 AND A.5/37 THEN A ELSE N/A | -- TSPC_A-GPS_Assist AND TSPC_A-GPS_Data_Reset AND TSPC_MOLR_POS |
| C403 | IF A.2/59 AND A.25/140 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_A-GPS_Data_Reset |
| C404 | IF A.2/71 AND NOT (A.2/47 OR A.2/62 OR A.2/69) THEN A ELSE N/A | -- TSPC_GAN AND NOT (TSPC_operation_mode_A OR TSPC_DTM_GPRS OR TSPC_DTM_EGPRS) |
| C405 | IF A.2/41 AND A.25/88 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_N_req_PDP_CA |
| C406 | IF A.2/41 AND A.25/85 AND A.25/115 AND A.25/89 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_mor1PDP_CA_SAPI AND TSPC_SEC_PDP_CONTEXT AND TSPC_AddInfo_min_QoS |
| C407 | IF A.25/114 AND A.25/20 THEN A ELSE N/A | -- TSPC_AddInfo_TTY AND TSPC_AddInfo_MOsvc |
| C408 | IF A.25/114 AND A.25/19 THEN A ELSE N/A | -- TSPC_AddInfo_TTY AND TSPC_AddInfo_MTsvc |
| C409 | IF A.25/3 OR A.25/112 THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_1 OR TSPC_AddInfo_Half_rate_version_3 |
| C410 | IF A.1/188 THEN A ELSE N/A | -- TSPC_EGPRS_Multislot_Uplink |
| C411 | IF A.25/26 AND A.25/19 THEN A ELSE N/A | -- TSPC_Addinfo_CCprotocol_oneBC AND TSPC_AddInfo_MOsvc |
| C412 | IF A.25/19 OR A.25/20 THEN A ELSE N/A | -- TSPC_AddInfo_MOsvc OR TSPC_AddInfo_MTsvc |
| C413 | IF A.25/60 OR A.25/148 THEN A ELSE N/A | -- TSPC_AddInfo_PermAntenna OR TSPC_AddInfo_TempAntenna |
| C414 | IF A.25/139 THEN A ELSE N/A | -- TSPC_Repeated_SACCH |
| C415 | IF A.2/41 AND A.2/75 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Feat_GEA2 |
| C416 | IF A.2/41 AND A.2/76 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_Feat_GEA3 |
| C417 | IF A.2/41 AND NOT (A.1/84 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND NOT (TSPC_Type_GPRS_Multislot_Class18 OR TSPC_Type_GPRS_Multislot_Class29) |
| C418 | IF A.2/41 AND NOT (A.1/84 OR A.1/90 OR A.1/91 OR A.1/92 OR A.1/93 OR A.1/94 OR A.1/95) THEN A ELSE N/A | -- TSPC_GPRS AND NOT (TSPC_Type_GPRS_Multislot_Class18 OR TSPC_Type_GPRS_Multislot_Class24 OR TSPC_Type_GPRS_Multislot_Class25 OR TSPC_Type_GPRS_Multislot_Class26 OR TSPC_Type_GPRS_Multislot_Class27 OR TSPC_Type_GPRS_Multislot_Class28 OR TSPC_Type_GPRS_Multislot_Class29) |
| C419 | IF A.2/41 AND NOT (A.1/67 OR A.1/68 OR A.1/69 OR A.1/70 OR A.1/74 OR A.1/149 OR A.1/150 OR A.1/151 OR A.1/152 OR A.1/153 OR A.1/154 OR A.1/155 OR A.1/156 OR A.1/157 OR A.1/158 OR A.1/159 OR A.1/160 OR A.1/161 OR A.1/162 OR A.1/163 OR A.1/164) THEN A ELSE N/A | -- TSPC_GPRS AND NOT (TSPC_Type_GPRS_Multislot_Class1 OR TSPC_Type_GPRS_Multislot_Class2 OR TSPC_Type_GPRS_Multislot_Class3 OR TSPC_Type_GPRS_Multislot_Class4 OR TSPC_Type_GPRS_Multislot_Class8 OR TSPC_Type_GPRS_Multislot_Class30 OR ... OR TSPC_Type_GPRS_Multislot_Class45) |
| C420 | IF A.2/41 AND A.2/70 AND (A.1/153 OR A.1/158 OR A.1/164) THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_ExtendedDynamic_Allocation AND (TSPC_Type_GPRS_Multislot_Class34 OR TSPC_Type_GPRS_Multislot_Class39 OR TSPC_Type_GPRS_Multislot_Class45) |
| C421 | IF A.2/42 AND (A.2/47 OR A.2/48) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_operation_mode_A OR TSPC_operation_mode_B) |
| C422 | IF A.2/42 AND A.2/48 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_operation_mode_B |
| C423 | IF A.2/42 AND NOT (A.1/113 OR A.1/124) THEN A ELSE N/A | -- TSPC_EGPRS AND NOT (TSPC_Type_EGPRS_Multislot_Class18 OR TSPC_Type_EGPRS_Multislot_Class29) |
| C424 | IF A.2/42 AND NOT (A.1/113 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124) THEN A ELSE N/A | -- TSPC_EGPRS AND NOT (TSPC_Type_EGPRS_Multislot_Class18 OR TSPC_Type_EGPRS_Multislot_Class24 OR TSPC_Type_EGPRS_Multislot_Class25 OR TSPC_Type_EGPRS_Multislot_Class26 OR TSPC_Type_EGPRS_Multislot_Class27 OR TSPC_Type_EGPRS_Multislot_Class28 OR TSPC_Type_EGPRS_Multislot_Class29) |

| | | |
|------|---|--|
| C425 | IF A.2/42 AND (A.1/98 OR A.1/100 OR A.1/101 OR A.1/102 OR A.1/104 OR A.1/105 OR A.1/106 OR A.1/107 OR A.1/108 OR A.1/109 OR A.1/110 OR A.1/111 OR A.1/112 OR A.1/113 OR A.1/114 OR A.1/115 OR A.1/116 OR A.1/117 OR A.1/118 OR A.1/119 OR A.1/120 OR A.1/121 OR A.1/122 OR A.1/123 OR A.1/124 OR A.1/166 OR A.1/167 OR A.1/168 OR A.1/169 OR A.1/171 OR A.1/172 OR A.1/173 OR A.1/174 OR A.1/176 OR A.1/177 OR A.1/178 OR A.1/179 OR A.1/180) THEN A ELSE N/A | -- TSPC_EGPRS AND (TSPC_Type_EGPRS_Multislot_Class3 OR TSPC_Type_EGPRS_Multislot_Class5 OR TSPC_Type_EGPRS_Multislot_Class6 OR TSPC_Type_EGPRS_Multislot_Class7 OR TSPC_Type_EGPRS_Multislot_Class9 OR...OR TSPC_Type_EGPRS_Multislot_Class29 OR TSPC_Type_EGPRS_Multislot_Class31 OR...OR TSPC_Type_EGPRS_Multislot_Class34 OR TSPC_Type_EGPRS_Multislot_Class36 OR...OR TSPC_Type_EGPRS_Multislot_Class39 OR TSPC_Type_EGPRS_Multislot_Class41 OR...OR TSPC_Type_EGPRS_Multislot_Class45) |
| C426 | IF A.2/78 THEN A ELSE N/A | -- TSPC_GERAN_FEATURE_PACKAGE_2 |
| C427 | IF A.2/78 AND A.1/15 THEN A ELSE N/A | -- TSPC_GERAN_FEATURE_PACKAGE_2 AND TSPC_Type_HSCSD_Multislot |
| C428 | IF A.2/80 THEN A ELSE N/A | -- TSPC_UTRAN_TO_GAN_CS_Handover |
| C429 | IF A.2/79 THEN A ELSE N/A | -- TSPC_GAN_TO_UTRAN_CS_Handover |
| C430 | IF (A.1/56 AND A.27/2 AND A.25/5 AND A.25/72 AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND TSPC_Streaming_14_4_CSRAB_3_4_SRAB AND TSPC_AddInfo_FullRateData AND TSPC_AddInfo_144Data AND (TSPC_Type_GSM_P_BAND OR TSPC_Type_GSM_E_BAND OR TSPC_Type_DCS_BAND OR TSPC_Type_GSM_450_BAND OR TSPC_Type_GSM_480_BAND OR TSPC_Type_PCS_BAND OR TSPC_Type_GSM_850_BAND OR TSPC_Type_GSM_710_BAND OR TSPC_Type_GSM_750_BAND OR TSPC_Type_T_GSM_810_BAND) |
| C431 | IF (A.1/56 AND ((A.27/3 AND A.25/5 AND A.25/72) OR (A.27/4 AND A.25/5 AND A.25/72)) AND (A.1/1 OR A.1/2 OR A.1/4 OR A.1/16 OR A.1/17 OR A.1/18 OR A.1/55 OR A.1/54 OR A.1/182 OR A.1/183)) THEN A ELSE N/A | -- TSPC_Type_UTRAN AND ((TSPC_STREAMING_28_8_CSRAB_3_4_SRAB AND TSPC_AddInfo_FullRateData AND TSPC_AddInfo_144Data) OR (TSPC_Streaming_57_6_CSRAB_3_4_SRAB AND TSPC_AddInfo_FullRateData AND TSPC_AddInfo_144Data)) AND (TSPC_Type_GSM_P_BAND OR TSPC_Type_GSM_E_BAND OR TSPC_Type_DCS_BAND OR TSPC_Type_GSM_450_BAND OR TSPC_Type_GSM_480_BAND OR TSPC_Type_PCS_BAND OR TSPC_Type_GSM_850_BAND OR TSPC_Type_GSM_710_BAND OR TSPC_Type_GSM_750_BAND OR TSPC_Type_T_GSM_810_BAND) |
| C432 | IF A.25/57 AND A.25/142 THEN A ELSE N/A | -- TSPC_AddInfo_SpeechHandset AND TSPC_AddInfo_Rel4_Acoustic |
| C433 | IF A.25/57 AND NOT A.25/142 THEN A ELSE N/A | -- TSPC_AddInfo_SpeechHandset AND NOT TSPC_AddInfo_Rel4_Acoustic |
| C434 | IF A.25/79 AND (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_full_rate_version_3 AND (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C435 | IF A.25/112 AND (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_AddInfo_half_rate_version_3 AND (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C436 | IF A.25/137 AND (A.25/132 OR A.25/129 OR A.25/141) THEN A ELSE N/A | -- TSPC_TCH_WFS AND (TSPC_Improv_RX_perform OR TSPC_DARP_Phase1 OR TSPC_DARP_Phase2) |
| C437 | IF A.25/67 AND A.5/29 THEN A ELSE N/A | -- TSPC_AddInfo_VBS_Originating AND TSPC_Serv_UTDI |
| C438 | IF A.25/70 AND A.5/29 THEN A ELSE N/A | -- TSPC_AddInfo_VGCS_Originating AND TSPC_Serv_UTDI |

| | | |
|------|---|---|
| C439 | IF A.25/67 AND A.5/30 THEN A ELSE N/A | -- TSPC_AddInfo_VBS_Originating AND TSPC_Serv_Compr_UTDI |
| C440 | IF A.25/70 AND A.5/30 THEN A ELSE N/A | -- TSPC_AddInfo_VGCS_Originating AND TSPC_Serv_Compr_UTDI |
| C441 | IF A.2/62 AND A.2/81 THEN A ELSE N/A | -- TSPC_DTM_GPRS AND TSPC_Enhanced_DTM_CS |
| C442 | IF (A.25/119 OR A.25/146 OR A.25/147) AND A.2/41 THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_NITZ_DST OR TSPC_NITZ_Time_Zone OR TSPC_NITZ_Universal_Time) |
| C443 | IF (A.25/145 OR A.25/144) AND A.2/41 THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_NITZ_Short_Name OR TSPC_NITZ_Full_Name) |
| C444 | IF A.2/59 AND A.5/37 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_MOLR_POS |
| C445 | IF A.2/60 AND A.5/37 THEN A ELSE N/A | -- TSPC_A-GPS_Assist AND TSPC_MOLR_POS |
| C446 | IF A.2/59 AND A.5/38 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_MOLR_3RD |
| C447 | IF A.2/60 AND A.5/38 THEN A ELSE N/A | -- TSPC_A-GPS_Assist AND TSPC_MOLR_3RD |
| C448 | IF A.2/41 AND A.25/141 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_DARP_Phase2 |
| C449 | IF A.2/42 AND A.25/141 THEN A ELSE N/A | -- TSPC_EGPRS AND TSPC_DARP_Phase2 |
| C450 | IF A.25/19 AND A.5/23 THEN A ELSE N/A | -- TSPC_Addinfo_MTsvc AND TSPC_Serv_SS_UUS |
| C451 | IF A.25/2 AND A.25/141 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_1 AND TSPC_DARP_Phase2 |
| C452 | Void | |
| C453 | IF A.25/79 AND A.25/113 AND A.25/141 THEN A ELSE N/A | -- TSPC_AddInfo_Full_rate_version_3 AND TSPC_AMR_LoopBack AND TSPC_DARP_Phase2 |
| C454 | IF A.25/112 AND A.25/113 AND A.25/141 THEN A ELSE N/A | -- TSPC_AddInfo_Half_rate_version_3 AND TSPC_AMR_LoopBack AND TSPC_DARP_Phase2 |
| C455 | IF (A.1/15 AND A.25/26) AND NOT A.1/22 THEN A ELSE N/A | -- (TSPC_Type_HSCSD_Multislot AND TSPC_Addinfo_CCprotocol_oneBC) AND NOT TSPC_Type_Multislot_Class1 |
| C456 | IF A.2/41 AND A.25/2 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_AddInfo_Full_rate_version_1 |
| C457 | IF A.5/20 OR A.25/26 THEN A ELSE N/A | -- TSPC_Serv_SS_unstruct OR TSPC_Addinfo_CCprotocol_oneBC |
| C458 | IF A.25/97 AND A.25/26 THEN A ELSE N/A | -- TSPC_AddInfo_MultSMsameRR AND TSPC_Addinfo_CCprotocol_oneBC |
| C459 | IF A.2/41 AND (A.2/47 OR A.2/48) AND A.25/19 THEN A ELSE N/A | -- TSPC_GPRS AND (TSPC_operation_mode_A OR TSPC_operation_mode_B) AND TSPC_AddInfo_MTsvc |
| C460 | IF A.2/59 AND A.5/39 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_MTLR |
| C461 | IF A.2/60 AND A.5/39 THEN A ELSE N/A | -- TSPC_A-GPS_Assist AND TSPC_MTLR |
| C462 | IF (A.25/2 OR A.25/3) AND A.5/9 THEN A ELSE N/A | -- (TSPC_AddInfo_Full_rate_version_1 OR TSPC_AddInfo_Half_rate_version_1) AND TSPC_Serv_SS_CW |
| C463 | IF A.2/41 AND A.2/82 THEN A ELSE N/A | -- TSPC_GPRS AND TSPC_PS_Handover |
| C464 | IF A.25/26 AND (A.3/1 OR A.3/2 OR A.4/20 OR A.4/21) THEN A ELSE N/A | -- TSPC_Addinfo_CCprotocol_oneBC AND (TSPC_Serv_TS11 OR TSPC_Serv_TS12 OR TSPC_Serv_BS61 OR TSPC_Serv_BS81) |
| C465 | IF A.2/59 AND A.5/40 THEN A ELSE N/A | -- TSPC_A-GPS_Based AND TSPC_MOLR_ASSIS |
| C466 | IF A.25/149 THEN A ELSE N/A | -- TSPC_Repeated_FACCH |

Note1: This test case concerns a feature introduced in R97, but it is applicable only for R99 and later as it has been created late.

Table B.1b: Limited Applicability of tests - Conditions definitions

| | | |
|-----|---------------------------------------|---|
| R1 | IF A.1/56 THEN R ELSE A | -- TSPC_Type_UTRAN |
| R2 | IF A.1/15 OR A.1/57 THEN R ELSE A | -- TSPC_Type_HSCSD_Multislot OR TSPC_GPRS_Multislot_Uplink |
| R3 | IF A.1/57 THEN R ELSE A | -- TSPC_GPRS_Multislot_Uplink |
| R4 | IF A.2/41 OR A.2/42 THEN R ELSE A | -- TSPC_GPRS OR TSPC_EGPRS |
| R5 | IF A.1/15 THEN R ELSE A | -- TSPC_Type_HSCSD_Multislot |
| R6 | IF A.2/42 THEN R ELSE A | -- TSPC_EGPRS |
| R7 | IF A.25/129 OR A.25/141 THEN R ELSE A | -- TSPC_DARP_Phase1 OR TSPC_DARP_Phase2 |
| R8 | void | |
| R9 | IF A.25/79 THEN R ELSE A | TSPC_AddInfo_Full_rate_version_3 |
| R10 | IF A.25/112 THEN R ELSE A | TSPC_AddInfo_Half_rate_version_3 |
| R11 | IF A.25/79 OR A.25/112 THEN R ELSE A | TSPC_AddInfo_Full_rate_version_3 OR TSPC_AddInfo_Half_rate_version_3 |
| R12 | IF A.25/79 AND A.25/113 THEN R ELSE A | TSPC_AddInfo_Full_rate_version_3 AND TSPC_AMR_LoopBack |

Table B.1c: Limited Execution of tests - Conditions definitions

| | | |
|----|---|---|
| L1 | Executed for 'Class C' MS or 'Class B' MS only if 'Class C' is not supported. | -- TSPC_operation_mode_C OR (TSPC_operation_mode_B and NOT TSPC_operation_mode_C) |
| L2 | Executed for 'Class B' MS or 'Class C' MS only if 'Class B' is not supported. | -- TSPC_operation_mode_B OR (TSPC_operation_mode_C and NOT TSPC_operation_mode_B) |
| L3 | Some parts of test are omitted for DARP capable MS due to overlap with DARP specific tests. | -- TSPC_DARP_Phase1 OR TSPC_DARP_Phase2 |
| L4 | Part of test where fading profile is same as used in half rate version of test is omitted. | -- TSPC_AddInfo_Half_rate_version_3 |
| L5 | Executed for R-GSM if supported, otherwise executed for E-GSM | -- TSPC_Type_GSM_R_Band OR (TSPC_Type_GSM_E_Band and NOT TSPC_Type_GSM_R_Band) |
| L6 | Vibration condition part of the test case is omitted | -- TSPC_No_Vibration_Sensitive_Components |

Annex C (informative): Guidance for updating the PICS specification

The purpose of this Guidance for updating the PICS specification is to check the influence of a newly created, deleted or modified test case to the PICS specification and to fit the tables according the change.

This Guidance for updating the PICS specification shall give a recommendation, how to check and update all relevant tables and columns.

C.1 Update of tables of annex A

In annex A, all PICS items are listed and structured in tables of options and features.

If a test case is newly created, modified or deleted, the PICS items used for this test case has to be identified or known to update annex A.

C.2 Identification of PICS items

Support of PICS items can either be necessary to perform a test case, these PICS can be called Applicability PICS, or the support of PICS items can be inquired within a test case, these PICS can be called Capability PICS.

Applicability PICS are mostly described in clause "Definition and Applicability" in a test case description.

Capability PICS should be defined in clause "Related PICS/PIXIT statements" which is mostly a part for the "Method of test" description.

C.3 Update of PICS items

It shall be checked, in which table of annex A the identified PICS items can be assigned to.

If there are new PICS to be added where no existing tables refer to, a new table shall be created. Here, the given prerequisites have to be considered and checked for assigning a table of annex A.

For newly inserted PICS items, a Mnemonic shall be created and the Status column shall be checked and set (M, O,X, N/A, O.i, Ci). For a Status "Ci: conditional", the logical expression has to be defined on the end of the table.

The Status of a PICS could either be mentioned in the PICS Reference (Reference column) or in the test case description or it should be set by the test case writer.

The PICS Reference refers to a certain Release (Release column), i.e. when the PICS appears for the first time in the GSM and/or 3GPP reference.

C.4 Update of table B.1 of annex B

In annex B, all test cases as described in 3GPP TS 51.010-1, 3GPP TS 11.10-1 or 3GPP TS 11.10-4 are listed in table B.1.

If a test case is newly created, modified or deleted, the table B.1 has to be updated accordingly.

C.5 Update of the listed tests of table B.1

For newly created or modified test cases, the test case title and the clause number has to be listed or updated in table B.1.

If a newly created or modified test case is separated in sub-procedures dependent on different applicability conditions, the test case should be listed accordingly.

A test case is grouped to test a certain feature. Therefore the Release column shall indicate, in which Release of the core specification the tested feature was included for the first time. For instance, if a newly created test case tests a GPRS feature, the Release column is to set to R97, where the feature GPRS was added in the core specification.

C.6 Update of the applicability conditions of table B.1

For newly created or modified test cases, the Status column shall be checked (A, N/A, Ci).

I.e. the updated applicability status for the test case has to be set in the Status column.

If there is no applicability PICS necessary to perform a test case, the status "A" should be assigned.

If there is a logical combination of PICS items necessary to perform a test case, this combination shall be defined and updated as Status "Ci: conditional" on the end of the table and assigned to this test case. For instance, if a newly created test case needs the support of GPRS, the Status is conditional "Ci" and the logical combination has to use the PICS item "Support of GPRS".

The applicability column shall be checked and updated towards the Status of the test case.

It gives a short overview, when this test case is applicable.

If a deleted test cases was assigned with a Status "Ci:conditional", it should be checked, if this condition is used for further test cases, if not, the logical expression on the end of table B.1 can be deleted.

If a logical expression is deleted, it should be checked, if the used PICS items of tables A are also be removable.

Annex D (informative): Labelling of Inter-RAT signalling test cases

This Annex provides a labelling guideline for the GERAN/UTRAN inter-RAT signalling test cases. The purpose of this Annex is to aid clear and traceable test case identification, both for the purposes of validation reporting in the certification organisations as well as for test houses to unambiguously identify the tested frequency bands. Note that actual band combinations to be tested shall be specified by the certification organisations.

D.1 GERAN/UTRAN band combinations for inter-RAT tests

It is recommended the following labelling convention should be used for the inter-RAT derivative test cases covering different GERAN/UTRAN band combinations:

"Test Case number"('GSM Frequency band'-'UTRAN band')

UTRAN bands are listed using Roman numerals.

For example: 60.1(900-I) for inter-RAT test covering GSM 900 and UTRAN band I.

The above mentioned labeling convention shall apply to the following inter-RAT tests defined in TS 51.010-1:

| Test Type | Test Case Number |
|-----------------------------|---|
| Idle Mode | 20.25.2, 20.25.3, 20.25.4 |
| Enhanced Measurement Report | 26.6.3.8 |
| Class Mark | 26.6.11.3, 26.6.11.4 |
| Inter-system Handover | 60.1, 60.2a, 60.2b, 60.3a, 60.3b, 60.4, 60.5, 60.6, 60.7, 60.8, 60.9, 60.10 |
| Packet Measurement Order | 20.22.29 |
| Inter-RAT Cell Change Order | 42.4.7.1, 42.4.7.2, 42.4.7.3, 42.4.7.4, 42.4.7.5.1, 42.4.7.5.2 |
| Inter-RAT DTM | 41.5.1.1.1.4, 47.3.4.1, 47.3.4.2 |

Annex E (informative): Change history

| Change history | | | | | | | | | | |
|----------------|-----------|-----|-----|---|-----|-------|-------|-----------|-----------------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| GP-04 | GP-010465 | | | Approved as v4.0.0 | | 2.0.0 | 4.0.0 | | | |
| GP-05 | GP-011151 | 001 | | Update to applicability table in 51.010-2 due to TDoc G4-010225 | F | 4.0.0 | 4.1.0 | G4-010242 | GPRS | |
| GP-05 | GP-011151 | 002 | | Addition of EDGE test cases to the applicability table | F | 4.0.0 | 4.1.0 | G4-010329 | EDGE | |
| GP-05 | GP-011151 | 004 | | Deletion of Test cases 13.5 and 13.17.5 from the Applicability Table | F | 4.0.0 | 4.1.0 | G4-010311 | TEI | |
| GP-05 | GP-011151 | 005 | | Update of the Applicability Table with test cases for GPRS Cell Selection/Reselection 20.22 | F | 4.0.0 | 4.1.0 | G4-010315 | GPRS | |
| GP-05 | GP-011151 | 006 | | Recommendation for updating the PICS specification 3GPP TS 51.010-2 according to changes in 3GPP TS 51.010-1 or 3GPP TS 11.10-4 | B | 4.0.0 | 4.1.0 | G4-010302 | TEI | |
| GP-06 | GP-011466 | 007 | | Harmonisation of conformance tests related to terminal acoustics in GSM and 3G | F | 4.1.0 | 4.2.0 | G4-010336 | TEI | |
| GP-06 | GP-011466 | 008 | | Correction of title for clause 44.2.3.3.4 | F | 4.1.0 | 4.2.0 | G4-010369 | GPRS | |
| GP-06 | GP-011466 | 009 | | Correction of conditional statement C226 | F | 4.1.0 | 4.2.0 | G4-010436 | GPRS | |
| GP-06 | GP-011466 | 010 | | Addition of new EGPRS test cases for section 51.3 (TBF Release) | F | 4.1.0 | 4.2.0 | G4-010419 | EDGE | |
| GP-06 | GP-011466 | 011 | | Addition of new EGPRS test cases for section 52.4 (Measurement reports and Cell change order procedures) | F | 4.1.0 | 4.2.0 | G4-010420 | EDGE | |
| GP-06 | GP-011466 | 012 | | Applicability table for EGPRS RR Paging Procedures | F | 4.1.0 | 4.2.0 | G4-010423 | EDGE | |
| GP-06 | GP-011466 | 013 | | Applicability table for EGPRS Medium Access Control (MAC) Protocol/ Fixed Allocation | F | 4.1.0 | 4.2.0 | G4-010425 | EDGE | |
| GP-06 | GP-011466 | 014 | | Addition of new EGPRS test cases for section 53 (EGPRS RLC Testcases) | F | 4.1.0 | 4.2.0 | G4-010429 | EDGE | |
| GP-06 | GP-011466 | 015 | | Addition of new EGPRS test cases for section 52.3 (EGPRS MAC Dynamic Allocation) | F | 4.1.0 | 4.1.0 | G4-010534 | EDGE | |
| GP-06 | GP-011466 | 016 | | Applicability table for Handover Test Cases | F | 4.1.0 | 4.2.0 | G4-010453 | GSM/UMTS interworking | |
| GP-06 | GP-011466 | 017 | | Addition of 1,8V and 1,8V/3V SIM-ME interface test cases into 51.010-2 section A4.8 and Annex B (applicability table) | F | 4.1.0 | 4.2.0 | G4-010494 | TEI | |
| GP-06 | GP-011466 | 018 | | Correction of COMPACT and SoLSA tests in the Release column of table B.1 | F | 4.1.0 | 4.2.0 | G4-010448 | TEI | |
| GP-07 | GP-012116 | 019 | | deletion of test case 27.11.2.1 | F | 4.2.0 | 4.3.0 | G5-010043 | TEI | |
| GP-07 | GP-012117 | 020 | | Correction of applicability condition C220 in Annex B.1 | F | 4.2.0 | 4.3.0 | G5-010027 | TEI | |
| GP-07 | GP-012118 | 021 | | Correction of applicability condition C52 in Annex B.1 | F | 4.2.0 | 4.3.0 | G5-010028 | TEI | |
| GP-07 | GP-012119 | 022 | | Changes to applicability of test case 44.2.1.2.3 | F | 4.2.0 | 4.3.0 | G5-010149 | GPRS | |
| GP-07 | GP-012120 | 023 | | 45.2.1.2.1 – This Test Case Should Only Be Applicable To Mobiles That Support Configuration of Their QoS. | F | 4.2.0 | 4.3.0 | G5-010159 | GPRS | |
| GP-07 | GP-012609 | 034 | | Applicability Table for E-OTD Test Cases for LCS Clause 70 (Rel-4) | F | 4.2.0 | 4.3.0 | - | LCS | |
| GP-07 | GP-012273 | 024 | | CR 51.010-2-024 on Annex B - removal of test case 51.2.4.2 (related to G4-010594) Rel-4 | F | 4.2.0 | 4.3.0 | G4-010622 | EDGE | |
| GP-07 | GP-012274 | 025 | | CR 51.010-2-025 on GSM 700 and GSM850 inclusion into forward Rel-4 | B | 4.2.0 | 4.3.0 | G4-010649 | GSM 700 | |
| GP-07 | GP-012275 | 026 | | CR 51.010-2-026 on New test cases for clause 42.1 Rel-4 | B | 4.2.0 | 4.3.0 | G4-010649 | GPRS | |
| GP-07 | GP-012276 | 027 | | CR 51.010-2-027 on change of test case name for clause 51.2.2.2. Rel-4 | F | 4.2.0 | 4.3.0 | G4-010663 | EDGE | |
| GP-07 | GP-012277 | 028 | | CR 51.010-2-028 on Table B1 - Addition of section 52.1 testcases to the applicability table Rel-4 | B | 4.2.0 | 4.3.0 | G4-010669 | EGPRS | |

| Change history | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|-------|-------|-----------|-----------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| GP-07 | GP-012191 | 030 | | CR 51.010-2-030 Correction to the Applicability of test cases 13.17.1; 13.17.3 and 13.17.4 (Rel 4) | F | 4.2.0 | 4.3.0 | GP-012191 | EDGE |
| GP-07 | GP-012201 | 031 | | CR 51.010-2-31 Annex B - renaming of test case 51.2.4.1 (Rel 4) | F | 4.2.0 | 4.3.0 | GP-012201 | EDGE |
| GP-07 | GP-012722 | 034 | 1 | CR 51.010-2-034r1 Bad frame indication - TCH/AFS - Random RF input 51.010-2 | B | 4.2.0 | 4.3.0 | GP-012722 | AMR |
| GP-07 | GP-012732 | 035 | | CR 51.010-2-035 14.18.7 Incremental Redundancy Performance, (addition of a new test) (Rel-4) | B | 4.2.0 | 4.3.0 | GP-012732 | EGPRS |
| GP-07 | GP-012784 | 036 | | CR 51.010-2-036 Applicability of test 42.2.2.4; Fixed Allocation/Uplink Transfer/T3184 Expiry | F | 4.2.0 | 4.3.0 | GP-012784 | GPRS |
| GP-07 | GP-012296 | 037 | | CR 51.010-2-035 Bad frame indication - TCH/AHS - Random RF input 51.010-2 | B | 4.2.0 | 4.3.0 | GP-012296 | AMR |
| GP-08 | GP-020367 | 041 | 1 | Applicability Table for E-OTD Test Cases for LCS Clause 70 (Rel-4) | F | 4.3.0 | 4.4.0 | GP-020367 | LCS |
| GP-08 | GP-020064 | 042 | | Update of references | F | 4.3.0 | 4.4.0 | GP-020064 | TEI |
| GP-08 | GP-020148 | 044 | | Additional Test Case | B | 4.3.0 | 4.4.0 | GP-020148 | GPRS |
| GP-08 | GP-020378 | 045 | 1 | Addition of LCS test cases to the Applicability Tables A2 and B.1 | F | 4.3.0 | 4.4.0 | GP-020378 | LCS |
| GP-09 | GP-021053 | 047 | 1 | Applicability Table B.1: Addition of test of short message type 0 (34.2.6) | F | 4.4.0 | 4.5.0 | GP-021053 | TEI |
| GP-09 | GP-020549 | 048 | - | Correction to reference clause | F | 4.4.0 | 4.5.0 | GP-020549 | TEI |
| GP-09 | GP-021213 | 049 | 1 | CR 51.010-2-049 Addition of LCS performance test cases to the Applicability Table B.1 | F | 4.4.0 | 4.5.0 | | LCS |
| GP-09 | GP-020605 | 051 | - | 51.010-2 Annex B: Correction of applicability table for section 46 | F | 4.4.0 | 4.8.0 | GP-020605 | GPRS |
| GP-09 | GP-020665 | 052 | | Removal of applicability of GPRS Fixed Allocation tests (42.2.x) for R99 and Rel-4 - (Rel-4). | F | 4.4.0 | 4.5.0 | | GPRS |
| GP-09 | GP-020666 | 053 | | Removal of EGPRS Fixed Allocation tests (52.2.x) for R99 and Rel-4 - (Rel-4). | F | 4.4.0 | 4.5.0 | | EDGE |
| GP-09 | GP-020728 | 054 | - | PICS update for GERAN to UTRAN Handover test cases | F | 4.4.0 | 4.5.0 | GP-020728 | GERAN> UTRAN HO |
| GP-09 | GP-020784 | 057 | | Removal of testcase 20.22.27 of 51.010-1 | F | 4.4.0 | 4.5.0 | | GPRS |
| GP-09 | GP-021181 | 058 | 3 | Applicability Table for A-GPS Test Cases for LCS Clause 70 (Rel 4) | F | 4.4.0 | 4.5.0 | GP-021181 | LCS |
| GP-10 | GP-021840 | 059 | 1 | CR to Applicability Table B.1: Correction of | F | 4.5.0 | 4.6.0 | GP-021840 | TEI |
| GP-10 | GP-021842 | 060 | 1 | 51.010-2-060 Correct the Applicability Tables | F | 4.5.0 | 4.6.0 | GP-021842 | LCS |
| GP-10 | GP-021561 | 061 | - | PICS update for AMR RATSCCH Test Cases | F | 4.5.0 | 4.6.0 | GP-021561 | AMR |
| GP-10 | GP-021871 | 062 | 1 | Annex B – Renaming of testcase 41.4.3.3.2 | F | 4.5.0 | 4.6.0 | GP-021561 | GPRS |
| GP-11 | GP-022747 | 069 | 2 | 51.010-2 PICS additions to section A.4.8 to better characterise non auto GPRS attach behaviour. | F | 4.6.0 | 4.7.0 | GP-022747 | GPRS |
| GP-11 | GP-022735 | 070 | 1 | CR 51.010-2-070 r1 Modification of Applicability Table for E-OTD Performance Tests | F | 4.6.0 | 4.7.0 | GP-022735 | LCS |
| GP-11 | GP-022621 | 071 | 1 | DTM additons to the PICS proforma tables for GSM mobile stations. | F | 4.6.0 | 4.7.0 | GP-022621 | DTM |
| GP-11 | GP-022294 | 072 | - | DTM additons to the test applicability tables for GSM mobile stations (WG5). | F | 4.6.0 | 4.7.0 | GP-022294 | DTM |
| GP-11 | GP-022320 | 073 | | CR 51.010-2-073 DTM additons to the test applicability tables for GSM mobile stations (WG4). | F | 4.6.0 | 4.7.0 | GP-022320 | DTM |
| GP-11 | GP-022342 | 074 | | CR 51.010-2-074 Removal of 5 EGPRS test cases from Annex B, Table B.1. - Rel-4 | F | 4.6.0 | 4.7.0 | GP-022342 | EDGE |
| GP-11 | GP-022693 | 075 | 1 | Correction of PICS conditions and corrected applicability of test case 45.2.1.2.2 in TS 51.010-2 | F | 4.6.0 | 4.7.0 | GP-022693 | TEI4 |
| GP-11 | GP-022424 | 077 | - | Applicability Table Update | F | 4.6.0 | 4.7.0 | GP-022424 | LCS |
| GP-11 | GP-022602 | 078 | 1 | CR 51.010-2-078 r1 Removal of TBF establishment via DCCH in Annex B, Table B.1 | F | 4.6.0 | 4.7.0 | GP-022602 | GPRS |
| GP-11 | GP-022734 | 079 | 1 | CR 51.010-2-079 r1 Addition of new layer 1 tests to matrix | F | 4.6.0 | 4.7.0 | GP-022734 | AMR |
| GP-11 | GP-022635 | 080 | 1 | Addition of new layer 3 tests to matrix | F | 4.6.0 | 4.7.0 | GP-022635 | AMR |
| GP-11 | GP-022473 | 081 | - | Applicability Table for E-OTD MOLR test cases | F | 4.6.0 | 4.7.0 | GP-022473 | LCS |

| Change history | | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|-------|-------|-----------|------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| GP | | | | | | | | | | |
| GP-11 | GP-022625 | 066 | 1 | CR to 51.010-2: Addition of test of short message type 0 REL-5 (34.2.6a) to Applicability Table B.1 | F | 4.6.0 | 5.0.0 | GP-022625 | TEI | |
| GP-11 | GP-022128 | 067 | - | Creation of 51.010-2 REL-5: Merging of REL-5, REL-4, R99 etc. PICS proforma Specifications | F | 4.6.0 | 5.0.0 | GP-022128 | TEI | |
| GP-12 | GP-023335 | 083 | 1 | CR 51.010-2-083 r1 Addition of WG4 DTM Conformance Tests to the Applicability table (Rel-5) | F | 5.0.0 | 5.1.0 | GP-023335 | DTM | |
| GP-12 | GP-022948 | 084 | - | Addition of WG5 DTM Conformance Tests to the Applicability Table | F | 5.0.0 | 5.1.0 | GP-022948 | DTM | |
| GP-12 | GP-023388 | 086 | 1 | Applicability Table Update | F | 5.0.0 | 5.1.0 | GP-023388 | LCS | |
| GP-12 | GP-023033 | 087 | | CR 51.010-2-087 Changed the name of clause 51.2.2.3. | F | 5.0.0 | 5.1.0 | GP-023033 | EDGE | |
| GP-12 | GP-023047 | 088 | - | Change of Applicability for test case 44.2.1.1.8 - GPRS attach/abnormal cases/power off | F | 5.0.0 | 5.1.0 | GP-023047 | GPRS | |
| GP-12 | GP-023295 | 089 | 1 | Add AMR half rate optional applicability | F | 5.0.0 | 5.1.0 | GP-023295 | AMR | |
| GP-12 | GP-023385 | 091 | 1 | Introduction of UTRAN Classmark Change test cases in section 26.6.11 | F | 5.0.0 | 5.1.0 | GP-023385 | TEI | |
| GP-12 | GP-023096 | 092 | | CR 51.010-2-092 Addition of Extended Uplink TBF Mode test cases to matrix | F | 5.0.0 | 5.1.0 | GP-023096 | GPRS | |
| GP-12 | GP-023142 | 093 | - | Applicability Table for GMM Test Cases | F | 5.0.0 | 5.1.0 | GP-023142 | GPRS | |
| GP-12 | GP-023393 | 094 | 2 | Applicability Table for E-OTD MOLR test cases | F | 5.0.0 | 5.1.0 | GP-023393 | LCS | |
| GP-12 | GP-023334 | 095 | 1 | CR 51.010-2-095 r1 Error in Conditional Expression C53 in Table B.1 | F | 5.0.0 | 5.1.0 | GP-023334 | GPRS | |
| GP-12 | GP-023392 | 096 | 2 | Modifications to allow introduction of the 11.10-4 R99 Test Spec | F | 5.0.0 | 5.1.0 | GP-023392 | TEI | |
| GP-12 | GP-023338 | 097 | | CR 51.010-2-097 Addition of 4 new EGPRS test cases. | F | 5.0.0 | 5.1.0 | GP-023338 | EDGE | |
| GP-13 | GP-030368 | 099 | 2 | Applicability of 'Speech teleservices' test cases in Annex B | F | 5.1.0 | 5.2.0 | GP-030368 | TEI | |
| GP-13 | GP-030394 | 100 | 2 | CR 51.010-2-100 r2 Update of applicability table | B | 5.1.0 | 5.2.0 | | EDGE | |
| GP-13 | GP-030167 | 101 | | Update to Applicability Table Indicating Tests for MS-Assisted E-OTD | F | 5.1.0 | 5.2.0 | GP-030167 | LCS | |
| GP-13 | GP-030363 | 102 | 1 | Update to Applicability Table for Assisted GPS MO-LR Tests | F | 5.1.0 | 5.2.0 | GP-030363 | LCS | |
| GP-13 | GP-030359 | 103 | 1 | suppression of table A.26.2 Terminal Profile | F | 5.1.0 | 5.2.0 | GP-030359 | SAT | |
| GP-13 | GP-030348 | 104 | | CR 51.010-2-104 Updating PICS for AMR test cases | B | 5.1.0 | 5.2.0 | | AMR-NB | |
| GP-13 | GP-030389 | 105 | | CR 51.010-2-105 Updating PICS for EMR cases | B | 5.1.0 | 5.2.0 | | TEI | |
| GP-13 | GP-030395 | 106 | 1 | CR 51.010-2 106 r1 Addition of test case on NC2 and Re-allocation in uplink | B | 5.1.0 | 5.2.0 | | GPRS (S42) | |
| GP-14 | GP-030499 | 107 | - | Clarification to speech codec definitions | F | 5.2.0 | 5.3.0 | GP-030499 | TEI | |
| GP-14 | GP-030500 | 108 | - | Correction of Applicability column for clause 14.2.4. | F | 5.2.0 | 5.3.0 | GP-030500 | TEI | |
| GP-14 | GP-030966 | 109 | 1 | Addition of some DTM test cases to the applicability table. | F | 5.2.0 | 5.3.0 | GP-030966 | DTM | |
| GP-14 | GP-030639 | 110 | - | Deletion of test cases 42.4.2.1.5 and 52.4.2.1.5 from Table B.1. | F | 5.2.0 | 5.3.0 | GP-030639 | GPRS | |
| GP-14 | GP-031044 | 111 | 2 | Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1 | F | 5.2.0 | 5.3.0 | GP-031044 | GPRS | |
| GP-14 | GP-031017 | 113 | 2 | Addition of test case in TS 51.010 S42: Packet Uplink Assignment containing a new Coding Scheme command. | F | 5.2.0 | 5.3.0 | GP-031017 | GPRS | |
| GP-14 | GP-030841 | 114 | - | Updating PICS for RxQual test cases | F | 5.2.0 | 5.3.0 | GP-030841 | AMR | |
| GP-14 | GP-030999 | 115 | 1 | Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1 | F | 5.2.0 | 5.3.0 | GP-030999 | GSM | |
| GP-14 | GP-030994 | 116 | 1 | Addition of test cases for Network Assisted Cell Change | B | 5.2.0 | 5.3.0 | GP-030994 | NACC | |
| GP-14 | GP-031013 | 117 | - | CR 51.010-2 Incorrect applicability for 6 test cases of section 42.3.1.1.* | F | 5.2.0 | 5.3.0 | GP-031013 | GPRS | |
| GP-14 | GP-031050 | 118 | 2 | Update PICS for GPRS EMR Test case | F | 5.2.0 | 5.3.0 | GP-031050 | GPRS | |
| GP-15 | GP-031086 | 119 | | CR 51.010-2-119 Table B.1: Conditions for TCs 14.2.18, 14.4.16, 26.6.5.2-2, 26.6.5.2-5, 26.6.5.2-6, 26.6.5.2-10 corrected; Missing TC 31.3.1.2.2.1 added | F | 5.3.0 | 5.4.0 | GP-031086 | TEI | |

| Change history | | | | | | | | | |
|----------------|-----------|-----|-----|---|-----|-------|-------|-----------|--------------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| GP-15 | GP-031287 | 122 | | CR 51.010-2-122 B1 Add new TC - 44.2.3.1.1a - Routing area updating / accepted / old P-TMSI | F | 5.3.0 | 5.4.0 | GP-031287 | GPRS |
| GP-15 | GP-031314 | 123 | | CR 51.010-2-123 Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1 and change of some testcases titles | F | 5.3.0 | 5.4.0 | GP-031314 | GPRS |
| GP-15 | GP-031460 | 124 | | CR 51.010-2-124 Update of Applicability Table for PEMR Test Cases (Rel-5) | F | 5.3.0 | 5.4.0 | GP-031460 | GPRS |
| GP-15 | GP-031714 | 125 | 1 | CR 51.010-2-125 rev1 Update of Applicability Table for SMS over GPRS (Rel-5) | F | 5.3.0 | 5.4.0 | GP-031714 | GPRS |
| GP-15 | GP-031493 | 126 | | CR 51.010-2-126 Deletion of clauses 42.4.2.1.2 and 42.4.2.3.2 from Table B.1. | F | 5.3.0 | 5.4.0 | GP-031493 | GPRS |
| GP-15 | GP-031506 | 127 | | CR 51.010-2-127 Deletion of clause 52.4 from Table B.1 | F | 5.3.0 | 5.4.0 | GP-031506 | EDGE |
| GP-15 | GP-031615 | 128 | | CR 51.010-2-1128 Deletion of test case 52.1.1.1 from Table B.1 | F | 5.3.0 | 5.4.0 | GP-031615 | EDGE |
| GP-15 | GP-031629 | 129 | | CR 51.010-2 129 Update PICS for 22.12 | F | 5.3.0 | 5.4.0 | GP-031629 | GPRS |
| GP-15 | GP-031631 | 130 | | CR 51.010-2 "Multiple PCCCH test cases 42.1.2.1.14, 42.1.2.1.15, 42.1.2.1.16, 42.1.2.1.17 and 42.1.2.1.18" | F | 5.3.0 | 5.4.0 | GP-031631 | GPRS |
| GP-15 | GP-031638 | 131 | 2 | CR 51.010-2-131 rev2 Update PICS for 20.22.29 | F | 5.3.0 | 5.4.0 | GP-031638 | Cell selection |
| GP-16 | GP-031952 | 121 | 1 | CR 51.010-2-121 rev 1 Removal of the closed-ended TBF feature in annex B, table B1 | C | 5.4.0 | 5.5.0 | | TEI |
| GP-16 | GP-032156 | 135 | 1 | CR 51.010-2-135 rev1 Modification in the applicability of the following testcases: 42.3.1.1.8, 42.7.4, 52.3.1.1.8. Changing the name of the testcase 20.22.5. | F | 5.4.0 | 5.5.0 | | GPRS |
| GP-16 | GP-031875 | 136 | | CR 51.010-2-136 Editorial changes to Packet Enhanced Measurement Reporting | F | 5.4.0 | 5.5.0 | | GPRS |
| GP-16 | GP-031961 | 137 | | CR 51.010-2-137 Applicability for 2G to 3G Cell Change Order Test Cases | F | 5.4.0 | 5.5.0 | | GPRS |
| GP-16 | GP-031974 | 138 | | CR 51.010-2-138 Update corresponding to changes to the DTM feature | F | 5.4.0 | 5.5.0 | | DTM |
| GP-16 | GP-032157 | 140 | | CR 51.010-2-140 Section 42: "New test cases: NC2 in Packet transfer mode" | F | 5.4.0 | 5.5.0 | | GPRS |
| GP-16 | GP-032178 | 141 | 1 | CR 51.010-2-141 rev1 Section 70: "New test case: Conventional GPS" | F | 5.4.0 | 5.5.0 | | LCS |
| GP-16 | GP-032160 | 143 | | CR 51.010-2-143 26.16.10 splitted in two test cases | F | 5.4.0 | 5.5.0 | | AMR |
| GP-17 | GP-032307 | 144 | - | Adding TTY test cases | B | 5.5.0 | 5.6.0 | GP-032307 | TTY |
| GP-17 | GP-032334 | 145 | - | Addition of new NC2 cases | F | 5.5.0 | 5.6.0 | GP-032334 | GPRS |
| GP-17 | GP-032776 | 146 | 1 | Modification to Applicability Table due to introduction of new testcases in 3GPP TS 51.010-1 | F | 5.5.0 | 5.6.0 | GP-032776 | GPRS |
| GP-17 | GP-032425 | 147 | - | CR 51.010-2 Test cases from section 53 missing | F | 5.5.0 | 5.6.0 | GP-032425 | GPRS |
| GP-17 | GP-032457 | 148 | - | Update PICS for MOLR MS-Based AGPS Test cases | F | 5.5.0 | 5.6.0 | GP-032457 | LCS |
| GP-17 | GP-032495 | 149 | - | Spilt of Multislot Classes for HSCSD, GPRS and EGPRS. | F | 5.5.0 | 5.6.0 | GP-032495 | EGPRS |
| GP-17 | GP-032566 | 150 | - | CR 51.010-2 Correction of test numbers in section 21.3 | F | 5.5.0 | 5.6.0 | GP-032566 | GPRS |
| GP-17 | GP-032643 | 151 | - | New test cases: NACC | B | 5.5.0 | 5.6.0 | GP-032643 | GPRS |
| GP-17 | GP-032784 | 153 | 1 | Modification of applicability table in 51.010-2 due to introduction of new test cases in 51.010-1 | F | 5.5.0 | 5.6.0 | GP-032784 | GSM |
| GP-17 | GP-032779 | 154 | - | Removal of test case 26.8.1.3.3.3 Incoming call / U9 mobile terminating call confirmed / termination requested by the user | F | 5.5.0 | 5.6.0 | GP-032779 | TEI |
| GP-18 | GP-040008 | 155 | - | New NC2 testcases | F | 5.6.0 | 5.7.0 | GP-040008 | GPRS |
| GP-18 | GP-040072 | 156 | - | 51.010-2 New NC2 testcases added in section 42.4.8.4 | F | 5.6.0 | 5.7.0 | GP-040072 | GPRS |
| GP-18 | GP-040509 | 157 | 1 | Addition of test cases for Intersystem Change | B | 5.6.0 | 5.7.0 | GP-040509 | Intersystem Change |
| GP-18 | GP-040504 | 158 | 1 | Removal of AMR C/I tests from section 26.16 | F | 5.6.0 | 5.7.0 | GP-040504 | AMR |
| GP-18 | GP-040496 | 159 | 1 | New section 20 NC2 test cases | F | 5.6.0 | 5.7.0 | GP-040496 | GPRS NC2 |
| GP-18 | GP-040148 | 160 | - | Correction of applicability for clauses 20.22.30.x. | F | 5.6.0 | 5.7.0 | GP-040148 | GPRS |
| GP-18 | GP-040155 | 161 | - | Change of applicability of 7 SM test cases in | F | 5.6.0 | 5.7.0 | GP-040155 | GPRS |

| Change history | | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|--------|--------|-----------|-----------------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| | | | | clauses 45.x. | | | | | | |
| GP-18 | GP-040176 | 162 | - | CR 51.010-2 Removal of test cases 20.22.21 and 44.2.8.2 | F | 5.6.0 | 5.7.0 | GP-040176 | GPRS | |
| GP-18 | GP-040202 | 163 | - | PICS/PIXIT missing for Extended Uplink TBF | B | 5.6.0 | 5.7.0 | GP-040202 | Extended Uplink TBF | |
| GP-18 | GP-040548 | 164 | 3 | New test case: L_level reporting New test case: Coding Scheme adaptation while the MS is in extended Uplink mode New test case: Modulation and Coding Scheme adaptation while the MS is in extended Uplink | F | 5.6.0 | 5.7.0 | GP-040548 | GPRS | |
| GP-18 | GP-040513 | 165 | 1 | CR 51.010-2 Section 45 applicability restrictions for three test cases | F | 5.6.0 | 5.7.0 | GP-040513 | GPRS | |
| GP-19 | GP-041174 | 166 | 2 | New PICS/PIXIT, conditions and Test cases for NITZ/GPRS. | F | 5.7.0 | 5.8.0 | GP-041174 | GPRS | |
| GP-19 | GP-041173 | 167 | 1 | Changes in applicability table for AMR RF testcases | F | 5.7.0 | 5.8.0 | GP-041173 | GSM | |
| GP-19 | GP-041116 | 168 | 1 | Removal of 42.3.1.1.2 and 52.3.1.1.2 | F | 5.7.0 | 5.8.0 | GP-041116 | TEI | |
| GP-19 | GP-041170 | 170 | 1 | Split Inter-System Handover high data rate test cases in keeping with 34.123-1CR727 (T1-040406) | F | 5.7.0 | 5.8.0 | GP-041170 | Inter System Handover | |
| GP-19 | GP-040688 | 171 | - | Modification of Applicability Table for testcase 53.1.2.19 | F | 5.7.0 | 5.8.0 | GP-040688 | GPRS | |
| GP-19 | GP-040694 | 172 | - | New test case for Intersystem Change and Integrity Protection | B | 5.7.0 | 5.8.0 | GP-040694 | Intersystem Change | |
| GP-19 | GP-040734 | 173 | - | Correction of applicability table for TCs 20.22.8, 20.22.9, 42.1.2.1.8.2.2, 42.1.2.1.9.3 | F | 5.7.0 | 5.8.0 | GP-040734 | GPRS | |
| GP-19 | GP-040735 | 174 | - | PICS parameters for concatenated SMS required | B | 5.7.0 | 5.8.0 | GP-040735 | GPRS | |
| GP-19 | GP-040865 | 175 | - | Addition of supported power classes for GSM 850 terminal equipment | F | 5.7.0 | 5.8.0 | GP-040865 | TEI | |
| GP-19 | GP-040997 | 176 | - | Update of applicability of test case 46.2.2.4.2 | F | 5.7.0 | 5.8.0 | GP-040997 | GPRS | |
| GP-19 | GP-041032 | 177 | - | Changing the name of the testcase 42.7.2 in the applicability table. | F | 5.7.0 | 5.8.0 | GP-041032 | GPRS | |
| GP-19 | GP-041189 | 179 | | Deletion of TC 31.1.4.2 from 51.010-2 | F | 5.7.0 | 5.8.0 | GP-041189 | GSM | |
| | | | | Addition of missing v5.8.0 history | | 5.8.0 | 5.8.1 | | | |
| GP-20 | GP-041638 | 180 | 1 | Correction of various Multislot Selection Expressions in Annex B, Table B.1 | F | 5.8.1 | 5.9.0 | | GPRS, EDGE | |
| GP-20 | GP-041237 | 181 | - | Part 2 : Addition of New NITZ TC 44.2.9.1.3 | F | 5.8.0 | 5.9.0 | | GPRS | |
| GP-20 | GP-041308 | 183 | - | 51.010-2: Addition of new Extended UL TBF | B | 5.8.0 | 5.9.0 | | GPRS | |
| GP-20 | GP-041338 | 184 | - | CR 051.010-2-184 Modification to Applicability Table due to addition of new Extended Uplink testcases in 51.010-1 | F | 5.8.0 | 5.9.0 | | GPRS | |
| GP-20 | GP-041416 | 185 | - | Removal of reference to 26.16.9.12 | F | 5.8.0 | 5.9.0 | | GSM | |
| GP-20 | GP-041649 | 189 | - | Addition of two new test cases: 'Network Control PEMR / Packet Cell Change Order' and 'Network Control PEMR / Packet Enhanced Measurement Report / Measurement reporting with PBCCH / Invalid BSIC' | B | 5.8.0 | 5.9.0 | | PEMR | |
| GP-21 | GP-041750 | 190 | - | Addition of supported power classes for 8-PSK terminal equipment. | F | 5.9.0 | 5.10.0 | GP-041750 | EGPRS | |
| GP-21 | GP-041998 | 191 | - | CR 51.010-2 PICS parameters for band interworking | B | 5.9.0 | 5.10.0 | GP-041998 | GPRS | |
| GP-21 | GP-041774 | 192 | - | 51.010-2: Addition of new Inter-RAT Cell Change Order / Failure cases | B | 5.9.0 | 5.10.0 | GP-041774 | GPRS | |
| GP-21 | GP-041901 | 193 | - | CR 51.010-2 Addition of 4 new extended uplink TBF test cases to Table B.1: "Applicability of tests". | F | 5.9.0 | 5.10.0 | GP-041901 | GPRS/EGPRS | |
| GP-21 | GP-041902 | 194 | - | CR 51.010-2 Section 41.5.1.1.2.3.5 Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Incorrect Allocation – applicable DTM Multislot class extend | B | 5.9.0 | 5.10.0 | GP-041902 | DTM | |
| GP-21 | GP-041903 | 195 | - | CR 51.010-2 Correction to applicability table for TC 53.1.2.19. | F | 5.9.0 | 5.10.0 | GP-041903 | GPRS | |
| GP-21 | GP-042157 | 196 | - | 51.010-2: Removal of 20.22.28 | B | 5.9.0 | 5.10.0 | GP-042157 | GPRS | |
| GP-22 | GP-042300 | 197 | - | Correction to Table B.1: Applicability of tests | F | 5.10.0 | 5.11.0 | | Phase 2 | |
| GP-22 | GP-042794 | 199 | 1 | Deletion of TC 20.22.25, TC 20.22.24 | F | 5.10.0 | 5.11.0 | | GPRS | |
| GP-22 | GP-042713 | 200 | 1 | Addition of PICS/PIXIT item for 14 and 21 series tests | F | 5.10.0 | 5.11.0 | | AMR | |

| Change history | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|--------|--------|-----------|--------------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| GP-22 | GP-042815 | 201 | 1 | A.4.8 - Addition of new PICS parameter | F | 5.10.0 | 5.11.0 | | GPRS |
| GP-22 | GP-042419 | 202 | - | Change of title on TC 26.16.9.9 | F | 5.10.0 | 5.11.0 | | AMR |
| GP-22 | GP-042423 | 203 | - | Title of TC 41.5.1.2.2 changed | F | 5.10.0 | 5.11.0 | | DTM |
| GP-22 | GP-042443 | 206 | - | Applicability of the individual test - 41.5.1.1.2.3.5 - Correction of Condition C308 | F | 5.10.0 | 5.11.0 | | GPRS |
| GP-22 | GP-042793 | 207 | 1 | Addition of test cases for DTM/EGPRS | C | 5.10.0 | 5.11.0 | | DTM |
| GP-22 | GP-042816 | 208 | 2 | Addition of a new test case for USFs decoding by a MS in GPRS TBF mode when the USFs are assigned with EGPRS RLC/MAC blocks coded with MCS-1 to MCS-4. | B | 5.10.0 | 5.11.0 | | GPRS |
| GP-22 | GP-042915 | 209 | 1 | Creation of 51.010-2 REL-6: Merging of REL-5, REL-4, R99 etc. test specifications (Foreword, clause 1 and clause 2) | F | 5.10.0 | 6.0.0 | GP-042915 | TEI |
| GP-23 | GP-050043 | 210 | - | Correction to Tables A.1, B.1 - DTM/GPRS Multislot Class 11, Condition C308 and Applicability of Testcase 57.2.1 | F | 6.0.0 | 6.1.0 | GP-050043 | DTM |
| GP-23 | GP-050093 | 211 | - | Corrections in the testcase applicability table. | F | 6.0.0 | 6.1.0 | GP-050093 | GPRS |
| GP-23 | GP-050181 | 213 | - | Annex B - Removal of testcase 34.4.5 | F | 6.0.0 | 6.1.0 | GP-050181 | GPRS |
| GP-23 | GP-050551 | 218 | 1 | Section A.4.8 addition of PICSs to specify support of header compression algorithm types | F | 6.0.0 | 6.1.0 | GP-050551 | GPRS |
| GP-23 | GP-050187 | 219 | - | Annex B - Modification of C327 | F | 6.0.0 | 6.1.0 | GP-050187 | AMR |
| GP-23 | GP-050227 | 221 | - | Correction to applicability condition C235 | F | 6.0.0 | 6.1.0 | GP-050227 | GPRS |
| GP-23 | GP-050234 | 222 | - | DARP Speech bearer tests / TCH/AFS / DTS-1 (new test) | F | 6.0.0 | 6.1.0 | GP-050234 | DARP |
| GP-23 | GP-050237 | 223 | - | Addition of PICS for GPRS | F | 6.0.0 | 6.1.0 | GP-050237 | GPRS |
| GP-23 | GP-050239 | 224 | - | Cell Reselection based on C32 - Cell Reselction on CCCH - PBCCH not present | F | 6.0.0 | 6.1.0 | GP-050239 | GPRS |
| GP-23 | GP-050507 | 225 | 2 | Applicability of RX Qual Test Cases 21.3.1, 21.3.2, 21.4.1 | F | 6.0.0 | 6.1.0 | GP-050507 | RX Qual Test Cases |
| GP-23 | GP-050025 | 226 | - | Removal of the TC 42.4.4.4 - Part 2 | F | 6.0.0 | 6.1.0 | GP-050025 | GPRS |
| GP-23 | GP-050500 | 227 | 1 | Correction to part 2 to include missing TCs in table B.1 | F | 6.0.0 | 6.1.0 | GP-050500 | TEI6 |
| GP-23 | GP-050478 | 228 | - | Differentiation of Single/Multi slot DTM test cases. | C | 6.0.0 | 6.1.0 | GP-050478 | DTM |
| GP-24 | GP-050614 | 229 | - | Annex B, Table B.1: Applicability for 46.1.2.7.2 corrected | F | 6.1.0 | 6.2.0 | GP-050614 | GPRS |
| GP-24 | GP-051069 | 230 | 1 | 14.11.1.1 DARP Speech bearer tests / TCH/FS / DTS-1 (new test) | F | 6.1.0 | 6.2.0 | GP-051069 | DARP |
| GP-24 | GP-051070 | 231 | 1 | 21.3.6 Signal Quality under static conditions - TCH/AHS DTX On (new test) | F | 6.1.0 | 6.2.0 | GP-051070 | DARP |
| GP-24 | GP-050637 | 232 | - | Addition of PICS value for test case 46.1.2.2.2.4 | F | 6.1.0 | 6.2.0 | GP-050637 | GPRS |
| GP-24 | GP-050638 | 233 | - | Test case 47.3.1.1 missing | F | 6.1.0 | 6.2.0 | GP-050638 | DTM |
| GP-24 | GP-051076 | 234 | 2 | Addition of new GPRS DARP test cases | B | 6.1.0 | 6.2.0 | GP-051076 | DARP |
| GP-24 | GP-050653 | 235 | - | 20.22.14 - Cell Reselection in case Cell reselection occurred in the previous 15 s | F | 6.1.0 | 6.2.0 | GP-050653 | GPRS |
| GP-24 | GP-050654 | 236 | - | 42.4.4.5 - New TC for Rel-6 | F | 6.1.0 | 6.2.0 | GP-050654 | GPRS |
| GP-24 | GP-050657 | 238 | - | Reinsert applicability for TC 47.3.1.1 in table B.1 | F | 6.1.0 | 6.2.0 | GP-050657 | DTM |
| GP-24 | GP-051105 | 239 | 3 | Additions in table A1 A2 and B1 for Extended dynamic allocation | F | 6.1.0 | 6.2.0 | GP-051105 | GPRS |
| GP-24 | GP-050668 | 240 | - | 51.010-2 - Miscellaneous inconsistencies wrt 51.010-1 | F | 6.1.0 | 6.2.0 | GP-050668 | TEI |
| GP-24 | GP-051082 | 241 | 1 | 51.010 -2 Corrections to the Test case Applicability Table. | F | 6.1.0 | 6.2.0 | GP-051082 | GPRS |
| GP-24 | GP-050688 | 242 | - | A4.8, Annex B DARP release applicability | F | 6.1.0 | 6.2.0 | GP-050688 | DARP |
| GP-24 | GP-051084 | 243 | 2 | Annex B new DARP tests TCH/AFS and TCH/AHS | F | 6.1.0 | 6.2.0 | GP-051084 | DARP |
| GP-24 | GP-051072 | 244 | 1 | Annex B 14.4.16 change applicability due to new DARP tests | F | 6.1.0 | 6.2.0 | GP-051072 | DARP |
| GP-24 | GP-050711 | 245 | - | CR 51.010-2 Correction in Table A.26.4 Display Text | F | 6.1.0 | 6.2.0 | GP-050711 | GSM |
| GP-24 | GP-050712 | 246 | - | CR 51.010-2 Annex B Applicability of the individual test | F | 6.1.0 | 6.2.0 | GP-050712 | GSM |
| GP-24 | GP-051078 | 247 | 1 | CR 051.010-2 Applicability table Annex B changed for 41.5.1.1.2.3.4 and 42.6.1. | F | 6.1.0 | 6.2.0 | GP-051078 | GPRS |
| GP-24 | GP-050800 | 248 | - | CR 51.010-2-248 Section 41.5.1.1.2.3.4 - | F | 6.1.0 | 6.2.0 | GP-050800 | - |

| Change history | | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|-------|-------|-----------|-----------------------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| | | | | Uplink TBF establishment with reallocation of CS resources / Abnormal case / Multislot class violation / Singleslot allocation – Applicability changed | | | | | | |
| GP-24 | GP-050833 | 249 | - | CR 51.010-2 Removal of A-GPS NI-LR test cases on SDCCCH | F | 6.1.0 | 6.2.0 | GP-050833 | TEI | |
| GP-24 | GP-050835 | 250 | - | CR 51.010-2 New A-GPS NI-LR emergency call test cases without SIM inserted. | F | 6.1.0 | 6.2.0 | GP-050835 | TEI | |
| GP-24 | GP-050910 | 251 | - | CR 51.010-2 Table B.1: Applicability of tests The Mnemonic A.25/26 (TSPC_Addinfo_CCprotocol_oneBC) is wrongly named in twelve clauses of Table B.1 | F | 6.1.0 | 6.2.0 | GP-050910 | GPRS | |
| GP-24 | GP-051079 | 252 | 1 | 51010-2: Changes in the condition of the testcase 47.1.4 | F | 6.1.0 | 6.2.0 | GP-051079 | GPRS | |
| GP-24 | GP-051096 | 253 | 1 | Table B.1: Correction of applicability for a mobile terminal supporting card application | F | 6.1.0 | 6.2.0 | GP-051096 | GERAN | |
| GP-24 | GP-051074 | 254 | 1 | CR 51.010-2-254 rev 1 Annex B 14.11.4 Change to 'Applicability of individual test' due to a new DARP test case | F | 6.1.0 | 6.2.0 | GP-051074 | DARP | |
| GP-24 | GP-051075 | 255 | - | CR 51.010-2-255 Annex B 14.11.4 Change to Application | F | 6.1.0 | 6.2.0 | GP-051075 | DARP | |
| GP-25 | GP-051193 | 258 | - | Editorial correction to Annex B, underline in table | D | 6.2.0 | 6.3.0 | GP-051193 | TEI | |
| GP-25 | GP-051196 | 259 | - | Splitting of Test Case 27.10 in Applicability Table B.1 | F | 6.2.0 | 6.3.0 | GP-051196 | Phase 2 | |
| GP-25 | GP-051209 | 263 | - | CR 51.010-2 Section A.4.9.1 SIM Application Toolkit Mechanism Applicability Tables Conflict | F | 6.2.0 | 6.3.0 | GP-051209 | GPRS | |
| GP-25 | GP-051735 | 264 | 1 | Additions in table B1 for Extended dynamic allocation | F | 6.2.0 | 6.3.0 | GP-051735 | GPRS | |
| GP-25 | GP-051215 | 265 | - | Corrections in Table B.1 | F | 6.2.0 | 6.3.0 | GP-051215 | GSM | |
| GP-25 | GP-051222 | 266 | - | Applicability for 26.17.2 - Adaptive Multi Rate Signalling - 8PSK/ Inband Signalling, Uplink Codec Adaptation (New TC) | F | 6.2.0 | 6.3.0 | GP-051222 | 8PSK-AH | |
| GP-25 | GP-051237 | 267 | - | Applicability for 14.2.21 DARP Reference sensitivity - O-TCH/AHS (new) | F | 6.2.0 | 6.3.0 | GP-051237 | 8PSK-AH | |
| GP-25 | GP-051742 | 268 | 4 | New PICS/PIXIT for Clause 83: PS Domain Procedures | B | 6.2.1 | 6.3.0 | GP-051742 | GAN | |
| GP-25 | GP-051261 | 269 | - | Annex B, Table B.1: Conditions C337/C338 corrected for test cases 41.3.6.9, 41.3.6.10, 51.3.6.9 and 51.3.6.10 | F | 6.2.0 | 6.3.0 | GP-051261 | GPRS | |
| GP-25 | GP-051737 | 271 | 1 | Add applicability for new tests 14.10.3 and 14.10.4 | F | 6.2.0 | 6.3.0 | GP-051737 | DARP | |
| GP-25 | GP-051731 | 272 | 1 | CR 51.010-2: New 8-PSK AMR HR Signalling Test Cases | F | 6.2.0 | 6.3.0 | GP-051731 | GSM | |
| GP-25 | GP-051736 | 273 | 1 | Update of PICS to include the new TCs for EDA 42.9.2.1.4, 42.9.2.1.5, 52.9.2.1.4, 52.9.2.1.5 | F | 6.2.0 | 6.3.0 | GP-051736 | GPRS | |
| GP-25 | GP-051304 | 274 | - | Corrections in Table B.1 | F | 6.2.0 | 6.3.0 | GP-051304 | TEI-6 | |
| GP-25 | GP-051320 | 275 | - | 51010-2: Changes in the applicability of the combined procedure testcases. | F | 6.2.0 | 6.3.0 | GP-051320 | GPRS | |
| GP-25 | GP-051321 | 276 | - | 51010-2: Correction in the testcase applicability table. | F | 6.2.0 | 6.3.0 | GP-051321 | GPRS | |
| GP-25 | GP-051336 | 277 | - | Addition of new EGPRS DARP test cases | B | 6.2.0 | 6.3.0 | GP-051336 | DARP | |
| GP-25 | GP-051739 | 278 | 1 | New PICS/PIXIT for Clause 82: GAN CS Domain Procedures | B | 6.2.0 | 6.3.0 | GP-051739 | GAN | |
| GP-25 | GP-051372 | 279 | - | New PICS/PIXIT for MS-Based A-GPS: RRLP Error Handling | F | 6.2.0 | 6.3.0 | GP-051372 | TEI | |
| GP-25 | GP-051401 | 280 | - | CR 51.010-2 - Annex B - Modification of C327 | F | 6.2.0 | 6.3.0 | GP-051401 | GPRS | |
| GP-25 | GP-051456 | 281 | - | CR 51.010-2: New 8-PSK AMR HR Signalling Test Cases | F | 6.2.0 | 6.3.0 | GP-051456 | GSM | |
| GP-25 | GP-051367 | 282 | - | Correction of Conventional GPS Applicability | F | 6.2.0 | 6.3.0 | GP-051367 | TEI | |
| GP-25 | GP-051740 | 283 | 2 | New PICS/PIXIT for Clause 81: GAN Discovery and Registration Procedures | B | 6.2.0 | 6.3.0 | GP-051740 | GAN | |
| GP-26 | GP-051829 | 284 | - | Applicability for new tests 14.2.22, 14.4.19 and 14.5.1.4 | F | 6.3.0 | 6.4.0 | GP-051829 | AMRWB | |
| GP-26 | GP-052286 | 285 | 1 | New 8-PSK AMR signalling test | B | 6.3.0 | 6.4.0 | GP-052286 | GSM | |
| GP-26 | GP-052192 | 286 | 1 | Addition of test cases for Extended Dynamic Allocation | B | 6.3.0 | 6.4.0 | GP-052192 | Extended Dynamic Allocation | |
| GP-26 | GP-052287 | 287 | 1 | Missing applicability for Extended Dynamic Allocation | F | 6.3.0 | 6.4.0 | GP-052287 | Extended Dynamic Allocation | |

| Change history | | | | | | | | | |
|----------------|-----------|-----|-----|--|-----|-------|-------|-----------|--------------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| | | | | | | | | | Allocation |
| GP-26 | GP-051876 | 288 | - | 31.6.2.1 Removal of SIM during an active call | F | 6.3.0 | 6.4.0 | GP-051876 | GSM |
| GP-26 | GP-052196 | 289 | 1 | Additions in table B1 for Extended dynamic allocation | F | 6.3.0 | 6.4.0 | GP-052196 | GPRS |
| GP-26 | GP-052136 | 290 | 1 | Applicability for new test 14.4.20 | F | 6.3.0 | 6.4.0 | GP-052136 | 8PSK-AH |
| GP-26 | GP-051898 | 291 | - | Part 2 for removal of test cases 21.5, 21.6 and 21.7 | F | 6.3.0 | 6.4.0 | GP-051898 | GSM |
| GP-26 | GP-052198 | 292 | 1 | CR 51.010-2 Change of Applicabilty of Test Case 31.8.1.2.3 | F | 6.3.0 | 6.4.0 | GP-052198 | GSM |
| GP-26 | GP-052199 | 293 | 1 | CR 51.010-2 Addition of PICS/PIXIT item 'R97/98 MS Use of DST' | F | 6.3.0 | 6.4.0 | GP-052199 | GPRS |
| GP-26 | GP-051945 | 294 | - | CR 51.010-2-294 Annex B - Applicability table entries for section 80 TTY tests moved to section 90 | D | 6.3.0 | 6.4.0 | GP-051945 | GPRS |
| GP-26 | GP-051946 | 295 | - | CR 51.010-2-295 Annex B - 41.5.1.1.2.3.4 - Expanded applicability | F | 6.3.0 | 6.4.0 | GP-051946 | GPRS |
| GP-26 | GP-052201 | 296 | 1 | 51010-2: Addition of new testcases for Extended Dynamic Allocation. | B | 6.3.0 | 6.4.0 | GP-052201 | GPRS |
| GP-26 | GP-052009 | 297 | - | PICS/PIXIT added for reduced interslot dynamic range in multislot configurations | F | 6.3.0 | 6.4.0 | GP-052009 | GPRS |
| GP-26 | GP-052291 | 298 | 1 | Introduction of a new RRLP Error Handling test cases for MS-based A-GPS Clause 70.9.4.x | F | 6.3.0 | 6.4.0 | GP-052291 | TEI |
| GP-27 | GP-052351 | 299 | - | Annex B: Correction to applicability for Extended Dynamic Allocation | F | 6.4.0 | 6.5.0 | GP-052351 | EDA |
| GP-27 | GP-052835 | 301 | 1 | Applicability of 14.1.3, 14.1.4, 14.4.3 – Tests reduction (tests deleted) | F | 6.4.0 | 6.5.0 | GP-052835 | AMR |
| GP-27 | GP-052367 | 302 | - | Applicability of 14.1.6, 14.2.5, 14.2.19 – Tests reduction | F | 6.4.0 | 6.5.0 | GP-052367 | AMR |
| GP-27 | GP-052821 | 304 | 1 | Update of the Applicability for some EGPRS TC | F | 6.4.0 | 6.5.0 | GP-052821 | EGPRS |
| GP-27 | GP-052390 | 305 | - | CR 51.010-2 Correction of Table A.2 concerning Cipherring Algorith A5/2 | F | 6.4.0 | 6.5.0 | GP-052390 | GSM |
| GP-27 | GP-052437 | 306 | - | CR 51.010-2 Section 83.1.8.1 and 83.1.8.2 Removal of both Test Cases | F | 6.4.0 | 6.5.0 | GP-052437 | GPRS |
| GP-27 | GP-052840 | 307 | 1 | Introduction of new MS-Based A-GPS test cases | F | 6.4.0 | 6.5.0 | GP-052840 | TEI |
| GP-27 | GP-052456 | 308 | - | Applicability of 60.x to add GSM 850 / PCS 1900 | F | 6.4.0 | 6.5.0 | GP-052456 | Intersystem Change |
| GP-27 | GP-052467 | 310 | - | part2 test reduction, change of applicability for 13.1, 13.3 and 13.4 | F | 6.4.0 | 6.5.0 | GP-052467 | GSM |
| GP-27 | GP-052857 | 315 | - | Part2, test reduction, change of applicability for test cases 13.6, 13.7 and 13.8 | F | 6.4.0 | 6.5.0 | GP-052857 | GSM |
| GP-27 | GP-052859 | 316 | - | Removal of 20.22.23 | F | 6.4.0 | 6.5.0 | GP-052859 | GPRS |

| Change history | | | | | | | | | | |
|----------------|-----------|------|-----|---|-----|-------|-------|-----------|------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| GP-28 | GP-060433 | 317 | 2 | Annex B, Table B.1: Correcting applicability for 'Frequency and phase error' transmitter testcases 13.1 and 13.6 | F | 6.5.0 | 6.6.0 | GP-060433 | GSM | |
| GP-28 | GP-060438 | 318 | 2 | Correction of the applicability of 13.3 and 13.4 | F | 6.5.0 | 6.6.0 | GP-060438 | GSM | |
| GP-28 | GP-060439 | 320 | 1 | Update of PICS to include the new TCs 26.18.1 and 51.6.1 for dynamic ARFCN mapping | F | 6.5.0 | 6.6.0 | GP-060439 | TEI4 | |
| GP-28 | GP-060101 | 321 | - | 51010-2: Addition of new testcases for WB AMR. | B | 6.5.0 | 6.6.0 | GP-060101 | AMRWB | |
| GP-28 | GP-060440 | 322 | 1 | 51010-2: Correction to the "applicability" and "status" columns for the testcase 26.6.5.2. | F | 6.5.0 | 6.6.0 | GP-060440 | GSM | |
| GP-28 | GP-060132 | 323 | - | Wrong Status Information in Table A.2 Item 71 | F | 6.5.0 | 6.6.0 | GP-060132 | GAN | |
| GP-28 | GP-060372 | 324 | 1 | Delete A5/2 in Table A.2 and remove reference of A5/2 in Annex B | F | 6.5.0 | 6.6.0 | GP-060372 | TEI | |
| GP-28 | GP-060126 | 325 | - | 22.2 part2 test reduction, removal of test case | F | 6.5.0 | 6.6.0 | GP-060126 | GSM | |
| GP-28 | GP-060441 | 328 | 1 | Applicability of testcases 26.6.5.2-2 and 26.6.5.2-10 changed | F | 6.5.0 | 6.6.0 | GP-060441 | GSM | |
| GP-28 | GP-060442 | 329 | 1 | Removal of testcases 82.7.2.1 and 82.9.1.2 from table B1 | F | 6.5.0 | 6.6.0 | GP-060442 | TEI-6 | |
| GP-28 | GP-060282 | 331 | - | 22.3 part2 change of applicability | F | 6.5.0 | 6.6.0 | GP-060282 | GSM | |
| GP-28 | GP-060283 | 332 | - | 22.4 part2 change of applicability | F | 6.5.0 | 6.6.0 | GP-060283 | GSM | |
| GP-28 | GP-060286 | 333 | - | GAN test cases clean up 51.010-2 part | F | 6.5.0 | 6.6.0 | GP-060286 | TEI6 | |
| GP-28 | GP-060351 | 334 | - | New test case to test removal of algorithm A5/2 from terminals | F | 6.5.0 | 6.6.0 | GP-060351 | TEI 6 | |
| GP-28 | GP-060389 | 337 | - | Applicability changes | F | 6.5.0 | 6.6.0 | GP-060389 | GPRS/EGPRS | |
| GP-28 | GP-060426 | 338 | - | Remove reference of A5/2 in section 39 | F | 6.5.0 | 6.6.0 | GP-060426 | TEI | |
| GP-28 | GP-060429 | 339 | - | Creation of 51.010-2 REL-7 | F | 6.5.0 | 7.0.0 | GP-060429 | TEI | |
| GP-28 | GP-060430 | 340 | - | Creation of 51.010-2 REL-7: Merging of REL-5, REL-4, R99 etc. test specifications (Foreword, clause 1 and clause 2) | F | 6.5.0 | 7.0.0 | GP-060430 | TEI | |
| GP-29 | GP-060498 | 341 | - | 81.2.3.6, invalid GANC | F | 7.0.0 | 7.1.0 | GP-060498 | GAAL-CT | |
| GP-29 | GP-060913 | 342 | 1 | 26.6.7.2 Applicability corrected | F | 7.0.0 | 7.1.0 | GP-060913 | GPRS | |
| GP-29 | GP-060919 | 344 | 2 | 31.1.5.* Introduction of Calling Name Presentation Testcases | F | 7.0.0 | 7.1.0 | GP-060919 | TEI | |
| GP-29 | GP-060579 | 350 | - | Table B.1, corrections to the previous changes in relation to test case reductions | F | 7.0.0 | 7.1.0 | GP-060579 | GSM | |
| GP-29 | GP-060564 | 352 | - | New test case 81.1.3.7 for GAN registration | F | 7.0.0 | 7.1.0 | GP-060564 | TEI | |
| GP-29 | GP-060884 | 353 | 1 | 14.1.1.1 Change of applicability for MS not supporting AMR speech Codec | F | 7.0.0 | 7.1.0 | GP-060884 | TEI7 | |
| GP-29 | GP-060885 | 354 | 1 | 14.1.1.2 Change of applicability for MS not supporting AMR speech Codec | F | 7.0.0 | 7.1.0 | GP-060885 | TEI7 | |
| GP-29 | GP-060886 | 355 | 1 | 14.5.1.1 Change of applicability for MS not supporting AMR speech Codec | F | 7.0.0 | 7.1.0 | GP-060886 | TEI7 | |
| GP-29 | GP-060614 | 358 | - | 51.010-2: New testcase 8PSK_MEAN_BEP Measurement for PDTCH | F | 7.0.0 | 7.1.0 | GP-060614 | TEI-7 | |
| GP-29 | GP-060622 | 359 | - | Delete 'Reserved for future use' in 51.010-2 | F | 7.0.0 | 7.1.0 | GP-060622 | TEI | |
| GP-29 | GP-060944 | 360 | 1 | 51.010-2 Addition of new test cases for WB AMR | F | 7.0.0 | 7.1.0 | GP-060944 | GAMRWB | |
| GP-29 | GP-060914 | 361 | 1 | New test case sequence to test support of algorithm A5/3 | F | 7.0.0 | 7.1.0 | GP-060914 | TEI7 | |
| GP-29 | GP-060918 | 362 | - | 26.6.3.9 Introduction of Enhanced Measurement Report Testcase | F | 7.0.0 | 7.1.0 | GP-060918 | TEI | |
| GP-29 | GP-060514 | 345 | - | Table A.1b: 'MS Feature Release Supported' is not up-to-date | F | 7.0.0 | 7.1.0 | GP-060514 | TEI7 | |
| GP-29 | GP-060515 | 346 | - | Table B.1: Inconsistent test sequences between 51.010-1 and 51.010-2 for SIM testcases | F | 7.0.0 | 7.1.0 | GP-060515 | TEI7 | |
| GP-29 | GP-060917 | 347 | 1 | Table B.1: Inconsistent applicabilities between 51.010-1 and 51.010-2 for some EDGE testcases | F | 7.0.0 | 7.1.0 | GP-060917 | EGPRS | |
| GP-29 | GP-060517 | 348 | - | Table B.1: Inconsistent applicabilities between 51.010-1 and 51.010-2 for some GPRS testcases | F | 7.0.0 | 7.1.0 | GP-060517 | GPRS | |
| GP-29 | GP-060920 | 349 | 1 | Update of some GPRS tests applicability | F | 7.0.0 | 7.1.0 | GP-060920 | GPRS | |
| GP-29 | GP-060603 | 356 | - | 51.010-2 Addition of new test cases for WB AMR | F | 7.0.0 | 7.1.0 | GP-060603 | GAMRWB | |
| GP-30 | GP-060999 | 0363 | - | GMSK_MEAN_BEP testcase part 2 | F | 7.1.0 | 7.2.0 | GP-060999 | TEI-7 | |
| GP-30 | GP-061027 | 0364 | - | Addition of AMR WB signalling tests | B | 7.1.0 | 7.2.0 | GP-061027 | GAMRWB | |
| GP-30 | GP-061028 | 0365 | - | Correction to speech version for AMR WB | F | 7.1.0 | 7.2.0 | GP-061028 | GAMRWB | |
| GP-30 | GP-061041 | 366 | - | Addition of new WB-AMR O-TCH/WHS | B | 7.1.0 | 7.2.0 | GP-061041 | AMRWB | |

| Change history | | | | | | | | | | |
|----------------|-----------|------|-----|--|-----|-------|-------|-----------|----------------|--|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item | |
| | | | | testcases | | | | | | |
| GP-30 | GP-061050 | 0367 | - | Table B.1: Removal of testcase 83.2.1.2 | F | 7.1.0 | 7.2.0 | GP-061050 | GAN | |
| GP-30 | GP-061051 | 0368 | - | Table B.1: Removal of PICS 'Support of one PDP Context Activation' from applicabilities | F | 7.1.0 | 7.2.0 | GP-061051 | GPRS | |
| GP-30 | GP-061383 | 0369 | 1 | Addition of GSM 710 and T-GSM 810 Bands to selection expressions for InterSystem testcases | F | 7.1.0 | 7.2.0 | GP-061383 | TGSM810-MStest | |
| GP-30 | GP-061096 | 0371 | - | 42.2.1.x – Remove erroneous entries from applicability table | F | 7.1.0 | 7.2.0 | GP-061096 | TEI7 | |
| GP-30 | GP-061127 | 0373 | - | 26.6.3.10 Introduction of Enhanced Measurement Report Testcase | F | 7.1.0 | 7.2.0 | GP-061127 | TEI | |
| GP-30 | GP-061385 | 0374 | 1 | DTM/EGPRS Multislot Class 11 PICS is missing | F | 7.1.0 | 7.2.0 | GP-061385 | TEI | |
| GP-30 | GP-061184 | 376 | - | 14.1.1.1 and 14.1.1.2 – AMR Loop Back Dependent Test Case Applicability | F | 7.1.0 | 7.2.0 | GP-061184 | TEI7 | |
| GP-30 | GP-061185 | 377 | - | 14.5.1.1- AMR Loop Back Dependent Test Case Applicability | F | 7.1.0 | 7.2.0 | GP-061185 | TEI7 | |
| GP-30 | GP-061187 | 0378 | - | Correction to Conventional GPS Test Case Applicability | F | 7.1.0 | 7.2.0 | GP-061187 | TEI | |
| GP-30 | GP-061370 | 0380 | - | Adding of Specific TC's PICS/PIXIT column to Table B.1 | F | 7.1.0 | 7.2.0 | GP-061370 | TEI | |
| GP-31 | GP-061831 | 0383 | 1 | Introduction of new test on Variable Bitmap | B | 7.2.0 | 7.3.0 | GP-061831 | TEI | |
| GP-31 | GP-061826 | 0385 | 1 | 51.010-2 Addition of New Test Cases for WB AMR | F | 7.2.0 | 7.3.0 | GP-061826 | WBAMR-MStest | |
| GP-31 | GP-061842 | 0386 | 1 | Assorted Typographical errors | F | 7.2.0 | 7.3.0 | GP-061842 | TEI | |
| GP-31 | GP-061568 | 0387 | - | 28.4 – Correction of applicability | F | 7.2.0 | 7.3.0 | GP-061568 | TEI | |
| GP-31 | GP-061845 | 0388 | 1 | Correction of Applicability Condition C53 of 14.5.2, 14.6.2, 14.7.2, and 14.8.2 | F | 7.2.0 | 7.3.0 | GP-061845 | TEI7 | |
| GP-31 | GP-061577 | 0389 | - | Incorrect Boolean Expressions within C393 and C394 in Table B.1 | F | 7.2.0 | 7.3.0 | GP-061577 | TEI7 | |
| GP-31 | GP-061618 | 0390 | - | Addition of New WB-AMR test cases 14.4.29 and 14.10.8 to Table B.1 | F | 7.2.0 | 7.3.0 | GP-061618 | WBAMR-MSTEST | |
| GP-31 | GP-061834 | 0392 | 1 | 34.2.3 – Applicability of the Test Case modified | F | 7.2.0 | 7.3.0 | GP-061834 | TEI | |
| GP-31 | GP-061844 | 0393 | 2 | 44.2.11 Introduction of Cell Notification Test Cases | F | 7.2.0 | 7.3.0 | GP-061844 | TEI | |
| GP-31 | GP-061813 | 0395 | - | AP#30.15 To remove not allowed characters used in mnemonics | F | 7.2.0 | 7.3.0 | GP-061813 | TEI | |
| GP-31 | GP-061830 | 0396 | - | Modify 51.010-2 to reflect the decision on use of PICS/PIXIT in 51.010 | F | 7.2.0 | 7.3.0 | GP-061830 | TEI | |
| GP-32 | GP-061932 | 0397 | - | Annex B - 14.10.9 Performance of the Codec Mode Request Generation – TCH/WFS – improved RX (new test) | F | 7.3.0 | 7.4.0 | GP-061932 | WBAMR-MStest | |
| GP-32 | GP-061935 | 0398 | - | Annex B - 26.7.5.2 Repeated FACCH testing added to existing test | F | 7.3.0 | 7.4.0 | GP-061935 | TEI | |
| GP-32 | GP-061936 | 0399 | - | Annex A, B – Adhock corrections and clarifications resulting from PICS/PIXIT clean-up of 26.17.x, 26.18.x, 26.19.x | F | 7.3.0 | 7.4.0 | GP-061936 | TEI | |
| GP-32 | GP-061938 | 0400 | - | Annex B: 26.16.x. PICS/PIXIT clean-up | F | 7.3.0 | 7.4.0 | GP-061938 | TEI | |
| GP-32 | GP-061940 | 0401 | - | Annex B: 26.17.x, 26.18.x, 26.19.x PICS/PIXIT clean-up | F | 7.3.0 | 7.4.0 | GP-061940 | TEI | |
| GP-32 | GP-061946 | 0402 | - | PICS/PIXIT clean up | F | 7.3.0 | 7.4.0 | GP-061946 | TEI7 | |
| GP-32 | GP-062425 | 0403 | 3 | 2G/3G test case redundancy | F | 7.3.0 | 7.4.0 | GP-062425 | TEI7 | |
| GP-32 | GP-062423 | 0405 | 1 | Missing PICS for A-GPS | F | 7.3.0 | 7.4.0 | GP-062423 | TEI7 | |
| GP-32 | GP-062435 | 0406 | 1 | Addition of PICS for new A-GPS Minimum Performance Test Cases | B | 7.3.0 | 7.4.0 | GP-062435 | GAGR | |
| GP-32 | GP-062321 | 0407 | 1 | PICS Cleaning for GPRS section 44 in table B1 | F | 7.3.0 | 7.4.0 | GP-062321 | TEI | |
| GP-32 | GP-062322 | 0408 | 1 | PICS Cleaning for GPRS section 45 in table B1 | F | 7.3.0 | 7.4.0 | GP-062322 | TEI | |
| GP-32 | GP-062331 | 0409 | 1 | PICS Cleaning for GPRS section 46 in table B1 | F | 7.3.0 | 7.4.0 | GP-062331 | TEI | |
| GP-32 | GP-061984 | 0410 | - | Update of Aplicability for some GPRS tests with a CS call | F | 7.3.0 | 7.4.0 | GP-061984 | TEI | |
| GP-32 | GP-062424 | 0411 | 1 | 26.9.6.1.1 – Addition of new PICS related to Emergency number & modification of Specific PICS | F | 7.3.0 | 7.4.0 | GP-062424 | TEI | |
| GP-32 | GP-061987 | 0413 | - | 26.6.1.1 – Modification to deal with Dual_Rate MS | F | 7.3.0 | 7.4.0 | GP-061987 | TEI | |
| GP-32 | GP-062433 | 0414 | 2 | Correction to the applicability of TCs 83.1.4.2 and 83.4.1.1 | F | 7.3.0 | 7.4.0 | GP-062433 | TEI | |

| Change history | | | | | | | | | |
|----------------|-----------|------|-----|--|-----|-------|-------|-----------|--------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| GP-32 | GP-062323 | 0415 | 2 | TCs 80-90: PICS/PIXIT Clean-Up | F | 7.3.0 | 7.4.0 | GP-062323 | TEI |
| GP-32 | GP-062330 | 0416 | 1 | Introduction of GEA2 and GEA3 encryption | F | 7.3.0 | 7.4.0 | GP-062330 | TEI |
| GP-32 | GP-062050 | 0417 | - | Removal of not allowed characters used in mnemonics | F | 7.3.0 | 7.4.0 | GP-062050 | TEI |
| GP-32 | GP-062341 | 0418 | 1 | Sections 11-13: PICS/PIXIT Clean-Up | F | 7.3.0 | 7.4.0 | GP-062341 | TEI |
| GP-32 | GP-062427 | 0419 | 1 | Section 14: PICS/PIXIT Clean-Up | F | 7.3.0 | 7.4.0 | GP-062427 | TEI |
| GP-32 | GP-062428 | 0420 | 1 | Sections 15-20: PICS/PIXIT Clean-Up | F | 7.3.0 | 7.4.0 | GP-062428 | TEI |
| GP-32 | GP-062429 | 0421 | 1 | Sections 21-25: PICS/PIXIT Clean-Up | F | 7.3.0 | 7.4.0 | GP-062429 | TEI |
| GP-32 | GP-062337 | 0422 | 1 | PICS/PIXIT and Band Dependency modifications in 33.x | F | 7.3.0 | 7.4.0 | GP-062337 | TEI7 |
| GP-32 | GP-062336 | 0423 | 1 | PICS/PIXIT and Band Dependency modifications in 34.x | F | 7.3.0 | 7.4.0 | GP-062336 | TEI7 |
| GP-32 | GP-062059 | 0424 | - | 27 - PICS/PIXIT rationalisation | F | 7.3.0 | 7.4.0 | GP-062059 | TEI |
| GP-32 | GP-062060 | 0425 | - | 28 - PICS/PIXIT rationalisation | F | 7.3.0 | 7.4.0 | GP-062060 | TEI |
| GP-32 | GP-062104 | 0428 | - | Invalid characters in mnemonics | F | 7.3.0 | 7.4.0 | GP-062104 | TEI |
| GP-32 | GP-062202 | 0429 | - | Table B.1a: Minor Corrections to Conditions | F | 7.3.0 | 7.4.0 | GP-062202 | TEI |
| GP-32 | GP-062305 | 0431 | - | Inserting 14.4.27 as Void | F | 7.3.0 | 7.4.0 | GP-062305 | WBAMR-MStest |
| GP-33 | GP-070011 | 0432 | - | Annex B: 14.4.28 Add specific PICS items | F | 7.4.0 | 7.5.0 | GP-070011 | TEI5 |
| GP-33 | GP-070012 | 0433 | - | Annex B: Invalid PICS references for A-GPS | F | 7.4.0 | 7.5.0 | GP-070012 | TEI |
| GP-33 | GP-070014 | 0434 | - | Annex B : 26.9.x PICS/PIXIT clean-up | F | 7.4.0 | 7.5.0 | GP-070014 | TEI |
| GP-33 | GP-070016 | 0435 | - | Annex B : 26.15.x PICS/PIXIT clean-up | F | 7.4.0 | 7.5.0 | GP-070016 | TEI |
| GP-33 | GP-070017 | 0436 | - | Annex B : DARP changes and reduced applicability, Annex A clean-up | F | 7.4.0 | 7.5.0 | GP-070017 | TEI |
| GP-33 | GP-070039 | 0437 | - | 26.6.x – PICS/PIXIT cleanup | F | 7.4.0 | 7.5.0 | GP-070039 | TEI7 |
| GP-33 | GP-070041 | 0438 | - | Table B.1 – Rationalise TC numbering | F | 7.4.0 | 7.5.0 | GP-070041 | TEI7 |
| GP-33 | GP-070057 | 0440 | - | Improving the specification of the applicability of testcase 22.9 | F | 7.4.0 | 7.5.0 | GP-070057 | TEI |
| GP-33 | GP-070058 | 0441 | - | Corrections to the applicability limitations of audio test cases 30.x | F | 7.4.0 | 7.5.0 | GP-070058 | TEI |
| GP-33 | GP-070060 | 0442 | - | Corrections to the applicability limitations of test case 44.2.3.1.7 | F | 7.4.0 | 7.5.0 | GP-070060 | TEI |
| GP-33 | GP-070062 | 0443 | - | Sections 26.1 to 26.5: PICS/PIXIT Clean-up | F | 7.4.0 | 7.5.0 | GP-070062 | TEI |
| GP-33 | GP-070064 | 0444 | - | Corrections to the Applicability of Testcases 11.3, 14.16.2.1, 14.18.2 and 20.4 | F | 7.4.0 | 7.5.0 | GP-070064 | TEI |
| GP-33 | GP-070065 | 0445 | - | Corrections to the Applicability of Testcase 12.1.1, 12.1.2 and 13.3.4.1 related to R-GSM | F | 7.4.0 | 7.5.0 | GP-070065 | TEI |
| GP-33 | GP-070394 | 0446 | 1 | Addition of New Repeated FACCH test cases 14.2.25 and 14.4.31 to Table B.1 | F | 7.4.0 | 7.5.0 | GP-070394 | TEI6 |
| GP-33 | GP-070070 | 0447 | - | Inserting 45.2.3 as Void | F | 7.4.0 | 7.5.0 | GP-070070 | TEI |
| GP-33 | GP-070072 | 0448 | - | PICS/PIXIT and Band Dependency modifications in 31.x | F | 7.4.0 | 7.5.0 | GP-070072 | TEI7 |
| GP-33 | GP-070397 | 0450 | 1 | Annex A25: Loop C Delay, possibility to separate HS (Half Rate) and FS (Full Rate), table A.25.1 | F | 7.4.0 | 7.5.0 | GP-070397 | TEI7 |
| GP-33 | GP-070503 | 0451 | 1 | GEAx: split of test cases | F | 7.4.0 | 7.5.0 | GP-070503 | TEI7 |
| GP-33 | GP-070083 | 0452 | - | Annex B, editorial corrections (Rel-7) | F | 7.4.0 | 7.5.0 | GP-070083 | TEI7 |
| GP-33 | GP-070504 | 0453 | 2 | PICS/PIXIT Clean-Up Section 41 Tests | F | 7.4.0 | 7.5.0 | GP-070504 | TEI |
| GP-33 | GP-070384 | 0454 | 1 | PICS/PIXIT Clean-Up Section 42 Tests | F | 7.4.0 | 7.5.0 | GP-070384 | TEI |
| GP-33 | GP-070105 | 0455 | - | PICS/PIXIT Clean-Up Section 43 Tests | F | 7.4.0 | 7.5.0 | GP-070105 | TEI |
| GP-33 | GP-070505 | 0456 | 2 | PICS/PIXIT Clean-Up Section 51 Tests | F | 7.4.0 | 7.5.0 | GP-070505 | TEI |
| GP-33 | GP-070506 | 0457 | 2 | PICS/PIXIT Clean-Up Section 52 Tests | F | 7.4.0 | 7.5.0 | GP-070506 | TEI |
| GP-33 | GP-070387 | 0458 | 1 | PICS/PIXIT Clean-Up Section 53 Tests | F | 7.4.0 | 7.5.0 | GP-070387 | TEI |
| GP-33 | GP-070088 | 0459 | - | Annex B : 26.10.x – 26.11.x PICS/PIXIT clean-up | F | 7.4.0 | 7.5.0 | GP-070088 | TEI |
| GP-33 | GP-070090 | 0460 | - | Annex B : 26.12.x PICS/PIXIT clean-up | F | 7.4.0 | 7.5.0 | GP-070090 | TEI |
| GP-33 | GP-070507 | 0461 | 1 | 22.13 and 22.14 Enhanced Power Control (EPC) timing and measurement reporting test scripts (new) | B | 7.4.0 | 7.5.0 | GP-070507 | EPC-MStest |
| GP-33 | GP-070414 | 0463 | 1 | Additional information element Tav, PICS/PIXIT added to table A.25.1 | F | 7.4.0 | 7.5.0 | GP-070414 | TEI |
| GP-33 | GP-070152 | 0465 | - | Incorrect Applicability Limitation on TC 44.2.3.1.1a in Table B.1 | F | 7.4.0 | 7.5.0 | GP-070152 | TEI7 |
| GP-33 | GP-070419 | 0467 | 1 | Annex B: Testing of lower layer failure | F | 7.4.0 | 7.5.0 | GP-070419 | GAAl-CT |
| GP-34 | GP-070900 | 0468 | - | Introduction of GAN-UTRAN, UTRAN-GAN handover test case | F | 7.5.0 | 7.6.0 | GP-070900 | TEI6 |
| GP-34 | GP-070914 | 0469 | 1 | Applicability for test cases 60.2a and 60.3a – new condition definitions | F | 7.5.0 | 7.6.0 | GP-070914 | TEI |
| GP-34 | GP-070915 | 0470 | 1 | 81.2.1.2 – Correction to test case title | D | 7.5.0 | 7.6.0 | GP-070915 | TEI6 |
| GP-34 | GP-071013 | 0472 | 1 | Addition of New Repeated SACCH test cases 14.2.26 and 14.4.32 to Table B.1 | F | 7.5.0 | 7.6.0 | GP-071013 | TEI6 |

| Change history | | | | | | | | | |
|----------------|-----------|------|-----|--|-----|-------|-------|-----------|--------------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| GP-34 | GP-070614 | 0473 | - | Additions and corrections to Annex B due to changed layout and content of Table B.1 | F | 7.5.0 | 7.6.0 | GP-070614 | TEI |
| GP-34 | GP-070615 | 0474 | - | Corrections to the Applicability of the acoustic testcases 30.x | F | 7.5.0 | 7.6.0 | GP-070615 | TEI |
| GP-34 | GP-070916 | 0475 | 1 | Corrections to the Applicability of the DARP testcases 14.10.x | F | 7.5.0 | 7.6.0 | GP-070916 | TEI |
| GP-34 | GP-070892 | 0476 | 1 | Section 26.14: PICS/PIXIT Clean-up | F | 7.5.0 | 7.6.0 | GP-070892 | TEI |
| GP-34 | GP-070619 | 0477 | - | Adding testcases 15.2 to 15.5 as void | F | 7.5.0 | 7.6.0 | GP-070619 | TEI |
| GP-34 | GP-070918 | 0478 | 1 | Annex B : Cxxx incorretly implemented on 52.1.2.1.10. | F | 7.5.0 | 7.6.0 | GP-070918 | TEI |
| GP-34 | GP-070919 | 0479 | 1 | 26.9.6.1.x : incorrect handling of half rate speech version 3 | F | 7.5.0 | 7.6.0 | GP-070919 | TEI |
| GP-34 | GP-070633 | 0480 | - | CR 51.010-2-0480 Correction to GERAN feature package 2 | F | 7.5.0 | 7.6.0 | GP-070633 | TEI5 |
| GP-34 | GP-070929 | 0481 | 4 | Introduction of Enhanced DTM Test Cases and PICS | F | 7.5.0 | 7.6.0 | GP-070929 | TEI6 |
| GP-34 | GP-070694 | 0483 | - | Correction to the applicability of testcase 15.8 | F | 7.5.0 | 7.6.0 | GP-070694 | TEI |
| GP-34 | GP-070696 | 0484 | - | Annex B: 81.1.3.3, 81.1.3.2 and 81.2.4.5 removed | F | 7.5.0 | 7.6.0 | GP-070696 | TEI |
| GP-34 | GP-070923 | 0486 | 1 | Additional information element PICS/PIXIT added to table A.25 stating RF performance sensitivity to vibration condition during testing | F | 7.5.0 | 7.6.0 | GP-070923 | TEI |
| GP-34 | GP-070872 | 0489 | - | Annex B : 26.7.x PICS/PIXIT clean-up | F | 7.5.0 | 7.6.0 | GP-070872 | TEI |
| GP-34 | GP-070899 | 0490 | - | Addition of informative Annex for GERAN/UTRAN band combinations for Inter-RAT signalling test cases | F | 7.5.0 | 7.6.0 | GP-070899 | TEI |
| GP-34 | GP-070912 | 0491 | - | Update of NITZ applicability | F | 7.5.0 | 7.6.0 | GP-070912 | TEI |
| GP-34 | GP-071019 | 0492 | - | Annex B – 26.6.23 Test of Repeated SACCH | B | 7.5.0 | 7.6.0 | GP-071019 | TEI6 |
| GP-35 | GP-071418 | 0493 | 1 | Error correction: A-GPS test case condition definitions | F | 7.6.0 | 7.7.0 | GP-071418 | TEI |
| GP-35 | GP-071429 | 0494 | 2 | Addition of New DARP phase 2 L1 test cases to Table B.1 | F | 7.6.0 | 7.7.0 | GP-071429 | TEI |
| GP-35 | GP-071124 | 0495 | - | PICS/PIXIT Clean-Up Section 26.8 | F | 7.6.0 | 7.7.0 | GP-071124 | TEI |
| GP-35 | GP-071394 | 0496 | 1 | PICS/PIXIT Clean-Up Section 26.13 | F | 7.6.0 | 7.7.0 | GP-071394 | TEI |
| GP-35 | GP-071126 | 0497 | - | Annex B : 26.9.x PICS/PIXIT corrections | F | 7.6.0 | 7.7.0 | GP-071126 | TEI |
| GP-35 | GP-071127 | 0498 | - | AMR WB: missing PIXIT for normalisation factors | F | 7.6.0 | 7.7.0 | GP-071127 | GAMRW B |
| GP-35 | GP-071410 | 0499 | 1 | Darp Ph II, new test for Reference Sensitivity | B | 7.6.0 | 7.7.0 | GP-071410 | MSRD2-MSconf |
| GP-35 | GP-071146 | 0501 | - | Various corrections to conditions in Table B.1a | F | 7.6.0 | 7.7.0 | GP-071146 | TEI |
| GP-35 | GP-071414 | 0502 | 1 | Addition of new Darp phase 2 Speech bearer test cases 14.19.1.1, 14.19.2.1, 14.19.2.2, 14.19.3.1 and 14.19.3.2, to Table B.1 | B | 7.6.0 | 7.7.0 | GP-071414 | MSRD2-MSconf |
| GP-35 | GP-071420 | 505 | 1 | Annex B: deletion of TC 20.22.26 | F | 7.6.0 | 7.7.0 | GP-071420 | TEI7 |
| GP-35 | GP-071382 | 0506 | 1 | Annex B: PICS correction for test case 20.15 | F | 7.6.0 | 7.7.0 | GP-071382 | TEI |
| GP-35 | GP-071421 | 0509 | 1 | Introduction of Enhanced DTM Test Cases | F | 7.6.0 | 7.7.0 | GP-071421 | TEI6 |
| GP-36 | GP-071579 | 0510 | - | Introduction of Enhanced DTM Test Cases | F | 7.7.0 | 7.8.0 | GP-071579 | TEI6 |
| GP-36 | GP-071599 | 0511 | - | Introduction of Enhanced DTM Test Cases | B | 7.7.0 | 7.8.0 | GP-071599 | TEI6 |
| GP-36 | GP-071594 | 0512 | - | Corrections to bearer services tables | F | 7.7.0 | 7.8.0 | GP-071594 | TEI |
| GP-36 | GP-071606 | 0513 | - | Annex B: support of basic service missing for some test cases | F | 7.7.0 | 7.8.0 | GP-071606 | TEI7 |
| GP-36 | GP-071607 | 0514 | - | Annex B: alignment of Status codes for DARP Ph II | F | 7.7.0 | 7.8.0 | GP-071607 | MSRD2-MSconf |
| GP-36 | GP-071608 | 0515 | - | Inconsistent applicablty concerning MT-LR test cases | F | 7.7.0 | 7.8.0 | GP-071608 | TEI7 |
| GP-36 | GP-071642 | 0516 | - | 31.3.1.2.2.1 – Test applicability correction | F | 7.7.0 | 7.8.0 | GP-071642 | TEI |
| GP-36 | GP-071659 | 0518 | - | Removal of PICS Item A5/36 | F | 7.7.0 | 7.8.0 | GP-071659 | TEI7 |
| GP-36 | GP-071861 | 0519 | - | Corrections to integral antenna wording in table A.25 | F | 7.7.0 | 7.8.0 | GP-071861 | TEI |
| GP-36 | GP-071862 | 0520 | - | Introduction of a new item in table A.25 for MS with a temporary antenna connector | F | 7.7.0 | 7.8.0 | GP-071862 | TEI |
| GP-36 | GP-071882 | 0521 | - | 26.5.7.3 – Addition of Specific PICS information to table B.1 | F | 7.7.0 | 7.8.0 | GP-071882 | TEI |
| GP-37 | GP-080021 | 0522 | - | Introduction of ew PS Handover TC 41.6.1.1 | F | 7.8.0 | 7.9.0 | GP-080021 | TEI |
| GP-37 | GP-080025 | 0523 | - | 26.19.5 Additionnal procedures for handover between speech version 3 and 5 | F | 7.8.0 | 7.9.0 | GP-080025 | TEI |
| GP-37 | GP-080055 | 524 | - | Testcase 26.6.3.4 not applicable for Data Only Terminals | F | 7.8.0 | 7.9.0 | GP-080055 | TEI |
| GP-37 | GP-080319 | 0526 | 1 | Corrections to applicability of MS Based | F | 7.8.0 | 7.9.0 | GP-080319 | TEI |

| Change history | | | | | | | | | |
|----------------|-----------|------|-----|---|-----|-------|-------|-----------|-----------|
| TSG # | TSG Doc | CR | Rev | Subject/Comment | Cat | Old | New | WG Doc | Work item |
| | | | | MOLR Basic Self Location Request Test Cases | | | | | |
| GP-37 | GP-080061 | 0527 | - | Annex B: PICS correction for test case 27.10-1 to 27.10-8 | F | 7.8.0 | 7.9.0 | GP-080061 | TEI |
| GP-37 | GP-080063 | 0529 | - | Annex B: Test applicability correction for test case 27.18.1.1 | F | 7.8.0 | 7.9.0 | GP-080063 | TEI |
| GP-37 | GP-080328 | 0530 | 2 | Correction to the applicability of Repeated FACCH and Repeated SACCH test cases | F | 7.8.0 | 7.9.0 | GP-080328 | TEI6 |
| GP-37 | GP-080321 | 0531 | - | 31.8.6.1 and 31.8.6.2 - Addition of Specific PICS | F | 7.8.0 | 7.9.0 | GP-080321 | TEI |

History

| Document history | | |
|-------------------------|----------------|-------------|
| V7.0.0 | January 2006 | Publication |
| V7.1.0 | May 2006 | Publication |
| V7.2.0 | July 2006 | Publication |
| V7.3.0 | September 2006 | Publication |
| V7.4.0 | December 2006 | Publication |
| V7.5.0 | March 2007 | Publication |
| V7.6.0 | June 2007 | Publication |
| V7.7.0 | October 2007 | Publication |
| V7.8.0 | January 2008 | Publication |
| V7.9.0 | April 2008 | Publication |