ETSITS 186 006-1 V3.1.1 (2017-12)



Core Network and Interoperability Testing (INT);
Originating Identification Presentation (OIP)
and Originating Identification Restriction (OIR)
using IP Multimedia (IM) Core Network (CN) subsystem;
Conformance Test Specification;
(3GPP™ Release 12);
Part 1: Protocol Implementation Conformance

Part 1: Protocol Implementation Conformance Statement (PICS)

Reference RTS/INT-00139-1

Keywords

conformance, OIP, OIR, PICS, SIP, testing

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommitteeSupportStaff.aspx

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017. All rights reserved.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intell	ectual Property Rights	4
Forev	word	4
Moda	al verbs terminology	4
Introd	duction	4
1	Scope	5
2	References	5
2.1	Normative references	
2.1	Informative references.	
3	Definitions and abbreviations	
3.1	Definitions	
3.2	Abbreviations	6
4	Conformance to this PICS pro forma specification	6
4 .0	The right to copy	
4.0 4.1	Guidance for completing the PICS pro forma	6
4.1.0	Introduction	
4.1.1	Purposes and structure	
4.1.2	Abbreviations and conventions.	
4.1.3	Instructions for completing the PICS pro forma	
4.2	Identification of the implementation	
4.2.0	Introduction	
4.2.1	Date of the statement	
4.2.2	Implementation Under Test (IUT) identification	
4.2.3	System Under Test (SUT) identification	
4.2.4	Product supplier	
4.2.5	Client (if different from product supplier)	
4.2.6	PICS contact person	
4.3	Identification of the ETSI TS 124 607	
4.3.0	Introduction	
4.4	Global statement of conformance	
4.5	Roles	11
4.6	User role	11
4.6.0	Introduction	11
4.6.1	Major capabilities	11
4.7	Network role	12
4.7.0	Introduction	12
4.7.1	Major capabilities	12
Histo	orv	13

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Core Network and Interoperability Testing (INT).

The present document is part 1 of a multi-part deliverable covering the Conformance Test Specification of Originating Identification Presentation (OIP) supplementary service and the Originating Identification Restriction (OIR) supplementary services using IP Multimedia (IM) Core Network (CN) subsystem, as identified below:

- Part 1: "Protocol Implementation Conformance Statement (PICS)";
- Part 2: "Test Suite Structure and Test Purposes (TSS&TP)";
- Part 3: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) pro forma specification".

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (PICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) pro forma of the Originating Identification Presentation (OIP) supplementary service and the Originating Identification Restriction (OIR) supplementary services, based on stage one and two of the ISDN CLIP and CLIR supplementary service defined in ETSI TS 124 607 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [4] and ETSI ETS 300 406 [2].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1]	ETSI TS 124 607 (V12.2.0): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR) using IP Multimedia (IM) Core Network (CN) subsystem; Protocol specification (3GPP TS 24.607 version 12.2.0 Release 12)".
[2]	ETSI ETS 300 406 (10-1995): "Methods for testing and Specification (MTS); Protocol and profile

- conformance testing specifications; Standardization methodology".

 [2] SO/IEC 0646-1: "Information technology". Open systems interconnection. Conformance
- [3] ISO/IEC 9646-1: "Information technology -- Open systems interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".
- [4] ISO/IEC 9646-7: "Information technology -- Open systems interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI TS 124 607 [1], ISO/IEC 9646-1 [3], ISO/IEC 9646-7 [4] and the following apply:

ICS pro forma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

NOTE: The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

Protocol ICS (PICS): ICS for an implementation or system claimed to conform to a given protocol specification

NOTE: This may contain additional information.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TS 124 607 [1] and the following apply:

CLIR	Calling Line Identification Restriction
ICS	Implementation Conformance Statement
IUT	Implementation Under Test
OIP	Originating Identification Presentation
OIR	Originating Identification Restriction
PICS	Protocol ICS
SUT	System Under Test

4 Conformance to this PICS pro forma specification

4.0 The right to copy

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the ICS pro forma in this clause so that it can be used for its intended purposes and may further publish the completed ICS.

4.1 Guidance for completing the PICS pro forma

4.1.0 Introduction

If it claims to conform to the present document, the actual PICS pro forma to be filled in by a supplier shall be technically equivalent to the text of the PICS pro forma given in clause 4, and shall preserve the numbering/naming and ordering of the pro forma items.

A PICS which conforms to the present document shall be a conforming PICS pro forma completed in accordance with the guidance for completion given in clause 4.1.

4.1.1 Purposes and structure

The purpose of this PICS pro forma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ETSI TS 124 607 [1] may provide information about the implementation in a standardized manner.

The ICS pro forma is subdivided into clauses for the following categories of information:

- guidance for completing the ICS pro forma;
- identification of the implementation;
- identification of the <reference specification type>;
- global statement of conformance;
- roles;
- user role:
 - major capabilities;
- network role:
 - major capabilities.

4.1.2 Abbreviations and conventions

The PICS pro forma contained in this clause is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [4].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is the requirement or option supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [4], are used for the status column:

- mandatory the capability is required to be supported. m
- optional the capability may be supported or not.
- qualified optional for mutually exclusive or selectable options from a set. "i" is an integer which o.i identifies an unique group of related optional items and the logic of their selection which is

defined immediately following the table.

conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of ci other optional or conditional items. "i" is an integer identifying an unique conditional status

expression which is defined immediately following the table.

Reference column

The reference column makes reference to ETSI TS 124 607 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [4], are used for the support column:

Y or y supported by the implementation.

N or n not supported by the implementation.

N/A, n/a or - no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional

status).

NOTE: As stated in ISO/IEC 9646-7 [4], support for a received PDU requires the ability to parse all valid

parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Prerequisite line

A prerequisite line takes the form: Prerequisite: cpredicate.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

4.1.3 Instructions for completing the PICS pro forma

The supplier of the implementation shall complete the PICS pro forma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause 4.1.2.

However, the tables containing in "user role" clause shall only be completed for user implementations, and the tables containing in "network role" clause shall only be completed for network implementations.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the PICS pro forma.

4.2 Identification of the implementation

4.2.0 Introduction

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

4.2.1	Date of the statement
4.2.2 IUT name:	Implementation Under Test (IUT) identification

IUT version:		
4.2.3 SUT name:	System Under Test (SUT) identification	
Hardware con	figuration:	
Operating syst	em:	
4.2.4 Name:	Product supplier	
Address:		
Telephone nur	mber:	
Facsimile num E-mail address		
Additional inf	ormation:	
4.2.5 Name:	Client (if different from product supplier)	

Telephone number:	
Facsimile number:	
E-mail address:	
Additional information:	
4.2.6 PICS contact person	
(A person to contact if there are any queries con	
	ncerning the content of the PICS)
Name:	ncerning the content of the PICS)
Name: Telephone number:	ncerning the content of the PICS)
	ncerning the content of the PICS)
Telephone number:	ncerning the content of the PICS)
Telephone number: Facsimile number:	ncerning the content of the PICS)
Telephone number: Facsimile number: E-mail address:	ncerning the content of the PICS)

4.3 Identification of the ETSLTS 124 607

4.3.0 Introduction

This PICS pro forma applies to the following standard:

ETSI TS 124 607 (V12.2.0) (2015-01) [1]: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR) using IP Multimedia (IM) Core Network (CN) subsystem; Protocol specification (3GPP TS 24.607 version 12.2.0 Release 12)".

4.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the <reference specification type> specification. Non-supported mandatory capabilities are to be identified in the ICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS pro forma.

4.5 Roles

Table 4.5.1: Roles

Item	Role	Reference	Status	Support
1	User	4.5.2.1, 4.5.2.12/[1]	0.1	
2	Network	4.5.2.4, 4.5.2.9/[1]	0.1	

o.1: It is mandatory to support at least one of these items.

Comments:

4.6 User role

4.6.0 Introduction

This clause contains the PICS pro forma tables related to the user role. They need to be completed only for user implementations:

Prerequisite: 4.5.1/1 -- user role

4.6.1 Major capabilities

Table 4.6.1: User Equipment capabilities

Item	Requirement or option	Reference	Status	Support
1	Is the implementation an originating user equipment?	4.5.2.1/[1]	0	
	Does the originating user equipment inserts P-Preferred-Identity header field?	4.5.2.1/[1]	0	
3	Is the terminating user a terminating user equipment?	4.5.2.12/[1]	0	

Comments:

4.7 Network role

4.7.0 Introduction

This clause contains the PICS pro forma tables related to the network role. They need to be completed only for network implementations:

Prerequisite: 4.5.1/2 network role

4.7.1 Major capabilities

Table 4.7.1: Network related requirements and options

Item	Requirement or option	Reference	Status	Support
	Does the Application Server serving the originating user modify the From header field to remove the identification information or set the Privacy header value to "user" if the originating user identity is restricted?	4.5.2.4/[1]	0	
	Does the Application Server serving the originating user set the From header field to the default public user identities if the received From header field does not match with one of the registered public user identities?	4.5.2.4/[1]	0	
3	Does the originating user subscribe the "no screening" special arrangement?	4.5.2.4/[1]	0	
4	Does the SUT supports the OIR service in permanent mode?	4.5.2.4/[1]	0	
5	Does the SUT supports the OIR service in temporary mode?	4.5.2.4/[1]	0	
6	Does the Application Server serving the terminating user anonymize the contents of the From header by setting it to a default non significant value if the terminating user does not subscribe the OIR service?	4.5.2.9/[1]	0	
7	Does the network serving the terminating user support the override category?	4.5.2.9/[1]	0	
8	Does the Application Server serving the terminating user removes the Privacy header value 'id' if it removes the P-Asserted-Identity or the terminating user has an override category?	4.5.2.9/[1]	0	

Comments:

History

Document history		
V1.1.1	October 2006	Publication
V2.1.1	October 2015	Publication
V3.1.1	December 2017	Publication