

ETSI TS 188 005-1 V2.1.1 (2009-02)

Technical Specification

Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Network and Service Management; Network Resource Model; Part 1: Requirements



Reference

RTS/TISPAN-08021-1-NGN-R2

Keywords

analysis, interface

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	6
3 Abbreviations	6
4 General requirements	7
4.1 Reuse of specifications	7
4.2 Granularity of Managed Objects	7
4.2.1 Motivation, remarks, or examples	7
4.2.2 Requirements	8
4.3 Inter Domain Management.....	8
4.3.1 Motivation, remarks, or examples	8
4.3.2 Requirements	8
5 NGN Managed Entities	8
5.1 Analysis of Service Layer	9
5.1.1 Common Managed Entities	9
5.1.2 The IMS	10
5.1.3 PSTN/ISDN Emulation Subsystem	11
5.1.4 IMS-based PSTN/ISDN Emulation Subsystem.....	12
5.2 Analysis of Transport Layer.....	13
5.2.1 Transfer Functions	13
5.2.2 NASS	14
5.2.3 RACS.....	15
5.3 List of NGN Managed Entities.....	16
5.3.1 Required NGN Managed Entities	16
5.3.2 Candidate NGN Managed Entities identified for further study	16
Annex A (normative): Agreed Use Cases.....	17
Annex B (informative): Candidate Use Cases.....	18
Annex C (informative): Bibliography.....	19
Annex D (informative): Change history	20
History	21

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN).

The present document is part 1 of a multi-part deliverable covering Network and Service Management; Network Resource Model, as identified below:

Part 1: "Requirements";

Part 2: "Information Service";

Part 3: "eXtensible Markup Language (XML) Schema definition".

The NRM (Network Resource Model) is part of the TISPAN Management Information Model (MIM).

1 Scope

The present document identifies the requirements for the NGN Network Resource Model (NRM).

This NRM is an information model of the NGN Resources defined in the NGN specified by ETSI TISPAN which captures the management aspects (i.e. the management view of the NGN).

Clause 4 of the present document captures the general requirements for the NRM. Clause 5 identifies the NGN subsystems and entities which are modelled in the NGN NRM. Annex A captures agreed Use Cases and annex B is an informative annex capturing proposed Use Cases.

This version of the document is based on the TISPAN Release 1 architecture and may be updated to reflect changes in subsequent releases.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TS 188 003: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); OSS requirements; OSS definition of requirements and priorities for further network management specifications for NGN".
- [2] ETSI TS 132 150: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Telecommunication management; Integration Reference Point (IRP) Concept and definitions (3GPP TS 32.150 version 6.5.0 Release 6)".
- [3] ETSI ES 282 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture Release 1".
- [4] ETSI ES 282 002: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN Emulation Sub-system (PES); Functional architecture".
- [5] ETSI ES 282 004: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture; Network Attachment Sub-System (NASS)".

- [6] ETSI ES 282 003: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control Sub-system (RACS); Functional Architecture".
- [7] ETSI ES 282 007: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IP Multimedia Subsystem (IMS); Functional architecture".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI TR 180 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Release 1; Release definition".
- [i.2] ETSI TS 182 012: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IMS-based PSTN/ISDN Emulation Subsystem; Functional architecture".

3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AF	Application Function
AGCF	Access Gateway Control Function
AGF	Access Gateway Function
AMF	Access Management Function
A-MGF	Access Media Gateway Function
A-RACF	Access Resource and Admission Control Function
ARF	Access Relay Function
ASF Type 1	Application Server Function Type 1
ASF Type 2	Application Server Function Type 2
ASF	Application Server Function
BGCF	Border Gateway Control Function
BGF	Border Gateway Function
C-BGF	Core Border Gateway Function
CLF	Connectivity session Location and repository Function
CNGCF	Customer Network Gateway Configuration Function
FQDN	Fully Qualified Domain Name
IBCF	Interconnection Border Control Function
I-BGF	Interconnection Border Gateway Function
I-CSCF	Interrogating Call Server Control Function
IMS	IP Multimedia System
ISDN	Integrated Services Digital Network
IWF	InterWorking Function
L2TF	Layer 2 Termination Function
MGCF	Media Gateway Control Function
MRFC	Multimedia Resource Function Controller
MRFP	Multimedia Resource Function Processor
NACF	Network Access Configuration Function
NASS	Network Attachment SubSystem
NAT	Network Address Translation
NGN	Next Generation Network
NRM	Network Resource Module
OSS	Operations Support Team
P-CSCF	Proxy Call Server Control Function
PDBF	Profile Data Base Function
PES	PSTN/ISDN Emulation Subsystem
PSTN	Public Switched Telephony Network

RACS	Resource Admission Control Subsystem
RCEF	Resource Control Enforcement Function
RGF	Residential Gateway Function
R-MGF	Residential Media Gateway Function
S-CSCF	Serving Call Server Control Function
SGF	Signalling Gateway Function
SLF	Subscription Locator Function
SPDF	Service Policy Decision Function
TE	Terminal Equipment
TISPAN	Telecommunications and Internet Converged Services and Protocols for Advanced Networking
TMF	TeleManagement Team
T-MGF	Trunking Media Gateway Function
UAAF	User Access Authorization Function
UE	User Equipment
UPSF	User profile Service Function

4 General requirements

The following general and high-level requirements apply for the NRM:

- NRM related requirements in TR 180 001 [i.1]. The present document provides a description of the content and capabilities of NGN Release 1 which need to be supported by the NRM.
- NRM related requirements in TS 188 003 [1]. The present document provides high level requirements for the NRM.
- The use of the IRP Methodology in TS 132 150 [2]. The present document provides the documentation structure and concept for the NRM.
- NGN Overall Functional Architecture ES 282 001 [3]. The present document identifies the subsystems and functional entities which make up the NGN.

4.1 Reuse of specifications

To avoid overlap and duplication, the Network Resource Model should import relevant definitions (e.g. Object classes, attributes, etc.) from the 3GPP, TMF, ITU-T etc. where appropriate.

4.2 Granularity of Managed Objects

This clause states requirements on the level of granularity for managed entities.

4.2.1 Motivation, remarks, or examples

Based on, (see ES 282 001 [3]), the TISPAN NGN overall architecture (see figure 2) is the starting point for decomposition of the TISPAN NGN. Entities of this overall architecture are further decomposed recursively. This decomposition is performed in three dimensions:

- Decomposition into layer entities e.g. Service Layer, Transport Layer (see figure 2), or Transport Control Sublayer (see ES 282 001 [3]). A layer need not map to a manageable entity. Therefore this kind of decomposition does not motivate a requirement.
- Decomposition into subsystems e.g. Core IMS, PSTN/ISDN Emulation Subsystem. This kind of decomposition motivates Requirement 1.
- Decomposition into functional entities e.g. User Profile Service Function, UPSF (see figure 3), Transfer functions (see figure 2). This kind of decomposition motivates Requirement 2.

4.2.2 Requirements

Requirement 1:

- Each subsystem that has manageable aspects which are agreed on the basis of documented technical analysis performed on existing TISPAN specifications or are documented within an agreed Use case for an NGN management interface shall map to one manageable model element of the NGN Network Resource Model.

Requirement 2:

- Each functional entity that has manageable aspects which are agreed on the basis of documented technical analysis performed on existing TISPAN specifications or are documented within an agreed Use case for an NGN management interface shall map to one manageable model element of the NGN Network Resource Model.

4.3 Inter Domain Management

4.3.1 Motivation, remarks, or examples

According to the NGN functional architecture (see ES 282 001 [3]), functional entities or subsystems may be distributed over network/service provider domain borders. E.g. a network attachment subsystem, an I-BGF, or a service-layer subsystem that supports nomadism may be distributed between a visited and a home network. Figure 1 is taken from ES 282 001 [3]. It illustrates this multi-domain context.




Figure 1: Example for a distributed Subsystem

4.3.2 Requirements

Requirement 1:

- The Network Resource Model shall allow management of resources which are shared between administrative domains.

5 NGN Managed Entities

ES 282 001 [3] describes the overall TISPAN NGN functional architecture, its subsystems and the relationships between them. The present document, together with the Functional Architectures of the IMS (see ES 282 007 [7]), PES (see ES 282 002 [4]), IMS based PES (see TS 182 012 [i.2]), NAS (see ES 282 004 [5]), and RACS (see ES 282 003 [6]), identifies the entities with the NGN subsystems and the relationships between them.

The requirement to manage these entities is documented in clause 4.3 (requirements A2 and A8) of TS 188 003 [1].




Figure 2: TISPAN NGN overall architecture

The NGN functional architecture is split into 2 layers, "Service Layer" and "Transport Layer". The Functional Entities which form part of the Service Layer are described in clause 5.1, the Entities which form part of the Transport Layer are described in clause 5.2.

5.1 Analysis of Service Layer

5.1.1 Common Managed Entities

The following entities are defined in ES 282 001 [3].





Figure 3: Common components overview

As a result of analysis, the following entities are required to be modelled in the NRM.

TISPAN Entity	Remark
BGCF	see note 1
MRFC	see note 1
MGCF	see note 1
I-CSCF	see note 1
S-CSCF	see note 1
P-CSCF	see note 1
NOTE 1: This entity meets Requirement 2 of clause 4.2.2 because it is well defined and it is able to generate alarms.	
NOTE 2: Modelling of interfaces (e.g. Cx, Mi, etc.) is for further study.	

5.1.3 PSTN/ISDN Emulation Subsystem

The following entities are defined in ES 282 002 [4].



NOTE: Lines inside the grey area are purely illustrative. Information flows may be through the Distributor or direct as an implementation option.

Figure 5: PES Managed Components

The inclusion of the following entities in the NRM is for further study.

TISPAN Entity	Remark
Trunk Routing	-
Customer Location	-
Access Gateway Function (AGF)	-
Residential Gateway Function (RGF)	-
Media Gateway Function	-

5.1.4 IMS-based PSTN/ISDN Emulation Subsystem

The following entities are defined in TS 182 012 [i.2].




Figure 6: IMS Based PES Managed Components

As a result of analysis, the following entities are required to be modelled in the NRM.

TISPAN Entity	Remark
Access Gateway Control Function (AGCF)	see note
NOTE: The other FEs in IMS-based PES are already covered in clause 5.1.2.	

5.2 Analysis of Transport Layer

5.2.1 Transfer Functions

The following entities are defined in ES 282 001 [3].




Figure 7: Transport Layer Managed Components

As a result of analysis, the following entities are required to be modelled in the NRM.

TISPAN Entity	Remark
A-MGF (Access)	see note
T-MGF (Trunking)	see note
C-BGF	see note
I-BGF	see note
RCEF	see note
ARF	see note
SGF	see note
MRFP	see note
NOTE:	This entity meets Requirement 2 of clause 4.2.2 because it is well defined and should be able to generate alarms.

The inclusion of the following entities in the NRM is for further study.

TISPAN Entity	Remark
BGF	-
L2TF	-
R-MGF	

NOTE 1: See clause 5.2.2 for Entities within the NASS.

NOTE 2: See clause 5.2.3 for Entities within the RACS.

5.2.2 NASS

The following entities are defined in ES 282 004 [5].




Figure 8: TISPAN NAS

As a result of analysis, the following entities are required to be modelled in the NRM.

TISPAN Entity	Remark
Network Access Configuration Function (NACF)	see note
Access Management Function (AMF)	see note
Connectivity Session Location and Repository Function (CLF)	see note
User Access Authorization Function (UAAF)	see note
Profile Data Base Function (PDBF)	see note
CNG Configuration Function (CNGCF)	see note
NOTE:	This entity meets Requirement 2 of clause 4.2.2 because it is well defined and should be able to generate alarms.

5.2.3 RACS

The following entities are defined in ES 282 003 [6].




Figure 9: TISPAN RACS

As a result of analysis, the following entities are required to be modelled in the NRM.

TISPAN Entity	Remarks
SPDF	see note
A-RACF	see note
NOTE: There is a requirement for this well defined NGN Functional Entity to generate alarms.	

5.3 List of NGN Managed Entities

5.3.1 Required NGN Managed Entities

Based on the analysis of clauses 5.1 and 5.2, the NGN entities to be managed are:

TISPAN Entity
AMF (Access Management Function)
A-MGF (Access)
A-RACF
ARF
ASF Type 1 (Application Server Function (ASF) Type 1)
ASF Type 2 (Application Server Function (ASF) Type 2)
BGCF
C-BGF
CLF (Connectivity Session Location and Repository Function)
CNGCF (Customer Network Gateway Configuration Function)
IBCF (Interconnection Border Control Function)
I-BGF
I-CSCF
IWF (Interworking Function)
MGCF
MRFC
MRFP
NACF (Network Access Configuration Function)
PDBF Profile Data Base Function)
P-CSCF
RCEF
SGF
SLF (Subscription Locator Function)
SPDF
S-CSCF
T-MGF (Trunking)
UAAF (User Access Authorization Function)
UPSF (User profile service Function)

5.3.2 Candidate NGN Managed Entities identified for further study

TISPAN Entity
Charging and data Collection Function
Trunk Routing
Customer Location
AGF (Access Gateway Function)
R-MGF (Residential Media Gateway Function)
Media Gateway Function
BGF
L2TF

Annex A (normative): Agreed Use Cases

This clause captures agreed use cases.

Table A.1: Configure new SPDF

Use Case Stage	Evolution / Specification	<<Uses>> Related use case
Goal	Configure new SPDF Required performance: Not real time. This Use Case identifies the mandatory steps and information that are necessary for a new SPDF to become 'Configured'. Refer to ES 282 003 [6], clause 5.2.3.1.	
Actor and Roles	SPDF Manager.	
Assumptions	The SPDF relies on local configuration (ES 282 003 [6], clause 5.2.3.1.10) to discover the contact points for the A-RACFs and the BGFs.	
Pre conditions	SPDF not configured.	
Begins when	SPDF Manager brings SPDF into service.	
Step1	Set list of IP Addresses/Ports or FQDNs towards interested Functional Entities it is allowed to communicate with: - set IP Addresses/Ports or FQDNs towards AF; - set IP Addresses/Ports or FQDNs towards A-RACF; - set IP Addresses/Ports or FQDNs towards BGF. There is no preferred order for the execution of the above tasks.	
Step 2	Set Charging information to be provided. They can be any combination of: - Charging correlation information. - Requestor Info. - Subscriber Info. - Service Priority. - Media Description. - Commit ID. - Time Stamp. - Reason.	
Step 3	Set operator-defined local policy. This use case is indicated as generic, because no further details are given in stage 2 specs.	
Step 4	Set, for each BGF, the BGF services to be requested. They can be any combination of: - Open/close gates. - Packet marking. - Resource allocation (per flow). - NAT. - Hosted NAT Traversal. - Policing of down/uplink traffic. - Usage metering.	
Step 7	Set Status to Active.	
Ends when	SPDF Status = Active.	
Exceptions	Failure of set IP Address/Port or FQDN towards AF. Failure of set IP Address/Port or FQDN towards A-RACF. Failure of set IP Address/Port or FQDN towards BGF.	
Post Conditions	SPDF Status = Active.	
Traceability	To be defined.	

NOTE: It is for further study if the Charging information related to this use case is to be included within the NRM.

It is expected that additional specific use cases covering areas such as fault management, configuration management, etc. will be specified in future versions of the present document.

Annex B (informative): Candidate Use Cases

<for further study>

Annex C (informative): Bibliography

ETSI TS 132 631: "Universal Mobile Telecommunications System (UMTS); Telecommunication Management; Configuration Management (CM); Core network resources Integration Reference Point (IRP): Requirements (3GPP TS 32 631 version 6.0.0 Release 6)".

Annex D (informative): Change history

Date	WG Doc.	CR	Rev	CAT	Title / Comment	Current Version	New Version
05-11-08	19WTD063r1	1	-	F	Correction to update R-MGF	2.0.0	2.0.1
					Publication	2.0.1	2.1.1

History

Document history		
V2.0.0	February 2007	Publication
V2.1.1	February 2009	Publication