

ETSI TS 126 143 V18.0.0 (2024-05)



5G;
Messaging Media profiles
(3GPP TS 26.143 version 18.0.0 Release 18)



Reference

RTS/TSGS-0426143vi00

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	7
2 References	7
3 Definitions of terms, symbols and abbreviations	8
3.1 Terms.....	8
3.2 Symbols.....	9
3.3 Abbreviations	9
4 Overview and Context.....	9
4.1 Background and Assumptions.....	9
4.2 System Description.....	10
4.3 MMBP Player Model	11
4.4 Generic MMBP Data Model	12
4.5 Media Capabilities and Profiles.....	12
5 MMBP Media Capabilities for different Media Types	13
5.1 Introduction	13
5.2 Multipart MMBPs and Container Formats	15
5.2.1 Player and Decoding capabilities.....	15
5.2.2 MMBP Content Generator capabilities.....	16
5.3 Text	16
5.3.1 Player and Decoding capabilities.....	16
5.3.2 MMBP Content Generator capabilities.....	16
5.4 Image.....	17
5.4.1 Player and Decoding capabilities.....	17
5.4.2 MMBP Content Generator capabilities.....	17
5.5 Speech and Audio.....	18
5.5.1 Player and Decoding capabilities.....	18
5.5.2 MMBP Content Generator capabilities.....	19
5.6 Video.....	20
5.6.1 Player and Decoding capabilities.....	20
5.6.2 MMBP Content Generator capabilities.....	22
5.7 Timed Text and Subtitles	23
5.7.1 Player and Decoding capabilities.....	23
5.7.2 MMBP Content Generator capabilities.....	24
5.8 3D scenes and assets.....	24
5.9 Presentation format.....	24
6 Messaging Media Profiles	25
6.1 Overview	25
6.2 Baseline MMBP Player Profile	25
6.2.1 Overview	25
6.2.2 Container Format	25
6.2.3 Media Types	26
6.3 Baseline MMBP Generator Profile	27
6.3.1 Overview	27
6.3.2 Container Format	27
6.3.3 Media Types	27
6.3.4 Packaging Requirements and Recommendations	28
Annex A (informative): Registration Information	29
A.1 3GPP Registered URIs	29

Annex B (informative): **Examples**.....30
Annex Z (informative): **Change history**31
History32

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

1 Scope

The present document specifies the media types, formats, codecs capabilities and profiles for the messaging applications used over the 5G System. The scope of the present document extends to codecs for speech, audio, video, still images, bitmap graphics, 3D scenes and assets, and other media in general, as well as scene description.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] Khronos glTF 2.0, [glTF™ 2.0 Specification \(khronos.org\)](https://www.khronos.org/specs/gltf/)
- [3] ISO/IEC 23090-14 AMD 2, Information technology — Coded representation of immersive media — Part 14: Scene description — Amendment 2: Support for haptics, augmented reality, avatars, Interactivity, MPEG-I audio, and lighting
- [4] 3GPP TS 26.511: "5G Media Streaming (5GMS); Profiles, Codecs and Formats".
- [5] 3GPP TS 26.117: "5G Media Streaming (5GMS); Speech and audio profiles".
- [6] IETF Draft draft-ietf-mimi-content-01: "More Instant Messaging Interoperability (MIMI) message content", Rohan Mahy
- [7] 3GPP TS 22.140: "Multimedia Messaging Service (MMS); Stage 1".
- [8] Open Mobile alliance, "MMS Architecture" OMA-AD-MMS-V1_3-20110913-A.
- [9] Open Mobile alliance, "Multimedia Messaging Service Encapsulation Protocol" OMA-TS-MMS_ENC-V1_3-20110913-A.
- [10] GSMA "RCS Universal Profile Service Definition Document", Version 2.6, 19 December 2022
- [11] GSMA PRD RCC.07 version 13.0 - "Rich Communication Suite - Advanced Communications Services and Client Specification" 19 December 2022[12] IETF RFC 2046: "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types"
- [12] IETF RFC 2046, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types"
- [13] ISO/IEC 14496-12: "Information technology - Coding of audio-visual objects -Part 12: ISO base media file format".
- [14] ISO/IEC 23000-24:2023 Preliminary Draft of: Information technology — Multimedia application format (MPEG-A) — Part 24: Messaging Media Application Format (MeMAF) ".

NOTE: A preliminary draft of this standard is available as MDS23345_W03_N1082 here:
https://www.mpeg.org/wp-content/uploads/mpeg_meetings/144_Hannover/w23345.zip

- [15] 3GPP 23.140: "Multimedia Messaging Service (MMS); Functional Description; Stage 2".
- [16] ITU-T Recommendation T.81: "Information technology; Digital compression and coding of continuous-tone still images: Requirements and guidelines".

- [17] "JPEG File Interchange Format", Version 1.02, September 1, 1992.
- [18] "Exchangeable image file format for digital still cameras: EXIF 2.2", Specification by the Japan Electronics and Information Technology Industries Association (JEITA), April 2002, URL: <http://www.exif.org/>
- [19] CompuServe Incorporated: "GIF Graphics Interchange Format: A Standard defining a mechanism for the storage and transmission of raster-based graphics information", Columbus, OH, USA, 1987.
- [20] Compuserve Incorporated, Columbus, Ohio (1990): "Graphics Interchange Format (Version 89a)".
- [21] IETF RFC 2083: "PNG (Portable Networks Graphics) Specification version 1.0 ", T. Boutell, et. al., March 1997.
- [22] ISO/IEC 23000-22:2019 Information technology — Multimedia application format (MPEG-A) — Part 22: Multi-image application format (MIAF)
- [23] IETF RFC 2045, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", November 1996
- [24] ISO/IEC 23008-12:2019 Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 12: Image File Format
- [25] ITU-T Recommendation H.265 (02/2018): "High efficiency video coding".
- [26] 3GPP TS 26.244: "Transparent end-to-end packet switched streaming service (PSS); 3GPP file format (3GP)"
- [27] 3GPP TS 26.245: "Transparent end-to-end packet switched streaming service (PSS); Timed text format"
- [28] ISO/IEC 14496-30: "Information technology - Coding of audio-visual objects - Part 30: Timed text and other visual overlays in ISO base media file format".
- [29] IETF RFC 2387, "The MIME Multipart/Related Content-type"
- [30] IETF RFC 6381, "The 'Codecs' and 'Profiles' Parameters for "Bucket" Media Types"
- [31] 3GPP TS 26.307, "Presentation Layer for 3GPP Services"
- [32] 3GPP TS 26.140, "Multimedia Messaging Service (MMS); Media formats and codecs"
- [33] IETF RFC 2077, "The Model Primary Content Type for Multipurpose Internet Mail Extensions"
- [34] 3GPP TS 26.119, "Media Capabilities for Augmented Reality"

3 Definitions of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Messaging Media Profile: a set of UE capability requirements associated to a media-centric messaging service scenario.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

<symbol> <Explanation>

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AAC	Advanced Audio Coding
AMR	Adaptive MultiRate
API	Application Programming Interface
AVC	Advanced Video Coding
DCT	Discrete Cosine Transform
gITF	Graphics Library Transmission Format
IANA	Internet Assigned Numbers Authority
MIME	Multipurpose Internet Mail Extensions
MIMI	More Instant Messaging Interoperability
MMBP	multimedia messaging body part
MMS	Multimedia Messaging Service
OMA	Open Mobile Alliance
PDU	Protocol Data Unit
RCS	Rich Communication Services

4 Overview and Context

4.1 Background and Assumptions

Messaging services typically define a message container. Such a container typically carries one or more body parts with the actual message content (for example, an emoji used in a reaction, a plain text or rich text message or reply, a link, or an inline image, or richer media types).

An important feature of messages are body parts that include media content. Different media content exists, such as simple and rich text, still images, graphics, speech, audio, video, 3D scenes and many other media types.

This specification is not defining a container format, but it addresses the usability of 3GPP defined media types and formats into messages as part of a message body within message containers. Examples for message containers are OMA MMS PDUs [7][8][9][15], IETF MIMI message containers [6] or GSMA RCS [10][11].

The focus of this specification is the definition of parts of *message body* that carry multimedia content, referred to as *multimedia messaging body part* (MMBP). This specification does not generally define how the body part is encoded: existing functionalities, for example the ones defined in OMA MMS PDUs [7][8][9][15] or MIMI message containers [6] may be used for this purpose. However, this specification provides the definition of an MMBP using the ISO Base Media File format [13] to provide features for mixing multiple sub-parts into a single body part. The specification relies on ISO/IEC 23000-24 [14].

NOTE: This specification does not define advanced MMBP features using the ISO Base Media File format [13] such that multiple sub-parts may be mixed into a single body part. This feature is for further study, possibly in alignment with ISO/IEC 23000-24 [14].

However, this specification is not restricted to be used with a fully specified Messaging Service, it may as well be used as part of third-party messaging services as message body, or more specifically as MMBP. It may also serve to support content interoperability across different messaging services.

The term *media type* is used as short to refer to the IANA media type, subtype, and parameters as defined in IETF RFC 2046 [12] and provides defined properties of a *content*. For example, it may tell if the content is video or audio, it

provides the encapsulation format, and it may provide parameters such as the codec in use. This specification defines, or at least assigns to each defined MMBP a media type, in order to uniquely identify the media type.

In order to use MMBPs as defined in this specification as part of a message container format, it is expected that the message container format supports the following functionalities:

- 1) It can carry an octet string representing the *content* of the MMBP
- 2) It can signal the *media type* of the content.
- 3) The content and media type of the content is not restricted but allows to include formats that are not defined in the core container format.

In addition, a container format may support one or more of the following functionalities in alignment of definitions in IETF MIMI [6] and IETF RFC 2046 [12]:

- the body can be *multi-part*, i.e, it can have multiple, possibly nested parts, referred to as *sub-parts*, with one of the following properties and structures
 - *mixed*: there are multiple media types associated with the same message which need to be rendered together, for example a rich-text message with an inline image. The receiver is expected to process as many of the nested parts at this level as possible.
 - *alternative*: there are multiple media types associated with the same message and the receiver can choose an appropriate one based on its own policies using the media type or possibly other parameters (e.g. a language) of each part.
 - *related*: there are multiple media types associated with the same message and all the nested body parts at this level are part of a single entity that are processed jointly, possibly by providing a root object for initial processing. If the receiver does not understand even one of the nested parts at this level, the receiver is not expected to process any of them.
 - *nested*: there are multiple media types associated with the same message, and one or several of the media types are representing a single, mixed, alternative or related structure.
- it may have body parts that reference external content via URI that will be processed automatically. It includes a media type and may optionally include the size of the data, an expiration timestamp other parameters. The content may be rendered with the other parts of the message, or a be downloaded or rendered separately.
- it may have body parts for which the content is encrypted.

Note that based on the above, the MMBP may be the entire part of a message body, or it may be a sub-part.

4.2 System Description

Based on the background and assumptions in clause 4.1, Figure 4.2-1 provides an example system for a messaging services and highlights scope of this specification, namely the definition of a *multimedia messaging body part* (MMBP) and the associated metadata.




Figure 4.2-1 Example system for Messaging multimedia message exchange

A Messaging Service Sender instructs a MMBP generator to generate an MMBP, for example using an API. This for example allows to define configurations on codecs, size, experiences or other attributes of the MMBP. The details of such an API are outside the scope of this specification. The sender adds the MMBP to a Container Message (either included as a body part or by reference), together with MMBP metadata parameters that provide information about the MMBP. Metadata includes, but is not limited to:

- The media type of the MMBP, including subtypes and parameters for codecs, etc.
- The size of the MMBP
- Accessibility or language information about the MMBP
- processing requirements or recommendations of the MMBP

The client of the messaging service receives the container message that includes the above information. The client communicates with a MMBP player its capabilities whether the MMBP can be played back, and if multiple alternatives are present, which of those are to be selected. Then the messaging service client instructs the MMBP player to playback the MMBP as part of the messaging service, based on the processing requirements and instructions. Playback may be combined with additional instructions for a player, including play, pause, seek, etc.

4.3 MMBP Player Model

The design of the formats defined in this document is based on the player model as shown in Figure 4.3-2. The figure illustrates the logical components of a conceptual MMBP Player model. In this figure, the MMBP parser receives the MMBP, and playback instructions. The Messaging Service Client may use metadata provided in a container message for playback selection. Such metadata may for example include codec capability information, language codes, accessibility information and other information for the selection of alternative parts in the MMBP.

The client then provides the sub-parts for processing and decoding to the related sub-part processors, and controls those for playback. The rendered message output may be handed back to the Messaging Service client for inband rendering or may be rendered directly.




Figure 4.3-1 MMBP Player Model

Beyond the MMBP formats, this specification also defines capabilities of 3GPP-based MMBP players.

4.4 Generic MMBP Data Model

Based on the description in clause 4.1, an MMBP can be the full body or part of the body of a container message.

An MMBP itself is identified by a media type.

The MMBP may be a single content with a media type.

The MMBP may include multiple additional MMBPs. The following multi-part MMBPs are defined:

- *mixed MMBP*: multiple MMBPs are associated with the mixed MMBP that shall be rendered together. Each MMBP is identified by a media type. The receiver is expected to process *as many as possible* of the included MMBPs based on its capabilities.
- *parallel MMBP*: multiple MMBPs are associated with the parallel MMBP that shall be rendered together. Each MMBP is identified by a media type. Real-time MMBPs included in a parallel MMBP share the same MMBP presentation timeline, which has a value of zero at the earliest media sample intended for presentation. If presented jointly, they shall be presented using this common MMBP presentation timeline.
- *alternative MMBP*: multiple MMBPs are associated with the alternative MMBP. Each MMBP is identified by a media type. The receiver is expected to process *exactly one* based on its capabilities.
- *related MMBP*: multiple objects are associated with the process MMBP. One object is identified as a *root MMBP*. The root MMBP is identified by a media type. The root MMBP is processed and identifies if any, several or all of the remaining objects are used as well. Hence, all other objects are typically also identified by media types, and a URL that links the objects being part of the related MMBP. The processor of the root MMBP also controls the selection, presentation and timing of the other objects.

MMBPs are a recursive structure. Hence, a receiver shall expect that multi-part MMBPs contain other multi-part MMBPs.

4.5 Media Capabilities and Profiles

This specification defines media capabilities for both, MMBP generators as well as MMBP players in clause 5. The media capabilities provide requirements for content generation as well as playback instructions, respectively.

This specification also defines profiles for content generators and players. Profiles are a collection of media capability requirements and recommendations as defined in clause 6.

External specifications may reference capabilities defined in this specification.

Preferably, external specifications should reference full media profiles.

5 MMBP Media Capabilities for different Media Types

5.1 Introduction

In order to guarantee a minimum support and compatibility between messaging capable terminals, MMBP Generators and MMBP Players in UEs supporting specific media content with associated media types.

The clause defines multimedia messaging body parts (MMBPs) for different media types as well as the associated media types.

According to the introduction in clause 4, MMBPs defined in this clause,

- may be used as full body parts or sub-parts in message bodies.
- may either be a single binary octet string, or they may consist of multiple parts. If the latter, the conceptual relationship introduced in clause 4.4 is defined that is mapped to container formats defined in clause 5.2.

Media Types and related capabilities defined in this specification for playback are provided in Table 5.1-1.

Table 5.1-1 Media Types and Capabilities defined in TS 26.143 for playback and decoding

Media Type in the present TS	Capabilities defined in this specification	Clause	Media Type signalling example
Multipart MMBPs and Container Formats	26143_CONTAINER_RFC2046_SINGLE 26143_CONTAINER_RFC2046_MIXED 26143_CONTAINER_RFC2046_ALTERNATIVE 26143_CONTAINER_RFC2046_PARALLEL 26143_CONTAINER_RFC2387_RELATED 26143_CONTAINER_MP4_3GP9	5.2.1	Media type of subtype multipart/mixed multipart/alternative multipart/parallel multipart/related video/mp4, profile="3gp9"
Text	26143_TEXT_PLAIN	5.3.1	text/plain
Speech	26143_AUDIO_EVS 26143_AUDIO_AMR-WB 26143_AUDIO_AMR	5.5.1	audio/mp4
Audio	26143_AUDIO_XHE-AAC 26143_AUDIO_EAAC+	5.5.1	audio/mp4
Image	26143_IMG_JPEG 26143_IMG_HEIC 26143_IMG_GIF 26143_IMG_PNG	5.4.1	image/jpeg image/heic, profile="heic,MiHB" imageTypes="hvc1.1.2.L153.B0" image/gif image/png

Video	26143_VIDEO_AVC-HD 26143_VIDEO_AVC-FullHD 26143_VIDEO_HEVC-HD 26143_VIDEO_HEVC-FullHD 26143_VIDEO_HEVC-UHD	5.6.1	video/mp4, profile="3gp9" codecs="avc1.640028" video/mp4, profile="3gp9" codecs="avc1.640029" video/mp4, profile="3gp9" codecs="hvc1.1.1.2.L93.B0" video/mp4, profile="3gp9" codecs="hvc1.1.1.2.L123.B0" video/mp4, profile="3gp9" codecs="hvc1.1.1.2.L153.B0"
Subtitles and Text	26143_TT_3GPP 26143_TT_IMSC11	5.7.1	text/mp4, profile="3gp9" codecs="tx3g" application/mp4, profile="3gp9" codecs="stpp.ttml.im2t"
3d scenes and assets	26143_SCENE_GLTF20 26143_SCENE_GLTF20_AR 26143_SCENE_GLTF20_GLB 26143_SCENE_GLTF20_GLB_AR	5.8	model/gltf+json model/gltf-binary
Presentation format	26143_PRESENTATION_HTML5	5.9	text/html

Media Types and related capabilities defined in this specification for content generation are provided in Table 5.1-2.

Table 5.1-2 Media Types and Capabilities defined in TS 26.143 for generation

Media Type in the present TS	Capabilities defined in this specification	Clause	Media Type signalling example
Multipart MMBPs and Container Formats	26143_CONTAINER_RFC2046_SINGLE_GEN 26143_CONTAINER_RFC2046_MIXED_GEN 26143_CONTAINER_RFC2046_ALTERNATIVE_GEN 26143_CONTAINER_RFC2046_PARALLEL_GEN 26143_CONTAINER_MP4_3GP9_GEN	5.2.2	Media type of subtype multipart/mixed multipart/alternative multipart/parallel video/mp4, profile="3gp9"
Text	26143_TEXT_ENC_PLAIN	5.3.1	text/plain
Speech	26143_AUDIO_ENC_EVS 26143_AUDIO_ENC_AMR-WB 26143_AUDIO_ENC_AMR	5.5.1	audio/mp4
Audio	26143_AUDIO_ENC_XHE-AAC	5.5.1	audio/mp4

	26143_AUDIO_ENC_EAAC+		
Image	26143_IMG_ENC_JPEG	5.4.1	image/jpeg
Video	26143_VIDEO_ENC_AVC-HD	5.6.2	video/mp4, profile="3gp9" codecs="avc1.640028"
	26143_VIDEO_ENC_AVC-FullHD		video/mp4, profile="3gp9" codecs="avc1.640029"
	26143_VIDEO_ENC_HEVC-HD		video/mp4, profile="3gp9" codecs="hvc1.1.2.L93.B0"
	26143_VIDEO_ENC_HEVC-FullHD		video/mp4, profile="3gp9" codecs="hvc1.1.2.L123.B0"
	26143_VIDEO_ENC_HEVC-UHD		video/mp4, profile="3gp9" codecs="hvc1.1.2.L153.B0"
Text	26143_TT_ENC_3GPP	5.7.2	text/mp4, profile="3gp9" codecs="tx3g"

5.2 Multipart MMBPs and Container Formats

5.2.1 Player and Decoding capabilities

The capability 26143_CONTAINER_RFC2046_SINGLE is defined as the capability of processing a body part of with a top-level media type as defined in IETF RFC 2046 [12] with one of the following top-level media types: text, audio, image, video, model, multipart, and application.

The capability 26143_CONTAINER_RFC2046_MIXED is defined as the capability of processing a body part of subtype `multipart/mixed` as defined in IETF RFC 2046 [12] further restricted by the processing defined in clause 4.4 for *mixed MMBPs*. In the context of this specification, the media type for multipart media types with this capability 26143_CONTAINER_RFC2046_MIXED shall be signalled with `multipart/mixed` as defined in IETF RFC 2046 [12].

The capability 26143_CONTAINER_RFC2046_ALTERNATIVE is defined as the capability of processing a body part of subtype `multipart/alternative` as defined in IETF RFC 2046 [12] further restricted by the processing defined in clause 4.4 for *alternative MMBPs*. In the context of this specification, the media type for multipart media types with this capability 26143_CONTAINER_RFC2046_MIXED shall be signalled with `multipart/alternative` as defined in IETF RFC 2046 [12].

The capability 26143_CONTAINER_RFC2046_PARALLEL is defined as the capability of processing a body part of subtype `multipart/parallel` as defined in IETF RFC 2046 [12] further restricted by the processing defined in clause 4.4 for *parallel MMBPs*. In the context of this specification, the media type for multipart media types with this capability 26143_CONTAINER_RFC2046_PARALLEL shall be signalled with `multipart/parallel` as defined in IETF RFC 2046 [12].

The capability 26143_CONTAINER_RFC2387_RELATED is defined as the capability of processing a body part of subtype `multipart/related` as defined in IETF RFC 2387 [29] further restricted by the processing defined in clause 4.4 for *related MMBPs*. In the context of this specification, the media type for multipart media types with this capability 26143_CONTAINER_RFC2387_RELATED shall be signalled with `multipart/parallel` as defined in IETF RFC 2387 [29] with the *root MMBP* either signalled with the `start` parameter, or if not present, the *root MMBP* being the first body part within the Multipart/Related body and the type of the *root MMBP* signalled with the `type` parameter.

The capability 26143_CONTAINER_MP4_3GP9 is defined as the capability of processing a body part conforming to a 3GP file Rel-9 basic profile as defined in TS 26.244 [26] identified by the brand '3gp9' and further restricted by the processing defined in clause 4.4 for *parallel MMBPs*. In the context of this specification, the media type for multipart

media types with this capability `26143_CONTAINER_MP4_3GP9` shall be signalled using a media type as defined IETF RFC 6381 [30] using for example `video/mp4, profile="3gp9"` or an equivalently compatible media type and shall use the `codecs` parameter to further provide information about the contained MMBPs.

NOTE: This specification does not define mechanisms for referencing external content. This aspect is for further study.

5.2.2 MMBP Content Generator capabilities

The capability `26143_CONTAINER_RFC2046_SINGLE_GEN` is defined as the capability of generating a body part of with a top-level media type as defined in IETF RFC 2046 [12] with one of the following top-level media types: `text`, `audio`, `image`, `video`, and `multipart` that can be processed by a MMBP processor with the capability `26143_CONTAINER_RFC2046_SINGLE`.

The capability `26143_CONTAINER_RFC2046_MIXED_GEN` is defined as the capability of generating a body part of subtype `multipart/mixed` as defined in IETF RFC 2046 [12] with media type signalling with `multipart/mixed` as defined in IETF RFC 2046 [12] that can be processed by a MMBP processor with the capability `26143_CONTAINER_RFC2046_MIXED`.

The capability `26143_CONTAINER_RFC2046_ALTERNATIVE_GEN` is defined as the capability of generating a body part of subtype `multipart/alternative` as defined in IETF RFC 2046 [12] with media type signalling with `multipart/alternative` as defined in IETF RFC 2046 [12] that can be processed by a MMBP processor with the capability `26143_CONTAINER_RFC2046_ALTERNATIVE`.

The capability `26143_CONTAINER_RFC2046_PARALLEL_GEN` is defined as the capability of generating a body part of subtype `multipart/parallel` as defined in IETF RFC 2046 [12] with media type signalling with `multipart/parallel` as defined in IETF RFC 2046 [12] that can be processed by a MMBP processor with the capability `26143_CONTAINER_RFC2046_PARALLEL`.

The capability `26143_CONTAINER_MP4_3GP9_GEN` is defined as the capability of generating a body part conforming to a 3GP file Rel-9 basic profile as defined in TS 26.244 [26] identified by the brand '3gp9' using a media type as defined IETF RFC 6381 [30], for example `video/mp4, profile="3gp9"` or an equivalently compatible media type and using the `codecs` parameter to further provide information about the contained MMBPs.

5.3 Text

5.3.1 Player and Decoding capabilities

The capability `26143_TEXT_PLAIN` is defined as the capability of decoding and rendering plain text with any character encoding (charset) that contains a subset of the logical characters in Unicode [2] (e.g. US-ASCII [3], ISO-8859-1 [4], UTF-8 [5], Shift_JIS, etc.). In the context of this specification, the media type for text with this capability `26143_TEXT_PLAIN` shall be signalled with `text/plain` as defined in IETF RFC 2046 [12]. However, the decoding and rendering capability `26143_TEXT_PLAIN` includes that unrecognized subtypes of "text" shall be treated as subtype "plain" as long as the MIME implementation knows how to handle the charset.

Interoperability with SMS/MMS text type is according to [15].

5.3.2 MMBP Content Generator capabilities

The capability `26143_TEXT_ENC_PLAIN` for a content generator is defined as the combination of the following capabilities:

- the capability to generate plain text with any character encoding (charset) that contains a subset of the logical characters in Unicode [2], such that the file can be played back by a player with the capability `26143_TEXT_PLAIN`,
- the provisioning of media type signalling with the MMBP using `text/plain` as defined in IETF RFC 2046 [12].

5.4 Image

5.4.1 Player and Decoding capabilities

The capability `26143_IMG_JPEG` is defined as the capability of decoding and rendering images according to, ISO/IEC JPEG [8] together

- with JFIF [16] and the following two modes:
 - baseline DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF0' in [17];
 - progressive DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF2' [17].- with EXIF compressed image file format, as defined in [18] and the baseline DCT mode.

In the context of this specification, the media type for images with this capability `26143_IMG_JPEG` shall be signalled with `image/jpeg` as defined in IETF RFC 2046 [12].

The capability `26143_IMG_HEIC` is defined as the capability of decoding and rendering images conforming to

- the 'heic' brand as defined in ISO/IEC 23008-12 [24],
- the 'MiHB' brand as defined in ISO/IEC 23000-22:2019 [22], and
- the contained elementary bitstream conforming to H.265 (HEVC) Main Profile, Main Tier, Level 5.1[25] bitstreams have `general_progressive_source_flag` equal to 1, `general_interlaced_source_flag` equal to 0, `general_non_packed_constraint_flag` equal to 1, and `general_frame_only_constraint_flag` equal to 1.

In the context of this specification, the media type for images with this capability `26143_IMG_HEIC` shall be signalled with `image/heic, profile="heic,MiHB" itemTypes="hvc1.1.2.L153.B0"` or an equivalently compatible media type as defined in [22].

The capability `26143_IMG_GIF` is defined as the capability of decoding and rendering bitmap graphics conforming either to GIF87a [19] or to GIF89a, [20]. In the context of this specification, the media type for images with this capability `26143_IMG_GIF` shall be signalled with `image/gif` as defined in IETF RFC 2046 [12].

The capability `26143_IMG_PNG` is defined as the capability of decoding and rendering bitmap graphics conforming to PNG [21]. In the context of this specification, the media type for images with this capability `26143_IMG_GIF` shall be signalled with `image/png`.

5.4.2 MMBP Content Generator capabilities

The capability `26143_IMG_ENC_JPEG` for a content generator is defined as the combination of the following capabilities:

- the capability to generate an image according to ISO/IEC JPEG [8] that can be played by a player conforming to `26143_IMG_JPEG` as defined in clause 5.4.1, i.e. restricted by either
 - using JFIF [16] and one of the following two modes:
 - baseline DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF0' in [17], or
 - progressive DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF2' [17].
 - using EXIF compressed image file format as defined in [18] and the baseline DCT mode.
- the provisioning of media type signalling with the MMBP using `image/jpeg` as defined in IETF RFC 2046 [12].

5.5 Speech and Audio

5.5.1 Player and Decoding capabilities

The capability `26143_AUDIO_EVS` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **EVS** decoding capabilities as defined in clause 5.2 of TS 26.117 [5] and the receiver requirements in clause 6.2.4.2 of TS 26.117 [5],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'sevs' as defined in TS 26.244 [26],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_AUDIO_EVS` shall be signalled with `audio/mp4, profile="3gp9" codecs="sevs"` or an equivalently compatible media type.

The capability `26143_AUDIO_AMR-WB` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **AMR-WB** decoding capabilities as defined in clause 5.2 of TS 26.117 [5] and the receiver requirements in clause 6.2.3.2 of TS 26.117 [5],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'sawb' as defined in TS 26.244 [26],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_AUDIO_EVS` shall be signalled with `audio/mp4, profile="3gp9" codecs="sawb"` or an equivalently compatible media type.

The capability `26143_AUDIO_AMR` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **AMR** decoding capabilities as defined in clause 5.2 of TS 26.117 [5] and the receiver requirements in clause 6.2.2.2 of TS 26.117 [5],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'samr' as defined in TS 26.244 [26],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_AUDIO_EVS` shall be signalled with `audio/mp4, profile="3gp9" codecs="samr"` or an equivalently compatible media type.

The capability `26143_AUDIO_XHE-AAC` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **xHE-AAC stereo** decoding capabilities as defined in clause 5.2 of TS 26.117 [5] and the receiver requirements in clause 6.4.2.2 of TS 26.117 [5],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'mp4a.40.29',
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_AUDIO_XHE-AAC` shall be signalled with `audio/mp4, profile="3gp9" codecs="mp4a.40.29"` or an equivalently compatible media type.

The capability `26143_AUDIO_EAAC+` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **eAAC+** decoding capabilities as defined in clause 5.2 of TS 26.117 [5] and the receiver requirements in clause 6.3.2.2 of TS 26.117 [5],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'mp4a.40.5',
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_AUDIO_EVS` shall be signalled with `audio/mp4, profile="3gp9" codecs="mp4a.40.5"` or an equivalently compatible media type.

5.5.2 MMBP Content Generator capabilities

The capability `26143_AUDIO_ENC_EVS` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from an audio signal in real-time, such that the file can be played back by a player with the capability `26143_AUDIO_EVS`,
- the *EVS* encoding capabilities as defined in clause 5.3 of TS 26.117 [5] and the sender requirements in clause 6.2.4.3 of TS 26.117 [5],
- the capability to generate an ISO BMFF track that conforms with the requirements of the sample entry 'sevs' as defined in TS 26.244 [26].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `audio/mp4, profile="3gp9" codecs="sevs"` or an equivalently compatible media type.

The capability `26143_AUDIO_ENC_AMR-WB` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from an audio signal in real-time, such that the file can be played back by a player with the capability `26143_AUDIO_AMR-WB`,
- the *AMR-WB* encoding capabilities as defined in clause 5.3 of TS 26.117 [5] and the sender requirements in clause 6.2.3.3 of TS 26.117 [5],
- the capability to generate an ISO BMFF track that conforms with the requirements of the sample entry 'sawb' as defined in TS 26.244 [26].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `audio/mp4, profile="3gp9" codecs="sawb"` or an equivalently compatible media type.

The capability `26143_AUDIO_ENC_AMR` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from an audio signal in real-time, such that the file can be played back by a player with the capability `26143_AUDIO_AMR`,

- the *EVS* encoding capabilities as defined in clause 5.3 of TS 26.117 [5] and the sender requirements in clause 6.2.2.3 of TS 26.117 [5],
- the capability to generate an ISO BMFF track that conforms with the requirements of the sample entry 'samr' as defined in TS 26.244 [26].
- the generation of a 3GP file from the ISO BMFF track that conforms to the 26143_CONTAINER_MP4_3GP9 capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `audio/mp4, profile="3gp9" codecs="samr"` or an equivalently compatible media type.

The capability 26143_AUDIO_ENC_XHE-AAC for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from an audio signal in real-time, such that the file can be played back by a player with the capability 26143_AUDIO_XHE-AAC,
- the *xHE-AAC stereo* encoding capabilities as defined in clause 5.3 of TS 26.117 [5] and the sender requirements in clause 6.4.2.3 of TS 26.117 [5],
- the capability to generate an ISO BMFF track that conforms with the requirements of the sample entry 'mp4a.40.29' as defined in TS 26.244 [26].
- the generation of a 3GP file from the ISO BMFF track that conforms to the 26143_CONTAINER_MP4_3GP9 capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `audio/mp4, profile="3gp9" codecs="mp4a.40.29"` or an equivalently compatible media type.

The capability 26143_AUDIO_ENC_EAAC+ for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from an audio signal in real-time, such that the file can be played back by a player with the capability 26143_AUDIO_EAAC+,
- the *eAAC+* encoding capabilities as defined in clause 5.3 of TS 26.117 [5] and the sender requirements in clause 6.3.2.3 of TS 26.117 [5],
- the capability to generate an ISO BMFF track that conforms with the requirements of the sample entry 'mp4a.40.5' as defined in TS 26.244 [26].
- the generation of a 3GP file from the ISO BMFF track that conforms to the 26143_CONTAINER_MP4_3GP9 capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `audio/mp4, profile="3gp9" codecs="mp4a.40.5"` or an equivalently compatible media type.

5.6 Video

5.6.1 Player and Decoding capabilities

The capability 26143_VIDEO_AVC-HD is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **AVC-HD-Dec** decoding capabilities as defined in clause 4.2.1.1 of TS 26.511 [4],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'avc1' as defined in ISO/IEC 14496-15 [15],
- is contained in a 3GP file that conforms to the 26143_CONTAINER_MP4_3GP9 capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_VIDEO_AVC-HD` shall be signalled with `video/mp4, profile="3gp9" codecs="avc1.640028"` or an equivalently compatible media type.

The capability `26143_VIDEO_AVC-FullHD` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **AVC-FullHD-Dec** decoding capabilities as defined in clause 4.2.1.1 of TS 26.511 [4],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'avc1' as defined in ISO/IEC 14496-15 [15],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_VIDEO_AVC-FullHD` shall be signalled with `video/mp4, profile="3gp9" codecs="avc1.640029"` or an equivalently compatible media type.

The capability `26143_VIDEO_HEVC-HD` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **HEVC-HD-Dec** decoding capabilities as defined in clause 4.2.2.1 of TS 26.511 [4],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_VIDEO_HEVC-HD` shall be signalled with `video/mp4, profile="3gp9" codecs="hvc1.1.2.L93.B0"` or an equivalently compatible media type.

The capability `26143_VIDEO_HEVC-FullHD` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **HEVC-FullHD-Dec** decoding capabilities as defined in clause 4.2.2.1 of TS 26.511 [4],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_VIDEO_HEVC-FullHD` shall be signalled with `video/mp4, profile="3gp9" codecs="hvc1.2.4.L123.B0"` or an equivalently compatible media type.

The capability `26143_VIDEO_HEVC-UHD` is defined as the capability of playing back (decoding and rendering) a file that

- is decodable by a decoder capable of the **HEVC-UHD-Dec** decoding capabilities as defined in clause 4.2.2.1 of TS 26.511 [4],
- is encapsulated in an ISO BMFF Track [14] conforming with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15],
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_VIDEO_HEVC-UHD` shall be signalled with `video/mp4, profile="3gp9" codecs="hvc1.2.4.L153.B0"` or an equivalently compatible media type.

NOTE: In the absence of knowledge of detailed capabilities, 16:9 and 9:16 image formats are preferably used.

5.6.2 MMBP Content Generator capabilities

The capability `26143_VIDEO_ENC_AVC-HD` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a video signal in real-time, such that the file can be played back by a player with the capability `26143_VIDEO_AVC-HD`,
- the **AVC-HD-Enc** encoding capabilities as defined in clause 4.1.2.2 of TS 26.511 [4] to generate a bitstream from the video signal
- the capability to generate an ISO BMFF track from the bitstream that conforms with the requirements of the sample entry 'avc1' as defined in ISO/IEC 14496-15 [15].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="avc1.640028"` or an equivalently compatible media type.

The capability `26143_VIDEO_ENC_AVC-FullHD` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a video signal in real-time, such that the file can be played back by a player with the capability `26143_VIDEO_AVC-FullHD`,
- the **AVC-FullHD-Enc** encoding capabilities as defined in clause 4.1.2.2 of TS 26.511 [4] to generate a bitstream from the video signal
- the capability to generate an ISO BMFF track from the bitstream that conforms with the requirements of the sample entry 'avc1' as defined in ISO/IEC 14496-15 [15].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="avc1.640029"` or an equivalently compatible media type.

The capability `26143_VIDEO_ENC_HEVC-HD` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a video signal in real-time, such that the file can be played back by a player with the capability `26143_VIDEO_HEVC-HD`,
- the **HEVC-HD-Enc** encoding capabilities as defined in clause 4.2.2.2 of TS 26.511 [4] to generate a bitstream from the video signal
- the capability to generate an ISO BMFF track from the bitstream that conforms with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="hvc1.1.2.L93.B0"` or an equivalently compatible media type.

The capability `26143_VIDEO_ENC_HEVC-FullHD` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a video signal in real-time, such that the file can be played back by a player with the capability `26143_VIDEO_HEVC-FullHD`,
- the **HEVC-FullHD-Enc** encoding capabilities as defined in clause 4.2.2.2 of TS 26.511 [4] to generate a bitstream from the video signal
- the capability to generate an ISO BMFF track from the bitstream that conforms with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="hvc1.2.4.L123.B0"` or an equivalently compatible media type.

The capability `26143_VIDEO_ENC_HEVC-UHD` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a video signal in real-time, such that the file can be played back by a player with the capability `26143_VIDEO_HEVC-UHD`,
- the **HEVC-UHD-Enc** encoding capabilities as defined in clause 4.2.2.2 of TS 26.511 [4] to generate a bitstream from the video signal
- the capability to generate an ISO BMFF track from the bitstream that conforms with the requirements of the sample entry 'hvc1' as defined in ISO/IEC 14496-15 [15].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="hvc1.2.4.L153.B0"` or an equivalently compatible media type.

5.7 Timed Text and Subtitles

5.7.1 Player and Decoding capabilities

The capability `26143_TT_3GPP` is defined as the capability of decoding and rendering a file that

- includes a track conforming to the sample entry 'tx3g' as defined in TS 26.245 [27] and
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_TT_3GPP` shall be signalled with `text/mp4, profile="3gp9" codecs="tx3g"` or an equivalently compatible media type.

The capability `26143_TT_IMSC11` is defined as the capability of decoding and rendering a file that

- includes a track conforming to the sample entry 'stpp' as defined in ISO/IEC 14496-30 [28] and
- is contained in a 3GP file that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.

In the context of this specification, the media type for files with this capability `26143_TT_IMSC11` shall be signalled with `application/mp4, profile="3gp9" codecs="stpp.ttml.im2t"` or an equivalently compatible media type.

5.7.2 MMBP Content Generator capabilities

The capability `26143_ENC_TT_3GPP` for a content generator is defined as the combination of the following capabilities:

- the capability to generate a file from a timed text signal, such that the file can be played back by a player with the capability `26143_TT_3GPP`,
- the capability to generate an ISO BMFF track from the bitstream track that conforms with the requirements of the sample entry 'tx3g' as defined in TS 26.245 [27].
- the generation of a 3GP file from the ISO BMFF track that conforms to the `26143_CONTAINER_MP4_3GP9` capability as defined in clause 5.2.
- the provisioning of media type signalling with the generated file using `video/mp4, profile="3gp9" codecs="tx3g"` or an equivalently compatible media type.

5.8 3D scenes and assets

The capability `26143_SCENE_GLTF20` is defined as the capability of rendering glTF 2.0 scenes as specified in [2] for which all components of the 3D scene are included as multiple parts in a *related MMBP* as defined in clause 4.4, for which the *root MMBP* is a glTF2.0 JSON document.

The capability `26143_SCENE_GLTF20_GLB` is defined as the capability of rendering glTF 2.0 scenes as specified in [2] for which all components of the 3D scene are either

- encapsulated in a GLB file, or
- included as multiple parts in a *related MMBP*, for which the *root MMBP* is a GLB file.

The capability `26143_SCENE_GLTF20_AR` is defined as the capability of `26143_SCENE_GLTF20` with the addition, that the scene may include `MPEG_anchor` extension, `EXT_lights_image_based` and `MPEG_lights_texture_based` extensions as defined in [3].

The capability `26143_SCENE_GLTF20_GLB_AR` is defined as the capability of `26143_SCENE_GLTF20_GLB` with the addition, that the scene may include `MPEG_anchor` extension, `EXT_lights_image_based` and `MPEG_lights_texture_based` extensions as defined in [3].

It is recommended that clients supporting such capabilities determine if the media can be safely processed prior to any processing and rendering.

In the context of this specification, the media type for scenes with this capability `26143_SCENE_GLTF20` and `26143_SCENE_GLTF20_GLB_AR` shall be signalled with `model/gltf+json` as defined in [2].

In the context of this specification, the media type for scenes with this capability `26143_SCENE_GLTF20_GLB` and `26143_SCENE_GLTF20_GLB_AR` shall be signalled with `model/gltf+binary` as defined in [2].

5.9 Presentation format

The capability `26143_PRESENTATION_HTML5` is defined as the capability of rendering HTML-5 content according to the profile defined TS 26.307 [31] with the following further restrictions:

- all components of the 3D scene are included as multiple parts in a *related MMBP* as defined in clause 4.4, for which the *root MMBP* is an HTML-5 document.
- the functionalities as defined in TS 26.307 [31], clause 4, are further restricted to the Markup in clause 4.2 and Style in clause 4.3.

NOTE: In order to address potential security risks, Scripting as defined in TS 26.307 [31], clause 4.4 is excluded from the capabilities.

- the APIs as defined in TS 26.307 [31], clause 5, are further restricted to the Forms API and the Canvas API.
- the media types may be further restricted.

NOTE: As this specification does not define mechanisms for referencing external content, any network APIs from TS 26.307 [31] are excluded.

It is recommended that clients supporting such capabilities determine if the media can be safely processed prior to any processing and rendering.

In the context of this specification, the media type for scenes with this capability `26143_PRESENTATION_HTML5` shall be signalled with `text/html` as defined in [2].

6 Messaging Media Profiles

6.1 Overview

This specification defines several messaging media profiles that apply for the player or the content generator.

6.2 Baseline MMBP Player Profile

6.2.1 Overview

The baseline MMBP Player profile is aligned with TS 26.140 [32].

The container format is based on IETF RFC 2045 [23] as the format for the MMBPs. Offering of alternative content in the container is permitted. In addition, the profile permits to encapsulate real-time video into the 3GP file format using the baseline profile. The container does not support external bodies, i.e. the MMBP is expected to be delivered as a single message. For details on the container format requirements, refer to clause 6.2.2.

The media types address basic text, audio/speech, images, video, text/subtitle, 3D scenes including AR as well as simple HTML-5 presentations.

Content conforming to the baseline MMBP player may include media types that are not explicitly supported by the media capabilities as defined in clause 6.2.3. Receivers shall ignore non-recognized media types. However, based on the container requirements, ignoring media types may result in specific processing requirements, for example pick an alternative, or ignore the entire MMBP.

Content generated to be compatible for playback on players for this profile as well as players exposing their capabilities should use the URN identifier `"urn:3GPP:26143:18:baseline-mmbp-player"`.

6.2.2 Container Format

The following capabilities for the container format as defined in clause 5.2.1 shall be supported:

- `26143_CONTAINER_RFC2046_SINGLE`
- `26143_CONTAINER_RFC2046_MIXED`
- `26143_CONTAINER_RFC2046_ALTERNATIVE`
- `26143_CONTAINER_RFC2387_RELATED`
- `26143_CONTAINER_MP4_3GP9`

The following capabilities for the container format as defined in clause 5.2 should be supported:

- 26143_CONTAINER_RFC2046_PARALLEL

In addition, `multipart/parallel` shall not be present in an MMBP on the same level if a 3GP file Rel-9 basic profile as defined in TS 26.244 [26] identified by the brand '3gp9' is present and contains more than on track.

6.2.3 Media Types

The capability `26143_TEXT_PLAIN` as defined in clause 5.3 shall be supported.

If still images are supported,

- the `26143_IMG_JPEG` capability as defined in clause 5.4.1 shall be supported,
- the `26143_IMG_HEIC` capability as defined in clause 5.4.1 should be supported.

If bitmap graphics are supported,

- the `26143_IMG_GIF` capability as defined in clause 5.4.1 should be supported.
- the `26143_IMG_PNG` capability as defined in clause 5.4.1 should be supported.

If the reception of audio or speech is supported, then the following applies:

- the `26143_AUDIO_EVS` capability as defined in clause 5.5.1 shall be supported.
- the `26143_AUDIO_AMR-WB` capability as defined in clause 5.5.1 shall be supported.
- the `26143_AUDIO_XHE-AAC` capability as defined in clause 5.5.1 should be supported.
- the `26143_AUDIO_AMR` capability as defined in clause 5.5.1 shall be supported.
- the `26143_AUDIO_EAAC+` capability as defined in clause 5.5.1 shall be supported.

If the reception of video is supported, then the following applies:

- the `26143_VIDEO_AVC-HD` capability as defined in clause 5.6.1 shall be supported.
- the `26143_VIDEO_HEVC-HD` capability as defined in clause 5.6.1 should be supported.

If the reception of HD-HDR video is supported, then the following applies:

- the `26143_VIDEO_AVC-FullHD` capability as defined in clause 5.6.1 shall be supported.
- the `26143_VIDEO_HEVC-FullHD` capability as defined in clause 5.6.1 shall be supported.
- the `26143_VIDEO_HEVC-UHD` capability as defined in clause 5.6.1 should be supported.

If timed text is supported,

- the `26143_TT_3GPP` capability as defined in clause 5.7.1 shall be supported.
- the `26143_TT_IMSC11` capability as defined in clause 5.7.1 should be supported.

If a processor for media type 'model' as defined in RFC2077 [33] is supported (i.e. a processor for 3D scenes and objects), then a processor for the media subtype 'model/gltf' should be supported. If a processor for the media subtype 'model/gltf' is supported,

- the `26143_SCENE_GLTF20` capability and the `26143_SCENE_GLTF20_GLB` capability as defined in clause 5.8 shall be supported assuming either a single body part or a `multipart/related` body part as defined in clause 5.2.
- and if the device is a device type as defined in TS 26.119 [34], clause 10, the `26143_SCENE_GLTF20_AR` and the `26143_SCENE_GLTF20_GLB_AR` capability as defined in clause 5.8 shall be supported assuming either a single body part or a `multipart/related` body part as defined in clause 5.2.

If a processor for the media type `text/html` is supported, the `26143_PRESENTATION_HTML5` capability as defined in clause 5.9 should be supported assuming either a single body part or a `multipart/related` body part as defined in clause 5.2. The media formats shall be restricted to the capabilities defined in this clause.

6.3 Baseline MMBP Generator Profile

6.3.1 Overview

The baseline MMBP Generator profile is aligned with TS 26.140 [32].

It primarily addresses the ability for users to generate content, for example on a mobile device.

The container format is based on IETF RFC 2045 [23] as the format for the MMBPs. Offering of alternative content is the container is permitted. In addition, the profile permits to encapsulate encapsulation of real-time video into the 3GP file format using the baseline profile. The container does not support external bodies, i.e. the MMBP is expected to be delivered as a single message. For details on the container format requirements, refer to clause 6.3.2.

The media types supported by this profile are basic text, audio/speech, images, video, and text.

Content conforming to the baseline MMBP generator profile may include media types that are not explicitly supported by the media capabilities as defined in clause 6.3.3. Receivers are expected to ignore non-recognized media types. However, based on the container requirements, ignoring media types may results in specific processing requirements, for example pick an alternative, or ignore the entire MMBP.

Additional packaging requirements and recommendations are provided in clause 6.3.4.

Content generated to be compatible for this profile as well as generators expose their capabilities should use the URN identifier `"urn:3GPP:26143:18:baseline-mmbp-generator"`.

6.3.2 Container Format

The following capabilities for the container format as defined in clause 5.2.2 shall be supported:

- `26143_CONTAINER_RFC2046_SINGLE_GEN`
- `26143_CONTAINER_RFC2046_MIXED_GEN`
- `26143_CONTAINER_MP4_3GP9_GEN`

The following capabilities for the container format as defined in clause 5.2 should be supported:

- `26143_CONTAINER_RFC2046_PARALLEL_GEN`
- `26143_CONTAINER_RFC2046_ALTERNATIVE_GEN`

6.3.3 Media Types

If the transmission of images is supported, then the following applies:

- the `26143_IMAGE_ENC_JPEG` capability as defined in clause 5.4.2 shall be supported.

If the transmission of speech is supported, then the following applies:

- the `26143_AUDIO_ENC_EVS` capability as defined in clause 5.5.2 shall be supported.
- the `26143_AUDIO_ENC_AMR-WB` capability as defined in clause 5.5.2 should be supported.
- the `26143_AUDIO_ENC_AMR` capability as defined in clause 5.5.2 may be supported.

If the transmission of audio is supported, then the following applies:

- the `26143_AUDIO_ENC_EAAC+` capability as defined in clause 5.5.2 shall be supported.

- the 26143_AUDIO_ENC_XHE-AAC capability as defined in clause 5.5.2 should be supported.

If the transmission of video is supported, then the following applies:

- the 26143_VIDEO_ENC_HEVC-FullHD capability as defined in clause 5.6.2 shall be supported.

If the transmission of timed text is supported, then the following applies:

- the 26143_TT_ENC_3GPP capability as defined in clause 5.7.2 shall be supported.

6.3.4 Packaging Requirements and Recommendations

For content generated by this baseline generator, `multipart/parallel` shall not be present in an MMBP on the same level if a 3GP file Rel-9 basic profile as defined in TS 26.244 [26] identified by the brand '3gp9' is present and contains more than one track.

NOTE: This avoids the necessity to playback multiple tracks included in a single file with tracks provided to the multipart MMBP in the parallel structure.

When generating a speech message, the MMBP Generator shall at least include an **EVS** Content together with potential alternatives.

When generating an Audio message, the MMBP Generator shall at least include an **eAAC+ stereo** Content together with potential alternatives.

Annex A (informative): Registration Information

A.1 3GPP Registered URIs

The clause documents the registered URIs in this specification following the process in <https://www.3gpp.org/3gpp-groups/core-network-terminals-ct/ct-wg1/uniform-resource-identifier-uri-list>,

Table A-1 lists all registered URN values as well as

- a brief description of its functionality;
- a reference to the specification or other publicly available document (if any) containing the definition;
- the name and email address of the person making the application; and
- any supplementary information considered necessary to support the application.

Table A-1: 3GPP Registered URNs

URN	Description	Reference	Contact	Remarks
urn:3GPP: 26143:18:baseline-mmbp- player	Media Messaging Baseline MMBP Player Profile	TS 26.143, clause 6.2.1	Thomas Stockhammer tsto@qti.qualcomm.com	none
urn:3GPP: 26143:18:baseline-mmbp- generator	Media Messaging Baseline MMBP Generator Profile	TS 26.143, clause 6.3.1	Thomas Stockhammer tsto@qti.qualcomm.com	none

Annex B (informative): Examples

NOTE: Examples are for further study

Annex Z (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2023-08	SA4#125	S4-231444				Initial draft	0.1.0
2023-11	SA4#126	S4-231670				New draft: S4-231993 (alignment from 26.140), S4-231958, S4-231871	0.2.0
2023-11	SA4-e (AH) MBS SWG post 126 (30 Nov. 2023)	S4al230180				New draft: S4al230183, S4al230184	0.3.0
2023-12	SA#102	SP-231575				Version 1.0.0 created by MCC	1.0.0
2024-02	SA4#127	S4-240214				Version 1.1.0 created by the editor Agreed pCRs: - S4-240365 - S4-240419 - S4-240420 - S4-240287	1.1.0
2024-03	SA#103	SP-240025				Version 2.0.0 created by MCC	2.0.0
2024-03	SA#103	SP-240502				Version 2.1.0 created by the editor. Agreed pCR: - SP-240284	2.1.0
2024-03	SA#103					version 18.0.0 created by MCC	18.0.0

History

Document history		
V18.0.0	May 2024	Publication