

ETSI TS 126 261 V18.0.0 (2024-07)



**5G;
Terminal audio quality performance requirements for
immersive audio services
(3GPP TS 26.261 version 18.0.0 Release 18)**



Reference

RTS/TSGS-0426261 vi00

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
ETSI [Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	5
1 Scope	6
2 References	6
3 Definitions of terms, symbols and abbreviations	6
3.1 Terms.....	6
3.2 Symbols.....	7
3.2 Abbreviations	7
4 Interfaces	7
4.1 General	7
4.2 Air interfaces.....	7
4.3 Acoustical interfaces	8
4.4 Electrical interfaces	8
5 Performance in sending.....	8
5.1 Applicability.....	8
5.2 Delay	8
5.3 Loudness.....	9
5.4 Frequency response	9
5.4.1 Frequency response for single source	9
5.4.1.1 General	9
5.4.1.2 Acoustical interface.....	9
5.4.1.3 Electrical interface	9
5.5 Directional information	10
5.5.1 Stereo	10
5.5.2 SBA	10
5.5.3 MASA.....	10
6 Performance in receiving.....	10
6.1 Applicability.....	10
6.2 Delay	10
6.3 Loudness.....	10
6.4 Frequency response	11
6.4.1 General	11
6.4.1.2 Acoustical interface.....	11
6.4.1.3 Electrical interface	12
6.5 Binaural rendering	12
6.5.1 ILD	12
6.5.2 ITD.....	12
7 Performance in sending+receiving.....	13
7.1 Applicability.....	13
7.2 Delay	13
Annex A (informative):	14
History	15

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, certain modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

NOTE 1: The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

NOTE 2: The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

NOTE 3: The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

NOTE 4: The constructions "can" and "cannot" shall not to be used as substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

NOTE 5: The constructions "is" and "is not" do not indicate requirements.

Introduction

TS 26.261 specifies minimum performance requirements for the electro-acoustic characteristics of LTE, NR and WLAN terminals when used to provide immersive services. The performance requirements are specified in the main body of the text; the test methods and test considerations are described in TS 26.260.

1 Scope

The present document specifies minimum performance requirements for the electro-acoustic characteristics of LTE, NR and WLAN terminal. It is applicable to any terminal capable of supporting wideband, super-wideband or fullband immersive services.

The set of minimum performance requirements enables a guaranteed level of speech quality while taking possible physical limits of the terminal design into account. Some performance objectives are also defined if such design limits can be overcome.

The present document covers both conversational services based on MTSI / telepresence and non-conversational services.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 26.260: "Objective test methodologies for the evaluation of immersive audio systems"
- [3] 3GPP TS 26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".
- [4] 3GPP TS 26.131: "Terminal Acoustic Characteristics for Telephony; Requirements".
- [5] ETSI TS 103 739 (2021-10) V1.4.1: "Transmission requirements for wideband mobile wireless terminals (handset and headset) from a QoS perspective as perceived by the user".
- [6] ETSI TS 103 740 (2021-10) V1.4.1: "Transmission requirements for wideband mobile wireless terminals (hands-free) from a QoS perspective as perceived by the user".

3 Definitions of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

For the purposes of the present document the terms *wideband*, *super-wideband* and *fullband* refer to test signals associated with the corresponding operating codec modes in TS 26.260.

The overload point (maximum load capacity) is for the purposes of this document defined as the RMS level of a digital representation of a full-scale pure tone at the input of the IVAS encoder. The overload point is defined in TS 26.260.

For the purposes of the present document, the term *electrical interface* is defined as an analogue or digital access to a UE, which allows injecting and capturing signals electrically instead of through an acoustical interface. The interface can be either analogue (wired) or digital (wired or wireless). The purpose of this interface is to connect a separate device (typically a headset), which provides a receiver and transmitter.

Stereo panorama: The spatial image of a stereo signal, in which the sound source directions lie in a range from -100% (left) to 100% (right).

3.2 Symbols

dB	Decibel
Hz	Unit of frequency (Hertz)
ϕ	Azimuth angle (phi)
θ	Elevation angle (theta)
T_R	UE delay in receiving direction
T_S	UE delay in sending direction
$\zeta(\phi)$	Estimate for a single source direction in the stereo panorama that is physically positioned in direction ϕ relative to the capturing device

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

DTX	Discontinuous Transmission
EVS	Enhanced Voice Services
HATS	Head and Torso Simulator
ILD	Interaural Level Difference
ISM	Independent Stream with Metadata
ITD	Interaural Time Difference
IVAS	Immersive Voice and Audio Services
MASA	Metadata-Assisted Spatial Audio
OMASA	Objects (ISM) with Metadata-Assisted Spatial Audio
OSBA	Objects (ISM) with Scene-Based Audio
POI	Point of Interconnection (with PSTN)
RLR	Receive Loudness Rating
SBA	Scene-Based Audio
SLR	Send Loudness Rating
WLAN	Wireless Local Area Network

4 Interfaces

4.1 General

The interfaces required to define immersive terminal electro-acoustic characteristics are shown in TS 26.260. These are the air interface and the point of interconnect (POI). The interfaces are shown for different types of immersive formats.

Measurements can be made using the system simulator (SS) described in TS 26.260. For conversational services, MTSI aspects are specified by TS 26.114 [3].

4.2 Air interfaces

The same air interfaces as in clause 4.2 of TS 26.131 [4] apply.

4.3 Acoustical interfaces

The acoustical interfaces are described in clause 5.4.2 of TS 26.260 [2].

4.4 Electrical interfaces

The electrical interface UE is considered in this specification and details on standardized analogue (wired) and digital (wired and wireless) electrical interfaces can be found in TS 26.260. For the electrical interface, the POI in sending / receiving direction is respectively defined as the input / output of the reference coder of the system simulator.

Any of the UE types mentioned in clause 4.3 providing an electrical interface can be considered as Electrical Interface UE.

5 Performance in sending

5.1 Applicability

The performance requirements in this clause shall apply when UE is used to provide immersive audio capture.

5.2 Delay

The UE delay T_s in send direction shall be less or equal to the delay requirements in Table 5.2.

Table 5.2: Requirement on sending UE delay

Audio format	Subformat	UE type(s)	Maximum delay T_s (ms)	
			Performance Requirement	Performance Objective
Stereo	Stereo	All	TBD	TBD
	Binaural	All	TBD	TBD
ISM	ISM1-ISM4	All	TBD	TBD
SBA	FOA	All	TBD	TBD
	HOA2	All	TBD	TBD
	HOA3	All	TBD	TBD
MASA	1 TC	All	TBD	TBD
	2 TC	All	TBD	TBD
OSBA	(ISM1-ISM4) x (FOA, HOA2, HOA3)	All	TBD	TBD
OMASA	(ISM1-ISM4) x MASA	All	TBD	TBD
Multichannel	5.1	All	TBD	TBD
	7.1	All	TBD	TBD
	5.1.2	All	TBD	TBD
	5.1.4	All	TBD	TBD
	7.1.4	All	TBD	TBD

NOTE: This requirement only applies for one-way (sending only) cases where round-delay does not apply.

Compliance shall be checked by the relevant tests described in TS 26.260.

5.3 Loudness

The nominal values of SLR to the POI shall be:

$$\text{SLR} = 13 \pm 3 \text{ dB}$$

NOTE: The value of 13 dB is motivated by the corresponding SLR requirement for desktop hands-free and handheld hands-free in TS 26.131 [4].

Compliance shall be checked by the relevant tests described in TS 26.260.

5.4 Frequency response

5.4.1 Frequency response for single source

5.4.1.1 General

The sensitivity/frequency characteristics shall be as follows.

The sending sensitivity frequency response, measured from the source direction under test to the SS audio output (digital output of the reference speech decoder of the SS), shall be within a mask, which can be drawn between the points given in the respective requirements table. The mask is drawn with straight lines between the breaking points in the requirements table on a logarithmic (frequency) - linear (dB sensitivity) scale.

5.4.1.2 Acoustical interface

The requirements for acoustical interface testing are given in Table 5.4.1.2.

Table 5.4.1.2: Sending sensitivity/frequency requirements table for acoustical interface

Frequency (Hz)	Upper limit (dB)	Lower limit (dB)
100	TBD	
200	TBD	TBD
300	TBD	TBD
4000	TBD	TBD
8000	TBD	TBD
12000	TBD	

Compliance shall be checked by the relevant tests described in TS 26.260.

5.4.1.3 Electrical interface

The requirements for electrical interface testing are given in Table 5.4.1.3.

Table 5.4.1.3: Sending sensitivity/frequency requirements table for electrical interface

Frequency (Hz)	Upper limit (dB)	Lower limit (dB)
100	TBD	
200	TBD	TBD
300	TBD	TBD
6000	TBD	TBD
8000	TBD	TBD
12000	TBD	

Compliance shall be checked by the relevant tests described in TS 26.260.

5.5 Directional information

5.5.1 Stereo

The estimated source directions in the stereo panorama $\zeta(\phi_i)$ shall be monotonically increasing between -60° and $+60^\circ$, i.e., $\zeta(\phi_i) - \zeta(\phi_{i-1}) \geq 10\%$ for $i = 3, \dots, 6$, where i is the source direction index according to Table 5 in TS 26.260. This requirement verifies that the estimated stereo panorama is consistent for the relevant source directions ϕ_i .

The estimated source directions in the stereo panorama shall provide a minimum and symmetric width between ϕ_2 and ϕ_6 , i.e., $|\zeta(\phi_2)|$ and $\zeta(\phi_6)$ shall be larger than or equal to 60%.

The estimated source directions in the stereo panorama shall be consistent at the edges, i.e., $\zeta(\phi_1) \leq \zeta(\phi_2)$ and $\zeta(\phi_7) \geq \zeta(\phi_6)$.

For frontal incidence position ($\phi_4 = 0^\circ$), the estimated sound source direction shall be in the center of the stereo panorama, i.e., $|\zeta(\phi_4)| < 3\%$.

For all $L = 7$ source directions of Table 5 in TS 26.260, the absolute value of ICTD shall be less than 1.5 ms.

Compliance shall be checked by the relevant tests described in TS 26.260.

5.5.2 SBA

The maximum absolute error ($|\phi_i - \hat{\phi}_i|$) shall be less than TBD degree for all directions.

The maximum absolute error of ($|\theta_i - \hat{\theta}_i|$) shall be less than TBD degree for all directions.

Compliance shall be checked by the relevant tests described in TS 26.260.

5.5.3 MASA

The maximum absolute error ($|\phi_i - \hat{\phi}_i|$) shall be less than TBD degree for all directions.

The maximum absolute error of ($|\theta_i - \hat{\theta}_i|$) shall be less than TBD degree for all directions.

Compliance shall be checked by the relevant tests described in TS 26.260.

6 Performance in receiving

6.1 Applicability

The performance requirements in this clause shall apply when UE is used to provide immersive audio rendering.

6.2 Delay

TBD

NOTE: this requirement only applies for one-way (receiving only) cases where round-delay does not apply.

Compliance shall be checked by the relevant tests described in TS 26.260.

6.3 Loudness

The nominal value of Loudness Level in Receive (LLR) shall be:

- 75 ± 4 phon for headset UE,
- 75 ± 4 phon for electrical interface UE (including binaural rendering and calibration),
- $67 -4/+8$ phon for handheld hands-free UE,
- 71 ± 4 phon for table-mounted hands-free UE,
- 75 ± 4 phon for loudspeaker UE.

In case a user controlled receive volume control is provided, for at least one setting of the control the LLR shall meet the nominal value.

When the control is set to maximum, the LLR shall not be louder than 89 phon for all UE types. With the volume control set to the minimum position the LLR shall not be quieter than 52 phon and should not be quieter than 58 phon for all UE types.

NOTE: The loudness level requirements are motivated by corresponding requirements in ETSI TS 103 739 [5] for desktop hands-free and handheld hands-free and in ETSI TS 103 740 [6] for headset, respectively.

Performance requirements and objectives apply for source position of azimuth 0° and elevation 0° in the test signal. They should also be evaluated for the source positions listed in Table 6.3, and results should be included in the test report.

Table 6.3: Additional source positions for loudness

Azimuth [°]	Elevation [°]
+90	0
-90	0
180	0
0	+90

Compliance shall be checked by the relevant tests described in TS 26.260.

6.4 Frequency response

6.4.1.1 General

The sensitivity/frequency characteristics shall be as follows.

The receiving sensitivity frequency response, measured either from the digital interface to the DRP with diffuse-field correction or from the SS audio input (analogue or digital input of the reference speech encoder of the SS) to the DRP with diffuse-field correction shall be within a mask, which can be drawn with straight lines between the breaking points in table 2 on a logarithmic (frequency) - linear (dB sensitivity) scale.

6.4.1.2 Acoustical interface

The requirements for acoustical interface testing are given in Table 6.4.1.2.

Table 6.4.1.2: Sending sensitivity/frequency requirements table for acoustical interface

Frequency (Hz)	Upper limit (dB)	Lower limit (dB)
100	TBD	
200	TBD	TBD
300	TBD	TBD
4000	TBD	TBD
8000	TBD	TBD
12000	TBD	

Compliance shall be checked by the relevant tests described in TS 26.260.

6.4.1.3 Electrical interface

The requirements for electrical interface testing are given in Table 6.4.1.3.

Table 6.4.1.3: Sending sensitivity/frequency requirements table for electrical interface

Frequency (Hz)	Upper limit (dB)	Lower limit (dB)
100	TBD	
200	TBD	TBD
300	TBD	TBD
6000	TBD	TBD
8000	TBD	TBD
12000	TBD	

Compliance shall be checked by the relevant tests described in TS 26.260.

6.5 Binaural rendering

6.5.1 ILD

For headset UE or electrical interface UE (if intended for headset usage), the UE shall pass ILD requirements defined in Table 6.5.1.

If the UE supports headtracking, the same requirements in Table 6.5.1 shall be met for each HATS orientation $\tilde{\varphi}_j \in \{0^\circ, -30^\circ, +30^\circ\}$.

NOTE: If the UE supports headtracking and the requirements are not met, the test operator should verify if the failure might be caused by an automatic reset of the reference orientation.

Table 6.5.1: ILD requirements

i	Source azimuth (°)	Source elevation (°)	500 Hz		1000 Hz		2000 Hz		4000 Hz		8000 Hz	
			Lower limit (dB)	Upper limit (dB)	Lower limit (dB)	Upper limit (dB)	Lower limit (dB)	Upper limit (dB)	Lower limit (dB)	Upper limit (dB)	Lower limit (dB)	Upper limit (dB)
1	0	0	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
2	180	0	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
3	0	90	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
4	90	0	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
5	-90 (270)	0	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD

Compliance shall be checked by the relevant tests described in TS 26.260.

6.5.2 ITD

For headset UE or electrical interface UE (if intended for headset usage), the UE shall pass ITD requirements defined in Table 6.5.2.

If the UE supports headtracking, the same requirements in Table 6.5.2 shall be met for each HATS orientation .

NOTE: If the UE supports headtracking and the requirements are not met, the test operator should verify if the failure might be caused by an automatic reset of the reference orientation.

Table 6.5.2: ITD requirements

i	Source azimuth (°)	Source elevation (°)	Lower limit (ms)	Upper limit (ms)
1	0	0	TBD	TBD
2	180	0	TBD	TBD
3	0	90	TBD	TBD
4	90	0	TBD	TBD
5	-90 (270)	0	TBD	TBD

Compliance shall be checked by the relevant tests described in TS 26.260.

7 Performance in sending+receiving

7.1 Applicability

The performance requirements in this clause shall apply when UE is used to provide end to end immersive audio, including both capture and rendering.

7.2 Delay

TBD

NOTE: This requirement does not apply for one-way scenarios, delay corresponds here to complete terminal delay.

Annex A (informative):

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2019-04	SA4#103	S4-190426				Initial version	0.0.1
2024-05	SA4#128	S4-241235				Definition of initial clauses and revision of structure	0.1.0
2024-05	SA4#128	S4-241333				Inclusion of preliminary requirements	0.2.0
2024-06	SA4-e (AH) Audio SWG post 128	SA4aA24003 2				Additional requirements, improvements and editorial changes	0.3.0
2024-06						Version 1.0.0 created by MCC	1.0.0
2024-06						Version 18.0.0 created by MCC upon TSG approval	18.0.0

History

Document history		
V18.0.0	July 2024	Publication