

# ETSI TS 129 329 V19.1.0 (2026-02)



TECHNICAL SPECIFICATION

**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
5G;  
Sh interface based on the Diameter protocol;  
Protocol details  
(3GPP TS 29.329 version 19.1.0 Release 19)**



A GLOBAL INITIATIVE

---

**Reference**

RTS/TSGC-0429329vj10

---

**Keywords**

5G, GSM, LTE, UMTS

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from the  
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,  
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to  
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our  
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.  
All rights reserved.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope .....	8
2 References .....	8
3 Definitions, symbols and abbreviations .....	9
3.1 Definitions .....	9
3.2 Abbreviations .....	9
4 General .....	9
5 Use of the Diameter base protocol .....	9
6 Diameter application for Sh interface .....	9
6.1 Command-Code values .....	10
6.1.1 User-Data-Request (UDR) Command .....	10
6.1.2 User-Data-Answer (UDA) Command .....	11
6.1.3 Profile-Update-Request (PUR) Command.....	11
6.1.4 Profile-Update-Answer (PUA) Command.....	12
6.1.5 Subscribe-Notifications-Request (SNR) Command .....	12
6.1.6 Subscribe-Notifications-Answer (SNA) Command.....	13
6.1.7 Push-Notification-Request (PNR) Command.....	14
6.1.8 Push-Notifications-Answer (PNA) Command.....	14
6.2 Result-Code AVP values.....	15
6.2.1 Success.....	15
6.2.2 Permanent Failures .....	15
6.2.2.1 DIAMETER_ERROR_USER_DATA_NOT_RECOGNIZED (5100).....	15
6.2.2.2 DIAMETER_ERROR_OPERATION_NOT_ALLOWED (5101).....	15
6.2.2.3 DIAMETER_ERROR_USER_DATA_CANNOT_BE_READ (5102).....	15
6.2.2.4 DIAMETER_ERROR_USER_DATA_CANNOT_BE_MODIFIED (5103).....	15
6.2.2.5 DIAMETER_ERROR_USER_DATA_CANNOT_BE_NOTIFIED (5104).....	15
6.2.2.6 DIAMETER_ERROR_TOO_MUCH_DATA (5008).....	15
6.2.2.7 DIAMETER_ERROR_TRANSPARENT_DATA_OUT_OF_SYNC (5105).....	15
6.2.2.8 DIAMETER_ERROR_FEATURE_UNSUPPORTED (5011).....	15
6.2.2.9 DIAMETER_ERROR_SUBS_DATA_ABSENT (5106).....	15
6.2.2.10 DIAMETER_ERROR_NO_SUBSCRIPTION_TO_DATA (5107).....	16
6.2.2.11 DIAMETER_ERROR_DSAI_NOT_AVAILABLE (5108).....	16
6.2.2.12 DIAMETER_ERROR_IDENTITIES_DONT_MATCH (5002).....	16
6.2.3 Transient Failures .....	16
6.2.3.1 DIAMETER_USER_DATA_NOT_AVAILABLE (4100) .....	16
6.2.3.2 DIAMETER_PRIOR_UPDATE_IN_PROGRESS (4101).....	16
6.3 AVPs .....	17
6.3.1 User-Identity AVP .....	18
6.3.2 MSISDN AVP .....	18
6.3.3 User-Data AVP .....	18
6.3.4 Data-Reference AVP .....	18
6.3.5 Service-Indication AVP.....	19
6.3.6 Subs-Req-Type AVP .....	19
6.3.7 Requested-Domain AVP.....	20
6.3.7A Requested-Nodes AVP .....	20
6.3.8 Current-Location AVP.....	20
6.3.9 Server-Name AVP .....	20
6.3.10 Identity-Set AVP .....	20
6.3.11 Supported-Features AVP .....	21

6.3.12	Feature-List-ID AVP .....	21
6.3.13	Feature-List AVP .....	21
6.3.14	Supported-Applications AVP .....	21
6.3.15	Public-Identity AVP .....	21
6.3.16	Expiry-Time AVP .....	21
6.3.17	Send-Data-Indication AVP .....	21
6.3.18	DSAI-Tag AVP .....	21
6.3.19	Wildcarded-Public-Identity AVP .....	21
6.3.20	Wildcarded-IMPU AVP .....	21
6.3.21	Session-Priority AVP .....	21
6.3.22	One-Time-Notification AVP .....	21
6.3.23	Serving-Node-Indication AVP .....	22
6.3.24	Repository-Data-ID AVP .....	22
6.3.25	Sequence-Number AVP .....	22
6.3.26	Pre-paging-Supported AVP .....	22
6.3.27	Local-Time-Zone-Indication AVP .....	22
6.3.28	UDR-Flags .....	22
6.3.29	Call-Reference-Info AVP .....	23
6.3.30	Call-Reference-Number AVP .....	23
6.3.31	AS-Number AVP .....	23
6.3.32	OC-Supported-Features .....	23
6.3.33	OC-OLR .....	23
6.3.34	DRMP AVP .....	23
6.3.35	Load .....	23
6.4	Use of namespaces .....	23
6.4.1	AVP codes .....	24
6.4.2	Experimental-Result-Code AVP values .....	24
6.4.3	Command Code values .....	24
6.4.4	Application-ID value .....	24
7	Special Requirements .....	25
7.1	Version Control .....	25
8	Diameter application of Sh-ee for IMS events subscription/notification .....	26
8.1	Command-Code values .....	26
8.1.1	Event-Subscribe-Request (ESR) Command .....	26
8.1.2	Event-Subscribe-Answer (ESA) Command .....	27
8.1.3	Event-Notification-Request (ENR) Command .....	27
8.1.4	Event-Notification-Answer (ENA) Command .....	28
8.2	Result-Code AVP values .....	29
8.2.1	Success .....	29
8.2.2	Permanent Failures .....	29
8.2.2.1	DIAMETER_INVALID_AVP_VALUE (5004) .....	29
8.2.2.2	DIAMETER_ERROR_OPERATION_NOT_ALLOWED (5101) .....	29
8.2.3	Transient Failures .....	29
8.3	AVPs .....	30
8.3.1	Any-User-Indication AVP .....	30
8.3.2	Subscription-Identity AVP .....	30
8.3.3	Notification-Address AVP .....	31
8.3.4	Notification-Correlation-Identity AVP .....	31
8.3.5	Event-Reporting-Options AVP .....	31
8.3.6	Report-Mode AVP .....	31
8.3.7	One-Time-Report AVP .....	31
8.3.8	Max-Number-of-Reports AVP .....	31
8.3.9	Report-Period AVP .....	32
8.3.10	Event-List AVP .....	32
8.3.11	Ims-Event AVP .....	32
8.3.12	Ims-Event-Filter AVP .....	32
8.3.13	Ims-Event-Report AVP .....	33
8.3.14	Ims-Event-Report-Information AVP .....	33
8.3.15	Adc-Report AVP .....	33
8.3.16	Bdc-Report AVP .....	33

8.3.17	Session-Identity AVP .....	33
8.3.18	Timestamp AVP .....	34
8.3.19	App-Bind-Information AVP .....	34
8.3.20	App-Dc-Information AVP .....	34
8.3.21	Application-Identity AVP .....	34
8.3.22	Stream-Identity AVP .....	34
8.3.23	Adc-Endpoint-Type AVP .....	34
8.3.24	Calling-Identity AVP .....	34
8.3.25	Called-Identity AVP .....	35
8.4	Use of namespaces .....	35
8.4.1	AVP codes .....	35
8.4.2	Experimental-Result-Code AVP values.....	35
8.4.3	Command Code values .....	35
8.4.4	Application-ID value .....	35
<b>Annex A (informative):</b>	<b>Change history .....</b>	<b>36</b>
History .....		40

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

---

# 1 Scope

The present document defines a transport protocol for use in the IP multimedia (IM) Core Network (CN) subsystem based on the Diameter base protocol as specified in IETF RFC 6733 [15].

The present document is applicable to:

- The Sh interface between an AS and the HSS.
- The Sh interface between an SCS and the HSS.

Whenever it is possible this document specifies the requirements for this protocol by reference to specifications produced by the IETF within the scope of Diameter base protocol as specified in IETF RFC 6733 [15]. Where this is not possible, extensions to the Diameter base protocol as specified in IETF RFC 6733 [15] are defined within this document.

---

# 2 References

The following documents contain provisions, which through reference in this text constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 29.328 "IP Multimedia (IM) Subsystem Sh interface; signalling flows and message contents".
- [2] 3GPP TS 33.210 "3G Security; Network Domain Security; IP Network Layer Security".
- [3] IETF RFC 2960 "Stream Control Transmission Protocol".
- [4] Void.
- [5] IETF RFC 2234 "Augmented BNF for syntax specifications".
- [6] 3GPP TS 29.229 "Cx and Dx Interfaces based on the Diameter protocol; protocol details".
- [7] IETF RFC 3589 "Diameter Command Codes for Third Generation Partnership Project (3GPP) Release 5".
- [8] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [9] 3GPP TR 33.978 "Security aspects of early IP Multimedia Subsystem (IMS) (Release 6)".
- [10] 3GPP TS 29.364 "IMS Application Server Service Data Descriptions for AS interoperability".
- [11] 3GPP TS 29.002 "Mobile Application Part (MAP) specification".
- [12] IETF RFC 7683: "Diameter Overload Indication Conveyance".
- [13] IETF RFC 7944: "Diameter Routing Message Priority".
- [14] IETF RFC 8583: "Diameter Load Information Conveyance".
- [15] IETF RFC 6733: "Diameter Base Protocol".
- [16] 3GPP TS 29.336: "Home Subscriber Server (HSS) diameter interfaces for interworking with packet data networks and applications".

[17] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

Refer to IETF RFC 6733 [15] for the definitions of some terms used in this document.

For the purposes of the present document, the following terms and definitions apply.

**Attribute-Value Pair:** see IETF RFC 6733 [15], it corresponds to an Information Element in a Diameter message.

**Server:** SIP-server.

**User data:** user profile data.

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAA	Authentication, Authorization and Accounting
AS	Application Server
ABNF	Augmented Backus-Naur Form
AVP	Attribute-Value Pair
CN	Core Network
DRMP	Diameter Routing Message Priority
DSCP	Differentiated Services Code Point
HSS	Home Subscriber Server
IANA	Internet Assigned Numbers Authority
IETF	Internet Engineering Task Force
IMS	IP Multimedia Subsystem
NDS	Network Domain Security
RFC	Request For Comment
SCTP	Stream Control Transport Protocol
UCS	Universal Character Set
URL	Uniform Resource Locator
UTF	UCS Transformation Formats

---

## 4 General

The Diameter base protocol as specified in IETF RFC 6733 [15] shall apply except as modified by the defined support of the methods and the defined support of the commands and AVPs, result and event codes specified in clause 6 and 8 of this specification. Unless otherwise specified, the procedures (including error handling and unrecognised information handling) are unmodified.

---

## 5 Use of the Diameter base protocol

The same clarifications of clause 5 of 3GPP TS 29.229 [6] shall apply to the Sh interface. An exception is that the application identifier for this application is defined in chapter 6 and 8.

---

## 6 Diameter application for Sh interface

This clause specifies a Diameter application that allows a Diameter server and a Diameter client:

- to download and update transparent and non-transparent user data
- to request and send notifications on changes on user data

The Sh interface protocol is defined as an IETF vendor specific Diameter application, where the vendor is 3GPP. The vendor identifier assigned by IANA to 3GPP ( <http://www.iana.org/assignments/enterprise-numbers>) is 10415.

The Diameter application identifier assigned to the Sh interface application is 16777217 (allocated by IANA).

## 6.1 Command-Code values

This clause defines Command-Code values for this Diameter application.

Every command is defined by means of the ABNF syntax (as defined in RFC 2234 [5]), according to the Command Code Format (CCF) specification defined in IETF RFC 6733 [15]. Whenever the definition and use of an AVP is not specified in this document, what is stated in 3GPP TS 29.229 [6] shall apply.

**NOTE:** As the Diameter commands described in this specification have been defined based on the former specification of the Diameter base protocol, the Vendor-Specific-Application-Id AVP is still listed as a required AVP (an AVP indicated as {AVP}) in the command code format specifications defined in this specification to avoid backward compatibility issues, even if the use of this AVP has been deprecated in the new specification of the Diameter base protocol (IETF RFC 6733 [15]).

The command codes for the Sh interface application are taken from the range allocated by IANA in IETF RFC 3589 [7] as assigned in this specification. For these commands, the Application-ID field shall be set to 16777217 (application identifier of the Sh interface application, allocated by IANA).

The following Command Codes are defined in this specification:

**Table 6.1.1: Command-Code values**

Command-Name	Abbreviation	Code	Clause
User-Data-Request	UDR	306	6.1.1
User-Data-Answer	UDA	306	6.1.2
Profile-Update-Request	PUR	307	6.1.3
Profile-Update-Answer	PUA	307	6.1.4
Subscribe-Notifications-Request	SNR	308	6.1.5
Subscribe-Notifications-Answer	SNA	308	6.1.6
Push-Notification-Request	PNR	309	6.1.7
Push-Notification-Answer	PNA	309	6.1.8

### 6.1.1 User-Data-Request (UDR) Command

The User-Data-Request (UDR) command, indicated by the Command-Code field set to 306 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to request user data.

Message Format

```

< User-Data -Request > ::= < Diameter Header: 306, REQ, PXY, 16777217 >
  < Session-Id >
  [ DRMP ]
  { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Destination-Host ]
  { Destination-Realm }
    * [ Supported-Features ]
    { User-Identity }
    [ Wildcarded-Public-Identity ]
    [ Wildcarded-IMPU ]
    [ Server-Name ]

```

```

    * [ Service-Indication ]
    * { Data-Reference }
    * [ Identity-Set ]
    [ Requested-Domain ]
    [ Current-Location ]
    * [ DSAI-Tag ]
    [ Session-Priority ]
    [ User-Name ]
    [ Requested-Nodes ]
    [ Serving-Node-Indication ]
    [ Pre-paging-Supported ]
    [ Local-Time-Zone-Indication ]
    [ UDR-Flags ]
    [ Call-Reference-Info ]
    [ OC-Supported-Features ]

    * [ AVP ]
    * [ Proxy-Info ]
    * [ Route-Record ]

```

## 6.1.2 User-Data-Answer (UDA) Command

The User-Data-Answer (UDA) command, indicated by the Command-Code field set to 306 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the User-Data-Request command. The Experimental-Result AVP may contain one of the values defined in clause 6.2 or in 3GPP TS 29.229 [6].

Message Format

```

< User-Data-Answer > ::= < Diameter Header: 306, PXY, 16777217 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    * [ Supported-Features ]
    [ Wildcarded-Public-Identity ]
    [ Wildcarded-IMPU ]
    [ User-Data ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    * [ Load ]
    * [ AVP ]
    [ Failed-AVP ]
    * [ Proxy-Info ]

    * [ Route-Record ]

```

## 6.1.3 Profile-Update-Request (PUR) Command

The Profile-Update-Request (PUR) command, indicated by the Command-Code field set to 307 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to update user data in the server.

Message Format

```

< Profile-Update-Request > ::= < Diameter Header: 307, REQ, PXY, 16777217 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }

```

```

[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
{ User-Identity }
[ Wildcarded-Public-Identity ]
[ Wildcarded-IMPU ]
[ User-Name ]
*{ Data-Reference }
{ User-Data }
[ OC-Supported-Features ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

NOTE: More than one Data-Reference AVP may be present in the message only if both the AS and the HSS support the Update-Eff-Enhance feature. How the AS knows whether the HSS supports the Update-Eff-Enhance feature is implementation issue, e.g. the AS can get the information from a previous PUA message.

## 6.1.4 Profile-Update-Answer (PUA) Command

The Profile-Update-Answer (PUA) command, indicated by the Command-Code field set to 307 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the Profile-Update-Request command. The Experimental-Result AVP may contain one of the values defined in clause 6.2 or in 3GPP TS 29.229 [6].

Message Format

```

< Profile-Update-Answer > ::= < Diameter Header: 307, PXY, 16777217 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Wildcarded-Public-Identity ]
    [ Wildcarded-IMPU ]
    [ Repository-Data-ID ]
    [ Data-Reference ]
    *[ Supported-Features ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    *[ Load ]
    *[ AVP ]
    [ Failed-AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]

```

NOTE: The Data-Reference AVP may be present in the message only if both the AS and the HSS support the Update-Eff-Enhance feature.

## 6.1.5 Subscribe-Notifications-Request (SNR) Command

The Subscribe-Notifications-Request (SNR) command, indicated by the Command-Code field set to 308 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to request notifications of changes in user data.

Message Format

```

< Subscribe-Notifications-Request > ::= < Diameter Header: 308, REQ, PXY, 16777217 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Destination-Host ]
    { Destination-Realm }
    * [ Supported-Features ]
    { User-Identity }
    [ Wildcarded-Public-Identity ]
    [ Wildcarded-IMPU ]
    * [ Service-Indication ]
    [ Send-Data-Indication ]
    [ Server-Name ]
    { Subs-Req-Type }
    * { Data-Reference }
    * [ Identity-Set ]
    [ Expiry-Time ]
    * [ DSAI-Tag ]
    [ One-Time-Notification ]
    [ User-Name ]
    [ OC-Supported-Features ]

    * [ AVP ]
    * [ Proxy-Info ]
    * [ Route-Record ]

```

### 6.1.6 Subscribe-Notifications-Answer (SNA) Command

The Subscribe-Notifications-Answer command, indicated by the Command-Code field set to 308 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the Subscribe-Notifications-Request command. The Result-Code or Experimental-Result AVP may contain one of the values defined in clause 6.2 or in 3GPP TS 29.229 [6].

#### Message Format

```

< Subscribe-Notifications-Answer > ::= < Diameter Header: 308, PXY, 16777217 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    [ Result-Code ]
    [ Experimental-Result ]
    { Origin-Host }
    { Origin-Realm }
    [ Wildcarded-Public-Identity ]
    [ Wildcarded-IMPU ]
    * [ Supported-Features ]
    [ User-Data ]
    [ Expiry-Time ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    * [ Load ]
    * [ AVP ]
    [ Failed-AVP ]
    * [ Proxy-Info ]
    * [ Route-Record ]

```

## 6.1.7 Push-Notification-Request (PNR) Command

The Push-Notification-Request (PNR) command, indicated by the Command-Code field set to 309 and the 'R' bit set in the Command Flags field, is sent by a Diameter server to a Diameter client in order to notify changes in the user data in the server.

### Message Format

```
< Push-Notification-Request > ::= < Diameter Header: 309, REQ, PXY, 16777217 >
< Session-Id >
[ DRMP ]
{ Vendor-Specific-Application-Id }
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
{ Destination-Host }
{ Destination-Realm }
*[ Supported-Features ]
{ User-Identity }
[ Wildcarded-Public-Identity ]
[ Wildcarded-IMPU ]
[ User-Name ]
{ User-Data }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]
```

## 6.1.8 Push-Notifications-Answer (PNA) Command

The Push-Notifications-Answer (PNA) command, indicated by the Command-Code field set to 309 and the 'R' bit cleared in the Command Flags field, is sent by a client in response to the Push-Notification-Request command. The Experimental-Result AVP may contain one of the values defined in clause 6.2 or in 3GPP TS 29.229 [6].

### Message Format

```
< Push-Notification-Answer > ::= < Diameter Header: 309, PXY, 16777217 >
< Session-Id >
[ DRMP ]
{ Vendor-Specific-Application-Id }
[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
*[ AVP ]
[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]
```

## 6.2 Result-Code AVP values

This clause defines new result code values that must be supported by all Diameter implementations that conform to this specification. The result codes defined in 3GPP TS 29.229 [6] are also applicable. When one of the result codes defined here is included in a response, it shall be inside an Experimental-Result AVP and Result-Code AVP shall be absent.

### 6.2.1 Success

Result codes that fall within the Success category are used to inform a peer that a request has been successfully completed.

No result codes within this category have been defined so far.

### 6.2.2 Permanent Failures

Errors that fall within the Permanent Failures category are used to inform the peer that the request failed, and should not be attempted again.

#### 6.2.2.1 DIAMETER\_ERROR\_USER\_DATA\_NOT\_RECOGNIZED (5100)

The data received by the AS is not supported or recognized.

#### 6.2.2.2 DIAMETER\_ERROR\_OPERATION\_NOT\_ALLOWED (5101)

The requested operation is not allowed for the user

#### 6.2.2.3 DIAMETER\_ERROR\_USER\_DATA\_CANNOT\_BE\_READ (5102)

The requested user data is not allowed to be read.

#### 6.2.2.4 DIAMETER\_ERROR\_USER\_DATA\_CANNOT\_BE\_MODIFIED (5103)

The requested user data is not allowed to be modified.

#### 6.2.2.5 DIAMETER\_ERROR\_USER\_DATA\_CANNOT\_BE\_NOTIFIED (5104)

The requested user data is not allowed to be notified on changes.

#### 6.2.2.6 DIAMETER\_ERROR\_TOO\_MUCH\_DATA (5008)

The size of the data pushed to the receiving entity exceeds its capacity. This error code is defined in 3GPP TS 29.229 [6].

#### 6.2.2.7 DIAMETER\_ERROR\_TRANSPARENT\_DATA\_OUT\_OF\_SYNC (5105)

The request to update the repository data at the HSS could not be completed because the requested update is based on an out-of-date version of the repository data. That is, the sequence number in the Sh-Update Request message, does not match with the immediate successor of the associated sequence number stored for that repository data at the HSS. It is also used where an AS tries to create a new set of repository data when the identified repository data already exists in the HSS.

#### 6.2.2.8 DIAMETER\_ERROR\_FEATURE\_UNSUPPORTED (5011)

See 3GPP TS 29.229 [6] clause 6.2.2.11.

#### 6.2.2.9 DIAMETER\_ERROR\_SUBS\_DATA\_ABSENT (5106)

The Application Server requested to subscribe to changes to Repository Data that is not present in the HSS.

#### 6.2.2.10 DIAMETER\_ERROR\_NO\_SUBSCRIPTION\_TO\_DATA (5107)

The AS received a notification of changes of some information to which it is not subscribed.

#### 6.2.2.11 DIAMETER\_ERROR\_DSAI\_NOT\_AVAILABLE (5108)

The Application Server addressed a DSAI not configured in the HSS.

#### 6.2.2.12 DIAMETER\_ERROR\_IDENTITIES\_DONT\_MATCH (5002)

See 3GPP TS 29.229 [6]

### 6.2.3 Transient Failures

Errors that fall within the transient failures category are those used to inform a peer that the request could not be satisfied at the time that it was received. The request may be able to be satisfied in the future.

#### 6.2.3.1 DIAMETER\_USER\_DATA\_NOT\_AVAILABLE (4100)

The requested user data is not available at this time to satisfy the requested operation.

#### 6.2.3.2 DIAMETER\_PRIOR\_UPDATE\_IN\_PROGRESS (4101)

The request to update data at the HSS could not be completed for one of the following reasons:

- If the Data Reference is Repository Data, then the related Repository Data is currently being updated by another entity;
- If the Data Reference is other than Repository Data, then the related data is currently being updated.

## 6.3 AVPs

The following table describes the Diameter AVPs defined for the Sh interface protocol, their AVP Code values, types, possible flag values and whether the AVP may or not be encrypted.

**Table 6.3.1: Diameter Multimedia Application AVPs**

Attribute Name	AVP Code	Clause defined	Value Type	AVP Flag rules				May Encrypt
				Must	May	Should not	Must not	
User-Identity	700	6.3.1	Grouped	M, V				No
MSISDN	701	6.3.2	OctetString	M, V				No
User-Data	702	6.3.3	OctetString	M, V				No
Data-Reference	703	6.3.4	Enumerated	M, V				No
Service-Indication	704	6.3.5	OctetString	M, V				No
Subs-Req-Type	705	6.3.6	Enumerated	M, V				No
Requested-Domain	706	6.3.7	Enumerated	M, V				No
Current-Location	707	6.3.8	Enumerated	M, V				No
Identity-Set	708	6.3.10	Enumerated	V			M	No
Expiry-Time	709	6.3.16	Time	V			M	No
Send-Data-Indication	710	6.3.17	Enumerated	V			M	No
Server-Name	602	6.3.9	UTF8String	M, V				No
Supported-Features	628	6.3.11	Grouped	V	M			No
Feature-List-ID	629	6.3.12	Unsigned32	V			M	No
Feature-List	630	6.3.13	Unsigned32	V			M	No
Supported-Applications	631	6.3.14	Grouped	V			M	No
Public-Identity	601	6.3.15	UTF8String	M, V				No
DSAI-Tag	711	6.3.18	OctetString	M, V				No
Wildcarded-Public-Identity	634	6.3.19	UTF8String	V			M	No
Wildcarded-IMPU	636	6.3.20	UTF8String	V			M	No
Session-Priority	650	6.3.21	Enumerated	V			M	No
One-Time-Notification	712	6.3.22	Enumerated	V			M	No
Requested-Nodes	713	6.3.7A	Unsigned32	V			M	No
Serving-Node-Indication	714	6.3.23	Enumerated	V			M	No
Repository-Data-ID	715	6.3.24	Grouped	V			M	No
Sequence-Number	716	6.3.25	Unsigned32	V			M	No
Pre-paging-Supported	717	6.3.26	Enumerated	V			M	No
Local-Time-Zone-Indication	718	6.3.27	Enumerated	V			M	No
UDR-Flags	719	6.3.28	Unsigned32	V			M	No
Call-Reference-Info	720	6.3.29	Grouped	V			M	No
Call-Reference-Number	721	6.3.30	OctetString	V			M	No
AS-Number	722	6.3.31	OctetString	V			M	No
OC-Supported-Features	621 NOTE 3	6.3.32	Grouped				M, V	No
OC-OLR	623 NOTE 3	6.3.33	Grouped				M, V	No
DRMP	301 NOTE 4	6.3.34	Enumerated				M, V	No
Load	NOTE 5	6.3.35	Grouped				M, V	No

NOTE 1: The AVP header bit denoted as 'M', indicates whether support of the AVP is required. The AVP header bit denoted as 'V', indicates whether the optional Vendor-ID field is present in the AVP header. For further details, see 3GPP TS 29.229 [6].

NOTE 2: If the M-bit is set for an AVP and the receiver does not understand the AVP, it shall return a rejection. If the M-bit is not set for an AVP, the receiver shall not return a rejection, whether or not it understands the AVP. If the receiver understands the AVP but the M-bit value does not match with the definition in this table, the receiver shall ignore the M-bit.

NOTE 3: The value of these attributes is defined in IETF RFC 7683 [12].

NOTE 4: The value of this attribute is defined in IETF RFC 7944 [13].

NOTE 5: The value of this attribute is defined in IETF RFC 8583 [14].

The following table specifies the Diameter AVPs re-used by the Sh interface protocol from existing Diameter Applications, including a reference to their respective specifications and when needed, a short description of their use within Sh.

**Table 6.3/2: Sh re-used Diameter AVPs**

Attribute Name	Reference	Comments	M-bit
External-Identifier	3GPP TS 29.336 [16]		Must set
NOTE 1: The M-bit settings for re-used AVPs override those of the defining specifications that are referenced. Values include: "Must set", "Must not set". If the M-bit setting is blank, then the defining specification applies.			
NOTE 2: If the M-bit is set for an AVP and the receiver does not understand the AVP, it shall return a rejection. If the M-bit is not set for an AVP, the receiver shall not return a rejection, whether or not it understands the AVP. If the receiver understands the AVP but the M-bit value does not match with the definition in this table, the receiver shall ignore the M-bit.			

### 6.3.1 User-Identity AVP

The User-Identity AVP is of type Grouped. This AVP contains either a Public-Identity AVP or an MSISDN AVP or an External-Identifier AVP.

AVP format

User-Identity ::= <AVP header: 700 10415>

[Public-Identity]

[MSISDN]

[External-Identifier]

\*[AVP]

### 6.3.2 MSISDN AVP

The MSISDN AVP is of type OctetString. This AVP contains an MSISDN, in international number format as described in ITU-T Rec E.164 [8], encoded as a TBCD-string, i.e. digits from 0 through 9 are encoded 0000 to 1001; 1111 is used as a filler when there is an odd number of digits; bits 8 to 5 of octet n encode digit 2n; bits 4 to 1 of octet n encode digit 2(n-1)+1.

### 6.3.3 User-Data AVP

The User-Data AVP is of type OctetString. This AVP contains the user data requested in the UDR/UDA, SNR/SNA and PNR/PNA operations and the data to be modified in the PUR/PUA operation. The exact content and format of this AVP is described in 3GPP TS 29.328 [1] Annex C as Sh-Data.

### 6.3.4 Data-Reference AVP

The Data-Reference AVP is of type Enumerated, and indicates the type of the requested user data in the operation UDR and SNR. Its exact values and meaning is defined in 3GPP TS 29.328 [1]. The following values are defined (more details are given in 3GPP TS 29.328 [1]):

RepositoryData (0)

IMSPublicIdentity (10)

IMSUserState (11)

S-CSCFName (12)

InitialFilterCriteria (13)

This value is used to request initial filter criteria relevant to the requesting AS

LocationInformation (14)

UserState (15)

ChargingInformation (16)

MSISDN (17)

PSIActivation (18)

DSAI (19)

ServiceLevelTraceInfo (21)

IPAddressSecureBindingInformation (22)

ServicePriorityLevel (23)

SMSRegistrationInfo (24)

UEReachabilityForIP (25)

TADSinformation (26)

STN-SR (27)

UE-SRVCC-Capability (28)

ExtendedPriority (29)

CSRN (30)

ReferenceLocationInformation (31)

IMSI (32)

IMSPrivateUserIdentity (33)

IMEISV (34)

UE-5G-SRVCC-Capability (35)

ASRegistrationInfo (36)

NOTE: Value 20 is reserved.

### 6.3.5 Service-Indication AVP

The Service-Indication AVP is of type OctetString. This AVP contains the Service Indication that identifies a service or a set of services in an AS and the related repository data in the HSS. Standardized values of Service-Indication identifying a standardized service or set of services in the AS and standardized format of the related repository data are defined in 3GPP TS 29.364 [10].

### 6.3.6 Subs-Req-Type AVP

The Subs-Req-Type AVP is of type Enumerated, and indicates the type of the subscription-to-notifications request. The following values are defined:

Subscribe (0)

This value is used by an AS to subscribe to notifications of changes in data.

Unsubscribe (1)

This value is used by an AS to unsubscribe to notifications of changes in data.

### 6.3.7 Requested-Domain AVP

The Requested-Domain AVP is of type Enumerated, and indicates the access domain for which certain data (e.g. user state) are requested. The following values are defined:

CS-Domain (0)

The requested data apply to the CS domain.

PS-Domain (1)

The requested data apply to the PS domain.

### 6.3.7A Requested-Nodes AVP

The Requested-Nodes AVP is of type Unsigned32 and it shall contain a bit mask. The meaning of the bits shall be as defined in table 6.3.7A/1:

**Table 6.3.7A/1: Requested-Nodes**

Bit	Name	Description
0	MME	The requested data apply to the MME
1	SGSN	The requested data apply to the SGSN
2	3GPP-AAA-SERVER-TWAN	The requested data apply to the 3GPP AAA Server for TWAN
3	AMF	The requested data apply to the AMF (for 3GPP access)

### 6.3.8 Current-Location AVP

The Current-Location AVP is of type Enumerated, and indicates whether an active location retrieval has to be initiated or not:

DoNotNeedInitiateActiveLocationRetrieval (0)

The request indicates that the initiation of an active location retrieval is not required.

InitiateActiveLocationRetrieval (1)

It is requested that an active location retrieval is initiated.

### 6.3.9 Server-Name AVP

The Server-Name contains a SIP-URL used to identify an AS. See 3GPP TS 29.229 [6] for further description of this AVP.

### 6.3.10 Identity-Set AVP

The Identity-Set AVP is of type Enumerated and indicates the requested set of IMS Public Identities. The following values are defined:

ALL\_IDENTITIES (0)

REGISTERED\_IDENTITIES (1)

IMPLICIT\_IDENTITIES (2)

ALIAS\_IDENTITIES (3)

### 6.3.11 Supported-Features AVP

See 3GPP TS 29.229 [6] clause 6.3.29.

### 6.3.12 Feature-List-ID AVP

See 3GPP TS 29.229 [6] clause 6.3.30.

### 6.3.13 Feature-List AVP

See 3GPP TS 29.229 [6] clause 6.3.31.

### 6.3.14 Supported-Applications AVP

See 3GPP TS 29.229 [6] clause 6.3.32.

### 6.3.15 Public-Identity AVP

The Public-Identity AVP contains a Public User Identity. See 3GPP TS 29.229 [6] for the definition of this AVP.

### 6.3.16 Expiry-Time AVP

The Expiry-Time AVP is of type Time. This AVP contains the expiry time of subscriptions to notifications in the HSS.

### 6.3.17 Send-Data-Indication AVP

The Send-Data-Indication AVP is of type Enumerated. If present it indicates that the sender requests the User-Data. The following values are defined:

USER\_DATA\_NOT\_REQUESTED (0)

USER\_DATA\_REQUESTED (1)

### 6.3.18 DSAI-Tag AVP

The DSAI-Tag AVP is of type OctetString. This AVP contains the DSAI-Tag identifying the instance of the Dynamic Service Activation Information being accessed for the Public Identity.

### 6.3.19 Wildcarded-Public-Identity AVP

See 3GPP TS 29.229 [6] clause 6.3.35 for the definition of the Wildcarded-Public-Identity AVP. This AVP only contains a Wildcarded PSI over Sh interface.

### 6.3.20 Wildcarded-IMPU AVP

See 3GPP TS 29.229 [6] clause 6.3.43.

### 6.3.21 Session-Priority AVP

See 3GPP TS 29.229 [6] clause 6.3.56.

### 6.3.22 One-Time-Notification AVP

The One-Time-Notification AVP is of type Enumerated. If present it indicates that the sender requests to be notified only one time. The following values are defined:

ONE\_TIME\_NOTIFICATION\_REQUESTED (0)

This AVP is only applicable to UE reachability for IP (25)

### 6.3.23 Serving-Node-Indication AVP

The Serving-Node-Indication AVP is of type Enumerated. If present it indicates that the sender does not require any location information other than the Serving Node Addresses/Identities requested (e.g. MME name, VLR number). Other location information (e.g. Global Cell ID, Tracking Area ID) may be absent. The following values are defined:

ONLY\_SERVING\_NODES\_REQUIRED (0)

### 6.3.24 Repository-Data-ID AVP

The Repository-Data-ID AVP is of type Grouped. This AVP shall contain a Service-Indication AVP and a Sequence-Number AVP.

AVP format

Repository-Data-ID ::= <AVP header: 715 10415>

{Service-Indication}

{Sequence-Number}

\*[AVP]

### 6.3.25 Sequence-Number AVP

The Sequence-Number AVP is of type Unsigned32. This AVP contains a number associated to a repository data.

### 6.3.26 Pre-paging-Supported AVP

The Pre-paging-Supported AVP is of type Enumerated. It indicates whether the sender supports pre-paging or not. The following values are defined:

PREPAGING\_NOT\_SUPPORTED (0)

PREPAGING\_SUPPORTED (1)

If this AVP is not present in the command, the default value is PREPAGING\_NOT\_SUPPORTED (0).

### 6.3.27 Local-Time-Zone-Indication AVP

The Local-Time-Zone-Indication AVP is of type Enumerated. If present it indicates that the Local Time Zone information (time zone and daylight saving time) of the visited network where the UE is attached is requested with or without other location information. The following values are defined:

ONLY\_LOCAL\_TIME\_ZONE\_REQUESTED (0)

LOCAL\_TIME\_ZONE\_WITH\_LOCATION\_INFO\_REQUESTED (1)

### 6.3.28 UDR-Flags

The UDR-Flags AVP is of type Unsigned32 and it shall contain a bit mask. The meaning of the bits shall be as defined in 3GPP TS 29.328 [1].

**Table 6.3.28/1: UDR-Flags**

Bit	Name
0	Location-Information-EPS-Supported
1	RAT-Type-Requested
NOTE:	Bits not defined in this table shall be cleared by the sender of the request and discarded by the receiver of the request.

### 6.3.29 Call-Reference-Info AVP

The Call-Reference-Info AVP is of type Grouped. This AVP shall contain a Call-Reference-Number AVP and an AS-Number AVP.

AVP format

```

Call-Reference-Info ::= <AVP header: 720 10415>
    { Call-Reference-Number }
    { AS-Number }
    *[AVP]

```

### 6.3.30 Call-Reference-Number AVP

The Call-Reference-Number AVP is of type OctetString. The exact content and format of this AVP is described in 3GPP TS 29.002 [11].

### 6.3.31 AS-Number AVP

The AS-Number AVP is of type OctetString. The exact content and format of this AVP corresponds to the gmsc-address parameter described in 3GPP TS 29.002 [11].

### 6.3.32 OC-Supported-Features

The OC-Supported-Features AVP is of type Grouped and it is defined in IETF RFC 7683 [12]. This AVP is used to support Diameter overload control mechanism.

### 6.3.33 OC-OLR

The OC-OLR AVP is of type Grouped and it is defined in IETF RFC 7683 [12]. This AVP is used to support Diameter overload control mechanism.

### 6.3.34 DRMP AVP

The DRMP AVP is of type Enumerated and it is defined in IETF RFC 7944 [13]. This AVP allows the HSS/SLF and the AS/OSA SCS to indicate the relative priority of Diameter messages. The DRMP AVP may be used to set the DSCP marking for transport of the associated Diameter message.

### 6.3.35 Load

The Load AVP is of type Grouped and it is defined in IETF RFC 8583 [14]. This AVP is used to support the Diameter load control mechanism.

## 6.4 Use of namespaces

This clause contains the namespaces that have either been created in this specification, or the values assigned to existing namespaces managed by IANA.

### 6.4.1 AVP codes

This specification assigns the AVP values from the AVP Code namespace managed by 3GPP for its Diameter vendor-specific applications. See clause 6.3 for the assignment of the namespace in this specification.

### 6.4.2 Experimental-Result-Code AVP values

This specification has assigned Experimental-Result-Code AVP values 4100-4101 and 5100-5105. See clause 6.2.

### 6.4.3 Command Code values

This specification assigns the values 306-309 from the range allocated by IANA to 3GPP in IETF RFC 3589 [7].

### 6.4.4 Application-ID value

IANA has allocated the value 16777217 for the 3GPP Sh interface application.

## 7 Special Requirements

### 7.1 Version Control

The version control mechanisms specified in 3GPP TS 29.229 [6] clauses 7.1, 7.2 and 7.3 apply to this specification.

The following table of features shall apply to the Sh interface.

**Table 7.1.1: Features of feature list 1 used in Sh**

Feature bit	Feature	M/O	Description
0	Notif-Eff	M	This feature is applicable to the UDR/UDA, SNR/SNA and PNR/PNA command pairs. It requires support in both the HSS and the AS. If multiple subscriptions to notifications are associated with a Public User Identity, the HSS may combine the notifications for multiple Data References and/or Service Indications and/or Identity Sets into a single Push-Notification-Request message. The User-Data-Request / Answer and the Subscribe-Notifications-Request / Answer allow multiple Data References, Service Indications and Identity Sets. The User-Data-Answer and Push-Notification-Request allow combining multiple DataReference items resulting in the User Data AVP including a single XML document with the separable XML clauses populated.
1	Update-Eff	O	This feature is applicable to the PUR/PUA commands. If both the HSS and the AS support this feature, a PUR command where the Data reference type is Repository Data, may contain an XML document with several Repository Data instances.
2	Update-Eff-Enhance	O	This feature is an enhancement of the Update-Eff feature and requires Update-Eff is supported. It is applicable to the PUR/PUA commands. If both the HSS and the AS support this feature, a PUR command may contain an XML document with several Data instances.
3	Additional-MSISDN	O	This feature is applicable to UDR/UDA commands. It requires support in both HSS and AS. If enabled, it extends the information returned with DataReference=17. Instead of returning only MSISDN, it includes ExtendedMSISDN. See 3GPP TS 29.328 [1] for more information.
Feature bit: The order number of the bit within the Supported-Features AVP, e.g. "1". Feature: A short name that can be used to refer to the bit and to the feature, e.g. "MOM". M/O: Defines if the implementation of the feature is mandatory ("M") or optional ("O"). Description: A clear textual description of the feature.			

The following table shall apply to the Sh interface; the column Application identifier lists the used application identifiers on Sh and 3GPP.

**Table 7.1.2: Application identifiers used in Sh**

Application identifier	First applied
16777217	3GPP Rel-5

## 8 Diameter application of Sh-ee for IMS events subscription/notification

This clause specifies a Diameter application named Sh-ee that allows:

- An HSS can subscribe to receive notifications from the AS of IMS event.
- The AS can notify an HSS of IMS events for which the HSS previously had subscribed

The Sh interface protocol is defined as an IETF vendor specific Diameter application, where the vendor is 3GPP. The vendor identifier assigned by IANA to 3GPP ( <http://www.iana.org/assignments/enterprise-numbers>) is 10415.

The Diameter application identifier assigned to Sh-ee application of the IMS events subscription/notification is **xx1** (allocated by IANA).

*Editor's Note: The value will be allocated by IANA.*

### 8.1 Command-Code values

This clause defines Command-Code values for this Diameter application.

Every command is defined by means of the ABNF syntax (as defined in RFC 2234 [5]), according to the Command Code Format (CCF) specification defined in IETF RFC 6733 [15]. Whenever the definition and use of an AVP is not specified in this document, what is stated in 3GPP TS 29.229 [6] shall apply.

**NOTE:** As the Diameter commands described in this specification have been defined based on the former specification of the Diameter base protocol, the Vendor-Specific-Application-Id AVP is still listed as a required AVP (an AVP indicated as {AVP}) in the command code format specifications defined in this specification to avoid backward compatibility issues, even if the use of this AVP has been deprecated in the new specification of the Diameter base protocol (IETF RFC 6733 [15]).

The command codes for the Sh-ee application of IMS events subscription/notification are taken from the range allocated by IANA in IETF RFC 3589 [7] as assigned in this specification. For these commands, the Application-ID field shall be set to **xx1** (application identifier of the Sh-ee application, allocated by IANA).

The following Command Codes are defined in this specification:

**Table 8.1.1: Command-Code values**

Command-Name	Abbreviation	Code	Clause
Event-Subscribe-Request	ESR	310	8.1.1
Event-Subscribe-Answer	ESA	310	8.1.2
Event-Notification-Request	ENR	311	8.1.3
Event-Notification-Answer	ENA	311	8.1.4

#### 8.1.1 Event-Subscribe-Request (ESR) Command

The Event-Subscribe-Request (ESR) command, indicated by the Command-Code field set to 310 and the 'R' bit set in the Command Flags field, is sent by a Diameter Multimedia client to a Diameter Multimedia server in order to subscribe to notifications for when a specific IMS event for a specified IMS Public User Identity is updated.

Message Format

```
<Event-Subscribe-Request> ::= < Diameter Header: 310, REQ, PXY, xx1 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
```

```

[ Destination-Host ]
{ Destination-Realm }
[ User-Name ]
[ OC-Supported-Features ]
*[ Supported-Features ]
[ Public-Identity ]
[ Any-User-Indication ]
{ Subs-Req-Type }
[ Send-Data-Indication ]
[ Expiry-Time ]
{ Event-Reporting-Options }
{ Event-List }
{ Notification-Address }
[ Notification-Correlation-Identity ]
*[ AVP ]
*[ Proxy-Info ]*[ Route-Record ]

```

### 8.1.2 Event-Subscribe-Answer (ESA) Command

The Event-Subscribe-Answer (ESA) command, indicated by the Command-Code field set to 310 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the Event-Subscribe-Request command. The Experimental-Result AVP may contain one of the values defined in clause 8.2.

Message Format

```

<Event-Subscribe-Answer> ::= < Diameter Header: 310, PXY, xx1 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ User-Name ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    *[ Load ]
    *[ Supported-Features ]
    [ Ims-Event-Report ]
    *{ Event-List }
    { Subscription-Identity }
    { Expiry-Time }
    *[ AVP ]
    [ Failed-AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]

```

### 8.1.3 Event-Notification-Request (ENR) Command

The Event-Notification-Request (ENR) command, indicated by the Command-Code field set to 311 and the 'R' bit set in the Command Flags field, is sent by a Diameter Multimedia client to a Diameter Multimedia server in order to notify IMS event for which the HSS previously had subscribed.

Message Format

```

<Event-Notification-Request> ::= < Diameter Header: 311, PXY, xx1 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }

```

```

[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ User-Name ]
[ OC-Supported-Features ]
[ OC-OLR ]
*[ Load ]
*[ Supported-Features ]
{ Public-Identity }
{ Ims-Event }
[ Ims-Event-Report ]
{ Notification-Correction-Identity }
{ Timestamp }
*[ AVP ]
[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

#### 8.1.4 Event-Notification-Answer (ENA) Command

The Event-Notification-Answer (ENA) command, indicated by the Command-Code field set to 311 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the Event-Notification-Request command. The Experimental-Result AVP may contain one of the values defined in clause 8.2.

Message Format

```

<Event-Notification-Answer> ::= < Diameter Header: 311, PXY, xx1 >
    < Session-Id >
    [ DRMP ]
    { Vendor-Specific-Application-Id }
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ User-Name ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    *[ Load ]
    *[ Supported-Features ]
    *[ AVP ]
    [ Failed-AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]

```

## 8.2 Result-Code AVP values

This clause defines new result code values that must be supported by all Diameter implementations that conform to this specification. The result codes defined in 3GPP TS 29.229 [6] are also applicable. When one of the result codes defined here is included in a response, it shall be inside an Experimental-Result AVP and Result-Code AVP shall be absent.

### 8.2.1 Success

Result codes that fall within the Success category are used to inform a peer that a request has been successfully completed.

No result codes within this category have been defined so far.

### 8.2.2 Permanent Failures

Errors that fall within the Permanent Failures category are used to inform the peer that the request failed, and should not be attempted again.

#### 8.2.2.1 DIAMETER\_INVALID\_AVP\_VALUE (5004)

The notification correlation identity received by the HSS is not supported or recognized.

#### 8.2.2.2 DIAMETER\_ERROR\_OPERATION\_NOT\_ALLOWED (5101)

The requested operation is not allowed for the user.

### 8.2.3 Transient Failures

Errors that fall within the transient failures category are those used to inform a peer that the request could not be satisfied at the time that it was received. The request may be able to be satisfied in the future.

## 8.3 AVPs

The following table describes the Diameter application of Sh-ee for IMS events subscription/notification AVPs, their AVP Code values, types, possible flag values and whether the AVP may or not be encrypted.

**Table 8.3.1: Diameter Application of IMS events subscription/notification AVPs**

Attribute Name	AVP Code	Clause defined	Value Type	AVP Flag rules				May Encrypt
				Must	May	Should not	Must not	
Public-Identity	601	6.3.15	UTF8String	M, V				No
Any-User-Indication	723	8.3.1	Enumerated	M,V				No
Subscription-Identity	724	8.3.2	UTF8String	M,V				No
Notification-Address	725	8.3.3	UTF8String	M,V				No
Notification-Correlation-Identity	726	8.3.4	UTF8String	M,V				No
Event-Reporting-Options	727	8.3.5	Grouped	M,V				No
Report-Mode	728	8.3.6	Enumerated	M,V				No
One-Time-Report	729	8.3.7	Enumerated	M,V				No
Max-Number-of-Reports	730	8.3.8	Unsigned32	M,V				No
Report-Period	731	8.3.9	Unsigned32	M,V				No
Event-List	732	8.3.10	Grouped	M,V				No
Ims-Event	733	8.3.11	Enumerated	M,V				No
Ims-Event-Filter	734	8.3.12	Grouped	M,V				No
Event-Report	735	8.3.13	Grouped	M,V				No
Ims-Event-Report-Information	736	8.3.14	Grouped	M,V				No
Adc-Report	737	8.3.15	Enumerated	M,V				No
Bdc-Report	738	8.3.16	Enumerated	M,V				No
Session-Identity	739	8.3.17	UTF8String	M,V				No
Timestamp	740	8.3.18	Time	M,V				No
App-Bind-Information	741	8.3.19	Grouped	M,V				No
App-Dc-Information	742	8.3.20	Grouped	M,V				No
Application-Identity	743	8.3.21	UTF8String	M,V				No
Stream-Identity	744	8.3.22	UTF8String	M,V				No
Adc-Endpoint-Type	745	8.3.23	Enumerated	M,V				No
Calling-Identity	746	8.3.24	UTF8String	M,V				No
Called-Identity	747	8.3.25	UTF8String	M,V				No

NOTE 1: The AVP header bit denoted as 'M', indicates whether support of the AVP is required. The AVP header bit denoted as 'V', indicates whether the optional Vendor-ID field is present in the AVP header. For further details, see 3GPP TS 29.229 [6].

NOTE 2: If the M-bit is set for an AVP and the receiver does not understand the AVP, it shall return a rejection. If the M-bit is not set for an AVP, the receiver shall not return a rejection, whether or not it understands the AVP. If the receiver understands the AVP but the M-bit value does not match with the definition in this table, the receiver shall ignore the M-bit.

NOTE 3: The value of these attributes is defined in IETF RFC 7683 [12].

NOTE 4: The value of this attribute is defined in IETF RFC 7944 [13].

NOTE 5: The value of this attribute is defined in IETF RFC 8583 [14].

### 8.3.1 Any-User-Indication AVP

The Any-User-Indication AVP is of type Enumerated and indicates whether the request applies to any UE. The following values are defined:

ANY\_UE\_NOT\_APPLICABLE (0)

The request indicates that the request is not applicable for any UE.

ANY\_UE\_APPLICABLE (1)

The request indicates that the request is applicable for any UE.

### 8.3.2 Subscription-Identity AVP

The Subscription-Identity AVP is of type UTF8String. This AVP contains the subscription ID.

### 8.3.3 Notification-Address AVP

The Notification-Address AVP is of type UTF8String. This AVP contains the recipient of notifications sent by the NF consumer. The syntax of this AVP corresponds with the format defined in IETF RFC 3986 [17].

### 8.3.4 Notification-Correlation-Identity AVP

The Notification-Correlation-Identity AVP is of type UTF8String. This AVP contains the notification correlation ID shall be present by NF consumer in subscription.

### 8.3.5 Event-Reporting-Options AVP

The Event-Reporting-Options AVP is of type Grouped. This AVP shall contain Report-Mode AVP, One-Time-Report AVP, One-Time-Notification AVP, Max-Number-of-Reports AVP, Report-Period AVP, and Expiry Time AVP.

AVP format

```
Event-Reporting-Options ::= <AVP header: 727 10415>
    [ Report-Mode ]
    [ One-Time-Report ]
    [ One-Time-Notification ]
    [ Max-Number-of-Reports ]
    [ Report-Period ]
    [ Expiry Time ]
    *[ AVP ]
```

### 8.3.6 Report-Mode AVP

The Report-Mode AVP is of type Enumerated and indicates the mode of report. The following values are defined:

ON\_EVENT\_DETECTION (0)

The request indicates that the report is sent based on event detection.

PERIODIC (1)

The request indicates that the report is periodically sent.

### 8.3.7 One-Time-Report AVP

The One-Time-Report AVP is of type Enumerated and indicates whether one time report is requested if immediate report is requested. The following values are defined:

ONE\_TIME\_REPORT\_NOT\_REQUESTED (0)

The request indicates that continuous notification is requested after the immediate report (if any) with the currently associated status is returned in the response.

ONE\_TIME\_REPORT\_REQUESTED (1)

The request indicates that a single notification or status report is requested.

### 8.3.8 Max-Number-of-Reports AVP

The Max-Number-of-Reports AVP is of type Unsigned32. This AVP contains the maximum number of reports.

### 8.3.9 Report-Period AVP

The Report-Period AVP is of type Unsigned32. This AVP contains the interval time between which the event notification is reported, shall be present if reportMode is "PERIODIC".

### 8.3.10 Event-List AVP

The Event-List AVP is of type Grouped. This AVP shall contain Ims-Event AVP, Event Information AVP, Request Current Status AVP and Ims Event Filter AVP.

AVP format

```
Event-List ::= <AVP header: 732 10415>
    { Ims-Event }
    [ Request Current Status ]
    *[ Ims Event Filter ]
    *[ AVP ]
```

### 8.3.11 Ims-Event AVP

The Ims-Event AVP is of type Enumerated and indicates the IMS event. The following values are defined:

ADC\_ESTABLISHMENT (0)

The request indicates the application data channel establishment event.

ADC\_RELEASE (1)

The request indicates the application data channel release event.

BDC\_ESTABLISHMENT (2)

The request indicates bootstrap data channel establishment event.

BDC\_RELEASE (3)

The request indicates the bootstrap data channel release event.

ADC\_IWK\_ESTABLISHMENT (4)

The request indicates the application data channel requiring interworking establishment event.

### 8.3.12 Ims-Event-Filter AVP

The Ims-Event-Filter AVP is of type Grouped. This AVP shall contain Calling-Identity AVP, Called-Identity AVP, App-Bin-Information AVP, and Session-Identity AVP.

AVP format

```
Ims-Event-Filter ::= <AVP header: 734 10415>
    [ Calling-Identity ]
    [ Called-Identity ]
    [ App-Bind-Information ]
    [ Session-Identity ]
    *[ AVP ]
```

### 8.3.13 Ims-Event-Report AVP

The Ims-Event-Report AVP is of type Grouped. This AVP shall contain Ims-Event AVP, Ims-Event-Report-Information AVP and Session-Identity AVP.

AVP format

```
Ims-Event-Report ::= <AVP header: 735 10415>
    { Ims-Event }
    [ Ims-Event-Report-Information ]
    [ Session-Identity ]
    *[ AVP ]
```

### 8.3.14 Ims-Event-Report-Information AVP

The Ims-Event-Report-Information AVP is of type Grouped. This AVP shall contain Adc-Report AVP and Bdc-Report AVP.

AVP format

```
Ims-Event-Report-Information ::= <AVP header: 736 10415>
    [ Adc-Report ]
    [ Bdc-Report ]
    *[ AVP ]
```

### 8.3.15 Adc-Report AVP

The Adc-Report AVP is of type Enumerated and indicates the ADC event status. The following values are defined:

ADC\_ESTABLISHMENT (0)

The request indicates the application data channel establishment event.

ADC\_RELEASE (1)

The request indicates the application data channel release event.

ADC\_IWK\_ESTABLISHMENT (2)

The request indicates the application data channel requiring interworking establishment event.

### 8.3.16 Bdc-Report AVP

The Bdc-Report AVP is of type Enumerated and indicates the BDC event status. The following values are defined:

BDC\_ESTABLISHMENT (0)

The request indicates bootstrap data channel establishment event.

BDC\_RELEASE (1)

The request indicates the bootstrap data channel release event.

### 8.3.17 Session-Identity AVP

The Session-Identity AVP is of type UTF8String. This AVP contains the IMS session ID.

### 8.3.18 Timestamp AVP

The Timestamp AVP is of type Time. This AVP contains the time at which the event is observed.

### 8.3.19 App-Bind-Information AVP

The App-Bind-Information AVP is of type Grouped. This AVP contains the data channel application binding information.

AVP format

```
App-Bind-Information ::= <AVP header: 741 10415>
    { Application-Identity }
    *[ App-Dc-Information ]
    *[AVP]
```

### 8.3.20 App-Dc-Information AVP

The App-Dc-Information AVP is of type Grouped. This AVP represents information of the remote endpoint type of application data channels.

AVP format

```
App-Dc-Information ::= <AVP header: 742 10415>
    { Stream-Identity }
    [ Adc-Endpoint-Type ]
    *[AVP]
```

### 8.3.21 Application-Identity AVP

The Application-Identity AVP is of type UTF8String. This AVP contains the application ID.

### 8.3.22 Stream-Identity AVP

The Stream-Identity AVP is of type UTF8String. This AVP contains the stream ID of the data channel.

### 8.3.23 Adc-Endpoint-Type AVP

The Adc-Endpoint-Type AVP is of type Enumerated and indicates the remote endpoint type of the ADC. The following values are defined:

UE (0)

The request indicates the remote endpoint type of the application data channel is the peer UE.

SERVER (1)

The request indicates the remote endpoint type of the application data channel is the application server.

### 8.3.24 Calling-Identity AVP

The Calling-Identity AVP is of type UTF8String. This AVP contains the public identity of the calling subscriber. The exact content and format of this AVP corresponds to the Public-Identity AVP described in 3GPP TS 29.229 [6].

### 8.3.25 Called-Identity AVP

The Called-Identity AVP is of type UTF8String. This AVP contains the public identity of the called subscriber. The exact content and format of this AVP corresponds to the Public-Identity AVP described in 3GPP TS 29.229 [6].

## 8.4 Use of namespaces

This clause contains the namespaces that have either been created in this specification, or the values assigned to existing namespaces managed by IANA.

### 8.4.1 AVP codes

This specification assigns the AVP values from the AVP Code namespace managed by 3GPP for its Diameter vendor-specific applications. See clause 6.3 for the assignment of the namespace in this specification.

### 8.4.2 Experimental-Result-Code AVP values

This specification has assigned Experimental-Result-Code AVP values 4100-4101 and 5100-5105. See clause 8.2.

### 8.4.3 Command Code values

This specification assigns the values 310-311 from the range allocated by IANA to 3GPP in IETF RFC 3589 [7].

### 8.4.4 Application-ID value

IANA has allocated the value **xx1** for the 3GPP Sh-ee application.

## Annex A (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
June 2002	CN#16	NP-020266				Version 2.0.1 present in CN#16 for approval	5.0.0
Sep 2002	CN#17	NP-020450	2	1		Cancellation of subscriptions to notifications	5.1.0
Sep 2002	CN#17	NP-020450	3	1		Addition of AVPs to User-Data-Request	5.1.0
Dec 2002	CN#18	NP-020592	6	-		Error handling in HSS when being updated with too much data	5.2.0
Mar 2003	CN#19	NP-030102	005	1		Initial Filter Criteria	5.3.0
Mar 2003	CN#19	NP-030102	007	2		Update after Diameter has become RFC	5.3.0
Mar 2003	CN#19	NP-030102	011	-		Missing code-point in Data-Reference AVP	5.3.0
Mar 2003	CN#19	NP-030102	013	-		Registration State Alignment	5.3.0
Mar 2003	CN#19	NP-030102	008	-		Correction of the Application Server Identification type for Initial Filter Criteria usage	5.3.0
Mar 2003	CN#19	NP-030102	009	-		Clarification on Sh interface for charging purposes	5.3.0
Jun 2003	CN#20	NP-030216	014	1		Co-ordination of Update of Repository Data	5.4.0
Jun 2003	CN#20	NP-030216	015	1		Command code correction for UDA plus editorial corrections	5.4.0
Jun 2003	CN#20	NP-030216	016	-		Correction on Current-Location AVP values	5.4.0
Jun 2003	CN#20	NP-030216	018	-		Correction to the use of User-Identity	5.4.0
Jun 2003	CN#20	NP-030216	019	1		Correction to the use of Data-Reference	5.4.0
Dec 2003	CN#22					Editorial changes in application IDs and references [4] and [7].	5.4.1
Mar 2004	CN#23	NP-040135	031	1		Add MSISDN to set of Data that may be downloaded	5.5.0
Mar 2004	CN#23	NP-040055	032	2		Introduction of 'Identity-Set' AVP	6.0.0
Jun 2004	CN#24	NP-040216	037	-		Correction to description of Data Reference AVP value 10	6.1.0
Jun 2004	CN#24	NP-040216	035	1		Correction of reference for definition of MSISDN	6.1.0
Sep 2004	CN#25	NP-040394	043	-		Incorrect Data-Reference AVP in Subscriber Notification Answer Command	6.2.0
Sep 2004	CN#25	NP-040395	046	1		Application version control	6.2.0
Sep 2004	CN#25	NP-040394	041	1		Public-Identity is unspecified for the Sh interface	6.2.0
Sep 2004	CN#25	NP-040395	045	1		Single Public_Identity required in Grouped User-Identity AVP	6.2.0
Sep 2004	CN#25	NP-040394	049	-		Correction of the Application-Id code	6.2.0
Sep 2004	CN#25	NP-040412	051	1		Re-numbering of 3GPP specific AVP codes	6.2.0
Dec 2004	CN#26	NP-040578	053	-		Sh ABNF corrections	6.3.0
Mar 2005	CN#27	NP-050031	057	1		Introduction of Failed AVP	6.4.0
Mar 2005	CN#27	NP-050031	064	-		Sh-Update needs to include Data-Reference to be future proof	6.4.0
Jun 2005	CT#28	CP-050216	069	-		Sh UDR correction	6.5.0
Jun 2005	CT#28	CP-050087	070	-		Correction of references	6.5.0
Jun 2005	CT#28	CP-050087	071	1		Corrections to message parameters	6.5.0
Jun 2005	CT#28	CP-050087	072	1		Miscellaneous Corrections	6.5.0
Jun 2005	CT#28	CP-050216	074	-		Correction to allow realm based routing	6.5.0
Sep 2005	CT#29	CP-050424	075	-		Identity-Set correction	6.6.0
Sep 2005	CT#29	CP-050422	095	1		State the condition for encryption of the Data Reference	6.6.0
Sep 2005	CT#29	CP-050423	097	1		Early IMS Security based protection for the Ut interface	6.6.0
Dec 2005	CT#30	CP-050625	098	3		Notification & Query Efficiency	7.0.0
Dec 2005	CT#30	CP-050625	099	1		Management of subscriptions	7.0.0
Mar 2006	CT#31	CP-060084	010 0	1		User-Data in the response to Sh-Subs-Notif	7.1.0
Mar 2006	CT#31	CP-060084	010 1	3		New error indications for the Sh-Subs-Notif procedure	7.1.0
Jun 2006	CT#32	CP-060319	010 5	2		Sh interface efficiency improvement	7.2.0
Sep 2006	CT#33	CP-060417	010 7	2		Introduction of Activation State Information for IMS (DSAI)	7.3.0
Sep 2006	CT#33	CP-060417	010 8	-		Addition of AVPs in SNR and SNA	7.3.0
Sep 2006	CT#33	CP-060417	011 0	1		Public User Identity Grouping Information	7.3.0
Sep 2006	CT#33	CP-060405	011 2	-		Missing Data Reference value	7.3.0
Sep 2006	CT#33	CP-060417	011 3	1		Errors to be sent in response to Sh-Notif	7.3.0
Sep 2007	CT#37	CP-070527	011 8	-		Define User-Data AVP	7.4.0
Sep 2007	CT#37	CP-070527	011 9	1		Wildcarded PSI as key in the Sh Interface	7.4.0
Nov 2007	CT#38	CP-070743	012 0	-		ABNF correction for UDR and SNR	7.5.0
Nov 2007	CT#38	CP-070743	012 1	1		PNR for Subscriptions to Notifications for all Identity Sets	7.5.0
Mar 2008	CT#39	CP-080019	012 2	-		Wildcarded Public User Identities	8.0.0

Jun 2008	CT#40	CP-080267	012 3	1	DSAI Corrections	8.1.0
Jun 2008	CT#40	CP-080702	013 0	1	Service Indication for standardized services	8.2.0
Jun 2008	CT#40	CP-080883	013 2	1	Correction of Identity-Set AVP	8.2.0
Mar 2009	CT#43	CP-090042	013 4	1	AliasesRepositoryData removal	8.3.0
Jun 2009	CT#44	CP-090305	013 6		Missing data-reference for GIBA	8.4.0
Dec 2009	CT#46	CP-090778	013 8		Session-Priority AVP	8.5.0
Dec 2009	CT#46				Upgraded unchanged from Rel-8	9.0.0
Mar 2010	CT#47	CP-100033	014 3	1	IP-SM-GW UE reachability handling over Sh	9.1.0
Mar 2010	CT#47	CP-100048	014 4	1	Sh handling of T-ADS	9.1.0
Mar 2010	CT#47	CP-100206	014 8	3	EPS Subscriber State and Location Information Request	9.1.0
Jun 2010	CT#48	CP-100275	014 9		EPS state and location retrieval	9.2.0
Jun 2010	CT#48	CP-100279	015 4	1		9.2.0
Sep 2010	CT#49	CP-100447	015 7	1	Correction to the Value of Data-Reference AVP	9.3.0
Sep 2010	CT#49	CP-100454	016 0	1	Correction on Requested-Domain	9.3.0
Sep 2010	CT#49	CP-100466	015 8	2	Usage of IMSI and IMPI for user identification over Sh	10.0.0
Sep 2010	CT#49	CP-100466	015 9	3	Location data including only serving node address	10.0.0
Sep 2010	CT#49	CP-100466	016 3	3	Update-Eff feature	10.0.0
Dec 2010	CT#50	CP-100699	016 4	2	Enhanced SRVCC	10.1.0
Mar 2011	CT#51	CP-110257	016 8	2	MPS over Sh	10.2.0
Mar 2011	CT#51	CP-110075	017 0	2	Retrieval of CSRN from HSS	10.2.0
Jun 2011	CT#52	CP-110370	017 5	1	Pre-paging Support Indicator for CSRN	10.3.0
Jun 2011	CT#52	CP-110370	017 6	1	Clarification on Notif-Eff description for SNR/SNA	10.3.0
Jun 2011	CT#52	CP-110370	017 7	-	Missing Repository-Data-ID AVP in PUA	10.3.0
Jun 2011	CT#52	CP-110383	017 3	2	Reference Location over Sh interface	11.0.0
Dec 2011	CT#54	CP-110781	018 9	-	Correction on Wildcarded Public Identity	11.1.0
Mar 2012	CT#55	CP-120035	019 4	2	Update of Multiple Data Instances in Sh-Update	11.2.0
Jun 2012	CT#56	CP-120240	019 5	3	Local Time for NPLI	11.3.0
Sep 2012	CT#57	CP-120481	019 7		A-MSISDN handling over Sh	11.4.0
Sep 2012	CT#57	CP-120481	019 8	1	Local Time Zone	11.4.0
Dec 2012	CT#58	CP-120743	020 2	1	EPS LocationInformation Support	11.5.0
Mar 2013	CT#59	CP-130020	020 8	1	PS Location Info request with RAT-type	11.6.0
Mar 2013	CT#59	CP-130020	021 0	1	Pre-paging-Supported and Local-Time-Zone-Indication AVPs	11.6.0
Mar 2013	CT#59	CP-130031	020 0	1	Sh IMSI retrieval	12.0.0
Jun 2013	CT#60	CP-130374	021 1	1	MTRR on Sh	12.1.0
Mar 2014	CT#63	CP-140027	021 4	1	Multiple notification due to the Update-Eff feature	12.2.0
Jun 2014	CT#64	CP-140262	021 7	-	Private User Identity retrieval	12.3.0
Jun 2014	CT#64	CP-140262	021 8	-	UE Reachability for IP	12.3.0

Sep 2014	CT#65	CP-140515	021 9	-		Session-Priority reference	12.4.0
Sep 2014	CT#65	CP-140509	022 0	1		Diameter Overload Control Over Sh	12.4.0
Dec 2014	CT#66	CP-140773	022 2	-		M-bit clarification	12.5.0
Dec 2014	CT#66	CP-140779	022 3	-		Retrieval of TWAN-Id over Sh	12.5.0
Dec 2014	CT#66	CP-140790	022 4	-		DOIC reference update	12.5.0
Dec 2015	CT#70	CP-150759	022 6	1		Update reference to DOIC new IETF RFC	12.6.0
Dec 2015	CT#70	CP-150849	022 7	4		Support of the DRMP AVP over Sh/Dh	13.0.0
2016-09	CT#73	CP-160431	022 8	1		Request to update data while a previous update request is in progress	14.0.0
2016-12	CT#74	CP-160649	023 6	1		RAT type included in EPS location information	14.1.0
2016-12	CT#74	CP-160681	023 7	1		Load Control	14.1.0
2016-12	CT#74	CP-160664	023 9	1		Correction to change IETF drmp draft version to official RFC 7944	14.1.0
2017-03	CT#75	CP-170035	024 1	-		Notif-Eff feature description correction	14.2.0
2017-03	CT#75	CP-170035	024 5	1		UDR flag description	14.2.0
2017-03	CT#75	CP-170048	024 3	1		Update of reference for the Diameter base protocol	14.2.0
2017-03	CT#75	CP-170048	024 4	-		Cardinality of the Failed-AVP AVP in answer	14.2.0
2017-06	CT#76	CP-171018	024 8	1		Support for signaling transport level packet marking	14.3.0
2017-06	CT#76	CP-171040	024 6	1		External Identifier on Sh	15.0.0
2018-06	CT#80	CP-181131	024 9	-		Requested Node AMF	15.1.0
2019-09	CT#85	CP-192094	025 1	2		draft-ietf-dime-load published as RFC 8583	15.2.0
2020-07	CT#88e	-	-	-		Update to Rel-16 version (MCC)	16.0.0
2020-12	CT#91e	CP-203022	025 3	1		Incomplete implemented CR	16.1.0
2021-03	CT#91e	CP-210044	035 4	-		IMEISV and 5G SRVCC Capability missing in Data Reference AVP	16.2.0
2022-04	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0
2024-03	-	-	-	-	-	Update to Rel-18 version (MCC)	<b>18.0.0</b>
2025-09	CT#109	CP-252050	025 5	3	B	Add new value of Data-Reference AVP to support IMS AS registration to HSS	19.0.0
2025-12	CT#110	CP-253155	025 6	7	B	Add commands and AVPs to support HSS subscription to IMS AS and event notification	19.1.0

---

## History

<b>Version</b>	<b>Date</b>	<b>Status</b>
V19.0.0	January 2026	Publication
V19.1.0	February 2026	Publication