ETSI TS 134 229-2 V17.1.0 (2024-08)



Universal Mobile Telecommunications System (UMTS);

LTE;

5G;

Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP)

and Session Description Protocol (SDP);

User Equipment (UE) conformance specification;

Part 2: Implementation Conformance Statement (ICS) specification (3GPP TS 34.229-2 version 17.1.0 Release 17)



Reference RTS/TSGR-0534229-2vh10 Keywords 5G,LTE,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the ETSI Search & Browse Standards application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver.

Users should be aware that the present document may be revised or have its status changed, this information is available in the Milestones listing.

If you find errors in the present document, please send your comments to the relevant service listed under <u>Committee Support Staff</u>.

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure (CVD) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024. All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M**TM logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under https://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intelle	ectual Property Rights	2
Legal	Notice	2
Moda	l verbs terminology	2
Forew	vord	
Introd	luction	
1	Scope	5
2	References	5
3	Definitions and abbreviations.	C
3.1	Definitions	
3.2	Abbreviations	
4	Recommended test case applicability	
4.1	Applicabilities for test cases specified in TS 34.229-1	
4.2	Applicabilities for test cases specified in TS 34.229-5	
Anne	x A (normative): ICS proforma for 3 rd Generation User Equipment supporting IP multimedia call control based on SIP and SDP	11
A.1	Guidance for completing the ICS proforma	
A.1.1	Purposes and structure	
A.1.2	Abbreviations and conventions	
A.1.3	Instructions for completing the ICS proforma	
A.2	Identification of the User Equipment	
A.2.1	Date of the statement	
A.2.2	User Equipment Under Test (UEUT) identification	
A.2.3	Product supplier	
A.2.4	Client	
A.2.5	ICS contact person	
A.3	Identification of the protocol	
A.4	ICS proforma tables	
A.4.1	Roles	
A.4.2	ICS related to SIP	
A.4.2.		
A.4.2.	v 1	
A.4.2.3		
A.4.2.4		
A.4.2.	S C C C C C C C C C C C C C C C C C C C	
A.4.3	Void	
A.4.4	Void	
A.4.5	Additional information	
A.4.6	Additional information for IPv4	
A.4.7	MTSI media	
A.4.8	MTSI supplementary services	
A.4.9	MTSI media change	
A.4.10		
A.4.11		
A.4.11		
A.4.13		
A.4.14		
Anne	x B (informative): Change history	62
Histor	·	73

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

The present document is 2nd part of a multi-part conformance test specification for UE and is *valid for 3GPP Release 5* (respectively Release 15 for 5GS test cases). The specification contains the UE IMS CC capability and the applicability of the UE IMS CC conformance test cases.

3GPP TS 34.229-1 [5]: Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 1: Protocol conformance specification.

3GPP TS 34.229-2 (the present document): "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification" - current document.

3GPP TS 34.229-3 [6]: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 3: Abstract Test Suites (ATS)".

3GPP TS 34.229-5 [95]: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 5: Protocol conformance specification using 5G System (5GS)"

Note: For conformance testing of the UTRAN requirements refer to 3GPP TS 34.123 Parts 1 to 3 [2] [3] [4].

1 Scope

The present document provides the Implementation Conformance Statement (ICS) proforma for 3rd Generation User Equipment (UE) supporting the Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP), in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [8] and ETS 300 406 [9].

The present document also specifies a recommended applicability statement for the test cases included in TS 34.229-1 [5] and TS 34.229-5 [95]. These applicability statements are based on the features implemented in the UE.

The present document is valid for UE implemented according to 3GPP releases starting from Release 5 up to the Release indicated on the cover page of the present document.

Also, it is generally assumed that an IMS capable UE is compliant to GSMA PRD IR.92 [83] and GSMA PRD IR.94 [75]; any update of requirements in these GSMA PRD documents, which are relevant to the present document will be handled on a case by case basis, with due consideration given for grace period to be granted for the UE to comply to any updated requirements.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document unless the context in which the reference is made suggests a different Release is relevant (information on the applicable release in a particular context can be found in e.g. test case title, description or applicability, message description or content).
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
 [2] 3GPP TS 34.123-1: "User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
 [3] 3GPP TS 34.123-2: "User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS) proforma specification".
 [4] 3GPP TS 34.123-3: "User Equipment (UE) conformance specification; Part 3: Abstract Test Suites (ATS)".
- [5] 3GPP TS 34.229-1: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 1: Protocol conformance specification".
- [6] 3GPP TS 34.229-3: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 3: Abstract Test Suites (ATS)".
- [7] ISO/IEC 9646-1: "Information technology Open systems interconnection Conformance testing methodology and framework Part 1: General concepts".
- [8] ISO/IEC 9646-7: "Information technology Open systems interconnection Conformance testing methodology and framework Part 7: Implementation Conformance Statements".
- [9] ETSI ETS 300 406: "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

[10]	3GPP TS 24.229: "IP Multimedia Call Control Protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
[11]	Void.
[12]	3GPP TS 33.203: "Access security for IP-based services".
[13]	3GPP TS 23.221: "Architectural requirements".
[14]	Void.
[15]	RFC 3261: "SIP: Session Initiation Protocol".
[16]	Void.
[17]	3GPP TS 24.247: "Messaging using the IP Multimedia (IM) Core Network (CN) subsystem; Stage 3".
[18]	3GPP TR 23.981: "Interworking aspects and migration scenarios for IPv4-based IP Multimedia Subsystem (IMS) implementations".
[19]	3GPP TS 24.147: "Conferencing using the IP Multimedia (IM) Core Network (CN) subsystem; Stage 3".
[20]	Void.
[21]	Void.
[22]	Void.
[23]	Void.
[24]	Void.
[25]	Void.
[26]	RFC 3312: "Integration of Resource Management and Session Initiation Protocol (SIP)".
[27]	RFC 3262: "Reliability of provisional responses in Session Initiation Protocol (SIP)".
[28]	Void.
[29]	Void.
[30]	Void.
[31]	Void.
[32]	Void.
[33]	Void.
[34]	Void.
[35]	Void.
[36]	Void.
[37]	Void.
[38]	Void.
[39]	Void.
[40]	Void.
[41]	Void.
[42]	Void.

[43]	Void.
[44]	Void.
[45]	Void.
[46]	Void.
[47]	Void.
[48]	Void.
[49]	Void.
[50]	Void.
[51]	Void.
[52]	Void.
[53]	Void.
[54]	Void.
[55]	3GPP TS 24.173: "IMS Multimedia Telephony Communication Service and supplementary services; stage 3".
[56]	$3\mbox{GPP TS }26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".$
[57]	Void.
[58]	Void.
[59]	Void.
[60]	Void.
[61]	Void.
[62]	Void.
[63]	3GPP TS 33.222: "Generic Authentication Architecture (GAA); Access to network application functions using Hypertext Transfer Protocol over Transport Layer Security (HTTPS)".
[64]	3GPP TS 24.109: "Bootstrapping interface (Ub) and network application function interface (Ua); Protocol details".
[65]	RFC 2617; "HTTP Authentication: Basic and Digest Access Authentication".
[66]	3GPP TS 24.341: "Support of SMS over IP networks; Stage 3".
[67]	Void.
[68]	3GPP TS 24.604: "Communication Diversion (CDIV) using IP Multimedia (IM)".
[69]	3GPP TS 24.615: "Communication Waiting (CW) using IP Multimedia (IM) Core Network (CN) subsystem".
[70]	3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
[71]	3GPP TR 21.904: "UE capability requirements".
[72]	Void.
[73]	3GPP TS 36.523-2: "User Equipment (UE) conformance specification; Part 2: Implementation Conformance Statement (ICS)proforma specification".

[74]	2CDD2 C 50005 E. "Human I avan (I avan 2) Signalling Standard for adma 2000 Spread Speatman
[74]	3GPP2 C.S0005-E: "Upper Layer (Layer 3) Signalling Standard for cdma2000 Spread Spectrum Systems".
[75]	GSMA PRD IR.94: "IMS Profile for Conversational Video Service".
[76]	3GPP TS 23.167: "IP Multimedia Subsystem (IMS) emergency sessions".
[77]	3GPP TS 24.237: "IP Multimedia Subsystem (IMS) Service Continuity; Stage 3".
[78]	3GPP TS 34.109: "Terminal logical test interface; Special conformance testing functions".
[79]	3GPP TS 36.509: "Special conformance testing functions for User Equipment (UE)".
[80]	Void.
[81]	3GPP TS 24.623: "Extensible Markup Language (XML) Configuration Access Protocol (XCAP) over the Ut interface for Manipulating Supplementary Services".
[82]	3GPP TS 33.220: "Generic Authentication Architecture (GAA); Generic Bootstrapping Architecture".
[83]	GSMA PRD IR.92: "IMS Profile for Voice and SMS".
[84]	GSMA PRD IR.51: "IMS Profile for Voice, Video and SMS over Wi-Fi".
[85]	3GPP TS 24.238: "Session Initiation Protocol (SIP) based user configuration; Stage3".
[86]	IETF RFC 4028 (April 2005): "Session Timers in the Session Initiation Protocol (SIP)".
[87]	GSMA PRD NG.108: "IMS Profile for Voice and SMS for UE category M1".[88] IETF RFC 8147 (May 2017): "Next-Generation Pan-European eCall".
[88]	FFS
[89]	GSMA PRD NG.102: "IMS Profile for Converged IP Communications".
[90]	3GPP TS 24.390: "Unstructured Supplementary Service Data (USSD) using IP Multimedia (IM) Core Network (CN) subsystem IMS; Stage 3"
[91]	3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone"
[92]	3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone"
[93]	3GPP TS 38.508-2: "5GS; User Equipment (UE) conformance specification; Part 2: Common Implementation Conformance Statement (ICS) proforma specification".
[94]	3GPP TS 23.040: "Technical realization of the Short Message Service (SMS)".
[95]	3GPP TS 34.229-5: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); User Equipment (UE) conformance specification; Part 5: Protocol conformance specification using 5G System (5GS)".
[96]	GSMA PRD NG.114: "IMS Profile for Voice, Video and Messaging over 5GS, Version 1.0".
[97]	3GPP TS 27.007: "AT command set for User Equipment (UE)".
[98]	GSMA PRD NG.114: "IMS Profile for Voice, Video and Messaging over 5GS, Version 2.0".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply, in addition to those in TR 21.905 [1]:

- terms defined in the relevant 3GPP core specifications (see normative references);
- terms defined in ISO/IEC 9646-1 [7] and in ISO/IEC 9646-7 [8].

In particular, the following terms defined in ISO/IEC 9646-1 [7] apply:

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

ICS Implementation Conformance Statement SCS System Conformance Statement UEUT User Equipment Under Test

4 Recommended test case applicability

The applicability of each individual test is identified in the table 1. This is just a recommendation based on the purpose for which the test case was written.

The applicability of every test is formally expressed by the use of Boolean expression that are based on parameters (ICS) included in annex A of the present document.

Additional information related to the Test Case (TC), e.g. affecting its dynamic behaviour or its execution may be provided as well.

The columns in table 1 have the following meaning:

Clause

The clause column indicates the clause number in TS 34.229-1 [5] that contains the test body.

Title

The title column describes the name of the test.

Release

The release column indicates the earliest release from which each testcase is applicable, except if otherwise stated of an individual test case.

NOTE: For the IMS Emergency Service test cases, the 3GPP Release of UTRAN and GERAN is independent of that indicated in the release column.

Applicability

The following notations are used for the applicability column:

R recommended - the test case is recommended

O optional – the test case is optional

N/A not applicable - in the given context, the test case is not recommended.

Ci conditional - the test is recommended ("R") or not ("N/A") depending on the support of other

items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ...

THEN ... ELSE...) ELSE ..." is used to avoid ambiguities.

Comments

This column contains a verbal description of the condition included in the applicability column.

4.1 Applicabilities for test cases specified in TS 34.229-1

Table 4.1: Applicability of TS 34.229-1 tests

8.5 Void 8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports IMS security and GIBA and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports GIBA only and E-UTRA and not UE category M1 8.16 User initiated re-registration using GIBA Rel-9 C17 UE supports GIBA only and E-UTRA and not UE category M1 8.16 User initiated re-registration using GIBA Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief T00 Brief T	6.2 6.3 7 7.1 7.2 7.3 7.4 7.5 7.6	General Purpose PDP Context Establishment (UE Requests for a Dedicated PDP Context) Dedicated PDP Context Establishment P-CSCF Discovery P-CSCF Discovery via PDP Context P-CSCF Discovery via DHCP - IPv4 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8 Rel-8 Rel-8	C04 C05 C06 C07 C08 C09	initiate Dedicated PDP Context UE capable of being configured to initiate Dedicated PDP Context UE capable of being configured to initiate P-CSCF Discovery via PCO UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
Establishment (UE Requests for a Dedicated PDP Context) P-GSCF Discovery 7.1 P-CSCF Discovery 7.1 P-CSCF Discovery via DHCP - IPv4 7.2 P-CSCF Discovery via DHCP - IPv4 7.3 P-CSCF Discovery via DHCP - IPv4 7.4 P-CSCF Discovery via DHCP - IPv4 7.5 P-CSCF Discovery via DHCP - IPv4 7.6 Requests P-CSCF discovery via DHCP - IPv4 7.7 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via DHCP - IPv4 7.6 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via DHCP - IPv6 7.7 P-CSCF Discovery via DHCP - IPv6 7.8 P-CSCF Discovery by DHCP - IPv6 8.9 P-CSCF Discovery by DHCP - IPv6 8.9 P-CSCF Discovery by DHCP - IPv6 9.0 P-CSCF Discovery by DHCP -	6.3 7 7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9	Establishment (UE Requests for a Dedicated PDP Context) Dedicated PDP Context Establishment P-CSCF Discovery P-CSCF Discovery via PDP Context P-CSCF Discovery via DHCP - IPv4 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8 Rel-8 Rel-8	C04 C05 C06 C07 C08 C09	initiate Dedicated PDP Context UE capable of being configured to initiate Dedicated PDP Context UE capable of being configured to initiate P-CSCF Discovery via PCO UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
Pedicated PDP Context Establishment Rel-8	7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery P-CSCF Discovery via PDP Context P-CSCF Discovery via PDP Context P-CSCF Discovery via DHCP - IPv4 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8 Rel-8	C05 C06 C07 C08	initiate Dedicated PDP Context UE capable of being configured to initiate P-CSCF Discovery via PCO UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
7.1 P-CSCF Discovery via PDP Context 7.2 P-CSCF Discovery via DHCP - IPv4 7.3 P-CSCF Discovery via DHCP - IPv4 (UE Rel-8 C07 UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via PCO Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) 7.4 P-CSCF Discovery via DHCP - IPv4 (UE Rel-8 C07 UE supports IPv4 supports P-CSCF Discovery via PCO and DHCPV4 and Control of the property of PCO Discovery via PCO and DHCPV4 and Control of Discovery via PCO and DHCPV4 and Control of DHCPv4 (IPv4 Property via PCO Discovery via PCO and DHCPV4 (IPv4 Property via PCO Discovery via PCO Discovery via PCO and DHCPV4 (IPv4 Property via PCO Discovery v	7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery via PDP Context P-CSCF Discovery via DHCP - IPv4 P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8	C06 C07 C08 C09	initiate P-CSCF Discovery via PCO UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
Initiate P-CSCF Discovery via DHCP - IPv4 Rel-8 C06 UE supports IPv4 and papile of being configured to initiate P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO Discovery vi	7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8	C06 C07 C08 C09	initiate P-CSCF Discovery via PCO UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
7.2 P-CSCP Discovery via DHCP - IPV4 Rel-8 C06 UE supports IPV4 and capable of being configured to initiate P-CSCP Discovery via DHCP-1 IPV4 (UE Requests P-CSCP discovery via DHCP-1 IPV4 (UE Requests P-CSCP discovery via DHCP-1 IPV4 (UE Requests P-CSCP discovery via PCO) and DHCPV4 and capable of being configured to initiate and capable of the promise produced to initiate and capable of the promise produced to initiate P-CSCP Discovery via DHCPV6 (UE Requests P-CSCP discovery by PCO) and DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 (UE does not Request P-CSCF discovery by PCO) and DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of being configured to initiate P-CSCP Discovery via DHCPV6 and capable of Discovery via DHCPV6 and capab	7.3 7.4 7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO) P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8 Rel-8 Rel-8	C07 C08 C09	UE supports IPv4 and capable of being configured to initiate P-CSCF Discovery via DHCPv4 UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
PCSCP Discovery via DHCP - IPv4 (UE Requests P-CSCF discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of PCO and DHCPv6 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCP Discovery via PCO and DHCPv6 and capable of PCO and DHCPv6 and Capable	7.4 7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery by DHCP - IPv6 P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8	C08	UE supports IPv4, supports P-CSCF Discovery via PCO and DHCPv4 and capable of being configured to initiate P-CSCF Discovery via PCO UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
P-CSCF Discovery by DHCP - IPv6 Rel-8 C08 UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 Requests P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF Discovery by PCO) Rel-8 C09 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO Discovery via PCO Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO and DHCPv6 and capable of being configured thin the P-CSCF Discovery via DHCPv6 and capable of being configured thin thin the P-CSCF Discovery via DHCPv6 and capable of being configured thin the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via PCO and P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discovery via DHCPv6 and capable of being configured the P-CSCF Discov	7.5 7.6 7.7 7.8 7.9	P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8	C09	UE capable of being configured to initiate P-CSCF Discovery via DHCPv6 UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
P-CSCF Discovery by DHCP-IPv6 (UE Requests P-CSCF discovery by PCO) Requests P-CSCF discovery by PCO, Rel-8 Rel-8 PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery by PCO, SS includes P-CSCF Address(es) in PCO PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via DHCPv6 and capable of being configured to initiate P-CSCF Discovery via DHCPv6 PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via DHCPv6 PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via DHCPv6 PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via DHCPv6 PCO and DHCPv6 P	7.6 7.7 7.8 7.9	Requests P-CSCF discovery by PCO) P-CSCF Discovery by DHCP - IPv6 (UE does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void			UE supports P-CSCF Discovery via PCO and DHCPv6 and capable of being configured to initiate P-CSCF Discovery via PCO UE supports P-CSCF Discovery via
does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO, SS includes P-CSCF Discovery via DHCPv6 7.9 Void 8. Void 8.1 Initial registration 8.1 Initial registration 8.2 User initiated Re-Registration 8.3 Mobile Initiated Deregistration 8.6 Rel-8 8.7 User initiated Deregistration 8.8 C17 Use supports IMS security and E-UTRA and not Use category M1 8.9 User initiated Deregistration 8.1 Invalid Behaviour - 423 Interval Too Brief 8.2 User initiated Deregistration 8.3 Invalid Behaviour - 423 Interval Too Brief 8.4 Invalid Behaviour - 423 Interval Too Brief 8.5 Void 8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA 8.11 Initial registration using GIBA 8.10 Initial registration using GIBA 8.11 Initial registration using GIBA 8.12 User initiated re-registration using GIBA 8.13 User initiated re-registration using GIBA 8.14 Void 8.15 Refresh for ISIM parameters 8.16 User initiated de-registration using GIBA 8.17 Rel-8 C18 Use supports GIBA only and E-UTRA and not Use category M1 8.18 User initiated re-registration using GIBA 8.19 Rel-8 C18 Use supports GIBA only and E-UTRA and not Use category M1 8.10 User initiated re-registration using GIBA 8.11 User initiated re-registration using GIBA 8.12 User initiated re-registration using GIBA 8.13 User initiated re-registration using GIBA 8.14 Void 8.15 Refresh for ISIM parameters 8.16 User initiated re-registration using GIBA 8.17 User initiated re-registration using GIBA 8.18 C18 User initiated re-registration using GIBA 8.19 User initiated re-registration using GIBA 8.10 User initiated re-registration using GIBA 8.11 User initiated re-registration using GIBA 8.12 User initiated re-registration using GIBA 8.13 User initiated re-registration using GIBA 8.14	7.7 7.8 7.9	does not Request P-CSCF discovery by PCO, SS includes P-CSCF Address(es) in PCO) Void Void	Rel-8	C10	
7.9 Void 8 Registration 8.1 Initial registration 8.2 User Initiated Re-Registration 8.3 Mobile Initiated Deregistration 8.4 Invalid Behaviour - 423 Interval Too Brief 8.5 Void 8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.1 Initial registration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.4 Invalid Behaviour - 423 Interval Too Brief 8.5 Void 8.6 Void 8.7 Void 8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA Rel-8 C19 UE supports IMS security and GIBA and not UE category M1 8.12 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration using GIBA Rel-8 C19 UE supports GIBA only and E-UTRA and not UE category M1 8.16 Void 8.17 Void 8.18 Void 8.19 Void 8.19 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.10 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Void 8.12 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.10 User initiated de-registration using GIBA Rel-8 C19 UE supports IMS security and E-UTRA and not UE category M1 8.11 Notification Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.12 User initiated de-registration using GIBA Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.12 User initiated de-registration Rel-8 C151 UE supports IMS security and E-UTRA and not UE category M1 8.12 User initiated de-registration Rel-8 C151 Userports IMS security and E-UTRA and not UE category M1 8.13 Network-initiated deregistration Rel-8 C151 U	7.8 7.9	Void			being configured to initiate P-CSCF
Reject R	7.9				_
Rejstration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1		Void			<u> </u>
8.1 Initial registration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.2 User Initiated Re-Registration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.3 Mobile Initiated Deregistration Rel-8 C80 UE supports IMS security and IMS deregistration and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category M1 8.4 Invalid Behaviour - 423 Interval Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category M1 8.5 Void UE supports IMS security and E-UTRA and not UE category M1 8.6 Void UE supports IMS security and E-UTRA and not UE category M1 8.7 Void UE supports IMS security and E-UTRA and not UE category M1 8.10 Initial registration using GIBA Rel-8 C18 UE supports IMS security and GIBA against a network with GIBA support only User initiated re-registration using GIBA Rel-8 C18 UE supports IMS security and GIBA and not UE category M1 8.12 User initiated de-registration using GIBA Rel-8 C18 UE supports IMS security and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports IMS security and E-UTRA and not UE category M1 8.14 Void User initiated re-registration 423 Interval Too Brief User initiated re-registration 423 Interval Too Brief Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 9. Authentication Invalid Behaviour - 500 Service Unavailable Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10. Invalid Behaviour - 500 Service Unavailable Rel-8 C15 E-UTRA and not UE category M1 11. Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11. Network-initiated deregistration Rel-8 C15 E-UTRA and not UE category M1 11. Network-initiated deregistration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11. Network-initiated deregistration Rel-8 C15 E-UTRA and not UE category M1 11. Network initiated de-registration Re	Q				
8.2 User Initiated Re-Registration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.3 Mobile Initiated Deregistration Rel-8 C80 UE supports IMS security and IAD UE supports IMS security and E-UTRA and (Support of CS/PS mode 2 or Support IAD				_	
8.3 Mobile Initiated Deregistration Rel-8 C80 UE supports IMS security and IMS deregistration and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category M1 8.4 Invalid Behaviour - 423 Interval Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.5 Void 8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports IMS and not UE category M1 8.11 Initial registration using MIS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports IMS security and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports IMS security and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration 423 Interval Too Brief Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.1 Notification Rel-8 C15 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C15 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C15 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control					and not UE category M1
deregistration and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category M1 8.4 Invalid Behaviour - 423 Interval Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 8.5 Void 8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration-423 Interval Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - SQN out of range Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.1 Notification Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.1 Network-initiated de-egistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network-initiated de-authentication Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control		_			and not UE category M1
Invalid Behaviour - 423 Interval Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1	8.3	Mobile Initiated Deregistration	Rel-8	C80	deregistration and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category
8.6 Void 8.7 Void 8.8 Void 8.9 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports IMS security and GIBA and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief Patternation Authority and E-UTRA and not UE category M1 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 9.3 Notification Rel-8 C151 E-UTRA and not UE category M1 9.4 Notification Rel-8 C151 UE supports IMS security and E-UTRA and not UE category M1 9.5 Network initiated deregistration Rel-8 C151 UE supports IMS security and E-UTRA and not UE category M1 9.5 Network initiated deregistration Rel-8 C151 UE supports IMS security and E-UTRA and not UE category M1 9.5 Network initiated re-authentication Rel-8 C151 UE supports IMS security and E-UTRA and not UE category M1	8.4	Invalid Behaviour - 423 Interval Too Brief	Rel-8	C17	UE supports IMS security and E-UTRA and not UE category M1
8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C19 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - 503 Service Unavailable Rel-8 C15 E-UTRA and not UE category M1 10 Notification Rel-8 C151 E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	8.5	Void			
8.7 Void 8.8 Void 8.9 Void 8.10 Initial registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.11 Initial registration using IMS AKA and GIBA against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C19 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief Too Brief Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - 503 Service Unavailable Rel-8 C15 E-UTRA and not UE category M1 10 Notification Rel-8 C151 E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network-initiated deregistration Rel-8 C15 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	8.6	Void			
8.9 Void		Void			
8.9 Void	8.8	Void			
8.10					
against a network with GIBA support only 8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief Rel-9 Authentication 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 Notification Rel-8 C151 E-UTRA and not UE category M1 Network-initiated deregistration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 11.2 Call Control			Rel-8	C18	
8.12 User initiated re-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.13 User initiated de-registration using GIBA Rel-8 C18 UE supports GIBA only and E-UTRA and not UE category M1 8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification Rel-8 C151 E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.2 Call Control	8.11		Rel-8	C19	
8.14 Void 8.15 Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 8.16 User initiated re-registration- 423 Interval Too Brief 9 Authentication 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.2 Call Control	8.12	User initiated re-registration using GIBA	Rel-8	C18	UE supports GIBA only and E-UTRA
Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 Position Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Notification Rel-8 C151 E-UTRA and not UE category M1 Network-initiated deregistration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 C10 C21 C21 C21 C31 C41 C41 C41 C41 C41 C41 C4	8.13	User initiated de-registration using GIBA	Rel-8	C18	UE supports GIBA only and E-UTRA
Refresh for ISIM parameters Rel-10 C17 UE supports IMS security and E-UTRA and not UE category M1 Rel-9 C17 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 Position Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 UE supports IMS security and E-UTRA and not UE category M1 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Notification Rel-8 C151 E-UTRA and not UE category M1 Network-initiated deregistration Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 C10 C21 C21 C21 C31 C41 C41 C41 C41 C41 C41 C4	8.14				
8.16 User initiated re-registration- 423 Interval Too Brief 9 Authentication 9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control		·	Rel-10	C17	UE supports IMS security and E-UTRA and not UE category M1
9.1 Invalid Behaviour - MAC Parameter Invalid Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control		Too Brief	Rel-9	C17	UE supports IMS security and E-UTRA
and not UE category M1 9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control					
9.2 Invalid Behaviour - SQN out of range Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	9.1	Invalid Behaviour - MAC Parameter Invalid	Rel-8	C17	
10 Subscription 10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	9.2	Invalid Behaviour - SQN out of range	Rel-8	C17	UE supports IMS security and E-UTRA
10.1 Invalid Behaviour - 503 Service Unavailable Rel-8 C151 E-UTRA and not UE category M1 11 Notification 11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	10	Subscription			
11.1 Network-initiated deregistration Rel-8 C151 E-UTRA and not UE category M1 11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control	10.1	Invalid Behaviour - 503 Service Unavailable	Rel-8	C151	E-UTRA and not UE category M1
11.2 Network initiated re-authentication Rel-8 C17 UE supports IMS security and E-UTRA and not UE category M1 12 Call Control			Rel-8	C151	F-LITRA and not LIF category M1
12 Call Control					UE supports IMS security and E-UTRA
	12	Call Control			and not or category ivi

Clause	Title	Release	Applicability	Comments
12.2	MO Call with preconditions at both originating UE and terminating UE - 503 Service Unavailable	Rel-8	C160	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1
12.2a	MO Call with preconditions at both originating and terminating UE - 504 Server Time-out	Rel-8	C160	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1
12.2b	MO Call without preconditions at both originating UE and terminating UE - 503 Service Unavailable	Rel-8	C164	UE supports MTSI and MTSI speech and initiating a session and no preconditions and E-UTRA and not UE category M1
12.2c	MO Call without preconditions at both originating and terminating UE - 504 Server Time-out	Rel-8	C164	UE supports MTSI and MTSI speech and initiating a session and no preconditions and E-UTRA and not UE category M1
12.3	Void			
12.4	Void			
12.5	Void			
12.6	Void			
12.7	Void			
12.8	Void			

Clause	Title	Release	Applicability	Comments
12.9	Void			
12.10	Void			
12.11	Void			
12.12	MO MTSI Voice Call Successful with preconditions at both originating UE and terminating UE	Rel-8	C160	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1
12.12a	MO MTSI Voice Call Successful without preconditions at both originating UE and terminating UE	Rel-14	C164	UE supports MTSI and MTSI speech and initiating a session and not preconditions and E-UTRA and not UE category M1
12.13	MT MTSI Speech call	Rel-8	C27	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1
12.13a	MT MTSI speech cal with preconditions at both originating UE and terminating UEI when MO reserves resources before sending INVITE	Rel-8	C27	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1
12.13b	MT MTSI Speech call Successful without preconditions at both originating UE and terminating UE	Rel-8	C165	UE supports MTSI and MTSI speech and E-UTRA and not preconditions and not UE category M1
12.13c	MT MTSI speech call Successful with preconditions at originating UE and without preconditions at terminating UE	Rel-14	C165	UE supports MTSI and MTSI speech and E-UTRA and not preconditions and not UE category M1
12.15	Void			
12.16	Void		1	
12.17	Void			
12.18 12.18a	Void Void			
12.18b	Void			
12.100	Void			
12.19a	Void			
12.19b	Void			
12.20	Void			
12.20a	Void			
12.21	MO MTSI Video call	Rel-8	C71	UE supports MTSI and initiating a session and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and E- UTRA and not UE category M1
12.22	MT MTSI Video call	Rel-8	C70	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and E-UTRA and not UE category M1
12.23	MO MTSI speech call / EVS	Rel-12	C83	UE supports MTSI and MTSI speech EVS (see NOTE 3 below) and preconditions and E-UTRA and not UE category M1 (NOTE 8).
12.23a	MO MTSI speech call / EVS / Default configuration	Rel-15	C170	UE supports MTSI and MTSI speech and preconditions and EN-DC
12.24	MT MTSI speech call / EVS	Rel-12	C83	UE supports MTSI and MTSI speech EVS (see NOTE 3 below) and preconditions and E-UTRA and not UE category M1 (NOTE 8).
12.24a	MT MTSI speech call / EVS / Default configuration	Rel-15	C170	UE supports MTSI and MTSI speech and preconditions and EN-DC
12.25	MO MTSI speech call / EVS offered but not supported by remote UE / AMR-WB agreed	Rel-12	C83	UE supports MTSI and MTSI speech EVS (see NOTE 3 below) and preconditions and E-UTRA and not UE category M1
12.25a	MT MTSI speech call / EVS offered but not supported by UE / AMR-WB agreed	Rel-8	C167	MTSI and MTSI speech and MTSI speech, AMR wideband and not MTSI speech, EVS and preconditions and E-UTRA and not UE category M1
12.26	MT MTSI speech call / EVS / AMR-WB IO mode	Rel-12	C83	UE supports MTSI and MTSI speech EVS (see NOTE 3 below) and preconditions and E-UTRA and not UE category M1
12.27	MO MTSI speech call / SRVCC on MT side / Codec Change from AMR-WB to AMR-NB	Rel-8	C160	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1

Clause	Title	Release	Applicability	Comments
12.27a	MO MTSI speech call / SRVCC on MT side /	Rel-12	C83	UE supports MTSI and MTSI speech
	Codec Change from EVS to AMR-NB			EVS (see NOTE 3 below) and preconditions and E-UTRA and not UE category M1
12.28	MO MTSI speech call / MO UE cancels call	Rel-8	C160	UE supports MTSI and MTSI speech
.=.=0	establishment	110.0		and initiating a session and preconditions and E-UTRA and not UE
12.29	MO MTSI Video call / MO UE cancels call	Rel-8	C71	category M1 UE supports MTSI and initiating a
12.29	establishment	Kel-o	C/ I	session and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and E-
13	SID Compression (SigComp)			UTRA and not UE category M1
13.1	SIP Compression (SigComp) SigComp in the Initial registration	FFS	C58	UE supports IMS security and Indicate Sigcomp
13.2	SigComp in the MO Call	FFS	FFS	FFS (see NOTE 1 below)
13.3	SigComp in the MT Call	FFS	FFS	FFS (see NOTE 1 below)
13.4	Void			
14 14.1	Emergency Service Void			
14.1	Void			
15	Supplementary Services			
15.1	Originating Identification Presentation	Rel-8	C43	UE supports MTSI and MTSI Originating Identification Presentation and (GBA or HTTP Digest) for XCAP authentication (NOTE 4) and E-UTRA and not UE category M1
15.2	Originating Identification Restriction	Rel-8	C88	UE supports MTSI and MTSI Originating Identification Restriction - Configuration and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.2a	Originating Identification Restriction / Signalling	Rel-8	C44	UE supports MTSI and MTSI Originating Identification Restriction and preconditions and E-UTRA and not UE category M1
15.3	Terminating Identification Presentation	Rel-8	C48	UE supports MTSI and MTSI Terminating Identification Presentation and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.4	Terminating Identification Restriction	Rel-8	C89	UE supports MTSI and MTSI Terminating Identification Restriction - Configuration and (GBA or HTTP Digest) (NOTE 4) and E-UTRA and not UE category M1
15.4a	Terminating Identification Restriction / Signalling	Rel-8	C49	UE supports MTSI and MTSI Terminating Identification Restriction and preconditions and E-UTRA and not UE category M1
15.5	Communication Forwarding unconditional	Rel-8	C30	UE supports MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.6	Void	D-LO	000	LIC composite NATOL and DATOL
15.7	Communication Forwarding on non Reply: activation	Rel-8	C30	UE supports MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.8	Communication Forwarding on non reply: MO call initiation	Rel-8	C31	UE supports MTSI and MTSI speech and MTSI Communication Diversion and preconditions and E-UTRA and not UE category M1
15.9	Communication Forwarding on Busy	Rel-8	C30	UE supports MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.10	Communication Forwarding on Not logged-in	Rel-8	C30	UE supports MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) (NOTE 4) and E-UTRA and not UE category M1
15.10a	Communication Forwarding on Not reachable	Rel-8	C30	UE supports MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1

Clause	Title	Release	Applicability	Comments
15.11	MO Call Hold without announcement	Rel-8	C23	UE supports MTSI and MTSI speech and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
15.11a	MO Video Call Hold without announcement	Rel-8	C77	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
15.12	MT Call Hold without announcement	Rel-8	C23	UE supports MTSI and MTSI speech and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
15.12a	MT Video Call Hold without announcement	Rel-8	C77	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
15.13	Incoming Communication Barring except for a specific user	Rel-8	C24	UE supports MTSI and MTSI Communication Barring and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.14	Incoming Communication Barring for anonymous users	Rel-8	C45	UE supports MTSI and MTSI Communication Barring and MTSI Anonymous Communication Rejection and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.14a	Incoming Communication Barring while roaming	Rel-8	C24	UE supports MTSI and MTSI Incoming Communication Barring and (GBA or HTTP Digest) (NOTE 5) and E-UTRA and not UE category M1
15.14b	Outgoing Communication Barring while roaming	Rel-8	C84	UE supports MTSI and MTSI Outgoing Communication Barring and (GBA or HTTP Digest) (NOTE 4) and E-UTRA and not UE category M1
15.15	Subscription to the MWI event package	Rel-8	C50	UE supports MTSI and MTSI Message Waiting Indication and E-UTRA and not UE category M1
15.17	Creating and leaving a conference	Rel-8	C32	UE supports MTSI and MTSI speech and MTSI Conference and preconditions and E-UTRA and not UE category M1
15.18	Inviting user to conference by sending a REFER request to the user	Rel-8	C32	UE supports MTSI and MTSI speech and MTSI Conference and preconditions and E-UTRA and not UE category M1
15.19	Inviting user to conference by sending a REFER request to the conference focus	Rel-8	C32	UE supports MTSI and MTSI speech and MTSI Conference and preconditions and E-UTRA and not UE category M1
15.19a	Inviting user to conference by sending a REFER request to the conference focus / Video	Rel-8	C78	UE supports MTSI and MTSI speech and MTSI video H.264 CBP Level 1.2 and MTSI Conference and preconditions and E-UTRA and not UE category M1
15.21 15.21a	Void Three way session creation	Rel-8	C61	UE supports MTSI and MTSI Conference and MTSI three way session and preconditions and E- UTRA and not UE category M1
15.21b	Void]	
15.21c	Three way session creation / Video	Rel-8	C79	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and MTSI three way session and preconditions and E-UTRA and not UE category M1
15.23	Void			
15.24	Void		1	<u> </u>

Clause	Title	Release	Applicability	Comments
15.25	MO Explicit Communication Transfer - Consultative Call Transfer	Rel-8	C29	UE supports MTSI and MTSI speech and MTSI Explicit Communication Transfer - consultative transfer and
				preconditions and E-UTRA and not UE category M1
15.26	Void			
15.27	Communication Waiting and answering the call	Rel-8	C57	UE supports MTSI and MTSI speech and MTSI Communication Waiting and preconditions and E-UTRA and not UE category M1
15.28	Communication Waiting and cancelling the call	Rel-8	C57	UE supports MTSI and MTSI speech and MTSI Communication Waiting and preconditions and E-UTRA and not UE category M1
15.29	GBA authentication	Rel-8	C81	UE supports MTSI and MTSI Originating Identification Presentation and GBA for XCAP authentication and E-UTRA and not UE category M1.
15.30	User initiated USSI	Rel-12	C159	UE supports MTSI and MTSI speech and initiating a session and E-UTRA and USSI and not UE category M1
16	Codec selecting			
16.1	Void		22-	115
16.2	Speech AMR, indicate selective codec modes	Rel-8	C27	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1
16.3	Speech AMR-WB, indicate all codec modes	Rel-8	C28	UE supports MTSI and MTSI speech and MTSI speech, AMR wideband and preconditions and E-UTRA and not UE category M1
16.4	Speech AMR-WB, indicate selective codec modes	Rel-8	C28	UE supports MTSI and MTSI speech and MTSI speech, AMR wideband and preconditions and E-UTRA and not UE category M1
16.5	Void			
16.6	Void			
16.7	Void			
16.8	Void			
16.10	Void			
16.11	Void			
16.12	Void Void			
16.13 17	Media use cases			
17.1	MO Speech, add video remove video	Rel-8	C71	UE supports MTSI and initiating a session and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and E-UTRA and not UE category M1
17.2	MT Speech, add video remove video	Rel-8	C70	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and E-UTRA and not UE category M1
17.4	Void			
17.5	Void			
17.6	Void			
17.8	Void		1	
17.10	Void Void		 	
17.12 17.14	Void		1	
17.14	Void			
17.16	Void		1	
17.17	Void		 	
18	SMS over IMS			
18.1	Mobile Originating SMS	Rel-8	C55	UE supports MO SMS over IMS and E-UTRA and UE configured to use SMS over IP and UE is not category M1
18.1a	Mobile Originating Concatenated SMS	Rel-8	C168	UE supports concatenated SM-over-IP sender and E-UTRA and UE is not category M1
18.1b	Mobile Originating SMS / RP-ERROR	Rel-8	C55	UE supports MO SMS over IMS and E-UTRA and UE configured to use SMS over IP and UE is not category M1

Clause	Title	Release	Applicability	Comments
18.2	Mobile Terminating SMS	Rel-8	C56	UE supports SM-over-IP receiver and E-UTRA and UE configured to use SMS over IP and UE is not category M1
18.2a	Mobile Terminating Concatenated SMS	Rel-8	C169	UE supports concatenated SM-over-IP receiver and E-UTRA and UE is not category M1
19	Emergency Service			
19.1.1	Emergency call with emergency registration / Success / Location information available	Rel-9	C76	UE supports EPS IMS emergency call and is capable of obtaining location information and E-UTRA and not UE category M1
19.1.2	Emergency call with emergency registration / Success / Location information not available	Rel-9	C59	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.1.3	Emergency call with emergency registration / Abnormal case / IM CN sends a 380 / UE performs emergency call via CS domain / UTRAN or GERAN	Rel-9	C62	UE supports EPS IMS emergency call and Emergency speech call and (UTRAN or GERAN) (NOTE 2, 6)
19.1.3a	Emergency call with emergency registration / Abnormal case / IM CN sends a 380 / UE performs emergency call via CS domain / CDMA 2000 1xRTT	Rel-9	C74	UE supports EPS IMS emergency call and Emergency speech call and 1XRTT (NOTE 2)
19.1.3b	Void			
19.1.3c	Emergency call with emergency registration / Abnormal case / IM CN sends 503 Service Unavailable / UE performs emergency call via CS domain / UTRAN or GERAN	Rel-9	C62	UE supports EPS IMS emergency call and Emergency speech call and (UTRAN or GERAN) (NOTE 6)
19.1.4	Void			
19.1.5	Emergency call with emergency registration / Emergency SIP signalling and media in parallel with an other ongoing IM CN subsystem signalling and media	Rel-9	C72	UE supports MTSI and MTSI speech and EPS IMS emergency call and Communication Hold during emergency call and preconditions and E-UTRA and not UE category M1
19.1.6	Emergency call with emergency registration / Success / GIBA against a network with GIBA support only	Rel-9	C124	UE supports IMS security and GIBA and EPS IMS emergency call and E- UTRA and not UE category M1
19.3.1	Non-UE detectable emergency call / IM CN sends a 1xx response / UE geographical location information available or not	Rel-9	C73	UE supports EPS IMS emergency call and MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1
19.3.2	Non-UE detectable emergency call / IM CN sends 380 Alternative Service including emergency service URN and no emergency subservice type / Non-emergency IMS registration / UTRAN or GERAN	Rel-9	C66	UE supports MTSI and MTSI Speech and EPS IMS emergency call and (UTRAN or GERAN) (NOTE 2, 6)
19.3.2a	Non-UE detectable emergency call / IM CN sends 380 Alternative Service / Non-emergency IMS registration / CDMA 2000 1xRTT	Rel-9	C75	UE supports initiating bidirectional voice session over IMS and MTSI Speech and IMS emergency call and emergency call over 1XRTT (NOTE 2)
19.3.2b	Non-UE detectable emergency call / IM CN sends a 380 with unavailable emergency service URN / UE performs normal call via CS domain / UTRAN or GERAN	Rel-9	C66	UE supports MTSI and MTSI Speech and EPS IMS emergency call and emergency call and (UTRAN or GERAN) (NOTE 6)
19.3.2c	Non-UE detectable emergency call / IM CN sends a 380 with available emergency service URN / UE performs CS Emergency call via CS domain / UTRAN or GERAN	Rel-9	C66	UE supports MTSI and MTSI Speech and EPS IMS emergency call and emergency call and (UTRAN or GERAN) (NOTE 6)
19.3.3	Non-UE detectable emergency call / IM CN sends 380 Alternative Service / Emergency IMS registration	Rel-9	C73	UE supports EPS IMS emergency call and MTSI and MTSI speech and E- UTRA and not UE category M1
19.3.4	Non-UE detectable emergency call / IM CN sends 380 with an Alternative Service / Previous emergency IMS registration not expired	Rel-9	C73	UE supports EPS IMS emergency call and MTSI and MTSI speech and E- UTRA and not UE category M1
19.4.1	Emergency call without emergency registration / EPS / UE does not contain an ISIM or USIM	Rel-9	C162	UE supports EPS IMS emergency call and E-UTRA and not UE category M1 and no USIM test execution
19.4.2	Emergency call without emergency registration / EPS / UE contains an ISIM or USIM / UE is in state EMM-REGISTERED.LIMITED-SERVICE	Rel-9	C64	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.4.3	Void			
19.4.4	Void			

Clause	Title	Release	Applicability	Comments
19.4.5	Emergency call without emergency registration / UE credentials are not accepted	Rel-9	C59	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.4.6	Emergency call without emergency registration / Failure of registration / Rejected by 403 (Forbidden)	Rel-9	C125	UE supports IMS emergency service and IMS emergency call without registration after rejection of emergency registration and E-UTRA and not UE category M1
19.4.7	Emergency call without emergency registration / Failure of registration / against a network with GIBA support only	Rel-9	C134	UE supports EPS IMS emergency call and IMS emergency call without registration after rejection of emergency registration that used IMS security. The UE does not support GIBA. UE supports IMS security and E-UTRA and not UE category M1
19.5.1	New initial emergency registration / UE obtains from the serving IP-CAN an IP address different than the IP address used for the emergency registration	Rel-9	C59	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.5.6	User-initiated emergency reregistration / UE has emergency related ongoing dialog	Rel-9	C59	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.5.7	User-initiated emergency reregistration / The user initiates an emergency call	Rel-9	C59	UE supports EPS IMS emergency call and E-UTRA and not UE category M1
19.5.8 19.5.9	Void In parallel emergency and non-emergency	Rel-9	C59	UE supports EPS IMS emergency call
19.5.10	registrations Deregistration upon emergency registration expiration	Rel-9	C59	and E-UTRA and not UE category M1 UE supports EPS IMS emergency call and E-UTRA and not UE category M1
20	Customized Alerting Tones (CAT)			and E-OTTA and not be category wit
20.1	Mobile Originating CAT - Forking Model	Rel-8	C82	UE supports MTSI and MTSI speech and early media and preconditions and E-UTRA and not UE category M1
21	eCall over IMS (eCall)			
21.1	eCall over IMS / Manual initiation / Normal registration / Emergency registration / Success / 200 OK with ACK	Rel-14	C147	UE supports IMS eCall type of emergency services over EPS and Manual type of eCall (NOTE 7)
21.2	eCall over IMS / Automatic initiation / Normal registration / Emergency registration / Success / 200 OK with ACK	Rel-14	C148	UE supports IMS eCall type of emergency services over EPS and Automatic type of eCall (NOTE 7)
21.3	eCall over IMS / Manual initiation / MSD transfer Failure / UE performs eCall in CS domain after Timer expiry / UTRAN or GERAN	Rel-14	C147	UE supports IMS eCall type of emergency services over EPS and manual type of eCall (NOTE 7)
21.4	eCall over IMS / Manual initiation / MSD transfer and 200 OK with ACK / SIP INFO request for MSD Update / Success	Rel-14	C147	UE supports IMS eCall type of emergency services over EPS and Manual type of eCall (NOTE 7)
21.5	eCall over IMS / Automatic initiation / MSD transfer and 200 OK with ACK / SIP INFO request for MSD Update / Success	Rel-14	C148	UE supports IMS eCall type of emergency services over EPS and Automatic type of eCall (NOTE 7)
21.6	eCall over IMS / Automatic initiation / MSD transfer and 200 OK with ACK / SIP INFO request for unsupported MSD / UE indicates unsuccessful in SIP INFO	Rel-14	C148	UE supports IMS eCall type of emergency services over EPS and Automatic type of eCall (NOTE 7)
21.13	eCall only mode / Manual initiation / Emergency registration / Abnormal case / IM CN sends a 486 (Busy Here) / UE performs eCall in CS domain / UTRAN or GERAN	Rel-14	C149	UE supports IMS eCall Only type of emergency services over EPS and manual type of call (NOTE 7)
21.14	eCall only mode / Automatic initiation / Emergency registration / Abnormal case / IM CN sends a 486 (Busy Here) / UE performs eCall in CS domain / UTRAN or GERAN	Rel-14	C150	UE supports IMS eCall Only type of emergency services over EPS and Automatic type of eCall (NOTE 7)
21.15	eCall only mode / Manual initiation / Emergency registration / Abnormal case / IM CN sends a 600 (Busy Everywhere) / UE performs eCall in CS domain / UTRAN or GERAN	Rel-14	C149	UE supports IMS eCall Only type of emergency services over EPS and manual type of call (NOTE 7)
21.16	eCall only mode / Automatic initiation / Emergency registration / Abnormal case / IM CN sends a 600 (Busy Everywhere) / UE performs eCall in CS domain / UTRAN or GERAN	Rel-14	C150	UE supports IMS eCall Only type of emergency services over EPS and Automatic type of eCall (NOTE 7)

Clause	Title	Release	Applicability	Comments
21.17	eCall only mode / Manual initiation /	Rel-14	C149	UE supports IMS eCall Only type of
	Emergency registration / Abnormal case / IM CN sends a 603 (Decline) / UE performs eCall in CS domain / UTRAN or GERAN			emergency services over EPS and manual type of call (NOTE 7)
21.18	eCall only mode / Automatic initiation / Emergency registration / Abnormal case / IM CN sends a 603 (Decline) / UE performs eCall in CS domain / UTRAN or GERAN	Rel-14	C150	UE supports IMS eCall Only type of emergency services over EPS and Automatic type of eCall (NOTE 7)
22	Session Timer			
22.1	MO Call – UE is able to refresh the session	Rel-8	C157	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1 and Session Timer
22.2	MO Call – Remote end is refresher	Rel-8	C157	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1 and Session Timer
22.3	MO Call – Remote end does not support Session Timer	Rel-8	C157	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1 and Session Timer
22.4	MO Call – Remote end seems oblivious to Session Timer parameters	Rel-8	C157	UE supports MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1 and Session Timer
22.5	MT Call – Remote end does not send Session-Expires	Rel-8	C158	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1 and Session Timer
22.6	MT Call – Remote end sends Session- Expires but does not choose refresher	Rel-8	C158	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1 and Session Timer
22.7	MT Call – Remote end chooses UE as refresher	Rel-8	C158	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1 and Session Timer
22.8	MT Call – Remote end does not support Session Timer	Rel-8	C158	UE supports MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1 and Session Timer
G.8	Registration / WLAN			
G.8.1	Initial Registration / WLAN	Rel-11	C108	UE supports MTSI and WLAN
G.12	Call Control / WLAN	5 1 1 1	0.150	
G.12.1 G.12.2	MO MTSI speech call / WLAN MT MTSI speech call / WLAN	Rel-11	C152	UE supports MTSI and MTSI speech and preconditions and WLAN UE supports MTSI and MTSI speech
0.12.2	WIT WITOI Speech call / WEAR	I Kei-11	0132	and preconditions and WLAN
G.12.3	MO MTSI video call / WLAN	Rel-11	C153	UE supports MTSI and MTSI speech and MTSI video and preconditions and WLAN
G.12.4	MT MTSI video call / WLAN	Rel-11	C153	UE supports MTSI and MTSI speech and MTSI video and preconditions and WLAN
G.15	Supplementary Services / WLAN			
G.15.1	Originating Identification Presentation / WLAN	Rel-11	C92	UE supports MTSI and MTSI Originating Identification Presentation and WLAN
G.15.2	Originating Identification Restriction / Signalling / WLAN	Rel-11	C93	UE supports MTSI and MTSI Originating Identification Restriction and preconditions and WLAN
G.15.3	Terminating Identification Presentation / WLAN	Rel-11	C94	UE supports MTSI and MTSI Terminating Identification Presentation and WLAN
G.15.4	Terminating Identification Restriction / Signalling / WLAN	Rel-11	C95	UE supports MTSI and MTSI Terminating Identification Restriction and preconditions and WLAN
G.15.5	Communication Forwarding unconditional / WLAN	Rel-11	C101	UE supports MTSI and MTSI Communication Diversion and WLAN
G.15.6	Communication Forwarding on non Reply: activation / WLAN	Rel-11	C101	UE supports MTSI and MTSI Communication Diversion and WLAN
G.15.7	Communication Forwarding on non reply: MO call initiation / WLAN	Rel-11	C102	UE supports MTSI and MTSI speech and MTSI Communication Diversion and preconditions and WLAN

Clause	Title	Release	Applicability	Comments
G.15.8	Communication Forwarding on Busy / WLAN	Rel-11	C101	UE supports MTSI and MTSI Communication Diversion and WLAN
G.15.9	Communication Forwarding on Not logged-in / WLAN	Rel-11	C101	UE supports MTSI and MTSI Communication Diversion and WLAN
G.15.10	Communication Forwarding on Not reachable /	Rel-11	C101	UE supports MTSI and MTSI Communication Diversion and WLAN
G.15.11	MO Call Hold without announcement / WLAN	Rel-11	C109	UE supports MTSI and MTSI speech and MTSI Communication Hold and preconditions and WLAN
G.15.12	MT Call Hold without announcement / WLAN	Rel-11	C109	UE supports MTSI and MTSI speech and Communication Hold and preconditions and WLAN
G.15.13	MO video Call Hold without announcement / WLAN	Rel-11	C110	UE supports MTSI and MTSI speech and MTSI video and MTSI Communication Hold and preconditions and WLAN
G.15.14	MT video Call Hold without announcement / WLAN	Rel-11	C110	UE supports MTSI and MTSI speech and MTSI video and MTSI Communication Hold and preconditions and WLAN
G.15.15	Incoming Communication Barring while roaming / WLAN	Rel-11	C111	UE supports MTSI and MTSI Incoming Communication Barring and WLAN and (GBA or HTTP Digest) (NOTE 4)
G.15.16	Outgoing Communication Barring while roaming / WLAN	Rel-11	C112	UE supports MTSI and Outgoing Communication Barring and WLAN and (GBA or HTTP Digest) (NOTE 4)
G.15.17	Subscription to the MWI event package / WLAN	Rel-11	C113	UE supports MTSI and MTSI Message Waiting Indication and WLAN
G.15.18	Inviting user to conference by sending a REFER request to the conference focus / WLAN	Rel-11	C114	UE supports MTSI and MTSI speech and MTSI Conference and preconditions and WLAN
G.15.19	Void			
G.15.20	Three way session creation / WLAN	Rel-11	C116	UE supports MTSI and MTSI speech and MTSI Conference and MTSI three way session and preconditions and WLAN
G.15.21	Inviting user to conference by sending a REFER request to the conference focus for video / WLAN	Rel-11	C117	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and preconditions and WLAN
G.15.22	Void			
G.15.23	Three way session creation for video / WLAN	Rel-11	C119	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and MTSI three way session and preconditions and WLAN
G.15.24	Communication Waiting and answering the call / WLAN	Rel-11	C120	UE supports MTSI and MTSI speech and MTSI Communication Waiting and preconditions and WLAN
G.15.25	Communication Waiting and cancelling the call / WLAN	Rel-11	C120	UE supports MTSI and MTSI speech and MTSI Communication Waiting and preconditions and WLAN
G.17	Media use cases / WLAN			
G.17.1	MO Speech, add video remove video / WLAN	Rel-11	C106	UE supports MTSI and initiating a session and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and WLAN
G.17.2	MT Speech, add video remove video / WLAN	Rel-11	C107	UE supports MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and preconditions and WLAN
G.19	Emergency Service over IMS / WLAN			
G.19.1	Emergency call with emergency registration / WLAN	Rel-11	C121	UE supports IMS emergency call over WLAN and WLAN
H.8	Registration / Fixed Broadband Access			
H.8.1	Initial registration / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.8.2	User Initiated Re-Registration / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.8.3	User Initiated Deregistration / Fixed Broadband Access	Rel-12	C100	UE supports SIP Digest without TLS and Fixed Broadband and IMS deregistration

Clause	Title	Release	Applicability	Comments
H.8.4	Invalid behaviour- 423 Interval too brief / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.8.5	User initiated re-registration - 423 Interval Too Brief / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.9	Authentication / Fixed Broadband Access			
H.9.1	SIP digest without TLS - abnormal procedures - 403 Forbidden / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.11	Notification / Fixed Broadband Access			
H.11.2	Network initiated re-authentication / Fixed Broadband Access	Rel-12	C90	UE supports SIP Digest without TLS and Fixed Broadband
H.12	Call Control / Fixed Broadband Access			
H.12.1	Originating - 503 Service Unavailable / Fixed Broadband Access	Rel-12	C91	UE supports MTSI and MTSI speech and SIP Digest without TLS and no preconditions and Fixed Broadband
H.12.2	Originating - 504 Server Time-out / Fixed Broadband Access	Rel-12	C161	UE supports MTSI and MTSI speech and SIP Digest without TLS and preconditions and Fixed Broadband
H.12.3	Originating MTSI Voice Call Successful with preconditions / Fixed Broadband Access	Rel-12	C161	UE supports MTSI and MTSI speech and SIP Digest without TLS and preconditions and Fixed Broadband
H.12.4	Originating MTSI Voice Call Successful without preconditions / Fixed Broadband Access	Rel-12	C105	UE supports MTSI and MTSI speech and SIP Digest without TLS and no preconditions and Fixed Broadband
H.12.5	Terminating MTSI Voice call with preconditions / Fixed Broadband Access	Rel-12	C161	UE supports MTSI and MTSI speech and SIP Digest without TLS and preconditions and Fixed Broadband
H.12.6	Terminating MTSI voice call without preconditions / Fixed Broadband Access	Rel-12	C105	UE supports MTSI and MTSI speech and SIP Digest without TLS and no preconditions and Fixed Broadband
H.12.7	Originating MTSI Video call without preconditions / Fixed Broadband Access	Rel-12	C122	UE supports MTSI and MTSI speech and video and SIP Digest without TLS and no preconditions and Fixed Broadband
H.12.8	Terminating MTSI Video call without preconditions / Fixed Broadband Access	Rel-12	C122	UE supports MTSI and MTSI speech and video and SIP Digest without TLS and no preconditions and Fixed Broadband
H.15	Supplementary Services / Fixed Broadband Access			

Clause	Title	Release	Applicability	Comments
H.15.1	Originating Identification Presentation / Fixed Broadband Access	Rel-12	C96	UE supports MTSI and MTSI Originating Identification Presentation and Fixed Broadband
H.15.2	Originating Identification Restriction / Signalling / Fixed Broadband Access	Rel-12	C97	UE supports MTSI and MTSI Originating Identification Restriction and preconditions and Fixed Broadband
H.15.3	Terminating Identification Presentation / Fixed Broadband Access	Rel-12	C98	UE supports MTSI and MTSI Terminating Identification Presentation and Fixed Broadband
H.15.4	Terminating Identification Restriction / Signalling / Fixed Broadband Access	Rel-12	C99	UE supports MTSI and MTSI Terminating Identification Restriction and no preconditions and Fixed Broadband
H.15.5	Communication Forwarding unconditional / Fixed Broadband Access	Rel-12	C103	UE supports MTSI and MTSI Communication Diversion and Fixed Broadband
H.15.6	Communication Forwarding on non Reply: activation / Fixed Broadband Access	Rel-12	C103	UE supports MTSI and MTSI Communication Diversion and Fixed Broadband
H.15.7	Communication Forwarding on non reply: Originating call initiation / Fixed Broadband Access	Rel-12	C104	UE supports MTSI and MTSI speech and MTSI Communication Diversion and no preconditions and Fixed Broadband
H.15.8	Communication Forwarding on Busy / Fixed Broadband Access	Rel-12	C103	UE supports MTSI and MTSI Communication Diversion and Fixed Broadband
H.15.9	Communication Forwarding on Not logged- in / Fixed Broadband	Rel-12	C103	UE supports MTSI and MTSI Communication Diversion and Fixed Broadband
H.15.10	Communication Forwarding on Not reachable / Fixed Broadband	Rel-12	C103	UE supports MTSI and MTSI Communication Diversion and Fixed Broadband
H.15.11	Self-Configuration via SIP based procedure / Fixed Broadband Access	Rel-12	C123	UE supports MTSI and MTSI Communication Diversion and SIP- based configuration and Fixed Broadband
H.17	Media use cases / Fixed Broadband Access			
H.17.1	Originating Voice, add video remove video / Fixed Broadband Access	Rel-12	C122	UE supports MTSI and MTSI speech and MTSI video and SIP Digest without TLS and no preconditions and Fixed Broadband
H.17.2	Terminating Voice, add video remove video / Fixed Broadband Access	Rel-12	C122	UE supports MTSI and MTSI speech and MTSI video and SIP Digest without TLS and no preconditions and Fixed Broadband
1.8	RCS	,	0405	115
I.8.1a	Initial Registration / single / E-UTRA	n/a	C135	UE supports combined registration over E-UTRA
I.8.1b	Initial Registration / dual / E-UTRA	n/a	C136	UE supports registration to two IMS core networks over E-UTRA
I.8.1c	Initial Registration / single / WLAN	n/a	C137	UE supports combined registration over WLAN
I.8.1d	Initial Registration / dual / WLAN	n/a	C138	UE supports registration to two IMS core networks over WLAN
I.12.1a	MO voice call / single / E-UTRA	n/a	C139	UE supports voice call after combined registration over E-UTRA
I.12.1b	MO voice call / dual / E-UTRA	n/a	C140	UE supports voice call after dual
I.12.1c	MO voice call / single / WLAN	n/a	C141	registration over E-UTRA UE supports voice call after combined
I.12.1d	MO voice call / dual / WLAN	n/a	C142	registration over WLAN UE supports voice call after dual
I.12.2a	RCS chat / single / E-UTRA	n/a	C143	registration over WLAN UE supports RCS chat after combined
I.12.2b	RCS chat / dual / E-UTRA	n/a	C144	registration over E-UTRA UE supports RCS chat after dual
I.12.2c	RCS chat / single / WLAN	n/a	C145	registration over E-UTRA UE supports RCS chat after combined
I.12.2d	RCS chat / dual / WLAN	n/a	C146	registration over WLAN UE supports RCS chat after combined
			1	registration over E-UTRA

Clause	Title	Release	Applicability	Comments
J.8.1	Initial Registration / UE category M1	Rel-13	C126	UE supports MTSI and UE category M1
J.12	Call control / UE category M1			IVII
J.12.1	MO MTSI speech call / UE category M1	Rel-13	C163	UE supports MTSI and preconditions and UE category M1
J.12.2	MT MTSI speech call / UE category M1	Rel-13	C163	UE supports MTSI and preconditions and UE category M1
J.15	Supplementary Services / UE category M1			
J.15.1	Communication Waiting and answering the call / UE category M1	Rel-13	C127	UE supports MTSI and MTSI Communication Waiting and preconditions and UE category M1
J.15.2	Communication Waiting and cancelling the call / UE category M1	Rel-13	C127	UE supports MTSI and MTSI Communication Waiting and preconditions and UE category M1
J.15.3	Subscription to the MWI event package / UE category M1	Rel-13	C128	UE supports MTSI and MTSI Message Waiting Indication and UE category M1
J.15.4	Originating Identification Restriction / Signalling / UE category M1	Rel-13	C129	UE supports MTSI and MTSI Originating Identification Restriction and preconditions and UE category M1
J.15.5	Terminating Identification Restriction / Signalling / UE category M1	Rel-13	C130	UE supports MTSI and MTSI Terminating Identification Restriction and preconditions and UE category M1
J.15.6	Communication forwarding on non-reply: MO call initiation / UE category M1	Rel-13	C131	UE supports MTSI and MTSI Communication Diversion and preconditions and UE category M1
J.18	SMS over IMS / UE category M1			-
J.18.1	Mobile Originating SMS / UE category M1	Rel-13	C154	UE supports MO SMS over IMS and UE configured to use SMS over IP and UE is category M1
J.18.2	Mobile Terminating SMS / UE category M1	Rel-13	C155	UE supports SM-over-IP receiver and UE configured to use SMS over IP and UE is category M1
J.19	Emergency Service over IMS / UE category M1			
J.19.1	Emergency call with emergency registration / Success / Location information available / UE category M1	Rel-13	C132	UE supports EPS IMS emergency call and is capable of obtaining location information and UE category M1
J.19.2	Emergency call with emergency registration / Success / Location information not available / UE category M1	Rel-13	C133	UE supports EPS IMS emergency call and UE category M1

NOTE 1: Applicability of test cases 13.2 and 13.3 are currently marked as FFS. The reason to this is that the contents of the specific messages sent by the SS (as currently specified within those Call Control test cases) do not match the contents of those messages as expected by any specific IMS application known. Further on the test specification apparently lacks support for certain application specific message exchanges which are however mandatory for a few specific IMS applications specified outside of TS 24.229. It is necessary to fully resolve the problem (by e.g. defining the applications for which the Call Control test cases would be applicable, possibly specifying the extensions to the test cases like required by those applications and creating the corresponding application profiles) before the applicability statements of Call Control test cases can be unambiguously defined.

- NOTE 2: Either one of the two adjacent test cases, i.e. (19.1.3 or 19.1.3a), (19.3.2 or 19.3.2a), shall be executed.
- NOTE 3: This TC can optionally be executed against Rel-8 and onwards UEs.
- NOTE 4: In case the UE supports both GBA and HTTP Digest, GBA shall be used as XCAP authentication.
- NOTE 5: In case the UE supports both GBA and HTTP Digest, HTTP Digest shall be used as XCAP authentication.

- NOTE 6: The TC contains multi-RAT branches not all mandatory in the scope of the TC. The E-UTRA/EPC branch will be executed always; the TC will go through any other RAT branch depending on the UE capability. Execution only of the E-UTRA/EPC branch regardless of the UE capabilities can also be imposed by setting the IXIT px_RATComb_Tested = EUTRA_only. For UEs supporting both UTRA and GERAN the TC should be executed once only for the E-UTRA/EPC and UTRA combination by setting the px_RATComb_Tested = EUTRA_UTRA.
- NOTE 7: This TC can optionally be executed against Rel-9 and onwards UEs.
- NOTE 8: If TC 12.23a is executed TC 12.23 is optional. If TC 12.24a is executed TC 12.24 is optional.

Table 4.1a: Applicability Conditions for TS 34.229-1 tests

Condition	Test Case Selection Expression	Comment
C00	Void	
C01	Void	
C02	Void	
C03	Void	
C04	IF A.12/4 THEN R ELSE N/A	Dedicated PDP Context
C05	IF A.12/5 THEN R ELSE N/A	P-CSCF Discovery via PCO
C06	IF A.7/1 AND A.13/1 THEN R ELSE N/A	IPv4 and configured to initiate P-CSCF discovery via DHCPv4
C07	IF A.7/1 AND A.12/8 AND A.13/2 AND A.12/5 THEN R ELSE N/A	IPv4 and P-CSCF discovery via PCO and P-CSCF discovery via DHCPv4 and configured to initiate P-CSCF discovery via PCO
C08	IF A.12/7 THEN R ELSE N/A	Configured to initiate P-CSCF discovery via DHCPv6
C09	IF A.12/8 AND A.12/10 AND A.12/5 THEN R ELSE N/A	P-CSCF Discovery via PCO and P- CSCF discovery via DHCPv6 and configured to initiate P-CSCF discovery via PCO
C10	IF A.12/8 AND A.12/10 AND A.12/7 THEN R ELSE N/A	P-CSCF Discovery via PCO and P- CSCF discovery via DHCPv6 and configured to initiate P-CSCF discovery via DHCPv6
C11	Void	
C12	Void	
C13	Void	
C14	Void	
C15	Void	
C16	Void	
C17	IF A.6a/2 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	IMS security and E-UTRA and not UE category M1
C18	IF A.6a/1 AND NOT A.6a/2 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	GIBA and not IMS security and E- UTRA and not UE category M1
C19	IF A.6a/2 AND A.6a/1 THEN R ELSE N/A	IMS security and GIBA
C20	Void	
C21	Void	
C22	Void	
C23	IF A.3A/50 AND A.15/1 AND A.16/6 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
C24	IF A.3A/50 AND A.16/7 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and Incoming Communication Barring and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C25	Void	
C26	Void	
C27	IF A.3A/50 AND A.15/1 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2- 2A/1 THEN R ELSE N/A	MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1
C28	IF A.3A/50 AND A.4/2B AND A.15/1 AND A.15/2 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI speech, AMR wideband and preconditions and E-UTRA and not UE category M1
C29	IF A.3A/50 AND A.15/1 AND A.16/11 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Explicit Communication Transfer - consultative transfer and preconditions and E-UTRA and not UE category M1
C30	IF A.3A/50 AND A.16/5 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Communication Diversion and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C31	IF A.3A/50 AND A.15/1 AND A.16/5 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Communication Diversion and preconditions and E-UTRA and not UE category M1
C32	IF A.3A/50 AND A.15/1 AND A.16/9 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Conference and preconditions and E- UTRA and not UE category M1
C33	Void	
C34	Void	
C35	Void	
C37	Void	
C38	Void	
C39	Void	
C40	Void	
C41	Void	

	Tire	
C42	Void	
C43	IF A.3A/50 AND A.16/1 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Originating Identification Presentation and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C44	IF A.3A/50 AND A.16/2 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Originating Identification Restriction and preconditions and E-UTRA and not UE category M1
C45	IF A.3A/50 AND A.16/7 AND A.16/12 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Communication Barring and MTSI Anonymous Communication Rejection and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C46	Void	
C47	Void	
C48	IF A.3A/50 AND A.16/3 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and Terminating Identification Presentation and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C49	IF A.3A/50 AND A.16/4 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Restriction and preconditions and E-UTRA and not UE category M1
C50	IF A.3A/50 AND A.16/8 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Message Waiting Indication and E-UTRA and not UE category M1
C51	Void	
C52	Void	
C53	Void	
C54	Void	
C55	IF A.3A/61 AND A.18/1 AND [73] A.4.4-2/32 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	SM-over-IP sender and E-UTRA and UE configured to use SMS over IP and UE is not category M1
C56	IF A.3A/62 AND A.18/1 AND [73] A.4.4-2/32 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	SM-over-IP receiver and E-UTRA and UE configured to use SMS over IP and UE is not category M1
C57	IF A.3A/50 AND A.15/1 AND A.16/13 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI communication waiting and preconditions and E-UTRA and not UE category M1
C58	IF A.6a/2 AND A.8/5 THEN R ELSE N/A	IMS security and Indicate Sigcomp
C59	IF [73] A.4.2.1.1-1/4 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A Void	EPS IMS emergency call and E-UTRA and not UE category M1
C60 C61	IF A.3A/50 AND A.16/9 AND A.16/14 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Conference and MTSI three way session and preconditions and E-UTRA and not UE category M1
C62	IF [73] A.4.2.1.1-1/4 AND [34.123-2] A.2/2 AND ([73] A.4.1-1/6 OR [73] A.4.1-1/7) THEN R ELSE N/A	EPS IMS emergency call and emergency speech call and (UTRAN or GERAN)
C63	Void	
C64	IF [73] A.4.2.1.1-1/4 AND A.18/1 AND NOT [73] A.4.3.2-2A/1THEN R ELSE N/A	EPS IMS emergency call and E-UTRA and not UE category M1
C65	Void	FRO 1140
C66	IF [73] A.4.2.1.1-1/4 AND A.12/12 AND A.15/1 AND [34.123-2] A.2/2 AND ([73] A.4.1-1/6 OR [73] A.4.1-1/7) THEN R ELSE N/A	EPS IMS emergency call and initiating bidirectional voice session over IMS and MTSI speech and emergency call and (UTRAN or GERAN)
C67	Void	
C68	Void	
C69	Void	
C70	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI Video H.264 CBP Level 1.2 and preconditions and E-UTRA and not UE category M1
C71	IF A.3A/50 AND A.4/2B AND A.15/1 AND A.15/3 AND A.15/9 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and initiating a session and MTSI speech and MTSI video and MTSI Video H.264 CBP Level 1.2 and preconditions and E-UTRA and not UE category M1

C72	IF [73] A.4.2.1.1-1/4 AND A.3A/50 AND A.15/1 AND A.12/33 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	EPS IMS emergency call and MTSI and MTSI speech and MTSI Communication Hold during emergency call and preconditions and
		E-UTRA and not UE category M1
C73	IF [73] A.4.2.1.1-1/4 AND A.3A/50 AND A.15/1 AND A.18/1 AND NOT [73] A.4.3.2-2A/1THEN R ELSE N/A	EPS IMS emergency call and MTSI and MTSI speech and E-UTRA and not UE category M1
C74	IF [73] A.4.2.1.1-1/4 AND [3] A.2/2 AND [73] A.4.1-1/4 THEN R ELSE N/A	EPS IMS emergency call and emergency speech call and 1xRTT
C75	IF A.12/12 AND A.15/1 AND [3] A.2/2 AND [73] A.4.1-1/4 THEN R ELSE N/A	initiating bidirectional voice session over IMS and MTSI Speech and IMS emergency call and emergency speech call and 1xRTT
C76	IF [73] A.4.2.1.1-1/4 AND A.12/27 AND A.18/1 AND NOT [73] A.4.3.2- 2A/1THEN R ELSE N/A	EPS IMS emergency call and capable of obtaining location Information and E-UTRA and not UE category M1
C77	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.16/6 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI Video H.264 CBP Level 1.2 and MTSI Communication Hold and preconditions and E-UTRA and not UE category M1
C78	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.16/9 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video H.264 CBP Level 1.2 and MTSI Conference and preconditions and E-UTRA and not UE category M1
C79	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.16/9 AND A.16/14 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and MTSI three way session and preconditions and E-UTRA and not UE category M1
C80	IF A.6a/2 AND A.12/39 AND A.18/1 AND ([73] A.4.4-2/5 OR [73] A.4.4-2/8) AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	IMS security and IMS deregistration and E-UTRA and (Support of CS/PS mode 2 or Support of PS mode 2) and not UE category M1
C81	IF A.3A/50 AND A.16/1 AND A.6a/3 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Originating Identification Presentation and GBA for XCAP authentication. and E-UTRA and not UE category M1
C82	IF A.3A/50 AND A.15/1 AND A.12/45 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and early media and preconditions and E-UTRA and not UE category M1
C83	IF A.3A/50 AND A.15/10 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2- 2A/1 THEN R ELSE N/A	MTSI and MTSI speech EVS and preconditions and E-UTRA and not UE category M1
C84	IF A.3A/50 AND A.16/15 AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Outgoing Communication Barring and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C85	Void	
C86	Void	
C87	Void	
C88	IF A.3A/50 AND A.16/2A AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Originating Identification Restriction Configuration and (GBA or HTTP Digest) and E- UTRA and not UE category M1
C89	IF A.3A/50 AND A.16/4A AND (A.6a/3 OR A.6a/4) AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Restriction - Configuration and (GBA or HTTP Digest) and E-UTRA and not UE category M1
C90	IF A.6a/5 AND A.18/3 THEN R ELSE N/A	SIP Digest without TLS and Fixed Broadband
C91	IF A.6a/5 AND A.18/3 AND A.3A/50 AND NOT A.4/16 AND A.15/1 THEN R ELSE N/A	MTSI and MTSI speech and SIP Digest without TLS and no preconditions and Fixed Broadband
C92	IF A.3A/50 AND A.16/1 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Originating Identification Presentation and WLAN
C93	IF A.3A/50 AND A.16/2 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Originating Identification Restriction and preconditions and WLAN
C94	IF A.3A/50 AND A.16/3 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Presentation and WLAN

C95	IF A.3A/50 AND A.16/4 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Restriction and
		preconditions and WLAN
C96	IF A.3A/50 AND A.16/1 AND A.18/3 THEN R ELSE N/A	MTSI and MTSI Originating Identification Presentation and Fixed Broadband
C97	IF A.3A/50 AND A.16/2 AND A.18/3 THEN R ELSE N/A	MTSI and MTSI Originating Identification Restriction and Fixed Broadband
C98	IF A.3A/50 AND A.16/3 AND A.18/3 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Presentation and Fixed Broadband
C99	IF A.3A/50 AND A.16/4 AND NOT A.4/16 AND A.18/3 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Restriction and no preconditions and Fixed Broadband
C100	IF A.6a/5 AND A.18/3 AND A.12/39 THEN R ELSE N/A	SIP Digest without TLS and Fixed Broadband and IMS deregistration
C101	IF A.3A/50 AND A.16/5 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Communication Diversion and WLAN
C102	IF A.3A/50 AND A.15/1 AND A.16/5 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Communication Diversion and preconditions and WLAN
C103	IF A.3A/50 AND A.16/5 AND A.18/3 THEN R ELSE N/A	MTSI and MTSI Communication Diversion and Fixed Broadband
C104	IF A.3A/50 AND A.15/1 AND A.16/5 AND A.18/3 AND NOT A.4/16 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Communication Diversion and Fixed Broadband and no preconditions
C105	IF A.3A/50 AND A.6a/5 AND A.18/3 AND A.15/1 AND NOT A.4/16 THEN R ELSE N/A	MTSI and MTSI speech and SIP Digest without TLS and Fixed Broadband and no preconditions
C106	IF A.3A/50 AND A.4/2B AND A.15/1 AND A.15/3 AND A.15/9 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and initiating a session and MTSI speech and MTSI video and MTSI Video H.264 CBP Level 1.2 and preconditions and WLAN
C107	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI Video H.264 CBP Level 1.2 and preconditions and WLAN
C108	IF A.3A/50 AND A.18/4 THEN R ELSE N/A	MTSI and WLAN
C109	IF A.3A/50 AND A.15/1 AND A.16/6 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Communication Hold and preconditions and WLAN
C110	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.16/6 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI Communication Hold and preconditions and WLAN
C111	IF A.3A/50 AND A.16/7 AND A.18/4 AND (A.6a/3 OR A.6a/4) THEN R ELSE N/A	MTSI and MTSI Incoming Communication Barring and WLAN and (GBA or HTTP Digest)
C112	IF A.3A/50 AND A.16/15 AND A.18/4 AND (A.6a/3 OR A.6a/4) THEN R ELSE N/A	MTSI and MTSI Outgoing Communication Barring and WLAN and (GBA or HTTP Digest)
C113	IF A.3A/50 AND A.16/8 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI Message Waiting Indication and WLAN
C114	IF A.3A/50 AND A.15/1 AND A.16/9 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Conference and preconditions and WLAN
C115	Void	
C116	IF A.3A/50 AND A.15/1 AND A.16/9 AND A.16/14 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI Conference and MTSI three way session and preconditions and WLAN
C117	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.16/9 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and preconditions and WLAN
C118	Void	
C119	IF A.3A/50 AND A.15/1 AND A.15/3 AND A.15/9 AND A.16/9 AND A.16/14 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and MTSI video H.264 CBP Level 1.2 and MTSI Conference and MTSI three way session and preconditions and WLAN
C120	IF A.3A/50 AND A.15/1 AND A.16/13 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and MTSI communication waiting and preconditions and WLAN
C121		preconditions and WLAN

C122	IF A.3A/50 AND A.6a/5 AND A.18/3 AND A.15/1 AND A.15/3 AND NOT A.4/16 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and SIP Digest without TLS and
C123	IF A.3A/50 AND A.16/5 AND A.16/18 AND A.18/3 THEN R ELSE N/A	Fixed Broadband and no preconditions MTSI and MTSI Communication Diversion and SIP-based configuration and Fixed Broadband
C124	IF A.6a/2 AND A.6a/1 AND [73] A.4.2.1.1-1/4 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	IMS security and GIBA and EPS IMS emergency call and E-UTRA and not UE category M1
C125	IF [73] A.4.2.1.1-1/4 AND A.12/52 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	EPS IMS emergency call and IMS emergency call without registration after rejection of emergency registration and E-UTRA and not UE category M1
C126	IF A.3A/50 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and preconditions and UE category M1
C127	IF A.3A/50 AND A.16/13 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI communication waiting and preconditions and UE category M1
C128	IF A.3A/50 AND A.16/8 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Message Waiting Indication and UE category M1
C129	IF A.3A/50 AND A.16/2 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Originating Identification Restriction and preconditions and UE category M1
C130	IF A.3A/50 AND A.16/4 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Terminating Identification Restriction and preconditions and UE category M1
C131	IF A.3A/50 AND A.16/5 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI Communication Diversion and preconditions and UE category M1
C132	IF [73] A.4.2.1.1-1/4 AND A.12/27 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	EPS IMS emergency call and capable of obtaining location Information and UE category M1
C133	IF [73] A.4.2.1.1-1/4 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	EPS IMS emergency call and UE category M1
C134	IF A.6a/2 AND NOT A.6a/1 AND [73] A.4.2.1.1-1/4 AND A.12/52 AND A.18/1 AND NOT [73] A.4.3.2-2A/1THEN R ELSE N/A	IMS security and NOT GIBA and EPS IMS emergency call and IMS emergency call without registration after rejection of emergency registration. UE supports E-UTRA and not UE category M1
C135	IF A.20/1 THEN R ELSE N/A	Combined Registration E-UTRA
C136 C137	IF A.20/2 THEN R ELSE N/A IF A.20/3 THEN R ELSE N/A	Dual Registration E-UTRA Combined Registration WLAN
C137	IF A.20/4 THEN R ELSE N/A	Dual Registration WLAN
C139	IF A.20/5 THEN R ELSE N/A	Voice Call after combined registration E-UTRA
C140	IF A.20/6 THEN R ELSE N/A	Voice call after dual registration E- UTRA
C141	IF A.20/7 THEN R ELSE N/A	Voice Call after combined registration WLAN
C142	IF A.20/8 THEN R ELSE N/A	Voice call after dual registration WLAN
C143	IF A.20/9 THEN R ELSE N/A	RCS chat after combined registration E-UTRA
C144	IF A.20/10 THEN R ELSE N/A	RCS chat after dual registration E- UTRA
C145	IF A.20/11 THEN R ELSE N/A	RCS chat after combined registration WLAN
C146	IF A.20/12 THEN R ELSE N/A	RCS chat after dual registration WLAN
C147	IF A.12/54 AND [3] A.10/16 THEN R ELSE N/A	IMS eCall type of emergency services over EPS and manual type of eCall
C148	IF A.12/54 AND [3] A.10/17 THEN R ELSE N/A	IMS eCall type of emergency services over EPS and automatic type of eCall
C149	IF A.12/55 AND [3] A.10/16 THEN R ELSE N/A	IMS eCall Only type of emergency services over EPS and manual type of eCall
C150	IF A.12/55 AND [3] A.10/17 THEN R ELSE N/A	IMS eCall Only type of emergency services over EPS and automatic type of eCall
C151	IF A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	E-UTRA and not UE category M1
C152	IF A.3A/50 AND A.15/1 AND A.4/16 AND A.18/4 THEN R ELSE N/A	MTSI and MTSI speech and preconditions and WLAN
C153	IF A.3A/50 AND A.15/1 AND A.4/16 AND A.18/4 AND A.15/3 THEN R ELSE N/A	MTSI and MTSI speech and MTSI video and preconditions and WLAN

0454	IE A OA/CA AND [70] A A A O/OO AND [70] A A O O OA/A THEN D EL CE AL/A	CM aver ID and are and UE and C
C154	IF A.3A/61 AND [73] A.4.4-2/32 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	SM-over-IP sender and UE configured to use SMS over IP and UE is category M1
C155	IF A.3A/62 AND [73] A.4.4-2/32 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	SM-over-IP receiver and UE configured to use SMS over IP and UE is category M1
C156	Void	-
C157	IF A.3A/50 AND A.15/1 AND A.4/2B AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 AND A.12/57 THEN R ELSE N/A	MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1 and Session Timer
C158	IF A.3A/50 AND A.15/1 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2- 2A/1 AND A.12/57 THEN R ELSE N/A	MTSI and MTSI speech and preconditions and E-UTRA and not UE category M1 and Session Timer
C159	IF A.3A/50 AND A.15/1 AND A.4/2B AND A.18/1 AND A.16/19 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	UE supports MTSI and MTSI speech and initiating a session and E-UTRA and USSI and not UE category M1
C160	IF A.3A/50 AND A.15/1 AND A.4/2B AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and initiating a session and preconditions and E-UTRA and not UE category M1
C161	IF A.6a/5 AND A.18/3 AND A.3A/50 AND A.4/16 AND A.15/1 THEN R ELSE N/A	MTSI and MTSI speech and SIP Digest without TLS and preconditions and Fixed Broadband
C162	IF [73] A.4.2.1.1-1/4 AND A.18/1 AND [3] A.20/90 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	EPS IMS emergency call and E-UTRA and no USIM test execution and not UE category M1
C163	IF A.3A/50 AND A.4/16 AND [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and preconditions and UE category M1
C164	IF A.3A/50 AND A.15/1 AND A.4/2B AND NOT A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and initiating a session and no preconditions and E-UTRA and not UE category M1
C165	IF A.3A/50 AND A.15/1 AND A.18/1 AND NOT A.4/16 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	UE supports MTSI and MTSI speech and E-UTRA and no preconditions and not UE category M1
C166	Void	
C167	IF A.3A/50 AND A.15/1 AND A.15/2 AND NOT A.15/10 AND A.4/16 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	MTSI and MTSI speech and MTSI speech, AMR wideband and not MTSI speech, EVS and preconditions and E-UTRA and not UE category M1
C168	IF A.3A/64 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	Concatenated SM-over-IP sender and E-UTRA and UE is not category M1
C169	IF A.3A/65 AND A.18/1 AND NOT [73] A.4.3.2-2A/1 THEN R ELSE N/A	Concatenated SM-over-IP receiver and E-UTRA and UE is not category M1
C170	IF A.3A/50 AND A.15/1 AND A.4/16 AND [93] A.4.1-3/2 THEN R ELSE N/A	UE supports MTSI and MTSI speech and preconditions and EN-DC

4.2 Applicabilities for test cases specified in TS 34.229-5

Table 4.2: Applicability of TS 34.229-5 tests

6 6.1 6.2 6.3 6.4	Registration Initial Registration / 5GS Initial Registration Failures / 5GS	Rel-15	C01	
6.2 6.3 6.4	Initial Registration Failures / 5GS	Rel-15	C01	
6.3 6.4			001	UE supports NR (see Note 1 below)
6.4		Rel-15	C01	UE supports NR
	Re-Registration Scenarios / 5GS	Rel-15	C01	UE supports NR
6.5	De-Registration Scenarios / 5GS	Rel-15	C13	UE supports NR and IMS de-
6.5				registration
0.0	Void	D-145	045	HE amount ND and
6.6	Re-Registration after capability update / 5GS	Rel-15	C15	UE supports NR and
6.7	Authentication / MAC Parameter Invalid /	Rel-15	C01	Enabling/Disabling SMS over IMS UE supports NR
0.7	Only two consecutive challenges / 5GS	Kel-13	COT	OL Supports NK
6.8	Authentication / Security Server missing /	Rel-15	C01	UE supports NR
0.0	SQN out of range / 5GS	1101 10	001	OE Supports (III)
6.9	Subscription / 503 Service Unavailable /	Rel-15	C01	UE supports NR
	5GS			
7	Call Control			
7.1	MTSI MO Voice Call / 503 Service	Rel-15	C28	UE supports NR and IMS voice over
ŀ	Unavailable / 5GS			NR and MTSI speech and
ŀ				preconditions and disabling
				preconditions and NG114 v1.0
7.2	MTSI MO Voice Call / 504 Server Time-out /	Rel-15	C28	UE supports NR and IMS voice over
ŀ	5GS			NR and MTSI speech and
ŀ				preconditions and disabling
7.3	Void			preconditions and NG114 v1.0
7.4	Void			
7.4a	MTSI MO Voice Call with preconditions at	Rel-15	C44	NR and IMS voice over NR and MTSI
7τα	both originating UE and terminating UE /	1101 10	011	Speech and preconditions and
	Default Configuration / 5GS			NG.114 v1.0
7.5	MTSI MO Voice call without preconditions at	Rel-15	C28	UE supports NR and IMS voice over
ŀ	both originating UE and terminating UE /			NR and MTSI speech and
ŀ	5GS			preconditions and disabling
				preconditions and NG114 v1.0
7.6	Void	D 145	0.11	ND HAS I ND HATOL
7.6a	MTSI MT Voice Call with preconditions at	Rel-15	C44	NR and IMS voice over NR and MTSI
	both originating UE and terminating UE / Default Configuration / 5GS			Speech and preconditions and NG.114 v1.0
7.7	MTSI MT Voice Call without preconditions	Rel-15	C28	UE supports NR and IMS voice over
	at both originating UE and terminating UE /	1101 10	020	NR and MTSI speech and
	5GS			preconditions and disabling
				preconditions and NG114 v1.0
7.8	MTSI MT Voice Call without preconditions	Rel-15	C44	NR and IMS voice over NR and MTSI
	at originating UE and with preconditions at			Speech and preconditions and
	terminating UE / 5GS			NG.114 v1.0
7.9	MTSI MT Voice Call with preconditions at	Rel-15	C28	UE supports NR and IMS voice over
ŀ	originating UE and without preconditions at			NR and MTSI speech and
	terminating UE / 5GS			preconditions and disabling preconditions and NG114 v1.0
7.10	MTSI MT Voice call without preconditions	Rel-15	C28	UE supports NR and IMS voice over
7.10	and without SDP offer in MT INVITE / 5GS	IXEI-13	020	NR and MTSI speech and
ŀ	and without obt oner in twit inverte, ode			preconditions and disabling
				preconditions and NG114 v1.0
7.11	MTSI MT Voice call without preconditions at	Rel-15	C05	UE supports NR and IMS voice over
	terminating UE and originating UE requiring			NR and MTSI and MTSI speech and
	them / 5GS			(not preconditions or (preconditions
			_	and disabling preconditions))
7.12	MTSI MO Voice Call with preconditions at	Rel-15	C44	NR and IMS voice over NR and MTSI
	originating UE and without preconditions at			Speech and preconditions and
7.10	terminating UE / 5GS	Dol 45	C44	NG.114 v1.0
7.13	MTSI MT Voice Call with RTCP disabled / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and
	363			NG.114 v1.0
7.14	MTSI MO Video Call with preconditions at	Rel-15	C61	NR and IMS voice over NR and MTSI
	both originating and terminating UE / 5GS	1701-10	001	Speech and MTSI video and
	25 originating and torriniding of 7 500			preconditions and NG.114 v1.0
ŀ	·		i	

Clause	Title	Release	Applicability	Comments
7.15	MTSI MO Video call without preconditions at both originating UE and terminating UE / 5GS	Rel-15	C31	UE supports NR and IMS voice over NR and MTSI and MTSI speech and AMR-WB and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and initiating a session and preconditions and disabling preconditions and NG114 v1.0 and (EVS Configuration B0 or EVS Configuration A1)
7.16	MTSI MT Video call with preconditions at both originating UE and terminating UE / 5GS	Rel-15	C61	NR and IMS voice over NR and MTSI Speech and MTSI video and preconditions and NG.114 v1.0 NOTE 3
7.17	MTSI MT Video call without preconditions at both originating UE and terminating UE / 5GS	Rel-15	C33	UE supports NR and IMS voice over NR and MTSI and MTSI speech and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and preconditions and disabling preconditions and NG114 v1.0 and EVS Configuration B0
7.18	MTSI MO Voice Call / EVS / AMR-WB / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.19	MTSI MT Voice Call / EVS / AMR-WB IO mode / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.20	MTSI MO Voice Call / add video and remove video / with preconditions at both originating UE and terminating UE / 5GS	Rel-15	C61	NR and IMS voice over NR and MTSI Speech and MTSI video and preconditions and NG.114 v1.0 NOTE 3
7.21	MTSI MO Voice Call / add video and remove video / without preconditions at both originating UE and terminating UE / 5GS	Rel-15	C31	UE supports NR and IMS voice over NR and MTSI and MTSI speech and AMR-WB and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and initiating a session and preconditions and disabling preconditions and NG114 v1.0 and (EVS Configuration B0 or EVS Configuration A1)
7.22	MTSI MT Voice Call / add video and remove video / with preconditions at both originating UE and terminating UE / 5GS	Rel-15	C61	NR and IMS voice over NR and MTSI Speech and MTSI video and preconditions and NG.114 v1.0 NOTE 3
7.23	MTSI MT Voice Call / add video and remove video / without preconditions at both originating UE and terminating UE / 5GS	Rel-15	C33	UE supports NR and IMS voice over NR and MTSI and MTSI speech and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and preconditions and disabling preconditions and NG114 v1.0 and EVS Configuration B0
7.24	MTSI MT Voice Call / Forking / UE receives CANCEL request for a forked MT voice call / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.24a	MTSI MO Voice Call / Forking / UE receives two preliminary responses and one early dialog termination / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.24b	MTSI MO Voice Call / UE receives two preliminary responses and one final response / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.25	MTSI MT Voice call without SDP offer in INVITE / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.26	Mobile Originating CAT / Forking Model / MO Voice Call / 5GS	Rel-15	C17	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.27	Session Timer / MO Voice Call / UE is able to refresh the session / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.28	Session Timer / MO Voice Call / Remote end is refresher / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0

Clause	Title	Release	Applicability	Comments
7.29	Session Timer / MO Voice Call / Remote end does not support Session Timer / 5GS	Rel-15	C29	NR and IMS voice over NR and MTSI Speech and preconditions and Session Timer for own benefit and NG.114 v1.0
7.30	Session Timer / MO Voice Call / Remote end supports but does not use Session Timer / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.31	Session Timer / MT Voice Call / Remote end supports but does not send Session-Expires / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.32	Session Timer / MT Voice Call / Remote end sends Session-Expires but does not choose refresher / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
7.33	Session Timer / MT Voice Call / Remote end chooses UE as refresher / 5GS	Rel-15	C30	UE supports NR and IMS voice over NR and MTSI speech and preconditions and Session Timer and re-INVITE for session refresh and NG114 v1.0
7.34	Session Timer / MT Voice Call / Remote end does not support Session Timer / 5GS	Rel-15	C44	NR and IMS voice over NR and MTSI Speech and preconditions and NG.114 v1.0
8	Supplementary Services			
8.1	Originating Identification Presentation / Configuration / 5GS	Rel-15	C06	UE supports NR and (GBA or HTTP Digest) and MTSI and MTSI Originating Identification Presentation
8.2	Originating Identification Restriction / Configuration / 5GS	Rel-15	C45	UE supports NR and (GBA or HTTP Digest) and MTSI and MTSI Originating Identification Restriction - Configuration
8.3	Originating Identification Restriction / Signalling / 5GS	Rel-15	C46	UE supports NR and IMS voice over NR and MTSI Originating Identification Restriction and MTSI speech and preconditions and NG114 v1.0
8.4	Terminating Identification Presentation / Configuration / 5GS	Rel-15	C47	UE supports NR and (GBA or HTTP Digest) and MTSI and Terminating Identification Presentation
8.5	Terminating Identification Restriction / Configuration / 5GS	Rel-15	C48	UE supports NR and (GBA or HTTP Digest) and MTSI and Terminating Identification Restriction - Configuration
8.6	Terminating Identification Restriction / Signalling / 5GS	Rel-15	C49	UE supports NR and IMS voice over NR and Terminating Identification Restriction and MTSI speech and preconditions and NG114 v1.0
8.7	Communication Forwarding Unconditional / Configuration / 5GS	Rel-15	C50	UE supports NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
8.8	Communication Forwarding Unconditional / Signalling / 5GS	Rel-15	C53	UE supports NR and IMS voice over NR and Communication Diversion and MTSI speech and preconditions and NG114 v1.0
8.9	Communication Forwarding on Not Logged- in / Configuration / 5GS	Rel-15	C50	UE supports NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
8.11	Communication Forwarding on Busy / Configuration / 5GS	Rel-15	C50	UE supports NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
8.13	Communication Forwarding on Subscriber Not Reachable / Configuration / 5GS	Rel-15	C50	UE supports NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
8.15	Communication Forwarding on No Reply / Configuration / 5GS	Rel-15	C50	UE supports NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
8.17	Barring of All Incoming Calls / Configuration / 5GS	Rel-15	C51	UE supports NR and (GBA or HTTP Digest) and MTSI and Incoming Communication Barring
8.18	Barring of All Incoming Calls / except for a specific user / Configuration / 5GS	Rel-15	C07	UE supports NR and (GBA or HTTP Digest) and MTSI and Incoming Communication Barring
8.19	Barring of All Incoming Calls from anonymous users / Configuration / 5GS	Rel-15	C51	UE supports NR and (GBA or HTTP Digest) and MTSI and Incoming Communication Barring
8.21	Barring of all Outgoing Calls / Configuration / 5GS	Rel-15	C52	UE supports NR and (GBA or HTTP Digest) and MTSI and Outgoing Communication Barring

Clause	Title	Release	Applicability	Comments
8.22	Barring of Outgoing International Calls / Configuration / 5GS	Rel-15	C52	UE supports NR and (GBA or HTTP Digest) and MTSI and Outgoing Communication Barring
8.23	Barring of Outgoing International Calls / ex Home Country / Configuration / 5GS	Rel-15	C52	UE supports NR and (GBA or HTTP Digest) and MTSI and Outgoing Communication Barring
8.24	Barring of Outgoing International Calls / When Roaming / Configuration / 5GS	Rel-15	C52	UE supports NR and (GBA or HTTP Digest) and MTSI and Outgoing Communication Barring
8.25	Barring of Incoming Calls / When Roaming / Configuration / 5GS	Rel-15	C51	UE supports NR and (GBA or HTTP Digest) and MTSI and Incoming Communication Barring
8.26	MO Voice Call Hold without announcement / 5GS	Rel-15	C20	UE supports NR and IMS voice over NR and MTSI speech and MTSI Communication Hold and preconditions and NG114 v1.0
8.27	MO Video Call Hold without announcement / 5GS	Rel-15	C34	UE supports NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Communication Hold and preconditions and NG114 v1.0
8.28	MT Voice Call Hold without announcement / 5GS	Rel-15	C21	UE supports NR and IMS voice over NR and MTSI speech and MTSI Communication Hold and preconditions and NG114 v1.0
8.29	MT Video Call Hold without announcement / 5GS	Rel-15	C34	UE supports NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Communication Hold and initiating a session and preconditions and NG114 v1.0
8.30	Subscription to the MWI event package / 5GS	Rel-15	C22	UE supports NR and MTSI Message Waiting Indication
8.31	Creating and leaving a conference / 5GS	Rel-15	C23	UE supports NR and IMS voice over NR and MTSI speech and MTSI Conference and preconditions and NG114 v1.0
8.32	Inviting user to conference by sending a REFER request to the conference focus / 5GS	Rel-15	C23	UE supports NR and IMS voice over NR and MTSI speech and MTSI Conference and preconditions and NG114 v1.0
8.33	Inviting user to conference by sending a REFER request to the conference focus / Video / 5GS	Rel-15	C36	UE supports NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Conference and preconditions and NG114 v1.0
8.34	Three way session creation / Voice / 5GS	Rel-15	C24	UE supports NR and IMS voice over NR and MTSI speech and MTSI Conference and MTSI three way session and preconditions and NG114 v1.0
8.35	Three way session creation / Video / 5GS	Rel-15	C35	UE supports NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Conference and MTSI three way session and preconditions and NG114 v1.0
8.36	MO Voice Call Explicit Communication Transfer / Consultative Call Transfer / 5GS	Rel-15	C25	UE supports NR and IMS voice over NR and MTSI and MTSI speech and MTSI Explicit Communication Transfer - consultative transfer and preconditions and NG114 v1.0
8.37	Communication Waiting and answering the call / 5Gs	Rel-15	C26	UE supports NR and IMS voice over NR and MTSI and MTSI speech and MTSI Communication Waiting and preconditions and NG114 v1.0
8.38	Communication Waiting and cancelling the voice call / 5GS	Rel-15	C26	UE supports NR and IMS voice over NR and MTSI and MTSI speech and MTSI Communication Waiting and preconditions and NG114 v1.0
8.39	GBA Authentication / 5GS	Rel-15	C55	UE supports NR and GBA and MTSI Originating Identification Presentation
8.39a	HTTP Digest Authentication / 5GS	Rel-15	C56	UE supports NR and HTTP Digest and MTSI Originating Identification Presentation
8.40	User initiated USSI / 5GS	Rel-15	C37	UE supports NR and MTSI and MTSI speech and USSI and initiating a session

Clause	Title	Release	Applicability	Comments
8.41	Communication Forwarding on No Reply:MO Voice Call initiation with preconditions	Rel-15	C38	UE supports NR and IMS voice over NR and MTSI speech and MTSI Communication Diversion and preconditions and NG114 v1.0
9	SMS			
9.1	Mobile Originating SMS / 5GS	Rel-15	C08	UE supports NR and SM-over-IP sender and UE configured to use SMS over IP
9.2	Mobile Terminating SMS / 5GS	Rel-15	C09	UE supports NR and SM-over-IP receiver and UE configured to use SMS over IP
9.3	Mobile Originating Concatenated SMS / 5GS	Rel-15	C10	UE supports NR and concatenated SM-over-IP sender and UE configured to use SMS over IP
9.4	Mobile Terminating Concatenated SMS / 5GS	Rel-15	C11	UE supports NR and concatenated SM-over-IP receiver and UE configured to use SMS over IP
9.5	Mobile Originating SMS / RP-ERROR / 5GS	Rel-15	C08	UE supports NR and SM-over-IP sender and UE configured to use SMS over IP
10	Emergency Calls			
10.1	Emergency Call with emergency registration / Success / Location information available / 5GS	Rel-15	C12	UE supports NR and emergency services in NR connected to 5GCN and is capable of obtaining location information
10.2	Emergency Call with emergency registration / Success / Location information not available / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.3	Emergency call with emergency registration / Emergency SIP signalling and media in parallel with another ongoing IM CN subsystem signalling and media / 5GS	Rel-15	C40	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN and preconditions and Communication Hold during emergency call
10.4	Non-UE detectable emergency call / IM CN sends a 1xx response / UE geographical location information available or not / 5GS	Rel-15	C41	UE supports NR and MTSI and MTSI speech and preconditions and emergency services in NR connected to 5GCN
10.6	Non-UE detectable emergency call / IM CN sends 380 with an Alternative Service / Previous emergency IMS registration not expired / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.7	Void			
10.8	Void			
10.9	Emergency call without emergency registration / UE credentials are not accepted / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.10	Emergency call without emergency registration / Failure of registration / Rejected by 403 (Forbidden) / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.11	Void			
10.12	User-initiated emergency reregistration / UE has emergency related ongoing dialog / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.13	User-initiated emergency reregistration / User initiates an emergency call / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.14	In parallel emergency and non-emergency registrations / 5GS	Rel-15	C39	UE supports NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
10.15	Void			
11	eCall over IMS			
11.1	eCall over IMS / Manual initiation / Normal registration / Emergency registration / Success / 200 OK with ACK / 5GS	Rel-16	C42	UE supports MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Manual type of eCall (NOTE 2)
11.2	eCall over IMS / Automatic initiation / Normal registration / Emergency registration / Success / 200 OK with ACK / 5GS	Rel-16	C43	UE supports MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Automatic type of eCall (NOTE 2)
11.4	eCall over IMS / Manual initiation / MSD transfer and 200 OK with ACK / SIP INFO for MSD Update / Success / 5GS	Rel-16	C42	UE supports MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Manual type of eCall (NOTE 2)

Clause	Title	Release	Applicability	Comments
11.5	eCall over IMS / Automatic initiation / MSD transfer and 200 OK with ACK / SIP INFO request for MSD Update / Success / 5GS	Rel-16	C43	UE supports and MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Automatic type of eCall (NOTE 2)
11.6	eCall over IMS / Automatic initiation / MSD transfer and 200 OK with ACK / SIP INFO request for unsupported MSD / UE indicates unsuccessful in SIP INFO / 5GS	Rel-16	C43	UE supports and MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Automatic type of eCall (NOTE 2)

NOTE 1: If any one of the other Registration test cases 6.2 until 6.9 is executed, this test case is optional.

NOTE 2: This test case can optionally be executed against Rel-15 UEs.

NOTE 3: As an exception to NG.114 support of MTSI Video Call is optional.

Table 4.2a: Applicability Conditions for TS 34.229-5 tests

Condition	Test Case Selection Expression	Comment
C01	IF A.18/5 THEN R ELSE N/A	NR
C02	Void	
C03	Void	
C04	Void	
C05	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.3A/50 AND A.15/1 AND (NOT A.4/16 OR (A.4/16 AND A.12/59)) THEN R ELSE N/A	NR and IMS voice over NR and MTSI and MTSI speech and (not preconditions or (preconditions and disabling preconditions))
C06	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/1 THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and MTSI Originating Identification Presentation
C07	IF A.18/5 AND A.3A/50 AND A.16/7 AND A.6a/3 THEN R ELSE N/A	NR and MTSI and MTSI Communication Barring and GBA for XCAP authentication
C08	IF A.18/5 AND A.3A/61 AND [73] A.4.4-2/32 THEN R ELSE N/A	NR and SM-over-IP sender and UE configured to use SMS over IP
C09	IF A.18/5 AND A.3A/62 AND [73] A.4.4-2/32 THEN R ELSE N/A	NR and SM-over-IP receiver and UE configured to use SMS over IP
C10	IF A.18/5 AND A.3A/64 AND [73] A.4.4-2/32 THEN R ELSE N/A	NR and concatenated SM-over-IP sender and UE configured to use SMS over IP
C11	IF A.18/5 AND A.3A/65 AND [73] A.4.4-2/32 THEN R ELSE N/A	NR and concatenated SM-over-IP receiver and UE configured to use SMS over IP
C12	IF A.18/5 AND [93] A.4.3.7-1/14 AND A.12/27 THEN R ELSE N/A	NR and emergency services in NR connected to 5GCN and is capable of obtaining location information
C13	IF A.18/5 AND A.12/39 THEN R ELSE N/A	NR and IMS de-registration
C14	Void	9
C15	IF A.18/5 AND A.12/58 THEN R ELSE N/A	NR and Enabling/Disabling SMS over IMS
C16	Void	
C17	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.4/16 AND A.12/45 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI Speech and preconditions and early media and NG.114 v1.0
C18	Void	
C19	Void	
C20	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.16/6 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI Communication Hold and preconditions and NG114 v1.0
C21	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.16/6 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR MTSI speech and MTSI Communication Hold and preconditions and NG114 v1.0
C22	IF A.18/5 AND A.16/8 THEN R ELSE N/A	NR and MTSI Message Waiting Indication
C23	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.16/9 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI Conference and preconditions and NG114 v1.0
C24	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.16/9 AND A.16/14 AND A.4/16 AND A.21/1 AND (A.22/15 OR A.22/18) THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI Conference and MTSI three way session and preconditions and NG114 v1.0
C25	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.3A/50 AND A.15/1 AND A.16/11 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI and MTSI speech and MTSI Explicit Communication Transfer - consultative transfer and preconditions and NG114 v1.0
C26	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.3A/50 AND A.15/1 AND A.16/13 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI and MTSI speech and MTSI Communication Waiting and preconditions and NG114 v1.0
C27	Void	
C28	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.4/16 AND A.12/59 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and preconditions and disabling preconditions and NG114 v1.0
C29	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.4/16 AND A.12/60 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI Speech and preconditions and Session Timer for own benefit and NG.114 v1.0

C30	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.4/16 AND A.12/57 AND A.12/61 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and preconditions and
		Session Timer and re-INVITE for session refresh and NG114 v1.0
C31	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.3A/50 AND A.15/1 AND A.15/2 AND A.15/10 AND A.15/3 AND A.15/11 AND A.15/12 AND A.15/13 AND A.4/2B AND A.4/16 AND A.12/59 AND A.21/1 AND (A.22/15 OR A.22/18) THEN R ELSE N/A	NR and IMS voice over NR and MTSI and MTSI speech and AMR-WB and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and initiating a session and preconditions and disabling preconditions and NG114 v1.0 and (EVS Configuration B0 or EVS Configuration A1)
C32	Void	ND and IMC using a year ND and MTCI
C33	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.3A/50 AND A.15/1 AND A.15/10 AND A.15/3 AND A.15/11 AND A.15/12 AND A.15/13 AND A.4/16 AND A.12/59 AND A.21/1 AND A.22/15 THEN R ELSE N/A	NR and IMS voice over NR and MTSI and MTSI speech and EVS and MTSI video and MTSI video H.265 MP MT Level 3.1 and MTSI video H.264 CHP Level 3.1 and H.264 CBP Level 3.1 and preconditions and disabling preconditions and NG114 v1.0 and EVS Configuration B0
C34	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.15/3 AND A.16/6 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Communication Hold and preconditions and NG114 v1.0
C35	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.15/3 AND A.16/9 AND A.16/14 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Conference and MTSI three way session and preconditions and NG114 v1.0
C36	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.15/3 AND A.16/9 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI video and MTSI Conference and preconditions and NG114 v1.0
C37	IF A.18/5 AND A.3A/50 AND A.15/1 AND A.16/19 AND A.4/2B THEN R ELSE N/A	NR and MTSI and MTSI speech and USSI and initiating a session
C38	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.16/5 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI Communication Diversion and preconditions and NG114 v1.0
C39	IF A.18/5 AND A.3A/50 AND A.15/1 AND [93] A.4.3.7-1/14 THEN R ELSE N/A	NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN
C40	IF A.18/5 AND A.3A/50 AND A.15/1 AND [93] A.4.3.7-1/14 AND A.4/16 AND A.12/33 THEN R ELSE N/A	NR and MTSI and MTSI speech and emergency services in NR connected to 5GCN and preconditions and Communication Hold during emergency call
C41	IF A.18/5 AND A.3A/50 AND A.15/1 AND A.4/16 AND [93] A.4.3.7-1/14 THEN R ELSE N/A	NR and MTSI and MTSI speech and preconditions and emergency services in NR connected to 5GCN
C42	IF A.3A/50 AND A.15/1 AND A.12/63 AND [3] A.10/16 THEN R ELSE N/A	MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Manual type of eCall
C43	IF A.3A/50 AND A.15/1 AND A.12/63 AND [3] A.10/17 THEN R ELSE N/A	MTSI and MTSI speech and IMS eCall type of emergency services over 5GS and Automatic type of eCall
C44	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and preconditions and NG.114 v1.0
C45	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/2A THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Originating Identification Restriction - Configuration
C46	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.16/2 AND A.15/1 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI Originating Identification Restriction and MTSI speech and preconditions and NG114 v1.0
C47	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/3 THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Terminating Identification Presentation
C48	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/4A THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Terminating Identification Restriction - Configuration

C49	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.16/4 AND A.15/1 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and Terminating Identification Restriction and MTSI speech and preconditions and NG114 v1.0
C50	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/5 THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Communication Diversion
C51	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/7 THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Incoming Communication Barring
C52	IF A.18/5 AND (A.6a/3 OR A.6a/4) AND A.3A/50 AND A.16/15 THEN R ELSE N/A	NR and (GBA or HTTP Digest) and MTSI and Outgoing Communication Barring
C53	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.16/5 AND A.15/1 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NRand Communication Diversion and MTSI speech and preconditions and NG114 v1.0
C54	Void	
C55	IF A.18/5 AND A.6a/3 AND A.16/1 THEN R ELSE N/A	NR and GBA and MTSI Originating Identification Presentation
C56	IF A.18/5 AND A.6a/4 AND A.16/1 THEN R ELSE N/A	NR and Digest and MTSI Originating Identification Presentation
C57	Void	
C58	Void	
C59	Void	
C60	Void	
C61	IF A.18/5 AND [93] A.4.3.7-1/32 AND A.15/1 AND A.15/3 AND A.4/16 AND A.21/1 THEN R ELSE N/A	NR and IMS voice over NR and MTSI speech and MTSI video and preconditions and NG.114 v1.0

Annex A (normative): ICS proforma for 3rd Generation User Equipment supporting IP multimedia call control based on SIP and SDP

Notwithstanding the provisions of the copyright related to the text of the present document, The Organizational Partners of 3GPP grant that users of the present document may freely reproduce the ICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed ICS.

A.1 Guidance for completing the ICS proforma

A.1.1 Purposes and structure

The purpose of this ICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in relevant specifications may provide information about the implementation in a standardised manner.

The ICS proforma is subdivided into clauses for the following categories of information:

- instructions for completing the ICS proforma;
- identification of the implementation;
- identification of the protocol;
- ICS proforma tables (for example: UE roles specific to additional capabilities, Major capabilities etc).

A.1.2 Abbreviations and conventions

This annex does not reflect dynamic conformance requirements but static ones. In particular, a condition for support of a PDU parameter does not reflect requirements about the syntax of the PDU (i.e. the presence of a parameter) but the capability of the implementation to support the parameter.

In the sending direction, the support of a parameter means that the implementation is able to send this parameter (but it does not mean that the implementation always sends it).

In the receiving direction, it means that the implementation supports the whole semantic of the parameter that is described in the main part of this specification.

As a consequence, PDU parameter tables in this annex are not the same as the tables describing the syntax of a PDU in the reference specification, e.g. RFC 3261 [15] tables 2 and 3. It is not rare to see a parameter which is optional in the syntax but mandatory in subclause below.

The ICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [8].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Reference column

The reference column gives reference to the relevant 3GPP core specifications and optional IMS profile documents (e.g. GSMA PRD IR.92).

Status column

The various statii used in this annex are in accordance with the rules in table A.1. The status column can also be used for IMS profile documents.

Table A.1: Key to status codes

Status code	Status name	Meaning
m	mandatory	the capability shall be supported. It is a static view of the fact that the conformance requirements related to the capability in the reference specification are mandatory requirements. This does not mean that a given behaviour shall always be observed (this would be a dynamic view), but that it shall be observed when the implementation is placed in conditions where the conformance requirements from the reference specification compel it to do so. For instance, if the support for a parameter in a sent PDU is mandatory, it does not mean that it shall always be present, but that it shall be present according to the description of the behaviour in the reference specification (dynamic conformance requirement).
0	optional	the capability may or may not be supported. It is an implementation choice.
n/a	not applicable	it is impossible to use the capability.
Х	prohibited (excluded)	It is not allowed to use the capability. This is more common for a profile.
c <integer></integer>	conditional	the requirement on the capability ("m", "o", "n/a" or "x") depends on the support of other optional or conditional items. <integer> is the identifier of the conditional expression.</integer>
o. <integer></integer>	qualified optional	for mutually exclusive or selectable options from a set. <integer> is the identifier of the group of options, and the logic of selection of the options.</integer>

Release column

The release column indicates the earliest release from which the capability or option is relevant.

Mnemonic column

The Mnemonic column contains mnemonic identifiers for each item.

Comments column

This column is left blank for particular use by the reader of the present document.

References to items

For each possible item answer (answer in the support column) within the ICS proforma there exists a unique reference, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table.

EXAMPLE: A.5/4 is the reference to the answer of item 4 in table A.5.

A.1.3 Instructions for completing the ICS proforma

The supplier of the implementation may complete the ICS proforma in each of the spaces provided. More detailed instructions are given at the beginning of the different clauses of the ICS proforma.

A.2 Identification of the User Equipment

Identification of the User Equipment should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

A.2.1	Date of the statement
A.2.2 UEUT name	User Equipment Under Test (UEUT) identification
Hardware co	onfiguration:
Software co	nfiguration:
A.2.3 Name:	Product supplier
Address:	
Telephone n	umber:
Facsimile nu	ımber:
E-mail addre	ess:
Additional is	nformation:
A.2.4 Name:	Client

Address:		
Telephone number:		
Facsimile number:		
E-mail address:		
Additional information:		
A.2.5 ICS contact person		
Name:	 	
Telephone number:	 	
Facsimile number:	 	
E-mail address:		
Additional information:		

A.3 Identification of the protocol

This ICS proforma applies to the 3GPP standards listed in the normative references clause of the present document.

A.4 ICS proforma tables

NOTE: Tables A.2, A. 3A and A. 4 have been based on tables with the same number in TS 24.229 [10]. In order to facilitate traceability, table and item numbers are the same as those in the corresponding tables in TS 24.229 [10].

A.4.1 Roles

Table A.2: Roles

Item	UE roles	Ref.	Status	Release	Commen ts
1	User agent	24.229 [10], A.1.3 RFC 3261 [15]	m	Rel-5	

Table A.3A: UE roles specific to additional capabilities

Item	UE roles	Ref.	Status	Release	Mnemonic	Comments
50	Multimedia telephony service participant	24.173 [55]	0	Rel-8	pc_MultimediaT elephonyService	
		IR.92 [83], 2.2.1	m	1	, ,	
		NG.114 [96]	m	Rel-15		
61	SM-over-IP sender	24.341 [66]	0	Rel-8	pc_SMS_IP_MO	
		IR.92 [83], 2.5	m]		
		NG.114 [96]	m NOTE 1	Rel-15		
62	SM-over-IP receiver	24.341 [66]	0	Rel-8	pc_SMS_IP_MT	
		IR.92 [83], 2.5	m]		
		NG.114 [96]	m NOTE 1	Rel-15		
63	Void					
64	Concatenated SM-over- IP sender	23.040 [94], 9.2.3.24.1	0	Rel-8	pc_Concatenate d_SMS_IP_MO	
65	Concatenated SM-over- IP receiver	23.040 [94], 9.2.3.24.1	0	Rel-8	pc_Concatenate d_SMS_IP_MT	

NOTE 1: As an exception to NG.114 support of SM-over-IP sender/Receiver is optional for RedCap devices with form factor limitation making it impossible to support these services.

A.4.2 ICS related to SIP

A.4.2.1 Major capabilities

Prerequisite: A.2/1 - - user agent role.

Table A.4: Major capabilities

Item	Does the implementation support	Ref.	Status	Release	Mnemonic	Comment s
	Capabilities within main protocol					3
2B	initiating a session?	24.229 [10], A.2.1.2; RFC 3261 [15], 13	0	Rel-5	pc_Initiate Session	
2C	initiating a session which require local and/or remote resource reservation?	24.229 [10], A.2.1.2; RFC 3262 [27] UE is capable of obtaining location information	c43	Rel-8		
	Extensions					
16	integration of resource management and SIP? (use of preconditions)	24.229 [10], A.2.1.2; RFC 3312 [26]	C44	Rel-8	pc_Precon ditions	
		IR.92 [83], 2.4.1	m			
		NG.114 [96], 2.3.5	m	Rel-15		
53	obtaining and using GRUUs in the Session Initiation Protocol (SIP)	24.229 [10], A.2.1.2	m (Note 1)	Rel-7	pc_IMS_G RUUsInSI P	
	Conditions/Options		· ·	1	•	
c43:	IF A.4/2B THEN o ELSE n/a initiat	ing sessions.				

IF A.4/2C THEN m ELSE o - - initiating a session which require local and/or remote resource reservation.

NOTE 1: If a UE is unable to become engaged in a service that potentially requires the ability to identify and interact with a specific UE even when multiple UEs share the same single Public User Identity then the UE support can be " o" instead of "m". Examples include telemetry applications, where point-to-point communication is desired between two users.

A.4.2.2 Void

A.4.2.3 Security

Table A.6a: Security scheme

Item	Security scheme	Reference	Status	Release	Mnemoni	Commer			
					С	S			
1	GIBA	24.229 [10]	0.1	Rel-8	pc_IMS_G				
					IBA_Sec				
2	IMS security (IMS AKA plus IPsec	24.229 [10]	0.1	Rel-8	pc_IMS_S				
	ESP)				ec				
			m	Rel-15					
3	GBA for XCAP authentication	33.220 [82] 4.5; 33.222	0.2	Rel-8	pc_HttpG				
		[63]; 24.109 [64]			BAAuthent				
					ication				
4	HTTP Digest for XCAP authentication	RFC 2617 [65]	0.2	Rel-8	pc_HttpDi				
					gestAuthe				
					ntication				
5	SIP Digest without TLS	33.203 [12]	0.3	Rel-8	pc_SIP_Di				
					gest				
6	SIP Digest with TLS	33.203 [12]	0.3	Rel-8	pc_SIP_Di				
					gest_TLS				
7	NASS-IMS-bundled authentication	33.203 [12]	0.3	Rel-8	pc_NASS				
					_IMS				
	Conditions/Options		•						
0.1	At least one of these options has to be	supported if A.18/1 or A18/4	•						
0.2	At least one of these options has to be	supported if the UE supports	XCAP						
0.3	At least one of these options has to be supported if A.18/3								

NOTE: Support of GPRS-IMS-Bundled authentication (GIBA) is considered as an interim security solution for IMS security (mandatory requirement as specified in TS 24.229 [10]). IMS security refer to IMS AKA plus IPsec ESP as specified in TS 24.229 [10].

A.4.2.4 Addressing

Table A.7: IP address format

Item	IP address format	Ref.	Status	Release	Mnemonic	Comments				
1	IPv4	23.221 [13], 5.1	0	Rel-5	pc_IPv4					
2	IPv6	23.221 [13], 5.1	m	Rel-5	pc_IPv6					
NOTE 1: Fo										

A.4.2.5 SIP Compression

Table A.8: SIP Compression

Item		Ref.	Status	Release	Mnemonic	Comments
1	Void					
2	Void					
3	Void					
4	Void					
5	Indicate the willingness to receive the responses and requests compressed from initial REGISTER onwards by using the " comp=sigcomp" parameter	24.229 [10], 8.1.1	0	Rel-5	pc_IndicateS igcomp	

- A.4.3 Void
- A.4.4 Void
- A.4.5 Additional information

Table A.12: Additional information

Item	Additional information	Reference	Status	Release	Mnemonic	Comments
1	Void					
2	Void					
3	Void UE capable of being	24.229 [10],	0	Rel-5	pc_InitiatesDedicatedPDPCo	
4	configured to initiate	9.2.1	U		ntext	
	Dedicated PDP Context					
5	UE capable of being	24.229 [10],	0	Rel-5	pc_InitiateP_CSCFDiscovery	
	configured to initiate P-	9.2.1			_viaPCO	
<u> </u>	CSCF discovery via PCO					
7	Void UE capable of being	24 220 [40]		Dol E	no Initiato P. CCC Piacovaria	
/	configured to initiate P-	24.229 [10], 9.2.1	0	Rel-5	pc_InitiateP_CSCFDiscovery viaDHCPv6	
	CSCF discovery via	3.2.1			_viabilioi vo	
	DHCPv6					
8	UE supports P-CSCF	24.229 [10],	0	Rel-5	pc_P_CSCFDiscovery_viaP	
	discovery via PCO	9.2.1			CO	
9	Void	0.4.000.5403		5.15	D 0005D:	
10	UE supports P-CSCF discovery via DHCPv6	24.229 [10], 9.2.1	0	Rel-5	pc_P_CSCFDiscovery_viaD HCPv6	
11	Void	J. Z. I			I IOI VU	
12		24.229 [10],	0	Rel-5	pc_BidirecVoiceOverIMS	
'-	bidirectional voice session			1.0.0		
	over IMS					
13	Void					
14	Void					
15	Void UE Supports " IPv6	22 004 [40]		Dalo		
16	address with embedded	23.981 [18], 5.2.1	0	Rel-6		
	IPv4 address" in PCO IE	0.2.1				
17	UE Supports IPv4	23.981 [18],	0	Rel-6		
	address in PCO IE	5.2.1				
18	Void					
19	UE supports UI capable of		0	Rel-7		
	showing user notification for Message Waiting	Annex F				
	Indication					
20	Void					
21	Void					
22	Void					
23	Void					
24	UE supports no reply	24.604 [68],	0	Rel-8		
	timer setting	4.9.1.4 IR.92 [83],		-		
		1R.92 [83], 2.3.8	m			
25	UE supports sending	26.114 [56],	0	Rel-7		
	DTMF events over RTP	Annex G]		
		IR.92 [83], 3.3	m			
		NG.114 [96]	m	Rel-15		
26	Void					
27	UE is capable of obtain	24.229 [10]	0	Rel-9	pc_IMS_Geolocation	
	ing location information	4.7, 36.509				
		[79] 4.1, 5.5.2, 34.109 [78]				
		5.4.2				
28	Void					
29	UE supports emergency	C.S0005-E	0		pc_CS_Em_Call_in_1xRTT	
	speech call over 1xRTT	[74]				
30	Void	0.4.000.7.4.03		D 10		
31	UE supports end-to- access-edge media	24.229 [10], 4.2.B.2	0	Rel-9		
	security using SDES	7.C.D.C				
	locounty doing ODLO	I		i	1	

UE supports video media 24,222 10 ,							
feature tag	32	UE supports video media		0	Rel-13	pc_IMS_Video_FeatureTag	
Result R		feature tag					
NG.114 (96)							
NOTE 1 NOTE 1 STATE NOTE 1 STATE S			IR.94 [75], 2.2	m			
NOTE 1 N			NG.114 [96]	m	Rel-15		
33 UE supports				NOTE 1			
Communication Hold during emergency call during	33	UE supports	23.167 [76],		Rel-9	pc CommunicationHold Duri	
during emergency call 34 UE indicates 24.237 [77], 0 12.23B.1 0							
34 UE indicates Q.3.3pp. srvco-alerting media feature tag in INVITE request or 180 (Ringling) response 24.237 [77] 0 Rel-12 pc_BSRVCC						···g=····g····j····	
Sapp.srvcc-alerting media feature tag in INVTE request or 180 (Ringing) response 24.237 [77] 0 Rel-12 pc_BSRVCC	34		24.237 [77].	0	Rel-10	pc IMS SRVCCAlert	
media feature tag in NVTE request or 180 (Ringing) response 35 Void 36 UE indicates 42 237 77					. 10. 10		
INVITE request or 180 (Ringing) response			12.2.05.1				
(Ringing) response							
36							
36 UE indicates Gazaria Gaza	35						
g 3gpp.ps2cs=srvcc-orig- pre-alerting media feature tag in INVITE request UE indicates OMA-TS- XDM_MO-V1_1- 20080627-A.doc, section 5.2.8 "Node: /xxx/ AAUTHNAME" is configured 38			24 237 [77]	0	Ral-12	nc BSRVCC	
pre-alerting media feature tag in INVITE request 37 UE indicates OMA-TS- XDM_MO-V1_1- 20080627-A_doc, section 5.2.8 "Node: \(\text{-X} \) ANUTHNAME" is configured S.2.8 "Node: \(\text{-X} \) ANUTHNAME S	30				1161-12	pc_bottvee	
tag in INVITE request Annex Role Annex B.2 Annex B.2 Service Associated Annex B.2 Anne			UA.Z.Z.Z				
37		tog in INIVITE request					
XDM_MC-V1_1- 2080627-A.doc, section 5.2.8 "Node: /cX:/ AAUTHNAME" is configured 38 The UE use the default public user identity received in P-Associated - URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 24.623 [81]	27		24 623 [81]	0	Rol₋2	nc XCAP HeernameleConfi	
20080627-A.doc, section 5.2.8 "Node: /-X-x/ AUTHNAME" is configured IR.92 [83] m pc_XCAP_XUIisDefaultPubli cUser identity received in P-Associated URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 24.623 [81] o Rel-8 pc_IMS_Deregistration support IMS deregistration 5.1.1.6 24.229 [10], o Rel-11 pc_IMS_CS_PS_SRVCC SRVCC 6.2.3 Rel-11 pc_IMS_CS_PS_SRVCC SRVCC G.2.3 Rel-11 pc_IMS_CS_PS_SRVCC SRVCC G.2.3 Rel-11 pc_IMS_CS_PS_SRVCC G.2.3 Rel-11 pc_IMS_CS_PS_SRVCCMid pc_IMS_CS_PS_S	31				1/61-0		
38 The UE use the default public user identity received in P-Associated - URI header in 20 OK for REGISTER as XCAP User Identity (XUI) 39 UE has the method that support IMS deregistration 5.1.1.6 40 UE supports Cs to PS SRVCC 6.2.3 41 UE supports Cs to PS SRVCC in Identity state 4.2237 [77], but in Identity is support IMS deregistration 5.2.3 42 UE supports Cs to PS SRVCC in Identity State 6.2.3 43 Void Call UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void Void Void State S			ATTITION D.Z			gureumor	
AAUTHNAME' is configured 38 The UE use the default public user identity received in P-Associated-URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 39 UE has the method that support IMS deregistration 5.1.1.6 40 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCC SRVCC 6.2.3 41 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCCAler tsupports Cs to PS SRVCC for alerting state 6.2.3 42 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCCAler tsupports Cs to PS SRVCC for alerting state 6.2.3 42 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCCMid Call leature 43 Void 44 Void 45 UE supports early media 24.229 [10], o Rel-8 pc_EarlyMedia 46 UE indicates 2.33pp.accesstype media leature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN FIRST [84], 4.6 o Rel-11 pc_WLAN_XCAP_without_P If PICS is true, Wi-Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access On the Pics of the present specification, a UE supporting fixed broadband, A.183, shall set this PICS Sala Sala Set this PICS Sala Sala Set this PICS SRVC Cand the MSC 24.237 [77], c 1 Rel-11 pc_WLAN_XCAP_without_P In the context of the present specification, a UE supporting fixed broadband, A.183, shall set this PICS							
Configured IR.92 [83] The UE use the default public user identity received in P-Associated - URI header in 200 Kt for REGISTER as XCAP User Identity (XUI) 24.623 [81] O Rel-8 Rel-8 Rel-11							
The ÜE use the default public user identity proceived in P-Associated - URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 24.623 [81]							
public user identity received in P-Associated URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 24.623 [81]	20		ID 03 [03]			DO YCAR VIIIIo Dofovit Divisi	
received in P-Associated - URI header in 200 OK for REGISTER as XCAP User Identity (XUI) 24.623 [81]	38		IK.92 [83]	ın			
URI header in 200 CK for REGISTER as XCAP User Identity (XUI) 24.623 [81] 0 Rel-8						coseria	
REGISTER as XCAP User Identity (XUI) 24.623 [81] 39 UE has the method that support IMS deregistration 5.1.1.6 40 UE supports Cs to PS SRVCC 6.2.3 41 UE supports Cs to PS SRVCC 6.2.3 42 UE supports Cs to PS SRVCC in alerting state 6.2.3 42 UE supports Cs to PS SRVCC in alerting state 6.2.3 42 UE supports Cs to PS SRVCC and the MSC server assisted mid-call feature 43 Void							
User Identity (XUI) 24.623 [81] 0 Rel-8 support IMS deregistration 5.1.1.6 40 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCC 6.2.3 41 UE supports Cs to PS 24.237 [77], o Rel-11 pc_IMS_CS_PS_SRVCCAler to alerting state 6.2.3 42 UE supports Cs to PS SRVCC and the MSC server assisted mid-call feature 43 Void 44 Void 45 UE supports early media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access The UE uses XCAP in fixed broadband access 60 Rel-12 pc_IMS_CS_PS_SRVCC in Rel-11 pc_IMS_CS_PS_SRVCCMid Call 70 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 71 Pc_IMS_CS_PS_SRVCCMid Call 72 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 73 Pc_IMS_CS_PS_SRVCCMid Call 74 Poid 75 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 76 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 76 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 77 Pc_IMS_CS_PS_SRVCCMid Call 78 Pc_IMS_CS_PS_SRVCCMid Call 78 Pc_IMS_CS_PS_SRVCCMid Call 79 Call 70 Pc_IMS_CS_PS_SRVCCMid Call 71 Pc_IMS_CS_PS_SRVCCMid Call 72 Pc_IMS_CS_PS_SRVCCMid Call 73 Pc_IMS_CS_PS_SRVCCMid Call 74 Pc_IMS_CS_PS_SRVCCMid Call 75 Pc_IMS_CS_PS_SRVCCMid Call 76 Pc_IMS_CS_PS_SRVCCMide Call 76 Pc_IMS_CS_PS_SRVCCMid Call 76 Pc_IMS_CS_PS_SRVCCMide Call 76 Pc_IMS_CS_PS_IMS_CO_PS_IMS_CO_PS_IMS_CALL 76 Pc_IMS_CS_PS_IMS_CO_PS_IMS_CALL 76 Pc_IM							
24.623 [81]							
UE has the method that support IMS deregistration 24.229 [10], 5.1.1.6		User Identity (XUI)					
support IMS deregistration 5.1.1.6							
40 UE supports Cs to PS SRVCC 6.2.3 41 UE supports Cs to PS SRVCC in alerting state 6.2.3 42 UE supports Cs to PS SRVCC and the MSC Server assisted mid-call feature 4.3 Void 44 Void 45 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 6.2.3 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 6.2.3 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 6.2.3 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 6.2.3 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 6.2.4.237 [77], c1 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 70 Rel-11 pc_IMS_CS_PS_SRVCCMid Call 80 Rel-11 pc_IMS_CS_PS_INCOMId 80 Rel-11 pc_IMS_CS_PS_	39			0	Rel-5	pc_IMS_Deregistration	
SRVCC in alerting state 6.2.3 24.237 [77], 6.2.3 c							
41 UE supports Cs to PS SRVCC in alerting state 6.2.3 42 UE supports Cs to PS SRVCC and the MSC Server assisted mid-call feature 43 Void 44 Void 5.1.3 45 UE supports early media feature 45 UE supports early media feature 47 Void 5.1.3 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN 48 Void 50 The UE uses XCAP in fixed broadband access 40 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in fixed broadband acces 50 The UE uses XCAP in	40			0	Rel-11	pc_IMS_CS_PS_SRVCC	
SRVCC in alerting state 6.2.3 t t 42 UE supports Cs to PS SRVCC and the MSC server assisted mid-call feature 43 Void 44 Void 45 UE supports early media feature 45 UE supports early media 5.1.3 24.229 [10], 5.1.3 24.237 [77], 6.2.2 6.2.2 6.2.2 6.2.2 7.1 Rel-11 Pc_EarlyMedia 6.2.2 6.2.2 7.1 Rel-11 Pc_WLAN_XCAP_without_P If PICS is true, Wi-Fi access without PDN connection in WLAN 8. Void 8. Void 9. Rel-11 Pc_WLAN_XCAP_without_P If is access without PDN connection applies. Otherwise, EPC-integrated WLAN applies In the context of the present specification, a UE supporting fixed broadband access 8. Rel-12 Pc_fixed_broadband_XCAP In the Context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
42 UE supports Cs to PS SRVCC and the MSC server assisted mid-call feature 43 Void 44 Void 45 UE supports early media 5.1.3 46 UE indicates g.agpp. accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN 50 The UE uses XCAP in fixed broadband access 51 The UE uses XCAP in fixed broadband access 62 L2.37 [77], contend to the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	41			0	Rel-11	pc_IMS_CS_PS_SRVCCAler	
SRVCC and the MSC server assisted mid-call feature 43 Void 44 Void 45 UE supports early media 46 UE indicates g. 3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 6.2.3 Call		SRVCC in alerting state				t	
server assisted mid-call feature 43 Void 44 Void 45 UE supports early media 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN 10 UR indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN 10 Rel-11 pc_WLAN_XCAP_without_P If PICS is true, Wi-Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access 10 Rel-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	42			0	Rel-11	· – – – –	
feature 43 Void 44 Void 45 UE supports early media 5.1.3 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access The UE uses XCAP in fixed broadband access 624.229 [10], o Rel-8 pc_EarlyMedia 71 Rel-11 824.237 [77], c1 Rel-11 824.237 [77], 6.2.2 88 Pc_EarlyMedia 71 Rel-11 88 Pc_EarlyMedia 724.237 [77], c1 Rel-11 88 Pc_H-11 90 Rel-11 90 Rel-11 90 Pc_WLAN_XCAP_without_P If PICS is true, Wi-Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 10 Rel-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS			6.2.3			Call	
43 Void 44 Void 45 UE supports early media 24.229 [10], 0 Rel-8 pc_EarlyMedia 5.1.3 6.2.2 6.2.2 6.2.2 Rel-11 6.2.2 Rel-11 9.2 Manual Point (Manual Point of the present specification, a UE supporting fixed broadband, A:18/3, shall set this PICS Pc_EarlyMedia 7.1.3 7.							
44 Void 45 UE supports early media 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access The UE uses XCAP in fixed broadband access 48 Void 49 The UE uses XCAP in fixed broadband access The UE uses XCAP in fixed broadband access 49 The UE uses XCAP in fixed broadband access 40 Rel-11 pc_WLAN_XCAP_without_P DN connection applies. 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access							
45 UE supports early media 24.229 [10], 5.1.3 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN IR.51 [84], 4.6 The UE uses XCAP in fixed broadband access OREI-12 pc_fixed_broadband_XCAP In the Context of the present specification, a UE supports early media 24.229 [10], 5.1.3 C1 Rel-11 Rel-11 Pc_WLAN_XCAP_without_P If PICS is true, Wi- Fi access without PDN connection applies. Otherwise, EPC- integrated WLAN applies In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	43						
5.1.3 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access Final Description of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	44	Void					
5.1.3 46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access Final Description of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	45	UE supports early media	24.229 [10],	0	Rel-8	pc_EarlyMedia	
46 UE indicates g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN IR.51 [84], 4.6 The UE uses XCAP in fixed broadband access OREI-12 Pc_fixed_broadband_XCAP IR to the indicates g.3gpp.accesstype media feature tag in REGISTER Rel-11 Rel-11 Pc_WLAN_XCAP_without_P DN If PICS is true, Wi- Fi access without PDN connection applies. Otherwise, EPC- integrated WLAN applies In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS		'' '				Ţ	
g.3gpp.accesstype media feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access OREI-12 Pc_fixed_broadband_XCAP No ReI-12 Pc_fixed_broadband_XCAP If PICS is true, Wi-Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies No ReI-12 Pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	46	UE indicates		c1	Rel-11		
Feature tag in REGISTER 47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN IR.51 [84], 4.6 0 Rel-11 pc_WLAN_XCAP_without_P DN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access 0 Rel-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband, A.18/3, shall set this PICS 10 Note that the process of the present specification is processed broadband.							
47 Void 48 Void 49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access 49 The UE uses XCAP in fixed broadband access 40 Rel-11 pc_WLAN_XCAP_without_P is access without PDN connection applies. Otherwise, EPC-integrated WLAN applies 50 The UE uses XCAP in fixed broadband access 40 Rel-12 pc_fixed_broadband_XCAP in the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
48 Void 49 The UE uses XCAP without PDN connection in WLAN 40 WLAN 41 The UE uses XCAP without PDN connection in WLAN 42 The UE uses XCAP in fixed broadband access 43 The UE uses XCAP in fixed broadband access 44 The UE uses XCAP in fixed broadband access 45 The UE uses XCAP in fixed broadband access 46 The UE uses XCAP in fixed broadband access 47 The UE uses XCAP in fixed broadband access 48 Void 49 The UE uses XCAP without PDN connection applies. 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access 50 The UE uses XCAP in fixed broadband access	47						
49 The UE uses XCAP without PDN connection in WLAN The UE uses XCAP without PDN connection in WLAN The UE uses XCAP without PDN connection in WLAN The UE uses XCAP in fixed broadband access The						<u> </u>	
without PDN connection in WLAN DN Fi access without PDN connection applies. Otherwise, EPC-integrated WLAN applies The UE uses XCAP in fixed broadband access OREI-12 Rel-12 PC_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS			ID 54 [04] 4.0	<u> </u>	Dalaa	no MI ANI VOAD with and D	If DICC := 4m := 14"
WLAN WLAN PDN connection applies. Otherwise, EPC-integrated WLAN applies The UE uses XCAP in fixed broadband access OREI-12 Rel-12 PDN connection applies. Otherwise, EPC-integrated WLAN applies In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	49			0	Kel-11	P – – – –	
applies. Otherwise, EPC- integrated WLAN applies The UE uses XCAP in fixed broadband access OREI-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS						אט	
Otherwise, EPC- integrated WLAN applies The UE uses XCAP in fixed broadband access ORel-12 Pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS		VVLAN					
integrated WLAN applies The UE uses XCAP in fixed broadband access OREI-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
The UE uses XCAP in fixed broadband access O Rel-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
The UE uses XCAP in fixed broadband access ORel-12 pc_fixed_broadband_XCAP In the context of the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
fixed broadband access the present specification, a UE supporting fixed broadband, A.18/3, shall set this PICS							
specification, a UE supporting fixed broadband, A.18/3, shall set this PICS	50			0	Rel-12	pc_fixed_broadband_XCAP	
supporting fixed broadband, A.18/3, shall set this PICS		fixed broadband access					
broadband, A.18/3, shall set this PICS							
broadband, A.18/3, shall set this PICS							
to true.							
					<u></u>		

51	The UE uses same public user Identity for From/To as in initial REGISTER	24.229 [10]	0	Rel-8	pc_Same_IMPU	
		IR.92 [83], 2.2.1	m			
		NG.114 [96]	m	Rel-15		
52	UE reattempts IMS emergency service without registration after rejection of emergency registration. (For Rel-14, this is applicable only when the rejection indicates an anonymous emergency call support)	23.167 [76], 4.1	0	Rel-9	pc_IMS_after_EmReg_rejection	
			m	Rel-14		
53	Void					
54	UE supports IMS eCall type of emergency services over EPS	24.229 [10], 5.1.6.11, L.2.2.6.2	0	Rel-14	pc_EPS_IMS_eCall_Capable	
55	UE supports IMS eCall Only type of emergency services over EPS	24.229 [10], 5.1.6.11, L.2.2.6.2	0	Rel-14	pc_EPS_IMS_eCall_Only	
56	UE supports audio media	24.229 [10],	m	Rel-13	pc_IMS_Audio_FeatureTag	
	feature tag	5.1.1.2.1, 5.1.3.1, 5.1.4				
		IR.92 [83], 2.2.1, 2.2.4 NG.114 [96]	 	Rel-15	<u> </u>	
<i></i>	LIE augusta Casaian				no IMC Consists Times	
57	UE supports Session Timer	24.229 [10], 5.1.2A, 5.2.7.2, 5.2.7.3, 5.4.5.3	0	Rel-6	pc_IMS_Session_Timer	
		IR.92 [83], 2.2.8	m			
		NG.114 [96]	m	Rel-15		
58	UE supports enabling/disabling SMS over IMS	27.007 [97], 8.72	0	Rel-15	pc_Enable_Disable_SMSove rIMS	
59	UE supports disabling preconditions	24.229 [10], 5.1.5A	0	Rel-15	pc_IMS_Disable_Preconditions	
60	UE uses Session Timer for its benefit alone	24.229 [10]	0	Rel-15	pc_IMS_Session_Timer_own benefit	
	lor its beliefit alone	NG.114 [96]	0		_beriefit	
		RFC 4028 [86]	0			
		cl 7.2	J			
61	UE supports usage of re- INVITE for session refresh		0	Rel-15	pc_IMS_Session_Timer_reIN VITE	
		NG.114 [96]	0			
		RFC 4028 [86] cl 7.2	0			
62	Void					
63	UE supports IMS eCall type of emergency services over 5GS	24.229 [10], 5.1.6.11, U.2.2.6.2	0	Rel-16	pc_5GS_IMS_eCall_Capable	
64	UE supports IMS eCall Only type of emergency services over 5GS	24.229 [10], 5.1.6.11,	0	Rel-16	pc_5GS_IMS_eCall_Only	
65	UE supports IMS emergency call over	U.2.2.6.2 24.229 [10], 5.1.6, R.2.2.6	0	Rel-13	pc_WLAN_IMS_Emergency Call	
	WLAN					
-4 -5	701 A 4 4 4/00 TUEN - E: 0			s/Options		
	73] A.4.4-1/32 THEN m ELS 1: As an exception to NG.11				nol	
INOIE	1. As an exception to NG.11	- support of MTS	viueu C	an is upilo	iiai.	

A.4.6 Additional information for IPv4

Table A.13: Additional information for IPv4

Item	Additional information	Reference	Status	Release	Mnemonic	Comments
	for IPv4					
1	UE capable of being configured to initiate P-CSCF discovery via DHCPv4	23.981 [18], 5.2.1	0	Rel-5	pc_InitiateP_CSCFDiscovery _viaDHCPv4	
2	UE supports P-CSCF discovery via DHCPv4	23.981 [18], 5.2.1	0	Rel-5	pc_P_CSCFDiscovery_viaD HCPv4	

A.4.7 MTSI media

Table A.15: MTSI media

Item	Media	Reference	Status	Release	Mnemonic	Comments
1	Speech	26.114 [56],	0	Rel-7	pc_MTSI_Speech	
		5.2.1				
		IR.92 [83], 3.2	m			
		IR 51 [84], 3	m			
		NG.108 [87]	m			
		NG.114 [96]	m	Rel-15		
2	Speech, AMR wideband	26.114 [56],	0	Rel-7	pc_MTSI_Speech_AMRWB	
		5.2.1				
		IR.51 [84], 3	m			
		IR.92 [83], 3.2	m			
		NG.114 [96]	m	Rel-15		
3	Video	26.114 [56],	0	Rel-7	pc_MTSI_Video	
		5.2.2				
		IR.94 [75], 3.3	m			
		IR.51 [84], 3	m			
		NG.114 [96]	m	Rel-15		
			NOTE 1			
4	Video, H.263 Profile 3	26.114 [56],	0	Rel-7		
	NO A	5.2.2		D 17		
5	Video, MPEG-4	26.114 [56],	0	Rel-7		
	Video, H.264	5.2.2	_	Dal 7		
6	Video, H.264	26.114 [56], 5.2.2	0	Rel-7		
7	Void	5.2.2				
8	Void					
9	Video codec H.264 CBP	26.114 [56],	0	Rel-8	pc_VideoCodecH264CBP	
	Level 1.2	5.2.2		11010	VIGCOCOCCO 12040D1	
		IR.94 [75], 3.3	m			
		IR.51 [84], 3	m	1		
10	Speech, EVS	26.114 [56]	0	Rel-12	pc_MTSI_Speech_EVS	
		NG.114 [96]	m	Rel-15		
11	Video codec H.265	26.114 [56],	c1	Rel-15	pc_VideoCodecH265Lv31	
	(HEVC), Main Profile, Main Tier, Level 3.1	5.2.2		I Kel 10	pc_viacocoacoi i2002vo1	
		NG.114 [96]	m	Rel-15	1	
			NOTE 1			
12	Video codec H.264 (AVC)	26.114 [56],	0	Rel-15	pc_VideoCodecH264CHPLv31	
	CHP Level 3.1	5.2.2				
		NG.114 [96]	m	Rel-15]	
			NOTE 1			
13	Video codec H.264 (AVC)	26.114 [56],	0	Rel-15	pc_VideoCodecH264CBPLv31	
	CBP Level 3.1	5.2.2			_	
		NG.114 [96]	m	Rel-15		
			NOTE 1			
NOTE 1	1: As an exception to NG.11	4 support of MTS	SI Video C	all is optior	nal.	

NOTE 1: As an exception to NG.114 support of MTSI Video Call is optional c1: IF NOT A.15/3 OR [93]

A.4.8 MTSI supplementary services

Table A.16: MTSI supplementary services

Item	Service	Reference	Status	Release	Mnemonic	Comments
1	Originating Identification	24.173 [55],	0	Rel-7	pc_MTSI_OIP	
	Presentation	Annex A				
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.114 [96]	m	Rel-15		

2	Originating Identification	24.173 [55],	0	Rel-7	pc_MTSI_OIR	
	Restriction	Annex A		-		
		IR.92 [83], 2.3	m	-		
		IR.51 [84], 2.3	m			
		NG.108 [87] NG.114 [96]	m m	Rel-15	4	
2A	Originating Identification	24.173 [55],	0	Rel-7	pc_MTSI_OIR_C	
ZA	Restriction - Configuration	Annex A	U	Kei-1	pc_WT3I_OIK_C	
	l comonon comigaranon					
		IR.92 [83], 2.3	0			
		[50], =:5				
		NG.114 [96]	0	Rel-15		
3	Terminating Identification	24.173 [55],	0	Rel-7	pc_MTSI_TIP	
	Presentation	Annex B				
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m	D 145	_	
4	Tamain ation a lalantification	NG.114 [96]	0	Rel-15	a MTCL TID	
4	Terminating Identification Restriction	24.173 [55], Annex B	0	Rel-7	pc_MTSI_TIR	
	T COUTOUOTT	IR.92 [83], 2.3	m	1		
		IR.51 [84], 2.3	m	-		
		NG.108 [87]	m	1		
		NG.114 [96]	m	Rel-15		
4A	Terminating Identification	24.173 [55],	0	Rel-7	pc_MTSI_TIR_C	
	Restriction - Configuration	Annex A				
		IR.92 [83], 2.3	0			
		NG.114 [96]	0	Rel-15		
5	Communication Diversion	24.173 [55],	0	Rel-7	pc_MTSI_CommDivert	
		Annex C				
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.108 [87]	m			
		NG.114 [96]	m	Rel-15		
6	Communication Hold	24.173 [55],	0	Rel-7	pc_MTSI_CommHold	
		Annex D IR.92 [83], 2.3	m	1		
		IR.51 [84], 2.3	m	1		
		NG.114 [96]	m	Rel-15	-	
7	Incoming Communication	24.173 [55],	0	Rel-7	pc_MTSI_Incoming_CB	
	Barring	Annex E]		
		IR.92 [83], 2.3	m]		
		IR.51 [84], 2.3	m			
		NG.114 [96]	m	Rel-15		
8	Message Waiting	24.173 [55],	0	Rel-7	pc_MTSI_MessageWait	
	Indication	Annex F IR.92 [83], 2.3	m	-		
		IR.51 [84], 2.3	m m	1		
		NG.108 [87]	m	1		
		NG.114 [96]	m	Rel-15	-	
9	Conference	24.173 [55],	0	Rel-7	pc_MTSI_Conference	
		Annex G				
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.114 [96]	m	Rel-15		
10	Void					

11	Explicit Communication Transfer - consultative transfer	24.173 [55], Annex H	0	Rel-7	pc_IMS_ExplicitConsultative Transfer	
		NG.114 [96]	m	Rel-15		
12	Anonymous Communication Rejection	24.173 [55], Annex E	0	Rel-7	pc_MTSI_ACR	
13	Communication Waiting	24.615 [69]	0	Rel-7	pc_MTSI_CommWaiting	
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.108 [87]	m			
		NG.114 [96]	m	Rel-15		
14	Three way session	24.147 [19]	0	Rel-8	pc_IMS_TWS	
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.114 [96]	m	Rel-15	-	
15	Outgoing Communication Barring	24.173 [55], Annex E	0	Rel-7	pc_MTSI_Outgoing_CB	
		IR.92 [83], 2.3	m			
		IR.51 [84], 2.3	m			
		NG.114 [96]	m	Rel-15		
16	Void					_
17	Void					
18	SIP based user configuration	24.238 [85], 432	0	Rel-7	pc_SIP_Based_UserConfigur ation	
19	USSI	24.390 [90]	0	Rel-12	pc_USSI	
		IR.92 [83], Annex D	0			
		NG.114 [96]	0	Rel-15		

A.4.9 MTSI media change

Table A.17: MTSI media change

Item	Media change	Ref.	Status	Release	Mnemonic	Comments
1	Text, add video remove		0	Rel-7		
	video					

A.4.10 UE Implementation Types

Table A.18: UE Access Technologies

Item	UE Access Technologies	Reference	Status	Release	Mnemonic	Comments
1	E-UTRA	36.101 [70]	0	Rel-8	pc_eFDD or pc_eTDD	pc_eFDD and pc_eTDD as defined in TS 36.523-2 [73] Table A.4.1-1
2	UTRA	21.904 [71], 5	0	R99	pc_UTRA	pc_UTRA as defined in TS 36.523-2 [73] Table A.4.1-1
3	Fixed Broadband	24.229 [10], Annex E	0	Rel-7	pc_FixedBroadband	
4	WLAN	IEEE Std 802.11	0		pc_WLAN	
5	NR	38.101-1 [91], 38.101-2 [92]	0	Rel-15	pc_NG_RAN_NR	pc_NG_RAN_NR as defined in TS 38.508-2 [93] Table A.4.1-3

A.4.11 Special Conformance Testing Functions

Table A.19: Special Conformance Testing Functions

Item	Special Conformance Testing Functions	Ref.	Release	Mnemonic	Comments
1	Update UE Location Information	34.109 [78],	Rel-10	See 36.523-2 [73]	
		5.4.2			
		36.509 [79],			
		5.5.2			

A.4.12 NG.102

Table A.20: NG.102 capabilities

Item		Ref.	Status	Release	Mnemonic	Comments
1	Combined Registration E- UTRA	NG.102 [89]	0	n/a	pc_NG102_Combined_Registration_EUT RA	
2	Dual Registration E-UTRA	NG.102 [89]	0	n/a	pc_NG102_Dual_Registration_EUTRA	
3	Combined Registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Combined_Registration_WLAN	
4	Dual Registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Dual_Registration_WLAN	
5	Voice Call after combined registration E-UTRA	NG.102 [89]	0	n/a	pc_NG102_Call_Combined_Registration_ EUTRA	
6	Voice call after dual registration E-UTRA	NG.102 [89]	0	n/a	pc_NG102_Call_Dual_Registration_EUT RA	
7	Voice Call after combined registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Call_Combined_Registration_ WLAN	
8	Voice call after dual registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Call_Dual_Registration_WLA	
9	RCS chat after combined registration E-UTRA	NG.102 [89]	0	n/a	pc_NG102_Chat_Combined_Registration _EUTRA	
10	RCS chat after dual registration E-UTRA	NG.102 [89]	0	n/a	pc_NG102_Chat_Dual_Registration_EUT RA	
11	RCS chat after combined registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Chat_Combined_Registration_WLAN	
12	RCS chat after dual registration WLAN	NG.102 [89]	0	n/a	pc_NG102_Chat_Dual_Registration_WL AN	

A.4.13 NG.114 versions

Table A.21: NG.114 versions

Item		Ref.	Status	Release	Mnemonic	Comment s
1	Version 1.0 as of 07 August 2020	NG.114 v1.0 [96]	0	n/a	pc_NG114_v1_0	
2	Version 2.0 as of 07 August 2021	NG.114 v2.0 [98]	0	n/a	pc_NG114_v2_0	

A.4.14 NG.114 capabilities

Table A.22: NG.114 capabilities

Item		Ref.	Status	Release	Mnemonic	Comment
1	mmtel ICSI value	NG.114 v1.0 [96]	m	n/a	pc_NG114_v1_0_mmtel	
2	audio feature tag	NG.114 v1.0 [96]	m	n/a	pc_NG114_v1_0_audio	
3	video feature tag	NG.114 v1.0 [96]	m NOTE 1	n/a	pc_NG114_v1_0_video	
4	Void					
5	Void					
6	Void					
7	Void					
8	Annex C.3 default configuration for voice exempt	NG.114 v2.0 [98]	m	n/a	pc_NG114_v1_0_default_config_voice_exempt	
9	Annex C.3 default configuration for video exempt	NG.114 v2.0 [98]	m	n/a	pc_NG114_v2_0_default_config_video_exempt	
10	Annex C.3 default configuration for EVS/Br	NG.114 v1.0 [96]	m	n/a	pc_NG114_v1_0_default_config_evs_br	
11	Annex C.3 default configuration for EVS/Bw	NG.114 v1.0 [96]	m	n/a	pc_NG114_v1_0_default_config_evs_bw	
12	Void					
13	Void					
14	Forking behavior	NG.114 v1.0 [96]	m	n/a	pc_NG114_v1_0_forking	
15	EVS Configuration B0	NG.114 v1.0 [96]	0		pc_NG114_v1_0_EVS_B0	
16	EVS Configuration B1	NG.114 v1.0 [96]	0		pc_NG114_v1_0_EVS_B1	
17	EVS Configuration B2	NG.114 v1.0 [96]	0		pc_NG114_v1_0_EVS_B2	
18	EVS Configuration A1	NG.114 v1.0 [96]	0		pc_NG114_v1_0_EVS_A1	
NOTI	1: As an exception to N	NG.114 supp	ort of MT	SI Video C	all is optional.	•

Annex B (informative): Change history

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
-	-	-	-	Update to version 2.0.0 during RAN5#31 e-mail agreement procedure	-	1.0.0	2.0.0	R5-061399
RP-32	RP-060320	-	-	MCC Editorial clean up version 2.0.1 - and present to RAN#32 for approval to go under revision control (as version 5.0.0)	-	2.0.0	2.0.1	-
	-	-	-	Update to version 5.0.0 after RAN#32	-	2.0.1	5.0.0	-
RP-33	RP-060565	0001	-	Applicability for new P-CSCF Discovery List test cases	F	5.0.0	5.1.0	R5-062365
RP-33	RP-060565	0002	-	CR to 34.229-2: Update applicability table for IMSCC test		5.0.0	5.1.0	R5-062026
RP-34	RP-060746	0003	-	Updating of test cases to cover both IMS support and early IMS security scenarios, ICS part	F	5.1.0	5.2.0	R5-063528
RP-34	RP-060746	0004	-	ICS part for new registration test cases 8.5, 8.6 and 8.7 for early IMS security	F	5.1.0	5.2.0	R5-063527
RP-34	RP-060746	0005	-	Removal of MO Call - 488 not accepted here for rel 5, ICS part	F	5.1.0	5.2.0	R5-063331
RP-34	RP-060746	0006	-	Production of pointer version 5.2.0 of TS 34.229-2 with no technical contents	F	5.1.0	5.2.0	R5-063292
RP-34	RP-060748	0007	-	Update to 34.229-2 : Major capabilities	F	5.1.0	6.0.0	R5-063571
RP-35	RP-070089	0008	-	IMS security and early IMS security capability update	F	6.0.0	6.1.0	R5-070426
RP-35	RP-070089	0009	-	Removal of applicability statements for IMS test cases 7.7 and 7.8	F	6.0.0	6.1.0	R5-070330
RP-36	RP-070362	0010		Applicability of IMS TC 13.4	F	6.1.0	6.2.0	R5-071060
RP-36	RP-070362	0010		Coding options for the IPv4 address in PCO IE	F	6.1.0	6.2.0	R5-071438
RP-36	RP-070362	0013		Applicability of Call Control TCs	F	6.1.0	6.2.0	R5-071507
RP-37	RP-070607	0014	-	Applicability of re- and de-registration TCs for early	F	6.2.0	6.3.0	R5-072115
RP-38	RP-070874	0017		Production of 34.229-2 pointer version in Rel-6 pointing to Rel-7 version	F	6.3.0	6.4.0	R5-073279
RP-38	RP-070882	0015		Applicability of new MTSI MO Call and Call Hold test cases	F	6.3.0	7.0.0	R5-073445
RP-38	RP-070882	0016		Add MTSI media capabilities	F	6.3.0	7.0.0	R5-073096
RP-39	RP-080113	0018		Applicability for new MTSI test cases 15.12, 15.13 and 15.23	F	7.0.0	7.1.0	R5-080597
RP-39	RP-080113	0019		Applicability for MTSI test case MO MTSI Text call	F	7.0.0	7.1.0	R5-080562
RP-39	RP-080114	0020		Applicability for MTSI test case Speech AMR, indicate all codec modes	F	7.0.0	7.1.0	R5-080081
RP-39	RP-080114	0021		Applicability for MTSI test case Speech AMR-WB, indicate all codec modes	F	7.0.0	7.1.0	R5-080083
RP-39	RP-080114	0022		Applicability for MTSI test case MT Video, add speech remove speech	F	7.0.0	7.1.0	R5-080590
RP-39	RP-080114	0023		Update SDP applicability tables	F	7.0.0	7.1.0	R5-080578
RP-39	RP-080114	0024		Update references in TS 34.229-2	F	7.0.0	7.1.0	R5-080090
RP-39	RP-080114	0025		Update key to status codes	F	7.0.0	7.1.0	R5-080091
RP-39	RP-080114	0026		Addition of Applicability Statement for new MTSI test cases	F	7.0.0	7.1.0	R5-080603
RP-40	RP-080376	0027		Applicability statements of new MTSI test cases	F	7.1.0	7.20	R5-081500
RP-40	RP-080376	0028		Media change capabilities	F	7.1.0	7.20	R5-081084
RP-40	RP-080376	0029		Applicability for new MTSI test case MT MTSI Speech call	F	7.1.0	7.20	R5-081085
RP-40	RP-080376	0030		Applicability for new MTSI test case MT MTSI Video call	F	7.1.0	7.20	R5-081086
RP-40	RP-080376	0031		Applicability for new MTSI test case Speech AMR indicate selective codec modes	F	7.1.0	7.20	R5-081088
RP-40	RP-080376	0032		Applicability for new MTSI test case Speech AMR-WB indicate selective codec modes	F	7.1.0	7.20	R5-081089
RP-40	RP-080376	0033			F	7.1.0	7.20	R5-081090
RP-40	RP-080376	0034			F	7.1.0	7.20	R5-081091
RP-41	RP-080564	0035		Update applicabilities for clause 12 test cases	F	7.2.0	7.3.0	R5-083134
RP-41	RP-080564	0036		Update applicabilities for clause 17 test cases	F	7.2.0	7.3.0	R5-083135
RP-41	RP-080564	0037		Update applicabilities for clause 16 test cases	F	7.2.0	7.3.0	R5-083136
RP-41	RP-080564	0038		Remove table for MTSI media change	F	7.2.0	7.3.0	R5-083137
RP-41	RP-080564	0039		Correct applicability for test case 14.2	F	7.2.0	7.3.0	R5-083452
RP-41	RP-080564	0040		Applicability statements of new MTSI test cases	F	7.2.0	7.3.0	R5-083560
RP-41	RP-080557	0041		Removal of reference to IMS test case 13.4	F	7.2.0	7.3.0	R5-083586
RP-42	RP-080966	0042		Applicability statements of new MTSI test cases	F	7.3.0	8.0.0	R5-085049

Meeting	Doc-1st- Level	CR	Rev	Subject	Cat	Version	Version -New	Doc-2nd- Level
Level	Level					Current	-new	Levei
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-42	RP-080966	0043		Remove applicabilities for non MTSI related call setup test cases	F	7.3.0	8.0.0	R5-085352
RP-42	RP-080966	0044		Remove applicabilities for non mandatory use cases	F	7.3.0	8.0.0	R5-085434
RP-42	RP-080966	0045		Update of applicability of MTSI test cases for adding/removing media	F	7.3.0	8.0.0	R5-085444
RP-43	RP-090205	0046		Update of TS 34.229-2 from Rel-7 to Rel-8	F	7.3.0	8.0.0	R5-090764
RP-43	RP-090214	0047		Applicability statements of new MTSI test cases	F	8.0.0	8.1.0	R5-090346
RP-43	RP-090214	0048		Applicability statements of new MTSI test cases	F	8.0.0	8.1.0	R5-090624
RP-43	RP-090214	0049		Remove applicabilities for non MTSI related call setup test cases (2nd)	F	8.0.0	8.1.0	R5-090626
RP-43	RP-090214	0050		Add applicabilities for new clause 16 test cases	F	8.0.0	8.1.0	R5-090627
RP-43	RP-090214	0051		Remove applicabilities for removed clause 16 test cases	F	8.0.0	8.1.0	R5-090628
RP-43	RP-090214	0052		Add applicability for new clause 17 test case	F	8.0.0	8.1.0	R5-090629
RP-44	RP-090433	0053		Addition of PICS for support of UI Message Waiting Indication	F	8.1.0	8.2.0	R5-092218
RP-45	RP-090794	0054		Update table A.318 SDP types	F	8.2.0	8.3.0	R5-094354
RP-46	RP-091116	0055		Update applicability for test cases 14.1 and 14.2	F	8.3.0	8.4.0	R5-095818
RP-46	RP-091118	0056		Update applicability for test case 12.2	F	8.3.0	8.4.0	R5-095820
RP-46	RP-091118	0057		Update table A.12	F	8.3.0	8.4.0	R5-096181
RP-47	RP-100155	0058	-	Addition of applicability for new SMS over IMS test case	F	8.4.0	8.5.0	R5-100083
RP-47	RP-100155	0059	-	Add capability for SMS over IP	F	8.4.0	8.5.0	R5-100510
RP-47	RP-100155	0060	-	Add applicability for SMS test cases	F	8.4.0	8.5.0	R5-100511
RP-47	-	-	-	Moved to v9.0.0 with no change	-	8.5.0	9.0.0	-
RP-48	RP-100511	0061	-	Adding capabilities to TS 34.229-2 for VoLTE profile alignment	F	9.0.0	9.1.0	R5-103856
RP-49	RP-100985	0063	-	Introducing new MTSI test cases for CF and CW	F	9.1.0	9.2.0	R5-104293
RP-49	RP-100986	0064	-	Add radio capabilities	F	9.1.0	9.2.0	R5-104312
RP-49 RP-49	RP-100986 RP-100986	0065 0066	-	Update security scheme with GIBA Update applicability for clause 8 registration test	F F	9.1.0 9.1.0	9.2.0 9.2.0	R5-104436 R5-104438
RP-49	DD 400006	0067		Cases	F	0.4.0	0.2.0	DE 104420
RP-49	RP-100986 RP-100838	0067	-	Update applicability for test case 13.1 Introducing new test cases for IMS emergency registration	F	9.1.0	9.2.0 9.2.0	R5-104439 R5-104737
-	-	-	-	Editorial renumbering of test cases 15.27 - 15.30 in order to align with GCF list	-	9.1.0	9.2.0	-
RP-50	RP-101146	0072	-	Remove applicability for test case 14.1 and 14.2	F	9.2.0	9.3.0	R5-106488
RP-50	RP-101146	0071	-	Update of applicability for MTSI test cases	F	9.2.0	9.3.0	R5-106302
RP-50	RP-101146	0070	-	Remove PSS tables	F	9.2.0	9.3.0	R5-106239
RP-50	RP-101146	0069	-	Add new test case 15.14a CB while roaming	F	9.2.0	9.3.0	R5-106153
RP-50	RP-101146	0073	-	Update security, adressing and SIP compression tables	F	9.2.0	9.3.0	R5-106579
RP-50	RP-101156	0076	-	Introducing TC 19.1.1 Basic IMS emergency call over EPS	F	9.2.0	9.3.0	R5-106591
RP-50	RP-101146	0075	-	Update MTSI information	F	9.2.0	9.3.0	R5-106584
RP-50	RP-101146	0074	-	Update additional information for IPv4	F	9.2.0	9.3.0	R5-106582
RP-50	RP-101146	0078	-	Update abbreviations and conventions	F	9.2.0	9.3.0	R5-106686
RP-50	RP-101146	0077	-	Rel-8 IMS test case applicabilities	F	9.2.0	9.3.0	R5-106685
-	-	-	-	Added email agreed R5-106685	-	9.3.0	9.3.1	-
RP-51	RP-110165	0079	-	Applicability for IMS TCs updated or added to Rel-8	F	9.3.1	9.4.0	R5-110264
RP-51	RP-110174	0800	=	Introducing IMS emergency TCs 19.1.2, 19.1.4, 19.5.6	F	9.3.1	9.4.0	R5-110270
RP-51	RP-110165	0081	-	Update roles and ICS related to SIP	F	9.3.1	9.4.0	R5-110291
RP-51	RP-110165	0082	-	Update applicability roles	F	9.3.1	9.4.0	R5-110292

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-51	RP-110165	0083	-	Update SIP compression table	F	9.3.1	9.4.0	R5-110293
RP-51	RP-110165	0084	-	Remove SDP tables	F	9.3.1	9.4.0	R5-110294
RP-51	RP-110165	0085	-	Update additional information	F	9.3.1	9.4.0	R5-110295
RP-51	RP-110165	0086	-	Update UE implementation types	F	9.3.1	9.4.0	R5-110296
RP-51	RP-110165	0087	-	Update applicability for test case 10.1	F	9.3.1	9.4.0	R5-110378
RP-51	RP-110165	0088	-	Update applicability for test cases 12.2, 12.13, 12.16 and 12.17	F	9.3.1	9.4.0	R5-110379
RP-51	RP-110165	0089	-	Update applicability for test cases 16.1, 16.2, 16.3 and 16.4	F	9.3.1	9.4.0	R5-110381
RP-51	RP-110165	0090	=	Applicable release upgrade for clause 6 and 7 test cases	F	9.3.1	9.4.0	R5-110401
RP-51	RP-110165	0091	-	Update applicability of test cases 16.11, 16.12, 16.13, 17.2, 17.6, 17.17 and 17.18.	F	9.3.1	9.4.0	R5-110500
RP-51	RP-110165	0092	-	update applicability for test cases 13.1, 13.2 and 13.3	F	9.3.1	9.4.0	R5-110707
RP-51	RP-110174	0093	-	Introduction of applicability conditions for new test cases for CT1 aspects of IMS emergency call over GPRS and EPS	F	9.3.1	9.4.0	R5-110811
RP-51	RP-110174	0094	-	Applicability for new emergency test case 19.3.2	F	9.3.1	9.4.0	R5-110812
RP-51	RP-110165	0095	-	Introducing new MTSI test cases for Three Way Session and CW	F	9.3.1	9.4.0	R5-110822
RP-52	RP-110660	0096	=	New IMS emergency TCs 19.5.7, 19.5.8, 19.5.9, 19.5.10	F	9.4.0	9.5.0	R5-112175
RP-52	RP-110660	0097	-	Add applicability for new test case 19.4.1	F	9.4.0	9.5.0	R5-112497
RP-52	RP-110651	0098	-	Applicability for IMS TCs updated or added to Rel-8	F	9.4.0	9.5.0	R5-112647
RP-52	RP-110660	0099	-	Introduction of applicability conditions for new test cases for CT1 aspects of IMS emergency call over GPRS and EPS	F	9.4.0	9.5.0	R5-112652
RP-53	RP-111151	0100	-	Applicability of new test cases for SSAC	F	9.5.0	9.6.0	R5-113746
RP-54	RP-111591	0101	=	Correction to applicability for test case 19.5.9 and 19.5.10	F	9.6.0	9.7.0	R5-115183
RP-54	RP-111583	0102	-	Update test case numbering	F	9.6.0	9.7.0	R5-115345
RP-55	RP-120195	0103	-	Update to test case 12.19	F	9.7.0	9.8.0	R5-120437
RP-55	RP-120192	0104	-	Correcting applicability for test case 19.3.2 and a PICS condition	F	9.7.0	9.8.0	R5-120692
RP-56	RP-120657	0105	-	Update to ICS proforma table for Additional information	F	9.8.0	9.9.0	R5-121282
RP-56	RP-120655	0106	-	Removing TC 19.1.4 applicability	F	9.8.0	9.9.0	R5-121431
RP-56	RP-120655	0107	-	Adding applicability for test case 19.3.3 and 19.3.4	F	9.8.0	9.9.0	R5-121499
RP-56	RP-120649	0108	-	Applicability for video test cases 12.21, 12.22. 17.1 and 17.2	F	9.8.0	9.9.0	R5-122120
RP-57	RP-121103	0109	-	Update to ICS proforma table for Additional information	F	9.9.0	9.10.0	R5-123201

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-58	RP-121664	0110	-	Update applicability for emergency test cases	F	9.10.0	9.11.0	R5-125617
RP-58	RP-121685	0111	=	Update to ICS proforma table for Additional information	F	9.11.0	10.0.0	R5-126005
RP-60	RP-130625	0113	-	Addition of testing function	F	10.0.0	10.1.0	R5-131165
RP-60	RP-130611	0114	-	Applicability of 19.1.3a and 19.3.2a	F	10.0.0	10.1.0	R5-131876
RP-60	RP-130625	0115	-	34.229-2 specification clean up	F	10.0.0	10.1.0	R5-132012
RP-61	RP-131114	0116	-	Update reference for Update UE Location Information	F	10.1.0	10.2.0	R5-133631
RP-61	RP-131102	0117	-	Correction of applicability for test cases 19.1.1 and 19.3.1	F	10.1.0	10.2.0	R5-133708
RP-62	RP-131875	0118	-	Remove applicabilities for not needed test cases	F	10.2.0	10.3.0	R5-134298
RP-62	RP-131875	0119	-	Update for IR.92 version 7	F	10.2.0	10.3.0	R5-135021
RP-63	-	-	-	Upgraded to v11.0.0 without change	F	10.3.0	11.0.0	-
RP-63	RP-140306	0120	-	Remove applicability for test case 16.1	F	11.0.0	12.0.0	R5-140929
RP-63	RP-140306	0120	-	Remove applicability for test case 16.1	F	11.0.0	12.0.0	R5-140929
RP-63	RP-140334	0121	=	Applicability of new test cases for SSAC in connected mode	F	11.0.0	12.0.0	R5-140930
RP-63	RP-140333	0122	-	Addition of new condition for bSRVCC	F	11.0.0	12.0.0	R5-140968
RP-64	RP-140815	0123	-	Applicability of new test cases for the UE receiving SIP_380	F	12.0.0	12.1.0	R5-142959
RP-64	RP-140812	0124	-	Update call hold applicability for IR.92 versions	F	12.0.0	12.1.0	R5-142960
RP-65	RP-141571	0125	-	Editorial correction of the 16.4 test case title	F	12.1.0	12.2.0	R5-144130
RP-65	RP-141571	0126	-	Add XCAP capabilities	F	12.1.0	12.2.0	R5-144531
RP-65	RP-141571	0127	-	Editorial correction of codec table number	F	12.1.0	12.2.0	R5-144559
RP-65	RP-141596	0128	-	Editorial correction of section order related to Rel-12 SSAC	F	12.1.0	12.2.0	R5-144696
RP-65	RP-141573	0129	=	Addition of new applicability for SIP error handling test cases	F	12.1.0	12.2.0	R5-144697
RP-65	RP-141571	0130	-	Addition of applicability statements for new IMS Video test cases	F	12.1.0	12.2.0	R5-144698
RP-65	RP-141573	0131	-	Correction to applicability of test case 19.1.3b	F	12.1.0	12.2.0	R5-144749
RP-66	RP-142054	0132	-	Correction to applicability of GCF WI-103 IMS Testcase 8.3	F	12.2.0	12.3.0	R5-145157
RP-66	RP-142073	0133	-	Update of Additional Information table for rSRVCC	F	12.2.0	12.3.0	R5-145751
RP-66	RP-142056	0134	-	Applicability of test case 19.3.2c	F	12.2.0	12.3.0	R5-145770
RP-66	RP-142056	0135	-	Correction to Applicability of GCF WI-154 IMS Emergency Call Testcases	F	12.2.0	12.3.0	R5-145778
RP-67	RP-150322	0136	-	Add applicability for new GBA test case	F	12.3.0	12.4.0	R5-150537
RP-67	RP-150322	0137	-	Add capability for GBA	F	12.3.0	12.4.0	R5-150712
RP-67	RP-150322	0138	-	Clarification on A.12/23 vs A.12/35	F	12.3.0	12.4.0	R5-150737

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-68	RP-150884	0140	-	Add capability for access type	F	12.4.0	12.5.0	R5-151243
RP-68	RP-150886	0145	-	Correction to test case applicability 19.1.1 and 19.3.1 for location information	F	12.4.0	12.5.0	R5-151518
RP-68	RP-150884	0139	1	Updates for GBA testing - Part2	F	12.4.0	12.5.0	R5-151962
RP-68	RP-150884	0144	1	Change of applicability for Testcase 8.3	F	12.4.0	12.5.0	R5-151963
RP-68	RP-150884	0146	1	Applicability for new TC 20.1 Mobile Originating CAT - Forking Model	F	12.4.0	12.5.0	R5-151964
RP-68	RP-150906	0142	1	Add capability for EVS	F	12.4.0	12.5.0	R5-151969
RP-68	RP-150906	0143	1	Add applicability for new MO EVS test case	F	12.4.0	12.5.0	R5-151970
RP-69	RP-151427	0149	-	Add applicability for new MT EVS test case	F	12.5.0	12.6.0	R5-153538
RP-69	RP-151409	0152	-	Rewording of PICS for video feature tag	F	12.5.0	12.6.0	R5-153680
RP-69	RP-151409	0148	1	Correction to description of applicability of testcase 8.3	F	12.5.0	12.6.0	R5-153767
RP-69	RP-151409	0153	-	New PICS for dialog usage upon subscription to conference event package	F	12.5.0	12.6.0	R5-153790
RP-69	RP-151427	0151	1	Add applicability for new MT EVS test case 12.25	F	12.5.0	12.6.0	R5-153951
RP-69	RP-151409	0154	1	Test case applicability changes due to Split of XCAP test case 15.14a	F	12.5.0	12.6.0	R5-153996
RP-69	-	-	-	update of the "non-specific references" in section 2 according to the approved R5-153582 and an action point on ETSI MCC	-	12.5.0	12.6.0	-
RP-70	RP-151703	0158	-	Add applicability for new MT EVS test case	F	12.6.0	12.7.0	R5-155468
RP-70	RP-151684	0159	-	Remove outdated reference	F	12.6.0	12.7.0	R5-155760
RP-71	RP-160117	0164	-	Removing item on subscription to conference event package	F	12.7.0	12.8.0	R5-160554
RP-71	RP-160116	0161	1	Correction of Applicability of Test Case 8.14 by introduction of PICS for Multiple IMPU per TS 24.229 Section 5.1.1.4	F	12.7.0	12.8.0	R5-160910
RP-71	RP-160117	0162	1	Correction of PICS applicability for TC 15.21 and 15.21b with introduction of new PICS for Network Invitation to Conference per TS 24.147 Section 5.3.1.4.2	F	12.7.0	12.8.0	R5-160911
RP-71	RP-160119	0166	-	Applicability updates on IMS emergency call test case 19.3.2	F	12.7.0	12.8.0	R5-160938
RP-71	RP-160117	0163	1	Removal of outdated versions of GSMA PRD IR.92	F	12.7.0	12.8.0	R5-160944
RP-71	RP-160096	0800	1	Applicability of new MTSI Fixed Broadband Access test cases	F	12.7.0	12.8.0	R5-160974
RP-71	RP-160117	0165	1	Addition of applicability statements for new OIR/TIR test cases	F	12.7.0	12.8.0	R5-160977
RP-72	RP-160831	0168	-	Add applicabilities for new WLAN supplementary services test cases	F	12.8.0	12.9.0	R5-162070
RP-72	RP-160831	0169	-	Add IR.51 IMS Profile for Voice, Video and SMS over Wi-Fi	F	12.8.0	12.9.0	R5-162071
RP-72	RP-160830	0173	-	Add applicabilities for new Fixed Broadband Access supplementary services test cases	F	12.8.0	12.9.0	R5-162106

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-72	RP-160830	0175	-	Adding mnemonics for PICS	F	12.8.0	12.9.0	R5-162149
RP-72	RP-160845	0177	=	Applicability of new MTSI Fixed Broadband Access test cases	F	12.8.0	12.9.0	R5-162162
RP-72	RP-160845	0178	-	Removing item 35 from Table A.12	F	12.8.0	12.9.0	R5-162314
RP-72	RP-160845	0170	1	Update applicability for AMR-WB	F	12.8.0	12.9.0	R5-162939
RP-72	RP-160845	0180	2	Correction to applicability of IMS test cases	F	12.8.0	12.9.0	R5-162941
RP-72	RP-160858	0172	1	Specification 34.229-2 clean up for XML project	F	12.8.0	12.9.0	R5-163014
RP-72	RP-160845	0167	1	Correction to the applicability of SS test cases requiring XCAP authentication	F	12.8.0	12.9.0	R5-163070
RP-73	RP-161426	0181	-	Removing unused references	F	12.9.0	12.10.0	R5-165202
RP-73	RP-161397	0182	-	Add applicabilities for WLAN supplementary services test cases	F	12.9.0	12.10.0	R5-165209
RP-73	RP-161396	0183	-	Add applicabilities for Fixed Broadband Access supplementary services test cases	F	12.9.0	12.10.0	R5-165291
RP-73	RP-161426	0185	-	Renaming of the PICS parameter for MO/MT SMS over IP feature capability	F	12.9.0	12.10.0	R5-165685
RP-73	RP-161426	0184	1	Align GBA usage	F	12.9.0	12.10.0	R5-166278
RP-73	-	-	-	upgraded to v13.0.0 with no change in order to align with 34.229-1	-	12.10.0	13.0.0	-
RP-74	RP-162102	0186	-	Update the support for AMR-WB	F	13.0.0	13.1.0	R5-168025
RP-74	RP-162116	0189	-	Maintenance of 34.229-2 Appendix A Tables for XML conversion	F	13.0.0	13.1.0	R5-168138
RP-74	RP-162073	0193	=	Applicability of new MTSI Fixed Broadband Access test cases	F	13.0.0	13.1.0	R5-168287
RP-74	RP-162102	0199	-	Deleting pc_TMPI_forGBA	F	13.0.0	13.1.0	R5-168963
RP-74	RP-162104	0198	1	Corrections to applicability of IMS test case 19.5.8	F	13.0.0	13.1.0	R5-169058
RP-74	RP-162102	0194	1	Correction to applicability of IMS test cases 15.21 and 15.21b	F	13.0.0	13.1.0	R5-169059
RP-74	RP-162075	0192	1	Add applicabilities for WLAN supplementary services test cases	F	13.0.0	13.1.0	R5-169073
RP-74	RP-162075	0191	1	Add applicability for XCAP over WLAN	F	13.0.0	13.1.0	R5-169154
RP-75	RP-170108	0200	-	Correcting Mnemonic in Table A.15	F	13.1.0	13.2.0	R5-170529
RP-75	RP-170066	0205	-	Applicability of new MTSI Fixed Broadband Access test cases	F	13.1.0	13.2.0	R5-170794
RP-75	RP-170066	0206	-	Add applicability for XCAP over fixed broadband access	F	13.1.0	13.2.0	R5-171076
RP-75	RP-170095	0201	1	Adding reuse of Public User Identity for To and From headers	F	13.1.0	13.2.0	R5-171493
RP-75	RP-170097	0203	1	Addition of new applicability and ICS for IMS Emergency call in VPLMN	F	13.1.0	13.2.0	R5-171494
RP-75	RP-170109	0204	1	Maintenance of 34.229-2 Table A.4 for XML conversion	F	13.1.0	13.2.0	R5-171520
RP-76	RP-171365	0207	-	Removal of applicability of IMS test case 19.5.8	F	13.2.0	13.3.0	R5-172033

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-76	RP-171376	0211	-	Corrections to test cases H.12.2 and H.15.7 titles	F	13.2.0	13.3.0	R5-172424
RP-76	RP-171377	0208	1	Maintenance of 34.229-2 for XML conversion	F	13.2.0	13.3.0	R5-172954
RP-76	RP-171363	0210	1	Add applicability for session timer	F	13.2.0	13.3.0	R5-173025
RP-77	RP-171660	0214	-	Add applicabilities for UE category M1 test cases	F	13.3.0	13.4.0	R5-173539
RP-77	RP-171660	0215	-	Add media requirements for UE category M1	F	13.3.0	13.4.0	R5-173540
RP-77	RP-171699	0216	-	Removal of technical content in 34.229-2 v12.10.0 and substitution with pointer to the next Release	F	13.3.0	13.4.0	R5-173549
RP-77	RP-171660	0217	-	Add supplementary service requirements for UE category M1	F	13.3.0	13.4.0	R5-173556
RP-77	RP-171688	0218	-	Editorial update of table A.12	F	13.3.0	13.4.0	R5-173590
RP-77	RP-171688	0221	-	Voiding PICS for Session-ID	F	13.3.0	13.4.0	R5-173604
RP-77	RP-171698	0219	1	Correction to PICS for XCAP PDN over WLAN	F	13.3.0	13.4.0	R5-174560
RP-77	RP-171690	0220	1	Correction to applicability of IMS test case 19.4.7	F	13.3.0	13.4.0	R5-174561
RP-77	RP-171688	0223	1	Removal of applicability for unneeded test cases	F	13.3.0	13.4.0	R5-174562
RP-77	RP-171690	0229	1	Addition of NOTE 6 to Test Cases 19.1.3, 19.3.2, 19.3.2b, 19.3.2c	F	13.3.0	13.4.0	R5-174563
RP-77	RP-171653	0224	1	Adding applicabilities for Converged IP Communications	F	13.3.0	13.4.0	R5-174702
RP-77	RP-171679	0227	-	Addition of RFC reference in applicability spec for eCall over IMS Release 14	F	13.4.0	14.0.0	R5-173777
RP-77	RP-171684	0232	-	Update of PICS condition related to IMS emergency registration failure case in Rel-14	F	13.4.0	14.0.0	R5-174559
RP-77	RP-171679	0230	2	Add applicability for new eCall in IMS testcases	F	13.4.0	14.0.0	R5-174695
RP-78	RP-172217	0233	-	Add applicability for eCall over IMS test cases	F	14.0.0	14.1.0	R5-176061
RP-78	RP-172237	0234	-	Update to applicability of FBBA test case H.15.7	F	14.0.0	14.1.0	R5-176170
RP-78	RP-172197	0235	-	Handling remaining Editor's Note	F	14.0.0	14.1.0	R5-176225
RP-78	RP-172233	0236	1	Add PICS for audio feature tag	F	14.0.0	14.1.0	R5-176940
RP-78	RP-172233	0237	1	Corrections to PICS for video feature tag	F	14.0.0	14.1.0	R5-176941
RP-78	RP-172233	0238	1	Corrections to test case applicabilities	F	14.0.0	14.1.0	R5-176943
RP-78	RP-172237	0239	1	Correction of table A.6a	F	14.0.0	14.1.0	R5-176944
RP-79	RP-180089	0241	1	Correction of eCall over IMS test case applicability	F	14.1.0	14.2.0	R5-181195
RP-80	RP-180725	0245	-	Addition of applicability for new IMS test cases J.18.1 and J.18.2	F	14.2.0	14.3.0	R5-183108
RP-81	RP-181577	0246	-	Addition of IR.92 to SM-over-IP roles	F	14.3.0	14.4.0	R5-184048
RP-81	RP-181577	0247	1	Adding SMS over IP configuration to applicabilities	F	14.3.0	14.4.0	R5-185088
RP-82	RP-182283	0248	-	Clarifications on applicability of OIR and TIR	F	14.4.0	14.5.0	R5-186467
RP-82	RP-182283	0249	-	Addition of PICS Mnemonic for ECT	F	14.4.0	14.5.0	R5-187416
RP-83	RP-190091	0253	-	Addition of new applicability for MT MTSI speech call when MO reserves resources before sending INVITE	F	14.5.0	14.6.0	R5-191732

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-83	RP-190091	0250	1	Adding applicabilities for Session Timer test cases	F	14.5.0	14.6.0	R5-192324
RP-83	RP-190091	0251	1	Adding PICS for Session Timer	F	14.5.0	14.6.0	R5-192325
RP-83	RP-190095	0252	1	Addition of new applicability for user initiated USSI	F	14.5.0	14.6.0	R5-192326
RP-83	RP-190091	0254	1	Update to applicability condition of IMS test cases with precondition support	F	14.5.0	14.6.0	R5-192327
RP-83	RP-190092	0255	1	Change in applicability of test case 19.4.1 which does not require SIM	F	14.5.0	14.6.0	R5-192734
RP-84	RP-190887	0258	1	Corrections to preconditions applicabilities	F	14.6.0	14.7.0	R5-194828
RP-84	RP-190887	0259	1	Addition of applicability for new MO and MT voice call test cases tested without pre-conditions	F	14.6.0	14.7.0	R5-194831
RP-84	RP-190888	0256	1	Applicability update of condition C162	F	14.6.0	14.7.0	R5-194832
RP-84	RP-190868	0257	1	Adding 5G capabilities	F	14.7.0	15.0.0	R5-195232
RP-84	-	-	-	Fixing small omissions concerning R5-194828		15.0.0	15.0.1	-
RP-85	RP-191689	0262	-	Reference PICS from other specifications	F	15.0.1	15.1.0	R5-195897
RP-85	RP-191689	0265	-	Applicabilities for new IMS test cases	F	15.0.1	15.1.0	R5-196706
RP-85	RP-191704	0263	1	Addition of applicability for new MO test cases with 503 and 504 response tested without preconditions	F	15.0.1	15.1.0	R5-197045
RP-85	RP-191704	0264	1	Addition of new test applicability for IMS	F	15.0.1	15.1.0	R5-197046
RP-85	RP-191704	0261	1	Miscellaneous fixes to test case applicabilities	F	15.0.1	15.1.0	R5-197047
RP-86	RP-192484	0267	-	Corrections to applicabilities of IMS test cases H.12.2 and H.15.4	F	15.1.0	15.2.0	R5-197933
RP-86	RP-192480	0268	2	Adding a new test applicability for IMS	F	15.1.0	15.2.0	R5-199068
RP-88	RP-200593	0270	1	Update test applicability to reflect the change of test case title	F	15.2.0	15.3.0	R5-202533
RP-89	RP-201448	0271	1	Extending TS 34.229-2 to host applicabilities for 5GS IMS test cases	F	15.3.0	15.4.0	R5-204476
RP-90	RP-202248	0272	-	Voiding applicabilities of old unverified test cases	F	15.4.0	15.5.0	R5-205095
RP-90	RP-202221	0274	-	Update applicabilities for 5GS tests 7.5 and 7.7	F	15.4.0	15.5.0	R5-205555
RP-90	RP-202248	0277	-	Correction to applicability of test case 8.3	F	15.4.0	15.5.0	R5-205844
RP-90	RP-202221	0273	1	Corrections and additions of applicabilities for IMS over 5GS test cases	F	15.4.0	15.5.0	R5-206371
RP-91	RP-210131	0280	-	Adding NG.114 dependencies and PICS for test case 7.4	F	15.5.0	15.6.0	R5-210346
RP-91	RP-210131	0281	-	Applicability of 'Re-registration after capability update / 5GS' test case	F	15.5.0	15.6.0	R5-211299
RP-91	RP-210131	0278	1	Addition of applicabilities for new IMS over 5GS test cases	F	15.5.0	15.6.0	R5-211419
RP-91	RP-210131	0279	1	Corrections and extensions to applicability statements of IMS over 5GS test cases	F	15.5.0	15.6.0	R5-211420
RP-92	RP-210990	0282	1	Corrections for 5GS test cases	F	15.6.0	15.7.0	R5-213517
RP-92	RP-210990	0283	1	Adding applicability statements for new IMS 5GS test cases	F	15.6.0	15.7.0	R5-213518

Meeting -1st- Level	Doc-1st- Level	CR	Rev	Subject	Cat	Version - Current	Version -New	Doc-2nd- Level
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-92	RP-210990	0284	1	Correction to the applicability of IMS 5GS test case 7.4	F	15.6.0	15.7.0	R5-213519
RP-93	RP-211737	0292	-	Applicability updates to EIEI IMS test cases	F	15.7.0	15.8.0	R5-215119
RP-93	RP-211687	0287	1	Adding applicabilities for new IMS5GS test cases	F	15.7.0	15.8.0	R5-215719
RP-93	RP-211687	0288	1	Update NG.114 capabilities	F	15.7.0	15.8.0	R5-215720
RP-93	RP-211687	0286	1	Corrections to applicability statements of IMS over 5GS test cases	F	15.7.0	15.8.0	R5-216206
RP-93	RP-211687	0289	1	Add NG.114 PS data off	F	15.7.0	15.8.0	R5-216209
RP-93	RP-211727	0291	1	Applicability updates for NR EIEI test case 11.1	F	15.8.0	16.0.0	R5-216330
RP-94	RP-212751	0294	1	Additions and corrections of IMS5GS applicability statements	F	16.0.0	16.1.0	R5-217833
RP-94	RP-212751	0295	1	Add applicabilities for test cases 7.4a and 7.6a	F	16.0.0	16.1.0	R5-217834
RP-94	RP-212785	0297	1	Addition of applicability for NR EIEI test cases	F	16.0.0	16.1.0	R5-217948
RP-94	RP-212800	0298	1	Update to applicability of eCall over IMS test cases	F	16.0.0	16.1.0	R5-217961
RP-94	RP-212800	0299	1	Updates to IMS emergency call test cases	F	16.0.0	16.1.0	R5-217962
RP-95	RP-220071	0301	-	Update applicability for test case 7.4	F	16.1.0	16.2.0	R5-220185
RP-95	RP-220071	0303	-	Corrections for IMS5GS test cases	F	16.1.0	16.2.0	R5-220213
RP-95	RP-220071	0308	-	Updates to IMS security applicabilities	F	16.1.0	16.2.0	R5-221218
RP-95	RP-220071	0302	1	Add applicabilities for EVS B0 and A1	F	16.1.0	16.2.0	R5-221468
RP-95	RP-220071	0307	1	Update for IMS emergency service applicability	F	16.1.0	16.2.0	R5-221469
RP-95	RP-220106	0305	1	Update to applicability of NR EIEI test cases	F	16.1.0	16.2.0	R5-222045
RP-96	RP-221114	0312	-	Updates to IMS test case applicabilities	F	16.2.0	16.3.0	R5-223078
RP-96	RP-221114	0310	1	Corrections and amendments of IMS5GS applicability statements	F	16.2.0	16.3.0	R5-223498
RP-97	RP-221997	0315	-	Correction to 5G IMS applicability C19	F	16.3.0	16.4.0	R5-225190
RP-97	RP-221997	0313	1	Update of applicability for 5GC test case 7.14 and 7.20	F	16.3.0	16.4.0	R5-225422
RP-98	RP-222791	0317	-	Correction to Applicability of TS 34.229-5 tests	F	16.4.0	16.5.0	R5-226311
RP-99	RP-230246	0318	-	Remove applicability clauses for test case 10.11 and 10.15	F	16.5.0	16.6.0	R5-230923
RP-100	RP-230973	0323	-	Updates to applicability for Supplementary Services test cases	F	16.6.0	16.7.0	R5-232769
RP-100	RP-230973	0319	1	Remove test case 7.4	F	16.6.0	16.7.0	R5-233374
RP-100	RP-230973	0320	1	Remove test case 7.6	F	16.6.0	16.7.0	R5-233375
RP-100	RP-230973	0321	1	Update applicabilities for NG.114 default test cases	F	16.6.0	16.7.0	R5-233485
RP-101	RP-231690	0328	-	Updates to IMS test case applicabilities	F	16.7.0	16.8.0	R5-235095
RP-101	RP-231688	0324	1	Correction of clause 4	F	16.7.0	16.8.0	R5-235317
RP-101	RP-231690	0327	1	Editorial updates to 34.229-2 tables	F	16.7.0	16.8.0	R5-235325
RP-101	RP-231690	0329	-	Update of applicability for IMS Test Cases	F	16.7.0	16.8.0	R5-235447

Meeting -1st-	Doc-1st- Level	CR	Rev	Subject	Cat	Version -	Version -New	Doc-2nd- Level
Level						Current		
RP-31	RP-060053	-	-	Update to version 1.0.0 and present to RAN#31 for information	-	0.0.1	1.0.0	R5-060523
RP-102	RP-232839	0330	-	Update of applicability of TC 8.39 and 8.39a	F	16.8.0	16.9.0	R5-236191
RP-102	RP-232837	0331	-	Correction of annex A	F	16.8.0	16.9.0	R5-236318
RP-102	RP-232837	0332	-	Correction of clause 4	F	16.8.0	16.9.0	R5-236319
RP-102	RP-232839	0335	-	Update applicabilities for Call Control test cases	F	16.8.0	16.9.0	R5-236893
RP-102	RP-232839	0333	1	Update applicabilities for test cases 7.1-2	F	16.8.0	16.9.0	R5-237388
RP-103	RP-240224	0336	-	Correction of clause 4	F	16.9.0	16.10.0	R5-240552
RP-103	RP-240187	0337	1	Updating applicability for RedCap	F	16.10.0	17.0.0	R5-241578
RP-103	RP-240224	0339	-	Updating applicability for video	F	16.10.0	17.0.0	R5-241579
RP-104	RP-241023	0341	2	Applicability for new test cases 12.23a and 12.24a	F	17.0.0	17.1.0	R5-243986

History

	Document history						
V17.0.0	May 2024	Publication					
V17.1.0	August 2024	Publication					